

MLT : Week 9

Perceptron & Logistic Regression

Vivek Sivaramakrishnan

The weight vector for two consecutive iterations of a perceptron model are given below:

The weight vector for two consecutive iterations of a perceptron model are given below:

$$\mathbf{w}^t = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix}, \mathbf{w}^{t+1} = \begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix}$$

The weight vector for two consecutive iterations of a perceptron model are given below:

$$\mathbf{w}^t = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix}, \mathbf{w}^{t+1} = \begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix}$$

Find all possible datapoints (along with its true label) that could've been used for the update from \mathbf{w}^t to \mathbf{w}^{t+1} .

Recall the update rule for the Perceptron Learning Algorithm:

if mistake:

$$\mathbf{w}^{t+1} = \mathbf{w}^t + y_i \mathbf{x}_i$$

Recall the update rule for the Perceptron Learning Algorithm:

if mistake:

$$\mathbf{w}^{t+1} = \mathbf{w}^t + y_i \mathbf{x}_i$$

Substituting $\mathbf{w}^t = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix}$, $\mathbf{w}^{t+1} = \begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix}$ from the question, we get:

Recall the update rule for the Perceptron Learning Algorithm:

if mistake:

$$\mathbf{w}^{t+1} = \mathbf{w}^t + y_i \mathbf{x}_i$$

Substituting $\mathbf{w}^t = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix}$, $\mathbf{w}^{t+1} = \begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix}$ from the question, we get:

$$\begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix} = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix} + y_i \mathbf{x}_i$$

Recall the update rule for the Perceptron Learning Algorithm:

if mistake:

$$\mathbf{w}^{t+1} = \mathbf{w}^t + y_i \mathbf{x}_i$$

Substituting $\mathbf{w}^t = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix}$, $\mathbf{w}^{t+1} = \begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix}$ from the question, we get:

$$\begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix} = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix} + y_i \mathbf{x}_i$$

$$\implies y_i \mathbf{x}_i = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix} - \begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix}$$

Recall the update rule for the Perceptron Learning Algorithm:

if mistake:

$$\mathbf{w}^{t+1} = \mathbf{w}^t + y_i \mathbf{x}_i$$

Substituting $\mathbf{w}^t = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix}$, $\mathbf{w}^{t+1} = \begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix}$ from the question, we get:

$$\begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix} = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix} + y_i \mathbf{x}_i$$

$$\implies y_i \mathbf{x}_i = \begin{bmatrix} 1 \\ 1 \\ -2 \end{bmatrix}$$

Recall the update rule for the Perceptron Learning Algorithm:

if mistake:

$$\mathbf{w}^{t+1} = \mathbf{w}^t + y_i \mathbf{x}_i$$

Substituting $\mathbf{w}^t = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix}$, $\mathbf{w}^{t+1} = \begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix}$ from the question, we get:

$$\begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix} = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix} + y_i \mathbf{x}_i$$

$$\implies y_i \mathbf{x}_i = \begin{bmatrix} 1 \\ 1 \\ -2 \end{bmatrix}$$

Case 1: $y_i = 1$

Case 2: $y_i = -1$

Recall the update rule for the Perceptron Learning Algorithm:

if mistake:

$$\mathbf{w}^{t+1} = \mathbf{w}^t + y_i \mathbf{x}_i$$

Substituting $\mathbf{w}^t = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix}$, $\mathbf{w}^{t+1} = \begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix}$ from the question, we get:

$$\begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix} = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix} + y_i \mathbf{x}_i$$

$$\Rightarrow y_i \mathbf{x}_i = \begin{bmatrix} 1 \\ 1 \\ -2 \end{bmatrix}$$

Case 1: $y_i = 1$

$$\Rightarrow \mathbf{x}_i = \begin{bmatrix} 1 \\ 1 \\ -2 \end{bmatrix}$$

Case 2: $y_i = -1$

Recall the update rule for the Perceptron Learning Algorithm:

if mistake:

$$\mathbf{w}^{t+1} = \mathbf{w}^t + y_i \mathbf{x}_i$$

Substituting $\mathbf{w}^t = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix}$, $\mathbf{w}^{t+1} = \begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix}$ from the question, we get:

$$\begin{bmatrix} 0 \\ 2 \\ 1 \end{bmatrix} = \begin{bmatrix} 1 \\ 3 \\ -1 \end{bmatrix} + y_i \mathbf{x}_i$$

$$\Rightarrow y_i \mathbf{x}_i = \begin{bmatrix} 1 \\ 1 \\ -2 \end{bmatrix}$$

Case 1: $y_i = 1$

$$\Rightarrow \mathbf{x}_i = \begin{bmatrix} 1 \\ 1 \\ -2 \end{bmatrix}$$

Case 2: $y_i = -1$

$$\Rightarrow \mathbf{x}_i = - \begin{bmatrix} 1 \\ 1 \\ -2 \end{bmatrix} = \begin{bmatrix} -1 \\ -1 \\ 2 \end{bmatrix}$$

Consider a linearly separable binary classification data set with 1000 data points and 100 features.

Consider a linearly separable binary classification data set with 1000 data points and 100 features.
Assume that there exists a \mathbf{w} such that

Consider a linearly separable binary classification data set with 1000 data points and 100 features.
Assume that there exists a \mathbf{w} such that

$$\|\mathbf{w}\| = 1, \quad y_i(\mathbf{w}^t \mathbf{x}_i) \geq 0.2 \quad \forall i$$

Consider a linearly separable binary classification data set with 1000 data points and 100 features.

Assume that there exists a \mathbf{w} such that

$$\|\mathbf{w}\| = 1, \quad y_i(\mathbf{w}^t \mathbf{x}_i) \geq 0.2 \quad \forall i$$


Also assume that $\|\mathbf{x}\|_2 \leq 1 \quad \forall i$.

Consider a linearly separable binary classification data set with 1000 data points and 100 features. Assume that there exists a \mathbf{w} such that

$$\|\mathbf{w}\| = 1, y_i(\mathbf{w}^t \mathbf{x}_i) \geq 0.2 \quad \forall i$$

Also assume that $\|\mathbf{x}\|_2 \leq 1 \quad \forall i$. What is the maximum number of mistakes that Perceptron algorithm can make on this dataset?

Consider a linearly separable binary classification data set with 1000 data points and 100 features.
Assume that there exists a \mathbf{w} such that


$$\|\mathbf{w}\| = 1, y_i(\mathbf{w}^t \mathbf{x}_i) \geq 0.2 \quad \forall i$$


Margin γ


Also assume that $\|\mathbf{x}\|_2 \leq 1 \quad \forall i$. What is the maximum number of mistakes that Perceptron algorithm can make on this dataset?

Consider a linearly separable binary classification data set with 1000 data points and 100 features.

Assume that there exists a \mathbf{w} such that


$$\|\mathbf{w}\| = 1, y_i(\mathbf{w}^t \mathbf{x}_i) \geq 0.2 \quad \forall i$$


Margin γ


Also assume that $\|\mathbf{x}\|_2 \leq 1 \quad \forall i$. What is the maximum number of mistakes that Perceptron algorithm can make on this dataset?  Radius R

Consider a linearly separable binary classification data set with 1000 data points and 100 features.

Assume that there exists a \mathbf{w} such that

$$\|\mathbf{w}\| = 1, y_i(\mathbf{w}^t \mathbf{x}_i) \geq 0.2 \quad \forall i$$


Margin γ

Also assume that $\|\mathbf{x}\|_2 \leq 1 \quad \forall i$. What is the maximum number of mistakes that Perceptron algorithm can make on this dataset?  Radius R


Recall the Radius-Margin Bound:

Consider a linearly separable binary classification data set with 1000 data points and 100 features.

Assume that there exists a \mathbf{w} such that


$$\|\mathbf{w}\| = 1, y_i(\mathbf{w}^t \mathbf{x}_i) \geq 0.2 \quad \forall i$$

Margin γ



Also assume that $\|\mathbf{x}\|_2 \leq 1 \quad \forall i$. What is the maximum number of mistakes that Perceptron algorithm can make on this dataset?

Radius R



Recall the Radius-Margin Bound:


$$\# \text{mistakes} \leq \frac{R^2}{\gamma^2}$$

Consider a linearly separable binary classification data set with 1000 data points and 100 features.

Assume that there exists a \mathbf{w} such that


$$\|\mathbf{w}\| = 1, y_i(\mathbf{w}^t \mathbf{x}_i) \geq 0.2 \quad \forall i$$

Margin γ



Also assume that $\|\mathbf{x}\|_2 \leq 1 \quad \forall i$. What is the maximum number of mistakes that Perceptron algorithm can make on this dataset?

Radius R



Recall the Radius-Margin Bound:


$$\begin{aligned} \# \text{mistakes} &\leq \frac{R^2}{\gamma^2} \\ &\leq \frac{1^2}{0.2^2} \end{aligned}$$

Consider a linearly separable binary classification data set with 1000 data points and 100 features.

Assume that there exists a \mathbf{w} such that


$$\|\mathbf{w}\| = 1, y_i(\mathbf{w}^t \mathbf{x}_i) \geq 0.2 \quad \forall i$$

Margin γ



Also assume that $\|\mathbf{x}\|_2 \leq 1 \quad \forall i$. What is the maximum number of mistakes that Perceptron algorithm can make on this dataset?


Radius R



Recall the Radius-Margin Bound:


$$\begin{aligned} \# \text{mistakes} &\leq \frac{R^2}{\gamma^2} \\ &\leq 25 \end{aligned}$$

Consider a logistic regression model that has been trained for a binary classification problem on a dataset in \mathbb{R}^2 . two data-points from the training set: (\mathbf{x}_1, y_1) and (\mathbf{x}_2, y_2) . The models' weight vector and these two data-points (along with their labels) are drawn in the diagram given below. The symbol $+$ corresponds to label 1 and $-$ corresponds to label 0.




Consider a logistic regression model that has been trained for a binary classification problem on a dataset in \mathbb{R}^2 . two data-points from the training set: (\mathbf{x}_1, y_1) and (\mathbf{x}_2, y_2) . The models' weight vector and these two data-points (along with their labels) are drawn in the diagram given below. The symbol $+$ corresponds to label 1 and $-$ corresponds to label 0.

Let σ_1, σ_2 be the probabilities output by the model for the two data-points.



Consider a logistic regression model that has been trained for a binary classification problem on a dataset in \mathbb{R}^2 . two data-points from the training set: (\mathbf{x}_1, y_1) and (\mathbf{x}_2, y_2) . The models' weight vector and these two data-points (along with their labels) are drawn in the diagram given below. The symbol $+$ corresponds to label 1 and $-$ corresponds to label 0.


Let σ_1, σ_2 be the probabilities output by the model for the two data-points. Compute the following quantity: $\frac{|\sigma_1 - y_1|}{|\sigma_2 - y_2|}$



Consider a logistic regression model that has been trained for a binary classification problem on a dataset in \mathbb{R}^2 . two data-points from the training set: (\mathbf{x}_1, y_1) and (\mathbf{x}_2, y_2) . The models' weight vector and these two data-points (along with their labels) are drawn in the diagram given below. The symbol $+$ corresponds to label 1 and $-$ corresponds to label 0.

Let σ_1, σ_2 be the probabilities output by the model for the two data-points. Compute the following quantity: $\frac{|\sigma_1 - y_1|}{|\sigma_2 - y_2|}$

Recall that the $\sigma_1 = \sigma(\mathbf{w}^T \mathbf{x}_1) = \frac{1}{1 + e^{-\mathbf{w}^T \mathbf{x}_1}}$
(sigmoid function)



It's worth to prove the following result before proceeding with the question:

$$\sigma(a) = 1 - \sigma(-a)$$

It's worth to prove the following result before proceeding with the question:

$$\sigma(a) = 1 - \sigma(-a)$$

Proof is straightforward; just evaluate the right hand side:

$$1 - \sigma(-a) = 1 - \frac{1}{1 + e^{-(-a)}}$$

It's worth to prove the following result before proceeding with the question:

$$\sigma(a) = 1 - \sigma(-a)$$

Proof is straightforward; just evaluate the right hand side:

$$\begin{aligned} 1 - \sigma(-a) &= 1 - \frac{1}{1 + e^{-(-a)}} \\ &= 1 - \frac{1}{1 + e^a} \end{aligned}$$

It's worth to prove the following result before proceeding with the question:

$$\sigma(a) = 1 - \sigma(-a)$$

Proof is straightforward; just evaluate the right hand side:

$$\begin{aligned} 1 - \sigma(-a) &= 1 - \frac{1}{1 + e^{-(-a)}} \\ &= 1 - \frac{1}{1 + e^a} \\ &= \frac{1 + e^a}{1 + e^a} - \frac{1}{1 + e^a} \end{aligned}$$

It's worth to prove the following result before proceeding with the question:

$$\sigma(a) = 1 - \sigma(-a)$$

Proof is straightforward; just evaluate the right hand side:

$$\begin{aligned} 1 - \sigma(-a) &= 1 - \frac{1}{1 + e^{-(-a)}} \\ &= 1 - \frac{1}{1 + e^a} \\ &= \frac{1 + e^a}{1 + e^a} - \frac{1}{1 + e^a} \\ &= \frac{e^a}{1 + e^a} \end{aligned}$$

It's worth to prove the following result before proceeding with the question:

$$\sigma(a) = 1 - \sigma(-a)$$


Proof is straightforward; just evaluate the right hand side:

$$\begin{aligned} 1 - \sigma(-a) &= 1 - \frac{1}{1 + e^{-(-a)}} \\ &= 1 - \frac{1}{1 + e^a} \\ &= \frac{1 + e^a}{1 + e^a} - \frac{1}{1 + e^a} \\ &= \frac{e^a}{1 + e^a} = \frac{1}{1 + e^{-a}} = \sigma(a) \end{aligned}$$

We begin with the question. We will first compute

$$\mathbf{w}^T \mathbf{x}_1 =$$


$$\mathbf{w}^T \mathbf{x}_2 =$$



We begin with the question. We will first compute

$$\mathbf{w}^T \mathbf{x}_1 = \begin{bmatrix} 1 \\ 1 \end{bmatrix}^T \begin{bmatrix} 2 \\ 2 \end{bmatrix}$$


$$\mathbf{w}^T \mathbf{x}_2 = \begin{bmatrix} 1 \\ 1 \end{bmatrix}^T \begin{bmatrix} -2 \\ -2 \end{bmatrix}$$



We begin with the question. We will first compute

$$\mathbf{w}^T \mathbf{x}_1 = \begin{bmatrix} 1 \\ 1 \end{bmatrix}^T \begin{bmatrix} 2 \\ 2 \end{bmatrix} = 2 + 2 = 4$$

$$\mathbf{w}^T \mathbf{x}_2 = \begin{bmatrix} 1 \\ 1 \end{bmatrix}^T \begin{bmatrix} -2 \\ -2 \end{bmatrix} = -2 - 2 = -4$$




We begin with the question. We will first compute

$$\mathbf{w}^T \mathbf{x}_1 = \begin{bmatrix} 1 \\ 1 \end{bmatrix}^T \begin{bmatrix} 2 \\ 2 \end{bmatrix} = 2 + 2 = 4$$

$$\mathbf{w}^T \mathbf{x}_2 = \begin{bmatrix} 1 \\ 1 \end{bmatrix}^T \begin{bmatrix} -2 \\ -2 \end{bmatrix} = -2 - 2 = -4$$

Note that $\mathbf{w}^T \mathbf{x}_1 = -\mathbf{w}^T \mathbf{x}_2$



We begin with the question. We will first compute

$$\mathbf{w}^T \mathbf{x}_1 = \begin{bmatrix} 1 \\ 1 \end{bmatrix}^T \begin{bmatrix} 2 \\ 2 \end{bmatrix} = 2 + 2 = 4$$


$$\mathbf{w}^T \mathbf{x}_2 = \begin{bmatrix} 1 \\ 1 \end{bmatrix}^T \begin{bmatrix} -2 \\ -2 \end{bmatrix} = -2 - 2 = -4$$

Note that $\mathbf{w}^T \mathbf{x}_1 = -\mathbf{w}^T \mathbf{x}_2$

$$\Rightarrow \boxed{\sigma_2 = 1 - \sigma_1}$$

$$\begin{aligned} \sigma_1 &= \sigma(\mathbf{w}^T \mathbf{x}_1), \\ \sigma_2 &= \sigma(\mathbf{w}^T \mathbf{x}_2) \end{aligned}$$

Also note $y_1 = 0, y_2 = +1$



We begin with the question. We will first compute

$$\mathbf{w}^T \mathbf{x}_1 = \begin{bmatrix} 1 \\ 1 \end{bmatrix}^T \begin{bmatrix} 2 \\ 2 \end{bmatrix} = 2 + 2 = 4$$


$$\mathbf{w}^T \mathbf{x}_2 = \begin{bmatrix} 1 \\ 1 \end{bmatrix}^T \begin{bmatrix} -2 \\ -2 \end{bmatrix} = -2 - 2 = -4$$

Note that $\mathbf{w}^T \mathbf{x}_1 = -\mathbf{w}^T \mathbf{x}_2$

$$\Rightarrow \boxed{\sigma_2 = 1 - \sigma_1}$$

Also note $y_1 = 0, y_2 = +1$


We are now ready to compute $\frac{|\sigma_1 - y_1|}{|\sigma_2 - y_2|}$



$$\sigma_2 = 1 - \sigma_1$$

$$y_1 = 0, y_2 = +1$$


$$\frac{|\sigma_1 - y_1|}{|\sigma_2 - y_2|}$$



$$\sigma_2 = 1 - \sigma_1$$

$$y_1 = 0, \quad y_2 = +1$$


$$\frac{|\sigma_1 - y_1|}{|\sigma_2 - y_2|} = \frac{|\sigma_1 - 0|}{|1 - \sigma_1 - 1|}$$



$$\sigma_2 = 1 - \sigma_1$$

$$y_1 = 0, \quad y_2 = +1$$

$$\frac{|\sigma_1 - y_1|}{|\sigma_2 - y_2|} = \frac{|\sigma_1 - 0|}{|1 - \sigma_1 - 1|} = \frac{|\sigma_1|}{|-\sigma_1|}$$



$$\sigma_2 = 1 - \sigma_1$$

$$y_1 = 0, y_2 = +1$$

$$\frac{|\sigma_1 - y_1|}{|\sigma_2 - y_2|} = \frac{|\sigma_1 - 0|}{|1 - \sigma_1 - 1|} = \frac{|\sigma_1|}{|-\sigma_1|} = 1$$

Note that this did not require an explicit computation of the output of the logistic function.

