Notes on Machine Learning for Kira IBP Reduction

Seed selection, elimination ordering and equation selection

October 12, 2026

Abstract

Feynman integral calculations are an important component of multiloop amplitude calculations in quantum field theory. In Quantum Chromodynamics (QCD), multiloop amplitudes and their associated Feynman integrals arise in higher-order perturbative calculations and can become increasingly complex at higher loop orders. Recent progress has automated these calculations to some extent using the framework Kira, which organizes target integrals into integral families and sectors, generate algebraic relations among the integrals by using integration by parts (IBP) identities, and reduce the resulting system to expressions in terms of a finite set of master integrals. We aim to explore the application of machine learning models to accelerate the IBP reduction process by investigating if learned models can improve seed selection. These models can predict the most useful integrals from which to generate IBP relations while minimizing redundant calculations. We will also explore machine learning models for learning efficient reduction and elimination sequences to minimize the number of algebraic operations required to express target integrals in terms of master integrals. Because the machine learning models will serve as decision-makers while the underlying IBP reduction and verification remain exact, these models can improve computational efficiency without compromising the correctness of the resulting reductions.

1 Introduction

Feynman integrals arise in higher-order perturbative corrections to scattering amplitudes and particle decay amplitudes. In QCD, these corrections involve quark and gluon loops and contribute to predictions for cross sections and decay rates. Calculating a loop contribution requires integration over the independent internal momenta that remain after imposing momentum conservation [1].

The scalar integrals that appear in an amplitude have the general form

$$\mathcal{J} = \left(\prod_{k=1}^{L} \int \frac{\mathrm{d}^d \ell_k}{\mathrm{i}\pi^{d/2}}\right) \frac{\mathcal{N}(\boldsymbol{\ell}, \boldsymbol{p})}{\prod_{i=1}^{n_{\mathrm{phys}}} D_i^{a_i}}, \qquad D_i = q_i^2 - m_i^2 + \mathrm{i}0. \tag{1}$$

Here L is the number of loops and $\boldsymbol{\ell} = (\ell_1, \ldots, \ell_L)$ is the list of independent loop momenta over which we integrate. The number of independent external momenta is E, and we keep these momenta, $\boldsymbol{p} = (p_1, \ldots, p_E)$, fixed during integration. The numerator $\mathcal{N}$ is a polynomial obtained from the spin and tensor algebra; we leave its mass dependence implicit in the notation. The number of physical denominators is n_{phys}, and each D_i corresponds to an internal particle line with momentum q_i and mass m_i. The positive integer a_i is the power of D_i in the denominator, and q_i is a fixed linear combination of loop and external momenta, with $q_i^2 = q_i \cdot q_i$ denoting the Lorentz scalar product.

The integration dimension is $d = 4 - 2\epsilon$, where ϵ is the regulator used to define divergent integrals, so the result depends on ϵ as well as the external momenta and masses. The factor $1/(\mathrm{i}\pi^{d/2})$ is our normalization convention for each integration measure, with $\mathrm{i}^2 = -1$. In each denominator, i0 is an infinitesimal positive imaginary term that specifies how to integrate past a propagator pole, where $q_i^2 = m_i^2$.

Higher loop orders produce collections of integrals with related numerators and denominators and algebraic identities can be used to express them in terms of an independent set of master integrals. Kira automates this reduction [2], after which the calculation requires the values of the master integrals. To explain how the reduction works and where machine learning (ML) could speed it up, we first define the notation used in this paper, then derive the identities and describe how Kira solves the resulting equations.

2 The mathematical form of Feynman integrals

To label the integrals related to Eq. (1), we specify their momentum dependence and write the numerator and denominator powers as a vector of integers. This vector identifies each integral as an unknown in the reduction equations.

2.1 Loop momenta, propagators and regularization

After choosing how the loop and external momenta flow through the internal lines, we write each physical denominator as

$$D_i = q_i^2 - m_i^2 + \mathrm{i}0, \qquad q_i = \sum_{k=1}^{L} \alpha_{ik} \ell_k + \sum_{\beta=1}^{E} \eta_{i\beta} p_\beta. \tag{2}$$

The constants α_{ik} and $\eta_{i\beta}$ specify which loop and external momenta make up q_i, with indices k, j for loop momenta and β, γ for external momenta. Squaring q_i gives the scalar products $\ell_k \cdot \ell_j$, $\ell_k \cdot p_\beta$ and $p_\beta \cdot p_\gamma$, and those containing loop momenta vary during integration. The

vector $\boldsymbol{x}$ contains the independent external scalar products and squared masses, which are the kinematic parameters we keep fixed during integration.

Loop integrals can diverge at large momenta or when massless momenta become small or parallel. Dimensional regularization defines these integrals at values of d for which they converge and extends the result by analytic continuation to $d = 4 - 2\epsilon$, using additional regulators where necessary. In an expansion around $\epsilon = 0$, the divergences appear as negative powers of ϵ, which renormalization and infrared cancellation in the observable address later in the calculation [1]. Having specified the regulated measure and momentum dependence, we can now use the powers of the numerator and denominator factors to label individual integrals.

2.2 A common notation for an integral family

We add auxiliary expressions to the physical denominators so that we can write every required loop-momentum scalar product in terms of the list $D_1, \ldots, D_N$ and the fixed parameters $\boldsymbol{x}$. Here N is the number of expressions in the list, and the auxiliary expressions allow us to represent numerator factors. Writing the numerator in terms of this list expresses $\mathcal{J}$ as a linear combination of integrals of the form

$$I_{\boldsymbol{a}}(\boldsymbol{x}, \epsilon) = \int_\ell \prod_{i=1}^{N} D_i^{-a_i}, \qquad \int_\ell \equiv \prod_{k=1}^{L} \int \frac{\mathrm{d}^d \ell_k}{\mathrm{i}\pi^{d/2}}, \qquad \boldsymbol{a} = (a_1, \ldots, a_N) \in \mathbb{Z}^N. \tag{3}$$

Here $\int_\ell$ is shorthand for the loop integration measure and $\boldsymbol{a}$ is the vector of N integer powers, with $\mathbb{Z}$ denoting the set of integers. These powers can be positive, zero or negative, so we can write numerator and denominator factors in the equivalent form

$$I_{\boldsymbol{a}}(\boldsymbol{x}, \epsilon) = \int_\ell \frac{\prod_{i:a_i<0} D_i^{-a_i}}{\prod_{i:a_i>0} D_i^{a_i}}. \tag{4}$$

A positive index places $D_i^{a_i}$ in the denominator, a negative index places $D_i^{-a_i}$ in the numerator, and a zero index removes the factor, with an empty product equal to one. Auxiliary expressions used only as numerators therefore have nonpositive indices. An irreducible scalar product is a numerator scalar product that cannot be written as a linear combination of the physical denominators and terms depending only on $\boldsymbol{x}$ [3].

An integral family contains the integrals obtained by varying $\boldsymbol{a}$ for a fixed list $D_1, \ldots, D_N$ and fixed kinematics. Within this family, the target list specifies the integrals that the amplitude requires, and grouping family members by their positive indices organizes them into sectors.

2.3 Sectors and the organization of related integrals

A sector is a set of integrals with the same positive-index positions, so they contain the same denominators. We assign a label to each sector using

$$\theta_i(\boldsymbol{a}) = \begin{cases} 1, & a_i > 0, \\ 0, & a_i \leq 0, \end{cases} \qquad S(\boldsymbol{a}) = \sum_{i=1}^{N} 2^{i-1} \theta_i(\boldsymbol{a}). \tag{5}$$

The indicator θ_i is one when denominator i is present and zero otherwise, and S is an integer that identifies this set of denominators. Integrals with different powers of the same denominators belong to the same sector because S depends only on which indices are positive. Removing one or more denominators gives a subsector containing a proper subset of the original sector's denominators.

Scaleless sectors contain no nonzero mass or kinematic scale and therefore vanish in dimensional regularization, while changes of loop integration variables can yield symmetry relations between integrals. Kira uses these zero sectors and symmetry mappings to reduce the number of unknowns [2]. We can then use the sector and index labels to write the identities that relate the remaining family members.

3 From integration to algebraic reduction

To express the targets in terms of master integrals, we generate relations between family members through integration by parts and solve the resulting equations. Evaluating the master integrals then gives the target integral values needed to calculate the amplitude.

3.1 How integration by parts produces relations

For differentiable functions $f(z)$ and $g(z)$ of a real variable z, the product rule gives the integration identity between endpoints z_0, z_1:

$$\int_{z_0}^{z_1} f'(z)g(z)\,\mathrm{d}z = [f(z)g(z)]_{z_0}^{z_1} - \int_{z_0}^{z_1} f(z)g'(z)\,\mathrm{d}z. \tag{6}$$

Primes denote derivatives with respect to z, and the brackets denote the endpoint difference $f(z_1)g(z_1) - f(z_0)g(z_0)$. To apply this product rule to loop-momentum derivatives, we derive the integration-by-parts (IBP) identity where the regulated integral has a vanishing boundary term and then extend it by analytic continuation [4, 3]. For a loop momentum ℓ_k and a vector $v \in \{\ell_1, \ldots, \ell_L, p_1, \ldots, p_E\}$, the identity is

$$0 = \int_\ell \frac{\partial}{\partial \ell_k^\mu} \left(v^\mu \prod_{i=1}^{N} D_i^{-a_i} \right). \tag{7}$$

The index μ is a spacetime index, and a repeated Lorentz index means that we sum over components using the spacetime metric. The derivative acts on both v^μ and the factors $D_i^{-a_i}$, so the product rule gives

$$0 = \int_\ell \left[\frac{\partial v^\mu}{\partial \ell_k^\mu} - \sum_{i=1}^{N} a_i \frac{v^\mu (\partial D_i / \partial \ell_k^\mu)}{D_i} \right] \prod_{j=1}^{N} D_j^{-a_j}. \tag{8}$$

The first term equals d for $v = \ell_k$ and vanishes when v is an external momentum or another independent loop momentum. Differentiating an inverse propagator produces scalar products, which we express through the family basis to convert each term into an integral with shifted indices:

$$\sum_{j=1}^{n_\lambda} c_{\lambda j}(\boldsymbol{a}; \boldsymbol{x}, \epsilon) I_{\boldsymbol{a}+\boldsymbol{\Delta}_{\lambda j}}(\boldsymbol{x}, \epsilon) = 0. \tag{9}$$

Here λ identifies the chosen pair (k, v), n_λ is the number of terms, and $\boldsymbol{\Delta}_{\lambda j}$ is the integer change in the index vector for term j. Differentiation gives the coefficient $c_{\lambda j}$, which depends on the integral indices and the parameters $\boldsymbol{x}, \epsilon$ [4].

The L choices of differentiated momentum and $L+E$ choices of v give $L(L+E)$ basic identities at each index vector, some of which may depend linearly on the others. Further relations follow from Lorentz invariance because a common rotation or Lorentz boost of all external momenta preserves a scalar integral, giving the infinitesimal identity

$$\sum_{\beta=1}^{E} \left(p_\beta^\nu \frac{\partial}{\partial p_{\beta\mu}} - p_\beta^\mu \frac{\partial}{\partial p_{\beta\nu}} \right) I_{\boldsymbol{a}} = 0. \tag{10}$$

Here μ, ν are free spacetime indices, meaning that the identity holds for each pair of components, and the derivatives act on the external-momentum dependence of the integral. Contracting these indices with external momenta gives scalar relations [5] that join the IBP and symmetry identities to form the reduction system.

3.2 From relations to master integrals

Let n_I be the number of distinct integrals in the generated equations and n_{eq} the number of equations. We arrange these integrals in a column vector so that the system takes the matrix form

$$A(\boldsymbol{x}, \epsilon)\, \boldsymbol{I} = 0, \qquad \boldsymbol{I} = (I_{\boldsymbol{a}^{(1)}}, \ldots, I_{\boldsymbol{a}^{(n_I)}})^{\mathsf{T}}. \tag{11}$$

The superscript T denotes transpose, so $\boldsymbol{I}$ is a column vector of integrals whose dependence on $\boldsymbol{x}, \epsilon$ we leave implicit here. The matrix A has n_{eq} rows and n_I columns, with each entry A_{ij} giving the coefficient of integral j in equation i. Solving this system expresses dependent integrals in terms of an independent set. This set is a master basis if the reduction relations express every required integral as a linear combination of its members. For the standard class of Feynman integrals at fixed graph, this basis contains a finite number of masters [6]. We write them as $M_1, \ldots, M_{n_M}$, where n_M is the number of master integrals, so the reduction formula is

$$I_{\boldsymbol{a}}(\boldsymbol{x}, \epsilon) = \sum_{m=1}^{n_M} C_{\boldsymbol{a}m}(\boldsymbol{x}, \epsilon) M_m(\boldsymbol{x}, \epsilon). \tag{12}$$

Here $C_{\boldsymbol{a}m}$ is the coefficient of master M_m in the reduction of target $I_{\boldsymbol{a}}$. The solver obtains it by adding, multiplying and dividing the identity coefficients, so it is a rational function, meaning a ratio of polynomials in $\boldsymbol{x}, \epsilon$. Different independent sets can define different master bases, and an insufficient equation set can leave additional integrals unresolved. Establishing the master basis therefore requires checking that the generated equations are enough to reduce the required integrals.

Equation (12) gives the coefficients multiplying the masters, whose evaluation requires a further calculation, for example by solving differential equations with known values or limits as boundary conditions [5]. Kira provides the reduction rules needed for this calculation by generating and processing the identities through the procedure described next.

4 How Kira performs the reduction

Kira implements the Laporta approach by generating a finite set of identities and eliminating integrals according to an ordering [7]. To obtain the coefficients in Eq. (12), Kira selects seeds, removes redundant equations and solves the retained system. We examine how Kira performs these steps to specify the seed and elimination choices that the proposed models would make.

4.1 Kira's input and seed generation

The user supplies the families in Eq. (3), relations among the parameters $\boldsymbol{x}$, the target list, and bounds on equation generation so that Kira can initialize the families and sectors. During this initialization, Kira detects scaleless sectors and identifies symmetry relations and mappings between compatible families [2].

A seed specifies the index vector $\boldsymbol{a}$ at which Kira evaluates Eq. (9) to generate several derivative identities, and the seed set may include integrals beyond the target list. The shifts $\boldsymbol{\Delta}_{\lambda j}$ in these

identities can introduce further integrals outside the seed set, so the resulting system depends on both the chosen seeds and the terms generated from them. To set limits on the indices of the seeds, Kira uses the quantities

$$t(\boldsymbol{a}) = \sum_{i=1}^{N} \theta_i(\boldsymbol{a}), \qquad r(\boldsymbol{a}) = \sum_{a_i>0} a_i, \tag{13}$$

$$s(\boldsymbol{a}) = -\sum_{a_i<0} a_i, \qquad n_{\mathrm{dot}}(\boldsymbol{a}) = r(\boldsymbol{a}) - t(\boldsymbol{a}). \tag{14}$$

Here t is the number of distinct denominators, r is the sum of their powers, and s is the sum of the numerator powers. The quantity n_{dot} is the sum of the extra denominator powers beyond one for each denominator. We use this symbol to keep d reserved for the integration dimension, and we restrict equation generation by specifying the allowed sectors and limits

$$r \le r_{\max}, \qquad s \le s_{\max}, \qquad n_{\mathrm{dot}} \le n_{\mathrm{dot,max}}, \tag{15}$$

where $r_{\max}$, $s_{\max}$ and $n_{\mathrm{dot,max}}$ are the upper limits on the corresponding quantities. The user sets $r_{\max}$ and $s_{\max}$ and may also set $n_{\mathrm{dot,max}}$. Because these choices determine which seeds contribute equations, a reduction run must establish whether the bounds supply enough relations for the targets [8].

Kira 3 changes seeding in symmetry-related sectors and provides the optional `truncate_sp` setting to restrict numerator seeding in subsectors, with parameter choices that require checks against the expected master basis [9]. The generated system can still contain redundant equations, which elimination identifies as it processes the relations into reduction rules.

4.2 Integral ordering, sector order and forward elimination

Elimination solves an identity for one integral and substitutes the result into other identities, using an integral ordering to select which unknown to eliminate from each equation. Kira defines these orderings through sector labels and the powers of the numerator and denominator factors, with choices that prioritize numerator powers or repeated denominators and thereby affect the master basis and runtime [8].

To describe this procedure, write $I_j = I_{\boldsymbol{a}^{(j)}}$ for the integrals in Eq. (11) and choose the ordering $I_1 \succ I_2 \succ \cdots \succ I_{n_I}$, where $\succ$ gives priority for elimination. In a row whose first nonzero term contains I_k, let b_j denote the coefficient of I_j, so choosing the nonzero coefficient b_k as the pivot gives

$$b_k I_k + \sum_{j>k} b_j I_j = 0 \quad \Longrightarrow \quad I_k = -\sum_{j>k} \frac{b_j}{b_k} I_j. \tag{16}$$

The coefficients b_j depend on $\boldsymbol{x}, \epsilon$, and substituting this expression into the other rows removes their dependence on I_k. Repeating this step gives forward elimination, which builds a triangular system in which each pivot integral depends on integrals later in the ordering. Back substitution then replaces the remaining pivot integrals using their own rules, completing the Laporta solution [7].

Sector scheduling sets the order in which the solver processes groups of integrals or equations, taking into account which other integrals their equations contain. Ordinary IBP identities for a sector involve that sector and its subsectors because nonpositive indices remain nonpositive when applying the derivative. Equations for one sector can therefore depend on integrals from its subsectors. The Kira 3 description starts equation generation with sectors earlier in its ordering and inserts previously obtained pivot relations into new equations [9], with the order of processing depending on the stage of the reduction.

When several rows share the same first integral, the choice of pivot row changes the substitutions that follow. Choosing row ρ to eliminate column k, for example, updates row i by

$$A_{ij} \longleftarrow A_{ij} - \frac{A_{ik}}{A_{\rho k}} A_{\rho j}, \qquad A_{\rho k} \neq 0. \tag{17}$$

Here i is the index of a row other than the pivot row, so $i \neq \rho$, and j is the column index. Subtracting the stated multiple of row ρ sets the coefficient in column k to zero and can create nonzero entries in other columns, a change called fill-in when a previously zero entry becomes nonzero. These substitutions also make the coefficient expressions longer by combining their numerators and denominators, so elimination can require more time and memory as it proceeds. Redundant equations add to this work [10], so Kira uses modular elimination to select equations before processing their full symbolic coefficients.

4.3 Removing redundant equations and selecting target dependencies

To reduce the number of equations it must solve, Kira identifies rows that follow from other equations. Elimination reduces every coefficient in such a row to zero, allowing the solver to omit that row. Kira tests these dependencies with modular arithmetic [2] by substituting sample values $\boldsymbol{x}_0, \epsilon_0$ and mapping the coefficients to a finite field $\mathbb{F}_P$ for a prime integer P:

$$A(\boldsymbol{x}, \epsilon) \longmapsto A(\boldsymbol{x}_0, \epsilon_0) \bmod P. \tag{18}$$

Integers from 0 to $P - 1$ represent the elements of $\mathbb{F}_P$, and addition and multiplication keep results in this range by taking the remainder upon division by P. Division uses the modular inverse of a nonzero element, which multiplies that element to one modulo P, so the sampling procedure excludes points where a required denominator vanishes. This arithmetic keeps field elements bounded in size while allowing the solver to identify independent rows and retain their original symbolic identities.

The matrix rank is the largest number of independent rows, where no row is a linear combination of the others in the chosen set. Some sample values can make otherwise independent rows dependent, giving a rank smaller than that of the symbolic matrix. Checks must account for this possibility when using the probabilistic equation-selection method developed by Kant [10].

Kira also tracks which independent equations contribute to the target reductions, using the dependencies of the forward-eliminated system for this selection in Kira 3 [9]. Seed selection therefore supplies the integrals from which Kira generates equations, and equation selection then retains the relations needed for the targets so that the solver can perform the full reduction on this smaller system.

4.4 Back substitution and the final symbolic result

To obtain $C_{\boldsymbol{a}m}$ from the retained equations, Kira applies back substitution to the pivot rules produced by forward elimination. Since these rules can contain other pivot integrals, back substitution inserts their expressions recursively until the right-hand sides contain only masters, giving Eq. (12). Kira's original symbolic solver carries out this calculation using rational-function arithmetic through the computer algebra system Fermat [2].

Kira also solves systems at finite-field sample points and reconstructs the rational coefficients with FireFly, the reconstruction library introduced into the solver in Kira 2.0 [11]. In this procedure, each sampled coefficient has the form

$$C_{\boldsymbol{a}m}(\boldsymbol{x}_0, \epsilon_0) \bmod P. \tag{19}$$

The modular operations use exact arithmetic, and reconstruction recovers $C_{\boldsymbol{am}}(\boldsymbol{x}, \epsilon)$ from sufficient samples before checking the result at additional points. Reconstruction therefore forms part of the calculation of the symbolic reduction coefficients, after which the master integrals still require evaluation [11].

Because seed selection determines the equations that enter this procedure and elimination decisions determine the substitutions and intermediate expressions, the proposed ML models would guide these two operations to reduce the time and memory needed for the reduction.

5 ML for seed selection and elimination ordering

We first study two machine learning models: one for seed selection and one for elimination ordering. These models learn from recorded reductions and assign scores to choices available at the current step. We select model types by complete reduction time, including inference and exact checks. Training requires targets with known master expansions, the seeds that supply their equations and the steps used to reduce them. The implemented models and their completed training appear in Sections 7 and 9, followed by their held-out tests. Section 18 then adds a third model that selects identities generated from the retained seeds for the requested targets.

The present experiments test seed-reference agreement, whether the stored identities from the predicted seeds suffice inside Kira, and reduction of a target coefficient row. We then compare complete symbolic reductions with Kira's existing strategies. A native adapter converts predicted seeds into sector bounds for equation generation, while the row adapter applies exact symbolic target-row updates before Kira finishes the reduction. Section 11 measures their costs. Section 12 then places the row model inside Kira's evolving matrix, and Section 13 tests direct seed filtering and a compiled row policy with lower prediction costs.

5.1 Selecting seeds before equation generation

The first model receives the family definition, the target terms and their index vectors $\boldsymbol{a}$, the chosen master basis and a candidate seed list within stated sectors and index bounds. It assigns each candidate a separate probability of belonging to the target's recorded sufficient seed set, which allows several seeds to receive label one.

During training, we pair each target with the seeds used by its checked reference reduction. Different reductions can use different sufficient sets, and the stored labels identify the selected reference set. They do not establish that every omitted seed is unnecessary. For use inside Kira, we supply the stored equations associated with the predicted seeds and check whether they suffice in the chosen master basis. An unresolved target requires further identities. Section 8 measures recovery of the recorded sets and then tests their algebraic sufficiency through symbolic Kira reductions. The second test also checks the full candidate pool as a fallback.

5.2 Choosing elimination steps within the solver

The second model receives the current coefficient matrix and the supplied allowed row operations. It assigns a probability to each operation, selects one operation and reports the selected probability as its confidence. An exact row update then applies Eq. (17). The next state supplies the information for the next choice.

Each training example specifies the matrix before the choice, the allowed pivots, and the recorded source row and integral to eliminate. The retained later steps permit checks of the complete path

and its arithmetic count, while predictive features use the current state and supplied actions. In the present data, the source identities stay fixed and one target row changes during reduction. The native integration follows Kira's integral ordering and supplies allowed choices from the current evolving equations. This changes the states seen by the model and requires separate exact and runtime checks.

The computational benefit depends on the total work: preparing features and evaluating the model must cost less than the algebraic work that its choices save. The tests therefore record complete-path arithmetic and timing as well as next-step agreement. The comparison in Section 11 measures complete symbolic reductions with the selected operations.

5.3 Integral data required for training and testing

To train and test both models, we need family denominators, kinematic parameters, targets and a master basis together with the exact coefficients in Eq. (12). For a target containing several integrals, these coefficients specify the master expansion of the complete expression. Each example also identifies its source equations, actual IBP seeds and derivative operators. Algebraic identities, including mass partial fractions, remain separately identified because they carry no IBP seed.

We construct targets from known master combinations and retain the operations used to form each target and reduce it back to the same basis. The elimination records give the coefficients before and after each step, all allowed source rows, the selected pivot and the operation counts. These records connect seed selection to the equations available for elimination.

The known master coefficients provide a reference for checking complete reduction in the chosen basis, as described in Section 3 [9]. We keep these answers, the selected labels and future construction histories separate from the information used to predict a choice. Section 6 explains how we obtain the bases, construct the targets and check their seed and elimination records.

6 Target Integral Generation for Machine Learning

To train and test the two models described in Section 5, we constructed targets from master bases while retaining their source identities, seeds and algebraic steps. The initial collection contains 49 master entries and 1,662 targets across 16 families. We then extended the collection to 1,000 families, giving 9,678 master entries and 240,472 targets with checked reference reductions [12, 13, 14]. We first added 100 restricted coupled-vacuum mass profiles at each loop order from two through twelve, then 1,250 further profiles at each order from one through twelve. The complete collection contains 17,100 family instances, 57,979 master entries and 2,301,272 targets. The following subsections define the earlier construction and then derive the added vacuum bases and reverse targets. Every target retains its exact symbolic definition and master expansion.

6.1 Initial one-loop families and their kinematics

We use the integral definition and normalization in Eq. (3), with $d = 4 - 2\epsilon$ and inverse propagators $D_i = q_i^2 - m_i^2 + \mathrm{i}0$. For each family, we specify the internal momenta q_i, the masses m_i and the scalar products of the external momenta, so every index vector defines a particular integral. In the equations below we suppress the common i0 prescription. We write $\mu = m^2$ for a common nonzero squared mass and $\mu_1 = m_1^2$, $\mu_2 = m_2^2$ for two independent nonzero squared masses. The symbols x_s and x_t denote momentum invariants and remain distinct from the index sums s and t in Eq. (14).

The one-loop collection begins with a massive tadpole, whose single inverse propagator is $D_1 = \ell_1^2 - \mu$ and which has no external momentum. We then include four bubble families with external momentum p and inverse propagators

$$D_1 = \ell_1^2 - m_1^2, \qquad D_2 = (\ell_1 - p)^2 - m_2^2, \qquad p^2 = x_s. \tag{20}$$

The squared-mass pairs are $(0,0)$, $(\mu,0)$, (μ,μ) and (μ_1,μ_2), corresponding to a massless bubble, a bubble with one massive line, an equal-mass bubble and an unequal-mass bubble. We keep x_s as an independent nonzero scale, with the massive families defined at generic values of their independent parameters.

To include three-point integrals, we define triangle families by

$$\begin{aligned} &D_1 = \ell_1^2 - m_1^2, \quad D_2 = (\ell_1 - p_1)^2 - m_2^2, \qquad D_3 = (\ell_1 - p_1 - p_2)^2 - m_3^2, \\ &p_1^2 = u_1, \qquad\qquad p_2^2 = u_2, \qquad\qquad (p_1 + p_2)^2 = u_3. \end{aligned} \tag{21}$$

Here u_1, u_2, u_3 are the squared external momenta, also called external virtualities, and $p_1 \cdot p_2 = (u_3 - u_1 - u_2)/2$ fixes the remaining external scalar product. We use three massless families with $(u_1,u_2,u_3) = (0,0,x_s)$, $(0,x_2,x_3)$ and (x_1,x_2,x_3). The parameters x_1, x_2, x_3 denote independent nonzero virtualities. We also use two families with $m_1^2 = m_2^2 = m_3^2 = \mu$ and virtualities $(0,0,x_s)$ and (x_1,x_2,x_3). Thus the five triangle families vary both the internal masses and the number of nonzero external virtualities.

For four-point integrals, we use three massless box families with $p_4 = -p_1 - p_2 - p_3$ and

$$\begin{aligned} &D_1 = \ell_1^2, \qquad\qquad D_2 = (\ell_1 - p_1)^2, \\ &D_3 = (\ell_1 - p_1 - p_2)^2, \quad D_4 = (\ell_1 - p_1 - p_2 - p_3)^2, \\ &x_s = (p_1 + p_2)^2, \qquad x_t = (p_2 + p_3)^2. \end{aligned} \tag{22}$$

Writing $u_i = p_i^2$ for $i = 1, \ldots, 4$, we fix the independent external scalar products through

$$p_1 \cdot p_2 = \frac{x_s - u_1 - u_2}{2}, \qquad p_2 \cdot p_3 = \frac{x_t - u_2 - u_3}{2}, \qquad p_1 \cdot p_3 = \frac{u_4 + u_2 - x_s - x_t}{2}. \tag{23}$$

The virtuality choices are $(0,0,0,0)$, $(0,0,0,x_4)$ and (x_1,x_2,x_3,x_4), where x_4 is the fourth nonzero virtuality parameter. These choices give boxes with zero, one and four off-shell legs; in this classification an on-shell external leg has $p_i^2 = 0$. We treat the remaining invariants as independent subject to the stated relations. These definitions give 13 one-loop families, which we extend with the following three two-loop families.

6.2 Initial two-loop families and auxiliary expressions

The two-loop families use loop momenta ℓ_1, ℓ_2. For a massless two-point integral with external momentum p and $p^2 = x_s$, we take

$$(D_1, D_2, D_3, D_4, D_5) = (\ell_1^2, \ell_2^2, (\ell_1 - \ell_2)^2, (\ell_1 - p)^2, (\ell_2 - p)^2). \tag{24}$$

These five expressions determine the five loop-dependent scalar products $\ell_1^2, \ell_2^2, \ell_1 \cdot \ell_2, \ell_1 \cdot p$ and $\ell_2 \cdot p$. Varying their indices therefore includes numerator insertions as well as repeated propagators.

For the equal-mass sunrise with the same external invariant, we use

$$\begin{aligned} &D_1 = \ell_1^2 - \mu, \qquad D_2 = \ell_2^2 - \mu, \qquad D_3 = (p - \ell_1 - \ell_2)^2 - \mu, \\ &D_4 = (p - \ell_1)^2, \quad D_5 = (p - \ell_2)^2, \quad a_4, a_5 \le 0. \end{aligned} \tag{25}$$

The first three expressions are the physical inverse propagators. The auxiliary expressions D_4, D_5 complete the five scalar products needed to express the derivatives in the IBP identities. Their nonpositive indices restrict them to numerator factors or their absence, so the top sector contains only D_1, D_2, D_3 as denominators. We keep x_s and μ independent.

The final family is the equal-mass two-loop vacuum sunset, which has no external momentum and uses

$$D_1 = \ell_1^2 - \mu, \qquad D_2 = \ell_2^2 - \mu, \qquad D_3 = (\ell_1 - \ell_2)^2 - \mu. \tag{26}$$

These three expressions determine all loop scalar products for this vacuum family. For every family, we include the sector containing all physical propagators and all its subsectors, so the resulting basis also accounts for integrals with removed propagators. The number of physical propagators in this top sector is denoted by t_{top}. It is one, two, three and four for the tadpole, bubble, triangle and box families, respectively, five for the massless two-loop propagator, and three for the sunrise and vacuum families. This number sets the initial range of identities used to identify the masters.

6.3 Identification and checks of the master bases

For each initial family, we used Kira 3.1 to generate IBP relations together with the applicable Lorentz-invariance and symmetry relations. Kira removes scaleless sectors and uses finite-field elimination to identify the integrals that remain independent in the equations needed for a selected integral range [2, 9]. We used Kira's integral ordering 1 throughout, which orders sectors by their labels and prefers numerator insertions over extra denominator powers when selecting representatives within a sector [8]. Keeping this ordering fixed gives a specified basis against which to compare later calculations.

We first generated identities from seeds satisfying

$$r \le t_{\text{top}} + 2, \qquad s \le 2, \qquad n_{\text{dot}} \le 2, \tag{27}$$

and selected integrals to probe the basis within

$$r \le t_{\text{top}} + 1, \qquad s \le 1, \qquad n_{\text{dot}} \le 1. \tag{28}$$

Here r is the sum of positive indices, s is minus the sum of negative indices and $n_{\text{dot}} = r - t$ is the number of extra denominator powers, as defined in Eq. (14). Both sets of limits apply to the top sector and its subsectors. The probe integrals specify the range for which Kira must identify the required masters, while the wider seed range supplies relations that can eliminate the additional integrals introduced by index shifts. These probes serve the basis calculation; the ML examples come from the subsequent reverse construction.

Kira evaluated the coefficients of these relations over a finite field using the substitution in Eq. (18). For the first calculation we used the prime $P_1 = 2147483647$ and dimension value $d_1 = 37$. To specify the kinematic substitutions, define the ordered parameter list

$$\boldsymbol{z} = (x_s, x_t, x_1, x_2, x_3, x_4, \mu, \mu_1, \mu_2). \tag{29}$$

The first sample was

$$\boldsymbol{z}^{(1)} = (-13, -19, -11, -17, -29, -43, 7, 7, 23), \tag{30}$$

using only the entries present in each family and retaining all zeros and equal-mass conditions in its definition. We interpret these assignments modulo P_1 when evaluating the identity coefficients. The dimension sample corresponds to $\epsilon_1 = (4 - d_1)/2$ in the same field. These

substitutions test algebraic relations; the master labels continue to refer to integrals at symbolic $\boldsymbol{x}, \epsilon$.

We then enlarged the seed and probe ranges to check whether the initial basis remained sufficient:

$$\begin{aligned} \text{seeds:} \quad & r \le t_{\text{top}} + 3, \qquad s \le 3, \qquad n_{\text{dot}} \le 3, \\ \text{probes:} \quad & r \le t_{\text{top}} + 2, \qquad s \le 2, \qquad n_{\text{dot}} \le 2. \end{aligned} \tag{31}$$

We repeated the calculation first at the original sample and then at a second sample with prime $P_2 = 1000000007$, dimension $d_2 = 41$ and

$$\boldsymbol{z}^{(2)} = (-31, -47, -23, -37, -53, -71, 11, 11, 29). \tag{32}$$

Changing the prime, the dimension and the independent kinematic parameters provides a second check of the linear dependencies, since particular substitutions can lower the rank of the symbolic coefficient matrix [10].

In both enlarged calculations, we supplied the original masters as the preferred basis and enabled Kira's check for additional or unused masters [9]. We required the complete list of master index vectors to agree in all three calculations, and also checked each vector against its family definition and sector label. All 16 families satisfied these requirements, giving 48 completed master-identification calculations. The agreement provides evidence for basis stability over the tested index ranges and sample points. Completeness for arbitrary integer indices would require further relations or an independent argument, and special kinematic limits can change the basis.

We stopped each calculation after master identification. This stage determines which symbolic integrals form the starting basis within the checked domains. We then obtained rational reduction coefficients for the constructed targets through the algebraic procedure described below. The numerical values and ϵ expansions of the master integrals remain separate from this basis determination.

6.4 Resulting bases and the starting coefficients

The massive tadpole gave one master. The massless, one-mass, equal-mass and unequal-mass bubbles gave one, two, two and three masters, respectively. The massive bubble bases include the necessary tadpole subsectors, with two distinct tadpoles when the internal masses differ.

The massless triangles with one, two and three nonzero external virtualities gave one, two and four masters, respectively. For the first two families, Kira chose bubble integrals in subsectors as the masters. The three-virtuality family also retained a triangle integral. The equal-mass triangles with one and three nonzero virtualities gave three and five masters. The massless boxes with zero, one and four off-shell legs gave three, four and eleven masters, respectively, including the required lower sectors in each count.

The massless two-loop propagator gave two masters, the equal-mass sunrise gave three, and the equal-mass vacuum sunset gave two. For the denominator order in Eq. (25), the sunrise basis is

$$M_1 = I_{(1,1,0,0,0)}, \qquad M_2 = I_{(1,1,1,0,0)}, \qquad M_3 = I_{(1,1,1,-2,0)}. \tag{33}$$

The first integral factorizes into a product of two massive tadpoles because removing D_3 separates the loop integrations. The other two integrals retain all three sunrise propagators, and M_3 contains the numerator factor D_4^2. This example shows how the chosen ordering can retain a numerator integral as a master.

The counts sum to 49 master entries across these 16 initial families. We count each basis within its own family, so shared tadpole and bubble subsectors can appear in more than one family.

The complete family definitions and master index vectors are available with the accompanying data [12]. Each entry specifies the denominators, kinematics, index vector, sector and mass dimension. With the normalization in Eq. (3), the latter is

$$[I_{\boldsymbol{a}}]_{\text{mass}} = Ld - 2\sum_{i=1}^{N} a_i, \tag{34}$$

where $[I_{\boldsymbol{a}}]_{\text{mass}}$ is the power of mass carried by the integral. Each loop measure contributes d powers and each factor $D_i^{-a_i}$ contributes $-2a_i$. This dimension constrains the coefficients used to combine integrals in the target construction.

For that construction, we kept the identified masters symbolic and initialized each master as itself. If $\boldsymbol{\mu}^{(m)}$ is the index vector of master M_m, the starting coefficients are

$$M_m = I_{\boldsymbol{\mu}^{(m)}}, \qquad C_{\boldsymbol{\mu}^{(m)}n} = \delta_{mn}, \qquad m, n = 1, \ldots, n_M. \tag{35}$$

Here n_M is the number of masters in the selected family, and δ_{mn} is one when $m = n$ and zero otherwise. Thus each master has coefficient one for itself and zero for the others. We held the family definition and basis fixed while constructing its targets, starting with these masters and extending the collection through the identities below. Each accepted target therefore has a specified reference basis and an exact master expansion.

6.5 Source identities and the reference integral order

To extend the starting masters into targets, we first generated relations among the integrals of each family. We used the IBP identity in Eq. (7) with seeds in every nonempty physical sector within the bounds of Eq. (27). The auxiliary sunrise indices remained nonpositive. We fixed this candidate seed set before constructing targets, and retained each equation with its seed $\boldsymbol{\sigma}$, differentiated loop momentum ℓ_k and vector v [4, 2]. The resulting equations can contain integrals beyond the seed bounds because differentiation shifts the indices.

The vectors v included loop momenta, external momenta and propagator momenta q_i. Each propagator momentum is a fixed linear combination of loop and external momenta, so its IBP equation is the corresponding linear combination of the usual IBP equations at the same seed. We retained this decomposition to specify how each equation follows from its source operators. We also obtained symmetry relations by explicit changes of loop variables whose loop transformation matrix has determinant $+1$ or -1. We accepted a transformation when it permuted the inverse propagators with their masses unchanged and preserved the physical and auxiliary index positions.

To give the constructions a reduction order, we protected the chosen masters from elimination and ordered every other integral by

$$(S(\boldsymbol{a}),\, n_{\text{dot}}(\boldsymbol{a}),\, s(\boldsymbol{a}),\, r(\boldsymbol{a}),\, \boldsymbol{a}). \tag{36}$$

Here S is the sector number in Eq. (5), and the remaining quantities are the index sums in Eq. (14). We compare the entries in the displayed order, using the first unequal entry to decide which integral is larger. We compare the components of $\boldsymbol{a}$ in the same way when all earlier entries agree. The leading integral of an equation is its largest integral outside the master basis. This reference order specifies the construction and recorded reductions; adapting the elimination model to Kira will require its actual ordering and available pivot choices.

6.6 Reverse construction from combinations of masters

To obtain target expressions with known answers, we selected subsets of masters from the same family and replaced their terms through the source identities. Let $\mathcal{J} = \{m_1, \ldots, m_h\}$ be the selected master labels, where h is the number of chosen masters. The initial expression is

$$\mathcal{T}_0 = \sum_{m \in \mathcal{J}} c_m(\boldsymbol{x}, d) M_m, \qquad 1 \le h \le \min(3, n_M). \tag{37}$$

The coefficients are rational functions of the independent kinematic parameters and $d = 4 - 2\epsilon$, with no dependence on the loop momenta. Writing them in terms of d is equivalent to writing them in terms of ϵ. Their mass dimensions must compensate for differences between the chosen masters so that every term in $\mathcal{T}_0$ has the same dimension.

For this purpose, let $B_m = \sum_i \mu_i^{(m)}$ be the sum of the indices of master M_m, and set $A = B_{m_1}$. For a fixed nonzero squared mass or momentum invariant Q^2 in the family, we used

$$c_{m_j} = u_j(d)(Q^2)^{B_{m_j} - A}, \qquad [\mathcal{T}_0]_{\text{mass}} = Ld - 2A. \tag{38}$$

Here $j = 1, \ldots, h$ identifies a selected master and u_j is dimensionless. We varied the weights through the three forms

$$\begin{gathered} u_j(d) \in \left\{ \eta_j,\ \eta_j \frac{d-2}{d-4},\ \eta_j \frac{j+1}{d-2} \right\}, \\ \eta_j \in \{-3, -2, -1, 1, 2, 3\}. \end{gathered} \tag{39}$$

Here η_j is a nonzero integer weight. For each sequence we chose one of these three forms and varied the integer weights and selected masters. The power of Q^2 in Eq. (38) gives c_m mass dimension $2(B_m - A)$, so Eq. (34) gives the stated common dimension.

To replace a term, write the current expression and a source IBP identity as

$$\mathcal{T}_n = \sum_{\boldsymbol{b}} w_{\boldsymbol{b}}^{(n)} I_{\boldsymbol{b}}, \qquad R = \sum_{\boldsymbol{b}} r_{\boldsymbol{b}} I_{\boldsymbol{b}} = 0. \tag{40}$$

Here n is the number of completed replacements, while $w_{\boldsymbol{b}}^{(n)}$ and $r_{\boldsymbol{b}}$ are the coefficients of integral $I_{\boldsymbol{b}}$ in the expression and identity. The sums contain their finitely many nonzero terms. For a present term $I_{\boldsymbol{a}}$, we selected an identity generated at seed $\boldsymbol{a}$ with $r_{\boldsymbol{a}} \neq 0$, and formed

$$\mathcal{T}_{n+1} = \mathcal{T}_n - \frac{w_{\boldsymbol{a}}^{(n)}}{r_{\boldsymbol{a}}} R. \tag{41}$$

This operation cancels the chosen term and introduces other family integrals. Since $R = 0$, the resulting expression has the same master expansion as $\mathcal{T}_0$. We required the identity to introduce a leading integral larger than every integral already present, so the recorded steps can be reversed through the order in Eq. (36).

For the initial collection, we attempted 24 sequences per family, with at most four replacements per sequence, and retained accepted intermediate expressions. A sequence stopped when no admissible replacement was found within the construction limits. We removed identical target expressions and retained only nonzero targets with complete reference reductions. When the final expression contained one integral with coefficient $q \neq 0$, we divided the expression and its master coefficients by q and recorded this normalization. Expressions containing several index vectors remain targets for reduction of the complete sum. To obtain further individual integrals, we also applied the source identities in the following way.

6.7 Constructing individual integrals from known reductions

Starting from Eq. (35), we searched for a source identity whose leading integral was the only term without a known master expansion. Such an identity has the form

$$h_0 I_{\boldsymbol{b}} + \sum_{j=1}^{n_R} h_j I_{\boldsymbol{a}^{(j)}} = 0, \qquad h_0 \neq 0, \tag{42}$$

where $I_{\boldsymbol{b}}$ is the new integral, n_R is the number of other terms and h_0, h_j are the identity coefficients. Substituting the known reductions of the other terms gives

$$I_{\boldsymbol{b}} = \sum_{m=1}^{n_M} C_{\boldsymbol{b}m} M_m, \qquad C_{\boldsymbol{b}m} = -\sum_{j=1}^{n_R} \frac{h_j}{h_0} C_{\boldsymbol{a}^{(j)}m}. \tag{43}$$

We added each resulting expansion to the known set so later identities could use it. If all its master coefficients vanished, we retained the zero-integral proof as a dependency for subsequent constructions. The target collection contains the accepted nonzero examples.

For the initial collection, we made at most five passes through the source equations and allowed at most 64 new nonzero constructions of this type per family. An equation with several still-unknown integrals became usable only after other identities supplied the missing expansions. Solving remaining coupled systems would extend this construction beyond the individual integrals obtained here. Both this procedure and the reverse replacements above preserve the source equations and their dependencies, which determine the seed and elimination records.

6.8 Seed records and elimination sequences

For each accepted target, we retained its exact master coefficients together with the source identities used to obtain them. An IBP identity contributes its seed and derivative operator, while a symmetry identity contributes its loop-variable transformation and integral mapping. Dependencies carry the earlier identities needed to reduce intermediate integrals or establish that they vanish. For an IBP step of the form in Eq. (42), the sufficient seed set therefore obeys

$$\mathcal{S}_{\boldsymbol{b}} = \{\boldsymbol{\sigma}\} \cup \bigcup_{j=1}^{n_R} \mathcal{S}_{\boldsymbol{a}^{(j)}}, \qquad \mathcal{S}_{\boldsymbol{\mu}^{(m)}} = \varnothing. \tag{44}$$

Here $\mathcal{S}_{\boldsymbol{a}}$ is the seed set recorded for $I_{\boldsymbol{a}}$, $\boldsymbol{\sigma}$ is the seed of the current IBP identity and $\varnothing$ is the empty set. Symmetry steps retain the dependency sets and their symmetry record. For reverse constructions, the seed set is the union of the seeds of the identities used along the recorded path.

We retained the full candidate seed set alongside each family so the seed model can compare possible choices. The recorded subset supplies enough equations for the known reduction, and seeds outside it can still contribute to other valid reductions. For the model inputs, we stored the family, basis, target coefficients and index information, including the sector and $t, r, s, n_{\mathrm{dot}}$. We kept the exact answer, construction history and reference seed choices separately.

To obtain elimination examples, we represented the target as a row of coefficients $T_{\boldsymbol{b}}$ multiplying $I_{\boldsymbol{b}}$. At each step, we selected its largest remaining integral outside the master basis, denoted by $I_{\boldsymbol{a}}$. The available pivot rows were the retained source identities with leading integral $I_{\boldsymbol{a}}$ and a nonzero coefficient for that integral. For the chosen row R, the update was

$$T_{\boldsymbol{b}} \longleftarrow T_{\boldsymbol{b}} - \frac{T_{\boldsymbol{a}}}{r_{\boldsymbol{a}}} r_{\boldsymbol{b}}. \tag{45}$$

This cancels $I_{\boldsymbol{a}}$ from the target and can introduce only smaller integrals or masters. Repeating the recorded choices gives the target's known master expansion. The source equations remain unchanged during this target-row reduction, so the current row, source equations and reference order specify the state seen by the elimination model.

For every step, we retained the row before and after the update, all available pivot rows, the selected equation and integral, the multiplier, and the numbers of new and cancelled nonzero entries. We kept the coefficients as exact rational functions and also stored numerical row states over a finite field. The first sample in Eq. (30), with $P_1 = 2147483647$ and $d_1 = 37$, supplied these numerical states. Substituting parameters into the coefficient functions leaves the integrals symbolic and uses exact modular arithmetic for the row operations [11].

For a selected source row with n_{row} nonzero terms, we counted one finite-field division and n_{row} multiplications and subtractions. Summing these counts gives the cost of the recorded target-row sequence. Equation generation, forming combined IBP operators, symbolic simplification, model inference and reconstruction fall outside this count. The construction gives a valid reference path and an upper bound on the minimum cost under these rules. Establishing a minimum would require a separate argument covering alternative seed sets and elimination paths.

6.9 Initial target collection and consistency checks

The initial collection contains 1,662 accepted targets across its 16 families, with 309 individual integrals, 1,353 integral expressions and 5,138 recorded elimination steps [13]. We divided the examples by complete families into 1,290 training targets, 185 validation targets and 187 test targets. Validation targets belong to the unequal-mass bubble and massless triangle with three off-shell legs. Test targets belong to the massless box with four off-shell legs and the equal-mass sunrise. These held-out targets contain terms in the full physical sector, while their basis definitions still include the required lower sectors.

In this initial collection, the validation set consists entirely of integral expressions, and the test set contains one individual integral and 186 expressions. These initial counts motivate the additional held-out individual constructions described below. This initial collection covers the specified one-loop and two-loop families and the stated construction bounds. The following sections describe seed-model training and its held-out comparison on the expanded collection. Section 9 describes the reduction model. Section 10 measures complete target-row sequences and their selection costs. Section 11 compares complete symbolic reductions, including native Kira seeding.

Before accepting the collection, we rederived all 55,654 stored source equations from their family definitions and checked the recorded symmetry transformations. We also checked 2,699 used IBP equations by independently differentiating the original quadratic expressions for the propagators in terms of loop scalar products. We then replayed every target construction and elimination sequence with exact rational functions, including intermediate zero-integral dependencies and final normalizations. Each final result agreed with its stored master expansion, and the checks also confirmed mass dimensions, seed records and allowed pivots.

To check the sampled coefficients, we repeated every elimination sequence at three finite-field points. The first two were the samples in Eqs. (30) and (32), with the primes and dimension values specified there. The third used $P_3 = 1000000009$, $d_3 = 43$ and

$$\boldsymbol{z}^{(3)} = (-59, -73, -41, -61, -83, -101, 17, 17, 47), \tag{46}$$

in the parameter order of Eq. (29). Each family used its own parameters and retained its prescribed zeros and equal masses. All required divisions were defined at the three points, and every sampled reduction reproduced the reference coefficients.

The exact symbolic checks establish the recorded reductions from their source identities at generic parameters, while the three-point checks verify the numerical data supplied with them. This construction already provides the symbolic coefficient functions, so obtaining the reference answers requires no rational-function reconstruction. The accompanying data contain the targets, equations, construction histories, sufficient seeds and elimination records needed to train and test the two proposed models [13].

6.10 Extension to different mass and kinematic conditions

To supply examples across a wider range of parameter conditions, we added 984 one-loop families with four physical propagators. For these families, we write

$$D_i = (\ell_1 - Q_i)^2 - \mu_{\alpha_i} + \mathrm{i}0, \qquad i = 1, \ldots, 4, \qquad Q_1 = 0. \tag{47}$$

Here Q_2, Q_3, Q_4 are three independent external momentum vectors, $\mu_0 = 0$ and μ_1, μ_2, μ_3 are independent nonzero squared masses. Each label $\alpha_i \in \{0, 1, 2, 3\}$ assigns the squared mass of the corresponding propagator. Repeated positive labels impose equal masses.

We specify the external kinematics through the six squared differences between the propagator shifts:

$$\Delta_{ij} = (Q_i - Q_j)^2 = y_{\beta_{ij}}, \qquad 1 \le i < j \le 4. \tag{48}$$

Here $y_0 = 0$, y_1, y_2, y_3 are independent nonzero momentum invariants, and $\beta_{ij} \in \{0, 1, 2, 3\}$. Repeated labels impose equality between the corresponding invariants. The mass parameters and momentum invariants remain independent of one another, and a family uses only the parameters that occur in its assignments.

These distances determine the external scalar products:

$$G^{\mathrm{ext}}_{ij} = Q_i \cdot Q_j = \frac{\Delta_{1i} + \Delta_{1j} - \Delta_{ij}}{2}, \qquad i, j = 2, 3, 4, \qquad \Delta_{ii} = 0. \tag{49}$$

The matrix G^{ext} is the external Gram matrix. We required it to be nonsingular at all three recorded sample points, which also excludes a determinant that vanishes identically under the stated parameter conditions. Each family then defines a symbolic integral problem through its particular zero and equality relations.

To remove equivalent definitions, we compared the assignments under all 24 permutations of the four propagators, together with independent relabelling of the nonzero mass and momentum-invariant parameters. The enumeration found 1,673 inequivalent profiles satisfying the parameter and sample requirements after excluding the existing massless box definitions. A fixed ordering selected 984 of these profiles [14]. Together with the original families, this earlier collection contained 997 one-loop and three two-loop families. The added profiles share the four-propagator box topology, so the family count describes different mass and kinematic conditions within this topology.

We identified and checked a master basis separately for every added family using the three calculations in Subsection 6.3. The four-propagator families have $t_{\mathrm{top}} = 4$, so the first seed range has $r \le 6$, $s \le 2$ and $n_{\mathrm{dot}} \le 2$. We then enlarged the seed and probe ranges, supplied the first masters as the preferred basis and repeated the basis check at a second point and prime. All 1,000 families passed their three basis calculations, giving 3,000 completed checks within the recorded domains.

For the added families, define

$$\boldsymbol{w} = (y_1, y_2, y_3, \mu_1, \mu_2, \mu_3). \tag{50}$$

We used the same three primes and dimension values specified above, with the parameter assignments

$$\begin{aligned} \boldsymbol{w}^{(1)} &= (-11, -19, -29, 7, 13, 23), \\ \boldsymbol{w}^{(2)} &= (-31, -47, -61, 11, 17, 29), \\ \boldsymbol{w}^{(3)} &= (-41, -67, -83, 17, 23, 37). \end{aligned} \tag{51}$$

Each family uses only its present parameters and retains all specified zeros and equalities. The first two points supply the basis checks, while the target validation uses all three.

6.11 Expanded targets and their verified reductions

Using the added bases, we applied the reverse construction in Eq. (41) with 48 attempted sequences per family and at most four replacements per sequence. We also allowed up to 96 nonzero individual-integral constructions per added family, using at most five passes through the source identities. The initial master weights retain the rational functions and mass-dimension conditions in Eqs. (38) and (39).

When the first construction produced no accepted targets, we extended the candidate equations to every retained IBP identity containing the selected current integral. Its seed $\boldsymbol{\sigma}$ can then differ from that integral's index vector $\boldsymbol{a}$. The substitution still uses the coefficient of $I_{\boldsymbol{a}}$ in the selected identity and preserves the known master expansion. This extension allows a reverse path to enter a higher sector through an identity generated there, including cases whose masters all lie in lower sectors. We retain the actual seed, require the new leading integral to increase under the reference order, and check every step in the resulting reduction.

To add individual integrals to the held-out sets, we also used the checked construction proofs to select integrals whose four indices are all nonzero and include at least one negative index. Each selected integral already has a known master expansion. We retained it as a separate target and rebuilt its elimination trace from the recorded identities. This step added 384 individual targets. Each has one denominator factor and three numerator factors, with their powers specified by the index vector. The complete four-expression definition therefore enters the target, while its positive indices place it in a one-propagator sector.

Before the higher-loop extension, the collection contained 9,678 master entries and 240,472 targets: 55,768 individual integrals and 184,704 integral expressions [14]. We count master entries within each family, so related lower-sector integrals can occur in several bases. Every target has its complete master expansion, source identities, sufficient seeds and recorded elimination path.

For the added families, we kept each complete kinematic zero and equality pattern in one data split across all mass assignments. This grouping also respects the original training box profiles. We assigned the original validation bubble and triangle examples to the combined training set because those integral families also occur as lower sectors of the added training families. The new grouped families supply the expanded validation set. The original data-generation split contained 771 training families with 198,527 targets, 106 validation families with 19,600 targets, and 123 test families with 22,345 targets. The reverse sequences require validation and test expressions to contain terms in their full physical sectors. The additional individual targets instead require all four family expressions to occur, including those in the numerator. Shared lower-sector masters remain part of the family definitions. The complete family profile is held out, while some lower-sector reduction structure can also occur in training.

The original data-generation validation set contained 183 individual integrals and 19,417 integral expressions, while the corresponding test set contained 202 individual integrals and 22,143 expressions. These counts describe the original construction samples. The grouped model division described below replaces this three-way data-generation division. The added individual

targets supply tests of numerator integrals in one-propagator sectors. The higher-loop construction below supplies additional individual targets and expressions in coupled vacuum families. Sections 8 and 10 measure the two models on the current grouped split.

We rederived 3,299,902 source equations and checked 227,330 used IBP equations by independent differentiation across this earlier collection. We replayed all 240,472 target constructions and 832,924 recorded elimination steps with exact rational functions. Every reduction reproduced its reference master coefficients, and the three finite-field replays checked the corresponding numerical rows. We also checked family equivalence, the grouping of data splits and the correspondence between every saved target and its records. The accompanying collection provides the family definitions, bases, targets and complete reduction data [14].

6.12 Coupled vacuum families from one through twelve loops

To supply examples at every loop order considered in the model study, we first added 100 mass profiles at each order from two through twelve. We then added 1,250 further profiles at each order from one through twelve, in groups of 250 and 1,000 profiles. These extensions provide 16,100 family instances beyond the original collection. They use coupled vacuum integrals whose master expansions follow from mass partial fractions and IBP identities, which allows us to retain exact reference answers as the number of loops increases. The profiles vary the masses within a restricted set of graphs, so the family count measures mass assignments as well as graph structure.

For this extension we use Euclidean loop momenta and define

$$V_{\boldsymbol{b}}^{(L)} = \int \prod_{i=1}^{L} \frac{d^d \ell_i}{\pi^{d/2}} \, \frac{1}{\ell_1^2 \cdots \ell_L^2} \prod_{j=1}^{R} \frac{1}{(Q^2+\mu_j)^{b_j}}, \qquad Q = \sum_{i=1}^{L} \ell_i, \qquad \mu_j = \rho_j \mu. \tag{52}$$

Here L is the number of loops, R is the number of distinct massive denominators, $\mu = m^2 > 0$ is a common squared-mass scale and ρ_j is a positive mass ratio. The nonnegative integer b_j is the power of the jth massive denominator, and $B = \sum_{j=1}^{R} b_j \geq 1$ is their total power. Every massless denominator has power one in the generated domain. The full integral index vector is $(1, \ldots, 1, b_1, \ldots, b_R)$, with $L+R$ entries. Equation (52) specifies the normalization and signs used for this Euclidean subcollection; the earlier families retain their stated Minkowski convention.

For $L > 1$, the common momentum Q couples the loop integrations. A graph representation has L parallel massless edges between two vertices and a chain of R massive edges joining the same vertices. It has $L + R$ edges and $R + 1$ vertices, giving L independent loops. All massive denominators depend on Q^2, which gives algebraic relations between them. This definition is a parent family for partial fractions with fixed massless powers; it does not specify a complete independent denominator and numerator basis for a generic L-loop scattering integral.

For profile number p, we choose

$$R = 2 + ((p-1) \bmod 3), \qquad \rho_1 = 1, \qquad \rho_{j+2} = 2 + 3p + j(p+2), \quad j = 0, \ldots, R-2. \tag{53}$$

The ratios are distinct within each profile, and $\rho_1 = 1$ fixes a common rescaling. The initial profiles use $p = 1, \ldots, 100$ at $L = 2, \ldots, 12$. The later groups use $p = 101, \ldots, 350$ and $p = 351, \ldots, 1350$ at $L = 1, \ldots, 12$. The latest group has 333 profiles with two massive denominators, 333 with three and 334 with four at each loop order. A twelve-loop family with four massive denominators has sixteen indices, which fits the existing model representation.

6.13 Exact masters and source equations for the added families

The dependence on the common momentum makes the master basis explicit. Write $\boldsymbol{e}_j$ for the unit vector in massive index position j and choose

$$M_j^{(L)} = V_{\boldsymbol{e}_j}^{(L)}, \qquad j = 1, \ldots, R. \tag{54}$$

To see why these integrals span the generated domain, first use $D_i - D_j = \mu_i - \mu_j$, where $D_j = Q^2 + \mu_j$. If $b_i, b_j > 0$, this identity gives

$$(\mu_i - \mu_j) V_{\boldsymbol{b}}^{(L)} - V_{\boldsymbol{b}-\boldsymbol{e}_i}^{(L)} + V_{\boldsymbol{b}-\boldsymbol{e}_j}^{(L)} = 0. \tag{55}$$

Repeated use removes products of distinct massive denominators. This equation is an algebraic mass relation and carries no IBP seed.

The remaining powers follow from the sum of the L IBP operators $\partial_{\ell_i^\nu} \ell_i^\nu$. Applying this sum to the integrand of Eq. (52) gives

$$0 = [Ld - 2(L + B)] V_{\boldsymbol{b}}^{(L)} + 2 \sum_{j=1}^{R} b_j \mu_j V_{\boldsymbol{b}+\boldsymbol{e}_j}^{(L)}. \tag{56}$$

Each such equation retains its actual seed $(1, \ldots, 1, \boldsymbol{b})$ and the contributing derivative operators. For one massive denominator this becomes

$$V_{k\boldsymbol{e}_j}^{(L)} = \left[\prod_{h=1}^{k-1} \frac{L + h - Ld/2}{h\mu_j} \right] M_j^{(L)}, \qquad k \geq 1. \tag{57}$$

The empty product at $k = 1$ equals one. Equations (55) and (57) therefore reduce every generated integral to the stated masters with coefficients rational in d and μ.

An analytic expression also checks the basis. Set $D = d/2$, $\alpha = L(D-1)$ and $c = L - (L-1)D$. Repeated integration of the massless subgraph at fixed Q gives

$$C_L(D)(Q^2)^{-c}, \qquad C_L(D) = \frac{\Gamma(c)\Gamma(D-1)^L}{\Gamma(\alpha)}. \tag{58}$$

For $L = 1$, $Q = \ell_1$, $c = 1$ and $C_1(D) = 1$, so this expression reduces directly to the single massless propagator. The remaining radial integration uses $\int d^dQ/\pi^D = \Gamma(D)^{-1} \int_0^\infty dx\, x^{D-1}$ for a rotationally invariant integrand, where $x = Q^2$. It gives

$$M_j^{(L)} = \mu_j^{\alpha-1} \frac{\Gamma(c)\Gamma(D-1)^L \Gamma(1-\alpha)}{\Gamma(D)}. \tag{59}$$

Here Γ is the Euler gamma function. These manipulations use the standard analytic continuation of dimensionally regularized integrals [3]. At generic d, distinct ρ_j give distinct exponential functions of d in $\rho_j^{\alpha-1}$. Their linear independence over rational functions of d establishes independence of the R masters in this restricted domain. After the common factors cancel, a proposed relation would combine exponentials with distinct growth rates. At fixed generic μ, rational coefficients grow or decay only as powers of d, so they cannot cancel the largest exponential unless its coefficient vanishes. Repeating this argument removes each coefficient. The latest addition supplies 3,001 master entries per loop order and 36,012 entries in total. The preceding extensions supplied 3,289 and 9,000 entries. We count the basis within each family, so the master with $\rho_1 = 1$ recurs across profiles at the same loop order.

We also obtain the master coefficients without following the selected row operations. With $z = Q^2/\mu$, the rational identity

$$\prod_{i=1}^{R}(z+\rho_i)^{-b_i} = \sum_{j:b_j>0}\sum_{k=1}^{b_j} A_{jk}(z+\rho_j)^{-k} \tag{60}$$

defines rational numbers A_{jk}. Expanding the other factors around $z = -\rho_j$ gives them directly:

$$A_{jk} = [w^{b_j-k}]\prod_{i\neq j}(\rho_i - \rho_j + w)^{-b_i}. \tag{61}$$

Here $w = z + \rho_j$ is the expansion variable, and $[w^n]$ means the coefficient of w^n in this Taylor series. Combining these coefficients with Eq. (57) yields the independent reference

$$V_{\boldsymbol{b}}^{(L)} = \mu^{1-B}\sum_{j:b_j>0}\sum_{k=1}^{b_j} A_{jk}\left[\prod_{h=1}^{k-1}\frac{L+h-Ld/2}{h\rho_j}\right] M_j^{(L)}. \tag{62}$$

The factor μ^{1-B} ensures that both sides have mass dimension $Ld - 2L - 2B$. This reference allows us to check the reduction path through a separate calculation.

6.14 Reverse target construction and the expanded data division

We supply every Euler seed with $1 \le B \le 5$ and retain the summed Euler identity in Eq. (56) as its source equation together with all mass partial-fraction identities through $B = 6$. Scalar target roots have $2 \le B \le 5$. The source pools contain 35, 160 or 545 equations for $R = 2, 3, 4$, respectively. These counts stay fixed as L changes because the massless powers and massive-index bounds stay fixed. The additional loop orders therefore test this controlled family structure, while large generic IBP systems require wider denominator and numerator domains. After obtaining a checked scalar relation, we reverse its steps to construct the corresponding integral from its master combination. For expressions containing several roots, we first combine their known master expansions and then apply the recorded inverse steps. Each inverse step adds a stated multiple of an exact zero identity, so the master coefficients remain known throughout the construction.

For roots with total powers B_ν, we use target weights of the form

$$\mathcal{T} = \sum_\nu \kappa_\nu d^{\eta_\nu}\mu^{B_\nu - B_*}V_{\boldsymbol{b}_\nu}^{(L)}, \qquad B_* = \max_\nu B_\nu, \qquad \eta_\nu \in \{0,1\}. \tag{63}$$

We choose $\kappa_\nu = n_\nu/q_\nu$, where $n_\nu \in \{-3,-2,-1,1,2,3\}$ and $q_\nu \in \{1,2,3\}$. The powers of μ give every term the same mass dimension. Each family contains eighteen individual target integrals for $R = 2$ and thirty-two for $R = 3$ or $R = 4$, with full massive sectors included before lower sectors. The remaining targets are weighted expressions with one, two or three distinct roots. Each such expression includes a root with every massive denominator present and at least one additional denominator power. We retain 128 distinct targets per family. The latest addition supplies 1,536,000 targets, following the earlier additions of 140,800 and 384,000 targets.

For each target we retain its master coefficients, exact reverse construction, source equations, sufficient IBP seed set and a forward elimination trace. The trace records all allowed source rows, the chosen pivot, the coefficients before and after the operation, and the arithmetic operation counts. Mass partial-fraction steps remain separately identified, so a seed label always refers to an actual IBP seed. The reference path minimizes the next symbolic row's number of nonmaster terms, then its total support and immediate operation count, with a fixed final tie rule. This supplies a reproducible valid path without establishing a globally minimal sequence.

We verify every source equation against Eq. (62) and separately check the partial-fraction formula and the Euler derivative before integration. We replay the symbolic constructions and forward reductions, then independently replay all saved records at three finite-field samples. A candidate target is rejected if a reference pivot vanishes at one of those samples. The checks also verify connected graphs and their loop counts. At $d = 2 + 1/L$ the radial master integral converges; numerical quadrature then checks Eq. (59) at both ends of the loop-order range.

The complete collection now contains 17,100 family instances, 57,979 family-local master entries and 2,301,272 targets. It contains 2,247 one-loop families, 1,353 two-loop families and 1,350 families at each order from three through twelve. We preserve every earlier grouped model assignment and assign 700 of the latest profiles to training and 300 to testing. A profile has the same assignment at every loop order, giving 1,610,890 training targets in 11,963 families and 690,382 test targets in 5,137 families. Shared lower-sector integrals can occur across different profiles. These tests measure transfer between the specified mass profiles with every loop order represented during training; they do not establish transfer to unseen loop orders or general high-loop topologies. The accompanying records contain the complete definitions and checks [15].

7 Machine Learning Model for Seed Selection

To train and test the seed-selection model, we use the target expressions and sufficient seed sets constructed in Section 6. We have implemented a small neural network that assigns a binary decision and its estimated confidence to each supplied candidate seed. We trained the model on the fixed training division and then evaluated it on the held-out targets. This section defines the inputs, probabilities and training procedure, and Section 8 gives the resulting seed predictions.

7.1 Model inputs and seed probabilities

A seed specifies an integral index vector at which the solver generates IBP identities. The resulting equations can contain other integrals whose elimination uses identities from additional seed vectors [2]. A target can therefore use several seeds in a sufficient reduction set. Some targets admit a reduction from one seed, while a target already expressed in the chosen masters needs no IBP seed. We formulate the prediction as a separate binary decision for every candidate, so the model can select several seeds for the same target.

For a fixed family and chosen master basis, write a target as

$$\mathcal{T} = \sum_{j=1}^{n_T} c_j(\boldsymbol{x}, d) I_{\boldsymbol{a}^{(j)}}, \qquad \mathcal{C} = \{\boldsymbol{\sigma}_1, \ldots, \boldsymbol{\sigma}_{n_C}\}. \tag{64}$$

Here n_T is the number of terms in the target, c_j is the rational coefficient of its jth term, $\boldsymbol{x}$ is the set of kinematic parameters and d is the space-time dimension. The vector $\boldsymbol{a}^{(j)}$ gives the integral indices of that term. The set $\mathcal{C}$ contains n_C candidate seed vectors within the stored family bounds. It supplies all candidates that this implementation scores for the target. Extending the seed bounds would require supplying an enlarged candidate set.

The model receives every term in the stored order, including its indices and symbolic coefficient. Each integral contributes its index values, the locations of positive indices and the quantities r, s, t and n_{dot} defined in Eq. (14). We transform an index value a to $\mathrm{sgn}(a)\log(1 + |a|)$ and transform the nonnegative counts with $\log(1 + v)$, where v denotes the count. The input also records the number of family indices and which positions are present. The current representation has capacity for 16 indices; the expanded collection uses up to sixteen.

To include the coefficient functions, we separate their written expressions into variable names, integers and mathematical symbols. We encode counts of individual symbols and consecutive groups of two and three symbols in a fixed vector with 64 components. A fixed signed assignment maps each group to a component, and division by the square root of the total number of groups sets the scale. Every coefficient symbol enters this representation, although different groups can share a component. The resulting vector is a compressed description of the coefficient expression. It does not perform symbolic simplification or establish equality between different expressions. In particular, modular residues do not enter as ordinary real coefficient values.

For each term we append its relative position in the stored list and the inverse term count. Denote the resulting term vector by $\boldsymbol{f}_j$. A shared learned map ϕ_θ forms

$$\boldsymbol{h}_j = \phi_\theta(\boldsymbol{f}_j), \qquad \boldsymbol{h}_j \in \mathbb{R}^{32}. \tag{65}$$

Here θ denotes the adjustable parameters of the model and $\boldsymbol{h}_j$ is a vector describing the term. The same map acts on each term, so its number of parameters does not depend on n_T. Combining shared term maps through averages follows the set-based construction of Ref. [16], with additional position information to retain the stored order.

We also include every ordered pair of distinct terms. If $n_T > 1$, their combined description is

$$\boldsymbol{h}_{\text{pair}} = \frac{1}{n_T(n_T-1)} \sum_{\substack{j,k=1 \\ j\neq k}}^{n_T} \psi_\theta([\boldsymbol{h}_j, \boldsymbol{h}_k, \boldsymbol{h}_j - \boldsymbol{h}_k, \boldsymbol{h}_j \odot \boldsymbol{h}_k])\,. \tag{66}$$

Square brackets join vectors, $\odot$ multiplies corresponding components, and ψ_θ maps each joined vector to 32 components. For an individual-integral target, we set $\boldsymbol{h}_{\text{pair}} = \boldsymbol{0}$. This representation includes both orders of each pair and the positions of the associated terms. The present model uses pairs as its specified form of term combinations; it does not enumerate longer subsets or all permutations of the full expression. The fixed stored term order must also be used when preparing later inputs.

The family information includes the propagator expressions, masses, external scalar products, invariant names, and the numbers of loops, propagators, external momenta and invariant parameters. We encode its symbolic structure with the same fixed 64-component rule and map it to a 32-component family vector $\boldsymbol{h}_F$. A further shared map acts on the index vectors of the chosen masters, and their mean gives the 32-component basis vector $\boldsymbol{h}_M$. This input identifies the basis available for reduction. The target's master coefficients, construction history and recorded seed choices remain outside the input.

Each candidate seed contributes its index and complexity information through a shared map that gives a vector $\boldsymbol{u}_b \in \mathbb{R}^{32}$ for candidate b. To associate a seed with particular target terms, we form

$$\begin{aligned} \omega_{bj} &= \frac{\exp(\boldsymbol{u}_b \cdot \boldsymbol{h}_j/\sqrt{32})}{\sum_{k=1}^{n_T} \exp(\boldsymbol{u}_b \cdot \boldsymbol{h}_k/\sqrt{32})}, \\ \boldsymbol{v}_b &= \sum_{j=1}^{n_T} \omega_{bj} \boldsymbol{h}_j. \end{aligned} \tag{67}$$

The weight ω_{bj} determines how much term j contributes to candidate b's description, and $\boldsymbol{v}_b$ is their weighted mean. This uses the scaled dot-product weighting of Ref. [17]. The weights sum to one over target terms for each seed.

The model then joins the mean and componentwise maximum of the term vectors with the pair, family, basis, seed and weighted-term vectors:

$$\begin{aligned} \boldsymbol{z}_b &= [\text{mean}_j\, \boldsymbol{h}_j,\ \max_j \boldsymbol{h}_j,\ \boldsymbol{h}_{\text{pair}}, \boldsymbol{h}_F, \boldsymbol{h}_M,\ \boldsymbol{u}_b, \boldsymbol{v}_b], \\ g_b &= F_\theta(\boldsymbol{z}_b), \qquad p_b = \frac{1}{1+\exp(-g_b)}. \end{aligned} \tag{68}$$

Here F_θ has a hidden layer with 64 components and one scalar output g_b. The other learned maps each use one layer with 32 components. All hidden layers use the hyperbolic tangent function. The implementation has 28,097 adjustable parameters and shares them across candidates, so reordering the candidate list only reorders the returned scores.

The quantity p_b represents the model's probability that $\boldsymbol{\sigma}_b$ belongs to the recorded sufficient seed set. Several seeds can contribute to the same reduction, so these probabilities are separate and need not sum to one. A high score ranks a seed for selection. The current data establish a valid reference set for each target; they do not establish the probability that a seed belongs to a globally minimal reduction. Exact reduction remains the criterion for deciding whether the selected seeds supply enough equations.

For each candidate we report probabilities for both possible labels:

$$\begin{aligned} P_\theta(y_b = 1 \mid \mathcal{T}, F, \mathcal{M}, \boldsymbol{\sigma}_b) &= p_b, \\ P_\theta(y_b = 0 \mid \mathcal{T}, F, \mathcal{M}, \boldsymbol{\sigma}_b) &= 1 - p_b. \end{aligned} \tag{69}$$

Here y_b is the reference label, F is the family definition and $\mathcal{M}$ is the chosen master basis. Label 1 means membership in the recorded sufficient seed set. Label 0 means absence from that set. The two class probabilities for one seed sum to one, while probabilities for different seeds remain separate.

The binary prediction uses a fixed threshold of one half:

$$\widehat{y}_b = \begin{cases} 1, & p_b \geq \frac{1}{2}, \\ 0, & p_b < \frac{1}{2}. \end{cases} \qquad q_b = \widehat{y}_b p_b + (1 - \widehat{y}_b)(1 - p_b). \tag{70}$$

The value $\widehat{y}_b$ is the returned label, and q_b is the model's estimated probability that this label agrees with the reference label. For example, $p_b = 0.90$ gives label 1 with confidence $q_b = 0.90$, while $p_b = 0.08$ gives label 0 with confidence $q_b = 0.92$. These values illustrate the output rule; they are not trained results. Candidate selection uses p_b, while q_b describes confidence in the returned binary decision.

The predicted seed set is

$$\widehat{\mathcal{S}}(\mathcal{T}) = \{\boldsymbol{\sigma}_b \in \mathcal{C} : \widehat{y}_b = 1\}. \tag{71}$$

Its size can vary between targets. Exact reduction must establish whether the identities from this set suffice to reduce the target. The probability q_b concerns one reference-membership decision; it is not a probability that the complete selected set gives a valid or minimum-cost reduction. Section 8 compares these confidence values with their observed agreement with the reference labels.

7.2 Training labels and the grouped data division

For each target, let $\mathcal{S}_\mathcal{T} \subseteq \mathcal{C}$ be the sufficient seed set used by its recorded reduction. The reference label for candidate b is

$$y_b(\mathcal{T}) = \begin{cases} 1, & \boldsymbol{\sigma}_b \in \mathcal{S}_\mathcal{T}, \\ 0, & \boldsymbol{\sigma}_b \notin \mathcal{S}_\mathcal{T}. \end{cases} \tag{72}$$

A zero label records absence from this particular set; another valid reduction can use that seed. Algebraic mass partial fractions carry no seed label. For example, a target whose reference uses the first and third of five candidates has

$$\boldsymbol{y}(\mathcal{T}) = (1, 0, 1, 0, 0). \tag{73}$$

The target coefficients and public family information enter the prediction, while this label vector enters the training loss.

We keep each family together and preserve the grouping of related mass and kinematic profiles described in Section 6.12. The expanded division contains 1,610,890 training targets in 11,963 families and 690,382 test targets in 5,137 families. Every loop order from one through twelve occurs in both sets. Each added mass profile stays in one set across all loop orders. The ratio applies to complete target examples, each with its full candidate list. Shared lower-sector integrals can occur across different profiles, and previously reserved families were also evaluated in earlier project stages. The latest mass profiles were assigned before the new parameter updates.

The training objective gives each target equal weight:

$$\mathcal{L}(\theta) = -\frac{1}{|\mathcal{D}_{\mathrm{train}}|} \sum_{\mathcal{T} \in \mathcal{D}_{\mathrm{train}}} \frac{1}{n_C(\mathcal{T})} \sum_{b=1}^{n_C(\mathcal{T})} \left[y_b \log p_b + (1 - y_b) \log(1 - p_b) \right]. \tag{74}$$

Here $\mathcal{D}_{\mathrm{train}}$ is the training set and $n_C(\mathcal{T})$ is the candidate count for target $\mathcal{T}$. All positive and zero labels enter this binary cross-entropy without additional class weighting. The threshold of one half determines reported decisions after the model supplies its probabilities.

7.3 Completed training and implementation checks

We continued the saved model and its AdamW optimizer on the expanded training set for twenty complete passes. The starting checkpoint had completed 20 passes over the preceding expanded collection. It also retains the earlier training lineage. The latest phase uses the enlarged collection and its own twenty-pass counter. It contains 32,217,800 target presentations and 1,012,000 parameter updates.

The architecture still has 28,097 parameters. AdamW uses a learning rate of 10^{-3}, weight decay of 10^{-4} and a maximum gradient norm of one [18]. Each update uses up to 32 targets from a training family. We change family and target order between passes and use the actual batch size for the final group. Masked batch calculations retain every target term, every ordered pair of distinct terms and every supplied seed. Comparisons with the individual-target calculation verified matching scores, losses and parameter derivatives across individual-integral and multi-term examples. Training uses four CPU threads, while inference uses one. A comparison on training examples verified matching scores and parameter derivatives across the selected thread counts.

The mean training loss changed from 0.0516102 in the first expanded-data pass to 0.008548661 in the twentieth. Figure 1 shows the complete history. These means include parameter changes within each pass and describe fitting on the training examples.

The checks verify target-label correspondence, membership of every recorded seed in the candidate pool, complete coverage during each pass, and equality of the published weights with the resumable checkpoint. The model retains the separate class probabilities and confidence rule in Eq. (70). Held-out examples supplied no gradient updates or threshold fitting.

The representation accepts up to sixteen indices, 512 target terms and 10,000 supplied candidates. The added twelve-loop examples reach the index limit. This capacity describes the input representation; the training evidence concerns the actual family domains defined above. Section 8 evaluates the frozen parameters on their reserved mass profiles.




Figure 1: Mean training binary cross-entropy during the twenty expanded-data passes. Each target has equal weight within the reported mean. The logarithmic vertical axis shows the training history; held-out examples do not enter this curve.

8 Testing the Seed-Selection Model

To measure seed selection after the expanded training, we froze the weights at the end of the twenty new passes and evaluated all 690,382 targets from 5,137 reserved families. The test contains 148,494 individual integrals and 541,888 integral expressions, with loop orders from one through twelve. It evaluates mass profiles excluded from parameter updates within the family domains of Section 6. The fixed threshold remains $p_b = 1/2$, and no test result changes the weights or the confidence map [19].

8.1 Reference agreement and seed ranking

The test supplies 76,536,115 candidate labels, of which 2,346,128 belong to the recorded sufficient sets. A true positive is a selected candidate with reference label one, while a false positive is a selected candidate absent from that set. A false negative is a recorded seed that the model omits. With these counts,

$$\text{precision} = \frac{\text{TP}}{\text{TP} + \text{FP}}, \qquad \text{recall} = \frac{\text{TP}}{\text{TP} + \text{FN}}, \qquad F_1 = \frac{2\,\text{precision}\,\text{recall}}{\text{precision} + \text{recall}}. \tag{75}$$

The pooled precision is 95.750%, recall is 96.892% and F_1 is 96.318%. The fraction of targets whose complete predicted set equals its recorded set is 84.332%. Candidate-label accuracy is 99.773%; the all-zero rule gives 96.935% because zero labels are frequent. Precision, recall and complete-set agreement therefore describe seed recovery more directly than accuracy alone [20].

To examine the scores without changing the threshold, we rank candidates by p_b and group candidates with equal scores. For a target T, let P_g and R_g be the precision and recall after including score group g in descending order. With $R_0 = 0$, the target average precision is [21]

$$\text{AP}_T = \sum_g (R_g - R_{g-1}) P_g. \tag{76}$$

Each increase in recovered reference seeds therefore weights the precision at that point. Averaging over targets with at least one recorded seed gives mean target average precision 99.090%. The first ten candidates recover, on average, 99.787% of recorded seeds and contain every recorded




Figure 2: Candidate decisions at the fixed threshold, with pooled precision, recall and F_1. Each confusion-matrix percentage is normalized within its reference-label row.

seed for 98.947% of targets in the corresponding nonempty-reference comparison. The score-curve calculation uses 4,096 fixed probability intervals; it supplies a descriptive curve and does not select a new operating threshold.




Figure 3: Pooled precision and recall as the score threshold varies. The marked point retains the fixed threshold of one half. The horizontal reference gives the positive-label fraction.

8.2 Confidence and dependence on the family

For a returned binary label, the model reports q_b from Eq. (70). We group decisions by this value and compare their mean confidence with the fraction matching the reference. Equality would place a group on the diagonal of Figure 5. These empirical comparisons assess the saved scores without fitting a calibration correction.

Figure 6 separates performance by family and loop order. The one-loop group has 681 families, the two-loop group has 406, and each remaining order has 405 held-out mass profiles. This




Figure 4: Recorded-seed recovery as the number of supplied highest-ranked candidates increases. The right panel requires every recorded seed to appear in the selected prefix. Individual integrals and integral expressions are also shown separately.




Figure 5: Reported confidence and observed label agreement, shown separately for returned labels zero and one. Marker area increases with the number of decisions in a group.

separation matters because the added vacuum families use different identities and candidate bounds from the earlier one-loop collection. Loop-order comparisons also reflect these differences in the mathematical domain. At one loop the pooled recall is 93.790% and F_1 is 92.181%; at twelve loops they are 97.334% and 97.300%, respectively. Across the groups from two through twelve loops, the lowest recall is 96.184% at $L = 6$. These missed reference seeds show why a proposed set still needs an exact sufficiency check before use in a complete reduction.




Figure 6: Distribution of mean target average precision across held-out families, and pooled seed precision, recall and F_1 at each loop order. The higher-loop groups cover the restricted vacuum mass profiles defined in the text.

8.3 Checks and interpretation

Independent checks reproduce the saved confusion counts and target counts, verify the prediction hashes and confirm that the weights remain fixed. All stored probabilities are finite and lie between zero and one. The mean time for input preparation and model inference is 1.6881 ms per target on the test allocation; this excludes a subsequent exact reduction.

The labels identify one recorded sufficient set. Other seed sets can also reduce the target, so disagreement with these labels does not by itself establish failure of the proposed reduction. The classification measurements above describe reference-set recovery and confidence. To determine whether the selected equations complete the target, we next use the saved predictions in Kira.

8.4 Sufficiency of the predicted seeds inside Kira

To determine whether the predicted seeds supply enough equations, we use Kira 3.1 to test whether each target belongs to the span of its specified masters modulo the available identities. This means that the target can be written as a linear combination of those masters after using the selected equations. We retain the frozen model, reserved families and threshold of one half from Eq. (71).

Let $\mathcal{E}_{\boldsymbol{\sigma}}$ contain the stored IBP identities from seed $\boldsymbol{\sigma}$, and let $\mathcal{B}$ contain the background identities, including partial fractions and symmetries. A supplied seed set $\mathcal{S}$ provides the equations

$$\mathcal{A}(\mathcal{S}) = \mathcal{B} \cup \bigcup_{\boldsymbol{\sigma} \in \mathcal{S}} \mathcal{E}_{\boldsymbol{\sigma}}. \tag{77}$$

Every selected seed contributes all its stored IBP identities. The reference seed labels, construction paths and master coefficients supply no equations to this test.

The sufficiency condition follows from linear algebra over the field $\mathbb{K} = \mathbb{Q}(\boldsymbol{x}, d)$ of rational functions in the kinematic parameters $\boldsymbol{x}$ and dimension d. Let V be the vector space with one formal basis vector for each integral in the supplied system, let $v_{\mathcal{T}}$ be the coefficient vector of the target, and let $\mathcal{R}(\mathcal{S})$ be the row space of the equations in $\mathcal{A}(\mathcal{S})$. Also let V_M be the span of the basis vectors for the specified masters. Then

$$\begin{aligned} \mathcal{T} = \sum_m r_{\mathcal{T}m} M_m \quad \text{using } \mathcal{A}(\mathcal{S}) \quad &\Longleftrightarrow \quad v_{\mathcal{T}} \in \mathcal{R}(\mathcal{S}) + V_M, \\ &\Longleftrightarrow \quad [v_{\mathcal{T}}] = 0 \quad \text{in } V/(\mathcal{R}(\mathcal{S}) + V_M). \end{aligned} \tag{78}$$

Here M_m is a specified master, $r_{\mathcal{T}m} \in \mathbb{K}$ is its reduction coefficient, and square brackets denote the equivalence class after removing combinations of available equations and master vectors. This condition tests whether such coefficients exist without requiring their full symbolic reconstruction. Sufficiency applies to the supplied target expression and permits exact cancellation among its terms.

We implement the condition through Kira's user-defined-equation interface, which accepts homogeneous linear systems with rational coefficients and uses Fermat for symbolic operations [8, 9]. Each target has an auxiliary variable $Z_{\mathcal{T}}$ and the input equation

$$Z_{\mathcal{T}} - \sum_{j=1}^{n_T} c_j(\boldsymbol{x}, d) I_{\boldsymbol{a}^{(j)}} = 0. \tag{79}$$

All terms in this equation come from the public target expression in Eq. (64). We add one unit row for each specified master vector. These rows impose $M_m = 0$ in the formal quotient used for the test, where every possible master combination represents zero. They do not change the physical values of the master integrals.

Kira reduces $Z_{\mathcal{T}}$ exactly in this system. A zero remainder establishes the condition in Eq. (78), and a nonzero remainder shows that the supplied equations leave an independent contribution outside the specified master span. The conclusion applies to rational functions at generic parameter values where their denominators are defined. A successful program exit alone does not establish sufficiency.

Different seed sets use separate copies of every integral variable so that they cannot share equations. Targets with the same selected set can share a system within one family. We retain every equation in a component connected to the target terms and remove only disconnected components. For each target we test its predicted set, the full candidate set $\mathcal{C}$, and the empty seed set. The full set checks the available fallback, while the empty set measures reduction through the target definition, master basis and background identities alone.

We independently reconstruct the selected row spaces from the original identities at each of the three stored finite-field samples. At each sample, sparse elimination checks membership after removing master columns and must agree with Kira's symbolic decision. Each nonzero symbolic remainder also has a regular sample with a nonzero value, which provides an exact witness that its coefficient does not vanish identically. The sample coordinates enter these checks after the symbolic calculation; reference master coefficients remain outside the full sufficiency test. For two pilot families, 765 target-and-seed-set comparisons also agree with reductions that retain the masters and compare their explicit rational coefficients.

8.5 Sufficiency results and the role of additional seeds

The test includes all 690,382 reserved targets from 5,137 families. The predicted sets supply enough equations for 652,517 targets (94.515%), while 37,865 (5.485%) have a nonzero remainder

outside the master span. The full candidate pool is sufficient for 690,382 targets (100.000%), and background identities alone suffice for 26,915 (3.899%). Within the coupled-vacuum subset, the predicted sets suffice for 595,919 of 618,240 targets (96.390%). Within the one-loop box subset, they suffice for 56,294 of 71,184 targets (79.082%). For the other one-loop samples, the predicted sets suffice for 89 of 380 bubble targets (23.421%), 152 of 431 triangle targets (35.267%), 60 of 144 propagator targets (41.667%), and 3 of 3 tadpole targets (100.000%). The overall fraction therefore depends on the mixture of tested family domains. All symbolic membership decisions agree with the independent row-space checks at the three stored samples. All requested targets have a recorded outcome, and the final evaluation has no unresolved solver or export errors [22].




Figure 7: Targets that belong to the specified master span after using the supplied identities, shown for predicted seeds, all candidate seeds and no IBP seeds. Each loop-order fraction uses every reserved target at that order. All three policies retain the same background identities.

Of the targets with sufficient predicted sets, 70,302 use a seed set different from the recorded reference set. This comparison shows that a model can supply enough equations through an alternative selection, so reference-set agreement and algebraic sufficiency measure different properties. The model selects 3.439 seeds per target on average. Across all target–candidate pairs, it selects 3.102% of the supplied candidates. This fraction describes selection within the bounded pools; it does not measure a runtime improvement over Kira's usual strategies.

The all-candidate control supplies a direct check of the fallback within the stored equation domain. A predicted set that leaves extra integrals requires further equations before we accept its reduction. We solve the full-pool control independently, which checks whether adding all candidates would supply a sufficient fallback. This test does not identify the smallest necessary addition or measure reuse of a preceding elimination. Its conclusions concern rational functions at generic parameter values, where the denominators in the reduction are defined.

These results establish algebraic sufficiency rates inside Kira for the stored identities. The user-defined interface is needed for the present family representation, including the dependent massive denominators of the higher-loop vacuum families. An insufficient outcome refers to the stored identities for the selected seeds. Additional valid IBP operators at the same seeds can enlarge that pool. Section 11 separately compares native Kira seeding through learned sector bounds with the stated native baselines. The grouped execution also shares work among targets with identical selected sets, so its elapsed times do not provide an end-to-end solver speedup measurement. The next section addresses the separate learned choice of an allowed elimination step.




Figure 8: The selected fraction of candidate seeds at each loop order, and the relation between reference-set agreement and seed sufficiency in Kira. Numbers above the bars are target counts. Different sufficient sets account for the difference between the two tests.

9 Machine Learning Model for Reduction Propagation

The seed model selects identities from which a reduction can proceed. Once these equations are available, the reduction model selects the next row operation from a supplied list of allowed steps. We use the current coefficient matrix and its integral labels to describe each choice, and the model returns a probability for every listed step. The step with the largest probability gives the proposed next operation. Exact arithmetic then updates the matrix, which supplies the input for the next choice. This section describes the model and its training on the reductions constructed in Section 6.

9.1 Current equations and allowed reduction steps

Let $A^{(n)}$ be the coefficient matrix after n reduction steps. A column j corresponds to an integral $I_{\boldsymbol{a}^{(j)}}$, and a row contains its coefficients in an identity or in the target expression currently being reduced. The chosen master basis specifies the columns protected from elimination. An action $a = (q, r, k)$ uses source row q to eliminate column k from destination row r:

$$A_{rj}^{(n+1)} = A_{rj}^{(n)} - \frac{A_{rk}^{(n)}}{A_{qk}^{(n)}} A_{qj}^{(n)}, \qquad q \neq r, \quad A_{qk}^{(n)} \neq 0, \quad A_{rk}^{(n)} \neq 0. \tag{80}$$

All other rows remain unchanged during this elementary step. If both rows are identities, this is an elementary row operation. If row r represents a target, row q must be a zero identity so that the target retains its value. The solver supplies the allowed action set $\mathcal{A}_n$, enforcing its integral ordering, master basis and row roles. The model ranks this finite list; completeness of the list remains the responsibility of the solver.

The stored examples describe a particular instance of this matrix. They contain one changing target row and the source identities available for eliminating its largest remaining nonmaster integral under Eq. (36). Each candidate specifies one of these identities, the target row and that integral. After a choice, the source identities remain fixed and the target row changes. The prediction interface also accepts several changing rows, while the present training data cover the stored target-row procedure. Section 12 tests the frozen policy on Kira's evolving selected

IBP matrix using admissible actions that retain its integral ordering [9]. This test changes the inference states while retaining the target-row training described here.

9.2 Information supplied to the model

For each allowed action, we construct a vector $\boldsymbol{f}_a$ from the current matrix, the pivot integral and the family definition. The pivot description includes its indices, sector membership, and the values of $r, s, t, n_{\mathrm{dot}}$ in Eq. (14). Descriptions of the source and destination rows give their nonzero counts, master content and the mean and largest integral complexities. A matrix summary gives its number of rows, columns and nonzero entries. The public family definition supplies the numbers of loops and kinematic parameters together with the propagators and scalar-product relations. We encode their written form through the same fixed signed token counts described in Section 7.1, using 32 components here. This encoding admits collisions between different groups of symbols. We transform nonnegative counts with $\log(1+v)$, where v is the count, and each signed index a_i with $\operatorname{sgn}(a_i)\log(1+|a_i|)$. The representation allows up to 16 indices and records which positions belong to the family. These definitions give 132 features for each candidate.

The current records supply coefficients in $\mathbb{F}_P$, the field of integers modulo a prime P. We use these coefficients to calculate the overlap of each source row with its destination, the number of terms that the proposed operation would cancel or introduce, and its immediate arithmetic count. For a source with n_q nonzero entries, this count is $1 + 2n_q$: one division and n_q multiplications and subtractions, using the convention in Section 6. These quantities require one sparse trial row update per action. They use only the current matrix and do not inspect later reduction steps or reference master coefficients. A symbolic coefficient can vanish at the chosen sample, so the model uses counts recomputed from the sampled rows. The data audit retains the distinction from the original symbolic support counts. Structural counts and integral descriptions carry this information into the model. The numerical size of a modular residue does not represent the magnitude of a real coefficient.

The representation compresses the supplied matrix into these features, so different states can have the same description. It includes local cancellation information and a summary of the candidate set. These quantities describe the current choices without enumerating complete reduction paths. Forming these features and evaluating the model contribute to the eventual runtime and must be included when measuring a reduction speedup.

9.3 Action probabilities and confidence

A shared map ϕ_θ converts each candidate vector into a 32-component vector,

$$\boldsymbol{h}_a = \tanh(W_1 \boldsymbol{f}_a + \boldsymbol{b}_1), \qquad \boldsymbol{u} = \frac{1}{|\mathcal{A}_n|} \sum_{a \in \mathcal{A}_n} \boldsymbol{h}_a, \qquad \boldsymbol{v} = \max_{a \in \mathcal{A}_n} \boldsymbol{h}_a. \tag{81}$$

Here θ denotes the adjustable parameters, W_1 is a learned matrix, $\boldsymbol{b}_1$ is a learned offset, and the maximum acts on each component separately. Sharing the map and combining candidates through averages and maxima makes the scores independent of their position in the supplied list [16]. The model joins $\boldsymbol{h}_a, \boldsymbol{u}, \boldsymbol{v}$ and applies a second map with 64 hidden components to obtain a scalar score $g_\theta(a)$. For a fixed family, master basis and finite-field sample, it returns

$$\begin{aligned} p_\theta(a \mid A^{(n)}, \mathcal{A}_n) &= \frac{\exp g_\theta(a)}{\sum_{b \in \mathcal{A}_n} \exp g_\theta(b)}, \\ \widehat{a}_n = \arg\max_{a \in \mathcal{A}_n} p_\theta(a), &\qquad q_n = p_\theta(\widehat{a}_n). \end{aligned} \tag{82}$$

Thus the probabilities sum to one over the supplied alternatives, and q_n is the reported confidence for the selected step. With one allowed step the probability is one by construction, which provides no evidence of learned discrimination. An empty candidate list returns no proposed operation; the solver must determine whether the reduction is complete or further identities are required.

Training gives these probabilities an interpretation as agreement with the recorded next choice, conditional on the supplied state and actions. Several choices can give valid reductions, and an alternative choice may even lead to a shorter sequence. The reference paths establish valid reductions and their recorded costs; they do not establish global minima. Section 10 compares this confidence with agreement on reserved choices. Confidence does not certify exactness, minimal cost or the success of a complete reduction. Equation (80) and the solver's checks retain responsibility for the algebra.

9.4 Training examples and separation from testing

We retain the same grouped family division used for the seed model: 11,963 families with 1,610,890 targets supply training records, while 5,137 families with 690,382 targets remain reserved for testing. Every state from one target stays with that target's family. We read the row before each recorded step and its complete stored list of admissible source equations. The chosen equation supplies the reference action $a_n^\star$. The row after the step and the stored operation counts check the data preparation but remain outside the predictive inputs. The target's construction history, final master coefficients and future choices also remain outside those inputs.

For the set $\mathcal{D}_{\text{choice}}$ of training states with at least two allowed actions, the objective is

$$\mathcal{L}_{\text{red}}(\theta) = -\frac{1}{|\mathcal{D}_{\text{choice}}|} \sum_{(A,\mathcal{A},a^\star)\in\mathcal{D}_{\text{choice}}} \log p_\theta(a^\star \mid A, \mathcal{A}). \tag{83}$$

Each such state has equal weight. States with one admissible action have zero loss and remain in the data audit. The recorded reference choice is the training label; absence of a label on another action does not establish that its reduction is invalid.

We use AdamW [18] with a learning rate of 10^{-3}, weight decay 10^{-4}, batches of 256 states and a gradient norm limit of one. We continued the saved expanded-data model and optimizer for twenty complete passes over the enlarged training states. The new phase retains the architecture and optimizer settings while adding 1,250 mass profiles at every represented loop order. Preparation replays every selected row operation with exact modular arithmetic and verifies its final recorded master row. Training shuffles states within bounded groups of families and retains complete resume states. The reserved families remain outside parameter updates and confidence fitting. Earlier project stages evaluated the preceding held-out families; the current experiment also reserves the newly assigned mass profiles at every added loop order.

9.5 Completed training and present scope

The expanded training set contains 14,684,059 recorded states from 1,610,890 targets in 11,963 families. Of these states, 5,840,122 supply at least two allowed actions and 8,843,937 supply one action. The records contain 26,775,999 candidate appearances. The unchanged model uses 132 features per candidate and has 10,529 adjustable parameters.

Preparation replays every reference row operation, checks continuity between steps and verifies the final master support. Symbolic coefficients can vanish at the sampled kinematic point, so the model uses the support of the actual sampled matrix. The audit records these differences without changing the exact symbolic references.

We continued the preceding expanded-data model and its AdamW optimizer for twenty complete passes over the enlarged data. Each new pass uses every training state with an action choice; a forced step has probability one and supplies no ranking decision. The new phase contains 116,802,440 choice-state presentations and 463,763 parameter updates. The preserved lineage contains thirty passes over the original smaller collection and twenty passes over the preceding 2,100-family collection. The latest twenty passes use the enlarged collection across all represented loop orders.

Mean training cross-entropy changed from 0.3823373 to 0.3804633 during this phase, while agreement with the recorded action changed from 99.841% to 99.895%. These values describe losses and choices encountered during parameter updates. Section 10 measures the frozen parameters on reserved families.

The implementation retains the original architecture, learning rate, gradient bound and state-batch limits. Training uses four CPU threads, while inference uses one. Parallel preparation reproduces the saved training features and labels exactly. Checks verify equal weights in the inference and resumable checkpoints, complete state coverage and the preserved optimizer lineage. The published implementation retains the inputs, learned parameters and exact reference records [23].

The training domain still consists of one changing target row and a fixed source-equation pool. The new records extend this domain through twelve loops for the coupled vacuum families specified above. They provide evidence about these allowed reduction steps; general sparse elimination inside Kira requires a separate integration and benchmark.

10 Testing the Reduction-Propagation Model

To test the model after twenty expanded-data passes, we froze its parameters and evaluated 690,382 targets in 5,137 held-out families. Every loop order from one through twelve occurs in this set. We first compared the predicted next step with the recorded choice, then allowed the model to choose a complete path from the initial target row. Both tests retain exact finite-field row operations [24].

10.1 Allowed steps and the comparison rule

At a given state, the candidates are the source identities whose leading nonmaster integral matches the target row's leading nonmaster integral. Both the learned policy and the comparison rule receive this same list and respect the recorded integral order. The source rows remain fixed while elimination changes the target row. This restriction makes the available actions and complete reference answers explicit.

For each allowed source row E, let u_E be the target row after the corresponding exact elimination. The local comparison rule selects the smallest tuple

$$(n_{\mathrm{nm}}(u_E),\ \mathrm{nnz}(u_E),\ 1 + 2\,\mathrm{nnz}(E),\ \mathrm{id}(E))\,. \tag{84}$$

Here n_{nm} is the number of nonmaster columns with nonzero coefficients, nnz is the total number of nonzero coefficients and $\mathrm{id}(E)$ is a fixed equation identifier used only to resolve ties. The third entry counts one division and one multiplication and subtraction for each source entry. The rule compares the immediate next rows; it does not search all complete reduction paths.

10.2 Next-step agreement and confidence

The reserved traces contain 6,364,695 states, including 2,558,472 with an action choice and 3,806,223 with one allowed action. On states with a choice, the learned model selects the recorded action in 95.845% of cases and places it among its first three candidates in 99.980%. Its selected action gives the same next sampled row as the reference in 95.846% of cases. The local rule selects the recorded action in 99.473% of these states.

When n_{tie} actions share the largest saved probability, the program selects one through its fixed identifier order. Such ties occur in 37.747% of choice states. We also assign credit $1/n_{\text{tie}}$ when the recorded action belongs to the highest-scoring set, and zero otherwise. Averaging this credit gives 74.506% reference agreement. This diagnostic describes the scores while retaining the stated deterministic choice rule for the actual reductions.




Figure 9: Next-step comparisons on states with at least two allowed actions. The uniform reference assigns equal probability to every available action. The tie-averaged result shares credit equally among highest-scoring tied actions. The same-row comparison permits different identities that produce the same sampled next row.

The model assigns a probability to every supplied action, with probabilities summing to one. We compare the selected action's reported probability with observed agreement after grouping predictions into ten fixed confidence intervals. Let $\mathcal{D}^{\text{test}}_{\text{choice}}$ be the set of held-out states with at least two allowed actions, and let $a^{\star}_{n}$ be the recorded action at state n. Applying the negative logarithmic loss in Eq. (83) to this set gives 0.400146. The calculation replaces probabilities below 10^{-38} by 10^{-38} when taking their logarithms.

To compare the full probability distribution with the recorded choice, we also calculate the multiclass Brier score [25],

$$B_{\text{test}} = \frac{1}{|\mathcal{D}^{\text{test}}_{\text{choice}}|} \sum_{n \in \mathcal{D}^{\text{test}}_{\text{choice}}} \sum_{a \in \mathcal{A}_n} \left[p_\theta(a \mid A^{(n)}, \mathcal{A}_n) - \mathbf{1}_{a=a^{\star}_{n}} \right]^2 . \tag{85}$$

Here $\mathcal{A}_n$ is the supplied action set and $\mathbf{1}_{a=a^{\star}_{n}}$ equals one for the recorded action and zero for every other action. We sum over all actions without dividing by their number, then give each state equal weight. The resulting score is 0.250632. The confidence comparison in Figure 10 uses the frozen scores without fitting a correction. A forced action has probability one, so these ranking and confidence comparisons exclude forced states.




Figure 10: Reported confidence and recorded-action agreement, with the number of choice states in each confidence interval. The diagonal represents equality between confidence and agreement.




Figure 11: Agreement across individual families and loop orders. Every higher-loop group uses held-out mass profiles of the restricted vacuum families. These comparisons include changes in the mathematical family domain as well as loop order.

10.3 Complete reductions and arithmetic work

For complete-path testing, the policy receives the initial target row and repeatedly selects an allowed identity until the row contains only protected masters or a stated failure condition occurs. Decisions use the first finite-field sample. We then replay the selected sequence at both additional samples and compare the resulting rows with the exact reference master coefficients evaluated at those points.

The learned policy matches all three sampled master expansions for 690,302 of 690,382 targets (99.988%). The local rule matches all three for 689,700 targets (99.901%). The respective numbers without this full three-sample agreement are 80 and 682. For the learned policy, 77 targets stop when the supplied pool has no allowed identity for the remaining leading integral, and 3 complete at the decision sample but fail an additional-sample check. The local rule gives 664 and 18 in these two categories. Agreement at the samples is the stated test criterion; the test does not reconstruct a new symbolic rational result from the learned path.




Figure 12: Complete target reductions at each loop order. The left panel requires agreement at the decision sample; the right panel requires agreement at all three samples.

We compare arithmetic counts on the 689,684 targets for which both policies pass all three samples and the reference count is nonzero. The learned policy uses fewer committed row operations than the local rule for 6,846 targets, the same number for 610,196 and more for 72,642. A committed operation changes the selected target row. Candidate trials used to construct model features or evaluate the local rule also perform arithmetic, so Figure 13 shows both accounting choices. The recorded path supplies a valid reference count without a proof that this count is minimal.

10.4 Timing, checks and scope

The mean attempted reduction time is 12.3438 ms per target for the learned policy and 0.6991 ms for the local rule. The learned policy therefore takes 17.657 times as long on this allocation. These times include action selection and committed elimination within the target-row experiment. We alternate policy execution order between targets and keep verification and disk output outside the timed interval. Four CPU workers on the same compute node process disjoint families, with one computation thread per worker. Both policies run in the same worker for each target. Figure 14 shows the timing distributions on the test allocation.

Independent checks reproduce probability summaries and replay the committed finite-field operations from the saved paths at the decision sample. They also verify the source coefficients,




Figure 13: Cumulative distributions of arithmetic counts relative to the recorded path, restricted to targets successful for both policies. The right panel also includes trial row operations used when choosing an action. Both horizontal axes use logarithmic scales.




Figure 14: Attempted target-row reduction times for the learned policy and local rule. Both receive identical initial rows, source pools and integral ordering.

data split and unchanged model hash. The tests distinguish agreement with a recorded next action from completion of an allowed alternative path.

The results concern the supplied equation pools and family domains. Every tested loop order also occurs in training, and related lower-sector integrals can occur in different mass profiles. Consequently, the experiment measures held-out profile performance within these domains. It does not establish globally optimal seed sets, globally minimal elimination paths or an end-to-end Kira speedup. Section 11 then measures complete symbolic reductions with Kira, including model and fallback costs.

11 Comparison with Kira

A useful learned choice must reduce the cost of obtaining the final master coefficients. The sufficiency test in Section 8.4 establishes which stored seed sets permit a reduction, while the preceding target-row test measures individual reduction paths. We now compare complete symbolic reductions with Kira's existing equation selection and seeding. The comparisons retain both trained models, the held-out families and the seed threshold of one half. The candidate seed lists and prescribed master bases are inputs; their earlier construction is outside the measured reduction costs.

11.1 Targets, baselines and exact checks

We use 19 held-out family instances: one restricted vacuum profile at each loop order from one through twelve, three box profiles, and one bubble, triangle, tadpole and two-loop propagator family. The three box profiles represent the smallest, middle and largest candidate-pool sizes in that domain. A fixed hash order selects the other profiles and the target expressions without consulting previous model outcomes. Nested batches contain 1, 4 and 16 targets, with batches of 1 and 3 for the three-target tadpole family. This gives 56 batch cases and 291 distinct targets. The restricted vacuum profiles retain the dependent denominators described in Section 6.12; their loop orders do not represent the complexity of general multiloop scattering.

For the supplied-equation comparison, Kira receives the connected part of the complete stored source pool and applies its own equation selection, forward elimination and back substitution. The learned seed method takes the union of the predicted seed sets for the requested batch and supplies the corresponding stored IBP identities together with the same background identities. If any target retains an integral outside the prescribed master basis, the method reruns the batch with the complete pool. Both attempts contribute to its cost. This comparison isolates selection from a common source library; generating that library is outside these timings.

For the row comparison, the learned model chooses source identities using a fixed finite-field sample, while Eq. (80) updates the target coefficients symbolically in $\mathbb{K} = \mathbb{Q}(\boldsymbol{x}, d)$. Kira then reduces any remaining terms. A second version applies the local rule from Section 10 through the same symbolic procedure. This control identifies the cost of the learned choice relative to the local choice. Both methods retain fixed source identities and a changing target row, which is the procedure covered by the training data.

We compare each final coefficient with its constructed rational reference and independently evaluate the coefficients and saved row operations at three finite-field points. The physical master coefficients remain present throughout this experiment. A reported completion therefore includes the full symbolic target expansion and its checks. Each batch-method pair runs three times on the same compute node, with the execution order rotated. Kira and the model each use one computation thread. At most two trials run concurrently on the cluster.

11.2 Learned seed bounds in native Kira

The seven families with independent propagator bases also permit native Kira equation generation. Kira reduces the component integrals, and its exact algebra combines their results into the requested target expressions. We record generation and reduction separately from this final combination. Native equation counts refer to the component reduction; the later combination has separate counts and contributes to every reported total time. For the default baseline, the seeding bounds are one above the largest values of r and s among the target components and prescribed masters. The restricted baseline also bounds n_{dot} one above its largest required value and uses Kira's subsector truncation with $l = N - s_{\max}$, where N is the number of propagators. A third control sets r, s and n_{dot} directly to the largest target/master values, uses the same subsector truncation, and falls back to the default bounds if needed. Both this control and the learned method reserve 60 seconds for the first native attempt and 100 seconds for its fallback, within the complete 180-second limit. These fixed settings retain Kira's own symmetry handling and equation selection [9]; they do not represent an exhaustive search over its settings.

To apply the seed model before native equation generation, let $\widehat{\mathcal{S}}_S$ be the predicted seeds in sector S. For every nonempty set, we pass the bounds

$$\begin{aligned} r_S &= \max_{\boldsymbol{\sigma}\in\widehat{\mathcal{S}}_S} r(\boldsymbol{\sigma}), \qquad s_S = \max_{\boldsymbol{\sigma}\in\widehat{\mathcal{S}}_S} s(\boldsymbol{\sigma}), \\ n_{\mathrm{dot},S} &= \max_{\boldsymbol{\sigma}\in\widehat{\mathcal{S}}_S} n_{\mathrm{dot}}(\boldsymbol{\sigma}). \end{aligned} \tag{86}$$

to Kira. These bounds enclose the selected seeds, and Kira can generate additional seeds within the bounds and inherited subsectors. Its own generated and selected equation counts therefore measure the resulting work. An incomplete first attempt triggers the default native bounds. This direct comparison repeats all four native methods on the largest fixed target batch in each of the seven families, giving 99 distinct targets and 84 trials. The learned method uses the same model and threshold as the supplied-pool test.

11.3 Measured cost and results

We record the complete elapsed time from process start to a checked result. It includes input loading, model loading, feature preparation, inference, exact algebra, any fallback, coefficient checks and output. We also record the time with the family already loaded and the model ready for use. This second quantity represents repeated use of prepared inputs; the complete process time retains the cost of starting the model. For a matched case, we compare the median of the three repeats and define

$$\rho_T = \frac{\operatorname{median} T_{\mathrm{learned}}}{\operatorname{median} T_{\mathrm{baseline}}}. \tag{87}$$

Thus $\rho_T < 1$ indicates a lower measured time for that case. Aggregate ratios use the geometric mean of the paired case ratios. Trials that reach their time or memory limit remain in the completion counts and are excluded from ratios that require two completed results.

We distinguish supplied equations, equations selected by Kira, logged forward insertions and coefficient-field operations. For a committed target-row step with n_q nonzero source entries, the last count is $1 + 2n_q$, as in Section 9. Feature construction also performs trial updates of candidate rows. These counts do not measure the internal polynomial work needed to simplify a rational coefficient. Runtime includes that work. Memory is the largest sampled sum of resident process memory for the driver, Kira and its algebra process; the sampling interval is 50 ms, and shared pages can contribute to more than one process's count. Every trial has a 180-second limit, a 1.5 GiB address-space limit per process and a 32 MiB scratch limit. The

comparisons use the existing symbolic Kira 3.1 build with Fermat. They do not benchmark finite-field reconstruction.

The main comparison contains 792 trials. The full stored-pool baseline completed 168/168, learned seeds completed 168/168, learned rows completed 168/168, and local-rule rows completed 168/168. On the 56 completed matched batch cases, learned seed selection gave complete-process and prepared-input time ratios of 1.720 and 1.116, respectively. It used the full-pool fallback in 24 trials. Across those batches, its supplied source-equation count, including fallback, was 0.251 times the baseline count, while the number of equations selected by Kira was 1.027 times the baseline. The distinction shows how Kira's existing selection changes the work left after an external seed choice. The learned method had lower complete-process median time in 0 of 56 batches and lower prepared-input median time in 15 of 56 batches.

The learned row procedure gave time ratios of 1.719 and 1.205 against the full stored-pool baseline over 56 matched cases. Its ratios against the local row rule were 1.520 and 1.043. Before the final Kira call, the learned row procedure completed every target in 54 of the 56 batches, while the local rule did so in 55. Kira completed the remaining terms in the other batches. For the 53 batch cases in which both row procedures themselves finished all targets before the final Kira call, their summed committed coefficient-operation counts were 19,401 and 18,881, giving a ratio of 1.028. This comparison excludes paths that left part of the reduction to Kira. The elapsed-time measurements retain all of that later work, as well as candidate feature preparation and exact coefficient simplification [26].

Kira's own equation selection removes much of the redundant input in the full-pool baseline. The learned seed filter reduces the supplied pool, and its measured complete cost includes the added model work and every fallback. Both learned methods have aggregate complete-process and prepared-input ratios above one in this comparison. The row-operation ratio also exceeds one relative to the local rule on the matched complete preprocessing paths. These results identify added cost in the current implementations and give no aggregate reduction in the stated time or committed-operation measures.




Figure 15: Matched time ratios relative to Kira with the full stored source pool. Each point uses a batch's three-repeat median. The left panel includes process and model loading; the right panel uses prepared family inputs and a loaded model. Short solid lines show the median case ratio; the dashed line denotes equal time.




Figure 16: Supplied source equations and equations selected by Kira for identical batches. Learned-seed counts include any full-pool fallback. Squares identify batches with fallback, and the diagonal denotes equal counts.




Figure 17: Sampled summed resident-memory ratios and committed coefficient-operation counts. Memory ratios use the largest recorded peak within each three-repeat group. The operation panel compares only batches that both row procedures completely reduced before the final Kira call. These counts exclude polynomial simplification and candidate-scoring work.

11.4 Native seeding results

The direct native-seeding comparison completed 21/21 learned trials, 21/21 default-baseline trials, 21/21 restricted-baseline trials and 21/21 target-index-bound control trials. Learned bounds required a default-bound fallback in 9 trials. For the 7 paired completed family batches, its complete-process and prepared-input time ratios against default native Kira were 1.596 and 1.344. Against restricted native Kira, the corresponding ratios were 1.671 and 1.373 over 7 paired batches. Against the control that sets bounds directly from target indices, the ratios were 1.425 and 1.141 over 7 paired batches. These measurements include native equation generation, exact reduction, target combination, coefficient checks and any repeated attempt.

The learned native method had lower complete-process median time in 0 of 7 matched batches against the default baseline, 0 of 7 against the restricted baseline and 1 of 7 against the target-index control. Across the completed paired batches, the ratios of summed initial equation counts were 0.624, 1.144 and 0.881, respectively. These counts include repeated attempts. The learned bounds generate fewer equations than the stated default bounds, and the restricted deterministic baseline generates still fewer equations on these batches. The learned method has aggregate complete-process and prepared-input time ratios above one against all three native controls. Thus the current native integration adds total cost under the tested settings.




Figure 18: Direct native-seeding comparison on the largest frozen batches in seven independent-basis families. Ratios compare learned sector bounds with the three stated native baselines. Equation counts sum the initial system sizes that Kira reports for each attempt; internal regeneration can perform additional work.




Figure 19: The methods using stored identities compared with native component reduction at the same targets and master basis. Native timings include equation generation and exact combination of the component results. This comparison changes the available source representation as well as the external method, so it does not isolate the benefit of learning.

Across both comparisons, all 876 trials produced a checked complete result within the stated bounds. The paired timing ratios above use three completed repeats for both methods. The recorded limits and three-repeat design bound the interpretation of small timing differences on the shared cluster.

These results describe the implemented policies and the stated symbolic Kira settings. The stored-pool tests reuse previously generated identities, and the native tests measure learned sector bounds that can include seeds beyond the model's selected set. The row comparison in this section acts on fixed source identities and target rows. Section 12 extends the test to changing identity rows inside Kira. General high-loop scattering families and finite-field reconstruction require further tests. Reduced input counts alone do not establish a speed improvement because equation selection, model execution, exact simplification and fallback all contribute to the total cost.

12 Learned Elimination Inside Kira's Evolving Matrix

The row comparison in Section 11 used fixed source identities to simplify target expressions before the final Kira call. To test the intended use inside the solver, we now apply the frozen row model during Kira's symbolic forward elimination. The input is the current selected IBP matrix, and every exact row update changes the state used for the next prediction. Kira continues to generate and select equations, preserve its integral ordering, normalize the triangular system and perform back substitution [9].

12.1 Choices in the current IBP matrix

We retain the matrix notation of Eq. (80). At step n, $A^{(n)}_{rj}$ is the coefficient of integral j in identity row r. Let $w(j)$ be Kira's ordering weight for integral column j, with larger weights denoting integrals to eliminate earlier. The leading column of a nonzero row r and the rows with a common leading column are

$$h_n(r) = \arg\max_{j:A^{(n)}_{rj}\neq 0} w(j), \qquad R^{(n)}_k = \{r : h_n(r) = k\}. \tag{88}$$

At each step we take the largest-weight column that leads at least two rows. If this column is k_n, the allowed choices are

$$\mathcal{A}_n = \{(q, r, k_n) : q, r \in R_{k_n}^{(n)},\ q \neq r\}. \tag{89}$$

Here q is the source row and r is the destination row. The prescribed master columns remain protected. A proposed elimination of a protected master, or a zero pivot at the public sampling point, causes the learned trial to fail its interface check.

The model assigns probabilities to every pair in Eq. (89) and selects the largest score. Kira then uses its existing symbolic update to calculate

$$A_{rj}^{(n+1)} = A_{rj}^{(n)} - \frac{A_{rk_n}^{(n)}}{A_{qk_n}^{(n)}} A_{qj}^{(n)}. \tag{90}$$

All these rows represent zero identities, so this operation preserves their solution space. The new destination row has a lower leading integral, or becomes zero and leaves the matrix. It can supply a source row in a later step. The next prediction therefore uses the updated identities throughout the matrix.

We use the saved 132-feature representation and model weights without retraining. The family definition, master labels and current rows supply the features; construction records and reference master coefficients remain outside the predictions. Rational coefficients at the fixed public finite-field point supply cancellation features. Kira and Fermat perform the actual row updates with symbolic rational coefficients. The process holding the model remains available during one forward solve, and it receives the initial matrix followed by each changed row. A system with no allowed row updates does not load the model.

12.2 Matched controls and measurements

We use the same seven families with independent master bases and 99 targets as the native comparison in Section 11. They include three one-loop box profiles, a one-loop bubble, triangle and tadpole, and a two-loop propagator. All methods use the same restricted native seed bounds, target components, preferred masters and symbolic output checks.

Four methods distinguish the learned choice from changes needed to measure it. Stock Kira uses the installed solver. Instrumented Kira retains that solver's forward algorithm and records its exact updates. The deterministic control uses the largest repeated leading integral defined above and selects a source by Kira's row-length and integral-order rule. A stable row identifier selects its destination. The learned method uses the same serial schedule and selects both rows from the allowed pairs. This control separates the model's decisions from the effect of the new schedule. Both methods return the triangular system to Kira for normalization and back substitution.

Each method runs three times per family on the same node, with rotated execution order and one computation thread. Complete elapsed time includes preparation, inference, exact algebra, target combination and coefficient verification. We also time the forward-elimination phase directly inside Kira and record model loading separately. The diagnostic quantity

$$T_{\text{fwd,load excluded}} = T_{\text{fwd}} - T_{\text{model load}} \tag{91}$$

subtracts that recorded loading interval; it retains feature construction, scoring, communication and exact row updates. It is a timing decomposition of these runs; a separate run with a preloaded model has not been measured. Ratios use three-repeat medians and the paired geometric mean of Eq. (87). Forward-stage ratios include only cases with actual row updates

in both methods. The tadpole batch needs no forward row updates and does not contribute to those phase ratios.

For each committed update, we retain the convention $1 + 2n_q$, where n_q is the source-row nonzero count. This counts coefficient-field operations and excludes the internal polynomial work in rational simplification. Elapsed time includes that work and the candidate trial updates used to prepare features. The tests keep the action capacity at 10,000, the matrix capacity at 10,000 rows and 250,000 nonzeros, and use bounded time and memory. These limits bound the systems and action sets tested here.

12.3 Exact checks and measured results

All 84 final trials produced the prescribed symbolic master coefficients. Independent evaluation of the archived native exports passed 3,564 checks of target coefficients at independent sample points, and the saved row updates passed 12,708 independent finite-field checks. The model made 1,413 choices across its repeated runs. In 465 choices, its source row had already changed in an earlier elimination. These records establish that the model acted on an evolving identity matrix [27].

The complete elapsed-time ratios for the learned method were 1.305 against stock Kira, 1.286 against instrumented Kira, and 1.274 against the deterministic control. Within forward elimination itself, the ratio against instrumented Kira was 276.149 over 6 active family batches. After subtracting the recorded model-loading interval, the ratio was 62.270. For those active batches, the native forward-stage medians ranged from 0.003267 to 0.076143 seconds, while the learned medians ranged from 3.061 to 6.909 seconds.

Summing one median operation count per family gives 5,771 coefficient operations for the learned method, 5,070 for instrumented Kira and 5,097 for the deterministic control. The corresponding learned and native row-update totals were 471 and 470. These sums count each family once, while the independent checks above cover all repeated runs. Figures 20 and 21 show the family-level measurements.




Figure 20: Complete checked reduction time and the forward-elimination time measured inside Kira. Bars show three-repeat medians. The forward panel uses a logarithmic time axis and separately shows the learned time after subtracting the recorded model-loading interval. The tadpole case has no row updates, so its forward time measures phase overhead. Box A, B and C denote profiles 0173, 0633 and 0156, respectively.




Figure 21: Committed row updates and coefficient-field operations for the same evolving matrices. Each update contributes $1 + 2n_q$ operations. The count excludes candidate scoring and polynomial simplification, whose costs remain in the time measurements.

12.4 Implications for the proposed reduction policy

This experiment tests learned choices inside Kira's changing selected IBP matrix. The measured cost includes the consequences of those choices for later rows and for the final exact reduction. The current model increases aggregate runtime, and its summed coefficient-operation count also exceeds the native count. Excluding model loading does not produce a forward-elimination speedup in this comparison.

Kira's native forward phase is already short for these selected systems. The added feature construction and scoring therefore have a small available time budget. The model was trained on target-row reductions with fixed source identities, so its application to changing identity rows also tests transfer beyond those training states. The results apply to the stated one- and two-loop families and a forward policy that preserves Kira's integral ordering. Larger independent multiloop systems, other admissible pivot-column choices and learned back-substitution order remain outside the present experiment.

13 Direct Seed Filtering and Lower-Cost Model Inference

The preceding comparisons show that a learned choice must save more algebraic work than its prediction costs. We therefore changed the interfaces between the frozen models and Kira, and measured the complete reductions again. The seed interface can now select individual seeds before Kira constructs their equations. We also tested a smaller set of row choices that follows the form of the reduction model's training examples. The original checkpoints remain unchanged.

13.1 Relating the predicted seeds to Kira's targets

A stored target can contain several integrals,

$$\mathcal{T}_\nu = \sum_{\boldsymbol{a}\in\mathcal{J}_\nu} c_{\nu\boldsymbol{a}}(\boldsymbol{x}, d) I_{\boldsymbol{a}}. \tag{92}$$

Here ν identifies a target, $\mathcal{J}_\nu$ is its set of component index vectors, and $c_{\nu\boldsymbol{a}}$ is the known coefficient of each component. The native interface asks Kira to reduce these components and then combines their reductions with exact algebra. This procedure provides two possible inputs for the seed model: the complete expression $\mathcal{T}_\nu$, or each component $I_{\boldsymbol{a}}$ with coefficient one.

Let $\mathcal{C}$ be the stored candidate seed pool and let $p_\theta(\boldsymbol{b} \mid \mathcal{T}_\nu)$ denote the frozen model's score for seed $\boldsymbol{b}$, with the family and chosen masters also supplied. For a threshold τ, the expression-based seed set is

$$\widehat{\mathcal{S}}_{\mathrm{expr}}(\tau) = \bigcup_{\nu} \{\boldsymbol{b} \in \mathcal{C} : p_\theta(\boldsymbol{b} \mid \mathcal{T}_\nu) \geq \tau\}. \tag{93}$$

The component-based set instead uses

$$\widehat{\mathcal{S}}_{\mathrm{comp}}(\tau) = \bigcup_{\boldsymbol{a}\in\bigcup_\nu \mathcal{J}_\nu} \{\boldsymbol{b} \in \mathcal{C} : p_\theta(\boldsymbol{b} \mid I_{\boldsymbol{a}}) \geq \tau\}. \tag{94}$$

Components already in the prescribed master basis need no prediction. A seed set sufficient for the combined expression can differ from a set sufficient for all components separately, since terms can cancel in Eq. (92). Both interfaces therefore require a check of the final expression in the prescribed master basis.

We also test a local enlargement of a predicted set,

$$\mathcal{N}_1(\mathcal{S}) = \left\{ \boldsymbol{b} \in \mathcal{C} : \min_{\boldsymbol{a} \in \mathcal{S}} \sum_{i=1}^{N} |b_i - a_i| \leq 1 \right\}. \tag{95}$$

Here N is the number of family indices. This rule adds candidate seeds that differ by one unit in one index. It supplies nearby IBP relations without using the reference reduction. It gives no general proof that the set suffices.

13.2 Filtering before equation construction

The earlier native adapter represented predictions by sector bounds. Those bounds include intermediate seeds even when the model omitted them. The new interface still supplies bounds that contain the chosen seeds, but it also checks each seed vector before Kira constructs its IBP equations. A vector outside the selected set contributes no IBP equations through this call. Kira retains its symmetry handling, equation selection, exact elimination and back substitution [9]. The audit records both the allowed seed vectors and the vectors that the generator actually used.

The model scores and the reference master coefficients serve separate purposes. Predictions use only public family, target, master-label and candidate information. After reduction, we check whether the target contains any integral outside the prescribed master basis. An incomplete learned attempt triggers a standard restricted native calculation within the remaining time allowance. The final symbolic coefficients are then compared with the recorded exact answer. Prediction, preparation, unsuccessful attempts, fallback, target combination and exact checks all contribute to the measured complete time.

13.3 Reducing prediction costs and choosing a source row

We exported the trained weights to a NumPy implementation of the same layers. This removes the need to import the training framework for each reduction, and it reuses the family, master and candidate embeddings within a target batch. On 64 development targets, the seed probabilities differed from the original implementation by at most 4.18×10^{-6}, and every decision at threshold 0.5 agreed. Separate bounded feature checks verified the exported row network. These checks concern numerical inference; exact reduction still comes from Kira and the final coefficient checks.

For the row model, we first retained the full changing-matrix interface of Section 12 with the exported network. We then restricted each decision to a source row for one current destination. Using the leading-column group $R^{(n)}_{k_n}$ defined there, the largest row identifier selects the destination r_n, and the model scores

$$\mathcal{A}^{\mathrm{source}}_n = \{(q, r_n, k_n) : q \in R^{(n)}_{k_n},\ q \neq r_n\}. \tag{96}$$

The feature input contains the current rows in this group, with the destination assigned the target role. Thus the model sees one changing destination and its allowed sources, as in its training examples. Kira applies the selected exact update from Eq. (90). The source can itself have changed in an earlier step. The candidate count falls from $g(g-1)$ to $g-1$ for a group of g rows, while Kira's ordering still fixes the pivot column. If the group contains only two rows, the supplied action set has one element, so we apply that forced action without evaluating the network.

We also implemented the source-row network inside Kira's compiled reduction code. Each choice reads the current rows directly, samples their rational coefficients at the fixed finite-field

point and forms the same input features. The trained weights and features retain their single-precision values, while the compiled layer arithmetic uses double precision. An independent implementation with the same arithmetic precision checks the probabilities, and development tests also compare selected sources with the original single-precision network. This numerical prediction only selects a valid source; Kira continues to perform the rational row update exactly.

The compiled interface removes per-choice communication with a Python process. It retains an audit of chosen rows and their probabilities, and the measured time includes this audit. A combined method applies both the learned seed filter and the compiled row policy during the same reduction. An incomplete seed attempt uses the same exact fallback rule as the seed-only method.

This restriction changes the model's supplied state and action set. Its purpose is to reduce prediction work and test transfer to a closer training configuration. It does not establish an optimal elimination order, and its benefit must be measured against Kira's native choices.

13.4 Checking and expanding an incomplete seed set

In separate development trials, we tested whether Kira's initial finite-field master check could reject an incomplete seed set before symbolic elimination [9]. This check compares the integrals left by the generated system with the prescribed master basis. A rejected set can then be enlarged before Kira starts the more expensive symbolic calculation. The final coefficients still require exact checks, since a numerical rank check alone does not prove the full symbolic reduction. We retained the frozen policies in the reserved comparison while testing these extensions.

For the first expansion rule, we rank each candidate seed by its largest model score across the supplied expressions,

$$Q_\theta(\boldsymbol{b}) = \max_\nu p_\theta(\boldsymbol{b} \mid \mathcal{T}_\nu). \tag{97}$$

We begin with the first $k_0 = 32$ seeds and, after a rejected master check, increase the budget according to

$$k_{j+1} = \min(2k_j, |\mathcal{C}|). \tag{98}$$

Here j is the number of completed expansion steps and $\mathcal{C}$ is the candidate pool defined above. A control ranks seeds by their smallest index distance to a component of a target expression, and uses the same budget rule. The full candidate pool and restricted native seeding provide two further controls.

A second rule begins with 64 seeds and uses the additional integrals returned by the master check as new model inputs. Each such input contains one integral with coefficient one. We add its four highest-ranked unused candidates and repeat the check, using the full pool after five rejected checks. A distance-based control applies the same expansion to the same additional integrals. These checks require every component to reduce in the prescribed basis, which can be stricter than reducing the complete expression when terms cancel.

The 26 development trials gave 23 exact completions and three bounded incomplete calculations. The latter used 64-target batches and affected the native control and both learned variants in the initial check experiment. All completed outputs passed 1104 independent finite-field target checks. Across four complete 16-target comparisons, the doubling rule with learned ranking took 1.022–1.422 times the native control's complete time. In the subsequent residual-driven trial, learned ranking reached a complete basis with 71 seeds, while the distance control used 121. Its complete-time ratio against native seeding was 0.996. These are single development measurements; they do not establish a repeatable speedup for either expansion strategy [28].

13.5 Development, validation and reserved comparisons

We selected family instances before the new timing comparisons. Development and adapter-validation instances use separate kinematic groups from the original model-training partition. The reserved cost-test instances come from the original test partition, and their kinematic groups exclude every box group in the earlier cost comparison. The network weights remain fixed throughout this selection. The adapter-validation families belong to the original training partition, so this stage selects an interface configuration and does not measure generalization of the network itself. We performed development comparisons on three of the reserved development instances, selected the seed configuration on six validation instances and then froze the policy before testing twelve instances from six reserved kinematic groups.

All new native cases use symbolic reduction of one-loop box families with independent propagator bases. Each case uses the same target expressions and master basis for every method. Controls include restricted native seed bounds, bounds taken directly from target indices, and the full stored candidate pool with the individual-seed filter. These controls separate the learned selection from changes to seed bounds or equation generation.

Every trial uses one computation thread with explicit time, memory and scratch limits. We increased the array allowance from two simultaneous jobs to four and then eight after checking the available node memory and project storage. This changed the scheduling of independent trials while preserving their individual resource limits and frozen policies. Methods run in rotated order on the same node for each family and target-batch size. The retained-evidence limit interrupted some batches before a new trial could start; after lossless archive recompression, we resumed the missing trials on their original nodes and retained every completed observation. Every reserved method receives the same initial 160-second native calculation allowance within a 180-second complete-process limit. The memory and scratch limits are also the same. We retain failed trials and report their completion status. The validation rule assigns the 180-second total cap to an incomplete trial when choosing the learned seed configuration. This capped score is a selection rule; it is not a measured time for a completed reduction. The reserved comparison uses the frozen configuration, five repetitions and batches of 16 and 64 stored target expressions. After an unsuccessful attempt, the remaining identical repetitions for that method and batch are marked as skipped. Skipped repetitions receive no measured time. Timing ratios require five successful repeats for both methods, while completion and failure counts retain every attempted case.

13.6 Reserved results and exact checks

The frozen comparison contains 720 planned records across twelve family instances, two target-batch sizes, six methods and five repetitions. We executed 616 trials and obtained 590 exact completions; the remaining 26 executed trials exceeded a resource limit or failed to complete. The early-stop rule left 104 repetitions unexecuted. These skipped records contain no timing measurement. The retained inputs, policy choices, successful reductions and failure records accompany the data release [28].

Validation selected the complete target expression with threshold $\tau = 0.01$. This configuration and both trained checkpoints remained fixed during the reserved tests. Each method used the same master basis and targets in a batch.

For the three controls, restricted native Kira produced 105 exact completions, 3 failed trials and 12 skipped repetitions, the target-bound control produced 100 exact completions, 4 failed trials and 16 skipped repetitions, and the full candidate-pool control produced 105 exact completions, 3 failed trials and 12 skipped repetitions. These counts describe the bounded experiment and

do not measure whether an unlimited calculation would complete.

Successful restricted-native trials took 10.54–112.46 seconds for the complete checked calculation. This range includes different family instances, target-batch sizes and CPU models. The paired ratios compare methods on the same node within each batch.

For the learned methods, the learned seed filter produced 100 exact completions, 4 failed trials and 16 skipped repetitions, the compiled row policy produced 105 exact completions, 3 failed trials and 12 skipped repetitions, and the combined method produced 75 exact completions, 9 failed trials and 36 skipped repetitions. Completed seed and combined trials used the standard fallback 30 and 50 times, respectively.

Every completed final expression matched its recorded rational master coefficients. The independent audit performed 67,920 additional master-coefficient sample checks and 65,355 exact-row sample checks. It checked 11,405 compiled model choices and 10,380 forced source actions. Trace checks cover completed native attempts; 55 failed attempts had incomplete traces. The final coefficient checks still apply to any successful fallback. Input and checkpoint hashes agree with the values frozen before testing.

13.7 Complete reduction time and algebraic work

For each family and batch size, we take the median of five successful repetitions. We then form the ratio of learned time to control time and report the geometric mean across complete paired batches. A ratio below one means a lower measured time. We resample complete kinematic groups 10,000 times to obtain descriptive 95% intervals, keeping related profiles and batch sizes together. These intervals describe the completed subset of this small collection; failed and skipped trials remain in the completion counts above.

Restricted native Kira completed all five repetitions in 1 batches where the learned seed filter did not, while the learned seed filter completed all five repetitions in 0 batches where that control did not.

The learned seed filter has a complete-time ratio of 1.295 (descriptive 95% interval 1.156–1.542; 20 batches) against restricted native Kira. Its native-calculation subtotal, including seed prediction when used, has ratio 1.400 (descriptive 95% interval 1.201–1.816; 20 batches). The subtotal excludes input preparation, final target combination and verification, which remain included in the complete time.

Restricted native Kira completed all five repetitions in 0 batches where the compiled row policy did not, while the compiled row policy completed all five repetitions in 0 batches where that control did not.

The compiled row policy has a complete-time ratio of 1.024 (descriptive 95% interval 0.998–1.053; 21 batches) against restricted native Kira. Its native-calculation subtotal, including seed prediction when used, has ratio 1.025 (descriptive 95% interval 1.001–1.078; 17 batches). The subtotal excludes input preparation, final target combination and verification, which remain included in the complete time.

Restricted native Kira completed all five repetitions in 6 batches where the combined method did not, while the combined method completed all five repetitions in 0 batches where that control did not.

The combined method has a complete-time ratio of 1.983 (descriptive 95% interval 1.575–2.476; 15 batches) against restricted native Kira. Its native-calculation subtotal, including seed prediction when used, has ratio 2.289 (descriptive 95% interval 1.247–3.673; 8 batches). The subtotal excludes input preparation, final target combination and verification, which remain included in

the complete time.

Against the target-bound control, complete-time ratios are 0.902 (descriptive 95% interval 0.711–1.163; 20 batches), 0.712 (descriptive 95% interval 0.597–0.864; 20 batches), 1.415 (descriptive 95% interval 0.902–2.160; 14 batches), in seed, row and combined order. Against the full candidate-pool control, the corresponding ratios are 1.317 (descriptive 95% interval 1.167–1.569; 20 batches), 1.040 (descriptive 95% interval 1.016–1.061; 21 batches), 2.028 (descriptive 95% interval 1.565–2.616; 15 batches). Each ratio uses its own complete paired cohort, so comparisons with different failure patterns can contain different batches.

The learned seed filter has a generated-equation ratio of 0.168 (descriptive 95% interval 0.097–0.294; 20 batches), a selected-equation ratio of 0.982 (descriptive 95% interval 0.797–1.205; 20 batches) and a forward-update ratio of 3.575 (descriptive 95% interval 2.647–5.211; 20 batches) against restricted native Kira. These are counters from the native reduction passes, including completed fallback passes.

The compiled row policy has a generated-equation ratio of 1.141 (descriptive 95% interval 1.032–1.275; 21 batches), a selected-equation ratio of 1.141 (descriptive 95% interval 1.032–1.275; 21 batches) and a forward-update ratio of 0.905 (descriptive 95% interval 0.840–0.972; 17 batches) against restricted native Kira. These are counters from the native reduction passes, including completed fallback passes.

The combined method has a generated-equation ratio of 0.462 (descriptive 95% interval 0.254–0.745; 15 batches), a selected-equation ratio of 1.341 (descriptive 95% interval 1.080–1.582; 15 batches) and a forward-update ratio of 2.363 (descriptive 95% interval 1.041–4.534; 8 batches) against restricted native Kira. These are counters from the native reduction passes, including completed fallback passes.

Generation counters count equations reported in successive generation passes and can include repeated equations. A forward update is one committed elimination step; this count does not measure every polynomial or rational-function operation. Failed attempts can have truncated work counters, so the complete time and completion status remain the primary measures.





Figure 22: Learned-to-control time ratios in the reserved native comparison. The upper panel includes the complete checked reduction, and the lower panel shows the native subprocess subtotal plus seed prediction. Points show geometric mean ratios and lines show descriptive intervals obtained by resampling kinematic groups. The label n gives the number of paired batches with five successful repeats for both methods.






Figure 23: Generated-equation and forward-update ratios on complete paired batches. The controls and cohort labels follow Fig. 22. These counters measure reported generation work and committed updates, while symbolic coefficient complexity can change the cost of each update.

13.8 Numerical inference and scope of the result

The compiled-model development audit checked 256 action feature vectors and 2,247 sampled coefficients. The maximum feature difference was 0, and the largest probability difference from the independent double-precision calculation was 1.41×10^{-13}. All selected sources agreed with the original single-precision model in these development trials. The separate maximum probability difference from that original arithmetic was 1.6×10^{-05}.

The largest sampled process-tree memory was 0.506 GB, and the largest trial scratch directory was 49.29 MB. The bounded runs kept their scientific records and model files on Hoffman; the report contains the derived plots and results.

The complete paired comparisons do not show a lower aggregate runtime than restricted native Kira for these learned methods. Lower inference costs alone do not ensure that the chosen seeds and rows save enough algebraic work. The new native tests cover one-loop boxes and do not establish performance on independent high-loop scattering families. The existing weights were trained to recover recorded seed sets and row choices, and Section 14 reports a separate cost-trained policy on native Kira trajectories.

13.9 Transfer to a two-loop propagator family

We also applied the unchanged interfaces to the massless two-loop propagator family used in the earlier cost comparisons. Its five independent family indices fit the compiled row interface. We fixed two batches of 16 and 64 stored target expressions and all policies before this transfer calculation. Each method uses five rotated repetitions, the same master basis and the same time and memory limits. Storage-interrupted trials resume on their original node, with earlier observations preserved. Because this family appeared in earlier comparisons, this experiment measures transfer of the revised implementation and does not establish generalization to a newly unseen family.

Alongside native seeding and the full candidate pool, we include a deterministic source-row control using the same compiled reduction structure. This control selects a source by row length and integral ordering within the same changing leading-column group. Comparing the learned row policy with this control separates the source choice from changes to the compiled reduction structure. Every completed reduction receives the same exact coefficient check and an independent finite-field check.

The transfer experiment contains 60 measured trials among 60 planned records, with 60 exact completions. The independent audit performed 7,200 target-coefficient checks and 2,355 row-update checks.

For 16 targets, the native control's median complete time was 12.003 seconds. The learned seed filter gave a time ratio of 0.992 with descriptive interval $[0.962, 1.030]$; the learned source-row policy gave a time ratio of 0.991 with descriptive interval $[0.984, 1.022]$; the combined policy gave a time ratio of 0.976 with descriptive interval $[0.961, 0.996]$. In the matched controls, the learned seed filter relative to the full pool had ratio 1.051 with interval $[1.024, 1.072]$ and the learned source choice relative to the deterministic compiled control had ratio 0.987 with interval $[0.979, 1.034]$.

For 64 targets, the native control's median complete time was 12.770 seconds. The learned seed filter gave a time ratio of 1.758 with descriptive interval $[1.744, 1.777]$; the learned source-row policy gave a time ratio of 0.976 with descriptive interval $[0.964, 0.992]$; the combined policy gave a time ratio of 1.755 with descriptive interval $[1.740, 1.777]$. In the matched controls, the learned seed filter relative to the full pool had ratio 1.907 with interval $[1.880, 1.920]$ and the

learned source choice relative to the deterministic compiled control had ratio 0.987 with interval $[0.952, 1.012]$.

The compiled learned-row pipeline reduced the median complete time for 64 targets from 12.770 to 12.460 seconds, a measured reduction of 2.4%. Its ratio against the deterministic compiled control has an interval that includes one, so this experiment does not resolve a benefit caused by the learned source choice itself. The full-pool control was faster, at 11.773 seconds. For 16 targets, the combined pipeline reduced the native median by 2.4%, but the full-pool control again completed sooner. For 64 targets, every learned-seed and combined trial required fallback, whose cost is included in the reported time. These observations establish limited gains relative to the stated native baseline and also identify stronger deterministic controls.

Figure 24 shows all complete paired comparisons. A ratio below one denotes a lower median complete time. The intervals come from 10,000 paired resamples of the five repetitions and describe repeat-to-repeat variation within this one family. They do not measure uncertainty across different integral families. Incomplete pairs remain in the completion counts and receive no timing ratio [28].

13.10 Applying the seed model to complete target expressions

The native interface reduces each component of Eq. (92) before combining the result. We also applied the fast seed model directly to that complete expression, using Kira's supplied-equation mode. This tests the form of the target used to train the seed model and allows cancellations between its components during the reduction.

Let $\mathcal{E}_{\boldsymbol{b}}$ be the stored IBP identities generated from candidate seed $\boldsymbol{b}$, and let $\mathcal{E}_{\mathrm{bg}}$ contain the stored symmetry and other background identities. The selected equation set is

$$\mathcal{E}(\mathcal{S}) = \mathcal{E}_{\mathrm{bg}} \cup \bigcup_{\boldsymbol{b}\in\mathcal{S}} \mathcal{E}_{\boldsymbol{b}}. \tag{99}$$

For each requested expression, we add its defining relation

$$\mathcal{T}_\nu - \sum_{\boldsymbol{a}\in\mathcal{J}_\nu} c_{\nu\boldsymbol{a}} I_{\boldsymbol{a}} = 0. \tag{100}$$

Kira eliminates the supplied system with the target expressions ordered above their component integrals and the prescribed masters preferred at the end of the ordering. It therefore obtains the master expansion of $\mathcal{T}_\nu$ in one exact solve. The same public identity pool, target definitions and master basis enter every compared method.

The model takes the union of candidates whose score reaches $\tau = 0.01$, using the unchanged weights and the fast inference implementation. We tested this set both with and without an early finite-field master check. An incomplete selected system triggers a full-pool calculation within the remaining time allowance. The early check compares the remaining integrals with the prescribed master basis; exact final coefficient checks still determine whether the requested reductions agree with their recorded answers. A global master check can require more relations than a particular target combination needs.

These calculations begin with stored IBP identities, whose prior generation cost is excluded for every method. The measured complete time includes loading those inputs, prediction, equation selection and export, Kira's exact calculation, admission checks when used, failed attempts, fallback and final verification. Thus the result concerns repeated reduction from a common identity pool. It does not measure native generation of a new family's equations.

The separate development and adapter-validation collection contains 80 trials, with 74 exact completions and 6 incomplete calculations. Independent checks evaluated 2,013 target coeffi-




Figure 24: Complete-time ratios in the two-loop transfer comparison for 16 targets (upper panel) and 64 targets (lower panel). Points show ratios of five-repeat medians, and bars show descriptive paired-repeat intervals. All times include prediction, target preparation, exact reduction, combination, checks and any required fallback.

cients at stored finite-field points. The six adapter-validation family instances belong to the original training partition and use two batch sizes, one and sixteen targets. We retained every measured cost and selected a learned interface only when its geometric mean complete-time ratio to the full-pool control was below one and it preserved every control completion.

The validation ratio without the early master check was 1.113 across 11 complete paired batches. The full-pool control completed 0 additional batches that this learned interface did not complete. These single validation measurements select the interface and do not establish a repeatable timing gain.

The validation ratio with the early master check was 0.930 across 11 complete paired batches. The full-pool control completed 0 additional batches that this learned interface did not complete. These single validation measurements select the interface and do not establish a repeatable timing gain.

13.11 Reserved tests of complete-expression reduction

Validation selected the early master check. We froze this choice before applying it to the twelve original-held-out box instances used in the native comparison. The network weights and threshold remain fixed. Each instance supplies batches of one and sixteen target expressions, with five rotated repetitions per method on the same node. These are reused physical families and constructed targets; the new comparison tests the revised interface on original-held-out model data.

The controls use the full stored identity pool and a fixed set of 64 seeds ranked by their smallest index distance to any target component. The distance control uses the same exact reduction and full-pool fallback as the learned method. This first distance control proceeds directly to symbolic elimination, while the selected learned method uses the early master check. Their time ratio therefore includes both seed selection and the difference in admission checks.

The frozen plan contains 360 records. We executed 348 trials and obtained 345 exact completions; 3 measured trials failed to complete within the bounds, and 12 remaining repeats were skipped after an earlier failure. Every completed master expansion matched its exact reference, and the independent audit checked 8,460 target coefficients directly against the exported Kira reductions. Skipped repetitions have no assigned runtime.

The learned interface produced 115 exact completions, 1 failed trial and 4 skipped repeats. Completed trials used fallback 25 times.

The full-pool control produced 115 exact completions, 1 failed trial and 4 skipped repeats. Completed trials used fallback 0 times.

The distance control produced 115 exact completions, 1 failed trial and 4 skipped repeats. Completed trials used fallback 55 times.

We form a median from five successful repetitions for each method and batch, and take geometric mean ratios over complete paired batches. Descriptive 95% intervals resample the six kinematic groups 10,000 times, preserving the relationship between profiles and batch sizes. Completion losses remain separate from these ratios.

The learned interface has a complete-time ratio of 0.944 against the full-pool control, with descriptive interval $[0.863, 1.042]$ across 23 paired batches. The control completed all repeats in 0 additional batches, and the learned method completed all repeats in 0 additional batches.

The learned interface has a complete-time ratio of 0.604 against the distance control, with descriptive interval $[0.534, 0.678]$ across 23 paired batches. The control completed all repeats in

0 additional batches, and the learned method completed all repeats in 0 additional batches.

The observed geometric mean complete time is 5.6% lower than the full-pool Kira control on batches where both methods completed all five repetitions. Because the descriptive interval includes one, the aggregate timing gain across both batch sizes remains uncertain. The result applies to these constructed target expressions and their existing identity pools; it does not establish a speedup for general multiloop amplitude reductions [28].




Figure 25: Complete-time ratios for direct reduction of complete target expressions. Points show geometric means of five-repeat median ratios, and intervals resample kinematic groups. The label n gives the number of complete paired batches. Failed and skipped trials remain in the completion counts.

13.12 Using the same master check for both seed selectors

The preceding distance control enters symbolic elimination directly, while the learned method first checks the selected master basis. To compare seed choices under the same admission procedure, we fixed a second confirmation in which both selected sets receive the same early check and full-pool fallback. The learned scores, threshold, distance rule, twelve family instances and target batches stay unchanged. The full-pool Kira control again uses its standard supplied-equation reduction. We retained every measurement in the first comparison.

Each method again uses five rotated repetitions on the same node within a family and batch. This new comparison contains independent timing repetitions of the same physical cases, so it checks the effect of matching the admission procedure and does not introduce new integral families. Complete times and descriptive intervals follow the definitions in the preceding subsection.

The comparison with the same early check contains 360 records, of which 348 are measured trials. It produced 345 exact completions, 3 incomplete measured trials and 12 skipped repetitions. Independent checks evaluated 8,460 target coefficients against the raw Kira exports. All completed reductions matched their exact reference coefficients.

The learned method completed 115 trials exactly, with 1 failed trial and 4 skipped repetitions. Its completed trials required fallback 25 times.

The full-pool control completed 115 trials exactly, with 1 failed trial and 4 skipped repetitions. Its completed trials required fallback 0 times.

The distance control with the early check completed 115 trials exactly, with 1 failed trial and 4 skipped repetitions. Its completed trials required fallback 55 times.

Across both batch sizes, the learned complete-time ratio to the full-pool control is 0.932, with descriptive interval $[0.845, 1.031]$ across 23 paired batches. The control completed 0 additional batches, while the learned method completed 0 additional batches.

For batches of 1 target, the learned complete-time ratio to the full-pool control is 0.914, with descriptive interval $[0.871, 0.958]$ across 12 paired batches. The control completed 0 additional batches, while the learned method completed 0 additional batches.

For batches of 16 targets, the learned complete-time ratio to the full-pool control is 0.952, with descriptive interval $[0.772, 1.148]$ across 11 paired batches. The control completed 0 additional batches, while the learned method completed 0 additional batches.

Across both batch sizes, the learned complete-time ratio to the distance control with the same early check is 0.925, with descriptive interval $[0.848, 1.024]$ across 23 paired batches. The control completed 0 additional batches, while the learned method completed 0 additional batches.

For batches of 1 target, the learned complete-time ratio to the distance control with the same early check is 0.913, with descriptive interval $[0.855, 0.972]$ across 12 paired batches. The control completed 0 additional batches, while the learned method completed 0 additional batches.

For batches of 16 targets, the learned complete-time ratio to the distance control with the same early check is 0.939, with descriptive interval $[0.764, 1.136]$ across 11 paired batches. The control completed 0 additional batches, while the learned method completed 0 additional batches.

For the predefined single-target comparison, the learned method reduced geometric mean complete time by 8.6% relative to the full pool and by 8.7% relative to the distance rule with the same early check. Both descriptive intervals lie below one, and every method completed all five repeats for all twelve instances. The first confirmation gave a 7.8% reduction relative to the full pool for this batch size. These results support a repeated gain for one constructed target expression at a time in this stored-identity setting. The sixteen-target intervals include one, so that batch size does not establish a consistent gain. The geometric means of the twelve per-family median complete times were 5.478 seconds for the full pool and 5.005 seconds for the learned method.

The learned workflow has an observed 6.8% lower geometric mean complete time than the full-pool Kira control on batches where both methods completed all five repetitions. Because the descriptive interval includes one, the aggregate timing gain across both batch sizes remains uncertain. These conclusions concern reduction from the supplied identity pools and the tested constructed target expressions. Native equation generation, arbitrary scattering amplitudes and larger independent multiloop families remain outside this result [28].




Figure 26: Complete-time ratios with the same early master check for learned and distance-selected seeds. Points show geometric means of five-repeat median ratios, intervals resample kinematic groups, and n gives the number of complete paired batches. The full-pool control uses standard supplied-equation Kira reduction.

13.13 Reducing fixed waits in the exact reduction workflow

The preceding comparisons show that the cost of using the seed model depends on the full reduction workflow. Inspection of the Kira version used here found a fixed one-second wait each time the program closed a Fermat process. Fermat performs exact rational-function arithmetic, and this wait occurs after the interface sends its exit command and closes its pipes. The program then checks whether the child has exited and forces termination if it is still running.

We replaced this fixed wait with repeated checks of the same child process at two-millisecond intervals. The modified interface returns as soon as it observes the exit and retains a one-second grace period before forced termination. It also handles interrupted checks and already reaped children. Tests checked that the arithmetic process exits normally or reaches the existing termination limit. We built this change separately from the original Kira executable. The symbolic elimination code, rational coefficients, model weights and seed threshold remain unchanged [29].

This change acts on a distinct part of the complete cost,

$$T_{\mathrm{total}} = T_{\mathrm{input}} + T_{\mathrm{model}} + T_{\mathrm{algebra}} + T_{\mathrm{exit}} + T_{\mathrm{check}}. \tag{101}$$

Here T_{input} includes loading and equation preparation, T_{model} includes loading the seed model and computing its scores, T_{algebra} is the time spent in exact reduction, T_{exit} is the time needed to close its arithmetic processes, and T_{check} is the final coefficient-verification time. Failed attempts and fallback contribute to the corresponding terms. Removing the fixed part of T_{exit} can improve a short reduction without changing its algebraic operation count.

13.13.1 Separating shutdown costs from learned seed selection

We compare four complete workflows: the original Kira with all supplied equations, the original Kira with learned seeds, the modified Kira with all supplied equations, and the modified Kira with learned seeds. The learned workflows use the existing model, the fixed threshold 0.01, the early master check and the same full-pool fallback. Thus, comparing the two learned workflows isolates the shutdown change, while comparing learned selection with the full pool within the modified Kira measures the remaining benefit of that seed-selection workflow.

Development uses three instances from the original training partition. The reserved comparison uses twelve other one-loop box instances in six original-test kinematic groups that were absent from all earlier box cost-test groups. Each instance has batches of one and sixteen constructed targets, and each workflow receives five rotated repetitions on the same node for that instance and batch size. We fixed the cases before timing the change and froze the executable, code, model and scientific inputs before the reserved runs.

Every measured time includes a fresh process start, input preparation, model inference where applicable, exact Kira reduction, failed attempts, fallback and exact coefficient checks. The prior generation of the shared IBP identity pools is outside all four methods. Each trial uses one thread, a 180-second complete-process cap, a 1.7 GB process-tree memory limit and 32 MiB of temporary storage. The array began with two simultaneous trials and increased to three and then six after memory and storage checks. The individual limits, targets, models and calculation code stayed fixed. After a failed measured attempt, further identical repetitions are marked as skipped and receive no measured time.

The timing comparison uses the median of five successful repetitions for each method and batch. We form the geometric mean of their paired time ratios and obtain descriptive 95% intervals by resampling entire kinematic groups 10,000 times. These intervals describe the completed subset, and the separate completion counts retain every planned case.

Development produced 10 exact completions from 12 measured trials. The reserved comparison contains 480 planned records, 416 measured trials and 400 exact completions. Independent checks compared 8,850 sampled master-coefficient vectors with the raw Kira exports. Every completed reduction matched its exact reference coefficients.

Each workflow completed 100 trials exactly and recorded 4 failed attempts and 16 skipped repetitions. Each learned workflow used full-pool fallback 10 times among its completed trials. The paired comparisons below identify the successful batch sets.

13.13.2 Measured complete-time changes

For one target at a time, the modified learned workflow has a complete-time ratio of 0.385, with a descriptive 95% interval $[0.342, 0.453]$ from 12 complete paired batches relative to the original learned workflow. The corresponding geometric mean times are 5.528 and 2.126 seconds, a 61.5% reduction. For sixteen targets, the ratio to the original learned workflow is 0.686, with a descriptive 95% interval $[0.540, 0.844]$ from 8 complete paired batches.

With the responsive shutdown active in both methods, learned seed selection has a one-target complete-time ratio of 0.690, with a descriptive 95% interval $[0.424, 0.931]$ from 11 complete paired batches relative to the full pool. The corresponding sixteen-target ratio is 0.983, with a descriptive 95% interval $[0.915, 1.063]$ from 8 complete paired batches. The one-target comparison therefore retains a measured 31.0% reduction from the learned seed workflow after the shutdown improvement. The sixteen-target interval includes one, so a consistent additional benefit remains unresolved for that batch size.

The modified learned workflow has a one-target complete-time ratio of 0.282, with a descriptive 95% interval $[0.199, 0.349]$ from 11 complete paired batches relative to the original full-pool workflow. The full-pool workflow alone has a modified-to-original ratio of 0.408, with a descriptive 95% interval $[0.355, 0.476]$ from 11 complete paired batches. These controls show that the shutdown improvement applies to the exact solver independently of machine learning. The unchanged seed model supplies a separate choice of equations, whose incremental effect is measured against the modified full-pool control.

Across 200 completed original/modified pairs, equation inputs and reported elimination counters agreed. The final raw coefficient exports were identical in 200 pairs, and 104 paired prediction records agreed exactly. The change therefore improves process completion time while preserving the tested mathematical calculations. It does not establish fewer algebraic operations, a better trained model or a general multiloop speedup. The measured domain remains the specified supplied-identity reductions of constructed one-loop targets.

The two learned workflows both completed all five repetitions in 12 of the twelve single-target batches and 8 of the twelve sixteen-target batches. Their successful batch sets agreed at each batch size. With the modified shutdown, learned selection alone completed 1 batch of 1 target. With the modified shutdown, the full pool alone completed 1 batch of 16 targets. The quoted ratios use only the stated complete paired subsets; all other outcomes remain in the completion counts.




Figure 27: Complete-time ratios for responsive Fermat shutdown and learned seed selection. Points show geometric means of paired five-repeat medians; intervals resample kinematic groups. Each row compares the same physical targets, and values below one indicate less complete time. Here n is the number of complete paired batches.

14 Complete native multiloop reductions

The preceding supplied-equation tests begin with an existing IBP pool. To include the work needed to form that pool, we now give Kira physical denominators and indexed target integrals and repeat equation generation in every measured calculation. We also train a separate row model from the algebraic work caused by choices inside Kira. This connects the training objective

to the intended reduction cost and permits a direct comparison with Kira's own source-row choices.

14.1 Physical families and independent targets

The integral notation remains $I_{\boldsymbol{a}}$, with $D_i = q_i^2 - m_i^2 + \mathrm{i}0$ as defined earlier. We use the following ordered momentum lists:

$$\boldsymbol{q}_{\text{sunrise}} = (\ell_1, \ell_2, p - \ell_1 - \ell_2, p - \ell_1, p - \ell_2), \tag{102}$$

$$\boldsymbol{q}_{\text{box}} = (\ell_1, \ell_1 - p_1, \ell_1 - p_1 - p_2, \ell_2, \ell_2 - p_1 - p_2, \ell_2 - p_1 - p_2 - p_3, \ell_1 - \ell_2, \ell_1 - p_3, \ell_2 - p_1), \tag{103}$$

$$\boldsymbol{q}_{\text{vacuum}} = (\ell_1, \ell_2, \ell_3, \ell_1 - \ell_2, \ell_2 - \ell_3, \ell_1 - \ell_3), \tag{104}$$

$$\boldsymbol{q}_{\text{ladder}} = (\ell_1, \ell_1 - p, \ell_2, \ell_2 - p, \ell_3, \ell_3 - p, \ell_1 - \ell_2, \ell_2 - \ell_3, \ell_1 - \ell_3). \tag{105}$$

The first three sunrise entries, seven box entries and eight ladder entries are physical propagators. Their remaining entries complete the scalar-product basis and can appear with nonpositive indices. All six vacuum entries are physical propagators. The first two lists contain two loop momenta, and the last two contain three. In particular, the three-loop vacuum and ladder systems couple the loop momenta through shared propagators.

For each list, we expand the squared momenta in $\ell_i \cdot \ell_j$ and $\ell_i \cdot p_j$ and check that the resulting coefficient matrix has rank

$$N_{\text{sp}} = \frac{L(L+1)}{2} + LE.$$

Here E is the number of independent external momenta, and N_{sp} is the number of independent scalar products involving loop momenta. All fifteen family definitions pass this check, and their nonempty external Gram matrices have nonzero determinants. This prevents a dependent denominator list from entering the comparison.

All squared masses and external scalar products have fixed rational values in a common squared-momentum unit, while the dimension d remains symbolic. The reduction coefficients therefore belong to $\mathbb{Q}(d)$. For the box, the external momenta satisfy

$$p_i^2 = 0, \qquad 2p_1 \cdot p_2 = s, \qquad 2p_1 \cdot p_3 = t, \qquad 2p_2 \cdot p_3 = -s - t.$$

The six training cases consist of two sunrise mass profiles $(1,1,1)$ and $(1,2,3)$ with $p^2 = -1, -2$ respectively, two massless boxes with $(s,t) = (-1,-2), (-2,-3)$, and two vacuum profiles $(1,1,1,1,1,1)$ and $(1,1,1,2,2,2)$. These profiles specify squared masses in the displayed propagator order. Validation uses the sunrise profile $(1,1,2)$ at $p^2 = -3$, a box at $(s,t) = (-3,-4)$, and the vacuum profile $(1,1,1,1,1,2)$.

The six reserved cases use boxes at $(s,t) = (-5,-7), (-7,-11)$, vacuum profiles $(1,1,2,1,2,2)$ and $(1,2,2,1,2,2)$, and two ladder instances. One ladder is massless with $p^2 = -1$; the other has $m_1^2 = 1$, all other squared masses zero, and $p^2 = -2$. The ladder topology appears only in the reserved set. The other reserved cases test different kinematic or mass conditions within training topologies. These tests concern rational kinematic points with symbolic d and do not establish performance for general symbolic multiscale coefficients.

Targets are individual indexed integrals. We begin with the full-sector corner, then increase each positive index by one and insert each available auxiliary numerator once. We repeat this enumeration after removing one, two and three physical denominators, retain at least two physical denominators, and remove duplicate index vectors. The reserved batches contain the first 32 or 128 targets in this fixed order. This construction selects targets without using learned scores or reverse construction paths.

14.2 Seed regions, learned subsets and complete fallback

For a batch $\mathcal{T}$, define

$$r_{\mathcal{T}} = \max_{\boldsymbol{a}\in\mathcal{T}} \sum_i \max(a_i, 0), \qquad s_{\mathcal{T}} = \max_{\boldsymbol{a}\in\mathcal{T}} \sum_i \max(-a_i, 0), \qquad b_{\mathcal{T}} = \max_{\boldsymbol{a}\in\mathcal{T}} \sum_i \max(a_i - 1, 0).$$

The last quantity is the largest total number of additional propagator powers, also called dots. We specify Kira seed bounds $(r_{\mathcal{T}} + \delta, s_{\mathcal{T}} + \delta, b_{\mathcal{T}} + \delta)$, where $\delta = 1$ defines the conservative reference region and $\delta = 0$ defines the smaller region. Kira still applies its native symmetry, equation-generation and equation-selection procedures within these bounds [9]. The bounds are explicit input choices; their difference is not a learned improvement to Kira.

The saved seed model scores the finite candidate region using the ordered sum of the batch targets, with coefficient one for each target. This sum supplies model context, while Kira still reduces every target separately. Every sector corner, target and prescribed master that belongs to the candidate region remains available. An additional deterministic rule can retain all seeds with at most one dot or one numerator power in total. The learned policy can add seeds above its probability threshold, and a separate control applies the same deterministic rule without model inference.

Kira first checks whether the selected system requires masters outside the prescribed reference basis. A rejected subset triggers the documented fallback sequence, and its time remains part of the measurement. A final successful calculation must produce every requested target and match its reference coefficient in $\mathbb{Q}(d)$. Other failed attempts also move through the prescribed fallback sequence. A coefficient mismatch makes the complete workflow unsuccessful. Splitting a batch into groups of 32 targets bounds each calculation, but it also repeats equation generation and process startup; the timing comparison includes both effects.

14.3 Training row choices on their algebraic consequences

The new row model chooses a source among equations with the same leading integral. It preserves Kira's native pivot and group order, and Kira carries out every resulting row operation exactly. At state S, the allowed action q selects one such source row, which removes the leading integral from the other rows in that group. The model therefore acts on the changing native matrix through a restricted, explicitly defined action set.

The first training objective measures the immediate symbolic insertion time for each source. We clone the destination rows, apply the exact native update, and average two rotated measurement orders while excluding clone time. This measures local arithmetic cost, but it does not include the equations created by later eliminations. We therefore also measure a continuation cost,

$$C(S, q) = \sum_{j\in\mathcal{U}(S,q)} (1 + 2n_j). \tag{106}$$

Here $\mathcal{U}(S, q)$ is the sequence of committed forward insertions after choosing q and then following Kira's native choices, and n_j is the number of nonzero coefficients in the source of insertion j. The count assigns one division and two coefficient operations per source entry. It is an algebraic operation estimate tied to measured native insertions; it does not count Fermat's internal polynomial operations or back substitution.

We choose up to four evenly spaced eligible states from the saved local-cost sample in each development case, which contains at most 100 measured groups. We prefer groups with at least three source choices and use smaller groups when no such group is available. Each alternative receives a separate complete Kira continuation. The recorded pivot and all candidate features

must match the original state, and the final master coefficients must match the reference reduction before its cost can enter training. The resulting labels measure a choice followed by native continuation. They do not prove a globally minimum reduction path.

Each candidate has eighteen features describing row length, coefficient text length and operations, overlap with destination columns, estimated new entries, and its position relative to Kira's preferred source. A linear fit to log continuation cost retained the native source in all nine validation states. We therefore also fit a small regression tree [30], which can represent conditions involving several features.

For this tree, the target is the normalized change in measured continuation cost,

$$y_q = \frac{C(S,q) - C(S,0)}{\max\{1, \max_{q'} C(S,q') - \min_{q'} C(S,q')\}}, \qquad \widehat{y}_q = h(\boldsymbol{x}_q - \boldsymbol{x}_0).$$

The index 0 denotes Kira's preferred source, $\boldsymbol{x}_q$ is the candidate feature vector, and h is the fitted tree. Lower targets correspond to fewer recorded operations. We fix $\widehat{y}_0 = 0$ and fit the remaining candidates with a weighted least-squares loss that gives each training family equal weight. Validation selects tree depth, minimum leaf population, target normalization and the required predicted gain.

The selected tree has 21 nodes, depth four and at least two training examples in each leaf. Its training set contains 68 candidate continuations in 24 states from six families, while validation contains 30 candidates in nine states from three families. All 98 continuations match their exact reference reductions. The tree changes nine training choices and three validation choices, with family-weighted continuation count ratios of 0.998602 and 0.999967 to the native choices. These ratios measure individual choices followed by native continuation; the next test must determine the effect of using the model repeatedly.

The model chooses the lowest predicted score and reports

$$P(q \mid S) = \frac{\exp(-\widehat{y}_q)}{\sum_{q'} \exp(-\widehat{y}_{q'})}.$$

This quantity expresses a relative model score, with no calibration claim. Kira evaluates each score directly in compiled code. Groups with two rows or more than 32 rows keep the native source, which also avoids feature construction for those groups. We preserve the original neural checkpoint and both earlier linear fits as separate artifacts, and hold the final tree fixed during reserved testing.

The seed implementation also reads its unchanged weight archive once per process and retains at most two sets of family and candidate embeddings within a workflow. A new target batch still receives its own target features and scores. Independent checks compare every probability with the original implementation and compare native tree scores and choices with the Python model. These changes reduce repeated loading and feature preparation while preserving the tested seed predictions.

14.4 Complete timing and reference checks

Every final trial starts a new process and includes input preparation, model loading and inference, native IBP generation and selection, symbolic elimination, back substitution, exact coefficient comparison, and all failed attempts and fallback reductions. Evidence compression follows the stop time. These checks establish reduction to the prescribed reference basis; they do not prove global minimality of the master set. We report the initial reference calculation separately as common benchmark preparation. Each policy receives the same prescribed master basis and exact comparison result within a case.

All controls use the responsive Fermat shutdown from the preceding section. We compare both the unchanged reduction executable with that shutdown fix and an instrumented executable that keeps native row choices. This separates the cost of measurement and integration from the learned action. We also compare smaller deterministic regions and matched deterministic seed subsets, since either could explain a gain over conservative bounds.

Each trial uses one calculation thread, a bounded scratch directory and limits on elapsed time and process-tree memory. Production trials have 128 MiB of scratch space, a 2,400 MiB solver address-space limit, and a 2,100 MiB solver process-tree resident-memory limit. The enclosing worker has a 2,800 MiB address-space limit and a 2,600 MiB process-tree resident-memory limit. A single common-reference calculation can use 256 MiB while retaining the same symbolic bounds, and the storage ledger includes additional monitoring headroom. Final comparisons use paired cases and report completion counts alongside time ratios. Repeated runs reduce timing noise within a case, while different kinematic instances remain distinct from different topologies. The reserved results do not select the policy or its thresholds.

14.5 Reserved results and complete-calculation cost

The frozen comparison contains six reserved cases, two target-batch sizes, nine policies and three repetitions of each policy. Each trial begins with physical denominators and includes native IBP equation generation. The results and exact evidence are available with the comparison data [31].

We measured 324 of 324 planned trials, and 324 completed every target with exact reference coefficients. The records retain 0 unsuccessful measured trials and 0 skipped trials. The independent audit checked 550 successful native reductions, including the training continuations and reserved attempts, and made 114,965 coefficient comparisons by exact polynomial cross multiplication. All 98 recorded training and validation continuations passed. The separate larger-region check completed 6 of 6 cases. These comparisons verify reduction to the prescribed basis; a finite region check does not prove that the basis is globally minimal.

The measured workflows contain 585 native reduction attempts. Kira rejected 66 attempted subsets because they required masters outside the prescribed basis. The remaining unsuccessful attempts comprise 84 other Kira errors, 3 elapsed-time limits. These attempts remain in complete-workflow times, and the fallback sequence determines whether every target can still be reduced within the budget.

The common reference preparation completed 12 of 12 case–batch calculations. The successful reference times ranged from 5.967 to 28.083 seconds and are outside the paired production timings. The two 128-target box cases use 8 master integrals each. Both contain 8 zero targets and 3 targets already in the master basis, leaving 117 nonzero targets that require reduction in each case. The two 128-target vacuum cases use 11 and 17 master integrals, respectively. The first contains 4 zero targets and 8 targets already in the master basis, leaving 116 nonzero targets that require reduction. The second contains 4 zero targets and 13 targets already in the master basis, leaving 111 nonzero targets that require reduction. The two 128-target ladder cases use 5 and 21 master integrals, respectively. The first contains 14 zero targets and 0 targets already in the master basis, leaving 114 nonzero targets that require reduction. The second contains 14 zero targets and 1 targets already in the master basis, leaving 113 nonzero targets that require reduction.

The following ratios use only case–batch pairs for which both policies completed all three repetitions. We take the median within each case and batch, average log ratios within a case, and then give cases equal weight. Ratios of operation counts also require positive counts in both methods. The intervals use 5,000 resamples of the fixed physical cases, so they describe this sample rather than a general distribution of multiloop families.

14.5.1 Seed selection and deterministic controls

Validation selected the smaller-region learned seed policy at probability threshold 0.01. Its complete-time ratio to instrumented native Kira was 1.118 on the validation sample; this selection therefore did not establish an aggregate validation gain. On reserved tests, its ratio to the responsive stock control is 0.742 with descriptive interval $[0.560, 1.009]$, and its ratio to the instrumented native control is 0.755 with descriptive interval $[0.573, 1.050]$. Against the smaller deterministic region with fallback, the ratio is 0.916 with descriptive interval $[0.723, 1.152]$. Against the same low-complexity coverage rule without ML, the ratio is 0.833 with descriptive interval $[0.679, 1.010]$. These controls separate the effects of region size, deterministic coverage, model inference and the learned additions.

For 32 targets, the learned seed ratio to responsive stock Kira is 0.713 with descriptive interval $[0.543, 0.967]$, using 6 complete paired batches. The corresponding geometric mean median times are 10.490 and 14.720 seconds. For 128 targets, the learned seed ratio to responsive stock Kira is 0.772 with descriptive interval $[0.558, 1.082]$, using 6 complete paired batches. The corresponding geometric mean median times are 13.723 and 17.764 seconds.

For the two-loop boxes, the seed-to-stock time ratio is 0.563 with descriptive interval $[0.531, 0.598]$. Its ratio to the smaller deterministic region is 0.642 with descriptive interval $[0.627, 0.658]$. Its ratio to the matched coverage rule is 0.606 with descriptive interval $[0.567, 0.648]$. For the three-loop vacuum integrals, the seed-to-stock time ratio is 1.266 with descriptive interval $[1.180, 1.357]$. Its ratio to the smaller deterministic region is 1.291 with descriptive interval $[1.245, 1.338]$. Its ratio to the matched coverage rule is 1.093 with descriptive interval $[1.016, 1.175]$. For the three-loop ladders, the seed-to-stock time ratio is 0.573 with descriptive interval $[0.554, 0.592]$. Its ratio to the smaller deterministic region is 0.928 with descriptive interval $[0.852, 1.010]$. Its ratio to the matched coverage rule is 0.871 with descriptive interval $[0.833, 0.910]$. These topology breakdowns retain every case in the stated class. The ladder class tests a topology absent from the new row-training and validation data.

The learned seed ratio for the initially generated equations summed across attempts is 0.086 with descriptive interval $[0.049, 0.152]$ relative to native Kira. The learned seed ratio for the committed forward coefficient-operation estimate is 0.798 with descriptive interval $[0.655, 0.992]$ relative to native Kira. The first generation count in each native attempt defines the equation measure; later selection counts are not added to it. The operation estimate follows Eq. (106), and all attempted stages contribute when a workflow requires fallback.

14.5.2 Repeated row decisions in the changing matrix

The cost-trained row tree has a complete-time ratio of 1.008 with descriptive interval $[0.937, 1.078]$ to the instrumented native policy. Its forward coefficient-operation ratio is 1.003 with descriptive interval $[0.983, 1.021]$, while the measured forward-stage time ratio is 0.943 with descriptive interval $[0.828, 1.033]$. The paired geometric mean forward times are 0.091 seconds for native choices and 0.085 seconds for the tree, while their complete times are 15.887 and 16.013 seconds. Most measured time therefore lies outside this recorded forward stage. The sampled continuation objective measures one altered source choice followed by native choices. Repeated tree choices change the later matrices and can therefore change the cost in a different direction. The full-workflow results determine whether the trained model saves work in this use.

The combined seed and row policy has a complete-time ratio of 0.759 with descriptive interval $[0.613, 0.962]$ to responsive stock Kira. Its paired geometric mean median time is 12.280 seconds, compared with 11.998 seconds for seeds alone. The row addition therefore does not lower this




Figure 28: Complete-time ratios to responsive stock Kira for 32 and 128 indexed targets. Points use medians of three exact repetitions and equal case weights. Bars show descriptive case-resampling intervals; the labels give complete paired batch counts. A ratio below one means lower measured time in the stated paired cohort.

point estimate. Combining two decisions requires a separate measurement because a different seed set changes the equations on which the row policy acts.




Figure 29: Per-case median work ratios in the reserved comparison. The row panel measures committed forward coefficient operations relative to the same instrumented native policy. The seed panel measures initial generated equations, summed over attempts, relative to native Kira. Cases A and B follow the parameter order given in the text. Counts concern different stages and do not measure Fermat's internal polynomial work.

14.5.3 Completion of larger target batches

With 32 targets, responsive stock Kira completed 18 of 18 trials. For the learned seed workflow, 18 of 18 completed, including 6 rescued by fallback. For the combined workflow, 18 of 18 completed, including 6 rescued by fallback. For native groups of 32 targets, 18 of 18 completed, including 0 rescued by fallback. For combined groups of 32 targets, 18 of 18 completed, including 6 rescued by fallback.

With 128 targets, responsive stock Kira completed 18 of 18 trials. For the learned seed workflow, 18 of 18 completed, including 6 rescued by fallback. For the combined workflow, 18 of 18 completed, including 6 rescued by fallback. For native groups of 32 targets, 18 of 18 completed, including 18 rescued by fallback. For combined groups of 32 targets, 18 of 18 completed, including 18 rescued by fallback.

For 128 targets, splitting the native workflow gives a time ratio of 2.151 with descriptive interval $[1.783, 2.647]$ to stock Kira. Splitting the combined workflow gives 2.078 with descriptive interval $[1.631, 2.845]$. The separate fallback counts show whether completion improves; the paired times include repeated generation and process startup.




Figure 30: Completion of all requested targets under the fixed time and storage limits. The filled components distinguish successful initial reductions from reductions completed through fallback. Unfilled trials include failed or explicitly skipped outcomes. Each policy has eighteen planned trials at each batch size.

14.5.4 Scope and resource outcomes

The largest recorded production process-tree memory use was 106.8 MiB, and the largest monitored production scratch allocation was 1.0 MiB. Among unsuccessful attempts, 7 logs report an allocation failure and 10 report recursive termination; these diagnostic counts can overlap. The fixed process limits constrain these outcomes, and the logs alone do not establish exhaustion of physical RAM. The workflow retains their costs and follows the same fallback rule. A separate post-comparison check repeated the smaller seed region for the 128-target validation box using both the responsive stock executable and the instrumented native executable. Both reported `std::bad_alloc` under the same solver limits, so this failure also occurs without the row-policy hook. This check concerns the failure mechanism and supplies no additional timing comparison; it leaves all frozen reserved settings unchanged.

One scheduler interruption stopped a test worker when the sum of its processes' virtual address spaces exceeded the job limit. We preserved its completed records and resumed only missing work with a larger scheduler address-space allowance, while keeping the measured physical-memory, scratch and elapsed-time limits fixed. This interruption is recorded separately from completed

workflow timings. With the resumed case excluded, the learned seed to stock complete-time ratio is 0.676 with descriptive interval $[0.549, 0.963]$. With the resumed case excluded, the learned row to native complete-time ratio is 1.039 with descriptive interval $[0.991, 1.102]$. The tests include two- and three-loop systems at fixed rational kinematics, a finite prescribed seed region and a restricted source-row action. They do not establish a speedup for arbitrary symbolic kinematics, every multiloop topology, or the earlier restricted collection through twelve loops.

15 Integrated seed and row policies with bounded execution

The complete reductions in Section 14 show that a learned choice can save algebraic work while other parts of the calculation determine most of the elapsed time. We therefore examine both the cost of applying the models and the native operations that surround them. Every comparison in this section starts from physical denominators, generates IBP equations and checks the final master coefficients. We retain the earlier checkpoints and results, and use separate training, validation and reserved cases for the new policies.

15.1 Removing costs shared by both decision methods

Back substitution replaces the remaining nonmaster integrals in each triangular equation with their reductions. If the equation for $I_{\boldsymbol{a}}$ contains $I_{\boldsymbol{b}}$ on its right-hand side, the latter reduction must be available before the former equation can finish. We represent this dependency by the directed edge

$$I_{\boldsymbol{b}} \longrightarrow I_{\boldsymbol{a}}.$$

A topological order is a sequence in which every dependency appears before the equation that uses it. The modified single-worker schedule constructs this order from the loaded equations, preserves the native arithmetic and rejects a cycle or an invalid dependency. This permits one bounded group of back-substitution workers. The inspected native implementation created helper workers for each sector range, even when the calculation used one arithmetic worker.

An initial merge that retained the loaded row order reached a dependency wait and exceeded its time limit. The corrected order completed all six subsequent bounded pilot reductions and reproduced their reference coefficients. The corresponding smaller-region native control reported an allocation failure. These are development checks of the scheduling change. They do not attribute a gain to either learned model or establish a general memory-exhaustion mechanism.

The calculation also creates temporary databases. We compare the same native reductions with those databases on project storage and on the compute node's temporary storage. The eight exact pilot runs use the same resource limits and two repetitions of each region and storage condition. Their geometric mean time ratio for node storage relative to project storage is 0.307. We use node storage for all later learned and deterministic controls. Both controls therefore receive the same scheduling and storage improvements.

15.2 Applying the seed model with unchanged probabilities

The seed policy retains the trained neural weights and the finite candidate region described earlier. For each batch, it constructs the family features, the ordered target features and the candidate index features before predicting a separate probability for every seed. We construct the index features in arrays and reuse shared family information so that the model performs less repeated preparation.

A parity check compares 5,000 generated index vectors and all candidate predictions for the nine development profiles. The feature values, embeddings and final probabilities agree exactly with the preceding implementation. In the development box checks with 3,510 candidates, shared feature construction and prediction decrease from approximately 0.08 to 0.01 seconds. These component measurements motivate the implementation change; complete-workflow comparisons must also include model loading, equation generation, exact algebra and any fallback.

The selected seeds always retain the prescribed mandatory integrals and the stated deterministic coverage rule. Kira checks whether the resulting system introduces masters outside the reference basis. An insufficient set triggers the fixed fallback sequence, and the elapsed time includes the unsuccessful attempt. Final coefficients must agree with the common reference in $\mathbb{Q}(d)$.

15.3 Estimating cancellations before a row choice

The row model chooses among source equations with the same leading integral, as in the preceding native experiment. To include cancellations in its description of each choice, consider source row $\boldsymbol{u}_q$ and destination row $\boldsymbol{v}_j$, with common leading column p and nonzero source coefficient u_{qp}. Exact elimination forms

$$v'_{jk} = v_{jk} - \frac{v_{jp}}{u_{qp}} u_{qk}.$$

A resulting coefficient vanishes when

$$v_{jk} u_{qp} - v_{jp} u_{qk} = 0.$$

We estimate this condition by evaluating the rational coefficients at $d = 17$ and $d = 19$ modulo the prime $2\,147\,483\,647$. Two zero evaluations supply a feature estimate of cancellation; they do not certify a symbolic identity. Kira still performs the exact update, and the final reduction still undergoes an exact coefficient check. Unsupported expressions and poles cause the policy to retain the native source.

Let $\widehat{n}_{jq}$ be the estimated number of surviving entries in destination j after using source q. Six additional features describe the total $\sum_{j \neq q} \widehat{n}_{jq}$, the cancellation fraction, the largest resulting row, the number of zero rows, the sum $\sum_{j \neq q} \widehat{n}_{jq}^2$, and whether the modular estimate is valid. They extend the previous eighteen features to twenty-four. The implementation bounds the group size, coefficient text and modular cache, and retains native behavior outside these limits.

Independent checks compare the evaluator with exact rational arithmetic for 210 expressions and three row-choice fixtures. A separate in-process comparison checks shared feature construction against the original formula in 4,041 changing row groups. Python and the compiled policy also agree on all 3,247 recorded decisions in that check, and all three full reductions match their reference coefficients. Shared construction calculates each row's length and coefficient statistics once per group and each pairwise overlap once.

15.4 Learning from local cost and complete trajectories

Each of the six training profiles and three validation profiles has an ordinary batch and a deeper batch. The deeper batch includes integrals with two extra propagator powers and mixed numerator and propagator powers. Both batches from a physical profile remain in the same partition. Collection gives 2,520 eligible training groups and 1,372 validation groups, with exact reference agreement required before any group can enter training.

We first fit small regression trees to immediate insertion time, resulting coefficient text length, and a combination of these quantities. The time-selected trees keep every native choice in their

recorded validation groups. The coefficient-length tree changes 371 choices and gives a family-weighted immediate coefficient-length ratio of 0.920, accompanied by an insertion-time ratio of 1.097. These labels describe a single group. Repeated deployment can change later matrices, so the full reduction supplies the required cost comparison.

The next search therefore evaluates a policy throughout the native forward reduction. A candidate assigns source q the score

$$s_{\boldsymbol{w}}(S,q) = \boldsymbol{w}^{\mathsf{T}}\boldsymbol{x}(S,q), \qquad q^*(S) = \arg\min_q s_{\boldsymbol{w}}(S,q),$$

where S is the current row group, $\boldsymbol{x}(S,q)$ is its feature vector and $\boldsymbol{w}$ is the policy's coefficient vector. Ties retain the native source. The bounded candidate set varies the emphasis on source length, coefficient length, predicted surviving entries, squared resulting row lengths and preference for the native source.

We evaluate eighteen coefficient vectors on all twelve training batches. For each complete trajectory, the forward-work estimate remains $\sum_j (1 + 2n_j)$ from Eq. (106). This count now includes every committed update caused by repeated policy choices. We rank candidates by the geometric mean ratio to native work, first averaging the ordinary and deeper batches within each physical profile and then giving profiles equal weight. Thus later algebraic consequences enter the training objective directly. The measured count excludes Fermat's internal polynomial operations and back substitution, which remain covered by the complete-time measurement.

The two nontrivial linear policies retained for the final comparison use

$$s_A(S,q) = 2\log(1+n_q) + \log\left(1 + \sum_{j\neq q} \widehat{n}_{jq}\right), \tag{107}$$

$$s_B(S,q) = \tfrac{1}{2}\log(1+n_q) + \log\left(1 + \sum_{j\neq q} \widehat{n}_{jq}\right) + 0.3\log\left(1 + \sum_{j\neq q} \widehat{n}_{jq}^{\,2}\right) - 0.01\,\delta_{q0}. \tag{108}$$

Here n_q is the number of entries in source row q, and δ_{q0} is one for the native source and zero for another source. The lower score selects the source. These coefficient vectors come from the stated finite search; validation then selects which vector to use for each topology. The small native-source preference in s_B reduces changes when its other features give nearly equal scores.

Separate validation compares the selected policies with native choices and a deterministic rule that minimizes the predicted number of surviving entries. It also measures the seed policy alone and the combined seed and row policy. A model reports the normalized score

$$P(q \mid S) = \frac{\exp[-s_{\boldsymbol{w}}(S,q)]}{\sum_{q'} \exp[-s_{\boldsymbol{w}}(S,q')]}.$$

This gives a relative preference among the supplied actions, with no calibration or global-optimality claim. Reserved cases do not select weights, thresholds or deployment rules.

15.5 Timing a complete integrated workflow

All methods use fresh processes, the same temporary storage and the same bounded back-substitution schedule. Production timing includes preparation, prediction, equation generation and selection, elimination, back substitution, exact comparison and every required fallback. A child-exit notification ends the wait promptly and avoids adding the monitor's polling interval to short calculations. Detailed training traces remain disabled during production timing, while aggregate operation and time counters remain enabled.

The reference reduction and prescribed master basis are common benchmark preparation and remain outside the paired production time. Successful trials must reduce every supplied target to that basis with exact coefficients. At most two production reductions run concurrently, each with 128 MiB of temporary storage and the preceding process-memory limits. The project ledger reserves storage for temporary files, retained records, publication copies and the local report while remaining below the user's combined 10 GB ceiling.

15.6 Reducing the cost of a single model call

The vector implementation accelerates repeated inference, but a short reduction also pays for loading its numerical library. We therefore export the same trained weights to a compiled evaluator that reads the same family, target and candidate features. The evaluator uses single-precision arithmetic and preserves the network's matrix operations, nonlinear functions and attention calculation. Different accumulation orders can change the last digits of a probability, so we check both probabilities and the selected sets.

Across thirty-six development contexts, the largest absolute probability difference is 9.48×10^{-6}. All selection masks agree at thresholds 0.003, 0.01, 0.03, 0.1, 0.3 and 0.5. A further forty-eight fresh-process checks use eight validation contexts, two implementations and three repetitions. Their selected sets also agree. The compiled implementation takes between 0.264 and 0.804 times the numerical-library implementation's median preparation and inference time across these contexts. Its arithmetic alone is slower in the warm tests; the fresh-process benefit comes from the lower startup cost. Production comparisons therefore retain startup in the timed workflow.

We also reduce the row policy's feature cost. Once training selects a sparse coefficient vector $\boldsymbol{w}$, only features with $w_k \neq 0$ affect its score. The production evaluator computes those features, while the diagnostic path retains the full vector. Thirty-six complete comparisons check three policies on six validation batches with this optimization enabled and disabled. The selected sources, committed operations and exact exports agree. The deterministic cancellation rule receives the same feature optimization, and its coverage control loads no neural model. These controls prevent model startup and unused feature work from creating an artificial learned advantage.

15.7 Selecting thresholds from complete reduction cost

The seed probabilities describe membership in the recorded construction data. Their classification threshold need not minimize the cost of a new native reduction. We therefore select an execution threshold using only the twelve native training batches. For each threshold τ in the six-value set above, the policy selects every candidate whose probability is at least τ, together with the mandatory coverage seeds. The search retains all time spent on unsuccessful attempts and the fixed native fallback.

Let $T_{i,\tau}$ be this complete time for training batch i, and let $T_{i,\mathrm{native}}$ be the time for the smaller native region with its fallback. Batches share a threshold when they have the same topology, largest number of additional propagator powers and largest total numerator power. For each such class $\mathcal{C}$, training selects

$$\tau_{\mathcal{C}} = \arg\min_{\tau} \exp\left[\frac{1}{|\mathcal{C}|}\sum_{i\in\mathcal{C}} \log\frac{T_{i,\tau}}{T_{i,\mathrm{native}}}\right].$$

Here $|\mathcal{C}|$ is the number of training batches in that class. The scan contains ninety-six complete workflows, including the smaller native and deterministic coverage controls. This threshold

search changes execution settings and preserves the earlier classification tests at their original threshold.

One development subset exposed an additional admission requirement. Its export still contained an integral outside the prescribed master basis, although the native master check had accepted the initial system. The exact reference comparison rejected the result. We now also inspect every integral on the right-hand side of the exported reduction. An extra integral marks an incomplete reduction and triggers the fixed expansion of the seed region. A disagreement between coefficients in the admitted basis stops the calculation. The original rejected result remains in the evidence, and its replacement workflow includes the unsuccessful subset's elapsed time.

15.8 Controls and the scope of the optimization

The smaller native control starts with the target's own bounds on propagator and numerator powers and expands them if needed. The conservative control starts one step beyond these bounds. The learned and deterministic coverage methods first try a subset of the smaller region, then the whole smaller region, then the conservative region. Row policies make each source choice inside the current native matrix throughout these attempts. This comparison separates the effect of a learned subset from the effect of starting with fewer native equations.

An additional experiment changes the database settings only for fresh, disposable trial directories. Three paired exact reductions give a median time ratio of approximately 1.011 to the unchanged settings, so the final configuration retains the usual database settings. A separate system-call diagnostic finds negligible time in database flushes for the examined box calculation. Disabling synchronization or moving a journal to memory changes recovery guarantees [32]; the retained configuration receives no performance claim from this rejected experiment.

These searches compare a finite set of models and execution choices under the stated memory and storage limits. They identify configurations with lower measured cost on their supported inputs. They do not prove a globally minimal number of algebraic operations or a globally shortest calculation time.

15.9 Initial independent tests of the integrated calculation

The initial comparison uses eight physical profiles that did not select the weights, thresholds or execution rules. Two two-loop sunrise profiles have squared masses $(1, 2, 2)$ and $(1, 2, 4)$, with external invariant $p^2 = -5$ and $p^2 = -7$, respectively. Two massless double-box profiles have $(s, t) = (-11, -13)$ and $(-13, -17)$. The three-loop vacuum profiles have squared masses $(1, 1, 1, 1, 1, 3)$ and $(1, 1, 1, 3, 3, 3)$. The three-loop ladder profiles have one squared mass equal to one, all other physical propagator masses equal to zero, and $p^2 = -3$ or -5. All values use the common arbitrary mass unit and denominator conventions of Section 14. The dimension d remains symbolic. The ladder topology remains absent from the new row-policy training and validation data.

Each sunrise profile supplies its ordinary twenty-one-target batch and a deeper thirty-two-target batch. Each other profile supplies batches of thirty-two and 128 targets. We compare seven methods on these sixteen batches: the conservative native region, the smaller native region, the deterministic cancellation rule, deterministic seed coverage, the seed model, the row model and both models together. Five repetitions per method give 560 planned workflows. We rotate and reverse method order within each physical profile. All methods use the same prescribed master basis, exact coefficient checks, temporary storage and single-worker schedule [33].

The validation-selected row score emphasizes source length for the boxes and uses the mixed

score for the sunrise and vacuum cases. The transfer test also uses the mixed score for the ladder topology. Seed thresholds come from the training classes; an unseen class uses the predefined threshold 0.01. The complete comparison executes the model ablations even where validation recommends native execution, so an unfavorable model cost remains visible in the results.

The recorded time begins with per-workflow preparation and ends after the final exact check and cleanup. It includes model import, weight loading, feature construction, prediction, every native generation and elimination attempt, and every fallback. Python interpreter launch, the common reference calculation, shared integrity checks and result compression remain outside this interval. Every candidate model and control uses the same timing boundary.

For each batch and method, we take the median of five repetitions. We then form paired ratios, average their logarithms within each physical profile and give the eight profiles equal weight. The descriptive intervals resample whole physical profiles while retaining their two batches. A topology-specific interval therefore contains only two independent profiles. Repeated timings measure execution variation; they do not create additional independent integral families.

The comparison records 560 workflows, of which 560 complete every target with the prescribed coefficients. It retains all 670 native attempts, including unsuccessful seed subsets. The independent audit reparses native exports and checks rational coefficients by exact polynomial cross multiplication in $\mathbb{Q}(d)$. Across the full development and test record, it reparses 2,386 successful native reductions and checks 507,630 coefficient comparisons. The separately retained development basis rejection remains a failed attempt and supplies no accepted reduction.

15.10 Measured model effects against matched native choices

Figure 31 compares each model with the smaller native control. This control receives the same runtime improvements and starts from the same target bounds. The comparison therefore tests whether the learned decisions save enough work to cover their own cost.

The seed policy has a complete-time ratio of 1.149, with descriptive interval $[1.021, 1.311]$, relative to the smaller native control. Its point estimate corresponds to a 14.9% increase in the profile-weighted complete time.

The row policy has a complete-time ratio of 1.004, with descriptive interval $[0.991, 1.016]$, relative to the smaller native control. Its point estimate corresponds to a 0.4% increase in the profile-weighted complete time.

The combined policy has a complete-time ratio of 1.165, with descriptive interval $[1.036, 1.323]$, relative to the smaller native control. Its point estimate corresponds to a 16.5% increase in the profile-weighted complete time.

These aggregate values combine inputs with different equation-generation and elimination costs. The separate physical classes show where a model contributes a measured saving and where its additional attempt or decision cost dominates.

For the two-loop sunrise profiles, the seed, row and combined complete-time ratios are 1.388, 0.990 and 1.424, respectively. Their descriptive intervals are $[1.386, 1.390]$, $[0.975, 1.005]$ and $[1.384, 1.464]$. These values average the two tested batches within each of the two physical profiles.

For the two-loop double-box profiles, the seed, row and combined complete-time ratios are 0.953, 1.003 and 0.961, respectively. Their descriptive intervals are $[0.945, 0.960]$, $[0.983, 1.024]$ and $[0.953, 0.968]$. These values average the two tested batches within each of the two physical profiles.

For the three-loop vacuum profiles, the seed, row and combined complete-time ratios are 1.309, 1.010 and 1.287, respectively. Their descriptive intervals are $[1.110, 1.543]$, $[0.997, 1.022]$ and $[1.104, 1.500]$. These values average the two tested batches within each of the two physical profiles.

For the three-loop ladder profiles, the seed, row and combined complete-time ratios are 1.007, 1.013 and 1.047, respectively. Their descriptive intervals are $[1.003, 1.011]$, $[1.003, 1.023]$ and $[1.002, 1.094]$. These values average the two tested batches within each of the two physical profiles.




Figure 31: Median complete time for the frozen seed, row and combined policies, divided by the smaller native control's median time on the same target batch. Every point uses five repeated workflows with fixed physical input and master basis. Values below one indicate lower complete time. The preceding text states the timing boundary and profile-weighted intervals.

15.11 Elimination work and the contribution of each model

A lower total runtime can come from seed generation, elimination or shared execution changes. We therefore also inspect committed forward operations and compare the combined method directly with the seed-only method.

The row policy relative to native choices gives an operation ratio of 0.985, a forward-stage time ratio of 1.030, and a complete-time ratio of 1.004. The operation count measures the stated coefficient-update proxy. It excludes Fermat's internal polynomial operations, while the two timing measures include the corresponding arithmetic within their stage boundaries.

The combined policy relative to the seed-only method gives an operation ratio of 0.988, a forward-stage time ratio of 1.018, and a complete-time ratio of 1.014. The operation count measures the stated coefficient-update proxy. It excludes Fermat's internal polynomial operations, while the two timing measures include the corresponding arithmetic within their stage boundaries.

The seed model's complete-time ratio to deterministic coverage is 0.978, with interval $[0.872, 1.071]$. The row model's ratio to the deterministic cancellation rule is 0.985, with interval $[0.975, 0.996]$. Both deterministic controls receive the same feature and runtime optimizations.

Starting from the smaller native region gives a complete-time ratio of 0.502 to the conservative native region. The combined model gives a ratio of 0.585 to that conservative control. The former comparison changes the initial native region without a learned decision. It therefore identifies a shared source of improvement that must be separated from the models' contributions.

15.12 Interpretation of the initial comparison

The integrated entry point applies the settings fixed from validation. It can run either model separately, run both models, or select the validation-recommended method from the topology and target powers. Automatic selection requires at least a two-percent validation improvement over the smaller native control; otherwise it retains that control. Unknown input classes also retain native execution. This rule avoids paying for models on inputs where development did not support their use. The reserved ablations above evaluate the fixed choices; reserved timings do not change their weights or the deployment rule.

The basis check and exact coefficient comparison remain active under every mode. Incomplete seed sets expand through the fixed fallback, and a coefficient disagreement in the admitted basis stops the workflow. The test uses exact rational functions of d at fixed rational masses and kinematics, with the master basis supplied in advance. Its measured times exclude discovering and certifying a new generic symbolic basis.

The new row policies learn from complete native trajectories and act inside Kira's changing matrix. Their allowed action is the source equation among rows with the same leading integral. They do not choose arbitrary columns, sectors or all mathematically possible reductions. The finite policy search, limited physical profiles and descriptive intervals bound the conclusion: the report establishes the measured changes on the stated inputs, while a general gain for both models and a globally fastest reduction require evidence beyond these comparisons.




Figure 32: Committed forward coefficient-operation ratios for the seed model against native choices, the row model against native choices, and the combined policy against seed selection alone. The last comparison isolates the additional row policy within the selected seed workflow. These counts describe the recorded update proxy and do not count internal polynomial work.

15.13 Removing redundant features in two-row decisions

The preceding comparison lowers the row-operation count while leaving the cost of evaluating row choices visible in the forward stage. The recorded training data contain 1,923 groups with two source candidates among 2,520 eligible groups. Their algebra supplies an additional way to reduce this cost.

Let $\boldsymbol{u}$ and $\boldsymbol{v}$ be two rows with the same leading integral, and let u_p and v_p be their nonzero leading coefficients. The two possible elimination updates satisfy

$$\boldsymbol{v}' = \boldsymbol{v} - \frac{v_p}{u_p}\boldsymbol{u}, \qquad \boldsymbol{u}' = \boldsymbol{u} - \frac{u_p}{v_p}\boldsymbol{v} = -\frac{u_p}{v_p}\boldsymbol{v}'.$$

Their nonzero positions therefore agree. The estimated number of surviving entries and its square also agree at the finite-field points where both leading coefficients remain nonzero. For either retained linear score, these shared terms cancel when we compare the two candidates. The remaining score difference is

$$s(S,1) - s(S,0) = \lambda \log \frac{1+n_1}{1+n_0} - \eta,$$

where S is the current row group, $s(S,i)$ is the score of candidate i, n_i is its number of nonzero entries, and candidate zero is the native source. The quantity λ is the coefficient of source length and η is the coefficient of the native-source indicator. The two retained policies use $(\lambda,\eta) = (2,0)$ and $(1/2,-0.01)$.

When this comparison selects source zero, the implementation retains that source without constructing cancellation features. Unsupported modular expressions already retain the native source, so the same decision also holds in that case. Other decisions follow the full feature calculation. The shortcut applies only to the stated sparse linear scores, and detailed diagnostic traces retain the full calculation.

We compare the shortcut enabled and disabled in 144 complete validation workflows. All seventy-two pairs agree on source-choice digests, operation counts, attempt outcomes and exact exports. The enabled path bypasses cancellation-feature construction in 42,702 row groups. The model-weighted ratios of decision time, forward-stage time and complete time are 0.345, 0.955 and 0.997, respectively. These ratios compare the same learned policy with and without the shortcut; they describe a reduction in inference cost without changing its algebraic choices.

A separate 4,096-entry cache for modular inverses also preserves all 144 validation reductions. Its forward-stage ratio is 1.002, its decision-time ratio is 1.024, and its complete-time ratio is 0.984. It fails the predefined forward-stage improvement criterion, so the retained implementation leaves this additional cache disabled. The original bounded cache of complete coefficient evaluations remains active.

15.14 Confirming the reduced inference cost

We freeze the two-row shortcut after validation and run a second comparison on the same eight previously reserved profiles. This confirmation preserves the model weights, seed thresholds, physical inputs, reference bases and routing rule. It does not supply eight additional independent families. The smaller native control, deterministic cancellation control, seed model, row model and combined policy each receive five repetitions on all sixteen batches, giving 400 workflows.

Every model and control uses the same new executable and temporary-storage settings. All 400 workflows complete and match their exact reference coefficients. They use 460 attempts, including sixty failed subset attempts whose time contributes to the completed workflows. Their

selected seed masks, committed operations, row-group counts and native exports also agree with the corresponding initial trials. Figure 33 separates complete time from the forward stage in this confirmation [33].

The seed model has a complete-time ratio of 1.155 to the smaller native control, with interval $[1.024, 1.316]$. The descriptive interval lies above one. Its forward-stage ratio is 1.083, with interval $[1.001, 1.186]$.

The row model has a complete-time ratio of 0.999 to the smaller native control, with interval $[0.992, 1.007]$. The descriptive interval includes one. Its forward-stage ratio is 1.041, with interval $[1.017, 1.065]$.

The combined policy has a complete-time ratio of 1.159 to the smaller native control, with interval $[1.030, 1.319]$. The descriptive interval lies above one. Its forward-stage ratio is 1.097, with interval $[1.010, 1.212]$.

For the two-loop sunrise profiles, the seed, row and combined complete-time ratios are 1.397, 0.992 and 1.400. The complete-time intervals are $[1.392, 1.402]$, $[0.985, 0.998]$ and $[1.388, 1.412]$, respectively. The row policy's forward-stage ratio is 1.044, with interval $[1.003, 1.085]$.

For the two-loop box profiles, the seed, row and combined complete-time ratios are 0.964, 1.012 and 0.969. The complete-time intervals are $[0.949, 0.979]$, $[1.003, 1.021]$ and $[0.959, 0.979]$, respectively. The row policy's forward-stage ratio is 1.028, with interval $[0.992, 1.065]$.

For the three-loop vacuum profiles, the seed, row and combined complete-time ratios are 1.319, 1.003 and 1.317. The complete-time intervals are $[1.129, 1.542]$, $[0.996, 1.010]$ and $[1.129, 1.537]$, respectively. The row policy's forward-stage ratio is 1.041, with interval $[1.007, 1.078]$.

For the three-loop ladder profiles, the seed, row and combined complete-time ratios are 1.001, 0.990 and 1.010. The complete-time intervals are $[0.999, 1.003]$, $[0.986, 0.994]$ and $[1.003, 1.017]$, respectively. The row policy's forward-stage ratio is 1.052, with interval $[1.047, 1.057]$.

Applying the row policy within the learned-seed workflow gives a complete-time ratio of 1.004 to seed selection alone, with interval $[1.000, 1.008]$. Its forward-stage ratio in that comparison is 1.013, with interval $[0.997, 1.031]$. These measurements include the model cost and the algebraic consequences of its choices.

The row model's complete-time ratio to the deterministic cancellation rule is 0.993, with interval $[0.983, 1.002]$. The deterministic rule receives the same two-row shortcut, which keeps this comparison matched.

The native integration audit verifies that every used seed belongs to the selected mask and that each learned row attempt loads the frozen policy for its physical class. It records 404 learned-seed attempts with 147,556 used selected seeds, and 324 learned-row attempts with 363,759 eligible groups and 5,795 changes from the native source. These counters show that the models affect native equation generation and the evolving elimination.

The aggregate row-operation reduction therefore does not establish a reduction in forward-stage time. The complete-time interval for the row policy includes one, while always enabling seed selection or both models increases aggregate complete time. The box cases support a conditional seed-model gain. The automatic rule remains the rule fixed on validation; the confirmation results do not retune it.




Figure 33: The implementation confirmation compares the same frozen models with the smaller native control after reducing two-row inference cost. The left panel shows complete-time ratios and the right panel shows forward-stage ratios. Each point uses five repeated complete reductions of the indicated batch. The physical profiles repeat those in the initial comparison; all algebraic choices and exact exports remain unchanged.

15.15 Reducing new targets from a known master basis

The reference answers above provide an independent benchmark check. The production interface also accepts only the physical family, target indices and prescribed master indices. It then determines the target coefficients through native IBP generation and exact elimination.

To state this distinction mathematically, let $\boldsymbol{I}$ be the vector of integrals in the generated system and let $A(d)$ be its IBP coefficient matrix. The identities give $A(d)\boldsymbol{I} = 0$. Native exact row operations replace this system by $U(d)A(d)\boldsymbol{I} = 0$, where $U(d)$ represents the valid elementary row operations. Once elimination expresses all requested targets through the prescribed masters, it gives

$$\boldsymbol{I}_{\mathcal{T}} = R_{\mathcal{T}}(d)\boldsymbol{M}.$$

Here $\boldsymbol{I}_{\mathcal{T}}$ contains the requested targets, $\boldsymbol{M}$ contains the supplied master integrals, and $R_{\mathcal{T}}(d)$ is the rational coefficient matrix calculated by Kira. The learned model chooses seeds and admissible source rows; the exact identities and row operations determine this relation.

The controller checks that every target has a reduction and that every integral on its right-hand side belongs to the supplied basis. An additional integral triggers the fixed seed expansion. The interface reports incompleteness if the allowed attempts fail. These checks establish completion relative to the supplied basis under native exact IBP algebra. They do not establish that an arbitrary supplied basis is globally minimal. If reference coefficients are available, the interface can additionally compare them exactly, and its records distinguish these two verification modes.

Eight application checks exercise native, seed, row, combined and automatic execution on sunrise and box inputs. The reducer receives master indices without target coefficients. After each run, a separate caller compares the result with the retained exact reference, and all eight checks pass. The application record includes input and routing time as well as the complete reduction time. It excludes lossless evidence compression and optional common release-integrity checks.

Automatic execution retains the routing rule fixed from validation. It enables a learned method only in the tested feature classes where validation found the required advantage, and uses native execution elsewhere. The individual model modes remain available for controlled comparisons. The reported model effects concern fixed rational kinematics, a known basis and symbolic dimension d. Generic multiscale reconstruction, unrestricted higher-loop families and global minimality remain outside this measured domain.

16 Reusing model calculations without changing reductions

The preceding comparison shows that model evaluation can offset savings in algebraic work. We therefore reduce repeated calculations inside the same models, while retaining their weights, seed thresholds, row choices and automatic routing rule. This section measures how the change affects both model evaluation and the complete reduction.

16.1 Sharing calculations in the seed network

The seed network uses the same family and target context for every candidate. Let $\boldsymbol{c} \in \mathbb{R}^{5h}$ be that context, $\boldsymbol{z}_j \in \mathbb{R}^h$ the embedding of candidate seed j, and $\boldsymbol{a}_j \in \mathbb{R}^h$ its attention-weighted target embedding. The embedding dimension is $h = 32$. The first score layer forms

$$\boldsymbol{h}_j = \tanh(W_c\boldsymbol{c} + W_z\boldsymbol{z}_j + W_a\boldsymbol{a}_j + \boldsymbol{b}),$$

where the matrices are the corresponding blocks of the existing weight matrix, $\boldsymbol{b}$ is its bias vector, and $\boldsymbol{h}_j$ is the hidden score vector. The term $W_c\boldsymbol{c}$ is common to all candidate seeds. We calculate its floating-point accumulator once and continue from that accumulator for each seed. The continuation preserves the original order of multiplications and additions.

The target-pair layer admits similar reuse. If $\boldsymbol{e}_i$ and $\boldsymbol{e}_k$ are two target embeddings, its pair embedding is

$$\boldsymbol{p}_{ik} = \tanh(U_1\boldsymbol{e}_i + U_2\boldsymbol{e}_k + U_3(\boldsymbol{e}_i - \boldsymbol{e}_k) + U_4(\boldsymbol{e}_i \odot \boldsymbol{e}_k) + \boldsymbol{b}_p).$$

Here $U_1, \ldots, U_4$ are blocks of the existing pair-layer matrix, $\boldsymbol{b}_p$ is its bias, and $\odot$ denotes componentwise multiplication. The first partial accumulator depends only on i, so we reuse it for each allowed k. The remaining operations and ordered-pair aggregation keep their original order. This removes repeated arithmetic without refitting the network.

All thirty-six development contexts give bitwise identical probability vectors and identical masks at the six tested thresholds. The largest probability difference is zero. The geometric mean ratio of new to preceding preparation and inference time is 0.527. These component measurements use repeated calls with the models already loaded; the complete-workflow comparisons below also include loading and fallback [34].

16.2 Sharing cancellation estimates between source choices

The two-row identity in the preceding section also applies to each pair within a larger group of equations. Let $\boldsymbol{R}_j$ and $\boldsymbol{R}_q$ be two coefficient rows whose first nonzero entries a_j and a_q multiply the same integral. If both entries are nonzero, the two possible updates give

$$\boldsymbol{R}'_j = \boldsymbol{R}_j - \frac{a_j}{a_q}\boldsymbol{R}_q, \qquad \boldsymbol{R}'_q = \boldsymbol{R}_q - \frac{a_q}{a_j}\boldsymbol{R}_j = -\frac{a_q}{a_j}\boldsymbol{R}'_j.$$

The updated rows differ by a nonzero scalar and therefore contain the same nonzero positions. Their predicted surviving-entry counts satisfy

$$\widehat{n}_{jq} = \widehat{n}_{qj}$$

at the valid finite-field points used by the policy. Here $\widehat{n}_{jq}$ is the predicted number of entries after source q updates row j. The union size, cancellation count and zero-row indicator also agree in the two directions.

We evaluate each unordered pair once and add its statistics to both candidate sources. The previous implementation evaluated both directions separately. The coefficient parser, finite-field

points, cache limits and invalid-input fallback remain the same. A further change reads fixed policy settings once per forward-reduction stage and evaluates only nonzero score coefficients. The policy calculates its normalized confidence when a requested decision record uses that value. The production path retains the selected source without calculating an unused confidence.

One thousand sparse-row checks compare all six cancellation features with the previous implementation. All checks agree, including 210 cases with invalid expressions or finite-field poles. Full validation then compares the old and new implementations on six batches from the three validation profiles. Its 180 workflows preserve probability vectors, masks, row-choice digests, operation counts, attempt outcomes and exact exports. The validation conditions require lower seed complete time, lower row decision time and a row complete-time ratio no larger than 1.02. These conditions are fixed before validation.

16.3 Complete calculations with the unchanged decisions

After validation, we freeze the implementation and compare five methods: native choices, the seed model, the row model, both models, and automatic routing. Each method runs with both implementations on the same sixteen batches from the eight physical profiles in the preceding section. Five repetitions give 800 complete workflows. We increase the confirmation from three to five repetitions before its freeze because validation shows execution-time variation between runs. This confirmation reuses the earlier physical profiles and provides no additional independent-family evidence.

The time includes preparation, model loading, inference, fresh IBP generation, exact elimination, back substitution, reference checks and every fallback. The common reference calculation, interpreter launch, top-level policy lookup and evidence compression remain outside the interval. Old and new runs alternate within each method, and method order rotates across repetitions. We take a median for each batch and use the same profile-weighted geometric ratios and descriptive bootstrap intervals as before.

All 800 workflows finish with exact reference agreement, using 920 attempts. The retained failures comprise 120 unsuccessful attempts and contribute to the completed workflow times. All 400 old–new pairs preserve the recorded algebraic choices and outputs. Across validation and confirmation, the independent parser verifies 269,820 coefficient equalities through exact polynomial cross multiplication in $\mathbb{Q}(d)$.

The native control has a new-to-preceding complete-time ratio of 0.997, with descriptive interval $[0.960, 1.030]$.

The seed model has a new-to-preceding complete-time ratio of 0.982, with descriptive interval $[0.970, 0.993]$.

The row model has a new-to-preceding complete-time ratio of 1.006, with descriptive interval $[0.978, 1.046]$. Its decision-time ratio is 0.669, and its forward-stage ratio is 0.977.

The combined method has a new-to-preceding complete-time ratio of 0.997, with descriptive interval $[0.976, 1.015]$. Its decision-time ratio is 0.647, and its forward-stage ratio is 0.966.

The automatic method has a new-to-preceding complete-time ratio of 0.982, with descriptive interval $[0.951, 1.009]$.

These comparisons isolate implementation cost while retaining each method's decisions. Comparing the new model paths with the new native control addresses the separate question of whether their choices repay the remaining model cost.

Relative to the new native control, the seed model has a complete-time ratio of 1.162, with interval $[1.019, 1.348]$, and a forward-stage ratio of 1.114.

Relative to the new native control, the row model has a complete-time ratio of 1.023, with interval $[1.002, 1.047]$, and a forward-stage ratio of 0.993.

Relative to the new native control, the combined method has a complete-time ratio of 1.145, with interval $[0.998, 1.334]$, and a forward-stage ratio of 1.065.

Relative to the new native control, the automatic method has a complete-time ratio of 0.998, with interval $[0.948, 1.049]$, and a forward-stage ratio of 0.987.

The seed implementation reduces the complete-time estimate by about 1.8% relative to its preceding implementation, and its descriptive interval remains below one. The row decision calculation takes about 33% less time, while the interval for complete row-model time includes one. The row comparison therefore resolves a reduction in decision cost but does not establish a reduction in complete time. The seed and row methods both have larger complete-time estimates than the new native control on this set of inputs. Automatic routing gives a ratio close to one, with an interval that spans both a gain and a loss. These measurements support the stated implementation savings within the tested inputs; they do not establish a general complete-reduction advantage for the learned policies.

The production interface uses the shared calculations with the unchanged validation-selected routing rule. Eight additional application checks supply only the family, target indices and master indices to the reducer, then compare its outputs independently with retained reference coefficients. All eight checks pass. The original model checkpoints, preceding implementations and negative comparisons remain available.

The operation counts are unchanged between implementations because the models choose the same seeds and source rows. The saving comes from calculating these choices with less repeated work. The comparison establishes measured costs for the stated two- and three-loop inputs with fixed rational kinematics and symbolic dimension d. A general gain across unrestricted higher-loop families and a globally fastest reduction remain outside this evidence.




Figure 34: Complete-time ratios after sharing model calculations. The left panel compares each method with its preceding implementation, and the right panel compares it with the new native control. Every point uses the median of five repetitions for one target batch. The tests keep model weights and algebraic choices fixed, include unsuccessful attempts, and reuse the preceding eight physical profiles.

17 Parallel seed evaluation and exact modular inverses

The shared calculations in the preceding section reduce repeated work, but the remaining model evaluation still contributes to the reduction time. We now evaluate independent outputs of the seed network together and use a different exact algorithm for modular division in the row features. We also reduce repeated coefficient parsing and storage allocation. The weights, thresholds, seed rules and source-row policy remain fixed, so this comparison measures the cost of calculating the same decisions.

17.1 Evaluating independent neural outputs together

Let $W \in \mathbb{R}^{n\times m}$ be a layer's weight matrix, $\boldsymbol{x} \in \mathbb{R}^m$ its input and $\boldsymbol{b} \in \mathbb{R}^n$ its bias. Here m is the number of input components and n is the number of output components. Each output uses the partial sums

$$y_j^{(0)} = 0, \qquad y_j^{(k+1)} = \mathrm{fl}\Big[y_j^{(k)} + \mathrm{fl}(W_{jk}x_k)\Big], \qquad k = 0, \ldots, m-1,$$

where j identifies an output component and fl denotes rounding to the existing 32-bit floating-point format. The layer then adds b_j and applies its activation when required. This expression states the order of arithmetic used by the preceding implementation.

The previous loop finishes one output before starting the next. The new loop advances several outputs at each input component k. These outputs are independent, so the compiler can evaluate four of them with one vector instruction while each output retains its original addition order. We store the weights with adjacent output entries and include this rearrangement in the model-loading cost. The shared target-context and target-pair partial sums from the preceding section remain in use. We retain separate multiplication and addition, the same activation functions, and the original target aggregation order.

All thirty-six development contexts give bitwise identical probability vectors. The selected masks also agree at all six tested thresholds. The geometric mean ratio of new to preceding preparation and inference time is 0.423. This component comparison uses five alternating repetitions with loaded models. The complete reductions below include loading and the weight rearrangement.

17.2 Computing modular inverses with Euclid's algorithm

The row policy evaluates rational coefficients at the same two finite-field points as before. Division by a nonzero field element a requires its inverse modulo the prime $p = 2^{31}-1$. The preceding implementation uses $a^{-1} = a^{p-2} \bmod p$. The extended Euclidean algorithm gives integers x and y such that

$$ax + py = 1, \qquad a^{-1} = x \bmod p.$$

Here x supplies the inverse because the greatest common divisor of a and p is one. The algorithm repeatedly divides the current integer remainders and updates the coefficients of a and p until it reaches that greatest common divisor.

We use this inverse in the same coefficient parser, including negative integer powers. The prime, evaluation points, cache bounds and unordered-pair cancellation estimates remain unchanged. A zero denominator still rejects that estimate and retains the existing fallback. These finite-field calculations guide the row choice; native Kira performs the symbolic row operations.

Integer coefficients have the same residue at both dimension points. For a coefficient $c \in \mathbb{Z}$, we calculate its residue r once,

$$r = c \bmod p, \qquad (c(17), c(19)) = (r, r) \quad \text{in } \mathbb{F}_p^2.$$

Here the two entries are the coefficient values used in the cancellation test, and $\mathbb{F}_p$ is the field of integers modulo p. For short integer expressions, this removes two general expression evaluations and the cache lookup. Other expressions retain the bounded parser and cache. We also allocate the evaluated coefficients for a row group in one contiguous array, which removes separate allocations for each row. These changes preserve every coefficient value and the order of the cancellation calculations.

Checks on 100,000 nonzero field elements agree with the preceding inverse and satisfy $aa^{-1} = 1 \bmod p$. A further 1,000 sparse-row checks agree on all six features, including the 210 cases with invalid expressions or finite-field poles. Five alternating repetitions give a ratio of 0.803 for new to preceding row-feature calculation time with cleared coefficient caches. The complete reductions also exercise the ordinary cache reuse and source-selection code.

17.3 Complete reduction costs and exact checks

We first tested the Euclidean inverse alone with the parallel seed calculation. Its 144 validation workflows preserved all decisions and exact exports, but its complete row-time ratio was 1.027 and its row-decision ratio was 1.017. Both missed the conditions stated below, so we retain this candidate as a rejected development result. The revised candidate adds the integer evaluation and contiguous storage described above. These changes use development and validation inputs; confirmation results do not select them.

The next 144 validation workflows compare native choices, seed selection, row selection and both learned choices on six batches from three physical profiles. We fix the adoption conditions before validation and require identical decisions and exports, lower seed complete time, lower row decision time and a row complete-time ratio at most 1.02. Both component comparisons must also improve.

After validation, we freeze the implementation and run the same four methods on sixteen batches from the eight physical profiles used in the preceding comparison. Five repetitions with each implementation give 640 workflows. These inputs provide a repeated implementation comparison and add no new independent-family evidence. Model weights and thresholds remain fixed.

Timing includes preparation, loading, prediction, fresh IBP generation, exact elimination, back substitution, reference checks and every fallback. Reference preparation, interpreter launch, release-hash verification, policy lookup and evidence compression remain outside the timed interval. We alternate the implementations within each method and rotate method order. We take the median for each batch and report the same profile-weighted geometric ratios and descriptive 95% bootstrap intervals as before. A ratio below one means less time. The internal decision timer covers completed policy paths. The complete workflow timer also includes feature evaluations that return an invalid estimate and retain the native source.

All 640 workflows pass the exact reference check, using 760 attempts, including 120 unsuccessful attempts. All 320 old–new pairs preserve probability vectors, selected seeds, row-choice digests, committed operations and exact exports. The independent audit verifies 215,856 coefficient equalities over $\mathbb{Q}(d)$ across the 784 validation and confirmation workflows [35].

The native control has a new-to-preceding complete-time ratio of 1.005, with descriptive interval $[0.976, 1.035]$.

The seed model has a new-to-preceding complete-time ratio of 0.990, with descriptive interval $[0.977, 1.003]$.

The row model has a new-to-preceding complete-time ratio of 0.990, with descriptive interval $[0.971, 1.010]$. Its decision-time ratio is 0.791, and its forward-stage ratio is 0.998.

The combined method has a new-to-preceding complete-time ratio of 0.984, with descriptive interval $[0.965, 1.007]$. Its decision-time ratio is 0.816, and its forward-stage ratio is 1.039.

The new native control provides a separate comparison for the cost and benefit of the learned decisions. It uses the same execution settings and exact checks.

Relative to that control, the seed model has a complete-time ratio of 1.096, with interval $[0.963, 1.275]$.

Relative to that control, the row model has a complete-time ratio of 0.982, with interval $[0.959, 1.003]$.

Relative to that control, the combined method has a complete-time ratio of 1.100, with interval $[0.966, 1.279]$.

All three new-to-preceding complete-time intervals include one. The component timings show lower evaluation cost, while these complete-workflow measurements leave the size of the overall change uncertain. Relative to native choices, the aggregate seed and combined ratios exceed one, and the row-only interval also includes one. The results therefore support lower model-evaluation cost within the measured scope; a general complete-time advantage over native Kira remains unestablished.

For the seed method, the complete-time ratios relative to native choices are 0.911 for the double boxes, 0.935 for the three-loop ladders, 1.380 for the sunrise integrals and 1.226 for the three-loop vacuum integrals.

For the row method, the complete-time ratios relative to native choices are 1.011 for the double boxes, 0.958 for the three-loop ladders, 0.962 for the sunrise integrals and 0.999 for the three-loop vacuum integrals.

For the combined method, the complete-time ratios relative to native choices are 0.902 for the double boxes, 0.945 for the three-loop ladders, 1.394 for the sunrise integrals and 1.232 for the three-loop vacuum integrals.

Eight further application checks supply family definitions, targets and master indices without supplying target coefficients. Independent comparisons after execution pass in all eight cases. The production interface uses the validated implementation with the unchanged routing rule.

The algebraic operation counts remain fixed between the two implementations. The time change comes from evaluating the same model decisions with different arithmetic. This distinguishes a reduction in model cost from a reduction in the algebra needed by Kira. The comparisons concern two- and three-loop inputs with fixed rational kinematics and symbolic dimension d; they do not establish a general speed advantage across unrestricted higher-loop or multiscale reductions.




Figure 35: Complete reduction times for the unchanged learned policies. The left panel compares the new implementation with the preceding shared calculations. The right panel compares each new method with the new native control. Each point is the median of five repetitions for one target batch, including failed attempts and fallback. A and B identify the two physical profiles within each topology, and the numbers give the target counts.

18 Target-dependent equation selection

The preceding policies choose seeds and source rows, but each retained seed can produce several identities. A third model selects identities for the requested targets before Kira performs modular independence elimination. This choice can reduce the system that Kira processes, provided that the saved algebraic work exceeds the cost of making the choice. We therefore measure equation preparation and the complete reduction with the model included [9, 36].

18.1 The equations and their training labels

Let $\mathcal{T}$ be the set of requested integral indices. An identity generated from seed $\boldsymbol{\sigma}$ and derivative or Lorentz-invariance operator o has the form

$$E_{\boldsymbol{\sigma},o}: \qquad \sum_{\boldsymbol{a}\in A_{\boldsymbol{\sigma},o}} c_{\boldsymbol{\sigma},o,\boldsymbol{a}}(\boldsymbol{x},d) I_{\boldsymbol{a}} = 0. \tag{109}$$

Here $A_{\boldsymbol{\sigma},o}$ is the set of integral indices that occur in the identity and $c_{\boldsymbol{\sigma},o,\boldsymbol{a}}$ is the coefficient of $I_{\boldsymbol{a}}$. The variables $\boldsymbol{x}$ and d retain their definitions as the kinematic parameters and integration dimension. The operator index distinguishes the several identities from one seed, so the third policy can retain only part of a seed's output.

We first run native Kira reductions on training families and record the integral supports of the equations retained in the final regenerated system. An integral support is the set of indices with nonzero coefficients after combining repeated terms at the finite-field selection point. If $\mathcal{S}_{\mathrm{native}}$ is the collection of these supports, the training label is

$$y_{\boldsymbol{\sigma},o} = \mathbf{1}[\mathrm{supp}(E_{\boldsymbol{\sigma},o}) \in \mathcal{S}_{\mathrm{native}}]\,. \tag{110}$$

The indicator $\mathbf{1}$ equals one when the condition holds and zero otherwise. Several equations can have the same support and different coefficients, so this label describes support membership in the recorded selection. It supplies a conservative training proxy and does not establish a necessary or smallest equation set.

The training collection contains 74,692 candidate equations, with 5,978 positive labels, from ten target batches in six physical profiles. These profiles comprise two-loop sunrise and double-box integrals and three-loop vacuum integrals. We keep three additional profiles for validation and eight for testing. The held-out tests also include a three-loop ladder topology absent from the training and validation collections. Each profile fixes rational masses and kinematic invariants, while the reductions retain symbolic dependence on d.

18.2 Features and the learned probability

The model receives 23 numerical features that describe the family, the target set, the seed and the generated equation. These features include the numbers of loops and external momenta, the number of integral indices, the target count, positive propagator powers, numerator powers, sector membership, the operator index and the equation's integral terms. For example, the distance from a seed to the targets is

$$\delta(\boldsymbol{\sigma},\mathcal{T}) = \min_{\boldsymbol{a}\in\mathcal{T}} \sum_{i=1}^{N} |\sigma_i - a_i|, \tag{111}$$

where N is the number of expressions in the integral family. The model also uses differences between the seed's dot or numerator counts and the largest corresponding counts in the target

set and in the same sector. These quantities describe which equations lie near the requested part of the integral-index lattice.

We fit a classification tree using weighted impurity reduction, with equal total weight for each training profile [30]. A sequence of feature comparisons leads to a leaf, which stores

$$p_{\boldsymbol{\sigma},o} = \frac{n_+ + 1/2}{n_{\mathrm{leaf}} + 1}, \qquad E_{\boldsymbol{\sigma},o} \text{ is retained if } p_{\boldsymbol{\sigma},o} \geq \tau. \tag{112}$$

Here n_+ is the number of positive training rows in that leaf, n_{leaf} is its total number of training rows and τ is the retention threshold. The fitted tree has 233 nodes and a maximum depth of eight. Each accepted split leaves at least 24 rows in each child. The score is a smoothed empirical frequency of the recorded label, and its numerical value has no separate calibration guarantee.

Training the tree takes 2.75 seconds after the native examples have been collected. This time excludes the generation of training reductions. We retain one additional diagnostic field for coefficient-text length, but exclude it from the decisions because equivalent coefficient expressions can have different printed lengths. The saved model and its compiled evaluator give identical probabilities for 18,754 candidates in the implementation checks.

18.3 Native integration and the cost of a decision

Kira constructs a candidate identity before the model first scores it. The retained identities then enter native modular equation processing. Symmetry identities and preferred-basis relations continue through their existing paths. The model scores the IBP and Lorentz-invariance identities at the generation interface; it does not replace Kira's later algebraic independence checks.

Several operators share one seed, so we calculate their common seed-to-target features once. We also store each seed–operator decision. When Kira later requests the same identity, a stored omission allows the generation code to skip rebuilding its coefficients. A retained identity is regenerated through the native code. The tree also calculates an equation feature only when a comparison on its chosen path needs that feature. Propagator and numerator counts come directly from the native integral ordering. These saved decisions avoid repeated predictions and remove part of the repeated equation generation. Exact comparisons check that the implementation changes preserve the decision features, probabilities, masks and reduction results.

After reduction, we require every target to lie in the prescribed master basis. An incomplete filtered attempt triggers an unfiltered native attempt, followed by an enlarged native seed range when necessary. The benchmark additionally compares every exported rational coefficient with an independently stored native reference. The application interface requires the master basis and can operate without reference target coefficients; we check these application outputs separately after the reducer returns.

18.4 Validation and held-out comparisons

We select thresholds using complete reduction times on the three validation profiles. A topology uses the learned filter in the automatic route only when its validation time ratio is below 0.98; other topologies retain native equation choices. The test also includes a forced learned filter and a deterministic distance filter using Eq. (111). Validation selects each filter's threshold before the test runs, and the saved hashes fix the model, integration and test protocol.

The test contains fourteen target batches from eight physical profiles. Each sunrise batch contains 21 targets; the other profiles use batches of 32 and 128 targets. Five alternating repetitions

compare native choices, the forced learned filter, the distance filter and the automatic route, giving 280 complete workflows. All four arms use the same compiled binary, with native choices switching off the three learned policies. Each time includes preparation, loading, predictions, equation generation, exact algebra, output checks and all failed attempts before fallback. The experiment driver is already running when timing begins; Kira process startup and model loading are included. Creation of the independent references and compression of the evidence files lie outside this timer.

Equation preparation includes generation with modular processing, equation selection, modular solving and equation regeneration. It therefore measures the full preparation affected by the filter. We report median times within each batch and geometric ratios with equal weight for each physical profile. Descriptive intervals resample these eight profiles 10,000 times. These intervals describe this finite set of profiles and do not establish performance for arbitrary multiloop families.

18.5 Results and scope

The validation route is double box: off, sunrise: learned at $\tau = 0.001$, vacuum3: learned at $\tau = 0.0001$. Other topologies use native equation choices. The forced learned filter uses $\tau = 0.001$, while the distance filter retains seeds with $\delta \leq 4$. These choices remain fixed throughout the held-out tests.

All 280 complete workflows reproduce their native reference coefficients. The independent audit checks 91,240 coefficient pairs, including 1,931 distinct expression pairs, by exact rational simplification in d. The workflows contain 40 failed filtered attempts before successful fallback, and their times include these attempts. Native median complete times range from 0.785 to 5.880 seconds across the fourteen batches.

The forced learned filter has a complete-time ratio of 1.080, with descriptive interval $[0.976, 1.220]$. Its equation-preparation ratio is 1.053, with descriptive interval $[0.904, 1.224]$. The generated-equation ratio is 0.769, and the selected-equation ratio is 0.985. All ratios use the matched native control, so a value below one indicates a lower measured cost.

The distance filter has a complete-time ratio of 1.016, with descriptive interval $[0.994, 1.040]$. Its equation-preparation ratio is 1.089, with descriptive interval $[1.035, 1.144]$. The generated-equation ratio is 1.000, and the selected-equation ratio is 1.000. All ratios use the matched native control, so a value below one indicates a lower measured cost.

The automatic route has a complete-time ratio of 1.098, with descriptive interval $[0.981, 1.259]$. Its equation-preparation ratio is 1.062, with descriptive interval $[0.896, 1.261]$. The generated-equation ratio is 0.849, and the selected-equation ratio is 1.000. All ratios use the matched native control, so a value below one indicates a lower measured cost.

The automatic route does not lower the aggregate complete time in this test. Equation-count changes therefore do not establish an overall runtime gain.

After freezing the model, we also collect 77,246 held-out candidate labels, with 6,932 positive labels. At the forced learned threshold, precision is 11.33% and recall is 95.63%, with mean squared probability error 0.0621. These quantities measure agreement with the native support-membership proxy. Exact coefficient comparisons measure the validity of the resulting reductions.

A further 48 complete workflows test the equation route together with the existing row policy and with both existing policies on four profiles. Adding the equation route gives a complete-time ratio of 1.165 to the row-only configuration and 1.184 to the configuration with both earlier




Figure 36: Median complete-time ratios for the fourteen held-out batches. Each point uses five repetitions and includes checks and fallback. The dashed line is the native control.




Figure 37: Profile-weighted geometric ratios of complete time, equation preparation time and generated-equation count. Bars show descriptive intervals from resampling the eight physical profiles.




Figure 38: Held-out model scores grouped by the native support-membership label. The vertical scale is linear near zero and logarithmic above ten equations. The labels describe selected supports rather than necessary equations.

models. These comparisons use three repetitions and retain all fallback costs. All pass the reference checks. Eight application runs also pass exact coefficient comparisons after execution with reference coefficients withheld from the reducer.

The early full-feature implementation and subsequent feature-sharing implementations remain in the evidence collection, including their slower results. The final comparison uses the frozen implementation selected before held-out testing. Its performance depends on target size, topology and the cost of generating and reducing the retained equations. The experiment covers physical two- and three-loop reductions at fixed rational kinematics with symbolic d; it does not establish gains on arbitrary higher-loop or fully multiscale problems [36].

18.6 The domain selected before testing

Validation enables the equation model for the sunrise and three-loop vacuum topologies. This identifies four of the eight test profiles before any test timing is available. On these profiles, the automatic route has a complete-time ratio of 1.194, with descriptive interval $[0.951, 1.498]$. Its equation-preparation ratio is 1.078, with descriptive interval $[0.765, 1.519]$. The corresponding generated-equation ratio is 0.722.

For sunrise profiles, the automatic complete-time ratio is 0.951 and the preparation ratio is 0.765. For vacuum3 profiles, the automatic complete-time ratio is 1.498 and the preparation ratio is 1.519. For double box profiles, the automatic complete-time ratio is 0.991 and the preparation ratio is 0.988. For ladder3 profiles, the automatic complete-time ratio is 1.027 and the preparation ratio is 1.110. The double-box and ladder routes retain native equation choices, so differences between their automatic and native timings mainly reflect repeated-run variation and routing overhead. The all-profile comparison remains the primary result; these fixed-domain results state where the learned filter was active.

18.7 Restricted deployment and fresh confirmation

The broad test exposes incomplete equation filters in the new vacuum profiles. Their native fallback retains exact results and adds cost. We therefore fix a restricted deployment using the same trained tree. It enables the equation filter at $\tau = 0.001$ for the recorded 21-target sunrise batches and retains native equation choices for other topologies and target sets. The broader test supplies development evidence for this deployment revision.

Each supported batch contains the top-sector scalar integral and its one-dot and one-numerator variants, together with the corresponding integrals in the three two-propagator sectors. This gives 21 targets whose index vectors are fixed in the deployment definition. We reserve six additional mass and momentum profiles before running their reductions. None of these profiles occurs in the preceding training, validation or broad-test sets. Their squared masses and external invariant are fixed rational numbers, while d remains symbolic. The tree, threshold, target domain and new profile definitions are fixed before this confirmation begins.

Nine alternating repetitions compare the learned filter, native choices and the previously selected distance control in each profile. These 162 complete workflows use the same timing and exact-check rules as the preceding test, including every failed attempt.

The learned filter has a complete-time ratio of 0.994, with descriptive interval $[0.991, 0.997]$ and an equation-preparation ratio of 0.785, with descriptive interval $[0.776, 0.794]$. Its generated-equation ratio is 0.414, and its selected-equation ratio is 1.000. The distance control has a complete-time ratio of 1.003, with descriptive interval $[1.000, 1.006]$.

The complete-time interval remains below one for these six profiles, supporting a measured gain within the restricted domain.

A further 36 workflows compare the existing seed and row policies with the configuration that also includes the equation filter. Adding the third model gives a complete-time ratio of 1.317, with descriptive interval $[1.296, 1.337]$ and a preparation ratio of 1.151, with descriptive interval $[1.136, 1.168]$ to the two-model configuration. This comparison uses three repetitions in each of the six profiles.

All 162 main workflows, 36 composition workflows and six basis-only applications pass the independent exact audit, which checks 7,582 coefficient pairs. The 204 workflows include 54 failed attempts. The six applications receive the prescribed masters without reference target coefficients, and their outputs pass coefficient comparisons after execution.

Native median complete times range from 0.692 to 0.709 seconds in these six profiles. The geometric mean preparation fraction of native complete time is 3.29%. This small fraction explains why the reduction in preparation time produces a smaller change in complete time. The main confirmation has zero failed attempts; all 54 failed attempts in its extended audit arise in the composition comparisons.

The application interface enables this equation policy when it runs with native seed and row choices. Requests for either earlier learned policy retain native equation choices. This guard avoids the slower measured three-model combination. The broader initial route and its slower vacuum results remain available as experimental evidence. The measured domain contains two-loop sunrise integrals with the stated target set, and extension to other target sets or topologies requires further independent evidence [36].




Figure 39: Fresh confirmation of the restricted sunrise deployment. Each profile uses nine repetitions for each method. Complete and preparation times include prediction and fallback costs.

18.8 Predicting equations before constructing their coefficients

The preceding equation model first inspects a constructed identity, so its initial prediction still requires that identity's coefficients. To reduce this cost, we train a new version of the same model that uses only the seed, the operator and the requested targets. This moves the decision to the point where Kira can avoid constructing an omitted identity.

A diagnostic study motivates this change. In twelve exact native runs, equation preparation forms the largest recorded block in the 128-target three-loop ladder reductions. The two ladder profiles have median preparation intervals of 1.41 and 1.23 seconds, within complete times of 4.23 and 4.36 seconds. Initial family preparation and equation preparation together account for about 54–55% of those times. These diagnostic intervals come from logged stage boundaries and include wrapper costs; the final comparison below uses the internal timers defined for this study.

For the identity in Eq. (109), the new decision has the form

$$\widehat{p}_{\boldsymbol{\sigma},o} = f_\theta(\phi(\boldsymbol{\sigma}, o, \mathcal{T}))\,, \qquad \widehat{p}_{\boldsymbol{\sigma},o} \geq \tau \implies E_{\boldsymbol{\sigma},o} \text{ is constructed.} \tag{113}$$

Here ϕ is the vector of features available before construction, f_θ is the classification tree with trained parameters θ, and τ is the retention threshold. The 17 features describe the numbers of loops, external momenta and indices, the target count, the seed's sector, dots and numerator rank, their differences from target limits, the distance in Eq. (111), whether the seed is itself a target, and the operator index. The tree therefore has no need to inspect the equation's coefficients or integral terms.

Kira supplies the ordered IBP operators, and the integration retains their positions when it omits an equation. Several operators share the same seed features, so we calculate those features once and store the decision for each seed–operator pair. Kira constructs accepted equations through its native algebra and reuses the stored decisions during later regeneration. Symmetry identities and preferred-basis relations retain their existing treatment. This placement reduces both repeated model work and the initial construction of identities that the model rejects.

We retain the support-membership labels in Eq. (110) and add four training batches from two new ladder profiles. The combined collection contains 153,124 candidate equations, including 12,270 positive labels, in fourteen batches from eight physical profiles. These profiles contain the two-loop sunrise and double-box and the three-loop vacuum and ladder structures. We fit trees with maximum depths eight and twelve, using equal total weight per profile and the same smoothed leaf frequency as before [30]. The trees contain 295 and 1,335 nodes and take 3.39 and 5.85 seconds to fit after collection of the native training reductions. Their splits leave at least 24 and eight rows in each child, respectively. A separate implementation check compares 918,744 decisions and finds agreement between the stored Python features and the C++ evaluator's recomputed seed features.

The training label still describes membership in a recorded native equation selection. It supplies neither a smallest sufficient equation set nor a calibrated completeness probability. Kira therefore checks whether the result expresses each target in the prescribed master basis. If the filtered equations are insufficient, the application retries native equations and then a larger native seed region. Exact algebra determines all coefficients, and the benchmark additionally compares them with an independent native reduction.

18.9 Selecting the complete calculation on validation profiles

We compare both trees at thresholds 0.001, 0.003 and 0.01 with native choices and a distance filter. Repeated validation requires at least 1% lower complete time, at least 5% lower equation-

preparation time and no fallback before activating an early filter. We then measure combinations with the existing seed and row models. An additional model must lower complete time by at least 1% relative to early filtering alone and require no fallback in validation.

The validation record contains 77 initial candidate and control workflows, 84 repeated candidate workflows, 72 row-composition workflows and 96 seed-composition workflows. A second vacuum profile checks another mass pattern in the composition stage. Adding the row model gives less than 1% incremental saving in the ladder and vacuum comparisons and increases double-box time. Seed combinations require extra attempts for some larger double-box and vacuum batches. These costs remain in the comparisons and prevent those combinations from meeting the activation rule.

Validation therefore selects the depth-twelve tree for double-box batches and the depth-eight tree for vacuum and ladder batches, with $\tau = 0.01$. The final route retains native seed and row choices. It keeps the preceding equation policy for the recorded 21-target sunrise batch, where early filtering fails the validation activation rule. Other structures and ordered target lists use the preceding guarded route. This selection minimizes measured cost among the eligible validation candidates; it does not establish a globally fastest reduction.

We preserve an excluded preliminary collection whose proposed additional profiles overlapped earlier reserved definitions. We replace those profiles before the final collection and exclude every provisional row, model and outcome from the results above. The final training, validation and test profiles are distinct. They can share topologies, target indices and lower-sector integral structure.

18.10 Independent complete-reduction comparison

We fix the models, integration, thresholds and target domains before testing eight additional physical profiles. Two profiles belong to each of the sunrise, double-box, vacuum and ladder structures. Sunrise uses 21 targets, and each remaining profile uses batches of 32 and 128 targets. Five alternating repetitions compare native choices, the preceding release, the deployed early policy and the validation-selected distance filter. This gives 280 complete comparison workflows. The same new binary runs the native, early and distance arms; the preceding release uses its saved binary and policy. The native control includes the existing project runtime improvements and switches off learned choices.

The profiles fix rational squared masses and external invariants, while d remains symbolic. The sunrise squared masses are $(2, 7, 11)$ and $(3, 7, 13)$, with $p^2 = -101$ and -103, respectively. The double-box pairs are $(s, t) = (-101, -103)$ and $(-107, -109)$. The vacuum squared-mass vectors are $(1, 1, 1, 1, 1, 11)$ and $(1, 1, 1, 13, 13, 13)$, and the ladder squared-mass vector is $(1, 0, 0, 0, 0, 0, 0, 0)$ with $p^2 = -101$ and -103. Here p is the external momentum of each two-point family, and s and t are the independent four-point invariants of the double-box family. These values use the common mass scale of the family definitions. The coefficient comparisons therefore take place in $\mathbb{Q}(d)$, the field of rational functions of d with rational coefficients. The graph structures and ordered target lists are known from development; the new profiles test transfer across masses and invariants within that domain.

Complete time includes route selection, input preparation, model loading and evaluation, Kira startup, IBP generation, exact algebra, basis and coefficient checks, cleanup and every fallback. The comparison driver is already running. Independent reference and master-basis preparation, the later independent audit and compression of retained results lie outside the timer. Equation-preparation time includes modular generation, selection and solving, together with symbolic equation regeneration. These internal intervals differ from the broader diagnostic intervals used to locate the initial bottleneck.

We take the median of five repetitions within each batch, average logarithmic time ratios over sizes within a physical profile, and give each profile equal weight. Descriptive 95% intervals resample whole profiles 10,000 times. For methods A and B, the reported ratio is

$$R_{A/B} = \exp\left[\frac{1}{G}\sum_{g=1}^{G}\frac{1}{|B_g|}\sum_{b\in B_g}\log\frac{\widetilde{T}_{A,b}}{\widetilde{T}_{B,b}}\right], \tag{114}$$

where G is the number of physical profiles, B_g is the set of batches for profile g, and $\widetilde{T}_{A,b}$ is the median complete time for method A and batch b. The same expression applies to preparation time. A ratio below one means that method A uses less time.

The deployed policy has a complete-time ratio of 0.943 to native choices, with descriptive interval $[0.915, 0.970]$, and a preparation ratio of 0.638, with interval $[0.546, 0.734]$. These correspond to 5.7% lower complete time and 36.2% lower preparation time in the profile-weighted comparison. Its complete-time ratio to the preceding release is 0.943, with interval $[0.912, 0.974]$. Its ratio to the distance control is 0.934, with interval $[0.904, 0.965]$.

For the two-loop sunrise profiles, the complete-time ratio is 0.986 and the preparation ratio is 0.819. For the two-loop double box profiles, the complete-time ratio is 0.884 and the preparation ratio is 0.655. For the three-loop vacuum profiles, the complete-time ratio is 0.958 and the preparation ratio is 0.453. For the three-loop ladder profiles, the complete-time ratio is 0.947 and the preparation ratio is 0.681.

Across fourteen batches, native median complete times range from 0.593 to 2.709 seconds, and deployed medians range from 0.589 to 2.579 seconds. Summing one median per batch gives 21.83 seconds for native choices and 20.28 seconds for the deployed route. This workload sum uses a different weighting from Eq. (114).




Figure 40: Complete and equation-preparation time relative to native choices. Points use physical-profile weighting and intervals resample profiles. Each topology has two new physical profiles.

All 280 comparison workflows and 8 additional applications pass the independent exact audit. The applications receive only the prescribed basis, and their coefficients agree with the reference after execution. The audit checks 94,970 coefficient pairs, including 1,915 distinct pairs. Every method completes on its first attempt. Maximum sampled memory for Kira and its child processes is 53.46 MiB, and maximum temporary solver storage is 1.39 MiB.

These results test a trained decision before native equation construction, with complete costs and exact output checks. They establish the measured domain at fixed rational kinematics.




Figure 41: Median complete time for each fixed target batch, including inference, exact checks and all fallback attempts. Each point is the median of five alternating repetitions.

General symbolic multiscale coefficients, new graph structures, broader target lists and high-loop reductions require separate evidence. Section 19 supplies subsequent tests on new scattering structures with independent symbolic invariants. The earlier negative comparisons remain part of the study, and the selected route activates only the combinations supported by validation [37].

18.11 Equation selection and shared reductions at higher loop orders

The preceding native comparisons cover specific structures with two or three loops. To study the higher orders already present in the integral collection, we now use the coupled vacuum family in Eq. (52). This family has one power of each massless denominator and two to four distinct massive denominators that depend on the same momentum Q. Its Euler identities and mass partial fractions remain valid for any positive integer number of loops. This structure allows us to test every order from one through twelve with an exact reference, while keeping the family restriction explicit.

The dependence on the loop order suggests a further reduction in repeated work. Let $B = \sum_j b_j$, retain the squared-mass scale μ, and define

$$z = L(d-2), \qquad W_{\boldsymbol{b}}^{(L)} = \mu^{B-1} V_{\boldsymbol{b}}^{(L)}. \tag{115}$$

The rescaling gives every $W_{\boldsymbol{b}}^{(L)}$ the same mass dimension as the masters $M_j^{(L)}$. Equations (56) and (55) then become

$$0 = (z - 2B) W_{\boldsymbol{b}}^{(L)} + 2 \sum_j b_j \rho_j W_{\boldsymbol{b}+\boldsymbol{e}_j}^{(L)}, \tag{116}$$

$$0 = (\rho_i - \rho_j) W_{\boldsymbol{b}}^{(L)} - W_{\boldsymbol{b}-\boldsymbol{e}_i}^{(L)} + W_{\boldsymbol{b}-\boldsymbol{e}_j}^{(L)}. \tag{117}$$

Here ρ_j is the positive squared-mass ratio defined earlier, and the second identity requires $b_i, b_j > 0$. The coefficient equations depend on L only through z. We can therefore solve one

system over $\mathbb{Q}(z)$ at fixed rational mass ratios and obtain

$$V_{\boldsymbol{b}}^{(L)} = \mu^{1-B} \sum_{j=1}^{R} C_{\boldsymbol{b}j}\big(L(d-2);\boldsymbol{\rho}\big) M_j^{(L)}. \tag{118}$$

Each $C_{\boldsymbol{b}j}$ is a polynomial in z with rational coefficients in the present domain. The master integrals retain their physical dependence on L. The shared calculation supplies their reduction coefficients.

We next reduce the number of identities passed to Kira. For a mixed integral, the model scores each allowed pair (i, j) in Eq. (117). The selected identity replaces that integral with two integrals of total massive power $B-1$. We repeat the choice for the resulting integrals and merge repeated dependencies across the target batch. An integral with only one massive denominator uses Eq. (116) at the seed $(k-1)\boldsymbol{e}_j$ to reduce power k. At $B = 1$, the integral belongs to the prescribed master basis. This decreasing total power proves termination and sufficiency for every allowed model choice. Mass partial fractions carry no IBP seed; the saved dependency choices also determine the actual Euler seeds with one massive denominator.

The training reference counts the distinct nonmaster integrals in recursively chosen dependency sets. If $\mathcal{D}(\boldsymbol{b})$ denotes such a set, the candidate cost is

$$c(\boldsymbol{b}; i, j) = \left|\{\boldsymbol{b}\} \cup \mathcal{D}(\boldsymbol{b} - \boldsymbol{e}_i) \cup \mathcal{D}(\boldsymbol{b} - \boldsymbol{e}_j)\right|. \tag{119}$$

Every pair tied for the smallest candidate cost receives label one. The recursion fixes a valid local reference and does not establish the minimum cost for an entire target batch. We train small classification trees using the ordered massive powers, pair positions, active-denominator count and simple power summaries. There are 18 features, with no loop order feature. The absence of L follows from Eqs. (116)–(117). A leaf score is an empirical training frequency. The runtime selects the highest score and uses exact identities for the algebra. For two active massive denominators, the single available pair is selected directly.

The training set contains 2,016 candidate actions in 546 exponent shapes, with total power through nine. We fit depth limits four, eight and twelve using a minimum child size of four examples. Validation selects the depth-4 candidate, which contains 15 nodes. On 277 distinct development coefficients, the reader agrees with symbolic algebra and takes 0.159 seconds, compared with 4.149 seconds for the symbolic reader. This reading improvement applies to every comparison arm and is separate from the learned decision.

Kira solves each selected system through its interface for supplied systems [11, 9]. We generate the Euler and mass identities within the measured workflow and use the same native elimination policy for every comparison arm. This experiment measures supplied-identity reductions. It does not measure Kira's native generation of a general IBP system at higher loop orders. The earlier native benchmarks retain that separate role.

The integration reads the exported coefficients with bounded rational polynomial arithmetic and checks that polynomial division leaves zero remainder. Development comparisons against symbolic algebra check this reader independently. The final check uses the Taylor partial fraction formula in Eq. (62), which does not follow the selected dependency path. The workflow rejects unresolved nonmaster integrals and retains a fallback to the full equation pool. Timings include input and model loading, selection, equation construction, Kira, coefficient reading, substitution, verification and any fallback. We also report external process times, which include Python startup and evidence writing. Queue waiting time and offline training are excluded.

The refined validation contains 144 workflows on six batches of mass profiles. It compares the three trees with first-pair, smallest-pair, largest-pair and extreme-pair rules and the full pool. Each candidate has three repetitions. The extreme-pair rule chooses an active denominator with

the smallest power and one with the largest power. Validation selects the extreme route; the selected learned candidate costs 1.7% more than the selected rule. We freeze sources, weights, profiles and target lists before 90 reserved workflows. The reserved set has two profiles for each of $R = 2, 3, 4$, with maximum powers eight and twelve, and runs every $L = 1, \ldots, 12$. Some exponent shapes with lower powers also occur in training; the cases with maximum power twelve extend its power bound. The tests vary mass profiles within the same topology and do not test new graph classes. We use three repetitions and report geometric means of the six ratios of batch medians. Descriptive intervals resample those six batches.

For each mass profile and target batch, we compare separate reductions with the full equation pool at each L, separate learned reductions, a shared reduction with the full equation pool in z, a shared reduction with a simple rule, and a shared learned reduction. The full pool contains Euler seeds through the largest target power and all mass-pair identities through one additional power. The control with a simple rule uses the rule selected on validation. All arms use the same project Kira binary with the earlier runtime improvements and native row choices. These controls separate the benefit of exact loop reuse from the benefit of selecting a smaller equation set.

For separate reductions at each loop order, learned selection gives a complete-time ratio of 0.911 to the full pool, with descriptive interval $[0.815, 0.986]$. With exact loop reuse in both arms, learned selection gives a ratio of 0.925 to the shared full pool, with interval $[0.889, 0.958]$. The learned/shared ratio to the rule/shared control is 0.968, with interval $[0.927, 1.003]$. These comparisons keep the incremental learned effect separate from the exact reuse of coefficient equations.

The deployed shared route gives a complete-time ratio of 0.155 to separate reductions with the full equation pool, with interval $[0.132, 0.184]$. This corresponds to 6.47 times faster execution of the twelve-order workload under the stated timing definition. Figures 42 and 43 show the batch costs and equation counts. Validation fixes the deployed rule before these tests; we retain the learned results as a measured alternative.

We separate calculation time from the cost of starting Python and archiving the test evidence. Before those two outer costs, the separate learned route has time ratio 0.943, with descriptive interval $[0.873, 0.995]$, to the full pool. The time spent inside Kira has ratio 0.965, with interval $[0.925, 0.992]$. Thus the calculation saves 5.7% and Kira itself saves 3.5% in this comparison. Archiving fewer source equations contributes to the larger saving in external process time.

With shared coefficients, the ratio of calculation times of the learned route to the full pool is 0.966, with interval $[0.941, 0.982]$. Its ratio to the control with a simple rule is 0.997, with interval $[0.984, 1.011]$. This comparison does not establish an added advantage over the simple rule. The deployed shared calculation has ratio 0.128 to separate calculations with the full equation pool, with interval $[0.102, 0.164]$. The exact change of variable supplies the main reduction in repeated work.

All 90 reserved workflows and six additional applications pass exact checks. The extra applications use loop orders 13, 16, 24 and 32. The audit checks 65,504 coefficient positions, including 5,696 distinct positions, across 492 Kira calls. It finds 0 failed attempts and 0 fallback workflows. The largest sampled memory of Kira and its child processes is 23.05 MiB, and the largest temporary solver storage is 0.58 MiB. The analytic reference also supplies a direct reduction for this special family. The reported comparisons measure routes that use Kira.

Equation (118) holds for any positive L in this scalar family. The finite tests cover the stated orders. Generic scattering families contain additional scalar products, numerator powers and kinematic variables, so their native IBP reduction needs separate tests. These results apply to the stated coupled vacuum family and supplied identities [38].




Figure 42: Median external complete times for the twelve loop orders in each reserved batch. Each bar includes the full cost of its stated workflow. The shared methods solve once in z and check the substituted coefficients separately at every requested loop order.




Figure 43: Separate-loop solver-time ratios and generated equation counts. The left panel includes construction, prediction, Kira and coefficient reading for each loop order; the complete workflow also includes the checks shown in Fig. 42. The intervals describe variation across the six reserved batches.

18.12 Learning equation choices for groups of targets

The shared variable in Eq. (115) removes repeated reductions at different loop orders. We now reduce repeated work within each target set and across independent mass profiles of the same restricted vacuum family. The calculation still uses one power of every massless denominator and $R = 2, 3, 4$ distinct massive denominators. Kira performs exact elimination on the supplied Euler and partial-fraction identities, and the retained native IBP-generation interfaces continue to serve their previously tested two- and three-loop domains.

For a target set $\mathcal{T}$, let π specify an ordering of the R massive denominators. At each mixed integral, we use the first two active denominators in this ordering in Eq. (117). Every resulting integral has a smaller total power B, and repeated integrals share the same subsequent reduction. Let $\mathcal{D}_\pi(\mathcal{T})$ be the resulting set of distinct nonmaster integrals. To train a model that favors small shared systems, we assign the cost

$$S_\pi(\mathcal{T}) = \sum_{\boldsymbol{b}\in\mathcal{D}_\pi(\mathcal{T})} \left(3\sum_{j=1}^{R} b_j - 2 \right). \tag{120}$$

The weight increases with the number of polynomial coefficients that can enter a substitution. It provides a training measure of algebraic work; actual Kira operation counts and the cost of large rational numbers also depend on its elimination and simplification choices. The smallest S_π among the $R!$ mass orderings supplies a restricted reference for the quality of a choice. More general reduction paths can have different costs.

We train ensembles of four and sixteen extremely randomized regression trees [39] to predict $\log S_\pi$, then select the ordering with the smallest predicted value. The 32 inputs describe the target count, number of massive denominators, total powers, the mean and mean squared power at each position of π, the largest power, the fraction of targets with that denominator present, and pairwise mean minima and products of powers. These inputs describe sharing across the entire target set. Each prediction estimates the reduction cost, while exact identities and Kira determine the reduction coefficients. Two massive denominators admit a single pair, so those requests bypass inference.

The training set contains 420 target batches and 6,300 candidate orderings, with total powers up to fourteen and at most 128 targets per batch. Both ensembles have maximum depth twelve and at least three training examples per leaf. We compare their complete calculation times with four simple ordering rules, the earlier learned pair selector, and enumeration of all fixed orderings. The first validation uses 324 calculations on twelve new mass profiles and selects the four-tree ensemble as the cheaper learned candidate. Its time ratio to the fastest simple rule is 1.000, so single-profile deployment retains that rule. A further 48 validation applications combine three profiles at a time and give a learned-to-simple time ratio of 0.925, which selects learned ordering for that route.

The selected trees require 7634 nodes in total. We also store their unchanged thresholds and leaf values in compiled inference routines to reduce loading and prediction cost. All 12,600 compared candidate scores agree exactly with the original tree evaluation. For the selected ensemble, compiled evaluation takes 0.921 times the Python decision time over the training batches. Fresh complete-calculation validation then chooses the inference implementation used for production calculations; this comparison includes model loading and inference and measures the time of the complete calculation.

18.12.1 Sharing exact checks and Kira calls

The original shared reduction still expanded and checked the same coefficient separately at each requested loop order. We instead compare the Kira coefficient $C_{\boldsymbol{bj}}(z)$ with an independent Taylor partial-fraction construction directly in $\mathbb{Q}[z]$. Exact equality in this polynomial ring implies equality after the substitution $z = L(d-2)$ for each requested L. Every returned coefficient therefore keeps an exact check while each symbolic comparison takes place once.

We also use integer polynomial arithmetic when reading the coefficients and applying the substitution. If $C(z) = D^{-1}\sum_{n=0}^{q} a_n z^n$, where the a_n are integers and D is a positive common denominator, then the coefficient of d^k after substitution is

$$[d^k]C(L(d-2)) = \frac{1}{D}\sum_{n=k}^{q} a_n L^n \binom{n}{k}(-2)^{n-k}. \tag{121}$$

Here q is the polynomial degree and $[d^k]$ denotes extraction of the coefficient of d^k. This form keeps the inner sums in integer arithmetic and reduces the number of repeated fraction normalizations. These savings follow from exact algebra, separately from the learned choice of equations.

Independent mass profiles can also share a Kira invocation. We give each profile its own integral identifiers and master basis, then form

$$A = \operatorname{diag}(A_1, \ldots, A_P), \qquad A \begin{pmatrix} \boldsymbol{I}_1 \\ \vdots \\ \boldsymbol{I}_P \end{pmatrix} = 0. \tag{122}$$

Here P is the number of profiles, A_p is the coefficient matrix of the selected identities for profile p, and $\boldsymbol{I}_p$ contains its integrals. Kira reduces this combined system in one call. The output checks require each target to contain only masters of its own profile, after which the same independent symbolic checks apply. The learned model chooses the equations for each profile before assembly. The current interface admits up to eight profiles, 512 targets and 12,000 selected equations per call. The timing tests use three profiles per call. A failed combined reduction retries the profiles separately, and a failed selected system uses the preserved full supplied system.

18.12.2 Independent timing and correctness results

The first reserved comparison uses twelve new mass profiles, powers up to fourteen, up to 96 requested targets per profile and every loop order from one through twelve. Five repetitions of five methods give 300 complete calculations. The learned route with shared checks has time ratio 0.394 to the preceding release, with descriptive interval $[0.314, 0.487]$. Its ratio to the updated simple rule is 0.986, with interval $[0.955, 1.019]$. These measurements separate the common arithmetic improvements from the additional equation-choice model. The mean weighted-cost ratio to the best enumerated mass ordering is 1.035. This reference concerns Eq. (120) within the finite set of mass orderings.

We then compare separate and combined reductions on four groups of three of these profiles. Eighty complete applications give a combined-to-separate learned time ratio of 0.516, with interval $[0.485, 0.563]$. Within combined calculations, the learned-to-simple ratio is 1.025, with interval $[0.941, 1.121]$. This comparison counts the model cost on both sides where the model is used.

A second reserved set contains twelve further mass profiles, powers up to thirteen and up to 80 requested targets per profile. Eighty applications compare the preceding separate workflow, the updated combined simple rule, and both learned inference implementations on the

same four groups. The compiled learned route has complete-time ratio 0.218 to the preceding workflow, with interval $[0.169, 0.276]$, and ratio 0.923 to the combined simple rule, with interval $[0.885, 0.962]$. Its ratio to Python inference in the otherwise identical learned workflow is 0.990, with interval $[0.885, 1.117]$. The two learned implementations produce identical selected equation systems. Complete-time validation retains the Python learned inference implementation for combined requests and the simple rule for a single profile. The compiled inference implementation remains available with its measured comparison.

All 460 reserved applications pass exact checks without fallback. Separate integration checks cover loop orders 1, 12, 16, 24 and 32 and include one deliberately failed check that successfully invokes the full system fallback. The independent audits check 54,594 saved coefficient occurrences in expanded loop-dependent expressions, and the final audit also compares 21,675 raw Kira coefficient occurrences with the earlier rational-expression reader. The peak sampled Kira process-tree memory is 21.27 MiB and peak native scratch use is 0.75 MiB in these tests.

Complete calculation time includes input reading, model loading, equation selection and construction, Kira execution, exact coefficient reading, loop substitution, verification and any fallback. Separate external-process measurements also include Python startup and evidence archiving. Reported ratios are geometric means of batch median ratios; the descriptive 95% intervals resample the twelve single batches or four combined groups. The small number of groups limits conclusions about other workloads. Figure 44 shows the single-profile comparison, and Fig. 45 shows the second combined comparison [40].

These results support acceleration within the stated vacuum family and fixed mass profiles. The Taylor construction also supplies a direct analytic solution for this family; these comparisons concern the reductions performed through Kira here. General scattering families, native generation of high-loop IBP systems and a globally fastest reduction remain outside the evidence.




Figure 44: Median complete calculation time for the twelve reserved single-profile batches. All methods return the same exact reductions at loop orders one through twelve. The updated simple and learned routes share the improved exact checks and coefficient arithmetic.




Figure 45: Median complete time for the second reserved comparison. Each group contains three independent mass profiles. The previous route makes separate Kira calls; the other routes combine the selected systems. The target count on the axis is the requested count per profile and is capped by the available index vectors.

18.13 Exact pre-reduction and a checked direct path

The combined workflow in Section 18.12 still spends much of its time in Kira after the model selects sufficient identities. For the restricted vacuum family, every selected identity lowers the total massive-denominator power. We can therefore evaluate the substitutions in increasing order of that power and return the completed result after an independent exact check. Kira remains available for comparison and as a fallback when this direct path fails its checks.

Let $\boldsymbol{C}_{\boldsymbol{b}}(z)$ be the vector of coefficients of the prescribed masters in $W_{\boldsymbol{b}}^{(L)}$, with $z = L(d-2)$ as defined earlier. For the master with index $\boldsymbol{e}_j$, this vector is the unit vector $\boldsymbol{C}_{\boldsymbol{e}_j} = \boldsymbol{e}_j$. The selected mass identity gives

$$\boldsymbol{C}_{\boldsymbol{b}}(z) = \frac{\boldsymbol{C}_{\boldsymbol{b}-\boldsymbol{e}_i}(z) - \boldsymbol{C}_{\boldsymbol{b}-\boldsymbol{e}_j}(z)}{\rho_i - \rho_j}, \qquad b_i, b_j > 0. \tag{123}$$

Here ρ_i and ρ_j are the distinct positive mass ratios specified for the family. When only denominator j is present, the Euler identity gives

$$\boldsymbol{C}_{k\boldsymbol{e}_j}(z) = \frac{2(k-1) - z}{2(k-1)\rho_j} \boldsymbol{C}_{(k-1)\boldsymbol{e}_j}(z), \qquad k \geq 2. \tag{124}$$

Both formulas reduce $B = \sum_j b_j$, so they terminate at the specified masters. We evaluate each distinct intermediate integral once.

The existing four-tree model selects the mass ordering before these substitutions, with unchanged weights and training examples. The learned direct route uses the previously checked compiled evaluator. We store each polynomial coefficient as integers over a positive common denominator and cancel their common divisor after each addition or scaling. This keeps the arithmetic exact and reduces repeated fraction normalization. The model selects the intermediate integrals that we visit, while Eqs. (123) and (124) determine their coefficients.

An independent Taylor partial-fraction construction checks the result. For an auxiliary dimensionless variable x, define

$$\prod_{i:b_i>0}(x+\rho_i)^{-b_i}=\sum_{j:b_j>0}\sum_{k=1}^{b_j}\frac{a_{jk}}{(x+\rho_j)^k},\qquad a_{jk}=[t^{\,b_j-k}]\prod_{\substack{i\neq j\\ b_i>0}}(\rho_i-\rho_j+t)^{-b_i}. \tag{125}$$

Here $[t^n]$ means the coefficient of t^n in the Taylor series. The corresponding master coefficient is

$$C_{\boldsymbol{b}j}(z)=\sum_{k=1}^{b_j}a_{jk}\prod_{h=1}^{k-1}\frac{2h-z}{2h\rho_j}. \tag{126}$$

An empty product equals one. This construction uses the same exact single-denominator relation and obtains the mixed-denominator coefficients independently of the selected pairs. We require equality of every polynomial coefficient before substituting $z=L(d-2)$. A failed check retries the original request through the preceding Kira route and its existing full-system fallback.

We compare five routes on identical targets. The preceding deployed route sends model-selected equations to Kira. A second route first evaluates the recurrence, then sends the completed target-to-master relations to Kira. Three direct routes return checked coefficients: one uses learned ordering, one uses simple extreme-power ordering, and one constructs the answer with Eq. (126) and checks it with the simple recurrence. The last route supplies an analytic control that includes an independent exact check.

Six new three-profile batches provide 90 validation calculations. Their mass ratios lie outside the ranges used in earlier training and tests. Validation selects the simple direct route before evaluating eight further three-profile batches with masses in a separate range. Each profile has two, three or four massive denominators, the largest total power is fourteen, and every request includes loop orders one through twelve. Five repetitions of five routes give 200 reserved calculations, all of which pass exact checks without fallback. The independent audit checks 30924 expanded master-coefficient positions and compares 25770 raw Kira coefficient expressions with the earlier rational reader. Five further applications include loop orders 1, 12, 16, 24 and 32 and a deliberately failed direct check that recovers through Kira.

The selected route has calculation-time ratio 0.306 to the preceding combined learned workflow, with descriptive interval $[0.246, 0.373]$. Its full worker-time ratio is 0.430, with interval $[0.414, 0.446]$. Calculation time includes request reading, model loading and inference where used, preparation, exact algebra, checks, loop substitution and fallback. Full worker time also includes interpreter startup and saving the output. We take the median of five repetitions per batch and then the geometric mean of the eight batch ratios. The intervals resample those eight batches and describe this finite comparison.

The learned direct route has calculation-time ratio 0.982 to the simple direct route, with interval $[0.971, 0.997]$, and ratio 0.991 to the analytic control, with interval $[0.973, 1.013]$. The comparison does not establish a further complete-time advantage from learned ordering over both direct controls. Pre-reduction followed by Kira has time ratio 0.927 to the preceding route. Figure 46 shows the batch times. The principal saving in the direct routes comes from finishing the exact triangular recurrence before a Kira invocation is needed. These measurements cover an outer reduction path for the stated vacuum family. Native IBP-generation policies retain their previously tested domains, and general high-loop families require separate comparisons. The implementation, fixed choices, raw outputs and checks accompany the measurements [41].




Figure 46: Reserved batch times for the preceding Kira route, pre-reduction followed by Kira, and three independently checked direct routes. Each point is the median of five complete calculations. The right panel includes startup and saving the output.

18.14 Sharing exact polynomial work across targets and loop orders

The direct reduction in Section 18.13 removes the Kira call when exact recurrence relations complete the requested reduction. Its remaining cost includes construction of the independent check and expansion of each coefficient at every requested loop order. We now reuse the algebraic terms that these operations have in common and keep the calculation process available for a bounded sequence of requests. The master basis, selected identities and exact checks remain the same.

Write a coefficient as $C(z) = D^{-1}\sum_{n=0}^{q} a_n z^n$, where D is a positive integer, the a_n are integers, and q is its degree. For each loop order L, define the integer transformation

$$T_{kn}^{(L)} = \begin{cases} \binom{n}{k} L^n (-2)^{n-k}, & n \geq k, \\ 0, & n < k. \end{cases} \tag{127}$$

$$C(L(d-2)) = \frac{1}{D}\sum_{k=0}^{q}\left(\sum_{n=k}^{q} T_{kn}^{(L)} a_n\right) d^k.$$

Here k is the power of d and n is the original power of z. We form this transformation once for each requested L and reuse it for all target coefficients. The present power limit gives $q \leq 13$. We also obtain the common denominator once per symbolic coefficient, then apply the integer transformations and cancel common factors. This removes repeated binomial coefficients, powers and denominator construction while retaining the full expanded result.

The independent check in Eq. (125) contains repeated Taylor terms. For a positive denominator power β, a nonnegative series index n, and a nonzero mass difference $\Delta = \rho_i - \rho_j$, these terms are

$$[t^n](\Delta + t)^{-\beta} = (-1)^n \binom{\beta + n - 1}{n} \Delta^{-(\beta+n)}. \tag{128}$$

We retain each required truncated factor within its mass profile and multiply the factors with integer polynomials over common denominators. We also form each single-denominator polynomial $\prod_{h=1}^{k-1}(2h-z)/(2h\rho_j)$ once for that profile and reuse it in Eq. (126). Every target still receives

its own independent master expansion and exact comparison with the selected recurrence. This reuse changes the arithmetic work needed to construct the check.

For a sequence of requests, one running process retains the transformation matrices and, when requested, the unchanged trained model. Each new mass profile receives fresh mass-dependent Taylor terms, so a repeated integral identifier cannot transfer coefficients between different physical inputs. The current interface bounds the retained transforms and the number of requests per process. A failed exact comparison retries the preserved Kira route. The previous ordering policy remains the default, and this extension introduces no new model training.

We compare the preceding arithmetic, shared transformations alone, shared Taylor terms alone, and both changes together. All routes use the same output writer, which stores each exact coefficient block once. Four new three-profile batches provide 48 validation calculations and select both arithmetic changes before the reserved test. Eight further batches provide 160 calculations: four variants with five repetitions each. The tests use two, three or four massive denominators, total massive-denominator power $B \leq 14$, up to 96 requested targets per profile, and every loop order from one through twelve. Validation and reserved mass ranges are disjoint from each other and from earlier training and comparisons.

The two changes together have calculation-time ratio 0.372 to the preceding arithmetic, with descriptive 95% interval $[0.343, 0.402]$. The ratio including process startup and output saving is 0.682, with interval $[0.592, 0.797]$. Shared transformations alone have calculation-time ratio 0.701, and shared Taylor terms alone have ratio 0.693. The combined route reduces expansion time to 0.414 of its previous value and construction time for the independent check to 0.158. These ratios compare batch medians and then take the geometric mean over eight batches. The descriptive intervals resample those eight batches. Figure 47 separates the component changes.

We then compare separate processes with one persistent process for streams of four, four and eight batches. The eight-batch stream contains the inputs from both four-batch streams. Three repetitions of four configurations give 36 stream runs and 192 additional batch calculations. All stream times include initial process startup, input reading, calculation, exact checks and output saving. With the updated arithmetic, process reuse has time ratio 0.524 to separate updated processes. Combining arithmetic and process reuse has ratio 0.365 to separate processes with the preceding arithmetic. The three specified streams overlap, so we report these descriptive ratios without a statistical interval. Figure 48 gives the individual stream times.

All 352 reserved batch calculations return identical exact coefficients across the applicable routes. The independent audit checks 28860 expanded coefficient positions with the older formula at each loop order. Additional interface checks cover changed masses and loop orders under the same integral identifier, continued operation after an invalid request, the request limit, retained model evaluation, and recovery through Kira after a deliberately failed check. These savings come from shared exact arithmetic and reduced process startup. They apply to the restricted vacuum family and its existing reduction interface; the earlier native IBP-generation scope remains unchanged. The frozen implementation, measurements and checks are available with the data [42].




Figure 47: Reserved batch medians for the preceding arithmetic, each reuse change separately, and both changes together. Each point uses five complete calculations with identical target outputs and checks.




Figure 48: Total time for the specified request streams, including startup, all exact checks and saving the results. Each bar gives the median of three runs. The eight-batch stream uses all inputs from the two four-batch streams.

18.15 Exact integer arithmetic and learned batch strategies

Section 18.14 reuses the transformations for $z = L(d-2)$, but its implementation still converts coefficients between integer polynomials and separate rational numbers. It also writes each integer as decimal text. We now retain the common-denominator representation, compile the loop-order expansion, and test a compact exact output format. We then train a small model to choose a recurrence strategy for a whole target batch and compare its cost with fixed strategies.

For a polynomial $C(z) = D^{-1}\sum_{n=0}^{q} u_n z^n$, we store the integer vector $(u_0, \ldots, u_q)$ and positive denominator D, with $\gcd(D, u_0, \ldots, u_q) = 1$. Both the selected recurrence and the independent Taylor construction return this form, so their exact comparison needs no conversion to separate fractions. The compiled expansion uses Eq. (127) to obtain

$$v_k = \sum_{n=k}^{q} T_{kn}^{(L)} u_n, \qquad g_k = \gcd(|v_k|, D), \qquad [d^k]C(L(d-2)) = \frac{v_k/g_k}{D/g_k}. \tag{129}$$

Here v_k is the integer numerator before cancellation, g_k is its greatest common divisor with D, and $[d^k]$ extracts the coefficient of d^k. The implementation uses integer operations from the GNU Multiple Precision Arithmetic Library (GMP); the installed library version is 6.0.0 [43]. Every coefficient retains its exact reduced numerator and denominator.

The compact format records the sign, byte length and base-256 digits of each integer, together with the target, master and loop-order indices. It therefore preserves the full symbolic and expanded coefficients. A supplied reader recovers the same coefficient arrays as the decimal format. We measure the cost of reading these arrays as well as the cost of producing and saving them, so the comparison includes the conversion needed by a consumer of the result. The same master basis, independent Taylor check and Kira fallback apply throughout.

The learned strategy selects one of five rules for each batch. The first rule is the preceding extreme-power rule. Two further rules order denominator slots by their total powers across the targets, in increasing or decreasing order. Another rule selects the active mass pair with the largest absolute mass difference, and the last uses a fixed slot order. Each rule generates a terminating set of exact recurrence relations. The model can change which intermediate integrals occur and the sizes of the rational coefficients during substitution.

For batch $\mathcal{B}$ and rule s, let $T_{\mathcal{B}sr}$ be the measured time in repetition r of an already running worker. This time includes request reading, recurrence selection, exact arithmetic, the independent check and output writing. The training target and the rule selected by the model are

$$y_{\mathcal{B}s} = \log(\mathrm{median}_{r=1,2,3}\, T_{\mathcal{B}sr}), \qquad \widehat{s}(\mathcal{B}) = \arg\min_{s} f_s(x_{\mathcal{B}}), \tag{130}$$

where $x_{\mathcal{B}}$ contains 49 input features and f_s is the tree prediction of the log time for rule s. The features describe target powers, numbers of active denominators, loop orders, masses, mass differences, and shared integrals obtained by lowering one positive target power. We combine profile means and maxima into a fixed-length batch description. A multi-output regression tree with maximum depth four and at least six training batches per leaf learns these costs; the fitted tree has 19 nodes. The scores estimate runtime and carry no calibrated probability claim.

Training uses 96 batches and 1,440 timed calculations. The first twelve validation batches provide 324 calculations that compare the preceding arithmetic, retained integer polynomials, compiled expansion with decimal output, compiled expansion with binary output, and the learned rule. The validation also compares every fixed recurrence rule with the compiled binary route. Each batch contains three profiles with two, three and four massive denominators. Total massive powers reach fourteen, requested target counts reach 96 per profile, and every profile includes loop orders one through twelve. The training, validation and reserved test stages use distinct targets and mass profiles.

The first validation selects retained integer polynomials with decimal output. Its reserved comparison contains 504 batch calculations and passes every exact check. Its full-time ratio, including output reading, is 0.998 with descriptive interval $[0.867, 1.162]$, so this comparison does not establish a complete-time improvement. The binary variants reduce production time, but their Python reader adds enough cost to remove the gain in the full comparison.

We therefore compile the expanded-coefficient reader while retaining the same binary format, exact arithmetic and trained tree. This change follows the reader cost observed during validation. The original frozen comparison remains intact. The compiled reader passes 1,000 loop-output comparisons with the Python reader and rejects 250 truncated records. A new set of twelve validation batches supplies 324 further calculations, and a separate set of twelve test batches supplies the final reserved comparison. An incomplete reader comparison is excluded because its selection step referenced the earlier validation set. We preserve those 360 measurements, correct the stage references, and freeze the prescribed choice from the new validation set before generating results for fresh reserved targets.

The second validation selects compiled expansion and binary output with a fixed recurrence rule using total process time plus output reading. A learned route must improve on the best fixed route by at least two percent to replace it. We freeze the implementation, tree, deployment choice and test inputs before the reserved comparison. Twelve new batches then provide 300 separate-process calculations, with five repetitions per method. The implementation comparison uses the same request interface and output writer for matched routes.

The selected route has calculation-time ratio 0.522 to the preceding arithmetic. Its full process-time ratio is 0.850, with descriptive 95% interval $[0.785, 0.909]$, and the ratio including output reading is 0.858, with interval $[0.800, 0.914]$. Retaining integer polynomials alone gives a ratio of 0.981 when output reading is included. Compiled expansion with decimal output gives 0.933, and compiled expansion with binary output and the preceding rule gives 0.858. These comparisons separate arithmetic changes from the output format. The ratios use geometric means of within-batch median ratios; the descriptive intervals resample the twelve batches. Figure 49 shows their measured times.

The learned route has total-time ratio 0.873 to the preceding arithmetic and ratio 1.017 to the fixed rule selected by validation, both including output reading. The latter interval is $[0.969, 1.070]$. This interval includes one, so the reserved comparison does not establish a further time reduction from learned choices. The deployed default uses the fixed validation choice. The model and its measurements remain available with the fixed-rule controls, including any extra inference cost.

We also compare persistent workers on three disjoint streams of four reserved batches. Four recorded route labels and three repetitions give 36 stream runs containing 144 additional batch calculations. The selected route has stream-time ratio 0.702 to the preceding arithmetic, or 0.725 when reading every output is included. Figure 50 separates these two costs. The compiled fixed-rule and deployed labels use the same settings and provide separately timed repetitions. These stream ratios describe the three specified sequences. A separate comparison of identical binary blocks gives compiled-to-Python reader-time ratio 0.147, using five repetitions per reader and batch.

All 444 final reserved batch calculations pass exact comparisons, and the two comparisons together contain 948 such calculations. The independent audit checks 35472 expanded master-coefficient positions against the older loop-dependent formula and verifies equality between the two output formats. The compiled arithmetic also passes 3,277 earlier exact checks. Additional interface checks cover changed physical inputs under a repeated identifier, invalid requests, the worker request limit, truncated output, and recovery through Kira after a deliberately failed independent check. These results apply to the restricted coupled vacuum family. The earlier

native IBP-generation results retain their stated domains. The implementation, new tree, frozen inputs and measurements accompany the report [44].




Figure 49: Reserved batch medians for the arithmetic and strategy variants. Each point uses five repetitions. The right panel includes reading and decoding the complete exact coefficient output.




Figure 50: Complete times for three disjoint four-batch streams. Each bar is the median of three repetitions. The right panel adds reading and decoding every output. The deployed route follows the validation choice.

18.16 Direct measurement of the cumulative change

The preceding sections compare successive changes on different target sets. To measure the cumulative change directly, we now run the original baseline and final deployed calculation on identical integrals. We retain the coupled vacuum family of Eq. (52), with unit massless powers, two to four distinct massive denominators and fixed positive integer mass ratios. We set the common squared-mass scale to $\mu = 1$, as in the preceding comparisons. Each target has the same prescribed master basis in every comparison.

The first control uses the saved original Kira 3.1 executable, whose file hash agrees with the first frozen cost comparison. It generates the full Euler and mass partial-fraction equation pool and reduces each mass profile separately at every requested loop order. The Euler seeds extend through the largest target power, and the mass-pair identities extend through one additional power. A second control uses exactly the same requests, equation generation, reader and verification, with the later project executable used in Section 18.11. Its learned policies are disabled. Comparing these controls separates the executable change from the subsequent removal of repeated reductions.

The final route remains the validation-selected implementation from Section 18.15. It evaluates the selected recurrences directly and calls Kira only if the exact check fails. It uses the fixed extreme-power recurrence, shares coefficients in $z = L(d-2)$, checks them through the independent Taylor construction, expands them with compiled exact arithmetic and saves lossless binary output. It retains the existing Kira fallback. No model is retrained and no strategy is selected from the cumulative test results. These calculations use explicitly supplied identities; the test does not invoke native generation of a general multiloop IBP system.

We declare eight new groups of three mass profiles, one each with $R = 2, 3, 4$, and request every loop order $L = 1, \ldots, 12$. Two groups use each maximum total massive power $8, 10, 12, 14$. The requested target counts per profile are $16, 32, 48, 64$, respectively, capped by the available index vectors. The mass profiles are new, while index shapes can overlap earlier data within this restricted family. A separate upper-bound pilot checks executable compatibility and resource use. We then freeze the implementations, executable hashes, final deployment choice and all reserved requests.

Five repetitions of each method give 120 complete workflows. Both controls use the same scheduler-provided job-local scratch. Four allocated CPU slots process independent groups on one scheduled node. Each worker binds to a distinct available physical core, and every matched comparison remains bound to that core, with a shuffled sequential order within each three-method block. Each trial starts a fresh worker process and uses ordinary filesystem caching. Content-addressed storage can reuse an identical saved output on a repeated trial in any arm, while each arm recomputes its reduction. The primary time includes process startup, input loading, equation construction, exact algebra, verification, output saving, and reading and decoding the full output. It also includes the diagnostic evidence written inside each worker. Queue waiting, offline training and the later independent audit lie outside this time. We separately retain calculation times before final output saving and reading.

Let T_{abr} denote the primary time for method a, batch b and repetition r. We compare the medians within each batch and combine the eight ratios through

$$\widetilde{T}_{ab} = \mathrm{median}_{r=1,\ldots,5}\, T_{abr}, \qquad R_T = \exp\left[\frac{1}{8}\sum_{b=1}^{8} \log \frac{\widetilde{T}_{\mathrm{final},b}}{\widetilde{T}_{\mathrm{original},b}}\right], \qquad S = \frac{1}{R_T}. \tag{131}$$

Here R_T is the final-to-original time ratio and S is the cumulative speedup. The percentage of time saved is $100(1 - R_T)$. A descriptive 95% interval resamples the eight complete batches 10,000 times, keeping all repetitions and methods within each batch. This direct comparison

uses neither products of earlier ratios nor different input sets for the two methods.

The measured time ratio is 0.001839, with descriptive interval $[0.001653, 0.002049]$. It corresponds to 543.815 times faster execution, with interval $[488.134, 605.064]$, and 99.82% less time. The ratio to the later full-pool control is 0.012, corresponding to 81.170 times faster execution. The calculation subtotal excludes outer worker startup and final output saving and reading, while retaining every Kira startup within the baseline reduction. Its final-to-original ratio is 0.000294, or 3402.846 times faster. Summing one primary-time median per batch gives 1027.781 seconds for the original control and 1.922 seconds for the final route, a workload speedup of 534.881. This sum weights large batches by their elapsed time, whereas Eq. (131) gives equal weight to each batch. Figure 51 shows the absolute times and individual speedups.

Within each batch, every method and repetition returns the same exact expanded coefficients. All 120 reserved workflows complete with no failure or fallback. Each baseline arm makes 1,440 Kira calls; the final arm makes none on these successful requests. The independent audit checks 27960 nonzero target–master coefficient polynomials after substituting each loop order, using the earlier loop-dependent Taylor formula. It also regenerates all 288 distinct baseline systems, checks their input hashes and uses SymPy to read 1464 coefficient positions directly from saved Kira exports. The two baseline executables receive identical systems at each mass profile and loop order. The maximum sampled worker process-tree memory is 78.488 MiB and temporary solver storage is 1.238 MiB.

The cumulative saving includes shared symbolic reductions, direct checked recurrences, compiled expansion and reduced output costs. The fixed-rule deployment makes this a measurement of the complete mathematical and implementation change. It supplies no separate ML-only speedup estimate. General scattering families and native generation of broader high-loop IBP systems remain outside this comparison. The frozen inputs, implementations, individual timings, raw exports and audits accompany the report [45].




Figure 51: Direct cumulative comparison on identical reserved vacuum batches. The left panel shows median total times, including output reading, on a logarithmic scale. The right panel divides each baseline median by the final-route median. Each point uses five repetitions, three mass profiles and loop orders one through twelve.

19 Scattering families, symbolic kinematics and certified reduction paths

The preceding comparisons establish costs for specified native families and for a restricted vacuum construction. To extend the physical scope, we now reduce new four-point and five-point families and retain independent kinematic invariants as symbols. We also construct small IBP systems for which every allowed elimination path can be examined. These two extensions test different questions: whether a frozen learned filter transfers to new physical inputs, and whether a recorded reduction cost can be proved minimal within an explicit set of operations.

19.1 New physical families and independent invariants

We continue to use $I_{\boldsymbol{a}}$ for an indexed integral and $D_i = q_i^2 + \mathrm{i}0$ for each massless denominator. The new two-loop family is the massless limit of the nonplanar four-point family `topo4` in Ref. [2]. Its ordered denominator momenta are

$$\begin{aligned}\boldsymbol{q}_{\mathrm{NP}} = (&\ell_1, \ell_2, p_1 - \ell_1, p_2 - \ell_2, p_1 + p_2 - p_3 - \ell_1,\\ &p_1 - \ell_1 + \ell_2, p_1 - p_3 - \ell_1 + \ell_2, \ell_1 - p_3, \ell_2 - p_1 - p_2).\end{aligned} \tag{132}$$

The first seven entries are physical propagators, and the last two complete the scalar-product basis and can appear as numerators. The momenta satisfy $p_1^2 = p_2^2 = p_3^2 = 0$ and $q = p_1 + p_2 - p_3$ with $q^2 = 0$. We define

$$s = (p_1 + p_2)^2, \qquad t = (p_1 - p_3)^2, \qquad 2p_1 \cdot p_2 = s, \quad 2p_1 \cdot p_3 = -t, \quad 2p_2 \cdot p_3 = s + t. \tag{133}$$

The symbolic reduction therefore takes place in $\mathbb{Q}(d, s, t)$.

The new one-loop pentagon has five massless external momenta satisfying $\sum_{i=1}^{5} p_i = 0$. Its denominator momenta are

$$\boldsymbol{q}_{\mathrm{P}} = (\ell, \ell - p_1, \ell - p_1 - p_2, \ell - p_1 - p_2 - p_3, \ell - p_1 - p_2 - p_3 - p_4). \tag{134}$$

All five entries are physical propagators. We retain the five adjacent invariants

$$s_{12} = (p_1 + p_2)^2, \quad s_{23} = (p_2 + p_3)^2, \quad s_{34} = (p_3 + p_4)^2, \quad s_{45} = (p_4 + p_5)^2, \quad s_{51} = (p_5 + p_1)^2.$$

Momentum conservation fixes the other scalar products. For example, $2p_1 \cdot p_3 = s_{45} - s_{12} - s_{23}$ and $2p_1 \cdot p_4 = s_{23} - s_{45} - s_{51}$. The coefficient field is $\mathbb{Q}(d, s_{12}, s_{23}, s_{34}, s_{45}, s_{51})$.

A one-loop box supplies an additional test with an external virtuality. Its denominator momenta are $(\ell, \ell - p_1, \ell - p_1 - p_2, \ell - p_3)$. Here p_1, p_2, p_3 are massless, while $v = q^2 = (p_1 + p_2 - p_3)^2$ is an independent symbol. The definitions of s and t remain the same, and $2p_2 \cdot p_3 = s + t - v$. Thus its coefficients belong to $\mathbb{Q}(d, s, t, v)$. This family has massless internal lines and one external line with nonzero virtuality.

The denominator coefficient matrices have ranks nine, five and four for the nonplanar box, pentagon and one-loop box, respectively. Each rank equals $L(L + 1)/2 + LE$, where E is the number of independent external momenta. The external Gram determinants are nonzero as rational functions and at the specified numerical points. The calculations use generic kinematics away from singular denominators. They retain every listed independent invariant, with no replacement of a scale by one. Internal masses remain zero in these scattering tests.

We first test two rational profiles of the nonplanar box and two of the pentagon, keeping d symbolic. The box profiles are $(s, t) = (-149, -147)$ and $(-167, -157)$ in a common squared-momentum unit. The pentagon profiles are $(-51, -53, -57, -59, -63)$ and

$(-71, -73, -77, -79, -83)$ in the displayed invariant order. We then test one fully symbolic instance of each of the three families. Targets start with the full-sector corner and each single additional propagator power, followed by auxiliary numerators and singly pinched sectors in a fixed index order. The four rational-profile batches contain sixteen targets each. The symbolic nonplanar box, pentagon and one-loop box contain ten, six and eight targets. The seven batches therefore contain 88 targets. Their definitions and target lists precede the timed comparisons.

19.2 Frozen model transfer and exact comparison

The experiment retains the preceding depth-twelve equation-selection tree, its weights and its retention threshold 0.01. The tree sees seed, operator and target features before Kira constructs an identity. These scattering topologies were absent from its training collection. No new fit or threshold selection uses the new results. Small feasibility pilots establish that the symbolic inputs run within the resource limits. Some symbolic pilot targets also occur in the final batches; the pilots do not select a learned policy.

Both methods use the same instrumented Kira 3.1 executable and the existing project runtime changes. The native control disables learned equation selection and retains native seed and row choices.

Kira first discovers a reference basis with seed limits enlarged by one relative to the target's maximum denominator sum, numerator rank and number of additional propagator powers. The native control and experimental filter then start with the target limits and the same prescribed basis. An incomplete filtered attempt retries native equations, and an incomplete native attempt uses the enlarged region. The complete workflow includes each failed attempt, model evaluation, IBP generation, exact algebra, coefficient comparison and cleanup. Reference discovery occurs outside this timer. The comparison driver is already running.

Five alternating repetitions of the two methods give seventy complete workflows. For each batch, we compare the median complete times. We also compare the coefficients as rational functions, repeat native reduction with seed limits enlarged by two, and substitute fresh rational kinematics into each symbolic result before comparing it with a separately generated native reduction. These specialization checks support the symbolic comparisons; they do not replace them. Kira's exact symbolic elimination determines the coefficients [9].

All seventy workflows reproduce the exact reference reductions. The independent audit checks 5,600 coefficient pairs, including 560 distinct pairs. All seven enlarged-seed checks and all three independent kinematic specializations agree. The frozen filter requires native fallback in all thirty-five learned workflows. Its case-weighted geometric mean complete-time ratio to native choices is 1.252, corresponding to 25.2% more time on these batches. Summing one median per batch gives 18.867 seconds for the native control and 22.256 seconds for the experimental route. This sum weights the work differently from the geometric mean.

The symbolic nonplanar box has median times 5.438 and 6.321 seconds for native and experimental reductions, respectively. The symbolic pentagon has median times 1.032 and 1.390 seconds for native and experimental reductions, respectively. The box with symbolic external virtuality has median times 0.723 and 0.958 seconds for native and experimental reductions, respectively. The largest sampled memory of Kira and its child processes is 61.14 MiB, and the largest sampled solver scratch space is 1.16 MiB. These measurements include the unsuccessful filtered attempts. A separate application receives only the family, targets and prescribed masters. All 10 application checks agree with the reference coefficients after execution, including the explicitly requested experimental-filter cases. These checks do not supply target answers to the reducer.




Figure 52: Complete native and experimental learned-filter times on the new scattering batches. Each point is a median of five repetitions. The experimental time includes native fallback. Symbolic batches retain all invariants specified in the text.

The new application accepts symbolic family definitions and a supplied master basis without reference target coefficients. It defaults to native choices for these domains. The transfer measurements do not change the earlier speedup estimates or activate a new learned route. They provide explicit examples for later training on broader scattering inputs [46].

19.3 Physical IBP systems with a finite optimum

A reverse construction supplies a valid path, while an optimality claim also requires a defined cost and a complete comparison with the allowed alternatives. We carry out that comparison on two small systems with symbolic coefficients. For the massless one-loop bubble, define

$$B_{a,b} = \int \frac{d^d\ell}{\mathrm{i}\pi^{d/2}} \frac{1}{(\ell^2+\mathrm{i}0)^a[(\ell-p)^2+\mathrm{i}0]^b}, \qquad p^2 = s. \tag{135}$$

Differentiation with the vectors ℓ and $\ell - p$ gives

$$0 = (d-2a-b)B_{a,b} - bB_{a-1,b+1} + bsB_{a,b+1}, \tag{136}$$
$$0 = (d-a-2b)B_{a,b} - aB_{a+1,b-1} + asB_{a+1,b}. \tag{137}$$

The massless one-denominator integrals vanish in dimensional regularization. Selecting both operators at seed $(1,1)$, the first at $(2,1)$ and the second at $(1,2)$ gives the closed system

$$\begin{pmatrix} 0 & s & 0 & d-3 \\ s & 0 & 0 & d-3 \\ d-5 & -1 & s & 0 \\ -1 & d-5 & s & 0 \end{pmatrix} \begin{pmatrix} B_{2,1} \\ B_{1,2} \\ B_{2,2} \\ B_{1,1} \end{pmatrix} = 0. \tag{138}$$

We protect $B_{1,1}$ as the master and reduce the other three integrals over $\mathbb{Q}(d,s)$. Their exact coefficients are

$$B_{2,1} = B_{1,2} = \frac{3-d}{s} B_{1,1}, \qquad B_{2,2} = \frac{(d-6)(d-3)}{s^2} B_{1,1}. \tag{139}$$

An independent check obtains the same ratios from the gamma-function expression for the bubble.

For a one-loop massive tadpole, define

$$T_a = \int \frac{d^d \ell}{\mathrm{i}\pi^{d/2}} \, (\ell^2 - m^2 + \mathrm{i}0)^{-a}.$$

The IBP identity with vector ℓ is

$$(d-2a)T_a - 2am^2 T_{a+1} = 0. \tag{140}$$

Seeds $a = 1, 2, 3$ give three equations for T_2, T_3, T_4 with master T_1 over $\mathbb{Q}(d, m^2)$. Native Kira reductions generated from the physical denominators provide an additional check of both systems.

At a matrix state S, an allowed action chooses any nonzero entry in an unprocessed row and an unprocessed nonmaster column. It moves that row to the next pivot position, normalizes it and eliminates the chosen column from every other row. The master column remains protected, and each action removes one nonmaster column from future pivot choices. There are three pivot stages in each system.

We count one division for each nonzero nonpivot source entry when the pivot differs from one. Each update of a nonpivot source entry counts one multiplication and one subtraction. Assignments, comparisons, structural cancellation of the pivot, and polynomial operations inside a rational-function operation are outside this cost. Thus the objective measures specified coefficient operations, with no claim that each operation takes the same time.

For this action set, define the remaining minimum cost by

$$V(S) = \min_{a \in \mathcal{A}(S)} \big[c(S,a) + V(S_a) \big], \qquad V(S_{\mathrm{done}}) = 0. \tag{141}$$

Here $\mathcal{A}(S)$ is the complete set of allowed pivots, $c(S,a)$ is the counted cost, and S_a is the exact next matrix. We evaluate every alternative and retain the state graph, using the finite recurrence of dynamic programming [47]. An independent checker reconstructs every row operation, checks all outgoing actions, verifies the cost recurrence, and checks the final master coefficients. Since each action reduces the number of remaining columns, induction from the terminal states proves the minimum for the full stated path space.

To include initial equation selection, we also examine every subset $\mathcal{E}$ of the saved source pool whose nonmaster matrix has rank three. Each subset starts its own complete pivot search, giving

$$C^*_{\mathrm{pool}} = \min_{\substack{\mathcal{E} \subseteq \mathcal{E}_{\mathrm{full}} \\ \operatorname{rank} A_{\mathcal{E}} = 3}} V(S_{\mathcal{E}}). \tag{142}$$

Here $A_{\mathcal{E}}$ contains the nonmaster coefficients, and $S_{\mathcal{E}}$ is the starting matrix for that subset. Initial row selection carries no coefficient-operation cost in this objective. The certificate records every sufficient subset and every subsequent pivot choice.

The massless bubble certificate contains 113 distinct states and checks 234 transitions. It covers 152 complete paths across 5 sufficient source subsets. The minimum is 7 coefficient operations when initial equation selection is allowed, and 13 when the full source pool is retained.

The massive tadpole certificate contains 24 distinct states and checks 32 transitions. It covers 15 complete paths across one sufficient source subset. The minimum is 7 coefficient operations when initial equation selection is allowed, and 7 when the full source pool is retained.

The fixed control chooses the first available nonmaster column and then the first available source row. It attains the full-pool minima of thirteen and seven operations. A control that minimizes only the immediate step cost uses thirteen operations for the bubble and nine for the tadpole. Thus immediate cost can give a larger complete cost even in a three-column physical system. The minimum sufficient equation count is three for each pool, with two distinct bubble seeds and three tadpole seeds. All exact state transitions and terminal coefficients pass independent checks, and six native Kira master coefficients agree with the two symbolic systems.

The subset checks also certify the smallest sufficient equation count and the smallest number of distinct source-seed labels within each saved pool. These records give exact cost labels for later model tests. The certificates apply to the displayed systems, protected masters, allowed operations and cost definition. They do not establish an optimum over additional IBP identities, changes of master basis, other algebraic algorithms or unrestricted scattering reductions. General high-loop scattering and wall-time optimality therefore remain separate questions.

20 Choosing a complete reduction strategy

The preceding tests show that supplying enough equations does not by itself ensure a faster reduction. We therefore train a model on complete reduction times. For a target batch and a prescribed master basis, the model chooses the initial seed region, an optional seed or equation filter, and an integral ordering. Kira then performs exact reduction. The choice occurs once for the batch, which avoids repeated model calls during elimination.

We also combine the earlier equation filter with an existing improvement to temporary data handling. This changes execution cost while preserving the equations and arithmetic. A separate control uses this combined path with native decisions. Comparing the model with that control measures what the learned choice adds to the integration improvement.

Let $B = (r_{\max}, s_{\max}, q_{\max})$ contain the largest positive index sum, numerator rank and dot count among the targets. A dot is one denominator power above one. Appendix A gives their definitions and the cost-model derivations. Table 1 lists the candidate strategies. Kira provides the seed limits and integral-ordering options used here [8]. Ordering five changes the sector priority while keeping the same within-sector preference as ordering one. Every comparison uses the same prescribed master basis. For the four earlier multiloop graphs, the seed-filter option uses native choices because no graph-specific seed tree is available in this route. The equation option uses the earlier tree for those graphs and the new scattering trees for the three additional structures.

Table 1: Strategies available to the complete-cost model. Negative seed bounds are replaced by zero. Native row choices remain active.

Strategy	Initial seed region and selection
Integrated native	Bounds B; native choices
Smaller region	Bounds $B-(1,1,1)$; native choices
Fewer dots	Bounds $B-(1,0,1)$; native choices
Equation filter	Bounds B; saved equation tree
Seed filter	Bounds B; saved seed tree where available
Different ordering	Bounds B; Kira ordering five
Larger region	Bounds $B+(1,1,1)$; native choices

The larger region can avoid an unsuccessful first attempt when a target needs equations beyond its own index limits. The smaller regions can avoid unnecessary generation when fewer equations suffice. If a proposed region or filter fails the basis check, the calculation retries with native choices at B, then at $B+(1,1,1)$ when needed. The native control also includes enlargement after an unsuccessful first attempt. Failed attempts remain in the time used for both training and testing.

The training label for each strategy is the logarithm of its complete-time ratio to integrated native choices. The model receives eighteen features that describe the graph, symbolic variables, target count, index powers and sectors. We compare a constant predictor, six regression trees, three ridge-regression models and two nearest-neighbour models. Regression trees follow the squared-error construction in Ref. [30]. Appendix A specifies each model. Validation selects ridge regression with penalty $\lambda = 10$ and margin $\gamma = 0$ before the held-out tests. Its validation time ratio to integrated native choices is 0.993. The best fixed strategy from training is integrated native choices. Thus the integrated and best-fixed controls repeat the same configuration in separate trials, and differences between their times reflect execution variation. The seed and equation trees retain their earlier weights, and the original row model remains omitted.

The study has 31 training batches, 17 validation batches and 31 test batches. It covers the sunrise, planar box, three-loop vacuum, three-loop ladder, nonplanar box, pentagon and box

with external virtuality. Rational batches use separate invariant or mass values in each split. Additional symbolic batches use different target lists. These are new inputs within known graph structures. The native tests cover one through three loops; the separate exact recurrence results through twelve loops retain their restricted vacuum scope.

Each training and validation cost uses three repetitions. Testing compares the previous native path, integrated native choices, the best fixed strategy from training, and the learned strategy with five repetitions. A running controller starts a fresh Kira process for every attempt. The timer includes input preparation, prediction, native IBP generation, algebra, exact coefficient checks, cleanup and every retry. Offline training, enlarged reference reductions and later evidence archiving are outside the timer. Separate applications receive only the target and master basis; their coefficients are checked afterward. The learned application uses native choices for unmatched graph structures or target complexity outside the training range. This guard also applies when requests are combined. Cold command startup is recorded in the application checks; the comparative timings describe the running controller.

20.1 Full reduction results

All 620 timed workflows pass exact checks of 59,640 coefficient entries. All 31 applications supplied with a master basis also pass their later coefficient checks. Each timed method makes fifteen fallback attempts. The new selector therefore changes some initial strategies without removing the remaining insufficiency failures.

The learned-to-previous-native time ratio is 0.9903, with descriptive interval $[0.9796, 0.9996]$, or about 1.0% less time. Its ratio to integrated native choices is 0.9965 with interval $[0.9875, 1.0070]$. Its ratio to the best-fixed control is 1.0026 with interval $[0.9979, 1.0081]$. Both latter intervals include equal time, so the test establishes no additional full-time saving from the learned choices. The integrated and best-fixed controls have ratios 0.9938 and 0.9878 to the preceding native path. Their difference, despite using the same configuration, also shows the scale of timing variation in this comparison.

Table 2 gives the results by graph. We average logarithmic ratios within each graph and then give each of the seven graphs equal weight. Appendix A derives this average and defines the descriptive intervals. The smallest measured ratio for the learned route is 0.9654, for the three-loop vacuum. The ladder and nonplanar box take slightly more time. These measurements do not establish a significant speedup across all the tested integral types.

Table 2: Complete-cost results. Native seconds are geometric means of batch median times. The other entries are geometric mean time ratios; a value below one means less time.

Graph	Native (s)	Integrated/native	Learned/native	Learned/integrated
Sunrise	0.502	1.0123	0.9932	0.9811
Planar box	1.621	0.9906	0.9771	0.9864
Three-loop vacuum	0.726	0.9745	0.9654	0.9907
Three-loop ladder	3.535	1.0146	1.0013	0.9869
Nonplanar box	3.119	1.0075	1.0073	0.9998
Pentagon	0.599	0.9758	0.9942	1.0189
Box with virtuality	0.484	0.9824	0.9944	1.0122




Figure 53: Learned choices and the native controls have similar full times. The best-fixed and integrated controls use the same configuration in separate trials. The plot shows variation across graph structures; the text gives the aggregate uncertainty intervals. The axis focuses on the measured range and retains the equal-time line.

20.2 Sharing reductions between compatible requests

The small differences between single-batch strategies motivate a change in how requests reach Kira. When two target lists have the same family and kinematics and are available together, we combine their targets, reduce the union once, and return the coefficient rows for each list. This shares the family preparation and algebra. Appendix A specifies the ten request groups and derives the output separation from linearity. The model and its settings remain fixed.

Five repetitions of four methods give 200 complete workflows, and all pass exact coefficient checks. Joint native reduction has time ratio 0.5252 to two separate native reductions. The combined integration with native choices gives ratio 0.5175 with interval $[0.5073, 0.5346]$, or 48.3% less time. This is a speedup of 1.93 with interval $[1.87, 1.97]$. Every tested graph group takes less time with joint reduction. The integrated native ratios range from 0.5040 to 0.5679 across the seven graphs, corresponding to savings of 43.2–49.6%.

The joint learned route gives ratio 0.5152 to separate native requests. Its ratio to joint integrated native choices is 0.9955, with interval $[0.9810, 1.0058]$. This interval includes equal time. Table 3 and Figure 54 therefore attribute the main measured gain to sharing the reduction. The model adds no reliable gain over the integrated native control. The standard application uses the best fixed strategy from training, which retains native choices. The learned strategy remains an optional route. Ten checks of each joint application supply only the basis, then verify the returned coefficients independently. Ten further checks exercise the single-batch command. These application checks add to the 31 basis-only applications in the main comparison.

Table 3: Joint-request time ratios and descriptive intervals over the seven graph groups. Each group contains two compatible target requests.

Comparison	Time ratio	95% interval
Joint native / separate native	0.5252	$[0.5130, 0.5420]$
Joint integrated / separate native	0.5175	$[0.5073, 0.5346]$
Joint learned / separate native	0.5152	$[0.5022, 0.5322]$
Joint learned / joint native	0.9810	$[0.9657, 0.9946]$
Joint learned / joint integrated	0.9955	$[0.9810, 1.0058]$




Figure 54: Combining compatible requests gives the main saving. Left: ratios by graph relative to two separate native reductions. Right: aggregate ratios and descriptive intervals. Comparing learned choices with joint integrated native choices gives no reliable extra saving. The panels retain the equal-time reference.

The joint comparison reuses reserved parameter points from the main test. It provides a new comparison on that population. Transfer to additional graph structures remains untested. The saving requires compatible requests that can share one calculation. These measurements neither establish a saving for an isolated arbitrary integral nor extend native IBP performance claims to general scattering graphs beyond three loops.

21 Choosing a policy for each integral type

The preceding study used one cost predictor across seven graph structures. We now train separate predictors and enlarge the set of possible seed strategies. This lets a target-dependent choice depend on the graph's own measured costs. The new candidates include restricting the maximal target sectors and reducing numerator seeding in lower sectors, using Kira's truncation option [9]. The comparison retains exact algebra, master-basis checks, and fallback. Every method first enforces a valid positive-index bound for its declared sectors.

We fit ten candidates for each graph, giving seventy fitted models. They include regression trees, a bagged tree ensemble, regularized linear models, and nearest-neighbour models. The model receives nine features of the target indices and family and predicts complete-time ratios for nine strategies. The response includes failed attempts and retries. We train on 36 batches, choose settings on 18 validation batches, and reserve 36 batches at new rational parameter values for testing. The dimension remains symbolic. The targets include denominators raised to power three, lower sectors, and numerator indices -2 on auxiliary entries. Appendix B gives the exact definitions, model fits, and selection rule. The final training and validation records contain 2,798.5 seconds of measured reductions, and fitting all seventy candidates takes 0.86 seconds. The label total excludes reference construction, development, and replaced measurements. These offline costs remain outside the reserved reduction times.

The route enables a new cost model only when validation shows at least five percent less time than the fastest available control. This threshold is fixed before testing. The controls are native choices, a deterministic sector-and-truncation rule, and one fixed strategy per graph selected from training. The last control can include the older equation filter. Validation activates a new cost model for 3 of the seven graphs and retains a control strategy for the others. Unknown graph structures and target features outside the training range use native choices. A chosen strategy can still fail its basis check; the route then retries, and the comparison includes that cost.

Five repetitions of four methods give 720 reserved timing trials. All trials pass exact coefficient checks. Giving each graph equal weight, the selected route has geometric mean full-time ratio 0.9368 with descriptive interval $[0.8867, 0.9878]$, corresponding to 6.3% less time. Its ratio to the fixed choice per graph is 0.9441 with descriptive interval $[0.8992, 0.9863]$. The aggregate interval lies below equal time. Table 4 gives each graph's result. The selected route has a time ratio below one for 5 of the seven graph groups. These are measurements within the tested input groups, not a speed guarantee for every integral in those graphs. Across its 180 timed trials, the selected route makes 0 retry attempts; native choices make 40 retries in the matched 180 trials. The time ratios include these retries.

The enabled trees give 14.2%, 12.4%, and 13.8% less time for the planar box, ladder, and nonplanar box, respectively. The vacuum and virtuality box show 3.7% and 0.8% more time. Both of those groups use a retained control throughout. The vacuum route selects native settings, so its measured difference includes routing overhead and timing variation.

Table 4: Results for each graph. Times are geometric means of the batch median times, in seconds. A ratio below one means less complete time. The route column names the enabled cost model or retained control.

Graph	Route	Native	Selected	Ratio
Sunrise	Stronger truncation	0.825	0.811	0.983
Planar box	Depth-two tree	3.410	2.925	0.858
Vacuum	Native	1.033	1.072	1.037
Ladder	Depth-one tree	5.144	4.506	0.876
Nonplanar box	Depth-two tree	6.234	5.376	0.862
Pentagon	Target sectors	1.040	0.989	0.951
Virtuality box	Sectors and truncation	0.808	0.815	1.008




Figure 55: The effect of choosing a separate policy for each graph. Left: full-time ratios to native choices. Right: the selected route relative to one fixed strategy per graph. Bars show the range across two reserved parameter profiles; they are not significance intervals. Both panels retain the equal-time reference.

The timing trials check 14,040 coefficient entries. We also complete 36 applications supplied only with the master basis and seven further application checks, then compare their coefficients independently. These additional applications check 945 coefficients. The new study uses the same seven graph structures as before, at one through three loops. Its target patterns occur in training, and it tests new kinematic profiles. General scattering beyond three loops and new target structures remain outside this comparison. The per-graph models have two training parameter profiles; the fixed range guard and reserved checks limit the claims accordingly.

22 Reducing the cost of seed expansion

The preceding graph-specific study records more solver time in symbolic equation regeneration than in any other instrumented stage. Some batches need larger seed regions to reach the prescribed masters, so generating fewer unnecessary equations in those regions can reduce the remaining cost. We test six ways to increase selected seed limits and two ways to reduce first to a temporary basis. The latter methods then reduce the remaining basis integrals and combine their exact coefficients. They retain the same final master-basis requirement. Appendix C defines all candidates and derives the basis conversion.

For each development batch, we retain its fastest new candidate if it saves at least ten percent against the preceding route. The preceding route also remains available. Let $B_c = (r_c, s_c, q_c)$ be the initial valid seed limits for target batch c. They bound the sum of positive indices, numerator rank, and number of extra denominator powers, respectively. The selected candidates are Preceding route, Full-sector basis completion, $B_c + (1, 0, 0)$, $B_c + (0, 1, 0)$, $B_c + (1, 1, 0)$. Development measurements guide this choice; they do not enter the reserved comparison. We train on 36 new batches, select settings on 18 validation batches, and reserve 36 further batches. All use new rational kinematic profiles of the same seven graphs, with symbolic d and the target patterns defined in Appendix B.

We fit ten predictors per graph using the earlier nine target features. They predict full time relative to the preceding route. Validation compares each predictor with that route and with a single fixed strategy chosen from training for each graph. A new predictor must save at least five percent against the faster control before it is enabled. Otherwise, the selected route uses the control. These comparisons measure the effect of the new seed options and the additional effect of the full selection procedure. A fixed candidate can itself call the preceding learned route; this control measures the extra choice among the new candidates. Validation enables a new predictor for 3 of the seven graphs. The final training and validation records contain 1,731.7 seconds of measured reductions; fitting the seventy candidates takes 0.88 seconds. These offline costs exclude reference construction and development and remain outside the reserved reduction timer.

The reserved test compares native choices, the preceding route, the new fixed strategy, and the selected route. Five repetitions give 720 full calculations. All pass exact coefficient checks, and all 43 further applications pass checks when target coefficients are withheld during reduction. The new route has time ratio 0.9115 with descriptive interval $[0.8105, 0.9980]$ to the preceding route, corresponding to 8.8% less time. Its ratio to native choices measured in the same experiment is 0.8516 with descriptive interval $[0.7282, 0.9647]$, or 14.8% less time. Its ratio to the new fixed strategy is 0.9264 with descriptive interval $[0.8760, 0.9747]$.

For one execution of each of the 36 reserved batches, the sum of median reduction times is 106.24 seconds for native choices, 96.32 seconds for the preceding route, and 77.03 seconds for the new route. This workload total weights each requested batch once; the geometric means above give each graph equal weight.

Across 180 timed runs per method, symbolic equation regeneration takes 138.02 seconds for the preceding route and 80.58 seconds for the new route. The new route makes 0 fallback attempts, compared with 0 for the preceding route and 40 for native choices. Planned second-stage basis reductions are counted in full time and are separate from fallback attempts.

The fixed-strategy comparison supports a further saving from the selection procedure on these inputs. This procedure combines validation-based control choices with target-dependent predictions.

Table 5: Full reduction times for the new reserved profiles. Times are geometric means of batch medians in seconds. Ratios below one indicate a faster new route. The policy is the fitted predictor or fixed control chosen by validation. Each graph has two reserved parameter profiles.

Graph	Policy	Previous (s)	New (s)	New/previous	New/native
Sunrise	Add s	0.596	0.593	0.995	0.979
Planar box	Tree depth 1	2.422	2.062	0.851	0.735
Vacuum	Complete basis	0.928	0.941	1.013	1.016
Ladder	Tree depth 1	4.477	3.007	0.672	0.584
Nonplanar box	Tree depth 1	4.091	3.550	0.868	0.759
Pentagon	Previous	0.723	0.754	1.043	0.998
Virtuality box	Previous	0.580	0.582	1.003	1.004




Figure 56: Selective choices change complete reduction time. Left: the new fixed strategy and selected route relative to the preceding route. Right: the preceding and new routes relative to native choices in the same test. Values below one are faster. Bars show the range over the two reserved profiles; they are not significance intervals.

Three graph groups take more time than the preceding route: vacuum, 1.3%; pentagon, 4.3%; virtuality box, 0.3%.

The result includes prediction, native IBP generation, exact algebra, checks, cleanup, and fallback. It measures an additional change from the preceding method and a direct comparison with native choices. It does not multiply speedups from earlier experiments. The graphs and target patterns are known during training; the new parameter profiles test transfer within those

inputs. General symbolic kinematics and arbitrary high-loop graphs remain outside this new measurement.

23 Conclusion

We integrated seed and source-row policies with exact native Kira reduction and reduced their evaluation cost while retaining the same decisions. The latest seed implementation evaluates independent neural outputs together, and the row implementation combines Euclid's modular inverse with direct integer evaluation and shared coefficient storage. All probability vectors agree in the thirty-six development contexts. Checks on 100,000 inverses and 1,000 sparse-row groups also agree.

The new seed component has a time ratio of 0.423 to the preceding shared implementation. The row-feature component has a ratio of 0.803. These component savings require separate complete-reduction measurements because model evaluation is only one part of the calculation.

The seed method has a complete-time ratio of 0.990 to its preceding implementation, with descriptive interval $[0.977, 1.003]$. Its ratio to the new native control is 1.096, with interval $[0.963, 1.275]$.

The row method has a complete-time ratio of 0.990 to its preceding implementation, with descriptive interval $[0.971, 1.010]$. Its ratio to the new native control is 0.982, with interval $[0.959, 1.003]$.

The combined method has a complete-time ratio of 0.984 to its preceding implementation, with descriptive interval $[0.965, 1.007]$. Its ratio to the new native control is 1.100, with interval $[0.966, 1.279]$.

The descriptive complete-time intervals include one for all three comparisons with the preceding implementation. Component evaluation is faster, and the complete-workflow gain remains uncertain at this sample size. The seed and combined methods still have aggregate costs above the native control. The row-only comparison with native choices also includes one in its interval.

All 144 validation workflows and 640 confirmation workflows pass the exact checks and preserve the recorded decisions and operation counts. These times include IBP generation, model evaluation, exact algebra, checks and fallback. The implementation comparison reuses eight physical profiles and retains the weights, thresholds and routing selected before confirmation [35].

The data construction provides 17,100 family instances, 57,979 family-local master entries and 2,301,272 targets with recorded identities and reduction paths. These paths provide valid reference constructions and costs. On 690,382 held-out targets, the seed model reaches 96.318% F_1, and its predicted stored equations supply complete master-span reductions for 94.515% of targets. The full candidate pool supplies the remaining reductions. These label and sufficiency measures require separate runtime tests; the earlier cost comparisons and their negative results remain part of the study [15, 19, 22, 26].

For production use, the interface needs a prescribed master basis and can calculate target coefficients without their reference answers. Native exact IBP operations determine the coefficients, and explicit output-basis admission detects incomplete seed sets. Eight application checks pass independent coefficient comparisons after execution with reference answers withheld from the reducer. The report keeps this native algebraic assurance separate from the additional reference comparisons used in the benchmark.

The original collection through twelve loops uses restricted coupled vacuum families. The native performance comparisons cover physical two- and three-loop inputs at fixed rational kinematics with symbolic d. The ladder topology is absent from that row-policy training and validation

sets. Those native timing comparisons retain their fixed-kinematic scope. Section 19 extends the tests to new scattering topologies and independent symbolic invariants and supplies finite optimality certificates. General high-loop scattering and optimality over unrestricted identity pools remain open.

The third model selects generated identities for the requested targets. The broad test found that incomplete vacuum filters added fallback cost. A restricted route was then fixed and tested on six fresh sunrise profiles. It gives a complete-time ratio of 0.994, with descriptive interval $[0.991, 0.997]$ and an equation-preparation ratio of 0.785, with descriptive interval $[0.776, 0.794]$. All 162 confirmation comparisons, 36 checks with the two earlier models and six applications pass exact coefficient checks. The preceding deployed equation policy uses the recorded 21-target sunrise domain and retains native choices elsewhere [36]. The measured three-model composition is slower, with time ratio 1.317 to the earlier two-model configuration. That preceding interface therefore retains native equation choices when either earlier learned policy is active.

Later training moves the equation decision before coefficient construction. The trees use 17 seed, operator and target features and train on 153,124 native candidates in eight physical profiles. Validation selects early filtering with native seed and row choices for the recorded double-box, vacuum and ladder batches and retains the earlier sunrise route. On eight fresh profiles, the deployed policy gives a complete-time ratio of 0.943 to native choices, with descriptive interval $[0.915, 0.970]$, and a preparation ratio of 0.638, with interval $[0.546, 0.734]$. Its complete-time ratio to the preceding release is 0.943. All 280 comparisons and eight basis-only applications pass independent exact checks. These results include inference and fallback costs and support the measured fixed-kinematic domain. The validation comparisons with the seed and row models remain recorded, and their added costs keep those combinations out of the selected route [37].

The higher-loop extension uses the exact variable $z = L(d-2)$ for the restricted coupled vacuum family. The trained equation selector and a shared symbolic reduction cover every tested order from one through twelve, with exact applications at 13, 16, 24 and 32. The learned route with separate reductions at each loop order has complete-time ratio 0.911 to the supplied full pool. Validation selects a simple rule for the mass pair for deployment; its shared route has complete-time ratio 0.155 to separate reductions with the full equation pool. Before Python startup and test-record archiving, the learned calculation has time ratio 0.943; time inside Kira has ratio 0.965. All 96 workflows pass exact checks. These results establish the stated coefficient reuse within this family and cost comparisons. General native IBP generation at higher loop orders remains outside this test domain [38].

The next extension learns shared equation choices for entire target batches and reduces repeated exact checks in the common variable z. Its four-tree cost model trains on 420 batches and 6,300 candidate orderings. Combining independent profiles in one Kira call preserves separate master bases and reduces repeated startup work. On the final twelve reserved profiles, the selected combined route has complete-time ratio 0.220 to the preceding separate workflow, with descriptive interval $[0.171, 0.270]$. All 460 reserved applications and the additional integration checks pass exact comparisons; the integration tests also verify the full-system fallback. Compiled and Python inference produce identical equation systems. The comparisons separate model decisions, shared exact arithmetic and shared Kira calls, and apply to the stated restricted vacuum family [40].

The direct-reduction extension evaluates selected triangular identities with exact integer polynomial arithmetic and checks every master coefficient through an independent Taylor construction. Validation selects the simple direct route. On eight fresh three-profile batches, its calculation-time ratio to the preceding combined workflow is 0.306, with descriptive interval $[0.246, 0.373]$. The full worker-time ratio is 0.430. All 200 reserved calculations pass exact checks, and an injected failure recovers through Kira. The comparison does not establish a further complete-time

advantage from learned ordering over both direct controls. The direct saving follows mainly from the exact family-specific recurrence; the native IBP-generation results retain their earlier scope [41].

The polynomial-reuse extension shares the exact transformations for $z = L(d-2)$ and the Taylor terms in the independent check. On eight new reserved batches, both changes together have calculation-time ratio 0.372 to the preceding direct route and full worker-time ratio 0.682. Keeping one process for several batches gives combined full-time ratio 0.365 across the three specified request streams. These streams share inputs, so this last ratio describes those sequences. All 352 reserved applications pass exact checks, including an independent audit of 28860 expanded coefficient positions. The request-interface checks also pass, including recovery through Kira after an injected failure. The changes reuse exact mathematical work and process startup; the previous model and ordering choice remain fixed. The supported domain remains the restricted coupled vacuum family, with native IBP-generation results retaining their earlier scope [42].

The compiled-arithmetic extension retains integer polynomial coefficients, compiles exact loop-order expansion and supplies lossless binary coefficient output. A 19-node regression tree learns batch strategies from 1,440 complete warm-worker measurements on 96 training batches. The first frozen test finds no established complete-time gain from the initial selected integer route once output reading is included. Compiling the binary reader then permits a new validation and independent test. Validation selects compiled expansion and binary output with a fixed recurrence rule. Its full process-time ratio to the preceding arithmetic is 0.850, and its ratio including output reading is 0.858, with descriptive interval $[0.800, 0.914]$. The deployed persistent-worker ratio including reading is 0.725 across three disjoint test streams. All 948 reserved batch calculations across both studies pass exact checks. The learned-to-fixed time ratio is 1.017, with descriptive interval $[0.969, 1.070]$. This interval includes one, so the reserved comparison does not establish a further time reduction from learned choices. The deployed default uses the fixed validation choice. The new tree, fixed-rule controls and earlier results remain preserved, and the supported domain remains the stated coupled vacuum family [44].

The direct cumulative comparison uses the saved original Kira executable and the final deployed route on identical restricted vacuum targets at every loop order from one through twelve. Eight independent mass-profile groups and five repetitions of three methods give 120 complete workflows. Including process startup, output saving and output reading, the final-to-original time ratio is 0.001839, corresponding to 543.815 times faster execution and 99.82% less time. The descriptive 95% speedup interval is $[488.134, 605.064]$. All matched outputs agree exactly, and the independent audit checks 27960 nonzero target–master coefficient polynomials after loop-order substitution. This directly measures the cumulative change without multiplying earlier ratios. The gain includes shared symbolic reductions, direct checked recurrences, compiled arithmetic and output changes. The selected route uses a fixed recurrence rule and makes no Kira call on these successful cases, so the result retains the restricted supplied-identity scope [45].

The scattering extension adds new nonplanar four-point and five-point inputs and exact reductions with independent symbolic invariants. All seventy comparison workflows pass, while the frozen equation filter requires native fallback in all thirty-five learned workflows and has complete-time ratio 1.252 to native choices. The new symbolic-capable application therefore defaults to native choices for these domains. Separate complete certificates prove seven-operation minima for two small physical systems when equation-subset selection and the stated pivot actions are allowed. The certificates cover finite source pools with three nonmaster columns; their costs and native coefficient checks provide exact reference labels without asserting a general minimum for scattering reductions [46].

The complete-cost study in Section 20 compares twelve fitted predictors and preserves the selected model during testing. All 620 timed reductions and 31 basis-only applications pass exact

checks, but the learned choice adds no reliable gain over integrated native controls. Combining two compatible target requests gives 48.3% less time, or 1.93 times faster reduction, in 200 exact comparisons across seven graph structures. The standard application retains the best fixed training strategy, and the learned route remains optional. Thirty further command checks verify the single-batch, learned joint and default joint applications without supplying target coefficients. These measurements cover native calculations at one through three loops. The earlier restricted vacuum result through twelve loops remains a separate result.

The graph-specific study in Section 21 fits seventy candidates and gives 6.3% less time relative to native choices on 720 reserved trials. Its ratio to a fixed strategy per graph is 0.9441. All trials and 43 additional applications pass exact checks. The study covers the seven known graphs at one through three loops with new rational profiles and repeated target patterns.

A Learning the cost of a complete reduction

The cost model receives a vector $\boldsymbol{f}_c$ for target batch c. Its entries are the number of loops, external momenta, inverse propagators, physical propagators and symbolic invariants; $\log(1 + n_c)$, where n_c is the number of targets; the maximum dot count, maximum numerator rank, mean dot count and mean numerator rank; the number of target sectors; and seven indicators for the graph structures. An indicator is one for its graph and zero for the other graphs. There are eighteen entries in total.

For an index vector $\boldsymbol{a}$, define

$$r(\boldsymbol{a}) = \sum_i \max(a_i, 0), \qquad s(\boldsymbol{a}) = \sum_i \max(-a_i, 0), \qquad q(\boldsymbol{a}) = \sum_i \max(a_i - 1, 0). \tag{143}$$

Here r is the positive index sum, s is the numerator rank, and q is the number of extra denominator powers, called dots. These definitions follow directly by counting the denominator and numerator factors. The initial bounds $B_c = (r_c, s_c, q_c)$ are the componentwise maxima over the targets. The trial seed regions use B_c, $B_c - (1,1,1)$, $B_c - (1,0,1)$, or $B_c + (1,1,1)$. Negative bounds are set to zero. These choices restrict equation generation. They do not assert that a smaller region always supplies a complete reduction.

Let t_{cj} be the median complete time of strategy j on training batch c, and let t_{c0} be the time of the integrated native strategy. The training response is

$$y_{cj} = \log \frac{t_{cj}}{t_{c0}}. \tag{144}$$

Each time includes unsuccessful attempts and the successful fallback. Thus the response penalizes a strategy that omits required equations. A smaller response means a smaller ratio because the logarithm is strictly increasing on positive numbers.

We fit constant, tree, linear and nearest-neighbour predictors of this response. The constant predictor averages each strategy's training responses. A tree splits the feature space and uses a constant vector within each leaf, following regression-tree construction [30]. For a leaf containing training set A, minimizing $\sum_{c \in A} (y_{cj} - v_j)^2$ gives

$$\frac{\partial}{\partial v_j} \sum_{c \in A} (y_{cj} - v_j)^2 = 2|A| v_j - 2 \sum_{c \in A} y_{cj} = 0, \qquad v_j = \frac{1}{|A|} \sum_{c \in A} y_{cj}. \tag{145}$$

Each split minimizes the sum of squared errors over the seven strategies. The tested maximum depths are two, four and six. Each depth is tested with a minimum of either one or three training batches per child.

For the linear models, we subtract each feature's training mean and divide by its training population standard deviation, computed with divisor equal to the number of training batches. A constant feature uses divisor one. Let Z contain these standardized feature rows with an leading intercept column, and let Y contain the responses. Ridge regression minimizes

$$J(W) = \|ZW - Y\|_F^2 + \lambda \operatorname{tr}(W^T P W), \qquad P = \operatorname{diag}(0, 1, \ldots, 1). \tag{146}$$

Here W is the matrix of fitted coefficients, $\|\cdot\|_F^2$ is the sum of squared matrix entries, and P leaves the intercept unpenalized. Differentiating each entry of W gives

$$\nabla_W J = 2Z^T(ZW - Y) + 2\lambda P W = 0, \qquad (Z^T Z + \lambda P) W = Z^T Y. \tag{147}$$

We solve this system for $\lambda = 0.1, 1, 10$.

The nearest-neighbour predictors restrict neighbours to the same graph, loop count, external-momentum count, propagator counts and number of symbolic invariants. They choose up to two or four training batches with the smallest squared distance in standardized features. The predicted response is the mean of their response vectors. The leaf-mean derivative above also derives this local constant estimate. If no eligible neighbour exists, the predictor returns equal costs and the selector uses native choices.

Let j_* be the strategy with the smallest predicted logarithmic cost $\widehat{y}_j(\boldsymbol{f})$. Validation selects a margin $\gamma \in \{0, 0.05, 0.15\}$, and the model chooses the strategy as follows:

$$\widehat{j}(\boldsymbol{f}) = \begin{cases} j_*, & \widehat{y}_{j_*}(\boldsymbol{f}) < \widehat{y}_0(\boldsymbol{f}) - \gamma, \\ 0, & \text{otherwise.} \end{cases} \tag{148}$$

Subtracting the two predicted logarithmic costs shows that the condition requires a predicted relative cost below $e^{-\gamma}$. Validation selects the model and margin with the smallest geometric mean time ratio. The selected settings remain fixed during reserved tests. This finite comparison establishes the best measured candidate within the study. It does not prove a globally optimal reduction strategy.

A.1 Parameter points and target lists

The complete-cost study keeps the seven denominator routings and their kinematic conventions defined earlier. Let h identify a rational parameter profile. Training uses $h = 41, 42$, validation uses $h = 43$, and testing uses $h = 44, 45$. In a common squared-momentum unit, the sunrise has squared masses $(2, 7, 11)$ and $p^2 = -1009 - 12h$. The planar box has $(s, t) = (-1009 - 12h, -1021 - 14h)$. The three-loop vacuum has squared masses $(1, 1, 1, 1, 1, 53 + 2h)$. The ladder keeps squared masses $(1, 0, 0, 0, 0, 0, 0, 0)$ and has $p^2 = -1009 - 12h$. The scattering assignments are

$$(s, t)_{\mathrm{NP}} = (-113 - 18h, -127 - 10h), \tag{149}$$

$$(s_{12}, s_{23}, s_{34}, s_{45}, s_{51})_{\mathrm{P}} = (-11 - 20h, -13 - 20h, -17 - 20h, -19 - 20h, -23 - 20h), \tag{150}$$

$$(s, t, v)_{\mathrm{box}} = (-113 - 18h, -127 - 10h, -149 - 12h). \tag{151}$$

These equations specify the selected input values. The dimension remains symbolic. The symbolic batches keep all independent invariants of their scattering graph symbolic.

For the four earlier multiloop graphs, we retain the ordered target list that starts with the corner, raises each physical denominator power once, and then introduces each single auxiliary numerator. We repeat these steps after removing one, two and three physical denominators, retain at least two, and remove duplicates. Each rational profile supplies a four-target batch and a batch of the first 32 targets, or all 21 targets for the sunrise. The three scattering graphs use the same construction with at most one removed denominator. Their larger batches have 32, 31 and 21 targets for the nonplanar box, pentagon and virtuality box.

For the symbolic nonplanar box and pentagon, training takes target entries 12–15, validation takes 16–19, and testing takes 20–23, with numbering starting at zero. These lists do not overlap. For the symbolic virtuality box, the respective single targets are $(3, 1, 1, 1)$, $(1, 3, 1, 1)$ and $(1, 1, 3, 1)$. These targets have two extra powers on one physical denominator. The rational batches reuse target patterns at different parameter points.

The joint-request test uses the larger rational batch at $h = 44$ for each graph and the three symbolic test batches. The symbolic virtuality box also includes $(1, 1, 1, 3)$, so it can supply two disjoint requests. A group of n targets is divided after entry $\lfloor n/2 \rfloor$, with the first request containing that many entries. The two requests have identical family definitions and are available

together. Their union contains each target once. Linearity of the reduction lets us return the coefficients for each original request by selecting its target rows from the joint result. This changes no coefficient and requires no additional integral identity. The test reuses reserved parameter points and keeps the learned model fixed.

A.2 Combining the measured times

Let m_{cj} be the median of the five test times for batch c and method j, and let method zero be its stated native control. For graph g with batch set C_g, we define

$$R_{gj} = \exp\left[\frac{1}{|C_g|}\sum_{c\in C_g}\log\frac{m_{cj}}{m_{c0}}\right], \qquad R_j = \exp\left[\frac{1}{7}\sum_{g=1}^{7}\log R_{gj}\right]. \tag{152}$$

The logarithm of a product equals the sum of the logarithms, so each expression is the corresponding geometric mean of the time ratios. The second expression assigns equal weight to each graph even when the numbers of batches differ. A ratio $R_j < 1$ means less time. The percentage saving is $100(1 - R_j)$, and the reciprocal $1/R_j$ is the speedup.

For the descriptive intervals, we sample seven graph labels with replacement, calculate their mean logarithmic ratio, and exponentiate. We repeat this 10,000 times and report the 2.5th and 97.5th percentiles. This procedure describes variation among the seven tested graphs. It does not provide a population guarantee for other integral families. The joint-request comparison uses the same calculation, with separate native requests as its first control. Its parameter points overlap the main reserved test, so it is an additional comparison on the same test population.

B Separate cost models for each graph

This experiment retains the seven denominator definitions and profile formulas in Appendix A. Development uses profile $h = 61$, training uses $h = 62, 63$, validation uses $h = 64$, and the reserved test uses $h = 65, 66$. The dimension remains symbolic. Related target batches share the same split, so their rational kinematic values cannot pass from the training set into the reserved set. The graph structures and target patterns occur in both sets.

Let P be the number of physical propagators and let $\boldsymbol{b} = (1, \ldots, 1, 0, \ldots, 0)$ have P entries equal to one. Let $\boldsymbol{e}_j$ be the unit vector for index j. The first batch contains $\boldsymbol{b} + 2\boldsymbol{e}_j$ for $j = 1, \ldots, \min(P, 3)$. Thus one denominator has power three in each target. For the second batch, define the lower-sector corner

$$\boldsymbol{b}^{\mathrm{low}} = \begin{cases} \boldsymbol{b} - \boldsymbol{e}_1, & P < 5, \\ \boldsymbol{b} - \boldsymbol{e}_1 - \boldsymbol{e}_3, & P \geq 5. \end{cases} \tag{153}$$

Include this corner and up to three single-dot targets, $\boldsymbol{b}^{\mathrm{low}} + \boldsymbol{e}_j$ with $b_j^{\mathrm{low}} = 1$, taking the first available indices in increasing order. The third batch uses the original corner $\boldsymbol{b}$ and contains $\boldsymbol{b} - 2\boldsymbol{e}_j$ for the first three auxiliary entries, or all auxiliary entries when fewer than three exist. When a family has no auxiliary entry, this construction repeats the first batch and we remove the duplicate. These formulas define the inputs; they do not infer their coefficients from the masters.

B.1 The allowed changes to Kira

For target batch $\mathcal{T}$ and a target $\boldsymbol{a}$, let $S(\boldsymbol{a}) = \{i : a_i > 0\}$ be its positive-index set. One strategy supplies only maximal target sectors:

$$\mathcal{S}_{\max} = \{S(\boldsymbol{a}) : \boldsymbol{a} \in \mathcal{T},\ S(\boldsymbol{a}) \not\subseteq S(\boldsymbol{a}') \text{ for every } \boldsymbol{a}' \in \mathcal{T}\}. \tag{154}$$

Kira then includes their subsectors. To see why this is a useful candidate, consider the shifted integrals produced by the IBP derivative. A raised index $a_i + 1$ carries a factor a_i, and the other shifts lower an index. If $a_i = 0$, the raising term vanishes; if $a_i < 0$, raising it once leaves it nonpositive. Thus an IBP equation seeded in one sector stays in that sector or its subsectors. This observation does not prove that the restricted pool contains every relation useful for a chosen master basis. We therefore retain the basis check and full-sector fallback.

Another strategy uses Kira's numerator truncation [9]. In a sector with t positive indices, Kira restricts the inherited numerator bound by

$$s \le \max(1, t - \tau + 1, s_{\text{explicit}}), \tag{155}$$

where τ is the chosen integer cutoff and s_{explicit} is a bound explicitly supplied for that sector. We test $\tau = P - s_c$ and $\tau = P - s_c + 1$, where s_c is the largest target numerator rank. The top-level sector retains its explicit target bound. The first cutoff combined with maximal target sectors forms the deterministic control. The development probes also test $\tau = P - s_c - 1$.

The remaining choices use the original bounds B_c, the smaller bounds $B_c - (1, 0, 1)$ with negative entries replaced by zero, the larger bounds $B_c + (1, 1, 1)$, Kira integral ordering five [8], or the preceding trained equation filter. Together these choices give nine strategies. Before each attempt, every strategy enforces a nonempty seed region in its declared top-level sectors. If $\mathcal{S}_0$ is that sector list and r_{req} is the requested positive-index bound, the actual bound is

$$r_{\text{run}} = \max\left(r_{\text{req}}, \max_{S \in \mathcal{S}_0} |S|\right). \tag{156}$$

Each positive index is at least one, so a seed in sector S has $\sum_{i \in S} a_i \ge |S|$. This proves the lower bound used in Eq. (156). The correction prevents an invalid configuration from adding a failed startup to any method's cost. Identical input configurations share one training or validation measurement. If a proposed reduction fails, it retries with native choices at B_c and then at $B_c + (1, 1, 1)$. The recorded cost includes every attempt.

B.2 Fitting and selecting the models

Each graph has its own predictors of $y_{cj} = \log(t_{cj}/t_{c0})$, where t_{cj} is the median complete cost of strategy j on batch c and zero denotes native choices. The nine input features are the target count; maximum dot count and numerator rank; minimum and maximum positive-index counts; mean dot count and numerator rank; number of maximal target sectors; and number of physical propagators. These features use the requested indices and family definition. They contain no reduced coefficients.

We fit ten candidates per graph: one constant predictor, trees of maximum depth one, two and three, a bagged ensemble of sixteen depth-three trees, ridge regressions with penalties $0.1, 1, 10$, and nearest-neighbour predictors with one and three neighbours. Trees use squared-error splits with at least one row in each child. Each ensemble tree receives a bootstrap sample of the training batches and uses all features at each split. This follows bootstrap aggregation [48]. For fitted trees $f_1, \ldots, f_{16}$, the ensemble prediction is

$$\widehat{y}_j(\boldsymbol{f}) = \frac{1}{16} \sum_{b=1}^{16} f_{bj}(\boldsymbol{f}). \tag{157}$$

This average also follows by minimizing $\sum_b (f_{bj}(\boldsymbol{f}) - v_j)^2$ with respect to v_j, using the leaf-mean derivative in Appendix A. That appendix derives the ridge fit and the local-mean estimates used here. Neighbour distances use the training standard deviations; a constant feature uses divisor one. We use two timing repetitions for training and three for validation. Within each batch comparison, every strategy uses the same computer. Different training batches can use different computers, and the training response normalizes each cost to its own batch baseline.

Validation considers decision margins $0, 0.05, 0.15$ in Eq. (148). It chooses the candidate and margin with the lowest complete cost separately for each graph. The controls are native choices, the deterministic sector-and-truncation rule, and the single strategy with the lowest geometric mean training cost for that graph. A fixed strategy can include the older equation filter. We enable the new model only when its validation cost ratio to the fastest control is at most 0.95. Otherwise, the route uses that control. This threshold is a selection rule, not a significance test. Unknown graph structures and features outside the fitted range use native choices.

The reserved comparison uses five repetitions of native choices, the deterministic rule, the fixed strategy per graph, and the selected route. The order rotates across batches and repetitions, giving every method the same number of appearances in each run position over the full test. Each run uses the same targets, prescribed basis, executable, and one processor. All methods retain the preceding exact implementation improvements, so the native control uses that same implementation with native selection rules. Full time includes input preparation, prediction, native IBP generation, exact reduction, coefficient checks, cleanup, and retries. Offline fitting, reference discovery, and saving measurement records stay outside the timer. Separate application checks receive the basis without target coefficients and compare their answers only after completion. The calling program and fitted parameters are loaded before the timing trials, and each trial starts a fresh Kira process. The additional application checks also record time with a newly started calling program; they do not supply a matched speed comparison for that condition.

We combine five-run median ratios within each graph and then give the seven graphs equal weight, as derived in Appendix A. The aggregate intervals resample graph groups. Per-graph plot bars show the range across the two reserved kinematic profiles. Two profiles do not support a general significance claim for that integral type, so those bars are reported as ranges.

C Selective seed expansion and exact basis completion

We keep the seven integral definitions in Appendix A and the target formulas in Appendix B. Development uses profile $h = 71$, training uses $h = 72, 73$, validation uses $h = 74$, and the reserved test uses $h = 75, 76$. These are separate rational parameter profiles. The graph structures and target index patterns occur in all splits, and d remains symbolic.

C.1 Changing individual seed bounds

The bounds $B_c = (r_c, s_c, q_c)$ retain the definitions in Appendix A: r_c bounds the sum of positive indices, s_c bounds the numerator rank, and q_c bounds the number of extra denominator powers. Each component starts from the largest value among the requested targets. We first enforce the sector lower bound in Eq. (156). The six new direct reductions use

$$B_c + \boldsymbol{\delta}, \qquad \boldsymbol{\delta} \in \{(1,0,0), (0,1,0), (0,0,1), (1,0,1), (1,1,0), (0,1,1)\}. \tag{158}$$

For a seed with t positive indices, summing $a_i = 1 + (a_i - 1)$ over those indices gives $r = t + q$. The positive-index and extra-power limits can therefore overlap, and different requested triples can

give the same seed region after all limits are applied. The candidate labels specify the requested settings. They do not assert distinct equation sets or sufficiency for every target. They let the model request extra numerator identities without also increasing both denominator bounds, for example. Each direct reduction keeps the prescribed-basis check described in Ref. [9]. If it fails, the calculation calls the preceding frozen graph-specific route and includes both attempts in its time.

C.2 Completing a temporary basis

We also test two ways to complete a smaller reduction. The first stage uses B_c and supplies the preferred masters, while allowing Kira to return additional integrals. Kira supports this behaviour when its early master-basis check is disabled [9]. Let M_m denote prescribed masters and let U_u denote additional integrals that remain in the first-stage output. For target I_t, this stage returns exact relations

$$I_t = \sum_m A_{tm} M_m + \sum_u C_{tu} U_u. \tag{159}$$

Here A_{tm} is the coefficient of prescribed master M_m, and C_{tu} is the coefficient of unresolved integral U_u. These coefficients are rational functions of the kinematics and d. The U_u need not form an independent master basis for the full family. They are unresolved integrals of the smaller equation system. Their indices, rather than the original target indices, define the second reduction request. That request uses its own componentwise target bounds plus $(1, 1, 1)$ and again supplies the prescribed basis. One candidate uses the maximal sectors of the U_u and their subsectors; the other keeps the original top-level sectors. Both retain the positive-index lower bound.

If the second reduction succeeds, it gives

$$U_u = \sum_m H_{um} M_m. \tag{160}$$

The coefficient H_{um} multiplies master M_m in the reduction of U_u. Substitution of Eq. (160) into Eq. (159) yields

$$I_t = \sum_m A_{tm} M_m + \sum_u C_{tu} \sum_m H_{um} M_m \tag{161}$$

$$= \sum_m \left(A_{tm} + \sum_u C_{tu} H_{um} \right) M_m. \tag{162}$$

Thus the final coefficient matrix is $A + CH$. We compute the sums and products exactly in the rational-function field, cancel common factors, and reject an output that contains an integral outside the prescribed basis. When either reduction fails, the preceding route supplies a full fallback. If no additional integral occurs, the second reduction is unnecessary. All basis conversion and fallback costs enter the timer. Independent reference coefficients check the final result only; the policy and the two reduction stages do not receive them.

C.3 Fitting, freezing, and comparison

The development set compares the preceding route, six direct expansions, and two basis-completion choices. We retain the preceding route and each case's fastest candidate when it lowers that case's complete time by at least ten percent. This rule selects candidates before training and does not inspect reserved data.

We then fit the ten model types and nine target features defined in Appendix B, separately for each graph. The new response is $\log(t_{cj}/t_{c\mathrm{prev}})$, so it directly measures improvement over the

preceding route. Here t_{cj} is the median complete time of candidate j on batch c, and t_{cprev} is the corresponding time of the preceding route. Two repetitions supply each training label, and three repetitions supply each validation cost. A fixed strategy minimizes geometric mean training time for each graph. Validation first selects the faster control between that fixed strategy and the preceding route. It then tests the fitted predictors at margins $0, 0.05, 0.15$ and enables one only when it lowers the control's validation time by at least five percent. The fitting formulas and their derivations remain those in Appendices A and B.

A fixed candidate can call the preceding learned route. Thus the fixed control isolates the extra choice among the new candidates, rather than removing all earlier learning.

The chosen graph policy and candidate set are fixed before the reserved tests. Inputs with another graph structure or target features outside the training range use the preceding route. That route retains its own native fallback. Each reserved batch compares native choices, the preceding route, the new fixed strategy, and the selected new route on the same computer. Five repetitions use a rotating order. All methods use the same executable and exact final coefficient checks. The time includes preparation, prediction, Kira, any basis conversion, checking, cleanup, and every retry. Offline training, independent reference generation, and writing benchmark records remain outside these times. The selection program and fitted parameters are loaded before these trials; each attempt starts a fresh Kira process. Separate application tests start a new caller and supply only the targets, family, and prescribed basis. They check the coefficients after the reduction.

We first take the median time for each batch and method, then combine ratios within each graph and give all seven graphs equal weight. The geometric-mean derivation in Appendix A also applies here. Descriptive aggregate intervals resample the seven graph groups. The per-graph bars show the range over the two reserved parameter profiles. These ranges describe the tested profiles and do not establish a gain for all integrals with the same graph.

Citations

[1] Stefan Weinzierl. Introduction to Feynman integrals, 2010. arXiv:1005.1855.

[2] Philipp Maierhöfer, Johann Usovitsch, and Peter Uwer. Kira—a Feynman integral reduction program. *Computer Physics Communications*, 230:99–112, 2018. arXiv:1705.05610.

[3] Stefan Weinzierl. *Feynman Integrals: A Comprehensive Treatment for Students and Researchers*. UNITEXT for Physics. Springer, 2022. arXiv:2201.03593; publisher DOI.

[4] K. G. Chetyrkin and F. V. Tkachov. Integration by parts: The algorithm to calculate β-functions in 4 loops. *Nuclear Physics B*, 192:159–204, 1981. publisher DOI.

[5] Thomas Gehrmann and Ettore Remiddi. Differential equations for two-loop four-point functions. *Nuclear Physics B*, 580:485–518, 2000. arXiv:hep-ph/9912329.

[6] A. V. Smirnov and A. V. Petukhov. The number of master integrals is finite, 2010. arXiv:1004.4199.

[7] Stefano Laporta. High-precision calculation of multiloop Feynman integrals by difference equations. *International Journal of Modern Physics A*, 15:5087–5159, 2000. arXiv:hep-ph/0102033.

[8] Philipp Maierhöfer and Johann Usovitsch. Kira 1.2 release notes, 2018. arXiv:1812.01491.

[9] Fabian Lange, Johann Usovitsch, and Zihao Wu. Kira 3: Integral reduction with efficient seeding and optimized equation selection, 2025. arXiv:2505.20197.

[10] Philipp Kant. Finding linear dependencies in integration-by-parts equations: A Monte Carlo approach. *Computer Physics Communications*, 185:1473–1476, 2014. arXiv:1309.7287.

[11] Jonas Klappert, Fabian Lange, Philipp Maierhöfer, and Johann Usovitsch. Integral reduction with Kira 2.0 and finite field methods. *Computer Physics Communications*, 266:108024, 2021. arXiv:2008.06494.

[12] Rushil Saraswat. Master-integral bases for sixteen one-loop and two-loop families. Accompanying family definitions, master bases and validation data, 2026.

[13] Rushil Saraswat. Target integrals constructed from master bases with seed and elimination records. Accompanying target integrals, source identities and validation data, 2026.

[14] Rushil Saraswat. Master bases and constructed targets for one thousand integral families. Accompanying family definitions, master bases, target reductions and validation data, 2026.

[15] Rushil Saraswat. Coupled vacuum master bases and reverse targets through twelve loops. Family definitions, source identities, grouped splits and independent checks, 2026.

[16] Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabas Poczos, Ruslan Salakhutdinov, and Alexander Smola. Deep sets. In *Advances in Neural Information Processing Systems*, volume 30, 2017. arXiv:1703.06114.

[17] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, volume 30, 2017. arXiv:1706.03762.

[18] Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*, 2019. arXiv:1711.05101.

[19] Rushil Saraswat. Seed-selection model after twenty expanded-data passes: Held-out tests through twelve loops. Frozen predictions, metrics, plots and validation records, 2026.

[20] Takaya Saito and Marc Rehmsmeier. The precision-recall plot is more informative than the ROC plot when evaluating binary classifiers on imbalanced datasets. *PLOS ONE*, 10(3):e0118432, 2015.

[21] scikit-learn developers. Average precision score: Definition and treatment of score thresholds. scikit-learn 1.5 documentation, 2024.

[22] Rushil Saraswat. Predicted-seed sufficiency through exact master-span tests in Kira. Frozen protocol, selected identities, symbolic results and independent checks, 2026.

[23] Rushil Saraswat. Reduction-propagation model trained on integral families through twelve loops. Model, optimizer lineage, state features and training records, 2026.

[24] Rushil Saraswat. Expanded-data reduction model: Held-out next-step and complete-path tests. Frozen predictions, exact row replays, plots and validation, 2026.

[25] Glenn W. Brier. Verification of forecasts expressed in terms of probability. *Monthly Weather Review*, 78(1):1–3, 1950.

[26] Rushil Saraswat. Exact reduction costs with learned seeds, learned rows and native Kira baselines. Frozen cases, exact reductions, repeated costs and independent checks, 2026.

[27] Rushil Saraswat. Frozen learned row choices inside the evolving symbolic matrix of Kira. Source changes, frozen protocol, exact row records and repeated comparisons, 2026.

[28] Rushil Saraswat. Learned seed selection and row choices in exact Kira reductions. Frozen policies, native and supplied-equation comparisons, and exact checks, 2026.

[29] Rushil Saraswat. Responsive fermat shutdown and learned seed selection in exact Kira reductions. Frozen code, paired solver comparisons, exact checks and complete timings, 2026.

[30] Leo Breiman, Jerome H. Friedman, Richard A. Olshen, and Charles J. Stone. *Classification and Regression Trees*. Chapman & Hall, 1984. Publisher record.

[31] Rushil Saraswat. Complete native multiloop reductions, learned seed selection and row choices trained on measured Kira cost. Physical families, frozen models, complete timings, exact checks and reproducible comparison code, 2026.

[32] SQLite Developers. PRAGMA statements: Synchronization and journal modes. `https://www.sqlite.org/pragma.html`. Accessed 10 October 2026.

[33] Rushil Saraswat. Integrated learned seed inference and native row policies with complete multiloop cost tests. Frozen methods, complete workflows, retained failures and independent exact checks, 2026.

[34] Rushil Saraswat. Shared model calculations with unchanged native kira reductions. Frozen implementations, complete timing pairs and independent exact checks, 2026.

[35] Rushil Saraswat. Parallel seed evaluation and exact modular inverses in native kira. Frozen arithmetic implementations, timing pairs and independent exact checks, 2026.

[36] Rushil Saraswat. Target-dependent equation selection: native training, frozen tests and exact checks. GitHub repository, commit `63d87b1e863e`, 2026. Code, model, measurements and retained development results.

[37] Rushil Saraswat. Learned equation selection before native kira identity construction. Frozen models, native integration, complete timings and independent exact checks, 2026. GitHub repository, commit `2e970c1c448c`.

[38] Rushil Saraswat. Equation selection and exact coefficient reuse across loop orders. Frozen models, identities, complete timings and exact higher-loop checks, 2026. GitHub repository, commit `0d088383aff7`.

[39] Pierre Geurts, Damien Ernst, and Louis Wehenkel. Extremely randomized trees. *Machine Learning*, 63:3–42, 2006.

[40] Rushil Saraswat. Learned batch equation reuse with shared exact checks and kira calls. Models, complete timings, exact checks and integration, 2026. Frozen data commit `61b97195b486`.

[41] Rushil Saraswat. Exact pre-reduction with learned ordering and a checked kira fallback. Frozen comparisons, exact outputs and implementation, 2026. Data commit `3c830972713b`.

[42] Rushil Saraswat. Exact polynomial reuse and persistent reduction workers. Frozen arithmetic comparisons, stream measurements and exact checks, 2026. Data commit `0dec744f90d6`.

[43] GNU MP developers. GNU MP manual: Integer functions. Integer arithmetic documentation. The recorded cluster implementation uses GMP 6.0.0.

[44] Rushil Saraswat. Exact integer expansion, lossless coefficient output and learned batch strategies. Frozen implementations, runtime-trained tree, full comparisons and exact checks, 2026. Data commit `94f9e0a9df8b`.

[45] Rushil Saraswat. Direct cumulative speedup comparison on identical restricted vacuum integrals. Frozen original and final implementations, identical inputs, timing records and exact audits, 2026.

[46] Rushil Saraswat. Native scattering reductions with symbolic kinematics and certified finite ibp paths. Physical definitions, frozen comparisons, exact symbolic checks and complete finite certificates, 2026.

[47] Richard Bellman. On the theory of dynamic programming. *Proceedings of the National Academy of Sciences*, 38(8):716–719, 1952.

[48] Leo Breiman. Bagging predictors. *Machine Learning*, 24:123–140, 1996. Publisher record.