ELECTRICAL CHARACTERISTICS (@ V_S = ±15 V, –55°C ≤ T_A ≤ +125°C, unless otherwise noted)

Parameter	Symbol	Conditions	OP177A Min	OP177A Typ	OP177A Max	OP177B Min	OP177B Typ	OP177B Max	Units
Input Offset Voltage	V_{OS}			10	20		25	55	µV
Average Input Offset Voltage Drift	TCV_{OS}	(Note 1)		0.03	0.1		0.1	0.3	µV/°C
Input Offset Current	I_{OS}			0.5	1.5		0.5	2.0	nA
Average Input Offset Current Drift	TCI_{OS}	(Note 2)		1.5	25		1.5	25	pA/°C
Input Bias Current	I_B		–0.2	2.4	4	–0.2	2.4	4	nA
Average Input Bias Current Drift	TCI_B	(Note 2)		8	25		8	25	pA/°C
Input Voltage Range	IVR	(Note 3)	±13	±13.5		±13	±13.5		V
Common-Mode Rejection Ratio	CMRR	V_{CM} = ±13 V	120	140		120	140		dB
Power Supply Rejection Ratio	PSRR	V_S = ±3 V to ±18 V	120	125		110	120		dB
Large-Signal Voltage Gain	A_{VO}	R_L ≥ 2 kΩ, V_O = ±10 V[4]	2000	6000		2000	6000		V/mV
Output Voltage Swing	V_O	R_L ≥ 2 kΩ	±12	±13.0		±12	±13.0		V
Power Consumption	P_D	V_S = ±15 V, No Load		60	75		60	75	mW
Supply Current	I_{SY}	V_S = ±15 V, No Load		2.0	2.5		2.0	2.5	mA

NOTES
[1]TCV_{OS} is 100% tested.
[2]Guaranteed by endpoint limits.
[3]Guaranteed by CMRR test condition.
[4]To insure high open-loop gain throughout the ±10 V output range, A_{VO} is tested at –10 V ≤ V_O ≤ 0 V, 0 V ≤ V_O ≤ +10 V, and –10 V ≤ V_O ≤ +10 V.

Specifications subject to change without notice.