

At $T_A = 25^{\circ}\text{C}$, $R_L = 10\text{ k}\Omega$ connected to $V_S / 2$, $V_{CM} = V_S / 2$, and $V_{OUT} = V_S / 2$, unless otherwise noted.

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFFSET VOLTAGE						
V _{OS}	Input offset voltage	V _S = 5 V		2	10	μV
dV _{OS} /dT	Input offset voltage drift	T _A = −40°C to 125°C		0.02	0.05	μV/°C
PSRR	Power-supply rejection ratio	V _S = 1.8 V to 5.5 V, T _A = −40°C to 125°C		1	5	μV/V
	Long-term stability ⁽¹⁾			See note ⁽¹⁾		μV
	Channel separation, dc			0.1		μV/V
INPUT BIAS CURRENT						
I _B	Input bias current	T _A = 25°C		±70	±200	pA
		T _A = −40°C to 125°C		±150		
I _{OS}	Input offset current			±140	±400	
NOISE						
	Input voltage noise	f = 0.01 Hz to 1 Hz		0.3		μV _{PP}
		f = 0.1 Hz to 10 Hz		1.1		
i _n	Input current noise	f = 10 Hz		100		fA/√Hz
INPUT VOLTAGE						
V _{CM}	Common-mode voltage range		(V−) − 0.1		(V+) + 0.1	V
CMRR	Common-mode rejection ratio	(V−) − 0.1 V < V _{CM} < (V+) + 0.1 V, T _A = −40°C to 125°C	106	130		dB