

Get started

Open in app





towards
data science

Follow

594K Followers



You have **2** free member-only stories left this month. [Sign up for Medium and get an extra one](#)



How to build your own Neural Network from scratch in Python

A beginner's guide to understanding the inner workings of Deep Learning




James Loy May 14, 2018 · 7 min read ★

Update: When I wrote this article a year ago, I did not expect it to be *this* popular. Since then, this article has been viewed more than 450,000 times, with more than 30,000 claps. It has also made it to the front page of Google, and it is among the first few search results for ‘*Neural Network*’. Many of you have reached out to me, and I am deeply humbled by the impact of this article on your learning journey.

This article also caught the eye of the editors at Packt Publishing. Shortly after this article was published, I was offered to be the sole author of the book ***Neural Network Projects with Python***. Today, I am happy to share with you that my book has been published!

The book is a continuation of this article, and it covers end-to-end implementation of neural network projects in areas such as face recognition, sentiment analysis, noise removal etc. Every chapter features a unique neural network architecture, including Convolutional Neural Networks, Long Short-Term Memory Nets and Siamese Neural Networks. If you’re looking to create a strong machine learning portfolio with deep learning projects, do consider getting the book!

You can get the book from Amazon: ***Neural Network Projects with Python***



James Loy

Neural Network Projects with Python: The ultimate guide to using Python to explore the true power of neural networks through six projects

^ See less

1st Edition

#1 New Release

in Neural Networks

Motivation: As part of my personal journey to gain a better understanding of Deep Learning, I've decided to build a Neural Network from scratch without a deep learning library like TensorFlow. I believe that understanding the inner workings of a Neural Network is important to any aspiring Data Scientist.

This article contains what I've learned, and hopefully it'll be useful for you as well!


What's a Neural Network?


Most introductory texts to Neural Networks brings up brain analogies when describing them. Without delving into brain analogies, I find it easier to simply describe Neural Networks as a mathematical function that maps a given input to a desired output.

Neural Networks consist of the following components

- An **input layer**, x
- An arbitrary amount of **hidden layers**
- An **output layer**, \hat{y}
- A set of **weights** and **biases** between each layer, W and b
- A choice of **activation function** for each hidden layer, σ . In this tutorial, we'll use a Sigmoid activation function.

The diagram below shows the architecture of a 2-layer Neural Network (*note that the input layer is typically excluded when counting the number of layers in a Neural Network*)





Input Layer

Hidden Layer

Output Layer

Architecture of a 2-layer Neural Network

Creating a Neural Network class in Python is easy.

Training the Neural Network

The output \hat{y} of a simple 2-layer Neural Network is:

$$\hat{y} = \sigma(W_2 \sigma(W_1 x + b_1) + b_2)$$


You might notice that in the equation above, the weights W and the biases b are the only variables that affects the output \hat{y} .

Naturally, the right values for the weights and biases determines the strength of the predictions. The process of fine-tuning the weights and biases from the input data is known as **training the Neural Network**.

Each iteration of the training process consists of the following steps:

- Calculating the predicted output \hat{y} , known as **feedforward**
- Updating the weights and biases, known as **backpropagation**

The sequential graph below illustrates the process.



Feedforward

As we've seen in the sequential graph above, feedforward is just simple calculus and for a basic 2-layer neural network, the output of the Neural Network is:

$$\hat{y} = \sigma(W_2 \sigma(W_1 x + b_1) + b_2)$$

Let's add a feedforward function in our python code to do exactly that. Note that for simplicity, we have assumed the biases to be 0.

```
1  class NeuralNetwork:
2      def __init__(self, x, y):
3          self.input      = x
4          self.weights1   = np.random.rand(self.input.shape[1],4)
5          self.weights2   = np.random.rand(4,1)
6          self.y          = y
7          self.output     = np.zeros(self.y.shape)
8
9      def feedforward(self):
10         self.layer1 = sigmoid(np.dot(self.input, self.weights1))
11         self.output = sigmoid(np.dot(self.layer1, self.weights2))
```

However, we still need a way to evaluate the “goodness” of our predictions (i.e. how far off are our predictions)? The **Loss Function** allows us to do exactly that.

Loss Function

There are many available loss functions, and the nature of our problem should dictate our choice of loss function. In this tutorial, we'll use a simple **sum-of-squares error** as our loss function.

$$\text{Sum-of-Squares Error} = \sum_{i=1}^n (y - \hat{y})^2$$

That is, the sum-of-squares error is simply the sum of the difference between each predicted value and the actual value. The difference is squared so that we measure the absolute value of the difference.


Our goal in training is to find the best set of weights and biases that minimizes the loss function.

Backpropagation

Now that we've measured the error of our prediction (loss), we need to find a way to **propagate** the error back, and to update our weights and biases.

In order to know the appropriate amount to adjust the weights and biases by, we need to know the **derivative of the loss function with respect to the weights and biases**.

Recall from calculus that the derivative of a function is simply the slope of the function.



Gradient descent algorithm

If we have the derivative, we can simply update the weights and biases by increasing/reducing with it (refer to the diagram above). This is known as **gradient descent**.

However, we can't directly calculate the derivative of the loss function with respect to the weights and biases because the equation of the loss function does not contain the weights and biases. Therefore, we need the **chain rule** to help us calculate it.

$$Loss(y, \hat{y}) = \sum_{i=1}^n (y - \hat{y})^2$$

$$\begin{aligned} \frac{\partial Loss(y, \hat{y})}{\partial W} &= \frac{\partial Loss(y, \hat{y})}{\partial \hat{y}} * \frac{\partial \hat{y}}{\partial z} * \frac{\partial z}{\partial W} \quad \text{where } z = Wx + b \\ &= 2(y - \hat{y}) * \text{derivative of sigmoid function} * x \\ &= 2(y - \hat{y}) * z(1-z) * x \end{aligned}$$

Chain rule for calculating derivative of the loss function with respect to the weights. Note that for simplicity, we have only displayed the partial derivative assuming a 1-layer Neural Network.

Phew! That was ugly but it allows us to get what we needed — the derivative (slope) of the loss function with respect to the weights, so that we can adjust the weights accordingly.

Now that we have that, let's add the backpropagation function into our python code.

```

1  class NeuralNetwork:
2      def __init__(self, x, y):
3          self.input      = x
4          self.weights1   = np.random.rand(self.input.shape[1],4)
5          self.weights2   = np.random.rand(4,1)
6          self.y          = y
7          self.output     = np.zeros(self.y.shape)
8
9      def feedforward(self):
10         self.layer1 = sigmoid(np.dot(self.input, self.weights1))
11         self.output = sigmoid(np.dot(self.layer1, self.weights2))
12
13     def backprop(self):
14         # application of the chain rule to find derivative of the loss function with respect to
15         d_weights2 = np.dot(self.layer1.T, (2*(self.y - self.output) * sigmoid_derivative(self.o
16         d_weights1 = np.dot(self.input.T, (np.dot(2*(self.y - self.output) * sigmoid_derivative
17
18         # update the weights with the derivative (slope) of the loss function
19         self.weights1 += d_weights1
20         self.weights2 += d_weights2

```

For a deeper understanding of the application of calculus and the chain rule in backpropagation, I strongly recommend this tutorial by 3Blue1Brown.

Backpropagation calculus | Deep learning, chapter 4



Putting it all together

Now that we have our complete python code for doing feedforward and backpropagation, let's apply our Neural Network on an example and see how well it does.

X1	X2	X3	Y
0	0	1	0
0	1	1	1
1	0	1	1
1	1	1	0

Our Neural Network should learn the ideal set of weights to represent this function. Note that it isn't exactly trivial for us to work out the weights just by inspection alone.

Let's train the Neural Network for 1500 iterations and see what happens. Looking at the loss per iteration graph below, we can clearly see the loss **monotonically decreasing towards a minimum**. This is consistent with the gradient descent algorithm that we've discussed earlier.



Let's look at the final prediction (output) from the Neural Network after 1500 iterations.

Prediction	Y (Actual)
0.023	0
0.979	1
0.975	1
0.025	0

Predictions after 1500 training iterations

We did it! Our feedforward and backpropagation algorithm trained the Neural Network successfully and the predictions converged on the true values.

Note that there's a slight difference between the predictions and the actual values. This is desirable, as it prevents **overfitting** and allows the Neural Network to **generalize** better to unseen data.

What's Next?

Fortunately for us, our journey isn't over. There's still **much** to learn about Neural Networks and Deep Learning. For example:

- What other **activation function** can we use besides the Sigmoid function?
- Using a **learning rate** when training the Neural Network
- Using **convolutions** for image classification tasks

I'll be writing more on these topics soon, so do follow me on Medium and keep an eye out for them!

Final Thoughts

I've certainly learnt a lot writing my own Neural Network from scratch.

Although Deep Learning libraries such as TensorFlow and Keras makes it easy to build deep nets without fully understanding the inner workings of a Neural Network, I find that it's beneficial for aspiring data scientist to gain a deeper understanding of Neural Networks.

This exercise has been a great investment of my time, and I hope that it'll be useful for you as well!

Sign up for The Variable

By Towards Data Science

Every Thursday, the Variable delivers the very best of Towards Data Science: from hands-on tutorials and cutting-edge research to original features you don't want to miss. [Take a look.](#)



Get this newsletter

You'll need to sign in or create an account to receive this newsletter.

Machine Learning

Deep Learning

Artificial Intelligence

Towards Data Science

Data Science

Get the Medium app

