


# RUby Beginner

A Programmer's Best Friend

Speaker: RIZQI NUR ASSYAUFI





### RIZQI NUR ASSYAUFI

bandithijo.github.io


🗘 🗹 🖪 🎯 bandithijo 🔀 gmail.com



/GNULinuxIndonesia /VimID
/JekyllID /ArchLinuxID
/dotfiles\_id /ruby\_id



### bandithijo





# .Introduction to Ruby

# > Sedikit tentang Ruby

```
:creator ⇒ Yukihiro "Matz" Matsumoto
:inspired ⇒ [ Perl, Smalltalk, Eiffel, Ada, Lisp ]
:public_release ⇒ 1995
:mass_acceptance \Rightarrow 2006 < DHH.create(Ruby on Rails,
                                        Basecamp,
                                        2003)
```

```
Matz.said("trying to make Ruby natural, not simple")
```

```
_.append("Ruby is simple in appearance,
         but is very complex inside,
         just like our human body.")
```

Source: About Ruby - http://www.ruby-lang.org/en/about/

- :dev\_a ⇒ "We moved away from Ruby.
   It's a dying language...
   and it has scalability problem"

Source: Nate Hopkins @hopsoft - https://twitter.com/hopsoft/status/1169706322851328000

```
success_stories("Ruby")

⇒ {
Simulations: [Nasa, Motorola, etc.]

3D_Modeling: [Google Scketchup, etc.]

Robotics : [Morpha Project (Siemens), etc.]

Security : [Metasploit Framework, etc.]

Web Apps : [Basecamp, etc.]
etc. : [...] }
```

Source: Ruby Lang Success Stories - http://www.ruby-lang.org/en/documentation/success-stories/

Ruby.who("INDONESIA").value

→ [ Bukalapak, Cookpad Indonesia, Midtrans, Quipper, Vidio, HIJUP, Alodokter, Apisentris, BBM, BelanjaQu, Binary Academy, Dropsuite, Forstok, GO-JEK, Jualo, Jurnal, Karir.com, KlikDokter, KMK Online, Mekari, Mitrais, Peentar, Qontak, Sejasa.com, Sleekr, Sribulancer, Stargle, Virkea, Wego, WGS

Source: :id\_ruby - Komunitas Ruby Indonesia - https://ruby.id

```
Language::Ruby.is_dead?(

"Ruby is alive and thinking about next 25 years"

"dev.to/teaglebuilt/is-ruby-dead-17em"

"hackernoon.com/the-state-of-ruby-2019-is-it-dying"

"GitHub Blog - Upgrading GitHub to Ruby 2.7"

"..."

> false
```

```
Language::Ruby.is_dead?(
    "Ruby is dead. (rubyisdead.science)"
)
    ⇒ false!
@jmcharnes.said("isrubydead.com")
    ⇒ NO
```

Just because Ruby is not popular anymore, it doesn't mean Ruby is dead, right?

### > Kenapa Memilih Ruby?

```
Learning::Ruby.is_worth?(:me).value
a: "Membantu menterjemahkan ide/solusi, menjadi sebuah
    script atau program."
  "Membantu menyederhanakan kerumitan."
c: "Membantu menjembatani interaksi user dengan sistem
    Operasi."
} ⇒ Handy & Practical
```

# > Kenapa Memilih Ruby?

```
PracticalThing::Ruby.can_do(:you)
a: "Full-stack web development"
b: "Web scraping & crawling"
c: "Static website generators"
d: "Automation, Backup, & DevOps tools"
e: "Build your own servers"
f: "Parsing data, cleaning & filtering"
  "API clients (like Twitter's or GitHub's)"
h: "Report generators (PDF, HTML, CSV, SpreadSheet)"
i: "Command-line tools"
j: "Games (gosu, Ruby2D, etc.)"
h: "Data Science"
1: "Machine Learning & AI" }
```

Source: RubyGuide - Jesus Castello - https://www.rubyquides.com/2019/11/what-can-you-do-with-ruby/

## > What's new on Ruby 2.7?

```
Ruby.whats_new?(2.7)

⇒ {
a: "Enumerable#tally"
b: "Numbered params for Blocks [Experimental]"
c: "Array#intersection"
d: "Enumerable#filter_map"
e: "Enumerator#produce"
f: "IRB gets a face lift"
g: "Ruby patern matching [Experimental]"
h: "10x performance ↑ for fiber & thread creattoin"
i: "Others changes, *go to source" }
```

Source: RubyGuide - Jesus Castello - https://www.rubyguides.com/2019/12/ruby-2-7-new-features/

# > What's new on Ruby 2.7?

 $\Leftrightarrow$ 

Ruby NEVER STOPS Improving!

Now, according to Matz...

This is the last 2.x version release. Because next year, we're getting <u>Ruby 3.0</u>!

Source: RubyGuide - Jesus Castello - https://www.rubyguides.com/2019/12/ruby-2-7-new-features/

# > Tips Memasang Ruby for Dev

### Groom your app's Ruby env. with Rbenv

#### Basic GitHub Checkout way:

```
$ cd
$ git clone https://github.com/rbenv/rbenv.git ~/.rbenv
$ echo 'export PATH="$HOME/.rbenv/bin:$PATH"' >> ~/.bashrc # ~/.zshrc
$ echo 'eval "$(rbenv init -)"' >> ~/.bashrc # ~/.zshrc
$ exec $SHELL
$ git clone https://github.com/rbenv/ruby-build.git ~/.rbenv/plugins/ruby-build
$ echo 'export PATH="$HOME/.rbenv/plugins/ruby-build/bin:$PATH"' >> ~/.bashrc
# ~/.zshrc
$ exec $SHELL
$ rbenv install 2.7.1
```

```
/home/bandithijo
project_a ← ruby 2.7.1
project_b ← ruby 2.6.3
project_c ← ruby 2.5.3
project_d ← ruby 2.4.2
```

Source: Rbenv (GitHub) - https://github.com/rbenv/rbenv/blob/master/README.md Source: GoRails.com - https://gorails.com/setup/ubuntu/20.04#ruby-rbenv

rbenv global 2.7.1

ruby -v



# .Variabel

## > Apa itu Variabel?

Digunakan untuk memberikan nama & menyimpan nilai (value)

```
In Ruby, Variable is just a label. ... a name for something that you can use to reference this value in your Ruby programs.
```

Just like the name we give to real-world things. When I say "apple" you know what I'm talking about. I don't have to describe it to you. That's what variables do!

```
nama_lengkap = 'Yukihiro Matsumoto' ← String

tahun_lahir = 1995 ← Integer

penjajahan = 3.5 ← Float

bumi_datar = false ← Boolean

kamar_kosong = nil ← NilClass

tim_dev = ['budi', 1, true] ← Array

kontak_dev = { 'nama': 'budi' } ← Hash
```

Source: RubyGuides - https://www.rubyguides.com/ruby-tutorial/variables/

# > Mengecek Class dari Variabel

Darimana kita tahu variable tertentu termasuk dalam Class apa?

#### Menggunakan .class

```
> nama = 'Yukihiro Matsumoto'
> nama.clas

⇒ String

> umur = 55
> umur.class
Integer

> tim_dev = ['Rizal', 'Reza', 'Rizqi']
> tim_dev.class
Array
```

# > Scope/jangkauan Variabel?

```
Local variable
team_name = "Elite Lokal"
Global variable (prefix: $)
$team_name = "Elite Global"
Instance variable (prefix: @)
@fav_food = "Indomie Instance"
Class variable (prefix: @@)
@@fav_drama = "Itaewon Class"
Constant variable (Huruf Besar)
```

Source: RubyGuides - https://www.rubyguides.com/ruby-tutorial/variables/

PHI = 3.14

# > Scope/jangkauan Variabel?

The difference between them? It's on their "scope".

A variable scope answers this question:

"From where can I access this variable?"

This is only going to matter when you start learning about Object-Oriented Programming.

Source: RubyGuides - https://www.rubyguides.com/ruby-tutorial/variables/ Source: RubyGuides - https://www.rubyguides.com/2019/03/ruby-scope-binding/

# > Scope/jangkauan Variabel?

Local variable

```
team_name = "Elite Lokal"
```

Source: RubyGuides - https://www.rubyguides.com/ruby-tutorial/variables/



# .Working with String (a)

Combining multiple string

#### a. Menggunakan operator +

```
> nama_depan = 'Yukihiro'
> nama_belakang = 'Matsumoto'
> nama_lengkap = nama_depan + nama_belakang
> puts nama_lengkap
"YukihiroMatsumoto"
> puts nama_depan + ' ' + nama_belakang
"Yukihiro Matsumoto"
> puts 'Yukihiro' + ' ' + 'Matsumoto'
"Yukihiro Matsumoto"
```

Combining multiple string

#### b. Menggunakan operator +=

```
> nama = ''
> nama += 'Yukihiro'
> nama += ' '
> nama += ' Matsumoto'
> puts nama
"Yukihiro Matsumoto"
```

Combining multiple string

c. Menggunakan Ruby concat method

```
> nama = ''
> nama.concat('Yukihiro')
> nama.concat(' ')
> nama.concat('Matsumoto')
> puts nama
"Yukihiro Matsumoto"
```

Combining multiple string

d. Menggunakan operator << (alias dari Ruby <a href="concat">concat</a> method)

```
> nama = ''
> nama << 'Yukihiro'
> nama << ' '
> nama << 'Matsumoto'

> puts nama
"Yukihiro Matsumoto"

> puts nama << 'Yukihiro' << ' ' << 'Matsumoto'
"Yukihiro Matsumoto"</pre>
```

```
> 'nomor rumah = ' << 1
# TypeError: no implicit conversion of Fixnum into String</pre>
```

Combining multiple string

d. Menggunakan operator << (alias dari Ruby <u>concat</u> method)

#### Problem:

```
> 'nomor rumah = ' << 1

⇒ "nomor rumah = \u0001"
```

#### Solusi:

```
> 'nomor rumah = ' << 1.to_s
⇒ "nomor rumah = 1"
```

Menggunakan to\_s method untuk mengkonversi Integer ke String.

```
Source: RubyGuides - https://www.rubyguides.com/2019/07/ruby-string-concatenation/Source: RubyGuides - https://www.rubyguides.com/2018/09/ruby-conversion-methods/
```

Combining multiple string

e. Menggunakan Ruby prepend method (kebalikan concat)

```
> nama = ''
> nama.prepend('Yukihiro')
> nama.prepend(' ')
> nama.prepend('Matsumoto')
> puts nama
"Matsumoto Yukihiro"
```

If you're thinking there is an append method, well there isn't for String.

append method only for arrays.

# > String Interpolation

Interpolation or merging of variables into strings is a powerful technique. It allows you to "templatize" a string.

#### a. Menggunakan "#{}"

```
> nama_depan = 'Yukihiro'
> nama_belakang = 'Matsumoto'
> umur_sekarang = 55
> puts "Nama: #{nama_depan} #{name_belakang}. Umur: #{umur}"
"Nama: Yukihiro Matsumoto. Umur: 55"
```

**Syarat:** String harus menggunakan tanda petik ganda ("...")

Source: RubyGuides - https://www.rubyguides.com/ruby-tutorial/variables/

# > Mengecek Method pada Class

Darimana kita tahu method apa yang tersedia dari sebuah Class?

#### Menggunakan .methods

```
> nama = 'Yukihiro Matsumoto'
> nama.clas
⇒ String

> nama.methods
=>[:unicode_normalize, :unicode_normalize!, :ascii_only?, :unpack, :unpack1, :to_r, :shells
plit, :encode, :encode!, :shellescape, :%, :include?, :*, :+, :pretty_print, :count, :partition, :
+@, :-@, :<=>, :<<, :==, :===, :sum, ..., ...]</pre>
```

Berapa banyak jumlah method yang tersedia? (misal: String)

```
> nama.class
String
> nama.methods.count
⇒ 192
```

# > String Method yang Biasa Digunakan

#### .upcase()

- > nama = 'Yukihiro Matsumoto'
- > nama.upcase
- ⇒ "YUKIHIRO MATSUMOTO"

#### .capitalize()

- > nama = 'yukihiro matsumoto'
- > nama.capitalize
- ⇒ "Yukihiro matsumoto"

#### .length()

- > nama = 'Yukihiro Matsumoto'
- > nama.length
- $\Rightarrow$  18

#### .downcase()

- > nama = 'Yukihiro Matsumoto'
- > nama.downcase
- ⇒ "yukihiro matsumoto"

#### .reverse()

- > nama = 'yukihiro matsumoto'
- > nama.reverse
- ⇒ "otomustam orihikuy"

#### .sub()

- > nama 'Yukihiro Matz'
- > nama.sub('Matz', 'Akita')
- ⇒ "Yukihiro Akita"

#### dmbl...

More: Ruby-Doc - https://ruby-doc.org/core-2.7.0/String.html

# > Escaping Character

Bagaimana cara melakukan escaping character pada String?

```
> 'malam jum'at'
SyntaxError: unexpected local variable or method...
> 'malam jum\'at'
"malam jum'at"
```

Alternatif gunakan double quote untuk escaping single quote:

```
> "malam jum'at"
"malam jum'at"
```

#### Contoh-contoh escaping character

```
\' : single quote
\" : double quote
\\ : backslash
\n : new line
\r : carriage return
\tag{thmuse}
```

More: AppSignal - https://blog.appsignal.com/2016/12/21/ruby-magic-escaping-in-ruby.html



# .Working with String (b)



# .Working with Number



# .Comparison Operators



# 



#### .Collection



# .Looping



#### . Method



## EXTENDED



### .File IO



## .Error Handling



# .Object Oriented Programming



#### .Module

#### > Tips mencari dengan Google

Gunakan prefix "ruby" sebagai awalan kata kunci untu mencari di Google.

Q ruby

Kemudian, diikuti dengan keyword apa yang mau dicari. Misal, tentang perulangan dengan method "each".

Q ruby each loop

Dengan cara ini, kita dapat membuat hasil pencarian yang lebih spesifik untuk bahasa pemrograman Ruby.

#### > Referensi Belajar Ruby

#### ▶ YouTube:

- GoRails
- Jesus Castello
- Drifting Ruby
- Nate Berkopec
- TechmakerTV
- Decypher Media
- zayne
- Code School
- FreeCodeCamp.org
- Sekolah Koding
- Agung Setiawan

#### 

- Ruby in 20 minutes
- RubyGuides.com

#### **≈**Online Course:

• IDRails.com

- > Referensi <u>Group</u> Telegram **A**untuk Bertanya seputar Ruby
  - Ruby Indonesia
  - Rails Indonesia

- > Referensi <u>Channel</u> Telegram **1**untuk Berita tentang Ruby
  - Ruby/Rails Inside



## :Terima\_Kasih

> Made with ♥by Rizqi Nur Assyaufi @BanditHijo ## 2020/09