i : Muhammad Sami, a Database Administrator (DBA), is tasked with creating and managing the student record system for a university.

Initially, Sami designs a table named `Students` with the following columns: `Student_ID`, `Student_Name`, and `Student_Semester`.

He populates the table with records for all students in the class.

After creating the schema and inserting the data, Sami realizes that he forgot to include an `Age` column.

He executes query to add the `Age` column. However, he notices that by default, the new column is positioned at the end of the table (after `Student_Semester`).

Dissatisfied with the column order, Sami drops (deletes) the `Age` column and re-adds it so that it appears immediately after `Student_Name`.

Upon running a `SELECT * FROM Students;` query, he observes that all existing student records show `NULL` values in the newly added `Age` column.

Finally, Sami writes SQL queries to update and populate the `Age` field for all existing student records.

Questions –

Q1:Write the SQL statement to create the initial `Students` table schema with appropriate data types and primary key constraints for `Student_ID`, `Student_Name`, and `Student_Semester`

`Q2`: Write a single SQL statement to insert sample records for three students into the newly created `Students` table

Q3: Write the SQL command that Sami initially used to add the `Age` column to the table.

Q4: Write the SQL command Sami used to drop (delete) the `Age` column from the table.

Q5: Explain why new columns added to an existing table appear at the end by default in standard SQL

Q6: Explain why the `Age` column contained `NULL` values for all previously inserted student records when Sami re-added the column.

ii : Joins

Create a Table name Personal !

```
CREATE TABLE personal (
   ID INT PRIMARY KEY,
   NAME VARCHAR(50),
   ADDRESS VARCHAR(50),
   CONTACT VARCHAR(15)
);
INSERT INTO personal (ID, NAME, ADDRESS, CONTACT) VALUES
(10, 'ankit', 'kapali', '2845236589'),
(20, 'ankush', 'kapali', '2845235491'),
(30, 'akhilesh', 'mango', '4567235491'),
(40, 'altaf', 'sakchi', '4567467490');
```

Create Another Table named professional

```
CREATE TABLE professional (
   WORK VARCHAR(50),
   DEPT VARCHAR(50),
   ID INT
);
INSERT INTO professional (WORK, DEPT, ID) VALUES
('teacher', 'BCA', 20),
('doctor', 'MBBS', 40),
('teacher', 'MBA', 50),
('programmer', 'java', 60),
('cashier', 'icici', 10);
```

Write

i-Apply Equi join Query and write it's Output

ii-Apply non-Equi join use > (Greater than) and write it's Output

ii- Apply Natural join and write it's Output

------ Attempt all questions carefully. Good luck! ----------