

# MongoDB Lab Manual



**RAJALAKSHMI  
ENGINEERING COLLEGE**

An AUTONOMOUS Institution  
Affiliated to ANNA UNIVERSITY, Chennai



**Department of Information  
Technology**

**Laboratory Record Regulation - 2023**

**MongoDB Essentials**

**IT23431**



# RAJALAKSHMI ENGINEERING COLLEGE

An Autonomous Institution, Affiliated to Anna University Rajalakshmi  
Nagar, Thandalam – 602 105



## DEPARTMENT OF INFORMATION TECHNOLOGY

### IT23431 - MONGODB ESSENTIALS

*(Regulation 2023)*

### LAB MANUAL

Name : .....

Register No. : .....

Year / Branch / Section : .....

Semester : .....

Academic Year : .....

| <b>Course Code</b> | <b>Course Title</b><br>(Laboratory Integrated Theory Course) | <b>L</b> | <b>T</b> | <b>P</b> | <b>C</b> |
|--------------------|--------------------------------------------------------------|----------|----------|----------|----------|
| <b>IT23431</b>     | <b>Mongo DB Essentials</b>                                   | <b>2</b> | <b>0</b> | <b>2</b> | <b>3</b> |

| <b>LIST OF EXPERIMENTS</b> |                                                         |                |             |
|----------------------------|---------------------------------------------------------|----------------|-------------|
| <b>SNO</b>                 | <b>NAME OF THE EXPERIMENT</b>                           | <b>PAGE NO</b> | <b>SIGN</b> |
| 1                          | Mongo DB installation and basic set up                  |                |             |
| 2                          | Creating and dropping tables with various constraints   |                |             |
| 3                          | Performing CRUD Operations                              |                |             |
| 4                          | Applying CRUD Operations                                |                |             |
| 5                          | Applying filtering and projections                      |                |             |
| 6                          | Perform Schema Design and Indexing                      |                |             |
| 7                          | Building aggregation pipelines                          |                |             |
| 8                          | Performing Data Transformation                          |                |             |
| 9                          | Establishing connection between Mongo Db and java       |                |             |
| 10                         | Develop a CRUD Application using Mongo Db(Mini Project) |                |             |

|                   |                                               |
|-------------------|-----------------------------------------------|
| <b>Ex. Nos. 1</b> | <b>MONGO DB INSTALLATION AND BASIC SET UP</b> |
| <b>Date :</b>     |                                               |

## AIM

To install Mongo DB and do the basic set up

## PROCEDURE

### 1. System Requirements and Pre-installation Checklist

Supported Windows Versions: Windows Server 2022, Windows Server 2019, Windows 11 (64-bit, x86\_64).

WSL Not Supported: MongoDB does not support Windows Subsystem for Linux (WSL).


Disk Space: Minimum 10 GB of free space (additional space for data).

Hardware Requirements:

- RAM: Minimum 4 GB.
- CPU: Intel (Sandy Bridge or later), AMD (Bulldozer or later).

### 2. Downloading and Setting Up MongoDB

Go to the MongoDB official download page to access the MongoDB Community Server section and begin downloading the installation package for Windows.




### 3. Selecting the Correct MongoDB Version and downloading the MongoDB Installer (MSI Package)

- ❖ Choose the latest stable release for optimal performance and security, unless you need an older version.
- ❖ Ensure you select the 64-bit version of MongoDB, as 32-bit versions are not compatible with MongoDB.


#### Downloading:

- ❖ Select the MSI package type for Windows and click Download.
- ❖ The .msi installer file will download to your default location (usually the Downloads folder).
- ❖ Double-click the .msi file to launch the installation wizard and begin setup.




## 4. Installing MongoDB on Windows

- i. Locate the downloaded .msi file in the Downloads folder.





- ii. Double-click the file to start the installation wizard.






iii. Follow the prompts in the wizard to complete the setup.





## 5. Choosing the Installation Type


- i. Choose Complete Setup for a default installation with all features (recommended).
- ii. Select Custom Setup to choose specific components and installation locations.



## 6. Configuring Network Options and Data Directories:


**Service & Network Setup:** Choose to run MongoDB as a service and configure network settings (localhost or custom IP).

**Install & Launch:** Complete installation, then start MongoDB with mongod and verify it's running with the "waiting for connections" message.




## 7. Completing the Installation Process

- i. **Install MongoDB Compass (Optional):** You can choose to install MongoDB Compass along with the MongoDB server. This GUI tool helps in managing your database.



- ii. **Finalize Installation:** Review your settings and click 'Install' to begin the installation process. A progress bar will display the installation status.




- iii. **Launch MongoDB:** Once the installation is complete, you can start MongoDB using the mongod command in the command prompt if it's not set to run as a service. Ensure that the mongod.exe process is running successfully by checking for the 'waiting for connections' message in the console output.



MongoDB Compass is being installed.

It will launch once it is done.

iv. **Mongo DB Start Screen:**



**RESULT**

|            |                                                       |
|------------|-------------------------------------------------------|
| Ex. Nos. 2 | CREATING AND DROPPING TABLES WITH VARIOUS CONSTRAINTS |
| Date:      |                                                       |

## CREATE

### Creating a database using the Use <db> command:

The use <db> command selects a specific database for executing queries in a MongoDB session. If the specified database does not exist, MongoDB creates it when data is inserted.

**syntax :** `use <databaseName>`

**Query:** `use employee`

**output:**

```
> use employee
< switched to db employee
```

### Creating a collection using the db.createCollection("<collectionName>") command :

The db.createCollection("<collectionName>") command in MongoDB creates a new collection with the specified name in the current database.

**syntax :** `db.createCollection("<collectionName>")`

**Query:** `db.createCollection("employees")`

**output:**

```
> db.createCollection("employees")
< { ok: 1 }
```

**Inserting Data into a collection using `db.<collectionName>.insertOne({<document>})` :**

The `db.<collectionName>.insert({<document>})` command in MongoDB inserts a new document into the specified collection. .

**syntax :** `db.<collectionName>.insertOne ({<document>})`

**Query:** `db.employees.insertOne ({name:"nick",age:25,desig:"HR",  
salary:30000}) ;`

**output:**

```
> db.employees.insertOne({name:"nick",age:25,desig:"HR",salary:30000});  
< {  
  acknowledged: true,  
  insertedId: ObjectId('67a84015fa341e0916c7ebea')  
}
```

**Viewing all collections in a database using `show collections` command:**

The `show collections` command in MongoDB lists all collections in the currently selected database.

**syntax :** `show collections`

**Query:** `show collections`

**output:**

```
> show collections  
< emp  
  employees
```

**Checking if a collection exists using the**

**`db.getCollectionNames().includes("<collectionName>")` command:**

The `db.getCollectionNames().includes("<collectionName>")` command in MongoDB checks if a specific collection exists in the current database and returns true or false.

**syntax :** `db.getCollectionNames().includes("<collectionName>")`

Query: `db.getCollectionNames().includes("employees")`

output:

```
> db.getCollectionNames().includes("employees")
< true
```

## DROP

**Dropping a collection using `db.<collectionName>.drop()` the command:**

The `db.<collectionName>.drop()` command in MongoDB permanently deletes the specified collection and all its documents from the database

syntax : `db.<collectionName>.drop()`

Query: `db.employees.drop()`

output:

```
> db.employees.drop()
< true
```

**Verifying if a collection has been dropped using show collections command:**

The show collections command in MongoDB lists all collections in the currently selected database.

syntax : `show collections`

Query: `show collections`

output:

```
> show collections
< emp
```

**Testing automatic collection creation using the**

**`db.<newCollectionName>.insert({<document>})` command:**

The `db.<newCollectionName>.insert({<document>})` command in MongoDB inserts a new document into the specified collection, creating the collection if it does not already exist.

**syntax :** `db.<newCollectionName>.insert({<document>})`

**Query:** `db.student.insertOne({name:"Riley",age:17,marks:95});`

**output:**

```
> db.student.insertOne({name:"Riley",age:17,marks:95});
< {
  acknowledged: true,
  insertedId: ObjectId('67a84761fa341e0916c7ebee')
}
```

## DROP DATABASE

**Dropping a database using the `db.dropDatabase()` command:**

The `db.dropDatabase()` command is used to permanently delete the selected database along with all its collections and documents. Before executing, ensure you have switched to the correct database using the `use database_name` command.

**syntax :** `db.dropDatabase()`

**Query:** `db.dropDatabase()`

**output:**

```
> use employee
< switched to db employee
> db.dropDatabase()
< { ok: 1, dropped: 'employee' }
```

**RESULT:**



|            |                            |
|------------|----------------------------|
| Ex. Nos. 3 | PERFORMING CRUD OPERATIONS |
| Date:      |                            |

## Creating a Collection

- Command: `db.createCollection("<collectionName>")`

## 4. Inserting Data (Create Operation)

### Insert One Document

### Insertion with Nested Fields

### Insert Multiple Documents

### Insertion with Specified `_id`

### Insertion with Arrays

## 5. Reading Data (Read Operation)

- Finding All Documents
  - Command: `db.<collectionName>.find()`
- Finding Specific Documents
  - Command: `db.<collectionName>.find({<query>})`
- Finding a Single Document
  - Command: `db.<collectionName>.findOne({<query>})`

## 6. Updating Data (Update Operation)

- Updating a Single Document
  - Command: `db.<collectionName>.updateOne({<query>}, {$set: {<update>}})`
- Updating Multiple Documents
  - Command: `db.<collectionName>.updateMany({<query>}, {$set: {<update>}})`

## 7. Deleting Data (Delete Operation)

- Deleting a Single Document
  - Command: `db.<collectionName>.deleteOne({<query>})`
- Deleting Multiple Documents
  - Command: `db.<collectionName>.deleteMany({<query>})`



|            |                          |
|------------|--------------------------|
| Ex. Nos. 4 | APPLYING CRUD OPERATIONS |
| Date:      |                          |

## SCENARIO 1: PROJECT TASK MANAGEMENT

The company assigns tasks to employees for various projects. Each task includes the task name, assigned employee, status, and deadline.

### 1. Create Database and Collections:

Create a MongoDB database called `taskdb`. In this database, create a collection named `tasks` to store task information.

```
>_MONGOSH
> use admin
< switched to db admin
> use taskdb
< switched to db taskdb
> db.createCollection("tasks")
< { ok: 1 }
taskdb> |
```

### 2. Insert Documents:

Insert a document for a task named "frontend development" assigned to "alice" with a status of "in progress" and a deadline of "2025-03-01".

```
> db.tasks.insertOne({name:"alice",task:"frontend development",status:"in progress",deadline:"2025-03-01"})
< {
  acknowledged: true,
  insertedId: ObjectId('67dc0e86990f9ff08c9059f4')
}
```

### 3. Update Documents:

- a) Change the status of the "frontend development" task to "completed".

```
> db.task.updateOne({task:"frontend development"},{$set:{task:"completed"}})
< {
  acknowledged: true,
  insertedId: null,
  matchedCount: 0,
  modifiedCount: 0,
  upsertedCount: 0
}
```

4.

5.

6. b) Extend the deadline of the "frontend development" task to "2025-04-01".

```
> db.task.updateMany({task:"frontend development"},{$set:{deadline:"2025-04-01"}})
< {
  acknowledged: true,
  insertedId: null,
  matchedCount: 0,
  modifiedCount: 0,
  upsertedCount: 0
}
```

7.

- c) Assign a new employee "bob" to the same task.

8.

### 9. Read Documents:

Retrieve all tasks that are assigned to "alice" and are marked as "in progress".

### 10. Delete Documents:

Delete the task document for "frontend development" from the `tasks` collection.

## SCENARIO 2: TESTING TEAM MANAGEMENT

The company has a testing team responsible for verifying the functionality of different software products. Each tester is assigned to various test cases, and the status of each test case is tracked (e.g., "passed", "failed", "in progress").

### 1. Create Database and Collections:

Create a MongoDB database called `testdb`. Inside this database, create two collections: `testers` (for storing tester information) and `testcases` (for storing test case details).

```
> use testdb  
< switched to db testdb
```

```
> show dbs  
< Classrooms 200.00 KiB  
  admin      40.00 KiB  
  config     96.00 KiB  
  librarydb  168.00 KiB  
  local      80.00 KiB  
  spacedb    72.00 KiB  
  testdb     16.00 KiB
```

```
> db.createCollection("testers")  
< { ok: 1 }  
> db.createCollection("testcases")  
< { ok: 1 }
```

```
> show collections  
< testcases  
  testers
```

## 2. Insert Documents:

Insert a document into the `testers` collection for a tester named "alice", with a role of "QA Engineer". Insert a test case document into the `testcases` collection, including the test case name "Login Test", status "in progress", assigned to "alice", and a priority of "high".

```
> db.testers.insertOne({eId:"e101",name:"Alice",roll:"QA Engineer"})
< {
  acknowledged: true,
  insertedId: ObjectId('67dbf183ca5096f1f917488c')
}
```

```
> db.testers.find()
< {
  _id: ObjectId('67dbf183ca5096f1f917488c'),
  eId: 'e101',
  name: 'Alice',
  roll: 'QA Engineer'
}
```

```
> db.testcases.insertOne({tcId:"tc101",tcName:"Login Test",status:"in progress",testerAssigned:"Alice",priority:"High"})
< {
  acknowledged: true,
  insertedId: ObjectId('67dbf245ca5096f1f917488e')
}
```

```
> db.testcases.find()
< {
  _id: ObjectId('67dbf245ca5096f1f917488e'),
  tcId: 'tc101',
  tcName: 'Login Test',
  status: 'passed',
  testerAssigned: 'Alice',
  priority: 'High'
}
```

### 3. Update Documents:

a) Change the status of "Login Test" to "passed".

```
> db.testcases.updateOne({tcName:"Login Test"},{$set:{status:"passed"}})
< {
  acknowledged: true,
  insertedId: null,
  matchedCount: 1,
  modifiedCount: 1,
  upsertedCount: 0
}
```

b) Add a new test case called "Signup Test" with status "failed" and assign it to "bob".

```
> db.testcases.insertOne({tcId:"tc102",tcName:"Sign Up Test",status:"failed",testerAssigned:"Bob",priority:"High"})
< {
  acknowledged: true,
  insertedId: ObjectId('67dbf3deca5096f1f917488f')
}
```

c) Update "alice's" role to "Senior QA Engineer".

```
> db.testers.updateOne({$and:[{eId:"e101"},{name:"Alice"}]},{$set:{roll:"Senior QA Engineer"}})
< {
  acknowledged: true,
  insertedId: null,
  matchedCount: 1,
  modifiedCount: 1,
  upsertedCount: 0
}
```

### 4. Read Documents:

Retrieve all test cases assigned to "alice" and list their names, statuses, and priorities.

```
> db.testcases.find({testerAssigned:"Alice"},{tcName:1,status:1,priority:1,_id:0})
< {
  tcName: 'Login Test',
  status: 'passed',
  priority: 'High'
}
```

## 5. Delete Documents:

Delete the "Signup Test" case from the `testcases` collection.

```
> db.testcases.deleteOne({tcName:"Sign Up Test"})
< {
  acknowledged: true,
  deletedCount: 1
}
```

```
> db.testcases.find()
< {
  _id: ObjectId('67dbf245ca5096f1f917488e'),
  tcId: 'tc101',
  tcName: 'Login Test',
  status: 'passed',
  testerAssigned: 'Alice',
  priority: 'High'
}
testdb> |
```



## Scenario: Student Management System

The school needs to manage student records, which include the student's name, age, grade, and the courses they are enrolled in. The system allows CRUD (Create, Read, Update, Delete) operations to efficiently manage student data.

### 1. Create Database and Collection

Create a MongoDB database called `studentdb` to store student information. Inside this database, create a collection called `students`. This collection will contain the following fields for each student:

- `name`: The name of the student (string).
- `age`: The student's age (integer).
- `grade`: The grade the student is in (string, e.g., "10th").
- `courses`: An array of courses the student is enrolled in (array of strings).

### 2. Insert Document

- Insert a student named "Alice Johnson", who is 16 years old, in the 10th grade, and enrolled in "Math", "Science", and "English".
- Insert another student named "Bob Smith", who is 15 years old, in the 9th grade, and enrolled in "History", "Math", and "Geography".

### 3. Update Documents

- a) Change Alice Johnson's grade to "11th" after she advances to the next year.
- b) Add a new course, "History," to Alice Johnson's list of enrolled courses.
- c) Change Bob Smith's age to 16 after he celebrates his birthday.

### 4. Read Documents

- a) Retrieve all students who are enrolled in "Math".
- b) Retrieve all students who are in the 10th grade.
- c) Get all students who are older than 15 years of age.

### 5. Delete Documents

- a) Delete a specific student, such as "Bob Smith," from the `students` collection.
- b) Remove a course, like "Geography," from Bob Smith's list of courses.

## SCENARIO-4

A hospital management system stores patient data in MongoDB.

The system needs to efficiently handle patient records, diagnoses, and treatment history while ensuring scalability and quick retrieval.

(a) Write MongoDB commands to create a new database named "HospitalDB" and a collection "patients".

```
> use HospitalDB
< switched to db HospitalDB
> db["patients"].find()
<
```

```
db.createCollection("patients")
{ ok: 1 }
```

b) Insert at least two sample patient documents with fields: patient\_id, name, age, diagnosis, and treatment\_plan.

```
db.patients.insertMany([{{patient_id:"p1",name:"Alex",age:19,diagnosis:"LIVER",treatment_plan:""}}])
{
  acknowledged: true,
  insertedIds: {
    '0': ObjectId('67dbbb2e9e04f76e124f13b5')
  }
}
db.patients.insertMany([{{patient_id:"p2",name:"Ale",age:19,diagnosis:"LIVER",treatment_plan:"done"},{patient_id:"p3",name:"Al",age:18,diagnosis:"DIABETES",treatment:"in progress"}}])
{
  acknowledged: true,
  insertedIds: {
    '0': ObjectId('67dbbcc99e04f76e124f13b6'),
    '1': ObjectId('67dbbcc99e04f76e124f13b7')
  }
}
```

```
db.patients.find()
{
  _id: ObjectId('67dbbb2e9e04f76e124f13b5'),
  patient_id: 'p1',
  name: 'Alex',
  age: 19,
  diagnosis: 'LIVER',
  treatment_plan: ''
}
{
  _id: ObjectId('67dbbcc99e04f76e124f13b6'),
  patient_id: 'p2',
  name: 'Ale',
  age: 19,
  diagnosis: 'LIVER',
  treatment_plan: 'done'
}
{
  _id: ObjectId('67dbbcc99e04f76e124f13b7'),
  patient_id: 'p3',
  name: 'Al',
  age: 18,
  diagnosis: 'DIABETES',
  treatment_plan: 'in progress'
}
```

c) Write a MongoDB query to retrieve all patients diagnosed with "Diabetes" from the "patients" collection.

Modify the query to return only the name and treatment\_plan fields while excluding \_id.

```
> db.patients.find({diagnosis:"DIABETES"})
< {
  _id: ObjectId('67dbbcc99e04f76e124f13b7'),
  patient_id: 'p3',
  name: 'Al',
  age: 18,
  diagnosis: 'DIABETES',
  treatment_plan: 'in progress'
}
> db.patients.find({diagnosis:"DIABETES"},{name:1,treatment_plan:1,_id:0})
< {
  name: 'Al',
  treatment_plan: 'in progress'
}
```

d) Assume the hospital management decides to archive old patient records. Write a MongoDB query to drop the patient records.

```
> show collections
< patients
> db.patients.drop()
< true
```

## SCENARIO-5

A university uses MongoDB to manage its course registration system. The database stores data about students, courses, and registrations. Each course document contains details such as `course_id`, `course_name`, `instructor`, and `enrolled_students`.

Task:

(a) Insert new courses into the `courses` collection. Provide MongoDB commands to insert at least three courses, each with details for `course_id`, `course_name`, `instructor`, and an empty array for `enrolled_students`.

```
> use mydatabase
< switched to db mydatabase
> db.createCollection("courses")
< { ok: 1 }
```

```
db.courses.insertMany([
  {course_id:"CS101",course_name:"OS",instructor:"Dr. Smith",enrolled_students:[]},
  {course_id:"CS102",course_name:"MongoDB",instructor:"Dr. Lilly",enrolled_students:[]},
  {course_id:"MA103",course_name:"Probability",instructor:"Dr. Frank",enrolled_students:[]}
])
{
  acknowledged: true,
  insertedIds: {
    '0': ObjectId('67dbc3ae66e8ef0c0b83b5d1'),
    '1': ObjectId('67dbc3ae66e8ef0c0b83b5d2'),
    '2': ObjectId('67dbc3ae66e8ef0c0b83b5d3')
  }
}
```

```
db.courses.find()
{
  _id: ObjectId('67dbc3ae66e8ef0c0b83b5d1'),
  course_id: 'CS101',
  course_name: 'OS',
  instructor: 'Dr. Smith',
  enrolled_students: []
}
{
  _id: ObjectId('67dbc3ae66e8ef0c0b83b5d2'),
  course_id: 'CS102',
  course_name: 'MongoDB',
  instructor: 'Dr. Lilly',
  enrolled_students: []
}
{
  _id: ObjectId('67dbc3ae66e8ef0c0b83b5d3'),
  course_id: 'MA103',
  course_name: 'Probability',
  instructor: 'Dr. Frank',
  enrolled_students: []
}
```

(b) Write a MongoDB update operation to enroll students in a course. Assume you need to add students to a course with the `course_id` of "CS101". The students' IDs to add are "S1001", "S1002", and "S1003".

```
> db.courses.updateOne({course_id:"CS101"},{$push:{enrolled_students:{$each:["S1001","S1002","S1003"]}}})
< {
  acknowledged: true,
  insertedId: null,
  matchedCount: 1,
  modifiedCount: 1,
  upsertedCount: 0
}
> db.courses.find()
< {
  _id: ObjectId('67dbc3ae66e8ef0c0b83b5d1'),
  course_id: 'CS101',
  course_name: 'OS',
  instructor: 'Dr. Smith',
  enrolled_students: [
    'S1001',
    'S1002',
    'S1003'
  ]
}
{
  _id: ObjectId('67dbc3ae66e8ef0c0b83b5d2'),
  course_id: 'CS102',
  course_name: 'MongoDB',
  instructor: 'Dr. Lilly',
  enrolled_students: []
}
{
  _id: ObjectId('67dbc3ae66e8ef0c0b83b5d3'),
  course_id: 'MA103',
  course_name: 'Probability',
  instructor: 'Dr. Frank',
  enrolled_students: []
}
```

(c) Create a MongoDB query to find all courses taught by a specific instructor named "Dr. Smith" and display only the course names and enrolled student IDs.

```
> db.courses.find({instructor:"Dr. Smith"},{_id:0,course_name:1,enrolled_students:1})
< {
  course_name: 'OS',
  enrolled_students: [
    'S1001',
    'S1002',
    'S1003'
  ]
}
```

(d) Also, write a command to delete a course if it has no enrolled students at the end of the registration period.

```
> db.courses.deleteMany({enrolled_students:{$eq:[]}})
< {
  acknowledged: true,
  deletedCount: 2
}
> db.courses.find()
< {
  _id: ObjectId('67dbc3ae66e8ef0c0b83b5d1'),
  course_id: 'CS101',
  course_name: 'OS',
  instructor: 'Dr. Smith',
  enrolled_students: [
    'S1001',
    'S1002',
    'S1003'
  ]
}
```





|                   |                                           |
|-------------------|-------------------------------------------|
| <b>Ex. Nos. 5</b> | <b>APPLYING FILTERING AND PROJECTIONS</b> |
| <b>Date:</b>      |                                           |

|                   |                                           |
|-------------------|-------------------------------------------|
| <b>Ex. Nos. 6</b> | <b>PERFORM SCHEMA DESIGN AND INDEXING</b> |
| <b>Date:</b>      |                                           |

|                   |                                       |
|-------------------|---------------------------------------|
| <b>Ex. Nos. 7</b> | <b>BUILDING AGGREGATION PIPELINES</b> |
| <b>Date:</b>      |                                       |

|            |                                |
|------------|--------------------------------|
| Ex. Nos. 8 | PERFORMING DATA TRANSFORMATION |
|            |                                |

|                   |                                                          |
|-------------------|----------------------------------------------------------|
| <b>Ex. Nos. 9</b> | <b>ESTABLISHING CONNECTION BETWEEN MONGO DB AND JAVA</b> |
| <b>Date:</b>      |                                                          |

|                    |                                                                 |
|--------------------|-----------------------------------------------------------------|
| <b>Ex. Nos. 10</b> | <b>DEVELOP A CRUD APPLICATION USING MONGO DB (MINI PROJECT)</b> |
|                    |                                                                 |

|                   |                         |
|-------------------|-------------------------|
| <b>Ex. Nos. 1</b> | <b>BASIC C PROGRAMS</b> |
|                   |                         |

|                   |                         |
|-------------------|-------------------------|
| <b>Ex. Nos. 1</b> | <b>BASIC C PROGRAMS</b> |
|                   |                         |

<https://www.guvi.com/blog/guide-for-mongodb-installation-on-windows/>





**Rajalakshmi Nagar Thandalam, Chennai - 602 105.**

**Phone : +91-44-67181111, 67181112**

**Website : [www.rajalakshmi.org](http://www.rajalakshmi.org)**

# Links and Instructions

1st exp : installation

<https://www.guvi.com/blog/guide-for-mongodb-installation-on-windows/>

FONT : TIMES NEW ROMAN

HEADING - 14 UPPER CASE BOLD

CONTENT - 13 NORMAL

SUB HEADINGS - 13 BOLD

LINE SPACING - 1.5

ORDER:

**Heading** (*Upper case, 14, bold*)

**Command Name** (*Font Size: 14, Bold*)

**description** (*Font Size: 13, Regular*)

**Syntax** (*Font Size: 14, Bold*)

**Query** (*Font Size: 14, Bold*) (*Code Formatting, Font Size: 13, Regular*)