```c
//17 flight
#include <stdio.h>
int main()
{
        int con, choice, time;
        con = 1;
        while(con == 1)
        {
                printf("select flight (1 for departure ,2 for arrival)");
                scanf(" %d",&choice);
                while(choice == 1)
                {
                        printf("select departure time\n 1.08:00 AM\n 2.09:43 AM\n 3.11:19 AM\n 4.12:47 PM\n 5.02:00 PM\n 6.03:45 PM \n");
                        scanf("%d",&time);

                                while (time == 1 )
                                {
                                        printf("Arrival Time is 10:16 AM \n");
                                        break;
                                }
                                while (time == 2 )
                                {
                                        printf("Arrival Time is 11:52 AM \n");
                                        break;
                                }
                                while (time == 3 )
                                {
                                        printf("Arrival Time is 01:31 PM \n");
                                        break;
                                }
                                while (time == 4 )
                                {
                                        printf("Arrival Time is 03:00 PM \n");
                                        break;
                                }
                                while (time == 5 )
                                {
                                        printf("Arrival Time is 04:08 PM \n");
                                        break;
                                }
                                while (time == 6 )
                                {
                                        printf("Arrival Time is 05:55 AM \n");
                                        break;
                                }
                                while(time < 1 || time > 6 )
                                {
                                        printf("wrong input\n");
```

```c
                                        break;
                                }
                        break;
                }
                while(choice == 2)
                {

                        printf("Select Arrival Time\n 1.10:16 AM\n 2.11:52 AM\n 3.01:31 PM\n 4.03:00 PM\n 5.04:08
PM\n 6.05:55 PM \n");
                        scanf("%d",&time);

                                while (time == 1 )
                                {
                                        printf("Departure Time is 08:00 AM \n");
                                        break;
                                }
                                while (time == 2 )
                                {
                                        printf("Departure Time is 09:43 AM \n");
                                        break;
                                }
                                while (time == 3 )
                                {
                                        printf("Departure Time is 11:19 PM \n");
                                        break;
                                }
                                while (time == 4 )
                                {
                                        printf("Departure Time is 12:47 PM \n");
                                        break;
                                }
                                while (time == 5 )
                                {
                                        printf("Departure Time is 02:00 PM \n");
                                        break;
                                }
                                while (time == 6 )
                                {
                                        printf("Departure Time is 03:45 AM \n");
                                        break;
                                }
                                while(time < 1 || time > 6 )
                                {
                                        printf("wrong input\n");
                                        break;
                                }
                        break;
                }
```

```c
            printf("continues ? (1 for continues) : ");
            scanf("%d", &con);
        }
}
```