CSE301 – Computer Organization

Lab 3: Memory Layout - Functions

Memory Layout in MIPS

- Text Segment → where instructions live (code section).
- Static Data Segment → contains .data and .bss:
  - .data → initialized variables (x: .word 5)
- Heap → for dynamically allocated memory (malloc, etc.).
- Stack → used for function calls, local variables, and saved registers.
  - Stack grows down (toward lower addresses).



Figure 1: Memory Layout

Accessing Memory: Load and Store Instructions

Load instructions

Instruction	Meaning	Example
`lb`	Load Byte (8 bits)	`lb $t0, 0($a0)`
`lh`	Load Halfword (16 bits)	`lh $t0, 2($a1)`
`lw`	Load Word (32 bits)	`lw $t0, 0($sp)`

Store instructions

Instruction	Meaning	Example
`sb`	Store Byte	`sb $t2, 0($a0)`
`sh`	Store Halfword	`sh $t3, 2($a1)`
`sw`	Store Word	`sw $t1, 0($sp)`

The Static/Data Segment

Used to store global, static, constants values or any data you write in compile time

```
.data

var1: .word 7
var2: .word 15
var3: .word 8

str1: .asciiz "hello world"
```

The Stack Segment

Used to store function data

- Save `$ra` (return address)
- Save any registers it modifies (`$s` registers)
- Allocate space for local variables

To allocate stack:

```
addi $sp, $sp, -8            # allocate two words
```



Figure 2: Allocate Stack

To deallocate stack:

```
addi $sp, $sp, 8
```

Exercise
Trace what is inside each register in the code while executing this program:

initially
$t0 = 7, $s0 = 15, $s1 = 8

```
    addi    $sp, $sp, -8

    sw      $s0, 0($sp)
    sw      $s1, 4($sp)
    lw      $t1, 0($sp)

    add     $t2, $t0, $t1
    addi    $sp, $sp, -4

    sw      $t2, 0($sp)

    add     $s0, $t1, $t2
    sub     $s1, $t2, $s1

    sw      $s1, 4($sp)

    addi    $sp, $sp, 12
```

Execution Table

Step	Instruction	$sp	$t0	$t1	$t2	$s0	$s1	Stack (from low → high)
Init	—	1000	7	—	—	15	8	—
1	`addi $sp, $sp, -12`	988	7	—	—	15	8	allocate 3 words
2	`sw $s0, 0($sp)`	988	7	—	—	15	8	[988]=15
3	`sw $s1, 4($sp)`	988	7	—	—	15	8	[992]=8
4	`lw $t1, 0($sp)`	988	7	15	—	15	8	—
5	`add $t2, $t0, $t1`	988	7	15	22	15	8	—
6	`sw $t2, 8($sp)`	988	7	15	22	15	8	[996]=22
7	`add $s0, $t1, $t2`	988	7	15	22	37	8	—
8	`sub $s1, $t2, $s1`	988	7	15	22	37	14	—
9	`sw $s1, 4($sp)`	988	7	15	22	37	14	[992]=14
10	`addi $sp, $sp, 12`	1000	7	15	22	37	14	stack restored

Functions

Function Call

1. Caller Save registers if needed
2. arguments are passed over $a0 - $a3 or Stack
3. `jal <function label>`
    - PC ← address of function
    - $ra ← address to return after return from function
4. Callee execute
5. return values are placed in $v0 - $v1 or Stack or ...

Function Create

```
<function-name>:
    addi $sp, $sp, -4
```

```
    sw   $ra, 0($sp)

    # function body
    # code to execute

    lw   $ra, 0($sp)
    addi $sp, $sp, 4

    jr $ra
```

Caller Save vs. Callee Save Convention

The Problem

When one function calls another, both functions use registers.
If both just freely overwrite registers, values will be lost — so MIPS defines rules for who is responsible for saving which registers.

Term	Meaning
Caller-save	The **calling function** must save a register *before calling* another function if it wants to preserve its value.
Callee-save	The **called function** must save and restore a register if it changes it.

Register	Name	Saved by	Purpose
`$a0–$a3`	Argument registers	Caller	Function arguments
`$v0–$v1`	Value registers	Caller	Return values
`$t0–$t9`	Temporary registers	**Caller-save**	Temporaries; caller must save if needed
`$ra`	Return address	Caller (in nested calls)	Return location
`$s0–$s7`	Saved registers	**Callee-save**	Must be restored by callee before return
`$sp`	Stack pointer	Callee	Must be restored before returning
`$fp` / `$s8`	Frame pointer	Callee	If used, must be preserved

Lab Exercise 1: Add two numbers

Write a MIPS assembly program that creates a function that add two numbers

Lab Exercise 2: Factorial

Write a MIPS assembly program that creates a function that return the factorial of a number n

Lab Exercise 3: Recursive Factorial

Edit the previous code to make the function recursive.

Task:

Task 1: Write a MIPS assembly program that creates a function to calculate fibonacci for a number entered by the user

Task 2: Edit the previous code to make the function recursive.

Task 3: Complete the given MIPS program to correctly save and restore registers according to the MIPS calling convention.

Note: You can find any required starter file for these tasks in the starterFiles/ directory.