Index

Note: Page numbers followed by f indicate figures; those followed by t indicate tables.

A

A (mass number), 13
Absolute activity, assay of, 177
Absolute quantification of PET, 339-340
Absolute spatial linearity, of gamma cameras, 229-230
Absorbed dose, 407, 432-435, 433t. *See also* Radiation dose.
  air kerma and, 428-430, 434
  average, 408, 414, 417, 428, 429t
  radiation safety and, 427, 428, 429-430, 435
  scaling factor for, 430, 430f
  units for, 431-432
Absorbed dose constant, equilibrium, 412-413
Absorbed fraction, 413-414, 414f, 415t
  specific absorbed fraction, 414-415
Absorbed fraction (MIRD) method, 407. *See also* Radiation dosimetry, internal.
  absorbed fraction and, 413-414
  anatomic models for, 409, 414, 414f, 415t, 424
  cumulated activity and, 409-410, 424
  dose reciprocity theorem and, 415
  effective dose and, 417
  equilibrium absorbed dose constant and, 412-413
  limitations of, 424-425
  mean dose per cumulated activity and, 415-416
  specific absorbed fraction and, 414-415
  steps in, 408-409
  surface dose and, 409
  time-activity curves and, 409-410, 410f-411f
  tissue weighting factors for, 417, 425t
  whole-body dose and, 417, 425t
Absorbers. *See also* Attenuation.
  atomic number of, 75, 79, 81f
  buildup factors for, 83, 84t
  charged particle interactions in. *See* Charged particles.
  density of, 71, 72, 73, 73f, 75, 78-79
Absorbers *(Continued)*
  photon attenuation in, 78-85
    broad-beam, 79-80, 81f, 83, 84t
    coefficients for, 78-79
    narrow-beam, 79-83, 81f, 82t
    with polyenergetic sources, 84-85
  radiation dose in, 407
  thickness of. *See also* Range of charged particles.
    attenuation and, 78-85. *See also* Attenuation.
    detection efficiency and, 160-162, 166f
    half-value, 82, 82t
    range and, 70-74. *See also* Range of charged particles.
    tenth-value, 82, 82t
  transmission factors for, 83
Absorption, detection efficiency and, 166, 173-175, 174f
Absorption edges, 79, 80f
Absorptive collimation, 201, 220, 312-321, 322
  electronic collimation vs., 308
Accelerators, charged-particle, 47-50, 48f-50f, 50t
Accidental coincidences. *See* Random coincidences.
ACD. *See* Annihilation coincidence detection (ACD).
ACF. *See* Attenuation correction factor (ACF).
Acquisition modes, 322, 329, 332-333, 334, 369
Activation cross section, 53-54, 54f
Activation rates, 54-56
Activation thresholds, 50t, 54
Active transport, 389
Activity, 31-32
  absolute, assay of, 177
  cumulated. *See* Cumulated activity.
  decay constant and, 31
  definition of, 31-32
  equivalent, 177
  measurement of
    with dose calibrator, 89, 89f, 189-190
    with NaI(Tl) well counter, 177
  of mixed samples, 38-39, 39f
Activity *(Continued)*
  of mixture
    parent-daughter, 39-42, 39f, 40f, 41f, 42f
    of unrelated species, 38-39, 39f
  product, buildup and decay of, 56
  specific, 37-38
    carrier-free, 37-38
    in nuclear medicine, 38, 56
    product, 56
    of radionuclides, 57-58
    of radiopharmaceuticals, 59
    saturation level of, 56
  typical amounts of, 32
  units of, 31-32
    for cumulated activity, 409
  in voxel, 285, 339-340, 364, 367
ADCs. *See* Analog-to-digital converters (ADCs).
AES. *See* Automatic external standardization (AES) method.
Agreement states, 431
Air kerma, 89, 428-431, 429t
Airborne radioactive materials, 432, 432t, 438
ALARA concept, 433-434, 437-438, 439
Albumin, radiolabeled, 393, 394
Aliasing, 263, 273, 484-485, 485f, 487
α (e/γ conversion ratio), 24
Alpha (α) particles. *See also* Charged particles.
  acceleration of, in cyclotron, 47
  Cerenkov effect and, 68-70
  decay of, 26-28
  detection of, with survey meter, 440
  emission of, 12, 15, 26, 27, 28
  energy losses by, 63-65. *See also* Energy losses.
  equivalent dose of, 408t
  interactions with matter, 63-70
    Cerenkov effect in, 68-70
    energy losses in, 66, 70
    ranges in, 70-71, 82-83, 83t
    specific ionization in, 68, 69f, 71
    tracks in, 66, 67, 67f, 68, 70
  range of, 65, 70, 70f, 72f-73f, 82t

Alpha (α) particles *(Continued)*
shielding of, 71
tracks of, 66-67, 67f
energy deposition along, 67-68
length of, 70, 70f, 72f-73f
Alumina, in ^{99}Mo-^{99m}Tc generators, 51, 51f, 53
Aluminum ion in ^{99m}Tc, 53
Alzheimer's disease, FDG-PET in, 341-342, 342f
Amplification factor, gas
in Geiger-Müller counters, 92-93, 94f
in proportional counter, 91, 92f
Amplifiers, 110-113, 110f, 111f, 114f
baseline shift in, 112-113, 112f
bipolar output of, 113
dead time and, 168
in nuclear instrument module, 122-123
pulse pileup in, 112-113, 112f
pulse shaping by, 110-113, 110f
in rate meter, 120-121
resistor-capacitor, 110f, 111-112, 112f
Analog buffers, 213-214
Analog radiopharmaceuticals, 60, 61, 382
Analog rate meters, 120-121, 120f
Analog signals, digitization of, 363, 364, 365f
Analog tracers, 382
Analog-to-digital converters (ADCs), 116-118, 116f, 120, 124, 363
of gamma camera, 196-197, 196f, 198, 365f
Anatomic models for radiation dosimetry, 409, 414, 414f, 415t, 424. *See also* Phantoms.
Anger, Hal, 2, 4f, 95-196
Anger cameras. *See* Gamma cameras.
Angular sampling intervals, 263-265, 266, 266f, 301
Angular sampling range, 266, 266f
in SPECT, 281, 301
Annihilation coincidence detection (ACD), 307-308. *See also* Positron emission tomography (PET).
basic principles of, 307-308, 308f, 309f
coincidence unit in, 121-122, 121f
counting rates in, 321
effective positron range and, 313, 313f
electronic collimation and, 308
energy resolution in, 150
event types in
prompt coincidences, 322-324, 322f, 340
random coincidences, 322-332, 322f
corrections for, 336-337
estimation of, 336, 340
Annihilation coincidence detection (ACD) *(Continued)*
scatter coincidences, 322f, 323-324, 329-330
true coincidences, 322-324, 322f
geometric efficiency for, 319-322
noncolinearity in, 314, 315f, 316
root mean square effective range and, 314
scintillators for, 309-310
sensitivity in, 308, 312, 319-320, 321, 322
spatial resolution in
depth-of-interaction effect in, 316-318, 317f
detectors and, 310, 311f, 312
with gamma cameras, 209-211, 210f, 211f
geometric efficiency and, 319-321
with PET scanner, 323
positron physics and, 312-316, 313f-315f, 313t
reconstruction filters and, 319
sampling and, 318-319, 318f
system resolution in, 314-315
in time-of-flight PET, 309-310, 310f
time-to-amplitude converter in, 118, 118f
Annihilation photons, 25, 25f
after pair production, 77, 77f
in annihilation coincidence detection, 307-308, 308f-309f
interactions with matter, 74-78
in radiation detectors, 142, 144, 145-146, 145f, 149, 150, 151, 159
shielding for, 437
Annihilation reaction, 25, 25f
Anode
in cathode ray tubes, 123, 123f
in ionization detectors, 87, 88f
in photomultiplier tubes, 98-99, 98f
Anthracene, 188
Anticoincidence circuits, 113, 114f
Antineutrino, 20
Application-specific integrated circuits (ASICs), 363
Archival systems for digital images, 378
Arithmetic mean in conjugate counting, 287-293, 289f
Artifacts
aliasing, 263
barrel, 216-217, 216f
from breath-holding, 359
from contrast agents, artifacts from, 359-360
in CT-based attenuation correction, 358-360, 359f
from dental implants, 360
Artifacts *(Continued)*
motion, 234, 266, 359
attenuation correction artifacts and, 359
breath-holding and, 359
image quality and, 234, 266, 359
pincushion, 199-200, 215f-216f, 216-217
in SPECT, 302
structured noise from, 243
truncation, 359, 359f
Atomic emissions, 10-13, 11f-12f
from radionuclides, 57, 58t
Atomic mass, isotope effect and, 20
Atomic mass unit, 7
Atomic number (Z), 9, 13-14
binding energy and, 10
collisional losses and, 64-65
definition of, 9, 13
effective, 65, 101t, 103-104
fluorescent yield and, 12, 13f
of naturally occurring elements, 445-447
photon attenuation and, 78-79, 81f
radiation losses and, 64-65
of scintillators, 101t, 102, 103-104
Atomic physics, basic concepts of, 7-18
Atomic weight, 13
Atoms, 9-13, 10f, 11f
binding energy of, 15
Bohr, 9, 10f
characteristic x rays of. *See* Characteristic x rays.
composition and structure of, 9
notation for, 12-15
nuclear, 9
nucleus of. *See* Nucleus.
Attenuation, 78-85, 160-162. *See also* Absorbers.
broad-beam, 79-80, 81f, 83, 84t
coefficients for, 78-79
conjugate counting and, 287-291, 287f, 288f, 289f, 290f, 291t, 292f, 292t, 293
contrast-media-related, 359-360
correction factors for, 293-294, 294f
detection efficiency and, 160-164
narrow-beam, 79-83, 81f, 82t
in PET, correction of, 338-339, 338f
in PET/CT and SPECT/CT, correction of, 356-360
artifacts in, 358-360, 359f
image segmentation in, 357
mapping in, 357-358, 358f
of photons, 78-85, 78f, 80f
broad-beam, 79-80, 81f, 83, 84t
coefficients for, 78-79
narrow-beam, 79-83, 81f, 82t
with polyenergetic sources, 84-85
quality assurance and, 302
scattering and, 286, 294f, 302
in SPECT, 287-293, 291t-292t

Attenuation *(Continued)*
conjugate counting and, 287
correction of, 293-294
Chang multiplicative method for, 294, 294f, 296, 297f
scatter correction and, 296-299, 298f
transmission scans and, 294-296, 295f-297f
transmission scans and, 294-295, 295f, 296f, 297f
in vivo probe measurements and, 192
Attenuation coefficients, 78-79, 78f, 80f, 81f. *See also* Linear attenuation coefficients; Mass attenuation coefficients.
scatter corrections and, in SPECT, 297, 297f
Attenuation correction factor (ACF)
for PET, 338
for SPECT, 293
Attenuation maps
in SPECT, 294-296, 296f, 298-299
in SPECT/CT and PET/CT, 357-358
Audio systems, frequency response curves for, 236-237, 236f
Auger effect, 10-13, 12f
Auger electrons, 10-13, 12f
after electron capture, 24
after internal conversion, 23
after ionization, 63
after photoelectron ejection, 74, 78t
photoelectric effect and, 74
Automatic external standardization (AES) method, 186-187, 187f
Autoradiography, deoxyglucose method and, 401
Avalanche ionization
in Geiger-Müller counters, 92-93, 94f
in ionization chambers, 91, 92f
in proportional counters, 91, 92f
Avalanche photodiode detectors, 99-100, 332
Average absorbed dose, 408, 414, 417, 424, 428, 429t
Average lifetime, 34, 82
cumulated activity and, 410, 411f
Average range for electrons, 73
Averaging, effects of, 130
Axial deviation of detector heads, 303
Axial resolution, 301

B

Background counting rates, 131
contrast and, 239-240
daily measurement of, 172
detectability and, 240
image noise and, 240
of liquid scintillation counter, 184
Background counting rates *(Continued)*
of NaI(Tl) conventional detector, 190
of NaI(Tl) well counter, 173, 174, 177-178, 180, 181
pulse-height analysis and, 132, 184-185
random coincidences causing, 336
scattered radiation and, 240-241, 241f
of semiconductor detector, 190
sources of, 240-242
statistics of, 131, 132-133
Background information density, 244
Background radiation
effective dose from, 427
sources of, 177-178, 427
Background subtraction, 242-243
Backprojection. *See also* Reconstruction tomography.
definition of, 257
filtered. *See* Filtered backprojection (FBP).
simple, 256-258, 266f
in SPECT, 294, 296
Backscatter peak, 143f, 144, 151
Backscattered photons, 75, 166-167, 167f
Backscattering, 75
detection efficiency and, 163, 167, 167f
Badge dosimeters, 440-441, 440f
BaF_2, 102-103, 310, 322t
Bar phantoms, 235, 235f
modular transfer functions and, 237-238
Barn, 53-54
Barrel distortion, 216-217, 216f
Baseline restoration, 112-113
Baseline shift, 112-113, 112f
dead time losses and, 168
in gamma camera, 220
in pulse-height spectrometry, 146, 147
Bateman equations, 39-40, 39f
Beam hardening, 84
Becquerel (Bq), 31
Becquerel, Henry, 2, 9
Becquerels per gram, 37
β^+ decay, 25-26, 26f
β^- decay, 20-21
inverse, 24-25
(β^+, EC) decay, competitive, 26
β^+ emission. *See* Positron (β^+, γ) emission; Positron (β^+) emission; Positrons.
β^- emission, 20-21, 20f, 21f
in decay series, 21-22, 22f
by fission products, 44, 45
by neutron-activated radionuclides, 46
β^- emitters
in cancer therapy, 61
detection and measurement of, 21
with gas flow counter, 183
with LS system, 183, 183t
problems in, 166-167, 167f
shielding of, 65, 66f
(β^+, γ) decay, 25-26
(β^-, γ) decay, 21-22, 22f
(β^-, γ) emission, 21-22, 22f
in medical applications, 46t, 57
metastable nuclide vs., 24
Beta (β) particles, 20-21. *See also* Charged particles; Electrons.
backscattering of, 166-167, 167f
Cerenkov effect and, 68-70
detection and measurement of, 21
with Bremsstrahlung counting, 168
with Geiger-Müller counters, 166-167, 167f
problems in, 166-168
with proportional counters, 166-167, 167f
with survey meters, 166-167, 166f
energy losses by, 63-65. *See also* Energy losses.
energy spectrum for, 21, 21f
interactions with matter, 63-70
Cerenkov effect and, 68-70
radiation losses in, 64-65, 67f
range of, 71-72, 72f, 73t
self-absorption of, 166-167, 167f
tracks of, 66-67, 67f
energy deposition along, 67-68
length of, 71, 73t
Beta-particle emitters, ranges for, 73, 73t
Beta-particle probes, miniature, 194
BGO. *See* Bismuth germanate (BGO).
Binary numbers, 364-365
Binding affinity, 403
Binding energy
of atoms, 15
of electrons, 9-10, 11f
photoelectric effect and, 74
nuclear, 15-16
nuclide stability and, 17-18, 17f
Binding potential, 402-403
Biologic excretion curve, 410-412
Biologic half-life, 59
Bipolar pulse, 112, 115
Bis-MSB [*p*-bis-(omethylstyryl) benzene], 105, 187
Bismuth germanate (BGO), 101t, 102-103
detection efficiency of, 161, 161f, 162
mass attenuation coefficients of, 477-478
in PET systems, 316, 324, 324f, 325, 325f, 328, 328f, 334
energy resolution and, 337
sensitivity and, 321, 322t
Bits, 364-365
Bladder, surface dose to, 409
Blank scans, 338
Block detectors, 324-325, 325f, 327f
modified, 325-326, 326f-327f

Blood flow
measurement of
area-height method for, 396, 396f
central volume principle and, 380, 394
clearance methods for, 394-396, 396f
diffusible tracers for, 394-395
equilibrium methods for, 393
Kety-Schmidt method for, 395
labeled microsphere technique for, 393-394
modeling for, 383, 386-388, 388f
nondiffusible tracers for, 394
reference sample technique for, 393-394
tracers for, 380, 381, 381t, 383-384, 386, 387-388, 390f, 393-396
labeled ammonia as, 341-342, 479
trapping methods for, 393-394
tracer delivery and, 387
Blood samples, counting systems for, 105, 173, 182
Blood volume, tracers for, 381t, 383
Blumgart, H.L., 2
Blunders, 125
Blurring. *See also* Artifacts; Image quality; Spatial resolution.
convolution and, 489, 491, 492
motion, 234, 266
attenuation correction artifacts and, 359
breath-holding and, 359
image quality and, 234, 266, 359
noncolinearity, 314, 315f, 316
1/r blurring, 258, 260-261
spectral, 144, 148-151. *See also* Energy resolution.
Blurring tomography, 257
Bohr atom, 9, 10f
Bone
attenuation by, 287, 294, 338
energy absorption in, 430
f factor for, 430, 430f
positron ranges in, 314
Bone marrow. *See also* Organs.
absorbed fraction in, 413
Bone scan, 1, 5t, 60t, 197, 207f
Bq (becquerel), 31
Bragg ionization peak, 68, 69f
Brain
blood flow in
imaging of, 323, 330, 330f, 375-376, 377f, 394, 395
during visual stimulation, 371-372, 372f
tracer measurements of, 394-395
receptor studies of, 304-305, 380, 381t, 402, 403
Brain imaging
co-registration of images in, 375-376, 377f
Brain imaging *(Continued)*
with gamma camera, 4f
parametric, for glucose metabolism, 400, 401f
with PET, 330-331, 330f
3-D acquisition in, 332, 333f, 334
FDG for, 342, 342f, 397-398, 398f, 400, 401f
perfusion studies in, 388, 394
random coincidences in, 323
resolution of, 330-331, 330f
scatter in, 323, 332, 338
systems for, 330, 330f
time-activity curves and, 373, 374f
during visual stimulation, 371, 372f
region of interest in, 372, 372f
with SPECT, 280-281, 282f, 304-305, 304f
attenuation corrections in, 294
in cerebral perfusion studies, 304-305, 304f
perfusion studies in, 304-305, 304f
systems for, 301, 302-303
Brain phantom
image contrast in, 240, 241f
motion blurring in, 234, 234f
Branching decay, 27-28, 31
Branching ratio, 31, 40
Breast imaging
gamma camera for, 207, 208f
PET systems for, 330-331, 331f
sentinel-node, gamma-ray probes for, 192-193
Bremsstrahlung, 64, 64f-66f
charged-particle tracks and, 66, 67f, 68
electron transmission curve and, 71
interactions with matter, 74-78
penetrating ability of, 195
radiation losses and, 64, 65, 65f, 66f
shielding and, 65, 67f, 437
in x-ray tubes, 346
Bremsstrahlung counting, of β particles, 168
Broad-beam attenuation coefficient, 297, 297f
Broad-beam geometry, 79-80, 81f, 83, 84t
Broad-scope licenses, 435
Buildup factors, 83, 84t
Bulk flow across capillaries, 389
Byte, 365

C

Cadmium telluride (CdTe) detectors, 89t, 96-97, 158, 164. *See also* Radiation detectors; Semiconductor detectors.
detection efficiency of, 164
energy resolution of, 190, 191
for gamma-ray probes, 193
Cadmium telluride (CdTe) detectors *(Continued)*
for intraoperative probe, 193, 193f
intrinsic efficiency of, 158
Cadmium zinc telluride (CZT) detectors, 89t, 96-97, 151-152, 153f. *See also* Radiation detectors; Semiconductor detectors.
for cardiac SPECT, 281, 283f
detection efficiency of, 164
energy resolution of, 190, 191
for gamma-ray probes, 293
for intraoperative probe, 193-194, 193f
intrinsic efficiency of, 158
mass attenuation coefficients of, 477-478
Calibration
of liquid scintillation counter, 185
of NaI(Tl) detector, 147-148, 148f
of NaI(Tl) well counter, 178
precalibrated radionuclides and, 35
quality assurance procedures for, 172
Calibration factor, 339-340
Calibration sources, 164, 165f, 165t, 166
absolute activity assays and, 177
americium-241 as, 28
detection efficiency and, 164-166, 165f, 165t
mock, 177
Calibrators, dose, 89, 89f, 189-190, 189f
shielding of, 189-190, 189f
Cancer
bone scan of, 5t, 197
coregistered images of, 375
FDG-PET imaging of, 50, 60, 61, 341-342, 341f, 354, 355
gamma-ray probes in, 192-193
PET/CT in, 355-356, 356f
probe systems and, 192-193
radiation exposure and, 427
SPECT in, 305-306
therapy for
dose in, 417, 424
β^- emitters in, 61
Capillary extraction. *See* Extraction.
Carbon-11, 450t
production of, 49
properties of, 58t
Carbon-14, 450. *See also* Liquid scintillation counters (LSCs).
Cardiac ejection fraction
calculation, with ^{99m}Tc-labeled red cells, 392, 392f
Cardiac imaging
with ^{99m}Tc-labeled red cells, 392, 392f
SPECT in, 281-283, 303, 305f, 306

Cardiac output, 393, 394
Cardiac studies
  first-pass
    gamma camera for, 213, 214, 392
    labeled RBCs for, 392, 392f
    PET for, 339
    SPECT system for, 81
  frame rates in, 368
  gated, 234, 303, 304, 304f, 392, 392f
  motion blurring in, 234, 369
  with PET, 339
  short axis views in, 369
  with SPECT, 281-283, 303, 305f, 306
Carrier-free samples, 37-38
  production of, 46
Carrier-free specific activity (CFSA), 37-38, 56
Carrier-mediated diffusion, 389-390, 397
Cassen, Benedict, 2, 3f, 195
Cathode ray tubes (CRTs), 123-124, 123f, 367
  digital image and, 367
  hard copy derived from, 367
Cathodes in ionization detectors, 87, 88f, 99
Cd-109, 165t
C-D studies. *See* Contrast-detail (C-D) studies.
CdTe detectors. *See* Cadmium telluride (CdTe) detectors.
Center of field-of-view (CFOV), 229-230
Center of rotation (COR) in SPECT, 302-303
Central processing units (CPUs), 363
Central volume principle, 380, 394
  Kety-Schmidt method and, 395
CERASPECT system, 280-281, 282f
Cerebral imaging
  image co-registration and, 375-376
  parametric, for glucose metabolism, 400, 401f
  PET in, 330-331, 330f
  SPECT in, 280-281, 282f, 304-305, 304f
Cerenkov counting, 188
Cerenkov effect, 68-70
Cesium-137, 165t, 473
Cesium antimony (CsSb), 98
Cesium fluoride (CsF), 102-103
Cesium iodide [CsI(Tl)], 100, 101t
  in compact gamma camera, 207
  in intraoperative gamma probe, 193, 193f
Cesium iodide [CsI(Tl)] detectors, 101t
  for cardiac SPECT, 281, 296-299
  in gamma-ray probes, 193
CFOV. *See* Center of field-of-view (CFOV).
CFSA. *See* Carrier-free specific activity (CFSA).
Chain reaction, nuclear, 43
Chang multiplicative method, 294, 294f, 296, 297f
Channels of multichannel analyzer, 116-118, 116f
Characteristic x rays, 10-13, 11f, 12t
  after electron capture, 24-25
  after internal conversion, 23
  after ionization, 63
  after photoelectron ejection, 74
  in radiation detector, 151
Charged particles. *See also* Alpha particles; Beta particles; Electrons; Positrons.
  Cerenkov effect and, 68-70
  definition of, 63
  energy losses and, 63-66, 67, 67f, 68, 70. *See also* Energy losses.
  interactions with matter, 63-68, 64f, 65f, 66f, 67f, 69f, 70
  ranges of, 70-74, 70f, 72f-73f, 73t
    ACD and, 312-314, 313f, 314f
    detector types and, 141
  tracks of, 66-68, 67f
    energy deposition along, 67-68, 67f
    length of, 70-74, 70f, 72f-73f, 73t
Charged-particle accelerators, 47-50, 48f-50f, 50t
Charge-sensitive preamplifiers, 107-108, 109f
Chelation, 58
Chemical elements, 9. *See also* Nuclides.
  properties of, 445
  transmutation of, 20, 21, 24, 25, 27
Chemical properties, radioactive decay and, 19-20
Chemical purity, 59
Chemical quenching, 106, 188
Chi square test, 133-134, 134f
  in quality assurance, 172
Chromatography
  liquid scintillation counting with, 188
  NaI(Tl) detector with, 182, 183f
Chromium-51, 452
Ci. *See* Curie (Ci).
Cine mode, 371
Classic method in internal radiation dosimetry, 407
Clearance, tracer, 388
Clearance methods for blood flow measurement, 394-396, 396f
Cloud chambers, 66
CNR. *See* Contrast-to-noise ratio (CNR).
Cobalt-57, 165t
Cobalt-60, 165t
Cocktails, liquid scintillation, 105, 187
Code of Federal Regulations, 431
Coherent scattering, 77
  in SPECT, 297
Coincidence circuits, 184
Coincidence counting rates, 162-163, 322-324, 322f, 329-330
  in PET, 322-324, 322f, 329-330
  random, 322-323, 322f, 329-330
    correction for, 336-337
    estimation of, 336, 340
  scatter, 322-324, 322f, 329-330
    correction for, 337-338
  true, 322-323, 322f
  uncertainty in, 336, 337
Coincidence detection. *See also* Annihilation coincidence detection (ACD).
  of cascaded emissions, 162-163
  efficiency of, 162-163
  for liquid scintillation counters, 183f, 184
  spatial resolution for, 310, 311f-312f
Coincidence rate, 319
Coincidence summing, 145, 146f
Coincidence timing windows, 121, 307
  definition of, 121
  in PET systems, 307, 322, 323, 329, 337
Coincidence units (logic), 121-122, 184
  in PET, 307
Cold lesions, 246, 248, 269
Coldfinger, 97, 97f
Collimation
  absorptive, 201, 220, 312-321, 322
  electronic, 308
Collimator efficiency
  of converging collimators, 225-228, 226f-227f
  definition of, 220, 223
  of diverging collimators, 225-228, 226f-227f
  of parallel-hole collimators, 222, 224f, 225t
  of pinhole collimators, 225-228, 226f-227f
  volume sensitivity and, 301
Collimator resolution. *See also* Spatial resolution.
  of converging collimators, 225-228, 226f-227f
  definition of, 220, 222
  of diverging collimators, 225-228, 226f-227f
  of parallel-hole collimators, 220, 222, 222f, 225t
    system resolution and, 225. *See also* Parallel-hole collimators: collimator resolution and.
  of pinhole collimators, 225-228, 226f
  source-to-collimator distance and, 223, 224f, 227-228, 227f-228f
  system resolution and, 225, 227
Collimators, 196, 196f, 201-203. *See also specific types*.
  absorptive, 201
  cone-beam, 274-275, 274f

Collimators *(Continued)*
converging. *See* Converging collimators.
diverging. *See* Diverging collimators.
fan-beam, 273-274, 274f-275f, 294, 295f, 304f
for gamma cameras. *See* Gamma cameras: collimators for.
multi-pinhole, 202f, 203
parallel-hole. *See* Parallel-hole collimators.
pinhole. *See* Pinhole collimators.
response characteristics of, 254, 254f
sensitivity of, 231
in gamma camera, 223, 224f, 225t, 227, 231
lesion detectability and, 246, 247f
septal thickness in, 203, 203f, 211, 220-221, 220f-221f
slant-hole, 203
Collisional energy losses, 64-65, 66f-67f
rate of, 66-68, 69f
Collisions of charged particles with matter, 63-64, 64f
Colloids, ^{99m}Tc-labeled, 192-193
Color displays, 367, 368f
Color quenching, 106
Combined-modality imaging. *See* Hybrid imaging systems.
Comparators, 113
Compartmental models, 390-392, 390f-391f. *See also* Tracer kinetic modeling: compartments in.
basic concepts of, 380, 382, 384f
for FDG, 396, 397
formulation of, 390-392, 390f, 391f
Renkin-Crone model vs., 389f, 390-391
Competitive (β^+, EC) decay, 26
Compton edge, 143, 143f, 144, 146, 151
Compton region, 143, 143f, 145, 147
Compton scattering, 74-78, 75f-77f, 75t, 78t, 104. *See also* Scattered radiation.
in gamma camera studies
energy resolution and, 209, 211-212
spatial resolution and, 209, 210
intrinsic spatial resolution and, 209-211, 210f-211f
in PET, 322-323, 322f, 329-330
correction for, 337-338
photon attenuation and, 79, 80f-81f
in radiation detectors, 141-143, 142f-143f
gamma-ray energy and, 146-147, 147f
nonlinearity and, 148
scintillator materials and, 102, 103, 104
in SPECT, 296-299
Compton scattering *(Continued)*
in tissue
detection efficiency and, 163-164, 164f
downscatter derived from, 296-297, 297f
probe measurements and, 192
in x-ray CT, 349
Computed tomography (CT), 253. *See also* Hybrid imaging systems; Positron emission tomography (PET); Single photon emission computed tomography (SPECT); X-ray computed tomography.
emission, 253. *See also* Reconstruction tomography; Tomographic imaging.
advantages of, 269-270
image quality in, 263-270
for low-contrast lesions, 269-270
noise in, 266-268
in multimodality instrumentation, 4-5
transmission, 253
Computer networks, 367, 378
Computer observer performance studies, 233
Computers, 363. *See also* Digital image processing; Digital images; Tomographic imaging.
contrast enhancement algorithms of, 242
dead time losses in, 168
in gamma camera SPECT system, 280
in liquid scintillation counting systems, 183f, 184, 189
pixelation effects caused by, 234
in well-counter systems, 178, 181
Concrete shielding, 437
Cone-beam collimators, 274-275, 274f
Cone-beam reconstruction, 273-275, 274f
Confidence intervals, 127, 127t
Conjugate counting, 287-291, 287f, 288f, 289f, 290f, 291t, 292f, 292t, 293
Conjugate variables, 481
Consistency requirements in reconstruction tomography, 266, 266f-267f
Constant fraction timing, 115-116
Contaminants
detection of, by curve stripping, 39
effects of, 58
in ^{99m}Tc, 53, 58
Contrast, 233, 239-240, 243-247
background counting rates and, 239-240
definition of, 233, 239
with gamma camera
energy resolution and, 214
pulse pile-up and, 213, 214, 214f
of hot vs. cold lesions, 246, 248
in image display, 369, 370f
Contrast *(Continued)*
information density and, 243-244
lesion size and, 243-244, 245
modulation transfer function and, 236, 237f
in PET, 241-242, 253, 336, 337, 346
Rose criterion for, 244, 269
scattered radiation and, 240-241, 242f
septal penetration and, 240-241, 242f
spatial resolution and, 243, 246, 247f, 249f
in SPECT, 241-242, 243f, 253
Contrast agents
artifacts from, in PET/CT and SPECT/CT attenuation correction, 359-360
for x-ray CT, 349-350
artifacts from, 359-360
Contrast enhancement, 242-243
Contrast-detail (C-D) studies, 247-249, 248f-249f
Contrast-to-noise ratio (CNR), 243-247. *See also* Noise.
in reconstruction tomography, 266-268
in tomographic imaging, 253, 266, 269-270
Control rods, 43-44
Converging collimators, 204, 204f
advantages and limitations of, 228
efficiency of, 225-228, 226f-227f
performance characteristics of, 225-228, 226f-227f
resolution of, 225-228, 226f-227f
source-to-collimator distance and, 228, 228f
in SPECT, 279-280
Conversion electrons, 22-24, 23f
Converter for proportional counter, 159
Convolution, 489-492, 490f, 491f, 492f
backprojection and, 258
smoothing filter and, 373
Convolution theorem, 492
Copper-62, 454
Copper-64, 455
COR (center of rotation) of SPECT system. *See* Center of rotation (COR) in SPECT.
Co-registration, 375-376, 377f
Coronal sections, orientation of, 369, 370f
Correlation coefficient, 139-140
Cosmic rays, 177-178, 432
Cost function, 271
Coulombic forces, 14
Count skimming, 218
Counter paralysis, 169. *See also* Paralyzable counting systems.
Counters, digital, 119-121, 120f
Counting, energy-selective. *See* Energy-selective counting.
Counting curves for Geiger-Müller counters, 94, 95f

Counting losses in gamma camera, 213-214, 213f, 215f, 230
Counting rates, 130
in annihilation coincidence detection, 321
background, 131
for calibration sources
absolute activity assays and, 177
detection efficiency and, 164
mock sources and, 177
coincidence. *See* Coincidence counting rates.
crosstalk and, 178-179
dead time losses and, 168-171
detection efficiency and, 155
with absorbing medium, 163
with cascaded emissions, 162-163
with full-spectrum counting, 159, 163
with scattering medium, 163
differences between, 130-131
with energy-selective counting, 159
estimation of, 132
of gamma camera, 213-216, 230
with multiple radionuclide sources, 178-179
noise equivalent, 340-341, 341f
observed vs. true, 168-169, 168f-169f
optimal division of, 133
for paralyzable vs. nonparalyzable counting systems, 168-169, 168f-169f
in pulse-height spectrometry, 146, 147f
of SPECT system, 302
statistical significance of, 130-131
total-spectrum, 170
uncertainty in, 130, 131, 132, 133
Counting statistics. *See* Statistical analysis.
Counting systems, 173-194
for Cerenkov counting, 188
comparison of, 132
components of, 107, 108f, 173
dead times of, 168-171
detectors for, 173
conventional NaI(Tl), 182
gas-filled, 189-190
gas-flow counters in, 190
liquid scintillation, 182-189. *See also* Liquid scintillation counters (LSCs).
NaI(Tl) well counters in, 173-182, 174f, 174t. *See also* NaI(Tl) well counters.
paralyzable vs. nonparalyzable, 168-169
probe
miniature beta particle, 194
miniature gamma-ray, 192-194, 193f
NaI(Tl), 192, 192f
quality assurance for, 171-172
semiconductor, 190-192, 191f
in vitro, 173
Counting systems *(Continued)*
in vivo, 173, 192-194
whole-body, 194
Counting time, statistical reliability and, 132-133
Counting vials, 184-185
Count-rate performance in SPECT, 302
Coverage requirements in reconstruction tomography, 266, 266f-267f
CPUs. *See* Central processing units (CPUs).
CR differentiation circuit, 111-112, 111f-112f
Cristy-Eckerman phantoms, 414, 414f, 415t
Cross section
activation, 53-54, 54f
neutron-capture, 45-47, 46t
Cross-plane data acquisition, 332, 333f
Crosstalk
in liquid scintillation counting, 184, 185, 187, 187f
between projection elements, 286
in well-counter measurements, 178, 178f, 179, 181-182
CRTs. *See* Cathode ray tubes (CRTs).
CsF. *See* Cesium fluoride (CsF).
CsI(Tl). *See* Cesium iodide [CsI(Tl)] detectors.
CsSb. *See* Cesium antimony (CsSb).
CT. *See* Computed tomography (CT).
Cumulated activity, 409-412, 410f, 411f
average absorbed dose and, 408, 414, 417, 424
calculation of, 424
mean dose per, 411f, 414f, 415-416, 418t-423t
for ^{18}F, 415-416, 422t-423t
for ^{131}I, 415-416, 420t-421t
for ^{99m}Tc, 415-416, 418t-419t
problems in determination of, 424
in source organ, 409-410, 424
Curie (Ci), 32
Curie, Marie, 2
Curve stripping, 39
Cut-off frequency in PET, 319
Cyclotrons, 47-49, 48f-49f, 50t
negative-ion, 48-49, 49f
principles and design of, 47-49, 48f-49f
radionuclides produced in, 49-50, 50t
in cyclotrons, 47-50, 50t
CZT detectors. *See* Cadmium zinc telluride (CZT) detectors.

D

(d, n) reaction, 47, 50t
Dalton (Da), 8
Dalton, John, 9
Dark adaptation of samples, 185
Daughter nucleus, 19
De Hevesy, Georg, 2
Dead time/dead time losses, 168-171, 168f, 169f, 171f
apparent, 213, 213f, 214
determination of
fixed-rate pulser method for, 171, 171f
two-source method for, 171, 171f
in gamma cameras, 213-214, 213f, 230
correction methods for, 213-214
in Geiger-Müller counters, 188
in liquid scintillation counters, 168
mathematical models of, 168-169
in NaI(Tl) well counters, 179
in paralyzable vs. nonparalyzable systems, 168-169, 168f-169f
percentage, 169
in PET, 326, 330, 332, 339, 340
in SPECT, 302
window fractions and, 170, 213, 213f
Decay. *See* Radioactive decay.
Decay constant, 31, 32
average lifetime and, 34
definition of, 31
half-life and, 33-34
Decay curve, universal, 35, 35f
Decay factors, 32-33, 33f
approximation to, 32, 32f, 33
determination of, 34-35
effective, 35-37, 36f
tables of, 34, 34t
Decay rate. *See* Activity.
Decay scheme diagrams, 20-21, 20f
of important radionuclides, 449, 449f-475f
Decay series, 27-28, 27f
Decay time of scintillators, 101t, 104
Decontamination measures, 439
Deep-dose equivalent, 431-432
Degrees of freedom, 136, 136f, 140
Delayed window method, 336-337
Delay-line methods, 111, 113
Delta (δ) rays, 63, 66, 67f
Density of absorbers
attenuation coefficient and, 78-79
energy losses and, 65
range of alpha particles and, 71
range of electrons and, 72, 73, 73f
range of positrons and, 314
Dental implants, artifacts from, 360
Deoxyglucose method, 397, 400
Depreotide, ^{99m}Tc-labeled, 305
Depth-of-interaction (DOI) effect, 316-318, 317f, 326, 329, 330, 331
Derandomizers, 213-214
Derived quantities, 7

Detectability. *See also* Phantoms.
of cold vs. hot lesions, 246, 248, 248f, 297
contrast-to-noise ratio and, 243-244
in emission computed tomography, 269-270
information density and, 244-245, 246
observer performance studies of, 247, 248, 249f, 250-251, 250f
Rose criterion for, 244, 269
size and, 244, 245, 246, 247
spatial resolution and, 246-247, 247f
Detection efficiency, 155-166
attenuation and, 156, 160-164
calibration sources and, 164-166, 165f, 165t
cascaded gamma emissions and, 162, 163
in coincidence detection, 162-163
complicating factors in, 160-164, 160f, 161f, 164f
components of, 155-156
definition of, 156
edge effects and, 160
emission rates and, 155
energy-selective counting and, 156, 159
factors affecting, 155-156
of gamma camera, 211, 212f
detector thickness and, 211, 212f
nonuniformity and, 217
used for PET, 329-330
of gamma cameras
detector thickness and, 211, 212f
nonuniform, 217
of gas flow counter, 190
geometric, 156, 157f-158f
of absorptive collimators, 321
edge effects on, 160
of gas flow counter, 190
of liquid scintillation counters, 157
of NaI(Tl) detectors, 156, 182
in whole-body counter, 194
of NaI(Tl) well counters, 157, 174, 175
of PET systems, 319-322, 330, 331, 334
of semiconductor detector, 190-191
housing of detector and, 164
intrinsic, 156, 158-159, 159f
calibration and, 164
of coincidence detector, 310, 311f, 312, 315, 319
definition of, 156
of gas-filled detectors, 158-159
of NaI(Tl) detectors, 158-159
nonuniform attenuation and, 160-162, 161f, 162f
of semiconductor detectors, 158
of well-counter detector, 174, 175f
Detection efficiency *(Continued)*
of liquid scintillation counter, 157, 185
of NaI(Tl) conventional detector, 156, 182
of NaI(Tl) well counter, 157, 174, 175, 175f-176f, 179
nonuniform, 160-162, 160f-161f
of PET systems, 324
Compton scattering and, 337
normalization corrections to, 335-336
in phantoms, 166
photofraction and, 159, 160f
photopeak and, 163
radiation absorption and, 156
radiation scatter and, 156, 163-164
scatter outside of detector and, 144, 163-164, 164f
of semiconductor detectors, 151, 158, 164, 190
total, 160-161, 160f
Detector scatter events, 204-205
Detectors. *See* Radiation detectors.
Detergents for LS sample preparation, 187
Deuterons in cyclotron, 47, 48
DF. *See* Decay factors.
DFT. *See* Discrete Fourier transform (DFT).
DICOM. *See* Digital Imaging and Communications in Medicine (DICOM).
Diethylenetriamine penta-acetic acid (DTPA), 5t, 60t, 381t, 479
Differential spatial linearity, 229-230
Differential uniformity, 229-230
Differentiation circuits, 111-112, 111f-112f
Diffusion, carrier-mediated, 389, 390, 395, 397
Diffusion constant, 389
Digital counters, 119-121, 120f
Digital image processing, 363-378. *See also* Digital images.
acquisition modes in, 367-369
frame-mode, 367-368
gated imaging, 245, 369
list-mode, 368-369
archival systems for, 378
binary numbers in, 364-365
computer processors for, 363
definition of, 363
display in
cathode ray tube, 367
hard copy, 367
liquid crystal, 367
edge detection in, 373-375
equipment for, 376-378
file format standards for, 378
for gamma camera images, 364
detector area and, 364, 365f
image arithmetic in, 371
image co-registration in, 375-376, 377f
Digital image processing *(Continued)*
image display in, 367
color, 367, 368f
grayscale, 367, 370f
image segmentation in, 373-375, 377f
in CT-based attenuation correction, 357
image smoothing in, 373, 375f
image visualization in
orientation of sections in, 369, 370f
parametric images and, 372
projection tool for, 369-371, 371f
surface rendering in, 369-371
windowing in, 369, 370f
Laplacian technique in, 373-375
linear sampling distance and, 365-366
matrix size in, 365
microprocessors for, 363
for multislice tomographic images, 364
networks for, 378
overview of, 363
pixel depth in, 365
pixels in, 364, 364f. *See also* Pixels.
regions of interest in, 372-373, 372f
spatial resolution and, 365-367, 366f. *See also* Spatial resolution.
steps in, 376-378
techniques of, 369-376
co-registration in, 375-376, 377f
edge detection in, 373, 375, 376f
image smoothing in, 373, 375f
regions of interest in, 372-373, 372f
segmentation in, 373, 375, 377f
time-activity curves in, 373, 374f
visualization tools in, 369, 370f, 371-372, 371f, 372f
terminology for, 364-365
time-activity curves and, 365, 374f
visualization tools for, 369-372, 370f-372f
volume of interest in, 373
voxels in, 364
Digital images, 364-369. *See also* Image quality.
acquisition modes of, 367-369
archiving of, 378
basic characteristics of, 364-365, 364f, 365f
computer networks for management of, 378
display of
image structure and, 367, 368f
spatial resolution and, 365-367, 366f

Digital images *(Continued)*
technologies for, 119-121, 119f, 120f, 121
visualization tools for, 367, 368f
file formats for, 378
gamma camera and, 197, 364, 365f, 482
hard copy of, 367
parametric, 372
retrieval of, 376, 378
spatial resolution of, 365-367, 366f
terminology of, 364-365, 364f, 365f
Digital Imaging and Communications in Medicine (DICOM), 378
Digital signal processors, 363
Digitization, 117-118, 363
Di-isopropylnaphthalene (DIN), 105, 187
Dilution principle, 382-383
Dilution quenching, 106
DIN. *See* Di-isopropylnaphthalene (DIN).
Direct Fourier transform reconstruction, 258-260, 259f-260f. *See also* Reconstruction tomography.
image quality in, 263-270
sampling in, 263-265
Direct substitution, 59-60
Discrete Fourier transform (DFT), 482
Discriminators, 114, 115f, 118, 121, 121f
of gamma camera, 201, 205
lower-level, 113, 114f
upper-level, 113, 114f
Disintegrations per second (dps), 31
Disposal of radioactive waste, 439
Distribution volume, 382-383, 384f
blood flow measurement and, 393
Diverging collimators, 202f, 203
advantages and limitations of, 228
efficiency of, 225-228, 226f-227f
performance characteristics of, 225-228, 226f-227f
resolution of, 225-228, 226f-227f
source-to-collimator distance and, 228, 228f
DMSA (2,3-dimercaptosuccinic acid), 60t
DOI. *See* Depth-of-interaction (DOI) effect.
DOPA, ^{18}F-Fluoro, 372f, 373, 374f, 381t
Dose. *See* Radiation dose; Radiation dosimetry, internal.
Dose calibrators, 89, 89f, 189-190, 189f
shielding of, 189-190, 189f, 437
Dose equivalent. *See* Effective dose equivalent; Equivalent dose.
Dose limits, 431-432
Dose reciprocity theorem, 415
Dose-equivalent rate, 435
Dose-modifying factors, 428
Dose-rate constant, 434-435, 435t
Dosimeters
badge, 440, 440f
pocket, 89-90, 90f, 440
ring, 440, 440f
Dosimetry, internal radiation. *See* Radiation dosimetry, internal.
Double differential shaping, 112, 112f
Double escape peaks, 144, 145f
Downscatter during transmission scan, 296, 297f
Dps. *See* Disintegrations per second (dps).
DTPA (diethylenetriamine penta-acetic acid), 5t, 60t, 381t, 480
Dynamic imaging, 392-403. *See also* Cardiac studies; Tracer kinetic modeling.
in blood flow measurement, 379-386, 394-396. *See also* Blood flow: measurement of.
in cardiac imaging, 392. *See also* Cardiac imaging.
in enzyme kinetic studies, 396-401
with gamma camera, 197, 206-207, 207f
in glucose metabolism studies, 396-401
with PET, 335
in receptor binding studies, 402
in receptor ligand assays, 401-403, 402f, 404f
with SPECT, 279-278, 284, 286f, 305f, 306
in receptor binding studies, 402
Dynodes, 98-99, 98f

E

EC. *See* Electron capture (EC).
(EC, γ) decay, 24-25
competitive, 26
ECD. *See* Ethyl-cysteine-dimer (ECD).
ECT. *See* Emission computed tomography (ECT).
Edge detection, 373, 375, 376f
Edge effects, 160
Edge packing, 217, 229
Edge sharpness, 237, 260-261
Effective atomic number, 65, 101t, 103-104
Effective decay factors, 35-37, 36f
Effective dose, 417, 425t, 429t
from background radiation, 427
recommended limits for, 434t
Effective dose equivalent, 417, 428, 429t, 432, 434t, 435. *See also* Equivalent dose.
regulatory limits for, 431-432
for selected radiopharmaceuticals, 478-479
Effective half-life, 411-412
Effective positron range, 313, 313f
Efficacy studies, 250-251
Efficiency. *See* Collimator efficiency; Detection efficiency.
e/γ conversion ratio, 24
Ejection fraction, 392, 392f
Electrical forces, 14
Electromagnetic radiation, 8-9, 66. *See also* Gamma rays; Photons; X rays.
Electromagnetic spectrum, 8-9, 8f
Electrometers, 89
in dose calibrators, 89, 89f
in survey meters, 89-91, 89f
Electron capture (EC), 24-25
competitive with positron emission, 27, 27f, 26, 26f
by cyclotron-produced radionuclides, 49, 50t
in (EC, γ) decay, 24-25, 24f
line of stability and, 28
by reactor-produced radionuclides, 49, 46, 46t
Electron gun, 123
Electron multiplication factor, 148-149
Electron shells, 9, 14
Electron volt (eV), 8
Electronic collimation, 308
Electronic instrumentation, 107-124
amplifiers in, 110-113, 110f, 111f, 112f
dead time and, 168, 170
in nuclear instrument module, 122-123
in rate meter, 120
coincidence units in, 121-122, 121f
for PET scanner, 307-308
counters and rate meters in, 119-121, 119f, 120f, 121f
detectors in. *See* Radiation detectors.
display technologies in, 123-124, 123f
high-voltage power supplies in, 122
NIM (modular) systems in, 122-123
preamplifiers in, 107-110, 108t, 109f
of gamma camera, 219
pulse-height analyzers in. *See* Pulse-height analyzers (PHAs).
time-to-amplitude converters in, 118-119, 119f
Electronic noise. *See also* Noise; Signal-to-noise ratio (SNR).
counting uncertainty and, 131
energy resolution and
with scintillation detectors, 148, 149, 150, 150f
with semiconductor detectors, 152, 152f
in liquid scintillation counters, 184, 185, 186
power supply and, 122
pulse shaping and, 110-111, 111f

Electronic noise *(Continued)*
reduction by coincidence detection, 184
spectral blurring and, 148
Electrons. *See also* Beta particles; Charged particles.
annihilation of, after pair production, 78, 78t
Auger, 10-13, 12f, 23, 24, 63, 74, 78t
binding energy of, 9-10, 11f
in Bohr atom, 9, 10f
Cerenkov effect and, 68-70
conversion, 22-24, 23f
decay modes involving, 20-22, 20f, 21f, 22f, 23f
energy losses by, 63-70. *See also* Energy losses.
rate of, 66-68, 69f
energy-level diagram of, 10, 11f
Exclusion Principle for, 9
interactions with matter, 63-70
Cerenkov effect in, 70
energy deposition in, 67-68, 67f, 77-78, 77f, 78t
by photoelectrons, 74, 74f
ranges in, 74, 75
photon MFP vs, 82t
tracks in, 66-67, 67f
mass-energy equivalence and, 8, 16
notation for, 12-13
orbits of, 9, 10f
pair production and, 76-77, 77f. *See also* Pair production.
as particulate radiation, 8
photoelectron as, 74, 74f. *See also* Photoelectric effect.
properties of, 13t
radiation from, 10-13, 11f-12f, 12t
range of, 71-72, 82t
recoil, 74-76, 75f, 75t, 78t, 144
pulse-height spectrum and, 142, 144
in Rutherford atomic model, 9
secondary, 63, 64f, 66, 67f, 78t
in photomultiplier tubes, 98-99, 100f
substates of, 9
tracks of, 66-67, 67f
energy deposition along, 67-68
length of, 70, 70f, 72f-73f
x-ray emission and. *See* Characteristic x rays.
Elements, 9
EM (expectation-maximization) algorithm, 272
Embryo, dose limits for, 432
Emission computed tomography (ECT), 253. *See also* Reconstruction tomography; Tomographic imaging.
advantages of, 269-270
image quality in, 263-270
for low-contrast lesions, 269-270
noise in, 266-268
Emission rates, 155
Emission scans with SPECT, 296
Emissions
cascaded, coincidence detection of, 162-163
inverse-square law and, 156, 157f
isotropic, 156
Emission/transmission scans, simultaneous, in PET attenuation correction, 338-339
Energy
binding
electron, 9-12
nuclear, 15-18, 17f
mass and, 8, 15-16, 19
of photon, 8
transition, 19
units of, 7-8
Energy corrections for gamma camera, 217-218
Energy deposition
by charged particles, 63-66, 67, 67f, 68, 70
dose and. *See* Radiation dose; Radiation dosimetry, internal.
by photons, 64, 77-78, 77f, 78t
in radiation detectors, 91
Energy levels
of electrons, 10, 10f
of nucleus, 13, 13t, 15-16
Energy linearity, 147-148, 148f
calibration for, 147-148, 148f
with well counter, 178
energy resolution and, 148-151
Energy losses, 63-64, 66
collisional vs. radiation, 64-65, 66f-67f
linear energy transfer and, 68
linear stopping power and, 68
rate of, 66-68, 69f
specific ionization and, 68
Energy resolution.
of crystal scintillation detectors, 148-151, 149f, 150f
definition of, 148-149
electronic noise and, 148, 149, 150, 150f
energy linearity and, 147-148
factors affecting, 148-151
of gamma cameras, 150, 201, 211-213, 212f, 231
measurement of, 231
integration time and, 150
of liquid scintillation detectors, 153, 153f
of NaI(Tl) detectors, 148-151
of PET detectors, 337
photoelectron production and, 149-150
of proportional counters, 151, 153
quality assurance and, 172
of semiconductor detectors, 151-152, 152f, 190-192, 191f, 240
in SPECT, 302
spectral blurring and, 144, 148-151
statistical variations and, 148-150
Energy response curve for survey meters, 90-91, 91f
Energy spectrometry. *See* Pulse-height spectrometry.
Energy window
of gamma camera, 212, 212f, 213, 218, 218f
for PET, 336, 337
image contrast and, 240, 241f
with NaI(Tl) detectors, 240
volume sensitivity and, 301-302
Energy-mass conversion in radioactive decay, 19
Energy-selective counting, 156, 159, 160f
cascaded gamma emissions in, 164
detection efficiency and, 156, 159
in gamma camera, 200, 201f
scattering medium in, 163
window fraction effect in, 170-171
Energy-sensitive detectors, 107, 108, 109, 111, 113. *See also* Proportional counters; Scintillation detectors; Semiconductor detectors.
Entrance windows, 98, 98f, 101-102, 104
thickness of, 166-167
Enzyme kinetics, 396-401
in carrier-mediated diffusion, 390
glucose metabolism and, 396-401, 397f, 398f, 401f
Michaelis-Menten hypothesis and, 396-397, 397f
Enzyme-substrate complex, 385, 385f, 397
Equilibrium absorbed dose constant, 412-413
Equilibrium dissociation constant, 401
Equilibrium methods for blood flow measurement, 393
Equilibrium models, 386
Equivalent dose, 407-408, 429t. *See also* Effective dose equivalent.
air kerma and, 435-436
distance from source and, 435-436
dose-equivalent rate and, 435
recommended limits for, 431-432, 434t
units of, 407-408, 428
Error. *See also* Statistical analysis.
propagation of, 128-130
types of, 125-126
Escape peaks, 144, 145f
iodine, 144, 144f
Ethyl-cysteine-dimer (ECD), 5t, 60t, 304
Euler's equation, 482
eV. *See* Electron volt (eV).
Event detection in gamma cameras, 204-206, 205f
Exchange forces, 14-15

Excitation, 63-64, 87
by charged particles, 63, 64, 64f
after photon interactions, 78
in radiation detection, 87
by Geiger-Müller counter, 92
by organic scintillator, 105
Excited states
See Excitation.
nuclear, 14, 15
in (β^-, γ) decay, 21, 22, 22f
in in (β+, γ) decay, 25
in (EC, γ) decay, 24
Exclusion Principle, 9
Excretion
of accidentally ingested radioactive material, 437
cumulated activity and, 409, 410, 411, 411f, 412
Expectation-maximization reconstruction, 272-273
Exponential decay, 32-34, 32f-33f
Exponential functions, properties of, 33, 34, 35
Exposure, radiation, 428-431, 429t
air kerma and, 428-431, 429t, 438-439
definition of, 429-430
minimizing duration of, 436
TDS rules and, 436
units of, 428-431, 429t
Exposure rate, 89, 428-431
External beam radiation, 48
Extraction, 386-388, 387f, 388f, 389f, 390-391, 390f
Extraction coefficient, 388
Extrapolated range, 71-74, 72f-73f
of electrons, 71-73, 72f, 73f, 74
of positrons, 312-314
Extrinsic uniformity for gamma cameras, 229-230

F

f factor, 430, 430f
False-positive fraction (FPF), 249, 250f
Families, nuclear, 14, 14f
Fan-beam collimators, 273-274, 274f-275f, 294, 295f, 304f
Fan-beam projections in PET, 320f, 321
Fan-beam reconstruction, 273-276, 274f-275f
Fast Fourier transform (FFT), 482, 485
FBP. *See* Filtered backprojection (FBP).
FDG. *See* Fluorodeoxyglucose (FDG).
FDG model for glucose metabolism, 397-401, 398f
FDG-PET, 341-342, 342f
with CT, 355-356, 356f
with MRI, 360-361, 361f
Feldkamp algorithm, 275
Fetus, dose limits for, 432, 433, 434t
18F-2-fluoro-2-deoxy-D-glucose. *See* Fluorodeoxyglucose (FDG).
FFT. *See* Fast Fourier transform (FFT).
Fick principle, 387, 395
Field-effect transistors, 109
Field-of-view (FOV)
Fourier transform and, 482, 483, 483f, 487
image quality and, 262, 263, 265, 266
in PET, 318, 319, 321, 323, 329, 335
axial, 326, 328, 332, 335
with gamma camera, 332
with three-D acquisition, 332, 334
pixel size and, 364, 365
in SPECT, 279, 280, 281
for performance measurements, 301, 302
for transmission scan, 295
useful, 217, 229, 230, 231
in PET, 319, 321
File format standards, 378
Film
analog images on, 364
spatial resolution on, 233-234
transparency, hard-copy images on, 367
Film badge, 440
Filtered backprojection (FBP), 260-262, 260f, 261f, 262f. *See also* Reconstruction tomography.
attenuation correction to, 293
for fan-beam data, 274
image quality in, 263, 264f, 265-270, 265f, 266f, 267f
iterative reconstruction vs., 270-271
limitations of, 262
noise in, 260-261, 263, 264f, 293f
for PET data, 332
sampling in, 263-265
simple backprojection vs., 260-261
steps in, 260, 261f
Filters
reconstruction, 260-261, 263, 264f
Hann, 261, 262f
in PET, 319
ramp, 260-261, 261f-262f
in SPECT, 301
Shepp-Logan, 261, 262f, 263-265, 264f
smoothing, 373
First-order kinetics, 384, 390
First-order rate constants, 384-385, 385f
Fission
radioactive decay by, 28
radionuclide production by, 43-47
in reactors, 43-44
Fission fragments, 28, 44-45, 45f
Fission moly generators, 53
Fission neutrons, 28, 43, 53
Flat-panel display, 124
Floating point numbers, 365
Flood source, 294, 295f
Flood-field images, 216f, 217
from block detector, 324, 325f
checks of, 229, 230
Flood-field images *(Continued)*
corrected, 217-218, 218f, 219f
in SPECT, 302
Flow counting
with liquid scintillation counters, 188
with NaI(Tl) detectors, 182
Flow rate, tracer measurement of, 380, 380f
Fluor, 105, 106
Fluorescent yield, 12, 13f
Fluorine-18
characteristics of, 451
decay of, 26, 27, 451
detection of, with CZT spectrometer, 151, 153f
in FDG labeling, 49-50
labeling with, 60-61
mean dose per cumulated activity for, 415-416, 422t-423t
positron range of, 314, 314f, 315
production of, 46-47, 49-50
properties of, 58t
Fluorodeoxyglucose (FDG), 61
advantages of, 60
as analog tracer, 382
clinical uses of, 5, 5t, 60, 61, 341-342, 342f
co-registered images with, 377f
^{18}F labeling of, 49-50
kinetics in metabolism of, 396, 397-400, 398f
production of, 50
radiation dose estimates for, 425t, 427, 478, 479
Flux, 383-384
steady state and, 385-386, 386f
Flux density, 54, 55f
Focal spot, 347
Forward projection, 270-272, 270f, 276
Fourier slice theorem. *See* Projection slice theorem.
Fourier transform (FT), 258
basic concept of, 481, 482f
calculation of, 258
of convolution, 492
definition of, 258
direct, 258-260. *See also* Direct Fourier transform reconstruction.
examples of, 487f, 487, 488f
inverse, 258
modulation transfer function and, 238, 481, 485f, 492
properties of, 483-485, 483f, 487
in tomographic reconstruction
for 3-D PET data, 334
direct, 258-260, 259f
FOV. *See* Field-of-view (FOV).
FPF. *See* False-positive fraction (FPF).
Frame-mode acquisition, 367-368
Free-response operating characteristics (FROC), 250
Frequency, 8
Frequency distributions, 126, 127f
Gaussian, 127f, 128
Poisson, 126, 127f, 128

Frequency response curves, 236-237, 236f
FT. *See* Fourier transform (FT).
Full width at half maximum (FWHM).
  computation of, 149, 149f
  definition of, 148-149
  of gamma camera image
    collimator resolution and, 222, 222f, 227
    intrinsic resolution and, 210-211, 221, 225t, 229
    system resolution and, 225, 229, 235-236
  of Gaussian function, 491-492
  linear sampling distance and, 263, 265
  in PET
    of angular distribution, 319
    partial-volume effects and, 340
    of positron range, 312f, 314, 314f, 316
    of spatial resolution, 310, 311f, 317, 318
  pixel size and, 234, 366
  in reconstruction tomography, 263
  in resolution evaluation, 235-236
  in SPECT
    partial-volume effects and, 299, 300f
    reconstruction tomography and, 301-302
    of spatial resolution, 301
Full width at tenth maximum (FWTM)
  of gamma camera image, 229
Fundamental quantities, 7
FWHM. *See* Full width at half maximum (FWHM).
FWTM. *See* Full width at tenth maximum (FWTM)

G

Gadolinium-153, transmission scan with, 295, 296, 297f
Gadolinium oxyorthosilicate (GSO)
  in PET detectors, 322t, 326
  properties of, 101t
Gain factor
  for amplifiers, 110
  drift in, in gamma camera, 219-220, 220f
  for preamplifiers, 108-109
Gallbladder, gamma camera imaging of, 207f
Gallbladder dynamics, tracers for, 381t
Gallium-67, 5t, 58t, 243, 305, 478
Gallium-68, 313t, 315f, 316, 328, 457
Gamma cameras, 195-208
  acceptance testing for, 228-231
  analog, 197-200
  analog buffers for, 213-214
  in annihilation coincidence detection, 310-312, 311f
  calibration of, 147-148
  clinical uses of, 1, 206-208, 206f, 207f, 208f
Gamma cameras *(Continued)*
  collimator efficiency and, 220
  collimator resolution and, 220, 222, 225t
  collimators for, 196, 196f, 201-204, 202f, 203f, 204f
    absorptive, 201
    converging, 204, 204f
    design and performance of, 220-223, 221f, 222f, 224f, 225, 225t, 226f, 230
    diverging, 202f, 203
    modulation transfer functions of, 236, 237f, 238f, 239f
    multi-pinhole, 202f, 203
    parallel-hole, 202f, 203, 220-225, 221f-222f, 224f, 226f. *See also* Parallel-hole collimators.
    penetration of. *See* Septal penetration.
    pinhole, 202-203, 202f
    scatter from, 204-205
    sensitivity of, 223, 224f, 225t, 227, 231
    septal thickness in, 203, 203f
    slant-hole, 203
    for small animal imaging, 207-208
  compact, 207, 208f
  components of, 196-206, 196f
  counting rates for
    high, 213-216
    measurement of, 230
  current availability of, 4
  definition of, 195
  derandomizers for, 213-214
  detectors in, 197-201, 207
    thickness of
      detection efficiency and, 211, 212f
      intrinsic spatial resolution and, 210, 211f
  development of, 196
  digital image processing for, 197, 200, 364, 365f, 482. *See also* Digital image processing.
  dual-headed, 206-207, 206f
  dynamic imaging with, 197, 206-207
  edge packing and, 217
  electronics of, 197-201, 197f, 198f, 199f, 200f, 201f
  energy corrections and, 217-218
  energy selection for, 200, 201f
  energy window for, 212, 212f, 213, 218, 218f, 336, 337
  event detection in, 204-206, 205f
  event localization in, 197, 198, 200f, 219
  film recorders for, 196
  flood-field images from, 216f, 217
  gallbladder imaging with, 207f
  gamma-ray energy in, 211
  historical development of, 4, 4f, 196
  image display for, 197
  image formation in, 196-197
  imaging modes with, 196-197
Gamma cameras *(Continued)*
  intrinsic spatial resolution of, 209-211, 210f-211f. *See also* Spatial resolution: intrinsic.
    Compton scattering and, 209
    detection efficiency vs., 211, 212f
    detector thickness and, 210, 211f
    full width at half maximum and, 210-211, 225
    gamma ray energy and, 210, 210f
    improvement of, 219
    limits on, 209-210
    measurement of, 210, 229
    optimum, 210-211
  mobile, 207, 208f
  modulation transfer functions for, 237, 238f
  NaI(Tl) crystal in, 196-198, 196f
  performance of, 209-231
    collimators in, 220-223, 221f, 222f, 224f, 225, 225t, 226f, 230
    dead time in, 213-214, 230
    detection efficiency in, 211, 212f
      detector thickness and, 211, 212f
      nonuniform, 217
    energy resolution in, 150, 201, 211-213, 212f
      measurement of, 231
    at high counting rates, 213-216
    image nonlinearity in, 216-217, 216f, 218, 218f-219f
    image nonuniformity in, 217-219, 218f-219f, 243
    measurements of, 228-231
    pulse pile-up in, 213-216, 213f, 214f-215f
    spatial resolution in. *See* Spatial resolution.
    tuning methods and, 219-220, 220f
  in PET, 327f, 329-330
  photomultiplier tubes of, 196, 196f
    arrangement of, 196-198, 196f, 216
    charge integration time for, 214
    dead time and, 214
    energy resolution and, 149-150
    image nonlinearity and, 216, 216f
    image nonuniformity and, 217
    intrinsic resolution and, 209, 210, 234
    light sharing between, 198, 199f
    pulse pile-up and, 214
    in scintillation event localization, 198-200
    statistical fluctuations in, 209-210
    tuning of, 219-220, 220f
  photopeak selection for, 200, 201f
  pincushion artifacts and, 199-200, 215f, 216

Gamma cameras *(Continued)*
quality assurance for, 228-231
response characteristics of, 254, 254f
scintillation event localization in
in analog camera, 198-200
in digital camera, 200
sensitivity of, measurement of, 231
single-headed, 206-207, 206f
for small animal imaging, 207-208
spatial linearity and, measurement of, 229-230
in SPECT, 279-280
in SPECT/CT, 350f, 351, 352f
static imaging with, 197
system resolution of, 210-211, 214, 225, 227-228
measurement of, 229
technical advances in, 207
in tomographic imaging, 254, 254f, 255, 255f, 256f
for PET, 4, 325-326, 327f, 329-330, 332, 334
for SPECT, 279-280, 280f, 281, 283, 301-303
triple-headed, 206-207
types of, 206-208, 206f, 207f, 208f
uniformity measures for, 230
whole-body imaging with, 207f
X- and Y-position signals in, 199-200
Gamma probes, intraoperative, 193f, 194
Gamma rays. *See also* Photons.
annihilation, 25
biologic effects of, 78, 428
in collimators, 201-203
Compton scattering of. *See* Compton scattering.
detection of. *See* Radiation detectors.
in electromagnetic spectrum, 8, 8f
energy of
attenuation and, 163-164, 164f
in SPECT, 287-294
gamma camera resolution and, 211-213, 234
intrinsic efficiency and, 158, 159f, 174, 175f
nuclear transitions and, 15
photofraction and, 159, 160f, 174, 174f
pulse-height spectrum and, 142-147, 143f, 145f, 146f, 147f, 151
scatter and, 163-164, 164f
in vivo measurements and, 163
interactions with matter, 74-78
in nuclear medicine, 1
from nuclear transitions, 8-9, 8f, 15
in (α, γ) decay, 28
in (β^+, γ) emission, 26
in (β^-, γ) emission, 21-22, 22f, 23f
in (EC, γ) decay, 24, 24f
isomeric, 22-23, 23f, 24
in (n, γ) reaction, 46
Gamma rays *(Continued)*
penetration by, 195
septal, 205, 220-221
prompt, 45-46
pulse-height spectrum of, 142-147, 143f, 145f, 146f, 147f, 151
radiation safety and, 434, 435, 437
Gamma-ray converters, 158-159
Gamma-ray probes
miniature, 192-194, 193f
in oncology, 192-193
radiation detectors for, 193
Gas amplification
in Geiger-Müller counters, 92-93, 94f
in ionization chambers, 91, 92f
in proportional counters, 91, 92f
Gas chromatograph
with gas-filled detector, 190
with liquid scintillation counter, 188
with NaI(Tl) detector, 182, 183f
Gas flow counters, 190
Gas flow counting with LS systems, 188
Gas proportional counters. *See* Proportional counters.
Gases, radioactive
dose limits for, 431-432
safe handling of, 437, 438
Gas-filled detectors, 87-96, 189-190. *See also* Geiger-Müller (GM) counters; Ionization chambers; Proportional counters.
advantages and limitations of, 102
applications of, 189-190
in dose calibrators, 189-190
energy deposition in, 141
in gas flow counters, 190
Geiger-Müller counters, 92-96, 93f-95f
intrinsic efficiency of, 158-159
ionization chamber, 87-91, 89f-91f. *See also* Ionization chambers.
principles and design of, 87, 88f
proportional counters, 91-92, 92f
semiconductor, 96-97, 97f
Gated imaging, 369
in cardiac studies, 234, 303, 304, 304f, 392, 392f
with gamma camera, 197
motion blurring and, 245
Gaussian blurring function, 235-236, 491
Gaussian distribution, 127f, 128
statistical tests and, 133, 135, 138
Gaussian function, convolution of, 491
Gaussian response profile of annihilation coincidence detector, 308, 310f
Gaussian smoothing filters, 373, 375f
Gaussian spectral curve, 149
Geiger-Müller (GM) counters, 92-96, 93f, 94f, 95f
avalanche ionization in, 92-93, 94f
backscatter and, 166-167, 167f
for β-emitting radionuclides, 167
as gas flow counters, 190
counting curves for, 94, 95f
dead time in, 168, 188
intrinsic efficiency of, 158-159
limitations of, 93, 95, 166-167
pancake, 95-96, 95f
power supply for, 122
principles and design of, 92, 93f, 95-96, 95f
pulse signals of, 107, 107t
self-absorption and, 166-167, 167f
self-quenched, 93-94
as survey meter, 95-96, 95f, 439
Generators, 24, 50-53, 51f, 51t
contaminants in, 50-53, 58
fission moly, 53
historical development of, 2
radionuclide, 50-53, 51f-52f, 51t
safe handling of, 436
Geometric detection efficiency. *See* Detection efficiency: geometric.
Geometric mean, in conjugate counting, 287-293
correction for, 293-294, 294f
Germanium-68, 165t
characteristics of, 457
as rod source, in PET scanner, 328f, 329, 338
Germanium detectors, 89t, 96-97. *See also* Radiation detectors; Semiconductor detectors.
detection efficiency of, 158
intrinsic, 96, 158
lithium-drifted, 89t, 96-97, 97f
spectrometry with, 151, 152f
GFR. *See* Glomerular filtration rates (GFR).
Gibbs phenomenon, 486
Glass, leaded, 436-437, 436f
Glass vials for liquid scintillation counting, 184-185
Glomerular filtration rate (GFR), 379
Glucose. *See also* Fluorodeoxyglucose (FDG).
metabolism of, 396-401
FDG model of, 397-401, 398f
Michaelis-Menten hypothesis and, 396-397, 397f
parametric brain imaging and, 400, 401f
Sokoloff deoxyglucose method and, 397, 400
transport of, 389
GM counters. *See* Geiger-Müller (GM) counters.
Graphics processing units, 363
Gray (Gy), 89, 407, 433-434
Grayscale images, 367, 370f

Ground state of nucleus, 14, 15, 15f, 16
GSO. *See* Gadolinium oxyorthosilicate (GSO).

H

Half-life, 33-34
  biologic, 59, 410-411, 411f, 412
  effective, 411-412
  physical, 33-34
    average lifetime and, 34
    for clinical applications, 59, 60-61
    cumulated activity and, 410-412
  of radiopharmaceuticals, 59
Half-time of turnover, 384, 480
Half-time of uptake, 410
Half-value layer (HVL). *See* Half-value thickness (HVT).
Half-value thickness (HVT), 82, 82t, 83, 84
Hann filter, 261, 262f
Harper, Paul, 2-4
Hasegawa, Bruce, 350
Health care workers, occupational exposure of. *See* Radiation safety.
Health physics, 427-428. *See also* Radiation safety.
  air kerma and, 428-431, 434-435
  dose-modifying factors and, 428
  exposure rate and, 89, 428-431
  quantities and units in, 428-431, 429t
Heart. *See* Cardiac studies; Organs.
Heat scale, 367
Hevesy, Georg de, 2
Hexokinase, 396, 397, 398f, 399
HIDA, ^{99m}Tc-labeled, 60t, 207f
High-voltage power supplies, 122
HMPAO (hexamethylpropyleneamine oxime), 304, 304f
Hormesis, 427
Hot lesions, 246
Hot-body scale, 367
Hounsfield units, 349
HPGe (high purity germanium), 97
Human observer performance studies, 233
  contrast-detail studies, 247-248, 248f-249f
  receiver operating characteristic studies, 248-251, 250f
HVT. *See* Half-value thickness (HVT).
Hybrid imaging systems
  CT-based, 346-354, 356-360. *See also* PET/CT; SPECT/CT; X-ray computed tomography.
    advantages of, 332-334
    future directions for, 345-346
  image co-registration and, 376
  MRI-based, 360-361
Hydrogen-3 (tritium), 449. *See also* Liquid scintillation counters (LSCs).
Hypoxia, tracers for, 381t

I

ICRP. *See* International Commission on Radiological Protection (ICRP).
ICRU. *See* International Commission on Radiological Units (ICRU).
Image arithmetic, 371, 371f
Image contrast. *See* Contrast.
Image intensity, Fourier transform of, 481, 482
Image noise, 243-247, 247f. *See also* Contrast-to-noise ratio (CNR); Statistical noise.
  in digital image, 366, 367
  in tomographic image, 266-270
    filtered backprojection and, 261-262
    in PET, 319
    ramp filter and, 268, 301
Image processing. *See* Digital image processing.
Image quality, 233-251. *See also* Detectability.
  basic methods for characterization of, 233
  contrast and, 233, 239-240
  coverage and, 266, 266f-267f
  definition of, 233
  in direct Fourier transform reconstruction, 263-270
  edge sharpness and, 237
  in emission CT, 263-270
  evaluation of, 233
    contrast-detail studies for, 247-249, 248f-249f
    observer performance studies for, 247-251
    receiver-operating characteristic studies in, 248-251, 250f
  filtered backprojection and, 263-270
  with gamma (Anger) camera, 233
    nonlinearity and, 216-217, 216f, 218
    in PET, 335
    nonuniformity and, 217-220, 218f, 219f, 220f, 243
    in PET, 335
    pulse pileup and, 213, 214, 214f
  information density and, 244, 245, 246-247, 247f
  noise and, 233, 243-247
  observer performance studies of, 233, 247-251, 248f, 249f, 250f
  patient motion and, 234, 266, 359
  in PET, 335
  processing and. *See* Digital image processing.
  quality assurance and. *See* Quality assurance.
  in reconstruction tomography, 263-270, 266f-267f
    coverage and consistency requirements and, 266
Image quality *(Continued)*
    in iterative reconstruction, 273
    Nyquist frequency and, 263
    sampling and, 263-265
  spatial resolution and, 233-239. *See also* Spatial resolution.
  in SPECT, 302-303
  system resolution and, 265-266
  tomographic reconstruction and
    with FT and FBP, 263, 264f, 265-270, 265f, 266f, 267f
    with iterative methods, 275-276
  in x-ray computed tomography, 263-270
Image reconstruction. *See* Reconstruction tomography.
Image registration. *See* Co-registration.
Image segmentation, 375, 377f
  in CT-based attenuation correction, 357
Image smoothing, 373, 375f, 489
Image space, 258
Image visualization, 369-372, 370f-372f
Image-frame decay corrections, 35-36, 36f
Images. *See* Digital images.
Imaging, radionuclide. *See* Gamma cameras; Tomographic imaging.
Impedance matching, 107
Impulse response, 391-392
In vitro counting systems, 173
In vivo counting systems, 173, 192-194, 192f, 193f
  detection efficiency in, 156, 166
Index of refraction of scintillators, 101t, 104
Indium-111, 58t
  characteristics of, 463
  pentetreotide labeled with, 305
  in radioimmunoguided surgery, 193
  white blood cells labeled with, 5t
Infection, tracers for, 5t, 381t
Information density, 244, 245, 247, 247f
Inorganic scintillators, 100-103, 101f, 101t, 102f, 103f
  NaI(Tl), 100-103, 101f-103f, 101t. *See also* NaI(Tl) detectors.
  for PET, 316, 322t, 324, 326
  properties of, 101t, 103, 103f
  selection of, 103
In-plane resolution, 301
Input function, 390, 391, 391f
Instrumentation. *See* Counting systems; Electronic instrumentation; Radiation detectors.
Integral uniformity, for gamma cameras, 229-230
Integration circuits, 111, 112f
Integration time
  energy resolution and, 150
  in gamma camera, 214
Internal conversion, 15, 22-23, 23f

Internal dosimetry. *See* Radiation dosimetry, internal.
Internal standardization method, 186, 186f
International Commission on Radiological Protection (ICRP), 417, 431, 433, 434t. *See also* Radiation safety.
International Commission on Radiological Units (ICRU), 437
Intersubject image co-registration, 375-376
Intrasubject intramodality image co-registration, 375-376
Intrinsic detection efficiency. *See* Detection efficiency: intrinsic.
Intrinsic germanium detectors, 96
Intrinsic photopeak efficiency
  for NaI(Tl) well counters, 174, 176f
  of semiconductor detector, 191
Intrinsic spatial resolution. *See* Spatial resolution: intrinsic.
Intrinsic uniformity, 229-230
Inverse β^- decay, 24-25
Inverse Fourier transform, 258
Inverse-square law, 156, 157f, 435
Iodine-123, 464-465
Iodine-124, 466-467
Iodine-125, 24-25, 24f, 58t, 468-469
Iodine-129, as calibration standard, 165t
Iodine-131
  characteristics of, 470-471
  dosimetry of, internal, 416, 420t
  as iodide ion, 57
  mean dose per cumulated activity of, 415-416, 420t-421t
  mock calibration source for, 177
  notation for, 14
  properties of, 58t
  in radioimmunoguided surgery, 193
  safe handling of, 432
  in thyroid imaging, 2, 3f, 5t
Iodine escape peak, 144, 144f
Ionization, 87, 87f
  avalanche
    in Geiger-Müller counters, 92-93, 94f
    in ionization chambers, 91, 92f
    in proportional counters, 91, 92f
  Bragg peak in, 68, 69f
  collisional energy losses in, 64-65, 66f-67f
  pair production and, 76-77, 87. *See also* Pair production.
  radiation detection and, 87, 141-142, 142f
  secondary, 63, 64f
    to charged-particle interactions, 63, 64, 141-142, 142f
    to photon interactions, 74, 76-77, 78, 141, 142f
  specific, 68, 69f, 71
Ionization *(Continued)*
  tracks associated with, 66, 67, 67f, 68, 70
  units of radiation and, 428-429
Ionization chambers, 87-91, 88f, 89f, 90f, 91f
  detector materials for, 89t
  in dose calibrators, 89, 89f, 189-190
  efficiency of, 90-91, 158-159
  energy response curve for, 90-91, 91f
  gas amplification in, 91, 92f
  gas-filled, 87-96
  limitations of, 90-91
  in pocket dosimeters, 89-90, 90f
  principles and design of, 87-91, 88f
  in survey meters, 89, 89f
  voltage response curve for, 87-88, 88f, 91, 92f
  vs. proportional counters, 91-92
Ionization detectors, 87. *See also* Gas-filled detectors; Semiconductor detectors.
  gas-filled, 87, 88f
  semiconductor, 96-97, 97f
Ionization events
  primary, 141, 142f
  secondary, 141, 142f
Ionization potential, 68
Ionizing radiation, 63
  biologic effects of, 427-428
  definition of, 8, 63
  secondary, 74
Isobaric decay modes, 20, 24, 25-26, 27
Isobars, 14, 14f
  stability of, 17
Isomeric state, 14-15
  decay of, 19-20
Isomeric transition, 22
Isomers, 14
Isotones, 14, 14f, 16f, 17, 28
Isotope effect, 20, 380
Isotopes, 14, 14f
  on chart of nuclides, 28
  definition of, 14
  radioactive. *See* Radionuclides.
  stable, 16f, 17
Isotropic emission, 156
Iterative reconstruction, 262, 270-273
  for coded aperture imaging, 285
  cone-beam data in, 275
  3-D, 276
  expectation-maximization, 272-273
  filtered backprojection vs., 271-272
  forward projection and, 270-272
  image quality in, 273
  overview of, 258
  for PET data, 331, 332, 334
  sampling in, 273
  scatter corrections in, 298, 299
  steps in, 270-271, 270f-271f
  tissue attenuation information in, 296, 298

J

Joule, 407

K

K absorption edges, 79, 80f
K shells, 65f-67f, 67-70, 73t
Kerma, air, 89, 428-431, 429t
Kety-Schmidt method, 387, 395
keV. *See* Kiloelectron volt (keV).
Kidney, functional evaluation of, 379
Kilocurie, 32
Kiloelectron volt (keV), 8
Kinetic energy
  kerma and, 429, 429t
  in radioactive decay, 19, 20
Kinetic modeling. *See* Tracer kinetic modeling.
k-space, 258-259, 260f, 481, 482, 483, 483f, 484, 485f, 487
  Nyquist frequency and, 263, 484, 485f, 487
Kuhl, D.E., 4

L

L (linear energy transfer), 68
L shells, 65f, 67-70, 72f-73f, 73t
Labeled microsphere technique, 393-394
Labels/labeling. *See also* Radiopharmaceuticals.
  by analog creation, 60
  by direct substitution, 59-60
  with ^{99m}Tc, 60, 60t
  with positron emitters, 60-61
  of radiopharmaceuticals, 59-60
  requirements for, 381-382
Laboratory design, 438
Laboratory monitors, 436
L absorption edges, 79, 80f
Lanthanum bromide, 101t, 103
Lanthanum chloride, 103
Laplacian technique, 373, 375, 376f
Lawrence, Ernest O., 2, 3f
LC. *See* Lumped constant (LC).
LCD. *See* Liquid crystal display (LCD).
Lead
  in bar phantom, 235
  in collimator
    of gamma camera, 195, 196, 203, 221
    of SPECT system, 281, 283
  mass attenuation coefficients of, 476-477
Lead shielding, 436-437, 436f. *See also* Shielding.
  for dose calibrator, 189, 437
  natural radioactivity in, 178
  in PET systems, 323
  for well counter, 178, 180f, 181, 183f
  x-ray peaks from, 144, 151
Lead x-ray peaks, 144
Leaded glass, 436-437, 436f
Leading-edge timing, 115, 115f
LEDs. *See* Light-emitting diodes (LEDs).

Left ventricular ejection fraction, 392, 392f
Lesion detectability. *See* Detectability.
Lesions. *See* Detectability.
LET. *See* Linear energy transfer (LET).
Licensing for use of radionuclides, 431, 432, 433
Ligand, 60
Light coupling. *See* Optical coupling.
Light guide of gamma camera, 196, 196f, 198, 219
Light-emitting diodes (LEDs), 219
Limited-angle tomography, 266
Limited-scope licenses, 431
Line broadening, 148. *See also* Energy resolution.
Line integrals, 254, 254f
Line of response, 254, 254f
  actual vs. idealized, 285-286
  conjugate counting and, 287
  scattering into, 296
  in transmission scan, 295-296
Line of stability, 16, 16f
  decay modes and, 28
Linear accelerators, 47
Linear attenuation coefficients, 78, 81, 82, 83, 158
  of bone, 287, 294, 338
  coincidence rate and, 319
  of collimator material, 221, 222
  detection efficiency and, 158, 159
    in PET, 321
  of tissue, 192, 296
    transmission scan and, 294, 338
Linear energy transfer (LET)
  of charged particles, 68, 71
  of photons, 78
Linear nonthreshold (LNT) model, 427
Linear regression, 139-140
Linear sampling distance, 263, 265
  in annihilation coincidence detection, 318, 318f
  in imaging processing, 365-366
  with iterative algorithms, 273
  performance measurement and, 301
  pixel size and, 366
  SNR and, 267
Linear stopping power, 68
Line-spread function (LSF)
  distance from source vs., 288f
  FWHM and, 235
  of gamma-camera collimators, 222-223, 222f, 224f, 225
  modular transfer function and, 238, 240-241, 242f
  pixel size and, 366
  in resolution evaluation, 235
  scattered radiation and, 240-241, 242f
  septal penetration and, 240-241, 242f
  in SPECT imaging, 288f, 298
Liquid chromatography, with NaI(Tl) detectors, 182, 183f
Liquid crystal display (LCD), 124, 367
Liquid nitrogen in semiconductor detectors, 97, 97f
Liquid scintillation (LS), 104-106, 105f, 187-188
Liquid scintillation (LS) cocktails, 105, 187
Liquid scintillation counters (LSCs), 184-185
  applications of, 105, 183-184, 189
  automated multi-sample, 188-189, 188f
  calibration of, 185
  Cerenkov counting with, 188
  coincidence detection by, 184
  components of, 105f, 182-184, 183f
  dark adaptation of samples and, 185
  dead time in, 168
  efficiency of, 157, 185
  flow counting with, 188
  gas/liquid chromatography with, 188
  limitations of, 106
  mixtures of radionuclides in, 185, 188-189
  noise in, 184, 185, 186
  organic scintillators for, 104-106
  principles and design of, 182-184, 183f
  pulse signals of, 108t
  pulse-height spectrometry with, 141, 153, 153f, 184, 185f
  quenching in, 106, 188
    correction methods for, 185-187, 186f-187f
  radionuclides counted with, 105, 166, 182-184, 183t
  refrigeration of, 184
  sample preparation for, 106, 187-188
  scintillator solutions in, 104-106, 187
  vials for, 184-185
List-mode acquisition, 335, 368-369
Lithium fluoride, thermoluminescent, 440f
Logarithmic rate meters, 121, 121f
Logic pulses, 118-119
Lower-level discriminator, 113, 114f
LS. *See* Liquid scintillation (LS).
LSCs. *See* Liquid scintillation counters (LSCs).
LSF. *See* Line-spread function (LSF).
LuAP, 101t, 103
Lumped constant (LC), 399, 400
Lung perfusion, 393
Lung ventilation, 381t
Lutetium oxyorthosilicate (LSO), 101t, 102-103
  in PET systems, 321, 322t, 324, 325, 325f, 326
    energy resolution and, 337
Lutetium yttrium orthosilicate (LYSO), 101t, 102-103
Lymph nodes, sentinel, gamma-ray probes for, 192-193

M

MAG3 (mercapto-acetyl-triglycine), 5t
Magnetic resonance imaging (MRI)
  combined with nuclear medicine imaging, 376, 377f
  image reconstruction in, 4, 259
  in k-space, 259
  limitations of, 1
  with PET, 345-346, 360-361, 361f
  with SPECT, 360
  stray fields from, gamma camera and, 197
Malignant melanoma, sentinel nodes in, gamma-ray probes for, 193-193
Mass
  equivalence to energy, 8, 15-16, 19
  units of, 7-8
Mass attenuation coefficients, 79, 158
  absorbed dose and, 430
  table of, 476-477
Mass deficiency, 15
Mass number (A), 13
Mass-energy conversion in radioactive decay, 19
Matrix of pixels, 365, 365f
Matrix size, 365-366, 366f
Maximum intensity projection, 369-371
Maximum-likelihood (ML) reconstruction, 272-273
MCAs. *See* Multichannel analyzers (MCAs).
MDA. *See* Minimum detectable activity (MDA).
MDP. *See* Methylene diphosphonate (MDP).
Mean dose per cumulated activity, 411f, 414f, 415-416, 418t-419t
  for ^{18}F, 415-416, 422t-423t
  for ^{131}I, 415-416, 420t-421t
  for ^{99m}Tc, 415-416, 418t-419t
Mean free path, photon, 82, 82t
Mean transit time, 380, 380f, 384
Mean value, 126, 127
  arithmetic vs. geometric, 287-288, 288f
  confidence interval for, 127, 127t
  t-test and, 135-137
  uncertainty in, 128
Measurement errors, 125-126
  blunders, 125
  propagation of, 128-130
  random, 125-126
  systematic, 125
  types of, 125-126
Measurement standards, 125

Measurements. *See also* Statistical analysis.
constant multipliers and, 129
frequency distribution of, 126, 127f
inaccurate, 125
reproducible, 126
sums and differences of, 129
true value of, 126
uncertainty in, 126-127, 129
Medical Internal Radiation Dose (MIRD) Committee, 28, 407, 414
Medical Internal Radiation Dosimetry (MIRD) method. *See* Absorbed fraction (MIRD) method.
Medical Internal Radiation Dosimetry (MIRD) publications, 28
Megaelectron volt (MeV), 8
Melanoma, sentinel nodes in, gamma-ray probes for, 192-193
Metabolic tracers. *See* Fluorodeoxyglucose (FDG); Methylene diphosphonate (MDP); Oxygen-15.
Metastable radionuclides, generators of, 24, 50-53, 51t, 52f
Metastable state, 10f, 14-15
decay of, 22
Methylene diphosphonate (MDP), 5t, 60t, 207f, 479
Metric units, 7
MeV. *See* Megaelectron volt (MeV).
Michaelis-Menten kinetics, 396-397, 397f
Microcurie, 32
Microdosimetry, 425
Microprocessors, 363
Microsphere technique, 393
Millibarn, 53-54
Miniature probes for surgery, 192-194
Minimum detectable activity (MDA), 131
with semiconductor detectors, 191
MIRD Committee. *See* Medical Internal Radiation Dose (MIRD) Committee.
MIRD method. *See* Absorbed fraction (MIRD) method; Radiation dosimetry, internal.
MIRD publications. *See* Medical Internal Radiation Dosimetry (MIRD) publications.
ML reconstruction. *See* Maximum-likelihood (ML) reconstruction.
ML-EM method, 272-273
Mn-54, 165t
Mock calibration sources, 177
Modulation transfer function (MTF), 236-237, 487, 492
3-D representation of, 238
derivation of, 238
line-spread function and, 238, 240-241, 242f
scatter and, 241, 242f
Modulation transfer function (MTF) *(Continued)*
of SPECT system, 301
system effects and, 238
Moly shield, 53
Molybdenum-99, 45, 51f, 51t, 53
breakthrough of, 50-53, 84
characteristics of, 460
detection of, with dose calibrator, 189
production of, 44-45
Molybdenum-99—technetium-99 generators, 50-53, 51f, 51t, 60
Monitoring of radiation. *See* Radiation monitoring; Radiation safety; Survey meters.
Motion, patient, 234, 234f
attenuation correction artifacts and, 359
breath-holding and, 359
gated imaging and, 234, 368
in SPECT, 303, 304f
image quality and, 234, 266, 359
in PET, 308, 339
Motion blurring, 234, 266
attenuation correction artifacts and, 359
breath-holding and, 359
image quality and, 234, 266, 359
MRI. *See* Magnetic resonance imaging (MRI).
MTF. *See* Modulation transfer function (MTF).
Multichannel analyzers (MCAs), 113, 116-118, 116f
dead time of, 168
of liquid scintillation counters, 184
of NaI(Tl) well counters, 173, 180f, 181
for radiochemical identification, 182
of semiconductor detectors, 190
Multi-pinhole collimators, 202f, 203
Multiple scattering, intrinsic resolution and, 209, 210
Multiprobe systems, 192
Multi-slice imaging, 262-263
Mu-metal shielding, 99, 101f
Muscle, *f* factor for, 430, 430f
Myocardial imaging
with ^{99m}Tc-labeled red cells, 392, 392f
SPECT in, 281-283, 303, 305f, 306
Myocardial perfusion. *See* Cardiac studies.

N

(n, γ) reaction, 45, 46
(n, p) reaction, 46, 47
NaI(Tl) detectors, 100-103, 182
advantages of, 102, 190-191
amplifiers for, 113
for cardiac SPECT, 281-283
NaI(Tl) detectors *(Continued)*
counting applications of
with gas/liquid chromatographs, 179
with large sample volumes, 182
with NaI(Tl) well counters, 173, 174f, 174t
cracked crystal in, 104, 150, 217
dead times of systems with, 179
detection efficiency of, 157, 174, 175, 175f-176f, 179
intrinsic, 158-159
with source in tissue, 163, 164f
total, 160-161, 161f
digitization of signals from, 117-118
disadvantages of, 102
energy linearity and, 147-148
energy resolution and, 148-151
in gamma cameras, 196-198, 196f
crystal thickness in, 210, 210f, 211, 211f
limitations of, 216
limitations of, 182
linear attenuation coefficient of, 321, 322t
mass attenuation coefficients of, 476-477
minimum detectable activity with, 191
in PET scanners, 321, 322t, 324, 327f, 330, 337
photofraction with, 159, 160f
power supply for, 122
preamplifiers for, 108-109
principles and design of, 91, 100-102, 101f
pulse-height spectrometry with, 142-151. *See also* Pulse-height spectrometry: with NaI(Tl) detectors.
advantages of, 151
calibration for, 147-148
counting rate and, 146, 147f
crystal size and, 145-146, 146f, 158, 159, 160f
energy linearity in, 148-149, 148f
energy resolution in, 148-151, 149f, 150f
vs. semiconductor detectors, 151, 152, 152f
gamma-ray energy and, 147, 147f
scatter rejection in, 240
spectral structure in, 142-145, 143f, 144f, 145f, 146f
timing methods in, 114-115
in SPECT
in brain imaging, 280-281, 282f
in cardiac imaging, 281-283
in CERASPECT system, 281, 282f
in small-animal imaging, 281-283, 282f
in SPRINT II system, 280-281, 282f
through-hole, 180, 180f-181f
timing methods for, 114-116

NaI(Tl) detectors *(Continued)*
in whole-body counters, 194
window fractions and, 170-171
in well counters. *See* NaI(Tl) well counters.
NaI(Tl) probe systems, 207, 208f
NaI(Tl) well counters, 173-182
absolute activity assays and, 177
applications of, 182
automated multiple-sample, 179-182, 180f
background in, 179, 180, 181
background radiation and, 177-178, 179, 180, 181
calibration of, 178
coincidence detection and, 163
coincidence summing in, 145, 146f, 163
dead time of, 179, 182
detection efficiency of, 157, 174, 175, 175f-176f, 179
detector characteristics in, 173, 174f
detectors in, 173, 174f, 174t
through-hole, 180, 180f
efficiency of, 174, 175, 175f-176f, 179
geometric, 157
energy calibration of, 178
energy resolution of, 173
multichannel analyzers for, 173, 180f, 181
multiple radionuclides in, 178-179, 178f, 181, 182
rod standards for, 164, 165f
sample volume effects and, 175-177, 177f
shielding for, 177-178
volume effects in, 174, 175-177, 177f
with through-hole detector, 180, 180f-181f
Nanocurie, 32
Narrow-beam attenuation coefficient, 297
Narrow-beam geometry, 79-83, 81f, 82t
National Council on Radiation Protection and Measurement (NCRP), 431, 433, 434t
NCRP. *See* National Council on Radiation Protection and Measurement (NCRP).
Negative-ion cyclotrons, 48-49, 49f
Net extraction fraction, 387
Neurodegenerative diseases, 341-342
Neutrinos, 20-21, 24, 25
Neutron activation, 45-47, 46t
Neutron activation analysis, 190, 192
Neutron deficient nuclides, 17, 28
Neutron number, 13
Neutron-capture cross-sections, 54
Neutrons, 13-14, 13t
arrangement of, 14-15
decay modes involving. *See also specific modes*.
β^- decay as, 20-21
electron capture as, 24, 28
Neutrons *(Continued)*
fission as, 26
positron emission and, 25
energy levels of, 10f, 14-15
equivalent dose of, 408t
fission, 28, 43
forces on, 14-15
nuclear stability and, 14-18, 16f-17f
number of, 13-14
properties of, 13, 14t
in shell model, 14
slow (thermal), 43-44
Neutron-to-proton ratio, 16
NIM. *See* Nuclear instrument modules (NIM).
Nitrogen-13, 58t, 60-61, 382, 450
Noise, 233, 239-240, 243-247
contrast-to-noise ratio and, 243-244
in reconstruction tomography, 266-268
definition of, 233
in filtered backprojection, 260-263, 293f
image quality and, 233, 243-247
image smoothing and, 373, 375f
in iterative reconstruction, 273
in liquid scintillation counters, 184
random, 243
contrast-to-noise ratio and, 243-244
in reconstruction tomography, 266-268
reduction of, by coincidence detection, 184
sampling requirements and, 366
signal-to-noise ratio and, 110
in filtered backprojection, 260-261, 263, 264f
image smoothing and, 373, 375f
in reconstruction tomography, 266-268
spectral blurring and, 148
structured, 243
Noise equivalent counting rates, 340-341, 341f
Noncolinearity, 314, 315f, 316
Nondisplaceable compartments, 384, 402f
Nonlinear energy response of NaI(Tl) detectors, 148, 149-150, 178
Nonparalyzable counting systems, 168-169, 168f-169f
Normal distribution, 127f, 128, 133
NRC. *See* Nuclear Regulatory Commission (NRC).
Nuclear atom, 9
Nuclear binding energy, 15-16
nuclide stability and, 17-18, 17f
Nuclear chain reactions, 43. *See also* Fission.
Nuclear counting statistics, 125-140. *See also* Measurements; Statistical analysis.
Nuclear counting systems, comparison of, 132
Nuclear emissions, 15. *See also* Radioactive decay.
Nuclear energy-level diagrams, 15, 15f
Nuclear families, 14, 14f
Nuclear fission, 26, 28
radioactive decay by, 28
radionuclide production by, 43-47
in reactors, 43-44
Nuclear forces, 14-15
Nuclear fragments, 43
Nuclear instrument modules (NIM), 122-123
Nuclear medicine, 1-6
advantages of, 1-2
applications of, 1-2, 12t
current practice of, 4-5
fundamental concepts of, 1
historical perspective on, 2-4, 3f-4f
risks of procedures in, 424, 427
role of physics in, 6
safety of, 2
selected procedures in, 5t
Nuclear physics
basic concepts of, 7-18
in medicine, 6
Nuclear reactors, 43-44, 44f
neutron-capture cross sections in, 54
principles and design of, 43-44, 44f
radionuclide production in, 43-47, 46t
Nuclear Regulatory Commission (NRC), 431, 432, 433
Nuclear-binding energy, 15-18
per nucleon, 17, 17f
Nucleons, 13-14, 13t. *See also* Neutrons; Protons.
arrangement of, 14-15
basic properties of, 13t
binding energy per, 17, 17f
energy levels of, 10f, 14-15
forces on, 14-15
nuclear stability and, 14-18, 16f-17f
in shell model, 14
Nucleus, 9, 13-18. *See also* Atomic number (Z).
binding energy of, 15-16, 17-18, 17f
composition of, 13, 13t
daughter, 19
decay of. *See* Radioactive decay.
in excitable state, 10f, 14-15
excited states of, 14, 15, 21, 22, 22f, 24, 25
forces and energy levels in, 14-15, 15f
in ground state, 14
mass number of, 13
in metastable state, 10f, 14-15
metastable states of, 14-15, 22, 24
neutron number of, 13
notation for, 13-15, 14f
parent, 19
of Rutherford atomic model, 9

Nucleus *(Continued)*
shell model of, 14
stability of, 14-18, 16f-17f
radioactive decay and, 19
Nuclides, 14, 14f. *See also* Radionuclides.
chart of, 29f
definition of, 14
energy-level diagram for, 15, 15f
isomers of, 14-15
metastable, separation of, 24
stable, 14-18, 16f-17f, 27, 28
Nutt, Ron, 354
Nyquist frequency, 263, 484, 485f, 487

O

Object detectability. *See* Detectability.
Object scatter, 144-145, 205
with gamma camera, 205, 205f
with NaI(Tl) detector, 144, 145, 147, 147f, 152f
Object space, 258, 481, 483, 483f, 485, 485f, 487
Observer performance studies, 247-251
computer, 233
human, 233
contrast-detail studies, 247-248, 248f-249f
receiver operating characteristic studies, 248-251, 250f
Occupational dose limits, 432, 434t
Occupational exposure. *See also* Radiation safety.
definition of, 431
dose limits for, 431-432, 434t
in pregnancy, 433
Oncology
FDG-PET in, 341
gamma-ray probes in, 192-193
PET/CT in, 355-356, 356f
SPECT in, 305-306
1/r blurring, 258, 260-261
One-sided *t* test, 136, 137
Optical coupling, 149, 150, 151
Optical windows, 101-102
Orbits, electron, 9, 10f
Order of reaction, 385
Ordered subsets, 272
Organic scintillators, 104-106
in liquid solution, 97, 104-106, 106f, 185, 187, 188
plastic, 105, 105f
solid, for flow counter, 187
Organs. *See also* Radiation dosimetry, internal; Tissue.
dose estimates for
with FDG, 424, 425t
phantom models and, 414, 414f, 415
for selected radiopharmaceuticals, 478-479t
dose limits for, 432, 432t
radiation damage to, 427, 428
Organs *(Continued)*
source and target, 408, 413-414, 415, 416, 418t-424t
weighting factors for, 424, 428, 429t, 435
Oscilloscopes
analog, 124
cathode ray tubes for, 123-124, 123f
digital, 124
Outliers, 138, 138t, 139f
Oxygen-15, 60-61
blood flow measurement with, 393, 395
decay of, 25-26, 26f
in PET
for cerebral perfusion studies, 371, 372f
dead time losses with, 339
positron range of, 113t, 314, 314f
production of, 49
properties of, 58, 58t, 381t, 382, 450
Oxygen utilization rate, 387

P

(p, n) reaction, 47, 50t
P value, 134, 134f, 135, 136-137, 136f, 172
PACs. *See* Picture archival communications systems (PACs).
Pair production, 76-77, 77f, 78t
photon attenuation and, 79, 80f-81f
in radiation detectors, 141-142, 142f
Paired data, 135, 137
Pancake Geiger-Müller counters, 95-96, 95f
Parallel-hole collimators, 202f, 203, 220
collimator resolution and, 222, 222f, 225t
efficiency and, 223
FWHM and, 222, 222f, 227
hole geometry and, 222
source-to-collimator distance and, 223, 224f, 228, 228f
system resolution and, 225
design and performance of, 220-223, 221f, 222f, 224f, 225, 225t, 226f
efficiency of, 222, 224f, 225t
collimator resolution and, 223
hole geometry and, 222
septal thickness and, 223
gamma-ray energy and, 221-222, 225t
hole geometry in, 222, 222f, 224f
line-spread function for, 222-223, 222f, 224f, 225
modulation transfer functions for, 237, 238f
point-spread function for, 222-223, 222f, 224f, 225
in reconstruction tomography, 273
Parallel-hole collimators *(Continued)*
septal thickness in, 203, 203f, 211, 220f-221f
efficiency and, 223
system resolution of, 225, 227
in tomographic imaging, 254-256, 254f, 255f, 256f
with SPECT, 279-281, 285, 288, 288f, 291, 293, 294
Paralyzable counting systems, 168-169, 168f-169f
gamma camera as, 213, 230
Parametric imaging, 372
of glucose metabolism in brain, 400, 401f
Parent nucleus, 19
Parent-daughter decay, 39-42
activity relationships in, 39-42, 39f, 40f, 41f, 42f
Bateman equations for, 39-40, 39f
definition of, 19
in generator, 50, 51, 51t, 52
in no equilibrium, 42
product activity and, 56
in secular equilibrium, 40-41, 40f
in transient equilibrium, 41-42
Partial-volume effects
in PET, 340, 373
in SPECT, 299, 300f, 373
Particulate radiation, 8. *See also* Charged particles.
Partition coefficient, 383, 383f, 395, 396, 399
Passive transport, 389-390
carrier-mediated diffusion and, 389
Patient motion
attenuation correction artifacts and, 359
breath-holding and, 359
image quality and, 234, 266, 359
Pauli Exclusion Principle, 9
Peak detection timing, 115-116
Penetrating radiation, 82-83. *See also* Photons.
absorbed fraction for, 414
definition of, 83
GM counters for, 95
Penetration, septal, 205, 220-221
Pentetreotide, ^{111}In-labeled, 305
Percentage uncertainty, 127, 129
in counting rate, 130, 131, 132, 133
Performance studies
computer, 233
human, 233, 247-251
Perfusion. *See also* Blood flow.
definition of, 386
measurement of, 393, 394, 395
uptake and, 387
Periodic table, 9
Permeability, membrane
diffusion constant and, 389
extraction and, 387, 387f, 389, 389f
Persistence time of phosphor in CRT, 124

Personal computers, 363
MCA boards for, 117
Personnel dosimeters, 440-441, 440f
badge, 440-441, 440f
pocket, 89-90, 90f, 440-441
ring, 440-441, 440f
Pertechnetate, ^{99m}Tc-labeled, 4f, 51, 60, 480
PET. *See* Positron emission tomography (PET).
PET/CT, 4-5, 330, 354-356
advantages of, 332-334, 356-357
applications of
clinical, 355-356, 356f
small-animal, 356, 356f
attenuation correction in, 348, 356-360
image segmentation in, 357
scanners in
clinical, 354-356, 354f-355f
small animal, 356, 356f
scatter correction in, 337, 356-360
PET/MRI, 345-346, 360-361, 361f
Phantoms
for absorbed fraction method, 409, 414, 414f, 415t
bar, 235, 235f
modular transfer functions and, 237-238
computer-simulation, 258f, 263, 264f, 265, 265f, 266f, 267f
in contrast-detail studies, 247-248, 248f, 249f
Cristy-Eckerman, 414, 414f, 415t
dosimetry calculations based on, 414, 414f, 415, 415t
in ROC studies, 248
Rollo, 247-248, 248f
scatter correction based on, 298
spatial resolution and, 234-235, 234f-235f
with bar phantom, 235, 235f, 237-238
detection efficiency in, 166
SPECT images of, 289-290, 291, 298, 298f, 299
volume sensitivity measurement with, 301-302
PHAs. *See* Pulse-height analyzers (PHAs).
Phelps, M.E., 4
Phosphorescence of scintillator solution, 184, 185
Phosphorus-32, 58t, 452
Phoswich detectors, 326, 327f
Photocathodes, 98-99, 98f
temperature and, 184
Photodiodes, silicon, 99-100
avalanche, 100
in PET systems, 332
in compact gamma camera, 207
in intraoperative gamma probe, 193, 193f
Photoelectric effect, 74, 74f, 77-78, 78t
in lead shielding, 144
in photomultiplier tube, 98, 98f, 148
Photoelectric effect *(Continued)*
in radiation detectors, 141-142, 142f
gamma-ray energy and, 147
iodine escape peak and, 144
nonlinearity and, 148
photon attenuation and, 79, 80f-81f
in scintillation detectors, 102, 103
Photoelectrons, 74
in photomultiplier tubes, 98, 100f
energy resolution and, 149-150
Photoemissive substance, 98
Photofraction
definition of, 159
for NaI(Tl) detectors, 159, 160f
in NaI(Tl) well counters, 174, 175f
Photomultiplier (PM) tubes, 98-99, 98f, 100f
of gamma cameras. *See* Gamma cameras: photomultiplier tubes of.
of liquid scintillation counters, 104, 153, 182-183, 206f
noise reduction and, 184
magnetic fields and, 197
of NaI(Tl) detectors, 101-102, 101f-102f
energy resolution and, 148, 149, 150
of NaI(Tl) well detectors, 173, 174f, 178, 180
of PET detectors, 324, 325-326, 325f, 326f, 330, 331, 332
data corrections and, 335
in PET/MRI, 360
power supply for, 122
in SPECT/CT, 351
in SPECT/MRI, 360
Photons, 8. *See also* Annihilation photons; Bremsstrahlung; Gamma rays; X rays.
annihilation, 25, 25f
after pair production, 77, 77f
in annihilation coincidence detection, 307-308, 308f-309f
interactions with matter, 74-78
in radiation detectors, 142, 144, 145-146, 145f, 149, 150, 151, 159
shielding for, 437
attenuation of. *See* Attenuation.
backscattered, 75, 166-167, 167f
bremsstrahlung. *See* Bremsstrahlung.
coherent scattering of, 77
Compton scattering of. *See* Compton scattering.
energies of, 8
energy deposition by, 64, 77-78, 77f, 78t
in radiation detectors, 141, 142f
interactions with matter, 74-78, 78t
pair production and. *See* Pair production.
Photons *(Continued)*
photoelectric effect and, 74, 74f, 77-78, 78t
secondary, 77, 78t, 141-142
transmission measurements for, 78-79, 78f
ultraviolet
in Geiger-Müller counter, 92, 94
in scintillation detector, 99-100
of visible light. *See also* Scintillation detectors.
in Geiger-Müller counter, 92
spectrum of, 8, 8f
Photopeak, 142, 143, 143f, 144, 144f, 145-146, 145f, 146f
baseline shift and, 146, 147r
cascaded gamma emissions and, 162, 163
coincidence detection and, 163
Compton-scattered gamma rays in, 163-164, 164f
crystal size and, 145, 146f
definition of, 142
gamma-ray energy and, 147
photofraction in, 159, 160f
for NaI(Tl) well counter, 174, 175f
pulse pile-up and, 146, 147f
selection of, for gamma cameras, 200, 201f
tail of, with CZT detector, 151
width of, 149
window fraction for, 170
Photopeak detection efficiency
of gamma camera, 211, 212f
intrinsic, of NaI(Tl) well counter, 174, 176f
Picture archival communications systems (PACs), 367, 378
Pile-up. *See* Pulse pile-up.
Pincushion distortion, 199-200, 215f-216f, 216-217
Pinhole collimators, 202-203, 202f, 225-228
advantages and limitations of, 228
collimator resolution of, 225-228, 226f-227f
source-to-collimator distance and, 228, 228f
efficiency of, 225-228, 226f-227f
performance characteristics of, 225-228, 226f-227f
in reconstruction tomography, 274-275
in small-animal SPECT, 284-285, 284f-286f, 302
Pixel depth, 365
Pixelation effects, 234
Pixels, 196-197
addresses of, 364, 364f
definition of, 364
display of
brightness levels in, 364
colors in, 367
on flat-panel display, 124
of gamma camera image, 196-197, 218

Pixels *(Continued)*
in grayscale displays, 367, 368f
in image smoothing, 373, 375f
number of, matrix size and, 365-366, 366f
of parametric image, 372
size of
full width at half maximum and, 234
spatial resolution and, 365-366
of tomographic image, 257
in iterative reconstruction, 273, 275
SNR of, 267, 268, 269
in SPECT, 279, 281, 284, 286f, 289f, 293-294, 296, 297, 299, 301
voxels vs., 364
Planar single-photon imaging, 1. *See also* Gamma cameras.
contrast in, 241, 243f
selected procedures with, 5t
structured noise in, 243
Plastic scintillators, 101, 101t
pulse signals of, 105, 105f
Plateau curves, for Geiger-Müller counters, 94, 95f
PM tubes. *See* Photomultiplier (PM) tubes.
Pocket dosimeters, 89-90, 90f, 440-441
Point-spread function (PSF), 224f, 235, 263
collimator, 222-223, 222f, 224f, 225
convolution as, 489, 492
modular transfer function and, 238
in resolution evaluation, 235
scattering and, 297
in SPECT, 301
Poisson distribution, 126-128, 127f
statistical tests and, 133, 134, 135, 149
Pole zero cancellation, 112-113
POPOP [1,4-di-(2,5-phenyloxazole) benzene], 105
Position logic circuits, 196
Positive ion cyclotron, 48, 48f, 49
Positron (β^+, γ) emission, 25, 26
Positron (β^+) emission, 25, 25f, 26
competitive with EC, 26, 26f
line of stability and, 28
Positron (β^+) emitters
cyclotron-produced, 49, 50, 50t
historical use of, 2, 313t
particle ranges of, 73-74, 73t
properties of, 313t
radiopharmaceuticals labeled with, 60-61
safe handling of, 437, 441
scintillation detectors for, 105, 182-183
Positron decay, 25-26, 25f
Positron emission tomography (PET), 253, 307-343. *See also* Tomographic imaging.
absolute quantification in, 339-340
Positron emission tomography (PET) *(Continued)*
advantages of, 253
annihilation coincidence detection in. *See* Annihilation coincidence detection (ACD).
applications of
clinical, 5t, 341-342, 341f-342f
research, 342, 342f
attenuation correction in, 338-339, 338f
binding potential and, 403
in brain imaging, 330-331, 330f
in breast imaging, 330-331, 331f
calibration factor for, 339-340
coincidence counting rates in, 322-324, 322f, 329-330
random, 322-323, 322f, 329-330
correction for, 336-337
estimation of, 336, 340
scattered, 322-324, 322f, 329-330
correction for, 337-338
true, 322-323, 322f
coincidence logic in, 307
combined with CT scanner, 330
contrast in, 241-242, 253, 336, 337, 346
co-registered images in, 375-376, 377f
current practice of, 4-5
data acquisition for, 332-335
cross-plane, 332, 333f
2-D, 321-322, 332, 333f
3-D, 321-322, 332-334, 333f
for dynamic studies, 335
list-mode, 335
for whole-body scans, 335
data correction for, 335-340
for attenuation, 338-339, 338f
for dead time, 339
normalization in, 335-336
for random coincidences, 336-337
for scattered radiation, 337-338
dead time in, 339
dynamic studies with, 335
of receptor binding, 402
with FDG, 341-342, 342f
Ge-68 rod source in, 328f, 329, 338
historical development of, 4
image reconstruction protocols for, 340-341
for low-contrast imaging, 241-242
multi-slice images in, 262-263, 321-322, 332-334
in neurodegenerative diseases, 341-342, 342f
noise equivalent counting rates and, 340-341, 341f
noncolinearity in, 314, 315f, 316
in oncology, 341
overview of, 1
parametric imaging with, 400, 401f
partial-volume effects in, 340
Positron emission tomography (PET) *(Continued)*
point source response profile in, 319
principles of, 307-324
quantification of, 337, 340, 371f, 372
radiopharmaceuticals for, 60
receptor binding and, 402-403, 402f
regions of interest in, 372-373, 372f, 374f
research applications of, 5
scintillation detectors for, 104, 316, 324-326, 325f, 326f, 327f, 328, 330-332, 337
spatial resolution and, 314-315, 314f
sensitivity of, 308, 319-322
for 2-D systems, 321-322, 332
for 3-D systems, 321-322, 332-334
in small animal imaging, 331-332, 331f, 342, 342f
spatial resolution in, 310, 311f, 312-319, 312f, 313f, 313t, 314f, 315f, 317f, 318f
with block detector, 324-325
with cross-plane data, 332
cut-off frequency and, 319
depth-of-interaction effect in, 316-318
detectors and, 310-312, 311f-312f
with gamma camera, 329-330
geometric efficiency and, 321
positron physics and, 312-316, 313f-315f, 313t
protocols for, 340-341
reconstruction filters and, 319
sampling and, 318-319, 318f
with specialized systems, 330
system resolution in, 314-315
systems for, 324-332
detectors
arrays of, 326-328
block, 324-325, 325f, 327f
detection efficiency of, 321, 322t
geometric efficiency of, 319-322
modified block, 325-326, 326f-327f
multicoincidence operation of, 320-321
phoswich, 326, 327f
quadrant-sharing, 325-326, 326f
types of, 324-332
in whole-body systems, 326-330, 327f
gamma cameras, 327f, 329-330
performance characteristics of, 340-341
scanners, 314, 326-330, 327f
multi-ring, 321-322, 332-334, 333f
septa of, 323, 324, 328f, 329, 332, 334

Positron emission tomography (PET) *(Continued)*
specialized, 330-332, 330f-331f
SPECT systems as, 307, 324
in whole-body systems, 326-330, 327f-328f
3-D reconstruction, 275-276, 276f
time-of-flight, 309-310, 310f
timing resolution in, 307-308
tomographic reconstruction in, 253, 254, 256. *See also* Tomographic imaging.
three-dimensional, 334
whole-body studies with, 335, 340, 340f
with x-ray CT. *See* PET/CT.
Positron probes, 194
Positronium, 25
Positron-labeled radiopharmaceuticals, 60-61
Positrons. *See also* Charged particles; Pair production.
in annihilation coincidence detection
non-colinearity of, 314, 315f, 316
ranges of, 307, 312-315, 313f, 314f, 315f, 316
spatial resolution and, 312-316, 313f-315f, 313t
definition of, 25
interactions with matter, 63
radionuclides emitting, 312, 313t
labeling with, 60-61
ranges of
in ACD, 307, 312-315, 313f, 314f, 315f, 316
average, 73
effective, 313, 313f
Postinjection transmission scans, 338-339
Potassium-40
background radiation from, 184-185
total-body potassium and, 194
Power supplies, high-voltage, 122
PPO (2,5-diphenyloxazole), 105, 187
Preamplifiers, 107-110, 108f
of gamma camera, 219
Precalibrated radionuclides, 35
Precise measurement, 126
Precursors, radionuclide, 58
Pregnancy
dose limits and, 433, 434t
internal dosimetry and, 414
occupational exposure in, 437
Primary ionization events, 141, 142f. *See also* Ionization.
Primary solute, 105, 106
Primary spectrum, 147f, 152f
Probability matrix, 286, 296
Probable error, 127
Probes
β-particle, 194
γ-ray
miniature, 192-194, 193f
Probes *(Continued)*
in oncology, 192-193
radiation detectors for, 193
Production rate, 56
Projection profiles, 254, 254f, 255, 255f, 256f
attenuation correction for, 293, 294
backprojection and, 256, 257, 257f, 259, 259f, 260, 261f, 263, 267
cone-beam data and, 274
fan-beam data and, 273
iterative reconstruction algorithms and, 270f, 272
scatter component in, 298
from transmission scan, 296
Projection slice theorem
definition of, 259
in direct Fourier transform reconstruction, 258-260
in filtered backprojection, 260-262
Projection tools, 369-371, 371f
Projections, 254, 254f
Proliferation, tracers for, 381t
Prompt coincidences, 322-324, 322f, 340
Prompt gamma rays, 45-46
Propagation of errors, 128-130
Proportional counters, 91-92, 92f
backscatter and, 166-167, 167f
dead times of, 168
intrinsic efficiency of, 158-159
limitations of, 166-167
in PET systems, 332
power supply for, 122
pulse signals of, 108t
pulse-height spectrometry with, 153-154
self-absorption and, 166-167, 167f
for β-emitting radionuclides, 167
as gas flow counters, 190
Protein synthesis, tracers for, 381t
Protein-binding assays, 173, 189
Proton deficient nuclides, 17, 28
Protons, 13-14, 13t. *See also* Charged particles.
arrangement of, 14-15
in cyclotron, 48, 49f
decay modes involving. *See also specific modes*.
β^+ emission as, 25
β^- emission as, 20
electron capture as, 24
energy levels of, 10f, 14-15
equivalent dose of, 408t
forces on, 14-15
nuclear stability and, 14-18, 16f-17f
number of, 13
as particulate radiation, 8
properties of, 13, 13t
in shell model, 14
Pseudocolor scale, 367, 368f
PSF. *See* Point-spread function (PSF).
PTSM [pyruvaldehyde bis(N-methy lthiosemithiocarbazone)], 381t, 394
Pulse mode, 107
Pulse pile-up, 112-113, 112f, 146, 147f
dead time losses and, 168
with gamma cameras, 213-216
correction of, 214-216
counting losses and, 213-214, 213f
dead time losses and, 213-214
image distortion and, 214-216, 214f-215f
in PET, 339
in pulse-height spectrometry, 146, 147f
pulse-tail extrapolation for, 214-216, 215f
Pulse resolving time. *See* Dead time/dead time losses.
Pulse shaping
by amplifier, 111-112, 112f
by preamplifier, 107-108, 108t
in rate meter, 120
Pulse signal of various radiation detectors, 107, 108t
Pulse-height analyzers (PHAs), 113-118, 114f, 115f, 116f, 117f
dead time losses and, 168
energy-selective counting with, 156, 158, 159, 160f
of gamma camera, 142-147, 143f, 145f, 146f, 147f, 151
energy resolution and, 212, 212f, 213
image corrections with, 218
image contrast and, 240, 241f
multichannel, 113, 116-118, 116f
of liquid scintillation counters, 184
of NaI(Tl) well counters, 173, 180f, 181
of semiconductor detectors, 190
as nonparalyzable systems, 168
object scatter and, 144, 145, 147
in PET, 337
principles and design of, 113, 114f
processor chip for, 363
single-channel, 113-116, 114f
dead times of, 168
NaI(Tl) well counters and, 173, 178, 181
timing methods for, 114-116, 115f
spectral blurring in, 144, 148-151
window fractions and, 170-171
Pulse-height spectrometry, 116f, 117, 141-154
dead time losses in, 168, 170
with liquid scintillation counters, 141, 153, 153f, 184, 185f
multichannel analyzer in, 113, 116-118, 116f, 141
with NaI(Tl) detectors, 142-151
actual spectrum for, 143-145, 143f-147f
counting rate and, 146, 147f

Pulse-height spectrometry *(Continued)*
detector size and, 145-146, 146f
energy linearity and, 147-148, 148f
energy resolution and, 148-151, 149f. *See also* Energy resolution.
gamma-ray energy effects in, 146-147, 147f
ideal spectrum for, 142-143, 143f
primary spectrum for, 147f
scatter spectrum for, 147f
principles of, 141-142
with proportional counters, 153-154
quality assurance checks of, 172
with semiconductor detectors, 151-153, 151f-152f
two-energy window analysis and, 184
Pulse-resolving time. *See* Dead time/dead time losses.
Pulse-tail extrapolation, 214-216, 215f
Purity
chemical, 59
radiochemical, 59
radionuclidic, 58
semiconductor detectors of, 190, 191
PXE (phenylxylethane), 105, 187

Q

Q. *See* Transition energy (*Q*).
Quadrant sharing, 325-326, 326f
Quality assurance, 171-172. *See also* Image quality.
for gamma cameras, 228-231
for NaI(Tl) well counters, 178
for radiopharmaceuticals, 182
for SPECT, 302-303
Quanta, 8
Quantities, physical, 7-8
Quantum efficiency, 98, 99f
Quantum mottle, 243
Quantum numbers, 9, 10f, 14
Quench correction, 106
automatic external standardization method for, 186-187, 187f
channel ratio method for, 186
internal standardization method for, 186, 186f
for liquid scintillation counters, 185-187, 186f-187f
Quenching, 106
Quenching gases, 93-94

R

Rad, 407
Radiation, 8-9. *See also* Charged particles; Photons.
accidental ingestion of, 437-438
background
effective dose from, 431
sources of, 177-178, 431
Radiation *(Continued)*
Cerenkov, 68-70
characteristic, 10-13, 11f, 12t
definition of, 8
GM counters for, 92
electromagnetic, 8-9, 66
emission of. *See* Emissions.
forms of, 8, 8f
ionizing, 63
biologic effects of, 78, 427-428
definition of, 63, 87
secondary, 74
long-term health effects of, 427
particulate, 8
penetrating, 82-83
scattered. *See* Scattered radiation.
Radiation biology, 407
Radiation counting rate. *See* Counting rates.
Radiation counting systems. *See* Counting systems.
Radiation detectors, 87-106, 122. *See also* Gas-filled detectors; Scintillation detectors; Semiconductor detectors; specific types.
amplifiers for, 110-113
for annihilation coincidence detection, 309-310
coincidence detection and, 162-163
coincidence units and, 121-122
dead areas of, 267f. *See also* Dead time/dead time losses.
digital counters and, 119-121
efficiency of, 155-166. *See also* Detection efficiency.
energy deposition in, 91, 141, 142
high-voltage power supplies for, 122
instrumentation for, 107-124
nuclear instrument modules and, 122-123
as paralyzable systems, 168-169, 168f-169f
phoswich, 326, 327f
preamplifiers in, 107-110, 108f
in pulse mode, 107
pulse output of, 107, 108t
pulse-height analyzers and, 113-118, 114f
quadrant-sharing, 325-326, 326f
quality assurance for, 171-172
rate meters and, 119-121
signal output of, 108t
spectral blurring with, 144, 148-151
thickness of
depth of interaction and, 316-317, 317f
intrinsic spatial resolution and, 210, 211f
time-to-amplitude converters and, 118-119, 119f
Radiation dose, 407-408. *See also* Radiation safety.
absorbed, 432-435, 433t
air kerma and, 434, 438-439
Radiation dose *(Continued)*
average, 414, 424, 427, 428
estimation of, 434
radiation safety and, 427, 428, 429t, 434t
scaling factor for, 430, 430f
units for, 428-431
air kerma and, 434-436. *See also* Air kerma.
in bone, 434
calculation of. *See* Absorbed fraction (MIRD) method; Radiation dosimetry, internal.
choice of radionuclide and, 57
contaminants and, 58
cumulated activity and, 409-410, 424
definition of, 407
distance from source and, 435-436
dose calibrators for, 89, 89f, 189-190, 437
effective, 417, 425t, 429t
from background radiation, 427
equivalent, 407-408, 429t
air kerma and, 434-436
distance from source and, 435-436
half-life and, 57, 58
information sources for, 422
internal. *See also* Radiation dosimetry, internal.
avoidance of, 440-441
limits on, 431-432, 432t, 433, 434t
mean, per unit cumulated activity, 415-417
for F-18, 422t-423t
for I-131, 420t-421t
for Tc-99m, 418t-419t
occupational limits for, 431-433, 434t. *See also* Radiation safety.
scaling factor for, 430, 430f
surface, 409
tissue weighting factors for, 417, 425t
units of, 407-408, 408t, 428, 429-430
whole-body (total-body), 417, 425t
Radiation dose-modifying factors, 428
Radiation dosimetry, internal, 2, 407-425. *See also* Organs.
absorbed fraction in, 413-414, 414f
specific, 414-415
anatomic models for, 409, 414, 414f, 415t, 424. *See also* Phantoms.
basic procedure in, 408-409, 409f
classic method in, 407
cumulated activity in, 409-412, 410f, 411f
average absorbed dose and, 414, 424, 427, 428

Radiation dosimetry, internal *(Continued)*
mean dose per unit of, 415-417
for F-18, 422t-423t
for I-131, 420t-421t
for Tc-99m, 418t-419t
problems in determination of, 424
dose in. *See* Radiation dose.
effective dose equivalent in, 417, 425t, 427, 429t, 478-479
effective dose in, 417, 425t, 427, 429t, 433t
equilibrium absorbed dose constant in, 412-413
future directions for, 424-425
information sources for, 422
limitations of MIRD method in, 424-425
MIRD Committee and, 407, 414
quantities and units in, 407-408, 408t
reciprocity theorem in, 414-415
therapeutic applications of, 416-417, 428
Radiation energy losses, 64-65, 66f-67f
Radiation hormesis, 431
Radiation losses, 64-66, 67, 67f, 68
Radiation monitoring, 439-441, 440f. *See also* Radiation safety; Survey meters.
laboratory monitors for, 440
personnel dosimeters for, 89-90, 90f, 440-441, 440f
survey meters for, 89, 89f, 439-440
wipe testing for, 441
Radiation safety, 2, 427-442. *See also* Health physics.
air kerma and, 428-431, 434-435
airborne materials and, 432, 432t, 438
background radiation and, 427
biologic effects and, 427-428
decontamination in, 439
distance from source and, 435-436
dose-modifying factors and, 428
exposure and, 428-431
general public and, 431, 432, 433t, 434t
government regulations for, 431-433
advisory boards and, 433
for airborne radioactivity, 432, 432t-433t
for dose limits, 431-432, 435-436
Nuclear Regulatory Commission (NRC) and, 431, 432, 433
for record keeping, 432-433
for restricted and unrestricted areas, 431
for sewage disposal, 432, 433t
information sources for, 427-428
for internal sources, 437-438
laboratory design and, 438
Radiation safety *(Continued)*
material handling and, 433-439
ALARA concept and, 433-434
dose reduction from external sources, 434-435
monitoring and. *See* Radiation monitoring.
NCRP recommendations for, 431, 433, 434t
quantities and units in, 428-431, 429t, 430f
for radioactive gases, 438
shielding and. *See* Shielding.
sources of exposure and, 427
spills and, 437
TDS rules and, 436-437
waste disposal and, 439
Radioactive decay, 19-29. *See also* Activity; Radionuclides.
by alpha emission, 26-28
average lifetime and, 34
chemical properties and, 19-20
decay constant in, 31, 32, 33, 34
decay factors in, 32-33, 33f
approximation to, 32, 32f, 33
determination of, 34-35
effective, 35-37, 36f
tables of, 34, 34t
decay scheme diagrams for, 20-21, 20f
of important radionuclides, 449-475
decay series and, 27-28, 27f
definition of, 19
general concepts of, 19
half-life and, 33-34
image-free decay corrections and, 35-36, 36f
by internal conversion, 22-24
isobaric, 20
isotope effect and, 20
line of stability and, 16, 16f, 28
mass-energy conversion in, 19
transition energy and, 19, 20, 20f, 21, 21f, 24
of mixed samples, 38-42, 39f
parent-daughter, 39-42. *See also* Parent-daughter decay.
of unrelated species, 38-39, 39f
modes of, 20-28. *See also* specific modes.
alpha-particle emission as, 26-28
by β^+, γ emission, 25-26
by β^-, γ emission, 21-22, 22f
by β^+ emission, 26-28
by β^- emission, 20-21f
competitive β^+ and EC as, 26
EC, 24-25
(EC, γ), 24-25
internal conversion as, 22-23, 23f
by isomeric transition, 22-24
nuclear fission, 28
overview of, 19
positron emission, 25-26, 25f
rate of, 31
series, 27-28, 27f
transition energy in, 19, 20, 20f, 21, 21f, 22, 24
Radioactive disintegration, 16
Radioactive gases, safety measures for, 438
Radioactive spills, handling of, 438
Radioactive tracers, stability of, 19-20
Radioactive waste disposal, 439
Radioactivity. *See also* Radioactive decay.
discovery of, 2, 9
natural, as background, 177, 427, 432
Radioactivity, from internal sources, 437-438. *See also* Radiation dosimetry, internal.
Radiobiology, 407
Radiochemical purity, 59
Radioimmunoassays, 173, 182, 189
Radioisotope, 19. *See also* Isotopes; Radionuclides.
Radioligands, 401
Radionuclide imaging, 195-196. *See also* Gamma cameras; Tomographic imaging.
Radionuclides, 19
Radionuclides. *See also* Radiopharmaceuticals.
activity of. *See* Activity.
average lifetime of, 34, 82
cumulated activity and, 410, 411f
as calibration standards, 164-166, 165t
carrier-free, 37-38
chemical properties of, 58
Compton-scattered photons from, 75-76, 75t
contaminants in
detection of, 39
effects of, 58
in generator systems, 53, 58
decay of. *See* Radioactive decay.
definition of, 19
dose calculations for, 424-425
dose-rate constants of, 434, 435t
emissions from, 57, 58t
fission fragments of, 28, 44-45, 45f
half-life of, 33-35, 57, 58t
cumulated activity and, 410-412
information sources for, 28, 29f
line of stability and, 16, 16f, 28
medically important, 57-59, 58t
characteristics of, 57-59, 58t, 449-475
cyclotron-produced, 49-50, 50t
generator-produced, 3, 24, 50-53, 51f-52f, 51t
neutron-activated, 45-47, 46t
metastable, separation of, 24
naturally occurring, 427
neutron-activated, 45-47, 46t
positron-emitting, 312, 313t
labeling with, 60-61
precalibrated, 35
production of, 43-61
in accelerators, 47-50, 49f-51f, 50t
charged-particle, 47, 50t

Radionuclides *(Continued)*
activity buildup and decay in, 56
in cyclotrons, 47-50, 50t
equations for, 53-57
in generators, 3, 24, 50-53, 51f-52f, 51t
contaminants and, 53, 58
safe handling of, 433-434
historical perspective on, 2
in reactors, 43-47, 46t
properties of, 19, 57-59, 58t
purity of, 58
specific activity of, 57-58
for transmission scans
in PET, 338, 339, 342
in SPECT, 294-295, 296, 300f
Radionuclidic purity, 58
semiconductor detectors of, 190-191
Radiopharmaceuticals, 1, 2, 5t, 59-61, 379, 380
analog, 60, 61, 382
applications of, 5t, 60t
therapeutic, 61
approval process for, 2, 424
assays of
semiconductor detectors for, 191
well counters for, 182
biologic half-life of, 59, 417
chemical properties of, 19-20
in clinical nuclear medicine, 61
commonly used, 5t, 60t, 381t
cumulated activity of. *See* Cumulated activity.
definition of, 57
diffusible, 394-395
distribution of, 409
dose estimates for, 425, 478-479
dosimetry for, 2
examples of, 5t, 60t, 381t
for FDG-PET, 341-342
ideal, 380
impurities in, 59
assay of, 191
in ^{99m}Tc, 51-53, 58, 85
labeling strategies for, 59-60
as metabolic tracers, 380. *See also* Fluorodeoxyglucose (FDG); Methylene diphosphonate (MDP); Oxygen-15.
microdosimetry of, 425
nondiffusible, 394
positron-labeled, 60-61
production of, 57-61
properties of, 59-61
purity of, 59
radionuclides for. *See* Radionuclides: medically important.
safety of, 59
specific activity of, 59
for SPECT, 304-306
^{99m}Tc-labeled, 60, 60t. *See also* Technetium-99m.
therapy applications of, 61, 425
in tracer kinetic modeling, 380-382, 381t
Radiotracer(s). *See* Radionuclides; Radiopharmaceuticals; Tracer kinetic modeling.
Radium-226, 27-28
curies and, 32
Rainbow scale, 367, 368f
Ramp converters, 117-118, 117f
Ramp filter, 260-261, 261f-262f
image quality and, 268, 269, 301
in SPECT, 301
Random coincidences, 322-323, 322f, 329-330
corrections for, 336-337
estimation of, 336, 340
with gamma camera, 332
septa and, 332
Random error, 125-126, 128
statistical significance and, 130, 131, 134
Random noise. *See* Statistical noise.
Range of charged particles, 70-74, 70f, 72f-73f, 73t
average, 73-74
effective, 313, 313f
extrapolated, 71-74, 72f-73f
mean, 70
Range straggling, 70, 70f
Rate constants, 384-385, 384f, 385f, 390-391, 390f
of enzymatic reaction, 396
Rate detectors, coincidence units and, 121-122
Rate meter time constant, 120
Rate meters, 119-121
analog, 120-121, 120f
logarithmic, 121, 121f
Rayleigh scattering, 77
RBCs. *See* Red blood cells (RBCs).
RC pulse shaping, 111-112, 112f
RCs. *See* Recovery coefficients (RCs).
Reaction rate, of enzymatic reaction, 396, 398f
Reactors, nuclear, 43-44, 44f
neutron-capture cross sections in, 54
principles and design of, 43-44, 44f
radionuclide production in, 43-44, 46t
Receiver operating characteristic (ROC) studies, 248-251, 250f
Receptor ligand assays, 401-403, 402f, 404f
tracers for, 381t
Recoil electrons, 74-76, 75f, 75t, 78t, 144
pulse-height spectrum and, 142, 144
Reconstruction algorithms. *See* Tomographic imaging: mathematical techniques in.
Reconstruction filters, 260-261, 263, 264f
Hann, 261, 262f
in PET, 319
ramp, 260-261, 261f-262f
in SPECT, 301
Reconstruction filters *(Continued)*
Shepp-Logan, 261, 262f, 263-265, 264f
spatial resolution and, 267, 269
in PET systems, 319
in SPECT systems, 302, 303f
Reconstruction tomography
backprojection in, 256-258, 266f
collimators in
cone-beam, 274-275, 274f
fan-beam, 273-274, 274f-275f
parallel-hole, 273
cone-beam, 273-275, 274f
coordinate systems for, 255, 256f
direct Fourier transform, 258-260, 259f-260f
emission CT in, 253
expectation-maximization reconstruction in, 272-273
fan-beam, 273-276, 274f-275f
Feldkamp algorithm in, 275
filtered backprojection in, 260-262
image quality in, 263-270
coverage and consistency requirements and, 266
Nyquist frequency and, 263
sampling and, 263-265
iterative reconstruction algorithms in, 262, 270-273. *See also* Iterative reconstruction.
multi-slice imaging in, 262-263
noise in, 266-268
overview of, 254-256
in PET, 319, 340-341
3-D, 275-276, 276f
projection profiles for, 254-256, 254f-256f
sinograms and, 255-256, 256f
ramp, 260-261, 262f
in SPECT, 301
response characteristics and, 254-256, 254f
Shepp-Logan, 261, 262f, 263-265, 264f
in SPECT, 301-303
transmission CT in, 253
in x-ray CT, 348-350, 349f
Record-keeping regulations, 432-433
Recovery coefficients (RCs), 299, 300f
Rectilinear scanner, 195-196
Red blood cells (RBCs)
in cardiac studies, 392, 392f
clumping of, by aluminum ion, 53
distribution volume of, 383
Reference sample technique, 393
Reference scan, 295
Regions of interest (ROI), 372-373, 372f
kinetic modeling and, 379, 391, 400, 404
time-activity curves and, 373, 374f
Registration algorithm, 296

Regression analysis, 390
linear, 139-140
in tracer kinetic modeling, 390
Regulations, U.S. government, 431, 432, 433, 435-437, 436t-437t
Rem, 408, 430
Renal function, evaluation of, 379
Renkin-Crone model, 387-388, 388f-389f, 390-391
Reproducibility of measurements, 126
Resistor-capacitor pulse shaping, 111-112, 112f
Resolution. *See* Energy resolution; Spatial resolution; Timing resolution.
Resolution volume of SPECT system, 301-302
Respiratory motion. *See* Motion blurring.
Restricted areas, 431
radiation levels in, 431-432
Rest/stress studies, 303
Ring dosimeters, 440-441, 440f
Ringing artifacts, 486
Ripple in HV power supply, 122
Rise time
of electronic signal, 111, 112
of scintillator light output, 309
ROC studies. *See* Receiver-operating characteristic (ROC) studies.
Rod standards, 164, 165f
Roentgen, Wilhelm, 2
Roentgens, 89, 90, 429-430
ROI. *See* Regions of interest (ROI).
Rollo phantom, 247-248, 248f
Root mean square effective range, 314
Rose criterion, 244, 269
Rubidium-82, properties of, 58t
Rutherford, Ernest, 9
Rutherford atomic model, 9

S

Safety. *See* Radiation safety.
Safety concerns. *See* Radiation safety.
Sagittal sections, orientation of, 369, 370f
Sample volume
with dose calibrator, 189-190
with NaI(Tl) conventional detector, 182
with NaI(Tl) well counter, 174, 175-177, 177f
Samples, dark adaptation of, 185
Sampling, 263, 264f, 265-266, 265f, 481, 482, 484, 487
in annihilation coincidence detection, 318-319, 318f
performance measurement and, 301
pixel size and, 366
preparation for liquid scintillation counters, 106, 187-188
SNR and, 268
Sampling interval. *See* Angular sampling intervals; Linear sampling distance.
Sampling theorem, 263, 366, 483, 484, 485
Saturation region, 87-88, 88f
Saturation specific activity, 56
Saturation voltage, 87-88, 88f
Scalers, 119-120
dead times of, 168
Scaler-timers, 119-120, 119f
dead time losses in, 168
Scaling factor, for absorbed dose, 427, 430
Scanner, rectilinear, 195-196
SCAs. *See* Single-channel analyzers (SCAs).
Scatter coincidences, 322-324, 322f
with 3-D data acquisition, 332, 334
with gamma camera, 329-330
septa and, 329
transmission scanning and, 339
uncertainty in, 336, 337
Scatter correction
in PET, 337-338
in SPECT, 296-299, 297f, 298f, 302
Scatter window, 298, 298f
Scattered radiation, 166-167, 167f
background counting rates and, 240-241, 241f
backscattered, 75, 143f, 144, 166-167, 167f
beam geometry and, 80, 81, 81f, 84
coherent, 77
in SPECT, 297
Compton-scattered. *See* Compton scattering.
detection efficiency and, 156, 163-164
downscattered, 296
in gamma camera, 200, 204, 205, 209
counting losses and, 213-214, 213f
energy resolution and, 212
as multiple scattering, 209, 210
image contrast and, 240-241, 242f
object scattered, 144-145, 205
in PET, 322-323, 322f, 329-330
correction for, 337-338
in PET/CT, correction of, 337, 356-360
in pulse-height spectrometry, 141, 212-213
Rayleigh scattering and, 77
scatter windows and, 298, 298f
in SPECT, 286, 296, 299, 302
correction of, 296-299
object scatter as
with gamma camera, 205, 205f
with Ge(Li) detector, 152f
with NaI(Tl) detector, 144, 145, 147, 147f, 152f
Scattered radiation *(Continued)*
in vivo probe measurements and, 192
window fraction and, 170
in SPECT/CT, correction of, 356-360
in x-ray computed tomography (CT), 349
Scintillation cameras, timing methods for, 114-115
Scintillation detectors, 97-106. *See also* Radiation detectors.
amplifiers for, 111
for intraoperative gamma probes, 194
NaI(Tl), 100-103, 101f-103f, 101t. *See also* NaI(Tl) detectors.
for PET systems, 104, 316, 324-326, 325f, 326f, 327f, 328, 330-332, 337
spatial resolution and, 314-315, 314f
photodiodes in, 99-100
photomultiplier tubes for, 98-99, 100f-101f, 101-102
with inorganic scintillators, 100-103, 101f-103f
with organic scintillators, 105f
power supplies for, 122
preamplifiers for, 109, 110
principles and design of, 97-98, 98f
spectral blurring with, 148
time-to-amplitude converters for, 118
Scintillators, 97
background noise associated with, 184
effective atomic number of, 103
energy response of, nonlinear, 148, 149-150
inorganic, 100-103, 101f, 101t, 102f, 103f
NaI(Tl), 100-103, 101f-103f, 101t. *See also* NaI(Tl) detectors.
for PET, 316, 322t, 324, 326
properties of, 101t, 103, 103f
selection of, 103
organic, 104-106
in liquid solution, 97, 104-106, 106f, 185, 187, 188
plastic, 105, 105f
solid, for flow counter, 187
SD. *See* Standard deviation (SD).
Secondary electrons, 63, 64f, 66, 67f, 78t
in photomultiplier tubes, 98-99, 100f
Secondary emission in photomultiplier tube, 98
Secondary ionization, 63, 64f, 141-142, 142f
charged-particle interactions and, 63, 68
photon interactions and, 77, 78t, 141-142

Secondary ionizing radiation, 74
Secondary photons, 77, 78t, 141-142
Secondary solute, 105, 106
Secular equilibrium, 40-41, 40f
Segmentation, image, 357, 375, 377f
Self-absorption, 167, 167f
  quench correction and, 187
Semiconductor detectors, 96-97, 97f, 190-192, 191f. *See also* Radiation detectors.
  advantages of, 96, 190-191, 240
  amplifiers for, 111, 112, 113
  applications of, 190-192
  cadmium telluride, 96-97
  cadmium zinc telluride, 96-97
  dead times of, 168
  design of, 97, 97f
  detection efficiency of, 151, 158, 164, 190
  efficiency of, 158, 190-191
  energy resolution of, 151-152, 152f, 190-192, 191f, 240
  for gamma-ray probes, 193
  germanium, 96-97
  intraoperative gamma probe as, 193f, 194
  limitations of, 96, 102, 190
  lithium-drifted, 96-97, 97f
  power supplies for, 122
  preamplifiers for, 107-110, 108f
  pulse signals of, 108t
  pulse-height spectrometry with, 151-153, 151f-152f
  silicon, 96-97
    applications of, 190
    in scintillation detectors, 99-100
Semiconductor photodiodes. *See* Silicon photodiodes.
Sensitivity
  of collimator
    in gamma camera, 223, 224f, 225t, 227, 231
    lesion detectability and, 246, 247f
  of PET, 308, 319-322
    with 2-D data acquisition, 321-322, 332
    with 3-D data acquisition, 321-322, 332-334
  of receiver operating characteristic, 249
Sentinel nodes, gamma-ray probes for, 192-193
Septal penetration, 205, 220-221
  background counting rates and, 240
  image contrast and, 240-241, 242f
  line-spread function and, 240-241, 242f
  pinhole collimators and, 227
Septal thickness in collimators, 203, 203f, 211, 220-221, 220f-221f
Series decay, 27-28, 27f
Sestamibi, ^{99m}Tc-labeled, 5t, 60t
  blood flow measurement with, 381t
  dose estimates for, 480
  SPECT imaging with, 5t, 303f, 304, 304f, 305
Sewage, dose limits and, 432, 433t
Shallow-dose equivalent, 432
Shell model of nucleus, 14
Shells, electron, 9-13
Shepp-Logan filter, 261, 262f, 263-265, 264f
Shielding, 82t, 436-437, 436f
  of α particles, 71
  background counting rates and, 240
  backscatter from, 144
  beam geometry and, 82, 83
  of β emitter, 65, 66f, 437
  Bremsstrahlung, 65, 67f
  of dose calibrators, 189-190, 189f, 437
  effectiveness of, 437
  lead. *See* Lead shielding.
  methods of, 436-437, 436f
  Mu-metal, 99, 101f
  for NaI(Tl) well counters, 177-178
  natural radioactivity in, 177-178
  pulse pile-up and, 214, 215f
  for radiation safety, 436-437, 436f
  TDS rules and, 436
  tenth-value thickness and, 82, 82t, 437
  of whole-body counting chambers, 194
  x-ray peaks caused by, 144, 151
Shunt, intracardiac, detection of
  with labeled microspheres, 394
  with labeled RBCs, 392
SI. *See* specific ionization (SI).
SI units. *See* Systeme International (SI) units.
Sievert (Sv), 408, 417, 428, 430
Signal amplification. *See* Amplifiers; Preamplifiers.
Signal-to-noise ratio (SNR), 110. *See also* Noise.
  amplifier time constant and, 110
  in filtered backprojection, 260-261, 263, 264f
  image smoothing and, 373, 375f
  preamplifier location and, 110
  in time-of-flight PET, 309, 310
  in tomographic reconstruction, 261, 263, 266-268
Silicon detectors, 96-97. *See also* Radiation detectors; Semiconductor detectors.
  energy resolution of, 190
  instrinsic efficiency of, 158
  lithium-drifted, 89t, 96-97, 97f
  in scintillation detectors, 99
Silicon photodiodes, 99-100
  avalanche, 100, 332
  in compact gamma camera, 207
  in gamma-ray probes, 193, 193f
Simple backprojection, 256-258, 266f. *See also* Reconstruction tomography.
  filtered backprojection vs., 260-261
Simultaneous emission/transmission scans in PET attenuation correction, 338-339
Single escape peaks, 144, 145f
Single photon emission computed tomography (SPECT), 253, 279-306. *See also* Tomographic imaging.
  advantages of, 253
  artifacts in, 286, 302
  attenuation in, 285-293, 291t-292t
    conjugate counting and, 287
    correction of, 293-294
      Chang multiplicative method, 294, 294f, 296, 297f
      scatter correction and, 296-299, 298f
    transmission scans and, 294-296, 295f-297f
  attenuation maps for, 294-296, 296f
  binding potential and, 403
  blank scans in, 295
  blood flow measurements with, 393, 395
  in brain imaging, 280-281, 282f, 304-305, 304f
  in cancer, 305-306
  in cardiac imaging, 281-283, 303, 305f, 306
  center of rotation in, 302-303
  CERASPECT system for, 280-281, 282f
  clinical applications of, 303-306, 303f-305f
  collimators in
    converging, 279-280
    parallel-hole, 279-281
  combined with x-ray CT. *See* SPECT/CT.
  contrast in, 241-242, 243f, 297, 299
  co-registered images in, 376
  current practice of, 4-5
  3-D, 364
  detector head orbits in, 280, 280f
  distortion sources and, 286
  downscatter in, 296
  dynamic
    FASTSPECT system for, 279-278, 284, 286f
    for receptor binding studies, 402
  flood-field uniformity in, 302
  gamma cameras for, 279-280
  historical development of, 4
  image quality in, 302-303
  image reconstruction in, 301-303
  imaging speed in, 280-281
  limitations of, 280

Single photon emission computed tomography (SPECT) *(Continued)*
for low-contrast imaging, 241-242
multihead systems for, 280f, 281-299
multiple detector heads in, 279
multislice images in, 262-263
performance characteristics of, 299-303
count-rate performance, 302
dead time, 302
energy resolution, 302
spatial resolution, 301
volume sensitivity, 301-302
practical implementation of, 285-299
attenuation corrections in, 293-294, 294f
conjugate counting in, 287, 288f
idealized assumptions and, 285-286
partial-volume effects in, 299, 300f, 373
scatter corrections in, 296-299, 297f, 298f, 302
transmission scans in, 294-296, 295f-297f
vs. idealized assumptions, 286
quality assurance for, 302-303
quantitative images in, 372
radiopharmaceuticals for, 304-306
recovery coefficients for, 299, 300f
reference scans in, 295
regions of interest in, 372-373
research applications of, 3, 403
sensitivity of, 308, 321-322
in small-animal imaging, 283-285, 286f, 305f, 306
spatial resolution in, 280, 280f, 281, 283, 284, 288, 289, 298, 299, 300f, 301
SPECT/CT vs., 351-352
spillover in, 299
SPRINT II system for, 280-281, 282f
system alignment in, 302-303
systems for, 279-281, 280f, 282f, 283-285, 283f, 284f, 285f, 286f
used for PET, 307, 324
tomographic reconstruction in, 253, 254, 255, 256
volume sensitivity in, 301-302
Single photon planar imaging, 1, 5t, 241, 243, 243f. *See also* Gamma cameras.
Single-channel analyzers (SCAs), 113-116, 114f, 118, 122
counting rate and, 146-147
dead times of, 168
of NaI(Tl) probe system, 207
NaI(Tl) well counters and, 173, 178, 181
for radiochemical identification, 181
Singles method for random coincidences, 337
Sinograms, 255-256, 256f, 270f, 271, 276
Skin. *See also* Organs.
contaminated, 439
dose to, 428, 432, 434, 434t
Slant-hole collimators, 203
Slice thickness, 301
in PET, 329
in SPECT, 301
Slow neutrons, 43-44
Small-animal imaging
3-D iterative reconstruction in, 276
gamma cameras for, 207-208
PET in, 331-332, 331f, 342, 342f
PET/CT in, 356, 356f
SPECT in, 283-285, 286f, 305f, 306
SPECT/CT in, 352-354, 353f
Smoothing, image, 373, 375f
Sn-113, as calibration standard, 165t
SNR. *See* Signal-to-noise ratio (SNR).
Sodium-22, 165t
Sodium iodide, 479t
Sodium iodide detectors. *See* NaI(Tl) detectors.
Sokoloff deoxyglucose method, 397, 400
Somatostatin receptors, 2, 305
Source organs, 408, 413-414, 415, 416, 418t-424t
Source-to-collimator distance
collimator resolution and, 223, 224f, 227-228, 227f-228f
modulation transfer function and, 238, 238f
in SPECT, 284
Spatial frequency, 236
Fourier transform and, 260f, 263, 481, 483, 484, 485f, 486f, 487, 492
pixel size and, 366
resolution and, 236, 237-238, 237f, 238, 239f
Spatial frequency space. *See* k-space.
Spatial linearity of gamma cameras, 229-230
Spatial resolution, 233-239. *See also* Image quality.
axial, 301
background subtraction and, 242-243
collimator, 234. *See also* Collimator resolution.
contrast enhancement and, 242-243
cut-off frequency and, 319
definition of, 209-211, 233-234
detectability and, 246-247
evaluation of, 234
full width at half maximum and, 235-236
line-spread function in, 235
modulation transfer function in, 233, 236-237, 237f-238f
objective, 234-239
Spatial resolution *(Continued)*
phantoms in, 234-235, 234f-235f
point-spread function in, 235
spatial frequency in, 245
subjective, 234
factors affecting, 233-234, 235f
in-plane, 301
intrinsic, 234
Compton scattering and, 209-211, 210f-211f
detector thickness and, 210, 211f
full width at half maximum and, 210-211, 221, 225t, 229
of gamma cameras, 209-211, 210f-211f, 219, 234
bar phantom and, 235, 235f
in coincidence detection, 310, 311f-312f
measurement of, 229
MTF for, 238
in PET systems, 329
in SPECT systems, 299, 300f
system resolution and, 229
γ-ray energy and, 210, 210f
limits on, 209-210
measurement of, 210, 229
optimum, 210-211
system resolution and, 210-211, 225, 227
lesion detectability and, 248, 249f
linear sampling distance and, 263, 365-366, 373
matrix size and, 365-366, 366f
patient motion and, 234
in PET. *See* Positron emission tomography (PET): spatial resolution in.
pixel size and, 365-366
pixelation effects and, 234
reconstructed, measurement of, 301. *See also* Reconstruction tomography.
smoothing filter and, 375f
in SPECT, 280, 280f, 281, 283, 284, 288, 289, 298, 299, 300f, 301
system resolution as. *See* System resolution.
tomographic reconstruction and collimator types and, 273, 279
cutoff frequency and, 263, 264f, 301, 319
with iterative algorithms, 273-274
sampling and, 265, 266, 267
transaxial, 301
in x-ray CT, 349
Specific absorbed fraction, 414-415
Specific activity, 37-38
carrier-free, 37-38
in nuclear medicine, 38, 56
of radionuclides, 57-58
of radiopharmaceuticals, 59
saturation level of, 56
Specific ionization (SI), 68, 69f, 71

Specificity of receiver operating characteristic, 249
SPECT. *See* Single photon emission computed tomography (SPECT).
SPECT/CT, 4-5
  advantages of, 332-334, 356-357
  applications of
    clinical, 351-352, 353f
    research, 353f, 354
  attenuation correction in, 356-360
    image segmentation in, 357
  detectors in
    clinical, 350-352
    small-animal, 352-354
  gamma cameras in, 350f, 351, 352f
  sampling in, 349
  scanners for
    clinical, 350-352, 350f, 352f-353f
    small-animal, 352-354, 353f
  scatter correction in, 356-360
  vs. SPECT, 351-352
SPECT/MRI, 360-361
Spectral blurring, 144, 148-151. *See also* Energy resolution.
Spectrometry. *See* Pulse-height spectrometry.
Spillover, 299
Spills, safety measures for, 438
Spontaneous fission, 43
Spontaneous radioactive decay, 19
SPRINT II system, 280-281, 282f
Sr-85, as calibration standard, 165t
Stable nuclides, 14-18, 16f-17f, 27, 28
Standard deviation (SD), 128, 134, 135-136
  of gaussian spectral curve, 149
Standards, measurement, 125. *See also* Calibration sources.
Statistical analysis, 125-140. *See also* Measurements.
  applications of, 130-133
    background effects, 131
    counting measurement differences, 130-131
    counting rates, 130-133. *See also* Counting rates.
    counting system comparisons, 132
    effects of averaging, 130
    estimating counting times, 132
    minimum detectable activity, 131
    optimal division of counting times, 133
  chi square test in, 133-134, 134f
  confidence intervals in, 127, 127t
  constant multipliers in, 129
  correlation coefficient in, 139-140
  counting system comparison and, 132
  dead time losses and, 171
  frequency distributions in, 126, 127f, 128
Statistical analysis *(Continued)*
  Gaussian distribution in, 127f, 128
  linear regression in, 139-140
  mean value in, 126, 127, 127t, 128, 135-137
  measurement errors and propagation of, 128-130
    types of, 125-126
  minimum detectable activity in, 131
  nuclear counting statistics in, 126-128
  outliers in, 138, 138t, 139f
  percentage uncertainty in, 127, 129
  Poisson distribution in, 126-128, 127f
  products and ratios in, 129
  standard deviation in, 128, 134, 135-136
    of gaussian spectral curve, 149
  statistical significance in, 130-131
  sums and differences in, 129
  tests of significance in, 130-131, 133, 135, 136f, 140
  t-test in, 135-137
Statistical errors. *See* Measurement errors.
Statistical noise, 243-247. *See also* Contrast-to-noise ratio (CNR); Signal-to-noise ratio (SNR).
  in PET image, data corrections and, 340, 341
  in reconstructed image, 261, 263, 271, 273
    scatter corrections and, 298
Statistical (random) noise, 243
  contrast-to-noise ratio and, 243-244
Statistical tests, 133-140
  chi square test, 133-134, 134f
  outliers in, 138, 138t, 139f
  t-test, 135-137
Steady state, 385-386, 386f
Stopping power, linear, 68
Streak artifacts, 262, 265f, 273
Structured noise, 243
Student *t*-test, 135-137
Substates of atom, 9, 9f, 10, 12
Substrates of enzymatic reactions, 385, 385f, 387
Subtraction, image, 371, 372f
Sulfur-35, 452
Summation circuits, 184
Surface dose, 409
Surface rendering, 369-371
Surgery, gamma probes for, 193f, 194
Survey meters, 439-440
  for β particles, 166-167, 166f
  Geiger-Müller counters in, 95-96, 95f, 439
  ionization chamber, 89, 89f
    energy response curve for, 90-91, 91f
  quality checks of, 172
Survey meters *(Continued)*
  surface contamination and, 166
  windows of, 166
Sv. *See* Sievert (Sv).
S-value tables
  for F-18, 422t-423t
  for I-131, 420t-421t
  for Tc-99m, 418t-419t
Synchrocyclotron, 48
Syringes
  dose rates in contact with, 431-432
  shielding for, 436-437, 436f
System alignment, in SPECT, 302-303
System resolution, 265-266
  of gamma camera, 210-211, 225, 227
  measurement of, 229
  in PET, 314-315
System sensitivity, for gamma cameras, 231
System volume sensitivity, 301-302
Systematic errors, 125
Systeme International (SI) units, 7, 32, 407, 408, 409, 429, 443

T

TAC (time-activity curve). *See* Time-activity curve (TAC).
Target nucleus, in neutron activation, 46, 47
Target organs, 408, 409, 409f, 413-414, 415, 418t-423t
TCT. *See* Transmission computed tomography (TCT).
TDS rules. *See* Time, distance, shielding (TDS) rules.
Technetium-99m
  advantages of, 50-51
  calibration standard for, 164, 166, 189
  carrier in sample of, 38
  carrier-free, 38
  characteristics of, 462
  contaminants in, 53, 58, 190
  decay factors for, 34, 34t
  dosimetry of, internal, 416
  energy resolution in detection of, 150, 151, 152f, 153f, 210, 211, 212, 231
  gamma camera imaging with
    collimator sensitivity in, 231
    counting rate in, 230
    energy resolution in, 150, 151, 152f, 153f, 210, 211, 212, 231
    image distortion in, 217
    intrinsic resolution in, 210, 211
    spatial resolution in, 235
  historical development of, 2, 4
  mean dose per cumulated activity for, 415-416, 418t-419t
  as metastable state, 15, 24
  production of, 50-53, 51f, 51t
  properties of, 58t

Technetium-99m *(Continued)*
radiopharmaceuticals labeled with
dose estimates for, 479t
examples of, 5t, 379, 381t
from kits, 60, 60t
RBCs labeled with, 392
renal studies with, 379
for sentinel node detection, 192-193
SPECT imaging with
attenuation in, 287, 287f, 288f, 289f, 290, 290f, 291t
clinical applications of, 303f, 304, 304f, 305, 305f, 306
performance measurement in, 301
scattering in, 297, 298, 298f
transmission scan and, 294, 296, 296f
in syringes, dose rates with, 431-432
Tenth-value thickness (TVT), 82, 82t, 437
Tetrofosmin, ^{99m}Tc-labeled, 5t, 304
Thallium-201, 58t, 303, 304, 474-475
Thallium-201 chloride, 5t, 394, 479t
Thallium-activated cesium iodide [CsI(Tl)], 100, 101t
in compact gamma camera, 207
in intraoperative gamma probe, 193, 193f
Thallium-activated sodium iodide [NaI(Tl)]. *See* NaI(Tl) detectors.
Thermal emission noise, 184
Thermal neutrons, 43-44
Thermoluminescent dosimeters (TLDs), 440, 440f
Thompson criteria, 138
Three-dimensional data acquisition
in PET, 332, 333f, 334-335
voxels in, 285, 339-340, 364, 367
Three-dimensional iterative reconstruction, 276
Three-dimensional PET reconstruction, 275-276, 276f
Threshold dose, 427
Through-hole detectors, 180, 180f-181f
Thyroid, uptake of iodine in, 192, 192f
Time, distance, shielding (TDS) rules, 436-437
Time constants
amplifier, 110-113, 110f, 111f, 114f
preamplifier, 107-110, 108f
rate meter, 120
Time stamp, 307
Time-activity curve (TAC)
cumulated activity and, 409, 410, 410f
image processing and, 373, 374f
kinetic modeling and, 379-380, 385f, 392, 396f, 401
Time-of-flight PET, 309-310, 310f
Timers, 119-120, 119f
Time-to-amplitude converters, 118-119, 119f
Timing resolution, 307-308
Timing walks, 115
Tissue. *See also* Organs.
attenuation coefficient in, 287, 287f, 293
transmission scan and, 294, 337
extraction of tracer by, 386-390, 387f, 388f, 389f
f factor for, 430, 430f
positron ranges in, 314
Tissue compartments. *See* Compartmental models.
Tissue response curves, 391
Tissue weighting factors, 417, 425t
TLDs. *See* Thermoluminescent dosimeters (TLDs).
Tomographic imaging, 253-278. *See also* Positron emission tomography (PET); Single photon emission computed tomography (SPECT).
advantages of, 253, 269
basic concepts of, 254-256, 254f, 255f, 256f
contrast in, 241-242, 243f, 269
in PET, 241-242, 253, 336, 337, 346
in SPECT, 241-242, 243f, 297, 299
coordinate systems in, 255-256, 256f
digital image format for, 364. *See also* Digital image processing.
emission, 253
historical development of, 4, 253
image processing in. *See* Digital image processing.
image quality in. *See also* Sampling; Spatial resolution: tomographic reconstruction and.
consistency requirements and, 266, 266f
with FT and FBP, 263, 264f, 265-270, 265f, 266f, 267f
noise and, 253, 266-270, 267f
image reconstruction in. *See* Reconstruction tomography.
limited-angle, 266
for low-contrast imaging, 241-242
mathematical techniques in. *See also* Fourier transform (FT).
with cone-beam collimator, 274-275, 274f
direct Fourier transform as, 258-260, 259f
with fan-beam collimator, 273-274, 274f-275f
filtered backprojection as. *See* Filtered backprojection (FBP).
iterative reconstruction as. *See* Iterative reconstruction.
for multiple slices, 262-263
for PET, 253, 336, 337
Tomographic imaging *(Continued)*
with pinhole collimator, 274-275
simple backprojection as, 256-258, 257f, 258f
in multimodality instrumentation, 4-5
overview of, 254-256
terminology of, 254-256
transmission, 253
types of, 253
Total-body dose, 417. *See also* Whole-body imaging.
Total-spectrum counting rate, 170
Townsend, David, 354
Townsend avalanche, 91
TPF. *See* True-positive fraction (TPF).
Tracer kinetic modeling, 379-405
basic concepts of, 379-380, 380f
blood flow measurement and, 392-396. *See also* Blood flow: measurement of.
cardiac imaging and, 392
compartment models for, 390-392, 390f-391f
compartments in, 380-386
dilution principle and, 382-383
distribution volume of, 382-383, 384f
flux between, 383-384
nondisplaceable, 384, 402f
open vs. closed, 382-383
partition coefficient and, 383
of complex systems, 402
distribution volume in, 382-383
dynamic imaging and, 392-403
enzyme kinetics and, 396-401
equilibrium models in, 386
extraction in, 386-388, 387f, 388f, 389f, 390-391, 390f
first-order kinetics in, 384-385
glucose metabolism and, 396-401
rate constants in, 384-385, 384f, 385f, 390-391, 390f, 396
receptor ligand assays and, 401-403, 402f, 404f
steady state in, 385-386, 386f
time-activity curves in, 373, 374f, 379-380, 410, 410f
tracer characteristics in, 380-382
tracer delivery and, 386-390
blood flow and, 386-387
clearance and, 388, 389f
extraction and, 386-388
Fick principle and, 387
Renkin-Crone model for, 387-388, 388f-389f, 390-391
transport and, 389-390
Tracer studies. *See also* Radiopharmaceuticals; Tracer kinetic modeling.
of blood flow. *See* Blood flow.
of cardiac function. *See* Cardiac studies.

Tracer studies *(Continued)*
of enzyme kinetics, 396-401, 397f, 398f, 401f
gamma camera for, 197
historical, 2
of receptors, 401-402, 402f
Tracers. *See* Radionuclides; Radiopharmaceuticals; Tracer kinetic modeling.
Transaxial direction, 254-255
Transaxial resolution, 301
Transaxial sections, orientation of, 369, 370f
Transient equilibrium, 41, 41f
Transistors, field-effect, 109
Transit time, mean, 380, 380f, 384
Transition energy (Q), 19, 20, 20f, 21, 21f, 22
Transmission computed tomography (TCT), 253. *See also* Tomographic imaging.
Transmission curves
for α particles, 70, 70f
for β particles and electrons, 71-72, 73f
for photons, 84
Transmission factors, 83
Transmission scans
in PET attenuation correction postinjection, 338-339
with SPECT, 294-296, 295f-297f
Transmutation of elements, 20, 21, 24, 25, 27
Transport
active, 389
passive, 389-390
carrier-mediated diffusion and, 389
Transverse direction, 254-255
Transverse sections, orientation of, 369, 370f
Trapping methods for blood flow measurement, 393-394
Triple-head gamma camera, 206-207
True coincidences, 322-323, 322f
True color display, 367
True-positive fraction (TPF), 249, 250f
Truncation artifacts, 359, 359f
t-test, 135-137
Tumor imaging
FDG-PET in, 341
gamma-ray probes in, 192-193
PET/CT in, 355-356, 356f
SPECT in, 305-306
Tungsten septa, 323
Turnover time, 384
TVT. *See* Tenth-value thickness (TVT).
Two-energy window analysis, 184
Two-source method, 171, 171f

U

Ultraviolet (UV) photons
in Geiger-Müller counter, 92, 94
in scintillation detector, 99-100
Undersampling, 263, 264f, 484, 485f, 486
in annihilation coincidence detection, 318
with iterative algorithms, 273
pixel size and, 366
Unidirectional extraction fraction, 387, 388, 388f, 389f
Unified atomic mass unit (u), 7
Uniformity measurements for gamma cameras, 229-230
Unipolar pulse, 112, 113
Units of measure, 7-8
for radiation, advisory body for, 433
for radiation dose, 407
SI, 7, 32
Universal decay curve, 35, 35f
Unrestricted areas, 431-432
Upper-level discriminator, 113, 114f
Uptake half-time, 410-411
Uptake of tracer, 59, 387, 410-411. *See also* Extraction.
Uranium, in nuclear reactors, 43-44
Urine samples, counting systems for, 105, 173, 182
Useful field-of-view (UFOV), 217, 229, 230, 231
in PET, 319, 320, 320f, 321, 323

V

Valid events, 204
Variance, 126-127
Ventricular ejection fraction, calculation of, ^{99m}Tc-labeled red cells for, 392, 392f
Vials, counting, 184-185
Voltage, saturation, 87-88, 88f
Voltage response curve, for ionization chambers, 87-88, 88f, 91, 92f
in Geiger-Müller counters, 94f
in proportional counters, 92f
Voltage-sensitive preamplifiers, 107-108, 109f
Volume, sample. *See* Sample volume.
Volume of interest, 373
Volume sensitivity in SPECT, 301-302
Voxels, 285, 339-340, 364, 367

W

Waste disposal, 439
Water, radioactivity in, regulation of, 431, 432
Wavelength, 8
Waveshifters, 89-90
Weight, atomic, 13
Weighting factors, 408, 408t, 417, 424, 428, 429t, 435
Weiss, S., 2
Well counters. *See* NaI(Tl) well counters.
White blood cells, labeling of, 5t
Whole-body counters, 194
Whole-body dose, 417
Whole-body imaging
with gamma camera, 207f
with PET, 335, 340, 340f
Wilkinson converters, 117-118, 117f
Window fractions, dead times and, 170-171, 213, 213f
Window width, 113
Windowing, 369
Windows
coincidence timing, 121, 307
entrance, 98, 98f, 101-102, 104
thickness of, 166-167
for gamma cameras, 201
optical, 101-102
scatter, 298, 298f
of survey meters, 166
Wipe testing, 441
Wrenn, F.R., 2

X

X rays, 8-9, 8f. *See also* Photons.
characteristic. *See* Characteristic x rays.
Compton scattering of, 75, 75t
detection of. *See* Radiation detectors.
discovery of, 2
in electromagnetic spectrum, 8, 8f
health physics and, 429, 434-435
interactions with matter, 74-78
passage through matter, 74-78
pulse-height spectrum and, 142-145
radiobiologic effects of, 78
scattering of. *See* Scattered radiation.
Xenon-133
blood flow measurement with, 395, 396
characteristics of, 472
decay scheme of, 21, 22, 22f, 472
safe handling of, 433t, 433
Xenon, nuclear energy-level diagram for, 15, 15f
X-ray computed tomography, 253, 346-350. *See also* Hybrid imaging systems.
coherent scattering in, 77
in co-registered imaging, 375-376, 377f
image quality in, 263-270
with PET. *See* PET/CT.
reconstruction in, 348-350, 349f
scanners in, 348, 348f
scattered radiation in, 349
spatial resolution in, 349
with SPECT. *See* SPECT/CT.
x-ray detectors in, 347-348, 348f
x-ray tubes in, 346-347, 346f-347f
X-ray detectors, 347-348, 348f
X-ray tubes, 346-347, 346f-347f, 355

Z

Z. *See* Atomic number (Z).
Zero padding, 489
Zero-crossover timing, 115-116