

Dialog

<https://playdocs1.orangeriver-ad055946.westus2.azurecontainerapps.io/play-docs/docs/ui-components/Overlay/Dialog>

Dialog

The system provides a comprehensive dialog solution with multiple variants, modal support, and flexible configuration options. Built around a service-based architecture, it offers both predefined dialog types and custom modal dialogs for various user interaction scenarios.

```
<ava-dialog>
```

How to use

```
import { AavaDialogService } from "@aava/play-core"; // Inject the service
constructor(private dialogService: AavaDialogService) {} // Show different types of dialogs
this.dialogService.success({ message: 'Operation completed!' });
this.dialogService.confirmation({ message: 'Are you sure?' });
```

```
import { AavaDialogService } from "@aava/play-core"; // Inject the service
constructor(private dialogService: AavaDialogService) {} // Show different types of dialogs
this.dialogService.success({ message: 'Operation completed!' });
this.dialogService.confirmation({ message: 'Are you sure?' });
```

Basic Usage

Simple dialog implementation with default settings and integrated functionality.

```
<aava-button label="Show Warning Dialog" variant="warning" (userClick)="showWarningDialog()"></aava-button>
```

```
<aava-button label="Show Warning Dialog" variant="warning" (userClick)="showWarningDialog()"></aava-button>
```

```
constructor(private dialogService: DialogService) {
  showWarningDialog() {
    this.dialogService.warning({
      title: 'Unsaved Changes',
      message: 'You have unsaved changes that will be lost if you continue. Are you sure you want to proceed?',
      showProceedButton: true,
      proceedButtonText: 'Discard Changes',
    })
    .then((result) => {
      console.log('Warning dialog closed:', result);
      if (result.action === 'proceed') {
        console.log('User chose to discard changes!');
      }
    });
  }
}
```

```
constructor(private dialogService: DialogService) {
  showWarningDialog() {
    this.dialogService.warning({
      title: 'Unsaved Changes',
      message: 'You have unsaved changes that will be lost if you continue. Are you sure you want to proceed?',
      showProceedButton: true,
      proceedButtonText: 'Discard Changes',
    })
    .then((result) => {
      console.log('Warning dialog closed:', result);
      if (result.action === 'proceed') {
        console.log('User chose to discard changes!');
      }
    });
  }
}
```

Basic Features

- Service-Based: Programmatic dialog creation via DialogService
- Multiple Variants: Success, error, warning, info, confirmation, loading, and custom dialogs
- Modal Support: Full modal dialog capabilities with content projection
- Responsive Design: Adapts to different screen sizes and content
- Accessibility: Built-in accessibility features and keyboard navigation

Dialog Variants

Seven distinct dialog variants for different user interaction scenarios.

```
<aava-button label="Show Success Dialog" variant="success" (userClick)="showSuccessDialog()"></aava-button>
<aava-button label="Show Error Dialog" variant="danger" (userClick)="showErrorDialog()"></aava-button>
<aava-button label="Show Warning Dialog" variant="warning" (userClick)="showWarningDialog()"></aava-button>
<aava-button label="Show Info Dialog" variant="primary" (userClick)="showInfoDialog()"></aava-button>
<aava-button label="Show Confirmation Dialog" variant="secondary" (userClick)="showConfirmationDialog()"></aava-button>
<aava-button label="Show Loading Dialog" variant="secondary" (userClick)="showLoadingDialog()"></aava-button>
```

```
<aava-button label="Show Success Dialog" variant="success" (userClick)="showSuccessDialog()"></aava-button>
<aava-button label="Show Error Dialog" variant="danger" (userClick)="showErrorDialog()"></aava-button><aava-
button label="Show Warning Dialog" variant="warning" (userClick)="showWarningDialog()"></aava-button><aava-
button label="Show Info Dialog" variant="primary" (userClick)="showInfoDialog()"></aava-button><aava-button
label="Show Confirmation Dialog" variant="secondary" (userClick)="showConfirmationDialog()"></aava-button><aava-
button label="Show Loading Dialog" variant="secondary" (userClick)="showLoadingDialog()"></aava-button>
```

```
constructor(private dialogService: DialogService) {} showSuccessDialog() { this.dialogService .success({
title: 'Operation Successful!', message: 'Your action has been completed successfully.', size: 'lg',
bottomBorder: true, }) .then((result: unknown) => { console.log('Success dialog closed:',
result); }); } showErrorDialog() { this.dialogService .error({ title: 'Operation Failed',
message: 'Something went wrong. Please try again.', showRetryButton: true, retryButtonText: 'Retry',
size: 'md', }) .then((result: unknown) => { console.log('Error dialog closed:', result); }); }
showWarningDialog() { this.dialogService .warning({ title: 'Please Review', message:
'Please review the information carefully before proceeding.', showProceedButton: true,
proceedButtonText: 'Proceed', showCancelButton: true, cancelButtonText: 'Cancel', })
.then((result: unknown) => { console.log('Warning dialog closed:', result); }); } showInfoDialog() {
this.dialogService .info({ title: 'Information', message: 'This is an informational message
with helpful details.', showOkButton: true, okButtonText: 'Got it', showLearnMoreButton:
true, learnMoreButtonText: 'Learn More', }) .then((result: unknown) => { console.log('Info
dialog closed:', result); }); } showConfirmationDialog() { this.dialogService .confirmation({
title: 'Confirm Action', message: 'Are you sure you want to perform this action?',
confirmButtonText: 'Confirm', cancelButtonText: 'Cancel', confirmButtonVariant: 'primary',
cancelButtonVariant: 'secondary', }) .then((result: unknown) => { console.log('Confirmation
dialog closed:', result); }); } showLoadingDialog() { this.dialogService .loading({ title:
'Processing', message: 'Please wait while we process your request.', showProgress: true,
progress: 0, showCancelButton: true, cancelButtonText: 'Cancel', }) .then((result:
unknown) => { console.log('Loading dialog closed:', result); }); }
```

```
constructor(private dialogService: DialogService) {} showSuccessDialog() { this.dialogService .success({
title: 'Operation Successful!', message: 'Your action has been completed successfully.', size: 'lg',
bottomBorder: true, }) .then((result: unknown) => { console.log('Success dialog closed:',
result); }); } showErrorDialog() { this.dialogService .error({ title: 'Operation Failed',
message: 'Something went wrong. Please try again.', showRetryButton: true, retryButtonText: 'Retry',
size: 'md', }) .then((result: unknown) => { console.log('Error dialog closed:', result); }); }
showWarningDialog() { this.dialogService .warning({ title: 'Please Review', message:
'Please review the information carefully before proceeding.', showProceedButton: true,
proceedButtonText: 'Proceed', showCancelButton: true, cancelButtonText: 'Cancel', })
.then((result: unknown) => { console.log('Warning dialog closed:', result); }); } showInfoDialog() {
this.dialogService .info({ title: 'Information', message: 'This is an informational message
with helpful details.', showOkButton: true, okButtonText: 'Got it', showLearnMoreButton:
true, learnMoreButtonText: 'Learn More', }) .then((result: unknown) => { console.log('Info
dialog closed:', result); }); } showConfirmationDialog() { this.dialogService .confirmation({
title: 'Confirm Action', message: 'Are you sure you want to perform this action?',
confirmButtonText: 'Confirm', cancelButtonText: 'Cancel', confirmButtonVariant: 'primary',
cancelButtonVariant: 'secondary', }) .then((result: unknown) => { console.log('Confirmation
dialog closed:', result); }); } showLoadingDialog() { this.dialogService .loading({ title:
'Processing', message: 'Please wait while we process your request.', showProgress: true,
progress: 0, showCancelButton: true, cancelButtonText: 'Cancel', }) .then((result:
unknown) => { console.log('Loading dialog closed:', result); }); }
```

Available Variants

- Success- Green styling for successful operations and confirmations
- Error- Red styling for errors and critical issues with retry options
- Warning- Orange/yellow styling for warnings and cautions
- Info- Blue styling for informational messages and tips
- Confirmation- Neutral styling for user confirmations and decisions
- Loading- Animated loading states with progress indicators
- Custom- Fully customizable styling and content

Custom Dialogs

Fully customizable dialogs with custom content and styling options.

```
<aava-button label="Show Info Custom Dialog" variant="info" (userClick)="showInfoCustomDialog()"></aava-button>
```

```
<aava-button label="Show Info Custom Dialog" variant="info" (userClick)="showInfoCustomDialog()"></aava-button>
```

```
showInfoCustomDialog() {
  this.dialogService.custom({
    title: 'New Features Available',
    message: 'We have added several new features to improve your experience:',
    variant: 'info',
    borderBottom: true,
    customContent: `
      <div style="text-align: left; margin: 1rem 0;">
        <div style="display: grid; grid-template-columns: 1fr 1fr; gap: 1rem;">
          <div style="background: #dbeafe; padding: 1rem; border-radius: 4px;">
            <strong> Mobile App</strong><br>
            New mobile app with offline support
          </div>
          <div style="background: #dbeafe; padding: 1rem; border-radius: 4px;">
            <strong> Enhanced Security</strong><br>
            Two-factor authentication support
          </div>
        </div>
      `
    ,
    buttons: [
      { label: 'Learn More', variant: 'primary', action: 'learn' },
      { label: 'Try Now', variant: 'primary', action: 'try' },
      { label: 'Maybe Later', variant: 'secondary', action: 'later' },
    ],
  })
  .then((result: unknown) => {
    console.log('Info custom dialog closed:', result);
    const dialogResult = result as { action?: string };
    switch (dialogResult.action) {
      case 'learn':
        console.log('User chose to learn more');
        break;
      case 'try':
        console.log('User chose to try now');
        break;
      case 'later':
        console.log('User chose to try later');
        break;
    }
  });
}
```

```
showInfoCustomDialog() {
  this.dialogService.custom({
    title: 'New Features Available',
    message: 'We have added several new features to improve your experience:',
    variant: 'info',
    borderBottom: true,
    customContent: `
      <div style="text-align: left; margin: 1rem 0;">
        <div style="display: grid; grid-template-columns: 1fr 1fr; gap: 1rem;">
          <div style="background: #dbeafe; padding: 1rem; border-radius: 4px;">
            <strong> Mobile App</strong><br>
            New mobile app with offline support
          </div>
          <div style="background: #dbeafe; padding: 1rem; border-radius: 4px;">
            <strong> Enhanced Security</strong><br>
            Two-factor authentication support
          </div>
        </div>
      `
    ,
    buttons: [
      { label: 'Learn More', variant: 'primary', action: 'learn' },
      { label: 'Try Now', variant: 'primary', action: 'try' },
      { label: 'Maybe Later', variant: 'secondary', action: 'later' },
    ],
  })
  .then((result: unknown) => {
    console.log('Info custom dialog closed:', result);
    const dialogResult = result as { action?: string };
    switch (dialogResult.action) {
      case 'learn':
        console.log('User chose to learn more');
        break;
      case 'try':
        console.log('User chose to try now');
        break;
      case 'later':
        console.log('User chose to try later');
        break;
    }
  });
}
```

Custom Features

- Custom Content: HTML content or component rendering
- Variant Styling: Multiple visual variants (default, success, error, warning, info)
- Flexible Layouts: Custom button configurations and layouts
- Icon Customization: Optional icons with custom colors and sizes
- Bottom Borders: Optional decorative bottom borders

Service Methods

The DialogService provides convenient methods for different dialog types:

Success Dialog

```
this.dialogService.success({
  title: "Success!",
  message: "Operation completed successfully.",
  size: "lg",
  showButtons: true,
  buttons: [{ label: "Continue", variant: "primary", action: "continue" }],
});
```

```
this.dialogService.success({
  title: "Success!",
  message: "Operation completed successfully.",
  size: "lg",
  showButtons: true,
  buttons: [{ label: "Continue", variant: "primary", action: "continue" }],
});
```

Error Dialog

```
this.dialogService.error({
  title: "Error!",
  message: "Something went wrong. Please try again.",
  showRetryButton: true,
  retryButtonText: "Retry",
  size: "md",
});
```

```
this.dialogService.error({
  title: "Error!",
  message: "Something went wrong. Please try again.",
  showRetryButton: true,
  retryButtonText: "Retry",
  size: "md",
});
```

Warning Dialog

```
this.dialogService.warning({
  title: "Warning",
  message: "Please review the information carefully.",
  showProceedButton: true,
  proceedButtonText: "Proceed",
  showCancelButton: true,
  cancelButtonText: "Cancel",
});
```

```
this.dialogService.warning({ title: "Warning", message: "Please review the information carefully.",
showProceedButton: true, proceedButtonText: "Proceed", showCancelButton: true, cancelButtonText: "Cancel",});
```

Confirmation Dialog

```
this.dialogService.confirmation({ title: "Delete Item", message: "Are you sure you want to delete this item?",
confirmButtonText: "Delete", cancelButtonText: "Cancel", confirmButtonVariant: "danger", destructive: true,});
```

```
this.dialogService.confirmation({ title: "Delete Item", message: "Are you sure you want to delete this item?",
confirmButtonText: "Delete", cancelButtonText: "Cancel", confirmButtonVariant: "danger", destructive: true,});
```

Loading Dialog

```
this.dialogService.loading({ title: "Processing", message: "Please wait while we process your request.",
showProgress: true, progress: 0, showCancelButton: true, cancelButtonText: "Cancel",});
```

```
this.dialogService.loading({ title: "Processing", message: "Please wait while we process your request.",
showProgress: true, progress: 0, showCancelButton: true, cancelButtonText: "Cancel",});
```

Custom Dialog

```
this.dialogService.custom({ title: "Custom Dialog", message: "This is a custom dialog with unique content.",
variant: "success", customContent: "<div>Custom HTML content here</div>", buttons: [ { label: "OK", variant:
"primary", action: "ok" }, { label: "Cancel", variant: "secondary", action: "cancel" }, ],});
```

```
this.dialogService.custom({ title: "Custom Dialog", message: "This is a custom dialog with unique content.",
variant: "success", customContent: "<div>Custom HTML content here</div>", buttons: [ { label: "OK", variant:
"primary", action: "ok" }, { label: "Cancel", variant: "secondary", action: "cancel" }, ],});
```

Modal Dialog

```
this.dialogService.openModal( MyCustomComponent, { width: "600px", maxWidth: "90vw", showCloseButton:
true, }, { data: { id: 123, name: "Example" }, });
```

```
this.dialogService.openModal( MyCustomComponent, { width: "600px", maxWidth: "90vw", showCloseButton:
true, }, { data: { id: 123, name: "Example" }, });
```

API Reference

DialogService Methods

Method	Parameters	Return Type	Description
success()	SuccessDialogConfig?	Promise	Show success dialog with green styling
error()	ErrorDialogConfig?	Promise	Show error dialog with red styling
warning()	WarningDialogConfig?	Promise	Show warning dialog with orange styling
info()	InfoDialogConfig?	Promise	Show info dialog with blue styling
confirmation()	ConfirmationDialogConfig?	Promise	Show confirmation dialog for user decisions
loading()	LoadingDialogConfig?	Promise	Show loading dialog with progress indicators
custom()	CustomDialogConfig?	Promise	Show custom dialog with full customization
feedback()	CustomDialogConfig?	Promise	Show feedback dialog for user input
open()	component, data?	Promise	Open custom component in dialog container
openModal()	component, config?, data?	Promise	Open custom component in modal dialog
close()	-	void	Close the currently open dialog

success()

SuccessDialogConfig?

Promise<DialogResult>

error()

ErrorDialogConfig?

Promise<DialogResult>

warning()

WarningDialogConfig?

Promise<DialogResult>

info()

InfoDialogConfig?

Promise<DialogResult>

confirmation()

ConfirmationDialogConfig?

Promise<DialogResult>

loading()

LoadingDialogConfig?

Promise<DialogResult>

custom()

CustomDialogConfig?

Promise<DialogResult>

feedback()

CustomDialogConfig?

Promise<DialogResult>

open()

component, data?

Promise<any>

openModal()

component, config?, data?

Promise<any>

close()

void

Base Dialog Configuration

Property	Type	Default	Description
title	string?	' '	Dialog header text
message	string?	' '	Dialog body text
icon	string?	' '	Icon name for the dialog
iconColor	string?	' '	Custom icon color
iconSize	number?	' '	Custom icon size in pixels
showCloseButton	boolean?	true	Whether to show close button
backdrop	boolean?	true	Whether to show backdrop
width	string?	' '	Custom dialog width
height	string?	' '	Custom dialog height
data	any?	' '	Additional data to pass to dialog

title

string?

' '

message

string?

' '

icon

string?

' '

iconColor

string?

' '

iconSize

number?

' '

showCloseButton

boolean?

true

backdrop
boolean?
true
width
string?
''
height
string?
''
data
any?
''

Success Dialog Configuration

Property	Type	Default	Description
buttons	DialogButton[]?	[]	Array of custom buttons
showButtons	boolean?	false	Whether to show custom buttons
bottomBorder	boolean?	true	Whether to show decorative bottom border
size	'lg' 'md' 'sm' 'lg'		Dialog size variant
buttons			
DialogButton[]?			
[]			
showButtons			
boolean?			
false			
bottomBorder			
boolean?			
true			
size			
'lg' 'md' 'sm'			

'lg'

Error Dialog Configuration

Property	Type	Default	Description
showRetryButton	boolean?	false	Whether to show retry button
retryButtonText	string?	'Retry'	Text for retry button
closeButtonText	string?	'Close'	Text for close button
bottomBorder	boolean?	true	Whether to show decorative bottom border
buttons	ErrorButton[]?	[]	Array of custom error buttons
showButtons	boolean?	false	Whether to show custom buttons
size	'lg' 'md' 'sm' 'lg'		Dialog size variant

showRetryButton

boolean?

false

retryButtonText

string?

'Retry'

closeButtonText

string?

'Close'

bottomBorder

boolean?

true

buttons

ErrorButton[]?

[]

showButtons

boolean?

false

size

'lg' | 'md' | 'sm'

'lg'

Warning Dialog Configuration

Property	Type	Default	Description
showProceedButton	boolean?	false	Whether to show proceed button
proceedButtonText	string?	'Proceed'	Text for proceed button
showCancelButton	boolean?	true	Whether to show cancel button
cancelButtonText	string?	'Cancel'	Text for cancel button
bottomBorder	boolean?	true	Whether to show decorative bottom border
buttons	WarningButton[]?	[]	Array of custom warning buttons
showButtons	boolean?	false	Whether to show custom buttons
size	'lg' 'md' 'sm' 'lg'		Dialog size variant
showProceedButton			
boolean?			
false			
proceedButtonText			
string?			
'Proceed'			
showCancelButton			
boolean?			
true			
cancelButtonText			
string?			
'Cancel'			
bottomBorder			
boolean?			
true			
buttons			
WarningButton[]?			
[]			
showButtons			
boolean?			
false			
size			

'lg' 'md' 'sm'
'lg'

Info Dialog Configuration

Property	Type	Default	Description
showOkButton	boolean?	true	Whether to show OK button
okButtonText	string?	'OK'	Text for OK button
showLearnMoreButton	boolean?	false	Whether to show learn more button
learnMoreButtonText	string?	'Learn More'	Text for learn more button
bottomBorder	boolean?	true	Whether to show decorative bottom border
buttons	InfoButton[]?	[]	Array of custom info buttons
showButtons	boolean?	false	Whether to show custom buttons
size	'lg' 'md' 'sm' 'lg'		Dialog size variant

showOkButton
boolean?
true
okButtonText
string?
'OK'
showLearnMoreButton
boolean?
false
learnMoreButtonText
string?
'Learn More'
bottomBorder
boolean?
true
buttons
InfoButton[]?
[]
showButtons
boolean?

false
size
'lg' 'md' 'sm'
'lg'

Confirmation Dialog Configuration

Property	Type	Default	Description
confirmButtonText	string?	'Confirm'	Text for confirm button
cancelButtonText	string?	'Cancel'	Text for cancel button
confirmButtonVariant	'primary' 'secondary' 'success' 'warning' 'danger'	'primary'	Confirm button styling variant
cancelButtonVariant	'primary' 'secondary' 'success' 'warning' 'danger' 'secondary'	'secondary'	Cancel button styling variant
destructive	boolean?	false	Whether this is a destructive action
bottomBorder	boolean?	false	Whether to show decorative bottom border
confirmButtonText			
string?			
'Confirm'			
cancelButtonText			
string?			
'Cancel'			
confirmButtonVariant			
'primary' 'secondary' 'success' 'warning' 'danger'			
'primary'			
cancelButtonVariant			
'primary' 'secondary' 'success' 'warning' 'danger'			
'secondary'			
destructive			
boolean?			
false			
bottomBorder			
boolean?			
false			

Loading Dialog Configuration

Property	Type	Default	Description
progress	number?	0	Progress value (0-100)
showProgress	boolean?	false	Whether to show progress bar
showCancelButton	boolean?	false	Whether to show cancel button
cancelButtonText	string?	'Cancel'	Text for cancel button
spinnerColor	string?	''	Custom spinner color
indeterminate	boolean?	true	Whether progress is indeterminate
bottomBorder	boolean?	false	Whether to show decorative bottom border
progress			
number?			
0			
showProgress			
boolean?			
false			
showCancelButton			
boolean?			
false			
cancelButtonText			
string?			
'Cancel'			
spinnerColor			
string?			
''			
indeterminate			
boolean?			
true			
bottomBorder			
boolean?			
false			

Custom Dialog Configuration

Property	Type	Default	Description
buttons	DialogButton[]?	[]	Array of custom buttons
variant	'default' 'success' 'error' 'warning' 'info' 'default'		Visual variant for styling
customContent	string?	''	Custom HTML content
showIcon	boolean?	true	Whether to show icon
showTitle	boolean?	true	Whether to show title
showMessage	boolean?	true	Whether to show message
bottomBorder	boolean?	false	Whether to show decorative bottom border
label	string?	''	Custom label text
confirmButtonText	string?	''	Text for confirm button
cancelButtonText	string?	''	Text for cancel button
destructive	boolean?	false	Whether this is a destructive action

buttons

DialogButton[]?

[]

variant

'default' | 'success' | 'error' | 'warning' | 'info'

'default'

customContent

string?

''

showIcon

boolean?

true

showTitle

boolean?

true

showMessage

boolean?

true

bottomBorder

boolean?

false

label

string?
''
confirmButtonText
string?
''
cancelButtonText
string?
''
destructive
boolean?
false

Modal Dialog Configuration

Property	Type	Default	Description
maxWidth	string?	''	Maximum width constraint
maxHeight	string?	''	Maximum height constraint
showCloseButton	boolean?	true	Whether to show close button
maxWidth			
string?			
''			
maxHeight			
string?			
''			
showCloseButton			
boolean?			
true			

Dialog Button Interface

Property	Type	Default	Description
label	string	-	Button display text
variant	'primary' 'secondary' 'success' 'warning' 'danger'	'primary'	Button styling variant
action	string?	''	Action identifier for button click
disabled	boolean?	false	Whether button is disabled

label
string
variant
'primary' 'secondary' 'success' 'warning' 'danger'
'primary'
action
string?
''
disabled
boolean?
false

Dialog Result Interface

Property	Type	Description
action	string?	Action that triggered dialog closure
data	any?	Additional data from dialog interaction
confirmed	boolean?	Whether user confirmed the action
action		
string?		
data		
any?		
confirmed		
boolean?		

Best Practices

Design Guidelines

- Clear Purpose: Make dialog purpose obvious through title and content
- Consistent Styling: Use consistent visual hierarchy across dialog types
- Appropriate Sizing: Choose dialog sizes that fit content without overwhelming
- Button Placement: Follow standard button placement conventions
- Visual Feedback: Provide clear visual feedback for user actions

Accessibility

- Keyboard Navigation: Ensure full keyboard accessibility (Tab, Escape, Enter)

- Screen Reader Support: Provide descriptive titles and content
- Focus Management: Trap focus within dialog and restore on close
- ARIA Attributes: Use appropriate ARIA roles and labels
- High Contrast: Maintain sufficient contrast for all text and elements

Performance

- Lazy Loading: Load dialog content only when needed
- Memory Management: Properly clean up dialog instances
- Change Detection: Use OnPush strategy for optimal performance
- Event Handling: Clean up event listeners and subscriptions
- Bundle Optimization: Import only needed dialog types

User Experience

- Clear Actions: Make button actions and consequences clear
- Progressive Disclosure: Use dialogs for focused, single-purpose interactions
- Error Handling: Provide clear error messages and recovery options
- Loading States: Show appropriate loading indicators for long operations
- Responsive Design: Ensure dialogs work well on all screen sizes

Implementation Considerations

- Service Injection: Inject DialogService where dialogs are needed
- Promise Handling: Use async/await or .then() for dialog results
- Error Boundaries: Handle dialog errors gracefully
- State Management: Integrate with application state management
- Testing: Test dialog interactions and accessibility features

Technical Notes

Component Architecture

The dialog system uses a service-based architecture:

- DialogService manages all dialog operations and lifecycle
- DialogContainerComponent provides the base container and backdrop
- Individual Dialog Components handle specific dialog types and styling
- ModalComponent provides advanced modal capabilities with content projection

Dialog Lifecycle

The dialog system manages complete lifecycle:

- Creation: Dynamic component creation via service methods
- Rendering: Automatic DOM insertion and view attachment
- Interaction: Event handling and user input processing
- Cleanup: Proper cleanup of views, components, and event listeners

Content Projection

Modal dialogs support advanced content projection:

- Header Content: Use[dialog-header]attribute for header sections
- Body Content: Use[dialog-body]attribute for main content
- Footer Content: Use[dialog-footer]attribute for action areas
- Dynamic Content: Any component can be rendered inside dialogs

[dialog-header]
[dialog-body]
[dialog-footer]

Event Handling

The system handles multiple event types:

- Close Events: User-initiated closure via close button or backdrop
- Button Events: Custom button click handling with action identification
- Result Events: Promise resolution with user action results
- Cleanup Events: Proper cleanup of resources and event listeners

CSS Integration

The component integrates with the design system:

- CSS Variables: Uses semantic CSS variables for theming
- Responsive Design: Adapts to different screen sizes
- State Management: Handles various dialog states
- Accessibility: Maintains proper contrast and focus indicators