

Test Level Attributes

Web Service Response Attribute	Description
mid	Test id
sid	Site id
ttime	Timestamp of test relative to GMT
sname	Site name
rtime	Response time
tpt	Total pages tested
tps	Total pages testing successful
tpf	Total pages testing failed
tot	Total objects tested
tos	Total objects testing successful
tof	Total objects testing failed
nbyte	Number of bytes downloaded

Page Level Attributes

Web Service Response Attribute	Description
pseq	Page sequence number
rtime	Response time of page in milliseconds
nobj	Number of objects downloaded in the page
rc200	Number of objects with a return code of 200-299
rc300	Number of objects with a return code of 300-399
rc400	Number of objects with a return code of 400-499
rc500	Number of objects with a return code of 500-599
rcnet	Binary flag to indicate network related errors. Default is 0
rcint	Binary flag to indicate site related errors: default is 0.
nbyte	Total number of bytes in the page
nhost	Number of hosts in the page
nconn	Number of connections opened for the page
tostat	Binary flag to indicate a socket time out error
usstat	Binary flag to indicate a User Script error
blstat	Binary flag to indicate a byte limit exceeded error
rtobjseq	Root object sequence number of the first object with a 200 return code. This id can be used to determine which object caused the page to fail
dnssum	Summary of all DNS times for all the connections in milliseconds
ndns	Number of DNS calls
connsum	Summary of all connection times in milliseconds
nconn1	Number of connections
sslsum	Summary of all SSL connection times in

Web Service Response Attribute	Description
	milliseconds
nssl	Number of SSL connections
fbsum	Summary of all First Byte times in milliseconds
nfb	Number of First Byte objects
contsum	Summary of Content download time in milliseconds
ncont	Number of content time objects

Object Level Attributes

Web Service Response Attribute	Description
mid	Unique test identifier [COMPOUND PRIMARY KEY]
sid	Unique node identifier [COMPOUND PRIMARY KEY]
ttime	Test timestamp in GMT format [COMPOUND PRIMARY KEY]
oseq	PAGE.rtojsseq attribute. Unique object sequence number for a test[COMPOUND PRIMARY KEY]
hid	Unique host id for the object
connid	Unique connection id for the object
rc	Return code of the downloaded object
ctype	MIME type of the object (only applicable with return code < 300)
rtime	Response time of the object in milliseconds
nbyte	Total number of bytes downloaded
fbstart	Start timestamp in GMT format of the object download
fbtime	Time in milliseconds to download the first byte of the object
contstart	Start timestamp in GMT format of the download of second and subsequent bytes of the object
conttime	Time in milliseconds to download the second and subsequent bytes of the object
urlhost	URL of the host from where the object is downloaded
upage	URL of the object
uparam	Request parameters in the URL of an object
redirobjid	If a redirect, the object ID of the redirection

Host Level Attributes

Web Service Response Attribute	Description
hid	Host id of the host
page	Page where the hostname is referenced
dnsstart	Timestamp in GMT format of the start of the DNS connection
dnstime	Time in milliseconds to resolve the DNS lookup
nbyte	Total number of bytes downloaded from this host
nerr	Total number of object errors from this host
nobj	Total number of objects downloaded from this host
ip	IP address of the host

Connection Level Attributes

Response Attribute	Description
connid	Connection identifier
page	Page where the connection is referenced
rttime	Time in milliseconds to download all objects
connstart	Timestamp in GMT format of the start of the object connection
conntime	Time in milliseconds to open the connection
sslstart	Timestamp in GMT format of the start of the SSL connection
ssltime	Time in milliseconds to complete the SSL connection
nbyte	Total number of bytes downloaded from this connection
nerr	Total number of object errors from this connection
nobj	Total number of objects downloaded from this connection