

Signature Inference for Functional Property Discovery

or: How never to come up with tests manually anymore(*)

Tom Sydney Kerckhove

ETH Zurich

<https://cs-syd.eu/>

<https://github.com/NorfairKing>

11 October 2017

Motivation

Writing correct software is hard for humans.

Unit Testing

```
sort
  [4, 1, 6]
  ==
    [1, 4, 6]
```

Unit Testing

```
sort
```

```
[4, 1, 6]
```

```
==
```

```
[1, 4, 6]
```

Property testing

```
forall
  arbitrary
    $ \ls ->
      isSorted (sort ls)
```

Property testing

```
forall
```

```
arbitrary
```

```
$ \ls ->
```

```
isSorted (sort ls)
```

Property testing

```
forAll
  arbitrary
    $ \ls ->
      isSorted (sort ls)
```

Property Discovery

```
forAll  
  arbitrary  
    $ \ls ->  
      isSorted (sort ls)
```


Property Discovery with QuickSpec

Example Code

```
module MySort where

mySort :: Ord a => [a] -> [a]
mySort [] = []
mySort (x:xs) = insert (mySort xs)
    where
        insert [] = [x]
        insert (y:ys)
            | x <= y = x : y : ys
            | otherwise = y : insert ys

myIsSorted :: Ord a => [a] -> Bool
myIsSorted [] = True
myIsSorted [_] = True
myIsSorted (x:y:ls) = x <= y && myIsSorted (y : ls)
```

Example Code

```
module MySort where
```

```
mySort :: Ord a => [a] -> [a]
```

```
mySort [] = []
```

```
mySort (x:xs) = insert (mySort xs)
```

```
  where
```

```
    insert [] = [x]
```

```
    insert (y:ys)
```

```
      | x <= y = x : y : ys
```

```
      | otherwise = y : insert ys
```

```
myIsSorted :: Ord a => [a] -> Bool
```

```
myIsSorted [] = True
```

```
myIsSorted [_] = True
```

```
myIsSorted (x:y:ls) = x <= y && myIsSorted (y : ls)
```

Property Discovery using QuickSpec

```
== Signature ==  
    True :: Bool  
    (<=) :: Ord a => a -> a -> Bool  
    (:)  :: a -> [a] -> [a]  
    mySort :: Ord a => [a] -> [a]  
    myIsSorted :: Ord a => [a] -> Bool
```

Property Discovery using QuickSpec

```
== Signature ==  
    True :: Bool  
    (<=) :: Ord a => a -> a -> Bool  
    (:)  :: a -> [a] -> [a]  
    mySort :: Ord a => [a] -> [a]  
    myIsSorted :: Ord a => [a] -> Bool
```

```
== Laws ==  
1. y <= y = True  
2. y <= True = True  
3. True <= x = x  
4. myIsSorted (mySort xs) = True  
5. mySort (mySort xs) = mySort xs  
6. xs <= mySort xs = myIsSorted xs  
7. mySort xs <= xs = True  
8. myIsSorted (y : (y : xs)) = myIsSorted (y : xs)  
9. mySort (y : mySort xs) = mySort (y : xs)
```

Property Discovery using QuickSpec

```
== Signature ==  
  True :: Bool  
  (<=) :: Ord a => a -> a -> Bool  
  (:)  :: a -> [a] -> [a]  
  mySort :: Ord a => [a] -> [a]  
  myIsSorted :: Ord a => [a] -> Bool
```

```
== Laws ==  
  1. y <= y = True  
  2. y <= True = True  
  3. True <= x = x  
  4. myIsSorted (mySort xs) = True  
  5. mySort (mySort xs) = mySort xs  
  6. xs <= mySort xs = myIsSorted xs  
  7. mySort xs <= xs = True  
  8. myIsSorted (y : (y : xs)) = myIsSorted (y : xs)  
  9. mySort (y : mySort xs) = mySort (y : xs)
```

QuickSpec Code

```
{-# LANGUAGE ScopedTypeVariables #-}  
{-# LANGUAGE ConstraintKinds #-}  
{-# LANGUAGE RankNTypes #-}  
{-# LANGUAGE FlexibleContexts #-}  
  
module MySortQuickSpec where  
  
import Control.Monad  
import MySort  
import QuickSpec  
  
main :: IO ()  
main =  
    void $  
        quickSpec  
            signature  
            { constants =  
                [ constant "True" (True :: Bool)  
                  , constant "<=" (mkDict (<=) :: Dict (Ord A) -> A -> A -> Bool)  
                  , constant ":" ((:) :: A -> [A] -> [A])  
                  , constant "mySort" (mkDict mySort :: Dict (Ord A) -> [A] -> [A])  
                  , constant  
                      "myIsSorted"  
                      (mkDict myIsSorted :: Dict (Ord A) -> [A] -> Bool)  
                ]  
            }  
  
mkDict ::  
    (c =>  
     a)  
    -> Dict c  
    -> a  
mkDict x Dict = x
```

Problems with QuickSpec: Monomorphisation

Only for monomorphic functions

```
constant "filter"  
  (filter :: (A -> B) -> [A] -> [B] -> Bool)
```


Problems with QuickSpec: Code

Programmer has to write code for all functions of interest
15 lines of subject code.
33 lines of QuickSpec code.

Problems with QuickSpec: Speed

Dumb version of the QuickSpec approach:

1. Generate all possible terms
2. Generate all possible equations (tuples) of terms
3. Type check them to make sure the equation makes sense
4. Check that the input can be generated and the output compared for equality
5. Run QuickCheck to see if the equation holds

Pause slide with a joke

```
strictId :: a -> a  
strictId !x = x
```

Property Discovery with EasySpec

Step 1: Automation

Signatures

```
{-# LANGUAGE ScopedTypeVariables #-}  
{-# LANGUAGE ConstraintKinds #-}  
{-# LANGUAGE RankNTypes #-}  
{-# LANGUAGE FlexibleContexts #-}  
  
module MySortQuickSpec where  
  
import Control.Monad  
import MySort  
import QuickSpec  
  
main :: IO ()  
main =  
    void $  
        quickSpec  
            signature  
            { constants =  
                [ constant "True" (True :: Bool)  
                  , constant "<=" (mkDict (<=) :: Dict (Ord A) -> A -> A -> Bool)  
                  , constant ":" ((:) :: A -> [A] -> [A])  
                  , constant "mySort" (mkDict mySort :: Dict (Ord A) -> [A] -> [A])  
                  , constant  
                      "myIsSorted"  
                      (mkDict myIsSorted :: Dict (Ord A) -> [A] -> Bool)  
                ]  
            }  
  
mkDict ::  
    (c =>  
     a)  
    -> Dict c  
    -> a  
mkDict x Dict = x
```

Signatures

```
{-# LANGUAGE ScopedTypeVariables #-}  
{-# LANGUAGE ConstraintKinds #-}  
{-# LANGUAGE RankNTypes #-}  
{-# LANGUAGE FlexibleContexts #-}
```

```
module MySortQuickSpec where
```

```
import Control.Monad  
import MySort  
import QuickSpec
```

```
main :: IO ()
```

```
main =
```

```
    void $
```

```
    quickSpec
```

```
        signature
```

```
        { constants =
```

```
            [ constant "True" (True :: Bool)
```

```
            , constant "<=" (mkDict (<=) :: Dict (Ord A) -> A -> A -> Bool)
```

```
            , constant ":" ((:) :: A -> [A] -> [A])
```

```
            , constant "mySort" (mkDict mySort :: Dict (Ord A) -> [A] -> [A])
```

```
            , constant
```

```
                "myIsSorted"
```

```
                (mkDict myIsSorted :: Dict (Ord A) -> [A] -> Bool)
```

```
            ]
```

```
        }
```

```
mkDict ::
```

```
    (c =>
```

```
        a)
```

```
    -> Dict c
```

```
    -> a
```

```
mkDict x Dict = x
```

A QuickSpec Signature

```
data Signature =  
  Signature {  
    functions      :: [Function],  
    [...]         :: [Function],  
    properties     :: [Prop],  
  }
```

```
quickSpec :: Signature -> IO Signature
```


Signature Expression Generation

Signature Expression Generation

```
filter :: (a -> Bool) -> [a] -> [a]
```

Signature Expression Generation

```
filter :: (a -> Bool) -> [a] -> [a]
```

```
filter :: (A -> Bool) -> [A] -> [A]
```

Signature Expression Generation

```
filter :: (a -> Bool) -> [a] -> [a]
```

```
filter :: (A -> Bool) -> [A] -> [A]
```

```
function "filter"  
  (filter :: (A -> Bool) -> [A] -> [A])
```

Signature Expression Generation

```
filter :: (a -> Bool) -> [a] -> [a]
```

```
filter :: (A -> Bool) -> [A] -> [A]
```

```
function "filter"  
  (filter :: (A -> Bool) -> [A] -> [A])
```

```
signature { constants = [...] }
```

Current situation

```
$ cat Reverse.hs
```

```
{-# LANGUAGE NoImplicitPrelude #-}
```

```
module Reverse where
```

```
import Data.List (reverse, sort)
```

Current situation

```
$ cat Reverse.hs
```

```
{-# LANGUAGE NoImplicitPrelude #-}
```

```
module Reverse where
```

```
import Data.List (reverse, sort)
```


```
$ easyspec discover Reverse.hs
```

```
reverse (reverse xs) = xs  
sort (reverse xs) = sort xs
```

Pause slide with a joke

```
safePerformIO :: IO a -> IO a  
safePerformIO ioa = ioa >>= return
```


Automated, but still slow



Definitions

Definitions: Property

Example:

```
reverse (reverse ls) = ls
```

Short for:

```
(\ls -> reverse (reverse ls)) = (\ls -> ls)
```

In general:

```
(f :: A -> B) = (g :: A -> B)  
for some A and B with  
instance Arbitrary A  
instance Eq B
```

Why is this slow?

1. Maximum size of the discovered properties

Why is this slow?

1. Maximum size of the discovered properties
2. Size of the signature

Idea



Critical insight

We are not interested in the entire codebase.

We are interested in a relatively small amount of code.

Reducing the size of the signature

```
inferSignature
  :: [Function] -- Focus functions
-> [Function] -- Functions in scope
-> [Function] -- Chosen functions
```


Full background and empty background

```
inferFullBackground _ scope = scope
```


```
inferEmptyBackground focus _ = focus
```

Full background and empty background

```
inferFullBackground _ scope = scope
```

```
inferEmptyBackground focus _ = focus
```


runtime (time seconds)



Full background and empty background

```
inferFullBackground _ scope = scope
```

```
inferEmptyBackground focus _ = focus
```



Pause slide with a joke

```
safeCoerce :: a ~ b => a -> b  
safeCoerce x = x
```


Syntactic similarity: Name

```
inferSyntacticSimilarityName [focus] scope
  = take 5 $ sortOn
    (\sf ->
      distance
        (name focus) (name sf))
    scope
```

Syntactic similarity: Name


```
inferSyntacticSimilarityName [focus] scope
= take 5 $ sortOn
  (\sf ->
    distance
      (name focus) (name sf))
  scope
```

runtime (time seconds)



Syntactic similarity: Name

```
inferSyntacticSimilarityName [focus] scope  
  = take 5 $ sortOn  
    (\sf ->  
      distance  
        (name focus) (name sf))  
    scope
```




Syntactic similarity: Implementation

```
inferSyntacticSimilaritySymbols i [focus] scope
  = take i $ sortOn
    (\sf ->
      distance
        (symbols focus) (symbols sf))
    scope
```


Syntactic similarity: Implementation


```
inferSyntacticSimilaritySymbols i [focus] scope
= take i $ sortOn
  (\sf ->
    distance
      (symbols focus) (symbols sf))
  scope
```

runtime (time seconds)



Syntactic similarity: Implementation

```
inferSyntacticSimilaritySymbols i [focus] scope
= take i $ sortOn
  (\sf ->
    distance
      (symbols focus) (symbols sf))
  scope
```




Syntactic similarity: Type

```
inferSyntacticSimilarityType i [focus] scope
  = take i $ sortOn
    (\sf ->
      distance
        (typeParts focus) (typeParts sf))
    scope
```

Syntactic similarity: Type


```
inferSyntacticSimilarityType i [focus] scope
= take i $ sortOn
  (\sf ->
    distance
      (typeParts focus) (typeParts sf))
  scope
```

runtime (time seconds)




Syntactic similarity: Type

```
inferSyntacticSimilarityType i [focus] scope
= take i $ sortOn
  (\sf ->
    distance
      (typeParts focus) (typeParts sf))
  scope
```



Breakthrough

Histogram of the number of different functions in an equation



Idea



We can run QuickSpec more than
once!

Inferred Signature

```
type SignatureInferenceStrategy  
  = [Function] -> [Function] -> InferredSignature
```

Inferred Signature

```
type SignatureInferenceStrategy  
  = [Function] -> [Function] -> InferredSignature
```

Combine the results of multiple runs:

```
type InferredSignature = [Signature]
```

Inferred Signature

```
type SignatureInferenceStrategy  
  = [Function] -> [Function] -> InferredSignature
```

Combine the results of multiple runs:

```
type InferredSignature = [Signature]
```

User previous results as background properties:

```
type InferredSignature = Forest Signature
```

Inferred Signature

```
type SignatureInferenceStrategy  
  = [Function] -> [Function] -> InferredSignature
```

Combine the results of multiple runs:

```
type InferredSignature = [Signature]
```

User previous results as background properties:

```
type InferredSignature = Forest Signature
```


Share previous runs:

```
type InferredSignature = DAG Signature
```


Chunks

```
chunks :: SignatureInferenceStrategy
```


```
> chunks  
> [sort :: Ord a => [a] -> [a]]  
> [reverse :: [a] -> [a], id :: a -> a]
```



The runtime of chunks



The outcome of chunks: Relevant equations



Inferred Signature

```
type SignatureInferenceStrategy  
  = [Function] -> [Function] -> InferredSignature
```

```
type InferredSignature =  
  DAG ([[Signature, [Equation]]] -> Signature)
```


Inferred Signature

```
type SignatureInferenceStrategy
  = [Function] -> [Function] -> InferM ()


data InferM a where
  InferPure  :: a -> InferM a
  InferFmap  :: (a -> b) -> InferM a -> InferM b
  InferApp   :: InferM (a -> b) -> InferM a -> InferM b
  InferBind  :: InferM a -> (a -> InferM b) -> InferM b

  InferFrom
    :: Signature
    -> [OptiToken]
    -> InferM (OptiToken, [Equation])
```


Chunks Plus

```
chunksPlus :: SignatureInferenceStrategy
```


```
> chunksPlus  
> [sort :: Ord a => [a] -> [a]]  
> [reverse :: [a] -> [a], id :: a -> a]
```



The runtime of chunks plus



The outcome of chunks plus: Relevant equations



Neat

```
$ time stack exec easyspec \  
    -- discover MySort.hs MySort.mySort  
  
xs <= mySort xs = myIsSorted xs  
mySort xs <= xs = True  
myIsSorted (mySort xs) = True  
mySort (mySort xs) = mySort xs  
  
3.61s user 1.14s system 193% cpu 2.450 total
```

Great promise, but ...

Great promise, but ...

1. Only works for functions in scope of which the type is in scope too.

Great promise, but ...

1. Only works for functions in scope of which the type is in scope too.
2. Crashes on partial functions.

Great promise, but ...

1. Only works for functions in scope of which the type is in scope too.
2. Crashes on partial functions.
3. Only works with built in instances.

Great promise, but ...

1. Only works for functions in scope of which the type is in scope too.
2. Crashes on partial functions.
3. Only works with built in instances.
4. Data has to have an `Arbitrary` instance in scope.

Great promise, but ...

1. Only works for functions in scope of which the type is in scope too.
2. Crashes on partial functions.
3. Only works with built in instances.
4. Data has to have an Arbitrary instance in scope.
5. Does not play with CPP.

Great promise, but ...

1. Only works for functions in scope of which the type is in scope too.
2. Crashes on partial functions.
3. Only works with built in instances.
4. Data has to have an Arbitrary instance in scope.
5. Does not play with CPP.
6. Does not play well with higher kinded type variables.

Great promise, but ...

1. Only works for functions in scope of which the type is in scope too.
2. Crashes on partial functions.
3. Only works with built in instances.
4. Data has to have an Arbitrary instance in scope.
5. Does not play with CPP.
6. Does not play well with higher kinded type variables.

All technical problems, not theoretical problems!

Further Research

1. Can we go faster?

Further Research

1. Can we go faster?
2. Which constants do we choose for built in types?

Further Research

1. Can we go faster?
2. Which constants do we choose for built in types?
3. Can we apply this to effectful code?

Further Research

1. Can we go faster?
2. Which constants do we choose for built in types?
3. Can we apply this to effectful code?
4. Relative importance of equations

Call to action

Proofs of concept:

<https://github.com/nick8325/quickcheck>

<https://github.com/nick8325/quickspec>

<https://github.com/NorfairKing/easyspec>

Now we need to make it production ready!

About Me

This was my master thesis

Wrote Haskell in open source

Taught Haskell at ETH

Haskell and DevOps in industry

<https://cs-syd.eu/>

<https://cs-syd.eu/cv>

<https://github.com/NorfairKing>