

ANNAI MIRA COLLEGE OF ENGINEERING AND TECHNOLOGY


NH-46, Chennai-Bengaluru National Highways, Arappakkam,

Ranipet-632517, Tamil Nadu, India

Telephone: 04172-292925 Fax: 04172-292926

Email:amcet.rtet@gmail.com/info@amcet.in Web: www.amcet.in

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING



CS3591 –COMPUTER NETWORKS LABORATORY

Name :

Register Number :

Year & Branch :

Semester :

Academic Year :

ANNAI MIRA COLLEGE OF ENGINEERING AND TECHNOLOGY

NH-46, Chennai-Bengaluru National Highways, Arappakkam,

Ranipet-632517, Tamil Nadu, India

Telephone: 04172-292925 Fax: 04172-292926

Email:amcet.rtet@gmail.com/info@amcet.in Web: www.amcet.in

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING



CERTIFICATE

This is to Certify that the Bonafide record of the practical work done by.....
Register Number..... of IIIrd year B.E (Computer Science and Engineering)
submitted for the B.E-Degree practical examination(Vth Semester) in **CS3591 – COMPUTER
NETWORKS LABORATORY** during the academic year **2023 – 2024**.

Staff in –Charge

Head of the Department

Submitted for the practical examination held on -----

Internal Examiner

External Examiner

TABLE OF CONTENTS

SL NO.	DATE	EXPERIMENT TITLE	PAGE NO.	SIGN
1		Usage of tcpdump, netstat, ifconfig, nslookup and traceroute, ping and traceroute commands	1	
2		HTTP web client program to download a web page using TCP sockets	3	
3(a)		TCP Socket program for echo client and echo server	6	
3(b)		TCP Socket application for chat	9	
4		Simulation of DNS using UDP sockets.	12	
5(a)		Simulation of ARP protocol	15	
5(b)		Simulation of RARP protocol	18	
6		Study of Network Simulator (NS) and Simulation of Congestion Control Algorithms using NS	21	
7		Study of TCP/UDP performance using Simulation tool	25	
8(a)		Simulation of Distance Vector Routing algorithm	30	
8(b)		Simulation of Link State Routing algorithm	34	
9		Simulation of error correction code (like CRC)	37	

EXP NO: 1	USAGE OF TCPDUMP, NETSTAT, IFCONFIG, NSLOOKUP AND TRACEROUTE, PING AND TRACEROUTE COMMANDS
DATE:	

AIM:

To study the basic networking commands.

NETWORKING COMMANDS:

C:>arp -a: ARP is short form of address resolution protocol, It will show the IP address of your computer along with the IP address and MAC address of your router.

C:>hostname: This is the simplest of all TCP/IP commands. It simply displays the name of your computer.

C:>ipconfig: The ipconfig command displays information about the host (the computer you're sitting at) computer TCP/IP configuration.

C:>ipconfig /all: This command displays detailed configuration information about your TCP/IP connection including Router, Gateway, DNS, DHCP, and type of Ethernet adapter in your system.

C:>Ipconfig /renew: Using this command will renew all your IP addresses that you are currently (leasing) borrowing from the DHCP server. This command is a quick problem solver if you are having connection issues, but does not work if you have been configured with a static IP address.

C:>Ipconfig /release: This command allows you to drop the IP lease from the DHCP server.

C:>ipconfig /flushdns: This command is only needed if you're having trouble with your network's DNS configuration. The best time to use this command is after network configuration frustration sets in, and you really need the computer to reply with flushed.

C:>nbtstat -a: This command helps solve problems with NetBIOS name resolution. (Nbt stands for NetBIOS over TCP/IP)

C:>netdiag: Netdiag is a network testing utility that performs a variety of network diagnostic tests, allowing you to pinpoint problems in your network. Netdiag isn't installed by default, but can be installed from the Windows XP CD after saying no to the install. Navigate to the CD ROM drive letter and open the support\tools folder on the XP CD and click the setup.exe icon in the support\tools folder.

C:>netstat: Netstat displays a variety of statistics about a computer's active TCP/IP connections. This tool is most useful when you're having trouble with TCP/IP applications such as HTTP, and FTP.

C:>nslookup: Nslookup is used for diagnosing DNS problems. If you can access a resource by specifying an IP address but not its DNS name, you have a DNS problem.

C:\>pathping: Pathping is unique to Windows, and is basically a combination of the Ping and Tracert commands. Pathping traces the route to the destination address then launches a 25 second test of each router along the way, gathering statistics on the rate of data loss along each hop.

C:\>ping: Ping is the most basic TCP/IP command, and it's the same as placing a phone call to your best friend. You pick up your telephone and dial a number, expecting your best friend to reply with "Hello" on the other end. Computers make phone calls to each other over a network by using a Ping command. The Ping command's main purpose is to place a phone call to another computer on the network, and request an answer. Ping has 2 options it can use to place a phone call to another computer on the network. It can use the computer's name or IP address.

C:\>route: The route command displays the computer's routing table. A typical computer, with a single network interface, connected to a LAN, with a router is fairly simple and generally doesn't pose any network problems. But if you're having trouble accessing other computers on your network, you can use the route command to make sure the entries in the routing table are correct.

C:\>tracert: The tracert command displays a list of all the routers that a packet has to go through to get from the computer where tracert is run to any other computer on the internet.

RESULT:

Thus the above list of primitives has been studied.

EXP NO: 2	HTTP WEB CLIENT PROGRAM TO DOWNLOAD A WEB PAGE USING TCP SOCKETS
DATE:	

AIM:

To Write a HTTP web client program to download a web page using TCP sockets.

ALGORITHM:

CLIENT SIDE:

- 1) Start the program.
- 2) Create a socket which binds the Ip address of server and the port address to acquire service.
- 3) After establishing connection send the url to server.
- 4) Open a file and store the received data into the file.
- 5) Close the socket.
- 6) End the program.

SERVER SIDE

- 1) Start the program.
- 2) Create a server socket to activate the port address.
- 3) Create a socket for the server socket which accepts the connection.
- 4) After establishing connection receive url from client.
- 5) Download the content of the url received and send the data to client.
- 6) Close the socket.
- 7) End the program.

PROGRAM

```

import javax.swing.*;
import java.net.*;
import java.awt.image.*;
import javax.imageio.*;
import java.io.*;
import java.awt.image.BufferedImage;
import java.io.ByteArrayOutputStream;
import java.io.File;
import java.io.IOException;
import javax.imageio.ImageIO;
public class Client{
public static void main(String args[]) throws Exception{
Socket soc;
BufferedImage img = null;
soc=new Socket("localhost",4000);
System.out.println("Client is running. ");
try {
System.out.println("Reading image from disk. ");
img = ImageIO.read(new File("digital_image_processing.jpg"));
ByteArrayOutputStream baos = new ByteArrayOutputStream();

```

```

ImageIO.write(img, "jpg", baos);
baos.flush();
byte[] bytes = baos.toByteArray();
baos.close(); System.out.println("Sending image to server. ");
OutputStream out = soc.getOutputStream();
DataOutputStream dos = new DataOutputStream(out);
dos.writeInt(bytes.length);
dos.write(bytes, 0, bytes.length);
System.out.println("Image sent to server. ");
dos.close();
out.close();
}catch (Exception e) {
System.out.println("Exception: " + e.getMessage());
soc.close();
}
soc.close();
}
}

```

SERVER PROGRAM

```

import java.net.*;
import java.io.*;
import java.awt.image.*;
import javax.imageio.*;
import javax.swing.*;
class Server {

public static void main(String args[]) throws Exception{
ServerSocket server=null;
Socket socket;
server=new ServerSocket(4000);
System.out.println("Server Waiting for image");
socket=server.accept();
System.out.println("Client connected.");
InputStream in = socket.getInputStream();
DataInputStream dis = new DataInputStream(in);
int len = dis.readInt();
System.out.println("Image Size: " + len/1024 + "KB");
byte[] data = new byte[len];
dis.readFully(data);
dis.close();
in.close();
InputStream ian = new ByteArrayInputStream(data);
BufferedImage bImage = ImageIO.read(ian); JFrame f =
new JFrame("Server"); ImageIcon icon = new
ImageIcon(bImage);

JLabel l = new JLabel();
l.setIcon(icon);
f.add(l);
f.pack();
f.setVisible(true); }}
```

OUTPUT

```
Server Waiting for image  
Client connected.  
Image Size: 29KB
```

RESULT:

The webpage is successfully downloaded and the contents are displayed and verified.

EXP NO: 3(a)	TCP SOCKET PROGRAM FOR ECHO CLIENT AND ECHO SERVER
DATE:	

AIM:

To write a TCP socket program for implementation of echo client and echo server.

ALGORITHM:**CLIENT SIDE**

1. Start the program.
2. Create a socket which binds the Ip address of server and the port address to acquire service.
3. After establishing connection send a data to server.
4. Receive and print the same data from server.
5. Close the socket.
6. End the program.

SERVER SIDE

1. Start the program.
2. Create a server socket to activate the port address.
3. Create a socket for the server socket which accepts the connection.
4. After establishing connection receive the data from client.
5. Print and send the same data to client.
6. Close the socket.
7. End the program.

PROGRAM:**ECHO CLIENT**

```
import java.io.*;
import java.net.*;
public class eclient
{
    public static void main(String args[])
    {
        Socket c=null;
        String line;
        DataInputStream is,is1;
        PrintStream os;
        try
        {
            c=new Socket("localhost",8080);
        }
        catch(IOException e)
        {
            System.out.println(e);
        }
    }
}
```

```

os=new PrintStream(c.getOutputStream());
is=new DataInputStream(System.in);
is1=new DataInputStream(c.getInputStream());
do
{
System.out.println("client");
line=is.readLine();
os.println(line);
if(!line.equals("exit"))
System.out.println("server:"+is1.readLine());
}while(!line.equals("exit"));
}
catch(IOException e)
{
System.out.println("socket closed");
}}}

```

Echo Server:

```

import java.io.*;
import java.net.*;
import java.lang.*;
public class eserver
{
public static void main(String args[])throws IOException
{
ServerSocket s=null;
String line;
DataInputStream is;
PrintStream ps;
Socket c=null;
try
{
s=new ServerSocket(8080);
}
catch(IOException e)
{
System.out.println(e);
}
try
{
c=s.accept();
is=new DataInputStream(c.getInputStream());
ps=new PrintStream(c.getOutputStream());
while(true)
{
line=is.readLine();
System.out.println("msg received and sent back to client");
ps.println(line);
}
}

```

```
    }
    catch(IOException e)
    {
        System.out.println(e);
    }
}
```

OUTPUT:

CLIENT

Enter the IP address 127.0.0.1

CONNECTION ESTABLISHED

Enter the data CSE

Client received CSE

SERVER

CONNECTION ACCEPTED

Server received CSE

RESULT:

Thus the program for simulation of echo server was written & executed.

EXP NO: 3(b)

DATE:

TCP SOCKET APPLICATION FOR CHAT

AIM:

To write a TCP Socket application for chat.

ALGORITHM:

CLIENT

1. Start the program
2. Include necessary package in java
3. To create a socket in client to server.
4. The client establishes a connection to the server.
5. The client accept the connection and to send the data from client to server.
6. The client communicates the server to send the end of the message
7. Stop the program.

SERVER

1. Start the program
2. Include necessary package in java
3. To create a socket in server to client
4. The server establishes a connection to the client.
5. The server accept the connection and to send the data from server to client and
6. vice versa
7. The server communicates the client to send the end of the message.
8. Stop the program.

PROGRAM:

TCPserver1.java

```
import java.net.*;
import java.io.*;

public class TCPserver1
{
    public static void main(String arg[])
    {
        ServerSocket s=null;
        String line;
        DataInputStream is=null,is1=null;
        PrintStream os=null;
        Socket c=null;
        try
        {
            s=new ServerSocket(9999);
        }
```

```

catch(IOException e)
{
System.out.println(e);
}
try
{
c=s.accept();
is=new DataInputStream(c.getInputStream());
is1=new DataInputStream(System.in);
os=new PrintStream(c.getOutputStream());
do
{
line=is.readLine();
System.out.println("Client:"+line);
System.out.println("Server:");
line=is1.readLine();
os.println(line);
}
while(line.equalsIgnoreCase("quit")==false);
is.close();
os.close();
}
catch(IOException e)
{
System.out.println(e);
}
}

```

TCPclient1.java

```

import java.net.*; import java.io.*;
public class TCPclient1
{
public static void main(String arg[])
{
Socket c=null;
String line;
DataInputStream is,is1;
PrintStream os;
try
{
c=new Socket("10.0.200.36",9999);
}
catch(IOException e)
{
System.out.println(e);
}

```

```

try
{
    os=new PrintStream(c.getOutputStream());
    is=new DataInputStream(System.in);
    is1=new DataInputStream(c.getInputStream());
    do
    {
        System.out.println("Client:");
        line=is.readLine();
        os.println(line);
        System.out.println("Server:" + is1.readLine());
    }
    while(line.equalsIgnoreCase("quit")==false);
    is1.close();
    os.close();
}
catch(IOException e)
{
    System.out.println("Socket Closed!Message Passing is over");
}

```

OUTPUT:

SERVER

C:\Program Files\Java\jdk1.5.0\bin>javac TCPserver1.java Note:
 TCPserver1.java uses or overrides a deprecated API. Note:
 Recompile with -deprecation for details. C:\Program
 Files\Java\jdk1.5.0\bin>java TCPserver1

Client: Hai Server
 Server:Hai Client
 Client: How are you
 Server:Fine
 Client: quit
 Server:quit

CLIENT

C:\Program Files\Java\jdk1.5.0\bin>javac TCPclient1.java
 Note: TCPclient1.java uses or overrides a deprecated API.
 Note: Recompile with -deprecation for details. C:\Program
 Files\Java\jdk1.5.0\bin>java TCPclient1

Client:Hai Server
 Server: Hai Client
 Client:How are you
 Server: Fine
 Client:quit
 Server: quit

RESULT:

Thus the above program a client-server application for chat using TCP / IP was executed successfully.

EXP NO: 4	SIMULATION OF DNS USING UDP SOCKETS
DATE:	

AIM:

To write a program for the Simulation of DNS using UDP sockets.

ALGORITHM:

1. Start the program.
2. Get the frame size from the user
3. To create the frame based on the user request.
4. To send frames to server from the client side.
5. If your frames reach the server it will send ACK signal to client otherwise it will send NACK signal to client.
6. Stop the program

PROGRAM:**/ UDP DNS Server****Udpdnsserver**

```
java import java.io.*;
import java.net.*;
public class udpdnsserver
{
    private static int indexOf(String[] array, String str)
    {
        str = str.trim();
        for (int i=0; i < array.length; i++)
        {
            if (array[i].equals(str)) return i;
        }
        return -1;
    }
    public static void main(String arg[])throws IOException
    {
        String[] hosts = {"yahoo.com", "gmail.com","cricinfo.com", "facebook.com"};
        String[] ip = {"68.180.206.184", "209.85.148.19","80.168.92.140", "69.63.189.16"};
        System.out.println("Press Ctrl + C to Quit");
        while (true){
            DatagramSocket serversocket=new DatagramSocket(1362);
            byte[] senddata = new byte[1021];
            byte[] receivedata = new byte[1021];
            DatagramPacket recvpak = new DatagramPacket(receivedata, receivedata.length);
```

```

serversocket.receive(recvpack);

String sen = new String(recvpack.getData()); InetAddress ipaddress =
recvpack.getAddress(); int port = recvpack.getPort();

String capsent;
System.out.println("Request for host " + sen);
if(indexOf(hosts, sen) != -1) capsent = ip[indexOf
(hosts, sen)]; else capsent = "Host Not Found";
senddata = capsent.getBytes();

DatagramPacket pack = new DatagramPacket (senddata, senddata.length,ipaddress, port);
serversocket.send(pack);
serversocket.close();
}
}
}

```

//UDP DNS Client –

```

Udpdnsclient

.java import java.io.*; import java.net.*;
public class udpdnsclient
{
public static void main(String args[])throws IOException
{
BufferedReader br = new BufferedReader(new InputStreamReader(System.in));
DatagramSocket clientsocket = new DatagramSocket();

InetAddress ipaddress; if (args.length == 0)
ipaddress = InetAddress.getLocalHost(); else
ipaddress = InetAddress.getByName(args[0]); byte[] senddata =
new byte[1024];
byte[] receivedata = new byte[1024];
int portaddr = 1362;
System.out.print("Enter the hostname : ");
String sentence = br.readLine();
Senddata = sentence.getBytes();

DatagramPacket pack = new DatagramPacket(senddata,senddata.length, ipaddress, portaddr);
clientsocket.send(pack);

DatagramPacket recvpack =new DatagramPacket(receivedata,receivedata.length);
clientsocket.receive(recvpack);

String modified = new String(recvpack.getData());
System.out.println("IP Address: " + modified);
clientsocket.close();
}
}

```

OUTPUT:**Server**

```
javac updpdnsserver.java  
java updpdnsserver  
Press Ctrl + C to Quit Request for host yahoo.com  
Request for host cricinfo.com  
Request for host youtube.com
```

Client

```
javac uppdnsclient.java  
java uppdnsclient  
Enter the hostname : yahoo.com  
IP Address: 68.180.206.184  
java uppdnsclient  
Enter the hostname : cricinfo.com  
IP Address: 80.168.92.140  
java uppdnsclient  
Enter the hostname : youtube.com  
IP Address: Host Not Found
```

RESULT:

Thus the program to simulate DNS using UP sockets is executed successfully and verified.

EXP NO: 5(a)

DATE:

SIMULATION OF ARP PROTOCOL

AIM

To write a code to simulate ARP (Address Resolution Protocol).

ALGORITHM

CLIENT SIDE

1. Establish a connection between the Client and Server. Socket
ss=new Socket(InetAddress.getLocalHost(),1100);
2. Create instance output stream writer
PrintWriter ps=new PrintWriter(s.getOutputStream(),true);
3. Get the IP Address to resolve its physical address.
4. Send the IPAddress to its output Stream.ps.println(ip);
5. Print the Physical Address received from the server.

SERVER SIDE

1. Accept the connection request by the client.
ServerSocket ss=new ServerSocket(2000);Socket s=ss.accept();
2. Get the IPaddress from its inputstream.
BufferedReader br1=new BufferedReader(new InputStreamReader(s.getInputStream()));
ip=br1.readLine();
3. During runtime execute the processRuntime r=Runtime.getRuntime();
Process p=r.exec("arp -a "+ip);
4. Send the Physical Address to the client.

PROGRAM

ARP CLIENT:

```
import java.io.*; import java.net.*;
class ArpClient
{
public static void main(String args[])throws IOException
{
try
{
Socket ss=new Socket(InetAddress.getLocalHost(),1100);
PrintStream ps=new PrintStream(ss.getOutputStream());
BufferedReader br=new BufferedReader(new InputStreamReader(System.in));
String ip;
System.out.println("Enter the IPADDRESS:");
```

```

ip=br.readLine();
ps.println(ip);
String str,data;
BufferedReader br2=new
BufferedReader(newInputStreamReader(ss.getInputStream()));
System.out.println("ARP From Server::");
do
{
str=br2.readLine();
System.out.println(str);
}
while(!(str.equalsIgnoreCase("end")));
}
catch(IOException e)
{
System.out.println("Error"+e);
}
}
}

```

ARP SERVER

```

import java.io.*;
import java.net.*;

class ArpServer
{
public static void main(String args[])throws IOException
{
try
{
ServerSocket ss=new ServerSocket(1100);
Socket s=ss.accept();
PrintStream ps=new PrintStream(s.getOutputStream());
BufferedReader br1=new BufferedReader(newInputStreamReader(s.getInputStream()));
String ip;
ip=br1.readLine();
Runtime r=Runtime.getRuntime();
Process p=r.exec("arp -a "+ip);
BufferedReader br2=new BufferedReader(newInputStreamReader(p.getInputStream()));
String str;
while((str=br2.readLine())!=null)
{
ps.println(str);
}
catch(IOException e)
{
System.out.println("Error"+e); }
}
}

```

OUTPUT

```
C:\Networking Programs>java ArpServer
C:\Networking Programs>java ArpClient
Enter the IPADDRESS:
192.168.11.58
ARP From Server::
Interface: 192.168.11.57 on Interface 0x1000003
Internet Address Physical Address Type
192.168.11.58 00-14-85-67-11-84 dynamic
```

RESULT:

Thus the implementation of ARP is done & executed successfully.

EXP NO: 5(b)	SIMULATION OF RARP PROTOCOL
DATE:	

AIM:

To write a java program for simulating RARP protocol.

ALGORITHM:**CLIENT**

1. Start the program
2. Using datagram sockets UDP function is established.
2. Get the MAC address to be converted into IP address.
3. Send this MAC address to server.
4. Server returns the IP address to client.

SERVER

1. Start the program.
2. Server maintains the table in which IP and corresponding MAC addresses are stored.
3. Read the MAC address which is send by the client.
4. Map the IP address with its MAC address and return the IP address to client.

CLIENT:

```
import java.io.*; import  
java.net.*; import  
java.util.*; class  
Clientrarp12  
{  
    public static void main(String args[])  
    {  
        try  
        {  
            DatagramSocket client=new DatagramSocket();  
            InetAddress addr=InetAddress.getByName("127.0.0.1");  
            byte[] sendbyte=new byte[1024];  
            byte[] receivebyte=new byte[1024];  
            BufferedReader in=new BufferedReader(new InputStreamReader(System.in));  
            System.out.println("Enter the Physical address (MAC):");  
            String str=in.readLine();  
            sendbyte=str.getBytes();  
            DatagramPacket sender=new DatagramPacket(sendbyte,sendbyte.length,addr,1309);  
            client.send(sender);  
            DatagramPacket receiver=new DatagramPacket(receivebyte,receivebyte.length);  
            client.receive(receiver);  
            String s=new String(receiver.getData()); System.out.println("The
```

```
Logical Address is(IP): "+s.trim()); client.close();  
}  
catch(Exception e)  
{  
    System.out.println(e);  
}  
}  
}
```

SERVER:

```
import java.io.*; import
java.net.*; import
java.util.*; class
Serverarp12
{
    public static void main(String args[])
    {
        try
        {
            DatagramSocket server=new DatagramSocket(1309);
            while(true)
            {
                byte[] sendbyte=new byte[1024];
                byte[] receivebyte=new byte[1024];
                DatagramPacket receiver=new DatagramPacket(receivebyte,receivebyte.length);
                server.receive(receiver);
                String str=new String(receiver.getData()); String
                s=str.trim();
                InetAddress addr=receiver.getAddress();
                int port=receiver.getPort();
                String ip[]{"165.165.80.80","165.165.79.1"};
                String
                mac[]{"6A:08:AA:C2","8A:BC:E3:FA"};
                for(int i=0;i<ip.length;i++)
                {
                    if(s.equals(mac[i]))
                    {
                        sendbyte=ip[i].getBytes();
                        DatagramPacket sender=new DatagramPacket(sendbyte,sendbyte.length,addr,port);
                        server.send(sender);
                    }
                }
            }
        }
    }
}
```

```
        server.send(sender);
        break;

    }
}
break;
}

}
catch(Exception e)
{
    System.out.println(e);

}
}

}
```

OUTPUT:

I:\ex>java Serverarp12

I:\ex>java Clientarp12

Enter the Physical address (MAC):

6A:08:AA:C2

The Logical Address is(IP): 165.165.80.80

RESULT:

Thus the implementation of RARP is done & executed successfully.

EXP NO: 6	STUDY OF NETWORK SIMULATOR (NS) AND SIMULATION OF CONGESTION CONTROL ALGORITHMS USING NS
DATE:	

AIM:

To study of network simulator (ns) and simulation of congestion control algorithms using ns.

SYSTEM REQUIREMENTS:

PC: Pentium or higher

One LAN card onboard or on PCI slot with 10/100Mbps speed.

128MB RAM

500MB free space on Hard
drive CD ROM drive

Serial port, LPT port & USB port installed on system
Operating System: Windows 2000 or higher

THEORY:

LTS-01 Local area network / wireless local area network trainer system:

It is designed to help students understand the basic concepts, modes of operation and protocols involved in networking. The trainer has integrated hardware flow control on panel board for better understanding of different types of LAN topologies involved in networking. The trainer system is provided with windows-based user friendly software with analysis of protocols, different layers, network and measurement of error rate and throughput.

Students can easily do connections in different topologies and can learn actual data transfer either through hardware or through simulated network concept. Facility is provided into system software to introduce errors into packets being sent and analyze the effect of error on different protocols and hence find the effect on throughput graph as well.

Trainer and its various types of experimentation using this system. This system works into server-client base. For any topology user has to select one server and select the network type whether it is LAN or WLAN. To understand the topology concept user can connect two or more clients to hardware. Depending on the topology selected user will have option to select protocols for the selected topology. Upon selection of protocol user can then create network of connected computers.


In any network which is created by user server can send or can communicate with any of the clients however clients can communicate only with server, no client to client communication is possible. Transmitter port protocol & network analysis can be done after communication is over between server and clients. Throughput v/s Packet size graph can be plotted for which at least two file transfers should be carried out. This plot can be printed to attach in the lab exercise sheet.

For the LAN network LAN cards must be installed prior to start work on this trainer. For wireless LAN USB ports should be available on the computers which are to be used for experimentation. In WLAN wireless access cards gets connected to computer USB ports and access point gets connected to hardware device.

L-SIM LAN Protocol Simulator & Analyzer Software:

It is designed to teach the basic concepts, topologies & various protocols involved in networking. The software is provided with analysis of protocols, different layers, network and measurement of error rate and throughput. Facility is provided to introduce errors into packets being sent and analyze the effect of error on different protocols and hence find the effect on throughput graph as well. Software is supported with neat operating instruction manual and online help.

MODEL WINDOW DIAGRAM FOR L-SIM



N-SIM NETWORK SIMULATION SOFTWARE:

It is developed to provide basic understanding and implementation of various advanced concepts in networking. The software provides an opportunity to understand network fundamentals through animations & simulations. The simulation provides for network experimentation with various LAN and WAN protocols, network devices, routers, encryption, decryption, file transfer, error insertion and analysis of error rate and throughput etc. This software covers Ethernet LAN, wireless LAN and router. All networking theory is explained using simulation and animation.

MODEL WINDOW DIAGRAM FOR N-SIM



Rapid advances in computer & communication technologies have resulted in the increasing merger of these two fields. The lines have blurred among computing, switching & digital transmission equipment; and the same digital techniques are being used for data, audio & video transmission. Merging & evolving technologies, coupled with increasing demands for efficient & timely collection, processing & dissemination of information, have led to the development of integrated systems that transmit & process all types of data.

These integrated systems are broadly divided as follows

- **DATA COMMUNICATION** dealing with transmission, transmission media, signal decoding, interfacing, data link control & multiplexing
- **NETWORKING** deals with the technology & architecture of communication network
- **COMMUNICATION PROTOCOLS** which covers the architecture as well as analysis of individual protocols at various layers depending on the hardware & software Network laboratory is designed & developed considering the curriculum offered by Anna University. Trainers offered under network laboratory are designed for students at all level to study and understand all the concepts of data communication, data transfer using serial and parallel ports, Ethernet and wireless LAN with complete protocol understanding and actual hands on with hardware & software with ease.

Network laboratory consists of DCT-03 Data communication trainer kit, LTS- 01 LAN / Wireless LAN training system, L-SIM LAN / WLAN protocol simulator and analyzer software & N-SIM Network simulation software.

The DCT-03: Data communication trainer is a unique trainer kit for the development of exercises and theoretical-experimental courses to understand the basic concept and working of modes and protocols in serial and parallel communication.

The trainer kit consists of functional blocks for serial and parallel communication system.

The trainer kit is highly innovative from a technological as well as an educational point of view. The trainer kit is used as “basic unit” to examine all the peculiar operating standards of serial and parallel communication system. The only external equipments required are two Computers with serial and parallel communication ports and an Oscilloscope. Utmost care has been laid in the design and quality control of all circuits, to ensure the repeatability of the results of the experiments.

Data communication is a term referred when the sender and receiver are digital devices, which communicate with each other by means of binary information. The objective of this trainer kit is to clear the various aspects of the data communications which comprise of

- The information source or sender.
- The medium for carrying information.
- The information receiver.
- The communication protocols, which ensure proper transfer of data.

With an increasing demand in information exchange the field of data communication technique is emerging as the only solution, to satisfy the various needs of today's communication sector and to achieve very high bandwidth along with highest accuracy. The communication media is shifting from analog signal transfer towards digital communication.

With PC becoming the biggest storage devices in digital form, it becomes the main source and destination for information exchange. With rapid growth in both the communication technologies as well as computer hardware and software technologies, these two fields are merged to form a data communication network. Now the digital data is used for data, voice and image transmission.

Depending upon the application the communication link can be of point to point communication between two devices or a multipoint communication between at least 3 devices and data transfer can occur.

RESULT:

The study of network simulator (ns) and simulation of congestion control algorithms using ns is executed and verified.

EXP NO: 7	
DATE:	

STUDY OF TCP/UDP PERFORMANCE USING SIMULATION TOOL

AIM:

To Study of TCP/UDP performance using Simulation tool.

TOOLS USED:

Opnet Simulator

INTRODUCTION:

The transport layer protocols provide connection- oriented sessions and reliable data delivery services. This paper seeks to reflect a comparative analysis between the two transport layer protocols, which are TCP/IP and UDP/IP, as well to observe the effect of using these two protocols in a client server network. The similarities and differences between TCP and UDP over the Internet are also presented in our work. We implement a network structure using Opnet Modeler and finally, based on the practical results obtained we present the conclusions-showing the difference between these two protocols and how they work.

The transport layer is not just another layer. It is the heart of the whole protocol hierarchy. Its task is to provide reliable, cost-effective data transport from the source machine to the destination machine, independently of the physical network or networks currently in use.

TCP and UDP are transport layer components that provide the connection point through which applications access network services. TCP and UDP use IP, which is a lower-layer best effort delivery service. IP encapsulates TCP packets and UDP datagrams and delivers this information across router-connected internet works.

The ultimate goal of the transport layer is to provide efficient, reliable, and cost-effective service to its users, normally processes in the application layer. To achieve this goal, the transport layer makes use of the services provided by the network layer. Without the transport layer, the whole concept of layered protocols would make little sense e.g. The Transport Layer prepares applications data for transport over the network and processes network data to be used by applications. It is responsible for the end-to-end transfer of data over the network and is the four of the OSI model. The Transport layer meets a number of functions:

- enabling the applications to communicate over the network at the same time when using a single device;
- ensure that all amount of data is receive by the correct application;
- responsible for fragmentation and reassembly;
- develop mechanism for handling errors.

Comparison between TCP and UDP

Service	TCP	UDP
Flow controls	The receiver can signal the sender to slow down.	ACKs, which are used in TCP to control packet flow, are not returned.
Connection setup	It takes time, but with TCP reliability is ensured.	No connection is required.
Guaranteed message delivery	Returns acknowledgments.	UDP does not return ACKs, the receiver can't signal that packets have been successfully delivered.
Congestion controls	Network devices can take advantage of TCP ACK to control the behavior of sender.	If ACKs are missing, the network cannot signal congestion to the sender.


A big difference between TCP and UDP is the congestion control algorithm. For the TCP, congestion algorithm prevents the sender from overrunning the network capacity, while TCP can adapt the sender's rate with the network capacity and attempt to avoid potential congestions problems.

User Datagram Protocol (UDP), another transport protocol in IP networks, is described e.g. The User Datagram Protocol (UDP) provides an unreliable connectionless delivery service using IP to transport messages between machines e.g. [5]. It uses IP to carry messages, but adds the ability to distinguish among multiple destinations within a given host computer. Is a connectionless protocol which doesn't provide flow control, reliability or error recovery and the retransmissions of data in case of errors must be ordered by other protocols. UDP is designed for applications that do not have to recompose the data segment that arrives from the sender. In another way, application-level protocols are directly responsible for the security of data transmitted.


Difference from the TCP is that there is no mechanism for error detections. If applications that use UDP doesn't have their own mechanism for information retrieval can lose those data and be forced to retransmitted again. On the other side this applications are not slow down by the confirmation process and the memory will be available for work much faster.

SIMULATION RESULTS:


The simulation time is set for two hours data transfer between LAN network and the server with no packet latency and packet discard ratio of 0% while packets traverse thru the WAN. The task response time, in seconds, Fig. 1, shows how long the application need to be completed. The time when using TCP to complete the task is greater than the one using UDP. When using TCP, source and destination need to perform a three-way handshake before starting sending data and all amount of data need to be acknowledged by the destination when it is received, so it is taking more time than UDP, which doesn't perform this tasks.




1. Response time for TCP and UDP



2. Traffic received (packets/sec) for the server



3. Traffic/Link utilization from the WAN to the server



4. Link utilization with a 0.5% packets discard ratio

The main difference between these two protocols is that TCP provides reliability and congestion control services, while UDP is orientated to improve performance.

The most important and common thing that TCP and UDP are using is the ability to set a host-to-host communication channel, so the packets will be delivered between processes running on two different computers. UDP is the right choice for application where reliability is not a must but the speed and performance is. Instead, TCP, even if it takes more time for the processes, has additional functions like same order delivery, reliability and flow control. As future work, we plan to conduct several studies regarding packets routing in computer networks to improve the fairness of data transmissions using different network protocols.

RESULT:

Thus the TCP/UDP performance has been simulated successfully using OPNET.

EXP NO: 8(a)	SIMULATION OF DISTANCE VECTOR ROUTING ALGORITHM
DATE:	

AIM:

To implement the Distance – Vector Routing Algorithm

APPARATUS REQUIRED:

1. VI-RTSIM software.
2. Personal computer.

THEORY:**Distance Vector Algorithm:**

- ❖ A Distance vector routing, each router periodically share its knowledge about the entire network with it's neighbors.
- ❖ The three keys to under this algorithm are
 1. Knowledge about the whole network.
 2. Routing only to neighbor.
 3. Information sharing at regular intervals.

Knowledge about the whole work:

- ❖ Each router shares its knowledge about entire network. It sends all of its collected knowledge about the network to its neighbors.

Routing only to neighbor:

- ❖ Each router periodically sends its knowledge about the network only to those routers to which it has direct links. It sends whatever knowledge it has.

Information sharing at regular intervals:

- ❖ The every 30 seconds, each router sends its information about the whole network to its neighbors.

Sharing Information:

- ❖ LAN's are connected by router, represented by the assuming A, B, C, D, E and F.
- ❖ Distance vector routing simplifies the routing process by assuming a lost of one unit for every link.

- ❖ The efficiency of transmission is a function only of the number of links required to reach a destination. In this, the cost on hop count.

Routing Table:


- ❖ Each router gets its initial knowledge about the internet work and how it uses shared information to update that knowledge.
- ❖ The routing table has e columns network lost router ID.
- ❖ The first block is final destination of packet.
- ❖ The second block is no of hop count.
- ❖ The third block is that to which a packet delivers must.

Updating algorithm:

- ❖ Updating algorithm requires that the router first has one hop to the hop count field for each advertised router.
- ❖ The router should apply the below rules to each router, if the advertised destination is not in routing table
 - ❖ If next hop field is same, router should replace the entry in the table with advertised one.
 - ❖ If next hop field is same, router should replace the entry in the table with advertised one.
 - ❖ . If next hop field is not the same, advertised hop count is smaller than the one in the table, the router should replace the entry in the table with new one.
 - ❖ IF advertised hop count is not smaller, the router should do no routing.

PROCEDURE:

1. Open VI-RTSIM software from desktop
2. Click the Simulation menu bar
3. Select the “Distance – Vector Routing Algorithm” option from Routing algorithm menu bar.
4. Network with routers connected through link is drawn by using option in editor(add router, join link, delete router, delete link, Add caption to link, add caption to router)
5. Select any two nodes to find the shortest distance between them.
6. Click the Find path Button to run the program.
7. Now the shortest paths between the two nodes are calculated.



Find Shortest Path

Distance vector table:

To	1	2	3	4	5	6	7	8
1	0	300	1000	0	0	0	0	1700
2	300	0	800	0	0	0	0	0
3	1000	800	0	1200	0	0	0	0
4	0	0	1200	0	1500	1000	0	0
5	0	0	0	1500	0	250	0	0
6	0	0	0	1000	250	0	900	1400
7	0	0	0	0	0	0	0	0
8	0	0	0	0	0	0	0	0

Calculate

Distance: From: 2 To:

Node	1	2	3	4	5	6	7	8
Distance	300	0	800	2000	3250	3000	3000	2000

Path:

Node	1	2	3	4	5	6	7	8
Path	2	0	2	3	6	4	8	1

The path is: 5 <- 6 <- 4 <- 3 <- 2

The distance is: 3250

RESULT:

Thus Distance Vector routing algorithm has been implemented and shortest-path has been circulated.

EXP NO: 8(b)

**SIMULATION OF LINK STATE ROUTING
ALGORITHM**

DATE:

AIM:

To implement the Link State Routing Algorithm

APPARATUS REQUIRED:

1. VI-RTSIM software.
2. Personal computer.

THEORY:

Link State Vector Algorithm:

In Link state routing, each router share its information of its neighbors with every other router in the inter-network.

Knowledge about the neighborhood:

Instead of sending its entire routing table, a router sends information about its neighborhood only.

To all routers:

- ❖ Each router send this information to every other router on the internetworking, not just to its neighbors.
- ❖ If s does so by a process called “flooding” it means that a router sends its information.

Information sharing when there is a Change:

Each router sends out information about the neighbors when there is a change.

Information sharing:

- ❖ Link state routing process use the same internet work as distance vector algorithm.
- ❖ Here each other sends its knowledge about is neighbors to every other router in the internet work.
- ❖ Cost is applied only by routers and not by any other station on a network, if cost was added by every station, instead of by routers alone, it would accumulate unpredictably.
- ❖ Cost is applied as a packet leaves the router rather then as if enters. Most networks are broadcast networks. When a packet is in network every station, including the router, can pick it up, we cannot assign any cost to a packet.

Link state packet:

When a router floods the network with information about its neighborhood, it is said to be advertising. The basis of this advertising is a short packet called a link state packet (LSP).

Advertiser	Network	Cost	Neighbor
-------------------	----------------	-------------	-----------------

Getting information about neighbors:

- ❖ A router gets its information about its neighbors by periodically sending them a short greeting packet.
- ❖ If the neighbor responds to the greeting as expected, it is assumed to be alive and functioning.

Initialization:


- ❖ Imagine that all routers in our sample internet work come up at the same time.
- ❖ Each router sends a greeting packet to its neighbors to find out the state of each link.

Link – State Database:

- ❖ Every router runs LSP and puts the information into a link-state database.
- ❖ It stores this database on its disk and uses it to calculate its routing table. If a router is added to or deleted from the system, the whole database must be shared for fast updating.

PROCEDURE:

1. Open VI-RTSIM software from desktop
2. Click the Simulation menu bar
3. Select the “Link State Routing Algorithm” option from Routing algorithm menu bar.
4. Network with routers connected through link is drawn by using option in editor(add router, join link, delete router, delete link, Add caption to link, add caption to router)
5. Select any two nodes to find the shortest distance between them.
6. Click the Find path Button to run the program.
7. Now the shortest paths between the two nodes using link state routing algorithm was calculated.



Find Shortest Path

Link State table:

To	A	B	C	D	E	F	G
A	0	1	0	1	1	0	0
B	1	0	1	0	1	0	0
C	0	1	0	0	1	1	0
D	1	0	0	0	1	0	1
E	1	1	1	1	0	1	0
F	0	0	1	0	1	0	0
G	0	0	0	1	0	0	0

Distance: From: A To:

Calculate

Node	A	B	C	D	E	F	G
Distance	0	1	2	1	1	2	2

Path:

Node	A	B	C	D	E	F	G
Path	0	1	2	1	1	5	4

The path is: F <- E <- A

The distance is: 2

RESULT:

Thus Link-State routing algorithm has been implemented and shortest-path has been circulated.

EXP NO: 9

DATE:

SIMULATION OF ERROR CORRECTION CODE (LIKE CRC)


AIM:

To perform Simulation of Error Correction Code using Java.


THEORY:

CYCLIC REDUNDANCY CHECK (CRC)

- Unlike checksum scheme, which is based on addition, CRC is based on binary division.
- In CRC, a sequence of redundant bits, called cyclic redundancy check bits, are appended to the end of data unit so that the resulting data unit becomes exactly divisible by a second, predetermined binary number.
- At the destination, the incoming data unit is divided by the same number. If at this step there is no remainder, the data unit is assumed to be correct and is therefore accepted.
- A remainder indicates that the data unit has been damaged in transit and therefore must be rejected.



EXAMPLE:



PROCEDURE:

1. Open the editor and type the program for error detection
2. Get the input in the form of bits.
3. Append the redundancy bits.
4. Divide the appended data using a divisor polynomial.
5. The resulting data should be transmitted to the receiver.
6. At the receiver the received data is entered.
7. The same process is repeated at the receiver.
8. If the remainder is zero there is no error otherwise there is some error in the received bits
9. Run the program.

PROGRAM:

```
import java.util.*;
class CRCExample {
    public static void main(String args[]) {
        Scanner scan = new Scanner(System.in);
        int size;
        System.out.println("Enter the size of the data array: ");
        size = scan.nextInt();
        int data[] = new int[size];
        System.out.println("Enter data bits in the array one by one: ");
        for(int i = 0 ; i < size ; i++) {
            System.out.println("Enter bit " + (size-i) + ":");
            data[i] = scan.nextInt();
        }
        System.out.println("Enter the size of the divisor array:");
        size = scan.nextInt();
        int divisor[] = new int[size];
        System.out.println("Enter divisor bits in the array one by one: ");
        for(int i = 0 ; i < size ; i++) {
            System.out.println("Enter bit " + (size-i) + ":");
            divisor[i] = scan.nextInt();
        }
        int rem[] = divideDataWithDivisor(data, divisor);
        for(int i = 0; i < rem.length-1; i++) {
            System.out.print(rem[i]);
        }
        System.out.println("\nGenerated CRC code is: ");

        for(int i = 0; i < data.length; i++) {
            System.out.print(data[i]);
        }
        for(int i = 0; i < rem.length-1; i++) {
            System.out.print(rem[i]);
        }
        System.out.println();
        int sendData[] = new int[data.length + rem.length - 1];
```

```

System.out.println("Enter bits in the array which you want to send: ");
for(int i = 0; i < sentData.length; i++) {
    System.out.println("Enter bit " +(sentData.length - 1)+ ":" );
    sentData[i] = scan.nextInt();
}
receiveData(sentData, divisor);
}

static int[] divideDataWithDivisor(int oldData[], int divisor[]) {
    int rem[] = new int[divisor.length];
    int i;
    int data[] = new int[oldData.length + divisor.length];
    System.arraycopy(oldData, 0, data, 0, oldData.length);
    System.arraycopy(data, 0, rem, 0, divisor.length);
    for(i = 0; i < oldData.length; i++) {
        System.out.println((i+1) + ".) First data bit is : "+ rem[0]);
        System.out.print("Remainder : ");
        if(rem[0] == 1) {
            for(int j = 1; j < divisor.length; j++) {
                rem[j-1] = exorOperation(rem[j], divisor[j]);
                System.out.print(rem[j-1]);
            }
        }
        else {
            for(int j = 1; j < divisor.length; j++) {
                rem[j-1] = exorOperation(rem[j], 0);
                System.out.print(rem[j-1]);
            }
        }
        rem[divisor.length-1] = data[i+divisor.length];
        System.out.println(rem[divisor.length-1]);
    }
    return rem;
}

static int exorOperation(int x, int y) {
    if(x == y) {
        return 0;
    }
}

```

```

    }

    return 1;
}

static void receiveData(int data[], int divisor[]) {
    int rem[] = divideDataWithDivisor(data, divisor);
    for(int i = 0; i < rem.length; i++) {
        if(rem[i] != 0) {
            System.out.println("Corrupted data received...");
            return;
        }
    }
    System.out.println("Data received without any error.");
}
}

```

OUTPUT:

```

Console > CRCExample [Java Application] C:\Users\rastogi ji\p2\pool\plugins\org.eclipse.justj.openjdk.hotspot.jre.full.win32.x86_64\bin>
<terminated> CRCExample [Java Application] C:\Users\rastogi ji\p2\pool\plugins\org.eclipse.justj.openjdk.hotspot.jre.full.win32.x86_64\bin>
Enter the size of the data array:
7
Enter data bits in the array one by one:
Enter bit 7:
1
Enter bit 6:
0
Enter bit 5:
0
Enter bit 4:
1
Enter bit 3:
1
Enter bit 2:
0
Enter bit 1:
1
Enter the size of the divisor array:
4
Enter divisor bits in the array one by one:
Enter bit 4:
1
Enter bit 3:
0
Enter bit 2:
1
Enter bit 1:
1
1.) First data bit is : 1
Remainder : 0101
2.) First data bit is : 0
-
```

```
Console <terminated> CRCExample [Java Application] C:\Users\rastogi ji\p2\pool\plugins\org.eclipse.justj.openjdk.hotspot.jre.full.win32.x86_64
Remainder : 1010
3.) First data bit is : 1
Remainder : 0011
4.) First data bit is : 0
Remainder : 0110
5.) First data bit is : 0
Remainder : 1100
6.) First data bit is : 1
Remainder : 1110
7.) First data bit is : 1
Remainder : 1010
101
Generated CRC code is:
1001101101
Enter bits in the array which you want to send:
Enter bit 9:
1
Enter bit 9:
0
Enter bit 9:
0
Enter bit 9:
1
Enter bit 9:
1
Enter bit 9:
0
Enter bit 9:
1
Enter bit 9:
1
Enter bit 9:
1
<
```

```
Console <terminated> CRCExample [Java Application] C:\Users\rastogi ji\p2\pool\plugins\org.eclipse.justj.openjdk.hotspot.jre.full.win32.x86_64
0
Enter bit 9:
1
Enter bit 9:
1
Enter bit 9:
0
Enter bit 9:
1
1.) First data bit is : 1
Remainder : 0101
2.) First data bit is : 0
Remainder : 1010
3.) First data bit is : 1
Remainder : 0011
4.) First data bit is : 0
Remainder : 0111
5.) First data bit is : 0
Remainder : 1110
6.) First data bit is : 1
Remainder : 1011
7.) First data bit is : 1
Remainder : 0000
8.) First data bit is : 0
Remainder : 0000
9.) First data bit is : 0
Remainder : 0000
10.) First data bit is : 0
Remainder : 0000
Data received without any error.
```

RESULT:

Thus the program for simulation of error correction code by CRC is executed and verified successfully.