

Features

High performance with low power consumption options

Advanced RISC Architecture

131 Instructions over 80% execute in a single cycle

32 x 8 General purpose working registers

Up to 32MHz with 32 MIPS

Internal single cycle multiplier (8x8)

Non-Volatile program and data memory

32Kbytes On-chip programmable Flash Memory

2Kbytes SRAM

Programmable EEPROM supports byte access

Program encryption

Two independently prescaled 8 Bit timers

Input capture and output compare modes

Internal 32KHz oscillator for Real Time Clock function

Up to 9 PWM outputs, Programmable dead-band control

12 Bit High Speed ADC with up to 12 channels

Optional internal or external voltage reference

Programmable Gain Amplifier (X 1/8/16/32)

Differential input channels

Automatic threshold voltage monitoring mode

Internal 1.024V / 2.048V / 4.096V Reference $\pm 1\%$

8 Bit programmable DAC

Watchdog timer

Synchronous and Asynchronous serial Interface

SPI with programmable master/slave TWI compatible

I2C with Master/Slave mode

16 Bit arithmetic accelerator unit (DSC)

SWD debug interface

POR built in power on reset circuit

LVD Low voltage detection circuit

8-bit LGT8XM

RISC Microcontroller with
In-System Programmable
FLASH Memory

LGT8F88P

LGT8F168P

LGT8F328P

Data book

Version 1.0.4 J

● **Packaging** QFP48/32L, SSOP20L

● **Power** 1uA@3.3V

● **Features**

Voltage 1.8V ~ 5.5V

Frequency 0 ~ 32MHz

Temperature -40C ~ +85C

HMB ESD > 4KV

Note: This document has been created for personal use. It is a combination of sources and information. This is not official documentation and is completely unaffiliated with any distribution company or manufacturer. This document is shared freely along with its source on github. This document is provided as-is in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. In no event will the authors and/or contributors be held liable for any damages arising from the use of this document.