## 33.4 Rev. 2545F-08/08

- 1. Updated "ATmega328P Typical Characteristics" on page 401 with Power-save numbers.
- Added ATmega328P "Standby Supply Current" on page 408.

## 33.5 Rev. 2545E-08/08

- Updated description of "Stack Pointer" on page 12.
- 2. Updated description of use of external capacitors in "Low Frequency Crystal Oscillator" on page 32.
- 3. Updated Table 6-9 in "Low Frequency Crystal Oscillator" on page 32.
- 4. Added note to "Address Match Unit" on page 222.
- 5. Added section "Reading the Signature Row from Software" on page 285.
- 6. Updated "Program And Data Memory Lock Bits" on page 294 to include ATmega328P in the description.
- 7. Added "ATmega328P DC Characteristics" on page 316.
- 8. Updated "Speed Grades" on page 316 for ATmega328P.
- 9. Removed note 6 and 7 from the table "2-wire Serial Interface Characteristics" on page 323.
- Added figure "Minimum Reset Pulse width vs. VCC." on page 352 for ATmega48P.
- 11. Added figure "Minimum Reset Pulse width vs. VCC." on page 376 for ATmega88P.
- 12. Added figure "Minimum Reset Pulse width vs. VCC." on page 400 for ATmega168P.
- 13. Added "ATmega328P Typical Characteristics" on page 401.
- 14. Updated Ordering Information for "ATmega328P" on page 435.

## 33.6 Rev. 2545D-03/08

- Updated figures in "Speed Grades" on page 316.
- Updated note in Table 26-4 in "System and Reset Characteristics" on page 320.
- 3. Ordering codes for "ATmega328P" on page 435 updated.
  - ATmega328P is offered in 20 MHz option only.
- 4. Added Errata for ATmega328P rev. B, "Errata ATmega328P" on page 440.

## 33.7 Rev. 2545C-01/08

 Power-save Maximum values removed form "ATmega48P DC Characteristics" on page 314, "ATmega88P DC Characteristics" on page 315, and "ATmega168P DC Characteristics" on page 315.

