

Package ‘NVIDb’

June 25, 2021

Title Facilitating use of Norwegian Veterinary Institute's databases

Version 0.5.4

Date 2021-05-10

Description The Norwegian Veterinary Institute has several internal databases as well as access to data from external databases. This package provides functions to facilitate downloading and processing of data from such databases, in particular PJS and EOS. The package comprises four categories of functions:

- 1) Manage credentials (i.e. password and username),
- 2) Login functions for database services,
- 3) Read, copy and update different in-house data registers,
- 4) Translate codes into descriptions.

NVIDb is dependant of NVIconfig which has to be installed manually from GitHub.

URL <https://github.com/NorwegianVeterinaryInstitute/NVIDb>

BugReports <https://github.com/NorwegianVeterinaryInstitute/NVIDb/issues>

Depends R (>= 3.5.0)

License BSD_3_clause + file LICENSE

Encoding UTF-8

LazyData true

Imports stats,
utils,
checkmate,
data.table,
dplyr,
getPass,
keyring,
magrittr,
poorman (>= 0.2.3),
RODBC,
snakecase,
svDialogs

RoxygenNote 7.1.1

Suggests devtools,
knitr,
remotes,
rmarkdown,
roxygen2,

spelling,
styler,
testthat,
withr

VignetteBuilder knitr
Language en-GB

R topics documented:

add_kommune_fylke	2
add_lokalitet	5
add_MT_omrader	7
add_PJS_code_description	9
add_poststed	12
add_produzent	14
build_query_hensikt	17
build_query_one_disease	18
build_sql_select_year	19
choose_PJS_levels	20
copy_Pkode_2_text	22
copy_Prodtilskudd	23
exclude_from_PJSdata	25
get_PAT	26
login	27
NVIDb	29
PJS_levels	30
read_leveransereg	31
remove_credentials	32
set_dir_NVI	33
standardize_columns	34
standardize_PJSdata	36
Index	38

add_kommune_fylke	<i>Manage translation from komnr to kommune, fylke and current komnr</i>
-------------------	--

Description

Function to add columns with kommune (name), fylkenr, fylke (name), gjeldende_komnr, gjeldende_kommune, gjeldende_fylkenr, and gjeldende_fylke. In addition there are functions to read and copy the translation tables.

Usage

```
add_kommune_fylke(  
  data,  
  translation_table = kommune_fylke,  
  code_column = c("komnr"),  
  new_column = c("gjeldende_komnr", "gjeldende_kommune", "gjeldende_fylkenr",
```

```

    "gjeldende_fylke"),
    position = "right",
    overwrite = FALSE
)

copy_kommune_fylke(
  filename = list("Kommune_UTF8.csv", "komnr_2_gjeldende_komnr_UTF8.csv",
    "Fylke_UTF8.csv"),
  from_path = paste0(set_dir_NVI("GrunndataLand"), "FormaterteData/"),
  to_path = NULL
)

read_kommune_fylke(
  filename = list("Kommune_UTF8.csv", "komnr_2_gjeldende_komnr_UTF8.csv",
    "Fylke_UTF8.csv"),
  from_path = paste0(set_dir_NVI("GrunndataLand"), "FormaterteData/")
)

```

Arguments

<code>data</code>	Data frame with data with a column with old komnr
<code>translation_table</code>	Data frame with the translation table for old komnr to current komnr
<code>code_column</code>	The name of the column with the old komnr
<code>new_column</code>	The name of the new column that should contain the current komnr
<code>position</code>	position for the new columns, can be one of c("first", "left", "right", "last", "keep")
<code>overwrite</code>	When the new column(s) already exist, the content in the existing column(s) is replaced by new data if <code>overwrite = TRUE</code> . If the new columns already exists and <code>overwrite = FALSE</code> , then an error is issued.
<code>filename</code>	Filename of the translation table for old komnr to current komnr
<code>from_path</code>	Path for the source translation table
<code>to_path</code>	Path for the target translation table when copying the translation table

Details

Data sources, like PJS, may provide data with komnr. These functions manage translating komnr to current komnr, kommune and fylke.

`add_kommune_fylke` can be used to translate komnr into kommune (name), fylkenr, fylke (name), `gjeldende_komnr`, `gjeldende_kommune`, `gjeldende_fylkenr`, and `gjeldende_fylke`. The function can also be used to translate fylkenr into fylke (name), `gjeldende_fylkenr`, and `gjeldende_fylke`.

One has to ensure that the code in the dataset represents a komnr or fylkenr. The function will translate any 4 and 2 digits that has the same ID as a kommune or fylke, respectively.

Standard name for the komnr is komnr. If the column with the komnr that should be translated has another name, the parameter `code_column` = can be input as a named vector. Standard names for the new columns are c("kommune", "fylkenr", "fylke", "gjeldende_komnr", "gjeldende_kommune", "gjeldende_fylkenr", "gjeldende_fylke"). Likewise, if the new columns should be given other names than, the parameter `new_column` = can be input as a named vector, see examples.

The function uses a premade translation tables that is made based on information in PJS adresseregister. The translation table is updated when informed that know there is a need, typically when there have been changes in kommune-structure.

position = is used to give the place if the new columns in the data.frame. For position = "right" the new variables are placed to the right of the code_variable. Likewise, for position = "left" the new variables are placed to the left of the code_variable. If position = "first" or position = "last" the new columns are placed first or last, respectively, in the data.frame. A special case occurs for position = "keep" which only has meaning when the new column has the same name as an existing column and overwrite = TRUE. In these cases, the existing column will be overwritten with new data and have the same position.

read_kommune_fylke read the files "komnr_2_gjeldende_komnr_UTF8.csv", Kommune_UTF8.csv, and Fylke_UTF8.csv, into a single data frame that can be used by add_kommune_fylke. Standard setting will read in the file from NVI's internal network. If changing the from_path, the function can be used to read the translation files from other directories. This can be useful if having a stand alone app with no connection the NVI's internal network. In other cases, it should be avoided.

copy_kommune_fylke copy the files komnr_2_gjeldende_komnr_UTF8.csv, Kommune_UTF8.csv, and Fylke_UTF8.csv, respectively, to a given directory.

Value

add_kommune_fylke A data frame where one or more of the columns c("kommune", "fylkenr", "fylke", "gjeldende_komnr", "gjeldende_kommune", "gjeldende_fylkenr", "gjeldende_fylke") have been added in the column(s) to the right of the column with the komnr.

read_kommune_fylke A data frame with the original komnr and the corresponding kommune, fylkenr, fylke, and the current komnr, kommune, fylkenr, fylke. If not changing standard input to the function, the standard file at NVI's internal network is read.

copy_kommune_fylke copies the source translation table for komnr to kommune, for old komnr to current komnr, and for fylkenr to fylke to given directory. If the target file already exists, the source file is copied only when it is newer than the target file.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Examples

```
## Not run:
# Reading from standard directory at NVI's network
kommune_fylke <- read_kommune_fylke()

# Copy standard file from standard location to the subdirectory Data below the working directory
copy_kommune_fylke(to_path = "./Data/")

# Reading from the subdirectory Data below the working directory
kommune_fylke <- read_kommune_fylke(from_path = "./Data/")

# Add new column with current komnr and kommune
# The variable gammelt_komnr should be translated and the new variables with gjeldende_komnr" and
# "gjeldende_kommune" is named komnr and kommune, respectively.
newdata <- add_kommune_fylke(olddata,
  translation_table = kommune_fylke,
  code_column = c("gammelt_komnr" = "komnr"),
  new_column = c("komnr" = "gjeldende_komnr",
```

```

                                "kommune" = "gjeldende_kommune"))

## End(Not run)

```

add_lokalitet	<i>Manage adding extra information to aquaculture sites</i>
---------------	---

Description

Function to add a column with current aquaculture zone and/or coordinates. In addition there are function to read the translation table.

Usage

```

add_lokalitet(
  data,
  translation_table,
  code_column,
  new_column,
  position = "right",
  overwrite = FALSE
)

read_sonetilhorighet(
  filename = "sonetilhorighet.txt",
  from_path = paste0(set_dir_NVI("EksterneDatakilder"), "Lokreg/FormaterteData/Soner/")
)

```

Arguments

data	Data frame with data with a column with a aquaculture site number ("LokNr")
translation_table	Data frame with the table for translating from loknr to the property in question.
code_column	The column with the coded value. Valid values are one of c("LokNr"). If the column in data has another name, it can be input as a named vector, see examples.
new_column	The new columns that should be included into the data frame. The new columns can be one ore more of c("sone", "EastUTM_33N_WGS84", "NorthUTM_33N_WGS84", "Longitude_WGS84", "Latitude_WGS84"). If the new columns in the result data frame should have other names, new_column can be input as a named vector, see examples.
position	position for the new columns, can be one of c("first", "left", "right", "last", "keep")
overwrite	When the new column(s) already exist, the content in the existing column(s) is replaced by new data if overwrite = TRUE. If the new columns already exists and overwrite = FALSE, then an error is issued.
filename	a list with the filenames of the source files with the tables for generating the translation table.
from_path	Path for the source files for the translation table.

Details

`add_lokalitet` can be used to add aquaculture zone to aquaculture sites.

`position` is used to give the place if the new columns in the `data.frame`. For `position = "right"` the new variables are placed to the right of the `code_variable`. Likewise, for `position = "left"` the new variables are placed to the left of the `code_variable`. If `position = "first"` or `position = "last"` the new columns are placed first or last, respectively, in the `data.frame`. A special case occurs for `position = "keep"` which only has meaning when the new column has the same name as an existing column and `overwrite = TRUE`. In these cases, the existing column will be overwritten with new data and have the same position.

`read_sonetilhorighet` reads the file "sonetilhorighet.txt" into a data frame that can be used by other routines. Standard setting will the file read in the latest updated file from NVT's internal network. If changing the `from_path`, the function can be used to read the translation file from other directories. This can be useful if having a stand alone app with no connection the NVT's internal network. In other cases, it should be avoided.

Value

add_lokalitet A data frame where the aquaculture zone and / or coordinates have been added in the column to the right of the column with the LokNr.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Examples

[illegible]

```
## End(Not run)
```

add_MT_omrader	<i>Manage translation from komnr to MT-avdeling and MT-region</i>
----------------	---

Description

Function to add columns with MT_avdelingnr, MT_avdelng (name), MT_regionnr and MT_region (name). In addition there are functions to read and copy the translation tables.

Usage

```
add_MT_omrader(
  data,
  translation_table = komnr_2_MT_omrader,
  code_column = c("komnr"),
  new_column = c("MT_avdelingnr", "MT_avdeling", "MT_regionnr", "MT_region"),
  position = "right",
  overwrite = FALSE
)

copy_MT_omrader(
  filename = list("komnr_2_MT_avdeling.csv", "MT_omrader.csv"),
  from_path = base::paste0(set_dir_NVI("GrunndataLand"), "FormaterteData/"),
  to_path = NULL
)

read_MT_omrader(
  filename = list("komnr_2_MT_avdeling.csv", "MT_omrader.csv"),
  from_path = base::paste0(set_dir_NVI("GrunndataLand"), "FormaterteData/")
)
```

Arguments

data	Data frame with data with a column with a komnr
translation_table	Data frame with the table for translating from komnr to MT_areas
code_column	The column with the coded value. Valid values are one of c("komnr", "MT_avdelingnr", "MT_regionnr"). If the column in data has another name, it can be input as a named vector, see examples.
new_column	The new columns that should be included into the dataframe. The new columns can be up to c("MT_avdelingnr", "MT_avdeling", "MT_regionnr", "MT_region") depending on code_column. If the new columns in the result dataframe should have other names, new_column can be input as a named vector, see examples.
position	position for the new columns, can be one of c("first", "left", "right", "last", "keep")
overwrite	When the new column(s) already exist, the content in the existing column(s) is replaced by new data if overwrite = TRUE. If the new columns already exists and overwrite = FALSE, then an error is issued.

filename	a list with the filenames of the source files with the tables for generating the translation table.
from_path	Path for the source files for the translation table.
to_path	Path to where the source files for the translation table should be copied.

Details

add_MT_omrader can be used to translate the komnr into MT_avdelingnr, MT_avdeling, MT_regionnr and MT_region. The function can also be used to translate MT_avdelingnr into MT_avdeling, MT_regionnr and MT_region or to translate MT_regionnr into MT_region. When the code_column = in the dataframe is not equal to one of c("komnr", "MT_avdelingnr", "MT_regionnr") the code_column = can be input as a named vector. Likewise, if the new columns should be given other names than c("MT_avdelingnr", "MT_avdeling", "MT_regionnr", "MT_region"), the new_column = can be input as a named vector, see examples.

The function uses a premade translation table (komnr_2_MT_avdeling.csv) that is made based on information in PJS adresseregister. The translation table is updated when we know there is a need.

position = is used to give the place if the new columns in the data.frame. For position = "right" the new variables are placed to the right of the code_variable. Likewise, for position = "left" the new variables are placed to the left of the code_variable. If position = "first" or position = "last" the new columns are placed first or last, respectively, in the data.frame. A special case occurs for position = "keep" which only has meaning when the new column has the same name as an existing column and overwrite = TRUE. In these cases, the existing column will be overwritten with new data and have the same position.

read_MT_omrader reads the files "komnr_2_MT_avdeling.csv" and "MT_omrader.csv" into a data frame, usually named komnr_2_MT_omrader. This file is used by add_MT_omrader. If no options to the function is given, the function will read the latest updated files from NVI's internal network. If changing the from_path, the function can be used to read the translation file from other directories. This can be useful if having a script that don't have access to NVI's internal network.

copy_MT_omrader Copies the csv-files "komnr_2_MT_avdeling.csv" and "MT_omrader.csv" to another directory. Thereby, these files are available for read_MT_omrader if they should be read from another directory.

Value

add_MT_omrader A dataframe where the MT_avdelingnr has been added in the column to the right of the column with the komnr.

read_MT_omrader A dataframe with the table for translating from komnr to c("MT_avdelingnr", "MT_avdeling", "MT_regionnr", "MT_region"). If not changing standard input to the function, the standard files at NVI's internal network is read.

copy_MT_omrader Copies the csv-files "komnr_2_MT_avdeling.csv" and "MT_omrader.csv" to another directory. If the target files already exists the source files are only copied if they are newer than the target files.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Examples

```
## Not run:
# Reading from standard directory at NVI's network
```



```

komnr_2_MT_omrader <- read_MT_omrader()

# Copy the csv-files used to generate the translation table from the standard location to
# the subdirectory Data below the working directory
copy_MT_omrader(to_path = "./Data/")

# Reading from the subdirectory Data below the working directory
komnr_2_MT_omrader <- read_MT_omrader(from_path = "./Data/")

# Add new columns with MT_avdelingnr, MT_avdeling, MT_regionnr, and MT_region based on komnr
newdata <- add_MT_omrader(olddata,
  translation_table = list(komnr_2_MT_omrader),
  code_column = "komnr",
  new_column = c("MT_avdelingnr", "MT_avdeling", "MT_regionnr", "MT_region"))

# Add new columns with MT_avdelingnr and MT_avdeling based on komnr. The colname of the column
# with komnr is komnr and the new columns are renamed to MT_avdnr and MT_avd.
newdata <- add_MT_omrader(olddata,
  translation_table = list(komnr_2_MT_omrader),
  code_column = c("komnr" = "komnr"),
  new_column = c("MT_avdnr" = "MT_avdelingnr", "MT_avd" = "MT_avdeling"))

# Add new columns with MT_region based on MT_regionnr. MT_region is renamed to MT_regionnavn
newdata <- add_MT_omrader(olddata,
  translation_table = list(komnr_2_MT_omrader),
  code_column = "MT_region",
  new_column = c("MT_regionnavn" = "MT_region"))

## End(Not run)

```

add_PJS_code_description

Manage translation of PJS-codes to descriptive text

Description

Functions to adds a column with descriptive text for a column with PJS-codes in a dataframe with PJS-data. In addition there are functions to read and copy an updated version of the PJS code registers.

Usage

```

add_PJS_code_description(
  data,
  translation_table = PJS_codes_2_text,
  PJS_variable_type,
  code_colname,
  new_column,
  position = "right",
  overwrite = FALSE
)

```

```

copy_PJS_codes_2_text(
  filename = "PJS_codes_2_text.csv",
  from_path = paste0(set_dir_NVI("Provedata_Rapportering"), "FormaterteData/"),
  to_path = NULL
)

read_PJS_codes_2_text(
  filename = "PJS_codes_2_text.csv",
  from_path = paste0(set_dir_NVI("Provedata_Rapportering"), "FormaterteData/")
)

```

Arguments

<code>data</code>	Dataframe with PJS-data with a column with codes for a PJS-variable
<code>translation_table</code>	Dataframe with the code and the description for PJS-variables
<code>PJS_variable_type</code>	A vector with PJS-variables, for example "hensikt". See details for a list of all PJS-variables included in the premade translation table <code>pjscode_2_descriptions.csv</code> . If more than one code should be translated, they can be given in the vector.
<code>code_colname</code>	The name of the column with codes that should be translated. If several codes should be translated, a vector with the names of the coded variables should be given.
<code>new_column</code>	The name of the new column with the text describing the code. If several codes should be translated, a vector with the new column names should be given.
<code>position</code>	position for the new columns, can be one of <code>c("first", "left", "right", "last", "keep")</code> . If several codes should be translated, either one value to be applied for all may be given or a vector with specified position for each code to be translated should be given.
<code>overwrite</code>	When the new column(s) already exist, the content in the existing column(s) is replaced by new data if <code>overwrite = TRUE</code> . If the new columns already exists and <code>overwrite = FALSE</code> , then an error is issued.
<code>filename</code>	Filename of the source file for the translation table for PJS-codes
<code>from_path</code>	Path for the source translation table for PJS-codes
<code>to_path</code>	Path for the target translation table for PJS-codes when copying the table

Details

Export of data from PJS will produce dataframes in which many columns have coded data. These need to be translated into descriptive text to increase readability.

`add_PJS_code_description` can be used to translate the codes into descriptive text. In a `data.frame` with coded values, the function can return a `data.frame` with the descriptive text in a new column. The descriptive text is input in a new column to the right of the column with codes.

The function uses a premade translation table (`PJS_codes_2_text.csv`) that normally is updated every night from PJS.

Currently, the translation table has PJS-codes and the corresponding description for the following PJS variable types:

- `hensikt`
- `utbrudd`

- registertype (categories for locations and addresses)
- seksjon
- art (species and breed codes to species name)
- artrase (species and breed codes to species or breed name)
- driftsform
- provetype
- provemateriale
- kjonn
- forbehandling
- fysiologisk_stadium
- metode
- konkl_type
- kjennelse
- analytt.

`position =` is used to give the place if the new columns in the data.frame. For `position = "right"` the new variables are placed to the right of the `code_variable`. Likewise, for `position = "left"` the new variables are placed to the left of the `code_variable`. If `position = "first"` or `position = "last"` the new columns are placed first or last, respectively, in the data.frame. A special case occurs for `position = "keep"` which only has meaning when the new column has the same name as an existing column and `overwrite = TRUE`. In these cases, the existing column will be overwritten with new data and have the same position.

`read_PJS_code_registers` reads the file "PJS_codes_2_text.csv" into a dataframe that can be used by `add_PJS_code_description`. In standard setting will the file read in the latest updated file from NVI's internal network. If changing the `from_path`, the function can be used to read the translation file from other directories. This can be useful if having a stand alone app with no connection the NVI's internal network. In other cases, it should be avoided.

PJS_codes_2_text.csv has the following columns: `c("type", "kode", "navn", "utgatt_dato")`, where "type" is the PJS variable type as listed above (for example `hensikt`), "kode" is the variable with the PJS-code, "navn" is the text describing the code, and "utgatt_dato" is the date for last date that the code was valid (NA if still valid). If translation tables are needed for other PJS variables, a dataframe with the same definition can be constructed to translate new variables.

`copy_PJS_code_registers` copies the file `pjsCodeDescriptions.csv` to a chosen directory.

Value

`add_PJS_code_description` A dataframe where the description text for the PJS-code has been added in the column to the right of the column with the code. If the input is a tibble, it will be transformed to a dataframe.

`read_PJS_codes_2_text` A dataframe with the translation table for PJS-codes as read from the source csv-file. If not changing standard input, the standard file at NVI's internal network is read.

`copy_PJS_codes_2_text` Copies the source translation table for PJS-codes to another location. If the target file already exists the source file is only copied if it is newer than the target file.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Examples

```
## Not run:
# Reading from standard directory at NVI's network
PJS_codes_2_text <- read_PJS_codes_2_text()

# Copy standard file from standard location to the subdirectory Data below the working directory
copy_PJS_codes_2_text(to_path = "./Data/")

# Reading from the subdirectory Data below the working directory
PJS_codes_2_text <- read_PJS_codes_2_text("PJS_codes_2_text.csv", "./Data/")

# Translating artkode into art
newdata <- add_PJS_code_description(olddata, PJS_codes_2_text, "art", "artkode", "art")

# Translating hensiktkode into Hensikt and konklusjonkode to Konklusjonskjennelse
newdata <- add_PJS_code_description(olddata,
                                     PJS_codes_2_text,
                                     PJS_variable_type = c("hensikt", "kjennelse"),
                                     code_colname = c("hensiktkode", "konklusjonkode"),
                                     new_column = c("Hensikt", "Konklusjonskjennelse"))

## End(Not run)
```

add_poststed

Manage translation from postnr to poststed and komnr

Description

Function to add columns with poststed and komnr. In addition there are functions to read and copy the translation tables.

Usage

```
add_poststed(
  data,
  translation_table = poststed,
  code_column = c("postnr"),
  new_column = c("poststed", "komnr"),
  position = "right",
  overwrite = FALSE
)

copy_poststed(
  filename = "Poststed_UTF8.csv",
  from_path = paste0(set_dir_NVI("GrunndataLand"), "FormaterteData/"),
  to_path = NULL
)

read_poststed(
  filename = "Poststed_UTF8.csv",
  from_path = paste0(set_dir_NVI("GrunndataLand"), "FormaterteData/")
)
```

Arguments

data	Data frame with data with a column with postnr
translation_table	Data frame with the translation table for postnr to poststed and komnr
code_column	The name of the column with the postnr
new_column	The name of the new column that should contain the poststed and/or komnr
position	position for the new columns, can be one of c("first", "left", "right", "last", "keep")
overwrite	When the new column(s) already exist, the content in the existing column(s) is replaced by new data if overwrite = TRUE. If the new columns already exists and overwrite = FALSE, then an error is issued.
filename	Filename of the translation table for postnr to poststed and komnr
from_path	Path for the source translation table
to_path	Path for the target translation table when copying the translation table

Details

Data sources may provide data with postnr. These functions manage translating postnr to poststed and komnr.

add_poststed can be used to translate postnr to poststed and komnr.

One has to ensure that the code in the data column represents a postnr. The function will translate any 4 digits that has the same ID as a postnr.

Standard name for the postnr is postnr. If the column with the postnr that should be translated has another name, the parameter code_column = can be input as a named vector. Standard names for the new columns are c("poststed", "komnr"). Likewise, if the new columns should be given other names than these, the parameter new_column = can be input as a named vector, see examples.

The function uses a premade translation tables that is generated from information in PJS adresseregister. The translation table is updated when we know there is a need.

position = is used to give the place if the new columns in the data.frame. For position = "right" the new variables are placed to the right of the code_variable. Likewise, for position = "left" the new variables are placed to the left of the code_variable. If position = "first" or position = "last" the new columns are placed first or last, respectively, in the data.frame. A special case occurs for position = "keep" which only has meaning when the new column has the same name as an existing column and overwrite = TRUE. In these cases, the existing column will be overwritten with new data and have the same position.

read_poststed read the file "Poststed_UTF8.csv" a data frame that can be used by add_poststed. Standard setting will read the file from NVI's internal network. If changing the from_path, the function can be used to read the translation files from other directories. This can be useful if having a stand alone app with no connection the NVI's internal network. In other cases, it should be avoided.

copy_poststed copy the file Poststed_UTF8.csv to a given directory.

Value

add_poststed A data frame where one or more of the columns c("poststed", "komnr") have been added in the column(s) to the right of the column with the postnr.

read_poststed A data frame with the original postnr and the corresponding poststed and komnr. If not changing standard input to the function, the standard file at NVI's internal network is read.

copy_poststed copies the source translation table for postnr to poststed and komnr to given directory. If the target file already exists, the source file is copied only when it is newer than the target file.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Examples

```
## Not run:
# Reading from standard directory at NVI's network
poststed <- read_poststed()

# Copy standard file from standard location to the subdirectory Data below the working directory
copy_poststed(to_path = "./Data/")

# Reading from the subdirectory Data below the working directory
poststed <- read_poststed(from_path = "./Data/")

# Add new column with poststed and komnr
# The variable postnummer should be translated into poststed and komnr. For poststed
# the standard name is kept. For komnr the new variable is named postkomnr.
newdata <- add_poststed(olddata,
                        translation_table = poststed,
                        code_column = c("postnummer" = "postnr"),
                        new_column = c("poststed", "postkomnr" = "komnr"))

## End(Not run)
```

add_producent

Manage translation from prodnr8 into gjeldende_prodnr8

Description

Function to add a column with gjeldende_prodnr8. In addition there are functions to read and copy the translation tables.

Usage

```
add_producent(
  data,
  translation_table,
  code_column,
  new_column,
  position = "right",
  overwrite = FALSE
)

copy_prodnr_2_current_prodnr(
  filename = "Prodnr2GjeldendeProdnr.csv",
  from_path = paste0(set_dir_NVI("Prodregister"), "FormaterteData/"),
```

```

    to_path = NULL
  )

  read_prodnr_2_coordinates(
    filename = "Prodnr2Koordinater.csv",
    from_path = paste0(set_dir_NVI("Prodregister"), "FormaterteData/")
  )

  read_prodnr_2_current_prodnr(
    filename = "Prodnr2GjeldendeProdnr.csv",
    from_path = paste0(set_dir_NVI("Prodregister"), "FormaterteData/")
  )

```

Arguments

<code>data</code>	Data frame with data with a column with a <code>prodnr8</code>
<code>translation_table</code>	Data frame with the table for translating from <code>prodnr8</code> to <code>gjeldende_prodnr8</code> .
<code>code_column</code>	The column with the coded value. Valid values are one of <code>c("prodnr8")</code> . If the column in <code>data</code> has another name, it can be input as a named vector, see examples.
<code>new_column</code>	The new columns that should be included into the dataframe. The new columns can be up to <code>c("gjeldende_prodnr8")</code> depending on <code>code_column</code> . If the new columns in the result dataframe should have other names, <code>new_column</code> can be input as a named vector, see examples.
<code>position</code>	position for the new columns, can be one of <code>c("first", "left", "right", "last", "keep")</code>
<code>overwrite</code>	When the new column(s) already exist, the content in the existing column(s) is replaced by new data if <code>overwrite = TRUE</code> . If the new columns already exists and <code>overwrite = FALSE</code> , then an error is issued.
<code>filename</code>	a list with the filenames of the source files with the tables for generating the translation table.
<code>from_path</code>	Path for the source files for the translation table.
<code>to_path</code>	Path for the target translation table when copying the translation table.

Details

`add_producentnr` can be used to translate the `prodnr8` into `gjeldende_prodnr8` and/or `geo-koordinater`.

`position =` is used to give the place if the new columns in the data.frame. For `position = "right"` the new variables are placed to the right of the `code_variable`. Likewise, for `position = "left"` the new variables are placed to the left of the `code_variable`. If `position = "first"` or `position = "last"` the new columns are placed first or last, respectively, in the data.frame. A special case occurs for `position = "keep"` which only has meaning when the new column has the same name as an existing column and `overwrite = TRUE`. In these cases, the existing column will be overwritten with new data and have the same position.

`read_prodnr_2_current_prodnr` reads the file "Prodnr2GjeldendeProdnr.csv" into a data frame that can be used by other routines. Standard setting will the file read in the latest updated file from NVI's internal network. If changing the `from_path`, the function can be used to read the translation file from other directories. This can be useful if having a stand alone app with no connection the NVI's internal network. In other cases, it should be avoided.

copy_prodnr_2_current_prodnr copies the file "Prodnr2GjeldendeProdnr.csv" to a chosen directory.

read_prodnr_2_coodinates reads the file "Prodnr2Koordinater.csv" into a data frame that can be used to merge with data frames with prodnr8. Standard setting will the file read in the latest updated file from NVI's internal network. If changing the from_path, the function can be used to read the translation file from other directories. This can be useful if having a stand alone app with no connection the NVI's internal network. In other cases, it should be avoided.

Value

add_producentnr A data frame where the gjeldende_prodnr8. has been added in the column to the right of the column with the prodnr8.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Examples

```
## Not run:
#CURRENT PRODNr8
# Reading from standard directory at NVI's network
prodnr_2_gjeldende_prodnr <- read_prodnr_2_current_prodnr()

# Copy standard file from standard location to the subdirectory Data below the working directory
copy_prodnr_2_current_prodnr(to_path = "../Data/")

# Reading from the subdirectory Data below the working directory
prodnr_2_gjeldende_prodnr <- read_prodnr_2_current_prodnr(from_path = "../Data/")

prodnr8 <- c("09140087", "14260856", "17020818", "50060129")
olddata <- as.data.frame(prodnr8)

# Add new column with current prodnr8
newdata <- add_producent(olddata,
                        translation_table = prodnr_2_gjeldende_prodnr,
                        code_column = "prodnr8",
                        new_column = "gjeldende_prodnr8",
                        position = "left")

# COORDINATES
# Reading from standard directory at NVI's network
prodnr_2_koordinater <- read_prodnr_2_coordinates()

newdata <- add_producent(newdata,
                        translation_table = prodnr_2_koordinater,
                        code_column = "prodnr8",
                        new_column = c("longitude" = "geo_eu89_o", "latutude" = "geo_eu89_n"))

## End(Not run)
```

build_query_hensikt	<i>Builds query for selecting data for hensikt from PJS</i>
---------------------	---

Description

Builds the query for selecting all data for one or more hensikt within one year from PJS. The query is written in T-SQL as used by MS-SQL.

Usage

```
build_query_hensikt(year, hensikt, db = "PJS")
```

Arguments

year	The year that should be selected as integer. Can be given as one year, the first and last year or a range of years.
hensikt	Vector with one or more hensiktkoder. Sub-hensikter are not included and must be explicitly mentioned.
db	The database for which the query is built. Currently only the value "PJS" is accepted.

Details

The function builds the SQL syntax to select all PJS-journals concerning the hensiktkoder from PJS.

Value

A list with select-statements for v2_sak_m_res and v_sakskonklusjon, respectively. The statements should be included in a RODBC::sqlQuery.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Examples

```
# SQL-select query for Pancreatic disease (PD)
build_query_hensikt(year = 2020,
                    hensikt = c("0200102"))
```

 build_query_one_disease

Builds query for selecting data for one disease from PJS

Description

Builds the query for selecting all data for one infection/disease within one year from PJS. The input is the analytter for the infectious agent and/or disease, the hensikter and metoder specific for the infection and/or disease. The the query is written in T-SQL as used by MS-SQL.

Usage

```
build_query_one_disease(
  year,
  analytt,
  hensikt = NULL,
  metode = NULL,
  db = "PJS"
)
```

Arguments

year	One year or a vector with years giving the first and last years that should be selected as integer.
analytt	One or more analyttkode given as a character. If sub-analytter should be included, end the code with %.
hensikt	Vector with specific hensikter. If sub-hensikter should be included, end the code with %. Can be NULL.
metode	Vector with specific metoder. Can be NULL.
db	The database for which the query is built. Currently only the value "PJS" is accepted.

Details

The function builds the SQL syntax to select all PJS-journals concerning one infection and/o disease from PJS. This is based on selecting all journals with the disease and/or infectious agent analytt in resultat, konklusjon or sakskonklusjon. By this, all journals where the examination have been performed and a result has been entered should be selected.

One or more specific hensikter may be input to the selection statement. With specific hensikt is meant a hensikt that will imply that the sample will be examined for the infectious agent or disease. Thereby, the selection will include samples that haven't been set up for examination yet, samples that were unfit for examination and samples for which wrong conclusions have been entered.

One or more specific metoder may be input to the selection statement. With specific metode is meant a metode that implies an examination that will give one of the input analytter as a result. Thereby, the query will include samples that have been set up for examination, but haven't been examined yet, samples that were unfit for examination and samples for which wrong results have been entered.

To select both the disease analytt and the infectious agent analytt ensures that all journals that have been examined with a result is included in the output. The inclusion of specific hensikter

and metoder, if exists, ensures that all journals received with the purpose of examining for the infectious agent and/or disease will be included even if the examination has not been performed. This is important for a full control of all relevant data for an infectious agent and/or disease.

Value

A list with select-statement fom v2_sak_m_res and v_sakskonklusjon to be included in a RODBCon::sqlQuery.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Examples

```
# SQL-select query for Pancreatic disease (PD)
build_query_one_disease(year = 2020,
  analytt = c("01220104%", "1502010235"),
  hensikt = c("0100108018", "0100109003", "0100111003", "0800109"),
  metode = c("070070", "070231", "010057", "060265"))
```

build_sql_select_year *Builds sql module for selecting year from PJS*

Description

Builds a sql module for selecting one or more years from PJS. This can be included into queries for selecting data from PJS.

Builds a sql module for selecting one or more codes from PJS. This can be included into queries for selecting data from PJS.

Usage

```
build_sql_select_year(year, varname, db = "PJS")

build_sql_select_code(values, varname, db = "PJS")
```

Arguments

year	the year that should be selected as integer. Can be given as one year, the first and last year or a range of years.
varname	The variable name of the variable from which the coded values should be selected
db	the database for which the query is built. Currently only the value "PJS" is accepted.
values	the value of the codes that should be selected given as character. If sub-codes should be included, add " after the code, see example.

Details

The function builds the SQL syntax to select one or more consecutive years from PJS.

The function builds the SQL syntax to select one or more codes for one variable from PJS.

Value

a SQL-code for selecting year from PJS to be included when building select-statements.

a SQL-code for selecting the codes from PJS to be included when building select-statements .

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Petter Hopp Petter.Hopp@vetinst.no

Examples

```
# SQL-select module for selecting year from PJS
build_sql_select_year(year = 2020, varname = "aar")

build_sql_select_year(year = c(2019, 2021), varname = "aar")

build_sql_select_year(year = c(2019:2021), varname = "aar")

# SQL-select module for selecting hensiktkode from PJS
build_sql_select_code(values = "0100101", varname = "hensiktkode", db = "PJS")

build_sql_select_code(values = "0100101%", varname = "hensiktkode", db = "PJS")

build_sql_select_code(values = c("0100101", "0100101007", "0100102%", "0100202%"),
                      varname = "hensiktkode",
                      db = "PJS")
```

choose_PJS_levels

Choose columns from specified PJS-levels

Description

Fast way to specify the variables from specific PJS-levels.

Usage

```
choose_PJS_levels(
  data,
  levels,
  keep_col = NULL,
  remove_col = NULL,
  unique_rows = TRUE
)
```



```

        "uttatt_parprove", "mottatt_parprove",
        "eksportland", "importdato",
        "tidl_eier", "avkom_imp_dyr",
        "okologisk_drift", "skrotnr", "kjonn",
        "fodselsdato", "konklnr"),
    unique_rows = TRUE)

sak_prove_und_res <- choose_PJS_levels(PJSdata,
    levels = c("sak", "prove", "undersokelse", "resultat"),
    remove_col = c("vet_distriktnr", "karantene",
        "kartreferanse", "epi_id", "landnr",
        "uttatt_parprove", "mottatt_parprove",
        "eksportland", "importdato",
        "tidl_eier", "avkom_imp_dyr",
        "okologisk_drift", "skrotnr", "kjonn",
        "fodselsdato"),
    unique_rows = TRUE)

## End(Not run)

```

copy_Pkode_2_text	<i>Manage translation table for produksjonstilskuddskoder (Pkoder)</i>
-------------------	--

Description

Read and copy the translation table for produksjonstilskuddskoder (Pkoder).

Usage

```

copy_Pkode_2_text(
  filename = "Produksjonstilskuddskoder_UTF8.csv",
  from_path = paste0(set_dir_NVI("Prodtilskudd"), "StotteData/"),
  to_path = NULL
)

read_Pkode_2_text(
  filename = "Produksjonstilskuddskoder_UTF8.csv",
  from_path = paste0(set_dir_NVI("Prodtilskudd"), "StotteData/")
)

```

Arguments

filename	name of the translation table, standard name is "Produksjonstilskuddskoder_UTF8.csv"
from_path	Path for the translation table for produksjonstilskuddskoder
to_path	Path for the target translation table when copying produksjonstilskuddskoder

Details

The translation table for Pkoder contains the Pkoder, descriptive text, unit of interest (Dyr), whether the code counts unique animals or not (used when summarising number of animals), and sorting to order the Pkoder. The register covers 2017 and later.

read_Pkode_2_text reads the file "Produksjonstilskuddskoder_UTF8.csv" into a data frame. The standard settings will read the file from NVI's internal network. If changing the from_path, the function can be used to read the translation file from other directories. This can be useful if having a stand alone app with no connection the NVI's internal network. In other cases, it should be avoided.

copy_Pkode_2_text copies the file Produksjonstilskuddskoder_UTF8.csv to a given location.

Value

Data frame with the translation table for produksjonstilskuddskoder.

read_Pkode_2_text A data frame with the translation table for Pkoder to description as read from the csv file. If not changing standard input to the function, the standard file at NVI's internal network is read.

copy_Pkode_2_text Copies the source translation table "Produksjonstilskuddskoder_UTF8.csv" to another location. If the target file already exists, the source file is only copied when it is newer than the target file.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Examples

```
## Not run:
# Reading from standard directory at NVI's network
Pkode_2_text <- read_Pkode_2_text()

# Copy standard file from standard location to the sub directory Data below the working directory
copy_Pkode_2_text(to_path = "./Data/")

# Reading from the sub directory Data below the working directory
Pkode_2_text <- read_Pkode_2_text(from_path = "./Data")

## End(Not run)
```

copy_Prodtilskudd

Read Register for søknad om produksjonstilskudd

Description

Functions to to read and copy versions of the produksjonstilskuddsregister.

Usage

```
copy_Prodtilskudd(
  from_path = paste0(set_dir_NVI("Prodtilskudd"), "FormaterteData/"),
  to_path = NULL,
  Pkode_year = "last",
  Pkode_month = "both"
)
```

```
read_Prodtilskudd(
  from_path = paste0(set_dir_NVI("Prodtilskudd"), "FormaterteData/"),
  Pkode_year = "last",
  Pkode_month = "both"
)
```

Arguments

from_path	Path for the produksjonstilskuddsregister.
to_path	Target path for the files with the produksjonstilskuddsregister.
Pkode_year	The year(s) from which the register should be read. Options is "last", or a vector with one or more years.
Pkode_month	the month for which the register should be read. The options are c("05", "10", "both", "last") for Pkode_year = 2017 and c("03", "10", "both", "last") for Pkode_year >= 2018.

Details

The produksjonstilskuddsregister includes information on number of animals that the produsent has applied subsidies for at the counting dates. Since 2017, the counting dates are in March and October. Landbruksdirektoratet provides three to four versions of the register for each counting date. The functions automatically selects the last updated version of the register.

`read_Prodtilskudd` Reads the produksjonstilskuddsregister into a data frame. The function gives options to select year and season. The standard settings will read in the files from NVI's internal network and select the latest updated file for both spring and autumn and combine them into one file. If changing the `from_path`, the function can be used to read the translation file from other directories. This can be useful if having a stand alone app with no connection to the NVI's internal network. In other cases, it should be avoided.

`copy_Prodtilskudd` copies the source produksjonstilskuddsregister for each of the year and seasons selected to a given directory.

Value

`read_Prodtilskudd` One or more data frame(s) with the produksjonstilskuddsregister for each of the year and seasons selected. If the options `Pkode_year = "last"` and `Pkode_month = "last"` is given, one file with the last produksjonstilskuddsregister is given.

`copy_Prodtilskudd` copies the source produksjonstilskuddsregister for each of the year and seasons selected. If the target file already exists, the source files are copied only when newer than the target file.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Examples

```
## Not run:
# Reading from standard directory at NVI's network
Pkode_last <- read_Prodtilskudd()

# Reading from standard directory at NVI's network and selecting a specific version of the register
Pkode201903 <- read_Prodtilskudd(Pkode_year = "2019", Pkode_month = "03")
```



```
## End(Not run)
```

exclude_from_PJSdata *exclude rows from PJS-data*

Description

Performs common subsetting of PJS-data by excluding rows

Usage

```
exclude_from_PJSdata(PJSdata, abroad = "exclude", quality = "exclude")
```

Arguments

PJSdata	Data frame with data extracted from PJS.
abroad	If "exclude" are samples from abroad be excluded. Allowed values are c("exclude", "include").
quality	If "exclude" are samples registered as quality assurance and ring trials excluded. Allowed values are c("exclude", "include").

Details

Performs common cleaning of PJSdata by removing samples that usually should not be included when analyzing PJSdata. The cleaning is dependent on having the following columns eier_lokalitettype, eierlokalitetnr and hensiktkode.

abroad = "exclude" will exclude samples that have eier_lokalitet of type "land" and eier_lokalitetnr being different from NO. Samples registered on other types than LAND are not excluded.

quality = "exclude" will exclude all samples registered s quality assurance and ring trials, i.e. hensiktkode starting with "09".

Value

data frame without excluded PJS-data.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Examples

```
## Not run:
# cleaning sak_m_res
sak_m_res <- exclude_from_PJSdata(PJSdata = sak_m_res, abroad = "exclude", quality = "exclude")

## End(Not run)
```

`get_PAT`*Manage personal access token (PAT) for internet services*

Description

Save or remove the current user's PAT for internet services in the the user profile.

Usage

```
get_PAT(service)
```

```
remove_PAT(service)
```

```
set_PAT(service)
```

Arguments

<code>service</code>	Name of the internet service, for example "GitHub". For internet services where one don't use the premade wrappers, the name can be chosen freely, but must be the same as used in <code>get_PAT</code>
----------------------	---

Details

For internet services like GitHub, personal access tokens can replace username and password when accessing the service. To simplify the access to the internet services when using R, the function `set_PAT` makes it possible to save the personal access token (PAT) in the user profile at the current machine. When the PAT has been saved in the user profile, the functions `get_PAT` will automatically get the PAT for use in code accessing the internet service.

The user profile is not copied between computers. Consequently, if a user runs scripts with `get_PAT` on different computers, the PAT has to be saved at each computer separately.

`set_PAT(service)` is used to set the PAT for a internet service. The PAT are input using windows and saved in the users profile at the current computer. When the PAT for the service has been changed, `set_PAT(service)` can be used to update the PAT.

`get_PAT(service)` is used to get the PAT for a internet service that previously has been saved in the users profile at the current computer.

`remove_PAT(service)` is used to delete the PAT for a internet service from the user's profile.

Value

`set_PAT` The PAT for a internet service are saved in the user profile at the current computer.

`get_PAT` The PAT for a internet service are fetched from the user profile at the current computer to be used in R-scripts.

`remove_PAT` The PAT for a internet service are deleted from the user profile at the current computer.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Examples

```
## Not run:
set_PAT("GitHub")

get_PAT("GitHub")

remove_PAT("GitHub")

## End(Not run)
```

login

*Log in to data base services***Description**

Log in to NVI's data base services, in particular journal_rapp/PJS and EOS.

Usage

```
login(
  dbservice,
  dbdriver = NULL,
  db = NULL,
  dbserver = NULL,
  dbport = NULL,
  dbprotocol = NULL
)

login_PJS()

login_EOS()

login_by_credentials(
  dbservice,
  dbdriver = NULL,
  db = NULL,
  dbserver = NULL,
  dbport = NULL,
  dbprotocol = NULL
)

login_by_credentials_PJS()

login_by_credentials_EOS()

login_by_input(
  dbservice,
  dbdriver = NULL,
  db = NULL,
  dbserver = NULL,
```

```

    dbport = NULL,
    dbprotocol = NULL,
    dbtext = NULL
)

login_by_input_PJS()

login_by_input_EOS()

```

Arguments

dbservice	Name of the database service, for example "PJS" or "EOS". For database services where one don't use the premade wrappers, the name can be chosen freely, but must be the same as used in <code>set_credentials</code>
dbdriver	Name of database engine
db	Name of database
dbserver	Name of database server
dbport	Port
dbprotocol	Protocol to be used
dbtext	used in login with input. Gives the possibility of showing another name than the dbservice in the windows asking for username and password.

Details

The NVI has access to several database services. These functions log in to such services. The functions provides methods to either log in using credentials set in the user profile by `set_credentials` or use input windows for username and password. Thereby the hard coding of username and password can be avoided.

`login` is general functions where all necessary specifications like server name and database name of the database must be input. The database provider can give information on what specifications that has to be used. This can be used to log in to many different databases. In the case that one login to a database service for which the connection parameters have been predefined (i.e. PJS, EOS, sea_sites and Fallvilt), it will be sufficient to provide the parameter `dbservice`.

Depending on whether username and password have been saved in the users profile at the current computer or not, the user is asked to input credentials.

`login_by_input` is general functions where all necessary specifications like server name and database name of the database must be input. In the case that one login to a database service for which the connection parameters have been predefined (i.e. PJS, EOS, sea_sites and Fallvilt), it will be sufficient to provide the parameter `dbservice`. The user is always asked to input username and password.

`login_by_credentials` is general functions where all necessary specifications like server name and database name of the database must be input. In the case that one login to a database service for which the connection parameters have been predefined (i.e. PJS, EOS, sea_sites and Fallvilt), it will be sufficient to provide the parameter `dbservice`. The user is never asked for username and password, and the function can only be used when the credentials previously have been set in the user's profile at the current computer.

`login_PJS`, `login_by_input_PJS`, and `login_by_credentials_PJS` are wrappers for the functions above where the specifications for the database journal_rapp/PJS have been preset. The user only need to input username and password or if the username and password for journal_rapp/PJS are stored in the user profile at the current computer, the user is automatically logged in to journal_rapp.

If the password is no longer valid, an error occur. If so, the user must update the username and password by `set_credentials_PJS`.

`login_EOS`, `login_by_input_EOS`, and `login_by_credentials_EOS` are wrappers for the functions above where the specifications for the database EOS have been preset. The user only need to input username and password or if the credentials are saved in the users profile by `set_credentials_EOS`, no input is needed.

The login functions returns an open ODBC-channel to the database service. The database can then be queried by using functions in the package RODBC.

When the session is finished, the script shall close the ODBC-channel by `odbcClose("myodbcchannel")` or `odbcCloseAll`.

Value

An open ODBC-channel to the database service.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

See Also

[set_credentials](#)

Examples

```
## Not run:
require(RODBC)
journal_rapp <- login_PJS()
# Reads hensiktregistret from PJS
hensikter <- sqlQuery(journal_rapp,
                      "select * from v_hensikt",
                      as.is = TRUE,
                      stringsAsFactors = FALSE)
#
odbcClose(journal_rapp)

## End(Not run)
```

Description

The NVIDb package provides functions to facilitate downloading and processing of data from NVI's databases, in particular PJS and EOS. The package comprises four categories of functions: manage credentials, login, read and copy data from in-house data registers and translation of codes into descriptive text.

Manage credentials

Set and remove credentials (i.e. password and user name) in the user profile at the current machine. These functions makes it possible to connect to database services automatically in scripts while avoiding hard coding of the password and the user name.

Login

These functions use the credentials set by functions for managing credentials to automatically login to database services. If the credentials have not been set, there are also login function for interactive input of credentials in windows when running scripts.

Read, copy and update R-data from in-house data registers

The NVI has copies of several data registers like kommuneregister, fylkesregister, register for søknad om Produksjonstilskudd. The aim of these functions are to make these registers easily accessible for R-scripts to ensure that one always uses the latest version of data. These functions reads the registers from where they are saved at NVI internal file system. If necessary, there are function to copy or update the registers to local directories when local versions are needed for example for shiny applications.

Translate codes into descriptive text

Data often only includes codes that should be translated into the description text. These functions perform the translation for PJS-codes and codes like komnr.

PJS_levels	<i>Data: Variables per PJS-level.</i>
------------	---------------------------------------

Description

A data frame with the variable names (column names) in PJS and their corresponding PJS-level. The column names are the standardized column names, i.e. after running NVIdb::standardize_columns. The raw data can be edited in the ./data-raw/PJS_levels.xlsx and the code for preparing of the data frame is written in ./data-raw/generate_PJS_levels.R. The PJS_levels is used as input for NVIdb::select_PJS_levels.

Usage

```
PJS_levels
```

Format

A data frame with 7 variables:

variable column name for variables read from PJs and standardized using NVIdb::standardize_columns

sak columns at sak-level are given value 1

prove columns at prove-level are given value 1

delprove columns at delprove-level are given value 1

undersokelse columns at undersokelse-level are given value 1

resultat columns at resultat-level are given value 1

konklusjon columns at konklusjon-level are given value 1

Details

The variables included into a specific level is given the value 1, if not included they are given the value 0. To ensure that information on a specific level can be traced to the correct sak, all index variables are given value 1.

Source

./data-raw/PJS_levels.xlsx in package NVIdb

read_leveransereg	<i>Read Leveranseregisteret for slakt</i>
-------------------	---

Description

Functions to read Leveranseregisteret for slakt.

Usage

```
read_leveransereg(
  filename,
  from_path = paste0(set_dir_NVI("LevReg"), "FormaterteData/")
)
```

Arguments

filename	The name of the file with Leveranseregisteret
from_path	Path for Leveranseregisteret

Details

The Leveranseregisteret for slakt includes information on carcasses delivered to slaughter. The register include identity of the farmer, slaughterhouse, date of slaughter, animal species, category (age group and sex), and weight. For poultry the individual animal is not reported, but number of slaughtered poultry per categories, slaughterhouse and date.

read_Prodtilskudd Reads the Leveranseregisteret for slakt into a data frame. The standard settings will read in the files from NVI's internal network. If changing the from_path, the function can be used to read Leveranseregisteret from other directories. This can be useful if having a stand alone app with no connection the NVI's internal network. In other cases, it should be avoided.

Value

read_LevReg A data frame with Leveranseregisteret as in selected csv-file.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Examples

```
## Not run:
# Reading from standard directory at NVI's network
Lev>>Reg2019 <- read_leveransereg(filename = "LevReg_201901_201912.csv")

## End(Not run)
```

remove_credentials	<i>Manage username and password (credentials) for database services at NVI</i>
--------------------	--

Description

Save or remove the current user's username and password for the data base services at the Norwegian Veterinary Institute in the the user profile.

Usage

```
remove_credentials(dbservice)

set_credentials(dbservice)

set_credentials_PJS()

set_credentials_EOS()
```

Arguments

dbservice	Name of the database service, for example "PJS" or "EOS". For database services where one don't use the premade wrappers, the name can be chosen freely, but must be the same as used in login and login_by_credentials
-----------	---

Details

The Norwegian Veterinary Institute has access to various database services. To simplify the access to the database services when using R, the function `set_credentials` makes it possible to save the username and password (credentials) in the user profile at the current machine. When the username and password have been saved in the user profile, the functions `login` or `login_by_credentials` will automatically log in to the database services without any need of new input of username and password.

The user profile is not copied between computers. Consequently, if a user runs scripts with `login` on different computers, the credentials have to be saved at each computer separately.

`set_credentials(dbservice)` is used to set the username and password for a database service. The username and password are input using windows and saved in the users profile at the current computer. When the password for the database service have been changed, `set_credentials(dbservice)` can be used to update the password.

`set_credentials_PJS` is a wrapper for `set_credentials(dbservice)` used to set the username and password for `journal_rapp/PJS`. `Journal_rapp` has views to information in PJS and some other internal databases at NVI. The username and password are the same as for PJS. When the password for PJS have been changed, `set_credentials_PJS` can be used to update the password.

set_credentials_EOS is a wrapper for set_credentials(dbservice) used to set the username and password for EOS. EOS has tables with surveillance data reported to the Norwegian Food Safety Authority.

remove_credentials(dbservice) is used to delete the credentials for a database service from the user's profile.

Value

set_credentials The username and password for a database service are saved in the user profile at the current computer.

remove_credentials The username and password for a database service are deleted from the user profile at the current computer.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

See Also

[login](#) and [login_by_credentials](#)

Examples

```
## Not run:
set_credentials(dbservice)

set_credentials_PJS()

set_credentials_EOS()

remove_credentials("PJS")

## End(Not run)

# NULL
```

set_dir_NVI

Set directories for data sources at NVI

Description

Set the directories for various data sources at NVI's network.

Usage

```
set_dir_NVI(datasource)
```

Arguments

datasource	The data source that one want to access. To identify short names for the available directories, use set_dir_NVI(datasource = "?").
------------	--

Details

The Norwegian Veterinary Institute has standard data sources at fixed directories. The function returns the standard directory for the given data source. Thereby hard coding of the paths may be avoided.

Value

The full path for the directory at NVI's network.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Examples

```
## Not run:
# Set path_ProdTilskudd to path for Prodtilskudd at the NVI network
prodtilskudd_path <- set_dir_NVI(datasource = "ProdTilskudd")

## End(Not run)
```

standardize_columns	<i>Standardize columns for scripts and reports</i>
---------------------	--

Description

Standardizes column names, labels, column width for variables in external databases.

Usage

```
standardize_columns(
  data,
  dbsource = deparse(substitute(data)),
  standards = NULL,
  property,
  language = "no",
  exclude = FALSE
)
```

Arguments

data	Data frame or if property = "colclasses" the path and filename of the csv-file used as data source
dbsource	database source of data. Set to data if not specifically specified. Needed if translation to column names is dependent on data source
standards	to input alternative standard tables to column_standards
property	Property of the column that should be standardized, currently c("colnames", "colclasses", "collabels", "colwidths_Excel", "colorder").
language	Language for labels. Valid input are c("no", "en")
exclude	Used in combination with property = "colorder". exclude = TRUE excludes all columns with no predefined colorder.

Details

Experimental, the standardization table is under development. This version only works when being connected to the NVI network.

Variables in internal and external data sources uses different variable names for the same content. Standardize_columns standardizes column names for use in scripts. It will be further developed to standardize column labels and column widths for both Excel and DT. Furthermore, input values for the parameter colClasses = for read.csv2 can be generated.

property = "colnames" will replace the column names in a data frame with standardized column names. All standard column names is snake_case. If no standard name is defined for a variable name, the variable name is translated to snake_case and the national characters c("æ", "ø", "å") are translated to c("ae", "oe", "aa").

property = "colclasses" will generate a named vector with the column classes for variables that may not be read correct when importing data from a csv-file. This applies for example to numbers with leading zero that must be imported as character. This vector can be used as a parameter for colClasses = .

property = "collabels" will generate a vector with column labels that can be used to replace the column names in the header of the data table. The column names are not changed automatically but can be changed by using a colname statement (see help). If no standard column label is defined, the column name as Sentence case is used as column label. If English names are used and no English column label exists, the Norwegian column label is used instead.

property = "colwidths_Excel" will generate a vector with column widths for Excel. To be used as input parameter to openxlsx::colwidth(). If no standard column width is defined, the Excel standard width of 10.78 is used. Be aware that the generation of column widths are based on the column names. Do not change the column names to labels before the column widths are generated.

property = "colorder" will generate a data frame with the column names in a predefined order. The column names should first have been standardized. No standard order will be given unless the dbsource is defined in the column_standards table. If exclude = FALSE (the standard) the columns with no predefined order will be moved to the last columns in the same order as they appeared in the original data frame. If exclude = TRUE all columns with no predefined order is excluded from the data frame. This option is mainly intended for well defined and worked through routines like making selections lists for the Food Safety Authority. Do not use exclude = TRUE unless you are certain that all columns that should be included are defined in the column_standards table for this dbsource. If uncertain, you may first try with exclude = FALSE and thereafter compare with exclude = TRUE to check if you loose important information.

Value

property = "colnames". A data frame with standard column names.

property = "colclasses". a named vector of column classes to be used as input to functions for reading csv-files.

property = "collabels". a vector with labels for the columns in the data frame.

property = "colwidths_Excel". a vector with column widths for Excel. To be used as input parameter to openxlsx::colwidth().

property = "colorder". A data frame with column names in predefined order. If exclude = TRUE only columns with a defined order is included

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Examples

```
## Not run:
# Generate data frame to be standardized
df <- cbind("\u00C5r" = 2020, "Hensiktkode" = "01001", komnr = "5001")
colnames(df)

# Standardize column names
df <- standardize_columns(data = df, property = "colnames")
colnames(df)

# Generate vector with standard labels
labels <- standardize_columns(data = df, property = "collabels")
# use the labels as column names
colnames(df) <- labels

# Generate vector with standard column widths for Excel
colwidths <- standardize_columns(data = df, property = "colwidths_Excel")
colwidths

## End(Not run)
```

standardize_PJSdata	<i>Standardizing PJS-data</i>
---------------------	-------------------------------

Description

Standardizing PJS-data that always should be performed.

Usage

```
standardize_PJSdata(PJSdata, dbsource = "v2_sak_m_res")
```

Arguments

PJSdata	Data frame with data extracted from PJS.
dbsource	If specified, this will be used for standardize columns when selecting standard column names

Details

The function performs the following standardizing of data extracted from PJS: - The unnecessary columns konkl_provenr and vet_distriktnr are removed, - The column names are standardized using standardize_columns, - Numeric variables are transformed to numbers, - Date variables are transformed to date format, - Character variables are trimmed for leading and trailing spaces, - The variables saksnr and, if possible, fagnr are generated, - Test data, i.e. saker with ansvarlig_seksjon in c("14", "99") or are deleted.

Value

data frame with standardized PJS-data.

Author(s)

Petter Hopp Petter.Hopp@vetinst.no

Johan Åkerstedt Johan.Akerstedt@vetinst.no

Examples

```
## Not run:  
# Standardizing sak_m_res  
sak_m_res <- standardize_PJSdata(PJSdata = sak_m_res)  
  
## End(Not run)
```

Index

* Log in functions

login, [27](#)

* datasets

PJS_levels, [30](#)

add_kommune_fylke, [2](#)

add_lokalitet, [5](#)

add_MT_omrader, [7](#)

add_PJS_code_description, [9](#)

add_poststed, [12](#)

add_producent, [14](#)

build_query_hensikt, [17](#)

build_query_one_disease, [18](#)

build_sql_select_code
(build_sql_select_year), [19](#)

build_sql_select_year, [19](#)

choose_PJS_levels, [20](#)

copy_kommune_fylke (add_kommune_fylke),
[2](#)

copy_MT_omrader (add_MT_omrader), [7](#)

copy_PJS_codes_2_text
(add_PJS_code_description), [9](#)

copy_Pkode_2_text, [22](#)

copy_poststed (add_poststed), [12](#)

copy_prodnr_2_current_prodnr
(add_producent), [14](#)

copy_Prodtilskudd, [23](#)

exclude_from_PJSdata, [25](#)

get_PAT, [26](#)

login, [27](#), [33](#)

login_by_credentials, [33](#)

login_by_credentials (login), [27](#)

login_by_credentials_EOS (login), [27](#)

login_by_credentials_PJS (login), [27](#)

login_by_input (login), [27](#)

login_by_input_EOS (login), [27](#)

login_by_input_PJS (login), [27](#)

login_EOS (login), [27](#)

login_PJS (login), [27](#)

NVIdb, [29](#)

PJS_levels, [30](#)

read_kommune_fylke (add_kommune_fylke),
[2](#)

read_leveransereg, [31](#)

read_MT_omrader (add_MT_omrader), [7](#)

read_PJS_codes_2_text
(add_PJS_code_description), [9](#)

read_Pkode_2_text (copy_Pkode_2_text),
[22](#)

read_poststed (add_poststed), [12](#)

read_prodnr_2_coordinates
(add_producent), [14](#)

read_prodnr_2_current_prodnr
(add_producent), [14](#)

read_Prodtilskudd (copy_Prodtilskudd),
[23](#)

read_sonetilhorighet (add_lokalitet), [5](#)

remove_credentials, [32](#)

remove_PAT (get_PAT), [26](#)

set_credentials, [29](#)

set_credentials (remove_credentials), [32](#)

set_credentials_EOS

(remove_credentials), [32](#)

set_credentials_PJS

(remove_credentials), [32](#)

set_dir_NVI, [33](#)

set_PAT (get_PAT), [26](#)

standardize_columns, [34](#)

standardize_PJSdata, [36](#)