

Project

Synchronous FIFO

Read the important notes and the requirements carefully at the end of the document.

Parameters

- FIFO_WIDTH: DATA in/out and memory word width (default: 16)
- FIFO_DEPTH: Memory depth (default: 8)

Ports

Port	Direction	Function
data_in	Input	Write Data: The input data bus used when writing the FIFO.
wr_en		Write Enable: If the FIFO is not full, asserting this signal causes data (on data_in) to be written into the FIFO
rd_en		Read Enable: If the FIFO is not empty, asserting this signal causes data (on data_out) to be read from the FIFO
clk		Clock signal
rst_n		Active low asynchronous reset
data_out	Output	Read Data: The sequential output data bus used when reading from the FIFO.
full		Full Flag: When asserted, this combinational output signal indicates that the FIFO is full. Write requests are ignored when the FIFO is full, initiating a write when the FIFO is full is not destructive to the contents of the FIFO.
almostfull		Almost Full: When asserted, this combinational output signal indicates that only one more write can be performed before the FIFO is full.
empty		Empty Flag: When asserted, this combinational output signal indicates that the FIFO is empty. Read requests are ignored when the FIFO is empty, initiating a read while empty is not destructive to the FIFO.
almostempty		Almost Empty: When asserted, this output combinational signal indicates that only one more read can be performed before the FIFO goes to empty.
overflow		Overflow: This sequential output signal indicates that a write request (wr_en) was rejected because the FIFO is full. Overflowing the FIFO is not destructive to the contents of the FIFO.
underflow		Underflow: This sequential output signal Indicates that the read request (rd_en) was rejected because the FIFO is empty. Under flowing the FIFO is not destructive to the FIFO.
wr_ack		Write Acknowledge: This sequential output signal indicates that a write request (wr_en) has succeeded.

- top

- DUT

- tb

- Monitor

- Shaved_pkg

sb
txa
cov

Overview of the testbench flow:

The top module will generate the clock, pass it to the interface, and the interface will be passed to the DUT, tb, and monitor modules. The tb will reset the DUT and then randomize the inputs. At the end of the test, the tb will assert a signal of size 1-bit named test_finished. The signal will be defined as well as the error_count and correct_count in a shared package that you will create named shared_pkg.

The monitor module will do the following:

1. Create objects of 3 different classes (FIFO_transaction, FIFO_scoreboard, FIFO_coverage). These classes will be discussed later in the document.
2. It will have an initial block and inside it a forever loop that waits for negedge clock at the start of the loop and then sample the data of the interface and assign it to the data variables of the object of class FIFO_transaction. Then after that there will be fork join, where 2 processes will run, the first one is calling a method named sample_data of the object of class FIFO_coverage and the second process is calling a method named check_data of the object of class FIFO_scoreboard.
3. So, in summary the monitor will sample the interface ports, and then pass these values through the FIFO_transaction object to be sampled for functional coverage and to be checked if the output ports are correct or not.
4. After the fork join ends, you will check for the signal test_finished if it is high or not. If it high, then stop the simulation and display a message with summary of correct and error counts.

Steps:

1. Adjust the design to take an interface and change the file extension to sv.
2. Create a package in a new file that will have a class named FIFO_transaction
 - a. Inside of this class add the FIFO inputs and outputs as class variables of the class as well as adding 2 integers (RD_EN_ON_DIST & WR_EN_ON_DIST)
 - b. Add a constructor that takes 2 inputs and override the values of RD_EN_ON_DIST and WR_EN_ON_DIST, let the default of RD_EN_ON_DIST be 30 and WR_EN_ON_DIST be 70
 - c. Add the following 3 constraint blocks
 1. Assert reset less often
 2. Constraint the write enable to be high with distribution of the value WR_EN_ON_DIST and to be low with 100-WR_EN_ON_DIST
 3. Constraint the read enable the same as write enable but using RD_EN_ON_DIST
3. Create a package in a new file that will have a class for functional coverage collection named FIFO_coverage
 - a. Import the previous package (Add the import statement after the package declaration)
 - b. The class will have an object of the class FIFO_transaction named F_cvg_txn.
 - c. Create a covergroup. The coverage needed is cross coverage between 3 signals which are write enable, read enable and each output control signals (outputs except data_out) to make sure that all combinations of write and read enable took place in all state of the FIFO so it is expected to have 7 total cross coverage inside of the covergroup.
 - d. Create the covergroup inside the constructor.
 - e. Create a void function inside it named sample_data that takes one input named F_txn. This input is an object of class FIFO_transaction. This function will do the following

- 
1. Assign `F_txn` to `F_cvg_txn`
 2. Trigger the sampling of the covergroup using the `.sample` method
4. Create a package in a new file named `FIFO_scoreboard`
- a. Import the `FIFO_transaction` package.
 - b. Add variables for the `data_out_ref`, `full_ref`, etc. to be used in the `reference_model` method
 - c. Create a method named `check_data` that takes one input which of type `FIFO_transaction`
 1. Inside this method, call another method named `reference_model` that you will create and pass to it the same object that you have received
 2. `Reference_model` method will check the input values from the input object and assign values to the class properties `data_out_ref`, `full_ref`, etc.
 3. After the `reference_model` the method `returns`, you will `compare the reference outputs` calculated with the outputs of the object received. Increment the `error_count` or `correct_count`. Also, display a message if error occurs.
5. Open the design file and `add assertions` to the FIFO `inside the design file`.
- a. Add `assertions` to all the FIFO output flags (`outputs except data_out`) as well as the `internal counters of the FIFO`.
 - b. **Extra part to be done:** Guard the assertions using conditional compilation with the ``ifdef` directive with macro named `"SIM"`, and then include the macro in the `vlog` command `+define+SIM` option in the `vlog` command of your `do` file. Refer to [this](#) link to learn more about conditional compilation.

Notes

1. Since assertions have been added to monitor the FIFO flags inside the design itself, the `check_result` method in your testbench will only need to `verify` the correctness of the `data_out`.
2. If both `read` and `write enables` are high simultaneously:
 - a. When the FIFO is `empty`, `only writing` will take place.
 - b. When the FIFO is `full`, `only reading` will take place.
3. On every `reset assertion`, all `FIFO counters and pointers are reset`. This means the FIFO is considered `empty` each time a reset occurs.
4. Use the event datatype to ensure the monitor samples the data before the testbench drives new values. Specifically:
 - a. Trigger the `event` after you finish driving inputs and wait for the negedge `clk`.
 - b. The `monitor` should wait for `this event` to be triggered and `then sample the interface with both the inputs and the corresponding outputs`.
5. Since class objects are created at simulation run time 0 in this testbench, they won't appear on the waveform unless you start the simulation. Here's a simple trick to add them on the wave from the beginning of the simulation:
 - a. In the transcript, type `"run 0"`. This ensures objects are initialized and visible in the `"Objects"` window.
 - b. Drag them to the waveform window.
 - c. Then type `run -all` to resume full simulation.
 - d. You can automate this in your `.do` file to streamline the process.

6. Here are some design requirements that the assertions need to check:
- ✓ a. Reset Behavior
 - i. After reset is asserted (`rst_n = 0`), internal pointers and counters must reset to 0
 - ✓ b. Write Acknowledge (`wr_ack`)
 - i. When a write enable signal (`wr_en`) is active and the FIFO is not full, `wr_ack` should be asserted to confirm the write operation.
 - ✓ c. Overflow Detection
 - i. If a write is attempted when the FIFO is full, overflow should be asserted.
 - ✓ d. Underflow Detection
 - i. If a read is attempted when the FIFO is empty, underflow should be asserted.
 - ✓ e. Empty Flag Assertion
 - i. When the internal count is zero, the empty flag should be asserted.
 - ✓ f. Full Flag Assertion
 - i. When the internal count equals the FIFO depth, the full flag should be asserted.
 - ✓ g. Almost Full Condition
 - i. When the count reaches FIFO depth - 1, `almostfull` should be asserted.
 - ✓ h. Almost Empty Condition
 - i. When the count equals 1, the `almostempty` signal should be asserted.
 - ~ i. Pointer Wraparound
 - i. After writing or reading `FIFO_DEPTH` entries (0 to 7), the write or read pointer should eventually wrap around back to 0.
 - ~ j. Pointer threshold
 - i. Internal pointers cannot exceed the `FIFO_DEPTH` entries in any given time. Same applies for the counter.
7. Add assertions in the top file ensuring that asynchronous reset is working as expected.

Requirements

1. Verification Plan, where you will list your verification plan, an example of the document can be found in the link [here](#). In the functionality check column, you can specify whether the requirements are being checked only by the golden/reference model, assertion or both.
2. You are welcome to create your own constraints, coverpoints, and assertions. If you would like feedback or ideas, feel free to share your additions with me or your assigned teaching assistant.
3. Use Do file to run the top and make sure to generate the coverage report and check that the code coverage, functional coverage, and sequential domain (assertions) coverage are 100%
4. QuestaSim snippets, report any bugs detected and modify the RTL. Report the before and after to show the changes made to the RTL.

Submission file: .rar file containing the following:

- PDF file having the requirements with the bugs detected for the FIFO
- Do file to run the top
- SystemVerilog files & also add snippets to the code in the PDF, it will be easier for the grading process