

# Release Engineering Quick-Start

November 4, 2025

## Contents

<b>1</b>	<b>Why Release Engineering Matters</b>	<b>3</b>
<b>2</b>	<b>Versioning Strategy (SemVer + Conventional Commits)</b>	<b>3</b>
2.1	Semantic Versioning . . . . .	3
2.2	Conventional Commits (supports automation) . . . . .	3
<b>3</b>	<b>Source Tagging &amp; GitHub Releases</b>	<b>4</b>
3.1	Tag and Release (UI + CLI) . . . . .	4
3.2	Auto-Generate Release Notes . . . . .	4
<b>4</b>	<b>Packaging Paths</b>	<b>4</b>
4.1	Node Package (GitHub Packages or npmjs) . . . . .	4
4.2	Python Package (PyPI or GitHub Packages) . . . . .	5
4.3	Java (Maven) to GitHub Packages . . . . .	6
<b>5</b>	<b>Containers to GHCR (GitHub Container Registry)</b>	<b>7</b>
5.1	Dockerfile (example) . . . . .	7
5.2	Build & push (CLI) . . . . .	7
5.3	Workflow: docker/build-push-action . . . . .	8
<b>6</b>	<b>Containers to AWS (ECR, ECS Fargate, EKS)</b>	<b>8</b>
6.1	Amazon ECR: Build, Tag, Push . . . . .	8
6.2	GitHub Actions → ECR (OIDC) . . . . .	9
6.3	ECS Fargate: Deploy . . . . .	11
6.4	EKS: Deploy . . . . .	12
6.5	Tips & Gotchas . . . . .	13
<b>7</b>	<b>Security: Checksums, Signatures, SBOM, Provenance</b>	<b>13</b>
7.1	Checksums . . . . .	13
7.2	Signing (cosign) and SBOM (syft) . . . . .	13
7.3	Supply-chain provenance (SLSA generator gist) . . . . .	13
<b>8</b>	<b>Release Trains, Channels, and Promotion</b>	<b>14</b>

<b>9 Branching &amp; Protection</b>	<b>14</b>
<b>10 Automated Changelog</b>	<b>14</b>
10.1 Keep a Changelog (example sections) . . . . .	14
10.2 Action example (conventional commits) . . . . .	14
<b>11 Monorepos (optional)</b>	<b>14</b>
<b>12 Troubleshooting Cheatsheet</b>	<b>15</b>

# 1 Why Release Engineering Matters

Release Engineering (*RelEng*) turns source code into dependable, reproducible artifacts and makes delivery routine. Core outcomes:

- A **versioning model** (usually SemVer) that maps change scope to version numbers.
- **Tagged source**, signed builds, and **immutable artifacts**.
- **Automations** that build, test, package, sign, scan, and publish on events (merge, tag, or manual).
- **Auditability**: release notes, provenance, SBOMs, checksums, signatures.

## 2 Versioning Strategy (SemVer + Conventional Commits)

### 2.1 Semantic Versioning

- MAJOR: breaking changes (v2.0.0)
- MINOR: new backward-compatible features (v1.1.0)
- PATCH: bug fixes (v1.0.1)

### 2.2 Conventional Commits (supports automation)

Use commit types to drive changelogs and version bumps (e.g., `feat:`, `fix:`, `perf:`, `docs:`, `refactor:`). Mark breaking changes with `!` or `BREAKING CHANGE:`.

```
1 # Examples
2 git commit -m "feat(auth): add OIDC login flow"
3 git commit -m "fix(router): handle trailing slash redirects"
4 git commit -m "feat(api)!: drop deprecated /v1 endpoints"
```

## 3 Source Tagging & GitHub Releases

### 3.1 Tag and Release (UI + CLI)

#### GitHub UI

1. Repo → **Releases** → **Draft a new release**.
2. Create tag (e.g., v1.0.0) targeting **main** (or your release branch).
3. Generate notes; attach binaries if applicable; **Publish**.

#### GitHub CLI

```
1 gh auth login
2 gh release create v1.1.0 --generate-notes
3 gh release list
```

### 3.2 Auto-Generate Release Notes

GitHub can generate notes from merged PRs and commits. Keep PR titles crisp and use labels to improve sections.

## 4 Packaging Paths

Choose the artifact type(s) that fit your distribution model.

### 4.1 Node Package (GitHub Packages or npmjs)

#### package.json essentials

```
1 {
2   "name": "@<owner>/<repo>",
3   "version": "1.1.1",
4   "main": "dist/index.js",
5   "files": ["dist"],
6   "repository": {"type": "git", "url": "https://github.com/<owner>/<repo>.git"},
7   "publishConfig": {"registry": "https://npm.pkg.github.com"}
8 }
```

#### .npmrc for owner scope

```
1 @<owner>:registry=https://npm.pkg.github.com
```

#### Local publish (PAT with packages:write)

```
1 npm ci
2 npm publish --access public    # or private if using GitHub Packages
```

## GitHub Actions: publish on Release

```
1 name: Publish package
2 on:
3   release:
4     types: [published]
5 permissions:
6   contents: read
7   packages: write
8 jobs:
9   publish:
10    runs-on: ubuntu-latest
11    steps:
12      - uses: actions/checkout@v4
13      - uses: actions/setup-node@v4
14        with:
15          node-version: 20
16          registry-url: https://npm.pkg.github.com
17          scope: "@<owner>"
18      - run: npm ci
19      - run: npm publish
20    env:
21      NODE_AUTH_TOKEN: ${ secrets.GITHUB_TOKEN }
```

## 4.2 Python Package (PyPI or GitHub Packages)

### Project metadata (pyproject.toml)

```
1 [build-system]
2 requires = ["setuptools", "wheel"]
3 build-backend = "setuptools.build_meta"
4
5 [project]
6 name = "your-package"
7 version = "1.0.0"
8 description = "Awesome thing"
9 requires-python = ">=3.9"
```

### Publish with Twine

```
1 python -m build
2 python -m twine upload dist/*      # uses ~/.pypirc
```

## GitHub Actions: build & publish on tag

```
1 name: PyPI publish
2 on:
3   push:
4     tags: ["v*.*.*"]
5 jobs:
6   build-publish:
7     runs-on: ubuntu-latest
8     steps:
9       - uses: actions/checkout@v4
10      - uses: actions/setup-python@v5
11        with: { python-version: "3.11" }
12      - run: pip install build twine
13      - run: python -m build
14      - run: python -m twine upload dist/*
15      env:
16        TWINE_USERNAME: __token__
17        TWINE_PASSWORD: ${ secrets.PYPI_TOKEN }
```

## 4.3 Java (Maven) to GitHub Packages

### pom.xml distributionManagement

```
1 <distributionManagement>
2   <repository>
3     <id>github</id>
4     <name>GitHub Packages</name>
5     <url>https://maven.pkg.github.com/&lt;owner>/&lt;repo></url>
6   </repository>
7 </distributionManagement>
```

### Settings (GITHUB\_TOKEN)

```
1 <servers>
2   <server>
3     <id>github</id>
4     <username>${env.GITHUB_ACTOR}</username>
5     <password>${env.GITHUB_TOKEN}</password>
6   </server>
7 </servers>
```

## Workflow

```
1 name: Maven publish
2 on:
3   release:
4     types: [published]
5 permissions:
6   contents: read
7   packages: write
8 jobs:
9   publish:
10    runs-on: ubuntu-latest
11    steps:
12      - uses: actions/checkout@v4
13      - name: Set up Java
14        uses: actions/setup-java@v4
15        with:
16          distribution: temurin
17          java-version: "21"
18          cache: maven
19          server-id: github
20          server-username: GITHUB_ACTOR
21          server-password: GITHUB_TOKEN
22      - run: mvn -B -DskipTests deploy
```

## 5 Containers to GHCR (GitHub Container Registry)

### 5.1 Dockerfile (example)

```
1 FROM node:20-alpine
2 LABEL org.opencontainers.image.source="https://github.com/<owner>/<repo>"
3 WORKDIR /app
4 COPY . /app
5 RUN npm ci --omit=dev
6 EXPOSE 3000
7 CMD ["npm", "start"]
```

### 5.2 Build & push (CLI)

```
1 export IMAGE=ghcr.io/<owner>/<repo>:v1.0.0
2 echo $GITHUB_TOKEN | docker login ghcr.io -u <owner> --password-stdin
3 docker build -t $IMAGE .
4 docker push $IMAGE
```

## 5.3 Workflow: docker/build-push-action

```
1 name: Build & Push Image
2 on:
3   push:
4     tags: ["v*.*.*"]
5 permissions:
6   contents: read
7   packages: write
8 jobs:
9   image:
10    runs-on: ubuntu-latest
11    steps:
12      - uses: actions/checkout@v4
13      - uses: docker/login-action@v3
14        with:
15          registry: ghcr.io
16          username: ${ github.actor }
17          password: ${ secrets.GITHUB_TOKEN }
18      - uses: docker/build-push-action@v6
19        with:
20          context: .
21          push: true
22          tags: ghcr.io/${ github.repository }:${ github.ref_name }
```

## 6 Containers to AWS (ECR, ECS Fargate, EKS)

### 6.1 Amazon ECR: Build, Tag, Push

Create (or use) a repository

```
1 aws ecr create-repository --repository-name <name> --region <region> \
2   --image-scanning-configuration scanOnPush=true
```

Authenticate (OIDC or static credentials)

```
1 aws ecr get-login-password --region <region> \
2 | docker login --username AWS --password-stdin <account>.dkr.ecr.<region>.amazonaws.com
```

Build, tag, push

```
1 IMAGE=<account>.dkr.ecr.<region>.amazonaws.com/<name>:v1.0.0
2 docker build -t "$IMAGE" .
3 docker push "$IMAGE"
```



## 6.2 GitHub Actions → ECR (OIDC)

**Set up AWS IAM OIDC trust (once)** Create an IAM role trusted by `token.actions.githubusercontent.com` (replace placeholders).

```
1 {
2   "Version": "2012-10-17",
3   "Statement": [{
4     "Effect": "Allow",
5     "Principal": {"Federated":
6       ↪ "arn:aws:iam:<account>:oidc-provider/token.actions.githubusercontent.com"},
7     "Action": "sts:AssumeRoleWithWebIdentity",
8     "Condition": {
9       "StringEquals": {
10        "token.actions.githubusercontent.com:aud": "sts.amazonaws.com"
11      },
12      "StringLike": {
13        "token.actions.githubusercontent.com:sub":
14        ↪ "repo:<owner>/<repo>:ref:refs/heads/main"
15      }
16    }
17  }]
18 }
```

Attach a policy granting ECR push (minimal example).

```
1 {
2   "Version": "2012-10-17",
3   "Statement": [{
4     "Effect": "Allow",
5     "Action": [
6       "ecr:GetAuthorizationToken",
7       "ecr:BatchCheckLayerAvailability",
8       "ecr:CompleteLayerUpload",
9       "ecr:DescribeRepositories",
10      "ecr:InitiateLayerUpload",
11      "ecr:PutImage",
12      "ecr:UploadLayerPart"
13    ],
14     "Resource": "*"
15   }]
16 }
```

## Workflow: build-push-to-ECR (with cache)

```
1 name: Build and Push (ECR)
2 on:
3   push:
4     tags: ["v*.*.*"]
5 permissions:
6   id-token: write
7   contents: read
8 jobs:
9   build-push:
10    runs-on: ubuntu-latest
11    steps:
12      - uses: actions/checkout@v4
13
14      - name: Configure AWS credentials (OIDC)
15        uses: aws-actions/configure-aws-credentials@v4
16        with:
17          role-to-assume: arn:aws:iam::<account>:role/<role-name>
18          aws-region: <region>
19
20      - name: Login to Amazon ECR
21        uses: aws-actions/amazon-ecr-login@v2
22
23      - name: Build and push
24        uses: docker/build-push-action@v6
25        with:
26          context: .
27          push: true
28          tags: |
29            <account>.dkr.ecr.<region>.amazonaws.com/<name>:${{ github.ref_name }}
30            <account>.dkr.ecr.<region>.amazonaws.com/<name>:${{ github.sha }}
31          cache-from: type=gha
32          cache-to: type=gha,mode=max
```

## 6.3 ECS Fargate: Deploy

### Task definition (snippet)

```
1 {
2   "family": "my-service",
3   "networkMode": "awsvpc",
4   "cpu": "512",
5   "memory": "1024",
6   "requiresCompatibilities": ["FARGATE"],
7   "executionRoleArn": "arn:aws:iam::<account>:role/ecsTaskExecutionRole",
8   "taskRoleArn": "arn:aws:iam::<account>:role/appTaskRole",
9   "containerDefinitions": [{
10    "name": "web",
11    "image": "<account>.dkr.ecr.<region>.amazonaws.com/<name>:v1.0.0",
12    "portMappings": [{"containerPort": 3000, "protocol": "tcp"}],
13    "essential": true
14  }]
15 }
```

## Workflow: update ECS service (rolling)

```
1 name: Deploy to ECS
2 on:
3   workflow_dispatch: {}
4 permissions:
5   id-token: write
6   contents: read
7 jobs:
8   deploy:
9     runs-on: ubuntu-latest
10    steps:
11      - uses: actions/checkout@v4
12
13      - uses: aws-actions/configure-aws-credentials@v4
14        with:
15          role-to-assume: arn:aws:iam::<account>:role/<role-name>
16          aws-region: <region>
17
18      - uses: aws-actions/amazon-ecr-login@v2
19
20      - name: Build and push image
21        uses: docker/build-push-action@v6
22        with:
23          context: .
24          push: true
25          tags: <account>.dkr.ecr.<region>.amazonaws.com/<name>:${{ github.sha }}
26
27      - name: Render task definition
28        uses: aws-actions/amazon-ecs-render-task-definition@v1
29        with:
30          task-definition: ecs-task-def.json
31          container-name: web
32          image: <account>.dkr.ecr.<region>.amazonaws.com/<name>:${{ github.sha }}
33
34      - name: Deploy service
35        uses: aws-actions/amazon-ecs-deploy-task-definition@v1
36        with:
37          task-definition: ${{ steps.render.outputs.task-definition }}
38          service: my-service
39          cluster: my-cluster
40          wait-for-service-stability: true
```

**Blue/Green (optional)** Use ECS + CodeDeploy for canary/blue-green; wire the service to a CodeDeploy application and deployment group, then trigger a deployment with a new task definition revision.

## 6.4 EKS: Deploy

**Configure kubeconfig via OIDC role** Grant the role `eks:DescribeCluster`. Map the role to a Kubernetes RBAC subject with cluster-admin or a bound role.

```
1 aws eks update-kubeconfig --name <cluster> --region <region> --role-arn
  ↪ arn:aws:iam::<account>:role/<role-name>
```

### Minimal Deployment (snippet)

```
1 apiVersion: apps/v1
2 kind: Deployment
3 metadata:
4   name: web
5 spec:
6   replicas: 2
7   selector: { matchLabels: { app: web } }
8   template:
9     metadata: { labels: { app: web } }
10    spec:
11      containers:
12      - name: web
13        image: <account>.dkr.ecr.<region>.amazonaws.com/<name>:v1.0.0
14        ports: [{containerPort: 3000}]
```

### Workflow: kubectl rollout

```
1 name: Deploy to EKS
2 on: { workflow_dispatch: {} }
3 permissions:
4   id-token: write
5   contents: read
6 jobs:
7   deploy:
8     runs-on: ubuntu-latest
9     steps:
10      - uses: actions/checkout@v4
11      - uses: aws-actions/configure-aws-credentials@v4
12        with:
13          role-to-assume: arn:aws:iam::<account>:role/<role-name>
14          aws-region: <region>
15      - name: Get kubeconfig
16        run: aws eks update-kubeconfig --name <cluster> --region <region>
17      - name: Update image
18        run: |
19          kubectl set image deploy/web
20          ↪ web=<account>.dkr.ecr.<region>.amazonaws.com/<name>:${{ github.sha }}
21          kubectl rollout status deploy/web
```

## 6.5 Tips & Gotchas

- Enable **scanOnPush** in ECR; fail builds on critical vulns (e.g., pre-deploy gate with Trivy/Grype).
- Use `cache-to: type=gha,mode=max` to speed Docker builds.
- Prefer **multi-arch** images when you have arm64/amd64 hosts (`platforms: linux/amd64,linux/arm64`).
- Grant the OIDC role least-privilege: ECR push, ECS deploy, or EKS describe; use separate roles per workflow if needed.

## 7 Security: Checksums, Signatures, SBOM, Provenance

### 7.1 Checksums

Generate SHA256 for assets and publish alongside releases.

```
1 shasum -a 256 artifact.tar.gz > artifact.tar.gz.sha256
```

### 7.2 Signing (cosign) and SBOM (syft)

```
1 # Image signature
2 cosign sign ghcr.io/<owner>/<repo>:v1.0.0
3
4 # SBOM
5 syft ghcr.io/<owner>/<repo>:v1.0.0 -o spdx-json > sbom.spdx.json
```

### 7.3 Supply-chain provenance (SLSA generator gist)

Record build provenance and attach to the release (or publish as attestation).

## 8 Release Trains, Channels, and Promotion

- **Channels:** `-alpha`, `-beta`, `-rc`, `-stable`.
- **Promotion:** build once, promote by retagging (no rebuild).
- **Canary** → **Staged** → **Global** rollouts with metrics and fast rollback.

## 9 Branching & Protection

- Protect **main**: require PR reviews, status checks, linear history.
- Optional maintenance branches (`release/1.x`) for patch backports.
- Tag from a green build of **main** (or from a release branch commit).

## 10 Automated Changelog

### 10.1 Keep a Changelog (example sections)

- Added, Changed, Deprecated, Removed, Fixed, Security.

### 10.2 Action example (conventional commits)

```
1 name: Changelog
2 on:
3   push:
4     tags: ["v*.*.*"]
5 jobs:
6   changelog:
7     runs-on: ubuntu-latest
8     steps:
9       - uses: actions/checkout@v4
10      - name: Generate changelog
11        uses: metcalfc/changelog-generator@v4.3.1
12      with:
13        mytoken: ${ secrets.GITHUB_TOKEN }
```

## 11 Monorepos (optional)

- Workspaces (npm/pnpm/yarn) or tools like Lerna/Changesets.
- Independent versioning per package vs. fixed version for all.
- Filtered workflows: build/test only what changed.

## 12 Troubleshooting Cheatsheet

Symptom	Likely Fix
403 on package publish	Missing scopes: add <code>packages:write</code> ; ensure registry/scope in <code>.npmrc</code> .
Image push denied	Workflow permissions: enable “Read and write” for GITHUB_TOKEN; login to GHCR.
Wrong version	Ensure tag matches version file; automate version bump via CI.
SBOM empty	Build stage excluded deps; generate SBOM from final artifact/image.