

GitOps Stack Blueprint

Docker, Kubernetes, Ansible, Debian, Terraform, NGINX Ingress, Argo CD,
OPA/Gatekeeper, Cloud Custodian, GitHub Actions & GitHub Advanced Security

October 23, 2025

Contents

1	Executive Summary	2
2	System Roles & Flow	2
3	Repository Layout (Suggested)	2
4	Minimal Working Snippets	3
4.1	Terraform: Cluster Provisioning (EKS placeholder)	3
4.2	Ansible: Node Bootstrap	3
4.3	Argo CD: ApplicationSet (GitOps Multi-Env)	3
4.4	NGINX Ingress for Sample App	4
4.5	Gatekeeper: Disallow Privileged Containers	4
4.6	Cloud Custodian: Require S3 Encryption	5
4.7	GitHub Actions: CI Build & GHAS	5
5	Quickstart (Happy Path)	6
6	Security & Governance Notes	6
7	Operations (Day 2)	7
8	Next Steps	7

1 Executive Summary

This document provides an opinionated, end-to-end blueprint for a modern GitOps platform. It compiles roles, flow, and minimal working snippets for the following stack:

- **Provisioning:** Terraform (cloud primitives, cluster), Debian (base OS on nodes where applicable), Ansible (node bootstrap and hardening).
- **Runtime:** Docker (image build), Kubernetes (orchestrator), NGINX Ingress (L7 entry).
- **Delivery:** Argo CD for continuous delivery and drift reconciliation from Git.
- **Policy & Governance:** OPA/Gatekeeper (admission control), Cloud Custodian (cloud governance & remediation).
- **CI & Security:** GitHub Actions for CI and GitHub Advanced Security (CodeQL, secrets, dependency review).

2 System Roles & Flow

- Step 1. Terraform** provisions cloud networking, registry access, and a managed Kubernetes control plane (or bare metal/VM where desired). Debian may be used for node OS images.
- Step 2. Ansible** bootstraps nodes (Docker/CRI, kube prerequisites) and applies baseline hardening.
- Step 3. Docker** builds application images; images are pushed to a registry (e.g., GHCR/ECR/GCR).
- Step 4. Kubernetes** runs workloads; **NGINX Ingress** exposes services.
- Step 5. Argo CD** continuously syncs cluster state from Git; detects and heals drift.
- Step 6. OPA/Gatekeeper** enforces admission-time policies (e.g., disallow privileged pods).
- Step 7. Cloud Custodian** enforces cloud-level governance and can auto-remediate violations.
- Step 8. GitHub Actions & GHAS** run tests, build/push images, and scan code/secrets/dependencies.

3 Repository Layout (Suggested)

```
1 infra/
2   terraform/           # VPC/cluster/IRSA/registries
3   policies/cloudcustodian/
4 platform/
5   ansible/             # roles: docker, k8s-prereqs, hardening
6   k8s/                 # base namespaces, rbac, ingress-nginx, argocd/
7   gatekeeper/          # constraints + templates
8 apps/
9   sample-web/
10    Dockerfile
11    k8s/                # deployment, service, ingress
```

```

12  appset/                # ArgoCD ApplicationSet
13  .github/
14  workflows/            # ci.yml, deploy.yml, security.yml

```

Listing 1: Top-level repository structure

4 Minimal Working Snippets

4.1 Terraform: Cluster Provisioning (EKS placeholder)

```

1  terraform { required_version = ">= 1.6.0" }
2
3  provider "aws" { region = var.region }
4
5  module "cluster" {
6      source      = "terraform-aws-modules/eks/aws"
7      cluster_name = var.name
8      vpc_id      = var.vpc_id
9      subnet_ids  = var.subnet_ids
10 }
11 # Optionally: Helm releases for ingress-nginx and argocd via Terraform.

```

Listing 2: infra/terraform/main.tf

4.2 Ansible: Node Bootstrap

```

1  - hosts: workers
2    become: true
3    roles:
4      - docker
5      - k8s_prereqs
6      - hardening

```

Listing 3: platform/ansible/playbooks/bootstrap.yaml

4.3 Argo CD: ApplicationSet (GitOps Multi-Env)

```

1  apiVersion: argoproj.io/v1alpha1
2  kind: ApplicationSet
3  metadata: { name: apps }
4  spec:
5      generators:
6          - list:
7              elements:
8                  - { name: sample-web, namespace: web, path: apps/sample-web/k8s,
9                      env: dev }
9      template:
10         metadata: { name: '{{name}}-{{env}}' }

```

```

11 spec:
12   project: default
13   source:
14     repoURL: https://github.com/your/org.git
15     targetRevision: main
16     path: '{{path}}'
17   destination:
18     server: https://kubernetes.default.svc
19     namespace: '{{namespace}}'
20   syncPolicy: { automated: { prune: true, selfHeal: true } }

```

Listing 4: apps/appset/apps.yaml

4.4 NGINX Ingress for Sample App

```

1 apiVersion: networking.k8s.io/v1
2 kind: Ingress
3 metadata:
4   name: sample-web
5   annotations:
6     kubernetes.io/ingress.class: nginx
7 spec:
8   rules:
9     - host: sample.local
10     http:
11       paths:
12         - path: /
13           pathType: Prefix
14           backend:
15             service:
16               name: sample-web
17               port:
18                 number: 80

```

Listing 5: apps/sample-web/k8s/ingress.yaml

4.5 Gatekeeper: Disallow Privileged Containers

```

1 apiVersion: templates.gatekeeper.sh/v1
2 kind: ConstraintTemplate
3 metadata: { name: k8spspprivilegedcontainer }
4 spec:
5   crd:
6     spec:
7       names: { kind: K8sPSPPrivilegedContainer }
8   targets:
9     - target: admission.k8s.gatekeeper.sh
10     rego: |

```

```

11     package k8spsspprivileged
12     violation[{"msg": msg}] {
13         input.review.object.spec.containers[_].securityContext.privileged
14             == true
15         msg := "Privileged containers are not allowed"
16     }
17 ---
18 apiVersion: constraints.gatekeeper.sh/v1beta1
19 kind: K8sPSPPrivilegedContainer
20 metadata: { name: disallow-privileged }
21 spec: {}

```

Listing 6: platform/gatekeeper/templates/k8spssp-privileged.yaml

4.6 Cloud Custodian: Require S3 Encryption

```

1 policies:
2   - name: s3-require-encryption
3     resource: s3
4     filters:
5       - type: bucket-encryption
6         state: false
7     actions:
8       - type: set-bucket-encryption
9         crypto: aws:kms

```

Listing 7: infra/policies/cloudcustodian/enforce-bucket-encryption.yml

4.7 GitHub Actions: CI Build & GHAS

```

1 name: ci
2 on: [push]
3
4 jobs:
5   build-test-scan:
6     runs-on: ubuntu-latest
7     steps:
8       - uses: actions/checkout@v4
9
10      - uses: actions/setup-node@v4
11      - run: npm ci && npm test
12
13      - name: Build image
14        run: docker build -t ghcr.io/your/app:${{ github.sha }} apps/sample
15          -web
16
17      - name: Push image
18        run: |

```

```

18     echo "${{ secrets.CR_PAT }}" | docker login ghcr.io \
19         -u "${{ github.actor }}" --password-stdin
20     docker push ghcr.io/your/app:${{ github.sha }}
21
22     - name: CodeQL
23       uses: github/codeql-action/analyze@v3
24
25     - name: Secret scanning (GHAS native)
26       run: echo "Enable at repo settings"
27
28     - name: Update K8s manifest image
29       run: |
30         sed -i "s#image: .*#image: ghcr.io/your/app:${GITHUB_SHA}#" \
31             apps/sample-web/k8s/deployment.yaml
32         git config user.name bot
33         git config user.email bot@users.noreply.github.com
34         git commit -am "bump image"
35         git push

```

Listing 8: .github/workflows/ci.yml

5 Quickstart (Happy Path)

- Q1. Bootstrap infra with Terraform.** Create VPC/subnets, registry, and cluster. Optionally manage Helm releases for ingress-nginx and Argo CD.
- Q2. Harden nodes with Ansible.** Install CRI/Docker, kube prerequisites, and security baselines.
- Q3. Install Argo CD.** Point to the Git repo; commit the base platform manifests (namespaces, RBAC, ingress, Gatekeeper).
- Q4. Apply policies.** Gatekeeper constraints and Cloud Custodian policies for guardrails and remediation.
- Q5. Wire CI.** GitHub Actions builds/tests, pushes images, scans with GHAS, and bumps manifest tags so Argo CD deploys.

6 Security & Governance Notes

- Enforce least-privilege via IRSA (AWS) or workload identity (GCP) and namespace-scoped RBAC.
- Use Gatekeeper libraries for common controls (privileged, hostPath, runAsNonRoot, image provenance).
- Enable GHAS features: CodeQL, secret scanning, Dependabot security updates.
- Apply Cloud Custodian for encryption at rest, public exposure checks, and lifecycle policies.

7 Operations (Day 2)

- **Drift & Sync:** Use Argo CD automated sync and health checks; protect prod with PR + manual sync if desired.
- **Environments:** Promote via Git branches or ApplicationSet generators (folder-per-env); avoid kubectl-by-hand.
- **Observability:** Add metrics/logs/traces; gate production with SLOs and rollout strategies (e.g., canary).

8 Next Steps

- Add Helm/Kustomize overlays per environment.
- Expand Gatekeeper constraints and Custodian policies to your regulatory profile.
- Introduce image signing (Sigstore/cosign) and policy checks (Conftest/OPA) in CI.

This document is a practical compilation intended as a quick-start blueprint. Adapt module versions, cloud providers, and security baselines to your environment.