

Mining Data Streams

Professor Wei-Min Shen
University of Southern California

Thanks for source slides and material to:
J. Leskovec, A. Rajaraman, J. Ullman: Mining of Massive Datasets
<http://www.mmds.org>

Note to other teachers and users of these slides: We would be delighted if you found this our material useful in giving your own lectures. Feel free to use these slides verbatim, or to modify them to fit your own needs. If you make use of a significant portion of these slides in your own lecture, please include this message, or a link to our web site: <http://www.mmds.org>

Mining Data Stream

- Motivation
- Sampling
 - Fixed-portion sampling
 - Fixed-size (reservoir) sampling
- Filtering
 - Bloom filter
- Counting
 - Estimating # of distinct values, moments
- Sliding window
 - Counting # of 1's in the window

Data streams & applications

- Query streams
 - How many unique users at Google last month?
- URL streams while crawling
 - Which URLs have been crawled before?
- Sensor data
 - What is the maximum temperature so far?

Stream data processing

- Stream of tuples arriving at a rapid rate
 - In contrast to traditional DBMS where all tuples are stored in secondary storage
- Infeasible to use all tuples to answer queries
 - Cannot store them all in main memory
 - Too much computation
 - Query response time critical

Query types


- Standing queries

- Executed **whenever a new data tuple arrives**
- keep only one value
 - e.g., report each new maximum value ever seen in the stream

- Ad-hoc queries

- Normal queries asked one time
- Need entire stream to have **an exact answer**
 - e.g., what is the number of unique visitors in the last two months?

Stream Processing Model



Example: Running averages

- Given a window of size N
 - Report the average of values in the window whenever a value arrives
 - N is so large that we can not store all tuples in the window
- What is the type of this query?
- How to do this?

Example: Running averages

- First N inputs, accumulate **sum** and **count**
 - $\text{Avg} = \text{sum}/\text{count}$
- A new element i
 - Change the average by **adding** $(i - j)/N$
 - j is the **oldest element** in the **window**
 - window size is fixed so we need to discard j

Roadmap

- Motivation
- Sampling
 - Fixed-portion & fixed-size (reservoir sampling)
- Filtering
 - Bloom filter
- Counting
 - Estimating # of distinct values, moments
- Sliding window
 - Counting # of 1's in the window

Sampling from a data stream

- **Scenario:** Search engine query stream
 - **Stream of tuples:** (user, query, time)
 - **Answer questions such as:** How often did a user run **the same query** in a single day
 - Have space to store **$1/10^{\text{th}}$** of query stream
- Method 1: sample a **fixed portion** of elements
 - e.g., $1/10$
- Method 2: maintain a **fixed-size** sample

SAMPLING FIXED-PORTION

Sampling a fixed proportion

- Search engine query stream
 - Stream of tuples: (user, query, time)
- Example query
 - What fraction of queries by a user are duplicates?
- Assumption
 - Have space to store $1/10$ of stream tuples

Naive solution

- For each tuple (store it or not?)
 - generate a random number in $[0..9]$
 - store it in the sample if the number is 0
 - Sample rate?
- Example stream tuples:
 - (john, data mining, 2015/12/01 9:45)
 - (mary, inf 553, 2015/12/01 10:08)
 - (john, data mining, 2015/12/01 11:30)
 - ...
- Problems?
 - Your sampling may contain duplicates

The true fraction of queries with duplicates

- A user issued **s** queries once & **d** queries twice
 - E.g., data mining, inf 553, **movie, movie, tom, tom**
($s=d=2$)
- Total number of queries & duplicates = $s + 2d$
- True fraction of queries with duplicates = $d/(s+d)$
- Sampling rate = $1/10$

Queries with duplicates in sample

- The sample contains:
 - $s/10$ “ s ” queries, e.g., data mining
 - $2d/10$ “ d ” tuples, e.g., movie, **tom**, **tom**
- If sample = data mining, movie, tom, tom, question:
 - What is **the expected number of d queries with duplicates** in the sample?
 - movie – d query **without** duplicates in the sample
 - tom, tom – d query **with** duplicates in the sample
 - E.g., both tom’s appear in the sample

Queries with duplicates in sample

- $s_1, s_2, \dots, s_{800}, d_1, d_1', d_2, d_2', \dots, d_{100}, d_{100}'$
 - $s = 800, d = 100$
 - Each d_j has probability of $1/10$ being selected
 - so prob. of two d_j 's being selected = $1/10 * 1/10$
 - There are d number of d_j 's
- ⇒ so the expected number of duplicated pairs in sample = $d/100$
- ⇒ or $d/100$ queries + $d/100$ their duplicates
- ⇒ That is $2d/100$

“d” Queries **without** duplicates in sample


- The sample contains:
 - $s/10$ “s” queries, e.g., data mining
 - $2d/10$ “**d**” tuples, e.g., movie, tom, tom
- Question:
 - What is the expected number of **d** queries **without** duplicates in the sample?
 - E.g., only one **movie** appears in the sample

“d” Queries **without** duplicates in sample

- $s_1, s_2, \dots, s_{800}, d_1, d_1', d_2, d_2', \dots, d_{100}, d_{100}'$
– $s = 800, d = 100$
- Expected # of singleton d queries in sample
 - d_j selected, d_j' not selected: $1/10 * 9/10$
 - d_j not selected, d_j' selected: $9/10 * 1/10$
 - $\Rightarrow 9d/100 + 9d/100 = 18d/100$

Fraction of queries in sample w/ duplicates

- $s_1, s_2, \dots, s_{800}, d_1, d_1', d_2, d_2', \dots, d_{100}, d_{100}'$
– $s = 800, d = 100$

- Fraction = $\frac{\frac{d}{100}}{\frac{s}{10} + \frac{d}{100} + \frac{18d}{100}} = \frac{d}{10s + 19d} \neq \frac{d}{s + d}$


- Note total # of **d queries** with and without duplicates = $\frac{d}{100} * 2 + \frac{18d}{100}$
= $20d/100$
= $2d/10$

What has been the problem?

- Mistake: sample by **position**
 - When search tuple arrives, we flip a 10-sided dice
 - Retain it if the dice shows up as 0
- Solution: **sample by user (by key)**
 - When search tuple (user, query, time) arrives
 - We extract its user (key) component
 - Hash user into 10 buckets: 0, 1, ..., 9
 - **Retain all tuples for the user in the bucket 0**

Sample by user

- Sample = all queries for users hashed into bucket 0
- All or none of queries of a user will be selected
- Thus, the fraction of unique queries in sample
 - will be the same as that in the stream as a whole

General Sampling Problem

- Stream of tuples with n components
 - Key = a **subset** of components
- Search stream: (user, query, time)
 - Sample size: a/b
- Sampling strategy:
 - Hash **key** (e.g., user) to b buckets
 - Accept tuple if **key value** $< a$

Example

- Tuples: (empID, dept, salary)
- Query: avg. range of salary within a dept.?
- Randomly selecting tuples
 - Might miss the min/max salary
- Key = dept.
- Sample: some departments and all tuples in these departments

SAMPLING FIXED-SIZED (RESERVOIR)

Roadmap

- Motivation
- Sampling
 - Fixed-portion sampling
 - Fixed-size (reservoir) sampling
- Filtering
 - Bloom filter
- Counting
 - Estimating # of distinct values, moments
- Sliding window
 - Counting # of 1's in the window

Problem with fixed portion sample

- Sample size may grow too big when data stream in
 - Even 10% could be too big, e.g., tuples in bucket 1/10 exceed the memory size
- Idea: throw away some queries
- Key: do this consistently
 - remove all or none of occurrences of a query

Controlling the sample size

- Put an **upper bound** on the sample size
 - Start out with 10%
- Solution:
 - Hash queries to a large # of buckets, say 100
 - Put them into sample if they hash to bucket 0 to 9
 - When sample grows too big, **throw away bucket 9**
 - So on

Maintaining a fixed-size sample

- Suppose we need to maintain a random sample, S , of size exactly s tuples (instead of %)
 - E.g., main memory size constraint
- **Why?** Don't know length of stream in advance
- Suppose at time n we have seen n items
 - Each item is in the sample S with equal prob. s/n
 - A challenge to achieve !

How to think about the problem: say $s = 2$

Stream: a x c y z k c d e g...

At $n = 5$, each of the first 5 tuples is included in the sample S with equal prob.

At $n = 7$, each of the first 7 tuples is included in the sample S with equal prob.

Impractical solution would be to store all the n tuples seen so far and out of them pick s at random

Solution: Fixed Size Sample

- **Algorithm (a.k.a. Reservoir Sampling)**

- Store all the first s elements of the stream to S
- Suppose we have seen $n-1$ elements, and now the n^{th} element arrives ($n > s$)
 - With probability s/n , keep the n^{th} element, else discard it
 - If we picked the n^{th} element, then it replaces one of the s elements in the sample S , picked uniformly at random

- **Claim:** This algorithm maintains a sample S with the desired property:

- After n elements, the sample contains each element seen so far with probability s/n

Proof: By Induction

- **We prove this by induction:**
 - Assume that after n elements, the sample contains each element seen so far with probability s/n
 - We need to show that after seeing element $n+1$ the sample maintains the property
 - Sample contains each element seen so far with probability $s/(n+1)$
- **Base case:**
 - After we see $n=s$ elements the sample S has the desired property
 - Each out of $n=s$ elements is in the sample with probability $s/s = 1$

Proof: By Induction

- **Inductive hypothesis:** After n elements, the sample S contains each element seen so far with prob. s/n
- **Now element $n+1$ arrives**
- **Inductive step:** For each element x already in S , probability that **the algorithm keeps x in S** is:

$$\left(1 - \frac{s}{n+1}\right) + \left(\frac{s}{n+1}\right)\left(\frac{s-1}{s}\right) = \frac{n}{n+1}$$

Element $n+1$ discarded Element $n+1$ not discarded Element in the sample not picked

- So, at time n , tuples in S were there with prob. s/n
- Time $n \rightarrow n+1$, tuple stayed in S with prob. $n/(n+1)$
- So prob. tuple is in S at time $n+1 = \frac{s}{n} \cdot \frac{n}{n+1} = \frac{s}{n+1}$

Roadmap

- Motivation
- Sampling
 - Fixed-portion & fixed-size (reservoir sampling)
- Filtering
 - Bloom filter
- Counting
 - Estimating # of distinct values, moments
- Sliding window
 - Counting # of 1's in the window

FILTERING

Stream Filtering

- Application: spam filtering
 - Check incoming emails against **a large set** of known email addresses (e.g., 1 billion)
- Application: URL filtering in Web crawling
 - Check if discovered URL's have already been crawled

Bloom filter

- Check if an object o is in a set S
 - without comparing o with all objects in S (explicitly)
- No false negatives
 - If Bloom says no, then o is definitely not in S
- But may have false positives
 - If Bloom says yes, it is possible that o is not in S

Components in a Bloom filter

- An array ***A*** of ***n*** bits, initially all 0's: ***A[0..n-1]***
- A set of hash functions, each
 - takes an object (stream element) as the input
 - returns a position in the array: ***0..n-1***
- A set ***S*** of objects

Construct and apply the filter

- Construction: for each object \mathbf{o} in S ,
 - Apply each hash function h_j to \mathbf{o}
 - If $h_j(\mathbf{o}) = i$, set $A[i] = 1$ (if it was 0)
- Application: check if new object \mathbf{o}' is in S
 - Hash \mathbf{o}' using each hash function
 - If for some hash function $h_j(\mathbf{o}') = i$ and $A[i] = 0$, stop and report \mathbf{o}' **not** in S

Example


- 11-bit array ($n=11$)
- Stream elements = integers
- Two hash functions
 - $h_1(x) = (\text{odd-position bits from the right}) \% 11$
 - $h_2(x) = (\text{even-position bits from the right}) \% 11$

Example: Building the filter

Stream element	h_1	h_2	Filter											
			<table><tr><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td></tr></table>	0	0	0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0	0	0				
$25 = 1\ 1\ 0\ 0\ 1$	5	2	<table><tr><td>0</td><td>0</td><td>1</td><td>0</td><td>0</td><td>1</td><td>0</td><td>0</td><td>0</td><td>0</td><td>0</td></tr></table>	0	0	1	0	0	1	0	0	0	0	0
0	0	1	0	0	1	0	0	0	0	0				
$159 = 1\ 0\ 0\ 1\ 1\ 1\ 1\ 1$	7	0	<table><tr><td>1</td><td>0</td><td>1</td><td>0</td><td>0</td><td>1</td><td>0</td><td>1</td><td>0</td><td>0</td><td>0</td></tr></table>	1	0	1	0	0	1	0	1	0	0	0
1	0	1	0	0	1	0	1	0	0	0				
$585 = 1\ 0\ 0\ 1\ 0\ 0\ 1\ 0\ 0\ 1$	9	7	<table><tr><td>1</td><td>0</td><td>1</td><td>0</td><td>0</td><td>1</td><td>0</td><td>1</td><td>0</td><td>1</td><td>0</td></tr></table>	1	0	1	0	0	1	0	1	0	1	0
1	0	1	0	0	1	0	1	0	1	0				


Example: Using the filter

- Is 118 in the set?
 - No false negative in Bloom




Example: False positive

- Is 38 in the set (25, 159, 585)?
 - It turns on the same bits as 25, but in diff. ways



Recall



False positive

- x not in S , but identified as in S
- Reason:
 - For all hash functions, x hashes into an **1** position
 - That is, $h_i(x) = h_j(e)$, for some e in S
 - Note: j may be different from i

False positive rate (upper bound)

- n = # of bits in array
- k = # of hash functions
- m = # of elements inserted
- f = fraction of 1's in bit array
- False positive rate = f^k
 - The probability of saying YES to the question “Is X in the set?”
- $f \leq m*k/n$ (this is an upper bound, why?)

Example (upper bound)

- $n = 8$ billions (bits in array)
- $m = 1$ billion (objects in the set)
- $k = 1$ (# of hash function)
- f is estimated to be $km/n = 1/8$
 - $1/8$ of bits in the array are 1
- False positive rate $\leq 1/8 = .125$

Accurate Estimation of fraction of 1's

- n = # of bits in array
- k = # of hash functions
- m = # of elements inserted
- Fraction of 1's = the probability that a bit in the array is set to 1 by at least one hashing
 - Total # of hashings: $k * m$

Estimation model

- Consider throwing d darts on t targets
- What is the probability, denoted as p , of a given target hit by at least one dart?
 - Prob. of a target not hit by a dart = $1 - 1/t$
 - Prob. of a target not hit by all darts = $(1 - 1/t)^d$
since $(1 - 1/t)^t = ((1 + \frac{1}{-t})^{-t})^{-1} = e^{-1} = 1/e$ for large t
 - we have $(1 - 1/t)^{t \cdot d/t} = e^{-d/t}$
 - $p = 1 - e^{-d/t}$

$$e = \lim_{n \rightarrow \infty} \left(1 + \frac{1}{n}\right)^n$$

Estimating the fraction of 1's

- n = # of bits in array
- k = # of hash functions
- m = # of elements inserted
- Fraction of 1's = the probability that a bit in the array is set to 1 by at least one hashing
– $1 - e^{-km/n}$

False Positive Rate (Accurate)

- f = fraction of 1's in bit array
- k = # of hash functions
- m = # of elements inserted
- False positive rate = f^k
- Instead of $f \leq m*k/n$, we have $f = 1 - e^{-km/n}$
- so false positive rate = $(1 - e^{-km/n})^k$
 - Multiple hash functions hit the same bit

Example (actual rate)


- $n = 8$ billions (bits in array)
- $m = 1$ billion (objects in the set)
- $k = 1$ (# of hash function)
- Recall that false positive rate $\leq 1/8 = .125$
- Actual rate = $(1 - e^{-km/n})^k = 1 - e^{-1/8} = .1175$
- What if $k = 2$?

Example (actual rate)

- $n = 8$ billions (bits in array)
- $m = 1$ billion (objects in the set)
- $k = 2$ (# of hash function)
- Actual rate = $(1 - e^{-km/n})^k = (1 - e^{-2/8})^2 = .2212^2 = .0489$

Optimal k

- $n = 8$ billions
- $m = 1$ billion
- $k = \#$ of hash functions
- Rate = $(1 - e^{-km/n})^k$
= $(1 - e^{-k/8})^k$
- Optimal $k = n/m \ln(2)$
 - E.g., $k = 8 \ln(2) = 5.54 \sim 6$
- Error rate at $k = 6$: $(1 - e^{-6/8})^6 = .0216$



Roadmap

- Motivation
- Sampling
 - Fixed-portion & fixed-size (reservoir sampling)
- Filtering
 - Bloom filter
- Counting
 - Estimating # of distinct values, moments
- Sliding window
 - Counting # of 1's in the window

COUNTING (DISTINCT ELEMENTS)

Compute # of distinct elements

- Applications
 - Compute # of **distinct users** to Facebook
 - Compute # of **distinct queries** submitted to Google
- Obvious solution:
 - Hash table of distinct elements
 - Check if new element is there; if not, add it
- Problems?

Flajolet-Martin algorithm

- Estimating the counts
1. Hash every element a to a sufficiently long bit-string (e.g., $h(\text{element } a) = 1100$ – 4 bits)
 2. Maintain R = length of *longest* trailing zeros among all bit-strings (e.g., $R = 2$)
 3. Estimate count = 2^R , e.g., $2^2 = 4$

Example (estimate by trailing 0s)

- Consider 4 distinct elements: a, b, c, d
- Hash value into bit string of length 4
- How likely do we see at least one hash value with a 0 in the last bit? Next slide
 - $\text{hash}(a) = 0010$
 - $\text{hash}(b) = 0111$
 - $\text{hash}(c) = 1010$
 - $\text{hash}(d) = 1111$

Example: at least one ends with 0

- E.g.,
 - $\text{hash}(a) = 0010$
 - $\text{hash}(b) = 0111$
 - $\text{hash}(c) = 1010$
 - $\text{hash}(d) = 1111$
- Prob. of none of hash values ending with 0:
 - $(1-\frac{1}{2})^4$ (*every string ends with 1; there are four strings*)
- Prob. of at least one ending with 0:
 - $1-(1-\frac{1}{2})^4 = .9375$

Example: at least one ends with 00

- E.g.,
 - $\text{hash}(a) = 0100$
 - $\text{hash}(b) = 0111$
 - $\text{hash}(c) = 1010$
 - $\text{hash}(d) = 1111$
- Prob. of someone ending with 00:
 - $(\frac{1}{2}) (\frac{1}{2}) = (\frac{1}{2})^2 = 2^{-2}$
- Prob. of none ending with 00:
 - $(1 - (\frac{1}{2})^2)^4 = .32$
- Prob. of at least one ending with 00:
 - $1 - .32 = .68$

Example: at least one ends with 000

- E.g.,
 - $\text{hash}(a) = 1000$
 - $\text{hash}(b) = 0111$
 - $\text{hash}(c) = 1010$
 - $\text{hash}(d) = 1111$
- Prob. of someone ending with 000:
 - $(\frac{1}{2}) (\frac{1}{2}) (\frac{1}{2}) = (\frac{1}{2})^3 = 2^{-3}$
- Prob. of none ending with 000:
 - $(1 - (\frac{1}{2})^3)^4 = .59$
- Prob. of at least one ending with 000:
 - $1 - .59 = .41$

Why it works?

- Prob. of $h(a)$ having at least r trailing 0's
– 2^{-r}
- Suppose there are m distinct elements (the true answer)
- Prob. that $h(a)$ for some element a has at least r trailing 0's (as in the examples in the previous slides)

$$1 - (1 - 2^{-r})^m = 1 - (1 - 2^{-r})^{2^r \frac{m}{2^r}} = \mathbf{1 - e^{-\frac{m}{2^r}}}$$

Why it works?

- Prob. that $h(\mathbf{a})$ for some element \mathbf{a} has at least r trailing 0's

$$\square p = 1 - (1 - 2^{-r})^m = 1 - e^{-\frac{m}{2^r}}$$

- Taylor expansion of e^x

$$\square 1 + \frac{x^1}{1!} + \frac{x^2}{2!} + \frac{x^3}{3!} + \dots \sim 1 + \frac{x^1}{1!}, \text{ if } |X| \ll 1$$

- $p = 1 - e^{-\frac{m}{2^r}} \sim 1 - \left(1 - \frac{m}{2^r}\right) = \frac{m}{2^r}, \text{ if } 2^r \gg m$

Why it works?

- Prob. that $h(a)$ for some element a has at least r trailing 0's

- $p = 1 - (1 - 2^{-r})^m = 1 - e^{-\frac{m}{2^r}}$

- Prob. that $h(a)$ for NO element a has at least r trailing 0's

- $p' = (1 - 2^{-r})^m = e^{-\frac{m}{2^r}}$

(1) If $2^r \gg m, p = \frac{m}{2^r} \rightarrow 0; p' = 1$

- the probability of finding a tail length at least r approaches 0
- R is unlikely to be too large, since otherwise it may not show up at all

(2) If $2^r \ll m, p = 1 - 1/e^{\frac{m}{2^r}} \rightarrow 1; p' = 0$

- the probability that we shall find a tail of length at least r approaches 1
- Since R is the longest 0's, it is unlikely to be too small.


Therefore, 2^R is around m

Problems in combining estimates

- We can hash multiple times, take **avg.** of 2^R values
- Problem: $\text{ExpectedValue}(2^R) \rightarrow \infty$
 - When $2^R \geq m$, increase R by 1 \Rightarrow **probability halves, but value 2^R doubles**
 - $p = 1 - (1 - 2^{-r})^m = 1 - e^{-\frac{m}{2^r}}$
 - Contribution from each large R to $E(2^R)$ grows, when R grows
 - Can have very large 2^R
- What about taking median instead?

Examples of Probability

- N people (e.g., $N=14$) with different age j
 - Probability $P(j) = N(j)/N$
 - Most probable? Media=? Average(mean) $\langle j \rangle = ?$



Combining the estimates

- Avg only: what if **one very large value**?
- Median: all values are power of 2
 - 1, 2, 4, 8,...,1024, 2048,...
- Solution:
 - Partition hash functions into **small groups**
 - Take **average** for each group
 - Take the **median of the averages**

COUNTING (MOMENTS)

Roadmap

- Motivation
- Sampling
 - Fixed-portion & fixed-size (reservoir sampling)
- Filtering
 - Bloom filter
- Counting
 - Estimating # of distinct values, moments
- Sliding window
 - Counting # of 1's in the window

Moments

- A stream S of elements drawn from a universal set: v_1, v_2, \dots, v_n
 - m_i is the number of occurrences of v_i in S
 - $(\textcolor{red}{1}, \textcolor{green}{4}, \textcolor{red}{1}, 3, \textcolor{green}{4}, \textcolor{red}{1}), m_{\textcolor{red}{1}}=3, m_{\textcolor{green}{2}}=2;$
- k -th moment of S :
 - $\sum_{i=1}^n (m_i)^k$

K-th moments

- 0-th moment of the stream S
 - # of **distinct elements** in S
 - **(1, 4, 1, 3, 4, 1)**
- 1st moment of S
 - **Length** of S
- 2nd moment of S : **sum of squared frequencies**
 - **Surprise number**, measuring **the evenness** of distribution of elements in S

$$- \sum_{i=1}^n (m_i)^k$$

Surprise number

- Stream of 100 elements, **11** values appeared

- Unsurprising: $m_i = 10, 9, 9, 9, 9, 9, 9, 9, 9, 9, 9$
 – Surprise number = $10^2 + 10 * 9^2 = 910$

$$- \sum_{i=1}^n (m_i)^k$$

- Surprising: 90, 1, 1, 1, 1, 1, 1, 1, 1, 1
 – Surprise number = $90^2 + 10 * 1^2 = 8,110$

AMS (Alon-Matias-Szegedy) Algorithm

- Estimating **2nd moment** of a stream of length n
- Pick k random numbers between 1 to n
- For each, construct a variable X at position t
 - Record its count from position t onwards to n as $X.value$
- Estimate $= \frac{1}{k} \sum_{i=1}^k n(2x_k.value - 1)$
 - Explain next


Example

- Stream: a, b, c, b, d, a, c, d, a, b, d, c, a, a, b
 - Stream length $n = 15$
 - **a** occurs 5 times
 - **b** occurs 4 times
 - **c** occurs 3 times
 - **d** occurs 3 times
- 2^{nd} moment = $5^2 + 4^2 + 3^2 + 3^2 = 59$

Random variables


- Each random variable X records:
 - $X.element$: element in X
 - $X.value$: # of occurrences of X from time t to n
- $X.value = 1$, at time t
 - At time t , we have the 1st encounter of this element
- $X.value++$, when another $X.element$ is seen

Random variables

- Stream: a, b, **c**, b, d, a, c, **d**, a, b, d, c, **a**, a, b


3 8 13
- Suppose we keep three variables: X_1 , X_2 , X_3
 - Introduced at position: 3, 8, and 13
- Position 3: $X_1.\text{element} = c$, $X_1.\text{value} = 1$
- Position 7: $X_1.\text{value} = 2$


Random variables

- Stream: a, b, **c**, b, d, a, **c**, **d**, a, b, **d**, **c**, **a**, **a**, b

- Position 8: $X_2.\text{element} = d$, $X_2.\text{value} = 1$
- Position 11: $X_2.\text{value} = 2$
- Position 12: $X_1.\text{value} = 3$
- Position 13: $X_3.\text{element} = a$, $X_3.\text{value} = 1$
- Position 14: $X_3.\text{value} = 2$

Random variables: final values

- $X_1.\text{value} = 3, X_2.\text{value} = 2, X_3.\text{value} = 2$
- Estimate of 2nd moment = **$n(2 * X.\text{value} - 1)$**
- Estimate using X_1 : $15(6-1) = 75$
- Estimate using X_2 or X_3 : $15(4-1) = 45$
- Avg. = $(75+45+45)/3 = 55$ (recall actual is 59)

Why AMS works?

- Stream: a, b, **c**, b, d, a, **c**, **d**, a, b, **d**, **c**, **a**, **a**, b


- $e(i)$** : element that appears in position i
 - A random variable introduced at this position will have $X.\text{element} = e(i)$
- $c(i)$** : # of times $e(i)$ appears in positions $i \dots n$
 - $X.\text{value} = c(i)$
- $e(6) = a, c(6) = 4, \text{ // 'a' appeared 4 times in } [6..n]$

Why AMS works?

- Stream: a, b, c, b, d, a, c, d, a, b, d, c, a, a, b

↑
3

↑
8

↑
13

- $e(1) = a, c(1) = 5 = m_a$

- $e(2) = b, c(2) = 4 = m_b$

- $e(3) = c, c(3) = 3 = m_c$

- $e(4) = b, c(4) = m_b - 1$

- ...

- $e(13) = a, c(13) = 2$

- $e(14) = a, c(14) = 1$

- $e(15) = b, c(15) = 1$

1, 2, 3, ..., m_a

If we can have a lot of random variables (e.g., 15)...


Why AMS works?

- Estimate = $1/k \sum_{i=1}^k n(2x_k.value - 1)$
 - $E(n(2X.value - 1))$
 - average over all positions i between 1 and n
- $$= \frac{1}{n} \sum_{i=1}^n n(2c(i) - 1)$$
- $$= \sum_{i=1}^n (2c(i) - 1)$$
- $$= \sum_x 1 + 3 + \dots + (2m_x - 1) \quad \text{for each } x$$
- $$= \sum_x m_x^2 \quad // \text{ this is the 2}^{nd} \text{ moments}$$

- Note: $1+3+\dots + (2n-1) = n^2$

$$\sum_{i=1}^{m_i} (2i - 1) = 2 \frac{m_i(m_i + 1)}{2} - m_i = (m_i)^2$$

Expectation Analysis



- **2nd moment** of $S = \sum_x m_x^2$
- c_t ... number of times item at time t appears from time t onwards ($c_1=m_a$, $c_2=m_a-1$, $c_3=m_b$)

- $E[f(X)] = \frac{1}{n} \sum_{t=1}^n n(2c_t - 1)$

$$= \frac{1}{n} \sum_x n (1 + 3 + 5 + \dots + 2m_x - 1)$$

m_i ... total count of item i in the stream (we are assuming stream has length n)


Group times by the value seen

Time t when the last x is seen ($c_t=1$)

Time t when the penultimate i is seen ($c_t=2$)

Time t when the first x is seen ($c_t=m_i$)

Expectation Analysis



- $E[f(X)] = \frac{1}{n} \sum_x n (1 + 3 + 5 + \dots + 2m_x - 1)$
 - Little side calculation: $(1 + 3 + 5 + \dots + 2m_x - 1) = \sum_{x=1}^{m_x} (2x - 1) = 2 \frac{m_x(m_x+1)}{2} - m_x = (m_x)^2$
- Then $E[f(X)] = \frac{1}{n} \sum_x n (m_x)^2$
- So, $E[f(X)] = \sum_x (m_x)^2$
- We have the second moment (in expectation)!

Higher-Order Moments

- To estimate the k^{th} moment, we essentially use the same algorithm but change the estimate:
 - For $k=2$ we used $n (2 \cdot c - 1)$
 - For $k=3$ we use: $n (3 \cdot c^2 - 3c + 1)$ (where $c=X.\text{val}$)
- Why?
 - For $k=2$: Remember we had $(1 + 3 + 5 + \dots + 2m_i - 1)$ and we showed terms $2c-1$ (for $c=1, \dots, m$) sum to m^2
 - $\sum_{c=1}^m 2c - 1 = \sum_{c=1}^m c^2 - \sum_{c=1}^m (c - 1)^2 = m^2$
 - So: $2c - 1 = c^2 - (c - 1)^2$
 - For $k=3$: $c^3 - (c-1)^3 = 3c^2 - 3c + 1$ $\sum_{v=1}^m 3v^2 - 3v + 1 = m^3$
 - Generally: Estimate = $n (c^k - (c - 1)^k)$

Combining Samples

- **In practice:**
 - Compute $f(X) = n(2c - 1)$ for as many variables X as you can fit in memory
 - Average them in groups
 - Take median of averages
- **Problem: Streams never end**
 - We assumed there was a number n , the number of positions in the stream
 - But real streams go on forever, so n is a variable – the number of inputs seen so far

Streams Never End: Fixups

- (1) The variables X have n as a factor – keep n separately; just hold the count in X
- (2) Suppose we can only store k counts.
We must throw some X s out as time goes on:
 - Objective:
 - Estimating 2nd moment of a stream of length n
 - Each starting time t is selected with probability k/n
 - Solution: (fixed-size sampling!)
 - Choose the first k times for k variables
 - When the n^{th} element arrives ($n > k$), choose it with probability k/n
 - If you choose it, throw one of the previously stored variables X out, with equal probability

SLIDING WINDOWS

Roadmap

- Motivation
- Sampling
 - Fixed-portion & fixed-size (reservoir sampling)
- Filtering
 - Bloom filter
- Counting
 - Estimating # of distinct values, moments
- Sliding window
 - Counting # of 1's in the window

Sliding Windows

- A useful model of stream processing is that queries are about a **window** of length N
 - the N most recent elements received
- **Interesting case:** N is so large that the data cannot be stored in memory, or even on disk
 - Or, there are so many streams that windows for all cannot be stored
- **Amazon example:**
 - For every product X we keep 0/1 stream of whether that product was sold in the n -th transaction
 - We want answer queries, how many times have we sold X in the last k sales (e.g., $k = 10, 20$, or 200 ; $N=100,000$)

Sliding Window: 1 Stream

N = 6

- **Sliding window on a single stream:**

q w e r t y u i o p a s d f g h j k l z x c v b n m

q w e r t y u i o p a s d f g h j k l z x c v b n m

q w e r t y u i o p a s d f g h j k l z x c v b n m

q w e r t y u i o p a s d f g h j k l z x c v b n m

← **Past** **Future** →

Counting Bits (1)


- **Problem:**

- Given a stream of **0**s and **1**s
- Be prepared to answer queries of the form
How many 1s are in the last N bits?

- **Obvious solution:**

Store the most recent N bits

- When new bit comes in, discard the $N+1^{\text{st}}$ bit



Suppose $N=6$

Counting Bits (2)

- You cannot get an exact answer without storing the entire window


- Real Problem:

What if we cannot afford to store N bits?

- E.g., we're processing 1 billion streams and

$N = 1$ billion

0 1 0 0 1 1 0 1 1 1 0 1 0 1 0 1 1 0




← Past

Future →

- But we are happy with an approximate answer

An attempt: Simple solution

- **Q: How many 1s are in the last N bits?**
- A simple solution that does not really solve our problem: **Uniformity assumption**




- **Maintain 2 counters:**
 - S : number of 1s from the beginning of the stream
 - Z : number of 0s from the beginning of the stream
- **How many 1s are in the last N bits?** $N \cdot \frac{S}{S+Z}$
- **But, what if stream is non-uniform?**
 - What if distribution changes over time?
 - Cannot handle various k

DGIM Method

- **DGIM solution that does not assume uniformity**
- We store $O(\log N \times \log N)$ bits per stream
 - $O(\log^2 N)$
- **Solution gives approximate answer, never off by more than 50%**
 - Error factor can be reduced to any fraction > 0 , with more complicated algorithm and **proportionally more stored bits**

Idea: Exponential Windows


- **Solution that doesn't (quite) work:**
 - Summarize **exponentially increasing** regions of the stream, looking backward
 - Drop small regions if they begin at the same point as a larger region



We can reconstruct the count of the last N bits, except we are not sure how many of the last 6 1s are included in the N

What's Not So Good?

- As long as the **1s** are fairly evenly distributed, the error due to the unknown region is small – **no more than 50%**
- But it could be that all the **1s** are in the unknown area at the end
- In that case, **the error is unbounded!**




DGIM Algorithm

- Storage: $O(\log^2 N)$ bits (N is the window size)
- Error rate for the queries $\leq 50\%$
- Key idea:
 - Partition N into a (small) set of buckets
 - Remember count for each bucket
 - Use the counts to approximate answers to queries

Fixup: DGIM method

- **Idea:** Instead of summarizing fixed-length blocks, summarize blocks with specific number of **1s**:
 - Let the block *sizes* (number of **1s**) increase exponentially
- When there are few **1s** in the window, block sizes stay small, so errors are small




DGIM: Timestamps

- Each bit in the stream has a *timestamp*, starting **1, 2, ...**
- Record timestamps modulo **N** (**the window size**), so we can represent any **relevant** timestamp in **$O(\log_2 N)$** bits

Bucket

- Each represents a sequence of bits in window
 - It does not store the actual bits
 - Rather a timestamp and # of 1's in the sequence
- Timestamp of bucket
 - Timestamp of its end time
- Bucket size = # of 1's in the bucket
 - Always some power of 2: 1, 2, 4, ...

Example Buckets



Window size $N = 25$


Rules for creating buckets

- Rightmost bit of each bucket = 1
- Every **1 position** in window is in some bucket
- A position can only be in a single bucket
- At most two buckets can have the same size
- Size of older buckets \geq size of news ones

Representing a Stream by Buckets


- Either **one** or **two** buckets with the same **power-of-2 number of 1s**
- **Buckets do not overlap in timestamps**
- **Buckets are sorted by size**
 - Earlier buckets are not smaller than later buckets
- Buckets disappear when their **end-time** is $> N$ time units in the past

Example buckets



Window size $N = 25$

Example: Bucketized Stream



Three properties of buckets that are maintained:

- Either **one** or **two** buckets with the same **power-of-2** number of **1s**
- Buckets do not overlap in timestamps
- Buckets are sorted by size

Updating Buckets (1)


- When a new bit comes in, drop the last (oldest) bucket if its **end-time** is prior to **N** time units before the current time
- **2 cases:** Current bit is **0** or **1**
- **If the current bit is 0:**
no other changes are needed

Updating Buckets (2)


- **If the current bit is 1:**
 - (1) Create a new bucket of size **1**, for just this bit
 - End timestamp = current time
 - (2) If there are now **three buckets of size 1**,
combine the oldest two into a bucket of size 2
 - (3) If there are now **three buckets of size 2**,
combine the oldest two into a bucket of size 4
 - (4) And so on ...

Example: Updating Buckets


Current state of the stream:




Bit of value 1 arrives




Two blue buckets get merged into a yellow bucket




Next bit 1 arrives, new blue bucket is created, then 0 comes, then 1:



Buckets get merged...




State of the buckets after merging



DGIM: Buckets

- A **bucket** in the DGIM method is a record consisting of:
 - (A) The timestamp of its end [$O(\log_2 N)$ bits]
 - (B) The number of 1s between its beginning and end [$O(\log_2 \log_2 N)$ bits]
 - $\log_2 N$ is the maximum # of bit, X , in a bucket (of size N)
 - to store X , we need $\log_2 X$ bits
- **Constraint on buckets:**
 Number of **1s** must be a power of 2
 - That explains the $O(\log_2 \log_2 N)$ in (B) above



Storage for each bucket

- Timestamp: $0..N-1$ (N is the window size)
 - So $\log_2 N$ bits
- Number of 1's: $2^j \leq N, j \leq \log_2 N$
 - So $\log_2(\log_2 N)$ for representing j
 - Can ignore; too small comparing to the timestamp requirement
- Each bucket requires $\approx O(\log_2 N)$


Storage requirements of DGIM

- At most $2*j$ buckets
 - of sizes: $2^j, 2^{j-1}, \dots, 1$ (at most two for each size)
- Size of the largest bucket $2^j \leq N$
 - So $j \leq \log_2 N$ and $2j \leq 2\log_2 N$
- Total storage: $O(\log_2 N * \log_2 N)$ or $O(\log^2 N)$
 - Recall that each bucket requires $O(\log_2 N)$

How to Query?

- To estimate the number of 1s in the most recent N bits:
 1. Sum the sizes of all buckets **but the last**
(note “size” means the number of 1s in the bucket)
 2. Add half the size of the last bucket
- **Remember:** We do not know how many **1s** of the last bucket are still within the wanted window

Example: Bucketized Stream



How close is the estimate?

- Suppose # of 1's in the last bucket $b = 2^j$
- **Case 1: estimate < actual value c**
 - Worst case: all 1's in bucket b are within range
 - So estimate missed “at most half of 2^j ” -> 2^{j-1}
 - **Want to show $c \geq 2^j$, so what's the minimum C ?**
 - C has at least one 1 from b , plus at least one of buckets of lower powers: $2^{j-1} + 2^{j-2} \dots + 1 = 2^j - 1$; $c \geq 1 + 2^j - 1$; missed at most 2^{j-1}
 - $1 + 2 + 4 + \dots + 2^{r-1} = 2^r - 1$
 - So estimate missed **at most 50% of c**
 - That is, **the estimate is at least 50% of c**

How close is the estimate?

- Suppose # of 1's in the last bucket **$b = 2^j$**
- ***Case 2: estimate > actual value c***
 - Worst case: **only rightmost bit of b is within range**
 - And only one bucket for each smaller power
 - **$c = 1 + 2^{j-1} + 2^{j-2} + \dots + 1 = 1 + 2^j - 1 = 2^j$**
 - Estimate = 2^{j-1} (last bucket) + $2^{j-1} + \dots + 1$
 $= 2^j - 1$ (*c minus the right most bit*) + 2^{j-1} (last bucket)
 - **$2^{j-1} + 2^{j-2} \dots + 1 = 2^j - 1$**
 - So ***estimate is no more than 50% greater than c***

Extensions

- Can we use the same trick to answer queries
How many 1's in the last k ? where $k < N$?
 - **A:** Find earliest bucket **B** that overlaps with k .
Number of **1s** is the **sum of sizes of more recent buckets + $\frac{1}{2}$ size of B**

