Modelling light propagation through radial-director liquid crystal waveguides

Miha Čančula

Faculty of Mathematics and Physics, University of Ljubljana, Slovenia

July 4, 2013

Outline

- Motivation
- FDTD Method
  - Maxwell's equations
  - Numerical modelling
  - Testing
- Results
  - Electric field
  - Pulse shape
  - Eigenmodes
- Conclusions

Motivation

- ~~Unique properties~~ of liquid crystals for guiding light
- Sm A fibres with radial director profile using 8CB
- Defects in LC $\leftrightarrow$ defects in optic fields



Methods – Maxwell's Equations

$$\nabla \cdot \vec{D} = \rho_f \qquad \nabla \cdot \vec{B} = 0$$

$$\nabla \times \vec{E} = -\frac{\partial \vec{B}}{\partial t} \qquad \nabla \times \vec{H} = \vec{J}_f + \frac{\partial \vec{D}}{\partial t}$$

Nice for simulations

- Time-derivative of one field $\propto$ space-derivative of other
- Alternate between calculating E and H
- Suitable for parallel computation

Methods – Finite-difference time-domain

$$\varepsilon \frac{\partial \vec{E}}{\partial t} = \nabla \times \vec{H} \qquad \frac{\partial \vec{H}}{\partial t} = -\nabla \times \vec{E}$$

- Direct time evolution of electromagnetic fields
- Anisotropic and non-uniform ε, follows director as $\Delta\varepsilon \propto Q$
- Staggered grid, fields known at different times





Methods – Testing

- Uniform director
- Refraction on interface
- Photonic bandgap of periodic structure





Results – Electric field

- Gaussian beam $\rightarrow$ Laguerre-Gaussian, dark spot at the axis
- The difference in refraction index deforms the beam



Results – Pulse shape



- 8 intensity regions in 2 ranks
- Positioned diagonally to incident polarization
- Two propagation modes with different polarizations

Results – Propagation modes



Faster mode



Slower mode

- Polarization forms -1 disclination line
- Rotated by 45° with respect to each other



Conclusions

Method

- Model the propagation of light through media with non-uniform fully-anisotropic dielectric tensor
- Direct solving of discretized Maxwell's equations

Results

- Topological defect in LC $\rightarrow$ defect in optical field
- Propagation modes of a radial-director liquid crystal waveguide
- Splitting of a single pulse into eight intensity regions