Real result

Real public test sites · actual captured output · latest update (UTC): 2026-10-27T22:20:37+00:00

> This document shows what the Cerberus tool integrations actually returned against public practice sites. The outputs are point-in-time observations, not guaranteed future results. No simulated result is presented as real.

At a glance

Tool	Latest status	Captured at (UTC)
nmap	CAPTURED	2026-10-27T22:20:27+00:00
sqlmap	CAPTURED	2026-10-27T22:20:37+00:00
metasploit	NOT TESTED	Not tested

Why not `127.0.0.1`? The earlier beginner lab starts a temporary intentionally vulnerable service there, so it does have something to test during the command. This document instead uses actual websites on the public Internet, as requested.

Read results carefully. Open ports and service versions can change; a HIGH result is a finding for a deliberately vulnerable training site, not for your application. A negative, failure, or timeout is not proof that a site is secure. Each entry below states its last attempt and any previous successful capture.

Authorization and limits

- **Nmap:** `scanme.nmap.org`. Its operator explicitly permits Nmap scans, but not exploits or denial of service, and asks for no more than 12 scans per day. This report uses one narrow TCP scan of ports 22, 80, and 443, with light service detection and **no NSE scripts**.
- **sqlmap:** `https://sekumart.sekuripy.hr/product.php?id=1`. SekuriPy operates this public, intentionally vulnerable sqlmap playground. This report tests only the `id` parameter of this page using GET, level 1, risk 1, one thread and error-based detection. No dump, file access, OS command, or database enumeration is requested.
- Check the current site policies before each refresh. Permission for one demo does not authorize testing another website. Do not repeatedly run public scans or set up automatic polling.

1. Nmap — real public scan

Latest attempt: CAPTURED · 2026-10-27T22:20:27+00:00. The real tool completed and the framework returned a recognizable result.

This capture: 2026-10-27T22:20:27+00:00 · Target: `http://scanme.nmap.org/` · Version: Nmap version 7.95 (https://nmap.org).

Cerberus framework output

This is a readable selection of fields from the actual `nmap_scanner` finding, not a simulated terminal transcript.

```
[INFO] Nmap scan: 3 open ports on scanme.nmap.org
target: http://scanme.nmap.org/
module: nmap_scanner
probed TCP ports: [22, 80, 443]
open TCP ports: [22, 80, 443]
services:
  22/tcp  ssh OpenSSH 6.6.1p1 Ubuntu 2ubuntu2.13
  80/tcp  http Apache httpd 2.4.7
  443/tcp  https
confidence: high
verified: false
```

Nmap's actual XML output — excerpt

The adapter requests XML (`-oX -`). The following elements and attributes come from that run; they are reformatted and other XML is omitted. Closed or filtered ports do not appear as open findings.

```
<status state="up" reason="user-set" />
<address addr="45.33.32.156" addrtype="ipv4" />
<port protocol="tcp" portid="22">
  <state state="open" reason="syn-ack" />
  <service name="ssh" product="OpenSSH" version="6.6.1p1 Ubuntu 2ubuntu2.13" method="probed" conf="10" />
</port>
<port protocol="tcp" portid="80">
  <state state="open" reason="syn-ack" />
  <service name="http" product="Apache httpd" version="2.4.7" method="probed" conf="10" />
</port>
<port protocol="tcp" portid="443">
  <state state="open" reason="syn-ack" />
  <service name="https" method="table" conf="3" />
</port>
```

How to read it: `open` means that a connection was accepted during this scan. `service`, `product`, and `version` are Nmap's observations or guesses; they are not, by themselves, proof of a vulnerability. Empty output, a skipped module, or an error is not a successful scan.

2. sqlmap — real public scan

Latest attempt: CAPTURED · 2026-10-27T22:20:37+00:00. The real tool completed and the framework returned a recognizable result.

This capture: 2026-10-27T22:20:37+00:00 · Target: `https://sekumart.sekuripy.hr/product.php?id=1` · Version: 1.9.6#stable.

Cerberus framework output

This is a readable selection of fields from the actual `sqlmap_scanner` finding produced by the framework. `verified: false` means a separate human validation has not been recorded.

```
[HIGH] sqlmap reported SQL injection in GET parameter 'id'
target: https://sekumart.sekuripy.hr/product.php?id=1
module: sqlmap_scanner
parameter: id (GET)
CWE: CWE-89
DBMS: MySQL >= 5.1 (MariaDB fork)
technique: error-based
  MySQL >= 5.1 AND error-based - WHERE, HAVING, ORDER BY or GROUP BY clause (EXTRACTVALUE)
confidence: high
verified: false
```

How to read the finding

- **HIGH / CWE-89** means sqlmap reported a possible SQL injection in the specified training-site parameter. Review and independently validate it.
- The recorded method, parameter, detection technique, and DBMS help identify the affected request.
- The adapter deliberately omits raw payloads from the framework finding and does not request a database dump. A separate excerpt of the real sqlmap console output appears on the next page.

3. sqlmap — actual console excerpt

The following is a selected excerpt from the real sqlmap subprocess output. It can include the detection payload sqlmap generated for the public practice site. Lines may be omitted; the excerpt is not fabricated. Never replay probes on an unauthorized site.

```
sqlmap identified the following injection point(s) with a total of 3 HTTP(s) requests:
---
Parameter: id (GET)
    Type: error-based
    Title: MySQL >= 5.1 AND error-based - WHERE, HAVING, ORDER BY or GROUP BY clause (EXTRACTVALUE)
    Payload: id=1 AND EXTRACTVALUE(7841,CONCAT(0x5c,0x7176626a71,(SELECT
(ELT(7841=7841,1))),0x716b627871))
---

[22:20:34] [INFO] the back-end DBMS is MySQL
web application technology: PHP, PHP 8.2.35, Apache
back-end DBMS: MySQL >= 5.1 (MariaDB fork)
```

Important: Payloads, timing, warnings, DBMS details, and the number of requests may change each time. The normal integration stores normalized evidence rather than the entire console transcript. No customer credentials or application secrets were used in this public example.

4. Metasploit — no real result yet

Latest attempt: NOT TESTED · not captured. No real Metasploit result: the Cerberus adapter is incompatible with real msfrpcd, and prior checks used a simulator.

The existing Cerberus adapter uses XML-RPC, while a real Metasploit `msfrpcd` uses MessagePack. The previous local tests used a fake service and do not show a real Metasploit result. Installing `msfconsole` alone does not resolve the protocol mismatch. No Metasploit scan of `scanme.nmap.org` was performed; its published permission covers Nmap scanning, not exploitation.

To include a genuine Metasploit example later, first make and verify an approved compatible integration, identify a public lab whose operator explicitly permits the **particular** module and activity, run only within those limits, and record the real output. Until then this entry remains **not tested**, not a manufactured result.

Important framework boundaries

The API, AI agent, and interface are not yet connected to these modules. Existing shared scope checks, Metasploit option handling, Nmap wildcard filtering, and testing-window enforcement have known gaps; the framework is not production-ready. The fixed-target demo avoids arbitrary targets and Nmap scripts, but does not repair those defects. sqlmap rejects an explicitly configured testing window rather than enforcing it and does not pin ordinary hostname DNS.

5. Refreshing and maintaining this PDF

What updates automatically

The on-demand refresh command reruns the selected **real**, fixed public-site checks, saves their latest results in `docs/real_results.json`, and rebuilds `docs/real result.pdf`. It does not run in the background or automatically scan sites when code changes. A failure is labelled as a failure; an older successful capture, if available, is separately dated. The local Nmap limit is best-effort: it cannot coordinate concurrent runners or count scans from other devices. You must follow the operator's global daily limit yourself.

First install the backend developer requirements, Nmap and sqlmap as described in the beginner guide. Review the operators' current policies, then run from the project root:

Mac / zsh

```
./backend/.venv/bin/python scripts/live_tests/public_tool_results.py all --confirm-public-tests
```

Windows / PowerShell

```
.\backend\.venv\Scripts\python.exe scripts\live_tests\public_tool_results.py all --confirm-public-tests
```

Use `nmap` or `sqlmap` instead of `all` to refresh just one. `all` means the two supported real checks, sequentially on **different public sites**; it does not include real Metasploit. Set `SQLMAP_PATH` or `NMAP_PATH` first if the binary is not on PATH. The command asks for explicit confirmation via the flag and accepts no arbitrary target.

Every time a tool is added

The contributor must add it to this document and the results data, find and verify an authorized test site and specific scope, perform a safe real test if feasible, record the genuine timestamped output, and rebuild and review this PDF. If no real test is possible, label the tool **not tested** and say why. The repository tests flag a missing registered-tool entry or a PDF whose source/data have changed; they cannot perform or certify a public scan.

References and permissions

- Nmap's permitted scope and rate limit: nmap.org/book/man-examples.html
- SekuMart's operator and public practice scope: sekuripy.hr/labs/sekumart
- sqlmap's official playground reference: sqlmap FAQ
- Metasploit's real RPC protocol: Rapid7 RPC API

The captures were made from a Linux sandbox; Mac and Windows refresh commands have not been executed on those operating systems for this edition. The displayed results are not a production assessment.