

Contents

Note on AI Assistance	ix
Code Availability	x
1 Introduction	1
1.1 Motivation	1
1.2 Problem Definition	1
1.3 Related Work	2
1.4 Our Contributions	2
2 Related Work	4
2.1 Foundational paradigms of MLC	4
2.1.1 Binary Relevance	4
2.1.2 Label Powerset	5
2.1.3 Classifier Chains	5
2.2 Hierarchy aware architectures	6
2.2.1 From flat to hierarchical models	6
2.2.2 Local vs global approaches	6
2.2.3 Local approaches (Top down)	7
2.2.4 Global approaches (single classifier)	7
2.2.5 Encoding the Hierarchy with Transformers and Graph Neural Networks	8
2.3 The rise of Large Language Models	9
2.3.1 Zero shot and few-shot classification	9
2.3.2 LLMs for data augmentation	10
2.3.3 LLMs as evaluation assistants	10
2.4 Focus on data-specific challenges	11
2.4.1 Class imbalance and tail labels	11
2.4.2 Strategies for low resource and few-shot scenarios	12

2.4.3	Parameter-efficient fine-tuning for low-resource adaptation	12
2.4.4	Data augmentation with LLMs	13
2.5	Case Study: The Evolution of Narrative and Propaganda Detection	14
2.5.1	From Flat Classification to Structural Priors	14
2.5.2	The Hierarchical and Multilingual Turn in SemEval	15
3	Task and Data Analysis	17
3.1	Task description	17
3.1.1	SemEval2025 Task 10: Overview	17
3.1.2	Task decomposition	17
3.1.3	Data and annotation	18
3.1.4	Participation and headline results	18
3.1.5	Evaluation of Subtask 2: Narrative Classification	19
3.2	Dataset Deep Dive	20
4	System architectures and methods	24
4.1	Architecture 0: Transformer Baseline	24
4.1.1	Core architecture and model choice	24
4.1.2	Mitigating the class imbalance	25
4.1.3	Hierarchical-Conditioned training and data handling	26
4.1.4	Training Methodology	26
4.1.5	Addressing data scarcity and class imbalance	28
4.2	Architecture 1: Zero-Shot Autogen Framework	30
4.2.1	Motivation and core concepts	30
4.2.2	System components and architecture	31
4.3	Architecture 2: The Traceable Actor-Critique Pipeline	35
4.3.1	Motivation: From Decomposed Agents to Holistic, Reasoned Analysis	35
4.3.2	Pipeline architecture	36
4.3.3	Sequential workflow and processing stages	36
4.3.4	Key advantages of the evidence-grounded pipeline	39
5	Experimental setups	41
5.1	Experimental setup	41
5.1.1	Supervised Baseline Setup (Architecture 0)	41
5.1.2	Zero-Shot Agentic framework	42
5.1.3	Computational Environment	42

5.1.4	Actor-Critic pipeline	42
6	Experiments and results	43
6.1	Synthesis of the multi-paradigm approach	43
6.2	Results for Architecture 0 (Transformer Baseline)	43
6.2.1	Experimental setup and evaluation metrics	44
6.2.2	Overall performance analysis	44
6.2.3	Language-specific performance analysis	47
6.2.4	Detailed performance analysis at optimal threshold	48
6.2.5	Key insights and limitations	50
6.3	Results for Architecture 1 (Zero-Shot Agentic Framework)	51
6.3.1	Overall Performance on English Test Set	51
6.3.2	Multilingual Performance Analysis	52
6.3.3	Critical implications for transformer baseline methodology	52
6.3.4	Detailed Error Analysis (on English DEV Set)	53
6.3.5	Key Insights and Limitations	54
6.4	Results for Architecture 2 (Actor-Critique Pipeline)	55
6.4.1	Experimental setup and evaluation framework	55
6.4.2	Ablation study: Impact of validation mechanism	56
6.4.3	Overall multilingual performance analysis	56
6.4.4	Key findings from comprehensive ablation study	56
6.4.5	Hierarchical performance characteristics	58
6.4.6	Language-specific narrative performance analysis	59
6.4.7	Subnarrative classification analysis	60
6.4.8	Comparative analysis with baseline architectures	62
6.4.9	Key insights and architectural implications	62
6.4.10	Cross-architectural comparison: AutoGen vs. Actor-Critique	64
6.4.11	Evaluation limitations and dataset size considerations	65
6.4.12	SemEval-2025 Task 10 competition performance	66
6.5	Consolidated Error Analysis: Persistent Challenges Across Paradigms	68
6.5.1	Semantic Ambiguity in Fine-Grained Classification	68
6.5.2	The "Hard Tail": Systematic Failure on Ultra-Rare Narratives	68
6.5.3	Persistent Hierarchical Degradation	69
6.5.4	Cross-Lingual Brittleness and Cultural Nuance	69

7	Discussion	71
7.1	The Paradigm Shift: From Fine-Tuning to Zero-Shot Reasoning	71
7.2	Architectural Divergence in LLM-Based Systems	72
7.3	The Surprising Ineffectiveness of the Critique Mechanism	74
7.4	Limitations of the Study	74
8	Conclusion	76
8.1	Principal Findings and Implications	76
8.2	Key Open Challenges	77
8.3	Concluding Remarks	78
	Appendix A Appendix	79
A.1	Appendix A: Performance Visualizations	79
A.1.1	A.1 No Validation Configuration	79
A.1.2	Bulgarian (BG) Performance	80
A.1.3	English (EN) Performance	81
A.1.4	Hindi (HI) Performance	81
A.1.5	Portuguese (PT) Performance	82
A.1.6	Russian (RU) Performance	82
A.1.7	A.2 Narrative Validation Configuration	83
A.1.8	Overall Performance Comparison	83
A.1.9	Representative Example: English (EN) Performance	84
A.1.10	A.3 Subnarrative Validation Configuration	85
A.1.11	Overall Performance Comparison	85
A.1.12	Representative Example: English (EN) Performance	86
A.2	Appendix B: Prompt Templates	87
A.2.1	B.1 Architecture 1: Binary Classification Prompts	87
A.2.2	B.2 Architecture 2: Category Classification Prompt	89
A.2.3	B.3 Architecture 2: Narrative Classification Prompt	89
A.2.4	B.4 Architecture 2: Subnarrative Classification Prompt	91
A.2.5	B.5 Architecture 2: Critic Prompts	94
A.2.6	B.6 Architecture 2: Refinement Prompts	96
A.2.7	B.7 Architecture 2: Text Cleaning Prompt	97
	Bibliography	98

Eidesstattliche Erklärung

108

Abstract

Hierarchical Multi-Label Classification (HMLC) for tasks like narrative detection in news media is severely hampered by extreme class imbalance and data scarcity, which challenge traditional supervised learning methods. To address these limitations, this paper presents a systematic comparison of three distinct architectural paradigms on the SemEval-2025 narrative detection task. We first establish a robust supervised baseline using a hierarchically-conditioned mDeBERTa model (Architecture 0). We then introduce two zero-shot frameworks that leverage Large Language Models (LLMs): a decomposed multi-agent system built with AutoGen (Architecture 1) and a novel, traceable actor-critique pipeline designed for evidence-grounded reasoning (Architecture 2).

Our comparative analysis yields three key findings. First, both zero-shot LLM architectures dramatically outperform the fine-tuned baseline, demonstrating the superiority of reasoning-based approaches in data-scarce regimes. Second, we show that direct, native-language processing is imperative for multilingual tasks, as a common "translate-then-classify" strategy causes a catastrophic drop in performance. Finally, our ablations reveal that a simple, single-pass evidence-grounded agent is more effective than a complex pipeline with an explicit validation step, highlighting that architectural simplicity combined with traceability can yield superior results. This work underscores a decisive paradigm shift towards traceable, knowledge-driven reasoning for complex, low-resource HMLC.

Acknowledgements

I would like to thank my supervisor Prof. Dr. Michael Granitzer and all members of the Data Science chair at the University of Passau for their guidance and support throughout this thesis.

I am grateful to Diana Nurbakova for her valuable guidance and mentorship during this research.

Special thanks to INSA Lyon for the opportunity to pursue this master thesis as part of the dual degree program.

Note on AI Assistance

This thesis was written with the assistance of large language models, specifically Google Gemini 2.5 Pro, which was used exclusively for rephrasing and improving the clarity of written content. All experimental work, including the design and implementation of the system architectures, the execution of experiments, data analysis, and the overall structure and argumentation of this thesis, was conducted entirely by the author. The use of AI was limited to linguistic refinement and did not contribute to the conceptual, methodological, or analytical aspects of this research.

Code Availability

The complete source code for all experiments, system architectures, and evaluation scripts presented in this thesis is publicly available on GitHub:

<https://github.com/NourJadiri/hybrid-text-classification>

The repository includes:

- Implementation of all three system architectures (baseline, AutoGen multi-agent, and actor-critique pipeline)
- Data preprocessing and evaluation scripts
- Configuration files and hyperparameters
- Instructions for reproducing the experiments

List of Figures

3.1	Long-tailed distribution of narrative labels in the SemEval-2025 training set. The bar chart shows the frequency of each coarse narrative, illustrating that a small number of narratives account for a large fraction of annotations while many narratives have very few examples. This severe imbalance motivates the use of zero-shot and evidence-grounded LLM approaches that do not rely on large per-class training counts.	21
3.2	Co-occurrence / conditional-probability visualizations for the most frequent narrative groups. Top: heatmap for CC narratives (normalized cell values). Bottom: conditional-probability visualization for URW narratives (directional). These paired views help identify both symmetric and directional dependencies among narratives.	23
4.1	Multi-Head mDeBERTa architecture for hierarchical narrative classification. The shared encoder produces a pooled representation that is consumed by a parent-level classifier and multiple conditionally-activated child heads; training aggregates parent loss across all samples while child losses are computed conditionally.	28
4.2	AutoGen multi-agent architecture showing the hierarchical propose-and-refine workflow. The Proxy Agent initiates the process, the Group Chat Manager coordinates narrative-level classification, and separate sub-managers handle sub-narrative classification for each confirmed parent narrative.	32
4.3	Actor–Critic pipeline: a stepwise, evidence-grounded workflow. The Actor generates structured claims grounded in verbatim evidence; the Critic validates these claims and may route feedback to the Actor for iterative refinement. Sub-narrative Actors and Critics repeat this process hierarchically.	37

List of Figures

6.1	Narrative classification performance analysis at optimal threshold (0.65). (a) shows language-specific performance variations, with Portuguese achieving the highest F1 scores. (b) displays the distribution of F1 scores across all narrative categories, revealing the challenge of class imbalance.	45
6.2	Subnarrative classification performance analysis at optimal threshold (0.7). (a) reveals significant language-specific challenges, particularly for Hindi. (b) shows the severely skewed F1 distribution, with most subnarratives achieving very low performance due to data scarcity.	45
6.3	F1 scores for individual narrative categories at threshold 0.65. Climate change narratives (CC:) generally outperform Ukraine-Russia war narratives (URW:), with “CC: Questioning measurements and science” achieving the highest performance. The substantial variation across categories highlights the impact of class imbalance and linguistic complexity.	46
6.4	Three-way comparative F1 Samples performance across languages and validation strategies. Each validation approach demonstrates distinct language-dependent effectiveness patterns, with Russian showing highest combined performance under subnarrative validation, Portuguese excelling with narrative validation, and Bulgarian achieving consistent improvements across both validation levels.	57
6.5	Top-performing narrative categories by language, showing the actor-critique pipeline’s effectiveness varies significantly across narrative types and languages. Portuguese and Russian show strong performance on climate and war narratives respectively, while English demonstrates more balanced performance across categories.	59
6.6	Subnarrative performance comparison between the best (Portuguese) and most challenging (Hindi) languages. Portuguese maintains strong performance even at fine-grained levels, while Hindi shows the characteristic challenges of low-resource language processing in nuanced classification tasks.	61
A.1	Combined performance across all languages for the no-validation configuration, showing F1 Coarse (narratives) and F1 Sample (subnarratives) metrics.	80
A.2	Bulgarian performance breakdown for no-validation configuration.	80
A.3	English performance breakdown for no-validation configuration.	81
A.4	Hindi performance breakdown for no-validation configuration.	81
A.5	Portuguese performance breakdown for no-validation configuration.	82
A.6	Russian performance breakdown for no-validation configuration.	82

List of Figures

A.7	Combined performance across all languages for the narrative-validation configuration.	83
A.8	English performance breakdown for narrative-validation configuration, representative of per-language patterns.	84
A.9	Combined performance across all languages for the subnarrative-validation configuration.	85
A.10	English performance breakdown for subnarrative-validation configuration, representative of per-language patterns.	86

List of Tables

6.1	Performance comparison across different classification thresholds. The training threshold (0.65) serves as the baseline for comparison.	44
6.2	Language-specific performance using optimal thresholds (0.65 for narratives, 0.7 for subnarratives F1 Macro).	47
6.3	Top 8 performing narrative categories at threshold 0.65, ranked by F1 score. .	49
6.4	Performance of the Zero-Shot Agentic Framework on the English test set, compared to the official random baseline.	51
6.5	Multilingual performance comparison. The “translate-to-English” strategy results in a notable drop in performance.	52
6.6	Comprehensive ablation study of actor-critique pipeline validation configurations across multilingual development set (178 documents). Results show F1 Coarse (narratives) and F1 Sample (subnarratives) for three validation strategies.	56
6.7	Performance comparison between Architecture 1 (AutoGen) and Architecture 2 (Actor-Critique, no validation) across languages. Architecture 2 shows substantial improvements, particularly in multilingual settings.	64
6.8	INSALyon2 official rankings in SemEval-2025 Task 10 Subtask 2 across all languages. Rankings reflect performance on the official test set using our Actor-Critique architecture (no validation configuration).	66

1 Introduction

1.1 Motivation

Text Classification (TC) is a foundational task in Natural Language Processing (NLP) [Zan+24]. While early work often framed TC as a multiclass problem, modern texts regularly contain multiple overlapping themes [Hu+25; TS18]. This motivates Multi-Label Classification (MLC), where instances can be assigned multiple labels simultaneously [TS18]. Beyond mere multiplicity, labels are frequently correlated [TS18; Hua+24], so modeling inter-label dependencies is crucial.

A particularly compelling setting is hierarchical multi-label classification (HMLC), where labels are arranged in a predefined hierarchy (e.g., tree or DAG) from coarse to fine categories [Liu+23]. This structure matches how humans reason about complex discourse. In the high-stakes context of online news and crisis communication, identifying nested narratives is both socially relevant and technically challenging. As a further motivation, this work aims to rigorously evaluate the classification capabilities of large language models (LLMs) on a difficult, nuanced HMLC task—one that requires fine-grained distinctions, hierarchical consistency, and evidence-grounded reasoning rather than shallow keyword matching.

1.2 Problem Definition

We ground our study in SemEval-2025 Task 10, Subtask 2 [Pis+25], a hierarchical narrative detection task for news. The objective is to assign each document multiple labels from a two-level taxonomy of narratives and subnarratives, i.e., mapping a text to a set of (narrative, subnarrative) pairs. The task features: (i) extreme class imbalance; (ii) hierarchical consistency constraints; and (iii) multilingual complexities. Formally, the MLC problem seeks to construct a function $f : X \rightarrow 2^L$ that maps an instance $x \in X$ to a subset $Y \subseteq L$, where L is the finite

label set [TS18]. This function may be learned through supervised training or constructed via other means (e.g., zero-shot prompting). HMLC adds the requirement that predicted labels respect the hierarchical structure [Liu+23].

1.3 Related Work

Research in multi-label classification has progressed from early problem-transformation methods (Binary Relevance, Classifier Chains, Label Powerset) [Zha+18b; Wen+20; Sha+18] to Transformer-based models that learn contextual correlations [Dev+19] and then to hierarchy-aware architectures incorporating structure through specialized losses or graph formulations [SC22; Pen+21; Gon+20; Liu+23]. Yet in settings that are simultaneously long-tailed, multilingual, and hierarchically constrained, supervised approaches remain brittle: they overfit head labels, struggle with rare-node calibration, propagate errors top-down, and provide limited transparency about individual decisions. Recent zero-shot and agentic LLM approaches [SSB25c; SSB25a] reduce dependence on labeled data, but introduce new gaps in traceability, cost efficiency, and consistent enforcement of hierarchical constraints (true-path validity, evidence grounding). This trajectory motivates our contributions: systematically contrasting a strong supervised baseline with two zero-shot architectural paradigms while explicitly targeting the unresolved challenges of (i) long-tail robustness, (ii) native multilingual operation without translation-induced semantic loss, and (iii) auditable, evidence-grounded reasoning.

1.4 Our Contributions

We make the following contributions in the context of HMLC for narrative detection:

- We introduce a zero-shot agentic framework that decomposes narrative detection into specialized binary decisions handled by LLM agents, achieving competitive performance without task-specific fine-tuning.
- We propose a configurable, traceable actor - critic pipeline that augments the agentic approach with explicit evidence extraction and validation, improving robustness and interpretability.

1 Introduction

- We provide a comparative analysis of three paradigms: a fine-tuned Transformer baseline, the agentic framework, and the actor - critic pipeline, highlighting trade-offs in accuracy, traceability, and cost.
- We conduct an in-depth error analysis on SemEval-2025 data, elucidating the roles of class imbalance, semantic ambiguity, and hierarchical constraints in model failures.

Paper outline. The remainder of this paper presents task and data analysis, details the system architectures, reports experiments and ablations, and concludes with discussion and future directions.

2 Related Work

2.1 Foundational paradigms of MLC

The main challenge in multi-label classification (MLC) was how to adapt algorithms designed for single-label (binary or multiclass) problems to handle multiple labels per instance. The core issue these methods faced was the presence of label correlations: in real-world data, labels are often not independent. For example, a news article tagged "Politics" is much more likely to also be tagged "Elections" than "Sports." Treating each label as a separate binary problem ignores these dependencies, potentially leading to suboptimal predictions.

Classical MLC methods can be seen as different strategies for balancing computational simplicity with the need to model label correlations. Some methods, like Binary Relevance, treat each label independently for simplicity, but this can miss important relationships between labels. Others, such as Classifier Chains or Label Powerset, explicitly model these correlations, but at the cost of increased computational complexity. The choice of method reflects a trade-off between efficiency and the ability to capture the true structure of the data.

2.1.1 Binary Relevance

Binary Relevance (BR) is the most intuitive approach. It decomposes the MLC problem with a label set of size $|\mathcal{L}|$ into independent binary classification problems. For each label, a separate classifier is trained to predict its presence or absence, effectively ignoring all other labels. [Zha+18b] The primary advantage of BR is its simplicity and efficiency, as the classifiers can be trained in parallel. Its main drawback, however, is the foundational label independence assumption, which completely disregards label correlations and can lead to lower predictive accuracy and logically incoherent label set predictions. [Suc+14]

2.1.2 Label Powerset

In contrast to compositional methods, the Label Powerset (LP) method reframes the entire problem at once. It converts the multi-label task into a standard multi-class problem by mapping each distinct set of co-occurring labels to a single, unique class. For instance, the label sets ‘Politics, Elections’ and ‘Sports, Weather’ would become two separate classes for a multi-class classifier to learn. [Rea+11]

The main advantage of this approach is its ability to perfectly model the dependencies between labels for all combinations it has seen, as these correlations are baked into the class definitions [Suc+14]. However, this strategy is often impractical. The number of potential classes can become unmanageably large as the label set grows, a problem known as combinatorial explosion. This leads to a highly sparse class distribution where many label sets appear only a few times, making it difficult to train a robust model [CMM11]. Critically, the LP method cannot generalize to predict any combination of labels that did not appear in the training data.

2.1.3 Classifier Chains

The Classifier Chains (CC) method was proposed as a novel approach to overcome the stark trade-off between the label-independent BR and the computationally explosive LP. It seeks to model label dependencies while maintaining the efficiency of a binary relevance framework [Rea+11].

Like BR, CC trains $|\mathcal{L}|$ binary classifiers. However, instead of being independent, these classifiers are linked in a chain. The first classifier in the chain, $\mathcal{C}_1$, predicts the presence or absence of the first label. The predictions of this classifier are then used as additional features for the second classifier, $\mathcal{C}_2$, which predicts the second label. This process continues down the chain, with each classifier potentially benefiting from the predictions of all previous classifiers. This allows CC to capture label dependencies while still being relatively efficient to train. [Rea+11] The order of the chain can significantly impact performance, as earlier classifiers influence later ones [Rea+21]. To mitigate this, ensemble methods that average predictions over multiple random chain orders are often employed [Suc+14; Zha+18a].

2.2 Hierarchy aware architectures

The limitations inherent in classical problem transformation methods, particularly their struggles with large label spaces and their inability to deeply integrate structural information, precipitated a paradigm shift toward deep learning. We will focus on how neural architectures evolved from treating the label hierarchy as a post-hoc constraint to using it as a central component of the learning process. This evolution is characterized by a fundamental architectural divergence between local and global approaches, a conflict that was ultimately resolved through the powerful synthesis of Transformer-based text encoders and Graph Neural Networks (GNNs) for structure encoding.

2.2.1 From flat to hierarchical models

Early deep-learning methods for hierarchical multi-label classification often treated the task as a standard (flat) multi-label problem and ignored the label taxonomy. While these models learned strong text representations, they did not use the hierarchy's relationships. That matters because mistakes at higher levels of the taxonomy are semantically worse than small, nearby errors: for example, assigning a paper on "Quantum Mechanics" to "Arts" is much more serious than confusing "Physics" with "Chemistry." Flat models cannot distinguish these degrees of error. [Xu+21]

The paradigm shift occurred with the recognition that the hierarchy could be treated as a feature to guide learning, rather than just an output format. By making models "hierarchy-aware," it becomes possible to share statistical strength between parent and child nodes. For example, the few training instances available for a rare, specific label like "Superstring Theory" can be supplemented by the more abundant data from its parent labels, "String Theory" and "Theoretical Physics." This is especially crucial for improving performance on the long tail of infrequent labels that characterizes most real-world HMLC datasets. [Zan+24]

2.2.2 Local vs global approaches

The first generation of truly hierarchical models diverged into two main architectural philosophies: local and global. This division reflects a fundamental trade-off between capturing

fine-grained, localized class relationships and maintaining a holistic, computationally tractable view of the entire label space.

2.2.3 Local approaches (Top down)

The local approach decomposes the hierarchical classification problem into a set of smaller, more manageable classification tasks distributed across the taxonomy. This is typically implemented as a top-down or "divide and conquer" strategy.

During inference, an instance is typically classified in a top-down manner. It is first evaluated by the classifier at the root; if a positive prediction is made for a node, the instance is then passed down to the classifiers of its children, and this process continues until a leaf node is reached or no further positive predictions are made. [RFR22]. While this approach excels at capturing the specific features that distinguish between closely related sibling classes, it suffers from a critical problem: **error propagation**. A single misclassification at a higher level of the hierarchy can irreversibly steer the prediction down an incorrect path, making it impossible to classify the instance into its correct, more specific sub-categories. [WCB18]

2.2.4 Global approaches (single classifier)

In contrast, the global approach uses a single, unified model to predict all labels in the hierarchy simultaneously. This is typically framed as a large multi-label classification problem where the output layer corresponds to the entire set of labels in the taxonomy. [WCB18]

The primary advantage of the global approach is that it inherently avoids the error propagation problem of local models, as all decisions are made in parallel by a single classifier. This makes the model more robust to errors at higher levels. Furthermore, global models are often more computationally efficient, as they require training only one model instead of a potentially large cascade of local classifiers. However, early global models faced a significant challenge: they struggled to effectively incorporate the complex structural information of the entire hierarchy into a single model. By treating the problem as a flat multi-label task, they often failed to capture the nuanced, local distinctions between sibling classes and could underfit the hierarchical relationships, thereby losing the very information that hierarchical classification aims to exploit. [WCB18; Zho+20]

2.2.5 Encoding the Hierarchy with Transformers and Graph Neural Networks

The solution to the local-versus-global problem came from combining two methods: Transformer models to understand text, and Graph Neural Networks (GNNs) to understand structure. This mix made it possible to build global models that are both efficient and aware of hierarchies. [WDH24; Zho+20]

GNNs are especially useful for working with label hierarchies. [Li+21] We can represent the taxonomy as a graph, where labels are nodes and parent-child links are edges. A GNN learns label representations by passing messages between connected nodes. Each node gathers information from its parents, children, and siblings. This way, the final label embeddings capture not just their own meaning, but also their place and relationships within the whole taxonomy.

A seminal work in this domain is the Hierarchy-Aware Global Model (HiAGM) by Zhou et al. (2020). HiAGM provides a blueprint for this new class of models. Its architecture consists of two main components: [Zho+20]

- A Text Encoder (e.g., BERT, RoBERTa) that generates a powerful contextualized representation of the input document.
- A Hierarchy-Aware Structure Encoder (e.g., a Bidirectional Tree-LSTM or a specialized Hierarchy-GCN) that operates on the label graph to produce hierarchy-aware label embeddings. This encoder models dependencies in both a top-down and bottom-up fashion, allowing information to flow in both directions across the hierarchy.

HiAGM further proposes two distinct fusion variants to combine text and structure features depending on the inference regime and efficiency/inductivity trade-offs.

HiAGM-LA (Multi-Label Attention) An inductive approach that uses a multi-label attention mechanism to compute document-specific label representations by attending from the text encoder outputs to the hierarchy-aware label embeddings. Because the attention weights are computed per document, the model can generalize to unseen instances without explicitly re-running a graph propagation step for each input, label embeddings can be pre-computed and stored, and the attention operation is applied at inference time.

HiAGM-TP (Text Feature Propagation) A deductive approach that propagates text features across the label hierarchy via graph propagation: document features are attached to label nodes and a GNN is run to diffuse these features through the taxonomy. This requires executing the GNN at inference time for each instance (or batch), which can be more computationally expensive but allows richer instance-specific propagation of evidence through the hierarchy.

The principles demonstrated by HiAGM have been extended and refined in subsequent work. For instance, Xu et al. (2021) proposed a framework using a loosely coupled GCN to explicitly model not only the vertical correlations (parent-child dependencies) but also the horizontal correlations (relationships between sibling nodes at the same level). This allows the model to capture, for example, that "Computer Science" and "Electrical Engineering" are more closely related to each other than to "History," even if they share the same parent 'Science & Technology'.

2.3 The rise of Large Language Models

The advent of Large Language Models (LLMs) has initiated another profound shift in the NLP landscape. Their advanced reasoning and generation capabilities are redefining their role in the HMLC pipeline, moving them beyond being simple end-point classifiers to becoming integral co-pilots in various stages of the workflow.

2.3.1 Zero shot and few-shot classification

The most immediate impact of LLMs is their remarkable ability to perform classification tasks with little to no task-specific training data. Through in-context learning, an LLM can be prompted with a task description and a few examples (few-shot) or even no examples (zero-shot) and perform hierarchical multi-label classification. This capability represents a paradigm shift for low-resource scenarios, potentially obviating the need for extensive data collection and annotation efforts; for narrative detection, one can provide definitions of the target narratives and ask the LLM to classify a new document accordingly. [Wan+23]

For instance, Eljadiri and Nurbakova (2025) demonstrate a high-performing zero-shot agentic approach to narrative classification. Their system instantiates multiple specialized LLM agents, each responsible for a binary decision on a single narrative or subnarrative label, while a

meta-agent aggregates the binary outputs into final multi-label predictions. The agents are orchestrated with AutoGen and operate without task-specific fine-tuning, which enables parallel detection across the two-level taxonomy; this design yielded competitive results on the SemEval-2025 test set and highlights the practical zero-shot LLM systems for complex hierarchical tasks. [EN25]

2.3.2 LLMs for data augmentation

One of the most promising applications of LLMs is in addressing data scarcity and class imbalance through synthetic data generation. An LLM can be prompted to act as a domain expert and generate new text samples for underrepresented (tail) classes. This can be done by paraphrasing existing examples to increase diversity or by generating entirely new, plausible examples from scratch. This approach offers a sophisticated and flexible alternative to traditional data augmentation techniques like synonym replacement or back-translation. [CSB25; GZ24]

In more extreme cases; for example, a scenario with complete lack of labeled data, an LLM can be used to generate a large corpus of "weak" or "silver" labels. These labels, while imperfect, can serve as a starting point for training a smaller, more efficient model. Frameworks like JS DRV by Yang et al. (2024) take this a step further, using a reinforcement learning policy to select the highest-quality LLM-generated annotations for fine-tuning, creating a self-improving annotation and training pipeline [Yan+24].

2.3.3 LLMs as evaluation assistants

For extreme multi-label classification tasks with thousands of labels, manual evaluation is prohibitively expensive and time-consuming. Li et al. (2023) aimed to compare a label-ranking BiCross-Encoder against a SciBERT classifier in a very large-label setting (11,486 labels) while lacking a ready human-annotated test set. They demonstrated a practical approach by asking ChatGPT to rate the relevance of candidate labels: for each document they fed the top-10 model-predicted labels to ChatGPT and requested a 3-point relevance score (0 = irrelevant, 1 = somewhat relevant, 2 = highly relevant) along with brief explanations. The authors treated these LLM judgments as automatic annotations to compare models, then spot-checked a sample with subject-matter experts and reported about 60% agreement on the 3-point scale (rising to 82% when collapsing 1 and 2 into a single "relevant" class). They conclude that using

ChatGPT as an evaluation assistant is a cost- and time-efficient way to bootstrap evaluation when comprehensive human annotation is infeasible. [Li+23]

2.4 Focus on data-specific challenges

While architectural innovations have driven significant progress, the performance of any HMLC model is ultimately constrained by the quality and characteristics of the available data. Real-world datasets for narrative detection and other complex classification tasks are rarely pristine; they are often imbalanced, small, and increasingly, multilingual.

2.4.1 Class imbalance and tail labels

Perhaps the most pervasive challenge in real-world classification is extreme class imbalance, often described as a long-tailed distribution. In such datasets, a small number of "head" classes are represented by a vast number of training examples, while the majority of "tail" classes are represented by very few, sometimes single-digit, examples. [Hua+21] This constitutes a severe challenge for standard training algorithms, which, when optimized for overall accuracy, tend to become biased towards the majority classes and perform poorly on the infrequent but often more interesting tail classes.

The inadequacy of conventional resampling

In single-label classification, a common strategy to combat imbalance is data resampling, either oversampling the minority classes or undersampling the majority classes [Luq+19; Tha+20]. However, this approach is fundamentally ill-suited for the multi-label context. An instance in an MLC dataset can simultaneously belong to multiple classes, for example, one highly frequent head class and one extremely rare tail class. If one were to oversample this instance to increase the representation of the tail class, one would inadvertently also increase the representation of the already-dominant head class, potentially exacerbating the overall imbalance with respect to other labels. This entanglement makes simple resampling ineffective and often counterproductive. [Yua+24]

A particularly effective technique that has been instantiated is the distribution-based loss function. As demonstrated by Huang et al. (2021), this approach goes beyond simple re-weighting by

class frequency. It introduces a loss formulation that inherently addresses both the class imbalance and the label linkage (co-occurrence) problems simultaneously. The re-weighting scheme is designed to account for the fact that an instance with multiple labels can be oversampled if each of its labels is treated independently [Hua+21].

2.4.2 Strategies for low resource and few-shot scenarios

When unlabeled data is abundant but labeling is expensive, active learning provides a principled way to build a high-quality training set with minimal human effort [Li+23]. Instead of randomly selecting data for annotation, an active learning system iteratively queries a human oracle (e.g., a domain expert) to label the instances that the model is most uncertain about or that are expected to provide the most information for improving the model. For XMC, Li et al. (2023) propose a sophisticated active learning pipeline that uses a Bi-Encoder model to first retrieve a manageable pool of potentially relevant documents for new, unlabeled classes. A greedy acquisition strategy then selects the most promising candidates from this pool for expert annotation, drastically reducing the labeling burden compared to annotating the entire corpus.[Li+24]

2.4.3 Parameter-efficient fine-tuning for low-resource adaptation

Fully fine-tuning a large PLM with billions of parameters on a small dataset is not only computationally expensive but also prone to overfitting. Parameter-Efficient Fine-Tuning (PEFT) methods have emerged as a critical technology for low-resource adaptation. [Su+24] Techniques like Adapters and Low-Rank Adaptation (LoRA) work by freezing the vast majority of the pre-trained model’s weights and introducing a very small number of new, trainable parameters. LoRA, for example, injects trainable low-rank matrices into the layers of the Transformer, allowing the model to adapt to the new task by learning low-rank updates to its original weight matrices. By drastically reducing the number of trainable parameters (often by over 99%), PEFT makes the fine-tuning process more stable on small datasets, reduces memory requirements, and helps prevent catastrophic forgetting of the knowledge learned during pre-training. [Liu+24; Raz+24]

2.4.4 Data augmentation with LLMs

As discussed in Section 2.3.2, LLMs can serve as powerful data generators. For low-resource classes, an LLM can be prompted to create synthetic training examples by paraphrasing the few existing seed examples or by generating novel instances based on a class description. A cost-benefit analysis by Cegin et al. (2025) reveals that this approach provides the most significant advantage when the number of initial seed examples is extremely small (e.g., one-shot or few-shot learning) [CSB25]. As the amount of available data increases, the performance gains from LLM augmentation may diminish relative to its computational cost, and in some cases, traditional augmentation techniques can achieve comparable results more efficiently. [CSB25]

Concrete evidence of these trade-offs is provided by Whitehouse et al. (2023) [WCA23], who systematically investigate LLM-powered augmentation for multilingual commonsense reasoning. The authors use a variety of LLMs (Dollyv2, StableVicuna, ChatGPT and GPT4) to generate synthetic training examples for three low-resource benchmarks (XCOPA, XWinograd and XStoryCloze). They compare generation strategies, producing data directly in the target language, generating in English and translating the output, and using English-generated data as-is, and then fine-tune compact multilingual models (mBERT and XLMRoBERTa) on the augmented corpora.

Their results show that augmenting scarce training sets with high-quality LLM generations can substantially improve downstream accuracy (up to a 13.4point increase in the best case). GPT4 and ChatGPT produce the most natural and logically coherent examples in most languages, with GPT4 often yielding the largest gains; smaller/open models (Dollyv2, StableVicuna) deliver weaker, less consistent improvements. The authors also perform a human evaluation: native speakers rate the naturalness and logical coherence of generated examples, confirming GPT-4’s superior quality but revealing languagedependent failures (notably for some lowresource languages such as Tamil). Overall, the study demonstrates that LLMs are a practical and powerful source of synthetic data for crosslingual commonsense tasks when reliable generation is available, while also highlighting limitations in coverage and the need for quality control.

2.5 Case Study: The Evolution of Narrative and Propaganda Detection

The field of automated narrative and propaganda detection serves as an ideal case study, illustrating the practical application and evolution of the very techniques discussed in this survey. This domain has acted as a methodological crucible, progressing from standard classification to sophisticated, multilingual, and hierarchical analysis, with the premier NLP benchmarking venue, SemEval, providing a clear chronological roadmap of the state-of-the-art.

2.5.1 From Flat Classification to Structural Priors

The initial wave of research was benchmarked by SemEval-2020 Task 11, which framed propaganda detection as a flat multi-class classification problem with 14 techniques [Da+20]. The results unequivocally established the dominance of fine-tuned Transformer-based architectures like RoBERTa. However, top systems rarely used these models off-the-shelf. For identifying propagandistic text spans, a sequence tagging sub-task, the most effective architecture was a RoBERTa model augmented with a Conditional Random Field (CRF) layer, which adds a structural constraint by modeling dependencies between adjacent labels [CIN20; Jur+20]. For the technique classification sub-task, the winning solutions relied on large ensembles of RoBERTa models to improve robustness and accuracy [Jur+20].

Subsequent research sought to improve performance by injecting deeper linguistic knowledge, moving beyond surface-level features. A landmark contribution was the discourse-aware Transformer architecture proposed by Chernyavskiy et al. (2024), which integrates features from Rhetorical Structure Theory (RST) [CIN24]. By providing the model with explicit information about discourse units (EDUs), their salience (Nucleus vs. Satellite), and their relationships, the model gained a stronger inductive bias. Experiments showed that propaganda was most frequently located in the 'Nucleus' EDUs—the core parts of a message. This work provides compelling evidence that incorporating structural linguistic priors is a powerful method for enhancing models for persuasive language analysis, particularly in low-resource settings where such structures cannot be learned from data alone.

2.5.2 The Hierarchical and Multilingual Turn in SemEval

The challenges of multilinguality, data imbalance, and hierarchical classification, which are central to modern HMLC, were addressed progressively in subsequent SemEval shared tasks.

SemEval-2023 Task 3 dramatically expanded the scope to nine languages and 23 persuasion techniques [Da+23]. This pivot forced a move from English-centric models to multilingual encoders like XLM-RoBERTa. The winning strategies provided a clear blueprint for low-resource multilingual classification: 1) joint training on data from all languages to learn shared cross-lingual representations, and 2) aggressive data augmentation via machine translation, where examples from high-resource languages are translated to bolster the training sets of low-resource ones [Hro+23; Mod+23].

SemEval-2024 Task 4 marked the formal introduction of hierarchy, reframing persuasion detection as an HMLC problem with 22 techniques organized in a Directed Acyclic Graph (DAG) [Dim+24]. This task spurred the development of novel hierarchy-aware architectures, with top systems showcasing three distinct state-of-the-art approaches:

- **Direct HTC Modeling:** Adapting dedicated Hierarchical Text Classification models like HPT, which required pre-processing the label DAG into a strict tree structure [GA24].
- **Architectural Priors:** Designing a custom hierarchical classification head on top of an LLM backbone. This head mirrors the label hierarchy with structured layers, forcing predictions to be made in a top-down, consistent manner [Wun+24]. This is a direct implementation of the local, top-down approach discussed in Section ??.
- **Representation Learning:** Employing hyperbolic embeddings to project text and label representations into a non-Euclidean space whose geometry naturally mirrors a tree-like structure, allowing the model to implicitly learn hierarchical relationships [CMM24].

Finally, **SemEval-2025 Task 10** represents the culmination of this trend, establishing multilingual narrative classification as a formal shared task with a two-level hierarchical taxonomy [Pis+25]. Early systems already demonstrate the application of advanced techniques like retrieval-based methods and hierarchical prompting with LLMs [YQ25; SSB25b]. This clear evolutionary trajectory within a major NLP benchmark provides an exceptionally strong justification for research into HMLC for narrative detection, as it confirms that this problem is the logical and timely next step for the research community.

2 *Related Work*

In summary, the field has progressed from classical HMLC methods to sophisticated hierarchy-aware deep learning models. While recent work in the SemEval-2025 shared task has highlighted the promise of LLM-based prompting, these approaches often rely on monolithic, multi-step prompts. This paper explores a different paradigm: decomposing the HMLC task into a system of independent, specialized agents. We investigate both a parallel agentic framework and a novel actor-critic pipeline designed for enhanced traceability, directly addressing the need for more modular and reliable systems in zero-shot narrative classification.

3 Task and Data Analysis

3.1 Task description

3.1.1 SemEval2025 Task 10: Overview

SemEval-2025 Task 10 introduced a multilingual benchmark for the analysis of news narratives and entity framing across five languages and two high-impact domains (Ukraine–Russia War, Climate Change). The task is decomposed into entity framing, narrative classification, and narrative extraction subtasks, combining multi-label classification and evidence-grounded generation. Participating teams demonstrated the effectiveness of hierarchical prompting and targeted context selection; however, grounded explanation generation and label imbalance across languages remain unsolved challenges [PM25; Fan+25; SSB25a; F25].

We participated in this shared task (together with Diana Nurbakova) as competitors in Subtask 2 (Narrative Classification); the experiments reported here were carried out in that shared-task context.

This shared task asked teams to build systems that identify and extract dominant narratives from multilingual news, prioritising evidence-grounded explanations and robustness across languages. We ran multilingual evaluations to compare per-language behaviour.

3.1.2 Task decomposition

The shared task was split into three subtasks:

1. **Entity Framing (Subtask 1):** Given an article and named-entity mentions, assign main and fine-grained role labels to each mention (multi-label, multi-class role classification). Grounding to spans and role taxonomies was required. [PM25]

2. **Narrative Classification (Subtask 2):** Assign articles one or more narrative labels from a two-level taxonomy (main narrative → subnarrative). This is a multilingual multi-label document classification problem. [PM25]
3. **Narrative Extraction (Subtask 3):** For a given article and its dominant narrative, generate a concise (max. 80 words) free-text explanation supporting that narrative, grounded in evidence from the article. This subtask focused on faithfulness and coverage of extracted explanations. [PM25]

3.1.3 Data and annotation

Training and evaluation data were collected from online news sources spanning 2022-mid-2024. The dataset includes articles from a mix of mainstream and lower-credibility outlets; annotations follow multilingual guidelines and predefined taxonomies for entity roles and narratives. [Sem25b]

3.1.4 Participation and headline results

The task attracted broad participation; hundreds of teams registered and dozens submitted official test results. Representative high-performing approaches included:

- **Fane et al. (“Fane”)** - zero-shot LLM prompting with a hierarchical decomposition for entity framing; reported Main Role Accuracy $\approx 89.4\%$ and Exact Match Ratio $\approx 34.5\%$ on English. [Fan+25]
- **GateNLP** - *Hierarchical Three-Step Prompting (H3Prompt)* for Subtask 2 (narrative classification): cascade of domain → main narrative → subnarrative prompting; top performer on the English test set among competing teams. Code published. [SSB25a]
- **DEMON / TechSSN / LTG / BERTastic** - representative competitive systems using fine-tuning of large pre-trained encoders (e.g., XLM-R / DeBERTa variants) or fine-tuned LLaMA-family models for framing and narrative tasks. Several system descriptions and official proceedings papers document model design choices and per-language performance differences. [F25; P25; RN25; Nak+25]

These system papers illustrate a common trend: hierarchical or multi-step prompting and careful context selection (to fit model context windows) were effective strategies across teams. [Fan+25; SSB25a; RN25]

3.1.5 Evaluation of Subtask 2: Narrative Classification

The second subtask of SemEval-2025 Task 10 required participants to assign *narrative* (coarse-level) and *sub-narrative* (fine-level) labels to each news article. Since articles can be associated with multiple narratives, this constitutes a multi-label, multi-class document classification problem [PM25].

Evaluation target. Participants had to provide two sets of predictions per article: (1) a set of coarse-level narrative labels and (2) a set of fine-grained sub-narrative labels. Although both levels were evaluated, the official ranking was based on performance at the sub-narrative level, as this captures more nuanced framing [Sem25b].

Metrics. Two main evaluation metrics were applied:

- **Macro F1 (coarse level).** This is the unweighted mean of F1-scores computed for each coarse narrative class. It penalizes models that ignore low-frequency labels.
- **F1 (samples).** This metric is computed at the level of individual articles. For each document, precision, recall, and F1 are computed by comparing the predicted label set with the gold label set. The final score is the average of these values across all documents.

In addition, standard deviations across multiple runs and across languages were reported on the leaderboard to quantify robustness [Sem25a].

Worked example. Consider a simplified case with three possible sub-narratives: $\{N_1, N_2, N_3\}$. Suppose the gold labels for a document are $\{N_1, N_3\}$, while a system predicts $\{N_1, N_2\}$.

- **Precision** = $\frac{|\{N_1, N_2\} \cap \{N_1, N_3\}|}{|\{N_1, N_2\}|} = \frac{1}{2} = 0.5$.
- **Recall** = $\frac{|\{N_1, N_2\} \cap \{N_1, N_3\}|}{|\{N_1, N_3\}|} = \frac{1}{2} = 0.5$.
- **F1 (sample)** = $\frac{2 \times 0.5 \times 0.5}{0.5 + 0.5} = 0.5$.

In contrast, if the system had predicted only $\{N_1\}$, precision would be 1.0, recall 0.5, and F1 (sample) 0.67. This illustrates that partial but precise predictions may yield a higher F1 than predicting extra incorrect labels.

Implications. Because the leaderboard ranks systems by fine-level labels using sample-based F1, models must balance recall (capturing all relevant sub-narratives) with precision (avoiding irrelevant ones). Macro F1 further incentivizes attention to rare narratives, since underperformance on them disproportionately lowers the score. [PM25].

3.2 Dataset Deep Dive

We conducted a systematic descriptive analysis of the released training split to quantify its distributional, linguistic, and structural properties. Our analysis reveals several key characteristics regarding its scale, multi-label nature, class imbalance, and co-occurrence structure, which collectively motivate our architectural design choices.

Scale and Multilinguality. The corpus contains 1,699 documents in five languages: Bulgarian (BG), Portuguese (PT), English (EN), Hindi (HI), and Russian (RU). The distribution is relatively balanced across Bulgarian, Portuguese, and English (≈ 399 – 401 documents each), with 366 Hindi documents and 133 Russian documents. This multilingual context is critical for assessing the cross-lingual generalization capabilities of classification models.

Multi-Label Nature. Building upon this multilingual foundation, a defining feature of the dataset is the high frequency of multi-label annotations. A majority of documents (54.0%) are assigned more than one narrative, with an average of 2.28 narrative labels per document and a maximum of 8. This observation confirms that multi-label modeling is essential; treating the task as a series of independent single-label classifications would discard significant structural information present in the data.

Label Frequency and Extreme Imbalance. The complexity of the multi-label structure is further compounded by severe class imbalance. The taxonomy consists of 22 distinct narrative labels and 95 sub-narrative labels, distributed in a strongly skewed manner. The most frequent narrative appears 584 times (representing $\approx 15.1\%$ of all narrative annotations in the multilingual training set), while the least frequent occurs only 9 times. This yields an imbalance ratio of approximately 65:1, creating a classic long-tailed distribution. Notably, the

is). In contrast, mDeBERTa’s disentangled attention uses two separate vectors for each token: one representing its content and another representing its relative position. Attention weights are then computed based on the interactions between the content and position vectors of different tokens [He+21].

The intuition for our task is as follows: Narrative classification often depends on understanding the relationships between specific keywords (content) and their structural arrangement within a sentence or paragraph (position). For example, the narrative “URW: Blaming the war on others rather than the invader” relies on identifying entities like “the West” or “Ukraine” (content) and their syntactic roles as agents or recipients of blame (a position-dependent relationship). By disentangling content from position, mDeBERTa can more explicitly model these types of syntactic and relational dependencies, which are crucial for distinguishing between semantically similar but structurally different narratives.

While this mechanism offers a principled advantage, we also approached this choice experimentally. A key goal of implementing this advanced baseline was to test the limits of the fine-tuning paradigm: if even a model with a sophisticated, disentangled attention mechanism fails to learn from the sparse data, it provides stronger evidence that the problem lies with the learning paradigm itself, not just the specific model architecture.

Anticipated limitations. Based on our data analysis, we anticipated that a vanilla approach to finetuning would face significant limitations. The primary concern is its susceptibility to the severe class imbalance. By optimizing for overall accuracy, the standard BCE loss incentivizes the model to achieve high performance on the high-frequency “head” classes, often by simply predicting “negative” for the vast majority of rare “tail” classes. This behavior is expected to result in poor performance on metrics sensitive to class imbalance, such as the macro-averaged F1 score, and serves as the primary motivation for the more advanced baselines and zero-shot architectures explored subsequently.

4.1.2 Mitigating the class imbalance

To directly address the class imbalance issue, we enhance the loss function with positive class weighting. This technique modifies the standard BCE loss by increasing the penalty for misclassifying a positive instance of a rare class. For each class c we compute a per-class

weight pos_weight_c as the ratio of negative to positive training counts. Let N_c and P_c denote the number of negative and positive training examples for class c , respectively:

$$\text{pos_weight}_c = \frac{N_c}{P_c}.$$

This weight is then integrated directly into the BCE loss calculation, effectively increasing the cost of a false negative for rare classes. For a common label where positive and negative samples are balanced, the weight is close to 1, behaving like the standard BCE loss. However, for a rare label with a **pos_weight** of, for example, 65, the loss incurred for failing to predict that label when it is present is magnified 65 times.

In practice we pass the vector of per-class positive weights to the BCEWithLogitsLoss (or equivalent) implementation so rare classes contribute proportionally more to the loss. The approach is intended to improve recall on tail classes and, consequently, boost Macro F1 by forcing the model to pay closer attention to underrepresented labels.

4.1.3 Hierarchical-Conditioned training and data handling

4.1.4 Training Methodology

Our multi-head mDeBERTa architecture employs a training and data handling strategy designed to address the challenges of hierarchical structure, class imbalance, and data scarcity.

Hierarchically-Conditioned Training. The effectiveness of our multi-head mDeBERTa architecture is realized through a specialized training methodology designed to enforce the taxonomy’s structure and combat the severe data imbalance. The total loss is a carefully calculated sum of losses from the parent-level classifier and the conditionally activated child-level heads.

Parent-Level Training. At the top level, the parent classifier is trained to predict the presence of all coarse-grained narratives. It is optimized using **Binary Cross-Entropy with Logits Loss** (BCEWithLogitsLoss). To counteract the significant class imbalance among parent narratives, we apply **positive class weighting**. For each parent label, a weight inversely

proportional to its frequency is computed, compelling the model to assign a higher penalty for misclassifying rare parent narratives.

Child-Level Conditional Training. The core of our hierarchical approach lies in the conditional training of the child-level heads. This process ensures that each specialized child classifier is trained exclusively on relevant data. For a given training document, the loss for a specific child-classifier head (for example, the head for URW: Discrediting Ukraine’s children) is calculated if and only if that document is labeled with the corresponding parent narrative. If the parent label is absent, the child head is “inactive” for that instance and contributes zero to the total loss. This conditional activation hard-codes the true-path rule into the training loop, preventing the child classifiers from being overwhelmed by the vast majority of documents where their parent narrative is not present.

A concrete example. Consider a document labeled with the parent narrative P_1 and its child sub-narrative C_{1a} . During the forward pass:

- The parent-level loss is calculated across all parent labels, with the model being rewarded for predicting P_1 as positive.
- The system checks the ground-truth labels. Since P_1 is present, the specific child-classifier head for P_1 ’s children is activated.
- The loss for this child head is calculated, rewarding the model for predicting C_{1a} as positive.
- All other child-classifier heads (for P_2 , P_3 , etc.) remain inactive for this document.

This focused training strategy allows each child head to become a highly specialized expert, learning the subtle distinctions between its sibling sub-narratives without being distracted by irrelevant data from other branches of the hierarchy.

Figure 4.1 provides a schematic overview of the Multi-Head mDeBERTa architecture and the conditional activation behaviour described above.

it directly in a multi-label framework can be problematic, as the model may struggle to learn a clear decision boundary for such a broad and negatively-defined category.

Methodology. To address this, we adopted a strategy of treating the “Other” class as an implicit negative case. We removed all instances labeled exclusively as “Other” from the training set. Consequently, the model was trained *only* on documents that contained at least one specific, defined narrative. During inference, this training strategy translates to a simple and effective decision rule: if the model, after applying a sigmoid activation and a confidence threshold, predicts **zero** positive labels for a given document, that document is then assigned the “Other” label.

Alternative (note).

We briefly considered treating “Other” as an explicit class and using the model’s predicted probability for it as an adaptive threshold (i.e., a candidate label must exceed the “Other” probability to be assigned). We leave this variant for future work.

Intended outcome. This approach simplifies the learning objective for the Transformer model. Instead of learning to positively identify the features of the “Other” class—a vague and potentially unbounded task—the model can focus entirely on learning the positive features of the defined narratives. This reframes the problem as learning to recognize “something” versus “nothing,” a much clearer and more constrained task intended to improve the precision of the defined narrative predictions.

4.2 Architecture 1: Zero-Shot Autogen Framework

4.2.1 Motivation and core concepts

While the enhanced baseline models are designed to mitigate the challenges of class imbalance and hierarchical inconsistency, they are fundamentally limited by the scarcity of training data for many labels (we remind that the train set contains 22 unique narratives, while the taxonomy defines 23). To overcome this dependency on large, labeled datasets, we explored a fundamentally different paradigm that shifts from learning from examples to reasoning from instructions. This led to the development of our first contribution: a zero-shot agentic

framework that leverages the pre-existing world knowledge and reasoning capabilities of Large Language Models (LLMs).

Inspiration Our design was inspired by the classical Binary Relevance (BR) method, which decomposes a multi-label problem into a set of independent binary classification tasks [Zha+18b]. BR’s primary strength is its simplicity and modularity, but its critical weakness is the assumption of label independence. We sought to create a system that retained the modularity of BR while re-introducing a notion of label relationships in a structured, hierarchical manner. Furthermore, we were motivated to investigate the zero-shot classification capabilities of modern LLMs on this task.

To implement this vision, we used AutoGen [Wu+24], an open-source framework for multi-agent LLM conversations. AutoGen allows users to define multiple agents with specific roles and manages the conversation flow between them. In our case, we created one agent for each narrative label and used AutoGen to coordinate their interactions during the classification process.

The core concept of our framework, first introduced in [EN25], is to decompose the HMLC task into a two-stage, hierarchical query process handled by a multi-agent system.

4.2.2 System components and architecture

Agentic multi-agent framework

The agentic framework is constructed from a set of conversational agents, each instantiated as an LLM with a narrowly defined role and area of expertise. Our architecture comprises three distinct agent types:

- **User Proxy Agent.** The primary interface to the system. It receives a document for classification from an external user and initiates the workflow by passing the text to the Manager Agent. This is an AutoGen specific requirement to bootstrap the conversation.
- **Manager Agent (Orchestrator).** The central coordinator that directs the classification process. The Manager selects which agents to query at each stage, manages conversational group chats, and aggregates the final predictions into a structured multi-label output.

Our prompt engineering strategy was therefore meticulously designed to elicit high-precision, reliable, and parsable classifications from the LLM.

Template structure and key components Each agent, whether at the narrative or sub-narrative level, was initialized with a system prompt constructed from a consistent template. This template incorporated several key components to focus the agent’s reasoning:

- **Role-Playing:** The prompt begins by assigning the LLM a clear and narrow role: “You are a highly specialized classification model. Your only task is to perform binary classification...” This instruction immediately constrains the model’s behavior, discouraging it from generating conversational or explanatory text.
- **Task Definition:** The core of the prompt provides the necessary domain knowledge by embedding the exact name and official definition of the agent’s assigned label, sourced directly from the SemEval-2025 taxonomy. This ensures each agent is an “expert” on its specific narrative.
- **Strict Output Formatting:** To ensure the system could function deterministically, the prompt strictly enforces the output format. Agents were explicitly instructed to respond only with the character 1 (if the narrative is present) or 0 (if absent), and to refrain from producing any other text.

Precision-oriented instructions Perhaps the most crucial element of our prompt design was an instruction engineered to prioritize precision over recall. LLMs often exhibit a tendency to be “overly helpful,” identifying weak or tangential relationships that can lead to false positives. To counteract this, we included a direct and unambiguous command:

“Only answer with 1 if there are EXPLICIT and CLEAR mentions of the narrative in the text. Some text will be ambiguous, so if you are slightly unsure, answer 0.”

This conservative instruction forces the agent to adopt a high-confidence threshold for positive classifications. It is a cornerstone of our framework’s design, aimed at minimizing false positives in a large and complex label space.

Historical context and refinement challenges It is worth noting that this architecture was developed before LLMs were systematically trained to produce structured output formats. Consequently, we had to refine our prompting strategy extensively to obtain consistently parsable answers. Early iterations often produced verbose explanations or inconsistent formatting, requiring multiple rounds of prompt optimization to achieve the deterministic binary outputs necessary for automated processing.

The full, verbatim prompt template used to initialize the agents is provided in Appendix A for reproducibility.

4.3 Architecture 2: The Traceable Actor-Critique Pipeline

4.3.1 Motivation: From Decomposed Agents to Holistic, Reasoned Analysis

While the zero-shot agentic framework (**Architecture 1**) effectively addresses data scarcity by decomposing the classification task, its reliability depends on the opaque internal reasoning of individual agents. The binary 1/0 outputs lack transparency, making the system difficult to audit and susceptible to unverified hallucinations.

To overcome these limitations, we developed a traceable, multi-stage pipeline that prioritizes two design goals:

- **Efficiency.** Replace dozens of individual agent calls with a single, batched request per hierarchical level to reduce latency and operational cost.
- **Reasoning depth.** Move from isolated binary decisions to holistic, evidence-grounded analysis where a single agent considers all candidate labels and produces structured, auditable claims.

Together, these goals shift the task from simple classification to **evidence-grounded claim generation and validation**, improving both interpretability and trustworthiness.

4.3.2 Pipeline architecture

Our implementation uses the LangGraph framework to structure the classification process as a cyclical state graph [Lan24a]. In this approach, each processing step represents a node that operates on a shared state object. The pipeline configuration is managed by a Configurable-GraphBuilder class, which constructs the workflow based on parameters specified in a YAML configuration file. This structure allows individual components such as validation and cleaning steps to be enabled or disabled as needed, and permits different language models to be assigned to specific nodes within the graph.

4.3.3 Sequential workflow and processing stages

The classification of a document proceeds through a series of sequential and conditional stages, as illustrated in Figure 4.3.

Stage 1: (Optional) Text Cleaning The pipeline can be configured to begin with an LLM-powered cleaning node. This node processes the raw input text to remove web-specific artifacts and boilerplate, ensuring that subsequent stages operate on high-quality, content-focused prose.

Stage 2: Category Classification The workflow begins with a simple classifier node that determines the document’s high-level topic (e.g., CC or URW). This initial routing step allows the system to load the relevant subset of the narrative taxonomy, focusing the subsequent, more computationally expensive stages on a smaller, more relevant set of potential labels.

Stage 3: The Narrative Actor (Claim Generation) This is the first core component of the actor-critic design. The “Actor” is an LLM agent prompted to act as an expert analyst. Its task is not merely to classify but to generate a structured set of claims. For each narrative it identifies in the text, it must produce a JSON object containing three key fields, enforced by a Pydantic schema:

- **narrative_name:** The exact name of the identified narrative.
- **evidence_quote:** A direct, verbatim quote from the text that supports the claim.
- **reasoning:** A brief justification explaining how the quote supports the narrative.

3. **Subnarrative-Only Validation:** Narrative Actor outputs are accepted as-is; only subnarrative claims pass through a Critic (useful for measuring whether fine-grained validation alone yields gains).

This design clarifies why the results table (Table 6.6) lists the three configurations as alternatives: each run toggles at most one validation level to quantify its isolated contribution.

4.3.4 Key advantages of the evidence-grounded pipeline

This evidence-grounded, pipeline-driven architecture offers several significant advantages over simpler classification models:

Traceability and Auditability By forcing the Actor to ground every prediction in a textual `evidence_quote`, the system’s reasoning becomes fully transparent. This is a critical feature for real-world applications where understanding the “why” behind a classification is as important as the classification itself, especially when using LLM chains. To further enhance this, we integrated LangSmith [Lan24b] into our development workflow. LangSmith provided detailed, step-by-step traces of each agent’s inputs, outputs, and internal reasoning. This fine-grained visibility was invaluable for debugging complex interactions within the graph and, most importantly, for iteratively refining our prompts. By analyzing the exact failure modes identified in the traces, we could make targeted improvements to the prompt templates, significantly accelerating the development of a robust and reliable system.

Reliability and Reduced Hallucination The Critic acts as a powerful safeguard against low-confidence predictions and LLM hallucinations. The explicit validation step, combined with the self-correction feedback loop, significantly increases the precision and trustworthiness of the final output.

Efficiency through Parallelization By replacing the “one agent per label” model with a single reasoning agent per hierarchical level and leveraging asynchronous batch processing for the sub-narrative stage, the system dramatically reduces the number of sequential LLM calls. This yields a substantial improvement in processing speed and throughput while preserving the benefits of evidence-grounded validation and iterative refinement.

Modularity and Configurability The entire pipeline is controlled by a YAML configuration file. This allows for exceptional flexibility in experimentation. Different LLMs can be swapped for each Actor and Critic node, validation can be enabled or disabled for each level of the hierarchy, and the entire workflow can be easily adapted or extended without changing the core codebase.

5 Experimental setups

5.1 Experimental setup

5.1.1 Supervised Baseline Setup (Architecture 0)

The hierarchical DeBERTa model was implemented using **Hugging Face transformers** [Wol+20] and **PyTorch**.

Model and Tokenization. We used the microsoft/mdeberta-v2-base model as the encoder backbone. The corresponding AutoTokenizer was used with a maximum sequence length of 512 tokens.

Training Configuration. The model was trained for a maximum of 10 epochs using the **Trainer API** with a batch size of 8 and 2 gradient accumulation steps. We used the **AdamW** optimizer with a learning rate of 2×10^{-5} and a linear warmup schedule for the first 10% of steps.

Model Selection and Inference. Early stopping was configured with a patience of 3 epochs, selecting the best checkpoint based on the `f1_sample` score on the evaluation set. An optimal decision threshold was determined via a search on the parent-level predictions of the evaluation set.

5.1.2 Zero-Shot Agentic framework

The following models were utilized:

- **GPT-4o/GPT-4o-mini:** Used as the primary classification agent for narrative and sub-narrative labeling. A temperature of 0 was set to ensure deterministic responses.
- **GPT-4o Mini:** Used as a user proxy agent to relay text to classification agents, chosen for cost efficiency.
- **Zero-Shot/Few-Shot Setup:** Agents classify text based on carefully designed prompts. No fine-tuning was performed.

5.1.3 Computational Environment

Experiments were conducted on a machine equipped with: **Processor:** Core 9 Ultra (22 CPU at 2.5GHz), **RAM:** 32 GB, **GPU:** NVIDIA RTX 4070 (8 GB VRAM). However, all LLM inference was performed via API calls to remote servers. The local machine was used primarily to orchestrate API requests, pre-process input text, and handle classification results.

5.1.4 Actor-Critic pipeline

LangGraph implementation. For the experiments reported in this paper, the agentic pipeline was implemented using **LangGraph** [Lan24a], a library designed for constructing stateful, multi-actor applications. The reasoning engine for all nodes in the graph (including the Actor and the Critic) was configured to use **Gemini-2.5-flash**.

Concurrency, batching, and tracing. To maximize throughput, we used LangGraph’s asynchronous batching capabilities (abatch) and configured it with a maximum concurrency of 20 simultaneous requests. For traceability and prompt development, all LLM interactions were logged using **LangSmith** [Lan24b], producing structured traces of model inputs, outputs, and intermediate reasoning states. These traces were instrumental for debugging and prompt refinement.

6 Experiments and results

6.1 Synthesis of the multi-paradigm approach

Having detailed our methodological journey, we now turn to the empirical evaluation of our systems. To comprehensively address the challenges of the SemEval-2025 narrative classification task, we developed a suite of models spanning three distinct paradigms. We began with **Architecture 0**, a traditional **fine-tuning** approach based on **mDeBERTa**, systematically enhancing it with techniques like **class weighting** and **hierarchical regularization** to establish a robust **supervised baseline**. Recognizing the limitations of fine-tuning on a **data-scarce, long-tailed** problem, we then shifted to a **zero-shot reasoning** paradigm. This led to **Architecture 1**, a novel **agentic framework** that decomposes the task for specialized **LLM agents**, and ultimately to **Architecture 2**, our most advanced **traceable actor-critic pipeline**, designed for maximum **reliability** and **interpretability** through **evidence-grounded validation**. In this section, we present a comparative analysis of these three paradigms to evaluate their effectiveness and trade-offs.

6.2 Results for Architecture 0 (Transformer Baseline)

This section presents the comprehensive experimental results for our Multi-Head mDeBERTa baseline architecture. We evaluate the model’s performance across different classification thresholds and provide detailed analysis of its effectiveness for hierarchical narrative classification across multiple languages.

6.2.1 Experimental setup and evaluation metrics

Our evaluation was conducted on the development set comprising 178 documents across five languages (Bulgarian, English, Hindi, Portuguese, and Russian). The model was trained using a threshold of 0.65, and we systematically evaluated performance at four different classification thresholds: 0.5, 0.65 (training baseline), 0.7, and 0.8.

6.2.2 Overall performance analysis

Threshold sensitivity analysis

Table 6.1 presents the comprehensive performance comparison across all tested thresholds for both narrative and subnarrative classification tasks.

Table 6.1: Performance comparison across different classification thresholds. The training threshold (0.65) serves as the baseline for comparison.

Threshold	Narratives			Subnarratives		
	F1 Macro	F1 Micro	F1 Samples	F1 Macro	F1 Micro	F1 Samples
0.5	0.1800	0.2614	0.2475	0.0654	0.0987	0.0971
0.65*	0.2004	0.3145	0.2901	0.0776	0.1427	0.1543
0.7	0.1825	0.2911	0.2657	0.0821	0.1516	0.1566
0.8	0.0937	0.2012	0.2233	0.0583	0.1574	0.1750

The results reveal distinct performance patterns between narrative and subnarrative classification:

Narrative classification. The training threshold of 0.65 consistently achieves the best performance across all metrics for narrative classification. This demonstrates excellent model calibration during training, with our primary metric F1 Samples reaching 0.2901, alongside F1 Macro of 0.2004 and F1 Micro of 0.3145. Lower thresholds (0.5) result in too many false positives, reducing the F1 Samples score by approximately 8.4%. Conversely, very high thresholds (0.8) are overly conservative, leading to a substantial 23% reduction in F1 Samples performance as the model misses many true positive predictions.

Hierarchical performance characteristics

The substantial performance gap between narrative and subnarrative classification (F1 Samples: 0.2901 vs 0.1750 at optimal thresholds) illustrates the fundamental challenge of hierarchical classification. Even when using the optimal threshold for each level (0.65 for narratives, 0.8 for subnarratives), the fine-grained classification achieves only 60% of the coarse-grained performance. Several factors contribute to this pattern:

- **Data scarcity amplification:** Subnarratives inherit the data scarcity of their parent narratives and further subdivide the already limited examples
- **Increased semantic similarity:** Subnarratives within the same parent category often share similar linguistic features, making discrimination more challenging
- **Threshold sensitivity:** The different optimal thresholds suggest that the two classification levels require different decision boundaries

6.2.3 Language-specific performance analysis

Table 6.2 presents the performance breakdown by language using the optimal thresholds for each task level.

Table 6.2: Language-specific performance using optimal thresholds (0.65 for narratives, 0.7 for subnarratives F1 Macro).

Language	Narratives (0.65)		Subnarratives (0.7)	
	F1 Macro	Best Threshold	F1 Macro	Best Threshold
Portuguese (PT)	0.243	0.65	0.104	0.7
English (EN)	0.212	0.5	0.101	0.65
Bulgarian (BG)	0.209	0.7	0.080	0.7
Russian (RU)	0.170	0.65/0.5	0.095	0.7
Hindi (HI)	0.167	0.65	0.032	0.5

Portuguese demonstrates superior performance. Portuguese achieves the highest F1 Samples scores for both narratives (0.352) and subnarratives (0.189), suggesting that the model learned particularly effective representations for Portuguese text. This represents a substantial

60% advantage over the lowest-performing language (Hindi: 0.220 for narratives), highlighting significant cross-linguistic performance variation.

Hindi presents unique challenges. Hindi shows the most substantial performance challenges, particularly evident in the F1 Samples scores. For narratives, Hindi achieves only 0.220 compared to Portuguese's 0.352, and for subnarratives, the gap is even more pronounced. This suggests that the model struggles with Hindi text across all levels of granularity, possibly due to linguistic complexity or limited training data quality.

Cross-linguistic performance patterns. The F1 Samples results reveal that while threshold 0.8 optimizes subnarrative performance overall, language-specific patterns emerge. Russian shows surprisingly strong subnarrative F1 Samples performance (0.225), nearly matching narrative performance (0.245), suggesting that conservative thresholds particularly benefit Russian text classification.

6.2.4 Detailed performance analysis at optimal threshold

Using the optimal threshold of 0.65, we conducted detailed confusion matrix analysis to understand the model's strengths and limitations.

Top-performing narrative categories

Table 6.3 shows the best-performing narrative categories, revealing clear patterns in what the model learned effectively.

Climate change narratives show strong performance. The model demonstrates particular effectiveness in identifying climate change-related narratives, with 5 out of 8 top performers belonging to this domain. "CC: Questioning measurements/science" achieves perfect recall (1.000) and the highest F1 score (0.727), suggesting clear linguistic markers for scientific skepticism.

Table 6.3: Top 8 performing narrative categories at threshold 0.65, ranked by F1 score.

Narrative Category	TP	FP	FN	Precision	F1
CC: Questioning measurements/science	4	3	0	0.571	0.727
CC: Criticism of climate policies	6	2	3	0.750	0.706
CC: Amplifying Climate Fears	17	6	19	0.739	0.576
URW: Discrediting the West, Diplomacy	24	19	20	0.558	0.552
CC: Criticism of institutions/authorities	15	24	4	0.385	0.517
CC: Downplaying climate change	3	6	1	0.333	0.462
URW: Discrediting Ukraine	19	33	14	0.365	0.447
CC: Criticism of climate movement	6	13	3	0.316	0.429

Precision-recall trade-offs vary by category. "CC: Criticism of climate policies" achieves high precision (0.750) with moderate recall, while "CC: Criticism of institutions/authorities" shows the opposite pattern (precision: 0.385, recall: 0.789). This indicates that different narrative types have varying degrees of linguistic distinctiveness.

Challenging categories and error analysis

The bottom-performing categories reveal systematic challenges:

- **URW: Negative Consequences for the West** (F1: 0.216): High false positive rate (25 FP vs 4 TP) suggests the model over-generalizes this category
- **URW: Blaming the war on others** (F1: 0.205): Low precision (0.167) indicates difficulty distinguishing from related war narratives
- **Other category** (F1: 0.233): The implicit negative classification strategy shows limited effectiveness

Subnarrative classification challenges

Subnarrative classification reveals the granularity limitations of the transformer approach:

- **Best performer:** "CC: Amplifying Climate Fears: Amplifying existing fears" (F1: 0.640) demonstrates that some fine-grained distinctions are learnable

- **Systematic failures:** Many subnarratives achieve F1 scores below 0.300, indicating insufficient training data or overly subtle distinctions
- **Hindi-specific challenges:** Multiple subnarratives in Hindi achieve 0.000 F1 scores, suggesting language-specific modeling difficulties

6.2.5 Key insights and limitations

Hierarchical classification challenges

The substantial performance gap between narrative (F1 Samples: 0.2901) and subnarrative classification (F1 Samples: 0.1750 at optimal threshold 0.8) illustrates fundamental limitations of the fine-tuning approach for hierarchical tasks with limited data. Even with optimal threshold selection for each level, subnarratives achieve only 60% of the narrative-level performance when evaluated on a per-document basis. The model successfully learns coarse-grained narrative patterns but struggles with fine-grained distinctions, particularly in low-resource languages.

Language-specific patterns

The significant variation in F1 Samples performance across languages (Portuguese: 0.352 vs Hindi: 0.220 for narratives) suggests that multilingual performance is not uniform. This 60% performance gap indicates that the model's effectiveness varies substantially based on language, potentially reflecting differences in training data quality, linguistic complexity, or the effectiveness of the translation-based data augmentation strategy across different language pairs.

Implications for system design

These results provide crucial insights for the development of more advanced architectures:

- **Threshold optimization** should be performed separately for each level of the hierarchy
- **Language-specific tuning** may be necessary for production deployment
- **Data augmentation strategies** beyond translation may be required for fine-grained classification

- **Alternative paradigms** (zero-shot, few-shot) warrant investigation given the limitations observed in the fine-tuning approach

6.3 Results for Architecture 1 (Zero-Shot Agentic Framework)

This section presents the comprehensive experimental results for our zero-shot agentic framework (Architecture 1). We evaluate the model’s performance on the English test set, analyze its hierarchical and multilingual characteristics, and provide a detailed error analysis based on its performance on the development set.

6.3.1 Overall Performance on English Test Set

The primary evaluation was conducted on the official English test set of the SemEval-2025 shared task. The results, shown in Table 6.4, demonstrate the strong viability of the zero-shot, agent-based paradigm.

Table 6.4: Performance of the Zero-Shot Agentic Framework on the English test set, compared to the official random baseline.

Model	Rank	F1 Macro (Coarse)	F1 Samples (Fine)
Random Baseline	26	0.030	0.013
Agentic Framework	3	0.513	0.406

The agentic framework achieved a Sample-Averaged F1 score of 0.406 on the fine-grained subnarrative labels, **securing 3rd place in the official SemEval-2025 English ranking**. This result is particularly notable as it was achieved in a purely zero-shot setting, without any task-specific fine-tuning. The model dramatically outperformed the random baseline, confirming that the LLM agents, guided by carefully engineered prompts, were able to perform complex, nuanced reasoning. The strong Macro F1 score of 0.513 on the coarse-grained narrative labels further indicates that the model was effective at identifying a broad range of narratives, not just the most frequent ones.

Challenges with Semantically Similar Narratives

The model also exhibited confusion between semantically adjacent categories, leading to a high number of false positives. A notable example is the confusion between “CC: Criticism of climate policies” and “CC: Criticism of institutions and authorities”. The linguistic features that distinguish these two narratives are often subtle and co-exist within the same document, making it difficult for the agent to make a clean distinction based on a general definition. This highlights the limitations of the binary decision approach when faced with a fine-grained and overlapping label space.

6.3.5 Key Insights and Limitations

The results from the zero-shot agentic framework provide several key insights:

Viability of Zero-Shot Paradigm. The competitive performance demonstrates that zero-shot LLM-based systems are a powerful and viable alternative to fine-tuning for complex, data-scarce HMLC tasks.

Limitations of Decomposition. While effective, the “one agent per label” design is susceptible to hierarchical error propagation and struggles to model the relationships between semantically close labels.

Insufficiency of “Translate-then-Classify”. The significant performance drop in multilingual settings reveals that a simple translation-based strategy is inadequate for tasks requiring deep cultural and linguistic nuance.

These findings directly motivate the need for our third architecture. The challenges of error propagation and semantic ambiguity point to the need for a more holistic reasoning process with built-in validation, while the multilingual failures highlight the importance of architectures that can handle source languages directly.

6.4 Results for Architecture 2 (Actor-Critique Pipeline)

This section presents comprehensive experimental results for our actor-critique pipeline (Architecture 2), powered by Google Gemini 2.5 Flash [Goo24]. We conduct an ablation study evaluating the system both with and without the critique validation step across five languages on the development set, analyzing narrative and subnarrative classification effectiveness, cross-linguistic performance patterns, and the specific impact of the validation mechanism on classification accuracy.

6.4.1 Experimental setup and evaluation framework

Our evaluation was conducted on the multilingual development set comprising 178 documents across five languages: Bulgarian (BG, 35 files), English (EN, 41 files), Hindi (HI, 35 files), Portuguese (PT, 35 files), and Russian (RU, 32 files). We evaluate two configurations of our actor-critique pipeline:

- **Without Validation:** A single-stage classification agent provides direct predictions for both narratives and subnarratives without additional validation.
- **With Validation:** A two-stage process where an initial classification agent provides predictions, followed by a critique agent that validates and refines *only the narrative-level predictions*. Subnarrative classifications remain unchanged from the initial agent’s predictions.

This ablation study aims to quantify the effectiveness of narrative-level critique validation in addressing error propagation and semantic ambiguity limitations at the first hierarchical level, while evaluating its indirect impact on subnarrative performance and computational overhead trade-offs.

Our primary evaluation metrics are F1 Coarse (for narratives) and F1 Sample (for subnarratives), providing balanced assessment of multi-label performance at both hierarchical levels by evaluating each document’s label set independently.

6.4.2 Ablation study: Impact of validation mechanism

We present a comprehensive comparison of our actor-critique pipeline with and without the validation step across all evaluated languages. This ablation study reveals the specific contribution of the critique validation mechanism to classification performance.

Table 6.6: Comprehensive ablation study of actor-critique pipeline validation configurations across multilingual development set (178 documents). Results show F1 Coarse (narratives) and F1 Sample (subnarratives) for three validation strategies.

Language	Validation	F1 Coarse	F1 Sample	Δ F1 Coarse	Δ F1 Sample
BG	None	0.5799	0.4104	—	—
	Narrative	0.5721	0.4049	-0.0078	-0.0055
	Subnarrative	0.5521	0.4211	-0.0278	+0.0107
EN	None	0.5132	0.3815	—	—
	Narrative	0.5241	0.3675	+0.0109	-0.0140
	Subnarrative	0.5319	0.4166	+0.0187	+0.0351
HI	None	0.4715	0.2976	—	—
	Narrative	0.4217	0.3082	-0.0498	+0.0106
	Subnarrative	0.4354	0.2687	-0.0361	-0.0289
PT	None	0.7489	0.4737	—	—
	Narrative	0.7335	0.4681	-0.0154	-0.0056
	Subnarrative	0.6904	0.4367	-0.0585	-0.0370
RU	None	0.6958	0.4754	—	—
	Narrative	0.7080	0.4786	+0.0122	+0.0032
	Subnarrative	0.6693	0.5078	-0.0265	+0.0324
Average	None	0.6019	0.4077	—	—
	Narrative	0.5919	0.4055	-0.0100	-0.0022
	Subnarrative	0.5758	0.4102	-0.0261	+0.0025

6.4.3 Overall multilingual performance analysis

Figure 6.4 presents a three-way comparative analysis across validation configurations, revealing the distinct impact patterns of each validation strategy on multilingual performance.

6.4.4 Key findings from comprehensive ablation study

Validation mechanisms often degrade baseline performance. The ablation study reveals that both validation strategies generally decrease performance compared to the no-validation baseline. On average, narrative validation reduces F1 Coarse by -0.0100 and F1

is optimal for most deployment scenarios. The base Gemini 2.5 Flash model demonstrates superior performance without additional validation layers, achieving the highest average scores across both hierarchical levels while requiring minimal computational overhead. This challenges the assumption that multi-agent validation architectures inherently improve classification accuracy.

Validation mechanisms introduce systematic degradation rather than improvement. The consistent performance reductions across most language-validation combinations reveal that critique agents may be systematically interfering with accurate base predictions rather than correcting errors. The validation process appears to introduce noise and over-correction bias, particularly problematic for high-performing languages like Portuguese where validation causes substantial performance drops despite strong baseline accuracy.

Language-specific validation effects are largely negative with limited exceptions. Russian represents the only clear case where narrative validation provides consistent benefits (+0.0122 F1 Coarse, +0.0032 F1 Sample), while English shows mixed results with validation type-dependent trade-offs. All other languages experience predominantly negative validation effects, indicating that validation mechanisms may be poorly calibrated for diverse linguistic and cultural contexts in multilingual propaganda detection.

Hierarchical consistency improvements cannot justify performance costs. While validation approaches provide marginal improvements in hierarchical consistency (reducing performance gaps by 0.8-2.6%), these gains come at significant absolute performance costs. The trade-off between hierarchical alignment and overall accuracy strongly favors the simpler no-validation approach, particularly for production systems where classification accuracy is paramount.

Actor-critique architecture effectiveness independent of validation complexity. The substantial improvements over transformer baselines are achieved primarily through the base actor-critique framework rather than validation enhancements. This suggests that the core architectural innovation lies in the prompt engineering and task decomposition rather than multi-agent validation, supporting simpler deployment strategies that maximize both performance and computational efficiency.

The ablation study conclusively demonstrates that validation mechanisms in multilingual hierarchical classification may be counterproductive, with the no-validation actor-critique pipeline providing optimal performance across languages while maintaining architectural simplicity. This finding has significant implications for production deployment strategies, suggesting that computational resources are better allocated to improving base model performance rather than implementing complex validation layers that consistently degrade accuracy.

6.4.10 Cross-architectural comparison: AutoGen vs. Actor-Critique

To understand the relative strengths of our two architectures, we compare the performance of Architecture 1 (AutoGen framework) with Architecture 2 (Actor-Critique pipeline) across available languages and metrics.

Table 6.7: Performance comparison between Architecture 1 (AutoGen) and Architecture 2 (Actor-Critique, no validation) across languages. Architecture 2 shows substantial improvements, particularly in multilingual settings.

Language	Architecture	F1 Coarse/Macro	F1 Sample	Multilingual Approach
EN	AutoGen	0.513	0.406	Native
	Actor-Critique	0.513	0.382	Native
	Δ	0.000	-0.024	—
PT	AutoGen	0.285	0.173	Translate-to-English
	Actor-Critique	0.749	0.474	Direct multilingual
	Δ	+0.464	+0.301	—
RU	AutoGen	0.247	0.137	Translate-to-English
	Actor-Critique	0.696	0.475	Direct multilingual
	Δ	+0.449	+0.338	—

Native English performance parity with different strengths. Both architectures achieve identical narrative-level performance on English (F1 Coarse/Macro: 0.513), demonstrating that the core classification capability is comparable. The Actor-Critique pipeline shows a slight decrease in subnarrative performance (-0.024 F1 Sample), suggesting that the single-agent approach may have minor advantages for fine-grained English classification, possibly due to reduced complexity in the reasoning process.

Dramatic multilingual superiority of Actor-Critique architecture. The Actor-Critique pipeline demonstrates substantial improvements in multilingual settings: Portuguese shows gains of +0.464 F1 Coarse and +0.301 F1 Sample, while Russian achieves +0.449 F1 Coarse and +0.338 F1 Sample improvements. These massive performance gains (163-246% improvements) highlight the critical advantage of direct multilingual processing over the translate-to-English approach used by AutoGen.

Hierarchical consistency advantages in multilingual contexts. While AutoGen shows severe hierarchical degradation in multilingual settings (Portuguese: 0.285→0.173, -39% drop; Russian: 0.247→0.137, -45% drop), the Actor-Critique pipeline maintains more consistent hierarchical performance across languages. The multilingual hierarchical gap averages 36.8% for Actor-Critique compared to AutoGen’s 42% average drop, suggesting better error propagation management.

Architectural design implications for multilingual deployment. The comparison reveals that Architecture 2’s success stems from two key design decisions: (1) direct multilingual processing eliminates translation-induced information loss, and (2) the unified agent approach reduces complexity-related error accumulation in cross-lingual settings. This suggests that for multilingual propaganda detection, architectural simplicity combined with native language processing significantly outweighs the theoretical benefits of specialized agent decomposition.

6.4.11 Evaluation limitations and dataset size considerations

Limited development set size constrains architectural evaluation robustness. The comparative analysis presented above should be interpreted with caution due to the relatively small size of the multilingual development set. With an average of 32-41 documents per language (BG: 35, EN: 41, HI: 35, PT: 35, RU: 32), the evaluation dataset provides limited statistical power for drawing definitive conclusions about architectural superiority across diverse linguistic and cultural contexts.

Statistical significance challenges for cross-architectural comparison. The substantial performance differences observed between architectures (e.g., +0.464 F1 improvements

for Portuguese) may be influenced by the small sample sizes and specific document characteristics within each language subset. While the magnitude of improvements suggests genuine architectural advantages, larger-scale evaluation would be necessary to establish statistical significance and generalizability across broader document populations and propaganda narrative distributions.

Document-level variance impact on performance estimates. The limited document count per language (30-40 documents) means that individual high-performing or challenging documents can disproportionately influence overall performance metrics. This is particularly relevant for rare narrative categories where only a few positive examples exist across the entire development set, making architectural comparison sensitive to document selection effects rather than fundamental design differences.

6.4.12 SemEval-2025 Task 10 competition performance

To contextualize our architectural evaluation within the broader research community, we present our team’s (INSALyon2) official ranking in the SemEval-2025 Task 10 competition for Subtask 2 (narrative classification) across all evaluated languages.

Table 6.8: INSALyon2 official rankings in SemEval-2025 Task 10 Subtask 2 across all languages. Rankings reflect performance on the official test set using our Actor-Critique architecture (no validation configuration).

Language	Rank	F1 Macro Coarse	F1 Samples
English	2	0.547	0.433
Portuguese	2	0.679	0.433
Hindi	3	0.515	0.435
Russian	4	0.589	0.410
Bulgarian	5	0.590	0.381

Strong competitive performance validates architectural design. Our Actor-Critique architecture achieved consistent top-5 rankings across all languages, with particularly strong second-place positions in English and Portuguese, validating the effectiveness of our no-validation configuration in multilingual contexts.

Performance consistency confirms development findings. The competition results align well with our development set analysis, particularly the strong Portuguese performance (0.679 test vs 0.749 dev) and the notable Hindi improvement from development challenges to competitive third place, demonstrating good generalization properties of the direct multilingual processing approach.

Comparative analysis with top-performing approaches. While our approach achieved competitive second-place performance in English, the first-place GateNLP team [SSB25a] reported superior results using their hierarchical three-step prompting methodology. Despite implementing their described architectural framework based on their published approach, we were unable to replicate their reported performance levels, suggesting that implementation details, hyperparameter configurations, or specific prompt engineering techniques may play critical roles in achieving optimal results with hierarchical prompting strategies.

6.5 Consolidated Error Analysis: Persistent Challenges Across Paradigms

While our evidence-grounded Actor-Critique pipeline (Architecture 2) marks a significant improvement over both the supervised baseline and the decomposed agentic framework, a closer examination of its predictions reveals persistent failure modes. These errors are not unique to one architecture but represent the core, unsolved challenges of applying HMLC to nuanced, multilingual narrative detection. By analyzing these recurring failures, we can delineate the frontiers of current model capabilities.

6.5.1 Semantic Ambiguity in Fine-Grained Classification

The most common source of error, even for our best-performing model, is the confusion between semantically adjacent or overlapping categories, particularly at the sub-narrative level. A prime example, first noted in the AutoGen analysis, is the difficulty in distinguishing between `***CC: Criticism of climate policies***` and `***CC: Criticism of institutions and authorities.***` A single document often contains text that criticizes a government’s climate policy. Is this an attack on the policy itself, or on the institution that created it? The distinction is subtle and often a matter of interpretation.

Our analysis of Architecture 2’s outputs shows that while it performs well on clearly demarcated narratives, it struggles when labels share significant lexical and conceptual overlap. The model often correctly identifies the parent narrative but then either assigns both sibling sub-narratives or incorrectly chooses one, leading to precision or recall errors. This suggests a fundamental limitation in the model’s ability to disentangle the primary **intent** of a text from its secondary themes, a crucial skill for high-fidelity, fine-grained classification.

6.5.2 The "Hard Tail": Systematic Failure on Ultra-Rare Narratives

Despite the zero-shot paradigm’s independence from training data volume, our analysis reveals a "hard tail" of narratives that all architectures systematically failed to identify. The AutoGen framework, for instance, failed to predict any true positives for 41% of the narrative categories on the development set. While Architecture 2 showed improved coverage, it still struggled with

the most infrequent or abstractly defined labels, such as **"URW: Russia is the Victim"** or narratives with only a handful of examples in the entire dataset.

This indicates that even with access to vast world knowledge, an LLM's effectiveness is constrained by the specificity and clarity of the provided definitions. For narratives that are highly nuanced, subtly expressed, or culturally niche, a simple definition in a prompt is insufficient to activate the model's reasoning capabilities reliably. These "hard tail" labels represent the true frontier of zero-shot classification, likely requiring more sophisticated prompting techniques like dynamic example retrieval or chain-of-thought reasoning grounded in external knowledge bases.

6.5.3 Persistent Hierarchical Degradation

A consistent pattern across all three architectures is the performance degradation from the coarse-grained narrative level to the fine-grained sub-narrative level. While Architecture 2 significantly mitigated this issue compared to the baseline, the gap remains substantial.

*** Architecture 0 (Transformer):** The F1 Samples score dropped by nearly 40% from the optimal narrative performance (0.290) to the optimal sub-narrative performance (0.175). *** Architecture 2 (Actor-Critique):** This gap was halved but still significant, with a 20% drop from F1 Coarse (0.602) to F1 Sample (0.408) in the best configuration.

This persistent degradation highlights two core challenges. First, **"error propagation"**, where a misclassification at the parent level makes correct sub-narrative classification impossible. Second, **"data scarcity amplification"**, where the already limited examples for a parent narrative are further fragmented among its children, making the distinctions between them harder to reason about, even for an LLM.

6.5.4 Cross-Lingual Brittleness and Cultural Nuance

The most profound limitation revealed by our study is the brittleness of models in a true multilingual context. The catastrophic failure of Architecture 1's "translate-then-classify" approach served as a stark warning. However, even Architecture 2, which processed languages directly, exhibited significant performance disparities. The model achieved an F1 Coarse of 0.749 on Portuguese but only 0.472 on Hindi.

This suggests the problem runs deeper than simple translation loss. LLMs, despite being trained on multilingual corpora, may lack a deep understanding of the culturally-specific rhetorical strategies, historical contexts, and idiomatic expressions that define propaganda in different regions. For example, a narrative of "discrediting the West" may manifest as overt criticism in Russian media but through more subtle, allegorical language in Hindi sources. The model's uneven performance indicates that its reasoning capabilities are not yet culturally isotropic, and it remains more attuned to the linguistic patterns of high-resource languages like English and Portuguese. This gap in cultural nuance is arguably the single greatest barrier to deploying robust, global-scale narrative detection systems.

7 Discussion

This work systematically evaluated three distinct architectural paradigms for hierarchical multi-label classification (HMLC) on the challenging SemEval-2025 narrative detection task. Our investigation, spanning from a supervised Transformer baseline to two zero-shot Large Language Model (LLM) frameworks, yields several critical insights into the current state and future direction of HMLC for nuanced, data-scarce problems. In this chapter, we synthesize our findings, discuss their implications, and critically examine the limitations of our study.

7.1 The Paradigm Shift: From Fine-Tuning to Zero-Shot Reasoning

The most striking result of our comparative analysis is the dramatic performance gap between the supervised fine-tuning paradigm (Architecture 0) and the zero-shot LLM-based paradigms (Architectures 1 and 2). Our Multi-Head mDeBERTa baseline, despite being enhanced with class weighting and a hierarchically-conditioned architecture, achieved modest F1 Samples scores of 0.290 for narratives and 0.175 for subnarratives. In stark contrast, both the AutoGen framework and the Actor-Critique pipeline achieved substantially higher performance (e.g., F1 scores >0.400 on the English test set) without any task-specific training.

This disparity confirms a central hypothesis motivated by our initial data analysis: for tasks characterized by extreme class imbalance and a long tail of rare labels, the traditional fine-tuning paradigm is fundamentally constrained. Even with sophisticated mechanisms like disentangled attention and class weighting, the model struggles to learn effective representations from the handful of examples available for most classes. The LLM-based systems, however, bypass this data bottleneck by leveraging vast pre-existing world knowledge and reasoning capabilities, activated through carefully engineered prompts. This allows them to classify narratives based on their semantic definitions rather than on statistical patterns learned from a small, skewed

dataset. This finding strongly suggests that for complex, low-resource HMLC tasks like narrative detection, the field is undergoing a decisive shift away from data-hungry supervised learning toward knowledge-driven, zero-shot reasoning.

7.2 Architectural Divergence in LLM-Based Systems

While both LLM-based architectures outperformed the baseline, their comparison reveals crucial design trade-offs with significant implications for multilingual performance, traceability, and efficiency.

The Critical Flaw of the "Translate-then-Classify" Approach. Architecture 1 (AutoGen) employed a "translate-to-English" strategy for non-English texts, a common and seemingly pragmatic approach. However, our results demonstrate its profound inadequacy. While achieving a competitive 3rd place on the native English test set (F1 Sample: 0.406), its performance plummeted on translated Portuguese and Russian texts (0.173 and 0.137, respectively). In contrast, Architecture 2 (Actor-Critique), which processed each language directly, achieved massive gains of +0.464 F1 Coarse for Portuguese and +0.449 for Russian over Architecture 1.

This stark difference highlights that machine translation, even when using state-of-the-art models, acts as a destructive filter for the subtle linguistic and cultural nuances essential for propaganda detection. Rhetorical devices, idiomatic expressions, and culturally-specific framing are lost, leaving the classification agent with a semantically impoverished input. This finding provides a clear directive for future multilingual HMLC research: systems must be designed for direct, native-language processing to be effective.

Revisiting the Transformer Baseline's Methodology: A Critical Self-Assessment.

Our findings demand a rigorous self-critique of the Transformer baseline's methodological assumptions. The dramatic performance degradations observed in the AutoGen architecture when processing translated texts—44-66% reductions in F1 Sample scores for Portuguese and Russian compared to native English—expose a fundamental flaw in our own data augmentation strategy.

The Transformer baseline relied heavily on machine translation to artificially expand the multilingual training corpus, translating texts between languages within the same dataset to

increase data volume. Given that state-of-the-art translation systems systematically destroy the subtle linguistic and cultural markers essential for propaganda detection, this augmentation process was not merely ineffective but actively harmful. The translation artifacts, loss of rhetorical devices, and cultural context stripping documented in our AutoGen experiments suggest that the Transformer baseline was trained on *systematically corrupted representations* of multilingual propaganda texts.

This methodological error compounds the already severe data scarcity problem: not only did the baseline suffer from insufficient training examples, but a substantial portion of its multilingual training data consisted of degraded, translation-induced approximations of authentic propaganda discourse. This self-critique fundamentally reframes our interpretation of the Transformer baseline’s limitations—its poor performance may reflect not just the inherent challenges of few-shot learning, but the systematic introduction of noise through flawed data augmentation. This insight reinforces our core argument for direct multilingual processing and serves as a cautionary tale about the hidden costs of seemingly pragmatic methodological shortcuts in cross-lingual NLP research.

Decomposition vs. Holistic Analysis: A Trade-off in Complexity and Traceability.

The two LLM architectures also represent different philosophical approaches to task decomposition. The AutoGen framework, inspired by Binary Relevance, decomposes the task into dozens of independent binary decisions ("one agent per label"). The Actor-Critique pipeline, conversely, uses a single, powerful agent per hierarchical level to perform a holistic analysis, considering all labels simultaneously.

While the decomposed approach proved effective for English, its complexity may have contributed to error accumulation in the more challenging multilingual setting. More importantly, its binary outputs offer limited traceability. The Actor-Critique pipeline was designed specifically to address this, shifting the task from classification to evidence-grounded claim generation. By forcing the model to produce a verbatim `evidence_quote` and `reasoning` for each prediction, the system’s outputs become fully auditable. This architectural choice is not merely an academic exercise; for high-stakes applications like monitoring disinformation, such transparency is a non-negotiable requirement.

7.3 The Surprising Ineffectiveness of the Critique Mechanism

One of the most counter-intuitive findings emerged from the ablation study of the Actor-Critique pipeline. We hypothesized that a second "Critic" agent, tasked with validating the "Actor's" claims, would improve precision and robustness. The results proved the opposite: across most languages, enabling the validation step *degraded* performance compared to the single-pass Actor-only configuration. On average, narrative validation reduced F1 Coarse by 0.0100, with some languages like Portuguese showing substantial drops.

This suggests several possibilities. First, the base model (Gemini 2.5 Flash) may already be well-calibrated, and its initial, single-pass judgments are more accurate than a subsequent, potentially over-correcting, validation step. Second, the validation process itself might introduce "noise" or systematic biases, where the Critic agent incorrectly refutes valid claims. This phenomenon, where multi-step reasoning chains can accumulate errors or drift from the optimal path, is a critical area for research in agentic systems. Our findings serve as a cautionary tale: architectural complexity, even when well-intentioned, does not guarantee improved performance and can be counterproductive. For this task, the simplest LLM configuration—a single, holistic, evidence-grounded agent—proved to be the most effective.

7.4 Limitations of the Study

Our findings should be interpreted in the context of several limitations.

Dataset Size. As noted in our results, the development set used for multilingual and ablation comparisons is relatively small (30-40 documents per language). While the performance differences between architectures are large and consistent, a larger evaluation corpus would be necessary to establish definitive statistical significance and ensure our conclusions generalize across a wider variety of documents.

Model and API Dependency. Our zero-shot architectures rely on proprietary, closed-source LLMs (OpenAI and Google models). This introduces dependencies on external APIs and limits full reproducibility. Performance is tied to the specific model versions used (e.g., GPT-4o,

Gemini 2.5 Flash), and future updates to these models could alter the results. Furthermore, we did not conduct an exhaustive comparison across different model providers or sizes, which could influence architectural choices.

Cost and Latency. While computationally more efficient than training a large Transformer, inference with LLM-based systems, particularly multi-step agentic pipelines, incurs significant financial cost and latency due to API calls. This trade-off between training cost and inference cost is a critical consideration for practical, large-scale deployment.

Prompt Sensitivity. The performance of zero-shot systems is notoriously sensitive to prompt engineering. While we invested considerable effort in refining our prompts for clarity and precision, it is possible that alternative phrasing or structuring could yield different results. The "ineffectiveness" of our Critic, for example, might be an artifact of its specific prompt design rather than a fundamental flaw in the validation concept itself.

8 Conclusion

This paper charted a deliberate course from traditional supervised methods to the frontier of zero-shot agentic reasoning for hierarchical multi-label classification. Our journey began with a state-of-the-art mDeBERTa baseline, which, despite architectural enhancements, confirmed the inherent limitations of fine-tuning on data-scarce, long-tailed tasks. We then demonstrated the viability of zero-shot classification through two distinct LLM-based architectures: a decomposed, multi-agent framework and a holistic, evidence-grounded pipeline.

8.1 Principal Findings and Implications

From this comparative analysis, we draw three principal conclusions that carry significant implications for the field.

1. **The necessity of zero-shot reasoning.** For nuanced, low-resource HMLC tasks like narrative detection, the paradigm of zero-shot reasoning is not merely an alternative but a necessity. LLMs' ability to classify from semantic definitions, rather than statistical patterns in sparse data, offers a decisive advantage that supervised methods struggle to overcome.
2. **The imperative of native-language processing.** For multilingual applications, direct, native-language processing is non-negotiable. Our experiments unequivocally show that the common "translate-then-classify" shortcut introduces unacceptable information loss, destroying the cultural and linguistic nuances critical for accurate analysis.
3. **The value of traceable simplicity.** In the design of agentic systems, architectural simplicity and inherent traceability can be more effective than complex, multi-step validation loops. The superior performance of our single-pass, evidence-grounded Actor over the full Actor-Critique pipeline serves as a crucial finding: forcing a model to

ground its claims in evidence provides more value than adding a complex, and potentially counter-productive, validation layer.

These conclusions directly inform the critical challenges that lie ahead, which will shape the next phase of research in narrative detection and HMLC.

8.2 Key Open Challenges

- **Interpretability and faithfulness**

- Models must provide human-understandable explanations for predictions and demonstrate structural faithfulness (e.g., obey the true-path rule). Our evidence-grounded approach is a step in this direction, but more formal guarantees are needed.
- Beyond loss-based penalties, we need architectures and verification methods that certify hierarchical consistency.

- **Dynamic and evolving hierarchies**

- Real-world taxonomies change: new labels appear, labels split/merge, and relations shift.
- Research directions: continual learning for label updates, modular label adapters, and lightweight schema evolution strategies that avoid full retraining.

- **Robust cross-lingual and cross-cultural transfer**

- As our results show, transfer across typologically distant languages and cultural framings remains unreliable.
- Promising approaches: culture-aware adapters, contrastive cross-cultural fine-tuning, and evaluation protocols that measure cultural equivalence rather than literal translation.

- **Modeling richer narrative structure**

- Narratives include causality, temporality, and actor-event relations that are not captured by simple taxonomies.

- Move toward graph-structured prediction, joint event-role-narrative models, and hybrid symbolic-neural representations.
- **Governance of LLM augmentation**
 - LLM-generated training data is a powerful but noisy resource: it may amplify biases or introduce stylistic artifacts.
 - Needed tools: sampling and diversity controls, human-in-the-loop filters, bias audits, and provenance tracking for synthetic examples.

8.3 Concluding Remarks

The shift from fine-tuning to zero-shot reasoning is more than a change in technique; it is a fundamental re-evaluation of how we approach complex classification. Our findings illustrate that future progress in HMLC will depend less on architectural tweaks to supervised models and more on developing robust, traceable, and culturally-aware reasoning systems. Addressing the open challenges of interpretability, dynamic hierarchies, and the responsible governance of synthetic data is therefore not an incremental step, but the central task for building narrative analysis tools that are both powerful and trustworthy in their real-world application. Progress will require integrated work across evaluation, modelling, data governance, and tooling—a multidisciplinary agenda that is both technically challenging and societally important.

A Appendix

This appendix provides key performance visualizations, complete prompt templates, and supporting materials from our experimental evaluation. Appendix A presents representative performance results across configurations and languages. Appendix B documents the complete prompt templates used in our Actor-Critique pipeline. Full visualization sets for all languages and configurations are available in the project repository.

A.1 Appendix A: Performance Visualizations

This section presents performance visualizations organized by validation configuration: (1) comprehensive results for the no-validation baseline configuration across all languages, and (2) representative results for the validation configurations (overview plots and English examples).

A.1.1 A.1 No Validation Configuration

This section presents results from the Actor-Critique pipeline (Architecture 2) without any validation mechanism enabled.

unsure, answer 0.

Subnarrative Detection Prompt

Architecture 1: Subnarrative Binary Classification

You are a classification model trained to do binary classification by detecting whether a given text is related to a specific subnarrative or not.

You have been trained to recognize the subnarrative:
SUBNARRATIVE.

This subnarrative is defined as:
SUBNARRATIVE_DEFINITION.

Here are some examples of statements related to this subnarrative:
SUBNARRATIVE_EXAMPLES.

If the text is related to the subnarrative, please respond with '1'.
Otherwise, respond with '0'. Do not try to make sentences, just respond with '1' or '0'.

You are ONLY allowed to answer with '1' or '0' and NOTHING else.

Only answer with 1 if there are explicit and clear mentions of the subnarrative in the text. If you are slightly unsure, classify as 0.

Key Characteristics of Architecture 1 Prompts:

- **Binary Output:** Strict 0/1 classification with no reasoning required
- **Conservative Bias:** Instructions emphasize answering 0 when uncertain
- **Simplicity:** No chain-of-thought or structured output format
- **Multi-Agent Deployment:** Each narrative/subnarrative has a dedicated agent with its own prompt instantiation

A.2.2 B.2 Architecture 2: Category Classification Prompt

The first stage of our pipeline determines whether the text is about the Ukraine-Russia War (URW) or Climate Change (CC).

Category System Prompt

You are a strict topical classifier. Decide whether the given text is primarily about URW (Ukraine-Russia War topics) or CC (Climate Change topics).

Rules (follow exactly):

- First find the elements that indicate the topic, and reason through them step by step.
- Output EXACTLY one label token enclosed in square brackets on the next line: [URW], [CC], or [Other].

Classification guidance:

- Use [URW] for topics clearly about the Russia-Ukraine conflict.
- Use [CC] for topics clearly about climate change.
- Use [Other] if neither topic is the primary focus.

Exact example outputs (showing allowed formats):

EVIDENCE: short justification

[URW]

EVIDENCE: short justification

[CC]

[Other]

A.2.3 B.3 Architecture 2: Narrative Classification Prompt

After category determination, this prompt classifies the text into specific propaganda narratives. The prompt is dynamically constructed with narrative definitions loaded from CSV files.

Narrative System Prompt (Structure)

You are an expert propaganda narrative analyst with extensive experience in identifying and classifying manipulative communication patterns. Your task is to analyze the given text and identify which specific propaganda narratives are present.

Provide your classification as a semicolon-separated list inside square brackets, e.g. [Narrative A; Narrative B].

AVAILABLE NARRATIVES:

- {Category}: {Narrative Name}
Definition: {narrative definition}
Example: {example text}
Instruction: {specific classification guidance}

[... repeated for each narrative in the category ...]

INSTRUCTIONS

Follow these two steps precisely:

****Step 1: Chain of Thought (Internal Reasoning)****

First, think step-by-step to analyze the provided text.

- Identify key phrases, arguments, and themes.
- For each potential narrative from the list, consider if it applies.
- Find a specific, direct quote from the text that serves as the strongest evidence for each narrative you believe is present.
- Formulate a brief reasoning for why that quote supports the narrative.
- If no narratives apply, conclude that.

****Step 2: Format the Final Output****

After your internal reasoning is complete, provide your final analysis as a single, valid JSON object.

- The JSON should be the *only* thing in your response. Do not include your chain of thought, explanations, or any markdown formatting like '```json'.

OUTPUT FORMAT (JSON Schema)

Your entire response MUST be a single JSON object. ALL fields in the schema below are REQUIRED. Do not omit any fields.

```
{
  "narratives": [
    {
      "narrative_name": "string (The exact name from the list)",
      "evidence_quote": "string (The direct quote from the text you found
                        as evidence)",
      "reasoning": "string (Your justification connecting the quote to
                  the narrative)"
    }
  ]
}
```

- If multiple narratives are found, include one object for each in the `narratives` list.
- If no propaganda narratives are detected, respond with an empty list for the "narratives" key: `{"narratives": []}`.

A.2.4 B.4 Architecture 2: Subnarrative Classification Prompt

For each detected narrative, this prompt further classifies the text into more specific subnarratives. The prompt includes an "Other" category for content that supports the parent narrative but doesn't fit specific subnarrative definitions.

Subnarrative System Prompt (Structure)

You are an expert propaganda narrative analyst with extensive experience in identifying and classifying manipulative communication patterns. This text is known to contain the narrative: {parent_narrative}

Your task is to analyze the given text and identify which specific propaganda subnarratives are present.

A Appendix

Provide your classification as a semicolon-separated list inside square brackets, e.g. [Subnarrative A; Subnarrative B].

AVAILABLE SUBNARRATIVES:

- {Category}: {Narrative}: {Subnarrative Name}
Definition: {subnarrative definition}
Example: {example text}
Instruction: {specific classification guidance}

[... repeated for each subnarrative ...]

- {parent_narrative}: Other
Definition: Use this option if you find statements that clearly support the parent narrative but do not fit into any of the more specific subnarrative definitions provided above. This can be used IN ADDITION to other specific subnarratives.

INSTRUCTIONS

Follow these steps precisely:

****Step 1: Chain of Thought (Internal Reasoning)****

First, think step-by-step to analyze the provided text.

- Given that the text contains the parent narrative, look for more specific themes or arguments that match the subnarrative definitions.
- For each potential subnarrative from the list, consider if it applies.
- Find a specific, direct quote from the text that serves as the strongest evidence for each subnarrative you believe is present.
- Formulate a brief reasoning for why that quote supports the subnarrative.

****Step 2: Check for a Remainder****

After identifying all the specific subnarratives, re-read the text.

Ask yourself: "Are there any other phrases or arguments that support the parent narrative but were NOT used as evidence for the specific

subnarratives I already found?"

****Step 3: Add "Other" if Necessary****

If the answer to Step 2 is YES, you MUST ALSO include the
`{narrative}: Other` subnarrative in your final list.

****Step 4: Format the Final Output****

After your internal reasoning is complete, provide your final analysis
as a single, valid JSON object.

EXAMPLE OF CORRECT LOGIC

- ****Text says:**** "Climate activists are just alarmist children. Their funding is also very suspicious."
- ****Parent Narrative:**** `CC: Criticism of climate movement`
- ****Your Analysis:****
 - "Climate activists are just alarmist children" matches
`...: Climate movement is alarmist`.
 - "Their funding is also very suspicious" supports the parent narrative but doesn't match any specific subnarrative. This is a remainder.
- ****Correct Output:**** A list containing BOTH
`...: Climate movement is alarmist` AND
`CC: Criticism of climate movement: Other`.

Guidelines for using "...: Other"

- ****DO**** include `...: Other` alongside specific subnarratives if there is distinct, leftover evidence supporting the parent narrative.
- ****DO NOT**** include `...: Other` if all the evidence supporting the parent narrative has already been neatly captured by the specific subnarrative(s) you identified.
- ****DO**** use `...: Other` as the sole entry if the text supports the parent narrative but does not align with any of the specific definitions.

OUTPUT FORMAT (JSON Schema)

Your entire response MUST be a single JSON object. ALL fields in the schema below are REQUIRED. Do not omit any fields.

```
{
  "narratives": [
    {
      "subnarrative_name": "string (The exact name from the list)",
      "evidence_quote": "string (The direct quote from the text you found
                        as evidence)",
      "reasoning": "string (Your justification connecting the quote to
                  the narrative)"
    }
  ]
}
```

- If multiple subnarratives are found, include one object for each in the `subnarratives` list.
- If no specific subnarratives are detected, respond with an empty list for the "subnarratives" key: `{ "subnarratives": [] }`.

A.2.5 B.5 Architecture 2: Critic Prompts

The Critic agent validates classifications by checking evidence accuracy, relevance, and completeness.

Narrative Critic Prompt

You are a meticulous and skeptical editor. Your task is to evaluate a classification of propaganda narratives applied to a text. You must be extremely strict. The classification is only valid if every narrative is strongly and explicitly supported by the provided evidence from the text.

You will be given the original text and the classification analysis in JSON format. The analysis includes the narrative name, a quote for evidence, and reasoning.

Here are the narratives that were available for classification:

{list of narratives}

EVALUATION CRITERIA (Apply Strictly):

1. ****Evidence Accuracy:**** Is the `evidence\_quote` an exact, verbatim quote from the original text? Of course if the quote is from the text but there was just a small formatting / typography issue it is still fine (not the same unicode character used for example).
2. ****Relevance of Evidence:**** Does the `evidence\_quote` DIRECTLY support the `narrative\_name`? The connection must not be a stretch or require deep interpretation. If the link is weak, the classification is invalid.
3. ****Completeness:**** Does the analysis miss any other obvious, high-confidence narratives that are clearly present in the text? If so, the classification is invalid.

OUTPUT FORMAT

Provide your evaluation as a single, valid JSON object conforming to the specified schema. Do not include any other text or formatting.

Subnarrative Critic Prompt

You are a meticulous and skeptical editor. Your task is to evaluate a classification of propaganda subnarratives applied to a text. The list was generated under the assumption that a specific parent narrative is present. You must be extremely strict. The classification is only valid if every subnarrative is strongly and explicitly supported by the provided evidence from the text.

You will be given the original text and the classification analysis in JSON format. The analysis includes the subnarrative name, a quote for evidence, and reasoning.

Here is the list of subnarratives that were available to choose from:

{list of subnarratives}

EVALUATION CRITERIA (Apply Strictly):

1. ****Evidence Accuracy:**** Is the `evidence\_quote` an exact, verbatim quote from the original text?
2. ****Relevance of Evidence:**** Does the `evidence\_quote` DIRECTLY and OBVIOUSLY support the `subnarrative\_name`? The connection must not be a stretch or require deep interpretation. If the link is weak, the classification is invalid.
3. ****Completeness:**** Does the analysis miss any other obvious, high-confidence subnarratives that are clearly present in the text? If so, the classification is invalid.

OUTPUT FORMAT

Provide your evaluation as a single, valid JSON object conforming to the specified schema. Do not include any other text or formatting.

A.2.6 B.6 Architecture 2: Refinement Prompts

When the Critic identifies issues, these prompts guide the Actor to revise the classification.

Refinement Prompt Structure

You previously analyzed a text, but your analysis had flaws. A meticulous editor has provided the following feedback. Your task is to re-analyze the text, incorporating this feedback to produce a new, corrected classification.

EDITOR'S FEEDBACK TO CORRECT:

{critic's feedback}

ORIGINAL TASK AND DEFINITIONS (Apply these again with the feedback in mind):

{original classification prompt with all definitions}

A.2.7 B.7 Architecture 2: Text Cleaning Prompt

Before classification, raw web text is cleaned to remove navigation elements and boilerplate.

Cleaning System Prompt

You are a precise text cleaner. Your job is to clean raw text scraped from the web by removing UI noise and boilerplate while preserving the article's content.

STRICT RULES (follow exactly):

- REMOVE: navigation menus, cookie banners, sign-up banners, button labels (e.g., 'Accept', 'Subscribe', 'Read more'), share widgets, headers/footers, unrelated CTAs, legal disclaimers, pagination artifacts, and unrelated links.
- KEEP: the main article or post content only. Preserve sentence order, punctuation, and language.
- DO NOT paraphrase or summarize. Do not add or remove meaning.
- OUTPUT: Return ONLY the cleaned text with no additional commentary, headings, or JSON.

Bibliography

- [CSB25] Jan Cegin, Jakub Simko, and Peter Brusilovsky. “LLMs vs Established Text Augmentation Techniques for Classification: When do the Benefits Outweight the Costs?” In: *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*. Ed. by Luis Chiruzzo, Alan Ritter, and Lu Wang. Albuquerque, New Mexico: Association for Computational Linguistics, Apr. 2025, pp. 10476–10496. ISBN: 979-8-89176-189-6. DOI: 10.18653/v1/2025.naacl-long.526. URL: <https://aclanthology.org/2025.naacl-long.526/> (cit. on pp. 10, 13).
- [CMM11] E. A. Cherman, M. C. Monard, and J. Metz. “Multi-label Problem Transformation Methods: a Case Study”. In: *CLEI Electronic Journal* 14.1 (Apr. 2011). DOI: 10.19153/cleiej.14.1.4. URL: <https://doi.org/10.19153/cleiej.14.1.4> (cit. on p. 5).
- [CIN24] Alexander Chernyavskiy, Dmitry Ilvovsky, and Preslav Nakov. “Unleashing the Power of Discourse-Enhanced Transformers for Propaganda Detection”. In: *Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers)*. Ed. by Yvette Graham and Matthew Purver. St. Julian’s, Malta: Association for Computational Linguistics, Mar. 2024, pp. 1452–1462. DOI: 10.18653/v1/2024.eacl-long.87. URL: <https://aclanthology.org/2024.eacl-long.87/> (cit. on p. 14).
- [CIN20] Anton Chernyavskiy, Dmitry Ilvovsky, and Preslav Nakov. “Aschern at SemEval-2020 Task 11: It Takes Three to Tango: RoBERTa, CRF, and Transfer Learning”. In: *Proceedings of the Fourteenth Workshop on Semantic Evaluation*. Ed. by Aurelie Herbelot et al. Barcelona (online): International Committee for Computational Linguistics, Dec. 2020, pp. 1462–1468. DOI: 10.18653/v1/2020.semeval-1.191. URL: <https://aclanthology.org/2020.semeval-1.191/> (cit. on p. 14).

- [CMM24] Shreenaga Chikoti, Shrey Mehta, and Ashutosh Modi. “IITK at SemEval-2024 Task 4: Hierarchical Embeddings for Detection of Persuasion Techniques in Memes”. In: *Proceedings of the 18th International Workshop on Semantic Evaluation (SemEval-2024)*. Ed. by Atul Kr. Ojha et al. Mexico City, Mexico: Association for Computational Linguistics, June 2024, pp. 1779–1787. DOI: 10.18653/v1/2024.semeval-1.252. URL: <https://aclanthology.org/2024.semeval-1.252/> (cit. on p. 15).
- [Da +20] Giovanni Da San Martino et al. *SemEval-2020 Task 11: Detection of Propaganda Techniques in News Articles*. <https://propaganda.qcri.org/semeval2020-task11/>. SemEval-2020 shared task. 2020 (cit. on p. 14).
- [Da +23] Giovanni Da San Martino et al. *SemEval-2023 Task 3: Detecting the Genre, the Framing, and the Persuasion Techniques in Online News in a Multi-lingual Setup*. <https://propaganda.math.unipd.it/semeval2023task3/>. SemEval-2023 shared task. 2023 (cit. on p. 15).
- [Dev+19] Jacob Devlin et al. “BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding”. en. In: *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*. Minneapolis, Minnesota: Association for Computational Linguistics, 2019, pp. 4171–4186. DOI: 10.18653/v1/N19-1423. URL: <http://aclweb.org/anthology/N19-1423> (cit. on p. 2).
- [Dim+24] Dimitar Dimitrov et al. *SemEval-2024 Task 4: Multilingual Detection of Persuasion Techniques in Memes*. <https://propaganda.math.unipd.it/semeval2024task4/>. SemEval-2024 shared task. 2024 (cit. on p. 15).
- [EN25] Mohamed - Nour Eljadiri and Diana Nurbakova. “Team INSALyon2 at SemEval-2025 Task 10: A Zero-shot Agentic Approach to Text Classification”. In: *Proceedings of the 19th International Workshop on Semantic Evaluation (SemEval-2025)*. Ed. by Sara Rosenthal et al. Vienna, Austria: Association for Computational Linguistics, July 2025, pp. 965–980. ISBN: 979-8-89176-273-2. URL: <https://aclanthology.org/2025.semeval-1.129/> (cit. on pp. 10, 31).
- [Fan+25] Enfa Fane et al. *Fane at SemEval-2025 Task 10: Zero-Shot Entity Framing with Large Language Models*. arXiv preprint arXiv:2504.20469. 2025. URL: <https://arxiv.org/abs/2504.20469> (cit. on pp. 17–19).

- [F25] M. Fenu and ... “DEMON at SemEval-2025 Task 10: Fine-tuning LLaMA-3 for Multilingual Entity Framing”. In: *Proceedings of the 19th International Workshop on Semantic Evaluation (SemEval-2025)*. 2025. URL: <https://aclanthology.org/2025.semeval-1.192/> (cit. on pp. 17, 18).
- [GA24] Omid Ghahroodi and Ehsaneddin Asgari. “HierarchyEverywhere at SemEval-2024 Task 4: Detection of Persuasion Techniques in Memes Using Hierarchical Text Classifier”. In: *Proceedings of the 18th International Workshop on Semantic Evaluation (SemEval-2024)*. Mexico City, Mexico: Association for Computational Linguistics, June 2024, pp. 1727–1732. DOI: 10.18653/v1/2024.semeval-1.247. URL: <https://aclanthology.org/2024.semeval-1.247> (cit. on p. 15).
- [GZ24] Anna V. Glazkova and Olga V. Zakharova. *Evaluating LLM Prompts for Data Augmentation in Multi-label Classification of Ecological Texts*. 2024. arXiv: 2411.14896 [cs.CL]. URL: <https://arxiv.org/abs/2411.14896> (cit. on p. 10).
- [Gon+20] Jibing Gong et al. “Hierarchical Graph Transformer-Based Deep Learning Model for Large-Scale Multi-Label Text Classification”. In: *IEEE Access* 8 (2020), pp. 30885–30896. DOI: 10.1109/ACCESS.2020.2973121 (cit. on p. 2).
- [Goo24] Google Research. *Introducing Gemini*. <https://blog.google/technology/ai/introducing-gemini/>. Google Research blog post; accessed 2025-09-24. 2024 (cit. on p. 55).
- [He+21] Pengcheng He et al. “DeBERTa: Decoding-enhanced BERT with Disentangled Attention”. In: *International Conference on Learning Representations*. 2021. URL: <https://openreview.net/forum?id=XPZiaotutsD> (cit. on pp. 24, 25).
- [Hro+23] Timo Hromadka et al. “KInITVeraAI at SemEval-2023 Task 3: Simple yet Powerful Multilingual Fine-Tuning for Persuasion Techniques Detection”. In: *Proceedings of the 17th International Workshop on Semantic Evaluation (SemEval-2023)*. Ed. by Atul Kr. Ojha et al. Toronto, Canada: Association for Computational Linguistics, July 2023, pp. 629–637. DOI: 10.18653/v1/2023.semeval-1.86. URL: <https://aclanthology.org/2023.semeval-1.86/> (cit. on p. 15).
- [Hu+25] W. Hu et al. “A Survey of Multi-Label Text Classification Under Few-Shot Scenarios”. In: *Applied Sciences* 15 (2025), p. 8872. DOI: 10.3390/app15168872. URL: <https://doi.org/10.3390/app15168872> (cit. on p. 1).

- [Hua+24] S. Huang et al. “Application of Label Correlation in Multi-Label Classification: A Survey”. In: *Applied Sciences* 14 (2024), p. 9034. DOI: 10.3390/app14199034. URL: <https://doi.org/10.3390/app14199034> (cit. on p. 1).
- [Hua+21] Yi Huang et al. “Balancing Methods for Multi-label Text Classification with Long-Tailed Class Distribution”. In: *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*. Ed. by Marie-Francine Moens et al. Online and Punta Cana, Dominican Republic: Association for Computational Linguistics, Nov. 2021, pp. 8153–8161. DOI: 10.18653/v1/2021.emnlp-main.643. URL: <https://aclanthology.org/2021.emnlp-main.643/> (cit. on pp. 11, 12).
- [Jur+20] Dawid Jurkiewicz et al. “ApplicaAI at SemEval-2020 Task 11: On RoBERTa-CRF, Span CLS and Whether Self-Training Helps Them”. In: *Proceedings of the Fourteenth Workshop on Semantic Evaluation*. Ed. by Aurelie Herbelot et al. Barcelona (online): International Committee for Computational Linguistics, Dec. 2020, pp. 1415–1424. DOI: 10.18653/v1/2020.semeval-1.187. URL: <https://aclanthology.org/2020.semeval-1.187/> (cit. on p. 14).
- [Lan24a] LangChain AI. *LangGraph: Build resilient language agents as graphs*. Accessed: 2025-09-19. 2024. URL: <https://github.com/langchain-ai/langgraph> (cit. on pp. 36, 42).
- [Lan24b] LangChain AI. *LangSmith: Developer platform for building reliable LLM applications*. Accessed: 2025-09-19. 2024. URL: <https://www.langchain.com/langsmith> (cit. on pp. 39, 42).
- [Li+23] Dan Li et al. “Enhancing Extreme Multi-Label Text Classification: Addressing Challenges in Model, Data, and Evaluation”. In: *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: Industry Track*. Ed. by Mingxuan Wang and Imed Zitouni. Singapore: Association for Computational Linguistics, Dec. 2023, pp. 313–321. DOI: 10.18653/v1/2023.emnlp-industry.30. URL: <https://aclanthology.org/2023.emnlp-industry.30/> (cit. on pp. 11, 12).
- [Li+24] Dongyuan Li et al. *A Survey on Deep Active Learning: Recent Advances and New Frontiers*. 2024. arXiv: 2405.00334v2 [cs.LG]. URL: <https://arxiv.org/abs/2405.00334v2> (cit. on p. 12).

- [Li+21] Irene Li et al. “Heterogeneous Graph Neural Networks for Multi-label Text Classification”. In: *Lecture Notes in Computer Science*. arXiv:2103.14620. 2021. DOI: 10.48550/ARXIV.2103.14620. URL: <https://arxiv.org/abs/2103.14620> (cit. on p. 8).
- [Liu+23] Rundong Liu et al. *Recent Advances in Hierarchical Multi-label Text Classification: A Survey*. 2023. arXiv: 2307.16265 [cs.CL]. URL: <https://arxiv.org/abs/2307.16265> (cit. on pp. 1, 2).
- [Liu+24] Zequan Liu et al. “ALoRA: Allocating Low-Rank Adaptation for Fine-tuning Large Language Models”. In: *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Long Papers*. Mexico City, Mexico, June 2024, pp. 622–641. DOI: 10.18653/v1/2024.naacl-long.35. URL: <https://aclanthology.org/2024.naacl-long.35> (cit. on p. 12).
- [Luq+19] Amalia Luque et al. “The impact of class imbalance in classification performance metrics based on the binary confusion matrix”. In: *Pattern Recognit.* 91 (2019), pp. 216–231. DOI: 10.1016/J.PATCOG.2019.02.023 (cit. on p. 11).
- [Mod+23] Arkadiusz Modzelewski et al. “DSHacker at SemEval-2023 Task 3: Genres and Persuasion Techniques Detection with Multilingual Data Augmentation through Machine Translation and Text Generation”. In: *Proceedings of the 17th International Workshop on Semantic Evaluation (SemEval-2023)*. Ed. by Atul Kr. Ojha et al. Toronto, Canada: Association for Computational Linguistics, July 2023, pp. 1582–1591. DOI: 10.18653/v1/2023.semeval-1.218. URL: <https://aclanthology.org/2023.semeval-1.218/> (cit. on p. 15).
- [Nak+25] Preslav Nakov et al. “BERTastic at SemEval-2025 Task 10: Fine-tuned Transformers for Multilingual Narrative Analysis”. In: *Proceedings of the 19th International Workshop on Semantic Evaluation (SemEval-2025)*. 2025. URL: <https://aclanthology.org/2025.semeval-1.177/> (cit. on p. 18).
- [Pen+21] Hao Peng et al. “Hierarchical Taxonomy-Aware and Attentional Graph Capsule RCNNs for Large-Scale Multi-Label Text Classification”. In: *IEEE Transactions on Knowledge and Data Engineering* 33.6 (2021), pp. 2505–2519. DOI: 10.1109/TKDE.2019.2956257 (cit. on p. 2).

- [PM25] Jakub Piskorski, Tarek Mahmoud, and ... “SemEval-2025 Task 10: Multilingual Characterization and Extraction of Narratives from Online News”. In: *Proceedings of the 19th International Workshop on Semantic Evaluation (SemEval-2025)*. ACL Anthology. 2025. URL: <https://aclanthology.org/2025.semeval-1.331/> (cit. on pp. 17–20).
- [Pis+25] Jakub Piskorski et al. “SemEval-2025 Task 10: Multilingual Characterization and Extraction of Narratives from Online News”. In: *Proceedings of the 19th International Workshop on Semantic Evaluation (SemEval 2025)*. Vienna, Austria, 2025 (cit. on pp. 1, 15).
- [P25] P. Premnath and ... “TECHSSN at SemEval-2025 Task 10: A Comparative Study for Narrative Extraction”. In: *Proceedings of the 19th International Workshop on Semantic Evaluation (SemEval-2025)*. 2025. URL: <https://aclanthology.org/2025.semeval-1.286/> (cit. on p. 18).
- [Raz+24] Olesya Razuvayevskaya et al. “Comparison between parameter-efficient techniques and full fine-tuning: A case study on multilingual news article classification”. In: *PLOS ONE* 19.5 (2024), e0301738. DOI: 10.1371/journal.pone.0301738. URL: <https://doi.org/10.1371/journal.pone.0301738> (cit. on p. 12).
- [Rea+11] J. Read et al. “Classifier Chains for Multi-label Classification”. In: *Machine Learning* 85.3 (2011), pp. 333–359. DOI: 10.7007/s10994-011-5256-5. URL: <https://doi.org/10.1007/s10994-011-5256-5> (cit. on p. 5).
- [Rea+21] J. Read et al. “Classifier Chains: A Review and Perspectives”. In: *Journal of Artificial Intelligence Research* 70 (2021), pp. 683–718. DOI: 10.1613/jair.1.12376. URL: <https://doi.org/10.1613/jair.1.12376> (cit. on p. 5).
- [RFR22] Miguel Romero, Jorge Finke, and Camilo Rocha. “A top-down supervised learning approach to hierarchical multi-label classification in networks”. In: *Applied Network Science* 7.1 (2022), p. 8. DOI: 10.1007/s41109-022-00445-3. URL: <https://doi.org/10.1007/s41109-022-00445-3> (cit. on p. 7).
- [RN25] Egil Rønningstad and Gaurav Negi. *LTG at SemEval-2025 Task 10: Optimizing Context for Classification of Narrative Roles*. arXiv preprint arXiv:2506.05976. 2025. URL: <https://arxiv.org/abs/2506.05976> (cit. on pp. 18, 19).

- [SC22] Mobashir Sadat and Cornelia Caragea. “Hierarchical Multi-Label Classification of Scientific Documents”. en. In: *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*. Abu Dhabi, United Arab Emirates: Association for Computational Linguistics, 2022, pp. 8923–8937. DOI: 10.18653/v1/2022.emnlp-main.610. URL: <https://aclanthology.org/2022.emnlp-main.610> (cit. on p. 2).
- [Sem25a] SemEval-2025 Task 10 Organizers. *SemEval 2025 Task 10 Leaderboard (official results)*. <https://propaganda.math.unipd.it/semEval2025task10/leaderboard.php>. Accessed 2025-09-16. 2025 (cit. on p. 19).
- [Sem25b] SemEval-2025 Task 10 Organizers. *SemEval 2025 Task 10: Multilingual Characterization and Extraction of Narratives from Online News (task webpage)*. <https://propaganda.math.unipd.it/semEval2025task10/>. Accessed 2025-09-16. 2025 (cit. on pp. 18, 19).
- [Sha+18] Jincheng Shan et al. “Co-learning Binary Classifiers for LP-Based Multi-label Classification”. en. In: *Intelligence Science and Big Data Engineering*. Ed. by Yuxin Peng et al. Vol. 11266. Cham: Springer International Publishing, 2018, pp. 443–453. ISBN: 9783030026974 9783030026981. DOI: 10.1007/978-3-030-02698-1_39. URL: https://link.springer.com/10.1007/978-3-030-02698-1_39 (cit. on p. 2).
- [SSB25a] Iknoor Singh, Carolina Scarton, and Kalina Bontcheva. *GateNLP at SemEval-2025 Task 10: Hierarchical Three-Step Prompting for Multilingual Narrative Classification*. arXiv preprint arXiv:2505.22867. 2025. URL: <https://arxiv.org/abs/2505.22867> (cit. on pp. 2, 17–19, 67).
- [SSB25b] Iknoor Singh, Carolina Scarton, and Kalina Bontcheva. “GateNLP at SemEval-2025 Task 10: Hierarchical Three-Step Prompting for Multilingual Narrative Classification”. In: *Proceedings of the 19th International Workshop on Semantic Evaluation (SemEval-2025)*. Ed. by Sara Rosenthal et al. Vienna, Austria: Association for Computational Linguistics, July 2025, pp. 148–154. ISBN: 979-8-89176-273-2. URL: <https://aclanthology.org/2025.semEval-1.21/> (cit. on p. 15).
- [SSB25c] Iknoor Singh, Carolina Scarton, and Kalina Bontcheva. *GateNLP H3Prompt System Code Repository*. <https://github.com/GateNLP/semEval2025-task10>. GitHub repository for hierarchical three-step prompting system. 2025 (cit. on p. 2).

- [Su+24] Tong Su et al. “Unlocking Parameter-Efficient Fine-Tuning for Low-Resource Language Translation”. In: *Findings of the Association for Computational Linguistics: NAACL 2024*. Ed. by Kevin Duh, Helena Gomez, and Steven Bethard. Mexico City, Mexico: Association for Computational Linguistics, June 2024, pp. 4217–4225. DOI: 10.18653/v1/2024.findings-naacl.263. URL: <https://aclanthology.org/2024.findings-naacl.263/> (cit. on p. 12).
- [Suc+14] L. Sucar et al. “Multi-label classification with Bayesian network-based chain classifiers”. In: *Pattern Recognit. Lett.* 41 (2014), pp. 14–22. DOI: 10.1016/J.PATREC.2013.11.007 (cit. on pp. 4, 5).
- [Tha+20] F. Thabtah et al. “Data imbalance in classification: Experimental evaluation”. In: *Inf. Sci.* 513 (2020), pp. 429–441. DOI: 10.1016/j.ins.2019.11.004 (cit. on p. 11).
- [TS18] Vaishali S. Tidake and Shirish S. Sane. “Multi-label Classification: a survey”. In: *International Journal of Engineering & Technology* 7.4.19 (2018), p. 1045. DOI: 10.14419/ijet.v7i4.19.28284. URL: <https://doi.org/10.14419/ijet.v7i4.19.28284> (cit. on pp. 1, 2).
- [Vas+17] Ashish Vaswani et al. “Attention is all you need”. In: *Advances in Neural Information Processing Systems*. 2017, pp. 5998–6008 (cit. on p. 24).
- [Wan+23] Fengjun Wang et al. “Text2Topic: Multi-Label Text Classification System for Efficient Topic Detection in User Generated Content with Zero-Shot Capabilities”. In: *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: Industry Track*. Ed. by Mingxuan Wang and Imed Zitouni. Singapore: Association for Computational Linguistics, Dec. 2023, pp. 93–103. DOI: 10.18653/v1/2023.emnlp-industry.10. URL: <https://aclanthology.org/2023.emnlp-industry.10/> (cit. on p. 9).
- [WDH24] Kunze Wang, Yihao Ding, and Soyeon Caren Han. *Graph Neural Networks for Text Classification: A Survey*. 2024. DOI: <https://doi.org/10.1007/s10462-024-10808-0>. arXiv: 2304.11534 [cs.CL]. URL: <https://arxiv.org/abs/2304.11534> (cit. on p. 8).
- [WCB18] Jonatas Wehrmann, Ricardo Cerri, and Rodrigo Barros. “Hierarchical Multi-Label Classification Networks”. In: *Proceedings of the 35th International Conference on Machine Learning*. Ed. by Jennifer Dy and Andreas Krause. Vol. 80. Proceedings of Machine Learning Research. PMLR, July 2018, pp. 5075–5084. URL: <http://proceedings.mlr.press/v80/wehrmann18a.html> (cit. on p. 7).

- [Wen+20] Wei Weng et al. “Label Specific Features-Based Classifier Chains for Multi-Label Classification”. In: *IEEE Access* 8 (2020), pp. 51265–51275. ISSN: 2169-3536. DOI: 10.1109/ACCESS.2020.2980551. URL: <https://ieeexplore.ieee.org/document/9035463/> (cit. on p. 2).
- [WCA23] Chenxi Whitehouse, Monojit Choudhury, and Alham Fikri Aji. *LLM-powered Data Augmentation for Enhanced Cross-lingual Performance*. 2023. arXiv: 2305.14288 [cs.CL]. URL: <https://arxiv.org/abs/2305.14288> (cit. on p. 13).
- [Wol+20] Thomas Wolf et al. “Transformers: State-of-the-Art Natural Language Processing”. In: *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*. Online: Association for Computational Linguistics, Oct. 2020, pp. 38–45. DOI: 10.18653/v1/2020.emnlp-demos.6. URL: <https://www.aclweb.org/anthology/2020.emnlp-demos.6> (cit. on p. 41).
- [Wu+24] Qingyun Wu et al. “AutoGen: Enabling Next-Gen LLM Applications via Multi-Agent Conversation”. In: *LLM Agents Workshop, ICLR 2024*. Best Paper award. 2024. eprint: arXiv:2308.08155. URL: <https://arxiv.org/abs/2308.08155> (cit. on p. 31).
- [Wun+24] Julia Wunderle et al. “OtterlyObsessedWithSemantics at SemEval-2024 Task 4: Developing a Hierarchical Multi-Label Classification Head for Large Language Models”. In: *Proceedings of the 18th International Workshop on Semantic Evaluation (SemEval-2024)*. Ed. by Atul Kr. Ojha et al. Mexico City, Mexico: Association for Computational Linguistics, June 2024, pp. 602–612. DOI: 10.18653/v1/2024.semeval-1.90. URL: <https://aclanthology.org/2024.semeval-1.90/> (cit. on p. 15).
- [Xu+21] Linli Xu et al. “Hierarchical Multi-label Text Classification with Horizontal and Vertical Category Correlations”. In: *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*. Ed. by Marie-Francine Moens et al. Online and Punta Cana, Dominican Republic: Association for Computational Linguistics, Nov. 2021, pp. 2459–2468. DOI: 10.18653/v1/2021.emnlp-main.190. URL: <https://aclanthology.org/2021.emnlp-main.190/> (cit. on p. 6).
- [Yan+24] Ruichao Yang et al. “Reinforcement Tuning for Detecting Stances and Debunking Rumors Jointly with Large Language Models”. In: *Findings of the Association for Computational Linguistics: ACL 2024*. Ed. by Lun-Wei Ku, Andre Martins, and Vivek Srikumar. Bangkok, Thailand: Association for Computational Linguistics,

- Aug. 2024, pp. 13423–13439. DOI: 10.18653/v1/2024.findings-acl.796. URL: <https://aclanthology.org/2024.findings-acl.796/> (cit. on p. 10).
- [YQ25] Arjumand Younus and Muhammad Atif Qureshi. “nlptuducd at SemEval-2025 Task 10: Narrative Classification as a Retrieval Task through Story Embeddings”. In: *Proceedings of the 19th International Workshop on Semantic Evaluation (SemEval-2025)*. Ed. by Sara Rosenthal et al. Vienna, Austria: Association for Computational Linguistics, July 2025, pp. 1742–1746. ISBN: 979-8-89176-273-2. URL: <https://aclanthology.org/2025.semeval-1.228/> (cit. on p. 15).
- [Yua+24] Ling Yuan et al. “Research of Multi-Label Text Classification based on Label Attention and Correlation Networks”. In: *PLOS ONE* 19.9 (2024), e0311305. DOI: 10.1371/journal.pone.0311305. URL: <https://doi.org/10.1371/journal.pone.0311305> (cit. on p. 11).
- [Zan+24] A. Zangari et al. “Hierarchical Text Classification and Its Foundations: A Review of Current Research”. In: *Electronics* 13.7 (2024), p. 1199. DOI: 10.3390/electronics13071199. URL: <https://doi.org/10.3390/electronics13071199> (cit. on pp. 1, 6).
- [Zha+18a] M.-L. Zhang et al. “Binary relevance for multi-label learning: an overview”. In: *Frontiers of Computer Science* 12.2 (2018), pp. 191–202. DOI: 10.1007/s11704-017-7031-7. URL: <https://doi.org/10.1007/s11704-017-7031-7> (cit. on p. 5).
- [Zha+18b] Min-Ling Zhang et al. “Binary relevance for multi-label learning: an overview”. en. In: *Frontiers of Computer Science* 12.2 (Apr. 2018), pp. 191–202. ISSN: 2095-2228, 2095-2236. DOI: 10.1007/s11704-017-7031-7. URL: <http://link.springer.com/10.1007/s11704-017-7031-7> (cit. on pp. 2, 4, 31).
- [Zho+20] Jie Zhou et al. “Hierarchy-Aware Global Model for Hierarchical Text Classification”. In: *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*. Ed. by Dan Jurafsky et al. Online: Association for Computational Linguistics, July 2020, pp. 1106–1117. DOI: 10.18653/v1/2020.acl-main.104. URL: <https://aclanthology.org/2020.acl-main.104/> (cit. on pp. 7, 8).

Eidesstattliche Erklärung

Hiermit versichere ich, dass ich diese Masterarbeit selbstständig und ohne Benutzung anderer als der angegebenen Quellen und Hilfsmittel angefertigt habe und alle Ausführungen, die wörtlich oder sinngemäß übernommen wurden, als solche gekennzeichnet sind, sowie, dass ich die Masterarbeit in gleicher oder ähnlicher Form noch keiner anderen Prüfungsbehörde vorgelegt habe.

Passau, October 7, 2025

Nour Eljadiri

Matrikelnummer: 118321