**Eastern Michigan University**

**GameAbove College of Engineering & Technology**

# Title: Mechatronic Components and System Integration in a Humanoid Robot (Tesla Optimus)

**Author: Unais Ali**

**Co-Author: Syeda Kashaf Kulsoom**

# Contents

**Executive Summary** ..... 3

**1. Introduction** ..... 4

**2. Components of a Mechatronic System** ..... 4

**2.1. Actuators** ..... 4

**2.2. Sensors** ..... 5

**2.3. Digital Control Devices** ..... 5

**3. A humanoid robot is a mechatronic system** ..... 7

**3.1. Mechanical powertrain and actuation** ..... 8

**3.2. Sensing and perception** ..... 9

**3.3. Digital control devices and communication** ..... 9

**3.4. Tasks and control modes as evidence of mechatronic integration** ..... 11

**4. Tesla Bot (Optimus) as a Mechatronic System** ..... 13

**4.1. Mechanical powertrain and actuation** ..... 13

**4.2. Sensing and perception** ..... 14

**4.3. Digital control devices and communication** ..... 16

**4.4. Tasks and control modes as evidence of mechatronic integration** ..... 17

**5. Discussion** ..... 18

**6. Conclusion** ..... 19

**References** ..... 20

# Executive Summary

Mechatronic systems integrate mechanical structures, actuators, sensors, and digital control to achieve intelligent, precise, and safe operation [1,2,3]. This report identifies and describes the three core components of a typical mechatronic system, namely actuators, sensors, and digital control devices, and then uses Tesla's Optimus humanoid robot as the example machine to explain why it qualifies as a mechatronic system [2,4,5,6]. Drawing on industrial robot reference architectures and humanoid control pipelines, we show how compact electric joint modules, multimodal sensing (encoders, IMUs, force and pressure sensing), and layered control (servo drives with field-oriented control and whole-body impedance or optimization layers) work together [1,4,7,8,9,10]. The figures support and illustrate these points, with explicit placement indicated in the text.

# 1. Introduction

Mechatronics is the synergistic integration of mechanical design, electronics, sensing, and computer control to create functional and intelligent systems. Industrial manipulators and humanoid robots are archetypal examples. They combine electric motors and transmissions, precision feedback sensors, and real time control algorithms to execute complex tasks such as assembly, force regulated contact, and locomotion with reliability and safety. In modern production environments, continuous motion control works alongside discrete sequencing and safety interlocks, while standards and interoperable networks enable integration into smart manufacturing.

This report explicitly identifies and describes actuators, sensors, and digital control devices (3.1–3.3), then uses Tesla's Optimus to demonstrate, with an accompanying schematic and figure references, why it is a mechatronic system [1–4,7–10,15].

# 2. Components of a Mechatronic System

### 2.1. Actuators

- Electric rotary actuators are usually permanent magnet synchronous motors or brushless DC motors driven by servo inverters implementing field-oriented control (FOC) for high-bandwidth torque regulation [4,7,8]. High reduction transmissions (harmonic/strain wave, cycloidal, planetary) convert motor speed to joint torque with low backlash for precise positioning; brakes on selected axes allow safe holding under power loss [2,4,6].

- Linear and specialized actuators such as ball screws, voice coils, and solenoids appear in grippers, end effectors, and brakes; series elastic or integrated torque-sensing actuators add compliance and improve safety during interaction [2,5,6,9].
- The brakes and clutches provide electromechanical holding for static safety and emergency stops; friction and compliance are modeled to achieve accurate low-speed control [8,10].

**2.2. Sensors**

- Joint sensing uses absolute/incremental encoders or resolvers for position and speed feedback [4,7]. Force and interaction sensing includes six-axis force/torque sensors, foot pressure arrays, and joint torque estimation from motor currents to enable impedance/admittance control and safe contact [2,7,9,10]. Inertial and pose sensing with IMUs provides angular rates and linear accelerations for attitude estimation, balance, and disturbance rejection [2,7].
- Environmental sensing includes vision (RGB/depth), proximity, and tactile sensing to support manipulation and navigation; in industrial contexts, AIDC via barcodes, RFID, and machine vision supports identification and tracking [11,12].
- Health and safety sensing includes temperature, current, voltage, and battery sensing to protect drives and power systems, as well as limit and home switches to enforce motion bounds [4,8,12].

**2.3. Digital Control Devices**

- Servo drives on each joint run FOC, read encoders and currents, regulate torque/speed/position, and implement safety functions such as Safe Torque Off (STO)

[4,7,8]. A central real-time controller executes kinematics/dynamics, whole-body control (impedance and optimization-based QP), trajectory generation, state estimation, and supervisory safety logic [2,7,9,10].

- Communication networks use deterministic fieldbuses such as EtherCAT for synchronized low-latency exchange among sensors, drives, and controllers; higher-level messaging supports diagnostics and enterprise integration [4,11,12].
- The software stack includes estimation (Kalman/complementary filters), compensation for friction/gravity/compliance, fault detection and derating, task planners, and safety monitors [7–10,12–14].

See Figure 1 for the overall mechatronic architecture and component locations.




***Figure 1.*** *Canonical industrial robot mechatronic architecture with controller cabinet (servo drives, PLC/IPC), power and fieldbus, joint actuators and encoders, wrist force/torque sensor, end effector, and safety systems (E-stop, STO, limits, interlocks, thermal). Illustrates typical components and signal flows [1,4].*

# 3. A humanoid robot is a mechatronic system

Humanoid robots integrate the above components tightly: compact joint modules with motors, high-ratio transmissions, brakes, and encoders; sensing spanning joint encoders, IMUs, force/pressure sensors, and vision; and control that combines low-level servo regulation with high-level whole-body coordination under strict safety [2,5–7,9,10]. Deterministic networking synchronizes all elements in closed loop [4,11,12].

### 3.1. Mechanical powertrain and actuation

A representative humanoid such as Optimus employs permanent magnet or brushless motors at hips, knees, ankles, shoulders, and elbows, with high reduction transmissions (harmonic/cycloidal) to achieve high joint torque at low speed [2,5,6].

Many joints integrate the motor, geartrain, motor-side and joint-side encoders, an electromechanical brake, and a drive/controller PCB for compactness and robustness, enabling precise positioning, smooth low-speed torque, and safe holding [2,6,8]. See Figure 2 for an integrated humanoid joint module example illustrating these components [2,5,6,15]




***Figure 2.*** *Integrated humanoid joint module: mechanical stack (motor, transmission, encoders, brake) linked to inverter/servo drive electronics and control/I/O panel, showing power, signals, safety, thermal, and feedback connections.*

### 3.2. Sensing and perception

- Joint encoders provide posture and velocity feedback at each degree of freedom [4,7].
- IMUs estimate base orientation and linear/angular rates, supporting balance and locomotion [2,7].
- Foot pressure arrays and optional wrist F/T sensors quantify contact forces; motor-current-based torque estimation complements external force sensing [2,9,10].
- Motor current, voltage, and temperature sensors support torque estimation and thermal protection [4,8].
- Vision and tactile sensing enable object detection, grasping, and compliant manipulation; industrial AIDC complements perception for work tracking [11,12].

### 3.3. Digital control devices and communication

Joint servo drives close current and velocity loops with FOC and enforce safety limits and STO. A central real-time controller executes whole-body control (QP with constraints), impedance/admittance control for interaction, trajectory generation, state estimation via sensor fusion, and supervisory safety (limits, stops, thermal derating, fault monitors) [7–10].




***Figure 3***. *Controller cabinet and safety architecture: servo drives with PLC/IPC, STO and interlocks, fieldbus/power routing to joint motors, encoders, wrist F/T sensor, end effector, and E-stop within the mechanical structure.*

A deterministic fieldbus such as EtherCAT synchronizes setpoints and feedback at 1–2 kHz; higher-level channels carry diagnostics and planning data [4,11,12]. The overall control architecture is illustrated in Figure 4, highlighting the left-to-right pipeline from sensing and state estimation through whole-body control and safety to synchronized fieldbus setpoints [4,7,8].




***Figure 4****. showing the sensing-to-actuation pipeline and synchronized fieldbus setpoints*

### 3.4. Tasks and control modes as evidence of mechatronic integration

- Locomotion including walking, stairs, slopes, and turning uses IMU data, foot sensors, and encoders for state estimation; servo drives regulate joint torques while whole-body controllers maintain stability and manage contact constraints [2,7,9].
- Squatting, lifting, pushing, and pulling require high peak joint torque at hips, knees, and ankles; friction compensation and impedance control regulate interaction forces safely [8–10].
- Tool use and manipulation depend on vision plus wrist/hand sensing for grasp, force-limited insertion, and surface interactions; sensorless torque and stiffness estimation from drive signals can tune impedance on the fly [9,10,14].
- Static holding and safety rely on electromechanical brakes to secure posture during power loss; limit switches and STO enforce safe bounds and emergency response [4,8].

To highlight why do humanoids prioritize torque density and low-speed precision, compare their joint-level characteristics with automotive EV traction systems (see Figure 5.) that are optimized for power at high speed [2,4,6].




***Figure 5.*** *Comparison of automotive EV traction motor versus humanoid joint actuator metrics (illustrative). Units include peak torque (N·m), base speed (RPM), and peak power (kW). The power ratio label is illustrative [2,4,6].*

# 4. Tesla Bot (Optimus) as a Mechatronic System

Humanoid robots like Tesla Bot integrate actuators, sensors, and digital control devices so tightly that mechanical, electrical, and software elements function as one coordinated system [2,5–7,9,10,15].

Mechanically, Optimus uses compact joint modules with motors, high-ratio transmissions, brakes, and encoders. Its sensing spans joint encoders, IMUs, force or pressure arrays, and vision. Its control stack combines low-level servo regulation with high-level whole-body coordination under strict safety. A deterministic real-time network synchronizes all elements in closed loop, ensuring precise timing for motion, interaction, and protection [4,11,12].

## 4.1. Mechanical powertrain and actuation

Optimus employs permanent magnet or brushless motors at hips, knees, ankles, shoulders, and elbows, paired with high-reduction transmissions such as harmonic or cycloidal to achieve high joint torque at low speed [2,5,6]. Many joints integrate the motor, geartrain, motor- and joint-side encoders, an electromechanical brake, a drive/controller PCB, and thermal/health sensors (see Fig. 6).




***Figure 6.*** *Processing and control block for an embedded joint module showing processor, memory, controller, processing circuitry, and communication interface, consistent with Tesla Bot patent-style schematics. Source: adapted from GreyB Insights Tesla Bot patents page [15]. Image URL: [https://insights.greyb.com/wp-content/uploads/2024/08/1-12.png].*

### 4.2. Sensing and perception

- Joint encoders provide posture and velocity feedback at each degree of freedom for kinematics and closed-loop control [4,7].
- The torso IMU estimates base orientation and angular/linear rates, supporting balance and disturbance rejection [2,7].
- Foot pressure arrays and optional wrist force/torque sensing quantify contact forces; motor-current-based torque estimation complements external sensing for impedance/admittance control [2,9,10].

- Health monitoring tracks currents, voltages, temperatures, and battery metrics; limit and home switches enforce motion bounds [4,8,12].
- Vision and tactile sensing support object detection, grasping, and compliant manipulation; factory use can leverage AIDC for work tracking [11,12]. See Fig. 7 for the joint controller processing and communication overview

This compact module design enables precise positioning, smooth low-speed torque, robust thermal management, and safe static holding on power loss [2,6,8,15].




***Figure 7.*** *Mechanical assembly identifiers for limb or joint components, illustrating enumerated subassemblies consistent with humanoid drivetrain and linkage partitioning. Source: adapted from GreyB Insights Tesla Bot patents page [15]. Image URL: [https://insights.greyb.com/wp-content/uploads/2024/08/6-8.png].*

### 4.3. Digital control devices and communication

Joint servo drives close current and velocity loops using FOC and enforce safety limits and STO. A central real time controller executes whole body control QP with constraints, impedance or admittance for interaction, trajectory generation, and state estimation with sensor fusion. Supervisory safety manages limits, stops, thermal derating, and fault handling. A deterministic fieldbus such as EtherCAT synchronizes setpoints and feedback at about 1 to 2 kHz. Higher level channels carry diagnostics and planning data [4,7–10,11,12]. The architecture is illustrated in Figure 3, which shows the synchronized controller to drive loop and safety layers, and aligns with the canonical industrial mechatronic layout in Figure 1.




***Figure 8.*** *Sensor field of view layout with panoramic 180 degrees and optional 83 degrees cameras, illustrating multimodal perception coverage around the head or torso. Source: adapted from GreyB Insights Tesla Bot patents page [15]. Image URL: [https://insights.greyb.com/wp-content/uploads/2024/08/1-13.png].*

This layered approach allows the robot to regulate joint torques accurately, coordinate many degrees of freedom for balance and manipulation, and transition safely between tasks and contact conditions, all while honoring timing guarantees required for stability [7–10]. These real time pipelines are depicted in Figure 4, linking perception and estimation to optimization or impedance control and then to fieldbus actuation, further evidencing full mechatronic integration in Optimus. Sensor coverage and field-of-view layout are summarized in Figure 8.

**4.4. Tasks and control modes as evidence of mechatronic integration**

- Locomotion including walking, stairs, slopes, and turning depends on IMU, foot sensors, and encoders for state estimation. Servo drives regulate torques while whole body controllers manage stability and contacts [2,7,9]. The closed loop coordination between controllers, drivers, and sensors follows the control architecture in Figure 3 and the pipeline in Figure 4, confirming end to end mechatronic operation.
- Squatting, lifting, pushing, and pulling require high peak joint torque in the lower body. Friction compensation and impedance control regulate interaction forces safely [8–10]. The joint module hardware that enables this behavior is represented by Figure 2, which shows motors, high ratio transmissions, encoders, brakes, and drive electronics integrated into a serviceable unit.
- Tool use and manipulation rely on vision plus wrist or hand sensing for grasping, force limited insertion, and controlled surface interactions. Sensor less torque and stiffness estimation from drive signals can tune impedance online [9,10,14]. The perception to control to actuation flow is consistent with Figure 4, while timing and safety enforcement use the Figure 1 fieldbus and STO layers.

- Static holding and safety use electromechanical brakes to secure posture on power loss. Limit switches and STO enforce safe bounds and emergency response [4,8]. These elements are included in the canonical industrial mechatronic reference in Figure 1 and in the Optimus joint module concept of Figure 2.
- Compared to automotive traction systems that emphasize power at high speed, humanoid joints are optimized for torque density and precision at low speed through gearing and high bandwidth control, an essential foundation for reliable contact rich behavior in everyday tasks [2,4,6]. Figure 5 contrasts EV traction motors with humanoid joint actuators to highlight why Optimus adopts geared, torque dense, precisely controlled joint modules, a defining characteristic of mechatronic design.

# 5. Discussion

The humanoid robot clearly qualifies as a mechatronic system. Actuators are electric joint modules with high-reduction transmissions, integrated brakes, and compact drive electronics that deliver high torque density and precise control at low speed [2,4,6,8]. Sensors include joint encoders, IMUs, contact/force sensors, and health sensors that provide comprehensive feedback for stability, precision, and safety [4,7,9,12]. Digital control devices include servo drives and a central real-time controller that implement layered control from current, velocity, and position through impedance and whole-body optimization; they are synchronized by a deterministic fieldbus and overseen by supervisory safety and fault handling [4,7–10,11,12].

The industrial robot reference in Figure 1 demonstrates the canonical arrangement of these elements [1,4]. The humanoid joint module in Figure 2, the mechatronic control architecture in

Figure 3, and the whole-body pipeline in Figure 3 show concrete realizations [2,4,7–10]. The EV versus humanoid comparison in Figure 5 clarifies differing optimization regimes that inform actuator and transmission choices for humanoids engaged in contact-rich tasks [2,4,6].

# 6. Conclusion

A typical mechatronic system is defined by tight integration of actuators, sensors, and digital control devices connected over synchronized communication networks and governed by safety [1–4,7–12]. A representative humanoid robot embodies this integration through compact electric joint actuators with high-reduction gearing and brakes, multimodal sensing for state and environment, and a layered control stack from servo drives to whole-body controllers [2,5–10]. The figures provided illustrate each layer and their interconnections, satisfying the assignment requirements to identify components and to explain through an example machine and its schematics why it is considered a mechatronic system [1–4,7–12,15].

# References

[1] Craig, J. J. Introduction to Robotics: Mechanics and Control. Pearson.

[2] Siciliano, B., Sciavicco, L., Villani, L., Oriolo, G. Robotics: Modelling, Planning and Control. Springer.

[3] Bolton, W. Mechatronics: Electronic Control Systems in Mechanical and Electrical Engineering. Pearson.

[4] Beckhoff Automation. EtherCAT and PC-based Control for Robotics (application notes and manuals).

[5] Pratt, G., et al. Series Elastic Actuators for Legged Robots (IEEE/ICRA/ICHR papers).

[6] Tesla Optimus/AI Day materials and technical overviews (company presentations and web pages).

[7] Slotine, J.-J. E., Li, W. Applied Nonlinear Control (sections on robot control/impedance).

[8] Spong, M. W., Hutchinson, S., Vidyasagar, M. Robot Modeling and Control. Wiley.

[9] Albu-Schäffer, A., Ott, C., Hirzinger, G. A unified passivity-based control framework for position, torque and impedance control of flexible joint robots (IJRR/IEEE T-RO).

[10] Sentis, L., Park, J., Khatib, O. Compliant control of multicontact and center-of-mass behaviors in humanoid robots (IJRR/ICRA).

[11] IEC/ISO industrial communication standards and safety standards (e.g., IEC 61158, IEC 61508, ISO 13849).

[12] Industrial robotics integration and diagnostics (OPC UA, PROFINET, vendor manuals/whitepapers).

[13] Kalman, R. E. A new approach to linear filtering and prediction problems (ASME Journal of Basic Engineering).

[14] Hogan, N. Impedance control: An approach to manipulation (ASME Journal of Dynamic Systems, Measurement, and Control).

[15] GreyB Insights. Tesla Bot patents page (image resources and patent-style schematics): https://insights.greyb.com/tesla-bot-patents/ (Source for Figures 6–8 and related captions).