

⚡ Current Skill Get (REST API)

GET Method

This method is used to get a resource from a server. If you perform a **GET** request, the server looks for the data you requested and sends it back to you. In other words, a **GET** request performs a **READ** operation. This is the default request method.

GET127.0.0.1:3000/languages/all

ParamsAuthHeaders (8)BodyPre-req. TestsSettingsCookiesCode

Status: 200 OKTime: 289msSize: 4.25 KB

Query Params

KEY	VALUE	DESCRIPTION
Key	Value	Description

...Bulk Edit

BodyCookiesHeaders (7)Test Results

PrettyRawPreviewVisualizeJSON

```
1[
2  {
3    "id": 45,
4    "name": "Assembly (NASM 2.14.02)",
5    "is_archived": false
6  },
7  {
8    "id": 2,
9    "name": "Bash (4.0)",
10   "is_archived": true
11  },
12  {
13    "id": 1,
14    "name": "Bash (4.4)",
15    "is_archived": true
16  },
17  {
18    "id": 46,
19    "name": "Bash (5.0.0)",
20    "is_archived": false
21  },
22  {
23    "id": 3,
24    "name": "Basic (fbc 1.05.0)",
25    "is_archived": true
26  },
27 ]
```

< Previous

next >