7 FAILED   8 PASSED

53% passed	**32 seconds ago**	**2.22 seconds**
15 executed	last run	duration

Windows 11

Java HotSpot(TM) 64-Bit Server VM 22.0.2+9-70

cucumber-jvm 7.18.0

🔍 Search with text or @tags

☑ failed   ☑ passed

You can search with plain text or Cucumber Tag Expressions to filter the output

❌ file:///C:/Users/nouba/IdeaProjects/RestAssured-API-Testing/src/test/resources/features/create_quote.feature

Feature: Create a New Quote

As a sales representative
I want to create a new quote for a customer
So that I can provide them with pricing and product details quickly

Background:

✅ **Given** the quote api service is running

@AC_1

Scenario Outline: : Successfully create a new quote with one item for a customer

✅ **Given** a customer "<customer_name>"
✅ **And** one item "<item_name>" with the quantity <quantity>, the unitary price <price>, and a percentage of <discount>
✅ **When** I create a quote for that customer with that items
✅ **Then** it returns the quote with the correct details, including the total line price calculated as <total_line_price>,
✅ **And** a confirmation message "Quote created successfully."

Examples:

	customer_name	item_name	quantity	price	discount	total_line_price
✅	Noushin	Product A	2	10.00	0.0	20.00
✅	Noushin	Product B	3	15.00	0.0	45.00

@AC_2

Scenario Outline: Successfully create a new quote with one item with discount for a customer

✅ **Given** a customer "<customer_name>"
✅ **And** one item "<item_name>" with the quantity <quantity>, the unitary price <price>, and a percentage of <discount>
✅ **When** I create a quote for that customer with that items
✅ **Then** it returns the quote with the correct details, including the discount amount <discount_amount> and the total lineprice <total_line_price>
✅ **And** a confirmation message "Quote created successfully."

Examples:

	customer_name	item_name	quantity	price	discount	discount_amount	total_line_price
✅	Noushin	Product B	3	15.00	0.05	2.25	42.75
✅	Noushin	Product C	2	50.00	0.1	10.00	90.00

@AC_3

Scenario Outline: Successfully create a new quote with two items for a customer

- ✅ **Given** a customer "<customer_name>"
- ✅ **And** one item "<item_A>" with the quantity <quantity_A>, the unitary price <price_A>, and a percentage of 0
- ✅ **And** one item "<item_B>" with the quantity <quantity_B>, the unitary price <price_B>, and a percentage of 0
- ✅ **When** I create a quote for that customer with that items
- ✅ **Then** the response status code is 200
- ✅ **Then** it returns the quote with the correct details, including two lines and the total quote price calculated as <total_quote_price>
- ✅ **And** a confirmation message "Quote created successfully."

Examples:

	customer_name	item_A	quantity_A	price_A	item_B	quantity_B	price_B	total_quote_price
✅	Noushin	Product A	2	30.00	Product B	3	20.00	120.00
✅	Noushin	Product X	5	10.00	Product Y	1	100.00	150.00

@AC_4

Scenario Outline: Successfully create a new quote with two items with discount for a customer

- ✅ **Given** a customer "<customer_name>"
- ✅ **And** one item "<item_A>" with the quantity <quantity_A>, the unitary price <price_A>, and a percentage of <discount_A>
- ✅ **And** one item "<item_B>" with the quantity <quantity_B>, the unitary price <price_B>, and a percentage of <discount_B>
- ✅ **When** I create a quote for that customer with that items
- ✅ **Then** it returns the quote with the correct details, including two lines and the total quote price calculated as <total_quote_price>
- ✅ **And** a confirmation message "Quote created successfully."

Examples:

	customer_name	item_A	quantity_A	price_A	discount_A	item_B	quantity_B	price_B	discount_B	total_quote_price
✅	Noushin	Product A	2	100	0.1	Product B	3	20.00	0.5	210.00

@AC_5

Scenario Outline: Create a quote with missing customer name

- ✅ **Given** a customer ""
- ✅ **And** one item "<item_name>" with the quantity <quantity>, the unitary price <price>, and a percentage of 0
- ✅ **When** I create a quote for that customer with that items
- ✅ **Then** the response status code is 400
- ✅ **And** the error message "Customer or Items cannot be null or empty"

Examples:

	item_name	quantity	price
✅	Product A	2	10.00

@AC_6

Scenario Outline: Create a quote with invalid quantity

- ✅ **Given** a customer "<customer_name>"
- ✅ **And** one item "<item_name>" with the quantity <quantity>, the unitary price <price>, and a percentage of 0
- ✅ **When** I create a quote for that customer with that items
- ❌ **Then** the response status code is 400

Examples:

	customer_name	item_name	quantity	price
✖	Noushin	Product B	-100	15.00
✖	Noushin	Product C	-5	10.00

@AC_7

Scenario Outline: Create a quote with invalid price

✔ **Given** a customer "<customer_name>"
✔ **And** one item "<item_name>" with the quantity <quantity>, the unitary price <price>, and a percentage of 0
✔ **When** I create a quote for that customer with that items
✖ **Then** the response status code is 400

Examples:

	customer_name	item_name	quantity	price
✖	Noushin	Product C	2	-10.00
✖	Noushin	Product D	3	-5.00

@AC_8

Scenario Outline: Create a quote with zero price

✔ **Given** a customer "<customer_name>"
✔ **And** one item "<item_name>" with the quantity <quantity>, the unitary price 0, and a percentage of 0
✔ **When** I create a quote for that customer with that items
✖ **Then** the response status code is 400

Examples:

	customer_name	item_name	quantity
✖	Noushin	Product C	2
✖	Noushin	Product D	3

@AC_9

Scenario Outline: Create a quote with discount exceeding 100%:

✔ **Given** a customer "<customer_name>"
✔ **And** one item "<item_name>" with the quantity <quantity>, the unitary price <price>, and a percentage of <discount>
✔ **When** I create a quote for that customer with that items
✖ **Then** the response status code is 400

Examples:

	customer_name	item_name	quantity	price	discount
✖	Noushin	Product B	3	15.00	1.1