Roll No. 18103 B. Tech. I - Sem. UD (Main) Exam., Jan. - 2020 1FY2 – 03 Engineering Chemistry

Time: 3 Hours

Maximum Marks: 100 Min. Passing Marks: 33

Total No of Pages: 2

Instructions to Candidates:

**PART - A**: Short answer questions (up to 25 words) 10 × 2 marks 20 marks. All ten questions are compulsory.

PART - B: Analytical/Problem Solving questions (up to 100 words) 6×5 marks 30 marks. Candidates have to answer six questions out of eight.

PART - C: Descriptive/Analytical/Problem Solving questions 5×10 marks - 50 marks. Candidates have to answer five questions out of seven.

NIL

NII.

## PART – A

- Q.1 How are exhausted ion exchange resins regenerated?
- Q.2 What happens when temporary hard water is boiled? Give equations.
- Q.3 What is power alcohol?
- Q.4 What is sweetening of petrol?
- Q.5 What is chemical formula of rust?
- 76.6 The rate of metallic corrosion increases with increase in temperature. Give reason.
- Q.7 Write the formula and uses of Paracetamol.
  - Q.8 Write the formula with percentage of borosilicate glass.
  - Og Define Emulsification.
  - Q.10 Write the components with percentage of Portland cement.

[18103]

Page 1 of 2

[600]

http://www.rtuonline.com

## PART - B

- Q.1 How calorific value of a gaseous fuel is determined by Junker's calorimeter.
- Q.2 What are the requirements of boiler feed water?
- Define cloud and pour points and how it is determined in laboratory?
  - Q.4 Explain the mechanism of free radical substitution reaction with suitable example.
- Q.5 Explain role of gypsum in cement manufacturing.
- Q.6 Differentiate between chemical corrosion and electrochemical corrosion.
- Write short notes on -
  - (a) Galvanic corrosion
  - (b) Breakpoint chlorination
- Q.8 What is the significance of octane number and cetane number and for which these are used. How these can be improved?

## PART - C

- Q.1 0.72gm of a fuel containing 80% carbon, when burnt in a Bomb calorimeter, increased the temperature of water from 27.3° C to 29.1° C. If the calorimeter contains 250 gms of water and its water equivalent is 150 gms, calculate the HVC of fuel. Answer is calculated in kJ/kg.
- A water sample on analysis give following data –

  Ca +2 = 30mg/L; Mg+2 = 24mg/L; CO<sub>2</sub> = 24mg/L; HCl = 50mg/L; K+ = 10mg/L;

  Calculate the quantity of lime (90% pure) and soda (94% pure) required to soften one million liters of water sample.
  - Q.3 Define cement and explain its manufacturing by R.K. method with chemical reaction and neat diagram.
    - Q.4 Explain scale formation and slug formation in boilers. How are they removed?
    - Q.5 Write short notes on any two -
      - (a) Refining of gasoline
      - (b) Characteristics of a good fuel
      - (c) Metallurgical coke
    - Q.6 (a) How is corrosion prevented by cathodic protection? Explain.
      - (b) Explain Pitting corrosion
    - Q.7 (a) Explain thick and thin layer mechanism of lubrication.
      - (b) Explain general chemistry of different types of glass.

[18103]

Page 2 of 2

[600]

http://www.rtuonline.com