Interview Prep — Huawei Walk-in Interview

Posisi fokus: Core Network / IP Engineer | Friday, 21 Aug 2026, Batch 1 (09:00 AM)

1. Self-Introduction (± 1 menit)

Nama, jurusan Telecommunication Engineering, Telkom University (2022–sekarang)
Pengalaman lapangan: instalasi & konfigurasi MPLS network
PT Maktekindo: 12 stasiun untuk KAI, pakai ERPS & ELPS, via fiber optic
Proyek P2P MPLS: LC duplex fiber, E1 traffic ke Access Multiplexer
Sedikit fullstack dev (React, Express, PostgreSQL) → paham infra & aplikasi
Alasan tertarik: deepen MPLS/core network experience di environment besar & terstruktur

2. Cerita STAR — 4 cerita utama

A. MPLS Ring Deployment (ERPS/ELPS) — 12 stasiun KAI

S: Proyek 12 stasiun untuk KAI, pakai MPLS ring topology
T: Install & konfigurasi MPLS devices, interkoneksi stabil via fiber optic
A: ERPS untuk ring protection (auto-reroute kalau link putus), ELPS untuk linear protection di beberapa segmen
R: Network stabil di 12 stasiun, sekalian training personel KAI supaya handover lancar

B. Point-to-Point MPLS + E1 Traffic

S: Proyek P2P MPLS link antar 2 stasiun
T: Install fiber + konfigurasi MPLS routing
A: LC duplex fiber patch cores (4 core/sisi, 4 SFP total), MPLS routing bawa E1 traffic ke Access Multiplexer
R: Voice/data komunikasi reliable antar stasiun

C. Padalarang–Cibungur (ERPS) & Padalarang–Bandung (ELPS)

S: Bagian dari proyek 12 stasiun yang sama, topologi beda per segmen
T: Konfigurasi ERPS di ring (Padalarang–Cibungur), ELPS di linear (Padalarang–Bandung)
A: ERPS → buat ring group, ring ports, RPL port, bind ke VLAN & maintenance domain (CFM). ELPS → working link + protection link paralel
R: Kedua segmen punya automatic failover — ring reroute dalam loop, linear punya backup path
Kalau ditanya kenapa beda: *"It depends on the physical topology — ring topology uses ERPS to manage the RPL and prevent loops, while point-to-point uses ELPS since there's no ring to protect, just a parallel backup path."*

D. Madiun–Babadan–Caruban — Device Upgrade G7860 ke G7860A

S: Upgrade perangkat transport dari G7860 (standar) ke G7860A di jalur Madiun–Babadan–Caruban
T: Reconfig MPLS network di device G7860A baru, tanpa ganggu E1 traffic (legacy voice/data) yang sudah jalan
A: Set up MPLS domain (global ID & node ID per device), buat MPLS tunnel antar stasiun (role HEAD/TAIL sesuai arah), buat LSP segment dengan label untuk Ethernet & E1 pseudowire, konfigurasi traffic policing per tunnel, setup BFD untuk OAM (deteksi failure cepat)

R: Segmen dapat kapasitas & interface headroom lebih besar untuk scaling ke depan, E1 circuit tetap stabil
Kalau ditanya kenapa upgrade ke G7860A: *"Both models support MPLS-TP, but the G7860A has stronger hardware specs — higher switching capacity and more built-in ports and interfaces — which gave the network more room to scale."*
⚠️ **Penting:** JANGAN bilang G7860 (non-A) tidak support MPLS — dua-duanya support MPLS-TP. Bedanya di kapasitas switching, jumlah interface built-in, dan cakupan circuit emulation (TDMoE/TDMoIP/TDMoMPLS/CESoPSN/SAToP/CEP).
Cerita cadangan (soft skill): Training personel KAI → komunikasi ke non-teknis, kesabaran.

3. Cheat Sheet Istilah Teknis (Inggris)

Istilah	Penjelasan singkat
MPLS	Label switching protocol, forward traffic pakai label bukan IP routing biasa
ERPS (G.8032)	Ring protection — 1 link jadi backup (RPL), diblokir normal, aktif kalau main link putus (switching ms)
ELPS	Linear/point-to-point protection — working link + backup link paralel
RPL (Ring Protection Link)	Link backup dalam ring ERPS, default blocked
LSP (Label Switched Path)	Jalur forwarding aktual berdasarkan MPLS label, hop-by-hop
Tunnel HEAD/TAIL	HEAD = node asal tunnel, TAIL = node tujuan — nentuin arah tunnel
Pseudowire (PW) / E1	Emulasi circuit E1 (TDM legacy) di atas jaringan MPLS packet
BFD	Protokol deteksi failure link secara cepat (lebih cepat dari protokol layer atas)
CFM	Connectivity Fault Management — dipakai untuk fault monitoring, prasyarat sebelum setup ERPS
Node ID / Global ID	Identifier unik MPLS domain & tiap node, biar tunnel bisa terbentuk ke device yang tepat
G7860 vs G7860A	Dua-duanya support MPLS-TP. G7860A punya switching capacity lebih tinggi (up to 85G), lebih banyak built-in interface (6x 10GbE SFP+, 4x 1GbE SFP, 16x E1/T1), dan LSP protection switching <50ms

4. Pertanyaan Umum HR (jawaban singkat)

Why Huawei?
"Huawei is a global leader in telecom infrastructure. I want to work with large-scale network systems and grow my MPLS/core network skills in a structured, international environment."
Strength?
"Hands-on and adaptable — I've worked directly in the field installing and configuring devices, not just theory."
Weakness?
"My experience so far has been project-based rather than large corporate structure, so I'm still building familiarity with enterprise-scale processes — part of why I'm excited about this role."
5 years from now?
"Growing into a specialist in core network/IP engineering, taking on larger infrastructure projects, eventually mentoring juniors."

5. Kalau Ditanya Detail / Follow-up Teknis

Kalau paham konsep tapi bingung Inggrisnya: jelasin konsep dulu pakai kalimat sederhana + analogi, istilah teknis belakangan
Kalau di luar yang dikuasai: *"I don't have hands-on experience with that specifically, but from what I understand... I'd be eager to learn more about it here."* — JANGAN mengarang
Kalau lupa angka spesifik: *"I don't remember the exact number, but roughly around..."*
Butuh waktu mikir: *"That's a good question, let me think for a second."*
Ngomong pelan & jelas, jeda boleh, parafrase kalau lupa kata

6. Checklist Bawaan Besok

- [ ] CV (Bahasa Inggris) hardcopy A4
- [ ] Ijazah / Surat Keterangan Lulus
- [ ] Transkrip akademik
- [ ] Datang jam 08.45–08.50 (venue: TULT 16th Floor, Room 16.01/16.02/16.04, Telkom University Bandung)