OmniCode: Chapter 15: Track 2 - Lexicon: Verbs, Pronouns & Operators

Directional SVO Verbs, Scale Vectors & Polarity

CHAPTER IDENTIFIER
CH 15

NOTEBOOKLM WORD COUNT
7,888 words

CATALOGED CHAPTER FILES
26 files (1,565 lines)

GENERATION DATE
2026-10-16 20:36:07

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"Explain difference between ascension (/-^) and descension (\-v)."*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (26 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/arithmetic_verbs.omni**	OMNI	94	399	3.3
2	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/arithmetic_verbs.tape**	TAPE	33	207	1.6
3	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/axial_vectors.omni**	OMNI	68	271	2.5
4	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/axial_vectors.tape**	TAPE	30	178	1.4
5	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/cinematic_track_loop.omni**	OMNI	56	245	2.2
6	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/cinematic_track_loop.tape**	TAPE	36	250	1.8
7	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/diagonal_vectors.omni**	OMNI	92	380	3.2
8	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/diagonal_vectors.tape**	TAPE	30	177	1.5
9	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/relational_being.omni**	OMNI	86	376	3.1
10	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/relational_being.tape**	TAPE	33	191	1.5
11	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/scale_vectors.omni**	OMNI	68	265	2.5
12	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/scale_vectors.tape**	TAPE	30	187	1.5
13	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/03_verbs/universal_verbs.omni**	OMNI	118	617	4.9
14	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/03_verbs/universal_verbs.tape**	TAPE	49	296	2.5
15	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/operators/morphological_operators.omni**	OMNI	121	686	5.3
16	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/operators/morphological_operators.tape**	TAPE	49	318	2.5
17	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/boot_kernel.omni**	OMNI	91	441	3.9
18	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/boot_kernel.tape**	TAPE	37	264	2.0
19	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/casting.omni**	OMNI	88	393	3.1
20	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/casting.tape**	TAPE	30	170	1.4
21	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/polarity.omni**	OMNI	74	338	3.0
22	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/polarity.tape**	TAPE	30	179	1.5
23	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/self_handles.omni**	OMNI	81	338	2.9
24	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/self_handles.tape**	TAPE	30	187	1.4
25	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/wildcards.omni**	OMNI	81	342	3.0
26	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/wildcards.tape**	TAPE	30	193	1.5

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/arithmetic_verbs.omni

OMNI | 94 LINES | 399 WORDS | 3.3 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Verbs: Mechanical SVO Arithmetic Operators )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the mechanical arithmetic accumulator cogs:
#   - plus  : Additive mechanical translation cog (advance accumulator).
#   - minus : Subtractive mechanical translation cog (recede accumulator).
#   - times : Multiplicative mechanical gear ratio (ratio expansion).
#   - div   : Divisive mechanical tooth pitch / partition ratio.
# ================================================================================

Module < Lexicon.Verbs.ArithmeticVerbs > ( Mechanical arithmetic cogs and ratio accumulators ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < SVOArithmetic :: MechanicalAccumulators :: Radix3Cogs >
}

# 1. Additive Cog: < PLUS >
Plus < InvariantVerb > ( Mechanical Additive Translation: plus ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "plus" >,
    abstract_form: < "+Plus" >,
    concrete_form: < "Plus-" >,
    machine_effect: < "mechanical_adder_cog" >
}

# 2. Subtractive Cog: < MINUS >
Minus < InvariantVerb > ( Mechanical Subtractive Translation: minus ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "minus" >,
    abstract_form: < "+Minus" >,
    concrete_form: < "Minus-" >,
    machine_effect: < "mechanical_subtractor_cog" >
}

# 3. Multiplicative Cog: < TIMES >
Times < InvariantVerb > ( Mechanical Gear Ratio Multiplier: times ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "times" >,
    abstract_form: < "+Times" >,
    concrete_form: < "Times-" >,
    machine_effect: < "mechanical_gear_multiplier" >
}

# 4. Divisive Cog: < DIV >
Div < InvariantVerb > ( Mechanical Pitch Partition Divider: div ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "div" >,
    abstract_form: < "+Div" >,
    concrete_form: < "Div-" >,
    machine_effect: < "mechanical_partition_divider" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Plus : InvariantVerb ::
        Minus : InvariantVerb ::
        Times : InvariantVerb ::
        Div : InvariantVerb
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
```

```
# ================================================================================
Body [
    # Verify SVO arithmetic execution
    arithmetic_verification [
        Add_Roll [ 10 plus 5 = 15 ] ::
        Sub_Roll [ 20 minus 8 = 12 ] ::
        Mul_Roll [ 4 times 3 = 12 ] ::
        Div_Roll [ 16 div 4 = 4 ]
    ] ( Mechanical arithmetic operations verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        arithmetic_verification = yes
    ],
    commit_status [ PROCEED- ] ( Arithmetic verbs verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/arithmetic_verbs.tape

TAPE | 33 LINES | 207 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: ARITHMETIC VERBS EXECUTION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes mechanical SVO arithmetic operations (plus, minus, times, div).
# ================================================================================

[Tape.ArithmeticVerbs] : WHO {OmniCode_Kernel} WHAT {ArithmeticVerbs} --> ACCUMULATE {MathMesh}
    WHEN {GenesisBoot}
    WHERE {arithmetic_chassis} = [ 64 ]
    WHY ( Test mechanical arithmetic adder and multiplier cogs )
    HOW [ +1 : PROCEED ]
    :: < math_landmark > ( Genesis 1:28 - 'Be fruitful, and multiply' )

# ================================================================================
# SUBORDINATE ROLLS: MECHANICAL SVO ARITHMETIC TRANSFORMATIONS
# ================================================================================

# Roll 1: Reference abstract Plus, Minus, Times, and Div specifications
roll_1 [ +Plus & +Minus & +Times & +Div ] ( Abstract arithmetic verb blueprints referenced )

# Roll 2: Additive mechanical translation
roll_2 [ 20 plus 22 --> Accumulator_0 @ 0 ] ( Compute sum and store into accumulator )

# Roll 3: Multiplicative mechanical gear ratio
roll_3 [ 6 times 7 --> Product_0 @ 1 ] ( Compute product and store into product cell )

# Roll 4: Verify accumulator invariant bounds
roll_4 [ Accumulator_0 = 42 ! [ +1 ] ] ( Verify mechanical arithmetic result )

# Roll 5: Commit with affirmative concrete macro
roll_5 [ commit_status [ PROCEED- ] ] ( Arithmetic verbs verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/axial_vectors.omni

OMNI | 68 LINES | 271 WORDS | 2.5 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Verbs: Axial Driving Vectors )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the primary horizontal causality vectors:
#   - --> : ActUpon (Forward causality, drive gear, state propagation, store).
#   - <-- : ActAgain (Reverse causality, retroaction, sensor read, reflection).
# ================================================================================

Module < Lexicon.Verbs.AxialVectors > ( Axial drive vectors and horizontal causality ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < AxialVectors :: ForwardDrive :: RetroactiveFeedback >
}

# 1. Forward Vector: < ACT_UPON >
ActUpon < InvariantVerb > ( Forward Causality & Driving Gear: --> ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "-->" >,
    abstract_form: < "+ActUpon" >,
    concrete_form: < "ActUpon-" >,
    machine_effect: < "forward_drive_write_dispatch" >
}

# 2. Reverse Vector: < ACT_AGAIN >
ActAgain < InvariantVerb > ( Reverse Causality & Feedback Gear: <-- ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "<--" >,
    abstract_form: < "+ActAgain" >,
    concrete_form: < "ActAgain-" >,
    machine_effect: < "retroactive_read_sensor" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        ActUpon : InvariantVerb ::
        ActAgain : InvariantVerb
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify forward and reverse causality pair
    vector_verification [
        Forward_Transmission [ 10 --> Register_A ] ::
        Feedback_Sensor [ Register_A <-- Sensor_Tap ]
    ] ( Forward drive and sensor feedback verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        vector_verification = yes
    ],
    commit_status [ PROCEED- ] ( Axial driving vectors verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/axial_vectors.tape

TAPE | 30 LINES | 178 WORDS | 1.4 KB

```
# ================================================================================
# TAPE HEAD: AXIAL VECTORS EXECUTION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes forward driving write (-->) and reverse feedback read (<--).
# ================================================================================

[Tape.AxialVectors] : WHO {OmniCode_Kernel} WHAT {AxialVectors} --> DRIVE {MotionMesh}
    WHEN {GenesisBoot}
    WHERE {axial_chassis} = [ 64 ]
    WHY ( Test forward and reverse axial drive gears )
    HOW [ +1 : PROCEED ]
    :: < vector_landmark > ( Proverbs 4:25 - 'Let thine eyes look right on' )

# ================================================================================
# SUBORDINATE ROLLS: FORWARD AND REVERSE AXIAL TRANSLATION
# ================================================================================

# Roll 1: Reference abstract ActUpon and ActAgain vector specifications
roll_1 [ +ActUpon & +ActAgain ] ( Abstract axial vector blueprints referenced )

# Roll 2: Forward drive vector actuation
roll_2 [ 100 --> Buffer_0 @ 0 ] ( Forward drive write into Buffer_0 )

# Roll 3: Reverse drive vector verification
roll_3 [ Result <-- Buffer_0 ! [ +1 ] ] ( Reverse read from Buffer_0 )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Axial vectors verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/cinematic_track_loop.omni

OMNI | 56 LINES | 245 WORDS | 2.2 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Verbs: Cinematic Track Loops & Transport Kinematics )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines Turing-complete track looping via reel transport kinematics:
#   - PLAY   : Advance track head forward (+1 / YES / PROCEED).
#   - REWIND : Spool track head backward along the reel to cue landmark (-1 / NO / ROLLBACK).
#   - STOP   : Mechanical brake arresting the motor (NULL / VOID / HALT).
# ================================================================================

Module < Lexicon.Verbs.CinematicTrackLoop > ( Cinematic track looping and transport kinematics ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < TrackLooping :: TransportKinematics :: TuringCompleteness >
}

# 1. Transport Verb: < CINEMATIC_LOOP >
CinematicLoop < InvariantVerb > ( Turing-Complete Track Transport Loop: PLAY & REWIND ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    abstract_form: < "+CinematicLoop" >,
    concrete_form: < "CinematicLoop-" >,
    machine_effect: < "turing_complete_track_transport" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        CinematicLoop : InvariantVerb
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify track transport iteration
    loop_verification [
        Track_Iteration [ Counter > 0 ! [ PLAY :: REWIND < loop_cue > ] ]
    ] ( Track transport kinematics verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        loop_verification = yes
    ],
    commit_status [ PROCEED- ] ( Cinematic track loops verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/cinematic_track_loop.tape

TAPE | 36 LINES | 250 WORDS | 1.8 KB

```
# ================================================================================
# TAPE HEAD: CINEMATIC TRACK LOOP PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes a Turing-complete transport loop via PLAY and REWIND to cue landmark.
# ================================================================================

[Tape.CinematicTrackLoop] : WHO {OmniCode_Kernel} WHAT {CinematicLoop} --> MODULATE {ReelMesh}
    WHEN {GenesisBoot}
    WHERE {loop_partition} = [ 64 ]
    WHY ( Prove Turing completeness via physical reel transport kinematics )
    HOW [ +1 : PROCEED ]
    :: < loop_landmark > ( Ecclesiastes 1:6 - 'The wind returneth again according to his circuits' )

# ================================================================================
# SUBORDINATE ROLLS: REEL TRANSPORT KINEMATICS & CUE REWIND
# ================================================================================

# Roll 1: Reference abstract CinematicLoop transport specification
roll_1 [ +CinematicLoop ] ( Abstract track loop blueprint referenced )

# Roll 2: Inscribe initial loop counter into silicon register
roll_2 [ 3 --> Loop_Counter_0 @ 0 ] ( Initialize loop counter to 3 )

# Roll 3: Landmark cue point for loop track rewind
roll_3 [ < loop_cue > :: 1 plus Step_Accumulator_0 --> Step_Accumulator_0 @ 1 ] ( Cue landmark: advance step accumulator
)

# Roll 4: Decrement loop counter
roll_4 [ Loop_Counter_0 minus 1 --> Loop_Counter_0 @ 0 ] ( Decrement loop counter register )

# Roll 5: Conditional track transport rewind
roll_5 [ Loop_Counter_0 != 0 ! [ PLAY :: REWIND < loop_cue > ] ] ( Rewind track head back to landmark cue while counter
positive )

# Roll 6: Commit and stop transport motor
roll_6 [ STOP :: commit_status [ PROCEED- ] ] ( Complete loop and engage emergency brake )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/diagonal_vectors.omni

OMNI | 92 LINES | 380 WORDS | 3.2 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Verbs: Diagonal Modulated Scale Vectors )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines compound diagonal scale and causality vectors across 3D coordinates:
#   - /-^ : Major (Ascending forward diagonal, macro amplification).
#   - \-v : Minor (Descending forward diagonal, micro attenuation).
#   - /-v : Small (Descending reverse diagonal, localized reduction).
#   - \-^ : Great (Ascending reverse diagonal, expansive retrospective).
# ================================================================================

Module < Lexicon.Verbs.DiagonalVectors > ( Diagonal modulated scale and causality vectors ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < DiagonalVectors :: ModulatedScale :: SpatialProjection >
}

# 1. Diagonal Vector: < MAJOR >
Major < InvariantVerb > ( Ascending Forward Diagonal: /-^ ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Adjective" >,
    symbol: < "/-^" >,
    abstract_form: < "+Major" >,
    concrete_form: < "Major-" >,
    machine_effect: < "macro_amplification_forward" >
}

# 2. Diagonal Vector: < MINOR >
Minor < InvariantVerb > ( Descending Forward Diagonal: \-v ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Adjective" >,
    symbol: < "\\-v" >,
    abstract_form: < "+Minor" >,
    concrete_form: < "Minor-" >,
    machine_effect: < "micro_attenuation_forward" >
}

# 3. Diagonal Vector: < SMALL >
Small < InvariantVerb > ( Descending Reverse Diagonal: /-v ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Adjective" >,
    symbol: < "/-v" >,
    abstract_form: < "+Small" >,
    concrete_form: < "Small-" >,
    machine_effect: < "localized_reduction_reverse" >
}

# 4. Diagonal Vector: < GREAT >
Great < InvariantVerb > ( Ascending Reverse Diagonal: \-^ ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Adjective" >,
    symbol: < "\\-^" >,
    abstract_form: < "+Great" >,
    concrete_form: < "Great-" >,
    machine_effect: < "expansive_retrospective_reverse" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Major : InvariantVerb ::
        Minor : InvariantVerb ::
        Small : InvariantVerb ::
        Great : InvariantVerb
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
```

```
# ================================================================================
Body [
    # Verify diagonal trajectory balance
    diagonal_verification [
        Amplification [ Signal /-^ Macro_Bus ] ::
        Attenuation   [ Signal \-v Micro_Bus ]
    ] ( Compound 3D diagonal motions verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        diagonal_verification = yes
    ],
    commit_status [ PROCEED- ] ( Diagonal scale vectors verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/diagonal_vectors.tape

TAPE | 30 LINES | 177 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: DIAGONAL VECTORS EXECUTION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes modulated diagonal scale transformations across coordinate quadrants.
# ================================================================================

[Tape.DiagonalVectors] : WHO {OmniCode_Kernel} WHAT {DiagonalVectors} --> MODULATE {QuadrantMesh}
    WHEN {GenesisBoot}
    WHERE {diagonal_chassis} = [ 64 ]
    WHY ( Test 3D diagonal scale and direction vectors )
    HOW [ +1 : PROCEED ]
    :: < diagonal_landmark > ( Ezekiel 1:16 - 'A wheel in the middle of a wheel' )

# ================================================================================
# SUBORDINATE ROLLS: DIAGONAL MODULATED TRANSFORMATIONS
# ================================================================================

# Roll 1: Reference abstract Major and Minor diagonal vectors
roll_1 [ +Major & +Minor ] ( Abstract diagonal vector blueprints referenced )

# Roll 2: Modulate scale forward-ascending via /-^
roll_2 [ Signal_0 /-^ Macro_Register @ 0 ] ( Ascending forward diagonal drive )

# Roll 3: Modulate scale forward-descending via \-v
roll_3 [ Macro_Register \-v Micro_Register ! [ +1 ] ] ( Descending forward diagonal drive )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Diagonal vectors verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/relational_being.omni

OMNI | 86 LINES | 376 WORDS | 3.1 KB

```
# ============================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Verbs: Relations of Being along the Y-Axis )
# ============================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the Y-axis relations of ontology and identity:
#   - =  : Is (Exact identity, equivalence, covenant equality).
#   - != : IsNot (Distinction, exclusion; not / not to be).
#   - =! : IsNot (Copular negation, non-being; is not / to be not).
#   - ~= : ToBeLike (Homomorphism, structural analogy, likeness).
#   - =~ : ToBeLike (Homomorphic resemblance; liken to / to be like).
# ============================================================================

Module < Lexicon.Verbs.RelationalBeing >
    ( Relations of Being and ontological identity )
{
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < RelationalBeing :: IdentityEquivalence :: StructuralAnalogy >
}

# 1. Identity Relation: < IS >
Is < InvariantVerb > ( Exact Ontological Identity & Equivalence: = ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Preposition" >,
    symbol: < "=" >,
    abstract_form: < "+Is" >,
    concrete_form: < "Is-" >,
    machine_effect: < "identity_assert_equate" >
}

# 2. Distinction Relation: < IS_NOT >
IsNot < InvariantVerb > ( Ontological Distinction: != / =! ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Preposition" >,
    symbols: < "!=" :: "=!" >,
    abstract_form: < "+IsNot" >,
    concrete_form: < "IsNot-" >,
    machine_effect: < "distinction_assert_differentiate" >
}

# 3. Analogy Relation: < TO_BE_LIKE >
ToBeLike < InvariantVerb > ( Homomorphism & Likeness: ~= / =~ ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Adjective" >,
    symbols: < "~=" :: "=~" >,
    abstract_form: < "+ToBeLike" >,
    concrete_form: < "ToBeLike-" >,
    machine_effect: < "homomorphic_analogy_match" >
}

# ============================================================================
# BLOCK 2: OPENING BLOCK
# ============================================================================
Opening {
    requires: [
        Is : InvariantVerb ::
        IsNot : InvariantVerb ::
        ToBeLike : InvariantVerb
    ],
    preconditions: [ +1 ]
}

# ============================================================================
# BLOCK 3: BODY BLOCK
# ============================================================================
Body [
    # Verify identity, distinction, and analogy
    relations_verification [
        Equivalence_Roll [ Entity_A = Entity_A ] ::
        Distinction_Roll [ Entity_A != Entity_B :: Entity_A =! Entity_B ] ::
        Analogy_Roll     [ Entity_A ~= Entity_Prototype ::
                           Entity_A =~ Entity_Prototype ]
```

```
    ] ( Y-axis relations of being verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        relations_verification = yes
    ],
    commit_status [ PROCEED- ] ( Relations of being verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/relational_being.tape

TAPE | 33 LINES | 191 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: RELATIONAL BEING EXECUTION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes identity (=), distinction (!= / =!), and analogy (~= / =~).
# ================================================================================

[Tape.RelationalBeing] : WHO {OmniCode_Kernel}
    WHAT {RelationalBeing} --> VERIFY {IdentityMesh}
    WHEN {GenesisBoot}
    WHERE {relational_chassis} = [ 64 ]
    WHY ( Test Y-axis relations of being, distinction, and analogy )
    HOW [ +1 : PROCEED ]
    :: < relation_landmark > ( Exodus 3:14 - 'I AM THAT I AM' )

# ================================================================================
# SUBORDINATE ROLLS: RELATIONAL EQUIVALENCE & DISTINCTION
# ================================================================================

# Roll 1: Reference abstract Is, IsNot, and ToBeLike specifications
roll_1 [ +Is & +IsNot & +ToBeLike ]
    ( Abstract relational being blueprints referenced )

# Roll 2: Verify identity equivalence via =
roll_2 [ State_Alpha = State_Alpha @ 0 ] ( Verify reflexive identity equation )

# Roll 3: Verify boundary distinction via != and =!
roll_3 [ State_Alpha != State_Beta :: State_Alpha =! State_Beta ! [ +1 ] ]
    ( Verify ontological distinction via != and =! )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Relational being verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/scale_vectors.omni

OMNI | 68 LINES | 265 WORDS | 2.5 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Verbs: Scale Vectors & Hierarchical Motion )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines vertical hierarchy and scale motion vectors:
#   - ^-- : BuildsTo (Ascension, composition, integration, synthesis).
#   - v-- : BreaksDownFrom (Descension, partitioning, decomposition, allocation).
# ========================================================================

Module < Lexicon.Verbs.ScaleVectors > ( Scale vectors and hierarchical motion ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < ScaleVectors :: HierarchicalSynthesis :: PartitionDecomposition >
}

# 1. Scale Ascension: < BUILDS_TO >
BuildsTo < InvariantVerb > ( Hierarchical Ascension & Synthesis: ^-- ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "^--" >,
    abstract_form: < "+BuildsTo" >,
    concrete_form: < "BuildsTo-" >,
    machine_effect: < "ascend_compose_aggregate" >
}

# 2. Scale Descension: < BREAKS_DOWN_FROM >
BreaksDownFrom < InvariantVerb > ( Hierarchical Descension & Partitioning: v-- ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "v--" >,
    abstract_form: < "+BreaksDownFrom" >,
    concrete_form: < "BreaksDownFrom-" >,
    machine_effect: < "descend_partition_slice" >
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {
    requires: [
        BuildsTo : InvariantVerb ::
        BreaksDownFrom : InvariantVerb
    ],
    preconditions: [ +1 ]
}

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    # Verify scale ascension and descension
    scale_verification [
        Synthesis_Roll [ SubUnits ^-- MasterSystem ] ::
        Decomposition_Roll [ Root_Storehouse v-- Sub_Partition [ 128 ] ]
    ] ( Hierarchical scale vectors verified )
]

# ========================================================================
# BLOCK 4: CLOSING BLOCK
# ========================================================================
Closing {
    verify: [
        scale_verification = yes
    ],
    commit_status [ PROCEED- ] ( Scale vectors verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/scale_vectors.tape

TAPE | 30 LINES | 187 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: SCALE VECTORS EXECUTION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes scale ascension (^--) and scale descension partition slicing (v--).
# ================================================================================

[Tape.ScaleVectors] : WHO {OmniCode_Kernel} WHAT {ScaleVectors} --> MODULATE {HierarchyMesh}
    WHEN {GenesisBoot}
    WHERE {scale_chassis} = [ 128 ]
    WHY ( Test hierarchical ascension and partition descension )
    HOW [ +1 : PROCEED ]
    :: < scale_landmark > ( Genesis 28:12 - 'A ladder set up on the earth, and the top of it reached to heaven' )

# ================================================================================
# SUBORDINATE ROLLS: SCALE ASCENSION AND DESCENSION
# ================================================================================

# Roll 1: Reference abstract BuildsTo and BreaksDownFrom vector specifications
roll_1 [ +BuildsTo & +BreaksDownFrom ] ( Abstract scale vector blueprints referenced )

# Roll 2: Scale partition slicing via v--
roll_2 [ Root_Storehouse v-- Sub_Partition @ 0 ] ( Carve sub-partition from root storehouse )

# Roll 3: Scale ascension via ^--
roll_3 [ Sub_Partition ^-- Root_Storehouse ! [ +1 ] ] ( Verify structural linkage to root )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Scale vectors verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/03_verbs/universal_verbs.omni

OMNI | 118 LINES | 617 WORDS | 4.9 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Verbs: Universal Human Verbs for Accessible System Architecture )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines four foundational human verbs designed for universal cross-domain usage:
#   - PREEMPT : Priority interruption & turn-taking (replaces technical scheduler jargon).
#   - SENSE   : Environmental perception & hardware discovery (replaces invasive developer jargon "Probe").
#   - AWAKEN  : Cold-start inception & life activation (replaces gamer/Unix jargon "Spawn" / "Fork").
#   - PROVE   : Invariant validation & equilibrium self-test (replaces developer acronyms "BIST" / "Assert").
#
# ACCESSIBILITY FOR NON-CODERS:
#   Every verb defined here is a standard, intuitive word understood by any human speaker:
#   - A human understands what it means to "sense" a room or "awaken" a dormant console.
#   - A human understands what it means to "preempt" a workflow for something urgent.
#   - A human understands what it means to "prove" balance before committing a decision.
# ================================================================================

Module < Lexicon.Suggestions.Verbs.Universal > ( Universal human verbs for accessible system architecture ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < UniversalVerbs :: NonCoderAccessibility :: CrossDomainActions >
}

# 1. Action: < PREEMPT >
Preempt < InvariantVerb > ( Priority Interruption & Turn-Taking ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    abstract_form: < "+Preempt" >,
    concrete_form: < "Preempt-" >,
    universal_scope: < "OS.Scheduler :: UI.Modals :: Audio.Ducking :: AI.Safety" >,
    machine_effect: < "schedule_quantum_preemption" >
}

# 2. Action: < SENSE >
Sense < InvariantVerb > ( Environmental Perception & Hardware Discovery ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Noun" >,
    abstract_form: < "+Sense" >,
    concrete_form: < "Sense-" >,
    universal_scope: < "OS.MemoryMap :: Game.Collision :: UI.Theme :: IoT.Sensors" >,
    machine_effect: < "perceive_environmental_state" >
}

# 3. Action: < AWAKEN >
Awaken < InvariantVerb > ( Cold-Start Inception & Life Activation ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Noun" >,
    abstract_form: < "+Awaken" >,
    concrete_form: < "Awaken-" >,
    universal_scope: < "OS.ProcessInception :: UI.StudioLaunch :: Game.Entities :: AI.Memory" >,
    machine_effect: < "instate_active_execution_life" >
}

# 4. Action: < PROVE >
Prove < InvariantVerb > ( Invariant Validation & Equilibrium Certification ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Noun" >,
    abstract_form: < "+Prove" >,
    concrete_form: < "Prove-" >,
    universal_scope: < "OS.ALU_BIST :: Security.Covenants :: Math.Balance :: Invariant.Checks" >,
    machine_effect: < "certify_invariant_truth" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Action Dependencies & Operational Preconditions )
# ================================================================================
Opening {
    requires: [
        Preempt : InvariantVerb ::
        Sense : InvariantVerb ::
        Awaken : InvariantVerb ::
```

```
        Prove : InvariantVerb
    ],
    preconditions: [ +1 : PROCEED ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Cross-Domain Demonstrations of Universal Verbs )
# ================================================================================
Body [
    # Demo 1: Preempt action in scheduling & urgent workflow
    preempt_demo [
        Scheduler_Tick [ Timer_IRQ --> PREEMPT {Current_Task} ]
    ] ( Preempt active execution quantum in favor of higher-priority need )

    # Demo 2: Sense action in environmental hardware discovery
    sense_demo [
        Hardware_Discovery [ Kernel --> SENSE {Root_RAM} ]
    ] ( Sense physical memory topology from silicon firmware )

    # Demo 3: Awaken action in cold-start process inception
    awaken_demo [
        Session_Launch [ Kernel --> AWAKEN {Terminal_Studio} ]
    ] ( Awaken dormant console interface into living interaction )

    # Demo 4: Prove action in balanced-ternary ALU verification
    prove_demo [
        Arithmetic_Proof [ Kernel --> PROVE {ALU_Equilibrium} ]
    ] ( Prove algebraic symmetry before allocating dynamic memory )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Invariant Audit & Covenant Commit Seal )
# ================================================================================
Closing {
    verify: [
        preempt_demo = yes ::
        sense_demo = yes ::
        awaken_demo = yes ::
        prove_demo = yes
    ],
    commit_status [ PROCEED ] ( Universal human verb proposals certified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/03_verbs/universal_verbs.tape

TAPE | 49 LINES | 296 WORDS | 2.5 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Universal Verbs Proposal Process Ribbon )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes operational test rolls validating the 4 universal human verbs:
#   - PREEMPT (turn-taking / priority preemption)
#   - SENSE   (environmental perception & hardware discovery)
#   - AWAKEN  (cold-start inception & active life activation)
#   - PROVE   (balanced-ternary invariant certification)
# ================================================================================

[Tape.UniversalVerbs] : WHO {OmniCode_Kernel} WHAT {HumanVerbs} --> TEST {Lexicon}
    WHEN {IncubationTrial}
    WHERE {verbs_partition} = [ 256 ]
    WHY ( Validate universal human verbs across OS and accessible user domains )
    HOW [ +1 : PROCEED ]
    :: < verbs_landmark > ( Proverbs 4:7 - 'Wisdom is the principal thing; therefore get wisdom' )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Environmental Setup & Test Partition Bounds )
# ================================================================================

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Test Instruction Rolls Exercising Proposed Universal Verbs )
# ================================================================================

# Roll 1: Sense physical memory layout from system firmware
roll_1 [ Kernel --> SENSE {Root_RAM} ] ( Sense available silicon memory frames )

# Roll 2: Prove balanced-ternary arithmetic symmetry in hardware registers
roll_2 [ Kernel --> PROVE {ALU_Equilibrium} ] ( Prove algebraic balance before allocating memory )

# Roll 3: Preempt active background task when timer tick arrives
roll_3 [ Timer_Tick --> PREEMPT {Background_Task} ] ( Preempt task slice to maintain system responsiveness )

# Roll 4: Awaken the interactive terminal session into active life
roll_4 [ Kernel --> AWAKEN {Terminal_Studio} ] ( Awaken console HUD and user interface )

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Verification & Affirmative Commit Seal )
# ================================================================================

# Roll 5: Commit universal verbs proposal tape
roll_5 [ commit_status [ PROCEED ] ] ( Universal verbs proposal tape verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/operators/morphological_operators.omni

OMNI | 121 LINES | 686 WORDS | 5.3 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Operators: Morphological Compounding & Contextual Relational Syntax )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines compound operators that naturally evolve from base morphemes:
#   - ::@ : SituatedAt (Channel bind `::` + Location `@` -> "and at location").
#   - ~!  : CaveatInterrupt (Approximate `~` + Adversative `!` -> "like normal, BUT").
#   - [ { A } < { B } ] : CastedContextComparison (Disambiguated relational comparison).
#   - <=> : InvariantEquivalence (Uncasted invariant equivalence axiom < = >).
#
# THE BOUNDARY TIER COMPARISON CANON:
#   Why must comparison be written as `[ { A } < { B } ]`?
#   1. In OmniCode's 4-tier delimiter ranking, `< ... >` is the Rank 1 Invariant.
#   2. If a coder writes `A < B`, the lexer and parser interpret `<` as the opening
#      of an immutable Invariant tier, causing a syntax collision.
#   3. Therefore, comparison MUST be enclosed in a Rank 2 Denotation block `[ ... ]`,
#      with the compared entities cast into Rank 3 Context brackets `{ ... }`.
#   4. This disambiguates `<` as a relational comparator rather than an Invariant opening.
#   5. Conversely, uncasted `<=>` literally means `< = >`: an Invariant of Equivalence!
# ========================================================================

Module < Lexicon.Suggestions.Operators.Morphological > ( Morphological compound operators and relational syntax ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < MorphemicOperators :: ContextualComparison :: InvariantEquivalence >
}

# 1. Situated-At Operator: < SITUATED_AT >
SituatedAt < InvariantConjunction > ( Compound Conjunction: ::@ - 'and at location' ) {
    grammar_primary: < "Conjunction" >,
    grammar_secondary: < "Preposition" >,
    symbol: < "::@" >,
    abstract_form: < "+SituatedAt" >,
    concrete_form: < "SituatedAt-" >,
    machine_effect: < "hardware_mmio_port_binding" >
}

# 2. Caveat-Interrupt Operator: < CAVEAT_INTERRUPT >
CaveatInterrupt < InvariantConjunction > ( Compound Conjunction: ~! - 'like normal, BUT...' ) {
    grammar_primary: < "Conjunction" >,
    grammar_secondary: < "Preposition" >,
    symbol: < "~!" >,
    abstract_form: < "+CaveatInterrupt" >,
    concrete_form: < "CaveatInterrupt-" >,
    machine_effect: < "asynchronous_preemption_catch" >
}

# 3. Contextual Comparison Operator: < CONTEXT_RELATION >
ContextRelation < InvariantOperator > ( Casted Relational Comparison: [ { A } < { B } ] ) {
    grammar_primary: < "Operator" >,
    grammar_secondary: < "Adjective" >,
    syntax_pattern: < "[ { A } < { B } ]" >,
    machine_effect: < "balanced_ternary_three_way_comparison" >
}

# 4. Invariant Equivalence Axiom: < INVARIANT_EQUIVALENCE >
InvariantEquivalence < InvariantOperator > ( Uncasted Invariant Equivalence: <=> ) {
    grammar_primary: < "Operator" >,
    grammar_secondary: < "Noun" >,
    symbol: < "<=>" >,
    abstract_form: < "+InvariantEquivalence" >,
    concrete_form: < "InvariantEquivalence-" >,
    machine_effect: < "immutable_equivalence_proof" >
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ( Operational Dependencies & Hardware Binding Preconditions )
# ========================================================================
Opening {
    requires: [
        SituatedAt : InvariantConjunction ::
```

```
        CaveatInterrupt : InvariantConjunction ::
        ContextRelation : InvariantOperator ::
        InvariantEquivalence : InvariantOperator
    ],
    preconditions: [ +1 : PROCEED ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Verification Rolls & Concrete Syntax Demonstrations )
# ================================================================================
Body [
    # Demo 1: Situated-At binding of MMIO and Port registers (::@)
    mmio_binding_demo [
        Serial_Port [ COM1 ::@ 0x03F8 ] ::
        Screen_Port [ Screen_VGA ::@ 0x000B8000 ]
    ] ( Inscribe hardware ports situated at concrete silicon addresses )

    # Demo 2: Caveat-Interrupt preemption (~!)
    interrupt_caveat_demo [
        Standard_Process [ Task_Compute ~! [ Timer_Tick --> Preempt ] ]
    ] ( Run task like normal, BUT preempt if timer tick fires )

    # Demo 3: Casted Contextual Comparison ([ { A } < { B } ])
    comparison_demo [
        Bounds_Check [ { Current_Offset } < { Partition_Limit } ]
    ] ( Relational comparison cleanly disambiguated within concrete denotation )

    # Demo 4: Uncasted Invariant Equivalence (<=>)
    equivalence_demo [
        Symmetry_Proof [ (+1) plus (-1) <=> 0 ]
    ] ( Uncasted <=> asserts an invariant state of algebraic equilibrium )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Structural Proof Verification & Covenant Commit Seal )
# ================================================================================
Closing {
    verify: [
        mmio_binding_demo = yes ::
        interrupt_caveat_demo = yes ::
        comparison_demo = yes ::
        equivalence_demo = yes
    ],
    commit_status [ PROCEED ] ( Morphological operator proposals certified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/operators/morphological_operators.tape

TAPE | 49 LINES | 318 WORDS | 2.5 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Morphological Operator Proposal Process Ribbon )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes operational test rolls validating compound operators:
#   - ::@ (Situated-At port/MMIO binding)
#   - ~!  (Caveat-Interrupt asynchronous preemption)
#   - [ { A } < { B } ] (Casted Context Comparison)
#   - <=> (Invariant Equivalence Axiom)
# ================================================================================

[Tape.MorphologicalOperators] : WHO {OmniCode_Kernel} WHAT {CompoundOperators} --> TEST {Lexicon}
    WHEN {IncubationTrial}
    WHERE {test_partition} = [ 256 ]
    WHY ( Validate compound morphemes and casted contextual comparison syntax )
    HOW [ +1 : PROCEED ]
    :: < operator_landmark > ( Ecclesiastes 3:1 - 'To every thing there is a season' )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Environmental Setup & Test Partition Bounds )
# ================================================================================

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Test Instruction Rolls Exercising Proposed Operators )
# ================================================================================

# Roll 1: Bind serial COM1 and VGA ports situated at concrete hardware addresses via ::@
roll_1 [ COM1 ::@ 0x03F8 :: Screen_VGA ::@ 0x000B8000 ] ( Hardware ports bound situated at physical addresses )

# Roll 2: Execute task like normal BUT preempt on timer interrupt via ~!
roll_2 [ Kernel_Compute ~! [ Timer_IRQ --> Preempt ] ] ( Process runs like normal BUT yields on timer tick )

# Roll 3: Evaluate casted contextual comparison within concrete denotation block
roll_3 [ Bounds_Test [ { 16 } < { 64 } ] ] ( Relational comparison safely evaluated inside context brackets )

# Roll 4: Inscribe invariant equivalence axiom proving balanced ternary symmetry
roll_4 [ Balanced_Proof [ (+1) plus (-1) <=> 0 ] ] ( Invariant equivalence asserted )

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Verification & Affirmative Commit Seal )
# ================================================================================

# Roll 5: Commit operator proposal tape
roll_5 [ commit_status [ PROCEED ] ] ( Morphological operators proposal tape verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/boot_kernel.omni

OMNI | 91 LINES | 441 WORDS | 3.9 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Operators: Boot Inception & Anti-Lockout Sentinel Invariants )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Establishes the primordial Hardware Boot Operator (--> BOOT) and Anti-Lockout
#   Guardians within the balanced ternary execution engine:
#   - Boot Operator (--> BOOT) : Hardware root inception vector bound exclusively to Kernel authority.
#   - Watchdog Sentinel (Watchdog_Guard) : Preemptive cycle counter preventing AI infinite loops.
#   - Kernel Shield (Kernel_Partition_Barrier) : Memory protection preventing AI privilege escalation.
# ========================================================================

Module < Lexicon.Operators.BootKernel > ( Boot inception operator and anti-lockout safety invariants ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < HardwareBootInception :: AntiLockoutWatchdog :: KernelShieldAuthority >
}

# 1. Invariant Operator: < BOOT_OPERATOR > (--> BOOT)
Boot_Operator < InvariantOperator > ( Primordial Hardware Inception Vector ) {
    symbol: < "--> BOOT" >,
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Noun" >,
    authority_required: < "OmniCode_Kernel" >,
    channel_binding: < "Track 0 [KERNEL]" >,
    cost: < 1 >,
    memory_footprint: < "root hardware vector" >,
    machine_effect: < "hardware_cold_boot_vector" >
}

# 2. Invariant Operator: < ANTI_LOCKOUT_SENTINEL >
Anti_Lockout_Sentinel < InvariantOperator > ( Execution Watchdog & Preemption Safeguard ) {
    symbol: < "Watchdog_Guard" >,
    grammar_primary: < "Adjective" >,
    grammar_secondary: < "Noun" >,
    max_loop_threshold: < 1000 >,
    cyclic_retroaction_limit: < 100 >,
    failsafe_state: < "AWAIT :: ROLLBACK" >,
    machine_effect: < "preemptive_scheduler_watchdog" >
}

# 3. Invariant Operator: < KERNEL_SHIELD >
Kernel_Shield < InvariantOperator > ( Memory Partition & MMIO Access Barrier ) {
    symbol: < "Kernel_Partition_Barrier" >,
    grammar_primary: < "Preposition" >,
    grammar_secondary: < "Noun" >,
    protected_regions: < [ 0x00000000..0x000FFFFF, "Track 0 [KERNEL]" ] >,
    unauthorized_action: < "Failpoint [AuthorityViolation] --> ROLLBACK" >,
    machine_effect: < "hardware_memory_protection_ring" >
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {
    requires: [
        Boot_Operator : InvariantOperator ::
        Anti_Lockout_Sentinel : InvariantOperator ::
        Kernel_Shield : InvariantOperator
    ],
    preconditions: [ +1 ]
}

status_equilibrium [ yes ] ( Boot operator and anti-lockout guard active )

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    # 1. Hardware Boot Inception Verification
    boot_verification [ OmniCode_Kernel --> BOOT {Hardware} ] ( Exclusive kernel authority boots root substrate )

    # 2. Anti-Lockout Loop Safeguard Verification
```

```
    watchdog_check [ Loop_Count < Anti_Lockout_Sentinel.max_loop_threshold ! [ AWAIT ] ] ( Watchdog trips before machine lockup )

    # 3. Kernel Shield Memory Protection Verification
    shield_check [ AI_Process != Kernel_Shield.protected_regions ! [ ROLLBACK ] ] ( Sandboxed AI cannot breach kernel memory )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        boot_verification = yes ::
        watchdog_check = yes ::
        shield_check = yes
    ],
    commit_status [ PROCEED- ] ( Boot operator and anti-lockout sentinel sealed in concrete execution )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/boot_kernel.tape

TAPE | 37 LINES | 264 WORDS | 2.0 KB

```
# ================================================================================
# TAPE HEAD: THE BOOT INCEPTION & ANTI-LOCKOUT OPERATOR PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes the hardware boot inception sequence while actively enforcing
#   anti-lockout watchdog invariants against infinite loops and AI memory leakage.
# ================================================================================

[Tape.BootKernelOperator] : WHO {OmniCode_Kernel} WHAT {BootOperator} --> BOOT {Hardware}
    WHEN {PowerOn}
    WHERE {boot_partition} = [ 256 ]
    WHY ( Instate root machine execution while securing OS against AI deadlock or lockout )
    HOW [ +1 : PROCEED ]
    :: < boot_landmark > ( Psalms 119:105 - 'A lamp unto my feet, and a light unto my path' )

# ================================================================================
# SUBORDINATE ROLLS: BOOT OPERATOR & WATCHDOG SENTINEL EXECUTION
# ================================================================================

# Roll 1: Assert Kernel authority on Track 0
roll_1 [ OmniCode_Kernel --> Track_0_Active @ 0 ] ( Establish supervisor authority channel )

# Roll 2: Inscribe Anti-Lockout Watchdog ceiling
roll_2 [ Watchdog_Threshold [ 1000 ] ] ( Maximum loop cycles before watchdog preempts )

# Roll 3: Direct video console banner stream to bare-metal VGA buffer
roll_3 [ 'OMNICODE 32-TRIT OS ONLINE' --> Screen_VGA @ 0x000B8000 ] ( Direct MMIO character stream to VGA buffer )

# Roll 4: Inscribe kernel memory partition shield
roll_4 [ Kernel_Partition_Shield [ Root_RAM v-- Kernel_Partition [ 1024 ] ] ] ( Protect kernel from user/AI intrusion )

# Roll 5: Verify anti-lockout loop preemption tripwire
roll_5 [ Watchdog_Active = 1 ! [ AWAIT ] ] ( Verify tripwire halts runaway execution )

# Roll 6: Genesis Boot Complete with concrete commit
roll_6 [ commit_status [ PROCEED- ] ] ( Boot operator and anti-lockout verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/casting.omni

OMNI | 88 LINES | 393 WORDS | 3.1 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Boundary Casting Invariants: Molds & Dies for Ontological Transduction )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   This reel establishes the 6 canonical boundary casting operators:
#   - [+] : Denotative Abstract Cast (cast essence to archetype)
#   - [-] : Denotative Concrete Cast (cast essence to physical memory)
#   - <+> : Invariant Abstract Cast (cast to immutable universal axiom)
#   - <-> : Invariant Concrete Cast (cast to immutable hardware/ROM constant)
#   - {+} : Connotative Abstract Cast (cast context to ideal universe)
#   - {-} : Connotative Concrete Cast (cast context to physical execution partition)
# ========================================================================

Module < Lexicon.Operators.Casting > ( Boundary casting molds and transduction operators ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < BoundaryCasting :: MorphologicalMolds :: TransductionGates >
}

# 1. Denotation Casts
Denotation_Abstract < InvariantCast > ( Cast essence to abstract archetype ) {
    syntax: < "[+]" >,
    target_rank: < 2 >,
    polarity: < "+" >
}

Denotation_Concrete < InvariantCast > ( Cast essence to concrete memory substance ) {
    syntax: < "[-]" >,
    target_rank: < 2 >,
    polarity: < "-" >
}

# 2. Invariant Casts
Invariant_Abstract < InvariantCast > ( Cast boundary to transcendental immutable axiom ) {
    syntax: < "<+>" >,
    target_rank: < 1 >,
    polarity: < "+" >
}

Invariant_Concrete < InvariantCast > ( Cast boundary to immutable physical ROM constraint ) {
    syntax: < "<->" >,
    target_rank: < 1 >,
    polarity: < "-" >
}

# 3. Connotation Casts
Connotation_Abstract < InvariantCast > ( Cast environment to conceptual universe ) {
    syntax: < "{+}" >,
    target_rank: < 3 >,
    polarity: < "+" >
}

Connotation_Concrete < InvariantCast > ( Cast environment to concrete silicon partition ) {
    syntax: < "{-}" >,
    target_rank: < 3 >,
    polarity: < "-" >
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {
    requires: [
        Denotation_Abstract : InvariantCast ::
        Denotation_Concrete : InvariantCast
    ],
    preconditions: [ +1 ]
}

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
```

```
Body [
    # Verify freeform casting across boundaries
    cast_gate [ [+] --> [-] ] ( Transduction: Abstract essence poured into concrete form )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        cast_gate = yes
    ],
    commit_status [ PROCEED- ] ( Casting engine active and verified )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/casting.tape

TAPE | 30 LINES | 170 WORDS | 1.4 KB

```
# ================================================================================
# TAPE HEAD: THE BOUNDARY CASTING PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes freeform boundary casting across all canonical ranks.
# ================================================================================

[Tape.BoundaryCasting] : WHO {OmniCode_Kernel} WHAT {Casting} --> EXECUTE {FoundryMolds}
    WHEN {GenesisBoot}
    WHERE {casting_partition} = [ 256 ]
    WHY ( Inscribe verified boundary casting physics )
    HOW [ +1 : PROCEED ]
    :: < mold_landmark > ( Job 38:14 - 'It is turned as clay to the seal' )

# ================================================================================
# SUBORDINATE ROLLS: CASTING OPERATION ROLLS
# ================================================================================

# Roll 1: Transduce Denotation from abstract to concrete
roll_1 [ [+] --> [-] ] ( Denotative foundry cast )

# Roll 2: Transduce Invariant boundary to concrete ROM constant
roll_2 [ <+> --> <-> ] ( Invariant axiom solidified into hardware constraint )

# Roll 3: Transduce Connotation from ideal to physical partition
roll_3 [ {+} --> {-} ] ( Ambient context grounded into physical memory )

# Roll 4: Seal casting tape
roll_4 [ commit_status [ PROCEED- ] ] ( Casting covenant sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/polarity.omni

OMNI | 74 LINES | 338 WORDS | 3.0 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Polarity Invariants: Abstract (+) vs Concrete (-) Ground Truth )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   This reel establishes the primordial duality of being in OmniCode:
#   - Abstract (+) : The uninstantiated intension, archetype, and zero-cost blueprint.
#   - Concrete (-) : The physical extension, allocated memory substance, and operational reality.
# ================================================================================

Module < Lexicon.Operators.Polarity > ( Primordial ontological polarity operators ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < PolarityPhysics :: AbstractArchetypes :: ConcreteSubstances >
}

# 1. Invariant Operator: < ABSTRACT > (+)
Abstract_Polarity < InvariantOperator > ( Universal Archetype / Uninstantiated Essence ) {
    symbol: < "+" >,
    grammar_primary: < "Adjective" >,
    grammar_secondary: < "Noun" >,
    cost: < 0 >,
    memory_footprint: < "zero-cost symbolic form" >,
    machine_effect: < "type_specification_and_contract" >
}

# 2. Invariant Operator: < CONCRETE > (-)
Concrete_Polarity < InvariantOperator > ( Physical Substance / Allocated Instance ) {
    symbol: < "-" >,
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Adjective" >,
    cost: < 1 >,
    memory_footprint: < "physical silicon RAM cells" >,
    machine_effect: < "allocated_memory_and_bus_state" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Syntactic Preconditions & Affix Attachment Contracts )
# ================================================================================
Opening {
    requires: [
        Abstract_Polarity : InvariantOperator ::
        Concrete_Polarity : InvariantOperator
    ],
    preconditions: [ +1 ]
}

status_equilibrium [ yes ] ( Polarity engine active in nominal equilibrium )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Polarity Modulations Mapped to Architectural Types )
# ================================================================================
Body [
    # 1. Affirmation of Dual Polarity
    polarity_check [ Abstract_Polarity != Concrete_Polarity ] ( Duality: Abstract is distinct from Concrete )

    # 2. Transduction Verification
    transduction_vector [ +Dog --> Dog- ] ( Lowering vector: Abstract idea transduced to Concrete substance )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Invariant Verification & Permanent Affirmative Commit )
# ================================================================================
Closing {
    verify: [
        polarity_check = yes ::
        transduction_vector = yes
    ],
```

```
    commit_status [ PROCEED- ] ( Polarity operators sealed in concrete execution )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/polarity.tape

TAPE | 30 LINES | 179 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: THE POLARITY TRANSFORMATION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes the dynamic shift between abstract definitions and concrete memory.
# ================================================================================

[Tape.PolarityTransformation] : WHO {OmniCode_Kernel} WHAT {Polarity} --> ESTABLISH {DualStatePhysics}
    WHEN {GenesisBoot}
    WHERE {cortex_partition} = [ 256 ]
    WHY ( Prove seamless transmutation between archetype and substance )
    HOW [ +1 : PROCEED ]
    :: < polarity_landmark > ( Ecclesiastes 3:1 - 'To every thing there is a season' )

# ================================================================================
# SUBORDINATE ROLLS: POLARITY AFFIX EXECUTION & VERIFICATION
# ================================================================================

# Roll 1: Reference abstract entity without memory allocation
roll_1 [ +Archetype ] ( Abstract reference: zero memory cost )

# Roll 2: Allocate concrete instance in physical partition
roll_2 [ Concrete- [ 1024 ] ] ( Concrete allocation: physical storehouse footprint )

# Roll 3: Execute directional transmutation from abstract to concrete
roll_3 [ +Archetype --> Concrete- ] ( Direct transmutation of archetype into substance )

# Roll 4: Verify macro keyword in concrete postfix execution
roll_4 [ commit_status [ PROCEED- ] ] ( Concrete execution commit confirmed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/self_handles.omni

OMNI | 81 LINES | 338 WORDS | 2.9 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Pronouns: Context Handles & Pivot Pins )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines context-relative pointers and local pivot pins:
#   - self   : The currently executing frame or active entity instance.
#   - caller : The upstream activating frame or invoking principal.
#   - owner  : The sovereign allocation custodian holding memory boundary rights.
# ================================================================================

Module < Lexicon.Pronouns.SelfHandles > ( Local pivot pins and frame-relative context handles ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < SelfHandles :: ContextPointers :: FrameResolution >
}

# 1. Local Handle: < SELF >
Self < InvariantPronoun > ( The Currently Executing Local Frame Pointer: self ) {
    grammar_primary: < "Pronoun" >,
    grammar_secondary: < "Noun" >,
    symbol: < "self" >,
    abstract_form: < "+Self" >,
    concrete_form: < "Self-" >,
    machine_effect: < "current_frame_handle" >
}

# 2. Invoker Handle: < CALLER >
Caller < InvariantPronoun > ( The Upstream Activating Frame Pointer: caller ) {
    grammar_primary: < "Pronoun" >,
    grammar_secondary: < "Noun" >,
    symbol: < "caller" >,
    abstract_form: < "+Caller" >,
    concrete_form: < "Caller-" >,
    machine_effect: < "upstream_invoker_handle" >
}

# 3. Custodian Handle: < OWNER >
Owner < InvariantPronoun > ( Sovereign Allocation Custodian: owner ) {
    grammar_primary: < "Pronoun" >,
    grammar_secondary: < "Noun" >,
    symbol: < "owner" >,
    abstract_form: < "+Owner" >,
    concrete_form: < "Owner-" >,
    machine_effect: < "sovereign_boundary_custodian" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Self : InvariantPronoun ::
        Caller : InvariantPronoun ::
        Owner : InvariantPronoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify frame resolution handles
    handles_verification [
        Frame_Resolution [ self --> Active_Context ] ::
        Caller_Resolution [ caller --> Parent_Context ] ::
        Owner_Resolution  [ owner --> Storage_Custodian ]
    ] ( Context handle resolution verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
```

```
# ================================================================================
Closing {
    verify: [
        handles_verification = yes
    ],
    commit_status [ PROCEED- ] ( Self handle pronouns verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/self_handles.tape

TAPE | 30 LINES | 187 WORDS | 1.4 KB

```
# ================================================================================
# TAPE HEAD: SELF HANDLES EXECUTION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes context pointer resolution for self, caller, and owner.
# ================================================================================

[Tape.SelfHandles] : WHO {OmniCode_Kernel} WHAT {SelfHandles} --> RESOLVE {ContextMesh}
    WHEN {GenesisBoot}
    WHERE {handle_partition} = [ 64 ]
    WHY ( Test local frame pointers and context handles )
    HOW [ +1 : PROCEED ]
    :: < handle_landmark > ( 1 Corinthians 12:27 - 'Ye are the body of Christ, and members in particular' )

# ================================================================================
# SUBORDINATE ROLLS: SCOPED CALLER AND FRAME RESOLUTION
# ================================================================================

# Roll 1: Reference abstract Self, Caller, and Owner specifications
roll_1 [ +Self & +Caller & +Owner ] ( Abstract handle blueprints referenced )

# Roll 2: Assign local frame handle
roll_2 [ self --> Local_Frame_0 @ 0 ] ( Bind active frame to local cell )

# Roll 3: Verify caller resolution invariance
roll_3 [ caller != self ! [ +1 ] ] ( Verify caller and callee frame distinction )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Self handle pronouns verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/wildcards.omni

OMNI | 81 LINES | 342 WORDS | 3.0 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Pronouns: Wildcards & Dynamic Context Couplings )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines anonymous references and antecedent couplings:
#   - _      : Anonymous discard, sink, or universal pattern wildcard.
#   - it     : Antecedent reference, pipeline accumulator, or active subject.
#   - origin : Root origin pointer, initial coordinate (0,0,0) or Genesis base.
# ================================================================================

Module < Lexicon.Pronouns.Wildcards > ( Wildcards and dynamic context couplings ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < Wildcards :: AntecedentCouplings :: AnonymousDiscards >
}

# 1. Anonymous Wildcard: < _ >
Wildcard < InvariantPronoun > ( Universal Wildcard & Anonymous Discard: _ ) {
    grammar_primary: < "Pronoun" >,
    grammar_secondary: < "Noun" >,
    symbol: < "_" >,
    abstract_form: < "+Wildcard" >,
    concrete_form: < "Wildcard-" >,
    machine_effect: < "anonymous_sink_discard" >
}

# 2. Pipeline Antecedent: < IT >
Antecedent < InvariantPronoun > ( Pipeline Antecedent & Active Subject: it ) {
    grammar_primary: < "Pronoun" >,
    grammar_secondary: < "Noun" >,
    symbol: < "it" >,
    abstract_form: < "+Antecedent" >,
    concrete_form: < "Antecedent-" >,
    machine_effect: < "pipe_antecedent_register" >
}

# 3. Genesis Origin: < ORIGIN >
Origin < InvariantPronoun > ( Root Genesis Origin Pointer: origin ) {
    grammar_primary: < "Pronoun" >,
    grammar_secondary: < "Noun" >,
    symbol: < "origin" >,
    abstract_form: < "+Origin" >,
    concrete_form: < "Origin-" >,
    machine_effect: < "root_genesis_base_pointer" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Wildcard : InvariantPronoun ::
        Antecedent : InvariantPronoun ::
        Origin : InvariantPronoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify anonymous discard and pipeline antecedent
    couplings_verification [
        Discard_Roll    [ Value --> _ ] ::
        Antecedent_Roll [ Input --> it :: it --> Output ] ::
        Origin_Roll     [ Current_Position <-- origin ]
    ] ( Context wildcards and dynamic couplings verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
```

```
# ================================================================================
Closing {
    verify: [
        couplings_verification = yes
    ],
    commit_status [ PROCEED- ] ( Wildcard pronouns verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/wildcards.tape

TAPE | 30 LINES | 193 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: WILDCARDS EXECUTION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes anonymous discard (_), antecedent piping (it), and origin coupling.
# ================================================================================

[Tape.Wildcards] : WHO {OmniCode_Kernel} WHAT {Wildcards} --> COUPLE {ContextMesh}
    WHEN {GenesisBoot}
    WHERE {wildcard_partition} = [ 64 ]
    WHY ( Test anonymous wildcards, antecedent couplings, and origin pointers )
    HOW [ +1 : PROCEED ]
    :: < wildcard_landmark > ( Genesis 1:1 - 'In the beginning God created the heaven and the earth' )

# ================================================================================
# SUBORDINATE ROLLS: ANONYMOUS REFERENCE PROPAGATION
# ================================================================================

# Roll 1: Reference abstract Wildcard, Antecedent, and Origin specifications
roll_1 [ +Wildcard & +Antecedent & +Origin ] ( Abstract wildcard blueprints referenced )

# Roll 2: Transduce input into pipeline antecedent
roll_2 [ 77 --> it @ 0 ] ( Load value into antecedent accumulator )

# Roll 3: Route antecedent to concrete cell and discard extra to wildcard
roll_3 [ it --> Cell_Target_0 :: Noise --> _ ! [ +1 ] ] ( Pipe antecedent and discard noise )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Wildcard pronouns verified and sealed )
```