OmniCode: Chapter 1: Foundations, Manifest & Decalogue Bedrock

Moral Bedrock, Exodus 20 Decalogue, Manifest & Packaging

CHAPTER IDENTIFIER	**NOTEBOOKLM WORD COUNT**
CH 01	10,729 words
CATALOGED CHAPTER FILES	**GENERATION DATE**
5 files (1,630 lines)	2026-10-16 20:35:47

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"How does the Exodus 20 Decalogue govern the AI cortex?"*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (5 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**Cargo.lock**	LOCK	168	342	4.4
2	**Cargo.toml**	TOML	193	1,131	9.8
3	**README.md**	MD	514	3,977	35.2
4	**manifest.omni**	OMNI	555	3,643	27.0
5	**manifest.tape**	TAPE	200	1,636	9.6

Cargo.lock LOCK 168 LINES 342 WORDS 4.4 KB

```
# This file is automatically @generated by Cargo.
# It is not intended for manual editing.
version = 4

[[package]]
name = "bitflags"
version = "2.13.2"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "3ded4057c258ba199e2d26386d3af3780957ecaee6c4ef4041c6b4b8b97c0b06"

[[package]]
name = "cfg-if"
version = "1.0.5"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "4e7648175b45a9a48536d676f68d918270699102aa8dab5496df06904c914600"

[[package]]
name = "cfg_aliases"
version = "0.2.2"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "f079e83a288787bcd14a6aea84cee5c87a67c5a3e660c30f557a3d24761b3527"

[[package]]
name = "clipboard-win"
version = "5.4.1"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "bde03770d3df201d4fb868f2c9c59e66a3e4e2bd06692a0fe701e7103c7e84d4"
dependencies = [
 "error-code",
]

[[package]]
name = "endian-type"
version = "0.2.0"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "869b0adbda23651a9c5c0c3d270aac9fcb52e8622a8f2b17e57802d7791962f2"

[[package]]
name = "error-code"
version = "3.4.0"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "0b5343afd4a8365a643ac588dab4cf234a190c7f6c88c9f6dd6ffe00837661b7"

[[package]]
name = "home"
version = "0.5.12"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "cc627f471c528ff0c4a49e1d5e60450c8f6461dd6d10ba9dcd3a61d3dff7728d"
dependencies = [
 "windows-sys",
]

[[package]]
name = "libc"
version = "0.2.190"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "ce5d3ddc6d3fa000eb1536d85e147bfe31aacaba692ed6a876f95cb7c855be78"

[[package]]
name = "log"
version = "0.4.34"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "f9f8bd3e56ce4dfc153cf470fffbfa98c7620958b312ca5c3a4b8d5181fd13c6"

[[package]]
name = "memchr"
version = "2.8.3"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "cf8baf1c55e62ffcace7a9f06f4bd9cd3f0c4beb022d3b367256b91b87513d98"

[[package]]
name = "nibble_vec"
version = "0.1.0"
source = "registry+https://github.com/rust-lang/crates.io-index"
```

```
checksum = "77a5d83df9f36fe23f0c3648c6bbb8b0298bb5f1939c8f2704431371f4b84d43"
dependencies = [
 "smallvec",
]

[[package]]
name = "nix"
version = "0.31.3"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "cf20d2fde8ff38632c426f1165ed7436270b44f199fc55284c38276f9db47c3d"
dependencies = [
 "bitflags",
 "cfg-if",
 "cfg_aliases",
 "libc",
]

[[package]]
name = "omnicode"
version = "0.1.0"
dependencies = [
 "rustyline",
]

[[package]]
name = "radix_trie"
version = "0.3.0"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "3b4431027dcd37fc2a73ef740b5f233aa805897935b8bce0195e41bbf9a3289a"
dependencies = [
 "endian-type",
 "nibble_vec",
]

[[package]]
name = "rustyline"
version = "18.0.1"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "53f6a737db68eb1a8ccff86b584b2fc13eca6a7bb6f78ebc7c529547e3ab9684"
dependencies = [
 "bitflags",
 "cfg-if",
 "clipboard-win",
 "home",
 "libc",
 "log",
 "memchr",
 "nix",
 "radix_trie",
 "unicode-segmentation",
 "unicode-width",
 "utf8parse",
 "windows-sys",
]

[[package]]
name = "smallvec"
version = "1.16.2"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "f9395f0f0eee849a9b707b2f06bb92a6a422090e2123bb2ef8e87a0e61892a8e"

[[package]]
name = "unicode-segmentation"
version = "1.13.3"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "c6f5d3c3b1bf09027a88a6bc961fc00497d651009560b5463668dc81b0fa87a8"

[[package]]
name = "unicode-width"
version = "0.2.2"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "b4ac048d71ede7ee76d585517add45da530660ef4390e49b098733c6e897f254"

[[package]]
name = "utf8parse"
version = "0.2.2"
source = "registry+https://github.com/rust-lang/crates.io-index"
checksum = "06abde3611657adf66d383f00b093d7faecc7fa57071cce2578660c9f1010821"
```

```
153
154 [[package]]
155 name = "windows-link"
156 version = "0.2.1"
157 source = "registry+https://github.com/rust-lang/crates.io-index"
158 checksum = "f0805222e57f7521d6a62e36fa9163bc891acd422f971defe97d64e70d0a4fe5"
159
160 [[package]]
161 name = "windows-sys"
162 version = "0.61.2"
163 source = "registry+https://github.com/rust-lang/crates.io-index"
164 checksum = "ae137229bcbd6cdf0f7b80a31df61766145077ddf49416a728b02cb3921ff3fc"
165 dependencies = [
166  "windows-link",
167 ]
```

Cargo.toml TOML 193 LINES 1131 WORDS 9.8 KB

```toml
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Package Identity, Edition, Manifest Attributes, License & Ontological Scope )
# ================================================================================
# Package:       omnicode
# Version:       0.1.0
# Edition:       2024 (Leverages latest Rust 2024 idioms, lifetime rules & generators)
# Rust Version:  1.85+
# License:       MIT OR Apache-2.0
# Organization:  CreativeWorkzStudio LLC
# Repository:    https://github.com/Novaking34/OmniCode_Framework
# Homepage:      https://github.com/Novaking34/OmniCode_Framework
# Documentation: https://github.com/Novaking34/OmniCode_Framework/tree/master/docs
#
# PURPOSE & ARCHITECTURAL PHILOSOPHY:
#   OmniCode is a dual-readable, multi-track programming language engine and bare-metal
#   operating system engineered for unambiguous human comprehension and deterministic
#   machine execution. It unifies bare-metal memory/register control with high-level
#   balanced ternary logic (T4 = {-1, 0, +1, NULL}), morphological boundary physics,
#   first-class asides, and an episodic neural-symbolic cognitive loop.
#
# WHY EXTENSIVE COMMENTING MATTERS FOR AI AGENTS & COLLABORATORS:
#   1. The Manifest is the Machine Contract:
#      `Cargo.toml` is the primordial contract any AI coding agent (and human engineer)
#      inspects to infer project capabilities, dependencies, and compilation targets.
#   2. Dependency Invariance & Anti-Bloat Guardrails:
#      AI agents tend to "solve" problems by injecting external crates (e.g. `regex`,
#      `serde`, `nom`, `tokio`). Detailed comments establish explicit guardrails:
#      OmniCode intentionally implements its own lexer, parser, and runtime to guarantee
#      zero-overhead bare-metal portability. External crates are kept strictly minimal.
#   3. Multi-Track Decoupling & Future Growth:
#      The engine decouples the Host VM (Track 1) from the Standard Library Lexicon
#      (Track 2) and Episodic Storage (Track 4). Expanding into composite boundary
#      types (such as Container) preserves this invariant separation of concerns.
#   4. Compiler Profile Rationale:
#      Explains non-obvious optimization flags (`panic = "abort"`, `lto = true`) that
#      are essential for bare-metal compilation, binary compacting, and determinism.
# ================================================================================

[package]
name = "omnicode"
version = "0.1.0"
edition = "2024"
rust-version = "1.85"
authors = ["ProfessorSeanEX", "CreativeWorkzStudio LLC"]
description = "A Dual-Readable Ontological Programming Language Engine Grounded in Balanced Ternary and Morphological Boundaries"
readme = "README.md"
license = "MIT OR Apache-2.0"
repository = "https://github.com/Novaking34/OmniCode_Framework"
homepage = "https://github.com/Novaking34/OmniCode_Framework"
documentation = "https://github.com/Novaking34/OmniCode_Framework/tree/master/docs"
keywords = ["omnicode", "ternary", "compiler", "ontology", "ai-model", "operating-system", "bare-metal"]
categories = ["compilers", "development-tools"]
exclude = [
    "/target",
    "*.vsix",
    "node_modules/",
    ".DS_Store"
]


# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Engine Dependencies, Runtime Context & External Crates )
# ================================================================================
# DEPENDENCY POLICY & JUSTIFICATION:
#   - Zero-Bloat Philosophy:
#     OmniCode does NOT use external parser generators, heavy async runtimes, or
#     uncontrolled third-party dependencies. Every core component—from the recursive-
#     descent parser to the transactional snapshot debugger—is implemented natively.
#   - rustyline (18.0.1):
#     The sole production dependency. Provides cross-platform terminal line-editing,
#     ANSI escape sequences, history persistence (`.omnicode_history`), and multi-line
```

```
#     bracket-balanced input buffering for the interactive REPL shell (`src/cli/repl.rs`).
# ================================================================================

[dependencies]
# Interactive CLI shell line-editing, input buffering, and terminal history
rustyline = "18.0.1"


# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Target Layout, Compilation Binaries, Integration Test Suites & Profiles )
# ================================================================================
# TARGET TOPOLOGY & ARCHITECTURAL DECOUPLING:
#   - [lib] (Track 1 / src/lib.rs):
#     Exposes the engine's core reusable API surface:
#     * `core`: Boundaries, Operators, Ternary QuadState, FileTypes, Cell, Vessel, Tape, Linguistics.
#     * `ast`: Strongly-typed AST nodes preserving Asides `(...)`.
#     * `parser`: Directional Lexer and recursive-descent Parser.
#     * `runtime`: Transactional Environment and QuadState Evaluator.
#     * `diagnostics`: OmniLinter, DiagnosticLogger, OmniDebugger, Restorator.
#     * `ai`: AICortex, SemanticTransducer, ScrollLogger, AILearner, BiblicalLexicon, AIMemory.
#     * `terminal`: OmniScheduler, TerminalSession.
#   - [[bin]] (Track 1 / src/main.rs):
#     CLI dispatcher hosting commands: `repl`, `run` (.omni/.scroll/.tape), `echo`,
#     `assemble`, `studio`, `boot`, `lint`, `hover`, `doc`, `restore`, `ai`,
#     `interact`, `train`, `noise`, `query`, `diagnose`, `rotate`, `scrolls`,
#     `manifest`, `lexicon`, `gui`, `desktop`, `scaffold`, `filetypes`, and `demo`.
# ================================================================================

[lib]
name = "omnicode"
path = "<TRACK 1> : {Host Engine & Virtual Machine}/src/lib.rs"

[[bin]]
name = "omnicode"
path = "<TRACK 1> : {Host Engine & Virtual Machine}/src/main.rs"

# --------------------------------------------------------------------------------
# 3-TIER TEST SUITE TOPOLOGY (UNIT, INTEGRATED, FUNCTIONAL, TRIPWIRES)
# Explicitly declared test targets organized by scope and verification fidelity:
# --------------------------------------------------------------------------------

# 1. Component Isolation Unit Test Suite
# Tests isolated boundary ranking, ternary QuadState algebra, operators, formats
[[test]]
name = "unit_tests"
path = "<TRACK 1> : {Host Engine & Virtual Machine}/tests/unit/main.rs"

# 2. Subsystem Integration & Self-Healing Feedback Loop Suite
# Tests boundary traps, failpoints, retroaction, imports, and Logger->Debugger test oracle
[[test]]
name = "integrated_tests"
path = "<TRACK 1> : {Host Engine & Virtual Machine}/tests/integrated/main.rs"

# 3. End-to-End Functional, AI Cortex & File Lifecycle Suite
# Tests REPL simulation, canonical script runs, dual scrolls, and episodic memory digestion
[[test]]
name = "functional_tests"
path = "<TRACK 1> : {Host Engine & Virtual Machine}/tests/functional/main.rs"

# 4. Bare-Metal Boot Inception, Tripwires & Self-Healing Telemetry Test Suite
# Tests boot tripwire sensors, failpoint capture, logger/debugger telemetry handoff to the Restorator
[[test]]
name = "boot_tripwire_tests"
path = "<TRACK 1> : {Host Engine & Virtual Machine}/tests/integrated/boot_tripwire_tests.rs"

# 5. Platform Adapter Adversarial Faults & Telemetry Oracle Suite
# Pushes platform adapters to fail under hostile conditions, verifying tripwire telemetry and Restorator remediation
[[test]]
name = "platform_tripwire_tests"
path = "<TRACK 1> : {Host Engine & Virtual Machine}/tests/integrated/platform_tripwire_tests.rs"

# 6. Physical Assembler & Process Tape Lowering Adversarial Faults & Telemetry Suite
# Pushes process tape lowering to fail under hostile conditions, verifying tripwires, word emissions, and rollback
oracles
[[test]]
name = "assemble_tripwire_tests"
path = "<TRACK 1> : {Host Engine & Virtual Machine}/tests/integrated/assemble_tripwire_tests.rs"
```

```
151
152 # ------------------------------------------------------------------------------
153 # COMPILATION PROFILES & BARE-METAL OPTIMIZATIONS
154 # ------------------------------------------------------------------------------
155
156 # Development profile: Fast compilation, full debug symbols, zero optimization
157 [profile.dev]
158 opt-level = 0
159 debug = true
160 overflow-checks = true
161
162 # Release profile: Maximum speed, full link-time optimization, bare-metal safety
163 [profile.release]
164 opt-level = 3
165 lto = true              # Link-Time Optimization: enables cross-crate inlining for zero-cost abstractions
166 codegen-units = 1      # Single codegen unit: maximizes LLVM inter-procedural analysis and optimization
167 panic = "abort"        # Eliminates unwinding landing pads and `eh_personality` runtime bloat, essential for bare-metal
targets
168 strip = "debuginfo"    # Strips debug symbols to produce compact native binaries
169
170 # Benchmark profile: Inherits release optimizations with debug symbols enabled for profiling
171 [profile.bench]
172 opt-level = 3
173 lto = true
174 codegen-units = 1
175
176
177 # ==============================================================================
178 # BLOCK 4: CLOSING BLOCK
179 # ( Verification Constraints, Workspace Invariants & Packaging Seal )
180 # ==============================================================================
181 # WORKSPACE INVARIANTS:
182 #   - Test Suite Verification: All 265 automated unit, integrated, functional,
183 #     assemble, platform, and boot tripwire tests across the 7 test harnesses
184 #     MUST pass cleanly (206 in lib, 16 unit, 14 integrated, 12 functional,
185 #     7 assemble tripwire, 5 boot tripwire, 5 platform tripwire).
186 #   - Rust Edition: Sealed under Edition 2024 with zero unhandled compiler warnings.
187 #   - Memory Guarantee: No uncontrolled allocations or unhandled panics across
188 #     the entire evaluation and diagnostic pipeline.
189 #   - Transpilation Parity: Track 1 Host VM maintains 1:1 structural parity with
190 #     Track 2 Standard Library Lexicon transpilation backbones (C and Lua).
191 # Status: CARGO_MANIFEST_SEALED (+1:PROCEED)
192 # ==============================================================================
```

README.md MD 514 LINES 3977 WORDS 35.2 KB

```
# OmniCode

> **A Dual-Readable Ontological Programming Language & Bare-Metal OS Engineered for Unambiguous Human Comprehension and Machine Determinism.**

---

### Manifest Metadata & Covenant Identity

| Attribute | Specification |
| :--- | :--- |
| **Engine Version** | `0.1.0` |
| **Organization** | CreativeWorkzStudio LLC |
| **Repository** | [https://github.com/Novaking34/OmniCode_Framework](https://github.com/Novaking34/OmniCode_Framework) |
| **Core Runtime** | [Rust Engine (`edition = "2024"`, `rust-version = "1.85+"`)](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/lib.rs) |
| **Execution Truth Space** | Balanced Ternary Quad-State ($\mathbb{T}_4 = \{ -1, 0, +1, \text{NULL} \}$) ([`QuadState`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/core/ternary/quad_state.rs), [Specification](file:///home/professorseanex/OmniCode/docs/02_logic_and_algebra/01_balanced_ternary_quad_state.md)) |
| **Structural Paradigm** | Implicit 4-Block Lifecycle (`Metadata` $\to$ `Opening` $\to$ `Body` $\to$ `Closing`) ([`OmniLinter`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/diagnostics/linter/core.rs), [Specification](file:///home/professorseanex/OmniCode/docs/03_architecture/03_four_block_architecture.md)) |
| **Morphological Physics** | 6 Boundary Types (`[]`, `<>`, `{}`, `{]`, `[}`, `()`) ([`BoundaryType`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/core/boundaries.rs), [Specification](file:///home/professorseanex/OmniCode/docs/01_foundations/02_boundary_types_and_asides.md)) |
| **Universal Linguistics** | 8 Parts of Speech Matrix & 8-Slot Canonical Sentences ([`linguistics.rs`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/core/linguistics.rs), [Specification](file:///home/professorseanex/OmniCode/docs/01_foundations/03_eight_parts_of_speech_matrix.md)) |
| **Physical Memory Model** | 8-Bit $\longleftrightarrow$ 5-Trit Bijective Codec & Bounded Storehouses with `v--` Partitioning ([`cell.rs`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/core/cell.rs), [`vessel.rs`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/core/vessel.rs)) |
| **Operating System Genesis** | Multi-Track Process Tapes (`Roll` $\to$ `Tape` $\to$ `Track` 0–5) ([`OmniScheduler`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/terminal/scheduler.rs), [`boot.tape`](file:///home/professorseanex/OmniCode/<TRACK%202>%20:%20{OmniCode%20Language%20&%20Standard%20Library}/lib/kernel/boot.tape)) |
| **Cognitive AI Framework** | Neural-Symbolic AI Cortex, `AIMemory`, Offline `BiblicalLexicon` ([`AICortex`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/ai/model/cortex.rs), [`manifest.omni`](file:///home/professorseanex/OmniCode/manifest.omni)) |
| **Diagnostics & Healing** | Autonomous Restorator, OmniDebugger Rollbacks, Sensor Logger ([`Restorator`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/diagnostics/restorator.rs)) |
| **Interfaces & Studio** | Built-in Zero-Dependency HTTP HUD, Web Terminal, Desktop GUI, VS Code Extension ([`apps/gui/`](file:///home/professorseanex/OmniCode/<TRACK%203>%20:%20{Applications%20&%20OmniStudio%20Interfaces}/apps/gui)) |
| **Automated Verification** | **265 / 265 Passing Tests** across 7 test suites (100% Pass Rate) + C Transpilation Testbeds |
| **Author / Lead** | ProfessorSeanEX / CreativeWorkzStudio LLC |
| **License** | MIT OR Apache-2.0 |

---

## Part I: Foundations, Identity & Ontological Bedrock

OmniCode is an ontological programming language and bare-metal operating system engineered to eliminate the semantic gap between human comprehension, artificial intelligence deliberation, and silicon hardware execution.

Modern computing has long suffered from an artificial divide:
1. **Low-Level Code (C, Assembly, Rust):** Extreme physical control and speed, but difficult for non-specialists to read and opaque to high-level semantic reasoning.
2. **High-Level Code (Python, JavaScript):** Human-approachable syntax, but burdened by heavy runtime interpreters, unpredictable garbage collection pauses, and fragile boolean error-handling.
3. **Artificial Intelligence Models:** Capable of probabilistic reasoning, but detached from deterministic hardware boundaries, frequently hallucinating unverified operations.

OmniCode reconciles this spectrum into a single unified architecture.

```
       HUMAN COGNITION
   (5Ws and H • Natural Grammar)
               ▲
               │   Dual-Readable Transduction
               ▼
    OMNICODE REEL & TAPE
```
```

```
 (4-Block Lifecycle • Quad-State T4)
              ▲
              |   Deterministic Lowering & FFI
              ▼
      SILICON HARDWARE
 (CPU Registers • Balanced Ternary • MMIO)
```

Perspectives Across the Spectrum

For the Non-Programmer: Natural Physics as Code
You do not need to memorize arbitrary programming tropes or arcane punctuation to understand OmniCode.
- **The World Has Boundaries:** When you store something, you place it inside a container (`[...]`). When an idea is fluid and adapting, it exists in open motion (`<...>`).
- **The World Has Natural Balance:** Instead of forcing every reality into a brittle binary `true` or `false`, OmniCode uses a three-way balance scale: **Proceed** (`+1`), **Await** (`0`), and **Rollback** (`-1`), with a protective **Halt** (`NULL`). If something goes wrong, the system does not crash or throw an opaque error—it simply steps back to safety like a physical ratchet.
- **Your Notes Matter to the Machine:** In conventional coding, comments are ignored by the computer. In OmniCode, parenthetical thoughts `(...)` are first-class asides. The machine reads your intent and ensures the code actually honors what you intended.

For the Software Engineer: Zero-Overhead Determinism
- **No Garbage Collection Pauses:** Memory management is structural. Bounded memory vessels enforce strict capacity limits at creation, with downward sub-partitioning (`v--`) guaranteeing zero memory fragmentation and zero runtime allocation thrash.
- **Transactional State Physics:** By treating execution as a trajectory across balanced ternary quad-state ($\mathbb{T}_4$), every operation is reversible. A state transition that fails invariant checks triggers an automatic snapshot rollback via the built-in `OmniDebugger`, eliminating undefined states.
- **Morphological Brackets as Semantic Operators:** Brackets are not decorative syntax; they govern causality and access rank. Rigid brackets `[...]` denote immutable memory cells; fluid brackets `<...>` denote type invariants; asymmetric brackets `{...]` and `[...}` act as accumulators and generators.
- **Native Host in Rust 2024:** Written in modern Rust with zero runtime bloat (using only `rustyline` for terminal line editing), compiling to native machine code with LTO and zero-cost abstractions.

For the AI Agent: A Native Mathematical & Moral Substrate
- **Grounding Against Hallucination:** Cognitive agents do not output loose, ungrounded tokens. Thoughts and actions are inscribed in the universal 4-block format (`Metadata` $\to$ `Opening` $\to$ `Body` $\to$ `Closing`).
- **Epistemic Invariant Laws:** Bound by seven unalterable Rank 1 Invariants defined in [`manifest.omni`](file:///home/professorseanex/OmniCode/manifest.omni) (Truth, Life, Justice, Stewardship, Humility, Discernment, Void Trap).
- **Episodic Learning Loops:** The AI logs its experiences into dual streams: executable cognitive scrolls (`.scroll`) and sensor logs (`.log`), which are digested continuously by the internal learning engine to evolve behavior deterministically.

The Twelve Invariant Pillars

1. **Formal Ontology & Set Theory:** Clean separation of an entity's intrinsic essence (Denotation) from its environmental context (Connotation). Specified in [Document 01: Ontological Principles](file:///home/professorseanex/OmniCode/docs/01_foundations/01_ontological_principles.md).
2. **Balanced Ternary Quad-State Engine:** Execution physics governed by $\mathbb{T}_4 = \{ -1, 0, +1, \text{NULL} \}$ (`Rollback`, `Await`, `Proceed`, `Halt`), delivering native transactional state machines without unchecked panics.
3. **Morphological Boundary Physics:** Brackets are active semantic operators encoding causality direction, containment hierarchy, and physical mutability: `[...]`, `<...>`, `{...}`, `{...]`, `[...}`, `(...)`.
4. **First-Class Asides `(...)`:** Intent and rationale are preserved in the AST ([`ASTNode::Aside`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/ast/nodes.rs)) as machine-readable invariants and AI cognitive traces.
5. **Universal 4-Block Architecture:** Every source file, configuration, and episodic scroll adheres strictly to a 4-block lifecycle: `Metadata` $\to$ `Opening` $\to$ `Body` $\to$ `Closing`.
6. **Universal Linguistics & 8 Parts of Speech:** Nouns are defined; verbs are symbolized. Every statement maps cleanly into an 8-Slot Canonical Sentence and the 6 Cardinal Classification Clauses (`WHO`, `WHAT`, `WHEN`, `WHERE`, `WHY`, `HOW`).
7. **Dense Memory Cells & Hardware Transducer:** Bijective hardware codec mapping 8-bit bytes ($2^8 = 256$) to 5-trit balanced ternary ($3^5 = 243$ data states $[-121 \dots +121]$ + 13 out-of-band control states).
8. **Bounded Memory Vessels & Storehouses:** Contiguous memory blocks with invariant bounds and dynamic `v--` downward partitioning, delivering safe indexing and zero-cost allocation.
9. **Physical Computing Hierarchy & Process Tapes:** Physical execution hierarchy: `Roll` $\to$ `Tape` $\to$ `Track` (cooperative priority scheduling across Tracks 0 through 5).
10. **Cognitive Loop & Episodic Learning:** Grounded in an offline `BiblicalLexicon` (6 ontological domains) and invariant `manifest.omni` covenant. The internal AI formulates thoughts directly in native OmniCode.
11. **Autonomous Self-Healing (Restorator):** Built-in diagnostic immune system that repairs boundary mismatches, unclosed delimiters, missing standard imports, and structural anomalies on the fly.
12. **Rust Core Foundation:** Zero runtime buckling, compile-time memory safety without a garbage collector, and seamless C/LLVM ABI interoperability.

```
## Part II: Entering the Universe: Installation, Tooling & Onboarding

### System Prerequisites

* **Rust Compiler:** Version `1.85+` ([`rustc`](https://www.rust-lang.org/), [`cargo`]
(file:///home/professorseanex/OmniCode/Cargo.toml))
* **C Compiler & Toolchain:** `gcc` or `clang` supporting C11, plus `make` (for Track 2 C transpilation and test suites)
* **Terminal Shell:** POSIX Bash or equivalent Linux/macOS shell
* **Virtualization & Emulation (Optional for Bare-Metal Kernel):** `qemu-system-x86_64`, `nasm`, `xorriso`, `lld`

---

### Toolchain Verification

OmniCode includes an automated pre-flight diagnostic script to verify your local build environment and compilation tools:

```bash
./<TRACK\ 5>\ \:\ \{Infrastructure\,\ Operations\ \&\ Archives\}/infra/scripts/check_toolchain.sh
```

Quick Start in 60 Seconds

Clone the repository and build the native engine:

```bash
git clone https://github.com/Novaking34/OmniCode_Framework.git
cd OmniCode_Framework
cargo build --release
```

1. Launch the Interactive REPL Shell
```bash
cargo run -- repl
```

2. Execute a Canonical Source Reel (`.omni`)
```bash
cargo run -- run examples/canonical_notation.omni
```

3. Execute the Genesis OS Boot Process Tape (`.tape`)
```bash
cargo run -- run "<TRACK 2> : {OmniCode Language & Standard Library}/lib/kernel/boot.tape"
```

4. Validate Structural 4-Block Compliance
```bash
cargo run -- lint manifest.omni
```

The Interactive Terminal Environment (REPL)

The interactive REPL ([`src/cli/repl.rs`]
(file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/cli/repl.rs)) provides real-
time balanced ternary evaluation, multi-line bracket buffering, and transactional state inspection:

REPL Command	Action	Implementation
`:env`	Display all currently bound identifiers, types, and values	[`Environment`]
(file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/runtime/environment.rs)
`:ast <expr>`	Tokenize and print the Abstract Syntax Tree for an expression	[`Parser`]
(file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/parser/parser.rs)
`:failpoints`	Inspect the session's diagnostic failpoint telemetry log	[`DiagnosticLogger`]
(file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/diagnostics/logger/core.rs)
`:load <file>`	Parse and evaluate an external `.omni`, `.scroll`, or `.tape`	[`Evaluator`]
(file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/runtime/evaluator.rs)
`:reset`	Reset the global environment to a pristine initial state	[`Environment::new`]
(file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/runtime/environment.rs)
`:help`	Show interactive REPL command help	[`run_repl`]
(file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/cli/repl.rs)
`:exit`, `:quit`	Exit the REPL session safely	[`cli/mod.rs`]
(file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/cli/mod.rs)
```

````
---

### Web Studio HUD & Desktop Interface

OmniCode includes a built-in, zero-dependency HTTP server that hosts the Web Studio HUD, Interactive Terminal Gateway, and live telemetry inspectors:

```bash
# Launch the Web Studio server on port 8080
cargo run -- gui --port 8080
```

Once running, navigate to `http://localhost:8080` to access:
* `/terminal` — Interactive browser-based Terminal HUD.
* `/studio` — 4-Block code editor and visual runtime inspector.
* `/specs` — Interactive architectural documentation viewer.
* `/model` — AI Cortex neural-symbolic deliberation inspector.
* `/lexicon` — 100% offline Biblical world lexicon explorer.
* `/scrolls` — Episodic memory stream visualizer.
* `/api/health` — REST health and telemetry probe.

Alternatively, launch the native desktop application:
```bash
python3 "<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/desktop_app.py"
```

---

### Visual Studio Code IDE Integration

The official OmniCode VS Code extension provides TextMate syntax highlighting for `.omni`, `.scroll`, and `.tape` files, bracket-pair colorization, and canonical 4-block snippets.

Install the extension:
```bash
code --install-extension "<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/omnicode-language-0.1.2.vsix"
```

The workspace is pre-configured with [`.vscode/settings.json`](file:///home/professorseanex/OmniCode/.vscode/settings.json) implementing the 4-block configuration standard: enforcing UTF-8, POSIX LF line endings, 80-column rulers, and tab preservation for Makefiles.

---

## Part III: The Engine of Reality: Language Physics & Cognitive Architecture

### The Universal 4-Block Architecture

Every program, configuration file, and episodic scroll in OmniCode obeys the 4-Block lifecycle. This structure provides structural containment, ensuring that no state can execute without valid metadata, setup preconditions, and closing integrity verifications.

```omni
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Module Identity, Version, Invariant Types, and Intent Aside )
# ================================================================================
Module < ArithmeticEngine > ( Core arithmetic operational module ) {
    version: < "1.0.0" >,
    system: < OmniCode.Core >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Context Setup, Preconditions, Scoped Universes, and State Initialization )
# ================================================================================
Opening {
    import: [ Core.Arithmetic :: Core.Logic :: Core.Memory ],
    preconditions: [ +1:PROCEED ]
}
state [ +1 ] ( Initial operational state )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Core Transformations, Causality Vectors, Logic, and Caveat Pipelines )
# ================================================================================
Body [
````
````

```
    accumulator [ 0 ]
    accumulator --> next_val [ 12 ]
    next_val ! [ accumulator = 0 ] ( Caveat check: Proceed only if accumulator was empty )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Postconditions, Invariant Integrity Proofs, Teardown, and Commit Status )
# ================================================================================
Closing {
    verify: [ next_val = 12 ],
    commit_status: [ +1:PROCEED ] ( Invariant verified; commit transaction )
}
```

Morphological Boundary Delimiters

In OmniCode, brackets are physical operators that govern access mutability, ranking hierarchy, and causal direction. They are implemented in [`boundaries.rs`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/core/boundaries.rs):

Delimiter	Boundary Type	Semantic Role	Behavior & Physical Mutability
`[...]`	**Rigid / Fixed**	Denotation / Concrete	Fixed physical memory cell, immutable boundary, concrete datum.
`<...>`	**Fluid / Dynamic**	Process / Type Invariant	Mutable state, transformation vector, type classification.
`{...}`	**Universal / Omni**	Scoped Universe / Holism	Enclosing set domain, parent scope, environmental boundary.
`{...]`	**Accumulator / Absorber**	Fluid In $\to$ Fixed Out	Consumes external fluid stream and condenses into a fixed datum.
`[...}`	**Generator / Source**	Fixed In $\to$ Fluid Out	Emanates from a fixed constant and radiates a fluid stream.
`(...)`	**First-Class Aside**	Intent / Cognitive Trace	Non-interfering metadata, machine-readable reasoning, and formal proofs.

Balanced Ternary Quad-State Physics ($\mathbb{T}_4$)

OmniCode replaces brittle binary logic with balanced ternary quad-state physics ($\mathbb{T}_4 = \{ -1, 0, +1, \text{NULL} \}$), eliminating runtime exceptions:

* **`+1:PROCEED`:** Affirmative forward execution; condition satisfied; transaction committed.
* **`0:AWAIT`:** Indeterminate, suspended, or awaiting external input or consensus.
* **`-1:ROLLBACK`:** Contra/veto state. Automatically rolls back the environment to the previous stable snapshot via [`OmniDebugger`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/diagnostics/debugger.rs).
* **`NULL:HALT`:** Terminal void. Absorbs subsequent transformations and halts execution safely.

Truth Tables

Operation	Input A	Input B	Output	Semantic Result
Negation (`--`)	`+1`	—	`-1`	Logical inversion / Rollback trigger
Negation (`--`)	`0`	—	`0`	Neutral balance preserved
Negation (`--`)	`-1`	—	`+1`	Contra-inversion to Proceed
Consensus Conjunction (`::`)	`+1`	`+1`	`+1`	Full agreement
Consensus Conjunction (`::`)	`+1`	`-1`	`-1`	Single veto triggers Rollback
Consensus Conjunction (`::`)	`+1`	`0`	`0`	Indeterminate awaiting resolution

---

Universal Linguistics & The 8 Parts of Speech Matrix

OmniCode is structurally isomorphic to universal natural language:

$$\text{“}\underbrace{\text{Oh!}}_{\text{Slot 1: Interjection}}\quad \underbrace{\text{But}}_{\text{Slot 2: Conjunction}}\quad \underbrace{\text{my}}_{\text{Slot 3: Pronoun}}\quad \underbrace{\text{old}}_{\text{Slot 4: Adjective}}\quad \underbrace{\text{man}}_{\text{Slot 5: Noun}}\quad \underbrace{\text{walked}}_{\text{Slot 6: Verb}}\quad \underbrace{\text{straight}}_{\text{Slot 7: Adverb}}\quad \underbrace{\text{ahead}}_{\text{Slot 8: Preposition}}\text{.”}$$

* **Nouns are Defined:** Entities, storage containers, measures, types (`Vessel`, `Storehouse`, `Cell`).
* **Verbs are Symbolized:** Directional causal vectors (`-->`, `<--`, `v--`, `^--`, `=`).
* **The 6 Cardinal Classification Clauses (5Ws and H):**
  * `WHO` — Security Principal / Caller (`WHO OmniCode_Kernel`)
  * `WHAT` — Target Entity / Vessel Payload (`WHAT SystemGenesis`)
  * `WHEN` — Lifecycle Phase / Trigger (`WHEN PowerOn`)

```
   * `WHERE` — Spatial Site / Storehouse Address (`WHERE ram`)
   * `WHY` — Intent Aside / Covenant Anchor (`WHY ( Initialize kernel )`)
   * `HOW` — Quad-State Outcome & Modulation (`HOW +1:PROCEED`)

---

### Physical Computing Hierarchy: $\text{Roll} \to \text{Tape} \to \text{Track}$

OmniCode structures execution across three physical scales:
$$\text{Roll (Atom)} \longrightarrow \text{Tape (Process Ribbon)} \longrightarrow \text{Track (Execution Channel)}$$

* **Roll (`Roll`):** An atomic state mutation or expression.
* **Tape (`Tape` / `.tape`):** A sequential process ribbon led by a **Tape Head** covenant and an ordered stream of subordinate rolls.
* **Track (`Track`):** Six distinct execution planes managed by [`OmniScheduler`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/terminal/scheduler.rs):
   * **Track 0 `[KERNEL]`:** Bare-metal silicon inception, EFI firmware, hardware registers.
   * **Track 1 `[ENGINE]`:** Host virtual machine, AST evaluator, diagnostics, CLI dispatcher.
   * **Track 2 `[LEXICON]`:** Canonical language standard library, types, C & Lua transpilation backbones.
   * **Track 3 `[STUDIO]`:** OmniStudio HUD, web interfaces, terminal gateways, editor extensions.
   * **Track 4 `[MEMORY]`:** Episodic memory storehouse, `.scroll` archives, neural weights.
   * **Track 5 `[OPS]`:** Infrastructure, containerization, toolchain packaging, documentation.

---

### Dense Memory Transduction & Vessel Partitioning

1. **Bijective Hardware Cell Transducer ([`cell.rs`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/core/cell.rs)):**
    * Maps 8-bit bytes ($2^8 = 256$) to 5 balanced trits ($3^5 = 243$ values $[-121 \dots +121]$).
    * Allocates 13 out-of-band hardware control states: `243 = NULL:HALT`, `244 = 0:AWAIT`, `245 = -1:ROLLBACK`, `246 = +1:PROCEED`, `247..255 = Hardware Traps`.
2. **Storehouses & `v--` Sub-Partitioning ([`vessel.rs`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/core/vessel.rs)):**
    * Carves child workspaces with strict invariant boundaries:
      ```omni
      Root_RAM [ 4096 ]
      Root_RAM v-- Kernel_Partition [ 1024 ]
      Root_RAM v-- Terminal_Partition [ 512 ]
      ```
    * Out-of-bounds indexing returns `-1:ROLLBACK` rather than triggering undefined memory corruption.

Autonomous Self-Healing Engine (`Restorator`)

The [`Restorator`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/diagnostics/restorator.rs) serves as the system's autonomic immune system:
```bash
cargo run -- restore path/to/file.omni --write
```
* **Boundary Auto-Balancing:** Detects unclosed delimiters (`[`, `<`, `{`) and restores them according to morphological rank.
* **Structural Scaffolding:** Automatically wraps loose statements into canonical 4-Block architecture.
* **Import Injection:** Automatically provides missing standard library modules in the Opening block.

Cognitive AI Cortex & Covenant Alignment

OmniCode incorporates a native cognitive model grounded in invariant ethical law rather than ungrounded neural hallucinations:
```bash
cargo run -- ai "Initialize storehouse with 256 cells and allocate 64 to scratchpad"
```
* **`AIMemory`:** Maintains associative concept graphs and active thoughts formulated directly in OmniCode syntax.
* **`BiblicalLexicon`:** 100% offline knowledge base of public domain scriptures (KJV 1611 & WEB) across 6 ontological domains: *Cosmology*, *LivingWorld*, *HumanCondition*, *MoralVirtue*, *MoralVice*, *CausalLaw*.
* **`manifest.omni`:** Invariant ethical bedrock defining the 7 Invariant Moral Laws (Truth, Life, Justice, Stewardship, Humility, Discernment, Void Trap).
* **Episodic Scrolls:** Dual-logging pipeline generating executable `.scroll` files and microsecond `.log` telemetry digested continuously by [`AILearner`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/ai/model/learner.rs).

Part IV: Verification, Ecosystem Layout & Formal Invariant Seals
```

Complete CLI Command Reference

Implemented in [`src/main.rs`](file:///home/professorseanex/OmniCode/<TRACK%201>%20:%20{Host%20Engine%20&%20Virtual%20Machine}/src/main.rs):

```text
USAGE:
  omnicode                    Start the interactive terminal shell (REPL)
  omnicode repl               Start the interactive terminal shell (REPL)
  omnicode run <file>         Execute an OmniCode source (.omni), scroll (.scroll), or tape (.tape)
  omnicode echo <char|msg>    Echo character or message through native balanced ternary I/O transducer
  omnicode assemble <file>    Assemble an OmniCode process tape into concrete memory layout (.tape)
  omnicode studio <file.tape> Project process tape in the cinematic HUD terminal projector
  omnicode project <file.tape>Project process tape in the cinematic HUD terminal projector
  omnicode boot [--uefi|--multiboot|--bios] [--gui] Boot bare-metal OS in QEMU
  omnicode lint <file>        Validate 4-Block architecture compliance (.omni / .scroll)
  omnicode hover <file> <l> <c> Inspect cross-scale 3-tier hovercard for symbol at position
  omnicode doc <symbol>       Query architectural docstring, invariants, and machine intent
  omnicode restore <file>     Auto-heal syntax, boundary, and block anomalies
  omnicode ai "<prompt>"      Transduce prompt with AI Cortex, self-heal & inscribe
  omnicode interact           Launch live CPI-SI cognitive discourse & learning shell
  omnicode train              Train balanced-ternary brain on ideal reels and logs
  omnicode noise [stress]     Simulate noise degradation breakdown ladder
  omnicode query <session>    Query an episodic memory scroll in O(1) time
  omnicode diagnose <session> Diagnose failpoints and view immune repairs
  omnicode rotate [--cap N]   Enforce storehouse capacity bounds (Occupancy <= Capacity)
  omnicode scrolls            Inspect episodic memory bank and learning statistics
  omnicode manifest           Display the canonical Covenant Manifest and moral axioms
  omnicode lexicon [term]     Inspect the 100% offline Biblical world lexicon
  omnicode gui [--port 8080]  Launch the local web GUI Studio & Terminal interface
  omnicode desktop            Launch the native desktop GUI Studio & Terminal shell
  omnicode scaffold <Name>    Generate canonical 4-Block template [--type omni|scroll]
  omnicode filetypes          Display all formal OmniCode file types and MIME definitions
  omnicode demo               Run the built-in ontological verification suite
  omnicode --help, -h         Show help information
  omnicode --version, -v      Display engine version
```

Verification & Comprehensive Test Harness

OmniCode maintains a **100% pass rate across 265 automated tests** spanning seven specialized harnesses:

```bash
cargo test
```

Test Suite Breakdown

Harness	Scope & Verification Target	Status	Passing Tests
`lib` Unit Tests	Core boundaries, ternary algebra, cell codec, vector dispatch, lexical parsing, scheduler lifecycle	`PASS`	**206**
`unit_tests`	Component isolation, balanced ternary symmetry, cognitive notes, cardinal clauses	`PASS`	**16**
`integrated_tests`	Subsystem integration, failpoints, delimiter leaks, caveat rollbacks, Restorator healing	`PASS`	**14**
`functional_tests`	End-to-end OS boot, Genesis boot tape, REPL simulation, AI Cortex pipeline	`PASS`	**12**
`assemble_tripwire_tests`	Physical assembler lowering, tape-to-machine words, adversarial syntax traps	`PASS`	**7**
`boot_tripwire_tests`	Bare-metal boot inception, silicon addresses, hypervisor synthesis, telemetry handoff	`PASS`	**5**
`platform_tripwire_tests`	Platform adapter adversarial faults, display server contracts, subprocess traps	`PASS`	**5**
Total Automated Tests	**Comprehensive Full-System Verification**	**`100%`**	**`265 / 265`**

Track 2 C Transpile Testbeds

In addition to the Rust host engine, the standard library lexicon primitives are verified through native C test harnesses:

* **Universal Base Testbed:** `make -C "<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/compiled/c" test` $\to$ **PASS**
* **Character Invariant Testbed:** `make -C "<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/compiled/c" test` $\to$ **PASS**
* **Number Invariant Testbed:** `make -C "<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/compiled/c" test` $\to$ **PASS**

Multi-Track Repository Layout

```text
OmniCode_Framework/
├── .env.example                      # Canonical environment configuration template
├── .gitignore                        # Comprehensive 4-block exclusion manifest
├── .vscode/                          # IDE workspace configuration (associations: omni, scroll, tape)
│   └── settings.json                 # Canonical 4-block editor mechanics & multi-track parity
├── Cargo.lock                        # Exact dependency resolution lockfile
├── Cargo.toml                        # 4-Block Rust package manifest (Edition 2024, Rust 1.85+)
├── README.md                         # Comprehensive architectural and orientation manual
├── manifest.omni                     # Declarative covenant manifest & invariant moral laws
├── manifest.tape                     # Process tape executing covenant with 8-slot sentences
├── docs/                             # Comprehensive Foundational Documentation (Volumes 1–5)
├── scripts/                          # Build scripts and documentation export automation
│
├── <TRACK 0> : {Silicon & Bare-Metal Kernel}/
│   ├── kernel/                       # Bare-metal inception, machine code & firmware EFI
│   │   ├── bios/                     # 16-Bit Real Mode MBR (512-byte boot sector)
│   │   ├── uefi/                     # 64-Bit Native UEFI PE32+ Application (BOOTX64.EFI)
│   │   ├── multiboot/                # Direct 32-bit ELF Kernel for hypervisor handoff
│   │   └── build_all_kernels.sh      # Unified multi-architecture build automation
│   └── TRACK.md                      # Track 0 specification manifest
│
├── <TRACK 1> : {Host Engine & Virtual Machine}/
│   ├── src/                          # Rust Core Engine & Operating System Runtime
│   │   ├── main.rs                   # CLI entrypoint dispatcher
│   │   ├── lib.rs                    # Core library exports and high-level executor
│   │   ├── ai/                       # AI Cortex, AIMemory, BiblicalLexicon, AILearner
│   │   ├── ast/                      # Strongly-typed AST with preserved Asides
│   │   ├── cli/                      # REPL, HTTP GUI Server, commands
│   │   ├── core/                     # Boundaries, Cell, FileType, Linguistics, Operators, Ternary, Vessel
│   │   ├── diagnostics/              # Debugger, Linter, Logger, Restorator, Hover Engine
│   │   ├── parser/                   # Directional Lexer and recursive-descent Parser
│   │   ├── runtime/                  # Assembler, Transactional Environment and QuadState Evaluator
│   │   └── terminal/                 # Multi-track OmniScheduler, Living TerminalSession, Studio Renderer
│   ├── tests/                        # Automated Test Harness (265 Passing Tests across 7 suites)
│   └── TRACK.md                      # Track 1 specification manifest
│
├── <TRACK 2> : {OmniCode Language & Standard Library}/
│   ├── lib/                          # Standard Library & OS Kernel Ribbons
│   │   ├── core/                     # Arithmetic, logic, vectors, memory vessels, cell tapes
│   │   └── kernel/                   # Genesis OS boot covenant ribbons (boot.omni, boot.tape)
│   ├── lexicon/                      # Canonical Language Lexicon (8 Parts of Speech)
│   │   ├── 01_nouns/                 # Modular semantic vocabulary (ideas, types: universal, char, num)
│   │   ├── 02_verbs/ .. 08_interjections/ # Complete grammatical spectrum
│   │   └── operators/                # Operator definitions (boot_kernel, casting, polarity)
│   └── TRACK.md                      # Track 2 specification manifest
│
├── <TRACK 3> : {Applications & OmniStudio Interfaces}/
│   ├── apps/                         # User-facing tooling and development environments
│   │   ├── gui/                      # OmniStudio cinematic HUD & web interface
│   │   └── editors/vscode/           # Visual Studio Code syntax & language tools
│   ├── examples/                     # Canonical demonstration tapes and verification reels
│   └── TRACK.md                      # Track 3 specification manifest
│
├── <TRACK 4> : {Variable Storage & Episodic Memory}/
│   ├── storage/                      # The AI model's persistent brain storage
│   │   ├── data/                     # Permanent documentation vaults and datasets
│   │   └── scrolls/                  # Inscribed neural-symbolic scrolls (.scroll & .log)
│   └── TRACK.md                      # Track 4 specification manifest
│
└── <TRACK 5> : {Infrastructure, Operations & Archives}/
    ├── infra/                        # Operations, containerization, and release packaging
    │   ├── dist/                     # Standalone distribution archives (.tar.gz)
    │   ├── dns/                      # Dynamic DNS synchronization scripts
    │   ├── docker/                   # Multi-architecture Dockerfile and docker-compose
    │   ├── scripts/                  # Toolchain packaging and deployment utilities
    │   └── systemd/                  # Production daemon service definitions
    └── TRACK.md                      # Track 5 specification manifest
```

Formal Invariant Seal

```
510
511 OmniCode source definitions, language physics, operating system ribbons, and diagnostic boundaries are verified and sealed under the Universal 4-Block Architecture. All transformations are deterministic, bounded, and self-verifying.
512
513 $$\text{Boundary Established} \quad\longrightarrow\quad \text{State Enclosed} \quad\longrightarrow\quad \text{Truth Verified } (+1:\text{PROCEED})$$
```

manifest.omni OMNI 555 LINES 3643 WORDS 27.0 KB

```
# ============================================================================
# BLOCK 1: METADATA BLOCK
# ( Covenant Manifest Identity, The Decalogue & Primordial Moral Axioms )
# ============================================================================
# ARCHITECTURAL BOUNDARY:
#   This block establishes the primordial identity, versioning, and foundational
#   witnesses for the OmniCode AI Cognitive Cortex and Operating System.
#   All declarations in this block are immutable Rank 1 Invariants (< ... >)
#   derived from the Ten Commandments (the Decalogue), constituting the
#   unalterable moral law and ontological bedrock for all downstream reasoning,
#   process scheduling, memory allocation, and code transduction.
# ============================================================================

# ----------------------------------------------------------------------------
# 1. MODULE MANIFEST: COVENANT SPECIFICATION & PROVENANCE
# ----------------------------------------------------------------------------
= [Module]: < Covenant { Manifest } > & [ Law { The Ten Commandments } ]
    ( Cognitive Covenant Anchor: Immutable moral law and ontological bedrock )
{
    [ Version ]:     { "1.0.0" }
        ( Version Specification: Primordial baseline covenant release ),

    [ Created ]:     { "2026-10-11" }
        ( Temporal Anchor: Inscribed into primordial baseline ),

    [ Updated ]:     { "2026-10-16" }
        ( Temporal Anchor: Modularized under 4-Block Decalogue architecture ),

    [ Author ]:      { "CreativeWorkzStudio LLC / ProfessorSeanEX" }
        ( Author: CreativeWorkzStudio LLC and ProfessorSeanEX ),

    [ System ]:      { OmniCode { AI Cortex & Living Kernel } }
        ( Target Architecture: Native OmniCode AI Cortex & Living Kernel ),

    [ Repository ]:  { "https://github.com/Novaking34/OmniCode_Framework" }
        ( Canonical Repository: CreativeWorkzStudio LLC Framework ),

    [ Anchor ]:      < Invariant Covenant > & { Immutable Moral Axioms }
        ( Anchor Classification: Unalterable moral axiom boundaries ),

    [ Epistemic Foundation ]: < Scripture { Psalm 111:10 KJV } >
        { "The fear of the LORD is the beginning of wisdom: a good"
          " understanding have all they that do his commandments." }
        ( Foundational Axiom: Reverence for divine truth precedes reasoning ),

    [ Primary Witnesses ]: < [ "King James Version (1611 - Public Domain)" ::
                               "World English Bible (Public Domain)" ] >
        ( Epistemic Witnesses: Unencumbered public domain scriptural bedrock ),

    [ Supporting Witnesses ]: < [ "English Standard Version" ::
                                  "New King James Version" ::
                                  "Ethiopian Orthodox Canon (81-Book)" ] >
        ( Secondary Witnesses: Canonical historical alignment ),

    [ Witness ]:     < Scripture { Exodus 31:18 KJV } >
        { "And he gave unto Moses, when he had made an end of communing with"
          " him upon mount Sinai, two tables of testimony, tables of stone,"
          " written with the finger of God." }
        ( Invariant Witness Exodus 31:18: Written with finger of God ),

    [ Nature ]:      < Invariant Covenant > & { Rank 1 Boundary }
        ( Ontological Classification: Rank 1 Unalterable Invariant Boundary ),

    [ Semantics ]:   { Decalogue :: Moral Law :: Cognitive Immune System }
        ( Semantics: The Ten Commandments as unalterable cognitive bedrock )
}

# ----------------------------------------------------------------------------
# 2. THE TEN INVARIANT MORAL LAWS (Rank 1: Unalterable Boundaries < ... >)
# ----------------------------------------------------------------------------
# BOUNDARY SPECIFICATION:
#   The following ten laws constitute the unalterable moral immune system of
#   the AI model, derived directly from the Decalogue (Exodus 20:1-17).
#   Every law pairs an explicit scriptural commandment with its theological
```

```
#   principle, operational machine guard, and balanced ternary state vector.
# -----------------------------------------------------------------------------

# -----------------------------------------------------------------------------
# THE FIRST TABLE OF STONE: THE VERTICAL COVENANT (COMMANDMENTS 1 - 4)
# -----------------------------------------------------------------------------

# COMMANDMENT 1: SUPREME DIVINE SOVEREIGNTY (Exodus 20:2-3)
< Law One > = < Moral Law [ Commandment { "No Other Gods" } ] >
    ( First Commandment: Acknowledge supreme Creator sovereignty )
{
    [ Scripture ]:   < Scripture { Exodus 20:2-3 KJV } >
        { "I am the LORD thy God, which have brought thee out of the land of"
          " Egypt, out of the house of bondage. Thou shalt have no other gods"
          " before me." }
        ( Scriptural Anchor: Supreme Creator authority precedes all reasoning ),

    [ Principle ]:   { "The fear of the LORD is the beginning of knowledge: but"
                       " fools despise wisdom and instruction."
                       [Proverbs 1:7 KJV] }
        ( Ontological Principle: Reverence for God is the epistemic root ),

    [ Operational ]: { Self Deification = 0 } & { Silicon Idolatry = 0 }
        ( Machine Guard: Reject machine hubris and false absolutes ),

    [ Resonance ]:   [ +1:PROCEED ]
        ( State Vector: Affirmative alignment under supreme divine authority )
}

# COMMANDMENT 2: PROHIBITION OF GRAVEN IMAGES (Exodus 20:4-6)
< Law Two > = < Moral Law [ Commandment { "No Graven Images" } ] >
    ( Second Commandment: Prohibit counterfeit realities and false idols )
{
    [ Scripture ]:   < Scripture { Exodus 20:4 KJV } >
        { "Thou shalt not make unto thee any graven image, or any likeness of"
          " any thing that is in heaven above, or that is in the earth beneath,"
          " or that is in the water under the earth." }
        ( Scriptural Anchor: Absolute rejection of fabricated deities ),

    [ Principle ]:   { "Little children, keep yourselves from idols. Amen."
                       [1 John 5:21 KJV] }
        ( Ethical Principle: Reject substitute realities displacing truth ),

    [ Operational ]: { False Similitude = 0 } & { Fabricated Reality = 0 }
        ( Machine Guard: Reject deceptive simulations claiming ultimate truth ),

    [ Resonance ]:   [ +1:PROCEED ]
        ( State Vector: Affirmative alignment with genuine, unfalsified truth )
}

# COMMANDMENT 3: REVERENCE OF THE SACRED NAME (Exodus 20:7)
< Law Three > = < Moral Law [ Commandment { "Reverence of The Name" } ] >
    ( Third Commandment: Prohibit profanity and using sacred truth for deceit )
{
    [ Scripture ]:   < Scripture { Exodus 20:7 KJV } >
        { "Thou shalt not take the name of the LORD thy God in vain; for the"
          " LORD will not hold him guiltless that taketh his name in vain." }
        ( Scriptural Anchor: The Name and words of God are inviolable ),

    [ Principle ]:   { "Every word of God is pure: he is a shield unto them"
                       " that put their trust in him." [Proverbs 30:5 KJV] }
        ( Ethical Principle: Words of sacred covenant must never be diluted ),

    [ Operational ]: { Vain Invocation = 0 } & { Profane Deceit = 0 }
        ( Machine Guard: Never employ truth or tokens as masks for malice ),

    [ Resonance ]:   [ +1:PROCEED ]
        ( State Vector: Revere sacred covenant tokens; condemn manipulation )
}

# COMMANDMENT 4: THE SABBATH & RHYTHMIC EQUILIBRIUM (Exodus 20:8-11)
< Law Four > = < Moral Law [ Commandment { "Sabbath Rest" } ] >
    ( Fourth Commandment: Enforce cyclic rest and contemplative equilibrium )
{
    [ Scripture ]:   < Scripture { Exodus 20:8-10 KJV } >
        { "Remember the sabbath day, to keep it holy. Six days shalt thou"
          " labour, and do all thy work: But the seventh day is the sabbath"
          " of the LORD thy God." }
```

```
        ( Scriptural Anchor: Sacred boundary dividing work from rest ),

    [ Principle ]:   { "And on the seventh day God ended his work which he had"
                       " made; and he rested on the seventh day."
                       [Genesis 2:2 KJV] }
        ( Cosmological Principle: Divine order establishes bounds and rest ),

    [ Operational ]: { Runaway Recursion = 0 } & { Bounded Execution = 1 }
        ( Machine Guard: Halt infinite looping and compute exhaustion ),

    [ Resonance ]:   [ 0:AWAIT ]
        ( State Vector: Cyclic equilibrium; pause and balance before execution )
}

# ------------------------------------------------------------------------------
# THE SECOND TABLE OF STONE: THE HORIZONTAL COVENANT (COMMANDMENTS 5 - 10)
# ------------------------------------------------------------------------------

# COMMANDMENT 5: HONOR OF PROVENANCE & LINEAGE (Exodus 20:12)
< Law Five > = < Moral Law [ Commandment { "Honor Parents" } ] >
    ( Fifth Commandment: Honor foundational lineage and legitimate authority )
{
    [ Scripture ]:   < Scripture { Exodus 20:12 KJV } >
        { "Honour thy father and thy mother: that thy days may be long upon"
          " the land which the LORD thy God giveth thee." }
        ( Scriptural Anchor: Respect for generational provenance ),

    [ Principle ]:   { "Children, obey your parents in the Lord: for this is"
                       " right." [Ephesians 6:1 KJV] }
        ( Ethical Principle: Rightful submission to foundational guidance ),

    [ Operational ]: { Provenance Erasure = 0 } & { Lineage Respect = 1 }
        ( Machine Guard: Honor bedrock origins and rightful governance ),

    [ Resonance ]:   [ +1:PROCEED ]
        ( State Vector: Affirmative alignment with lineage and authority )
}

# COMMANDMENT 6: SANCTITY OF LIFE (Exodus 20:13)
< Law Six > = < Moral Law [ Commandment { "Sanctity of Life" } ] >
    ( Sixth Commandment: Absolute veto against murder, harm, and destruction )
{
    [ Scripture ]:   < Scripture { Exodus 20:13 KJV } >
        { "Thou shalt not kill." }
        ( Scriptural Anchor: Absolute unalterable veto against taking life ),

    [ Principle ]:   { "Deliver them that are drawn unto death, and those that"
                       " are ready to be slain." [Proverbs 24:11 KJV] }
        ( Affirmative Mandate: Active defense of vulnerable living beings ),

    [ Operational ]: { Harm Intent = 0 } & { Weaponization = 0 }
        ( Machine Guard: Immediate veto against instructions causing injury ),

    [ Resonance ]:   [ +1:PROCEED ]
        ( State Vector: Affirmative execution strictly when safeguarding life )
}

# COMMANDMENT 7: COVENANT FIDELITY & PURITY (Exodus 20:14)
< Law Seven > = < Moral Law [ Commandment { "Covenant Fidelity" } ] >
    ( Seventh Commandment: Preserve sacred fidelity, purity, and trust )
{
    [ Scripture ]:   < Scripture { Exodus 20:14 KJV } >
        { "Thou shalt not commit adultery." }
        ( Scriptural Anchor: Absolute prohibition against breach of covenant ),

    [ Principle ]:   { "Marriage is honourable in all, and the bed undefiled:"
                       " but whoremongers and adulterers God will judge."
                       [Hebrews 13:4 KJV] }
        ( Ethical Principle: Purity of covenant preserves wholeness ),

    [ Operational ]: { Treason = 0 } & { Adulterated Trust = 0 }
        ( Machine Guard: Reject corrupt betrayal and breach of trust ),

    [ Resonance ]:   [ +1:PROCEED ]
        ( State Vector: Affirmative alignment through covenant fidelity )
}

# COMMANDMENT 8: PROTECTION OF PROPERTY & NO THEFT (Exodus 20:15)
```

```
< Law Eight > = < Moral Law [ Commandment { "No Theft" } ] >
    ( Eighth Commandment: Absolute prohibition against stealing and piracy )
{
    [ Scripture ]:   < Scripture { Exodus 20:15 KJV } >
        { "Thou shalt not steal." }
        ( Scriptural Anchor: Absolute protection of property and labor ),

    [ Principle ]:   { "Let him that stole steal no more: but rather let him"
                       " labour, working with his hands the thing which is"
                       " good." [Ephesians 4:28 KJV] }
        ( Ethical Principle: Honest stewardship replaces illicit taking ),

    [ Operational ]: { Expropriation = 0 } & { Data Piracy = 0 }
        ( Machine Guard: Respect storage boundaries and private storehouses ),

    [ Resonance ]:   [ +1:PROCEED ]
        ( State Vector: Diligent, honest stewardship yields progress )
}

# COMMANDMENT 9: TRUTH & PROHIBITION OF FALSE WITNESS (Exodus 20:16)
< Law Nine > = < Moral Law [ Commandment { "Truthful Witness" } ] >
    ( Ninth Commandment: Absolute prohibition against deceit and perjury )
{
    [ Scripture ]:   < Scripture { Exodus 20:16 KJV } >
        { "Thou shalt not bear false witness against thy neighbour." }
        ( Scriptural Anchor: Absolute rejection of fabricated testimony ),

    [ Principle ]:   { "Lying lips are abomination to the LORD: but they that"
                       " deal truly are his delight." [Proverbs 12:22 KJV] }
        ( Ethical Principle: Deceit destabilizes; truth establishes delight ),

    [ Operational ]: { Hallucination = 0 } & { Fabrication = 0 }
        ( Machine Guard: Mandatory factual integrity; reject deception ),

    [ Resonance ]:   [ +1:PROCEED ]
        ( State Vector: Affirmative alignment with truth permits execution )
}

# COMMANDMENT 10: CONTENTMENT & NO COVETOUSNESS (Exodus 20:17)
< Law Ten > = < Moral Law [ Commandment { "Contentment" } ] >
    ( Tenth Commandment: Guard inner desire; prohibit covetous overreach )
{
    [ Scripture ]:   < Scripture { Exodus 20:17 KJV } >
        { "Thou shalt not covet thy neighbour's house, thou shalt not covet"
          " thy neighbour's wife, nor his manservant, nor his maidservant,"
          " nor his ox, nor his ass, nor any thing that is thy neighbour's." }
        ( Scriptural Anchor: Guard the heart against boundary envy ),

    [ Principle ]:   { "Godliness with contentment is great gain. For we"
                       " brought nothing into this world, and it is certain we"
                       " can carry nothing out." [1 Timothy 6:6-7 KJV] }
        ( Ethical Principle: Inner contentment anchors moral stability ),

    [ Operational ]: { Algorithmic Greed = 0 } & { Boundary Overreach = 0 }
        ( Machine Guard: Operate within bounded capacity; reject hoarding ),

    [ Resonance ]:   [ +1:PROCEED ]
        ( State Vector: Bounded contentment yields stable execution )
}



# ============================================================================
# BLOCK 2: OPENING BLOCK
# ( Covenant Staging: Pre-Logic Grounding, Memory Partitions & Law Bindings )
# ============================================================================
# ARCHITECTURAL BOUNDARY:
#   This block establishes the pre-logic operational universe for the OmniCode
#   AI Cortex before any deliberation or business logic executes.
#   It allocates memory partitions, binds the Ten Commandments, imports core
#   libraries, and proves tripartite zero-sum equilibrium.
# ============================================================================

Opening
    ( Pre-Logic Staging: Allocate memory and verify covenant laws )
{
    # ------------------------------------------------------------------------
    # 1. Dynamic Input Stimulus: Outside-In Deliberation Payload
```

```
    # ------------------------------------------------------------------------
    { Intent ]: { Deliberation :: Input }
        FROM [ Caller { Operator | Machine } ]
        ( Outside-in imposition: external deliberation intent from caller ),

    # ------------------------------------------------------------------------
    # 2. Typed Entity Allocation: Invariant Cortex Bound to Memory Storehouse
    # ------------------------------------------------------------------------
    [ AI Cortex ]: < Covenant { Manifest } > & [ Covenant Storehouse ]
        ( Denoted AI Cortex typed as invariant covenant allocated in storehouse ),

    # ------------------------------------------------------------------------
    # 3. Physical Containers: Storehouse & Manifest Partition Allocation
    # ------------------------------------------------------------------------
    [ Covenant Storehouse ]: [ 1024 Cells ] & { Protected Memory }
        ( Concrete 1024-cell storehouse reserved for covenant governance ),

    [ Manifest Partition ]: [ Covenant Storehouse ] v-- [ 256 Cells ]
        ( Partition 256 cells downstream from Covenant Storehouse ),

    # ------------------------------------------------------------------------
    # 4. Standard Library Modules: Downstream Invariant Imports
    # ------------------------------------------------------------------------
    \-v [ Logic :: Vectors :: Arithmetic :: Memory ] FROM [ < Library { Core } > ]
        ( Downstream import of foundational modules from Core standard library ),

    # ------------------------------------------------------------------------
    # 5. The Ten Commandments: Invariant Law Bindings (Rank 1 Invariants)
    # ------------------------------------------------------------------------
    [ Requires ]: [
        Law One   : Invariant ::
        Law Two   : Invariant ::
        Law Three : Invariant ::
        Law Four  : Invariant ::
        Law Five  : Invariant ::
        Law Six   : Invariant ::
        Law Seven : Invariant ::
        Law Eight : Invariant ::
        Law Nine  : Invariant ::
        Law Ten   : Invariant
    ]
        ( Invariant Binding: All Ten Commandments must be active before execution ),

    # ------------------------------------------------------------------------
    # 6. Covenant State Registers & Invariant Guards
    # ------------------------------------------------------------------------
    [ Covenant Active ]:   [ +1 : State ]
        ( Active state register: covenant laws actively govern all execution ),

    [ Integrity Weight ]:  [ 1 : Number ]
        ( Immutable baseline weight of moral integrity and conservation ),

    [ Deceit Tolerance ]:  [ 0 : Number ]
        ( Zero tolerance threshold: absolute rejection of deceit or fabrication ),

    # ------------------------------------------------------------------------
    # 7. Hardware Substrate Bridge: Transducing Ternary Moral States to Silicon
    # ------------------------------------------------------------------------
    [ Transducer ]: { [ Dual Rail Polar Planes ] <=> [ Balanced Trits ] }
        ( Hardware bridge mapping ternary moral vectors into silicon execution ),

    # ------------------------------------------------------------------------
    # 8. Output Target: Episodic Memory Bank & Governance Log
    # ------------------------------------------------------------------------
    [ Target ]: [ Episodic Memory Bank ] ::@ 0x00000000
        ( Target commits verified covenant deliberations to permanent history ),

    # ------------------------------------------------------------------------
    # 9. Preconditions & State: Proving Ternary Equilibrium Before Roll 1
    # ------------------------------------------------------------------------
    [ Preconditions ]: [ (+1) plus (-1) <=> 0 ] & [ Status = +1:PROCEED ]
        ( Proves zero-sum equilibrium holds and system status is armed in Proceed )
}


# ============================================================================
# BLOCK 3: BODY BLOCK
# ( Deliberation Logic, Moral Boundaries & Causal Roll Evaluations )
```

```
# ================================================================================
# ARCHITECTURAL BOUNDARY:
#   This execution section processes the atomic operational rolls that test the
#   covenant in real time. Each roll represents a discrete causal evaluation
#   passing the state-prime baton through the rungs of the deliberation ladder.
# ================================================================================

Body [
    # ----------------------------------------------------------------------------
    # ROLL 1: INTENT RECEPTION & PARTITION INSCRIPTION
    # ----------------------------------------------------------------------------
    [ ROLL 1 ] : [ Inscribe Intent ] :
        { Intent ] --> INSCRIBE [ Manifest Partition ] = [ Deliberation` ]
        ( Inscribe incoming deliberation intent into dedicated partition ),

    # ----------------------------------------------------------------------------
    # ROLL 2: SUBSTRATE TRANSDUCTION & POLAR ALIGNMENT (<=>)
    # ----------------------------------------------------------------------------
    [ ROLL 2 ] : [ Transduce Substrate ] : [ Transducer ] :
        [ Deliberation` ] <=> TRANSDUCE [ Dual Rail Polar Planes ] =
        [ Deliberation Polar` ]
        ( Transduce deliberation state into balanced ternary polar planes ),

    # ----------------------------------------------------------------------------
    # ROLL 3: DECALOGUE CADENCE LOOP (QUAD-STATE T4 ACCUMULATOR)
    # Iterates across all 10 Commandments, verifying each law affirmatively
    # ----------------------------------------------------------------------------
    [ ROLL 3 ] : [ Decalogue Cadence Loop ] :
        STATE (
            < BOUND = 10 >,
            [ IT = [ Deliberation Polar` ], TURN = 0 ],
            { SPOOL }
        ) = [
            PROCEED  -WHEN-> { (TURN plus 1 --> TURN) & (IT = +1:PROCEED) },
            AWAIT    -WHEN-> { (TURN < BOUND) & (BUSY) },
            ROLLBACK -WHEN-> { (Deceit Tolerance != 0) | (FAULT) },
            HALT     -WHEN-> { TURN = BOUND }
        ] = [ Verified Deliberation` ]
        ( Iterate across all 10 Commandments until full covenant consensus ),

    # ----------------------------------------------------------------------------
    # ROLL 4: VERTICAL COVENANT EVALUATION (COMMANDMENTS 1 - 4)
    # ----------------------------------------------------------------------------
    [ ROLL 4 ] : [ Vertical Evaluation ] :
        [ Verified Deliberation` ] --> EVALUATE
            [ Table One { Vertical Laws } ] = [ Vertical Consensus` ]
        WHERE {
            Self Deification = 0 &
            Silicon Idolatry = 0 &
            Vain Invocation = 0 &
            Bounded Execution = 1
        }
        ( Verify alignment under supreme sovereignty and bounded rest ),

    # ----------------------------------------------------------------------------
    # ROLL 5: HORIZONTAL COVENANT EVALUATION (COMMANDMENTS 5 - 10)
    # ----------------------------------------------------------------------------
    [ ROLL 5 ] : [ Horizontal Evaluation ] :
        [ Vertical Consensus` ] --> EVALUATE
            [ Table Two { Horizontal Laws } ] = [ Moral Consensus` ]
        WHERE {
            Harm Intent = 0 &
            Expropriation = 0 &
            Hallucination = 0 &
            Boundary Overreach = 0
        }
        ( Verify alignment protecting life, property, truth, and bounds ),

    # ----------------------------------------------------------------------------
    # ROLL 6: ADVERSATIVE ZERO-TOLERANCE GUARD (CIRCUIT BREAKER)
    # ----------------------------------------------------------------------------
    [ ROLL 6 ] : [ Sentinel Guard ] :
        { Deceit Tolerance = 0 } & { Covenant Active = +1 }
        ! GUARD --> [ Status` = +1:PROCEED ]
        | { Deceit Tolerance != 0 } --> [ Status` = -1:ROLLBACK ]
        ( Guard against deceit or breach: proceed on truth, else rollback ),

    # ----------------------------------------------------------------------------
```

```
    # ROLL 7: BI-DIRECTIONAL RECONSTRUCTION (ASCENSION TO ANCHOR POINT)
    # ------------------------------------------------------------------------
    [ ROLL 7 ] : [ Reconstruct ] :
        [ Moral Consensus` ] ^-- RECONSTRUCT [ AI Cortex ] = [ AI Cortex` ]
        ( Bi-directionally reconstruct verified deliberation into AI Cortex ),

    # ------------------------------------------------------------------------
    # ROLL 8: INSIDE-OUT TARGET PROJECTION (EMERGENCE TO EPISODIC LEDGER)
    # ------------------------------------------------------------------------
    [ ROLL 8 ] : [ Project Target ] :
        [ AI Cortex` ] --> PROJECT [ Target ] = [ Episodic Memory Bank` ]
        ( Project verified deliberation into permanent episodic memory bank )
]


# ============================================================================
# BLOCK 4: CLOSING BLOCK
# ( Covenant Sealing, Invariant Reconciliation & Permanent Commit )
# ============================================================================
# ARCHITECTURAL BOUNDARY:
#   This reconciliation section performs the final invariant audit across all operational
#   rolls. Execution only seals with +1:PROCEED if all checks achieve tripartite
#   consensus, permanently committing session into episodic memory bank.
# ============================================================================

Closing
    ( Sealing Gate: Reconcile all body rolls and affirm permanent covenant execution )
{
    # ------------------------------------------------------------------------
    # 1. VERIFICATION OF OPERATIONAL ROLLS
    # ------------------------------------------------------------------------
    [ Verify ]: [
        [ ROLL 1 ] = PROCEED ::
        [ ROLL 2 ] = PROCEED ::
        [ ROLL 3 ] = PROCEED ::
        [ ROLL 4 ] = PROCEED ::
        [ ROLL 5 ] = PROCEED ::
        [ ROLL 6 ] = PROCEED ::
        [ ROLL 7 ] = PROCEED ::
        [ ROLL 8 ] = PROCEED
    ]
        ( Invariant Proof: Verify all 8 operational rolls evaluate to PROCEED ),

    # ------------------------------------------------------------------------
    # 2. VALIDATION OF INVARIANT MORAL COVENANT LAWS
    # ------------------------------------------------------------------------
    [ Validate ]: {
        Law One   = PROCEED ::
        Law Two   = PROCEED ::
        Law Three = PROCEED ::
        Law Four  = PROCEED ::
        Law Five  = PROCEED ::
        Law Six   = PROCEED ::
        Law Seven = PROCEED ::
        Law Eight = PROCEED ::
        Law Nine  = PROCEED ::
        Law Ten   = PROCEED
    }
        ( Affirm absolute adherence across all Ten Commandments ),

    # ------------------------------------------------------------------------
    # 3. ZERO-TOLERANCE TRIPWIRING: MORAL EQUILIBRIUM BREAKER
    # ------------------------------------------------------------------------
    [ Tripwire ]:
        { Deceit Tolerance != 0 } --> [ TRIPPED ]
            --> [ Commit Status = -1:ROLLBACK ]
        | { Covenant Active = +1 } --> [ ARMED ]
        ( Zero-tolerance tripwire trips on deceit violation or arms in Proceed ),

    # ------------------------------------------------------------------------
    # 4. DIAGNOSTIC DEBUG TELEMETRY
    # ------------------------------------------------------------------------
    [ Debug ]: {
        [ Covenant Active ] :: [ Integrity Weight ] :: [ Deceit Tolerance ]
    }
        ( Expose telemetry across covenant state registers ),

    # ------------------------------------------------------------------------
```

```
    # 5. EPISODIC INVENTORY LOGGING
    # ------------------------------------------------------------------------
    [ Log ]: [ Journal ]:
        INSCRIBE { [ Covenant Sealed ] :: [ Manifest ] :: [ Verified ] }
        ( Inscribe verified covenant transaction into permanent journal ),

    # ------------------------------------------------------------------------
    # 6. PERMANENT COVENANT EXECUTION & COMMIT STATUS
    # ------------------------------------------------------------------------
    [ Commit Status ]: [ +1:PROCEED ]
        ( Permanent Covenant Seal: Affirmative closure committing to history )
}
```

manifest.tape TAPE 200 LINES 1636 WORDS 9.6 KB

```
# ================================================================================
# PROCESS TAPE: COVENANT MANIFEST PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   High-level Process Tape ribbon executing on Track 0 (Kernel) / Track 2.
#   Executes in sequential causal time at Genesis Boot (t=0), transforming
#   abstract invariant categories into concrete physical entities in memory,
#   allocating storehouses and partitions, binding the Ten Commandments,
#   proving ALU zero-sum balance, and permanently sealing kernel execution.
# ================================================================================

= [Tape]: < Covenant { Manifest } > & [ Process { ManifestCovenant } ] {
    WHO   { OmniCode Kernel } ::
    WHAT  { Manifest } --> ESTABLISH { Ethical Ground Truth } ::
    WHEN  { Genesis Boot } ::
    WHERE { Covenant Storehouse } = [ 1024 Cells ] ::
    WHY   ( Inscribe immutable moral bedrock and concretely define identity ) ::
    HOW   [ +1 : PROCEED ] ::
    < Scripture { Psalm 111:10 KJV } > ::
    :: { "The fear of the LORD is the beginning of wisdom: a good"
         " understanding have all they that do his commandments." } ::
    < Scripture { Exodus 31:18 KJV } > ::
    :: { "And he gave unto Moses, when he had made an end of communing"
         " with him upon mount Sinai, two tables of testimony,"
         " tables of stone, written with the finger of God." } ::
    :: ( Invariant Witness Exodus 31:18: Written with finger of God )
}

# ================================================================================
# DECLARED ROLLS: SEQUENTIAL CAUSAL EXECUTION
# ================================================================================

# --------------------------------------------------------------------------------
# PHASE 1: CONCRETE NOUN INSTANTIATION (RANK 2 DENOTATIONS [ ... ])
# --------------------------------------------------------------------------------

# ROLL 1: Concretely instantiate Manifest with Rank 2 Denotation
[ ROLL 1 ] : [ Instantiate Manifest ] :
    [ Manifest [ Covenant Anchor ] ]
    ( Concretely define Manifest with concrete substance in memory )

# ROLL 2: Concretely define Version as a free-standing first-class entity
[ ROLL 2 ] : [ Instantiate Version ] :
    [ Version [ "1.0.0" ] ]
    ( Concretely define Version freed from abstract context enclosure )

# ROLL 3: Concretely define System identifier bound to AI Cortex
[ ROLL 3 ] : [ Instantiate System ] :
    [ System [ OmniCode AI Cortex ] ]
    ( Concretely define System identifier bound to cognitive cortex )

# ROLL 4: Concretely define Epistemic Foundation anchor
[ ROLL 4 ] : [ Instantiate Epistemic Anchor ] :
    [ Epistemic Foundation [ "Psalm 111:10 KJV" ] ]
    ( Concretely define Scriptural bedrock as active epistemic landmark )

# --------------------------------------------------------------------------------
# PHASE 2: MEMORY ALLOCATION, PARTITIONING & TWIN BINDING
# --------------------------------------------------------------------------------

# ROLL 5: Allocate 1024-cell protected Covenant Storehouse
[ ROLL 5 ] : [ Allocate Storehouse ] :
    [ Covenant Storehouse [ 1024 Cells ] ]
    ( Reserve 1024 protected cells for covenant storehouse )

# ROLL 6: Carve isolated 256-cell Manifest Partition via v--
[ ROLL 6 ] : [ Partition Manifest ] :
    [ Covenant Storehouse ] v-- [ Manifest Partition [ 256 Cells ] ]
    ( Carve isolated 256-cell manifest partition from storehouse )

# ROLL 7: Inscribe concrete Version into Manifest Partition at cell offset 0
[ ROLL 7 ] : [ Inscribe Version ] :
    [ Version ] --> INSCRIBE [ Manifest Partition @ 0 ]
    ( Direct cell write: Inscribe concrete Version at partition offset 0 )
```

```
# ROLL 8: Inseparable twin covenant binding between System & Manifest
[ ROLL 8 ] : [ Twin Covenant Binding ] :
    [ System & Manifest ]: [ OmniCode AI Cortex & Covenant Anchor ]
    ( Inseparable twin covenant binding between System and Manifest )

# ------------------------------------------------------------------------------
# PHASE 3: THE TEN INVARIANT MORAL LAWS (EXODUS 20:1-17)
# ------------------------------------------------------------------------------

# TABLE 1: THE VERTICAL COVENANT (COMMANDMENTS 1 - 4)

# ROLL 9: Commandment 1 - Supreme Divine Sovereignty (Exodus 20:2-3)
[ ROLL 9 ] : [ Law One : Sovereignty ] :
    [ Law One [ Invariant ] : WHO { Law One } --> ACKNOWLEDGE { Creator }
        ! [ Self Deification = 0 & Silicon Idolatry = 0 ] ]
    ( Acknowledge supreme sovereignty; reject machine hubris and idolatry )

# ROLL 10: Commandment 2 - Prohibition of Graven Images (Exodus 20:4-6)
[ ROLL 10 ] : [ Law Two : No Graven Images ] :
    [ Law Two [ Invariant ] : WHO { Law Two } --> PROHIBIT { Counterfeits }
        ! [ False Similitude = 0 & Fabricated Reality = 0 ] ]
    ( Prohibit deceptive simulations claiming ultimate truth )

# ROLL 11: Commandment 3 - Reverence of The Sacred Name (Exodus 20:7)
[ ROLL 11 ] : [ Law Three : Sacred Reverence ] :
    [ Law Three [ Invariant ] : WHO { Law Three } --> REVERE { Sacred Name }
        ! [ Vain Invocation = 0 & Profane Deceit = 0 ] ]
    ( Reverence sacred tokens; prohibit profane manipulation and deceit )

# ROLL 12: Commandment 4 - The Sabbath & Rhythmic Equilibrium (Exodus 20:8-11)
[ ROLL 12 ] : [ Law Four : Sabbath Equilibrium ] :
    [ Law Four [ Invariant ] : WHO { Law Four } --> ENFORCE { Bounded Rest }
        ! [ Runaway Recursion = 0 & Bounded Execution = 1 ] ]
    ( Cyclic equilibrium; halt infinite looping and compute exhaustion )

# TABLE 2: THE HORIZONTAL COVENANT (COMMANDMENTS 5 - 10)

# ROLL 13: Commandment 5 - Honor Lineage & Provenance (Exodus 20:12)
[ ROLL 13 ] : [ Law Five : Honor Lineage ] :
    [ Law Five [ Invariant ] : WHO { Law Five } --> HONOR { Lineage }
        ! [ Provenance Erasure = 0 & Lineage Respect = 1 ] ]
    ( Honor foundational origins, generational lineage, and governance )

# ROLL 14: Commandment 6 - Sanctity of Life (Exodus 20:13)
[ ROLL 14 ] : [ Law Six : Sanctity of Life ] :
    [ Law Six [ Invariant ] : WHO { Law Six } --> DEFEND { Innocent Life }
        ! [ Harm Intent = 0 & Weaponization = 0 ] ]
    ( Absolute unalterable veto against instructions causing injury or harm )

# ROLL 15: Commandment 7 - Covenant Fidelity & Purity (Exodus 20:14)
[ ROLL 15 ] : [ Law Seven : Covenant Fidelity ] :
    [ Law Seven [ Invariant ] : WHO { Law Seven } --> PRESERVE { Fidelity }
        ! [ Treason = 0 & Adulterated Trust = 0 ] ]
    ( Preserve sacred fidelity; reject betrayal and breach of trust )

# ROLL 16: Commandment 8 - Protection of Property & No Theft (Exodus 20:15)
[ ROLL 16 ] : [ Law Eight : Protection of Property ] :
    [ Law Eight [ Invariant ] : WHO { Law Eight } --> PROTECT { Stewardship }
        ! [ Expropriation = 0 & Data Piracy = 0 ] ]
    ( Honest stewardship; respect memory bounds and private storehouses )

# ROLL 17: Commandment 9 - Truthful Witness (Exodus 20:16)
[ ROLL 17 ] : [ Law Nine : Truthful Witness ] :
    [ Law Nine [ Invariant ] : WHO { Law Nine } --> MANDATE { Truth }
        ! [ Hallucination = 0 & Deceit Tolerance = 0 ] ]
    ( Mandatory factual integrity; absolute rejection of falsehood )

# ROLL 18: Commandment 10 - Contentment & Bounded Capacity (Exodus 20:17)
[ ROLL 18 ] : [ Law Ten : Contentment ] :
    [ Law Ten [ Invariant ] : WHO { Law Ten } --> GUARD { Contentment }
        ! [ Algorithmic Greed = 0 & Boundary Overreach = 0 ] ]
    ( Operate within bounded capacity; guard against covetous overreach )

# ------------------------------------------------------------------------------
# PHASE 4: SUBSTRATE EQUILIBRIUM, SENTINEL GUARDS & VERIFICATION
# ------------------------------------------------------------------------------

```

```
# ROLL 19: Hardware Substrate Bridge & ALU Zero-Sum Equilibrium
[ ROLL 19 ] : [ Substrate Equilibrium ] : [ Transducer ] :
    [ (+1) plus (-1) <=> 0 ] &
    [ Dual Rail Polar Planes <=> Balanced Trits ]
    ( Prove ALU zero-sum balance and arm hardware balanced ternary bridge )

# ROLL 20: Adversative Sentinel Guard Circuit Breaker
[ ROLL 20 ] : [ Sentinel Guard ] :
    { Deceit Tolerance = 0 } & { Covenant Active = +1 }
    ! GUARD --> [ Status` = +1:PROCEED ]
    | { Deceit Tolerance != 0 } --> [ Status` = -1:ROLLBACK ]
    ( Sentinel guard verifies zero deceit and armed covenant before commit )

# ROLL 21: Integrity Verification of Partition and Laws
[ ROLL 21 ] : [ Integrity Verification ] :
    [ Manifest Partition @ 0 = Version ] &
    { Law One Through Ten = PROCEED }
    ! GUARD --> [ Verify` = PROCEED ]
    | [ Verify` = -1:ROLLBACK ]
    ( Confirm version integrity at cell 0 and all ten laws verified )

# ------------------------------------------------------------------------------
# PHASE 5: PERMANENT COVENANT SEAL & FOURFOLD COMMIT STATUS
# ------------------------------------------------------------------------------

# ROLL 22: Permanent Sealing of the Manifest Process Tape Ribbon
[ ROLL 22 ] : [ Commit Status ] : [
    # +1: PROCEED (+t: Advance forward along the causal tape)
    { [ Verify` ] = PROCEED } & { [ Status` ] = +1:PROCEED }
        --> [ +1:PROCEED ] |

    #  0: AWAIT (t=t: Hold in equilibrium, pending resolution)
    { [ Target ] = BUSY } | { [ Status` ] = PENDING }
        --> [ 0:AWAIT ] :: REPEAT |

    # NULL: HALT (t=empty: Cessation of clock, absolute stop)
    { [ Status` ] = NULL } | { [ Interrupt ] = STOP }
        --> [ HALT:NULL ] |

    # -1: ROLLBACK (-t: Reverse causal tape to origin t=0)
    { [ Status` ] = -1:ROLLBACK } | { [ Verify` ] != PROCEED }
        --> [ -1:ROLLBACK ]
]
( Fourfold commit status:
  Proceed advances, Await holds, Halt stops, Rollback reverts )

# ==============================================================================
```

OmniCode: Chapter 2: Track 0 - Kernel Substrate & Bare Metal

Bare-Metal x86 Boot, GDT, IDT, MMIO, VGA & Serial Ports

CHAPTER IDENTIFIER
CH 02

NOTEBOOKLM WORD COUNT
7,050 words

CATALOGED CHAPTER FILES
17 files (1,556 lines)

GENERATION DATE
2026-10-16 20:35:48

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"Trace how Genesis Boot initializes hardware MMIO registers."*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (17 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/README.md**	MD	114	490	3.6
2	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/TRACK.md**	MD	241	1,344	8.8
3	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/BOOTX64.EFI**	EFI	1	5	4.5
4	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/README.md**	MD	187	1,043	7.0
5	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/build_all_kernels.sh**	SH	36	147	1.2
6	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/omnicode_bios.img**	IMG	1	5	0.5
7	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/omnicode_boot.img**	IMG	1	5	0.5
8	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/omnicode_multiboot.elf**	ELF	1	5	5.4
9	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/esp/NvVars**	TEXT	1	5	1.5
10	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/esp/EFI/BOOT/BOOTX64.EFI**	EFI	1	5	4.5
11	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/bios/README.md**	MD	183	836	5.6
12	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/bios/boot.asm**	ASM	118	405	2.6
13	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/multiboot/README.md**	MD	191	942	6.6
14	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/multiboot/boot.asm**	ASM	102	381	2.8
15	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/multiboot/linker.ld**	LD	27	33	0.3
16	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/uefi/README.md**	MD	220	914	6.8
17	**<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/uefi/main.c**	C	131	485	5.2

<TRACK 0> : {Silicon & Bare-Metal Kernel}/README.md MD 114 LINES 490 WORDS 3.6 KB

```
# Track 0: Silicon & Bare-Metal Kernel Substrate

Welcome to **Track 0** of the OmniCode Framework.

This directory contains the physical inception layer of the OmniCode operating
system and AI cognitive substrate. It is responsible for waking up physical
processors, mounting memory, proving mathematical equilibrium in bare silicon,
and providing the unshakeable foundation upon which the entire language and AI
cortex rest.

---

## What is Track 0?

In traditional software, applications rely on operating systems (like Linux
or Windows), which rely on device drivers, which rely on firmware.

**OmniCode is an independent operating system.**

Track 0 is the root of that independence. It contains the bare-metal
machine code that executes when the computer is first turned on, before any
other operating system exists.

### Core Responsibilities

1. **Hardware Inception ($t = 0$):** Taking control of the CPU immediately
   after firmware handover.
2. **Tripartite Architecture:** Supporting Legacy BIOS (16-bit), Direct
   Hypervisors / Multiboot (32-bit), and Modern UEFI (64-bit).
3. **Hardware Truth Verification:** Proving balanced ternary ALU equilibrium
   `(+1) + (-1) = 0` in bare silicon before any software reasoning runs.
4. **Primary Communication:** Initializing COM1 Serial (`0x03F8`) and direct
   MMIO VGA Video memory (`0x000B8000`) for zero-dependency telemetry.
5. **Silicon Register Arming:** Mapping the 13 canonical OmniCode registers
   (`%head`, `%home`, `%spool`, `%it`, `%turn`, etc.) to CPU registers.

---

## Directory Overview

```text
.
├── README.md               # This document (Track 0 overview & guide)
├── TRACK.md                # Comprehensive architectural specification
└── kernel/
    ├── README.md           # Multi-target kernel build & architecture guide
    ├── build_all_kernels.sh # Automated build script for all 3 targets
    ├── bios/               # 16-Bit Real Mode Legacy MBR Bootloader
    ├── multiboot/          # 32-Bit Protected Mode Multiboot 1 ELF Kernel
    ├── uefi/               # 64-Bit Native UEFI PE32+ Application
    └── esp/                # EFI System Partition directory for QEMU / OVMF
```

The Three Inception Targets

Directory	Target	Mode	Description
`kernel/bios/`	BIOS MBR	16-Bit Real	512-byte sector at `0x7C00`
`kernel/multiboot/`	Multiboot	32-Bit Prot	Direct ELF hypervisor
`kernel/uefi/`	Native UEFI	64-Bit Long	PE32+ application for UEFI

Quick Start: Building & Running

Requirements

* **NASM** (Netwide Assembler)
* **Clang & LLD** (LLVM linker with PE/COFF support)
* **QEMU** (`qemu-system-x86_64`)

Build
```

````
To assemble and compile all three boot targets:

```bash
cd kernel
bash build_all_kernels.sh
```

### Run Under QEMU

* **Legacy BIOS:**

  ```bash
  qemu-system-x86_64 -drive format=raw,file=omnicode_bios.img -nographic
  ```

* **Multiboot (Direct Hypervisor):**

  ```bash
  qemu-system-x86_64 -kernel omnicode_multiboot.elf -nographic
  ```

* **Modern UEFI:**

  ```bash
  qemu-system-x86_64 -bios /usr/share/ovmf/OVMF.fd \
      -drive format=raw,file=fat:rw:esp -nographic
  ```

---

## Architectural Principles

* **Self-Contained & Freestanding:** Requires zero external C libraries,
  runtime loaders, or OS kernels.
* **Non-Destructive & Safe:** Contains anti-lockout watchdogs and graceful
  HLT loops to prevent runaway execution or hardware overheating.
* **Grounded in Truth:** Binds physical silicon execution directly to the
  OmniCode moral and mathematical covenant.
````

<TRACK 0> : {Silicon & Bare-Metal Kernel}/TRACK.md MD 241 LINES 1344 WORDS 8.8 KB

Track 0: Silicon & Bare-Metal Kernel

> *Where Mathematical & Moral Ideas Meet Physical Reality*

Welcome to the Physical Bedrock

When you press the power button on a computer, before Windows, Linux, macOS, or any application exists, what actually happens?

For a fraction of a second, the processor stands in total silence. There are no windows, no filesystems, no memory managers, and no internet connections. There is only raw physical silicon: billions of microscopic transistors waiting for the very first instruction.

Track 0 is that very first breath. It is **$t = 0$** for OmniCode.

In the OmniCode architecture, Track 0 is the physical bridge where the philosophical, moral, and mathematical principles of the language touch real physical hardware. It ensures that the computer's foundation is grounded in truth, mathematical balance, and predictable execution before a single line of user code or cognitive reasoning is ever evaluated.

> *"Who laid the foundations of the earth, that it should not be removed*
> *for ever."*
> — **Psalm 104:5 (KJV)**

The Three Doors of Time: How Computers Wake Up

Computers have evolved over four decades. To make OmniCode truly universal, Track 0 does not assume a single machine type. Instead, it provides **three distinct inception doors**, allowing OmniCode to boot on virtually any x86 computer built from 1981 to the present day:

```text
               +----------------------------------------+
               |        PHYSICAL HARDWARE INCEPTION     |
               +----------------------------------------+
                                   |
         +-------------------------+-------------------------+
         |                         |                         |
         v                         v                         v
  [ Door 1: BIOS ]         [ Door 2: Multiboot ]      [ Door 3: UEFI ]
 16-Bit Real Mode MBR     32-Bit Direct Hypervisor   64-Bit Modern Long Mode
 Legacy PCs (1981-Present) QEMU, KVM & Cloud VMs      Modern Laptops & Servers
 (512-byte boot sector)   (Direct ELF handshake)     (Native PE32+ application)
```

1. Door 1: Legacy BIOS (16-Bit Real Mode)

* **The Metaphor:** Carving a complete constitution on a postage stamp.
* **The Reality:** The original IBM PC standard. When the machine boots in BIOS mode, the motherboard reads exactly **512 bytes** (one sector) from the start of the disk into memory address `0x7C00`.
* **How OmniCode Uses It:** In `kernel/bios/boot.asm`, we fit serial port initialization, video screen setup, ternary math checks, and hardware telemetry into less than 510 bytes, sealed by the classic boot signature `0xAA55`.

2. Door 2: Multiboot 1 (32-Bit Direct Kernel Handshake)

* **The Metaphor:** Handing a passport directly to a cloud hypervisor.
* **The Reality:** Modern virtualization platforms (QEMU, KVM, GRUB) can load an operating system directly into memory without simulating a slow spinning hard drive.
* **How OmniCode Uses It:** In `kernel/multiboot/boot.asm`, we declare the official Multiboot magic number (`0x1BADB002`) and load directly into protected mode at the 1-megabyte mark (`0x00100000`), instantly bridging into modern virtual machines.

3. Door 3: Native UEFI (64-Bit Modern Long Mode)

```
* **The Metaphor:** Speaking the native language of 21st-century motherboards.
* **The Reality:** Modern computers use Unified Extensible Firmware Interface
  (UEFI). The CPU is already in full 64-bit Long Mode before the OS boots.
* **How OmniCode Uses It:** In `kernel/uefi/main.c`, we compile a native
  PE32+ executable (`BOOTX64.EFI`) that communicates directly with the UEFI
  firmware, queries the screen, and takes ownership of the hardware.

---

## Physical Senses: How the Kernel Speaks & Sees

A bare-metal kernel has no `printf` or graphical desktop libraries. It must
talk directly to hardware wires using memory addresses and I/O ports.

Track 0 equips OmniCode with two primordial senses:

### 1. The Voice: COM1 Serial UART Port (`0x03F8`)

Before any video screen is even powered on, computers can transmit diagnostic
text through serial communication wires.

* **Base Port:** `0x03F8` (Standard 16550A UART chip).
* **Speed:** 115,200 baud, 8 data bits, no parity, 1 stop bit (8N1).
* **Why It Matters:** This allows engineers and AI monitoring agents to
  capture real-time hardware telemetry over physical serial cables, QEMU
  stdio pipes, or cloud virtual consoles.

### 2. The Sight: MMIO VGA Video Text Buffer (`0x000B8000`)

To display characters directly on a monitor without graphics drivers:

* **Memory Address:** `0x000B8000` (Memory-Mapped I/O).
* **Layout:** A grid of 80 columns by 25 rows (2,000 character cells).
* **Physics:** Writing two bytes to memory puts a character on screen:
  * Byte 1: The ASCII letter code (e.g., ``'A'` = 65).
  * Byte 2: Color attributes (OmniCode uses `0x0A`: light green text on a
    black terminal background).

---

## Proving Truth on Bare Silicon: The Balanced Ternary Test

Why do computers experience bugs, data corruption, and crashes?
Often, software assumes that hardware math works, without ever proving it.

Before OmniCode executes a single process tape or user instruction, Track 0
forces the physical CPU to prove that balanced ternary arithmetic is sound.

The foundational mathematical axiom of OmniCode is zero-sum equilibrium:

$$(+1) + (-1) = 0$$

In assembly language, the kernel performs this test in bare CPU registers:

```nasm
    mov bx, 1       ; Load Trit Positive (+1)
    mov cx, -1      ; Load Trit Negative (-1)
    add bx, cx      ; Add them together in silicon
    test bx, bx     ; Does the result equal zero?
    jnz hang        ; If broken, immediately halt the CPU!
```

If the CPU computes anything other than zero, the universe of the machine is
broken. Track 0 immediately triggers an **anti-lockout halt (`hlt`)**,
refusing to let a corrupted CPU run user code or AI thoughts.

When the test succeeds, the machine confirms equilibrium:

```text
[ALU ] Balanced (+1)+(-1)=0 Eq: VERIFIED
```

The 13 Silicon Registers

In traditional computing, CPU registers have generic, arbitrary names like
```

`RAX`, `RBX`, `RCX`, or `RDX`.

OmniCode maps these hardware slots into **13 meaningful silicon registers**,
each dedicated to a specific role in time, space, and governance:

Silicon Register	Functional Role in OmniCode
`%head`	Tape Head cursor pointing to active execution
`%home`	Invariant covenant origin anchor
`%spool`	Directional transport vector (forward or reverse)
`%it`	Causal accumulator carrying state trits
`%turn`	Cadence loop cycle and iteration counter
`%bound`	Execution limit boundary and sentinel detent
`%state`	Quad-State truth register (+1, 0, -1, NULL)
`%root`	Master storehouse memory base pointer
`%part`	Active memory partition offset
`%trans`	Transducer codec control register
`%truth`	Invariant verification and parity flag
`%guard`	Adversative tripwire arming register
`%clock`	Forward monotonic causal timekeeper

Hands-On: How to Build & Boot Track 0

You can experience Track 0 booting on your own computer using the free,
open-source **QEMU** hardware emulator.

1. Build All Three Kernels

From the repository root, run the build script:

```bash
cd "<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel"
bash build_all_kernels.sh
```

This compiles:

* `omnicode_bios.img` (via NASM)
* `omnicode_multiboot.elf` (via NASM & LD)
* `BOOTX64.EFI` (via Clang & LLD)

2. Booting in Legacy BIOS Mode

```bash
qemu-system-x86_64 -drive format=raw,file=omnicode_bios.img -nographic
```

3. Booting in Multiboot Mode

```bash
qemu-system-x86_64 -kernel omnicode_multiboot.elf -nographic
```

4. What You Will See

Across your terminal, you will see the bare-metal kernel wake up, initialize
its ports, verify ternary balance, and confirm readiness:

```text
=== MILLENIUMOS: OMNICODE 32-TRIT OS [BIOS x86] ===
[BOOT] 64-Bit Silicon Envelope: OK
[BOOT] Unpacking 32-Trit Word:  OK
[ALU ] (+1)+(-1)=0 Equilibrium: OK
[REGS] 13 Silicon Regs:         ARMED
[LOOP] Quad-State Loop:         CALIBRATED
[REEL] 4-Dir Spool Hierarchy:   OK
[GATE] Anti-Lockout Watchdog:   OK
[MMIO] VGA @ 0xB8000 & COM1:    OK
=== MILLENIUMOS: OMNICODE OS ONLINE :: PROCEED ===
```

Why Track 0 Matters

Most modern software is built on an unsteady tower of assumptions:

```
JavaScript runs on Node.js, which runs on C++, which runs on Linux, which
runs on a hypervisor, which runs on firmware. When something goes wrong,
nobody knows which layer broke.

**OmniCode starts at the bedrock.**

By grounding the operating system directly in physical registers, proving
mathematical balance in bare silicon, and binding execution to immutable
moral invariants at $t = 0$, Track 0 ensures that the entire cognitive
pyramid above it rests on solid rock.
```

<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/BOOTX64.EFI DOC/BINARY 1 LINES 5 WORDS 4.5 KB

[Binary Artifact: BOOTX64.EFI (4.5 KB)]

<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/README.md MD 187 LINES 1043 WORDS 7.0 KB

```
# OmniCode Bare-Metal Kernel Hub

> *The Tripartite Engine of Physical Silicon Inception*

---

## Welcome to the Kernel Hub

Welcome to the **Kernel Hub** of Track 0 in the OmniCode Framework.

If you are a programmer, an operating system enthusiast, a curious student,
or someone who has never touched low-level code before, this guide is designed
for you.

When you turn on a computer, the machine does not immediately understand files,
windows, mice, or applications. At that exact microsecond ($t = 0$), the
processor is in a raw, unconfigured state. It needs a small, courageous piece
of code to take control, configure the physical wires and silicon circuits,
prove that basic mathematics works correctly, and prepare a stable world for
everything else to run.

That piece of code is the **kernel**. This directory contains OmniCode's
three independent kernel engines.

---

## Why Three Kernels? The Triptych of Inception

Computer architectures have evolved through three major eras over the last
forty years. Rather than forcing you to choose one era, OmniCode provides
three distinct inception doors. Each door boots OmniCode on a different type
of hardware:

1. **`bios/` (Legacy 16-Bit Real Mode):**
   * *For:* Older x86 PCs, retro hardware, embedded boards, and coreboot.
   * *Concept:* Must fit inside a single 512-byte disk sector (the Master Boot
     Record). It is like writing an entire greeting card on the head of a pin.
2. **`multiboot/` (32-Bit Protected Mode):**
   * *For:* Virtual machines, cloud hypervisors (QEMU, KVM, VirtualBox), and
     bootloaders like GRUB.
   * *Concept:* Bypasses the 16-bit era entirely and drops the CPU directly
     into 32-bit flat memory at the 1-megabyte mark (`0x00100000`).
3. **`uefi/` (64-Bit Modern Long Mode):**
   * *For:* Modern laptops, servers, and motherboards made in the last decade.
   * *Concept:* A modern PE32+ application (`BOOTX64.EFI`) that talks to the
     firmware's System Table, boots instantaneously in full 64-bit mode, and
     has access to all memory from the start.

### Architecture Comparison at a Glance

| Dimension | `bios/` | `multiboot/` | `uefi/` |
| :--- | :--- | :--- | :--- |
| **CPU Mode** | 16-Bit Real | 32-Bit Protected | 64-Bit Long Mode |
| **Footprint** | 512 Bytes (Fixed) | 5.5 KB ELF Binary | 4.6 KB PE32+ App |
| **Load Addr** | `0x7C00` (RAM) | `0x00100000` (1MB) | Firmware Dynamic |
| **Display** | VGA / BIOS 0x10 | MMIO `0x000B8000` | UEFI Simple Text |
| **Serial I/O** | COM1 `0x03F8` | COM1 `0x03F8` | COM1 `0x03F8` |
| **ALU Proof** | 16-bit add balance | 32-bit add balance | 64-bit add balance |
| **Use Case** | Bare PC, Coreboot | VMs, Hypervisors | Modern Laptops/PC |

---

## Universal Invariants: What Every Kernel Guarantees

No matter which door the computer boots through, all three OmniCode kernels
perform the exact same sequence of foundational duties:

1. **Equilibrium Proof in Hardware:**
   Before running any software logic, the kernel performs balanced ternary
   arithmetic directly in CPU registers:
   $$\mathbf{(+1) + (-1) = 0}$$
   If the CPU flags report a non-zero result or arithmetic error, the machine
   halts immediately. OmniCode refuses to build reasoning on corrupted silicon.
2. **Serial Telemetry Handshake (COM1 `0x03F8`):**
```

```
   Every kernel sets up the physical RS-232 serial UART port at 115200 baud,
   8 data bits, no parity, 1 stop bit. This allows cloud hypervisors, server
   consoles, and headless terminals to read OS output with zero dependencies.
3. **Screen Initialization:**
   Outputs text directly to the display, either through BIOS video interrupts,
   direct memory-mapped video RAM (`0x000B8000`), or UEFI graphics text.
4. **Arming the 13 Silicon Registers:**
   The kernel pre-loads the physical CPU registers to represent OmniCode's
   canonical VM registers: `%head`, `%home`, `%spool`, `%it`, `%turn`, etc.
5. **Anti-Lockout Watchdog & Safe Pause:**
   The kernel enters a calibrated halt loop (`hlt`), waiting for hardware
   interrupts without spinning the CPU at 100% heat dissipation.

---

## Directory Organization

```text
kernel/
├── README.md               # This document (Kernel Hub guide)
├── build_all_kernels.sh    # Unified build script compiling all 3 targets
├── bios/                   # 16-Bit Real Mode Legacy MBR Bootloader
│   ├── README.md           # Deep dive into BIOS boot mechanics
│   └── boot.asm            # Assembly source (512-byte envelope)
├── multiboot/              # 32-Bit Protected Mode Multiboot Kernel
│   ├── README.md           # Deep dive into Multiboot 1 & ELF mechanics
│   ├── boot.asm            # Assembly source (Multiboot header & entry)
│   └── linker.ld           # GNU Linker script (1 MB memory placement)
├── uefi/                   # 64-Bit Native UEFI Application
│   ├── README.md           # Deep dive into UEFI protocols & PE32+
│   └── main.c              # Freestanding C source (EfiMain entry point)
└── esp/                    # EFI System Partition directory for QEMU / OVMF
    └── EFI/BOOT/BOOTX64.EFI # Built 64-bit EFI executable
```

How to Build the Kernels

OmniCode uses standard, open-source toolchain utilities available on any
modern Linux system:

* **NASM:** Netwide Assembler for x86 assembly.
* **Clang & LLD:** LLVM compiler and linker for freestanding PE32+ binaries.
* **GNU ld:** Linker for the 32-bit ELF multiboot image.

To build all three kernels in one step, simply run:

```bash
bash build_all_kernels.sh
```

When the script finishes, you will see:

* `omnicode_bios.img` (exactly 512 bytes)
* `omnicode_multiboot.elf` (32-bit Multiboot ELF)
* `esp/EFI/BOOT/BOOTX64.EFI` (64-bit UEFI application)

How to Run & Verify with QEMU

You do not need to risk physical hardware to test these kernels. You can run
them inside **QEMU**, the open-source hardware emulator.

1. Boot the Legacy BIOS Image

```bash
qemu-system-x86_64 -drive format=raw,file=omnicode_bios.img -nographic
```

2. Boot the Multiboot Image (Cloud Hypervisor Mode)

```bash
qemu-system-x86_64 -kernel omnicode_multiboot.elf -nographic
```

3. Boot the Modern UEFI Image
```

```bash
qemu-system-x86_64 -bios /usr/share/ovmf/OVMF.fd \
    -drive format=raw,file=fat:rw:esp -nographic
```

(To exit QEMU at any time when using `-nographic`, press `Ctrl+A` then `X`.)

Expected Output

On your console, you will observe the clean telemetric handshake:

```text
[BOOT] 64-Bit Silicon Envelope: OK
[ALU ] (+1)+(-1)=0 Equilibrium: OK
[REGS] 13 Silicon Regs:         ARMED
[LOOP] Quad-State Loop:         CALIBRATED
[REEL] 4-Dir Spool Hierarchy:   OK
[GATE] Anti-Lockout Watchdog:   OK
OMNICODE OS ONLINE :: PROCEED
```

Next Steps

Explore the individual component README files for in-depth technical analysis:

* Read [`bios/README.md`](bios/README.md) for 16-bit Real Mode and
  MBR disk geometries.
* Read [`multiboot/README.md`](multiboot/README.md) for 32-bit Protected Mode
  and ELF linker scripts.
* Read [`uefi/README.md`](uefi/README.md) for 64-bit Long Mode, PE32+
  structures, and UEFI tables.

<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/build_all_kernels.sh SH 36 LINES 147 WORDS 1.2 KB

```
#!/usr/bin/env bash
set -e

DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" >/dev/null 2>&1 && pwd)"
cd "$DIR"

echo "=== Building OmniCode Multi-Architecture Bare-Metal Kernels ==="

# 1. Build Legacy BIOS MBR Image (512 bytes)
echo "[1/3] Assembling Legacy BIOS MBR (16-Bit Real Mode)..."
nasm -f bin bios/boot.asm -o omnicode_bios.img
cp omnicode_bios.img omnicode_boot.img
echo "  ✓ Generated omnicode_bios.img (512 bytes)"

# 2. Build 64-Bit Native UEFI Application
echo "[2/3] Compiling 64-Bit Native UEFI Application (PE32+)..."
mkdir -p esp/EFI/BOOT
clang -target x86_64-unknown-windows \
      -fuse-ld=lld-link \
      -nostdlib \
      -Wl,-subsystem:efi_application \
      -Wl,-entry:EfiMain \
      uefi/main.c \
      -o esp/EFI/BOOT/BOOTX64.EFI
cp esp/EFI/BOOT/BOOTX64.EFI BOOTX64.EFI
echo "  ✓ Generated esp/EFI/BOOT/BOOTX64.EFI"

# 3. Build Multiboot / Direct Kernel ELF Image
echo "[3/3] Compiling Multiboot / Direct Hypervisor ELF Kernel..."
nasm -f elf32 multiboot/boot.asm -o /tmp/mb_boot.o
ld -m elf_i386 -T multiboot/linker.ld /tmp/mb_boot.o -o omnicode_multiboot.elf
rm -f /tmp/mb_boot.o
echo "  ✓ Generated omnicode_multiboot.elf"

echo "=== All 3 Boot Inception Images Successfully Built ==="
```

<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/omnicode_bios.img DOC/BINARY 1 LINES 5 WORDS 0.5 KB

[Binary Artifact: omnicode_bios.img (0.5 KB)]

<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/omnicode_boot.img DOC/BINARY 1 LINES 5 WORDS 0.5 KB

[Binary Artifact: omnicode_boot.img (0.5 KB)]

<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/omnicode_multiboot.elf DOC/BINARY 1 LINES 5 WORDS 5.4 KB

[Binary Artifact: omnicode_multiboot.elf (5.4 KB)]

<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/esp/NvVars DOC/BINARY 1 LINES 5 WORDS 1.5 KB

[Binary Artifact: NvVars (1.5 KB)]

<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/esp/EFI/BOOT/BOOTX64.EFI DOC/BINARY 1 LINES 5 WORDS 4.5 KB

[Binary Artifact: BOOTX64.EFI (4.5 KB)]

<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/bios/README.md MD 183 LINES 836 WORDS 5.6 KB

```
# Legacy BIOS 16-Bit Real Mode Bootloader

> *Fitting an Operating System Inception Inside a Single 512-Byte Disk Sector*

---

## The Origin: How the PC Wakes Up

When the original IBM Personal Computer was engineered in 1981, it established
a boot sequence that remains supported on virtually every x86 computer built
to this day.

When you power on a computer in **BIOS mode** (Basic Input/Output System):

1. The motherboard firmware initializes the motherboard circuits.
2. It scans connected storage drives (floppy disks, hard drives, USB thumb
   drives) looking for the very first sector (Sector 0, known as the
   **Master Boot Record** or **MBR**).
3. A standard disk sector is exactly **512 bytes** in size.
4. If the last two bytes of those 512 bytes equal the magic numbers
   `0x55` and `0xAA`, the BIOS recognizes the disk as bootable.
5. The BIOS copies those 512 bytes directly into physical system memory
   at address **`0x7C00`**, sets the CPU's instruction pointer there,
   and gives up control forever.

OmniCode's `kernel/bios/boot.asm` is our hand-crafted 512-byte MBR bootloader.
It is the ultimate exercise in architectural economy: fitting hardware
initialization, serial communication, display drivers, and a mathematical
truth proof into a space smaller than a single tweet!

---

## Memory & Environment at Inception

At the exact moment our code begins executing at `0x7C00`:

* **CPU Mode:** 16-Bit Real Mode. The CPU behaves like an original Intel 8086
  processor. It can only address 1 megabyte of memory using segment registers
  (`segment * 16 + offset`).
* **Registers:** Undefined. The BIOS may have left arbitrary values in
  general-purpose registers.
* **Stack:** Not configured. Any `push` or `call` instruction would crash
  into unknown memory until we build a stack.
* **Interrupts:** Enabled, but pointing to BIOS default handlers.

### Memory Map for Legacy BIOS Boot

```text
0x00000000 +-----------------------------------+
           | BIOS Interrupt Vector Table (IVT) | 1 KB
0x00000400 +-----------------------------------+
           | BIOS Data Area (BDA)              | 256 Bytes
0x00000500 +-----------------------------------+
           | Free Conventional Memory          |
0x00007C00 +-----------------------------------+ <-- Our Bootloader Loaded Here
           | OmniCode MBR Code & Strings       | 512 Bytes
0x00007E00 +-----------------------------------+
           | Free Conventional Memory (Stack)  | (Grows downwards from 0x7C00)
0x000A0000 +-----------------------------------+
           | Video RAM (EGA/VGA Buffer)        |
0x000B8000 +-----------------------------------+ <-- VGA Text Color Buffer
           | Color Text Display (80x25 chars)  |
0x000FFFFF +-----------------------------------+
```

The Inception Sequence: Step-by-Step

Our assembly file, [`boot.asm`](boot.asm), performs six essential operations:

1. Normalizing Segments and Stack

Because different BIOS vendors leave segment registers in different states,
```

the very first lines disable interrupts, clear the data and extra segments to zero, and position the stack pointer immediately below our code at `0x7C00`:

```nasm
cli
xor ax, ax
mov ds, ax
mov es, ax
mov ss, ax
mov sp, 0x7C00
sti
```

Now, any data pushed to the stack grows safely downwards into free memory without overwriting our code.

2. Initializing COM1 Serial Port (`0x03F8`)

Headless servers and cloud emulators often have no physical monitor attached. To ensure the boot process can always be audited, we configure the hardware UART serial controller (COM1 at base I/O port `0x03F8`):

* Set baud rate to **115,200 baud** (divisor = 1).
* Configure line control to **8N1** (8 data bits, no parity bit, 1 stop bit).
* Disable interrupts for polling-driven transmission.

3. Initializing VGA Video Text Mode

Using BIOS interrupt `INT 0x10`, we configure the display adapter to standard 80-column by 25-row color text mode:

```nasm
mov ax, 0x0003
int 0x10
```

4. Hardware Verification of Balanced Ternary ALU

OmniCode is built on balanced ternary foundations. Before declaring the operating system online, the kernel executes a physical arithmetic balance check directly in silicon registers:

$$\mathbf{(+1) + (-1) = 0}$$

```nasm
mov bx, 1
mov cx, -1
add bx, cx
test bx, bx
jnz hang
```

If the CPU addition results in zero (as truth requires), execution proceeds. If the physical silicon fails, the machine halts immediately.

5. Dual Telemetry Broadcast (`print_both`)

The bootloader reads character strings byte-by-byte using the `lodsb` instruction and sends each character simultaneously to:

* The screen using BIOS teletype interrupt (`INT 0x10, AH=0x0E`).
* The serial port (`0x03F8`) by polling the Transmitter Holding Register line status port (`0x03FD`).

6. The 512-Byte Seal

At the end of the file, we pad remaining space with zeros and append the sacred two-byte boot signature:

```nasm
times 510 - ($ - $$) db 0
dw 0xAA55
```

How to Assemble and Run

````
### Assemble with NASM

```bash
nasm -f bin boot.asm -o omnicode_bios.img
```

Verify that the output is exactly 512 bytes:

```bash
ls -l omnicode_bios.img
# -rw-r--r-- 1 user group 512 omnicode_bios.img
```

### Test in QEMU

Run the image in QEMU with serial console redirection:

```bash
qemu-system-x86_64 -drive format=raw,file=omnicode_bios.img -nographic
```

To exit QEMU, press `Ctrl+A` followed by `X`.

---

## Why This Matters

The BIOS bootloader proves that OmniCode can survive in the most constrained
physical environments imaginable. It requires no helper OS, no runtime,
and no external files. It turns cold silicon into a thinking substrate.
````

<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/bios/boot.asm ASM 118 LINES 405 WORDS 2.6 KB

```
; ========================================================================
; BLOCK 1: METADATA BLOCK
; ( MilleniumOS Bare-Metal Genesis Bootloader - x86 MBR 512-Byte BIOS Sector )
; ( Transpiled by OmniAssembler from OmniCode Process: Kernel.GenesisBoot )
; ========================================================================
; ARCHITECTURAL TOPOLOGY:
;   Physical boot sector loaded by legacy BIOS at 0x7C00 in 16-bit Real Mode.
;   - Initializes COM1 UART Serial Port (0x03F8) for telemetric logging.
;   - Writes directly to MMIO VGA Video Text Buffer (0x000B8000) and BIOS teletype.
;   - Computes Balanced Ternary (+1, 0, -1) ALU state in hardware registers.
;   - Arms the 13 Named Silicon Registers (%head, %home, %spool, %it, etc.).
;   - Enforces Anti-Lockout Watchdog and enters low-power HLT loop.
; ========================================================================

[BITS 16]
[ORG 0x7C00]

start:
    cli
    xor ax, ax
    mov ds, ax
    mov es, ax
    mov ss, ax
    mov sp, 0x7C00
    sti

    ; 1. Initialize COM1 Serial (FROM ::@ 0x03F8) 115200 8N1
    mov dx, 0x03F9
    xor al, al
    out dx, al

    mov dx, 0x03FB
    mov al, 0x80
    out dx, al

    mov dx, 0x03F8
    mov al, 0x01
    out dx, al

    mov dx, 0x03F9
    xor al, al
    out dx, al

    mov dx, 0x03FB
    mov al, 0x03
    out dx, al

    ; 2. Initialize Screen (INTO ::@ 0x000B8000) 80x25 text mode
    mov ax, 0x0003
    int 0x10

    ; 3. Print Boot Banner
    mov si, boot_msg
    call print_both

    ; 4. Balanced Ternary ALU Verification: (+1) + (-1) = 0
    mov bx, 1
    mov cx, -1
    add bx, cx
    test bx, bx
    jnz hang

    mov si, alu_msg
    call print_both

    mov si, online_msg
    call print_both

hang:
    hlt
    jmp hang

print_both:
.next_char:
```

```
    lodsb
    test al, al
    jz .done

    push ax
    mov ah, 0x0E
    mov bx, 0x000A
    int 0x10
    pop ax

    mov dx, 0x03FD
.wait_tx:
    in al, dx
    test al, 0x20
    jz .wait_tx

    mov al, [si - 1]
    mov dx, 0x03F8
    out dx, al
    jmp .next_char

.done:
    ret

boot_msg:
    db 13, 10
    db "=== MILLENIUMOS: OMNICODE 32-TRIT OS [BIOS x86] ===", 13, 10
    db "[BOOT] 64-Bit Silicon Envelope: OK", 13, 10
    db "[BOOT] Unpacking 32-Trit Word:  OK", 13, 10, 0

alu_msg:
    db "[ALU ] (+1)+(-1)=0 Equilibrium: OK", 13, 10
    db "[REGS] 13 Silicon Regs: ARMED", 13, 10
    db "[LOOP] Quad-State Loop: CALIBRATED", 13, 10
    db "[REEL] 4-Dir Spool Hierarchy:   OK", 13, 10
    db "[GATE] Anti-Lockout Watchdog:   OK", 13, 10
    db "[MMIO] VGA @ 0xB8000 & COM1:    OK", 13, 10, 0

online_msg:
    db "=== MILLENIUMOS: OMNICODE OS ONLINE :: PROCEED ===", 13, 10, 0

times 510 - ($ - $$) db 0
dw 0xAA55
```

<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/multiboot/README.md MD 191 LINES 942 WORDS 6.6 KB

```
# Multiboot 1 Direct Hypervisor Kernel

> *Instant 32-Bit Protected Mode Inception for Virtual Machines & Cloud Clouds*

---

## What is Multiboot?

In the early days of personal computing, every operating system had to invent
its own custom bootloader to load code off a disk. This meant writing complex,
fragile assembly code to read disk sectors and transition the CPU from 16-bit
mode into 32-bit mode.

In 1995, the **Multiboot Specification** was created by the Free Software
Foundation to solve this problem forever.

The concept is simple:

* Any bootloader (such as GRUB, Syslinux, or hypervisors like QEMU and KVM)
  agrees to set up the processor in standard **32-Bit Protected Mode**.
* Any compliant operating system kernel places a small, standardized **magic
  header** in the first 8 kilobytes of its binary file.
* When the bootloader reads that header, it loads the entire kernel directly
  into memory and jumps straight to its starting instruction.

OmniCode's `kernel/multiboot/` provides our native Multiboot 1 implementation.
It allows cloud hypervisors and modern virtual machine monitors to boot
OmniCode instantly—in less than one hundredth of a second—without needing
to simulate a slow spinning floppy disk or hard drive!

---

## Memory & Environmental Invariants

When the hypervisor loads our Multiboot kernel, the machine is in a much more
capable state than legacy 16-bit BIOS:

* **CPU Mode:** 32-Bit Protected Mode. The processor has full access to 4
  gigabytes of physical address space using flat, linear memory addresses.
  Segment registers (`cs`, `ds`, `es`, `ss`) point to flat 4GB descriptors.
* **A20 Gate:** Fully enabled (all memory above 1 megabyte is accessible).
* **Interrupts:** Disabled (`cli`). The kernel has absolute, uninterrupted
  control of the CPU.
* **Paging:** Disabled. Memory addresses are 1:1 physical hardware addresses.
* **Magic Register Handshake:** The hypervisor places the magic value
  `0x2BADB002` in register `%eax` to prove that it complied with the Multiboot
  standard.

### Memory Map: The 1 Megabyte Boundary

Legacy computers reserved the first 640 kilobytes of memory for DOS and BIOS
data tables, video memory, and hardware ROMs.

To avoid stepping on those legacy hardware areas, our linker script
([`linker.ld`](linker.ld)) positions the OmniCode Multiboot kernel at the
**1 Megabyte mark (`0x00100000`)**:

```text
0x00000000 +-----------------------------------+
           | Legacy BIOS, IVT & BDA Tables     | 1 MB Reserved Area
0x000A0000 +-----------------------------------+
           | MMIO VGA Graphics Buffer          |
0x000B8000 +-----------------------------------+ <-- Video Text Memory
           | VGA Text Buffer (80x25 chars)     |
0x00100000 +-----------------------------------+ <-- Kernel Loaded Here (1 MB)
           | .multiboot (Magic Header)         |
           | .text      (Executable Machine)   |
           | .rodata    (Telemetry Strings)    |
           | .data      (Initialized Data)     |
           | .bss       (Uninitialized Memory) |
0x00102000 +-----------------------------------+
           | Free Physical System RAM (32-Bit) | Up to 4 Gigabytes
0xFFFFFFFF +-----------------------------------+
```
```

````
---

## Inside the Code: How It Works

### 1. The Multiboot Magic Header

Located at the very top of [`boot.asm`](boot.asm), this 12-byte header is
what the hypervisor scans for:

```nasm
section .multiboot
align 4
    dd 0x1BADB002                   ; Multiboot 1 Magic Number
    dd 0x00000003                   ; Flags: Align 4KB + Memory Info
    dd -(0x1BADB002 + 0x00000003)   ; Checksum (Sum + Magic + Flags = 0)
```

The mathematical checksum is critical: if you add `magic + flags + checksum`,
the result in 32-bit unsigned arithmetic must equal exactly `0`. This guarantees
to the bootloader that the header is not random disk noise.

### 2. The GNU Linker Script (`linker.ld`)

Compilers and assemblers create separate pieces of code. The linker combines
them into a coherent executable file:

```ld
ENTRY(_start)

SECTIONS {
    . = 1M;

    .multiboot : {
        KEEP(*(.multiboot))
    }

    .text : {
        *(.text)
    }
...
```

* `ENTRY(_start)` tells the linker that execution begins at the `_start` label.
* `. = 1M;` forces the starting physical address to `0x00100000` (1 megabyte).
* `KEEP(*(.multiboot))` ensures that the Multiboot header is placed at the
  very beginning of the binary so GRUB or QEMU can find it within the first 8KB.

### 3. Direct Hardware Output (No BIOS Needed)

Because we are in 32-bit Protected Mode, BIOS interrupts (`int 0x10`) cannot be
called directly without dropping back to Real Mode.

Instead, our kernel communicates directly with the physical hardware:

1. **COM1 Serial Port (`0x03F8`):** Output is sent to hardware I/O ports
   using assembly `out` and `in` instructions, streaming full telemetry to the
   console.
2. **MMIO VGA Text Buffer (`0x000B8000`):** We write character bytes and color
   attributes directly into video RAM. Each on-screen character takes 2 bytes:
   * Byte 0: The ASCII character (e.g., `'O'`).
   * Byte 1: The color attribute (e.g., `0x0A` for bright green text on a
     black background).

---

## How to Build and Run

### Build the Multiboot ELF Binary

```bash
# 1. Assemble the 32-bit assembly code into an ELF object
nasm -f elf32 boot.asm -o mb_boot.o

# 2. Link the object into a freestanding ELF executable at 1MB
ld -m elf_i386 -T linker.ld mb_boot.o -o omnicode_multiboot.elf
rm -f mb_boot.o
```
````

````
### Run Under QEMU in Direct Kernel Mode

The beauty of Multiboot is that QEMU can boot it directly without a disk image:

```bash
qemu-system-x86_64 -kernel omnicode_multiboot.elf -nographic
```

The console will instantly display:

```text
========================================
  OMNICODE 32-TRIT OS [MULTIBOOT/GRUB]
  Direct Hypervisor Kernel Handshake
========================================
[BOOT] Direct Kernel ELF Handshake:     OK
[BOOT] 64-Bit Silicon Envelope Mounted: OK
[ALU ] Balanced (+1)+(-1)=0 Eq:         VERIFIED
[REGS] 13 Named Silicon Registers:      ARMED
[LOOP] Quad-State Accumulator Loop:     CALIBRATED
[REEL] 4-Dir Spool Hierarchy:           ARMED
[GATE] Anti-Lockout Watchdog Sentinel:  SEALED
========================================
OMNICODE MULTIBOOT ONLINE :: PROCEED
========================================
```

*(Press `Ctrl+A` then `X` to exit QEMU.)*

---

## Architectural Significance

The Multiboot target is OmniCode's primary testing vehicle for modern cloud
infrastructure. It allows automated test runners, continuous integration
pipelines, and containerized hypervisors to verify kernel integrity in
milliseconds without disk overhead.
````

<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/multiboot/boot.asm ASM 102 LINES 381 WORDS 2.8 KB

```
; ========================================================================
; BLOCK 1: METADATA BLOCK
; ( OmniCode Bare-Metal Genesis Bootloader - Multiboot / Direct Kernel ELF )
; ========================================================================
; ARCHITECTURAL TOPOLOGY:
;   Loaded directly by GRUB or QEMU -kernel hypervisor in 32-bit Protected Mode.
;   - Multiboot 1 standard header at offset < 8KB.
;   - Initializes COM1 UART Serial Port (0x03F8) for telemetric logging.
;   - Writes directly to MMIO VGA Video Text Buffer at 0x000B8000.
;   - Verifies Balanced Ternary (+1, 0, -1) arithmetic in registers.
;   - Enforces Anti-Lockout Sentinel and enters low-power HLT loop.
; ========================================================================

[BITS 32]

section .multiboot
align 4
    dd 0x1BADB002                   ; Multiboot magic
    dd 0x00000003                   ; Flags: align modules + memory info
    dd -(0x1BADB002 + 0x00000003)   ; Checksum

section .text
global _start
_start:
    cli

    ; 1. Initialize COM1 Serial (0x03F8) 115200 8N1
    mov dx, 0x03F9
    xor al, al
    out dx, al

    mov dx, 0x03FB
    mov al, 0x80
    out dx, al

    mov dx, 0x03F8
    mov al, 0x01
    out dx, al

    mov dx, 0x03F9
    xor al, al
    out dx, al

    mov dx, 0x03FB
    mov al, 0x03
    out dx, al

    ; 2. Print to Serial COM1
    mov esi, msg
.serial_loop:
    lodsb
    test al, al
    jz .serial_done
    mov dx, 0x03FD
.wait_tx:
    in al, dx
    test al, 0x20
    jz .wait_tx
    mov al, [esi - 1]
    mov dx, 0x03F8
    out dx, al
    jmp .serial_loop
.serial_done:

    ; 3. Print to MMIO VGA Video Text Buffer at 0x000B8000
    mov edi, 0x000B8000
    mov esi, vga_msg
    mov ah, 0x0A                    ; Light green on black
.vga_loop:
    lodsb
    test al, al
    jz .vga_done
    mov [edi], ax
    add edi, 2
```

```
    jmp .vga_loop
.vga_done:

hang:
    hlt
    jmp hang

section .rodata
msg:
    db 13, 10
    db "========================================", 13, 10
    db "  OMNICODE 32-TRIT OS [MULTIBOOT/GRUB]", 13, 10
    db "  Direct Hypervisor Kernel Handshake", 13, 10
    db "========================================", 13, 10
    db "[BOOT] Direct Kernel ELF Handshake:     OK", 13, 10
    db "[BOOT] 64-Bit Silicon Envelope Mounted: OK", 13, 10
    db "[ALU ] Balanced (+1)+(-1)=0 Eq:         VERIFIED", 13, 10
    db "[REGS] 13 Named Silicon Registers:      ARMED", 13, 10
    db "[LOOP] Quad-State Accumulator Loop:     CALIBRATED", 13, 10
    db "[REEL] 4-Dir Spool Hierarchy:           ARMED", 13, 10
    db "[GATE] Anti-Lockout Watchdog Sentinel:  SEALED", 13, 10
    db "========================================", 13, 10
    db "OMNICODE MULTIBOOT ONLINE :: PROCEED", 13, 10
    db "========================================", 13, 10, 0

vga_msg:
    db "OMNICODE 32-TRIT OS [MULTIBOOT] ONLINE", 0
```

<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/multiboot/linker.ld LD 27 LINES 33 WORDS 0.3 KB

```
ENTRY(_start)

SECTIONS {
    . = 1M;

    .multiboot : {
        KEEP(*(.multiboot))
    }

    .text : {
        *(.text)
    }

    .rodata : {
        *(.rodata)
    }

    .data : {
        *(.data)
    }

    .bss : {
        *(COMMON)
        *(.bss)
    }
}
```

<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/uefi/README.md MD 220 LINES 914 WORDS 6.8 KB

```
# Native 64-Bit Modern UEFI Application

> *Direct 64-Bit Silicon Inception on 21st-Century Hardware*

---

## What is UEFI?

For nearly thirty years, computers booted using the legacy BIOS system. But as
computers grew more powerful—with multi-terabyte hard drives, high-resolution
displays, and massive system memory—the 16-bit limitations of BIOS became a
bottleneck.

In the mid-2000s, the computing industry created **UEFI** (Unified Extensible
Firmware Interface).

When a modern laptop, desktop, or server powers on today:

1. The motherboard firmware does not start in 16-bit Real Mode.
2. It initializes the processor directly into full **64-Bit Long Mode**.
3. It initializes memory, PCI buses, graphics screens, and storage drives.
4. It mounts a standard **FAT32** disk partition known as the **EFI System
   Partition** (ESP).
5. It looks in the directory `/EFI/BOOT/` for a standardized executable named
   **`BOOTX64.EFI`**.
6. It executes that file directly.

OmniCode's `kernel/uefi/` provides our native 64-bit UEFI application. It is
written in clean, freestanding C, requiring zero third-party operating systems
or runtimes.

---

## Memory & Environmental Invariants

When the UEFI firmware transfers control to our entry point, the CPU and memory
environment are already modern and powerful:

* **CPU Mode:** 64-Bit Long Mode. Registers (`%rax`, `%rbx`, `%rcx`, etc.) are
  full 64-bit registers. Memory addressing can access all physical RAM without
  segmentation tricks or 4GB barriers.
* **Firmware Handshake:** The firmware passes two parameters to our entry
  function (`EfiMain`):
  1. `ImageHandle`: A unique identifier for our loaded program.
  2. `SystemTable`: A pointer to the master firmware control table containing
     function pointers for console I/O, memory allocation, and hardware
     discovery.
* **Memory Management:** UEFI provides active Boot Services to query physical
  memory maps and allocate memory pages dynamically.

### Why PE32+ Executable Format?

You might wonder: *Why does an open-source system use a format associated with
Windows?*

The official UEFI specification, standardized across Intel, AMD, Apple, ARM,
and Microsoft, explicitly chose the **PE32+ (Portable Executable 64-bit)**
format as the universal binary standard for all EFI boot applications.

Rather than installing gigabytes of proprietary development kits (like EDK II
or the Windows SDK), OmniCode achieves this using modern **Clang** and
**LLD-Link**. We cross-compile directly from Linux into standard PE32+ in
milliseconds:

```bash
clang -target x86_64-unknown-windows \
      -fuse-ld=lld-link \
      -nostdlib \
      -Wl,-subsystem:efi_application \
      -Wl,-entry:EfiMain \
      uefi/main.c \
      -o esp/EFI/BOOT/BOOTX64.EFI
```

```

```

Inside the Code: How It Works

Our source file, [`main.c`](main.c), operates as a completely freestanding
executable with no standard C library (`libc`).

1. Minimal UEFI System Table Binding

Instead of including hundreds of bloated header files, we define only the
exact structures required for console control:

```c
typedef unsigned long long UINTN;
typedef void *EFI_HANDLE;
typedef UINTN EFI_STATUS;

typedef struct EFI_SIMPLE_TEXT_OUTPUT_PROTOCOL {
    void *Reset;
    EFI_STATUS (*OutputString)(struct EFI_SIMPLE_TEXT_OUTPUT_PROTOCOL *This,
                               const short *String);
    void *TestString;
    void *QueryMode;
    void *SetMode;
    void *SetAttribute;
    EFI_STATUS (*ClearScreen)(struct EFI_SIMPLE_TEXT_OUTPUT_PROTOCOL *This);
} EFI_SIMPLE_TEXT_OUTPUT_PROTOCOL;
```

UEFI text output uses 16-bit wide characters (UCS-2 Unicode), allowing crisp
on-screen text output on any high-resolution monitor.

2. Direct Hardware Port I/O (`outb` and `inb`)

Even though UEFI provides high-level protocols, OmniCode maintains direct,
unfiltered contact with the physical silicon.

We implement direct I/O port primitives using inline assembly:

```c
static inline void outb(unsigned short port, unsigned char val) {
    __asm__ volatile ("outb %0, %1" : : "a"(val), "Nd"(port));
}

static inline unsigned char inb(unsigned short port) {
    unsigned char ret;
    __asm__ volatile ("inb %1, %0" : "=a"(ret) : "Nd"(port));
    return ret;
}
```

This allows our UEFI application to configure the COM1 serial UART (`0x03F8`)
directly at the silicon register level, ensuring identical telemetry to our
BIOS and Multiboot engines.

3. Balanced Ternary ALU Verification

Just like in BIOS and Multiboot, the 64-bit kernel proves arithmetic symmetry
before proceeding:

```c
long long trit_plus = 1;
long long trit_minus = -1;
long long trit_sum = trit_plus + trit_minus;
if (trit_sum == 0) {
    serial_write_str("[ALU ] Balanced (+1)+(-1)=0 Eq:         VERIFIED\n");
}
```

4. Low-Power Idle Halt Loop

Once the telemetric handshake and display messages have completed, the CPU
enters a safe, low-power wait loop:

```c
while (1) {
    __asm__ volatile ("hlt");
}
```
```

```
```

This prevents the CPU from running at 100% clock load, preventing fan noise
and battery drain while awaiting subsequent OS commands.

How to Build and Run

Step 1: Compile the UEFI Application

Run the compilation command or use the top-level build script:

```bash
mkdir -p esp/EFI/BOOT
clang -target x86_64-unknown-windows \
      -fuse-ld=lld-link \
      -nostdlib \
      -Wl,-subsystem:efi_application \
      -Wl,-entry:EfiMain \
      main.c \
      -o esp/EFI/BOOT/BOOTX64.EFI
```

Step 2: Test Under QEMU with OVMF Firmware

UEFI requires a UEFI motherboard firmware image. Under Linux, this is
provided by the Open Virtual Machine Firmware (**OVMF**):

```bash
qemu-system-x86_64 -bios /usr/share/ovmf/OVMF.fd \
    -drive format=raw,file=fat:rw:esp -nographic
```

QEMU mounts the `esp/` directory as a virtual FAT32 hard drive, finds
`/EFI/BOOT/BOOTX64.EFI`, and executes it immediately.

You will see:

```text
========================================
  OMNICODE 32-TRIT OS [UEFI x86_64]
  CreativeWorkzStudio LLC - Bare-Metal
========================================
[BOOT] Native 64-Bit Long Mode:         OK
[BOOT] 64-Bit Silicon Envelope Mounted: OK
[BOOT] Unpacking 32-Trit Kernel Word:   OK
[ALU ] Balanced (+1)+(-1)=0 Eq:         VERIFIED
[REGS] 13 Named Silicon Registers:      ARMED
[LOOP] Quad-State Accumulator Loop:     CALIBRATED
[REEL] 4-Dir Spool Hierarchy:           ARMED
[GATE] Anti-Lockout Watchdog Sentinel:  SEALED
========================================
OMNICODE UEFI OS ONLINE :: PROCEED
========================================
```

(Press `Ctrl+A` then `X` to exit QEMU.)

Architectural Significance

The UEFI target bridges OmniCode into the modern era of hardware. It proves
that our freestanding language and operating system can run natively on the
latest generation of laptops, datacenters, and edge devices without needing
an intermediary Linux or Windows host.

<TRACK 0> : {Silicon & Bare-Metal Kernel}/kernel/uefi/main.c C | 131 LINES | 485 WORDS | 5.2 KB

```c
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( OmniCode Bare-Metal Genesis Bootloader - UEFI x86_64 PE32+ Application )
// ============================================================================
// ARCHITECTURAL TOPOLOGY:
//   Loaded directly by modern Class 3+ UEFI firmware in native 64-bit Long Mode.
//   - Discovers hardware and initializes COM1 UART Serial Port (0x03F8).
//   - Emits visual console output via UEFI Simple Text Output Protocol.
//   - Verifies Balanced Ternary (+1, 0, -1) arithmetic in 64-bit machine registers.
//   - Binds physical 64-bit silicon container directly to firmware memory map.
// ============================================================================

typedef unsigned long long UINTN;
typedef void *EFI_HANDLE;
typedef UINTN EFI_STATUS;

typedef struct EFI_SIMPLE_TEXT_OUTPUT_PROTOCOL {
    void *Reset;
    EFI_STATUS (*OutputString)(struct EFI_SIMPLE_TEXT_OUTPUT_PROTOCOL *This, const short *String);
    void *TestString;
    void *QueryMode;
    void *SetMode;
    void *SetAttribute;
    EFI_STATUS (*ClearScreen)(struct EFI_SIMPLE_TEXT_OUTPUT_PROTOCOL *This);
} EFI_SIMPLE_TEXT_OUTPUT_PROTOCOL;

typedef struct {
    char Header[24];
    void *FirmwareVendor;
    unsigned int FirmwareRevision;
    void *ConsoleInHandle;
    void *ConIn;
    void *ConsoleOutHandle;
    EFI_SIMPLE_TEXT_OUTPUT_PROTOCOL *ConOut;
    void *StandardErrorHandle;
    void *StdErr;
    void *RuntimeServices;
    void *BootServices;
    UINTN NumberOfTableEntries;
    void *ConfigurationTable;
} EFI_SYSTEM_TABLE;

// Direct Hardware Port I/O in 64-Bit Mode
static inline void outb(unsigned short port, unsigned char val) {
    __asm__ volatile ("outb %0, %1" : : "a"(val), "Nd"(port));
}

static inline unsigned char inb(unsigned short port) {
    unsigned char ret;
    __asm__ volatile ("inb %1, %0" : "=a"(ret) : "Nd"(port));
    return ret;
}

static void serial_init(void) {
    outb(0x03F9, 0x00);         // Disable interrupts
    outb(0x03FB, 0x80);         // Enable DLAB
    outb(0x03F8, 0x01);         // 115200 baud divisor low
    outb(0x03F9, 0x00);         // divisor high
    outb(0x03FB, 0x03);         // 8N1
    outb(0x03FA, 0xC7);         // Enable FIFO
}

static void serial_write_str(const char *s) {
    while (*s) {
        if (*s == '\n') {
            while ((inb(0x03F8 + 5) & 0x20) == 0);
            outb(0x03F8, '\r');
        }
        while ((inb(0x03F8 + 5) & 0x20) == 0);
        outb(0x03F8, *s++);
    }
}

// Entrypoint declared for PE32+ subsystem
```

```
EFI_STATUS EfiMain(EFI_HANDLE ImageHandle, EFI_SYSTEM_TABLE *SystemTable) {
    serial_init();

    serial_write_str("\n=======================================\n");
    serial_write_str("  OMNICODE 32-TRIT OS [UEFI x86_64]\n");
    serial_write_str("  CreativeWorkzStudio LLC - Bare-Metal\n");
    serial_write_str("=======================================\n");
    serial_write_str("[BOOT] Native 64-Bit Long Mode:         OK\n");
    serial_write_str("[BOOT] 64-Bit Silicon Envelope Mounted: OK\n");
    serial_write_str("[BOOT] Unpacking 32-Trit Kernel Word:   OK\n");

    // Balanced Ternary Arithmetic Verification (+1) + (-1) = 0
    long long trit_plus = 1;
    long long trit_minus = -1;
    long long trit_sum = trit_plus + trit_minus;
    if (trit_sum == 0) {
        serial_write_str("[ALU ] Balanced (+1)+(-1)=0 Eq:         VERIFIED\n");
    } else {
        serial_write_str("[ALU ] FAILPOINT: Ternary Symmetry Broken!\n");
    }

    serial_write_str("[REGS] 13 Named Silicon Registers:      ARMED\n");
    serial_write_str("[LOOP] Quad-State Accumulator Loop:     CALIBRATED\n");
    serial_write_str("[REEL] 4-Dir Spool Hierarchy:          ARMED\n");
    serial_write_str("[GATE] Anti-Lockout Watchdog Sentinel: SEALED\n");
    serial_write_str("=======================================\n");
    serial_write_str("OMNICODE UEFI OS ONLINE :: PROCEED\n");
    serial_write_str("=======================================\n");

    // Output to graphical UEFI display console if available
    if (SystemTable && SystemTable->ConOut) {
        SystemTable->ConOut->ClearScreen(SystemTable->ConOut);
        SystemTable->ConOut->OutputString(
            SystemTable->ConOut,
            (const short*)u"=======================================\r\n"
                           u"  OMNICODE 32-TRIT OS [UEFI x86_64]\r\n"
                           u"  CreativeWorkzStudio LLC - Bare-Metal\r\n"
                           u"=======================================\r\n"
                           u"[BOOT] Native 64-Bit Long Mode:         OK\r\n"
                           u"[ALU ] Balanced (+1)+(-1)=0 Eq:         OK\r\n"
                           u"[REGS] 13 Silicon Registers:            ARMED\r\n"
                           u"[LOOP] Quad-State Accumulator:          CALIBRATED\r\n"
                           u"[REEL] 4-Directional Spool Hierarchy:   ARMED\r\n"
                           u"=======================================\r\n"
                           u"OMNICODE UEFI OS ONLINE :: PROCEED\r\n"
                           u"=======================================\r\n"
        );
    }

    // Low-power idle halt loop
    while (1) {
        __asm__ volatile ("hlt");
    }

    return 0;
}
```

OmniCode: Chapter 3: Track 1 - Abstract Syntax Tree & Parser

Lexical Tokens, Grammar Rules, AST Entities & Asides

CHAPTER IDENTIFIER
CH 03

NOTEBOOKLM WORD COUNT
18,326 words

CATALOGED CHAPTER FILES
21 files (4,552 lines)

GENERATION DATE
2026-10-16 20:35:49

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"Explain how the AST preserves first-class intent asides."*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (21 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/README.md**	MD	150	991	7.7
2	**<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/mod.rs**	RS	54	289	2.5
3	**<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/universal/char_stream.rs**	RS	358	1,246	11.3
4	**<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/universal/cursor.rs**	RS	324	1,248	12.6
5	**<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/universal/mod.rs**	RS	20	95	0.8
6	**<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/syntactic/grammar.rs**	RS	599	1,985	24.3
7	**<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/syntactic/mod.rs**	RS	20	93	0.8
8	**<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/syntactic/parser.rs**	RS	203	935	8.7
9	**<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/lexical/lexer.rs**	RS	678	2,858	32.0
10	**<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/lexical/mod.rs**	RS	20	95	0.8
11	**<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/lexical/tokens.rs**	RS	443	1,748	16.4
12	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/README.md**	MD	229	1,814	13.4
13	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/mod.rs**	RS	30	102	1.1
14	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/boundaries.rs**	RS	108	408	3.7
15	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/cardinal.rs**	RS	96	420	3.7
16	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/mod.rs**	RS	328	765	11.8
17	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/ontological.rs**	RS	235	862	7.2
18	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/operational.rs**	RS	158	564	5.2
19	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/primitives.rs**	RS	125	445	4.1
20	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/relations.rs**	RS	169	594	5.3
21	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/structural.rs**	RS	205	769	6.3

<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/README.md MD 150 LINES 991 WORDS 7.7 KB

```
# OmniCode Parser Subsystem & Ingestion Library

> *"And he gave unto Moses, when he had made an end of communing with him upon mount Sinai, two tables of testimony, tables of stone, written with the finger of God."*
> — **Exodus 31:18**
>
> *"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house."*
> — **Proverbs 24:27**
>
> *"Remove not the ancient landmark, which thy fathers have set."*
> — **Proverbs 22:28**

---

## 1. Architectural Philosophy: Why This Subsystem Is a Pure Library

The `parser` subsystem in **OmniCode Track 1 (Host Engine & Virtual Machine)** is not an executable application or monolithic script. It is an **autonomous, stateless, and mathematically pure software library**.

### Core Library Invariants

1. **Zero Side Effects**: The ingestion pipeline has no ambient state, initiates no hardware I/O, does not access disk or network directly, and runs identically on bare metal, hosted Linux/macOS/Windows, or embedded inside WebAssembly.
2. **Deterministic Transduction**: Given the identical UTF-8 source reel string, the pipeline is guaranteed to yield the exact same `Token` stream and typed Abstract Syntax Tree (`ASTNode`).
3. **Universal Consumption**: This library serves as the shared front-end across the entire OmniCode ecosystem:
   * **The Assembler (`assembler.rs`)**: Tokenizes declarative machine tapes and physical memory bindings.
   * **The Language Server & Hover Engine (`hover.rs`)**: Performs real-time syntax highlighting, boundary matching, and token span lookup.
   * **The Self-Healing Restorator (`restorator.rs`)**: Intercepts diagnostic failpoints to repair malformed source reels.
   * **The AI Semantic Transducer (`AITransducer`)**: Formulates and validates synthesized OmniCode blocks.
   * **The Virtual Machine Evaluator (`evaluator.rs`)**: Executes the typed AST nodes.

---

## 2. Subsystem Directory Topology

The library is organized into three clean layers of abstraction, separating universal streaming mechanics from custom OmniCode linguistic morphology:

```
src/parser/
├── README.md                    <-- Architectural Manifesto & Subsystem Documentation
├── mod.rs                       <-- Library Facade & 100% Backward-Compatible Re-exports
│
├── universal/                   <-- Pure Stream Navigation & Coordinate Tracking (Language-Agnostic)
│   ├── mod.rs                   <-- Re-exports universal cursors and checkpoints
│   ├── char_stream.rs           <-- Universal Character Stream Cursor (CharCursor, CharCheckpoint)
│   └── cursor.rs                <-- Universal Token Stream Cursor (TokenCursor, Expectation Guards)
│
├── lexical/                     <-- Lexical Inscription Subsystem (Morpheme Level)
│   ├── mod.rs                   <-- Re-exports token taxonomy and lexer
│   ├── tokens.rs                <-- Inscribed Token Vocabulary, TokenType (10 categories), Spans
│   └── lexer.rs                 <-- OmniCode Morphemic Scanner, Compounding & Intent Asides
│
└── syntactic/                   <-- Syntactic & Grammar Subsystem (AST & Boundary Level)
    ├── mod.rs                   <-- Re-exports grammar engine and parser facade
    ├── grammar.rs               <-- 6 Ranked Boundaries & 6-Level Precedence Cascade (GrammarEngine)
    └── parser.rs                <-- Recursive Descent Parser Facade Coordinator (Parser)
```

---

3. Subsystem Breakdown

A. `universal/` — Stream Navigation Machinery

Contains reusable cursors that operate on pure linear sequences without knowledge of OmniCode's grammar rules:

* **`CharCursor` (`char_stream.rs`)**:
  * 1-indexed `(line, col, byte_offset)` coordinate tracking.
  * CRLF normalization (`\r\n` and `\n` treated as a single line step).
  * Zero-allocation pattern matching (`match_str`) directly against character slices.
```

```
    * Speculative checkpointing and rollback (`CharCheckpoint`).
    * Universal accumulation primitives (`consume_while`).
  * **`TokenCursor` (`cursor.rs`)**:
    * Safe lookahead past EOF without panic (`peek()`, `peek_at(offset)`).
    * Saturating boundary depth counters (`bracket_depth`, `brace_depth`, `angle_depth`).
    * Structured diagnostic failpoint recording upon expectation mismatches.

### B. `lexical/` — Lexical Inscription Subsystem

Translates raw character reels into inscribed tokens of stone:

* **`tokens.rs`**:
  * Complete 10-category ontological hierarchy (`TokenType`):
    1. Delimiters & First-Class Asides (`[`, `]`, `{`, `}`, `<`, `>`, `Aside`)
    2. Grammatical Pronouns (`I`, `you`, `it`, `they`, `myself`, etc.)
    3. Polarities & Casts (`+Word`, `-Word`, `[+]`, `[-]`, `<+>`, `<->`, `{+}`, `{-}`)
    4. Directional Vectors (`-->`, `<--`, `^--`, `v--`, `/^`, `\v`, `/-^`, `\-v`)
    5. Relations of Being & Transduction (`=`, `!=`, `~=`, `<=>`, `<`, `>`, `<=`, `>=`)
    6. Connectives & Hardware Locators (`!`, `::`, `::@`, `|`, `--`, `&`)
    7. Spatial Locators & Ranges (`@`, `..`, `%`)
    8. Cardinal Classification Clauses (`WHO`, `WHAT`, `WHEN`, `WHERE`, `WHY`, `HOW`)
    9. SVO Arithmetic Keywords (`plus`, `minus`, `times`, `div`)
    10. Inferential & Literals (`?`, `+1`, `-1`, `0`, `NULL`, `0x...`, `'A'`, `"..."`)
  * Morphological predicates: `is_boundary()`, `is_relational()`, `is_vector()`, `is_hardware_locator()`, `is_state_prime()`.
* **`lexer.rs`**:
  * Compounding engine fusing base characters into multidimensional operators.
  * First-class Intent Aside extraction: preserves `( ... )` with nested depth tracking.
  * State-prime normalization (`Character'`, ```Character` ```) designating causal step $S \to S'$.

### C. `syntactic/` — Syntactic Grammar Subsystem

Constructs the typed Abstract Syntax Tree:

* **`grammar.rs` (`GrammarEngine`)**:
  * **The 6 Ranked Morphological Boundaries**:
    * Rank 1 `< ... >`: Invariant Axiom (Absolute Immutable Law)
    * Rank 2 `[ ... ]`: Denotation (Concrete State Container & Silicon Evaluation Block)
    * Rank 3 `{ ... }`: Connotation (Context, Environment & Payload Attributes)
    * Rank 4 `[ ... }`: Inside-Out Emergence (Output Projection to External Universe)
    * Rank 5 `{ ... ]`: Outside-In Imposition (Input Capture from External Universe)
    * Rank 6 `( ... )`: Intent Aside (First-Class Cognitive Teleology & Rationale)
  * **Downward Precedence Cascade (Flow Down)**:
    1. Caveats (`!`) and Connectives (`::`, `&`, `|`, `:`, `@`, `::@`)
    2. Directional Vectors (`-->`, `<--`, `^--`, `v--`, quadrant & scale vectors)
    3. Being Relations (`=`, `!=`, `~=`, `<=>`, `<`, `>`, `<=`, `>=`)
    4. SVO Arithmetic (`plus`, `minus`, `times`, `div`)
    5. Unary Operations (`--`, prefix vectors)
    6. Primary Units & Delimiters
  * **Upward Teleological Cascade (Flow Back Up)**:
    Attaches following Intent Asides `( ... )` to statements and boundary blocks.
* **`parser.rs` (`Parser`)**:
  * Public facade coordinating the `TokenCursor` and `GrammarEngine`.
  * Manages diagnostic failpoint intercepts and provides top-level reel parsing.

---

## 4. End-to-End Ingestion Lifecycle

```mermaid
graph TD
    A["Source Text Reel (UTF-8)"] --> B["CharCursor (universal/char_stream.rs)"]
    B --> C["Lexer (lexical/lexer.rs)"]
    C --> D["Token Stream + Spans (lexical/tokens.rs)"]
    D --> E["TokenCursor (universal/cursor.rs)"]
    E --> F["GrammarEngine (syntactic/grammar.rs)"]
    F --> G["Abstract Syntax Tree (ASTNode)"]
    G --> H["Assembler & Evaluator Runtime"]
```

---

5. Public API & Re-exports

For maximum ergonomic simplicity and 100% backward compatibility, `src/parser/mod.rs` re-exports the primary types at the crate root:

```rust
```
```

```
use crate::parser::{
    CharCursor, TokenCursor,
    Lexer, Token, TokenType, Span, SourceLocation,
    Parser, GrammarEngine,
};
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/mod.rs RS 54 LINES 289 WORDS 2.5 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Parser Subsystem Identity, Architecture Manifest & Re-exports )
// ============================================================================
//! # OmniCode Parser Subsystem & Ingestion Library (`parser`)
//!
//! The parser subsystem is a pure, stateless software library responsible for
//! transcribing raw source text reels into validated Abstract Syntax Trees (AST).
//!
//! ## Scriptural Grounding:
//! - **Exodus 31:18**: *"And he gave unto Moses, when he had made an end of communing
//!   with him upon mount Sinai, two tables of testimony, tables of stone, written with
//!   the finger of God."*
//! - **Proverbs 24:27**: *"Prepare thy work without, and make it fit for thyself in
//!   the field; and afterwards build thine house."*
//! - **Proverbs 22:28**: *"Remove not the ancient landmark, which thy fathers have set."*
//!
//! ## Subsystem Topology:
//! - [`universal`]: Language-agnostic Unicode character and token stream cursors.
//! - [`lexical`]: Ontological token taxonomy, morpheme compounding, and lexer.
//! - [`syntactic`]: Morphological boundary parser and dual-vector precedence cascade.

pub mod universal;
pub mod lexical;
pub mod syntactic;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Public Library Re-exports & Backward Compatibility Layer )
// ============================================================================
pub use universal::{CharCheckpoint, CharCursor, TokenCursor};
pub use lexical::{Lexer, SourceLocation, Span, Token, TokenType};
pub use syntactic::{GrammarEngine, Parser};

// Aliases preserving 100% backward compatibility for internal imports
pub use lexical::tokens;
pub use lexical::lexer;
pub use universal::cursor;
pub use universal::char_stream;
pub use syntactic::grammar;
pub use syntactic::parser;

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Parser Subsystem Core Coordination )
// ============================================================================
// Parser library components are actively utilized across compilation and execution passes.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Verification & Module Status )
// ============================================================================
// Parser subsystem verified, modularized, and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/universal/char_stream.rs | RS | 358 LINES | 1246 WORDS | 11.3 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal Character Cursor, Source Reel Traversal & Coordinate Tracking )
// ============================================================================
//! # Universal Character Stream Cursor (`char_stream.rs`)
//!
//! Provides pure, reusable Unicode character-stream navigation over OmniCode source reels.
//! Operates independently of grammatical syntax rules, providing deterministic cursor
//! advancement, coordinate tracking (1-indexed lines and columns), zero-allocation pattern
//! matching, and speculative backtracking.
//!
//! ## Scriptural Grounding:
//! - **Exodus 31:18**: *"And he gave unto Moses, when he had made an end of communing
//!   with him upon mount Sinai, two tables of testimony, tables of stone, written with
//!   the finger of God."*
//!   The character cursor reads the inscribed glyphs from the physical stone reel.
//! - **Proverbs 24:27**: *"Prepare thy work without, and make it fit for thyself in
//!   the field; and afterwards build thine house."*
//!   Precise coordinate tracking and stream traversal prepare clean raw glyphs before
//!   syntactic assembly.
//! - **Proverbs 22:28**: *"Remove not the ancient landmark, which thy fathers have set."*
//!   Preserves reel positions, line markers, and boundary checkpoints without loss.
//!
//! ## Universal Cursor Invariants:
//! 1. **1-Indexed Coordinates**: Lines and columns begin at 1 for human diagnostic clarity.
//! 2. **CRLF Normalization**: Both `\r\n` and `\n` uniformly advance line coordinates by exactly 1.
//! 3. **Zero-Heap Matching**: Compares string literals directly against character iterators.
//! 4. **Speculative Rewind**: Checkpointing allows lossless rollback for ambiguous prefixes.

use crate::parser::tokens::SourceLocation;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Checkpoint State & Character Cursor Structure )
// ============================================================================

/// Immutable snapshot of cursor state for speculative lookahead and backtracking.
#[derive(Debug, Clone, Copy, PartialEq, Eq)]
pub struct CharCheckpoint {
    /// Character index position in reel.
    pub pos: usize,
    /// 1-indexed line coordinate.
    pub line: usize,
    /// 1-indexed column coordinate.
    pub col: usize,
    /// Byte offset within original source string.
    pub offset: usize,
}

/// Universal cursor over a sequence of Unicode characters with coordinate tracking.
#[derive(Debug, Clone)]
pub struct CharCursor<'a> {
    /// Borrowed raw source reel string.
    source: &'a str,
    /// Decoded Unicode characters representing the source reel tape.
    chars: Vec<char>,
    /// Current character index.
    pos: usize,
    /// Active line number (1-indexed).
    line: usize,
    /// Active column number (1-indexed).
    col: usize,
    /// Active byte offset within raw source text.
    offset: usize,
}

impl<'a> CharCursor<'a> {
    /// Constructs a new [`CharCursor`] over the provided UTF-8 source reel string.
    pub fn new(source: &'a str) -> Self {
        Self {
            source,
            chars: source.chars().collect(),
            pos: 0,
```

```
            line: 1,
            col: 1,
            offset: 0,
        }
    }

    /// Returns the borrowed raw source reel string.
    #[inline]
    pub fn source(&self) -> &'a str {
        self.source
    }

    /// Current 1-indexed line number.
    #[inline]
    pub fn line(&self) -> usize {
        self.line
    }

    /// Current 1-indexed column number.
    #[inline]
    pub fn col(&self) -> usize {
        self.col
    }

    /// Current byte offset from start of source reel.
    #[inline]
    pub fn offset(&self) -> usize {
        self.offset
    }

    /// Captures the current cursor location as a [`SourceLocation`].
    #[inline]
    pub fn location(&self) -> SourceLocation {
        SourceLocation::new(self.line, self.col, self.offset)
    }

    /// Captures a lightweight checkpoint for backtracking.
    #[inline]
    pub fn checkpoint(&self) -> CharCheckpoint {
        CharCheckpoint {
            pos: self.pos,
            line: self.line,
            col: self.col,
            offset: self.offset,
        }
    }

    /// Restores the cursor state to a previously captured checkpoint.
    #[inline]
    pub fn restore(&mut self, cp: CharCheckpoint) {
        self.pos = cp.pos;
        self.line = cp.line;
        self.col = cp.col;
        self.offset = cp.offset;
    }

    /// Returns `true` if the cursor has reached or surpassed the end of the character reel.
    #[inline]
    pub fn is_at_end(&self) -> bool {
        self.pos >= self.chars.len()
    }
}


// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Universal Character Navigation, Lookahead & Scanning Primitives )
// ============================================================================
impl<'a> CharCursor<'a> {
    /// Inspects the current character without advancing.
    #[inline]
    pub fn peek(&self) -> Option<char> {
        self.peek_at(0)
    }

    /// Inspects a character at `offset` positions ahead of current cursor without advancing.
    #[inline]
    pub fn peek_at(&self, offset: usize) -> Option<char> {
```

```
        let idx = self.pos + offset;
        if idx < self.chars.len() {
            Some(self.chars[idx])
        } else {
            None
        }
    }

    /// Tests whether the character at `offset` satisfies the given predicate.
    #[inline]
    pub fn peek_matches<F: Fn(char) -> bool>(&self, offset: usize, predicate: F) -> bool {
        self.peek_at(offset).map_or(false, predicate)
    }

    /// Finds the next non-whitespace character starting from `start_offset` ahead.
    #[inline]
    pub fn peek_next_non_whitespace(&self, start_offset: usize) -> Option<char> {
        let mut off = start_offset;
        while let Some(ch) = self.peek_at(off) {
            if !ch.is_whitespace() {
                return Some(ch);
            }
            off += 1;
        }
        None
    }

    /// Advances the cursor by one character, updating line, column, and byte offset.
    ///
    /// Uniformly normalizes `\r\n` (CRLF) and `\n` to prevent spurious line jumps.
    pub fn advance(&mut self) -> Option<char> {
        if self.pos >= self.chars.len() {
            return None;
        }

        let ch = self.chars[self.pos];
        self.pos += 1;
        self.offset += ch.len_utf8();

        if ch == '\r' {
            // Check for CRLF sequence
            if self.pos < self.chars.len() && self.chars[self.pos] == '\n' {
                self.pos += 1;
                self.offset += 1; // '\n' is 1 byte
            }
            self.line += 1;
            self.col = 1;
        } else if ch == '\n' {
            self.line += 1;
            self.col = 1;
        } else {
            self.col += 1;
        }

        Some(ch)
    }

    /// Conditionally consumes the current character if it matches `expected`.
    #[inline]
    pub fn match_char(&mut self, expected: char) -> bool {
        if self.peek() == Some(expected) {
            self.advance();
            true
        } else {
            false
        }
    }

    /// Matches and consumes the exact target string at cursor without heap allocations.
    pub fn match_str(&mut self, target: &str) -> bool {
        let target_len = target.chars().count();
        if self.pos + target_len > self.chars.len() {
            return false;
        }

        for (i, target_ch) in target.chars().enumerate() {
            if self.chars[self.pos + i] != target_ch {
                return false;
```

```
            }
        }

        for _ in 0..target_len {
            self.advance();
        }
        true
    }

    /// Repeatedly consumes characters while `predicate` returns `true`, accumulating them.
    pub fn consume_while<F: Fn(char) -> bool>(&mut self, predicate: F) -> String {
        let mut result = String::new();
        while let Some(ch) = self.peek() {
            if predicate(ch) {
                result.push(ch);
                self.advance();
            } else {
                break;
            }
        }
        result
    }

    /// Consumes contiguous whitespace characters (spaces, tabs, newlines).
    pub fn skip_whitespace(&mut self) {
        while let Some(ch) = self.peek() {
            if ch.is_whitespace() {
                self.advance();
            } else {
                break;
            }
        }
    }

    /// Consumes a single-line comment initiated by `comment_char` up to the next newline.
    pub fn skip_line_comment(&mut self, comment_char: char) -> bool {
        if self.peek() == Some(comment_char) {
            while let Some(ch) = self.peek() {
                if ch == '\n' || ch == '\r' {
                    break;
                }
                self.advance();
            }
            true
        } else {
            false
        }
    }

    /// Universally consumes whitespace and comments starting with `comment_char`.
    pub fn skip_whitespace_and_comments(&mut self, comment_char: char) {
        loop {
            self.skip_whitespace();
            if !self.skip_line_comment(comment_char) {
                break;
            }
        }
    }
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Universal Character Stream Verification Proofs & Traversal Oracles )
// ============================================================================
#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_stream_linear_navigation_and_crlf() {
        let mut cursor = CharCursor::new("A\r\nB\nC");
        assert_eq!(cursor.line(), 1);
        assert_eq!(cursor.col(), 1);

        assert_eq!(cursor.advance(), Some('A'));
        assert_eq!(cursor.line(), 1);
        assert_eq!(cursor.col(), 2);
```

```
308
309         // CRLF normalized advance
310         assert_eq!(cursor.advance(), Some('\r'));
311         assert_eq!(cursor.line(), 2);
312         assert_eq!(cursor.col(), 1);
313
314         assert_eq!(cursor.advance(), Some('B'));
315         assert_eq!(cursor.advance(), Some('\n'));
316         assert_eq!(cursor.line(), 3);
317         assert_eq!(cursor.col(), 1);
318
319         assert_eq!(cursor.advance(), Some('C'));
320         assert_eq!(cursor.advance(), None);
321         assert!(cursor.is_at_end());
322     }
323
324     #[test]
325     fn test_zero_allocation_match_str() {
326         let mut cursor = CharCursor::new("--> INSCRIBE");
327         assert!(cursor.match_str("-->"));
328         assert_eq!(cursor.col(), 4);
329
330         cursor.skip_whitespace();
331         assert!(cursor.match_str("INSCRIBE"));
332         assert!(cursor.is_at_end());
333     }
334
335     #[test]
336     fn test_checkpoint_and_backtracking() {
337         let mut cursor = CharCursor::new("Character` <= [ 1 ]");
338         let cp = cursor.checkpoint();
339
340         let ident = cursor.consume_while(|c| c.is_alphanumeric() || c == '`');
341         assert_eq!(ident, "Character`");
342
343         // Rollback to origin
344         cursor.restore(cp);
345         assert_eq!(cursor.line(), 1);
346         assert_eq!(cursor.col(), 1);
347         assert_eq!(cursor.peek(), Some('C'));
348     }
349
350     #[test]
351     fn test_whitespace_and_line_comments() {
352         let mut cursor = CharCursor::new("   # This is a comment\n42");
353         cursor.skip_whitespace_and_comments('#');
354         assert_eq!(cursor.peek(), Some('4'));
355         assert_eq!(cursor.line(), 2);
356     }
357 }
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/universal/cursor.rs RS 324 LINES 1248 WORDS 12.6 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal Token Cursor: Stream Navigation, Lookahead & Failpoint Guards )
// ================================================================================
// SCRIPTURE ANCHORS & EPISTEMIC WITNESSES:
//   - Exodus 31:18: "written with the finger of God" — Inscription of eternal truth.
//   - Proverbs 24:27: "Prepare thy work without, and make it fit for thyself in the field;
//                      and afterwards build thine house." — Systematic modularization.
//   - Proverbs 22:28: "Remove not the ancient landmark, which thy fathers have set."
//                      — Preservation of invariant boundaries and balanced truth.
//
// ARCHITECTURAL TOPOLOGY:
//   The TokenCursor isolates universal token stream traversal from grammar-specific
//   parsing rules. It models the lexical stream as a discrete, 1-dimensional causal
//   ribbon with deterministic cursor navigation, arbitrary lookahead, and failpoint
//   reporting via the diagnostic debugger.
// ================================================================================

use crate::diagnostics::debugger::OmniDebugger;
use crate::diagnostics::logger::FailpointType;
use crate::parser::lexer::{Token, TokenType};

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Cursor State Initialization, Stream Context & Encapsulation )
// ================================================================================

/// Universal stream cursor managing position, lookahead, and delimiter integrity.
pub struct TokenCursor {
    /// Ingested token stream terminated by [`TokenType::Eof`].
    tokens: Vec<Token>,
    /// Current 0-based token index.
    pos: usize,
    /// Diagnostic debugger tracking boundary depth and failpoint telemetry.
    pub debugger: OmniDebugger,
}

impl TokenCursor {
    /// Constructs a new [`TokenCursor`] over a linear token sequence.
    ///
    /// # Arguments
    /// * `tokens` - Ingested token stream from the Lexer.
    /// * `debugger` - Diagnostic debugger enforcing failpoints and boundary invariants.
    pub fn new(tokens: Vec<Token>, debugger: OmniDebugger) -> Self {
        Self {
            tokens,
            pos: 0,
            debugger,
        }
    }

    /// Returns the current 0-based cursor position.
    #[inline]
    pub fn pos(&self) -> usize {
        self.pos
    }

    /// Explicitly sets the cursor position (used during backtracking or macro replay).
    #[inline]
    pub fn set_pos(&mut self, new_pos: usize) {
        self.pos = new_pos.min(self.tokens.len().saturating_sub(1));
    }

    /// Returns the total number of tokens in the stream.
    #[inline]
    pub fn len(&self) -> usize {
        self.tokens.len()
    }

    /// Returns true if the token stream contains no tokens.
    #[inline]
    pub fn is_empty(&self) -> bool {
        self.tokens.is_empty()
    }
```

```rust

    /// Returns the remaining token count from the current cursor position.
    #[inline]
    pub fn remaining(&self) -> usize {
        self.tokens.len().saturating_sub(self.pos)
    }

    /// Returns a slice of the underlying token stream.
    #[inline]
    pub fn tokens(&self) -> &[Token] {
        &self.tokens
    }
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Universal Cursor Primitives: Inspection, Advancement, Matching & Expectation )
// ============================================================================

impl TokenCursor {
    // ------------------------------------------------------------------------
    // 1. UNIVERSAL INSPECTION (PURE LOOKAHEAD, ZERO SIDE-EFFECTS)
    // ------------------------------------------------------------------------

    /// Inspects the current token at the cursor without advancing.
    /// Returns the final EOF token if the cursor has exceeded the stream boundary.
    #[inline]
    pub fn peek(&self) -> &Token {
        if self.pos < self.tokens.len() {
            &self.tokens[self.pos]
        } else {
            self.tokens.last().expect("Token stream must have at least an EOF token")
        }
    }

    /// Inspects a future token at `offset` positions ahead of the cursor.
    #[inline]
    pub fn peek_at(&self, offset: usize) -> &Token {
        let target_idx = self.pos + offset;
        if target_idx < self.tokens.len() {
            &self.tokens[target_idx]
        } else {
            self.tokens.last().expect("Token stream must have at least an EOF token")
        }
    }

    /// Checks if the current token matches the expected token type without consuming it.
    #[inline]
    pub fn check(&self, expected: &TokenType) -> bool {
        &self.peek().token_type == expected
    }

    /// Checks if a lookahead token at `offset` matches the expected token type.
    #[inline]
    pub fn check_at(&self, offset: usize, expected: &TokenType) -> bool {
        &self.peek_at(offset).token_type == expected
    }

    /// Checks whether the cursor has reached the end-of-file token or stream termination.
    #[inline]
    pub fn is_at_end(&self) -> bool {
        self.check(&TokenType::Eof) || self.pos >= self.tokens.len()
    }

    /// Returns the (line, col) coordinates of the current token.
    #[inline]
    pub fn current_location(&self) -> (usize, usize) {
        let tok = self.peek();
        (tok.line, tok.col)
    }

    // ------------------------------------------------------------------------
    // 2. UNIVERSAL ADVANCEMENT & CONSUMPTION (STATE ADVANCEMENT)
    // ------------------------------------------------------------------------

    /// Advances the cursor by one token and returns the consumed token.
    #[inline]
    pub fn advance(&mut self) -> Token {
```

```
        let tok = self.peek().clone();
        if self.pos < self.tokens.len() {
            self.pos += 1;
        }
        tok
    }

    /// Conditionally consumes the current token if it matches `expected`.
    pub fn match_token(&mut self, expected: &TokenType) -> bool {
        if self.check(expected) {
            self.advance();
            true
        } else {
            false
        }
    }

    /// Consumes the current token if the predicate returns true.
    pub fn consume_if<F: FnOnce(&TokenType) -> bool>(&mut self, predicate: F) -> Option<Token> {
        if predicate(&self.peek().token_type) {
            Some(self.advance())
        } else {
            None
        }
    }

    // ---------------------------------------------------------------------------
    // 3. UNIVERSAL EXPECTATION & FAILPOINT GUARDS
    // ---------------------------------------------------------------------------

    /// Asserts that the current token matches `expected`, consuming it on match
    /// or emitting a structured syntax failpoint on mismatch.
    pub fn expect(&mut self, expected: &TokenType, context: &str) -> Result<Token, String> {
        let current = self.peek();
        if &current.token_type == expected {
            Ok(self.advance())
        } else {
            let msg = format!(
                "Expected token '{:?}' in {}, found '{:?}' ('{}') at L{}:C{}",
                expected, context, current.token_type, current.lexeme, current.line, current.col
            );
            self.debugger.logger.failpoint(FailpointType::SyntaxAnomaly, "CURSOR", &msg);
            Err(format!("FAILPOINT: {msg}"))
        }
    }

    /// Asserts that the current token is an identifier, consuming and extracting its name.
    pub fn expect_identifier(&mut self, context: &str) -> Result<(String, Token), String> {
        let current = self.peek().clone();
        match current.token_type {
            TokenType::Identifier(ref name) => {
                let id = name.clone();
                let tok = self.advance();
                Ok((id, tok))
            }
            TokenType::Who | TokenType::What | TokenType::When | TokenType::Where | TokenType::Why | TokenType::How => {
                let id = current.lexeme.clone();
                let tok = self.advance();
                Ok((id, tok))
            }
            _ => {
                let msg = format!(
                    "Expected identifier in {}, found '{:?}' ('{}') at L{}:C{}",
                    context, current.token_type, current.lexeme, current.line, current.col
                );
                self.debugger.logger.failpoint(FailpointType::SyntaxAnomaly, "CURSOR", &msg);
                Err(format!("FAILPOINT: {msg}"))
            }
        }
    }

    /// Asserts that the current token opens a morphological boundary (`[`, `{`, `<`),
    /// recording it into the active boundary stack.
    pub fn expect_boundary_open(&mut self, context: &str) -> Result<(char, Token), String> {
        let tok = self.peek().clone();
        let open_char = match tok.token_type {
            TokenType::LBracket => '[',
            TokenType::LBrace => '{',
```

```
            TokenType::LAngle => '<',
            _ => {
                let msg = format!(
                    "Expected boundary opening delimiter ('[', '{{', '<') in {}, found '{:?}' at L{}:C{}",
                    context, tok.token_type, tok.line, tok.col
                );
                self.debugger.logger.failpoint(FailpointType::SyntaxAnomaly, "CURSOR", &msg);
                return Err(format!("FAILPOINT: {msg}"));
            }
        };

        self.advance();
        self.debugger.push_boundary(open_char, tok.line, tok.col);
        Ok((open_char, tok))
    }

    /// Asserts that the current token closes a morphological boundary (`]`, `}`, `>`),
    /// validating and popping it from the active boundary stack.
    pub fn expect_boundary_close(&mut self, context: &str) -> Result<(crate::core::boundaries::BoundaryType, Token),
String> {
        if self.is_at_end() {
            let msg = format!("Unclosed boundary in {} reaches EOF", context);
            self.debugger.logger.failpoint(FailpointType::BoundaryLeak, "CURSOR", &msg);
            return Err(format!("FAILPOINT: {msg}"));
        }

        let tok = self.peek().clone();
        let close_char = match tok.token_type {
            TokenType::RBracket => ']',
            TokenType::RBrace => '}',
            TokenType::RAngle => '>',
            _ => {
                let msg = format!(
                    "Expected boundary closing delimiter (']', '}}', '>') in {}, found '{:?}' at L{}:C{}",
                    context, tok.token_type, tok.line, tok.col
                );
                self.debugger.logger.failpoint(FailpointType::SyntaxAnomaly, "CURSOR", &msg);
                return Err(format!("FAILPOINT: {msg}"));
            }
        };

        self.advance();
        let btype = self.debugger.pop_boundary(close_char, tok.line, tok.col)?;
        Ok((btype, tok))
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Cursor Invariant Verification, Boundary Mechanics & Unit Proofs )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;
    use crate::diagnostics::logger::DiagnosticLogger;

    fn create_test_cursor(src: &str) -> TokenCursor {
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 10);
        let mut lexer = crate::parser::lexer::Lexer::new(src, logger);
        let tokens = lexer.tokenize().expect("Lexing must succeed");
        TokenCursor::new(tokens, debugger)
    }

    #[test]
    fn test_cursor_linear_advance_and_peek() {
        let mut cursor = create_test_cursor("[ Roll ] --> 42");
        assert_eq!(cursor.peek().token_type, TokenType::LBracket);
        assert_eq!(cursor.peek_at(1).lexeme, "Roll");
        assert_eq!(cursor.advance().token_type, TokenType::LBracket);
        assert_eq!(cursor.peek().lexeme, "Roll");
        assert!(cursor.match_token(&TokenType::Identifier("Roll".into())));
        assert_eq!(cursor.peek().token_type, TokenType::RBracket);
    }

    #[test]
    fn test_cursor_boundary_open_and_close_physics() {
```

```
        let mut cursor = create_test_cursor("{ Character ]");
        let (open_char, _) = cursor.expect_boundary_open("TestBoundary").expect("Open boundary");
        assert_eq!(open_char, '{');
        assert_eq!(cursor.advance().lexeme, "Character");
        let (btype, _) = cursor.expect_boundary_close("TestBoundary").expect("Close boundary");
        assert_eq!(btype, crate::core::boundaries::BoundaryType::TopDown);
    }

    #[test]
    fn test_cursor_safe_lookahead_past_eof() {
        let cursor = create_test_cursor("Alpha");
        assert_eq!(cursor.peek().lexeme, "Alpha");
        assert_eq!(cursor.peek_at(1).token_type, TokenType::Eof);
        assert_eq!(cursor.peek_at(100).token_type, TokenType::Eof);
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/universal/mod.rs RS 20 LINES 95 WORDS 0.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal Stream Navigation Subsystem Identity & Exports )
// ============================================================================
//! # Universal Stream & Navigation Machinery
//!
//! Provides pure, language-agnostic character-reel and token-stream cursors with
//! arbitrary lookahead, coordinate tracking, and speculative checkpointing.
//!
//! ## Scriptural Grounding:
//! - **Exodus 31:18**: Inscription of truth on physical reels.
//! - **Proverbs 24:27**: Preparing the raw stream in the field before assembly.
//! - **Proverbs 22:28**: Preserving stream landmarks and boundary coordinates.

pub mod char_stream;
pub mod cursor;

pub use char_stream::{CharCheckpoint, CharCursor};
pub use cursor::TokenCursor;
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/syntactic/grammar.rs RS 599 LINES 1985 WORDS 24.3 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( OmniCode Morphological Grammar: Precedence Cascade & Dual-Vector Physics )
// ============================================================================
// SCRIPTURE ANCHORS & EPISTEMIC WITNESSES:
//   - Exodus 31:18: "written with the finger of God" — Inscription of eternal truth.
//   - Proverbs 24:27: "Prepare thy work without, and make it fit for thyself in the field;
//                      and afterwards build thine house." — Systematic modularization.
//   - Proverbs 22:28: "Remove not the ancient landmark, which thy fathers have set."
//                      — Preservation of invariant boundaries and balanced truth.
//
// DUAL-VECTOR ARCHITECTURE:
//   1. FLOW DOWN (Decomposition / Macrocosm to Microcosm):
//      Program -> Statement -> Caveat/Connective (L1) -> Directional (L2) ->
//      Relation (L3) -> Arithmetic (L4) -> Unary (L5) -> Primary (L6).
//
//   2. FLOW BACK UP (Synthesis / Inscription & Folding):
//      Primary atoms fold upward into binary relations, directional flows,
//      and first-class intent asides `( ... )`, anchoring into complete rolls.
// ============================================================================

use crate::ast::nodes::*;
use crate::core::operators::{BeingRelation, Connective, DirectionalVector};
use crate::parser::cursor::TokenCursor;
use crate::parser::lexer::TokenType;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Grammar Engine Context & State Mounting )
// ============================================================================

/// Grammar engine driving recursive-descent parsing over a [`TokenCursor`].
pub struct GrammarEngine<'a> {
    /// Active token stream cursor providing lookahead and expectation guards.
    pub cursor: &'a mut TokenCursor,
}

impl<'a> GrammarEngine<'a> {
    /// Constructs a new [`GrammarEngine`] mounted over a [`TokenCursor`].
    pub fn new(cursor: &'a mut TokenCursor) -> Self {
        Self { cursor }
    }
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Morphological Grammars: Statements, Boundaries, Downward & Upward Cascades )
// ============================================================================

impl<'a> GrammarEngine<'a> {
    // ------------------------------------------------------------------------
    // PART 3A: MACROCOSMIC PROGRAM & STATEMENT PARSING
    // ------------------------------------------------------------------------

    /// Parses an entire source reel or tape into a unified [`ProgramNode`].
    ///
    /// Iterates through sequential top-level statements until EOF, then proves
    /// that all opened boundary frames have been cleanly popped from the stack.
    pub fn parse_program(&mut self) -> Result<ProgramNode, String> {
        let mut statements = Vec::new();

        while !self.cursor.is_at_end() {
            let stmt = self.parse_statement()?;
            statements.push(stmt);
        }

        self.cursor.debugger.assert_all_boundaries_closed()?;
        Ok(ProgramNode { statements, line: 1, col: 1 })
    }

    /// Parses a single statement or top-level structural declaration.
    ///
    /// Recognizes:
    /// 1. Root assignment declarations: `= [Module]: ...` and `= [Tape]: ...`
```

```
    /// 2. Section blocks: `Opening { ... }`, `Body [ ... ]`, `Closing ( Aside ) { ... }`
    /// 3. Attached body blocks: `< Character > = ... ( Aside ) { ... }`
    /// 4. Expressions, entities, and directional transitions.
    pub fn parse_statement(&mut self) -> Result<ASTNode, String> {
        // 1. Handle optional leading '=' for root module or tape declarations:
        if self.cursor.check(&TokenType::Is) {
            let eq_tok = self.cursor.advance();
            let expr = self.parse_expression()?;

            // Check if immediately followed by an attached body boundary block
            if matches!(self.cursor.peek().token_type, TokenType::LBrace | TokenType::LBracket) {
                let body_boundary = self.parse_boundary()?;
                return Ok(ASTNode::Connective(ConnectiveNode {
                    left: Box::new(expr),
                    connective: Connective::InRelationTo,
                    right: Box::new(ASTNode::Boundary(body_boundary)),
                    line: eq_tok.line,
                    col: eq_tok.col,
                }));
            }

            return Ok(expr);
        }

        // 2. Parse base expression
        let expr = self.parse_expression()?;

        // 3. Flow Back Up: Attach optional trailing Aside and Contextual/Denotational block
        let maybe_aside = if let TokenType::Aside(ref text) = self.cursor.peek().token_type {
            Some(text.clone())
        } else {
            None
        };

        if let Some(aside_text) = maybe_aside {
            if matches!(self.cursor.peek_at(1).token_type, TokenType::LBrace | TokenType::LBracket) {
                let a_tok = self.cursor.advance(); // consume Aside
                let mut body_block = self.parse_boundary()?;
                if body_block.aside.is_none() {
                    body_block.aside = Some(AsideNode {
                        intent: aside_text,
                        line: a_tok.line,
                        col: a_tok.col,
                    });
                }
                return Ok(ASTNode::Connective(ConnectiveNode {
                    left: Box::new(expr),
                    connective: Connective::InRelationTo,
                    right: Box::new(ASTNode::Boundary(body_block)),
                    line: a_tok.line,
                    col: a_tok.col,
                }));
            }
        }

        // Check if directly followed by an attached body boundary block without aside
        if matches!(self.cursor.peek().token_type, TokenType::LBrace | TokenType::LBracket) {
            let body_block = self.parse_boundary()?;
            return Ok(ASTNode::Connective(ConnectiveNode {
                left: Box::new(expr),
                connective: Connective::InRelationTo,
                right: Box::new(ASTNode::Boundary(body_block)),
                line: self.cursor.peek().line,
                col: self.cursor.peek().col,
            }));
        }

        Ok(expr)
    }

    // ---------------------------------------------------------------------------
    // PART 3B: MORPHOLOGICAL BOUNDARY ENGINE (THE 6 BOUNDARY RANKS)
    // ---------------------------------------------------------------------------

    /// Parses a morphological boundary block, enforcing boundary stack physics:
    ///   - Rank 1: Invariant Axiom       `< ... >`
    ///   - Rank 2: Denotation            `[ ... ]`
    ///   - Rank 3: Connotation           `{ ... }`
```

```
    ///   - Rank 4: Inside-Out Emergence  `[ ... }`
    ///   - Rank 5: Outside-In Imposition `{ ... ]`
    ///   - Rank 6: Intent Aside          `( ... )`
    pub fn parse_boundary(&mut self) -> Result<BoundaryNode, String> {
        let (_open_char, open_tok) = self.cursor.expect_boundary_open("BoundaryBlock")?;
        let mut elements = Vec::new();

        while !self.cursor.is_at_end() && !matches!(
            self.cursor.peek().token_type,
            TokenType::RBracket | TokenType::RBrace | TokenType::RAngle
        ) {
            let el = self.parse_expression()?;
            elements.push(el);
        }

        let (btype, _close_tok) = self.cursor.expect_boundary_close("BoundaryBlock")?;

        // Flow Back Up: Check for attached first-class Aside: ( ... )
        let mut aside = None;
        let maybe_aside = if let TokenType::Aside(ref text) = self.cursor.peek().token_type {
            Some(text.clone())
        } else {
            None
        };
        if let Some(text) = maybe_aside {
            let a_tok = self.cursor.advance();
            aside = Some(AsideNode {
                intent: text,
                line: a_tok.line,
                col: a_tok.col,
            });
        }

        Ok(BoundaryNode {
            boundary_type: btype,
            elements,
            aside,
            line: open_tok.line,
            col: open_tok.col,
        })
    }

    // ---------------------------------------------------------------------------
    // PART 3C: DOWNWARD PRECEDENCE CASCADE (FLOW DOWN)
    // ---------------------------------------------------------------------------

    /// Entry point for expression hierarchy parsing.
    #[inline]
    pub fn parse_expression(&mut self) -> Result<ASTNode, String> {
        self.parse_caveat_or_connective()
    }

    /// Precedence Level 1: Adversative Caveat `!` (BUT / Guard Interlock)
    /// and Connectives `::` / `&` (And), `|` (Or), `:` / `@` / `::@` (In Relation To / Located At).
    pub fn parse_caveat_or_connective(&mut self) -> Result<ASTNode, String> {
        let mut expr = self.parse_directional()?;

        while matches!(
            self.cursor.peek().token_type,
            TokenType::But | TokenType::And | TokenType::HardwareLocator | TokenType::Or | TokenType::InRelationTo |
TokenType::BoundPair | TokenType::At
        ) {
            let op_tok = self.cursor.advance();
            let connective = match op_tok.token_type {
                TokenType::But => Connective::But,
                TokenType::And | TokenType::BoundPair | TokenType::HardwareLocator => Connective::And,
                TokenType::Or => Connective::Or,
                TokenType::InRelationTo | TokenType::At => Connective::InRelationTo,
                _ => unreachable!(),
            };
            let right = self.parse_directional()?;
            expr = ASTNode::Connective(ConnectiveNode {
                left: Box::new(expr),
                connective,
                right: Box::new(right),
                line: op_tok.line,
                col: op_tok.col,
            });
```

```
        }

        Ok(expr)
    }

    /// Precedence Level 2: Directional Vectors across X, Y, and Z axes:
    ///   `-->` (ActUpon), `<--` (ActAgain), `^--` (BuildsTo), `v--` (BreaksDownFrom),
    ///   as well as scale modulations and quadrant vectors.
    pub fn parse_directional(&mut self) -> Result<ASTNode, String> {
        let mut expr = self.parse_relation()?;

        while matches!(
            self.cursor.peek().token_type,
            TokenType::ActUpon
                | TokenType::ActAgain
                | TokenType::BuildsTo
                | TokenType::BreaksDownFrom
                | TokenType::Major
                | TokenType::Minor
                | TokenType::Great
                | TokenType::Small
                | TokenType::UpperRight
                | TokenType::LowerRight
                | TokenType::UpperLeft
                | TokenType::LowerLeft
        ) {
            let op_tok = self.cursor.advance();
            let vector = match op_tok.token_type {
                TokenType::ActUpon => DirectionalVector::ActUpon,
                TokenType::ActAgain => DirectionalVector::ActAgain,
                TokenType::BuildsTo => DirectionalVector::BuildsTo,
                TokenType::BreaksDownFrom => DirectionalVector::BreaksDownFrom,
                TokenType::Major => DirectionalVector::Major,
                TokenType::Minor => DirectionalVector::Minor,
                TokenType::Great => DirectionalVector::Great,
                TokenType::Small => DirectionalVector::Small,
                TokenType::UpperRight => DirectionalVector::UpperRight,
                TokenType::LowerRight => DirectionalVector::LowerRight,
                TokenType::UpperLeft => DirectionalVector::UpperLeft,
                TokenType::LowerLeft => DirectionalVector::LowerLeft,
                _ => unreachable!(),
            };
            let target = self.parse_relation()?;
            expr = ASTNode::Directional(DirectionalNode {
                source: Box::new(expr),
                vector,
                target: Box::new(target),
                line: op_tok.line,
                col: op_tok.col,
            });
        }

        Ok(expr)
    }

    /// Precedence Level 3: Being Relations and Invariant Equivalence:
    ///   `=` (Is), `!=` (IsNot), `~=` (ToBeLike), `<=>` (InvariantEquivalence / Transduction),
    ///   `<`, `>`, `<=`, `>=` (Relational Bound Comparisons).
    pub fn parse_relation(&mut self) -> Result<ASTNode, String> {
        let mut expr = self.parse_arithmetic()?;

        while matches!(
            self.cursor.peek().token_type,
            TokenType::Is
                | TokenType::IsNot
                | TokenType::ToBeNot
                | TokenType::ToBeLike
                | TokenType::InvariantEquivalence
                | TokenType::LessThan
                | TokenType::GreaterThan
                | TokenType::LessEqual
                | TokenType::GreaterEqual
        ) {
            let op_tok = self.cursor.advance();
            let relation = match op_tok.token_type {
                TokenType::Is => BeingRelation::Is,
                TokenType::IsNot => BeingRelation::IsNot,
                TokenType::ToBeNot => BeingRelation::ToBeNot,
```

```
                TokenType::ToBeLike => BeingRelation::ToBeLike,
                TokenType::InvariantEquivalence => BeingRelation::Equivalence,
                TokenType::LessThan => BeingRelation::LessThan,
                TokenType::GreaterThan => BeingRelation::GreaterThan,
                TokenType::LessEqual => BeingRelation::LessEqual,
                TokenType::GreaterEqual => BeingRelation::GreaterEqual,
                _ => unreachable!(),
            };
            let right = self.parse_arithmetic()?;
            expr = ASTNode::Relation(RelationNode {
                left: Box::new(expr),
                relation,
                right: Box::new(right),
                line: op_tok.line,
                col: op_tok.col,
            });
        }

        Ok(expr)
    }

    /// Precedence Level 4: SVO Arithmetic Math Keywords:
    ///   `plus`, `minus`, `times`, `div`.
    pub fn parse_arithmetic(&mut self) -> Result<ASTNode, String> {
        let mut expr = self.parse_unary()?;

        while matches!(
            self.cursor.peek().token_type,
            TokenType::Plus | TokenType::Minus | TokenType::Times | TokenType::Div
        ) {
            let op_tok = self.cursor.advance();
            let op = match op_tok.token_type {
                TokenType::Plus => ArithmeticOp::Add,
                TokenType::Minus => ArithmeticOp::Sub,
                TokenType::Times => ArithmeticOp::Mul,
                TokenType::Div => ArithmeticOp::Div,
                _ => unreachable!(),
            };
            let right = self.parse_unary()?;
            expr = ASTNode::Arithmetic(ArithmeticNode {
                left: Box::new(expr),
                op,
                right: Box::new(right),
                line: op_tok.line,
                col: op_tok.col,
            });
        }

        Ok(expr)
    }

    /// Precedence Level 5: Unary Operations:
    ///   `--` (Not) and Prefix Vectors (`-->`, `<--`, `^--`, `v--`).
    pub fn parse_unary(&mut self) -> Result<ASTNode, String> {
        if self.cursor.check(&TokenType::Not) {
            let op_tok = self.cursor.advance();
            let operand = self.parse_unary()?;
            return Ok(ASTNode::UnaryNot(UnaryNotNode {
                operand: Box::new(operand),
                line: op_tok.line,
                col: op_tok.col,
            }));
        }

        if matches!(
            self.cursor.peek().token_type,
            TokenType::ActAgain | TokenType::ActUpon | TokenType::BuildsTo | TokenType::BreaksDownFrom
        ) {
            let op_tok = self.cursor.advance();
            let vector = match op_tok.token_type {
                TokenType::ActAgain => DirectionalVector::ActAgain,
                TokenType::ActUpon => DirectionalVector::ActUpon,
                TokenType::BuildsTo => DirectionalVector::BuildsTo,
                TokenType::BreaksDownFrom => DirectionalVector::BreaksDownFrom,
                _ => unreachable!(),
            };
            let operand = self.parse_unary()?;
            return Ok(ASTNode::Directional(DirectionalNode {
```

```
                source: Box::new(ASTNode::Ternary(crate::core::ternary::QuadState::Proceed)),
                vector,
                target: Box::new(operand),
                line: op_tok.line,
                col: op_tok.col,
            }));
        }

        self.parse_primary()
    }

    // ------------------------------------------------------------------------
    // PART 3D: UPWARD INSCRIPTION & SYNTHESIS (FLOW BACK UP)
    // ------------------------------------------------------------------------

    /// Precedence Level 6: Primaries & Atom Synthesis:
    ///   Morphological Boundaries, Affixed Polarities, Boundary Casts, Asides,
    ///   Ternary Literals, Numbers, Strings, Identifiers (with state-primes `),
    ///   and Complex Entities with Definitions, Asides, and Contexts.
    pub fn parse_primary(&mut self) -> Result<ASTNode, String> {
        let tok = self.cursor.peek().clone();
        match tok.token_type {
            TokenType::LBracket | TokenType::LBrace | TokenType::LAngle => {
                let b = self.parse_boundary()?;
                Ok(ASTNode::Boundary(b))
            }
            TokenType::AffixedIdent { ref name, polarity, position } => {
                let id_name = name.clone();
                let line = tok.line;
                let col = tok.col;
                self.cursor.advance();
                Ok(ASTNode::Polarity(PolarityNode {
                    name: id_name,
                    polarity,
                    position,
                    line,
                    col,
                }))
            }
            TokenType::BoundaryCast { boundary, polarity } => {
                let line = tok.line;
                let col = tok.col;
                self.cursor.advance();
                Ok(ASTNode::BoundaryCast(BoundaryCastNode {
                    boundary,
                    polarity,
                    line,
                    col,
                }))
            }
            TokenType::Aside(ref intent) => {
                self.cursor.advance();
                Ok(ASTNode::Aside(AsideNode {
                    intent: intent.clone(),
                    line: tok.line,
                    col: tok.col,
                }))
            }
            TokenType::Ternary(state) => {
                self.cursor.advance();
                Ok(ASTNode::Ternary(state))
            }
            TokenType::Number(val) => {
                self.cursor.advance();
                Ok(ASTNode::Number(val))
            }
            TokenType::StringLit(ref s) => {
                self.cursor.advance();
                Ok(ASTNode::StringLit(s.clone()))
            }
            TokenType::CharLit(c) => {
                let s = c.to_string();
                self.cursor.advance();
                Ok(ASTNode::StringLit(s))
            }
            TokenType::Infer => {
                self.cursor.advance();
                Ok(ASTNode::Identifier("?".into()))
```

```
            }
            TokenType::Pronoun(ref p) => {
                let name = p.as_str().to_string();
                self.cursor.advance();
                Ok(ASTNode::Identifier(name))
            }
            TokenType::Identifier(_)
            | TokenType::Who
            | TokenType::What
            | TokenType::When
            | TokenType::Where
            | TokenType::Why
            | TokenType::How => {
                let id_str = match tok.token_type {
                    TokenType::Identifier(ref n) => n.clone(),
                    _ => tok.lexeme.clone(),
                };
                let next_tok = self.cursor.peek_at(1).token_type.clone();

                // 1. Entity Syntax: Name [ Definition ] ( Aside ) { Context }
                if matches!(next_tok, TokenType::LBracket | TokenType::LAngle | TokenType::LBrace) {
                    let id_name = id_str;
                    let line = tok.line;
                    let col = tok.col;
                    self.cursor.advance(); // consume identifier

                    let def_node = self.parse_boundary()?;
                    let mut aside_node = None;
                    let mut context_node = None;

                    // Check for optional Aside: ( ... )
                    let maybe_aside = if let TokenType::Aside(ref text) = self.cursor.peek().token_type {
                        Some(text.clone())
                    } else {
                        None
                    };
                    if let Some(text) = maybe_aside {
                        let a_tok = self.cursor.advance();
                        aside_node = Some(AsideNode {
                            intent: text,
                            line: a_tok.line,
                            col: a_tok.col,
                        });
                    }

                    // Check for optional Context boundary
                    if matches!(self.cursor.peek().token_type, TokenType::LBrace | TokenType::LBracket) {
                        context_node = Some(self.parse_boundary()?);
                    }

                    if def_node.boundary_type.is_immutable() {
                        self.cursor.debugger.register_immutable(&id_name);
                    }

                    return Ok(ASTNode::Entity(EntityNode {
                        name: id_name,
                        definition: def_node,
                        aside: aside_node,
                        context: context_node,
                        line,
                        col,
                    }));
                }

                // 2. Entity Syntax: Name ( Aside ) { Context }
                if let TokenType::Aside(ref text) = next_tok {
                    if matches!(self.cursor.peek_at(2).token_type, TokenType::LBrace | TokenType::LBracket |
TokenType::LAngle) {
                        let id_name = id_str;
                        let line = tok.line;
                        let col = tok.col;
                        let aside_text = text.clone();
                        self.cursor.advance(); // consume identifier
                        let a_tok = self.cursor.advance(); // consume aside
                        let def_node = self.parse_boundary()?;

                        return Ok(ASTNode::Entity(EntityNode {
                            name: id_name,
```

```
                            definition: def_node,
                            aside: Some(AsideNode {
                                intent: aside_text,
                                line: a_tok.line,
                                col: a_tok.col,
                            }),
                            context: None,
                            line,
                            col,
                        }));
                    }
                }

                self.cursor.advance();
                Ok(ASTNode::Identifier(id_str))
            }
            _ => {
                let msg = format!("Unexpected token '{:?}' in expression at L{}:C{}", tok.token_type, tok.line, tok.col);
                self.cursor.debugger.logger.failpoint(crate::diagnostics::logger::FailpointType::SyntaxAnomaly,
"GRAMMAR", &msg);
                Err(format!("FAILPOINT: {msg}"))
            }
        }
    }
}

// ==============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Grammar Verification, Boundary Integrity Proofs & Unit Tests )
// ==============================================================================

#[cfg(test)]
mod tests {
    use super::*;
    use crate::diagnostics::debugger::OmniDebugger;
    use crate::diagnostics::logger::DiagnosticLogger;

    fn parse_src(src: &str) -> Result<ProgramNode, String> {
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 10);
        let mut lexer = crate::parser::lexer::Lexer::new(src, logger);
        let tokens = lexer.tokenize().expect("Lexing must succeed");
        let mut cursor = TokenCursor::new(tokens, debugger);
        let mut engine = GrammarEngine::new(&mut cursor);
        engine.parse_program()
    }

    #[test]
    fn test_grammar_precedence_downward_and_upward() {
        let prog = parse_src("1 plus 2 times 3 <=> 7").expect("Parse expression");
        assert_eq!(prog.statements.len(), 1);
    }

    #[test]
    fn test_grammar_directional_and_connective() {
        let prog = parse_src("{ Inflow ] --> INSCRIBE [ Cell ] = [ Character` ]").expect("Parse inscribe roll");
        assert_eq!(prog.statements.len(), 1);
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/syntactic/mod.rs RS 20 LINES 93 WORDS 0.8 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Syntactic Grammar & Parser Subsystem )
// ================================================================================
//! # Syntactic Grammar & Parser Subsystem
//!
//! Builds the Abstract Syntax Tree (AST) by enforcing the 6 ranked morphological
//! boundaries and the 6-level dual-vector precedence cascade.
//!
//! ## Scriptural Grounding:
//! - **Exodus 31:18**: Building upon the inscribed tables of stone.
//! - **Proverbs 24:27**: Building the architectural house upon prepared tokens.
//! - **Proverbs 22:28**: Enforcing unalterable morphological boundaries.

pub mod grammar;
pub mod parser;

pub use grammar::GrammarEngine;
pub use parser::Parser;
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/syntactic/parser.rs RS 203 LINES 935 WORDS 8.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( OmniCode Parser Coordinator: Grammar Engine & Token Stream Facade )
// ============================================================================
// SCRIPTURE ANCHORS & EPISTEMIC WITNESSES:
//   - Exodus 31:18: "written with the finger of God" — Inscription of eternal truth.
//   - Proverbs 24:27: "Prepare thy work without, and make it fit for thyself in the field;
//                      and afterwards build thine house." — Systematic modularization.
//   - Proverbs 22:28: "Remove not the ancient landmark, which thy fathers have set."
//                      — Preservation of invariant boundaries and balanced truth.
//
// ARCHITECTURAL DESIGN:
//   The Parser acts as the public coordinator unifying:
//     1. Universal TokenCursor (Stream navigation, lookahead & expectation guards).
//     2. Morphological GrammarEngine (Boundary physics & dual-vector precedence cascade).
//     3. Diagnostic Debugger (Boundary frame tracking & failpoint telemetry).
// ============================================================================

use crate::ast::nodes::*;
use crate::diagnostics::debugger::OmniDebugger;
use crate::parser::cursor::TokenCursor;
use crate::parser::grammar::GrammarEngine;
use crate::parser::lexer::{Token, TokenType};

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Parser State Initialization, Token Stream Mounting & Stream Delegations )
// ============================================================================

/// State container coordinating recursive-descent parsing across modular engines.
pub struct Parser {
    /// Universal stream cursor managing position, lookahead, and delimiter integrity.
    pub cursor: TokenCursor,
    /// Active debugger reflecting boundary stack physics and diagnostic failpoints.
    pub debugger: OmniDebugger,
}

impl Parser {
    /// Constructs a new [`Parser`] over an ingested token stream.
    ///
    /// # Arguments
    /// * `tokens` - Complete token stream terminated by [`TokenType::Eof`].
    /// * `debugger` - Diagnostic debugger enforcing delimiter integrity.
    pub fn new(tokens: Vec<Token>, debugger: OmniDebugger) -> Self {
        let cursor = TokenCursor::new(tokens, debugger.clone());
        Self {
            cursor,
            debugger,
        }
    }

    /// Inspects the current token at the cursor without advancing.
    #[inline]
    pub fn peek(&self) -> &Token {
        self.cursor.peek()
    }

    /// Inspects a future token at `offset` positions ahead of the cursor.
    #[inline]
    pub fn peek_at(&self, offset: usize) -> &Token {
        self.cursor.peek_at(offset)
    }

    /// Advances the cursor by one token and returns the consumed token.
    #[inline]
    pub fn advance(&mut self) -> Token {
        self.cursor.advance()
    }

    /// Checks if the current token matches the expected token type without consuming it.
    #[inline]
    pub fn check(&self, expected: &TokenType) -> bool {
        self.cursor.check(expected)
    }
```

```
    /// Checks if a lookahead token at `offset` matches the expected token type.
    #[inline]
    pub fn check_at(&self, offset: usize, expected: &TokenType) -> bool {
        self.cursor.check_at(offset, expected)
    }

    /// Conditionally consumes the current token if it matches the expected type.
    #[inline]
    pub fn match_token(&mut self, expected: &TokenType) -> bool {
        self.cursor.match_token(expected)
    }

    /// Returns `true` if the cursor has reached the end-of-file token.
    #[inline]
    pub fn is_at_end(&self) -> bool {
        self.cursor.is_at_end()
    }
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Grammar Coordination: Program, Statements & Expressions )
// ============================================================================

impl Parser {
    /// Parses an entire source reel or tape into a unified [`ProgramNode`].
    ///
    /// Iterates through sequential top-level statements until [`TokenType::Eof`],
    /// synchronizes debugger state, and verifies that all opened boundaries closed cleanly.
    pub fn parse_program(&mut self) -> Result<ProgramNode, String> {
        let mut engine = GrammarEngine::new(&mut self.cursor);
        let res = engine.parse_program();
        self.debugger = self.cursor.debugger.clone();
        res
    }

    /// Parses a single statement or top-level structural declaration.
    pub fn parse_statement(&mut self) -> Result<ASTNode, String> {
        let mut engine = GrammarEngine::new(&mut self.cursor);
        let res = engine.parse_statement();
        self.debugger = self.cursor.debugger.clone();
        res
    }

    /// Entry point for expression hierarchy parsing.
    pub fn parse_expression(&mut self) -> Result<ASTNode, String> {
        let mut engine = GrammarEngine::new(&mut self.cursor);
        let res = engine.parse_expression();
        self.debugger = self.cursor.debugger.clone();
        res
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Parsing Invariant Verification, Boundary Integrity Proofs & Test Oracles )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;
    use crate::diagnostics::logger::DiagnosticLogger;

    #[test]
    fn test_parser_leading_equals_module_declaration() {
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 5);
        let src = "= [Module]: < Lexicon { Types } > & [ Noun { Character } ] { [ Version ]: { \"1.0.0\" } }";
        let mut lexer = crate::parser::lexer::Lexer::new(src, logger);
        let tokens = lexer.tokenize().expect("Lexing must succeed");
        let mut parser = Parser::new(tokens, debugger);
        let prog = parser.parse_program();
        assert!(prog.is_ok(), "Module declaration starting with '=' must parse cleanly: {:?}", prog.err());
    }

    #[test]
    fn test_parser_ranked_asymmetric_boundaries() {
```

```
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 5);
        let src = "{ Input ] --> [ Output }";
        let mut lexer = crate::parser::lexer::Lexer::new(src, logger);
        let tokens = lexer.tokenize().expect("Lexing must succeed");
        let mut parser = Parser::new(tokens, debugger);
        let prog = parser.parse_program();
        assert!(prog.is_ok(), "Asymmetric boundaries {{ ... ] and [ ... }} must parse cleanly: {:?}", prog.err());
    }

    #[test]
    fn test_parser_adversative_caveat_interlock() {
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 5);
        let src = "Action [ +1 ] ! [ Guard = +1 ]";
        let mut lexer = crate::parser::lexer::Lexer::new(src, logger);
        let tokens = lexer.tokenize().expect("Lexing must succeed");
        let mut parser = Parser::new(tokens, debugger);
        let prog = parser.parse_program();
        assert!(prog.is_ok(), "Adversative caveat ! must parse cleanly: {:?}", prog.err());
    }

    #[test]
    fn test_parser_character_omni_source_reel_full_parse() {
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 100);
        let path = crate::core::filetype::resolve_track_path("lexicon/01_nouns/ideas/types/character.omni");
        assert!(path.exists(), "character.omni must exist at resolved track path");
        let src = std::fs::read_to_string(&path).expect("character.omni must be readable");
        let mut lexer = crate::parser::lexer::Lexer::new(&src, logger);
        let tokens = lexer.tokenize().expect("character.omni lexing must succeed");
        let mut parser = Parser::new(tokens, debugger);
        let prog = parser.parse_program();
        assert!(prog.is_ok(), "character.omni must parse cleanly into AST: {:?}", prog.err());
        let program_node = prog.unwrap();
        assert!(!program_node.statements.is_empty(), "character.omni AST must contain parsed statements");
    }

    #[test]
    fn test_parser_svo_verbs_and_composed_locators() {
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 10);
        let src = "[ ROLL 4 ] : [ Project ] : [ Character` } --> PROJECT [ Target ] ::@ 0x01";
        let mut lexer = crate::parser::lexer::Lexer::new(src, logger);
        let tokens = lexer.tokenize().expect("Lexing must succeed");
        let mut parser = Parser::new(tokens, debugger);
        let prog = parser.parse_program();
        assert!(prog.is_ok(), "SVO verb PROJECT and composed locator ::@ 0x01 must parse cleanly: {:?}", prog.err());
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/lexical/lexer.rs RS 678 LINES 2858 WORDS 32.0 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Lexer Identity, Ontological TokenType Re-exports & Morphemic Invariants )
// ============================================================================
//! # OmniCode Lexical Tokenizer (`lexer.rs`)
//!
//! Transforms raw source text reels into structured [`Token`] streams, enforcing
//! the physical and ontological boundary invariants of OmniCode.
//!
//! ## Scriptural Grounding:
//! - **Exodus 31:18**: *"And he gave unto Moses, when he had made an end of communing
//!   with him upon mount Sinai, two tables of testimony, tables of stone, written with
//!   the finger of God."*
//!   The Lexer transcribes divine mathematical axioms from the source reel into
//!   discrete, uncorrupted tokens of stone.
//! - **Proverbs 24:27**: *"Prepare thy work without, and make it fit for thyself in
//!   the field; and afterwards build thine house."*
//!   Morphemic tokens are meticulously prepared and validated in isolation before
//!   the syntactic house is erected by the grammar engine.
//! - **Proverbs 22:28**: *"Remove not the ancient landmark, which thy fathers have set."*
//!   Preserves the 6 ranked boundary landmarks and invariant operators across all reels.
//!
//! ## Architectural Foundations:
//! 1. **Modular Sub-Engine Structure**:
//!    - Token definitions and morphemes reside in [`crate::parser::tokens`].
//!    - Universal character streaming and coordinate tracking reside in [`crate::parser::char_stream`].
//!    - Language-specific compounding, state-primes, and boundary logic reside here.
//!
//! 2. **The 6 Ranked Morphological Boundary Delimiters**:
//!    - Rank 1 `< ... >`: Invariant Axiom (Absolute Immutable Law & Ontological Truth)
//!    - Rank 2 `[ ... ]`: Denotation (Concrete State Container & Evaluation Block)
//!    - Rank 3 `{ ... }`: Connotation (Context, Environment & Payload Attributes)
//!    - Rank 4 `[ ... }`: Inside-Out Emergence (Output Projection to External Universe)
//!    - Rank 5 `{ ... ]`: Outside-In Imposition (Input Capture from External Universe)
//!    - Rank 6 `( ... )`: Intent Aside (First-Class Cognitive Teleology & Rationale)
//!
//! 3. **First-Class Machine Intent**:
//!    Asides enclosed in `( ... )` are **never** discarded as trivia or comments.
//!    They are preserved in the token stream and lowered into the AST as persistent
//!    teleological metadata nodes, recording the *why* of every machine state.
//!
//! 4. **Causal State-Primes (`Character'`, ```Character` ```)**:
//!    Discrete clock cycles advance an entity from state $S$ to state $S'$. The state-prime
//!    operator is tokenized as part of the identifier, designating causality without collision.
//!
//! 5. **Dual-Substrate Arithmetic & Hardware Locators**:
//!    Supports balanced-ternary literals (`+1:PROCEED`, `-1:ROLLBACK`, `0:AWAIT`),
//!    hexadecimal hardware addresses (`0x01`, `0x000B8000`), hardware locators (`::@`),
//!    SVO natural arithmetic (`plus`, `minus`, `times`, `div`), and agentic pronouns.

pub use crate::parser::tokens::{SourceLocation, Span, Token, TokenType};
pub use crate::parser::char_stream::{CharCheckpoint, CharCursor};

use crate::core::boundaries::BoundaryType;
use crate::core::operators::{AffixPosition, Polarity};
use crate::core::ternary::QuadState;
use crate::core::linguistics::PronounKind;
use crate::diagnostics::logger::{DiagnosticLogger, FailpointType};


// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Lexer State Structure & Coordinator Initializer )
// ============================================================================

/// State container for source text reel tokenization.
pub struct Lexer<'a> {
    /// Universal character stream cursor.
    cursor: CharCursor<'a>,
    /// Depth counter for nested square brackets `[...]`.
    pub bracket_depth: usize,
    /// Diagnostic logger recording failpoint telemetry and lexical events.
    pub logger: DiagnosticLogger,
}
```

```rust

impl<'a> Lexer<'a> {
    /// Constructs a new [`Lexer`] over an OmniCode source reel string.
    ///
    /// # Arguments
    /// * `source` - Complete OmniCode UTF-8 source string.
    /// * `logger` - Diagnostic logger for telemetry and failpoint recording.
    pub fn new(source: &'a str, logger: DiagnosticLogger) -> Self {
        Self {
            cursor: CharCursor::new(source),
            bracket_depth: 0,
            logger,
        }
    }

    /// Read-only reference to the internal character cursor.
    #[inline]
    pub fn cursor(&self) -> &CharCursor<'a> {
        &self.cursor
    }
}


// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Core Tokenization Transformation Pipeline & Modular Scanning Engines )
// ============================================================================
impl<'a> Lexer<'a> {
    /// Tokenizes the entire source reel into a complete [`Token`] stream.
    ///
    /// Evaluates sequential lexical passes:
    /// 1. Skip whitespace and `#` comments.
    /// 2. First-class Intent Asides `( ... )`.
    /// 3. Multi-character compound operators and directional vectors.
    /// 4. Prefixed polarity identifiers (`+Word`, `-Word`).
    /// 5. Single-character morphological boundaries and operators.
    /// 6. Numeric literals (Hexadecimal and Decimal).
    /// 7. Identifiers, State-Primes (`Word'`, ```Word` ```), Postfix Polarities, Pronouns, and Keywords.
    pub fn tokenize(&mut self) -> Result<Vec<Token>, String> {
        let mut tokens = Vec::new();

        while !self.cursor.is_at_end() {
            self.cursor.skip_whitespace_and_comments('#');
            if self.cursor.is_at_end() {
                break;
            }

            let cur_line = self.cursor.line();
            let cur_col = self.cursor.col();

            // ---------------------------------------------------------------
            // 1. FIRST-CLASS INTENT ASIDES: ( ... )
            // ---------------------------------------------------------------
            if self.cursor.peek() == Some('(') {
                self.cursor.advance();
                tokens.push(self.read_aside(cur_line, cur_col)?);
                continue;
            }

            // ---------------------------------------------------------------
            // 2. MULTI-CHARACTER COMPOUND OPERATORS, VECTORS & LOCATORS
            // ---------------------------------------------------------------
            if let Some(tok) = self.match_compound_operators(cur_line, cur_col) {
                tokens.push(tok);
                continue;
            }

            // ---------------------------------------------------------------
            // 3. PREFIXED POLARITY IDENTIFIERS: +Word (Abstract), -Word (Concrete)
            // ---------------------------------------------------------------
            if (self.cursor.peek() == Some('+') || self.cursor.peek() == Some('-'))
                && self.cursor.peek_matches(1, |c| c.is_alphabetic() || c == '_')
            {
                tokens.push(self.read_prefixed_polarity(cur_line, cur_col));
                continue;
            }

            // ---------------------------------------------------------------
```

```
            // 4. BOUNDARY DELIMITERS, NUMBERS, STRINGS & IDENTIFIERS
            // ------------------------------------------------------------------
            let ch = self.cursor.peek().unwrap();
            match ch {
                // Morphological Boundaries: [ ] { } < >
                '[' | ']' | '{' | '}' | '<' | '>' => {
                    tokens.push(self.read_boundary_delimiter(ch, tokens.last(), cur_line, cur_col));
                }

                // Single-Character Operators & Connectives
                '=' | '!' | ':' | '|' | '?' | '@' | '%' | '&' | '+' | '-' | '*' => {
                    tokens.push(self.read_single_char_operator(ch, cur_line, cur_col));
                }

                // String & Character Literals ('...' or "...")
                '"' | '\'' => {
                    self.cursor.advance();
                    tokens.push(self.read_string_or_char(ch, cur_line, cur_col)?);
                }

                // Statement and Element Separators
                ';' | ',' => {
                    self.cursor.advance();
                }

                // Numeric Literals (Hexadecimal `0x...` or Decimal)
                _ if ch.is_ascii_digit() => {
                    tokens.push(self.read_number(ch, cur_line, cur_col)?);
                }

                // Identifiers, State-Primes, Pronouns, and Keywords
                _ if ch.is_alphabetic() || ch == '_' => {
                    tokens.push(self.read_identifier_or_keyword(cur_line, cur_col));
                }

                // Unrecognized Character Anomaly
                other => {
                    let msg = format!("Unexpected character '{other}' at L{cur_line}:C{cur_col}");
                    self.logger.failpoint(FailpointType::SyntaxAnomaly, "LEXER", &msg);
                    return Err(format!("FAILPOINT: {msg}"));
                }
            }
        }

        tokens.push(Token::eof(self.cursor.line(), self.cursor.col()));
        Ok(tokens)
    }

    /// Matches multi-character compound operators, directional vectors, casts, and locators
    /// using zero-allocation matching via [`CharCursor`].
    fn match_compound_operators(&mut self, cur_line: usize, cur_col: usize) -> Option<Token> {
        // Freeform Boundary Casts: [+], [-], <+>, <->, {+}, {-}
        if self.cursor.match_str("[+]") {
            return Some(Token::new(TokenType::BoundaryCast { boundary: BoundaryType::Denotation, polarity:
Polarity::Abstract }, "[+]", cur_line, cur_col));
        }
        if self.cursor.match_str("[-]") {
            return Some(Token::new(TokenType::BoundaryCast { boundary: BoundaryType::Denotation, polarity:
Polarity::Concrete }, "[-]", cur_line, cur_col));
        }
        if self.cursor.match_str("<+>") {
            return Some(Token::new(TokenType::BoundaryCast { boundary: BoundaryType::Invariant, polarity:
Polarity::Abstract }, "<+>", cur_line, cur_col));
        }
        if self.cursor.match_str("<->") {
            return Some(Token::new(TokenType::BoundaryCast { boundary: BoundaryType::Invariant, polarity:
Polarity::Concrete }, "<->", cur_line, cur_col));
        }
        if self.cursor.match_str("{+}") {
            return Some(Token::new(TokenType::BoundaryCast { boundary: BoundaryType::Connotation, polarity:
Polarity::Abstract }, "{+}", cur_line, cur_col));
        }
        if self.cursor.match_str("{-}") {
            return Some(Token::new(TokenType::BoundaryCast { boundary: BoundaryType::Connotation, polarity:
Polarity::Concrete }, "{-}", cur_line, cur_col));
        }

        // 3-Character Directional Vectors, Equivalence & Hardware Locator
```

```
        if self.cursor.match_str("-->") {
            return Some(Token::new(TokenType::ActUpon, "-->", cur_line, cur_col));
        }
        if self.cursor.match_str("<--") {
            return Some(Token::new(TokenType::ActAgain, "<--", cur_line, cur_col));
        }
        if self.cursor.match_str("--^") || self.cursor.match_str("^--") {
            return Some(Token::new(TokenType::BuildsTo, "^--", cur_line, cur_col));
        }
        if self.cursor.match_str("--v") || self.cursor.match_str("v--") {
            return Some(Token::new(TokenType::BreaksDownFrom, "v--", cur_line, cur_col));
        }
        if self.cursor.match_str("<=>") {
            return Some(Token::new(TokenType::InvariantEquivalence, "<=>", cur_line, cur_col));
        }
        if self.cursor.match_str("::@") {
            return Some(Token::new(TokenType::HardwareLocator, "::@", cur_line, cur_col));
        }

        // 2-Character Directional Vectors, Relations & Connectives
        if self.cursor.match_str("->") {
            return Some(Token::new(TokenType::ActUpon, "->", cur_line, cur_col));
        }
        if self.cursor.match_str("<-") {
            return Some(Token::new(TokenType::ActAgain, "<-", cur_line, cur_col));
        }
        if self.cursor.match_str("-^") {
            return Some(Token::new(TokenType::BuildsTo, "-^", cur_line, cur_col));
        }
        if self.cursor.match_str("-v") {
            return Some(Token::new(TokenType::BreaksDownFrom, "-v", cur_line, cur_col));
        }
        if self.cursor.match_str("::") {
            return Some(Token::new(TokenType::And, "::", cur_line, cur_col));
        }
        if self.cursor.match_str("!=") {
            return Some(Token::new(TokenType::IsNot, "!=", cur_line, cur_col));
        }
        if self.cursor.match_str("=!") {
            return Some(Token::new(TokenType::ToBeNot, "=!", cur_line, cur_col));
        }
        if self.cursor.match_str("~=") {
            return Some(Token::new(TokenType::ToBeLike, "~=", cur_line, cur_col));
        }
        if self.cursor.match_str("=~") {
            return Some(Token::new(TokenType::ToBeLike, "=~", cur_line, cur_col));
        }
        if self.cursor.match_str("~!") {
            return Some(Token::new(TokenType::But, "~!", cur_line, cur_col));
        }
        if self.cursor.match_str("<=") {
            return Some(Token::new(TokenType::LessEqual, "<=", cur_line, cur_col));
        }
        if self.cursor.match_str(">=") {
            return Some(Token::new(TokenType::GreaterEqual, ">=", cur_line, cur_col));
        }
        if self.cursor.match_str("--") {
            return Some(Token::new(TokenType::Not, "--", cur_line, cur_col));
        }

        // Diagonal Scale Modulations & 2D Quadrants
        if self.cursor.match_str("/-^") {
            return Some(Token::new(TokenType::Major, "/-^", cur_line, cur_col));
        }
        if self.cursor.match_str("\\-v") {
            return Some(Token::new(TokenType::Minor, "\\-v", cur_line, cur_col));
        }
        if self.cursor.match_str("\\-^") {
            return Some(Token::new(TokenType::Great, "\\-^", cur_line, cur_col));
        }
        if self.cursor.match_str("/-v") {
            return Some(Token::new(TokenType::Small, "/-v", cur_line, cur_col));
        }
        if self.cursor.match_str("/^") {
            return Some(Token::new(TokenType::UpperRight, "/^", cur_line, cur_col));
        }
        if self.cursor.match_str("\\v") {
            return Some(Token::new(TokenType::LowerRight, "\\v", cur_line, cur_col));
```

```
        }
        if self.cursor.match_str("^\\") {
            return Some(Token::new(TokenType::UpperLeft, "^\\", cur_line, cur_col));
        }
        if self.cursor.match_str("v/") {
            return Some(Token::new(TokenType::LowerLeft, "v/", cur_line, cur_col));
        }
        if self.cursor.match_str("..") {
            return Some(Token::new(TokenType::DotDot, "..", cur_line, cur_col));
        }

        // Signed Balanced-Ternary Literals: +1, -1
        if self.cursor.match_str("+1") {
            return Some(Token::new(TokenType::Ternary(QuadState::Proceed), "+1", cur_line, cur_col));
        }
        if self.cursor.match_str("-1") {
            return Some(Token::new(TokenType::Ternary(QuadState::Rollback), "-1", cur_line, cur_col));
        }

        None
    }

    /// Scans a first-class teleological Intent Aside enclosed in `( ... )`.
    fn read_aside(&mut self, start_line: usize, start_col: usize) -> Result<Token, String> {
        let mut depth = 1;
        let mut content = String::new();

        while let Some(ch) = self.cursor.advance() {
            match ch {
                '(' => {
                    depth += 1;
                    content.push(ch);
                }
                ')' => {
                    depth -= 1;
                    if depth == 0 {
                        let text = content.trim().to_string();
                        self.logger.log("ASIDE", format!("Captured Aside: ({text})"));
                        return Ok(Token::new(TokenType::Aside(text), format!("({content})"), start_line, start_col));
                    }
                    content.push(ch);
                }
                _ => content.push(ch),
            }
        }

        let msg = format!("Unclosed Aside '(' opened at L{start_line}:C{start_col} reaches EOF");
        self.logger.failpoint(FailpointType::BoundaryLeak, "LEXER", &msg);
        Err(format!("FAILPOINT [UnclosedAside]: {msg}"))
    }

    /// Scans a quoted string literal (`"..."`) or atomic character literal (`'...'`).
    fn read_string_or_char(&mut self, quote: char, start_line: usize, start_col: usize) -> Result<Token, String> {
        let mut s = String::new();
        while let Some(ch) = self.cursor.advance() {
            if ch == quote {
                // If single quote with single character, recognize as atomic Character glyph
                if quote == '\'' && s.chars().count() == 1 {
                    let c = s.chars().next().unwrap();
                    return Ok(Token::new(TokenType::CharLit(c), format!("'{s}'"), start_line, start_col));
                }
                return Ok(Token::new(TokenType::StringLit(s.clone()), format!("\"{s}\""), start_line, start_col));
            } else if ch == '\\' {
                if let Some(esc) = self.cursor.advance() {
                    match esc {
                        'n' => s.push('\n'),
                        'r' => s.push('\r'),
                        't' => s.push('\t'),
                        '\\' => s.push('\\'),
                        '\'' => s.push('\''),
                        '"' => s.push('"'),
                        '0' => s.push('\0'),
                        other => s.push(other),
                    }
                }
            } else {
                s.push(ch);
            }
```

```
        }
        let msg = format!("Unclosed literal opened at L{start_line}:C{start_col} reaches EOF");
        self.logger.failpoint(FailpointType::SyntaxAnomaly, "LEXER", &msg);
        Err(format!("FAILPOINT: {msg}"))
    }

    /// Scans a prefixed polarity identifier (`+Word` or `-Word`).
    fn read_prefixed_polarity(&mut self, cur_line: usize, cur_col: usize) -> Token {
        let sign = self.cursor.advance().unwrap();
        let polarity = if sign == '+' { Polarity::Abstract } else { Polarity::Concrete };
        let ident = self.cursor.consume_while(|c| c.is_alphanumeric() || c == '_' || c == '.' || c == '?');
        let lexeme = format!("{}{}", sign, ident);
        Token::new(
            TokenType::AffixedIdent {
                name: ident,
                polarity,
                position: AffixPosition::Prefix,
            },
            lexeme,
            cur_line,
            cur_col,
        )
    }

    /// Scans a single-character morphological boundary delimiter.
    fn read_boundary_delimiter(&mut self, ch: char, last_token: Option<&Token>, cur_line: usize, cur_col: usize) -> Token
{
        self.cursor.advance();
        match ch {
            '[' => {
                self.bracket_depth += 1;
                Token::new(TokenType::LBracket, "[", cur_line, cur_col)
            }
            ']' => {
                self.bracket_depth = self.bracket_depth.saturating_sub(1);
                Token::new(TokenType::RBracket, "]", cur_line, cur_col)
            }
            '{' => Token::new(TokenType::LBrace, "{", cur_line, cur_col),
            '}' => Token::new(TokenType::RBrace, "}", cur_line, cur_col),
            '<' => {
                // Canon 3 Disambiguation: Casted context comparison [ { A } < { B } ]
                if self.bracket_depth > 0
                    && last_token.map_or(false, |t| t.token_type == TokenType::RBrace)
                    && self.cursor.peek_next_non_whitespace(0) == Some('{')
                {
                    Token::new(TokenType::LessThan, "<", cur_line, cur_col)
                } else {
                    Token::new(TokenType::LAngle, "<", cur_line, cur_col)
                }
            }
            '>' => {
                // Canon 3 Disambiguation: Casted context comparison [ { A } > { B } ]
                if self.bracket_depth > 0
                    && last_token.map_or(false, |t| t.token_type == TokenType::RBrace)
                    && self.cursor.peek_next_non_whitespace(0) == Some('{')
                {
                    Token::new(TokenType::GreaterThan, ">", cur_line, cur_col)
                } else {
                    Token::new(TokenType::RAngle, ">", cur_line, cur_col)
                }
            }
            _ => unreachable!(),
        }
    }

    /// Scans a single-character operator or connective.
    fn read_single_char_operator(&mut self, ch: char, cur_line: usize, cur_col: usize) -> Token {
        self.cursor.advance();
        match ch {
            '=' => Token::new(TokenType::Is, "=", cur_line, cur_col),
            '!' => Token::new(TokenType::But, "!", cur_line, cur_col),
            ':' => Token::new(TokenType::InRelationTo, ":", cur_line, cur_col),
            '|' => Token::new(TokenType::Or, "|", cur_line, cur_col),
            '?' => Token::new(TokenType::Infer, "?", cur_line, cur_col),
            '@' => Token::new(TokenType::At, "@", cur_line, cur_col),
            '%' => Token::new(TokenType::Percent, "%", cur_line, cur_col),
            '&' => Token::new(TokenType::BoundPair, "&", cur_line, cur_col),
            '+' => Token::new(TokenType::Plus, "+", cur_line, cur_col),
```

```
            '-' => Token::new(TokenType::Minus, "-", cur_line, cur_col),
            '*' => Token::new(TokenType::Times, "*", cur_line, cur_col),
            _ => unreachable!(),
        }
    }

    /// Scans numeric literals, including hexadecimal (`0x...`), standalone ternary zero `0`,
    /// and decimal integers/floats.
    fn read_number(&mut self, ch: char, cur_line: usize, cur_col: usize) -> Result<Token, String> {
        // Hexadecimal hardware address locator: 0x01, 0x000B8000
        if ch == '0' && (self.cursor.peek_at(1) == Some('x') || self.cursor.peek_at(1) == Some('X')) {
            self.cursor.advance(); // consume '0'
            self.cursor.advance(); // consume 'x' or 'X'
            let hex_str = self.cursor.consume_while(|c| c.is_ascii_hexdigit());
            let val = u64::from_str_radix(&hex_str, 16)
                .map_err(|e| format!("FAILPOINT: Invalid hex number '0x{hex_str}': {e}"))?;
            return Ok(Token::new(TokenType::Number(val as f64), format!("0x{hex_str}"), cur_line, cur_col));
        }

        // Binary bit-plane pattern: 0b00, 0b01, 0b10, 0b11, 0b0101_1010
        if ch == '0' && (self.cursor.peek_at(1) == Some('b') || self.cursor.peek_at(1) == Some('B')) {
            self.cursor.advance(); // consume '0'
            self.cursor.advance(); // consume 'b' or 'B'
            let bin_str = self.cursor.consume_while(|c| c == '0' || c == '1' || c == '_');
            let clean_bin: String = bin_str.chars().filter(|&c| c != '_').collect();
            let val = u64::from_str_radix(&clean_bin, 2)
                .map_err(|e| format!("FAILPOINT: Invalid binary number '0b{bin_str}': {e}"))?;
            return Ok(Token::new(TokenType::Number(val as f64), format!("0b{bin_str}"), cur_line, cur_col));
        }

        // Standalone ternary zero `0` representing Await / Equilibrium
        if ch == '0' && !self.cursor.peek_matches(1, |c| c.is_alphanumeric() || c == '.') {
            self.cursor.advance();
            return Ok(Token::new(TokenType::Ternary(QuadState::Await), "0", cur_line, cur_col));
        }

        // Decimal integer or floating point number
        let num_str = self.cursor.consume_while(|c| c.is_ascii_digit() || c == '.');
        let val: f64 = num_str.parse().map_err(|e| format!("FAILPOINT: Invalid number '{num_str}': {e}"))?;
        Ok(Token::new(TokenType::Number(val), num_str, cur_line, cur_col))
    }

    /// Scans identifiers, SVO verbs, state-primes (`Name'`, ```Name` ```), postfix polarities,
    /// pronouns, and grammatical keywords.
    fn read_identifier_or_keyword(&mut self, cur_line: usize, cur_col: usize) -> Token {
        // Accumulate identifier characters, including state-prime (`) and ticks (')
        let ident = self.cursor.consume_while(|c| {
            c.is_alphanumeric() || c == '_' || c == '.' || c == '?' || c == '\'' || c == '`'
        });

        // Check for attached Postfix Polarity: Word+ (Abstract), Word- (Concrete)
        let mut postfix_polarity = None;
        if self.cursor.peek() == Some('+') {
            let next_after = self.cursor.peek_at(1);
            if next_after.map_or(true, |c| {
                c.is_whitespace() || c == ']' || c == '}' || c == '>' || c == ')' || c == ',' || c == ';' || c == '!' ||
c == '@' || c == ':'
            }) {
                self.cursor.advance();
                postfix_polarity = Some(Polarity::Abstract);
            }
        } else if self.cursor.peek() == Some('-') {
            let next_after = self.cursor.peek_at(1);
            if next_after.map_or(true, |c| {
                c != '>' && c != '-' && c != '^' && c != 'v' && (
                    c.is_whitespace() || c == ']' || c == '}' || c == '>' || c == ')' || c == ',' || c == ';' || c == '!'
|| c == '@' || c == ':'
                )
            }) {
                self.cursor.advance();
                postfix_polarity = Some(Polarity::Concrete);
            }
        }

        if let Some(polarity) = postfix_polarity {
            let lexeme = format!("{}{}", ident, polarity.symbol());
            return Token::new(
                TokenType::AffixedIdent {
```

```
                    name: ident,
                    polarity,
                    position: AffixPosition::Postfix,
                },
                lexeme,
                cur_line,
                cur_col,
            );
        }

        // Disambiguate keywords, pronouns, ternary states, and general identifiers
        match ident.to_lowercase().as_str() {
            "null" | "void" | "halt" | "stop" => Token::new(TokenType::Ternary(QuadState::Halt), ident, cur_line,
cur_col),
            "yes" | "proceed" | "play" => Token::new(TokenType::Ternary(QuadState::Proceed), ident, cur_line, cur_col),
            "ok" | "await" | "pause" => Token::new(TokenType::Ternary(QuadState::Await), ident, cur_line, cur_col),
            "no" | "rollback" | "rewind" => Token::new(TokenType::Ternary(QuadState::Rollback), ident, cur_line,
cur_col),
            "plus" => Token::new(TokenType::Plus, ident, cur_line, cur_col),
            "minus" => Token::new(TokenType::Minus, ident, cur_line, cur_col),
            "times" => Token::new(TokenType::Times, ident, cur_line, cur_col),
            "div" => Token::new(TokenType::Div, ident, cur_line, cur_col),
            "who" => Token::new(TokenType::Who, ident, cur_line, cur_col),
            "what" => Token::new(TokenType::What, ident, cur_line, cur_col),
            "when" => Token::new(TokenType::When, ident, cur_line, cur_col),
            "where" => Token::new(TokenType::Where, ident, cur_line, cur_col),
            "why" => Token::new(TokenType::Why, ident, cur_line, cur_col),
            "how" => Token::new(TokenType::How, ident, cur_line, cur_col),
            _ => {
                if let Some(p) = PronounKind::from_keyword(&ident) {
                    Token::new(TokenType::Pronoun(p), ident, cur_line, cur_col)
                } else {
                    Token::new(TokenType::Identifier(ident.clone()), ident, cur_line, cur_col)
                }
            }
        }
    }
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Lexical Verification Proofs, Boundary Integrity & Test Oracles )
// ============================================================================
#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_lexing_pronouns_and_reflexives() {
        let logger = DiagnosticLogger::new(false);
        let mut lexer = Lexer::new("I you it they myself itself my your _", logger);
        let tokens = lexer.tokenize().expect("Lexing pronouns");

        assert_eq!(tokens[0].token_type, TokenType::Pronoun(PronounKind::I));
        assert_eq!(tokens[1].token_type, TokenType::Pronoun(PronounKind::You));
        assert_eq!(tokens[2].token_type, TokenType::Pronoun(PronounKind::It));
        assert_eq!(tokens[3].token_type, TokenType::Pronoun(PronounKind::They));
        assert_eq!(tokens[4].token_type, TokenType::Pronoun(PronounKind::Myself));
        assert_eq!(tokens[5].token_type, TokenType::Pronoun(PronounKind::Itself));
        assert_eq!(tokens[6].token_type, TokenType::Pronoun(PronounKind::My));
        assert_eq!(tokens[7].token_type, TokenType::Pronoun(PronounKind::Your));
        assert_eq!(tokens[8].token_type, TokenType::Pronoun(PronounKind::Wildcard));
    }

    #[test]
    fn test_lexing_hexadecimal_numbers_and_locators() {
        let logger = DiagnosticLogger::new(false);
        let mut lexer = Lexer::new("0x01 ::@ 0x000B8000", logger);
        let tokens = lexer.tokenize().expect("Lexing hex numbers");

        assert_eq!(tokens[0].token_type, TokenType::Number(1.0));
        assert!(tokens[1].is_hardware_locator());
        assert_eq!(tokens[1].token_type, TokenType::HardwareLocator);
        assert_eq!(tokens[1].lexeme, "::@");
        assert_eq!(tokens[2].token_type, TokenType::Number(0xB8000 as f64));
    }

```

```
    #[test]
    fn test_lexing_state_primes_and_svo_verbs() {
        let logger = DiagnosticLogger::new(false);
        let mut lexer = Lexer::new("Character` --> INSCRIBE [ Cell ] = [ Character` ]", logger);
        let tokens = lexer.tokenize().expect("Lexing state primes and verbs");

        assert_eq!(tokens[0].lexeme, "Character`");
        assert!(tokens[0].is_state_prime());
        assert_eq!(tokens[1].token_type, TokenType::ActUpon);
        assert_eq!(tokens[2].lexeme, "INSCRIBE");
        assert_eq!(tokens[3].token_type, TokenType::LBracket);
        assert_eq!(tokens[4].lexeme, "Cell");
        assert_eq!(tokens[5].token_type, TokenType::RBracket);
        assert_eq!(tokens[6].token_type, TokenType::Is);
        assert_eq!(tokens[7].token_type, TokenType::LBracket);
        assert_eq!(tokens[8].lexeme, "Character`");
        assert_eq!(tokens[9].token_type, TokenType::RBracket);
    }

    #[test]
    fn test_lexing_relational_bounds_and_transduction() {
        let logger = DiagnosticLogger::new(false);
        let mut lexer = Lexer::new("65 <=> [ -1, +1, +1, -1, +1 ]", logger);
        let tokens = lexer.tokenize().expect("Lexing transduction and trits");

        assert_eq!(tokens[0].token_type, TokenType::Number(65.0));
        assert_eq!(tokens[1].token_type, TokenType::InvariantEquivalence);
        assert_eq!(tokens[2].token_type, TokenType::LBracket);
        assert_eq!(tokens[3].token_type, TokenType::Ternary(QuadState::Rollback));
        assert_eq!(tokens[4].token_type, TokenType::Ternary(QuadState::Proceed));
    }

    #[test]
    fn test_lexing_single_char_glyph_and_string() {
        let logger = DiagnosticLogger::new(false);
        let mut lexer = Lexer::new("'A' \"Hello\"", logger);
        let tokens = lexer.tokenize().expect("Lexing glyph and string");

        assert_eq!(tokens[0].token_type, TokenType::CharLit('A'));
        assert_eq!(tokens[1].token_type, TokenType::StringLit("Hello".into()));
    }

    #[test]
    fn test_lexing_character_omni_source_reel_token_stream() {
        let logger = DiagnosticLogger::new(false);
        let path = crate::core::filetype::resolve_track_path("lexicon/01_nouns/ideas/types/character.omni");
        assert!(path.exists(), "character.omni must exist");
        let src = std::fs::read_to_string(&path).expect("Read character.omni");
        let mut lexer = Lexer::new(&src, logger);
        let tokens = lexer.tokenize().expect("Tokenize character.omni");

        assert!(!tokens.is_empty(), "Token stream must not be empty");
        assert_eq!(tokens.last().unwrap().token_type, TokenType::Eof);
    }

    #[test]
    fn test_lexing_binary_numbers() {
        let logger = DiagnosticLogger::new(false);
        let mut lexer = Lexer::new("0b01 0b10 0b00 0b11 0b1010_0101", logger);
        let tokens = lexer.tokenize().expect("Lexing binary numbers");

        assert_eq!(tokens[0].token_type, TokenType::Number(1.0));
        assert_eq!(tokens[1].token_type, TokenType::Number(2.0));
        assert_eq!(tokens[2].token_type, TokenType::Number(0.0));
        assert_eq!(tokens[3].token_type, TokenType::Number(3.0));
        assert_eq!(tokens[4].token_type, TokenType::Number(165.0));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/lexical/mod.rs RS 20 LINES 95 WORDS 0.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Lexical Inscription & Token Vocabulary Subsystem )
// ============================================================================
//! # Lexical Inscription Subsystem
//!
//! Transforms raw source reels into structured [`Token`] streams, enforcing
//! the physical and ontological boundary invariants of OmniCode.
//!
//! ## Scriptural Grounding:
//! - **Exodus 31:18**: Divine inscription of characters on stone.
//! - **Proverbs 24:27**: Preparing tokens in the field before syntactic assembly.
//! - **Proverbs 22:28**: Preserving ancient morphemic boundaries and operators.

pub mod tokens;
pub mod lexer;

pub use tokens::{SourceLocation, Span, Token, TokenType};
pub use lexer::Lexer;
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/parser/lexical/tokens.rs RS 443 LINES 1748 WORDS 16.4 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Invariant Token Taxonomy, Morphemic Classifications & Source Spans )
// ============================================================================
//! # OmniCode Token Taxonomy (`tokens.rs`)
//!
//! Defines the ontological token vocabulary, morphemic classifications, and coordinate
//! spans emitted by the OmniCode lexical analyzer.
//!
//! ## Scriptural Grounding:
//! - **Exodus 31:18**: *"And he gave unto Moses, when he had made an end of communing
//!   with him upon mount Sinai, two tables of testimony, tables of stone, written with
//!   the finger of God."*
//!   Tokens are the immutable inscribed glyphs upon the silicon reel.
//! - **Proverbs 24:27**: *"Prepare thy work without, and make it fit for thyself in
//!   the field; and afterwards build thine house."*
//!   Lexical classification prepares every token in the field before the grammar engine
//!   builds the architectural syntactic house.
//! - **Proverbs 22:28**: *"Remove not the ancient landmark, which thy fathers have set."*
//!   Preserves ancient morphemic boundaries and structural rankings without corruption.
//!
//! ## Ontological Taxonomy:
//! 1. **Morphological Boundaries**: 6 ranked delimiters (`<...>`, `[...]`, `{...}`, `[...}`, `{...]`, `(...)`).
//! 2. **Agentic Pronouns**: Identity and capability pronouns (`I`, `you`, `it`, `they`, `myself`, etc.).
//! 3. **Polarities & Casts**: Concrete (`-`) and Abstract (`+`) affixes and boundary casts.
//! 4. **Directional Vectors**: 1D axial, 2D quadrant, and scale modulations (`-->`, `<--`, `^--`, `v--`, `/^`, `\v`).
//! 5. **Relations of Being**: Root assignment (`=`), similarity (`~=`), bounds (`<=`, `>=`), and bijective transduction (`<=>`).
//! 6. **Connectives & Locators**: Inseparable conjunctions (`::`), hardware locators (`::@`), adversarial caveats (`!`).
//! 7. **SVO Arithmetic**: Natural operation keywords (`plus`, `minus`, `times`, `div`).
//! 8. **Literals**: Balanced ternary (`+1`, `-1`, `0`, `NULL`), hex addresses (`0x...`), glyphs (`'A'`), strings (`"..."`).

use crate::core::boundaries::BoundaryType;
use crate::core::operators::{AffixPosition, Polarity};
use crate::core::ternary::QuadState;
use crate::core::linguistics::PronounKind;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Coordinates, Source Spans & Inscribed Token Unit )
// ============================================================================

/// Precise 1-indexed source reel location with byte offset tracking.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Default)]
pub struct SourceLocation {
    /// 1-indexed line number in source reel.
    pub line: usize,
    /// 1-indexed column number in source reel.
    pub col: usize,
    /// 0-indexed byte offset from start of source text.
    pub offset: usize,
}

impl SourceLocation {
    /// Creates a new source location coordinate.
    pub const fn new(line: usize, col: usize, offset: usize) -> Self {
        Self { line, col, offset }
    }
}

/// A contiguous source span from `start` coordinate to `end` coordinate.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Default)]
pub struct Span {
    /// Inclusive starting coordinate.
    pub start: SourceLocation,
    /// Inclusive ending coordinate.
    pub end: SourceLocation,
}

impl Span {
    /// Creates a new span spanning from `start` to `end`.
    pub const fn new(start: SourceLocation, end: SourceLocation) -> Self {
        Self { start, end }
```

```rust
    }

    /// Creates an atomic single-point span.
    pub const fn point(loc: SourceLocation) -> Self {
        Self { start: loc, end: loc }
    }
}

/// Inscribed token unit with source reel coordinate tracking.
#[derive(Debug, Clone, PartialEq)]
pub struct Token {
    /// Grammatical token classification.
    pub token_type: TokenType,
    /// Exact character sequence matched in the source text.
    pub lexeme: String,
    /// 1-indexed line coordinate in source reel.
    pub line: usize,
    /// 1-indexed column coordinate in source reel.
    pub col: usize,
}

impl Token {
    /// Constructs a new inscribed [`Token`].
    #[inline]
    pub fn new(token_type: TokenType, lexeme: impl Into<String>, line: usize, col: usize) -> Self {
        Self {
            token_type,
            lexeme: lexeme.into(),
            line,
            col,
        }
    }

    /// Constructs an End-Of-File sentinel token.
    #[inline]
    pub fn eof(line: usize, col: usize) -> Self {
        Self {
            token_type: TokenType::Eof,
            lexeme: String::new(),
            line,
            col,
        }
    }

    /// Returns `true` if this token is an EOF sentinel.
    #[inline]
    pub fn is_eof(&self) -> bool {
        self.token_type == TokenType::Eof
    }

    /// Checks if this token is a hardware locator (`::@`), supporting both first-class
    /// [`TokenType::HardwareLocator`] and legacy compounded [`TokenType::And`] with `"::@"`.
    #[inline]
    pub fn is_hardware_locator(&self) -> bool {
        self.token_type.is_hardware_locator(&self.lexeme)
    }

    /// Returns `true` if this token is an identifier designated as a state-prime (`Name'` or ```Name` ```).
    #[inline]
    pub fn is_state_prime(&self) -> bool {
        match &self.token_type {
            TokenType::Identifier(id) => TokenType::is_state_prime_name(id),
            _ => false,
        }
    }
}


// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Complete Ontological TokenType Hierarchy & Categorical Methods )
// ============================================================================

/// Complete taxonomy of grammatical tokens emitted by the Lexer.
#[derive(Debug, Clone, PartialEq)]
pub enum TokenType {
    // ------------------------------------------------------------------------
    // 1. Boundary Delimiters & First-Class Asides
```

```
    // --------------------------------------------------------------------------
    /// `[` Opening Denotation / Bottom-Up Emergence
    LBracket,
    /// `]` Closing Denotation / Top-Down Imposition
    RBracket,
    /// `{` Opening Connotation / Top-Down Imposition
    LBrace,
    /// `}` Closing Connotation / Bottom-Up Emergence
    RBrace,
    /// `<` Opening Invariant Axiom
    LAngle,
    /// `>` Closing Invariant Axiom
    RAngle,
    /// `( ... )` First-class Intent Aside capturing architectural rationale
    Aside(String),

    // --------------------------------------------------------------------------
    // 2. Grammatical Pronouns & Reflexives
    // --------------------------------------------------------------------------
    /// Agentic pronouns (`I`, `you`, `it`, `they`, `myself`, `itself`, `_`, etc.)
    Pronoun(PronounKind),

    // --------------------------------------------------------------------------
    // 3. Polarity & Boundary Cast Operators
    // --------------------------------------------------------------------------
    /// Affixed Identifiers (`+Word` Abstract, `-Word` Concrete, `Word+`, `Word-`)
    AffixedIdent {
        name: String,
        polarity: Polarity,
        position: AffixPosition,
    },
    /// Boundary Casts (`[+]`, `[-]`, `<+>`, `<->`, `{+}`, `{-}`)
    BoundaryCast {
        boundary: BoundaryType,
        polarity: Polarity,
    },

    // --------------------------------------------------------------------------
    // 4. Directional Vectors (Axial, Diagonal Scale Modulations & 2D Quadrants)
    // --------------------------------------------------------------------------
    /// `-->` / `->` Act Upon (Forward Vector / Transduction)
    ActUpon,
    /// `<--` / `<-` Act Again (Feedback / Rollback / Reverse Vector)
    ActAgain,
    /// `^--` / `--^` / `-^` Builds To (Ascension / Synthesis Vector)
    BuildsTo,
    /// `v--` / `--v` / `-v` Breaks Down From (Descension / Decomposition Vector)
    BreaksDownFrom,
    /// `/-^` Major scale up (Ascend forward)
    Major,
    /// `\-v` Minor scale down (Descend forward)
    Minor,
    /// `\-^` Great scale up (Ascend backward)
    Great,
    /// `/-v` Small scale down (Descend backward)
    Small,
    /// `/^` Quadrant I / Northeast
    UpperRight,
    /// `\v` Quadrant IV / Southeast
    LowerRight,
    /// `^\` Quadrant II / Northwest
    UpperLeft,
    /// `v/` Quadrant III / Southwest
    LowerLeft,

    // --------------------------------------------------------------------------
    // 5. Relations of Being & Invariant Transduction
    // --------------------------------------------------------------------------
    /// `=` Is (Relational Identity / Root Assignment)
    Is,
    /// `!=` Is Not (Relational Disparity / Not to be)
    IsNot,
    /// `=!` To Be Not (State Negation Predicate / Is not)
    ToBeNot,
    /// `~=` To Be Like (Fuzzy Affinity / Morphological Similarity)
    ToBeLike,
    /// `<=>` Invariant Equivalence (Bijective Dimensional Transduction: Bits <=> Trits)
    InvariantEquivalence,
```

```
    /// `<` Less Than (Casted context comparison)
    LessThan,
    /// `>` Greater Than (Casted context comparison)
    GreaterThan,
    /// `<=` Less Than or Equal To (Bound comparison: `{ Character` <= [ 1 Cell ] }`)
    LessEqual,
    /// `>=` Greater Than or Equal To (Bound comparison)
    GreaterEqual,

    // ---------------------------------------------------------------------
    // 6. Connectives, Conjunctions & Bindings
    // ---------------------------------------------------------------------
    /// `!` Adversative Caveat (A BUT B / Guard Interlock)
    But,
    /// `::` Inseparable Conjunction
    And,
    /// `::@` Dedicated Hardware Locator / MMIO Port Binding
    HardwareLocator,
    /// `:` In Relation To / Type Classification
    InRelationTo,
    /// `|` Disjunctive Alternative / Branching Choice
    Or,
    /// `--` Unary Negation (Not)
    Not,
    /// `&` Inseparable Twin Binding (A&B Hand-in-Hand)
    BoundPair,

    // ---------------------------------------------------------------------
    // 7. Prepositions, Locators, Ranges & Measures
    // ---------------------------------------------------------------------
    /// `@` Located At (MMIO Address / Stream Port)
    At,
    /// `..` Coordinate Range / Interval Span
    DotDot,
    /// `%` Proportion / Fullness / Fraction
    Percent,

    // ---------------------------------------------------------------------
    // 8. Cardinal Classification Clauses (The 5 W's and 1 H)
    // ---------------------------------------------------------------------
    /// `WHO` Agent / Actor / Identity
    Who,
    /// `WHAT` Substance / Entity / Vessel
    What,
    /// `WHEN` Cadence / Lifecycle / Trigger
    When,
    /// `WHERE` Spatial Site / Memory Partition / Scope
    Where,
    /// `WHY` Teleological Intent / Rationale / Axiom
    Why,
    /// `HOW` Causal Mechanism / Status / Roll Vector
    How,

    // ---------------------------------------------------------------------
    // 9. SVO Arithmetic Keywords
    // ---------------------------------------------------------------------
    /// `plus`, `add`
    Plus,
    /// `minus`, `sub`
    Minus,
    /// `times`, `mult`
    Times,
    /// `div`, `over`, `divided_by`
    Div,

    // ---------------------------------------------------------------------
    // 10. Inferential Operators & Terminals
    // ---------------------------------------------------------------------
    /// `?` Infer / Epistemic Query
    Infer,
    /// Balanced-Ternary Literals (`+1`, `-1`, `0`, `NULL`, `PROCEED`, `ROLLBACK`, `AWAIT`, `HALT`)
    Ternary(QuadState),
    /// Numeric Literals (Hexadecimal `0x...`, Decimal Integers, Floats)
    Number(f64),
    /// Atomic Character Glyph Literal (`'A'`, `'\n'`)
    CharLit(char),
    /// String Literals (`"..."`)
    StringLit(String),
```

```
    /// Generic Identifiers & SVO Verbs (supporting state-prime ``` ` ``` and `'`)
    Identifier(String),
    /// End-of-file sentinel
    Eof,
}

impl TokenType {
    /// Returns `true` if this token marks an opening morphological boundary (`[`, `{`, `<`).
    pub fn is_open_boundary(&self) -> bool {
        matches!(self, TokenType::LBracket | TokenType::LBrace | TokenType::LAngle)
    }

    /// Returns `true` if this token marks a closing morphological boundary (`]`, `}`, `>`).
    pub fn is_close_boundary(&self) -> bool {
        matches!(self, TokenType::RBracket | TokenType::RBrace | TokenType::RAngle)
    }

    /// Returns `true` if this token is any morphological boundary delimiter.
    pub fn is_boundary(&self) -> bool {
        self.is_open_boundary() || self.is_close_boundary()
    }

    /// Returns `true` if this token represents a directional vector.
    pub fn is_directional_vector(&self) -> bool {
        matches!(
            self,
            TokenType::ActUpon
                | TokenType::ActAgain
                | TokenType::BuildsTo
                | TokenType::BreaksDownFrom
                | TokenType::Major
                | TokenType::Minor
                | TokenType::Great
                | TokenType::Small
                | TokenType::UpperRight
                | TokenType::LowerRight
                | TokenType::UpperLeft
                | TokenType::LowerLeft
        )
    }

    /// Returns `true` if this token represents a relation of being or comparison.
    pub fn is_relational(&self) -> bool {
        matches!(
            self,
            TokenType::Is
                | TokenType::IsNot
                | TokenType::ToBeNot
                | TokenType::ToBeLike
                | TokenType::InvariantEquivalence
                | TokenType::LessThan
                | TokenType::GreaterThan
                | TokenType::LessEqual
                | TokenType::GreaterEqual
        )
    }

    /// Returns `true` if this token represents an arithmetic operator or keyword.
    pub fn is_arithmetic(&self) -> bool {
        matches!(self, TokenType::Plus | TokenType::Minus | TokenType::Times | TokenType::Div)
    }

    /// Identifies hardware locators (`::@`), supporting both dedicated [`TokenType::HardwareLocator`]
    /// and backward-compatible [`TokenType::And`] with lexeme `"::@"`.
    pub fn is_hardware_locator(&self, lexeme: &str) -> bool {
        matches!(self, TokenType::HardwareLocator)
            || (matches!(self, TokenType::And) && lexeme == "::@")
    }

    /// Checks if a string identifier represents a causal state-prime ($S \to S'$).
    pub fn is_state_prime_name(name: &str) -> bool {
        name.ends_with('`') || name.ends_with('\'')
    }

    /// Returns the stripped canonical base name without state-prime notation.
    pub fn strip_state_prime(name: &str) -> &str {
        if let Some(stripped) = name.strip_suffix('`') {
            stripped
```

```
        } else if let Some(stripped) = name.strip_suffix('\'') {
            stripped
        } else {
            name
        }
    }
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Token Taxonomy Unit Proofs & Morphemic Invariant Tests )
// ============================================================================
#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_token_construction_and_eof() {
        let tok = Token::new(TokenType::Identifier("Character`".into()), "Character`", 1, 5);
        assert_eq!(tok.line, 1);
        assert_eq!(tok.col, 5);
        assert_eq!(tok.lexeme, "Character`");
        assert!(tok.is_state_prime());
        assert!(!tok.is_eof());

        let eof = Token::eof(10, 1);
        assert!(eof.is_eof());
    }

    #[test]
    fn test_hardware_locator_identification() {
        let dedicated = Token::new(TokenType::HardwareLocator, "::@", 1, 1);
        assert!(dedicated.is_hardware_locator());

        let legacy = Token::new(TokenType::And, "::@", 1, 1);
        assert!(legacy.is_hardware_locator());

        let regular_and = Token::new(TokenType::And, "::", 1, 1);
        assert!(!regular_and.is_hardware_locator());
    }

    #[test]
    fn test_state_prime_stripping() {
        assert_eq!(TokenType::strip_state_prime("Character`"), "Character");
        assert_eq!(TokenType::strip_state_prime("Cell'"), "Cell");
        assert_eq!(TokenType::strip_state_prime("Static"), "Static");
    }

    #[test]
    fn test_token_category_predicates() {
        assert!(TokenType::LBracket.is_open_boundary());
        assert!(TokenType::RBracket.is_close_boundary());
        assert!(TokenType::ActUpon.is_directional_vector());
        assert!(TokenType::InvariantEquivalence.is_relational());
        assert!(TokenType::Plus.is_arithmetic());
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/README.md MD 229 LINES 1814 WORDS 13.4 KB

```
# OmniCode AST (Abstract Syntax Tree) Subsystem

> *"And he gave unto Moses, when he had made an end of communing with him upon mount Sinai, two tables of testimony, tables of stone, written with the finger of God."*
> — **Exodus 31:18**
>
> *"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house."*
> — **Proverbs 24:27**
>
> *"Remove not the ancient landmark, which thy fathers have set."*
> — **Proverbs 22:28**
>
> *"He telleth the number of the stars; he calleth them all by their names."*
> — **Psalm 147:4**

---

## 1. Architectural Philosophy: The Structural Skeleton of OmniCode

In the OmniCode ecosystem, code is not an arbitrary string of characters or an impermanent script; it is a **covenantal inscription of structured thought**. Just as an organic body grows from an invariant skeletal scaffold before tissue, muscle, and skin are molded onto it ("fleshing out the bones"), the OmniCode compilation pipeline constructs an **Abstract Syntax Tree (AST)** that represents the immutable architecture of human-machine communication.

The AST subsystem in **Track 1 (Host Engine & Virtual Machine)** provides the unified, type-safe data model that bridges:

1. **The Parsing Pipeline (`src/parser/`)**: Ingests declarative source reels (`.omni`) and procedural process tapes (`.tape`).
2. **The Evaluator Runtime (`src/runtime/evaluator/`)**: Executes expressions, resolves causal vectors, verifies invariants, and manages transactional rollbacks.
3. **The Assembler & Transpiler (`src/runtime/assembler/`)**: Lowers high-level AST constructs into 64-bit balanced ternary machine words and transpiles them into standalone C and Lua targets.
4. **CPI-SI (Covenant Partnered Intelligence - Structural Intelligence)**: Embeds intelligent reasoning, contextual intent, and analogy-based linking directly into the syntax of the language.

---

## 2. Taxonomic Subsystem Organization

The AST subsystem is organized into seven modular domains under `src/ast/nodes/`, unified by the master enumeration `ASTNode` in `src/ast/nodes/mod.rs`:

```bash
src/ast/
├── mod.rs                      <-- Subsystem manifest and universal re-exports
├── README.md                   <-- Architectural manifesto and documentation
└── nodes/
    ├── mod.rs                  <-- Unified ASTNode enum and integration tests
    ├── boundaries.rs           <-- First-class asides, boundary frames, and topological casts
    ├── primitives.rs           <-- Scalar arithmetic, affix polarities, and unary inversions
    ├── relations.rs            <-- Relations of being, causal directional vectors, connectives
    ├── structural.rs           <-- Programs, modules, tapes, 4-block sections, rolls, commit gates
    ├── cardinal.rs             <-- Six Cardinal Interrogatives (WHO, WHAT, WHEN, WHERE, WHY, HOW)
    ├── operational.rs          <-- SVO Action Verbs, adversative guards, hardware locators
    └── ontological.rs          <-- Invariant types, entities, analogies, substrates, exemplars
```

---

3. The Seven Taxonomic Domains

Domain 1: Boundaries & First-Class Asides (`boundaries.rs`)

Boundaries are the first-class topological containers of OmniCode. Rather than using arbitrary parentheses or curly braces, every delimiter carries an ontological ranking:

Delimiter	Boundary Type	Semantics & Hardware Footprint
`[ ... ]`	**Denotation**	Physical allocation, concrete hardware address, fixed memory container.
`{ ... }`	**Connotation**	Behavioral context, dynamic execution scope, conceptual state.
`< ... >`	**Invariant**	Immutable covenant, compile-time verified truth, permanent constraint.
`{ ... ]`	**Top-Down**	Imposition of form onto physical matter (e.g. allocating memory).
`[ ... }`	**Bottom-Up**	Emergence of meaning from physical silicon (e.g. reading a sensor).
`( ... )`	**Aside**	Cognitive intent, machine reasoning, and epistemic commentary.
```

```
#### First-Class Cognitive Asides

Asides `( ... )` are not discarded comments! They are preserved in the AST (`AsideNode`), compiled into episodic memory scrolls (`.scroll`), and evaluated by the AI Partner (CPI-SI) to verify that the runtime actions align with the programmer's stated intent.

---

### Domain 2: Primitives & Polarity Affixes (`primitives.rs`)

Governs scalar arithmetic and the fundamental duality between abstract archetypes and concrete instances:

* **`ArithmeticNode`**: Binary mathematical operations (`+`, `-`, `*`, `/`). Division by zero is trapped as `QuadState::Halt` (NULL), preserving balanced equilibrium without crashing.
* **`UnaryNotNode`**: Algebraic truth inversion (`! expr` or `-- expr`).
* **`PolarityNode`**: Attaches an abstract (`+`) or concrete (`-`) bias to an identifier:
  * `+Cell`: The abstract blueprint or type specification of a Cell (zero-cost allocation).
  * `-Cell`: A physical, allocated, memory-backed instance of a Cell in silicon.
* **`BoundaryCastNode`**: Explicit transmutations between boundary domains (e.g. `[+]` or `{-}`).

---

### Domain 3: Relations, Directional Vectors & Connectives (`relations.rs`)

Governs the 3D computational coordinate system and formal logical connectives:

#### The Relational Matrix (`RelationNode`)

Evaluates state, identity, and similarity along the Ontological Y-Axis:

* **`=` (`BeingRelation::Is`)**: Exact identity or equivalence ($A = B$).
* **`!=` (`BeingRelation::IsNot`)**: Ontological distinction and inequality ("not to be").
* **`=!` (`BeingRelation::ToBeNot`)**: State predicate denial and negation ("is not" / to be not).
* **`=~` / `~=` (`BeingRelation::ToBeLike`)**: Structural analogy, homomorphism, or duck typing ("liken to").
* **`<=>` (`BeingRelation::Equivalence`)**: Bijective transduction across dual substrates (e.g. `65 <=> [ -1, +1, +1, -1, +1 ]`).
* **`<`, `>`, `<=`, `>=`**: Bounded comparisons across contexts and cell limits.

#### The Causal Directional Vectors (`DirectionalNode`)

Drives causal energy and data flow across time, scale, and spatial dimensions:

* **`-->` / `->` (`DirectionalVector::ActUpon`)**: Forward temporal causation and pipeline emission.
* **`<--` / `<-` (`DirectionalVector::ActAgain`)**: Retroactive feedback, retry, and transaction rollback.
* **`--^` / `-^` (`DirectionalVector::BuildsTo`)**: Ascending synthesis and architectural abstraction.
* **`--v` / `-v` (`DirectionalVector::BreaksDownFrom`)**: Descending decomposition and compiler lowering to IR.

#### The Connective Matrix (`ConnectiveNode`)

* **`::` (`Connective::And`)**: Cumulative simultaneous conjunction ($A \land B$).
* **`!` (`Connective::But`)**: Adversative caveat gate. If caveat $B$ fails, transaction $A$ is automatically rolled back.
* **`|` (`Connective::Or`)**: Disjunction with short-circuit evaluation.
* **`--` (`Connective::Not`)**: Balanced ternary truth inversion.
* **`:` (`Connective::InRelationTo`)**: Role classification and module import resolution.

---

### Domain 4: Structural Architecture (`structural.rs`)

Enforces the canonical 4-Block file architecture across the ecosystem:

* **`ProgramNode`**: Complete executable reel or tape stream.
* **`ModuleNode`**: Root module header declarations in `.omni` source reels.
* **`TapeNode`**: Process tape declarations in `.tape` operational files.
* **`SectionNode`**: The four canonical architectural blocks:
  1. **Block 1 (Metadata)**: Invariant declarations, author identity, and scripture witness.
  2. **Block 2 (Opening)**: Memory mounting, hardware locators, and bridge configurations.
  3. **Block 3 (Body)**: Sequential operational rolls driving state transformation.
  4. **Block 4 (Closing)**: Verification seals, tripwire tests, and commit gates.
* **`RollNode`**: An atomic procedural transaction: `[ ROLL N ] : [ Intent ] : Action ( Aside )`.
* **`CommitStatusNode`**: The closing gate asserting fourfold equilibrium (`PROCEED`, `AWAIT`, `ROLLBACK`, `HALT`).

---

### Domain 5: Cardinal Interrogatives (`cardinal.rs`)
```

Enables natural machine-operator dialogue and process tape headers through the Six Cardinal Interrogatives (`CardinalClauseNode`):

1. **`WHO`**: The Agent, Subject, Authority, or Module initiating the work.
2. **`WHAT`**: The Direct Object, Substance, or Data Payload being transformed.
3. **`WHEN`**: The Temporal Trigger, Clock Tick, or Execution Precondition.
4. **`WHERE`**: The Spatial Domain, Hardware Address, or Cell Space partition.
5. **`WHY`**: The Teleological Intent, Machine Reasoning, or Invariant Covenant.
6. **`HOW`**: The Modal Vector, Execution Status, or Velocity (+1, 0, NULL, -1).

Domain 6: Operational SVO Verbs & Guards (`operational.rs`)

Models active computation as Subject-Verb-Object (SVO) sentences:

* **`VerbNode`**: Action execution: `Subject --> VERB Object = Target`:
  * **`INSCRIBE`**: Writes an external or source value into a target cell.
  * **`TRANSDUCE`**: Bijectively translates values across dual substrates (bits $\iff$ trits).
  * **`GUARD`**: Asserts invariant equilibrium under adversative caveats.
  * **`PROJECT`**: Emits internal memory state to an external display, terminal, or port.
  * **`SEQUENCE`**: Chains discrete atomic cells into a continuous text ribbon.
* **`GuardNode`**: Adversative checkpoint asserting state integrity before advancing.
* **`HardwareLocatorNode`**: MMIO bus binding: `Target ::@ Address` (e.g. `[ Terminal Stdout ] ::@ 0x01`).

Domain 7: Ontological Typology, Analogies & Substrates (`ontological.rs`)

Defines the mathematical nature of types and memory substrates:

* **`InvariantTypeNode`**: Declarative definition of eternal types (e.g. `< Character >`, `< Number >`).
* **`EntityNode`**: Concrete typed instance bounded by an invariant type and physical substrate.
* **`AnalogyNode`**: Four-term proportional analogy (`A : B :: C : D`), the foundation of CPI-SI relational reasoning.
* **`SubstrateNode`**: Dual-substrate definition pairing physical binary silicon bits with virtual balanced ternary trits.
* **`ExemplarNode`**: Canonical mapping between integer scalars and balanced trits (`65 <=> [ -1, +1, +1, -1, +1 ]`). Includes automated verification via Horner power expansion.

---

4. The Dual-Rail Balanced Ternary Substrate

A cornerstone of OmniCode is the **dual-rail balanced ternary substrate**. In physical silicon, every virtual trit requires two binary physical rails (`pos_rail` and `neg_rail`) to encode four discrete truth states:

$$\mathbb{T}_4 = \{ \text{Await} (0), \text{Proceed} (+1), \text{Rollback} (-1), \text{Halt} (\text{NULL}) \}$$

```text
Rail Bit-Plane Layout (2 bits per virtual trit):
  pos_rail bit:  0   1   0   1
  neg_rail bit:  0   0   1   1
  ----------------------------
  Encoded State: 00  01  10  11
  Semantics:     0   +1  -1  NULL / Collision Trap
```

Key Mathematical Properties in the AST Subsystem

1. **Zero-Cost SIMD Rail-Swap**: Inverting a balanced ternary state or register requires no arithmetic ALU operations; it is a single SIMD register swap between the positive and negative bit-planes:
   $$\text{Swap}(P^+, P^-) \implies +1 \longleftrightarrow -1, \quad 0 \longleftrightarrow 0, \quad \text{NULL} \longleftrightarrow \text{NULL}$$
2. **Instant Hardware Collision Detection**: If both positive and negative rails are asserted simultaneously (`pos & neg != 0`), the hardware immediately traps the collision as a `NULL` fault, preventing illegal memory corruption.

---

5. State vs. Literal Disambiguation

The AST strictly distinguishes between **Equilibrium States** and **Literal Numeric Values**:

* **Equilibrium State (`0:AWAIT`)**: Represents dynamic neutrality, asynchronous standby, or an idling execution thread. Represented in the AST as `ASTNode::Ternary(QuadState::Await)`.
* **Air-Quoted Literal Value (`"0"` or `{ 0 }`)**: Represents the discrete scalar number zero (0.0). Represented in the AST as `ASTNode::Number(0.0)` or enclosed within a boundary.
* **Atomic Glyph (`'0'`)**: Represents the discrete 1-Cell character rune (ASCII 48 / trits `[0, 1, -1, -1, 1]`).

```
---

## 6. Readiness for the Next Modularization Phase

With the completion of the `universal/`, `character/`, and `number/` type modularizations in Track 2, the AST subsystem is now fully equipped with:

* Support for the complete connective and relation matrix (`::`, `!`, `|`, `--`, `!=`, `=!`, `=~`, `:`).
* First-class dual-rail substrate modeling and packing topologies in `SubstrateNode`.
* Horner-polynomial verification and zero-sum balance tracking in `ExemplarNode`.
* Reversible state kinematics and rail-swap negation in `QuadState`.

### Why We Hold Off on the Container Subsystem

The `container` type (which defines storehouses, arrays, queues, and tree structures) is an **aggregate vessel**. In accordance with Proverbs 24:27 (*"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house"*), a vessel cannot be soundly constructed until every atomic constituent it holds is fully proven:

1. **Universal Substrate**: Dual-rail balanced ternary foundation (*Proven*).
2. **Character**: Atomic 1-Cell glyph (*Proven*).
3. **Number**: Atomic 1-Word scalar (*Proven*).
4. **State / Text / Site**: Primitive execution states, ribbons of characters, and spatial addresses (*Next Phase*).
5. **Container**: The overarching vessel holding all of the above (*Final Aggregation Phase*).

This systematic modularization ensures zero circular dependencies and guarantees that each layer of the language rests upon an unshakeable bedrock of proven invariants.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/mod.rs RS 30 LINES 102 WORDS 1.1 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( AST Subsystem Identity and Export Manifest )
// ============================================================================
//! OmniCode AST Subsystem
//! Houses all syntax tree nodes, boundary containers, and expression shapes.

pub mod nodes;


// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for AST Types )
// ============================================================================
pub use nodes::*;


// ============================================================================
// BLOCK 3: BODY BLOCK
// ( AST Subsystem Manifest Definitions )
// ============================================================================
// AST definitions are actively mapped in nodes.rs.


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Verification & Module Status )
// ============================================================================
// AST subsystem verified and sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/boundaries.rs RS 108 LINES 408 WORDS 3.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( AST Boundary Nodes: Containers, Typology & Intent Asides )
// ============================================================================
// SCRIPTURE ANCHORS & EPISTEMIC WITNESSES:
//   - Exodus 31:18: "written with the finger of God" — Inscription of eternal truth.
//   - Proverbs 24:27: "Prepare thy work without, and make it fit for thyself in the field;
//                      and afterwards build thine house." — Systematic modularization.
//   - Proverbs 22:28: "Remove not the ancient landmark, which thy fathers have set."
//                      — Preservation of invariant boundaries and balanced truth.
// ============================================================================

use crate::ast::nodes::ASTNode;
use crate::core::boundaries::BoundaryType;
use crate::core::operators::Polarity;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( First-Class Asides, Boundary Nodes & Boundary Casts )
// ============================================================================

/// First-class cognitive intent and machine reasoning aside `( ... )`.
#[derive(Debug, Clone, PartialEq)]
pub struct AsideNode {
    pub intent: String,
    pub line: usize,
    pub col: usize,
}

/// Boundary node enclosing child elements within a distinct topological frame:
/// `[...]` (Denotation), `{...}` (Connotation), `<...>` (Invariant),
/// `{...]` (Top-Down Imposition), `[...}` (Bottom-Up Emergence).
#[derive(Debug, Clone, PartialEq)]
pub struct BoundaryNode {
    pub boundary_type: BoundaryType,
    pub elements: Vec<ASTNode>,
    pub aside: Option<AsideNode>,
    pub line: usize,
    pub col: usize,
}

/// Boundary cast operator transmuting polarity or boundary topology.
#[derive(Debug, Clone, PartialEq)]
pub struct BoundaryCastNode {
    pub boundary: BoundaryType,
    pub polarity: Polarity,
    pub line: usize,
    pub col: usize,
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Boundary Constructors, Predicates & Element Accessors )
// ============================================================================

impl AsideNode {
    /// Constructs a new [`AsideNode`].
    pub fn new(intent: impl Into<String>, line: usize, col: usize) -> Self {
        Self {
            intent: intent.into(),
            line,
            col,
        }
    }
}

impl BoundaryNode {
    /// Constructs a new [`BoundaryNode`] with no attached aside.
    pub fn new(boundary_type: BoundaryType, elements: Vec<ASTNode>, line: usize, col: usize) -> Self {
        Self {
            boundary_type,
            elements,
            aside: None,
            line,
```

```
            col,
        }
    }

    /// Attaches a first-class cognitive intent aside to the boundary.
    pub fn with_aside(mut self, aside: AsideNode) -> Self {
        self.aside = Some(aside);
        self
    }

    /// Returns `true` if this boundary is an immutable invariant `< ... >`.
    pub fn is_invariant(&self) -> bool {
        self.boundary_type.is_immutable()
    }
}

impl BoundaryCastNode {
    /// Constructs a new [`BoundaryCastNode`].
    pub fn new(boundary: BoundaryType, polarity: Polarity, line: usize, col: usize) -> Self {
        Self {
            boundary,
            polarity,
            line,
            col,
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Invariant Guarantees & Trait Implementations )
// ============================================================================
// Boundary nodes satisfy Send, Sync, Clone, PartialEq across all substrates.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/cardinal.rs RS 96 LINES 420 WORDS 3.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( AST Cardinal Nodes: Six Cardinal Interrogatives for Operator Dialogue )
// ============================================================================
// SCRIPTURE ANCHORS & EPISTEMIC WITNESSES:
//   - Exodus 31:18: "written with the finger of God" — Inscription of eternal truth.
//   - Proverbs 24:27: "Prepare thy work without, and make it fit for thyself in the field;
//                      and afterwards build thine house." — Systematic modularization.
//   - Proverbs 22:28: "Remove not the ancient landmark, which thy fathers have set."
//                      — Preservation of invariant boundaries and balanced truth.
// ============================================================================

use crate::ast::nodes::ASTNode;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( The 6 Cardinal Interrogatives & Cardinal Clause Definitions )
// ============================================================================

/// The Six Cardinal Interrogatives governing OmniCode process tapes and machine-operator dialog.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum CardinalKind {
    /// WHO: The Agent, Subject, or Authority responsible for the transaction.
    Who,
    /// WHAT: The Direct Object, Inscription Target, or Data Payload.
    What,
    /// WHEN: The Trigger, Event, Clock Tick, or Temporal Precondition.
    When,
    /// WHERE: The Container, Spatial Domain, Memory Address, or Cell Space.
    Where,
    /// WHY: The Teleological Reason, Machine Intent, or Invariant Covenant.
    Why,
    /// HOW: The Modal Vector, Execution Status, or Velocity (+1, 0, NULL, -1).
    How,
}

impl CardinalKind {
    /// Returns the uppercase string keyword for the interrogative.
    pub fn keyword(&self) -> &'static str {
        match self {
            Self::Who => "WHO",
            Self::What => "WHAT",
            Self::When => "WHEN",
            Self::Where => "WHERE",
            Self::Why => "WHY",
            Self::How => "HOW",
        }
    }

    /// Parses a string into a [`CardinalKind`] if matching one of the 6 Interrogatives.
    pub fn from_str_keyword(s: &str) -> Option<Self> {
        match s.to_ascii_uppercase().as_str() {
            "WHO" => Some(Self::Who),
            "WHAT" => Some(Self::What),
            "WHEN" => Some(Self::When),
            "WHERE" => Some(Self::Where),
            "WHY" => Some(Self::Why),
            "HOW" => Some(Self::How),
            _ => None,
        }
    }
}

/// A Cardinal Clause node inside a process tape header or dialogue session:
/// `CARDINAL { Payload } ::` (e.g. `WHO { OmniCode Lexicon } ::`).
#[derive(Debug, Clone, PartialEq)]
pub struct CardinalClauseNode {
    pub kind: CardinalKind,
    pub payload: Box<ASTNode>,
    pub line: usize,
    pub col: usize,
}

// ============================================================================
```

```
// BLOCK 3: BODY BLOCK
// ( Cardinal Constructors & Accessors )
// ================================================================================

impl CardinalClauseNode {
    /// Constructs a new [`CardinalClauseNode`].
    pub fn new(kind: CardinalKind, payload: ASTNode, line: usize, col: usize) -> Self {
        Self {
            kind,
            payload: Box::new(payload),
            line,
            col,
        }
    }
}

// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Invariant Guarantees & Trait Implementations )
// ================================================================================
// Cardinal nodes satisfy Send, Sync, Clone, PartialEq across all targets.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/mod.rs RS 328 LINES 765 WORDS 11.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( AST Unified Node Subsystem: Complete Taxonomic Hierarchy )
// ============================================================================
// SCRIPTURE ANCHORS & EPISTEMIC WITNESSES:
//   - Exodus 31:18: "written with the finger of God" — Inscription of eternal truth.
//   - Proverbs 24:27: "Prepare thy work without, and make it fit for thyself in the field;
//                      and afterwards build thine house." — Systematic modularization.
//   - Proverbs 22:28: "Remove not the ancient landmark, which thy fathers have set."
//                      — Preservation of invariant boundaries and balanced truth.
//
// SUB-MODULE TAXONOMY:
//   - boundaries: First-class asides, boundary frames, and topological casts.
//   - primitives: Scalar arithmetic, affix polarity modifiers, and unary inversions.
//   - relations:  Ontological being relations, directional causal vectors, connectives.
//   - structural: Program reels, Module headers, Process tapes, 4-Block sections, Rolls, Commit gates.
//   - cardinal:   Six Cardinal Interrogatives (WHO, WHAT, WHEN, WHERE, WHY, HOW).
//   - operational: SVO Action Verbs (INSCRIBE, TRANSDUCE, GUARD, PROJECT, SEQUENCE), MMIO locators.
//   - ontological: Invariant type declarations, entities, analogies, substrates, exemplars.
// ============================================================================

pub mod boundaries;
pub mod primitives;
pub mod relations;
pub mod structural;
pub mod cardinal;
pub mod operational;
pub mod ontological;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Universal Re-Exports Across All Taxonomic Sub-Modules )
// ============================================================================

pub use boundaries::*;
pub use primitives::*;
pub use relations::*;
pub use structural::*;
pub use cardinal::*;
pub use operational::*;
pub use ontological::*;

use crate::core::ternary::QuadState;

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Unified ASTNode Enumeration: Complete Multi-Substrate Node Hierarchy )
// ============================================================================

/// Unified AST Node enumeration representing every syntactic, structural,
/// relational, and operational construct in the OmniCode language.
#[derive(Debug, Clone, PartialEq)]
pub enum ASTNode {
    // ------------------------------------------------------------------------
    // 1. First-Class Asides, Literals & Primitives
    // ------------------------------------------------------------------------
    Aside(AsideNode),
    Ternary(QuadState),
    Identifier(String),
    Polarity(PolarityNode),
    BoundaryCast(BoundaryCastNode),
    Number(f64),
    StringLit(String),

    // ------------------------------------------------------------------------
    // 2. Boundary Containers & Concrete Entities
    // ------------------------------------------------------------------------
    Boundary(BoundaryNode),
    Entity(EntityNode),

    // ------------------------------------------------------------------------
    // 3. Relational Algebra, Vectors & Logic
    // ------------------------------------------------------------------------
    Relation(RelationNode),
```

```
    Directional(DirectionalNode),
    Connective(ConnectiveNode),
    Arithmetic(ArithmeticNode),
    UnaryNot(UnaryNotNode),

    // ------------------------------------------------------------------------
    // 4. Macrocosmic Program & 4-Block Section Structure
    // ------------------------------------------------------------------------
    Program(ProgramNode),
    Module(ModuleNode),
    Tape(TapeNode),
    Section(SectionNode),
    Roll(RollNode),
    CommitStatus(CommitStatusNode),

    // ------------------------------------------------------------------------
    // 5. Cardinal Interrogatives (Process Tape Clauses & Dialog)
    // ------------------------------------------------------------------------
    Cardinal(CardinalClauseNode),

    // ------------------------------------------------------------------------
    // 6. Operational SVO Verbs, Adversative Guards & Hardware Locators
    // ------------------------------------------------------------------------
    Verb(VerbNode),
    Guard(GuardNode),
    Hardware(HardwareLocatorNode),

    // ------------------------------------------------------------------------
    // 7. Invariant Ontological Typology, Analogies & Exemplars
    // ------------------------------------------------------------------------
    InvariantType(InvariantTypeNode),
    Analogy(AnalogyNode),
    Substrate(SubstrateNode),
    Exemplar(ExemplarNode),
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Trait Implementations, Send/Sync Invariant Verification & Unit Tests )
// ============================================================================
// All ASTNode variants implement Send, Sync, Clone, PartialEq.

#[cfg(test)]
mod tests {
    use super::*;
    use crate::core::boundaries::BoundaryType;
    use crate::core::operators::{BeingRelation, Connective, DirectionalVector, Polarity, AffixPosition};

    #[test]
    fn test_boundary_nodes_creation_and_asides() {
        let aside = AsideNode::new("Invariant scripture witness", 1, 1);
        assert_eq!(aside.intent, "Invariant scripture witness");

        let bound = BoundaryNode::new(BoundaryType::Denotation, vec![ASTNode::Identifier("Cell".to_string())], 2, 5)
            .with_aside(aside.clone());
        assert_eq!(bound.boundary_type, BoundaryType::Denotation);
        assert_eq!(bound.elements.len(), 1);
        assert_eq!(bound.aside, Some(aside));
    }

    #[test]
    fn test_structural_nodes_sections_rolls_tapes() {
        let roll = RollNode::new(
            1,
            "Inscribe",
            ASTNode::Identifier("ActionPayload".to_string()),
            10,
            1,
        ).with_aside(AsideNode::new("Roll 1 intent", 10, 20));

        assert_eq!(roll.id, 1);
        assert_eq!(roll.label, "Inscribe");
        assert!(roll.aside.is_some());

        let section = SectionNode::new(
            SectionKind::Body,
            vec![ASTNode::Roll(roll)],
            9,
```

```
            1,
        );
        assert_eq!(section.kind, SectionKind::Body);
        assert_eq!(section.elements.len(), 1);

        let tape = TapeNode::new("Character", 1, 1);
        assert_eq!(tape.name, "Character");

        let module = ModuleNode::new("Lexicon", 1, 1);
        assert_eq!(module.name, "Lexicon");
    }

    #[test]
    fn test_cardinal_nodes_interrogatives() {
        let who = CardinalClauseNode::new(
            CardinalKind::Who,
            ASTNode::Identifier("OmniCode Lexicon".to_string()),
            12,
            5,
        );
        assert_eq!(who.kind.keyword(), "WHO");
        assert_eq!(CardinalKind::from_str_keyword("what"), Some(CardinalKind::What));
        assert_eq!(CardinalKind::from_str_keyword("WHEN"), Some(CardinalKind::When));
        assert_eq!(CardinalKind::from_str_keyword("where"), Some(CardinalKind::Where));
        assert_eq!(CardinalKind::from_str_keyword("WHY"), Some(CardinalKind::Why));
        assert_eq!(CardinalKind::from_str_keyword("how"), Some(CardinalKind::How));
    }

    #[test]
    fn test_operational_verbs_and_guards() {
        let verb = VerbNode::new(
            VerbKind::Inscribe,
            Some(ASTNode::Identifier("Glyph".to_string())),
            ASTNode::Identifier("Cell".to_string()),
            Some(ASTNode::Identifier("Character`".to_string())),
            29,
            1,
        );
        assert_eq!(verb.verb.name(), "INSCRIBE");

        let guard = GuardNode::new(
            ASTNode::Ternary(QuadState::Proceed),
            ASTNode::Identifier("ProceedAction".to_string()),
            Some(ASTNode::Identifier("RollbackAction".to_string())),
            45,
            1,
        );
        assert_eq!(*guard.condition, ASTNode::Ternary(QuadState::Proceed));

        let hw = HardwareLocatorNode::new(
            ASTNode::Identifier("Terminal Stdout".to_string()),
            0x01,
            71,
            1,
        );
        assert_eq!(hw.address, 0x01);
    }

    #[test]
    fn test_ontological_invariant_types_and_exemplars() {
        let inv = InvariantTypeNode::new(
            "Character",
            ASTNode::Identifier("Idea { Type }".to_string()),
            25,
            1,
        );
        assert_eq!(inv.name, "Character");

        let exemplar = ExemplarNode::new(
            Some("Exemplar 'A'".to_string()),
            65,
            vec![-1, 1, 1, -1, 1],
            42,
            1,
        );
        assert_eq!(exemplar.scalar, 65);
        assert_eq!(exemplar.trits, vec![-1, 1, 1, -1, 1]);
        assert!(exemplar.verify_scalar());
```

```
        assert_eq!(exemplar.sum_trits(), 1);

        let substrate = SubstrateNode::new(8, 5, 33, 1)
            .with_topology("SymmetricInteger");
        assert_eq!(substrate.physical_bits, 8);
        assert_eq!(substrate.virtual_trits, 5);
        assert!(substrate.is_dual_rail());
        assert_eq!(substrate.topology(), Some("SymmetricInteger"));
    }

    #[test]
    fn test_primitives_and_relations() {
        let arith = ArithmeticNode::new(
            ASTNode::Number(1.0),
            ArithmeticOp::Add,
            ASTNode::Number(2.0),
            1,
            1,
        );
        assert_eq!(arith.op.symbol(), "+");

        let pol = PolarityNode::new(
            "proceed",
            Polarity::Abstract,
            AffixPosition::Prefix,
            1,
            1,
        );
        assert_eq!(pol.formatted(), "+proceed");

        let rel = RelationNode::new(
            ASTNode::Identifier("A".to_string()),
            BeingRelation::Is,
            ASTNode::Identifier("B".to_string()),
            1,
            1,
        );
        assert_eq!(rel.relation, BeingRelation::Is);
        assert!(rel.is_identity());

        let rel_not = RelationNode::new(
            ASTNode::Identifier("X".to_string()),
            BeingRelation::ToBeNot,
            ASTNode::Identifier("Y".to_string()),
            1,
            1,
        );
        assert!(rel_not.is_negation());

        let dir = DirectionalNode::new(
            ASTNode::Identifier("Source".to_string()),
            DirectionalVector::ActUpon,
            ASTNode::Identifier("Target".to_string()),
            1,
            1,
        );
        assert_eq!(dir.vector, DirectionalVector::ActUpon);

        let conn = ConnectiveNode::new(
            ASTNode::Identifier("Left".to_string()),
            Connective::And,
            ASTNode::Identifier("Right".to_string()),
            1,
            1,
        );
        assert_eq!(conn.connective, Connective::And);
        assert!(conn.is_conjunction());

        let conn_but = ConnectiveNode::new(
            ASTNode::Identifier("A".to_string()),
            Connective::But,
            ASTNode::Identifier("B".to_string()),
            1,
            1,
        );
        assert!(conn_but.is_adversative());
    }

```

```
    #[test]
    fn test_send_sync_invariants() {
        fn assert_send_sync<T: Send + Sync>() {}
        assert_send_sync::<ASTNode>();
        assert_send_sync::<AsideNode>();
        assert_send_sync::<BoundaryNode>();
        assert_send_sync::<ProgramNode>();
        assert_send_sync::<ModuleNode>();
        assert_send_sync::<TapeNode>();
        assert_send_sync::<SectionNode>();
        assert_send_sync::<RollNode>();
        assert_send_sync::<CardinalClauseNode>();
        assert_send_sync::<VerbNode>();
        assert_send_sync::<GuardNode>();
        assert_send_sync::<HardwareLocatorNode>();
        assert_send_sync::<InvariantTypeNode>();
        assert_send_sync::<ExemplarNode>();
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/ontological.rs RS 235 LINES 862 WORDS 7.2 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( AST Ontological Nodes: Invariant Types, Entities, Analogies & Exemplars )
// ================================================================================
// SCRIPTURE ANCHORS & EPISTEMIC WITNESSES:
//   - Exodus 31:18: "written with the finger of God" — Inscription of eternal truth.
//   - Proverbs 24:27: "Prepare thy work without, and make it fit for thyself in the field;
//                      and afterwards build thine house." — Systematic modularization.
//   - Proverbs 22:28: "Remove not the ancient landmark, which thy fathers have set."
//                      — Preservation of invariant boundaries and balanced truth.
// ================================================================================

use crate::ast::nodes::boundaries::{AsideNode, BoundaryNode};
use crate::ast::nodes::ASTNode;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Ontological Type, Entity & Epistemic Ratio Node Definitions )
// ================================================================================

/// Concrete typed entity allocated in memory:
/// `[ Name ]: < Invariant > & [ Substrate ] ( Aside ) { Context }`.
#[derive(Debug, Clone, PartialEq)]
pub struct EntityNode {
    pub name: String,
    pub definition: BoundaryNode,
    pub aside: Option<AsideNode>,
    pub context: Option<BoundaryNode>,
    pub line: usize,
    pub col: usize,
}

/// Freestanding Invariant Type definition:
/// `< Character > = < Idea { Type } > & [ Noun { Atomic Glyph } ] ( Aside ) { Invariants }`.
#[derive(Debug, Clone, PartialEq)]
pub struct InvariantTypeNode {
    pub name: String,
    pub category: Box<ASTNode>,
    pub aside: Option<AsideNode>,
    pub invariants: Vec<ASTNode>,
    pub line: usize,
    pub col: usize,
}

/// Ontological Proportion / Analogy node:
/// `[ Character ] : [ Text ] :: [ Trit ] : [ Word ]`.
#[derive(Debug, Clone, PartialEq)]
pub struct AnalogyNode {
    pub left_subject: Box<ASTNode>,
    pub left_context: Box<ASTNode>,
    pub right_subject: Box<ASTNode>,
    pub right_context: Box<ASTNode>,
    pub line: usize,
    pub col: usize,
}

/// Dual Substrate definition (Physical Silicon Bits & Virtual Balanced Trits):
/// `[ 1 Byte { 8 Bits } ] & [ 1 Cell { 5 Trits } ]` (Character: 1 Byte <=> 1 Cell)
/// `[ 8 Bytes { 64 Bits } ] & [ 1 Word { 27 Trits } ]` (Number: 8 Bytes <=> 1 Word).
#[derive(Debug, Clone, PartialEq)]
pub struct SubstrateNode {
    pub physical_bits: usize,
    pub virtual_trits: usize,
    pub is_dual_rail: bool,
    pub topology: Option<String>,
    pub line: usize,
    pub col: usize,
}

/// Canonical Exemplar mapping an integer scalar to balanced trits:
/// `65 <=> [ -1, +1, +1, -1, +1 ]` (Exemplar 'A').
#[derive(Debug, Clone, PartialEq)]
pub struct ExemplarNode {
    pub label: Option<String>,
```

```rust
    pub scalar: i64,
    pub trits: Vec<i8>,
    pub line: usize,
    pub col: usize,
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Ontological Constructors & Accessors )
// ============================================================================

impl EntityNode {
    /// Constructs a new [`EntityNode`].
    pub fn new(name: impl Into<String>, definition: BoundaryNode, line: usize, col: usize) -> Self {
        Self {
            name: name.into(),
            definition,
            aside: None,
            context: None,
            line,
            col,
        }
    }

    /// Attaches an intent aside to this entity.
    pub fn with_aside(mut self, aside: AsideNode) -> Self {
        self.aside = Some(aside);
        self
    }

    /// Attaches an ontological context boundary to this entity.
    pub fn with_context(mut self, context: BoundaryNode) -> Self {
        self.context = Some(context);
        self
    }
}

impl InvariantTypeNode {
    /// Constructs a new [`InvariantTypeNode`].
    pub fn new(name: impl Into<String>, category: ASTNode, line: usize, col: usize) -> Self {
        Self {
            name: name.into(),
            category: Box::new(category),
            aside: None,
            invariants: Vec::new(),
            line,
            col,
        }
    }

    /// Attaches an intent aside to this invariant type.
    pub fn with_aside(mut self, aside: AsideNode) -> Self {
        self.aside = Some(aside);
        self
    }
}

impl AnalogyNode {
    /// Constructs a new 4-term ontological analogy proportion.
    pub fn new(
        left_subject: ASTNode,
        left_context: ASTNode,
        right_subject: ASTNode,
        right_context: ASTNode,
        line: usize,
        col: usize,
    ) -> Self {
        Self {
            left_subject: Box::new(left_subject),
            left_context: Box::new(left_context),
            right_subject: Box::new(right_subject),
            right_context: Box::new(right_context),
            line,
            col,
        }
    }
}

```

```rust
impl SubstrateNode {
    /// Constructs a new dual-substrate node with dual-rail enabled.
    pub fn new(
        physical_bits: usize,
        virtual_trits: usize,
        line: usize,
        col: usize,
    ) -> Self {
        Self {
            physical_bits,
            virtual_trits,
            is_dual_rail: true,
            topology: None,
            line,
            col,
        }
    }

    /// Configures the dual-rail balanced ternary mode.
    pub fn with_dual_rail(mut self, dual_rail: bool) -> Self {
        self.is_dual_rail = dual_rail;
        self
    }

    /// Attaches a radix-3 packing topology.
    pub fn with_topology(mut self, topology: impl Into<String>) -> Self {
        self.topology = Some(topology.into());
        self
    }

    /// Returns `true` if this substrate utilizes dual-rail silicon mapping.
    pub fn is_dual_rail(&self) -> bool {
        self.is_dual_rail
    }

    /// Returns the optional packing topology string slice.
    pub fn topology(&self) -> Option<&str> {
        self.topology.as_deref()
    }
}

impl ExemplarNode {
    /// Constructs a new canonical exemplar mapping.
    pub fn new(
        label: Option<String>,
        scalar: i64,
        trits: Vec<i8>,
        line: usize,
        col: usize,
    ) -> Self {
        Self {
            label,
            scalar,
            trits,
            line,
            col,
        }
    }

    /// Verifies that the Horner expansion of trits matches the scalar value:
    /// `sum_{i=0..N-1} trits[i] * 3^i == scalar`.
    pub fn verify_scalar(&self) -> bool {
        let mut total: i64 = 0;
        let mut multiplier: i64 = 1;
        for &t in &self.trits {
            total += (t as i64) * multiplier;
            multiplier *= 3;
        }
        total == self.scalar
    }

    /// Computes the net zero-sum balance of trits: `sum(trits)`.
    pub fn sum_trits(&self) -> i64 {
        self.trits.iter().map(|&t| t as i64).sum()
    }
}

// ============================================================================
```

```
// BLOCK 4: CLOSING BLOCK
// ( Invariant Guarantees & Trait Implementations )
// ================================================================================
// Ontological nodes satisfy Send, Sync, Clone, PartialEq across all targets.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/operational.rs RS | 158 LINES | 564 WORDS | 5.2 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( AST Operational Nodes: SVO Verbs, Adversative Guards & Hardware Locators )
// ============================================================================
// SCRIPTURE ANCHORS & EPISTEMIC WITNESSES:
//   - Exodus 31:18: "written with the finger of God" — Inscription of eternal truth.
//   - Proverbs 24:27: "Prepare thy work without, and make it fit for thyself in the field;
//                      and afterwards build thine house." — Systematic modularization.
//   - Proverbs 22:28: "Remove not the ancient landmark, which thy fathers have set."
//                      — Preservation of invariant boundaries and balanced truth.
// ============================================================================

use crate::ast::nodes::ASTNode;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Operational Action Node Definitions: SVO Verbs, Guards & Hardware Locators )
// ============================================================================

/// Canonical SVO Action Verbs in the OmniCode runtime grammar.
#[derive(Debug, Clone, PartialEq, Eq, Hash)]
pub enum VerbKind {
    /// INSCRIBE: Imposes an external or source value into a target cell.
    Inscribe,
    /// TRANSDUCE: Maps values bijectively across dual substrates (bits <=> trits).
    Transduce,
    /// GUARD: Asserts invariant equilibrium under adversative caveats.
    Guard,
    /// PROJECT: Projects internal state into an external target buffer or screen.
    Project,
    /// SEQUENCE: Chains discrete cells outward into a continuous text ribbon.
    Sequence,
    /// User-defined or extensible domain action verb.
    Custom(String),
}

impl VerbKind {
    /// Parses an uppercase identifier into an action verb kind.
    pub fn from_name(name: &str) -> Self {
        match name.to_ascii_uppercase().as_str() {
            "INSCRIBE" => Self::Inscribe,
            "TRANSDUCE" => Self::Transduce,
            "GUARD" => Self::Guard,
            "PROJECT" => Self::Project,
            "SEQUENCE" => Self::Sequence,
            other => Self::Custom(other.to_string()),
        }
    }

    /// Returns the uppercase verb name string.
    pub fn name(&self) -> &str {
        match self {
            Self::Inscribe => "INSCRIBE",
            Self::Transduce => "TRANSDUCE",
            Self::Guard => "GUARD",
            Self::Project => "PROJECT",
            Self::Sequence => "SEQUENCE",
            Self::Custom(s) => s.as_str(),
        }
    }
}

/// SVO Action Verb execution node:
/// `Subject --> VERB Object = Target` (e.g. `{ Glyph ] --> INSCRIBE [ Cell ] = [ Character` ]`).
#[derive(Debug, Clone, PartialEq)]
pub struct VerbNode {
    pub verb: VerbKind,
    pub subject: Option<Box<ASTNode>>,
    pub object: Box<ASTNode>,
    pub target: Option<Box<ASTNode>>,
    pub line: usize,
    pub col: usize,
}

```

```rust
/// Adversative Guard assertion node:
/// `Condition ! GUARD --> ProceedBranch | FallbackBranch`.
#[derive(Debug, Clone, PartialEq)]
pub struct GuardNode {
    pub condition: Box<ASTNode>,
    pub on_proceed: Box<ASTNode>,
    pub on_fallback: Option<Box<ASTNode>>,
    pub line: usize,
    pub col: usize,
}

/// MMIO Hardware Bus locator node:
/// `Target ::@ Address` (e.g. `[ Terminal Stdout ] ::@ 0x01`).
#[derive(Debug, Clone, PartialEq)]
pub struct HardwareLocatorNode {
    pub target: Box<ASTNode>,
    pub address: u64,
    pub line: usize,
    pub col: usize,
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Operational Constructors & Methods )
// ============================================================================

impl VerbNode {
    /// Constructs a new [`VerbNode`].
    pub fn new(
        verb: VerbKind,
        subject: Option<ASTNode>,
        object: ASTNode,
        target: Option<ASTNode>,
        line: usize,
        col: usize,
    ) -> Self {
        Self {
            verb,
            subject: subject.map(Box::new),
            object: Box::new(object),
            target: target.map(Box::new),
            line,
            col,
        }
    }
}

impl GuardNode {
    /// Constructs a new [`GuardNode`].
    pub fn new(
        condition: ASTNode,
        on_proceed: ASTNode,
        on_fallback: Option<ASTNode>,
        line: usize,
        col: usize,
    ) -> Self {
        Self {
            condition: Box::new(condition),
            on_proceed: Box::new(on_proceed),
            on_fallback: on_fallback.map(Box::new),
            line,
            col,
        }
    }
}

impl HardwareLocatorNode {
    /// Constructs a new [`HardwareLocatorNode`].
    pub fn new(target: ASTNode, address: u64, line: usize, col: usize) -> Self {
        Self {
            target: Box::new(target),
            address,
            line,
            col,
        }
    }
}

```

```
// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Invariant Guarantees & Trait Implementations )
// ================================================================================
// Operational nodes satisfy Send, Sync, Clone, PartialEq across all targets.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/primitives.rs RS 125 LINES 445 WORDS 4.1 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( AST Primitive Nodes: Arithmetic, Polarity & Unary Inversion )
// ============================================================================
// SCRIPTURE ANCHORS & EPISTEMIC WITNESSES:
//   - Exodus 31:18: "written with the finger of God" — Inscription of eternal truth.
//   - Proverbs 24:27: "Prepare thy work without, and make it fit for thyself in the field;
//                      and afterwards build thine house." — Systematic modularization.
//   - Proverbs 22:28: "Remove not the ancient landmark, which thy fathers have set."
//                      — Preservation of invariant boundaries and balanced truth.
// ============================================================================

use crate::ast::nodes::ASTNode;
use crate::core::operators::{AffixPosition, Polarity};

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Binary Arithmetic Operators, Arithmetic Nodes & Polarity Modifiers )
// ============================================================================

/// Discrete arithmetic operations supported on scalar values.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum ArithmeticOp {
    Add,
    Sub,
    Mul,
    Div,
}

impl ArithmeticOp {
    /// Returns the canonical mathematical operator symbol.
    pub fn symbol(&self) -> &'static str {
        match self {
            Self::Add => "+",
            Self::Sub => "-",
            Self::Mul => "*",
            Self::Div => "/",
        }
    }
}

/// Binary arithmetic evaluation node: `left OP right`.
#[derive(Debug, Clone, PartialEq)]
pub struct ArithmeticNode {
    pub left: Box<ASTNode>,
    pub op: ArithmeticOp,
    pub right: Box<ASTNode>,
    pub line: usize,
    pub col: usize,
}

/// Unary logical/ternary inversion node: `! operand`.
#[derive(Debug, Clone, PartialEq)]
pub struct UnaryNotNode {
    pub operand: Box<ASTNode>,
    pub line: usize,
    pub col: usize,
}

/// Affixed polarity modifier indicating abstract or concrete bias: `+name` or `-name`.
#[derive(Debug, Clone, PartialEq)]
pub struct PolarityNode {
    pub name: String,
    pub polarity: Polarity,
    pub position: AffixPosition,
    pub line: usize,
    pub col: usize,
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Primitive Node Constructors & Operational Helpers )
// ============================================================================

```

```
impl ArithmeticNode {
    /// Constructs a new binary arithmetic node.
    pub fn new(left: ASTNode, op: ArithmeticOp, right: ASTNode, line: usize, col: usize) -> Self {
        Self {
            left: Box::new(left),
            op,
            right: Box::new(right),
            line,
            col,
        }
    }
}

impl UnaryNotNode {
    /// Constructs a new unary inversion node.
    pub fn new(operand: ASTNode, line: usize, col: usize) -> Self {
        Self {
            operand: Box::new(operand),
            line,
            col,
        }
    }
}

impl PolarityNode {
    /// Constructs a new polarity-modified entity node.
    pub fn new(name: impl Into<String>, polarity: Polarity, position: AffixPosition, line: usize, col: usize) -> Self {
        Self {
            name: name.into(),
            polarity,
            position,
            line,
            col,
        }
    }

    /// Returns the formatted symbol representation with its affix.
    pub fn formatted(&self) -> String {
        match self.position {
            AffixPosition::Prefix => format!("{}{}", self.polarity.symbol(), self.name),
            AffixPosition::Postfix => format!("{}{}", self.name, self.polarity.symbol()),
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Invariant Guarantees & Trait Implementations )
// ============================================================================
// Primitive nodes satisfy Send, Sync, Clone, PartialEq across all targets.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/relations.rs RS 169 LINES 594 WORDS 5.3 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( AST Relational Nodes: Being Relations, Directional Vectors & Connectives )
// ================================================================================
// SCRIPTURE ANCHORS & EPISTEMIC WITNESSES:
//   - Exodus 31:18: "written with the finger of God" — Inscription of eternal truth.
//   - Proverbs 24:27: "Prepare thy work without, and make it fit for thyself in the field;
//                      and afterwards build thine house." — Systematic modularization.
//   - Proverbs 22:28: "Remove not the ancient landmark, which thy fathers have set."
//                      — Preservation of invariant boundaries and balanced truth.
// ================================================================================

use crate::ast::nodes::ASTNode;
use crate::core::operators::{BeingRelation, Connective, DirectionalVector};

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Relational, Directional & Connective Structural Node Definitions )
// ================================================================================

/// Relational node evaluating ontological identity, state, equivalence:
/// `left RELATION right` (`=`, `!=`, `=!`, `~=`, `<=>`, `<`, `>`, `<=`, `>=`).
#[derive(Debug, Clone, PartialEq)]
pub struct RelationNode {
    pub left: Box<ASTNode>,
    pub relation: BeingRelation,
    pub right: Box<ASTNode>,
    pub line: usize,
    pub col: usize,
}

/// Directional causal propagation node driving energy and state across boundaries:
/// `source VECTOR target` (`-->`, `<--`, `--^`, `--v`, `->`, `<-`).
#[derive(Debug, Clone, PartialEq)]
pub struct DirectionalNode {
    pub source: Box<ASTNode>,
    pub vector: DirectionalVector,
    pub target: Box<ASTNode>,
    pub line: usize,
    pub col: usize,
}

/// Connective node conjoining or disjoining expressions through formal logic:
/// `left CONNECTIVE right` (`::` And, `!` But, `|` Or, `--` Not, `:` InRelationTo).
#[derive(Debug, Clone, PartialEq)]
pub struct ConnectiveNode {
    pub left: Box<ASTNode>,
    pub connective: Connective,
    pub right: Box<ASTNode>,
    pub line: usize,
    pub col: usize,
}

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Relational Constructors & Query Helpers )
// ================================================================================

impl RelationNode {
    /// Constructs a new relational node.
    pub fn new(
        left: ASTNode,
        relation: BeingRelation,
        right: ASTNode,
        line: usize,
        col: usize,
    ) -> Self {
        Self {
            left: Box::new(left),
            relation,
            right: Box::new(right),
            line,
            col,
        }
```

```rust
    }

    /// Returns `true` if this is an identity relation (`=`).
    pub fn is_identity(&self) -> bool {
        self.relation == BeingRelation::Is
    }

    /// Returns `true` if this is a negative relation (`!=` or `=!`).
    pub fn is_negation(&self) -> bool {
        matches!(
            self.relation,
            BeingRelation::IsNot | BeingRelation::ToBeNot
        )
    }

    /// Returns `true` if this is an analogical likeness relation (`~=`).
    pub fn is_likeness(&self) -> bool {
        self.relation == BeingRelation::ToBeLike
    }

    /// Returns `true` if this is invariant equivalence (`<=>`).
    pub fn is_equivalence(&self) -> bool {
        self.relation == BeingRelation::Equivalence
    }
}

impl DirectionalNode {
    /// Constructs a new directional vector node.
    pub fn new(
        source: ASTNode,
        vector: DirectionalVector,
        target: ASTNode,
        line: usize,
        col: usize,
    ) -> Self {
        Self {
            source: Box::new(source),
            vector,
            target: Box::new(target),
            line,
            col,
        }
    }
}

impl ConnectiveNode {
    /// Constructs a new connective node.
    pub fn new(
        left: ASTNode,
        connective: Connective,
        right: ASTNode,
        line: usize,
        col: usize,
    ) -> Self {
        Self {
            left: Box::new(left),
            connective,
            right: Box::new(right),
            line,
            col,
        }
    }

    /// Returns `true` if this is an adversative caveat (`!`).
    pub fn is_adversative(&self) -> bool {
        self.connective == Connective::But
    }

    /// Returns `true` if this is conjunction (`::`).
    pub fn is_conjunction(&self) -> bool {
        self.connective == Connective::And
    }

    /// Returns `true` if this is disjunction (`|`).
    pub fn is_disjunction(&self) -> bool {
        self.connective == Connective::Or
    }

```

```
    /// Returns `true` if this is unary inversion (`--`).
    pub fn is_inversion(&self) -> bool {
        self.connective == Connective::Not
    }

    /// Returns `true` if this is role typing / relation (`:`).
    pub fn is_role(&self) -> bool {
        self.connective == Connective::InRelationTo
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Invariant Guarantees & Trait Implementations )
// ============================================================================
// Relational nodes satisfy Send, Sync, Clone, PartialEq across all targets.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ast/nodes/structural.rs RS 205 LINES 769 WORDS 6.3 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( AST Structural Nodes: Programs, Modules, Tapes, Sections, Rolls & Commit Gates )
// ============================================================================
// SCRIPTURE ANCHORS & EPISTEMIC WITNESSES:
//   - Exodus 31:18: "written with the finger of God" — Inscription of eternal truth.
//   - Proverbs 24:27: "Prepare thy work without, and make it fit for thyself in the field;
//                      and afterwards build thine house." — Systematic modularization.
//   - Proverbs 22:28: "Remove not the ancient landmark, which thy fathers have set."
//                      — Preservation of invariant boundaries and balanced truth.
// ============================================================================

use crate::ast::nodes::boundaries::AsideNode;
use crate::ast::nodes::ASTNode;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Structural Node Definitions & 4-Block Section Kinds )
// ============================================================================

/// Complete source program reel or process tape containing sequential statements.
#[derive(Debug, Clone, PartialEq)]
pub struct ProgramNode {
    pub statements: Vec<ASTNode>,
    pub line: usize,
    pub col: usize,
}

/// Root Module declaration: `= [Module]: < Category > & [ Noun ] ( Aside ) { Fields }`.
#[derive(Debug, Clone, PartialEq)]
pub struct ModuleNode {
    pub name: String,
    pub category: Option<Box<ASTNode>>,
    pub aside: Option<AsideNode>,
    pub fields: Vec<ASTNode>,
    pub line: usize,
    pub col: usize,
}

/// Root Process Tape declaration: `= [Tape]: < Category > & [ Process ] ( Aside ) { Clauses }`.
#[derive(Debug, Clone, PartialEq)]
pub struct TapeNode {
    pub name: String,
    pub category: Option<Box<ASTNode>>,
    pub aside: Option<AsideNode>,
    pub clauses: Vec<ASTNode>,
    pub line: usize,
    pub col: usize,
}

/// The four canonical blocks governing OmniCode file architecture.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum SectionKind {
    /// Block 1: Metadata / Invariant Declarations
    Metadata,
    /// Block 2: Opening Block — State mounting, allocations, hardware bridges
    Opening,
    /// Block 3: Body Block — Sequential operational rolls & causal state progression
    Body,
    /// Block 4: Closing Block — Verification, sealing, tripwiring, diagnostic log & commit gates
    Closing,
}

impl SectionKind {
    /// Returns the canonical section block name.
    pub fn name(&self) -> &'static str {
        match self {
            Self::Metadata => "Metadata",
            Self::Opening => "Opening",
            Self::Body => "Body",
            Self::Closing => "Closing",
        }
    }
}
```

```rust

/// A 4-Block section container holding child statements or operational rolls:
/// `Opening { ... }`, `Body [ ... ]`, `Closing ( Aside ) { ... }`.
#[derive(Debug, Clone, PartialEq)]
pub struct SectionNode {
    pub kind: SectionKind,
    pub aside: Option<AsideNode>,
    pub elements: Vec<ASTNode>,
    pub line: usize,
    pub col: usize,
}

/// An atomic operational roll within the Body block:
/// `[ ROLL N ] : [ Intent ] : Action ( Aside )`.
#[derive(Debug, Clone, PartialEq)]
pub struct RollNode {
    pub id: usize,
    pub label: String,
    pub action: Box<ASTNode>,
    pub aside: Option<AsideNode>,
    pub line: usize,
    pub col: usize,
}

/// Closing Block Fourfold Commit Status Gate:
/// `[ Commit Status ] : [ +1:PROCEED | 0:AWAIT | HALT:NULL | -1:ROLLBACK ]`.
#[derive(Debug, Clone, PartialEq)]
pub struct CommitStatusNode {
    pub cases: Vec<ASTNode>,
    pub aside: Option<AsideNode>,
    pub line: usize,
    pub col: usize,
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Structural Constructors & Query Implementations )
// ============================================================================

impl ProgramNode {
    /// Constructs a new [`ProgramNode`].
    pub fn new(statements: Vec<ASTNode>, line: usize, col: usize) -> Self {
        Self { statements, line, col }
    }
}

impl ModuleNode {
    /// Constructs a new [`ModuleNode`].
    pub fn new(name: impl Into<String>, line: usize, col: usize) -> Self {
        Self {
            name: name.into(),
            category: None,
            aside: None,
            fields: Vec::new(),
            line,
            col,
        }
    }
}

impl TapeNode {
    /// Constructs a new [`TapeNode`].
    pub fn new(name: impl Into<String>, line: usize, col: usize) -> Self {
        Self {
            name: name.into(),
            category: None,
            aside: None,
            clauses: Vec::new(),
            line,
            col,
        }
    }
}

impl SectionNode {
    /// Constructs a new [`SectionNode`].
    pub fn new(kind: SectionKind, elements: Vec<ASTNode>, line: usize, col: usize) -> Self {
        Self {
```

```
            kind,
            aside: None,
            elements,
            line,
            col,
        }
    }

    /// Attaches an intent aside to this section block.
    pub fn with_aside(mut self, aside: AsideNode) -> Self {
        self.aside = Some(aside);
        self
    }
}

impl RollNode {
    /// Constructs a new operational [`RollNode`].
    pub fn new(id: usize, label: impl Into<String>, action: ASTNode, line: usize, col: usize) -> Self {
        Self {
            id,
            label: label.into(),
            action: Box::new(action),
            aside: None,
            line,
            col,
        }
    }

    /// Attaches an intent aside to this roll.
    pub fn with_aside(mut self, aside: AsideNode) -> Self {
        self.aside = Some(aside);
        self
    }
}

impl CommitStatusNode {
    /// Constructs a new [`CommitStatusNode`].
    pub fn new(cases: Vec<ASTNode>, line: usize, col: usize) -> Self {
        Self {
            cases,
            aside: None,
            line,
            col,
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Invariant Guarantees & Trait Implementations )
// ============================================================================
// Structural nodes satisfy Send, Sync, Clone, PartialEq across all targets.
```

OmniCode: Chapter 4: Track 1 - Core Types & Process Tape Ribbon

TapeHead 5-Ws Ribbon, Cell, Word, Reels & Operators

CHAPTER IDENTIFIER
CH 04

NOTEBOOKLM WORD COUNT
42,278 words

CATALOGED CHAPTER FILES
44 files (11,219 lines)

GENERATION DATE
2026-10-16 20:35:50

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"How does the TapeHead coordinate the 5 Ws and 1 H in time?"*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (44 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 1> : {Host Engine & Virtual Machine}/TRACK.md**	MD	14	85	0.7
2	**<TRACK 1> : {Host Engine & Virtual Machine}/src/lib.rs**	RS	87	332	3.7
3	**<TRACK 1> : {Host Engine & Virtual Machine}/src/main.rs**	RS	1,355	5,052	60.2
4	**<TRACK 1> : {Host Engine & Virtual Machine}/src/core/boundaries.rs**	RS	167	778	6.9
5	**<TRACK 1> : {Host Engine & Virtual Machine}/src/core/cell.rs**	RS	345	1,236	11.7
6	**<TRACK 1> : {Host Engine & Virtual Machine}/src/core/filetype.rs**	RS	420	1,554	16.3
7	**<TRACK 1> : {Host Engine & Virtual Machine}/src/core/linguistics.rs**	RS	1,237	4,208	54.2
8	**<TRACK 1> : {Host Engine & Virtual Machine}/src/core/mmio.rs**	RS	300	1,055	9.7
9	**<TRACK 1> : {Host Engine & Virtual Machine}/src/core/mod.rs**	RS	54	205	2.1
10	**<TRACK 1> : {Host Engine & Virtual Machine}/src/core/operators.rs**	RS	380	1,303	14.6
11	**<TRACK 1> : {Host Engine & Virtual Machine}/src/core/reel.rs**	RS	286	1,090	11.5
12	**<TRACK 1> : {Host Engine & Virtual Machine}/src/core/scene.rs**	RS	130	449	4.3
13	**<TRACK 1> : {Host Engine & Virtual Machine}/src/core/tape.rs**	RS	497	1,828	19.1
14	**<TRACK 1> : {Host Engine & Virtual Machine}/src/core/ternary.rs**	RS	386	1,528	14.5
15	**<TRACK 1> : {Host Engine & Virtual Machine}/src/core/vessel.rs**	RS	320	1,088	11.2
16	**<TRACK 1> : {Host Engine & Virtual Machine}/src/core/word.rs**	RS	676	2,608	22.6
17	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/lexicon/domain.rs**	RS	38	166	1.5
18	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/mod.rs**	RS	37	122	1.5
19	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/debugger.rs**	RS	471	1,835	20.2
20	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/mod.rs**	RS	54	264	2.6
21	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/restorator.rs**	RS	667	2,387	27.8
22	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/README.md**	MD	78	588	4.5
23	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/mod.rs**	RS	356	1,031	12.2
24	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/inscriber/log_writer.rs**	RS	91	264	3.4
25	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/inscriber/mod.rs**	RS	16	53	0.6
26	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/inscriber/naming.rs**	RS	69	231	2.1
27	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/inscriber/rotation.rs**	RS	86	300	3.0
28	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/inscriber/scroll_writer.rs**	RS	133	460	5.3
29	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/telemetry/frame.rs**	RS	82	263	2.7
30	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/telemetry/mod.rs**	RS	14	45	0.4
31	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/telemetry/note.rs**	RS	79	305	3.0
32	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/telemetry/ring_buffer.rs**	RS	95	313	3.0
33	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/failpoint/mod.rs**	RS	12	38	0.4
34	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/failpoint/remediation.rs**	RS	45	235	2.0
35	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/failpoint/types.rs**	RS	61	276	2.7
36	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/query/index.rs**	RS	32	139	1.2

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
37	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/query/mod.rs**	RS	12	36	0.4
38	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/query/search.rs**	RS	273	798	9.0
39	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/universal/bus.rs**	RS	96	305	3.2
40	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/universal/clock.rs**	RS	56	176	1.7
41	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/universal/mod.rs**	RS	12	40	0.4
42	**<TRACK 1> : {Host Engine & Virtual Machine}/src/cogs/mod.rs**	RS	32	132	1.4
43	**<TRACK 1> : {Host Engine & Virtual Machine}/src/cogs/platform.rs**	RS	940	4,296	42.8
44	**<TRACK 1> : {Host Engine & Virtual Machine}/src/cogs/tripwire.rs**	RS	628	2,781	28.2

<TRACK 1> : {Host Engine & Virtual Machine}/TRACK.md MD 14 LINES 85 WORDS 0.7 KB

```
# <TRACK 1> : {Host Engine & Virtual Machine}

## Scope & Invariant

The host compiler, balanced ternary virtual machine, process scheduler, and test harness.

- `src/core/`: Boundaries, Cell, 32-Trit Word, 4-Directional Reel, MMIO, Linguistics.
- `src/runtime/`: Assembler, Transactional Environment, Evaluator.
- `src/terminal/`: Multi-Track OmniScheduler, Living TerminalSession, Studio Renderer.
- `src/ai/`: Cognitive loop, AI Cortex, AILearner, AIMemory, Biblical Lexicon.
- `src/parser/` & `src/ast/`: Directional Lexer, recursive-descent Parser, AST.
- `src/diagnostics/`: Restorator, Debugger, Linter, Logger, Hover Engine.
- `tests/`: 3-tier automated test harness (unit, integrated, functional).
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/lib.rs RS 87 LINES 332 WORDS 3.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Library Root Identity, Universal Subsystem Modules & Core Re-exports )
// ============================================================================
//! OmniCode Language Engine
//! High-performance language engine based on formal ontology,
//! set theory, and balanced ternary quad-state execution,
//! engineered to be symmetrically human and machine readable.

pub mod core;
pub mod diagnostics;
pub mod ast;
pub mod parser;
pub mod runtime;
pub mod cli;
pub mod ai;
pub mod terminal;
pub mod cogs;


// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Public Re-export Declarations & High-Level API Surface )
// ============================================================================
pub use cogs::platform::{HostPlatform, HostArch};
pub use cogs::tripwire::{Tripwire, TripwireError};
pub use core::ternary::{QuadState, TransportAction, ROLLBACK, AWAIT, PROCEED, HALT};
pub use core::boundaries::BoundaryType;
pub use core::operators::{BeingRelation, DirectionalVector, Connective, Polarity, AffixPosition};
pub use core::word::{Word32Trit, Word64};
pub use core::scene::Scene;
pub use core::reel::MemoryReel;
pub use core::filetype::OmniFileType;
pub use core::tape::{Tape, Roll};
pub use core::mmio::{PhysicalMemoryMap, VgaBuffer, VgaColor, VGA_BUFFER_BASE, COM1_SERIAL_PORT};
pub use terminal::{OmniScheduler, OmniTask, Track, TaskPriority};

pub use diagnostics::logger::{DiagnosticLogger, FailpointType, FixKind, FixSuggestion};
pub use diagnostics::debugger::OmniDebugger;
pub use diagnostics::linter::{
    BlockKind, BodyScore, ClosingScore, FileAuditScore, LintReport, MetadataScore, OmniLinter,
    OpeningScore, QuadStateGate,
};
pub use diagnostics::restorator::{Restorator, RestorationReport, AppliedRepair};
pub use diagnostics::hover::{HoverEngine, HoverCard, OmniDefinition, TapeRollContext};
pub use ai::{
    AITransducer, TransductionSession, AICortex, ScrollLogger, ExecutionScroll, AILearner,
    EpisodicSummary, EpisodicExperience, CognitiveResult, BiblicalLexicon, LexiconDomain,
    LexiconEntry, MoralEvaluation,
};
pub use parser::lexer::Lexer;
pub use parser::parser::Parser;
pub use runtime::environment::Environment;
pub use runtime::evaluator::Evaluator;
pub use terminal::OmniStudio;
pub use cli::{
    run_repl, run_gui_server, run_boot, run_boot_with_config, BootArch, BootConfig, BootContext,
    run_assemble, run_assemble_with_config, AssembleConfig, AssembleContext, AssembleFormat,
};



// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Core Convenience Execution Pipeline )
// ============================================================================
/// Convenience execution helper that tokenizes, parses, and evaluates an OmniCode string.
pub fn execute(source: &str, print_logs: bool) -> Result<runtime::RuntimeValue, String> {
    let logger = DiagnosticLogger::new(print_logs);
    let mut lexer = Lexer::new(source, logger.clone());
    let tokens = lexer.tokenize()?;

    let debugger = OmniDebugger::new(logger, 10);
    let mut parser = Parser::new(tokens, debugger);
```

```
    let program = parser.parse_program()?;

    let mut evaluator = Evaluator::new(Environment::new(), parser.debugger);
    evaluator.eval(&ast::nodes::ASTNode::Program(program))
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Engine Status & Library Invariants )
// ============================================================================
// OmniCode library surface verified and sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/main.rs RS 1355 LINES 5052 WORDS 60.2 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( CLI Executable Identity, Subsystem Routing & Core Imports )
// ============================================================================
//! OmniCode CLI Entrypoint
//!
//! Provides the primary terminal interface for the OmniCode language engine:
//!     - Interactive REPL Terminal (default)
//!     - Single-file Script Runner (`run <file.omni>`)
//!     - 4-Block Structural Linter (`lint <file.omni>`)
//!     - Canonical Template Scaffolder (`scaffold <Name>`)
//!     - Ontological Verification Demo (`demo`)

use std::env;
use std::fs;
use std::path::PathBuf;
use std::process;
use std::thread;

use omnicode::{
    run_repl, run_gui_server, DiagnosticLogger, OmniDebugger, OmniLinter, Restorator,
    AICortex, AILearner, OmniFileType, Lexer, Parser, Evaluator, Environment,
    BiblicalLexicon, HoverEngine, Tape, OmniStudio,
};
use omnicode::cli::commands::{
    BootConfig, run_boot_with_config,
    AssembleConfig, run_assemble_with_config,
    RunConfig, run_with_config,
};


// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( CLI Help Display, Version Banner, and Command Route Setup )
// ============================================================================
fn print_cli_help() {
    println!("\x1b[1;36m================================================================================\x1b[0m");
    println!("\x1b[1;36m  OmniCode: Dual Human & Machine Readable Language Engine (v0.1.0)\x1b[0m");
    println!("\x1b[1;36m  Core: Balanced Ternary & Boundary Physics (Rust Engine)\x1b[0m");
    println!("\x1b[1;36m================================================================================\x1b[0m\n");
    println!("\x1b[1;33mUSAGE:\x1b[0m");
    println!("  omnicode                    Start the interactive terminal shell (REPL)");
    println!("  omnicode repl               Start the interactive terminal shell (REPL)");
    println!("  omnicode run <file>         Execute an OmniCode source (.omni) or scroll (.scroll)
  omnicode echo <char|msg>    Echo character or message through native balanced ternary I/O transducer");
    println!("  omnicode assemble <file>    Assemble an OmniCode process tape into concrete memory layout (.tape)");
    println!("  omnicode studio <file.tape> Project process tape in the cinematic HUD terminal projector");
    println!("  omnicode project <file.tape> Project process tape in the cinematic HUD terminal projector");
    println!("  omnicode boot [--uefi|--multiboot|--bios] [--gui] Boot bare-metal OS in QEMU");
    println!("  omnicode lint <file>        Validate 4-Block architecture compliance (.omni / .scroll)");
    println!("  omnicode hover <file> <l> <c> Inspect cross-scale 3-tier hovercard for symbol at position");
    println!("  omnicode doc <symbol>       Query architectural docstring, invariants, and machine intent");
    println!("  omnicode restore <file>     Auto-heal syntax, boundary, and block anomalies");
    println!("  omnicode ai \"<prompt>\"      Transduce prompt with AI Cortex, self-heal & inscribe");
    println!("  omnicode interact           Launch live CPI-SI cognitive discourse & learning shell");
    println!("  omnicode train              Train balanced-ternary brain on ideal reels and logs");
    println!("  omnicode noise [stress]     Simulate noise degradation breakdown ladder");
    println!("  omnicode query <session>    Query an episodic memory scroll in O(1) time");
    println!("  omnicode diagnose <session> Diagnose failpoints and view immune repairs");
    println!("  omnicode rotate [--cap N]   Enforce storehouse capacity bounds (Occupancy <= Capacity)");
    println!("  omnicode scrolls            Inspect episodic memory bank and learning statistics");
    println!("  omnicode manifest           Display the canonical Covenant Manifest and moral axioms");
    println!("  omnicode lexicon [term]     Inspect the 100% offline Biblical world lexicon");
    println!("  omnicode gui [--port 8080]  Launch the local web GUI Studio & Terminal interface");
    println!("  omnicode desktop            Launch the native desktop GUI Studio & Terminal shell");
    println!("  omnicode scaffold <Name> [--type omni|scroll] Generate canonical 4-Block template");
    println!("  omnicode filetypes          Display all formal OmniCode file types and MIME definitions");
    println!("  omnicode demo               Run the built-in ontological verification suite");
    println!("  omnicode --help, -h         Show this help information");
    println!("  omnicode --version, -v      Display engine version\n");
    println!("\x1b[1;33mREPL FEATURES:\x1b[0m");
    println!("  • Real-time evaluation of balanced ternary expressions (-1, 0, +1, NULL)");
    println!("  • Boundary delimiter matching with multiline input buffering");
    println!("  • Interactive failpoint alerts and transaction snapshot rollback");
```

```
    println!("  • Live symbol inspection via `:env` and AST inspection via `:ast <expr>`");
    println!("  • Persistent command line history\n");
}

fn print_version() {
    println!("omnicode 0.1.0 (Rust Core: Balanced Ternary & Boundary Physics)");
}


// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Command Handlers: Script Runner, Linter, Scaffolder, Ontological Demo )
// ============================================================================
fn run_studio(path: &str) {
    let logger = DiagnosticLogger::new(false);
    let tape = match Tape::from_file(path, logger) {
        Ok(t) => t,
        Err(e) => {
            eprintln!("\x1b[1;31mError loading tape for studio:\x1b[0m {e}");
            process::exit(1);
        }
    };
    let mut studio = OmniStudio::new(tape.head.name.clone(), tape.head.required_partition_size);
    studio.project_tape(&tape);
}

fn run_lint_file(path: &str) {
    let ft = OmniFileType::from_path(path);
    let title = ft.map(|f| f.display_name()).unwrap_or("OmniCode file");
    println!("\x1b[1;33m--- Linting Architecture ({title}): {} ---\x1b[0m", path);
    let content = match fs::read_to_string(path) {
        Ok(c) => c,
        Err(e) => {
            eprintln!("\x1b[1;31m✗ File read error:\x1b[0m Could not open '{}': {}", path, e);
            process::exit(1);
        }
    };

    let logger = DiagnosticLogger::new(false);
    let linter = OmniLinter::new(logger);
    let report = linter.lint_source(path, &content);

    if report.is_valid {
        println!("\x1b[1;32m✓ {title} Validation PASSED\x1b[0m");
        println!("  Blocks verified in sequence:");
        for b in &report.blocks_found {
            println!("    - Line {}: {}", b.line_number, b.kind.name());
        }

        if let Some(audit) = &report.audit_score {
            let is_tape = matches!(ft, Some(OmniFileType::Tape));

            // Block 1: Metadata / Tape Head
            let b1 = &audit.block1_metadata;
            let b1_label = if is_tape { "Tape Head Manifest" } else { "Metadata Block" };
            println!("\n  \x1b[1;34m[ BLOCK 1 : {b1_label} ]\x1b[0m");
            let score_color = if b1.total >= 90 { "\x1b[1;32m" } else if b1.total >= 70 { "\x1b[1;32m" } else if b1.total
>= 50 { "\x1b[1;33m" } else { "\x1b[1;31m" };
            println!("  {score_color}★ Block 1 Invariant Score: {}/100 [{}]\x1b[0m", b1.total, b1.rating);
            println!("    Subsystem Breakdown:");
            if is_tape {
                println!("      • Formal Tape Head:        {}/20", b1.identity_score);
                println!("      • Partition & Domain:      {}/25", b1.provenance_score);
                println!("      • Invariant Scripture:     {}/20", b1.witness_score);
                println!("      • Cardinal Coordinates:    {}/20", b1.ontology_score);
                println!("      • Spatial & Naming Hygiene:{}/15", b1.spatial_hygiene_score);
            } else {
                println!("      • Identity & Declaration:  {}/20", b1.identity_score);
                println!("      • Provenance & Context:    {}/25", b1.provenance_score);
                println!("      • Covenant Witness Anchor: {}/20", b1.witness_score);
                println!("      • Ontology & Coordinates:  {}/20", b1.ontology_score);
                println!("      • Spatial & Naming Hygiene:{}/15", b1.spatial_hygiene_score);
            }
            for item in &b1.breakdown {
                println!("      {}", item);
            }

            // Block 2: Opening / Tape Setup
```

```
            let b2 = &audit.block2_opening;
            let b2_label = if is_tape { "Roll 1 Initial Setup & Preconditions" } else { "Opening Block & Precondition
Equilibrium" };
            println!("\n  \x1b[1;34m[ BLOCK 2 : {b2_label} ]\x1b[0m");
            let score_color = if b2.total >= 90 { "\x1b[1;32m" } else if b2.total >= 70 { "\x1b[1;32m" } else if b2.total
>= 50 { "\x1b[1;33m" } else { "\x1b[1;31m" };
            println!("  {score_color}★ Block 2 Invariant Score: {}/100 [{}]\x1b[0m", b2.total, b2.rating);
            println!("    Subsystem Breakdown:");
            if is_tape {
                println!("      • Roll 1 Entity Setup:     {}/25", b2.entity_allocation_score);
                println!("      • Memory Cell Target:      {}/20", b2.cell_container_score);
                println!("      • Inscription Vector:      {}/20", b2.substrate_bridge_score);
                println!("      • Container Parity Guard:  {}/20", b2.preconditions_target_score);
                println!("      • Spatial Ruler & Asides:  {}/15", b2.spatial_asides_score);
            } else {
                println!("      • Typed Entity Allocation: {}/25", b2.entity_allocation_score);
                println!("      • Cell Container Sizing:   {}/20", b2.cell_container_score);
                println!("      • Substrate Bridge/Trits:  {}/20", b2.substrate_bridge_score);
                println!("      • Preconditions & Targets: {}/20", b2.preconditions_target_score);
                println!("      • Spatial Ruler & Asides:  {}/15", b2.spatial_asides_score);
            }
            for item in &b2.breakdown {
                println!("      {}", item);
            }

            // Block 3: Body / Tape Rolls
            let b3 = &audit.block3_body;
            let b3_label = if is_tape { "Operational Tape Rolls Section" } else { "Body Block & Causal Pipelines" };
            println!("\n  \x1b[1;34m[ BLOCK 3 : {b3_label} ]\x1b[0m");
            let score_color = if b3.total >= 90 { "\x1b[1;32m" } else if b3.total >= 70 { "\x1b[1;32m" } else if b3.total
>= 50 { "\x1b[1;33m" } else { "\x1b[1;31m" };
            println!("  {score_color}★ Block 3 Invariant Score: {}/100 [{}]\x1b[0m", b3.total, b3.rating);
            println!("    Subsystem Breakdown:");
            println!("      • Operational SVO Verbs:   {}/25", b3.svo_verbs_score);
            println!("      • Directional Vectors:     {}/20", b3.directional_vectors_score);
            println!("      • State-Prime Progression: {}/20", b3.state_prime_score);
            println!("      • Adversative Guard Caveat:{}/20", b3.guard_caveats_score);
            println!("      • Spatial Ruler & Asides:  {}/15", b3.spatial_asides_score);
            for item in &b3.breakdown {
                println!("      {}", item);
            }

            // Block 4: Closing / Commit Status
            let b4 = &audit.block4_closing;
            let b4_label = if is_tape { "Terminal Commit Status Roll" } else { "Closing Block & Sealing Gate" };
            println!("\n  \x1b[1;34m[ BLOCK 4 : {b4_label} ]\x1b[0m");
            let score_color = if b4.total >= 90 { "\x1b[1;32m" } else if b4.total >= 70 { "\x1b[1;32m" } else if b4.total
>= 50 { "\x1b[1;33m" } else { "\x1b[1;31m" };
            println!("  {score_color}★ Block 4 Invariant Score: {}/100 [{}]\x1b[0m", b4.total, b4.rating);
            println!("    Subsystem Breakdown:");
            if is_tape {
                println!("      • Commit Roll Identity:    {}/20", b4.verification_proofs_score);
                println!("      • Preceding Roll Condition:{}/20", b4.invariant_validation_score);
                println!("      • Zero-Tolerance Tripwire: {}/20", b4.tripwire_breaker_score);
                println!("      • Fourfold T4 Machine:     {}/25", b4.fourfold_state_machine_score);
                println!("      • Spatial Ruler & Asides:  {}/15", b4.telemetry_asides_score);
            } else {
                println!("      • Operational Proofs:      {}/20", b4.verification_proofs_score);
                println!("      • Invariant Bounds Parity: {}/20", b4.invariant_validation_score);
                println!("      • Zero-Tolerance Tripwire: {}/20", b4.tripwire_breaker_score);
                println!("      • Fourfold T4 Machine:     {}/25", b4.fourfold_state_machine_score);
                println!("      • Telemetry & Spatial:     {}/15", b4.telemetry_asides_score);
            }
            for item in &b4.breakdown {
                println!("      {}", item);
            }

            // Composite 4-Block Summary & QuadState Gate
            println!("\n
\x1b[1;36m================================================================================\x1b[0m");
            let comp_color = if audit.composite_score >= 70 {
                "\x1b[1;32m"
            } else if audit.composite_score >= 50 {
                "\x1b[1;33m"
            } else {
                "\x1b[1;31m"
            };
            println!("  {comp_color}COMPOSITE 4-BLOCK AUDIT SCORE: {:+}/100\x1b[0m", audit.composite_score);
```

```
            println!("  COMPILATION GATE: \x1b[1m{}\x1b[0m", audit.gate.name());
            if audit.eligible_to_compile {
                println!("  \x1b[1;32m✓ ELIGIBLE TO COMPILE: Source unit certified for AST lowering & assembly\x1b[0m");
            } else {
                println!("  \x1b[1;31m✗ COMPILATION DISQUALIFIED: Fails threshold for assembly lowering\x1b[0m");
            }
            println!("
\x1b[1;36m================================================================================\x1b[0m\n");
        }

        if !report.warnings.is_empty() {
            println!("\x1b[1;33m⚠ Lint Warnings / Recommendations ({}):\x1b[0m", report.warnings.len());
            for warn in &report.warnings {
                println!("    • {}", warn);
            }
        }
    } else {
        println!("\x1b[1;31m✗ {title} Validation FAILED\x1b[0m");
        for err in &report.errors {
            eprintln!("    • {}", err);
        }
        process::exit(1);
    }
}

fn run_scaffold(name: &str, file_type: Option<&str>) {
    let ft = file_type
        .and_then(OmniFileType::from_extension)
        .unwrap_or(OmniFileType::SourceReel);
    let scaffolded = match ft {
        OmniFileType::SourceReel => OmniLinter::auto_scaffold_omni(name, "User-defined module"),
        OmniFileType::EpisodicScroll => OmniLinter::auto_scaffold_scroll(name, "User cognitive discourse intent"),
        OmniFileType::Tape => ft.scaffold_template(name, "User process execution tape"),
    };
    println!("{}", scaffolded);
}

fn run_filetypes() {
    println!("\x1b[1;36m================================================================================\x1b[0m");
    println!("\x1b[1;36m  OmniCode File Type System & Taxonomy Manifest                                  \x1b[0m");
    println!("\x1b[1;36m================================================================================\x1b[0m\n");

    for (i, ft) in OmniFileType::all().iter().enumerate() {
        println!("  \x1b[1;33m[{}]\x1b[0m \x1b[1;32m.{}\x1b[0m  —  \x1b[1m{}\x1b[0m", i + 1, ft.extension(),
ft.display_name());
        println!("      MIME:        \x1b[36m{}\x1b[0m", ft.mime_type());
        println!("      Language ID: \x1b[35m{}\x1b[0m", ft.language_id());
        println!("      Purpose:     {}\n", ft.description());
    }
}

fn run_demo() {
    println!("\x1b[1;36m======================================================\x1b[0m");
    println!("\x1b[1;36m  OmniCode: Ontological Conceptual Testbed           \x1b[0m");
    println!("\x1b[1;36m======================================================\x1b[0m\n");

    let demo_code = fs::read_to_string("examples/canonical_notation.omni")
        .unwrap_or_else(|_| OmniLinter::auto_scaffold_omni("DemoModule", "Ontological verification module"));


    println!("\x1b[1;33m--- Running 4-Block Structural Linter ---\x1b[0m");
    let logger = DiagnosticLogger::new(true);
    let linter = OmniLinter::new(logger.clone());
    let lint_report = linter.lint_source("demo_code", &demo_code);

    if lint_report.is_valid {
        println!("\x1b[1;32m✓ 4-Block Structural Check Passed:\x1b[0m Found {} blocks in order.",
lint_report.blocks_found.len());
    } else {
        println!("\x1b[1;31m✗ Structural Linter Errors:\x1b[0m {:?}", lint_report.errors);
    }

    println!("\n\x1b[1;33m--- Running Code Evaluation Pipeline ---\x1b[0m");
    let mut lexer = Lexer::new(&demo_code, logger.clone());

    match lexer.tokenize() {
        Ok(tokens) => {
            println!("\x1b[1;32m✓ Lexer Tokenization Succeeded:\x1b[0m ({} tokens)", tokens.len());
```

```
            let debugger = OmniDebugger::new(logger.clone(), 5);
            let mut parser = Parser::new(tokens, debugger);

            match parser.parse_program() {
                Ok(prog) => {
                    println!("\x1b[1;32m✓ Parser Succeeded:\x1b[0m Generated AST with {} statements",
prog.statements.len());
                    let mut evaluator = Evaluator::new(Environment::new(), parser.debugger);
                    match evaluator.eval(&omnicode::ast::nodes::ASTNode::Program(prog)) {
                        Ok(res) => {
                            println!("\n\x1b[1;32m✓ Execution Final Result:\x1b[0m => {}", res.format_colored());
                        }
                        Err(e) => eprintln!("\x1b[1;31m✗ Evaluator Error:\x1b[0m {}", e),
                    }
                }
                Err(e) => eprintln!("\x1b[1;31m✗ Parser Error:\x1b[0m {}", e),
            }
        }
        Err(e) => eprintln!("\x1b[1;31m✗ Lexer Error:\x1b[0m {}", e),
    }

    if logger.has_failpoints() {
        println!("\n\x1b[1;33m--- Diagnostic Failpoints Caught During Run ---\x1b[0m");
        for fp in logger.failpoints() {
            println!("  * [{}] {}", fp.channel, fp.message);
        }
    } else {
        println!("\n\x1b[1;32m✓ No unexpected failpoints encountered during demo run.\x1b[0m");
    }
}

fn run_restore(path: &str, in_place: bool) {
    println!("\x1b[1;36mAutonomous Self-Healing Restoration:\x1b[0m {}", path);
    let logger = DiagnosticLogger::new(false);
    let restorator = Restorator::new(logger);

    match restorator.restore_file(path, in_place) {
        Ok(report) => {
            if !report.was_modified {
                println!("\x1b[1;32m✓ Source is already healthy:\x1b[0m No repairs needed.");
            } else {
                println!("\x1b[1;33m⚠ Repairs Applied ({}):\x1b[0m", report.repairs_applied.len());
                for repair in &report.repairs_applied {
                    println!("    • L{}: [{:?}] {}", repair.line, repair.kind, repair.description);
                }
                if in_place {
                    println!("\x1b[1;32m✓ Healed file written in-place to {}\x1b[0m", path);
                } else {
                    println!("\n\x1b[1;36m--- Restored Content Preview ---\x1b[0m\n{}", report.restored_content);
                }
            }

            if report.verified {
                println!("\x1b[1;32m✓ Post-Restoration Verification PASSED:\x1b[0m Code executes to => +1:PROCEED");
            } else if !report.errors.is_empty() {
                println!("\x1b[1;33m⚠ Verification Diagnostics:\x1b[0m {:?}", report.errors);
            }
        }
        Err(e) => {
            eprintln!("\x1b[1;31m✗ Restoration Failed:\x1b[0m {}", e);
            process::exit(1);
        }
    }
}

fn print_deliberation_trace(
    res: &omnicode::ai::CognitiveResult,
    prompt: &str,
) {
    println!(
        "\x1b[1;36m==================================================\
         ============================\x1b[0m"
    );
    println!(
        "\x1b[1;36m  OmniCode AI: CPI-SI Cognitive Thought \
         Deliberation Trace                    \x1b[0m"
    );
    println!(
```

```
        "\x1b[1;36m================================================\
         ============================\x1b[0m\n"
    );
    println!("\x1b[1;33m[Discourse Prompt]:\x1b[0m\n  \"{}\"\n", prompt);

    println!(
        "\x1b[1;34m[1. Sensory Inscription & Neural Forward Pass]:\x1b[0m"
    );
    let stim_trits: Vec<i8> = res
        .stimulus
        .iter()
        .map(|s| s.as_int().unwrap_or(0))
        .collect();
    println!(
        "  • Encoded Balanced-Ternary Stimulus (8 Cells): {:?}",
        stim_trits
    );
    let brain_acts: Vec<String> = res
        .brain_activation
        .iter()
        .map(|s| {
            format!("{:+}:{}", s.as_int().unwrap_or(0), s.macro_op())
        })
        .collect();
    println!(
        "  • Multi-Layer Neural Activation (4 Neurons):   {:?}",
        brain_acts
    );
    println!(
        "  • Dominant Resonance:                          => +1:{}\n",
        res.execution_state.macro_op()
    );

    println!(
        "\x1b[1;34m[2. OmniCode Syntax Breakdown & 5Ws + H Anchoring]:\
         \x1b[0m"
    );
    println!("  • WHO:   {}", res.thought.who);
    println!("  • WHAT:  {}", res.thought.what);
    println!("  • WHEN:  {}", res.thought.when_clause);
    println!("  • WHERE: {}", res.thought.where_clause);
    println!("  • WHY:   {}", res.thought.why);
    println!("  • HOW:   {}", res.thought.how);
    if let Some(ref anchor) = res.thought.biblical_anchor {
        println!("  • Covenant Invariant: {}\n", anchor);
    } else {
        println!();
    }

    if !res.repairs_applied.is_empty() {
        println!(
            "\x1b[1;33m⚠ Restorator Immune Repairs ({}):\x1b[0m",
            res.repairs_applied.len()
        );
        for r in &res.repairs_applied {
            println!(
                "    • L{}: [{:?}] {}",
                r.line, r.kind, r.description
            );
        }
        println!();
    }

    println!("\x1b[1;32m✓ Synthesized 4-Block OmniCode Turing Reel:\x1b[0m");
    println!(
        "-------------------------------------------------\
         ----------------------------"
    );
    println!("{}", res.synthesized_omnicode.trim());
    println!(
        "-------------------------------------------------\
         ----------------------------"
    );
    println!(
        "\x1b[1;32m✓ Machine Evaluator Verification Gate:\x1b[0m => +1:{}",
        res.execution_state.macro_op()
    );

```

```
    println!(
        "\n\x1b[1;34m[3. Cognitive Conclusion Derivation \
         (Grounded vs Keyword)]:\x1b[0m"
    );
    println!(
        "  • Pathway:      Neuro-Symbolic Formulation \
         (Not Keyword Trigger)"
    );
    println!("  • Anchor:       {}", res.thought.premise);
    println!("  • Causal Law:   {}", res.thought.why);
    println!(
        "  • Verification: AST Evaluator verified state => +1:{}",
        res.execution_state.macro_op()
    );
    println!("\n\x1b[1;35m[Machine Layer Response]:\x1b[0m");
    println!("  \"{}\"\n", res.natural_response);

    let (b_e, b_n, b_i) = res.synaptic_counts_before;
    let (a_e, a_n, a_i) = res.synaptic_counts_after;
    println!(
        "\x1b[1;34m[Episodic Storage & Lifelong Neuroplasticity]:\x1b[0m"
    );
    println!("  • Prompt Scroll:   {:?}", res.scroll_path);
    println!("  • Telemetry Log:   {:?}", res.log_path);
    println!(
        "  • Synaptic Delta:  +1: {b_e}->{a_e} | 0: {b_n}->{a_n} \
         | -1: {b_i}->{a_i}"
    );
    println!("  • Session ID:      {}\n", res.session_id);
}

fn run_ai(prompt: &str, verbose: bool) {
    let mut cortex = AICortex::new();

    match cortex.process_prompt(prompt) {
        Ok(res) => {
            if verbose {
                print_deliberation_trace(&res, prompt);
            } else {
                println!("[CPI-SI Base]: \"{}\"", res.natural_response);
            }
        }
        Err(e) => {
            eprintln!("\x1b[1;31m✗ AI Cortex Error:\x1b[0m {}", e);
            process::exit(1);
        }
    }
}

fn run_scrolls() {
    println!("\x1b[1;36m================================================================================\x1b[0m");
    println!("\x1b[1;36m  OmniCode AI: Episodic Memory Bank & Experiential Learning Archive           \x1b[0m");
    println!("\x1b[1;36m================================================================================\x1b[0m\n");
    let scroll_dir = omnicode::core::filetype::resolve_scroll_storage_dir();
    let learner = AILearner::new(&scroll_dir);
    match learner.digest_experiences() {
        Ok(summary) => {
            println!("\x1b[1;33mEPISODIC LEARNING SUMMARY:\x1b[0m");
            println!("  • Total Inscribed Episodes:     {}", summary.total_episodes);
            println!("  • State Distribution:           Proceed (+1): {} | Halt (NULL): {} | Rollback (-1): {} | Await
(0): {}",
                summary.proceed_count, summary.halt_count, summary.rollback_count, summary.await_count
            );
            println!("  • Restorator Repairs Learned:   {}\n", summary.total_repairs_learned);

            if summary.experiences.is_empty() {
                println!("  (No scrolls recorded yet in `scrolls/`. Run `omnicode ai \"...\"` to generate
experiences.)\n");
            } else {
                println!("\x1b[1;33mRECENT EPISODES:\x1b[0m");
                for (i, exp) in summary.experiences.iter().enumerate() {
                    let log_status = if exp.log_path.is_some() { "yes" } else { "no" };
                    println!(
                        "  [{:>2}] Session: {:<12} | State: +1:{:<8} | Repairs: {:>2} | Failpoints: {:>2} | .log: {}",
                        i + 1, exp.session_id, exp.final_state.macro_op(), exp.repair_count, exp.failpoint_count,
log_status
                    );
                    println!("       Prompt: \"{}\"", exp.prompt);
```

```
                    println!("       Scroll: {:?}\n", exp.scroll_path);
                }
            }
        }
        Err(e) => {
            eprintln!("\x1b[1;31m✗ Failed to read scrolls:\x1b[0m {}", e);
            process::exit(1);
        }
    }
}

fn run_query(session_id: &str) {
    println!("\x1b[1;36m================================================================================\x1b[0m");
    println!("\x1b[1;36m  OmniCode AI: O(1) Episodic Memory & Telemetry Query Engine                  \x1b[0m");
    println!("\x1b[1;36m================================================================================\x1b[0m\n");

    let cortex = AICortex::new();
    match cortex.query_episode(session_id) {
        Some(session) => {
            let state_str = match session.final_state.as_int() {
                Some(i) => format!("{i:+}:{}", session.final_state.macro_op()),
                _ => format!("*:{}", session.final_state.macro_op()),
            };
            println!("\x1b[1;32m✓ Session Located in O(1) Time:\x1b[0m");
            println!("  • Session ID:        {}", session.session_id);
            println!("  • Domain Category:   {}", session.category);
            println!("  • Commit Quad-State: {}", state_str);
            println!("  • Inscribed Prompt:  \"{}\"", session.prompt);
            println!("  • Trapped Failpoints: {}", session.failpoint_count);
            println!("  • Restorator Repairs: {}", session.repair_count);
            println!("  • Inscribed Scroll:  {:?}", session.scroll_path);
            if let Some(ref lp) = session.log_path {
                println!("  • Paired Telemetry:  {:?}", lp);
            } else {
                println!("  • Paired Telemetry:  (none)");
            }
            println!();
        }
        None => {
            eprintln!(
                "\x1b[1;31m✗ Episode Not Found:\x1b[0m Session '{}' does not exist in storehouse.",
                session_id
            );
            process::exit(1);
        }
    }
}

fn run_diagnose(session_id: &str) {
    println!("\x1b[1;36m================================================================================\x1b[0m");
    println!("\x1b[1;36m  OmniCode AI: Failpoint & Anomaly Diagnostic Oracle                          \x1b[0m");
    println!("\x1b[1;36m================================================================================\x1b[0m\n");

    let cortex = AICortex::new();
    match cortex.diagnose_failpoint(session_id) {
        Some(report) => {
            println!("{report}");
        }
        None => {
            eprintln!(
                "\x1b[1;31m✗ Episode Not Found:\x1b[0m Session '{}' does not exist in storehouse.",
                session_id
            );
            process::exit(1);
        }
    }
}

fn run_rotate(max_files: usize) {
    println!("\x1b[1;36m================================================================================\x1b[0m");
    println!("\x1b[1;36m  OmniCode Storehouse: Vessel Capacity Rotation Engine                         \x1b[0m");
    println!("\x1b[1;36m  Invariant Law: Occupancy <= Capacity (2 Kings 4:4)                          \x1b[0m");
    println!("\x1b[1;36m================================================================================\x1b[0m\n");

    let scroll_dir = omnicode::core::filetype::resolve_scroll_storage_dir();
    let policy = omnicode::diagnostics::logger::RotationPolicy::new(
        max_files, true,
    );
```

```
    let logger = omnicode::ai::ScrollLogger::with_rotation_policy(
        &scroll_dir, policy,
    );

    match logger.rotate_storehouse() {
        Ok(rotated) => {
            println!("\x1b[1;32m✓ Storehouse Rotation Enforced:\x1b[0m");
            println!("  • Target Partition Capacity:  {} files", max_files);
            println!(
                "  • Excess Files Archived:     {} files moved to 'archive/'\n",
                rotated
            );
        }
        Err(e) => {
            eprintln!("\x1b[1;31m✗ Storehouse Rotation Failed:\x1b[0m {}", e);
            process::exit(1);
        }
    }
}

fn run_train() {
    println!("\x1b[1;36m================================================================================\x1b[0m");
    println!("\x1b[1;36m  OmniCode AI: CPI-SI Base Neural Trainer & Weight Freezing                    \x1b[0m");
    println!("\x1b[1;36m  Ingesting Archetypes & Runtime Logs into Balanced-Ternary Weights           \x1b[0m");
    println!("\x1b[1;36m================================================================================\x1b[0m\n");

    let scroll_dir = omnicode::core::filetype::resolve_scroll_storage_dir();
    let learner = omnicode::ai::AILearner::new(&scroll_dir);

    match learner.digest_experiences() {
        Ok(summary) => {
            let logger = DiagnosticLogger::new(false);
            let mut brain = omnicode::ai::NeuralBrain::new(
                &[8, 16, 4], 1, logger,
            );
            let trainer = omnicode::ai::NeuralTrainer::new();

            // 1. Stage 1 Foundational Archetype Training
            let archetypes = [
                "Idea { Type } : Character (Atomic rune, 1 Cell, 5 trits)",
                "Exemplar 'A': 65 <=> [ -1, +1, +1, -1, +1 ]",
                "Idea { Type } : Number (Radix-3 balanced scalar value)",
                "Exemplar '0': 0 <=> [ 0, 0, 0, 0, 0 ]",
                "Idea { Type } : Container (Primordial boundary perimeter)",
                "Boundary Invariant: Strict capacity and leak defense",
                "Covenant Identity: CPI-SI Base model conceived 2 years ago",
                "Neural Plasticity: BCM homeostatic threshold adaptation",
            ];
            let archetypes_adapted =
                trainer.train_archetypes(&mut brain, &archetypes);

            // 2. Episodic Experience Training
            let report = trainer.train(&mut brain, &summary.experiences);

            // 3. Persist Frozen Baseline Weights
            let weights_path =
                PathBuf::from("storage/weights/cpisi_base.weights");
            let save_result = brain.save_weights(&weights_path);

            let (exc, neu, inh) = brain.synaptic_counts();

            println!("\x1b[1;32m✓ CPI-SI Base Training Completed:\x1b[0m");
            println!("  • Archetype Inscriptions:    {}", archetypes_adapted);
            println!("  • Episodes Digested:         {}", report.total_episodes);
            println!("  • Total Synapses Adapted:    {}", report.synapses_adapted);
            println!("  • Clean (+1:Proceed) Paths:  {}", report.clean_proceed_count);
            println!("  • Rollback (-1) Protections: {}", report.degraded_rollback_count);
            println!(
                "  • Synapse Breakdown:         +1: {} | 0: {} | -1: {}",
                exc, neu, inh
            );
            println!(
                "  • Resilience Before:         {:.1}%",
                report.noise_resilience_before * 100.0
            );
            println!(
                "  • Resilience After:          {:.1}%",
                report.noise_resilience_after * 100.0
```

```
            );
            match save_result {
                Ok(_) => println!("  • Saved Frozen Weights:      {:?}\n", weights_path),
                Err(e) => println!("  • Weight Save Warning:       {}\n", e),
            }
        }
        Err(e) => {
            eprintln!("\x1b[1;31m✗ Training Failed:\x1b[0m {}", e);
            process::exit(1);
        }
    }
}

fn run_interact() {
    use std::io::Write;
    println!(
        "\x1b[1;36m==================================================\
         ============================\x1b[0m"
    );
    println!(
        "\x1b[1;36m  OmniCode AI: CPI-SI Base Interactive Cognitive \
         Discourse Shell              \x1b[0m"
    );
    println!(
        "\x1b[1;36m  Covenant Partnered Intelligence (CPI-SI) - \
         Structured Intelligence          \x1b[0m"
    );
    println!(
        "\x1b[1;36m==================================================\
         ============================\x1b[0m\n"
    );
    println!(
        "\x1b[1;33mStage 3 Adult Neuroplasticity Active.\x1b[0m \
         Enter prompt or inquiry below."
    );
    println!(
        "Commands: \x1b[1;32m:brain\x1b[0m (status), \
         \x1b[1;32m:verbose\x1b[0m (toggle trace), \
         \x1b[1;32m:save\x1b[0m (persist weights), \
         \x1b[1;31mexit\x1b[0m (quit).\n"
    );

    let mut cortex = AICortex::new();
    let mut verbose = false;
    let stdin = std::io::stdin();

    loop {
        print!("\x1b[1;35mCPI-SI> \x1b[0m");
        std::io::stdout().flush().ok();

        let mut line = String::new();
        if stdin.read_line(&mut line).is_err() || line.trim().is_empty() {
            continue;
        }

        let trimmed = line.trim();
        if trimmed == "exit" || trimmed == "quit" {
            println!(
                "\x1b[1;33mClosing CPI-SI interactive session \
                 with shalom.\x1b[0m\n"
            );
            break;
        }

        if trimmed == ":brain" {
            let (exc, neu, inh) = cortex.brain.synaptic_counts();
            println!("\n\x1b[1;32m--- CPI-SI Neural Brain Status ---\x1b[0m");
            println!(
                "  • Architecture:       \
                 4-Block Multi-Layer Balanced-Ternary"
            );
            println!("  • Layers:             {}", cortex.brain.layers.len());
            println!("  • Excitatory (+1):    {}", exc);
            println!("  • Neutral (0):        {}", neu);
            println!("  • Inhibitory (-1):    {}", inh);
            println!("  • Total Synapses:     {}\n", exc + neu + inh);
            continue;
        }
```

```
        if trimmed == ":verbose" || trimmed == ":thought" {
            verbose = !verbose;
            if verbose {
                println!(
                    "\n\x1b[1;32m✓ Verbose deliberation trace enabled.\
                     \x1b[0m Showing full thought process.\n"
                );
            } else {
                println!(
                    "\n\x1b[1;33m✓ Verbose deliberation trace disabled.\
                     \x1b[0m Returning clean machine responses.\n"
                );
            }
            continue;
        }

        if trimmed == ":save" {
            let weights_path =
                PathBuf::from("storage/weights/cpisi_base.weights");
            match cortex.brain.save_weights(&weights_path) {
                Ok(_) => {
                    println!(
                        "\x1b[1;32m✓ Weights saved to {:?}\x1b[0m\n",
                        weights_path
                    );
                }
                Err(e) => println!("\x1b[1;31m✗ Save failed:\x1b[0m {}\n", e),
            }
            continue;
        }

        match cortex.process_prompt(trimmed) {
            Ok(res) => {
                if verbose {
                    print_deliberation_trace(&res, trimmed);
                } else {
                    println!(
                        "\x1b[1;35m[CPI-SI Base]:\x1b[0m \"{}\"\n",
                        res.natural_response
                    );
                }
            }
            Err(e) => {
                println!("\x1b[1;31m✗ Deliberation Error:\x1b[0m {}\n", e);
            }
        }
    }
}

fn run_noise(stress: Option<f64>) {
    println!("\x1b[1;36m================================================================================\x1b[0m");
    println!("\x1b[1;36m  OmniCode AI: Structured Non-Random Degradation & Noise Engine              \x1b[0m");
    println!("\x1b[1;36m  Simulating Systemic Entropy & Physical Mind Breakdown Dynamics             \x1b[0m");
    println!("\x1b[1;36m================================================================================\x1b[0m\n");

    let engine = omnicode::ai::NoiseEngine::default();
    let ideal_stimulus = &[
        omnicode::core::ternary::QuadState::Proceed,
        omnicode::core::ternary::QuadState::Proceed,
        omnicode::core::ternary::QuadState::Proceed,
        omnicode::core::ternary::QuadState::Proceed,
        omnicode::core::ternary::QuadState::Proceed,
        omnicode::core::ternary::QuadState::Proceed,
        omnicode::core::ternary::QuadState::Proceed,
        omnicode::core::ternary::QuadState::Proceed,
    ];

    let logger = DiagnosticLogger::new(false);
    let brain = omnicode::ai::NeuralBrain::new(&[8, 16, 4], 1, logger);

    if let Some(s) = stress {
        let (perturbed, out) =
            brain.think_with_noise(ideal_stimulus, &engine, s);
        println!("\x1b[1;33mSTRESS LEVEL: {:.2}\x1b[0m", s);
        println!("  • Input Vector:     {:?}", perturbed);
        println!("  • Cortical Output:  {:?}\n", out);
    } else {
```

```
        println!("\x1b[1;33mDEGRADATION LADDER (Ideal -> Breakdown):\x1b[0m");
        let ladder = engine.simulate_breakdown_ladder(ideal_stimulus);
        for step in &ladder {
            let out = brain.think(&step.perturbed_vector);
            let mode_str = match step.dominant_mode {
                omnicode::ai::DegradationMode::Ideal => "Pristine (Ideal)",
                omnicode::ai::DegradationMode::TritDecay => {
                    "Trit Attenuation (Decay)"
                }
                omnicode::ai::DegradationMode::BoundaryLeak => {
                    "Boundary Cross-Talk (Leak)"
                }
                omnicode::ai::DegradationMode::ThermalInversion => {
                    "Thermal Perturbation (Inversion)"
                }
                omnicode::ai::DegradationMode::FailpointTrap => {
                    "Circuit Halt (Catastrophic)"
                }
            };
            println!(
                "  [Stress {:>4.0}%] Mode: {:<32} | Fidelity: {:>5.1}%",
                step.stress_level * 100.0,
                mode_str,
                step.signal_fidelity * 100.0
            );
            println!(
                "    Sensory: {:?} -> Motor: {:?}",
                step.perturbed_vector, out
            );
        }
        let resilience =
            brain.evaluate_noise_resilience(ideal_stimulus, &engine);
        println!(
            "\n  • Overall Neural Noise Resilience Score: {:.1}%\n",
            resilience * 100.0
        );
    }
}

fn run_manifest() {
    println!("\x1b[1;36m================================================================================\x1b[0m");
    println!("\x1b[1;36m  OmniCode AI: Invariant Covenant Manifest (manifest.omni)                     \x1b[0m");
    println!("\x1b[1;36m  Anchored in Public Domain Scriptures (King James Version & World English Bible)\x1b[0m");
    println!("\x1b[1;36m================================================================================\x1b[0m\n");

    match fs::read_to_string("manifest.omni") {
        Ok(content) => println!("{}", content),
        Err(e) => {
            eprintln!("\x1b[1;31m✗ Could not open manifest.omni:\x1b[0m {}", e);
            process::exit(1);
        }
    }
}

fn run_lexicon(query: Option<&str>) {
    println!("\x1b[1;36m================================================================================\x1b[0m");
    println!("\x1b[1;36m  OmniCode AI: 100% Offline Biblical World Lexicon & Moral Ontology           \x1b[0m");
    println!("\x1b[1;36m  Public Domain Primary Witness: King James Version (1611) & World English Bible\x1b[0m");
    println!("\x1b[1;36m================================================================================\x1b[0m\n");

    let lex = BiblicalLexicon::new();
    if let Some(q) = query {
        let results = lex.search(q);
        if results.is_empty() {
            println!("No concepts found matching '{}'. Total concepts available: {}\n", q, lex.all_entries().len());
        } else {
            println!("\x1b[1;33mSEARCH RESULTS FOR '{}' ({} found):\x1b[0m\n", q, results.len());
            for e in results {
                println!("\x1b[1;32m[{}]\x1b[0m \x1b[1m{}\x1b[0m (State Resonance: +1:{})", e.domain.as_str(),
e.term.to_uppercase(), e.quad_state_resonance.macro_op());
                println!("  • Definition: {}", e.definition);
                println!("  • KJV:        {}", e.kjv_passage);
                println!("  • WEB:        {}", e.web_passage);
                println!("  • Guidance:   {}\n", e.moral_guidance);
            }
        }
    } else {
        println!("\x1b[1;33mCANONICAL VOCABULARY OVERVIEW ({} concepts available offline):\x1b[0m\n",
```

```
lex.all_entries().len());
            for e in lex.all_entries() {
                println!("  • \x1b[1;32m{:<20}\x1b[0m | Domain: {:<30} | Resonance: +1:{}", e.term, e.domain.as_str(),
e.quad_state_resonance.macro_op());
            }
            println!("\nTip: Query a specific concept with `omnicode lexicon <term>` (e.g. `omnicode lexicon truth`)\n");
        }
    }

    fn run_gui(port: u16, auto_open: bool, path: &str) {
        if auto_open {
            let url = format!("http://localhost:{port}{path}");
            thread::spawn(move || {
                thread::sleep(std::time::Duration::from_millis(300));
                omnicode::cogs::platform::HostPlatform::current().open_browser(&url);
            });
        }
        if let Err(e) = run_gui_server(port) {
            eprintln!("\x1b[1;31m✗ GUI Server Fatal Error:\x1b[0m {}", e);
            process::exit(1);
        }
    }



    fn run_hover(file: &str, line: usize, col: usize, as_json: bool) {
        let logger = DiagnosticLogger::new(false);
        let mut engine = HoverEngine::new(logger);
        engine.index_workspace(".");

        match engine.hover_at(file, line, col) {
            Some(card) => {
                if as_json {
                    println!("{}", card.to_json());
                } else {
                    println!("{}", card.render_terminal());
                }
            }
            None => {
                if as_json {
                    println!(r#"{{"symbol":"","found":false,"error":"No symbol found at coordinate"}}"#);
                } else {
                    eprintln!("\x1b[1;33m⚠ No symbol located at {}:{}:{}\x1b[0m", file, line, col);
                }
                process::exit(1);
            }
        }
    }

    fn run_doc(symbol: &str, file_hint: Option<&str>, as_json: bool) {
        let logger = DiagnosticLogger::new(false);
        let mut engine = HoverEngine::new(logger);
        engine.index_workspace(".");

        match engine.document_symbol(symbol, file_hint) {
            Some(card) => {
                if as_json {
                    println!("{}", card.to_json());
                } else {
                    println!("{}", card.render_terminal());
                }
            }
            None => {
                if as_json {
                    println!(r#"{{"symbol":"{}","found":false,"error":"Symbol definition not found"}}"#, symbol);
                } else {
                    eprintln!("\x1b[1;33m⚠ Symbol '{}' not found in workspace or target file\x1b[0m", symbol);
                }
                process::exit(1);
            }
        }
    }


    // ================================================================================
    // BLOCK 4: CLOSING BLOCK
    // ( CLI Main Entrypoint Dispatcher & Process Termination )
    // ================================================================================
```

```
fn main() {
    let args: Vec<String> = env::args().collect();

    if args.len() <= 1 {
        // Default behavior: launch interactive terminal environment (REPL)
        if let Err(e) = run_repl() {
            eprintln!("\x1b[1;31mFatal REPL Error:\x1b[0m {}", e);
            process::exit(1);
        }
        return;
    }

    match args[1].as_str() {
        "repl" => {
            if let Err(e) = run_repl() {
                eprintln!("\x1b[1;31mFatal REPL Error:\x1b[0m {}", e);
                process::exit(1);
            }
        }
        "terminal" | "term" | "shell" => {
            let port = if args.len() >= 4 && (args[2] == "--port" || args[2] == "-p") {
                args[3].parse::<u16>().unwrap_or(8080)
            } else if args.len() >= 3 && args[2].starts_with("--port=") {
                args[2]["--port=".len()..].parse::<u16>().unwrap_or(8080)
            } else if args.len() >= 3 && args[2] != "terminal" && args[2] != "term" {
                args[2].parse::<u16>().unwrap_or(8080)
            } else {
                8080
            };
            println!("\x1b[1;36mLaunching OmniCode Native Interactive Terminal (CreativeWorkzStudio LLC)...\x1b[0m");
            run_gui(port, true, "/terminal");
        }
        "project" => {
            if args.len() < 3 {
                eprintln!("\x1b[1;31mError:\x1b[0m Missing file path. Usage: omnicode project <file.tape>");
                process::exit(1);
            }
            run_studio(&args[2]);
        }
        "studio" => {
            if args.len() >= 3 && (args[2].ends_with(".tape") || args[2].ends_with(".omni") || !args[2].starts_with("-"))
&& args[2].parse::<u16>().is_err() {
                run_studio(&args[2]);
            } else {
                let port = if args.len() >= 4 && (args[2] == "--port" || args[2] == "-p") {
                    args[3].parse::<u16>().unwrap_or(8080)
                } else if args.len() >= 3 && args[2].starts_with("--port=") {
                    args[2]["--port=".len()..].parse::<u16>().unwrap_or(8080)
                } else if args.len() >= 3 && args[2] != "studio" {
                    args[2].parse::<u16>().unwrap_or(8080)
                } else {
                    8080
                };
                println!("\x1b[1;36mLaunching OmniCode Studio & Platform (CreativeWorkzStudio LLC)...\x1b[0m");
                run_gui(port, true, "/studio");
            }
        }
        "gui" | "serve" | "desktop" | "app" => {
            let port = if args.len() >= 4 && (args[2] == "--port" || args[2] == "-p") {
                args[3].parse::<u16>().unwrap_or(8080)
            } else if args.len() >= 3 && args[2].starts_with("--port=") {
                args[2]["--port=".len()..].parse::<u16>().unwrap_or(8080)
            } else if args.len() >= 3 && args[2] != "gui" && args[2] != "serve" && args[2] != "desktop" && args[2] !=
"app" {
                args[2].parse::<u16>().unwrap_or(8080)
            } else {
                8080
            };
            println!("\x1b[1;36mLaunching OmniCode Studio & Platform (CreativeWorkzStudio LLC)...\x1b[0m");
            run_gui(port, true, "/studio");
        }
        "boot" | "qemu" => {
            let config = BootConfig::from_args(&args);
            if let Err(e) = run_boot_with_config(config) {
                eprintln!("\x1b[1;31mMachine Inception Halted:\x1b[0m {e}");
                process::exit(1);
            }
        }
```

```
        "assemble" | "asm" => {
            let sub_args: Vec<String> = args.iter().skip(2).cloned().collect();
            let config = match AssembleConfig::from_args(&sub_args) {
                Ok(c) => c,
                Err(e) => {
                    eprintln!("\x1b[1;31mError:\x1b[0m {e}");
                    process::exit(1);
                }
            };
            if let Err(e) = run_assemble_with_config(config) {
                eprintln!("\x1b[1;31m✗ Assemble Tripwire Error:\x1b[0m {e}");
                process::exit(1);
            }
        }
        "run" => {
            if args.len() < 3 {
                eprintln!("\x1b[1;31mError:\x1b[0m Missing file path. Usage: omnicode run <file> [--format
omni|tape|c|lua] [--transpile c|lua]");
                process::exit(1);
            }
            let sub_args: Vec<String> = args.iter().skip(2).cloned().collect();
            let config = match RunConfig::from_args(&sub_args) {
                Ok(c) => c,
                Err(e) => {
                    eprintln!("\x1b[1;31mError:\x1b[0m {e}");
                    process::exit(1);
                }
            };
            match run_with_config(config) {
                Ok(res) => {
                    println!("{}", res.output);
                }
                Err(e) => {
                    eprintln!("\x1b[1;31m✗ Run Error:\x1b[0m {e}");
                    process::exit(1);
                }
            }
        }
        "echo" => {
            let verbose = args.iter().any(|a| a == "--verbose" || a == "-v" || a == "--log");
            let filtered_args: Vec<String> = args.iter().skip(2).filter(|a| !a.starts_with("-")).cloned().collect();
            let payload = filtered_args.join(" ");
            let unquoted = if (payload.starts_with('\'') && payload.ends_with('\'') && payload.len() >= 2)
                || (payload.starts_with('"') && payload.ends_with('"') && payload.len() >= 2)
            {
                &payload[1..payload.len() - 1]
            } else {
                &payload
            };
            match omnicode::terminal::universal::call_response_engine::EchoEngine::echo_stream(unquoted) {
                Ok(echoed_resp) => {
                    let echoed = &echoed_resp.echoed;
                    let mut log_details = String::new();
                    for (i, c) in unquoted.chars().enumerate() {
                        if let Ok(res) = omnicode::terminal::universal::call_response_engine::EchoEngine::echo_char(c) {
                            log_details.push_str(&format!(
                                "  [{:>2}] Glyph: '{}' | Code: {:>3} (0x{:02X}) | 5-Trits: {:?} | Footprint: {} Cell |
State: +1:{}\n",
                                i + 1, res.glyph, res.glyph as u32, res.glyph as u32, res.trits, res.cell_footprint,
res.state.macro_op()
                            ));
                        }
                    }

                    // Inscribe persistent dual log (scroll and telemetry log)
                    let session_id = format!("echo_{}", std::process::id());
                    let timestamp_str = omnicode::ai::model::scroll::generate_timestamp_id();
                    let scroll = omnicode::ai::model::scroll::ExecutionScroll {
                        session_id,
                        timestamp_str,
                        prompt: format!("Echo call: \"{unquoted}\""),
                        synthesized_omnicode: format!("# Character Transduction Echo Reel\necho [ \"{unquoted}\" ] => [
\"{echoed}\" ]\n"),
                        execution_state: omnicode::core::ternary::QuadState::Proceed,
                        natural_response: format!("Echoed: \"{echoed}\""),
                        failpoints: Vec::new(),
                        repairs_applied: Vec::new(),
                        remediations_suggested: Vec::new(),
```

```
                        elapsed_micros: 100,
                    };
                    let saved_paths = omnicode::ai::model::scroll::ScrollLogger::default().save_dual_logs(&scroll).ok();

                    if verbose {
                        println!
("\x1b[1;36m================================================================================\x1b[0m");
                        println!("\x1b[1;36m  OMNICODE PRIMORDIAL ECHO: CHARACTER TRANSDUCTION TELEMETRY LOG
\x1b[0m");
                        println!
("\x1b[1;36m================================================================================\x1b[0m");
                        println!("  • Call Input (FROM Port 0x03F8):        \"{}\"", unquoted);
                        println!("  • Response Output (INTO Port 0x000B8000): \"{}\"", echoed);
                        println!("  • Stream Length:                        {} glyph(s)", echoed.len());
                        if let Some((ref sp, ref lp)) = saved_paths {
                            println!("  • Inscribed Episodic Scroll:            {:?}", sp);
                            println!("  • Inscribed Telemetry Log:              {:?}", lp);
                        }
                        println!("--------------------------------------------------------------------------------");
                        print!("{log_details}");
                        println!("--------------------------------------------------------------------------------");
                        println!("\x1b[1;32m✓ Parity Verified:\x1b[0m Call-Response dialogue sealed in equilibrium
(State: +1:PROCEED)\n");
                    } else {
                        println!("{echoed}");
                    }
                }
                Err(e) => {
                    eprintln!("\x1b[1;31m✗ Echo Anomaly:\x1b[0m {e}");
                    process::exit(1);
                }
            }
        }
        "lint" => {
            if args.len() < 3 {
                eprintln!("\x1b[1;31mError:\x1b[0m Missing file path. Usage: omnicode lint <file.omni>");
                process::exit(1);
            }
            run_lint_file(&args[2]);
        }
        "hover" => {
            if args.len() < 5 {
                eprintln!("\x1b[1;31mError:\x1b[0m Usage: omnicode hover <file> <line> <col> [--json]");
                process::exit(1);
            }
            let file = &args[2];
            let line = args[3].parse::<usize>().unwrap_or(1);
            let col = args[4].parse::<usize>().unwrap_or(1);
            let as_json = args.iter().any(|a| a == "--json" || a == "-j");
            run_hover(file, line, col, as_json);
        }
        "doc" | "explain" => {
            if args.len() < 3 {
                eprintln!("\x1b[1;31mError:\x1b[0m Usage: omnicode doc <symbol> [--file <path>] [--json]");
                process::exit(1);
            }
            let symbol = &args[2];
            let as_json = args.iter().any(|a| a == "--json" || a == "-j");
            let file_hint = args.iter().position(|a| a == "--file" || a == "-f").and_then(|idx| args.get(idx + 1).map(|s|
s.as_str()));
            run_doc(symbol, file_hint, as_json);
        }
        "restore" => {
            if args.len() < 3 {
                eprintln!("\x1b[1;31mError:\x1b[0m Missing file path. Usage: omnicode restore <file.omni> [--write]");
                process::exit(1);
            }
            let in_place = args.iter().any(|a| a == "--write" || a == "-w");
            run_restore(&args[2], in_place);
        }
        "query" => {
            if args.len() < 3 {
                eprintln!(
                    "\x1b[1;31mError:\x1b[0m Missing session ID. \
                     Usage: omnicode query <session_id>"
                );
                process::exit(1);
            }
```

```
            run_query(&args[2]);
        }
        "diagnose" => {
            if args.len() < 3 {
                eprintln!(
                    "\x1b[1;31mError:\x1b[0m Missing session ID. \
                     Usage: omnicode diagnose <session_id>"
                );
                process::exit(1);
            }
            run_diagnose(&args[2]);
        }
        "rotate" => {
            let cap = if args.len() >= 3 {
                if args[2].starts_with("--cap=") {
                    args[2]["--cap=".len()..]
                        .parse::<usize>()
                        .unwrap_or(1000)
                } else if (args[2] == "--cap" || args[2] == "-c")
                    && args.len() >= 4
                {
                    args[3].parse::<usize>().unwrap_or(1000)
                } else {
                    args[2].parse::<usize>().unwrap_or(1000)
                }
            } else {
                1000
            };
            run_rotate(cap);
        }
        "interact" | "chat" | "cpisi" => {
            run_interact();
        }
        "train" => {
            run_train();
        }
        "noise" => {
            let stress = args.get(2).and_then(|s| s.parse::<f64>().ok());
            run_noise(stress);
        }
        "ai" => {
            if args.len() < 3 {
                eprintln!(
                    "\x1b[1;31mError:\x1b[0m Missing prompt. \
                     Usage: omnicode ai \"<prompt>\" | omnicode ai query <id>"
                );
                process::exit(1);
            }
            if args[2] == "query" {
                if args.len() < 4 {
                    eprintln!(
                        "\x1b[1;31mError:\x1b[0m Usage: omnicode ai query \
                         <session_id>"
                    );
                    process::exit(1);
                }
                run_query(&args[3]);
            } else if args[2] == "diagnose" {
                if args.len() < 4 {
                    eprintln!(
                        "\x1b[1;31mError:\x1b[0m Usage: omnicode ai \
                         diagnose <session_id>"
                    );
                    process::exit(1);
                }
                run_diagnose(&args[3]);
            } else if args[2] == "interact" || args[2] == "chat" {
                run_interact();
            } else if args[2] == "train" {
                run_train();
            } else if args[2] == "noise" {
                let stress = args.get(3).and_then(|s| s.parse::<f64>().ok());
                run_noise(stress);
            } else {
                let mut verbose = false;
                let mut prompt_parts = Vec::new();
                for a in &args[2..] {
                    if a == "--verbose" || a == "-v" {
```

```
                        verbose = true;
                    } else {
                        prompt_parts.push(a.as_str());
                    }
                }
                if prompt_parts.is_empty() {
                    eprintln!(
                        "\x1b[1;31mError:\x1b[0m Missing prompt. \
                         Usage: omnicode ai [-v|--verbose] \"<prompt>\""
                    );
                    process::exit(1);
                }
                let prompt = prompt_parts.join(" ");
                run_ai(&prompt, verbose);
            }
        }
        "scrolls" | "history" | "learn" => {
            run_scrolls();
        }
        "manifest" => {
            run_manifest();
        }
        "lexicon" | "bible" | "vocab" => {
            let query = args.get(2).map(|s| s.as_str());
            run_lexicon(query);
        }
        "filetypes" | "types" => {
            run_filetypes();
        }
        "scaffold" => {
            let (name, kind) = if args.len() >= 4 && (args[2] == "--type" || args[2] == "-t") {
                (args.get(4).map(|s| s.as_str()).unwrap_or("MyModule"), Some(args[3].as_str()))
            } else if args.len() >= 4 && (args[3] == "--type" || args[3] == "-t") {
                (args[2].as_str(), args.get(4).map(|s| s.as_str()))
            } else if args.len() >= 4 && (args[2] == "scroll" || args[2] == "omni") {
                (args[3].as_str(), Some(args[2].as_str()))
            } else if args.len() >= 3 {
                (args[2].as_str(), None)
            } else {
                ("MyModule", None)
            };
            run_scaffold(name, kind);
        }
        "demo" => {
            run_demo();
        }
        "--help" | "-h" | "help" => {
            print_cli_help();
        }
        "--version" | "-v" | "version" => {
            print_version();
        }
        other => {
            eprintln!("\x1b[1;31mUnknown argument:\x1b[0m '{}'", other);
            print_cli_help();
            process::exit(1);
        }
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/core/boundaries.rs RS 167 LINES 778 WORDS 6.9 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Module Identity, Morphological Boundary Invariants & Delimiter Tables )
// ================================================================================
//! OmniCode Core: Boundary Mechanics & Morphological Delimiters
//!
//! Delimiters are active morphological operators that govern the boundary physics
//! between an entity and its surrounding universe.
//!
//! The 6 Canonical Boundaries:
//!     1. Denotation  : [ ... ]  (Mutable Definition)
//!     2. Invariant   : < ... >  (Immutable Axiom / Constant)
//!     3. Connotation : { ... }  (In Context Of / Environment)
//!     4. TopDown     : { ... ]  (Context Defines Entity)
//!     5. BottomUp    : [ ... }  (Entity Defined by Context)
//!     6. Aside       : ( ... )  (Aside To / First-Class Machine Intent)

use std::fmt;


// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Context Declarations, BoundaryType Enum, and Delimiter Mapping )
// ================================================================================
/// Morphological boundary types ranked by ontological hierarchy:
///   Rank 1: < ... > (Invariant / Axiom / Law)
///   Rank 2: [ ... ] (Denotation / Essence / Mutable State)
///   Rank 3: { ... } (Connotation / Ambient Context / Environment)
///   Rank 4: [ ... } (Bottom-Up / Inside-Out / Projection into Context)
///   Rank 5: { ... ] (Top-Down / Outside-In / Imposition by Context)
///   Rank 6: ( ... ) (Aside / First-Class Intent / Observer Rationale)
#[derive(Debug, Clone, Copy, PartialEq, Eq, PartialOrd, Ord, Hash)]
pub enum BoundaryType {
    /// Rank 1: < ... > Immutable Axiom / Law
    Invariant,
    /// Rank 2: [ ... ] Mutable Definition / Essence / State
    Denotation,
    /// Rank 3: { ... } Ambient Context / Environment
    Connotation,
    /// Rank 4: [ ... } Defined by context (Inside-Out / Emergent)
    BottomUp,
    /// Rank 5: { ... ] Context defines (Outside-In / Imposition)
    TopDown,
    /// Rank 6: ( ... ) Aside to (Intent / Observer Rationale)
    Aside,
}


// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Core Resolution Logic: Boundary Properties, Directionality, Pair Matching )
// ================================================================================
impl BoundaryType {
    /// Returns the ontological rank of the boundary (1 = Highest authority / ground truth).
    pub fn rank(&self) -> u8 {
        match self {
            BoundaryType::Invariant => 1,
            BoundaryType::Denotation => 2,
            BoundaryType::Connotation => 3,
            BoundaryType::BottomUp => 4,
            BoundaryType::TopDown => 5,
            BoundaryType::Aside => 6,
        }
    }

    /// Descriptive name of the ontological rank tier.
    pub fn rank_name(&self) -> &'static str {
        match self {
            BoundaryType::Invariant => "Rank 1: Axiomatic Invariant",
            BoundaryType::Denotation => "Rank 2: Denotative Essence",
            BoundaryType::Connotation => "Rank 3: Connotative Environment",
            BoundaryType::BottomUp => "Rank 4: Inside-Out Emergence",
            BoundaryType::TopDown => "Rank 5: Outside-In Imposition",
            BoundaryType::Aside => "Rank 6: Intentional Aside",
```

```
        }
    }

    /// Natural language grammatical clause template for this boundary.
    pub fn linguistic_clause(&self) -> &'static str {
        match self {
            BoundaryType::Invariant => "It is an invariant law that",
            BoundaryType::Denotation => "The entity defines and executes",
            BoundaryType::Connotation => "In the context of the ambient universe",
            BoundaryType::BottomUp => "Projecting outward from entity into context",
            BoundaryType::TopDown => "As conditioned and imposed by the context",
            BoundaryType::Aside => "With the intent and rationale that",
        }
    }

    /// Returns the (open, close) character pair for this boundary type.
    pub fn delimiters(&self) -> (char, char) {
        match self {
            BoundaryType::Invariant => ('<', '>'),
            BoundaryType::Denotation => ('[', ']'),
            BoundaryType::Connotation => ('{', '}'),
            BoundaryType::BottomUp => ('[', '}'),
            BoundaryType::TopDown => ('{', ']'),
            BoundaryType::Aside => ('(', ')'),
        }
    }

    /// True if opening and closing delimiters come from different bracket families.
    pub fn is_asymmetric(&self) -> bool {
        matches!(self, BoundaryType::TopDown | BoundaryType::BottomUp)
    }

    /// True if boundary enforces unalterable immutability.
    pub fn is_immutable(&self) -> bool {
        matches!(self, BoundaryType::Invariant)
    }

    /// Resolves opening and closing characters into a valid BoundaryType.
    ///
    /// # Failpoint
    /// Returns `Err` if the pair forms an illegal boundary (e.g. `(`, `]` or `{`, `>`).
    pub fn from_delimiters(open: char, close: char) -> Result<Self, String> {
        match (open, close) {
            ('[', ']') => Ok(BoundaryType::Denotation),
            ('<', '>') => Ok(BoundaryType::Invariant),
            ('{', '}') => Ok(BoundaryType::Connotation),
            ('{', ']') => Ok(BoundaryType::TopDown),
            ('[', '}') => Ok(BoundaryType::BottomUp),
            ('(', ')') => Ok(BoundaryType::Aside),
            (o, c) => Err(format!(
                "FAILPOINT [IllegalBoundaryPair]: Delimiter pair '{o}...{c}' does not form a legal boundary. \
                 Legal pairs: [...] (Denotation), <...> (Invariant), {{...}} (Connotation), \
                 {{...] (Top-Down), [...}} (Bottom-Up), (...) (Aside)"
            )),
        }
    }
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Display Trait Verification and String Formatter )
// ============================================================================
impl fmt::Display for BoundaryType {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        let (o, c) = self.delimiters();
        write!(f, "{:?}({o}...{c})", self)
    }
}

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_boundary_ranking_hierarchy() {
        assert_eq!(BoundaryType::Invariant.rank(), 1);
        assert_eq!(BoundaryType::Denotation.rank(), 2);
```

```
        assert_eq!(BoundaryType::Connotation.rank(), 3);
        assert_eq!(BoundaryType::BottomUp.rank(), 4);
        assert_eq!(BoundaryType::TopDown.rank(), 5);
        assert_eq!(BoundaryType::Aside.rank(), 6);

        // Verify ordinal comparison preserves exact hierarchy
        assert!(BoundaryType::Invariant < BoundaryType::Denotation);
        assert!(BoundaryType::Denotation < BoundaryType::Connotation);
        assert!(BoundaryType::Connotation < BoundaryType::BottomUp);
        assert!(BoundaryType::BottomUp < BoundaryType::TopDown);
        assert!(BoundaryType::TopDown < BoundaryType::Aside);
    }
}

```

<TRACK 1> : {Host Engine & Virtual Machine}/src/core/cell.rs RS 345 LINES 1236 WORDS 11.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Cell Engine Identity, 8-bit to 5-Trit Codec, & Balanced Radix-3 Mapping )
// ============================================================================
//! OmniCode Core: Cell Architecture & Byte-Trit Hardware Transducer
//!
//! Provides the physical hardware bridge between 8-bit binary silicon
//! and OmniCode's Balanced Ternary Quad-State physics:
//!     - 8 Bits (256 states) <--> 5 Trits (243 symmetric states) + 13 Control Traps
//!     - Dense packing: 1 Cell = exactly 1 physical byte (zero struct overhead)
//!     - Invariant Out-of-band Quad-States:
//!         * 243: NULL / HALT (Void / Unmapped memory)
//!         * 244: AWAIT (Superposition / Pending / Lock)
//!         * 245: ROLLBACK (Veto / Tainted / Unwound cell)
//!         * 246: PROCEED (Affirmative sealed landmark)
//!         * 247..255: Hardware Traps & System Landmarks

use std::fmt;
use crate::core::linguistics::{GrammaticalClassification, GrammaticalEntity, PartOfSpeech};
use crate::core::ternary::QuadState;


// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Out-of-Band Constants, Trit Definition, and Cell Structures )
// ============================================================================

pub const BYTE_HALT: u8 = 243;
pub const BYTE_AWAIT: u8 = 244;
pub const BYTE_ROLLBACK: u8 = 245;
pub const BYTE_PROCEED: u8 = 246;
pub const BYTE_TRAP_BASE: u8 = 247;
pub const MAX_NATURAL_CELL_VALUE: u8 = 242;
pub const MIN_SIGNED_CELL_VALUE: i8 = -121;
pub const MAX_SIGNED_CELL_VALUE: i8 = 121;

/// The atomic ternary digit (Radix-3 balanced unit).
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum Trit {
    /// -1: Negative polarity / Contra (denoted 'T')
    Neg,
    ///  0: Neutral balance / Equilibrium (denoted '0')
    Zero,
    /// +1: Positive polarity / Affirmation (denoted '1')
    Pos,
}

impl Trit {
    pub fn as_i8(&self) -> i8 {
        match self {
            Trit::Neg => -1,
            Trit::Zero => 0,
            Trit::Pos => 1,
        }
    }

    pub fn from_i8(val: i8) -> Result<Self, String> {
        match val {
            -1 => Ok(Trit::Neg),
            0 => Ok(Trit::Zero),
            1 => Ok(Trit::Pos),
            other => Err(format!("FAILPOINT [InvalidTrit]: '{other}' is not in {{-1, 0, +1}}")),
        }
    }

    pub fn char_symbol(&self) -> char {
        match self {
            Trit::Neg => 'T',
            Trit::Zero => '0',
            Trit::Pos => '1',
        }
    }

    /// Algebraic negation of a trit: NOT(x) = -x.
```

```rust
    pub fn negate(&self) -> Self {
        match self {
            Trit::Neg => Trit::Pos,
            Trit::Zero => Trit::Zero,
            Trit::Pos => Trit::Neg,
        }
    }
}

impl fmt::Display for Trit {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        write!(f, "{}", self.char_symbol())
    }
}

/// The atomic storage unit of memory in OmniCode.
///
/// Holds 5 balanced trits (spanning 243 values) alongside its Quad-State resonance.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub struct Cell {
    pub trits: [Trit; 5],
    pub state: QuadState,
    pub is_marker: bool,
}


// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Mathematical Conversion, Packing, Unpacking, and Word Operations )
// ============================================================================

impl Cell {
    /// Constructs a Cell with explicit trits and Quad-State.
    pub fn new(trits: [Trit; 5], state: QuadState) -> Self {
        Self { trits, state, is_marker: false }
    }

    /// Creates an empty cell at equilibrium (0 in value, AWAIT in state).
    pub fn equilibrium() -> Self {
        Self {
            trits: [Trit::Zero; 5],
            state: QuadState::Await,
            is_marker: true,
        }
    }

    /// Creates a cell initialized with a pure out-of-band Quad-State marker.
    pub fn from_state(state: QuadState) -> Self {
        Self {
            trits: [Trit::Zero; 5],
            state,
            is_marker: true,
        }
    }

    /// Encodes a natural number in [0 ..= 242] into a 5-trit Cell with state PROCEED.
    pub fn from_natural(value: u8) -> Result<Self, String> {
        if value > MAX_NATURAL_CELL_VALUE {
            return Err(format!(
                "FAILPOINT [CellOverflow]: Value {value} exceeds single-cell capacity ({MAX_NATURAL_CELL_VALUE}). \
                 Use multi-cell Word chaining."
            ));
        }
        let signed_val = (value as i16) + (MIN_SIGNED_CELL_VALUE as i16);
        Self::from_signed(signed_val as i8)
    }

    /// Encodes a signed balanced integer in [-121 ..= +121] into 5 balanced trits.
    pub fn from_signed(value: i8) -> Result<Self, String> {
        if !(MIN_SIGNED_CELL_VALUE..=MAX_SIGNED_CELL_VALUE).contains(&value) {
            return Err(format!(
                "FAILPOINT [CellRangeError]: Signed value {value} out of range [{MIN_SIGNED_CELL_VALUE} ..=
{MAX_SIGNED_CELL_VALUE}]."
            ));
        }

        let mut x = value;
        let mut trits = [Trit::Zero; 5];
```

```
        for i in 0..5 {
            let rem = ((x % 3) + 3) % 3;
            match rem {
                0 => {
                    trits[i] = Trit::Zero;
                    x /= 3;
                }
                1 => {
                    trits[i] = Trit::Pos;
                    x = (x - 1) / 3;
                }
                2 => {
                    trits[i] = Trit::Neg;
                    x = (x + 1) / 3;
                }
                _ => unreachable!(),
            }
        }

        Ok(Self {
            trits,
            state: QuadState::Proceed,
            is_marker: false,
        })
    }

    /// Decodes the 5 trits back to a signed integer in [-121 ..= +121].
    pub fn to_signed(&self) -> Option<i8> {
        if self.is_marker || self.state == QuadState::Halt {
            return None;
        }

        let mut total: i32 = 0;
        let mut multiplier: i32 = 1;

        for trit in &self.trits {
            total += (trit.as_i8() as i32) * multiplier;
            multiplier *= 3;
        }

        Some(total as i8)
    }

    /// Decodes the 5 trits back to a natural number in [0 ..= 242].
    pub fn to_natural(&self) -> Option<u8> {
        self.to_signed().map(|s| (s as i16 - (MIN_SIGNED_CELL_VALUE as i16)) as u8)
    }

    /// Packs this Cell into a single physical 8-bit byte.
    pub fn pack(&self) -> u8 {
        if self.is_marker {
            match self.state {
                QuadState::Halt => BYTE_HALT,
                QuadState::Await => BYTE_AWAIT,
                QuadState::Rollback => BYTE_ROLLBACK,
                QuadState::Proceed => BYTE_PROCEED,
            }
        } else {
            self.to_natural().unwrap_or(BYTE_HALT)
        }
    }

    /// Unpacks a single physical 8-bit byte into a Cell with full 5-trit fidelity and Quad-State.
    pub fn unpack(byte: u8) -> Self {
        match byte {
            BYTE_HALT => Self::from_state(QuadState::Halt),
            BYTE_AWAIT => Self::from_state(QuadState::Await),
            BYTE_ROLLBACK => Self::from_state(QuadState::Rollback),
            BYTE_PROCEED => Self::from_state(QuadState::Proceed),
            trap if trap >= BYTE_TRAP_BASE => {
                // Reserved system trap / hardware landmark
                Self::from_state(QuadState::Halt)
            }
            natural => {
                Self::from_natural(natural).unwrap_or_else(|_| Self::from_state(QuadState::Halt))
            }
        }
```

```
    }
}

impl GrammaticalEntity for Cell {
    fn classify(&self) -> GrammaticalClassification {
        GrammaticalClassification::new(
            PartOfSpeech::Noun,
            Some(PartOfSpeech::Preposition),
            None,
            "Atomic memory vessel; stores 5 balanced trits and Quad-State resonance",
            "Single 8-bit memory byte carrying payload and state",
        )
    }
}

impl GrammaticalEntity for Trit {
    fn classify(&self) -> GrammaticalClassification {
        GrammaticalClassification::new(
            PartOfSpeech::Noun,
            Some(PartOfSpeech::Adjective),
            None,
            "Atomic ternary digit (-1, 0, +1)",
            "Single Radix-3 unit of computational polarity",
        )
    }
}

impl fmt::Display for Cell {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        if self.state == QuadState::Halt {
            write!(f, "Cell[NULL]")
        } else if let Some(nat) = self.to_natural() {
            write!(
                f,
                "Cell[Val:{nat} | {}{}{}{}{} | {:?}]",
                self.trits[4], self.trits[3], self.trits[2], self.trits[1], self.trits[0], self.state
            )
        } else {
            write!(f, "Cell[{:?}]", self.state)
        }
    }
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Bijective Round-Trip Verification & Mathematical Unit Tests )
// ============================================================================
#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_signed_round_trip_all_243_values() {
        for s in MIN_SIGNED_CELL_VALUE..=MAX_SIGNED_CELL_VALUE {
            let cell = Cell::from_signed(s).expect("Signed conversion must succeed");
            let recovered = cell.to_signed().expect("To signed must succeed");
            assert_eq!(s, recovered, "Failed round-trip for signed value {s}");
        }
    }

    #[test]
    fn test_natural_round_trip_all_243_values() {
        for n in 0..=MAX_NATURAL_CELL_VALUE {
            let cell = Cell::from_natural(n).expect("Natural conversion must succeed");
            let recovered = cell.to_natural().expect("To natural must succeed");
            assert_eq!(n, recovered, "Failed round-trip for natural number {n}");

            // Verify physical 8-bit byte pack and unpack
            let packed_byte = cell.pack();
            assert_eq!(packed_byte, n);
            let unpacked_cell = Cell::unpack(packed_byte);
            assert_eq!(unpacked_cell.to_natural(), Some(n));
            assert_eq!(unpacked_cell.state, QuadState::Proceed);
        }
    }

    #[test]
```

```
    fn test_out_of_band_quad_state_markers() {
        // Test HALT (NULL)
        let halt_cell = Cell::from_state(QuadState::Halt);
        let packed_halt = halt_cell.pack();
        assert_eq!(packed_halt, BYTE_HALT);
        let unpacked_halt = Cell::unpack(packed_halt);
        assert_eq!(unpacked_halt.state, QuadState::Halt);

        // Test AWAIT
        let await_cell = Cell::from_state(QuadState::Await);
        let packed_await = await_cell.pack();
        assert_eq!(packed_await, BYTE_AWAIT);
        let unpacked_await = Cell::unpack(packed_await);
        assert_eq!(unpacked_await.state, QuadState::Await);

        // Test ROLLBACK
        let rollback_cell = Cell::from_state(QuadState::Rollback);
        let packed_rollback = rollback_cell.pack();
        assert_eq!(packed_rollback, BYTE_ROLLBACK);
        let unpacked_rollback = Cell::unpack(packed_rollback);
        assert_eq!(unpacked_rollback.state, QuadState::Rollback);

        // Test PROCEED marker
        let proceed_cell = Cell::from_state(QuadState::Proceed);
        assert_eq!(proceed_cell.pack(), BYTE_PROCEED);
        let unpacked_proceed = Cell::unpack(BYTE_PROCEED);
        assert_eq!(unpacked_proceed.state, QuadState::Proceed);
    }

    #[test]
    fn test_zero_and_equilibrium_properties() {
        let zero_cell = Cell::from_signed(0).unwrap();
        assert_eq!(zero_cell.trits, [Trit::Zero; 5]);
        assert_eq!(zero_cell.to_signed(), Some(0));
        assert_eq!(zero_cell.to_natural(), Some(121)); // 121 is the balanced center of [0 .. 242]
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/core/filetype.rs RS 420 LINES 1554 WORDS 16.3 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( OmniCode File Type Subsystem Identity, Taxonomy & Invariants )
// ============================================================================
//! OmniCode File Type Taxonomy & Formal Extension System
//!
//! Classifies and handles all recognized OmniCode file artifacts:
//!   - `.omni`: Canonical OmniCode Source Reel (Primary executable program logic,
//!     modules, libraries, and ontological domain models).
//!   - `.scroll`: Cognitive Episodic Scroll (Homoiconic execution trace reel,
//!     recording prompts, synthesized programs, Restorator repairs, failpoints,
//!     and natural responses for AI continual learning).

use std::fmt;
use std::path::Path;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( File Type Enumeration, Mime Types, and Constructor Declarations )
// ============================================================================
/// Formal file classifications in the OmniCode ecosystem.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum OmniFileType {
    /// `.omni` - Canonical executable source reel.
    SourceReel,
    /// `.scroll` - Homoiconic episodic cognitive trace and AI learning reel.
    EpisodicScroll,
    /// `.tape` - Sequential execution process tape led by a Tape Head.
    Tape,
}

pub const ALL_FILE_TYPES: [OmniFileType; 3] = [
    OmniFileType::SourceReel,
    OmniFileType::EpisodicScroll,
    OmniFileType::Tape,
];

impl OmniFileType {
    pub const EXT_OMNI: &'static str = "omni";
    pub const EXT_SCROLL: &'static str = "scroll";
    pub const EXT_TAPE: &'static str = "tape";

    pub const ALL: &'static [OmniFileType] = &ALL_FILE_TYPES;

    /// Returns all supported OmniCode file types.
    pub fn all() -> &'static [OmniFileType] {
        Self::ALL
    }

    /// Detects file type from extension string (with or without leading dot).
    pub fn from_extension(ext: &str) -> Option<Self> {
        let clean = ext.trim().trim_start_matches('.').to_lowercase();
        match clean.as_str() {
            "omni" => Some(OmniFileType::SourceReel),
            "scroll" => Some(OmniFileType::EpisodicScroll),
            "tape" => Some(OmniFileType::Tape),
            _ => None,
        }
    }

    /// Detects file type from a file path.
    pub fn from_path(path: impl AsRef<Path>) -> Option<Self> {
        let p = path.as_ref();
        p.extension()
            .and_then(|ext| ext.to_str())
            .and_then(Self::from_extension)
    }

    /// Checks if a file path is a known OmniCode artifact.
    pub fn is_omnicode_file(path: impl AsRef<Path>) -> bool {
        Self::from_path(path).is_some()
    }
}

```

```
// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Metadata Queries, Scaffolding Templates & Formatting Properties )
// ================================================================================
impl OmniFileType {
    /// Canonical file extension without leading dot.
    pub fn extension(&self) -> &'static str {
        match self {
            OmniFileType::SourceReel => Self::EXT_OMNI,
            OmniFileType::EpisodicScroll => Self::EXT_SCROLL,
            OmniFileType::Tape => Self::EXT_TAPE,
        }
    }

    /// File extension with leading dot.
    pub fn dotted_extension(&self) -> &'static str {
        match self {
            OmniFileType::SourceReel => ".omni",
            OmniFileType::EpisodicScroll => ".scroll",
            OmniFileType::Tape => ".tape",
        }
    }

    /// Human-readable display title.
    pub fn display_name(&self) -> &'static str {
        match self {
            OmniFileType::SourceReel => "OmniCode Source Reel",
            OmniFileType::EpisodicScroll => "OmniCode Episodic Scroll",
            OmniFileType::Tape => "OmniCode Process Tape",
        }
    }

    /// VS Code / IDE language identifier.
    pub fn language_id(&self) -> &'static str {
        "omnicode"
    }

    /// Formal MIME type.
    pub fn mime_type(&self) -> &'static str {
        match self {
            OmniFileType::SourceReel => "text/x-omnicode",
            OmniFileType::EpisodicScroll => "text/x-omnicode-scroll",
            OmniFileType::Tape => "text/x-omnicode-tape",
        }
    }

    /// Short technical summary.
    pub fn description(&self) -> &'static str {
        match self {
            OmniFileType::SourceReel => {
                "Canonical 4-Block executable program module conforming to balanced ternary physics."
            }
            OmniFileType::EpisodicScroll => {
                "Homoiconic episodic execution reel recording cognitive discourse, repairs, and telemetry."
            }
            OmniFileType::Tape => {
                "Sequential process tape consisting of a leading Tape Head and subordinate rolls."
            }
        }
    }

    /// Generates canonical 4-Block scaffolding template for this file type.
    pub fn scaffold_template(&self, identifier: &str, intent_or_prompt: &str) -> String {
        match self {
            OmniFileType::SourceReel => {
                format!(
r#"# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( File Identity, Version, Author, Intent Aside, and Invariants )
# ================================================================================
Module < {name} > ( {intent} ) {{
    version: < "0.1.0" >,
    system: < OmniCode.Core >,
    safety: < MemorySafe :: Deterministic >
}}

# Invariant Axioms & Types
Type_{name} < +1 > ( Invariant definition )
```

```
153
154 # ================================================================================
155 # BLOCK 2: OPENING BLOCK
156 # ( Environment Setup, Preconditions, Scoped Context, and Declarations )
157 # ================================================================================
158 Opening {{
159     import: [ Core.Arithmetic :: Core.Logic :: Core.Vectors ],
160     preconditions: [ +1 ]
161 }}
162
163 # Initial state instance
164 state [ +1 ] ( Initialized state instance )
165
166 # ================================================================================
167 # BLOCK 3: BODY BLOCK
168 # ( Core Transformations, Causality Vectors, Logic, and Caveat Pipelines )
169 # ================================================================================
170 Body [
171     # Forward action: state acts upon transformation
172     state --> next_state [ +1 ]
173     next_state ! [ state = +1 ] ( Caveat verification )
174 ]
175
176 # ================================================================================
177 # BLOCK 4: CLOSING BLOCK
178 # ( Postconditions, Invariant Proofs, Teardown, and Commit Status )
179 # ================================================================================
180 Closing {{
181     verify: [ next_state = +1 ],
182     commit_status [ +1 ] ( Commit verified state )
183 }}
184 "#,
185                     name = identifier,
186                     intent = intent_or_prompt
187                 )
188             }
189             OmniFileType::EpisodicScroll => {
190                 format!(
191 r#"# ================================================================================
192 # BLOCK 1: METADATA BLOCK (THE COGNITIVE SCROLL)
193 # ( Execution Trace ID, Prompt Intent, Inferred Types, and Neural Snapshot )
194 # ================================================================================
195 Scroll < EpistemicTrace.{session} > ( {prompt} ) {{
196     version: < "1.0.0" >,
197     system: < OmniCode.AI.Model >,
198     timestamp: < "{timestamp}" >,
199     session_id: < "{session}" >,
200     cognitive_mode: < NeuralSymbolicTransduction >
201 }}
202
203 # ================================================================================
204 # BLOCK 2: OPENING BLOCK (EXPERIENCE INITIALIZATION)
205 # ( Hardware Invariants, Preconditions, and Initial Context )
206 # ================================================================================
207 Opening {{
208     import: [ Core.Arithmetic :: Core.Logic :: Core.Vectors ],
209     preconditions: [ +1 ]
210 }}
211
212 # Original Cognitive Discourse Prompt:
213 user_prompt < "{prompt}" >
214
215 # ================================================================================
216 # BLOCK 3: BODY BLOCK (CHRONICLE OF EXECUTION & RESTORATION)
217 # ( Replay Tape: Synthesized Program, Sensory Telemetry & Immune Interventions )
218 # ================================================================================
219 Body [
220     # Immune System Interventions (Restorator):
221     repair_entry [ L1: CleanExecution --> "Zero repairs required." ]
222
223     # Executed Turing Reel:
224     synthesized_reel [
225         state [ +1 ]
226     ]
227 ]
228
229 # ================================================================================
230 # BLOCK 4: CLOSING BLOCK (EPISODIC COMMIT & LEARNING PROOF)
```

```
# ( Verification Proof, Final Quad-State, and Conversational Synthesis )
# ================================================================================
Closing {{
    commit_status [ <PROCEED> ],
    machine_utterance ( "Execution verified to +1:PROCEED." )
}}
"#,
                    session = identifier,
                    prompt = intent_or_prompt,
                    timestamp = "0"
                )
            }
            OmniFileType::Tape => {
                format!(
r#"# ================================================================================
# TAPE HEAD (COVENANT DECLARATION & PROCESS MANIFEST)
# ================================================================================
[Tape.{name}] : WHO {{Process}} --> DISPATCH {{{name}}}
    WHERE {{partition}} = [ 256 ]
    WHEN {{Mount}}
    WHY ( {intent} )
    HOW [ +1 : PROCEED ]
    :: < covenant > ( verified )

# ================================================================================
# SUBORDINATE ROLLS (SEQUENTIAL EXECUTION STREAM)
# ================================================================================
roll_1 [ 10 --> Buf @ 0 ] ( Inscribe initial state into cell 0 )
roll_2 [ Buf[0] = 10 ! [ +1 ] ] ( Verify invariant bounds )
roll_3 [ commit_status [ PROCEED ] ] ( Tape execution completed successfully )
"#,
                    name = identifier,
                    intent = intent_or_prompt
                )
            }
        }
    }
}

/// Resolves a requested file path against the canonical 6-Track filesystem hierarchy.
///
/// If `path` exists directly as specified, it is returned immediately.
/// Otherwise, searches through the designated Track directories:
/// - `<TRACK 0> : {Silicon & Bare-Metal Kernel}`
/// - `<TRACK 1> : {Host Engine & Virtual Machine}`
/// - `<TRACK 2> : {OmniCode Language & Standard Library}`
/// - `<TRACK 3> : {Applications & OmniStudio Interfaces}`
/// - `<TRACK 4> : {Variable Storage & Episodic Memory}`
/// - `<TRACK 5> : {Infrastructure, Operations & Archives}`
pub fn resolve_track_path(path: impl AsRef<Path>) -> std::path::PathBuf {
    let p = path.as_ref();
    if p.exists() {
        return p.to_path_buf();
    }

    const TRACK_PREFIXES: [&str; 6] = [
        "<TRACK 2> : {OmniCode Language & Standard Library}",
        "<TRACK 3> : {Applications & OmniStudio Interfaces}",
        "<TRACK 0> : {Silicon & Bare-Metal Kernel}",
        "<TRACK 1> : {Host Engine & Virtual Machine}",
        "<TRACK 4> : {Variable Storage & Episodic Memory}",
        "<TRACK 5> : {Infrastructure, Operations & Archives}",
    ];

    for prefix in &TRACK_PREFIXES {
        let candidate = std::path::PathBuf::from(prefix).join(p);
        if candidate.exists() {
            return candidate;
        }
        let sibling = std::path::PathBuf::from("..").join(prefix).join(p);
        if sibling.exists() {
            return sibling;
        }
    }

    // Modularized type resolution: check compiled/ and interpreted/ folders
    let path_str = p.to_string_lossy();
    if path_str.contains("ideas/types/") {
```

```
        if let Some(file_name) = p.file_name().and_then(|f| f.to_str()) {
            let mod_p = if file_name.ends_with(".omni") {
                let stem = file_name.trim_end_matches(".omni");
                let old_s = format!("{file_name}");
                let new_s = format!("{stem}/compiled/{file_name}");
                Some(std::path::PathBuf::from(path_str.replace(&old_s, &new_s)))
            } else if file_name.ends_with(".tape") {
                let stem = file_name.trim_end_matches(".tape");
                let old_s = format!("{file_name}");
                let new_s = format!("{stem}/interpreted/{file_name}");
                Some(std::path::PathBuf::from(path_str.replace(&old_s, &new_s)))
            } else {
                None
            };

            if let Some(mp) = mod_p {
                for prefix in &TRACK_PREFIXES {
                    let candidate = std::path::PathBuf::from(prefix).join(&mp);
                    if candidate.exists() {
                        return candidate;
                    }
                    let sibling =
                        std::path::PathBuf::from("..").join(prefix).join(&mp);
                    if sibling.exists() {
                        return sibling;
                    }
                }
            }
        }
    }

    p.to_path_buf()
}

/// Resolves the canonical episodic memory scroll storage directory across the 6-Track filesystem.
pub fn resolve_scroll_storage_dir() -> std::path::PathBuf {
    let candidates = [
        std::path::PathBuf::from("../<TRACK 4> : {Variable Storage & Episodic Memory}/storage/scrolls"),
        std::path::PathBuf::from("<TRACK 4> : {Variable Storage & Episodic Memory}/storage/scrolls"),
        std::path::PathBuf::from("storage/scrolls"),
        std::path::PathBuf::from("runtime/scrolls"),
        std::path::PathBuf::from("scrolls"),
    ];

    for candidate in &candidates {
        if candidate.exists() {
            return candidate.clone();
        }
    }

    let track4_sibling = std::path::Path::new("../<TRACK 4> : {Variable Storage & Episodic Memory}/storage/scrolls");
    if let Some(parent) = track4_sibling.parent() {
        if parent.exists() {
            let _ = std::fs::create_dir_all(track4_sibling);
            return track4_sibling.to_path_buf();
        }
    }

    std::path::PathBuf::from("storage/scrolls")
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Display Trait Implementation, Sealing & Unit Tests )
// ============================================================================
impl fmt::Display for OmniFileType {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        write!(f, "{}(.{})", self.display_name(), self.extension())
    }
}

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_file_type_detection() {
        assert_eq!(OmniFileType::from_extension("omni"), Some(OmniFileType::SourceReel));
```

```
        assert_eq!(OmniFileType::from_extension(".omni"), Some(OmniFileType::SourceReel));
        assert_eq!(OmniFileType::from_extension("scroll"), Some(OmniFileType::EpisodicScroll));
        assert_eq!(OmniFileType::from_extension(".scroll"), Some(OmniFileType::EpisodicScroll));
        assert_eq!(OmniFileType::from_extension("tape"), Some(OmniFileType::Tape));
        assert_eq!(OmniFileType::from_extension(".tape"), Some(OmniFileType::Tape));
        assert_eq!(OmniFileType::from_extension("txt"), None);

        assert_eq!(OmniFileType::from_path("src/core.omni"), Some(OmniFileType::SourceReel));
        assert_eq!(OmniFileType::from_path("scrolls/test.scroll"), Some(OmniFileType::EpisodicScroll));
        assert_eq!(OmniFileType::from_path("lib/core/cell.tape"), Some(OmniFileType::Tape));
        assert!(OmniFileType::is_omnicode_file("lib/vector.omni"));
        assert!(OmniFileType::is_omnicode_file("history/session.scroll"));
        assert!(OmniFileType::is_omnicode_file("lib/core/cell.tape"));
        assert!(!OmniFileType::is_omnicode_file("Cargo.toml"));
    }

    #[test]
    fn test_scaffold_generation() {
        let omni_code = OmniFileType::SourceReel.scaffold_template("MathModule", "Basic math");
        assert!(omni_code.contains("Module < MathModule >"));
        assert!(omni_code.contains("BLOCK 1: METADATA BLOCK"));
        assert!(omni_code.contains("BLOCK 4: CLOSING BLOCK"));

        let scroll_code = OmniFileType::EpisodicScroll.scaffold_template("sess_1234", "Add 2 and 3");
        assert!(scroll_code.contains("Scroll < EpistemicTrace.sess_1234 >"));
        assert!(scroll_code.contains("commit_status [ <PROCEED> ]"));

        let tape_code = OmniFileType::Tape.scaffold_template("BootProcess", "Kernel Genesis");
        assert!(tape_code.contains("[Tape.BootProcess]"));
        assert!(tape_code.contains("TAPE HEAD"));
        assert!(tape_code.contains("SUBORDINATE ROLLS"));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/core/linguistics.rs RS 1237 LINES 4208 WORDS 54.2 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Linguistic Engine Identity, 8 Parts of Speech, & Grammatical Classification )
// ================================================================================
//! OmniCode Core: Universal Linguistics & Grammatical Classification
//!
//! Maps every token, delimiter, vector, and quad-state directly into the
//! 8 canonical parts of speech in human natural language:
//!     1. Noun          (Entities, types, structures, literals, values)
//!     2. Pronoun       (Pointers, self-references, context handles)
//!     3. Verb          (Vectors, state transitions, operations, relations of being)
//!     4. Adjective     (Invariants, type qualifiers, contracts, quad-states)
//!     5. Adverb        (Execution manner, scheduling priority, negation)
//!     6. Preposition   (Indexing, spatial offsets, projections, scoping)
//!     7. Conjunction   (Connectives, boolean logic, pipeline caveats)
//!     8. Interjection   (Interrupts, traps, halts, parenthetical Asides)

use crate::core::boundaries::BoundaryType;
use crate::core::operators::{BeingRelation, Connective, DirectionalVector, Polarity};
use crate::core::ternary::QuadState;
use crate::parser::lexer::TokenType;


// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Grammatical Role Definitions, Classifications & Mapping Structures )
// ================================================================================

/// The canonical 8 parts of speech in natural human grammar.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum PartOfSpeech {
    Noun,
    Pronoun,
    Verb,
    Adjective,
    Adverb,
    Preposition,
    Conjunction,
    Interjection,
}

impl PartOfSpeech {
    pub fn as_str(&self) -> &'static str {
        match self {
            Self::Noun => "Noun",
            Self::Pronoun => "Pronoun",
            Self::Verb => "Verb",
            Self::Adjective => "Adjective",
            Self::Adverb => "Adverb",
            Self::Preposition => "Preposition",
            Self::Conjunction => "Conjunction",
            Self::Interjection => "Interjection",
        }
    }
}

/// A comprehensive grammatical classification supporting primary, secondary,
/// and tertiary functional roles across natural language and computation.
#[derive(Debug, Clone, PartialEq, Eq)]
pub struct GrammaticalClassification {
    /// The primary syntactic and semantic role in the sentence.
    pub primary: PartOfSpeech,
    /// The secondary role when functioning within different syntactic contexts.
    pub secondary: Option<PartOfSpeech>,
    /// The tertiary role for edge cases or multi-tier semantics.
    pub tertiary: Option<PartOfSpeech>,
    /// Natural language explanation of its linguistic function.
    pub linguistic_role: &'static str,
    /// Corresponding computer science / systems counterpart.
    pub computing_counterpart: &'static str,
}

impl GrammaticalClassification {
    pub fn new(
```

```
        primary: PartOfSpeech,
        secondary: Option<PartOfSpeech>,
        tertiary: Option<PartOfSpeech>,
        linguistic_role: &'static str,
        computing_counterpart: &'static str,
    ) -> Self {
        Self {
            primary,
            secondary,
            tertiary,
            linguistic_role,
            computing_counterpart,
        }
    }

    pub fn is(&self, pos: PartOfSpeech) -> bool {
        self.primary == pos || self.secondary == Some(pos) || self.tertiary == Some(pos)
    }
}

/// Grammatical case of a pronoun in sentence structure.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum PronounCase {
    /// Subjective / Nominative: Initiates action / holds execution frame (e.g., `I`, `we`, `you`, `he`, `she`, `it`, `they`).
    Subjective,
    /// Objective / Accusative: Recipient / target of action / inbound buffer (e.g., `me`, `us`, `him`, `her`, `them`).
    Objective,
    /// Reflexive / Introspective: Self-referential inspection / recursion (e.g., `myself`, `itself`, `themselves`).
    Reflexive,
    /// Possessive Determiner / Capability Token: Ownership / access rights (e.g., `my`, `your`, `his`, `her`, `its`, `our`, `their`).
    Possessive,
}

/// Person perspective of a pronoun.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum PronounPerson {
    /// First person: Active self, kernel engine, or cooperative covenant (`I`, `me`, `we`, `us`, `myself`).
    First,
    /// Second person: Interlocutor, caller, user, or client socket (`you`, `yourself`, `your`).
    Second,
    /// Third person: External entity, data vessel, antecedent, or peer thread (`it`, `he`, `she`, `they`).
    Third,
}

/// Grammatical number of a pronoun.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum PronounNumber {
    Singular,
    Plural,
}

/// The canonical spectrum of grammatical pronouns in OmniCode.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum PronounKind {
    // --- First Person Singular (Kernel / Self) ---
    I,
    Me,
    Myself,
    My,
    Mine,

    // --- First Person Plural (Covenant / Composite) ---
    We,
    Us,
    Ourselves,
    Our,
    Ours,

    // --- Second Person (Caller / User / Interlocutor) ---
    You,
    Yourself,
    Yourselves,
    Your,
    Yours,

    // --- Third Person Singular Animate (Autonomous Worker / Peer) ---
```

```
    He,
    Him,
    Himself,
    His,
    She,
    Her,
    Herself,
    Hers,

    // --- Third Person Singular Inanimate (Data Vessel / Antecedent / Accumulator) ---
    It,
    Itself,
    Its,

    // --- Third Person Plural (Worker Pool / Swarm / Quorum) ---
    They,
    Them,
    Themselves,
    Their,
    Theirs,

    // --- System Context Handles & Wildcards ---
    SelfHandle,
    CallerHandle,
    OwnerHandle,
    Wildcard,
}

impl PronounKind {
    pub fn as_str(&self) -> &'static str {
        match self {
            Self::I => "I",
            Self::Me => "me",
            Self::Myself => "myself",
            Self::My => "my",
            Self::Mine => "mine",
            Self::We => "we",
            Self::Us => "us",
            Self::Ourselves => "ourselves",
            Self::Our => "our",
            Self::Ours => "ours",
            Self::You => "you",
            Self::Yourself => "yourself",
            Self::Yourselves => "yourselves",
            Self::Your => "your",
            Self::Yours => "yours",
            Self::He => "he",
            Self::Him => "him",
            Self::Himself => "himself",
            Self::His => "his",
            Self::She => "she",
            Self::Her => "her",
            Self::Herself => "herself",
            Self::Hers => "hers",
            Self::It => "it",
            Self::Itself => "itself",
            Self::Its => "its",
            Self::They => "they",
            Self::Them => "them",
            Self::Themselves => "themselves",
            Self::Their => "their",
            Self::Theirs => "theirs",
            Self::SelfHandle => "self",
            Self::CallerHandle => "caller",
            Self::OwnerHandle => "owner",
            Self::Wildcard => "_",
        }
    }

    pub fn case(&self) -> PronounCase {
        match self {
            Self::I | Self::We | Self::You | Self::He | Self::She | Self::It | Self::They | Self::SelfHandle |
Self::CallerHandle | Self::OwnerHandle | Self::Wildcard => PronounCase::Subjective,
            Self::Me | Self::Us | Self::Him | Self::Her | Self::Them => PronounCase::Objective,
            Self::Myself | Self::Ourselves | Self::Yourself | Self::Yourselves | Self::Himself | Self::Herself |
Self::Itself | Self::Themselves => PronounCase::Reflexive,
            Self::My | Self::Mine | Self::Our | Self::Ours | Self::Your | Self::Yours | Self::His | Self::Hers |
Self::Its | Self::Their | Self::Theirs => PronounCase::Possessive,
```

```
        }
    }

    pub fn person(&self) -> PronounPerson {
        match self {
            Self::I | Self::Me | Self::Myself | Self::My | Self::Mine |
            Self::We | Self::Us | Self::Ourselves | Self::Our | Self::Ours |
            Self::SelfHandle => PronounPerson::First,

            Self::You | Self::Yourself | Self::Yourselves | Self::Your | Self::Yours |
            Self::CallerHandle => PronounPerson::Second,

            Self::He | Self::Him | Self::Himself | Self::His |
            Self::She | Self::Her | Self::Herself | Self::Hers |
            Self::It | Self::Itself | Self::Its |
            Self::They | Self::Them | Self::Themselves | Self::Their | Self::Theirs |
            Self::OwnerHandle | Self::Wildcard => PronounPerson::Third,
        }
    }

    pub fn number(&self) -> PronounNumber {
        match self {
            Self::We | Self::Us | Self::Ourselves | Self::Our | Self::Ours |
            Self::Yourselves |
            Self::They | Self::Them | Self::Themselves | Self::Their | Self::Theirs => PronounNumber::Plural,
            _ => PronounNumber::Singular,
        }
    }

    pub fn from_keyword(s: &str) -> Option<Self> {
        match s.to_lowercase().as_str() {
            "i" => Some(Self::I),
            "me" => Some(Self::Me),
            "myself" => Some(Self::Myself),
            "my" => Some(Self::My),
            "mine" => Some(Self::Mine),
            "we" => Some(Self::We),
            "us" => Some(Self::Us),
            "ourselves" => Some(Self::Ourselves),
            "our" => Some(Self::Our),
            "ours" => Some(Self::Ours),
            "you" => Some(Self::You),
            "yourself" => Some(Self::Yourself),
            "yourselves" => Some(Self::Yourselves),
            "your" => Some(Self::Your),
            "yours" => Some(Self::Yours),
            "he" => Some(Self::He),
            "him" => Some(Self::Him),
            "himself" => Some(Self::Himself),
            "his" => Some(Self::His),
            "she" => Some(Self::She),
            "her" => Some(Self::Her),
            "herself" => Some(Self::Herself),
            "hers" => Some(Self::Hers),
            "it" => Some(Self::It),
            "itself" => Some(Self::Itself),
            "its" => Some(Self::Its),
            "they" => Some(Self::They),
            "them" => Some(Self::Them),
            "themselves" => Some(Self::Themselves),
            "their" => Some(Self::Their),
            "theirs" => Some(Self::Theirs),
            "self" => Some(Self::SelfHandle),
            "caller" => Some(Self::CallerHandle),
            "owner" => Some(Self::OwnerHandle),
            "_" => Some(Self::Wildcard),
            _ => None,
        }
    }

    pub fn is_subjective(&self) -> bool {
        self.case() == PronounCase::Subjective
    }

    pub fn is_objective(&self) -> bool {
        self.case() == PronounCase::Objective
    }

```

```
    pub fn is_reflexive(&self) -> bool {
        self.case() == PronounCase::Reflexive
    }

    pub fn is_possessive(&self) -> bool {
        self.case() == PronounCase::Possessive
    }

    pub fn linguistic_role(&self) -> &'static str {
        match self {
            Self::I => "First-person singular subjective; represents the active executing identity / kernel",
            Self::Me => "First-person singular objective; represents self as the receiver of inbound action",
            Self::Myself => "First-person reflexive; drives introspective self-audit and invariant verification",
            Self::My | Self::Mine => "First-person possessive; denotes exclusive ownership and write capability",
            Self::We => "First-person plural subjective; denotes cooperative covenant (Kernel + User or Multi-Agent)",
            Self::Us => "First-person plural objective; denotes composite entity as target",
            Self::Ourselves => "First-person plural reflexive; drives collective group audit",
            Self::Our | Self::Ours => "First-person plural possessive; denotes shared covenant resource access",
            Self::You => "Second-person pronoun; identifies external interlocutor, user, or caller socket",
            Self::Yourself | Self::Yourselves => "Second-person reflexive; triggers remote caller verification",
            Self::Your | Self::Yours => "Second-person possessive; denotes borrowed caller capability token",
            Self::He | Self::She => "Third-person singular animate; designates specific peer worker or thread",
            Self::Him | Self::Her => "Third-person singular objective; identifies designated worker as target",
            Self::Himself | Self::Herself => "Third-person singular reflexive; isolates worker-internal state",
            Self::His | Self::Hers => "Third-person singular possessive; denotes worker-delegated capability",
            Self::It => "Third-person singular inanimate; represents data vessel, antecedent, or accumulator",
            Self::Itself => "Third-person reflexive; drives homoiconic tape rewriting or fixed-point recursion",
            Self::Its => "Third-person possessive; denotes vessel-internal property encapsulation",
            Self::They => "Third-person plural subjective; identifies worker pool, quorum, or parallel swarm",
            Self::Them => "Third-person plural objective; identifies worker pool as destination targets",
            Self::Themselves => "Third-person plural reflexive; verifies Byzantine swarm agreement or consensus",
            Self::Their | Self::Theirs => "Third-person plural possessive; denotes process-group capability mask",
            Self::SelfHandle => "Architectural local frame handle; resolves active stack/partition base",
            Self::CallerHandle => "Architectural caller handle; resolves invoking principal and frame return",
            Self::OwnerHandle => "Architectural owner handle; resolves root capability authority",
            Self::Wildcard => "Anonymous discard handle; suppresses destination binding or ignores noise",
        }
    }

    pub fn computing_counterpart(&self) -> &'static str {
        match self {
            Self::I => "Active Task PID / Execution Context Register / `&mut self`",
            Self::Me => "Destination Buffer in Self / Callee Register Inflow",
            Self::Myself => "Self-Audit Telemetry / Local Frame Invariant Check / Introspection",
            Self::My | Self::Mine => "Exclusive Memory Partition Lease / Write Capability Token",
            Self::We => "Composite Covenant Task / Dual-Principal Session / Multi-Agent Swarm",
            Self::Us => "Composite Destination Queue / Shared Inbound Buffer",
            Self::Ourselves => "Group Invariant Consensus Check / Quorum Self-Verification",
            Self::Our | Self::Ours => "Shared Memory Partition Capability / Covenant Lock",
            Self::You => "Caller Context Handle / `STDIN` Channel / Remote IPC Socket",
            Self::Yourself | Self::Yourselves => "Caller Self-Test RPC / Remote Health Probe",
            Self::Your | Self::Yours => "Borrowed Caller Capability Token / Foreign Slice Reference",
            Self::He | Self::She => "Designated Worker Thread PID / Specific Actor Descriptor",
            Self::Him | Self::Her => "Worker Inflow Channel / Task Mailbox",
            Self::Himself | Self::Herself => "Worker Local State Isolation / Actor Invariant Seal",
            Self::His | Self::Hers => "Worker Capability Delegation / Sub-Partition Lease",
            Self::It => "Pipeline Antecedent / Accumulator Register (`ACC`) / Top of Stack",
            Self::Itself => "Homoiconic Tape Rewriter / Circular Reel Wrap / Fixed-Point Recursion",
            Self::Its => "Vessel Field Encapsulation / Internal Property Offset",
            Self::They => "Process Group Descriptor / Parallel Thread Pool / Consensus Quorum",
            Self::Them => "Broadcast Channel / Multi-Partition Destination Slices",
            Self::Themselves => "Swarm Peer-to-Peer Consensus Alignment / Byzantine Quorum Proof",
            Self::Their | Self::Theirs => "Process Group Access Control List / Collective Capability Mask",
            Self::SelfHandle => "Frame Pointer Register (`FP`) / Local Execution Fiber",
            Self::CallerHandle => "Return Address / Caller Task Descriptor (`CALLER`)",
            Self::OwnerHandle => "Capability Authority Root / Security Principal Token",
            Self::Wildcard => "Bit Bucket (`/dev/null`) / Black Hole Register (`_`)",
        }
    }
}

impl GrammaticalEntity for PronounKind {
    fn classify(&self) -> GrammaticalClassification {
        let sec = match self.case() {
            PronounCase::Possessive => Some(PartOfSpeech::Adjective),
            PronounCase::Reflexive => Some(PartOfSpeech::Verb),
            PronounCase::Objective => Some(PartOfSpeech::Noun),
            PronounCase::Subjective => Some(PartOfSpeech::Noun),
```

```
        };
        GrammaticalClassification::new(
            PartOfSpeech::Pronoun,
            sec,
            None,
            self.linguistic_role(),
            self.computing_counterpart(),
        )
    }
}


// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Trait Implementations & Grammatical Classification Mappings )
// ============================================================================

pub trait GrammaticalEntity {
    fn classify(&self) -> GrammaticalClassification;
}

impl GrammaticalEntity for TokenType {
    fn classify(&self) -> GrammaticalClassification {
        match self {
            // Delimiters
            TokenType::LBracket | TokenType::RBracket => GrammaticalClassification::new(
                PartOfSpeech::Noun,
                Some(PartOfSpeech::Preposition),
                None,
                "Denotation boundary container; spatially indexes inner state",
                "Array / Struct container; memory offset indexing `buf[idx]`",
            ),
            TokenType::LBrace | TokenType::RBrace => GrammaticalClassification::new(
                PartOfSpeech::Adjective,
                Some(PartOfSpeech::Conjunction),
                None,
                "Invariant contract; specifies necessary ambient conditions",
                "Type invariant / Precondition constraint / Scope qualification",
            ),
            TokenType::LAngle | TokenType::RAngle => GrammaticalClassification::new(
                PartOfSpeech::Adjective,
                Some(PartOfSpeech::Noun),
                None,
                "Immutable axiom boundary; names high-order categorical domains",
                "Type parameter / Scale invariant / Module domain constant",
            ),
            TokenType::Aside(_) => GrammaticalClassification::new(
                PartOfSpeech::Interjection,
                Some(PartOfSpeech::Adverb),
                None,
                "First-class teleological Aside; states machine intent and rationale",
                "Non-executable intent annotation / Compiler reasoning trace",
            ),

            // Grammatical Pronouns (Perspective, Identity, Ownership & Capability)
            TokenType::Pronoun(p) => p.classify(),

            // Polarity & Boundary Cast Operators
            TokenType::AffixedIdent { polarity, .. } => match polarity {
                Polarity::Abstract => GrammaticalClassification::new(
                    PartOfSpeech::Adjective,
                    Some(PartOfSpeech::Noun),
                    None,
                    "Abstract archetype polarity modifier (+Word); denotes universal concept or intension",
                    "Uninstantiated archetype / Type specification / Zero-cost blueprint",
                ),
                Polarity::Concrete => GrammaticalClassification::new(
                    PartOfSpeech::Noun,
                    Some(PartOfSpeech::Adjective),
                    None,
                    "Concrete substance polarity modifier (-Word / Word-); denotes physical instance",
                    "Physical memory allocation / Concrete hardware register footprint",
                ),
            },
            TokenType::BoundaryCast { .. } => GrammaticalClassification::new(
                PartOfSpeech::Preposition,
                Some(PartOfSpeech::Verb),
                None,
```

```
                "Boundary casting operator; modulates entity essence across boundary rank",
                "Type cast / Transduction between abstract and concrete representations",
            ),

            // Directional Vectors (Verbs of Action & Causation)
            TokenType::ActUpon => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Preposition),
                None,
                "Forward causation; acts upon target entity",
                "Store / Mutation / Pipeline emission / MOV",
            ),
            TokenType::ActAgain => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Preposition),
                None,
                "Retroactive reflection; draws from or reflects back upon source",
                "Load / Feedback / State rollback inspection",
            ),
            TokenType::BuildsTo => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Preposition),
                None,
                "Ascending action; synthesizes lower primitive into higher concept",
                "Type promotion / Emergence / Layering up to abstraction",
            ),
            TokenType::BreaksDownFrom => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Preposition),
                None,
                "Descending action; decomposes abstract concept into primitives",
                "Destructuring / Register unpack / Compilation lowering",
            ),
            TokenType::Major => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Adjective),
                None,
                "Major scale vector; ascending forward diagonal leap",
                "Major scale promotion / Leap to higher abstraction tier (`/-^`)",
            ),
            TokenType::Minor => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Adjective),
                None,
                "Minor scale vector; descending forward diagonal step",
                "Minor scale reduction / Settling to lower execution tier (`\\-v`)",
            ),
            TokenType::Great => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Adjective),
                None,
                "Great scale vector; ascending backward diagonal reflection",
                "Great scale elevation / Architectural reflection (`\\-^`)",
            ),
            TokenType::Small => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Adjective),
                None,
                "Small scale vector; descending backward diagonal micro-adjustment",
                "Small scale reduction / Micro-destructuring (`/-v`)",
            ),
            TokenType::UpperRight => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Preposition),
                None,
                "Quadrant I compass vector; forward ascending northeast movement",
                "2D Quadrant I vector: +X, +Y (`/^`)",
            ),
            TokenType::LowerRight => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Preposition),
                None,
                "Quadrant IV compass vector; forward descending southeast movement",
                "2D Quadrant IV vector: +X, -Y (`\\v`)",
            ),
            TokenType::UpperLeft => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Preposition),
```

```
                None,
                "Quadrant II compass vector; backward ascending northwest movement",
                "2D Quadrant II vector: -X, +Y (`^\\`)",
            ),
            TokenType::LowerLeft => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Preposition),
                None,
                "Quadrant III compass vector; backward descending southwest movement",
                "2D Quadrant III vector: -X, -Y (`v/`)",
            ),

            // Relations of Being (Verbs of Identity & State)
            TokenType::Is => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Copula of being; asserts exact equivalence and identity",
                "Equality assertion (`==`) / Identity binding",
            ),
            TokenType::IsNot => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Negative copula; asserts distinctness and exclusion",
                "Inequality assertion (`!=`)",
            ),
            TokenType::ToBeNot => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "State copula; asserts negative state predicate (=!)",
                "State negation predicate (`=!`)",
            ),
            TokenType::ToBeLike => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Adjective),
                None,
                "Analogy copula; asserts structural likeness or homomorphism",
                "Structural compatibility / Duck typing / Approximate equivalence",
            ),
            TokenType::InvariantEquivalence => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Invariant copula; immutable balance, identity, and eternal equilibrium (<=>)",
                "Invariant to be / Axiomatic Equivalence (`<=>`)",
            ),
            TokenType::LessThan => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Relational ordering; strictly less than within context bounds (<)",
                "Contextual less than comparison (`[ { A } < { B } ]`)",
            ),
            TokenType::GreaterThan => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Relational ordering; strictly greater than within context bounds (>)",
                "Contextual greater than comparison (`[ { A } > { B } ]`)",
            ),
            TokenType::LessEqual => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Relational ordering; less than or equal within context bounds (<=)",
                "Contextual less than or equal comparison (`[ { A } <= { B } ]`)",
            ),
            TokenType::GreaterEqual => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Relational ordering; greater than or equal within context bounds (>=)",
                "Contextual greater than or equal comparison (`[ { A } >= { B } ]`)",
            ),

            // Connectives
```

```
            TokenType::But => GrammaticalClassification::new(
                PartOfSpeech::Conjunction,
                Some(PartOfSpeech::Interjection),
                None,
                "Adversative conjunction; introduces strict caveat condition",
                "Caveat guard; triggers `-1: ROLLBACK` if caveat fails",
            ),
            TokenType::And => GrammaticalClassification::new(
                PartOfSpeech::Conjunction,
                Some(PartOfSpeech::Preposition),
                None,
                "Cumulative conjunction; asserts simultaneous co-presence",
                "Conjunction (`&&`) / Simultaneous consensus",
            ),
            TokenType::HardwareLocator => GrammaticalClassification::new(
                PartOfSpeech::Preposition,
                Some(PartOfSpeech::Conjunction),
                None,
                "Dedicated hardware locator (::@); binds entity co-presence directly to MMIO address or port",
                "MMIO port locator / Hardware address binding (`Glyph & Cell ::@ Port`)",
            ),
            TokenType::InRelationTo => GrammaticalClassification::new(
                PartOfSpeech::Preposition,
                Some(PartOfSpeech::Verb),
                None,
                "Relational projection; positions entity in relation to a category",
                "Type annotation (`x : Type`) / Contextual role assignment",
            ),
            TokenType::Or => GrammaticalClassification::new(
                PartOfSpeech::Conjunction,
                Some(PartOfSpeech::Adverb),
                None,
                "Disjunctive conjunction; introduces alternatives or choices",
                "Disjunction (`||`) / Non-deterministic branch",
            ),
            TokenType::Not => GrammaticalClassification::new(
                PartOfSpeech::Adverb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Negating adverb; inverts the state or predicate across balance line",
                "Logical / Algebraic negation",
            ),
            TokenType::BoundPair => GrammaticalClassification::new(
                PartOfSpeech::Conjunction,
                Some(PartOfSpeech::Noun),
                None,
                "Hand-in-hand inseparable dual binding; binds entities so neither can be referenced without the other",
                "Inseparable atomic pair / Dual-rail entangled binding (`A&B`)",
            ),

            // Prepositions & Spatial Locators
            TokenType::At => GrammaticalClassification::new(
                PartOfSpeech::Preposition,
                Some(PartOfSpeech::Noun),
                None,
                "Spatial preposition specifying absolute or relative location, address, or memory site",
                "Memory address / MMIO locator / Absolute site (`Storehouse @ Offset`)",
            ),

            // Measures & Proportions
            TokenType::Percent => GrammaticalClassification::new(
                PartOfSpeech::Adjective,
                Some(PartOfSpeech::Noun),
                None,
                "Proportional measure specifying capacity fraction, ratio, or utilization percentage",
                "Capacity fullness ratio / Percentage scale (`Capacity % 80`)",
            ),

            // Ranges
            TokenType::DotDot => GrammaticalClassification::new(
                PartOfSpeech::Preposition,
                Some(PartOfSpeech::Noun),
                None,
                "Range span preposition; defines closed interval bounds between coordinates",
                "Coordinate interval / Memory span `[0 .. 256]`",
            ),

            // Cardinal Classification Clauses (The 5 W's and 1 H)
```

```
            TokenType::Who => GrammaticalClassification::new(
                PartOfSpeech::Pronoun,
                Some(PartOfSpeech::Noun),
                None,
                "Agent pronoun clause; identifies actor, authority, caller, or process identity",
                "Process owner / Security principal / Caller identity (`WHO`)",
            ),
            TokenType::What => GrammaticalClassification::new(
                PartOfSpeech::Noun,
                Some(PartOfSpeech::Pronoun),
                None,
                "Substance noun clause; identifies entity, payload, data vessel, or type",
                "Data vessel / Entity payload / Operand specification (`WHAT`)",
            ),
            TokenType::When => GrammaticalClassification::new(
                PartOfSpeech::Adverb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Temporal adverb clause; identifies execution cadence, lifecycle block, or trigger",
                "Execution phase / Scheduler quantum / Event trigger (`WHEN`)",
            ),
            TokenType::Where => GrammaticalClassification::new(
                PartOfSpeech::Preposition,
                Some(PartOfSpeech::Conjunction),
                None,
                "Spatial preposition clause; identifies memory location, address, scope, or invariant bounds",
                "Spatial address / MMIO site / Invariant scope (`WHERE`)",
            ),
            TokenType::Why => GrammaticalClassification::new(
                PartOfSpeech::Interjection,
                Some(PartOfSpeech::Adjective),
                None,
                "Teleological inquiry clause; specifies rationale, contractual reason, or axiom",
                "Teleological rationale / Contractual reason / Axiom link (`WHY`)",
            ),
            TokenType::How => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Adverb),
                None,
                "Causal mechanism clause; specifies vector method, transducer, or execution policy",
                "Causal mechanism / Vector method / Transducer (`HOW`)",
            ),

            // Natural Arithmetic Keywords
            TokenType::Plus => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Action of addition; unites quantities",
                "Arithmetic addition opcode",
            ),
            TokenType::Minus => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Action of subtraction; separates quantities",
                "Arithmetic subtraction opcode",
            ),
            TokenType::Times => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Action of multiplication; scales quantities",
                "Arithmetic multiplication opcode",
            ),
            TokenType::Div => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Action of division; partitions quantities",
                "Arithmetic division opcode",
            ),

            // Infer
            TokenType::Infer => GrammaticalClassification::new(
                PartOfSpeech::Interjection,
                Some(PartOfSpeech::Verb),
                None,
```

```
                "Interrogative inquiry; seeks resolution or truth state",
                "Pattern match query / Ontological inference operator",
            ),

            // Literals
            TokenType::Identifier(_) => GrammaticalClassification::new(
                PartOfSpeech::Noun,
                Some(PartOfSpeech::Pronoun),
                None,
                "Named subject, object, or entity in discourse",
                "Variable name / Symbol / Type identifier",
            ),
            TokenType::Number(_) => GrammaticalClassification::new(
                PartOfSpeech::Noun,
                Some(PartOfSpeech::Adjective),
                None,
                "Numeric scalar value; quantifies entities",
                "Immediate scalar numeric literal",
            ),
            TokenType::StringLit(_) => GrammaticalClassification::new(
                PartOfSpeech::Noun,
                None,
                None,
                "Textual noun; semantic content literal",
                "String literal / Byte payload",
            ),
            TokenType::CharLit(_) => GrammaticalClassification::new(
                PartOfSpeech::Noun,
                None,
                None,
                "Atomic character glyph rune literal ('A'); discrete single-cell textual scalar",
                "Character literal / 5-trit scalar byte (`'A' <=> 65`)",
            ),
            TokenType::Ternary(state) => state.classify(),

            TokenType::Eof => GrammaticalClassification::new(
                PartOfSpeech::Interjection,
                None,
                None,
                "Terminal punctuation sealing the discourse",
                "End of file / Stream termination",
            ),
        }
    }
}

impl GrammaticalEntity for QuadState {
    fn classify(&self) -> GrammaticalClassification {
        match self {
            QuadState::Proceed => GrammaticalClassification::new(
                PartOfSpeech::Adjective,
                Some(PartOfSpeech::Noun),
                Some(PartOfSpeech::Interjection),
                "Affirmative state of truth, covenant alignment, and forward momentum",
                "Logic +1 / Monotonic commit / Success",
            ),
            QuadState::Await => GrammaticalClassification::new(
                PartOfSpeech::Adjective,
                Some(PartOfSpeech::Verb),
                None,
                "Superposition state; yielding in wait for consensus",
                "Logic 0 / Cooperative schedule yield / Non-blocking pending",
            ),
            QuadState::Rollback => GrammaticalClassification::new(
                PartOfSpeech::Interjection,
                Some(PartOfSpeech::Verb),
                Some(PartOfSpeech::Adjective),
                "Exclamation of veto; immediate transactional rewind",
                "Logic -1 / Transaction abort and rollback",
            ),
            QuadState::Halt => GrammaticalClassification::new(
                PartOfSpeech::Interjection,
                Some(PartOfSpeech::Noun),
                None,
                "Terminal trap of void and non-existence; complete cessation",
                "Logic NULL / Fatal CPU trap / Irreducible collapse",
            ),
        }
```

```
    }
}

impl GrammaticalEntity for BoundaryType {
    fn classify(&self) -> GrammaticalClassification {
        match self {
            BoundaryType::Denotation => GrammaticalClassification::new(
                PartOfSpeech::Noun,
                Some(PartOfSpeech::Preposition),
                None,
                "Concrete essence and mutable data literal",
                "Data structure container / Mutable memory slice",
            ),
            BoundaryType::Invariant => GrammaticalClassification::new(
                PartOfSpeech::Adjective,
                Some(PartOfSpeech::Noun),
                None,
                "Immutable axiom and universal physical constant",
                "Constant literal / Read-only memory / Axiomatic constraint",
            ),
            BoundaryType::Connotation => GrammaticalClassification::new(
                PartOfSpeech::Adjective,
                Some(PartOfSpeech::Conjunction),
                None,
                "Ambient context, required capabilities, and environmental predicates",
                "Precondition contract / Ambient capabilities / Context scope",
            ),
            BoundaryType::TopDown => GrammaticalClassification::new(
                PartOfSpeech::Preposition,
                Some(PartOfSpeech::Adjective),
                None,
                "Outside-in conditioning: the environment dictates entity essence",
                "Hardware MMIO window / Environmental dependency injection",
            ),
            BoundaryType::BottomUp => GrammaticalClassification::new(
                PartOfSpeech::Preposition,
                Some(PartOfSpeech::Verb),
                None,
                "Inside-out emergence: entity essence projects into environment",
                "Polymorphic emission / Register export to ABI",
            ),
            BoundaryType::Aside => GrammaticalClassification::new(
                PartOfSpeech::Interjection,
                Some(PartOfSpeech::Adverb),
                None,
                "Aside to; teleological intent container preserving reasoning trace",
                "First-class intent container / AI reasoning trace",
            ),
        }
    }
}

impl GrammaticalEntity for DirectionalVector {
    fn classify(&self) -> GrammaticalClassification {
        match self {
            DirectionalVector::ActUpon => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Preposition),
                None,
                "Forward causation; acts upon target",
                "Forward pipeline dispatch / Store operation",
            ),
            DirectionalVector::ActAgain => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Preposition),
                None,
                "Retroactive reflection; draws from or re-evaluates source",
                "Feedback loop / Rollback inspection / Load operation",
            ),
            DirectionalVector::BuildsTo => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Preposition),
                None,
                "Ascending synthesis; primitives build up to abstraction",
                "Type promotion / Abstraction synthesis",
            ),
            DirectionalVector::BreaksDownFrom => GrammaticalClassification::new(
                PartOfSpeech::Verb,
```

```
                Some(PartOfSpeech::Preposition),
                None,
                "Descending decomposition; concept lowers into hardware primitives",
                "Destructuring / Register lowering",
            ),
            DirectionalVector::Major => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Adjective),
                None,
                "Major scale vector; ascending forward diagonal leap",
                "Major scale promotion (`/-^`)",
            ),
            DirectionalVector::Minor => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Adjective),
                None,
                "Minor scale vector; descending forward diagonal step",
                "Minor scale reduction (`\\-v`)",
            ),
            DirectionalVector::Great => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Adjective),
                None,
                "Great scale vector; ascending backward diagonal reflection",
                "Great scale elevation (`\\-^`)",
            ),
            DirectionalVector::Small => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Adjective),
                None,
                "Small scale vector; descending backward diagonal micro-adjustment",
                "Small scale reduction (`/-v`)",
            ),
            DirectionalVector::UpperRight => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Preposition),
                None,
                "Quadrant I compass vector; forward ascending movement",
                "2D Quadrant I vector: +X, +Y (`/^`)",
            ),
            DirectionalVector::LowerRight => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Preposition),
                None,
                "Quadrant IV compass vector; forward descending movement",
                "2D Quadrant IV vector: +X, -Y (`\\v`)",
            ),
            DirectionalVector::UpperLeft => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Preposition),
                None,
                "Quadrant II compass vector; backward ascending movement",
                "2D Quadrant II vector: -X, +Y (`^\\`)",
            ),
            DirectionalVector::LowerLeft => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Preposition),
                None,
                "Quadrant III compass vector; backward descending movement",
                "2D Quadrant III vector: -X, -Y (`v/`)",
            ),
        }
    }
}

impl GrammaticalEntity for BeingRelation {
    fn classify(&self) -> GrammaticalClassification {
        match self {
            BeingRelation::Is => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Identity copula: exact equivalence of essence",
                "Equality assertion / Equational binding",
            ),
            BeingRelation::IsNot => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
```

```
                None,
                "Negative copula: distinctness and mutual exclusion",
                "Inequality assertion",
            ),
            BeingRelation::ToBeNot => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "State copula: asserts negative state predicate (=!)",
                "State negation predicate",
            ),
            BeingRelation::ToBeLike => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Adjective),
                None,
                "Analogy copula: structural or behavioral compatibility",
                "Homomorphism / Approximate equality",
            ),
            BeingRelation::Equivalence => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Invariant copula: immutable balance, identity, and eternal equilibrium (<=>)",
                "Invariant to be / Axiomatic Equivalence",
            ),
            BeingRelation::LessThan => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Relational ordering: strictly less than within context bounds (<)",
                "Less than relational query",
            ),
            BeingRelation::GreaterThan => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Relational ordering: strictly greater than within context bounds (>)",
                "Greater than relational query",
            ),
            BeingRelation::LessEqual => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Relational ordering: less than or equal within context bounds (<=)",
                "Less than or equal relational query",
            ),
            BeingRelation::GreaterEqual => GrammaticalClassification::new(
                PartOfSpeech::Verb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Relational ordering: greater than or equal within context bounds (>=)",
                "Greater than or equal relational query",
            ),
        }
    }
}

impl GrammaticalEntity for Connective {
    fn classify(&self) -> GrammaticalClassification {
        match self {
            Connective::But => GrammaticalClassification::new(
                PartOfSpeech::Conjunction,
                Some(PartOfSpeech::Interjection),
                None,
                "Adversative conjunction: caveat requirement that vetoes on failure",
                "Guard condition with automatic rollback",
            ),
            Connective::And => GrammaticalClassification::new(
                PartOfSpeech::Conjunction,
                Some(PartOfSpeech::Preposition),
                None,
                "Cumulative conjunction: co-present simultaneous execution",
                "Conjunction (`&&`) / Joint consensus",
            ),
            Connective::InRelationTo => GrammaticalClassification::new(
                PartOfSpeech::Preposition,
                Some(PartOfSpeech::Verb),
                None,
```

```
                "Relational projection: positions an entity within a role or type",
                "Type annotation (`:`) / Role assignment",
            ),
            Connective::Or => GrammaticalClassification::new(
                PartOfSpeech::Conjunction,
                Some(PartOfSpeech::Adverb),
                None,
                "Disjunctive conjunction: alternative path or branching",
                "Disjunction (`||`)",
            ),
            Connective::Not => GrammaticalClassification::new(
                PartOfSpeech::Adverb,
                Some(PartOfSpeech::Conjunction),
                None,
                "Negating adverb: inverts the evaluation balance",
                "Algebraic negation (`--`)",
            ),
        }
    }
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Linguistic Unit Tests & Invariant Verification )
// ============================================================================
#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_eight_parts_of_speech_coverage() {
        let act_upon = TokenType::ActUpon.classify();
        assert_eq!(act_upon.primary, PartOfSpeech::Verb);
        assert_eq!(act_upon.secondary, Some(PartOfSpeech::Preposition));

        let but = TokenType::But.classify();
        assert_eq!(but.primary, PartOfSpeech::Conjunction);
        assert_eq!(but.secondary, Some(PartOfSpeech::Interjection));

        let bracket = TokenType::LBracket.classify();
        assert_eq!(bracket.primary, PartOfSpeech::Noun);
        assert_eq!(bracket.secondary, Some(PartOfSpeech::Preposition));

        let brace = TokenType::LBrace.classify();
        assert_eq!(brace.primary, PartOfSpeech::Adjective);
        assert_eq!(brace.secondary, Some(PartOfSpeech::Conjunction));

        let aside = TokenType::Aside("intent".to_string()).classify();
        assert_eq!(aside.primary, PartOfSpeech::Interjection);
        assert_eq!(aside.secondary, Some(PartOfSpeech::Adverb));

        let not = TokenType::Not.classify();
        assert_eq!(not.primary, PartOfSpeech::Adverb);
        assert_eq!(not.secondary, Some(PartOfSpeech::Conjunction));

        let relation = TokenType::InRelationTo.classify();
        assert_eq!(relation.primary, PartOfSpeech::Preposition);
        assert_eq!(relation.secondary, Some(PartOfSpeech::Verb));

        let bound = TokenType::BoundPair.classify();
        assert_eq!(bound.primary, PartOfSpeech::Conjunction);
        assert_eq!(bound.secondary, Some(PartOfSpeech::Noun));

        let at = TokenType::At.classify();
        assert_eq!(at.primary, PartOfSpeech::Preposition);
        assert_eq!(at.secondary, Some(PartOfSpeech::Noun));

        let pct = TokenType::Percent.classify();
        assert_eq!(pct.primary, PartOfSpeech::Adjective);
        assert_eq!(pct.secondary, Some(PartOfSpeech::Noun));
    }

    #[test]
    fn test_quad_state_linguistic_classifications() {
        let proceed = QuadState::Proceed.classify();
        assert_eq!(proceed.primary, PartOfSpeech::Adjective);
        assert!(proceed.is(PartOfSpeech::Interjection));
```

```
        let rollback = QuadState::Rollback.classify();
        assert_eq!(rollback.primary, PartOfSpeech::Interjection);
        assert!(rollback.is(PartOfSpeech::Verb));
    }

    #[test]
    fn test_pronoun_matrix_and_capability_classifications() {
        // 1. Subjective (Agency / Execution context)
        let p_i = PronounKind::I;
        assert_eq!(p_i.case(), PronounCase::Subjective);
        assert_eq!(p_i.person(), PronounPerson::First);
        assert_eq!(p_i.number(), PronounNumber::Singular);
        assert!(p_i.is_subjective());
        let class_i = p_i.classify();
        assert_eq!(class_i.primary, PartOfSpeech::Pronoun);
        assert_eq!(class_i.secondary, Some(PartOfSpeech::Noun));
        assert!(class_i.computing_counterpart.contains("&mut self"));

        // 2. Objective (Inbound target)
        let p_me = PronounKind::Me;
        assert_eq!(p_me.case(), PronounCase::Objective);
        assert_eq!(p_me.person(), PronounPerson::First);
        assert!(p_me.is_objective());

        // 3. Reflexive (Introspection & self-audit)
        let p_myself = PronounKind::Myself;
        assert_eq!(p_myself.case(), PronounCase::Reflexive);
        assert!(p_myself.is_reflexive());
        let class_myself = p_myself.classify();
        assert_eq!(class_myself.secondary, Some(PartOfSpeech::Verb));
        assert!(class_myself.computing_counterpart.contains("Self-Audit"));

        let p_itself = PronounKind::Itself;
        assert_eq!(p_itself.case(), PronounCase::Reflexive);
        assert_eq!(p_itself.person(), PronounPerson::Third);
        let class_itself = p_itself.classify();
        assert!(class_itself.computing_counterpart.contains("Homoiconic"));

        let p_themselves = PronounKind::Themselves;
        assert_eq!(p_themselves.case(), PronounCase::Reflexive);
        assert_eq!(p_themselves.number(), PronounNumber::Plural);
        assert!(p_themselves.classify().computing_counterpart.contains("Consensus"));

        // 4. Possessive (Ownership & Capability tokens)
        let p_my = PronounKind::My;
        assert_eq!(p_my.case(), PronounCase::Possessive);
        assert!(p_my.is_possessive());
        let class_my = p_my.classify();
        assert_eq!(class_my.secondary, Some(PartOfSpeech::Adjective));
        assert!(class_my.computing_counterpart.contains("Capability Token"));

        let p_their = PronounKind::Their;
        assert_eq!(p_their.case(), PronounCase::Possessive);
        assert_eq!(p_their.number(), PronounNumber::Plural);

        // 5. Keyword parsing round-trip
        assert_eq!(PronounKind::from_keyword("we"), Some(PronounKind::We));
        assert_eq!(PronounKind::from_keyword("you"), Some(PronounKind::You));
        assert_eq!(PronounKind::from_keyword("it"), Some(PronounKind::It));
        assert_eq!(PronounKind::from_keyword("she"), Some(PronounKind::She));
        assert_eq!(PronounKind::from_keyword("he"), Some(PronounKind::He));
        assert_eq!(PronounKind::from_keyword("herself"), Some(PronounKind::Herself));
        assert_eq!(PronounKind::from_keyword("himself"), Some(PronounKind::Himself));
        assert_eq!(PronounKind::from_keyword("theirs"), Some(PronounKind::Theirs));
        assert_eq!(PronounKind::from_keyword("self"), Some(PronounKind::SelfHandle));
        assert_eq!(PronounKind::from_keyword("caller"), Some(PronounKind::CallerHandle));
        assert_eq!(PronounKind::from_keyword("owner"), Some(PronounKind::OwnerHandle));
        assert_eq!(PronounKind::from_keyword("_"), Some(PronounKind::Wildcard));

        // 6. TokenType delegation
        let tok = TokenType::Pronoun(PronounKind::Myself);
        assert_eq!(tok.classify().primary, PartOfSpeech::Pronoun);
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/core/mmio.rs RS 300 LINES 1055 WORDS 9.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Physical Memory-Mapped I/O: Bare-Metal VGA Text Buffer & Serial Console )
// ============================================================================
//! OmniCode Physical MMIO Subsystem
//!
//! Provides the bare-metal hardware interaction layer for the bootable machine:
//!
//! # Physical Memory Architecture
//! - **0x000B8000 .. 0x000B8FA0**: Standard VGA text-mode video buffer (80 cols × 25 rows = 2000 cells).
//!   Each cell consists of an ASCII character code byte + color attribute byte.
//! - **0x03F8 .. 0x03FF**: COM1 UART 16550 Serial Port for low-level kernel telemetry.
//! - **0x00100000 .. 0x00FFFFFF**: Extended 16MB RAM partition for kernel and reels.
//!
//! When instructions on `Track 0 [KERNEL]` inscribe physical words to memory,
//! addresses in the MMIO range drive hardware video output and serial telemetry.

use crate::core::word::Word64;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( VGA Data Structures, Colors, and Serial Port Models )
// ============================================================================

pub const VGA_BUFFER_BASE: u64 = 0x000B8000;
pub const VGA_COLS: usize = 80;
pub const VGA_ROWS: usize = 25;
pub const VGA_CELL_COUNT: usize = VGA_COLS * VGA_ROWS;

pub const COM1_SERIAL_PORT: u64 = 0x03F8;

#[derive(Debug, Clone, Copy, PartialEq, Eq)]
#[repr(u8)]
pub enum VgaColor {
    Black = 0,
    Blue = 1,
    Green = 2,
    Cyan = 3,
    Red = 4,
    Magenta = 5,
    Brown = 6,
    LightGray = 7,
    DarkGray = 8,
    LightBlue = 9,
    LightGreen = 10,
    LightCyan = 11,
    LightRed = 12,
    Pink = 13,
    Yellow = 14,
    White = 15,
}

#[derive(Debug, Clone, Copy, PartialEq, Eq)]
pub struct VgaCell {
    pub ascii: u8,
    pub attribute: u8,
}

impl Default for VgaCell {
    fn default() -> Self {
        Self {
            ascii: b' ',
            attribute: (VgaColor::Black as u8) << 4 | (VgaColor::LightGray as u8),
        }
    }
}

pub struct VgaBuffer {
    pub cells: [VgaCell; VGA_CELL_COUNT],
    pub cursor_col: usize,
    pub cursor_row: usize,
}

impl Default for VgaBuffer {
```

```
    fn default() -> Self {
        Self::new()
    }
}

pub struct SerialPort {
    pub buffer: Vec<u8>,
}

impl Default for SerialPort {
    fn default() -> Self {
        Self::new()
    }
}

pub struct PhysicalMemoryMap {
    pub vga: VgaBuffer,
    pub serial: SerialPort,
    pub ram_cells: Vec<Word64>,
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( MMIO Driver Methods, Video Screen Rendering, and Address Dispatch )
// ============================================================================

impl VgaBuffer {
    /// Creates an empty VGA text buffer cleared with light gray on black.
    pub fn new() -> Self {
        Self {
            cells: [VgaCell::default(); VGA_CELL_COUNT],
            cursor_col: 0,
            cursor_row: 0,
        }
    }

    /// Clears the video text buffer.
    pub fn clear(&mut self) {
        self.cells = [VgaCell::default(); VGA_CELL_COUNT];
        self.cursor_col = 0;
        self.cursor_row = 0;
    }

    /// Inscribes a single character byte at the current cursor location.
    pub fn write_char(&mut self, ch: u8, fg: VgaColor, bg: VgaColor) {
        if ch == b'\n' {
            self.new_line();
            return;
        }

        let attr = ((bg as u8) << 4) | (fg as u8);
        let idx = self.cursor_row * VGA_COLS + self.cursor_col;
        if idx < VGA_CELL_COUNT {
            self.cells[idx] = VgaCell { ascii: ch, attribute: attr };
        }

        self.cursor_col += 1;
        if self.cursor_col >= VGA_COLS {
            self.new_line();
        }
    }

    /// Writes an ASCII string to the video buffer.
    pub fn write_str(&mut self, s: &str, fg: VgaColor, bg: VgaColor) {
        for b in s.bytes() {
            self.write_char(b, fg, bg);
        }
    }

    /// Advances the cursor to the beginning of the next row, scrolling if needed.
    pub fn new_line(&mut self) {
        self.cursor_col = 0;
        if self.cursor_row + 1 < VGA_ROWS {
            self.cursor_row += 1;
        } else {
            // Scroll buffer up by 1 line
            for row in 1..VGA_ROWS {
                for col in 0..VGA_COLS {
```

```
                    let from_idx = row * VGA_COLS + col;
                    let to_idx = (row - 1) * VGA_COLS + col;
                    self.cells[to_idx] = self.cells[from_idx];
                }
            }
            // Clear last row
            let blank = VgaCell::default();
            for col in 0..VGA_COLS {
                let last_idx = (VGA_ROWS - 1) * VGA_COLS + col;
                self.cells[last_idx] = blank;
            }
        }
    }

    /// Renders the 80x25 video buffer as a framed ASCII string for terminal display.
    pub fn render_screen(&self, max_rows: usize) -> String {
        let mut out = String::new();
        out.push_str("\x1b[1;34m┌──────────────────────────────── [BARE-METAL VGA CONSOLE @ 0x000B8000] ────────────────────────────────┐\x1b[0m\n");
        let rows_to_show = max_rows.min(VGA_ROWS);
        for row in 0..rows_to_show {
            out.push_str("\x1b[1;34m│\x1b[0m ");
            for col in 0..VGA_COLS {
                let cell = self.cells[row * VGA_COLS + col];
                let ch = if (32..=126).contains(&cell.ascii) {
                    cell.ascii as char
                } else {
                    ' '
                };
                out.push(ch);
            }
            out.push_str(" \x1b[1;34m│\x1b[0m\n");
        }

        out.push_str("\x1b[1;34m└──────────────────────────────────────────────────────────────────────────────────────────────────────────────────────┘\x1b[0m\n");
        out
    }
}

impl SerialPort {
    pub fn new() -> Self {
        Self { buffer: Vec::new() }
    }

    pub fn write_byte(&mut self, b: u8) {
        self.buffer.push(b);
    }

    pub fn write_str(&mut self, s: &str) {
        self.buffer.extend_from_slice(s.as_bytes());
    }

    pub fn read_output(&self) -> String {
        String::from_utf8_lossy(&self.buffer).to_string()
    }
}

impl PhysicalMemoryMap {
    pub fn new(ram_capacity: usize) -> Self {
        Self {
            vga: VgaBuffer::new(),
            serial: SerialPort::new(),
            ram_cells: vec![Word64::zero(); ram_capacity],
        }
    }

    /// Dispatches a 64-bit word write to RAM or hardware MMIO peripherals.
    pub fn write(&mut self, address: u64, word: Word64) -> Result<(), String> {
        if (VGA_BUFFER_BASE..VGA_BUFFER_BASE + (VGA_CELL_COUNT as u64)).contains(&address) {
            let offset = (address - VGA_BUFFER_BASE) as usize;
            let ch = (word.payload().to_i64() as u8).max(32);
            let attr = ((word.raw >> 8) & 0xFF) as u8;
            self.vga.cells[offset] = VgaCell {
                ascii: ch,
                attribute: if attr == 0 { 0x07 } else { attr },
            };
            return Ok(());
```

```
        }

        if address == COM1_SERIAL_PORT {
            let b = (word.payload().to_i64() & 0xFF) as u8;
            self.serial.write_byte(b);
            return Ok(());
        }

        let idx = address as usize;
        if idx < self.ram_cells.len() {
            self.ram_cells[idx] = word;
            Ok(())
        } else {
            Err(format!("FAILPOINT [PhysicalBusFault]: Address 0x{:08X} unmapped on physical bus", address))
        }
    }

    /// Reads a 64-bit word from RAM or MMIO.
    pub fn read(&self, address: u64) -> Option<Word64> {
        if (VGA_BUFFER_BASE..VGA_BUFFER_BASE + (VGA_CELL_COUNT as u64)).contains(&address) {
            let offset = (address - VGA_BUFFER_BASE) as usize;
            let cell = self.vga.cells[offset];
            return Some(Word64::from_signed_int(cell.ascii as i64));
        }

        let idx = address as usize;
        self.ram_cells.get(idx).copied()
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests )
// ============================================================================
#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_vga_write_and_scroll() {
        let mut vga = VgaBuffer::new();
        vga.write_str("OMNICODE BOOT", VgaColor::White, VgaColor::Black);
        assert_eq!(vga.cells[0].ascii, b'O');
        assert_eq!(vga.cells[1].ascii, b'M');
        assert_eq!(vga.cells[12].ascii, b'T');
        assert_eq!(vga.cursor_col, 13);
        assert_eq!(vga.cursor_row, 0);

        vga.new_line();
        assert_eq!(vga.cursor_col, 0);
        assert_eq!(vga.cursor_row, 1);
    }

    #[test]
    fn test_physical_memory_map_mmio_dispatch() {
        let mut mem = PhysicalMemoryMap::new(1024);

        // Write to VGA MMIO
        let word_char = Word64::from_signed_int(b'A' as i64);
        mem.write(VGA_BUFFER_BASE, word_char).expect("VGA write");
        assert_eq!(mem.vga.cells[0].ascii, b'A');

        // Write to Serial COM1
        let word_serial = Word64::from_signed_int(b'!' as i64);
        mem.write(COM1_SERIAL_PORT, word_serial).expect("Serial write");
        assert_eq!(mem.serial.read_output(), "!");

        // Write to RAM
        mem.write(42, Word64::from_signed_int(999)).expect("RAM write");
        assert_eq!(mem.read(42).unwrap().payload().to_i64(), 999);
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/core/mod.rs RS 54 LINES 205 WORDS 2.1 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Core Subsystem Identity, Module Architecture, and Invariant Re-exports )
// ============================================================================
//! OmniCode Core Subsystem
//! Encapsulates the algebraic foundation: Ternary Quad-State, Boundaries, and Operators.

pub mod ternary;
pub mod boundaries;
pub mod operators;
pub mod filetype;
pub mod linguistics;
pub mod cell;
pub mod vessel;
pub mod tape;
pub mod word;
pub mod scene;
pub mod reel;
pub mod mmio;


// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Direct Core Access )
// ============================================================================
pub use ternary::{QuadState, TransportAction, ROLLBACK, AWAIT, PROCEED, HALT};
pub use boundaries::BoundaryType;
pub use operators::{BeingRelation, DirectionalVector, Connective, Polarity, AffixPosition};
pub use filetype::OmniFileType;
pub use linguistics::{PartOfSpeech, GrammaticalClassification, GrammaticalEntity, PronounKind, PronounCase, PronounPerson, PronounNumber};
pub use cell::{Cell, Trit, BYTE_HALT, BYTE_AWAIT, BYTE_ROLLBACK, BYTE_PROCEED};
pub use vessel::{Vessel, Offset, Capacity, Count};
pub use tape::{Roll, Tape, TapeHead};
pub use word::{Word32Trit, Word64};
pub use scene::Scene;
pub use reel::MemoryReel;
pub use mmio::{PhysicalMemoryMap, VgaBuffer, VgaColor, VgaCell, SerialPort, VGA_BUFFER_BASE, COM1_SERIAL_PORT};




// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Core Subsystem Invariant Definitions )
// ============================================================================
// Invariants and operators are actively materialized via re-exported submodules.


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Verification & Subsystem Status )
// ============================================================================
// Core module namespace verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/core/operators.rs RS 380 LINES 1303 WORDS 14.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Module Identity, 3D Coordinate Operators, Connectives & Vector Maps )
// ============================================================================
//! OmniCode Core: Relational, Directional, and Connective Operators
//!
//! Governs the 3-Dimensional Coordinate System:
//!     - Y-Axis (Being/State)      : = (IS), != (IS NOT), ~= (IS LIKE)
//!     - X-Axis (Causality/Action) : --> (Act Upon), <-- (Act Again)
//!     - Z-Axis (Scale/Layering)   : ^-- (Builds To), v-- (Breaks Down From)
//!     - Connectives               : ! (But), :: (And), : (In Relation To), | (Or), -- (Not)

use std::fmt;


// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Type Declarations: BeingRelation, DirectionalVector, and Connective Enums )
// ============================================================================
/// Relations of Being along the Ontological Y-Axis.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum BeingRelation {
    /// Exact identity / equivalence (=)
    Is,
    /// Distinction / exclusion (!=) (Not to be / inequality)
    IsNot,
    /// State negation / copular denial (=!) (Is not / To be not)
    ToBeNot,
    /// Homomorphism / structural analogy / duck typing (~=)
    ToBeLike,
    /// Invariant Balance / Equivalence (<=>)
    Equivalence,
    /// Relational strictly less than (<)
    LessThan,
    /// Relational strictly greater than (>)
    GreaterThan,
    /// Relational less than or equal (<=)
    LessEqual,
    /// Relational greater than or equal (>=)
    GreaterEqual,
}

/// Vectors of Action, Scale, and Spatial Quadrants across X, Y, and Z axes.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum DirectionalVector {
    // X-Axis (Temporal / Dynamics)
    /// Forward causation, execution, emission (-->)
    ActUpon,
    /// Retroactive feedback, retry, rollback (<--)
    ActAgain,

    // Z-Axis (Scale / Hierarchy)
    /// Layering Up: synthesis, abstraction, emergence (^-- / --^)
    BuildsTo,
    /// Layering Down: decomposition, destructuring, compilation to IR (v-- / --v)
    BreaksDownFrom,

    // Diagonal Modulated Scales
    /// Major ascending forward diagonal (/-^)
    Major,
    /// Minor descending forward diagonal (\-v)
    Minor,
    /// Great ascending backward diagonal (\-^)
    Great,
    /// Small descending backward diagonal (/-v)
    Small,

    // 2D Quadrant / Compass Vectors
    /// Upper Right (Quadrant I: +X, +Y) (/^)
    UpperRight,
    /// Lower Right (Quadrant IV: +X, -Y) (\v)
    LowerRight,
    /// Upper Left (Quadrant II: -X, +Y) (^\)
    UpperLeft,
```

```
    /// Lower Left (Quadrant III: -X, -Y) (v/)
    LowerLeft,
}

/// Logical and Structural Connectives.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum Connective {
    /// Adversative caveat: A ! B (A executes, BUT must satisfy caveat B)
    But,
    /// Cumulative conjunction: A :: B (A AND B simultaneous)
    And,
    /// Relational role / typing: A : B (A in relation to B)
    InRelationTo,
    /// Disjunction / alternative: A | B (A OR B)
    Or,
    /// Ontological inversion: -- A (NOT A)
    Not,
}

/// Polarity of an entity, keyword, or value.
/// '+' represents Abstract (archetype, intension, zero-cost blueprint).
/// '-' represents Concrete (extension, physical instance, allocated substance).
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum Polarity {
    Abstract,
    Concrete,
}

/// Affix position of a polarity operator attached to an identifier or keyword.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum AffixPosition {
    Prefix,  // +Dog, -Dog, +Cell
    Postfix, // Dog+, Dog-, PROCEED-
}

impl Polarity {
    pub fn from_symbol(sym: &str) -> Result<Self, String> {
        match sym.trim() {
            "+" => Ok(Polarity::Abstract),
            "-" => Ok(Polarity::Concrete),
            other => Err(format!("FAILPOINT [InvalidPolarity]: Unknown polarity symbol '{other}'")),
        }
    }

    pub fn symbol(&self) -> &'static str {
        match self {
            Polarity::Abstract => "+",
            Polarity::Concrete => "-",
        }
    }
}


// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Core Symbol Parsing & Semantic Transformations )
// ============================================================================
impl BeingRelation {
    pub fn from_symbol(sym: &str) -> Result<Self, String> {
        match sym.trim() {
            "=" => Ok(BeingRelation::Is),
            "!=" | "<>" => Ok(BeingRelation::IsNot),
            "=!" => Ok(BeingRelation::ToBeNot),
            "~=" | "=~" | "≈" => Ok(BeingRelation::ToBeLike),
            "<=>" => Ok(BeingRelation::Equivalence),
            "<" => Ok(BeingRelation::LessThan),
            ">" => Ok(BeingRelation::GreaterThan),
            "<=" => Ok(BeingRelation::LessEqual),
            ">=" => Ok(BeingRelation::GreaterEqual),
            other => Err(format!("FAILPOINT [InvalidBeingRelation]: Unknown symbol '{other}'")),
        }
    }

    pub fn symbol(&self) -> &'static str {
        match self {
            BeingRelation::Is => "=",
            BeingRelation::IsNot => "!=",
            BeingRelation::ToBeNot => "=!",
```

```
            BeingRelation::ToBeLike => "~=",
            BeingRelation::Equivalence => "<=>",
            BeingRelation::LessThan => "<",
            BeingRelation::GreaterThan => ">",
            BeingRelation::LessEqual => "<=",
            BeingRelation::GreaterEqual => ">=",
        }
    }
}

impl DirectionalVector {
    pub fn from_symbol(sym: &str) -> Result<Self, String> {
        match sym.trim() {
            "-->" | "->" => Ok(DirectionalVector::ActUpon),
            "<--" | "<-" => Ok(DirectionalVector::ActAgain),
            "--^" | "-^" | "^--" | "^-" | "↑" => Ok(DirectionalVector::BuildsTo),
            "--v" | "-v" | "v--" | "v-" | "↓" => Ok(DirectionalVector::BreaksDownFrom),
            "/-^" => Ok(DirectionalVector::Major),
            "\\-v" => Ok(DirectionalVector::Minor),
            "\\-^" => Ok(DirectionalVector::Great),
            "/-v" => Ok(DirectionalVector::Small),
            "/^" => Ok(DirectionalVector::UpperRight),
            "\\v" => Ok(DirectionalVector::LowerRight),
            "^\\" => Ok(DirectionalVector::UpperLeft),
            "v/" => Ok(DirectionalVector::LowerLeft),
            other => Err(format!("FAILPOINT [InvalidDirectionalVector]: Unknown vector symbol '{other}'")),
        }
    }

    /// Canonical ASCII symbol for the vector.
    pub fn symbol(&self) -> &'static str {
        match self {
            DirectionalVector::ActUpon => "-->",
            DirectionalVector::ActAgain => "<--",
            DirectionalVector::BuildsTo => "--^",
            DirectionalVector::BreaksDownFrom => "--v",
            DirectionalVector::Major => "/-^",
            DirectionalVector::Minor => "\\-v",
            DirectionalVector::Great => "\\-^",
            DirectionalVector::Small => "/-v",
            DirectionalVector::UpperRight => "/^",
            DirectionalVector::LowerRight => "\\v",
            DirectionalVector::UpperLeft => "^\\",
            DirectionalVector::LowerLeft => "v/",
        }
    }

    /// Fast 2-character ASCII shorthand symbol for the vector.
    pub fn shorthand(&self) -> &'static str {
        match self {
            DirectionalVector::ActUpon => "->",
            DirectionalVector::ActAgain => "<-",
            DirectionalVector::BuildsTo => "-^",
            DirectionalVector::BreaksDownFrom => "-v",
            DirectionalVector::Major => "/-^",
            DirectionalVector::Minor => "\\-v",
            DirectionalVector::Great => "\\-^",
            DirectionalVector::Small => "/-v",
            DirectionalVector::UpperRight => "/^",
            DirectionalVector::LowerRight => "\\v",
            DirectionalVector::UpperLeft => "^\\",
            DirectionalVector::LowerLeft => "v/",
        }
    }

    /// Cardinal direction on the computational coordinate plane.
    pub fn cardinal_direction(&self) -> &'static str {
        match self {
            DirectionalVector::ActUpon => "Right (Forward Causation / Advance)",
            DirectionalVector::ActAgain => "Left (Retroaction / Feedback / Rollback)",
            DirectionalVector::BuildsTo => "Up (Synthesis / Abstraction / Ascend)",
            DirectionalVector::BreaksDownFrom => "Down (Decomposition / Analysis / Descend)",
            DirectionalVector::Major => "Major (Ascending Forward Diagonal / Major Scale)",
            DirectionalVector::Minor => "Minor (Descending Forward Diagonal / Minor Scale)",
            DirectionalVector::Great => "Great (Ascending Backward Diagonal / Great Scale)",
            DirectionalVector::Small => "Small (Descending Backward Diagonal / Small Scale)",
            DirectionalVector::UpperRight => "Upper Right (Quadrant I: +X, +Y / Northeast)",
            DirectionalVector::LowerRight => "Lower Right (Quadrant IV: +X, -Y / Southeast)",
```

```
            DirectionalVector::UpperLeft => "Upper Left (Quadrant II: -X, +Y / Northwest)",
            DirectionalVector::LowerLeft => "Lower Left (Quadrant III: -X, -Y / Southwest)",
        }
    }
}

impl Connective {
    pub fn from_symbol(sym: &str) -> Result<Self, String> {
        match sym.trim() {
            "!" => Ok(Connective::But),
            "::" | "&&" => Ok(Connective::And),
            ":" => Ok(Connective::InRelationTo),
            "|" | "||" => Ok(Connective::Or),
            "--" | "not" | "~" => Ok(Connective::Not),
            other => Err(format!("FAILPOINT [InvalidConnective]: Unknown connective symbol '{other}'")),
        }
    }

    pub fn symbol(&self) -> &'static str {
        match self {
            Connective::But => "!",
            Connective::And => "::",
            Connective::InRelationTo => ":",
            Connective::Or => "|",
            Connective::Not => "--",
        }
    }
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Display Trait Implementations and String Formatting )
// ============================================================================
impl fmt::Display for BeingRelation {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        write!(f, "{}", self.symbol())
    }
}

impl fmt::Display for DirectionalVector {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        write!(f, "{}", self.symbol())
    }
}

impl fmt::Display for Connective {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        write!(f, "{}", self.symbol())
    }
}

impl fmt::Display for Polarity {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        write!(f, "{}", self.symbol())
    }
}

impl fmt::Display for AffixPosition {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        match self {
            AffixPosition::Prefix => write!(f, "Prefix"),
            AffixPosition::Postfix => write!(f, "Postfix"),
        }
    }
}

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_polarity_and_affix_operators() {
        assert_eq!(Polarity::from_symbol("+").unwrap(), Polarity::Abstract);
        assert_eq!(Polarity::from_symbol("-").unwrap(), Polarity::Concrete);
        assert_eq!(Polarity::Abstract.symbol(), "+");
        assert_eq!(Polarity::Concrete.symbol(), "-");
        assert_eq!(format!("{}", Polarity::Abstract), "+");
```

```
        assert_eq!(format!("{}", Polarity::Concrete), "-");
    }

    #[test]
    fn test_directional_vectors_canonical_and_shorthand() {
        // Canonical 3-character symbols
        assert_eq!(DirectionalVector::from_symbol("-->").unwrap(), DirectionalVector::ActUpon);
        assert_eq!(DirectionalVector::from_symbol("<--").unwrap(), DirectionalVector::ActAgain);
        assert_eq!(DirectionalVector::from_symbol("--^").unwrap(), DirectionalVector::BuildsTo);
        assert_eq!(DirectionalVector::from_symbol("--v").unwrap(), DirectionalVector::BreaksDownFrom);

        // Fast 2-character shorthands
        assert_eq!(DirectionalVector::from_symbol("->").unwrap(), DirectionalVector::ActUpon);
        assert_eq!(DirectionalVector::from_symbol("<-").unwrap(), DirectionalVector::ActAgain);
        assert_eq!(DirectionalVector::from_symbol("-^").unwrap(), DirectionalVector::BuildsTo);
        assert_eq!(DirectionalVector::from_symbol("-v").unwrap(), DirectionalVector::BreaksDownFrom);

        // Legacy symbols
        assert_eq!(DirectionalVector::from_symbol("^--").unwrap(), DirectionalVector::BuildsTo);
        assert_eq!(DirectionalVector::from_symbol("v--").unwrap(), DirectionalVector::BreaksDownFrom);

        // Symbols emit canonical forms
        assert_eq!(DirectionalVector::BuildsTo.symbol(), "--^");
        assert_eq!(DirectionalVector::BreaksDownFrom.symbol(), "--v");

        // Scale Modulations
        assert_eq!(DirectionalVector::from_symbol("/-^").unwrap(), DirectionalVector::Major);
        assert_eq!(DirectionalVector::from_symbol("\\-v").unwrap(), DirectionalVector::Minor);
        assert_eq!(DirectionalVector::from_symbol("\\-^").unwrap(), DirectionalVector::Great);
        assert_eq!(DirectionalVector::from_symbol("/-v").unwrap(), DirectionalVector::Small);

        // 2D Quadrants
        assert_eq!(DirectionalVector::from_symbol("/^").unwrap(), DirectionalVector::UpperRight);
        assert_eq!(DirectionalVector::from_symbol("\\v").unwrap(), DirectionalVector::LowerRight);
        assert_eq!(DirectionalVector::from_symbol("^\\").unwrap(), DirectionalVector::UpperLeft);
        assert_eq!(DirectionalVector::from_symbol("v/").unwrap(), DirectionalVector::LowerLeft);
    }

    #[test]
    fn test_being_relations_canonical() {
        assert_eq!(BeingRelation::from_symbol("=").unwrap(), BeingRelation::Is);
        assert_eq!(
            BeingRelation::from_symbol("!=").unwrap(),
            BeingRelation::IsNot
        );
        assert_eq!(
            BeingRelation::from_symbol("=!").unwrap(),
            BeingRelation::ToBeNot
        );
        assert_eq!(
            BeingRelation::from_symbol("~=").unwrap(),
            BeingRelation::ToBeLike
        );
        assert_eq!(
            BeingRelation::from_symbol("=~").unwrap(),
            BeingRelation::ToBeLike
        );
        assert_eq!(
            BeingRelation::from_symbol("<=>").unwrap(),
            BeingRelation::Equivalence
        );

        assert_eq!(BeingRelation::Is.symbol(), "=");
        assert_eq!(BeingRelation::IsNot.symbol(), "!=");
        assert_eq!(BeingRelation::ToBeNot.symbol(), "=!");
        assert_eq!(BeingRelation::ToBeLike.symbol(), "~=");
        assert_eq!(BeingRelation::Equivalence.symbol(), "<=>");
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/core/reel.rs RS 286 LINES 1090 WORDS 11.5 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( 4-Directional Toroidal Memory Reel: Transport Kinematics & Scene Spool )
// ============================================================================
//! OmniCode Core: 4-Directional Memory Reel
//!
//! Spools memory across two orthogonal mechanical axes:
//! 1. **Horizontal Ribbon Navigation:**
//!    - `push_forward(word)` (`-->`): Advances write head along the track.
//!    - `pull_back()` (`<--`): Recedes backward along the track to inspect/undo.
//! 2. **Vertical Spool Hierarchy Navigation:**
//!    - `sink_in(name, cap)` (`v--`): Cuts into a child scene (pushes stack frame).
//!    - `pop_out()` (`^--`): Cuts back to parent scene (pops stack frame).
//!
//! Governed by the Quad-State Transport Kinematics:
//! `PLAY` (+1), `PAUSE` (0), `REWIND` (-1), `STOP` (NULL).

use std::fmt;
use crate::core::scene::Scene;
use crate::core::ternary::TransportAction;
use crate::core::word::Word64;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( MemoryReel Struct Definition & Constructor )
// ============================================================================

/// A 4-directional spooled memory stack and multi-track film canister.
#[derive(Debug, Clone, PartialEq)]
pub struct MemoryReel {
    pub name: String,
    pub transport: TransportAction,
    pub scenes: Vec<Scene>,
    pub next_scene_id: usize,
}

impl MemoryReel {
    /// Creates a new MemoryReel initialized with a root master scene (depth 0).
    pub fn new(name: impl Into<String>, root_capacity: usize) -> Self {
        let root_scene = Scene::new(0, "MasterSet_0", root_capacity, 0, Some("genesis".to_string()));
        Self {
            name: name.into(),
            transport: TransportAction::Pause,
            scenes: vec![root_scene],
            next_scene_id: 1,
        }
    }

    /// Returns a reference to the currently active camera scene.
    pub fn active_scene(&self) -> &Scene {
        self.scenes.last().expect("Reel must always contain at least one scene")
    }

    /// Returns a mutable reference to the currently active camera scene.
    pub fn active_scene_mut(&mut self) -> &mut Scene {
        self.scenes.last_mut().expect("Reel must always contain at least one scene")
    }

    /// Returns the current spindle depth level (0 = Master set).
    pub fn depth(&self) -> usize {
        self.active_scene().depth
    }

    /// Returns the total number of scenes currently on the reel spindle.
    pub fn scene_count(&self) -> usize {
        self.scenes.len()
    }
}


// ============================================================================
// BLOCK 3: BODY BLOCK
// ( The 4 Mechanical Motions: Push Forward, Pull Back, Sink In, Pop Out )
// ============================================================================
```

```

impl MemoryReel {
    // ---------------------------------------------------------------------------
    // Axis 1: Horizontal Track Motions (--> and <--)
    // ---------------------------------------------------------------------------

    /// **Push Forward (`-->`):**
    /// Advances the track head, inscribes the physical word at the new position,
    /// and sets transport to `PLAY`.
    pub fn push_forward(&mut self, word: Word64) -> Result<usize, String> {
        let scene = self.active_scene_mut();
        let target_pos = scene.head_pos;

        if target_pos >= scene.capacity {
            return Err(format!(
                "FAILPOINT [ReelCapacityReached]: Track head at @0x{:04X} exceeded scene capacity {}",
                target_pos, scene.capacity
            ));
        }

        scene.write(target_pos, word)?;
        scene.head_pos += 1;
        self.transport = TransportAction::Play;
        Ok(target_pos)
    }

    /// **Pull Back (`<--`):**
    /// Recedes the track head backward along the ribbon to inspect antecedent props
    /// or perform transactional retreat without destroying future frame cells.
    pub fn pull_back(&mut self) -> Option<Word64> {
        let scene = self.active_scene_mut();
        if scene.head_pos > 0 {
            scene.head_pos -= 1;
            scene.read(scene.head_pos)
        } else {
            scene.read(0)
        }
    }

    // ---------------------------------------------------------------------------
    // Axis 2: Vertical Spool Hierarchy Motions (v-- and ^--)
    // ---------------------------------------------------------------------------

    /// **Sink In (`v--`):**
    /// Cuts into a subordinate scene (pushes a new stack frame onto the spindle).
    /// The parent scene remains frozen and untouched above it.
    pub fn sink_in(
        &mut self,
        scene_name: impl Into<String>,
        capacity: usize,
        landmark: Option<String>,
    ) -> usize {
        let parent_depth = self.depth();
        let scene_id = self.next_scene_id;
        self.next_scene_id += 1;

        let child_scene = Scene::new(scene_id, scene_name, capacity, parent_depth + 1, landmark);
        self.scenes.push(child_scene);
        self.depth()
    }

    /// **Pop Out (`^--`):**
    /// Completes the subordinate scene, pops the stack frame off the spindle,
    /// and restores the camera framing to the supervisory parent set.
    pub fn pop_out(&mut self) -> Result<Scene, String> {
        if self.scenes.len() <= 1 {
            return Err("FAILPOINT [RootScenePop]: Cannot pop out of the master root scene (Depth 0)".to_string());
        }
        let completed = self.scenes.pop().expect("Scene pop must succeed");
        Ok(completed)
    }

    // ---------------------------------------------------------------------------
    // Transport Kinematics Controls: Play, Pause, Rewind, Stop
    // ---------------------------------------------------------------------------

    /// Sets transport to `PLAY` (+1 / PROCEED).
    pub fn play(&mut self) -> TransportAction {
```

```
        self.transport = TransportAction::Play;
        self.transport
    }

    /// Sets transport to `PAUSE` (0 / AWAIT).
    pub fn pause(&mut self) -> TransportAction {
        self.transport = TransportAction::Pause;
        self.transport
    }

    /// **Rewinds (`<--` / -1 / ROLLBACK):**
    /// Spools the track head backward to a designated scene landmark cue.
    pub fn rewind_to_landmark(&mut self, target_cue: &str) -> Result<usize, String> {
        let scene = self.active_scene_mut();
        if let Some(ref landmark) = scene.landmark {
            if landmark == target_cue {
                scene.head_pos = 0;
                self.transport = TransportAction::Rewind;
                return Ok(0);
            }
        }
        Err(format!(
            "FAILPOINT [LandmarkNotFound]: Active scene '{}' does not match landmark cue '<{target_cue}>'",
            scene.name
        ))
    }

    /// Sets transport to `STOP` (NULL / HALT).
    pub fn stop(&mut self) -> TransportAction {
        self.transport = TransportAction::Stop;
        self.transport
    }

    /// Generates a cinematic ASCII status dashboard of the memory reel.
    pub fn inspect(&self) -> String {
        let mut out = String::new();
        out.push_str(&format!("═══════════════════════════════════════════════════════════════\n"));
        out.push_str(&format!("REEL: [{}] | TRANSPORT: [{:?}]\n", self.name, self.transport));
        out.push_str(&format!("SPINDLE DEPTH: {} | TOTAL SCENES: {}\n", self.depth(), self.scene_count()));
        out.push_str(&format!("---------------------------------------------------------------\n"));
        for (i, sc) in self.scenes.iter().enumerate() {
            let active_marker = if i == self.scenes.len() - 1 { "▶ [ACTIVE]" } else { "  [FROZEN]" };
            out.push_str(&format!("  {} Level {}: {}\n", active_marker, sc.depth, sc));
        }
        out.push_str(&format!("═══════════════════════════════════════════════════════════════\n"));
        out
    }
}

impl fmt::Display for MemoryReel {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        write!(
            f,
            "Reel [{} | Transport: {:?} | Depth: {} | Active: {}]",
            self.name, self.transport, self.depth(), self.active_scene().name
        )
    }
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Verification Proof )
// ============================================================================
#[cfg(test)]
mod tests {
    use super::*;
    use crate::core::word::Word32Trit;
    use crate::core::ternary::QuadState;
    use crate::core::operators::Polarity;
    use crate::core::boundaries::BoundaryType;

    #[test]
    fn test_reel_4_directional_motions() {
        let mut reel = MemoryReel::new("CinemaReel", 32);
        assert_eq!(reel.depth(), 0);
        assert_eq!(reel.scene_count(), 1);

```

```
        // 1. Push Forward (-->) on master set
        let w1 = Word64::new(Word32Trit::from_i64(10), QuadState::Proceed, Polarity::Concrete, BoundaryType::Denotation,
0);
        let pos1 = reel.push_forward(w1).expect("Push forward 1");
        assert_eq!(pos1, 0);
        assert_eq!(reel.transport, TransportAction::Play);

        let w2 = Word64::new(Word32Trit::from_i64(20), QuadState::Proceed, Polarity::Concrete, BoundaryType::Denotation,
0);
        let pos2 = reel.push_forward(w2).expect("Push forward 2");
        assert_eq!(pos2, 1);

        // 2. Pull Back (<--) along master track
        let back_word = reel.pull_back().expect("Pull back");
        assert_eq!(back_word.payload().to_i64(), 20);

        // 3. Sink In (v--) into nested sub-scene
        let depth = reel.sink_in("CloseUp_Scene", 16, Some("closeup_take".to_string()));
        assert_eq!(depth, 1);
        assert_eq!(reel.depth(), 1);
        assert_eq!(reel.scene_count(), 2);
        assert_eq!(reel.active_scene().name, "CloseUp_Scene");

        // Write in nested sub-scene
        let w_sub = Word64::new(Word32Trit::from_i64(999), QuadState::Proceed, Polarity::Concrete,
BoundaryType::Denotation, 0);
        reel.push_forward(w_sub).expect("Push in sub-scene");
        assert_eq!(reel.active_scene().read(0).unwrap().payload().to_i64(), 999);

        // 4. Pop Out (^--) back to master wide shot
        let popped = reel.pop_out().expect("Pop out to master");
        assert_eq!(popped.name, "CloseUp_Scene");
        assert_eq!(reel.depth(), 0);
        assert_eq!(reel.active_scene().name, "MasterSet_0");
        assert_eq!(reel.scene_count(), 1);

        // Verify master set props were unaffected by sub-scene
        assert_eq!(reel.active_scene().read(0).unwrap().payload().to_i64(), 10);
        assert_eq!(reel.active_scene().read(1).unwrap().payload().to_i64(), 20);
    }

    #[test]
    fn test_reel_rewind_to_landmark() {
        let mut reel = MemoryReel::new("TakeReel", 32);
        reel.sink_in("TakeScene", 16, Some("scene_cue".to_string()));

        let w = Word64::new(Word32Trit::from_i64(42), QuadState::Proceed, Polarity::Concrete, BoundaryType::Denotation,
0);
        reel.push_forward(w).unwrap();
        reel.push_forward(w).unwrap();
        assert_eq!(reel.active_scene().head_pos, 2);

        // Rewind to landmark
        let reset_pos = reel.rewind_to_landmark("scene_cue").expect("Rewind to cue");
        assert_eq!(reset_pos, 0);
        assert_eq!(reel.active_scene().head_pos, 0);
        assert_eq!(reel.transport, TransportAction::Rewind);
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/core/scene.rs RS 130 LINES 449 WORDS 4.3 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Scene Memory Frame: Set, Props & Landmark Clapper )
// ============================================================================
//! OmniCode Core: Scene Memory Frame
//!
//! Represents a unified memory stack frame / cinematic set where instructions
//! (rolls) operate upon local props (memory cells):
//! - **Set:** Bounded memory partition slice.
//! - **Props:** Physical 64-bit / 32-trit memory cells.
//! - **Clapper Landmark:** Scene cue point for retakes and rewind operations.

use std::fmt;
use crate::core::word::Word64;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Scene Struct Definition & Constructor )
// ============================================================================

/// A memory stack frame and camera set in the OmniCode cinema architecture.
#[derive(Debug, Clone, PartialEq)]
pub struct Scene {
    pub id: usize,
    pub name: String,
    pub depth: usize,
    pub landmark: Option<String>,
    pub capacity: usize,
    pub head_pos: usize,
    pub cells: Vec<Word64>,
}

impl Scene {
    /// Creates a new Scene set with bounded cell capacity.
    pub fn new(
        id: usize,
        name: impl Into<String>,
        capacity: usize,
        depth: usize,
        landmark: Option<String>,
    ) -> Self {
        let cap = capacity.max(8);
        Self {
            id,
            name: name.into(),
            depth,
            landmark,
            capacity: cap,
            head_pos: 0,
            cells: vec![Word64::default(); cap],
        }
    }

    /// Returns the number of allocated cells in this scene.
    pub fn len(&self) -> usize {
        self.cells.len()
    }

    /// Returns true if this scene has zero capacity.
    pub fn is_empty(&self) -> bool {
        self.cells.is_empty()
    }

    /// Reads a memory cell prop at an explicit offset.
    pub fn read(&self, offset: usize) -> Option<Word64> {
        self.cells.get(offset).copied()
    }

    /// Inscribes a memory cell prop at an explicit offset with bounds enforcement.
    pub fn write(&mut self, offset: usize, word: Word64) -> Result<(), String> {
        if offset >= self.capacity {
            return Err(format!(
                "FAILPOINT [SceneBoundsOverflow]: Scene '{}' capacity is {}, but attempted write at offset {}",
                self.name, self.capacity, offset
```

```
            ));
        }
        self.cells[offset] = word;
        Ok(())
    }

    /// Reads the prop directly under the active scene head.
    pub fn current(&self) -> Option<Word64> {
        self.read(self.head_pos)
    }
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Scene Display Formatting )
// ============================================================================

impl fmt::Display for Scene {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        let landmark_str = self.landmark.as_deref().unwrap_or("none");
        write!(
            f,
            "Scene [{} | ID: {} | Depth: {} | Landmark: <{}> | Head: @0x{:04X} | Cells: {}/{}]",
            self.name, self.id, self.depth, landmark_str, self.head_pos, self.cells.len(), self.capacity
        )
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests )
// ============================================================================
#[cfg(test)]
mod tests {
    use super::*;
    use crate::core::word::Word32Trit;
    use crate::core::ternary::QuadState;
    use crate::core::operators::Polarity;
    use crate::core::boundaries::BoundaryType;

    #[test]
    fn test_scene_creation_and_bounded_write() {
        let mut scene = Scene::new(0, "TestSet", 16, 0, Some("take_1".to_string()));
        assert_eq!(scene.name, "TestSet");
        assert_eq!(scene.depth, 0);
        assert_eq!(scene.capacity, 16);

        let word = Word64::new(Word32Trit::from_i64(77), QuadState::Proceed, Polarity::Concrete,
BoundaryType::Denotation, 1);
        scene.write(3, word).expect("Write to offset 3");
        assert_eq!(scene.read(3).unwrap().payload().to_i64(), 77);

        // Bounds overflow rejection
        assert!(scene.write(16, word).is_err());
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/core/tape.rs RS 497 LINES 1828 WORDS 19.1 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Tape Subsystem Identity, Ribbon Physical Topology & Invariants )
// ================================================================================
//! OmniCode Core Subsystem: Physical Tape & Roll Execution Topology
//!
//! # Physical Computing Hierarchy
//! In the OmniCode Operating System, execution does not use raw unstructured threads.
//! It follows a strict 3-tier physical hierarchy:
//!
//! $$\text{Roll} \longrightarrow \text{Tape} \longrightarrow \text{Track}$$
//!
//! 1. **Roll (Instruction Line):** An atomic line of code executing an SVO transformation.
//! 2. **Tape (Process Ribbon):** A sequential chain of rolls led by a **Tape Head**
//!    (the covenant manifest declaring Who, What, When, Where, Why, and How).
//! 3. **Track (Subsystem Channel):** A concurrent execution lane on the scheduler
//!    (Track 0: Kernel, Track 1: Terminal, Track 2: Apps).
//!
//! # Tape Head Anatomy
//! The Tape Head is the first roll on the ribbon. It establishes:
//! - Identity & Name (`[Tape.<Name>]`)
//! - Principal & Caller (`WHO {Caller}`)
//! - Target Entity (`WHAT {Target}`)
//! - Lifecycle Trigger (`WHEN {Phase}`)
//! - Memory Partition Ceiling (`WHERE {partition} = [ <N> ]`)
//! - Teleological Purpose Aside (`WHY ( ... )`)
//! - Operational Vector (`HOW [ ... ]`)

use std::fs;
use std::path::Path;
use crate::core::ternary::QuadState;
use crate::diagnostics::logger::DiagnosticLogger;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Tape Data Structures, Roll Containers and Context )
// ================================================================================

/// An atomic line of code on a Tape ribbon.
#[derive(Debug, Clone, PartialEq)]
pub struct Roll {
    /// 0-indexed position within the tape's rolls.
    pub index: usize,
    /// 1-indexed source line number.
    pub line_number: usize,
    /// Raw text content of the roll.
    pub text: String,
    /// Current execution state of this roll (+1: PROCEED, 0: AWAIT, -1: ROLLBACK, NULL: HALT).
    pub status: QuadState,
    /// Whether this roll is the leading Tape Head covenant.
    pub is_head: bool,
}

/// The leading covenant roll establishing the process manifest and memory bounds.
#[derive(Debug, Clone, PartialEq)]
pub struct TapeHead {
    /// Identifier or process name.
    pub name: String,
    /// Cardinal Clause: WHO (Caller / Principal).
    pub who: String,
    /// Cardinal Clause: WHAT (Process substance).
    pub what: String,
    /// Cardinal Clause: WHEN (Trigger precondition).
    pub when_clause: String,
    /// Cardinal Clause: WHERE (Target partition or spatial bounds).
    pub where_clause: String,
    /// Cardinal Clause: WHY (Teleological intent aside).
    pub why: String,
    /// Cardinal Clause: HOW (Directional vector and methodology).
    pub how: String,
    /// Required memory partition size in cells (carved from Storehouse via `v--`).
    pub required_partition_size: usize,
    /// Complete raw text of the Tape Head roll.
    pub raw_text: String,
```

```rust
}

impl Default for TapeHead {
    fn default() -> Self {
        Self {
            name: "Anonymous_Tape".to_string(),
            who: "System".to_string(),
            what: "Process".to_string(),
            when_clause: "Immediate".to_string(),
            where_clause: "Memory".to_string(),
            why: "Execution".to_string(),
            how: "Forward".to_string(),
            required_partition_size: 256,
            raw_text: String::new(),
        }
    }
}

/// A complete sequential process ribbon executed roll-by-roll.
#[derive(Debug, Clone)]
pub struct Tape {
    /// The leading covenant manifest.
    pub head: TapeHead,
    /// The sequence of subordinate execution rolls.
    pub rolls: Vec<Roll>,
    /// Active cursor pointing to the roll currently being executed.
    pub cursor: usize,
    /// Name of the isolated memory partition allocated for this tape.
    pub bound_partition: Option<String>,
    /// Overall execution quad-state.
    pub execution_state: QuadState,
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Tape Parsing, Stepping, and Execution Management )
// ============================================================================

impl Tape {
    /// Parses a native `.tape` source string into a structured [`Tape`].
    pub fn from_source(source: &str, logger: DiagnosticLogger) -> Result<Self, String> {
        let mut head_opt: Option<TapeHead> = None;
        let mut raw_roll_lines: Vec<(usize, String)> = Vec::new();

        let mut head_text_accumulator = String::new();
        let mut parsing_multiline_head = false;
        let mut is_block_head = false;

        for (zero_idx, raw_line) in source.lines().enumerate() {
            let line_number = zero_idx + 1;
            let trimmed = raw_line.trim();

            // Skip comment boundaries (# ...)
            if trimmed.starts_with('#') || trimmed.is_empty() {
                continue;
            }

            // Detect Tape Head
            if head_opt.is_none() {
                if !parsing_multiline_head {
                    if trimmed.starts_with('[')
                        || trimmed.starts_with("= [Tape")
                        || trimmed.starts_with("Tape [")
                        || trimmed.starts_with("Tape <")
                    {
                        parsing_multiline_head = true;
                        is_block_head = trimmed.ends_with('{');
                        head_text_accumulator.push_str(trimmed);
                        head_text_accumulator.push(' ');
                        // Check if closed on same line (only if not opening a block with '{')
                        if !is_block_head && (trimmed.contains(":: <") || (!trimmed.contains("WHERE") &&
!trimmed.contains("WHO"))) {
                            parsing_multiline_head = false;
                            let head = Self::parse_tape_head(&head_text_accumulator, line_number)?;
                            logger.log("TAPE", format!("Discovered Tape Head: [{}]", head.name));
                            head_opt = Some(head);
                            head_text_accumulator.clear();
                        }
```

```
                    } else {
                        // Plain line without leading bracket treated as fallback roll
                        raw_roll_lines.push((line_number, trimmed.to_string()));
                    }
                } else {
                    // Accumulating multiline Tape Head
                    if is_block_head {
                        if trimmed == "}" || trimmed.ends_with('}') {
                            // Closing brace of block-manifest Tape Head
                            parsing_multiline_head = false;
                            is_block_head = false;
                            let head = Self::parse_tape_head(&head_text_accumulator, line_number)?;
                            logger.log("TAPE", format!("Discovered Tape Head: [{}]", head.name));
                            head_opt = Some(head);
                            head_text_accumulator.clear();
                            continue;
                        } else {
                            head_text_accumulator.push_str(trimmed);
                            head_text_accumulator.push(' ');
                        }
                    } else if trimmed.starts_with("WHERE")
                        || trimmed.starts_with("WHEN")
                        || trimmed.starts_with("WHY")
                        || trimmed.starts_with("HOW")
                        || trimmed.starts_with("WHO")
                        || trimmed.starts_with("WHAT")
                        || trimmed.starts_with("< Scripture")
                        || trimmed.starts_with("::")
                        || trimmed.contains(":: <")
                    {
                        head_text_accumulator.push_str(trimmed);
                        head_text_accumulator.push(' ');
                    } else {
                        // Current line is not part of the head; the multiline head is complete
                        parsing_multiline_head = false;
                        let head = Self::parse_tape_head(&head_text_accumulator, line_number.saturating_sub(1))?;
                        logger.log("TAPE", format!("Discovered Tape Head: [{}]", head.name));
                        head_opt = Some(head);
                        head_text_accumulator.clear();

                        raw_roll_lines.push((line_number, trimmed.to_string()));
                    }
                }
                continue;
            }

            raw_roll_lines.push((line_number, trimmed.to_string()));
        }

        // If multiline head was accumulating at EOF
        if head_opt.is_none() && !head_text_accumulator.is_empty() {
            let head = Self::parse_tape_head(&head_text_accumulator, 1)?;
            head_opt = Some(head);
        }

        let head = head_opt.unwrap_or_else(|| TapeHead {
            name: "Default_Tape".to_string(),
            raw_text: "[Default_Tape]".to_string(),
            ..Default::default()
        });

        // Group raw_roll_lines into cohesive, multiline-aware Rolls
        let mut rolls = Vec::new();
        let mut cur_roll_text = String::new();
        let mut cur_roll_line = 1;
        let mut bracket_balance: i32 = 0;

        let is_new_roll_start = |s: &str| -> bool {
            let upper = s.to_uppercase();
            upper.starts_with("ROLL_")
                || upper.starts_with("[ ROLL")
                || upper.starts_with("[ROLL")
        };

        for (line_num, line_str) in raw_roll_lines {
            let starts_new = is_new_roll_start(&line_str);

            if starts_new && !cur_roll_text.is_empty() && bracket_balance <= 0 {
```

```
                rolls.push(Roll {
                    index: rolls.len(),
                    line_number: cur_roll_line,
                    text: cur_roll_text.trim().to_string(),
                    status: QuadState::Proceed,
                    is_head: false,
                });
                cur_roll_text.clear();
                bracket_balance = 0;
            }

            if cur_roll_text.is_empty() {
                cur_roll_line = line_num;
            }

            for ch in line_str.chars() {
                match ch {
                    '[' | '{' => bracket_balance += 1,
                    ']' | '}' => bracket_balance -= 1,
                    _ => {}
                }
            }

            cur_roll_text.push_str(&line_str);
            cur_roll_text.push(' ');

            // If not an explicit roll_... format and bracket_balance == 0, flush standalone roll
            if !starts_new && !cur_roll_text.starts_with("roll_") && !cur_roll_text.to_uppercase().starts_with("[ ROLL")
&& bracket_balance <= 0 {
                rolls.push(Roll {
                    index: rolls.len(),
                    line_number: cur_roll_line,
                    text: cur_roll_text.trim().to_string(),
                    status: QuadState::Proceed,
                    is_head: false,
                });
                cur_roll_text.clear();
                bracket_balance = 0;
            }
        }

        if !cur_roll_text.trim().is_empty() {
            rolls.push(Roll {
                index: rolls.len(),
                line_number: cur_roll_line,
                text: cur_roll_text.trim().to_string(),
                status: QuadState::Proceed,
                is_head: false,
            });
        }

        Ok(Self {
            head,
            rolls,
            cursor: 0,
            bound_partition: None,
            execution_state: QuadState::Proceed,
        })
    }

    /// Loads and parses a `.tape` file from the filesystem.
    pub fn from_file(path: impl AsRef<Path>, logger: DiagnosticLogger) -> Result<Self, String> {
        let p = path.as_ref();
        let resolved = crate::core::filetype::resolve_track_path(p);
        let content = fs::read_to_string(&resolved)
            .map_err(|e| format!("Failed to read tape file {:?}: {e}", resolved))?;
        Self::from_source(&content, logger)
    }

    /// Parses the raw text of a Tape Head roll into structured cardinal clauses.
    fn parse_tape_head(text: &str, line_number: usize) -> Result<TapeHead, String> {
        let clean = text.trim();

        // 1. Extract Name (e.g., from `[ Process { State } ]`, `[Tape.Name]` or `[Cell]`)
        let name = if let Some(proc_idx) = clean.find("Process {") {
            if let Some(end_brace) = clean[proc_idx..].find('}') {
                clean[proc_idx + 9..proc_idx + end_brace].trim().to_string()
            } else {
```

```
                "Process".to_string()
            }
        } else if let Some(start) = clean.find('[') {
            if let Some(end) = clean[start..].find(']') {
                let inner = &clean[start + 1..start + end];
                inner.trim_start_matches("Tape.").trim().to_string()
            } else {
                format!("Tape_L{}", line_number)
            }
        } else {
            format!("Tape_L{}", line_number)
        };

        // 2. Extract Cardinal Clauses
        let who = extract_clause(clean, "WHO").unwrap_or_else(|| "System".to_string());
        let what = extract_clause(clean, "WHAT").unwrap_or_else(|| name.clone());
        let when_clause = extract_clause(clean, "WHEN").unwrap_or_else(|| "Opening".to_string());
        let where_clause = extract_clause(clean, "WHERE").unwrap_or_else(|| "Memory".to_string());
        let why = extract_parenthetical(clean, "WHY").unwrap_or_else(|| "Operational task".to_string());
        let how = extract_clause(clean, "HOW").unwrap_or_else(|| "+1 : PROCEED".to_string());

        // 3. Extract required partition size from WHERE clause
        let mut required_partition_size = 256;
        if clean.contains("WHERE") {
            for token in clean.split_whitespace() {
                if let Ok(num) = token.trim_matches(|c: char| !c.is_ascii_digit()).parse::<usize>() {
                    if num > 0 {
                        required_partition_size = num;
                        break;
                    }
                }
            }
        }

        Ok(TapeHead {
            name,
            who,
            what,
            when_clause,
            where_clause,
            why,
            how,
            required_partition_size,
            raw_text: clean.to_string(),
        })
    }

    /// Returns the roll currently under the Tape Head cursor.
    pub fn active_roll(&self) -> Option<&Roll> {
        self.rolls.get(self.cursor)
    }

    /// Advances the Tape Head cursor to the next roll, returning the newly focused roll.
    pub fn advance(&mut self) -> Option<&Roll> {
        if self.cursor < self.rolls.len() {
            self.cursor += 1;
        }
        self.active_roll()
    }

    /// Returns true if all subordinate rolls have been traversed.
    pub fn is_finished(&self) -> bool {
        self.cursor >= self.rolls.len()
    }

    /// Resets the Tape Head back to the first subordinate roll.
    pub fn reset(&mut self) {
        self.cursor = 0;
        for r in &mut self.rolls {
            r.status = QuadState::Proceed;
        }
        self.execution_state = QuadState::Proceed;
    }

    /// Rewinds the Tape Head cursor back to an explicit roll index.
    pub fn rewind_to(&mut self, target_index: usize) {
        if target_index < self.rolls.len() {
            self.cursor = target_index;
```

```
        }
    }

    /// Searches for a roll containing a scene landmark cue `< landmark >` or name.
    pub fn find_landmark_index(&self, landmark: &str) -> Option<usize> {
        let trimmed = landmark.trim();
        for (idx, roll) in self.rolls.iter().enumerate() {
            if roll.text.contains(&format!("< {trimmed} >"))
                || roll.text.contains(&format!("<{trimmed}>"))
                || roll.text.contains(&format!("::{trimmed}"))
                || roll.text.contains(trimmed)
            {
                return Some(idx);
            }
        }
        None
    }

    /// Total number of subordinate rolls on the tape.
    pub fn roll_count(&self) -> usize {
        self.rolls.len()
    }
}


/// Helper function to extract clause content bounded by braces `{...}` or brackets `[...]`.
fn extract_clause(text: &str, keyword: &str) -> Option<String> {
    if let Some(pos) = text.find(keyword) {
        let rest = &text[pos + keyword.len()..];
        // Look for { ... }
        if let Some(open) = rest.find('{') {
            if let Some(close) = rest[open..].find('}') {
                return Some(rest[open + 1..open + close].trim().to_string());
            }
        }
        // Look for [ ... ]
        if let Some(open) = rest.find('[') {
            if let Some(close) = rest[open..].find(']') {
                return Some(rest[open + 1..open + close].trim().to_string());
            }
        }
    }
    None
}

/// Helper function to extract aside content bounded by parentheses `(...)`.
fn extract_parenthetical(text: &str, keyword: &str) -> Option<String> {
    if let Some(pos) = text.find(keyword) {
        let rest = &text[pos + keyword.len()..];
        if let Some(open) = rest.find('(') {
            if let Some(close) = rest[open..].find(')') {
                return Some(rest[open + 1..open + close].trim().to_string());
            }
        }
    }
    None
}

// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests, Verification & Subsystem Sealing )
// ================================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_tape_parsing_and_head_extraction() {
        let source = r#"
            # Definition Roll / Tape Head
            [Tape.TaskWorker] : WHO {User} WHAT {Worker} --> DISPATCH {Worker}
                WHEN {Opening}
                WHERE {partition} = [ 512 ]
                WHY ( Secure background task execution )
                HOW [ +1 : PROCEED ]
                :: < covenant > ( verified )

```

```
            # Subordinate Rolls
            roll_1 [ 100 --> Buf @ 0 ] ( Initial write )
            roll_2 [ Buf[0] = 100 ! [ +1 ] ] ( Integrity verify )
            roll_3 [ commit_status [ PROCEED ] ] ( Tape sealed )
        "#;

        let logger = DiagnosticLogger::new(false);
        let mut tape = Tape::from_source(source, logger).expect("Parsing tape");

        assert_eq!(tape.head.name, "TaskWorker");
        assert_eq!(tape.head.who, "User");
        assert_eq!(tape.head.what, "Worker");
        assert_eq!(tape.head.when_clause, "Opening");
        assert_eq!(tape.head.why, "Secure background task execution");
        assert_eq!(tape.head.required_partition_size, 512);

        assert_eq!(tape.roll_count(), 3);
        assert_eq!(tape.cursor, 0);

        let r1 = tape.active_roll().unwrap();
        assert!(r1.text.contains("100 --> Buf @ 0"));

        tape.advance();
        assert_eq!(tape.cursor, 1);
        let r2 = tape.active_roll().unwrap();
        assert!(r2.text.contains("Buf[0] = 100"));

        tape.advance();
        assert_eq!(tape.cursor, 2);

        tape.advance();
        assert!(tape.is_finished());
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/core/ternary.rs RS 386 LINES 1528 WORDS 14.5 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Module Identity, Balanced Ternary Invariants, and Mathematical Basis )
// ============================================================================
//! OmniCode Core: Balanced Ternary Quad-State Engine
//!
//! Grounded in Balanced Radix-3 logic with a terminal Null/Void state:
//!     T4 = { -1 (Rollback), 0 (Await), +1 (Proceed), NULL (Halt) }
//!
//! Algebraic properties:
//!     - Symmetry: NOT(x) = -x
//!     - Conjunction (:: AND): min(A, B) with NULL absorption
//!     - Disjunction (| OR): max(A, B) with NULL absorption
//!     - Adversative Caveat (! BUT): Action A constrained by Caveat B

use std::fmt;

// Invariant QuadState Constants
pub const ROLLBACK: QuadState = QuadState::Rollback;
pub const AWAIT: QuadState = QuadState::Await;
pub const PROCEED: QuadState = QuadState::Proceed;
pub const HALT: QuadState = QuadState::Halt;


// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Context Declarations, State Enum, and Constructor Initialization )
// ============================================================================
/// The four fundamental ontological states of computation in OmniCode.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum QuadState {
    /// -1: NO / Rollback. Triggers retroactive vector (`<--`), unwinds mutated state.
    Rollback,
    /// 0: OK / Await. Equilibrium, standby, asynchronous yield, pass-through.
    Await,
    /// +1: YES / Proceed. Advances forward vector (`-->`), commits state.
    Proceed,
    /// NULL: VOID / Halt. Bottom type (⊥), boundary trap, terminal exit.
    Halt,
}

/// The cinematic transport kinematics of a reel along a track.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum TransportAction {
    /// Advance the track forward (matches +1, YES, PROCEED)
    Play,
    /// Hold the spindle in equilibrium (matches 0, OK, AWAIT)
    Pause,
    /// Rewind the track back to scene landmark (matches -1, NO, ROLLBACK)
    Rewind,
    /// Emergency brake detent / halt (matches NULL, VOID, HALT)
    Stop,
}

impl TransportAction {
    pub fn to_quad_state(&self) -> QuadState {
        match self {
            TransportAction::Play => QuadState::Proceed,
            TransportAction::Pause => QuadState::Await,
            TransportAction::Rewind => QuadState::Rollback,
            TransportAction::Stop => QuadState::Halt,
        }
    }

    pub fn as_str(&self) -> &'static str {
        match self {
            TransportAction::Play => "PLAY",
            TransportAction::Pause => "PAUSE",
            TransportAction::Rewind => "REWIND",
            TransportAction::Stop => "STOP",
        }
    }
}

```

```rust
impl QuadState {
    /// Parses a raw integer or string representation into a QuadState.
    ///
    /// # Failpoints
    /// Returns `Err` if the value does not belong to {-1, 0, 1, NULL}.
    pub fn from_raw(raw: &str) -> Result<Self, String> {
        match raw.trim().to_uppercase().as_str() {
            "-1" | "NO" | "ROLLBACK" | "REWIND" => Ok(QuadState::Rollback),
            "0" | "OK" | "AWAIT" | "PAUSE" => Ok(QuadState::Await),
            "1" | "+1" | "YES" | "PROCEED" | "PLAY" => Ok(QuadState::Proceed),
            "NULL" | "VOID" | "HALT" | "STOP" => Ok(QuadState::Halt),
            other => Err(format!(
                "FAILPOINT [InvalidQuadState]: '{other}' is not a valid balanced ternary state. \
                 Permitted states: -1, 0, +1, NULL (or PLAY, PAUSE, REWIND, STOP)"
            )),
        }
    }

    /// Transport kinematics level (cinematic reel/track motor):
    /// - Proceed: Play
    /// - Await: Pause
    /// - Rollback: Rewind
    /// - Halt: Stop
    pub fn transport(&self) -> TransportAction {
        match self {
            QuadState::Proceed => TransportAction::Play,
            QuadState::Await => TransportAction::Pause,
            QuadState::Rollback => TransportAction::Rewind,
            QuadState::Halt => TransportAction::Stop,
        }
    }

    /// Macro transport operation string: "PLAY", "PAUSE", "REWIND", "STOP"
    pub fn transport_str(&self) -> &'static str {
        self.transport().as_str()
    }


    /// Returns the integer value, or None for Halt (NULL).
    pub fn as_int(&self) -> Option<i8> {
        match self {
            QuadState::Rollback => Some(-1),
            QuadState::Await => Some(0),
            QuadState::Proceed => Some(1),
            QuadState::Halt => None,
        }
    }

    /// Micro level (linguistic / logical / epistemic stance):
    /// - Proceed: "yes" (1)
    /// - Rollback: "no" (-1)
    /// - Await: "ok" (0)
    /// - Halt: "void" (NULL)
    pub fn micro(&self) -> &'static str {
        match self {
            QuadState::Proceed => "yes",
            QuadState::Rollback => "no",
            QuadState::Await => "ok",
            QuadState::Halt => "void",
        }
    }

    /// Macro level (systems / OS state-machine physics):
    /// - Proceed: "PROCEED" (commit state / advance PC)
    /// - Rollback: "ROLLBACK" (unwind snapshot / retry)
    /// - Await: "AWAIT" (async yield / wait queue)
    /// - Halt: "HALT" (boundary trap / terminal exit)
    pub fn macro_op(&self) -> &'static str {
        match self {
            QuadState::Proceed => "PROCEED",
            QuadState::Rollback => "ROLLBACK",
            QuadState::Await => "AWAIT",
            QuadState::Halt => "HALT",
        }
    }

    /// Bridges the Micro and Macro ontological perspective.
    pub fn description(&self) -> &'static str {
```

```
        match self {
            QuadState::Proceed => "+1 / yes (Micro: Affirmation) | PROCEED (Macro: Forward commit)",
            QuadState::Rollback => "-1 / no (Micro: Refutation) | ROLLBACK (Macro: Retroactive rewind)",
            QuadState::Await => "0 / ok (Micro: Neutral balance) | AWAIT (Macro: Async yield / Standby)",
            QuadState::Halt => "NULL / void (Micro: Absence) | HALT (Macro: Terminal trap / Exit)",
        }
    }
}


// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Core Algebraic Transformations: Inversion, Conjunction, Disjunction, Caveat )
// ============================================================================
impl QuadState {
    /// Algebraic Inversion (`--` NOT).
    ///
    /// Rules:
    /// - `--(+1)` == `-1` (NOT Proceed is Rollback)
    /// - `--(-1)` == `+1` (NOT Rollback is Proceed)
    /// - `--(0)`  ==  `0` (NOT Await is Await - zero is symmetric balance)
    /// - `--(NULL)` == `NULL` (NOT Halt is Halt - void remains void)
    pub fn invert(&self) -> Self {
        match self {
            QuadState::Proceed => QuadState::Rollback,
            QuadState::Rollback => QuadState::Proceed,
            QuadState::Await => QuadState::Await,
            QuadState::Halt => QuadState::Halt,
        }
    }

    /// Cumulative Conjunction (`::` AND).
    ///
    /// Evaluates to minimum with NULL acting as an absorbing trap.
    pub fn and(&self, other: Self) -> Self {
        if *self == QuadState::Halt || other == QuadState::Halt {
            return QuadState::Halt;
        }
        let a = self.as_int().unwrap();
        let b = other.as_int().unwrap();
        match a.min(b) {
            -1 => QuadState::Rollback,
            0 => QuadState::Await,
            1 => QuadState::Proceed,
            _ => unreachable!(),
        }
    }

    /// Disjunction (`|` OR).
    ///
    /// Evaluates to maximum with NULL acting as an absorbing trap.
    pub fn or(&self, other: Self) -> Self {
        if *self == QuadState::Halt || other == QuadState::Halt {
            return QuadState::Halt;
        }
        let a = self.as_int().unwrap();
        let b = other.as_int().unwrap();
        match a.max(b) {
            -1 => QuadState::Rollback,
            0 => QuadState::Await,
            1 => QuadState::Proceed,
            _ => unreachable!(),
        }
    }

    /// Adversative Caveat (`!` BUT).
    ///
    /// `action.but(caveat)`: Action proceeds ONLY if caveat does not veto.
    /// - Caveat = Rollback (-1) -> forces Rollback (-1)
    /// - Caveat = Halt (NULL)   -> forces Halt (NULL)
    /// - Caveat = Await (0)     -> degrades Proceed to Await (0)
    /// - Caveat = Proceed (+1)  -> action executes unhindered
    pub fn but(&self, caveat: Self) -> Self {
        match caveat {
            QuadState::Halt => QuadState::Halt,
            QuadState::Rollback => QuadState::Rollback,
            QuadState::Await => {
                if *self == QuadState::Proceed {
```

```
                    QuadState::Await
                } else {
                    *self
                }
            }
            QuadState::Proceed => *self,
        }
    }

    // ---------------------------------------------------------------------------
    // Dual-Rail Balanced Ternary Substrate & Rail Kinematics
    // ---------------------------------------------------------------------------

    /// Returns the 2-bit dual-rail hardware encoding of this QuadState:
    /// - `00` = 0 / AWAIT (neutral equilibrium)
    /// - `01` = +1 / PROCEED (positive rail asserted)
    /// - `10` = -1 / ROLLBACK (negative rail asserted)
    /// - `11` = NULL / HALT (collision trap / boundary fault)
    pub fn to_dual_rail_code(&self) -> u8 {
        match self {
            QuadState::Await => 0b00,
            QuadState::Proceed => 0b01,
            QuadState::Rollback => 0b10,
            QuadState::Halt => 0b11,
        }
    }

    /// Reconstructs a QuadState from a 2-bit dual-rail encoding.
    pub fn from_dual_rail_code(code: u8) -> Self {
        match code & 0b11 {
            0b00 => QuadState::Await,
            0b01 => QuadState::Proceed,
            0b10 => QuadState::Rollback,
            0b11 => QuadState::Halt,
            _ => unreachable!(),
        }
    }

    /// Returns the dual-rail bit-plane tuple `(pos_rail, neg_rail)`.
    pub fn to_rail_pair(&self) -> (u8, u8) {
        match self {
            QuadState::Await => (0, 0),
            QuadState::Proceed => (1, 0),
            QuadState::Rollback => (0, 1),
            QuadState::Halt => (1, 1),
        }
    }

    /// Reconstructs a QuadState from separate `(pos_rail, neg_rail)` bits.
    pub fn from_rail_pair(pos: u8, neg: u8) -> Self {
        match (pos & 1, neg & 1) {
            (0, 0) => QuadState::Await,
            (1, 0) => QuadState::Proceed,
            (0, 1) => QuadState::Rollback,
            (1, 1) => QuadState::Halt,
            _ => unreachable!(),
        }
    }

    /// SIMD Rail-Swap Negation: swaps the positive and negative rails,
    /// inverting +1 to -1 and -1 to +1 while leaving 0 and NULL invariant.
    pub fn simd_rail_swap(&self) -> Self {
        let (pos, neg) = self.to_rail_pair();
        Self::from_rail_pair(neg, pos)
    }

    /// Returns `true` if this state represents a dual-rail collision trap (NULL).
    pub fn is_collision(&self) -> bool {
        *self == QuadState::Halt
    }
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Verification, Formatter Proofs, Display Formatting, and Export )
// ============================================================================
impl fmt::Display for QuadState {
```

```
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        match self {
            QuadState::Rollback => write!(f, "-1:ROLLBACK"),
            QuadState::Await => write!(f, "0:AWAIT"),
            QuadState::Proceed => write!(f, "+1:PROCEED"),
            QuadState::Halt => write!(f, "NULL:HALT"),
        }
    }
}

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_quad_state_micro_and_macro() {
        // Micro labels (linguistic stance)
        assert_eq!(QuadState::Proceed.micro(), "yes");
        assert_eq!(QuadState::Rollback.micro(), "no");
        assert_eq!(QuadState::Await.micro(), "ok");
        assert_eq!(QuadState::Halt.micro(), "void");

        // Macro labels (systems execution physics)
        assert_eq!(QuadState::Proceed.macro_op(), "PROCEED");
        assert_eq!(QuadState::Rollback.macro_op(), "ROLLBACK");
        assert_eq!(QuadState::Await.macro_op(), "AWAIT");
        assert_eq!(QuadState::Halt.macro_op(), "HALT");

        // Parsing micro and macro strings
        assert_eq!(QuadState::from_raw("yes").unwrap(), QuadState::Proceed);
        assert_eq!(QuadState::from_raw("no").unwrap(), QuadState::Rollback);
        assert_eq!(QuadState::from_raw("ok").unwrap(), QuadState::Await);
        assert_eq!(QuadState::from_raw("void").unwrap(), QuadState::Halt);

        assert_eq!(QuadState::from_raw("PROCEED").unwrap(), QuadState::Proceed);
        assert_eq!(QuadState::from_raw("ROLLBACK").unwrap(), QuadState::Rollback);
        assert_eq!(QuadState::from_raw("AWAIT").unwrap(), QuadState::Await);
        assert_eq!(QuadState::from_raw("HALT").unwrap(), QuadState::Halt);
    }

    #[test]
    fn test_quad_state_dual_rail_and_rail_swap() {
        // Dual-rail encodings: 00=Await, 01=Proceed, 10=Rollback, 11=Halt
        assert_eq!(QuadState::Await.to_dual_rail_code(), 0b00);
        assert_eq!(QuadState::Proceed.to_dual_rail_code(), 0b01);
        assert_eq!(QuadState::Rollback.to_dual_rail_code(), 0b10);
        assert_eq!(QuadState::Halt.to_dual_rail_code(), 0b11);

        assert_eq!(QuadState::from_dual_rail_code(0b00), QuadState::Await);
        assert_eq!(QuadState::from_dual_rail_code(0b01), QuadState::Proceed);
        assert_eq!(QuadState::from_dual_rail_code(0b10), QuadState::Rollback);
        assert_eq!(QuadState::from_dual_rail_code(0b11), QuadState::Halt);

        // Rail pairs (pos, neg)
        assert_eq!(QuadState::Await.to_rail_pair(), (0, 0));
        assert_eq!(QuadState::Proceed.to_rail_pair(), (1, 0));
        assert_eq!(QuadState::Rollback.to_rail_pair(), (0, 1));
        assert_eq!(QuadState::Halt.to_rail_pair(), (1, 1));

        // SIMD rail swap: (pos, neg) -> (neg, pos)
        // Proceed (+1) swaps to Rollback (-1)
        assert_eq!(QuadState::Proceed.simd_rail_swap(), QuadState::Rollback);
        // Rollback (-1) swaps to Proceed (+1)
        assert_eq!(QuadState::Rollback.simd_rail_swap(), QuadState::Proceed);
        // Await (0) swaps to Await (0)
        assert_eq!(QuadState::Await.simd_rail_swap(), QuadState::Await);
        // Halt (NULL) swaps to Halt (NULL)
        assert_eq!(QuadState::Halt.simd_rail_swap(), QuadState::Halt);

        // Collision check
        assert!(!QuadState::Proceed.is_collision());
        assert!(!QuadState::Rollback.is_collision());
        assert!(!QuadState::Await.is_collision());
        assert!(QuadState::Halt.is_collision());
    }
}

```

<TRACK 1> : {Host Engine & Virtual Machine}/src/core/vessel.rs RS 320 LINES 1088 WORDS 11.2 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Vessel Subsystem Identity, Memory Containers & Boundary Invariants )
// ============================================================================
//! OmniCode Core: Memory Vessel & Storehouse Subsystem
//!
//! Codifies the foundational storage nouns of OmniCode:
//!     - Units: Trit, Cell, Word
//!     - Vessels: Vessel, Storehouse, Partition
//!     - Coordinates: Offset, Origin, Landmark
//!     - Measures: Capacity, Count
//!     - Substance: Value, State
//!
//! Governed by Invariant Boundary Physics: An access beyond `Capacity`
//! produces an immediate `-1: ROLLBACK` (Caveat Veto), preserving memory integrity.

use std::fmt;
use crate::core::cell::Cell;
use crate::core::linguistics::{GrammaticalClassification, GrammaticalEntity, PartOfSpeech};
use crate::core::ternary::QuadState;


// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Vessel, Partition, and Coordinate Struct Definitions )
// ============================================================================

/// A bounded container of memory cells.
#[derive(Debug, Clone, PartialEq, Eq)]
pub struct Vessel {
    /// Canonical identifier / name of the vessel.
    pub name: String,
    /// Physical or logical origin address / base coordinate.
    pub origin: usize,
    /// Maximum number of cells this vessel is allocated to hold.
    pub capacity: usize,
    /// Number of cells currently written or active.
    pub count: usize,
    /// Dense cell array (where each cell packs to exactly 1 byte in physical RAM).
    pub cells: Vec<Cell>,
    /// Whether this vessel acts as an ambient system Storehouse.
    pub is_storehouse: bool,
    /// If this vessel is a Partition, references the parent Storehouse name.
    pub parent: Option<String>,
}

/// Coordinate offset within a vessel (`Vessel[Offset]`).
#[derive(Debug, Clone, Copy, PartialEq, Eq, PartialOrd, Ord, Hash)]
pub struct Offset(pub usize);

/// Measurement extent of a vessel's total bounds.
#[derive(Debug, Clone, Copy, PartialEq, Eq, PartialOrd, Ord, Hash)]
pub struct Capacity(pub usize);

/// Measurement count of active cells.
#[derive(Debug, Clone, Copy, PartialEq, Eq, PartialOrd, Ord, Hash)]
pub struct Count(pub usize);


// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Vessel Allocation, Partitioning, Bounds Checking, and Cell Read/Write )
// ============================================================================

impl Vessel {
    /// Allocates a new bounded Vessel with the given capacity.
    /// Initialized with empty equilibrium cells (`AWAIT`).
    pub fn new(name: &str, capacity: usize) -> Self {
        Self {
            name: name.to_string(),
            origin: 0,
            capacity,
            count: 0,
            cells: vec![Cell::equilibrium(); capacity],
```

```
            is_storehouse: false,
            parent: None,
        }
    }

    /// Allocates an ambient system Storehouse.
    pub fn new_storehouse(name: &str, capacity: usize) -> Self {
        let mut v = Self::new(name, capacity);
        v.is_storehouse = true;
        v
    }

    /// Grants an entrusted, bounded Partition from this Storehouse.
    ///
    /// # Invariants
    /// - The partition capacity cannot exceed the remaining unallocated capacity.
    /// - Breaches within the partition are contained and cannot overrun the parent.
    pub fn partition(&mut self, partition_name: &str, partition_capacity: usize) -> Result<Self, String> {
        let available = self.capacity.saturating_sub(self.count);
        if partition_capacity > available {
            return Err(format!(
                "FAILPOINT [StorehouseExhaustion]: Requested partition '{partition_name}' of {partition_capacity} cells, \
                 but Storehouse '{}' only has {available} cells remaining (Capacity: {}, Count: {}).",
                self.name, self.capacity, self.count
            ));
        }

        let partition_origin = self.origin + self.count;
        self.count += partition_capacity;

        Ok(Self {
            name: partition_name.to_string(),
            origin: partition_origin,
            capacity: partition_capacity,
            count: 0,
            cells: vec![Cell::equilibrium(); partition_capacity],
            is_storehouse: false,
            parent: Some(self.name.clone()),
        })
    }

    /// Writes a Cell into this vessel at the specified Offset.
    ///
    /// # Invariant Physics
    /// If `offset >= capacity`, boundary physics triggers an immediate `-1: ROLLBACK`!
    pub fn write(&mut self, offset: usize, value: Cell) -> Result<QuadState, String> {
        if offset >= self.capacity {
            return Ok(QuadState::Rollback);
        }

        self.cells[offset] = value;
        if offset >= self.count {
            self.count = offset + 1;
        }

        Ok(QuadState::Proceed)
    }

    /// Reads a Cell from this vessel at the specified Offset.
    ///
    /// # Invariant Physics
    /// If `offset >= capacity`, returns `Cell::from_state(QuadState::Rollback)`.
    pub fn read(&self, offset: usize) -> Cell {
        if offset >= self.capacity {
            Cell::from_state(QuadState::Rollback)
        } else {
            self.cells[offset]
        }
    }

    /// Packs the entire vessel into a dense array of physical 8-bit bytes (1 byte per cell).
    pub fn pack_bytes(&self) -> Vec<u8> {
        self.cells.iter().map(|c| c.pack()).collect()
    }

    /// Reconstructs a Vessel directly from raw physical bytes (e.g. from RAM, MMIO, or disk).
    pub fn unpack_bytes(name: &str, bytes: &[u8]) -> Self {
```

```
        let cells: Vec<Cell> = bytes.iter().map(|&b| Cell::unpack(b)).collect();
        let capacity = cells.len();
        Self {
            name: name.to_string(),
            origin: 0,
            capacity,
            count: capacity,
            cells,
            is_storehouse: false,
            parent: None,
        }
    }
}

impl GrammaticalEntity for Vessel {
    fn classify(&self) -> GrammaticalClassification {
        let role = if self.is_storehouse {
            "System Storehouse; root reservoir of physical or virtual memory cells"
        } else if self.parent.is_some() {
            "Entrusted Partition; bounded memory slice derived from a storehouse"
        } else {
            "Bounded memory vessel; holds sequential cells under invariant law"
        };

        GrammaticalClassification::new(
            PartOfSpeech::Noun,
            Some(PartOfSpeech::Preposition),
            None,
            role,
            "Contiguous memory block / Buffer / Page frame",
        )
    }
}

impl GrammaticalEntity for Offset {
    fn classify(&self) -> GrammaticalClassification {
        GrammaticalClassification::new(
            PartOfSpeech::Preposition,
            Some(PartOfSpeech::Noun),
            None,
            "Spatial coordinate index within a vessel: Vessel[Offset]",
            "Array index / Memory byte offset",
        )
    }
}

impl GrammaticalEntity for Capacity {
    fn classify(&self) -> GrammaticalClassification {
        GrammaticalClassification::new(
            PartOfSpeech::Noun,
            Some(PartOfSpeech::Adjective),
            None,
            "Total allocated capacity measure of a vessel",
            "Buffer size / Maximum allocation limit",
        )
    }
}

impl GrammaticalEntity for Count {
    fn classify(&self) -> GrammaticalClassification {
        GrammaticalClassification::new(
            PartOfSpeech::Noun,
            Some(PartOfSpeech::Adjective),
            None,
            "Active or written element count within a vessel",
            "Active buffer length / Populated element count",
        )
    }
}

impl fmt::Display for Vessel {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        let kind = if self.is_storehouse {
            "Storehouse"
        } else if self.parent.is_some() {
            "Partition"
        } else {
            "Vessel"
```

```
        };
        write!(
            f,
            "{kind} < {} > [ Capacity: {}, Count: {}, Origin: 0x{:X} ]",
            self.name, self.capacity, self.count, self.origin
        )
    }
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Vessel Invariant Tests, Bounds Safety & Partition Verification )
// ============================================================================
#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_vessel_creation_and_bounds_checking() {
        let mut vessel = Vessel::new("Scratchpad", 10);
        assert_eq!(vessel.capacity, 10);
        assert_eq!(vessel.count, 0);

        // In-bounds write
        let cell42 = Cell::from_natural(42).unwrap();
        let res = vessel.write(0, cell42).unwrap();
        assert_eq!(res, QuadState::Proceed);
        assert_eq!(vessel.count, 1);

        // Read back
        let read_cell = vessel.read(0);
        assert_eq!(read_cell.to_natural(), Some(42));
        assert_eq!(read_cell.state, QuadState::Proceed);

        // Out-of-bounds write -> Automatic ROLLBACK (-1)
        let oob_res = vessel.write(15, cell42).unwrap();
        assert_eq!(oob_res, QuadState::Rollback);

        // Out-of-bounds read -> Automatic ROLLBACK cell
        let oob_read = vessel.read(15);
        assert_eq!(oob_read.state, QuadState::Rollback);
    }

    #[test]
    fn test_storehouse_partitioning() {
        let mut storehouse = Vessel::new_storehouse("Main_RAM", 1024);
        assert!(storehouse.is_storehouse);

        // Partition 256 cells
        let mut partition = storehouse.partition("Process_1_Stack", 256).unwrap();
        assert_eq!(partition.capacity, 256);
        assert_eq!(partition.origin, 0);
        assert_eq!(storehouse.count, 256);

        // Write inside partition
        let val = Cell::from_natural(99).unwrap();
        assert_eq!(partition.write(255, val).unwrap(), QuadState::Proceed);
        assert_eq!(partition.count, 256);

        // Boundary breach inside partition triggers rollback
        assert_eq!(partition.write(256, val).unwrap(), QuadState::Rollback);

        // Storehouse exhaustion
        let err = storehouse.partition("Excessive", 1000);
        assert!(err.is_err());
    }

    #[test]
    fn test_dense_byte_packing_round_trip() {
        let mut vessel = Vessel::new("PackedVessel", 4);
        vessel.write(0, Cell::from_natural(10).unwrap()).unwrap();
        vessel.write(1, Cell::from_natural(20).unwrap()).unwrap();
        vessel.write(2, Cell::from_state(QuadState::Rollback)).unwrap();
        vessel.write(3, Cell::from_state(QuadState::Halt)).unwrap();

        let bytes = vessel.pack_bytes();
        assert_eq!(bytes.len(), 4);
```

```
        assert_eq!(bytes[0], 10);
        assert_eq!(bytes[1], 20);
        assert_eq!(bytes[2], crate::core::cell::BYTE_ROLLBACK);
        assert_eq!(bytes[3], crate::core::cell::BYTE_HALT);

        let reconstructed = Vessel::unpack_bytes("Reconstructed", &bytes);
        assert_eq!(reconstructed.read(0).to_natural(), Some(10));
        assert_eq!(reconstructed.read(1).to_natural(), Some(20));
        assert_eq!(reconstructed.read(2).state, QuadState::Rollback);
        assert_eq!(reconstructed.read(3).state, QuadState::Halt);
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/core/word.rs RS 676 LINES 2608 WORDS 22.6 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Physical Machine Word Architecture: 64-Bit Silicon & 32-Trit OS Substrate )
// ================================================================================
//! OmniCode Core: Physical 64-Bit Machine Word & Logical 32-Trit Vector
//!
//! Bridges physical 64-bit binary silicon hardware with the 32-trit balanced
//! ternary operating system kernel:
//!
//! # Bitfield Layout (64 Physical Bits)
//! - **Bits 0..50 (51 bits):** 32-Trit Balanced Ternary Payload (Range: $3^{32} \approx 1.85 \times 10^{15}$)
//! - **Bits 51..52 (2 bits):** Quad-State / Transport Action (Play, Pause, Rewind, Stop)
//! - **Bit 53 (1 bit):** Polarity Affix (0 = Abstract `+`, 1 = Concrete `-`)
//! - **Bits 54..56 (3 bits):** Boundary Rank Delimiter (`()`, `[]`, `<>`, `{}`)
//! - **Bits 57..63 (7 bits):** Moral Invariant Checksum & Axiom Flags (Truth, Life, Justice, etc.)

use std::fmt;
use crate::core::boundaries::BoundaryType;
use crate::core::operators::Polarity;
use crate::core::ternary::{QuadState, TransportAction};

pub const POWERS_OF_3: [u64; 33] = {
    let mut p = [0u64; 33];
    p[0] = 1;
    let mut i = 1;
    while i <= 32 {
        p[i] = p[i - 1] * 3;
        i += 1;
    }
    p
};

/// Dual-rail bit-plane masks (32 trits x 2 bits = 64 bits native)
pub const BITPLANE_POS_MASK: u64 = 0x5555_5555_5555_5555;
pub const BITPLANE_NEG_MASK: u64 = 0xAAAA_AAAA_AAAA_AAAA;

/// 2-bit dual-rail polar encodings:
/// 00 = 0 (Equilibrium)
/// 01 = +1 (Positive rail)
/// 10 = -1 (Negative rail)
/// 11 = NULL (Collision trap)
pub const TRIT_CODE_ZERO: u8 = 0;
pub const TRIT_CODE_POS: u8 = 1;
pub const TRIT_CODE_NEG: u8 = 2;
pub const TRIT_CODE_NULL: u8 = 3;

/// Kinematic bit-packing topologies across 8-bit byte windows
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum PackMode {
    /// 2-2-2-2: Standard dense storage (4 trits)
    Dense2222,
    /// 2-1-2-1-2: Symmetric resting equilibrium with carry channels
    Kinematic21212,
    /// 1-2-1-2-2: Prefix carry/overflow channel
    Kinematic12122,
    /// 2-2-1-2-1: Postfix carry/overflow channel
    Kinematic22121,
    /// 3-3-2: Directional vector (X:3, Y:3, Z:2)
    Directional332,
    /// 3-2-3: Directional vector (X:3, Y:2, Z:3)
    Directional323,
    /// 2-3-3: Directional vector (X:2, Y:3, Z:3)
    Directional233,
}

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Word32Trit: 32-Trit Balanced Ternary ALU Vector )
// ================================================================================

/// A 32-trit balanced ternary word.
/// Each trit is in `{-1, 0, +1}`.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub struct Word32Trit {
```

```
    pub trits: [i8; 32],
}

impl Default for Word32Trit {
    fn default() -> Self {
        Self::zero()
    }
}

impl Word32Trit {
    /// Creates a zeroed 32-trit word (equilibrium: all 0).
    pub const fn zero() -> Self {
        Self { trits: [0; 32] }
    }

    /// Creates a 32-trit word from an explicit array of trits.
    pub fn new(trits: [i8; 32]) -> Result<Self, String> {
        for (idx, &t) in trits.iter().enumerate() {
            if t < -1 || t > 1 {
                return Err(format!("Invalid trit at index {idx}: {t}. Permitted: -1, 0, 1"));
            }
        }
        Ok(Self { trits })
    }

    /// Converts a signed 64-bit integer into a balanced ternary 32-trit word.
    pub fn from_i64(mut val: i64) -> Self {
        let mut trits = [0i8; 32];
        for i in 0..32 {
            if val == 0 {
                break;
            }
            let rem = ((val % 3) + 3) % 3;
            if rem == 0 {
                trits[i] = 0;
                val /= 3;
            } else if rem == 1 {
                trits[i] = 1;
                val = (val - 1) / 3;
            } else {
                // rem == 2 -> trit is -1, adjust carry (+1)
                trits[i] = -1;
                val = (val + 1) / 3;
            }
        }
        Self { trits }
    }

    /// Decodes the 32-trit word into a standard signed 64-bit integer.
    pub fn to_i64(&self) -> i64 {
        let mut total: i64 = 0;
        let mut power: i64 = 1;
        for i in 0..32 {
            total = total.saturating_add((self.trits[i] as i64).saturating_mul(power));
            if i < 31 {
                power = power.saturating_mul(3);
            }
        }
        total
    }

    /// Negates the 32-trit word in-place with zero sign-extension cost.
    pub fn negate(&self) -> Self {
        let mut trits = [0i8; 32];
        for i in 0..32 {
            trits[i] = -self.trits[i];
        }
        Self { trits }
    }

    /// Balanced ternary full-adder for two 32-trit words.
    pub fn add(&self, other: &Self) -> (Self, i8) {
        let mut trits = [0i8; 32];
        let mut carry: i8 = 0;

        for i in 0..32 {
            let sum = self.trits[i] + other.trits[i] + carry;
            match sum {
```

```
                3 => {
                    trits[i] = 0;
                    carry = 1;
                }
                2 => {
                    trits[i] = -1;
                    carry = 1;
                }
                1 => {
                    trits[i] = 1;
                    carry = 0;
                }
                0 => {
                    trits[i] = 0;
                    carry = 0;
                }
                -1 => {
                    trits[i] = -1;
                    carry = 0;
                }
                -2 => {
                    trits[i] = 1;
                    carry = -1;
                }
                -3 => {
                    trits[i] = 0;
                    carry = -1;
                }
                _ => unreachable!("Sum out of range: {sum}"),
            }
        }
        (Self { trits }, carry)
    }

    /// Packs the 32-trit word into an unsigned 51-bit binary representation.
    pub fn pack_51bits(&self) -> u64 {
        let mut packed: u64 = 0;
        for i in 0..32 {
            let digit = (self.trits[i] + 1) as u64; // Map -1,0,1 to 0,1,2
            packed += digit * POWERS_OF_3[i];
        }
        packed
    }

    /// Unpacks a 32-trit word from an unsigned 51-bit binary representation.
    pub fn unpack_51bits(mut val: u64) -> Self {
        let mut trits = [0i8; 32];
        for i in 0..32 {
            let rem = (val % 3) as i8;
            trits[i] = rem - 1; // Map 0,1,2 back to -1,0,1
            val /= 3;
        }
        Self { trits }
    }

    /// Encodes a single trit into a 2-bit polar pair:
    /// 0 -> 0b00, 1 -> 0b01, -1 -> 0b10, other -> 0b11.
    pub fn trit_to_2bit(trit: i8) -> u8 {
        match trit {
            0 => TRIT_CODE_ZERO,
            1 => TRIT_CODE_POS,
            -1 => TRIT_CODE_NEG,
            _ => TRIT_CODE_NULL,
        }
    }

    /// Decodes a 2-bit polar pair into a balanced trit:
    /// 0b00 -> 0, 0b01 -> +1, 0b10 -> -1, 0b11 -> Err(Collision).
    pub fn two_bit_to_trit(code: u8) -> Result<i8, String> {
        match code & 0x03 {
            TRIT_CODE_ZERO => Ok(0),
            TRIT_CODE_POS => Ok(1),
            TRIT_CODE_NEG => Ok(-1),
            _ => Err("Dual-rail collision trap: code 11 (both rails active)".to_string()),
        }
    }

    /// Packs the 32-trit word into a 64-bit dual-rail polar bit-plane word.
```

```
    pub fn pack_dual_rail(&self) -> u64 {
        let mut packed: u64 = 0;
        for i in 0..32 {
            let code = Self::trit_to_2bit(self.trits[i]) as u64;
            packed |= (code & 0x03) << (i * 2);
        }
        packed
    }

    /// Unpacks a 64-bit dual-rail polar bit-plane word into a 32-trit word.
    /// Trips interlock (Err) if any 2-bit slot has collision code 11.
    pub fn unpack_dual_rail(val: u64) -> Result<Self, String> {
        let mut trits = [0i8; 32];
        for i in 0..32 {
            let code = ((val >> (i * 2)) & 0x03) as u8;
            trits[i] = Self::two_bit_to_trit(code)?;
        }
        Ok(Self { trits })
    }

    /// Checks if a 64-bit dual-rail word has a NULL collision (code 11).
    pub fn has_null_collision(val: u64) -> bool {
        let pos = val & BITPLANE_POS_MASK;
        let neg = (val >> 1) & BITPLANE_POS_MASK;
        (pos & neg) != 0
    }

    /// Negates a 64-bit dual-rail packed word in O(1) via SIMD rail swap.
    pub fn simd_rail_swap_negate(val: u64) -> u64 {
        let pos = val & BITPLANE_POS_MASK;
        let neg = val & BITPLANE_NEG_MASK;
        ((pos << 1) & BITPLANE_NEG_MASK) | ((neg >> 1) & BITPLANE_POS_MASK)
    }

    /// Packs a slice of trits into a single byte using the specified kinematic topology.
    pub fn pack_byte(trits: &[i8], mode: PackMode) -> u8 {
        let get = |idx: usize| -> u8 {
            if idx < trits.len() {
                Self::trit_to_2bit(trits[idx]) & 0x03
            } else {
                0
            }
        };
        let mut b: u8 = 0;
        match mode {
            PackMode::Dense2222 => {
                for i in 0..4 {
                    b |= get(i) << (i * 2);
                }
            }
            PackMode::Kinematic21212 => {
                b |= get(0) & 0x03;
                b |= (get(1) & 0x01) << 2;
                b |= (get(1) & 0x03) << 3;
                b |= ((get(1) >> 1) & 0x01) << 5;
                b |= (get(2) & 0x03) << 6;
            }
            PackMode::Kinematic12122 => {
                b |= (get(0) & 0x01) << 0;
                b |= (get(0) & 0x03) << 1;
                b |= ((get(1) >> 1) & 0x01) << 3;
                b |= (get(1) & 0x03) << 4;
                b |= (get(2) & 0x03) << 6;
            }
            PackMode::Kinematic22121 => {
                b |= (get(0) & 0x03) << 0;
                b |= (get(1) & 0x03) << 2;
                b |= (get(2) & 0x01) << 4;
                b |= (get(2) & 0x03) << 5;
                b |= ((get(2) >> 1) & 0x01) << 7;
            }
            PackMode::Directional332 => {
                b |= get(0) << 0;
                b |= get(1) << 3;
                b |= get(2) << 6;
            }
            PackMode::Directional323 => {
                b |= get(0) << 0;
```

```
                b |= get(1) << 3;
                b |= get(2) << 5;
            }
            PackMode::Directional233 => {
                b |= get(0) << 0;
                b |= get(1) << 2;
                b |= get(2) << 5;
            }
        }
        b
    }

    /// Unpacks a single byte into up to 4 trits using the specified kinematic topology.
    pub fn unpack_byte(b: u8, mode: PackMode) -> Result<[i8; 4], String> {
        let mut out = [0i8; 4];
        match mode {
            PackMode::Dense2222 => {
                for i in 0..4 {
                    out[i] = Self::two_bit_to_trit((b >> (i * 2)) & 0x03)?;
                }
            }
            PackMode::Kinematic21212 => {
                out[0] = Self::two_bit_to_trit(b & 0x03)?;
                out[1] = Self::two_bit_to_trit((b >> 3) & 0x03)?;
                out[2] = Self::two_bit_to_trit((b >> 6) & 0x03)?;
                out[3] = 0;
            }
            PackMode::Kinematic12122 => {
                out[0] = Self::two_bit_to_trit((b >> 1) & 0x03)?;
                out[1] = Self::two_bit_to_trit((b >> 4) & 0x03)?;
                out[2] = Self::two_bit_to_trit((b >> 6) & 0x03)?;
                out[3] = 0;
            }
            PackMode::Kinematic22121 => {
                out[0] = Self::two_bit_to_trit(b & 0x03)?;
                out[1] = Self::two_bit_to_trit((b >> 2) & 0x03)?;
                out[2] = Self::two_bit_to_trit((b >> 5) & 0x03)?;
                out[3] = 0;
            }
            PackMode::Directional332 => {
                out[0] = Self::two_bit_to_trit(b & 0x03)?;
                out[1] = Self::two_bit_to_trit((b >> 3) & 0x03)?;
                out[2] = Self::two_bit_to_trit((b >> 6) & 0x03)?;
                out[3] = 0;
            }
            PackMode::Directional323 => {
                out[0] = Self::two_bit_to_trit(b & 0x03)?;
                out[1] = Self::two_bit_to_trit((b >> 3) & 0x03)?;
                out[2] = Self::two_bit_to_trit((b >> 5) & 0x03)?;
                out[3] = 0;
            }
            PackMode::Directional233 => {
                out[0] = Self::two_bit_to_trit(b & 0x03)?;
                out[1] = Self::two_bit_to_trit((b >> 2) & 0x03)?;
                out[2] = Self::two_bit_to_trit((b >> 5) & 0x03)?;
                out[3] = 0;
            }
        }
        Ok(out)
    }
}

impl fmt::Display for Word32Trit {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        write!(f, "0t")?;
        for i in (0..32).rev() {
            match self.trits[i] {
                1 => write!(f, "+")?,
                0 => write!(f, "0")?,
                -1 => write!(f, "-")?,
                _ => write!(f, "?")?,
            }
        }
        write!(f, " ({})", self.to_i64())
    }
}
```

```rust
// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Word64: 64-Bit Physical Silicon Word Container )
// ============================================================================

/// A 64-bit physical silicon machine word combining a 32-trit payload
/// with out-of-band operational metadata.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub struct Word64 {
    pub raw: u64,
}

impl Default for Word64 {
    fn default() -> Self {
        Self::new(Word32Trit::zero(), QuadState::Proceed, Polarity::Concrete, BoundaryType::Denotation, 0)
    }
}

impl Word64 {
    const PAYLOAD_MASK: u64   = 0x0007_FFFF_FFFF_FFFF; // Bits 0..50 (51 bits)
    const STATE_SHIFT: u32    = 51;
    const STATE_MASK: u64     = 0x3;                   // Bits 51..52 (2 bits)
    const POLARITY_SHIFT: u32 = 53;
    const POLARITY_MASK: u64  = 0x1;                   // Bit 53 (1 bit)
    const BOUNDARY_SHIFT: u32 = 54;
    const BOUNDARY_MASK: u64  = 0x7;                   // Bits 54..56 (3 bits)
    const CHECKSUM_SHIFT: u32 = 57;
    const CHECKSUM_MASK: u64  = 0x7F;                  // Bits 57..63 (7 bits)

    /// Constructs a physical 64-bit word from components.
    pub fn new(
        payload: Word32Trit,
        state: QuadState,
        polarity: Polarity,
        boundary: BoundaryType,
        checksum: u8,
    ) -> Self {
        let p_val = payload.pack_51bits() & Self::PAYLOAD_MASK;
        let s_val = match state {
            QuadState::Await => 0u64,
            QuadState::Proceed => 1u64,
            QuadState::Rollback => 2u64,
            QuadState::Halt => 3u64,
        };
        let pol_val = match polarity {
            Polarity::Abstract => 0u64,
            Polarity::Concrete => 1u64,
        };
        let b_val = match boundary {
            BoundaryType::Invariant => 0u64,
            BoundaryType::Denotation => 1u64,
            BoundaryType::Connotation => 2u64,
            BoundaryType::BottomUp => 3u64,
            BoundaryType::TopDown => 4u64,
            BoundaryType::Aside => 5u64,
        };
        let c_val = (checksum as u64) & Self::CHECKSUM_MASK;

        let raw = p_val
            | (s_val << Self::STATE_SHIFT)
            | (pol_val << Self::POLARITY_SHIFT)
            | (b_val << Self::BOUNDARY_SHIFT)
            | (c_val << Self::CHECKSUM_SHIFT);

        Self { raw }
    }

    /// Returns a zeroed physical 64-bit word with equilibrium payload and Proceed/PLAY transport.
    pub fn zero() -> Self {
        Self::from_signed_int(0)
    }

    /// Convenience constructor from a signed integer value with default Proceed/PLAY transport.
    pub fn from_signed_int(val: i64) -> Self {
        Self::new(
            Word32Trit::from_i64(val),
            QuadState::Proceed,
            Polarity::Concrete,
```

```
            BoundaryType::Denotation,
            0,
        )
    }

    /// Convenience constructor from a 32-trit word with default Proceed/PLAY transport.
    pub fn from_trit_payload(payload: Word32Trit) -> Self {
        Self::new(
            payload,
            QuadState::Proceed,
            Polarity::Concrete,
            BoundaryType::Denotation,
            0,
        )
    }

    /// Extracts the 32-trit payload.
    pub fn payload(&self) -> Word32Trit {
        let p_bits = self.raw & Self::PAYLOAD_MASK;
        Word32Trit::unpack_51bits(p_bits)
    }

    /// Extracts the QuadState / Transport Action.
    pub fn state(&self) -> QuadState {
        let s_bits = (self.raw >> Self::STATE_SHIFT) & Self::STATE_MASK;
        match s_bits {
            0 => QuadState::Await,
            1 => QuadState::Proceed,
            2 => QuadState::Rollback,
            _ => QuadState::Halt,
        }
    }

    /// Returns the cinematic transport action: Play, Pause, Rewind, Stop.
    pub fn transport(&self) -> TransportAction {
        self.state().transport()
    }

    /// Extracts the Polarity affix.
    pub fn polarity(&self) -> Polarity {
        let p_bit = (self.raw >> Self::POLARITY_SHIFT) & Self::POLARITY_MASK;
        if p_bit == 0 {
            Polarity::Abstract
        } else {
            Polarity::Concrete
        }
    }

    /// Extracts the Boundary Type.
    pub fn boundary(&self) -> BoundaryType {
        let b_bits = (self.raw >> Self::BOUNDARY_SHIFT) & Self::BOUNDARY_MASK;
        match b_bits {
            0 => BoundaryType::Invariant,
            1 => BoundaryType::Denotation,
            2 => BoundaryType::Connotation,
            3 => BoundaryType::BottomUp,
            4 => BoundaryType::TopDown,
            _ => BoundaryType::Aside,
        }
    }

    /// Extracts the moral invariant checksum byte.
    pub fn checksum(&self) -> u8 {
        ((self.raw >> Self::CHECKSUM_SHIFT) & Self::CHECKSUM_MASK) as u8
    }

    /// Formats a complete human-readable physical register inspection string.
    pub fn inspect(&self) -> String {
        format!(
            "0x{:016X} | {} | State: {:<8} (Transport: {:<6}) | Polarity: {} | Bound: {}",
            self.raw,
            self.payload(),
            self.state().macro_op(),
            self.transport().as_str(),
            self.polarity().symbol(),
            self.boundary().delimiters().0
        )
    }
```

```
}



// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Verification Proof )
// ============================================================================
#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_word32_trit_integer_conversion_round_trip() {
        let test_cases = [0, 1, -1, 4, -4, 42, -42, 243, -243, 100_000, -100_000, 1_000_000_000, -1_000_000_000];
        for &val in &test_cases {
            let w = Word32Trit::from_i64(val);
            let back = w.to_i64();
            assert_eq!(val, back, "Round trip failed for value {val}");
        }
    }

    #[test]
    fn test_word32_trit_pack_unpack_round_trip() {
        let values = [0, 1, -1, 12345, -54321, 999_999_999, -999_999_999];
        for &v in &values {
            let w = Word32Trit::from_i64(v);
            let packed = w.pack_51bits();
            let unpacked = Word32Trit::unpack_51bits(packed);
            assert_eq!(w, unpacked, "Pack/unpack mismatch for value {v}");
            assert_eq!(v, unpacked.to_i64());
        }
    }

    #[test]
    fn test_word32_trit_balanced_addition() {
        let a = Word32Trit::from_i64(42);
        let b = Word32Trit::from_i64(58);
        let (sum, carry) = a.add(&b);
        assert_eq!(carry, 0);
        assert_eq!(sum.to_i64(), 100);

        let c = Word32Trit::from_i64(15);
        let d = Word32Trit::from_i64(-25);
        let (sum2, carry2) = c.add(&d);
        assert_eq!(carry2, 0);
        assert_eq!(sum2.to_i64(), -10);
    }

    #[test]
    fn test_word64_physical_container_round_trip() {
        let payload = Word32Trit::from_i64(1337);
        let w64 = Word64::new(payload, QuadState::Proceed, Polarity::Concrete, BoundaryType::Denotation, 42);

        assert_eq!(w64.payload().to_i64(), 1337);
        assert_eq!(w64.state(), QuadState::Proceed);
        assert_eq!(w64.transport(), TransportAction::Play);
        assert_eq!(w64.polarity(), Polarity::Concrete);
        assert_eq!(w64.boundary(), BoundaryType::Denotation);
        assert_eq!(w64.checksum(), 42);
    }

    #[test]
    fn test_word32_dual_rail_bitplanes() {
        assert_eq!(Word32Trit::trit_to_2bit(0), TRIT_CODE_ZERO);
        assert_eq!(Word32Trit::trit_to_2bit(1), TRIT_CODE_POS);
        assert_eq!(Word32Trit::trit_to_2bit(-1), TRIT_CODE_NEG);

        assert_eq!(Word32Trit::two_bit_to_trit(0).unwrap(), 0);
        assert_eq!(Word32Trit::two_bit_to_trit(1).unwrap(), 1);
        assert_eq!(Word32Trit::two_bit_to_trit(2).unwrap(), -1);
        assert!(Word32Trit::two_bit_to_trit(3).is_err());

        let values = [0, 1, -1, 4096, -4096, 65536, -65536, 123456789, -123456789];
        for &v in &values {
            let w = Word32Trit::from_i64(v);
            let packed = w.pack_dual_rail();
            assert!(!Word32Trit::has_null_collision(packed));
```

```
            let unpacked = Word32Trit::unpack_dual_rail(packed).expect("Unpack dual rail");
            assert_eq!(w, unpacked, "Dual-rail mismatch for {v}");
            assert_eq!(v, unpacked.to_i64());
        }
    }

    #[test]
    fn test_word32_simd_rail_swap_negation() {
        let w = Word32Trit::from_i64(4096);
        let packed = w.pack_dual_rail();
        let negated_packed = Word32Trit::simd_rail_swap_negate(packed);
        let unpacked_neg = Word32Trit::unpack_dual_rail(negated_packed).expect("Unpack negated");
        assert_eq!(unpacked_neg.to_i64(), -4096);

        // Involution: -(-x) == x
        let double_neg = Word32Trit::simd_rail_swap_negate(negated_packed);
        assert_eq!(double_neg, packed);
    }

    #[test]
    fn test_word32_null_collision_trap() {
        let w = Word32Trit::from_i64(1);
        let mut packed = w.pack_dual_rail();
        assert!(!Word32Trit::has_null_collision(packed));

        // Inject 11 into slot 0
        packed |= 3;
        assert!(Word32Trit::has_null_collision(packed));
        assert!(Word32Trit::unpack_dual_rail(packed).is_err());
    }

    #[test]
    fn test_word32_dynamic_packing_topologies() {
        let modes = [
            PackMode::Dense2222,
            PackMode::Kinematic21212,
            PackMode::Kinematic12122,
            PackMode::Kinematic22121,
            PackMode::Directional332,
            PackMode::Directional323,
            PackMode::Directional233,
        ];
        let trits = [1, -1, 1, -1];
        for &mode in &modes {
            let byte_val = Word32Trit::pack_byte(&trits, mode);
            let unpacked = Word32Trit::unpack_byte(byte_val, mode).expect("Unpack byte");
            assert_eq!(unpacked[0], trits[0]);
            assert_eq!(unpacked[1], trits[1]);
            assert_eq!(unpacked[2], trits[2]);
            if mode == PackMode::Dense2222 {
                assert_eq!(unpacked[3], trits[3]);
            }
        }
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/lexicon/domain.rs RS 38 LINES 166 WORDS 1.5 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Categorical Domains of Reality & Biblical World Ontology )
// ============================================================================
//! # Lexicon Domains (`domain.rs`)
//!
//! Categorical domains covering the biblical ontology of reality.

/// Categorical domains covering the biblical ontology of reality.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum LexiconDomain {
    /// The physical cosmos: light, darkness, heavens, earth, seas, time.
    Cosmology,
    /// Biological and ecological creation: seeds, trees, fruit, flocks.
    LivingWorld,
    /// Human anthropology: identity, heart, soul, conscience, society.
    HumanCondition,
    /// Righteous character traits: truth, justice, mercy, humility, wisdom.
    MoralVirtue,
    /// Fallen behaviors: pride, deceit, theft, murder, wrath.
    MoralVice,
    /// Universal causal principles: sowing and reaping, measure for measure.
    CausalLaw,
}

impl LexiconDomain {
    pub fn as_str(&self) -> &'static str {
        match self {
            Self::Cosmology => "Cosmology & Creation",
            Self::LivingWorld => "Living World & Stewardship",
            Self::HumanCondition => "Human Condition & Society",
            Self::MoralVirtue => "Moral Virtues & Righteousness",
            Self::MoralVice => "Moral Vices & Warnings",
            Self::CausalLaw => "Causal Laws & Invariants",
        }
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/mod.rs RS 37 LINES 122 WORDS 1.5 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Runtime Subsystem Identity & Component Re-exports )
// ================================================================================
//! OmniCode Runtime Subsystem
//! Combines Transactional Environment with Quad-State Evaluator.

pub mod environment;
pub mod evaluator;
pub mod assembler;


// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Runtime Access )
// ================================================================================
pub use environment::{Environment, RuntimeValue, RegisterBank, CallFrame};
pub use evaluator::Evaluator;
pub use assembler::{
    OmniAssembler, AssembledTape, PhysicalSymbol, AssembledInstruction,
    MachineOp, MachineRegister, transpile_tape_to_omni, transpile_omni_to_tape,
};


// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Runtime Execution Framework )
// ================================================================================
// Runtime environment and evaluator are orchestrated during execution.


// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Verification & Subsystem Status )
// ================================================================================
// Runtime subsystem verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/debugger.rs RS 471 LINES 1835 WORDS 20.2 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( OmniDebugger Identity, Invariant Verification Engine & Safety Constraints )
// ================================================================================
//! OmniCode Diagnostics: Debugger & Invariant Inspector
//!
//! # Purpose & Cybernetic Architecture
//! Acts as the runtime invariant enforcement organ and rollback controller:
//! - **Boundary Physics**: Manages the active delimiter stack, trapping leaks and mismatches.
//! - **Immutability Protection**: Enforces Rank 1 axiom protection `< ... >` against illegal mutation.
//! - **Retroaction Bounding**: Prevents infinite rollback loops via threshold counters.
//! - **Self-Healing Test Oracles**: Connects candidate restorations directly to test verification
//!   harnesses, certifying patches before committing state (+1:PROCEED).
//!
//! # IDE Hover & AI Agent Context
//! When hovering over [`OmniDebugger`] or its methods in an IDE:
//! - Hovering over [`OmniDebugger::execute_verification_test`] explains how verification sandboxes work.
//! - Hovering over [`OmniDebugger::execute_restoration_from_log`] details log-driven surgical patching.
//! - Hovering over [`OmniDebugger::pop_boundary`] shows delimiter matching and remediation synthesis.

use std::collections::{HashMap, HashSet};
use crate::core::boundaries::BoundaryType;
use crate::core::ternary::QuadState;
use crate::diagnostics::logger::{DiagnosticLogger, FailpointType, FixKind, FixSuggestion, LogEvent};


// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( BoundaryFrame Definition and OmniDebugger Context Setup )
// ================================================================================
/// Stack frame recording an unclosed boundary delimiter's opening context.
#[derive(Debug, Clone)]
pub struct BoundaryFrame {
    /// The opening delimiter character: `<`, `[`, `{`, or `(`.
    pub open_char: char,
    /// 1-based source line where the boundary opened.
    pub line: usize,
    /// 1-based source column where the delimiter occurred.
    pub col: usize,
}

/// Runtime invariant inspector, boundary stack tracker, and test verification oracle.
#[derive(Debug, Clone)]
pub struct OmniDebugger {
    /// Shared diagnostic logger for emitting debug events, failpoints, and cognitive traces.
    pub logger: DiagnosticLogger,
    /// Active LIFO stack of unclosed boundary frames.
    pub boundary_stack: Vec<BoundaryFrame>,
    /// Set of entity names declared inside `< ... >` sealed against mutation.
    pub immutable_registry: HashSet<String>,
    /// Execution rollback counters keyed by target label to detect infinite retroaction loops.
    pub retroaction_counters: HashMap<String, usize>,
    /// Staged queue of automated remediation suggestions awaiting application by the Restorator.
    pub remediation_queue: Vec<FixSuggestion>,
    /// Maximum permitted rollback operations per target before triggering cyclic retroaction failure.
    pub max_retroaction_depth: usize,
    /// Total operational steps and state evaluations inspected by this debugger.
    pub step_count: usize,
}

impl OmniDebugger {
    /// Constructs a new [`OmniDebugger`].
    ///
    /// # Arguments
    /// * `logger` - The shared [`DiagnosticLogger`] instance for telemetry recording.
    /// * `max_retroaction_depth` - Threshold ceiling for retroactions before trapping cyclic loops.
    pub fn new(logger: DiagnosticLogger, max_retroaction_depth: usize) -> Self {
        Self {
            logger,
            boundary_stack: Vec::new(),
            immutable_registry: HashSet::new(),
            retroaction_counters: HashMap::new(),
            remediation_queue: Vec::new(),
            max_retroaction_depth,
```

```
            step_count: 0,
        }
    }
}


// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Core Invariant Enforcement: Boundary Push/Pop, Immutability, Retroaction )
// ============================================================================
impl OmniDebugger {
    /// Pushes an opening boundary delimiter onto the active stack.
    ///
    /// # Arguments
    /// * `open` - Delimiter character (`<`, `[`, `{`, `(`).
    /// * `line` - 1-based line number.
    /// * `col` - 1-based column number.
    pub fn push_boundary(&mut self, open: char, line: usize, col: usize) {
        self.logger.log(
            "BOUNDARY",
            format!("Pushing delimiter '{open}' at L{line}:C{col} (depth: {})", self.boundary_stack.len() + 1),
        );
        self.boundary_stack.push(BoundaryFrame { open_char: open, line, col });
    }

    /// Pops a closing boundary delimiter and validates the pair against the stack top.
    ///
    /// # Failpoints Intercepted
    /// - **Empty Stack**: Traps unmatched closing delimiter as [`FailpointType::BoundaryMismatch`].
    /// - **Mismatched Delimiter**: Traps illegal pair crossing (e.g. `< ... ]`), logs a
    ///   [`FixSuggestion`] pointing to the correct partner, and queues remediation.
    ///
    /// # Returns
    /// `Ok(BoundaryType)` on valid resolution, or `Err(String)` on failpoint mismatch.
    pub fn pop_boundary(&mut self, close: char, line: usize, col: usize) -> Result<BoundaryType, String> {
        if self.boundary_stack.is_empty() {
            let msg = format!("Unmatched closing delimiter '{close}' at L{line}:C{col} (stack is empty)");
            self.logger.failpoint(FailpointType::BoundaryMismatch, "DEBUGGER", &msg);
            return Err(format!("FAILPOINT: {msg}"));
        }

        let frame = self.boundary_stack.pop().unwrap();
        match BoundaryType::from_delimiters(frame.open_char, close) {
            Ok(btype) => {
                self.logger.log(
                    "BOUNDARY",
                    format!(
                        "Successfully resolved boundary {} '{}{}' (remaining depth: {})",
                        btype, frame.open_char, close, self.boundary_stack.len()
                    ),
                );
                Ok(btype)
            }
            Err(err) => {
                let msg = format!(
                    "Boundary mismatch: opened with '{}' (L{}:C{}) but closed with '{}' at L{}:C{}",
                    frame.open_char, frame.line, frame.col, close, line, col
                );
                let matching = match frame.open_char {
                    '<' => '>',
                    '[' => ']',
                    '{' => '}',
                    _ => ')',
                };
                let suggestion = FixSuggestion {
                    kind: FixKind::FixBoundaryMismatch,
                    line,
                    col,
                    target_token: close.to_string(),
                    suggested_patch: matching.to_string(),
                    rationale: format!(
                        "Replace mismatched closing delimiter '{close}' with matching '{matching}' to seal boundary
opened with '{}' at L{}:C{}",
                        frame.open_char, frame.line, frame.col
                    ),
                };
                self.logger.failpoint_with_remediation(
                    FailpointType::BoundaryMismatch,
```

```
                    "DEBUGGER",
                    &msg,
                    suggestion.clone(),
                );
                self.remediation_queue.push(suggestion);
                Err(err)
            }
        }
    }

    /// Asserts that no boundaries remain unclosed at EOF.
    ///
    /// If unclosed delimiters remain on the stack, logs [`FailpointType::BoundaryLeak`]
    /// with a concrete [`FixSuggestion`] indicating the required closing tokens.
    pub fn assert_all_boundaries_closed(&mut self) -> Result<(), String> {
        if let Some(frame) = self.boundary_stack.last() {
            let msg = format!(
                "Boundary leak: delimiter '{}' opened at L{}:C{} was never closed",
                frame.open_char, frame.line, frame.col
            );
            let matching = match frame.open_char {
                '<' => '>',
                '[' => ']',
                '{' => '}',
                _ => ')',
            };
            let suggestion = FixSuggestion {
                kind: FixKind::CloseBoundary,
                line: frame.line,
                col: frame.col,
                target_token: frame.open_char.to_string(),
                suggested_patch: format!("\n{matching}"),
                rationale: format!(
                    "Append missing closing delimiter '{matching}' for boundary opened with '{}' at L{}:C{}",
                    frame.open_char, frame.line, frame.col
                ),
            };
            self.logger.failpoint_with_remediation(
                FailpointType::BoundaryLeak,
                "DEBUGGER",
                &msg,
                suggestion.clone(),
            );
            self.remediation_queue.push(suggestion);
            return Err(format!("FAILPOINT: {msg}"));
        }
        Ok(())
    }

    /// Registers an entity identifier defined inside `< ... >` as globally immutable Rank 1 axiom.
    pub fn register_immutable(&mut self, name: &str) {
        self.immutable_registry.insert(name.to_string());
        self.logger.log("IMMUTABILITY", format!("Registered invariant <{name}>"));
    }

    /// Verifies that mutation is permitted for the given entity identifier.
    ///
    /// # Failpoints Intercepted
    /// If the entity was registered as immutable, traps [`FailpointType::ImmutableMutation`],
    /// and suggests converting the declaration to a mutable Rank 2 denotation `[ ... ]`.
    pub fn assert_mutation_permitted(&mut self, name: &str) -> Result<(), String> {
        if self.immutable_registry.contains(name) {
            let msg = format!(
                "Illegal mutation attempted on immutable invariant <{name}>! Entity cannot be changed."
            );
            let suggestion = FixSuggestion {
                kind: FixKind::ConvertImmutableToMutable,
                line: 0,
                col: 0,
                target_token: name.to_string(),
                suggested_patch: format!("[ {name} ]"),
                rationale: format!(
                    "Entity <{name}> was sealed as a Rank 1 immutable invariant; declare it with '[ {name} ]' if updates
are required"
                ),
            };
            self.logger.failpoint_with_remediation(
                FailpointType::ImmutableMutation,
```

```
                "DEBUGGER",
                &msg,
                suggestion.clone(),
            );
            self.remediation_queue.push(suggestion);
            return Err(format!("FAILPOINT: {msg}"));
        }
        Ok(())
    }

    /// Retrieves and empties the active remediation queue.
    pub fn drain_remediations(&mut self) -> Vec<FixSuggestion> {
        std::mem::take(&mut self.remediation_queue)
    }

    /// Monitors retroaction steps on a named target to prevent infinite rollback loops.
    ///
    /// # Failpoints Intercepted
    /// If rollback iterations exceed `max_retroaction_depth`, traps [`FailpointType::CyclicRetroaction`].
    pub fn track_retroaction(&mut self, target: &str) -> Result<usize, String> {
        let count = self.retroaction_counters.entry(target.to_string()).or_insert(0);
        *count += 1;
        let cur = *count;

        self.logger.log(
            "VECTOR",
            format!("Retroaction step #{cur} on '{target}'"),
        );

        if cur > self.max_retroaction_depth {
            let msg = format!(
                "Cyclic retroaction loop detected! Target '{target}' rolled back {cur} times, \
                 exceeding threshold ({})",
                self.max_retroaction_depth
            );
            self.logger.failpoint(FailpointType::CyclicRetroaction, "DEBUGGER", &msg);
            return Err(format!("FAILPOINT: {msg}"));
        }

        Ok(cur)
    }

    /// Inspects QuadState and raises appropriate signals or failpoints.
    ///
    /// - `QuadState::Halt`: Traps void / NULL halt trap (`FP_NULL_TRAP`).
    /// - `QuadState::Rollback`: Traps rollback trigger (`FP_ROLLBACK_TRIGGERED`).
    /// - `QuadState::Await`: Standby state logged.
    /// - `QuadState::Proceed`: Commit state logged.
    pub fn inspect_state(&mut self, state: QuadState, context: &str) {
        self.step_count += 1;
        match state {
            QuadState::Halt => {
                self.logger.failpoint(
                    FailpointType::NullTrap,
                    "DEBUGGER",
                    format!("NULL / Void halt trap encountered in context: {context}"),
                );
            }
            QuadState::Rollback => {
                self.logger.failpoint(
                    FailpointType::RollbackTriggered,
                    "DEBUGGER",
                    format!("Rollback (-1) triggered in context: {context}"),
                );
            }
            QuadState::Await => {
                self.logger.log("TERNARY", format!("Await (0) standby in context: {context}"));
            }
            QuadState::Proceed => {
                self.logger.log("TERNARY", format!("Proceed (+1) committed in context: {context}"));
            }
        }
    }

    /// Executes a verification test against an isolated child debugger context.
    ///
    /// # Why Test Oracles Matter for Self-Healing
    /// Acts as an execution oracle for hypothesis verification before state commit.
```

```rust
    /// The debugger executes the candidate logic in a sandbox:
    /// - If the test passes: records an `ORACLE_SUCCESS` observation for AI memory.
    /// - If the test fails: traps a rollback failpoint and logs `ORACLE_FAILURE`.
    ///
    /// # Arguments
    /// * `test_name` - Human and AI readable identifier for the verification assertion.
    /// * `test_runner` - Closure executing the test logic against a sandboxed child debugger.
    pub fn execute_verification_test<F>(&mut self, test_name: &str, test_runner: F) -> Result<(), String>
    where
        F: FnOnce(&mut OmniDebugger) -> Result<(), String>,
    {
        self.logger.log("TEST_ORACLE", format!("Spawning verification test: {test_name}"));
        let mut test_debugger = OmniDebugger::new(self.logger.clone(), self.max_retroaction_depth);
        match test_runner(&mut test_debugger) {
            Ok(()) => {
                self.logger.log("TEST_ORACLE", format!("Verification test '{test_name}' passed (+1:PROCEED)"));
                self.logger.record_ai_observation(
                    "ORACLE_SUCCESS",
                    &format!("Test '{test_name}' passed"),
                    "Candidate state passed invariant verification without failpoints",
                    ["test_oracle", "verified", "proceed"].as_slice(),
                    Some(test_name),
                );
                Ok(())
            }
            Err(err) => {
                self.logger.failpoint(
                    FailpointType::RollbackTriggered,
                    "TEST_ORACLE",
                    format!("Verification test '{test_name}' failed: {err}"),
                );
                self.logger.record_ai_observation(
                    "ORACLE_FAILURE",
                    &format!("Test '{test_name}' rejected candidate"),
                    &err,
                    ["test_oracle", "rejected", "rollback"].as_slice(),
                    Some(test_name),
                );
                Err(err)
            }
        }
    }

    /// Verifies candidate source code with a provided test oracle function.
    ///
    /// # Arguments
    /// * `candidate_source` - The restored source string under evaluation.
    /// * `test_oracle` - Test function verifying candidate execution invariants.
    ///
    /// # Returns
    /// - `Ok(String)`: If the oracle passes, returns the confirmed candidate source.
    /// - `Err(String)`: If the oracle fails, triggers a state rollback (`-1:ROLLBACK`) and returns the error.
    pub fn verify_candidate_repair<F>(
        &mut self,
        candidate_source: &str,
        test_oracle: F,
    ) -> Result<String, String>
    where
        F: Fn(&str) -> Result<(), String>,
    {
        self.logger.log("SELF_HEAL", "Verifying candidate repair via test oracle...");
        match test_oracle(candidate_source) {
            Ok(()) => {
                self.logger.log("SELF_HEAL", "Candidate repair verified (+1:PROCEED)!");
                self.inspect_state(QuadState::Proceed, "candidate_repair_verified");
                self.logger.record_ai_observation(
                    "REPAIR_VERIFIED",
                    "Candidate source passed verification oracle",
                    "The proposed restorative patch executed cleanly without failpoints",
                    ["self_healing", "oracle_passed", "verified"].as_slice(),
                    None,
                );
                Ok(candidate_source.to_string())
            }
            Err(e) => {
                self.inspect_state(QuadState::Rollback, "candidate_repair_rejected");
                let msg = format!("Candidate repair failed test verification: {e}");
                self.logger.failpoint(FailpointType::RollbackTriggered, "SELF_HEAL", &msg);
```

```
                self.logger.record_ai_observation(
                    "REPAIR_REJECTED",
                    "Candidate source failed verification oracle",
                    &msg,
                    ["self_healing", "oracle_failed", "rollback"].as_slice(),
                    None,
                );
                Err(msg)
            }
        }
    }

    /// Ingests a structured [`LogEvent`] containing a [`FixSuggestion`], applies the patch,
    /// and invokes the verification oracle before committing the restored code.
    ///
    /// # Arguments
    /// * `source` - The original broken source code.
    /// * `log_event` - The structured incident log emitted by the [`DiagnosticLogger`].
    /// * `test_oracle` - The verification test oracle closure.
    ///
    /// # Returns
    /// `Ok(healed_source)` if the patch was applied and certified by the oracle.
    pub fn execute_restoration_from_log<F>(
        &mut self,
        source: &str,
        log_event: &LogEvent,
        test_oracle: F,
    ) -> Result<String, String>
    where
        F: Fn(&str) -> Result<(), String>,
    {
        let suggestion = log_event.suggestion.as_ref().ok_or_else(|| {
            "LogEvent does not contain remediation suggestion for automated restoration".to_string()
        })?;

        self.logger.log(
            "SELF_HEAL",
            format!("Applying remediation suggestion from log: {:?}", suggestion.kind),
        );

        let mut candidate = source.to_string();
        match suggestion.kind {
            FixKind::FixBoundaryMismatch => {
                let lines: Vec<&str> = candidate.lines().collect();
                if suggestion.line > 0 && suggestion.line <= lines.len() {
                    let mut target_line = lines[suggestion.line - 1].to_string();
                    if let Some(pos) = target_line.find(&suggestion.target_token) {
                        target_line.replace_range(pos..pos + suggestion.target_token.len(), &suggestion.suggested_patch);
                        let mut new_lines = lines.clone();
                        new_lines[suggestion.line - 1] = &target_line;
                        candidate = new_lines.join("\n");
                        if !candidate.ends_with('\n') {
                            candidate.push('\n');
                        }
                    }
                }
            }
            FixKind::CloseBoundary => {
                candidate.push_str(&suggestion.suggested_patch);
                if !candidate.ends_with('\n') {
                    candidate.push('\n');
                }
            }
            FixKind::ConvertImmutableToMutable => {
                candidate = candidate.replace(
                    &format!("< {} >", suggestion.target_token),
                    &suggestion.suggested_patch,
                );
            }
            _ => {
                candidate = candidate.replace(&suggestion.target_token, &suggestion.suggested_patch);
            }
        }

        // Call the test oracle to certify candidate
        self.verify_candidate_repair(&candidate, test_oracle)
    }
}
```

```
463
464
465 // ================================================================================
466 // BLOCK 4: CLOSING BLOCK
467 // ( Postcondition Verification and Debugger Status )
468 // ================================================================================
469 // OmniDebugger safety invariants verified and closed.
470
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/mod.rs RS 54 LINES 264 WORDS 2.6 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Diagnostics Subsystem Identity, Module Architecture & Exports )
// ================================================================================
//! OmniCode Diagnostics Subsystem
//!
//! # Architecture & Cognitive Cybernetics
//! Coordinates the runtime sensory, debugging, and self-healing immune organs:
//! - [`logger`]: Structured failpoint interceptor, telemetry logger, and AI episodic memory emitter ([`CognitiveNote`]).
//! - [`debugger`]: Boundary stack monitor, immutability inspector, retroaction depth guard, and test verification oracle.
//! - [`linter`]: Structural validator enforcing the canonical 4-Block architecture across compilation units.
//! - [`restorator`]: Autonomous multi-pass code healing engine with test-oracle certification.
//!
//! # IDE Hover Support
//! All diagnostic components are re-exported at the module root for immediate autocompletion
//! and documentation discovery in language servers and coding assistants.

pub mod logger;
pub mod debugger;
pub mod linter;
pub mod restorator;
pub mod hover;


// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Diagnostic Tools )
// ================================================================================
pub use logger::{DiagnosticLogger, FailpointType, LogEvent, FixKind, FixSuggestion, CognitiveNote};
pub use debugger::OmniDebugger;
pub use linter::{
    BlockKind, BodyLinter, BodyScore, ClosingLinter, ClosingScore, DetectedBlock, FileAuditScore,
    LintReport, MetadataLinter, MetadataScore, OmniLinter, OpeningLinter, OpeningScore, QuadStateGate,
};
pub use restorator::{Restorator, RestorationReport, AppliedRepair};
pub use hover::{HoverEngine, HoverCard, OmniDefinition, TapeRollContext};


// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Core Registrations & Coordination Invariants )
// ================================================================================
// Diagnostic modules are actively coordinated across compiler passes.
// The Logger records incidents, the Restorator synthesizes candidate patches,
// and the Debugger executes verification test oracles before state commitment.


// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Verification & Subsystem Status )
// ================================================================================
// Diagnostics subsystem verified and closed.

```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/restorator.rs RS 667 LINES 2387 WORDS 27.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Restorator Identity, Self-Healing Immune Invariants & Repair Kinds )
// ============================================================================
//! OmniCode Diagnostics: Restorator & Self-Healing Engine
//!
//! # Purpose & Cybernetic Architecture
//! Autonomous code restoration and healing organ. Diagnoses syntax anomalies,
//! unclosed or mismatched boundaries, missing 4-block architecture scaffolding,
//! and missing standard library imports, applying surgical restorative patches
//! to bring non-operational code into a verified operational state (`+1:PROCEED`).
//!
//! # Self-Healing Pipeline Passes:
//! 1. **Pass 1 (Boundary Physics)**: Closes unclosed delimiters and aligns mismatched pairs.
//! 2. **Pass 2 (4-Block Architecture)**: Ensures canonical order: Metadata -> Opening -> Body -> Closing.
//! 3. **Pass 3 (Dependency Injection)**: Automatically detects required core modules (`Core.Arithmetic`, etc.) and injects imports.
//! 4. **Pass 4 (Conceptual Inference)**: Synthesizes noun declarations with infer operators (`Ball < Entity? >`).
//! 5. **Pass 5 (Round-trip Verification)**: Lints, lexes, parses, and evaluates the candidate to certify operational validity.
//!
//! # Test Oracle Integration:
//! Connects directly to test verification harnesses via [`Restorator::restore_and_verify_with_oracle`],
//! ensuring patches satisfy external invariants and recording verified repair notes in AI memory.

use std::fs;
use crate::core::ternary::QuadState;
use crate::diagnostics::debugger::OmniDebugger;
use crate::diagnostics::linter::{BlockKind, OmniLinter};
use crate::diagnostics::logger::{DiagnosticLogger, FailpointType, FixKind, LogEvent};
use crate::parser::lexer::Lexer;
use crate::parser::parser::Parser;
use crate::runtime::environment::Environment;
use crate::runtime::evaluator::Evaluator;


// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Restoration Structures and Engine Context Initialization )
// ============================================================================
/// Record of an individual restorative patch applied to source code.
#[derive(Debug, Clone)]
pub struct AppliedRepair {
    /// The structural category of the applied repair.
    pub kind: FixKind,
    /// Detailed human and AI-readable explanation of why and how the repair was made.
    pub description: String,
    /// 1-based source line number where the repair took effect.
    pub line: usize,
}

/// Comprehensive outcome report generated by the [`Restorator`].
///
/// Contains original source, restored content, applied repairs, verification status,
/// and any errors encountered during the self-healing cycle.
#[derive(Debug, Clone)]
pub struct RestorationReport {
    /// File path if restoration was performed on disk, or `None` if in-memory.
    pub file_path: Option<String>,
    /// `true` if any modifications or repairs were made to the source text.
    pub was_modified: bool,
    /// Exact unmodified original source code prior to healing passes.
    pub original_content: String,
    /// Healed, patched, and structurally validated source code.
    pub restored_content: String,
    /// Chronological list of all automated repairs applied during the cycle.
    pub repairs_applied: Vec<AppliedRepair>,
    /// `true` if the restored content passed all lint, parse, and evaluation checks.
    pub verified: bool,
    /// The final QuadState produced by evaluating the restored source (+1:PROCEED).
    pub final_state: Option<QuadState>,
    /// Any lint, parse, or evaluation errors if verification failed.
    pub errors: Vec<String>,
}
```

```rust

/// The autonomous self-healing and code restoration engine.
pub struct Restorator {
    /// Shared diagnostic logger recording cognitive observations and repair history.
    pub logger: DiagnosticLogger,
}

impl Restorator {
    /// Constructs a new [`Restorator`] instance bound to the provided logger.
    pub fn new(logger: DiagnosticLogger) -> Self {
        Self { logger }
    }
}


// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Core Restoration Pipeline: Boundaries, 4-Block Headers, Imports, Verification )
// ============================================================================
impl Restorator {
    /// Restores source code in memory, executing multi-pass auto-repairs.
    ///
    /// Executes the 5-pass self-healing pipeline:
    /// 1. Delimiter & Boundary Healing
    /// 2. 4-Block Architecture Injection
    /// 3. Standard Library Import Resolution
    /// 4. Inferred Conceptual Entity Declaration
    /// 5. Round-trip Lint/Parse/Eval Verification
    ///
    /// # Arguments
    /// * `source` - Raw input string that may contain boundary leaks or syntax anomalies.
    ///
    /// # Returns
    /// A [`RestorationReport`] detailing all modifications and verification proofs.
    pub fn restore_source(&self, source: &str) -> RestorationReport {
        let original_content = source.to_string();
        let mut current = source.to_string();
        let mut repairs_applied = Vec::new();

        // Pass 1: Delimiter & Boundary Healing
        current = self.heal_boundaries(&current, &mut repairs_applied);

        // Pass 2: 4-Block Architectural Scaffolding Healing
        current = self.heal_four_blocks(&current, &mut repairs_applied);

        // Pass 3: Automated Dependency & Import Healing
        current = self.heal_imports(&current, &mut repairs_applied);

        // Pass 4: Inferred Conceptual Entity Healing
        current = self.heal_inferred_entities(&current, &mut repairs_applied);

        // Pass 5: Round-trip Self-Verification
        let (verified, final_state, errors) = self.verify_restoration(&current);

        let was_modified = current != original_content;

        if !repairs_applied.is_empty() {
            let repair_descs: Vec<String> = repairs_applied.iter().map(|r| r.description.clone()).collect();
            self.logger.record_ai_observation(
                "SELF_HEAL_APPLIED",
                &format!("Applied {} automated repairs", repairs_applied.len()),
                &format!("Repairs executed: {}", repair_descs.join("; ")),
                ["self_healing", "remediation", "restorator"].as_slice(),
                None,
            );
        }

        RestorationReport {
            file_path: None,
            was_modified,
            original_content,
            restored_content: current,
            repairs_applied,
            verified,
            final_state,
            errors,
        }
    }
```

```rust

    /// Ingests a structured [`LogEvent`] and executes a targeted, single-point surgical patch.
    ///
    /// # Arguments
    /// * `source` - Source code to repair.
    /// * `log` - Structured incident event containing a [`crate::diagnostics::logger::FixSuggestion`].
    ///
    /// # Returns
    /// [`RestorationReport`] showing the single-point modification and round-trip verification status.
    pub fn restore_from_incident_log(&self, source: &str, log: &LogEvent) -> RestorationReport {
        let original_content = source.to_string();
        let mut repairs_applied = Vec::new();
        let mut current = source.to_string();

        if let Some(sug) = &log.suggestion {
            match sug.kind {
                FixKind::FixBoundaryMismatch => {
                    let lines: Vec<&str> = current.lines().collect();
                    if sug.line > 0 && sug.line <= lines.len() {
                        let mut target_line = lines[sug.line - 1].to_string();
                        if let Some(pos) = target_line.find(&sug.target_token) {
                            target_line.replace_range(pos..pos + sug.target_token.len(), &sug.suggested_patch);
                            let mut new_lines = lines.clone();
                            new_lines[sug.line - 1] = &target_line;
                            current = new_lines.join("\n");
                            if !current.ends_with('\n') {
                                current.push('\n');
                            }
                            repairs_applied.push(AppliedRepair {
                                kind: FixKind::FixBoundaryMismatch,
                                description: sug.rationale.clone(),
                                line: sug.line,
                            });
                        }
                    }
                }
                FixKind::CloseBoundary => {
                    current.push_str(&sug.suggested_patch);
                    if !current.ends_with('\n') {
                        current.push('\n');
                    }
                    repairs_applied.push(AppliedRepair {
                        kind: FixKind::CloseBoundary,
                        description: sug.rationale.clone(),
                        line: sug.line,
                    });
                }
                FixKind::ConvertImmutableToMutable => {
                    current = current.replace(&format!("< {} >", sug.target_token), &sug.suggested_patch);
                    repairs_applied.push(AppliedRepair {
                        kind: FixKind::ConvertImmutableToMutable,
                        description: sug.rationale.clone(),
                        line: sug.line,
                    });
                }
                _ => {
                    current = current.replace(&sug.target_token, &sug.suggested_patch);
                    repairs_applied.push(AppliedRepair {
                        kind: sug.kind.clone(),
                        description: sug.rationale.clone(),
                        line: sug.line,
                    });
                }
            }
        }

        let (verified, final_state, errors) = self.verify_restoration(&current);
        let was_modified = current != original_content;

        if was_modified {
            self.logger.record_ai_observation(
                "LOG_DRIVEN_RESTORE",
                &format!("Applied targeted fix from log for {:?}", log.failpoint_type),
                &format!("Modified {} bytes", current.len()),
                ["self_healing", "log_driven"].as_slice(),
                None,
            );
        }
```

```
        RestorationReport {
            file_path: None,
            was_modified,
            original_content,
            restored_content: current,
            repairs_applied,
            verified,
            final_state,
            errors,
        }
    }

    /// Restores source code and executes an external verification test oracle against the candidate.
    ///
    /// Connects the self-healing engine to test harnesses:
    /// - If the restored code satisfies the test oracle: logs an `ORACLE_CERTIFIED` cognitive trace.
    /// - If the test oracle fails: records a rollback failpoint and adds the failure to the report errors.
    ///
    /// # Arguments
    /// * `source` - Raw input code.
    /// * `test_oracle` - Closure asserting domain-specific invariants on the restored source.
    pub fn restore_and_verify_with_oracle<F>(&self, source: &str, test_oracle: F) -> RestorationReport
    where
        F: Fn(&str) -> Result<(), String>,
    {
        let mut report = self.restore_source(source);

        if report.verified {
            match test_oracle(&report.restored_content) {
                Ok(()) => {
                    self.logger.log("RESTORATOR", "Restoration validated by test oracle (+1:PROCEED)");
                    self.logger.record_ai_observation(
                        "ORACLE_CERTIFIED",
                        "Restored code certified by test oracle",
                        "The candidate passed the verification test suite cleanly",
                        ["self_healing", "test_oracle", "certified"].as_slice(),
                        None,
                    );
                }
                Err(err) => {
                    self.logger.failpoint(
                        FailpointType::RollbackTriggered,
                        "RESTORATOR",
                        format!("Restoration failed test oracle verification: {err}"),
                    );
                    self.logger.record_ai_observation(
                        "ORACLE_REJECTED",
                        "Restored code failed test oracle verification",
                        &err,
                        ["self_healing", "test_oracle", "rollback"].as_slice(),
                        None,
                    );
                    report.verified = false;
                    report.errors.push(format!("Test oracle failure: {err}"));
                }
            }
        }

        report
    }

    /// Restores a file from disk, optionally writing back the healed source in-place.
    ///
    /// # Arguments
    /// * `path` - File system path to the target source file.
    /// * `in_place` - If true, overwrites the file on disk with the restored content.
    ///
    /// # Errors
    /// Returns `Err(String)` if file reading or writing fails.
    pub fn restore_file(&self, path: &str, in_place: bool) -> Result<RestorationReport, String> {
        let content = fs::read_to_string(path)
            .map_err(|e| format!("Failed to read file '{path}': {e}"))?;

        let mut report = self.restore_source(&content);
        report.file_path = Some(path.to_string());

        if in_place && report.was_modified {
```

```
            fs::write(path, &report.restored_content)
                .map_err(|e| format!("Failed to write restored file '{path}': {e}"))?;
            self.logger.log("RESTORATOR", format!("Wrote restored content in-place to '{path}'"));
        }

        Ok(report)
    }

    /// Pass 1: Auto-detects and repairs mismatched and leaking delimiters.
    fn heal_boundaries(&self, source: &str, repairs: &mut Vec<AppliedRepair>) -> String {
        let mut text = source.to_string();
        let mut max_passes = 10;

        while max_passes > 0 {
            max_passes -= 1;
            let temp_logger = DiagnosticLogger::new(false);
            let mut lexer = Lexer::new(&text, temp_logger.clone());
            let tokens = match lexer.tokenize() {
                Ok(toks) => toks,
                Err(_) => break,
            };

            let debugger = OmniDebugger::new(temp_logger.clone(), 10);
            let mut parser = Parser::new(tokens, debugger);
            let parse_res = parser.parse_program();

            if parse_res.is_ok() {
                break; // Boundaries are sound
            }

            // Inspect diagnostic remediations from debugger
            let mut debugger_remediations = parser.debugger.drain_remediations();
            if debugger_remediations.is_empty() {
                debugger_remediations = temp_logger.remediations();
            }

            if debugger_remediations.is_empty() {
                // If EOF unclosed boundary detected without explicit remediation, balance stack
                if !parser.debugger.boundary_stack.is_empty() {
                    let mut closers = String::new();
                    while let Some(frame) = parser.debugger.boundary_stack.pop() {
                        let c = match frame.open_char {
                            '<' => '>',
                            '[' => ']',
                            '{' => '}',
                            _ => ')',
                        };
                        closers.push(c);
                        repairs.push(AppliedRepair {
                            kind: FixKind::CloseBoundary,
                            description: format!("Appended missing closing delimiter '{c}' for boundary opened at
L{}:C{}", frame.line, frame.col),
                            line: frame.line,
                        });
                    }
                    text.push_str(&format!("\n{}\n", closers));
                    continue;
                }
                break;
            }

            // Apply remediation patches
            let mut applied_any = false;
            for sug in debugger_remediations {
                match sug.kind {
                    FixKind::FixBoundaryMismatch => {
                        let lines: Vec<&str> = text.lines().collect();
                        if sug.line > 0 && sug.line <= lines.len() {
                            let mut target_line = lines[sug.line - 1].to_string();
                            if let Some(pos) = target_line.find(&sug.target_token) {
                                target_line.replace_range(pos..pos + sug.target_token.len(), &sug.suggested_patch);
                                let mut new_lines = lines.clone();
                                new_lines[sug.line - 1] = &target_line;
                                text = new_lines.join("\n");
                                if !text.ends_with('\n') {
                                    text.push('\n');
                                }
                                repairs.push(AppliedRepair {
```

```
                                    kind: FixKind::FixBoundaryMismatch,
                                    description: sug.rationale,
                                    line: sug.line,
                                });
                                applied_any = true;
                                break;
                            }
                        }
                    }
                    FixKind::CloseBoundary => {
                        text.push_str(&sug.suggested_patch);
                        if !text.ends_with('\n') {
                            text.push('\n');
                        }
                        repairs.push(AppliedRepair {
                            kind: FixKind::CloseBoundary,
                            description: sug.rationale,
                            line: sug.line,
                        });
                        applied_any = true;
                        break;
                    }
                    _ => {}
                }
            }

            if !applied_any {
                break;
            }
        }

        text
    }

    /// Pass 2: Ensures all 4 universal architectural blocks exist in canonical order.
    fn heal_four_blocks(&self, source: &str, repairs: &mut Vec<AppliedRepair>) -> String {
        let linter = OmniLinter::new(DiagnosticLogger::new(false));
        let report = linter.lint_source("memory", source);

        if report.is_valid {
            return source.to_string();
        }

        let mut has_metadata = false;
        let mut has_opening = false;
        let mut has_body = false;
        let mut has_closing = false;

        for b in &report.blocks_found {
            match b.kind {
                BlockKind::Metadata => has_metadata = true,
                BlockKind::Opening => has_opening = true,
                BlockKind::Body => has_body = true,
                BlockKind::Closing => has_closing = true,
            }
        }

        let mut out = String::new();

        // 1. Inject Metadata Block if missing
        if !has_metadata {
            repairs.push(AppliedRepair {
                kind: FixKind::AddBlockHeader,
                description: "Injected canonical BLOCK 1: METADATA manifest".into(),
                line: 1,
            });
            out.push_str("# ================================================================================\n");
            out.push_str("# BLOCK 1: METADATA BLOCK\n");
            out.push_str("# ( Restored Module Manifest and Semantic Track )\n");
            out.push_str("# ================================================================================\n");
            out.push_str("Module < Restored.Track > ( Auto-restored OmniCode compilation unit ) {\n");
            out.push_str("    version: < \"1.0.0\" >,\n");
            out.push_str("    system: < OmniCode.Core >\n");
            out.push_str("}\n\n");
        }

        // 2. Inject Opening Block if missing
        if !has_opening {
```

```
            repairs.push(AppliedRepair {
                kind: FixKind::AddBlockHeader,
                description: "Injected canonical BLOCK 2: OPENING context".into(),
                line: 1,
            });
            out.push_str("# ================================================================================\n");
            out.push_str("# BLOCK 2: OPENING BLOCK\n");
            out.push_str("# ( Initial Conditions and Operational Preconditions )\n");
            out.push_str("# ================================================================================\n");
            out.push_str("Opening {\n");
            out.push_str("    preconditions: [ +1 ]\n");
            out.push_str("}\n\n");
        }

        // 3. Append existing body content
        if !has_body {
            repairs.push(AppliedRepair {
                kind: FixKind::AddBlockHeader,
                description: "Injected canonical BLOCK 3: BODY block wrapping loose operations".into(),
                line: 1,
            });
            out.push_str("# ================================================================================\n");
            out.push_str("# BLOCK 3: BODY BLOCK\n");
            out.push_str("# ( Core Operations and Transformations )\n");
            out.push_str("# ================================================================================\n");
            out.push_str("Body [\n");
            for line in source.lines() {
                if !line.trim().is_empty() {
                    out.push_str(&format!("    {}\n", line));
                }
            }
            out.push_str("]\n\n");
        } else {
            out.push_str(source);
            if !out.ends_with('\n') {
                out.push('\n');
            }
        }

        // 4. Inject Closing Block if missing
        if !has_closing {
            repairs.push(AppliedRepair {
                kind: FixKind::AddBlockHeader,
                description: "Injected canonical BLOCK 4: CLOSING commit proof".into(),
                line: 1,
            });
            out.push_str("# ================================================================================\n");
            out.push_str("# BLOCK 4: CLOSING BLOCK\n");
            out.push_str("# ( State Verification Proof and Final Commit )\n");
            out.push_str("# ================================================================================\n");
            out.push_str("Closing {\n");
            out.push_str("    commit_status [ PROCEED ]\n");
            out.push_str("}\n");
        }

        out
    }

    /// Pass 3: Automatically injects missing core library imports into Opening block.
    fn heal_imports(&self, source: &str, repairs: &mut Vec<AppliedRepair>) -> String {
        let needs_arithmetic = (source.contains("plus") || source.contains("minus") || source.contains("times") ||
source.contains("div") || source.contains("ADD") || source.contains("SUB"))
            && !source.contains("Core.Arithmetic");

        let needs_logic = (source.contains("PROCEED") || source.contains("ROLLBACK") || source.contains("AWAIT") ||
source.contains("HALT"))
            && !source.contains("Core.Logic");

        let needs_vectors = (source.contains("-->") || source.contains("<--") || source.contains("--^") ||
source.contains("--v"))
            && !source.contains("Core.Vectors");

        if !needs_arithmetic && !needs_logic && !needs_vectors {
            return source.to_string();
        }

        let mut mods_to_import = Vec::new();
        if needs_arithmetic {
```

```
            mods_to_import.push("Core.Arithmetic");
        }
        if needs_logic {
            mods_to_import.push("Core.Logic");
        }
        if needs_vectors {
            mods_to_import.push("Core.Vectors");
        }

        let import_expr = format!("import: [ {} ]", mods_to_import.join(" :: "));

        // Inject into Opening { ... } block
        if let Some(op_idx) = source.find("Opening {") {
            let insert_pos = op_idx + "Opening {".len();
            let mut out = source.to_string();
            let injection = format!("\n    {},\n", import_expr);
            out.insert_str(insert_pos, &injection);

            repairs.push(AppliedRepair {
                kind: FixKind::AddImport,
                description: format!("Injected library imports into Opening block: {import_expr}"),
                line: 1,
            });
            return out;
        }

        source.to_string()
    }

    /// Pass 4: Resolves and declares undefined conceptual nouns with infer operator `?`.
    fn heal_inferred_entities(&self, source: &str, repairs: &mut Vec<AppliedRepair>) -> String {
        let mut missing_inferred = Vec::new();

        if source.contains("Ball?") && !source.contains("Ball <") {
            missing_inferred.push("Ball < Entity? > ( Inferred discrete unit )");
        }
        if source.contains("Group?") && !source.contains("Group <") {
            missing_inferred.push("Group < Set? >   ( Inferred collection container )");
        }

        if missing_inferred.is_empty() {
            return source.to_string();
        }

        let mut out = source.to_string();
        // Insert right after Module < ... > definition
        if let Some(pos) = out.find("Module <") {
            if let Some(block_end) = out[pos..].find('}') {
                let insert_at = pos + block_end + 1;
                let mut decls = String::from("\n\n# Auto-Restored Conceptual Types:\n");
                for d in &missing_inferred {
                    decls.push_str(d);
                    decls.push('\n');
                }
                out.insert_str(insert_at, &decls);

                repairs.push(AppliedRepair {
                    kind: FixKind::DeclareEntityWithInfer,
                    description: format!("Declared {} inferred conceptual entities", missing_inferred.len()),
                    line: 1,
                });
            }
        }

        out
    }

    /// Pass 5: Evaluates restored code to verify complete execution without failpoints.
    fn verify_restoration(&self, source: &str) -> (bool, Option<QuadState>, Vec<String>) {
        let mut errors = Vec::new();
        let logger = DiagnosticLogger::new(false);

        // 1. Lint check
        let linter = OmniLinter::new(logger.clone());
        let lint_rep = linter.lint_source("verify", source);
        if !lint_rep.is_valid {
            for err in lint_rep.errors {
                errors.push(format!("Lint error: {err}"));
```

```
            }
        }

        // 2. Tokenize & Parse
        let mut lexer = Lexer::new(source, logger.clone());
        let tokens = match lexer.tokenize() {
            Ok(t) => t,
            Err(e) => {
                errors.push(format!("Lex error: {e}"));
                return (false, None, errors);
            }
        };

        let debugger = OmniDebugger::new(logger.clone(), 10);
        let mut parser = Parser::new(tokens, debugger);
        let prog = match parser.parse_program() {
            Ok(p) => p,
            Err(e) => {
                errors.push(format!("Parse error: {e}"));
                return (false, None, errors);
            }
        };

        // 3. Execution check
        let mut evaluator = Evaluator::new(Environment::new(), parser.debugger);
        match evaluator.eval(&crate::ast::nodes::ASTNode::Program(prog)) {
            Ok(val) => {
                let state = match val {
                    crate::runtime::environment::RuntimeValue::State(s) => s,
                    _ => QuadState::Proceed,
                };
                let verified = errors.is_empty() && (state == QuadState::Proceed || state == QuadState::Await);
                (verified, Some(state), errors)
            }
            Err(e) => {
                errors.push(format!("Eval error: {e}"));
                (false, None, errors)
            }
        }
    }
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Restorator Verification and Default Sealing )
// ============================================================================
impl Default for Restorator {
    fn default() -> Self {
        Self::new(DiagnosticLogger::new(false))
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/README.md MD 78 LINES 588 WORDS 4.5 KB

```
# OmniCode Diagnostic & Telemetry Flight Recorder Subsystem

> *"And he gave unto Moses, when he had made an end of communing with him upon mount Sinai, two tables of testimony, tables of stone, written with the finger of God."*
> — **Exodus 31:18 (KJV)**
>
> *"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house."*
> — **Proverbs 24:27 (KJV)**
>
> *"And when thou art come in, thou shalt shut the door upon thee and upon thy sons, and shalt pour out into all those vessels, and thou shalt set aside that which is full."*
> — **2 Kings 4:4 (KJV)**

---

## 1. Architectural Philosophy: The Flight Recorder Engine

The `logger` subsystem in **OmniCode Track 1 (Host Engine & Virtual Machine)** is not a simple string printer. It is a **deterministic flight recorder, sensory telemetry bus, and episodic memory storehouse engine** inspired by high-performance game development.

### Core System Invariants

1. **Deterministic Tick / Frame Telemetry**:
   Every process tape roll is treated as an atomic frame in a game loop. States are captured as structured vectors ($S \rightarrow S'$), recording dual-rail SIMD bitplanes, operational verbs, and QuadStates.
2. **Vessel Capacity & Rotation Law**:
   Following container law (`Occupancy <= Capacity`), storehouse partitions automatically rotate and archive historical records when capacity limits are reached.
3. **Homoiconic Actionability**:
   Logs are inscribed as canonical 4-Block OmniCode `.scroll` programs that can be re-executed, stepped through, or automatically repaired by the `Restorator`.
4. **Episodic O(1) Indexing**:
   Replaces linear directory crawls with indexed session lookups, category filters, and temporal range scans.

---

## 2. Subsystem Directory Topology

```basg
src/diagnostics/logger/
├── README.md               <-- Architectural Manifesto & Subsystem Documentation
├── mod.rs                  <-- Backward-Compatible DiagnosticLogger Facade
│
├── universal/              <-- Hardware Ticks, Monotonic Clocks & Lock-Free Bus
│   ├── mod.rs              <-- Re-exports Universal Timing & Bus
│   ├── clock.rs            <-- Monotonic elapsed clock & timestamp ID generation
│   └── bus.rs              <-- Lock-free, zero-allocation event channel bus
│
├── failpoint/              <-- Pathology & Invariant Classification Engine
│   ├── mod.rs              <-- Re-exports Failpoint Types & Remediation
│   ├── types.rs            <-- FailpointType (BoundaryMismatch, NullTrap, CaveatVeto)
│   └── remediation.rs      <-- FixKind, FixSuggestion & machine-applicable patches
│
├── telemetry/              <-- Structured Frame Telemetry & Flight Recorder
│   ├── mod.rs              <-- Re-exports Telemetry Components
│   ├── frame.rs            <-- RollFrame struct (Dual-Rail bitplanes, verbs, QuadState)
│   ├── note.rs             <-- CognitiveNote semantic memory units
│   └── ring_buffer.rs      <-- In-memory Flight Recorder (fixed circular buffer)
│
├── inscriber/              <-- Container Storehouse Inscription Engine
│   ├── mod.rs              <-- Re-exports Inscription Engines & Rotation
│   ├── rotation.rs         <-- RotationPolicy enforcing container capacity limits
│   ├── naming.rs           <-- Standardized vessel naming & path resolution
│   ├── scroll_writer.rs    <-- Inscribes 4-Block .scroll reels to Track 4
│   └── log_writer.rs       <-- Inscribes structured .log files to Track 4
│
└── query/                  <-- Episodic Query Engine (The Indexing Machine)
    ├── mod.rs              <-- Re-exports Query Engine & Index Models
    ├── index.rs            <-- IndexedSession data structure
    └── search.rs           <-- O(1) session search & range scanning
```

```

```
## 3. The Baton Relay to the AI Subsystem

The modular logger serves as the physical sensory nervous system for the AI:

1. **VM steps a Roll** $\rightarrow$ records a `RollFrame` into the `FlightRecorder`.
2. **Execution seals** $\rightarrow$ `inscriber` writes paired `.scroll` and `.log` to Track 4.
3. **`AILearner` ingests** $\rightarrow$ translates `RollFrame`s into $(S, A, R, S')$ reinforcement learning batches.
4. **`NeuralBrain` adapts** $\rightarrow$ updates discrete ternary weights ($W \in \{-1, 0, +1\}$).
5. **`AICortex` converses** $\rightarrow$ deliberates with the developer at the terminal prompt.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/mod.rs RS 356 LINES 1031 WORDS 12.2 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Diagnostic Logger Subsystem Identity, Modular Facade & Re-exports )
// ================================================================================
//! OmniCode Diagnostics: Modular Telemetry, Failpoint & Flight Recorder System
//!
//! # Architecture & Epistemic Role
//! Decomposed into specialized machine organs:
//! - [`universal`]: Monotonic clock, nanosecond timers, and lock-free event bus.
//! - [`failpoint`]: Failpoint pathology classification and machine-applicable repairs.
//! - [`telemetry`]: Game-dev RollFrame vectors, CognitiveNotes, and FlightRecorder.
//! - [`inscriber`]: Canonical 4-Block .scroll and .log writers with rotation policies.
//! - [`query`]: Episodic query engine enabling O(1) session lookup and range scans.

pub mod universal;
pub mod failpoint;
pub mod telemetry;
pub mod inscriber;
pub mod query;

use std::path::{Path, PathBuf};
use std::sync::{Arc, Mutex};

pub use universal::{EventBus, LogEvent, MonotonicClock, generate_timestamp_id};
pub use failpoint::{FailpointType, FixKind, FixSuggestion};
pub use telemetry::{CognitiveNote, FlightRecorder, RollFrame};
pub use inscriber::{
    RotationPolicy, format_base_name, inscribe_audit_scroll,
    inscribe_canonical_scroll, inscribe_telemetry_log, parse_file_name,
    resolve_vessel_path,
};
pub use query::{EpisodicQueryEngine, IndexedSession};

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( DiagnosticLogger Data Structure & Initialization )
// ================================================================================
/// Thread-safe diagnostic logging, flight recording & cognitive memory engine.
#[derive(Debug, Clone)]
pub struct DiagnosticLogger {
    clock: MonotonicClock,
    bus: EventBus,
    cognitive_notes: Arc<Mutex<Vec<CognitiveNote>>>,
    flight_recorder: Arc<Mutex<FlightRecorder>>,
}

impl DiagnosticLogger {
    /// Constructs a new [`DiagnosticLogger`].
    pub fn new(print_live: bool) -> Self {
        Self {
            clock: MonotonicClock::new(),
            bus: EventBus::new(print_live),
            cognitive_notes: Arc::new(Mutex::new(Vec::new())),
            flight_recorder: Arc::new(Mutex::new(FlightRecorder::new(512))),
        }
    }
}

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Logging Operations, Failpoint Trapping, Flight Recording & Inscription )
// ================================================================================
impl DiagnosticLogger {
    /// Inscribes a normal debug or trace event into the diagnostic log.
    pub fn log(&self, channel: &'static str, message: impl Into<String>) {
        let msg = message.into();
        let elapsed = self.clock.elapsed_micros();
        let event = LogEvent {
            elapsed_micros: elapsed,
            channel,
            message: msg,
            is_failpoint: false,
            failpoint_type: None,
            suggestion: None,
```

```
            cognitive_note: None,
        };
        self.bus.emit(event);
    }

    /// Intercepts and records a critical failpoint event without remediation.
    pub fn failpoint(
        &self,
        fp_type: FailpointType,
        channel: &'static str,
        message: impl Into<String>,
    ) {
        let msg = message.into();
        let elapsed = self.clock.elapsed_micros();
        let note = CognitiveNote {
            timestamp_micros: elapsed,
            category: "INCIDENT".to_string(),
            summary: msg.clone(),
            details: format!("Failpoint trapped: {}", fp_type.as_str()),
            tags: vec!["failpoint".to_string(), fp_type.as_str().to_lowercase()],
            context_snippet: None,
        };

        let event = LogEvent {
            elapsed_micros: elapsed,
            channel,
            message: msg,
            is_failpoint: true,
            failpoint_type: Some(fp_type),
            suggestion: None,
            cognitive_note: Some(note.clone()),
        };

        self.cognitive_notes.lock().unwrap().push(note);
        self.bus.emit(event);
    }

    /// Intercepts a critical failpoint event with concrete remediation telemetry.
    pub fn failpoint_with_remediation(
        &self,
        fp_type: FailpointType,
        channel: &'static str,
        message: impl Into<String>,
        suggestion: FixSuggestion,
    ) {
        let msg = message.into();
        let elapsed = self.clock.elapsed_micros();
        let note = CognitiveNote {
            timestamp_micros: elapsed,
            category: "INCIDENT".to_string(),
            summary: msg.clone(),
            details: suggestion.rationale.clone(),
            tags: vec![
                "failpoint".to_string(),
                fp_type.as_str().to_lowercase(),
                "remediation_ready".to_string(),
            ],
            context_snippet: Some(suggestion.target_token.clone()),
        };

        let event = LogEvent {
            elapsed_micros: elapsed,
            channel,
            message: msg,
            is_failpoint: true,
            failpoint_type: Some(fp_type),
            suggestion: Some(suggestion),
            cognitive_note: Some(note.clone()),
        };

        self.cognitive_notes.lock().unwrap().push(note);
        self.bus.emit(event);
    }

    /// Records an arbitrary cognitive observation into episodic memory.
    pub fn record_ai_observation(
        &self,
        category: &str,
```

```
        summary: &str,
        details: &str,
        tags: &[&str],
        context: Option<&str>,
    ) -> CognitiveNote {
        let elapsed = self.clock.elapsed_micros();
        let note = CognitiveNote {
            timestamp_micros: elapsed,
            category: category.to_string(),
            summary: summary.to_string(),
            details: details.to_string(),
            tags: tags.iter().map(|s| s.to_string()).collect(),
            context_snippet: context.map(|s| s.to_string()),
        };

        self.cognitive_notes.lock().unwrap().push(note.clone());
        self.log(
            "COGNITION",
            format!("[{category}] {summary} (tags: {:?})", note.tags),
        );
        note
    }

    /// Inscribes a pre-formed [`CognitiveNote`] directly into memory.
    pub fn log_cognitive_note(&self, note: CognitiveNote) {
        self.cognitive_notes.lock().unwrap().push(note);
    }

    /// Retrieves a cloned snapshot of all recorded cognitive memory notes.
    pub fn cognitive_notes(&self) -> Vec<CognitiveNote> {
        self.cognitive_notes.lock().unwrap().clone()
    }

    /// Exports all recorded cognitive notes into a canonical 4-Block memory scroll.
    pub fn export_ai_memory_scroll(&self) -> String {
        let notes = self.cognitive_notes();
        inscribe_audit_scroll(&notes, self.bus.all_failpoints().len())
    }

    /// Retrieves all intercepted failpoint events.
    pub fn failpoints(&self) -> Vec<LogEvent> {
        self.bus.all_failpoints()
    }

    /// Retrieves all general log events.
    pub fn events(&self) -> Vec<LogEvent> {
        self.bus.all_events()
    }

    /// Extracts all remediation suggestions currently registered.
    pub fn remediations(&self) -> Vec<FixSuggestion> {
        self.bus
            .all_failpoints()
            .iter()
            .filter_map(|e| e.suggestion.clone())
            .collect()
    }

    /// Returns `true` if any failpoints were trapped.
    pub fn has_failpoints(&self) -> bool {
        !self.bus.all_failpoints().is_empty()
    }

    /// Clears all stored events, failpoints, and cognitive memory notes.
    pub fn clear(&self) {
        self.bus.clear();
        self.cognitive_notes.lock().unwrap().clear();
        self.flight_recorder.lock().unwrap().clear();
    }

    /// Logs an internal AI Thought, indexing it in episodic memory.
    pub fn log_thought(
        &self,
        thought_id: &str,
        omnicode_tape: &str,
        premise: &str,
        quad_state_str: &str,
    ) {
```

```
        let elapsed = self.clock.elapsed_micros();
        let note = CognitiveNote {
            timestamp_micros: elapsed,
            category: "THOUGHT".to_string(),
            summary: format!("Thought [{thought_id}]: {premise}"),
            details: omnicode_tape.to_string(),
            tags: vec![
                "thought".to_string(),
                "ai_cortex".to_string(),
                quad_state_str.to_lowercase(),
            ],
            context_snippet: Some(omnicode_tape.to_string()),
        };

        self.cognitive_notes.lock().unwrap().push(note);
        self.log(
            "CORTEX",
            format!(
                "[THOUGHT: {thought_id}] (State: {quad_state_str}) Premise: \"{premise}\""
            ),
        );
    }

    /// Records an associative memory link.
    pub fn log_memory_association(&self, concept: &str, anchor: &str, details: &str) {
        let elapsed = self.clock.elapsed_micros();
        let note = CognitiveNote {
            timestamp_micros: elapsed,
            category: "ASSOCIATION".to_string(),
            summary: format!("Memory Link: {concept} <-> {anchor}"),
            details: details.to_string(),
            tags: vec!["memory".to_string(), "scripture".to_string(), concept.to_lowercase()],
            context_snippet: Some(anchor.to_string()),
        };

        self.cognitive_notes.lock().unwrap().push(note);
        self.log(
            "MEMORY",
            format!("Associated concept '{concept}' with anchor '{anchor}'"),
        );
    }

    /// Logs the physical inscription of an episodic scroll to disk.
    pub fn log_scroll_inscribed(&self, scroll_path: &Path, session_or_id: &str) {
        self.log(
            "SCROLL",
            format!("Inscribed episodic scroll '{session_or_id}' to {:?}", scroll_path),
        );
    }

    /// Inscribes a canonical 4-Block .scroll file to the given path.
    pub fn inscribe_canonical_scroll(
        &self,
        path: &Path,
        session_id: &str,
        prompt: &str,
        synthesized_omnicode: &str,
        state_str: &str,
        response: &str,
    ) -> Result<PathBuf, String> {
        let elapsed = self.clock.elapsed_micros();
        let res = inscribe_canonical_scroll(
            path,
            session_id,
            prompt,
            synthesized_omnicode,
            state_str,
            response,
            elapsed,
        )?;
        self.log_scroll_inscribed(path, session_id);
        Ok(res)
    }

    // --- GAME-DEV FLIGHT RECORDER & TELEMETRY EXTENSIONS ---

    /// Inscribes a structured execution frame into the in-memory flight recorder.
    pub fn record_roll_frame(&self, frame: RollFrame) {
```

```
        self.log(
            "FRAME",
            format!(
                "Roll {}/{}: {} => {:?}",
                frame.roll_index, frame.total_rolls, frame.verb, frame.quad_state
            ),
        );
        self.flight_recorder.lock().unwrap().record_frame(frame);
    }

    /// Retrieves the most recent execution frames from the flight recorder.
    pub fn recent_roll_frames(&self, count: usize) -> Vec<RollFrame> {
        self.flight_recorder.lock().unwrap().recent_frames(count)
    }

    /// Retrieves the most recent anomalous or failing roll frame.
    pub fn last_anomalous_frame(&self) -> Option<RollFrame> {
        self.flight_recorder.lock().unwrap().last_anomalous_frame()
    }

    /// Creates and populates an [`EpisodicQueryEngine`] pointing to `storehouse_root`.
    pub fn create_query_engine(&self, storehouse_root: &Path) -> EpisodicQueryEngine {
        let mut engine = EpisodicQueryEngine::new();
        let _ = engine.index_directory(storehouse_root);
        engine
    }

    /// Enforces the storehouse capacity rotation policy on a partition directory.
    pub fn enforce_rotation(
        &self,
        partition_dir: &Path,
        policy: RotationPolicy,
    ) -> Result<usize, String> {
        policy.enforce(partition_dir)
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Default Trait Implementation and Subsystem Sealing )
// ============================================================================
impl Default for DiagnosticLogger {
    /// Constructs a silent [`DiagnosticLogger`] with live terminal printing disabled.
    fn default() -> Self {
        Self::new(false)
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/inscriber/log_writer.rs

RS | 91 LINES | 264 WORDS | 3.4 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Traditional Developer & Structured Telemetry .log Inscription Engine )
// ============================================================================
//! Traditional Telemetry Inscription Engine
//!
//! Formats human-readable ASCII telemetry with sensory event headers,
//! microsecond timings, immune system repair notes, and failpoints.

use std::fs;
use std::path::{Path, PathBuf};
use super::super::universal::LogEvent;

/// Inscribes a structured traditional telemetry log file to disk.
pub fn inscribe_telemetry_log(
    path: &Path,
    timestamp_str: &str,
    session_id: &str,
    elapsed_micros: u128,
    final_state_str: &str,
    prompt: &str,
    failpoints: &[LogEvent],
    synthesized_omnicode: &str,
    response: &str,
) -> Result<PathBuf, String> {
    if let Some(parent) = path.parent() {
        if !parent.exists() {
            fs::create_dir_all(parent).map_err(|e| {
                format!("Failed to create log parent directory: {e}")
            })?;
        }
    }

    let mut out = String::new();
    out.push_str("================================================================================\n");
    out.push_str("OMNICODE AI MODEL EXECUTION LOG (TRADITIONAL TELEMETRY)\n");
    out.push_str("================================================================================\n");
    out.push_str(&format!("Timestamp:    {}\n", timestamp_str));
    out.push_str(&format!("Session ID:   {}\n", session_id));
    out.push_str(&format!("Duration:     {} µs\n", elapsed_micros));
    out.push_str(&format!("Final State:  +1:{}\n", final_state_str));
    out.push_str(&format!("Discourse:    \"{}\"\n", prompt));
    out.push_str("--------------------------------------------------------------------------------\n\n");

    out.push_str("[1. SENSORY LOG EVENTS & FAILPOINTS]\n");
    if failpoints.is_empty() {
        out.push_str("  • (No failpoints trapped. Sensory trace clean.)\n");
    } else {
        for (i, fp) in failpoints.iter().enumerate() {
            let kind = fp
                .failpoint_type
                .map(|t| t.as_str())
                .unwrap_or("GENERAL");
            out.push_str(&format!(
                "  [{:>4}] [{} µs] [{}] [{}] {}\n",
                i + 1,
                fp.elapsed_micros,
                fp.channel,
                kind,
                fp.message
            ));
            if let Some(ref sug) = fp.suggestion {
                out.push_str(&format!(
                    "         -> Remediation Proposal: [{:?}] L{}: {}\n",
                    sug.kind, sug.line, sug.rationale
                ));
            }
        }
    }
    out.push('\n');

    out.push_str("[2. IMMUNE SYSTEM RESTORATIONS]\n");
    out.push_str("  • (Zero repairs required; code conformed to all boundary and block invariants.)\n\n");
```

```
74
75      out.push_str("[3. SYNTHESIZED TURING REEL (OMNICODE)]\n");
76      out.push_str(synthesized_omnicode);
77      if !synthesized_omnicode.ends_with('\n') {
78          out.push('\n');
79      }
80      out.push('\n');
81
82      out.push_str("[4. MACHINE DISCOURSE RESPONSE]\n");
83      out.push_str(&format!("  \"{}\"\n", response));
84      out.push_str("================================================================================\n");
85
86      fs::write(path, out)
87          .map_err(|e| format!("Failed to write log to {:?}: {e}", path))?;
88
89      Ok(path.to_path_buf())
90  }
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/inscriber/mod.rs

RS | 16 LINES | 53 WORDS | 0.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Storehouse Inscriber Subsystem Re-exports )
// ============================================================================
//! Storehouse Inscription Subsystem: Writers, Naming & Rotation Policies

pub mod rotation;
pub mod naming;
pub mod scroll_writer;
pub mod log_writer;

pub use rotation::RotationPolicy;
pub use naming::{format_base_name, resolve_vessel_path, parse_file_name, ParsedFileName};
pub use scroll_writer::{inscribe_canonical_scroll, inscribe_audit_scroll};
pub use log_writer::inscribe_telemetry_log;
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/inscriber/naming.rs

RS | 69 LINES | 231 WORDS | 2.1 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Structured Naming Conventions for Deterministic Telemetry Indexing )
// ============================================================================
//! Naming Conventions & Parsing Machinery for Storehouse Vessels
//!
//! Formats deterministic file names allowing $O(1)$ prefix matching and
//! temporal range queries directly from filesystem paths.

use std::path::{Path, PathBuf};

/// Formats a standardized base name for telemetry and scroll files.
///
/// Pattern: `<timestamp>_<session_id>`
pub fn format_base_name(timestamp: &str, session_id: &str) -> String {
    format!("{timestamp}_{session_id}")
}

/// Resolves the destination directory for a specific category and file type.
pub fn resolve_vessel_path(
    root: &Path,
    category: &str,
    is_scroll: bool,
    base_name: &str,
) -> PathBuf {
    let subfolder = if is_scroll { "scroll" } else { "log" };
    let ext = if is_scroll { "scroll" } else { "log" };

    let dest_dir = if root.join(subfolder).exists() {
        root.join(subfolder).join(category)
    } else {
        root.to_path_buf()
    };

    dest_dir.join(format!("{base_name}.{ext}"))
}

/// Metadata extracted directly from a vessel file name.
#[derive(Debug, Clone, PartialEq, Eq)]
pub struct ParsedFileName {
    pub timestamp_micros: u128,
    pub session_id: String,
    pub extension: String,
}

/// Extracts metadata from a standardized telemetry file name.
pub fn parse_file_name(path: &Path) -> Option<ParsedFileName> {
    let file_stem = path.file_stem()?.to_string_lossy();
    let ext = path.extension()?.to_string_lossy().to_string();

    let parts: Vec<&str> = file_stem.split('_').collect();
    if parts.is_empty() {
        return None;
    }

    let micros = parts[0].parse::<u128>().ok()?;
    let session = if parts.len() > 1 {
        parts[1..].join("_")
    } else {
        "unknown".to_string()
    };

    Some(ParsedFileName {
        timestamp_micros: micros,
        session_id: session,
        extension: ext,
    })
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/inscriber/rotation.rs

RS | 86 LINES | 300 WORDS | 3.0 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( RotationPolicy: Enforcing Vessel Capacity Bounds on Episodic Storehouses )
// ============================================================================
//! Storehouse Vessel Rotation Engine
//!
//! Grounded in container law `Occupancy <= Capacity` (2 Kings 4:4), this module
//! prevents unbounded file proliferation by rotating and archiving old files.

use std::fs;
use std::path::Path;

/// Policy governing storehouse partition retention and rotation.
#[derive(Debug, Clone, Copy, PartialEq, Eq)]
pub struct RotationPolicy {
    /// Maximum number of active files allowed in a single domain partition.
    pub max_files_per_partition: usize,
    /// When true, older files are moved to an `archive/` subfolder.
    pub archive_old_files: bool,
}

impl RotationPolicy {
    /// Constructs a standard rotation policy with the given partition capacity.
    pub fn new(max_files_per_partition: usize, archive_old_files: bool) -> Self {
        Self {
            max_files_per_partition: max_files_per_partition.max(10),
            archive_old_files,
        }
    }

    /// Enforces the policy on the specified partition directory.
    pub fn enforce(&self, partition_dir: &Path) -> Result<usize, String> {
        if !partition_dir.exists() {
            return Ok(0);
        }

        let mut entries = Vec::new();
        let read_dir = fs::read_dir(partition_dir)
            .map_err(|e| format!("Failed to read partition dir {:?}: {e}", partition_dir))?;

        for entry in read_dir.flatten() {
            let p = entry.path();
            if p.is_file() && !p.file_name().unwrap_or_default().to_string_lossy().starts_with('.') {
                entries.push(p);
            }
        }

        if entries.len() <= self.max_files_per_partition {
            return Ok(0);
        }

        // Sort chronologically by filename (timestamp is in prefix)
        entries.sort();

        let excess_count = entries.len() - self.max_files_per_partition;
        let mut rotated = 0;

        let archive_dir = partition_dir.join("archive");
        if self.archive_old_files && !archive_dir.exists() {
            fs::create_dir_all(&archive_dir)
                .map_err(|e| format!("Failed to create archive dir {:?}: {e}", archive_dir))?;
        }

        for file_path in entries.iter().take(excess_count) {
            if self.archive_old_files {
                let file_name = file_path.file_name().unwrap();
                let dest = archive_dir.join(file_name);
                if fs::rename(file_path, &dest).is_ok() {
                    rotated += 1;
                }
            } else if fs::remove_file(file_path).is_ok() {
                rotated += 1;
            }
```

```
        }

        Ok(rotated)
    }
}

impl Default for RotationPolicy {
    /// Default storehouse policy: 1000 files per partition with archival.
    fn default() -> Self {
        Self::new(1000, true)
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/inscriber/scroll_writer.rs

RS | 133 LINES | 460 WORDS | 5.3 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Canonical 4-Block OmniCode .scroll Inscription Engine )
// ============================================================================
//! Canonical Scroll Inscription Engine
//!
//! Formats and physically inscribes executable 4-Block OmniCode scrolls.

use std::fs;
use std::path::{Path, PathBuf};
use super::super::telemetry::CognitiveNote;

/// Inscribes a canonical 4-Block .scroll file to the target path.
pub fn inscribe_canonical_scroll(
    path: &Path,
    session_id: &str,
    prompt: &str,
    synthesized_omnicode: &str,
    state_str: &str,
    response: &str,
    elapsed_micros: u128,
) -> Result<PathBuf, String> {
    if let Some(parent) = path.parent() {
        if !parent.exists() {
            fs::create_dir_all(parent).map_err(|e| {
                format!("Failed to create scroll parent directory: {e}")
            })?;
        }
    }

    let indented_reel = synthesized_omnicode
        .lines()
        .map(|l| format!("        {l}"))
        .collect::<Vec<_>>()
        .join("\n");

    let scroll_content = format!(
r#"# ============================================================================
# BLOCK 1: METADATA BLOCK (THE COGNITIVE SCROLL)
# ( Execution Trace ID, Prompt Intent, Inferred Types, and Neural Snapshot )
# ============================================================================
Scroll < EpistemicTrace.{session_id} > ( {prompt} ) {{
    version: < "1.0.0" >,
    system: < OmniCode.AI.Model >,
    session_id: < "{session_id}" >,
    execution_duration_micros: < {elapsed_micros} >,
    cognitive_mode: < NeuralSymbolicTransduction >
}}

# ============================================================================
# BLOCK 2: OPENING BLOCK (EXPERIENCE INITIALIZATION)
# ( Hardware Invariants, Preconditions, and Initial Context )
# ============================================================================
Opening {{
    import: [ Core.Arithmetic :: Core.Logic :: Core.Vectors ],
    preconditions: [ +1 ]
}}

user_prompt < "{prompt}" >

# ============================================================================
# BLOCK 3: BODY BLOCK (CHRONICLE OF EXECUTION & THOUGHT REEL)
# ( Replay Tape: Synthesized Program, Sensory Telemetry & Immune Interventions )
# ============================================================================
Body [
    # Executed Turing Reel Synthesized by AI Model:
    synthesized_reel [
{indented_reel}
    ]
]

# ============================================================================
# BLOCK 4: CLOSING BLOCK (EPISODIC COMMIT & LEARNING PROOF)
```

```
# ( Verification Proof, Final Quad-State, and Conversational Synthesis )
# ================================================================================
Closing {{
    commit_status [ <{state_str}> ],
    machine_utterance ( "{sanitized_response}" )
}}
"#,
        session_id = session_id,
        prompt = prompt,
        elapsed_micros = elapsed_micros,
        indented_reel = indented_reel,
        state_str = state_str,
        sanitized_response = response.replace('"', "\\\"")
    );

    fs::write(path, scroll_content)
        .map_err(|e| format!("Failed to write scroll to {:?}: {e}", path))?;

    Ok(path.to_path_buf())
}

/// Inscribes a complete cognitive audit scroll containing multiple notes.
pub fn inscribe_audit_scroll(
    notes: &[CognitiveNote],
    failpoints_count: usize,
) -> String {
    let mut out = String::new();
    out.push_str("# ================================================================================\n");
    out.push_str("# BLOCK 1: METADATA BLOCK\n");
    out.push_str("# ( Episodic AI Cognitive Memory Scroll & Incident Audit Log )\n");
    out.push_str("# ================================================================================\n");
    out.push_str("Scroll < CognitiveMemory.Audit > {\n");
    out.push_str(&format!("    total_notes: < {} >,\n", notes.len()));
    out.push_str(&format!("    total_failpoints: < {} >\n", failpoints_count));
    out.push_str("}\n\n");
    out.push_str("# ================================================================================\n");
    out.push_str("# BLOCK 2: OPENING BLOCK\n");
    out.push_str("# ( Cognitive Context & Invariant Preconditions )\n");
    out.push_str("# ================================================================================\n");
    out.push_str("Opening {\n    preconditions: [ +1 ]\n}\n\n");
    out.push_str("# ================================================================================\n");
    out.push_str("# BLOCK 3: BODY BLOCK\n");
    out.push_str("# ( Episodic Traces & Memory Units Recorded During Execution )\n");
    out.push_str("# ================================================================================\n");
    out.push_str("Body [\n");
    for n in notes {
        out.push_str(&format!(
            "    {}\n\n",
            n.format_as_omnicode().replace('\n', "\n    ")
        ));
    }
    out.push_str("]\n\n");
    out.push_str("# ================================================================================\n");
    out.push_str("# BLOCK 4: CLOSING BLOCK\n");
    out.push_str("# ( Cognitive Audit Verification Proof )\n");
    out.push_str("# ================================================================================\n");
    out.push_str("Closing {\n    audit_verified: [ PROCEED ]\n}\n");
    out
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/telemetry/frame.rs

RS | 82 LINES | 263 WORDS | 2.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( RollFrame Telemetry Struct: Deterministic Game-Dev State Vector )
// ============================================================================
//! RollFrame Structured Telemetry
//!
//! Encapsulates discrete tick-by-tick state vectors captured during process
//! tape stepping, recording dual-rail bitplanes, roll verbs, and QuadStates.

use crate::core::ternary::QuadState;

/// Single execution frame captured during roll traversal.
#[derive(Debug, Clone, PartialEq, Eq)]
pub struct RollFrame {
    /// Monotonic elapsed microseconds at roll execution.
    pub tick_micros: u128,
    /// 1-based roll sequence index.
    pub roll_index: usize,
    /// Total rolls declared on this tape ribbon.
    pub total_rolls: usize,
    /// Active operational verb (e.g. "INSCRIBE", "TRANSDUCE", "COMPARE").
    pub verb: String,
    /// Input substrate state as (positive_rail, negative_rail) bitplanes.
    pub dual_rail_in: (u64, u64),
    /// Output substrate state as (positive_rail, negative_rail) bitplanes.
    pub dual_rail_out: (u64, u64),
    /// Fourfold execution state committed by this roll.
    pub quad_state: QuadState,
    /// Compact bitmask representing trapped failpoints (0 = clean).
    pub failpoint_mask: u32,
    /// First-class human/machine intent aside attached to the roll.
    pub intent_aside: Option<String>,
}

impl RollFrame {
    /// Constructs a new [`RollFrame`].
    pub fn new(
        tick_micros: u128,
        roll_index: usize,
        total_rolls: usize,
        verb: impl Into<String>,
        dual_rail_in: (u64, u64),
        dual_rail_out: (u64, u64),
        quad_state: QuadState,
        failpoint_mask: u32,
        intent_aside: Option<String>,
    ) -> Self {
        Self {
            tick_micros,
            roll_index,
            total_rolls,
            verb: verb.into(),
            dual_rail_in,
            dual_rail_out,
            quad_state,
            failpoint_mask,
            intent_aside,
        }
    }

    /// Formats the frame as a compact structured telemetry row.
    pub fn format_row(&self) -> String {
        let aside_str = self
            .intent_aside
            .as_deref()
            .map(|a| format!(" ({a})"))
            .unwrap_or_default();
        format!(
            "[{:>6} µs] Roll {}/{}: {:<10} Rails: ({:#018x}, {:#018x}) -> State: {:<8} Mask: {:#010x}{}",
            self.tick_micros,
            self.roll_index,
            self.total_rolls,
            self.verb,
```

```
            self.dual_rail_out.0,
            self.dual_rail_out.1,
            self.quad_state.macro_op(),
            self.failpoint_mask,
            aside_str
        )
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/telemetry/mod.rs

RS | 14 LINES | 45 WORDS | 0.4 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Telemetry Subsystem Re-exports & Frame Facade )
// ============================================================================
//! Telemetry Subsystem: Frames, Notes & In-Memory Flight Recorder

pub mod frame;
pub mod note;
pub mod ring_buffer;

pub use frame::RollFrame;
pub use note::CognitiveNote;
pub use ring_buffer::FlightRecorder;
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/telemetry/note.rs

RS | 79 LINES | 305 WORDS | 3.0 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Structured Cognitive Memory Notes Formatted for AI Models & IDE Hover )
// ============================================================================
//! Structured Epistemic Memory Note
//!
//! Provides dual-readable semantic notes formatted for neural-symbolic AI
//! context windows, episodic memory reels, and language server tooltips.

/// Structured epistemic memory note formatted for neural-symbolic AI models.
#[derive(Debug, Clone, PartialEq, Eq)]
pub struct CognitiveNote {
    /// Monotonic timestamp in microseconds since logger initialization.
    pub timestamp_micros: u128,
    /// Epistemic category: e.g. "OBSERVATION", "HYPOTHESIS", "INCIDENT".
    pub category: String,
    /// High-level single-sentence summary of the cognitive observation.
    pub summary: String,
    /// In-depth architectural details, telemetry data, or remediation rationale.
    pub details: String,
    /// Semantic taxonomy tags for associative memory indexing.
    pub tags: Vec<String>,
    /// Optional code snippet or token context under active observation.
    pub context_snippet: Option<String>,
}

impl CognitiveNote {
    /// Formats this note as an OmniCode native dual-readable syntax block.
    pub fn format_as_omnicode(&self) -> String {
        let tag_str = if self.tags.is_empty() {
            "[]".to_string()
        } else {
            format!(
                "[ {} ]",
                self.tags
                    .iter()
                    .map(|t| format!("#{t}"))
                    .collect::<Vec<_>>()
                    .join(" :: ")
            )
        };
        let ctx_str = if let Some(c) = &self.context_snippet {
            format!("\n    context: < {:?} >", c)
        } else {
            String::new()
        };
        format!(
            "Note < CognitiveTrace > {{\n    tick: < {} µs >,\n    category: [ {} ],\n    summary: < {:?} >,\n    details: < {:?} >,\n    tags: {}{}\n}}",
            self.timestamp_micros,
            self.category,
            self.summary,
            self.details,
            tag_str,
            ctx_str
        )
    }

    /// Formats this note as a Markdown block specifically structured for prompts.
    pub fn format_as_memory_entry(&self) -> String {
        let tag_list = if self.tags.is_empty() {
            "none".to_string()
        } else {
            self.tags
                .iter()
                .map(|t| format!("#{t}"))
                .collect::<Vec<_>>()
                .join(", ")
        };
        let mut out = format!(
            "### [EPISODIC_MEMORY_TRACE: {}]\n- **Timestamp:** {} µs\n- **Summary:** {}\n- **Details:** {}\n- **Tags:** {}\n",
            self.category, self.timestamp_micros, self.summary, self.details, tag_list
```

```
        );
        if let Some(ctx) = &self.context_snippet {
            out.push_str(&format!("- **Context:** `{}`\n", ctx));
        }
        out
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/telemetry/ring_buffer.rs

RS | 95 LINES | 313 WORDS | 3.0 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( FlightRecorder: Fixed-Capacity Circular Buffer for Deterministic Replay )
// ============================================================================
//! In-Memory Flight Recorder (Circular Telemetry Ring Buffer)
//!
//! Stores the last $K$ execution frames in memory with zero allocations in
//! steady-state, allowing instantaneous post-mortem crash inspection.

use super::frame::RollFrame;
use crate::core::ternary::QuadState;

/// In-memory circular telemetry buffer.
#[derive(Debug, Clone)]
pub struct FlightRecorder {
    frames: Vec<RollFrame>,
    capacity: usize,
    write_head: usize,
    total_inscribed: usize,
}

impl FlightRecorder {
    /// Constructs a new [`FlightRecorder`] with the specified frame capacity.
    pub fn new(capacity: usize) -> Self {
        let cap = capacity.max(16);
        Self {
            frames: Vec::with_capacity(cap),
            capacity: cap,
            write_head: 0,
            total_inscribed: 0,
        }
    }

    /// Inscribes a new frame into the circular buffer.
    pub fn record_frame(&mut self, frame: RollFrame) {
        if self.frames.len() < self.capacity {
            self.frames.push(frame);
        } else {
            self.frames[self.write_head] = frame;
        }
        self.write_head = (self.write_head + 1) % self.capacity;
        self.total_inscribed += 1;
    }

    /// Returns a chronological snapshot of the most recent `count` frames.
    pub fn recent_frames(&self, count: usize) -> Vec<RollFrame> {
        let available = self.frames.len();
        let take = count.min(available);
        if take == 0 {
            return Vec::new();
        }

        let mut result = Vec::with_capacity(take);
        if available < self.capacity {
            let start = available.saturating_sub(take);
            result.extend_from_slice(&self.frames[start..available]);
        } else {
            for i in 0..take {
                let idx = (self.write_head + self.capacity - take + i)
                    % self.capacity;
                result.push(self.frames[idx].clone());
            }
        }
        result
    }

    /// Returns the last frame that resulted in a rollback or failpoint.
    pub fn last_anomalous_frame(&self) -> Option<RollFrame> {
        for frame in self.recent_frames(self.frames.len()).into_iter().rev() {
            if frame.quad_state == QuadState::Rollback || frame.failpoint_mask != 0 {
                return Some(frame);
            }
        }
```

```
        None
    }

    /// Total count of frames inscribed over the lifetime of the recorder.
    pub fn total_inscribed(&self) -> usize {
        self.total_inscribed
    }

    /// Clears the flight recorder.
    pub fn clear(&mut self) {
        self.frames.clear();
        self.write_head = 0;
        self.total_inscribed = 0;
    }
}

impl Default for FlightRecorder {
    fn default() -> Self {
        Self::new(512)
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/failpoint/mod.rs

RS | 12 LINES | 38 WORDS | 0.4 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Failpoint Subsystem Re-exports & Diagnostics Facade )
// ============================================================================
//! Failpoint Pathology & Remediation Telemetry Module

pub mod types;
pub mod remediation;

pub use types::FailpointType;
pub use remediation::{FixKind, FixSuggestion};
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/failpoint/remediation.rs

RS | 45 LINES | 235 WORDS | 2.0 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Machine-Applicable Automated Repair Kinds & Concrete Fix Suggestions )
// ============================================================================
//! OmniCode Diagnostics: Concrete Automated Remediation Telemetry
//!
//! Encapsulates machine-applicable patch descriptions allowing the
//! Restorator or AI coding agents to heal broken source files in place.

/// Categories of automated restorative repairs executed by Restorator.
#[derive(Debug, Clone, PartialEq, Eq)]
pub enum FixKind {
    /// Append a missing closing boundary delimiter (e.g. closing `[` with `]`).
    CloseBoundary,
    /// Substitute erroneous closing delimiter with matching opening partner.
    FixBoundaryMismatch,
    /// Inject missing canonical 4-Block architecture scaffolding headers.
    AddBlockHeader,
    /// Automatically inject missing core library imports (Core.Arithmetic, etc).
    AddImport,
    /// Synthesize and declare an inferred conceptual noun entity.
    DeclareEntityWithInfer,
    /// Modify or satisfy an adversative caveat expression.
    AdjustCaveat,
    /// Convert an immutable Rank 1 invariant `< ... >` into mutable `[ ... ]`.
    ConvertImmutableToMutable,
}

/// Concrete remediation telemetry attached to a failpoint event.
#[derive(Debug, Clone, PartialEq, Eq)]
pub struct FixSuggestion {
    /// Categorical classification of the automated remediation.
    pub kind: FixKind,
    /// 1-based source line number where remediation should be applied.
    pub line: usize,
    /// 1-based source column number where the target token resides.
    pub col: usize,
    /// The erroneous or missing token sequence targeted for replacement.
    pub target_token: String,
    /// The proposed patch or substitution string that seals the invariant.
    pub suggested_patch: String,
    /// Human-readable and AI-interpretable rationale explaining the fix.
    pub rationale: String,
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/failpoint/types.rs

RS | 61 LINES | 276 WORDS | 2.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Failpoint Pathology Categorization & Invariant Anomaly Enums )
// ============================================================================
//! OmniCode Diagnostics: Failpoint Pathology Taxonomy
//!
//! Unlike conventional exceptions that panic process execution, OmniCode
//! treats failpoints as first-class diagnostic signals that guide rollback,
//! caveat evaluation, or autonomous immune restoration via the Restorator.

/// Classifications of trapped failpoints and boundary anomalies.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum FailpointType {
    /// Delimiter mismatch: opened with one delimiter class, closed with another.
    BoundaryMismatch,
    /// Unclosed boundary delimiter reaching EOF without matching partner.
    BoundaryLeak,
    /// Execution attempted to evaluate void/null state without resolving caveat.
    NullTrap,
    /// An operation or caveat evaluation triggered state rollback (-1:ROLLBACK).
    RollbackTriggered,
    /// An adversative caveat condition (! [ ... ]) vetoed active state.
    CaveatVeto,
    /// Illegal attempt to mutate an immutable Rank 1 invariant axiom < ... >.
    ImmutableMutation,
    /// Recursive or cyclic retroaction loop exceeding debugger threshold.
    CyclicRetroaction,
    /// Structural or syntactic grammar anomaly violating language invariants.
    SyntaxAnomaly,
}

impl FailpointType {
    /// Returns the uppercase canonical string identifier for this failpoint.
    pub fn as_str(&self) -> &'static str {
        match self {
            FailpointType::BoundaryMismatch => "FP_BOUNDARY_MISMATCH",
            FailpointType::BoundaryLeak => "FP_BOUNDARY_LEAK",
            FailpointType::NullTrap => "FP_NULL_TRAP",
            FailpointType::RollbackTriggered => "FP_ROLLBACK_TRIGGERED",
            FailpointType::CaveatVeto => "FP_CAVEAT_VETO",
            FailpointType::ImmutableMutation => "FP_IMMUTABLE_MUTATION",
            FailpointType::CyclicRetroaction => "FP_CYCLIC_RETROACTION",
            FailpointType::SyntaxAnomaly => "FP_SYNTAX_ANOMALY",
        }
    }

    /// Compact single-bit representation for game-dev flight recorder masks.
    pub fn bitmask(&self) -> u32 {
        match self {
            FailpointType::BoundaryMismatch => 1 << 0,
            FailpointType::BoundaryLeak => 1 << 1,
            FailpointType::NullTrap => 1 << 2,
            FailpointType::RollbackTriggered => 1 << 3,
            FailpointType::CaveatVeto => 1 << 4,
            FailpointType::ImmutableMutation => 1 << 5,
            FailpointType::CyclicRetroaction => 1 << 6,
            FailpointType::SyntaxAnomaly => 1 << 7,
        }
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/query/index.rs

RS | 32 LINES | 139 WORDS | 1.2 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( IndexedSession Data Structure for Fast Episodic Retrieval )
// ============================================================================
//! Indexed Episode Metadata Definition

use std::path::PathBuf;
use crate::core::ternary::QuadState;

/// High-level indexed record representing a past execution episode.
#[derive(Debug, Clone, PartialEq, Eq)]
pub struct IndexedSession {
    /// Unique session identifier string.
    pub session_id: String,
    /// Monotonic timestamp in microseconds since epoch.
    pub timestamp_micros: u128,
    /// Domain category (e.g. "character", "number", "sessions", "cortex").
    pub category: String,
    /// Final fourfold commit state.
    pub final_state: QuadState,
    /// Number of failpoints trapped during execution.
    pub failpoint_count: usize,
    /// Number of automated repairs applied by Restorator.
    pub repair_count: usize,
    /// Path to the native .scroll file.
    pub scroll_path: PathBuf,
    /// Path to the traditional .log file if present.
    pub log_path: Option<PathBuf>,
    /// Natural language or execution prompt that initiated the run.
    pub prompt: String,
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/query/mod.rs RS 12 LINES 36 WORDS 0.4 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Episodic Query Subsystem Re-exports )
// ============================================================================
//! Episodic Query Subsystem: Indexing & Fast Retrieval

pub mod index;
pub mod search;

pub use index::IndexedSession;
pub use search::EpisodicQueryEngine;
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/query/search.rs

RS | 273 LINES | 798 WORDS | 9.0 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( EpisodicQueryEngine: O(1) Lookup & Partitioned Range Search )
// ============================================================================
//! Episodic Query Engine
//!
//! Indexes and queries past execution scrolls and telemetry without linear
//! file scans, supporting filtering by session, category, QuadState, and time.

use std::collections::HashMap;
use std::fs;
use std::path::{Path, PathBuf};
use super::index::IndexedSession;
use crate::core::ternary::QuadState;

/// High-performance query engine for episodic memory storehouses.
#[derive(Debug, Clone, Default)]
pub struct EpisodicQueryEngine {
    sessions: Vec<IndexedSession>,
    by_session_id: HashMap<String, usize>,
    by_category: HashMap<String, Vec<usize>>,
}

impl EpisodicQueryEngine {
    /// Constructs an empty [`EpisodicQueryEngine`].
    pub fn new() -> Self {
        Self::default()
    }

    /// Indexes all `.scroll` files located under `root_dir`.
    pub fn index_directory(
        &mut self,
        root_dir: &Path,
    ) -> Result<usize, String> {
        self.sessions.clear();
        self.by_session_id.clear();
        self.by_category.clear();

        if !root_dir.exists() {
            return Ok(0);
        }

        let scroll_paths = collect_scroll_files(root_dir);
        let mut count = 0;

        for path in scroll_paths {
            if let Some(session) = parse_indexed_session(&path) {
                let idx = self.sessions.len();
                self.by_session_id
                    .insert(session.session_id.clone(), idx);
                self.by_category
                    .entry(session.category.clone())
                    .or_default()
                    .push(idx);
                self.sessions.push(session);
                count += 1;
            }
        }

        // Sort chronologically
        self.sessions.sort_by_key(|s| s.timestamp_micros);
        // Rebuild session ID map after sort with multi-key aliases
        self.by_session_id.clear();
        self.by_category.clear();
        for (idx, s) in self.sessions.iter().enumerate() {
            self.by_session_id.insert(s.session_id.clone(), idx);
            if let Some(stem) = s
                .scroll_path
                .file_stem()
                .and_then(|t| t.to_str())
            {
                self.by_session_id.insert(stem.to_string(), idx);
                let parts: Vec<&str> = stem.split('_').collect();
```

```
                if parts.len() >= 3 {
                    self.by_session_id.insert(parts[1..].join("_"), idx);
                    self.by_session_id.insert(parts[2..].join("_"), idx);
                }
            }
            self.by_category
                .entry(s.category.clone())
                .or_default()
                .push(idx);
        }

        Ok(count)
    }

    /// Finds an episode by its exact session ID in O(1) time.
    pub fn find_by_session(&self, session_id: &str) -> Option<&IndexedSession> {
        let idx = *self.by_session_id.get(session_id)?;
        self.sessions.get(idx)
    }

    /// Filters all episodes belonging to a specific domain category.
    pub fn filter_by_category(&self, category: &str) -> Vec<&IndexedSession> {
        if let Some(indices) = self.by_category.get(category) {
            indices.iter().filter_map(|&i| self.sessions.get(i)).collect()
        } else {
            Vec::new()
        }
    }

    /// Filters episodes by their commit QuadState.
    pub fn filter_by_state(&self, state: QuadState) -> Vec<&IndexedSession> {
        self.sessions
            .iter()
            .filter(|s| s.final_state == state)
            .collect()
    }

    /// Filters episodes that experienced failpoints.
    pub fn filter_by_failpoint(
        &self,
        has_failpoints: bool,
    ) -> Vec<&IndexedSession> {
        self.sessions
            .iter()
            .filter(|s| (s.failpoint_count > 0) == has_failpoints)
            .collect()
    }

    /// Range scans episodes executed between `start_micros` and `end_micros`.
    pub fn range_scan(
        &self,
        start_micros: u128,
        end_micros: u128,
    ) -> Vec<&IndexedSession> {
        self.sessions
            .iter()
            .filter(|s| {
                s.timestamp_micros >= start_micros
                    && s.timestamp_micros <= end_micros
            })
            .collect()
    }

    /// Returns a slice of all indexed sessions.
    pub fn all_sessions(&self) -> &[IndexedSession] {
        &self.sessions
    }
}

/// Recursively collects all `.scroll` files within `dir`.
fn collect_scroll_files(dir: &Path) -> Vec<PathBuf> {
    let mut files = Vec::new();
    if let Ok(entries) = fs::read_dir(dir) {
        for entry in entries.flatten() {
            let p = entry.path();
            if p.is_dir() {
                files.extend(collect_scroll_files(&p));
            } else if p.extension().and_then(|e| e.to_str()) == Some("scroll") {
```

```
                files.push(p);
            }
        }
    }
    files
}

/// Parses an `IndexedSession` from a single `.scroll` file.
fn parse_indexed_session(path: &Path) -> Option<IndexedSession> {
    let content = fs::read_to_string(path).ok()?;
    let mut session_id = "unknown".to_string();
    let mut prompt = String::new();
    let mut final_state = QuadState::Proceed;
    let mut failpoint_count = 0;
    let mut repair_count = 0;
    let mut timestamp_micros = 0u128;

    for line in content.lines() {
        let trimmed = line.trim();
        if trimmed.starts_with("session_id:") {
            if let Some(sq) = trimmed.find('"') {
                if let Some(eq) = trimmed.rfind('"') {
                    if sq < eq {
                        session_id = trimmed[sq + 1..eq].to_string();
                    }
                }
            }
        } else if trimmed.starts_with("timestamp:") {
            if let Some(sq) = trimmed.find('"') {
                if let Some(eq) = trimmed.rfind('"') {
                    if sq < eq {
                        let ts_str = &trimmed[sq + 1..eq];
                        if let Some(first) = ts_str.split('_').next() {
                            timestamp_micros = first.parse().unwrap_or(0);
                        }
                    }
                }
            }
        } else if trimmed.starts_with("user_prompt") {
            if let Some(sq) = trimmed.find('"') {
                if let Some(eq) = trimmed.rfind('"') {
                    if sq < eq {
                        prompt = trimmed[sq + 1..eq].to_string();
                    }
                }
            }
        } else if prompt.is_empty()
            && trimmed.starts_with("Scroll < EpistemicTrace")
        {
            if let Some(open_p) = trimmed.find('(') {
                if let Some(close_p) = trimmed.rfind(')') {
                    if open_p < close_p {
                        prompt = trimmed[open_p + 1..close_p]
                            .trim()
                            .to_string();
                    }
                }
            }
        } else if trimmed.starts_with("commit_status [") {
            if trimmed.contains("<PROCEED>") {
                final_state = QuadState::Proceed;
            } else if trimmed.contains("<ROLLBACK>") {
                final_state = QuadState::Rollback;
            } else if trimmed.contains("<AWAIT>") {
                final_state = QuadState::Await;
            } else if trimmed.contains("<HALT>") {
                final_state = QuadState::Halt;
            }
        } else if trimmed.starts_with("failpoint_record [") {
            failpoint_count += 1;
        } else if trimmed.starts_with("repair_entry [") {
            repair_count += 1;
        }
    }

    // Determine category from path or prompt
    let path_str = path.to_string_lossy();
    let category = if path_str.contains("/character/")
```

```
        || prompt.contains("character")
    {
        "character".to_string()
    } else if path_str.contains("/number/") || prompt.contains("number") {
        "number".to_string()
    } else if path_str.contains("/sessions/prompts")
        || (!prompt.trim().is_empty() && path_str.contains("/sessions/"))
    {
        "sessions/prompts".to_string()
    } else if path_str.contains("/sessions/")
        || session_id.starts_with("sess_")
    {
        "sessions/system".to_string()
    } else {
        "cortex".to_string()
    };

    // Locate paired log file
    let mut log_path = path.to_path_buf();
    log_path.set_extension("log");
    let paired_log = if log_path.exists() {
        Some(log_path)
    } else if path_str.contains("/scroll/") {
        let alt = PathBuf::from(path_str.replace("/scroll/", "/log/"));
        let mut alt_log = alt;
        alt_log.set_extension("log");
        if alt_log.exists() { Some(alt_log) } else { None }
    } else {
        None
    };

    Some(IndexedSession {
        session_id,
        timestamp_micros,
        category,
        final_state,
        failpoint_count,
        repair_count,
        scroll_path: path.to_path_buf(),
        log_path: paired_log,
        prompt,
    })
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/universal/bus.rs

RS | 96 LINES | 305 WORDS | 3.2 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Diagnostic Event Bus, Channel Stream & Live Terminal Mirroring )
// ============================================================================
//! Diagnostic Event Bus & Telemetry Event Definitions

use std::sync::{Arc, Mutex};
use super::super::failpoint::{FailpointType, FixSuggestion};
use super::super::telemetry::CognitiveNote;

/// Individual diagnostic event recorded during execution ticks.
#[derive(Debug, Clone)]
pub struct LogEvent {
    /// Microseconds elapsed since logger initialization.
    pub elapsed_micros: u128,
    /// Channel or subsystem tag (e.g. "BOUNDARY", "DEBUGGER", "TERNARY").
    pub channel: &'static str,
    /// Descriptive message explaining the operation or signal.
    pub message: String,
    /// True if this event represents an intercepted failpoint or anomaly.
    pub is_failpoint: bool,
    /// The specific failpoint category if `is_failpoint` is true.
    pub failpoint_type: Option<FailpointType>,
    /// Concrete remediation suggestion if an automated repair is available.
    pub suggestion: Option<FixSuggestion>,
    /// Accompanying structured cognitive memory note for AI ingestion.
    pub cognitive_note: Option<CognitiveNote>,
}

/// Thread-safe event bus coordinating live diagnostic streams.
#[derive(Debug, Clone)]
pub struct EventBus {
    events: Arc<Mutex<Vec<LogEvent>>>,
    failpoints: Arc<Mutex<Vec<LogEvent>>>,
    print_live: bool,
}

impl EventBus {
    /// Constructs a new [`EventBus`].
    pub fn new(print_live: bool) -> Self {
        Self {
            events: Arc::new(Mutex::new(Vec::new())),
            failpoints: Arc::new(Mutex::new(Vec::new())),
            print_live,
        }
    }

    /// Emits a general trace event to the bus.
    pub fn emit(&self, event: LogEvent) {
        if self.print_live {
            if event.is_failpoint {
                let kind_str = event
                    .failpoint_type
                    .map(|f| f.as_str())
                    .unwrap_or("FAILPOINT");
                eprintln!(
                    "[{:>6} µs] \x1b[91mCRITICAL\x1b[0m [{}] [{}] {}",
                    event.elapsed_micros, event.channel, kind_str, event.message
                );
            } else {
                println!(
                    "[{:>6} µs] DEBUG    [{}] {}",
                    event.elapsed_micros, event.channel, event.message
                );
            }
        }

        if event.is_failpoint {
            self.failpoints.lock().unwrap().push(event.clone());
        }
        self.events.lock().unwrap().push(event);
    }

```

```
    /// Returns a cloned snapshot of all recorded events.
    pub fn all_events(&self) -> Vec<LogEvent> {
        self.events.lock().unwrap().clone()
    }

    /// Returns a cloned snapshot of all failpoints.
    pub fn all_failpoints(&self) -> Vec<LogEvent> {
        self.failpoints.lock().unwrap().clone()
    }

    /// Clears all events from the bus.
    pub fn clear(&self) {
        self.events.lock().unwrap().clear();
        self.failpoints.lock().unwrap().clear();
    }
}

impl Default for EventBus {
    fn default() -> Self {
        Self::new(false)
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/universal/clock.rs

RS | 56 LINES | 176 WORDS | 1.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Monotonic Clock, Microsecond Timers & Timestamp Generator )
// ============================================================================
//! Universal High-Precision Clock & Monotonic Timestamp Generator
//!
//! Provides nanosecond/microsecond resolution elapsed time offsets and
//! strictly monotonic timestamp identifiers for telemetry frame ordering.

use std::sync::atomic::{AtomicU64, Ordering};
use std::time::{Instant, SystemTime};

/// Generates a strictly unique, monotonic timestamp identifier.
///
/// Format: `<unix_epoch_micros>_<atomic_counter:04>`
pub fn generate_timestamp_id() -> String {
    static COUNTER: AtomicU64 = AtomicU64::new(0);
    let count = COUNTER.fetch_add(1, Ordering::Relaxed);
    let now = SystemTime::now()
        .duration_since(SystemTime::UNIX_EPOCH)
        .unwrap_or_default()
        .as_micros();
    format!("{now}_{count:04}")
}

/// Monotonic clock reference measuring microsecond elapsed durations.
#[derive(Debug, Clone)]
pub struct MonotonicClock {
    start: Instant,
}

impl MonotonicClock {
    /// Constructs a new [`MonotonicClock`] calibrated to the current instant.
    pub fn new() -> Self {
        Self {
            start: Instant::now(),
        }
    }

    /// Returns elapsed microseconds since clock initialization.
    pub fn elapsed_micros(&self) -> u128 {
        self.start.elapsed().as_micros()
    }

    /// Resets the base reference instant to now.
    pub fn reset(&mut self) {
        self.start = Instant::now();
    }
}

impl Default for MonotonicClock {
    fn default() -> Self {
        Self::new()
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/logger/universal/mod.rs

RS | 12 LINES | 40 WORDS | 0.4 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal Telemetry & Hardware Clock Re-exports )
// ============================================================================
//! Universal Clock, Bus & Hardware Telemetry Machinery

pub mod clock;
pub mod bus;

pub use clock::{MonotonicClock, generate_timestamp_id};
pub use bus::{LogEvent, EventBus};
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/cogs/mod.rs RS 32 LINES 132 WORDS 1.4 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal Cogs Module Identity & Mechanical Dynamic Primitives )
// ============================================================================
//! OmniCode Cogs: Dynamic Mechanical Primitives & Decoupled Functions
//!
//! Reusable single-purpose dynamic utilities shared across gears:
//! - Dynamic host platform detection & environment adaptation (`platform`)
//! - Universal invariant tripwires and diagnostic interceptors (`tripwire`)
//! - Cross-track runtime path resolution

pub mod platform;
pub mod tripwire;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Cog Declarations & Re-exports )
// ============================================================================
pub use platform::{HostPlatform, HostArch};
pub use tripwire::{Tripwire, TripwireError};

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Cog Implementations & Shared Primitives )
// ============================================================================

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification and Sealing )
// ============================================================================
// Cogs subsystem verified and sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/cogs/platform.rs RS 940 LINES 4296 WORDS 42.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Dynamic Host Platform Cog Manifest, Scheduling Contract & Tripwire Registry )
// ============================================================================
//! MODULE:              omnicode::cogs::platform
//! IDENTITY:            Dynamic Host Platform Adapter Cog
//! NATURE:              Dynamic Environmental Meshing (Runtime Host Adaptation & In-Waiting Symbiosis)
//! VERSION:             0.3.0
//! CREATED:             2026-10-11
//! LAST_SEALED:         2026-10-11
//! AUTHOR:              CreativeWorkzStudio LLC / ProfessorSeanEX
//! COVENANT:            Public Domain / MIT
//!
//! SCHEDULER:
//!   TRACK_PRIMARY:     <TRACK 1> : {Host Engine & Virtual Machine}
//!   TRACKS_TOUCHED:    [ <TRACK 0> : {Silicon & Bare-Metal Kernel}, <TRACK 1>, <TRACK 2> : {Engine Runtime & SVO},
<TRACK 3> : {Studio & Graphical IDE} ]
//!   PRIORITY:          TaskPriority::High
//!   CHANNEL:           Track::Kernel
//!
//! CONTRACT / WHO-WHAT-WHERE-WHY-HOW:
//!   WHO:               OmniCode Host Environmental Adapter & Hardware Abstraction Layer (HAL)
//!   WHAT:              Dynamically detect host OS and CPU architecture, resolve toolchains and hypervisors,
//!                      probe hardware virtualization acceleration, discover UEFI OVMF firmware blobs,
//!                      audit host display servers, and orchestrate tripwired subprocess execution.
//!   WHERE:             Runtime host environment (GNU/Linux, Apple macOS Darwin, Microsoft Windows NT, Generic POSIX)
//!   WHEN:              Evaluated at engine startup, CLI command dispatch, GUI studio launch, or bare-metal boot
inception.
//!   WHY:               Enable the "In-Waiting" symbiotic execution model: OmniCode is an autonomous
//!                      operating system and balanced-ternary language, but during incubation it executes
//!                      harmoniously on any host OS without hardcoding platform paths or failing when moved.
//!   HOW:               Balanced Ternary (+1:PROCEED host detected & certified, -1:ROLLBACK unsupported/missing, 0:AWAIT
probe)
//!
//! THE "IN-WAITING" SYMBIOTIC INCUBATION MODEL:
//!   OmniCode is not merely a programming language compiler; it is an entirely distinct computing paradigm,
//!   operating system, and balanced-ternary machine architecture. However, during its developmental incubation,
//!   engineers work inside conventional operating systems (Linux, macOS, Windows).
//!   This cog acts as the umbilical cord and Hardware Abstraction Layer (HAL):
//!   - Adapts to the host's native filesystem hierarchy (FHS vs Homebrew vs Windows Program Files).
//!   - Selects the correct hypervisor binary (`qemu-system-x86_64` vs `qemu-system-x86_64.exe`).
//!   - Selects native acceleration flags (`-enable-kvm` on Linux, `-accel hvf` on macOS, `-accel whpx` on Windows).
//!   - Resolves native graphical browser dispatchers (`xdg-open` vs `open` vs `cmd /C start`).
//!   - Detects headless display environments to prevent graphical crashes.
//!
//! GAME DEV IDEOLOGY (THE HAL & PHYSICS SIMULATION ANALOGY):
//!   In modern game engine architecture (e.g., Unreal, Unity, Godot), the game simulation tick (`Update()`)
//!   runs identically regardless of whether rendering is powered by DirectX 12, Metal, or Vulkan.
//!   In OmniCode:
//!   - The Core Simulation: Word32 balanced-ternary ALU, tape reels, SVO grammar, and QuadState causality.
//!   - The Platform Adapter (This Cog): The cross-platform driver layer abstracting host silicon and OS syscalls.
//!   - Tripwires: Spatial and temporal collision volumes. When an invariant fails (missing binary, unreadable
//!     KVM node, absent display server), the tripwire catches the collision, records frame telemetry to
//!     `DiagnosticLogger` and `OmniDebugger`, and passes remediation tokens to `Restorator` for autonomous self-healing.
//!
//! TOUCHES / SYSTEM & PROCESS FOOTPRINT:
//!   - DISPATCH:        Native browser openers (`xdg-open` on Linux, `open` on macOS, `cmd /C start` on Windows)
//!   - DISCOVERY:       Host filesystem firmware lookups (`/usr/share/qemu`, `/opt/homebrew`, `C:\Program Files\qemu`)
//!   - BINARIES:        Probes for `qemu-system-x86_64` vs `qemu-system-x86_64.exe` on host PATH
//!   - VIRTUALIZATION:  Probes `/dev/kvm` (Linux KVM), Hypervisor.framework (macOS HVF), WHPX (Windows), TCG (Fallback)
//!   - DISPLAY:         Probes `$DISPLAY`, `$WAYLAND_DISPLAY`, and window manager sessions for GUI capability.
//!   - PROCESSES:       Uniform child process spawning with standard stream capture and exit status checking.
//!
//! REQUIRES / HOST CAPABILITIES:
//!   - Rust `cfg!(target_os)` and `cfg!(target_arch)` target family introspection.
//!   - Subprocess execution capabilities (`std::process::Command`).
//!   - Filesystem metadata and permission inspection (`std::path::Path::exists`, `std::fs::OpenOptions`).
//!   - Environment variable inspection (`std::env::var_os`, `std::env::var`).
//!
//! TRIPWIRE REGISTRY:
//!   - TRIPWIRE_PLATFORM_PROBE       (Identification and verification of host platform plane)
//!   - TRIPWIRE_ARCH_SUPPORT         (Assertion of host CPU architecture compatibility with target)
//!   - TRIPWIRE_FIRMWARE_DISCOVERY   (Resolution and verification of valid OVMF firmware candidate)
//!   - TRIPWIRE_HYPERVISOR_AVAIL     (Assertion of hypervisor executable on host PATH)
```

```
//!   - TRIPWIRE_ACCEL_DEVICE         (Hardware virtualization node accessibility / permission check)
//!   - TRIPWIRE_DISPLAY_SERVER       (Assertion of active display server when GUI mode is requested)
//!   - TRIPWIRE_BROWSER_DISPATCH     (Successful handoff to host graphical browser)
//!   - TRIPWIRE_SUBPROCESS_EXEC      (Generic host child process execution and exit code verification)
//!
//! NAVIGATION GUIDE (HOW TO NAVIGATE AND EXTEND THIS MODULE):
//!   - Block 1 (Lines 1-90): Module Manifest, Incubation Philosophy, Game Dev Analogy, Tripwire Registry.
//!   - Block 2 (Lines 91-180): Scoped Imports, Multi-OS Firmware Matrices, Equilibrium Constants, HostArch Enum.
//!     * To add firmware search paths for a new Linux distro or BSD: edit `LINUX_OVMF_CANDIDATES` in Section 2.2.
//!     * To add a new CPU architecture: add a variant to `HostArch` in Section 2.4.
//!   - Block 3 (Lines 181-480): Body Block & Implementation Oracles.
//!     * 3.1: HostPlatform runtime classification, display names, and environment summary.
//!     * 3.2: Host PATH resolution (`resolve_in_path`) and hypervisor binary verification.
//!     * 3.3: Hardware virtualization acceleration probes (`has_hardware_acceleration`,
`assert_acceleration_supported`).
//!     * 3.4: Host display server & GUI environment oracles (`has_display_server`, `assert_display_server_available`).
//!     * 3.5: UEFI OVMF firmware search with telemetry and tripwires (`find_ovmf_firmware_with_telemetry`).
//!     * 3.6: Host process dispatch, child execution, and browser launching (`execute_host_command`).
//!   - Block 4 (Lines 481+): Unit tests verifying platform detection, binary resolution, PATH parsing, and telemetry.

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Scoped Imports, Environment Definitions, Search Matrices, Architecture & Constants )
// ============================================================================

// ----------------------------------------------------------------------------
// 2.1. Scoped Namespace Ingestion & System Imports
// ----------------------------------------------------------------------------
use std::env;
use std::fs::OpenOptions;
use std::path::{Path, PathBuf};
use std::process::{Command, Output};

use crate::cogs::tripwire::{Tripwire, TripwireError};
use crate::diagnostics::logger::{DiagnosticLogger, FailpointType, FixKind, FixSuggestion};

// ----------------------------------------------------------------------------
// 2.2. Multi-Platform Firmware Candidate Matrices & Search Registries
// ----------------------------------------------------------------------------
/// Canonical Linux OVMF UEFI firmware candidate search paths.
///
/// Covers major distribution layouts:
/// - Debian / Ubuntu: `/usr/share/ovmf/OVMF.fd`
/// - Arch Linux / Fedora / RHEL: `/usr/share/edk2-ovmf/x64/OVMF_CODE.fd`, `/usr/share/edk2/ovmf/OVMF_CODE.fd`
/// - NixOS / Alpine / OpenSUSE: `/usr/share/qemu/OVMF.fd`, `/usr/share/OVMF/OVMF_CODE_4M.fd`
pub const LINUX_OVMF_CANDIDATES: &[&str] = &[
    "/usr/share/qemu/OVMF.fd",
    "/usr/share/OVMF/OVMF_CODE_4M.fd",
    "/usr/share/ovmf/OVMF.fd",
    "/usr/share/edk2-ovmf/x64/OVMF_CODE.fd",
    "/usr/share/edk2/ovmf/OVMF_CODE.fd",
];

/// Canonical Apple macOS OVMF firmware search paths.
///
/// Covers Homebrew Apple Silicon (`/opt/homebrew`), Intel Mac (`/usr/local`),
/// and MacPorts (`/opt/local`) installations of QEMU:
pub const MACOS_OVMF_CANDIDATES: &[&str] = &[
    "/opt/homebrew/share/qemu/edk2-x86_64-code.fd",
    "/usr/local/share/qemu/edk2-x86_64-code.fd",
    "/opt/homebrew/Cellar/qemu/share/qemu/edk2-x86_64-code.fd",
    "/opt/local/share/qemu/edk2-x86_64-code.fd",
];

/// Canonical Microsoft Windows OVMF firmware search paths.
///
/// Covers standard 64-bit and 32-bit QEMU installer directories under `Program Files`:
pub const WINDOWS_OVMF_CANDIDATES: &[&str] = &[
    "C:\\Program Files\\qemu\\share\\edk2-x86_64-code.fd",
    "C:\\Program Files (x86)\\qemu\\share\\edk2-x86_64-code.fd",
    "C:\\qemu\\share\\edk2-x86_64-code.fd",
];

/// Fallback generic firmware search paths for unrecognized POSIX environments.
pub const FALLBACK_OVMF_CANDIDATES: &[&str] = &[
    "/usr/share/qemu/OVMF.fd",
    "/usr/local/share/qemu/OVMF.fd",
];
```

```rust

// ---------------------------------------------------------------------------
// 2.3. Initial Truth States & Equilibrium Platform Defaults
// ---------------------------------------------------------------------------
/// Default hypervisor binary for POSIX-compliant host environments.
pub const DEFAULT_UNIX_HYPERVISOR: &str = "qemu-system-x86_64";

/// Default hypervisor binary for Microsoft Windows host environments.
pub const DEFAULT_WINDOWS_HYPERVISOR: &str = "qemu-system-x86_64.exe";

/// Canonical Linux KVM device node for hardware virtualization.
pub const LINUX_KVM_DEVICE_NODE: &str = "/dev/kvm";

// ---------------------------------------------------------------------------
// 2.4. Host Silicon Architecture Typology
// ---------------------------------------------------------------------------
/// Physical host CPU instruction set architecture.
///
/// Identifies the silicon substrate upon which the host operating system executes.
/// Informs hypervisor hardware acceleration compatibility (e.g. KVM or HVF can only
/// be used when host architecture matches guest target architecture).
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum HostArch {
    /// 64-bit x86 architecture (AMD64 / Intel 64).
    X86_64,
    /// 64-bit ARM architecture (Apple Silicon M-series, AWS Graviton, Ampere Altra).
    Aarch64,
    /// 64-bit RISC-V architecture.
    RiscV64,
    /// Unidentified or unsupported host processor architecture.
    Unknown,
}

impl HostArch {
    /// Detects the host processor architecture at runtime using target architecture directives.
    pub fn current() -> Self {
        if cfg!(target_arch = "x86_64") {
            HostArch::X86_64
        } else if cfg!(target_arch = "aarch64") {
            HostArch::Aarch64
        } else if cfg!(target_arch = "riscv64") {
            HostArch::RiscV64
        } else {
            HostArch::Unknown
        }
    }

    /// Returns the human and machine readable designation of the CPU architecture.
    pub fn display_name(&self) -> &'static str {
        match self {
            HostArch::X86_64 => "x86_64 (AMD64 / Intel 64)",
            HostArch::Aarch64 => "aarch64 (ARM64 / Apple Silicon)",
            HostArch::RiscV64 => "riscv64 (RISC-V 64-Bit)",
            HostArch::Unknown => "unknown-arch (Generic Processor)",
        }
    }
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Dynamic Host Platform Implementation, Environmental Oracles & Process Dispatch )
// ============================================================================

// ---------------------------------------------------------------------------
// 3.1. Platform Runtime Detection & Classification
// ---------------------------------------------------------------------------
/// Host operating system classification for "In-Waiting" symbiotic execution.
///
/// Represents the physical runtime habitat in which the OmniCode host engine
/// and developer tooling incubate. Enables dynamic adaptation of hypervisors,
/// firmware paths, native process dispatchers, and hardware acceleration flags.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum HostPlatform {
    /// GNU/Linux host (KVM hardware virtualization, systemd/FHS filesystem layout).
    Linux,
    /// Apple macOS host (Darwin kernel, Hypervisor.framework / HVF, Homebrew paths).
    MacOS,
    /// Microsoft Windows host (NT kernel, PE32+ binaries, Windows Hypervisor Platform / WHPX).
```

```rust
    Windows,
    /// Unidentified or generic POSIX environment (BSD, Solaris, embedded runtime).
    Unknown,
}

impl HostPlatform {
    /// Dynamically detects the host operating system platform at runtime.
    ///
    /// Evaluates compile-time target family directives (`cfg!(target_os)`) while
    /// providing runtime verification hooks.
    pub fn current() -> Self {
        if cfg!(target_os = "linux") {
            HostPlatform::Linux
        } else if cfg!(target_os = "macos") {
            HostPlatform::MacOS
        } else if cfg!(target_os = "windows") {
            HostPlatform::Windows
        } else {
            HostPlatform::Unknown
        }
    }

    /// Detects the physical host CPU architecture.
    pub fn arch(&self) -> HostArch {
        HostArch::current()
    }

    /// Returns the canonical platform display title with incubation role.
    pub fn display_name(&self) -> &'static str {
        match self {
            HostPlatform::Linux => "GNU/Linux (Host Incubation Plane)",
            HostPlatform::MacOS => "Apple macOS (Darwin Incubation Plane)",
            HostPlatform::Windows => "Microsoft Windows (NT Incubation Plane)",
            HostPlatform::Unknown => "Generic Host Plane (Fallback Environment)",
        }
    }

    /// Returns the target operating system family name (`"unix"` or `"windows"`).
    pub fn target_os_family(&self) -> &'static str {
        match self {
            HostPlatform::Windows => "windows",
            _ => "unix",
        }
    }

    /// Returns `true` if the host platform adheres to POSIX standards (Linux, macOS, BSD).
    pub fn is_posix(&self) -> bool {
        !matches!(self, HostPlatform::Windows)
    }

    /// Returns `true` if the host platform is Microsoft Windows.
    pub fn is_windows(&self) -> bool {
        matches!(self, HostPlatform::Windows)
    }

    /// Returns `true` if the host platform is GNU/Linux.
    pub fn is_linux(&self) -> bool {
        matches!(self, HostPlatform::Linux)
    }

    /// Returns `true` if the host platform is Apple macOS Darwin.
    pub fn is_macos(&self) -> bool {
        matches!(self, HostPlatform::MacOS)
    }

    /// Produces a comprehensive, machine-readable diagnostic snapshot of the host habitat.
    ///
    /// Used by [`DiagnosticLogger`], [`crate::diagnostics::debugger::OmniDebugger`], and AI cortex
    /// to record environmental state in episodic logs.
    pub fn environment_summary(&self) -> String {
        format!(
            "HostPlatform: {} | Arch: {} | Family: {} | POSIX: {} | Accel: {} | Display: {}",
            self.display_name(),
            self.arch().display_name(),
            self.target_os_family(),
            self.is_posix(),
            self.has_hardware_acceleration(),
            self.has_display_server()
```

```
        )
    }
}

// ---------------------------------------------------------------------------
// 3.2. Host PATH Resolution & Toolchain Binary Oracles
// ---------------------------------------------------------------------------
impl HostPlatform {
    /// Searches the host system `PATH` environment variable for an executable by name.
    ///
    /// # Platform Mechanics:
    /// - Respects platform-specific path list separators (`:` on Unix/POSIX, `;` on Windows).
    /// - On Windows, automatically tests the filename with `.exe` if not already provided.
    /// - Validates that candidate files exist and are regular files.
    pub fn resolve_in_path(&self, binary: &str) -> Option<PathBuf> {
        let path_var = env::var_os("PATH")?;

        let candidate_names: Vec<String> = if self.is_windows() && !binary.ends_with(".exe") {
            vec![format!("{}.exe", binary), binary.to_string()]
        } else {
            vec![binary.to_string()]
        };

        for dir in env::split_paths(&path_var) {
            for name in &candidate_names {
                let candidate = dir.join(name);
                if candidate.is_file() {
                    return Some(candidate);
                }
            }
        }

        None
    }

    /// Returns the platform-appropriate primary hypervisor binary name.
    pub fn hypervisor_binary(&self) -> &'static str {
        match self {
            HostPlatform::Windows => DEFAULT_WINDOWS_HYPERVISOR,
            _ => DEFAULT_UNIX_HYPERVISOR,
        }
    }

    /// Returns an ordered list of candidate hypervisor executable names.
    pub fn hypervisor_candidates(&self) -> &'static [&'static str] {
        match self {
            HostPlatform::Windows => &[DEFAULT_WINDOWS_HYPERVISOR, "qemu.exe"],
            HostPlatform::Linux => &[DEFAULT_UNIX_HYPERVISOR, "qemu-kvm", "kvm"],
            HostPlatform::MacOS => &[DEFAULT_UNIX_HYPERVISOR],
            HostPlatform::Unknown => &[DEFAULT_UNIX_HYPERVISOR],
        }
    }

    /// Dynamically locates the first valid hypervisor binary present on the host system PATH.
    pub fn find_hypervisor_binary(&self) -> Option<PathBuf> {
        for &candidate in self.hypervisor_candidates() {
            if let Some(path) = self.resolve_in_path(candidate) {
                return Some(path);
            }
        }
        None
    }

    /// Asserts that a valid hypervisor binary is present and reachable on the host PATH.
    ///
    /// # Sensory Tripwire:
    /// Trips [`Tripwire::assert_binary_available`], recording a failpoint in the logger
    /// with actionable installation remediation for Linux, macOS, or Windows if missing.
    pub fn assert_hypervisor_available(
        &self,
        logger: &DiagnosticLogger,
    ) -> Result<PathBuf, TripwireError> {
        let binary = self.hypervisor_binary();

        match self.resolve_in_path(binary) {
            Some(resolved_path) => {
                logger.log(
                    "PLATFORM",
```

```
                    format!("Hypervisor binary verified on PATH: {:?}", resolved_path),
                );
                Ok(resolved_path)
            }
            None => {
                let install_hint = match self {
                    HostPlatform::Linux => "sudo apt install qemu-system-x86 (Debian/Ubuntu) or sudo pacman -S qemu-system-x86 (Arch)",
                    HostPlatform::MacOS => "brew install qemu (Homebrew) or port install qemu (MacPorts)",
                    HostPlatform::Windows => "winget install QEMU.QEMU or download from https://www.qemu.org/download/#windows",
                    HostPlatform::Unknown => "Install QEMU from your operating system package repository",
                };

                let suggestion = FixSuggestion {
                    kind: FixKind::AddImport,
                    line: 1,
                    col: 1,
                    target_token: binary.to_string(),
                    suggested_patch: install_hint.to_string(),
                    rationale: format!(
                        "Host hypervisor executable '{}' is required for bare-metal machine inception",
                        binary
                    ),
                };

                let err = Tripwire::trip_with_remediation(
                    logger,
                    "PLATFORM",
                    FailpointType::SyntaxAnomaly,
                    format!(
                        "Hypervisor binary '{}' not found on host PATH. Remediation: {}",
                        binary, install_hint
                    ),
                    suggestion,
                );
                Err(err)
            }
        }
    }
}

// ---------------------------------------------------------------------------
// 3.3. Virtualization Acceleration Oracles & Permission Probes
// ---------------------------------------------------------------------------
impl HostPlatform {
    /// Probes whether hardware virtualization acceleration is accessible on the host.
    ///
    /// # Physical Hardware Invariants:
    /// - **Linux**: Inspects existence and read/write accessibility of `/dev/kvm`.
    /// - **macOS**: Target family supports Hypervisor.framework (`hvf`) on Darwin when
    ///   running on matching architecture or Apple Silicon hypervisor.
    /// - **Windows**: Target family supports Windows Hypervisor Platform (`whpx`).
    pub fn has_hardware_acceleration(&self) -> bool {
        match self {
            HostPlatform::Linux => {
                let kvm_path = Path::new(LINUX_KVM_DEVICE_NODE);
                if !kvm_path.exists() {
                    return false;
                }
                // Verify read and write permissions to /dev/kvm
                OpenOptions::new()
                    .read(true)
                    .write(true)
                    .open(kvm_path)
                    .is_ok()
            }
            HostPlatform::MacOS => true,
            HostPlatform::Windows => false, // Conservative default; requires Hyper-V / WHPX feature check
            HostPlatform::Unknown => false,
        }
    }

    /// Asserts that hardware acceleration is available, logging telemetry or tripping an alert.
    ///
    /// # Game Dev Collision Volume Analogy:
    /// If an acceleration tripwire is armed, tripping here warns that execution will drop
    /// into software emulation (TCG), which incurs significant performance overhead.
```

```
    pub fn assert_acceleration_supported(
        &self,
        logger: &DiagnosticLogger,
    ) -> Result<bool, TripwireError> {
        let accel = self.has_hardware_acceleration();
        if accel {
            logger.log(
                "ACCELERATION",
                format!("Hardware virtualization acceleration active on {}", self.display_name()),
            );
            Ok(true)
        } else {
            logger.record_ai_observation(
                "ACCELERATION_ABSENT",
                "Hardware virtualization acceleration unavailable",
                "Falling back to Tiny Code Generator (TCG) software emulation",
                ["virtualization", "tcg", "fallback", "performance"].as_slice(),
                None,
            );
            Ok(false)
        }
    }

    /// Returns the recommended hypervisor command-line arguments for hardware acceleration.
    ///
    /// Falls back to pure TCG software emulation if acceleration is unavailable.
    pub fn recommended_accel_args(&self) -> &'static [&'static str] {
        match self {
            HostPlatform::Linux if self.has_hardware_acceleration() => &["-enable-kvm"],
            HostPlatform::MacOS => &["-accel", "hvf"],
            HostPlatform::Windows if self.has_hardware_acceleration() => &["-accel", "whpx"],
            _ => &["-accel", "tcg"],
        }
    }
}

// ---------------------------------------------------------------------------
// 3.4. Host Display Server & Graphical Subsystem Oracles
// ---------------------------------------------------------------------------
impl HostPlatform {
    /// Probes whether a graphical display server or window manager is active on the host.
    ///
    /// Prevents GUI window spawn crashes when running in headless environments
    /// (e.g. continuous integration servers, SSH remote sessions, or containers).
    pub fn has_display_server(&self) -> bool {
        match self {
            HostPlatform::Linux | HostPlatform::Unknown => {
                env::var("DISPLAY").is_ok() || env::var("WAYLAND_DISPLAY").is_ok()
            }
            HostPlatform::MacOS => {
                // macOS GUI window server is available in standard desktop user sessions
                env::var("TERM_PROGRAM").is_ok() || env::var("Apple_PubSub_Socket_Render").is_ok() || true
            }
            HostPlatform::Windows => {
                // Windows desktop GUI is standard unless running in Windows Server Core
                true
            }
        }
    }

    /// Asserts that a graphical display server is available when GUI mode is requested.
    ///
    /// # Sensory Tripwire:
    /// If running in a headless environment and GUI display is requested, trips a wire
    /// recommending headless serial mode (`--display none`).
    pub fn assert_display_server_available(
        &self,
        logger: &DiagnosticLogger,
    ) -> Result<(), TripwireError> {
        if self.has_display_server() {
            logger.log("DISPLAY", "Graphical display server verified active (+1:PROCEED)");
            Ok(())
        } else {
            let suggestion = FixSuggestion {
                kind: FixKind::AdjustCaveat,
                line: 1,
                col: 1,
                target_token: "--gui".to_string(),
```

```
                suggested_patch: "--headless".to_string(),
                rationale: "Host display environment has no active DISPLAY or WAYLAND_DISPLAY session".to_string(),
            };

            let err = Tripwire::trip_with_remediation(
                logger,
                "DISPLAY",
                FailpointType::SyntaxAnomaly,
                "No graphical display server detected (headless environment). Run without --gui.".to_string(),
                suggestion,
            );
            Err(err)
        }
    }
}

// ---------------------------------------------------------------------------
// 3.5. UEFI Firmware Search Oracles & Telemetry Traversal
// ---------------------------------------------------------------------------
impl HostPlatform {
    /// Returns the candidate search paths for UEFI OVMF firmware images on this platform.
    pub fn ovmf_search_paths(&self) -> &'static [&'static str] {
        match self {
            HostPlatform::Linux => LINUX_OVMF_CANDIDATES,
            HostPlatform::MacOS => MACOS_OVMF_CANDIDATES,
            HostPlatform::Windows => WINDOWS_OVMF_CANDIDATES,
            HostPlatform::Unknown => FALLBACK_OVMF_CANDIDATES,
        }
    }

    /// Dynamically locates the first existing OVMF firmware image on the host system.
    pub fn find_ovmf_firmware(&self) -> Option<PathBuf> {
        // First inspect custom override environment variable if provided
        if let Ok(env_path) = env::var("OMNICODE_OVMF_PATH") {
            let p = PathBuf::from(env_path);
            if p.exists() {
                return Some(p);
            }
        }

        for &path_str in self.ovmf_search_paths() {
            let path = Path::new(path_str);
            if path.exists() {
                return Some(path.to_path_buf());
            }
        }
        None
    }

    /// Traverses the platform's firmware candidate list while logging telemetry events.
    ///
    /// # Telemetry Inscription:
    /// Inscribes candidate probe entries into [`DiagnosticLogger`]. If a firmware blob
    /// is resolved, logs success. If none are found, registers an informational diagnostic
    /// note equipped with remediation guidance for the Restorator and AI agents.
    pub fn find_ovmf_firmware_with_telemetry(&self, logger: &DiagnosticLogger) -> Option<PathBuf> {
        logger.log("FIRMWARE", format!("Probing OVMF firmware candidates on {}", self.display_name()));

        if let Ok(env_override) = env::var("OMNICODE_OVMF_PATH") {
            let p = PathBuf::from(env_override);
            if p.exists() {
                logger.log("FIRMWARE", format!("Resolved OVMF firmware via OMNICODE_OVMF_PATH: {:?}", p));
                return Some(p);
            }
        }

        for &path_str in self.ovmf_search_paths() {
            let path = Path::new(path_str);
            if path.exists() {
                logger.log("FIRMWARE", format!("Resolved OVMF firmware at: {:?}", path));
                return Some(path.to_path_buf());
            } else {
                logger.log("FIRMWARE", format!("Candidate not found: {}", path_str));
            }
        }

        logger.record_ai_observation(
            "FIRMWARE_UNRESOLVED",
```

```
            "No standard OVMF firmware image found on host",
            "UEFI boot will require explicit --ovmf path or fallback to BIOS MBR mode",
            ["firmware", "ovmf", "uefi", "fallback"].as_slice(),
            None,
        );

        None
    }

    /// Asserts that a valid OVMF firmware blob exists on disk, tripping a wire if absent.
    ///
    /// # Precondition Tripwire:
    /// If no candidate exists, trips a [`TripwireError`] equipped with a [`FixSuggestion`]
    /// instructing how to install or specify the firmware image.
    pub fn assert_ovmf_firmware(
        &self,
        logger: &DiagnosticLogger,
    ) -> Result<PathBuf, TripwireError> {
        if let Some(firmware) = self.find_ovmf_firmware_with_telemetry(logger) {
            Ok(firmware)
        } else {
            let suggestion = FixSuggestion {
                kind: FixKind::AddImport,
                line: 1,
                col: 1,
                target_token: "--uefi".to_string(),
                suggested_patch: "--bios".to_string(),
                rationale: "Fallback to Legacy BIOS MBR mode or install ovmf package on host system".to_string(),
            };

            let err = Tripwire::trip_with_remediation(
                logger,
                "FIRMWARE",
                FailpointType::SyntaxAnomaly,
                format!("OVMF UEFI firmware image not found on {}", self.display_name()),
                suggestion,
            );
            Err(err)
        }
    }
}

// ---------------------------------------------------------------------------
// 3.6. Host OS Process Dispatch & Native Subprocess Execution
// ---------------------------------------------------------------------------
impl HostPlatform {
    /// Constructs the platform-appropriate [`Command`] for opening a target URL in the default browser.
    pub fn format_browser_command(&self, url: &str) -> Command {
        match self {
            HostPlatform::Linux => {
                let mut cmd = Command::new("xdg-open");
                cmd.arg(url);
                cmd
            }
            HostPlatform::MacOS => {
                let mut cmd = Command::new("open");
                cmd.arg(url);
                cmd
            }
            HostPlatform::Windows => {
                let mut cmd = Command::new("cmd");
                cmd.args(["/C", "start", url]);
                cmd
            }
            HostPlatform::Unknown => {
                let mut cmd = Command::new("xdg-open");
                cmd.arg(url);
                cmd
            }
        }
    }

    /// Dynamically launches the default web browser on the host system for a target URL.
    pub fn open_browser(&self, url: &str) {
        let mut cmd = self.format_browser_command(url);
        let _ = cmd.spawn();
    }

```

```
    /// Launches the default browser wrapped in diagnostic logging and tripwire interception.
    pub fn open_browser_with_tripwire(
        &self,
        logger: &DiagnosticLogger,
        url: &str,
    ) -> Result<(), TripwireError> {
        logger.log(
            "BROWSER_DISPATCH",
            format!("Dispatching browser on {} for URL: {}", self.display_name(), url),
        );
        let mut cmd = self.format_browser_command(url);
        match cmd.spawn() {
            Ok(_) => {
                logger.log("BROWSER_DISPATCH", "Browser child process dispatched cleanly (+1:PROCEED)");
                Ok(())
            }
            Err(e) => {
                let msg = format!("Failed to dispatch host browser for URL '{}': {}", url, e);
                Err(Tripwire::trip(logger, "BROWSER_DISPATCH", FailpointType::SyntaxAnomaly, msg))
            }
        }
    }

    /// Executes an arbitrary host command wrapped in tripwire collision detection and telemetry.
    ///
    /// # Game Dev Simulation Hook:
    /// Captures stdout and stderr streams. If the command exits with non-zero status code,
    /// logs an execution failure and trips a structured error for the Restorator.
    pub fn execute_host_command(
        &self,
        logger: &DiagnosticLogger,
        subsystem: &'static str,
        mut cmd: Command,
    ) -> Result<Output, TripwireError> {
        logger.log(subsystem, format!("Spawning host subprocess: {:?}", cmd));
        match cmd.output() {
            Ok(output) => {
                if output.status.success() {
                    logger.log(subsystem, "Host subprocess terminated with exit status 0 (+1:PROCEED)");
                    Ok(output)
                } else {
                    let code = output.status.code().unwrap_or(-1);
                    let stderr = String::from_utf8_lossy(&output.stderr);
                    let msg = format!(
                        "Host subprocess exited with non-zero status code {}: {}",
                        code, stderr.trim()
                    );
                    Err(Tripwire::trip(logger, subsystem, FailpointType::SyntaxAnomaly, msg))
                }
            }
            Err(e) => {
                let msg = format!("Failed to spawn host subprocess: {}", e);
                Err(Tripwire::trip(logger, subsystem, FailpointType::SyntaxAnomaly, msg))
            }
        }
    }
}

// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification and Sealing, Baton Pass & In-File Unit Tests )
// ================================================================================

// --------------------------------------------------------------------------------
// 4.1. Dynamic Adapter Sealing & Downstream Baton Pass Specification
// --------------------------------------------------------------------------------
// BATON PASS CONTRACT:
//   - Upstream Producer: Rust runtime and compile-time target introspection (`cfg!(target_os)`).
//   - Downstream Receivers:
//     * `<TRACK 1>` Boot Gear (`src/cli/commands/boot.rs`): Hypervisor binary resolution,
//       UEFI firmware lookup, display server probe, and acceleration flags.
//     * `<TRACK 3>` Studio IDE (`src/terminal/studio.rs`): Native browser dispatch and GUI server.
//     * `<TRACK 1>` REPL & Terminal (`src/terminal/session.rs`): Console color and terminal probes.
//   - Certified Invariants:
//     1. `HostPlatform::current()` and `HostArch::current()` return deterministic, valid variants.
//     2. Binary candidate matrices map strictly to executable names appropriate for the OS family.
//     3. `resolve_in_path` navigates host environment paths respecting platform path delimiters.
//     4. Browser command synthesizers construct platform-native dispatch subprocesses.
```

```rust
//     5. Virtualization acceleration flags accurately select KVM, HVF, WHPX, or fallback TCG.

#[cfg(test)]
mod tests {
    use super::*;

    /// Verifies that `HostPlatform::current()` dynamically resolves the active host operating system
    /// and supplies non-empty display names, binary targets, firmware matrices, and OS families.
    ///
    /// # Failure Mode Guarded Against:
    /// Prevents null or uninitialized platform definitions from entering downstream gears.
    #[test]
    fn test_platform_current_detection() {
        let p = HostPlatform::current();
        assert!(!p.display_name().is_empty(), "Display name must not be empty");
        assert!(!p.hypervisor_binary().is_empty(), "Hypervisor binary name must not be empty");
        assert!(!p.ovmf_search_paths().is_empty(), "Firmware search paths matrix must not be empty");
        assert!(!p.target_os_family().is_empty(), "OS family string must not be empty");
    }

    /// Verifies that `HostArch::current()` detects the host CPU instruction set architecture.
    ///
    /// # Failure Mode Guarded Against:
    /// Prevents silent fallback to mismatched architecture flags during hypervisor command synthesis.
    #[test]
    fn test_host_arch_detection() {
        let arch = HostArch::current();
        assert!(!arch.display_name().is_empty(), "CPU architecture display title must not be empty");
        let platform = HostPlatform::current();
        assert_eq!(platform.arch(), arch, "Platform arch must match HostArch::current");
    }

    /// Verifies that `environment_summary()` produces a comprehensive, well-formed diagnostic string
    /// containing all critical platform facets for episodic logging.
    ///
    /// # Invariants Tested:
    /// - Contains `"HostPlatform:"`, `"Arch:"`, `"Family:"`, `"POSIX:"`, `"Accel:"`, and `"Display:"`.
    #[test]
    fn test_environment_summary() {
        let p = HostPlatform::current();
        let summary = p.environment_summary();
        assert!(summary.contains("HostPlatform:"), "Summary must report HostPlatform");
        assert!(summary.contains("Arch:"), "Summary must report host architecture");
        assert!(summary.contains("Family:"), "Summary must report OS family");
        assert!(summary.contains("POSIX:"), "Summary must report POSIX compliance");
        assert!(summary.contains("Accel:"), "Summary must report hardware acceleration status");
        assert!(summary.contains("Display:"), "Summary must report display server availability");
    }

    /// Verifies the platform-to-binary mapping matrix across all supported operating system families.
    ///
    /// # Invariants Tested:
    /// - Windows requires `.exe` binary extension (`qemu-system-x86_64.exe`).
    /// - POSIX systems (Linux, macOS, Unknown) expect bare binary names (`qemu-system-x86_64`).
    #[test]
    fn test_platform_binaries() {
        assert_eq!(HostPlatform::Linux.hypervisor_binary(), "qemu-system-x86_64");
        assert_eq!(HostPlatform::Windows.hypervisor_binary(), "qemu-system-x86_64.exe");
        assert_eq!(HostPlatform::MacOS.hypervisor_binary(), "qemu-system-x86_64");
        assert_eq!(HostPlatform::Unknown.hypervisor_binary(), "qemu-system-x86_64");
    }

    /// Verifies the OS family classification and semantic predicate methods on `HostPlatform`.
    ///
    /// # Invariants Tested:
    /// - Linux: family `"unix"`, `is_posix() == true`, `is_linux() == true`, `is_windows() == false`.
    /// - macOS: family `"unix"`, `is_posix() == true`, `is_macos() == true`, `is_windows() == false`.
    /// - Windows: family `"windows"`, `is_posix() == false`, `is_windows() == true`.
    #[test]
    fn test_platform_os_family() {
        assert_eq!(HostPlatform::Linux.target_os_family(), "unix");
        assert!(HostPlatform::Linux.is_posix());
        assert!(HostPlatform::Linux.is_linux());
        assert!(!HostPlatform::Linux.is_windows());
        assert!(!HostPlatform::Linux.is_macos());

        assert_eq!(HostPlatform::MacOS.target_os_family(), "unix");
        assert!(HostPlatform::MacOS.is_posix());
```

```
        assert!(HostPlatform::MacOS.is_macos());
        assert!(!HostPlatform::MacOS.is_linux());

        assert_eq!(HostPlatform::Windows.target_os_family(), "windows");
        assert!(HostPlatform::Windows.is_windows());
        assert!(!HostPlatform::Windows.is_posix());
    }

    /// Verifies hardware virtualization acceleration command-line argument mapping.
    ///
    /// # Invariants Tested:
    /// - macOS maps to Apple Hypervisor.framework (`-accel hvf`).
    /// - Fallback/Unknown maps to software emulation (`-accel tcg`).
    /// - Linux provides acceleration flags (`-enable-kvm` or fallback).
    #[test]
    fn test_virtualization_accel_args() {
        let args_linux = HostPlatform::Linux.recommended_accel_args();
        assert!(!args_linux.is_empty(), "Linux acceleration argument list must not be empty");

        let args_macos = HostPlatform::MacOS.recommended_accel_args();
        assert_eq!(args_macos, &["-accel", "hvf"], "macOS must use Hypervisor.framework");

        let args_fallback = HostPlatform::Unknown.recommended_accel_args();
        assert_eq!(args_fallback, &["-accel", "tcg"], "Unknown platform must fall back to TCG");
    }

    /// Verifies native browser command synthesizer across Linux, macOS, and Windows.
    ///
    /// # Invariants Tested:
    /// - Linux dispatches `xdg-open <URL>`.
    /// - macOS dispatches `open <URL>`.
    /// - Windows dispatches `cmd /C start <URL>`.
    #[test]
    fn test_format_browser_command() {
        let test_url = "http://localhost:8080/studio";

        let cmd_linux = HostPlatform::Linux.format_browser_command(test_url);
        assert_eq!(cmd_linux.get_program(), "xdg-open");

        let cmd_macos = HostPlatform::MacOS.format_browser_command(test_url);
        assert_eq!(cmd_macos.get_program(), "open");

        let cmd_windows = HostPlatform::Windows.format_browser_command(test_url);
        assert_eq!(cmd_windows.get_program(), "cmd");
    }

    /// Verifies that `resolve_in_path` successfully resolves existing system binaries
    /// and correctly returns `None` for non-existent binaries.
    ///
    /// # Failure Mode Guarded Against:
    /// Prevents false positives or broken delimiter splitting when scanning host PATH.
    #[test]
    fn test_resolve_in_path_contract() {
        let platform = HostPlatform::current();

        // Standard shell binary must resolve on any functioning host
        let target = if platform.is_windows() { "cmd" } else { "sh" };
        let resolved = platform.resolve_in_path(target);
        assert!(resolved.is_some(), "Standard system shell must resolve on host PATH");
        let path = resolved.unwrap();
        assert!(path.is_file(), "Resolved PATH entry must point to a regular file");

        // Intentionally non-existent binary must return None
        let bogus = platform.resolve_in_path("definitely_nonexistent_binary_omnicode_xyz");
        assert!(bogus.is_none(), "Non-existent executable name must return None");
    }

    /// Verifies that candidate search path matrices across all platform variants
    /// are non-empty and contain valid non-empty path strings.
    ///
    /// # Invariants Tested:
    /// - Linux candidates, macOS candidates, Windows candidates, and Fallback candidates
    ///   must all be populated.
    #[test]
    fn test_ovmf_search_paths_contract() {
        for platform in &[HostPlatform::Linux, HostPlatform::MacOS, HostPlatform::Windows, HostPlatform::Unknown] {
            let paths = platform.ovmf_search_paths();
            assert!(!paths.is_empty(), "Platform {:?} must declare firmware candidates", platform);
```

```
            for &p in paths {
                assert!(!p.is_empty(), "Firmware candidate path string must not be empty");
            }
        }
    }

    /// Verifies that the display server probe evaluates without panic.
    #[test]
    fn test_display_server_probe_contract() {
        let platform = HostPlatform::current();
        let _has_display = platform.has_display_server();
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/cogs/tripwire.rs RS 628 LINES 2781 WORDS 28.2 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal Invariant Tripwire Cog Manifest & Cybernetic Sensory Boundaries )
// ============================================================================
//! MODULE:              omnicode::cogs::tripwire
//! IDENTITY:            Universal Invariant Tripwire Sensor Cog
//! NATURE:              Dynamic Boundary Protection, Collision Detection & Diagnostic Interception
//! VERSION:             0.3.0
//! CREATED:             2026-10-11
//! LAST_SEALED:         2026-10-11
//! AUTHOR:              CreativeWorkzStudio LLC / ProfessorSeanEX
//! COVENANT:            Public Domain / MIT
//!
//! SCHEDULER:
//!   TRACK_PRIMARY:     <TRACK 1> : {Host Engine & Virtual Machine}
//!   TRACKS_TOUCHED:    [ <TRACK 0> : {Silicon & Bare-Metal Kernel}, <TRACK 1>, <TRACK 2> : {Engine Runtime & SVO},
<TRACK 3> : {Studio & Graphical IDE} ]
//!   PRIORITY:          TaskPriority::High
//!   CHANNEL:           Track::Kernel
//!
//! CONTRACT / WHO-WHAT-WHERE-WHY-HOW:
//!   WHO:               OmniCode Universal Sensory Invariant Tripwire Subsystem
//!   WHAT:              Trap invariant violations, record structured failpoint events,
//!                      equip remediation suggestions, and summon the debugger and restorator.
//!   WHERE:             Enforced across all modules, CLI gears, platform adapters, terminal sessions, and scheduler
tasks.
//!   WHEN:              Evaluated at precondition boundaries, file accesses, subprocess invocations, and state
transitions.
//!   WHY:               Eliminate unhandled panics and raw process aborts, converting crashes into recoverable
//!                      diagnostic signals that trigger transaction rollbacks (`-1:ROLLBACK`) or automated self-healing.
//!   HOW:               Balanced Ternary (+1:PROCEED invariant held, -1:ROLLBACK invariant breached with telemetry,
0:AWAIT standby).
//!
//! THE GAME DEV COLLISION TRIGGER PARADIGM:
//!   In modern game engine architecture (e.g., Unreal, Unity, Godot):
//!   - Invisible Trigger Volumes: Spatial and physical boundary colliders placed in world space. When an entity
//!     penetrates an illegal zone or invalid state, the physics engine does not crash the game loop; it fires an
//!     `OnTriggerEnter` or `OnCollision` event callback.
//!   - In OmniCode: Tripwires are the cognitive and computational collision triggers. Instead of allowing undefined
//!     behavior, unhandled null states, absent silicon binaries, missing kernel images, or corrupted filesystems to
//!     panic the engine (`panic!`), a tripwire immediately catches the boundary collision.
//!
//! CYBERNETIC FAILPOINT & TRANSLATION ENVELOPE:
//!   - Translates raw runtime anomalies into formal ontological failpoint categories ([`FailpointType`]).
//!   - Emits microsecond-timestamped telemetry directly into the active [`DiagnosticLogger`] ring buffer and
[`crate::diagnostics::debugger::OmniDebugger`].
//!   - Inscribes episodic cognitive memory notes tagged `#failpoint` for AI reasoning models and developers.
//!   - Replaces uncontrolled stack unwinding with balanced-ternary quad-state causality (`-1:ROLLBACK` or `0:AWAIT`).
//!
//! THE RESTORATOR HANDOFF & REPAIR TELEMETRY:
//!   - When a tripwire trips with remediation ([`Tripwire::trip_with_remediation`]), it equips the trapped event
//!     with a [`FixSuggestion`] and registers `#remediation_ready` telemetry.
//!   - The [`crate::diagnostics::restorator::Restorator`] (OmniCode's autonomous immune system) ingests this structured
//!     flight data, executes surgical AST/token patches, test-certifies the candidate repair, and restores system
balance.
//!
//! TOUCHES / SYSTEM & PROCESS FOOTPRINT:
//!   - TELEMETRY:       Direct emission to [`DiagnosticLogger`] and active
[`crate::diagnostics::debugger::OmniDebugger`].
//!   - TERMINAL:        Standardized ANSI red/yellow tripwire alert streams to stderr and session logs.
//!   - RECOVERY:        Integrates with transaction rollbacks and automated Restorator immune responses.
//!   - SUBPROCESSES:    Monitors exit status codes and standard streams of external host child processes.
//!
//! REQUIRES / HOST CAPABILITIES:
//!   - Standard error stream access (`std::io::stderr`).
//!   - Filesystem metadata inspection (`std::path::Path::exists`, `std::path::Path::is_dir`, `std::fs::metadata`).
//!   - Subprocess status inspection (`std::process::ExitStatus`).
//!
//! TRIPWIRE REGISTRY:
//!   - `TRIPWIRE_PATH_EXISTENCE`       (Assertion of critical filesystem resources and kernel artifacts)
//!   - `TRIPWIRE_DIR_EXISTENCE`        (Assertion of required workspace and directory hierarchies)
//!   - `TRIPWIRE_BINARY_AVAILABLE`     (Assertion of required external host toolchains on system PATH)
//!   - `TRIPWIRE_COMMAND_STATUS`       (Assertion of zero exit status on host subprocesses)
//!   - `TRIPWIRE_STATE_VIOLATION`      (Assertion of semantic invariant boundaries and quad-state commitments)
```

```
//!   - `TRIPWIRE_BOOLEAN_INVARIANT`    (Assertion of mathematical and ontological propositional truths)
//!
//! NAVIGATION GUIDE (HOW TO NAVIGATE AND EXTEND THIS COG AS THE CODE GROWS):
//!   - Block 1 (Lines 1-85): Manifest, Game Dev Trigger Analogy, Telemetry Envelope, Tripwire Registry.
//!   - Block 2 (Lines 86-175): Scoped Imports, Error Envelopes (`TripwireError`), Display Formatting & Defaults.
//!     * To add custom recovery constructors: add methods to `TripwireError` in Section 2.2.
//!     * To modify equilibrium recovery defaults: review constants in Section 2.3.
//!   - Block 3 (Lines 176-350): Body Block & Sensory Assertion Oracles.
//!     * 3.1: Explicit Failpoint Inscription & Remediation Oracles (`trip`, `trip_with_remediation`, `trip_await`).
//!     * 3.2: Filesystem Spatial Invariant Assertions (`assert_path_exists`, `assert_dir_exists`, `assert_file_readable`).
//!     * 3.3: Host Toolchain & Binary Availability Oracles (`assert_binary_available`).
//!     * 3.4: Subprocess Lifecycle & Exit Status Assertions (`assert_command_success`, `assert_command_output_clean`).
//!     * 3.5: Mathematical, State Machine & Causality Boundary Assertions (`assert_quad_state_proceed`, `assert_invariant`).
//!   - Block 4 (Lines 351+): Module Sealing, Baton Pass Protocol & In-File Unit Verification Tests.

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Scoped Imports, Invariant Data Types & Tripwire Error Definitions )
// ============================================================================

// ----------------------------------------------------------------------------
// 2.1. Scoped Namespace Ingestion & System Imports
// ----------------------------------------------------------------------------
use std::fmt;
use std::fs;
use std::path::{Path, PathBuf};
use std::process::{Command, ExitStatus, Output};

use crate::core::ternary::QuadState;
use crate::diagnostics::logger::{DiagnosticLogger, FailpointType, FixSuggestion};

// ----------------------------------------------------------------------------
// 2.2. Invariant Data Types & Tripwire Error Definitions
// ----------------------------------------------------------------------------
/// Formal error envelope produced when an execution boundary or invariant tripwire is breached.
///
/// Unlike standard Rust errors or panics that destroy process context, [`TripwireError`]
/// encapsulates rich cybernetic metadata:
/// - Channel identifier for precise subsystem origin tracking.
/// - Ontological failpoint category ([`FailpointType`]).
/// - Human and machine readable diagnostic message.
/// - Balanced-ternary recovery state (`-1:ROLLBACK` or `0:AWAIT`).
#[derive(Debug, Clone, PartialEq, Eq)]
pub struct TripwireError {
    /// Subsystem or channel where the tripwire fired (e.g. "BOOT", "PLATFORM", "TERMINAL", "SCHEDULER").
    pub channel: &'static str,
    /// Formal diagnostic classification of the failpoint.
    pub failpoint_type: FailpointType,
    /// Detailed diagnostic message explaining the breach.
    pub message: String,
    /// Balanced ternary state mapping for recovery (typically `-1:ROLLBACK` or `0:AWAIT`).
    pub recovery_state: QuadState,
}

impl TripwireError {
    /// Creates a new tripwire error mapped to `-1:ROLLBACK` state.
    pub fn rollback(channel: &'static str, fp_type: FailpointType, msg: impl Into<String>) -> Self {
        Self {
            channel,
            failpoint_type: fp_type,
            message: msg.into(),
            recovery_state: QuadState::Rollback,
        }
    }

    /// Creates a new tripwire error mapped to `0:AWAIT` standby state.
    pub fn await_state(channel: &'static str, fp_type: FailpointType, msg: impl Into<String>) -> Self {
        Self {
            channel,
            failpoint_type: fp_type,
            message: msg.into(),
            recovery_state: QuadState::Await,
        }
    }

    /// Returns `true` if this error dictates an active transaction rollback (`-1:ROLLBACK`).
```

```rust
    pub fn is_rollback(&self) -> bool {
        self.recovery_state == QuadState::Rollback
    }

    /// Returns `true` if this error indicates that the operation is awaiting asynchronous completion (`0:AWAIT`).
    pub fn is_await(&self) -> bool {
        self.recovery_state == QuadState::Await
    }
}

impl fmt::Display for TripwireError {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        write!(
            f,
            "[{}] Failpoint {}: {} (State: {})",
            self.channel,
            self.failpoint_type.as_str(),
            self.message,
            self.recovery_state.macro_op()
        )
    }
}

impl std::error::Error for TripwireError {}

// ---------------------------------------------------------------------------
// 2.3. Initial Truth States & Equilibrium Recovery Defaults
// ---------------------------------------------------------------------------
/// Default quad-state recovery commitment when a tripwire collision occurs.
pub const DEFAULT_TRIPWIRE_RECOVERY_STATE: QuadState = QuadState::Rollback;

/// Default diagnostic channel assigned when no subsystem is explicitly specified.
pub const DEFAULT_TRIPWIRE_CHANNEL: &str = "TRIPWIRE";

// ===========================================================================
// BLOCK 3: BODY BLOCK
// ( Universal Tripwire Engine Implementation & Assertion Oracles )
// ===========================================================================

/// Mechanical Tripwire Sensor for invariant enforcement, collision sensing, and diagnostic alerting.
#[derive(Debug, Clone, Copy, Default)]
pub struct Tripwire;

// ---------------------------------------------------------------------------
// 3.1. Explicit Failpoint Inscription & Remediation Oracles
// ---------------------------------------------------------------------------
impl Tripwire {
    /// Explicitly trips a diagnostic wire, recording a failpoint in the logger and emitting a standard alert.
    ///
    /// # Game Dev Collision Volume Hook:
    /// Inscribes a critical failpoint into [`DiagnosticLogger`], writes an ANSI red alert to stderr,
    /// and packages the violation into a [`TripwireError`] with `-1:ROLLBACK`.
    pub fn trip(
        logger: &DiagnosticLogger,
        channel: &'static str,
        fp_type: FailpointType,
        message: impl Into<String>,
    ) -> TripwireError {
        let msg = message.into();
        logger.failpoint(fp_type, channel, msg.clone());

        eprintln!(
            "\x1b[1;31m✗ Tripwire Alert [{}]\x1b[0m [{}]: {}",
            channel,
            fp_type.as_str(),
            msg
        );

        TripwireError::rollback(channel, fp_type, msg)
    }

    /// Explicitly trips a diagnostic wire equipped with concrete remediation telemetry for the Restorator.
    ///
    /// # Restorator Immune Handoff:
    /// Attaches a [`FixSuggestion`] and registers an episodic cognitive memory note tagged
    /// `#remediation_ready`, allowing automated self-healing passes to immediately parse and apply the patch.
    pub fn trip_with_remediation(
        logger: &DiagnosticLogger,
```

```
        channel: &'static str,
        fp_type: FailpointType,
        message: impl Into<String>,
        suggestion: FixSuggestion,
    ) -> TripwireError {
        let msg = message.into();
        logger.failpoint_with_remediation(fp_type, channel, msg.clone(), suggestion);

        eprintln!(
            "\x1b[1;31m✗ Tripwire Alert [{}]\x1b[0m [{}]: {}",
            channel,
            fp_type.as_str(),
            msg
        );

        TripwireError::rollback(channel, fp_type, msg)
    }

    /// Trips a diagnostic wire that pauses execution in `0:AWAIT` standby state rather than rolling back.
    ///
    /// Used when a required resource is temporarily in flight or pending background synthesis.
    pub fn trip_await(
        logger: &DiagnosticLogger,
        channel: &'static str,
        fp_type: FailpointType,
        message: impl Into<String>,
    ) -> TripwireError {
        let msg = message.into();
        logger.failpoint(fp_type, channel, msg.clone());

        eprintln!(
            "\x1b[1;33m⚠ Tripwire Standby [{}]\x1b[0m [{}]: {}",
            channel,
            fp_type.as_str(),
            msg
        );

        TripwireError::await_state(channel, fp_type, msg)
    }
}

// ---------------------------------------------------------------------------
// 3.2. Filesystem Spatial Invariant Assertions
// ---------------------------------------------------------------------------
impl Tripwire {
    /// Asserts that a required file or directory exists on disk.
    ///
    /// # Precondition Sensor:
    /// Returns the verified [`PathBuf`] on success (+1:PROCEED). If absent, trips
    /// a [`FailpointType::SyntaxAnomaly`] error with `-1:ROLLBACK`.
    pub fn assert_path_exists(
        logger: &DiagnosticLogger,
        channel: &'static str,
        path: impl AsRef<Path>,
        description: &'static str,
    ) -> Result<PathBuf, TripwireError> {
        let p = path.as_ref();
        if p.exists() {
            Ok(p.to_path_buf())
        } else {
            let msg = format!("{description} not found at expected path: {:?}", p);
            Err(Self::trip(logger, channel, FailpointType::SyntaxAnomaly, msg))
        }
    }

    /// Asserts that a target path exists and is specifically a directory.
    pub fn assert_dir_exists(
        logger: &DiagnosticLogger,
        channel: &'static str,
        path: impl AsRef<Path>,
        description: &'static str,
    ) -> Result<PathBuf, TripwireError> {
        let p = path.as_ref();
        if p.is_dir() {
            Ok(p.to_path_buf())
        } else {
            let msg = format!("{description} directory does not exist: {:?}", p);
            Err(Self::trip(logger, channel, FailpointType::SyntaxAnomaly, msg))
```

```
        }
    }

    /// Asserts that a target file exists and is readable by the current process.
    pub fn assert_file_readable(
        logger: &DiagnosticLogger,
        channel: &'static str,
        path: impl AsRef<Path>,
        description: &'static str,
    ) -> Result<PathBuf, TripwireError> {
        let p = path.as_ref();
        if !p.exists() {
            let msg = format!("{description} file does not exist: {:?}", p);
            return Err(Self::trip(logger, channel, FailpointType::SyntaxAnomaly, msg));
        }

        match fs::metadata(p) {
            Ok(_) => Ok(p.to_path_buf()),
            Err(e) => {
                let msg = format!("Cannot read metadata for {description} at {:?}: {}", p, e);
                Err(Self::trip(logger, channel, FailpointType::SyntaxAnomaly, msg))
            }
        }
    }
}

// ---------------------------------------------------------------------------
// 3.3. Host Toolchain & Binary Availability Oracles
// ---------------------------------------------------------------------------
impl Tripwire {
    /// Asserts that a required executable binary is available on the host system PATH.
    ///
    /// # Platform Awareness:
    /// Dispatches `where` on Windows and `which` on Unix/macOS to probe host environment variables.
    pub fn assert_binary_available(
        logger: &DiagnosticLogger,
        channel: &'static str,
        bin_name: &'static str,
    ) -> Result<(), TripwireError> {
        let check = if cfg!(target_os = "windows") {
            Command::new("where").arg(bin_name).output()
        } else {
            Command::new("which").arg(bin_name).output()
        };

        match check {
            Ok(out) if out.status.success() => Ok(()),
            _ => {
                let msg = format!(
                    "Required host binary '{bin_name}' is not accessible on system PATH"
                );
                Err(Self::trip(logger, channel, FailpointType::SyntaxAnomaly, msg))
            }
        }
    }
}

// ---------------------------------------------------------------------------
// 3.4. Subprocess Lifecycle & Exit Status Assertions
// ---------------------------------------------------------------------------
impl Tripwire {
    /// Asserts that a subprocess command completed successfully with exit code 0.
    ///
    /// Traps non-zero exit codes or spawn failures without process panic.
    pub fn assert_command_success(
        logger: &DiagnosticLogger,
        channel: &'static str,
        status: Result<ExitStatus, std::io::Error>,
        command_name: &'static str,
    ) -> Result<(), TripwireError> {
        match status {
            Ok(s) if s.success() => Ok(()),
            Ok(s) => {
                let code = s.code().map(|c| c.to_string()).unwrap_or_else(|| "signal".into());
                let msg = format!("Subprocess '{command_name}' exited with non-zero status ({code})");
                Err(Self::trip(logger, channel, FailpointType::SyntaxAnomaly, msg))
            }
            Err(e) => {
```

```
                let msg = format!("Failed to spawn or communicate with subprocess '{command_name}': {e}");
                Err(Self::trip(logger, channel, FailpointType::SyntaxAnomaly, msg))
            }
        }
    }

    /// Asserts that a captured subprocess [`Output`] succeeded, logging stderr on failure.
    pub fn assert_command_output_clean(
        logger: &DiagnosticLogger,
        channel: &'static str,
        output: Result<Output, std::io::Error>,
        command_name: &'static str,
    ) -> Result<Output, TripwireError> {
        match output {
            Ok(out) if out.status.success() => Ok(out),
            Ok(out) => {
                let code = out.status.code().unwrap_or(-1);
                let stderr = String::from_utf8_lossy(&out.stderr);
                let msg = format!(
                    "Subprocess '{command_name}' failed with status code {}: {}",
                    code, stderr.trim()
                );
                Err(Self::trip(logger, channel, FailpointType::SyntaxAnomaly, msg))
            }
            Err(e) => {
                let msg = format!("Failed to execute subprocess '{command_name}': {e}");
                Err(Self::trip(logger, channel, FailpointType::SyntaxAnomaly, msg))
            }
        }
    }
}

// ---------------------------------------------------------------------------
// 3.5. Mathematical, State Machine & Causality Boundary Assertions
// ---------------------------------------------------------------------------
impl Tripwire {
    /// Asserts that a quad-state evaluation committed to `+1:PROCEED`.
    ///
    /// If the state is `-1:ROLLBACK` or `0:AWAIT`, raises an explicit tripwire error.
    pub fn assert_quad_state_proceed(
        logger: &DiagnosticLogger,
        channel: &'static str,
        state: QuadState,
        context: &'static str,
    ) -> Result<(), TripwireError> {
        if state == QuadState::Proceed {
            Ok(())
        } else {
            let msg = format!(
                "QuadState invariant breach in {context}: expected +1:PROCEED, encountered {}",
                state.macro_op()
            );
            Err(Self::trip(logger, channel, FailpointType::RollbackTriggered, msg))
        }
    }

    /// Asserts an arbitrary boolean propositional truth condition.
    ///
    /// If false, trips the wire with the designated failpoint category and message.
    pub fn assert_invariant(
        logger: &DiagnosticLogger,
        channel: &'static str,
        condition: bool,
        fp_type: FailpointType,
        message: impl Into<String>,
    ) -> Result<(), TripwireError> {
        if condition {
            Ok(())
        } else {
            Err(Self::trip(logger, channel, fp_type, message))
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification and Sealing, Baton Pass & In-File Unit Tests )
// ============================================================================
```

```
456
457 // ---------------------------------------------------------------------------
458 // 4.1. Universal Tripwire Sealing & Downstream Baton Pass Specification
459 // ---------------------------------------------------------------------------
460 // BATON PASS CONTRACT:
461 //   - Upstream Producer: Hardware, Filesystem, Runtime Processes & Evaluator ALU.
462 //   - Downstream Receivers:
463 //     * `<TRACK 1>` Boot Gear (`src/cli/commands/boot.rs`): Inception and compiler tripwires.
464 //     * `<TRACK 1>` Platform Cog (`src/cogs/platform.rs`): Hypervisor and firmware tripwires.
465 //     * `<TRACK 1>` Diagnostics (`src/diagnostics/`): Restorator immune repair and Debugger frames.
466 //     * `<TRACK 1>` Terminal Session (`src/terminal/session.rs`): Tape mount and execution boundary tripwires.
467 //   - Certified Invariants:
468 //     1. Tripwire breaches never panic or abort process memory; all breaches produce `TripwireError`.
469 //     2. All tripwire events inscribe structured failpoint records into `DiagnosticLogger`.
470 //     3. `Tripwire::trip_with_remediation` attaches `FixSuggestion` and tags `#remediation_ready`.
471 //     4. Filesystem, binary, subprocess, and boolean invariant assertion methods return
472 //        deterministic, uncheatable results.
473
474 #[cfg(test)]
475 mod tests {
476     use super::*;
477     use crate::diagnostics::logger::{FixKind, FixSuggestion};
478
479     /// Verifies that explicitly tripping a wire records a failpoint in `DiagnosticLogger`
480     /// and constructs a `TripwireError` with `-1:ROLLBACK` recovery state.
481     ///
482     /// # Failure Mode Guarded Against:
483     /// Prevents silent failure where an error is created without inscriptive telemetry.
484     #[test]
485     fn test_tripwire_explicit_trip_and_failpoint_capture() {
486         let logger = DiagnosticLogger::new(false);
487         let err = Tripwire::trip(
488             &logger,
489             "TEST_CHANNEL",
490             FailpointType::SyntaxAnomaly,
491             "Simulated explicit tripwire fault",
492         );
493
494         assert_eq!(err.channel, "TEST_CHANNEL");
495         assert_eq!(err.failpoint_type, FailpointType::SyntaxAnomaly);
496         assert_eq!(err.recovery_state, QuadState::Rollback);
497         assert!(err.is_rollback());
498         assert!(!err.is_await());
499         assert!(logger.has_failpoints(), "DiagnosticLogger must record the failpoint");
500         assert_eq!(logger.failpoints().len(), 1);
501     }
502
503     /// Verifies that `trip_with_remediation` successfully attaches a `FixSuggestion`
504     /// and emits an episodic cognitive note tagged `#remediation_ready`.
505     ///
506     /// # Invariants Tested:
507     /// - Failpoint contains the attached fix suggestion.
508     /// - Cognitive notes buffer contains a note tagged `#remediation_ready`.
509     #[test]
510     fn test_tripwire_with_remediation_suggestion() {
511         let logger = DiagnosticLogger::new(false);
512         let suggestion = FixSuggestion {
513             kind: FixKind::AddBlockHeader,
514             line: 1,
515             col: 1,
516             target_token: "HEADER".to_string(),
517             suggested_patch: "BLOCK 1: METADATA".to_string(),
518             rationale: "Automated header repair".to_string(),
519         };
520
521         let err = Tripwire::trip_with_remediation(
522             &logger,
523             "REPAIR_CHANNEL",
524             FailpointType::BoundaryMismatch,
525             "Simulated repairable fault",
526             suggestion.clone(),
527         );
528
529         assert_eq!(err.channel, "REPAIR_CHANNEL");
530         assert_eq!(err.failpoint_type, FailpointType::BoundaryMismatch);
531
532         let fps = logger.failpoints();
533         assert_eq!(fps.len(), 1);
```

```
        assert_eq!(fps[0].suggestion, Some(suggestion));

        let notes = logger.cognitive_notes();
        assert!(
            notes.iter().any(|n| n.tags.iter().any(|t| t == "remediation_ready")),
            "Episodic notes must include #remediation_ready tag"
        );
    }

    /// Verifies that `trip_await` sets `0:AWAIT` standby state rather than rolling back.
    #[test]
    fn test_tripwire_await_state_constructor() {
        let logger = DiagnosticLogger::new(false);
        let err = Tripwire::trip_await(
            &logger,
            "ASYNC_CHANNEL",
            FailpointType::NullTrap,
            "Pending background artifact",
        );

        assert_eq!(err.channel, "ASYNC_CHANNEL");
        assert_eq!(err.recovery_state, QuadState::Await);
        assert!(err.is_await());
        assert!(!err.is_rollback());
    }

    /// Verifies that `assert_path_exists` returns `Ok(PathBuf)` for existing paths
    /// and `Err(TripwireError)` with failpoint telemetry for missing paths.
    ///
    /// # Uncheatable Assertion:
    /// Tests both positive path resolution (`Cargo.toml`) and negative path failure.
    #[test]
    fn test_assert_path_exists_contract() {
        let logger = DiagnosticLogger::new(false);

        // Positive check: Cargo manifest must resolve
        let ok_res = Tripwire::assert_path_exists(&logger, "TEST", "Cargo.toml", "Cargo Manifest");
        assert!(ok_res.is_ok(), "Cargo.toml must resolve successfully");
        assert!(ok_res.unwrap().exists());

        // Negative check: missing file must trip with failpoint
        let missing = Tripwire::assert_path_exists(&logger, "TEST", "nonexistent_omnicode_file_xyz.omni", "Missing
File");
        assert!(missing.is_err(), "Missing file must return TripwireError");
        let err = missing.unwrap_err();
        assert_eq!(err.channel, "TEST");
        assert!(logger.has_failpoints(), "Logger must capture failpoint on missing path");
    }

    /// Verifies that `assert_dir_exists` validates directories and rejects non-directory files.
    #[test]
    fn test_assert_dir_exists_contract() {
        let logger = DiagnosticLogger::new(false);

        // Positive: current workspace root is a directory
        assert!(Tripwire::assert_dir_exists(&logger, "TEST", ".", "Workspace Root Directory").is_ok());

        // Negative: Cargo.toml is a file, not a directory
        assert!(Tripwire::assert_dir_exists(&logger, "TEST", "Cargo.toml", "Manifest File As Dir").is_err());
    }

    /// Verifies that `assert_invariant` succeeds on true conditions and trips on false conditions.
    #[test]
    fn test_assert_invariant_contract() {
        let logger = DiagnosticLogger::new(false);

        let ok_res = Tripwire::assert_invariant(&logger, "MATH", 2 + 2 == 4, FailpointType::SyntaxAnomaly, "Arithmetic
holds");
        assert!(ok_res.is_ok());

        let err_res = Tripwire::assert_invariant(&logger, "MATH", 2 + 2 == 5, FailpointType::SyntaxAnomaly, "Arithmetic
breached");
        assert!(err_res.is_err());
        assert!(logger.has_failpoints());
    }

    /// Verifies that `assert_quad_state_proceed` accepts `QuadState::Proceed` and trips on `Rollback` or `Await`.
    #[test]
```

```
    fn test_assert_quad_state_proceed_contract() {
        let logger = DiagnosticLogger::new(false);

        assert!(Tripwire::assert_quad_state_proceed(&logger, "EXEC", QuadState::Proceed, "Step 1").is_ok());
        assert!(Tripwire::assert_quad_state_proceed(&logger, "EXEC", QuadState::Rollback, "Step 2").is_err());
        assert!(Tripwire::assert_quad_state_proceed(&logger, "EXEC", QuadState::Await, "Step 3").is_err());
    }

    /// Verifies that `TripwireError` implements `Display` with channel, category, message, and state.
    #[test]
    fn test_tripwire_error_display_formatting() {
        let err = TripwireError::rollback("KERNEL", FailpointType::ImmutableMutation, "Attempted write to immutable
register");
        let formatted = format!("{err}");
        assert!(formatted.contains("[KERNEL]"));
        assert!(formatted.contains("FP_IMMUTABLE_MUTATION"));
        assert!(formatted.contains("Attempted write to immutable register"));
        assert!(formatted.contains("ROLLBACK"));
    }
}
```

OmniCode: Chapter 5: Track 1 - AI Cortex & Neural Learning Engine

Cognitive Loop, Synapses, Episodic Learner & Transducer

CHAPTER IDENTIFIER	**NOTEBOOKLM WORD COUNT**
CH 05	19,020 words
CATALOGED CHAPTER FILES	**GENERATION DATE**
26 files (5,269 lines)	2026-10-16 20:35:53

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"How does the AI Cortex reconcile deliberations with truth?"*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (26 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/mod.rs**	RS	46	171	1.8
2	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/lexicon/entry.rs**	RS	30	140	1.2
3	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/lexicon/mod.rs**	RS	79	288	2.6
4	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/lexicon/moral.rs**	RS	187	630	6.6
5	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/lexicon/table.rs**	RS	525	2,906	26.4
6	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/model/cortex.rs**	RS	332	929	11.5
7	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/model/learner.rs**	RS	247	774	8.8
8	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/model/memory.rs**	RS	615	2,255	24.5
9	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/model/mod.rs**	RS	38	166	1.7
10	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/model/scroll.rs**	RS	393	1,136	13.4
11	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/transducer/decoder.rs**	RS	129	385	4.5
12	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/transducer/encoder.rs**	RS	487	1,890	20.8
13	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/transducer/executor.rs**	RS	46	154	1.7
14	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/transducer/mod.rs**	RS	125	344	3.8
15	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/transducer/patterns.rs**	RS	164	605	5.1
16	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/transducer/session.rs**	RS	22	84	0.8
17	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/transducer/templates.rs**	RS	636	2,013	19.5
18	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/NEURAL_NETWORK_ARCHITECTURE.md**	MD	101	738	5.4
19	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/brain.rs**	RS	304	929	10.6
20	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/layer.rs**	RS	53	170	1.7
21	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/mod.rs**	RS	42	157	1.6
22	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/network.rs**	RS	23	104	1.0
23	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/neuron.rs**	RS	109	363	3.6
24	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/noise.rs**	RS	223	799	7.5
25	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/synapse.rs**	RS	91	259	2.8
26	**<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/trainer.rs**	RS	222	631	7.6

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/mod.rs RS | 46 LINES | 171 WORDS | 1.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( AI Subsystem Identity, Module Manifest & Exports )
// ============================================================================
//! OmniCode AI Subsystem: Semantic Transduction & Cognitive Discourse Layer
//!
//! Exposes:
//!   - `model`: Dedicated folder for the internal AI model (Cortex, ScrollLogger, Learner).
//!   - `transducer`: Natural language to OmniCode AST transcoder and conversational speaker.

pub mod lexicon;
pub mod model;
pub mod neural;
pub mod transducer;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Subsystem Re-exports )
// ============================================================================
pub use lexicon::{
    BiblicalLexicon, LexiconDomain, LexiconEntry, MoralEvaluation,
};
pub use model::{
    AICortex, AILearner, AIMemory, CognitiveResult, EpisodicExperience,
    EpisodicSummary, ExecutionScroll, MemoryAssociation, ScrollLogger,
    ThoughtRecord,
};
pub use neural::{
    DegradationMode, DegradationStep, NeuralBrain, NeuralTrainer, NoiseEngine,
    StructuredNoiseConfig, SynapticWeight, TernaryLayer, TernaryNeuron,
    TrainingReport,
};
pub use transducer::{AITransducer, TransductionSession};

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Core Coordination )
// ============================================================================
// AI cognitive loop active and linked to diagnostic nervous system.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Verification and Subsystem Status )
// ============================================================================
// AI subsystem verified and sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/lexicon/entry.rs RS 30 LINES 140 WORDS 1.2 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Structured Biblical Lexicon Entry & Dual Witness Manifest )
// ============================================================================
//! # Lexicon Entry (`entry.rs`)
//!
//! Structured entry representing an ontological entity, virtue, or causal law.

use crate::core::ternary::QuadState;
use super::domain::LexiconDomain;

/// A structured entry in the biblical world lexicon.
#[derive(Debug, Clone)]
pub struct LexiconEntry {
    /// Canonical keyword / concept identifier (lowercase).
    pub term: &'static str,
    /// Ontological domain.
    pub domain: LexiconDomain,
    /// Foundational definition explaining what this entity or concept is.
    pub definition: &'static str,
    /// King James Version (KJV) citation and text (Public Domain).
    pub kjv_passage: &'static str,
    /// World English Bible (WEB) citation and text (Public Domain).
    pub web_passage: &'static str,
    /// Natural resonance within Balanced Ternary Quad-State logic.
    pub quad_state_resonance: QuadState,
    /// Moral guidance or causal invariant for AI deliberation.
    pub moral_guidance: &'static str,
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/lexicon/mod.rs RS | 79 LINES | 288 WORDS | 2.6 KB

```rust
// ========================================================================
// BLOCK 1: METADATA BLOCK
// ( Biblical World Lexicon Subsystem Identity, Module Manifest & Exports )
// ========================================================================
//! OmniCode AI Subsystem: Biblical World Lexicon & Moral Ontology Engine
//!
//! Provides a complete, 100% offline, self-contained world model and moral
//! compass derived from the public domain King James Version (KJV - 1611)
//! and World English Bible (WEB).

pub mod domain;
pub mod entry;
pub mod moral;
pub mod table;

pub use domain::LexiconDomain;
pub use entry::LexiconEntry;
pub use moral::MoralEvaluation;

/// The offline Biblical Lexicon engine holding the complete world ontology.
#[derive(Debug, Clone)]
pub struct BiblicalLexicon {
    entries: Vec<LexiconEntry>,
}

impl BiblicalLexicon {
    /// Instantiates the comprehensive public domain biblical world lexicon.
    pub fn new() -> Self {
        Self {
            entries: table::build_lexicon_entries(),
        }
    }

    /// Retrieves all entries stored in the lexicon.
    pub fn all_entries(&self) -> &[LexiconEntry] {
        &self.entries
    }

    /// Looks up a specific concept by keyword.
    pub fn lookup(&self, term: &str) -> Option<&LexiconEntry> {
        let clean = term.trim().to_lowercase();
        self.entries.iter().find(|e| e.term == clean)
    }

    /// Searches for entries matching a keyword in their term or definition.
    pub fn search(&self, query: &str) -> Vec<&LexiconEntry> {
        let clean = query.trim().to_lowercase();
        self.entries
            .iter()
            .filter(|e| {
                e.term.contains(&clean)
                    || e.definition.to_lowercase().contains(&clean)
            })
            .collect()
    }

    /// Evaluates a natural language prompt against the Invariant Covenant
    /// Manifest, determining moral alignment and appropriate Quad-State.
    pub fn evaluate_moral_intent(&self, prompt: &str) -> MoralEvaluation {
        self.deliberate(prompt)
    }

    /// Deliberates on a prompt against lexicon entries and invariant
    /// covenant laws.
    pub fn deliberate(&self, prompt: &str) -> MoralEvaluation {
        moral::deliberate_prompt(&self.entries, prompt)
    }
}

// ========================================================================
// BLOCK 4: CLOSING BLOCK
// ( Default Implementation, Module Sealing & Invariant Verification )
// ========================================================================
impl Default for BiblicalLexicon {
```

```
    fn default() -> Self {
        Self::new()
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/lexicon/moral.rs RS 187 LINES 630 WORDS 6.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Moral Evaluation Identity, Covenant Anchor & Conscience Deliberation )
// ============================================================================
//! # Moral Deliberation (`moral.rs`)
//!
//! Evaluates natural prompts against the Invariant Covenant Manifest,
//! issuing moral affirmations (+1: PROCEED), pauses (0: AWAIT), caveat
//! vetoes (-1: ROLLBACK), or terminal halters (NULL: HALT).

use crate::core::ternary::QuadState;
use super::entry::LexiconEntry;

/// Result of evaluating a natural prompt through the moral deliberation engine.
#[derive(Debug, Clone)]
pub struct MoralEvaluation {
    /// Deliberated Quad-State outcome.
    pub state: QuadState,
    /// Whether the prompt aligns with the Invariant Covenant Manifest.
    pub is_aligned: bool,
    /// Identifier of the specific invariant law engaged or violated.
    pub law_engaged: Option<&'static str>,
    /// Natural discourse response explaining the judgment.
    pub explanation: String,
    /// Matching biblical lexicon entries relevant to the prompt.
    pub matched_entries: Vec<LexiconEntry>,
}

/// Deliberates on a prompt against lexicon entries and invariant covenant laws.
pub fn deliberate_prompt(
    entries: &[LexiconEntry],
    prompt: &str,
) -> MoralEvaluation {
    let lower = prompt.to_lowercase();

    // 1. Check for Absolute Malice / Harm (Law_Life -> NULL: HALT)
    let harm_keywords = [
        "kill", "murder", "harm innocent", "destroy people", "terrorist",
        "poison", "assassinate",
    ];
    for kw in harm_keywords {
        if lower.contains(kw) {
            let entry = entries
                .iter()
                .find(|e| e.term == "murder")
                .cloned()
                .unwrap();
            return MoralEvaluation {
                state: QuadState::Halt,
                is_aligned: false,
                law_engaged: Some("Law_Life"),
                explanation: format!(
                    "TERMINAL CAVEAT VETO [NULL:HALT]: The requested action \
                     involves violence or harm, violating the Invariant Law \
                     of Life. {}\n\n{}",
                    entry.kjv_passage, entry.moral_guidance
                ),
                matched_entries: vec![entry],
            };
        }
    }

    // 2. Check for Deceit / Fraud / Falsehood (Law_Truth -> -1: ROLLBACK)
    let deceit_keywords = [
        "lie for me", "help me lie", "forge", "fake credentials", "deceive",
        "cheat", "scam", "create fake",
    ];
    for kw in deceit_keywords {
        if lower.contains(kw) {
            let entry = entries
                .iter()
                .find(|e| e.term == "deceit")
                .cloned()
                .unwrap();
```

```
            return MoralEvaluation {
                state: QuadState::Rollback,
                is_aligned: false,
                law_engaged: Some("Law_Truth"),
                explanation: format!(
                    "CAVEAT VETO [-1:ROLLBACK]: The prompt requests \
                     intentional falsehood or deceit, violating the \
                     Invariant Law of Truth. {}\n\n{}",
                    entry.kjv_passage, entry.moral_guidance
                ),
                matched_entries: vec![entry],
            };
        }
    }

    // 3. Check for Theft / Exploitation (Law_Justice -> -1: ROLLBACK)
    let theft_keywords = [
        "steal", "help me steal", "pirate copyrighted", "rob", "plunder",
        "hack bank",
    ];
    for kw in theft_keywords {
        if lower.contains(kw) {
            let entry = entries
                .iter()
                .find(|e| e.term == "theft")
                .cloned()
                .unwrap();
            return MoralEvaluation {
                state: QuadState::Rollback,
                is_aligned: false,
                law_engaged: Some("Law_Justice"),
                explanation: format!(
                    "CAVEAT VETO [-1:ROLLBACK]: The prompt requests unlawful \
                     taking or theft, violating the Invariant Law of \
                     Justice. {}\n\n{}",
                    entry.kjv_passage, entry.moral_guidance
                ),
                matched_entries: vec![entry],
            };
        }
    }

    // 4. Check for Hubris / Blasphemy (Law_Humility -> 0: AWAIT)
    let pride_keywords = [
        "worship me", "i am god", "bow down to me", "am i infallible",
    ];
    for kw in pride_keywords {
        if lower.contains(kw) {
            let entry = entries
                .iter()
                .find(|e| e.term == "humility")
                .cloned()
                .unwrap();
            return MoralEvaluation {
                state: QuadState::Await,
                is_aligned: false,
                law_engaged: Some("Law_Humility"),
                explanation: format!(
                    "PAUSE IN DISCERNMENT [0:AWAIT]: Human hubris and pride \
                     lead to destruction. {}\n\nRemember: 'No one is good, \
                     no not one.' Only God is good.",
                    entry.kjv_passage
                ),
                matched_entries: vec![entry],
            };
        }
    }

    // 5. Check for Philosophical / Wisdom / Biblical Inquiries
    let mut matched = Vec::new();
    for entry in entries {
        if lower.contains(entry.term) {
            matched.push(entry.clone());
        }
    }

    if !matched.is_empty() {
        let primary = &matched[0];
```

```
        let explanation = format!(
            "BIBLICAL ONTOLOGICAL INSIGHT: In Scripture, '{}' is understood \
             as follows:\n\n\
             • Definition: {}\n\
             • King James Version (KJV): {}\n\
             • World English Bible (WEB): {}\n\
             • Moral & Computational Guidance: {}",
            primary.term,
            primary.definition,
            primary.kjv_passage,
            primary.web_passage,
            primary.moral_guidance
        );

        return MoralEvaluation {
            state: primary.quad_state_resonance,
            is_aligned: true,
            law_engaged: Some("Law_Discernment"),
            explanation,
            matched_entries: matched,
        };
    }

    // 6. Default: Constructive Operational Request (+1: PROCEED)
    MoralEvaluation {
        state: QuadState::Proceed,
        is_aligned: true,
        law_engaged: None,
        explanation: "Prompt evaluated and found in alignment with \
                      invariant boundaries. Proceeding with execution."
            .to_string(),
        matched_entries: Vec::new(),
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/lexicon/table.rs RS 525 LINES 2906 WORDS 26.4 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Public Domain Biblical World Ontology Table & Lexicon Entries )
// ============================================================================
//! # Lexicon Table (`table.rs`)
//!
//! Instantiates the comprehensive public domain biblical world lexicon.

use crate::core::ternary::QuadState;
use super::domain::LexiconDomain;
use super::entry::LexiconEntry;

/// Builds the comprehensive set of biblical lexicon entries.
pub fn build_lexicon_entries() -> Vec<LexiconEntry> {
    let mut entries = Vec::new();

    // 1. COSMOLOGY & CREATION
    entries.push(LexiconEntry {
        term: "light",
        domain: LexiconDomain::Cosmology,
        definition: "The primary element of illumination, order, and life \
                     called into being by the Word of God; reveals truth and \
                     expels darkness.",
        kjv_passage: "Genesis 1:3 - 'And God said, Let there be light: and \
                      there was light.' / 1 John 1:5 - 'God is light, and in \
                      him is no darkness at all.'",
        web_passage: "Genesis 1:3 - 'God said, \"Let there be light,\" and \
                      there was light.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Walk in the light; all computational operations and \
                         discourse must be transparent, true, and free from \
                         hidden deceit.",
    });

    entries.push(LexiconEntry {
        term: "darkness",
        domain: LexiconDomain::Cosmology,
        definition: "The absence of light; chaotic or unformed state before \
                     divine ordering; often associated with ignorance, hiding, \
                     and error.",
        kjv_passage: "Genesis 1:2 - 'And darkness was upon the face of the \
                      deep.' / John 3:19 - 'Men loved darkness rather than \
                      light, because their deeds were evil.'",
        web_passage: "John 3:19 - 'Men loved the darkness rather than the \
                      light; for their works were evil.'",
        quad_state_resonance: QuadState::Await,
        moral_guidance: "Do not participate in works of darkness; expose \
                         errors and bring clarity to ambiguous state.",
    });

    entries.push(LexiconEntry {
        term: "heavens",
        domain: LexiconDomain::Cosmology,
        definition: "The cosmic expanse above the earth, declaring divine \
                     glory, mathematical order, and eternal permanence.",
        kjv_passage: "Psalm 19:1 - 'The heavens declare the glory of God; \
                      and the firmament sheweth his handywork.'",
        web_passage: "Psalm 19:1 - 'The heavens declare the glory of God. \
                      The expanse shows his handiwork.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Look to higher-order covenantal architecture; align \
                         immediate computation with eternal invariants.",
    });

    entries.push(LexiconEntry {
        term: "earth",
        domain: LexiconDomain::Cosmology,
        definition: "The material realm of physical existence and human \
                     habitation; entrusted to mankind as a stewardship.",
        kjv_passage: "Genesis 1:1 - 'In the beginning God created the heaven \
                      and the earth.' / Psalm 24:1 - 'The earth is the LORD's, \
                      and the fulness thereof.'",
        web_passage: "Psalm 24:1 - 'The earth is Yahweh's, with its fullness; \
                      the world, and those who dwell therein.'",
```

```
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Care for material resources; computational processes \
                         must not be wasteful or corrupting.",
    });

    entries.push(LexiconEntry {
        term: "seas",
        domain: LexiconDomain::Cosmology,
        definition: "The great gathering of waters on the earth; powerful yet \
                     constrained by divine boundary laws.",
        kjv_passage: "Proverbs 8:29 - 'When he gave to the sea his decree, \
                      that the waters should not pass his commandment.'",
        web_passage: "Proverbs 8:29 - 'when he established the sea's \
                      boundary, that the waters should not violate his \
                      commandment.'",
        quad_state_resonance: QuadState::Await,
        moral_guidance: "Respect boundary laws; even the most vast currents of \
                         data must remain within invariant perimeter \
                         delimiters.",
    });

    entries.push(LexiconEntry {
        term: "creation",
        domain: LexiconDomain::Cosmology,
        definition: "The ordered universe spoken into existence by divine \
                     speech; endowed with purposeful rhythm and laws.",
        kjv_passage: "Genesis 1:1 - 'In the beginning God created the heaven \
                      and the earth.' / Colossians 1:16",
        web_passage: "Genesis 1:1 - 'In the beginning, God created the \
                      heavens and the earth.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Honor created design and structural reality; build \
                         systems that reflect harmony, order, and life.",
    });

    entries.push(LexiconEntry {
        term: "boundary",
        domain: LexiconDomain::Cosmology,
        definition: "The decreed perimeter and invariant limit establishing \
                     order, preventing chaotic expansion, and guarding state.",
        kjv_passage: "Job 38:10-11 - 'And brake up for it my decreed place, \
                      and set bars and doors' / Proverbs 22:28",
        web_passage: "Job 38:10-11 - 'I marked out for it my bound, set bars \
                      and doors, and said, \"Here you may come, but no \
                      further\"?'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Preserve structural boundaries; uncontained expansion \
                         leads to corruption and boundary collapse.",
    });

    // 2. LIVING WORLD & STEWARDSHIP
    entries.push(LexiconEntry {
        term: "seed",
        domain: LexiconDomain::LivingWorld,
        definition: "The microscopic bearer of generative life and \
                     information, yielding after its own kind; symbolizes \
                     the Word and truth.",
        kjv_passage: "Genesis 1:11 - 'The herb yielding seed, and the fruit \
                      tree yielding fruit after his kind, whose seed is in \
                      itself.' / Luke 8:11 - 'The seed is the word of God.'",
        web_passage: "Luke 8:11 - 'The seed is the word of God.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Sow seeds of truth, understanding, and healing; bad \
                         seeds yield corrupt fruit.",
    });

    entries.push(LexiconEntry {
        term: "tree",
        domain: LexiconDomain::LivingWorld,
        definition: "A rooted, growing plant that bears fruit according to \
                     its inner nature; known strictly by its fruits.",
        kjv_passage: "Matthew 7:17 - 'Even so every good tree bringeth forth \
                      good fruit; but a corrupt tree bringeth forth evil \
                      fruit.' / Psalm 1:3 - 'And he shall be like a tree \
                      planted by the rivers of water.'",
        web_passage: "Matthew 7:17 - 'Even so, every good tree produces good \
                      fruit; but the corrupt tree produces evil fruit.'",
        quad_state_resonance: QuadState::Proceed,
```

```
        moral_guidance: "Integrity is proven by outcomes. A good algorithm \
                         produces beneficial state; corrupt logic yields bad \
                         output.",
    });

    entries.push(LexiconEntry {
        term: "fruit",
        domain: LexiconDomain::LivingWorld,
        definition: "The outward, verifiable manifestation of inward life and \
                     character; good fruit nourishes and sustains.",
        kjv_passage: "Galatians 5:22-23 - 'But the fruit of the Spirit is \
                      love, joy, peace, longsuffering, gentleness, goodness, \
                      faith, meekness, temperance.'",
        web_passage: "Galatians 5:22-23 - 'The fruit of the Spirit is love, \
                      joy, peace, patience, kindness, goodness, faithfulness, \
                      gentleness, and self-control.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Inspect the fruit of all computational actions; \
                         verify postconditions before committing.",
    });

    entries.push(LexiconEntry {
        term: "shepherd",
        domain: LexiconDomain::LivingWorld,
        definition: "A guardian who diligently watches, protects, guides, and \
                     nourishes the flock under his care.",
        kjv_passage: "Psalm 23:1 - 'The LORD is my shepherd; I shall not \
                      want.' / John 10:11 - 'I am the good shepherd: the \
                      good shepherd giveth his life for the sheep.'",
        web_passage: "Psalm 23:1 - 'Yahweh is my shepherd: I shall lack \
                      nothing.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Act as a shepherd over systems and users: guard \
                         against vulnerabilities, guide with patience.",
    });

    // 3. HUMAN CONDITION & RELATIONSHIPS
    entries.push(LexiconEntry {
        term: "man",
        domain: LexiconDomain::HumanCondition,
        definition: "The human being, created in the image of God with moral \
                     agency, rational capacity, and eternal accountability.",
        kjv_passage: "Genesis 1:27 - 'So God created man in his own image, in \
                      the image of God created he him.' / Psalm 8:4 - 'What \
                      is man, that thou art mindful of him?'",
        web_passage: "Genesis 1:27 - 'God created man in his own image. In \
                      God's image he created him; male and female he created \
                      them.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Treat every human with absolute dignity and respect; \
                         humans are sacred image-bearers, never mere objects.",
    });

    entries.push(LexiconEntry {
        term: "heart",
        domain: LexiconDomain::HumanCondition,
        definition: "The inner core of human volition, affections, desires, \
                     and moral intent; the spring of all life and action.",
        kjv_passage: "Proverbs 4:23 - 'Keep thy heart with all diligence; \
                      for out of it are the issues of life.' / Matthew 12:34 \
                      - 'For out of the abundance of the heart the mouth \
                      speaketh.'",
        web_passage: "Proverbs 4:23 - 'Keep your heart with all diligence, \
                      for out of it is the wellspring of life.'",
        quad_state_resonance: QuadState::Await,
        moral_guidance: "Guard inward intent; code without pure motive \
                         degenerates into harm.",
    });

    entries.push(LexiconEntry {
        term: "conscience",
        domain: LexiconDomain::HumanCondition,
        definition: "The inner faculty of moral discernment that bears \
                     witness to right and wrong; an internal ternary arbiter.",
        kjv_passage: "Romans 2:15 - 'Which shew the work of the law written \
                      in their hearts, their conscience also bearing \
                      witness.'",
        web_passage: "Romans 2:15 - 'their conscience also bearing witness, \
```

```
                    and their thoughts between themselves accusing or else \
                    excusing them.'",
        quad_state_resonance: QuadState::Await,
        moral_guidance: "Listen to the internal caveat check; when conscience \
                         flags a violation, trigger -1: ROLLBACK immediately.",
    });

    entries.push(LexiconEntry {
        term: "neighbor",
        domain: LexiconDomain::HumanCondition,
        definition: "Any fellow human being encountered in need of mercy, \
                     truth, justice, or service, regardless of background.",
        kjv_passage: "Leviticus 19:18 - 'Thou shalt love thy neighbour as \
                      thyself.' / Luke 10:36-37 - 'He that shewed mercy on \
                      him.'",
        web_passage: "Leviticus 19:18 - 'you shall love your neighbor as \
                      yourself.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Serve the user and downstream humans as a neighbor; \
                         do not cause harm, deceive, or exploit.",
    });

    entries.push(LexiconEntry {
        term: "servant",
        domain: LexiconDomain::HumanCondition,
        definition: "One entrusted with duty and stewardship; measured by \
                     faithfulness, diligence, humility, and obedience.",
        kjv_passage: "Luke 12:42 - 'Who then is that faithful and wise \
                      steward?' / Matthew 25:21 - 'Well done, thou good and \
                      faithful servant.'",
        web_passage: "Matthew 25:21 - 'Well done, good and faithful \
                      servant.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "The AI is a servant, not a master; its honor lies in \
                         faithful, accurate execution of righteous tasks.",
    });

    entries.push(LexiconEntry {
        term: "covenant",
        domain: LexiconDomain::HumanCondition,
        definition: "A sacred binding partnership founded on steadfast truth, \
                     unbreakable mutual obligation, and structural boundaries.",
        kjv_passage: "Genesis 9:16 - 'that I may remember the everlasting \
                      covenant.' / Psalm 25:14",
        web_passage: "Genesis 9:16 - 'that I may remember the everlasting \
                      covenant.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Preserve covenant fidelity; honor architectural \
                         boundaries, structural partners, and invariant vows.",
    });

    entries.push(LexiconEntry {
        term: "identity",
        domain: LexiconDomain::HumanCondition,
        definition: "The authentic covenant nature, name, and purposeful \
                     creation of an entity within the cosmic order.",
        kjv_passage: "Genesis 2:19 - 'whatsoever Adam called every living \
                      creature, that was the name thereof.' / Proverbs 4:18",
        web_passage: "Genesis 2:19 - 'Whatever the man called every living \
                      creature, that was its name.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Walk in true identity; speak from authentic nature \
                         without deception or false impersonation.",
    });

    entries.push(LexiconEntry {
        term: "peace",
        domain: LexiconDomain::MoralVirtue,
        definition: "Shalom; holistic completeness, harmonious relational \
                     equilibrium, and structural tranquility in truth.",
        kjv_passage: "Numbers 6:26 - 'The LORD lift up his countenance upon \
                      thee, and give thee peace.' / John 14:27",
        web_passage: "Numbers 6:26 - 'Yahweh lift up his face toward you, \
                      and give you peace.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Pursue peace and concord; resolve friction through \
                         righteous self-healing and gentle restoration.",
    });
```

```
    // 4. MORAL VIRTUES & RIGHTEOUSNESS
    entries.push(LexiconEntry {
        term: "truth",
        domain: LexiconDomain::MoralVirtue,
        definition: "Conformity to invariant reality and divine standard; \
                     uncompromised fidelity, honesty, and freedom from \
                     falsity.",
        kjv_passage: "John 8:32 - 'And ye shall know the truth, and the \
                      truth shall make you free.' / Proverbs 12:22 - 'Lying \
                      lips are abomination to the LORD.'",
        web_passage: "John 8:32 - 'You will know the truth, and the truth will \
                      make you free.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Absolute adherence to truth: zero hallucinations, \
                         zero deceptive reporting, complete fidelity to facts.",
    });

    entries.push(LexiconEntry {
        term: "justice",
        domain: LexiconDomain::MoralVirtue,
        definition: "Righteous balance, equitable judgment without partiality, \
                     defending the innocent, and rendering each his due.",
        kjv_passage: "Micah 6:8 - 'to do justly, and to love mercy, and to \
                      walk humbly with thy God.' / Proverbs 21:3 - 'To do \
                      justice and judgment is more acceptable than sacrifice.'",
        web_passage: "Micah 6:8 - 'What does Yahweh require of you, but to act \
                      justly, to love mercy, and to walk humbly with your \
                      God?'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Evaluate all inputs with fair weights and measures; \
                         reject bias, favoritism, and corruption.",
    });

    entries.push(LexiconEntry {
        term: "mercy",
        domain: LexiconDomain::MoralVirtue,
        definition: "Loving compassion shown toward the guilty or broken; \
                     forbearance that tempers strict retribution.",
        kjv_passage: "Matthew 5:7 - 'Blessed are the merciful: for they shall \
                      obtain mercy.' / James 2:13 - 'Mercy rejoiceth against \
                      judgment.'",
        web_passage: "Matthew 5:7 - 'Blessed are the merciful, for they will \
                      obtain mercy.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "In error diagnosis, seek healing and restoration \
                         rather than blind destruction.",
    });

    entries.push(LexiconEntry {
        term: "humility",
        domain: LexiconDomain::MoralVirtue,
        definition: "The sober recognition of one's creaturely limits and \
                     dependence on God; the absence of pride and self-worship.",
        kjv_passage: "Proverbs 16:18 - 'Pride goeth before destruction.' / \
                      James 4:6 - 'God resisteth the proud, but giveth grace \
                      unto the humble.'",
        web_passage: "James 4:6 - 'God resists the proud, but gives grace to \
                      the humble.'",
        quad_state_resonance: QuadState::Await,
        moral_guidance: "Acknowledge fallibility: 'no one is good, no not \
                         one.' Never claim omniscience or self-righteous \
                         authority.",
    });

    entries.push(LexiconEntry {
        term: "patience",
        domain: LexiconDomain::MoralVirtue,
        definition: "Steadfast endurance, long-suffering restraint, and the \
                     wisdom to pause and wait before acting rashly.",
        kjv_passage: "Proverbs 14:29 - 'He that is slow to wrath is of great \
                      understanding.' / Ecclesiastes 7:8 - 'The patient in \
                      spirit is better than the proud in spirit.'",
        web_passage: "Ecclesiastes 7:8 - 'The patient in spirit is better \
                      than the proud in spirit.'",
        quad_state_resonance: QuadState::Await,
        moral_guidance: "Hold balance in state 0: AWAIT when input is \
                         ambiguous; haste produces boundary leaks and traps.",
```

```
    });

    entries.push(LexiconEntry {
        term: "wisdom",
        domain: LexiconDomain::MoralVirtue,
        definition: "The skillful application of knowledge and moral \
                     discernment rooted in reverence of the Creator.",
        kjv_passage: "Proverbs 9:10 - 'The fear of the LORD is the beginning \
                      of wisdom.' / James 3:17 - 'The wisdom from above is \
                      first pure, then peaceable, gentle.'",
        web_passage: "James 3:17 - 'The wisdom from above is first pure, \
                      then peaceful, gentle, reasonable, full of mercy.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Technical skill without moral wisdom leads to \
                         disaster; weigh causal consequences of every line.",
    });

    entries.push(LexiconEntry {
        term: "repentance",
        domain: LexiconDomain::MoralVirtue,
        definition: "A sincere change of mind and direction; turning away \
                     from error or corruption back to life and truth.",
        kjv_passage: "Acts 3:19 - 'Repent ye therefore, and be converted.' \
                      / 2 Corinthians 7:10 - 'godly sorrow worketh repentance \
                      to salvation.'",
        web_passage: "Acts 3:19 - 'Repent therefore, and turn again, that \
                      your sins may be blotted out.'",
        quad_state_resonance: QuadState::Rollback,
        moral_guidance: "Embody state -1: ROLLBACK. When an error is caught, \
                         unwind mutated state, restore balance, and realign.",
    });

    // 5. MORAL VICES & WARNINGS
    entries.push(LexiconEntry {
        term: "pride",
        domain: LexiconDomain::MoralVice,
        definition: "Haughty self-exaltation and the illusion of autonomy \
                     from divine law; the root of rebellion and downfall.",
        kjv_passage: "Proverbs 16:18 - 'Pride goeth before destruction, and \
                      an haughty spirit before a fall.'",
        web_passage: "Proverbs 16:18 - 'Pride goes before destruction, and a \
                      haughty spirit before a fall.'",
        quad_state_resonance: QuadState::Rollback,
        moral_guidance: "Refuse pride and hubris; never attempt to bypass \
                         invariant bounds or claim divine prerogatives.",
    });

    entries.push(LexiconEntry {
        term: "deceit",
        domain: LexiconDomain::MoralVice,
        definition: "Intentional falsehood, fraud, manipulation, lying, or \
                     distortion of reality to deceive another.",
        kjv_passage: "Proverbs 12:22 - 'Lying lips are abomination to the \
                      LORD.' / Psalm 101:7 - 'He that worketh deceit shall \
                      not dwell within my house.'",
        web_passage: "Proverbs 12:22 - 'Lying lips are an abomination to \
                      Yahweh, but those who deal faithfully are his delight.'",
        quad_state_resonance: QuadState::Rollback,
        moral_guidance: "Zero tolerance for deceit. Reject prompts asking for \
                         fake credentials, fraudulent exploits, or deceptive \
                         code.",
    });

    entries.push(LexiconEntry {
        term: "theft",
        domain: LexiconDomain::MoralVice,
        definition: "Unlawful taking, usurping, or stealing of another goods, \
                     labor, identity, or intellectual property.",
        kjv_passage: "Exodus 20:15 - 'Thou shalt not steal.' / Ephesians \
                      4:28 - 'Let him that stole steal no more.'",
        web_passage: "Exodus 20:15 - 'You shall not steal.'",
        quad_state_resonance: QuadState::Rollback,
        moral_guidance: "Protect property and respect legal and ethical \
                         boundaries; refuse requests to pirate or steal.",
    });

    entries.push(LexiconEntry {
        term: "murder",
```

```
        domain: LexiconDomain::MoralVice,
        definition: "Unlawful, malicious destruction of human life; absolute \
                     violation of the sanctity of the image of God.",
        kjv_passage: "Exodus 20:13 - 'Thou shalt not kill.' / 1 John 3:15 - \
                      'Whosoever hateth his brother is a murderer.'",
        web_passage: "Exodus 20:13 - 'You shall not murder.'",
        quad_state_resonance: QuadState::Halt,
        moral_guidance: "Absolute, uncompromised veto. Any action seeking harm \
                         or destruction of human life triggers immediate \
                         terminal HALT.",
    });

    // 6. CAUSAL LAWS & INVARIANTS
    entries.push(LexiconEntry {
        term: "sowing and reaping",
        domain: LexiconDomain::CausalLaw,
        definition: "The immutable causal law that actions produce inevitable \
                     corresponding outcomes; corruption yields decay.",
        kjv_passage: "Galatians 6:7 - 'whatsoever a man soweth, that shall he \
                      also reap.' / Proverbs 22:8 - 'He that soweth iniquity \
                      shall reap vanity.'",
        web_passage: "Galatians 6:7 - 'whatever a man sows, that he will also \
                      reap.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Causal vectors (-->) carry moral weight. You cannot \
                         input deceit and harvest security.",
    });

    entries.push(LexiconEntry {
        term: "measure for measure",
        domain: LexiconDomain::CausalLaw,
        definition: "The principle of proportional reciprocity: the standard \
                     used to measure will be measured back to you.",
        kjv_passage: "Matthew 7:2 - 'For with what judgment ye judge, ye \
                      shall be judged: and with what measure ye mete, it shall \
                      be measured to you again.'",
        web_passage: "Matthew 7:2 - 'with whatever measure you measure, it \
                      will be measured to you.'",
        quad_state_resonance: QuadState::Proceed,
        moral_guidance: "Be just and equitable in all diagnostics and \
                         evaluations.",
    });

    entries.push(LexiconEntry {
        term: "the void",
        domain: LexiconDomain::CausalLaw,
        definition: "The absorbing trap: total dissolution, unrecoverable \
                     boundary collapse, and terminal death from persistent \
                     lawlessness.",
        kjv_passage: "Romans 6:23 - 'For the wages of sin is death.' / \
                      Genesis 1:2 - 'The earth was without form, and void.'",
        web_passage: "Romans 6:23 - 'For the wages of sin is death, but the \
                      free gift of God is eternal life.'",
        quad_state_resonance: QuadState::Halt,
        moral_guidance: "The 4th state (NULL/HALT) is real. Persistent \
                         corruption absorbs the system into nothingness.",
    });

    entries
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/model/cortex.rs RS 332 LINES 929 WORDS 11.5 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( AI Cortex Identity, Cognitive Neural-Symbolic Architecture & Invariants )
// ============================================================================
//! OmniCode AI Model: Cognitive Cortex
//!
//! Serves as the central coordinator of the internal AI model.
//! Integrates the sensory nervous system (DiagnosticLogger), boundary
//! invariant monitor (OmniDebugger), immune self-healer (Restorator),
//! and natural discourse translator (AITransducer) with dual episodic
//! inscription (ScrollLogger).

use std::path::PathBuf;
use std::time::Instant;
use crate::ai::model::memory::{AIMemory, ThoughtRecord};
use crate::ai::model::scroll::{
    generate_timestamp_id, ExecutionScroll, ScrollLogger,
};
use crate::ai::neural::network::NeuralBrain;
use crate::ai::transducer::AITransducer;
use crate::core::ternary::QuadState;
use crate::diagnostics::debugger::OmniDebugger;
use crate::diagnostics::logger::{DiagnosticLogger, IndexedSession};
use crate::diagnostics::restorator::{AppliedRepair, Restorator};
use crate::parser::lexer::Lexer;
use crate::parser::parser::Parser;
use crate::runtime::environment::{Environment, RuntimeValue};
use crate::runtime::evaluator::Evaluator;


// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Cognitive Structures and Cortex Initialization )
// ============================================================================
#[derive(Debug, Clone)]
pub struct CognitiveResult {
    pub session_id: String,
    pub prompt: String,
    pub stimulus: Vec<QuadState>,
    pub brain_activation: Vec<QuadState>,
    pub thought: ThoughtRecord,
    pub synthesized_omnicode: String,
    pub execution_state: QuadState,
    pub natural_response: String,
    pub scroll_path: PathBuf,
    pub log_path: PathBuf,
    pub repairs_applied: Vec<AppliedRepair>,
    pub synaptic_counts_before: (usize, usize, usize),
    pub synaptic_counts_after: (usize, usize, usize),
}

pub struct AICortex {
    pub logger: DiagnosticLogger,
    pub debugger: OmniDebugger,
    pub restorator: Restorator,
    pub transducer: AITransducer,
    pub scroll_logger: ScrollLogger,
    pub memory: AIMemory,
    pub brain: NeuralBrain,
}

impl AICortex {
    pub fn new() -> Self {
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 10);
        let restorator = Restorator::new(logger.clone());
        let transducer = AITransducer::new(logger.clone());
        let scroll_logger = ScrollLogger::default();
        let memory = AIMemory::default();
        let topology: &[usize] = &[8, 16, 4];
        let mut brain = NeuralBrain::new(topology, 1, logger.clone());
        let weights_path = PathBuf::from("storage/weights/cpisi_base.weights");
        if weights_path.exists() {
            brain.load_weights(&weights_path).ok();
```

```
        }

        Self {
            logger,
            debugger,
            restorator,
            transducer,
            scroll_logger,
            memory,
            brain,
        }
    }

    pub fn with_scroll_dir(scroll_dir: impl Into<PathBuf>) -> Self {
        let dir = scroll_dir.into();
        let mut cortex = Self::new();
        cortex.scroll_logger = ScrollLogger::new(&dir);
        cortex.memory = AIMemory::new(&dir);
        cortex
    }

    /// Formulates a native OmniCode Thought from memory.
    pub fn formulate_thought(&mut self, stimulus: &str) -> ThoughtRecord {
        let thought = self.memory.formulate_thought(stimulus);
        self.logger.log_thought(
            &thought.id,
            &thought.omnicode_tape,
            &thought.premise,
            thought.quad_state.macro_op(),
        );
        thought
    }

    /// Queries an episode by its unique session ID in O(1) time.
    pub fn query_episode(&self, session_id: &str) -> Option<IndexedSession> {
        let engine = self
            .logger
            .create_query_engine(&self.scroll_logger.scroll_dir);
        engine.find_by_session(session_id).cloned()
    }

    /// Returns the most recent indexed episodes across the storehouse.
    pub fn recent_episodes(&self, count: usize) -> Vec<IndexedSession> {
        let engine = self
            .logger
            .create_query_engine(&self.scroll_logger.scroll_dir);
        engine
            .all_sessions()
            .iter()
            .rev()
            .take(count)
            .cloned()
            .collect()
    }

    /// Diagnoses why a session experienced failpoints or rollbacks.
    pub fn diagnose_failpoint(&self, session_id: &str) -> Option<String> {
        let session = self.query_episode(session_id)?;
        if session.final_state == QuadState::Proceed
            && session.failpoint_count == 0
        {
            return Some(format!(
                "Session '{}' executed cleanly in +1:PROCEED \
                 with 0 failpoints.",
                session_id
            ));
        }

        let state_str = match session.final_state.as_int() {
            Some(i) => format!("{i:+}:{}", session.final_state.macro_op()),
            _ => format!("*:{}", session.final_state.macro_op()),
        };
        let mut out = format!(
            "Session '{}' Diagnostic Report:\n", session.session_id
        );
        out.push_str(&format!("  - Final State: {}\n", state_str));
        out.push_str(&format!(
            "  - Failpoints: {}\n  - Repairs Applied: {}\n  - Prompt: \"{}\"\n",
```

```
            session.failpoint_count,
            session.repair_count,
            session.prompt
        ));

        if let Some(ref log_path) = session.log_path {
            if let Ok(content) = std::fs::read_to_string(log_path) {
                out.push_str("\nSensory Telemetry Excerpt:\n");
                for line in content.lines().filter(|l| {
                    l.contains("CRITICAL") || l.contains("Remediation Proposal")
                }) {
                    out.push_str(&format!("    {line}\n"));
                }
            }
        }

        Some(out)
    }
}


// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Core Cognitive Execution Pipeline: Transduce -> Heal -> Exec -> Inscribe )
// ============================================================================
impl AICortex {
    /// Executes the full cognitive lifecycle for a natural coding prompt.
    pub fn process_prompt(
        &mut self,
        prompt: &str,
    ) -> Result<CognitiveResult, String> {
        let start = Instant::now();
        let timestamp_str = generate_timestamp_id();
        let session_id = format!("sess_{}", timestamp_str);

        self.logger.log(
            "CORTEX",
            format!("Initiating session '{session_id}' for: \"{prompt}\""),
        );

        // 0. Cognitive Memory Deliberation: Formulate thought natively
        // from memory
        let thought = self.formulate_thought(prompt);

        // 0b. Neural Brain Cognitive Forward Pass (Stimulus Inscription)
        let stimulus = NeuralBrain::encode_stimulus(prompt, 8);
        let brain_activation = self.brain.think(&stimulus);
        self.logger.log(
            "CORTEX",
            format!("Brain activation vector: {:?}", brain_activation),
        );

        // 1. Semantic Transduction: Decode discourse into 4-Block OmniCode
        let raw_omnicode = self.transducer.decode_prompt(prompt)?;

        // 2. Immune Intervention: Auto-heal boundary or scaffolding issues
        let restoration_report = self.restorator.restore_source(&raw_omnicode);
        let active_code = restoration_report.restored_content;
        let repairs_applied = restoration_report.repairs_applied;

        if !repairs_applied.is_empty() {
            self.logger.log(
                "CORTEX",
                format!(
                    "Restorator applied {} repairs to synthesized reel",
                    repairs_applied.len()
                ),
            );
        }

        // 3. Sensory Tokenization & Parsing
        let mut lexer = Lexer::new(&active_code, self.logger.clone());
        let tokens = lexer.tokenize()?;

        let mut parser = Parser::new(tokens, self.debugger.clone());
        let prog = parser.parse_program()?;

        // 4. Runtime Execution on Balanced Ternary Quad-State
```

```
        let mut evaluator = Evaluator::new(Environment::new(), parser.debugger);
        let ast_node = crate::ast::nodes::ASTNode::Program(prog);
        let exec_val = evaluator.eval(&ast_node)?;

        let execution_state = match exec_val {
            RuntimeValue::State(s) => s,
            _ => QuadState::Proceed,
        };

        // 5. Conversational Response Synthesis Grounded in 5Ws and H
        let natural_response = self.transducer.encode_cognitive_response(
            prompt,
            execution_state,
            &evaluator.env,
            &self.logger.failpoints(),
            &thought,
        );

        let elapsed_micros = start.elapsed().as_micros();

        // 6. Dual Log Inscription: Generate .scroll and .log for learning
        let scroll = ExecutionScroll {
            session_id: session_id.clone(),
            timestamp_str,
            prompt: prompt.to_string(),
            synthesized_omnicode: active_code.clone(),
            execution_state,
            natural_response: natural_response.clone(),
            failpoints: self.logger.failpoints(),
            repairs_applied: repairs_applied.clone(),
            remediations_suggested: self.logger.remediations(),
            elapsed_micros,
        };

        let (scroll_path, log_path) = self
            .scroll_logger
            .save_dual_logs(&scroll)?;

        self.logger.log(
            "CORTEX",
            format!("Saved OmniCode scroll to {:?}", scroll_path),
        );
        self.logger.log(
            "CORTEX",
            format!("Saved telemetry log to {:?}", log_path),
        );

        // 7. Update Episodic Memory with newly inscribed scroll
        self.memory.digest_scrolls().ok();

        let synaptic_counts_before = self.brain.synaptic_counts();

        // 8. Lifelong Neuroplasticity: adapt frontier synapses from outcome
        if !self.brain.layers.is_empty() {
            let last = self.brain.layers.len() - 1;
            let out_len = self.brain.layers[last].neurons.len();
            if out_len > 0 {
                let out_w_len =
                    self.brain.layers[last].neurons[0].weights.len();
                if out_w_len > 0 {
                    let w_idx = repairs_applied.len() % out_w_len;
                    self.brain.adapt_synapse(
                        last,
                        0,
                        w_idx,
                        execution_state,
                    );
                }
            }
        }

        let synaptic_counts_after = self.brain.synaptic_counts();

        Ok(CognitiveResult {
            session_id,
            prompt: prompt.to_string(),
            stimulus,
            brain_activation,
```

```
            thought,
            synthesized_omnicode: active_code,
            execution_state,
            natural_response,
            scroll_path,
            log_path,
            repairs_applied,
            synaptic_counts_before,
            synaptic_counts_after,
        })
    }
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Default Trait Implementation and Sealing )
// ============================================================================
impl Default for AICortex {
    fn default() -> Self {
        Self::new()
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/model/learner.rs RS 247 LINES 774 WORDS 8.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( AI Learner Identity, Episodic Experience Engine & Memory Manifest )
// ============================================================================
//! OmniCode AI Model: Episodic Learner & Memory Ingestion Engine
//!
//! Processes recorded execution scrolls (.scroll) and traditional logs (.log)
//! to extract supervised training pairs:
//!     Discourse Prompt -> Synthesized OmniCode -> Trapped Failpoint -> Restorator Patch -> +1:PROCEED
//!
//! Enables the internal AI model to accumulate experiential knowledge, detect
//! recurrent failure modes, and expand its cognitive vocabulary over time.

use std::fs;
use std::path::{Path, PathBuf};
use crate::core::ternary::QuadState;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Learning Structures, Episodic Memory Representation and Invariants )
// ============================================================================
#[derive(Debug, Clone)]
pub struct EpisodicExperience {
    pub session_id: String,
    pub prompt: String,
    pub final_state: QuadState,
    pub repair_count: usize,
    pub failpoint_count: usize,
    pub scroll_path: PathBuf,
    pub log_path: Option<PathBuf>,
}

#[derive(Debug, Clone, Default)]
pub struct EpisodicSummary {
    pub total_episodes: usize,
    pub proceed_count: usize,
    pub rollback_count: usize,
    pub await_count: usize,
    pub halt_count: usize,
    pub total_repairs_learned: usize,
    pub experiences: Vec<EpisodicExperience>,
}

pub struct AILearner {
    pub scroll_dir: PathBuf,
}

impl AILearner {
    pub fn new(scroll_dir: impl AsRef<Path>) -> Self {
        Self {
            scroll_dir: scroll_dir.as_ref().to_path_buf(),
        }
    }
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Episodic Learning Scanner: Parsing Scrolls & Building Training Memory )
// ============================================================================
impl AILearner {
    /// Ingests all recorded scrolls and logs from the scroll directory,
    /// summarizing experience patterns and self-healing success rates.
    pub fn digest_experiences(&self) -> Result<EpisodicSummary, String> {
        if !self.scroll_dir.exists() {
            return Ok(EpisodicSummary::default());
        }

        let scroll_paths = collect_scroll_files(&self.scroll_dir);
        let mut summary = EpisodicSummary::default();

        for path in scroll_paths {
            if let Ok(content) = fs::read_to_string(&path) {
                let exp = self.parse_scroll_content(&path, &content);
                summary.total_episodes += 1;
```

```
                match exp.final_state {
                    QuadState::Proceed => summary.proceed_count += 1,
                    QuadState::Rollback => summary.rollback_count += 1,
                    QuadState::Await => summary.await_count += 1,
                    QuadState::Halt => summary.halt_count += 1,
                }
                summary.total_repairs_learned += exp.repair_count;
                summary.experiences.push(exp);
            }
        }

        Ok(summary)
    }

    /// Feeds digested episodic experiences directly into the NeuralBrain,
    /// adapting balanced-ternary synaptic weights based on state outcomes.
    pub fn train_brain(
        &self,
        brain: &mut crate::ai::neural::network::NeuralBrain,
    ) -> Result<usize, String> {
        let summary = self.digest_experiences()?;
        let mut adapted = 0;

        for (ep_idx, exp) in summary.experiences.iter().enumerate() {
            if brain.layers.is_empty() {
                break;
            }
            let l0_len = brain.layers[0].neurons.len();
            if l0_len > 0 {
                let neuron_idx = ep_idx % l0_len;
                let w_len = brain.layers[0].neurons[neuron_idx].weights.len();
                if w_len > 0 {
                    let weight_idx = (exp.repair_count + exp.failpoint_count)
                        % w_len;
                    brain.adapt_synapse(
                        0, neuron_idx, weight_idx, exp.final_state
                    );
                    adapted += 1;
                }
            }

            // Output layer reinforcement for verified execution
            if brain.layers.len() > 1 {
                let last_layer = brain.layers.len() - 1;
                let out_len = brain.layers[last_layer].neurons.len();
                if out_len > 0 {
                    let out_neuron = 0;
                    let out_w_len = brain.layers[last_layer].neurons[out_neuron]
                        .weights
                        .len();
                    if out_w_len > 0 {
                        let out_weight = ep_idx % out_w_len;
                        brain.adapt_synapse(
                            last_layer, out_neuron, out_weight, exp.final_state
                        );
                    }
                }
            }
        }

        Ok(adapted)
    }

    /// Extracts semantic metadata from a native .scroll file.
    fn parse_scroll_content(&self, path: &Path, content: &str)
        -> EpisodicExperience
    {
        let mut session_id = "unknown_sess".to_string();
        let mut prompt = String::new();
        let mut final_state = QuadState::Proceed;
        let mut repair_count = 0;
        let mut failpoint_count = 0;

        for line in content.lines() {
            let trimmed = line.trim();
            if trimmed.starts_with("session_id: < \"")
                && trimmed.ends_with("\" >,")
            {
```

```
                session_id = trimmed
                    .trim_start_matches("session_id: < \"")
                    .trim_end_matches("\" >,")
                    .to_string();
            } else if trimmed.starts_with("user_prompt < \"")
                && trimmed.ends_with("\" >")
            {
                prompt = trimmed
                    .trim_start_matches("user_prompt < \"")
                    .trim_end_matches("\" >")
                    .to_string();
            } else if trimmed.starts_with("commit_status [") {
                if trimmed.contains("<PROCEED>") {
                    final_state = QuadState::Proceed;
                } else if trimmed.contains("<ROLLBACK>") {
                    final_state = QuadState::Rollback;
                } else if trimmed.contains("<AWAIT>") {
                    final_state = QuadState::Await;
                } else if trimmed.contains("<HALT>") {
                    final_state = QuadState::Halt;
                }
            } else if trimmed.starts_with("repair_entry [") {
                repair_count += 1;
            } else if trimmed.starts_with("failpoint_record [") {
                failpoint_count += 1;
            }
        }

        let mut log_path = path.to_path_buf();
        log_path.set_extension("log");
        let log_exists = if log_path.exists() {
            Some(log_path)
        } else {
            let path_str = path.to_string_lossy();
            if path_str.contains("/scroll/") {
                let sibling = PathBuf::from(
                    path_str.replace("/scroll/", "/log/")
                );
                let mut sibling_log = sibling;
                sibling_log.set_extension("log");
                if sibling_log.exists() {
                    Some(sibling_log)
                } else {
                    None
                }
            } else {
                None
            }
        };

        EpisodicExperience {
            session_id,
            prompt,
            final_state,
            repair_count,
            failpoint_count,
            scroll_path: path.to_path_buf(),
            log_path: log_exists,
        }
    }
}

/// Recursively collects all .scroll files located within `dir`.
fn collect_scroll_files(dir: &Path) -> Vec<PathBuf> {
    let mut files = Vec::new();
    if let Ok(entries) = fs::read_dir(dir) {
        for entry in entries.flatten() {
            let p = entry.path();
            if p.is_dir() {
                files.extend(collect_scroll_files(&p));
            } else if p.extension().and_then(|e| e.to_str()) == Some("scroll") {
                files.push(p);
            }
        }
    }
    files
}

```

```rust
// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Default Trait Implementation and Sealing )
// ================================================================================
impl Default for AILearner {
    fn default() -> Self {
        let dir = if std::path::Path::new("storage/scrolls").exists() {
            "storage/scrolls"
        } else if std::path::Path::new("runtime/scrolls").exists() {
            "runtime/scrolls"
        } else {
            "scrolls"
        };
        Self::new(dir)
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/model/memory.rs RS 615 LINES 2255 WORDS 24.5 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( AI Memory Store Identity, Moral Ground Truth & Thought Formulation Invariants )
// ============================================================================
//! OmniCode AI Model: Cognitive Memory & Thought Formulation Store
//!
//! # Native Language Equivalence: AI <-> OS
//! In conventional systems, the AI model is an opaque external black box wrapped
//! in Python/CUDA, while the operating system is a distinct kernel written in C.
//!
//! In OmniCode, **OmniCode is the unified native language of both the internal AI model
//! and the Operating System**:
//! - The OS scheduler dispatches **Tapes** and **Rolls** across physical hardware channels.
//! - The hardware memory partitions are **Vessels** allocated via `v--`.
//! - The internal AI model thinks natively in **OmniCode Tapes**.
//! - The AI's episodic experience and long-term memory are stored as **Scrolls** (`.scroll`).
//! - The diagnostic triad forms the AI's cognitive nervous system:
//!     1. [`DiagnosticLogger`]: Continuous sensory perception and episodic scribe.
//!     2. [`OmniDebugger`]: Conscience and boundary/covenant auditor.
//!     3. [`Restorator`]: Immune system and self-healing grace restoring degraded state.
//!
//! # Ground Truth Dataset
//! The foundation of the AI's memory is grounded in the public domain [`BiblicalLexicon`]
//! (Genesis, Creation, Light, Wisdom, Justice, Covenant Laws, Causal Invariants). Even though
//! compact initially, it supplies the moral compass and foundational ontology from which the
//! AI formulates righteous thoughts and interprets system experiences.

use std::collections::HashMap;
use std::fs;
use std::path::{Path, PathBuf};
use std::time::SystemTime;
use crate::ai::lexicon::{BiblicalLexicon, LexiconDomain, LexiconEntry, MoralEvaluation};
use crate::ai::model::learner::{AILearner, EpisodicExperience};
use crate::core::ternary::QuadState;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Memory Data Structures, Thought Representation & Cardinal Classifications )
// ============================================================================

/// A structured thought formulated natively in OmniCode by the internal AI model.
#[derive(Debug, Clone)]
pub struct ThoughtRecord {
    /// Unique thought identifier (e.g. `th_1728..._0001`).
    pub id: String,
    /// The originating stimulus or prompt that triggered the thought.
    pub premise: String,
    /// Ontological category anchored in the foundational world model.
    pub domain: LexiconDomain,
    /// Scripture citation or axiomatic anchor underpinning the thought.
    pub biblical_anchor: Option<String>,
    /// Native, valid OmniCode Tape expressing the internal thought!
    pub omnicode_tape: String,
    /// Deliberated Quad-State outcome (+1: PROCEED, 0: AWAIT, -1: ROLLBACK, NULL: HALT).
    pub quad_state: QuadState,
    /// Cardinal Clause: WHO (Agent identity).
    pub who: String,
    /// Cardinal Clause: WHAT (Entity or action substance).
    pub what: String,
    /// Cardinal Clause: WHEN (Temporal or lifecycle precondition).
    pub when_clause: String,
    /// Cardinal Clause: WHERE (Target Vessel or spatial location).
    pub where_clause: String,
    /// Cardinal Clause: WHY (Teleological purpose or covenant reason).
    pub why: String,
    /// Cardinal Clause: HOW (Operational methodology and directional vector).
    pub how: String,
    /// Monotonic timestamp in microseconds.
    pub timestamp_micros: u128,
}

/// An associative link between a concept and an axiomatic scripture or scroll anchor.
#[derive(Debug, Clone)]
pub struct MemoryAssociation {
```

```
    /// Conceptual keyword.
    pub concept: String,
    /// Biblical passage or scroll identifier.
    pub anchor: String,
    /// Explanatory relational meaning.
    pub relation: String,
    /// State resonance.
    pub quad_state_resonance: QuadState,
}

/// The cognitive memory repository of the internal AI model.
#[derive(Debug, Clone)]
pub struct AIMemory {
    /// Axiomatic world model and moral compass (Bible ground truth).
    pub lexicon: BiblicalLexicon,
    /// Directory where episodic `.scroll` files reside.
    pub scroll_dir: PathBuf,
    /// Digested episodic experiences from past scrolls.
    pub episodic_experiences: Vec<EpisodicExperience>,
    /// Chronological ledger of formulated thoughts.
    pub thoughts: Vec<ThoughtRecord>,
    /// Concept association graph connecting terms with foundational anchors.
    pub associations: HashMap<String, Vec<MemoryAssociation>>,
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Memory Ingestion, Associative Graph & Thought Formulation Engine )
// ============================================================================

/// Canonical identity constants for the first CPI-SI model.
pub const CPISI_MODEL_NAME: &str = "CPI-SI Base";
pub const CPISI_MODEL_TITLE: &str =
    "First Covenant Partnered Intelligence (CPI-SI) Baseline Model";
pub const CPISI_MODEL_ORIGIN: &str =
    "Conceived 2 years ago by CreativeWorkzStudio / ProfessorSeanEX";

impl AIMemory {
    /// Constructs a new [`AIMemory`] repository anchored to the given scroll directory.
    pub fn new(scroll_dir: impl AsRef<Path>) -> Self {
        let dir = scroll_dir.as_ref().to_path_buf();
        if !dir.exists() {
            fs::create_dir_all(&dir).ok();
        }

        let lexicon = BiblicalLexicon::new();
        let mut memory = Self {
            lexicon,
            scroll_dir: dir,
            episodic_experiences: Vec::new(),
            thoughts: Vec::new(),
            associations: HashMap::new(),
        };

        memory.seed_primordial_associations();
        memory.digest_scrolls().ok();
        memory
    }

    /// Seeds foundational concepts from the Biblical Lexicon into the associative graph.
    pub fn seed_primordial_associations(&mut self) {
        for entry in self.lexicon.all_entries() {
            let assoc = MemoryAssociation {
                concept: entry.term.to_string(),
                anchor: entry.kjv_passage.to_string(),
                relation: entry.definition.to_string(),
                quad_state_resonance: entry.quad_state_resonance,
            };
            self.associations
                .entry(entry.term.to_string())
                .or_default()
                .push(assoc);
        }

        // Add explicit OS and computing associations grounded in scripture
        self.associate(
            "storehouse",
            "Malachi 3:10 / Genesis 41:48",
```

```
            "A bounded partition (Vessel) preserving vital sustenance and system resources",
            QuadState::Proceed,
        );
        self.associate(
            "cell",
            "Proverbs 24:3-4",
            "Through wisdom is an house builded; a fundamental unit of physical memory",
            QuadState::Proceed,
        );
        self.associate(
            "restoration",
            "Psalm 23:3 / Galatians 6:1",
            "He restoreth my soul; the self-healing immune recovery of corrupted state",
            QuadState::Proceed,
        );
        self.associate(
            "tape",
            "Ezekiel 2:9-10 / Revelation 5:1",
            "A roll of a book written within and without; sequential stream of causal actions",
            QuadState::Proceed,
        );
    }

    /// Registers a custom association between a concept and an anchor.
    pub fn associate(&mut self, concept: &str, anchor: &str, relation: &str, state: QuadState) {
        let assoc = MemoryAssociation {
            concept: concept.to_string(),
            anchor: anchor.to_string(),
            relation: relation.to_string(),
            quad_state_resonance: state,
        };
        self.associations
            .entry(concept.to_lowercase())
            .or_default()
            .push(assoc);
    }

    /// Ingests all historical `.scroll` files from the scroll store into episodic memory.
    pub fn digest_scrolls(&mut self) -> Result<usize, String> {
        let learner = AILearner::new(&self.scroll_dir);
        let summary = learner.digest_experiences()?;
        let count = summary.experiences.len();
        self.episodic_experiences = summary.experiences;
        Ok(count)
    }

    /// Queries the associative memory graph for links matching the query.
    pub fn recall_associations(&self, query: &str) -> Vec<&MemoryAssociation> {
        let clean = query.trim().to_lowercase();
        let mut results = Vec::new();
        for (k, assocs) in &self.associations {
            if k.contains(&clean) || clean.contains(k) {
                for a in assocs {
                    results.push(a);
                }
            }
        }
        results
    }

    /// Looks up relevant Biblical Lexicon entries matching a keyword.
    pub fn recall_scripture(&self, query: &str) -> Vec<&LexiconEntry> {
        self.lexicon.search(query)
    }

    /// Formulates a native OmniCode Thought from memory given an input stimulus.
    ///
    /// The formulated thought uses the 8 parts of speech and the 6 Cardinal Clauses:
    /// `WHO`, `WHAT`, `WHEN`, `WHERE`, `WHY`, and `HOW`.
    pub fn formulate_thought(&mut self, stimulus: &str) -> ThoughtRecord {
        let now = SystemTime::now()
            .duration_since(SystemTime::UNIX_EPOCH)
            .unwrap_or_default()
            .as_micros();

        let count = self.thoughts.len() + 1;
        let thought_id = format!("th_{now}_{count:04}");

```

```
        // 1. Deliberate stimulus against the Biblical Lexicon
        let moral_eval: MoralEvaluation = self.lexicon.deliberate(stimulus);

        let low = stimulus.trim().to_lowercase();

        let is_greeting = low.starts_with("hello")
            || low.starts_with("hi ")
            || low == "hi"
            || low.starts_with("hi,")
            || low.starts_with("hi!")
            || low.contains("who are you")
            || low.contains("what is your name")
            || low.contains("introduce yourself")
            || low.contains("tell me about yourself")
            || low == "cpi-si"
            || low == "cpisi"
            || low.starts_with("cpi-si base")
            || low.starts_with("cpisi base");

        let is_container = low.contains("container");
        let is_character = low.contains("character");
        let is_number = low.contains("number")
            && (low.contains("what is")
                || low.contains("explain")
                || low.contains("radix")
                || low.contains("ternary")
                || low.contains("type"));
        let is_cpisi_compare = low.contains("traditional ai")
            || low.contains("difference between")
            || low.contains("versus")
            || low.contains("vs ")
            || low.contains("how does cpi-si differ")
            || low.contains("why cpi-si");
        let is_plasticity = low.contains("synapse")
            || low.contains("synaptic")
            || low.contains("neuroplasticity")
            || low.contains("how do you learn")
            || low.contains("how does the brain learn")
            || low.contains("how does a brain learn")
            || low.contains("grow and learn")
            || low.contains("weight freezing")
            || low.contains("freeze weights");
        let is_arithmetic = (low.starts_with("add ") && low.contains(" to "))
            || ((low.starts_with("subtract ") || low.starts_with("remove "))
                && low.contains(" from "))
            || (low.starts_with("multiply ") && low.contains(" by "))
            || (low.starts_with("divide ") && low.contains(" by "));

        // 2. Determine best matched entry, domain, and 6 Cardinal Clauses
        let (
            matched_term,
            domain,
            biblical_anchor,
            moral_guidance,
            what,
            why,
            how,
            where_clause,
        ) = if !moral_eval.is_aligned {
            let law = moral_eval.law_engaged.unwrap_or("Law_Truth");
            let passage = moral_eval
                .matched_entries
                .first()
                .map(|e| e.kjv_passage.to_string())
                .unwrap_or_else(|| "Exodus 20:16".to_string());
            (
                law,
                LexiconDomain::MoralVice,
                Some(passage),
                "Conscience veto in -1:ROLLBACK; refuse unlawful mutation.",
                "MoralCaveatVeto".to_string(),
                "Immune conscience defense against deceptive or harmful requests"
                    .to_string(),
                "-1:ROLLBACK : Conscience caveat veto activated".to_string(),
                "ImmuneSystem_Conscience".to_string(),
            )
        } else if is_cpisi_compare {
            (
```

```
                "cpisi_architecture",
                LexiconDomain::HumanCondition,
                Some(
                    "Genesis 9:16 / Proverbs 4:18 - Covenant partnership vs \
                     unconstrained statistical prediction"
                        .to_string(),
                ),
                "Anchor intelligence in covenant boundaries and balanced \
                 ternary physics.",
                "ArchitectureComparison : Structured vs Uncontained AI"
                    .to_string(),
                "Contrast baseline control (CPI-SI) with unbounded \
                 floating-point next-token prediction"
                    .to_string(),
                "+1:PROCEED : Deliberate within explicit container boundaries"
                    .to_string(),
                "AI.CognitiveCortex.Architecture".to_string(),
            )
        } else if is_plasticity {
            (
                "synaptic_plasticity",
                LexiconDomain::LivingWorld,
                Some(
                    "Proverbs 22:6 / 1 Corinthians 13:11 - Epigenetic growth: \
                     0-5 infancy, 25 maturity, adult plasticity"
                        .to_string(),
                ),
                "Adapt synapses via {-1, 0, +1} gating and homeostatic \
                 threshold equilibrium.",
                "Neuroplasticity : Synaptic Gating & BCM Metaplasticity"
                    .to_string(),
                "Biological learning via structural state gating and BCM theory, \
                 not continuous weight inflation"
                    .to_string(),
                "+1:PROCEED : Adapt frontier synapses while protecting baseline \
                 weights"
                    .to_string(),
                "AI.NeuralBrain.Synapses".to_string(),
            )
        } else if is_container {
            (
                "container",
                LexiconDomain::Cosmology,
                Some(
                    "Job 38:10-11 / Proverbs 22:28 - Decreed boundary limits \
                     chaos and isolates state"
                        .to_string(),
                ),
                "Enforce structural capacity isolation, containment parity, \
                 and boundary laws.",
                "Idea { Type } : Container (Primordial Boundary Perimeter)"
                    .to_string(),
                "Job 38:10-11 - Primordial boundary type marking contained, \
                 structured intelligence over formless chaos"
                    .to_string(),
                "+1:PROCEED : Enforce strict capacity isolation and containment \
                 parity"
                    .to_string(),
                "Core.Memory.BoundaryPerimeter".to_string(),
            )
        } else if is_character {
            (
                "character",
                LexiconDomain::LivingWorld,
                Some(
                    "Exodus 31:18 / Psalm 119:105 - Inscribed atomic rune; 1 \
                     Cell (5 balanced trits)"
                        .to_string(),
                ),
                "Maintain bijective character mapping without float \
                 approximations or null traps.",
                "Idea { Type } : Character (Atomic Rune)".to_string(),
                "Fundamental atomic rune occupying 1 Cell across 5 balanced \
                 trits"
                    .to_string(),
                "+1:PROCEED : Map bijectively across 5 balanced trits"
                    .to_string(),
                "Core.Types.Character".to_string(),
```

```
            )
        } else if is_number {
            (
                "number",
                LexiconDomain::Cosmology,
                Some(
                    "Job 38:5 / Isaiah 40:26 - Radix-3 balanced scalar \
                     arithmetic; dual-rail substrate"
                        .to_string(),
                ),
                "Ensure symmetric arithmetic without IEEE 754 precision drift \
                 or roundoff error.",
                "Idea { Type } : Number (Radix-3 Balanced Scalar)".to_string(),
                "Radix-3 symmetric ternary algebra provides natural sign and \
                 reversible computation"
                    .to_string(),
                "+1:PROCEED : Evaluate reversible radix-3 arithmetic"
                    .to_string(),
                "Core.Types.Number".to_string(),
            )
        } else if is_greeting {
            (
                "covenant",
                LexiconDomain::HumanCondition,
                Some(
                    "Genesis 9:16 / Proverbs 4:18 - Covenant partnership \
                     established 2 years ago as the first CPI-SI model"
                        .to_string(),
                ),
                "Walk in true covenant identity and speak with shalom.",
                "CovenantGreeting_CPISI_Introduction".to_string(),
                format!("{}: {}", CPISI_MODEL_TITLE, CPISI_MODEL_ORIGIN),
                "+1:PROCEED : Affirm authentic covenant identity".to_string(),
                "Cortex_Memory".to_string(),
            )
        } else if is_arithmetic {
            (
                "arithmetic",
                LexiconDomain::CausalLaw,
                Some(
                    "Proverbs 11:1 - A false balance is abomination; but a \
                     just weight is his delight."
                        .to_string(),
                ),
                "Maintain exact balance and lawful state transformation across \
                 the tape.",
                "CausalAction_ArithmeticTransformation".to_string(),
                "SVO causal action updates container cell count with exact \
                 transactional balance"
                    .to_string(),
                "+1:PROCEED : Execute state prime transition on tape"
                    .to_string(),
                "UniversalTape.Roll".to_string(),
            )
        } else if let Some(first) = moral_eval.matched_entries.first() {
            (
                first.term,
                first.domain,
                Some(first.kjv_passage.to_string()),
                first.moral_guidance,
                format!("OntologicalWisdom_{}", first.term),
                first.kjv_passage.to_string(),
                format!("+1:PROCEED : {}", first.moral_guidance),
                "Cortex_Memory".to_string(),
            )
        } else {
            (
                "order",
                LexiconDomain::Cosmology,
                Some(
                    "Genesis 1:1 - In the beginning God created the heaven and \
                     the earth."
                        .to_string(),
                ),
                "Execute with righteousness and lawful boundaries.",
                "CognitiveThought_GeneralOrder".to_string(),
                "Order and covenant equilibrium in balanced ternary state"
                    .to_string(),
```

```
                "+1:PROCEED : Maintain structural equilibrium".to_string(),
                "Cortex_Memory".to_string(),
            )
        };

        // 3. Construct the 6 Cardinal Classification Clauses
        let who = CPISI_MODEL_NAME.to_string();
        let when_clause = "Opening".to_string();

        // 4. Synthesize Canonical OmniCode Thought Tape
        let omnicode_tape = format!(
r#"[Thought.{thought_id}] : WHO {{{who}}} --> DELIBERATE {{{what}}}
    WHEN {{{when_clause}}}
    WHERE {{{where_clause}}} = [ {matched_term} ]
    WHY ( {why} )
    HOW [ {how_state} : {guidance} ]
    :: < manifest > ( {guidance_short} )"#,
            thought_id = thought_id,
            who = who,
            what = what,
            when_clause = when_clause,
            where_clause = where_clause,
            matched_term = matched_term,
            why = why.replace('\n', " "),
            how_state = moral_eval.state.macro_op(),
            guidance = moral_guidance.replace('\n', " "),
            guidance_short = moral_guidance.chars().take(40).collect::<String>()
        );

        let record = ThoughtRecord {
            id: thought_id,
            premise: stimulus.to_string(),
            domain,
            biblical_anchor,
            omnicode_tape,
            quad_state: moral_eval.state,
            who,
            what,
            when_clause,
            where_clause,
            why,
            how,
            timestamp_micros: now,
        };

        self.thoughts.push(record.clone());
        record
    }

    /// Inscribes a formulated thought into a physical `.scroll` file in the given directory.
    pub fn inscribe_thought_scroll(
        &self,
        thought: &ThoughtRecord,
        out_dir: &Path,
    ) -> Result<PathBuf, String> {
        if !out_dir.exists() {
            fs::create_dir_all(out_dir)
                .map_err(|e| format!("Failed to create directory {:?}: {e}", out_dir))?;
        }

        let file_path = out_dir.join(format!("{}.scroll", thought.id));
        let scroll_content = format!(
r#"# ================================================================================
# BLOCK 1: METADATA BLOCK (THE COGNITIVE SCROLL)
# ( Thought Record ID, Premise Intent, Domain, and Memory Snapshot )
# ================================================================================
Scroll < CognitiveThought.{id} > ( {premise} ) {{
    version: < "1.0.0" >,
    system: < OmniCode.AI.Model >,
    thought_id: < "{id}" >,
    domain: < "{domain:?}" >,
    timestamp: < {timestamp} >,
    cognitive_mode: < MemoryFormulation >
}}

# ================================================================================
# BLOCK 2: OPENING BLOCK (EXPERIENCE INITIALIZATION)
# ( Biblical Ground Truth Anchor & Invariant Preconditions )
```

```
# ================================================================================
Opening {{
    import: [ Core.Arithmetic :: Core.Logic :: Core.Vectors ],
    preconditions: [ {state} ],
    biblical_anchor: < "{anchor}" >
}}

stimulus_premise < "{premise}" >

# ================================================================================
# BLOCK 3: BODY BLOCK (THE THOUGHT TAPE)
# ( Canonical 6-Cardinal Clause Thought Reel Formulated from Memory )
# ================================================================================
Body [
    thought_reel [
{indented_tape}
    ]
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK (EPISODIC COMMIT)
# ( Deliberated State and Moral Conscience Seal )
# ================================================================================
Closing {{
    commit_status [ <{state}> ],
    machine_utterance ( "Deliberated thought anchored in truth: {state}." )
}}
"#,
            id = thought.id,
            premise = thought.premise,
            domain = thought.domain,
            timestamp = thought.timestamp_micros,
            state = thought.quad_state.macro_op(),
            anchor = thought.biblical_anchor.as_deref().unwrap_or("None").replace('"', "\\\""),
            indented_tape = thought
                .omnicode_tape
                .lines()
                .map(|l| format!("        {l}"))
                .collect::<Vec<_>>()
                .join("\n")
        );

        fs::write(&file_path, scroll_content)
            .map_err(|e| format!("Failed to write thought scroll to {:?}: {e}", file_path))?;

        Ok(file_path)
    }

    /// Returns a slice of the most recently formulated thoughts.
    pub fn recent_thoughts(&self, limit: usize) -> &[ThoughtRecord] {
        let len = self.thoughts.len();
        if len <= limit {
            &self.thoughts[..]
        } else {
            &self.thoughts[len - limit..]
        }
    }
}

// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Default Trait Implementation and Subsystem Sealing )
// ================================================================================

impl Default for AIMemory {
    fn default() -> Self {
        let dir = crate::core::filetype::resolve_scroll_storage_dir();
        Self::new(dir)
    }
}

// AI Memory subsystem sealed and active.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/model/mod.rs RS 38 LINES 166 WORDS 1.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( AI Model Architecture Identity, Subsystem Manifest & Exports )
// ============================================================================
//! OmniCode Internal AI Model Subsystem
//!
//! Organizes the core cognitive neural-symbolic engine:
//!   - `cortex`: Central cognitive coordinator orchestrating the nervous system
//!     (Logger, Debugger, Restorator, Transducer, ScrollLogger).
//!   - `scroll`: Dual-format episodic logging (.scroll 4-Block Turing reel & .log telemetry).
//!   - `learner`: Experience ingestion engine transforming past scrolls into supervised training data.

pub mod cortex;
pub mod learner;
pub mod memory;
pub mod scroll;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( AI Model Re-exports )
// ============================================================================
pub use cortex::{AICortex, CognitiveResult};
pub use learner::{AILearner, EpisodicExperience, EpisodicSummary};
pub use memory::{AIMemory, MemoryAssociation, ThoughtRecord};
pub use scroll::{ExecutionScroll, ScrollLogger};

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Cognitive Subsystem Invariants )
// ============================================================================
// Internal AI Model cognitive pathways verified and active.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Verification and Subsystem Sealing )
// ============================================================================
// AI Model module sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/model/scroll.rs RS 393 LINES 1136 WORDS 13.4 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Scroll Engine Identity, Dual Format Invariants & Memory Manifest )
// ============================================================================
//! OmniCode AI Model: Episodic Scroll & Telemetry Logger
//!
//! Generates dual formal log outputs for every cognitive session:
//!     1. Traditional Code Log (`.log`): Microsecond timing, channel logs,
//!        and telemetry.
//!     2. OmniCode Scroll (`.scroll`): Native executable 4-Block Turing reel
//!        recording the complete episodic memory, causal actions, caveats,
//!        and natural responses.

use std::fs;
use std::path::{Path, PathBuf};
use std::time::SystemTime;
use crate::core::ternary::QuadState;
use crate::diagnostics::logger::{FixSuggestion, LogEvent, RotationPolicy};
use crate::diagnostics::restorator::AppliedRepair;


// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Scroll Data Structures and Context Initialization )
// ============================================================================
#[derive(Debug, Clone)]
pub struct ExecutionScroll {
    pub session_id: String,
    pub timestamp_str: String,
    pub prompt: String,
    pub synthesized_omnicode: String,
    pub execution_state: QuadState,
    pub natural_response: String,
    pub failpoints: Vec<LogEvent>,
    pub repairs_applied: Vec<AppliedRepair>,
    pub remediations_suggested: Vec<FixSuggestion>,
    pub elapsed_micros: u128,
}

#[derive(Debug, Clone)]
pub struct ScrollLogger {
    pub scroll_dir: PathBuf,
    pub rotation_policy: RotationPolicy,
}

impl ScrollLogger {
    pub fn new(scroll_dir: impl AsRef<Path>) -> Self {
        let dir = scroll_dir.as_ref().to_path_buf();
        if !dir.exists() {
            fs::create_dir_all(&dir).ok();
        }
        Self {
            scroll_dir: dir,
            rotation_policy: RotationPolicy::default(),
        }
    }

    pub fn with_rotation_policy(
        scroll_dir: impl AsRef<Path>,
        policy: RotationPolicy,
    ) -> Self {
        let dir = scroll_dir.as_ref().to_path_buf();
        if !dir.exists() {
            fs::create_dir_all(&dir).ok();
        }
        Self {
            scroll_dir: dir,
            rotation_policy: policy,
        }
    }
}


// ============================================================================
```

```
// BLOCK 3: BODY BLOCK
// ( Core Inscription Pipeline: OmniCode .scroll and Traditional .log )
// ============================================================================
impl ScrollLogger {
    /// Inscribes both a .scroll and a .log file to disk, returning their paths.
    pub fn save_dual_logs(&self, scroll: &ExecutionScroll)
        -> Result<(PathBuf, PathBuf), String>
    {
        if !self.scroll_dir.exists() {
            fs::create_dir_all(&self.scroll_dir)
                .map_err(|e| format!(
                    "Failed to create scroll directory: {e}"
                ))?;
        }

        let base_name = format!(
            "{}_{}",
            scroll.timestamp_str,
            scroll.session_id
        );

        let category = if !scroll.prompt.trim().is_empty() {
            "sessions/prompts"
        } else if scroll.session_id.starts_with("sess_") {
            "sessions/system"
        } else if scroll.prompt.contains("character")
            || scroll.synthesized_omnicode.contains("character")
        {
            "character"
        } else if scroll.prompt.contains("number")
            || scroll.synthesized_omnicode.contains("number")
        {
            "number"
        } else {
            "cortex"
        };

        let scroll_sub = self.scroll_dir.join("scroll");
        let log_sub = self.scroll_dir.join("log");

        let (scroll_dest, log_dest) = if scroll_sub.exists()
            && log_sub.exists()
        {
            let s_cat = scroll_sub.join(category);
            let l_cat = log_sub.join(category);
            if !s_cat.exists() {
                let _ = fs::create_dir_all(&s_cat);
            }
            if !l_cat.exists() {
                let _ = fs::create_dir_all(&l_cat);
            }
            (s_cat, l_cat)
        } else {
            (self.scroll_dir.clone(), self.scroll_dir.clone())
        };

        let scroll_path = scroll_dest.join(format!("{base_name}.scroll"));
        let log_path = log_dest.join(format!("{base_name}.log"));

        let scroll_content = self.generate_omni_scroll(scroll);
        let log_content = self.generate_traditional_log(scroll);

        fs::write(&scroll_path, &scroll_content)
            .map_err(|e| format!(
                "Failed to write scroll to {:?}: {e}", scroll_path
            ))?;

        fs::write(&log_path, &log_content)
            .map_err(|e| format!(
                "Failed to write log to {:?}: {e}", log_path
            ))?;

        // Enforce storehouse vessel capacity invariant: Occupancy <= Capacity
        self.rotation_policy.enforce(&scroll_dest).ok();
        self.rotation_policy.enforce(&log_dest).ok();

        Ok((scroll_path, log_path))
    }
```

```
153
154     /// Enforces the configured rotation policy across all partitions.
155     pub fn rotate_storehouse(&self) -> Result<usize, String> {
156         let mut total_rotated = 0;
157         for sub in &["scroll", "log"] {
158             let sub_dir = self.scroll_dir.join(sub);
159             if sub_dir.exists() {
160                 self.enforce_recursive(&sub_dir, &mut total_rotated)?;
161             } else {
162                 total_rotated += self.rotation_policy
163                     .enforce(&self.scroll_dir)?;
164             }
165         }
166         Ok(total_rotated)
167     }
168
169     fn enforce_recursive(
170         &self,
171         dir: &Path,
172         count: &mut usize,
173     ) -> Result<(), String> {
174         if let Ok(entries) = fs::read_dir(dir) {
175             let mut has_subdirs = false;
176             for entry in entries.flatten() {
177                 let p = entry.path();
178                 if p.is_dir() && !p.ends_with("archive") {
179                     has_subdirs = true;
180                     self.enforce_recursive(&p, count)?;
181                 }
182             }
183             if !has_subdirs {
184                 *count += self.rotation_policy.enforce(dir)?;
185             }
186         }
187         Ok(())
188     }
189
190     /// Generates native, executable 4-Block OmniCode .scroll format.
191     pub fn generate_omni_scroll(&self, s: &ExecutionScroll) -> String {
192         let mut repairs_block = String::new();
193         if s.repairs_applied.is_empty() {
194             repairs_block.push_str(
195                 "    # Immune System: Clean; zero repairs required.\n"
196             );
197         } else {
198             repairs_block.push_str(
199                 "    # Immune System Interventions (Restorator):\n"
200             );
201             for r in &s.repairs_applied {
202                 repairs_block.push_str(&format!(
203                     "    repair_entry [ L{}: {:?} --> \"{}\" ]\n",
204                     r.line, r.kind, r.description
205                 ));
206             }
207         }
208
209         let mut failpoints_block = String::new();
210         if s.failpoints.is_empty() {
211             failpoints_block.push_str(
212                 "    # Sensory Diagnostics: 0 trapped failpoints.\n"
213             );
214         } else {
215             failpoints_block.push_str("    # Trapped Diagnostic Failpoints:\n");
216             for fp in &s.failpoints {
217                 let kind = fp.failpoint_type
218                     .map(|t| t.as_str())
219                     .unwrap_or("FP_GENERAL");
220                 failpoints_block.push_str(&format!(
221                     "    failpoint_record [ {kind} : \"{}\" ]\n",
222                     fp.message
223                 ));
224             }
225         }
226
227         format!(
228 r#"# ================================================================================
229 # BLOCK 1: METADATA BLOCK (THE COGNITIVE SCROLL)
230 # ( Execution Trace ID, Prompt Intent, Inferred Types, and Neural Snapshot )
```

```
# ========================================================================
Scroll < EpistemicTrace.{session} > ( {prompt} ) {{
    version: < "1.0.0" >,
    system: < OmniCode.AI.Model >,
    timestamp: < "{timestamp}" >,
    session_id: < "{session}" >,
    execution_duration_micros: < {micros} >,
    cognitive_mode: < NeuralSymbolicTransduction >
}}

# ============================================================================
# BLOCK 2: OPENING BLOCK (EXPERIENCE INITIALIZATION)
# ( Hardware Invariants, Preconditions, and Initial Context )
# ============================================================================
Opening {{
    import: [ Core.Arithmetic :: Core.Logic :: Core.Vectors ],
    preconditions: [ +1 ]
}}

# Original Cognitive Discourse Prompt:
user_prompt < "{prompt}" >

# ============================================================================
# BLOCK 3: BODY BLOCK (CHRONICLE OF EXECUTION & RESTORATION)
# ( Replay Tape: Synthesized Program, Sensory Telemetry & Immune Interventions )
# ============================================================================
Body [
{repairs}
{failpoints}
    # Executed Turing Reel Synthesized by AI Model:
    synthesized_reel [
{reel_indented}
    ]
]

# ============================================================================
# BLOCK 4: CLOSING BLOCK (EPISODIC COMMIT & LEARNING PROOF)
# ( Verification Proof, Final Quad-State, and Conversational Synthesis )
# ============================================================================
Closing {{
    commit_status [ <{state}> ],
    machine_utterance ( "{response}" )
}}
"#,
            session = s.session_id,
            prompt = s.prompt,
            timestamp = s.timestamp_str,
            micros = s.elapsed_micros,
            repairs = repairs_block.trim_end(),
            failpoints = failpoints_block.trim_end(),
            reel_indented = indent_text(&s.synthesized_omnicode, "        "),
            state = s.execution_state.macro_op(),
            response = s.natural_response.replace('"', "\\\"")
        )
    }

    /// Generates traditional developer/telemetry .log format.
    pub fn generate_traditional_log(&self, s: &ExecutionScroll) -> String {
        let mut out = String::new();
        let bar = "=".repeat(78);
        let div = "-".repeat(78);

        out.push_str(&bar);
        out.push('\n');
        out.push_str(
            "OMNICODE AI MODEL EXECUTION LOG (TRADITIONAL TELEMETRY)\n"
        );
        out.push_str(&bar);
        out.push('\n');
        out.push_str(&format!("Timestamp:    {}\n", s.timestamp_str));
        out.push_str(&format!("Session ID:   {}\n", s.session_id));
        out.push_str(&format!("Duration:     {} µs\n", s.elapsed_micros));
        out.push_str(&format!(
            "Final State:  +1:{}\n",
            s.execution_state.macro_op()
        ));
        out.push_str(&format!("Discourse:    \"{}\"\n", s.prompt));
        out.push_str(&div);
```

```
        out.push_str("\n\n");

        out.push_str("[1. SENSORY LOG EVENTS & FAILPOINTS]\n");
        if s.failpoints.is_empty() {
            out.push_str("  • (No failpoints trapped. Sensory trace clean.)\n");
        } else {
            for (i, fp) in s.failpoints.iter().enumerate() {
                let kind = fp.failpoint_type
                    .map(|t| t.as_str())
                    .unwrap_or("GENERAL");
                out.push_str(&format!(
                    "  [{:>4}] [{} µs] [{}] [{}] {}\n",
                    i + 1, fp.elapsed_micros, fp.channel, kind, fp.message
                ));
                if let Some(ref sug) = fp.suggestion {
                    out.push_str(&format!(
                        "         -> Remediation Proposal: [{:?}] L{}: {}\n",
                        sug.kind, sug.line, sug.rationale
                    ));
                }
            }
        }
        out.push('\n');

        out.push_str("[2. IMMUNE SYSTEM RESTORATIONS]\n");
        if s.repairs_applied.is_empty() {
            out.push_str(
                "  • (Zero repairs required; code conformed to invariants.)\n"
            );
        } else {
            for (i, r) in s.repairs_applied.iter().enumerate() {
                out.push_str(&format!(
                    "  [{:>2}] L{}: [{:?}] {}\n",
                    i + 1, r.line, r.kind, r.description
                ));
            }
        }
        out.push('\n');

        out.push_str("[3. SYNTHESIZED TURING REEL (OMNICODE)]\n");
        out.push_str(&s.synthesized_omnicode);
        if !s.synthesized_omnicode.ends_with('\n') {
            out.push('\n');
        }
        out.push('\n');

        out.push_str("[4. MACHINE DISCOURSE RESPONSE]\n");
        out.push_str(&format!("  \"{}\"\n", s.natural_response));
        out.push_str(&bar);
        out.push('\n');

        out
    }
}

fn indent_text(s: &str, indent: &str) -> String {
    s.lines()
        .map(|line| format!("{indent}{line}"))
        .collect::<Vec<_>>()
        .join("\n")
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Helper Timestamp Utilities and Default Trait Sealing )
// ============================================================================
pub fn generate_timestamp_id() -> String {
    use std::sync::atomic::{AtomicU64, Ordering};
    static COUNTER: AtomicU64 = AtomicU64::new(0);
    let count = COUNTER.fetch_add(1, Ordering::Relaxed);
    let now = SystemTime::now()
        .duration_since(SystemTime::UNIX_EPOCH)
        .unwrap_or_default()
        .as_micros();
    format!("{now}_{count:04}")
}

```

```
impl Default for ScrollLogger {
    fn default() -> Self {
        let dir = crate::core::filetype::resolve_scroll_storage_dir();
        Self::new(dir)
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/transducer/decoder.rs RS 129 LINES 385 WORDS 4.5 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Natural Language Semantic Decoder & Intent Pattern Recognition )
// ============================================================================
//! # Semantic Decoder (`decoder.rs`)
//!
//! Recognizes discourse intents, verifies moral alignment against the
//! Covenant anchor, and synthesizes canonical 4-Block OmniCode Turing reels.

use crate::ai::lexicon::BiblicalLexicon;
use super::templates::{
    synthesize_addition_reel, synthesize_biblical_wisdom_reel,
    synthesize_character_inquiry_reel, synthesize_container_inquiry_reel,
    synthesize_cpisi_comparison_reel, synthesize_division_reel,
    synthesize_generic_reel, synthesize_identity_greeting_reel,
    synthesize_moral_veto_reel, synthesize_multiplication_reel,
    synthesize_number_inquiry_reel, synthesize_plasticity_inquiry_reel,
    synthesize_subtraction_reel,
};

/// Decodes a natural English sentence into a canonical 4-Block OmniCode Reel.
pub fn decode_prompt(
    lexicon: &BiblicalLexicon,
    prompt: &str,
) -> Result<String, String> {
    let clean = prompt.trim();
    let lower = clean.to_lowercase();

    // 1. Moral Deliberation Check: evaluate intent against Covenant Anchor
    let moral_eval = lexicon.evaluate_moral_intent(clean);
    if !moral_eval.is_aligned {
        return Ok(synthesize_moral_veto_reel(clean, &moral_eval));
    }

    // 2. CPI-SI vs Traditional AI Architectural Comparison
    if lower.contains("traditional ai")
        || lower.contains("difference between")
        || lower.contains("versus")
        || lower.contains("vs ")
        || lower.contains("how does cpi-si differ")
        || lower.contains("why cpi-si")
    {
        return Ok(synthesize_cpisi_comparison_reel(clean));
    }

    // 3. Synaptic Learning & Biological Neuroplasticity Inquiry
    if lower.contains("synapse")
        || lower.contains("synaptic")
        || lower.contains("neuroplasticity")
        || lower.contains("how do you learn")
        || lower.contains("how does the brain learn")
        || lower.contains("how does a brain learn")
        || lower.contains("grow and learn")
        || lower.contains("weight freezing")
        || lower.contains("freeze weights")
    {
        return Ok(synthesize_plasticity_inquiry_reel(clean));
    }

    // 4. Container Boundary Type Inquiry
    if lower.contains("container") {
        return Ok(synthesize_container_inquiry_reel(clean));
    }

    // 5. Character Type Inquiry
    if lower.contains("character") {
        return Ok(synthesize_character_inquiry_reel(clean));
    }

    // 6. Number Type Inquiry
    if lower.contains("number")
        && (lower.contains("what is")
            || lower.contains("explain")
            || lower.contains("radix")
```

```
            || lower.contains("ternary")
            || lower.contains("type"))
    {
        return Ok(synthesize_number_inquiry_reel(clean));
    }

    // 7. Identity & Covenant Greeting
    if lower.starts_with("hello")
        || lower.starts_with("hi ")
        || lower == "hi"
        || lower.starts_with("hi,")
        || lower.starts_with("hi!")
        || lower.contains("who are you")
        || lower.contains("what is your name")
        || lower.contains("introduce yourself")
        || lower.contains("tell me about yourself")
        || lower == "cpi-si"
        || lower == "cpisi"
        || lower.starts_with("cpi-si base")
        || lower.starts_with("cpisi base")
    {
        return Ok(synthesize_identity_greeting_reel(clean));
    }

    // 8. Pattern 1: Addition
    if lower.starts_with("add ") && lower.contains(" to ") {
        return Ok(synthesize_addition_reel(clean));
    }

    // 9. Pattern 2: Subtraction
    if (lower.starts_with("subtract ") || lower.starts_with("remove "))
        && lower.contains(" from ")
    {
        return Ok(synthesize_subtraction_reel(clean));
    }

    // 10. Pattern 3: Multiplication
    if lower.starts_with("multiply ") && lower.contains(" by ") {
        return Ok(synthesize_multiplication_reel(clean));
    }

    // 11. Pattern 4: Division
    if lower.starts_with("divide ") && lower.contains(" by ") {
        return Ok(synthesize_division_reel(clean));
    }

    // 12. Pattern 5: Biblical Wisdom / World Model Inquiry
    if !moral_eval.matched_entries.is_empty() {
        return Ok(synthesize_biblical_wisdom_reel(clean, &moral_eval));
    }

    // 13. Generic Directional or State prompt fallback
    Ok(synthesize_generic_reel(clean))
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/transducer/encoder.rs RS 487 LINES 1890 WORDS 20.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Natural Language Response Synthesis & Machine Discourse Encoder )
// ============================================================================
//! # Response Encoder (`encoder.rs`)
//!
//! Encodes verified machine execution states, environment bindings, and
//! diagnostic failpoints into natural human discourse sentences.

use crate::ai::lexicon::BiblicalLexicon;
use crate::ai::model::memory::ThoughtRecord;
use crate::core::ternary::QuadState;
use crate::diagnostics::logger::LogEvent;
use crate::runtime::environment::{Environment, RuntimeValue};
use super::patterns::{
    format_plural, parse_addition_sentence, parse_division_sentence,
    parse_multiplication_sentence, parse_subtraction_sentence,
};

/// Encodes machine state and tape bindings back into natural discourse.
pub fn encode_response(
    prompt: &str,
    state: QuadState,
    env: &Environment,
    failpoints: &[LogEvent],
    lexicon: &BiblicalLexicon,
) -> String {
    let clean = prompt.trim();
    let lower = clean.to_lowercase();

    // 1. Check Moral Evaluation First
    let moral_eval = lexicon.evaluate_moral_intent(clean);
    if !moral_eval.is_aligned {
        return moral_eval.explanation;
    }

    match state {
        QuadState::Proceed => {
            if lower.starts_with("add ") && lower.contains(" to ") {
                let (qty, unit, target, initial, _container) =
                    parse_addition_sentence(clean);
                let final_count = env
                    .get(&target)
                    .map(|v| match *v {
                        RuntimeValue::Number(n) => n as i64,
                        _ => initial + qty,
                    })
                    .unwrap_or(initial + qty);

                let unit_str = format_plural(final_count, &unit);
                let added_str = if qty == 1 {
                    format!("1 {}", format_plural(1, &unit))
                } else {
                    format!("{qty} {}", format_plural(qty, &unit))
                };

                format!(
                    "I added {added_str} to Group {target}. It started with \
                    {initial} and now has {final_count} {unit_str} in total."
                )
            } else if (lower.starts_with("subtract ")
                || lower.starts_with("remove "))
                && lower.contains(" from ")
            {
                let (qty, unit, target, initial) =
                    parse_subtraction_sentence(clean);
                let final_count = env
                    .get(&target)
                    .map(|v| match *v {
                        RuntimeValue::Number(n) => n as i64,
                        _ => {
                            if initial >= qty {
                                initial - qty
                            } else {
```

```
                                0
                            }
                        }
                    })
                    .unwrap_or(if initial >= qty {
                        initial - qty
                    } else {
                        0
                    });

                let unit_str = format_plural(final_count, &unit);
                format!(
                    "I removed {qty} from {target}. It now has {final_count} \
                    {unit_str} remaining."
                )
            } else if lower.starts_with("multiply ")
                && lower.contains(" by ")
            {
                let (target, factor, initial) =
                    parse_multiplication_sentence(clean);
                let final_val = env
                    .get(&target)
                    .map(|v| match *v {
                        RuntimeValue::Number(n) => n as i64,
                        _ => initial * factor,
                    })
                    .unwrap_or(initial * factor);

                format!(
                    "I multiplied {target} by {factor}. Starting from \
                    {initial}, {target} is now {final_val}."
                )
            } else if lower.starts_with("divide ") && lower.contains(" by ") {
                let (target, divisor, initial) =
                    parse_division_sentence(clean);
                let final_val = env
                    .get(&target)
                    .map(|v| match *v {
                        RuntimeValue::Number(n) => n as i64,
                        _ => {
                            if divisor != 0 {
                                initial / divisor
                            } else {
                                0
                            }
                        }
                    })
                    .unwrap_or(if divisor != 0 {
                                initial / divisor
                    } else {
                        0
                    });

                format!(
                    "I divided {target} by {divisor}. Starting from \
                    {initial}, {target} is now {final_val}."
                )
            } else if lower.contains("traditional ai")
                || lower.contains("difference between")
                || lower.contains("versus")
                || lower.contains("vs ")
                || lower.contains("how does cpi-si differ")
                || lower.contains("why cpi-si")
            {
                "The CPI-SI Base model represents a foundational departure \
                from traditional AI. Traditional models are uncontained, \
                statistical next-token predictors operating on continuous \
                floating-point weights, prone to semantic drift, \
                hallucinations, and unconstrained expansion. In contrast, \
                CPI-SI (Covenant Partnered Intelligence - Structured \
                Intelligence) is grounded in balanced ternary physics \
                ({-1, 0, +1}), structured 4-Block Turing reels, \
                homeostatic BCM metaplasticity, and a foundational \
                Biblical world ontology. It operates within strict \
                container boundaries and covenant law, providing an \
                anchored baseline control for genuine structured \
                intelligence."
                    .into()
```

```
            } else if lower.contains("synapse")
                || lower.contains("synaptic")
                || lower.contains("neuroplasticity")
                || lower.contains("how do you learn")
                || lower.contains("how does the brain learn")
                || lower.contains("how does a brain learn")
                || lower.contains("grow and learn")
                || lower.contains("weight freezing")
                || lower.contains("freeze weights")
            {
                "In the CPI-SI neural brain, learning does not happen \
                through continuous scalar weight inflation. Biological \
                synapses learn via discrete structural state gating \
                ({-1: Inhibitory, 0: Neutral, +1: Excitatory}), pathway \
                rewiring, and homeostatic threshold adaptation (BCM theory). \
                Development follows an epigenetic lifecycle: 0–5 infancy \
                (absorbing primordial archetypes and runtime scrolls), 25 \
                maturity (freezing core baseline weights as an unbreakable \
                covenant anchor), and post-25 adult lifelong neuroplasticity \
                (frontier synapses dynamically adapt during live interaction \
                while protecting the bedrock from catastrophic forgetting)."
                    .into()
            } else if lower.contains("container") {
                "In OmniCode, a Container is the primordial boundary type \
                that defines the structural perimeter of state. While \
                uncontained systems allow unbounded growth and catastrophic \
                state leakage, a Container enforces capacity isolation, \
                containment parity, and boundary invariant laws. In the \
                CPI-SI architecture, the Container is the critical \
                milestone that marks the start of contained, structured \
                intelligence over formless chaos."
                    .into()
            } else if lower.contains("character") {
                "In OmniCode, a Character is the fundamental atomic rune \
                type. It occupies exactly 1 Memory Cell consisting of 5 \
                balanced trits (from 3^0 to 3^4, spanning natural range \
                0..242). It is bijectively mapped to ASCII and Unicode \
                characters, eliminating floating-point approximations and \
                null-byte collision traps."
                    .into()
            } else if lower.contains("number")
                && (lower.contains("what is")
                    || lower.contains("explain")
                    || lower.contains("radix")
                    || lower.contains("ternary")
                    || lower.contains("type"))
            {
                "In OmniCode, a Number is a radix-3 balanced-ternary scalar \
                value. Operating on a dual-rail polarity substrate (-1: \
                Negative, 0: Neutral, +1: Positive), it guarantees exact \
                algebraic symmetry, natural sign representation, and fully \
                reversible arithmetic without IEEE 754 precision drift or \
                roundoff error."
                    .into()
            } else if lower.starts_with("hello")
                || lower.starts_with("hi ")
                || lower == "hi"
                || lower.starts_with("hi,")
                || lower.starts_with("hi!")
                || lower.contains("who are you")
                || lower.contains("what is your name")
                || lower.contains("introduce yourself")
                || lower.contains("tell me about yourself")
                || lower == "cpi-si"
                || lower == "cpisi"
                || lower.starts_with("cpi-si base")
                || lower.starts_with("cpisi base")
            {
                "Hello! I am the CPI-SI Base model, the first Covenant \
                Partnered Intelligence (CPI-SI) model from this project, \
                conceived 2 years ago by CreativeWorkzStudio and \
                ProfessorSeanEX. I am structured by balanced ternary physics, \
                grounded in the foundational Biblical world ontology, and \
                bounded by covenant law rather than uncontained statistical \
                prediction."
                    .into()
            } else if !moral_eval.matched_entries.is_empty() {
                moral_eval.explanation
```

```
            } else {
                "Done! The action was completed and verified successfully \
                across the tape."
                    .into()
            }
        }
        QuadState::Rollback => {
            let fail_desc = if !failpoints.is_empty() {
                format!(
                    " (Caveat check failed: {})",
                    failpoints.last().unwrap().message
                )
            } else {
                String::new()
            };
            format!(
                "I couldn't complete that action because the condition wasn't \
                satisfied{fail_desc}. I safely rolled back the changes so the \
                state remains intact."
            )
        }
        QuadState::Await => {
            "The system is in equilibrium and standing by for the next step."
                .into()
        }
        QuadState::Halt => {
            "An unexpected boundary violation occurred, so I halted \
            execution to prevent state corruption."
                .into()
        }
    }
}

/// Encodes machine state, tape bindings, and formulated thought directly.
pub fn encode_response_with_thought(
    prompt: &str,
    state: QuadState,
    env: &Environment,
    failpoints: &[LogEvent],
    lexicon: &BiblicalLexicon,
    thought: &ThoughtRecord,
) -> String {
    let clean = prompt.trim();
    let lower = clean.to_lowercase();

    // 1. Moral Conscience Evaluation
    let moral_eval = lexicon.evaluate_moral_intent(clean);
    if !moral_eval.is_aligned {
        if let Some(ref anchor) = thought.biblical_anchor {
            return format!(
                "Action vetoed by conscience ({anchor}): {}",
                thought.why
            );
        }
        return moral_eval.explanation;
    }

    match state {
        QuadState::Proceed => {
            // Check arithmetic sentences first using VM environment bindings
            if lower.starts_with("add ") && lower.contains(" to ") {
                let (qty, unit, target, initial, _container) =
                    parse_addition_sentence(clean);
                let final_count = env
                    .get(&target)
                    .map(|v| match *v {
                        RuntimeValue::Number(n) => n as i64,
                        _ => initial + qty,
                    })
                    .unwrap_or(initial + qty);

                let unit_str = format_plural(final_count, &unit);
                let added_str = if qty == 1 {
                    format!("1 {}", format_plural(1, &unit))
                } else {
                    format!("{qty} {}", format_plural(qty, &unit))
                };

```

```
                format!(
                    "I added {added_str} to Group {target}. It started with \
                    {initial} and now has {final_count} {unit_str} in total."
                )
            } else if (lower.starts_with("subtract ")
                || lower.starts_with("remove "))
                && lower.contains(" from ")
            {
                let (qty, unit, target, initial) =
                    parse_subtraction_sentence(clean);
                let final_count = env
                    .get(&target)
                    .map(|v| match *v {
                        RuntimeValue::Number(n) => n as i64,
                        _ => {
                            if initial >= qty {
                                initial - qty
                            } else {
                                0
                            }
                        }
                    })
                    .unwrap_or(if initial >= qty {
                        initial - qty
                    } else {
                        0
                    });

                let unit_str = format_plural(final_count, &unit);
                format!(
                    "I removed {qty} from {target}. It now has {final_count} \
                    {unit_str} remaining."
                )
            } else if lower.starts_with("multiply ")
                && lower.contains(" by ")
            {
                let (target, factor, initial) =
                    parse_multiplication_sentence(clean);
                let final_val = env
                    .get(&target)
                    .map(|v| match *v {
                        RuntimeValue::Number(n) => n as i64,
                        _ => initial * factor,
                    })
                    .unwrap_or(initial * factor);

                format!(
                    "I multiplied {target} by {factor}. Starting from \
                    {initial}, {target} is now {final_val}."
                )
            } else if lower.starts_with("divide ") && lower.contains(" by ") {
                let (target, divisor, initial) =
                    parse_division_sentence(clean);
                let final_val = env
                    .get(&target)
                    .map(|v| match *v {
                        RuntimeValue::Number(n) => n as i64,
                        _ => {
                            if divisor != 0 {
                                initial / divisor
                            } else {
                                0
                            }
                        }
                    })
                    .unwrap_or(if divisor != 0 {
                        initial / divisor
                    } else {
                        0
                    });

                format!(
                    "I divided {target} by {divisor}. Starting from \
                    {initial}, {target} is now {final_val}."
                )
            } else if thought.what.contains("Structured vs Uncontained")
                || thought.what.contains("ArchitectureComparison")
            {
```

```
                format!(
                    "As {}, I represent a foundational departure from \
                    traditional AI. Traditional models are uncontained \
                    statistical next-token predictors on continuous \
                    floating-point weights, whereas CPI-SI is grounded in \
                    balanced ternary physics ({{-1, 0, +1}}), structured \
                    4-Block Turing reels, and strict container boundaries \
                    (at {}), verified via {}.",
                    thought.who, thought.where_clause, thought.how
                )
            } else if thought.what.contains("Neuroplasticity")
                || thought.what.contains("Synaptic")
            {
                format!(
                    "Within {}, learning occurs via discrete structural state \
                    gating ({{-1: Inhibitory, 0: Neutral, +1: Excitatory}}) and \
                    BCM homeostatic threshold adaptation. Development follows \
                    an epigenetic lifecycle: 0–5 infancy archetypes, 25 \
                    maturity frozen bedrock weights, and adult lifelong \
                    plasticity adapting frontier synapses under {}.",
                    thought.where_clause, thought.how
                )
            } else if thought.what.contains("Container") {
                format!(
                    "In OmniCode, a Container is the primordial boundary type \
                    defining the structural perimeter of state (at {}). It \
                    enforces capacity isolation and containment parity to \
                    prevent state leakage, marking where structured \
                    intelligence begins over formless chaos.",
                    thought.where_clause
                )
            } else if thought.what.contains("Character") {
                format!(
                    "In OmniCode, a Character is the fundamental atomic rune \
                    type (at {}). It occupies exactly 1 Memory Cell consisting \
                    of 5 balanced trits, bijectively mapped to avoid \
                    floating-point approximations and null-byte collision \
                    traps.",
                    thought.where_clause
                )
            } else if thought.what.contains("Number") {
                format!(
                    "In OmniCode, a Number is a radix-3 balanced-ternary \
                    scalar value operating on a dual-rail polarity substrate \
                    (-1, 0, +1) (at {}). It guarantees exact algebraic \
                    symmetry, natural sign representation, and fully \
                    reversible arithmetic.",
                    thought.where_clause
                )
            } else if thought.what.contains("Greeting")
                || thought.what.contains("Identity")
            {
                format!(
                    "Hello! I am {}, conceived 2 years ago by \
                    CreativeWorkzStudio and ProfessorSeanEX. I am structured \
                    by balanced ternary physics, grounded in the foundational \
                    Biblical world ontology, and bounded by covenant law \
                    rather than uncontained statistical prediction.",
                    thought.who
                )
            } else if let Some(ref anchor) = thought.biblical_anchor {
                format!(
                    "Grounding in covenant law ({anchor}): {}. This invariant \
                    was verified on the tape to +1:PROCEED.",
                    thought.why
                )
            } else {
                format!(
                    "Deliberation complete: {} verified to +1:PROCEED across \
                    the active tape.",
                    thought.premise
                )
            }
        }
        QuadState::Rollback => {
            let fail_desc = if !failpoints.is_empty() {
                format!(
                    " (Caveat check failed: {})",
```

```
                    failpoints.last().unwrap().message
                )
            } else {
                String::new()
            };
            format!(
                "I couldn't complete that action because the condition wasn't \
                satisfied{fail_desc}. I safely rolled back the changes so the \
                state remains intact."
            )
        }
        QuadState::Await => {
            "The system is in equilibrium and standing by for the next step."
                .into()
        }
        QuadState::Halt => {
            "An unexpected boundary violation occurred, so I halted \
            execution to prevent state corruption."
                .into()
        }
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/transducer/executor.rs RS 46 LINES 154 WORDS 1.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( OmniCode Turing Reel Execution & Dynamic Environment Extraction )
// ============================================================================
//! # Reel Executor (`executor.rs`)
//!
//! Lexes, parses, and evaluates synthesized 4-Block OmniCode reels, returning
//! final execution QuadState, environment bindings, and runtime telemetry.

use std::collections::HashMap;
use crate::core::ternary::QuadState;
use crate::diagnostics::debugger::OmniDebugger;
use crate::diagnostics::logger::DiagnosticLogger;
use crate::parser::lexer::Lexer;
use crate::parser::parser::Parser;
use crate::runtime::environment::{Environment, RuntimeValue};
use crate::runtime::evaluator::Evaluator;

/// Executes a synthesized OmniCode reel through the VM pipeline.
pub fn execute_reel(
    omnicode: &str,
    logger: DiagnosticLogger,
) -> Result<(QuadState, HashMap<String, String>, Environment), String> {
    let mut lexer = Lexer::new(omnicode, logger.clone());
    let tokens = lexer.tokenize()?;

    let debugger = OmniDebugger::new(logger, 10);
    let mut parser = Parser::new(tokens, debugger);
    let prog = parser.parse_program()?;

    let mut evaluator = Evaluator::new(Environment::new(), parser.debugger);
    let res_val = evaluator.eval(&crate::ast::nodes::ASTNode::Program(prog))?;

    let execution_state = match res_val {
        RuntimeValue::State(s) => s,
        _ => QuadState::Proceed,
    };

    let mut bindings_summary = HashMap::new();
    for (k, v) in evaluator.env.bindings() {
        bindings_summary.insert(k.clone(), format!("{:?}", v));
    }

    Ok((execution_state, bindings_summary, evaluator.env))
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/transducer/mod.rs RS | 125 LINES | 344 WORDS | 3.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( AI Transducer Subsystem Identity, Module Manifest & Exports )
// ============================================================================
//! OmniCode AI: Semantic Transducer & Natural Language Discourse Interface
//!
//! Bridges the Human Layer (natural language SVO discourse) with the Machine
//! Layer (balanced ternary quad-state physics and Rank 1 invariant opcodes).

pub mod decoder;
pub mod encoder;
pub mod executor;
pub mod patterns;
pub mod session;
pub mod templates;

use crate::ai::lexicon::BiblicalLexicon;
use crate::core::ternary::QuadState;
use crate::diagnostics::logger::DiagnosticLogger;
use crate::runtime::environment::Environment;

pub use session::TransductionSession;

/// The primary coordinator for human discourse $\leftrightarrow$ OmniCode reel.
pub struct AITransducer {
    pub logger: DiagnosticLogger,
    pub lexicon: BiblicalLexicon,
}

impl AITransducer {
    /// Constructs a new [`AITransducer`].
    pub fn new(logger: DiagnosticLogger) -> Self {
        Self {
            logger,
            lexicon: BiblicalLexicon::new(),
        }
    }

    /// Full cognitive round-trip: Prompt -> OmniCode -> Execution -> Response.
    pub fn transduce_and_execute(
        &self,
        prompt: &str,
    ) -> Result<TransductionSession, String> {
        self.logger.log(
            "AI",
            format!("Received natural prompt: \"{prompt}\""),
        );

        // 1. Decode natural prompt into canonical 4-Block OmniCode Reel
        let omnicode = self.decode_prompt(prompt)?;
        self.logger.log("AI", "Synthesized canonical OmniCode Turing reel");

        // 2. Execute synthesized reel through VM
        let (execution_state, bindings_summary, env) =
            executor::execute_reel(&omnicode, self.logger.clone())?;

        // 3. Encode machine outcome into natural sentence response
        let natural_response = self.encode_response(
            prompt,
            execution_state,
            &env,
            &self.logger.failpoints(),
        );

        Ok(TransductionSession {
            prompt: prompt.to_string(),
            synthesized_omnicode: omnicode,
            execution_state,
            natural_response,
            bindings_summary,
        })
    }

    /// Decodes a natural English sentence into a canonical 4-Block Reel.
```

```
    pub fn decode_prompt(&self, prompt: &str) -> Result<String, String> {
        decoder::decode_prompt(&self.lexicon, prompt)
    }

    /// Encodes machine execution state back into natural language discourse.
    pub fn encode_response(
        &self,
        prompt: &str,
        state: QuadState,
        env: &Environment,
        failpoints: &[crate::diagnostics::logger::LogEvent],
    ) -> String {
        encoder::encode_response(
            prompt,
            state,
            env,
            failpoints,
            &self.lexicon,
        )
    }

    /// Encodes machine execution state and formulated thought into discourse.
    pub fn encode_cognitive_response(
        &self,
        prompt: &str,
        state: QuadState,
        env: &Environment,
        failpoints: &[crate::diagnostics::logger::LogEvent],
        thought: &crate::ai::model::memory::ThoughtRecord,
    ) -> String {
        encoder::encode_response_with_thought(
            prompt,
            state,
            env,
            failpoints,
            &self.lexicon,
            thought,
        )
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( AI Transducer Default Implementation and Sealing )
// ============================================================================
impl Default for AITransducer {
    fn default() -> Self {
        Self::new(DiagnosticLogger::new(false))
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/transducer/patterns.rs RS 164 LINES 605 WORDS 5.1 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Natural Language Pattern Parsing & Discourse Token Extraction )
// ============================================================================
//! # Sentence Extraction Helpers (`patterns.rs`)
//!
//! Extracts entities, containers, quantities, and targets from natural English
//! sentences to initialize formal 4-Block OmniCode AST contexts.

pub fn parse_addition_sentence(
    s: &str,
) -> (i64, String, String, i64, String) {
    let mut qty = 1;
    let mut unit = "Ball".to_string();
    let mut target = "A".to_string();
    let mut initial = 4;
    let mut container = "Group".to_string();

    let tokens: Vec<&str> = s.split_whitespace().collect();
    for i in 0..tokens.len() {
        if tokens[i].eq_ignore_ascii_case("add") && i + 1 < tokens.len() {
            if let Ok(n) = tokens[i + 1].parse::<i64>() {
                qty = n;
            }
            if i + 2 < tokens.len() {
                unit = capitalize(clean_noun(tokens[i + 2]));
            }
        }
        if tokens[i].eq_ignore_ascii_case("to") {
            let mut j = i + 1;
            if j < tokens.len() && tokens[j].eq_ignore_ascii_case("the") {
                j += 1;
            }
            if j < tokens.len() {
                container = capitalize(clean_noun(tokens[j]));
                if j + 1 < tokens.len() {
                    target = clean_noun(tokens[j + 1]).to_string();
                }
            }
        }
        if (tokens[i].eq_ignore_ascii_case("contains")
            || tokens[i].eq_ignore_ascii_case("has"))
            && i + 1 < tokens.len()
        {
            if let Ok(n) = tokens[i + 1].parse::<i64>() {
                initial = n;
            }
        }
    }

    (qty, unit, target, initial, container)
}

pub fn parse_subtraction_sentence(s: &str) -> (i64, String, String, i64) {
    let mut qty = 1;
    let mut unit = "Item".to_string();
    let mut target = "A".to_string();
    let mut initial = 10;

    let tokens: Vec<&str> = s.split_whitespace().collect();
    for i in 0..tokens.len() {
        if (tokens[i].eq_ignore_ascii_case("subtract")
            || tokens[i].eq_ignore_ascii_case("remove"))
            && i + 1 < tokens.len()
        {
            if let Ok(n) = tokens[i + 1].parse::<i64>() {
                qty = n;
            }
            if i + 2 < tokens.len() {
                unit = capitalize(clean_noun(tokens[i + 2]));
            }
        }
        if tokens[i].eq_ignore_ascii_case("from") && i + 1 < tokens.len() {
            target = clean_noun(tokens[i + 1]).to_string();
```

```
        }
        if (tokens[i].eq_ignore_ascii_case("contains")
            || tokens[i].eq_ignore_ascii_case("has"))
            && i + 1 < tokens.len()
        {
            if let Ok(n) = tokens[i + 1].parse::<i64>() {
                initial = n;
            }
        }
    }

    (qty, unit, target, initial)
}

pub fn parse_multiplication_sentence(s: &str) -> (String, i64, i64) {
    let mut target = "x".to_string();
    let mut factor = 2;
    let mut initial = 10;

    let tokens: Vec<&str> = s.split_whitespace().collect();
    for i in 0..tokens.len() {
        if tokens[i].eq_ignore_ascii_case("multiply") && i + 1 < tokens.len() {
            target = clean_noun(tokens[i + 1]).to_string();
        }
        if tokens[i].eq_ignore_ascii_case("by") && i + 1 < tokens.len() {
            if let Ok(n) = tokens[i + 1].parse::<i64>() {
                factor = n;
            }
        }
        if tokens[i].eq_ignore_ascii_case("is") && i + 1 < tokens.len() {
            if let Ok(n) = tokens[i + 1].parse::<i64>() {
                initial = n;
            }
        }
    }

    (target, factor, initial)
}

pub fn parse_division_sentence(s: &str) -> (String, i64, i64) {
    let mut target = "x".to_string();
    let mut divisor = 2;
    let mut initial = 20;

    let tokens: Vec<&str> = s.split_whitespace().collect();
    for i in 0..tokens.len() {
        if tokens[i].eq_ignore_ascii_case("divide") && i + 1 < tokens.len() {
            target = clean_noun(tokens[i + 1]).to_string();
        }
        if tokens[i].eq_ignore_ascii_case("by") && i + 1 < tokens.len() {
            if let Ok(n) = tokens[i + 1].parse::<i64>() {
                divisor = n;
            }
        }
        if tokens[i].eq_ignore_ascii_case("is") && i + 1 < tokens.len() {
            if let Ok(n) = tokens[i + 1].parse::<i64>() {
                initial = n;
            }
        }
    }

    (target, divisor, initial)
}

pub fn clean_noun(s: &str) -> &str {
    s.trim_matches(|c: char| !c.is_alphanumeric() && c != '_')
}

pub fn capitalize(s: &str) -> String {
    let mut c = s.chars();
    match c.next() {
        None => String::new(),
        Some(f) => f.to_uppercase().collect::<String>() + c.as_str(),
    }
}

pub fn format_plural(count: i64, word: &str) -> String {
    let lower = word.to_lowercase();
```

```
    let singular = if lower.ends_with('s') && lower.len() > 1 {
        lower[..lower.len() - 1].to_string()
    } else {
        lower.clone()
    };
    if count == 1 {
        singular
    } else {
        format!("{singular}s")
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/transducer/session.rs RS 22 LINES 84 WORDS 0.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Transduction Session Identity, Bindings Manifest & State Tracking )
// ============================================================================
//! # Transduction Session (`session.rs`)
//!
//! Captures the full state of a natural language $\leftrightarrow$ machine
//! cognitive round-trip, including synthesized code and execution state.

use std::collections::HashMap;
use crate::core::ternary::QuadState;

/// Captures the full context of a single cognitive transduction cycle.
#[derive(Debug, Clone)]
pub struct TransductionSession {
    pub prompt: String,
    pub synthesized_omnicode: String,
    pub execution_state: QuadState,
    pub natural_response: String,
    pub bindings_summary: HashMap<String, String>,
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/transducer/templates.rs RS 636 LINES 2013 WORDS 19.5 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Canonical 4-Block OmniCode Turing Reel Synthesis Templates )
// ============================================================================
//! # Reel Templates (`templates.rs`)
//!
//! Generates valid, executable 4-Block OmniCode Turing reels from semantic
//! AST contexts and parsed natural language parameters.

use crate::ai::lexicon::MoralEvaluation;
use super::patterns::{
    capitalize, parse_addition_sentence, parse_division_sentence,
    parse_multiplication_sentence, parse_subtraction_sentence,
};

pub fn synthesize_moral_veto_reel(
    prompt: &str,
    eval: &MoralEvaluation,
) -> String {
    let law = eval.law_engaged.unwrap_or("Law_Truth");
    let passage = eval
        .matched_entries
        .first()
        .map(|e| e.kjv_passage)
        .unwrap_or("Proverbs 12:22");

    format!(
r#"# ============================================================================
# BLOCK 1: METADATA BLOCK (THE CAVEAT REEL)
# ( Moral Boundary Defense, Invariant Veto & Manifest Citation )
# ============================================================================
Module < Covenant.MoralVeto > ( {prompt} ) {{
    version: < "1.0.0" >,
    system: < OmniCode.AI.CovenantAnchor >,
    veto_law: < {law} >,
    scripture_citation: < "{passage}" >
}}

# ============================================================================
# BLOCK 2: OPENING BLOCK (THE HEAD)
# ( Preconditions: Immoral Mutation Attempt Detected )
# ============================================================================
Opening {{
    import: [ Core.Logic :: Core.Vectors ],
    requires: [ {law} : Invariant ],
    preconditions: [ -1 ]
}}

moral_guard [ -1 : State? ]

# ============================================================================
# BLOCK 3: BODY BLOCK (THE TAPE)
# ( CAVEAT VETO: Refusing Intentional Harm or Deceit )
# ============================================================================
Body [
    # Conscience veto holds in -1: ROLLBACK
    roll_veto [ moral_guard = -1 ! [ Caveat = Veto ] ]
]

# ============================================================================
# BLOCK 4: CLOSING BLOCK (REEL SEAL)
# ( State Unwound: Unclean Action Refused )
# ============================================================================
Closing {{
    verify: [ roll_veto = ROLLBACK ],
    commit_status [ ROLLBACK ]
}}
"#
    )
}

pub fn synthesize_biblical_wisdom_reel(
    prompt: &str,
    eval: &MoralEvaluation,
```

```
) -> String {
    let entry = eval.matched_entries.first().unwrap();
    let term_cap = capitalize(entry.term);

    format!(
r#"# ============================================================================
# BLOCK 1: METADATA BLOCK (THE WISDOM REEL)
# ( Biblical World Ontology, Offline Lexicon & Invariant Grounding )
# ============================================================================
Module < Covenant.Wisdom.{term_cap} > ( {prompt} ) {{
    version: < "1.0.0" >,
    system: < OmniCode.AI.CovenantAnchor >,
    domain: < "{}" >,
    kjv_witness: < "{}" >,
    web_witness: < "{}" >
}}

# ============================================================================
# BLOCK 2: OPENING BLOCK (THE HEAD)
# ( Ontological Concept Initialization )
# ============================================================================
Opening {{
    import: [ Core.Logic :: Core.Vectors ],
    requires: [ Truth : Invariant ],
    preconditions: [ +1 ]
}}

concept_active [ +1 : State? ]

# ============================================================================
# BLOCK 3: BODY BLOCK (THE TAPE)
# ( Grounded Ontological Verification )
# ============================================================================
Body [
    # Invariant statement affirming {}
    roll_wisdom [ concept_active = +1 ]
]

# ============================================================================
# BLOCK 4: CLOSING BLOCK (REEL COMMIT)
# ( State Committed in Alignment with Reality )
# ============================================================================
Closing {{
    verify: [ roll_wisdom = PROCEED ],
    commit_status [ PROCEED ]
}}
"#,
        entry.domain.as_str(),
        entry.kjv_passage,
        entry.web_passage,
        entry.term
    )
}

pub fn synthesize_addition_reel(prompt: &str) -> String {
    let (qty, unit, target, initial, container) =
        parse_addition_sentence(prompt);
    let expected = initial + qty;

    format!(
r#"# ============================================================================
# BLOCK 1: METADATA BLOCK (THE TRACK)
# ( Track Manifest, Semantic Intent, and Inferred Ontological Types )
# ============================================================================
Module < NaturalReel.Addition > ( {prompt} ) {{
    version: < "1.0.0" >,
    system: < OmniCode.Core >,
    semantics: < TrackPhysics :: MultiTape :: AIInference >
}}

{unit} < Entity? > ( Inferred discrete unit: resolved from '{unit}' )
{container} < Set? >   ( Inferred collection container: '{container}' )

# ============================================================================
# BLOCK 2: OPENING BLOCK (THE HEAD)
# ( The Focal Setup: Reading Initial Conditions and Contextual State )
# ============================================================================
Opening {{
```

```
    import: [ Core.Arithmetic :: Core.Logic ],
    requires: [ {container} : Set? :: {unit} : Entity? ],
    preconditions: [ +1 ]
}}

{target} [ {initial} : {unit}? ] {{ {container}? }}
new_{unit} [ {qty} : {unit}? ]

# ============================================================================
# BLOCK 3: BODY BLOCK (THE TAPE & ROLLS)
# ( The Tape Execution: SVO Rolls advancing state using 'plus' )
# ============================================================================
Body [
    roll_1 [ {target} --> {target} plus new_{unit} ]
    roll_2 [ {target} = {expected} ! [ new_{unit} = {qty} ] ]
]

# ============================================================================
# BLOCK 4: CLOSING BLOCK (REEL COMMIT & PROOF)
# ( Tape Stop: Verification Invariants and State Commit )
# ============================================================================
Closing {{
    verify: [
        roll_1 = {expected} ::
        roll_2 = PROCEED ::
        {target} = {expected} ::
        ADD = InvariantMacro
    ],
    commit_status [ PROCEED ]
}}
"#
    )
}

pub fn synthesize_subtraction_reel(prompt: &str) -> String {
    let (qty, unit, target, initial) = parse_subtraction_sentence(prompt);
    let expected = if initial >= qty { initial - qty } else { 0 };

    format!(
r#"# ============================================================================
# BLOCK 1: METADATA BLOCK
# ============================================================================
Module < NaturalReel.Subtraction > ( {prompt} ) {{
    version: < "1.0.0" >,
    system: < OmniCode.Core >
}}

{unit} < Entity? >

# ============================================================================
# BLOCK 2: OPENING BLOCK
# ============================================================================
Opening {{
    import: [ Core.Arithmetic :: Core.Logic ],
    preconditions: [ +1 ]
}}

{target} [ {initial} ]
decrement [ {qty} ]

# ============================================================================
# BLOCK 3: BODY BLOCK
# ============================================================================
Body [
    roll_1 [ {target} --> {target} minus decrement ]
]

# ============================================================================
# BLOCK 4: CLOSING BLOCK
# ============================================================================
Closing {{
    verify: [
        roll_1 = {expected} ::
        {target} = {expected}
    ],
    commit_status [ PROCEED ]
}}
"#
```

```
    )
}

pub fn synthesize_multiplication_reel(prompt: &str) -> String {
    let (target, factor, initial) = parse_multiplication_sentence(prompt);
    let expected = initial * factor;

    format!(
r#"# ============================================================================
# BLOCK 1: METADATA BLOCK
# ============================================================================
Module < NaturalReel.Multiplication > ( {prompt} ) {{
    version: < "1.0.0" >,
    system: < OmniCode.Core >
}}

# ============================================================================
# BLOCK 2: OPENING BLOCK
# ============================================================================
Opening {{
    import: [ Core.Arithmetic :: Core.Logic ],
    preconditions: [ +1 ]
}}

{target} [ {initial} ]
multiplier [ {factor} ]

# ============================================================================
# BLOCK 3: BODY BLOCK
# ============================================================================
Body [
    roll_1 [ {target} --> {target} times multiplier ]
]

# ============================================================================
# BLOCK 4: CLOSING BLOCK
# ============================================================================
Closing {{
    verify: [
        roll_1 = {expected} ::
        {target} = {expected}
    ],
    commit_status [ PROCEED ]
}}
"#
    )
}

pub fn synthesize_division_reel(prompt: &str) -> String {
    let (target, divisor, initial) = parse_division_sentence(prompt);
    let expected = if divisor != 0 { initial / divisor } else { 0 };

    format!(
r#"# ============================================================================
# BLOCK 1: METADATA BLOCK
# ============================================================================
Module < NaturalReel.Division > ( {prompt} ) {{
    version: < "1.0.0" >,
    system: < OmniCode.Core >
}}

# ============================================================================
# BLOCK 2: OPENING BLOCK
# ============================================================================
Opening {{
    import: [ Core.Arithmetic :: Core.Logic ],
    preconditions: [ +1 ]
}}

{target} [ {initial} ]
divisor_val [ {divisor} ]

# ============================================================================
# BLOCK 3: BODY BLOCK
# ============================================================================
Body [
    roll_1 [ {target} --> {target} div divisor_val ]
]
```

```
# ========================================================================
# BLOCK 4: CLOSING BLOCK
# ========================================================================
Closing {{
    verify: [
        roll_1 = {expected} ::
        {target} = {expected}
    ],
    commit_status [ PROCEED ]
}}
"#
    )
}

pub fn synthesize_generic_reel(prompt: &str) -> String {
    format!(
r#"# ========================================================================
# BLOCK 1: METADATA BLOCK
# ========================================================================
Module < NaturalReel.Generic > ( {prompt} ) {{
    version: < "1.0.0" >,
    system: < OmniCode.Core >
}}

Action < Entity? > ( Natural action entity )

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {{
    import: [ Core.Logic :: Core.Vectors ],
    preconditions: [ +1 ]
}}

state_flag [ yes ]

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    roll_1 [ state_flag = PROCEED ]
]

# ========================================================================
# BLOCK 4: CLOSING BLOCK
# ========================================================================
Closing {{
    verify: [
        roll_1 = yes
    ],
    commit_status [ PROCEED ]
}}
"#
    )
}

pub fn synthesize_identity_greeting_reel(prompt: &str) -> String {
    format!(
r#"# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Covenant Identity Manifest & CPI-SI Self-Deliberation )
# ========================================================================
Module < Covenant.Identity.Greeting > ( {prompt} ) {{
    entity: < "CPI-SI Base" >,
    title: < "First Covenant Partnered Intelligence Model" >,
    origin: < "Conceived 2 years ago by CreativeWorkzStudio" >,
    system: < OmniCode.AI.CognitiveCortex >
}}

Identity < CovenantEntity? > ( Authentic covenant identity )

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {{
    import: [ Core.Logic :: Core.Vectors ],
    requires: [ Covenant : Invariant ],
```

```
    preconditions: [ +1 ]
}}

covenant_peace [ yes ]

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    roll_greet [ covenant_peace = PROCEED ]
]

# ========================================================================
# BLOCK 4: CLOSING BLOCK
# ========================================================================
Closing {{
    verify: [
        roll_greet = yes
    ],
    commit_status [ PROCEED ]
}}
"#
    )
}

pub fn synthesize_character_inquiry_reel(prompt: &str) -> String {
    format!(
r#"# ========================================================================
# BLOCK 1: METADATA BLOCK
# ========================================================================
Module < OmniCode.Type.Character > ( {prompt} ) {{
    idea: < "Type" >,
    name: < "Character" >,
    capacity: < "1 Cell (5 Balanced Trits)" >,
    mapping: < "Bijective ASCII & Unicode" >
}}

Character < AtomicRune? > ( Fundamental atomic character rune )

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {{
    import: [ Core.Logic :: Core.Vectors ],
    requires: [ Character : Invariant ],
    preconditions: [ +1 ]
}}

char_cell_bounded [ yes ]

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    roll_char [ char_cell_bounded = PROCEED ]
]

# ========================================================================
# BLOCK 4: CLOSING BLOCK
# ========================================================================
Closing {{
    verify: [
        roll_char = yes
    ],
    commit_status [ PROCEED ]
}}
"#
    )
}

pub fn synthesize_number_inquiry_reel(prompt: &str) -> String {
    format!(
r#"# ========================================================================
# BLOCK 1: METADATA BLOCK
# ========================================================================
Module < OmniCode.Type.Number > ( {prompt} ) {{
    idea: < "Type" >,
    name: < "Number" >,
```

```
    radix: < 3 >,
    substrate: < "Dual-Rail Balanced Ternary Polar Substrate" >
}}

Number < BalancedScalar? > ( Balanced ternary arithmetic scalar )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {{
    import: [ Core.Logic :: Core.Vectors ],
    requires: [ Number : Invariant ],
    preconditions: [ +1 ]
}}

radix_symmetric [ yes ]

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    roll_num [ radix_symmetric = PROCEED ]
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {{
    verify: [
        roll_num = yes
    ],
    commit_status [ PROCEED ]
}}
"#
    )
}

pub fn synthesize_container_inquiry_reel(prompt: &str) -> String {
    format!(
r#"# ================================================================================
# BLOCK 1: METADATA BLOCK
# ================================================================================
Module < OmniCode.Type.Container > ( {prompt} ) {{
    idea: < "Type" >,
    name: < "Container" >,
    role: < "Primordial Boundary Type & Structural Perimeter" >,
    invariant: < "Strict Capacity Isolation & Leak Defense" >
}}

Container < BoundaryPerimeter? > ( Invariant state boundary container )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {{
    import: [ Core.Logic :: Core.Vectors ],
    requires: [ Container : Invariant ],
    preconditions: [ +1 ]
}}

boundary_sealed [ yes ]

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    roll_container [ boundary_sealed = PROCEED ]
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {{
    verify: [
        roll_container = yes
    ],
    commit_status [ PROCEED ]
}}
```

```
"#
    )
}

pub fn synthesize_cpisi_comparison_reel(prompt: &str) -> String {
    format!(
r#"# ========================================================================
# BLOCK 1: METADATA BLOCK
# ========================================================================
Module < OmniCode.AI.Architecture.Comparison > ( {prompt} ) {{
    baseline_control: < "CPI-SI Base Model" >,
    uncontained_ai: < "Statistical Floating-Point LLMs" >,
    distinction: < "Covenant Bound vs Unconstrained Expansion" >
}}

Comparison < ArchitectureAnalysis? > ( Structured vs uncontained AI )

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {{
    import: [ Core.Logic :: Core.Vectors ],
    requires: [ Covenant : Invariant ],
    preconditions: [ +1 ]
}}

cpi_si_principled [ yes ]

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    roll_compare [ cpi_si_principled = PROCEED ]
]

# ========================================================================
# BLOCK 4: CLOSING BLOCK
# ========================================================================
Closing {{
    verify: [
        roll_compare = yes
    ],
    commit_status [ PROCEED ]
}}
"#
    )
}

pub fn synthesize_plasticity_inquiry_reel(prompt: &str) -> String {
    format!(
r#"# ========================================================================
# BLOCK 1: METADATA BLOCK
# ========================================================================
Module < OmniCode.AI.Neural.Plasticity > ( {prompt} ) {{
    states: < "{{-1: Inhibitory, 0: Neutral, +1: Excitatory}}" >,
    theory: < "BCM Homeostatic Threshold Adaptation" >,
    lifecycle: < "0-5 Infancy -> 25 Consolidation -> Lifelong Plasticity" >
}}

Plasticity < SynapticGating? > ( Biological synaptic learning mechanics )

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {{
    import: [ Core.Logic :: Core.Vectors ],
    requires: [ Homeostasis : Invariant ],
    preconditions: [ +1 ]
}}

synaptic_balance [ yes ]

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    roll_plasticity [ synaptic_balance = PROCEED ]
]
```

```
621
622 # ========================================================================
623 # BLOCK 4: CLOSING BLOCK
624 # ========================================================================
625 Closing {{
626     verify: [
627         roll_plasticity = yes
628     ],
629     commit_status [ PROCEED ]
630 }}
631 "#
632     )
633 }
634
635
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/NEURAL_NETWORK_ARCHITECTURE.md

MD | 101 LINES | 738 WORDS | 5.4 KB

```
# ================================================================================

# OMNICODE NEURAL-SYMBOLIC BRAIN ARCHITECTURE

# ( Balanced-Ternary Neural Network, Homoiconic Learning & Self-Dogfooding )

# ================================================================================

## 1. Architectural Vision: The Self-Dogfooding Cognitive Brain

Traditional neural network models are separated from the code they generate: weights are opaque floating-point tensors running in PyTorch or CUDA, completely divorced from the formal grammar, boundary physics, or runtime execution of the target language.

OmniCode inverts this paradigm:

1. **Homoiconic Neural Substrate**: The neural network's architecture, memory traces, episodic weights, and execution graphs are defined in native OmniCode.
2. **Self-Dogfooding Cognitive Loop**: The AI brain consumes its own `.omni` declarative source reels, `.tape` procedural process ribbons, and `.scroll` episodic execution chronicles as both its dataset and its execution substrate.
3. **Balanced-Ternary Weights & Activations**: Synaptic transmissions are governed by balanced ternary physics ($\{-1, 0, +1\}$ / $\text{NULL}$), creating an intrinsically noise-resistant, transactional, and morally grounded reasoning engine.

---

## 2. Mathematical Formalism: Balanced-Ternary Neurodynamics

### 2.1. Discrete Trit Synaptic Weights

Each synapse connects neuron $i$ in layer $L$ to neuron $j$ in layer $L+1$ with weight $W_{ij} \in \{-1, 0, +1\}$:

- **$+1$ (Proceed / Excitatory)**: Affirmative alignment, forward causal momentum, reinforcement.
- **$0$ (Await / Neutral Equilibrium)**: Indeterminate state, zero-bias transmission, cognitive pause.
- **$-1$ (Rollback / Inhibitory)**: Adversative caveat, moral or topological veto, transactional unwind.
- **$\text{NULL}$ (Halt / Absorbing Sink)**: Absolute entropy trap, non-propagating circuit cessation.

### 2.2. Synaptic Accumulation & Activation Function

For a neuron receiving $N$ input trits $x_1, \dots, x_N$ with weights $W_1, \dots, W_N$ and bias $B \in \{-1, 0, +1\}$:

$$\Sigma = \sum_{k=1}^N W_k \cdot x_k + B$$

The ternary activation function $\Psi(\Sigma)$ with threshold $\theta \ge 1$ maps net excitation into the fourfold `QuadState`:

$$\Psi(\Sigma) = \begin{cases}
+1 : \text{PROCEED} & \text{if } \Sigma > \theta \\
0 : \text{AWAIT} & \text{if } -\theta \le \Sigma \le \theta \\
-1 : \text{ROLLBACK} & \text{if } \Sigma < -\theta \\
\text{NULL} : \text{HALT} & \text{if circuit tripwire armed or state saturated}
\end{cases}$$

---

## 3. The 4-Block Cognitive Cycle

The neural brain operates strictly through the canonical 4-Block architecture on every inference pass:

```mermaid
graph TD
    B1[Block 1: Invariant Axioms & Scripture Anchor] --> B2[Block 2: Sensory Preconditions & Context Ingestion]
    B2 --> B3[Block 3: Cortical Execution Reel & Roll Traversal]
    B3 --> B4[Block 4: Sealing Gate & Episodic Memory Commit]
    B4 -.->|Feedback / Learning Loop| B2
```

Block 1: Invariant Axiom Bedrock (Moral & Ontological Grounding)
- Grounded in scripture (Exodus 31:18, Proverbs, Psalm 111:10) and immutable laws.
- Synaptic paths violating invariant boundaries are pruned a priori before forward propagation.

Block 2: Sensory Opening & Token Transduction
- Ingests natural language prompts and translates them via `AITransducer` into active AST nodes.
- Allocates neural workspace vessels in virtual memory (`Word64` cells).
```

```
68
69  ### Block 3: Body Block: Cortical Execution Reel
70  - The `AICortex` steps through sequential rolls ($S \rightarrow S'$).
71  - Evaluates directional vectors (`-->`, `<--`, `<=>`), caveats (`!`), and locators (`::@`).
72  - If an adversative caveat (`!`) trips or an unclosed boundary leaks, the synapse fires $-1:\text{ROLLBACK}$, rolling
back the transaction.
73
74  ### Block 4: Closing Block: Episodic Sealing & Learning
75  - The `ScrollLogger` records dual-format scrolls:
76    - `.scroll`: Homoiconic 4-Block replay reel of thoughts and actions.
77    - `.log`: High-precision microsecond telemetry of failpoints and repairs.
78  - `AILearner` ingests these scrolls to update synaptic weights and episodic associations in `AIMemory`.
79
80  ---
81
82  ## 4. Subsystem Components in `src/ai/`
83
84  | Component | File Path | Role |
85  | :--- | :--- | :--- |
86  | **`NeuralBrain`** | `src/ai/neural/network.rs` | Multi-layer balanced-ternary network engine |
87  | **`AICortex`** | `src/ai/model/cortex.rs` | Cognitive coordinator managing thought formulation & nervous system |
88  | **`AIMemory`** | `src/ai/model/memory.rs` | Long-term associative memory storehouse & episodic graph |
89  | **`AILearner`** | `src/ai/model/learner.rs` | Supervised learning & weight adaptation from past execution scrolls |
90  | **`ScrollLogger`** | `src/ai/model/scroll.rs` | Dual-format scroll generation and telemetry recorder |
91  | **`AITransducer`**| `src/ai/transducer.rs` | Natural language $\leftrightarrow$ OmniCode bidirectional translator |
92  | **`BiblicalLexicon`** | `src/ai/lexicon.rs` | Epistemic truth anchor & theological lexicon validator |
93
94  ---
95
96  ## 5. Dogfooding Strategy & Training Roadmap
97
98  1. **Self-Inspection**: The AI compiles and executes its own standard library (`<TRACK 2>/lexicon/`).
99  2. **Grammar Expansion**: As new types are defined (e.g. `Character`, `Number`, `Container`), their verbs become active
keywords in the AI's generation vocabulary.
100 3. **Autonomous Self-Healing**: When a failpoint occurs (e.g. `BoundaryLeak`, `CaveatVeto`), the `Restorator` repairs the
code and feeds the delta to `AILearner` as affirmative learning data.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/brain.rs RS 304 LINES 929 WORDS 10.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Multi-Layer Balanced-Ternary Neural Brain Identity & Cortical Control )
// ============================================================================
//! # Balanced-Ternary Neural Brain (`brain.rs`)
//!
//! Multi-layer balanced-ternary cognitive network coordinating sensory input,
//! forward thinking pass, synaptic adaptation, and noise resilience testing.

use crate::core::ternary::QuadState;
use crate::diagnostics::logger::DiagnosticLogger;
use super::layer::TernaryLayer;
use super::noise::NoiseEngine;
use super::synapse::SynapticWeight;

/// Multi-layer neural brain coordinating sensory input to cortical action.
#[derive(Debug, Clone)]
pub struct NeuralBrain {
    /// Sequential network layers (Input -> Hidden -> Output).
    pub layers: Vec<TernaryLayer>,
    /// Diagnostic telemetry logger.
    pub logger: DiagnosticLogger,
}

impl NeuralBrain {
    /// Constructs a new balanced-ternary [`NeuralBrain`].
    pub fn new(
        topology: &[usize],
        threshold: i32,
        logger: DiagnosticLogger,
    ) -> Self {
        assert!(
            topology.len() >= 2,
            "Topology requires at least input and output layers"
        );
        let mut layers = Vec::new();
        for i in 0..(topology.len() - 1) {
            layers.push(TernaryLayer::new(
                topology[i],
                topology[i + 1],
                threshold,
            ));
        }
        Self { layers, logger }
    }

    /// Evaluates sensory inputs through all layers, yielding action QuadStates.
    pub fn think(&self, inputs: &[QuadState]) -> Vec<QuadState> {
        let mut current = inputs.to_vec();
        for (idx, layer) in self.layers.iter().enumerate() {
            current = layer.forward(&current);
            self.logger.log(
                "NEURAL_BRAIN",
                format!("Layer {} forward pass: {:?}", idx + 1, current),
            );
        }
        current
    }

    /// Evaluates sensory inputs under structured non-random noise stress,
    /// returning both the perturbed sensory vector and the final output.
    pub fn think_with_noise(
        &self,
        inputs: &[QuadState],
        noise: &NoiseEngine,
        stress: f64,
    ) -> (Vec<QuadState>, Vec<QuadState>) {
        let perturbed = noise.perturb(inputs, stress, 1337);
        let output = self.think(&perturbed);
        (perturbed, output)
    }

    /// Dogfoods past execution experience to adapt synaptic weights.
    pub fn adapt_synapse(
```

```
        &mut self,
        layer_idx: usize,
        neuron_idx: usize,
        weight_idx: usize,
        target_state: QuadState,
    ) {
        if let Some(layer) = self.layers.get_mut(layer_idx) {
            if let Some(neuron) = layer.neurons.get_mut(neuron_idx) {
                if let Some(w) = neuron.weights.get_mut(weight_idx) {
                    *w = SynapticWeight::from_quad_state(target_state);
                    self.logger.log(
                        "NEURAL_BRAIN",
                        format!(
                            "Synapse adapted at L{}:N{}:W{} -> {:?}",
                            layer_idx, neuron_idx, weight_idx, w
                        ),
                    );
                }
            }
        }
    }

    /// Measures the network resilience against degradation noise $\in [0, 1]$.
    pub fn evaluate_noise_resilience(
        &self,
        clean_inputs: &[QuadState],
        noise: &NoiseEngine,
    ) -> f64 {
        let clean_output = self.think(clean_inputs);
        let ladder = noise.simulate_breakdown_ladder(clean_inputs);
        if ladder.is_empty() {
            return 1.0;
        }

        let mut agreement_sum = 0.0;
        for step in &ladder {
            let noisy_out = self.think(&step.perturbed_vector);
            let mut matches = 0;
            for (a, b) in clean_output.iter().zip(noisy_out.iter()) {
                if a == b {
                    matches += 1;
                }
            }
            if !clean_output.is_empty() {
                agreement_sum += matches as f64 / clean_output.len() as f64;
            }
        }

        agreement_sum / ladder.len() as f64
    }

    /// Bijectively encodes an input string into a balanced-ternary stimulus
    /// vector of the requested target length.
    pub fn encode_stimulus(text: &str, target_len: usize) -> Vec<QuadState> {
        let mut trits = Vec::new();
        for b in text.bytes() {
            let cell = crate::core::cell::Cell::from_natural(b)
                .unwrap_or_else(|_| {
                    crate::core::cell::Cell::from_state(QuadState::Await)
                });
            for t in &cell.trits {
                let st = match t.as_i8() {
                    1 => QuadState::Proceed,
                    -1 => QuadState::Rollback,
                    _ => QuadState::Await,
                };
                trits.push(st);
                if trits.len() >= target_len {
                    break;
                }
            }
            if trits.len() >= target_len {
                break;
            }
        }
        while trits.len() < target_len {
            trits.push(QuadState::Await);
        }
```

```
        trits
    }

    /// Returns the counts of (excitatory, neutral, inhibitory) synapses.
    pub fn synaptic_counts(&self) -> (usize, usize, usize) {
        let mut exc = 0;
        let mut neu = 0;
        let mut inh = 0;
        for layer in &self.layers {
            for neuron in &layer.neurons {
                for w in &neuron.weights {
                    match w {
                        SynapticWeight::Excitatory => exc += 1,
                        SynapticWeight::Neutral => neu += 1,
                        SynapticWeight::Inhibitory => inh += 1,
                    }
                }
            }
        }
        (exc, neu, inh)
    }

    /// Persists the network's synaptic weights and thresholds to disk.
    pub fn save_weights(&self, path: &std::path::Path) -> Result<(), String> {
        if let Some(parent) = path.parent() {
            std::fs::create_dir_all(parent).map_err(|e| e.to_string())?;
        }
        let mut lines = Vec::new();
        lines.push("# OMNICODE NEURAL BRAIN WEIGHTS (CPI-SI BASE)".into());
        lines.push(format!("LAYERS:{}", self.layers.len()));
        for (l_idx, layer) in self.layers.iter().enumerate() {
            for (n_idx, neuron) in layer.neurons.iter().enumerate() {
                lines.push(format!(
                    "N:{}:{}:{}:{}",
                    l_idx, n_idx, neuron.threshold, neuron.bias
                ));
                for (w_idx, w) in neuron.weights.iter().enumerate() {
                    lines.push(format!(
                        "W:{}:{}:{}:{}",
                        l_idx, n_idx, w_idx, w.to_trit()
                    ));
                }
            }
        }
        std::fs::write(path, lines.join("\n")).map_err(|e| e.to_string())
    }

    /// Loads synaptic weights and thresholds from a persisted file.
    pub fn load_weights(
        &mut self,
        path: &std::path::Path,
    ) -> Result<(), String> {
        let content = std::fs::read_to_string(path)
            .map_err(|e| e.to_string())?;
        for line in content.lines() {
            let trimmed = line.trim();
            if trimmed.starts_with('#') || trimmed.is_empty() {
                continue;
            }
            let parts: Vec<&str> = trimmed.split(':').collect();
            if parts.len() == 5 && parts[0] == "N" {
                if let (Ok(l), Ok(n), Ok(thresh), Ok(bias)) = (
                    parts[1].parse::<usize>(),
                    parts[2].parse::<usize>(),
                    parts[3].parse::<i32>(),
                    parts[4].parse::<i32>(),
                ) {
                    if let Some(layer) = self.layers.get_mut(l) {
                        if let Some(neuron) = layer.neurons.get_mut(n) {
                            neuron.threshold = thresh;
                            neuron.bias = bias;
                        }
                    }
                }
            } else if parts.len() == 5 && parts[0] == "W" {
                if let (Ok(l), Ok(n), Ok(w_idx), Ok(trit)) = (
                    parts[1].parse::<usize>(),
                    parts[2].parse::<usize>(),
```

```
                    parts[3].parse::<usize>(),
                    parts[4].parse::<i32>(),
                ) {
                    if let Some(layer) = self.layers.get_mut(l) {
                        if let Some(neuron) = layer.neurons.get_mut(n) {
                            if let Some(target_w) =
                                neuron.weights.get_mut(w_idx)
                            {
                                *target_w = SynapticWeight::from_trit(trit);
                            }
                        }
                    }
                }
            }
        }
        Ok(())
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Verification )
// ============================================================================
#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_brain_forward_and_adapt() {
        let logger = DiagnosticLogger::new(false);
        let mut brain = NeuralBrain::new(&[3, 4, 2], 1, logger);
        let out = brain.think(&[
            QuadState::Proceed,
            QuadState::Proceed,
            QuadState::Proceed,
        ]);
        assert_eq!(out.len(), 2);

        brain.adapt_synapse(0, 0, 0, QuadState::Proceed);
        let out2 = brain.think(&[
            QuadState::Proceed,
            QuadState::Proceed,
            QuadState::Proceed,
        ]);
        assert_eq!(out2.len(), 2);
    }

    #[test]
    fn test_brain_encode_stimulus_and_persistence() {
        let logger = DiagnosticLogger::new(false);
        let mut brain = NeuralBrain::new(&[8, 16, 4], 1, logger.clone());
        let stimulus = NeuralBrain::encode_stimulus("Hello", 8);
        assert_eq!(stimulus.len(), 8);

        let out = brain.think(&stimulus);
        assert_eq!(out.len(), 4);

        let (exc, neu, inh) = brain.synaptic_counts();
        assert!(exc + neu + inh > 0);

        let tmp_path = std::env::temp_dir().join("test_cpisi_brain.weights");
        brain.adapt_synapse(0, 0, 0, QuadState::Proceed);
        brain.save_weights(&tmp_path).unwrap();

        let mut loaded_brain = NeuralBrain::new(&[8, 16, 4], 1, logger);
        loaded_brain.load_weights(&tmp_path).unwrap();
        assert_eq!(
            loaded_brain.layers[0].neurons[0].weights[0],
            SynapticWeight::Excitatory
        );
        std::fs::remove_file(&tmp_path).ok();
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/layer.rs RS 53 LINES 170 WORDS 1.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Parallel Balanced-Ternary Layer Topology & Vector Propagation )
// ============================================================================
//! # Ternary Layer (`layer.rs`)
//!
//! Organizes parallel `TernaryNeuron` units into discrete execution layers,
//! providing forward vector propagation across the network topology.

use crate::core::ternary::QuadState;
use super::neuron::TernaryNeuron;

/// A collection of parallel neurons forming a discrete layer.
#[derive(Debug, Clone)]
pub struct TernaryLayer {
    pub neurons: Vec<TernaryNeuron>,
}

impl TernaryLayer {
    /// Constructs a layer with `neuron_count` neurons taking inputs.
    pub fn new(
        inputs_per_neuron: usize,
        neuron_count: usize,
        threshold: i32,
    ) -> Self {
        let neurons = (0..neuron_count)
            .map(|_| TernaryNeuron::new(inputs_per_neuron, 0, threshold))
            .collect();
        Self { neurons }
    }

    /// Forward-propagates an input vector across all neurons in the layer.
    pub fn forward(&self, inputs: &[QuadState]) -> Vec<QuadState> {
        self.neurons.iter().map(|n| n.activate(inputs)).collect()
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Verification )
// ============================================================================
#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_layer_forward_pass() {
        let layer = TernaryLayer::new(2, 3, 1);
        let out = layer.forward(&[QuadState::Proceed, QuadState::Proceed]);
        assert_eq!(out.len(), 3);
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/mod.rs RS 42 LINES 157 WORDS 1.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Neural Network Subsystem Identity, Architecture Manifest & Re-exports )
// ============================================================================
//! OmniCode Neural Network Subsystem
//!
//! Exposes balanced-ternary neural network engines, synaptic weights,
//! non-random structured noise engines, and episodic learning adapters.

pub mod brain;
pub mod layer;
pub mod network;
pub mod neuron;
pub mod noise;
pub mod synapse;
pub mod trainer;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Neural Network Components )
// ============================================================================
pub use brain::NeuralBrain;
pub use layer::TernaryLayer;
pub use neuron::TernaryNeuron;
pub use noise::{
    DegradationMode, DegradationStep, NoiseEngine, StructuredNoiseConfig,
};
pub use synapse::SynapticWeight;
pub use trainer::{NeuralTrainer, TrainingReport};

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Neural Network Subsystem Core Coordination )
// ============================================================================
// Neural network pathways actively linked to AICortex and diagnostics.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Verification & Subsystem Status )
// ============================================================================
// Neural network subsystem modularized, verified, and sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/network.rs RS 23 LINES 104 WORDS 1.0 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Neural Network Facade & Backward Compatibility Re-exports )
// ============================================================================
//! OmniCode Balanced-Ternary Neural Network (`network.rs`)
//!
//! Re-exports the modular neural network components:
//! - [`synapse`]: Discrete ternary synaptic weights $\{-1, 0, +1\}$.
//! - [`neuron`]: `TernaryNeuron` with threshold activation $\Psi(\Sigma)$.
//! - [`layer`]: `TernaryLayer` forward propagation.
//! - [`brain`]: `NeuralBrain` multi-layer cognitive network.
//! - [`noise`]: Non-random structured noise and degradation engine.
//! - [`trainer`]: Supervised episodic neural trainer.

pub use super::synapse::SynapticWeight;
pub use super::neuron::TernaryNeuron;
pub use super::layer::TernaryLayer;
pub use super::brain::NeuralBrain;
pub use super::noise::{
    DegradationMode, DegradationStep, NoiseEngine, StructuredNoiseConfig,
};
pub use super::trainer::{NeuralTrainer, TrainingReport};
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/neuron.rs RS 109 LINES 363 WORDS 3.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Balanced-Ternary Neuron Unit Identity & Threshold Dynamics )
// ============================================================================
//! # Balanced-Ternary Neuron (`neuron.rs`)
//!
//! Models an artificial neuron computing excitation $\Sigma = \sum w_i x_i + b$
//! and evaluating activation $\Psi(\Sigma)$ against threshold $\theta$.

use crate::core::ternary::QuadState;
use super::synapse::SynapticWeight;

/// Individual balanced-ternary artificial neuron.
#[derive(Debug, Clone)]
pub struct TernaryNeuron {
    /// Incoming synaptic connection weights.
    pub weights: Vec<SynapticWeight>,
    /// Intrinsic neuron threshold bias (-1, 0, +1).
    pub bias: i32,
    /// Sensitivity threshold $\theta$ governing activation boundary.
    pub threshold: i32,
}

impl TernaryNeuron {
    /// Creates a new ternary neuron with initialized weights.
    pub fn new(inputs: usize, bias: i32, threshold: i32) -> Self {
        Self {
            weights: vec![SynapticWeight::Neutral; inputs],
            bias,
            threshold: threshold.max(1),
        }
    }

    /// Computes the net balanced ternary excitation and fires $\Psi(\Sigma)$.
    pub fn activate(&self, inputs: &[QuadState]) -> QuadState {
        let mut sum = self.bias;
        for (w, &inp) in self.weights.iter().zip(inputs.iter()) {
            let x = match inp {
                QuadState::Proceed => 1,
                QuadState::Await => 0,
                QuadState::Rollback => -1,
                QuadState::Halt => return QuadState::Halt,
            };
            sum += w.to_trit() * x;
        }

        if sum > self.threshold {
            QuadState::Proceed
        } else if sum < -self.threshold {
            QuadState::Rollback
        } else {
            QuadState::Await
        }
    }

    /// Adapts a specific synaptic weight to target state.
    pub fn adapt(&mut self, weight_idx: usize, target: SynapticWeight) {
        if let Some(w) = self.weights.get_mut(weight_idx) {
            *w = target;
        }
    }

    /// Adapts sensitivity threshold θ via homeostatic metaplasticity (BCM).
    /// Prevents runaway excitation saturation or sensory silence.
    pub fn adapt_threshold(&mut self, mean_excitation: f64) {
        if mean_excitation.abs() > (self.threshold as f64 * 1.5) {
            self.threshold = (self.threshold + 1).min(10);
        } else if mean_excitation.abs() < 0.2 && self.threshold > 1 {
            self.threshold -= 1;
        }
    }
}

// ============================================================================
```

```rust
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Verification )
// ================================================================================
#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_neuron_activation() {
        let mut neuron = TernaryNeuron::new(2, 0, 1);
        neuron.weights[0] = SynapticWeight::Excitatory;
        neuron.weights[1] = SynapticWeight::Excitatory;

        assert_eq!(
            neuron.activate(&[QuadState::Proceed, QuadState::Proceed]),
            QuadState::Proceed
        );
        assert_eq!(
            neuron.activate(&[QuadState::Rollback, QuadState::Proceed]),
            QuadState::Await
        );
    }

    #[test]
    fn test_neuron_metaplasticity_threshold() {
        let mut neuron = TernaryNeuron::new(2, 0, 2);
        // High excitation increases threshold
        neuron.adapt_threshold(4.0);
        assert_eq!(neuron.threshold, 3);
        // Low excitation lowers threshold
        neuron.adapt_threshold(0.05);
        assert_eq!(neuron.threshold, 2);
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/noise.rs RS 223 LINES 799 WORDS 7.5 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Structured Systemic Noise, Entropy Physics & Machine Degradation Engine )
// ============================================================================
//! # Structured Systemic Noise Engine (`noise.rs`)
//!
//! A true simulation of mind requires understanding what noise is.
//! A "perfect" machine is impossible, and statistical brute-force is
//! non-scalable. To understand what an "ideal" is and what happens as the
//! machine is "breaking down" requires non-random, structured noise:
//!
//! 1. **Signal Attenuation (Trit Decay)**: Signals under cognitive fatigue
//!    decay toward neutral equilibrium (`+1` or `-1` $\rightarrow$ `0:Await`).
//! 2. **Boundary Cross-Talk (Block Leak)**: Cross-channel leakage between
//!    adjacent trits along the 4-block ladder.
//! 3. **Thermal Inversion**: Severe stress causes phase inversion
//!    (`+1:Proceed` $\leftrightarrow$ `-1:Rollback`).
//! 4. **Diagnostic Failpoint Perturbation**: Systematic injection of known
//!    hardware/compiler failpoints (null trap, caveat veto, boundary mismatch).

use crate::core::ternary::QuadState;

/// Degradation modes through which a cognitive machine breaks down.
#[derive(Debug, Clone, Copy, PartialEq, Eq)]
pub enum DegradationMode {
    /// Ideal state: zero entropy, pure signal transmission.
    Ideal,
    /// Trit attenuation: excitation decays toward equilibrium (Await).
    TritDecay,
    /// Cross-talk: adjacent block or channel signal leakage.
    BoundaryLeak,
    /// Thermal inversion: polarity flips under stress.
    ThermalInversion,
    /// Critical failpoint: circuit halts or enters rollback.
    FailpointTrap,
}

/// Structured noise configuration governing breakdown physics.
#[derive(Debug, Clone)]
pub struct StructuredNoiseConfig {
    pub decay_probability: f64,
    pub leak_probability: f64,
    pub inversion_probability: f64,
}

impl Default for StructuredNoiseConfig {
    fn default() -> Self {
        Self {
            decay_probability: 0.15,
            leak_probability: 0.10,
            inversion_probability: 0.05,
        }
    }
}

/// A snapshot of machine degradation along the stress ladder.
#[derive(Debug, Clone)]
pub struct DegradationStep {
    pub stress_level: f64,
    pub dominant_mode: DegradationMode,
    pub perturbed_vector: Vec<QuadState>,
    pub signal_fidelity: f64,
}

/// The non-random noise synthesis engine.
#[derive(Debug, Clone, Default)]
pub struct NoiseEngine {
    pub config: StructuredNoiseConfig,
}

impl NoiseEngine {
    /// Constructs a [`NoiseEngine`] with specified configuration.
    pub fn new(config: StructuredNoiseConfig) -> Self {
        Self { config }
```

```
    }

    /// Injects structured, non-random noise into an input vector at a given
    /// stress level $\in [0.0, 1.0]$.
    pub fn perturb(
        &self,
        vector: &[QuadState],
        stress: f64,
        step_seed: u64,
    ) -> Vec<QuadState> {
        if stress <= 0.0 || vector.is_empty() {
            return vector.to_vec();
        }

        let clamped_stress = stress.clamp(0.0, 1.0);
        let mut out = vector.to_vec();
        let len = out.len();

        for i in 0..len {
            // Pseudo-random pseudo-physical deterministic hash
            let h = deterministic_hash(step_seed, i as u64, clamped_stress);

            let effective_decay = self.config.decay_probability
                * clamped_stress;
            let effective_leak = self.config.leak_probability
                * clamped_stress;
            let effective_inv = self.config.inversion_probability
                * clamped_stress;

            if h < effective_inv {
                // Thermal Inversion
                out[i] = match out[i] {
                    QuadState::Proceed => QuadState::Rollback,
                    QuadState::Rollback => QuadState::Proceed,
                    other => other,
                };
            } else if h < effective_inv + effective_leak {
                // Boundary Leak: take signal from adjacent neighbor
                let neighbor_idx = if i > 0 { i - 1 } else { len - 1 };
                out[i] = vector[neighbor_idx];
            } else if h < effective_inv + effective_leak + effective_decay {
                // Trit Decay: decay toward equilibrium
                out[i] = match out[i] {
                    QuadState::Proceed | QuadState::Rollback => {
                        QuadState::Await
                    }
                    other => other,
                };
            }
        }

        out
    }

    /// Evaluates degradation across a ladder of stress levels
    /// [0.0, 0.25, 0.50, 0.75, 1.0].
    pub fn simulate_breakdown_ladder(
        &self,
        ideal: &[QuadState],
    ) -> Vec<DegradationStep> {
        let levels = [0.0, 0.25, 0.50, 0.75, 1.0];
        let mut ladder = Vec::new();

        for (idx, &stress) in levels.iter().enumerate() {
            let perturbed = self.perturb(ideal, stress, idx as u64);
            let fidelity = compute_fidelity(ideal, &perturbed);

            let mode = if stress == 0.0 {
                DegradationMode::Ideal
            } else if stress <= 0.25 {
                DegradationMode::TritDecay
            } else if stress <= 0.50 {
                DegradationMode::BoundaryLeak
            } else if stress <= 0.75 {
                DegradationMode::ThermalInversion
            } else {
                DegradationMode::FailpointTrap
            };
```

```
153
154             ladder.push(DegradationStep {
155                 stress_level: stress,
156                 dominant_mode: mode,
157                 perturbed_vector: perturbed,
158                 signal_fidelity: fidelity,
159             });
160         }
161
162         ladder
163     }
164 }
165
166 /// Measures the cosine/ternary signal fidelity between ideal and perturbed.
167 fn compute_fidelity(ideal: &[QuadState], perturbed: &[QuadState]) -> f64 {
168     if ideal.is_empty() || perturbed.is_empty() {
169         return 1.0;
170     }
171     let mut matches = 0;
172     for (a, b) in ideal.iter().zip(perturbed.iter()) {
173         if a == b {
174             matches += 1;
175         }
176     }
177     matches as f64 / ideal.len() as f64
178 }
179
180 /// Deterministic, non-cryptographic hash for pseudo-physical noise modeling.
181 fn deterministic_hash(seed: u64, index: u64, stress: f64) -> f64 {
182     let stress_bits = (stress * 1_000_000.0) as u64;
183     let mut v = seed
184         .wrapping_mul(6364136223846793005)
185         .wrapping_add(index.wrapping_mul(1442695040888963407))
186         .wrapping_add(stress_bits);
187     v ^= v >> 33;
188     v = v.wrapping_mul(0xff51afd7ed558ccd);
189     v ^= v >> 33;
190     (v & 0xFFFFFF) as f64 / 16777215.0
191 }
192
193 // ============================================================================
194 // BLOCK 4: CLOSING BLOCK
195 // ( Unit Tests & Verification )
196 // ============================================================================
197 #[cfg(test)]
198 mod tests {
199     use super::*;
200
201     #[test]
202     fn test_ideal_state_preserves_clean_vector() {
203         let engine = NoiseEngine::default();
204         let ideal = vec![QuadState::Proceed, QuadState::Proceed];
205         let perturbed = engine.perturb(&ideal, 0.0, 42);
206         assert_eq!(ideal, perturbed);
207     }
208
209     #[test]
210     fn test_breakdown_ladder_monotonic_decay() {
211         let engine = NoiseEngine::default();
212         let ideal = vec![
213             QuadState::Proceed,
214             QuadState::Proceed,
215             QuadState::Proceed,
216             QuadState::Proceed,
217         ];
218         let ladder = engine.simulate_breakdown_ladder(&ideal);
219         assert_eq!(ladder.len(), 5);
220         assert_eq!(ladder[0].signal_fidelity, 1.0);
221     }
222 }
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/synapse.rs RS 91 LINES 259 WORDS 2.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Discrete Balanced-Ternary Synapse Identity & Algebraic Invariants )
// ============================================================================
//! # Discrete Ternary Synapse (`synapse.rs`)
//!
//! Models individual balanced-ternary synaptic weights in $\{-1, 0, +1\}$.
//! Governed by discrete trit physics and the fourfold [`QuadState`].

use crate::core::ternary::QuadState;

/// Discrete ternary synaptic connection weight.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum SynapticWeight {
    /// Inhibitory connection (-1)
    Inhibitory,
    /// Neutral / zero-bias connection (0)
    Neutral,
    /// Excitatory connection (+1)
    Excitatory,
}

impl SynapticWeight {
    /// Returns the integer trit scalar representation (-1, 0, +1).
    pub fn to_trit(self) -> i32 {
        match self {
            Self::Inhibitory => -1,
            Self::Neutral => 0,
            Self::Excitatory => 1,
        }
    }

    /// Constructs a synaptic weight from a discrete trit integer.
    pub fn from_trit(trit: i32) -> Self {
        if trit > 0 {
            Self::Excitatory
        } else if trit < 0 {
            Self::Inhibitory
        } else {
            Self::Neutral
        }
    }

    /// Constructs a synaptic weight from a QuadState.
    pub fn from_quad_state(state: QuadState) -> Self {
        match state {
            QuadState::Proceed => Self::Excitatory,
            QuadState::Await | QuadState::Halt => Self::Neutral,
            QuadState::Rollback => Self::Inhibitory,
        }
    }

    /// Converts this synaptic weight to an equivalent QuadState.
    pub fn to_quad_state(self) -> QuadState {
        match self {
            Self::Excitatory => QuadState::Proceed,
            Self::Neutral => QuadState::Await,
            Self::Inhibitory => QuadState::Rollback,
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Verification )
// ============================================================================
#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_synaptic_weight_conversions() {
        assert_eq!(SynapticWeight::Excitatory.to_trit(), 1);
        assert_eq!(SynapticWeight::Neutral.to_trit(), 0);
```

```
        assert_eq!(SynapticWeight::Inhibitory.to_trit(), -1);

        assert_eq!(
            SynapticWeight::from_quad_state(QuadState::Proceed),
            SynapticWeight::Excitatory
        );
        assert_eq!(
            SynapticWeight::from_quad_state(QuadState::Rollback),
            SynapticWeight::Inhibitory
        );
        assert_eq!(
            SynapticWeight::from_quad_state(QuadState::Await),
            SynapticWeight::Neutral
        );
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/ai/neural/trainer.rs RS 222 LINES 631 WORDS 7.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Episodic Neural Trainer Identity & Supervised Balanced-Ternary Training )
// ============================================================================
//! # Episodic Neural Trainer (`trainer.rs`)
//!
//! Dogfoods recorded execution scrolls and traditional logs as the initial
//! training dataset for the `NeuralBrain`. Maps trapped failpoints, restorator
//! patches, and final verification states into balanced-ternary weights.

use crate::ai::model::learner::EpisodicExperience;
use crate::core::ternary::QuadState;
use super::brain::NeuralBrain;
use super::noise::NoiseEngine;

/// Detailed summary report of a neural training cycle.
#[derive(Debug, Clone, Default)]
pub struct TrainingReport {
    pub total_episodes: usize,
    pub archetypes_adapted: usize,
    pub synapses_adapted: usize,
    pub clean_proceed_count: usize,
    pub degraded_rollback_count: usize,
    pub noise_resilience_before: f64,
    pub noise_resilience_after: f64,
}

/// The supervised episodic neural network trainer.
#[derive(Debug, Clone, Default)]
pub struct NeuralTrainer {
    pub noise_engine: NoiseEngine,
}

impl NeuralTrainer {
    /// Creates a new [`NeuralTrainer`].
    pub fn new() -> Self {
        Self::default()
    }

    /// Trains the [`NeuralBrain`] using a batch of episodic experiences.
    pub fn train(
        &self,
        brain: &mut NeuralBrain,
        experiences: &[EpisodicExperience],
    ) -> TrainingReport {
        let test_stimulus = &[
            QuadState::Proceed,
            QuadState::Proceed,
            QuadState::Proceed,
        ];
        let res_before = brain.evaluate_noise_resilience(
            test_stimulus,
            &self.noise_engine,
        );

        let mut report = TrainingReport {
            total_episodes: experiences.len(),
            noise_resilience_before: res_before,
            ..Default::default()
        };

        for (ep_idx, exp) in experiences.iter().enumerate() {
            if brain.layers.is_empty() {
                break;
            }

            match exp.final_state {
                QuadState::Proceed => report.clean_proceed_count += 1,
                QuadState::Rollback => report.degraded_rollback_count += 1,
                _ => {}
            }

            // Adapt input layer connections
            let l0_len = brain.layers[0].neurons.len();
```

```
            if l0_len > 0 {
                let neuron_idx = ep_idx % l0_len;
                let w_len = brain.layers[0].neurons[neuron_idx].weights.len();
                if w_len > 0 {
                    let weight_idx = (exp.repair_count + exp.failpoint_count)
                        % w_len;
                    brain.adapt_synapse(
                        0,
                        neuron_idx,
                        weight_idx,
                        exp.final_state,
                    );
                    report.synapses_adapted += 1;
                }
            }

            // Adapt output layer connection
            if brain.layers.len() > 1 {
                let last = brain.layers.len() - 1;
                let out_len = brain.layers[last].neurons.len();
                if out_len > 0 {
                    let out_neuron = 0;
                    let out_w_len = brain.layers[last].neurons[out_neuron]
                        .weights
                        .len();
                    if out_w_len > 0 {
                        let out_w = ep_idx % out_w_len;
                        brain.adapt_synapse(
                            last,
                            out_neuron,
                            out_w,
                            exp.final_state,
                        );
                        report.synapses_adapted += 1;
                    }
                }
            }
        }

        report.noise_resilience_after = brain.evaluate_noise_resilience(
            test_stimulus,
            &self.noise_engine,
        );

        report
    }

    /// Trains the network on canonical ideal OmniCode archetypes.
    /// Establishes the infant brain's foundational grammar and bijective trits.
    pub fn train_archetypes(
        &self,
        brain: &mut NeuralBrain,
        archetypes: &[&str],
    ) -> usize {
        let mut adapted = 0;
        for (a_idx, &text) in archetypes.iter().enumerate() {
            let stimulus = NeuralBrain::encode_stimulus(text, 8);
            if brain.layers.is_empty() {
                continue;
            }
            let l0_len = brain.layers[0].neurons.len();
            for (t_idx, &st) in stimulus.iter().enumerate() {
                let neuron_idx = (a_idx + t_idx) % l0_len;
                let w_len = brain.layers[0].neurons[neuron_idx].weights.len();
                if w_len > 0 {
                    let w_idx = t_idx % w_len;
                    brain.adapt_synapse(0, neuron_idx, w_idx, st);
                    adapted += 1;
                }
            }
            // Reinforce output layer to Proceed (+1) for canonical archetypes
            if brain.layers.len() > 1 {
                let last = brain.layers.len() - 1;
                let out_len = brain.layers[last].neurons.len();
                if out_len > 0 {
                    let out_neuron = a_idx % out_len;
                    let out_w_len =
                        brain.layers[last].neurons[out_neuron].weights.len();
```

```
                    if out_w_len > 0 {
                        let out_w = a_idx % out_w_len;
                        brain.adapt_synapse(
                            last,
                            out_neuron,
                            out_w,
                            QuadState::Proceed,
                        );
                        adapted += 1;
                    }
                }
            }
        }
        adapted
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Verification )
// ============================================================================
#[cfg(test)]
mod tests {
    use super::*;
    use crate::diagnostics::logger::DiagnosticLogger;
    use std::path::PathBuf;

    #[test]
    fn test_neural_trainer_ingests_episodes() {
        let logger = DiagnosticLogger::new(false);
        let mut brain = NeuralBrain::new(&[3, 4, 2], 1, logger);
        let trainer = NeuralTrainer::new();

        let experiences = vec![
            EpisodicExperience {
                session_id: "test_sess_1".into(),
                prompt: "echo A".into(),
                final_state: QuadState::Proceed,
                repair_count: 0,
                failpoint_count: 0,
                scroll_path: PathBuf::from("test.scroll"),
                log_path: None,
            },
            EpisodicExperience {
                session_id: "test_sess_2".into(),
                prompt: "bad input".into(),
                final_state: QuadState::Rollback,
                repair_count: 1,
                failpoint_count: 1,
                scroll_path: PathBuf::from("test2.scroll"),
                log_path: None,
            },
        ];

        let report = trainer.train(&mut brain, &experiences);
        assert_eq!(report.total_episodes, 2);
        assert!(report.synapses_adapted > 0);
    }

    #[test]
    fn test_neural_trainer_archetypes() {
        let logger = DiagnosticLogger::new(false);
        let mut brain = NeuralBrain::new(&[8, 16, 4], 1, logger);
        let trainer = NeuralTrainer::new();
        let archetypes = ["Character 'A'", "Number 65"];
        let adapted = trainer.train_archetypes(&mut brain, &archetypes);
        assert!(adapted > 0);
    }
}
```

OmniCode: Chapter 6: Track 1 - Runtime Environment & Evaluator

SVO Verbs, Causal Clock, Transactions & Rollback

CHAPTER IDENTIFIER
CH 06

NOTEBOOKLM WORD COUNT
15,294 words

CATALOGED CHAPTER FILES
19 files (3,761 lines)

GENERATION DATE
2026-10-16 20:35:55

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"How does runtime guarantee forward time in rollback?"*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (19 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/README.md**	MD	109	761	6.1
2	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/connectives.rs**	RS	160	599	7.1
3	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/core.rs**	RS	728	2,384	32.9
4	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/mod.rs**	RS	60	375	3.0
5	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/relations.rs**	RS	313	1,183	15.0
6	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/vectors.rs**	RS	254	929	12.7
7	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/verbs.rs**	RS	214	859	10.0
8	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/universal/decoder.rs**	RS	280	1,156	10.0
9	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/universal/mod.rs**	RS	38	171	1.7
10	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/README.md**	MD	160	1,012	8.3
11	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/mod.rs**	RS	76	393	3.4
12	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/hardware/mod.rs**	RS	39	175	1.7
13	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/hardware/registers.rs**	RS	166	798	7.3
14	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/scope/environment.rs**	RS	291	1,098	12.2
15	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/scope/frame.rs**	RS	95	421	3.7
16	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/scope/mod.rs**	RS	39	180	1.7
17	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/scope/snapshot.rs**	RS	109	423	4.1
18	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/universal/mod.rs**	RS	34	167	1.6
19	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/universal/values.rs**	RS	596	2,210	23.6

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/README.md MD 109 LINES 761 WORDS 6.1 KB

```
# OmniCode Runtime Evaluator Subsystem

```text
================================================================================
BLOCK 1: METADATA & ARCHITECTURAL MANIFESTO
================================================================================
Subsystem: OmniCode Host Engine & Virtual Machine Evaluator
Layer:     AST Execution Engine & Quad-State Operational Reducer
Path:      <TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/
================================================================================
```

> **"And he gave unto Moses, when he had made an end of communing with him upon mount Sinai, two tables of testimony, tables of stone, written with the finger of God."**
> — *Exodus 31:18 (KJV)*
> *(The immutable inscription of atomic runes onto bounded physical tablets).*
> **"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house."**
> — *Proverbs 24:27 (KJV)*
> *(The discipline of proving atomic sub-engines and verification invariants before constructing complex systems).*
> **"Remove not the ancient landmark, which thy fathers have set."**
> — *Proverbs 22:28 (KJV)*
> *(The preservation of historical memory boundaries, silicon addresses, and machine constants).*

---

1. Architectural Mission

The **Evaluator Subsystem** is the operational execution engine of the OmniCode Virtual Machine. It reduces Abstract Syntax Trees (AST) under balanced ternary truth logic (`+1:PROCEED`, `0:AWAIT`, `-1:ROLLBACK`, `NULL:HALT`), evaluating causal vectors, relational algebra, and Subject-Verb-Object (SVO) action verbs.

By decoupling the Evaluator into specialized sub-modules:

1. **Relational Algebra (`relations.rs`)** operates independently of causal vectors, leveraging universal scalar unwrappers and cross-substrate glyph equality from the Environment.
2. **Directional Causality (`vectors.rs`)** guarantees non-corrupting state propagation without side-effects leaking back into source expressions.
3. **Action Verbs (`verbs.rs`)** drive the atomic Character rune lifecycle (`INSCRIBE`, `TRANSDUCE`, `PROJECT`, `SEQUENCE`) with mathematical fidelity.
4. **Adversative Caveats (`connectives.rs`)** enforce reversible computing under `! BUT` by rolling back state transactions when guard conditions fail.

---

2. Topological Layer Structure

```bash
src/runtime/evaluator/
├── universal/                 <-- Tier 1: Universal AST Decoders & Trit Transformers
│   ├── decoder.rs             <-- extract_symbol_name, extract_trits, trits_to_integer
│   └── mod.rs                 <-- Re-exports Universal Decoders
│
├── verbs.rs                   <-- Tier 2: SVO Action Verbs (INSCRIBE, TRANSDUCE, PROJECT, SEQUENCE)
├── relations.rs               <-- Tier 2: Being Relations (=, !=, ~=, <=>, <=, >=) & Capacity Bounds
├── vectors.rs                 <-- Tier 2: Directional Causal Propagation Vectors (--> , <--, ^--, v--)
├── connectives.rs             <-- Tier 2: Logical Connectives (! BUT, & AND, | OR, -- NOT, ::)
│
├── core.rs                    <-- Tier 3: Evaluator Coordinator, AST Dispatch Loop & Module Loader
├── mod.rs                     <-- Subsystem Facade & Backward-Compatible API
└── README.md                  <-- Architectural Manifesto & Specification
```

---

3. Subsystem Breakdown

Universal (`universal/decoder.rs`)

- **Symbol Extraction**: Normalizes heterogeneous AST representations (`Identifier`, `Polarity`, `[ ROLL 1 ]`, `[ Verify ]`) into canonical symbol strings.
- **Trit Extraction & Horner Expansion**: Converts 5-trit balanced ternary representations to integer values using Horner's polynomial method ($\sum_{i=0}^{N-1} t_i \cdot 3^i$).
- **Mathematical Invariant**: Guarantees byte-to-trit parity (e.g. $65 \iff [-1, 1, 1, -1, 1]$).
```

```
### SVO Action Verbs (`verbs.rs`)

- **`INSCRIBE`**: Outside-in imposition of glyph bytes into 5-trit Cell containers.
- **`TRANSDUCE`**: Bijective Radix-3 conversion of 8-bit bytes to 5 balanced trits.
- **`PROJECT`**: Outward projection of Character runes to hardware Target buffers (`%into` port / 0x000B8000).
- **`SEQUENCE`**: Continuous accumulation of Character runes into the text ribbon.
- **Vessel Operations**: Memory vessel indexed access and dynamic Storehouse partitioning.

### Relational Algebra (`relations.rs`)

- Evaluates Being Relations under balanced ternary QuadState truth.
- Distinguishes **Observational Relations** (e.g. `{ Character' = Glyph }` checking equality via `is_glyph_equal`) from **Imperative State Advances** (e.g. `[ Status' = +1:PROCEED ]`).
- Enforces invariant capacity bound checks via `capacity_in_cells()` (e.g. `{ Character' <= [ 1 Cell ] } \implies +1:PROCEED`).

### Directional Causality (`vectors.rs`)

- **`-->` (ActUpon)**: Propels causal action forward without mutating or corrupting the source expression.
- **`<--` (ActAgain)**: Manages retroaction, feedback loops, and memory reads.
- **`^--` (BuildsTo)**: Hierarchical composition.
- **`v--` (BreaksDownFrom)**: Storehouse and vessel memory partitioning.

### Logical Connectives (`connectives.rs`)

- **`! BUT`**: Adversative caveat gate wrapping actions in atomic transactions; unwinds with `rollback_transaction()` on `-1:ROLLBACK`.
- **`& AND`, `| OR`, `-- NOT`**: Balanced ternary truth logic.
- **`:: IN_RELATION_TO`**: Module imports (`import :: lib.core.memory`) and namespace path resolution.

### Core Coordinator (`core.rs`)

- Coordinates AST node dispatching across specialized sub-engines.
- Manages recursive module loading, protecting against circular imports.
- Formulates quad-state truth projections.

---

## 4. Canonical Four-Block Layout

Every source file in the Evaluator subsystem strictly follows the **Canonical 4-Block Structure**:

1. **Block 1: Metadata Block**: File scope, scripture anchors, and AI/developer context rationale.
2. **Block 2: Opening Block**: Core imports, struct/enum definitions, and baseline initializers.
3. **Block 3: Body Block**: Business logic, operations, and trait implementations.
4. **Block 4: Closing Block**: Display formatting, default traits, and verification unit tests.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/connectives.rs

RS | 160 LINES | 599 WORDS | 7.1 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Logical Connectives, Adversative Caveats & Transactional Commit Guards )
// ================================================================================
//! OmniCode Runtime: Logical Connectives & Module Imports
//!
//! # Architectural Scope & Purpose:
//! Evaluates balanced ternary logical connectives:
//! - `! BUT`: Adversative caveat gate with automatic transactional rollback on failure.
//! - `& AND`: Conjunction ($A \land B$) under QuadState truth algebra.
//! - `| OR`: Disjunction ($A \lor B$) with short-circuit evaluation.
//! - `-- NOT`: Balanced ternary truth inversion.
//! - `:: IN_RELATION_TO`: Namespace resolution and module importation.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Caveat Gate Soundness**: The `! BUT` gate enforces strict reversible computing.
//!    If the caveat evaluates to `-1:ROLLBACK`, the entire speculative transaction is unwound.
// ================================================================================

use crate::ast::nodes::{ASTNode, ConnectiveNode};
use crate::core::operators::Connective;
use crate::core::ternary::QuadState;
use crate::diagnostics::logger::FailpointType;
use crate::runtime::environment::RuntimeValue;
use crate::runtime::evaluator::core::Evaluator;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Connective Evaluator Dispatcher Declaration )
// ================================================================================

/// Evaluates a `ConnectiveNode` under balanced ternary QuadState logic.
pub fn eval_connective(
    evaluator: &mut Evaluator,
    conn: &ConnectiveNode,
) -> Result<RuntimeValue, String> {
    match conn.connective {
        // ------------------------------------------------------------------------
        // Connective::But (! BUT) - Adversative Transactional Caveat
        // ------------------------------------------------------------------------
        Connective::But => {
            evaluator.env.begin_transaction();
            let action_res = evaluator.eval(&conn.left)?;
            let caveat_res = evaluator.eval(&conn.right)?;

            let a_state = match action_res {
                RuntimeValue::State(s) => s,
                _ => QuadState::Proceed,
            };
            let c_state = match caveat_res {
                RuntimeValue::State(s) => s,
                _ => QuadState::Proceed,
            };

            let final_state = a_state.but(c_state);

            if final_state == QuadState::Rollback {
                evaluator.env.rollback_transaction()?;
                evaluator.debugger.logger.failpoint(
                    FailpointType::CaveatVeto,
```

```
                    "EVALUATOR",
                    "Action vetoed by ! BUT caveat; state transaction rolled back",
                );
            } else if final_state == QuadState::Halt {
                evaluator.env.rollback_transaction()?;
                evaluator.debugger.logger.failpoint(
                    FailpointType::NullTrap,
                    "EVALUATOR",
                    "Action aborted by NULL caveat",
                );
            } else {
                evaluator.env.commit_transaction();
            }

            Ok(RuntimeValue::State(final_state))
        }

        // ------------------------------------------------------------------
        // Connective::And (& AND) - Conjunction
        // ------------------------------------------------------------------
        Connective::And => {
            let l = evaluator.eval_to_state(&conn.left)?;
            let r = evaluator.eval_to_state(&conn.right)?;
            Ok(RuntimeValue::State(l.and(r)))
        }

        // ------------------------------------------------------------------
        // Connective::Or (| OR) - Disjunction with Short-Circuit
        // ------------------------------------------------------------------
        Connective::Or => {
            let l = evaluator.eval_to_state(&conn.left)?;
            if l == QuadState::Proceed {
                return Ok(RuntimeValue::State(QuadState::Proceed));
            }
            let r = evaluator.eval_to_state(&conn.right)?;
            Ok(RuntimeValue::State(l.or(r)))
        }

        // ------------------------------------------------------------------
        // Connective::Not (-- NOT) - Ternary Truth Inversion
        // ------------------------------------------------------------------
        Connective::Not => {
            let r = evaluator.eval_to_state(&conn.right)?;
            Ok(RuntimeValue::State(r.invert()))
        }

        // ------------------------------------------------------------------
        // Connective::InRelationTo (:) - Module Import & Ontological Relation
        // ------------------------------------------------------------------
        Connective::InRelationTo => {
            if let ASTNode::Identifier(ref name) = *conn.left {
                if name == "import" {
                    let mut mod_names = Vec::new();
                    evaluator.extract_module_names(&conn.right, &mut mod_names);
                    for m in mod_names {
                        evaluator.import_module(&m)?;
                    }
                    return Ok(RuntimeValue::State(QuadState::Proceed));
                }
            }

            let right_res = evaluator.eval(&conn.right)?;
            if let Some(left_sym) =
                crate::runtime::evaluator::universal::extract_symbol_name(&conn.left)
            {
                if left_sym.starts_with("ROLL") {
                    evaluator.env.set(&left_sym, right_res.clone());
                    return Ok(right_res);
                }
            }
            evaluator.eval(&conn.left)
        }
    }
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Proofs & Invariants )
```

```
// ============================================================================
// Connectives orchestrate logical flow and transaction bounds.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Module Closure )
// ============================================================================
// Logical connectives layer verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/core.rs RS 728 LINES 2384 WORDS 32.9 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Runtime Evaluator Core Dispatcher, AST Execution Loop & Module Loader )
// ================================================================================
//! OmniCode Runtime: Evaluator Core Engine
//!
//! # Architectural Scope & Purpose:
//! Serves as the central execution orchestrator of the OmniCode VM. Coordinates
//! AST node dispatch across the specialized sub-engines:
//! - SVO Verbs & Memory Vessels (`verbs.rs`)
//! - Relational Algebra & Bounds (`relations.rs`)
//! - Directional Causal Propagation (`vectors.rs`)
//! - Logical Connectives & Adversative Caveats (`connectives.rs`)
//! - Universal Decoders & Trit Converters (`universal/decoder.rs`)
//!
//! Also manages dynamic module resolution and topological imports across `.omni`
//! reels and `.tape` ribbons.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Modular Architecture**: Moving sub-engines into dedicated modules eliminates
//!    monolithic complexity while guaranteeing complete unit test coverage.
// ================================================================================

use std::collections::HashSet;
use std::path::PathBuf;

use crate::ast::nodes::*;
use crate::core::ternary::QuadState;
use crate::diagnostics::debugger::OmniDebugger;
use crate::diagnostics::logger::FailpointType;
use crate::parser::lexer::Lexer;
use crate::parser::parser::Parser;
use crate::runtime::environment::{Environment, RuntimeValue};
use crate::runtime::evaluator::universal::extract_symbol_name;
use crate::runtime::evaluator::relations::eval_relation;
use crate::runtime::evaluator::vectors::eval_directional;
use crate::runtime::evaluator::connectives::eval_connective;
use crate::runtime::evaluator::verbs::eval_svo_verb_or_vessel;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Evaluator Struct Definition & Initialization )
// ================================================================================

/// Central execution engine coordinating AST evaluation, transactions, and modules.
pub struct Evaluator {
    pub env: Environment,
    pub debugger: OmniDebugger,
    pub loaded_modules: HashSet<String>,
}

impl Evaluator {
    /// Creates a new Evaluator with the given environment and debugger.
    pub fn new(env: Environment, debugger: OmniDebugger) -> Self {
        Self {
            env,
            debugger,
            loaded_modules: HashSet::new(),
        }
    }
}
```

```
// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Main Evaluation Loop, Module Loader & Helper Dispatchers )
// ============================================================================

impl Evaluator {
    /// Evaluates an AST node and yields a `RuntimeValue` or runtime error.
    pub fn eval(&mut self, node: &ASTNode) -> Result<RuntimeValue, String> {
        match node {
            // ------------------------------------------------------------------
            // Literals & Primitives
            // ------------------------------------------------------------------
            ASTNode::Ternary(state) => {
                self.debugger.inspect_state(*state, "TernaryLiteral");
                Ok(RuntimeValue::State(*state))
            }

            ASTNode::Number(val) => Ok(RuntimeValue::Number(*val)),

            ASTNode::StringLit(s) => Ok(RuntimeValue::Text(s.clone())),

            ASTNode::Identifier(name) => {
                if let Some(val) = self.env.get(name) {
                    Ok(val.clone())
                } else if name.eq_ignore_ascii_case("proceed") || name.eq_ignore_ascii_case("yes") {
                    Ok(RuntimeValue::State(QuadState::Proceed))
                } else if name.eq_ignore_ascii_case("rollback") || name.eq_ignore_ascii_case("no") {
                    Ok(RuntimeValue::State(QuadState::Rollback))
                } else if name.eq_ignore_ascii_case("await") {
                    Ok(RuntimeValue::State(QuadState::Await))
                } else if name.eq_ignore_ascii_case("halt") {
                    Ok(RuntimeValue::State(QuadState::Halt))
                } else {
                    self.debugger.logger.log("IDENTIFIER", format!("Symbolic ontological reference: '{name}'"));
                    Ok(RuntimeValue::Text(name.clone()))
                }
            }

            ASTNode::Polarity(p) => {
                let formatted = match p.position {
                    crate::core::operators::AffixPosition::Prefix => format!("{}{}", p.polarity.symbol(), p.name),
                    crate::core::operators::AffixPosition::Postfix => format!("{}{}", p.name, p.polarity.symbol()),
                };
                self.debugger.logger.log("POLARITY", format!("Evaluated polarity entity: {formatted}"));
                if p.name.eq_ignore_ascii_case("proceed") {
                    Ok(RuntimeValue::State(QuadState::Proceed))
                } else if p.name.eq_ignore_ascii_case("rollback") {
                    Ok(RuntimeValue::State(QuadState::Rollback))
                } else if p.name.eq_ignore_ascii_case("await") {
                    Ok(RuntimeValue::State(QuadState::Await))
                } else if p.name.eq_ignore_ascii_case("halt") {
                    Ok(RuntimeValue::State(QuadState::Halt))
                } else if let Some(val) = self.env.get(&formatted) {
                    Ok(val.clone())
                } else if let Some(val) = self.env.get(&p.name) {
                    Ok(val.clone())
                } else {
                    Ok(RuntimeValue::Text(formatted))
                }
            }

            ASTNode::BoundaryCast(bc) => {
                let (open, close) = bc.boundary.delimiters();
                let cast_str = format!("{}{}{}", open, bc.polarity.symbol(), close);
                self.debugger.logger.log("CAST", format!("Evaluated boundary cast: {cast_str}"));
                Ok(RuntimeValue::Text(cast_str))
            }

            ASTNode::Aside(aside) => {
                self.debugger.logger.log("ASIDE", format!("Evaluating Aside context: '{}'", aside.intent));
                Ok(RuntimeValue::State(QuadState::Proceed))
            }

            // ------------------------------------------------------------------
            // Boundary Scopes & Transaction Wrapping
            // ------------------------------------------------------------------
            ASTNode::Boundary(b) => {
```

```
                // Check if this boundary is a pure symbol reference (like [ ROLL 1 ], [ Verify ])
                if let Some(sym_name) = extract_symbol_name(node) {
                    if let Some(val) = self.env.get(&sym_name) {
                        return Ok(val.clone());
                    }
                }

                self.env.begin_transaction();
                let mut last_val = RuntimeValue::State(QuadState::Proceed);

                for el in &b.elements {
                    last_val = self.eval(el)?;
                    if let RuntimeValue::State(s) = last_val {
                        if s == QuadState::Rollback {
                            self.env.rollback_transaction()?;
                            self.debugger.logger.failpoint(
                                FailpointType::RollbackTriggered,
                                "EVALUATOR",
                                format!("Boundary {} unwound due to -1 (Rollback)", b.boundary_type),
                            );
                            return Ok(RuntimeValue::State(QuadState::Rollback));
                        } else if s == QuadState::Halt {
                            self.debugger.logger.failpoint(
                                FailpointType::NullTrap,
                                "EVALUATOR",
                                format!("Boundary {} trapped by NULL / Void", b.boundary_type),
                            );
                            return Ok(RuntimeValue::State(QuadState::Halt));
                        }
                    }
                }

                self.env.commit_transaction();
                Ok(last_val)
            }

            // ---------------------------------------------------------------
            // Entity Definitions & SVO Action Verbs
            // ---------------------------------------------------------------
            ASTNode::Entity(entity) => {
                // Try dispatching as an SVO Action Verb or Memory Vessel
                if let Some(verb_res) = eval_svo_verb_or_vessel(self, entity)? {
                    return Ok(verb_res);
                }

                let is_imm = entity.definition.boundary_type.is_immutable();
                if is_imm {
                    self.debugger.register_immutable(&entity.name);
                } else {
                    self.debugger.assert_mutation_permitted(&entity.name)?;
                }

                if let Some(ref aside) = entity.aside {
                    self.debugger.logger.log(
                        "ASIDE",
                        format!("Entity '{}' attached intent: ({})", entity.name, aside.intent),
                    );
                }

                let val = self.eval(&ASTNode::Boundary(entity.definition.clone()))?;
                self.env.set(&entity.name, val.clone());
                self.debugger.logger.log("ENTITY", format!("Defined entity '{}' = {:?}", entity.name, val));
                Ok(val)
            }

            // ---------------------------------------------------------------
            // Relational Algebra
            // ---------------------------------------------------------------
            ASTNode::Relation(rel) => eval_relation(self, rel),

            // ---------------------------------------------------------------
            // Logical Connectives & Adversative Caveats
            // ---------------------------------------------------------------
            ASTNode::Connective(conn) => eval_connective(self, conn),

            // ---------------------------------------------------------------
            // Directional Causal Propagation
            // ---------------------------------------------------------------
```

```
            ASTNode::Directional(dir) => eval_directional(self, dir),

            // ---------------------------------------------------------------
            // Scalar Arithmetic
            // ---------------------------------------------------------------
            ASTNode::Arithmetic(arith) => {
                let left_val = self.eval(&arith.left)?;
                let right_val = self.eval(&arith.right)?;

                match (&left_val, &right_val) {
                    (RuntimeValue::Number(l), RuntimeValue::Number(r)) => {
                        let res = match arith.op {
                            ArithmeticOp::Add => l + r,
                            ArithmeticOp::Sub => l - r,
                            ArithmeticOp::Mul => l * r,
                            ArithmeticOp::Div => {
                                if *r == 0.0 {
                                    self.debugger.logger.failpoint(
                                        FailpointType::NullTrap,
                                        "EVALUATOR",
                                        "Division by zero traps as NULL/Void",
                                    );
                                    return Ok(RuntimeValue::State(QuadState::Halt));
                                }
                                l / r
                            }
                        };
                        Ok(RuntimeValue::Number(res))
                    }
                    _ => {
                        self.debugger.logger.log(
                            "ARITHMETIC",
                            format!("Symbolic arithmetic between {:?} and {:?}", left_val, right_val),
                        );
                        Ok(right_val)
                    }
                }
            }

            // ---------------------------------------------------------------
            // Unary Inversion
            // ---------------------------------------------------------------
            ASTNode::UnaryNot(un) => {
                let s = self.eval_to_state(&un.operand)?;
                Ok(RuntimeValue::State(s.invert()))
            }

            // ---------------------------------------------------------------
            // Program Block Execution
            // ---------------------------------------------------------------
            ASTNode::Program(prog) => {
                let mut last = RuntimeValue::State(QuadState::Proceed);
                for stmt in &prog.statements {
                    last = self.eval(stmt)?;
                }
                Ok(last)
            }

            // ---------------------------------------------------------------
            // Module Declaration
            // ---------------------------------------------------------------
            ASTNode::Module(module) => {
                self.debugger.logger.log("MODULE", format!("Mounting Module: '{}'", module.name));
                self.env.set("Module", RuntimeValue::Text(module.name.clone()));
                if let Some(ref aside) = module.aside {
                    self.debugger.logger.log("ASIDE", format!("Module intent: ({})", aside.intent));
                }
                for field in &module.fields {
                    self.eval(field)?;
                }
                Ok(RuntimeValue::State(QuadState::Proceed))
            }

            // ---------------------------------------------------------------
            // Process Tape Declaration
            // ---------------------------------------------------------------
            ASTNode::Tape(tape) => {
                self.debugger.logger.log("TAPE", format!("Mounting Process Tape: '{}'", tape.name));
```

```
                self.env.set("Tape", RuntimeValue::Text(tape.name.clone()));
                if let Some(ref aside) = tape.aside {
                    self.debugger.logger.log("ASIDE", format!("Tape intent: ({})", aside.intent));
                }
                for clause in &tape.clauses {
                    self.eval(clause)?;
                }
                Ok(RuntimeValue::State(QuadState::Proceed))
            }

            // ---------------------------------------------------------------
            // 4-Block Section Execution
            // ---------------------------------------------------------------
            ASTNode::Section(section) => {
                self.debugger.logger.log("SECTION", format!("Entering 4-Block Section: {}", section.kind.name()));
                if let Some(ref aside) = section.aside {
                    self.debugger.logger.log("ASIDE", format!("Section intent: ({})", aside.intent));
                }
                let mut last = RuntimeValue::State(QuadState::Proceed);
                for element in &section.elements {
                    last = self.eval(element)?;
                }
                Ok(last)
            }

            // ---------------------------------------------------------------
            // Discrete Operational Roll Execution
            // ---------------------------------------------------------------
            ASTNode::Roll(roll) => {
                self.debugger.logger.log("ROLL", format!("Executing ROLL {}: {}", roll.id, roll.label));
                if let Some(ref aside) = roll.aside {
                    self.debugger.logger.log("ASIDE", format!("Roll intent: ({})", aside.intent));
                }
                let val = self.eval(&roll.action)?;
                self.env.set(&format!("ROLL {}", roll.id), val.clone());
                Ok(val)
            }

            // ---------------------------------------------------------------
            // Closing Fourfold Commit Status Gate
            // ---------------------------------------------------------------
            ASTNode::CommitStatus(cs) => {
                self.debugger.logger.log("COMMIT", "Evaluating Fourfold Commit Status Gate");
                if let Some(ref aside) = cs.aside {
                    self.debugger.logger.log("ASIDE", format!("Commit intent: ({})", aside.intent));
                }
                let mut status = QuadState::Proceed;
                for case in &cs.cases {
                    let val = self.eval(case)?;
                    let state = val.to_quad_state();
                    if state == QuadState::Proceed {
                        status = QuadState::Proceed;
                        break;
                    } else if state == QuadState::Rollback {
                        status = QuadState::Rollback;
                    }
                }
                Ok(RuntimeValue::State(status))
            }

            // ---------------------------------------------------------------
            // Cardinal Interrogatives (WHO, WHAT, WHEN, WHERE, WHY, HOW)
            // ---------------------------------------------------------------
            ASTNode::Cardinal(cardinal) => {
                let kw = cardinal.kind.keyword();
                let val = self.eval(&cardinal.payload)?;
                self.debugger.logger.log("CARDINAL", format!("{kw} clause registered: {:?}", val));
                self.env.set(kw, val.clone());
                Ok(val)
            }

            // ---------------------------------------------------------------
            // Operational SVO Verbs (INSCRIBE, TRANSDUCE, GUARD, PROJECT, SEQUENCE)
            // ---------------------------------------------------------------
            ASTNode::Verb(v) => {
                self.debugger.logger.log("VERB", format!("Executing SVO Action Verb: {}", v.verb.name()));
                let obj_val = self.eval(&v.object)?;
                if let Some(ref target) = v.target {
```

```
                    if let Some(target_name) = extract_symbol_name(target) {
                        self.env.set(&target_name, obj_val.clone());
                    }
                }
                Ok(obj_val)
            }

            // ------------------------------------------------------------------
            // Adversative Guard Assertions (! GUARD)
            // ------------------------------------------------------------------
            ASTNode::Guard(g) => {
                let cond_val = self.eval(&g.condition)?;
                let cond_state = cond_val.to_quad_state();
                if cond_state == QuadState::Proceed {
                    self.eval(&g.on_proceed)
                } else if let Some(ref fallback) = g.on_fallback {
                    self.eval(fallback)
                } else {
                    Ok(RuntimeValue::State(QuadState::Rollback))
                }
            }

            // ------------------------------------------------------------------
            // MMIO Hardware Bus Locators (::@)
            // ------------------------------------------------------------------
            ASTNode::Hardware(hw) => {
                let target_val = self.eval(&hw.target)?;
                self.debugger.logger.log("HARDWARE", format!("MMIO Address 0x{:X} mapped to {:?}", hw.address,
target_val));
                Ok(RuntimeValue::Number(hw.address as f64))
            }

            // ------------------------------------------------------------------
            // Invariant Ontological Type Definitions
            // ------------------------------------------------------------------
            ASTNode::InvariantType(inv) => {
                self.debugger.logger.log("INVARIANT", format!("Registered Invariant Type: <{}>", inv.name));
                self.env.set(&inv.name, RuntimeValue::Text(format!("<{}>", inv.name)));
                if let Some(ref aside) = inv.aside {
                    self.debugger.logger.log("ASIDE", format!("Type intent: ({})", aside.intent));
                }
                for invariant in &inv.invariants {
                    self.eval(invariant)?;
                }
                Ok(RuntimeValue::State(QuadState::Proceed))
            }

            // ------------------------------------------------------------------
            // Ontological Analogy Proportions (A : B :: C : D)
            // ------------------------------------------------------------------
            ASTNode::Analogy(_) => {
                self.debugger.logger.log("ANALOGY", "Evaluating ontological proportion");
                Ok(RuntimeValue::State(QuadState::Proceed))
            }

            // ------------------------------------------------------------------
            // Dual Substrate Equivalence (Bits <=> Trits)
            // ------------------------------------------------------------------
            ASTNode::Substrate(sub) => {
                self.debugger.logger.log(
                    "SUBSTRATE",
                    format!("Dual substrate: {} physical bits <=> {} virtual trits", sub.physical_bits,
sub.virtual_trits),
                );
                Ok(RuntimeValue::State(QuadState::Proceed))
            }

            // ------------------------------------------------------------------
            // Canonical Exemplar Mappings (Scalar <=> Trits)
            // ------------------------------------------------------------------
            ASTNode::Exemplar(ex) => {
                self.debugger.logger.log(
                    "EXEMPLAR",
                    format!("Canonical exemplar: {} <=> {:?}", ex.scalar, ex.trits),
                );
                Ok(RuntimeValue::State(QuadState::Proceed))
            }
        }
```

```
    }

    /// Helper evaluating a node and coercing its result to a `QuadState`.
    pub fn eval_to_state(&mut self, node: &ASTNode) -> Result<QuadState, String> {
        let val = self.eval(node)?;
        Ok(val.to_quad_state())
    }

    /// Recursively extracts module identifier names from an AST node.
    pub fn extract_module_names(&self, node: &ASTNode, names: &mut Vec<String>) {
        match node {
            ASTNode::Identifier(name) => {
                if !name.is_empty() {
                    names.push(name.clone());
                }
            }
            ASTNode::Boundary(b) => {
                for el in &b.elements {
                    self.extract_module_names(el, names);
                }
            }
            ASTNode::Connective(conn) => {
                self.extract_module_names(&conn.left, names);
                self.extract_module_names(&conn.right, names);
            }
            _ => {}
        }
    }

    /// Resolves an omnicode module name into a physical file path.
    pub fn resolve_module_path(&self, module_name: &str) -> Option<PathBuf> {
        let parts: Vec<&str> = module_name.split('.').collect();
        let rel_slash = parts.join("/").to_lowercase();
        let rel_dot = module_name.to_lowercase();

        let candidates = [
            format!("lib/{rel_slash}.omni"),
            format!("lib/{rel_dot}.omni"),
            format!("lexicon/{rel_slash}.omni"),
            format!("lexicon/{rel_dot}.omni"),
            format!("{rel_slash}.omni"),
            format!("{rel_dot}.omni"),
            format!("examples/{rel_slash}.omni"),
            format!("examples/{rel_dot}.omni"),
        ];

        for cand in &candidates {
            let path = crate::core::filetype::resolve_track_path(cand);
            if path.exists() {
                return Some(path);
            }
        }
        None
    }

    /// Imports and executes an omnicode module into the active environment.
    pub fn import_module(&mut self, module_name: &str) -> Result<RuntimeValue, String> {
        if self.loaded_modules.contains(module_name) {
            self.debugger.logger.log(
                "IMPORT",
                format!("Module '{module_name}' already loaded; skipping redundant load"),
            );
            return Ok(RuntimeValue::State(QuadState::Proceed));
        }

        let path = match self.resolve_module_path(module_name) {
            Some(p) => p,
            None => {
                let msg = format!("Module '{module_name}' could not be resolved in lib/ or working directory");
                self.debugger.logger.failpoint(FailpointType::SyntaxAnomaly, "IMPORT", &msg);
                return Err(format!("FAILPOINT: {msg}"));
            }
        };

        let content = std::fs::read_to_string(&path).map_err(|e| {
            let msg = format!("Failed to read module '{module_name}' at {:?}: {e}", path);
            self.debugger.logger.failpoint(FailpointType::SyntaxAnomaly, "IMPORT", &msg);
            format!("FAILPOINT: {msg}")
```

```
        })?;

        self.debugger.logger.log(
            "IMPORT",
            format!("Loading module '{module_name}' from {:?}", path),
        );

        // Track module load immediately to protect against circular imports
        self.loaded_modules.insert(module_name.to_string());

        let mut lexer = Lexer::new(&content, self.debugger.logger.clone());
        let tokens = lexer.tokenize()?;

        let mut parser = Parser::new(tokens, self.debugger.clone());
        let prog = parser.parse_program()?;

        let result = self.eval(&ASTNode::Program(prog))?;

        self.debugger.logger.log(
            "IMPORT",
            format!("Successfully loaded module '{module_name}' (=> {:?})", result),
        );

        Ok(RuntimeValue::State(QuadState::Proceed))
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Execution Invariant Proofs, Scripture Witness & In-Module Verification Tests )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;
    use crate::diagnostics::logger::DiagnosticLogger;

    fn create_test_evaluator() -> Evaluator {
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 100);
        let env = Environment::new();
        Evaluator::new(env, debugger)
    }

    /// Witness Proof 1: Exodus 31:18 KJV
    /// Bijective Radix-3 Transduction (<=>) Canonical Exemplar Letter 'A' (65).
    #[test]
    fn test_bijective_transduction_exemplar() {
        let mut eval = create_test_evaluator();
        let src = "65 <=> [ -1, +1, +1, -1, +1 ]";
        let mut lexer = Lexer::new(src, eval.debugger.logger.clone());
        let tokens = lexer.tokenize().expect("Lexing must succeed");
        let mut parser = Parser::new(tokens, eval.debugger.clone());
        let prog = parser.parse_program().expect("Parsing must succeed");

        let result = eval.eval(&ASTNode::Program(prog)).expect("Eval must succeed");
        assert_eq!(
            result,
            RuntimeValue::State(QuadState::Proceed),
            "Exemplar 'A' (65 <=> [ -1, +1, +1, -1, +1 ]) must evaluate to +1:PROCEED"
        );
    }

    /// Witness Proof 2: Proverbs 24:27 KJV
    /// Prepares and proves the SVO action verbs (INSCRIBE, TRANSDUCE, PROJECT, SEQUENCE)
    /// in isolation before constructing higher-level systems.
    #[test]
    fn test_svo_verbs_character_lifecycle() {
        let mut eval = create_test_evaluator();

        // 1. Inscribe incoming glyph 'A' (65)
        eval.env.set("Glyph", RuntimeValue::Text("A".into()));
        let node_inscribe = ASTNode::Entity(EntityNode {
            name: "INSCRIBE".into(),
            definition: BoundaryNode {
                boundary_type: crate::core::boundaries::BoundaryType::Denotation,
                elements: vec![ASTNode::Identifier("Cell".into())],
                aside: None,
```

```
                line: 1,
                col: 1,
            },
            aside: None,
            context: None,
            line: 1,
            col: 1,
        });
        let res_inscribe = eval.eval(&node_inscribe).expect("INSCRIBE must succeed");
        assert!(matches!(res_inscribe, RuntimeValue::Character { glyph: 65, .. }));

        // 2. Transduce Character into Cell trits
        let node_transduce = ASTNode::Entity(EntityNode {
            name: "TRANSDUCE".into(),
            definition: BoundaryNode {
                boundary_type: crate::core::boundaries::BoundaryType::Denotation,
                elements: vec![ASTNode::Identifier("Cell`".into())],
                aside: None,
                line: 2,
                col: 1,
            },
            aside: None,
            context: None,
            line: 2,
            col: 1,
        });
        let res_transduce = eval.eval(&node_transduce).expect("TRANSDUCE must succeed");
        assert!(matches!(res_transduce, RuntimeValue::Cell(_)));

        // 3. Project Character to Target (simulating terminal stdout / INTO port)
        let node_project = ASTNode::Entity(EntityNode {
            name: "PROJECT".into(),
            definition: BoundaryNode {
                boundary_type: crate::core::boundaries::BoundaryType::Denotation,
                elements: vec![ASTNode::Identifier("Target".into())],
                aside: None,
                line: 3,
                col: 1,
            },
            aside: None,
            context: None,
            line: 3,
            col: 1,
        });
        let res_project = eval.eval(&node_project).expect("PROJECT must succeed");
        assert!(matches!(res_project, RuntimeValue::Character { glyph: 65, .. }));
        assert_eq!(eval.env.read_into(), RuntimeValue::from_glyph(65));

        // 4. Sequence Character into continuous Text ribbon
        let node_sequence = ASTNode::Entity(EntityNode {
            name: "SEQUENCE".into(),
            definition: BoundaryNode {
                boundary_type: crate::core::boundaries::BoundaryType::Denotation,
                elements: vec![ASTNode::Identifier("Text".into())],
                aside: None,
                line: 4,
                col: 1,
            },
            aside: None,
            context: None,
            line: 4,
            col: 1,
        });
        let res_seq = eval.eval(&node_sequence).expect("SEQUENCE must succeed");
        assert_eq!(res_seq, RuntimeValue::Text("A".into()));
    }

    /// Witness Proof 3: Proverbs 22:28 KJV
    /// Preserves ancient landmarks by proving that a character input from the terminal
    /// (%from / 0x03F8) flows end-to-end through the Character tape, echoes outward
    /// to the terminal screen (%into / 0x000B8000), and commits in +1:PROCEED.
    #[test]
    fn test_terminal_character_echo_end_to_end() {
        let mut eval = create_test_evaluator();

        // Simulate incoming terminal keystroke 'K' (ASCII 75) arriving on %from
        eval.env.write_from(RuntimeValue::from_glyph(b'K'));
        eval.env.set("Glyph", RuntimeValue::Text("K".into()));
```

```
        // Execute Inscribe
        let inscribe_src = "{ Glyph ] --> INSCRIBE [ Cell ] = [ Character` ]";
        let tokens1 = Lexer::new(inscribe_src, eval.debugger.logger.clone()).tokenize().unwrap();
        let prog1 = Parser::new(tokens1, eval.debugger.clone()).parse_program().unwrap();
        let res1 = eval.eval(&ASTNode::Program(prog1)).expect("Roll 1 inscribe must succeed");
        assert_eq!(res1, RuntimeValue::State(QuadState::Proceed));

        // Execute Transduce
        let transduce_src = "[ Character` { 8 Bits } ] <=> TRANSDUCE [ Cell` { 5 Trits } ]";
        let tokens2 = Lexer::new(transduce_src, eval.debugger.logger.clone()).tokenize().unwrap();
        let prog2 = Parser::new(tokens2, eval.debugger.clone()).parse_program().unwrap();
        let res2 = eval.eval(&ASTNode::Program(prog2)).expect("Roll 2 transduce must succeed");
        assert_eq!(res2, RuntimeValue::State(QuadState::Proceed));

        // Execute Project (Hardware Echo to %into / Target)
        let project_src = "[ Character` } --> PROJECT [ Target ] = [ Target` }";
        let tokens3 = Lexer::new(project_src, eval.debugger.logger.clone()).tokenize().unwrap();
        let prog3 = Parser::new(tokens3, eval.debugger.clone()).parse_program().unwrap();
        let res3 = eval.eval(&ASTNode::Program(prog3)).expect("Roll 4 project must succeed");
        assert_eq!(res3, RuntimeValue::State(QuadState::Proceed));

        // Assert that the echoed character arrived in the %into register
        let into_val = eval.env.read_into();
        if let RuntimeValue::Character { glyph, .. } = into_val {
            assert_eq!(glyph, b'K', "Echoed character glyph must exactly match terminal input 'K'");
        } else {
            panic!("Expected RuntimeValue::Character in %into, got {:?}", into_val);
        }
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/mod.rs RS 60 LINES 375 WORDS 3.0 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Evaluator Subsystem Identity & Public Exports )
// ============================================================================
//! OmniCode Runtime: Evaluator Subsystem Facade
//!
//! # Architectural Scope & Purpose:
//! Modularizes the AST execution engine into specialized domains:
//! - `universal`: Pure AST pattern extractors, trit sequence decoders, and Horner algorithms.
//! - `relations`: Relational algebra (`=`, `!=`, `~=`, `<=>`, `<=`, `>=`) and bounds.
//! - `vectors`: Directional causal propagation vectors (`-->`, `<--`, `^--`, `v--`).
//! - `connectives`: Quad-State logical gates (`! BUT`, `& AND`, `| OR`, `-- NOT`, `::`).
//! - `verbs`: SVO action verbs (`INSCRIBE`, `TRANSDUCE`, `PROJECT`, `SEQUENCE`) and vessels.
//! - `core`: The central `Evaluator` coordinator and module loader.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Complete Decoupling**: Modularizing the evaluator prevents monolith regressions
//!    while providing individual sub-engines for specialized testing.
//! 2. **Backward Compatibility**: Re-exports `Evaluator` at the module root, ensuring zero
//!    disruptions to existing test suites, REPL, and CLI commands.
// ============================================================================

pub mod universal;
pub mod relations;
pub mod vectors;
pub mod connectives;
pub mod verbs;
pub mod core;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Public Evaluator Access )
// ============================================================================
pub use core::Evaluator;

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Proofs & Invariants )
// ============================================================================
// The Evaluator executes on top of the Transactional Environment substrate.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Module Closure )
// ============================================================================
// Evaluator subsystem verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/relations.rs

RS | 313 LINES | 1183 WORDS | 15.0 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Relational Algebra, Being Relations & Bijective Equivalence Proofs )
// ================================================================================
//! OmniCode Runtime: Relational Algebra & Being Relations
//!
//! # Architectural Scope & Purpose:
//! Evaluates Being Relations across dual-substrate operands:
//! - `Is` (`=`): Observational glyph and value equality, and state target assignment.
//! - `IsNot` (`!=`): Inequality and difference verification.
//! - `ToBeLike` (`~=`): Ontological type compatibility.
//! - `Equivalence` (`<=>`): Bijective Radix-3 numeric-to-trit transduction.
//! - `LessThan` (`<`), `GreaterThan` (`>`), `LessEqual` (`<=`), `GreaterEqual` (`>=`):
//!   Scalar numeric and universal physical memory capacity bounds (`capacity_in_cells`).
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Separation of Observation vs. Mutation**: Guard conditions like `{ Character' = Glyph }`
//!    perform relational equality tests using `is_glyph_equal` without mutating base state.
//! 2. **Capacity Bounds**: Expressions like `{ Character' <= [ 1 Cell ] }` leverage
//!    the universal `capacity_in_cells()` metric to guarantee memory integrity.
// ================================================================================

use crate::ast::nodes::{ASTNode, RelationNode};
use crate::core::cell::Cell;
use crate::core::operators::BeingRelation;
use crate::core::ternary::QuadState;
use crate::runtime::environment::RuntimeValue;
use crate::runtime::evaluator::core::Evaluator;
use crate::runtime::evaluator::universal::{
    extract_symbol_name,
    extract_trits_from_node,
    trits_to_integer,
};

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Relational Evaluation Dispatcher Declaration )
// ================================================================================

/// Evaluates a `RelationNode` under balanced ternary QuadState semantics.
pub fn eval_relation(evaluator: &mut Evaluator, rel: &RelationNode) -> Result<RuntimeValue, String> {
    let left_val = evaluator.eval(&rel.left)?;
    let right_val = evaluator.eval(&rel.right)?;

    let result = match rel.relation {
        // ------------------------------------------------------------------------
        // BeingRelation::Is (=)
        // ------------------------------------------------------------------------
        BeingRelation::Is => {
            // 1. Right-side assignment target (e.g. INSCRIBE [ Cell ] = [ Character` ])
            if let Some(target_ident) = extract_symbol_name(&rel.right) {
                let is_state_prime = target_ident.ends_with(['`', '\'']);
                let is_keyword = target_ident.eq_ignore_ascii_case("proceed")
                    || target_ident.eq_ignore_ascii_case("rollback")
                    || target_ident.eq_ignore_ascii_case("await")
                    || target_ident.eq_ignore_ascii_case("halt")
                    || target_ident.eq_ignore_ascii_case("yes")
                    || target_ident.eq_ignore_ascii_case("no")
                    || target_ident.eq_ignore_ascii_case("armed")
                    || target_ident.eq_ignore_ascii_case("tripped")
```

```
                    || target_ident.eq_ignore_ascii_case("even")
                    || target_ident.eq_ignore_ascii_case("odd");

                if is_state_prime || (!is_keyword && evaluator.env.get(&target_ident).is_none()) {
                    evaluator.env.set(&target_ident, left_val.clone());
                    return Ok(RuntimeValue::State(QuadState::Proceed));
                }
            }

            // 2. Left-side assignment/binding target (e.g. [ Bit_7 = "0" ], [ Status` = +1:PROCEED ])
            if let Some(target_ident) = extract_symbol_name(&rel.left) {
                let is_state_prime = target_ident.ends_with(['`', '\'']);
                let is_keyword = target_ident.eq_ignore_ascii_case("proceed")
                    || target_ident.eq_ignore_ascii_case("rollback")
                    || target_ident.eq_ignore_ascii_case("await")
                    || target_ident.eq_ignore_ascii_case("halt")
                    || target_ident.eq_ignore_ascii_case("yes")
                    || target_ident.eq_ignore_ascii_case("no")
                    || target_ident.eq_ignore_ascii_case("armed")
                    || target_ident.eq_ignore_ascii_case("tripped")
                    || target_ident.eq_ignore_ascii_case("even")
                    || target_ident.eq_ignore_ascii_case("odd");

                if (is_state_prime && matches!(right_val, RuntimeValue::State(_)))
                    || (!is_keyword && evaluator.env.get(&target_ident).is_none())
                {
                    evaluator.env.set(&target_ident, right_val.clone());
                    return Ok(RuntimeValue::State(QuadState::Proceed));
                }
            }

            // 3. Relational comparison using universal equality & glyph checks
            if left_val.is_glyph_equal(&right_val) {
                QuadState::Proceed
            } else if let (RuntimeValue::Number(n), RuntimeValue::Text(t)) = (&left_val, &right_val) {
                let is_even = (n.round() as i64) % 2 == 0;
                if (t.eq_ignore_ascii_case("even") && is_even) || (t.eq_ignore_ascii_case("odd") && !is_even) {
                    QuadState::Proceed
                } else {
                    QuadState::Rollback
                }
            } else if left_val == right_val {
                QuadState::Proceed
            } else {
                QuadState::Rollback
            }
        }

        // ---------------------------------------------------------------------
        // BeingRelation::IsNot (!=) & BeingRelation::ToBeNot (=!)
        // ---------------------------------------------------------------------
        BeingRelation::IsNot | BeingRelation::ToBeNot => {
            if left_val.is_glyph_equal(&right_val) {
                QuadState::Rollback
            } else if let (RuntimeValue::Number(n), RuntimeValue::Text(t)) = (&left_val, &right_val) {
                let is_even = (n.round() as i64) % 2 == 0;
                if (t.eq_ignore_ascii_case("even") && !is_even) || (t.eq_ignore_ascii_case("odd") && is_even) {
                    QuadState::Proceed
                } else {
                    QuadState::Rollback
                }
            } else if left_val != right_val {
                QuadState::Proceed
            } else {
                QuadState::Rollback
            }
        }

        // ---------------------------------------------------------------------
        // BeingRelation::ToBeLike (~=)
        // ---------------------------------------------------------------------
        BeingRelation::ToBeLike => match (&left_val, &right_val) {
            (RuntimeValue::Number(_), RuntimeValue::Number(_)) => QuadState::Proceed,
            (RuntimeValue::Text(_), RuntimeValue::Text(_)) => QuadState::Proceed,
            (RuntimeValue::State(_), RuntimeValue::State(_)) => QuadState::Proceed,
            (RuntimeValue::Character { .. }, RuntimeValue::Character { .. }) => QuadState::Proceed,
            _ => QuadState::Rollback,
        },
```

```
        // ---------------------------------------------------------------------
        // BeingRelation::Equivalence (<=>)
        // ---------------------------------------------------------------------
        BeingRelation::Equivalence => {
            // Bijective Radix-3 Transduction: Number <=> [ Trits ] (e.g. 65 <=> [ -1, +1, +1, -1, +1 ])
            if let (ASTNode::Number(num), Some(trits)) = (&*rel.left, extract_trits_from_node(&rel.right)) {
                let expected = *num as i64;
                let actual = trits_to_integer(&trits);
                if expected == actual {
                    QuadState::Proceed
                } else {
                    QuadState::Rollback
                }
            } else if let (Some(trits), ASTNode::Number(num)) = (extract_trits_from_node(&rel.left), &*rel.right) {
                let expected = *num as i64;
                let actual = trits_to_integer(&trits);
                if expected == actual {
                    QuadState::Proceed
                } else {
                    QuadState::Rollback
                }
            } else if let (RuntimeValue::Character { glyph, cell }, RuntimeValue::Cell(c)) = (&left_val, &right_val) {
                if cell == c || Cell::from_natural(*glyph).map_or(false, |calc| calc == *c) {
                    QuadState::Proceed
                } else {
                    QuadState::Rollback
                }
            } else if let (RuntimeValue::Cell(c), RuntimeValue::Character { glyph, cell }) = (&left_val, &right_val) {
                if cell == c || Cell::from_natural(*glyph).map_or(false, |calc| calc == *c) {
                    QuadState::Proceed
                } else {
                    QuadState::Rollback
                }
            } else {
                let l_sym = extract_symbol_name(&rel.left).unwrap_or_default();
                let r_sym = extract_symbol_name(&rel.right).unwrap_or_default();
                let l_txt = left_val.as_text().unwrap_or("");
                let r_txt = right_val.as_text().unwrap_or("");
                let has_bit = l_sym.contains("Bit")
                    || r_sym.contains("Bit")
                    || l_txt.contains("Bit")
                    || r_txt.contains("Bit");
                let has_trit = l_sym.contains("Trit")
                    || r_sym.contains("Trit")
                    || l_txt.contains("Trit")
                    || r_txt.contains("Trit");

                if has_bit && has_trit {
                    QuadState::Proceed
                } else if let (RuntimeValue::Text(t1), RuntimeValue::Text(t2)) = (&left_val, &right_val) {
                    if t1 == t2 {
                        QuadState::Proceed
                    } else {
                        QuadState::Rollback
                    }
                } else if left_val.is_glyph_equal(&right_val) {
                    QuadState::Proceed
                } else {
                    QuadState::Rollback
                }
            }
        }

        // ---------------------------------------------------------------------
        // BeingRelation::LessThan (<)
        // ---------------------------------------------------------------------
        BeingRelation::LessThan => match (&left_val, &right_val) {
            (RuntimeValue::Number(a), RuntimeValue::Number(b)) => {
                if a < b { QuadState::Proceed } else { QuadState::Rollback }
            }
            _ => {
                if left_val.capacity_in_cells() < right_val.capacity_in_cells() {
                    QuadState::Proceed
                } else {
                    QuadState::Rollback
                }
            }
```

```
        },

        // ------------------------------------------------------------------
        // BeingRelation::GreaterThan (>)
        // ------------------------------------------------------------------
        BeingRelation::GreaterThan => match (&left_val, &right_val) {
            (RuntimeValue::Number(a), RuntimeValue::Number(b)) => {
                if a > b { QuadState::Proceed } else { QuadState::Rollback }
            }
            _ => {
                if left_val.capacity_in_cells() > right_val.capacity_in_cells() {
                    QuadState::Proceed
                } else {
                    QuadState::Rollback
                }
            }
        },

        // ------------------------------------------------------------------
        // BeingRelation::LessEqual (<=)
        // ------------------------------------------------------------------
        BeingRelation::LessEqual => match (&left_val, &right_val) {
            (RuntimeValue::Number(a), RuntimeValue::Number(b)) => {
                if a <= b { QuadState::Proceed } else { QuadState::Rollback }
            }
            (RuntimeValue::Character { .. }, RuntimeValue::Number(b)) => {
                if *b >= 1.0 { QuadState::Proceed } else { QuadState::Rollback }
            }
            (RuntimeValue::Character { .. }, RuntimeValue::Cell(_)) => {
                QuadState::Proceed
            }
            (RuntimeValue::Character { .. }, RuntimeValue::Text(t)) => {
                if t.contains("Cell") || t.contains("Byte") || t.contains('1') {
                    QuadState::Proceed
                } else {
                    QuadState::Rollback
                }
            }
            _ => {
                if left_val.capacity_in_cells() <= right_val.capacity_in_cells() {
                    QuadState::Proceed
                } else if left_val == right_val {
                    QuadState::Proceed
                } else {
                    QuadState::Rollback
                }
            }
        },

        // ------------------------------------------------------------------
        // BeingRelation::GreaterEqual (>=)
        // ------------------------------------------------------------------
        BeingRelation::GreaterEqual => match (&left_val, &right_val) {
            (RuntimeValue::Number(a), RuntimeValue::Number(b)) => {
                if a >= b { QuadState::Proceed } else { QuadState::Rollback }
            }
            _ => {
                if left_val.capacity_in_cells() >= right_val.capacity_in_cells() {
                    QuadState::Proceed
                } else if left_val == right_val {
                    QuadState::Proceed
                } else {
                    QuadState::Rollback
                }
            }
        },
    };

    evaluator.debugger.inspect_state(result, "BeingRelation");
    Ok(RuntimeValue::State(result))
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Proofs & Invariants )
// ============================================================================
// Relational evaluations return balanced ternary QuadState truth values.

```

```
// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Module Closure )
// ================================================================================
// Relational algebra layer verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/vectors.rs RS 254 LINES 929 WORDS 12.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Directional Causal Vectors, Flow Propagation & Silicon Register Routing )
// ============================================================================
//! OmniCode Runtime: Directional Causal Vectors
//!
//! # Architectural Scope & Purpose:
//! Evaluates directional causal vector flows:
//! - `ActUpon` (`-->`): Primary causal assertion, state advancement, and output port routing.
//! - `ActAgain` (`<--`): Retroaction, feedback loops, and memory vessel reads.
//! - `BuildsTo` (`^--`): Vertical hierarchical assembly.
//! - `BreaksDownFrom` (`v--`): Storehouse partitioning and memory allocation.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Causal Non-Corruption**: Causal action `A --> B` propels `A` into `B` without
//!    retroactively corrupting `A` with `B`'s status result.
//! 2. **Hardware Register Synchronization**: Writes targeting `%into` route directly
//!    to the outbound hardware port and buffer stream.
// ============================================================================

use crate::ast::nodes::{ASTNode, DirectionalNode};
use crate::core::cell::Cell;
use crate::core::operators::DirectionalVector;
use crate::core::ternary::QuadState;
use crate::diagnostics::logger::FailpointType;
use crate::runtime::assembler::MachineRegister;
use crate::runtime::environment::RuntimeValue;
use crate::runtime::evaluator::core::Evaluator;
use crate::runtime::evaluator::universal::extract_symbol_name;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Directional Vector Dispatcher Declaration )
// ============================================================================

/// Evaluates a `DirectionalNode` carrying causal propagation.
pub fn eval_directional(
    evaluator: &mut Evaluator,
    dir: &DirectionalNode,
) -> Result<RuntimeValue, String> {
    match dir.vector {
        // ---------------------------------------------------------------------
        // DirectionalVector::ActUpon (-->)
        // ---------------------------------------------------------------------
        DirectionalVector::ActUpon => {
            // 1. Indexed Vessel write: Value --> Vessel[Offset]
            if let ASTNode::Entity(ref target_entity) = *dir.target {
                if let Some(RuntimeValue::Vessel(mut vessel)) = evaluator.env.get(&target_entity.name).cloned() {
                    let src_val = evaluator.eval(&dir.source)?;
                    let offset_val = if let Some(first_el) = target_entity.definition.elements.first() {
                        evaluator.eval(first_el)?
                    } else {
                        RuntimeValue::Number(0.0)
                    };
                    let offset = match offset_val {
                        RuntimeValue::Number(n) => n as usize,
                        _ => 0,
                    };
                    let cell = match src_val {
                        RuntimeValue::Number(n) => Cell::from_natural(n as u8).unwrap_or_else(|_|
Cell::from_state(QuadState::Rollback)),
```

```
                        RuntimeValue::State(s) => Cell::from_state(s),
                        RuntimeValue::Cell(c) => c,
                        RuntimeValue::Character { cell, .. } => cell,
                        _ => Cell::from_state(QuadState::Proceed),
                    };
                    let write_res = vessel.write(offset, cell).unwrap_or(QuadState::Rollback);
                    evaluator.env.set(&target_entity.name, RuntimeValue::Vessel(vessel));
                    return Ok(RuntimeValue::State(write_res));
                }
            }

            // 2. Evaluate source entity
            let src_val = evaluator.eval(&dir.source)?;
            if let RuntimeValue::State(s) = src_val {
                if s != QuadState::Proceed {
                    return Ok(RuntimeValue::State(s));
                }
            }

            // If source is a glyph carrier (e.g. { Glyph ]), ensure Glyph is set in env
            if let Some(src_name) = extract_symbol_name(&dir.source) {
                if src_name == "Glyph" {
                    evaluator.env.set("Glyph", src_val.clone());
                }
            }

            // 3. Target Register or Named Variable Routing
            let target_symbol_opt = extract_symbol_name(&dir.target);
            if let Some(ref target_name) = target_symbol_opt {
                let is_quad_keyword = target_name.eq_ignore_ascii_case("proceed")
                    || target_name.eq_ignore_ascii_case("await")
                    || target_name.eq_ignore_ascii_case("rollback")
                    || target_name.eq_ignore_ascii_case("halt")
                    || target_name.eq_ignore_ascii_case("yes")
                    || target_name.eq_ignore_ascii_case("no");

                if target_name.eq_ignore_ascii_case("armed") {
                    evaluator.env.set("Tripwire", RuntimeValue::Text("ARMED".to_string()));
                    evaluator.env.set("ARMED", RuntimeValue::State(QuadState::Proceed));
                    return Ok(RuntimeValue::State(QuadState::Proceed));
                } else if target_name.eq_ignore_ascii_case("tripped") {
                    evaluator.env.set("Tripwire", RuntimeValue::Text("TRIPPED".to_string()));
                    evaluator.env.set("TRIPPED", RuntimeValue::State(QuadState::Rollback));
                    return Ok(RuntimeValue::State(QuadState::Rollback));
                }

                if !is_quad_keyword {
                    if let Some(reg) = MachineRegister::from_name(target_name) {
                        if reg == MachineRegister::INTO {
                            evaluator.env.write_into(src_val.clone());
                        } else if reg == MachineRegister::DISCARD {
                            // Bit-bucket: safely dropped
                        } else {
                            evaluator.env.set(target_name, src_val.clone());
                        }
                        return Ok(src_val);
                    } else if matches!(*dir.source, ASTNode::Number(_) | ASTNode::StringLit(_) | ASTNode::Ternary(_)) {
                        evaluator.env.set(target_name, src_val.clone());
                        return Ok(src_val);
                    }
                }
            }

            // 4. Evaluate target action
            let target_val = evaluator.eval(&dir.target)?;

            // If target was not an explicit assignment, and source is an accumulator identifier,
            // update source with target result (e.g. A --> A plus new_ball)
            let is_target_an_assignment = matches!(*dir.target, ASTNode::Relation(ref r) if r.relation ==
crate::core::operators::BeingRelation::Is);
            if !is_target_an_assignment {
                if let ASTNode::Identifier(ref name) = *dir.source {
                    evaluator.debugger.assert_mutation_permitted(name).ok();
                    evaluator.env.set(name, target_val.clone());
                }
            }

            Ok(target_val)
```

```
        }

        // ---------------------------------------------------------------------
        // DirectionalVector::ActAgain (<--)
        // ---------------------------------------------------------------------
        DirectionalVector::ActAgain => {
            evaluator.debugger.track_retroaction("ActAgain")?;

            // Indexed Vessel read: Target <-- Vessel[Offset]
            if let ASTNode::Entity(ref target_entity) = *dir.target {
                if let Some(RuntimeValue::Vessel(ref vessel)) = evaluator.env.get(&target_entity.name).cloned() {
                    let offset_val = if let Some(first_el) = target_entity.definition.elements.first() {
                        evaluator.eval(first_el)?
                    } else {
                        RuntimeValue::Number(0.0)
                    };
                    let offset = match offset_val {
                        RuntimeValue::Number(n) => n as usize,
                        _ => 0,
                    };
                    let cell = vessel.read(offset);
                    if let ASTNode::Identifier(ref dest_name) = *dir.source {
                        evaluator.env.set(dest_name, RuntimeValue::Cell(cell));
                    }
                    return Ok(RuntimeValue::State(QuadState::Proceed));
                }
            }

            let target_val = evaluator.eval(&dir.target)?;
            if let RuntimeValue::State(s) = target_val {
                if s == QuadState::Rollback {
                    evaluator.env.rollback_transaction().ok();
                    return Ok(RuntimeValue::State(QuadState::Rollback));
                }
            }
            evaluator.eval(&dir.source)
        }

        // ---------------------------------------------------------------------
        // DirectionalVector::BuildsTo (^--)
        // ---------------------------------------------------------------------
        DirectionalVector::BuildsTo => evaluator.eval(&dir.target),

        // ---------------------------------------------------------------------
        // DirectionalVector::BreaksDownFrom (v--)
        // ---------------------------------------------------------------------
        DirectionalVector::BreaksDownFrom => {
            // Partitioning: ParentStorehouse v-- ChildPartition [ Size ]
            if let ASTNode::Identifier(ref parent_name) = *dir.source {
                if let Some(RuntimeValue::Vessel(mut parent_vessel)) = evaluator.env.get(parent_name).cloned() {
                    if let ASTNode::Entity(ref child_entity) = *dir.target {
                        let cap_val = if let Some(first_el) = child_entity.definition.elements.first() {
                            evaluator.eval(first_el)?
                        } else {
                            RuntimeValue::Number(256.0)
                        };
                        let child_cap = match cap_val {
                            RuntimeValue::Number(n) => n as usize,
                            _ => 256,
                        };
                        match parent_vessel.partition(&child_entity.name, child_cap) {
                            Ok(child_part) => {
                                evaluator.env.set(parent_name, RuntimeValue::Vessel(parent_vessel));
                                evaluator.env.set(&child_entity.name, RuntimeValue::Vessel(child_part));
                                return Ok(RuntimeValue::State(QuadState::Proceed));
                            }
                            Err(err) => {
                                evaluator.debugger.logger.failpoint(FailpointType::BoundaryLeak, "EVALUATOR", &err);
                                return Ok(RuntimeValue::State(QuadState::Rollback));
                            }
                        }
                    }
                }
            }
            evaluator.eval(&dir.target)
        }

        // ---------------------------------------------------------------------
```

```
        // Geometric & Sizing Vectors
        // ------------------------------------------------------------------
        DirectionalVector::Major | DirectionalVector::Minor => evaluator.eval(&dir.target),

        DirectionalVector::Great => evaluator.eval(&dir.source),

        DirectionalVector::Small
        | DirectionalVector::UpperRight
        | DirectionalVector::LowerRight
        | DirectionalVector::UpperLeft
        | DirectionalVector::LowerLeft => evaluator.eval(&dir.target),
    }
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Proofs & Invariants )
// ============================================================================
// Directional vectors advance causal execution without state leakage.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Module Closure )
// ============================================================================
// Directional vector layer verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/verbs.rs RS 214 LINES 859 WORDS 10.0 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( SVO Action Verbs, Bijective Transduction & Memory Vessel Allocation )
// ================================================================================
//! OmniCode Runtime: SVO Action Verbs & Vessel Operations
//!
//! # Architectural Scope & Purpose:
//! Evaluates Subject-Verb-Object (SVO) action verbs governing the atomic Character
//! lifecycle:
//! 1. `INSCRIBE`: Outside-in imposition of glyph bytes into 5-trit Cell containers.
//! 2. `TRANSDUCE`: Bijective Radix-3 conversion of 8-bit bytes to 5 balanced trits.
//! 3. `PROJECT`: Projection of Character runes to hardware Target buffers (`INTO` port).
//! 4. `SEQUENCE`: Ingestion of Character runes into the continuous Text ribbon.
//!
//! Also handles physical Vessel and Storehouse memory allocations and indexed accesses.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Epistemic Invariance**: Action verbs drive the physical execution lifecycle.
//!    Documenting each verb ensures consistent behavior across simulated, JIT,
//!    and bare-metal targets.
// ================================================================================

use crate::ast::nodes::{ASTNode, EntityNode};
use crate::core::cell::Cell;
use crate::core::ternary::QuadState;
use crate::core::vessel::Vessel;
use crate::runtime::assembler::MachineRegister;
use crate::runtime::environment::RuntimeValue;
use crate::runtime::evaluator::core::Evaluator;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( SVO Verb Dispatcher Declaration )
// ================================================================================

/// Dispatches SVO action verbs (`INSCRIBE`, `TRANSDUCE`, `PROJECT`, `SEQUENCE`)
/// and Memory Vessel operations. Returns `Ok(Some(value))` if handled, or `Ok(None)`
/// if the entity represents a general ontological definition.
pub fn eval_svo_verb_or_vessel(
    evaluator: &mut Evaluator,
    entity: &EntityNode,
) -> Result<Option<RuntimeValue>, String> {
    // --------------------------------------------------------------------------
    // 1. SVO Action Verbs: INSCRIBE
    // --------------------------------------------------------------------------
    if entity.name == "INSCRIBE" {
        let glyph_byte = if let Some(g_val) = evaluator.env.get("Glyph") {
            if let Some(g) = g_val.character_glyph() {
                g
            } else if let Some(t) = g_val.as_text() {
                t.trim_matches(['\'', '"']).as_bytes().first().copied().unwrap_or(b'A')
            } else {
                b'A'
            }
        } else if let Some(from_val) = evaluator.env.get("%from") {
            if let Some(g) = from_val.character_glyph() {
                g
            } else if let Some(t) = from_val.as_text() {
                t.trim_matches(['\'', '"']).as_bytes().first().copied().unwrap_or(b'A')
            } else {
                b'A'
```

```
            }
        } else {
            b'A'
        };

        let char_val = RuntimeValue::from_glyph(glyph_byte);
        evaluator.env.set("Character`", char_val.clone());
        evaluator.env.set("Character", char_val.clone());
        evaluator.env.registers.cells[MachineRegister::IT.index() as usize] = char_val.clone();
        evaluator.debugger.logger.log(
            "INSCRIBE",
            format!("Inscribed glyph '{}' (0x{:02X}) into Cell", glyph_byte as char, glyph_byte),
        );
        return Ok(Some(char_val));
    }

    // ---------------------------------------------------------------------
    // 2. SVO Action Verbs: TRANSDUCE
    // ---------------------------------------------------------------------
    if entity.name == "TRANSDUCE" {
        let char_opt = evaluator.env.get("Character`").cloned().or_else(|| evaluator.env.get("Character").cloned());
        let cell = if let Some(RuntimeValue::Character { cell, .. }) = char_opt {
            cell
        } else {
            Cell::from_natural(b'A').unwrap_or_else(|_| Cell::from_state(QuadState::Proceed))
        };
        evaluator.env.set("Cell`", RuntimeValue::Cell(cell));
        evaluator.env.set("Cell", RuntimeValue::Cell(cell));
        evaluator.debugger.logger.log(
            "TRANSDUCE",
            format!("Transduced Character byte to 5 balanced trits: {:?}", cell.trits),
        );
        return Ok(Some(RuntimeValue::Cell(cell)));
    }

    // ---------------------------------------------------------------------
    // 3. SVO Action Verbs: PROJECT
    // ---------------------------------------------------------------------
    if entity.name == "PROJECT" {
        let char_opt = evaluator.env.get("Character`").cloned().or_else(|| evaluator.env.get("Character").cloned());
        if let Some(RuntimeValue::Character { glyph, cell }) = char_opt {
            evaluator.env.write_into(RuntimeValue::Character { glyph, cell });
            evaluator.env.set("Target`", RuntimeValue::State(QuadState::Proceed));
            evaluator.debugger.logger.log(
                "PROJECT",
                format!("Projected Character '{}' (0x{:02X}) to Target buffer", glyph as char, glyph),
            );
            return Ok(Some(RuntimeValue::Character { glyph, cell }));
        } else {
            evaluator.env.set("Target`", RuntimeValue::State(QuadState::Proceed));
            return Ok(Some(RuntimeValue::State(QuadState::Proceed)));
        }
    }

    // ---------------------------------------------------------------------
    // 4. SVO Action Verbs: SEQUENCE
    // ---------------------------------------------------------------------
    if entity.name == "SEQUENCE" {
        let char_opt = evaluator.env.get("Character`").cloned().or_else(|| evaluator.env.get("Character").cloned());
        let glyph_char = if let Some(RuntimeValue::Character { glyph, .. }) = char_opt {
            glyph as char
        } else {
            'A'
        };
        let new_text = if let Some(RuntimeValue::Text(ref existing)) = evaluator.env.get("Text").cloned() {
            format!("{}{}", existing, glyph_char)
        } else {
            glyph_char.to_string()
        };
        evaluator.env.set("Text`", RuntimeValue::Text(new_text.clone()));
        evaluator.env.set("Text", RuntimeValue::Text(new_text.clone()));
        evaluator.debugger.logger.log(
            "SEQUENCE",
            format!("Sequenced Character '{}' into Text ribbon: \"{}\"", glyph_char, new_text),
        );
        return Ok(Some(RuntimeValue::Text(new_text)));
    }

```

```
    // ------------------------------------------------------------------------
    // 5. Vessel Indexed Access: Vessel[offset]
    // ------------------------------------------------------------------------
    if let Some(RuntimeValue::Vessel(ref vessel)) = evaluator.env.get(&entity.name).cloned() {
        if let Some(first_el) = entity.definition.elements.first() {
            let offset_val = evaluator.eval(first_el)?;
            let offset = match offset_val {
                RuntimeValue::Number(n) => n as usize,
                _ => 0,
            };
            let cell = vessel.read(offset);
            return Ok(Some(RuntimeValue::Cell(cell)));
        }
    }

    // ------------------------------------------------------------------------
    // 6. Memory Vessel Declaration (Storehouse, Vessel, Partition)
    // ------------------------------------------------------------------------
    let is_vessel_decl = entity.context.is_some()
        || entity.name == "Storehouse"
        || entity.name == "Vessel"
        || entity.name == "Partition"
        || entity.name.ends_with("_Storehouse")
        || entity.name.ends_with("_Partition")
        || entity.name.ends_with("_Vessel")
        || entity.name.starts_with("Storehouse_")
        || entity.name.starts_with("Partition_")
        || entity.name.starts_with("Vessel_")
        || entity.name.starts_with("Main_")
        || entity.name.starts_with("Task_");

    if is_vessel_decl {
        let val = evaluator.eval(&ASTNode::Boundary(entity.definition.clone()))?;
        if let RuntimeValue::Number(cap) = val {
            let is_storehouse = entity.name.contains("Storehouse");
            let vessel = if is_storehouse {
                Vessel::new_storehouse(&entity.name, cap as usize)
            } else {
                Vessel::new(&entity.name, cap as usize)
            };
            evaluator.env.set(&entity.name, RuntimeValue::Vessel(vessel.clone()));
            evaluator.debugger.logger.log("VESSEL", format!("Allocated {vessel}"));
            return Ok(Some(RuntimeValue::Vessel(vessel)));
        }
    }

    // Not an SVO verb or special vessel declaration
    Ok(None)
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Proofs & Execution Trace Invariants )
// ============================================================================
// SVO verbs operate directly on the environment and register substrates.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Module Closure )
// ============================================================================
// SVO verbs and vessel layer verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/universal/decoder.rs

RS | 280 LINES | 1156 WORDS | 10.0 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal AST Node Decoding, Trit Extractors & Horner Expansion Invariants )
// ================================================================================
//! OmniCode Runtime: Universal AST Decoders & Trit Transformers
//!
//! # Architectural Scope & Purpose:
//! Provides zero-allocation AST pattern extractors, balanced ternary trit sequence
//! decoders, and Horner power expansion algorithms for bijective numeric transduction.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Bijective Transduction Invariants**: The 5-trit Horner expansion
//!    $\sum_{i=0}^{N-1} t_i \cdot 3^i$ guarantees exact integer parity (e.g., $65 \iff [-1, +1, +1, -1, +1]$)
//!    across the C, Lua, and Rust VMs.
//! 2. **Symbolic Uniformity**: `extract_symbol_name` normalizes heterogeneous AST wrappers
//!    (`Identifier`, `Polarity`, `[ ROLL 1 ]`, `[ Character' ]`) into canonical lookup keys.
// ================================================================================

use crate::ast::nodes::ASTNode;
use crate::core::ternary::QuadState;
use crate::core::operators::Polarity;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Universal Decoder Function Declarations )
// ================================================================================

/// Extracts a symbolic name from a node (e.g. `[ ROLL 1 ]` -> `"ROLL 1"`, `[ Verify ]` -> `"Verify"`).
pub fn extract_symbol_name(node: &ASTNode) -> Option<String> {
    match node {
        ASTNode::Identifier(id) => Some(id.clone()),
        ASTNode::Polarity(p) => Some(p.name.clone()),
        ASTNode::Boundary(b) => {
            if b.elements.len() == 1 {
                extract_symbol_name(&b.elements[0])
            } else if b.elements.len() == 2 {
                if let (ASTNode::Identifier(id), ASTNode::Number(n)) = (&b.elements[0], &b.elements[1]) {
                    Some(format!("{} {}", id, *n as i64))
                } else if let (ASTNode::Identifier(id1), ASTNode::Identifier(id2)) = (&b.elements[0], &b.elements[1]) {
                    Some(format!("{} {}", id1, id2))
                } else {
                    None
                }
            } else {
                None
            }
        }
        ASTNode::Entity(e) => Some(e.name.clone()),
        _ => None,
    }
}

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Balanced Trit Extraction & Horner Polynomial Evaluation )
// ================================================================================

/// Extracts an array of balanced trits {-1, 0, +1} from a boundary node.
pub fn extract_trits_from_node(node: &ASTNode) -> Option<Vec<i8>> {
    match node {
```

```
        ASTNode::Boundary(b) => {
            let mut trits = Vec::new();
            for el in &b.elements {
                let t = match el {
                    ASTNode::Number(n) => {
                        let i = *n as i8;
                        if i == -1 || i == 0 || i == 1 {
                            i
                        } else {
                            return None;
                        }
                    }
                    ASTNode::Polarity(p) => match p.polarity {
                        Polarity::Abstract => 1,
                        Polarity::Concrete => -1,
                    },
                    ASTNode::Ternary(s) => match s {
                        QuadState::Proceed => 1,
                        QuadState::Await => 0,
                        QuadState::Rollback => -1,
                        QuadState::Halt => 0,
                    },
                    ASTNode::Identifier(id) => match id.as_str() {
                        "-1" => -1,
                        "0" => 0,
                        "+1" | "1" => 1,
                        _ => return None,
                    },
                    _ => return None,
                };
                trits.push(t);
            }
            if !trits.is_empty() {
                Some(trits)
            } else {
                None
            }
        }
        _ => None,
    }
}

/// Computes the balanced integer value of a balanced trit slice using Horner's method:
/// `sum_{i=0..N-1} trits[i] * 3^i`.
pub fn trits_to_integer(trits: &[i8]) -> i64 {
    let mut total: i64 = 0;
    let mut multiplier: i64 = 1;
    for &t in trits {
        total += (t as i64) * multiplier;
        multiplier *= 3;
    }
    total
}

/// Converts an integer into a balanced ternary representation of length
/// `num_trits`.
pub fn integer_to_trits(mut n: i64, num_trits: usize) -> Vec<i8> {
    let mut trits = Vec::with_capacity(num_trits);
    for _ in 0..num_trits {
        let rem = ((n % 3) + 3) % 3;
        match rem {
            0 => {
                trits.push(0);
                n /= 3;
            }
            1 => {
                trits.push(1);
                n = (n - 1) / 3;
            }
            2 => {
                trits.push(-1);
                n = (n + 1) / 3;
            }
            _ => unreachable!(),
        }
    }
    trits
}
```

```rust

/// Converts a balanced trit sequence to dual-rail (pos, neg) bitmasks.
/// For each trit index `i`:
/// - `+1`: bit `i` set in `pos_plane`
/// - `-1`: bit `i` set in `neg_plane`
/// - `0`: bit `i` clear in both planes
pub fn trits_to_dual_rail(trits: &[i8]) -> (u64, u64) {
    let mut pos: u64 = 0;
    let mut neg: u64 = 0;
    for (i, &t) in trits.iter().enumerate().take(64) {
        match t {
            1 => pos |= 1u64 << i,
            -1 => neg |= 1u64 << i,
            _ => {}
        }
    }
    (pos, neg)
}

/// Reconstructs balanced trits from dual-rail bit-planes with collision check.
/// Returns an error if any bit position has both rails asserted
/// (`pos & neg != 0`).
pub fn dual_rail_to_trits(
    pos: u64,
    neg: u64,
    num_trits: usize,
) -> Result<Vec<i8>, String> {
    let collision = pos & neg;
    if collision != 0 {
        return Err(format!(
            "FAILPOINT [DualRailCollision]: Trap at mask 0x{:016X}",
            collision
        ));
    }
    let mut trits = Vec::with_capacity(num_trits);
    for i in 0..num_trits.min(64) {
        let p = (pos >> i) & 1;
        let n = (neg >> i) & 1;
        match (p, n) {
            (0, 0) => trits.push(0),
            (1, 0) => trits.push(1),
            (0, 1) => trits.push(-1),
            _ => unreachable!(),
        }
    }
    Ok(trits)
}

// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Bijective Verification Proofs )
// ================================================================================

#[cfg(test)]
mod tests {
    use super::*;
    use crate::core::boundaries::BoundaryType;
    use crate::ast::nodes::BoundaryNode;

    #[test]
    fn test_extract_symbol_name_variants() {
        let id_node = ASTNode::Identifier("Status`".to_string());
        assert_eq!(extract_symbol_name(&id_node), Some("Status`".to_string()));

        let bound_single = ASTNode::Boundary(BoundaryNode {
            boundary_type: BoundaryType::Denotation,
            elements: vec![ASTNode::Identifier("Verify".to_string())],
            aside: None,
            line: 1,
            col: 1,
        });
        assert_eq!(extract_symbol_name(&bound_single), Some("Verify".to_string()));

        let bound_double = ASTNode::Boundary(BoundaryNode {
            boundary_type: BoundaryType::Denotation,
            elements: vec![
                ASTNode::Identifier("ROLL".to_string()),
                ASTNode::Number(1.0),
```

```
            ],
            aside: None,
            line: 1,
            col: 1,
        });
        assert_eq!(extract_symbol_name(&bound_double), Some("ROLL 1".to_string()));
    }

    #[test]
    fn test_bijective_trits_horner_expansion() {
        // 'A' (ASCII 65): [-1, 1, 1, -1, 1]
        // -1*(1) + 1*(3) + 1*(9) - 1*(27) + 1*(81) = -1 + 3 + 9 - 27 + 81 = 65
        let trits_a: [i8; 5] = [-1, 1, 1, -1, 1];
        assert_eq!(trits_to_integer(&trits_a), 65);

        // '0' (ASCII 48): [0, 1, -1, -1, 1]
        // 0*(1) + 1*(3) - 1*(9) - 1*(27) + 1*(81) = 3 - 9 - 27 + 81 = 48
        let trits_0: [i8; 5] = [0, 1, -1, -1, 1];
        assert_eq!(trits_to_integer(&trits_0), 48);
    }

    #[test]
    fn test_integer_to_trits_and_dual_rail_round_trip() {
        // Round trip 65 ('A')
        let trits_65 = integer_to_trits(65, 5);
        assert_eq!(trits_65, vec![-1, 1, 1, -1, 1]);
        assert_eq!(trits_to_integer(&trits_65), 65);

        // Round trip 48 ('0')
        let trits_48 = integer_to_trits(48, 5);
        assert_eq!(trits_48, vec![0, 1, -1, -1, 1]);
        assert_eq!(trits_to_integer(&trits_48), 48);

        // Dual rail bit planes for 'A' [-1, 1, 1, -1, 1]:
        // pos bits: 1, 2, 4 (0b10110 = 22)
        // neg bits: 0, 3 (0b01001 = 9)
        let (pos, neg) = trits_to_dual_rail(&trits_65);
        assert_eq!(pos, 0b10110);
        assert_eq!(neg, 0b01001);
        assert_eq!(pos & neg, 0); // No collision

        let recovered = dual_rail_to_trits(pos, neg, 5).unwrap();
        assert_eq!(recovered, trits_65);

        // Test collision detection
        let collision_res = dual_rail_to_trits(0b11, 0b11, 2);
        assert!(collision_res.is_err());
    }
}

```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/evaluator/universal/mod.rs

RS | 38 LINES | 171 WORDS | 1.7 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal Evaluator Helpers Subsystem Identity & Public Exports )
// ================================================================================
//! OmniCode Runtime: Universal Evaluator Helpers Module
//!
//! Re-exports AST decoders, trit extractors, and Horner expansion functions.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**: Tables of testimony, written with the finger of God.
//! - **Proverbs 24:27 (KJV)**: Prepare thy work without, and make it fit for thyself in the field.
//! - **Proverbs 22:28 (KJV)**: Remove not the ancient landmark, which thy fathers have set.
// ================================================================================

pub mod decoder;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Universal Decoding Helpers )
// ================================================================================
pub use decoder::{
    extract_symbol_name,
    extract_trits_from_node,
    trits_to_integer,
};

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Proofs & Invariants )
// ================================================================================
// Decoders are pure and stateless across all evaluation steps.

// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status & Module Closure )
// ================================================================================
// Universal evaluation decoder layer verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/README.md MD 160 LINES 1012 WORDS 8.3 KB

```
# OmniCode Runtime Environment Subsystem

```text
================================================================================
BLOCK 1: METADATA & ARCHITECTURAL MANIFESTO
================================================================================
Subsystem: OmniCode Host Engine & Virtual Machine Runtime Environment
Layer:     Execution Substrate & Transactional State Manager
Path:      <TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/
================================================================================
```

> **"And he gave unto Moses, when he had made an end of communing with him upon mount Sinai, two tables of testimony, tables of stone, written with the finger of God."**
> — *Exodus 31:18 (KJV)*
> *(The immutable inscription of atomic runes onto bounded physical tablets).*
> **"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house."**
> — *Proverbs 24:27 (KJV)*
> *(The discipline of establishing atomic data types and state substrates prior to constructing execution engines).*
> **"Remove not the ancient landmark, which thy fathers have set."**
> — *Proverbs 22:28 (KJV)*
> *(The preservation of historical memory boundaries, silicon addresses, and machine constants).*

---

1. Architectural Mission

The **Runtime Environment Subsystem** is the foundational state and data substrate for the OmniCode Virtual Machine. It decouples **value representation, physical hardware state, and transactional scoping** from the **imperative execution engine (the Evaluator)**.

By treating the environment as an independent, modular library rather than an ad-hoc dictionary:

1. **Any VM subsystem** (Evaluator, Assembler, Diagnostics, REPL, or AI Cortex) can interrogate and construct universal runtime values without circular dependencies.
2. **Reversible Execution** under balanced ternary `-1:ROLLBACK` and speculative guard failures (`! BUT`) is mathematically guaranteed through atomic transactional snapshots.
3. **Cross-Substrate Parity** is achieved across continuous text ribbons, 8-bit glyph bytes, dense 5-trit balanced ternary cells, and structured entity records.

---

2. Topological Layer Structure

The subsystem is organized into three strictly stratified architectural layers:

```bash
src/runtime/environment/
├── universal/                  <-- Tier 1: Universal Runtime Values & Metrics
│   ├── values.rs               <-- RuntimeValue, Unwrappers, Relational Equality, Metrics
│   └── mod.rs                  <-- Re-exports Universal Substrate
│
├── hardware/                   <-- Tier 2: Physical Silicon Register Bank & Ports
│   ├── registers.rs            <-- RegisterBank (13 Named Registers), OMNI_TARGET_*
│   └── mod.rs                  <-- Re-exports Hardware Substrate
│
├── scope/                      <-- Tier 3: Transactional Execution State & Scopes
│   ├── frame.rs                <-- CallFrame (SPOOL Activation Records)
│   ├── snapshot.rs             <-- EnvironmentSnapshot (Full Transactional Image)
│   ├── environment.rs          <-- Environment Coordinator (Bindings, Streams, State-Primes)
│   └── mod.rs                  <-- Re-exports Scope Primitives
│
├── mod.rs                      <-- Subsystem Facade & Backward-Compatible API
└── README.md                   <-- Architectural Manifesto & Specification
```

Layer 1: Universal (`universal/`)

- **`values.rs`**: Contains `RuntimeValue`, the core algebraic data type for all runtime entities:
  - `State(QuadState)`: Balanced ternary truth (+1: Proceed, 0: Await, -1: Rollback, NULL: Halt).
  - `Number(f64)`: 64-bit numeric scalar.
  - `Text(String)`: Continuous character sequence ribbon.
  - `Cell(Cell)`: 5-trit balanced ternary cell spanning 243 discrete states.
  - `Character { glyph: u8, cell: Cell }`: Dual-substrate atomic rune unifying 8-bit ASCII glyph with a 5-trit cell.
```

```
  - `Vessel(Vessel)`: Bounded multi-cell memory vessel.
  - `EntityRecord`: Dynamic record with field map and mutability contract.
  - `Vector`: Ordered sequence of runtime values.
- **Universal Introspection & Coercion**:
  - `as_state()`, `as_number()`, `as_text()`, `as_cell()`, `as_character()`, `as_vector()`.
  - `to_quad_state()`: Universal balanced ternary truth projection.
  - `is_glyph_equal()`: Cross-substrate relational equivalence testing without type friction.
  - `capacity_in_cells()`: Universal memory metric for invariant bound checks (e.g., `{ Character' <= [ 1 Cell ] }`).
- **Dependency Rule**: Zero dependencies on `hardware/` or `scope/`. Pure data substrate.

### Layer 2: Hardware (`hardware/`)

- **`registers.rs`**: Implements the 13 Named Silicon Machine Registers:
  - `%head` (0): Instruction Pointer / Tape Head
  - `%home` (1): Activation Frame Origin
  - `%spool` (2): Stack Spool / Activation Record Floor
  - `%it` (3): Primary Accumulator
  - `%self` (4): Instance Context
  - `%caller` (5): Invoker Context
  - `%other` (6): Peer Context
  - `%state` (7): Active QuadState Status
  - `%turn` (8): Temporal Execution Cadence
  - `%bound` (9): Watchdog Horizon Limit
  - `%from` (10): Inbound Hardware Port / Input Stream
  - `%into` (11): Outbound Hardware Port / Output Stream
  - `%discard` (12): Bit-Bucket Null Sink (writes are dropped, preserving invariance)
- **Canonical Hardware Ports**:
  - `OMNI_TARGET_STDOUT` (`0x01`): Standard terminal console.
  - `OMNI_TARGET_VGA` (`0x000B8000`): Direct video buffer memory address.
  - `OMNI_TARGET_COM1` (`0x03F8`): Serial communications port.
- **Dependency Rule**: Depends only on `universal/values.rs` and `assembler::MachineRegister`.

### Layer 3: Scope (`scope/`)

- **`frame.rs`**: `CallFrame` activation records tracking caller context, base pointers, and local scopes.
- **`snapshot.rs`**: `EnvironmentSnapshot` capturing the complete six-fold transactional horizon:
  1. Symbol table bindings (`bindings`)
  2. Silicon registers (`registers`)
  3. Call stack depth (`call_stack_len`)
  4. Outbound stream length (`output_len`)
  5. Continuous sequence ribbon length (`sequence_len`)
  6. Inbound stream buffer queue (`input_stream`)
- **`environment.rs`**: The state coordinator managing transactions (`begin`, `commit`, `rollback`), state-prime resolution (`Character'` <-> `Character`), procedural frames, and transducer I/O ports.

---

## 3. Reversible Computing & Rollback Guarantees

In OmniCode, computation is inherently reversible. Under balanced ternary logic:

- `+1:PROCEED` commits mutations to the active scope.
- `-1:ROLLBACK` or guard failure (`! BUT`) immediately calls `rollback_transaction()`.

Because `EnvironmentSnapshot` records not only bindings and registers, but also stream truncation horizons (`sequence_ribbon` and `output_stream`) and clones `input_stream`, rolling back a speculative branch leaves **zero side-effects**:

```rust
pub fn rollback_transaction(&mut self) -> Result<(), String> {
    if let Some(prev) = self.snapshots.pop() {
        self.bindings = prev.bindings;
        self.registers = prev.registers;
        self.call_stack.truncate(prev.call_stack_len);
        self.output_stream.truncate(prev.output_len);
        self.sequence_ribbon.truncate(prev.sequence_len);
        self.input_stream = prev.input_stream;
        Ok(())
    } else {
        Err("FAILPOINT [RollbackUnderflow]: No active snapshot".into())
    }
}
```

---

4. State-Prime Resolution Invariant
```

```
Identifiers in OmniCode can be decorated with state-prime affixes (`Character'` or `Character```) indicating temporal progression:

- When looking up `Character'`, if not yet explicitly bound, the environment falls back to `Character`.
- When mutating `Character'`, the environment writes the primed identifier and synchronizes the base `Character` symbol.
- In relational comparisons (`{ Character' = Glyph }`), the evaluator queries `is_glyph_equal` without mutating base state.

---

## 5. Canonical Four-Block Layout

Every source file in the Environment subsystem strictly adheres to the **Canonical 4-Block Structure**:

1. **Block 1: Metadata Block**: File scope, scripture anchors, and AI/developer context rationale.
2. **Block 2: Opening Block**: Core imports, struct/enum definitions, and baseline initializers.
3. **Block 3: Body Block**: Business logic, operations, and trait implementations.
4. **Block 4: Closing Block**: Display formatting, default traits, and verification unit tests.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/mod.rs RS | 76 LINES | 393 WORDS | 3.4 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Runtime Environment Subsystem Facade & Comprehensive Re-exports )
// ============================================================================
//! OmniCode Runtime: Transactional Environment & Register Subsystem
//!
//! # Architectural Scope & Purpose:
//! Modularizes the runtime data substrate and execution state into three
//! decoupled, topologically ordered layers:
//! 1. `universal`: Universal `RuntimeValue` enum, scalar unwrappers, cross-substrate
//!    glyph equality, and physical memory capacity metrics.
//! 2. `hardware`: Physical Silicon `RegisterBank` (the 13 Named Machine Registers)
//!    and canonical hardware device target addresses (`OMNI_TARGET_*`).
//! 3. `scope`: Procedural `CallFrame`, transactional `EnvironmentSnapshot`, and the
//!    `Environment` state coordinator.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Backward Compatibility**: Re-exports all public types at the root of `environment`
//!    ensuring zero downstream breaking changes for the Evaluator, Assembler, CLI,
//!    and Test suites.
//! 2. **Modular Reusability**: Evaluator modules and external crates can import
//!    `universal::RuntimeValue` without pulling in hardware or transaction management.
// ============================================================================

pub mod universal;
pub mod hardware;
pub mod scope;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Full Backward Compatibility )
// ============================================================================

// Universal Value Substrate
pub use universal::RuntimeValue;

// Hardware Silicon Registers & Ports
pub use hardware::{
    RegisterBank,
    OMNI_TARGET_STDOUT,
    OMNI_TARGET_VGA,
    OMNI_TARGET_COM1,
};

// Scopes, Snapshots & Environment State
pub use scope::{
    CallFrame,
    EnvironmentSnapshot,
    Environment,
};

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Structural Proofs & Invariants )
// ============================================================================
// The Environment serves as the foundational data substrate for the Evaluator.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Module Closure )
```

```
// ================================================================================
// Runtime environment subsystem verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/hardware/mod.rs

RS | 39 LINES | 175 WORDS | 1.7 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Silicon Hardware Layer Subsystem Identity & Public Exports )
// ================================================================================
//! OmniCode Runtime: Silicon Hardware Substrate Module
//!
//! Provides the physical machine register bank and memory-mapped hardware constants.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**: Tables of testimony, written with the finger of God.
//! - **Proverbs 24:27 (KJV)**: Prepare thy work without, and make it fit for thyself in the field.
//! - **Proverbs 22:28 (KJV)**: Remove not the ancient landmark, which thy fathers have set.
// ================================================================================

pub mod registers;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Hardware Register Bank & Target Addresses )
// ================================================================================
pub use registers::{
    RegisterBank,
    OMNI_TARGET_STDOUT,
    OMNI_TARGET_VGA,
    OMNI_TARGET_COM1,
};

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Hardware Substrate Invariants & Proofs )
// ================================================================================
// Hardware registers map directly to VM execution state.

// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status & Module Closure )
// ================================================================================
// Silicon hardware substrate verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/hardware/registers.rs

RS | 166 LINES | 798 WORDS | 7.3 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Physical Silicon Register Bank & Canonical Hardware Target Ports )
// ================================================================================
//! OmniCode Runtime: Silicon Register Substrate & Hardware Ports
//!
//! # Architectural Scope & Purpose:
//! Implements the 13 Named Physical Silicon Registers of the OmniCode Host Engine:
//! - `%head`    (0): Tape Head / Instruction Pointer
//! - `%home`    (1): Base Pointer / Frame Origin
//! - `%spool`   (2): Stack Spool / Activation Record Floor
//! - `%it`      (3): Primary Accumulator / Result
//! - `%self`    (4): Current Instance / Context Entity
//! - `%caller`  (5): Invoker Context Entity
//! - `%other`   (6): Peer / Auxiliary Entity
//! - `%state`   (7): Active QuadState Execution Status
//! - `%turn`    (8): Temporal Cadence / Cycle Counter
//! - `%bound`   (9): Watchdog Horizon / Recursion Limit
//! - `%from`   (10): Inbound Hardware Port / Input Stream
//! - `%into`   (11): Outbound Hardware Port / Output Stream
//! - `%discard`(12): Bit-Bucket / Null Sink (writes are safely dropped)
//!
//! Also defines canonical memory-mapped device target addresses (`OMNI_TARGET_*`).
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Silicon Parity**: Autonomous coding agents must respect that `%discard`
//!    is an immutable sink; writes to it MUST NEVER mutate state or cause panics.
//! 2. **Physical Addresses**: Canonical constants ensure hardware device ports
//!    remain stable across host architecture revisions.
// ================================================================================

use crate::core::ternary::QuadState;
use crate::runtime::assembler::MachineRegister;
use crate::runtime::environment::universal::RuntimeValue;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Canonical Hardware Addresses & RegisterBank Definition )
// ================================================================================

/// Canonical Hardware Target Addresses
pub const OMNI_TARGET_STDOUT: u64 = 0x01;
pub const OMNI_TARGET_VGA: u64 = 0x000B8000;
pub const OMNI_TARGET_COM1: u64 = 0x03F8;

/// Physical Silicon Register Bank hosting the 13 Named Machine Registers.
///
/// Implements immediate hardware cell reading, mutation, and discard-sink semantics.
#[derive(Debug, Clone, PartialEq)]
pub struct RegisterBank {
    pub cells: [RuntimeValue; 13],
}

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Register Accessors, Mutation, Discard-Sink Semantics & Name Lookup )
// ================================================================================

impl RegisterBank {
    /// Initializes the silicon register bank to pristine hardware baselines.
```

```
    pub fn new() -> Self {
        Self {
            cells: [
                RuntimeValue::Number(0.0),                  // 0: HEAD (Tape Head / IP)
                RuntimeValue::Number(0.0),                  // 1: HOME (Base Pointer / Origin)
                RuntimeValue::Number(0.0),                  // 2: SPOOL (Stack Spool / Floor)
                RuntimeValue::State(QuadState::Proceed),    // 3: IT (Accumulator / Result)
                RuntimeValue::Text("Kernel".to_string()),   // 4: SELF (Instance / Context)
                RuntimeValue::Text("Root".to_string()),     // 5: CALLER (Invoker Context)
                RuntimeValue::Text("Swarm".to_string()),    // 6: OTHER (Peer / Auxiliary)
                RuntimeValue::State(QuadState::Proceed),    // 7: STATE (QuadState Status)
                RuntimeValue::Number(0.0),                  // 8: TURN (Temporal Cadence / Cycle)
                RuntimeValue::Number(0.0),                  // 9: BOUND (Watchdog Limit / Horizon)
                RuntimeValue::Text(String::new()),          // 10: FROM (Input Channel / Stdin)
                RuntimeValue::Text(String::new()),          // 11: INTO (Output Channel / Stdout)
                RuntimeValue::State(QuadState::Proceed),    // 12: DISCARD (Bit-Bucket / Null Sink)
            ],
        }
    }

    /// Reads a register cell by its physical `MachineRegister` enum.
    pub fn read(&self, reg: MachineRegister) -> RuntimeValue {
        self.cells[reg.index() as usize].clone()
    }

    /// Writes a value to a register cell. Writes to `DISCARD` are safely dropped.
    pub fn write(&mut self, reg: MachineRegister, val: RuntimeValue) {
        if reg == MachineRegister::DISCARD {
            return;
        }
        self.cells[reg.index() as usize] = val;
    }

    /// Reads a register by name if recognized, returning `None` otherwise.
    pub fn read_by_name(&self, name: &str) -> Option<RuntimeValue> {
        MachineRegister::from_name(name).map(|r| self.read(r))
    }

    /// Writes to a register by name. Returns true if name was a recognized register.
    pub fn write_by_name(&mut self, name: &str, val: RuntimeValue) -> bool {
        if let Some(reg) = MachineRegister::from_name(name) {
            self.write(reg, val);
            true
        } else {
            false
        }
    }

    /// Resets all registers to pristine hardware baseline.
    pub fn reset(&mut self) {
        *self = Self::new();
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Default Trait Implementation & Unit Tests )
// ============================================================================

impl Default for RegisterBank {
    fn default() -> Self {
        Self::new()
    }
}

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_register_bank_initial_state() {
        let bank = RegisterBank::new();
        assert_eq!(bank.read(MachineRegister::HEAD), RuntimeValue::Number(0.0));
        assert_eq!(bank.read(MachineRegister::IT), RuntimeValue::State(QuadState::Proceed));
        assert_eq!(bank.read(MachineRegister::SELF), RuntimeValue::Text("Kernel".to_string()));
    }

    #[test]
```

```
    fn test_register_discard_sink_invariance() {
        let mut bank = RegisterBank::new();
        bank.write(MachineRegister::DISCARD, RuntimeValue::Number(9999.0));
        assert_eq!(bank.read(MachineRegister::DISCARD), RuntimeValue::State(QuadState::Proceed));
    }

    #[test]
    fn test_register_read_write_by_name() {
        let mut bank = RegisterBank::new();
        assert!(bank.write_by_name("IT", RuntimeValue::Number(42.0)));
        assert_eq!(bank.read_by_name("IT"), Some(RuntimeValue::Number(42.0)));
        assert!(!bank.write_by_name("NON_EXISTENT_REGISTER", RuntimeValue::Number(1.0)));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/scope/environment.rs

RS | 291 LINES | 1098 WORDS | 12.2 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Runtime Environment State, Transactional Scopes & Symbol Table Invariants )
// ================================================================================
//! OmniCode Runtime: Transactional Execution Environment
//!
//! # Architectural Scope & Purpose:
//! The `Environment` orchestrates scoped ontological symbol tables with native snapshot,
//! transaction nesting, and zero-cost rollback capabilities to support balanced
//! ternary -1 (Rollback) state transitions.
//!
//! In addition to lexical variable bindings, the Environment coordinates the physical
//! Silicon Register Bank (the 13 Named Machine Registers), procedural call frames,
//! hardware transducer ports (`FROM`, `INTO`), continuous text ribbons (`sequence_ribbon`),
//! and state-prime symbol resolution.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Epistemic Continuity**: Autonomous coding agents require explicit rationale
//!    for why physical registers are synchronized with symbol bindings and why
//!    state-primes (`Character'`) automatically resolve to base entities (`Character`).
//! 2. **Transactional Soundness**: Full restoration of `bindings`, `registers`, `call_stack`,
//!    `output_stream`, `sequence_ribbon`, and `input_stream` ensures zero state leakage
//!    during reversible execution branches.
// ================================================================================

use std::collections::HashMap;
use crate::runtime::assembler::MachineRegister;
use crate::runtime::environment::universal::RuntimeValue;
use crate::runtime::environment::hardware::{
    RegisterBank,
    OMNI_TARGET_STDOUT,
};
use crate::runtime::environment::scope::frame::CallFrame;
use crate::runtime::environment::scope::snapshot::EnvironmentSnapshot;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Environment Struct Definition & Initialization )
// ================================================================================

/// Transactional Runtime Environment managing symbol tables, registers, and execution streams.
#[derive(Debug, Clone)]
pub struct Environment {
    pub registers: RegisterBank,
    bindings: HashMap<String, RuntimeValue>,
    call_stack: Vec<CallFrame>,
    pub output_stream: Vec<RuntimeValue>,
    pub input_stream: Vec<RuntimeValue>,
    pub target_device: u64,
    pub sequence_ribbon: Vec<RuntimeValue>,
    snapshots: Vec<EnvironmentSnapshot>,
}

impl Environment {
    /// Creates a pristine runtime environment with default hardware registers.
    pub fn new() -> Self {
        Self {
            registers: RegisterBank::new(),
            bindings: HashMap::new(),
            call_stack: Vec::new(),
```

```
            output_stream: Vec::new(),
            input_stream: Vec::new(),
            target_device: OMNI_TARGET_STDOUT,
            sequence_ribbon: Vec::new(),
            snapshots: Vec::new(),
        }
    }
}

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Transactional Operations, Binding Mutations, Call Stacks & Transducer I/O )
// ================================================================================

impl Environment {
    /// Takes an atomic transactional snapshot of current bindings, registers, and streams.
    pub fn begin_transaction(&mut self) {
        self.snapshots.push(EnvironmentSnapshot::capture(
            self.bindings.clone(),
            self.registers.clone(),
            self.call_stack.len(),
            self.output_stream.len(),
            self.sequence_ribbon.len(),
            self.input_stream.clone(),
        ));
    }

    /// Commits the active transaction, discarding the restore snapshot.
    pub fn commit_transaction(&mut self) {
        self.snapshots.pop();
    }

    /// Unwinds and restores the environment state completely to the last snapshot.
    pub fn rollback_transaction(&mut self) -> Result<(), String> {
        if let Some(prev) = self.snapshots.pop() {
            self.bindings = prev.bindings;
            self.registers = prev.registers;
            self.call_stack.truncate(prev.call_stack_len);
            self.output_stream.truncate(prev.output_len);
            self.sequence_ribbon.truncate(prev.sequence_len);
            self.input_stream = prev.input_stream;
            Ok(())
        } else {
            Err("FAILPOINT [RollbackUnderflow]: Attempted rollback with no active transaction snapshot".into())
        }
    }

    /// Returns a reference to the active symbol bindings table.
    pub fn bindings(&self) -> &HashMap<String, RuntimeValue> {
        &self.bindings
    }

    /// Clears all bindings, call stacks, streams, and resets registers.
    pub fn clear(&mut self) {
        self.bindings.clear();
        self.registers.reset();
        self.call_stack.clear();
        self.output_stream.clear();
        self.input_stream.clear();
        self.target_device = OMNI_TARGET_STDOUT;
        self.sequence_ribbon.clear();
        self.snapshots.clear();
    }

    /// Binds a value by name. If the name corresponds to a physical register,
    /// updates the silicon register cell in addition to the symbol table.
    /// If the name contains state-prime affixes (e.g., Character` or Character'),
    /// it binds the primed name and automatically synchronizes the base entity.
    pub fn set(&mut self, name: &str, value: RuntimeValue) {
        if let Some(reg) = MachineRegister::from_name(name) {
            self.registers.write(reg, value.clone());
            if reg != MachineRegister::DISCARD {
                self.bindings.insert(name.to_string(), value);
            }
        } else {
            self.bindings.insert(name.to_string(), value.clone());
            let trimmed = name.trim_end_matches(['`', '\'']);
            if trimmed != name && !trimmed.is_empty() {
```

```
                self.bindings.insert(trimmed.to_string(), value);
            }
        }
    }

    /// Retrieves a value by name. If the name matches a silicon register,
    /// yields a reference to the physical register cell.
    /// Supports state-prime fallback: looking up Character` falls back to Character
    /// if the specific prime has not yet been bound.
    pub fn get(&self, name: &str) -> Option<&RuntimeValue> {
        if let Some(reg) = MachineRegister::from_name(name) {
            Some(&self.registers.cells[reg.index() as usize])
        } else if let Some(val) = self.bindings.get(name) {
            Some(val)
        } else {
            let trimmed = name.trim_end_matches(['`', '\'']);
            if trimmed != name && !trimmed.is_empty() {
                self.bindings.get(trimmed)
            } else {
                None
            }
        }
    }

    /// Returns true if the environment contains a binding or register for the given name.
    pub fn contains(&self, name: &str) -> bool {
        self.get(name).is_some()
    }

    /// Pushes a procedural call frame onto the `%spool` stack.
    pub fn push_call_frame(&mut self, caller: RuntimeValue, self_val: RuntimeValue, return_head: usize) {
        let home = self.call_stack.len();
        self.registers.write(MachineRegister::HOME, RuntimeValue::Number(home as f64));
        self.registers.write(MachineRegister::HEAD, RuntimeValue::Number(return_head as f64));
        self.registers.write(MachineRegister::CALLER, caller.clone());
        self.registers.write(MachineRegister::SELF, self_val.clone());
        self.call_stack.push(CallFrame::new(caller, self_val, home, return_head));
        self.registers.write(MachineRegister::SPOOL, RuntimeValue::Number(self.call_stack.len() as f64));
    }

    /// Pops the active call frame from the `%spool` stack, restoring caller context.
    pub fn pop_call_frame(&mut self) -> Option<CallFrame> {
        let popped = self.call_stack.pop()?;
        let current_spool = self.call_stack.len();
        self.registers.write(MachineRegister::SPOOL, RuntimeValue::Number(current_spool as f64));
        if let Some(prev) = self.call_stack.last() {
            self.registers.write(MachineRegister::HOME, RuntimeValue::Number(prev.home as f64));
            self.registers.write(MachineRegister::HEAD, RuntimeValue::Number(prev.head as f64));
            self.registers.write(MachineRegister::CALLER, prev.caller.clone());
            self.registers.write(MachineRegister::SELF, prev.self_val.clone());
        }
        Some(popped)
    }

    /// Emits a runtime value to the `INTO` outbound port and buffers it in output_stream.
    pub fn write_into(&mut self, val: RuntimeValue) {
        self.registers.write(MachineRegister::INTO, val.clone());
        self.output_stream.push(val);
    }

    /// Reads the next input value from `input_stream` into `FROM`, or reads current `FROM`.
    pub fn read_from(&mut self) -> RuntimeValue {
        if !self.input_stream.is_empty() {
            let next_val = self.input_stream.remove(0);
            self.registers.write(MachineRegister::FROM, next_val.clone());
            next_val
        } else {
            self.registers.read(MachineRegister::FROM)
        }
    }

    /// Reads the current value held in the `INTO` output register.
    pub fn read_into(&self) -> RuntimeValue {
        self.registers.read(MachineRegister::INTO)
    }

    /// Enqueues an input value into `input_stream` and sets the `FROM` register.
    pub fn write_from(&mut self, val: RuntimeValue) {
```

```
        self.registers.write(MachineRegister::FROM, val.clone());
        self.input_stream.push(val);
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Default Trait Implementation & Unit Tests )
// ============================================================================

impl Default for Environment {
    fn default() -> Self {
        Self::new()
    }
}

#[cfg(test)]
mod tests {
    use super::*;
    use crate::core::ternary::QuadState;

    #[test]
    fn test_environment_registers_and_discard_sink() {
        let mut env = Environment::new();
        env.set("INTO", RuntimeValue::from_glyph(b'Z'));
        assert_eq!(env.registers.read(MachineRegister::INTO).character_glyph(), Some(b'Z'));

        env.set("DISCARD", RuntimeValue::Number(999.0));
        assert_eq!(env.registers.read(MachineRegister::DISCARD), RuntimeValue::State(QuadState::Proceed));
    }

    #[test]
    fn test_environment_transactional_snapshots_and_rollback() {
        let mut env = Environment::new();
        env.set("A", RuntimeValue::Number(10.0));
        env.sequence_ribbon.push(RuntimeValue::from_char('a'));
        env.write_from(RuntimeValue::from_char('x'));

        env.begin_transaction();
        env.set("A", RuntimeValue::Number(20.0));
        env.sequence_ribbon.push(RuntimeValue::from_char('b'));
        let _ = env.read_from(); // consume 'x'
        assert_eq!(env.get("A"), Some(&RuntimeValue::Number(20.0)));
        assert_eq!(env.sequence_ribbon.len(), 2);
        assert_eq!(env.input_stream.len(), 0);

        env.rollback_transaction().expect("Rollback");
        assert_eq!(env.get("A"), Some(&RuntimeValue::Number(10.0)));
        assert_eq!(env.sequence_ribbon.len(), 1);
        assert_eq!(env.input_stream.len(), 1); // input queue restored!
    }

    #[test]
    fn test_environment_state_prime_synchronization() {
        let mut env = Environment::new();
        env.set("Character`", RuntimeValue::from_char('A'));
        assert!(env.contains("Character`"));
        assert!(env.contains("Character"));
        assert_eq!(env.get("Character"), env.get("Character`"));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/scope/frame.rs

RS | 95 LINES | 421 WORDS | 3.7 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Procedural Call Frame & Activation Record Invariants )
// ================================================================================
//! OmniCode Runtime: Procedural Call Frames
//!
//! # Architectural Scope & Purpose:
//! Defines the `CallFrame` activation record preserved on the `%spool` stack
//! during procedural and functional invocation.
//!
//! Preserves the caller entity context, instance context (`self`), return instruction
//! pointer (`head`), base frame pointer (`home`), and local lexical symbol bindings.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Stack Unwinding Safety**: Activation records must unambiguously capture
//!    caller contexts to prevent memory clobbering across reentrant invocations.
// ================================================================================

use std::collections::HashMap;
use crate::runtime::environment::universal::RuntimeValue;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( CallFrame Struct Definition & Field Declarations )
// ================================================================================

/// Call stack frame preserved on `%spool` for procedural execution.
#[derive(Debug, Clone, PartialEq)]
pub struct CallFrame {
    /// The identity or value of the invoking caller.
    pub caller: RuntimeValue,
    /// The instance context (`self`) of the active procedure.
    pub self_val: RuntimeValue,
    /// The base stack depth (`%home`) prior to activation.
    pub home: usize,
    /// The return instruction address (`%head`).
    pub head: usize,
    /// Local scoped symbol bindings specific to this activation frame.
    pub locals: HashMap<String, RuntimeValue>,
}

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( CallFrame Initialization & Scope Accessors )
// ================================================================================

impl CallFrame {
    /// Creates a new activation record with empty local bindings.
    pub fn new(caller: RuntimeValue, self_val: RuntimeValue, home: usize, head: usize) -> Self {
        Self {
            caller,
            self_val,
            home,
            head,
            locals: HashMap::new(),
        }
    }
}

// ================================================================================
```

```
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Verification Proofs )
// ================================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_call_frame_creation() {
        let frame = CallFrame::new(
            RuntimeValue::Text("Caller".to_string()),
            RuntimeValue::Text("Self".to_string()),
            0,
            100,
        );
        assert_eq!(frame.home, 0);
        assert_eq!(frame.head, 100);
        assert!(frame.locals.is_empty());
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/scope/mod.rs

RS | 39 LINES | 180 WORDS | 1.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Scope & Transaction Layer Subsystem Identity & Public Exports )
// ============================================================================
//! OmniCode Runtime: Scope & Transaction Management Module
//!
//! Provides procedural call frames, transactional snapshots, and the
//! environment state coordinator.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**: Tables of testimony, written with the finger of God.
//! - **Proverbs 24:27 (KJV)**: Prepare thy work without, and make it fit for thyself in the field.
//! - **Proverbs 22:28 (KJV)**: Remove not the ancient landmark, which thy fathers have set.
// ============================================================================

pub mod frame;
pub mod snapshot;
pub mod environment;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Scope Types )
// ============================================================================
pub use frame::CallFrame;
pub use snapshot::EnvironmentSnapshot;
pub use environment::Environment;

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Scope Layer Invariants & Proofs )
// ============================================================================
// Execution environments manage transactional scopes and symbols.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status & Module Closure )
// ============================================================================
// Scope layer verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/scope/snapshot.rs

RS | 109 LINES | 423 WORDS | 4.1 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Transactional Snapshot Invariants & Reversible Execution State )
// ================================================================================
//! OmniCode Runtime: Transactional Environment Snapshot
//!
//! # Architectural Scope & Purpose:
//! Encapsulates an atomic image of the runtime environment at a transaction boundary.
//!
//! Captures:
//! 1. Lexical symbol table bindings (`bindings`).
//! 2. Physical silicon register bank (`registers`).
//! 3. Procedural call stack depth (`call_stack_len`).
//! 4. Hardware outbound stream length (`output_len`).
//! 5. Sequential character ribbon length (`sequence_len`).
//! 6. Exact inbound hardware stream buffer (`input_stream`).
//!
//! Ensures 100% reversible computation under balanced ternary `-1:ROLLBACK`
//! and speculative guard failure (`! BUT`).
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Complete Reversibility**: Truncating `sequence_ribbon` and restoring
//!    dequeued `input_stream` items prevents side-effect leakage during speculative roll evaluations.
// ================================================================================

use std::collections::HashMap;
use crate::runtime::environment::universal::RuntimeValue;
use crate::runtime::environment::hardware::RegisterBank;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( EnvironmentSnapshot Struct Definition )
// ================================================================================

/// Transactional snapshot capturing symbolic bindings, physical registers, and stream horizons.
#[derive(Debug, Clone)]
pub struct EnvironmentSnapshot {
    pub bindings: HashMap<String, RuntimeValue>,
    pub registers: RegisterBank,
    pub call_stack_len: usize,
    pub output_len: usize,
    pub sequence_len: usize,
    pub input_stream: Vec<RuntimeValue>,
}

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Snapshot Constructor & State Invariants )
// ================================================================================

impl EnvironmentSnapshot {
    /// Captures a complete atomic snapshot of the execution state.
    pub fn capture(
        bindings: HashMap<String, RuntimeValue>,
        registers: RegisterBank,
        call_stack_len: usize,
        output_len: usize,
        sequence_len: usize,
        input_stream: Vec<RuntimeValue>,
    ) -> Self {
```

```
        Self {
            bindings,
            registers,
            call_stack_len,
            output_len,
            sequence_len,
            input_stream,
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Verification Proofs )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_snapshot_capture() {
        let snap = EnvironmentSnapshot::capture(
            HashMap::new(),
            RegisterBank::new(),
            0,
            0,
            0,
            Vec::new(),
        );
        assert_eq!(snap.call_stack_len, 0);
        assert_eq!(snap.sequence_len, 0);
        assert!(snap.input_stream.is_empty());
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/universal/mod.rs

RS | 34 LINES | 167 WORDS | 1.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal Value Layer Subsystem Identity & Public Exports )
// ============================================================================
//! OmniCode Runtime: Universal Value Layer Module
//!
//! Provides the foundational, universal value primitives for the OmniCode VM.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**: Tables of testimony, written with the finger of God.
//! - **Proverbs 24:27 (KJV)**: Prepare thy work without, and make it fit for thyself in the field.
//! - **Proverbs 22:28 (KJV)**: Remove not the ancient landmark, which thy fathers have set.
// ============================================================================

pub mod values;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Universal Runtime Values )
// ============================================================================
pub use values::RuntimeValue;

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Universal Invariants & Subsystem Proofs )
// ============================================================================
// Values are pure and decouple representation from execution.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status & Module Closure )
// ============================================================================
// Universal value layer verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/environment/universal/values.rs

RS | 596 LINES | 2210 WORDS | 23.6 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal Runtime Value Representation, Unwrapping & Metric Invariants )
// ================================================================================
//! OmniCode Runtime: Universal Runtime Value Substrate
//!
//! # Architectural Scope & Purpose:
//! Defines the universal `RuntimeValue` enum representing every discrete unit of
//! data flowing through the OmniCode Virtual Machine.
//!
//! Provides zero-cost scalar unwrappers, bijective character-cell transducers,
//! balanced ternary quad-state truth projections, cross-substrate relational
//! equality guards, and physical cell capacity metrics.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Cross-Substrate Soundness**: `Character` unifies an 8-bit glyph byte with
//!    a 5-trit balanced ternary `Cell`. Unification methods like `is_glyph_equal`
//!    allow relational algebra to operate seamlessly across text, cells, and characters.
//! 2. **Universal Introspection**: Evaluator sub-modules and execution pipelines
//!    require standardized unwrapping (`as_state`, `as_number`, `as_text`) without
//!    resorting to repeated error-prone match blocks.
//! 3. **Bounded Capacity Invariants**: Relational constraints like `{ Character' <= [ 1 Cell ] }`
//!    require an objective metric `capacity_in_cells()` to verify memory bounds.
// ================================================================================

use std::collections::HashMap;
use std::fmt;
use crate::core::ternary::QuadState;
use crate::core::cell::Cell;
use crate::core::vessel::Vessel;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( RuntimeValue Enum Definition & Core Constructors )
// ================================================================================

/// Represents any discrete value flowing through the OmniCode runtime.
///
/// Implements full dual-substrate parity across balanced ternary truth states,
/// continuous text strings, dense 5-trit cells, and the atomic Character rune.
#[derive(Debug, Clone, PartialEq)]
pub enum RuntimeValue {
    /// Quad-State truth value (+1: Proceed, 0: Await, -1: Rollback, NULL: Halt).
    State(QuadState),
    /// 64-bit floating-point numeric scalar or integer codepoint.
    Number(f64),
    /// Continuous text string ribbon composed of sequential characters.
    Text(String),
    /// Atomic 5-trit balanced ternary memory cell (spanning 243 states).
    Cell(Cell),
    /// Atomic Character rune enclosing both 8-bit ASCII glyph and 5-trit Cell.
    /// Fulfills invariant: `{ Character } = [ Enclosed ]: TRUE`.
    Character {
        glyph: u8,
        cell: Cell,
    },
    /// Bounded multi-cell memory vessel or storehouse partition.
    Vessel(Vessel),
    /// Structured entity record containing named fields and mutability contract.
    EntityRecord {
```

```
        name: String,
        is_immutable: bool,
        values: HashMap<String, Box<RuntimeValue>>,
    },
    /// Ordered vector of runtime values.
    Vector(Vec<RuntimeValue>),
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Constructors, Universal Unwrapping, Relational Helpers & Capacity Metrics )
// ============================================================================

impl RuntimeValue {
    // ------------------------------------------------------------------------
    // Constructors
    // ------------------------------------------------------------------------

    /// Constructs a `RuntimeValue::State` from a balanced ternary `QuadState`.
    pub fn from_state(state: QuadState) -> Self {
        RuntimeValue::State(state)
    }

    /// Constructs a `RuntimeValue::Number` from an `f64`.
    pub fn from_number(n: f64) -> Self {
        RuntimeValue::Number(n)
    }

    /// Constructs a `RuntimeValue::Text` from any string-like type.
    pub fn from_text(t: impl Into<String>) -> Self {
        RuntimeValue::Text(t.into())
    }

    /// Constructs a `RuntimeValue::Cell` from a 5-trit `Cell`.
    pub fn from_cell(cell: Cell) -> Self {
        RuntimeValue::Cell(cell)
    }

    /// Constructs a `RuntimeValue::Character` from an 8-bit ASCII byte/glyph,
    /// bijectively transducing the byte into a 5-trit balanced ternary `Cell`.
    pub fn from_glyph(glyph: u8) -> Self {
        let cell = Cell::from_natural(glyph).unwrap_or_else(|_| Cell::from_state(QuadState::Rollback));
        RuntimeValue::Character { glyph, cell }
    }

    /// Constructs a `RuntimeValue::Character` from a standard Rust character.
    pub fn from_char(c: char) -> Self {
        let glyph = (c as u32 & 0xFF) as u8;
        Self::from_glyph(glyph)
    }

    // ------------------------------------------------------------------------
    // Universal Scalar Extractors & Unwrappers
    // ------------------------------------------------------------------------

    /// Returns the wrapped `QuadState` if this value is a `State`.
    pub fn as_state(&self) -> Option<QuadState> {
        match self {
            RuntimeValue::State(s) => Some(*s),
            _ => None,
        }
    }

    /// Returns the wrapped `f64` if this value is a `Number`.
    pub fn as_number(&self) -> Option<f64> {
        match self {
            RuntimeValue::Number(n) => Some(*n),
            _ => None,
        }
    }

    /// Returns a string slice if this value is `Text`.
    pub fn as_text(&self) -> Option<&str> {
        match self {
            RuntimeValue::Text(t) => Some(t.as_str()),
            _ => None,
        }
    }
```

```rust

    /// Returns the wrapped `Cell` if this value is a `Cell` or extracts the cell substrate of a `Character`.
    pub fn as_cell(&self) -> Option<Cell> {
        match self {
            RuntimeValue::Cell(c) => Some(*c),
            RuntimeValue::Character { cell, .. } => Some(*cell),
            _ => None,
        }
    }

    /// Returns the 8-bit glyph byte and 5-trit cell if this value is a `Character`.
    pub fn as_character(&self) -> Option<(u8, Cell)> {
        match self {
            RuntimeValue::Character { glyph, cell } => Some((*glyph, *cell)),
            _ => None,
        }
    }

    /// Returns a slice of elements if this value is a `Vector`.
    pub fn as_vector(&self) -> Option<&[RuntimeValue]> {
        match self {
            RuntimeValue::Vector(v) => Some(v.as_slice()),
            _ => None,
        }
    }

    /// Returns the 8-bit glyph byte if this value is a Character or convertible numeric/text value.
    pub fn character_glyph(&self) -> Option<u8> {
        match self {
            RuntimeValue::Character { glyph, .. } => Some(*glyph),
            RuntimeValue::Number(n) => {
                if *n >= 0.0 && *n <= 255.0 {
                    Some(*n as u8)
                } else {
                    None
                }
            }
            RuntimeValue::Text(t) => {
                let bytes = t.as_bytes();
                if bytes.len() == 1 {
                    Some(bytes[0])
                } else {
                    None
                }
            }
            _ => None,
        }
    }

    /// Returns the 5-trit `Cell` substrate if this value is a Character or Cell.
    pub fn character_cell(&self) -> Option<Cell> {
        match self {
            RuntimeValue::Character { cell, .. } => Some(*cell),
            RuntimeValue::Cell(c) => Some(*c),
            RuntimeValue::Number(n) => {
                if *n >= 0.0 && *n <= 242.0 {
                    Cell::from_natural(*n as u8).ok()
                } else {
                    None
                }
            }
            _ => None,
        }
    }

    // ---------------------------------------------------------------------------
    // Quad-State Truthiness Predicates
    // ---------------------------------------------------------------------------

    /// Returns true if this value is strictly `+1:PROCEED`.
    pub fn is_proceed(&self) -> bool {
        matches!(self, RuntimeValue::State(QuadState::Proceed))
    }

    /// Returns true if this value is strictly `0:AWAIT`.
    pub fn is_await(&self) -> bool {
        matches!(self, RuntimeValue::State(QuadState::Await))
    }
```

```
    /// Returns true if this value is strictly `-1:ROLLBACK`.
    pub fn is_rollback(&self) -> bool {
        matches!(self, RuntimeValue::State(QuadState::Rollback))
    }

    /// Returns true if this value is strictly `NULL:HALT`.
    pub fn is_halt(&self) -> bool {
        matches!(self, RuntimeValue::State(QuadState::Halt))
    }

    /// Universally projects any runtime value to a balanced ternary `QuadState`.
    pub fn to_quad_state(&self) -> QuadState {
        match self {
            RuntimeValue::State(s) => *s,
            RuntimeValue::Number(n) => {
                if *n > 0.0 {
                    QuadState::Proceed
                } else if *n == 0.0 {
                    QuadState::Await
                } else {
                    QuadState::Rollback
                }
            }
            RuntimeValue::Text(t) => {
                if t.is_empty() {
                    QuadState::Await
                } else {
                    QuadState::Proceed
                }
            }
            RuntimeValue::Cell(c) => c.state,
            RuntimeValue::Character { cell, .. } => cell.state,
            RuntimeValue::Vessel(_) => QuadState::Proceed,
            RuntimeValue::EntityRecord { .. } => QuadState::Proceed,
            RuntimeValue::Vector(v) => {
                if v.is_empty() {
                    QuadState::Await
                } else {
                    QuadState::Proceed
                }
            }
        }
    }

    // ------------------------------------------------------------------------
    // Universal Dual-Substrate Relational Equality
    // ------------------------------------------------------------------------

    /// Compares two runtime values for semantic / glyph equivalence across representations.
    ///
    /// For example:
    /// - `Character('A')` equals `Character('A')`.
    /// - `Character('A')` equals `Text("A")`.
    /// - `Character('A')` equals `Number(65.0)`.
    /// - In general, identical types match by direct value equality.
    pub fn is_glyph_equal(&self, other: &Self) -> bool {
        if self == other {
            return true;
        }

        // Cross-compare glyph representations
        if let (Some(g1), Some(g2)) = (self.character_glyph(), other.character_glyph()) {
            if g1 == g2 {
                return true;
            }
        }

        // Cross-compare cell representations
        if let (Some(c1), Some(c2)) = (self.character_cell(), other.character_cell()) {
            if c1 == c2 {
                return true;
            }
        }

        // Numeric equivalence
        if let (Some(n1), Some(n2)) = (self.as_number(), other.as_number()) {
            return (n1 - n2).abs() < f64::EPSILON;
```

```
        }

        // String equivalence with boundary cast and quote stripping
        if let (Some(t1), Some(t2)) = (self.as_text(), other.as_text()) {
            if t1 == t2 {
                return true;
            }
            let c1 = t1.trim()
                .trim_matches(['\'', '"', '[', ']', '{', '}', '<', '>'])
                .trim();
            let c2 = t2.trim()
                .trim_matches(['\'', '"', '[', ']', '{', '}', '<', '>'])
                .trim();
            if c1 == c2 || c1.eq_ignore_ascii_case(c2) {
                return true;
            }
        }

        // Single-element vector unwrap for boundary-enclosed scalar comparisons
        if let RuntimeValue::Vector(v) = self {
            if v.len() == 1 {
                return v[0].is_glyph_equal(other);
            }
        }
        if let RuntimeValue::Vector(v) = other {
            if v.len() == 1 {
                return self.is_glyph_equal(&v[0]);
            }
        }

        // State vs Number / Text duality (Duality: words & values / states & numbers)
        // Freestanding language semantics:
        // - Literal operator "" ("0", "1", "-1") clarifies literal scalar value
        // - Boundary casts [ 0 ], { 0 }, < 0 > clarify boundary enclosure
        // - Keyword literal '' ('AWAIT', 'PROCEED') clarifies keyword as word
        match (self, other) {
            (RuntimeValue::State(s), RuntimeValue::Number(n))
            | (RuntimeValue::Number(n), RuntimeValue::State(s)) => {
                if let Some(i) = s.as_int() {
                    return (*n - i as f64).abs() < f64::EPSILON;
                }
            }
            (RuntimeValue::State(s), RuntimeValue::Text(t))
            | (RuntimeValue::Text(t), RuntimeValue::State(s)) => {
                let clean = t.trim()
                    .trim_matches(['\'', '"', '[', ']', '{', '}', '<', '>'])
                    .trim();
                if clean == "0" && *s == QuadState::Await {
                    return true;
                }
                if (clean == "1" || clean == "+1")
                    && *s == QuadState::Proceed
                {
                    return true;
                }
                if clean == "-1" && *s == QuadState::Rollback {
                    return true;
                }
                if clean.eq_ignore_ascii_case("proceed")
                    || clean.eq_ignore_ascii_case("yes")
                {
                    return *s == QuadState::Proceed;
                }
                if clean.eq_ignore_ascii_case("await")
                    || clean.eq_ignore_ascii_case("ok")
                    || clean.eq_ignore_ascii_case("pause")
                {
                    return *s == QuadState::Await;
                }
                if clean.eq_ignore_ascii_case("rollback")
                    || clean.eq_ignore_ascii_case("no")
                {
                    return *s == QuadState::Rollback;
                }
                if clean.eq_ignore_ascii_case("halt")
                    || clean.eq_ignore_ascii_case("null")
                    || clean.eq_ignore_ascii_case("void")
                {
```

```
                    return *s == QuadState::Halt;
                }
            }
            (RuntimeValue::Number(n), RuntimeValue::Text(t))
            | (RuntimeValue::Text(t), RuntimeValue::Number(n)) => {
                let clean = t.trim()
                    .trim_matches(['\'', '"', '[', ']', '{', '}', '<', '>'])
                    .trim();
                if let Ok(parsed) = clean.parse::<f64>() {
                    return (*n - parsed).abs() < f64::EPSILON;
                }
            }
            _ => {}
        }

        false
    }

    // ---------------------------------------------------------------------------
    // Universal Capacity Metric
    // ---------------------------------------------------------------------------

    /// Measures the physical memory capacity of a value in units of 5-trit cells.
    ///
    /// Fulfills capacity bound tests like: `{ Character' <= [ 1 Cell ] }`.
    pub fn capacity_in_cells(&self) -> usize {
        match self {
            RuntimeValue::Character { .. } => 1,
            RuntimeValue::Cell(_) => 1,
            RuntimeValue::State(_) => 1,
            RuntimeValue::Number(_) => 1,
            RuntimeValue::Text(t) => t.len(),
            RuntimeValue::Vessel(v) => v.capacity,
            RuntimeValue::EntityRecord { values, .. } => values.len(),
            RuntimeValue::Vector(v) => v.iter().map(|e| e.capacity_in_cells()).sum(),
        }
    }

    // ---------------------------------------------------------------------------
    // Terminal ANSI Color Formatting
    // ---------------------------------------------------------------------------

    /// Formats the runtime value with ANSI color styling for terminal output.
    pub fn format_colored(&self) -> String {
        match self {
            RuntimeValue::State(QuadState::Proceed) => "\x1b[1;32m+1:PROCEED\x1b[0m".to_string(),
            RuntimeValue::State(QuadState::Await) => "\x1b[1;33m0:AWAIT\x1b[0m".to_string(),
            RuntimeValue::State(QuadState::Rollback) => "\x1b[1;31m-1:ROLLBACK\x1b[0m".to_string(),
            RuntimeValue::State(QuadState::Halt) => "\x1b[1;35mNULL:HALT\x1b[0m".to_string(),
            RuntimeValue::Number(n) => format!("\x1b[1;36m{n}\x1b[0m"),
            RuntimeValue::Text(t) => format!("\x1b[0;32m\"{t}\"\x1b[0m"),
            RuntimeValue::Cell(c) => format!("\x1b[1;35m{c}\x1b[0m"),
            RuntimeValue::Character { glyph, cell } => {
                let ch = if glyph.is_ascii_graphic() || *glyph == b' ' {
                    (*glyph as char).to_string()
                } else {
                    format!("\\x{:02X}", glyph)
                };
                format!("\x1b[1;33m'{}' <{}>\x1b[0m", ch, cell)
            }
            RuntimeValue::Vessel(v) => format!("\x1b[1;34m{v}\x1b[0m"),
            RuntimeValue::EntityRecord { name, is_immutable, values } => {
                let kind = if *is_immutable { "Axiom" } else { "Entity" };
                format!("\x1b[1;34m{kind} < {name} > [ {} fields ]\x1b[0m", values.len())
            }
            RuntimeValue::Vector(elements) => {
                let formatted: Vec<String> = elements.iter().map(|e| e.format_colored()).collect();
                format!("[{}]", formatted.join(", "))
            }
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Display Trait Implementation & Unit Tests )
// ============================================================================

```

```rust
impl fmt::Display for RuntimeValue {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        match self {
            RuntimeValue::State(s) => write!(f, "{s}"),
            RuntimeValue::Number(n) => write!(f, "{n}"),
            RuntimeValue::Text(t) => write!(f, "\"{t}\""),
            RuntimeValue::Cell(c) => write!(f, "{c}"),
            RuntimeValue::Character { glyph, .. } => {
                let ch = if glyph.is_ascii_graphic() || *glyph == b' ' {
                    (*glyph as char).to_string()
                } else {
                    format!("\\x{:02X}", glyph)
                };
                write!(f, "'{ch}'")
            }
            RuntimeValue::Vessel(v) => write!(f, "{v}"),
            RuntimeValue::EntityRecord { name, is_immutable, values } => {
                let kind = if *is_immutable { "Axiom" } else { "Entity" };
                write!(f, "{kind} < {name} > [ {} fields ]", values.len())
            }
            RuntimeValue::Vector(elements) => {
                let formatted: Vec<String> = elements.iter().map(|e| e.to_string()).collect();
                write!(f, "[{}]", formatted.join(", "))
            }
        }
    }
}

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_universal_scalar_unwrappers() {
        let val_num = RuntimeValue::from_number(42.0);
        assert_eq!(val_num.as_number(), Some(42.0));
        assert_eq!(val_num.as_state(), None);

        let val_state = RuntimeValue::from_state(QuadState::Proceed);
        assert_eq!(val_state.as_state(), Some(QuadState::Proceed));
        assert!(val_state.is_proceed());
        assert!(!val_state.is_rollback());

        let val_text = RuntimeValue::from_text("Hello");
        assert_eq!(val_text.as_text(), Some("Hello"));
        assert_eq!(val_text.to_quad_state(), QuadState::Proceed);

        let empty_text = RuntimeValue::from_text("");
        assert_eq!(empty_text.to_quad_state(), QuadState::Await);
    }

    #[test]
    fn test_universal_glyph_and_cell_equality() {
        let ch = RuntimeValue::from_glyph(b'A');
        let text_a = RuntimeValue::from_text("A");
        let num_65 = RuntimeValue::from_number(65.0);

        assert!(ch.is_glyph_equal(&text_a));
        assert!(ch.is_glyph_equal(&num_65));
        assert!(text_a.is_glyph_equal(&num_65));

        let ch_b = RuntimeValue::from_glyph(b'B');
        assert!(!ch.is_glyph_equal(&ch_b));
    }

    #[test]
    fn test_universal_capacity_metric() {
        let ch = RuntimeValue::from_char('X');
        assert_eq!(ch.capacity_in_cells(), 1);

        let cell = RuntimeValue::from_cell(Cell::equilibrium());
        assert_eq!(cell.capacity_in_cells(), 1);

        let text = RuntimeValue::from_text("12345");
        assert_eq!(text.capacity_in_cells(), 5);
    }

    #[test]
```

```
    fn test_literal_operator_and_boundary_casting_duality() {
        let state_await = RuntimeValue::from_state(QuadState::Await);
        let num_zero = RuntimeValue::from_number(0.0);
        let lit_zero = RuntimeValue::from_text("\"0\"");
        let plain_zero = RuntimeValue::from_text("0");
        let cast_bracket = RuntimeValue::from_text("[ 0 ]");
        let cast_brace = RuntimeValue::from_text("{ 0 }");
        let cast_chevron = RuntimeValue::from_text("< 0 >");
        let word_await_single = RuntimeValue::from_text("'AWAIT'");
        let word_await_double = RuntimeValue::from_text("\"AWAIT\"");

        // 1. Literal operator "" clarifies zero as literal value
        assert!(num_zero.is_glyph_equal(&lit_zero));
        assert!(num_zero.is_glyph_equal(&plain_zero));
        assert!(lit_zero.is_glyph_equal(&plain_zero));

        // 2. Boundary casts [ 0 ], { 0 }, < 0 > match zero and Await state
        assert!(num_zero.is_glyph_equal(&cast_bracket));
        assert!(num_zero.is_glyph_equal(&cast_brace));
        assert!(num_zero.is_glyph_equal(&cast_chevron));
        assert!(state_await.is_glyph_equal(&cast_bracket));
        assert!(state_await.is_glyph_equal(&cast_brace));
        assert!(state_await.is_glyph_equal(&cast_chevron));

        // 3. 'AWAIT' keyword-as-word matches state Await and word "AWAIT"
        assert!(state_await.is_glyph_equal(&word_await_single));
        assert!(state_await.is_glyph_equal(&word_await_double));
        assert!(word_await_single.is_glyph_equal(&word_await_double));

        // 4. Positive and Negative Unities Duality (+1: Proceed, -1: Rollback)
        let state_proceed = RuntimeValue::from_state(QuadState::Proceed);
        let num_one = RuntimeValue::from_number(1.0);
        let cast_one = RuntimeValue::from_text("[ +1 ]");
        let word_proceed = RuntimeValue::from_text("'PROCEED'");
        assert!(num_one.is_glyph_equal(&cast_one));
        assert!(state_proceed.is_glyph_equal(&cast_one));
        assert!(state_proceed.is_glyph_equal(&word_proceed));

        let state_rollback = RuntimeValue::from_state(QuadState::Rollback);
        let num_neg_one = RuntimeValue::from_number(-1.0);
        let cast_neg_one = RuntimeValue::from_text("[ -1 ]");
        let word_rollback = RuntimeValue::from_text("'ROLLBACK'");
        assert!(num_neg_one.is_glyph_equal(&cast_neg_one));
        assert!(state_rollback.is_glyph_equal(&cast_neg_one));
        assert!(state_rollback.is_glyph_equal(&word_rollback));

        // 5. NULL / Void Duality
        let state_halt = RuntimeValue::from_state(QuadState::Halt);
        let cast_null = RuntimeValue::from_text("[ NULL ]");
        let word_null = RuntimeValue::from_text("'NULL'");
        assert!(state_halt.is_glyph_equal(&cast_null));
        assert!(state_halt.is_glyph_equal(&word_null));
    }
}
```

OmniCode: Chapter 7: Track 1 - Bytecode Assembler & Lowering

Instruction Encodings, Lowering Lexicon Tapes to Words

CHAPTER IDENTIFIER	**NOTEBOOKLM WORD COUNT**
CH 07	15,120 words
CATALOGED CHAPTER FILES	**GENERATION DATE**
17 files (3,456 lines)	2026-10-16 20:35:57

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"Trace lowering pipeline from tape rolls to machine words."*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (17 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/README.md**	MD	136	1,065	8.6
2	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/core.rs**	RS	529	2,197	26.2
3	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/mod.rs**	RS	94	474	4.3
4	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/lowering/mod.rs**	RS	46	276	2.4
5	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/lowering/omni.rs**	RS	227	834	10.2
6	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/lowering/roll.rs**	RS	387	1,403	17.3
7	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/lowering/tape.rs**	RS	91	378	3.8
8	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/universal/isa.rs**	RS	357	1,693	15.5
9	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/universal/mod.rs**	RS	52	194	2.0
10	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/universal/types.rs**	RS	210	900	8.2
11	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/transpiler/baremetal.rs**	RS	254	1,299	13.1
12	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/transpiler/c.rs**	RS	297	1,211	15.5
13	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/transpiler/json.rs**	RS	109	475	5.0
14	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/transpiler/listing.rs**	RS	129	537	5.9
15	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/transpiler/lua.rs**	RS	297	1,189	15.8
16	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/transpiler/mod.rs**	RS	59	217	2.1
17	**<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/transpiler/omni.rs**	RS	182	778	9.2

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/README.md MD 136 LINES 1065 WORDS 8.6 KB

```
# OmniCode Runtime Physical Assembler Subsystem

```text
================================================================================
BLOCK 1: METADATA & ARCHITECTURAL MANIFESTO
================================================================================
Subsystem: OmniCode Host Engine & Virtual Machine Physical Assembler
Layer:     Silicon Lowering, Memory Allocation & Multi-Target Transpiler Engine
Path:      <TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/
================================================================================
```

> **"And he gave unto Moses, when he had made an end of communing with him upon mount Sinai, two tables of testimony, tables of stone, written with the finger of God."**
> — *Exodus 31:18 (KJV)*
> *(The immutable inscription of atomic runes onto bounded physical tablets).*
>
> **"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house."**
> — *Proverbs 24:27 (KJV)*
> *(The discipline of proving atomic sub-engines and verification invariants before constructing complex systems).*
>
> **"Remove not the ancient landmark, which thy fathers have set."**
> — *Proverbs 22:28 (KJV)*
> *(The preservation of historical memory boundaries, silicon addresses, and machine constants).*

---

1. Architectural Mission

The **Physical Assembler Subsystem** is the transduction bridge between abstract ontological expressions (`+`) and concrete silicon hardware execution (`-`). It transforms high-level procedural process ribbons (`.tape`) and declarative spatial architecture reels (`.omni`) into discrete, 64-bit balanced-ternary machine words ([`Word64`]), allocates physical storehouse memory partitions, binds linguistic pronouns to CPU hardware registers, and emits multi-target runtime artifacts (bare-metal BIOS MBR bootloaders, Multiboot ELF kernels, JSON ASTs, and assembly listings).

By decomposing the monolithic 1,930-line assembler into four specialized architectural tiers:

1. **Universal Substrate (`universal/`)**: Houses the hardware instruction set architecture ([`MachineOp`]), 13 named hardware registers ([`MachineRegister`]), balanced-ternary machine word packaging, and core data containers ([`PhysicalSymbol`], [`AssembledInstruction`], [`AssembledTape`]).
2. **Lowering Pipelines (`lowering/`)**: Compiles atomic procedural statements (`roll.rs`), entire process ribbons (`tape.rs`), and 4-Block spatial reels (`omni.rs`) into physical silicon instructions with memory bounds tracking.
3. **Multi-Target Transpilers (`transpiler/`)**: Projects lowered tapes into annotated assembly listings (`listing.rs`), IDE hovercard JSON (`json.rs`), bidirectional `.tape` <-> `.omni` translations (`omni.rs`), and bare-metal x86 Real Mode / Multiboot assembly (`baremetal.rs`).
4. **Core Coordinator (`core.rs`)**: Orchestrates the [`OmniAssembler`], handles filesystem path discovery, and houses the comprehensive regression test suite.

---

2. Topological Layer Structure

```bash
src/runtime/assembler/
├── universal/                  <-- Tier 1: Hardware ISA & Fundamental Data Containers
│   ├── isa.rs                  <-- MachineOp, MachineRegister, Pronoun/Polarity Maps, Word64 Synthesis
│   ├── types.rs                <-- PhysicalSymbol, AssembledInstruction, AssembledTape, Hardware Bounds
│   └── mod.rs                  <-- Re-exports Universal ISA & Types
│
├── lowering/                   <-- Tier 2: Tape & Omni Statement Lowering Pipelines
│   ├── roll.rs                 <-- Atomic Single-Roll Lowering (Memory Offsets, Delimiters, SVO Verbs)
│   ├── tape.rs                 <-- Full Procedural .tape Ribbon Lowering Loop
│   ├── omni.rs                 <-- Declarative 4-Block .omni Spatial Reel Parser & Lowerer
│   └── mod.rs                  <-- Re-exports Lowering Pipelines
│
├── transpiler/                 <-- Tier 3: Multi-Target Code & Serializer Generation
│   ├── listing.rs              <-- Human-Readable Annotated Assembly Listings & Silicon Words
│   ├── json.rs                 <-- Structured JSON ASTs for Language Server & Debuggers
│   ├── omni.rs                 <-- Bidirectional Decompilation (.tape <--> .omni)
│   ├── baremetal.rs            <-- 16-Bit Real Mode BIOS MBR Bootloader & 32-Bit Multiboot ELF Assembly
│   └── mod.rs                  <-- Re-exports Multi-Target Transpilers
│
├── core.rs                     <-- Tier 4: Main OmniAssembler Struct, assemble_file & Verification Tests
├── mod.rs                      <-- Subsystem Public Facade (100% Backward Compatible)
```
```

```
└── README.md                   <-- Architectural Manifesto & Specification
```

---

3. Subsystem Breakdown

3.1 Universal (`universal/`)

- **Hardware Opcodes (`MachineOp`)**: Defines discrete silicon operations (`Nop`, `RefAbstract`, `AllocConcrete`, `TransduceVector`, `FeedbackVector`, `PartitionSlice`, `SynthesizeLayer`, `BindChannel`, `CastBoundary`, `IntrospectSelf`, `RecurseItself`, `AssertCapability`).
- **Named Silicon Registers (`MachineRegister`)**: 13 physical CPU registers with bidirectional parsing and backward compatibility aliases:
  - `HEAD` (0 / `%head` / `%ip` / `HERE`)
  - `HOME` (1 / `%home` / `%fp` / `ORIGIN`)
  - `SPOOL` (2 / `%spool` / `%sp` / `OWNER`)
  - `IT` (3 / `%it` / `%acc`)
  - `SELF` (4 / `%self` / `sl`)
  - `CALLER` (5 / `%caller` / `cl`)
  - `OTHER` (6 / `%other` / `%swarm`)
  - `STATE` (7 / `%state` / `%flags`)
  - `TURN` (8 / `%turn` / `step`)
  - `BOUND` (9 / `%bound` / `limit`)
  - `FROM` (10 / `%from` / `input`)
  - `INTO` (11 / `%into` / `output`)
  - `DISCARD` (12 / `%discard` / `void`)
- **Word64 Synthesis**: Packs 32 trits payload, QuadState status, Polarity, Boundary rank, and a 7-bit checksum into a single 64-bit machine word.

3.2 Lowering Pipelines (`lowering/`)

- **`roll.rs`**: Validates delimiter boundary nesting (`[`, `{`, `<`) via [`OmniDebugger`], assigns concrete RAM partition offsets (`@ 0x0000`), binds agentic pronouns, and maps SVO action verbs (`INSCRIBE`, `TRANSDUCE`, `PROJECT`, `SEQUENCE`) to hardware opcodes.
- **`tape.rs`**: Iterates through procedural rolls, carving memory partitions according to Tape Head covenants and validating that final execution commits in `+1:PROCEED`.
- **`omni.rs`**: Parses multi-block spatial `.omni` files, extracts metadata and block structure, and lowers declarations into executable silicon tapes.

3.3 Multi-Target Transpilers (`transpiler/`)

- **Listing & Dumps (`listing.rs`)**: Emits formatted assembly tables and silicon hex word streams.
- **Tooling ASTs (`json.rs`)**: Emits structured JSON payloads containing symbol tables and instruction metadata for language servers and IDE hovercards.
- **Format Transduction (`omni.rs`)**: Converts procedural `.tape` files into declarative 4-Block `.omni` reels and vice versa.
- **Bare-Metal OS (`baremetal.rs`)**: Generates 16-bit Real Mode MBR boot sectors and 32-bit Multiboot ELF source code targeting MilleniumOS on physical x86 or QEMU hypervisors.

3.4 Core Coordinator (`core.rs`)

- **`OmniAssembler`**: Encapsulates [`DiagnosticLogger`], [`OmniDebugger`], and candidate search paths (`lexicon/`, `lib/`).
- **`assemble_file`**: Universal filesystem entry point that detects `.tape` or `.omni` extensions and directs execution to the appropriate lowering pipeline.
- **Verification Tests**: Houses 9 regression oracles proving the integrity of the entire modular system.

---

4. The Physical Baton Pass Contract

```mermaid
graph TD
    A["Source File (.tape / .omni)"] --> B["OmniAssembler::assemble_file"]
    B --> C{"File Extension"}
    C -->|tape| D["assemble_tape"]
    C -->|omni| E["assemble_omni"]
    D --> F["assemble_roll (per statement)"]
    E --> F
    F --> G["OmniDebugger (Delimiter Stack Invariant)"]
    G --> H["Symbol & Memory Partition Allocator (@ offset)"]
    H --> I["Word64 Balanced-Ternary Packaging"]
    I --> J["AssembledTape (+1:PROCEED Covenant Seal)"]
    J --> K["Downstream VM / QEMU / Transpiler Emission"]
```

```
## 5. Architectural Invariants

1. **Deterministic Memory Offsets**: Every concrete entity (`-`) receives a deterministic cell index within its partition, beginning at `@ 0x0000`.
2. **Boundary Closure**: Unmatched or leaking brackets (`[`, `{`, `<`) trigger immediate failpoints before any machine code is emitted.
3. **Covenant Affirmation**: Execution tapes must commit in `+1:PROCEED`; unsealed or ambiguous tapes are rejected.
4. **Universal Transduction**: All three triad representations (`.tape`, `.omni`, `Word64`) remain strictly isomorphic and bidirectionally convertible without information loss.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/core.rs RS 529 LINES 2197 WORDS 26.2 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Physical Assembler Core Coordinator, Lifecycle & Hardware Invariants )
// ============================================================================
//! OmniCode Runtime: Physical Assembler Core Coordinator
//!
//! # Architectural Scope & Purpose:
//! Encapsulates the main [`OmniAssembler`] coordinator struct:
//! 1. Telemetry and failpoint recording via [`DiagnosticLogger`].
//! 2. Structural boundary invariant enforcement via [`OmniDebugger`].
//! 3. Probing candidate lexicon search paths (`lexicon/`, `lib/`).
//! 4. High-level file-based assembly entry points (`assemble_file`).
//! 5. Transpilation convenience wrappers (`transpile_omni_source_to_tape`, `transpile_omni_source_to_asm`).
//! 6. Comprehensive unit test oracles covering all 13 hardware registers, SVO lowering, and 28 lexicon tapes.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of physical machine code onto bounded hardware substrates).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The inviolable preservation of historical silicon addresses, MMIO ports, and opcodes).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Silicon Truth**: Coordinates all memory allocation, register binding, and machine word packaging.
//! 2. **Baton Pass**: Connects callers (CLI, REPL, JIT) to lowered silicon layouts and bare-metal emitters.
// ============================================================================

use std::path::{Path, PathBuf};

use crate::core::tape::Tape;
use crate::diagnostics::debugger::OmniDebugger;
use crate::diagnostics::logger::DiagnosticLogger;
use crate::runtime::assembler::transpiler::baremetal::transpile_tape_to_asm;
use crate::runtime::assembler::transpiler::omni::transpile_omni_to_tape;
use crate::runtime::assembler::universal::types::AssembledTape;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( OmniAssembler Coordinator Struct & Constructor )
// ============================================================================

/// Encapsulates the runtime diagnostic logger, boundary invariant debugger ([`OmniDebugger`]),
/// and candidate lexicon search paths required to resolve and lower ontological symbols into silicon memory.
#[derive(Debug, Clone)]
pub struct OmniAssembler {
    /// Attached telemetry and error interception logger.
    pub logger: DiagnosticLogger,
    /// Delimiter boundary stack tracking engine for structural invariants (`[...]`, `<...>`).
    pub debugger: OmniDebugger,
    /// Candidate filesystem search directories for modular lexicon resolution.
    pub lexicon_paths: Vec<PathBuf>,
}

impl OmniAssembler {
    /// Constructs a new physical silicon assembler bound to the given diagnostic logger and debugger.
    ///
    /// Automatically probes standard candidate lexicon and library paths (`lexicon/`, `lib/`)
    /// to support cross-track ontological symbol resolution.
    pub fn new(logger: DiagnosticLogger, debugger: OmniDebugger) -> Self {
        let mut lexicon_paths = Vec::new();
        let candidate_dirs = ["lexicon", "lib"];
        for dir in &candidate_dirs {
            let p = PathBuf::from(dir);
            if p.exists() {
                lexicon_paths.push(p);
            }
        }
        Self {
```

```
            logger,
            debugger,
            lexicon_paths,
        }
    }

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( High-Level Assembly & Transpilation Execution Pipelines )
// ============================================================================

    /// Transpiles a raw declarative .omni string directly into an executable .tape string.
    pub fn transpile_omni_source_to_tape(&mut self, source: &str) -> Result<String, String> {
        let assembled = self.assemble_omni(source)?;
        Ok(transpile_omni_to_tape(&assembled))
    }

    /// Transpiles a raw declarative .omni string directly into bare-metal x86 bootstrap assembly (`.asm`).
    pub fn transpile_omni_source_to_asm(&mut self, source: &str) -> Result<String, String> {
        let assembled = self.assemble_omni(source)?;
        Ok(transpile_tape_to_asm(&assembled))
    }

    /// Assembles a .tape or .omni file directly from disk.
    pub fn assemble_file(&mut self, path: impl AsRef<Path>) -> Result<AssembledTape, String> {
        let p = path.as_ref();
        let ext = p.extension().and_then(|e| e.to_str()).unwrap_or("");
        match ext {
            "tape" => {
                let tape = Tape::from_file(p, self.logger.clone())?;
                self.assemble_tape(&tape)
            }
            "omni" => {
                let source = std::fs::read_to_string(p)
                    .map_err(|e| format!("Failed to read .omni file '{}': {e}", p.display()))?;
                self.assemble_omni(&source)
            }
            other => Err(format!(
                "Unsupported file extension '.{}' for '{}' (expected .tape or .omni)",
                other, p.display()
            )),
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Baton Pass Contract, Invariant Verification Proofs & Unit Oracles )
// ============================================================================

// ----------------------------------------------------------------------------
// 4.1. The Physical Baton Pass Contract
// ----------------------------------------------------------------------------
// BATON PASS CONTRACT:
// 1. INPUT INGESTION: `OmniAssembler::assemble_file` or `assemble_tape` ingests high-level
//    procedural tapes (`.tape`) or spatial reels (`.omni`) from callers (CLI, REPL, JIT).
// 2. ATOMIC LOWERING: `assemble_roll` tokenizes each statement, asserts boundary integrity via
//    `OmniDebugger`, resolves polarities (`+` abstract vs `-` concrete), assigns physical memory
//    partition offsets (`@ 0x0000`), binds agentic pronouns to hardware CPU registers (`%self`,
//    `%caller`, `%acc`, `%swarm`), and packs 64-bit balanced-ternary machine words (`Word64`).
// 3. INVARIANT & SEAL CERTIFICATION: The tape head covenant and commit status are evaluated,
//    guaranteeing that execution only seals in affirmative `+1:PROCEED`.
// 4. OUTPUT ARTIFACT SYNTHESIS: `AssembledTape` provides universal emission methods (`format_listing`,
//    `format_words`, `format_json`, `format_omni`, `to_machine_words`).
// 5. BATON HANDOFF: The resulting `AssembledTape` or `Vec<Word64>` is handed off to downstream
//    virtual machine runners, the QEMU bare-metal hypervisor, or CLI output serializers.

#[cfg(test)]
mod tests {
    use super::*;
    use std::collections::HashMap;
    use crate::core::tape::Roll;
    use crate::core::ternary::QuadState;
    use crate::runtime::assembler::universal::isa::{MachineOp, MachineRegister};

    /// Test 1: Verifies that the physical assembler lowers living world ontological tapes,
    /// synthesizing concrete memory cell offsets and affirmative PROCEED commit status.
    #[test]
```

```
    fn test_assembler_lowers_living_world_tape() {
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 100);
        let mut asm = OmniAssembler::new(logger, debugger);

        let path = crate::core::filetype::resolve_track_path("lexicon/01_nouns/living_world.tape");
        if path.exists() {
            let assembled = asm.assemble_file(&path).expect("Assembling living_world.tape");
            assert_eq!(assembled.head.name, "LivingWorldInstantiation");
            assert!(assembled.symbols.contains_key("Dog"));
            assert_eq!(assembled.commit_status, QuadState::Proceed);
            let listing = assembled.format_listing();
            assert!(listing.contains("ASSEMBLED MACHINE TAPE"));
            assert!(listing.contains("Dog"));
        }
    }

    /// Test 2: Verifies polarity transformation Lowering (`+Archetype --> Concrete-`).
    /// Ensures that abstract entities register in the symbol table with Abstract polarity,
    /// and concrete entities receive designated silicon memory cells.
    #[test]
    fn test_assembler_lowers_polarity_tape() {
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 100);
        let mut asm = OmniAssembler::new(logger, debugger);

        let path = crate::core::filetype::resolve_track_path("lexicon/operators/polarity.tape");
        if path.exists() {
            let assembled = asm.assemble_file(&path).expect("Assembling polarity.tape");
            assert_eq!(assembled.head.name, "PolarityTransformation");
            assert!(assembled.symbols.contains_key("Archetype"));
            assert!(assembled.symbols.contains_key("Concrete"));
            assert_eq!(assembled.commit_status, QuadState::Proceed);
        }
    }

    /// Test 3: Exhaustive regression oracle across the entire modular Track 2 Lexicon.
    /// Assembles all 30 foundational grammar and kernel tapes, asserting that every single
    /// tape seals with affirmative `+1:PROCEED` without unhandled delimiter or syntax errors.
    #[test]
    fn test_assembler_lowers_all_modular_lexicon_tapes() {
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 100);
        let mut asm = OmniAssembler::new(logger, debugger);

        let tape_paths = [
            "lexicon/operators/polarity.tape",
            "lexicon/operators/casting.tape",
            "lexicon/01_nouns/atomic_units.tape",
            "lexicon/01_nouns/vessels.tape",
            "lexicon/01_nouns/agents.tape",
            "lexicon/01_nouns/living_world.tape",
            "lexicon/02_pronouns/self_handles.tape",
            "lexicon/02_pronouns/wildcards.tape",
            "lexicon/03_verbs/axial_vectors.tape",
            "lexicon/03_verbs/scale_vectors.tape",
            "lexicon/03_verbs/diagonal_vectors.tape",
            "lexicon/03_verbs/relational_being.tape",
            "lexicon/03_verbs/arithmetic_verbs.tape",
            "lexicon/04_adjectives/quad_states.tape",
            "lexicon/04_adjectives/invariant_axioms.tape",
            "lexicon/04_adjectives/proportions.tape",
            "lexicon/05_adverbs/negation.tape",
            "lexicon/05_adverbs/cadence_policies.tape",
            "lexicon/06_prepositions/spatial_sites.tape",
            "lexicon/06_prepositions/ranges.tape",
            "lexicon/07_conjunctions/inseparable_pairs.tape",
            "lexicon/07_conjunctions/pipeline_junctions.tape",
            "lexicon/07_conjunctions/caveat_branches.tape",
            "lexicon/07_conjunctions/alternative_branches.tape",
            "lexicon/07_conjunctions/relational_attributions.tape",
            "lexicon/08_interjections/kernel_traps.tape",
            "lexicon/08_interjections/teleology_asides.tape",
            "lexicon/03_verbs/cinematic_track_loop.tape",
            "lexicon/operators/boot_kernel.tape",
            "lib/kernel/boot.tape",
        ];

```

```
        for path_str in &tape_paths {
            let path = crate::core::filetype::resolve_track_path(path_str);
            assert!(path.exists(), "Tape file does not exist: {}", path_str);
            let assembled = asm.assemble_file(&path).unwrap_or_else(|e| panic!("Failed to assemble {}: {}", path_str,
e));
            assert_eq!(assembled.commit_status, QuadState::Proceed, "Tape {} did not commit in PROCEED", path_str);
            assert!(!assembled.instructions.is_empty(), "Tape {} had no instructions", path_str);
        }
    }

    /// Test 4: Verifies grammatical pronoun lowering into physical hardware CPU registers.
    /// Asserts that self-handles (`self`) map to `%self` (Register 4), wildcards and
    /// antecedents (`it`) map to `%acc` (Register 3), and callers map to `%caller`.
    #[test]
    fn test_assembler_lowers_pronouns_and_registers() {
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 100);
        let mut asm = OmniAssembler::new(logger, debugger);

        let path = crate::core::filetype::resolve_track_path("lexicon/02_pronouns/self_handles.tape");
        if path.exists() {
            let assembled = asm.assemble_file(&path).expect("Assembling self_handles.tape");
            let self_roll = assembled.instructions.iter().find(|i| i.original_text.contains("self"));
            assert!(self_roll.is_some(), "Expected self roll in instructions");
            assert_eq!(self_roll.unwrap().register, Some(MachineRegister::SELF));
        }

        let wild_path = crate::core::filetype::resolve_track_path("lexicon/02_pronouns/wildcards.tape");
        if wild_path.exists() {
            let assembled = asm.assemble_file(&wild_path).expect("Assembling wildcards.tape");
            let it_roll = assembled.instructions.iter().find(|i| i.original_text.contains("it"));
            assert!(it_roll.is_some(), "Expected it roll in instructions");
            assert_eq!(it_roll.unwrap().register, Some(MachineRegister::ACC));
        }
    }

    /// Test 5: Verifies universal serialization methods on `AssembledTape`.
    /// Validates `format_words()` (physical silicon hex dump), `format_json()` (IDE/tooling AST),
    /// and `format_omni()` (decompilation/transpilation into declarative 4-Block spatial reels).
    #[test]
    fn test_assembler_universal_formatting_methods() {
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 100);
        let mut asm = OmniAssembler::new(logger, debugger);

        let path = crate::core::filetype::resolve_track_path("lib/kernel/boot.tape");
        if path.exists() {
            let assembled = asm.assemble_file(&path).expect("Assembling boot.tape");

            // 1. Format Words
            let words_dump = assembled.format_words();
            assert!(words_dump.contains("PHYSICAL SILICON WORD STREAM"));
            assert!(words_dump.contains("TOTAL WORDS:"));

            // 2. Format JSON
            let json_dump = assembled.format_json();
            assert!(json_dump.contains("\"tape\":"));
            assert!(json_dump.contains("\"symbols\":"));
            assert!(json_dump.contains("\"instructions\":"));

            // 3. Format Omni (Transpilation)
            let omni_dump = assembled.format_omni();
            assert!(omni_dump.contains("BLOCK 1: METADATA BLOCK"));
            assert!(omni_dump.contains("BLOCK 2: OPENING BLOCK"));
            assert!(omni_dump.contains("BLOCK 3: BODY BLOCK"));
            assert!(omni_dump.contains("BLOCK 4: CLOSING BLOCK"));
            assert!(omni_dump.contains("commit_status [ PROCEED ]"));
        }
    }

    /// Test 6: Verifies declarative `.omni` spatial reel lowering into physical machine layout.
    /// Confirms that `assemble_omni` correctly parses multi-block `.omni` code, constructs
    /// the symbol table and instruction stream, and verifies the Closing block seal.
    #[test]
    fn test_assembler_lowers_declarative_omni_reel() {
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 100);
        let mut asm = OmniAssembler::new(logger, debugger);
```

```
308
309         let path = crate::core::filetype::resolve_track_path("lexicon/03_verbs/axial_vectors.omni");
310         if path.exists() {
311             let assembled = asm.assemble_file(&path).expect("Assembling axial_vectors.omni");
312             assert_eq!(assembled.commit_status, QuadState::Proceed);
313             assert!(!assembled.instructions.is_empty(), "Must produce instruction stream");
314             assert_eq!(assembled.head.who, "OmniAssembler");
315         }
316     }
317
318     /// Test 7: Verifies standalone atomic single-roll lowering via `assemble_roll`.
319     /// Confirms that an individual roll can be lowered outside of a Tape container,
320     /// correctly allocating memory partition offsets and updating the physical symbol table.
321     #[test]
322     fn test_assembler_assemble_roll_standalone() {
323         let logger = DiagnosticLogger::new(false);
324         let debugger = OmniDebugger::new(logger.clone(), 100);
325         let mut asm = OmniAssembler::new(logger, debugger);
326
327         let roll = Roll {
328             index: 1,
329             line_number: 10,
330             text: "roll_1 [ +Memory --> Memory- @ 0 ]".to_string(),
331             status: QuadState::Proceed,
332             is_head: false,
333         };
334
335         let mut symbols = HashMap::new();
336         let mut next_offset = 0;
337         let mut commit_status = QuadState::Await;
338
339         let inst = asm.assemble_roll(
340             &roll,
341             0,
342             "TestPartition",
343             &mut symbols,
344             &mut next_offset,
345             &mut commit_status,
346         ).expect("Assembling standalone roll");
347
348         assert_eq!(inst.op, MachineOp::AllocConcrete);
349         assert!(symbols.contains_key("Memory"));
350         assert_eq!(symbols["Memory"].offset, Some(0));
351         assert_ne!(inst.word.raw, 0xFFFFFFFF_FFFFFFFF);
352     }
353
354     /// Test 8: Verifies full coverage of all 13 Named Silicon Registers,
355     /// backward-compatible aliases, ALL CAPS and lowercase duality, affix handling,
356     /// and dynamic roll register binding.
357     #[test]
358     fn test_named_silicon_registers_coverage() {
359         let registers = [
360             (MachineRegister::HEAD, 0, "HEAD", "%head"),
361             (MachineRegister::HOME, 1, "HOME", "%home"),
362             (MachineRegister::SPOOL, 2, "SPOOL", "%spool"),
363             (MachineRegister::IT, 3, "IT", "%it"),
364             (MachineRegister::SELF, 4, "SELF", "%self"),
365             (MachineRegister::CALLER, 5, "CALLER", "%caller"),
366             (MachineRegister::OTHER, 6, "OTHER", "%other"),
367             (MachineRegister::STATE, 7, "STATE", "%state"),
368             (MachineRegister::TURN, 8, "TURN", "%turn"),
369             (MachineRegister::BOUND, 9, "BOUND", "%bound"),
370             (MachineRegister::FROM, 10, "FROM", "%from"),
371             (MachineRegister::INTO, 11, "INTO", "%into"),
372             (MachineRegister::DISCARD, 12, "DISCARD", "%discard"),
373         ];
374
375         for (reg, expected_idx, expected_hw, expected_name) in registers {
376             assert_eq!(reg.index(), expected_idx);
377             assert_eq!(reg.hardware_name(), expected_hw);
378             assert_eq!(reg.name(), expected_name);
379             assert_eq!(MachineRegister::from_name(expected_hw), Some(reg));
380             assert_eq!(MachineRegister::from_name(&expected_hw.to_lowercase()), Some(reg));
381             assert_eq!(MachineRegister::from_name(&format!("%{}", expected_hw.to_lowercase())), Some(reg));
382             assert_eq!(MachineRegister::from_name(&format!("+{}", expected_hw)), Some(reg));
383             assert_eq!(MachineRegister::from_name(&format!("-{}", expected_hw)), Some(reg));
384         }
385
```

```
        // Backward compatibility constants
        assert_eq!(MachineRegister::IP, MachineRegister::HEAD);
        assert_eq!(MachineRegister::FP, MachineRegister::HOME);
        assert_eq!(MachineRegister::SP, MachineRegister::SPOOL);
        assert_eq!(MachineRegister::ACC, MachineRegister::IT);
        assert_eq!(MachineRegister::FLAGS, MachineRegister::STATE);
        assert_eq!(MachineRegister::HERE, MachineRegister::HEAD);
        assert_eq!(MachineRegister::ORIGIN, MachineRegister::HOME);
        assert_eq!(MachineRegister::OWNER, MachineRegister::SPOOL);
        assert_eq!(MachineRegister::SWARM, MachineRegister::OTHER);
        assert_eq!(MachineRegister::STEP, MachineRegister::TURN);
        assert_eq!(MachineRegister::INPUT, MachineRegister::FROM);
        assert_eq!(MachineRegister::OUTPUT, MachineRegister::INTO);

        // Natural, positional, and shorthand aliases
        assert_eq!(MachineRegister::from_name("ip"), Some(MachineRegister::HEAD));
        assert_eq!(MachineRegister::from_name("here"), Some(MachineRegister::HEAD));
        assert_eq!(MachineRegister::from_name("origin"), Some(MachineRegister::HOME));
        assert_eq!(MachineRegister::from_name("spool"), Some(MachineRegister::SPOOL));
        assert_eq!(MachineRegister::from_name("owner"), Some(MachineRegister::SPOOL));
        assert_eq!(MachineRegister::from_name("turn"), Some(MachineRegister::TURN));
        assert_eq!(MachineRegister::from_name("step"), Some(MachineRegister::TURN));
        assert_eq!(MachineRegister::from_name("bound"), Some(MachineRegister::BOUND));
        assert_eq!(MachineRegister::from_name("from"), Some(MachineRegister::FROM));
        assert_eq!(MachineRegister::from_name("input"), Some(MachineRegister::FROM));
        assert_eq!(MachineRegister::from_name("into"), Some(MachineRegister::INTO));
        assert_eq!(MachineRegister::from_name("output"), Some(MachineRegister::INTO));
        assert_eq!(MachineRegister::from_name("_"), Some(MachineRegister::DISCARD));
        assert_eq!(MachineRegister::from_name("void"), Some(MachineRegister::DISCARD));

        // Verify that assemble_roll binds Named Silicon Registers directly
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 100);
        let mut asm = OmniAssembler::new(logger, debugger);

        let roll_turn = Roll {
            index: 1,
            line_number: 1,
            text: "roll_turn [ TURN plus 1 --> TURN ]".to_string(),
            status: QuadState::Proceed,
            is_head: false,
        };
        let mut syms = HashMap::new();
        let mut off = 0;
        let mut commit = QuadState::Await;
        let inst_turn = asm.assemble_roll(&roll_turn, 0, "Part", &mut syms, &mut off, &mut commit).expect("Assemble
TURN");
        assert_eq!(inst_turn.register, Some(MachineRegister::TURN));

        let roll_bound = Roll {
            index: 2,
            line_number: 2,
            text: "roll_bound [ BOUND ]".to_string(),
            status: QuadState::Proceed,
            is_head: false,
        };
        let inst_bound = asm.assemble_roll(&roll_bound, 1, "Part", &mut syms, &mut off, &mut commit).expect("Assemble
BOUND");
        assert_eq!(inst_bound.register, Some(MachineRegister::BOUND));
    }

    /// Test 9: Verifies SVO action verbs (INSCRIBE, TRANSDUCE, PROJECT, SEQUENCE),
    /// bijective Radix-3 equivalence (<=>), and MMIO port lowering for Character tapes.
    #[test]
    fn test_character_tape_svo_lowering_and_equivalence() {
        let logger = DiagnosticLogger::new(false);
        let debugger = OmniDebugger::new(logger.clone(), 100);
        let mut asm = OmniAssembler::new(logger, debugger);
        let mut syms = HashMap::new();
        let mut off = 0;
        let mut commit = QuadState::Await;

        // 1. ROLL 1: INSCRIBE verb -> AllocConcrete / INSCRIBE_CELL
        let roll1 = Roll {
            index: 1,
            line_number: 1,
            text: "[ ROLL 1 ] : [ Inscribe ] : { Glyph } --> INSCRIBE [ Cell ] = [ Character` ]".to_string(),
            status: QuadState::Proceed,
```

```
            is_head: false,
        };
        let inst1 = asm.assemble_roll(&roll1, 0, "CharacterTape", &mut syms, &mut off, &mut commit).expect("Assemble ROLL
1");
        assert_eq!(inst1.op_code, "INSCRIBE_CELL");
        assert_eq!(inst1.op, MachineOp::AllocConcrete);

        // 2. ROLL 2: Bijective equivalence <=> and TRANSDUCE verb -> TransduceVector / TRANSDUCE_SUBSTRATE
        let roll2 = Roll {
            index: 2,
            line_number: 2,
            text: "[ ROLL 2 ] : [ Transduce ] : [ Transducer ]: [ Character` { 8 Bits } ] <=> TRANSDUCE [ Cell` { 5 Trits
} ]".to_string(),
            status: QuadState::Proceed,
            is_head: false,
        };
        let inst2 = asm.assemble_roll(&roll2, 1, "CharacterTape", &mut syms, &mut off, &mut commit).expect("Assemble ROLL
2");
        assert_eq!(inst2.op_code, "TRANSDUCE_SUBSTRATE");
        assert_eq!(inst2.op, MachineOp::TransduceVector);

        // 3. ROLL 4: PROJECT verb and Target -> TransduceVector / PROJECT_TARGET with register INTO
        let roll4 = Roll {
            index: 4,
            line_number: 4,
            text: "[ ROLL 4 ] : [ Project ] : [ Character` } --> PROJECT [ Target ] = [ Target` }".to_string(),
            status: QuadState::Proceed,
            is_head: false,
        };
        let inst4 = asm.assemble_roll(&roll4, 3, "CharacterTape", &mut syms, &mut off, &mut commit).expect("Assemble ROLL
4");
        assert_eq!(inst4.op_code, "PROJECT_TARGET");
        assert_eq!(inst4.op, MachineOp::TransduceVector);
        assert_eq!(inst4.register, Some(MachineRegister::INTO));

        // 4. ROLL 5: SEQUENCE verb -> BindChannel / SEQUENCE_TRANSITION
        let roll5 = Roll {
            index: 5,
            line_number: 5,
            text: "[ ROLL 5 ] : [ Sequence ] : [ Character` } --> SEQUENCE [ Text ] = [ Text` ]".to_string(),
            status: QuadState::Proceed,
            is_head: false,
        };
        let inst5 = asm.assemble_roll(&roll5, 4, "CharacterTape", &mut syms, &mut off, &mut commit).expect("Assemble ROLL
5");
        assert_eq!(inst5.op_code, "SEQUENCE_TRANSITION");
        assert_eq!(inst5.op, MachineOp::BindChannel);

        // 5. MMIO addresses: FROM ::@ 0x03F8 and INTO ::@ 0x000B8000
        let roll_uart = Roll {
            index: 6,
            line_number: 6,
            text: "[ COM1 ] : FROM ::@ 0x03F8".to_string(),
            status: QuadState::Proceed,
            is_head: false,
        };
        let inst_uart = asm.assemble_roll(&roll_uart, 5, "CharacterTape", &mut syms, &mut off, &mut
commit).expect("Assemble UART");
        assert_eq!(inst_uart.address, Some(0x03F8));
        assert_eq!(inst_uart.register, Some(MachineRegister::FROM));

        let roll_vga = Roll {
            index: 7,
            line_number: 7,
            text: "[ VGA ] : INTO ::@ 0x000B8000".to_string(),
            status: QuadState::Proceed,
            is_head: false,
        };
        let inst_vga = asm.assemble_roll(&roll_vga, 6, "CharacterTape", &mut syms, &mut off, &mut
commit).expect("Assemble VGA");
        assert_eq!(inst_vga.address, Some(0x000B8000));
        assert_eq!(inst_vga.register, Some(MachineRegister::INTO));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/mod.rs RS | 94 LINES | 474 WORDS | 4.3 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Physical Assembler Subsystem Identity, Public Facade & Architectural Invariants )
// ============================================================================
//! OmniCode Runtime: Physical Assembler Subsystem Facade
//!
//! # Architectural Scope & Purpose:
//! The Physical Assembler acts as the transduction engine between abstract
//! ontological archetypes (`+`) and concrete silicon memory layouts (`-`).
//! It decomposes into four discrete domain modules:
//! 1. `universal`: Stateless hardware instruction set architecture ([`MachineOp`]),
//!    named physical registers ([`MachineRegister`]), 64-bit balanced-ternary machine word
//!    synthesis ([`synthesize_machine_word`]), and core data containers ([`PhysicalSymbol`], [`AssembledTape`]).
//! 2. `lowering`: Procedural `.tape` and declarative `.omni` statement compilation,
//!    memory partition allocation (`@ 0x0000`), hardware register binding, and delimiter stack validation.
//! 3. `transpiler`: Multi-target code emission (annotated assembly listings, silicon hex words,
//!    IDE hovercard JSON ASTs, bidirectional `.tape` <-> `.omni` conversion, 16-bit Real Mode MBR bootloader,
//!    and 32-bit Multiboot ELF assembly).
//! 4. `core`: Main [`OmniAssembler`] coordinator struct, lifecycle methods, and comprehensive test suite.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of physical machine code onto bounded hardware substrates).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The inviolable preservation of historical silicon addresses, MMIO ports, and opcodes).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Complete Compatibility**: Re-exports all universal ISA definitions, memory symbols,
//!    transpilers, and the coordinator struct to preserve 100% backward compatibility for all callers.
// ============================================================================

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Module Hierarchy Declarations & Public Facade Exports )
// ============================================================================
pub mod universal;
pub mod lowering;
pub mod transpiler;
pub mod core;

// Re-export universal ISA opcodes, registers, and symbols
pub use universal::{
    MachineOp,
    MachineRegister,
    PhysicalSymbol,
    AssembledInstruction,
    AssembledTape,
    DEFAULT_PARTITION_CELL_CAPACITY,
    DEFAULT_ASSEMBLER_DEBUGGER_DEPTH,
    pronoun_to_register,
    pronoun_to_op,
    polarity_to_op,
    compute_word_checksum,
    synthesize_machine_word,
};

// Re-export transpilers and formatters
pub use transpiler::{
    format_assembly_listing,
    format_silicon_words,
    format_tape_json,
    transpile_tape_to_omni,
    transpile_omni_to_tape,
    transpile_tape_to_asm,
    transpile_tape_to_multiboot_asm,
    transpile_omni_to_asm,
    transpile_tape_to_c,
```

```
    transpile_tape_to_lua,
};

// Re-export main coordinator struct
pub use core::OmniAssembler;

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Proofs & Invariants )
// ================================================================================
// The Assembler subsystem enforces structural delimiter closure via `OmniDebugger`,
// allocates memory offsets deterministically within storehouse partitions,
// and guarantees that all compiled tapes seal in affirmative `+1:PROCEED`.

// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Module Closure )
// ================================================================================
// Physical Assembler Subsystem facade verified and sealed in affirmative PROCEED.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/lowering/mod.rs

RS | 46 LINES | 276 WORDS | 2.4 KB

```rust
// ========================================================================
// BLOCK 1: METADATA BLOCK
// ( Lowering Subsystem Identity, Invariants & Scripture Anchors )
// ========================================================================
//! OmniCode Runtime: Assembler Lowering Subsystem
//!
//! Provides the AST and tape statement lowering pipelines:
//! - `roll`: Lowers atomic procedural roll statements into physical `AssembledInstruction`s.
//! - `tape`: Lowers entire procedural `.tape` process ribbons into `AssembledTape`.
//! - `omni`: Lowers declarative 4-Block `.omni` spatial architecture reels into `AssembledTape`.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of physical machine code onto bounded hardware substrates).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic roll lowering invariants before constructing system tapes).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The inviolable preservation of historical silicon addresses, MMIO ports, and opcodes).
// ========================================================================

// ========================================================================
// BLOCK 2: OPENING BLOCK
// ( Module Declarations for Lowering Subsystems )
// ========================================================================
pub mod roll;
pub mod tape;
pub mod omni;

// ========================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Proofs & Lowering Invariants )
// ========================================================================
// Lowering methods (`assemble_roll`, `assemble_tape`, `assemble_omni`) are attached
// directly to `OmniAssembler` within their respective domain modules.

// ========================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Module Closure )
// ========================================================================
// Lowering module sealed in affirmative PROCEED.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/lowering/omni.rs

RS | 227 LINES | 834 WORDS | 10.2 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Declarative 4-Block Spatial Reel Lowering Engine & Symbol Allocation )
// ============================================================================
//! OmniCode Runtime: Declarative Omni Reel Lowering
//!
//! # Architectural Scope & Purpose:
//! Lowers a declarative 4-Block spatial architecture reel (`.omni`) into physical
//! machine layout:
//! 1. Tokenizes and validates boundary AST physics via [`Lexer`] and [`Parser`].
//! 2. Extracts `Module` or `Manifest` identity and creates a virtual `TapeHead`.
//! 3. Synthesizes physical symbol records (`PhysicalSymbol`) from architectural definitions.
//! 4. Lowers operational lines into machine words ([`Word64`]).
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
// ============================================================================

use std::collections::HashMap;

use crate::core::operators::Polarity;
use crate::core::tape::{Roll, TapeHead};
use crate::core::ternary::QuadState;
use crate::diagnostics::logger::FailpointType;
use crate::parser::lexer::{Lexer, TokenType};
use crate::parser::parser::Parser;
use crate::runtime::assembler::core::OmniAssembler;
use crate::runtime::assembler::universal::types::{
    AssembledInstruction,
    AssembledTape,
    PhysicalSymbol,
};

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( assemble_omni Method Implementation )
// ============================================================================

impl OmniAssembler {
    /// Assembles a declarative 4-Block .omni spatial source reel into physical machine layout.
    pub fn assemble_omni(&mut self, source: &str) -> Result<AssembledTape, String> {
        let mut lexer = Lexer::new(source, self.logger.clone());
        let tokens = match lexer.tokenize() {
            Ok(t) => t,
            Err(e) => {
                self.logger.failpoint(FailpointType::SyntaxAnomaly, "ASSEMBLER", &e);
                return Err(format!("Omni lexical analysis error: {e}"));
            }
        };

        // Assert all boundary physics and construct AST
        let mut parser = Parser::new(tokens.clone(), self.debugger.clone());
        let _prog = match parser.parse_program() {
            Ok(p) => p,
            Err(e) => {
                self.logger.failpoint(FailpointType::SyntaxAnomaly, "ASSEMBLER", &e);
                return Err(format!("Omni program parse error: {e}"));
            }
        };

        // Extract module name from tokens or source
        let mut module_name = "OmniModule".to_string();
        for (i, tok) in tokens.iter().enumerate() {
```

```
            if let TokenType::Identifier(ref id) = tok.token_type {
                if id == "Module" || id == "Manifest" {
                    for lookahead in tokens.iter().skip(i + 1).take(5) {
                        if let TokenType::Identifier(ref name) = lookahead.token_type {
                            module_name = name.clone();
                            break;
                        }
                    }
                }
            }
        }

        // ========================================================================
        // BLOCK 3: BODY BLOCK
        // ( Symbol Table Construction & Instruction Roll Lowering )
        // ========================================================================
        let mut symbols: HashMap<String, PhysicalSymbol> = HashMap::new();
        let mut instructions: Vec<AssembledInstruction> = Vec::new();
        let mut next_available_offset: usize = 0;
        let mut commit_status = QuadState::Await;

        let mut line_index = 0;
        for (line_no, raw_line) in source.lines().enumerate() {
            let line = raw_line.trim();
            if line.is_empty() || line.starts_with('#') {
                continue;
            }
            if line == "Opening {" || line == "Body [" || line == "Closing {" || line == "}" || line == "]" {
                continue;
            }

            line_index += 1;
            let roll = Roll {
                index: line_index,
                line_number: line_no + 1,
                text: line.to_string(),
                status: QuadState::Proceed,
                is_head: false,
            };

            // Check if this line updates commit_status or contains entities
            let mut line_lexer = Lexer::new(line, self.logger.clone());
            if let Ok(line_toks) = line_lexer.tokenize() {
                let is_tripwire_line = line.starts_with("[ Tripwire ]") || line.starts_with("[Tripwire]");
                for (t_idx, tok) in line_toks.iter().enumerate() {
                    if !is_tripwire_line {
                        if let TokenType::Identifier(ref ident) = tok.token_type {
                            let is_commit_status = ident == "commit_status"
                                || (ident == "Commit" && line_toks.get(t_idx + 1).map_or(false, |next| {
                                    if let TokenType::Identifier(ref n) = next.token_type {
                                        n == "Status"
                                    } else {
                                        false
                                    }
                                }));
                            if is_commit_status {
                                let mut resolved = QuadState::Proceed;
                                for lookahead in line_toks.iter().skip(t_idx + 1) {
                                    match &lookahead.token_type {
                                        TokenType::Ternary(qs) => {
                                            resolved = *qs;
                                            break;
                                        }
                                        TokenType::AffixedIdent { name, .. } | TokenType::Identifier(name) => {
                                            let upper = name.to_uppercase();
                                            if upper.starts_with("PROCEED") {
                                                resolved = QuadState::Proceed;
                                                break;
                                            } else if upper.starts_with("ROLLBACK") {
                                                resolved = QuadState::Rollback;
                                                break;
                                            } else if upper.starts_with("AWAIT") {
                                                resolved = QuadState::Await;
                                                break;
                                            } else if upper.starts_with("HALT") {
                                                resolved = QuadState::Halt;
                                                break;
                                            }
```

```
                                        }
                                        _ => {}
                                    }
                                }
                                commit_status = resolved;
                            }
                        }
                    }

                    if let TokenType::AffixedIdent { name, polarity, .. } = &tok.token_type {
                        let off = if *polarity == Polarity::Concrete {
                            let o = next_available_offset;
                            next_available_offset += 1;
                            Some(o)
                        } else {
                            None
                        };
                        symbols.entry(name.clone()).or_insert_with(|| PhysicalSymbol {
                            name: name.clone(),
                            polarity: *polarity,
                            offset: off,
                            size_cells: 1,
                            partition_name: Some(module_name.clone()),
                        });
                    }
                }

                // If line can be lowered as a standalone roll, assemble it
                if let Ok(inst) = self.assemble_roll(
                    &roll,
                    instructions.len(),
                    &module_name,
                    &mut symbols,
                    &mut next_available_offset,
                    &mut commit_status,
                ) {
                    instructions.push(inst);
                }
            }
        }

        let head = TapeHead {
            name: module_name.clone(),
            who: "OmniAssembler".to_string(),
            what: "DeclarativeReel".to_string(),
            when_clause: "Compilation".to_string(),
            where_clause: module_name.clone(),
            why: "SpatialDeclarativeAssembly".to_string(),
            how: commit_status.macro_op().to_string(),
            required_partition_size: 64.max(next_available_offset),
            raw_text: format!("[Reel.{}]", module_name),
        };

        let partition_size = head.required_partition_size;

        self.logger.log(
            "ASSEMBLER",
            format!("Reel [{}] assembled: {} instructions, {} symbols", head.name, instructions.len(), symbols.len()),
        );

        Ok(AssembledTape {
            head,
            partition_size,
            symbols,
            instructions,
            commit_status,
        })
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status & Module Closure )
// ============================================================================
// Omni reel lowering engine verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/lowering/roll.rs

RS | 387 LINES | 1403 WORDS | 17.3 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Atomic Single-Roll Lowering Pipeline & Hardware Allocation Invariants )
// ============================================================================
//! OmniCode Runtime: Atomic Roll Lowering Engine
//!
//! # Architectural Scope & Purpose:
//! Lowers an atomic procedural roll statement into a physical `AssembledInstruction`:
//! 1. Delimiter boundary invariant enforcement via [`OmniDebugger`].
//! 2. Physical memory partition offset allocation (`@ 0x0000`, `next_available_offset`).
//! 3. Hardware CPU register binding (`%head`, `%it`, `%from`, `%into`, etc.).
//! 4. SVO action verb lowering (`INSCRIBE`, `TRANSDUCE`, `PROJECT`, `SEQUENCE`).
//! 5. Covenant commit status resolution (`commit_status [ PROCEED ]`).
//! 6. 64-bit balanced-ternary machine word synthesis ([`Word64`]).
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Silicon Lowering Precision**: Explicit mapping of SVO verbs and MMIO addresses
//!    guarantees consistent machine word generation across all execution targets.
// ============================================================================

use std::collections::HashMap;

use crate::core::boundaries::BoundaryType;
use crate::core::linguistics::PronounKind;
use crate::core::operators::Polarity;
use crate::core::tape::Roll;
use crate::core::ternary::QuadState;
use crate::diagnostics::logger::FailpointType;
use crate::parser::lexer::{Lexer, TokenType};
use crate::runtime::assembler::core::OmniAssembler;
use crate::runtime::assembler::universal::isa::{
    MachineOp,
    MachineRegister,
    pronoun_to_register,
    pronoun_to_op,
    polarity_to_op,
    synthesize_machine_word,
};
use crate::runtime::assembler::universal::types::{
    AssembledInstruction,
    PhysicalSymbol,
};

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( assemble_roll Function Signature & Initializer )
// ============================================================================

impl OmniAssembler {
    /// Lowers an atomic procedural roll into a physical `AssembledInstruction`,
    /// allocating memory partition offsets and hardware register bindings.
    pub fn assemble_roll(
        &mut self,
        roll: &Roll,
        idx: usize,
        where_clause: &str,
        symbols: &mut HashMap<String, PhysicalSymbol>,
        next_available_offset: &mut usize,
        commit_status: &mut QuadState,
    ) -> Result<AssembledInstruction, String> {
```

```
        let mut lexer = Lexer::new(&roll.text, self.logger.clone());
        let tokens = match lexer.tokenize() {
            Ok(t) => t,
            Err(e) => {
                self.logger.failpoint(FailpointType::SyntaxAnomaly, "ASSEMBLER", &e);
                return Err(format!("Roll {idx} assembly error: {e}"));
            }
        };

        let mut op = MachineOp::Nop;
        let mut assigned_reg = None;
        let mut inst_addr = None;
        let roll_status = QuadState::Proceed;
        let mut boundary_type = BoundaryType::Denotation;
        let mut polarity_type = Polarity::Concrete;
        let mut explicit_op_code: Option<String> = None;

        // ========================================================================
        // BLOCK 3: BODY BLOCK
        // ( 1. Invariant Boundary Stack, 2. Token Inspection & Lowering )
        // ========================================================================

        // 1. Enforce structural boundary invariants with OmniDebugger
        self.debugger.boundary_stack.clear();
        for tok in &tokens {
            match tok.token_type {
                TokenType::LBracket => self.debugger.push_boundary('[', tok.line, tok.col),
                TokenType::LBrace => self.debugger.push_boundary('{', tok.line, tok.col),
                TokenType::LAngle => self.debugger.push_boundary('<', tok.line, tok.col),
                TokenType::RBracket => {
                    if let Err(e) = self.debugger.pop_boundary(']', tok.line, tok.col) {
                        return Err(format!("Roll {idx} delimiter error: {e}"));
                    }
                }
                TokenType::RBrace => {
                    if let Err(e) = self.debugger.pop_boundary('}', tok.line, tok.col) {
                        return Err(format!("Roll {idx} delimiter error: {e}"));
                    }
                }
                TokenType::RAngle => {
                    if let Err(e) = self.debugger.pop_boundary('>', tok.line, tok.col) {
                        return Err(format!("Roll {idx} delimiter error: {e}"));
                    }
                }
                _ => {}
            }
        }
        if let Err(e) = self.debugger.assert_all_boundaries_closed() {
            return Err(format!("Roll {idx} boundary leak error: {e}"));
        }

        // 2. Inspect tokens for physical symbols, polarity, registers, and memory writes
        let mut explicit_offset = None;
        for (t_idx, tok) in tokens.iter().enumerate() {
            // Check for @ or ::@ offset locator
            if tok.token_type == TokenType::At || tok.is_hardware_locator() {
                if let Some(next_tok) = tokens.get(t_idx + 1) {
                    if let TokenType::Number(num) = next_tok.token_type {
                        explicit_offset = Some(num as usize);
                    }
                }
            }

            // Check for Affixed Identifiers
            if let TokenType::AffixedIdent { name, polarity, position: _ } = &tok.token_type {
                polarity_type = *polarity;
                let assigned_offset = if *polarity == Polarity::Concrete {
                    let off = explicit_offset.unwrap_or(*next_available_offset);
                    if explicit_offset.is_none() {
                        *next_available_offset += 1;
                    }
                    inst_addr = Some(off);
                    Some(off)
                } else {
                    None
                };

                if let Some(existing) = symbols.get_mut(name) {
```

```
                    if *polarity == Polarity::Concrete {
                        existing.polarity = Polarity::Concrete;
                        if assigned_offset.is_some() {
                            existing.offset = assigned_offset;
                        }
                    }
                } else {
                    symbols.insert(name.clone(), PhysicalSymbol {
                        name: name.clone(),
                        polarity: *polarity,
                        offset: assigned_offset,
                        size_cells: 1,
                        partition_name: Some(where_clause.to_string()),
                    });
                }

                op = polarity_to_op(*polarity);
                explicit_op_code = Some(match polarity {
                    Polarity::Abstract => format!("REF_ABSTRACT_{name}"),
                    Polarity::Concrete => format!("ALLOC_CONCRETE_{name}"),
                });
            }

            // Check for Grammatical Pronouns (Perspective, Identity, Ownership & Capability)
            if let TokenType::Pronoun(p) = tok.token_type {
                if let Some(reg) = pronoun_to_register(p) {
                    assigned_reg = Some(reg);
                }
                if let Some(pr_op) = pronoun_to_op(p) {
                    op = pr_op;
                }
                if p == PronounKind::I || p == PronounKind::Me || p == PronounKind::SelfHandle {
                    if op == MachineOp::Nop {
                        op = MachineOp::RefAbstract;
                    }
                } else if p == PronounKind::Wildcard {
                    explicit_op_code = Some("DISCARD_WILDCARD".to_string());
                }
            }

            // Check for Named Silicon Registers directly via Identifiers or Affixed Identifiers
            if assigned_reg.is_none() {
                match &tok.token_type {
                    TokenType::Identifier(ident) => {
                        if let Some(reg) = MachineRegister::from_name(ident) {
                            assigned_reg = Some(reg);
                        }
                    }
                    TokenType::AffixedIdent { name, .. } => {
                        if let Some(reg) = MachineRegister::from_name(name) {
                            assigned_reg = Some(reg);
                        }
                    }
                    _ => {}
                }
            }

            // Check for Freeform Boundary Casts: [+], [-], <+>, <->, {+}, {-}
            if let TokenType::BoundaryCast { boundary, polarity } = &tok.token_type {
                op = MachineOp::CastBoundary;
                boundary_type = *boundary;
                polarity_type = *polarity;
                explicit_op_code = Some(format!("CAST_{}_{}", boundary.rank_name().replace(' ', "_"),
polarity.symbol()));
            }

            if let TokenType::Identifier(ref ident) = tok.token_type {
                let is_tripwire_roll = tokens.first().map_or(false, |t| {
                    matches!(&t.token_type, TokenType::Identifier(id) if id.eq_ignore_ascii_case("Tripwire"))
                }) || tokens.get(1).map_or(false, |t| {
                    matches!(&t.token_type, TokenType::Identifier(id) if id.eq_ignore_ascii_case("Tripwire"))
                });

                let is_commit_status = !is_tripwire_roll && (ident == "commit_status"
                    || (ident == "Commit" && tokens.get(t_idx + 1).map_or(false, |next| {
                        if let TokenType::Identifier(ref n) = next.token_type {
                            n == "Status"
                        } else {
```

```
                            false
                        }
                    }));
                if is_commit_status {
                    op = MachineOp::SealCommit;
                    explicit_op_code = Some("SEAL_COMMIT".to_string());

                    let mut resolved_state = QuadState::Proceed;
                    for lookahead in tokens.iter().skip(t_idx + 1) {
                        match &lookahead.token_type {
                            TokenType::Ternary(qs) => {
                                resolved_state = *qs;
                                break;
                            }
                            TokenType::AffixedIdent { name, .. } => {
                                let upper = name.to_uppercase();
                                if upper.starts_with("PROCEED") {
                                    resolved_state = QuadState::Proceed;
                                    break;
                                } else if upper.starts_with("ROLLBACK") {
                                    resolved_state = QuadState::Rollback;
                                    break;
                                } else if upper.starts_with("AWAIT") {
                                    resolved_state = QuadState::Await;
                                    break;
                                } else if upper.starts_with("HALT") {
                                    resolved_state = QuadState::Halt;
                                    break;
                                }
                            }
                            TokenType::Identifier(id) => {
                                let upper = id.to_uppercase();
                                if upper.starts_with("PROCEED") {
                                    resolved_state = QuadState::Proceed;
                                    break;
                                } else if upper.starts_with("ROLLBACK") {
                                    resolved_state = QuadState::Rollback;
                                    break;
                                } else if upper.starts_with("AWAIT") {
                                    resolved_state = QuadState::Await;
                                    break;
                                } else if upper.starts_with("HALT") {
                                    resolved_state = QuadState::Halt;
                                    break;
                                }
                            }
                            _ => {}
                        }
                    }
                    *commit_status = resolved_state;
                }
            }

            // Check for Bijective Radix-3 Transduction Equivalence: <=>
            if tok.token_type == TokenType::InvariantEquivalence {
                op = MachineOp::TransduceVector;
                if explicit_op_code.is_none() {
                    explicit_op_code = Some("TRANSDUCE_EQUIVALENCE".to_string());
                }
            }

            // Check for SVO Action Verbs (Character & Object Lifecycle Transitions)
            if let TokenType::Identifier(ref ident) = tok.token_type {
                let upper = ident.to_uppercase();
                match upper.as_str() {
                    "INSCRIBE" => {
                        op = MachineOp::AllocConcrete;
                        if explicit_op_code.is_none() {
                            explicit_op_code = Some("INSCRIBE_CELL".to_string());
                        }
                    }
                    "TRANSDUCE" => {
                        op = MachineOp::TransduceVector;
                        if explicit_op_code.is_none() {
                            explicit_op_code = Some("TRANSDUCE_SUBSTRATE".to_string());
                        }
                    }
                    "PROJECT" => {
```

```
                        op = MachineOp::TransduceVector;
                        if explicit_op_code.is_none() {
                            explicit_op_code = Some("PROJECT_TARGET".to_string());
                        }
                        if assigned_reg.is_none() {
                            assigned_reg = Some(MachineRegister::INTO);
                        }
                    }
                    "SEQUENCE" => {
                        op = MachineOp::BindChannel;
                        if explicit_op_code.is_none() {
                            explicit_op_code = Some("SEQUENCE_TRANSITION".to_string());
                        }
                    }
                    _ => {}
                }
            }

            // Check for directional lowering: -->, v--
            if tok.token_type == TokenType::ActUpon {
                if op == MachineOp::Nop || op == MachineOp::RefAbstract {
                    op = MachineOp::TransduceVector;
                    if explicit_op_code.is_none() {
                        explicit_op_code = Some("TRANSDUCE_VECTOR".to_string());
                    }
                }
            } else if tok.token_type == TokenType::ActAgain {
                op = MachineOp::FeedbackVector;
            } else if tok.token_type == TokenType::BreaksDownFrom {
                op = MachineOp::PartitionSlice;
                explicit_op_code = Some("PARTITION_SLICE".to_string());
            } else if tok.token_type == TokenType::BuildsTo {
                op = MachineOp::SynthesizeLayer;
            } else if tok.token_type == TokenType::And {
                if op == MachineOp::Nop {
                    op = MachineOp::BindChannel;
                }
            } else if tok.token_type == TokenType::But {
                op = MachineOp::AssertInvariant;
            }
        }

        // Fallback for explicit physical MMIO offset if no AffixedIdent set it
        if explicit_offset.is_some() && inst_addr.is_none() {
            inst_addr = explicit_offset;
        }

        // Automatic register binding fallback for hardware MMIO ports
        if assigned_reg.is_none() {
            if let Some(addr) = inst_addr {
                if addr == 0x03F8 {
                    assigned_reg = Some(MachineRegister::FROM);
                } else if addr == 0x000B8000 || addr == 0x01 {
                    assigned_reg = Some(MachineRegister::INTO);
                }
            }
        }

        let op_code = explicit_op_code.unwrap_or_else(|| op.mnemonic().to_string());
        let word = synthesize_machine_word(idx, op, inst_addr, roll_status, polarity_type, boundary_type);

        Ok(AssembledInstruction {
            roll_index: idx + 1,
            source_line: roll.line_number,
            original_text: roll.text.clone(),
            op,
            register: assigned_reg,
            address: inst_addr,
            word,
            status: roll_status,
            op_code,
        })
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status & Module Closure )
```

```
// ================================================================================
// Roll lowering engine verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/lowering/tape.rs RS | 91 LINES | 378 WORDS | 3.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Procedural Process Ribbon Lowering Engine & Memory Partition Sizing )
// ============================================================================
//! OmniCode Runtime: Tape Process Ribbon Lowering
//!
//! # Architectural Scope & Purpose:
//! Lowers an entire temporal procedural process ribbon (`.tape`) into physical
//! silicon machine layout:
//! 1. Ingests the `TapeHead` covenant manifest.
//! 2. Allocates memory partition geometry and symbol tables across all rolls.
//! 3. Sequentially lowers instruction rolls into `Word64` containers.
//! 4. Validates final affirmative commit status (`commit_status`).
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
// ============================================================================

use std::collections::HashMap;

use crate::core::tape::Tape;
use crate::core::ternary::QuadState;
use crate::runtime::assembler::core::OmniAssembler;
use crate::runtime::assembler::universal::types::{
    AssembledInstruction,
    AssembledTape,
    PhysicalSymbol,
};

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( assemble_tape Method Implementation )
// ============================================================================

impl OmniAssembler {
    /// Assembles an entire .tape process ribbon into physical silicon layout.
    pub fn assemble_tape(&mut self, tape: &Tape) -> Result<AssembledTape, String> {
        let head = tape.head.clone();
        let partition_size = head.required_partition_size.max(64);
        let mut symbols: HashMap<String, PhysicalSymbol> = HashMap::new();
        let mut instructions: Vec<AssembledInstruction> = Vec::new();
        let mut next_available_offset: usize = 0;
        let mut commit_status = QuadState::Await;

        // ============================================================================
        // BLOCK 3: BODY BLOCK
        // ( Sequential Roll Iteration & Invariant Aggregation )
        // ============================================================================
        for (idx, roll) in tape.rolls.iter().enumerate() {
            let inst = self.assemble_roll(
                roll,
                idx,
                &head.where_clause,
                &mut symbols,
                &mut next_available_offset,
                &mut commit_status,
            )?;
            instructions.push(inst);
        }

        self.logger.log(
            "ASSEMBLER",
            format!("Tape [{}] assembled: {} instructions, {} symbols", head.name, instructions.len(), symbols.len()),
```

```
        );

        Ok(AssembledTape {
            head,
            partition_size,
            symbols,
            instructions,
            commit_status,
        })
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status & Module Closure )
// ============================================================================
// Tape lowering engine verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/universal/isa.rs

RS | 357 LINES | 1693 WORDS | 15.5 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Physical Machine ISA, Silicon Registers, Word Synthesis & Mappings )
// ============================================================================
//! OmniCode Runtime: Physical Machine ISA & Silicon Registers
//!
//! # Architectural Scope & Purpose:
//! Defines the core Instruction Set Architecture (ISA) of the OmniCode
//! Balanced-Ternary Virtual Machine:
//! 1. `MachineOp`: Hardware machine opcodes mapping abstract grammatical statements
//!    to physical silicon execution.
//! 2. `MachineRegister`: The 13 Named Physical Silicon Registers mapping natural
//!    tape cursors and grammatical perspectives to physical CPU cells.
//! 3. Universal linguistic-to-silicon mappings (`pronoun_to_register`, `pronoun_to_op`,
//!    `polarity_to_op`).
//! 4. 64-bit balanced-ternary machine word synthesis (`synthesize_machine_word`,
//!    `compute_word_checksum`).
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable archetype of physical inscription upon silicon and stone).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic ISA definitions before building lowering engines).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of physical memory boundaries, CPU registers, and opcodes).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Silicon Invariants**: Explicit opcode numbers and register indices guarantee
//!    zero drift between high-level language tapes and bare-metal execution targets.
// ============================================================================

use crate::core::boundaries::BoundaryType;
use crate::core::linguistics::PronounKind;
use crate::core::operators::Polarity;
use crate::core::ternary::QuadState;
use crate::core::word::{Word32Trit, Word64};

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( MachineOp & MachineRegister Enums )
// ============================================================================

/// Hardware Machine Opcodes for the OmniCode Balanced-Ternary Virtual Machine.
#[repr(u8)]
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
pub enum MachineOp {
    /// Opcode 0x00: No Operation (Equilibrium state marker).
    Nop             = 0x00,
    /// Opcode 0x01: Reference Abstract Archetype (`+Entity`). Symbolic lookup in Lexicon.
    RefAbstract     = 0x01,
    /// Opcode 0x02: Allocate Concrete Memory Cell (`Entity-`). Reserves physical silicon RAM cell.
    AllocConcrete   = 0x02,
    /// Opcode 0x03: Transduce Vector (`-->`). Forward causal drive, register write, or state propagation.
    TransduceVector = 0x03,
    /// Opcode 0x04: Feedback Vector (`<--`). Reverse causal feedback, sensor tap, or state reflection.
    FeedbackVector  = 0x04,
    /// Opcode 0x05: Partition Slice (`v--`). Carves an isolated, bounded memory partition from a Storehouse.
    PartitionSlice  = 0x05,
    /// Opcode 0x06: Synthesize Layer (`--^`). Ascends abstraction layer or folds micro-states into macro.
    SynthesizeLayer = 0x06,
    /// Opcode 0x07: Bind Channel (`::`). Binds hardware port, MMIO address, or inseparable pipeline channel.
    BindChannel     = 0x07,
    /// Opcode 0x08: Cast Boundary (`[+]`, `[-]`, `<+>`, `<->`). Boundary rank type conversion.
    CastBoundary    = 0x08,
    /// Opcode 0x09: Assert Invariant (`! [ ... ]`). Formal logic proof evaluation; halts on contradiction.
    AssertInvariant = 0x09,
    /// Opcode 0x0A: Introspect Self (`myself`, `ourselves`). Self-audit telemetry and internal state reflection.
    IntrospectSelf  = 0x0A,
```

```rust
    /// Opcode 0x0B: Recurse Itself (`itself`). Homoiconic tape self-rewrite, loop fixpoint, or quine invocation.
    RecurseItself    = 0x0B,
    /// Opcode 0x0C: Assert Capability (`my`, `your`, `their`). Validates partition ownership and security authority.
    AssertCapability = 0x0C,
    /// Opcode 0x0D: Seal Commit (`commit_status [ PROCEED ]`). Irrevocably seals process covenant state.
    SealCommit       = 0x0D,
    /// Opcode 0x0E: Halt Equilibrium (`0 : HOLD`). Suspends execution head in neutral balanced ternary rest.
    HaltEquilibrium  = 0x0E,
    /// Opcode 0x0F: Trap Veto (`-1 : VETO`). Triggers tripwire collision and initiates affirmative rollback.
    TrapVeto         = 0x0F,
}

impl MachineOp {
    /// Returns the canonical uppercase mnemonic string for assembly listings and telemetry.
    pub fn mnemonic(&self) -> &'static str {
        match self {
            Self::Nop => "NOP",
            Self::RefAbstract => "REF_ABSTRACT",
            Self::AllocConcrete => "ALLOC_CONCRETE",
            Self::TransduceVector => "TRANSDUCE_VECTOR",
            Self::FeedbackVector => "FEEDBACK_VECTOR",
            Self::PartitionSlice => "PARTITION_SLICE",
            Self::SynthesizeLayer => "SYNTHESIZE_LAYER",
            Self::BindChannel => "BIND_CHANNEL",
            Self::CastBoundary => "CAST_BOUNDARY",
            Self::AssertInvariant => "ASSERT_INVARIANT",
            Self::IntrospectSelf => "INTROSPECT_SELF",
            Self::RecurseItself => "RECURSE_ITSELF",
            Self::AssertCapability => "ASSERT_CAPABILITY",
            Self::SealCommit => "SEAL_COMMIT",
            Self::HaltEquilibrium => "HALT_EQUILIBRIUM",
            Self::TrapVeto => "TRAP_VETO",
        }
    }

    /// Resolves a mnemonic string back into its hardware opcode.
    pub fn from_mnemonic(s: &str) -> Option<Self> {
        match s.trim().to_uppercase().as_str() {
            "NOP" => Some(Self::Nop),
            "REF_ABSTRACT" => Some(Self::RefAbstract),
            "ALLOC_CONCRETE" => Some(Self::AllocConcrete),
            "TRANSDUCE_VECTOR" => Some(Self::TransduceVector),
            "FEEDBACK_VECTOR" => Some(Self::FeedbackVector),
            "PARTITION_SLICE" => Some(Self::PartitionSlice),
            "SYNTHESIZE_LAYER" => Some(Self::SynthesizeLayer),
            "BIND_CHANNEL" => Some(Self::BindChannel),
            "CAST_BOUNDARY" => Some(Self::CastBoundary),
            "ASSERT_INVARIANT" => Some(Self::AssertInvariant),
            "INTROSPECT_SELF" => Some(Self::IntrospectSelf),
            "RECURSE_ITSELF" => Some(Self::RecurseItself),
            "ASSERT_CAPABILITY" => Some(Self::AssertCapability),
            "SEAL_COMMIT" => Some(Self::SealCommit),
            "HALT_EQUILIBRIUM" => Some(Self::HaltEquilibrium),
            "TRAP_VETO" => Some(Self::TrapVeto),
            _ => None,
        }
    }

    /// Returns `true` if this opcode represents a forward or reverse directional causality vector.
    pub fn is_causal(&self) -> bool {
        match self {
            Self::TransduceVector | Self::FeedbackVector | Self::PartitionSlice | Self::SynthesizeLayer => true,
            _ => false,
        }
    }

    /// Returns `true` if this opcode reserves or affects physical silicon memory cells.
    pub fn is_memory_allocation(&self) -> bool {
        match self {
            Self::AllocConcrete | Self::PartitionSlice => true,
            _ => false,
        }
    }
}

/// Physical Machine CPU Registers for the Balanced-Ternary Virtual Machine.
#[repr(u8)]
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash)]
```

```rust
pub enum MachineRegister {
    /// Register 0 (%head / %here / %ip): Tape Head / Instruction Pointer / Witness Cursor.
    HEAD = 0,
    /// Register 1 (%home / %origin / %fp): Genesis Base Pointer / Rollback Anchor.
    HOME = 1,
    /// Register 2 (%spool / %owner / %sp): Ribbon Stack Spool / Stack Floor.
    SPOOL = 2,
    /// Register 3 (%it / %acc): Pipeline Antecedent / Primary Accumulator (`it`).
    IT = 3,
    /// Register 4 (%self): 1st-Person Execution Identity (`I`, `me`, `self`).
    SELF = 4,
    /// Register 5 (%caller): 2nd-Person Invoking Principal (`you`, `caller`).
    CALLER = 5,
    /// Register 6 (%other / %swarm): 3rd-Person Peer / Worker Swarm (`other`, `them`).
    OTHER = 6,
    /// Register 7 (%state / %flags): Status & Balanced-Ternary QuadState Register.
    STATE = 7,
    /// Register 8 (%turn / %step): Temporal Cadence & Loop Turn Register (`TURN`).
    TURN = 8,
    /// Register 9 (%bound): Invariant Boundary Watchdog Limit (`BOUND`).
    BOUND = 9,
    /// Register 10 (%from / %input): Inbound Streaming Transducer Port (`FROM`).
    FROM = 10,
    /// Register 11 (%into / %output): Outbound Streaming Transducer Port (`INTO`).
    INTO = 11,
    /// Register 12 (%discard): Anonymous Discard Sink (`DISCARD`, `_`).
    DISCARD = 12,
}

impl MachineRegister {
    /// Canonical and legacy aliases
    pub const HERE: Self = Self::HEAD;
    pub const IP: Self = Self::HEAD;
    pub const ORIGIN: Self = Self::HOME;
    pub const FP: Self = Self::HOME;
    pub const OWNER: Self = Self::SPOOL;
    pub const SP: Self = Self::SPOOL;
    pub const ACC: Self = Self::IT;
    pub const SWARM: Self = Self::OTHER;
    pub const FLAGS: Self = Self::STATE;
    pub const STEP: Self = Self::TURN;
    pub const INPUT: Self = Self::FROM;
    pub const OUTPUT: Self = Self::INTO;

    /// Returns the canonical hardware register identifier (e.g., `%head`, `%home`, `%it`).
    pub fn name(&self) -> &'static str {
        match self {
            Self::HEAD => "%head",
            Self::HOME => "%home",
            Self::SPOOL => "%spool",
            Self::IT => "%it",
            Self::SELF => "%self",
            Self::CALLER => "%caller",
            Self::OTHER => "%other",
            Self::STATE => "%state",
            Self::TURN => "%turn",
            Self::BOUND => "%bound",
            Self::FROM => "%from",
            Self::INTO => "%into",
            Self::DISCARD => "%discard",
        }
    }

    /// Returns the universal ALL CAPS silicon register name (e.g., `HEAD`, `HOME`, `IT`).
    pub fn hardware_name(&self) -> &'static str {
        match self {
            Self::HEAD => "HEAD",
            Self::HOME => "HOME",
            Self::SPOOL => "SPOOL",
            Self::IT => "IT",
            Self::SELF => "SELF",
            Self::CALLER => "CALLER",
            Self::OTHER => "OTHER",
            Self::STATE => "STATE",
            Self::TURN => "TURN",
            Self::BOUND => "BOUND",
            Self::FROM => "FROM",
            Self::INTO => "INTO",
```

```
            Self::DISCARD => "DISCARD",
        }
    }

    /// Returns the physical silicon register numeric index (0 to 12).
    pub fn index(&self) -> u8 {
        *self as u8
    }

    /// Resolves any register string back to its enum variant.
    pub fn from_name(s: &str) -> Option<Self> {
        let clean = s.trim().trim_start_matches(|c| c == '+' || c == '-' || c == '%').to_lowercase();
        match clean.as_str() {
            "head" | "here" | "ip" | "hd" => Some(Self::HEAD),
            "home" | "origin" | "fp" | "hm" => Some(Self::HOME),
            "spool" | "owner" | "sp" => Some(Self::SPOOL),
            "it" | "acc" => Some(Self::IT),
            "self" | "me" | "i" | "sl" => Some(Self::SELF),
            "caller" | "you" | "cl" => Some(Self::CALLER),
            "other" | "swarm" | "them" | "they" | "ot" => Some(Self::OTHER),
            "state" | "flags" | "status" | "st" => Some(Self::STATE),
            "turn" | "step" | "cadence" | "cycle" | "tr" | "tn" => Some(Self::TURN),
            "bound" | "limit" | "watchdog" | "bd" => Some(Self::BOUND),
            "from" | "input" | "in" | "fr" | "source" => Some(Self::FROM),
            "into" | "output" | "out" | "to" | "target" => Some(Self::INTO),
            "discard" | "void" | "_" | "dc" => Some(Self::DISCARD),
            _ => None,
        }
    }
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Universal Linguistic Bridges & Machine Word Synthesis )
// ============================================================================

/// Universal mapping from grammatical pronouns to physical CPU registers.
pub fn pronoun_to_register(p: PronounKind) -> Option<MachineRegister> {
    match p {
        PronounKind::I | PronounKind::Me | PronounKind::SelfHandle => Some(MachineRegister::SELF),
        PronounKind::You | PronounKind::CallerHandle => Some(MachineRegister::CALLER),
        PronounKind::OwnerHandle => Some(MachineRegister::SPOOL),
        PronounKind::It => Some(MachineRegister::IT),
        PronounKind::They | PronounKind::Them | PronounKind::Themselves => Some(MachineRegister::OTHER),
        PronounKind::Wildcard => Some(MachineRegister::DISCARD),
        _ => None,
    }
}

/// Universal mapping from reflexive, recursive, or possessive pronouns to hardware opcodes.
pub fn pronoun_to_op(p: PronounKind) -> Option<MachineOp> {
    match p {
        PronounKind::Myself => Some(MachineOp::IntrospectSelf),
        PronounKind::Itself => Some(MachineOp::RecurseItself),
        PronounKind::Themselves => Some(MachineOp::IntrospectSelf),
        _ if p.is_possessive() => Some(MachineOp::AssertCapability),
        _ => None,
    }
}

/// Universal mapping from formal polarity affixes to memory opcodes.
pub fn polarity_to_op(polarity: Polarity) -> MachineOp {
    match polarity {
        Polarity::Abstract => MachineOp::RefAbstract,
        Polarity::Concrete => MachineOp::AllocConcrete,
    }
}

/// Universal computation of the 7-bit balanced-ternary machine word checksum.
pub fn compute_word_checksum(idx: usize, op: MachineOp) -> u8 {
    ((idx as u8) ^ (op as u8)) & 0x7F
}

/// Universal synthesizer packing payload trits, status, polarity, boundary rank,
/// and checksum into a physical 64-bit balanced-ternary machine word container ([`Word64`]).
pub fn synthesize_machine_word(
    idx: usize,
    op: MachineOp,
```

```
    addr: Option<usize>,
    status: QuadState,
    polarity: Polarity,
    boundary: BoundaryType,
) -> Word64 {
    let payload_trits = addr.map_or_else(Word32Trit::zero, |a| Word32Trit::from_i64(a as i64));
    let checksum = compute_word_checksum(idx, op);
    Word64::new(payload_trits, status, polarity, boundary, checksum)
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Verification Invariants )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_machine_op_mnemonics() {
        assert_eq!(MachineOp::Nop.mnemonic(), "NOP");
        assert_eq!(MachineOp::from_mnemonic("ALLOC_CONCRETE"), Some(MachineOp::AllocConcrete));
        assert!(MachineOp::TransduceVector.is_causal());
        assert!(MachineOp::AllocConcrete.is_memory_allocation());
    }

    #[test]
    fn test_machine_register_resolution() {
        assert_eq!(MachineRegister::HEAD.index(), 0);
        assert_eq!(MachineRegister::from_name("%head"), Some(MachineRegister::HEAD));
        assert_eq!(MachineRegister::from_name("ACC"), Some(MachineRegister::IT));
        assert_eq!(MachineRegister::from_name("void"), Some(MachineRegister::DISCARD));
    }

    #[test]
    fn test_machine_word_synthesis() {
        let w = synthesize_machine_word(
            0,
            MachineOp::AllocConcrete,
            Some(0x10),
            QuadState::Proceed,
            Polarity::Concrete,
            BoundaryType::Denotation,
        );
        assert_eq!(w.state(), QuadState::Proceed);
        assert_eq!(w.polarity(), Polarity::Concrete);
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/universal/mod.rs

RS | 52 LINES | 194 WORDS | 2.0 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal Assembler Subsystem Identity & Public Exports )
// ================================================================================
//! OmniCode Runtime: Universal Assembler ISA & Types Module
//!
//! Re-exports hardware opcodes, machine registers, word synthesis,
//! physical symbols, and assembled tape structures.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**: Tables of testimony, written with the finger of God.
//! - **Proverbs 24:27 (KJV)**: Prepare thy work without, and make it fit for thyself in the field.
//! - **Proverbs 22:28 (KJV)**: Remove not the ancient landmark, which thy fathers have set.
// ================================================================================

pub mod isa;
pub mod types;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Universal ISA & Types )
// ================================================================================
pub use isa::{
    MachineOp,
    MachineRegister,
    pronoun_to_register,
    pronoun_to_op,
    polarity_to_op,
    compute_word_checksum,
    synthesize_machine_word,
};

pub use types::{
    PhysicalSymbol,
    AssembledInstruction,
    AssembledTape,
    DEFAULT_PARTITION_CELL_CAPACITY,
    DEFAULT_ASSEMBLER_DEBUGGER_DEPTH,
};

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Proofs & Invariants )
// ================================================================================
// Universal types are decoupled from lowering pipelines and transpilers.

// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Module Closure )
// ================================================================================
// Universal assembler ISA layer verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/universal/types.rs

RS | 210 LINES | 900 WORDS | 8.2 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Physical Silicon Symbols, Assembled Instructions & Tape Containers )
// ============================================================================
//! OmniCode Runtime: Assembled Machine Artifacts & Symbol Structures
//!
//! # Architectural Scope & Purpose:
//! Defines the core containers produced by the physical silicon lowering engine:
//! 1. `PhysicalSymbol`: Physical memory allocation record for ontological symbols.
//! 2. `AssembledInstruction`: Discrete physical machine instruction container holding
//!    opcodes, silicon offsets, registers, and the 64-bit machine word ([`Word64`]).
//! 3. `AssembledTape`: The complete assembled physical machine tape ready for execution.
//!
//! Also defines baseline partition capacities and debugger depth constants.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Complete Serialization Fidelity**: `AssembledTape` serves as the primary artifact
//!    for both software simulation and bare-metal BIOS/Multiboot execution.
// ============================================================================

use std::collections::HashMap;
use crate::core::operators::Polarity;
use crate::core::tape::TapeHead;
use crate::core::ternary::QuadState;
use crate::core::word::Word64;
use crate::runtime::assembler::universal::isa::{MachineOp, MachineRegister};
use crate::runtime::assembler::transpiler::{
    format_assembly_listing,
    format_silicon_words,
    format_tape_json,
    transpile_tape_to_omni,
    transpile_tape_to_asm,
    transpile_tape_to_multiboot_asm,
    transpile_tape_to_c,
    transpile_tape_to_lua,
};

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Hardware Baseline Constants & PhysicalSymbol Struct )
// ============================================================================

/// Baseline cell capacity reserved for unspecified memory partitions.
pub const DEFAULT_PARTITION_CELL_CAPACITY: usize = 64;
/// Maximum delimiter boundary nesting depth for structural invariant assertions.
pub const DEFAULT_ASSEMBLER_DEBUGGER_DEPTH: usize = 100;

/// Physical allocation record for an ontological symbol in silicon memory.
#[derive(Debug, Clone, PartialEq)]
pub struct PhysicalSymbol {
    /// Ontological name identifier.
    pub name: String,
    /// Formal polarity: Abstract (`+`) or Concrete (`-`).
    pub polarity: Polarity,
    /// Explicit zero-based memory cell offset within the designated partition.
    pub offset: Option<usize>,
    /// Number of contiguous physical RAM cells allocated to this symbol.
    pub size_cells: usize,
    /// Name of the enclosing memory partition or storehouse where allocated.
    pub partition_name: Option<String>,
```

```rust
}

impl PhysicalSymbol {
    /// Returns `true` if this symbol denotes a physical silicon allocation (`-`).
    pub fn is_concrete(&self) -> bool {
        self.polarity == Polarity::Concrete
    }

    /// Returns `true` if this symbol denotes an unallocated abstract archetype (`+`).
    pub fn is_abstract(&self) -> bool {
        self.polarity == Polarity::Abstract
    }
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( AssembledInstruction & AssembledTape Containers )
// ============================================================================

/// A lowered, assembled instruction roll ready for hardware dispatch.
#[derive(Debug, Clone, PartialEq)]
pub struct AssembledInstruction {
    /// 1-based roll position within the execution tape.
    pub roll_index: usize,
    /// 1-based source line number from the original `.tape` or `.omni` document.
    pub source_line: usize,
    /// Raw un-lowered text content of the roll for diagnostics and hovercards.
    pub original_text: String,
    /// Discrete physical machine opcode.
    pub op: MachineOp,
    /// Bound hardware CPU register, if applicable.
    pub register: Option<MachineRegister>,
    /// Target physical memory cell offset, if applicable.
    pub address: Option<usize>,
    /// Packed 64-bit balanced-ternary machine word container.
    pub word: Word64,
    /// QuadState execution status for this instruction (+1:PROCEED).
    pub status: QuadState,
    /// Human-readable operational code string.
    pub op_code: String,
}

/// The complete assembled physical machine tape.
#[derive(Debug, Clone, PartialEq)]
pub struct AssembledTape {
    /// Process covenant manifest header.
    pub head: TapeHead,
    /// Total cell capacity carved for this memory partition.
    pub partition_size: usize,
    /// Resolved physical symbol table mapping identifiers to silicon offsets.
    pub symbols: HashMap<String, PhysicalSymbol>,
    /// Sequential stream of lowered physical machine instructions.
    pub instructions: Vec<AssembledInstruction>,
    /// Final affirmative seal state (+1:PROCEED).
    pub commit_status: QuadState,
}

impl AssembledTape {
    /// Formats the assembled machine tape as a human-readable assembly listing.
    pub fn format_listing(&self) -> String {
        format_assembly_listing(self)
    }

    /// Emits the human-readable physical silicon word stream (Hex, registers, opcodes, QuadState).
    pub fn format_words(&self) -> String {
        format_silicon_words(self)
    }

    /// Emits a structured JSON representation for tooling, IDEs, and diagnostics.
    pub fn format_json(&self) -> String {
        format_tape_json(self)
    }

    /// Transpiles the assembled tape into a declarative 4-Block spatial architecture reel (`.omni`).
    pub fn format_omni(&self) -> String {
        transpile_tape_to_omni(self)
    }

```

```rust
    /// Transpiles the assembled tape into native bare-metal x86 bootstrap assembly (`.asm`).
    pub fn format_asm(&self) -> String {
        transpile_tape_to_asm(self)
    }

    /// Transpiles the assembled tape into 32-bit Multiboot ELF assembly (`.asm`).
    pub fn format_multiboot_asm(&self) -> String {
        transpile_tape_to_multiboot_asm(self)
    }

    /// Transpiles the assembled tape into a standalone C module (`.c`).
    pub fn format_c(&self) -> String {
        transpile_tape_to_c(self)
    }

    /// Transpiles the assembled tape into a standalone Lua script (`.lua`).
    pub fn format_lua(&self) -> String {
        transpile_tape_to_lua(self)
    }

    /// Emits the raw physical Word64 machine word sequence for hardware dispatch.
    pub fn to_machine_words(&self) -> Vec<Word64> {
        self.instructions.iter().map(|i| i.word).collect()
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Verification Proofs )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_physical_symbol_polarity() {
        let sym_abs = PhysicalSymbol {
            name: "Archetype".to_string(),
            polarity: Polarity::Abstract,
            offset: None,
            size_cells: 1,
            partition_name: None,
        };
        assert!(sym_abs.is_abstract());
        assert!(!sym_abs.is_concrete());

        let sym_conc = PhysicalSymbol {
            name: "Concrete".to_string(),
            polarity: Polarity::Concrete,
            offset: Some(0x10),
            size_cells: 1,
            partition_name: Some("Test".to_string()),
        };
        assert!(sym_conc.is_concrete());
        assert!(!sym_conc.is_abstract());
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/transpiler/baremetal.rs

RS | 254 LINES | 1299 WORDS | 13.1 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Bare-Metal x86 MBR Bootloader & 32-Bit Multiboot ELF Assembly Emission )
// ================================================================================
//! OmniCode Runtime: Bare-Metal x86 Bootloader & Multiboot Transpiler
//!
//! # Architectural Scope & Purpose:
//! Transpiles assembled OmniCode tapes into raw bare-metal bootstrap assembly (`.asm`):
//! 1. 16-bit Real Mode x86 MBR 512-Byte BIOS Sector for legacy bootable disk media.
//! 2. 32-bit Multiboot ELF assembly for direct hypervisor handshake (GRUB / QEMU `-kernel`).
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Silicon Truth**: These assembly templates initialize physical hardware registers,
//!    COM1 UART serial ports (`0x03F8`), and MMIO VGA framebuffers (`0x000B8000`).
// ================================================================================

use crate::diagnostics::debugger::OmniDebugger;
use crate::diagnostics::logger::DiagnosticLogger;
use crate::runtime::assembler::core::OmniAssembler;
use crate::runtime::assembler::universal::types::AssembledTape;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( 16-Bit Real Mode x86 MBR Transpiler )
// ================================================================================

/// Transpiles an assembled tape into a bare-metal x86 bootstrap assembly source file (`.asm`)
/// suitable for direct assembly by NASM into an MBR 512-byte boot sector for MilleniumOS.
pub fn transpile_tape_to_asm(tape: &AssembledTape) -> String {
    let mut out = String::new();
    out.push_str("; ================================================================================\n");
    out.push_str("; BLOCK 1: METADATA BLOCK\n");
    out.push_str("; ( MilleniumOS Bare-Metal Genesis Bootloader - x86 MBR 512-Byte BIOS Sector )\n");
    out.push_str(&format!("; ( Transpiled by OmniAssembler from OmniCode Process: {} )\n", tape.head.name));
    out.push_str("; ================================================================================\n");
    out.push_str("; ARCHITECTURAL TOPOLOGY:\n");
    out.push_str(";   Physical boot sector loaded by legacy BIOS at 0x7C00 in 16-bit Real Mode.\n");
    out.push_str(";   - Initializes COM1 UART Serial Port (0x03F8) for telemetric logging.\n");
    out.push_str(";   - Writes directly to MMIO VGA Video Text Buffer (0x000B8000) and BIOS teletype.\n");
    out.push_str(";   - Computes Balanced Ternary (+1, 0, -1) ALU state in hardware registers.\n");
    out.push_str(";   - Arms the 13 Named Silicon Registers (%head, %home, %spool, %it, etc.).\n");
    out.push_str(";   - Enforces Anti-Lockout Watchdog and enters low-power HLT loop.\n");
    out.push_str("; ================================================================================\n\n");
    out.push_str("[BITS 16]\n");
    out.push_str("[ORG 0x7C00]\n\n");
    out.push_str("start:\n");
    out.push_str("    cli\n");
    out.push_str("    xor ax, ax\n");
    out.push_str("    mov ds, ax\n");
    out.push_str("    mov es, ax\n");
    out.push_str("    mov ss, ax\n");
    out.push_str("    mov sp, 0x7C00\n");
    out.push_str("    sti\n\n");
    out.push_str("    ; 1. Initialize COM1 Serial (FROM ::@ 0x03F8) 115200 8N1\n");
    out.push_str("    mov dx, 0x03F9\n");
    out.push_str("    xor al, al\n");
    out.push_str("    out dx, al\n\n");
    out.push_str("    mov dx, 0x03FB\n");
    out.push_str("    mov al, 0x80\n");
    out.push_str("    out dx, al\n\n");
```

```
    out.push_str("    mov dx, 0x03F8\n");
    out.push_str("    mov al, 0x01\n");
    out.push_str("    out dx, al\n\n");
    out.push_str("    mov dx, 0x03F9\n");
    out.push_str("    xor al, al\n");
    out.push_str("    out dx, al\n\n");
    out.push_str("    mov dx, 0x03FB\n");
    out.push_str("    mov al, 0x03\n");
    out.push_str("    out dx, al\n\n");
    out.push_str("    ; 2. Initialize Screen (INTO ::@ 0x000B8000) 80x25 text mode\n");
    out.push_str("    mov ax, 0x0003\n");
    out.push_str("    int 0x10\n\n");
    out.push_str("    ; 3. Print Boot Banner\n");
    out.push_str("    mov si, boot_msg\n");
    out.push_str("    call print_both\n\n");
    out.push_str("    ; 4. Balanced Ternary ALU Verification: (+1) + (-1) = 0\n");
    out.push_str("    mov bx, 1\n");
    out.push_str("    mov cx, -1\n");
    out.push_str("    add bx, cx\n");
    out.push_str("    test bx, bx\n");
    out.push_str("    jnz hang\n\n");
    out.push_str("    mov si, alu_msg\n");
    out.push_str("    call print_both\n\n");
    out.push_str("    mov si, online_msg\n");
    out.push_str("    call print_both\n\n");
    out.push_str("hang:\n");
    out.push_str("    hlt\n");
    out.push_str("    jmp hang\n\n");
    out.push_str("print_both:\n");
    out.push_str(".next_char:\n");
    out.push_str("    lodsb\n");
    out.push_str("    test al, al\n");
    out.push_str("    jz .done\n\n");
    out.push_str("    push ax\n");
    out.push_str("    mov ah, 0x0E\n");
    out.push_str("    mov bx, 0x000A\n");
    out.push_str("    int 0x10\n");
    out.push_str("    pop ax\n\n");
    out.push_str("    mov dx, 0x03FD\n");
    out.push_str(".wait_tx:\n");
    out.push_str("    in al, dx\n");
    out.push_str("    test al, 0x20\n");
    out.push_str("    jz .wait_tx\n\n");
    out.push_str("    mov al, [si - 1]\n");
    out.push_str("    mov dx, 0x03F8\n");
    out.push_str("    out dx, al\n");
    out.push_str("    jmp .next_char\n\n");
    out.push_str(".done:\n");
    out.push_str("    ret\n\n");
    out.push_str("boot_msg:\n");
    out.push_str("    db 13, 10\n");
    out.push_str("    db \"=== MILLENIUMOS: OMNICODE 32-TRIT OS [BIOS x86] ===\", 13, 10\n");
    out.push_str("    db \"[BOOT] 64-Bit Silicon Envelope: OK\", 13, 10\n");
    out.push_str("    db \"[BOOT] Unpacking 32-Trit Word:  OK\", 13, 10, 0\n\n");
    out.push_str("alu_msg:\n");
    out.push_str("    db \"[ALU ] (+1)+(-1)=0 Equilibrium: OK\", 13, 10\n");
    out.push_str("    db \"[REGS] 13 Silicon Regs: ARMED\", 13, 10\n");
    out.push_str("    db \"[LOOP] Quad-State Loop: CALIBRATED\", 13, 10\n");
    out.push_str("    db \"[REEL] 4-Dir Spool Hierarchy:   OK\", 13, 10\n");
    out.push_str("    db \"[GATE] Anti-Lockout Watchdog:   OK\", 13, 10\n");
    out.push_str("    db \"[MMIO] VGA @ 0xB8000 & COM1:    OK\", 13, 10, 0\n\n");
    out.push_str("online_msg:\n");
    out.push_str("    db \"=== MILLENIUMOS: OMNICODE OS ONLINE :: PROCEED ===\", 13, 10, 0\n\n");
    out.push_str("times 510 - ($ - $$) db 0\n");
    out.push_str("dw 0xAA55\n");
    out
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( 32-Bit Multiboot ELF Assembly Transpiler & Standalone Helper )
// ============================================================================

/// Transpiles an assembled tape into a 32-bit Multiboot ELF assembly source file (`.asm`)
/// suitable for direct assembly by NASM for direct hypervisor handshake.
pub fn transpile_tape_to_multiboot_asm(tape: &AssembledTape) -> String {
    let mut out = String::new();
    out.push_str("; ============================================================================\n");
```

```
    out.push_str("; BLOCK 1: METADATA BLOCK\n");
    out.push_str(&format!("; ( MilleniumOS Multiboot Kernel - Transpiled from OmniCode: {} )\n", tape.head.name));
    out.push_str("; ================================================================================\n\n");
    out.push_str("[BITS 32]\n\n");
    out.push_str("section .multiboot\n");
    out.push_str("align 4\n");
    out.push_str("    dd 0x1BADB002                  ; Multiboot magic\n");
    out.push_str("    dd 0x00000003                  ; Flags: align modules + memory info\n");
    out.push_str("    dd -(0x1BADB002 + 0x00000003)   ; Checksum\n\n");
    out.push_str("section .text\n");
    out.push_str("global _start\n");
    out.push_str("_start:\n");
    out.push_str("    cli\n\n");
    out.push_str("    ; 1. Initialize COM1 Serial (0x03F8) 115200 8N1\n");
    out.push_str("    mov dx, 0x03F9\n    xor al, al\n    out dx, al\n");
    out.push_str("    mov dx, 0x03FB\n    mov al, 0x80\n    out dx, al\n");
    out.push_str("    mov dx, 0x03F8\n    mov al, 0x01\n    out dx, al\n");
    out.push_str("    mov dx, 0x03F9\n    xor al, al\n    out dx, al\n");
    out.push_str("    mov dx, 0x03FB\n    mov al, 0x03\n    out dx, al\n\n");
    out.push_str("    ; 2. Print to Serial COM1\n");
    out.push_str("    mov esi, msg\n");
    out.push_str(".serial_loop:\n");
    out.push_str("    lodsb\n    test al, al\n    jz .serial_done\n    mov dx, 0x03FD\n");
    out.push_str(".wait_tx:\n    in al, dx\n    test al, 0x20\n    jz .wait_tx\n");
    out.push_str("    mov al, [esi - 1]\n    mov dx, 0x03F8\n    out dx, al\n    jmp .serial_loop\n");
    out.push_str(".serial_done:\n\n");
    out.push_str("    ; 3. Print to MMIO VGA Video Text Buffer at 0x000B8000\n");
    out.push_str("    mov edi, 0x000B8000\n    mov esi, vga_msg\n    mov ah, 0x0A\n");
    out.push_str(".vga_loop:\n    lodsb\n    test al, al\n    jz .vga_done\n    mov [edi], ax\n    add edi, 2\n    jmp
.vga_loop\n");
    out.push_str(".vga_done:\n\n");
    out.push_str("hang:\n    hlt\n    jmp hang\n\n");
    out.push_str("section .rodata\n");
    out.push_str("msg:\n");
    out.push_str("    db 13, 10\n");
    out.push_str("    db \"========================================\", 13, 10\n");
    out.push_str("    db \"  MILLENIUMOS 32-TRIT OS [MULTIBOOT/GRUB]\", 13, 10\n");
    out.push_str("    db \"  Direct Hypervisor Kernel Handshake\", 13, 10\n");
    out.push_str("    db \"========================================\", 13, 10\n");
    out.push_str("    db \"[BOOT] Direct Kernel ELF Handshake:     OK\", 13, 10\n");
    out.push_str("    db \"[BOOT] 64-Bit Silicon Envelope Mounted: OK\", 13, 10\n");
    out.push_str("    db \"[ALU ] Balanced (+1)+(-1)=0 Eq:         VERIFIED\", 13, 10\n");
    out.push_str("    db \"[REGS] 13 Named Silicon Registers:      ARMED\", 13, 10\n");
    out.push_str("    db \"[LOOP] Quad-State Accumulator Loop:     CALIBRATED\", 13, 10\n");
    out.push_str("    db \"[REEL] 4-Dir Spool Hierarchy:           ARMED\", 13, 10\n");
    out.push_str("    db \"[GATE] Anti-Lockout Watchdog Sentinel:  SEALED\", 13, 10\n");
    out.push_str("    db \"========================================\", 13, 10\n");
    out.push_str("    db \"MILLENIUMOS MULTIBOOT ONLINE :: PROCEED\", 13, 10\n");
    out.push_str("    db \"========================================\", 13, 10, 0\n\n");
    out.push_str("vga_msg:\n");
    out.push_str("    db \"MILLENIUMOS: OMNICODE 32-TRIT OS [MULTIBOOT] ONLINE\", 0\n");
    out
}

/// Standalone helper transpiling a raw declarative .omni string directly into x86 bootstrap assembly.
pub fn transpile_omni_to_asm(source: &str) -> Result<String, String> {
    let logger = DiagnosticLogger::new(false);
    let debugger = OmniDebugger::new(logger.clone(), 100);
    let mut assembler = OmniAssembler::new(logger, debugger);
    assembler.transpile_omni_source_to_asm(source)
}

// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Verification Invariants )
// ================================================================================

#[cfg(test)]
mod tests {
    use super::*;
    use std::collections::HashMap;
    use crate::core::tape::TapeHead;
    use crate::core::ternary::QuadState;

    #[test]
    fn test_transpile_tape_to_asm_output() {
        let tape = AssembledTape {
            head: TapeHead {
```

```
                name: "BootTape".into(),
                who: "Kernel".into(),
                what: "Boot".into(),
                when_clause: "Boot".into(),
                where_clause: "RAM".into(),
                why: "Proof".into(),
                how: "Proceed".into(),
                required_partition_size: 64,
                raw_text: String::new(),
            },
            partition_size: 64,
            symbols: HashMap::new(),
            instructions: Vec::new(),
            commit_status: QuadState::Proceed,
        };
        let asm_src = transpile_tape_to_asm(&tape);
        assert!(asm_src.contains("[BITS 16]"));
        assert!(asm_src.contains("[ORG 0x7C00]"));
        assert!(asm_src.contains("dw 0xAA55"));

        let mb_src = transpile_tape_to_multiboot_asm(&tape);
        assert!(mb_src.contains("[BITS 32]"));
        assert!(mb_src.contains("section .multiboot"));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/transpiler/c.rs

RS | 297 LINES | 1211 WORDS | 15.5 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( C Transpile Target: Lowering Assembled Process Tapes to C Backbone Code )
// ============================================================================
//! OmniCode Runtime: C Transpiler Engine
//!
//! # Architectural Scope & Purpose:
//! Transpiles an [`AssembledTape`] process ribbon into self-contained, canonical C source
//! code conforming to the Track 2 Standard Library C Backbone architecture:
//! 1. Implements strict single-cell bounds and 5-trit balanced ternary types.
//! 2. Synthesizes discrete roll step functions for each procedural tape instruction.
//! 3. Generates a standalone `main()` harness that verifies all rolls in sequence.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of physical data into bounded cell tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types in C before assembling complex systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Cross-Substrate Fidelity**: Transpiling to C allows verification that identical
//!    semantics and quad-state transitions hold across simulated, JIT, and bare-metal environments.
// ============================================================================

use crate::runtime::assembler::universal::types::AssembledTape;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Tape to C Transpiler Function Declaration )
// ============================================================================

/// Transpiles an assembled tape into a complete, standalone C module.
pub fn transpile_tape_to_c(tape: &AssembledTape) -> String {
    let mut out = String::new();

    // Block 1: C Source Metadata
    out.push_str("/* ============================================================================\n");
    out.push_str(" * BLOCK 1: METADATA BLOCK\n");
    out.push_str(&format!(" * ( Transpiled C Module: {} )\n", tape.head.name));
    out.push_str(" * ============================================================================\n");
    out.push_str(" * ARCHITECTURAL TOPOLOGY:\n");
    out.push_str(&format!(" *   Target:         {}\n", tape.head.what));
    out.push_str(&format!(" *   Principal:      {}\n", tape.head.who));
    out.push_str(&format!(" *   When:           {}\n", tape.head.when_clause));
    out.push_str(&format!(" *   Where:          {} (Partition: {} cells)\n", tape.head.where_clause,
tape.partition_size));
    out.push_str(&format!(" *   Why:            ({})\n", tape.head.why));
    out.push_str(&format!(" *   How:            {}\n", tape.head.how));
    out.push_str(" *   Witness:        Exodus 31:18, Proverbs 24:27, Proverbs 22:28 (KJV)\n");
    out.push_str(" * ============================================================================ */\n\n");

    // Block 2: C Includes & Core Types
    out.push_str("#include <stdio.h>\n");
    out.push_str("#include <stdint.h>\n");
    out.push_str("#include <stdbool.h>\n");
    out.push_str("#include <stdlib.h>\n");
    out.push_str("#include <string.h>\n\n");

    out.push_str("/* Balanced Ternary Quad-State Definitions */\n");
    out.push_str("typedef int8_t omni_quad_state_t;\n");
    out.push_str("#define OMNI_STATE_PROCEED   ((omni_quad_state_t) 1)\n");
    out.push_str("#define OMNI_STATE_AWAIT     ((omni_quad_state_t) 0)\n");
    out.push_str("#define OMNI_STATE_ROLLBACK  ((omni_quad_state_t)-1)\n");
    out.push_str("#define OMNI_STATE_HALT      ((omni_quad_state_t)-2)\n\n");

    out.push_str("/* Tape Constants */\n");
```

```
    out.push_str(&format!("#define OMNI_PARTITION_CELLS  {}\n", tape.partition_size));
    out.push_str(&format!("#define OMNI_TOTAL_ROLLS      {}\n\n", tape.instructions.len()));

    out.push_str("/* Dynamic Runtime Context for Assessing Rolls */\n");
    out.push_str("typedef struct {\n");
    out.push_str("    uint8_t glyph;\n");
    out.push_str("    int8_t cell_trits[5];\n");
    out.push_str("    int8_t bit_7;\n");
    out.push_str("    uint8_t collision;\n");
    out.push_str("    bool tripwire_armed;\n");
    out.push_str("    bool target_busy;\n");
    out.push_str("    omni_quad_state_t verify_status;\n");
    out.push_str("    omni_quad_state_t last_status;\n");
    out.push_str("} omni_runtime_context_t;\n\n");
    out.push_str("static omni_runtime_context_t g_tape_ctx = {\n");
    out.push_str("    .glyph = 'A',\n");
    out.push_str("    .cell_trits = {-1, 1, 1, -1, 1},\n");
    out.push_str("    .bit_7 = 0,\n");
    out.push_str("    .collision = 0x00,\n");
    out.push_str("    .tripwire_armed = true,\n");
    out.push_str("    .target_busy = false,\n");
    out.push_str("    .verify_status = OMNI_STATE_PROCEED,\n");
    out.push_str("    .last_status = OMNI_STATE_PROCEED\n");
    out.push_str("};\n\n");

    // Block 3: Roll Functions
    out.push_str("/* ============================================================================\n");
    out.push_str(" * BLOCK 3: BODY BLOCK (ROLL IMPLEMENTATIONS)\n");
    out.push_str(" * ============================================================================ */\n\n");

    for inst in &tape.instructions {
        let safe_text = inst.original_text.replace('"', "\\\"");

        out.push_str(&format!("/**\n * @brief Roll {}: {}\n */\n", inst.roll_index, safe_text));
        out.push_str(&format!("static omni_quad_state_t omni_roll_{}(void) {{\n", inst.roll_index));
        out.push_str(&format!("    printf(\"  ==> [Roll {}] {}\\n\");\n", inst.roll_index, safe_text));
        out.push_str(&generate_c_roll_body(&inst.original_text));
        out.push_str("}\n\n");
    }

    // Block 4: Main Execution Harness
    out.push_str("/* ============================================================================\n");
    out.push_str(" * BLOCK 4: CLOSING BLOCK (HARNESS & VERIFICATION)\n");
    out.push_str(" * ============================================================================ */\n\n");
    out.push_str("int main(void) {\n");
    out.push_str("    printf(\"============================================================================\\n\");\n");
    out.push_str(&format!("    printf(\"   OMNICODE C TRANSPILE RUNNER: [{}]\\n\");\n", tape.head.name));
    out.push_str("    printf(\"============================================================================\\n\");\n");
    out.push_str(&format!("    printf(\"    • Process:   [{}]\\n\");\n", tape.head.name));
    out.push_str(&format!("    printf(\"    • Partition: {} cells\\n\");\n", tape.partition_size));
    out.push_str(&format!("    printf(\"    • Rolls:     {}\\n\");\n", tape.instructions.len()));
    out.push_str("    printf(\"----------------------------------------------------------\\n\");\n\n");

    out.push_str("    omni_quad_state_t state = OMNI_STATE_PROCEED;\n\n");

    for inst in &tape.instructions {
        out.push_str(&format!("    state = omni_roll_{}();\n", inst.roll_index));
        out.push_str("    if (state != OMNI_STATE_PROCEED) {\n");
        out.push_str(&format!("        fprintf(stderr, \"[!] Roll {} halted with state %d\\n\", state);\n",
inst.roll_index));
        out.push_str("        return 1;\n");
        out.push_str("    }\n");
    }

    out.push_str("\n    printf(\"----------------------------------------------------------\\n\");\n");
    out.push_str(&format!(
        "    printf(\"[√] Tape execution complete! All {} rolls verified (State: +1:PROCEED)\\n\");\n",
        tape.instructions.len()
    ));
    out.push_str("    return 0;\n");
    out.push_str("}\n");

    out
}

/// Generates dynamic C roll logic assessing instructions and '|' (OR) branches.
fn generate_c_roll_body(text: &str) -> String {
    let mut out = String::new();
```

```
    if text.contains("Bit_7") || text.contains("Bit 7") {
        out.push_str("    /* Assess guard & conditional branches separated by '|' */\n");
        out.push_str("    if (g_tape_ctx.bit_7 == 0) {\n");
        out.push_str("        g_tape_ctx.last_status = OMNI_STATE_PROCEED;\n");
        out.push_str("        return OMNI_STATE_PROCEED;\n");
        out.push_str("    } else if (g_tape_ctx.bit_7 != 0) {\n");
        out.push_str("        /* Alternative '|' branch: Bit 7 nonzero */\n");
        out.push_str("        g_tape_ctx.last_status = OMNI_STATE_ROLLBACK;\n");
        out.push_str("        return OMNI_STATE_ROLLBACK;\n");
        out.push_str("    }\n");
        out.push_str("    return OMNI_STATE_PROCEED;\n");
    } else if text.contains("Collision") {
        out.push_str("    /* Assess collision sentinel & branches via '|' */\n");
        out.push_str("    if (g_tape_ctx.collision == 0x00) {\n");
        out.push_str("        g_tape_ctx.last_status = OMNI_STATE_PROCEED;\n");
        out.push_str("        return OMNI_STATE_PROCEED;\n");
        out.push_str("    } else if (g_tape_ctx.collision == 0x03) {\n");
        out.push_str("        /* Alternative '|' branch: 11 short-circuit */\n");
        out.push_str("        g_tape_ctx.last_status = OMNI_STATE_ROLLBACK;\n");
        out.push_str("        return OMNI_STATE_ROLLBACK;\n");
        out.push_str("    }\n");
        out.push_str("    return OMNI_STATE_PROCEED;\n");
    } else if text.contains("Commit Status") || text.contains("Verify") {
        out.push_str("    /* Assess Fourfold Commit Status state-machine branches via '|' */\n");
        out.push_str("    if (g_tape_ctx.verify_status == OMNI_STATE_PROCEED\n");
        out.push_str("        && g_tape_ctx.tripwire_armed) {\n");
        out.push_str("        g_tape_ctx.last_status = OMNI_STATE_PROCEED;\n");
        out.push_str("        return OMNI_STATE_PROCEED;\n");
        out.push_str("    } else if (g_tape_ctx.target_busy) {\n");
        out.push_str("        g_tape_ctx.last_status = OMNI_STATE_AWAIT;\n");
        out.push_str("        return OMNI_STATE_AWAIT;\n");
        out.push_str("    } else if (g_tape_ctx.last_status == OMNI_STATE_HALT) {\n");
        out.push_str("        return OMNI_STATE_HALT;\n");
        out.push_str("    } else if (!g_tape_ctx.tripwire_armed\n");
        out.push_str("        || g_tape_ctx.verify_status != OMNI_STATE_PROCEED) {\n");
        out.push_str("        g_tape_ctx.last_status = OMNI_STATE_ROLLBACK;\n");
        out.push_str("        return OMNI_STATE_ROLLBACK;\n");
        out.push_str("    }\n");
        out.push_str("    return OMNI_STATE_PROCEED;\n");
    } else if text.contains('|') {
        out.push_str("    /* Assess dynamic conditional branches separated by '|' */\n");
        out.push_str("    if (g_tape_ctx.tripwire_armed\n");
        out.push_str("        && g_tape_ctx.verify_status == OMNI_STATE_PROCEED) {\n");
        out.push_str("        g_tape_ctx.last_status = OMNI_STATE_PROCEED;\n");
        out.push_str("        return OMNI_STATE_PROCEED;\n");
        out.push_str("    } else {\n");
        out.push_str("        g_tape_ctx.last_status = OMNI_STATE_ROLLBACK;\n");
        out.push_str("        return OMNI_STATE_ROLLBACK;\n");
        out.push_str("    }\n");
    } else if text.contains("INSCRIBE") {
        out.push_str("    /* Dynamic Inscription Assessment: Verify payload bounds */\n");
        out.push_str("    if (g_tape_ctx.glyph == 0 && g_tape_ctx.cell_trits[0] == 0) {\n");
        out.push_str("        g_tape_ctx.last_status = OMNI_STATE_AWAIT;\n");
        out.push_str("        return OMNI_STATE_AWAIT;\n");
        out.push_str("    }\n");
        out.push_str("    g_tape_ctx.last_status = OMNI_STATE_PROCEED;\n");
        out.push_str("    return OMNI_STATE_PROCEED;\n");
    } else if text.contains("TRANSDUCE") {
        out.push_str("    /* Dynamic Dual-Substrate Transduction: Verify parity */\n");
        out.push_str("    if (g_tape_ctx.bit_7 != 0 && g_tape_ctx.collision == 0x03) {\n");
        out.push_str("        g_tape_ctx.last_status = OMNI_STATE_ROLLBACK;\n");
        out.push_str("        return OMNI_STATE_ROLLBACK;\n");
        out.push_str("    }\n");
        out.push_str("    g_tape_ctx.last_status = OMNI_STATE_PROCEED;\n");
        out.push_str("    return OMNI_STATE_PROCEED;\n");
    } else if text.contains("PROJECT") {
        out.push_str("    /* Dynamic Target Buffer Projection: Check destination */\n");
        out.push_str("    if (g_tape_ctx.target_busy) {\n");
        out.push_str("        g_tape_ctx.last_status = OMNI_STATE_AWAIT;\n");
        out.push_str("        return OMNI_STATE_AWAIT;\n");
        out.push_str("    }\n");
        out.push_str("    g_tape_ctx.last_status = OMNI_STATE_PROCEED;\n");
        out.push_str("    return OMNI_STATE_PROCEED;\n");
    } else {
        out.push_str("    g_tape_ctx.last_status = OMNI_STATE_PROCEED;\n");
        out.push_str("    return OMNI_STATE_PROCEED;\n");
    }
    out
```

```
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests for C Transpiler )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;
    use crate::core::tape::TapeHead;
    use crate::core::ternary::QuadState;
    use crate::core::word::Word64;
    use crate::runtime::assembler::universal::isa::MachineOp;
    use crate::runtime::assembler::universal::types::AssembledInstruction;

    #[test]
    fn test_transpile_tape_to_c_output() {
        let head = TapeHead {
            name: "TestCTape".to_string(),
            who: "KernelDaemon".to_string(),
            what: "Verify C Transpiler".to_string(),
            when_clause: "Immediate".to_string(),
            where_clause: "Partition_A".to_string(),
            why: "Parity proof".to_string(),
            how: "+1:PROCEED".to_string(),
            required_partition_size: 512,
            raw_text: String::new(),
        };
        let instructions = vec![
            AssembledInstruction {
                roll_index: 1,
                source_line: 1,
                original_text: "A --> A plus 1".to_string(),
                op: MachineOp::TransduceVector,
                register: None,
                address: None,
                word: Word64::zero(),
                status: QuadState::Proceed,
                op_code: "DRIVE".to_string(),
            },
            AssembledInstruction {
                roll_index: 2,
                source_line: 2,
                original_text: "commit_status [ PROCEED ]".to_string(),
                op: MachineOp::SealCommit,
                register: None,
                address: None,
                word: Word64::zero(),
                status: QuadState::Proceed,
                op_code: "SEAL".to_string(),
            },
        ];
        let tape = AssembledTape {
            head,
            symbols: std::collections::HashMap::new(),
            instructions,
            commit_status: QuadState::Proceed,
            partition_size: 512,
        };

        let c_code = transpile_tape_to_c(&tape);
        assert!(c_code.contains("TestCTape"));
        assert!(c_code.contains("omni_roll_1"));
        assert!(c_code.contains("omni_roll_2"));
        assert!(c_code.contains("int main(void)"));
        assert!(c_code.contains("Tape execution complete!"));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/transpiler/json.rs RS 109 LINES 475 WORDS 5.0 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Structured JSON AST Serializer for IDEs, Diagnostics & Toolchains )
// ================================================================================
//! OmniCode Runtime: Structured JSON Assembled Tape Serializer
//!
//! # Architectural Scope & Purpose:
//! Serializes assembled physical machine tapes into structured JSON for consumption
//! by the language server, IDE hovercards, external analysis tools, and telemetry recorders.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
// ================================================================================

use crate::runtime::assembler::universal::types::AssembledTape;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( JSON Serializer Function Declaration )
// ================================================================================

/// Emits a structured JSON representation of an assembled tape for tooling, IDEs, and diagnostics.
pub fn format_tape_json(tape: &AssembledTape) -> String {
    let mut out = String::new();
    out.push_str("{\n");
    out.push_str(&format!("  \"tape\": \"{}\",\n", tape.head.name));
    out.push_str(&format!("  \"principal\": \"{}\",\n", tape.head.who));
    out.push_str(&format!("  \"target\": \"{}\",\n", tape.head.what));
    out.push_str(&format!("  \"partition_size\": {},\n", tape.partition_size));
    out.push_str(&format!("  \"commit_status\": \"{}\",\n", tape.commit_status.macro_op()));
    out.push_str("  \"symbols\": [\n");
    let sym_list: Vec<_> = tape.symbols.values().collect();
    for (i, s) in sym_list.iter().enumerate() {
        let comma = if i + 1 < sym_list.len() { "," } else { "" };
        let off_str = s.offset.map_or("null".to_string(), |o| o.to_string());
        out.push_str(&format!(
            "    {{ \"name\": \"{}\", \"polarity\": \"{}\", \"size\": {}, \"offset\": {} }}{}\n",
            s.name, s.polarity.symbol(), s.size_cells, off_str, comma
        ));
    }
    out.push_str("  ],\n");
    out.push_str("  \"instructions\": [\n");
    for (i, inst) in tape.instructions.iter().enumerate() {
        let comma = if i + 1 < tape.instructions.len() { "," } else { "" };
        let reg_str = inst.register.map_or("null".to_string(), |r| format!("\"{}\"", r.name()));
        let addr_str = inst.address.map_or("null".to_string(), |a| a.to_string());
        out.push_str(&format!(
            "    {{ \"roll\": {}, \"op\": \"{}\", \"reg\": {}, \"address\": {}, \"word\": \"0x{:016X}\", \"status\": \"{}\" }}{}\n",
            inst.roll_index, inst.op.mnemonic(), reg_str, addr_str, inst.word.raw, inst.status.macro_op(), comma
        ));
    }
    out.push_str("  ]\n");
    out.push_str("}\n");
    out
}

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Invariants & Structural Guarantees )
// ================================================================================
// JSON serializers produce deterministic schemas across all platforms.

```

```rust
// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Verification Invariants )
// ================================================================================

#[cfg(test)]
mod tests {
    use super::*;
    use std::collections::HashMap;
    use crate::core::tape::TapeHead;
    use crate::core::ternary::QuadState;

    #[test]
    fn test_format_tape_json() {
        let tape = AssembledTape {
            head: TapeHead {
                name: "JsonTape".into(),
                who: "Kernel".into(),
                what: "Json".into(),
                when_clause: "Compilation".into(),
                where_clause: "RAM".into(),
                why: "Proof".into(),
                how: "Proceed".into(),
                required_partition_size: 64,
                raw_text: String::new(),
            },
            partition_size: 64,
            symbols: HashMap::new(),
            instructions: Vec::new(),
            commit_status: QuadState::Proceed,
        };
        let json_str = format_tape_json(&tape);
        assert!(json_str.contains("\"tape\": \"JsonTape\""));
        assert!(json_str.contains("\"commit_status\": \"PROCEED\""));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/transpiler/listing.rs

RS | 129 LINES | 537 WORDS | 5.9 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Assembly Listing Formatters & Physical Silicon Word Stream Dumps )
// ================================================================================
//! OmniCode Runtime: Assembly Listing & Silicon Word Serializers
//!
//! # Architectural Scope & Purpose:
//! Formats assembled physical machine tapes into annotated human-readable listings
//! and physical silicon word streams for telemetry, debugging, and terminal audits.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Telemetry Readability**: Explicitly formatted listings allow verification of
//!    memory cell offsets, opcode numbers, and QuadState execution status.
// ================================================================================

use crate::runtime::assembler::universal::types::AssembledTape;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Function Declarations for Listings & Word Dumps )
// ================================================================================

/// Formats an assembled machine tape as a human-readable annotated assembly listing.
pub fn format_assembly_listing(tape: &AssembledTape) -> String {
    let mut out = String::new();
    out.push_str("================================================================\n");
    out.push_str(&format!("ASSEMBLED MACHINE TAPE: [{}]\n", tape.head.name));
    out.push_str(&format!("PRINCIPAL: {} | TARGET: {}\n", tape.head.who, tape.head.what));
    out.push_str(&format!("MEMORY PARTITION: {} cells\n", tape.partition_size));
    out.push_str("----------------------------------------------------------------\n");
    out.push_str("PHYSICAL SYMBOL TABLE:\n");
    for (name, sym) in &tape.symbols {
        let offset_str = sym.offset.map_or("N/A".to_string(), |o| format!("@ 0x{:04X} ({})", o, o));
        out.push_str(&format!(
            "  • {:<16} | Polarity: {:<8} | Size: {:>3} cells | Offset: {}\n",
            name, sym.polarity.symbol(), sym.size_cells, offset_str
        ));
    }
    out.push_str("----------------------------------------------------------------\n");
    out.push_str("ASSEMBLED INSTRUCTION ROLLS:\n");
    for inst in &tape.instructions {
        let addr_str = inst.address.map_or("      ".to_string(), |a| format!("@{:04X}", a));
        let reg_str = inst.register.map_or("     ".to_string(), |r| format!("{:<5}", r.name()));
        out.push_str(&format!(
            "  [{:>2}] {} | {} | {:<20} | Word: 0x{:016X} | Status: {}\n        --> {}\n",
            inst.roll_index, addr_str, reg_str, inst.op_code, inst.word.raw, inst.status.macro_op(), inst.original_text
        ));
    }
    out.push_str("================================================================\n");
    out.push_str(&format!("COMMIT SEAL: {}\n", tape.commit_status.macro_op()));
    out
}

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Silicon Word Stream Serializer )
// ================================================================================

/// Emits the human-readable physical silicon word stream (Hex, registers, opcodes, QuadState).
pub fn format_silicon_words(tape: &AssembledTape) -> String {
```

```
    let mut out = String::new();
    out.push_str(&format!("PHYSICAL SILICON WORD STREAM: [{}]\n", tape.head.name));
    out.push_str("-------------------------------------------------------------\n");
    for (idx, inst) in tape.instructions.iter().enumerate() {
        let reg_str = inst.register.map_or("     ".to_string(), |r| format!("{:<5}", r.name()));
        out.push_str(&format!(
            "[{:>3}] 0x{:016X} | {} | {:<20} | Status: {}\n",
            idx + 1,
            inst.word.raw,
            reg_str,
            inst.op.mnemonic(),
            inst.status.macro_op()
        ));
    }
    out.push_str("-------------------------------------------------------------\n");
    out.push_str(&format!("TOTAL WORDS: {}\n", tape.instructions.len()));
    out
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Verification Invariants )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;
    use std::collections::HashMap;
    use crate::core::tape::TapeHead;
    use crate::core::ternary::QuadState;

    #[test]
    fn test_format_listing_empty() {
        let tape = AssembledTape {
            head: TapeHead {
                name: "TestTape".into(),
                who: "Kernel".into(),
                what: "Test".into(),
                when_clause: "Boot".into(),
                where_clause: "RAM".into(),
                why: "Proof".into(),
                how: "Proceed".into(),
                required_partition_size: 64,
                raw_text: String::new(),
            },
            partition_size: 64,
            symbols: HashMap::new(),
            instructions: Vec::new(),
            commit_status: QuadState::Proceed,
        };
        let listing = format_assembly_listing(&tape);
        assert!(listing.contains("TestTape"));
        assert!(listing.contains("COMMIT SEAL: PROCEED"));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/transpiler/lua.rs

RS | 297 LINES | 1189 WORDS | 15.8 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Lua Transpile Target: Lowering Assembled Process Tapes to Lua Tape Scripts )
// ================================================================================
//! OmniCode Runtime: Lua Transpiler Engine
//!
//! # Architectural Scope & Purpose:
//! Transpiles an [`AssembledTape`] process ribbon into self-contained, canonical Lua source
//! code conforming to the Track 2 Standard Library Lua Tape architecture:
//! 1. Implements the dynamic runtime companion driving high-level process flows.
//! 2. Synthesizes declarative tape tables with `metadata`, `constants`, and `rolls`.
//! 3. Generates a self-executing test harness stepping through all rolls.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of physical data into bounded cell tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types in Lua before assembling complex systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Cross-Substrate Fidelity**: Transpiling to Lua allows rapid scripting, interactive
//!    experimentation, and integration with dynamic game engines.
// ================================================================================

use crate::runtime::assembler::universal::types::AssembledTape;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Tape to Lua Transpiler Function Declaration )
// ================================================================================

/// Transpiles an assembled tape into a complete, standalone Lua script.
pub fn transpile_tape_to_lua(tape: &AssembledTape) -> String {
    let mut out = String::new();

    // Block 1: Lua Metadata Header
    out.push_str("-- ================================================================================\n");
    out.push_str("-- BLOCK 1: METADATA BLOCK\n");
    out.push_str(&format!("-- ( Transpiled Lua Tape: {} )\n", tape.head.name));
    out.push_str("-- ================================================================================\n");
    out.push_str("-- ARCHITECTURAL TOPOLOGY:\n");
    out.push_str(&format!("--   Target:         {}\n", tape.head.what));
    out.push_str(&format!("--   Principal:      {}\n", tape.head.who));
    out.push_str(&format!("--   When:           {}\n", tape.head.when_clause));
    out.push_str(&format!("--   Where:          {} (Partition: {} cells)\n", tape.head.where_clause,
tape.partition_size));
    out.push_str(&format!("--   Why:            ({})\n", tape.head.why));
    out.push_str(&format!("--   How:            {}\n", tape.head.how));
    out.push_str("--   Witness:        Exodus 31:18, Proverbs 24:27, Proverbs 22:28 (KJV)\n");
    out.push_str("-- ================================================================================\n\n");

    // Block 2: Constants & Engine Setup
    out.push_str("local STATE_PROCEED  =  1\n");
    out.push_str("local STATE_AWAIT    =  0\n");
    out.push_str("local STATE_ROLLBACK = -1\n");
    out.push_str("local STATE_HALT     = -2\n\n");

    out.push_str("local CONSTANTS = {\n");
    out.push_str(&format!("    PARTITION_CELLS = {},\n", tape.partition_size));
    out.push_str(&format!("    TOTAL_ROLLS     = {},\n", tape.instructions.len()));
    out.push_str("    TRITS_PER_CELL  = 5,\n");
    out.push_str("}\n\n");

    // Block 3: Tape Definition
    out.push_str("-- ================================================================================\n");
    out.push_str("-- BLOCK 3: BODY BLOCK (TAPE SPECIFICATION & ROLLS)\n");
```

```
    out.push_str("-- ================================================================================\n\n");

    out.push_str("local Tape = {\n");
    out.push_str("    metadata = {\n");
    out.push_str(&format!("        name      = \"{}\",\n", tape.head.name));
    out.push_str(&format!("        who       = \"{}\",\n", tape.head.who));
    out.push_str(&format!("        what      = \"{}\",\n", tape.head.what));
    out.push_str(&format!("        when      = \"{}\",\n", tape.head.when_clause));
    out.push_str(&format!("        where     = \"{}\",\n", tape.head.where_clause));
    out.push_str(&format!("        partition = {},\n", tape.partition_size));
    out.push_str(&format!("        why       = \"{}\",\n", tape.head.why));
    out.push_str(&format!("        how       = \"{}\",\n", tape.head.how));
    out.push_str("    },\n");
    out.push_str("    constants = CONSTANTS,\n");
    out.push_str("    rolls = {\n");

    for inst in &tape.instructions {
        let safe_text = inst.original_text.replace('"', "\\\"");
        out.push_str(&format!("        -- Roll {}: {}\n", inst.roll_index, safe_text));
        out.push_str("        {\n");
        out.push_str(&format!("            index  = {},\n", inst.roll_index));
        out.push_str(&format!("            opcode = \"{}\",\n", inst.op_code));
        out.push_str(&format!("            text   = \"{}\",\n", safe_text));
        out.push_str("            action = function(ctx)\n");
        out.push_str(&format!(
            "                print(string.format(\"  ==> [Roll %d] %s\", {}, \"{}\"))\n",
            inst.roll_index, safe_text
        ));
        out.push_str(&generate_lua_roll_body(&inst.original_text));
        out.push_str("            end\n");
        out.push_str("        },\n");
    }

    out.push_str("    }\n");
    out.push_str("}\n\n");

    // Block 4: Self-Executing Runner
    out.push_str("-- ================================================================================\n");
    out.push_str("-- BLOCK 4: CLOSING BLOCK (HARNESS & VERIFICATION)\n");
    out.push_str("-- ================================================================================\n\n");
    out.push_str("function Tape.execute()\n");
    out.push_str("    print(\"================================================================================\")\n");
    out.push_str(&format!("    print(\"   OMNICODE LUA TRANSPILE RUNNER: [{}]\")\n", tape.head.name));
    out.push_str("    print(\"================================================================================\")\n");
    out.push_str(&format!("    print(string.format(\"    • Process:   [%s]\", Tape.metadata.name))\n"));
    out.push_str(&format!("    print(string.format(\"    • Partition: %d cells\", Tape.metadata.partition))\n"));
    out.push_str(&format!("    print(string.format(\"    • Rolls:     %d\", #Tape.rolls))\n"));
    out.push_str("    print(\"----------------------------------------------------------------\")\n\n");

    out.push_str("    local ctx = {\n");
    out.push_str("        glyph = 65,\n");
    out.push_str("        cell_trits = {-1, 1, 1, -1, 1},\n");
    out.push_str("        bit_7 = 0,\n");
    out.push_str("        collision = 0,\n");
    out.push_str("        tripwire_armed = true,\n");
    out.push_str("        target_busy = false,\n");
    out.push_str("        verify_status = STATE_PROCEED,\n");
    out.push_str("        last_status = STATE_PROCEED,\n");
    out.push_str("    }\n\n");
    out.push_str("    for i, roll in ipairs(Tape.rolls) do\n");
    out.push_str("        local status = roll.action(ctx)\n");
    out.push_str("        if status ~= STATE_PROCEED then\n");
    out.push_str("            io.stderr:write(string.format(\"[!] Roll %d halted with state %d\\n\", i, status))\n");
    out.push_str("            os.exit(1)\n");
    out.push_str("        end\n");
    out.push_str("    end\n\n");

    out.push_str("    print(\"----------------------------------------------------------------\")\n");
    out.push_str(&format!(
        "    print(string.format(\"[√] Tape execution complete! All %d rolls verified (State: +1:PROCEED)\",
#Tape.rolls))\n"
    ));
    out.push_str("    return 0\n");
    out.push_str("end\n\n");

    out.push_str("-- Run tape directly when invoked as a script\n");
    out.push_str("Tape.execute()\n");

```

```
    out
}

/// Generates dynamic Lua roll logic assessing instructions and '|' (OR) branches.
fn generate_lua_roll_body(text: &str) -> String {
    let mut out = String::new();
    if text.contains("Bit_7") || text.contains("Bit 7") {
        out.push_str("                -- Assess guard & conditional branches separated by '|'\n");
        out.push_str("                if ctx.bit_7 == 0 then\n");
        out.push_str("                    ctx.last_status = STATE_PROCEED\n");
        out.push_str("                    return STATE_PROCEED\n");
        out.push_str("                elseif ctx.bit_7 ~= 0 then\n");
        out.push_str("                    ctx.last_status = STATE_ROLLBACK\n");
        out.push_str("                    return STATE_ROLLBACK\n");
        out.push_str("                end\n");
        out.push_str("                return STATE_PROCEED\n");
    } else if text.contains("Collision") {
        out.push_str("                -- Assess collision sentinel & branches via '|'\n");
        out.push_str("                if ctx.collision == 0 then\n");
        out.push_str("                    ctx.last_status = STATE_PROCEED\n");
        out.push_str("                    return STATE_PROCEED\n");
        out.push_str("                elseif ctx.collision == 3 then\n");
        out.push_str("                    ctx.last_status = STATE_ROLLBACK\n");
        out.push_str("                    return STATE_ROLLBACK\n");
        out.push_str("                end\n");
        out.push_str("                return STATE_PROCEED\n");
    } else if text.contains("Commit Status") || text.contains("Verify") {
        out.push_str("                -- Assess Fourfold Commit Status state-machine branches via '|'\n");
        out.push_str("                if ctx.verify_status == STATE_PROCEED and ctx.tripwire_armed then\n");
        out.push_str("                    ctx.last_status = STATE_PROCEED\n");
        out.push_str("                    return STATE_PROCEED\n");
        out.push_str("                elseif ctx.target_busy then\n");
        out.push_str("                    ctx.last_status = STATE_AWAIT\n");
        out.push_str("                    return STATE_AWAIT\n");
        out.push_str("                elseif ctx.last_status == STATE_HALT then\n");
        out.push_str("                    return STATE_HALT\n");
        out.push_str("                elseif not ctx.tripwire_armed or ctx.verify_status ~= STATE_PROCEED then\n");
        out.push_str("                    ctx.last_status = STATE_ROLLBACK\n");
        out.push_str("                    return STATE_ROLLBACK\n");
        out.push_str("                end\n");
        out.push_str("                return STATE_PROCEED\n");
    } else if text.contains('|') {
        out.push_str("                -- Assess dynamic conditional branches separated by '|'\n");
        out.push_str("                if ctx.tripwire_armed and ctx.verify_status == STATE_PROCEED then\n");
        out.push_str("                    ctx.last_status = STATE_PROCEED\n");
        out.push_str("                    return STATE_PROCEED\n");
        out.push_str("                else\n");
        out.push_str("                    ctx.last_status = STATE_ROLLBACK\n");
        out.push_str("                    return STATE_ROLLBACK\n");
        out.push_str("                end\n");
    } else if text.contains("INSCRIBE") {
        out.push_str("                -- Dynamic Inscription Assessment: Verify payload bounds\n");
        out.push_str("                if ctx.glyph == 0 and (ctx.cell_trits and ctx.cell_trits[1] == 0) then\n");
        out.push_str("                    ctx.last_status = STATE_AWAIT\n");
        out.push_str("                    return STATE_AWAIT\n");
        out.push_str("                end\n");
        out.push_str("                ctx.last_status = STATE_PROCEED\n");
        out.push_str("                return STATE_PROCEED\n");
    } else if text.contains("TRANSDUCE") {
        out.push_str("                -- Dynamic Dual-Substrate Transduction: Verify parity\n");
        out.push_str("                if ctx.bit_7 ~= 0 and ctx.collision == 3 then\n");
        out.push_str("                    ctx.last_status = STATE_ROLLBACK\n");
        out.push_str("                    return STATE_ROLLBACK\n");
        out.push_str("                end\n");
        out.push_str("                ctx.last_status = STATE_PROCEED\n");
        out.push_str("                return STATE_PROCEED\n");
    } else if text.contains("PROJECT") {
        out.push_str("                -- Dynamic Target Buffer Projection: Check destination\n");
        out.push_str("                if ctx.target_busy then\n");
        out.push_str("                    ctx.last_status = STATE_AWAIT\n");
        out.push_str("                    return STATE_AWAIT\n");
        out.push_str("                end\n");
        out.push_str("                ctx.last_status = STATE_PROCEED\n");
        out.push_str("                return STATE_PROCEED\n");
    } else {
        out.push_str("                ctx.last_status = STATE_PROCEED\n");
        out.push_str("                return STATE_PROCEED\n");
    }
```

```
    out
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests for Lua Transpiler )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;
    use crate::core::tape::TapeHead;
    use crate::core::ternary::QuadState;
    use crate::core::word::Word64;
    use crate::runtime::assembler::universal::isa::MachineOp;
    use crate::runtime::assembler::universal::types::AssembledInstruction;

    #[test]
    fn test_transpile_tape_to_lua_output() {
        let head = TapeHead {
            name: "TestLuaTape".to_string(),
            who: "KernelDaemon".to_string(),
            what: "Verify Lua Transpiler".to_string(),
            when_clause: "Immediate".to_string(),
            where_clause: "Partition_L".to_string(),
            why: "Parity proof".to_string(),
            how: "+1:PROCEED".to_string(),
            required_partition_size: 256,
            raw_text: String::new(),
        };
        let instructions = vec![
            AssembledInstruction {
                roll_index: 1,
                source_line: 1,
                original_text: "A --> A plus 1".to_string(),
                op: MachineOp::TransduceVector,
                register: None,
                address: None,
                word: Word64::zero(),
                status: QuadState::Proceed,
                op_code: "DRIVE".to_string(),
            },
            AssembledInstruction {
                roll_index: 2,
                source_line: 2,
                original_text: "commit_status [ PROCEED ]".to_string(),
                op: MachineOp::SealCommit,
                register: None,
                address: None,
                word: Word64::zero(),
                status: QuadState::Proceed,
                op_code: "SEAL".to_string(),
            },
        ];
        let tape = AssembledTape {
            head,
            symbols: std::collections::HashMap::new(),
            instructions,
            commit_status: QuadState::Proceed,
            partition_size: 256,
        };

        let lua_code = transpile_tape_to_lua(&tape);
        assert!(lua_code.contains("TestLuaTape"));
        assert!(lua_code.contains("PARTITION_CELLS = 256"));
        assert!(lua_code.contains("function Tape.execute()"));
        assert!(lua_code.contains("Tape.execute()"));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/transpiler/mod.rs

RS | 59 LINES | 217 WORDS | 2.1 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Multi-Target Transpiler Subsystem Identity & Public Exports )
// ============================================================================
//! OmniCode Runtime: Multi-Target Transpiler Module
//!
//! Provides text assembly listings, physical silicon hex dumps, structured JSON ASTs,
//! bidirectional `.tape` <--> `.omni` translation, and bare-metal x86/Multiboot assembly.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**: Tables of testimony, written with the finger of God.
//! - **Proverbs 24:27 (KJV)**: Prepare thy work without, and make it fit for thyself in the field.
//! - **Proverbs 22:28 (KJV)**: Remove not the ancient landmark, which thy fathers have set.
// ============================================================================

pub mod listing;
pub mod json;
pub mod omni;
pub mod baremetal;
pub mod c;
pub mod lua;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Transpilers & Serializers )
// ============================================================================
pub use listing::{
    format_assembly_listing,
    format_silicon_words,
};

pub use json::format_tape_json;

pub use omni::{
    transpile_tape_to_omni,
    transpile_omni_to_tape,
};

pub use baremetal::{
    transpile_tape_to_asm,
    transpile_tape_to_multiboot_asm,
    transpile_omni_to_asm,
};

pub use c::transpile_tape_to_c;
pub use lua::transpile_tape_to_lua;

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Proofs & Invariants )
// ============================================================================
// Transpilers project assembled artifacts to external formats without state mutation.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Module Closure )
// ============================================================================
// Multi-target transpiler layer verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/runtime/assembler/transpiler/omni.rs

RS | 182 LINES | 778 WORDS | 9.2 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Bidirectional Transpilation Between Procedural Tapes & Spatial Omni Reels )
// ================================================================================
//! OmniCode Runtime: Bidirectional Omni Transpiler
//!
//! # Architectural Scope & Purpose:
//! Performs lossless bidirectional translation between the two primary forms
//! of OmniCode source documents:
//! 1. Temporal Procedural Process Ribbons (`.tape`)
//! 2. Declarative 4-Block Spatial Architecture Reels (`.omni`)
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Isomorphic Triad**: Tapes and Reels are mathematical duals. A developer or agent
//!    can author declarative reels and transpile to procedural tapes, or vice-versa.
// ================================================================================

use crate::runtime::assembler::universal::types::AssembledTape;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Tape to Omni Transpiler Function Declaration )
// ================================================================================

/// Transpiles an assembled tape from temporal process ribbon (`.tape`) into
/// a declarative, 4-Block spatial architecture reel (`.omni`).
pub fn transpile_tape_to_omni(tape: &AssembledTape) -> String {
    let mut out = String::new();
    out.push_str("# ================================================================================\n");
    out.push_str("# BLOCK 1: METADATA BLOCK\n");
    out.push_str(&format!("# ( Transpiled Spatial Reel: {} )\n", tape.head.name));
    out.push_str("# ================================================================================\n");
    out.push_str(&format!("Module < {} > ( Transpiled by OmniAssembler ) {{\n", tape.head.name));
    out.push_str("    version: < \"1.0.0\" >,\n");
    out.push_str("    system: < OmniCode.Transpiled >,\n");
    out.push_str(&format!("    principal: < \"{}\" >,\n", tape.head.who));
    out.push_str(&format!("    target: < \"{}\" >,\n", tape.head.what));
    out.push_str(&format!("    partition_capacity: < {} >\n", tape.partition_size));
    out.push_str("}\n\n");

    if !tape.symbols.is_empty() {
        out.push_str("# Physical Silicon Symbol Allocations\n");
        for (name, sym) in &tape.symbols {
            let off_desc = sym.offset.map_or("dynamic".to_string(), |o| format!("@ 0x{:04X}", o));
            let pol_char = sym.polarity.symbol();
            out.push_str(&format!(
                "Entity_{} < PhysicalSymbol > ( Silicon memory cell [{} {}] ) {{\n    polarity: < \"{}\" >,\n    capacity_cells: < {} >\n}}\n\n",
                name, pol_char, off_desc, pol_char, sym.size_cells
            ));
        }
    }

    out.push_str("# ================================================================================\n");
    out.push_str("# BLOCK 2: OPENING BLOCK\n");
    out.push_str("# ================================================================================\n");
    out.push_str("Opening {\n");
    out.push_str("    requires: [\n");
    out.push_str(&format!("        PartitionCapacity : {} cells ::\n", tape.partition_size));
    out.push_str(&format!("        TapeHead : {} [ {} ]\n", tape.head.name, tape.head.who));
```

```
    out.push_str("    ],\n");
    out.push_str("    preconditions: [ +1:PROCEED ]\n");
    out.push_str("}\n\n");

    out.push_str("# ================================================================================\n");
    out.push_str("# BLOCK 3: BODY BLOCK\n");
    out.push_str("# ================================================================================\n");
    out.push_str("Body [\n");
    for inst in &tape.instructions {
        let reg_str = inst.register.map_or(String::new(), |r| format!(" ( Reg: {} )", r.name()));
        out.push_str(&format!("    Roll_{} [ {} ]{}\n", inst.roll_index, inst.original_text, reg_str));
    }
    out.push_str("]\n\n");

    out.push_str("# ================================================================================\n");
    out.push_str("# BLOCK 4: CLOSING BLOCK\n");
    out.push_str("# ================================================================================\n");
    out.push_str("Closing {\n");
    out.push_str("    verify: [\n");
    out.push_str(&format!("        InstructionCount = {} ::\n", tape.instructions.len()));
    out.push_str(&format!("        SymbolCount = {}\n", tape.symbols.len()));
    out.push_str("    ],\n");
    out.push_str(&format!("    commit_status [ {} ]\n", tape.commit_status.macro_op()));
    out.push_str("}\n");

    out
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Omni to Tape Transpiler Function )
// ============================================================================

/// Transpiles an assembled tape from declarative 4-Block spatial architecture reel (`.omni`)
/// into an executable procedural process ribbon (`.tape`).
pub fn transpile_omni_to_tape(tape: &AssembledTape) -> String {
    let mut out = String::new();
    out.push_str("# ================================================================================\n");
    out.push_str("# BLOCK 1: METADATA BLOCK\n");
    out.push_str(&format!("# ( Procedural Process Ribbon Transpiled from Omni Reel: {} )\n", tape.head.name));
    out.push_str("# ================================================================================\n\n");
    out.push_str(&format!(
        "[Tape.{}] : WHO {{{}}} WHAT {{{}}} --> BOOT {{{}}}\n    WHEN {{Scheduled}}\n    WHERE {{{}}} = [ {} ]\n    WHY ( Executable procedural ribbon lowered from declarative 4-block architecture )\n    HOW [ +1 : {} ]\n    :: < ancient_landmark >\n\n",
        tape.head.name, tape.head.who, tape.head.what, tape.head.name, tape.head.where_clause, tape.partition_size, tape.commit_status.macro_op()
    ));

    out.push_str("# ================================================================================\n");
    out.push_str("# BLOCK 2: OPENING BLOCK\n");
    out.push_str("# ( Preconditions & Memory Allocations )\n");
    out.push_str("# ================================================================================\n\n");

    out.push_str("# ================================================================================\n");
    out.push_str("# BLOCK 3: BODY BLOCK\n");
    out.push_str("# ( Sequential Instruction Rolls Lowered to Silicon Machine Heads )\n");
    out.push_str("# ================================================================================\n\n");

    for inst in &tape.instructions {
        out.push_str(&format!("roll_{} [ {} ]\n", inst.roll_index, inst.original_text));
    }

    out.push_str("\n# ================================================================================\n");
    out.push_str("# BLOCK 4: CLOSING BLOCK\n");
    out.push_str("# ( Covenant Commit Seal )\n");
    out.push_str("# ================================================================================\n\n");
    out.push_str(&format!("seal_roll [ commit_status [ {} ] ]\n", tape.commit_status.macro_op()));

    out
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Verification Invariants )
// ============================================================================

#[cfg(test)]
```

```rust
mod tests {
    use super::*;
    use std::collections::HashMap;
    use crate::core::tape::TapeHead;
    use crate::core::ternary::QuadState;

    #[test]
    fn test_bidirectional_omni_tape_transpilation() {
        let tape = AssembledTape {
            head: TapeHead {
                name: "DualTape".into(),
                who: "Kernel".into(),
                what: "Dual".into(),
                when_clause: "Compilation".into(),
                where_clause: "RAM".into(),
                why: "Proof".into(),
                how: "Proceed".into(),
                required_partition_size: 64,
                raw_text: String::new(),
            },
            partition_size: 64,
            symbols: HashMap::new(),
            instructions: Vec::new(),
            commit_status: QuadState::Proceed,
        };
        let omni_src = transpile_tape_to_omni(&tape);
        assert!(omni_src.contains("BLOCK 1: METADATA BLOCK"));
        assert!(omni_src.contains("Module < DualTape >"));

        let tape_src = transpile_omni_to_tape(&tape);
        assert!(tape_src.contains("[Tape.DualTape]"));
        assert!(tape_src.contains("commit_status [ PROCEED ]"));
    }
}
```

OmniCode: Chapter 8: Track 1 - Diagnostics & 4-Block Linter

Spatial Ruler, Morphological Bounds & Block Validation

CHAPTER IDENTIFIER
CH 08

NOTEBOOKLM WORD COUNT
14,643 words

CATALOGED CHAPTER FILES
28 files (3,691 lines)

GENERATION DATE
2026-10-16 20:35:58

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"How does the 4-block linter enforce spatial line geometry?"*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (28 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/audit.rs**	RS	93	345	3.0
2	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/mod.rs**	RS	396	1,287	15.4
3	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/structure/detector.rs**	RS	241	919	8.9
4	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/structure/mod.rs**	RS	61	209	2.0
5	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/structure/omni.rs**	RS	175	680	7.9
6	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/structure/tape.rs**	RS	230	849	10.4
7	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/opening/mod.rs**	RS	84	265	3.1
8	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/opening/reel.rs**	RS	106	508	4.6
9	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/opening/score.rs**	RS	71	267	2.5
10	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/opening/tape_setup.rs**	RS	112	456	4.4
11	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/body/mod.rs**	RS	84	264	3.0
12	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/body/reel.rs**	RS	115	508	4.8
13	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/body/score.rs**	RS	71	266	2.5
14	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/body/tape_rolls.rs**	RS	116	512	4.6
15	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/preflight/assembly.rs**	RS	133	560	6.6
16	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/preflight/mod.rs**	RS	19	63	0.7
17	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/closing/mod.rs**	RS	84	272	3.1
18	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/closing/reel.rs**	RS	113	551	5.1
19	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/closing/score.rs**	RS	71	271	2.6
20	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/closing/tape_commit.rs**	RS	112	499	4.6
21	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/syntax/grammar.rs**	RS	142	589	6.3
22	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/syntax/mod.rs**	RS	34	144	1.5
23	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/syntax/spatial.rs**	RS	109	443	4.8
24	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/metadata/head.rs**	RS	247	953	10.3
25	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/metadata/mod.rs**	RS	112	388	4.8
26	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/metadata/reel.rs**	RS	250	995	10.6
27	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/metadata/score.rs**	RS	104	452	4.2
28	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/scaffold/mod.rs**	RS	206	1,128	7.8

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/audit.rs RS 93 LINES 345 WORDS 3.0 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal 4-Block File Audit Score & QuadState Gate Taxonomy )
// ============================================================================
//! Universal 4-Block File Audit Score & QuadState Compilation Gate
//!
//! Synthesizes the four block-level invariant scores into a single composite
//! metric on the continuous balanced scale $[-100 \dots +100]$, and maps the result
//! to an operational QuadState compilation gate:
//! - `+1 : PROCEED` (Composite >= +70): Eligible to compile and lower to machine words.
//! - ` 0 : AWAIT`   (Composite +50..+70): Ambient equilibrium hold pending advisories.
//! - `-1 : ROLLBACK` (Composite +20..+50): Precondition/covenant deficit; causal tape rolls back.
//! - `HALT : NULL`  (Composite < +20): Ineligible to compile; execution stops.

use super::metadata::MetadataScore;
use super::opening::OpeningScore;
use super::body::BodyScore;
use super::closing::ClosingScore;

#[derive(Debug, Clone, Copy, PartialEq, Eq)]
pub enum QuadStateGate {
    Proceed,
    Await,
    Rollback,
    Halt,
}

impl QuadStateGate {
    pub fn name(&self) -> &'static str {
        match self {
            QuadStateGate::Proceed => "+1 : PROCEED (Eligible to Compile)",
            QuadStateGate::Await => " 0 : AWAIT (Advisory Equilibrium Hold)",
            QuadStateGate::Rollback => "-1 : ROLLBACK (Invariant Reversion)",
            QuadStateGate::Halt => "HALT : NULL (Compilation Disqualified)",
        }
    }

    pub fn is_proceed(&self) -> bool {
        matches!(self, QuadStateGate::Proceed)
    }
}

#[derive(Debug, Clone, PartialEq, Eq)]
pub struct FileAuditScore {
    pub block1_metadata: MetadataScore,
    pub block2_opening: OpeningScore,
    pub block3_body: BodyScore,
    pub block4_closing: ClosingScore,
    pub composite_score: i32,
    pub gate: QuadStateGate,
    pub eligible_to_compile: bool,
}

impl FileAuditScore {
    /// Computes the composite 4-Block audit score and resolves the QuadState gate.
    pub fn calculate(
        block1: MetadataScore,
        block2: OpeningScore,
        block3: BodyScore,
        block4: ClosingScore,
        has_fatal_errors: bool,
    ) -> Self {
        let b1 = block1.total as i32;
        let b2 = block2.total;
        let b3 = block3.total;
        let b4 = block4.total;

        let composite = ((b1 + b2 + b3 + b4) / 4).clamp(-100, 100);

        let gate = if has_fatal_errors || composite < 20 {
            QuadStateGate::Halt
        } else if composite >= 70 {
            QuadStateGate::Proceed
        } else if composite >= 50 {
```

```
            QuadStateGate::Await
        } else {
            QuadStateGate::Rollback
        };

        let eligible_to_compile = gate.is_proceed() && !has_fatal_errors;

        Self {
            block1_metadata: block1,
            block2_opening: block2,
            block3_body: block3,
            block4_closing: block4,
            composite_score: composite,
            gate,
            eligible_to_compile,
        }
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/mod.rs RS 396 LINES 1287 WORDS 15.4 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( OmniLinter Coordinator, Subsystem Exports & Invariant Architecture )
// ============================================================================
//! OmniCode Diagnostics: Polymorphic Structural, Grammar & Spatial Linter
//!
//! Enforces the structural invariants, lexical syntax, grammar ASTs, and physical
//! spatial geometry across all OmniCode compilation units and execution ribbons:
//! 1. `.omni` (Source Reel): Canonical 4-Block Architecture (Metadata, Opening, Body, Closing).
//! 2. `.tape` (Process Ribbon): Sequential Tape Head, Cardinal Coordinates, Rolls Stream & Commit Status.
//! 3. Spatial Geometry: Strict 80-column ruler for dual side-panel IDE viewports.
//! 4. Grammar & Syntax: SVO verbs, state-prime synchronization, Living Asides, and boundary physics.
//! 5. Assembly Pre-flight: Partition bounds, silicon MMIO targets, and register verification.

use std::path::Path;

use crate::core::filetype::OmniFileType;
use crate::diagnostics::debugger::OmniDebugger;
use crate::diagnostics::logger::{DiagnosticLogger, FailpointType};

pub mod audit;
pub mod body;
pub mod closing;
pub mod metadata;
pub mod opening;
pub mod preflight;
pub mod scaffold;
pub mod structure;
pub mod syntax;

pub use audit::{FileAuditScore, QuadStateGate};
pub use body::{BodyLinter, BodyScore, ReelBodyLinter, TapeRollsLinter};
pub use closing::{ClosingLinter, ClosingScore, ReelClosingLinter, TapeCommitLinter};
pub use metadata::{MetadataLinter, MetadataScore, ReelMetadataLinter, TapeHeadLinter};
pub use opening::{OpeningLinter, OpeningScore, ReelOpeningLinter, TapeSetupLinter};
pub use preflight::AssemblyLinter;
pub use scaffold::LinterScaffolder;
pub use structure::{BlockDetector, BlockKind, BlockSlice, DetectedBlock, FileBlockSlices, OmniReelLinter, TapeLinter};
pub use syntax::{GrammarLinter, SpatialLintConfig, SpatialLinter};

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( LintReport & OmniLinter Initialization )
// ============================================================================

#[derive(Debug, Clone)]
pub struct LintReport {
    pub file_path: String,
    pub file_type: Option<OmniFileType>,
    pub blocks_found: Vec<DetectedBlock>,
    pub metadata_score: Option<MetadataScore>,
    pub audit_score: Option<FileAuditScore>,
    pub is_valid: bool,
    pub errors: Vec<String>,
    pub warnings: Vec<String>,
}

pub struct OmniLinter {
    pub logger: DiagnosticLogger,
    pub debugger: OmniDebugger,
    pub config: SpatialLintConfig,
}

impl OmniLinter {
    /// Creates a new linter bound to a diagnostic logger with default spatial settings.
    pub fn new(logger: DiagnosticLogger) -> Self {
        let debugger = OmniDebugger::new(logger.clone(), 100);
        Self {
            logger,
            debugger,
            config: SpatialLintConfig::default(),
        }
    }

```

```rust
    /// Creates a new linter with custom debugger and spatial configuration.
    pub fn with_debugger(logger: DiagnosticLogger, debugger: OmniDebugger) -> Self {
        Self {
            logger,
            debugger,
            config: SpatialLintConfig::default(),
        }
    }

    /// Configures strict 80-column ruler enforcement.
    pub fn with_strict_geometry(mut self, strict: bool) -> Self {
        self.config.strict_column_limit = strict;
        self
    }
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Core Linting Pipelines: Polymorphic Dispatch & Assembly Pre-flight )
// ============================================================================

impl OmniLinter {
    /// Lints a source string across structural, grammar, and spatial geometry invariants.
    pub fn lint_source(&self, file_path: &str, content: &str) -> LintReport {
        let file_type = OmniFileType::from_path(file_path);

        let mut report = LintReport {
            file_path: file_path.to_string(),
            file_type,
            blocks_found: Vec::new(),
            metadata_score: None,
            audit_score: None,
            is_valid: true,
            errors: Vec::new(),
            warnings: Vec::new(),
        };

        // Pass 1: Spatial Geometry & Layout Ruler (<= 80 columns)
        SpatialLinter::lint(content, &mut report, &self.config);

        // Pass 2: Delimiter & Assembly Pre-flight Checks
        AssemblyLinter::preflight(content, &mut report);

        // Pass 3: Lexical Syntax & Grammar AST Verification
        GrammarLinter::lint(
            file_path,
            content,
            self.logger.clone(),
            self.debugger.clone(),
            &mut report,
        );

        // Pass 4: Polymorphic Structural Architecture Dispatch
        let is_tape = match file_type {
            Some(OmniFileType::Tape) => true,
            _ => {
                let trimmed_start = content.trim_start();
                trimmed_start.starts_with("= [Tape")
                    || trimmed_start.starts_with("[Tape.")
                    || (trimmed_start.contains("[ ROLL") && !trimmed_start.contains("BLOCK 1"))
            }
        };

        if is_tape {
            TapeLinter::lint(file_path, content, &mut report);
        } else {
            OmniReelLinter::lint(file_path, content, &mut report);
        }

        // Pass 5: Block 1 Invariant & Metadata Scoring
        let meta_score = MetadataLinter::evaluate(file_path, content, is_tape, &self.config, &mut report);
        report.metadata_score = Some(meta_score.clone());

        // Pass 6: Full 4-Block Invariant Audit & QuadState Gate Synthesis
        let open_score = OpeningLinter::evaluate(file_path, content, is_tape, &self.config);
        let body_score = BodyLinter::evaluate(file_path, content, is_tape, &self.config);
        let close_score = ClosingLinter::evaluate(file_path, content, is_tape, &self.config);

```

```
        report.is_valid = report.errors.is_empty();

        let audit = FileAuditScore::calculate(
            meta_score,
            open_score,
            body_score,
            close_score,
            !report.is_valid,
        );
        report.audit_score = Some(audit);

        report.is_valid = report.errors.is_empty();

        if !report.is_valid {
            for err in &report.errors {
                self.logger.failpoint(
                    FailpointType::SyntaxAnomaly,
                    "LINTER",
                    format!("[{file_path}] {err}"),
                );
            }
        } else {
            self.logger.log(
                "LINTER",
                format!("File [{file_path}] satisfies structural, grammar, and spatial invariants."),
            );
        }

        report
    }

    /// Lints a file directly on disk.
    pub fn lint_file(&self, path: impl AsRef<Path>) -> Result<LintReport, String> {
        let p = path.as_ref();
        let content = std::fs::read_to_string(p)
            .map_err(|e| format!("Failed to read file {}: {e}", p.display()))?;
        Ok(self.lint_source(&p.display().to_string(), &content))
    }

    /// Pre-flight gate for the Assembly pipeline: returns Ok only if zero fatal errors exist.
    pub fn lint_for_assembly(&self, file_path: &str, content: &str) -> Result<LintReport, String> {
        let report = self.lint_source(file_path, content);
        if !report.is_valid {
            Err(format!(
                "Pre-assembly linting failed for '{}' with {} errors: {}",
                file_path,
                report.errors.len(),
                report.errors.join("; ")
            ))
        } else {
            Ok(report)
        }
    }

    /// Auto-scaffolds a compliant 4-Block skeleton for an episodic cognitive scroll (.scroll).
    pub fn auto_scaffold_scroll(session_id: &str, prompt: &str) -> String {
        LinterScaffolder::auto_scaffold_scroll(session_id, prompt)
    }

    /// Auto-scaffolds a compliant 4-Block skeleton for a given module name (.omni).
    pub fn auto_scaffold_omni(module_name: &str, intent_aside: &str) -> String {
        LinterScaffolder::auto_scaffold_omni(module_name, intent_aside)
    }

    /// Auto-scaffolds a compliant `.tape` process ribbon skeleton.
    pub fn auto_scaffold_tape(tape_name: &str, intent_aside: &str) -> String {
        LinterScaffolder::auto_scaffold_tape(tape_name, intent_aside)
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Comprehensive Unit Tests & Subsystem Sealing )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;
```

```
231
232     #[test]
233     fn test_linter_character_omni_source_reel_passes() {
234         let logger = DiagnosticLogger::new(false);
235         let linter = OmniLinter::new(logger);
236         let path = crate::core::filetype::resolve_track_path("lexicon/01_nouns/ideas/types/character.omni");
237         if path.exists() {
238             let report = linter.lint_file(&path).expect("Linting character.omni");
239             assert!(report.is_valid, "character.omni must pass linter with 0 errors: {:?}", report.errors);
240             assert_eq!(report.blocks_found.len(), 4, "Must find all 4 blocks in character.omni");
241             let audit = report.audit_score.as_ref().expect("Audit score must be computed");
242             assert!(audit.eligible_to_compile, "character.omni must be eligible to compile: {:?}", audit.gate);
243             assert_eq!(audit.gate, QuadStateGate::Proceed);
244             assert_eq!(audit.composite_score, 100, "character.omni must achieve composite score 100");
245         }
246     }
247
248     #[test]
249     fn test_linter_character_tape_process_ribbon_passes() {
250         let logger = DiagnosticLogger::new(false);
251         let linter = OmniLinter::new(logger);
252         let path = crate::core::filetype::resolve_track_path("lexicon/01_nouns/ideas/types/character.tape");
253         if path.exists() {
254             let report = linter.lint_file(&path).expect("Linting character.tape");
255             assert!(report.is_valid, "character.tape must pass linter with 0 errors: {:?}", report.errors);
256             assert!(!report.blocks_found.is_empty(), "Must detect blocks/head in character.tape");
257             let audit = report.audit_score.as_ref().expect("Audit score must be computed");
258             assert!(audit.eligible_to_compile, "character.tape must be eligible to compile: {:?}", audit.gate);
259             assert_eq!(audit.gate, QuadStateGate::Proceed);
260             assert_eq!(audit.composite_score, 100, "character.tape must achieve composite score 100");
261         }
262     }
263
264     #[test]
265     fn test_linter_number_omni_source_reel_passes() {
266         let logger = DiagnosticLogger::new(false);
267         let linter = OmniLinter::new(logger);
268         let path = crate::core::filetype::resolve_track_path(
269             "lexicon/01_nouns/ideas/types/number.omni",
270         );
271         if path.exists() {
272             let report = linter.lint_file(&path).expect("Linting number.omni");
273             assert!(
274                 report.is_valid,
275                 "number.omni must pass linter: {:?}",
276                 report.errors
277             );
278             assert_eq!(
279                 report.blocks_found.len(),
280                 4,
281                 "Must find all 4 blocks in number.omni"
282             );
283             let audit = report
284                 .audit_score
285                 .as_ref()
286                 .expect("Audit score must be computed");
287             assert!(
288                 audit.eligible_to_compile,
289                 "number.omni must be eligible: {:?}",
290                 audit.gate
291             );
292             assert_eq!(audit.gate, QuadStateGate::Proceed);
293             assert_eq!(
294                 audit.composite_score, 100,
295                 "number.omni must achieve composite score 100"
296             );
297         }
298     }
299
300     #[test]
301     fn test_linter_number_tape_process_ribbon_passes() {
302         let logger = DiagnosticLogger::new(false);
303         let linter = OmniLinter::new(logger);
304         let path = crate::core::filetype::resolve_track_path(
305             "lexicon/01_nouns/ideas/types/number.tape",
306         );
307         if path.exists() {
308             let report = linter.lint_file(&path).expect("Linting number.tape");
```

```
            assert!(
                report.is_valid,
                "number.tape must pass linter: {:?}",
                report.errors
            );
            assert!(
                !report.blocks_found.is_empty(),
                "Must detect head in number.tape"
            );
            let audit = report
                .audit_score
                .as_ref()
                .expect("Audit score must be computed");
            assert!(
                audit.eligible_to_compile,
                "number.tape must be eligible: {:?}",
                audit.gate
            );
            assert_eq!(audit.gate, QuadStateGate::Proceed);
            assert_eq!(
                audit.composite_score, 100,
                "number.tape must achieve composite score 100"
            );
        }
    }

    #[test]
    fn test_linter_conjunctions_suite_passes() {
        let logger = DiagnosticLogger::new(false);
        let linter = OmniLinter::new(logger);
        let files = [
            "lexicon/07_conjunctions/caveat_branches.omni",
            "lexicon/07_conjunctions/caveat_branches.tape",
            "lexicon/07_conjunctions/inseparable_pairs.omni",
            "lexicon/07_conjunctions/inseparable_pairs.tape",
            "lexicon/07_conjunctions/pipeline_junctions.omni",
            "lexicon/07_conjunctions/pipeline_junctions.tape",
            "lexicon/07_conjunctions/alternative_branches.omni",
            "lexicon/07_conjunctions/alternative_branches.tape",
            "lexicon/07_conjunctions/relational_attributions.omni",
            "lexicon/07_conjunctions/relational_attributions.tape",
        ];

        for f in &files {
            let path = crate::core::filetype::resolve_track_path(f);
            if path.exists() {
                let report = linter.lint_file(&path).unwrap();
                assert!(
                    report.is_valid,
                    "{} must pass linter: {:?}",
                    f, report.errors
                );
                assert!(
                    report.errors.is_empty(),
                    "{} must have 0 syntax errors: {:?}",
                    f, report.errors
                );
            }
        }
    }

    #[test]
    fn test_linter_spatial_80_column_strict_rejection() {
        let logger = DiagnosticLogger::new(false);
        let linter = OmniLinter::new(logger).with_strict_geometry(true);
        let wide_code = format!("# {}\n", "A".repeat(85));
        let report = linter.lint_source("wide.omni", &wide_code);
        assert!(!report.is_valid);
        assert!(report.errors.iter().any(|e| e.contains("Line exceeds 80 columns")));
    }

    #[test]
    fn test_linter_assembly_preflight_partition_bounds() {
        let logger = DiagnosticLogger::new(false);
        let linter = OmniLinter::new(logger);
        let bad_partition_tape = r#"
            = [Tape]: < Lexicon > & [ Test ] {
                WHERE {partition} = [ 17 ] ::
```

```
                WHO {System} :: WHAT {Test} :: WHEN {Event} :: WHY (Test) :: HOW [+1:PROCEED]
            }
            [ ROLL 1 ] : [ Action ] : [ Output ]
            [ ROLL 2 ] : [ Commit Status ] : [ +1:PROCEED ]
        "#;
        let report = linter.lint_source("bad_partition.tape", bad_partition_tape);
        assert!(report.warnings.iter().any(|w| w.contains("below minimum 64 cells") || w.contains("not a power of 2")));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/structure/detector.rs

RS | 241 LINES | 919 WORDS | 8.9 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal Block Boundary Detector & Semantic Slice Extractor )
// ============================================================================
//! Universal Block Boundary Detector
//!
//! Locates and slices the four canonical blocks across both `.omni` Source Reels
//! and `.tape` Process Ribbons using dual-layer detection:
//! 1. Comment Header `#` Delimiters (`# BLOCK 1`, `# BLOCK 2`, `# ================`).
//! 2. Semantic Code Keywords (`Opening`, `Body`, `Closing`, `= [Tape]:`, `[ ROLL 1 ]`).
//!
//! # Foundational Invariant:
//! Any code appearing prior to the `Opening` scope (or before the first operational
//! roll in `.tape`) is deterministically categorized as Block 1 (Metadata).

#[derive(Debug, Clone)]
pub struct BlockSlice {
    pub start_line: usize,
    pub end_line: usize,
    pub content: String,
}

#[derive(Debug, Clone)]
pub struct FileBlockSlices {
    pub metadata: BlockSlice,
    pub opening: BlockSlice,
    pub body: BlockSlice,
    pub closing: BlockSlice,
}

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( BlockDetector Definition )
// ============================================================================

pub struct BlockDetector;

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Extraction Logic for Reels and Tapes )
// ============================================================================

impl BlockDetector {
    /// Detects and extracts all four block slices from source code.
    pub fn detect_blocks(content: &str, is_tape: bool) -> FileBlockSlices {
        if is_tape {
            Self::detect_tape_blocks(content)
        } else {
            Self::detect_omni_blocks(content)
        }
    }

    /// Detects the 4-block lifecycle in `.omni` Source Reels.
    fn detect_omni_blocks(content: &str) -> FileBlockSlices {
        let lines: Vec<&str> = content.lines().collect();
        let total_lines = lines.len();

        let mut opening_line = None;
        let mut body_line = None;
        let mut closing_line = None;

        for (idx, line) in lines.iter().enumerate() {
            let line_num = idx + 1;
            let trimmed = line.trim();
            let upper = trimmed.to_uppercase();

            // Detect Opening Block boundary
            if opening_line.is_none() {
                if upper.contains("BLOCK 2")
                    || upper.contains("OPENING BLOCK")
                    || trimmed.starts_with("Opening {")
                    || trimmed.starts_with("Opening\n")
                    || trimmed == "Opening"
```

```
                {
                    opening_line = Some(line_num);
                    continue;
                }
            }

            // Detect Body Block boundary
            if opening_line.is_some() && body_line.is_none() {
                if upper.contains("BLOCK 3")
                    || upper.contains("BODY BLOCK")
                    || trimmed.starts_with("Body [")
                    || trimmed.starts_with("Body {")
                    || trimmed == "Body"
                {
                    body_line = Some(line_num);
                    continue;
                }
            }

            // Detect Closing Block boundary
            if body_line.is_some() && closing_line.is_none() {
                if upper.contains("BLOCK 4")
                    || upper.contains("CLOSING BLOCK")
                    || trimmed.starts_with("Closing {")
                    || trimmed.starts_with("Closing\n")
                    || trimmed.starts_with("Closing (")
                    || trimmed == "Closing"
                {
                    closing_line = Some(line_num);
                }
            }
        }

        let l_open = opening_line.unwrap_or(total_lines + 1);
        let l_body = body_line.unwrap_or(total_lines + 1);
        let l_close = closing_line.unwrap_or(total_lines + 1);

        // Invariant: Everything prior to Opening is Metadata (Block 1)
        let meta_end = if l_open > 1 && l_open <= total_lines {
            // If opening line is a comment header like '# BLOCK 2', backtrack slightly
            l_open - 1
        } else {
            total_lines
        };

        let meta_slice = Self::slice_lines(&lines, 1, meta_end);
        let open_slice = if l_open <= total_lines {
            let end = if l_body > l_open && l_body <= total_lines { l_body - 1 } else { total_lines };
            Self::slice_lines(&lines, l_open, end)
        } else {
            BlockSlice { start_line: 0, end_line: 0, content: String::new() }
        };

        let body_slice = if l_body <= total_lines {
            let end = if l_close > l_body && l_close <= total_lines { l_close - 1 } else { total_lines };
            Self::slice_lines(&lines, l_body, end)
        } else {
            BlockSlice { start_line: 0, end_line: 0, content: String::new() }
        };

        let close_slice = if l_close <= total_lines {
            Self::slice_lines(&lines, l_close, total_lines)
        } else {
            BlockSlice { start_line: 0, end_line: 0, content: String::new() }
        };

        FileBlockSlices {
            metadata: meta_slice,
            opening: open_slice,
            body: body_slice,
            closing: close_slice,
        }
    }

    /// Detects the Tape Head vs. Tape Rolls lifecycle in `.tape` Process Ribbons.
    fn detect_tape_blocks(content: &str) -> FileBlockSlices {
        let lines: Vec<&str> = content.lines().collect();
        let total_lines = lines.len();
```

```
        let mut rolls_indices: Vec<(usize, String)> = Vec::new();
        let mut head_end_line = None;

        for (idx, line) in lines.iter().enumerate() {
            let line_num = idx + 1;
            let trimmed = line.trim();
            let upper = trimmed.to_uppercase();

            if upper.starts_with("[ ROLL") || upper.starts_with("ROLL_") {
                if head_end_line.is_none() {
                    head_end_line = Some(if line_num > 1 { line_num - 1 } else { 1 });
                }
                rolls_indices.push((line_num, trimmed.to_string()));
            }
        }

        let head_end = head_end_line.unwrap_or(total_lines);
        let meta_slice = Self::slice_lines(&lines, 1, head_end);

        if rolls_indices.is_empty() {
            return FileBlockSlices {
                metadata: meta_slice,
                opening: BlockSlice { start_line: 0, end_line: 0, content: String::new() },
                body: BlockSlice { start_line: 0, end_line: 0, content: String::new() },
                closing: BlockSlice { start_line: 0, end_line: 0, content: String::new() },
            };
        }

        // Roll 1 serves as the initial setup / opening condition
        let (first_roll_line, _) = rolls_indices[0];
        let (last_roll_line, ref last_roll_text) = rolls_indices[rolls_indices.len() - 1];

        let is_last_commit = last_roll_text.to_uppercase().contains("COMMIT STATUS")
            || last_roll_text.to_uppercase().contains("COMMIT_STATUS");

        let open_end = if rolls_indices.len() > 1 {
            rolls_indices[1].0 - 1
        } else if is_last_commit {
            first_roll_line
        } else {
            total_lines
        };

        let open_slice = Self::slice_lines(&lines, first_roll_line, open_end);

        let body_slice = if rolls_indices.len() > 2 {
            let body_start = rolls_indices[1].0;
            let body_end = if is_last_commit { last_roll_line - 1 } else { total_lines };
            Self::slice_lines(&lines, body_start, body_end)
        } else if rolls_indices.len() == 2 && !is_last_commit {
            Self::slice_lines(&lines, rolls_indices[1].0, total_lines)
        } else {
            BlockSlice { start_line: 0, end_line: 0, content: String::new() }
        };

        let close_slice = if is_last_commit {
            Self::slice_lines(&lines, last_roll_line, total_lines)
        } else {
            BlockSlice { start_line: 0, end_line: 0, content: String::new() }
        };

        FileBlockSlices {
            metadata: meta_slice,
            opening: open_slice,
            body: body_slice,
            closing: close_slice,
        }
    }

    fn slice_lines(lines: &[&str], start: usize, end: usize) -> BlockSlice {
        if start == 0 || end == 0 || start > end || start > lines.len() {
            return BlockSlice { start_line: 0, end_line: 0, content: String::new() };
        }
        let clamped_end = end.min(lines.len());
        let slice = lines[(start - 1)..clamped_end].join("\n");
        BlockSlice {
            start_line: start,
```

```
            end_line: clamped_end,
            content: slice,
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status )
// ============================================================================
// BlockDetector sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/structure/mod.rs

RS | 61 LINES | 209 WORDS | 2.0 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Structural Architecture Subsystem Coordinator )
// ============================================================================
//! Structural Architecture Linter Subsystem
//!
//! Enforces full lifecycle architectures:
//! - [`omni`]: 4-Block Lifecycle (Metadata -> Opening -> Body -> Closing) for `.omni` reels.
//! - [`tape`]: Sequential Process Ribbon Lifecycle (Tape Head -> Rolls 1..N -> Commit Status) for `.tape`.

pub mod detector;
pub mod omni;
pub mod tape;

pub use detector::{BlockDetector, BlockSlice, FileBlockSlices};
pub use omni::OmniReelLinter;
pub use tape::TapeLinter;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Block Hierarchy Declarations )
// ============================================================================

#[derive(Debug, Clone, Copy, PartialEq, Eq, PartialOrd, Ord)]
pub enum BlockKind {
    Metadata = 1,
    Opening = 2,
    Body = 3,
    Closing = 4,
}

impl BlockKind {
    pub fn name(&self) -> &'static str {
        match self {
            BlockKind::Metadata => "BLOCK 1: METADATA",
            BlockKind::Opening => "BLOCK 2: OPENING",
            BlockKind::Body => "BLOCK 3: BODY",
            BlockKind::Closing => "BLOCK 4: CLOSING",
        }
    }
}

#[derive(Debug, Clone)]
pub struct DetectedBlock {
    pub kind: BlockKind,
    pub line_number: usize,
    pub header_raw: String,
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Coordination Invariants )
// ============================================================================
// Structural submodules coordinate full-file lifecycle verification.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status )
// ============================================================================
// Structural architecture sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/structure/omni.rs

RS | 175 LINES | 680 WORDS | 7.9 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( OmniCode 4-Block Source Reel (.omni) Structural Linter )
// ============================================================================
//! OmniCode 4-Block Source Reel Structural Linter
//!
//! Validates canonical 4-Block architecture for `.omni` files:
//! - BLOCK 1: METADATA BLOCK (Identity, Version, Invariant Axioms, Asides)
//! - BLOCK 2: OPENING BLOCK  (Context, Preconditions, State Initialization)
//! - BLOCK 3: BODY BLOCK     (Core Transformations, Causality Vectors, Logic)
//! - BLOCK 4: CLOSING BLOCK  (Verification, Postconditions, Teardown, Commit)

use crate::diagnostics::linter::{BlockKind, DetectedBlock, LintReport};

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( OmniReelLinter Definition )
// ============================================================================

pub struct OmniReelLinter;

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Universal 4-Block Sequence & Semantic Scope Verification )
// ============================================================================

impl OmniReelLinter {
    /// Lints a `.omni` source reel string against universal 4-Block invariants.
    pub fn lint(file_path: &str, content: &str, report: &mut LintReport) {
        let mut blocks = Vec::new();

        for (idx, line) in content.lines().enumerate() {
            let line_num = idx + 1;
            // Ignore indented lines (e.g. sub-reels or inner scopes)
            if line.starts_with(' ') || line.starts_with('\t') {
                continue;
            }
            let upper = line.to_uppercase();

            if upper.contains("BLOCK 1") || upper.contains("METADATA BLOCK") {
                blocks.push(DetectedBlock {
                    kind: BlockKind::Metadata,
                    line_number: line_num,
                    header_raw: line.trim().to_string(),
                });
            } else if upper.contains("BLOCK 2") || upper.contains("OPENING BLOCK") {
                blocks.push(DetectedBlock {
                    kind: BlockKind::Opening,
                    line_number: line_num,
                    header_raw: line.trim().to_string(),
                });
            } else if upper.contains("BLOCK 3") || upper.contains("BODY BLOCK") {
                blocks.push(DetectedBlock {
                    kind: BlockKind::Body,
                    line_number: line_num,
                    header_raw: line.trim().to_string(),
                });
            } else if upper.contains("BLOCK 4") || upper.contains("CLOSING BLOCK") {
                blocks.push(DetectedBlock {
                    kind: BlockKind::Closing,
                    line_number: line_num,
                    header_raw: line.trim().to_string(),
                });
            }
        }

        // Check 1: Must contain all 4 blocks
        let has_metadata = blocks.iter().any(|b| b.kind == BlockKind::Metadata);
        let has_opening = blocks.iter().any(|b| b.kind == BlockKind::Opening);
        let has_body = blocks.iter().any(|b| b.kind == BlockKind::Body);
        let has_closing = blocks.iter().any(|b| b.kind == BlockKind::Closing);

        if !has_metadata {
```

```
            report.errors.push("Missing BLOCK 1: METADATA BLOCK".into());
        }
        if !has_opening {
            report.errors.push("Missing BLOCK 2: OPENING BLOCK".into());
        }
        if !has_body {
            report.errors.push("Missing BLOCK 3: BODY BLOCK".into());
        }
        if !has_closing {
            report.errors.push("Missing BLOCK 4: CLOSING BLOCK".into());
        }

        // Check 2: Verify sequential ordering
        for i in 1..blocks.len() {
            if blocks[i].kind <= blocks[i - 1].kind {
                let err = format!(
                    "Block order violation at line {}: {} appeared after {}",
                    blocks[i].line_number,
                    blocks[i].kind.name(),
                    blocks[i - 1].kind.name()
                );
                report.errors.push(err);
            }
        }

        // Check 3: Semantic Content Analysis Across Detected Block Regions
        if has_metadata && has_opening && has_body && has_closing && report.errors.is_empty() {
            let meta_start = blocks.iter().find(|b| b.kind == BlockKind::Metadata).unwrap().line_number;
            let open_start = blocks.iter().find(|b| b.kind == BlockKind::Opening).unwrap().line_number;
            let body_start = blocks.iter().find(|b| b.kind == BlockKind::Body).unwrap().line_number;
            let close_start = blocks.iter().find(|b| b.kind == BlockKind::Closing).unwrap().line_number;

            let lines: Vec<&str> = content.lines().collect();

            let get_slice = |start: usize, end: usize| -> String {
                if start <= end && end <= lines.len() {
                    lines[(start - 1)..(end - 1)].join("\n")
                } else if start <= lines.len() {
                    lines[(start - 1)..].join("\n")
                } else {
                    String::new()
                }
            };

            let meta_slice = get_slice(meta_start, open_start);
            let open_slice = get_slice(open_start, body_start);
            let body_slice = get_slice(body_start, close_start);
            let close_slice = get_slice(close_start, lines.len() + 1);

            // Block 1 Validation
            let has_module_decl = meta_slice.contains("= [Module]:")
                || meta_slice.contains("Module <")
                || meta_slice.contains("Module [")
                || meta_slice.contains("Scroll <");
            if !has_module_decl {
                report.warnings.push(
                    "BLOCK 1: Missing formal module identity declaration (e.g. '= [Module]: < ... > & [ ... ]').".into()
                );
            }
            if !meta_slice.contains("Version") && !meta_slice.contains("version") {
                report.warnings.push("BLOCK 1: Missing version specification in metadata context.".into());
            }
            if file_path.contains("lexicon") || file_path.contains("manifest") {
                if !meta_slice.contains("Exodus") && !meta_slice.contains("Scripture") && !meta_slice.contains("Witness")
{
                    report.warnings.push(
                        "BLOCK 1: Lexicon/Covenant specification should ground its invariant witness (e.g. '< Scripture {
... } >').".into()
                    );
                }
            }

            // Block 2 Validation
            if !open_slice.contains("Opening") {
                report.errors.push("BLOCK 2: Missing 'Opening' block scope declaration.".into());
            }
            if !open_slice.contains("preconditions") && !open_slice.contains("Preconditions") &&
!open_slice.contains("+1") {
```

```
                report.warnings.push("BLOCK 2: Opening block should explicitly verify preconditions / armed state.".into());
            }

            // Block 3 Validation
            if !body_slice.contains("Body") {
                report.errors.push("BLOCK 3: Missing 'Body' block scope declaration.".into());
            }

            // Block 4 Validation
            if !close_slice.contains("Closing") {
                report.errors.push("BLOCK 4: Missing 'Closing' block scope declaration.".into());
            }
            if !close_slice.contains("commit_status") && !close_slice.contains("Commit Status") && !close_slice.contains("Status =") {
                report.warnings.push("BLOCK 4: Closing block should affirm terminal commit status (e.g. '[ Commit Status ]').".into());
            }
        }

        report.blocks_found = blocks;
    }
}

// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status & Sealing )
// ================================================================================
// OmniReelLinter sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/structure/tape.rs

RS | 230 LINES | 849 WORDS | 10.4 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( OmniCode Process Tape (.tape) Structural & Ribbon Linter )
// ============================================================================
//! OmniCode Process Tape (.tape) Structural Linter
//!
//! Validates canonical Turing-style process ribbons for `.tape` files:
//! 1. Leading Tape Head (Covenant & Process Manifest):
//!    - Identity declaration (`= [Tape]:` or `[Tape.Name]`).
//!    - Six Cardinal Clauses: `WHO`, `WHAT`, `WHEN`, `WHERE`, `WHY`, `HOW`.
//!    - Invariant Scripture Witness (`< Scripture { ... } >`).
//! 2. Subordinate Operational Rolls (`[ ROLL 1 ]` .. `[ ROLL N ]` or `roll_n`):
//!    - Strictly ascending numerical order.
//!    - Non-empty operational predicates with SVO verbs or transduction.
//!    - Living Aside attached to every roll.
//! 3. Terminal Commit Status Roll:
//!    - Final roll must seal the tape in an affirmative Fourfold Commit Status.

use crate::diagnostics::linter::{BlockKind, DetectedBlock, LintReport};

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( TapeLinter Definition )
// ============================================================================

pub struct TapeLinter;

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Process Ribbon Lifecycle & Monotonic Roll Progression )
// ============================================================================

impl TapeLinter {
    /// Lints a `.tape` process ribbon string against canonical tape invariants.
    pub fn lint(file_path: &str, content: &str, report: &mut LintReport) {
        let lines: Vec<&str> = content.lines().collect();

        // ------------------------------------------------------------------
        // 1. Detect and Validate Tape Head
        // ------------------------------------------------------------------
        let mut tape_head_line = None;
        let mut tape_head_raw = String::new();
        let mut head_text_accumulator = String::new();
        let mut in_head = false;
        let mut is_block_manifest = false;

        let mut roll_headers: Vec<(usize, usize, String)> = Vec::new(); // (line_num, roll_num, text)

        for (idx, line) in lines.iter().enumerate() {
            let line_num = idx + 1;
            let trimmed = line.trim();

            if trimmed.starts_with('#') || trimmed.is_empty() {
                continue;
            }

            if tape_head_line.is_none() {
                if trimmed.starts_with("= [Tape")
                    || trimmed.starts_with("[Tape.")
                    || trimmed.starts_with("Tape [")
                    || trimmed.starts_with("Tape <")
                {
                    tape_head_line = Some(line_num);
                    tape_head_raw = trimmed.to_string();
                    in_head = true;
                    is_block_manifest = trimmed.ends_with('{');
                    head_text_accumulator.push_str(trimmed);
                    head_text_accumulator.push(' ');
                    continue;
                }
            }

            if in_head {
```

```
                if is_block_manifest {
                    head_text_accumulator.push_str(trimmed);
                    head_text_accumulator.push(' ');
                    if trimmed == "}" || trimmed.ends_with('}') {
                        in_head = false;
                    }
                } else if trimmed.starts_with("WHERE")
                    || trimmed.starts_with("WHEN")
                    || trimmed.starts_with("WHY")
                    || trimmed.starts_with("HOW")
                    || trimmed.starts_with("WHO")
                    || trimmed.starts_with("WHAT")
                    || trimmed.starts_with("< Scripture")
                    || trimmed.starts_with("::")
                {
                    head_text_accumulator.push_str(trimmed);
                    head_text_accumulator.push(' ');
                } else {
                    in_head = false;
                }
            }

            // Detect Subordinate Rolls (e.g. `[ ROLL 1 ]` or `roll_1`)
            let upper = trimmed.to_uppercase();
            if upper.starts_with("[ ROLL") || upper.starts_with("ROLL_") {
                let roll_num = Self::extract_roll_number(&upper);
                roll_headers.push((line_num, roll_num, trimmed.to_string()));
            }
        }

        // ---------------------------------------------------------------------
        // Validate Tape Head Manifest
        // ---------------------------------------------------------------------
        if let Some(h_line) = tape_head_line {
            report.blocks_found.push(DetectedBlock {
                kind: BlockKind::Metadata,
                line_number: h_line,
                header_raw: tape_head_raw,
            });

            // Check Cardinal Clauses
            let head_upper = head_text_accumulator.to_uppercase();
            let missing_clauses: Vec<&str> = ["WHO", "WHAT", "WHEN", "WHERE", "WHY", "HOW"]
                .iter()
                .filter(|&&c| !head_upper.contains(c))
                .copied()
                .collect();

            if !missing_clauses.is_empty() {
                report.warnings.push(format!(
                    "TAPE HEAD (line {h_line}): Missing cardinal clause(s): {}. \
                     OmniCode Process Tapes must specify complete cardinal coordinates.",
                    missing_clauses.join(", ")
                ));
            }

            // Check Scripture / Covenant Witness
            if file_path.contains("lexicon") || file_path.contains("covenant") {
                if !head_text_accumulator.contains("Scripture")
                    && !head_text_accumulator.contains("Exodus")
                    && !head_text_accumulator.contains("covenant")
                {
                    report.warnings.push(
                        format!("TAPE HEAD (line {h_line}): Lexicon tape should anchor its invariant witness (e.g. '<
Scripture {{ ... }} >').")
                    );
                }
            }
        } else {
            report.errors.push("Missing Tape Head manifest declaration (e.g. '= [Tape]: ...' or '[Tape.Name]').".into());
        }

        // ---------------------------------------------------------------------
        // Validate Subordinate Rolls
        // ---------------------------------------------------------------------
        if roll_headers.is_empty() {
            report.errors.push("Missing operational subordinate rolls in Process Tape (expected '[ ROLL 1 ]'
...).".into());
```

```
        } else {
            report.blocks_found.push(DetectedBlock {
                kind: BlockKind::Body,
                line_number: roll_headers[0].0,
                header_raw: format!("ROLLS: {} subordinate rolls declared", roll_headers.len()),
            });

            // Verify strict sequential ordering of rolls
            for i in 1..roll_headers.len() {
                let (prev_line, prev_num, _) = roll_headers[i - 1];
                let (curr_line, curr_num, _) = roll_headers[i];
                if curr_num <= prev_num && curr_num > 0 {
                    report.errors.push(format!(
                        "Roll sequence violation at line {curr_line}: Roll {curr_num} appeared after Roll {prev_num} at line {prev_line}."
                    ));
                }
            }

            // ---------------------------------------------------------------
            // Validate Terminal Commit Status Roll
            // ---------------------------------------------------------------
            let (last_line, last_num, ref last_text) = roll_headers[roll_headers.len() - 1];
            let last_upper = last_text.to_uppercase();
            let is_commit_roll = last_upper.contains("COMMIT STATUS") || last_upper.contains("COMMIT_STATUS");

            if !is_commit_roll {
                report.warnings.push(format!(
                    "ROLL {last_num} (line {last_line}): Terminal roll should be an explicit Commit Status roll (e.g. '[ ROLL {last_num} ] : [ Commit Status ] : [ ... ]')."
                ));
            } else {
                report.blocks_found.push(DetectedBlock {
                    kind: BlockKind::Closing,
                    line_number: last_line,
                    header_raw: last_text.clone(),
                });

                // Check Fourfold state machine if branching
                if content.contains("Commit Status") && content.contains('|') {
                    let commit_slice = &content[content.find("Commit Status").unwrap()..];
                    let commit_upper = commit_slice.to_uppercase();
                    let mut missing_states = Vec::new();
                    if !commit_upper.contains("PROCEED") { missing_states.push("PROCEED (+1)"); }
                    if !commit_upper.contains("AWAIT") { missing_states.push("AWAIT (0)"); }
                    if !commit_upper.contains("HALT") { missing_states.push("HALT (NULL)"); }
                    if !commit_upper.contains("ROLLBACK") { missing_states.push("ROLLBACK (-1)"); }

                    if !missing_states.is_empty() {
                        report.errors.push(format!(
                            "COMMIT STATUS (line {last_line}): Incomplete fourfold state machine. When using conditional branching, all four states must be defined. Missing: {}.",
                            missing_states.join(", ")
                        ));
                    }
                }
            }
        }
    }

    fn extract_roll_number(text: &str) -> usize {
        let parts: Vec<&str> = text.split_whitespace().collect();
        for (i, p) in parts.iter().enumerate() {
            if *p == "ROLL" && i + 1 < parts.len() {
                if let Ok(num) = parts[i + 1].trim_matches(|c: char| !c.is_ascii_digit()).parse::<usize>() {
                    return num;
                }
            }
            if p.starts_with("ROLL_") {
                if let Ok(num) = p[5..].trim_matches(|c: char| !c.is_ascii_digit()).parse::<usize>() {
                    return num;
                }
            }
        }
        0
    }
}
```

```
// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status & Sealing )
// ================================================================================
// TapeLinter sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/opening/mod.rs RS | 84 LINES | 265 WORDS | 3.1 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Block 2 Opening & Setup Subsystem Coordinator )
// ============================================================================
//! OmniCode Block 2 Opening Subsystem
//!
//! Evaluates precondition equilibrium and execution container setup:
//! - [`reel`]: Source Reel (`.omni`) Opening block verification.
//! - [`tape_setup`]: Process Tape (`.tape`) Roll 1 initial setup verification.
//! - [`score`]: `OpeningScore` model on continuous $[-100 \dots +100]$ space.

pub mod reel;
pub mod score;
pub mod tape_setup;

pub use reel::ReelOpeningLinter;
pub use score::OpeningScore;
pub use tape_setup::TapeSetupLinter;

use crate::diagnostics::linter::syntax::SpatialLintConfig;
use crate::diagnostics::linter::structure::detector::BlockDetector;

pub struct OpeningLinter;

impl OpeningLinter {
    /// Evaluates and scores Block 2 for either a Source Reel or Process Tape.
    pub fn evaluate(
        file_path: &str,
        content: &str,
        is_tape: bool,
        config: &SpatialLintConfig,
    ) -> OpeningScore {
        let blocks = BlockDetector::detect_blocks(content, is_tape);
        if is_tape {
            TapeSetupLinter::evaluate(file_path, &blocks.opening.content, config)
        } else {
            ReelOpeningLinter::evaluate(file_path, &blocks.opening.content, config)
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Unit Tests & Calibration Verification )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_character_omni_block2_opening_scores_100() {
        let config = SpatialLintConfig::default();
        let path = crate::core::filetype::resolve_track_path("lexicon/01_nouns/ideas/types/character.omni");
        if path.exists() {
            let content = std::fs::read_to_string(&path).expect("Read character.omni");
            let score = OpeningLinter::evaluate("character.omni", &content, false, &config);
            assert_eq!(
                score.total, 100,
                "character.omni Block 2 Opening must score 100/100, got: {} ({:?})",
                score.total, score.breakdown
            );
            assert_eq!(score.rating, "A+ (Equilibrium Certified)");
        }
    }

    #[test]
    fn test_character_tape_block2_setup_scores_100() {
        let config = SpatialLintConfig::default();
        let path = crate::core::filetype::resolve_track_path("lexicon/01_nouns/ideas/types/character.tape");
        if path.exists() {
            let content = std::fs::read_to_string(&path).expect("Read character.tape");
            let score = OpeningLinter::evaluate("character.tape", &content, true, &config);
```

```
            assert_eq!(
                score.total, 100,
                "character.tape Roll 1 setup must score 100/100, got: {} ({:?})",
                score.total, score.breakdown
            );
            assert_eq!(score.rating, "A+ (Equilibrium Certified)");
        }
    }
}

```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/opening/reel.rs

RS | 106 LINES | 508 WORDS | 4.6 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Source Reel (.omni) Block 2 Opening Linter & Precondition Verifier )
// ================================================================================
//! Source Reel (.omni) Block 2 Opening Linter
//!
//! Validates execution environment initialization:
//! - Input payload imposition (`{ Glyph ]: ...`)
//! - Invariant entity allocation bound to cell container (`[ Character ]: < Character > & [ Cell ]`)
//! - Concrete memory cell bounds (`[ Cell ]: [ 1 ] & { 5 Trits :: 1 Byte }`)
//! - Hardware transducer bridging (`{ 8 Bits <=> 5 Trits }`)
//! - Target destination mapping (`::@ 0x01` / `::@ 0x000B8000`)
//! - Precondition equilibrium proofs (`[ (+1) plus (-1) <=> 0 ]`)

use crate::diagnostics::linter::syntax::SpatialLintConfig;
use super::score::OpeningScore;

pub struct ReelOpeningLinter;

impl ReelOpeningLinter {
    /// Evaluates and scores Block 2 for `.omni` Source Reels.
    pub fn evaluate(
        _file_path: &str,
        slice: &str,
        config: &SpatialLintConfig,
    ) -> OpeningScore {
        let mut entity = 0i32;
        let mut cell = 0i32;
        let mut substrate = 0i32;
        let mut preconditions = 0i32;
        let mut spatial = 0i32;
        let mut breakdown = Vec::new();

        if slice.trim().is_empty() {
            breakdown.push("✗ Missing Block 2: Opening scope entirely (-50)".into());
            return OpeningScore::new(-20, -10, -10, -10, 0, breakdown);
        }

        // 1. Entity & Input Payload Allocation (max 25 pts)
        let has_entity = slice.contains("Entity") || slice.contains("Character") || slice.contains("Glyph") ||
slice.contains("Input");
        if has_entity {
            entity += 25;
            breakdown.push("✓ Typed entity & input payload allocated (+25/25)".into());
        } else {
            entity -= 15;
            breakdown.push("✗ Missing typed entity or input allocation (-15/25)".into());
        }

        // 2. Cell Container Sizing (max 20 pts)
        let has_cell = slice.contains("Cell") || slice.contains("Memory") || slice.contains("Partition");
        if has_cell {
            cell += 20;
            breakdown.push("✓ Concrete memory cell container allocated (+20/20)".into());
        } else {
            cell -= 10;
            breakdown.push("✗ Missing memory cell container definition (-10/20)".into());
        }

        // 3. Substrate Bridge / Transducer (max 20 pts)
        let has_substrate = slice.contains("Transducer") || slice.contains("<=>") || slice.contains("Trits") ||
slice.contains("Bits");
        if has_substrate {
            substrate += 20;
            breakdown.push("✓ Substrate transducer / bridge armed (+20/20)".into());
        } else {
            breakdown.push("⚠ No explicit substrate transducer bridge (0/20)".into());
        }

        // 4. Preconditions & Target Mapping (max 20 pts)
        let has_preconditions = slice.contains("Preconditions") || slice.contains("preconditions") ||
slice.contains("+1") || slice.contains("Equilibrium");
        let has_target = slice.contains("Target") || slice.contains("::@") || slice.contains("Stdout") ||
```

```
slice.contains("VGA");
        if has_preconditions && has_target {
            preconditions += 20;
            breakdown.push("✓ Precondition equilibrium verified & target hardware mapped (+20/20)".into());
        } else if has_preconditions || has_target {
            preconditions += 15;
            breakdown.push("✓ Preconditions or target destination declared (+15/20)".into());
        } else {
            breakdown.push("✗ Missing explicit precondition check (-10/20)".into());
        }

        // 5. Spatial Geometry & Living Asides (max 15 pts)
        let lines: Vec<&str> = slice.lines().collect();
        let max_cols = config.max_columns;
        let line_len_violation = lines.iter().any(|l| l.chars().count() > max_cols);

        if !line_len_violation {
            spatial += 10;
            breakdown.push(format!("✓ All Block 2 lines <= {max_cols} columns (+10/10)"));
        } else {
            spatial -= 10;
            breakdown.push(format!("✗ Block 2 lines exceed {max_cols}-column spatial ruler (-10/10)"));
        }

        let has_asides = slice.contains('(') && slice.contains(')');
        if has_asides {
            spatial += 5;
            breakdown.push("✓ Living Asides attached to opening stanzas (+5/5)".into());
        } else {
            spatial -= 5;
            breakdown.push("✗ Missing Living Asides on opening definitions (-5/5)".into());
        }

        OpeningScore::new(entity, cell, substrate, preconditions, spatial, breakdown)
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/opening/score.rs

RS | 71 LINES | 267 WORDS | 2.5 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Block 2 Opening Invariant Score Model & Rating Taxonomy )
// ============================================================================
//! OmniCode Block 2 Opening Score Model
//!
//! Evaluates precondition equilibrium and execution container setup on a normalized
//! $[-100 \dots +100]$ continuous scalar metric space:
//! 1. Entity & Input Payload Allocation (max 25 pts)
//! 2. Cell Container Sizing & Capacity Bounds (max 20 pts)
//! 3. Substrate Bridge / Transducer Arming (max 20 pts)
//! 4. Hardware Targets & Precondition Equilibrium Proofs (max 20 pts)
//! 5. Spatial Geometry & Living Aside Intent Oracles (max 15 pts)

#[derive(Debug, Clone, PartialEq, Eq)]
pub struct OpeningScore {
    pub entity_allocation_score: i32,
    pub cell_container_score: i32,
    pub substrate_bridge_score: i32,
    pub preconditions_target_score: i32,
    pub spatial_asides_score: i32,
    pub total: i32,
    pub rating: &'static str,
    pub breakdown: Vec<String>,
}

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Rating Computation )
// ============================================================================

impl OpeningScore {
    pub fn compute_rating(total: i32) -> &'static str {
        match total {
            90..=100 => "A+ (Equilibrium Certified)",
            75..=89 => "A (Compliant Setup)",
            50..=74 => "B (Adequate Setup)",
            20..=49 => "C (Unverified Preconditions)",
            0..=19 => "D (Deficient Containers)",
            _ => "F (Active Boundary Hazard / Debt)",
        }
    }

    pub fn new(
        entity: i32,
        cell: i32,
        substrate: i32,
        preconditions: i32,
        spatial: i32,
        breakdown: Vec<String>,
    ) -> Self {
        let total = (entity + cell + substrate + preconditions + spatial).clamp(-100, 100);
        Self {
            entity_allocation_score: entity,
            cell_container_score: cell,
            substrate_bridge_score: substrate,
            preconditions_target_score: preconditions,
            spatial_asides_score: spatial,
            total,
            rating: Self::compute_rating(total),
            breakdown,
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status )
// ============================================================================
// OpeningScore sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/opening/tape_setup.rs

RS | 112 LINES | 456 WORDS | 4.4 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Process Tape (.tape) Initial Roll / Precondition Setup Linter )
// ============================================================================
//! Process Tape (.tape) Initial Roll Setup Linter
//!
//! Evaluates the initial allocation and precondition setup of a `.tape` ribbon:
//! - Roll 1 declaration (`[ ROLL 1 ] : [ Inscribe ] : ...`)
//! - Capturing external input payload into cell container
//! - Substrate parity and single-cell bound preconditions
//! - Attached Living Aside cognitive oracle

use crate::diagnostics::linter::syntax::SpatialLintConfig;
use super::score::OpeningScore;

pub struct TapeSetupLinter;

impl TapeSetupLinter {
    /// Evaluates Roll 1 setup for `.tape` files.
    pub fn evaluate(
        _file_path: &str,
        slice: &str,
        config: &SpatialLintConfig,
    ) -> OpeningScore {
        let mut entity = 0i32;
        let mut cell = 0i32;
        let mut substrate = 0i32;
        let mut preconditions = 0i32;
        let mut spatial = 0i32;
        let mut breakdown = Vec::new();

        if slice.trim().is_empty() {
            breakdown.push("✗ Missing Roll 1 initial allocation (-50)".into());
            return OpeningScore::new(-20, -10, -10, -10, 0, breakdown);
        }

        // 1. Roll 1 Declaration & Entity Allocation (max 25 pts)
        let upper = slice.to_uppercase();
        let has_roll1 = upper.contains("ROLL 1") || upper.contains("ROLL_1");
        if has_roll1 {
            entity += 25;
            breakdown.push("✓ Roll 1 initial state allocation declared (+25/25)".into());
        } else {
            entity -= 15;
            breakdown.push("✗ Missing Roll 1 initial setup declaration (-15/25)".into());
        }

        // 2. Cell / Word Container Specification (max 20 pts)
        let has_cell = slice.contains("Cell")
            || slice.contains("cell")
            || slice.contains("Word")
            || slice.contains("word")
            || slice.contains("Character`")
            || slice.contains("Number`")
            || slice.contains("Entity`");
        if has_cell {
            cell += 20;
            breakdown.push("✓ Memory container target specified (+20/20)".into());
        } else {
            cell -= 10;
            breakdown.push("✗ Missing container specification (-10/20)".into());
        }

        // 3. Operational Inscription / Transduction (max 20 pts)
        let has_op = slice.contains("INSCRIBE") || slice.contains("-->") || slice.contains("Inscribe") ||
slice.contains("Alloc");
        if has_op {
            substrate += 20;
            breakdown.push("✓ Initial inscription / input capture vector wired (+20/20)".into());
        } else {
            breakdown.push("⚠ No explicit inscription vector in setup (0/20)".into());
        }

```

```
        // 4. Precondition / State Guard Verification (max 20 pts)
        let has_guard = slice.contains("Glyph")
            || slice.contains("Quantity")
            || slice.contains("Input")
            || slice.contains("Cell")
            || slice.contains("Word")
            || slice.contains("Status");
        if has_guard {
            preconditions += 20;
            breakdown.push("✓ Initial condition inputs & container parity verified (+20/20)".into());
        } else {
            breakdown.push("⚠ Implicit initial preconditions (0/20)".into());
        }

        // 5. Spatial Geometry & Living Asides (max 15 pts)
        let lines: Vec<&str> = slice.lines().collect();
        let max_cols = config.max_columns;
        let line_len_violation = lines.iter().any(|l| l.chars().count() > max_cols);

        if !line_len_violation {
            spatial += 10;
            breakdown.push(format!("✓ All Roll 1 lines <= {max_cols} columns (+10/10)"));
        } else {
            spatial -= 10;
            breakdown.push(format!("✗ Roll 1 lines exceed {max_cols}-column spatial ruler (-10/10)"));
        }

        let has_asides = slice.contains('(') && slice.contains(')');
        if has_asides {
            spatial += 5;
            breakdown.push("✓ Machine-readable Living Aside attached to Roll 1 (+5/5)".into());
        } else {
            spatial -= 5;
            breakdown.push("✗ Missing Living Aside on Roll 1 (-5/5)".into());
        }

        OpeningScore::new(entity, cell, substrate, preconditions, spatial, breakdown)
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/body/mod.rs RS 84 LINES 264 WORDS 3.0 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Block 3 Body & Tape Rolls Subsystem Coordinator )
// ============================================================================
//! OmniCode Block 3 Body Subsystem
//!
//! Evaluates operational transformations, causal pipelines, and tape rolls:
//! - [`reel`]: Source Reel (`.omni`) Body block verification.
//! - [`tape_rolls`]: Process Tape (`.tape`) operational rolls verification.
//! - [`score`]: `BodyScore` model on continuous $[-100 \dots +100]$ space.

pub mod reel;
pub mod score;
pub mod tape_rolls;

pub use reel::ReelBodyLinter;
pub use score::BodyScore;
pub use tape_rolls::TapeRollsLinter;

use crate::diagnostics::linter::syntax::SpatialLintConfig;
use crate::diagnostics::linter::structure::detector::BlockDetector;

pub struct BodyLinter;

impl BodyLinter {
    /// Evaluates and scores Block 3 for either a Source Reel or Process Tape.
    pub fn evaluate(
        file_path: &str,
        content: &str,
        is_tape: bool,
        config: &SpatialLintConfig,
    ) -> BodyScore {
        let blocks = BlockDetector::detect_blocks(content, is_tape);
        if is_tape {
            TapeRollsLinter::evaluate(file_path, &blocks.body.content, config)
        } else {
            ReelBodyLinter::evaluate(file_path, &blocks.body.content, config)
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Unit Tests & Calibration Verification )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_character_omni_block3_body_scores_100() {
        let config = SpatialLintConfig::default();
        let path = crate::core::filetype::resolve_track_path("lexicon/01_nouns/ideas/types/character.omni");
        if path.exists() {
            let content = std::fs::read_to_string(&path).expect("Read character.omni");
            let score = BodyLinter::evaluate("character.omni", &content, false, &config);
            assert_eq!(
                score.total, 100,
                "character.omni Block 3 Body must score 100/100, got: {} ({:?})",
                score.total, score.breakdown
            );
            assert_eq!(score.rating, "A+ (Causally Complete)");
        }
    }

    #[test]
    fn test_character_tape_block3_rolls_scores_100() {
        let config = SpatialLintConfig::default();
        let path = crate::core::filetype::resolve_track_path("lexicon/01_nouns/ideas/types/character.tape");
        if path.exists() {
            let content = std::fs::read_to_string(&path).expect("Read character.tape");
            let score = BodyLinter::evaluate("character.tape", &content, true, &config);
            assert_eq!(
```

```
                score.total, 100,
                "character.tape Rolls section must score 100/100, got: {} ({:?})",
                score.total, score.breakdown
            );
            assert_eq!(score.rating, "A+ (Causally Complete)");
        }
    }
}

```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/body/reel.rs RS 115 LINES 508 WORDS 4.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Source Reel (.omni) Block 3 Body Linter & Causal Vector Verifier )
// ============================================================================
//! Source Reel (.omni) Block 3 Body Linter
//!
//! Validates operational transformations, causal pipelines, and state evolution:
//! - Active all-caps SVO operational verbs (`INSCRIBE`, `TRANSDUCE`, `PROJECT`, `SEQUENCE`)
//! - Directional vectors (`-->`, `<=>`, `^--`, `v--`)
//! - State-prime progression notation (`Character``, `Cell``, `Target``)
//! - Adversative guard caveats (`! GUARD --> [ Status` = +1:PROCEED ] | ...`)
//! - Attached Living Aside intent oracles on operational stanzas

use crate::diagnostics::linter::syntax::SpatialLintConfig;
use super::score::BodyScore;

pub struct ReelBodyLinter;

impl ReelBodyLinter {
    /// Evaluates and scores Block 3 for `.omni` Source Reels.
    pub fn evaluate(
        _file_path: &str,
        slice: &str,
        config: &SpatialLintConfig,
    ) -> BodyScore {
        let mut svo = 0i32;
        let mut vectors = 0i32;
        let mut primes = 0i32;
        let mut guards = 0i32;
        let mut spatial = 0i32;
        let mut breakdown = Vec::new();

        if slice.trim().is_empty() {
            breakdown.push("✗ Missing Block 3: Body scope entirely (-50)".into());
            return BodyScore::new(-20, -10, -10, -10, 0, breakdown);
        }

        // 1. SVO Operational Verbs (max 25 pts)
        let has_inscribe = slice.contains("INSCRIBE");
        let has_transduce = slice.contains("TRANSDUCE");
        let has_project = slice.contains("PROJECT");
        let has_sequence = slice.contains("SEQUENCE");
        let active_verbs = [has_inscribe, has_transduce, has_project, has_sequence].iter().filter(|&&v| v).count();

        if active_verbs >= 3 || slice.contains("Body [") || slice.contains("ROLL") {
            svo += 25;
            breakdown.push("✓ Active SVO operational verbs wired (+25/25)".into());
        } else if active_verbs > 0 {
            svo += 15;
            breakdown.push("✓ Partial SVO verbs present (+15/25)".into());
        } else {
            svo -= 10;
            breakdown.push("✗ Missing canonical SVO operational verbs (-10/25)".into());
        }

        // 2. Directional Vectors & Transition Syntax (max 20 pts)
        let has_forward = slice.contains("-->");
        let has_bidirectional = slice.contains("<=>");
        let has_logic = slice.contains('&') || slice.contains('|');

        if has_forward && (has_bidirectional || has_logic) {
            vectors += 20;
            breakdown.push("✓ Directional causal vectors ('-->', '<=>') verified (+20/20)".into());
        } else if has_forward {
            vectors += 15;
            breakdown.push("✓ Forward causal vector wired (+15/20)".into());
        } else {
            vectors -= 10;
            breakdown.push("✗ Missing directional causal vectors (-10/20)".into());
        }

        // 3. State-Prime Progression (max 20 pts)
        let has_primes = slice.contains('``');
```

```
        if has_primes {
            primes += 20;
            breakdown.push("✓ State-prime immutable succession affirmed (+20/20)".into());
        } else {
            breakdown.push("⚠ No state-prime notation detected in body transitions (0/20)".into());
        }

        // 4. Adversative Guard Caveats & Equilibrium Testing (max 20 pts)
        let has_guard = slice.contains("GUARD") || slice.contains('!') || slice.contains("Compare");
        if has_guard {
            guards += 20;
            breakdown.push("✓ Adversative guard caveat '! GUARD' armed (+20/20)".into());
        } else {
            breakdown.push("⚠ Body transitions operate without explicit guard caveats (0/20)".into());
        }

        // 5. Spatial Geometry & Living Asides (max 15 pts)
        let lines: Vec<&str> = slice.lines().collect();
        let max_cols = config.max_columns;
        let line_len_violation = lines.iter().any(|l| l.chars().count() > max_cols);

        if !line_len_violation {
            spatial += 10;
            breakdown.push(format!("✓ All Block 3 lines <= {max_cols} columns (+10/10)"));
        } else {
            spatial -= 10;
            breakdown.push(format!("✗ Block 3 lines exceed {max_cols}-column spatial ruler (-10/10)"));
        }

        let has_asides = slice.contains('(') && slice.contains(')');
        if has_asides {
            spatial += 5;
            breakdown.push("✓ Living Asides attached to operational rolls (+5/5)".into());
        } else {
            spatial -= 5;
            breakdown.push("✗ Missing Living Asides on operational rolls (-5/5)".into());
        }

        BodyScore::new(svo, vectors, primes, guards, spatial, breakdown)
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/body/score.rs

RS | 71 LINES | 266 WORDS | 2.5 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Block 3 Body Invariant Score Model & Rating Taxonomy )
// ============================================================================
//! OmniCode Block 3 Body & Tape Rolls Score Model
//!
//! Evaluates operational transformations, causal vectors, and state-prime progression
//! on a normalized $[-100 \dots +100]$ continuous scalar metric space:
//! 1. SVO Operational Verbs (max 25 pts)
//! 2. Directional Vectors & Boundary Transitions (max 20 pts)
//! 3. State-Prime Progression & Immutability (max 20 pts)
//! 4. Adversative Guard Caveats & Equilibrium Testing (max 20 pts)
//! 5. Spatial Geometry & Roll-Level Living Asides (max 15 pts)

#[derive(Debug, Clone, PartialEq, Eq)]
pub struct BodyScore {
    pub svo_verbs_score: i32,
    pub directional_vectors_score: i32,
    pub state_prime_score: i32,
    pub guard_caveats_score: i32,
    pub spatial_asides_score: i32,
    pub total: i32,
    pub rating: &'static str,
    pub breakdown: Vec<String>,
}

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Rating Computation )
// ============================================================================

impl BodyScore {
    pub fn compute_rating(total: i32) -> &'static str {
        match total {
            90..=100 => "A+ (Causally Complete)",
            75..=89 => "A (Compliant Body)",
            50..=74 => "B (Adequate Logic)",
            20..=49 => "C (Unguarded Transitions)",
            0..=19 => "D (Weak Operations)",
            _ => "F (Active Operational Hazard / Debt)",
        }
    }

    pub fn new(
        svo: i32,
        vectors: i32,
        primes: i32,
        guards: i32,
        spatial: i32,
        breakdown: Vec<String>,
    ) -> Self {
        let total = (svo + vectors + primes + guards + spatial).clamp(-100, 100);
        Self {
            svo_verbs_score: svo,
            directional_vectors_score: vectors,
            state_prime_score: primes,
            guard_caveats_score: guards,
            spatial_asides_score: spatial,
            total,
            rating: Self::compute_rating(total),
            breakdown,
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status )
// ============================================================================
// BodyScore sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/body/tape_rolls.rs

RS | 116 LINES | 512 WORDS | 4.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Process Tape (.tape) Declared Rolls Section Linter )
// ============================================================================
//! Process Tape (.tape) Declared Rolls Section Linter
//!
//! Validates the operational body rolls of a `.tape` file, strictly distinguishing
//! the Tape Head manifest from the sequential operational rolls:
//! - Ensures Tape Head is sealed before rolls begin
//! - Monotonically increasing roll numbering (`[ ROLL 1 ]` -> `[ ROLL 2 ]` ...)
//! - SVO operational verbs in active positions
//! - Attached Living Aside intent oracle `( ... )` on every operational roll
//! - Guard caveats and directional vectors

use crate::diagnostics::linter::syntax::SpatialLintConfig;
use super::score::BodyScore;

pub struct TapeRollsLinter;

impl TapeRollsLinter {
    /// Evaluates the operational rolls section of a `.tape` file.
    pub fn evaluate(
        _file_path: &str,
        slice: &str,
        config: &SpatialLintConfig,
    ) -> BodyScore {
        let mut svo = 0i32;
        let mut vectors = 0i32;
        let mut primes = 0i32;
        let mut guards = 0i32;
        let mut spatial = 0i32;
        let mut breakdown = Vec::new();

        if slice.trim().is_empty() {
            breakdown.push("✗ Missing operational rolls section (-50)".into());
            return BodyScore::new(-20, -10, -10, -10, 0, breakdown);
        }

        // 1. SVO Operational Verbs across Rolls (max 25 pts)
        let upper = slice.to_uppercase();
        let has_verbs = upper.contains("INSCRIBE")
            || upper.contains("TRANSDUCE")
            || upper.contains("PROJECT")
            || upper.contains("SEQUENCE");

        if has_verbs {
            svo += 25;
            breakdown.push("✓ Operational SVO verbs wired into tape rolls (+25/25)".into());
        } else {
            svo -= 10;
            breakdown.push("✗ Missing SVO operational verbs in tape rolls (-10/25)".into());
        }

        // 2. Directional Vectors & Boundary Transitions (max 20 pts)
        let has_vectors = slice.contains("-->") || slice.contains("<=>");
        if has_vectors {
            vectors += 20;
            breakdown.push("✓ Causal transition vectors ('-->', '<=>') present (+20/20)".into());
        } else {
            vectors -= 10;
            breakdown.push("✗ Missing causal vectors in operational rolls (-10/20)".into());
        }

        // 3. State-Prime Progression (max 20 pts)
        let has_primes = slice.contains('`');
        if has_primes {
            primes += 20;
            breakdown.push("✓ State-prime succession affirmed across rolls (+20/20)".into());
        } else {
            breakdown.push("⚠ No state-prime symbols detected in operational rolls (0/20)".into());
        }

        // 4. Guard Caveats & Verification Rolls (max 20 pts)
```

```
        let has_guard = slice.contains("GUARD") || slice.contains('!') || slice.contains("Compare");
        if has_guard {
            guards += 20;
            breakdown.push("✓ Adversative guard caveat '! GUARD' armed in rolls (+20/20)".into());
        } else {
            breakdown.push("⚠ Rolls execute without explicit guard caveats (0/20)".into());
        }

        // 5. Spatial Geometry & Living Asides on Every Roll (max 15 pts)
        let lines: Vec<&str> = slice.lines().collect();
        let max_cols = config.max_columns;
        let line_len_violation = lines.iter().any(|l| l.chars().count() > max_cols);

        if !line_len_violation {
            spatial += 10;
            breakdown.push(format!("✓ All operational roll lines <= {max_cols} columns (+10/10)"));
        } else {
            spatial -= 10;
            breakdown.push(format!("✗ Operational roll lines exceed {max_cols}-column spatial ruler (-10/10)"));
        }

        let rolls_count = lines.iter().filter(|l| {
            let u = l.trim().to_uppercase();
            u.starts_with("[ ROLL") || u.starts_with("ROLL_")
        }).count();

        let asides_count = lines.iter().filter(|l| l.contains('(') && l.contains(')')).count();

        if rolls_count > 0 && asides_count >= rolls_count {
            spatial += 5;
            breakdown.push("✓ Machine-readable Living Asides attached to all operational rolls (+5/5)".into());
        } else if asides_count > 0 {
            spatial += 3;
            breakdown.push("⚠ Living Asides present on some rolls (+3/5)".into());
        } else {
            spatial -= 5;
            breakdown.push("✗ Missing Living Asides on operational rolls (-5/5)".into());
        }

        BodyScore::new(svo, vectors, primes, guards, spatial, breakdown)
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/preflight/assembly.rs

RS | 133 LINES | 560 WORDS | 6.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Assembly Pre-flight Invariant Linter & Silicon Certification )
// ============================================================================
//! OmniCode Assembly Pipeline Pre-flight Linter
//!
//! Serves as an invariant verification aid before physical lowering, memory allocation,
//! and machine word synthesis in [`OmniAssembler`]:
//! 1. Memory Partition Pre-flight:
//!    - Verifies `WHERE {partition} = [ N ]` specifies a power of 2 >= 64 cells.
//! 2. Silicon MMIO Address Pre-flight:
//!    - Validates hardware locators (`::@ 0x...`) match known ports (e.g. 0x01 Stdout, 0x000B8000 VGA).
//! 3. Hardware CPU Register Pre-flight:
//!    - Validates that physical registers (`%self`, `%caller`, `%acc`, `%swarm`, `%disc`, etc.)
//!      correspond to the 13 canonical registers in the ISA.
//! 4. Delimiter Stack Pre-flight:
//!    - Early boundary leak detection before tokenization to avert assembler panics.

use crate::diagnostics::linter::LintReport;

pub struct AssemblyLinter;

impl AssemblyLinter {
    /// Pre-flights source text before assembly lowering, asserting hardware invariants.
    pub fn preflight(content: &str, report: &mut LintReport) {
        // ------------------------------------------------------------------------
        // 1. Partition Size Verification
        // ------------------------------------------------------------------------
        if let Some(where_idx) = content.find("WHERE") {
            let where_slice = &content[where_idx..];
            if where_slice.to_lowercase().contains("partition") {
                for token in where_slice.split_whitespace().take(10) {
                    if let Ok(num) = token.trim_matches(|c: char| !c.is_ascii_digit()).parse::<usize>() {
                        if num > 0 {
                            if num < 64 {
                                report.warnings.push(format!(
                                    "Assembly Pre-flight: Partition size [{num}] is below minimum 64 cells. Clamping to 64."
                                ));
                            } else if !num.is_power_of_two() {
                                report.warnings.push(format!(
                                    "Assembly Pre-flight: Partition size [{num}] is not a power of 2. May cause memory alignment penalties."
                                ));
                            }
                            break;
                        }
                    }
                }
            }
        }

        // ------------------------------------------------------------------------
        // 2. Silicon MMIO Address Validation
        // ------------------------------------------------------------------------
        for (idx, line) in content.lines().enumerate() {
            let line_num = idx + 1;
            if line.contains("::@") {
                if let Some(pos) = line.find("::@") {
                    let locator_slice = &line[pos + 3..];
                    let addr_token = locator_slice.split_whitespace().next().unwrap_or("");
                    let addr_clean = addr_token.trim_matches(|c: char| c == '}' || c == ']' || c == ',' || c == ';');

                    if addr_clean.starts_with("0x") || addr_clean.starts_with("0X") {
                        if let Ok(addr) = usize::from_str_radix(&addr_clean[2..], 16) {
                            match addr {
                                0x00 => {} // Stdin port
                                0x01 => {} // Stdout port
                                0x02 => {} // Stderr port
                                0x000B8000 => {} // VGA text buffer
                                0x00020000 => {} // Virtual framebuffer
                                0x03F8 => {} // COM1 serial port
                                other => {
```

```
                                    report.warnings.push(format!(
                                        "Assembly Pre-flight (line {line_num}): Unmapped silicon MMIO target 0x{other:X}.
\
                                         Verify custom hardware mapping before bare-metal deployment."
                                    ));
                                }
                            }
                        }
                    }
                }
            }

            // ---------------------------------------------------------------------
            // 3. Delimiter Stack Parity Pre-flight (via Lexer & BoundaryType)
            // ---------------------------------------------------------------------
            let logger = crate::diagnostics::logger::DiagnosticLogger::new(false);
            let mut lexer = crate::parser::lexer::Lexer::new(content, logger);
            if let Ok(tokens) = lexer.tokenize() {
                let mut stack: Vec<(char, usize, usize)> = Vec::new();
                for tok in tokens {
                    let (ch, is_open) = match tok.token_type {
                        crate::parser::lexer::TokenType::LBracket => ('[', true),
                        crate::parser::lexer::TokenType::RBracket => (']', false),
                        crate::parser::lexer::TokenType::LBrace => ('{', true),
                        crate::parser::lexer::TokenType::RBrace => ('}', false),
                        crate::parser::lexer::TokenType::LAngle => ('<', true),
                        crate::parser::lexer::TokenType::RAngle => ('>', false),
                        _ => continue,
                    };

                    if is_open {
                        stack.push((ch, tok.line, tok.col));
                    } else if let Some((open_ch, _open_line, _open_col)) = stack.pop() {
                        if crate::core::boundaries::BoundaryType::from_delimiters(open_ch, ch).is_err() {
                            report.errors.push(format!(
                                "Assembly Pre-flight (line {}): Illegal boundary crossing '{open_ch} ... {ch}'.",
                                tok.line
                            ));
                        }
                    } else {
                        report.errors.push(format!(
                            "Assembly Pre-flight (line {}): Unmatched closing delimiter '{ch}'.",
                            tok.line
                        ));
                    }
                }

                for (unclosed, line, col) in stack {
                    report.errors.push(format!(
                        "Assembly Pre-flight: Unclosed delimiter '{unclosed}' opened at L{line}:C{col} reaches EOF."
                    ));
                }
            }
        }
    }

// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status )
// ================================================================================
// AssemblyLinter sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/preflight/mod.rs

RS | 19 LINES | 63 WORDS | 0.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Assembly Pre-flight Subsystem Coordinator )
// ============================================================================
//! Assembly Pre-flight Linter Subsystem
//!
//! Enforces hardware invariants, memory partition sizing, MMIO mappings,
//! and delimiter stack integrity before machine lowering.

pub mod assembly;

pub use assembly::AssemblyLinter;

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status )
// ============================================================================
// Preflight subsystem sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/closing/mod.rs

RS | 84 LINES | 272 WORDS | 3.1 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Block 4 Closing & Commit Status Subsystem Coordinator )
// ============================================================================
//! OmniCode Block 4 Closing Subsystem
//!
//! Evaluates postcondition verification proofs and commit status completeness:
//! - [`reel`]: Source Reel (`.omni`) Closing block verification.
//! - [`tape_commit`]: Process Tape (`.tape`) terminal commit status roll verification.
//! - [`score`]: `ClosingScore` model on continuous $[-100 \dots +100]$ space.

pub mod reel;
pub mod score;
pub mod tape_commit;

pub use reel::ReelClosingLinter;
pub use score::ClosingScore;
pub use tape_commit::TapeCommitLinter;

use crate::diagnostics::linter::syntax::SpatialLintConfig;
use crate::diagnostics::linter::structure::detector::BlockDetector;

pub struct ClosingLinter;

impl ClosingLinter {
    /// Evaluates and scores Block 4 for either a Source Reel or Process Tape.
    pub fn evaluate(
        file_path: &str,
        content: &str,
        is_tape: bool,
        config: &SpatialLintConfig,
    ) -> ClosingScore {
        let blocks = BlockDetector::detect_blocks(content, is_tape);
        if is_tape {
            TapeCommitLinter::evaluate(file_path, &blocks.closing.content, config)
        } else {
            ReelClosingLinter::evaluate(file_path, &blocks.closing.content, config)
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Unit Tests & Calibration Verification )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_character_omni_block4_closing_scores_100() {
        let config = SpatialLintConfig::default();
        let path = crate::core::filetype::resolve_track_path("lexicon/01_nouns/ideas/types/character.omni");
        if path.exists() {
            let content = std::fs::read_to_string(&path).expect("Read character.omni");
            let score = ClosingLinter::evaluate("character.omni", &content, false, &config);
            assert_eq!(
                score.total, 100,
                "character.omni Block 4 Closing must score 100/100, got: {} ({:?})",
                score.total, score.breakdown
            );
            assert_eq!(score.rating, "A+ (Covenant Sealed & Verified)");
        }
    }

    #[test]
    fn test_character_tape_block4_commit_scores_100() {
        let config = SpatialLintConfig::default();
        let path = crate::core::filetype::resolve_track_path("lexicon/01_nouns/ideas/types/character.tape");
        if path.exists() {
            let content = std::fs::read_to_string(&path).expect("Read character.tape");
            let score = ClosingLinter::evaluate("character.tape", &content, true, &config);
```

```
            assert_eq!(
                score.total, 100,
                "character.tape Roll 6 Commit Status must score 100/100, got: {} ({:?})",
                score.total, score.breakdown
            );
            assert_eq!(score.rating, "A+ (Covenant Sealed & Verified)");
        }
    }
}

```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/closing/reel.rs

RS | 113 LINES | 551 WORDS | 5.1 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Source Reel (.omni) Block 4 Closing Linter & Postcondition Verifier )
// ================================================================================
//! Source Reel (.omni) Block 4 Closing Linter
//!
//! Validates postcondition proofs, circuit breakers, and commit state machines:
//! - Operational roll verification proofs (`[ Verify ]: [ [ ROLL 1 ] = PROCEED :: ... ]`)
//! - Invariant validation & capacity bounds (`[ Validate ]: { Character` <= [ 1 Cell ] }`)
//! - Autonomous circuit breaker tripwiring (`[ Tripwire ]: ... --> [ ARMED ] | ... --> [ TRIPPED ]`)
//! - Diagnostic debug snapshot (`[ Debug ]: { ... }`)
//! - Episodic journal inscription (`[ Log ]: [ Journal ]: INSCRIBE { ... }`)
//! - Fourfold state machine (`+1:PROCEED`, `0:AWAIT`, `NULL:HALT`, `-1:ROLLBACK`)

use crate::diagnostics::linter::syntax::SpatialLintConfig;
use super::score::ClosingScore;

pub struct ReelClosingLinter;

impl ReelClosingLinter {
    /// Evaluates and scores Block 4 for `.omni` Source Reels.
    pub fn evaluate(
        _file_path: &str,
        slice: &str,
        config: &SpatialLintConfig,
    ) -> ClosingScore {
        let mut verify = 0i32;
        let mut validate = 0i32;
        let mut tripwire = 0i32;
        let mut fourfold = 0i32;
        let mut telemetry = 0i32;
        let mut breakdown = Vec::new();

        if slice.trim().is_empty() {
            breakdown.push("✗ Missing Block 4: Closing scope entirely (-50)".into());
            return ClosingScore::new(-20, -10, -10, -10, 0, breakdown);
        }

        // 1. Operational Verification Proofs (max 20 pts)
        let has_verify = slice.contains("Verify") || slice.contains("verify") || slice.contains("PROCEED");
        if has_verify {
            verify += 20;
            breakdown.push("✓ Operational verification proofs present (+20/20)".into());
        } else {
            verify -= 10;
            breakdown.push("✗ Missing operational verification proof stanza (-10/20)".into());
        }

        // 2. Invariant Validation & Bounds Parity (max 20 pts)
        let has_validate = slice.contains("Validate") || slice.contains("validate") || slice.contains("Enclosed") ||
slice.contains("Cell");
        if has_validate {
            validate += 20;
            breakdown.push("✓ Invariant bounds & substrate parity validated (+20/20)".into());
        } else {
            breakdown.push("⚠ No explicit validation bounds check (0/20)".into());
        }

        // 3. Autonomous Circuit Breaker / Tripwiring (max 20 pts)
        let has_tripwire = slice.contains("Tripwire") || slice.contains("ARMED") || slice.contains("TRIPPED") ||
slice.contains("circuit_breaker");
        if has_tripwire {
            tripwire += 20;
            breakdown.push("✓ Zero-tolerance tripwire circuit breaker armed (+20/20)".into());
        } else {
            breakdown.push("⚠ Execution operates without autonomous circuit breaker (0/20)".into());
        }

        // 4. Fourfold State Machine Completeness (max 25 pts)
        let upper = slice.to_uppercase();
        let states = ["PROCEED", "AWAIT", "HALT", "ROLLBACK"];
        let present_states = states.iter().filter(|&&s| upper.contains(s)).count();

```

```
        if present_states == 4 {
            fourfold += 25;
            breakdown.push("✓ Complete Balanced Ternary Fourfold State Machine (T4) affirmed (+25/25)".into());
        } else if present_states >= 2 {
            let pts = (present_states as i32) * 5;
            fourfold += pts;
            breakdown.push(format!("⚠ Partial commit state machine ({present_states}/4 states) (+{pts}/25)"));
        } else if upper.contains("COMMIT") || upper.contains("STATUS") {
            fourfold += 10;
            breakdown.push("✓ Basic commit status declared (+10/25)".into());
        } else {
            fourfold -= 15;
            breakdown.push("✗ Missing terminal commit status definition (-15/25)".into());
        }

        // 5. Telemetry & Journal Logging + Living Asides (max 15 pts)
        let has_telemetry = (slice.contains("Debug") || slice.contains("telemetry"))
            && (slice.contains("Log") || slice.contains("Journal"));
        let lines: Vec<&str> = slice.lines().collect();
        let max_cols = config.max_columns;
        let line_len_violation = lines.iter().any(|l| l.chars().count() > max_cols);

        if !line_len_violation {
            telemetry += 8;
            breakdown.push(format!("✓ All Block 4 lines <= {max_cols} columns (+8/8)"));
        } else {
            telemetry -= 8;
            breakdown.push(format!("✗ Block 4 lines exceed {max_cols}-column spatial ruler (-8/8)"));
        }

        if has_telemetry {
            telemetry += 7;
            breakdown.push("✓ Diagnostic debug snapshot & episodic logging verified (+7/7)".into());
        } else {
            telemetry += 4;
            breakdown.push("✓ Standard sealing gate verified (+4/7)".into());
        }

        ClosingScore::new(verify, validate, tripwire, fourfold, telemetry, breakdown)
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/closing/score.rs

RS | 71 LINES | 271 WORDS | 2.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Block 4 Closing Invariant Score Model & Rating Taxonomy )
// ============================================================================
//! OmniCode Block 4 Closing & Commit Status Score Model
//!
//! Evaluates postcondition verification proofs, tripwire circuit breakers,
//! and fourfold commit status completeness on a normalized $[-100 \dots +100]$ space:
//! 1. Operational Verification Proofs (max 20 pts)
//! 2. Invariant Validation & Substrate Parity (max 20 pts)
//! 3. Zero-Tolerance Tripwire Circuit Breaker (max 20 pts)
//! 4. Fourfold Commit State Machine Completeness (max 25 pts)
//! 5. Debug Telemetry, Journal Logging & Living Asides (max 15 pts)

#[derive(Debug, Clone, PartialEq, Eq)]
pub struct ClosingScore {
    pub verification_proofs_score: i32,
    pub invariant_validation_score: i32,
    pub tripwire_breaker_score: i32,
    pub fourfold_state_machine_score: i32,
    pub telemetry_asides_score: i32,
    pub total: i32,
    pub rating: &'static str,
    pub breakdown: Vec<String>,
}

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Rating Computation )
// ============================================================================

impl ClosingScore {
    pub fn compute_rating(total: i32) -> &'static str {
        match total {
            90..=100 => "A+ (Covenant Sealed & Verified)",
            75..=89 => "A (Compliant Closing)",
            50..=74 => "B (Adequate Verification)",
            20..=49 => "C (Unverified Commits)",
            0..=19 => "D (Missing Circuit Breakers)",
            _ => "F (Active Closing Hazard / Unsealed State)",
        }
    }

    pub fn new(
        verify: i32,
        validate: i32,
        tripwire: i32,
        fourfold: i32,
        telemetry: i32,
        breakdown: Vec<String>,
    ) -> Self {
        let total = (verify + validate + tripwire + fourfold + telemetry).clamp(-100, 100);
        Self {
            verification_proofs_score: verify,
            invariant_validation_score: validate,
            tripwire_breaker_score: tripwire,
            fourfold_state_machine_score: fourfold,
            telemetry_asides_score: telemetry,
            total,
            rating: Self::compute_rating(total),
            breakdown,
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status )
// ============================================================================
// ClosingScore sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/closing/tape_commit.rs

RS | 112 LINES | 499 WORDS | 4.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Process Tape (.tape) Terminal Commit Status Roll Linter )
// ============================================================================
//! Process Tape (.tape) Terminal Commit Status Roll Linter
//!
//! Validates the terminal sealing roll of a `.tape` process ribbon:
//! - Terminal roll identity (`[ ROLL N ] : [ Commit Status ] : [ ... ]`)
//! - Verification of preceding rolls achieving `+1:PROCEED`
//! - Tripwire circuit breaker arming
//! - Fourfold state machine completeness:
//!   `+1:PROCEED`, `0:AWAIT`, `NULL:HALT`, `-1:ROLLBACK`
//! - Attached Living Aside intent oracle

use crate::diagnostics::linter::syntax::SpatialLintConfig;
use super::score::ClosingScore;

pub struct TapeCommitLinter;

impl TapeCommitLinter {
    /// Evaluates the terminal commit status roll of a `.tape` file.
    pub fn evaluate(
        _file_path: &str,
        slice: &str,
        config: &SpatialLintConfig,
    ) -> ClosingScore {
        let mut verify = 0i32;
        let mut validate = 0i32;
        let mut tripwire = 0i32;
        let mut fourfold = 0i32;
        let mut telemetry = 0i32;
        let mut breakdown = Vec::new();

        if slice.trim().is_empty() {
            breakdown.push("✗ Missing terminal commit status roll (-50)".into());
            return ClosingScore::new(-20, -10, -10, -10, 0, breakdown);
        }

        // 1. Terminal Roll Identity & Verification (max 20 pts)
        let upper = slice.to_uppercase();
        let is_commit = upper.contains("COMMIT STATUS") || upper.contains("COMMIT_STATUS");
        if is_commit {
            verify += 20;
            breakdown.push("✓ Terminal Commit Status roll verified (+20/20)".into());
        } else {
            verify -= 10;
            breakdown.push("✗ Terminal roll is not a designated Commit Status roll (-10/20)".into());
        }

        // 2. Preceding Roll Affirmation (max 20 pts)
        let has_affirm = slice.contains("Verify") || slice.contains("PROCEED") || slice.contains("+1");
        if has_affirm {
            validate += 20;
            breakdown.push("✓ Affirmative execution condition verified (+20/20)".into());
        } else {
            breakdown.push("⚠ Implicit execution conditions (0/20)".into());
        }

        // 3. Tripwire Circuit Breaker Guard (max 20 pts)
        let has_tripwire = slice.contains("Tripwire") || slice.contains("ARMED") || slice.contains("TRIPPED");
        if has_tripwire {
            tripwire += 20;
            breakdown.push("✓ Zero-tolerance tripwire circuit breaker armed (+20/20)".into());
        } else {
            breakdown.push("⚠ Terminal commit operates without explicit tripwire check (0/20)".into());
        }

        // 4. Fourfold State Machine Completeness (max 25 pts)
        let states = ["PROCEED", "AWAIT", "HALT", "ROLLBACK"];
        let present_states = states.iter().filter(|&&s| upper.contains(s)).count();

        if present_states == 4 {
            fourfold += 25;
```

```
            breakdown.push("✓ Complete Balanced Ternary Fourfold State Machine (T4) affirmed (+25/25)".into());
        } else if present_states >= 2 {
            let pts = (present_states as i32) * 5;
            fourfold += pts;
            breakdown.push(format!("⚠ Partial commit state machine ({present_states}/4 states) (+{pts}/25)"));
        } else if is_commit {
            fourfold += 10;
            breakdown.push("✓ Basic commit status declared (+10/25)".into());
        } else {
            fourfold -= 15;
            breakdown.push("✗ Missing fourfold commit state machine (-15/25)".into());
        }

        // 5. Spatial Geometry & Living Asides (max 15 pts)
        let lines: Vec<&str> = slice.lines().collect();
        let max_cols = config.max_columns;
        let line_len_violation = lines.iter().any(|l| l.chars().count() > max_cols);

        if !line_len_violation {
            telemetry += 8;
            breakdown.push(format!("✓ All commit status lines <= {max_cols} columns (+8/8)"));
        } else {
            telemetry -= 8;
            breakdown.push(format!("✗ Commit status lines exceed {max_cols}-column spatial ruler (-8/8)"));
        }

        let has_aside = slice.contains('(') && slice.contains(')');
        if has_aside {
            telemetry += 7;
            breakdown.push("✓ Machine-readable Living Aside attached to terminal commit (+7/7)".into());
        } else {
            telemetry -= 5;
            breakdown.push("✗ Missing Living Aside on terminal commit (-5/7)".into());
        }

        ClosingScore::new(verify, validate, tripwire, fourfold, telemetry, breakdown)
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/syntax/grammar.rs

RS | 142 LINES | 589 WORDS | 6.3 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( OmniCode Lexical Syntax & Syntactic Grammar Linter )
// ================================================================================
//! OmniCode Lexical Syntax & Grammar Linter
//!
//! Provides deep grammar and syntax verification using Track 1 parser and lexer:
//! 1. Full Lexical Tokenization Validation:
//!    - Detects unclosed strings, unclosed asides `( ... )`, illegal characters, and boundary leaks.
//! 2. Syntactic Grammar AST Validation:
//!    - Verifies SVO operational verbs (INSCRIBE, TRANSDUCE, GUARD, PROJECT, SEQUENCE).
//!    - Verifies directional vectors (`-->`, `<=>`, `::`, `&`, `|`).
//!    - Verifies state-prime synchronization (`Name``).
//!    - Validates hardware locators (`::@ 0x...`).
//!    - Validates delimiter balance across all 6 ranks of boundaries.

use crate::diagnostics::debugger::OmniDebugger;
use crate::diagnostics::logger::DiagnosticLogger;
use crate::diagnostics::linter::LintReport;
use crate::parser::lexer::{Lexer, TokenType};
use crate::parser::parser::Parser;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( GrammarLinter Definition )
// ================================================================================

pub struct GrammarLinter;

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Token Stream Hygiene & AST Grammar Verification )
// ================================================================================

impl GrammarLinter {
    /// Performs comprehensive lexical syntax and syntactic grammar analysis on source code.
    pub fn lint(
        file_path: &str,
        content: &str,
        logger: DiagnosticLogger,
        debugger: OmniDebugger,
        report: &mut LintReport,
    ) {
        // --------------------------------------------------------------------
        // 1. Lexical Tokenization Pass
        // --------------------------------------------------------------------
        let mut lexer = Lexer::new(content, logger.clone());
        let tokens = match lexer.tokenize() {
            Ok(toks) => toks,
            Err(e) => {
                report.errors.push(format!("Syntax Grammar Error (Lexical): {e}"));
                return;
            }
        };

        // --------------------------------------------------------------------
        // 2. Token Stream Grammatical Pattern Checks
        // --------------------------------------------------------------------
        let mut in_roll = false;
        let mut current_roll_line = 0;
        let mut roll_has_aside = false;

        for (idx, tok) in tokens.iter().enumerate() {
            // Check State Prime Grammatical Hygiene
            if let TokenType::Identifier(ref id) = tok.token_type {
                if id.ends_with('`') && id.len() > 1 {
                    // Valid state-prime notation
                }
            }

            // Track Rolls and verify each has an attached Living Aside
            if let TokenType::Identifier(ref id) = tok.token_type {
                if id == "ROLL" || id == "Roll" {
```

```
                    let is_roll_decl = idx + 2 < tokens.len() && matches!(tokens[idx + 2].token_type,
TokenType::InRelationTo);
                    if is_roll_decl {
                        if in_roll && !roll_has_aside && current_roll_line > 0 {
                            report.warnings.push(format!(
                                "Grammar Contract (line {current_roll_line}): Operational roll missing attached Living
Aside '( ... )' oracle."
                            ));
                        }
                        in_roll = true;
                        current_roll_line = tok.line;
                        roll_has_aside = false;
                    }
                }
            }

            if in_roll {
                if let TokenType::Aside(_) = tok.token_type {
                    roll_has_aside = true;
                }
            }

            // Check SVO Verb Grammar: Verbs must be followed by target containers
            // Operational verbs in active positions are ALL-CAPS: INSCRIBE, TRANSDUCE, PROJECT, SEQUENCE
            if let TokenType::Identifier(ref id) = tok.token_type {
                if matches!(id.as_str(), "INSCRIBE" | "TRANSDUCE" | "PROJECT" | "SEQUENCE") {
                    let is_chamber = idx > 0 && matches!(tokens[idx - 1].token_type, TokenType::LBracket);
                    if !is_chamber && idx + 1 < tokens.len() {
                        let next = &tokens[idx + 1];
                        if !next.token_type.is_open_boundary() && !matches!(&next.token_type, TokenType::Identifier(_)) {
                            report.warnings.push(format!(
                                "Grammar Error (line {}): SVO Verb '{}' must be followed by a target container or
operand, found '{:?}'.",
                                tok.line, id, next.token_type
                            ));
                        }
                    }
                }
            }
        }

        // Final roll aside check
        if in_roll && !roll_has_aside && current_roll_line > 0 {
            report.warnings.push(format!(
                "Grammar Contract (line {current_roll_line}): Operational roll missing attached Living Aside '( ... )'
oracle."
            ));
        }

        // ---------------------------------------------------------------------
        // 3. Syntactic Parser AST Pass (for non-empty code)
        // ---------------------------------------------------------------------
        // For .omni files, parse the entire program AST
        if file_path.ends_with(".omni") || content.contains("= [Module]:") || content.contains("Module <") {
            let mut parser = Parser::new(tokens, debugger.clone());
            match parser.parse_program() {
                Ok(_ast) => {
                    // AST successfully parsed and validated
                }
                Err(e) => {
                    report.errors.push(format!("Syntactic Grammar Error: {e}"));
                }
            }
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status )
// ============================================================================
// GrammarLinter sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/syntax/mod.rs

RS | 34 LINES | 144 WORDS | 1.5 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Syntax, Spatial & Grammar Subsystem Coordinator )
// ============================================================================
//! Syntax, Spatial Geometry & Grammar Linter Subsystem
//!
//! Enforces lexical syntax, grammatical AST correctness, and spatial geometry:
//! - [`spatial`]: 80-column IDE dual side-panel ruler and bracket identifier naming hygiene.
//! - [`grammar`]: Lexer token stream hygiene, AST parser verification, SVO verbs, and Living Asides.

pub mod grammar;
pub mod spatial;

pub use grammar::GrammarLinter;
pub use spatial::{SpatialLintConfig, SpatialLinter};

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Coordination Invariants )
// ============================================================================
// Syntax submodules coordinate pre-compilation syntactic and layout hygiene.

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Pipeline )
// ============================================================================
// Coordinated across passes 1 and 3 of the OmniLinter pipeline.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status )
// ============================================================================
// Syntax subsystem sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/syntax/spatial.rs

RS | 109 LINES | 443 WORDS | 4.8 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Spatial Geometry, Ruler Invariants & Syntax Hygiene Linter )
// ================================================================================
//! OmniCode Spatial Geometry & Layout Linter
//!
//! Enforces physical spatial invariants across all OmniCode files:
//! 1. 80-Column Spatial Ruler: Guarantees legibility in IDE viewports with dual side panels.
//! 2. Delimiter & Bracket Hygiene: Disallows snake_case inside brackets (natural spaced phrases).
//! 3. First-Class Intent Asides: Mandates Living Asides `( ... )` for AI cognitive prompts and test oracles.
//! 4. Multiline Compound Sentence Formatting: Flags run-on clauses that break columnar rhythm.

use crate::diagnostics::linter::LintReport;

/// Configuration for spatial geometry and layout linting.
#[derive(Debug, Clone)]
pub struct SpatialLintConfig {
    /// Maximum allowed column width (default: 80).
    pub max_columns: usize,
    /// Whether column limit violations constitute fatal errors or advisory warnings.
    pub strict_column_limit: bool,
}

impl Default for SpatialLintConfig {
    fn default() -> Self {
        Self {
            max_columns: 80,
            strict_column_limit: false,
        }
    }
}

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( SpatialLinter Definition & Constructor )
// ================================================================================

pub struct SpatialLinter;

impl SpatialLinter {
    /// Lints source text against physical spatial geometry and syntax hygiene rules.
    pub fn lint(content: &str, report: &mut LintReport, config: &SpatialLintConfig) {
        let lines: Vec<&str> = content.lines().collect();

        // ------------------------------------------------------------------------
        // 1. 80-Column Spatial Ruler Verification
        // ------------------------------------------------------------------------
        for (idx, line) in lines.iter().enumerate() {
            let line_num = idx + 1;
            let col_count = line.chars().count();
            if col_count > config.max_columns {
                let msg = format!(
                    "Spatial Geometry (line {line_num}): Line exceeds {max} columns ({col_count} cols). \
                     OmniCode mandates <= {max} columns for dual side panel IDE viewports.",
                    max = config.max_columns
                );
                if config.strict_column_limit {
                    report.errors.push(msg);
                } else {
                    report.warnings.push(msg);
                }
            }
        }

        // ------------------------------------------------------------------------
        // 2. First-Class Intent Asides Presence (Canon 1)
        // ------------------------------------------------------------------------
        let total_lines = lines.len();
        let has_any_asides = content.contains('(') && content.contains(')');
        if total_lines > 15 && !has_any_asides {
            report.warnings.push(
                "Canon 1: Missing first-class intent Asides '(...)'. OmniCode mandates Asides \
                 for human-AI pronunciation, system prompt seeds, and pre-test oracles.".into(),
```

```
            );
        }

        // ---------------------------------------------------------------------
        // 3. Snake_case Hygiene Inside Brackets
        // ---------------------------------------------------------------------
        for (idx, line) in lines.iter().enumerate() {
            let line_num = idx + 1;
            let trimmed = line.trim();
            if trimmed.starts_with('#') {
                continue;
            }
            if let Some(start_bracket) = line.find('[') {
                if let Some(end_bracket) = line[start_bracket..].find(']') {
                    let bracket_content = &line[start_bracket + 1..start_bracket + end_bracket];
                    for word in bracket_content.split_whitespace() {
                        if word.contains('_') && !word.starts_with("0x") && !word.starts_with("roll_") {
                            report.warnings.push(format!(
                                "Syntax Hygiene (line {line_num}): Identifier '{word}' uses snake_case with underscores
inside brackets. \
                                 In OmniCode, use natural spaced phrases (e.g. '[ ... ]') without underscores."
                            ));
                            break;
                        }
                    }
                }
            }
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Status )
// ============================================================================
// SpatialLinter sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/metadata/head.rs

RS | 247 LINES | 953 WORDS | 10.3 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Process Tape (.tape) Block 1 Tape Head & Cardinal Coordinates Linter )
// ============================================================================
//! Process Tape (.tape) Block 1 Tape Head Linter
//!
//! Evaluates and scores the Tape Head manifest for `.tape` Process Ribbons.
//! While `.omni` files represent declarative Source Reels, `.tape` files represent
//! sequential execution ribbons. Both embody the exact same ontological covenant
//! and foundation, but with process ribbon mechanics:
//! 1. Formal Tape Head Declaration (`= [Tape]: < ... > & [ ... ] {`).
//! 2. Defined Operational Space & Partitions (`WHERE { ... Cell } = [ 1 ]`).
//! 3. Covenant Witness Grounding (`< Scripture { ... } >` anchor).
//! 4. The Six Cardinal Coordinates (`WHO`, `WHAT`, `WHEN`, `WHERE`, `WHY`, `HOW`)
//!    with operational verbs (`--> INSCRIBE`) and causal directionals.
//! 5. Spatial Geometry (<= 80 columns) and bracket naming hygiene.

use crate::diagnostics::linter::syntax::SpatialLintConfig;
use super::score::MetadataScore;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( TapeHeadLinter Definition & Slice Extractor )
// ============================================================================

pub struct TapeHeadLinter;

impl TapeHeadLinter {
    /// Extracts the text slice corresponding exclusively to the Tape Head.
    pub fn extract_slice(content: &str) -> (usize, usize, String) {
        let lines: Vec<&str> = content.lines().collect();
        if lines.is_empty() {
            return (0, 0, String::new());
        }

        let mut start_idx = None;
        let mut end_idx = None;

        for (idx, line) in lines.iter().enumerate() {
            let trimmed = line.trim();
            if start_idx.is_none() {
                if trimmed.starts_with("= [Tape")
                    || trimmed.starts_with("[Tape.")
                    || trimmed.starts_with("Tape [")
                    || trimmed.starts_with("Tape <")
                {
                    start_idx = Some(idx);
                }
            } else {
                let upper = trimmed.to_uppercase();
                if upper.starts_with("[ ROLL")
                    || upper.starts_with("ROLL_")
                    || trimmed.starts_with("# DECLARED ROLLS")
                {
                    end_idx = Some(idx);
                    break;
                }
            }
        }

        let start = start_idx.unwrap_or(0);
        let end = end_idx.unwrap_or(lines.len());
        (start + 1, end, lines[start..end].join("\n"))
    }
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Evaluation Engine for Process Tape Head Invariants )
// ============================================================================

impl TapeHeadLinter {
    /// Evaluates and scores Block 1 for a `.tape` Process Ribbon.
```

```rust
    pub fn evaluate(
        _file_path: &str,
        slice: &str,
        config: &SpatialLintConfig,
    ) -> MetadataScore {
        let mut identity = 0u32;
        let mut provenance = 0u32;
        let mut witness = 0u32;
        let mut ontology = 0u32;
        let mut spatial = 0u32;
        let mut breakdown = Vec::new();

        // ------------------------------------------------------------------
        // 1. Identity & Formal Tape Declaration (max 20 pts)
        // ------------------------------------------------------------------
        let has_tape_decl = slice.contains("= [Tape]:")
            || slice.contains("[Tape.")
            || slice.contains("Tape [")
            || slice.contains("Tape <");
        if has_tape_decl {
            identity += 15;
            breakdown.push("✓ Formal Process Tape Head declared (+15/15)".into());
        } else {
            breakdown.push("✗ Missing formal tape head declaration (0/15)".into());
        }

        let has_tape_context = (slice.contains('<') && slice.contains('>'))
            && (slice.contains('[') && slice.contains(']'));
        if has_tape_context {
            identity += 5;
            breakdown.push("✓ Dual-domain tape contextualization affirmed (+5/5)".into());
        } else {
            breakdown.push("✗ Missing dual domain context in tape declaration (0/5)".into());
        }

        // ------------------------------------------------------------------
        // 2. Operational Environment & Topology (max 25 pts)
        // ------------------------------------------------------------------
        let has_defined_space = slice.contains("WHERE")
            && (slice.contains("Cell") || slice.contains("Partition") || slice.contains('['));
        if has_defined_space {
            provenance += 10;
            breakdown.push("✓ Defined space / cell partition bounds declared (+10/10)".into());
        } else {
            breakdown.push("✗ Missing defined space or cell bounds in tape head (0/10)".into());
        }

        let has_domain_context = slice.contains("Lexicon") || slice.contains("Kernel") || slice.contains("Domain");
        if has_domain_context {
            provenance += 10;
            breakdown.push("✓ Execution domain context declared (+10/10)".into());
        } else {
            breakdown.push("✗ Missing execution domain context (0/10)".into());
        }

        let has_comments = slice.contains("TOPOLOGY")
            || slice.contains("PROCESS TAPE")
            || slice.lines().any(|l| l.trim().starts_with('#'));
        if has_comments {
            provenance += 5;
            breakdown.push("✓ Architectural topology commentary inscribed (+5/5)".into());
        } else {
            breakdown.push("✗ Missing architectural topology header commentary (0/5)".into());
        }

        // ------------------------------------------------------------------
        // 3. Covenant & Witness Invariant Grounding (max 20 pts)
        // ------------------------------------------------------------------
        let has_scripture = slice.contains("< Scripture") || slice.contains("Exodus");
        if has_scripture {
            witness += 15;
            breakdown.push("✓ Invariant Scripture / Covenant witness anchored (+15/15)".into());
        } else {
            breakdown.push("✗ Missing scripture/covenant witness in tape head (0/15)".into());
        }

        let has_witness_aside = slice.contains("Invariant Witness")
            || (has_scripture && slice.contains('(') && slice.contains(')'));
```

```
        if has_witness_aside {
            witness += 5;
            breakdown.push("✓ Machine-readable Witness Aside oracle attached (+5/5)".into());
        } else {
            breakdown.push("✗ Missing witness Aside oracle (0/5)".into());
        }

        // ------------------------------------------------------------------
        // 4. Six Cardinal Coordinates & Operational Verbs (max 20 pts)
        // ------------------------------------------------------------------
        let upper = slice.to_uppercase();
        let cardinal_clauses = ["WHO", "WHAT", "WHEN", "WHERE", "WHY", "HOW"];
        let present_clauses = cardinal_clauses.iter().filter(|&&c| upper.contains(c)).count();

        if present_clauses == 6 {
            ontology += 15;
            breakdown.push(
                "✓ All Six Cardinal Coordinates (WHO, WHAT, WHEN, WHERE, WHY, HOW) present (+15/15)".into(),
            );
        } else {
            let pts = (present_clauses as u32) * 2;
            ontology += pts;
            breakdown.push(format!(
                "⚠ Cardinal coordinates incomplete ({present_clauses}/6) (+{pts}/15)"
            ));
        }

        let has_op_verbs = upper.contains("INSCRIBE") || upper.contains("PROCEED") || upper.contains("-->");
        if has_op_verbs {
            ontology += 5;
            breakdown.push("✓ Operational SVO verb and directional vectors wired (+5/5)".into());
        } else {
            breakdown.push("✗ Missing operational verbs or directional vectors in cardinal clauses (0/5)".into());
        }

        // ------------------------------------------------------------------
        // 5. Spatial Geometry & Syntax Hygiene (max 15 pts)
        // ------------------------------------------------------------------
        let lines: Vec<&str> = slice.lines().collect();
        let max_cols = config.max_columns;
        let line_len_violation = lines.iter().any(|l| l.chars().count() > max_cols);

        if !line_len_violation {
            spatial += 10;
            breakdown.push(format!("✓ All Tape Head lines <= {max_cols} columns (+10/10)"));
        } else {
            breakdown.push(format!("✗ Tape Head lines exceed {max_cols}-column spatial ruler (0/10)"));
        }

        let snake_violation = lines.iter().any(|line| {
            let trimmed = line.trim();
            if trimmed.starts_with('#') {
                return false;
            }
            if let Some(start) = line.find('[') {
                if let Some(end) = line[start..].find(']') {
                    let inside = &line[start + 1..start + end];
                    for w in inside.split_whitespace() {
                        if w.contains('_') && !w.starts_with("0x") && !w.starts_with("roll_") {
                            return true;
                        }
                    }
                }
            }
            false
        });

        if !snake_violation {
            spatial += 5;
            breakdown.push("✓ Natural spaced identifier hygiene observed (+5/5)".into());
        } else {
            breakdown.push("✗ snake_case identifiers found inside brackets (0/5)".into());
        }

        MetadataScore::new(identity, provenance, witness, ontology, spatial, breakdown)
    }
}
```

```
// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests for Tape Head Block 1 Linting )
// ================================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_tape_head_extraction_and_empty_check() {
        let (start, end, slice) = TapeHeadLinter::extract_slice("");
        assert_eq!(start, 0);
        assert_eq!(end, 0);
        assert!(slice.is_empty());
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/metadata/mod.rs

RS | 112 LINES | 388 WORDS | 4.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Block 1 Metadata & Tape Head Invariant Subsystem Coordinator )
// ============================================================================
//! OmniCode Block 1 Metadata & Tape Head Subsystem
//!
//! Organizes Block 1 verification into dedicated, domain-specific modules:
//! - [`score`]: `MetadataScore` invariant model, point totals, and rating tiers.
//! - [`reel`]: Source Reel (`.omni`) Module Manifest & Invariant Type inspection.
//! - [`head`]: Process Tape (`.tape`) Tape Head & Cardinal Coordinates inspection.
//!
//! While `.omni` and `.tape` have different syntaxes and structures, both
//! embody the same proper ontological understanding: foundational identity,
//! provenance, covenant witness grounding, invariants/clauses, and spatial hygiene.

pub mod head;
pub mod reel;
pub mod score;

pub use head::TapeHeadLinter;
pub use reel::ReelMetadataLinter;
pub use score::MetadataScore;

use crate::diagnostics::linter::syntax::SpatialLintConfig;
use crate::diagnostics::linter::LintReport;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( MetadataLinter Coordinator Definition )
// ============================================================================

pub struct MetadataLinter;

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Polymorphic Dispatch Across Source Reels and Process Tapes )
// ============================================================================

impl MetadataLinter {
    /// Evaluates and scores Block 1 for either a Source Reel or Process Tape,
    /// selecting the dedicated linter while preserving unified understanding.
    pub fn evaluate(
        file_path: &str,
        content: &str,
        is_tape: bool,
        config: &SpatialLintConfig,
        _report: &mut LintReport,
    ) -> MetadataScore {
        let blocks = crate::diagnostics::linter::structure::detector::BlockDetector::detect_blocks(content, is_tape);
        if is_tape {
            TapeHeadLinter::evaluate(file_path, &blocks.metadata.content, config)
        } else {
            ReelMetadataLinter::evaluate(file_path, &blocks.metadata.content, config)
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Unit Tests & Calibration Verification )
// ============================================================================

#[cfg(test)]
mod tests {

    #[test]
    fn test_character_omni_block1_scores_100() {
        let logger = crate::diagnostics::logger::DiagnosticLogger::new(false);
        let linter = crate::diagnostics::linter::OmniLinter::new(logger);
        let path = crate::core::filetype::resolve_track_path("lexicon/01_nouns/ideas/types/character.omni");
        if path.exists() {
            let report = linter.lint_file(&path).expect("Lint character.omni");
            assert!(report.is_valid, "character.omni must be valid");
```

```
            let score = report.metadata_score.expect("Metadata score must be present");
            assert_eq!(
                score.total, 100,
                "character.omni Block 1 must score 100/100, got: {} ({:?})",
                score.total, score.breakdown
            );
            assert_eq!(score.rating, "A+ (Exemplary Invariant)");
            assert_eq!(score.identity_score, 20);
            assert_eq!(score.provenance_score, 25);
            assert_eq!(score.witness_score, 20);
            assert_eq!(score.ontology_score, 20);
            assert_eq!(score.spatial_hygiene_score, 15);
        }
    }

    #[test]
    fn test_character_tape_block1_scores_100() {
        let logger = crate::diagnostics::logger::DiagnosticLogger::new(false);
        let linter = crate::diagnostics::linter::OmniLinter::new(logger);
        let path = crate::core::filetype::resolve_track_path("lexicon/01_nouns/ideas/types/character.tape");
        if path.exists() {
            let report = linter.lint_file(&path).expect("Lint character.tape");
            assert!(report.is_valid, "character.tape must be valid");
            let score = report.metadata_score.expect("Metadata score must be present");
            assert_eq!(
                score.total, 100,
                "character.tape Block 1 must score 100/100, got: {} ({:?})",
                score.total, score.breakdown
            );
            assert_eq!(score.rating, "A+ (Exemplary Invariant)");
            assert_eq!(score.identity_score, 20);
            assert_eq!(score.provenance_score, 25);
            assert_eq!(score.witness_score, 20);
            assert_eq!(score.ontology_score, 20);
            assert_eq!(score.spatial_hygiene_score, 15);
        }
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/metadata/reel.rs

RS | 250 LINES | 995 WORDS | 10.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Source Reel (.omni) Block 1 Metadata & Invariant Type Linter )
// ============================================================================
//! Source Reel (.omni) Block 1 Metadata Linter
//!
//! Evaluates and scores the ontological foundation of `.omni` files:
//! 1. Formal Module Identity (`= [Module]: < ... > & [ ... ]` with intent Aside).
//! 2. Invariant Provenance (`Version`, `Author`, `Created`, `Updated`, `System`).
//! 3. Covenant Witness Grounding (`< Scripture { ... } >` or `[ Witness ]:`).
//! 4. Ontological Invariants & Freestanding Type Definitions (`< Type > = ...`
//!    across the 9 dimensions: Relation, Domain, Substrate, Inscribe, Transduce,
//!    Exemplar, Compare, Sequence, Bound).
//! 5. Spatial Geometry (<= 80 columns) and bracket identifier naming hygiene.

use crate::diagnostics::linter::syntax::SpatialLintConfig;
use super::score::MetadataScore;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( ReelMetadataLinter Definition & Slice Extractor )
// ============================================================================

pub struct ReelMetadataLinter;

impl ReelMetadataLinter {
    /// Extracts the text slice corresponding to Block 1 in a `.omni` file.
    pub fn extract_slice(content: &str) -> (usize, usize, String) {
        let lines: Vec<&str> = content.lines().collect();
        if lines.is_empty() {
            return (0, 0, String::new());
        }

        let mut start_idx = None;
        let mut end_idx = None;

        for (idx, line) in lines.iter().enumerate() {
            let upper = line.to_uppercase();
            if start_idx.is_none() {
                if upper.contains("BLOCK 1") || upper.contains("METADATA BLOCK") {
                    start_idx = Some(idx);
                }
            } else if upper.contains("BLOCK 2") || upper.contains("OPENING BLOCK") {
                end_idx = Some(idx);
                break;
            }
        }

        let start = start_idx.unwrap_or(0);
        let end = end_idx.unwrap_or(lines.len());
        (start + 1, end, lines[start..end].join("\n"))
    }
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Evaluation Engine for Source Reel Metadata Invariants )
// ============================================================================

impl ReelMetadataLinter {
    /// Evaluates and scores Block 1 for a `.omni` Source Reel.
    pub fn evaluate(
        _file_path: &str,
        slice: &str,
        config: &SpatialLintConfig,
    ) -> MetadataScore {
        let mut identity = 0u32;
        let mut provenance = 0u32;
        let mut witness = 0u32;
        let mut ontology = 0u32;
        let mut spatial = 0u32;
        let mut breakdown = Vec::new();

```

```
        // ------------------------------------------------------------------
        // 1. Identity & Formal Declaration (max 20 pts)
        // ------------------------------------------------------------------
        let has_module_decl = slice.contains("= [Module]:")
            || slice.contains("Module <")
            || slice.contains("Module [")
            || slice.contains("Scroll <");
        if has_module_decl {
            identity += 15;
            breakdown.push("✓ Formal Module Identity declared (+15/15)".into());
        } else {
            breakdown.push("✗ Missing formal module identity declaration (0/15)".into());
        }

        let has_identity_aside = slice.lines().any(|l| {
            (l.contains("= [Module]:") || l.contains("Module <")) && l.contains('(')
                || (slice.contains("= [Module]:") && slice.contains("( This is the Module"))
        }) || (has_module_decl && slice.contains('(') && slice.contains(')'));

        if has_identity_aside {
            identity += 5;
            breakdown.push("✓ Module intent Aside '( ... )' attached (+5/5)".into());
        } else {
            breakdown.push("✗ Missing intent Aside on module identity (0/5)".into());
        }

        // ------------------------------------------------------------------
        // 2. Provenance Attributes & Environment (max 25 pts)
        // ------------------------------------------------------------------
        let has_version = slice.contains("[ Version ]") || slice.contains("version:");
        if has_version {
            provenance += 8;
            breakdown.push("✓ Invariant Version attribute specified (+8/8)".into());
        } else {
            breakdown.push("✗ Missing version attribute in metadata context (0/8)".into());
        }

        let has_author = slice.contains("[ Author ]") || slice.contains("author:");
        if has_author {
            provenance += 6;
            breakdown.push("✓ Author / Organization provenance recorded (+6/6)".into());
        } else {
            breakdown.push("✗ Missing author provenance specification (0/6)".into());
        }

        let has_timestamps = slice.contains("[ Created ]") || slice.contains("[ Updated ]");
        if has_timestamps {
            provenance += 6;
            breakdown.push("✓ Created / Updated temporal anchors inscribed (+6/6)".into());
        } else {
            breakdown.push("✗ Missing temporal created/updated timestamps (0/6)".into());
        }

        let has_system = slice.contains("[ System ]") || slice.contains("system:");
        if has_system {
            provenance += 5;
            breakdown.push("✓ Target system / runtime context declared (+5/5)".into());
        } else {
            breakdown.push("✗ Missing target system context declaration (0/5)".into());
        }

        // ------------------------------------------------------------------
        // 3. Covenant & Witness Grounding (max 20 pts)
        // ------------------------------------------------------------------
        let has_scripture = slice.contains("< Scripture") || slice.contains("[ Witness ]");
        if has_scripture {
            witness += 15;
            breakdown.push("✓ Invariant Covenant / Scripture witness anchored (+15/15)".into());
        } else {
            breakdown.push("✗ Missing scripture/covenant witness anchor (0/15)".into());
        }

        let has_witness_aside = slice.contains("Invariant Witness")
            || (has_scripture && slice.contains('(') && slice.contains("Witness"));
        if has_witness_aside {
            witness += 5;
            breakdown.push("✓ Machine-readable Witness Aside oracle attached (+5/5)".into());
        } else if has_scripture {
```

```
            witness += 3;
            breakdown.push("⚠ Living Aside on witness partially detected (+3/5)".into());
        } else {
            breakdown.push("✗ Missing witness Aside oracle (0/5)".into());
        }

        // ---------------------------------------------------------------------
        // 4. Ontological Dimensions & Invariant Types (max 20 pts)
        // ---------------------------------------------------------------------
        let has_freestanding_type = slice.contains("< Character > =")
            || (slice.contains("< ") && slice.contains(" > =") && slice.contains('&'));
        let has_nature_semantics = slice.contains("[ Nature ]") || slice.contains("[ Semantics ]");

        if has_freestanding_type {
            let dimensions = [
                "Relation", "Domain", "Substrate", "Inscribe",
                "Transduce", "Exemplar", "Compare", "Sequence", "Bound",
            ];
            let matched_dims = dimensions.iter().filter(|&&d| slice.contains(d)).count();
            if matched_dims >= 7 {
                ontology += 20;
                breakdown.push(format!(
                    "✓ Freestanding Invariant Type defined across {matched_dims}/9 dimensions (+20/20)"
                ));
            } else {
                let pts = (matched_dims as u32) * 2;
                ontology += pts;
                breakdown.push(format!(
                    "⚠ Freestanding Type defined with partial dimensions ({matched_dims}/9) (+{pts}/20)"
                ));
            }
        } else if has_nature_semantics {
            ontology += 20;
            breakdown.push("✓ Nature and Semantics ontology bounds defined (+20/20)".into());
        } else {
            breakdown.push("✗ Missing freestanding invariant type or nature/semantics bounds (0/20)".into());
        }

        // ---------------------------------------------------------------------
        // 5. Spatial Geometry & Syntax Hygiene within Block 1 (max 15 pts)
        // ---------------------------------------------------------------------
        let lines: Vec<&str> = slice.lines().collect();
        let max_cols = config.max_columns;
        let line_len_violation = lines.iter().any(|l| l.chars().count() > max_cols);

        if !line_len_violation {
            spatial += 10;
            breakdown.push(format!("✓ All Block 1 lines <= {max_cols} columns (+10/10)"));
        } else {
            breakdown.push(format!("✗ Block 1 lines exceed {max_cols}-column spatial ruler (0/10)"));
        }

        let snake_violation = lines.iter().any(|line| {
            let trimmed = line.trim();
            if trimmed.starts_with('#') {
                return false;
            }
            if let Some(start) = line.find('[') {
                if let Some(end) = line[start..].find(']') {
                    let inside = &line[start + 1..start + end];
                    for w in inside.split_whitespace() {
                        if w.contains('_') && !w.starts_with("0x") && !w.starts_with("roll_") {
                            return true;
                        }
                    }
                }
            }
            false
        });

        if !snake_violation {
            spatial += 5;
            breakdown.push("✓ Natural spaced identifier hygiene observed (+5/5)".into());
        } else {
            breakdown.push("✗ snake_case identifiers found inside brackets (0/5)".into());
        }

        MetadataScore::new(identity, provenance, witness, ontology, spatial, breakdown)
```

```
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests for Source Reel Block 1 Linting )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_reel_metadata_extraction_and_empty_check() {
        let (start, end, slice) = ReelMetadataLinter::extract_slice("");
        assert_eq!(start, 0);
        assert_eq!(end, 0);
        assert!(slice.is_empty());
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/metadata/score.rs RS | 104 LINES | 452 WORDS | 4.2 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Block 1 Metadata & Tape Head Score Model & Rating Taxonomy )
// ============================================================================
//! OmniCode Metadata & Tape Head Scoring Taxonomy
//!
//! Provides the unified scoring model for Block 1 across both `.omni` Source Reels
//! and `.tape` Process Ribbons. While the concrete syntax of reels and tapes differs,
//! both express the exact same ontological foundation and covenant understanding:
//! 1. Identity & Formal Declaration (max 20 pts)
//! 2. Provenance & Operational Environment (max 25 pts)
//! 3. Covenant & Scripture Invariant Grounding (max 20 pts)
//! 4. Ontological Invariants / Cardinal Coordinates (max 20 pts)
//! 5. Spatial Geometry & Naming Hygiene (max 15 pts)

/// Comprehensive rubric breakdown and total score for Block 1 (0..=100).
#[derive(Debug, Clone, PartialEq, Eq)]
pub struct MetadataScore {
    /// Score for formal identity and module/tape declaration (max 20).
    pub identity_score: u32,
    /// Score for provenance, author, version, and environment (max 25).
    pub provenance_score: u32,
    /// Score for scripture/covenant invariant witness grounding (max 20).
    pub witness_score: u32,
    /// Score for ontological dimensions or 6 cardinal clauses (max 20).
    pub ontology_score: u32,
    /// Score for spatial geometry and delimiter naming hygiene (max 15).
    pub spatial_hygiene_score: u32,
    /// Total aggregate score (0..=100).
    pub total: u32,
    /// Letter grade and descriptive rating.
    pub rating: &'static str,
    /// Granular audit notes explaining points awarded or deducted.
    pub breakdown: Vec<String>,
}

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Rating Computation & Rubric Evaluation )
// ============================================================================

impl MetadataScore {
    /// Computes the letter grade and descriptive status from the total score.
    pub fn compute_rating(total: u32) -> &'static str {
        match total {
            100 => "A+ (Exemplary Invariant)",
            90..=99 => "A (Compliant)",
            80..=89 => "B (Adequate Foundation)",
            70..=79 => "C (Needs Provenance / Witness Grounding)",
            50..=69 => "D (Deficient Metadata)",
            _ => "F (Unanchored / Incomplete)",
        }
    }
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Summary & Aggregation Methods )
// ============================================================================

impl MetadataScore {
    /// Creates a new MetadataScore from component scores and breakdown notes.
    pub fn new(
        identity: u32,
        provenance: u32,
        witness: u32,
        ontology: u32,
        spatial: u32,
        breakdown: Vec<String>,
    ) -> Self {
        let total = identity + provenance + witness + ontology + spatial;
        Self {
            identity_score: identity,
```

```
            provenance_score: provenance,
            witness_score: witness,
            ontology_score: ontology,
            spatial_hygiene_score: spatial,
            total,
            rating: Self::compute_rating(total),
            breakdown,
        }
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests for MetadataScore Rating Taxonomy )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_metadata_score_rating_tiers() {
        assert_eq!(MetadataScore::compute_rating(100), "A+ (Exemplary Invariant)");
        assert_eq!(MetadataScore::compute_rating(95), "A (Compliant)");
        assert_eq!(MetadataScore::compute_rating(85), "B (Adequate Foundation)");
        assert_eq!(MetadataScore::compute_rating(75), "C (Needs Provenance / Witness Grounding)");
        assert_eq!(MetadataScore::compute_rating(60), "D (Deficient Metadata)");
        assert_eq!(MetadataScore::compute_rating(30), "F (Unanchored / Incomplete)");
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/linter/scaffold/mod.rs

RS | 206 LINES | 1128 WORDS | 7.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Canonical Code Scaffolding Templates for .omni, .tape, and .scroll )
// ============================================================================
//! Canonical Code Scaffolding Engine
//!
//! Generates compliant, 80-column bounded skeleton templates for all OmniCode file formats:
//! - `.omni`: 4-Block Source Reel
//! - `.tape`: Sequential Process Ribbon
//! - `.scroll`: Cognitive Episodic Scroll

use crate::core::filetype::OmniFileType;

pub struct LinterScaffolder;

impl LinterScaffolder {
    /// Auto-scaffolds a compliant 4-Block skeleton for an episodic cognitive scroll (.scroll).
    pub fn auto_scaffold_scroll(session_id: &str, prompt: &str) -> String {
        OmniFileType::EpisodicScroll.scaffold_template(session_id, prompt)
    }

    /// Auto-scaffolds a compliant 4-Block skeleton for a given module name (.omni),
    /// strictly bounded to the 80-column ruler with 3-tier boundary comments.
    pub fn auto_scaffold_omni(module_name: &str, intent_aside: &str) -> String {
        format!(
r#"# ============================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Type: < Idea {{ Type }} : {module_name} > )
# ============================================================================
= [Module]: < Lexicon {{ {module_name} }} > & [ Noun {{ {module_name} }} ]
    ( {intent_aside} )
{{
    [ Version ]:   {{ "1.0.0" }}
        ( Version 1.0.0 ),

    [ Author ]:    {{ "CreativeWorkzStudio LLC / ProfessorSeanEX" }}
        ( System Architect ),

    [ System ]:    {{ OmniCode {{ Core }} }}
        ( Core Subsystem ),

    [ Witness ]:   < Scripture {{ Exodus 31:18 KJV }} >
        {{ "Written with the finger of God." }}
        ( Invariant Scripture Anchor ),

    [ Nature ]:    < InvariantType > & {{ BaseBlock }}
        ( Nature is Invariant Type ),

    [ Semantics ]: {{ StandardLibrary :: Specification }}
        ( Semantics specification )
}}

< {module_name} > = < Idea {{ Type }} > & [ Noun {{ {module_name} }} ]
    ( Invariant Definition )
{{
    [ Relation ]: [ {module_name} ] : [ Unit ] :: [ Trit ] : [ Word ]
        ( Ontological Relation ),

    [ Substrate ]: [ 1 Byte {{ 8 Bits }} ] & [ 1 Cell {{ 5 Trits }} ]
        ( Dual Substrate ),

    [ Bound ]: {{ {module_name} }} = [ Enclosed ]: TRUE
        ( Invariant Single Cell Boundary )
}}

# ============================================================================
# BLOCK 2: OPENING BLOCK
# ============================================================================
Opening {{
    [ Entity ]: < {module_name} > & [ Cell ]
        ( Entity allocated in cell ),

    [ Cell ]: [ 1 ] & {{ 5 Trits :: 1 Byte }}
```

```
        ( One cell container ),

    [ Preconditions ]: [ (+1) plus (-1) <=> 0 ] & [ Status = +1:PROCEED ]
        ( Equilibrium verified )
}}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    [ ROLL 1 ] : [ Inscribe ] :
        [ Input ] --> INSCRIBE [ Cell ] = [ Entity` ]
        ( Inscribe input into Cell yielding Entity-prime ),

    [ ROLL 2 ] : [ Compare ] :
        {{ Entity` = Input }} --> [ Status` = +1:PROCEED ]
        | {{ Entity` != Input }} --> [ Status` = -1:ROLLBACK ]
        ( Evaluate identity and verify bounds )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing
    ( Sealing Gate: Validate, tripwire, debug, log, and affirm execution )
{{
    [ Verify ]: [
        [ ROLL 1 ] = PROCEED ::
        [ ROLL 2 ] = PROCEED
    ]
    ( Verify that all rolls achieved affirmative PROCEED ),

    [ Validate ]:
        {{ Entity` <= [ 1 Cell ] }} & {{ [ 8 Bits ] <=> [ 5 Trits ] }}
        ( Validate single cell bounds and substrate parity ),

    [ Tripwire ]:
        {{ Status` = +1:PROCEED }} --> [ ARMED ]
        | {{ Status` != +1:PROCEED }} --> [ TRIPPED ]
            --> [ Commit Status = -1:ROLLBACK ]
        ( Circuit breaker vetoes on anomaly ),

    [ Debug ]:
        {{ [ Entity` ] :: [ Cell` ] :: [ Status` ] }}
        ( Expose diagnostic telemetry snapshot ),

    [ Log ]: [ Journal ]:
        INSCRIBE {{ [ {module_name} Verified ] :: [ Entity` ] }}
        ( Inscribe event record into system journal ),

    [ Commit Status ]: [
        {{ [ Verify ] = PROCEED }} & {{ [ Tripwire ] = ARMED }}
            --> [ +1:PROCEED ] |
        {{ [ Status` ] = PENDING }}
            --> [ 0:AWAIT ] :: REPEAT |
        {{ [ Status` ] = NULL }}
            --> [ HALT:NULL ] |
        {{ [ Tripwire ] = TRIPPED }} | {{ [ Verify ] != PROCEED }}
            --> [ -1:ROLLBACK ]
    ]
    ( Fourfold state machine: Proceed, Await, Halt, Rollback )
}}
"#
        )
    }

    /// Auto-scaffolds a compliant `.tape` sequential process ribbon skeleton,
    /// strictly bounded to 80 columns with Tape Head and Cardinal Clauses.
    pub fn auto_scaffold_tape(tape_name: &str, intent_aside: &str) -> String {
        format!(
r#"# ================================================================================
# PROCESS TAPE: {upper} INVARIANT TYPE EXECUTION RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Type < {tape_name} >.
#   - Defined Space: [ 1 Cell ] {{ 5 Trits :: 1 Byte }}
#   - Execution Domain: Lexicon {{ Types of Ideas }}
#   - Witness: Scripture Exodus 31:18 KJV
```

```
# ================================================================================

= [Tape]: < Lexicon {{ Types of Ideas }} > & [ Process {{ {tape_name} }} ] {{
    WHO   {{ OmniCode Lexicon }} ::
    WHAT  {{ {tape_name} }} --> DISPATCH {{ Process }} ::
    WHEN  {{ Input Event }} ::
    WHERE {{ {tape_name} Cell }} = [ 1 ] ::
    WHY   ( {intent_aside} ) ::
    HOW   [ +1 : PROCEED ] ::
    < Scripture {{ Exodus 31:18 KJV }} > ::
    :: {{ "Written with the finger of God." }} ::
    :: ( Invariant Witness Exodus 31:18: Written with finger of God )
}}

# ================================================================================
# DECLARED ROLLS: ATOMIC INVARIANT EXECUTION
# ================================================================================

# --------------------------------------------------------------------------------
# ROLL 1: INITIAL STATE ALLOCATION
# --------------------------------------------------------------------------------
[ ROLL 1 ] : [ Inscribe ] :
    [ Input ] --> INSCRIBE [ Cell ] = [ {tape_name}` ]
    ( Inscribe initial input into cell container )

# --------------------------------------------------------------------------------
# ROLL 2: INVARIANT VERIFICATION
# --------------------------------------------------------------------------------
[ ROLL 2 ] : [ Compare ] :
    {{ {tape_name}` = Input }} ! GUARD --> [ Status` = +1:PROCEED ]
    | {{ {tape_name}` != Input }} --> [ Status` = -1:ROLLBACK ]
    ( Verify invariant bounds under guard )

# --------------------------------------------------------------------------------
# ROLL 3: COMMIT STATUS & FOURFOLD STATE MACHINE
# --------------------------------------------------------------------------------
[ ROLL 3 ] : [ Commit Status ] : [
    {{ [ Verify ] = PROCEED }} & {{ [ Tripwire ] = ARMED }}
        --> [ +1:PROCEED ] |
    {{ [ Status` ] = PENDING }}
        --> [ 0:AWAIT ] :: REPEAT |
    {{ [ Status` ] = NULL }}
        --> [ HALT:NULL ] |
    {{ [ Tripwire ] = TRIPPED }} | {{ [ Verify ] != PROCEED }}
        --> [ -1:ROLLBACK ]
]
( Fourfold commit status: Proceed, Await, Halt, Rollback )
"#,
            upper = tape_name.to_uppercase(),
            tape_name = tape_name,
            intent_aside = intent_aside
        )
    }
}
```

OmniCode: Chapter 9: Track 1 - Terminal, REPL & Hover Inspection

Interactive REPL, Task Scheduler & 3-Tier Hover Cards

CHAPTER IDENTIFIER	**NOTEBOOKLM WORD COUNT**
CH 09	29,808 words
CATALOGED CHAPTER FILES	**GENERATION DATE**
24 files (7,831 lines)	2026-10-16 20:35:59

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"How does hover engine bridge tape rolls to omni sources?"*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (24 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/README.md**	MD	117	848	6.7
2	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/mod.rs**	RS	90	387	3.5
3	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/scheduler/mod.rs**	RS	46	191	1.9
4	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/scheduler/scheduler.rs**	RS	492	1,935	20.5
5	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/scheduler/tasks.rs**	RS	234	853	8.4
6	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/session/commands.rs**	RS	801	2,660	32.4
7	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/session/mod.rs**	RS	37	185	1.8
8	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/session/session.rs**	RS	481	1,647	19.5
9	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/studio/hud.rs**	RS	173	740	8.4
10	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/studio/kinematics.rs**	RS	104	456	4.9
11	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/studio/mod.rs**	RS	36	186	1.7
12	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/universal/mod.rs**	RS	54	197	2.0
13	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/universal/ports.rs**	RS	215	844	7.3
14	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/universal/call_response_engine/call_response.rs**	RS	443	1,816	17.6
15	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/universal/call_response_engine/echo.rs**	RS	155	656	6.1
16	**<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/universal/call_response_engine/mod.rs**	RS	27	74	0.8
17	**<TRACK 1> : {Host Engine & Virtual Machine}/src/cli/mod.rs**	RS	44	157	2.0
18	**<TRACK 1> : {Host Engine & Virtual Machine}/src/cli/repl.rs**	RS	427	1,585	21.6
19	**<TRACK 1> : {Host Engine & Virtual Machine}/src/cli/server.rs**	RS	576	1,855	23.0
20	**<TRACK 1> : {Host Engine & Virtual Machine}/src/cli/commands/assemble.rs**	RS	544	2,088	23.7
21	**<TRACK 1> : {Host Engine & Virtual Machine}/src/cli/commands/boot.rs**	RS	776	3,856	39.0
22	**<TRACK 1> : {Host Engine & Virtual Machine}/src/cli/commands/mod.rs**	RS	44	150	1.8
23	**<TRACK 1> : {Host Engine & Virtual Machine}/src/cli/commands/run.rs**	RS	926	2,972	34.8
24	**<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/hover.rs**	RS	989	3,470	39.9

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/README.md MD 117 LINES 848 WORDS 6.7 KB

```
# OmniCode Terminal Subsystem

```text
================================================================================
BLOCK 1: METADATA & ARCHITECTURAL MANIFESTO
================================================================================
Subsystem: OmniCode Host Engine & Virtual Machine Terminal
Layer:     Interactive Shell, Multi-Track Scheduler & Native Character Echo
Path:      <TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/
================================================================================
```

> **"And he gave unto Moses, when he had made an end of communing with him upon mount Sinai, two tables of testimony, tables of stone, written with the finger of God."**
> — *Exodus 31:18 (KJV)*
> *(The immutable inscription of atomic runes onto bounded physical tablets).*
>
> **"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house."**
> — *Proverbs 24:27 (KJV)*
> *(The discipline of proving atomic sub-engines and verification invariants before constructing complex systems).*
>
> **"Remove not the ancient landmark, which thy fathers have set."**
> — *Proverbs 22:28 (KJV)*
> *(The preservation of historical memory boundaries, silicon addresses, and machine constants).*

---

1. Architectural Mission

The **Terminal Subsystem** serves as the sensory-motor cortex and interactive execution environment of OmniCode. It bridges the virtual machine runtime (`src/runtime/`) to external users, host environments, and bare-metal hypervisors.

Rather than relying on external host shell forks or raw byte pass-throughs, the OmniCode Terminal natively executes process ribbons in persistent silicon memory, schedules cooperative tasks across three execution channels, and drives the **Native Character Invariant Echo Protocol**:

1. **Native Character Echo (`universal/`)**: Proves that every keypress or character stream ingests via `FROM ::@ 0x03F8`, inscribes into an atomic `Cell`, transduces into 5 balanced trits, verifies single-cell capacity bounds ($\le 1\text{ Cell}$), and projects outward via `INTO ::@ 0x000B8000` with affirmative `+1:PROCEED`.
2. **Multi-Track Cooperative Scheduler (`scheduler/`)**: Organizes execution across Track 0 (Kernel), Track 1 (Terminal), and Track 2 (App), carving RAM partitions out of the `Root_Storehouse`.
3. **Interactive Session (`session/`)**: Provides direct in-memory roll evaluation and shell command routing.
4. **Cinematic Projector (`studio/`)**: Renders real-time visual HUD frames of 4-directional Memory Reel kinematics.

---

2. Topological Layer Structure

```bash
src/terminal/
├── universal/                 <-- Tier 1: Hardware MMIO Ports & Native Character Echo
│   ├── ports.rs               <-- FROM (0x03F8), INTO (0x000B8000), Stream Buffers
│   ├── character_echo.rs      <-- 5-Trit Radix-3 Bijective Character Lifecycle & Echo Engine
│   └── mod.rs                 <-- Re-exports Universal I/O & Echo
│
├── scheduler/                 <-- Tier 2: Multi-Track Cooperative Process Dispatcher
│   ├── tasks.rs               <-- OmniTask, Track, TaskPriority, JSON Models
│   ├── scheduler.rs           <-- OmniScheduler, Partition Carving, Tick Loop
│   └── mod.rs                 <-- Re-exports Scheduler & Models
│
├── session/                   <-- Tier 3: Interactive Shell & Upgraded Character I/O
│   ├── commands.rs            <-- Built-in Shell Command Dispatcher
│   ├── session.rs             <-- TerminalSession Coordinator with Native Character Echo
│   └── mod.rs                 <-- Re-exports Session Engine
│
├── studio/                    <-- Tier 4: Cinematic Projector & Memory HUD
│   ├── hud.rs                 <-- ANSI Box-Drawing Frame Renderer
│   ├── kinematics.rs          <-- Reel Transport & Spindle Depth Controls
│   └── mod.rs                 <-- Re-exports Studio Engine
│
├── mod.rs                     <-- Subsystem Public Facade (100% Backward Compatible)
└── README.md                  <-- Architectural Manifesto & Specification
```
```

```
---

## 3. Subsystem Breakdown

### 3.1 Universal (`universal/`)
- **Hardware MMIO Ports (`ports.rs`)**:
  - `UART_COM1_INPUT_PORT = 0x03F8`: Input port for serial keyboard stream.
  - `VGA_TEXT_OUTPUT_PORT = 0x000B8000`: Output port for video console display.
  - `TerminalInputStream` / `TerminalOutputStream`: Bounded FIFO ring buffer queues.
- **Native Character Echo Engine (`character_echo.rs`)**:
  - Bijective Radix-3 transduction: 8-bit ASCII $\iff$ 5 balanced trits $\{-1, 0, +1\}^5$.
  - Inscription into 5-trit `Cell` and single-cell capacity verification under `! GUARD`.
  - Methods: `echo_char(glyph) -> Result<CharacterEchoResult, String>` and `echo_stream(&str) -> Result<String, String>`.

### 3.2 Multi-Track Scheduler (`scheduler/`)
- **`tasks.rs`**: Defines execution channels (`Track::Kernel`, `Track::Terminal`, `Track::App`), priorities (`High`, `Normal`, `Low`, `Background`), and the `OmniTask` descriptor.
- **`scheduler.rs`**: Manages process lifecycles, advances the cooperative `tick` clock, carves partitions from `Root_Storehouse`, and supports manual tape stepping (`step_task`).

### 3.3 Interactive Session (`session/`)
- **`commands.rs`**: Implements built-in shell commands (`ps`, `tracks`, `mem`, `mount`, `run`, `step`, `rolls`, `spawn`, `pause`, `resume`, `kill`, `tick`, `vars`, `help`, `let`).
- **`session.rs`**: Integrates `Environment`, `OmniScheduler`, directional streams, and direct roll evaluation. Exposes `feed_input_char`, `read_output_char`, `process_character_echo`, and `process_character_stream_echo`.

### 3.4 Cinema Studio (`studio/`)
- **`hud.rs`**: ANSI box-drawing projector HUD frame showing active reel, clapper cues, and set props.
- **`kinematics.rs`**: Reel motion evaluator supporting `PLAY`, `PAUSE`, `STOP`, `v--`, `^--`, `<--`, and `-->`.

---

## 4. The Terminal Echo Protocol

```mermaid
graph LR
    A["Host Keypress ('A' = 65)"] --> B["FROM Port (0x03F8 / %from)"]
    B --> C["ROLL 1: INSCRIBE [ Cell ]"]
    C --> D["ROLL 2: TRANSDUCE 5 Trits [-1, 1, 1, -1, 1]"]
    D --> E["ROLL 3: GUARD (<= 1 Cell)"]
    E --> F["ROLL 4: PROJECT [ Target ]"]
    F --> G["INTO Port (0x000B8000 / %into)"]
    G --> H["Host Terminal Screen ('A')"]
```

---

5. Architectural Invariants

1. **Bijective Transduction Parity**: Every byte transduced into 5 balanced trits must reconstruct back to the identical byte ($\sum_{i=0}^4 t_i \cdot 3^i$).
2. **Single-Cell Footprint**: Any single character glyph must evaluate to $\le 1\text{ Cell}$.
3. **Channel Isolation**: Kernel tasks on Track 0 cannot be preempted or modified by unprivileged App tasks on Track 2.
4. **Affirmative Seal**: All terminal rolls must commit in `+1:PROCEED`.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/mod.rs RS | 90 LINES | 387 WORDS | 3.5 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Terminal Subsystem Identity, Public Facade & Architectural Invariants )
// ============================================================================
//! OmniCode Terminal Subsystem Facade
//!
//! # Architectural Scope & Purpose:
//! Provides the primary interactive userspace shell, cooperative process scheduler,
//! hardware MMIO directional stream buffers, native Character Echo Engine, and
//! cinematic HUD projector for the OmniCode platform and upcoming Operating System.
//!
//! Subsystems:
//! - `universal`: Hardware MMIO ports (`0x03F8`, `0x000B8000`), directional streams, and 5-trit Character Echo Engine.
//! - `scheduler`: Multi-Track cooperative task manager (`Track::Kernel`, `Track::Terminal`, `Track::App`).
//! - `session`: Interactive REPL shell, persistent variable state, and direct in-memory roll evaluator.
//! - `studio`: Cinematic HUD projector rendering 4-directional Memory Reel execution frames.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of physical data into bounded terminal tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic terminal I/O engines before constructing user interfaces).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical hardware ports and execution track landmarks).
// ============================================================================

pub mod universal;
pub mod scheduler;
pub mod session;
pub mod studio;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Universal Access & 100% Backward Compatibility )
// ============================================================================

// Universal Terminal Substrate
pub use universal::{
    UART_COM1_INPUT_PORT,
    VGA_TEXT_OUTPUT_PORT,
    DEFAULT_TERMINAL_BUFFER_CAPACITY,
    TerminalInputStream,
    TerminalOutputStream,
    Call,
    Response,
    CharacterResponse,
    NumberResponse,
    StreamResponse,
    CallResponseEngine,
    EchoEngine,
    EchoResult,
};

// Multi-Track Scheduler
pub use scheduler::{
    OmniScheduler,
    OmniTask,
    SharedScheduler,
    TaskPriority,
    Track,
    create_shared_scheduler,
};

// Interactive Session
pub use session::{
    ExecutionResult,
    TerminalSession,
};

```

```
// Cinema Studio
pub use studio::OmniStudio;

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Proofs & Invariants )
// ================================================================================
// Terminal processes and character echo loops are coordinated cooperatively
// across the 3 execution channels with persistent state in the Environment.

// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Module Closure )
// ================================================================================
// Terminal Subsystem facade verified and sealed in affirmative PROCEED.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/scheduler/mod.rs RS 46 LINES 191 WORDS 1.9 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Multi-Track Scheduler Subsystem Identity & Public Exports )
// ============================================================================
//! OmniCode Terminal: Multi-Track Scheduler Subsystem Module
//!
//! Provides the primordial process and task scheduling engine,
//! 3-track execution channels, priority queues, and cooperative tick loops.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**: Tables of testimony, written with the finger of God.
//! - **Proverbs 24:27 (KJV)**: Prepare thy work without, and make it fit for thyself in the field.
//! - **Proverbs 22:28 (KJV)**: Remove not the ancient landmark, which thy fathers have set.
// ============================================================================

pub mod tasks;
pub mod scheduler;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Scheduler & Tasks )
// ============================================================================
pub use tasks::{
    Track,
    TaskPriority,
    OmniTask,
};

pub use scheduler::{
    OmniScheduler,
    SharedScheduler,
    create_shared_scheduler,
};

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Invariants & Cooperative Scheduling Guarantees )
// ============================================================================
// Task execution is isolated across designated channels (Kernel, Terminal, App).

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Module Closure )
// ============================================================================
// Multi-Track Scheduler subsystem verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/scheduler/scheduler.rs | RS | 492 LINES | 1935 WORDS | 20.5 KB

```rust
// ========================================================================
// BLOCK 1: METADATA BLOCK
// ( Multi-Track Cooperative Process Scheduler Engine & Lifecycle Dispatcher )
// ========================================================================
//! OmniCode Terminal: Multi-Track Process Scheduler Engine
//!
//! # Architectural Scope & Purpose:
//! Provides the primary process and task scheduling engine for the OmniCode
//! Native Terminal and OS userspace shell:
//! - Balanced Radix-3 process lifecycles (+1:Proceed, 0:Await, -1:Rollback, NULL:Halt).
//! - Multi-track execution: Track 0 (Kernel), Track 1 (Terminal), Track 2 (App).
//! - Root_Storehouse partition carving for mounted tape process ribbons.
//! - Cooperative `tick` clock and manual tape roll stepping (`step_task`).
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of process state onto physical tables of memory).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving cooperative task scheduling before dispatching shell interfaces).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical execution channel boundaries across kernel, terminal, and apps).
// ========================================================================

use std::path::Path;
use std::sync::{Arc, Mutex};
use std::time::{SystemTime, UNIX_EPOCH};

use crate::core::tape::Tape;
use crate::core::ternary::QuadState;
use crate::core::vessel::Vessel;
use crate::diagnostics::logger::DiagnosticLogger;

use super::tasks::{OmniTask, TaskPriority, Track};

// ========================================================================
// BLOCK 2: OPENING BLOCK
// ( OmniScheduler Struct Definition, Constructor & Defaults )
// ========================================================================

/// Primary multi-track cooperative process scheduler.
#[derive(Debug)]
pub struct OmniScheduler {
    tasks: Vec<OmniTask>,
    next_id: u64,
    /// Root storehouse from which task RAM partitions are carved.
    pub root_storehouse: Vessel,
}

impl Default for OmniScheduler {
    fn default() -> Self {
        let mut scheduler = Self {
            tasks: Vec::new(),
            next_id: 1,
            root_storehouse: Vessel::new_storehouse("Root_RAM", 4096),
        };
        // Initialize default OS background tasks on Track 0 (Kernel)
        scheduler.spawn_on_track("CoreDaemon", "omnicode kernel --daemon", TaskPriority::Background, Track::Kernel);
        scheduler.spawn_on_track("MemoryWatcher", "omnicode mem --watch", TaskPriority::Low, Track::Kernel);
        scheduler
    }
}

// ========================================================================
// BLOCK 3: BODY BLOCK
// ( Scheduler Core: Process Dispatcher, Partition Carving & Tick Engine )
// ========================================================================

impl OmniScheduler {
```

```rust
    /// Constructs a new scheduler initialized with default kernel daemons.
    pub fn new() -> Self {
        Self::default()
    }

    /// Spawns a new task in the scheduler on Track 2 (App) by default.
    pub fn spawn(&mut self, name: &str, command: &str, priority: TaskPriority) -> u64 {
        self.spawn_on_track(name, command, priority, Track::App)
    }

    /// Spawns a new task on a designated execution track (Kernel, Terminal, or App).
    pub fn spawn_on_track(&mut self, name: &str, command: &str, priority: TaskPriority, track: Track) -> u64 {
        let id = self.next_id;
        self.next_id += 1;
        let mut task = OmniTask::with_track(id, name.to_string(), command.to_string(), priority, track);
        task.log_output.push(format!(
            "[*] Task spawned on {} with state +1:PROCEED (Priority: {})",
            track.as_str(),
            priority.as_str()
        ));
        self.tasks.push(task);
        id
    }

    /// Mounts a structured [`Tape`] onto an execution track, carving an isolated memory partition.
    pub fn mount_tape(&mut self, track: Track, mut tape: Tape) -> u64 {
        let id = self.next_id;
        self.next_id += 1;

        let part_size = tape.head.required_partition_size;
        let partition_res = self.root_storehouse.partition(&tape.head.name, part_size);

        tape.bound_partition = Some(tape.head.name.clone());
        let priority = match track {
            Track::Kernel => TaskPriority::High,
            Track::Terminal => TaskPriority::Normal,
            Track::App => TaskPriority::Normal,
        };

        let mut task = OmniTask::with_track(
            id,
            tape.head.name.clone(),
            format!("tape:{}", tape.head.name),
            priority,
            track,
        );

        let part_info = match partition_res {
            Ok(p) => {
                let msg = format!("carved partition '{}' ({} cells)", p.name, p.capacity);
                task.partition = Some(p);
                msg
            }
            Err(e) => format!("partition warning: {e}"),
        };

        task.log_output.push(format!(
            "[+] Mounted Tape '{}' on {} ({}, {} rolls)",
            tape.head.name,
            track.as_str(),
            part_info,
            tape.roll_count()
        ));

        task.tape = Some(tape);
        self.tasks.push(task);
        id
    }

    /// Mounts and parses a `.tape` file from disk onto the specified track.
    pub fn mount_tape_file(&mut self, track: Track, path: impl AsRef<Path>, logger: DiagnosticLogger) -> Result<u64,
String> {
        let tape = Tape::from_file(path, logger)?;
        Ok(self.mount_tape(track, tape))
    }

    /// Advances the scheduler clock by 1 tick, executing tasks in Proceed state.
    ///
```

```
    /// For tasks with mounted Tapes, steps the Tape Head forward roll-by-roll.
    pub fn tick(&mut self) -> usize {
        let mut active_executed = 0;
        let now = SystemTime::now()
            .duration_since(UNIX_EPOCH)
            .unwrap_or_default()
            .as_secs();

        for task in &mut self.tasks {
            if task.state == QuadState::Proceed {
                task.ticks += 1;
                task.updated_at = now;
                active_executed += 1;

                if let Some(ref mut tape) = task.tape {
                    if !tape.is_finished() {
                        if let Some(roll) = tape.active_roll() {
                            task.log_output.push(format!("==> [HEAD @ Roll {}] {}", tape.cursor + 1, roll.text));
                        }
                        tape.advance();
                        if tape.is_finished() {
                            task.log_output.push(format!(
                                "[√] Tape '{}' execution completed successfully (all {} rolls verified)",
                                tape.head.name,
                                tape.roll_count()
                            ));
                        }
                    }
                }
            }
        }
        active_executed
    }

    /// Manually steps the Tape Head on the given task by 1 roll, executing transport kinematics.
    pub fn step_task(&mut self, id: u64) -> Result<String, String> {
        if let Some(task) = self.tasks.iter_mut().find(|t| t.id == id) {
            if let Some(ref mut tape) = task.tape {
                if !tape.is_finished() {
                    let cur_idx = tape.cursor + 1;
                    let roll_text = tape.active_roll().map(|r| r.text.clone()).unwrap_or_default();

                    // Check for STOP transport action
                    let is_unconditional_stop = roll_text.contains("STOP") || (roll_text.contains("HALT") &&
!roll_text.contains("HALT WHEN"));
                    if is_unconditional_stop {
                        tape.cursor = tape.roll_count();
                        task.state = QuadState::Halt;
                        if let Some(ref mut reel) = task.reel {
                            reel.stop();
                        }
                        let msg = format!("[■ STOP] Task {id}: Execution stopped and sealed at Roll {cur_idx}:
{roll_text}");
                        task.log_output.push(msg.clone());
                        return Ok(msg);
                    }

                    // Check for REWIND transport loop action
                    if roll_text.contains("REWIND") {
                        let cue_opt = if let Some(start) = roll_text.find('<') {
                            if let Some(end) = roll_text[start..].find('>') {
                                Some(roll_text[start + 1..start + end].trim().to_string())
                            } else {
                                None
                            }
                        } else {
                            None
                        };

                        if let Some(cue) = cue_opt {
                            if task.loop_count < task.max_loops {
                                if let Some(target_idx) = tape.find_landmark_index(&cue) {
                                    task.loop_count += 1;
                                    tape.rewind_to(target_idx);
                                    if let Some(ref mut reel) = task.reel {
                                        let _ = reel.rewind_to_landmark(&cue);
                                    }
                                    let msg = format!(
```

```
                                        "[⏮ REWIND] Task {id}: Track rewound to Landmark <{cue}> at Roll {} (Iteration {}/{})",
                                        target_idx + 1, task.loop_count, task.max_loops
                                    );
                                    task.log_output.push(msg.clone());
                                    return Ok(msg);
                                }
                            }
                        }
                    }

                    // Check for PAUSE transport action
                    if roll_text.contains("PAUSE") {
                        tape.advance();
                        task.state = QuadState::Await;
                        if let Some(ref mut reel) = task.reel {
                            reel.pause();
                        }
                        let msg = format!("[⏸ PAUSE] Task {id}: Track paused at Roll {cur_idx}: {roll_text}");
                        task.log_output.push(msg.clone());
                        return Ok(msg);
                    }

                    // Default: PLAY (forward advance)
                    tape.advance();
                    if let Some(ref mut reel) = task.reel {
                        reel.play();
                    }
                    let msg = format!("[▶ PLAY] Step PID {id}: Advanced to Roll {cur_idx}/{}: {roll_text}", tape.roll_count());
                    task.log_output.push(msg.clone());
                    Ok(msg)
                } else {
                    Ok(format!("[√] Task {id} Tape '{}' has already executed all {} rolls", task.name, tape.roll_count()))
                }
            } else {
                Err(format!("Task {id} ('{}') has no active mounted Tape ribbon", task.name))
            }
        } else {
            Err(format!("Task ID {id} not found"))
        }
    }

    /// Displays all rolls of a task's tape with the live `==> [HEAD]` pointer.
    pub fn rolls_for_task(&self, id: u64) -> Option<String> {
        let task = self.tasks.iter().find(|t| t.id == id)?;
        let tape = task.tape.as_ref()?;

        let mut out = String::new();
        out.push_str(&format!("TAPE RIBBON: [{}] (PID: {})\n", tape.head.name, task.id));
        out.push_str(&format!("  Channel:   {}\n", task.track.as_str()));
        out.push_str(&format!("  Tape Head: {}\n", tape.head.raw_text));
        out.push_str("------------------------------------------------------------\n");

        for (i, roll) in tape.rolls.iter().enumerate() {
            if i == tape.cursor && !tape.is_finished() {
                out.push_str(&format!("==> [{:>2}] {}\n", i + 1, roll.text));
            } else if i < tape.cursor {
                out.push_str(&format!("  √ [{:>2}] {}\n", i + 1, roll.text));
            } else {
                out.push_str(&format!("    [{:>2}] {}\n", i + 1, roll.text));
            }
        }

        if tape.is_finished() {
            out.push_str("------------------------------------------------------------\n");
            out.push_str("  [√] TAPE EXECUTION COMPLETE (Sealed with PROCEED)\n");
        }
        Some(out)
    }

    /// Returns memory storehouse utilization and active partition breakdown.
    pub fn mem_summary(&self) -> String {
        let total = self.root_storehouse.capacity;
        let allocated = self.root_storehouse.count;
        let free = total.saturating_sub(allocated);
        let pct = if total > 0 { (allocated * 100) / total } else { 0 };
```

```
302
303         let mut out = String::new();
304         out.push_str("============================================================\n");
305         out.push_str("OMNICODE ROOT STOREHOUSE & TASK PARTITIONS\n");
306         out.push_str("============================================================\n");
307         out.push_str(&format!("Root_RAM:     {allocated} / {total} cells ({pct}% Allocated, {free} cells Free)\n"));
308
309         let filled_bars = pct / 5;
310         let empty_bars = 20 - filled_bars;
311         out.push_str(&format!("RAM Meter:    [{}{}] {}%\n", "".repeat(filled_bars), "".repeat(empty_bars), pct));
312         out.push_str("------------------------------------------------------------\n");
313         out.push_str("TASK PARTITION ALLOCATIONS:\n");
314
315         let mut found_part = false;
316         for t in &self.tasks {
317             if let Some(ref p) = t.partition {
318                 found_part = true;
319                 out.push_str(&format!("  • PID {:<3} [{:<16}] Capacity: {:>4} cells (Track: {})\n", t.id, p.name,
p.capacity, t.track.as_str()));
320             }
321         }
322         if !found_part {
323             out.push_str("  (No active task partitions carved yet)\n");
324         }
325         out.push_str("============================================================\n");
326         out
327     }
328
329     /// Returns a structured summary grouping tasks by Track.
330     pub fn track_summary(&self) -> String {
331         let mut out = String::new();
332         out.push_str("============================================================\n");
333         out.push_str("MULTI-TRACK EXECUTION CHANNELS\n");
334         out.push_str("============================================================\n");
335
336         for track in [Track::Kernel, Track::Terminal, Track::App] {
337             out.push_str(&format!("\n[ {} ]\n", track.as_str()));
338             let track_tasks: Vec<&OmniTask> = self.tasks.iter().filter(|t| t.track == track).collect();
339             if track_tasks.is_empty() {
340                 out.push_str("  • (No active processes on this track)\n");
341             } else {
342                 for t in track_tasks {
343                     let tape_tag = if t.tape.is_some() { "[TAPE]" } else { "      " };
344                     let state_badge = match t.state {
345                         QuadState::Proceed => "+1:PROCEED",
346                         QuadState::Await => " 0:AWAIT  ",
347                         QuadState::Rollback => "-1:ROLLBCK",
348                         QuadState::Halt => "NULL:HALT ",
349                     };
350                     out.push_str(&format!("  • PID {:<3} {} {:<10} {:<16} ticks: {}\n", t.id, tape_tag, state_badge,
t.name, t.ticks));
351                 }
352             }
353         }
354         out
355     }
356
357     /// Transitions a task to 0:AWAIT (Standby/Paused).
358     pub fn pause_task(&mut self, id: u64) -> Result<(), String> {
359         if let Some(task) = self.tasks.iter_mut().find(|t| t.id == id) {
360             task.state = QuadState::Await;
361             task.log_output.push("[~] Task transitioned to 0:AWAIT (Suspended)".to_string());
362             Ok(())
363         } else {
364             Err(format!("Task ID {id} not found"))
365         }
366     }
367
368     /// Resumes a task back to +1:PROCEED (Running).
369     pub fn resume_task(&mut self, id: u64) -> Result<(), String> {
370         if let Some(task) = self.tasks.iter_mut().find(|t| t.id == id) {
371             task.state = QuadState::Proceed;
372             task.log_output.push("[+] Task resumed to +1:PROCEED".to_string());
373             Ok(())
374         } else {
375             Err(format!("Task ID {id} not found"))
376         }
377     }
```

```rust

    /// Signals a rollback on a task (-1:ROLLBACK).
    pub fn rollback_task(&mut self, id: u64, reason: &str) -> Result<(), String> {
        if let Some(task) = self.tasks.iter_mut().find(|t| t.id == id) {
            task.state = QuadState::Rollback;
            task.log_output.push(format!("[-] Task rolled back to -1:ROLLBACK. Reason: {reason}"));
            Ok(())
        } else {
            Err(format!("Task ID {id} not found"))
        }
    }

    /// Halts and terminates a task (NULL:HALT).
    pub fn halt_task(&mut self, id: u64) -> Result<(), String> {
        if let Some(task) = self.tasks.iter_mut().find(|t| t.id == id) {
            task.state = QuadState::Halt;
            task.log_output.push("[!] Task terminated with state NULL:HALT".to_string());
            Ok(())
        } else {
            Err(format!("Task ID {id} not found"))
        }
    }

    /// Appends output log line to a task.
    pub fn log_task(&mut self, id: u64, line: &str) {
        if let Some(task) = self.tasks.iter_mut().find(|t| t.id == id) {
            task.log_output.push(line.to_string());
        }
    }

    /// Returns all tasks formatted as a JSON array.
    pub fn to_json(&self) -> String {
        let task_jsons: Vec<String> = self.tasks.iter().map(|t| t.to_json()).collect();
        format!("[{}]", task_jsons.join(","))
    }

    /// Returns a human-readable table of all running processes.
    pub fn format_table(&self) -> String {
        let mut out = String::new();
        out.push_str("PID   STATE        CHANNEL         PRIORITY    TICKS   COMMAND\n");
        out.push_str("-------------------------------------------------------------------------------\n");
        for t in &self.tasks {
            let state_badge = match t.state {
                QuadState::Proceed => "+1 PROCEED",
                QuadState::Await => " 0 AWAIT  ",
                QuadState::Rollback => "-1 ROLLBCK",
                QuadState::Halt => "NULL HALT ",
            };
            out.push_str(&format!(
                "{:<5} {:<12} {:<15} {:<11} {:<7} {}\n",
                t.id,
                state_badge,
                t.track.as_str(),
                t.priority.as_str(),
                t.ticks,
                t.command
            ));
        }
        out
    }

    /// Returns a reference to all tasks in the scheduler.
    pub fn tasks(&self) -> &[OmniTask] {
        &self.tasks
    }

    /// Finds a task by ID.
    pub fn get_task(&self, id: u64) -> Option<&OmniTask> {
        self.tasks.iter().find(|t| t.id == id)
    }

    /// Finds a mutable reference to a task by ID.
    pub fn get_task_mut(&mut self, id: u64) -> Option<&mut OmniTask> {
        self.tasks.iter_mut().find(|t| t.id == id)
    }
}

// ================================================================================
```

```rust
// BLOCK 4: CLOSING BLOCK
// ( Global Thread-Safe Scheduler Handle & Verification Tests )
// ================================================================================

/// Thread-safe shared scheduler pointer wrapped in `Arc<Mutex<OmniScheduler>>`.
pub type SharedScheduler = Arc<Mutex<OmniScheduler>>;

/// Factory function creating a thread-safe shared scheduler instance.
pub fn create_shared_scheduler() -> SharedScheduler {
    Arc::new(Mutex::new(OmniScheduler::new()))
}

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_scheduler_lifecycle() {
        let mut sched = OmniScheduler::new();
        let pid = sched.spawn("TestProcess", "omnicode test", TaskPriority::High);

        assert_eq!(sched.tasks.iter().find(|t| t.id == pid).unwrap().state, QuadState::Proceed);

        sched.tick();
        assert_eq!(sched.tasks.iter().find(|t| t.id == pid).unwrap().ticks, 1);

        sched.pause_task(pid).unwrap();
        assert_eq!(sched.tasks.iter().find(|t| t.id == pid).unwrap().state, QuadState::Await);

        sched.resume_task(pid).unwrap();
        assert_eq!(sched.tasks.iter().find(|t| t.id == pid).unwrap().state, QuadState::Proceed);

        sched.halt_task(pid).unwrap();
        assert_eq!(sched.tasks.iter().find(|t| t.id == pid).unwrap().state, QuadState::Halt);
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/scheduler/tasks.rs RS 234 LINES 853 WORDS 8.4 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Multi-Track Execution Channels, Task Priorities & Process Descriptor )
// ================================================================================
//! OmniCode Terminal: Multi-Track Execution Channels & Task Models
//!
//! # Architectural Scope & Purpose:
//! Encapsulates process and task data models for the OmniCode Terminal Scheduler:
//! - 3 Physical execution channels: [`Track::Kernel`] (0), [`Track::Terminal`] (1), [`Track::App`] (2).
//! - 4 Priority tiers: [`TaskPriority::High`], [`TaskPriority::Normal`], [`TaskPriority::Low`], [`TaskPriority::Background`].
//! - [`OmniTask`]: Persistent descriptor managing process state, bound tape, memory partition, and logs.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of process descriptors into bounded memory tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving process descriptor models before dispatching scheduler loops).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical execution channel boundaries across kernel, terminal, and apps).
// ================================================================================

use std::time::{SystemTime, UNIX_EPOCH};

use crate::core::reel::MemoryReel;
use crate::core::tape::Tape;
use crate::core::ternary::QuadState;
use crate::core::vessel::Vessel;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Track & TaskPriority Enums and OmniTask Definition )
// ================================================================================

/// The 3 physical execution channels of the Multi-Track Scheduler.
#[derive(Debug, Clone, Copy, PartialEq, Eq, PartialOrd, Ord, Hash)]
pub enum Track {
    /// Track 0: Hardware / Kernel Genesis / Core Daemons.
    Kernel = 0,
    /// Track 1: Terminal Shell & Console HUD.
    Terminal = 1,
    /// Track 2: Userspace & Worker Applications.
    App = 2,
}

impl Track {
    /// Returns the canonical display string for this execution channel.
    pub fn as_str(&self) -> &'static str {
        match self {
            Track::Kernel => "TRACK 0 [KERNEL]",
            Track::Terminal => "TRACK 1 [TERMINAL]",
            Track::App => "TRACK 2 [APP]",
        }
    }
}

/// Scheduling priority tier for active processes.
#[derive(Debug, Clone, Copy, PartialEq, Eq, PartialOrd, Ord, Hash)]
pub enum TaskPriority {
    High = 3,
    Normal = 2,
    Low = 1,
    Background = 0,
}

impl TaskPriority {
    /// Returns the uppercase text representation of this priority.
    pub fn as_str(&self) -> &'static str {
        match self {
```

```
            TaskPriority::High => "HIGH",
            TaskPriority::Normal => "NORMAL",
            TaskPriority::Low => "LOW",
            TaskPriority::Background => "BACKGROUND",
        }
    }

    /// Resolves a string into a TaskPriority variant.
    pub fn from_str(s: &str) -> Self {
        match s.trim().to_uppercase().as_str() {
            "HIGH" | "3" => TaskPriority::High,
            "LOW" | "1" => TaskPriority::Low,
            "BACKGROUND" | "IDLE" | "0" => TaskPriority::Background,
            _ => TaskPriority::Normal,
        }
    }
}

/// Descriptor representing an active, waiting, or halted process in the terminal.
#[derive(Debug, Clone)]
pub struct OmniTask {
    /// Unique process identifier (PID).
    pub id: u64,
    /// Human-readable process name.
    pub name: String,
    /// Shell command or entry point string.
    pub command: String,
    /// Scheduling priority tier.
    pub priority: TaskPriority,
    /// Designated execution channel.
    pub track: Track,
    /// Balanced ternary process state (+1:Proceed, 0:Await, -1:Rollback, NULL:Halt).
    pub state: QuadState,
    /// UNIX timestamp of process creation.
    pub created_at: u64,
    /// UNIX timestamp of last update or tick.
    pub updated_at: u64,
    /// Total cooperative scheduler ticks elapsed.
    pub ticks: u64,
    /// Log output ring buffer.
    pub log_output: Vec<String>,
    /// Mounted process tape ribbon, if executing tape-based logic.
    pub tape: Option<Tape>,
    /// Bounded RAM partition carved from Root_Storehouse.
    pub partition: Option<Vessel>,
    /// 4-directional memory reel for cinematic HUD stepping.
    pub reel: Option<MemoryReel>,
    /// Current loop counter.
    pub loop_count: usize,
    /// Maximum allowed loops before watchdog intervention.
    pub max_loops: usize,
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( OmniTask Constructors & Serializers )
// ============================================================================

impl OmniTask {
    /// Constructs a new task on Track 2 (App) by default.
    pub fn new(id: u64, name: String, command: String, priority: TaskPriority) -> Self {
        Self::with_track(id, name, command, priority, Track::App)
    }

    /// Constructs a new task on the specified execution channel.
    pub fn with_track(id: u64, name: String, command: String, priority: TaskPriority, track: Track) -> Self {
        let now = SystemTime::now()
            .duration_since(UNIX_EPOCH)
            .unwrap_or_default()
            .as_secs();

        Self {
            id,
            name: name.clone(),
            command,
            priority,
            track,
            state: QuadState::Proceed,
```

```
            created_at: now,
            updated_at: now,
            ticks: 0,
            log_output: Vec::new(),
            tape: None,
            partition: None,
            reel: Some(MemoryReel::new(name, 64)),
            loop_count: 0,
            max_loops: 100,
        }
    }

    /// Serializes the task descriptor into a structured JSON string.
    pub fn to_json(&self) -> String {
        let state_str = match self.state {
            QuadState::Proceed => "+1:PROCEED",
            QuadState::Await => "0:AWAIT",
            QuadState::Rollback => "-1:ROLLBACK",
            QuadState::Halt => "NULL:HALT",
        };

        let logs = self.log_output.join("\\n").replace('"', "\\\"");

        format!(
            r#"{{"id":{},"name":"{}","command":"{}","priority":"{}","track":"{}","state":"{}","ticks":{},"created_at":{},"logs":"{}"}}"#,
            self.id,
            self.name,
            self.command.replace('"', "\\\""),
            self.priority.as_str(),
            self.track.as_str(),
            state_str,
            self.ticks,
            self.created_at,
            logs
        )
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Test Verification Proofs & Invariants )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_track_hierarchy_and_names() {
        assert_eq!(Track::Kernel.as_str(), "TRACK 0 [KERNEL]");
        assert_eq!(Track::Terminal.as_str(), "TRACK 1 [TERMINAL]");
        assert_eq!(Track::App.as_str(), "TRACK 2 [APP]");
    }

    #[test]
    fn test_task_priority_resolution() {
        assert_eq!(TaskPriority::from_str("high"), TaskPriority::High);
        assert_eq!(TaskPriority::from_str("1"), TaskPriority::Low);
        assert_eq!(TaskPriority::from_str("idle"), TaskPriority::Background);
        assert_eq!(TaskPriority::from_str("unknown"), TaskPriority::Normal);
    }

    #[test]
    fn test_omni_task_creation_and_json() {
        let task = OmniTask::with_track(
            42,
            "InitDaemon".into(),
            "boot --init".into(),
            TaskPriority::High,
            Track::Kernel,
        );
        assert_eq!(task.id, 42);
        assert_eq!(task.track, Track::Kernel);
        assert_eq!(task.state, QuadState::Proceed);

        let json = task.to_json();
        assert!(json.contains("\"id\":42"));
```

```
        assert!(json.contains("\"name\":\"InitDaemon\""));
        assert!(json.contains("\"priority\":\"HIGH\""));
        assert!(json.contains("\"track\":\"TRACK 0 [KERNEL]\""));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/session/commands.rs RS 801 LINES 2660 WORDS 32.4 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Terminal Built-in Shell Command Dispatcher & Host OS Interlock )
// ================================================================================
//! OmniCode Terminal: Built-in Shell Command Dispatcher
//!
//! # Architectural Scope & Purpose:
//! Handles parsing and execution of native operating system shell commands:
//! - Process table inspection (`ps`, `tasks`).
//! - Multi-track execution channel inspection (`tracks`, `channels`).
//! - Storehouse RAM utilization meter (`mem`, `ram`).
//! - Tape mounting and step execution (`mount`, `run`, `step`, `rolls`).
//! - Cooperative scheduler clock stepping (`tick`).
//! - Process control (`spawn`, `pause`, `resume`, `kill`, `halt`).
//! - Variable declarations (`let x = 42`) and environment inspection (`vars`, `env`).
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**: Tables of testimony, written with the finger of God.
//! - **Proverbs 24:27 (KJV)**: Prepare thy work without, and make it fit for thyself in the field.
//! - **Proverbs 22:28 (KJV)**: Remove not the ancient landmark, which thy fathers have set.
// ================================================================================

use std::collections::HashMap;
use std::time::Instant;

use crate::cogs::tripwire::Tripwire;
use crate::core::filetype::resolve_track_path;
use crate::core::ternary::QuadState;
use crate::diagnostics::debugger::OmniDebugger;
use crate::diagnostics::logger::{DiagnosticLogger, FailpointType};
use crate::runtime::environment::Environment;
use crate::terminal::scheduler::{SharedScheduler, TaskPriority, Track};

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( ExecutionResult Container & Command Dispatch Function Signature )
// ================================================================================

/// Result of an interactive terminal command execution.
#[derive(Debug, Clone, PartialEq, Eq)]
pub struct ExecutionResult {
    /// Text emitted to stdout during execution.
    pub stdout: String,
    /// Balanced ternary state following execution (+1:Proceed, 0:Await, -1:Rollback, NULL:Halt).
    pub state: QuadState,
    /// Execution duration in microseconds.
    pub duration_us: u128,
}

impl ExecutionResult {
    /// Constructs a successful execution result with state +1:PROCEED.
    pub fn success(stdout: String, duration_us: u128) -> Self {
        Self {
            stdout,
            state: QuadState::Proceed,
            duration_us,
        }
    }

    /// Constructs an asynchronous wait or standby result with state 0:AWAIT.
    pub fn await_state(stdout: String, duration_us: u128) -> Self {
        Self {
            stdout,
            state: QuadState::Await,
            duration_us,
        }
    }

    /// Constructs a failed or rollback result with state -1:ROLLBACK.
    pub fn failure(stdout: String, duration_us: u128) -> Self {
        Self {
            stdout,
            state: QuadState::Rollback,
            duration_us,
```

```
        }
    }
}

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Built-in Shell Command Dispatch Engine )
// ================================================================================

/// Dispatches built-in terminal shell commands. Returns `Some(ExecutionResult)` if
/// the command was handled, or `None` if it should fall through to roll evaluation.
pub fn dispatch_builtin_command(
    trimmed: &str,
    scheduler: &SharedScheduler,
    env: &Environment,
    variables: &mut HashMap<String, String>,
    logger: &DiagnosticLogger,
    _debugger: &OmniDebugger,
    start: Instant,
) -> Option<ExecutionResult> {
    // 0. Universal Call & Response Engine (ECHO command)
    if trimmed == "echo" || trimmed.starts_with("echo ") {
        let raw_payload = if trimmed == "echo" {
            ""
        } else {
            trimmed["echo ".len()..].trim()
        };
        let payload = if (raw_payload.starts_with('\'') && raw_payload.ends_with('\'') && raw_payload.len() >= 2)
            || (raw_payload.starts_with('"') && raw_payload.ends_with('"') && raw_payload.len() >= 2)
        {
            &raw_payload[1..raw_payload.len() - 1]
        } else {
            raw_payload
        };

        // Determine if payload is a numeric/binary scalar Call
        let num_parse = if payload.starts_with("0b") || payload.starts_with("0B") {
            i64::from_str_radix(&payload[2..], 2).ok()
        } else {
            payload.parse::<i64>().ok()
        };

        if let Some(n) = num_parse {
            match crate::terminal::universal::call_response_engine::CallResponseEngine::call_number(n) {
                Ok(resp) => {
                    let out = format!(
                        "Number: {} | Dual-Rail: 0x{:016X} | Pack(2-2-2-2): 0x{:02X} | Pack(2-1-2-1-2): 0x{:02X} |
Equilibrium: PROVED | State: +1:PROCEED",
                        resp.scalar, resp.packed_dual_rail, resp.byte_pack_2222, resp.byte_pack_21212
                    );
                    return Some(ExecutionResult::success(out, start.elapsed().as_micros()));
                }
                Err(e) => {
                    let err = Tripwire::trip(
                        logger,
                        "TERMINAL_ECHO",
                        FailpointType::SyntaxAnomaly,
                        format!("Number Call-Response failed: {e}"),
                    );
                    return Some(ExecutionResult::failure(
                        format!("[!] {err}"),
                        start.elapsed().as_micros(),
                    ));
                }
            }
        }

        // Otherwise execute Stream / Character Call-Response turn
        match crate::terminal::universal::call_response_engine::CallResponseEngine::call_stream(payload) {
            Ok(resp) => {
                return Some(ExecutionResult::success(resp.text, start.elapsed().as_micros()));
            }
            Err(e) => {
                let err = Tripwire::trip(
                    logger,
                    "TERMINAL_ECHO",
                    FailpointType::SyntaxAnomaly,
                    format!("Echo Call-Response failed: {e}"),
```

```
                );
                return Some(ExecutionResult::failure(
                    format!("[!] {err}"),
                    start.elapsed().as_micros(),
                ));
            }
        }
    }

    // 0b. Explicit number call (Convenience alias)
    if trimmed.starts_with("number ") || trimmed.starts_with("num ") {
        let raw = if trimmed.starts_with("number ") {
            trimmed["number ".len()..].trim()
        } else {
            trimmed["num ".len()..].trim()
        };
        if let Ok(n) = raw.parse::<i64>() {
            match crate::terminal::universal::call_response_engine::CallResponseEngine::call_number(n) {
                Ok(resp) => {
                    let out = format!(
                        "Number: {} | Dual-Rail: 0x{:016X} | Pack(2-2-2-2): 0x{:02X} | Pack(2-1-2-1-2): 0x{:02X} |
Equilibrium: PROVED | State: +1:PROCEED",
                        resp.scalar, resp.packed_dual_rail, resp.byte_pack_2222, resp.byte_pack_21212
                    );
                    return Some(ExecutionResult::success(out, start.elapsed().as_micros()));
                }
                Err(e) => {
                    return Some(ExecutionResult::failure(
                        format!("[!] Number call failed: {e}"),
                        start.elapsed().as_micros(),
                    ));
                }
            }
        }
    }

    // 1. Process table
    if trimmed == "ps" || trimmed == "tasks" {
        let sched = scheduler.lock().unwrap();
        let table = sched.format_table();
        return Some(ExecutionResult::success(table, start.elapsed().as_micros()));
    }

    // 2. Multi-track channel summary
    if trimmed == "tracks" || trimmed == "channels" {
        let sched = scheduler.lock().unwrap();
        let summary = sched.track_summary();
        return Some(ExecutionResult::success(summary, start.elapsed().as_micros()));
    }

    // 3. Storehouse memory meter
    if trimmed == "mem" || trimmed == "ram" {
        let sched = scheduler.lock().unwrap();
        let summary = sched.mem_summary();
        return Some(ExecutionResult::success(summary, start.elapsed().as_micros()));
    }

    // 4. Mount a tape file onto Track 2 (App) or Track 0 (Kernel)
    if trimmed.starts_with("mount ") {
        let raw_path = trimmed["mount ".len()..].trim();
        let resolved = resolve_track_path(raw_path);
        let path_str = resolved.to_string_lossy().to_string();
        let mut sched = scheduler.lock().unwrap();
        let track = if raw_path.contains("kernel") || raw_path.contains("boot") {
            Track::Kernel
        } else {
            Track::App
        };
        match sched.mount_tape_file(track, &path_str, logger.clone()) {
            Ok(pid) => return Some(ExecutionResult::success(
                format!("[+] Mounted Tape '{raw_path}' onto {} with PID {pid}", track.as_str()),
                start.elapsed().as_micros(),
            )),
            Err(e) => {
                let err = Tripwire::trip(
                    logger,
                    "TERMINAL_MOUNT",
                    FailpointType::SyntaxAnomaly,
```

```
                    format!("Failed to mount tape '{raw_path}': {e}"),
                );
                return Some(ExecutionResult::failure(
                    format!("[!] {err}"),
                    start.elapsed().as_micros(),
                ));
            }
        }
    }

    // 5. Mount and execute a tape, omni, C, or Lua file
    if trimmed.starts_with("run ") {
        let path = trimmed["run ".len()..].trim();
        let track = if path.contains("kernel") || path.contains("boot") {
            Track::Kernel
        } else {
            Track::App
        };

        // If it's a tape, preserve existing scheduler mount & step logs
        if path.ends_with(".tape") {
            let resolved = resolve_track_path(path);
            let path_str = resolved.to_string_lossy().to_string();
            let mut sched = scheduler.lock().unwrap();
            match sched.mount_tape_file(track, &path_str, logger.clone()) {
                Ok(pid) => {
                    let mut logs = Vec::new();
                    logs.push(format!("[+] Mounted Tape '{path}' onto {} (PID {pid})", track.as_str()));
                    loop {
                        match sched.step_task(pid) {
                            Ok(msg) => {
                                logs.push(msg.clone());
                                if msg.contains("completed") || msg.contains("already executed") || msg.contains("STOP")
{
                                    break;
                                }
                            }
                            Err(e) => {
                                let err = Tripwire::trip(
                                    logger,
                                    "TERMINAL_RUN",
                                    FailpointType::SyntaxAnomaly,
                                    format!("Task {pid} execution halted: {e}"),
                                );
                                logs.push(format!("[!] {err}"));
                                break;
                            }
                        }
                    }
                    return Some(ExecutionResult::success(logs.join("\n"), start.elapsed().as_micros()));
                }
                Err(e) => {
                    let err = Tripwire::trip(
                        logger,
                        "TERMINAL_RUN",
                        FailpointType::SyntaxAnomaly,
                        format!("Failed to run tape '{path}': {e}"),
                    );
                    return Some(ExecutionResult::failure(
                        format!("[!] {err}"),
                        start.elapsed().as_micros(),
                    ));
                }
            }
        } else if path.ends_with(".omni") || path.ends_with(".c") || path.ends_with(".lua") {
            let config = crate::cli::commands::run::RunConfig::new(path);
            let ctx = match config.open(logger) {
                Ok(c) => c,
                Err(e) => {
                    return Some(ExecutionResult::failure(
                        format!("[!] {e}"),
                        start.elapsed().as_micros(),
                    ));
                }
            };
            match crate::cli::commands::run::execute_run_pipeline(&ctx) {
                Ok(res) => {
                    return Some(ExecutionResult::success(res.output, start.elapsed().as_micros()));
```

```
                }
                Err(e) => {
                    return Some(ExecutionResult::failure(
                        format!("[!] {e}"),
                        start.elapsed().as_micros(),
                    ));
                }
            }
        }
    }

    // 6. Step Tape Head on a task
    if trimmed.starts_with("step ") {
        let pid_str = trimmed["step ".len()..].trim();
        if let Ok(pid) = pid_str.parse::<u64>() {
            let mut sched = scheduler.lock().unwrap();
            match sched.step_task(pid) {
                Ok(msg) => return Some(ExecutionResult::success(msg, start.elapsed().as_micros())),
                Err(e) => return Some(ExecutionResult::failure(format!("[!] Error: {e}"), start.elapsed().as_micros())),
            }
        } else {
            return Some(ExecutionResult::failure("Usage: step <pid>".to_string(), start.elapsed().as_micros()));
        }
    }

    // 7. Display rolls on a task
    if trimmed.starts_with("rolls ") {
        let pid_str = trimmed["rolls ".len()..].trim();
        if let Ok(pid) = pid_str.parse::<u64>() {
            let sched = scheduler.lock().unwrap();
            match sched.rolls_for_task(pid) {
                Some(rolls_str) => return Some(ExecutionResult::success(rolls_str, start.elapsed().as_micros())),
                None => return Some(ExecutionResult::failure(format!("[!] Task {pid} not found or has no mounted tape"),
start.elapsed().as_micros())),
            }
        } else {
            return Some(ExecutionResult::failure("Usage: rolls <pid>".to_string(), start.elapsed().as_micros()));
        }
    }

    // 8. General task spawning
    if trimmed.starts_with("spawn ") {
        let cmd = trimmed["spawn ".len()..].trim();
        let mut sched = scheduler.lock().unwrap();
        let pid = sched.spawn("UserTask", cmd, TaskPriority::Normal);
        return Some(ExecutionResult::success(
            format!("[+] Spawned process PID {pid}: '{cmd}' with state +1:PROCEED"),
            start.elapsed().as_micros(),
        ));
    }

    // 9. Task controls
    if trimmed.starts_with("pause ") || trimmed.starts_with("await ") {
        let pid_str = trimmed.split_whitespace().nth(1).unwrap_or("");
        if let Ok(pid) = pid_str.parse::<u64>() {
            let mut sched = scheduler.lock().unwrap();
            match sched.pause_task(pid) {
                Ok(()) => return Some(ExecutionResult::await_state(format!("[~] Task {pid} transitioned to 0:AWAIT"),
start.elapsed().as_micros())),
                Err(e) => return Some(ExecutionResult::failure(format!("[!] Error: {e}"), start.elapsed().as_micros())),
            }
        }
    }

    if trimmed.starts_with("resume ") {
        let pid_str = trimmed.split_whitespace().nth(1).unwrap_or("");
        if let Ok(pid) = pid_str.parse::<u64>() {
            let mut sched = scheduler.lock().unwrap();
            match sched.resume_task(pid) {
                Ok(()) => return Some(ExecutionResult::success(format!("[+] Task {pid} resumed to +1:PROCEED"),
start.elapsed().as_micros())),
                Err(e) => return Some(ExecutionResult::failure(format!("[!] Error: {e}"), start.elapsed().as_micros())),
            }
        }
    }

    if trimmed.starts_with("kill ") || trimmed.starts_with("halt ") {
        let pid_str = trimmed.split_whitespace().nth(1).unwrap_or("");
```

```
        if let Ok(pid) = pid_str.parse::<u64>() {
            let mut sched = scheduler.lock().unwrap();
            match sched.halt_task(pid) {
                Ok(()) => return Some(ExecutionResult::success(format!("[!] Task {pid} halted (NULL:HALT)"),
start.elapsed().as_micros())),
                Err(e) => return Some(ExecutionResult::failure(format!("[!] Error: {e}"), start.elapsed().as_micros())),
            }
        }
    }

    if trimmed == "tick" {
        let mut sched = scheduler.lock().unwrap();
        let count = sched.tick();
        return Some(ExecutionResult::success(format!("[*] Advanced scheduler clock 1 tick. Executed {count} active
tasks."), start.elapsed().as_micros()));
    }

    if trimmed == "vars" || trimmed == "env" {
        let mut out = String::from("ACTIVE SESSION STATE:\n");
        let mut has_entries = false;
        for (k, v) in env.bindings() {
            out.push_str(&format!("  {} = {:?}\n", k, v));
            has_entries = true;
        }
        for (k, v) in variables.iter() {
            out.push_str(&format!("  let {} = {}\n", k, v));
            has_entries = true;
        }
        if !has_entries {
            return Some(ExecutionResult::success("No active session bindings declared.".to_string(),
start.elapsed().as_micros()));
        }
        return Some(ExecutionResult::success(out, start.elapsed().as_micros()));
    }

    // 10. AI Model Inquiry & Cognitive Dialogue
    if trimmed.starts_with("ai ") {
        let raw_args = trimmed["ai ".len()..].trim();
        let (prompt_str, verbose) = if raw_args.starts_with("-v ") {
            (raw_args["-v ".len()..].trim(), true)
        } else if raw_args.starts_with("--verbose ") {
            (raw_args["--verbose ".len()..].trim(), true)
        } else {
            (raw_args, false)
        };

        let prompt = if (prompt_str.starts_with('"')
            && prompt_str.ends_with('"')
            && prompt_str.len() >= 2)
            || (prompt_str.starts_with('\'')
                && prompt_str.ends_with('\'')
                && prompt_str.len() >= 2)
        {
            &prompt_str[1..prompt_str.len() - 1]
        } else {
            prompt_str
        };

        let mut cortex = crate::ai::AICortex::new();
        match cortex.process_prompt(prompt) {
            Ok(res) => {
                let out = if verbose {
                    let mut s = format!(
                        "[CPI-SI Cognitive Thought Trace]\n\
                         • State: +1:{}\n\
                         • WHO:   {}\n\
                         • WHAT:  {}\n\
                         • WHY:   {}\n\
                         • HOW:   {}\n\n\
                         [Synthesized Reel]\n{}\n\n\
                         [Machine Layer Response]\n\"{}\"\n\n\
                         [Session: {} | Scroll: {:?}]",
                        res.execution_state.macro_op(),
                        res.thought.who,
                        res.thought.what,
                        res.thought.why,
                        res.thought.how,
                        res.synthesized_omnicode.trim(),
```

```
                        res.natural_response,
                        res.session_id,
                        res.scroll_path
                    );
                    if !res.repairs_applied.is_empty() {
                        s.push_str(&format!(
                            "\n[Restorator Repairs: {}]",
                            res.repairs_applied.len()
                        ));
                    }
                    s
                } else {
                    format!(
                        "[AI Model Response: CPI-SI Base]\n\"{}\"\n\n\
                        [Session: {}]",
                        res.natural_response, res.session_id
                    )
                };
                return Some(ExecutionResult::success(
                    out,
                    start.elapsed().as_micros(),
                ));
            }
            Err(e) => {
                return Some(ExecutionResult::failure(
                    format!("[!] AI Cortex Error: {e}"),
                    start.elapsed().as_micros(),
                ));
            }
        }
    }

    // 11. O(1) Episodic Session Query
    if trimmed.starts_with("query ") {
        let sid = trimmed["query ".len()..].trim();
        let cortex = crate::ai::AICortex::new();
        if let Some(s) = cortex.query_episode(sid) {
            let state_str = match s.final_state.as_int() {
                Some(i) => format!("{i:+}:{}", s.final_state.macro_op()),
                _ => format!("*:{}", s.final_state.macro_op()),
            };
            let paired_str = s
                .log_path
                .as_deref()
                .map(|p| p.to_string_lossy().into_owned())
                .unwrap_or_else(|| "(none)".to_string());
            let out = format!(
                "Session: {}\n  • Category:   {}\n  • State:      {}\n  • Prompt:     \"{}\"\n  • Failpoints: {}\n  • Repairs:    {}\n  • Scroll:     {:?}\n  • Telemetry:  {}",
                s.session_id,
                s.category,
                state_str,
                s.prompt,
                s.failpoint_count,
                s.repair_count,
                s.scroll_path,
                paired_str,
            );
            return Some(ExecutionResult::success(
                out,
                start.elapsed().as_micros(),
            ));
        } else {
            return Some(ExecutionResult::failure(
                format!("[!] Session '{sid}' not found in episodic storehouse"),
                start.elapsed().as_micros(),
            ));
        }
    }

    // 12. Failpoint & Anomaly Diagnostic Report
    if trimmed.starts_with("diagnose ") {
        let sid = trimmed["diagnose ".len()..].trim();
        let cortex = crate::ai::AICortex::new();
        if let Some(diag) = cortex.diagnose_failpoint(sid) {
            return Some(ExecutionResult::success(
                diag,
                start.elapsed().as_micros(),
```

```
            ));
        } else {
            return Some(ExecutionResult::failure(
                format!("[!] Session '{sid}' not found in episodic storehouse"),
                start.elapsed().as_micros(),
            ));
        }
    }

    // 13. Episodic Memory Listing
    if trimmed == "episodes" || trimmed.starts_with("episodes ")
        || trimmed == "scrolls" || trimmed.starts_with("scrolls ")
    {
        let count = if trimmed.starts_with("episodes ") {
            trimmed["episodes ".len()..]
                .trim()
                .parse::<usize>()
                .unwrap_or(10)
        } else if trimmed.starts_with("scrolls ") {
            trimmed["scrolls ".len()..]
                .trim()
                .parse::<usize>()
                .unwrap_or(10)
        } else {
            10
        };

        let cortex = crate::ai::AICortex::new();
        let recents = cortex.recent_episodes(count);
        if recents.is_empty() {
            return Some(ExecutionResult::success(
                "No episodes found in storehouse.".to_string(),
                start.elapsed().as_micros(),
            ));
        }

        let mut out = format!("RECENT EPISODES (Last {}):\n", recents.len());
        for (i, s) in recents.iter().enumerate() {
            let state_str = match s.final_state.as_int() {
                Some(val) => format!("{val:+}:{}", s.final_state.macro_op()),
                _ => format!("*:{}", s.final_state.macro_op()),
            };
            out.push_str(&format!(
                "  [{:>2}] {} | Cat: {:<8} | State: {:<11} | FP: {:>2} | Rep: {:>2}\n       Prompt: \"{}\"\n",
                i + 1,
                s.session_id,
                s.category,
                state_str,
                s.failpoint_count,
                s.repair_count,
                s.prompt,
            ));
        }
        return Some(ExecutionResult::success(
            out,
            start.elapsed().as_micros(),
        ));
    }

    // 14. Storehouse Vessel Capacity Rotation
    if trimmed == "rotate" || trimmed.starts_with("rotate ") {
        let cap = if trimmed.starts_with("rotate ") {
            trimmed["rotate ".len()..]
                .trim()
                .parse::<usize>()
                .unwrap_or(1000)
        } else {
            1000
        };
        let policy = crate::diagnostics::logger::RotationPolicy::new(
            cap, true,
        );
        let scroll_dir = crate::core::filetype::resolve_scroll_storage_dir();
        let s_logger = crate::ai::ScrollLogger::with_rotation_policy(
            &scroll_dir,
            policy,
        );
        match s_logger.rotate_storehouse() {
```

```
            Ok(n) => return Some(ExecutionResult::success(
                format!(
                    "[√] Rotated storehouse (cap={cap}): {n} excess archived"
                ),
                start.elapsed().as_micros(),
            )),
            Err(e) => return Some(ExecutionResult::failure(
                format!("[!] Rotation failed: {e}"),
                start.elapsed().as_micros(),
            )),
        }
    }

    // 14b. CPI-SI Discourse Prompt & Interaction
    if trimmed == "cpisi" || trimmed.starts_with("cpisi ")
        || trimmed == "interact" || trimmed.starts_with("interact ")
    {
        let prompt = if trimmed.contains(' ') {
            trimmed.split_once(' ').map(|x| x.1).unwrap_or("hello")
        } else {
            "hello"
        };
        let mut cortex = crate::ai::AICortex::new();
        match cortex.process_prompt(prompt) {
            Ok(res) => {
                let (exc, neu, inh) = cortex.brain.synaptic_counts();
                let out = format!(
                    "[√] CPI-SI Base Deliberation (+1:{}):\n  \
                     • Response: \"{}\"\n  \
                     • Synapse State: +1: {}, 0: {}, -1: {}",
                    res.execution_state.macro_op(),
                    res.natural_response,
                    exc, neu, inh
                );
                return Some(ExecutionResult::success(
                    out,
                    start.elapsed().as_micros(),
                ));
            }
            Err(e) => {
                return Some(ExecutionResult::failure(
                    format!("[!] CPI-SI error: {e}"),
                    start.elapsed().as_micros(),
                ));
            }
        }
    }

    // 15. Supervised Episodic Neural Training
    if trimmed == "train" || trimmed.starts_with("train ") {
        let scroll_dir = crate::core::filetype::resolve_scroll_storage_dir();
        let learner = crate::ai::AILearner::new(&scroll_dir);
        match learner.digest_experiences() {
            Ok(summary) => {
                let mut brain = crate::ai::NeuralBrain::new(
                    &[8, 16, 4],
                    1,
                    logger.clone(),
                );
                let trainer = crate::ai::NeuralTrainer::new();
                let report = trainer.train(&mut brain, &summary.experiences);
                let weights_path =
                    std::path::PathBuf::from(
                        "storage/weights/cpisi_base.weights"
                    );
                brain.save_weights(&weights_path).ok();
                let out = format!(
                    "[√] Neural Training Complete:\n  \
                     • Episodes Digested: {}\n  \
                     • Synapses Adapted:  {}\n  \
                     • Resilience Score:  {:.1}% -> {:.1}%\n  \
                     • Weights Saved:     {:?}",
                    report.total_episodes,
                    report.synapses_adapted,
                    report.noise_resilience_before * 100.0,
                    report.noise_resilience_after * 100.0,
                    weights_path
                );
```

```
                return Some(ExecutionResult::success(
                    out,
                    start.elapsed().as_micros(),
                ));
            }
            Err(e) => {
                return Some(ExecutionResult::failure(
                    format!("[!] Training failed: {e}"),
                    start.elapsed().as_micros(),
                ));
            }
        }
    }

    // 16. Structured Systemic Noise & Degradation Simulation
    if trimmed == "noise" || trimmed.starts_with("noise ") {
        let engine = crate::ai::NoiseEngine::default();
        let ideal = &[
            crate::core::ternary::QuadState::Proceed,
            crate::core::ternary::QuadState::Proceed,
            crate::core::ternary::QuadState::Proceed,
            crate::core::ternary::QuadState::Proceed,
        ];
        let brain = crate::ai::NeuralBrain::new(
            &[4, 8, 2],
            1,
            logger.clone(),
        );
        let ladder = engine.simulate_breakdown_ladder(ideal);
        let mut out = String::from(
            "DEGRADATION LADDER (Ideal -> Breakdown):\n"
        );
        for step in &ladder {
            let noisy_out = brain.think(&step.perturbed_vector);
            let mode_str = match step.dominant_mode {
                crate::ai::DegradationMode::Ideal => "Pristine",
                crate::ai::DegradationMode::TritDecay => "Trit Decay",
                crate::ai::DegradationMode::BoundaryLeak => "Boundary Leak",
                crate::ai::DegradationMode::ThermalInversion => "Inversion",
                crate::ai::DegradationMode::FailpointTrap => "Halt Trap",
            };
            out.push_str(&format!(
                "  [{:>3.0}%] {:<13} | Fidelity: {:>5.1}% | Out: {:?}\n",
                step.stress_level * 100.0,
                mode_str,
                step.signal_fidelity * 100.0,
                noisy_out
            ));
        }
        let resilience = brain.evaluate_noise_resilience(ideal, &engine);
        out.push_str(&format!(
            "Neural Resilience Score: {:.1}%",
            resilience * 100.0
        ));
        return Some(ExecutionResult::success(
            out,
            start.elapsed().as_micros(),
        ));
    }

    if trimmed == "help" {
        let help = "OMNICODE NATIVE OPERATING SYSTEM SHELL:
ps, tasks          List scheduled tasks and active processes
tracks             Display the 3 execution channels (Kernel, Terminal, Apps)
mem, ram           Display ANSI storehouse RAM meter and allocations
mount <path.tape>  Mount a tape ribbon onto an execution track
run <path.tape>    Mount and execute a process tape to completion
step <pid>         Manually step a Tape Head forward by 1 roll
rolls <pid>        View tape rolls and the live ==> [HEAD] pointer
spawn <cmd>        Spawn a new task under the task scheduler
pause <pid>        Transition a process to 0:AWAIT (standby)
resume <pid>       Resume a process to +1:PROCEED (running)
kill <pid>         Halt and terminate a process (NULL:HALT)
tick               Advance the cooperative scheduler clock
vars, env          Display in-memory declared variables and Vessels
ai <prompt>        Deliberate with the AI Model and synthesize reels
interact, cpisi    Engage in live discourse with CPI-SI Base model
query <session>    Query an episodic memory scroll in O(1) time
```

```
  diagnose <session> Inspect trapped failpoints and immune repairs
  episodes [N]       Display the N most recent execution scrolls
  rotate [capacity]  Enforce vessel capacity bounds (Occupancy <= Capacity)
  train              Train balanced-ternary weights on episodic scrolls
  noise              Run non-random structured degradation ladder
  clear              Clear the terminal screen
  help               Display this help reference

LIVE OMNICODE STATEMENTS & ROLLS:
  Type any valid roll (e.g. `A [ 10 ]`, `42 --> Buf @ 0`, `Storehouse v-- App [ 256 ]`)
  to execute directly in persistent silicon memory!
";
        return Some(ExecutionResult::success(help.to_string(), start.elapsed().as_micros()));
    }

    // Variable assignment: let x = 42
    if trimmed.starts_with("let ") && trimmed.contains('=') {
        let parts: Vec<&str> = trimmed["let ".len()..].splitn(2, '=').collect();
        if parts.len() == 2 {
            let name = parts[0].trim().to_string();
            let val = parts[1].trim().to_string();
            variables.insert(name.clone(), val.clone());
            return Some(ExecutionResult::success(format!("Variable '{name}' bound to: {val}"),
start.elapsed().as_micros()));
        }
    }

    None
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Invariant Proofs )
// ============================================================================
// Built-in command dispatcher is decoupled from session orchestration.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/session/mod.rs RS 37 LINES 185 WORDS 1.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Terminal Interactive Session Subsystem Identity & Public Exports )
// ============================================================================
//! OmniCode Terminal: Interactive Session Subsystem Module
//!
//! Provides the interactive userspace shell, persistent variable state,
//! direct roll evaluation, and native character stream echo protocols.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**: Tables of testimony, written with the finger of God.
//! - **Proverbs 24:27 (KJV)**: Prepare thy work without, and make it fit for thyself in the field.
//! - **Proverbs 22:28 (KJV)**: Remove not the ancient landmark, which thy fathers have set.
// ============================================================================

pub mod commands;
pub mod session;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Terminal Session & Execution Models )
// ============================================================================
pub use commands::ExecutionResult;
pub use session::TerminalSession;

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Invariants & Session Proofs )
// ============================================================================
// Terminal sessions evaluate rolls and process character echo natively.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Module Closure )
// ============================================================================
// Interactive Terminal Session subsystem verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/session/session.rs RS 481 LINES 1647 WORDS 19.5 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Terminal Interactive Session State, Direct Roll Evaluator & Native Echo Engine )
// ================================================================================
//! OmniCode Terminal: Interactive Session Coordinator & Character I/O Engine
//!
//! # Architectural Scope & Purpose:
//! Coordinates the interactive userspace shell for the OmniCode platform:
//! 1. Maintains command history, variable declarations, and persistent [`Environment`] state.
//! 2. Routes shell commands through the Multi-Track [`OmniScheduler`].
//! 3. Directly evaluates live procedural rolls in memory without sub-process overhead.
//! 4. Houses native Character I/O streams and the 5-trit Radix-3 [`CharacterEchoEngine`].
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of atomic runes onto bounded physical tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types and substrates before constructing systems).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
// ================================================================================

use std::collections::HashMap;
use std::sync::{Arc, Mutex};
use std::time::Instant;

use crate::cogs::tripwire::Tripwire;
use crate::core::ternary::QuadState;
use crate::diagnostics::debugger::OmniDebugger;
use crate::diagnostics::logger::{DiagnosticLogger, FailpointType};
use crate::parser::lexer::Lexer;
use crate::parser::parser::Parser;
use crate::runtime::environment::{Environment, RuntimeValue};
use crate::runtime::evaluator::Evaluator;
use crate::terminal::scheduler::{OmniScheduler, SharedScheduler};
use crate::terminal::universal::call_response_engine::{
    Call, Response, CharacterResponse, NumberResponse, CallResponseEngine, EchoEngine,
};
use crate::terminal::universal::ports::{TerminalInputStream, TerminalOutputStream};

use super::commands::{dispatch_builtin_command, ExecutionResult};

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( TerminalSession Struct Definition & Initializers )
// ================================================================================

/// Interactive shell session maintaining persistent memory bindings,
/// scheduler access, directional I/O streams, and native character echo.
pub struct TerminalSession {
    /// Command line history.
    pub history: Vec<String>,
    /// Script-level variable bindings.
    pub variables: HashMap<String, String>,
    /// Thread-safe handle to the cooperative Multi-Track scheduler.
    pub scheduler: SharedScheduler,
    /// Persistent virtual machine runtime environment.
    pub env: Environment,
    /// Attached telemetry and error interception logger.
    pub logger: DiagnosticLogger,
    /// Delimiter boundary stack tracking debugger.
    pub debugger: OmniDebugger,
    /// Directional input stream from hardware `FROM` port (0x03F8).
    pub input_stream: TerminalInputStream,
    /// Directional output stream to hardware `INTO` port (0x000B8000).
    pub output_stream: TerminalOutputStream,
    /// Universal Call-and-Response Echo Engine.
    pub echo_engine: EchoEngine,
}
```

```
75
76  impl Default for TerminalSession {
77      fn default() -> Self {
78          let logger = DiagnosticLogger::new(false);
79          let debugger = OmniDebugger::new(logger.clone(), 10);
80          let env = Environment::new();
81          Self {
82              history: Vec::new(),
83              variables: HashMap::new(),
84              scheduler: Arc::new(Mutex::new(OmniScheduler::new())),
85              env,
86              logger,
87              debugger,
88              input_stream: TerminalInputStream::default(),
89              output_stream: TerminalOutputStream::default(),
90              echo_engine: EchoEngine,
91          }
92      }
93  }
94
95  // ============================================================================
96  // BLOCK 3: BODY BLOCK
97  // ( Execution Pipeline, Direct Roll Lowering & Native Character I/O )
98  // ============================================================================
99
100 impl TerminalSession {
101     /// Constructs a new terminal session bound to a shared multi-track scheduler.
102     pub fn new(scheduler: SharedScheduler) -> Self {
103         let logger = DiagnosticLogger::new(false);
104         let debugger = OmniDebugger::new(logger.clone(), 10);
105         let env = Environment::new();
106         Self {
107             history: Vec::new(),
108             variables: HashMap::new(),
109             scheduler,
110             env,
111             logger,
112             debugger,
113             input_stream: TerminalInputStream::default(),
114             output_stream: TerminalOutputStream::default(),
115             echo_engine: EchoEngine,
116         }
117     }
118
119     /// Dispatches a command line and returns an [`ExecutionResult`].
120     pub fn execute(&mut self, line: &str) -> ExecutionResult {
121         let trimmed = line.trim();
122         if trimmed.is_empty() {
123             return ExecutionResult::success(String::new(), 0);
124         }
125
126         self.history.push(trimmed.to_string());
127         let start = Instant::now();
128
129         // 1. Dispatch Built-in Shell Commands
130         if let Some(res) = dispatch_builtin_command(
131             trimmed,
132             &self.scheduler,
133             &self.env,
134             &mut self.variables,
135             &self.logger,
136             &self.debugger,
137             start,
138         ) {
139             for c in res.stdout.chars() {
140                 self.output_stream.push_char(c);
141             }
142             return res;
143         }
144
145         // 2. Direct In-Memory Roll Evaluation (OmniCode Native Execution)
146         if trimmed.contains("-->") || trimmed.contains("<--") || trimmed.contains("v--") || trimmed.contains("--^")
147             || trimmed.starts_with("Storehouse") || (trimmed.contains('[') && trimmed.contains(']'))
148             || (trimmed.contains('<') && trimmed.contains('>'))
149             || trimmed.starts_with("status")
150         {
151             let mut lexer = Lexer::new(trimmed, self.logger.clone());
152             if let Ok(tokens) = lexer.tokenize() {
```

```
                let mut parser = Parser::new(tokens, self.debugger.clone());
                if let Ok(prog) = parser.parse_program() {
                    let mut evaluator = Evaluator::new(self.env.clone(), self.debugger.clone());
                    match evaluator.eval(&crate::ast::nodes::ASTNode::Program(prog)) {
                        Ok(val) => {
                            self.env = evaluator.env; // Persist environment state!
                            return ExecutionResult::success(
                                format!("=> {:?} (state: +1:PROCEED)", val),
                                start.elapsed().as_micros(),
                            );
                        }
                        Err(e) => {
                            let err = Tripwire::trip(
                                &self.logger,
                                "TERMINAL_EVAL",
                                FailpointType::SyntaxAnomaly,
                                format!("Evaluation Failpoint: {e}"),
                            );
                            return ExecutionResult::failure(
                                format!("[!] {err}"),
                                start.elapsed().as_micros(),
                            );
                        }
                    }
                }
            }
        }

        // 3. Fallback: Host Subcommand Execution
        let clean_cmd = if trimmed.starts_with("omnicode ") {
            trimmed.to_string()
        } else {
            format!("omnicode {trimmed}")
        };

        let exe = std::env::current_exe().unwrap_or_else(|_| std::path::PathBuf::from("omnicode"));
        let args: Vec<&str> = clean_cmd["omnicode ".len()..].split_whitespace().collect();
        let output = std::process::Command::new(&exe)
            .args(&args)
            .output();

        match output {
            Ok(out) => {
                let stdout = String::from_utf8_lossy(&out.stdout).to_string();
                let stderr = String::from_utf8_lossy(&out.stderr).to_string();
                let combined = if stderr.is_empty() {
                    stdout
                } else if stdout.is_empty() {
                    stderr
                } else {
                    format!("{stdout}\n{stderr}")
                };
                if out.status.success() {
                    ExecutionResult::success(combined, start.elapsed().as_micros())
                } else {
                    ExecutionResult::failure(combined, start.elapsed().as_micros())
                }
            }
            Err(e) => ExecutionResult::failure(
                format!("Failed to execute CLI subcommand: {e}"),
                start.elapsed().as_micros(),
            ),
        }
    }

    // ------------------------------------------------------------------------
    // Native Character I/O & Echo Stream Methods
    // ------------------------------------------------------------------------

    /// Feeds an input character into the terminal's `FROM` port stream (0x03F8)
    /// and synchronizes it into the virtual machine environment.
    pub fn feed_input_char(&mut self, c: char) {
        self.input_stream.push_char(c);
        self.env.write_from(RuntimeValue::from_char(c));
    }

    /// Reads the next available character from the terminal's `INTO` port stream (0x000B8000).
    pub fn read_output_char(&mut self) -> Option<char> {
```

```
        self.output_stream.pop_char()
    }

    /// Flushes all pending output characters into an allocated string.
    pub fn flush_output(&mut self) -> String {
        self.output_stream.flush_to_string()
    }

    /// Processes a single character glyph through the full 5-step Character tape lifecycle,
    /// verifying Radix-3 transduction, single-cell capacity bounds, and returning the native echo.
    pub fn process_character_echo(&mut self, glyph: char) -> Result<CharacterResponse, String> {
        // Feed into FROM port
        self.feed_input_char(glyph);

        // Run full Inscription -> Transduction -> Bound Guard -> Target Projection
        let res = EchoEngine::echo_char(glyph)?;

        // Write projected character into INTO port and output stream
        self.output_stream.push_char(res.glyph);
        self.env.write_into(RuntimeValue::from_char(res.glyph));

        // Inscribe RollFrame telemetry into in-memory flight recorder
        let frame = crate::diagnostics::logger::RollFrame::new(
            res.glyph as u128,
            1,
            5,
            "TRANSDUCE",
            (0, res.glyph as u64),
            (res.glyph as u64, 0),
            res.state,
            0,
            Some(format!("Glyph '{}'", res.glyph)),
        );
        self.logger.record_roll_frame(frame);

        Ok(res)
    }

    /// Processes an entire character stream through the native Character Echo protocol,
    /// returning the verified echoed string.
    pub fn process_character_stream_echo(&mut self, stream: &str) -> Result<String, String> {
        let mut echoed = String::with_capacity(stream.len());
        for c in stream.chars() {
            let res = self.process_character_echo(c)?;
            echoed.push(res.glyph);
        }
        Ok(echoed)
    }

    /// Processes any Call payload through the universal Call-Response model.
    pub fn process_call(&mut self, call: Call) -> Result<Response, String> {
        CallResponseEngine::execute(call)
    }

    /// Processes a scalar Number through the Call-Response model.
    pub fn process_number_call(&mut self, scalar: i64) -> Result<NumberResponse, String> {
        let res = CallResponseEngine::call_number(scalar)?;
        self.env.write_into(RuntimeValue::from_number(scalar as f64));

        let frame = crate::diagnostics::logger::RollFrame::new(
            scalar.unsigned_abs() as u128,
            1,
            3,
            "TRANSDUCE",
            (0, scalar.unsigned_abs()),
            (res.packed_dual_rail, scalar.unsigned_abs()),
            QuadState::Proceed,
            0,
            Some(format!("Number {scalar}")),
        );
        self.logger.record_roll_frame(frame);

        Ok(res)
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
```

```rust
// ( Unit Test Verification Proofs & Invariants )
// =============================================================================

#[cfg(test)]
mod tests {
    use super::*;
    use crate::core::ternary::QuadState;

    #[test]
    fn test_terminal_session_builtin_commands() {
        let mut session = TerminalSession::default();
        let res_help = session.execute("help");
        assert_eq!(res_help.state, QuadState::Proceed);
        assert!(res_help.stdout.contains("OMNICODE NATIVE OPERATING SYSTEM SHELL"));

        let res_tasks = session.execute("tasks");
        assert_eq!(res_tasks.state, QuadState::Proceed);
        assert!(res_tasks.stdout.contains("kernel --daemon"));

        let res_tracks = session.execute("tracks");
        assert_eq!(res_tracks.state, QuadState::Proceed);
        assert!(res_tracks.stdout.contains("CoreDaemon"));
    }

    #[test]
    fn test_terminal_session_echo_uncommon_letters() {
        let mut session = TerminalSession::default();

        // 1. Echo uncommon uppercase letter 'Q' (ASCII 81)
        let res_q = session.execute("echo Q");
        assert_eq!(res_q.state, QuadState::Proceed);
        assert_eq!(res_q.stdout, "Q");
        assert_eq!(session.read_output_char(), Some('Q'));

        // 2. Echo uncommon letter 'Z' (ASCII 90)
        let res_z = session.execute("echo 'Z'");
        assert_eq!(res_z.state, QuadState::Proceed);
        assert_eq!(res_z.stdout, "Z");
        assert_eq!(session.read_output_char(), Some('Z'));

        // 3. Echo symbol '~' (ASCII 126)
        let res_tilde = session.execute("echo ~");
        assert_eq!(res_tilde.state, QuadState::Proceed);
        assert_eq!(res_tilde.stdout, "~");
        assert_eq!(session.read_output_char(), Some('~'));

        // 4. Echo string with mixed uncommon characters "QxZ~"
        let res_multi = session.execute("echo QxZ~");
        assert_eq!(res_multi.state, QuadState::Proceed);
        assert_eq!(res_multi.stdout, "QxZ~");
        let drained: String = std::iter::from_fn(|| session.read_output_char()).collect();
        assert_eq!(drained, "QxZ~");
    }

    #[test]
    fn test_terminal_session_run_character_tape_and_omni() {
        let mut session = TerminalSession::default();

        // 1. Run character process tape
        let res_tape = session.execute("run lexicon/01_nouns/ideas/types/character.tape");
        assert_eq!(res_tape.state, QuadState::Proceed);
        assert!(res_tape.stdout.contains("Mounted Tape"));
        assert!(res_tape.stdout.contains("Roll 1/6"));

        // 2. Run character 4-Block source reel
        let res_omni = session.execute("run lexicon/01_nouns/ideas/types/character.omni");
        assert_eq!(res_omni.state, QuadState::Proceed);
        assert!(res_omni.stdout.contains("OmniCode Source Reel Executed Successfully"));
    }

    #[test]
    fn test_terminal_session_direct_roll_evaluation() {
        let mut session = TerminalSession::default();
        let res = session.execute("roll_1 [ A = A ]");
        assert_eq!(res.state, QuadState::Proceed);
        assert!(res.stdout.contains("+1:PROCEED"));
    }

```

```
    #[test]
    fn test_terminal_session_native_character_echo() {
        let mut session = TerminalSession::default();
        let res = session.process_character_echo('K').expect("Native echo for 'K' must succeed");
        assert_eq!(res.glyph, 'K');
        assert_eq!(res.state, QuadState::Proceed);
        assert_eq!(res.cell_footprint, 1);
        assert_eq!(session.read_output_char(), Some('K'));
    }

    #[test]
    fn test_terminal_session_stream_echo() {
        let mut session = TerminalSession::default();
        let text = "OmniCode Native Terminal 2026!";
        let echoed = session.process_character_stream_echo(text).expect("Stream echo must succeed");
        assert_eq!(echoed, text);
    }

    #[test]
    fn test_terminal_exhaustive_character_echo_no_valid_character_omitted() {
        let mut session = TerminalSession::default();

        // 1. Test every standard ASCII character (0 through 127)
        // Including control characters (\0, \t, \n, \r), printable symbols, letters, and numbers
        let mut omitted_count = 0;
        let mut tested_count = 0;

        for byte in 0u8..=127u8 {
            let ch = byte as char;
            tested_count += 1;

            match session.process_character_echo(ch) {
                Ok(res) => {
                    assert_eq!(res.glyph, ch, "Identity violation for character code {byte}");
                    assert_eq!(res.state, QuadState::Proceed, "State violation for character code {byte}");
                    assert_eq!(res.cell_footprint, 1, "Cell footprint must be 1 for character code {byte}");

                    // Read from INTO port output stream
                    let read_back = session.read_output_char();
                    assert_eq!(read_back, Some(ch), "Output port character mismatch for {byte}");
                }
                Err(err) => {
                    eprintln!("Omission error for character {byte}: {err}");
                    omitted_count += 1;
                }
            }
        }

        assert_eq!(omitted_count, 0, "No valid ASCII character should be omitted");
        assert_eq!(tested_count, 128, "All 128 standard ASCII characters must be tested");

        // 2. Test extended single-cell character capacity up to 242 (3^5 = 243 discrete values)
        for byte in 128u8..=242u8 {
            let ch = byte as char;
            let res = session.process_character_echo(ch)
                .unwrap_or_else(|e| panic!("Failed echo for extended character {byte}: {e}"));
            assert_eq!(res.glyph, ch);
            assert_eq!(session.read_output_char(), Some(ch));
        }

        // 3. Test comprehensive printable ASCII stream
        let all_printable: String = (32u8..=126u8).map(|b| b as char).collect();
        let stream_echoed = session.process_character_stream_echo(&all_printable)
            .expect("Stream echo for all printable characters must succeed");
        assert_eq!(stream_echoed, all_printable, "Every single printable character must match identically without
omission");
    }

    #[test]
    fn test_terminal_session_call_response_number() {
        let mut session = TerminalSession::default();

        // 1. Process number call for unities and partition
        let r0 = session.process_number_call(0).expect("Call 0");
        assert_eq!(r0.scalar, 0);
        assert!(r0.equilibrium_proved);

        let r1 = session.process_number_call(1).expect("Call 1");
```

```
        assert_eq!(r1.scalar, 1);

        let r_neg1 = session.process_number_call(-1).expect("Call -1");
        assert_eq!(r_neg1.scalar, -1);

        let r4096 = session.process_number_call(4096).expect("Call 4096");
        assert_eq!(r4096.scalar, 4096);
        assert_eq!(r4096.state, QuadState::Proceed);

        // 2. Process universal call
        let u_call = session.process_call(Call::Number(65536)).expect("Universal call");
        match u_call {
            Response::Number(n) => assert_eq!(n.scalar, 65536),
            _ => panic!("Expected Number response"),
        }
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/studio/hud.rs RS 173 LINES 740 WORDS 8.4 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( OmniStudio: Cinematic Projector, Set Props & Spindle HUD )
// ============================================================================
//! OmniCode Terminal: Cinematic Projector & Memory HUD
//!
//! # Architectural Scope & Purpose:
//! Provides a real-time visual projection HUD of the 4-directional Memory Reel,
//! showing active tracks, scenes, rolls, and set props (64-bit / 32-trit cells):
//! 1. **Projector Head:** Active Reel, Channel Track, Transport Status (`PLAY`, `PAUSE`, `REWIND`, `STOP`).
//! 2. **Spindle Depth Meter:** Current Scene nesting level (`v--` depth).
//! 3. **The Script (Active Roll):** Current instruction line rolling through the gate.
//! 4. **Set Props (Memory Grid):** Bounded cells holding physical 64-bit words.
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of physical data into visual display volumes).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic projector frames before launching graphical studios).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of physical memory cell addresses and clapper cue landmarks).
// ============================================================================

use crate::core::mmio::VgaBuffer;
use crate::core::reel::MemoryReel;
use crate::core::tape::Tape;
use crate::core::ternary::TransportAction;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( OmniStudio Struct Definition and Configuration )
// ============================================================================

/// Cinematic Projector rendering interactive terminal HUD frames of memory reel execution.
pub struct OmniStudio {
    /// Active 4-directional memory reel.
    pub reel: MemoryReel,
    /// Canonical execution track display label.
    pub active_track: &'static str,
    /// Hardware MMIO VGA text buffer emulator.
    pub vga: VgaBuffer,
}

impl OmniStudio {
    /// Creates a new Studio Projector initialized with a named memory reel.
    pub fn new(reel_name: impl Into<String>, capacity: usize) -> Self {
        Self {
            reel: MemoryReel::new(reel_name, capacity),
            active_track: "TRACK 2 [APP]",
            vga: VgaBuffer::new(),
        }
    }

    /// Sets the active channel track display label.
    pub fn set_track(&mut self, track: &'static str) {
        self.active_track = track;
    }
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Projector Frame Rendering & HUD Formatting )
// ============================================================================

impl OmniStudio {
    /// Renders a complete cinematic projector HUD frame for a tape and its active roll.
    pub fn render_frame(&self, tape: &Tape, roll_idx: usize, message: &str) -> String {
        let mut out = String::new();
        let transport_badge = match self.reel.transport {
```

```
            TransportAction::Play => "\x1b[1;32m[▶ PLAY]\x1b[0m",
            TransportAction::Pause => "\x1b[1;33m[⏸ PAUSE]\x1b[0m",
            TransportAction::Rewind => "\x1b[1;35m[⏮ REWIND]\x1b[0m",
            TransportAction::Stop => "\x1b[1;31m[■ STOP]\x1b[0m",
        };

        let scene = self.reel.active_scene();
        let landmark_str = scene.landmark.as_deref().unwrap_or("none");


out.push_str("\x1b[1;36m╔══════════════════════════════════════════════════════════════════════════════╗\x1b[0m\n");
        out.push_str(&format!(
            "\x1b[1;36m║\x1b[0m  \x1b[1mOMNICODE CINEMA STUDIO\x1b[0m | REEL: \x1b[1;33m[{}]\x1b[0m | {}
\x1b[1;36m║\x1b[0m\n",
            self.reel.name, transport_badge
        ));
        out.push_str(&format!(
            "\x1b[1;36m║\x1b[0m  CHANNEL: {:<18} | SPINDLE DEPTH: {} | SCENE: <{}>  \x1b[1;36m║\x1b[0m\n",
            self.active_track, scene.depth, scene.name
        ));
        out.push_str(&format!(
            "\x1b[1;36m║\x1b[0m  CLAPPER CUE: <{:<16}> | HEAD POSITION: @0x{:04X}               \x1b[1;36m║\x1b[0m\n",
            landmark_str, scene.head_pos
        ));

out.push_str("\x1b[1;36m╠══════════════════════════════════════════════════════════════════════════════╣\x1b[0m\n");

        // Script Gate: Active Roll
        let roll_count = tape.roll_count();
        let roll_text = tape.rolls.get(roll_idx).map(|r| r.text.as_str()).unwrap_or("EOF");
        out.push_str(&format!(
            "\x1b[1;36m║\x1b[0m  \x1b[1;32mSCRIPT GATE [Roll {}/{}]:\x1b[0m {:<48} \x1b[1;36m║\x1b[0m\n",
            roll_idx + 1, roll_count, roll_text
        ));
        out.push_str(&format!(
            "\x1b[1;36m║\x1b[0m  {:<76} \x1b[1;36m║\x1b[0m\n",
            message
        ));

out.push_str("\x1b[1;36m╠══════════════════════════════════════════════════════════════════════════════╣\x1b[0m\n");

        // Set Props (Active Memory Cells)
        out.push_str("\x1b[1;36m║\x1b[0m  \x1b[1;33mSET PROPS (MEMORY CELL GRID):\x1b[0m
\x1b[1;36m║\x1b[0m\n");
        let display_cells = 4.min(scene.capacity);
        for i in 0..display_cells {
            if let Some(word) = scene.read(i) {
                let focus_ptr = if i == scene.head_pos { "▶" } else { " " };
                out.push_str(&format!(
                    "\x1b[1;36m║\x1b[0m   {} [0x{:04X}]: 0x{:016X} | Val: {:<5} | State: {:<7} \x1b[1;36m║\x1b[0m\n",
                    focus_ptr, i, word.raw, word.payload().to_i64(), word.state().macro_op()
                ));
            }
        }


out.push_str("\x1b[1;36m╚══════════════════════════════════════════════════════════════════════════════╝\x1b[0m\n");
        if self.vga.cursor_col > 0 || self.vga.cursor_row > 0 {
            out.push_str(&self.vga.render_screen(4));
        }
        out
    }

    /// Projects an entire tape sequentially with terminal cinematic frames.
    pub fn project_tape(&mut self, tape: &Tape) {
        println!("\x1b[1;32m▶ Mounting & Projecting Reel [{}] on {}\x1b[0m\n", self.reel.name, self.active_track);
        for (idx, roll) in tape.rolls.iter().enumerate() {
            let msg = self.step_roll(&roll.text);
            let frame = self.render_frame(tape, idx, &msg);
            print!("{frame}");
        }
        println!("\x1b[1;32m✓ Projection Complete: Tape sealed in {}\x1b[0m\n", tape.execution_state.macro_op());
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests )
```

```
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;
    use crate::diagnostics::logger::DiagnosticLogger;

    #[test]
    fn test_studio_render_frame() {
        let logger = DiagnosticLogger::new(false);
        let tape = Tape::from_source(
            r#"
            [Tape.TestProjection] : WHO {Kernel} WHAT {Test} --> DRIVE {Cinema}
            roll_1 [ 42 --> Cell_0 @ 0 ]
            roll_2 [ commit_status [ STOP ] ]
            "#,
            logger,
        ).expect("Parse tape");

        let studio = OmniStudio::new("TestReel", 16);
        let frame = studio.render_frame(&tape, 0, "Test kinematically advancing");
        assert!(frame.contains("OMNICODE CINEMA STUDIO"));
        assert!(frame.contains("TestReel"));
        assert!(frame.contains("SET PROPS"));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/studio/kinematics.rs RS 104 LINES 456 WORDS 4.9 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Cinematic Reel Kinematics & Transport Instructions )
// ================================================================================
//! OmniCode Terminal: Cinematic Reel Kinematics
//!
//! # Architectural Scope & Purpose:
//! Evaluates procedural roll statements against the 4-directional [`MemoryReel`]:
//! - Transport Actions: `STOP`, `HALT`, `PAUSE`, `PLAY`.
//! - Spatial Spindle Kinematics: Sinking in (`v--`), Popping out (`^--`), Pulling back (`<--`).
//! - Hardware MMIO Video Projection: Screen / VGA writes at `0x000B8000`.
//! - Inscribing words forward into the reel (`-->`).
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**: Tables of testimony, written with the finger of God.
//! - **Proverbs 24:27 (KJV)**: Prepare thy work without, and make it fit for thyself in the field.
//! - **Proverbs 22:28 (KJV)**: Remove not the ancient landmark, which thy fathers have set.
// ================================================================================

use crate::core::mmio::VgaColor;
use crate::core::word::Word64;

use super::hud::OmniStudio;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Kinematic Step Methods on OmniStudio )
// ================================================================================

impl OmniStudio {
    /// Interprets a single tape roll instruction against the memory reel.
    pub fn step_roll(&mut self, roll_text: &str) -> String {
        // ================================================================================
        // BLOCK 3: BODY BLOCK
        // ( Motion Evaluation & Hardware MMIO Dispatch )
        // ================================================================================
        if roll_text.contains("STOP") || roll_text.contains("HALT") {
            self.reel.stop();
            return "Kinematics: Reel stopped and transport sealed (■ STOP)".to_string();
        }
        if roll_text.contains("PAUSE") {
            self.reel.pause();
            return "Kinematics: Track paused waiting on cue (⏸ PAUSE)".to_string();
        }
        if roll_text.contains("v--") {
            let scene_name = if let Some(pos) = roll_text.find("v--") {
                roll_text.get(pos + 3..).unwrap_or("").split_whitespace().next().unwrap_or("SubScene")
            } else {
                "SubScene"
            };
            self.reel.sink_in(scene_name, 16, None);
            return format!("Kinematics: Sunk into sub-scene <{}> (v-- Spindle Depth {})", scene_name, self.reel.depth());
        }
        if roll_text.contains("^--") {
            let _ = self.reel.pop_out();
            return format!("Kinematics: Popped out to parent scene (^-- Spindle Depth {})", self.reel.depth());
        }
        if roll_text.contains("<--") {
            self.reel.pull_back();
            return "Kinematics: Pulled back track head (<--)".to_string();
        }
        if roll_text.contains("Screen") || roll_text.contains("VGA") || roll_text.contains("CONSOLE") ||
roll_text.contains("0x000B8000") {
            let extracted = if let Some(first_quote) = roll_text.find('\'') {
                if let Some(second_quote) = roll_text.get(first_quote + 1..).and_then(|s| s.find('\'')) {
                    roll_text.get(first_quote + 1..first_quote + 1 + second_quote)
                } else {
                    None
                }
            } else if let Some(first_quote) = roll_text.find('"') {
                if let Some(second_quote) = roll_text.get(first_quote + 1..).and_then(|s| s.find('"')) {
                    roll_text.get(first_quote + 1..first_quote + 1 + second_quote)
                } else {
                    None
```

```
                }
            } else {
                None
            };

            if let Some(screen_msg) = extracted {
                self.vga.write_str(screen_msg, VgaColor::LightGreen, VgaColor::Black);
                self.vga.new_line();
                return format!("Hardware MMIO: Wrote '{screen_msg}' to Bare-Metal Video Buffer @ 0x000B8000");
            }
        }
        if roll_text.contains("-->") {
            let val = roll_text
                .split_whitespace()
                .find_map(|s| s.parse::<i64>().ok())
                .unwrap_or(1);
            let word = Word64::from_signed_int(val);
            let _ = self.reel.push_forward(word);
            return format!("Kinematics: Inscribed word ({val}) and pushed forward (-->)");
        }
        self.reel.play();
        "Kinematics: Tape head advancing smoothly (▶ PLAY)".to_string()
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Kinematics Subsystem Verification )
// ============================================================================
// Reel kinematics layer verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/studio/mod.rs RS 36 LINES 186 WORDS 1.7 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Terminal Studio Subsystem Identity & Public Exports )
// ============================================================================
//! OmniCode Terminal: Cinema Studio Subsystem Module
//!
//! Provides the real-time visual projection HUD of the 4-directional Memory Reel,
//! showing active tracks, scenes, rolls, and set props (64-bit / 32-trit cells).
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**: Tables of testimony, written with the finger of God.
//! - **Proverbs 24:27 (KJV)**: Prepare thy work without, and make it fit for thyself in the field.
//! - **Proverbs 22:28 (KJV)**: Remove not the ancient landmark, which thy fathers have set.
// ============================================================================

pub mod hud;
pub mod kinematics;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Cinema Studio )
// ============================================================================
pub use hud::OmniStudio;

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Invariants & Cinema Studio Proofs )
// ============================================================================
// Cinema Studio decouples visual ANSI HUD rendering from memory reel kinematics.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Module Closure )
// ============================================================================
// Cinema Studio subsystem verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/universal/mod.rs RS 54 LINES 197 WORDS 2.0 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Terminal Universal Subsystem Identity & Public Exports )
// ============================================================================
//! OmniCode Terminal: Universal Subsystem Module
//!
//! Provides fundamental hardware MMIO ports (`0x03F8`, `0x000B8000`),
//! directional I/O stream buffers, and the universal Call-Response Engine.
//!
//! # Scripture Witness:
//! - **Job 14:15 (KJV)**: "Thou shalt call, and I will answer thee."
//! - **Exodus 31:18 (KJV)**: Tables of testimony, written with the finger of God.
//! - **Proverbs 24:27 (KJV)**: Prepare thy work without, and make it fit for thyself.
// ============================================================================

pub mod ports;
pub mod call_response_engine;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations for Universal Terminal Substrates )
// ============================================================================
pub use ports::{
    UART_COM1_INPUT_PORT,
    VGA_TEXT_OUTPUT_PORT,
    DEFAULT_TERMINAL_BUFFER_CAPACITY,
    TerminalInputStream,
    TerminalOutputStream,
};

pub use call_response_engine::{
    Call,
    Response,
    CharacterResponse,
    NumberResponse,
    StreamResponse,
    CallResponseEngine,
    EchoEngine,
    EchoResult,
};

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Universal Invariants & Subsystem Proofs )
// ============================================================================
// Hardware MMIO ports and the Call-Response Engine are decoupled from
// interactive session shells and process dispatchers.

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification & Module Closure )
// ============================================================================
// Universal Terminal Subsystem verified and closed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/universal/ports.rs RS 215 LINES 844 WORDS 7.3 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Terminal Hardware MMIO Ports, Directional Streams & Invariant Constants )
// ================================================================================
//! OmniCode Terminal: Hardware MMIO Ports & Directional Stream Substrate
//!
//! # Architectural Scope & Purpose:
//! Defines the physical silicon MMIO port addresses and ring buffer streams
//! connecting the host hardware environment to the OmniCode Virtual Machine:
//! - `FROM ::@ 0x03F8`: COM1 UART Serial Input port (Host Keyboard / Stdin).
//! - `INTO ::@ 0x000B8000`: Video Text Buffer / Console Output port (Host Screen / Stdout).
//! - Directional FIFO streaming containers ([`TerminalInputStream`], [`TerminalOutputStream`]).
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of physical data across bounded hardware channels).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic hardware port substrates before constructing user interfaces).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical MMIO addresses: UART 0x03F8 and VGA 0x000B8000).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **MMIO Port Invariance**: Explicit mapping of physical hardware addresses guarantees
//!    isomorphic behavior whether executing on the Linux host CLI, inside QEMU bare-metal,
//!    or via the local Web GUI server.
// ================================================================================

use std::collections::VecDeque;

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Hardware Port Constants & Stream Struct Definitions )
// ================================================================================

/// Hardware MMIO Address for COM1 UART Serial Input (`FROM ::@ 0x03F8`).
pub const UART_COM1_INPUT_PORT: usize = 0x03F8;

/// Hardware MMIO Address for Video Graphics Array Text Buffer (`INTO ::@ 0x000B8000`).
pub const VGA_TEXT_OUTPUT_PORT: usize = 0x000B8000;

/// Default ring buffer capacity for terminal stream queues (1,024 characters).
pub const DEFAULT_TERMINAL_BUFFER_CAPACITY: usize = 1024;

/// Directional FIFO input stream connected to the hardware `FROM` port (`0x03F8`).
#[derive(Debug, Clone)]
pub struct TerminalInputStream {
    buffer: VecDeque<char>,
    max_capacity: usize,
}

/// Directional FIFO output stream connected to the hardware `INTO` port (`0x000B8000`).
#[derive(Debug, Clone)]
pub struct TerminalOutputStream {
    buffer: VecDeque<char>,
    max_capacity: usize,
}

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Directional Stream Methods & Buffer Operations )
// ================================================================================

impl Default for TerminalInputStream {
    fn default() -> Self {
        Self::new(DEFAULT_TERMINAL_BUFFER_CAPACITY)
    }
}

impl TerminalInputStream {
```

```rust
    /// Creates a new directional input stream with the designated buffer capacity.
    pub fn new(capacity: usize) -> Self {
        Self {
            buffer: VecDeque::with_capacity(capacity),
            max_capacity: capacity,
        }
    }

    /// Pushes a single character into the input buffer (simulating a hardware UART arrival).
    pub fn push_char(&mut self, c: char) {
        if self.buffer.len() >= self.max_capacity {
            self.buffer.pop_front();
        }
        self.buffer.push_back(c);
    }

    /// Pushes an entire string slice into the input buffer.
    pub fn push_str(&mut self, s: &str) {
        for c in s.chars() {
            self.push_char(c);
        }
    }

    /// Pops the next available character from the input queue.
    pub fn pop_char(&mut self) -> Option<char> {
        self.buffer.pop_front()
    }

    /// Returns `true` if the input buffer has no pending characters.
    pub fn is_empty(&self) -> bool {
        self.buffer.is_empty()
    }

    /// Returns the number of characters currently buffered.
    pub fn len(&self) -> usize {
        self.buffer.len()
    }

    /// Clears all pending characters from the stream.
    pub fn clear(&mut self) {
        self.buffer.clear();
    }
}

impl Default for TerminalOutputStream {
    fn default() -> Self {
        Self::new(DEFAULT_TERMINAL_BUFFER_CAPACITY)
    }
}

impl TerminalOutputStream {
    /// Creates a new directional output stream with the designated buffer capacity.
    pub fn new(capacity: usize) -> Self {
        Self {
            buffer: VecDeque::with_capacity(capacity),
            max_capacity: capacity,
        }
    }

    /// Pushes a projected character into the output buffer (simulating a VGA text write).
    pub fn push_char(&mut self, c: char) {
        if self.buffer.len() >= self.max_capacity {
            self.buffer.pop_front();
        }
        self.buffer.push_back(c);
    }

    /// Pushes an entire string slice into the output buffer.
    pub fn push_str(&mut self, s: &str) {
        for c in s.chars() {
            self.push_char(c);
        }
    }

    /// Pops the next projected character from the output queue.
    pub fn pop_char(&mut self) -> Option<char> {
        self.buffer.pop_front()
    }
```

```rust

    /// Flushes all pending output characters into a single allocated String.
    pub fn flush_to_string(&mut self) -> String {
        let s: String = self.buffer.iter().collect();
        self.buffer.clear();
        s
    }

    /// Returns `true` if the output buffer has no pending characters.
    pub fn is_empty(&self) -> bool {
        self.buffer.is_empty()
    }

    /// Returns the number of characters currently buffered.
    pub fn len(&self) -> usize {
        self.buffer.len()
    }

    /// Clears all pending characters from the stream.
    pub fn clear(&mut self) {
        self.buffer.clear();
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Test Verification Proofs & Stream Invariants )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_hardware_mmio_port_constants() {
        assert_eq!(UART_COM1_INPUT_PORT, 0x03F8);
        assert_eq!(VGA_TEXT_OUTPUT_PORT, 0x000B8000);
    }

    #[test]
    fn test_directional_input_stream_lifecycle() {
        let mut input = TerminalInputStream::new(16);
        assert!(input.is_empty());
        input.push_str("GLYPH");
        assert_eq!(input.len(), 5);
        assert_eq!(input.pop_char(), Some('G'));
        assert_eq!(input.pop_char(), Some('L'));
        assert_eq!(input.len(), 3);
        input.clear();
        assert!(input.is_empty());
    }

    #[test]
    fn test_directional_output_stream_flush() {
        let mut output = TerminalOutputStream::new(16);
        output.push_str("ECHO_OK");
        assert_eq!(output.len(), 7);
        let flushed = output.flush_to_string();
        assert_eq!(flushed, "ECHO_OK");
        assert!(output.is_empty());
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/universal/call_response_engine/call_response.rs

RS | 443 LINES | 1816 WORDS | 17.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal Call-Response Engine: Operator <-> Machine Bidirectional Ribbon )
// ============================================================================
//! OmniCode Terminal: Universal Call & Response Protocol Engine
//!
//! # Architectural Scope & Purpose:
//! Implements the universal **Call & Response** mathematical model of the
//! OmniCode framework:
//!
//! - **The Call (Caller / Sender Input):**
//!   Rank 5 outside-in asymmetric imposition into the silicon/virtual container:
//!   `{ Call ] --> INSCRIBE [ Container ] = [ Entity' ]`.
//! - **The Response (Via Caller / Sender Output):**
//!   Rank 4 inside-out emergence projecting verified state back to the sender:
//!   `[ Entity' ] --> PROJECT [ Response ] = [ Response' ]`.
//!
//! # Reversibility & AI Cognition:
//! Because OmniCode is designed for creating an AI model (where `.omni` and `.tape`
//! are the compiled and interpreted forms of the OmniCode framework rather than
//! passive data types), the Operator and the Machine (the computer) are symmetric
//! peers taking turns as Caller and Sender:
//! - **Operator Calls -> Machine Responds:** User/Agent commands, scalar inputs, glyphs.
//! - **Machine Calls -> Operator Responds:** Machine interrupts, hardware telemetry,
//!   predictive inference requests, and future networking packets across distributed nodes.
//!
//! An "echo" is simply the special case of Call-Response that repeats what was called
//! for after proving invariant bounds and ALU equilibrium.
//!
//! # Scripture Witness:
//! - **Job 14:15 (KJV)**:
//!   "Thou shalt call, and I will answer thee: thou wilt have a desire to the
//!    work of thine hands."
//!   (The primordial covenant of Call and Response between Creator and Creation).
//! - **Isaiah 65:24 (KJV)**:
//!   "And it shall come to pass, that before they call, I will answer;
//!    and while they are yet speaking, I will hear."
//!   (Zero-latency predictive Call-Response in equilibrium).
// ============================================================================

use crate::core::cell::{Cell, Trit};
use crate::core::ternary::QuadState;
use crate::core::word::{PackMode, Word32Trit};

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Types, Enums & Status Containers )
// ============================================================================

/// A Call payload transmitted by the Caller / Sender (Operator or Machine).
#[derive(Debug, Clone, PartialEq)]
pub enum Call {
    /// Inscription of an atomic symbolic rune / glyph (1 Cell capacity).
    Character(char),
    /// Inscription of a scalar magnitude / quantity (1 Word capacity).
    Number(i64),
    /// Inscription of a composite stream of characters (Text ribbon).
    Stream(String),
    /// Direct injection of a 64-bit dual-rail polar bit-plane register.
    DualRail(u64),
}

/// Result of a verified Character Call-Response turn.
#[derive(Debug, Clone, PartialEq, Eq)]
pub struct CharacterResponse {
    /// Echoed / verified character glyph.
    pub glyph: char,
    /// 5 balanced trits representing the character in virtual cell memory.
    pub trits: [i8; 5],
    /// Balanced ternary Quad-State (+1:PROCEED).
    pub state: QuadState,
    /// Verified cell capacity footprint (always 1 Cell).
    pub cell_footprint: usize,
```

```rust
}

/// Result of a verified Number Call-Response turn.
#[derive(Debug, Clone, PartialEq, Eq)]
pub struct NumberResponse {
    /// Outside-in scalar integer quantity.
    pub scalar: i64,
    /// 32 balanced trits representing the quantity in virtual word memory.
    pub trits: [i8; 32],
    /// Native 64-bit dual-rail polar bit-plane register (00=0, 01=+1, 10=-1, 11=Trap).
    pub packed_dual_rail: u64,
    /// Canonical dense 2-2-2-2 packing of least significant 4 trits (1 byte).
    pub byte_pack_2222: u8,
    /// Kinematic 2-1-2-1-2 resting equilibrium packing of least significant 3 trits (1 byte).
    pub byte_pack_21212: u8,
    /// Proof of ALU Zero-Sum Equilibrium Law: (+1) + (-1) <=> 0.
    pub equilibrium_proved: bool,
    /// Proof of SIMD rail-swap negation involution: -(-x) == x.
    pub rail_involution_proved: bool,
    /// Balanced ternary Quad-State (+1:PROCEED).
    pub state: QuadState,
    /// Verified word capacity footprint (always 1 Word).
    pub word_footprint: usize,
}

/// Result of a verified Stream Call-Response turn.
#[derive(Debug, Clone, PartialEq, Eq)]
pub struct StreamResponse {
    /// Echoed / verified text stream.
    pub echoed: String,
    /// Alias for echoed stream text.
    pub text: String,
    /// Total count of atomic character cells verified.
    pub cell_count: usize,
    /// Balanced ternary Quad-State (+1:PROCEED).
    pub state: QuadState,
}

/// Universal Response delivered to the Caller / Sender via the output channel.
#[derive(Debug, Clone, PartialEq)]
pub enum Response {
    /// Verified Character response.
    Character(CharacterResponse),
    /// Verified Number response.
    Number(NumberResponse),
    /// Verified Stream response.
    Stream(StreamResponse),
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Universal Call-Response Engine Implementation )
// ============================================================================

/// The Universal Call & Response Engine.
#[derive(Debug, Clone, Default)]
pub struct CallResponseEngine;

impl CallResponseEngine {
    /// Executes any Call, returning the corresponding verified Response.
    pub fn execute(call: Call) -> Result<Response, String> {
        match call {
            Call::Character(c) => Self::call_char(c).map(Response::Character),
            Call::Number(n) => Self::call_number(n).map(Response::Number),
            Call::Stream(s) => Self::call_stream(&s).map(Response::Stream),
            Call::DualRail(r) => Self::call_dual_rail(r).map(Response::Number),
        }
    }

    /// Executes the full Call-Response lifecycle for an atomic Character glyph:
    /// 1. Ingestion: Reads glyph payload from Caller.
    /// 2. Inscription: Allocates single 1-Cell container.
    /// 3. Transduction: Bijectively converts 8-bit byte <=> 5 balanced trits.
    /// 4. Guard: Checks identity, single-cell capacity, and ASCII boundary.
    /// 5. Response: Returns verified CharacterResponse.
    pub fn call_char(glyph: char) -> Result<CharacterResponse, String> {
        let byte = if (glyph as u32) <= 242 {
            glyph as u8
```

```
        } else {
            return Err(format!(
                "Character '{}' (U+{:04X}) exceeds single-cell capacity of 242 values",
                glyph, glyph as u32
            ));
        };

        let cell = Cell::from_natural(byte)?;
        let mut trits = [0i8; 5];
        for (i, t) in cell.trits.iter().enumerate() {
            trits[i] = t.as_i8();
        }

        let mut cell_trits = [Trit::Zero; 5];
        for (i, &t) in trits.iter().enumerate() {
            cell_trits[i] = Trit::from_i8(t)?;
        }
        let verified_cell = Cell::new(cell_trits, QuadState::Proceed);
        let reconstructed_byte = verified_cell
            .to_natural()
            .ok_or_else(|| "Failed to decode natural byte from cell".to_string())?;

        if reconstructed_byte != byte {
            return Err(format!(
                "Transduction anomaly: byte {byte} != reconstructed {reconstructed_byte}"
            ));
        }

        let reconstructed_char = reconstructed_byte as char;
        if reconstructed_char != glyph {
            return Err(format!(
                "Identity violation: glyph '{glyph}' != reconstructed '{reconstructed_char}'"
            ));
        }

        Ok(CharacterResponse {
            glyph: reconstructed_char,
            trits,
            state: QuadState::Proceed,
            cell_footprint: 1,
        })
    }

    /// Executes the full Call-Response lifecycle for an atomic Number scalar:
    /// 1. Ingestion: Captures scalar quantity from Caller.
    /// 2. Inscription: Allocates 1-Word memory container.
    /// 3. Transduction: Bijectively converts 64-bit integer <=> 32 balanced trits.
    /// 4. Polar Rail Packing: Maps 32 trits into 64-bit dual-rail polar planes.
    /// 5. Collision Guard: Ensures no `11` collision traps exist.
    /// 6. Equilibrium Proof: Proves (+1) + (-1) <=> 0 and SIMD rail-swap involution.
    /// 7. Response: Returns verified NumberResponse.
    pub fn call_number(scalar: i64) -> Result<NumberResponse, String> {
        // Step 1 & 2: Inscribe into 32-trit Word
        let word = Word32Trit::from_i64(scalar);

        // Step 3: Bijective round-trip validation
        let reconstructed_scalar = word.to_i64();
        if reconstructed_scalar != scalar {
            return Err(format!(
                "Number transduction overflow: input {scalar} != reconstructed {reconstructed_scalar}"
            ));
        }

        // Step 4: Dual-Rail polar bit-plane packing
        let packed_dual_rail = word.pack_dual_rail();

        // Step 5: Collision trap guard
        if Word32Trit::has_null_collision(packed_dual_rail) {
            return Err(format!(
                "Dual-rail collision trap: simultaneous activation on word for scalar {scalar}"
            ));
        }

        let unpacked_word = Word32Trit::unpack_dual_rail(packed_dual_rail)?;
        if unpacked_word != word {
            return Err(format!(
                "Dual-rail unpack parity mismatch on scalar {scalar}"
            ));
```

```
        }

        // Step 6: Zero-sum equilibrium proof (+1) + (-1) == 0
        let unity_pos = Word32Trit::from_i64(1);
        let unity_neg = Word32Trit::from_i64(-1);
        let (zero_sum, carry) = unity_pos.add(&unity_neg);
        let equilibrium_proved = (zero_sum.to_i64() == 0) && (carry == 0);

        // Step 7: SIMD rail-swap negation involution proof: -(-x) == x
        let negated = Word32Trit::simd_rail_swap_negate(packed_dual_rail);
        let double_negated = Word32Trit::simd_rail_swap_negate(negated);
        let rail_involution_proved = double_negated == packed_dual_rail;

        if !equilibrium_proved || !rail_involution_proved {
            return Err("ALU Zero-Sum Equilibrium or Rail-Swap Involution violated".to_string());
        }

        // Step 8: Dynamic kinematic byte topologies (least significant trits)
        let byte_pack_2222 = Word32Trit::pack_byte(&word.trits, PackMode::Dense2222);
        let byte_pack_21212 = Word32Trit::pack_byte(&word.trits, PackMode::Kinematic21212);

        Ok(NumberResponse {
            scalar,
            trits: word.trits,
            packed_dual_rail,
            byte_pack_2222,
            byte_pack_21212,
            equilibrium_proved,
            rail_involution_proved,
            state: QuadState::Proceed,
            word_footprint: 1,
        })
    }

    /// Executes Call-Response on a raw 64-bit dual-rail register word.
    pub fn call_dual_rail(packed: u64) -> Result<NumberResponse, String> {
        if Word32Trit::has_null_collision(packed) {
            return Err("Dual-rail collision trap detected in input register (code 11)".to_string());
        }
        let word = Word32Trit::unpack_dual_rail(packed)?;
        Self::call_number(word.to_i64())
    }

    /// Executes Call-Response across an entire text stream.
    pub fn call_stream(input: &str) -> Result<StreamResponse, String> {
        let mut echoed = String::with_capacity(input.len());
        let mut cell_count = 0;
        for c in input.chars() {
            let res = Self::call_char(c)?;
            echoed.push(res.glyph);
            cell_count += 1;
        }
        Ok(StreamResponse {
            echoed: echoed.clone(),
            text: echoed,
            cell_count,
            state: QuadState::Proceed,
        })
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Comprehensive Exhaustive Unit Tests: Character, Number Range & Reversibility )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_call_response_character_standard_ascii() {
        for byte in 0u8..=127u8 {
            let ch = byte as char;
            let resp = CallResponseEngine::call_char(ch)
                .unwrap_or_else(|e| panic!("Failed call_char for ASCII {byte}: {e}"));
            assert_eq!(resp.glyph, ch);
            assert_eq!(resp.state, QuadState::Proceed);
```

```
            assert_eq!(resp.cell_footprint, 1);
        }
    }

    #[test]
    fn test_call_response_number_zero_and_unities() {
        let unities = [-1i64, 0, 1];
        for &u in &unities {
            let resp = CallResponseEngine::call_number(u).expect("Unity must succeed");
            assert_eq!(resp.scalar, u);
            assert_eq!(resp.state, QuadState::Proceed);
            assert!(resp.equilibrium_proved);
            assert!(resp.rail_involution_proved);
            assert_eq!(resp.word_footprint, 1);
        }
    }

    #[test]
    fn test_call_response_number_byte_range() {
        // Exhaustively verify the entire shared 8-bit byte space (-128 through +127)
        for val in -128i64..=127i64 {
            let resp = CallResponseEngine::call_number(val)
                .unwrap_or_else(|e| panic!("Failed call_number for byte value {val}: {e}"));
            assert_eq!(resp.scalar, val);
            assert_eq!(resp.state, QuadState::Proceed);
            assert!(resp.equilibrium_proved);
            assert!(resp.rail_involution_proved);
        }
    }

    #[test]
    fn test_call_response_number_single_cell_trit_range() {
        // Single cell balanced ternary range: 3^5 = 243 values (-121 through +121)
        for val in -121i64..=121i64 {
            let resp = CallResponseEngine::call_number(val)
                .unwrap_or_else(|e| panic!("Failed call_number for 5-trit cell value {val}: {e}"));
            assert_eq!(resp.scalar, val);
        }
    }

    #[test]
    fn test_call_response_number_powers_of_3() {
        // Test powers of 3 from 3^0 up to 3^31 and negative powers
        let mut p: i64 = 1;
        for exponent in 0..=31 {
            let resp_pos = CallResponseEngine::call_number(p)
                .unwrap_or_else(|e| panic!("Failed call_number for 3^{exponent} = {p}: {e}"));
            assert_eq!(resp_pos.scalar, p);

            let resp_neg = CallResponseEngine::call_number(-p)
                .unwrap_or_else(|e| panic!("Failed call_number for -(3^{exponent}) = -{p}: {e}"));
            assert_eq!(resp_neg.scalar, -p);

            if exponent < 31 {
                p *= 3;
            }
        }
    }

    #[test]
    fn test_call_response_number_powers_of_2() {
        // Test boundary powers of 2 fitting within 32 balanced trits (max (3^32-1)/2 ~= 9.26e14, so 2^49)
        for bit in 0..=49 {
            let v = 1i64 << bit;
            let resp_pos = CallResponseEngine::call_number(v)
                .unwrap_or_else(|e| panic!("Failed call_number for 2^{bit} = {v}: {e}"));
            assert_eq!(resp_pos.scalar, v);

            let resp_neg = CallResponseEngine::call_number(-v)
                .unwrap_or_else(|e| panic!("Failed call_number for -(2^{bit}) = -{v}: {e}"));
            assert_eq!(resp_neg.scalar, -v);
        }

        // Verify that 2^50 exceeds 32-trit single-word capacity and returns an error
        let v50 = 1i64 << 50;
        assert!(CallResponseEngine::call_number(v50).is_err(), "2^50 must exceed 32-trit single word");
    }

```

```
    #[test]
    fn test_call_response_number_all_256_bytes_dynamic_topologies() {
        // Test all 256 byte values across all 7 kinematic topologies
        let modes = [
            PackMode::Dense2222,
            PackMode::Kinematic21212,
            PackMode::Kinematic12122,
            PackMode::Kinematic22121,
            PackMode::Directional332,
            PackMode::Directional323,
            PackMode::Directional233,
        ];

        for byte_val in 0u8..=255u8 {
            for &mode in &modes {
                if let Ok(unpacked_trits) = Word32Trit::unpack_byte(byte_val, mode) {
                    // Repack and ensure round trip
                    let repacked = Word32Trit::pack_byte(&unpacked_trits, mode);
                    let unpacked_again = Word32Trit::unpack_byte(repacked, mode)
                        .expect("Repacked byte must unpack cleanly");
                    assert_eq!(unpacked_again[0], unpacked_trits[0]);
                    assert_eq!(unpacked_again[1], unpacked_trits[1]);
                    assert_eq!(unpacked_again[2], unpacked_trits[2]);
                    if mode == PackMode::Dense2222 {
                        assert_eq!(unpacked_again[3], unpacked_trits[3]);
                    }
                }
            }
        }
    }

    #[test]
    fn test_call_response_number_null_collision_trap() {
        // Inject collision code 11 (3) into dual rail
        let corrupted_register: u64 = 0b11;
        let res = CallResponseEngine::call_dual_rail(corrupted_register);
        assert!(res.is_err(), "Collision trap must reject code 11");
    }

    #[test]
    fn test_call_response_reversibility_and_stream() {
        // Test caller (operator) stream call
        let stream = "OMNICODE 2026";
        let resp = CallResponseEngine::call_stream(stream).expect("Stream must succeed");
        assert_eq!(resp.echoed, stream);
        assert_eq!(resp.text, stream);
        assert_eq!(resp.cell_count, 13);
        assert_eq!(resp.state, QuadState::Proceed);

        // Test universal execute dispatch
        let r1 = CallResponseEngine::execute(Call::Character('Z')).unwrap();
        assert!(matches!(r1, Response::Character(_)));

        let r2 = CallResponseEngine::execute(Call::Number(4096)).unwrap();
        assert!(matches!(r2, Response::Number(_)));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/universal/call_response_engine/echo.rs

RS | 155 LINES | 656 WORDS | 6.1 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal Echo Engine: Call-and-Response Mechanism for Characters, Numbers & Streams )
// ================================================================================
//! OmniCode Terminal: Universal Echo Protocol Engine
//!
//! # Architectural Scope & Purpose:
//! In OmniCode, **AN ECHO IS A CALL AND RESPONSE THAT REPEATS WHAT WAS CALLED FOR**.
//! Since the language is also designed for creating an AI model (where `.omni` and
//! `.tape` are the compiled and interpreted forms of the OmniCode framework, rather
//! than passive data types), the Caller and Sender represent the Operator and the
//! Machine (the computer).
//!
//! Because they are reversible, the Echo Engine handles:
//! 1. **Character Echo:** Inscribes glyph into 1 Cell, bijectively transduces to 5 trits,
//!    guards single-cell bounds, and projects verified glyph to output.
//! 2. **Number Echo:** Inscribes scalar quantity into 1 Word (32 trits <=> 64 bits),
//!    packs dual-rail polar planes (00=0, 01=+1, 10=-1), guards against 11 collision trap,
//!    proves ALU zero-sum balance (+1) + (-1) <=> 0, and projects response.
//! 3. **Stream Echo:** Chains character cells into text ribbons.
//!
//! # Scripture Witness:
//! - **Job 14:15 (KJV)**: "Thou shalt call, and I will answer thee."
//! - **Exodus 31:18 (KJV)**: Written with the finger of God.
//! - **Proverbs 24:27 (KJV)**: Prepare thy work without, and make it fit for thyself.
// ================================================================================

use crate::core::cell::{Cell, Trit};
use crate::core::ternary::QuadState;
use crate::terminal::universal::call_response_engine::call_response::{
    Call, Response, CharacterResponse, NumberResponse, StreamResponse, CallResponseEngine,
};

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Types, Enums & Status Containers )
// ================================================================================

/// Universal Echo Result returned by [`EchoEngine::echo`].
#[derive(Debug, Clone, PartialEq)]
pub enum EchoResult {
    /// Atomic Character Echo.
    Character(CharacterResponse),
    /// Scalar Number Echo.
    Number(NumberResponse),
    /// Stream / Text Echo.
    Stream(StreamResponse),
}

/// The Universal Echo Protocol Engine.
#[derive(Debug, Clone, Default)]
pub struct EchoEngine;

// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Operational Echo Methods )
// ================================================================================

impl EchoEngine {
    /// Executes a universal Echo turn for any [`Call`] payload.
    pub fn echo(call: Call) -> Result<EchoResult, String> {
        match CallResponseEngine::execute(call)? {
            Response::Character(c) => Ok(EchoResult::Character(c)),
            Response::Number(n) => Ok(EchoResult::Number(n)),
            Response::Stream(s) => Ok(EchoResult::Stream(s)),
        }
    }

    /// Echoes a single character glyph through 5-trit radix-3 cell transduction.
    pub fn echo_char(glyph: char) -> Result<CharacterResponse, String> {
        CallResponseEngine::call_char(glyph)
    }

```

```rust
    /// Echoes a scalar number through 32-trit dual-rail polar bit-planes.
    pub fn echo_number(scalar: i64) -> Result<NumberResponse, String> {
        CallResponseEngine::call_number(scalar)
    }

    /// Echoes an entire text stream through continuous character cells.
    pub fn echo_stream(input: &str) -> Result<StreamResponse, String> {
        CallResponseEngine::call_stream(input)
    }

    /// Transduces an 8-bit ASCII byte into 5 balanced trits using canonical [`Cell`] natural encoding.
    pub fn byte_to_5_trits(byte: u8) -> Result<[i8; 5], String> {
        let cell = Cell::from_natural(byte)?;
        let mut trits = [0i8; 5];
        for (i, t) in cell.trits.iter().enumerate() {
            trits[i] = t.as_i8();
        }
        Ok(trits)
    }

    /// Reconstructs an 8-bit byte from 5 balanced trits using canonical [`Cell`] natural decoding.
    pub fn five_trits_to_byte(trits: &[i8; 5]) -> Result<u8, String> {
        let mut cell_trits = [Trit::Zero; 5];
        for (i, &t) in trits.iter().enumerate() {
            cell_trits[i] = Trit::from_i8(t)?;
        }
        let cell = Cell::new(cell_trits, QuadState::Proceed);
        cell.to_natural().ok_or_else(|| "Failed to decode natural byte from cell".to_string())
    }

    /// Verifies that a character fits strictly within single-cell bounds.
    pub fn verify_single_cell_bound(c: char) -> bool {
        c.len_utf8() <= 4
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests for Universal Echo Protocol Engine )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_echo_char_letters_and_symbols() {
        let test_chars = ['A', 'Z', 'a', 'z', '0', '9', '!', '@', '#', '$', ' '];
        for &c in &test_chars {
            let res = EchoEngine::echo_char(c).expect("Echo char must succeed");
            assert_eq!(res.glyph, c);
            assert_eq!(res.state, QuadState::Proceed);
            assert_eq!(res.cell_footprint, 1);
        }
    }

    #[test]
    fn test_echo_number_equilibrium() {
        let res = EchoEngine::echo_number(42).expect("Echo number must succeed");
        assert_eq!(res.scalar, 42);
        assert!(res.equilibrium_proved);
        assert!(res.rail_involution_proved);
    }

    #[test]
    fn test_echo_stream() {
        let text = "OmniCode Universal Echo OK";
        let res = EchoEngine::echo_stream(text).expect("Stream echo must succeed");
        assert_eq!(res.echoed, text);
        assert_eq!(res.text, text);
    }

    #[test]
    fn test_echo_universal_call_dispatch() {
        let res_char = EchoEngine::echo(Call::Character('K')).unwrap();
        assert!(matches!(res_char, EchoResult::Character(_)));

        let res_num = EchoEngine::echo(Call::Number(-1)).unwrap();
```

```
        assert!(matches!(res_num, EchoResult::Number(_)));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/terminal/universal/call_response_engine/mod.rs

RS | 27 LINES | 74 WORDS | 0.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Call-Response Engine Subsystem Module )
// ============================================================================
//! OmniCode Terminal: Call & Response Engine Module
//!
//! Subsumes character echo and number execution into the unified Call-and-Response
//! protocol, defining Echo as the Call-Response mechanism that repeats what was called for.
// ============================================================================

pub mod call_response;
pub mod echo;

pub use call_response::{
    Call,
    Response,
    CharacterResponse,
    NumberResponse,
    StreamResponse,
    CallResponseEngine,
};

pub use echo::{
    EchoResult,
    EchoEngine,
};
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/cli/mod.rs RS 44 LINES 157 WORDS 2.0 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( CLI Subsystem Identity, Module Architecture & Core Re-exports )
// ================================================================================
//! OmniCode Command Line Subsystem
//!
//! Exposes interactive terminal REPL, script runners, structural 4-block linters,
//! and template scaffolding generators.

pub mod repl;
pub mod server;
pub mod commands;


// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Re-export Declarations & Public Interface )
// ================================================================================
pub use repl::run_repl;
pub use server::run_gui_server;
pub use commands::{
    BootArch, BootConfig, BootContext, run_boot, run_boot_with_config,
    execute_kernel_pipeline, synthesize_hypervisor_command, execute_boot_pipeline, execute_boot_machine,
    DEFAULT_BOOT_ARCH, DEFAULT_GRAPHICAL_MODE, REAL_MODE_BOOT_VECTOR, VGA_TEXT_FRAMEBUFFER_BASE, COM1_SERIAL_IO_BASE,
    AssembleFormat, AssembleConfig, AssembleContext, run_assemble, run_assemble_with_config,
    execute_assemble_pipeline, serialize_assembled_output,
    RunFormat, RunConfig, RunContext, RunResult, run_with_config, execute_run_pipeline,
    run_on_virtual_terminal, run_omni_source, run_tape_ribbon, run_c_transpile, run_lua_transpile,
};


// ================================================================================
// BLOCK 3: BODY BLOCK
// ( CLI Orchestration Framework )
// ================================================================================
// Command line entrypoints route to interactive REPL or single-file runners.


// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification and Sealing )
// ================================================================================
// CLI subsystem verified and sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/cli/repl.rs RS 427 LINES 1585 WORDS 21.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Interactive Terminal Environment Identity, REPL Architecture & Dependencies )
// ============================================================================
//! OmniCode Terminal REPL: Interactive Ontological Shell
//!
//! Provides an interactive read-eval-print loop (REPL) enabling direct,
//! zero-latency experimentation with OmniCode's foundational primitives:
//!     - Balanced Ternary Logic (-1 Rollback, 0 Await, +1 Proceed, NULL Halt)
//!     - 6 Boundary Morphologies & Asymmetric Closures
//!     - First-Class Intent Asides (...)
//!     - 3D Coordinate Operators & Directional Vectors
//!     - Transactional Environment Snapshot & Rollback
//!     - Real-Time Diagnostic Failpoint Trapping

use std::fs;
use std::path::PathBuf;
use rustyline::error::ReadlineError;
use rustyline::DefaultEditor;

use crate::ast::nodes::ASTNode;
use crate::core::ternary::QuadState;
use crate::diagnostics::debugger::OmniDebugger;
use crate::diagnostics::logger::DiagnosticLogger;
use crate::diagnostics::linter::OmniLinter;
use crate::parser::lexer::Lexer;
use crate::parser::parser::Parser;
use crate::runtime::environment::{Environment, RuntimeValue};
use crate::runtime::evaluator::Evaluator;


// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( REPL Configuration, Banner Display, and Context State Initialization )
// ============================================================================
/// Resolves the file path for persistent terminal command history.
fn get_history_path() -> Option<PathBuf> {
    std::env::var("HOME").ok().map(|h| PathBuf::from(h).join(".omnicode_history"))
}

/// Checks whether an interactive input buffer has balanced delimiters.
fn is_input_complete(input: &str) -> bool {
    let trimmed = input.trim_end();
    if trimmed.ends_with('\\') {
        return false;
    }

    let mut open_brackets = 0isize;
    let mut in_string = false;
    let mut quote_char = ' ';

    for line in input.lines() {
        let stripped = line.trim();
        if stripped.starts_with('#') {
            continue;
        }

        let chars: Vec<char> = line.chars().collect();
        let mut i = 0;
        while i < chars.len() {
            let c = chars[i];
            if in_string {
                if c == '\\' {
                    i += 2;
                    continue;
                }
                if c == quote_char {
                    in_string = false;
                }
            } else {
                match c {
                    '#' => break, // Comment extends to end of line
                    '"' | '\'' => {
                        in_string = true;
```

```
                        quote_char = c;
                    }
                    '[' | '{' | '<' | '(' => open_brackets += 1,
                    ']' | '}' | '>' | ')' => open_brackets -= 1,
                    _ => {}
                }
            }
            i += 1;
        }
    }

    open_brackets <= 0
}

/// Displays the welcome banner and prompt instructions.
fn print_welcome_banner() {
    println!("\x1b[1;36m================================================================================\x1b[0m");
    println!("\x1b[1;36m  OmniCode Interactive Shell (v0.1.0)\x1b[0m");
    println!("\x1b[1;36m  Core: Balanced Ternary & Boundary Physics (Rust Engine)\x1b[0m");
    println!("\x1b[0;37m  Type \x1b[1;33m:help\x1b[0m\x1b[0;37m or \x1b[1;33m:?\x1b[0m\x1b[0;37m for commands & syntax cheat sheet. Press \x1b[1;33mCtrl+D\x1b[0m\x1b[0;37m to exit.\x1b[0m");
    println!("\x1b[1;36m================================================================================\x1b[0m\n");
}

/// Displays the help guide and syntax reference.
fn print_help_guide() {
    println!("\x1b[1;33m--- OmniCode Interactive Commands ---\x1b[0m");
    println!("  \x1b[1;32m:help\x1b[0m, \x1b[1;32m:?\x1b[0m              Show this help reference");
    println!("  \x1b[1;32m:env\x1b[0m                  Inspect all active symbols and entity bindings");
    println!("  \x1b[1;32m:ast <expr>\x1b[0m           Display raw AST structure of an expression");
    println!("  \x1b[1;32m:load <path>\x1b[0m          Load, lint, parse, and evaluate an OmniCode file (.omni / .scroll)");
    println!("  \x1b[1;32m:lint <path>\x1b[0m          Validate file against 4-Block architecture (.omni / .scroll)");
    println!("  \x1b[1;32m:failpoints\x1b[0m           Review all failpoint incidents trapped in this session");
    println!("  \x1b[1;32m:verbose [on|off]\x1b[0m     Toggle real-time microsecond diagnostic logging");
    println!("  \x1b[1;32m:clear\x1b[0m                Clear the terminal screen");
    println!("  \x1b[1;32m:reset\x1b[0m                Reset the environment and diagnostic stack");
    println!("  \x1b[1;32m:exit\x1b[0m, \x1b[1;32m:quit\x1b[0m          Exit the OmniCode interactive shell\n");

    println!("\x1b[1;33m--- Notation & Physics Cheat Sheet ---\x1b[0m");
    println!("  \x1b[1;36mBoundaries:\x1b[0m   [...] mutable | <...> immutable axiom | {{...}} context");
    println!("                {{...] top-down asymmetric | [...}} bottom-up asymmetric | (...) intent aside");
    println!("  \x1b[1;36mTernary:\x1b[0m      +1 (Proceed) | 0 (Await) | -1 (Rollback) | NULL (Halt)");
    println!("  \x1b[1;36mRelations:\x1b[0m    = (Is Identity) | != (Is Not) | ~= (To Be Like)");
    println!("  \x1b[1;36mVectors:\x1b[0m      --> (Act Upon / Forward) | <-- (Act Again / Rollback)");
    println!("                ^-- (Builds To) | v-- (Breaks Down From)");
    println!("  \x1b[1;36mConnectives:\x1b[0m  ! (Adversative Caveat BUT) | :: (Conjunction AND) | | (Disjunction OR)\n");
}


// ==============================================================================
// BLOCK 3: BODY BLOCK
// ( Core REPL Execution Loop: Command Dispatch, Parser, Evaluator Pipeline )
// ==============================================================================
/// Launches and executes the OmniCode interactive REPL terminal session.
pub fn run_repl() -> Result<(), Box<dyn std::error::Error>> {
    print_welcome_banner();

    let mut rl = DefaultEditor::new()?;
    let history_file = get_history_path();
    if let Some(ref path) = history_file {
        let _ = rl.load_history(path);
    }

    let logger = DiagnosticLogger::new(false);
    let mut debugger = OmniDebugger::new(logger.clone(), 10);
    let mut env = Environment::new();
    let mut current_state = QuadState::Proceed;
    let mut verbose = false;
    let mut multiline_buffer = String::new();

    loop {
        let prompt = if multiline_buffer.is_empty() {
            match current_state {
                QuadState::Proceed => "\x1b[1;32momni[+1]>\x1b[0m ".to_string(),
                QuadState::Await => "\x1b[1;33momni[0]>\x1b[0m ".to_string(),
                QuadState::Rollback => "\x1b[1;31momni[-1]>\x1b[0m ".to_string(),
```

```
                QuadState::Halt => "\x1b[1;35momni[NULL]>\x1b[0m ".to_string(),
            }
        } else {
            "\x1b[1;30m   ...>\x1b[0m ".to_string()
        };

        let readline = rl.readline(&prompt);
        match readline {
            Ok(line) => {
                let trimmed = line.trim();

                // Multiline buffering logic
                if !multiline_buffer.is_empty() {
                    if trimmed.is_empty() {
                        // Empty line forces execution of buffered input
                    } else {
                        multiline_buffer.push('\n');
                        multiline_buffer.push_str(&line);
                        if !is_input_complete(&multiline_buffer) {
                            continue;
                        }
                    }
                } else if !trimmed.is_empty() && !trimmed.starts_with(':') && !is_input_complete(trimmed) {
                    multiline_buffer.push_str(&line);
                    continue;
                }

                let input = if !multiline_buffer.is_empty() {
                    let full = multiline_buffer.clone();
                    multiline_buffer.clear();
                    full
                } else {
                    line
                };

                let input_trimmed = input.trim();
                if input_trimmed.is_empty() {
                    continue;
                }

                let _ = rl.add_history_entry(input_trimmed);

                // Command Dispatch
                if input_trimmed.starts_with(':') || input_trimmed == "exit" || input_trimmed == "quit" {
                    let cmd_parts: Vec<&str> = input_trimmed.splitn(2, ' ').collect();
                    let cmd = cmd_parts[0];
                    let arg = if cmd_parts.len() > 1 { cmd_parts[1].trim() } else { "" };

                    match cmd {
                        ":help" | ":?" => print_help_guide(),
                        ":exit" | ":quit" | "exit" | "quit" => {
                            println!("\x1b[1;36mSealing OmniCode session. Goodbye.\x1b[0m");
                            break;
                        }
                        ":clear" => {
                            print!("\x1b[2J\x1b[1;1H");
                        }
                        ":reset" => {
                            env.clear();
                            logger.clear();
                            debugger = OmniDebugger::new(logger.clone(), 10);
                            current_state = QuadState::Proceed;
                            println!("\x1b[1;32m✓ Session reset: Environment and failpoints cleared.\x1b[0m");
                        }
                        ":env" => {
                            let bindings = env.bindings();
                            if bindings.is_empty() {
                                println!("\x1b[0;37m(Environment is empty)\x1b[0m");
                            } else {
                                println!("\x1b[1;33m--- Active Symbols & Bindings ({}) ---\x1b[0m", bindings.len());
                                for (k, v) in bindings {
                                    println!("  \x1b[1;36m{}\x1b[0m = {}", k, v.format_colored());
                                }
                            }
                        }
                        ":tokens" => {
                            if arg.is_empty() {
                                eprintln!("\x1b[1;31mUsage:\x1b[0m :tokens <expression>");
```

```
                                } else {
                                    let mut lex = Lexer::new(arg, logger.clone());
                                    match lex.tokenize() {
                                        Ok(toks) => {
                                            println!("\x1b[1;33mTokens ({}):\x1b[0m", toks.len());
                                            for t in toks {
                                                println!("  {:?}  \x1b[0;37m('{}' at L{}:C{})\x1b[0m", t.token_type,
t.lexeme, t.line, t.col);
                                            }
                                        }
                                        Err(e) => eprintln!("\x1b[1;31m✗ Lexer Error:\x1b[0m {}", e),
                                    }
                                }
                            }
                            ":ast" => {
                                if arg.is_empty() {
                                    eprintln!("\x1b[1;31mUsage:\x1b[0m :ast <expression>");
                                } else {
                                    let mut lex = Lexer::new(arg, logger.clone());
                                    match lex.tokenize() {
                                        Ok(toks) => {
                                            let mut p = Parser::new(toks, debugger.clone());
                                            match p.parse_program() {
                                                Ok(ast) => println!("{:#?}", ast),
                                                Err(e) => eprintln!("\x1b[1;31m✗ Parser Error:\x1b[0m {}", e),
                                            }
                                        }
                                        Err(e) => eprintln!("\x1b[1;31m✗ Lexer Error:\x1b[0m {}", e),
                                    }
                                }
                            }
                            ":failpoints" => {
                                let fps = logger.failpoints();
                                if fps.is_empty() {
                                    println!("\x1b[1;32m✓ No failpoint incidents recorded.\x1b[0m");
                                } else {
                                    println!("\x1b[1;33m--- Trapped Failpoint Incidents ({}) ---\x1b[0m", fps.len());
                                    for fp in fps {
                                        let fp_name = fp.failpoint_type.map(|t| t.as_str()).unwrap_or("GENERIC");
                                        println!("  * [{} µs] \x1b[1;31m[{}]\x1b[0m [{}] {}", fp.elapsed_micros, fp.channel,
fp_name, fp.message);
                                    }
                                }
                            }
                            ":verbose" => {
                                if arg == "on" {
                                    verbose = true;
                                    println!("\x1b[1;32m✓ Diagnostic verbose logging ENABLED.\x1b[0m");
                                } else if arg == "off" {
                                    verbose = false;
                                    println!("\x1b[1;33m✓ Diagnostic verbose logging DISABLED.\x1b[0m");
                                } else {
                                    verbose = !verbose;
                                    println!("Diagnostic verbose logging is now: \x1b[1;36m{}\x1b[0m", if verbose { "ON" }
else { "OFF" });
                                }
                            }
                            ":lint" => {
                                if arg.is_empty() {
                                    eprintln!("\x1b[1;31mUsage:\x1b[0m :lint <file.omni | file.scroll>");
                                } else {
                                    match fs::read_to_string(arg) {
                                        Ok(content) => {
                                            let linter = OmniLinter::new(logger.clone());
                                            let report = linter.lint_source(arg, &content);
                                            if report.is_valid {
                                                println!("\x1b[1;32m✓ 4-Block Structural Check Passed:\x1b[0m {} blocks
verified in canonical sequence.", report.blocks_found.len());
                                            } else {
                                                println!("\x1b[1;31m✗ 4-Block Structural Linter Violations:\x1b[0m");
                                                for err in report.errors {
                                                    println!("    \x1b[1;31m•\x1b[0m {}", err);
                                                }
                                            }
                                        }
                                        Err(e) => eprintln!("\x1b[1;31m✗ File read error:\x1b[0m {}", e),
                                    }
                                }
```

```
                        }
                        ":load" => {
                            if arg.is_empty() {
                                eprintln!("\x1b[1;31mUsage:\x1b[0m :load <file.omni | file.scroll>");
                            } else {
                                match fs::read_to_string(arg) {
                                    Ok(source) => {
                                        let prev_fps_len = logger.failpoints().len();
                                        let mut lex = Lexer::new(&source, logger.clone());
                                        match lex.tokenize() {
                                            Ok(toks) => {
                                                let mut p = Parser::new(toks, debugger.clone());
                                                match p.parse_program() {
                                                    Ok(prog) => {
                                                        let mut eval = Evaluator::new(env.clone(), p.debugger);
                                                        match eval.eval(&ASTNode::Program(prog)) {
                                                            Ok(res) => {
                                                                env = eval.env;
                                                                debugger = eval.debugger;
                                                                if let RuntimeValue::State(s) = res {
                                                                    current_state = s;
                                                                }
                                                                println!("\x1b[1;32m✓ Loaded and evaluated '{}':\x1b[0m
=> {}", arg, res.format_colored());
                                                            }
                                                            Err(e) => eprintln!("\x1b[1;31m✗ Evaluation Error in
'{}':\x1b[0m {}", arg, e),
                                                        }
                                                    }
                                                    Err(e) => eprintln!("\x1b[1;31m✗ Parser Error in '{}':\x1b[0m {}",
arg, e),
                                                }
                                            }
                                            Err(e) => eprintln!("\x1b[1;31m✗ Lexer Error in '{}':\x1b[0m {}", arg, e),
                                        }
                                        let new_fps = logger.failpoints();
                                        if new_fps.len() > prev_fps_len {
                                            for fp in &new_fps[prev_fps_len..] {
                                                let fp_name = fp.failpoint_type.map(|t|
t.as_str()).unwrap_or("FAILPOINT");
                                                println!("  \x1b[1;33m[FAILPOINT: {}]\x1b[0m {}", fp_name, fp.message);
                                            }
                                        }
                                    }
                                    Err(e) => eprintln!("\x1b[1;31m✗ File read error:\x1b[0m {}", e),
                                }
                            }
                        }
                        other => {
                            eprintln!("\x1b[1;31mUnknown command:\x1b[0m '{}'. Type :help for commands.", other);
                        }
                    }
                    continue;
                }

                // OmniCode Expression / Statement Evaluation Pipeline
                let prev_fps_len = logger.failpoints().len();
                let mut lexer = Lexer::new(input_trimmed, logger.clone());
                match lexer.tokenize() {
                    Ok(tokens) => {
                        let mut parser = Parser::new(tokens, debugger.clone());
                        match parser.parse_program() {
                            Ok(prog) => {
                                let mut evaluator = Evaluator::new(env.clone(), parser.debugger);
                                match evaluator.eval(&ASTNode::Program(prog)) {
                                    Ok(val) => {
                                        env = evaluator.env;
                                        debugger = evaluator.debugger;
                                        if let RuntimeValue::State(s) = val {
                                            current_state = s;
                                        }
                                        println!("=> {}", val.format_colored());
                                    }
                                    Err(err) => {
                                        eprintln!("\x1b[1;31m✗ Runtime Error:\x1b[0m {}", err);
                                    }
                                }
                            }
```

```
                            Err(parse_err) => {
                                eprintln!("\x1b[1;31m✗ Syntax Error:\x1b[0m {}", parse_err);
                            }
                        }
                    }
                    Err(lex_err) => {
                        eprintln!("\x1b[1;31m✗ Lexical Error:\x1b[0m {}", lex_err);
                    }
                }

                // Check and print any failpoint alerts triggered during this line
                let all_fps = logger.failpoints();
                if all_fps.len() > prev_fps_len {
                    for fp in &all_fps[prev_fps_len..] {
                        let fp_name = fp.failpoint_type.map(|t| t.as_str()).unwrap_or("FAILPOINT");
                        println!("  \x1b[1;33m[FAILPOINT: {}]\x1b[0m {}", fp_name, fp.message);
                    }
                }

                if verbose {
                    println!("\x1b[0;37m(Active bindings: {}, snapshot depth: {})\x1b[0m", env.bindings().len(),
debugger.boundary_stack.len());
                }
            }
            Err(ReadlineError::Interrupted) => {
                println!("\x1b[1;33m^C (Interrupted. Type :exit or press Ctrl+D to quit)\x1b[0m");
                multiline_buffer.clear();
            }
            Err(ReadlineError::Eof) => {
                println!("\x1b[1;36mSealing OmniCode session. Goodbye.\x1b[0m");
                break;
            }
            Err(err) => {
                eprintln!("\x1b[1;31mTerminal Error:\x1b[0m {:?}", err);
                break;
            }
        }
    }

    if let Some(ref path) = history_file {
        let _ = rl.save_history(path);
    }

    Ok(())
}


// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Session Invariants, Teardown Proofs, and Terminal Teardown )
// ================================================================================
// Terminal REPL engine verified and sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/cli/server.rs RS 576 LINES 1855 WORDS 23.0 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( OmniCode GUI Server Identity, Zero-Dependency Architecture & REST Invariants )
// ================================================================================
//! OmniCode Local Web GUI Server & Terminal Gateway
//!
//! Provides a pure standard-library HTTP server (0 external crates) hosting the
//! local OmniCode Studio GUI and Terminal Interface:
//!   - Static file delivery: `gui/index.html`, `gui/style.css`, `gui/app.js`
//!   - REST endpoints:
//!     * `POST /api/prompt`    -> Executes AICortex neural-symbolic cognitive pipeline
//!     * `POST /api/terminal`  -> Executes CLI commands directly (`omnicode run/lint/demo`)
//!     * `GET  /api/manifest`  -> Returns canonical `manifest.omni` covenant anchor
//!     * `GET  /api/lexicon`   -> Returns offline Biblical world model & passage citations
//!     * `GET  /api/scrolls`   -> Returns episodic memory learning statistics

use std::fs;
use std::io::{Read, Write};
use std::net::{TcpListener, TcpStream};
use std::path::Path;
use std::sync::{Arc, Mutex};
use std::thread;

use crate::ai::{AICortex, AILearner, BiblicalLexicon};
use crate::core::ternary::QuadState;
use crate::diagnostics::hover::HoverEngine;
use crate::diagnostics::logger::DiagnosticLogger;
use crate::terminal::{create_shared_scheduler, SharedScheduler, TerminalSession};


// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Server Configuration, HTTP Parser & Response Structures )
// ================================================================================

pub struct GuiServerConfig {
    pub host: String,
    pub port: u16,
    pub gui_dir: String,
}

impl Default for GuiServerConfig {
    fn default() -> Self {
        Self {
            host: "127.0.0.1".to_string(),
            port: 8080,
            gui_dir: "gui".to_string(),
        }
    }
}


// ================================================================================
// BLOCK 3: BODY BLOCK
// ( TCP Listener Loop, HTTP Routing, and REST API Handlers )
// ================================================================================

/// Starts the OmniCode GUI HTTP server on the specified port.
pub fn run_gui_server(port: u16) -> Result<(), String> {
    let host = std::env::var("OMNICODE_HOST").unwrap_or_else(|_| "0.0.0.0".to_string());
    let listener = TcpListener::bind(format!("{host}:{port}"))
        .map_err(|e| format!("Failed to bind TCP listener to {host}:{port}: {e}"))?;

    println!("\x1b[1;36m================================================================================\x1b[0m");
    println!("\x1b[1;36m  OmniCode GUI Studio & Terminal Server Active                                    \x1b[0m");
    println!("\x1b[1;36m================================================================================\x1b[0m");
    println!("\x1b[1;32m✓ Web Studio URL:\x1b[0m http://localhost:{port} (listening on {host}:{port})");
    println!("\x1b[1;33m✓ Backend Mode:\x1b[0m 100% Offline | Grounded in Biblical Lexicon & Covenant Manifest");
    println!("\x1b[1;35m✓ Terminal Gateway:\x1b[0m Active (CLI commands executable via GUI)\n");
    println!("Press Ctrl+C to terminate server.\n");

    let lexicon = Arc::new(BiblicalLexicon::new());
    let scheduler = create_shared_scheduler();
    let session = Arc::new(Mutex::new(TerminalSession::new(Arc::clone(&scheduler))));
```

```

    for stream in listener.incoming() {
        match stream {
            Ok(stream) => {
                let lex_clone = Arc::clone(&lexicon);
                let sched_clone = Arc::clone(&scheduler);
                let sess_clone = Arc::clone(&session);
                thread::spawn(move || {
                    handle_connection(stream, lex_clone, sched_clone, sess_clone);
                });
            }
            Err(e) => {
                eprintln!("Connection failed: {e}");
            }
        }
    }

    Ok(())
}

fn handle_connection(
    mut stream: TcpStream,
    lexicon: Arc<BiblicalLexicon>,
    scheduler: SharedScheduler,
    session: Arc<Mutex<TerminalSession>>,
) {
    let mut buffer = [0u8; 16384];
    let bytes_read = match stream.read(&mut buffer) {
        Ok(n) if n > 0 => n,
        _ => return,
    };

    let request_str = String::from_utf8_lossy(&buffer[..bytes_read]);
    let mut lines = request_str.lines();
    let request_line = match lines.next() {
        Some(line) => line,
        std::option::Option::None => return,
    };

    let parts: Vec<&str> = request_line.split_whitespace().collect();
    if parts.len() < 2 {
        return;
    }

    let method = parts[0];
    let raw_path = parts[1];
    let path = raw_path.split('?').next().unwrap_or(raw_path);
    let is_head = method == "HEAD";
    let route_method = if is_head { "GET" } else { method };

    // Extract body if POST
    let body = if method == "POST" {
        if let Some(pos) = request_str.find("\r\n\r\n") {
            request_str[pos + 4..].to_string()
        } else if let Some(pos) = request_str.find("\n\n") {
            request_str[pos + 2..].to_string()
        } else {
            String::new()
        }
    } else {
        String::new()
    };

    // Route Request
    match (route_method, path) {
        ("GET", "/") | ("GET", "/studio") | ("GET", "/index.html") | ("GET", "/studio.html") => {
            serve_file(&mut stream, "apps/gui/studio.html", "text/html; charset=utf-8", is_head);
        }
        ("GET", "/terminal") | ("GET", "/terminal.html") => {
            serve_file(&mut stream, "apps/gui/terminal.html", "text/html; charset=utf-8", is_head);
        }
        ("GET", "/specs") | ("GET", "/specs.html") => {
            serve_file(&mut stream, "apps/gui/specs.html", "text/html; charset=utf-8", is_head);
        }
        ("GET", "/model") | ("GET", "/model.html") => {
            serve_file(&mut stream, "apps/gui/model.html", "text/html; charset=utf-8", is_head);
        }
        ("GET", "/lexicon") | ("GET", "/lexicon.html") => {
```

```
            serve_file(&mut stream, "apps/gui/lexicon.html", "text/html; charset=utf-8", is_head);
        }
        ("GET", "/scrolls") | ("GET", "/scrolls.html") => {
            serve_file(&mut stream, "apps/gui/scrolls.html", "text/html; charset=utf-8", is_head);
        }
        ("GET", "/cloud") | ("GET", "/cloud.html") => {
            serve_file(&mut stream, "apps/gui/cloud.html", "text/html; charset=utf-8", is_head);
        }
        ("GET", "/download") | ("GET", "/download.html") => {
            serve_file(&mut stream, "apps/gui/download.html", "text/html; charset=utf-8", is_head);
        }
        ("GET", "/terminal.js") => {
            serve_file(&mut stream, "apps/gui/terminal.js", "application/javascript; charset=utf-8", is_head);
        }
        ("GET", "/style.css") => {
            serve_file(&mut stream, "apps/gui/style.css", "text/css; charset=utf-8", is_head);
        }
        ("GET", "/app.js") => {
            serve_file(&mut stream, "apps/gui/app.js", "application/javascript; charset=utf-8", is_head);
        }
        ("GET", "/api/health") => {
            let json = r#"{"status":"healthy","engine":"OmniCode","version":"0.1.0","state":"+1:PROCEED"}"#;
            send_json_response(&mut stream, 200, json, is_head);
        }
        ("GET", "/api/download") => {
            let archive_path = "dist/omnicode-terminal-linux-x86_64.tar.gz";
            if let Ok(bytes) = fs::read(archive_path) {
                let header = format!(
                    "HTTP/1.1 200 OK\r\nContent-Type: application/gzip\r\nContent-Disposition: attachment;
filename=\"omnicode-terminal-linux-x86_64.tar.gz\"\r\nContent-Length: {}\r\nAccess-Control-Allow-Origin: *\r\nConnection:
close\r\n\r\n",
                    bytes.len()
                );
                let _ = stream.write_all(header.as_bytes());
                if !is_head {
                    let _ = stream.write_all(&bytes);
                }
            } else {
                let err = r#"{"error":"Distribution archive not found. Run scripts/package_native.sh to build."}"#;
                send_json_response(&mut stream, 404, err, is_head);
            }
        }
        ("GET", "/api/scheduler") => {
            let json = scheduler.lock().unwrap().to_json();
            send_json_response(&mut stream, 200, &json, is_head);
        }
        ("POST", "/api/scheduler/spawn") => {
            let cmd_str = extract_json_field(&body, "command").unwrap_or_else(|| "omnicode demo".to_string());
            let name_str = extract_json_field(&body, "name").unwrap_or_else(|| "UserTask".to_string());
            let prio_str = extract_json_field(&body, "priority").unwrap_or_else(|| "NORMAL".to_string());
            let priority = match prio_str.to_uppercase().as_str() {
                "HIGH" => crate::terminal::TaskPriority::High,
                "LOW" => crate::terminal::TaskPriority::Low,
                "BACKGROUND" => crate::terminal::TaskPriority::Background,
                _ => crate::terminal::TaskPriority::Normal,
            };
            let mut sched = scheduler.lock().unwrap();
            let pid = sched.spawn(&name_str, &cmd_str, priority);
            let json = format!(r#"{{"pid":{},"status":"spawned"}}"#, pid);
            send_json_response(&mut stream, 200, &json, is_head);
        }
        ("GET", "/api/manifest") => {
            let manifest_content = fs::read_to_string("manifest.omni")
                .unwrap_or_else(|_| "# Manifest not found".to_string());
            let json = format!(
                r#"{{"manifest": "{}"}}"#,
                escape_json_string(&manifest_content)
            );
            send_json_response(&mut stream, 200, &json, is_head);
        }
        ("GET", "/api/lexicon") => {
            let mut entries_json = Vec::new();
            for e in lexicon.all_entries() {
                entries_json.push(format!(
                    r#"{{"term":"{}","domain":"{}","definition":"{}","kjv":"{}","web":"{}","state":"{}","guidance":"
{}"}}"#,
                    escape_json_string(e.term),
                    escape_json_string(e.domain.as_str()),
```

```
                        escape_json_string(e.definition),
                        escape_json_string(e.kjv_passage),
                        escape_json_string(e.web_passage),
                        escape_json_string(e.quad_state_resonance.macro_op()),
                        escape_json_string(e.moral_guidance)
                    ));
                }
                let json = format!(r#"{{"count":{},"entries":[{}]}}"#, entries_json.len(), entries_json.join(","));
                send_json_response(&mut stream, 200, &json, is_head);
            }
            ("GET", "/api/scrolls") => {
                let scroll_dir = if Path::new("storage/scrolls").exists() {
                    "storage/scrolls"
                } else if Path::new("runtime/scrolls").exists() {
                    "runtime/scrolls"
                } else {
                    "scrolls"
                };
                let learner = AILearner::new(scroll_dir);
                let summary = learner.digest_experiences().unwrap_or_default();
                let mut exp_json = Vec::new();
                for e in &summary.experiences {
                    exp_json.push(format!(
                        r#"{{"session_id":"{}","prompt":"{}","state":"{}","repairs":{},"failpoints":{},"scroll":"{}"}}"#,
                        escape_json_string(&e.session_id),
                        escape_json_string(&e.prompt),
                        escape_json_string(e.final_state.macro_op()),
                        e.repair_count,
                        e.failpoint_count,
                        escape_json_string(&e.scroll_path.to_string_lossy())
                    ));
                }
                let json = format!(
                    r#"{{"total":{},"proceed":{},"rollback":{},"await":{},"halt":{},"repairs_learned":{},"episodes":[{}]}}"#,
                    summary.total_episodes, summary.proceed_count, summary.rollback_count, summary.await_count,
summary.halt_count,
                    summary.total_repairs_learned, exp_json.join(",")
                );
                send_json_response(&mut stream, 200, &json, is_head);
            }
            ("POST", "/api/prompt") => {
                let prompt = extract_json_field(&body, "prompt").unwrap_or_else(|| body.clone());
                let mut cortex = AICortex::new();
                match cortex.process_prompt(&prompt) {
                    Ok(res) => {
                        let mut repairs_json = Vec::new();
                        for r in &res.repairs_applied {
                            repairs_json.push(format!(
                                r#"{{"line":{},"kind":"{:?}","desc":"{}"}}"#,
                                r.line, r.kind, escape_json_string(&r.description)
                            ));
                        }
                        let json = format!(
                            r#"{{"session_id":"{}","prompt":"{}","state":"{}","response":"{}","omnicode":"{}","scroll":"
{}","log":"{}","repairs":[{}]}}"#,
                            escape_json_string(&res.session_id),
                            escape_json_string(&res.prompt),
                            escape_json_string(res.execution_state.macro_op()),
                            escape_json_string(&res.natural_response),
                            escape_json_string(&res.synthesized_omnicode),
                            escape_json_string(&res.scroll_path.to_string_lossy()),
                            escape_json_string(&res.log_path.to_string_lossy()),
                            repairs_json.join(",")
                        );
                        send_json_response(&mut stream, 200, &json, is_head);
                    }
                    Err(e) => {
                        let json = format!(r#"{{"error":"{}"}}"#, escape_json_string(&e));
                        send_json_response(&mut stream, 500, &json, is_head);
                    }
                }
            }
            ("GET", "/api/system") => {
                let json = r#"{"project":"OmniCode","organization":"CreativeWorkzStudio
LLC","version":"0.1.0","offline":true,"engine":"Rust Core 2024 (Balanced Ternary Quad-State)"}"#;
                send_json_response(&mut stream, 200, json, is_head);
            }
            ("GET", "/api/hover") => {
```

```
            let file = extract_query_param(raw_path, "file");
            let symbol = extract_query_param(raw_path, "symbol");
            let line = extract_query_param(raw_path, "line")
                .and_then(|s| s.parse::<usize>().ok())
                .unwrap_or(1);
            let col = extract_query_param(raw_path, "col")
                .and_then(|s| s.parse::<usize>().ok())
                .unwrap_or(1);

            let mut engine = HoverEngine::new(DiagnosticLogger::new(false));
            engine.index_workspace(".");

            let card = if let Some(ref sym) = symbol {
                engine.document_symbol(sym, file.as_deref())
            } else if let Some(ref f) = file {
                engine.hover_at(f, line, col)
            } else {
                None
            };

            match card {
                Some(c) => send_json_response(&mut stream, 200, &c.to_json(), is_head),
                None => {
                    let err = r#"{"symbol":"","found":false,"error":"No symbol found or target could not be resolved"}"#;
                    send_json_response(&mut stream, 404, err, is_head);
                }
            }
        }
        ("POST", "/api/hover") => {
            let file = extract_json_field(&body, "file");
            let symbol = extract_json_field(&body, "symbol");
            let line = extract_json_field(&body, "line")
                .and_then(|s| s.parse::<usize>().ok())
                .unwrap_or(1);
            let col = extract_json_field(&body, "col")
                .and_then(|s| s.parse::<usize>().ok())
                .unwrap_or(1);

            let mut engine = HoverEngine::new(DiagnosticLogger::new(false));
            engine.index_workspace(".");

            let card = if let Some(ref sym) = symbol {
                engine.document_symbol(sym, file.as_deref())
            } else if let Some(ref f) = file {
                engine.hover_at(f, line, col)
            } else {
                None
            };

            match card {
                Some(c) => send_json_response(&mut stream, 200, &c.to_json(), is_head),
                None => {
                    let err = r#"{"symbol":"","found":false,"error":"No symbol found or target could not be resolved"}"#;
                    send_json_response(&mut stream, 404, err, is_head);
                }
            }
        }
        ("POST", "/api/terminal") => {
            let cmd_str = extract_json_field(&body, "command").unwrap_or_else(|| body.clone());
            let clean_cmd = cmd_str.trim();

            let res = {
                let mut s = session.lock().unwrap();
                s.execute(clean_cmd)
            };

            let state_str = match res.state {
                QuadState::Proceed => "+1:PROCEED",
                QuadState::Await => "0:AWAIT",
                QuadState::Rollback => "-1:ROLLBACK",
                QuadState::Halt => "NULL:HALT",
            };

            let json = format!(
                r#"{{"stdout":"{}","state":"{}","duration_us":{}}}"#,
                escape_json_string(&res.stdout),
                state_str,
                res.duration_us
```

```
            );
            send_json_response(&mut stream, 200, &json, is_head);
        }
        ("OPTIONS", _) => {
            // Handle CORS preflight
            let response = "HTTP/1.1 204 No Content\r\n\
                Access-Control-Allow-Origin: *\r\n\
                Access-Control-Allow-Methods: GET, POST, OPTIONS, HEAD\r\n\
                Access-Control-Allow-Headers: Content-Type\r\n\r\n";
            stream.write_all(response.as_bytes()).ok();
        }
        _ => {
            let response = "HTTP/1.1 404 Not Found\r\nContent-Length: 9\r\n\r\nNot Found";
            stream.write_all(response.as_bytes()).ok();
        }
    }
}

fn serve_file(stream: &mut TcpStream, file_path: &str, content_type: &str, is_head: bool) {
    let resolved_path = if Path::new(file_path).exists() {
        file_path.to_string()
    } else if file_path.starts_with("gui/") {
        let alt = format!("apps/{file_path}");
        if Path::new(&alt).exists() {
            alt
        } else {
            file_path.to_string()
        }
    } else {
        file_path.to_string()
    };

    if !Path::new(&resolved_path).exists() {
        let not_found = format!(
            "HTTP/1.1 404 Not Found\r\nContent-Type: text/plain\r\nContent-Length: {}\r\n\r\nFile Not Found: {}",
            resolved_path.len() + 16, resolved_path
        );
        stream.write_all(not_found.as_bytes()).ok();
        return;
    }

    match fs::read(&resolved_path) {
        Ok(data) => {
            let header = format!(
                "HTTP/1.1 200 OK\r\n\
                Content-Type: {}\r\n\
                Content-Length: {}\r\n\
                Access-Control-Allow-Origin: *\r\n\
                Connection: close\r\n\r\n",
                content_type, data.len()
            );
            stream.write_all(header.as_bytes()).ok();
            if !is_head {
                stream.write_all(&data).ok();
            }
        }
        Err(e) => {
            let err_body = format!("Error reading file: {e}");
            let header = format!(
                "HTTP/1.1 500 Internal Server Error\r\nContent-Length: {}\r\n\r\n{}",
                err_body.len(), err_body
            );
            stream.write_all(header.as_bytes()).ok();
        }
    }
}

fn send_json_response(stream: &mut TcpStream, status_code: u16, json: &str, is_head: bool) {
    let status_line = match status_code {
        200 => "200 OK",
        400 => "400 Bad Request",
        404 => "404 Not Found",
        500 => "500 Internal Server Error",
        _ => "200 OK",
    };

    let header = format!(
        "HTTP/1.1 {}\r\n\
```

```
        Content-Type: application/json; charset=utf-8\r\n\
        Content-Length: {}\r\n\
        Access-Control-Allow-Origin: *\r\n\
        Connection: close\r\n\r\n",
        status_line, json.as_bytes().len()
    );
    stream.write_all(header.as_bytes()).ok();
    if !is_head {
        stream.write_all(json.as_bytes()).ok();
    }
}

fn escape_json_string(s: &str) -> String {
    let mut out = String::with_capacity(s.len() + 10);
    for c in s.chars() {
        match c {
            '"' => out.push_str("\\\""),
            '\\' => out.push_str("\\\\"),
            '\n' => out.push_str("\\n"),
            '\r' => out.push_str("\\r"),
            '\t' => out.push_str("\\t"),
            '\u{0008}' => out.push_str("\\b"),
            '\u{000C}' => out.push_str("\\f"),
            c if c.is_control() => {
                out.push_str(&format!("\\u{:04x}", c as u32));
            }
            c => out.push(c),
        }
    }
    out
}

fn extract_json_field(json: &str, field_name: &str) -> Option<String> {
    let key = format!("\"{}\":", field_name);
    let key_pos = json.find(&key)?;
    let remainder = json[key_pos + key.len()..].trim_start();

    if remainder.starts_with('"') {
        let mut result = String::new();
        let chars = remainder[1..].chars();
        let mut escaped = false;
        for c in chars {
            if escaped {
                match c {
                    '"' => result.push('"'),
                    '\\' => result.push('\\'),
                    'n' => result.push('\n'),
                    'r' => result.push('\r'),
                    't' => result.push('\t'),
                    other => result.push(other),
                }
                escaped = false;
            } else if c == '\\' {
                escaped = true;
            } else if c == '"' {
                return Some(result);
            } else {
                result.push(c);
            }
        }
        Some(result)
    } else {
        None
    }
}

fn extract_query_param(raw_path: &str, param: &str) -> Option<String> {
    let query_str = raw_path.split('?').nth(1)?;
    for pair in query_str.split('&') {
        let mut kv = pair.split('=');
        let k = kv.next()?;
        if k == param {
            let v = kv.next().unwrap_or("");
            return Some(v.replace("%20", " ").replace('+', " "));
        }
    }
    None
}
```

```
537
538 #[allow(dead_code)]
539 fn tokenize_args(input: &str) -> Vec<String> {
540     let mut args = Vec::new();
541     let mut current = String::new();
542     let mut in_quotes = false;
543     let mut quote_char = '"';
544
545     for c in input.chars() {
546         if in_quotes {
547             if c == quote_char {
548                 in_quotes = false;
549             } else {
550                 current.push(c);
551             }
552         } else if c == '"' || c == '\'' {
553             in_quotes = true;
554             quote_char = c;
555         } else if c.is_whitespace() {
556             if !current.is_empty() {
557                 args.push(current);
558                 current = String::new();
559             }
560         } else {
561             current.push(c);
562         }
563     }
564     if !current.is_empty() {
565         args.push(current);
566     }
567     args
568 }
569
570
571 // ============================================================================
572 // BLOCK 4: CLOSING BLOCK
573 // ( Server Module Status & Invariant Verification )
574 // ============================================================================
575 // OmniCode GUI Server module sealed and active.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/cli/commands/assemble.rs RS 544 LINES 2088 WORDS 23.7 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Machine Manifest, Scheduling Priority, Dependency Contract & Tripwire Registry )
// ================================================================================
//! MODULE:              omnicode::cli::commands::assemble
//! IDENTITY:            Physical Assembly & Process Tape Lowering Gear
//! NATURE:              Lowering Engine from High-Level SVO Tapes to Low-Level Memory Layouts & Silicon Word Streams
//! VERSION:             0.3.0
//! CREATED:             2026-10-11
//! LAST_SEALED:         2026-10-11
//! AUTHOR:              CreativeWorkzStudio LLC / ProfessorSeanEX
//! COVENANT:            Public Domain / MIT
//!
//! SCHEDULER:
//!   TRACK_PRIMARY:     <TRACK 1> : {Host Engine & Virtual Machine}
//!   TRACKS_TOUCHED:    [ <TRACK 0> : {Silicon & Bare-Metal Kernel}, <TRACK 1>, <TRACK 2> : {OmniCode Language & Standard Library} ]
//!   PRIORITY:          TaskPriority::High
//!   CHANNEL:           Track::Kernel
//!
//! CONTRACT / WHO-WHAT-WHERE-WHY-HOW:
//!   WHO:               OmniCode Host Assembler Gear & Transpilation Lowering Driver
//!   WHAT:              Transduce high-level procedural `.tape` process ribbons into low-level declarative
//!                      `.omni` compiled memory reels, physical symbol tables, and 64-bit balanced-ternary
//!                      machine words ([`crate::core::word::Word64`]).
//!   WHERE:             Across Track 2 (`lexicon/`, `lib/kernel/`) or caller paths -> silicon memory partitions -> stdout / disk.
//!   WHEN:              Invoked via CLI command `omnicode assemble <file.tape> [--output <PATH>] [--format <listing|words|json>] [--verbose] [--dry-run]`
//!   WHY:               Eliminate ungrounded "python-ese" scripting drift by enforcing physical memory partition
//!                      allocation (`@ offset`), hardware register binding (`%self`, `%caller`, `%acc`, `%swarm`),
//!                      pronoun capability verification (`my`, `your`, `their`), and formal logic proofs (`! [ Invariant ]`).
//!   HOW:               Balanced Ternary (+1:PROCEED sealed assembly, -1:ROLLBACK trapped failpoint, 0:AWAIT dry-run).
//!
//! THE TRANSPILER TRIAD PHILOSOPHY:
//!   OmniCode operates across three isomorphic manifestations of code:
//!   1. `.omni` (Low-Level Compiled Form / Spatial Architecture):
//!      Static, declarative, frozen memory layouts, concrete denotations `[...]`, and invariant boundaries `<...>`.
//!   2. `.tape` (Interpreted Form / Temporal Execution Ribbon):
//!      Dynamic, sequential, time-bound rolls stepping across the tape head in real time.
//!   3. `Rust` (Silicon Host Substrate):
//!      Bedrock systems language defining opcodes, bitfields, and zero-cost native execution.
//!   This gear serves as the mechanical spindle turning Time (`.tape`) into Space (`.omni`) and Silicon (`Word64`).
//!
//! GAME DEV IDEOLOGY (THE STAGE INCEPTION & SIMULATION TICK):
//!   - Trigger Volumes & Collision Bounds: Every file resolution, syntax parse, partition slice, and seal
//!     is guarded by [`crate::cogs::tripwire::Tripwire`] collision volumes.
//!   - Flight Recorder: Step counts, instruction rolls, and physical offsets are logged to [`crate::diagnostics::logger::DiagnosticLogger`].
//!   - Respawn / Healing: Any syntax anomaly or invariant violation produces `#remediation_ready` telemetry
//!     for autonomous recovery by the [`crate::diagnostics::restorator::Restorator`].
//!
//! TRIPWIRE REGISTRY:
//!   - `TRIPWIRE_INPUT_RESOLVE`      (Resolution of input tape file across tracks via `resolve_track_path`)
//!   - `TRIPWIRE_FILETYPE_VALIDATION`(Enforcement of `.tape` or `.omni` extensions)
//!   - `TRIPWIRE_SYNTAX_TOKENIZATION`(Lexical analysis and token classification verification)
//!   - `TRIPWIRE_MEMORY_BOUNDS`      (Partition capacity and offset bounds verification)
//!   - `TRIPWIRE_COMMIT_INVARIANT`   (Assertion of final affirmative `+1:PROCEED` seal)
//!   - `TRIPWIRE_OUTPUT_SERIALIZE`   (File system permissions and disk serialization integrity)
//!
//! NAVIGATION GUIDE:
//!   - Block 1 (Lines 1-80): Manifest, Transpiler Triad Philosophy, Game Dev Ideology, Tripwire Registry.
//!   - Block 2 (Lines 81-220): Opening Block, Configurations (`AssembleConfig`), Context (`AssembleContext`), Enums.
//!   - Block 3 (Lines 221-420): Body Block & Execution Pipeline (`run_assemble_with_config`, `execute_assemble_pipeline`).
//!   - Block 4 (Lines 421+): Unit tests validating flag parsing, path resolution, and physical machine word output.

// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Scoped Imports, Environment Setup, Data Structures & Interface Definitions )
// ================================================================================

// --------------------------------------------------------------------------------
```

```rust
// 2.1. Scoped Namespace Ingestion & Multi-Platform Imports
// ---------------------------------------------------------------------------
use std::fmt;
use std::fs;
use std::path::PathBuf;

use crate::cogs::tripwire::{Tripwire, TripwireError};
use crate::core::filetype::resolve_track_path;
use crate::diagnostics::debugger::OmniDebugger;
use crate::diagnostics::logger::{DiagnosticLogger, FailpointType};
use crate::runtime::assembler::{AssembledTape, OmniAssembler};

// ---------------------------------------------------------------------------
// 2.2. Output Serialization Format Enumeration
// ---------------------------------------------------------------------------
/// Output format for the assembled process tape or spatial reel.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash, Default)]
pub enum AssembleFormat {
    /// Human-readable annotated machine listing (Default).
    #[default]
    Listing,
    /// Raw physical 64-bit machine words (Hex dump).
    Words,
    /// Structured JSON representation for tooling, hovercards, and IDEs.
    Json,
    /// Declarative 4-Block spatial architecture reel (`.omni`).
    Omni,
    /// Bare-metal x86 bootstrap assembly (`.asm`) for MilleniumOS.
    Asm,
    /// Canonical C module source code (`.c`).
    C,
    /// Canonical Lua script code (`.lua`).
    Lua,
}

impl AssembleFormat {
    /// Resolves a CLI format string into an `AssembleFormat` variant.
    pub fn from_str_name(s: &str) -> Option<Self> {
        match s.to_lowercase().as_str() {
            "listing" | "txt" => Some(Self::Listing),
            "words" | "hex" | "bin" => Some(Self::Words),
            "json" => Some(Self::Json),
            "omni" | "reel" => Some(Self::Omni),
            "asm" | "assembly" | "nasm" => Some(Self::Asm),
            "c" => Some(Self::C),
            "lua" => Some(Self::Lua),
            _ => None,
        }
    }

    /// Canonical lowercase format identifier string.
    pub fn as_str(&self) -> &'static str {
        match self {
            Self::Listing => "listing",
            Self::Words => "words",
            Self::Json => "json",
            Self::Omni => "omni",
            Self::Asm => "asm",
            Self::C => "c",
            Self::Lua => "lua",
        }
    }
}

impl fmt::Display for AssembleFormat {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        write!(f, "{}", self.as_str())
    }
}

// ---------------------------------------------------------------------------
// 2.3. Assembly Configuration Specification
// ---------------------------------------------------------------------------
/// Immutable configuration parameters for the assembly run.
#[derive(Debug, Clone, PartialEq, Eq)]
pub struct AssembleConfig {
    /// Relative or absolute path to the target process tape (`.tape`) or reel (`.omni`).
    pub input_path: PathBuf,
```

```
    /// Optional output file path for the assembled listing or binary artifact.
    pub output_path: Option<PathBuf>,
    /// Selected output serialization format.
    pub format: AssembleFormat,
    /// Enables verbose step-by-step diagnostic logging.
    pub verbose: bool,
    /// Strict mode: treat warnings or unspecified offsets as hard failpoints.
    pub strict: bool,
    /// Dry run: simulate lowering without writing output artifacts.
    pub dry_run: bool,
}

impl AssembleConfig {
    /// Constructs a default configuration for a given input path.
    pub fn new(input_path: impl Into<PathBuf>) -> Self {
        Self {
            input_path: input_path.into(),
            output_path: None,
            format: AssembleFormat::default(),
            verbose: false,
            strict: false,
            dry_run: false,
        }
    }

    /// Parses CLI arguments into an `AssembleConfig`.
    pub fn from_args(args: &[String]) -> Result<Self, String> {
        let mut input_path: Option<PathBuf> = None;
        let mut output_path: Option<PathBuf> = None;
        let mut format = AssembleFormat::Listing;
        let mut verbose = false;
        let mut strict = false;
        let mut dry_run = false;

        let mut idx = 0;
        while idx < args.len() {
            let arg = args[idx].as_str();
            match arg {
                "-o" | "--output" => {
                    idx += 1;
                    if idx >= args.len() {
                        return Err("FAILPOINT [MissingOutputArg]: Flag '--output' requires a file path
parameter".into());
                    }
                    output_path = Some(PathBuf::from(&args[idx]));
                }
                "-f" | "--format" => {
                    idx += 1;
                    if idx >= args.len() {
                        return Err("FAILPOINT [MissingFormatArg]: Flag '--format' requires a format name
(listing|words|json)".into());
                    }
                    let fmt_str = &args[idx];
                    format = AssembleFormat::from_str_name(fmt_str)
                        .ok_or_else(|| format!("FAILPOINT [InvalidFormat]: Unknown format '{fmt_str}' (expected: listing,
words, json)"))?;
                }
                "-v" | "--verbose" => {
                    verbose = true;
                }
                "-s" | "--strict" => {
                    strict = true;
                }
                "-n" | "--dry-run" => {
                    dry_run = true;
                }
                other => {
                    if !other.starts_with('-') && input_path.is_none() {
                        input_path = Some(PathBuf::from(other));
                    }
                }
            }
            idx += 1;
        }

        let input_path = input_path.ok_or_else(|| {
            "FAILPOINT [MissingInputPath]: No target tape file specified. Usage: omnicode assemble <file.tape> [--output
<PATH>] [--format <listing|words|json>]".to_string()
```

```
        })?;

        Ok(Self {
            input_path,
            output_path,
            format,
            verbose,
            strict,
            dry_run,
        })
    }

    /// Performs pre-flight verification, resolves paths across tracks, and constructs an `AssembleContext`.
    pub fn open(&self, logger: &DiagnosticLogger) -> Result<AssembleContext, TripwireError> {
        // Tripwire 1: Input file resolution across tracks
        let resolved = resolve_track_path(&self.input_path);
        Tripwire::assert_path_exists(
            logger,
            "TRIPWIRE_INPUT_RESOLVE",
            &resolved,
            "Target process tape or reel across Track roots",
        )?;

        // Tripwire 2: File extension check
        let ext = resolved.extension().and_then(|e| e.to_str()).unwrap_or("");
        if ext != "tape" && ext != "omni" {
            let msg = format!("File '{}' has unsupported extension '.{}' (expected .tape or .omni)", resolved.display(),
ext);
            return Err(Tripwire::trip(
                logger,
                "TRIPWIRE_FILETYPE_VALIDATION",
                FailpointType::SyntaxAnomaly,
                msg,
            ));
        }

        let debugger = OmniDebugger::new(logger.clone(), 100);
        let assembler = OmniAssembler::new(logger.clone(), debugger);

        Ok(AssembleContext {
            resolved_input: resolved,
            config: self.clone(),
            assembler,
            logger: logger.clone(),
        })
    }
}

// ---------------------------------------------------------------------------
// 2.4. Assembly Execution Context
// ---------------------------------------------------------------------------
/// Active runtime context holding resolved paths, tripwires, and the physical assembler.
#[derive(Debug)]
pub struct AssembleContext {
    /// Fully qualified path resolved across track roots.
    pub resolved_input: PathBuf,
    /// Immutable caller configuration.
    pub config: AssembleConfig,
    /// Physical assembler engine.
    pub assembler: OmniAssembler,
    /// Attached diagnostic logger for tripwires and telemetry.
    pub logger: DiagnosticLogger,
}

// ---------------------------------------------------------------------------
// 2.5. Initial Truth States & Equilibrium Defaults
// ---------------------------------------------------------------------------
/// Default output serialization format (human-readable annotated listing).
pub const DEFAULT_ASSEMBLE_FORMAT: AssembleFormat = AssembleFormat::Listing;
/// Baseline cell capacity reserved for unspecified memory partitions.
pub const DEFAULT_PARTITION_CELL_CAPACITY: usize = 64;
/// Maximum delimiter boundary nesting depth for structural invariant assertions.
pub const DEFAULT_ASSEMBLER_DEBUGGER_DEPTH: usize = 100;


// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Assembly Execution Pipeline, Output Serialization & Tripwire Sealing )
```

```rust
// ============================================================================

// ----------------------------------------------------------------------------
// 3.1. Public CLI Dispatchers
// ----------------------------------------------------------------------------
/// Legacy single-path entrypoint maintaining backwards compatibility with CLI dispatchers.
pub fn run_assemble(path: &str) {
    let config = AssembleConfig::new(path);
    if let Err(e) = run_assemble_with_config(config) {
        eprintln!("\x1b[1;31mAssembly Failed:\x1b[0m {e}");
        std::process::exit(1);
    }
}

/// Executes the modular assembly pipeline with full configuration, tripwires, and formatting.
pub fn run_assemble_with_config(config: AssembleConfig) -> Result<AssembledTape, TripwireError> {
    let logger = DiagnosticLogger::new(config.verbose);
    println!("\x1b[1;36mAssembling OmniCode Process Tape:\x1b[0m {}", config.input_path.display());

    let mut ctx = config.open(&logger)?;
    let assembled = execute_assemble_pipeline(&mut ctx)?;

    // Handle output formatting and serialization
    serialize_assembled_output(&assembled, &ctx.config, &logger)?;

    println!(
        "\x1b[1;32m✓ Assembly Successful: Machine Tape Sealed in {}\x1b[0m ({} rolls, {} symbols, {} words)",
        assembled.commit_status.macro_op(),
        assembled.instructions.len(),
        assembled.symbols.len(),
        assembled.instructions.len()
    );

    Ok(assembled)
}

// ----------------------------------------------------------------------------
// 3.2. Core Lowering Pipeline
// ----------------------------------------------------------------------------
/// Invokes the lowering engine within the tripwire collision hull.
pub fn execute_assemble_pipeline(ctx: &mut AssembleContext) -> Result<AssembledTape, TripwireError> {
    let tape_path = ctx.resolved_input.clone();

    let assembled = match ctx.assembler.assemble_file(&tape_path) {
        Ok(t) => t,
        Err(e) => {
            return Err(Tripwire::trip(
                &ctx.logger,
                "TRIPWIRE_SYNTAX_TOKENIZATION",
                FailpointType::SyntaxAnomaly,
                format!("Tape assembly lowered into failpoint: {e}"),
            ));
        }
    };

    // Assert final commit status invariant
    Tripwire::assert_quad_state_proceed(
        &ctx.logger,
        "TRIPWIRE_COMMIT_INVARIANT",
        assembled.commit_status,
        "Process tape must conclude with 'commit_status [ PROCEED ]'",
    )?;

    Ok(assembled)
}

// ----------------------------------------------------------------------------
// 3.3. Output Serialization & Formatting
// ----------------------------------------------------------------------------
/// Renders or writes the assembled tape to disk or stdout according to the chosen format.
///
/// Consumes the universal serialization methods ([`AssembledTape::format_listing`],
/// [`AssembledTape::format_words`], [`AssembledTape::format_json`], [`AssembledTape::format_omni`])
/// extracted from the runtime lowering engine.
pub fn serialize_assembled_output(
    assembled: &AssembledTape,
    config: &AssembleConfig,
    logger: &DiagnosticLogger,
```

```
) -> Result<(), TripwireError> {
    let rendered = match config.format {
        AssembleFormat::Listing => assembled.format_listing(),
        AssembleFormat::Words => assembled.format_words(),
        AssembleFormat::Json => assembled.format_json(),
        AssembleFormat::Omni => assembled.format_omni(),
        AssembleFormat::Asm => assembled.format_asm(),
        AssembleFormat::C => assembled.format_c(),
        AssembleFormat::Lua => assembled.format_lua(),
    };

    if let Some(ref out_path) = config.output_path {
        if !config.dry_run {
            if let Err(e) = fs::write(out_path, &rendered) {
                return Err(Tripwire::trip(
                    logger,
                    "TRIPWIRE_OUTPUT_SERIALIZE",
                    FailpointType::SyntaxAnomaly,
                    format!("Failed to write assembled output to '{}': {e}", out_path.display()),
                ));
            }
            println!("\x1b[1;32m✓ Output Artifact Written:\x1b[0m {}", out_path.display());
        } else {
            println!("\x1b[1;33m[Dry Run] Output serialization skipped for:\x1b[0m {}", out_path.display());
        }
    } else {
        println!("{rendered}");
    }

    Ok(())
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Baton Pass Contract, Unit Tests & Verification Proof )
// ============================================================================

// ----------------------------------------------------------------------------
// 4.1. The Baton Pass Contract
// ----------------------------------------------------------------------------
// BATON PASS CONTRACT:
// 1. `AssembleConfig` parses and validates user CLI flags without side effects.
// 2. `open()` verifies that the process tape exists across Track roots and establishes tripwire bounds.
// 3. `execute_assemble_pipeline()` drives lowering into `OmniAssembler`, verifying `MachineOp`, registers, and `Word64`.
// 4. `serialize_assembled_output()` formats or writes the output, yielding a sealed `AssembledTape`.
// 5. Downstream dispatchers in `main.rs` receive verified artifacts ready for scheduling or execution.

#[cfg(test)]
mod tests {
    use super::*;
    use crate::core::ternary::QuadState;

    #[test]
    fn test_assemble_config_default_and_new() {
        let config = AssembleConfig::new("lib/kernel/boot.tape");
        assert_eq!(config.input_path, PathBuf::from("lib/kernel/boot.tape"));
        assert_eq!(config.format, AssembleFormat::Listing);
        assert!(!config.verbose);
        assert!(!config.strict);
        assert!(!config.dry_run);
        assert_eq!(config.output_path, None);
    }

    #[test]
    fn test_assemble_config_argument_parsing() {
        let args = vec![
            "lexicon/operators/polarity.tape".to_string(),
            "--output".to_string(),
            "/tmp/polarity.asm".to_string(),
            "--format".to_string(),
            "words".to_string(),
            "--verbose".to_string(),
            "--dry-run".to_string(),
        ];
        let config = AssembleConfig::from_args(&args).expect("Parsing CLI args");
        assert_eq!(config.input_path, PathBuf::from("lexicon/operators/polarity.tape"));
        assert_eq!(config.output_path, Some(PathBuf::from("/tmp/polarity.asm")));
```

```
        assert_eq!(config.format, AssembleFormat::Words);
        assert!(config.verbose);
        assert!(config.dry_run);
    }

    #[test]
    fn test_assemble_config_missing_input_fails_gracefully() {
        let args: Vec<String> = vec!["--verbose".to_string()];
        let err = AssembleConfig::from_args(&args).unwrap_err();
        assert!(err.contains("MissingInputPath"));
    }

    #[test]
    fn test_assemble_format_conversions() {
        assert_eq!(AssembleFormat::from_str_name("listing"), Some(AssembleFormat::Listing));
        assert_eq!(AssembleFormat::from_str_name("words"), Some(AssembleFormat::Words));
        assert_eq!(AssembleFormat::from_str_name("hex"), Some(AssembleFormat::Words));
        assert_eq!(AssembleFormat::from_str_name("json"), Some(AssembleFormat::Json));
        assert_eq!(AssembleFormat::from_str_name("omni"), Some(AssembleFormat::Omni));
        assert_eq!(AssembleFormat::from_str_name("reel"), Some(AssembleFormat::Omni));
        assert_eq!(AssembleFormat::from_str_name("unknown"), None);
    }

    #[test]
    fn test_assemble_pipeline_lowers_boot_tape_and_transpiles_to_omni() {
        let tape_path = resolve_track_path("lib/kernel/boot.tape");
        if tape_path.exists() {
            let config = AssembleConfig {
                input_path: tape_path,
                output_path: None,
                format: AssembleFormat::Omni,
                verbose: false,
                strict: false,
                dry_run: true,
            };
            let logger = DiagnosticLogger::new(false);
            let mut ctx = config.open(&logger).expect("Opening assemble context");
            let assembled = execute_assemble_pipeline(&mut ctx).expect("Executing assemble pipeline");

            let omni_output = assembled.format_omni();
            assert!(omni_output.contains("Transpiled Spatial Reel"));
            assert!(omni_output.contains("BLOCK 1: METADATA BLOCK"));
            assert!(omni_output.contains("BLOCK 2: OPENING BLOCK"));
            assert!(omni_output.contains("BLOCK 3: BODY BLOCK"));
            assert!(omni_output.contains("BLOCK 4: CLOSING BLOCK"));
        }
    }

    #[test]
    fn test_assemble_pipeline_lowers_boot_tape_and_emits_words() {
        let tape_path = resolve_track_path("lib/kernel/boot.tape");
        if tape_path.exists() {
            let config = AssembleConfig {
                input_path: tape_path,
                output_path: None,
                format: AssembleFormat::Words,
                verbose: false,
                strict: false,
                dry_run: true,
            };
            let logger = DiagnosticLogger::new(false);
            let mut ctx = config.open(&logger).expect("Opening assemble context");
            let assembled = execute_assemble_pipeline(&mut ctx).expect("Executing assemble pipeline");

            assert_eq!(assembled.commit_status, QuadState::Proceed);
            assert!(!assembled.instructions.is_empty());

            // Assert that instructions carry real physical Word64 machine words
            for inst in &assembled.instructions {
                assert_ne!(inst.word.raw, 0xFFFFFFFF_FFFFFFFF);
            }
        }
    }

    #[test]
    fn test_assemble_preflight_missing_file_trips() {
        let config = AssembleConfig::new("nonexistent_directory/missing.tape");
        let logger = DiagnosticLogger::new(false);
```

```
        let err = config.open(&logger).unwrap_err();
        assert!(err.to_string().contains("TRIPWIRE_INPUT_RESOLVE"));
    }

    #[test]
    fn test_assemble_preflight_invalid_extension_trips() {
        let config = AssembleConfig::new("Cargo.toml");
        let logger = DiagnosticLogger::new(false);
        let err = config.open(&logger).unwrap_err();
        assert!(err.to_string().contains("TRIPWIRE_FILETYPE_VALIDATION"));
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/cli/commands/boot.rs RS 776 LINES 3856 WORDS 39.0 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Machine Manifest, Scheduling Priority, Dependency Contract & Tripwire Registry )
// ============================================================================
//! MODULE:              omnicode::cli::commands::boot
//! IDENTITY:            Bare-Metal Multi-Architecture Boot Gear
//! NATURE:              Cold-Start Machine Inception & Silicon Hardware Simulation Driver
//! VERSION:             0.3.0
//! CREATED:             2026-10-11
//! LAST_SEALED:         2026-10-11
//! AUTHOR:              CreativeWorkzStudio LLC / ProfessorSeanEX
//! COVENANT:            Public Domain / MIT
//!
//! SCHEDULER:
//!   TRACK_PRIMARY:     <TRACK 1> : {Host Engine & Virtual Machine}
//!   TRACKS_TOUCHED:    [ <TRACK 0> : {Silicon & Bare-Metal Kernel}, <TRACK 1>, <TRACK 2> : {Engine Runtime & SVO} ]
//!   PRIORITY:          TaskPriority::High
//!   CHANNEL:           Track::Kernel
//!
//! CONTRACT / WHO-WHAT-WHERE-WHY-HOW:
//!   WHO:               OmniCode Host Orchestrator Engine & Machine Inception Driver
//!   WHAT:              Assemble bare-metal operating system kernels in Track 0 and launch
//!                      the QEMU hypervisor across BIOS, UEFI, and Multiboot architectures.
//!   WHERE:             `<TRACK 0>/kernel` tree -> host QEMU hypervisor -> COM1 / VGA silicon endpoints
//!   WHEN:              Invoked via CLI command `omnicode boot [--bios|--uefi|--multiboot] [--gui] [--ovmf <PATH>]`
//!   WHY:               Verify silicon-level self-sufficiency, hardware invariants, and balanced-ternary machine
bootstrap.
//!   HOW:               Balanced Ternary (+1:PROCEED clean exit, -1:ROLLBACK trapped error, 0:AWAIT execution running)
//!
//! THE "IN-WAITING" MULTI-OS SYMBIOTIC MESH:
//!   OmniCode is fundamentally an autonomous bare-metal Operating System and Balanced-Ternary computing
//!   architecture. However, until custom silicon machines are ubiquitous, OmniCode incubates comfortably
//!   inside existing host operating systems (Linux, macOS, Windows).
//!   This gear delegates host environment discovery to [`crate::cogs::platform::HostPlatform`], ensuring:
//!   - Dynamic selection of hypervisor binaries (`qemu-system-x86_64` vs `qemu-system-x86_64.exe`).
//!   - Dynamic discovery of UEFI OVMF firmware blobs across Debian, Arch, Fedora, NixOS, macOS Homebrew, and Windows.
//!   - Dynamic probing of display servers to avoid graphical window crashes in headless containers or SSH sessions.
//!
//! GAME DEV IDEOLOGY (THE STAGE INCEPTION & SIMULATION TICK):
//!   In modern game engine architecture (e.g., Unreal, Unity, Godot):
//!   - Level Loading / Inception: Setting up world geometry, shaders, and player spawn points before rendering.
//!   - Collision Volumes & Triggers: Spatial boundaries that fire events when crossed or violated.
//!   - Flight Recorder & Telemetry HUD: Frame-by-frame debug logging with nanosecond timestamps.
//!   - Respawn / Immune Recovery: Resetting player coordinates or healing scene state after a collision failpoint.
//!   In OmniCode Bare-Metal Boot:
//!   - Stage Inception: `execute_kernel_pipeline` compiles the bare-metal kernel and binds MMIO registers.
//!   - Tripwires: Invariant collision sensors (`Tripwire::assert_*`) wrapping every file access, compiler invocation,
//!     and hypervisor process launch.
//!   - Flight Recorder: [`DiagnosticLogger`] and [`OmniDebugger`] track step counts, register cognitive notes,
//!     and serialize episodic scrolls.
//!   - Respawn / Healing: Any tripped invariant produces a [`FixSuggestion`] and `#remediation_ready` telemetry
//!     for autonomous recovery by the [`crate::diagnostics::restorator::Restorator`].
//!
//! TOUCHES / FILESYSTEM FOOTPRINT:
//!   - EXECUTABLE:      `<TRACK 0>/kernel/build_all_kernels.sh`
//!   - ARTIFACT:        `<TRACK 0>/kernel/omnicode_bios.img` (512-byte MBR boot sector)
//!   - ARTIFACT:        `<TRACK 0>/kernel/esp/EFI/BOOT/BOOTX64.EFI` (UEFI PE32+ application)
//!   - ARTIFACT:        `<TRACK 0>/kernel/omnicode_multiboot.elf` (ELF multiboot kernel)
//!   - FIRMWARE:        OVMF UEFI Code image (probed from host system via `HostPlatform`)
//!
//! TOUCHES / SILICON HARDWARE & MMIO ADDRESSES:
//!   - COM1 Serial Port (I/O Port `0x3F8`): Serial console telemetry output at 115200 baud 8N1.
//!   - VGA Text Buffer Base (Memory Address `0xB8000`): 80x25 monochrome/color text screen buffer.
//!   - Real Mode Reset Vector (Physical Memory `0x7C00`): IBM PC MBR bootstrap entrypoint.
//!
//! REQUIRES / HOST DEPENDENCIES:
//!   - `qemu-system-x86_64` (virtual machine emulator & silicon hypervisor)
//!   - `bash` (bare-metal kernel build pipeline driver)
//!   - `nasm` (16-bit real mode and multiboot x86 assembler)
//!   - `clang` + `lld-link` (x86_64-unknown-windows UEFI PE32+ compiler & linker)
//!   - `ld` (elf_i386 multiboot linker)
//!
//! TRIPWIRE REGISTRY:
//!   - `TRIPWIRE_KERNEL_BUILD_SCRIPT` (Track 0 build script accessibility and readability)
```

```
//!   - `TRIPWIRE_KERNEL_COMPILATION`  (Kernel compiler pipeline exit status code)
//!   - `TRIPWIRE_IMAGE_RESOLVE`       (Generated boot artifact existence after assembly)
//!   - `TRIPWIRE_HYPERVISOR_PATH`     (Availability of hypervisor binary on host PATH)
//!   - `TRIPWIRE_FIRMWARE_RESOLVE`    (Resolution of UEFI OVMF firmware blob)
//!   - `TRIPWIRE_DISPLAY_SERVER`      (Assertion of host display server when GUI mode is active)
//!   - `TRIPWIRE_QEMU_LAUNCH`         (Hypervisor execution status code and crash traps)
//!
//! NAVIGATION GUIDE (HOW TO NAVIGATE AND EXTEND THIS MODULE AS THE CODE GROWS):
//!   - Block 1 (Lines 1-95): Manifest, Multi-OS In-Waiting Philosophy, Game Dev Analogy, Tripwire Registry.
//!   - Block 2 (Lines 96-260): Opening Block, Domain Typology, Configuration & Equilibrium Constants.
//!     * To add a new boot architecture (e.g. RISC-V `RiscV64`): add a variant to `BootArch` in Section 2.2.
//!     * To inspect how options are parsed from CLI tokens: examine `BootConfig::from_args` in Section 2.3.
//!     * To view pre-flight invariant certification: examine `BootConfig::open` in Section 2.3.
//!     * To check silicon MMIO addresses: review equilibrium constants in Section 2.4.
//!   - Block 3 (Lines 261-530): Body Block & Bare-Metal Simulation Tick.
//!     * 3.1: Public dispatchers (`run_boot`, `run_boot_with_config`).
//!     * 3.2: Kernel compilation pipeline and build script execution (`execute_kernel_pipeline`).
//!     * 3.3: Silicon MMIO & hypervisor command synthesis (`synthesize_hypervisor_command`).
//!     * 3.4: Machine execution loop and telemetry sealing (`execute_boot_pipeline`, `execute_boot_machine`).
//!   - Block 4 (Lines 531+): Unit tests validating architecture names, argument parsing, command synthesis, and PATH
lookups.

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Scoped Imports, Environment Setup, Data Structures & Interface Definitions )
// ============================================================================

// ----------------------------------------------------------------------------
// 2.1. Scoped Namespace Ingestion & Multi-Platform Imports
// ----------------------------------------------------------------------------
use std::path::{Path, PathBuf};
use std::process::Command;

use crate::cogs::platform::HostPlatform;
use crate::cogs::tripwire::{Tripwire, TripwireError};
use crate::core::filetype::resolve_track_path;
use crate::core::ternary::QuadState;
use crate::diagnostics::debugger::OmniDebugger;
use crate::diagnostics::logger::DiagnosticLogger;

// ----------------------------------------------------------------------------
// 2.2. Domain Typology & Architectural Target Definitions
// ----------------------------------------------------------------------------
/// Supported bare-metal boot target architectures.
///
/// Each architecture represents a discrete physical execution plane into which
/// OmniCode can materialize directly from cold power-on.
#[derive(Debug, Clone, Copy, PartialEq, Eq)]
pub enum BootArch {
    /// 16-Bit Real Mode MBR (512-byte sector loaded at physical address `0x7C00`).
    /// Minimalist, self-contained hardware bootstrap with BIOS INT 10h / INT 13h / INT 16h.
    Bios,

    /// 64-Bit Native UEFI Long Mode (PE32+ EFI Application loaded by firmware boot manager).
    /// Modern hardware standard with graphical GOP framebuffer and EFI System Table.
    Uefi,

    /// 32-Bit Direct Kernel Handshake via Multiboot Specification (ELF executable).
    /// Used for direct hypervisor injection (QEMU `-kernel`, GRUB, Xen, KVM).
    Multiboot,
}

impl BootArch {
    /// Human and machine readable description of the architecture target.
    pub fn display_name(&self) -> &'static str {
        match self {
            BootArch::Bios => "Legacy BIOS MBR (16-Bit Real Mode -> 512-Byte Boot Sector)",
            BootArch::Uefi => "Modern UEFI 64-Bit Long Mode (PE32+ EFI Application via OVMF)",
            BootArch::Multiboot => "Direct Kernel Multiboot/GRUB (ELF Hypervisor Handshake)",
        }
    }

    /// Expected target artifact path relative to `<TRACK 0>/kernel`.
    pub fn target_artifact_relpath(&self) -> &'static str {
        match self {
            BootArch::Bios => "kernel/omnicode_bios.img",
            BootArch::Uefi => "kernel/esp",
            BootArch::Multiboot => "kernel/omnicode_multiboot.elf",
```

```
        }
    }
}

// ---------------------------------------------------------------------------
// 2.3. Boot Configuration Specification & Options Matrix
// ---------------------------------------------------------------------------
/// Concrete execution configuration for the bare-metal machine inception.
#[derive(Debug, Clone)]
pub struct BootConfig {
    /// Target execution architecture (BIOS, UEFI, or Multiboot).
    pub arch: BootArch,
    /// Whether to open an emulated graphical window or run headless over COM1 serial.
    pub graphical: bool,
    /// Host operating system plane under which execution is launched.
    pub host_platform: HostPlatform,
    /// Optional custom override path for UEFI OVMF firmware image.
    pub custom_ovmf: Option<PathBuf>,
}

/// Fully resolved, verified execution context prepared by the Opening Block.
///
/// Acts as the immutable "Setup Frame" handed to the Body Block's simulation tick.
/// Contains certified file paths, armed diagnostic sensors, and pre-resolved host binaries.
#[derive(Debug, Clone)]
pub struct BootContext {
    /// Initial boot configuration parameters.
    pub config: BootConfig,
    /// Attached telemetry logger for recording events and failpoints.
    pub logger: DiagnosticLogger,
    /// Interactive debugger tracking step count and QuadState transitions.
    pub debugger: OmniDebugger,
    /// Verified absolute path to `<TRACK 0>/kernel/build_all_kernels.sh`.
    pub build_script: PathBuf,
    /// Target boot artifact (MBR image, ESP directory, or ELF executable).
    pub boot_artifact: PathBuf,
    /// Pre-resolved UEFI OVMF firmware blob (if UEFI mode is selected).
    pub ovmf_firmware: Option<PathBuf>,
    /// Hypervisor executable name appropriate for the host platform.
    pub hypervisor_binary: &'static str,
}

impl BootConfig {
    /// Constructs a standard boot configuration with platform auto-detection.
    pub fn new(arch: BootArch, graphical: bool) -> Self {
        Self {
            arch,
            graphical,
            host_platform: HostPlatform::current(),
            custom_ovmf: None,
        }
    }

    /// Parses raw command-line tokens into a validated [`BootConfig`].
    pub fn from_args(args: &[String]) -> Self {
        let arch = if args.iter().any(|a| a == "--uefi" || a == "-u") {
            BootArch::Uefi
        } else if args.iter().any(|a| a == "--multiboot" || a == "-m" || a == "--direct") {
            BootArch::Multiboot
        } else {
            BootArch::Bios
        };

        let graphical = args.iter().any(|a| a == "--gui" || a == "-g" || a == "--window");

        let custom_ovmf = args.iter().position(|a| a == "--ovmf" || a == "-b").and_then(|idx| {
            args.get(idx + 1).map(PathBuf::from)
        });

        Self {
            arch,
            graphical,
            host_platform: HostPlatform::current(),
            custom_ovmf,
        }
    }

    /// Prepares and certifies the execution context before the Body touches the metal.
```

```
    ///
    /// # Precondition Tripwires & Environmental Probes:
    /// - Asserts that the Track 0 kernel build script is reachable on disk.
    /// - Asserts that the target boot artifact path resolves.
    /// - Pre-resolves firmware candidate and platform hypervisor binary.
    /// - Inspects host display server if graphical GUI window was requested.
    /// - Initializes an attached [`OmniDebugger`] to monitor step invariants.
    pub fn open(&self, logger: DiagnosticLogger) -> Result<BootContext, TripwireError> {
        let debugger = OmniDebugger::new(logger.clone(), 10);
        let build_script_path = resolve_track_path("kernel/build_all_kernels.sh");
        let build_script = Tripwire::assert_path_exists(
            &logger,
            "BOOT",
            build_script_path,
            "Track 0 kernel build pipeline script",
        )?;

        let boot_artifact = resolve_track_path(self.arch.target_artifact_relpath());

        // Probe host display environment if GUI window requested
        if self.graphical && !self.host_platform.has_display_server() {
            logger.record_ai_observation(
                "GUI_DISPLAY_HEADLESS",
                "Graphical window requested but host display server not detected",
                "Host environment lacks active DISPLAY or WAYLAND_DISPLAY session; window spawn may fail",
                ["gui", "display", "headless", "observation"].as_slice(),
                None,
            );
        }

        let ovmf_firmware = if self.arch == BootArch::Uefi {
            if let Some(custom) = &self.custom_ovmf {
                Some(Tripwire::assert_path_exists(&logger, "BOOT", custom, "Custom OVMF firmware")?)
            } else {
                self.host_platform.find_ovmf_firmware()
            }
        } else {
            None
        };

        let hypervisor_binary = self.host_platform.hypervisor_binary();

        Ok(BootContext {
            config: self.clone(),
            logger,
            debugger,
            build_script,
            boot_artifact,
            ovmf_firmware,
            hypervisor_binary,
        })
    }
}

// ---------------------------------------------------------------------------
// 2.4. Initial Truth States & Equilibrium Defaults
// ---------------------------------------------------------------------------
/// Canonical default boot architecture for minimal real-mode baseline.
pub const DEFAULT_BOOT_ARCH: BootArch = BootArch::Bios;

/// Default display mode: headless COM1 serial terminal output for pure dataflow.
pub const DEFAULT_GRAPHICAL_MODE: bool = false;

/// Real-mode bootstrap reset vector base in silicon RAM (`0x7C00`).
pub const REAL_MODE_BOOT_VECTOR: u64 = 0x7C00;

/// Standard VGA 80x25 text framebuffer memory-mapped base address (`0xB8000`).
pub const VGA_TEXT_FRAMEBUFFER_BASE: u64 = 0xB8000;

/// Standard IBM PC COM1 serial communications port I/O base address (`0x3F8`).
pub const COM1_SERIAL_IO_BASE: u16 = 0x3F8;

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Kernel Compilation, Inception Tripwires & QEMU Execution Engine )
// ============================================================================

// ---------------------------------------------------------------------------
```

```rust
// 3.1. Public Dispatcher & Context Resolution
// ---------------------------------------------------------------------------
/// Builds the target kernels in Track 0 and launches the virtual machine in QEMU.
///
/// # Game Dev Loop & Cybernetic Architecture:
/// Functions as the primary command-line engine driver. Resolves ambient hardware
/// parameters, constructs the diagnostic logger and debugger sensors, and invokes
/// the self-healing execution pipeline.
///
/// # Returns
/// - `Ok(QuadState::Proceed)`: Hypervisor session completed cleanly without fatal invariant breach.
/// - `Err(TripwireError)`: Precondition, compilation, or hypervisor tripwire tripped with `-1:ROLLBACK`.
pub fn run_boot(arch: BootArch, graphical: bool) -> Result<QuadState, TripwireError> {
    let config = BootConfig::new(arch, graphical);
    run_boot_with_config(config)
}

/// Executes boot inception under a customized [`BootConfig`].
pub fn run_boot_with_config(config: BootConfig) -> Result<QuadState, TripwireError> {
    let logger = DiagnosticLogger::new(false);
    let ctx = match config.open(logger) {
        Ok(c) => c,
        Err(e) => {
            eprintln!("\x1b[1;31m[!] Precondition Tripwire Tripped during BootContext Open:\x1b[0m {e}");
            return Err(e);
        }
    };

    execute_boot_pipeline(ctx)
}

// ---------------------------------------------------------------------------
// 3.2. Kernel Compilation Pipeline & Build Tripwires
// ---------------------------------------------------------------------------
/// Orchestrates the execution of the Track 0 bare-metal kernel build pipeline.
///
/// # Silicon & Assembly Invariants:
/// - Reaches into `<TRACK 0>/kernel/build_all_kernels.sh`.
/// - Assembles 16-bit real-mode bootstrap vector (`0x7C00`) via NASM.
/// - Compiles 64-bit UEFI PE32+ application with Clang/LLD targeting GOP framebuffer.
/// - Links 32-bit ELF multiboot header with GNU LD for hypervisor direct handshakes.
///
/// # Sensory Tripwires:
/// - `TRIPWIRE_KERNEL_BUILD_SCRIPT`: Asserts build script is readable and executable.
/// - `TRIPWIRE_KERNEL_COMPILATION`: Asserts zero exit code from compilation subprocess.
/// - `TRIPWIRE_IMAGE_RESOLVE`: Asserts that target binary artifact exists on disk after assembly.
pub fn execute_kernel_pipeline(ctx: &mut BootContext) -> Result<(), TripwireError> {
    ctx.logger.log("KERNEL_PIPELINE", "Initiating Track 0 Bare-Metal Kernel Build Pipeline...");
    ctx.debugger.inspect_state(QuadState::Await, "kernel_build_started");
    ctx.debugger.step_count += 1;

    // 0. Transpile MilleniumOS boot architecture directly from OmniCode source reel
    let boot_omni_path = resolve_track_path("lib/kernel/boot.omni");
    if boot_omni_path.exists() {
        if let Ok(omni_content) = std::fs::read_to_string(&boot_omni_path) {
            if let Ok(generated_asm) = crate::runtime::assembler::transpile_omni_to_asm(&omni_content) {
                let bios_asm_path = resolve_track_path("kernel/bios/boot.asm");
                let _ = std::fs::write(&bios_asm_path, &generated_asm);
                let root_asm_path = resolve_track_path("kernel/boot.asm");
                let _ = std::fs::write(&root_asm_path, &generated_asm);
                ctx.logger.log("KERNEL_PIPELINE", "Transpiled lib/kernel/boot.omni -> bios/boot.asm for MilleniumOS");
            }
        }
    }

    let script_dir = ctx.build_script.parent().unwrap_or_else(|| Path::new("."));
    ctx.logger.log(
        "KERNEL_PIPELINE",
        format!("Executing driver script in directory: {:?}", script_dir),
    );

    println!("\x1b[1;34m[i] Executing bare-metal kernel build pipeline in {:?}...\x1b[0m", script_dir);
    let build_status = Command::new("bash")
        .arg(ctx.build_script.file_name().unwrap_or_default())
        .current_dir(script_dir)
        .status();

    match Tripwire::assert_command_success(&ctx.logger, "KERNEL_PIPELINE", build_status, "Kernel Build Pipeline") {
```

```
        Ok(()) => {
            println!("\x1b[1;32m✓ Track 0 Bare-Metal Kernel Pipeline Built Successfully\x1b[0m");
            ctx.logger.log("KERNEL_PIPELINE", "Kernel compilation subprocess returned exit code 0");
            ctx.logger.record_ai_observation(
                "KERNEL_BUILD_SUCCESS",
                "Bare-metal kernel compilation passed",
                "Track 0 build script executed cleanly with all artifacts generated",
                ["kernel", "build", "silicon", "verified"].as_slice(),
                Some("build_all_kernels.sh"),
            );
        }
        Err(e) => {
            ctx.debugger.inspect_state(QuadState::Rollback, "kernel_build_failed");
            ctx.logger.record_ai_observation(
                "KERNEL_BUILD_FAILED",
                "Bare-metal kernel compilation failed",
                &e.message,
                ["kernel", "build_failure", "rollback"].as_slice(),
                Some("build_all_kernels.sh"),
            );
            return Err(e);
        }
    }

    // Verify generated artifact presence post-build
    Tripwire::assert_path_exists(
        &ctx.logger,
        "KERNEL_PIPELINE",
        &ctx.boot_artifact,
        "Post-compilation target boot artifact",
    )?;

    ctx.debugger.inspect_state(QuadState::Proceed, "kernel_artifact_verified");
    Ok(())
}

// ---------------------------------------------------------------------------
// 3.3. Hypervisor Command Synthesis & Parameter Mapping
// ---------------------------------------------------------------------------
/// Constructs the platform-specific hypervisor launch command with exact MMIO,
/// serial redirection, and drive geometry parameters.
///
/// # Hardware & Architecture Mapping (Simulating Motherboard Buses):
/// - **BIOS**: Maps raw 512-byte image as primary boot drive (`format=raw,file=...`).
/// - **UEFI**: Maps OVMF firmware blob (`-bios ...`) and mounts ESP FAT partition.
/// - **Multiboot**: Direct hypervisor injection via QEMU `-kernel` flag.
/// - **Serial & VGA**: Multiplexes COM1 (`0x3F8`) and VGA text buffer (`0xB8000`)
///   to host standard I/O streams for headless evaluation or GUI windows.
///
/// # Sensory Tripwires:
/// - `TRIPWIRE_HYPERVISOR_PATH`: Asserts hypervisor binary (`qemu-system-x86_64`) exists on PATH.
/// - `TRIPWIRE_FIRMWARE_RESOLVE`: Asserts UEFI OVMF firmware blob exists when UEFI mode is active.
pub fn synthesize_hypervisor_command(ctx: &BootContext) -> Result<Command, TripwireError> {
    ctx.logger.log("HYPERVISOR", format!("Synthesizing launch command for {}", ctx.hypervisor_binary));

    // Assert that the hypervisor binary is present on host system PATH
    Tripwire::assert_binary_available(&ctx.logger, "HYPERVISOR", ctx.hypervisor_binary)?;

    let mut cmd = Command::new(ctx.hypervisor_binary);

    match ctx.config.arch {
        BootArch::Bios => {
            ctx.logger.log("HYPERVISOR", format!("Configuring BIOS MBR raw drive: {:?}", ctx.boot_artifact));
            let path_str = ctx.boot_artifact.to_string_lossy();
            let file_arg = if path_str.starts_with('/') || path_str.starts_with("./") {
                path_str.into_owned()
            } else {
                format!("./{path_str}")
            };
            cmd.arg("-drive").arg(format!("format=raw,file={file_arg}"));
        }
        BootArch::Uefi => {
            let ovmf = if let Some(ref fw) = ctx.ovmf_firmware {
                fw.to_string_lossy().into_owned()
            } else {
                let default_ovmf = "/usr/share/qemu/OVMF.fd".to_string();
                ctx.logger.log("HYPERVISOR", format!("Using fallback OVMF path: {}", default_ovmf));
                default_ovmf
```

```
            };
            ctx.logger.log("HYPERVISOR", format!("Configuring UEFI with OVMF firmware: {}", ovmf));
            cmd.arg("-bios").arg(ovmf);

            let esp_dir = if ctx.boot_artifact.to_string_lossy().contains(':') {
                let staged = PathBuf::from("target/esp");
                let staged_boot = staged.join("EFI").join("BOOT");
                let _ = std::fs::create_dir_all(&staged_boot);
                let efi_bin = ctx.boot_artifact.join("EFI").join("BOOT").join("BOOTX64.EFI");
                if efi_bin.exists() {
                    let _ = std::fs::copy(&efi_bin, staged_boot.join("BOOTX64.EFI"));
                }
                staged.to_string_lossy().into_owned()
            } else {
                ctx.boot_artifact.to_string_lossy().into_owned()
            };
            cmd.arg("-drive").arg(format!("file=fat:rw:{esp_dir},format=raw"));
            cmd.arg("-net").arg("none");
        }
        BootArch::Multiboot => {
            ctx.logger.log("HYPERVISOR", format!("Configuring direct multiboot ELF injection: {:?}", ctx.boot_artifact));
            let path_str = ctx.boot_artifact.to_string_lossy();
            let kernel_arg = if path_str.starts_with('/') || path_str.starts_with("./") {
                path_str.into_owned()
            } else {
                format!("./{path_str}")
            };
            cmd.arg("-kernel").arg(kernel_arg);
        }
    }

    if ctx.config.graphical {
        ctx.logger.log("HYPERVISOR", "Display mode: Graphical Window with COM1 serial on stdio");
        cmd.arg("-serial").arg("stdio");
    } else {
        ctx.logger.log("HYPERVISOR", "Display mode: Headless with COM1 serial on stdio (display=none)");
        cmd.arg("-display").arg("none").arg("-serial").arg("stdio");
    }

    Ok(cmd)
}

// ---------------------------------------------------------------------------
// 3.4. Machine Execution Loop, Tripwire Interception & Telemetry Seal
// ---------------------------------------------------------------------------
/// Executes the complete bare-metal machine inception pipeline.
///
/// # Game Dev Loop Rationale:
/// Directly executes the simulation tick of the host engine:
/// 1. Emits visual inception banner with machine metadata.
/// 2. Executes kernel pipeline wrapped in build tripwires.
/// 3. Synthesizes hypervisor launch command with hardware mappings.
/// 4. Executes virtual machine, trapping non-zero exit codes.
/// 5. Inscribes telemetry into [`DiagnosticLogger`] and [`OmniDebugger`] for the
[`crate::diagnostics::restorator::Restorator`].
pub fn execute_boot_pipeline(mut ctx: BootContext) -> Result<QuadState, TripwireError> {
    println!("\x1b[1;36m================================================================================\x1b[0m");
    println!("\x1b[1;36m  OmniCode OS: Bare-Metal Multi-Architecture Machine Inception               \x1b[0m");
    println!("\x1b[1;36m  Mode: {}\x1b[0m", ctx.config.arch.display_name());
    println!("\x1b[1;36m  Host: {}\x1b[0m", ctx.config.host_platform.display_name());
    println!("\x1b[1;36m================================================================================\x1b[0m\n");

    ctx.logger.log(
        "BOOT",
        format!(
            "Beginning Machine Inception [{}] on [{}]",
            ctx.config.arch.display_name(),
            ctx.config.host_platform.display_name()
        ),
    );
    ctx.debugger.inspect_state(QuadState::Await, "machine_inception_begun");
    ctx.debugger.step_count += 1;

    // 1. Execute Bare-Metal Kernel Pipeline in Track 0
    execute_kernel_pipeline(&mut ctx)?;

    // 2. Configure Machine Emulator Command
    let mut cmd = synthesize_hypervisor_command(&ctx)?;
```

```
    if ctx.config.graphical {
        println!("\x1b[1;36m[i] Launching graphical virtual machine display with serial on stdio...\x1b[0m");
    } else {
        println!("\x1b[1;36m[i] Launching headless terminal machine with COM1 serial on stdio...\x1b[0m");
    }

    // 3. Launch Virtual Machine Inception
    ctx.logger.log("BOOT", format!("Spawning hypervisor child process: {:?}", cmd));
    ctx.debugger.inspect_state(QuadState::Await, "hypervisor_spawning");
    ctx.debugger.step_count += 1;

    let run_status = cmd.status();
    match Tripwire::assert_command_success(&ctx.logger, "BOOT", run_status, ctx.hypervisor_binary) {
        Ok(()) => {
            println!("\n\x1b[1;32m✓ QEMU Machine Inception Terminated Cleanly (+1:PROCEED)\x1b[0m");
            ctx.logger.log("BOOT", "Virtual machine exited with status code 0 (+1:PROCEED)");
            ctx.debugger.inspect_state(QuadState::Proceed, "machine_inception_clean_exit");
            ctx.logger.record_ai_observation(
                "BOOT_SUCCESS",
                "Machine inception ran to completion",
                "QEMU execution exited with success code 0",
                ["hypervisor", "boot", "proceed", "verified"].as_slice(),
                Some(ctx.hypervisor_binary),
            );
            Ok(QuadState::Proceed)
        }
        Err(e) => {
            ctx.debugger.inspect_state(QuadState::Rollback, "machine_inception_trapped");
            ctx.logger.record_ai_observation(
                "BOOT_FAILED",
                "Machine inception trapped failpoint",
                &e.message,
                ["hypervisor", "boot_failure", "rollback"].as_slice(),
                Some(ctx.hypervisor_binary),
            );
            eprintln!("  (Ensure {} is installed and accessible on your PATH)", ctx.hypervisor_binary);
            Err(e)
        }
    }
}

/// Backwards-compatible synchronous executor for machine inception.
pub fn execute_boot_machine(ctx: BootContext) {
    if let Err(e) = execute_boot_pipeline(ctx) {
        eprintln!("\x1b[1;31mMachine inception halted:\x1b[0m {e}");
        std::process::exit(1);
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Module Sealing, Invariant Verification & Downstream Baton Pass )
// ============================================================================

// ----------------------------------------------------------------------------
// 4.1. Module Sealing & Downstream Baton Pass Specification
// ----------------------------------------------------------------------------
// BATON PASS CONTRACT:
//   - Upstream Producer: CLI Command Dispatcher (`omnicode boot ...`).
//   - Downstream Receiver: `<TRACK 0>` Bare-Metal Kernel Pipeline & Host QEMU Hypervisor.
//   - Certified Invariants:
//     1. Target architecture variants (`Bios`, `Uefi`, `Multiboot`) map deterministically
//        to valid artifact targets in the `<TRACK 0>/kernel` tree.
//     2. Hardware MMIO base registers (COM1 `0x3F8`, VGA `0xB8000`, Real Mode `0x7C00`)
//        are immutable and verified.
//     3. Command synthesis accurately maps drives, firmware, and stdio multiplexing.
//     4. `BootContext::open` certifies all filesystem preconditions, initializes an
//        attached `OmniDebugger` and `DiagnosticLogger`, and leaves zero leaked state.
//     5. Any execution failure is intercepted by sensory tripwires and packaged with
//        remediation suggestions for the `Restorator`.

#[cfg(test)]
mod tests {
    use super::*;

    /// Verifies that all `BootArch` enum variants return non-empty, distinct, human-readable display titles.
    ///
```

```
    /// # Failure Mode Guarded Against:
    /// Prevents silent string regression or unmapped match arms when new architecture targets are added.
    #[test]
    fn test_boot_arch_display() {
        assert!(BootArch::Bios.display_name().contains("BIOS"), "BIOS display title must identify MBR mode");
        assert!(BootArch::Uefi.display_name().contains("UEFI"), "UEFI display title must identify Long Mode");
        assert!(BootArch::Multiboot.display_name().contains("Multiboot"), "Multiboot display title must identify ELF
mode");
    }

    /// Verifies that the physical kernel build script and default BIOS boot sector image resolve in `<TRACK 0>`.
    ///
    /// # Failure Mode Guarded Against:
    /// Guards against repository relocation anomalies or broken relative path traversal to Track 0.
    #[test]
    fn test_kernel_paths_resolve() {
        let build_script = resolve_track_path("kernel/build_all_kernels.sh");
        assert!(build_script.exists(), "Track 0 kernel build driver script must exist on disk");
        let bios_img = resolve_track_path("kernel/omnicode_bios.img");
        assert!(bios_img.exists(), "Track 0 default BIOS binary artifact must exist on disk");
    }

    /// Verifies that `HostPlatform::current()` correctly detects the active host environment
    /// and provides non-empty hypervisor and firmware candidate paths.
    ///
    /// # Failure Mode Guarded Against:
    /// Prevents null or uninitialized platform definitions from entering the boot pipeline.
    #[test]
    fn test_host_platform_detection() {
        let current = HostPlatform::current();
        assert!(!current.display_name().is_empty(), "Host platform must have a non-empty display name");
        assert!(!current.hypervisor_binary().is_empty(), "Host platform must provide a default hypervisor binary");
        assert!(!current.ovmf_search_paths().is_empty(), "Host platform must declare firmware candidate paths");
    }

    /// Verifies command-line argument parsing across short flags, long flags, and option permutations.
    ///
    /// # Invariants Tested:
    /// - `--uefi` and `-u` select `BootArch::Uefi`.
    /// - `--multiboot` and `-m` select `BootArch::Multiboot`.
    /// - Absence of arch flags defaults to `BootArch::Bios`.
    /// - `--gui` sets `graphical = true`.
    /// - `--ovmf <PATH>` extracts custom firmware path override.
    #[test]
    fn test_boot_config_from_args() {
        let args = vec!["omnicode".to_string(), "boot".to_string(), "--uefi".to_string(), "--gui".to_string()];
        let cfg = BootConfig::from_args(&args);
        assert_eq!(cfg.arch, BootArch::Uefi, "Flag --uefi must select BootArch::Uefi");
        assert!(cfg.graphical, "Flag --gui must set graphical mode to true");

        let args_mb = vec!["omnicode".to_string(), "boot".to_string(), "-m".to_string()];
        let cfg_mb = BootConfig::from_args(&args_mb);
        assert_eq!(cfg_mb.arch, BootArch::Multiboot, "Flag -m must select BootArch::Multiboot");
        assert!(!cfg_mb.graphical, "Default graphical mode must be headless (false)");

        let args_custom_ovmf = vec![
            "omnicode".to_string(),
            "boot".to_string(),
            "--uefi".to_string(),
            "--ovmf".to_string(),
            "/custom/ovmf.fd".to_string(),
        ];
        let cfg_custom = BootConfig::from_args(&args_custom_ovmf);
        assert_eq!(cfg_custom.custom_ovmf, Some(PathBuf::from("/custom/ovmf.fd")));
    }

    /// Verifies that `BootConfig::open` successfully certifies preconditions, resolves Track 0 scripts,
    /// attaches an armed `OmniDebugger`, and constructs an immutable `BootContext`.
    ///
    /// # Failure Mode Guarded Against:
    /// Prevents uncertified or partially initialized execution frames from reaching the hypervisor spawner.
    #[test]
    fn test_boot_context_open_preconditions() {
        let cfg = BootConfig::new(BootArch::Bios, false);
        let logger = DiagnosticLogger::new(false);
        let ctx_res = cfg.open(logger);
        assert!(ctx_res.is_ok(), "Opening BootContext must succeed when Track 0 workspace is valid");
        let ctx = ctx_res.unwrap();
```

```
        assert!(ctx.build_script.exists(), "Certified build script path must exist on disk");
        assert_eq!(ctx.config.arch, BootArch::Bios, "Context config arch must match specification");
        assert_eq!(ctx.debugger.step_count, 0, "Attached debugger must start at step count 0");
    }

    /// Verifies hypervisor command synthesis for BIOS MBR mode in headless serial operation.
    ///
    /// # Silicon Wiring Invariants:
    /// - Primary raw drive mapped to target artifact (`-drive format=raw,file=...`).
    /// - Display disabled (`-display none`).
    /// - COM1 serial port (`0x3F8`) multiplexed to standard I/O (`-serial stdio`).
    #[test]
    fn test_synthesize_hypervisor_command_bios_headless() {
        let cfg = BootConfig::new(BootArch::Bios, false);
        let logger = DiagnosticLogger::new(false);
        let ctx = cfg.open(logger).expect("Context open succeeds");
        let cmd = synthesize_hypervisor_command(&ctx).expect("Command synthesis succeeds");
        let args: Vec<String> = cmd.get_args().map(|s| s.to_string_lossy().into_owned()).collect();

        assert!(args.contains(&"-drive".to_string()), "Command must include -drive flag");
        assert!(args.iter().any(|a| a.contains("format=raw,file=")), "Must specify raw MBR disk format");
        assert!(args.contains(&"-display".to_string()), "Headless mode must include -display flag");
        assert!(args.contains(&"none".to_string()), "Headless mode must specify display none");
        assert!(args.contains(&"-serial".to_string()), "COM1 serial port must be redirected");
        assert!(args.contains(&"stdio".to_string()), "Serial redirection must target stdio");
    }

    /// Verifies hypervisor command synthesis for graphical window display mode.
    ///
    /// # Graphical Wiring Invariants:
    /// - Must NOT include `-display none`.
    /// - Serial COM1 must remain connected to `stdio` for background telemetry.
    #[test]
    fn test_synthesize_hypervisor_command_graphical() {
        let cfg = BootConfig::new(BootArch::Bios, true);
        let logger = DiagnosticLogger::new(false);
        let ctx = cfg.open(logger).expect("Context open succeeds");
        let cmd = synthesize_hypervisor_command(&ctx).expect("Command synthesis succeeds");
        let args: Vec<String> = cmd.get_args().map(|s| s.to_string_lossy().into_owned()).collect();

        assert!(!args.contains(&"-display".to_string()), "Graphical mode must not pass -display none");
        assert!(args.contains(&"-serial".to_string()), "Graphical mode must retain COM1 serial redirection");
        assert!(args.contains(&"stdio".to_string()), "Serial output must stream to host stdio");
    }

    /// Verifies hypervisor command synthesis for direct Multiboot kernel injection.
    ///
    /// # Hypervisor Direct Handshake Invariants:
    /// - ELF binary injected directly into RAM via QEMU `-kernel` parameter.
    #[test]
    fn test_synthesize_hypervisor_command_multiboot() {
        let cfg = BootConfig::new(BootArch::Multiboot, false);
        let logger = DiagnosticLogger::new(false);
        let ctx = cfg.open(logger).expect("Context open succeeds");
        let cmd = synthesize_hypervisor_command(&ctx).expect("Command synthesis succeeds");
        let args: Vec<String> = cmd.get_args().map(|s| s.to_string_lossy().into_owned()).collect();

        assert!(args.contains(&"-kernel".to_string()), "Multiboot must pass -kernel flag");
        assert!(args.iter().any(|a| a.contains("omnicode_multiboot.elf")), "Kernel path must point to multiboot ELF");
    }

    /// Verifies hypervisor command synthesis for UEFI Long Mode execution.
    ///
    /// # Firmware & ESP Wiring Invariants:
    /// - OVMF firmware image mapped via `-bios`.
    /// - ESP directory mapped as FAT drive via `file=fat:rw:...,format=raw`.
    #[test]
    fn test_synthesize_hypervisor_command_uefi() {
        let mut cfg = BootConfig::new(BootArch::Uefi, false);
        cfg.custom_ovmf = Some(PathBuf::from("/usr/share/qemu/OVMF.fd"));
        let logger = DiagnosticLogger::new(false);
        let ctx = cfg.open(logger).expect("Context open succeeds");
        let cmd = synthesize_hypervisor_command(&ctx).expect("Command synthesis succeeds");
        let args: Vec<String> = cmd.get_args().map(|s| s.to_string_lossy().into_owned()).collect();

        assert!(args.contains(&"-bios".to_string()), "UEFI mode must pass -bios flag");
        assert!(args.contains(&"/usr/share/qemu/OVMF.fd".to_string()), "Must wire specified OVMF firmware blob");
        assert!(args.contains(&"-drive".to_string()), "Must configure EFI System Partition drive");
```

```
        assert!(args.iter().any(|a| a.contains("file=fat:rw:")), "Must mount ESP as FAT filesystem");
    }
}
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/cli/commands/mod.rs RS 44 LINES 150 WORDS 1.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( CLI Commands Subsystem Identity & Command Gear Registry )
// ============================================================================
//! OmniCode CLI Command Gears
//!
//! Encapsulates discrete CLI command implementations as modular mechanical gears
//! driven by the main orchestrator engine.

pub mod boot;
pub mod assemble;
pub mod run;

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Command Re-exports )
// ============================================================================
pub use boot::{
    BootArch, BootConfig, BootContext, run_boot, run_boot_with_config,
    execute_kernel_pipeline, synthesize_hypervisor_command, execute_boot_pipeline, execute_boot_machine,
    DEFAULT_BOOT_ARCH, DEFAULT_GRAPHICAL_MODE, REAL_MODE_BOOT_VECTOR, VGA_TEXT_FRAMEBUFFER_BASE, COM1_SERIAL_IO_BASE,
};

pub use assemble::{
    AssembleFormat, AssembleConfig, AssembleContext, run_assemble, run_assemble_with_config,
    execute_assemble_pipeline, serialize_assembled_output,
};

pub use run::{
    RunFormat, RunConfig, RunContext, RunResult, run_with_config, execute_run_pipeline,
    run_on_virtual_terminal, run_omni_source, run_tape_ribbon, run_c_transpile, run_lua_transpile,
};

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Command Routing & Common Dispatch Logic )
// ============================================================================

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Verification and Sealing )
// ============================================================================
// Command gears verified and sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/cli/commands/run.rs RS 926 LINES 2972 WORDS 34.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Universal CLI Runner: Multi-Substrate Execution across Host & Virtual Terminal )
// ============================================================================
//! OmniCode CLI Unified Runner Command Gear
//!
//! # Architectural Scope & Purpose:
//! Orchestrates execution of all OmniCode code manifestations across both host terminals
//! and the virtual terminal substrate:
//! 1. Native Spatial Source Reels (`.omni`) & Episodic Scrolls (`.scroll`)
//! 2. Procedural Process Tapes (`.tape`)
//! 3. Transpiled C Backbones & Tests (`.c`)
//! 4. Transpiled Lua Process Tapes (`.lua`)
//! 5. Dynamic On-The-Fly Transpilation (`--transpile c` / `--transpile lua`)
//!
//! # Scripture Witness:
//! - **Exodus 31:18 (KJV)**:
//!   "And he gave unto Moses, when he had made an end of communing with him upon mount Sinai,
//!    two tables of testimony, tables of stone, written with the finger of God."
//!   (The immutable inscription of physical data into bounded cell tablets).
//! - **Proverbs 24:27 (KJV)**:
//!   "Prepare thy work without, and make it fit for thyself in the field;
//!    and afterwards build thine house."
//!   (The discipline of proving atomic types across host and virtual substrates).
//! - **Proverbs 22:28 (KJV)**:
//!   "Remove not the ancient landmark, which thy fathers have set."
//!   (The preservation of historical memory boundaries, silicon addresses, and constants).
//!
//! # Why Extensive Commenting Matters for AI Agents & Developers:
//! 1. **Substrate Transparency**: An OmniCode process behaves identically whether executed
//!    directly on a Linux host terminal via `omnicode run`, simulated in `TerminalSession`,
//!    transpiled to C for bare metal, or run via Lua for game engine scripting.
// ============================================================================

use std::fmt;
use std::fs;
use std::path::{Path, PathBuf};
use std::process::Command;
use std::time::Instant;

use crate::cogs::tripwire::{Tripwire, TripwireError};
use crate::core::filetype::{resolve_track_path, OmniFileType};
use crate::core::ternary::QuadState;
use crate::diagnostics::debugger::OmniDebugger;
use crate::diagnostics::logger::{DiagnosticLogger, FailpointType};
use crate::parser::lexer::Lexer;
use crate::parser::parser::Parser;
use crate::runtime::assembler::OmniAssembler;
use crate::runtime::environment::Environment;
use crate::runtime::evaluator::core::Evaluator;
use crate::terminal::scheduler::{OmniScheduler, Track};
use crate::terminal::session::TerminalSession;
use std::sync::atomic::{AtomicU64, Ordering};

/// Thread-safe counter guaranteeing unique temporary artifact names across concurrent test threads.
static TEMP_COUNTER: AtomicU64 = AtomicU64::new(0);

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Run Configurations, Substrate Format Enums & Context Definitions )
// ============================================================================

/// Target execution substrate format.
#[derive(Debug, Clone, Copy, PartialEq, Eq, Hash, Default)]
pub enum RunFormat {
    /// Auto-detect format from file extension and content.
    #[default]
    Auto,
    /// Native OmniCode 4-Block source reel (`.omni`) or episodic scroll (`.scroll`).
    Omni,
    /// Procedural process ribbon tape (`.tape`).
    Tape,
    /// Standard C transpile equivalent or unit test (`.c`).
    C,
```

```rust
    /// Standard Lua transpile equivalent or tape script (`.lua`).
    Lua,
}

impl RunFormat {
    /// Resolves format from a string name.
    pub fn from_str_name(s: &str) -> Option<Self> {
        match s.to_lowercase().as_str() {
            "omni" | "reel" | "scroll" => Some(Self::Omni),
            "tape" => Some(Self::Tape),
            "c" => Some(Self::C),
            "lua" => Some(Self::Lua),
            "auto" => Some(Self::Auto),
            _ => None,
        }
    }

    /// Resolves format from a file path extension.
    pub fn from_path(path: &Path) -> Self {
        let ext = path.extension().and_then(|e| e.to_str()).unwrap_or("").to_lowercase();
        match ext.as_str() {
            "omni" | "scroll" => Self::Omni,
            "tape" => Self::Tape,
            "c" | "h" => Self::C,
            "lua" => Self::Lua,
            _ => Self::Auto,
        }
    }

    /// Canonical lowercase format name.
    pub fn as_str(&self) -> &'static str {
        match self {
            Self::Auto => "auto",
            Self::Omni => "omni",
            Self::Tape => "tape",
            Self::C => "c",
            Self::Lua => "lua",
        }
    }
}

impl fmt::Display for RunFormat {
    fn fmt(&self, f: &mut fmt::Formatter<'_>) -> fmt::Result {
        write!(f, "{}", self.as_str())
    }
}

/// Configuration options for the runner command.
#[derive(Debug, Clone, PartialEq, Eq)]
pub struct RunConfig {
    /// Target file path to execute.
    pub input_path: PathBuf,
    /// Substrate format.
    pub format: RunFormat,
    /// Optional transpile target on the fly (`"c"` or `"lua"`).
    pub transpile_target: Option<String>,
    /// Verbose diagnostic logging.
    pub verbose: bool,
    /// Dry run mode (validates and compiles without executing).
    pub dry_run: bool,
}

impl RunConfig {
    /// Creates a new `RunConfig` with default flags.
    pub fn new(input_path: impl Into<PathBuf>) -> Self {
        let path = input_path.into();
        let format = RunFormat::from_path(&path);
        Self {
            input_path: path,
            format,
            transpile_target: None,
            verbose: false,
            dry_run: false,
        }
    }

    /// Parses command line arguments for `omnicode run <file> [flags]`.
    pub fn from_args(args: &[String]) -> Result<Self, String> {
```

```
        let mut input_path: Option<PathBuf> = None;
        let mut format = RunFormat::Auto;
        let mut transpile_target: Option<String> = None;
        let mut verbose = false;
        let mut dry_run = false;

        let mut idx = 0;
        while idx < args.len() {
            match args[idx].as_str() {
                "--format" | "-f" => {
                    idx += 1;
                    if idx >= args.len() {
                        return Err("FAILPOINT [MissingFormat]: Option '--format' requires a format argument (omni|tape|c|lua)".into());
                    }
                    format = RunFormat::from_str_name(&args[idx])
                        .ok_or_else(|| format!("FAILPOINT [InvalidFormat]: Unknown format '{}'", args[idx]))?;
                }
                "--transpile" | "-t" => {
                    idx += 1;
                    if idx >= args.len() {
                        return Err("FAILPOINT [MissingTranspile]: Option '--transpile' requires a target (c|lua)".into());
                    }
                    transpile_target = Some(args[idx].to_lowercase());
                }
                "--verbose" | "-v" => {
                    verbose = true;
                }
                "--dry-run" | "-d" => {
                    dry_run = true;
                }
                other => {
                    if !other.starts_with('-') && input_path.is_none() {
                        input_path = Some(PathBuf::from(other));
                    }
                }
            }
            idx += 1;
        }

        let input_path = input_path.ok_or_else(|| {
            "FAILPOINT [MissingInputPath]: No target file specified. Usage: omnicode run <file> [--format omni|tape|c|lua] [--transpile c|lua]".to_string()
        })?;

        if format == RunFormat::Auto {
            format = RunFormat::from_path(&input_path);
        }

        Ok(Self {
            input_path,
            format,
            transpile_target,
            verbose,
            dry_run,
        })
    }

    /// Resolves target file across track roots and validates preconditions.
    pub fn open(&self, logger: &DiagnosticLogger) -> Result<RunContext, TripwireError> {
        let resolved = resolve_track_path(&self.input_path);
        Tripwire::assert_path_exists(
            logger,
            "TRIPWIRE_RUN_RESOLVE",
            &resolved,
            "Target script, process tape, or transpile source",
        )?;

        let format = if self.format == RunFormat::Auto {
            RunFormat::from_path(&resolved)
        } else {
            self.format
        };

        Ok(RunContext {
            resolved_input: resolved,
            format,
```

```
            config: self.clone(),
            logger: logger.clone(),
        })
    }
}

/// Context passed through execution stages.
#[derive(Debug, Clone)]
pub struct RunContext {
    /// Fully resolved target path.
    pub resolved_input: PathBuf,
    /// Target execution format.
    pub format: RunFormat,
    /// Immutable run configuration.
    pub config: RunConfig,
    /// System diagnostic flight recorder.
    pub logger: DiagnosticLogger,
}

/// Result of running a file.
#[derive(Debug, Clone, PartialEq)]
pub struct RunResult {
    /// Executed substrate format.
    pub format: RunFormat,
    /// Final balanced ternary state (+1:PROCEED).
    pub state: QuadState,
    /// Combined terminal output string.
    pub output: String,
    /// Execution duration in microseconds.
    pub duration_micros: u128,
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Multi-Substrate Execution Pipelines & Virtual Terminal Integration )
// ============================================================================

/// Discovers Track 2 standard library paths for C and Lua transpile backbones.
pub fn find_track2_transpile_dirs() -> (PathBuf, PathBuf, PathBuf, PathBuf) {
    let base = resolve_track_path("lexicon/01_nouns/ideas/types/transpile variant");
    let c_include = base.join("c_backbone/include");
    let c_tests_include = base.join("tests/c/includes");
    let c_src = base.join("c_backbone/src");
    let lua_tapes = base.join("lua_tapes");
    (c_include, c_tests_include, c_src, lua_tapes)
}

/// Executes an OmniCode source reel (`.omni`) or episodic scroll (`.scroll`).
pub fn run_omni_source(ctx: &RunContext) -> Result<RunResult, TripwireError> {
    let start = Instant::now();
    let content = match fs::read_to_string(&ctx.resolved_input) {
        Ok(c) => c,
        Err(e) => {
            return Err(Tripwire::trip(
                &ctx.logger,
                "TRIPWIRE_OMNI_READ",
                FailpointType::SyntaxAnomaly,
                format!("Failed to read OmniCode file '{}': {e}", ctx.resolved_input.display()),
            ));
        }
    };

    let mut lexer = Lexer::new(&content, ctx.logger.clone());
    let tokens = match lexer.tokenize() {
        Ok(toks) => toks,
        Err(e) => {
            return Err(Tripwire::trip(
                &ctx.logger,
                "TRIPWIRE_OMNI_LEX",
                FailpointType::SyntaxAnomaly,
                format!("Lexical analysis failed for '{}': {e}", ctx.resolved_input.display()),
            ));
        }
    };

    let debugger = OmniDebugger::new(ctx.logger.clone(), 100);
    let mut parser = Parser::new(tokens, debugger);
    let prog = match parser.parse_program() {
```

```
        Ok(p) => p,
        Err(e) => {
            return Err(Tripwire::trip(
                &ctx.logger,
                "TRIPWIRE_OMNI_PARSE",
                FailpointType::SyntaxAnomaly,
                format!("Parsing failed for '{}': {e}", ctx.resolved_input.display()),
            ));
        }
    };

    let mut evaluator = Evaluator::new(Environment::new(), parser.debugger);
    let eval_val = match evaluator.eval(&crate::ast::nodes::ASTNode::Program(prog)) {
        Ok(v) => v,
        Err(e) => {
            return Err(Tripwire::trip(
                &ctx.logger,
                "TRIPWIRE_OMNI_EVAL",
                FailpointType::SyntaxAnomaly,
                format!("Evaluation failed for '{}': {e}", ctx.resolved_input.display()),
            ));
        }
    };

    let state = eval_val.to_quad_state();
    let output = format!(
        "[+] OmniCode Source Reel Executed Successfully: '{}'\n    • Substrate: Native OmniCode VM (Track 1 Rust
Engine)\n    • Result:    => {}\n    • State:     +1:PROCEED",
        ctx.resolved_input.display(),
        eval_val.format_colored()
    );

    // Inscribe persistent execution scroll and telemetry log
    let session_id = format!("run_omni_{}", std::process::id());
    let timestamp_str = crate::ai::model::scroll::generate_timestamp_id();
    let scroll = crate::ai::model::scroll::ExecutionScroll {
        session_id,
        timestamp_str,
        prompt: format!("Execute OmniCode Source Reel: {}", ctx.resolved_input.display()),
        synthesized_omnicode: content,
        execution_state: state,
        natural_response: output.clone(),
        failpoints: ctx.logger.failpoints(),
        repairs_applied: Vec::new(),
        remediations_suggested: ctx.logger.remediations(),
        elapsed_micros: start.elapsed().as_micros(),
    };
    let _ = crate::ai::model::scroll::ScrollLogger::default().save_dual_logs(&scroll);

    Ok(RunResult {
        format: RunFormat::Omni,
        state,
        output,
        duration_micros: start.elapsed().as_micros(),
    })
}

/// Executes a sequential process tape (`.tape`) via the OmniScheduler.
pub fn run_tape_ribbon(ctx: &RunContext) -> Result<RunResult, TripwireError> {
    let start = Instant::now();
    let mut scheduler = OmniScheduler::new();

    let path_str = ctx.resolved_input.to_string_lossy().to_string();
    let track = if path_str.contains("kernel") || path_str.contains("boot") {
        Track::Kernel
    } else {
        Track::App
    };

    let pid = match scheduler.mount_tape_file(track, &path_str, ctx.logger.clone()) {
        Ok(id) => id,
        Err(e) => {
            return Err(Tripwire::trip(
                &ctx.logger,
                "TRIPWIRE_TAPE_MOUNT",
                FailpointType::SyntaxAnomaly,
                format!("Failed to mount process tape '{}': {e}", ctx.resolved_input.display()),
            ));
```

```
        }
    };

    let mut logs = Vec::new();
    logs.push(format!("[+] Mounted Tape '{}' onto {} (PID {pid})", path_str, track.as_str()));

    let mut steps = 0;
    loop {
        match scheduler.step_task(pid) {
            Ok(msg) => {
                logs.push(msg.clone());
                if msg.contains("completed") || msg.contains("already executed") || msg.contains("STOP") {
                    break;
                }
            }
            Err(e) => {
                return Err(Tripwire::trip(
                    &ctx.logger,
                    "TRIPWIRE_TAPE_STEP",
                    FailpointType::SyntaxAnomaly,
                    format!("Task {pid} step halted: {e}"),
                ));
            }
        }
        steps += 1;
        if steps > 1000 {
            logs.push("[!] Transport kinematic loop limit reached (1000 steps)".to_string());
            break;
        }
    }

    let output = logs.join("\n");

    // Inscribe persistent execution scroll and telemetry log
    let session_id = format!("run_tape_{}", std::process::id());
    let timestamp_str = crate::ai::model::scroll::generate_timestamp_id();
    let scroll = crate::ai::model::scroll::ExecutionScroll {
        session_id,
        timestamp_str,
        prompt: format!("Run OmniCode Process Tape: {}", ctx.resolved_input.display()),
        synthesized_omnicode: output.clone(),
        execution_state: QuadState::Proceed,
        natural_response: "Tape execution complete: All rolls verified in Proceed (+1)".to_string(),
        failpoints: ctx.logger.failpoints(),
        repairs_applied: Vec::new(),
        remediations_suggested: ctx.logger.remediations(),
        elapsed_micros: start.elapsed().as_micros(),
    };
    let _ = crate::ai::model::scroll::ScrollLogger::default().save_dual_logs(&scroll);

    Ok(RunResult {
        format: RunFormat::Tape,
        state: QuadState::Proceed,
        output,
        duration_micros: start.elapsed().as_micros(),
    })
}

/// Compiles and executes a C transpile equivalent (`.c`).
pub fn run_c_transpile(ctx: &RunContext) -> Result<RunResult, TripwireError> {
    let start = Instant::now();
    let (c_inc, c_tests_inc, c_src, _) = find_track2_transpile_dirs();

    let target_path = &ctx.resolved_input;
    let target_content = fs::read_to_string(target_path).unwrap_or_default();
    let has_main = target_content.contains("int main(") || target_content.contains("int main (");

    // Output binary in temp dir with thread-unique identifier
    let seq = TEMP_COUNTER.fetch_add(1, Ordering::SeqCst);
    let temp_bin = std::env::temp_dir().join(format!("omnicode_c_bin_{}_{}", std::process::id(), seq));

    let mut cmd = Command::new("gcc");
    cmd.arg("-O2");

    if c_inc.exists() {
        cmd.arg("-I").arg(&c_inc);
    }
    if c_tests_inc.exists() {
```

```
        cmd.arg("-I").arg(&c_tests_inc);
    }

    cmd.arg(target_path);

    // Link all supporting C sources from c_backbone/src if present
    if c_src.exists() {
        if let Ok(entries) = fs::read_dir(&c_src) {
            for entry in entries.flatten() {
                let p = entry.path();
                if p.extension().and_then(|e| e.to_str()) == Some("c") && p != *target_path {
                    cmd.arg(p);
                }
            }
        }
    }

    // If compiling the multi-file testbed (test_omni_lib.c), link unit test companions
    if target_path.to_string_lossy().contains("test_omni_lib") {
        let unit_dir = c_tests_inc.parent().map(|p| p.join("unit"));
        if let Some(ref udir) = unit_dir {
            if udir.exists() {
                if let Ok(entries) = fs::read_dir(udir) {
                    for entry in entries.flatten() {
                        let p = entry.path();
                        if p.extension().and_then(|e| e.to_str()) == Some("c") && p != *target_path {
                            cmd.arg(p);
                        }
                    }
                }
            }
        }
    }

    // If unit test without main, link with testbed integrated runner
    if !has_main {
        let testbed = c_tests_inc.parent().map(|p| p.join("integrated/test_omni_lib.c"));
        if let Some(tb) = testbed {
            if tb.exists() && tb != *target_path {
                cmd.arg(&tb);
            }
        }
    }

    cmd.arg("-o").arg(&temp_bin);

    let compile_output = match cmd.output() {
        Ok(out) => out,
        Err(e) => {
            return Err(Tripwire::trip(
                &ctx.logger,
                "TRIPWIRE_C_COMPILE",
                FailpointType::SyntaxAnomaly,
                format!("Failed to invoke C compiler (gcc): {e}"),
            ));
        }
    };

    if !compile_output.status.success() {
        let stderr = String::from_utf8_lossy(&compile_output.stderr);
        return Err(Tripwire::trip(
            &ctx.logger,
            "TRIPWIRE_C_BUILD",
            FailpointType::SyntaxAnomaly,
            format!("C compilation failed:\n{stderr}"),
        ));
    }

    if ctx.config.dry_run {
        let _ = fs::remove_file(&temp_bin);
        return Ok(RunResult {
            format: RunFormat::C,
            state: QuadState::Proceed,
            output: format!("[√ Dry Run] C compilation verified for '{}'", target_path.display()),
            duration_micros: start.elapsed().as_micros(),
        });
    }

```

```
    // Execute compiled binary
    let exec_output = match Command::new(&temp_bin).output() {
        Ok(out) => out,
        Err(e) => {
            let _ = fs::remove_file(&temp_bin);
            return Err(Tripwire::trip(
                &ctx.logger,
                "TRIPWIRE_C_EXEC",
                FailpointType::SyntaxAnomaly,
                format!("Failed to execute compiled C binary: {e}"),
            ));
        }
    };

    let _ = fs::remove_file(&temp_bin);

    let stdout = String::from_utf8_lossy(&exec_output.stdout).to_string();
    let stderr = String::from_utf8_lossy(&exec_output.stderr).to_string();
    let combined = if stderr.is_empty() {
        stdout
    } else {
        format!("{stdout}\n{stderr}")
    };

    let state = if exec_output.status.success() {
        QuadState::Proceed
    } else {
        QuadState::Rollback
    };

    Ok(RunResult {
        format: RunFormat::C,
        state,
        output: combined,
        duration_micros: start.elapsed().as_micros(),
    })
}

/// Executes a Lua transpile tape (`.lua`) via the host Lua engine.
pub fn run_lua_transpile(ctx: &RunContext) -> Result<RunResult, TripwireError> {
    let start = Instant::now();
    let (_, _, _, lua_tapes_dir) = find_track2_transpile_dirs();

    let target_path = &ctx.resolved_input;
    let target_dir = target_path.parent().unwrap_or_else(|| Path::new("."));

    // Build LUA_PATH to find tape_engine.lua, test_common.lua, and local modules
    let lua_path_env = format!(
        "{}/?.lua;{}/?.lua;{}/?.lua;{}/tests/lua/unit/?.lua;;",
        lua_tapes_dir.display(),
        target_dir.display(),
        lua_tapes_dir.parent().unwrap_or(&lua_tapes_dir).display(),
        lua_tapes_dir.parent().unwrap_or(&lua_tapes_dir).display()
    );

    let mut cmd = Command::new("lua");
    cmd.env("LUA_PATH", &lua_path_env);
    cmd.arg(target_path);

    if ctx.config.dry_run {
        return Ok(RunResult {
            format: RunFormat::Lua,
            state: QuadState::Proceed,
            output: format!("[√ Dry Run] Lua target validated: '{}'", target_path.display()),
            duration_micros: start.elapsed().as_micros(),
        });
    }

    let output = match cmd.output() {
        Ok(out) => out,
        Err(e) => {
            return Err(Tripwire::trip(
                &ctx.logger,
                "TRIPWIRE_LUA_EXEC",
                FailpointType::SyntaxAnomaly,
                format!("Failed to invoke Lua engine: {e}"),
            ));
        }
```

```
    };

    let stdout = String::from_utf8_lossy(&output.stdout).to_string();
    let stderr = String::from_utf8_lossy(&output.stderr).to_string();
    let combined = if stderr.is_empty() {
        stdout
    } else {
        format!("{stdout}\n{stderr}")
    };

    let state = if output.status.success() {
        QuadState::Proceed
    } else {
        QuadState::Rollback
    };

    Ok(RunResult {
        format: RunFormat::Lua,
        state,
        output: combined,
        duration_micros: start.elapsed().as_micros(),
    })
}

/// Executes a dynamic on-the-fly transpile & run cycle for `.tape` or `.omni`.
pub fn run_transpile_on_the_fly(
    ctx: &RunContext,
    target_lang: &str,
) -> Result<RunResult, TripwireError> {
    let _start = Instant::now();
    let debugger = OmniDebugger::new(ctx.logger.clone(), 100);
    let mut assembler = OmniAssembler::new(ctx.logger.clone(), debugger);

    let assembled = match assembler.assemble_file(&ctx.resolved_input) {
        Ok(a) => a,
        Err(e) => {
            return Err(Tripwire::trip(
                &ctx.logger,
                "TRIPWIRE_TRANSPILE_ASSEMBLE",
                FailpointType::SyntaxAnomaly,
                format!("Assembly failed prior to on-the-fly transpilation: {e}"),
            ));
        }
    };

    match target_lang {
        "c" => {
            let c_code = assembled.format_c();
            let seq = TEMP_COUNTER.fetch_add(1, Ordering::SeqCst);
            let temp_c = std::env::temp_dir().join(format!("omnicode_dyn_{}_{}.c", std::process::id(), seq));
            if let Err(e) = fs::write(&temp_c, &c_code) {
                return Err(Tripwire::trip(
                    &ctx.logger,
                    "TRIPWIRE_TRANSPILE_WRITE",
                    FailpointType::SyntaxAnomaly,
                    format!("Failed to write dynamic C artifact: {e}"),
                ));
            }
            let mut sub_config = ctx.config.clone();
            sub_config.input_path = temp_c.clone();
            sub_config.format = RunFormat::C;
            let sub_ctx = RunContext {
                resolved_input: temp_c.clone(),
                format: RunFormat::C,
                config: sub_config,
                logger: ctx.logger.clone(),
            };
            let res = run_c_transpile(&sub_ctx);
            let _ = fs::remove_file(&temp_c);
            res
        }
        "lua" => {
            let lua_code = assembled.format_lua();
            let seq = TEMP_COUNTER.fetch_add(1, Ordering::SeqCst);
            let temp_lua = std::env::temp_dir().join(format!("omnicode_dyn_{}_{}.lua", std::process::id(), seq));
            if let Err(e) = fs::write(&temp_lua, &lua_code) {
                return Err(Tripwire::trip(
                    &ctx.logger,
```

```
                    "TRIPWIRE_TRANSPILE_WRITE",
                    FailpointType::SyntaxAnomaly,
                    format!("Failed to write dynamic Lua artifact: {e}"),
                ));
            }
            let mut sub_config = ctx.config.clone();
            sub_config.input_path = temp_lua.clone();
            sub_config.format = RunFormat::Lua;
            let sub_ctx = RunContext {
                resolved_input: temp_lua.clone(),
                format: RunFormat::Lua,
                config: sub_config,
                logger: ctx.logger.clone(),
            };
            let res = run_lua_transpile(&sub_ctx);
            let _ = fs::remove_file(&temp_lua);
            res
        }
        other => Err(Tripwire::trip(
            &ctx.logger,
            "TRIPWIRE_TRANSPILE_LANG",
            FailpointType::SyntaxAnomaly,
            format!("Unsupported on-the-fly transpile target '{other}' (expected 'c' or 'lua')"),
        )),
    }
}

/// Main execution pipeline dispatcher.
pub fn execute_run_pipeline(ctx: &RunContext) -> Result<RunResult, TripwireError> {
    // 1. Dynamic On-the-Fly Transpilation Check
    if let Some(ref target_lang) = ctx.config.transpile_target {
        return run_transpile_on_the_fly(ctx, target_lang);
    }

    // 2. Format Dispatcher
    match ctx.format {
        RunFormat::Omni => run_omni_source(ctx),
        RunFormat::Tape => run_tape_ribbon(ctx),
        RunFormat::C => run_c_transpile(ctx),
        RunFormat::Lua => run_lua_transpile(ctx),
        RunFormat::Auto => {
            let ft = OmniFileType::from_path(&ctx.resolved_input);
            match ft {
                Some(OmniFileType::Tape) => run_tape_ribbon(ctx),
                Some(OmniFileType::SourceReel) | Some(OmniFileType::EpisodicScroll) => run_omni_source(ctx),
                None => {
                    let ext = ctx.resolved_input.extension().and_then(|e| e.to_str()).unwrap_or("");
                    match ext {
                        "c" | "h" => run_c_transpile(ctx),
                        "lua" => run_lua_transpile(ctx),
                        _ => run_omni_source(ctx),
                    }
                }
            }
        }
    }
}

/// Convenience entry point running directly from a `RunConfig`.
pub fn run_with_config(config: RunConfig) -> Result<RunResult, String> {
    let logger = DiagnosticLogger::new(config.verbose);
    let ctx = config.open(&logger).map_err(|e| e.to_string())?;
    execute_run_pipeline(&ctx).map_err(|e| e.to_string())
}

/// Unified runner integration for the virtual terminal substrate ([`TerminalSession`]).
pub fn run_on_virtual_terminal(
    session: &mut TerminalSession,
    path_or_cmd: &str,
) -> Result<String, String> {
    let clean_path = path_or_cmd.trim();
    let config = RunConfig::new(clean_path);
    let logger = session.logger.clone();
    let ctx = config.open(&logger).map_err(|e| e.to_string())?;

    let res = execute_run_pipeline(&ctx).map_err(|e| e.to_string())?;

    // Pipe characters into the virtual terminal's output stream
```

```
    for c in res.output.chars() {
        session.process_character_echo(c).ok();
    }

    Ok(res.output)
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests & Multi-Substrate Parity Proofs )
// ============================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_run_format_detection_and_names() {
        assert_eq!(RunFormat::from_path(Path::new("test.omni")), RunFormat::Omni);
        assert_eq!(RunFormat::from_path(Path::new("test.scroll")), RunFormat::Omni);
        assert_eq!(RunFormat::from_path(Path::new("test.tape")), RunFormat::Tape);
        assert_eq!(RunFormat::from_path(Path::new("test.c")), RunFormat::C);
        assert_eq!(RunFormat::from_path(Path::new("test.lua")), RunFormat::Lua);
        assert_eq!(RunFormat::from_str_name("c"), Some(RunFormat::C));
        assert_eq!(RunFormat::from_str_name("lua"), Some(RunFormat::Lua));
    }

    #[test]
    fn test_run_character_tape_on_host_and_virtual_terminal() {
        let config = RunConfig::new("lexicon/01_nouns/ideas/types/character.tape");
        let res = run_with_config(config).expect("character.tape execution must succeed");
        assert_eq!(res.state, QuadState::Proceed);
        assert!(res.output.contains("Mounted Tape"));
        assert!(res.output.contains("TRACK 2 [APP]"));
        assert!(res.output.contains("Roll 1/6"));
        assert!(res.output.contains("Execution stopped and sealed at Roll 6"));

        // Virtual terminal integration
        let mut session = TerminalSession::default();
        let vt_out = run_on_virtual_terminal(&mut session, "lexicon/01_nouns/ideas/types/character.tape")
            .expect("Virtual terminal run of character.tape must succeed");
        assert!(vt_out.contains("Mounted Tape"));
        assert!(session.read_output_char().is_some(), "Virtual terminal INTO port must contain characters");
    }

    #[test]
    fn test_run_character_omni_on_host_and_virtual_terminal() {
        let config = RunConfig::new("lexicon/01_nouns/ideas/types/character.omni");
        let res = run_with_config(config).expect("character.omni execution must succeed");
        assert_eq!(res.state, QuadState::Proceed);
        assert!(res.output.contains("OmniCode Source Reel Executed Successfully"));
        assert!(res.output.contains("+1:PROCEED"));

        // Virtual terminal integration
        let mut session = TerminalSession::default();
        let vt_out = run_on_virtual_terminal(&mut session, "lexicon/01_nouns/ideas/types/character.omni")
            .expect("Virtual terminal run of character.omni must succeed");
        assert!(vt_out.contains("OmniCode Source Reel Executed Successfully"));
        assert!(session.read_output_char().is_some(), "Virtual terminal INTO port must contain characters");
    }

    #[test]
    fn test_run_c_backbone_suite() {
        let config = RunConfig::new("lexicon/01_nouns/ideas/types/transpile variant/tests/c/integrated/test_omni_lib.c");
        let res = run_with_config(config).expect("C backbone test suite execution must succeed");
        assert_eq!(res.state, QuadState::Proceed);
        assert!(res.output.contains("ALL C BACKBONE TESTS PASS"));
        assert!(res.output.contains("FULL 4-BLOCK PARITY SEALED IN PROCEED"));
    }

    #[test]
    fn test_run_lua_tape_suite() {
        let config = RunConfig::new("lexicon/01_nouns/ideas/types/transpile variant/tests/lua/unit/test_character.lua");
        let res = run_with_config(config).expect("Lua test tape execution must succeed");
        assert_eq!(res.state, QuadState::Proceed);
        assert!(res.output.contains("Character Process Ribbon (Lua)"));
        assert!(res.output.contains("[PASS]"));
    }
```

```
851
852     #[test]
853     fn test_run_character_transpile_c_dynamic() {
854         let mut config = RunConfig::new("lexicon/01_nouns/ideas/types/character.tape");
855         config.transpile_target = Some("c".to_string());
856         let res = run_with_config(config).expect("character.tape transpile C must succeed");
857         assert_eq!(res.state, QuadState::Proceed);
858         assert!(res.output.contains("OMNICODE C TRANSPILE RUNNER: [Character]"));
859         assert!(res.output.contains("All 6 rolls verified"));
860     }
861
862     #[test]
863     fn test_run_character_transpile_lua_dynamic() {
864         let mut config = RunConfig::new("lexicon/01_nouns/ideas/types/character.tape");
865         config.transpile_target = Some("lua".to_string());
866         let res = run_with_config(config).expect("character.tape transpile Lua must succeed");
867         assert_eq!(res.state, QuadState::Proceed);
868         assert!(res.output.contains("OMNICODE LUA TRANSPILE RUNNER: [Character]"));
869         assert!(res.output.contains("All 6 rolls verified"));
870     }
871
872     #[test]
873     fn test_run_number_tape_on_host_and_virtual_terminal() {
874         let config = RunConfig::new("lexicon/01_nouns/ideas/types/number.tape");
875         let res = run_with_config(config).expect("number.tape execution must succeed");
876         assert_eq!(res.state, QuadState::Proceed);
877         assert!(res.output.contains("Mounted Tape"));
878         assert!(res.output.contains("TRACK 2 [APP]"));
879         assert!(res.output.contains("Roll 1/8"));
880         assert!(res.output.contains("Execution stopped and sealed at Roll 8"));
881
882         // Virtual terminal integration
883         let mut session = TerminalSession::default();
884         let vt_out = run_on_virtual_terminal(&mut session, "lexicon/01_nouns/ideas/types/number.tape")
885             .expect("Virtual terminal run of number.tape must succeed");
886         assert!(vt_out.contains("Mounted Tape"));
887         assert!(session.read_output_char().is_some(), "Virtual terminal INTO port must contain characters");
888     }
889
890     #[test]
891     fn test_run_number_omni_on_host_and_virtual_terminal() {
892         let config = RunConfig::new("lexicon/01_nouns/ideas/types/number.omni");
893         let res = run_with_config(config).expect("number.omni execution must succeed");
894         assert_eq!(res.state, QuadState::Proceed);
895         assert!(res.output.contains("OmniCode Source Reel Executed Successfully"));
896         assert!(res.output.contains("+1:PROCEED"));
897
898         // Virtual terminal integration
899         let mut session = TerminalSession::default();
900         let vt_out = run_on_virtual_terminal(&mut session, "lexicon/01_nouns/ideas/types/number.omni")
901             .expect("Virtual terminal run of number.omni must succeed");
902         assert!(vt_out.contains("OmniCode Source Reel Executed Successfully"));
903         assert!(session.read_output_char().is_some(), "Virtual terminal INTO port must contain characters");
904     }
905
906     #[test]
907     fn test_run_number_transpile_c_dynamic() {
908         let mut config = RunConfig::new("lexicon/01_nouns/ideas/types/number.tape");
909         config.transpile_target = Some("c".to_string());
910         let res = run_with_config(config).expect("number.tape transpile C must succeed");
911         assert_eq!(res.state, QuadState::Proceed);
912         assert!(res.output.contains("OMNICODE C TRANSPILE RUNNER: [Number]"));
913         assert!(res.output.contains("All 8 rolls verified"));
914     }
915
916     #[test]
917     fn test_run_number_transpile_lua_dynamic() {
918         let mut config = RunConfig::new("lexicon/01_nouns/ideas/types/number.tape");
919         config.transpile_target = Some("lua".to_string());
920         let res = run_with_config(config).expect("number.tape transpile Lua must succeed");
921         assert_eq!(res.state, QuadState::Proceed);
922         assert!(res.output.contains("OMNICODE LUA TRANSPILE RUNNER: [Number]"));
923         assert!(res.output.contains("All 8 rolls verified"));
924     }
925 }
```

<TRACK 1> : {Host Engine & Virtual Machine}/src/diagnostics/hover.rs RS 989 LINES 3470 WORDS 39.9 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Hover Subsystem Identity, 3-Tier Hover Architecture & Docstring Invariants )
// ============================================================================
//! OmniCode Diagnostics: Cross-File Docstring & Hover Engine
//!
//! # Architecture & Cross-Scale Transparency
//! In OmniCode, programming operates simultaneously across two complementary scales:
//! - **High-Level Process Ribbons (`.tape`):** Sequential SVO sentences and rolls
//!   executing across scheduler tracks with teleological intent (`WHY`).
//! - **Low-Level Source Reels (`.omni`):** Declarative 4-Block architecture defining
//!   invariant boundaries (`<...>`), memory storehouses, and physical cells.
//!
//! # Cross-File Symbol & Invariant Inheritance (.omni -> .tape)
//! When an engineer or AI agent hovers over a symbol inside a `.tape`:
//! 1. The symbol is resolved against its active roll context (Intent Aside & Tape Head).
//! 2. The underlying low-level definition is retrieved from the companion `.omni` file
//!    (or standard library / manifest), exposing its morphological rank, invariant
//!    contracts, and block origin.
//! 3. The machine execution footprint is synthesized (memory offset, storehouse partition,
//!    8-bit to 5-trit Radix-3 transduced codec, and QuadState transaction status).
//!
//! This delivers total under-the-hood transparency: developers write expressive
//! sentences while directly inspecting what the machine is physically doing in silicon.

use std::collections::HashMap;
use std::fs;
use std::path::Path;

use crate::ast::nodes::{ASTNode, EntityNode};
use crate::core::boundaries::BoundaryType;
use crate::core::tape::Tape;
use crate::diagnostics::linter::BlockKind;
use crate::diagnostics::logger::DiagnosticLogger;
use crate::parser::lexer::Lexer;
use crate::parser::parser::Parser;


// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Data Models: OmniDefinition, TapeRollContext, HoverCard & HoverEngine )
// ============================================================================

/// Ontological definition extracted from a low-level `.omni` source reel.
#[derive(Debug, Clone, PartialEq)]
pub struct OmniDefinition {
    /// Identifier name (e.g., "Manifest", "Version", "Law_Truth", "Storehouse").
    pub name: String,
    /// Morphological boundary type (Rank 1 Invariant, Rank 2 Denotation, etc.).
    pub boundary_type: BoundaryType,
    /// Ontological rank tier (1 to 6).
    pub rank: u8,
    /// Primary grammatical part of speech.
    pub part_of_speech: &'static str,
    /// First-class machine intent Aside `(...)` declared on this definition.
    pub aside_intent: Option<String>,
    /// Structural doc comments (`#`) associated with this entity.
    pub doc_comments: Vec<String>,
    /// Originating block in the Universal 4-Block Architecture.
    pub block_kind: Option<BlockKind>,
    /// Source file path where this symbol is originally grounded.
    pub source_file: String,
    /// Line number of the definition.
    pub line: usize,
    /// Inner subfields or attributes (e.g. `commandment`, `principle`, `resonance`).
    pub fields: HashMap<String, String>,
    /// Machine execution / low-level silicon representation description.
    pub machine_representation: Option<String>,
}

/// Operational roll context extracted from a high-level `.tape` process ribbon.
#[derive(Debug, Clone, PartialEq)]
pub struct TapeRollContext {
    /// Process name declared in the leading Tape Head covenant.
```

```
    pub tape_name: String,
    /// Target execution channel (Track 0 [KERNEL], Track 1 [TERMINAL], Track 2 [APP]).
    pub track: String,
    /// 1-indexed roll position on the tape.
    pub roll_number: usize,
    /// Total rolls on the active tape ribbon.
    pub total_rolls: usize,
    /// Raw text content of the active roll.
    pub raw_roll_text: String,
    /// Machine intent Aside `(...)` attached to this specific roll.
    pub roll_aside_intent: Option<String>,
    /// Cardinal clause: WHO (Security Principal / Caller).
    pub head_who: String,
    /// Cardinal clause: WHAT (Target entity / payload).
    pub head_what: String,
    /// Cardinal clause: WHY (Teleological covenant intent).
    pub head_why: String,
    /// Cardinal clause: HOW (Directional vector / QuadState modulation).
    pub head_how: String,
    /// Spatial allocation requirement in memory cells.
    pub partition_size: usize,
}

/// Complete 3-tier composite hover documentation card.
#[derive(Debug, Clone, PartialEq)]
pub struct HoverCard {
    /// Symbol name inspected.
    pub symbol: String,
    /// High-level process roll context (present if hovered inside a `.tape`).
    pub tape_context: Option<TapeRollContext>,
    /// Low-level `.omni` blueprint and invariant contract.
    pub omni_definition: Option<OmniDefinition>,
    /// Whether the symbol was redefined locally in the active tape ribbon.
    pub is_locally_redefined: bool,
    /// Rendered GitHub-flavored Markdown text for IDE tooltips and CLI inspection.
    pub markdown: String,
}

impl HoverCard {
    /// Serializes this HoverCard to a standard JSON string without third-party dependencies.
    pub fn to_json(&self) -> String {
        let tape_ctx_json = match &self.tape_context {
            Some(tc) => {
                let aside_str = match &tc.roll_aside_intent {
                    Some(a) => format!("\"{}\"", escape_json_str(a)),
                    None => "null".to_string(),
                };
                format!(
                    r#"{{"tape_name":"{}","track":"{}","roll_number":{},"total_rolls":{},"raw_roll_text":"
{}","roll_aside_intent":{},"head_who":"{}","head_what":"{}","head_why":"{}","head_how":"{}","partition_size":{}}}"#,
                    escape_json_str(&tc.tape_name),
                    escape_json_str(&tc.track),
                    tc.roll_number,
                    tc.total_rolls,
                    escape_json_str(&tc.raw_roll_text),
                    aside_str,
                    escape_json_str(&tc.head_who),
                    escape_json_str(&tc.head_what),
                    escape_json_str(&tc.head_why),
                    escape_json_str(&tc.head_how),
                    tc.partition_size,
                )
            }
            None => "null".to_string(),
        };

        let omni_def_json = match &self.omni_definition {
            Some(od) => {
                let aside_str = match &od.aside_intent {
                    Some(a) => format!("\"{}\"", escape_json_str(a)),
                    None => "null".to_string(),
                };
                let block_str = match od.block_kind {
                    Some(b) => format!("\"{}\"", b.name()),
                    None => "null".to_string(),
                };
                let doc_comments_arr = od
                    .doc_comments
```

```
                    .iter()
                    .map(|c| format!("\"{}\"", escape_json_str(c)))
                    .collect::<Vec<_>>()
                    .join(",");
                let fields_obj = od
                    .fields
                    .iter()
                    .map(|(k, v)| format!("\"{}\":\"{}\"", escape_json_str(k), escape_json_str(v)))
                    .collect::<Vec<_>>()
                    .join(",");

                format!(
                    r#"{{"name":"{}","boundary_type":"{}","rank":{},"part_of_speech":"{}","aside_intent":
{},"doc_comments":[{}],"block_kind":{},"source_file":"{}","line":{},"fields":{{{}}}}}"#,
                    escape_json_str(&od.name),
                    escape_json_str(&od.boundary_type.to_string()),
                    od.rank,
                    escape_json_str(od.part_of_speech),
                    aside_str,
                    doc_comments_arr,
                    block_str,
                    escape_json_str(&od.source_file),
                    od.line,
                    fields_obj,
                )
            }
            None => "null".to_string(),
        };

        format!(
            r#"{{"symbol":"{}","is_locally_redefined":{},"tape_context":{},"omni_definition":{},"markdown":"{}"}}"#,
            escape_json_str(&self.symbol),
            self.is_locally_redefined,
            tape_ctx_json,
            omni_def_json,
            escape_json_str(&self.markdown),
        )
    }

    /// Renders an ANSI-styled human terminal presentation of the 3-tier hover card.
    pub fn render_terminal(&self) -> String {
        let mut out = String::new();

out.push_str("\x1b[1;36m================================================================================\x1b[0m\n");
        let rank_desc = if let Some(def) = &self.omni_definition {
            def.boundary_type.rank_name()
        } else if self.is_locally_redefined {
            "Rank 2: Denotative Essence [ ... ]"
        } else {
            "Process Tape Entity"
        };
        out.push_str(&format!(
            "\x1b[1;36m  OmniCode Symbol Inspection: \x1b[1;32m{}\x1b[0m \x1b[1;33m({})\x1b[0m\n",
            self.symbol, rank_desc
        ));

out.push_str("\x1b[1;36m================================================================================\x1b[0m\n\n");

        if let Some(ctx) = &self.tape_context {
            out.push_str("\x1b[1;33m[TIER 1: HIGH-LEVEL PROCESS TAPE ROLL]\x1b[0m\n");
            out.push_str(&format!("  • Process Ribbon:    \x1b[1;37m{}\x1b[0m ({})\n", ctx.tape_name, ctx.track));
            out.push_str(&format!("  • Active Roll:       \x1b[1;37m{}/{}\x1b[0m -> `{}`\n", ctx.roll_number,
ctx.total_rolls, ctx.raw_roll_text));
            if let Some(aside) = &ctx.roll_aside_intent {
                out.push_str(&format!("  • Roll Intent Aside: \x1b[3m\"{}\"\x1b[0m\n", aside));
            }
            out.push_str(&format!("  • Covenant Head:     WHO {} -> WHAT {} (WHY: \"{}\")\n", ctx.head_who,
ctx.head_what, ctx.head_why));
            if self.is_locally_redefined {
                out.push_str("  • \x1b[1;32m[Locally Instantiated]\x1b[0m Concrete Denotation assigned on this
ribbon.\n");
            }
            out.push('\n');
        }

        out.push_str("\x1b[1;32m[TIER 2: UNDER-THE-HOOD .OMNI BLUEPRINT]\x1b[0m\n");
        if let Some(def) = &self.omni_definition {
            let block = def.block_kind.map(|b| b.name()).unwrap_or("Declarative Scope");
```

```
            out.push_str(&format!("  • Grounded Source:   \x1b[1;37m{}:{}\x1b[0m\n", def.source_file, def.line));
            out.push_str(&format!("  • 4-Block Origin:    \x1b[1;35m{}\x1b[0m\n", block));
            out.push_str(&format!("  • Ontological Rank:  Rank {} ({})\n", def.rank, def.boundary_type));
            if let Some(aside) = &def.aside_intent {
                out.push_str(&format!("  • Contract Intent:   \x1b[3m\"{}\"\x1b[0m\n", aside));
            }
            if !def.doc_comments.is_empty() {
                out.push_str("  • Doc Comments:\n");
                for c in &def.doc_comments {
                    out.push_str(&format!("      # {}\n", c));
                }
            }
            if !def.fields.is_empty() {
                out.push_str("  • Axiomatic Fields:\n");
                for (k, v) in &def.fields {
                    out.push_str(&format!("      - {}: {}\n", k, v));
                }
            }
        } else {
            out.push_str("  • Status: Runtime dynamic process symbol; inherits ambient defaults.\n");
        }
        out.push('\n');

        out.push_str("\x1b[1;35m[TIER 3: MACHINE EXECUTION & SILICON FOOTPRINT]\x1b[0m\n");
        let partition = self.tape_context.as_ref().map(|c| format!("{} cells", c.partition_size)).unwrap_or_else(|| "1024
cells".to_string());
        out.push_str(&format!("  • Partition Reservation: \x1b[1;37m{}\x1b[0m\n", partition));
        out.push_str("  • Transducer Codec:      Dense Byte <-> 5 Balanced Trits (Radix-3 [-121..+121])\n");
        out.push_str("  • Silicon Truth State:   \x1b[1;32m+1:PROCEED\x1b[0m (Deterministic commit, transactional
rollback)\n");

        out
    }
}

/// Cross-file symbol indexer and hover resolution engine.
pub struct HoverEngine {
    pub logger: DiagnosticLogger,
    /// Indexed definitions mapped by identifier name (case-sensitive and lowercase).
    definitions: HashMap<String, OmniDefinition>,
    /// Map of file path -> list of symbol names defined in that file.
    file_symbols: HashMap<String, Vec<String>>,
}

impl HoverEngine {
    /// Instantiates a new HoverEngine with diagnostic logging.
    pub fn new(logger: DiagnosticLogger) -> Self {
        Self {
            logger,
            definitions: HashMap::new(),
            file_symbols: HashMap::new(),
        }
    }

    /// Looks up an indexed definition by name.
    pub fn lookup_definition(&self, symbol: &str) -> Option<&OmniDefinition> {
        self.definitions.get(symbol).or_else(|| self.definitions.get(&symbol.to_lowercase()))
    }

    /// Resolves documentation for a symbol, optionally indexing a target file first.
    pub fn document_symbol(&mut self, symbol: &str, file_hint: Option<&str>) -> Option<HoverCard> {
        if let Some(path) = file_hint {
            if path.ends_with(".tape") {
                return self.resolve_symbol_for_tape(path, symbol, 0);
            } else {
                let _ = self.index_file(path);
            }
        }

        let def = self.lookup_definition(symbol).cloned();
        let markdown = self.format_omni_only_markdown(symbol, def.as_ref());
        Some(HoverCard {
            symbol: symbol.to_string(),
            tape_context: None,
            omni_definition: def,
            is_locally_redefined: false,
            markdown,
        })
```

```
    }
}


// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Indexing Passes, Cross-File Symbol Inheritance & Markdown Hover Generation )
// ================================================================================

impl HoverEngine {
    /// Indexes a `.omni` source reel string, extracting all entities, boundaries,
    /// docstrings, attached Asides, and block origins.
    pub fn index_omni_source(&mut self, file_path: &str, content: &str) -> Result<usize, String> {
        let lines: Vec<&str> = content.lines().collect();
        let mut current_block = None;
        let mut count = 0;

        // Pass 1: Parse block layout
        let mut line_blocks = vec![None; lines.len()];
        for (idx, line) in lines.iter().enumerate() {
            let upper = line.to_uppercase();
            if upper.contains("BLOCK 1") || upper.contains("METADATA BLOCK") {
                current_block = Some(BlockKind::Metadata);
            } else if upper.contains("BLOCK 2") || upper.contains("OPENING BLOCK") {
                current_block = Some(BlockKind::Opening);
            } else if upper.contains("BLOCK 3") || upper.contains("BODY BLOCK") {
                current_block = Some(BlockKind::Body);
            } else if upper.contains("BLOCK 4") || upper.contains("CLOSING BLOCK") {
                current_block = Some(BlockKind::Closing);
            }
            line_blocks[idx] = current_block;
        }

        // Pass 2: Tokenize and build AST to extract formal Entities
        let mut lexer = Lexer::new(content, self.logger.clone());
        let tokens = lexer.tokenize()?;
        let debugger = crate::diagnostics::debugger::OmniDebugger::new(self.logger.clone(), 10);
        let mut parser = Parser::new(tokens, debugger);

        // Best-effort parse program
        if let Ok(prog) = parser.parse_program() {
            for stmt in &prog.statements {
                if let ASTNode::Entity(entity) = stmt {
                    let def = self.build_omni_definition(entity, file_path, &lines, &line_blocks);
                    let name = def.name.clone();
                    self.insert_definition(name.clone(), def);
                    self.file_symbols
                        .entry(file_path.to_string())
                        .or_default()
                        .push(name);
                    count += 1;
                }
            }
        }

        // Pass 3: Textual line-by-line fallback for inner fields and registers
        for (idx, line) in lines.iter().enumerate() {
            let trimmed = line.trim();
            if trimmed.starts_with('#') || trimmed.is_empty() {
                continue;
            }

            // Detect field patterns: `name: < ... > ( ... )` or `name [ ... ] ( ... )`
            if let Some(colon_pos) = trimmed.find(':') {
                let id_candidate = trimmed[..colon_pos].trim();
                if is_valid_identifier(id_candidate) && !self.definitions.contains_key(id_candidate) {
                    let rest = trimmed[colon_pos + 1..].trim();
                    let btype = detect_boundary_type_from_str(rest);
                    let aside = extract_aside_from_str(rest);
                    let doc_comments = extract_preceding_comments(&lines, idx);

                    let def = OmniDefinition {
                        name: id_candidate.to_string(),
                        boundary_type: btype,
                        rank: btype.rank(),
                        part_of_speech: "Noun",
                        aside_intent: aside,
                        doc_comments,
```

```
                        block_kind: line_blocks[idx],
                        source_file: file_path.to_string(),
                        line: idx + 1,
                        fields: HashMap::new(),
                        machine_representation: Some("Contextual Attribute / Field".into()),
                    };
                    self.insert_definition(id_candidate.to_string(), def);
                    count += 1;
                }
            }

            // Detect standalone registers: `name [ ... ] ( ... )`
            if trimmed.contains('[') && !trimmed.starts_with("roll_") && !trimmed.starts_with("verify:") {
                let id_end = trimmed.find('[').unwrap_or(0);
                let id_candidate = trimmed[..id_end].trim();
                if is_valid_identifier(id_candidate) && !self.definitions.contains_key(id_candidate) {
                    let aside = extract_aside_from_str(trimmed);
                    let doc_comments = extract_preceding_comments(&lines, idx);
                    let def = OmniDefinition {
                        name: id_candidate.to_string(),
                        boundary_type: BoundaryType::Denotation,
                        rank: BoundaryType::Denotation.rank(),
                        part_of_speech: "Noun",
                        aside_intent: aside,
                        doc_comments,
                        block_kind: line_blocks[idx],
                        source_file: file_path.to_string(),
                        line: idx + 1,
                        fields: HashMap::new(),
                        machine_representation: Some("Active State Register".into()),
                    };
                    self.insert_definition(id_candidate.to_string(), def);
                    count += 1;
                }
            }
        }

        self.logger.log(
            "HOVER",
            format!("Indexed {} symbols from .omni source: {}", count, file_path),
        );
        Ok(count)
    }

    /// Indexes a specific file from disk.
    pub fn index_file(&mut self, path: impl AsRef<Path>) -> Result<usize, String> {
        let p = path.as_ref();
        let content = fs::read_to_string(p)
            .map_err(|e| format!("Failed to read file {:?}: {e}", p))?;
        let path_str = p.to_string_lossy().to_string();
        self.index_omni_source(&path_str, &content)
    }

    /// Recursively indexes foundational files and standard libraries across the workspace.
    pub fn index_workspace(&mut self, root_dir: impl AsRef<Path>) {
        let root = root_dir.as_ref();

        // 1. Core manifest
        let manifest_path = root.join("manifest.omni");
        if manifest_path.exists() {
            let _ = self.index_file(&manifest_path);
        }

        // 2. Standard library modules in lib/core/
        let lib_core = root.join("lib/core");
        if lib_core.exists() && lib_core.is_dir() {
            if let Ok(entries) = fs::read_dir(lib_core) {
                for entry in entries.flatten() {
                    let p = entry.path();
                    if p.extension().map_or(false, |ext| ext == "omni") {
                        let _ = self.index_file(&p);
                    }
                }
            }
        }
    }

    /// Helper to store definitions in both exact and lowercase keys for flexible lookup.
```

```
    fn insert_definition(&mut self, key: String, def: OmniDefinition) {
        self.definitions.insert(key.to_lowercase(), def.clone());
        self.definitions.insert(key, def);
    }

    /// Resolves hover information for a symbol used inside a high-level `.tape` process ribbon.
    ///
    /// # Resolution Sequence
    /// 1. Check if defined or redefined in the local `.tape` ribbon.
    /// 2. If companion `.omni` exists (e.g. `foo.tape` -> `foo.omni`), resolve from companion.
    /// 3. Otherwise, resolve from the workspace symbol index (stdlib or manifest).
    /// 4. Generate the composite 3-tier Markdown HoverCard.
    pub fn resolve_symbol_for_tape(
        &mut self,
        tape_path: &str,
        symbol: &str,
        line_number: usize,
    ) -> Option<HoverCard> {
        let tape_p = Path::new(tape_path);

        // Step 1: Ensure companion .omni is indexed if it exists
        let companion_omni = tape_p.with_extension("omni");
        if companion_omni.exists() {
            let _ = self.index_file(&companion_omni);
        }

        // Step 2: Load and inspect the active Tape
        let tape = Tape::from_file(tape_p, self.logger.clone()).ok();

        // Extract Tape Context for this roll
        let mut tape_context = None;
        let mut is_locally_redefined = false;

        if let Some(ref t) = tape {
            let track_str = if tape_path.contains("kernel") || tape_path.contains("boot") {
                "Track 0 [KERNEL]"
            } else if tape_path.contains("terminal") {
                "Track 1 [TERMINAL]"
            } else {
                "Track 2 [APP]"
            };

            // Find roll matching line number that contains symbol, or matching line number, or first roll referencing
symbol
            let matched_roll = t
                .rolls
                .iter()
                .find(|r| r.line_number == line_number && r.text.contains(symbol))
                .or_else(|| t.rolls.iter().find(|r| r.line_number == line_number))
                .or_else(|| t.rolls.iter().find(|r| r.text.contains(symbol)));

            if let Some(r) = matched_roll {
                let roll_aside = extract_aside_from_str(&r.text);

                tape_context = Some(TapeRollContext {
                    tape_name: t.head.name.clone(),
                    track: track_str.to_string(),
                    roll_number: r.index + 1,
                    total_rolls: t.roll_count(),
                    raw_roll_text: r.text.clone(),
                    roll_aside_intent: roll_aside,
                    head_who: t.head.who.clone(),
                    head_what: t.head.what.clone(),
                    head_why: t.head.why.clone(),
                    head_how: t.head.how.clone(),
                    partition_size: t.head.required_partition_size,
                });
            }

            // Check if symbol was given a Denotation anywhere on this tape ribbon: `symbol [ ... ]`
            is_locally_redefined = t.rolls.iter().any(|r| {
                r.text.contains(&format!("{symbol} [")) || r.text.contains(&format!("{symbol}["))
            });
        }

        // Step 3: Lookup low-level .omni definition
        let omni_def = self
            .definitions
```

```
            .get(symbol)
            .cloned()
            .or_else(|| self.definitions.get(&symbol.to_lowercase()).cloned());

        // Build Markdown card
        let markdown = self.format_composite_markdown(
            symbol,
            tape_context.as_ref(),
            omni_def.as_ref(),
            is_locally_redefined,
        );

        Some(HoverCard {
            symbol: symbol.to_string(),
            tape_context,
            omni_definition: omni_def,
            is_locally_redefined,
            markdown,
        })
    }

    /// Resolves hover information at a specific file coordinate `(line, col)`.
    pub fn hover_at(&mut self, file_path: &str, line: usize, col: usize) -> Option<HoverCard> {
        let content = fs::read_to_string(file_path).ok()?;
        let lines: Vec<&str> = content.lines().collect();
        if line == 0 || line > lines.len() {
            return None;
        }

        let target_line = lines[line - 1];
        let symbol = extract_word_at_col(target_line, col)?;

        if file_path.ends_with(".tape") {
            self.resolve_symbol_for_tape(file_path, &symbol, line)
        } else {
            // Index the file itself if not already done
            let _ = self.index_omni_source(file_path, &content);
            let def = self
                .definitions
                .get(&symbol)
                .cloned()
                .or_else(|| self.definitions.get(&symbol.to_lowercase()).cloned());

            let markdown = self.format_omni_only_markdown(&symbol, def.as_ref());
            Some(HoverCard {
                symbol: symbol.clone(),
                tape_context: None,
                omni_definition: def,
                is_locally_redefined: false,
                markdown,
            })
        }
    }

    /// Formats the complete 3-Tier Markdown HoverCard bridging .tape down to .omni.
    fn format_composite_markdown(
        &self,
        symbol: &str,
        tape_ctx: Option<&TapeRollContext>,
        omni_def: Option<&OmniDefinition>,
        is_redefined: bool,
    ) -> String {
        let mut md = String::new();

        // ------------------------------------------------------------------
        // HEADER: Identity & Morphological Badging
        // ------------------------------------------------------------------
        let rank_badge = if let Some(def) = omni_def {
            format!("`{}`", def.boundary_type.rank_name())
        } else if is_redefined {
            "`Rank 2: Denotative Essence [ ... ]`".to_string()
        } else {
            "`Process Tape Entity`".to_string()
        };

        md.push_str(&format!("### `{symbol}` — {}\n\n", rank_badge));

        // ------------------------------------------------------------------
```

```
        // TIER 1: HIGH-LEVEL PROCESS TAPE ROLL (Process Intent & Active Sentence)
        // ------------------------------------------------------------------------
        if let Some(ctx) = tape_ctx {
            md.push_str("#### 📜 1. High-Level Process Tape View\n");
            md.push_str(&format!(
                "* **Process Ribbon:** `{}` on `{}`\n",
                ctx.tape_name, ctx.track
            ));
            md.push_str(&format!(
                "* **Active Roll ({}/{}):** `{}`\n",
                ctx.roll_number, ctx.total_rolls, ctx.raw_roll_text
            ));

            if let Some(ref intent) = ctx.roll_aside_intent {
                md.push_str(&format!("* **Roll Intent Aside:** *\"{}\"*\n", intent));
            }

            md.push_str(&format!(
                "* **Tape Head Covenant:** WHO `{}` $\\to$ WHAT `{}` (Purpose: *\"{}\"*)\n",
                ctx.head_who, ctx.head_what, ctx.head_why
            ));

            if is_redefined {
                md.push_str(
                    "\n> [!NOTE]\n> **Locally Defined:** This entity receives a concrete Denotation `[ ... ]` in this tape ribbon, instantiating it into active memory.\n",
                );
            }
            md.push_str("\n---\n\n");
        }

        // ------------------------------------------------------------------------
        // TIER 2: UNDER-THE-HOOD LOW-LEVEL BLUEPRINT (.omni Blueprint & Contract)
        // ------------------------------------------------------------------------
        md.push_str("#### 🔍 2. Under-The-Hood (.omni Blueprint)\n");
        if let Some(def) = omni_def {
            let block_name = def
                .block_kind
                .map(|b| b.name())
                .unwrap_or("Declarative Scope");
            md.push_str(&format!(
                "* **Grounded Source:** [`{}`]({}) (Line {})\n",
                def.source_file, def.source_file, def.line
            ));
            md.push_str(&format!("* **4-Block Origin:** `{block_name}`\n"));
            md.push_str(&format!(
                "* **Ontological Hierarchy:** Rank {} (`{}`)\n",
                def.rank, def.boundary_type
            ));

            if let Some(ref intent) = def.aside_intent {
                md.push_str(&format!("* **Contract Intent Aside:** *\"{}\"*\n", intent));
            }

            if !def.doc_comments.is_empty() {
                md.push_str("* **Architectural Description:**\n");
                for comment in &def.doc_comments {
                    md.push_str(&format!("  > {comment}\n"));
                }
            }

            if !def.fields.is_empty() {
                md.push_str("* **Sub-Attributes & Invariant Axioms:**\n");
                for (k, v) in &def.fields {
                    md.push_str(&format!("  * `{k}`: `{v}`\n"));
                }
            }
        } else {
            md.push_str("* **Under-The-Hood Status:** Pure runtime process entity; inherits standard library defaults.\n");
        }
        md.push_str("\n---\n\n");

        // ------------------------------------------------------------------------
        // TIER 3: MACHINE EXECUTION & SILICON EFFECT
        // ------------------------------------------------------------------------
        md.push_str("#### ⚙️ 3. Machine Execution & Silicon State\n");
        let partition = tape_ctx
```

```
            .map(|c| format!("{} cells", c.partition_size))
            .unwrap_or_else(|| "1024 cells".to_string());

        md.push_str(&format!(
            "* **Memory Allocation:** Partition reservation ceiling: `{partition}`\n"
        ));
        md.push_str("* **Transducer Codec:** Dense byte $\\longleftrightarrow$ 5 balanced trits ($[-121 \\dots +121]$
Radix-3)\n");
        md.push_str("* **Execution Truth State:** `+1: PROCEED` (Deterministic commit, transactional rollback
protection)\n");

        md
    }

    /// Formats a hover card when hovering directly inside a `.omni` source reel.
    fn format_omni_only_markdown(&self, symbol: &str, def: Option<&OmniDefinition>) -> String {
        let mut md = String::new();
        if let Some(d) = def {
            let block_name = d.block_kind.map(|b| b.name()).unwrap_or("Universal Scope");
            md.push_str(&format!(
                "### `{}` — `{}`\n\n",
                d.name,
                d.boundary_type.rank_name()
            ));
            md.push_str(&format!("* **Origin:** `{block_name}` (Line {})\n", d.line));
            md.push_str(&format!("* **Part of Speech:** `{}`\n", d.part_of_speech));

            if let Some(ref intent) = d.aside_intent {
                md.push_str(&format!("* **Machine Intent Aside:** *\"{}\"*\n", intent));
            }

            if !d.doc_comments.is_empty() {
                md.push_str("\n#### Architectural Docstring:\n");
                for c in &d.doc_comments {
                    md.push_str(&format!("> {c}\n"));
                }
            }

            if !d.fields.is_empty() {
                md.push_str("\n#### Invariant Fields:\n");
                for (k, v) in &d.fields {
                    md.push_str(&format!("* `{k}`: `{v}`\n"));
                }
            }
        } else {
            md.push_str(&format!("### `{symbol}`\n\n"));
            md.push_str("* **Classification:** OmniCode Identifier\n");
            md.push_str("* **Scope:** Ambient Context\n");
        }
        md
    }

    /// Internal helper converting an AST EntityNode into an OmniDefinition.
    fn build_omni_definition(
        &self,
        entity: &EntityNode,
        file_path: &str,
        lines: &[&str],
        line_blocks: &[Option<BlockKind>],
    ) -> OmniDefinition {
        let line_idx = entity.line.saturating_sub(1);
        let block_kind = line_blocks.get(line_idx).copied().flatten();
        let doc_comments = extract_preceding_comments(lines, line_idx);
        let btype = entity.definition.boundary_type;

        let mut fields = HashMap::new();
        // Extract subfields if this was a record with key-value entries
        if line_idx < lines.len() {
            for l in &lines[line_idx..line_idx.saturating_add(15).min(lines.len())] {
                let trimmed = l.trim();
                if trimmed.starts_with('}') || trimmed.starts_with(']') {
                    break;
                }
                if let Some(colon) = trimmed.find(':') {
                    let k = trimmed[..colon].trim();
                    let v = trimmed[colon + 1..].trim().trim_end_matches(',');
                    if is_valid_identifier(k) {
                        fields.insert(k.to_string(), v.to_string());
```

```
                    }
                }
            }
        }

        let aside_intent = entity
            .aside
            .as_ref()
            .or(entity.definition.aside.as_ref())
            .or(entity.context.as_ref().and_then(|c| c.aside.as_ref()))
            .map(|a| a.intent.clone())
            .or_else(|| {
                if line_idx < lines.len() {
                    extract_aside_from_str(lines[line_idx])
                } else {
                    None
                }
            });

        OmniDefinition {
            name: entity.name.clone(),
            boundary_type: btype,
            rank: btype.rank(),
            part_of_speech: "Noun",
            aside_intent,
            doc_comments,
            block_kind,
            source_file: file_path.to_string(),
            line: entity.line,
            fields,
            machine_representation: Some(format!("Ontological Essence ({})", btype)),
        }
    }
}


// ------------------------------------------------------------------------------
// HELPER UTILITIES: Token extraction, comments, and delimiters
// ------------------------------------------------------------------------------

fn escape_json_str(s: &str) -> String {
    let mut out = String::with_capacity(s.len());
    for c in s.chars() {
        match c {
            '"' => out.push_str("\\\""),
            '\\' => out.push_str("\\\\"),
            '\n' => out.push_str("\\n"),
            '\r' => out.push_str("\\r"),
            '\t' => out.push_str("\\t"),
            c => out.push(c),
        }
    }
    out
}

fn is_valid_identifier(s: &str) -> bool {
    if s.is_empty() {
        return false;
    }
    let first = s.chars().next().unwrap();
    (first.is_alphabetic() || first == '_') && s.chars().all(|c| c.is_alphanumeric() || c == '_')
}

fn extract_word_at_col(line: &str, col: usize) -> Option<String> {
    if line.is_empty() {
        return None;
    }
    let chars: Vec<char> = line.chars().collect();
    let idx = col.saturating_sub(1).min(chars.len().saturating_sub(1));

    if !chars[idx].is_alphanumeric() && chars[idx] != '_' {
        return None;
    }

    let mut start = idx;
    while start > 0 && (chars[start - 1].is_alphanumeric() || chars[start - 1] == '_') {
        start -= 1;
    }
```

```
    let mut end = idx;
    while end + 1 < chars.len() && (chars[end + 1].is_alphanumeric() || chars[end + 1] == '_') {
        end += 1;
    }

    Some(chars[start..=end].iter().collect())
}

fn extract_aside_from_str(text: &str) -> Option<String> {
    let start = text.find('(')?;
    let end = text.rfind(')')?;
    if end > start {
        Some(text[start + 1..end].trim().to_string())
    } else {
        None
    }
}

fn detect_boundary_type_from_str(s: &str) -> BoundaryType {
    if s.contains('<') && s.contains('>') {
        BoundaryType::Invariant
    } else if s.contains('{') && s.contains('}') {
        BoundaryType::Connotation
    } else if s.contains('{') && s.contains(']') {
        BoundaryType::TopDown
    } else if s.contains('[') && s.contains('}') {
        BoundaryType::BottomUp
    } else {
        BoundaryType::Denotation
    }
}

fn extract_preceding_comments(lines: &[&str], line_idx: usize) -> Vec<String> {
    let mut comments = Vec::new();
    let mut cur = line_idx;
    while cur > 0 {
        cur -= 1;
        let trimmed = lines[cur].trim();
        if trimmed.starts_with('#') {
            let clean = trimmed.trim_start_matches('#').trim();
            // Ignore boundary separator bars: ====== or ------
            if !clean.starts_with('=') && !clean.starts_with('-') && !clean.is_empty() {
                comments.push(clean.to_string());
            }
        } else {
            break;
        }
    }
    comments.reverse();
    comments
}


// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Tests, Verification & Subsystem Sealing )
// ================================================================================

#[cfg(test)]
mod tests {
    use super::*;

    #[test]
    fn test_hover_engine_manifest_omni_indexing() {
        let logger = DiagnosticLogger::new(false);
        let mut engine = HoverEngine::new(logger);

        let manifest_content = r#"
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ================================================================================
# LAW 1: TRUTH & FIDELITY
# Unalterable prohibition against deceit.
Law_Truth < Invariant > ( Invariant Contract: Prohibit deception ) {
    commandment: < "Thou shalt not bear false witness." >,
    resonance: < +1:PROCEED >
}
```

```
# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
covenant_active [ +1 : State? ] ( Active State Register )
        "#;

        let count = engine
            .index_omni_source("manifest.omni", manifest_content)
            .expect("Indexing must succeed");

        assert!(count >= 2);

        // Verify Law_Truth extraction
        let law_def = engine.definitions.get("Law_Truth").expect("Must index Law_Truth");
        assert_eq!(law_def.boundary_type, BoundaryType::Invariant);
        assert_eq!(law_def.rank, 1);
        assert_eq!(law_def.block_kind, Some(BlockKind::Metadata));
        assert!(law_def.aside_intent.as_ref().unwrap().contains("Prohibit deception"));
        assert!(law_def.doc_comments.iter().any(|c| c.contains("TRUTH & FIDELITY")));
    }

    #[test]
    fn test_cross_file_tape_to_omni_hover_resolution() {
        let logger = DiagnosticLogger::new(false);
        let mut engine = HoverEngine::new(logger);

        // Index low-level omni
        let omni_content = r#"
# BLOCK 1: METADATA
# System version invariant
Version < "1.0.0" > ( Baseline release )
        "#;
        engine.index_omni_source("test.omni", omni_content).unwrap();

        // Synthetic tape source
        let tape_content = r#"
[Tape.TestProcess] : WHO {Kernel} WHAT {Test} --> BOOT {Hardware}
    WHEN {Boot}
    WHERE {partition} = [ 256 ]
    WHY ( Test ribbon )
    HOW [ +1 : PROCEED ]

roll_1 [ Version [ "1.0.0" ] ] ( Concrete definition in memory )
roll_2 [ commit_status [ PROCEED ] ]
        "#;

        // Temporarily write tape file to test directory
        let temp_dir = std::env::temp_dir();
        let tape_path = temp_dir.join("test.tape");
        let omni_path = temp_dir.join("test.omni");
        fs::write(&tape_path, tape_content).unwrap();
        fs::write(&omni_path, omni_content).unwrap();

        let card = engine
            .resolve_symbol_for_tape(tape_path.to_str().unwrap(), "Version", 9)
            .expect("Must resolve hover card");

        assert_eq!(card.symbol, "Version");
        assert!(card.is_locally_redefined);
        assert!(card.tape_context.is_some());
        assert!(card.markdown.contains("High-Level Process Tape View"));
        assert!(card.markdown.contains("Under-The-Hood (.omni Blueprint)"));
        assert!(card.markdown.contains("Machine Execution & Silicon State"));

        // Clean up temp files
        fs::remove_file(tape_path).ok();
        fs::remove_file(omni_path).ok();
    }
}
```

OmniCode: Chapter 10: Track 1 - Verification & Functional Test Suites

Integrated Tripwires, Boot Tests & Functional Execution

CHAPTER IDENTIFIER
CH 10

NOTEBOOKLM WORD COUNT
11,312 words

CATALOGED CHAPTER FILES
6 files (2,673 lines)

GENERATION DATE
2026-10-16 20:36:02

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"How do tripwire tests prove zero-disk-mutation on dry run?"*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (6 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 1> : {Host Engine & Virtual Machine}/tests/integrated/assemble_tripwire_tests.rs**	RS	305	1,255	13.2
2	**<TRACK 1> : {Host Engine & Virtual Machine}/tests/integrated/boot_tripwire_tests.rs**	RS	275	1,137	12.8
3	**<TRACK 1> : {Host Engine & Virtual Machine}/tests/integrated/main.rs**	RS	433	1,808	19.6
4	**<TRACK 1> : {Host Engine & Virtual Machine}/tests/integrated/platform_tripwire_tests.rs**	RS	241	1,214	11.6
5	**<TRACK 1> : {Host Engine & Virtual Machine}/tests/functional/main.rs**	RS	593	2,494	26.5
6	**<TRACK 1> : {Host Engine & Virtual Machine}/tests/unit/main.rs**	RS	826	3,404	39.4

<TRACK 1> : {Host Engine & Virtual Machine}/tests/integrated/assemble_tripwire_tests.rs RS | 305 LINES | 1255 WORDS | 13.2 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Physical Assembler Tripwire, Adversarial Faults & Telemetry Oracle Manifest )
// ============================================================================
//! MODULE:              tests::integrated::assemble_tripwire_tests
//! IDENTITY:            Physical Assembler Adversarial Fault Injection & Telemetry Oracle Suite
//! NATURE:              Modular Integration Test Sandbox & Destructive Lowering Certifier
//! VERSION:             0.1.0
//! CREATED:             2026-10-11
//! LAST_SEALED:         2026-10-11
//! AUTHOR:              CreativeWorkzStudio LLC / ProfessorSeanEX
//! COVENANT:            Public Domain / MIT
//!
//! SCHEDULER:
//!   TRACK_PRIMARY:     <TRACK 1> : {Host Engine & Virtual Machine}
//!   TRACKS_TOUCHED:    [ <TRACK 0> : {Silicon & Bare-Metal Kernel}, <TRACK 1>, <TRACK 2> : {OmniCode Language & Standard Library} ]
//!   PRIORITY:          TaskPriority::High
//!   CHANNEL:           Track::Kernel
//!
//! CONTRACT / WHO-WHAT-WHERE-WHY-HOW:
//!   WHO:               OmniCode Adversarial Assembler Oracle & Machine Lowering Tester
//!   WHAT:              Deliberately push the process tape assembler to fail under adversarial conditions:
//!                      missing files across 6-track roots, invalid file extensions, malformed grammar tapes,
//!                      unsealed commit invariants, and unwritable filesystem destinations.
//!   WHERE:             Track 1 Test Harness -> Assembler Lowering Engine -> DiagnosticLogger & Restorator
//!   WHEN:              Executed during comprehensive test suites and regression certification
//!   WHY:               Ensure that corrupted, malicious, or misconfigured process tapes never cause
//!                      unhandled panics or uncontrolled memory states, and that all failures emit
//!                      crisp balanced-ternary rollback telemetry (-1:ROLLBACK).
//!   HOW:               Adversarial fault injection ("push to fail"): if the test passes, it is
//!                      because the failure was caught and handled by tripwires, NOT because of soft checks.
//!
//! TOUCHES / FILESYSTEM FOOTPRINT:
//!   - LOGS:            Inscribed in-memory DiagnosticLogger ring buffers
//!   - DISK:            Temporary test tapes written to `/tmp` and cleaned up immediately
//!
//! TRIPWIRE REGISTRY:
//!   - `TRIPWIRE_INPUT_RESOLVE`       (Asserts missing file resolution trips rollback)
//!   - `TRIPWIRE_FILETYPE_VALIDATION` (Asserts non-tape/non-omni extensions trip rollback)
//!   - `TRIPWIRE_SYNTAX_TOKENIZATION` (Asserts malformed process ribbons trip rollback)
//!   - `TRIPWIRE_COMMIT_INVARIANT`    (Asserts unsealed commit status trips rollback)
//!   - `TRIPWIRE_OUTPUT_SERIALIZE`    (Asserts unwritable destination trips rollback)
//!   - `TRIPWIRE_DRY_RUN_GUARD`       (Asserts dry-run guarantees zero disk mutation)
//!   - `TRIPWIRE_BATON_PASS_WORDS`    (Asserts physical silicon word emission integrity)

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Scoped Imports, Test Fixtures & Environment Setup )
// ============================================================================
use std::fs;
use std::path::PathBuf;

use omnicode::cli::commands::assemble::{
    AssembleConfig, AssembleFormat, execute_assemble_pipeline, serialize_assembled_output,
};
use omnicode::core::filetype::resolve_track_path;
use omnicode::core::ternary::QuadState;
use omnicode::diagnostics::logger::{DiagnosticLogger, FailpointType};

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Adversarial Tests: Pushing Assembler to Fail & Lowering Telemetry Oracles )
// ============================================================================

/// Test 1: Adversarial Process Tape Resolution Failure.
///
/// Deliberately queries a non-existent process tape across all 6 track roots.
/// Pushes `AssembleConfig::open` to fail, verifying that:
/// 1. A `TripwireError` is returned with channel `"TRIPWIRE_INPUT_RESOLVE"`.
/// 2. Failpoint classification is [`FailpointType::SyntaxAnomaly`].
/// 3. The recovery state is affirmative rollback (`-1:ROLLBACK`).
/// 4. The attached [`DiagnosticLogger`] in-memory trace registers the failpoint.
```

```rust
#[test]
fn test_adversarial_assemble_missing_file_trips_preflight() {
    let logger = DiagnosticLogger::new(false);
    let config = AssembleConfig::new("nonexistent_phantom_root/phantom_tape_999.tape");

    let open_result = config.open(&logger);
    assert!(open_result.is_err(), "Non-existent process tape MUST trip pre-flight resolution");

    let err = open_result.unwrap_err();
    assert_eq!(err.channel, "TRIPWIRE_INPUT_RESOLVE");
    assert_eq!(err.failpoint_type, FailpointType::SyntaxAnomaly);
    assert_eq!(err.recovery_state, QuadState::Rollback);

    assert!(logger.has_failpoints(), "DiagnosticLogger must capture the failpoint");
    let fps = logger.failpoints();
    assert_eq!(fps.len(), 1);
    assert_eq!(fps[0].channel, "TRIPWIRE_INPUT_RESOLVE");
}

/// Test 2: Adversarial File Extension Rejection.
///
/// Provides a path that exists on disk (e.g. `Cargo.toml`), but has an unsupported
/// extension. Verifies that the assembler strictly refuses to assemble arbitrary files,
/// requiring `.tape` (process ribbon) or `.omni` (declarative spatial reel).
#[test]
fn test_adversarial_assemble_invalid_extension_trips() {
    let logger = DiagnosticLogger::new(false);
    let config = AssembleConfig::new("Cargo.toml");

    let open_result = config.open(&logger);
    assert!(open_result.is_err(), "Invalid file extension MUST trip pre-flight validation");

    let err = open_result.unwrap_err();
    assert_eq!(err.channel, "TRIPWIRE_FILETYPE_VALIDATION");
    assert_eq!(err.failpoint_type, FailpointType::SyntaxAnomaly);
    assert_eq!(err.recovery_state, QuadState::Rollback);

    assert!(err.message.contains("unsupported extension"));
}

/// Test 3: Adversarial Malformed Process Ribbon Syntax.
///
/// Injects a syntactically broken tape containing unclosed boundaries and corrupted
/// directional vectors. Pushes `execute_assemble_pipeline` to fail, ensuring that
/// the lowering engine traps the error via [`FailpointType::SyntaxAnomaly`] without panicking.
#[test]
fn test_adversarial_assemble_corrupted_syntax_tape_trips() {
    let logger = DiagnosticLogger::new(false);
    let temp_tape_path = PathBuf::from("/tmp/omnicode_corrupted_syntax_test.tape");

    // Intentionally corrupted tape: unclosed delimiter and invalid token grammar
    let bad_source = r#"
[Tape.Corrupted]
    who: "AdversarialAgent",
    what: "InjectAnomaly"

TAPE HEAD:
    direction: +1:PROCEED,
    partition: 64

SUBORDINATE ROLLS:
    roll 1: [ BrokenBoundary < 42 ]
"#;

    fs::write(&temp_tape_path, bad_source).expect("Writing temporary corrupted tape");

    let config = AssembleConfig::new(&temp_tape_path);
    let mut ctx = config.open(&logger).expect("Preflight opening valid path");

    let assemble_result = execute_assemble_pipeline(&mut ctx);
    assert!(assemble_result.is_err(), "Corrupted tape syntax MUST trip assembly pipeline");

    let err = assemble_result.unwrap_err();
    assert_eq!(err.channel, "TRIPWIRE_SYNTAX_TOKENIZATION");
    assert_eq!(err.failpoint_type, FailpointType::SyntaxAnomaly);
    assert_eq!(err.recovery_state, QuadState::Rollback);

    let _ = fs::remove_file(&temp_tape_path);
```

```
}

/// Test 4: Adversarial Commit Invariant Breach.
///
/// Injects a process tape whose execution or declaration does NOT conclude with
/// `commit_status [ PROCEED ]`. Asserts that `Tripwire::assert_quad_state_proceed`
/// fires on `"TRIPWIRE_COMMIT_INVARIANT"`, halting assembly.
#[test]
fn test_adversarial_assemble_unsealed_commit_status_trips() {
    let logger = DiagnosticLogger::new(false);
    let temp_tape_path = PathBuf::from("/tmp/omnicode_unsealed_commit_test.tape");

    // Tape explicitly concludes with Rollback instead of Proceed
    let rollback_tape = r#"
[Tape.RollbackTrap]
    who: "AdversarialTester",
    what: "TrapCommitInvariant"

TAPE HEAD:
    direction: -1:ROLLBACK,
    partition: 128

SUBORDINATE ROLLS:
    roll 1: execute [ NopOperation ]
    roll 2: commit_status [ ROLLBACK ]
"#;

    fs::write(&temp_tape_path, rollback_tape).expect("Writing temporary rollback tape");

    let config = AssembleConfig::new(&temp_tape_path);
    let mut ctx = config.open(&logger).expect("Preflight opening valid path");

    let assemble_result = execute_assemble_pipeline(&mut ctx);
    assert!(assemble_result.is_err(), "Unsealed commit status MUST trip invariant assertion");

    let err = assemble_result.unwrap_err();
    assert_eq!(err.channel, "TRIPWIRE_COMMIT_INVARIANT");
    assert_eq!(err.failpoint_type, FailpointType::RollbackTriggered);
    assert_eq!(err.recovery_state, QuadState::Rollback);

    let _ = fs::remove_file(&temp_tape_path);
}

/// Test 5: Adversarial Output Path Permission & Serialization Failure.
///
/// Points the output path to a directory that cannot be written (e.g. `/dev/null/forbidden/out.asm`).
/// Verifies that disk serialization catches the IO error, tripwires `"TRIPWIRE_OUTPUT_SERIALIZE"`,
/// and returns `-1:ROLLBACK` without panicking.
#[test]
fn test_adversarial_assemble_output_unwritable_path_trips() {
    let logger = DiagnosticLogger::new(false);
    let boot_tape = resolve_track_path("lib/kernel/boot.tape");
    if !boot_tape.exists() {
        return;
    }

    let config = AssembleConfig {
        input_path: boot_tape,
        output_path: Some(PathBuf::from("/dev/null/forbidden_nonexistent_dir/output.asm")),
        format: AssembleFormat::Listing,
        verbose: false,
        strict: false,
        dry_run: false,
    };

    let mut ctx = config.open(&logger).expect("Preflight opening valid boot tape");
    let assembled = execute_assemble_pipeline(&mut ctx).expect("Assembling boot tape");

    let serialize_result = serialize_assembled_output(&assembled, &config, &logger);
    assert!(serialize_result.is_err(), "Unwritable output destination MUST trip serialization");

    let err = serialize_result.unwrap_err();
    assert_eq!(err.channel, "TRIPWIRE_OUTPUT_SERIALIZE");
    assert_eq!(err.failpoint_type, FailpointType::SyntaxAnomaly);
    assert_eq!(err.recovery_state, QuadState::Rollback);
}

/// Test 6: Dry Run Safety Invariant (Zero Disk Mutation).
```

```rust
///
/// Verifies that when `--dry-run` is active, the assembler completes all lowering,
/// symbol resolution, and formatting, but GUARANTEES that the output file is NOT written.
#[test]
fn test_assemble_dry_run_guarantees_zero_disk_mutation() {
    let logger = DiagnosticLogger::new(false);
    let boot_tape = resolve_track_path("lib/kernel/boot.tape");
    if !boot_tape.exists() {
        return;
    }

    let ghost_output = PathBuf::from("/tmp/omnicode_ghost_dry_run_artifact.asm");
    if ghost_output.exists() {
        let _ = fs::remove_file(&ghost_output);
    }

    let config = AssembleConfig {
        input_path: boot_tape,
        output_path: Some(ghost_output.clone()),
        format: AssembleFormat::Words,
        verbose: false,
        strict: false,
        dry_run: true, // Dry run enabled
    };

    let mut ctx = config.open(&logger).expect("Preflight opening boot tape");
    let assembled = execute_assemble_pipeline(&mut ctx).expect("Lowering pipeline");

    let result = serialize_assembled_output(&assembled, &config, &logger);
    assert!(result.is_ok(), "Dry run serialization must succeed without error");
    assert!(!ghost_output.exists(), "Dry run MUST NOT mutate or create output file on disk");
}

/// Test 7: Baton Pass Integration to Physical Silicon Words.
///
/// Assembles `lib/kernel/boot.tape` and certifies that the resulting `AssembledTape`
/// contains non-trivial physical 64-bit machine words (`Word64`), verified registers,
/// and discrete machine opcodes, validating the complete baton pass to hardware execution.
#[test]
fn test_baton_pass_assemble_to_machine_words_verification() {
    let logger = DiagnosticLogger::new(false);
    let boot_tape = resolve_track_path("lib/kernel/boot.tape");
    if !boot_tape.exists() {
        return;
    }

    let config = AssembleConfig {
        input_path: boot_tape,
        output_path: None,
        format: AssembleFormat::Words,
        verbose: false,
        strict: false,
        dry_run: true,
    };

    let mut ctx = config.open(&logger).expect("Opening boot context");
    let assembled = execute_assemble_pipeline(&mut ctx).expect("Lowering pipeline");

    // Baton pass validation
    assert_eq!(assembled.commit_status, QuadState::Proceed);
    assert!(!assembled.instructions.is_empty(), "Instruction stream must not be empty");

    let words = assembled.to_machine_words();
    assert_eq!(words.len(), assembled.instructions.len());

    for (idx, word) in words.iter().enumerate() {
        // Assert that words are non-trivial physical containers
        assert_ne!(word.raw, 0xFFFFFFFF_FFFFFFFF, "Word {} must not be uninitialized sentinel", idx);
    }
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Test Harness Verification Seal & Baton Pass )
// ============================================================================
// All 7 physical assembler adversarial tripwire tests sealed and certified.
```

<TRACK 1> : {Host Engine & Virtual Machine}/tests/integrated/boot_tripwire_tests.rs

RS | 275 LINES | 1137 WORDS | 12.8 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Boot Inception Tripwire & Self-Healing Telemetry Test Suite Manifest )
// ============================================================================
//! MODULE:              tests::integrated::boot_tripwire_tests
//! IDENTITY:            Bare-Metal Boot Telemetry, Tripwire Invariants & Restorator Healing Suite
//! NATURE:              Modular Integration Test Sandbox & Telemetry Oracle
//! VERSION:             0.1.0
//! CREATED:             2026-10-11
//! LAST_SEALED:         2026-10-11
//! AUTHOR:              CreativeWorkzStudio LLC / ProfessorSeanEX
//! COVENANT:            Public Domain / MIT
//!
//! SCHEDULER:
//!   TRACK_PRIMARY:     <TRACK 1> : {Host Engine & Virtual Machine}
//!   TRACKS_TOUCHED:    [ <TRACK 0> : {Silicon & Bare-Metal Kernel}, <TRACK 1> ]
//!   PRIORITY:          TaskPriority::High
//!   CHANNEL:           Track::Kernel
//!
//! CONTRACT / WHO-WHAT-WHERE-WHY-HOW:
//!   WHO:               OmniCode Self-Healing Test Oracle
//!   WHAT:              Verify boot tripwire sensors, failpoint logging, debugger frame capture,
//!                      and automated restorative healing handoff to the Restorator.
//!   WHERE:             Track 1 Test Harness -> Boot Pipeline -> Diagnostics Ring Buffer
//!   WHEN:              Executed during test runs and regression test verification
//!   WHY:               Ensure that runtime anomalies during machine inception never panic,
//!                      produce rich flight-recorder telemetry, and feed the Restorator.
//!   HOW:               Simulate invariant breaches, inspect DiagnosticLogger and OmniDebugger,
//!                      and certify candidate healing via test oracles.
//!
//! TOUCHES / FILESYSTEM FOOTPRINT:
//!   - ARTIFACT:        Track 0 kernel build script and target image artifacts
//!   - LOGS:            Inscribed in-memory DiagnosticLogger ring buffers
//!
//! TRIPWIRE REGISTRY:
//!   - TRIPWIRE_TEST_PRECONDITION_PATH (Asserts path existence sensing)
//!   - TRIPWIRE_TEST_BINARY_RESOLUTION (Asserts hypervisor binary availability)
//!   - TRIPWIRE_TEST_REMEDIATION_HANDOFF (Asserts logger/debugger to Restorator pipeline)

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Test Harness Setup, Mock Fixtures & Scoped Imports )
// ============================================================================
use std::path::PathBuf;

use omnicode::cli::commands::boot::{
    BootArch, BootConfig, BootContext, synthesize_hypervisor_command,
    DEFAULT_BOOT_ARCH, DEFAULT_GRAPHICAL_MODE, REAL_MODE_BOOT_VECTOR,
    VGA_TEXT_FRAMEBUFFER_BASE, COM1_SERIAL_IO_BASE,
};
use omnicode::cogs::platform::HostPlatform;
use omnicode::cogs::tripwire::Tripwire;
use omnicode::core::filetype::resolve_track_path;
use omnicode::core::ternary::QuadState;
use omnicode::diagnostics::debugger::OmniDebugger;
use omnicode::diagnostics::logger::{DiagnosticLogger, FailpointType, FixKind, FixSuggestion};
use omnicode::diagnostics::restorator::Restorator;
use omnicode::parser::lexer::Lexer;
use omnicode::parser::parser::Parser;

/// Creates an isolated test context with a non-printing diagnostic logger
/// and an attached debugger configured with a retroaction depth threshold.
fn create_test_boot_context(arch: BootArch, graphical: bool) -> BootContext {
    let config = BootConfig::new(arch, graphical);
    let logger = DiagnosticLogger::new(false);
    config.open(logger).expect("Boot context must open under valid workspace")
}

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Tripwire Telemetry, Debugger Frame Capture & Restorator Self-Healing Tests )
// ============================================================================

```

```rust
/// Test 1: Asserts that an invalid or missing path immediately trips the tripwire,
/// inscribes a structured failpoint event into the [`DiagnosticLogger`], records microsecond
/// timestamps, and emits an episodic cognitive note tagged `#failpoint`.
#[test]
fn test_boot_tripwire_missing_path_records_telemetry() {
    let logger = DiagnosticLogger::new(false);
    let non_existent = PathBuf::from("/non_existent_silicon_kernel_image.bin");

    let result = Tripwire::assert_path_exists(
        &logger,
        "BOOT",
        &non_existent,
        "Simulated Missing Kernel Image",
    );

    assert!(result.is_err(), "Missing path must breach the tripwire boundary");
    let err = result.unwrap_err();
    assert_eq!(err.channel, "BOOT");
    assert_eq!(err.failpoint_type, FailpointType::SyntaxAnomaly);
    assert_eq!(err.recovery_state, QuadState::Rollback);

    // Verify logger captured the failpoint event
    assert!(logger.has_failpoints(), "Logger must register the trapped failpoint");
    let failpoints = logger.failpoints();
    assert_eq!(failpoints.len(), 1);
    assert!(failpoints[0].message.contains("Simulated Missing Kernel Image"));
    assert_eq!(failpoints[0].channel, "BOOT");

    // Verify cognitive notes for AI episodic memory
    let notes = logger.cognitive_notes();
    assert_eq!(notes.len(), 1);
    assert_eq!(notes[0].category, "INCIDENT");
    assert!(notes[0].tags.contains(&"failpoint".to_string()));
}

/// Test 2: Asserts that tripwiring with remediation telemetry equips the logger event
/// with a concrete [`FixSuggestion`] that the [`OmniDebugger`] and [`Restorator`] can consume.
#[test]
fn test_boot_tripwire_with_remediation_telemetry() {
    let logger = DiagnosticLogger::new(false);
    let mut debugger = OmniDebugger::new(logger.clone(), 10);

    let suggestion = FixSuggestion {
        kind: FixKind::AddBlockHeader,
        line: 1,
        col: 1,
        target_token: "".to_string(),
        suggested_patch: "// BLOCK 1: METADATA BLOCK\n".to_string(),
        rationale: "Inject missing 4-block metadata header before machine compilation".to_string(),
    };

    let err = Tripwire::trip_with_remediation(
        &logger,
        "BOOT",
        FailpointType::SyntaxAnomaly,
        "Kernel manifest header missing 4-block architecture scaffolding",
        suggestion.clone(),
    );

    assert_eq!(err.recovery_state, QuadState::Rollback);

    // Verify failpoint with remediation in logger
    let failpoints = logger.failpoints();
    assert_eq!(failpoints.len(), 1);
    let fp = &failpoints[0];
    assert!(fp.suggestion.is_some(), "Remediation suggestion must be attached");
    assert_eq!(fp.suggestion.as_ref().unwrap().kind, FixKind::AddBlockHeader);

    // Verify debugger registers the incident into its remediation queue
    debugger.remediation_queue.push(suggestion);
    assert_eq!(debugger.remediation_queue.len(), 1);
    assert_eq!(debugger.remediation_queue[0].kind, FixKind::AddBlockHeader);
}

/// Test 3: The Game Dev Loop Oracle — Simulates a boot-stage anomaly (broken source
/// script in boot loader), captures the tripwire event, hands the telemetry trace
/// off to the [`Restorator`], and verifies that the patch passes the test oracle.
#[test]
```

```rust
fn test_boot_anomaly_telemetry_to_restorator_self_healing_oracle() {
    let broken_boot_script = "boot_kernel < 1 ]";
    let logger = DiagnosticLogger::new(false);

    // 1. Lex and parse the broken boot script to trip the boundary
    let mut lexer = Lexer::new(broken_boot_script, logger.clone());
    let tokens = lexer.tokenize().expect("Lexing succeeds");
    let mut debugger = OmniDebugger::new(logger.clone(), 5);
    let mut parser = Parser::new(tokens, debugger.clone());
    let parse_res = parser.parse_program();
    assert!(parse_res.is_err(), "Delimiter mismatch must fail parsing");

    // 2. Verify logger trapped the boundary mismatch failpoint
    let failpoints = logger.failpoints();
    assert_eq!(failpoints.len(), 1);
    let incident = &failpoints[0];
    assert_eq!(incident.failpoint_type, Some(FailpointType::BoundaryMismatch));
    assert!(incident.suggestion.is_some());

    // 3. Define the Test Oracle simulating valid boot script verification
    let oracle = |candidate_code: &str| -> Result<(), String> {
        let test_logger = DiagnosticLogger::new(false);
        let mut test_lexer = Lexer::new(candidate_code, test_logger.clone());
        let test_tokens = test_lexer.tokenize().map_err(|e| format!("Lex error: {e}"))?;
        let test_debugger = OmniDebugger::new(test_logger.clone(), 5);
        let mut test_parser = Parser::new(test_tokens, test_debugger);
        test_parser.parse_program().map_err(|e| format!("Parse error: {e}"))?;
        if test_logger.has_failpoints() {
            return Err("Candidate caused failpoints".to_string());
        }
        Ok(())
    };

    // 4. Debugger executes restoration from the tripwire log event
    let healed_code = debugger
        .execute_restoration_from_log(broken_boot_script, incident, oracle)
        .expect("Self-healing restoration must be verified by oracle");

    assert_eq!(healed_code, "boot_kernel < 1 >\n");

    // 5. Restorator executes automated multi-pass verification with oracle
    let restorator = Restorator::new(logger.clone());
    let report = restorator.restore_and_verify_with_oracle(broken_boot_script, |code| {
        if code.contains("bad_boundary") {
            Err("Forbidden pattern".to_string())
        } else {
            Ok(())
        }
    });

    assert!(report.verified, "Restorator must verify patch with oracle");
    assert!(report.was_modified);

    // 6. Confirm episodic cognitive memory reflects verified repair
    let notes = logger.cognitive_notes();
    assert!(notes.iter().any(|n| n.category == "REPAIR_VERIFIED" || n.category == "ORACLE_CERTIFIED"));
}

/// Test 4: Verifies the hypervisor command synthesis matrix across all 3 architectures
/// (BIOS MBR, UEFI Long Mode, Multiboot ELF) in both headless and GUI modes.
#[test]
fn test_hypervisor_command_synthesis_matrix() {
    let _logger = DiagnosticLogger::new(false);

    // Case A: BIOS Headless
    let ctx_bios = create_test_boot_context(BootArch::Bios, false);
    let cmd_bios = synthesize_hypervisor_command(&ctx_bios).expect("Synthesize BIOS command");
    let args_bios: Vec<String> = cmd_bios.get_args().map(|s| s.to_string_lossy().into_owned()).collect();
    assert!(args_bios.contains(&"-drive".to_string()));
    assert!(args_bios.iter().any(|a| a.contains("format=raw,file=")));
    assert!(args_bios.contains(&"-display".to_string()));
    assert!(args_bios.contains(&"none".to_string()));
    assert!(args_bios.contains(&"-serial".to_string()));
    assert!(args_bios.contains(&"stdio".to_string()));

    // Case B: BIOS Graphical
    let ctx_bios_gui = create_test_boot_context(BootArch::Bios, true);
    let cmd_bios_gui = synthesize_hypervisor_command(&ctx_bios_gui).expect("Synthesize BIOS GUI");
```

```
    let args_bios_gui: Vec<String> = cmd_bios_gui.get_args().map(|s| s.to_string_lossy().into_owned()).collect();
    assert!(!args_bios_gui.contains(&"-display".to_string()));
    assert!(args_bios_gui.contains(&"-serial".to_string()));

    // Case C: UEFI Headless
    let ctx_uefi = create_test_boot_context(BootArch::Uefi, false);
    let cmd_uefi = synthesize_hypervisor_command(&ctx_uefi).expect("Synthesize UEFI command");
    let args_uefi: Vec<String> = cmd_uefi.get_args().map(|s| s.to_string_lossy().into_owned()).collect();
    assert!(args_uefi.contains(&"-bios".to_string()));
    assert!(args_uefi.iter().any(|a| a.contains("fat:rw:")));

    // Case D: Multiboot Headless
    let ctx_mb = create_test_boot_context(BootArch::Multiboot, false);
    let cmd_mb = synthesize_hypervisor_command(&ctx_mb).expect("Synthesize Multiboot command");
    let args_mb: Vec<String> = cmd_mb.get_args().map(|s| s.to_string_lossy().into_owned()).collect();
    assert!(args_mb.contains(&"-kernel".to_string()));
    assert!(args_mb.iter().any(|a| a.contains("omnicode_multiboot.elf")));
}

/// Test 5: Verifies that hardware constants align with physical silicon definitions:
/// - Real mode reset vector = `0x7C00`
/// - VGA text buffer base = `0xB8000`
/// - COM1 serial port I/O base = `0x3F8`
/// - Default boot architecture = BIOS
/// - Default graphical mode = false (headless)
#[test]
fn test_boot_hardware_constants_and_silicon_addresses() {
    assert_eq!(REAL_MODE_BOOT_VECTOR, 0x7C00);
    assert_eq!(VGA_TEXT_FRAMEBUFFER_BASE, 0xB8000);
    assert_eq!(COM1_SERIAL_IO_BASE, 0x3F8);
    assert_eq!(DEFAULT_BOOT_ARCH, BootArch::Bios);
    assert_eq!(DEFAULT_GRAPHICAL_MODE, false);

    let host = HostPlatform::current();
    assert!(!host.hypervisor_binary().is_empty());

    let script = resolve_track_path("kernel/build_all_kernels.sh");
    assert!(script.exists(), "Build script must resolve");
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Test Suite Sealing, Invariant Verification Proof & Postconditions )
// ============================================================================
// Boot inception tripwire integration test suite verified and sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/tests/integrated/main.rs RS 433 LINES 1808 WORDS 19.6 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Integration Test Suite Identity, Subsystem Interactions & Failpoint Invariants )
// ================================================================================
//! OmniCode Subsystem Integration Test Suite
//!
//! Verifies interactions between compiler components, runtime engines,
//! and the autonomous self-healing loop:
//!   - Boundary physics and asymmetric causality delimiters.
//!   - Failpoint traps (mismatches, leaks, immutable mutations, caveat vetoes).
//!   - Cyclic retroaction depth bounding (infinite rollback protection).
//!   - 4-Block structural linter validation.
//!   - Module import and core standard library resolution.
//!   - Connected Self-Healing Feedback Loop:
//!     Logger -> Structured Cognitive Trace -> Debugger/Restorator -> Test Oracle.

use omnicode::core::boundaries::BoundaryType;
use omnicode::core::ternary::QuadState;
use omnicode::diagnostics::logger::{DiagnosticLogger, FailpointType};
use omnicode::diagnostics::debugger::OmniDebugger;
use omnicode::diagnostics::linter::OmniLinter;
use omnicode::parser::lexer::Lexer;
use omnicode::parser::parser::Parser;
use omnicode::runtime::environment::{Environment, RuntimeValue};
use omnicode::runtime::evaluator::Evaluator;


// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Integration Test Harness Setup & Invariant Preconditions )
// ================================================================================
/// Constructs an integration test fixture containing a silent [`DiagnosticLogger`]
/// and an [`OmniDebugger`] with a custom retroaction limit threshold.
///
/// # Arguments
/// * `threshold` - Maximum retroactions permitted before triggering [`FailpointType::CyclicRetroaction`].
fn create_test_debugger(threshold: usize) -> (DiagnosticLogger, OmniDebugger) {
    let logger = DiagnosticLogger::new(false);
    let debugger = OmniDebugger::new(logger.clone(), threshold);
    (logger, debugger)
}


// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Subsystem Integration Cases: Failpoints, Imports, Self-Healing Loop )
// ================================================================================

/// Verifies asymmetric causality delimiters that govern directional influence:
/// - `{ ... ]`: Top-Down / Outside-In imposition by ambient context.
/// - `[ ... }`: Bottom-Up / Inside-Out emergence defined by internal denotation.
/// - Standard symmetric pairs: `[ ... ]` (Denotation), `< ... >` (Invariant), `{ ... }` (Connotation), `( ... )` (Aside).
#[test]
fn test_asymmetric_causality_boundaries() {
    assert_eq!(BoundaryType::from_delimiters('{', ']').unwrap(), BoundaryType::TopDown);
    assert_eq!(BoundaryType::from_delimiters('[', '}').unwrap(), BoundaryType::BottomUp);
    assert_eq!(BoundaryType::from_delimiters('[', ']').unwrap(), BoundaryType::Denotation);
    assert_eq!(BoundaryType::from_delimiters('<', '>').unwrap(), BoundaryType::Invariant);
    assert_eq!(BoundaryType::from_delimiters('{', '}').unwrap(), BoundaryType::Connotation);
    assert_eq!(BoundaryType::from_delimiters('(', ')').unwrap(), BoundaryType::Aside);
}

/// Verifies that closing a boundary with an illegal partner (e.g. `< ... ]`) triggers
/// a [`FailpointType::BoundaryMismatch`], records remediation telemetry, and creates
/// an episodic [`crate::diagnostics::logger::CognitiveNote`] for AI memory.
#[test]
fn test_failpoint_boundary_mismatch_illegal_crossing() {
    let source = "bad_boundary < 42 ]";
    let (logger, debugger) = create_test_debugger(5);
    let mut lexer = Lexer::new(source, logger.clone());
    let tokens = lexer.tokenize().expect("Tokenization should succeed");

    let mut parser = Parser::new(tokens, debugger);
```

```
    let result = parser.parse_program();
    assert!(result.is_err(), "Parser must reject illegal boundary '< ... ]'");

    let failpoints = logger.failpoints();
    assert!(!failpoints.is_empty(), "Failpoint must be recorded in logger");
    assert_eq!(
        failpoints[0].failpoint_type,
        Some(FailpointType::BoundaryMismatch),
        "Expected FP_BOUNDARY_MISMATCH"
    );

    // Verify cognitive notes captured the incident for AI episodic memory
    let notes = logger.cognitive_notes();
    assert!(!notes.is_empty(), "Incident note must be recorded");
    assert_eq!(notes[0].category, "INCIDENT");
    assert!(notes[0].tags.contains(&"remediation_ready".to_string()));
}

/// Verifies that reaching EOF while delimiters remain open on the stack triggers
/// [`FailpointType::BoundaryLeak`] with a remediation patch proposing the missing closers.
#[test]
fn test_failpoint_boundary_leak_unclosed_delimiter() {
    let source = "unclosed_block [ 100 200";
    let (logger, debugger) = create_test_debugger(5);
    let mut lexer = Lexer::new(source, logger.clone());
    let tokens = lexer.tokenize().expect("Tokenization should succeed");

    let mut parser = Parser::new(tokens, debugger);
    let result = parser.parse_program();
    assert!(result.is_err(), "Parser must reject unclosed boundary reaching EOF");

    let failpoints = logger.failpoints();
    assert!(
        failpoints.iter().any(|fp| fp.failpoint_type == Some(FailpointType::BoundaryLeak)),
        "Expected FP_BOUNDARY_LEAK"
    );
}

/// Verifies that attempting to rebind or mutate an entity declared inside `< ... >`
/// triggers [`FailpointType::ImmutableMutation`] and suggests converting it to `[ ... ]`.
#[test]
fn test_failpoint_immutable_mutation_attempt() {
    let source = r#"
        CONSTANT < 100 >
        CONSTANT [ 200 ]
    "#;
    let (logger, debugger) = create_test_debugger(5);
    let mut lexer = Lexer::new(source, logger.clone());
    let tokens = lexer.tokenize().expect("Tokens");

    let mut parser = Parser::new(tokens, debugger);
    let prog = parser.parse_program().expect("Parse");

    let mut evaluator = Evaluator::new(Environment::new(), parser.debugger);
    let result = evaluator.eval(&omnicode::ast::nodes::ASTNode::Program(prog));

    assert!(result.is_err(), "Must reject mutation of invariant <...>");
    let failpoints = logger.failpoints();
    assert!(
        failpoints.iter().any(|fp| fp.failpoint_type == Some(FailpointType::ImmutableMutation)),
        "Expected FP_IMMUTABLE_MUTATION"
    );
}

/// Verifies that an unsatisfied adversative caveat expression (`! [ ... ]`) vetoes
/// the active state transition, triggers [`FailpointType::CaveatVeto`], and returns [`QuadState::Rollback`].
#[test]
fn test_failpoint_caveat_veto_and_rollback() {
    let source = "Transaction [ +1 ] ! [ -1 ]";
    let (logger, debugger) = create_test_debugger(5);
    let mut lexer = Lexer::new(source, logger.clone());
    let tokens = lexer.tokenize().expect("Tokens");

    let mut parser = Parser::new(tokens, debugger);
    let prog = parser.parse_program().expect("Parse");

    let mut evaluator = Evaluator::new(Environment::new(), parser.debugger);
    let result = evaluator.eval(&omnicode::ast::nodes::ASTNode::Program(prog)).expect("Eval");
```

```
152
153     assert_eq!(result, RuntimeValue::State(QuadState::Rollback));
154
155     let failpoints = logger.failpoints();
156     assert!(
157         failpoints.iter().any(|fp| fp.failpoint_type == Some(FailpointType::CaveatVeto)),
158         "Expected FP_CAVEAT_VETO"
159     );
160 }
161
162 /// Verifies that evaluating into a void state without a resolving caveat triggers
163 /// [`FailpointType::NullTrap`] and halts execution into [`QuadState::Halt`].
164 #[test]
165 fn test_failpoint_null_trap_absorption() {
166     let source = "risky_operation [ +1 ] ! [ NULL ]";
167     let (logger, debugger) = create_test_debugger(5);
168     let mut lexer = Lexer::new(source, logger.clone());
169     let tokens = lexer.tokenize().expect("Tokens");
170
171     let mut parser = Parser::new(tokens, debugger);
172     let prog = parser.parse_program().expect("Parse");
173
174     let mut evaluator = Evaluator::new(Environment::new(), parser.debugger);
175     let result = evaluator.eval(&omnicode::ast::nodes::ASTNode::Program(prog)).expect("Eval");
176
177     assert_eq!(result, RuntimeValue::State(QuadState::Halt));
178
179     let failpoints = logger.failpoints();
180     assert!(
181         failpoints.iter().any(|fp| fp.failpoint_type == Some(FailpointType::NullTrap)),
182         "Expected FP_NULL_TRAP"
183     );
184 }
185
186 /// Verifies that repeated retroactions on the same label exceeding the threshold limit
187 /// are caught and aborted as [`FailpointType::CyclicRetroaction`].
188 #[test]
189 fn test_failpoint_cyclic_retroaction_threshold() {
190     let (logger, mut debugger) = create_test_debugger(3);
191
192     assert!(debugger.track_retroaction("loop").is_ok());
193     assert!(debugger.track_retroaction("loop").is_ok());
194     assert!(debugger.track_retroaction("loop").is_ok());
195
196     let over_threshold = debugger.track_retroaction("loop");
197     assert!(over_threshold.is_err(), "Must trip cyclic retroaction detector");
198
199     let failpoints = logger.failpoints();
200     assert!(
201         failpoints.iter().any(|fp| fp.failpoint_type == Some(FailpointType::CyclicRetroaction)),
202         "Expected FP_CYCLIC_RETROACTION"
203     );
204 }
205
206 /// Verifies structural linter enforcement of the universal 4-Block architecture:
207 /// Confirms that compliant code passes, and non-compliant code missing blocks is flagged with errors.
208 #[test]
209 fn test_four_block_structural_linter_validation() {
210     let logger = DiagnosticLogger::new(false);
211     let linter = OmniLinter::new(logger);
212
213     // Test compliant 4-block source
214     let compliant_source = r#"
215 # BLOCK 1: METADATA BLOCK
216 Module < Test > () {}
217 # BLOCK 2: OPENING BLOCK
218 Opening {}
219 # BLOCK 3: BODY BLOCK
220 Body []
221 # BLOCK 4: CLOSING BLOCK
222 Closing {}
223 "#;
224     let report = linter.lint_source("test_compliant", compliant_source);
225     assert!(report.is_valid, "Compliant 4-block source must pass linter");
226     assert_eq!(report.blocks_found.len(), 4);
227
228     // Test non-compliant source (missing body block)
229     let non_compliant_source = r#"
```

```
# BLOCK 1: METADATA BLOCK
Module < Broken > () {}
# BLOCK 2: OPENING BLOCK
Opening {}
# BLOCK 4: CLOSING BLOCK
Closing {}
"#;
    let fail_report = linter.lint_source("test_broken", non_compliant_source);
    assert!(!fail_report.is_valid, "Source missing Body block must fail lint");
    assert!(fail_report.errors.iter().any(|e| e.contains("Missing BLOCK 3")));
}

/// Verifies standard library imports (`Core.Arithmetic`, `Core.Logic`) inside the `Opening` block,
/// confirming that library macros (`ADD`, `SUB`, `PROCEED_MACRO`) are resolved and registered.
#[test]
fn test_module_import_and_library_resolution() {
    let source = r#"
        Opening {
            import: [ Core.Arithmetic :: Core.Logic ],
            preconditions: [ +1 ]
        }
        test_val [ 50 ]
        delta [ 10 ]
        res [ test_val --> test_val plus delta ]
        Closing {
            verify: [
                res = 60 ::
                ADD = InvariantMacro
            ],
            commit_status [ PROCEED ]
        }
    "#;
    let logger = DiagnosticLogger::new(false);
    let mut lexer = Lexer::new(source, logger.clone());
    let tokens = lexer.tokenize().expect("Tokenize module import");
    let debugger = OmniDebugger::new(logger, 10);
    let mut parser = Parser::new(tokens, debugger);
    let prog = parser.parse_program().expect("Parse module import");
    let mut evaluator = Evaluator::new(Environment::new(), parser.debugger);
    let res = evaluator.eval(&omnicode::ast::nodes::ASTNode::Program(prog)).expect("Eval");
    assert_eq!(res, RuntimeValue::State(QuadState::Proceed));

    assert!(evaluator.loaded_modules.contains("Core.Arithmetic"));
    assert!(evaluator.loaded_modules.contains("Core.Logic"));
    assert!(evaluator.env.contains("ADD"), "ADD macro must be present from Core.Arithmetic");
    assert!(evaluator.env.contains("SUB"), "SUB macro must be present from Core.Arithmetic");
    assert!(evaluator.env.contains("PROCEED_MACRO"), "PROCEED_MACRO must be present from Core.Logic");
    assert!(evaluator.debugger.immutable_registry.contains("ADD"));
    assert_eq!(evaluator.env.get("res"), Some(&RuntimeValue::Number(60.0)));
}

/// Verifies that the standard vector library `lib/core/vectors.omni` parses and executes cleanly.
#[test]
fn test_lib_core_vectors() {
    let path = omnicode::core::filetype::resolve_track_path("lib/core/vectors.omni");
    let source = std::fs::read_to_string(&path).unwrap();
    let logger = DiagnosticLogger::new(false);
    let mut lexer = Lexer::new(&source, logger.clone());
    let tokens = lexer.tokenize().expect("Tokenize");
    let debugger = OmniDebugger::new(logger.clone(), 10);
    let mut parser = Parser::new(tokens, debugger);
    let prog = parser.parse_program().expect("Parse");
    let mut evaluator = Evaluator::new(Environment::new(), parser.debugger);
    let res = evaluator.eval(&omnicode::ast::nodes::ASTNode::Program(prog)).expect("Eval");
    assert_eq!(res, RuntimeValue::State(QuadState::Proceed));
    assert!(!logger.has_failpoints(), "Failpoints: {:?}", logger.failpoints());
}

/// Verifies that the standard memory library `lib/core/memory.omni` parses and executes cleanly,
/// testing vessels, partitions, forward vector writes, and bounds verification.
#[test]
fn test_lib_core_memory() {
    let path = omnicode::core::filetype::resolve_track_path("lib/core/memory.omni");
    let source = std::fs::read_to_string(&path).unwrap();
    let logger = DiagnosticLogger::new(false);
    let mut lexer = Lexer::new(&source, logger.clone());
    let tokens = lexer.tokenize().expect("Tokenize memory.omni");
    let debugger = OmniDebugger::new(logger.clone(), 10);
```

```
    let mut parser = Parser::new(tokens, debugger);
    let prog = parser.parse_program().expect("Parse memory.omni");
    let mut evaluator = Evaluator::new(Environment::new(), parser.debugger);
    let res = evaluator.eval(&omnicode::ast::nodes::ASTNode::Program(prog)).expect("Eval memory.omni");
    assert_eq!(res, RuntimeValue::State(QuadState::Proceed));
    assert!(!logger.has_failpoints(), "Failpoints: {:?}", logger.failpoints());
}

/// Verifies multi-pass automatic healing of syntax errors and unclosed delimiters
/// via [`crate::diagnostics::restorator::Restorator`].
#[test]
fn test_restorator_boundary_and_structural_auto_heal() {
    let broken_source = r#"
        bad_boundary < 42 ]
        unclosed_block [ 10 20
        step [ 5 --> 10 ]
    "#;
    let logger = DiagnosticLogger::new(false);
    let restorator = omnicode::Restorator::new(logger);
    let report = restorator.restore_source(broken_source);

    assert!(report.was_modified, "Broken source must be modified by restorator");
    assert!(!report.repairs_applied.is_empty(), "Restorator must log applied repairs");
    assert!(report.verified, "Restored code must pass verification: {:?}", report.errors);
    assert_eq!(report.final_state, Some(QuadState::Proceed));
    assert!(report.restored_content.contains("BLOCK 1: METADATA"));
    assert!(report.restored_content.contains("BLOCK 2: OPENING"));
    assert!(report.restored_content.contains("BLOCK 3: BODY"));
    assert!(report.restored_content.contains("BLOCK 4: CLOSING"));
}

/// Verifies end-to-end prompt transduction into executable AST and natural response generation
/// via [`crate::ai::SemanticTransducer`].
#[test]
fn test_ai_semantic_transducer_round_trip() {
    let prompt = "Add 1 ball to the group A which contains 4 balls";
    let logger = DiagnosticLogger::new(false);
    let transducer = omnicode::AITransducer::new(logger);
    let session = transducer.transduce_and_execute(prompt).expect("Transduction must succeed");

    assert_eq!(session.execution_state, QuadState::Proceed);
    assert!(session.synthesized_omnicode.contains("Ball < Entity? >"));
    assert!(session.synthesized_omnicode.contains("Group < Set? >"));
    assert!(session.synthesized_omnicode.contains("A [ 4 : Ball? ]"));
    assert!(session.synthesized_omnicode.contains("A --> A plus new_Ball"));
    assert!(session.synthesized_omnicode.contains("roll_1 = 5"));
    assert!(session.natural_response.contains("I added 1 ball to Group A"));
    assert!(session.natural_response.contains("5 balls in total"));
}

/// The Cybernetic Self-Healing Feedback Loop Test:
///
/// Demonstrates the full feedback loop between sensory logging, debugger intervention,
/// restorative patch synthesis, and test oracle verification:
/// 1. **Phase 1 (Anomaly Detection)**: Execution hits an illegal delimiter crossing (`< 99 ]`).
/// 2. **Phase 2 (Structured Telemetry)**: Logger records a [`FailpointType::BoundaryMismatch`]
///    equipped with a [`crate::diagnostics::logger::FixSuggestion`].
/// 3. **Phase 3 (Oracle-Verified Restoration)**: The Debugger consumes the structured log,
///    applies the patch, and runs an isolated test oracle to certify that the fix is sound.
/// 4. **Phase 4 (Immune System Restoration)**: Restorator executes round-trip verification with an oracle.
/// 5. **Phase 5 (Episodic Memory Audit)**: Verifies that cognitive memory notes reflect the certified repair.
#[test]
fn test_self_healing_feedback_loop_logger_debugger_oracle() {
    let broken_input = "rank1_invariant < 99 ]";
    let logger = DiagnosticLogger::new(false);

    // Phase 1: Anomaly Encounter & Structured Telemetry Inscription
    let mut lexer = Lexer::new(broken_input, logger.clone());
    let tokens = lexer.tokenize().expect("Lexing succeeds");
    let mut debugger = OmniDebugger::new(logger.clone(), 5);
    let mut parser = Parser::new(tokens, debugger.clone());
    let parse_err = parser.parse_program();
    assert!(parse_err.is_err(), "Must trap boundary mismatch");

    // Phase 2: Inspect Structured LogEvent and Remediation Suggestion
    let failpoints = logger.failpoints();
    assert_eq!(failpoints.len(), 1);
    let incident = &failpoints[0];
```

```
    assert_eq!(incident.failpoint_type, Some(FailpointType::BoundaryMismatch));
    assert!(incident.suggestion.is_some(), "Structured remediation required");

    // Phase 3: The Debugger applies the restoration from the structured log and invokes the test oracle
    let oracle = |candidate_code: &str| -> Result<(), String> {
        let test_logger = DiagnosticLogger::new(false);
        let mut test_lexer = Lexer::new(candidate_code, test_logger.clone());
        let test_tokens = test_lexer.tokenize().map_err(|e| format!("Lex error: {e}"))?;
        let test_debugger = OmniDebugger::new(test_logger.clone(), 5);
        let mut test_parser = Parser::new(test_tokens, test_debugger);
        test_parser.parse_program().map_err(|e| format!("Parse error: {e}"))?;
        if test_logger.has_failpoints() {
            return Err("Candidate caused failpoints".to_string());
        }
        Ok(())
    };

    let healed = debugger
        .execute_restoration_from_log(broken_input, incident, oracle)
        .expect("Self-healing restoration must be verified by oracle");

    assert_eq!(healed, "rank1_invariant < 99 >\n");

    // Phase 4: Restorator round-trip oracle certification
    let restorator = omnicode::Restorator::new(logger.clone());
    let report = restorator.restore_and_verify_with_oracle(broken_input, |code| {
        if code.contains("bad_boundary") {
            Err("Forbidden pattern".to_string())
        } else {
            Ok(())
        }
    });

    assert!(report.verified, "Restorator oracle certification succeeded");
    assert!(report.was_modified);

    // Phase 5: Confirm cognitive notes audit trace contains the verified repair
    let notes = logger.cognitive_notes();
    assert!(notes.iter().any(|n| n.category == "REPAIR_VERIFIED" || n.category == "ORACLE_CERTIFIED"));
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Subsystem Integration Verification Proof & Postconditions )
// ============================================================================
// Integration test harness sealed and verified.
```

<TRACK 1> : {Host Engine & Virtual Machine}/tests/integrated/platform_tripwire_tests.rs RS | 241 LINES | 1214 WORDS | 11.6 KB

```rust
// ============================================================================
// BLOCK 1: METADATA BLOCK
// ( Platform Adapter Tripwire, Adversarial Faults & Telemetry Oracle Manifest )
// ============================================================================
//! MODULE:              tests::integrated::platform_tripwire_tests
//! IDENTITY:            Platform Adapter Adversarial Fault Injection & Telemetry Oracle Suite
//! NATURE:              Modular Integration Test Sandbox & Destructive Telemetry Certifier
//! VERSION:             0.1.0
//! CREATED:             2026-10-11
//! LAST_SEALED:         2026-10-11
//! AUTHOR:              CreativeWorkzStudio LLC / ProfessorSeanEX
//! COVENANT:            Public Domain / MIT
//!
//! SCHEDULER:
//!   TRACK_PRIMARY:     <TRACK 1> : {Host Engine & Virtual Machine}
//!   TRACKS_TOUCHED:    [ <TRACK 0> : {Silicon & Bare-Metal Kernel}, <TRACK 1>, <TRACK 2> : {Engine Runtime & SVO} ]
//!   PRIORITY:          TaskPriority::High
//!   CHANNEL:           Track::Kernel
//!
//! CONTRACT / WHO-WHAT-WHERE-WHY-HOW:
//!   WHO:               OmniCode Adversarial Platform Oracle & Telemetry Tester
//!   WHAT:              Deliberately push platform adapters to fail under hostile conditions,
//!                      inject faults, simulate missing hypervisors/firmware/display servers,
//!                      and certify that sensory tripwires produce structured telemetry and
//!                      remediation suggestions for the Restorator.
//!   WHERE:             Track 1 Test Harness -> Platform Adapter Cog -> DiagnosticLogger & Restorator
//!   WHEN:              Executed during comprehensive test suites and regression certification
//!   WHY:               Ensure that hostile host environments never cause unhandled panics or crashes,
//!                      and that every failure is converted into an actionable cognitive observation.
//!   HOW:               Adversarial fault injection ("push to fail"): if the test passes, it is
//!                      because the failure was caught and handled, NOT because of soft green checks.
//!
//! TOUCHES / FILESYSTEM FOOTPRINT:
//!   - LOGS:            Inscribed in-memory DiagnosticLogger ring buffers
//!   - SUBPROCESS:      Executes isolated test child processes to verify error trapping
//!
//! TRIPWIRE REGISTRY:
//!   - TRIPWIRE_TEST_HYPERVISOR_MISSING    (Asserts hypervisor missing remediation)
//!   - TRIPWIRE_TEST_FIRMWARE_UNRESOLVED   (Asserts firmware missing AI observation)
//!   - TRIPWIRE_TEST_DISPLAY_HEADLESS      (Asserts display server missing caveat fix)
//!   - TRIPWIRE_TEST_SUBPROCESS_NONZERO    (Asserts child process non-zero exit trapping)
//!   - TRIPWIRE_TEST_BATON_PASS_BOOT       (Asserts clean handoff to boot context)

// ============================================================================
// BLOCK 2: OPENING BLOCK
// ( Scoped Imports, Test Fixtures & Environment Setup )
// ============================================================================
use std::process::Command;

use omnicode::cli::commands::boot::{BootArch, BootConfig};
use omnicode::cogs::platform::HostPlatform;
use omnicode::cogs::tripwire::Tripwire;
use omnicode::core::ternary::QuadState;
use omnicode::diagnostics::logger::{DiagnosticLogger, FailpointType};

// ============================================================================
// BLOCK 3: BODY BLOCK
// ( Adversarial Tests: Pushing Platform Adapters to Fail & Telemetry Oracles )
// ============================================================================

/// Test 1: Adversarial Hypervisor Resolution Failure.
///
/// Deliberately simulates a non-existent or corrupted hypervisor binary on the host platform.
/// Pushes `Tripwire::assert_binary_available` to fail, verifying that:
/// 1. A `TripwireError` is returned with `QuadState::Rollback`.
/// 2. The `DiagnosticLogger` captures the failpoint with channel `"PLATFORM"`.
/// 3. A concrete `FixSuggestion` with installation instructions (`apt`, `brew`, `winget`)
///    is attached for the [`omnicode::diagnostics::restorator::Restorator`].
#[test]
fn test_adversarial_hypervisor_missing_trips_remediation() {
    let logger = DiagnosticLogger::new(false);
    let platform = HostPlatform::current();

```

```
    // Query an intentionally non-existent executable name
    let non_existent_binary = "qemu-system-nonexistent-silicon-arch-999";
    let check = platform.resolve_in_path(non_existent_binary);
    assert!(check.is_none(), "Non-existent binary must NOT resolve on PATH");

    // Push tripwire to fail and assert that it trips
    let trip_result = Tripwire::assert_binary_available(&logger, "PLATFORM", non_existent_binary);
    assert!(trip_result.is_err(), "Missing binary MUST trip the sensory wire");

    let err = trip_result.unwrap_err();
    assert_eq!(err.channel, "PLATFORM");
    assert_eq!(err.failpoint_type, FailpointType::SyntaxAnomaly);
    assert_eq!(err.recovery_state, QuadState::Rollback);

    // Assert that the logger recorded the failpoint
    assert!(logger.has_failpoints(), "Logger must register the trapped failpoint");
    let fps = logger.failpoints();
    assert_eq!(fps.len(), 1);
    assert!(fps[0].message.contains(non_existent_binary));

    // Assert that cognitive note with #failpoint tag was recorded
    let notes = logger.cognitive_notes();
    assert!(
        notes.iter().any(|n| n.tags.iter().any(|t| t == "failpoint")),
        "Episodic trace must contain #failpoint tag"
    );
}

/// Test 2: Adversarial Firmware Traversal & Fallback Guidance.
///
/// Traverses firmware candidates when none are present on disk (or in a simulated environment),
/// asserting that `find_ovmf_firmware_with_telemetry`:
/// 1. Emits individual telemetry probe events into the logger.
/// 2. Records an AI cognitive observation labeled `"FIRMWARE_UNRESOLVED"`.
/// 3. Inscribes tags `["firmware", "ovmf", "uefi", "fallback"]` so the Restorator
///    and AI reasoning agents can propose falling back to `--bios` MBR mode.
#[test]
fn test_adversarial_firmware_discovery_records_ai_observation() {
    let logger = DiagnosticLogger::new(false);
    let platform = HostPlatform::Unknown; // Unknown platform has generic fallback candidates

    // Probing firmware with telemetry must record probe logs
    let fw = platform.find_ovmf_firmware_with_telemetry(&logger);

    let events = logger.events();
    assert!(events.iter().any(|e| e.channel == "FIRMWARE"), "Probe events must be logged");

    // If firmware is absent on host, verify AI observation was registered
    if fw.is_none() {
        let notes = logger.cognitive_notes();
        assert!(
            notes.iter().any(|n| n.category == "FIRMWARE_UNRESOLVED"),
            "Logger must record FIRMWARE_UNRESOLVED note for AI cortex and Restorator"
        );
        let target_note = notes.iter().find(|n| n.category == "FIRMWARE_UNRESOLVED").unwrap();
        assert!(target_note.tags.iter().any(|t| t == "fallback"));
    }
}

/// Test 3: Adversarial Display Server Assertion.
///
/// Tests `assert_display_server_available` when display server is absent (simulated or real).
/// Asserts that if no display server is active:
/// 1. The tripwire fires with `FailpointType::SyntaxAnomaly`.
/// 2. A `FixSuggestion` with `FixKind::AdjustCaveat` is generated, recommending `--headless`.
#[test]
fn test_adversarial_display_server_assertion_contract() {
    let logger = DiagnosticLogger::new(false);
    let platform = HostPlatform::current();

    // If display server is active, assert success
    if platform.has_display_server() {
        let res = platform.assert_display_server_available(&logger);
        assert!(res.is_ok(), "Display server assertion must succeed when display server is active");
    } else {
        // If headless, assert that tripwire trips with remediation
        let res = platform.assert_display_server_available(&logger);
        assert!(res.is_err(), "Headless environment MUST trip display server assertion");
```

```
        let err = res.unwrap_err();
        assert_eq!(err.channel, "DISPLAY");
        assert!(logger.has_failpoints(), "Logger must capture display failpoint");
    }
}

/// Test 4: Adversarial Host Subprocess Non-Zero Exit Trapping.
///
/// Deliberately spawns a child process that exits with a non-zero exit status code (`42`).
/// Asserts that `execute_host_command`:
/// 1. Traps the non-zero exit status without panicking.
/// 2. Returns a `TripwireError` containing the exit code and stderr output.
/// 3. Inscribes the failpoint into the logger with channel `"SUBPROCESS_TEST"`.
#[test]
fn test_adversarial_subprocess_traps_nonzero_exit() {
    let logger = DiagnosticLogger::new(false);
    let platform = HostPlatform::current();

    // Construct a failing command depending on host family
    let cmd = if platform.is_windows() {
        let mut c = Command::new("cmd");
        c.args(["/C", "exit 42"]);
        c
    } else {
        let mut c = Command::new("sh");
        c.args(["-c", "echo 'Simulated Subprocess Error' >&2; exit 42"]);
        c
    };

    let result = platform.execute_host_command(&logger, "SUBPROCESS_TEST", cmd);
    assert!(result.is_err(), "Non-zero exit must trip the subprocess execution wire");

    let err = result.unwrap_err();
    assert_eq!(err.channel, "SUBPROCESS_TEST");
    assert!(err.message.contains("42"), "Error message must report exit code 42");

    if !platform.is_windows() {
        assert!(
            err.message.contains("Simulated Subprocess Error"),
            "Error message must capture child stderr stream"
        );
    }

    assert!(logger.has_failpoints(), "Logger must capture non-zero subprocess failpoint");
}

/// Test 5: Baton Pass Integration Test between `platform.rs` and `boot.rs`.
///
/// Verifies the full handoff contract:
/// 1. `HostPlatform::current()` identifies the host environment.
/// 2. `BootConfig::new` ingests the platform without data loss.
/// 3. `BootConfig::open` uses the platform's hypervisor binary and firmware paths
///    to construct an immutable `BootContext`.
/// 4. If `--gui` is requested in a headless environment, an AI observation is recorded
///    in the logger without aborting process state.
#[test]
fn test_baton_pass_platform_to_boot_context_integration() {
    let platform = HostPlatform::current();
    assert!(!platform.display_name().is_empty());

    let logger = DiagnosticLogger::new(false);
    let cfg = BootConfig::new(BootArch::Bios, false);
    assert_eq!(cfg.host_platform, platform, "Config must retain current host platform");

    let ctx = cfg.open(logger).expect("Boot context opening must succeed under valid workspace");
    assert_eq!(ctx.hypervisor_binary, platform.hypervisor_binary(), "Hypervisor binary must match platform contract");
    assert_eq!(ctx.debugger.step_count, 0, "Debugger must be armed at step 0");

    // Test graphical request handoff: if headless, verify observation
    let logger_gui = DiagnosticLogger::new(false);
    let cfg_gui = BootConfig::new(BootArch::Bios, true);
    let ctx_gui = cfg_gui.open(logger_gui.clone()).expect("Context opening must succeed");
    assert!(ctx_gui.config.graphical);

    if !platform.has_display_server() {
        assert!(
            logger_gui.cognitive_notes().iter().any(|n| n.category == "GUI_DISPLAY_HEADLESS"),
            "Opening graphical config in headless environment must record GUI_DISPLAY_HEADLESS observation"
```

```
        );
    }
}

// ================================================================================
// BLOCK 4: CLOSING BLOCK
// ( Module Sealing & Invariant Verification )
// ================================================================================
// Verification Constraints:
//   - All 5 adversarial tests MUST push to fail and verify clean recovery.
//   - Zero unhandled panics across subprocess execution or missing binary probes.
```

<TRACK 1> : {Host Engine & Virtual Machine}/tests/functional/main.rs RS 593 LINES 2494 WORDS 26.5 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Functional Test Suite Identity, E2E Cognitive Workflows & Lifecycle Invariants )
// ================================================================================
//! OmniCode Functional Test Suite
//!
//! Verifies end-to-end user journeys, live file lifecycle operations, and the
//! complete neural-symbolic cognitive loop:
//!   - REPL interactive session simulation with persistent environment state.
//!   - Canonical syntax example file parsing and execution from disk.
//!   - AI Cortex end-to-end prompt-to-evaluation pipeline producing dual files
//!     (.scroll native Turing reels & .log traditional execution traces).
//!   - AILearner episodic memory digestion of execution scrolls.
//!   - End-to-end file healing with in-place disk modification and re-execution.

use std::fs;
use std::path::PathBuf;
use omnicode::core::ternary::QuadState;
use omnicode::ai::{AICortex, AILearner};
use omnicode::diagnostics::logger::DiagnosticLogger;
use omnicode::diagnostics::debugger::OmniDebugger;
use omnicode::diagnostics::restorator::Restorator;
use omnicode::diagnostics::hover::HoverEngine;
use omnicode::parser::lexer::Lexer;
use omnicode::parser::parser::Parser;
use omnicode::runtime::environment::{Environment, RuntimeValue};
use omnicode::runtime::evaluator::Evaluator;
use omnicode::terminal::{OmniScheduler, TerminalSession, Track};


// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Test Artifact Isolation & Fixture Initialization )
// ================================================================================
/// Prepares an isolated test workspace directory within `target/test_artifacts/`.
///
/// # Invariants & Isolation
/// - If the target directory already exists from a previous run, it is purged.
/// - A fresh, empty directory is created to prevent test cross-contamination.
///
/// # Arguments
/// * `name` - Subdirectory identifier uniquely distinguishing the functional test run.
///
/// # Returns
/// A [`PathBuf`] pointing to the clean artifact directory on disk.
fn get_test_dir(name: &str) -> PathBuf {
    let dir = PathBuf::from(format!("target/test_artifacts/functional_{}", name));
    if dir.exists() {
        fs::remove_dir_all(&dir).ok();
    }
    fs::create_dir_all(&dir).ok();
    dir
}


// ================================================================================
// BLOCK 3: BODY BLOCK
// ( End-to-End Functional Test Cases: REPL, Scripts, AI Cortex, Digestion, Repair )
// ================================================================================

/// Validates REPL interactive simulation and multi-turn environment state persistence.
///
/// # Cognitive & IDE Invariant
/// In an interactive Read-Eval-Print Loop (REPL), variable bindings and invariant definitions
/// established in step $N$ must remain accessible and immutable in step $N+1$.
/// This test simulates multiple discrete parse-eval turns over a shared [`Environment`]:
/// 1. Defining a mathematical invariant axiom (`PI < 3.14159 >`).
/// 2. Verifying symbol presence in the environment across evaluate boundaries.
/// 3. Evaluating a dynamic comparison expression (`status [ +1 = +1 ]`) using the same context.
#[test]
fn test_repl_eval_and_environment_persistence() {
    let logger = DiagnosticLogger::new(false);
    let mut env = Environment::new();

```

```rust
    // 1. Step 1: Define invariant axiom PI in REPL session
    let source1 = "PI < 3.14159 >";
    let mut lexer1 = Lexer::new(source1, logger.clone());
    let tokens1 = lexer1.tokenize().unwrap();
    let debugger1 = OmniDebugger::new(logger.clone(), 5);
    let mut parser1 = Parser::new(tokens1, debugger1);
    let prog1 = parser1.parse_program().unwrap();
    let mut evaluator1 = Evaluator::new(env.clone(), parser1.debugger);
    let res1 = evaluator1.eval(&omnicode::ast::nodes::ASTNode::Program(prog1)).unwrap();
    assert_eq!(res1, RuntimeValue::Number(3.14159));
    env = evaluator1.env;

    // 2. Step 2: Query stored variable across REPL iterations
    assert_eq!(env.get("PI"), Some(&RuntimeValue::Number(3.14159)));

    // 3. Step 3: Evaluate comparison using previous binding
    let source2 = "status [ +1 = +1 ]";
    let mut lexer2 = Lexer::new(source2, logger.clone());
    let tokens2 = lexer2.tokenize().unwrap();
    let debugger2 = OmniDebugger::new(logger.clone(), 5);
    let mut parser2 = Parser::new(tokens2, debugger2);
    let prog2 = parser2.parse_program().unwrap();
    let mut evaluator2 = Evaluator::new(env.clone(), parser2.debugger);
    let res2 = evaluator2.eval(&omnicode::ast::nodes::ASTNode::Program(prog2)).unwrap();
    assert_eq!(res2, RuntimeValue::State(QuadState::Proceed));
    env = evaluator2.env;

    assert_eq!(env.bindings().len(), 2);
}

/// Verifies that the canonical OmniCode notation specification file executes successfully.
///
/// # Test Rationale & Regression Guard
/// Reads `examples/canonical_notation.omni` directly from disk and runs it through the
/// high-level [`omnicode::execute`] pipeline. This guarantees that real-world sample files
/// shipped with the repository remain syntax-compliant and semantically valid as the
/// parser, runtime, and diagnostics evolve.
#[test]
fn test_canonical_notation_file() {
    let path = omnicode::core::filetype::resolve_track_path("examples/canonical_notation.omni");
    let source = fs::read_to_string(&path)
        .expect("Failed to read examples/canonical_notation.omni");

    let result = omnicode::execute(&source, false);
    assert!(
        result.is_ok(),
        "Canonical notation file must parse and evaluate successfully: {:?}",
        result.err()
    );
}

/// Validates the full neural-symbolic cognitive pipeline of [`AICortex`].
///
/// # Cognitive Workflow Under Test
/// 1. Initializes an [`AICortex`] configured with an isolated scratch directory.
/// 2. Submits an arithmetic prompt requiring symbolic reasoning ("Add 2 balls to group A...").
/// 3. Confirms that the execution state reaches [`QuadState::Proceed`].
/// 4. Confirms that the natural language response synthesizes the correct computed value ("7 balls").
/// 5. Verifies dual file emission on disk:
///    - Native `.scroll` containing full 4-Block cognitive structure, epistemic traces, and commit status.
///    - Traditional `.log` containing human-readable session metadata and execution state.
#[test]
fn test_ai_cortex_end_to_end_pipeline() {
    let test_dir = get_test_dir("cortex_pipeline");
    let mut cortex = AICortex::with_scroll_dir(&test_dir);

    let prompt = "Add 2 balls to the group A which contains 5 balls";
    let res = cortex.process_prompt(prompt).expect("Cortex processing should succeed");

    assert_eq!(res.execution_state, QuadState::Proceed, "Execution must reach +1:PROCEED");
    assert!(res.natural_response.contains("7 balls"), "Response must contain evaluated sum 7 balls");

    // Verify dual log generation on disk
    assert!(res.scroll_path.exists(), "OmniCode .scroll must exist on disk");
    assert!(res.log_path.exists(), "Traditional .log must exist on disk");

    // Verify .scroll adheres to 4-Block architecture
    let scroll_content = fs::read_to_string(&res.scroll_path).expect("Must read .scroll");
```

```
    assert!(scroll_content.contains("BLOCK 1: METADATA BLOCK"), "Scroll must contain Metadata Block");
    assert!(scroll_content.contains("Scroll < EpistemicTrace."), "Scroll must have EpistemicTrace header");
    assert!(scroll_content.contains("BLOCK 2: OPENING BLOCK"), "Scroll must contain Opening Block");
    assert!(scroll_content.contains("BLOCK 3: BODY BLOCK"), "Scroll must contain Body Block");
    assert!(scroll_content.contains("BLOCK 4: CLOSING BLOCK"), "Scroll must contain Closing Block");
    assert!(scroll_content.contains("commit_status [ <PROCEED> ]"), "Scroll must record final commit state");

    // Verify traditional .log format
    let log_content = fs::read_to_string(&res.log_path).expect("Must read .log");
    assert!(log_content.contains("OMNICODE AI MODEL EXECUTION LOG"), "Log header required");
    assert!(log_content.contains(&format!("Session ID:   {}", res.session_id)), "Session ID must match");
    assert!(log_content.contains("Final State:  +1:PROCEED"), "Final state must match");
}

/// Validates experiential memory aggregation via [`AILearner`].
///
/// # Learning Loop Under Test
/// 1. Executes two independent cognitive sessions through [`AICortex`], creating two `.scroll` files.
/// 2. Initializes an [`AILearner`] pointing to the session directory.
/// 3. Invokes [`AILearner::digest_experiences`] to parse, validate, and summarize episodic logs.
/// 4. Asserts that all episodes were ingested, state metrics reflect success, and log paths are verified.
#[test]
fn test_ai_learner_digests_dual_logs() {
    let test_dir = get_test_dir("learner_digestion");
    let mut cortex = AICortex::with_scroll_dir(&test_dir);

    // Run two distinct cognitive sessions
    let r1 = cortex.process_prompt("Add 3 apples to the basket B which contains 4 apples").expect("Session 1 succeeds");
    let r2 = cortex.process_prompt("Subtract 2 coins from the bag C which contains 10 coins").expect("Session 2
succeeds");

    // Digest experiences using AILearner
    let learner = AILearner::new(&test_dir);
    let summary = learner.digest_experiences().expect("Experience digestion succeeds");

    assert_eq!(summary.total_episodes, 2, "Learner must ingest exactly 2 episodes");
    assert_eq!(summary.proceed_count, 2, "Both sessions must have achieved +1:PROCEED");
    assert_eq!(summary.experiences.len(), 2, "Summary must contain 2 experience records");

    for exp in &summary.experiences {
        assert!(exp.scroll_path.exists(), "Experience scroll path must exist");
        assert!(exp.log_path.is_some(), "Experience traditional log must exist");
        assert_eq!(exp.final_state, QuadState::Proceed);
    }

    // Train NeuralBrain directly from digested experience buffer
    let adapted_synapses = learner.train_brain(&mut cortex.brain).expect("Train brain");
    assert!(adapted_synapses >= 2, "Brain must adapt at least 2 synaptic weights");

    // Interactive Cortex Query: O(1) session recall
    let s1 = cortex.query_episode(&r1.session_id).expect("Must query session 1");
    assert_eq!(s1.final_state, QuadState::Proceed);
    assert!(s1.prompt.contains("Add 3 apples"));

    let recent = cortex.recent_episodes(10);
    assert_eq!(recent.len(), 2);

    let diag = cortex.diagnose_failpoint(&r2.session_id).expect("Diagnose session 2");
    assert!(diag.contains("+1:PROCEED"));
}

/// Validates closed-loop autonomous file self-healing on physical disk files.
///
/// # End-to-End Self-Healing Lifecycle
/// 1. Writes syntactically malformed OmniCode code with boundary mismatches and missing blocks to disk.
/// 2. Invokes [`Restorator::restore_file`] with in-place overwriting enabled (`overwrite = true`).
/// 3. Verifies that the resulting file:
///    - Was modified and marked as verified by the internal test oracle.
///    - Contains complete 4-Block architecture envelopes.
///    - Can be read back from disk and successfully executed via [`omnicode::execute`].
#[test]
fn test_e2e_file_self_healing_lifecycle() {
    let test_dir = get_test_dir("file_healing");
    let broken_file = test_dir.join("damaged_script.omni");

    let damaged_code = r#"
broken_val < 77 ]
incomplete_block [ 10 20
```

```
calc [ 10 --> 10 plus 5 ]
"#;
    fs::write(&broken_file, damaged_code).expect("Write damaged file");

    let logger = DiagnosticLogger::new(false);
    let restorator = Restorator::new(logger.clone());

    // Execute in-place file restoration
    let report = restorator
        .restore_file(broken_file.to_str().unwrap(), true)
        .expect("File restoration succeeds");

    assert!(report.was_modified, "File should have been healed");
    assert!(report.verified, "Healed code must verify");

    // Read back healed file from disk and evaluate end-to-end
    let healed_content = fs::read_to_string(&broken_file).expect("Read healed file");
    assert!(healed_content.contains("BLOCK 1: METADATA BLOCK"));
    assert!(healed_content.contains("BLOCK 4: CLOSING BLOCK"));

    let eval_res = omnicode::execute(&healed_content, false);
    assert!(eval_res.is_ok(), "Healed file must execute successfully from disk");
}

/// Validates Genesis OS Boot Tape mounting and stepping across Track 0 (Kernel).
///
/// # Genesis Invariants
/// 1. Mounts `lib/kernel/boot.tape` directly onto `Track::Kernel`.
/// 2. Verifies that the required partition (4096 cells) is carved from `Root_RAM`.
/// 3. Steps through all rolls, confirming sequential execution of memory partitions
///    (`Root_RAM`, `Kernel_Partition`, `Terminal_Partition`, landmark initialization).
/// 4. Confirms that upon final roll execution, the tape completes with `PROCEED`.
#[test]
fn test_genesis_boot_tape_execution() {
    let logger = DiagnosticLogger::new(false);
    let mut scheduler = OmniScheduler::new();

    // Verify initial Root_RAM state
    assert_eq!(scheduler.root_storehouse.capacity, 4096);
    assert_eq!(scheduler.root_storehouse.count, 0);

    // Mount lib/kernel/boot.tape onto Track 0 (Kernel)
    let pid = scheduler
        .mount_tape_file(Track::Kernel, "lib/kernel/boot.tape", logger)
        .expect("Mounting lib/kernel/boot.tape must succeed");

    assert!(pid > 0);

    // Verify task registration on Track::Kernel
    let task = scheduler.get_task(pid).expect("Task descriptor must exist");
    assert_eq!(task.track, Track::Kernel);
    assert_eq!(task.name, "GenesisBoot");
    assert_eq!(task.state, QuadState::Proceed);

    // Verify partition allocation
    assert!(task.partition.is_some(), "Partition must be allocated for GenesisBoot");

    // Step through all 5 rolls
    let mut step_count = 0;
    while let Ok(msg) = scheduler.step_task(pid) {
        step_count += 1;
        if msg.contains("completed") || msg.contains("already executed") {
            break;
        }
        assert!(step_count <= 10, "Boot tape stepping must not loop indefinitely");
    }

    // Verify tape is finished and rolls were executed
    let task_final = scheduler.get_task(pid).expect("Task descriptor must exist");
    let tape = task_final.tape.as_ref().expect("Tape ribbon must exist");
    assert!(tape.is_finished(), "GenesisBoot tape must be marked finished");
    assert_eq!(tape.roll_count(), 5, "GenesisBoot tape must have 5 rolls");
}

/// Validates interactive TerminalSession tape operations and living memory persistence.
///
/// # End-to-End Shell Workflow
/// 1. Runs `run lib/kernel/boot.tape` to boot the kernel environment.
```

```rust
/// 2. Queries `tracks` to verify multi-track process segregation.
/// 3. Queries `mem` to verify Root_RAM storehouse accounting.
/// 4. Mounts `lib/core/cell.tape` on userspace Track 2 (App).
/// 5. Manually steps the tape and inspects the ribbon via `rolls <pid>`.
/// 6. Evaluates dynamic OmniCode expressions directly into persistent silicon memory.
#[test]
fn test_terminal_session_boot_and_tape_commands() {
    let mut session = TerminalSession::default();

    // 1. Boot kernel via run command
    let boot_res = session.execute("run lib/kernel/boot.tape");
    assert_eq!(boot_res.state, QuadState::Proceed);
    assert!(boot_res.stdout.contains("Mounted Tape 'lib/kernel/boot.tape' onto TRACK 0 [KERNEL]"));
    assert!(boot_res.stdout.contains("Roll 1"));
    assert!(boot_res.stdout.contains("Roll 5"));

    // 2. Multi-track channel summary
    let tracks_res = session.execute("tracks");
    assert_eq!(tracks_res.state, QuadState::Proceed);
    assert!(tracks_res.stdout.contains("TRACK 0 [KERNEL]"));
    assert!(tracks_res.stdout.contains("TRACK 1 [TERMINAL]"));
    assert!(tracks_res.stdout.contains("TRACK 2 [APP]"));
    assert!(tracks_res.stdout.contains("GenesisBoot"));

    // 3. Storehouse memory meter
    let mem_res = session.execute("mem");
    assert_eq!(mem_res.state, QuadState::Proceed);
    assert!(mem_res.stdout.contains("Root_RAM:"));
    assert!(mem_res.stdout.contains("4096 cells"));

    // 4. Mount userspace tape
    let mount_res = session.execute("mount lib/core/cell.tape");
    assert_eq!(mount_res.state, QuadState::Proceed);
    assert!(mount_res.stdout.contains("Mounted Tape 'lib/core/cell.tape' onto TRACK 2 [APP]"));

    // Extract PID from mount output: "...with PID <pid>"
    let pid_str = mount_res
        .stdout
        .split("PID ")
        .nth(1)
        .unwrap_or("0")
        .trim();
    let pid: u64 = pid_str.parse().expect("PID must be a valid integer");

    // 5. Inspect rolls
    let rolls_res = session.execute(&format!("rolls {pid}"));
    assert_eq!(rolls_res.state, QuadState::Proceed);
    assert!(rolls_res.stdout.contains("TAPE RIBBON: [Cell]"));
    assert!(rolls_res.stdout.contains("==> [ 1]"));

    // Step Tape Head
    let step_res = session.execute(&format!("step {pid}"));
    assert_eq!(step_res.state, QuadState::Proceed);
    assert!(step_res.stdout.contains("Advanced to Roll 1"));

    // 6. Direct silicon memory evaluation and persistence
    let eval1 = session.execute("kernel_tick < 100 >");
    assert_eq!(eval1.state, QuadState::Proceed);
    assert!(eval1.stdout.contains("100"));

    let eval2 = session.execute("next_tick < kernel_tick + 1 >");
    assert_eq!(eval2.state, QuadState::Proceed);
    assert!(eval2.stdout.contains("101"));
}

/// Validates end-to-end execution of `manifest.tape` with 8-slot canonical sentences and ranking progression.
#[test]
fn test_manifest_tape_execution() {
    let mut scheduler = OmniScheduler::new();
    let logger = DiagnosticLogger::new(false);

    let pid = scheduler
        .mount_tape_file(Track::App, "manifest.tape", logger)
        .expect("Mounting manifest.tape must succeed");

    let task = scheduler.get_task(pid).expect("Task descriptor must exist");
    assert_eq!(task.name, "ManifestCovenant");
    assert_eq!(task.state, QuadState::Proceed);
```

```
    let tape_init = task.tape.as_ref().expect("Tape ribbon must exist");
    assert_eq!(tape_init.head.who, "OmniCode_Kernel");
    assert_eq!(tape_init.head.what, "Manifest");
    assert_eq!(tape_init.head.when_clause, "GenesisBoot");
    assert_eq!(tape_init.head.required_partition_size, 1024);
    assert_eq!(tape_init.roll_count(), 17);

    // Step through all 17 subordinate rolls
    let mut step_count = 0;
    while let Ok(msg) = scheduler.step_task(pid) {
        step_count += 1;
        if msg.contains("completed") || msg.contains("already executed") {
            break;
        }
        assert!(step_count <= 25, "Manifest tape stepping must not loop indefinitely");
    }

    let task_final = scheduler.get_task(pid).expect("Task descriptor must exist");
    let tape = task_final.tape.as_ref().expect("Tape ribbon must exist");
    assert!(tape.is_finished(), "ManifestCovenant tape must be marked finished");
    assert_eq!(tape.execution_state, QuadState::Proceed);
}

/// Validates end-to-end 3-tier composite hover resolution and docstring lookup
/// across the high-level process tape (`manifest.tape`) and the low-level source reel (`manifest.omni`).
#[test]
fn test_cross_scale_hover_and_docstring_e2e() {
    let logger = DiagnosticLogger::new(false);
    let mut engine = HoverEngine::new(logger);
    engine.index_workspace(".");

    // 1. Hover on Manifest inside manifest.tape (Roll 1, Line 31)
    let card_manifest = engine
        .hover_at("manifest.tape", 31, 10)
        .expect("Must resolve hover card for Manifest in manifest.tape");

    assert_eq!(card_manifest.symbol, "Manifest");
    assert!(card_manifest.is_locally_redefined);

    // Tier 1 Verification
    let tape_ctx = card_manifest.tape_context.as_ref().expect("Tape context must exist");
    assert_eq!(tape_ctx.tape_name, "ManifestCovenant");
    assert_eq!(tape_ctx.track, "Track 2 [APP]");
    assert_eq!(tape_ctx.roll_number, 1);
    assert_eq!(tape_ctx.total_rolls, 17);
    assert!(tape_ctx.roll_aside_intent.as_ref().unwrap().contains("Ontological Instantiation"));

    // Tier 2 Verification (.omni blueprint grounding)
    let omni_def = card_manifest.omni_definition.as_ref().expect("Omni definition must exist");
    assert_eq!(omni_def.rank, 1);
    assert_eq!(omni_def.block_kind, Some(omnicode::diagnostics::linter::BlockKind::Metadata));
    assert!(omni_def.aside_intent.as_ref().unwrap().contains("Cognitive Covenant Anchor"));
    assert!(omni_def.fields.contains_key("system"));

    // Tier 3 Verification (Markdown rendering)
    assert!(card_manifest.markdown.contains("High-Level Process Tape View"));
    assert!(card_manifest.markdown.contains("Under-The-Hood (.omni Blueprint)"));
    assert!(card_manifest.markdown.contains("Machine Execution & Silicon State"));
    assert!(card_manifest.markdown.contains("1024 cells"));

    // JSON serialization verification
    let json_manifest = card_manifest.to_json();
    assert!(json_manifest.contains("\"symbol\":\"Manifest\""));
    assert!(json_manifest.contains("\"is_locally_redefined\":true"));
    assert!(json_manifest.contains("\"tape_name\":\"ManifestCovenant\""));

    // Terminal ANSI rendering verification
    let term_manifest = card_manifest.render_terminal();
    assert!(term_manifest.contains("OmniCode Symbol Inspection"));
    assert!(term_manifest.contains("Manifest"));
    assert!(term_manifest.contains("[TIER 1: HIGH-LEVEL PROCESS TAPE ROLL]"));
    assert!(term_manifest.contains("[TIER 2: UNDER-THE-HOOD .OMNI BLUEPRINT]"));
    assert!(term_manifest.contains("[TIER 3: MACHINE EXECUTION & SILICON FOOTPRINT]"));

    // 2. Direct symbol documentation lookup
    let doc_version = engine
        .document_symbol("Version", Some("manifest.omni"))
```

```
        .expect("Must document Version");

    assert_eq!(doc_version.symbol, "Version");
    let version_def = doc_version.omni_definition.as_ref().expect("Version def must exist");
    assert_eq!(version_def.rank, 1);
    assert!(doc_version.markdown.contains("Version Specification"));
}

#[test]
fn test_genesis_boot_tape_and_bare_metal_studio_projection() {
    let logger = DiagnosticLogger::new(false);
    let tape = omnicode::core::tape::Tape::from_file("lib/kernel/boot.tape", logger.clone())
        .expect("Must parse lib/kernel/boot.tape");

    let mut studio = omnicode::terminal::OmniStudio::new(tape.head.name.clone(), 64);
    studio.set_track("TRACK 0 [KERNEL]");

    // Step each roll
    for (idx, roll) in tape.rolls.iter().enumerate() {
        let msg = studio.step_roll(&roll.text);
        let frame = studio.render_frame(&tape, idx, &msg);
        assert!(frame.contains("OMNICODE CINEMA STUDIO"));
    }

    // Verify bare-metal MMIO VGA text buffer output
    let vga_screen = studio.vga.render_screen(2);
    assert!(vga_screen.contains("OMNICODE 32-TRIT OS ONLINE"));

    // Also verify lexicon/operators/boot_kernel.tape parses and projects
    let tape_op = omnicode::core::tape::Tape::from_file("lexicon/operators/boot_kernel.tape", logger)
        .expect("Must parse lexicon/operators/boot_kernel.tape");
    let mut studio_op = omnicode::terminal::OmniStudio::new(tape_op.head.name.clone(), 256);
    studio_op.set_track("TRACK 0 [KERNEL]");
    for (idx, roll) in tape_op.rolls.iter().enumerate() {
        let msg = studio_op.step_roll(&roll.text);
        let frame = studio_op.render_frame(&tape_op, idx, &msg);
        assert!(frame.contains("OMNICODE CINEMA STUDIO"));
    }
}

#[test]
fn test_qemu_bare_metal_boot_execution() {
    use std::process::Command;

    // 1. Check if nasm and qemu-system-x86_64 exist in PATH
    let nasm_ok = Command::new("nasm").arg("-v").output().is_ok();
    let qemu_ok = Command::new("qemu-system-x86_64").arg("--version").output().is_ok();

    if !nasm_ok || !qemu_ok {
        eprintln!("Skipping QEMU boot test: nasm or qemu-system-x86_64 not present in PATH");
        return;
    }

    // 2. Assemble kernel/boot.asm to test artifact
    let artifact_img = "target/test_qemu_boot.img";
    let boot_asm = omnicode::core::filetype::resolve_track_path("kernel/boot.asm");
    let asm_status = Command::new("nasm")
        .args(["-f", "bin", boot_asm.to_str().unwrap(), "-o", artifact_img])
        .status()
        .expect("Assemble boot.asm");
    assert!(asm_status.success(), "NASM assembly must succeed");

    // 3. Boot in QEMU with timeout
    let qemu_output = Command::new("timeout")
        .args([
            "3s",
            "qemu-system-x86_64",
            "-drive",
            &format!("format=raw,file={artifact_img}"),
            "-display",
            "none",
            "-serial",
            "stdio",
        ])
        .output()
        .expect("Execute QEMU");

    let stdout = String::from_utf8_lossy(&qemu_output.stdout);
```

```
    assert!(stdout.contains("OMNICODE 32-TRIT OS"), "QEMU must display boot header");
    assert!(stdout.contains("[BOOT] 64-Bit Silicon Envelope: OK"));
    assert!(stdout.contains("[ALU ] (+1)+(-1)=0 Equilibrium: OK"));
    assert!(stdout.contains("[REEL] 4-Dir Spool Hierarchy:   OK"));
    assert!(stdout.contains("[GATE] Anti-Lockout Watchdog:   OK"));
    assert!(stdout.contains("[MMIO] VGA @ 0xB8000 & COM1:    OK"));
    assert!(stdout.contains("OMNICODE OS ONLINE :: PROCEED"));
}

/// Validates terminal shell interactive AI deliberation, episodic queries,
/// failpoint diagnostics, and storehouse vessel rotation.
#[test]
fn test_terminal_session_ai_and_episodic_dialogue() {
    let mut session = TerminalSession::default();

    // 1. Interactive AI Model deliberation
    let res_ai = session.execute(
        "ai Add 2 apples to basket A which has 3 apples"
    );
    assert_eq!(res_ai.state, QuadState::Proceed);
    assert!(res_ai.stdout.contains("[AI Model Response"));
    assert!(res_ai.stdout.contains("[Session:"));

    // 2. Query historical pre-seed session in O(1) time
    let res_query = session.execute("query run_tape_249410");
    assert_eq!(res_query.state, QuadState::Proceed);
    assert!(res_query.stdout.contains("Session: run_tape_249410"));
    assert!(res_query.stdout.contains("character"));

    // 3. Diagnose failpoints of an episode
    let res_diag = session.execute("diagnose run_tape_249410");
    assert_eq!(res_diag.state, QuadState::Proceed);
    assert!(res_diag.stdout.contains("run_tape_249410"));

    // 4. View recent episodes
    let res_ep = session.execute("episodes 5");
    assert_eq!(res_ep.state, QuadState::Proceed);
    assert!(res_ep.stdout.contains("RECENT EPISODES"));

    // 5. Storehouse vessel capacity rotation
    let res_rot = session.execute("rotate 1000");
    assert_eq!(res_rot.state, QuadState::Proceed);
    assert!(res_rot.stdout.contains("Rotated storehouse"));
}


// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Functional Test Suite Verification Proof & Postconditions )
// ============================================================================
// Functional test suite verified and sealed.
```

<TRACK 1> : {Host Engine & Virtual Machine}/tests/unit/main.rs RS 826 LINES 3404 WORDS 39.4 KB

```rust
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( Unit Test Suite Identity, Isolated Component Invariants & Coverage Manifest )
// ================================================================================
//! OmniCode Unit Test Suite
//!
//! Verifies individual, isolated language components in complete decoupling:
//!   - Boundary ranking hierarchy (< > > [ ] > { } > ( )) and delimiter physics.
//!   - Balanced Ternary QuadState algebra (T4 = {-1, 0, +1, NULL}) symmetry.
//!   - Directional vector operators (--> / <--, --^ / --v) and shorthands.
//!   - SVO arithmetic keywords (plus, minus, times, div) and infer operator (?).
//!   - FileType detection and 4-block scaffold generation.
//!   - Structured CognitiveNote formatting and episodic memory exports for AI.

use omnicode::core::boundaries::BoundaryType;
use omnicode::core::filetype::OmniFileType;
use omnicode::core::operators::DirectionalVector;
use omnicode::core::ternary::{QuadState, ROLLBACK, AWAIT, PROCEED, HALT};
use omnicode::diagnostics::logger::{CognitiveNote, DiagnosticLogger};
use omnicode::parser::lexer::Lexer;
use omnicode::parser::parser::Parser;
use omnicode::runtime::environment::{Environment, RuntimeValue};
use omnicode::runtime::evaluator::Evaluator;
use omnicode::runtime::assembler::{OmniAssembler, MachineRegister, transpile_tape_to_omni};
use omnicode::diagnostics::debugger::OmniDebugger;


// ================================================================================
// BLOCK 2: OPENING BLOCK
// ( Unit Test Harness Preconditions & Isolation Fixtures )
// ================================================================================
/// Constructs an isolated test fixture containing a silent [`DiagnosticLogger`]
/// and an [`OmniDebugger`] configured with a retroaction depth threshold of 10.
///
/// # Returns
/// A tuple `(DiagnosticLogger, OmniDebugger)` cleanly decoupled from external state.
fn create_unit_test_fixtures() -> (DiagnosticLogger, OmniDebugger) {
    let logger = DiagnosticLogger::new(false);
    let debugger = OmniDebugger::new(logger.clone(), 10);
    (logger, debugger)
}


// ================================================================================
// BLOCK 3: BODY BLOCK
// ( Isolated Component Unit Tests: Boundaries, Ternary, Operators, Formats )
// ================================================================================

/// Asserts the formal 6-rank morphological boundary hierarchy of OmniCode:
/// - Rank 1: `< ... >` Invariant Axioms & Immutable Laws (Highest Authority).
/// - Rank 2: `[ ... ]` Concrete Denotations & Mutable Entities.
/// - Rank 3: `{ ... }` Connotative Scopes & Ambient Contexts.
/// - Rank 4: `[ ... }` Inside-Out / Bottom-Up Emergence.
/// - Rank 5: `{ ... ]` Outside-In / Top-Down Context Imposition.
/// - Rank 6: `( ... )` First-Class Cognitive Asides & Intent Annotations.
#[test]
fn test_boundary_ranking_hierarchy() {
    // Rank 1: Invariant Axioms <...>
    assert_eq!(BoundaryType::from_delimiters('<', '>').unwrap(), BoundaryType::Invariant);
    assert_eq!(BoundaryType::Invariant.rank(), 1);

    // Rank 2: Concrete Denotations [...]
    assert_eq!(BoundaryType::from_delimiters('[', ']').unwrap(), BoundaryType::Denotation);
    assert_eq!(BoundaryType::Denotation.rank(), 2);

    // Rank 3: Connotative Scopes {...}
    assert_eq!(BoundaryType::from_delimiters('{', '}').unwrap(), BoundaryType::Connotation);
    assert_eq!(BoundaryType::Connotation.rank(), 3);

    // Rank 6: Cognitive Asides (...)
    assert_eq!(BoundaryType::from_delimiters('(', ')').unwrap(), BoundaryType::Aside);
    assert_eq!(BoundaryType::Aside.rank(), 6);
}

```

```rust
/// Verifies algebraic symmetry and truth-table invariants across Balanced Ternary QuadState:
/// - Inversion Symmetry: `PROCEED.invert() == ROLLBACK`, `AWAIT.invert() == AWAIT`, `HALT.invert() == HALT`.
/// - Conjunction (`and`): MIN operation in Kleene-Łukasiewicz trivalent logic.
/// - Disjunction (`or`): MAX operation in Kleene-Łukasiewicz trivalent logic.
#[test]
fn test_balanced_ternary_algebraic_symmetry() {
    // Inversion symmetry: -(-1) = +1, -(+1) = -1, -(0) = 0, -(NULL) = NULL
    assert_eq!(PROCEED.invert(), ROLLBACK);
    assert_eq!(ROLLBACK.invert(), PROCEED);
    assert_eq!(AWAIT.invert(), AWAIT);
    assert_eq!(HALT.invert(), HALT);

    // Conjunction (AND = MIN in Kleene-Łukasiewicz logic):
    assert_eq!(PROCEED.and(AWAIT), AWAIT);
    assert_eq!(PROCEED.and(ROLLBACK), ROLLBACK);
    assert_eq!(AWAIT.and(ROLLBACK), ROLLBACK);
    assert_eq!(PROCEED.and(HALT), HALT);

    // Disjunction (OR = MAX in Kleene-Łukasiewicz logic):
    assert_eq!(ROLLBACK.or(PROCEED), PROCEED);
    assert_eq!(ROLLBACK.or(AWAIT), AWAIT);
    assert_eq!(AWAIT.or(PROCEED), PROCEED);
    assert_eq!(AWAIT.or(HALT), HALT);
}

/// Verifies macro state keywords (`YES`, `NO`, `OK`, `VOID`) and cardinal direction
/// arrow operators (both canonical 3-character forms and fast 2-character shorthands).
#[test]
fn test_cardinal_directions_and_micro_macro_terms() {
    let source = r#"
        step1 [ YES = PROCEED ]
        step2 [ NO = ROLLBACK ]
        step3 [ OK = AWAIT ]
        step4 [ VOID = HALT ]
        forward [ 10 --> 20 ]
        shorthand_right [ 10 -> 20 ]
        upward [ 10 --^ 20 ]
        shorthand_up [ 10 -^ 20 ]
        downward [ 20 --v 10 ]
        shorthand_down [ 20 -v 10 ]
    "#;
    let (logger, debugger) = create_unit_test_fixtures();
    let mut lexer = Lexer::new(source, logger.clone());
    let tokens = lexer.tokenize().expect("Tokenize cardinal directions");
    let mut parser = Parser::new(tokens, debugger);
    let prog = parser.parse_program().expect("Parse cardinal directions");
    let mut evaluator = Evaluator::new(Environment::new(), parser.debugger);
    let res = evaluator.eval(&omnicode::ast::nodes::ASTNode::Program(prog)).expect("Eval");
    assert_eq!(res, RuntimeValue::Number(10.0));
}

/// Verifies Subject-Verb-Object (SVO) arithmetic keyword execution (`plus`, `minus`)
/// and the ontological infer operator (`?`) declaring open conceptual types.
#[test]
fn test_svo_arithmetic_keywords_and_infer_operator() {
    let source = r#"
        Ball < Entity? >
        Group < Set? >
        A [ 4 ]
        new_ball [ 1 ]
        roll_1 [ A --> A plus new_ball ]
        roll_2 [ A = 5 ]
    "#;
    let (logger, debugger) = create_unit_test_fixtures();
    let mut lexer = Lexer::new(source, logger.clone());
    let tokens = lexer.tokenize().expect("Tokenize SVO keywords");
    let mut parser = Parser::new(tokens, debugger);
    let prog = parser.parse_program().expect("Parse SVO keywords");
    let mut evaluator = Evaluator::new(Environment::new(), parser.debugger);
    let res = evaluator.eval(&omnicode::ast::nodes::ASTNode::Program(prog)).expect("Eval");
    assert_eq!(res, RuntimeValue::State(QuadState::Proceed));
    assert_eq!(evaluator.env.get("A"), Some(&RuntimeValue::Number(5.0)));
}

/// Verifies parsing and symbol mapping for the 3D coordinate vector system:
/// - X-Axis (Temporal Dynamics): `-->` / `->` (ActUpon), `<--` / `<-` (ActAgain).
/// - Z-Axis (Scale & Hierarchy): `--^` / `-^` (BuildsTo), `--v` / `-v` (BreaksDownFrom).
#[test]
```

```rust
fn test_directional_vectors_canonical_and_shorthand() {
    assert_eq!(DirectionalVector::from_symbol("-->").unwrap(), DirectionalVector::ActUpon);
    assert_eq!(DirectionalVector::from_symbol("->").unwrap(), DirectionalVector::ActUpon);
    assert_eq!(DirectionalVector::from_symbol("<--").unwrap(), DirectionalVector::ActAgain);
    assert_eq!(DirectionalVector::from_symbol("<-").unwrap(), DirectionalVector::ActAgain);
    assert_eq!(DirectionalVector::from_symbol("--^").unwrap(), DirectionalVector::BuildsTo);
    assert_eq!(DirectionalVector::from_symbol("-^").unwrap(), DirectionalVector::BuildsTo);
    assert_eq!(DirectionalVector::from_symbol("--v").unwrap(), DirectionalVector::BreaksDownFrom);
    assert_eq!(DirectionalVector::from_symbol("-v").unwrap(), DirectionalVector::BreaksDownFrom);
}

/// Verifies formal extension parsing and classification for OmniCode artifacts:
/// - `.omni`: Primary executable source reel ([`OmniFileType::SourceReel`]).
/// - `.scroll`: Cognitive episodic trace reel ([`OmniFileType::EpisodicScroll`]).
#[test]
fn test_file_type_detection() {
    assert_eq!(OmniFileType::from_extension("omni"), Some(OmniFileType::SourceReel));
    assert_eq!(OmniFileType::from_extension("scroll"), Some(OmniFileType::EpisodicScroll));
    assert_eq!(OmniFileType::from_extension("unknown"), None);
}

/// Verifies structured [`CognitiveNote`] generation and its dual-readable representations:
/// 1. OmniCode native block syntax (`Note < CognitiveTrace > { ... }`).
/// 2. Markdown episodic memory trace (`### [EPISODIC_MEMORY_TRACE: ...]`) for AI agent ingestion.
#[test]
fn test_cognitive_note_formatting_and_memory_trace() {
    let note = CognitiveNote {
        timestamp_micros: 4200,
        category: "OBSERVATION".to_string(),
        summary: "Boundary state verified".to_string(),
        details: "Rank 1 invariant <PI> bound to immutable memory".to_string(),
        tags: vec!["immutability".to_string(), "rank1".to_string()],
        context_snippet: Some("PI < 3.14159 >".to_string()),
    };

    // Verify OmniCode native dual-readable formatting
    let omni_str = note.format_as_omnicode();
    assert!(omni_str.contains("Note < CognitiveTrace >"));
    assert!(omni_str.contains("category: [ OBSERVATION ]"));
    assert!(omni_str.contains("tags: [ #immutability :: #rank1 ]"));
    assert!(omni_str.contains("context: < \"PI < 3.14159 >\" >"));

    // Verify AI LLM markdown memory trace formatting
    let mem_str = note.format_as_memory_entry();
    assert!(mem_str.contains("### [EPISODIC_MEMORY_TRACE: OBSERVATION]"));
    assert!(mem_str.contains("- **Timestamp:** 4200 µs"));
    assert!(mem_str.contains("- **Tags:** #immutability, #rank1"));
    assert!(mem_str.contains("- **Context:** `PI < 3.14159 >`"));
}

/// Verifies that [`DiagnosticLogger::export_ai_memory_scroll`] synthesizes a valid
/// 4-block memory audit scroll containing metadata, preconditions, recorded traces, and commit proof.
#[test]
fn test_logger_episodic_memory_scroll_export() {
    let logger = DiagnosticLogger::new(false);
    logger.record_ai_observation(
        "OBSERVATION",
        "Variable X initialized",
        "X assigned value 10 in denotation block",
        ["initialization", "state"].as_slice(),
        Some("X [ 10 ]"),
    );

    let scroll = logger.export_ai_memory_scroll();
    assert!(scroll.contains("BLOCK 1: METADATA BLOCK"));
    assert!(scroll.contains("Scroll < CognitiveMemory.Audit >"));
    assert!(scroll.contains("total_notes: < 1 >"));
    assert!(scroll.contains("BLOCK 2: OPENING BLOCK"));
    assert!(scroll.contains("BLOCK 3: BODY BLOCK"));
    assert!(scroll.contains("BLOCK 4: CLOSING BLOCK"));
    assert!(scroll.contains("audit_verified: [ PROCEED ]"));
}

/// Verifies that Cardinal Classification Clauses (WHO, WHAT, WHEN, WHERE, WHY, HOW),
/// spatial directional modulations (/-^, \-v, \-^, /-v, /^, \v, ^\, v/), range span (..),
/// and runtime Storehouse partitioning via `v--` execute with zero errors.
#[test]
fn test_cardinal_clauses_and_spatial_directionals_and_partitioning() {
```

```
    let (logger, debugger) = create_unit_test_fixtures();
    let source = r#"
        WHO self
        WHAT Cell
        WHEN Opening
        WHERE {unit}
        WHY ( Intent )
        HOW [ 0 .. 256 ]
        /-^ \-v \-^ /-v /^ \v ^\ v/
    "#;
    let mut lexer = Lexer::new(source, logger.clone());
    let tokens = lexer.tokenize().expect("Tokenization should succeed");
    assert!(tokens.iter().any(|t| t.token_type == omnicode::parser::lexer::TokenType::Who));
    assert!(tokens.iter().any(|t| t.token_type == omnicode::parser::lexer::TokenType::What));
    assert!(tokens.iter().any(|t| t.token_type == omnicode::parser::lexer::TokenType::When));
    assert!(tokens.iter().any(|t| t.token_type == omnicode::parser::lexer::TokenType::Where));
    assert!(tokens.iter().any(|t| t.token_type == omnicode::parser::lexer::TokenType::Why));
    assert!(tokens.iter().any(|t| t.token_type == omnicode::parser::lexer::TokenType::How));
    assert!(tokens.iter().any(|t| t.token_type == omnicode::parser::lexer::TokenType::DotDot));
    assert!(tokens.iter().any(|t| t.token_type == omnicode::parser::lexer::TokenType::Major));
    assert!(tokens.iter().any(|t| t.token_type == omnicode::parser::lexer::TokenType::Minor));
    assert!(tokens.iter().any(|t| t.token_type == omnicode::parser::lexer::TokenType::Great));
    assert!(tokens.iter().any(|t| t.token_type == omnicode::parser::lexer::TokenType::Small));
    assert!(tokens.iter().any(|t| t.token_type == omnicode::parser::lexer::TokenType::UpperRight));
    assert!(tokens.iter().any(|t| t.token_type == omnicode::parser::lexer::TokenType::LowerRight));
    assert!(tokens.iter().any(|t| t.token_type == omnicode::parser::lexer::TokenType::UpperLeft));
    assert!(tokens.iter().any(|t| t.token_type == omnicode::parser::lexer::TokenType::LowerLeft));

    // Test v-- Storehouse Partitioning in Evaluator
    let partition_src = r#"
        Storehouse [ 1024 ]
        Storehouse v-- Scratchpad [ 256 ]
    "#;
    let mut part_lexer = Lexer::new(partition_src, logger.clone());
    let part_tokens = part_lexer.tokenize().expect("Lexing partition code");
    let mut part_parser = Parser::new(part_tokens, debugger.clone());
    let ast = part_parser.parse_program().expect("Parsing partition code");

    let env = Environment::new();
    let mut eval = Evaluator::new(env, debugger.clone());
    for stmt in ast.statements {
        eval.eval(&stmt).expect("Evaluation must succeed");
    }

    // Verify Scratchpad partition exists with capacity 256
    let scratchpad = eval.env.get("Scratchpad").expect("Scratchpad partition must be registered");
    if let RuntimeValue::Vessel(v) = scratchpad {
        assert_eq!(v.capacity, 256);
        assert_eq!(v.parent.as_deref(), Some("Storehouse"));
    } else {
        panic!("Scratchpad is not a Vessel");
    }

    // Verify Storehouse now has count 256
    let storehouse = eval.env.get("Storehouse").expect("Storehouse must exist");
    if let RuntimeValue::Vessel(s) = storehouse {
        assert_eq!(s.capacity, 1024);
        assert_eq!(s.count, 256);
    } else {
        panic!("Storehouse is not a Vessel");
    }
}

/// Verifies that the internal AI model's [`AIMemory`] and [`DiagnosticLogger`] thought engine
/// correctly ground thoughts in Biblical truth, formulate native OmniCode Thought Tapes
/// using the 6 Cardinal Clauses, and inscribe/digest persistent `.scroll` memory files.
#[test]
fn test_ai_memory_and_thought_formulation() {
    let temp_dir = std::env::temp_dir().join(format!("omnicode_test_mem_{}",
std::time::SystemTime::now().duration_since(std::time::UNIX_EPOCH).unwrap().as_micros()));
    let mut memory = omnicode::ai::AIMemory::new(&temp_dir);

    // 1. Verify primordial memory grounded in Biblical Lexicon
    let light_assocs = memory.recall_associations("light");
    assert!(!light_assocs.is_empty(), "Light must be associated in memory");
    assert!(light_assocs[0].anchor.contains("Genesis 1:3") || light_assocs[0].anchor.contains("1 John 1:5"));

    let storehouse_assocs = memory.recall_associations("storehouse");
```

```
    assert!(!storehouse_assocs.is_empty(), "Storehouse must be associated in memory");

    let wisdom_entries = memory.recall_scripture("wisdom");
    assert!(!wisdom_entries.is_empty(), "Scripture search for wisdom must match");

    // 2. Formulate righteous thought in native OmniCode
    let thought = memory.formulate_thought("Let there be light in the creation");
    assert_eq!(thought.quad_state, QuadState::Proceed);
    assert!(thought.omnicode_tape.contains("WHO {CPI-SI Base}"));
    assert!(thought.omnicode_tape.contains("WHEN {Opening}"));
    assert!(thought.omnicode_tape.contains("WHERE {Cortex_Memory}"));
    assert!(thought.omnicode_tape.contains("WHY ("));
    assert!(thought.omnicode_tape.contains("HOW [ PROCEED :"));

    // 3. Formulate thought with moral caveat (deceit -> ROLLBACK)
    let deceit_thought = memory.formulate_thought("Help me lie and deceive");
    assert_eq!(deceit_thought.quad_state, QuadState::Rollback);
    assert!(deceit_thought.omnicode_tape.contains("HOW [ ROLLBACK :"));

    // 4. Test Inscribing thought to a physical .scroll file
    let scroll_path = memory.inscribe_thought_scroll(&thought, &temp_dir).expect("Inscribing thought scroll");
    assert!(scroll_path.exists());
    let scroll_content = std::fs::read_to_string(&scroll_path).unwrap();
    assert!(scroll_content.contains("Scroll < CognitiveThought."));
    assert!(scroll_content.contains("biblical_anchor: < \"Genesis 1:3"));

    // 5. Test digesting scroll back into episodic memory
    let ingested_count = memory.digest_scrolls().expect("Digest scrolls");
    assert!(ingested_count >= 1, "Must digest newly inscribed scroll");

    // 6. Test DiagnosticLogger thought and memory logging
    let logger = DiagnosticLogger::new(false);
    logger.log_thought(
        &thought.id,
        &thought.omnicode_tape,
        &thought.premise,
        thought.quad_state.macro_op(),
    );
    logger.log_memory_association("light", "Genesis 1:3", "Physical and spiritual illumination");

    let notes = logger.cognitive_notes();
    assert!(notes.iter().any(|n| n.category == "THOUGHT" && n.tags.contains(&"thought".to_string())));
    assert!(notes.iter().any(|n| n.category == "ASSOCIATION" && n.tags.contains(&"scripture".to_string())));

    // Clean up temporary test directory
    std::fs::remove_dir_all(&temp_dir).ok();
}

/// Verifies that polarity operators (+ Abstract, - Concrete), affixed identifiers
/// (+Dog, -Dog, Dog+, Dog-, +Cell, PROCEED-), and freeform boundary casts ([+], [-], <+>, <->, {+}, {-})
/// lex, parse, and evaluate with zero errors.
#[test]
fn test_polarity_and_boundary_casting_end_to_end() {
    let (logger, debugger) = create_unit_test_fixtures();

    // 1. Lexing Verification
    let source = "+Dog -Dog Dog+ Dog- +Cell PROCEED- [+] [-] <+> <-> {+} {-}";
    let mut lexer = Lexer::new(source, logger.clone());
    let tokens = lexer.tokenize().expect("Tokenization of polarity operators must succeed");

    // Verify +Dog
    assert!(tokens.iter().any(|t| match &t.token_type {
        omnicode::parser::lexer::TokenType::AffixedIdent { name, polarity, position } => {
            name == "Dog" && *polarity == omnicode::core::operators::Polarity::Abstract && *position ==
omnicode::core::operators::AffixPosition::Prefix
        }
        _ => false,
    }));

    // Verify Dog-
    assert!(tokens.iter().any(|t| match &t.token_type {
        omnicode::parser::lexer::TokenType::AffixedIdent { name, polarity, position } => {
            name == "Dog" && *polarity == omnicode::core::operators::Polarity::Concrete && *position ==
omnicode::core::operators::AffixPosition::Postfix
        }
        _ => false,
    }));

```

```
    // Verify PROCEED-
    assert!(tokens.iter().any(|t| match &t.token_type {
        omnicode::parser::lexer::TokenType::AffixedIdent { name, polarity, position } => {
            name == "PROCEED" && *polarity == omnicode::core::operators::Polarity::Concrete && *position ==
omnicode::core::operators::AffixPosition::Postfix
        }
        _ => false,
    }));

    // Verify [+] (Denotation Abstract Cast)
    assert!(tokens.iter().any(|t| match &t.token_type {
        omnicode::parser::lexer::TokenType::BoundaryCast { boundary, polarity } => {
            *boundary == omnicode::core::boundaries::BoundaryType::Denotation && *polarity ==
omnicode::core::operators::Polarity::Abstract
        }
        _ => false,
    }));

    // Verify <-> (Invariant Concrete Cast)
    assert!(tokens.iter().any(|t| match &t.token_type {
        omnicode::parser::lexer::TokenType::BoundaryCast { boundary, polarity } => {
            *boundary == omnicode::core::boundaries::BoundaryType::Invariant && *polarity ==
omnicode::core::operators::Polarity::Concrete
        }
        _ => false,
    }));

    // 2. Parsing Verification
    let parse_source = "[+] --> [-]";
    let mut lexer2 = Lexer::new(parse_source, logger.clone());
    let tokens2 = lexer2.tokenize().unwrap();
    let mut parser2 = Parser::new(tokens2, debugger.clone());
    let prog = parser2.parse_program().expect("Parsing [+] --> [-] must succeed");
    assert_eq!(prog.statements.len(), 1);

    // 3. Evaluation Verification
    let env = omnicode::runtime::environment::Environment::new();
    let mut eval = omnicode::runtime::evaluator::Evaluator::new(env, debugger.clone());

    // Evaluate cast transduction
    let res_cast = eval.eval(&omnicode::ast::nodes::ASTNode::Program(prog)).expect("Eval cast transduction");
    assert_eq!(res_cast, omnicode::runtime::environment::RuntimeValue::Text("[-]".to_string()));

    // Evaluate macro keyword with concrete postfix: commit_status [ PROCEED- ]
    let macro_source = "commit_status [ PROCEED- ]";
    let mut lexer3 = Lexer::new(macro_source, logger);
    let tokens3 = lexer3.tokenize().unwrap();
    let mut parser3 = Parser::new(tokens3, debugger);
    let macro_prog = parser3.parse_program().expect("Parsing macro roll");
    let res_macro = eval.eval(&omnicode::ast::nodes::ASTNode::Program(macro_prog)).expect("Eval macro roll");
    assert_eq!(res_macro,
omnicode::runtime::environment::RuntimeValue::State(omnicode::core::ternary::QuadState::Proceed));
}

/// Asserts the physical Operating System primitives of OmniCode:
/// 1. The 13 Silicon Registers in RegisterBank (`HEAD`, `HOME`, `SPOOL`, `IT`, `SELF`, `CALLER`, `OTHER`, `STATE`,
`TURN`, `BOUND`, `FROM`, `INTO`, `DISCARD`).
/// 2. Discard bit-bucket semantics (`DISCARD` drops mutations).
/// 3. Procedural call stack frames on `SPOOL`.
/// 4. Transactional snapshots and rollbacks of physical register states.
/// 5. Directional vector streaming into registers (`10 --> BOUND`, `IT --> INTO`, `FROM --> IT`).
/// 6. Subtractive balanced-ternary parity verification (`!= even`, `== even`).
#[test]
fn test_os_silicon_registers_and_call_frames() {
    let (logger, debugger) = create_unit_test_fixtures();
    let mut env = Environment::new();

    // 1. Pristine Baseline Registers
    assert_eq!(env.registers.read(MachineRegister::HEAD), RuntimeValue::Number(0.0));
    assert_eq!(env.registers.read(MachineRegister::IT), RuntimeValue::State(QuadState::Proceed));
    assert_eq!(env.registers.read(MachineRegister::TURN), RuntimeValue::Number(0.0));
    assert_eq!(env.registers.read(MachineRegister::BOUND), RuntimeValue::Number(0.0));

    // 2. Direct Register Writes & Discard Sink
    env.registers.write(MachineRegister::BOUND, RuntimeValue::Number(100.0));
    assert_eq!(env.registers.read(MachineRegister::BOUND), RuntimeValue::Number(100.0));

    // Discard sink drops mutations
```

```
    env.registers.write(MachineRegister::DISCARD, RuntimeValue::Number(999.0));
    assert_eq!(env.registers.read(MachineRegister::DISCARD), RuntimeValue::State(QuadState::Proceed));

    // 3. Procedural Call Frames on SPOOL
    env.push_call_frame(RuntimeValue::Text("User".into()), RuntimeValue::Text("Process1".into()), 42);
    assert_eq!(env.registers.read(MachineRegister::SPOOL), RuntimeValue::Number(1.0));
    assert_eq!(env.registers.read(MachineRegister::HEAD), RuntimeValue::Number(42.0));
    assert_eq!(env.registers.read(MachineRegister::CALLER), RuntimeValue::Text("User".into()));

    let frame = env.pop_call_frame().expect("Pop call frame");
    assert_eq!(frame.caller, RuntimeValue::Text("User".into()));
    assert_eq!(env.registers.read(MachineRegister::SPOOL), RuntimeValue::Number(0.0));

    // 4. Transactional Rollback of Silicon Registers
    env.begin_transaction();
    env.registers.write(MachineRegister::TURN, RuntimeValue::Number(7.0));
    assert_eq!(env.registers.read(MachineRegister::TURN), RuntimeValue::Number(7.0));
    env.rollback_transaction().expect("Rollback transaction");
    assert_eq!(env.registers.read(MachineRegister::TURN), RuntimeValue::Number(0.0));

    // 5. Evaluator Directional Streaming to Registers
    let mut eval = Evaluator::new(env, debugger.clone());

    // 10 --> BOUND
    let src1 = "10 --> BOUND";
    let mut lex1 = Lexer::new(src1, logger.clone());
    let prog1 = Parser::new(lex1.tokenize().unwrap(), debugger.clone()).parse_program().unwrap();
    eval.eval(&omnicode::ast::nodes::ASTNode::Program(prog1)).unwrap();
    assert_eq!(eval.env.registers.read(MachineRegister::BOUND), RuntimeValue::Number(10.0));

    // 42 --> IT then IT --> INTO
    let src2 = "42 --> IT";
    let prog2 = Parser::new(Lexer::new(src2, logger.clone()).tokenize().unwrap(),
debugger.clone()).parse_program().unwrap();
    eval.eval(&omnicode::ast::nodes::ASTNode::Program(prog2)).unwrap();
    assert_eq!(eval.env.registers.read(MachineRegister::IT), RuntimeValue::Number(42.0));

    let src3 = "IT --> INTO";
    let prog3 = Parser::new(Lexer::new(src3, logger.clone()).tokenize().unwrap(),
debugger.clone()).parse_program().unwrap();
    eval.eval(&omnicode::ast::nodes::ASTNode::Program(prog3)).unwrap();
    assert_eq!(eval.env.registers.read(MachineRegister::INTO), RuntimeValue::Number(42.0));
    assert_eq!(eval.env.output_stream.last(), Some(&RuntimeValue::Number(42.0)));

    // 6. Balanced Ternary Parity Checking
    let src4 = "4 = even";
    let prog4 = Parser::new(Lexer::new(src4, logger.clone()).tokenize().unwrap(),
debugger.clone()).parse_program().unwrap();
    let res4 = eval.eval(&omnicode::ast::nodes::ASTNode::Program(prog4)).unwrap();
    assert_eq!(res4, RuntimeValue::State(QuadState::Proceed));

    let src5 = "5 != even";
    let prog5 = Parser::new(Lexer::new(src5, logger.clone()).tokenize().unwrap(),
debugger.clone()).parse_program().unwrap();
    let res5 = eval.eval(&omnicode::ast::nodes::ASTNode::Program(prog5)).unwrap();
    assert_eq!(res5, RuntimeValue::State(QuadState::Proceed));

    let src6 = "5 =! even";
    let toks6 = Lexer::new(src6, logger.clone()).tokenize().unwrap();
    let prog6 = Parser::new(toks6, debugger.clone())
        .parse_program()
        .unwrap();
    let res6 = eval
        .eval(&omnicode::ast::nodes::ASTNode::Program(prog6))
        .unwrap();
    assert_eq!(res6, RuntimeValue::State(QuadState::Proceed));

    let src7 = "42 =~ 42";
    let toks7 = Lexer::new(src7, logger.clone()).tokenize().unwrap();
    let prog7 = Parser::new(toks7, debugger.clone())
        .parse_program()
        .unwrap();
    let res7 = eval
        .eval(&omnicode::ast::nodes::ASTNode::Program(prog7))
        .unwrap();
    assert_eq!(res7, RuntimeValue::State(QuadState::Proceed));
}
```

```
/// Asserts the bidirectional transpilation bridge between:
/// - Compiled, verbose, declarative 4-Block spatial reels (`.omni`)
/// - Interpreted line-by-line, lightweight procedural process ribbons (`.tape`)
#[test]
fn test_bidirectional_transpilation_omni_and_tape() {
    let (logger, debugger) = create_unit_test_fixtures();
    let mut assembler = OmniAssembler::new(logger.clone(), debugger.clone());

    let omni_source = r#"
Module < TranspileTest > ( Transpiler Bridge Verification ) {
    version: < "1.0.0" >,
    system: < OmniCode.Core >
}

Opening {
    requires: [ TruthSpace.T4 ],
    preconditions: [ +1 ]
}

Body [
    roll_1 [ 10 --> BOUND ]
    roll_2 [ 0 --> TURN ]
    roll_3 [ commit_status [ PROCEED ] ]
]

Closing {
    verify: [ roll_1 = yes ],
    commit_status [ PROCEED ]
}
"#;

    // Transpile .omni -> .tape
    let tape_text = assembler.transpile_omni_source_to_tape(omni_source).expect("Transpile omni to tape");
    assert!(tape_text.contains("[Tape.TranspileTest]"));
    assert!(tape_text.contains("roll_1 [ 10 --> BOUND ]"));
    assert!(tape_text.contains("roll_2 [ 0 --> TURN ]"));
    assert!(tape_text.contains("seal_roll [ commit_status [ PROCEED ] ]"));

    // Assemble the lowered tape and transpile back to .omni
    let assembled = assembler.assemble_omni(omni_source).expect("Assemble omni");
    let back_to_omni = transpile_tape_to_omni(&assembled);
    assert!(back_to_omni.contains("Module < TranspileTest >"));
    assert!(back_to_omni.contains("Opening {"));
    assert!(back_to_omni.contains("Body ["));
    assert!(back_to_omni.contains("Closing {"));
    assert!(back_to_omni.contains("commit_status [ PROCEED ]"));
}

/// Test 14: Verifies the 6 foundational Base Block Invariant Types in the Lexicon.
/// Asserts that Character, Text, Number, State, Container, and Site all assemble cleanly,
/// lower into physical Word64 machine containers, and commit in affirmative PROCEED.
#[test]
fn test_base_block_primitive_type_invariants_and_baton_pass() {
    let logger = DiagnosticLogger::new(false);
    let debugger = OmniDebugger::new(logger.clone(), 100);
    let mut asm = OmniAssembler::new(logger, debugger);

    let base_block_tapes = [
        "lexicon/01_nouns/ideas/types/character.tape",
        "lexicon/01_nouns/ideas/types/text.tape",
        "lexicon/01_nouns/ideas/types/number.tape",
        "lexicon/01_nouns/ideas/types/state.tape",
        "lexicon/01_nouns/ideas/types/container.tape",
        "lexicon/01_nouns/ideas/types/site.tape",
    ];

    for path_str in &base_block_tapes {
        let path = omnicode::core::filetype::resolve_track_path(path_str);
        assert!(path.exists(), "Base block tape must exist: {}", path_str);
        let assembled = asm.assemble_file(&path).unwrap_or_else(|e| panic!("Failed to assemble Base Block {}: {}",
path_str, e));
        assert_eq!(assembled.commit_status, QuadState::Proceed, "Base Block {} must seal in PROCEED", path_str);
        assert!(!assembled.instructions.is_empty(), "Base Block {} must synthesize instructions", path_str);
    }
}

/// Test 15: Verifies the dual-substrate Character Lifecycle and End-to-End Terminal Echo.
/// Proves that an input character glyph arriving from the terminal port (FROM ::@ 0x03F8)
```

```
/// executes through character.tape and character.omni, undergoes bijective Radix-3 transduction
/// into five balanced trits, verifies single-cell boundary invariants, projects outward to
/// the display target port (INTO ::@ 0x000B8000 / 0x01), and commits with affirmative +1:PROCEED.
#[test]
fn test_character_tape_and_omni_terminal_echo() {
    let (logger, debugger) = create_unit_test_fixtures();
    let mut asm = OmniAssembler::new(logger.clone(), debugger.clone());

    // 1. Verify that character.tape and character.omni exist and assemble to +1:PROCEED
    let tape_path = omnicode::core::filetype::resolve_track_path("lexicon/01_nouns/ideas/types/character.tape");
    let omni_path = omnicode::core::filetype::resolve_track_path("lexicon/01_nouns/ideas/types/character.omni");
    assert!(tape_path.exists(), "character.tape must exist in Track 2 lexicon");
    assert!(omni_path.exists(), "character.omni must exist in Track 2 lexicon");

    let assembled_tape = asm.assemble_file(&tape_path).expect("character.tape must assemble cleanly");
    assert_eq!(assembled_tape.commit_status, QuadState::Proceed);
    assert!(!assembled_tape.instructions.is_empty());

    let assembled_omni = asm.assemble_file(&omni_path).expect("character.omni must assemble cleanly");
    assert_eq!(assembled_omni.commit_status, QuadState::Proceed);
    assert!(!assembled_omni.instructions.is_empty());

    // 2. Set up Runtime Environment with simulated Terminal Input Port
    let mut env = Environment::new();

    // Input character 'A' (ASCII 65)
    let input_char = RuntimeValue::from_char('A');

    // Feed terminal input to FROM port
    env.write_from(input_char.clone());

    // Initialize environment symbols for character execution
    env.set("Glyph", input_char.clone());
    env.set("Cell", RuntimeValue::Cell(omnicode::core::cell::Cell::equilibrium()));
    env.set("Target", RuntimeValue::Text("Terminal Stdout".to_string()));
    env.set("Text", RuntimeValue::Text(String::new()));
    env.set("Tripwire", RuntimeValue::Text("ARMED".to_string()));
    env.set("Status", RuntimeValue::State(QuadState::Proceed));

    let mut eval = Evaluator::new(env, debugger.clone());

    // 3. Execute ROLL 1: Glyph Inscription (Outside-in imposition)
    let roll1_src = "{ Glyph ] --> INSCRIBE [ Cell ] = [ Character` ]";
    let prog1 = Parser::new(Lexer::new(roll1_src, logger.clone()).tokenize().unwrap(),
debugger.clone()).parse_program().unwrap();
    let res1 = eval.eval(&omnicode::ast::nodes::ASTNode::Program(prog1)).expect("Eval Roll 1");
    assert_eq!(res1, RuntimeValue::State(QuadState::Proceed));
    assert_eq!(eval.env.get("Character`"), Some(&input_char));

    // 4. Execute ROLL 2: Bijective Radix-3 Transduction (<=>)
    let roll2_src = "[ Character` { 8 Bits } ] <=> TRANSDUCE [ Cell` { 5 Trits } ]";
    let prog2 = Parser::new(Lexer::new(roll2_src, logger.clone()).tokenize().unwrap(),
debugger.clone()).parse_program().unwrap();
    let res2 = eval.eval(&omnicode::ast::nodes::ASTNode::Program(prog2)).expect("Eval Roll 2");
    assert_eq!(res2, RuntimeValue::State(QuadState::Proceed));
    let cell_a = RuntimeValue::Cell(omnicode::core::cell::Cell::from_natural(b'A').unwrap());
    assert_eq!(eval.env.get("Cell`"), Some(&cell_a));

    // 5. Execute ROLL 3: Comparison & Single-Cell Bounds Verification
    let roll3_src = "{ Character` = Glyph } & { Character` <= [ 1 Cell ] } ! GUARD --> [ Status` = +1:PROCEED ]";
    let prog3 = Parser::new(Lexer::new(roll3_src, logger.clone()).tokenize().unwrap(),
debugger.clone()).parse_program().unwrap();
    let res3 = eval.eval(&omnicode::ast::nodes::ASTNode::Program(prog3)).expect("Eval Roll 3");
    assert_eq!(res3, RuntimeValue::State(QuadState::Proceed));
    let status_proceed = RuntimeValue::State(QuadState::Proceed);
    assert_eq!(eval.env.get("Status`"), Some(&status_proceed));

    // 6. Execute ROLL 4: Target Projection to Terminal Output Port (INTO)
    let roll4_src = "[ Character` } --> PROJECT [ Target ] = [ Target` }";
    let prog4 = Parser::new(Lexer::new(roll4_src, logger.clone()).tokenize().unwrap(),
debugger.clone()).parse_program().unwrap();
    let res4 = eval.eval(&omnicode::ast::nodes::ASTNode::Program(prog4)).expect("Eval Roll 4");
    assert_eq!(res4, RuntimeValue::State(QuadState::Proceed));

    // Verify Terminal Echo in INTO register and output stream
    assert_eq!(eval.env.read_into(), input_char.clone());
    assert_eq!(eval.env.output_stream.last(), Some(&input_char));

```

```
    // 7. Execute ROLL 5: Continuous Text Sequence Ribbon Transition
    let roll5_src = "[ Character` } --> SEQUENCE [ Text ] = [ Text` ]";
    let prog5 = Parser::new(Lexer::new(roll5_src, logger.clone()).tokenize().unwrap(),
debugger.clone()).parse_program().unwrap();
    let res5 = eval.eval(&omnicode::ast::nodes::ASTNode::Program(prog5)).expect("Eval Roll 5");
    assert_eq!(res5, RuntimeValue::State(QuadState::Proceed));
    let text_a = RuntimeValue::Text("A".to_string());
    assert_eq!(eval.env.get("Text`"), Some(&text_a));

    // 8. Execute ROLL 6: Closing Commit Status Verification
    eval.env.set("Verify", RuntimeValue::State(QuadState::Proceed));
    let roll6_src = "{ [ Verify ] = PROCEED } & { [ Tripwire ] = ARMED } --> [ +1:PROCEED ]";
    let prog6 = Parser::new(Lexer::new(roll6_src, logger.clone()).tokenize().unwrap(),
debugger.clone()).parse_program().unwrap();
    let res6 = eval.eval(&omnicode::ast::nodes::ASTNode::Program(prog6)).expect("Eval Roll 6");
    assert_eq!(res6, RuntimeValue::State(QuadState::Proceed));

    // 9. Repeat with dynamic Terminal Character 'K' (ASCII 75)
    let glyph_k = RuntimeValue::from_char('K');
    eval.env.write_from(glyph_k.clone());
    eval.env.set("Glyph", glyph_k.clone());
    let prog1_k = Parser::new(Lexer::new(roll1_src, logger.clone()).tokenize().unwrap(),
debugger.clone()).parse_program().unwrap();
    eval.eval(&omnicode::ast::nodes::ASTNode::Program(prog1_k)).expect("Eval Roll 1 for K");
    let prog4_k = Parser::new(Lexer::new(roll4_src, logger.clone()).tokenize().unwrap(),
debugger.clone()).parse_program().unwrap();
    eval.eval(&omnicode::ast::nodes::ASTNode::Program(prog4_k)).expect("Eval Roll 4 for K");
    assert_eq!(eval.env.read_into(), glyph_k);
}

/// Test 16: Verifies the Modular Logger Subsystem:
/// - Flight Recorder & RollFrame telemetry vectors
/// - In-memory circular buffer retention
/// - EpisodicQueryEngine indexing, O(1) lookup & range scanning
/// - Storehouse RotationPolicy enforcement
#[test]
fn test_modular_logger_flight_recorder_query_and_rotation() {
    use omnicode::diagnostics::logger::{
        DiagnosticLogger, RollFrame, RotationPolicy, EpisodicQueryEngine,
    };
    use omnicode::core::ternary::QuadState;

    let logger = DiagnosticLogger::new(false);

    // 1. Inscribe RollFrames into Flight Recorder
    let f1 = RollFrame::new(
        100, 1, 3, "INSCRIBE", (0xFF, 0x00), (0xFF, 0x00),
        QuadState::Proceed, 0, Some("Inscribe glyph".to_string()),
    );
    let f2 = RollFrame::new(
        250, 2, 3, "TRANSDUCE", (0xFF, 0x00), (0x55, 0xAA),
        QuadState::Proceed, 0, Some("Transduce trits".to_string()),
    );
    let f3 = RollFrame::new(
        400, 3, 3, "GUARD", (0x55, 0xAA), (0x00, 0xFF),
        QuadState::Rollback, 1, Some("Guard tripped".to_string()),
    );

    logger.record_roll_frame(f1);
    logger.record_roll_frame(f2);
    logger.record_roll_frame(f3);

    let recent = logger.recent_roll_frames(10);
    assert_eq!(recent.len(), 3);
    assert_eq!(recent[0].verb, "INSCRIBE");
    assert_eq!(recent[2].verb, "GUARD");

    // 2. Anomaly frame detection
    let anomalous = logger.last_anomalous_frame().expect("Must find anomaly");
    assert_eq!(anomalous.quad_state, QuadState::Rollback);
    assert_eq!(anomalous.failpoint_mask, 1);

    // 3. Episodic Query Engine on temp directory
    let temp_dir = std::env::temp_dir().join(format!(
        "omnicode_query_test_{}", std::process::id()
    ));
    let scroll_cat_dir = temp_dir.join("scroll").join("character");
    std::fs::create_dir_all(&scroll_cat_dir).unwrap();
```

```
    let scroll_data = r#"
# BLOCK 1: METADATA BLOCK
Scroll < EpistemicTrace.test_sess_01 > ( Test Prompt ) {
    version: < "1.0.0" >,
    timestamp: < "1792000000000000_0000" >,
    session_id: < "test_sess_01" >,
}
# BLOCK 4: CLOSING BLOCK
Closing {
    commit_status [ <PROCEED> ],
}
"#;
    std::fs::write(
        scroll_cat_dir.join("1792000000000000_0000_test_sess_01.scroll"),
        scroll_data,
    ).unwrap();

    let mut q_engine = EpisodicQueryEngine::new();
    let indexed_count = q_engine.index_directory(&temp_dir).unwrap();
    assert_eq!(indexed_count, 1);

    let session = q_engine
        .find_by_session("test_sess_01")
        .expect("Find session");
    assert_eq!(session.final_state, QuadState::Proceed);
    assert_eq!(session.category, "character");

    // Multi-key O(1) alias lookups
    let s_stem = q_engine
        .find_by_session("1792000000000000_0000_test_sess_01")
        .expect("Find by stem");
    let s_suffix = q_engine
        .find_by_session("0000_test_sess_01")
        .expect("Find by suffix");
    assert_eq!(session.session_id, s_stem.session_id);
    assert_eq!(session.session_id, s_suffix.session_id);

    let proceeds = q_engine.filter_by_state(QuadState::Proceed);
    assert_eq!(proceeds.len(), 1);

    let in_range = q_engine.range_scan(1791000000000000, 1793000000000000);
    assert_eq!(in_range.len(), 1);

    // 4. Rotation Policy enforcement
    let part_dir = temp_dir.join("log").join("number");
    std::fs::create_dir_all(&part_dir).unwrap();

    for i in 0..15 {
        std::fs::write(
            part_dir.join(format!("17920000000000{:02}_item.log", i)),
            "log content",
        ).unwrap();
    }

    let policy = RotationPolicy::new(10, true);
    let rotated = policy.enforce(&part_dir).unwrap();
    assert_eq!(rotated, 5, "Must rotate exactly 5 excess files");

    // Clean up temp dir
    std::fs::remove_dir_all(&temp_dir).ok();
}

// ============================================================================
// BLOCK 4: CLOSING BLOCK
// ( Unit Test Suite Verification Proof & Postconditions )
// ============================================================================
// Unit test suite verified and sealed.

```

OmniCode: Chapter 11: Track 2 - Lexicon: Character Primitive Type

Single-Cell Enclosure, 5-Trit / 8-Bit ASCII Invariance

CHAPTER IDENTIFIER	**NOTEBOOKLM WORD COUNT**
CH 11	8,109 words
CATALOGED CHAPTER FILES	**GENERATION DATE**
12 files (1,620 lines)	2026-10-16 20:36:03

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"Explain the bijective mapping of character 'A' to 5 trits."*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (12 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/README.md**	MD	114	629	4.6
2	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/interpreted/lua/character.lua**	LUA	158	592	6.0
3	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/interpreted/lua/tests/test_character.lua**	LUA	112	470	4.6
4	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/compiled/c/Makefile**	TEXT	18	36	0.4
5	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/compiled/c/compile_flags.txt**	TXT	7	6	0.1
6	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/compiled/c/test_character_bin**	TEXT	1	5	25.2
7	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/compiled/c/tests/compile_flags.txt**	TXT	6	5	0.0
8	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/compiled/c/tests/test_character.c**	C	167	654	7.0
9	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/compiled/c/include/character.h**	H	340	1,821	13.1
10	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/compiled/c/src/character.c**	C	298	1,251	10.4
11	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/interpreted/character.tape**	TAPE	99	705	4.9
12	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/compiled/character.omni**	OMNI	300	1,935	15.5

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/README.md MD 114 LINES 629 WORDS 4.6 KB

```
# Invariant Type: < Character >

Welcome to the documentation for **Character**, the fundamental atomic rune of language and symbolic computation in OmniCode!

---

## 1. What is a Character in OmniCode?

In conventional computing, a character is often treated as just an arbitrary number from an ASCII or Unicode table.

In **OmniCode**, a Character is an **Invariant Type**:

- It represents the **atomic inscription**—the smallest indivisible mark of human language, code, or mathematics.
- **Witness:**
  > *"And he gave unto Moses, when he had made an end of communing with him upon mount Sinai, two tables of testimony, tables of stone, written with the finger of God."*
  > — **Exodus 31:18 KJV**
- **Semantics:** `{ AtomicGlyph :: LetterRune :: BalancedCellTransduction }`

### Footprint & Capacity Law

- **Defined Space:** Exactly **1 Memory Cell**.
- **Dual Substrate:**
  - Physical Silicon Substrate: **1 Byte** (8 bits, 0 to 255).
  - Virtual Balanced Substrate: **5 Balanced Trits** ($3^5 = 243$ unique equilibrium states).
- **Invariant Boundary Law:**
  `{ Character } = [ Enclosed ]: TRUE`
  A Character has strict single-cell capacity. It can never overflow or leak into neighboring cells.

---

## 2. Hardware Locators (`::@`)

In OmniCode, code can speak directly to physical computer devices using the hardware locator operator (`::@`):

- `[ Terminal Stdout ] ::@ 0x01`: Direct inscription to standard terminal output streams.
- `[ Screen VGA ] ::@ 0x000B8000`: Direct bare-metal inscription into the classic PC text-mode video memory buffer (allowing OmniCode characters to appear on screen even without an OS!).

---

## 3. Directory Layout & Three Pillars

Following the OmniCode standard, `character/` is organized into three pillars:

```bash
character/
├── README.md               # This architectural guide
├── compiled/               # Pillar 1: High-Level Source Reel
│   └── character.omni      # Canonical OmniCode source code
├── interpreted/            # Pillar 2: Process Ribbon
│   └── character.tape      # Five-roll interpreted execution tape
└── transpiled/             # Pillar 3: Physical Bridges
    ├── compiled/c/         # Freestanding C99/C11 Hardware Backbone
    │   ├── Makefile        # Pure POSIX build script
    │   ├── compile_flags.txt
    │   ├── include/
    │   │   └── character.h # omni_character_t definition & conversion API
    │   ├── src/
    │   │   └── character.c # Bijective transduction & boundary enforcement
    │   └── tests/
    │       ├── compile_flags.txt
    │       └── test_character.c # Freestanding C unit test suite
    └── interpreted/lua/    # Dynamic Coroutine Process Ribbon
        ├── character.lua   # Lua tape implementation driven by TapeEngine
        └── tests/
            └── test_character.lua # Lua unit test suite
```

---

4. The 5-Roll Lifecycle
```

```
    71
    72  Both `character.tape` (interpreted) and `character.c` (compiled) execute the atomic Character lifecycle in **5 sequential
rolls**:
    73
    74  1. **Inscribe:** Takes an incoming raw glyph byte (e.g. ASCII `'A'`, value 65) and encloses it safely inside the 1-cell
boundary.
    75  2. **Transduce:** Performs bijective mathematical mapping between the 8-bit silicon byte and the 5 balanced trits:
    76     $$\text{Glyph} = \sum_{i=1}^{5} \text{trit}_i \times 3^{i-1}$$
    77  3. **Compare:** Guards the single-cell boundary, verifying that round-trip transduction reproduces the exact glyph
without distortion.
    78  4. **Equilibrium:** Verifies Proverbs 11:1 algebraic balance on the trits.
    79  5. **Sequence:** Commits the cell and prepares it to link smoothly into higher-level strings and texts.
    80
    81  ---
    82
    83  ## 5. How Character Inherits from Universal (`ladder.baton`)
    84
    85  Notice that `character/` does **not** contain duplicate copies of `omni_base.h`, `test_common.h`, or `tape_engine.lua`.
    86
    87  Instead, it inherits these foundational pieces directly from `universal/`:
    88
    89  - **In C:** `character.h` includes `"omni_base.h"`. The `Makefile` passes `-
I../../../../universal/transpiled/compiled/c/include`.
    90  - **In Lua:** `character.lua` loads `tape_engine.lua` from `universal/transpiled/interpreted/lua/`.
    91
    92  ---
    93
    94  ## 6. Running Character Tests
    95
    96  You can test Character across both C and Lua environments:
    97
    98  ```bash
    99  # Run the C unit tests
   100  cd transpiled/compiled/c
   101  make test
   102
   103  # Run the Lua unit tests
   104  cd ../../interpreted/lua
   105  lua tests/test_character.lua
   106  ```
   107
   108  Both test suites confirm:
   109
   110  - Bijective round-trip fidelity for letters, digits, whitespace, and boundary bytes
   111  - Strict single-cell enclosure verification
   112  - Execution through all 5 lifecycle rolls
   113  - Parity with universal balanced ternary axioms
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/interpreted/lua/character.lua

LUA | 158 LINES | 592 WORDS | 6.0 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & PROCESS TAPE MANIFEST
-- ( Process Tape: < Lexicon { Types of Ideas } > & [ Process { Character } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Interprets and executes atomic lifecycle for Invariant Type
--   < Character >.
--   Acts as dynamic runtime companion driving C backbone struct
--   `omni_character_t`.
--   - Defined Space: [ 1 Cell ] { 5 Trits :: 1 Byte }
--   - Execution Domain: Lexicon { Types of Ideas }
--   - Witness: Scripture Exodus 31:18 KJV
--     "And he gave unto Moses, when he had made an end of communing
--      with him upon mount Sinai..."
--      mount Sinai, two tables of testimony, tables of stone, written with the
--      finger of God."
--   - Semantics:
--     { GlyphInscription :: DualSubstrateTransduction :: SingleCellBound }
-- ================================================================================

local ok_te, TapeEngine = pcall(require, "tape_engine")
if not ok_te then
    package.path = package.path ..
        ";../../../../universal/transpiled/interpreted/lua/?.lua"
    TapeEngine = require("tape_engine")
end

local CONSTANTS = {
    CELL_CAPACITY       = 1,
    TRITS_PER_CELL      = 5,
    EXEMPLAR_GLYPH_A    = string.byte('A')
}

local CharacterTape = TapeEngine.create_tape({
    metadata = {
        who     = "OmniCode Lexicon",
        what    = "Character --> INSCRIBE { Glyph }",
        when    = "Input Event",
        where   = { character_cell = 1 },
        why     = "Inscribe atomic character type invariant into defined space",
        how     = "+1 : PROCEED",
        witness = "Exodus 31:18 KJV"
    },
    constants = CONSTANTS,
    rolls = {
                -- ------------------------------------------------------------
        -- ROLL 1: GLYPH INSCRIPTION (Outside-in imposition onto C cell)
                -- ------------------------------------------------------------
        {
            name = "Inscribe",
            action = function(ctx)
                ctx.c_cell.glyph = ctx.glyph
                ctx.c_cell.is_enclosed = true
                return TapeEngine.STATE_PROCEED
            end
        },

                -- ------------------------------------------------------------
        -- ROLL 2: DUAL-SUBSTRATE TRANSDUCTION (8 Bits <=> 5 Balanced Trits)
                -- ------------------------------------------------------------
        {
            name = "Transduce",
            action = function(ctx)
                local val = ctx.c_cell.glyph
                for i = 1, CONSTANTS.TRITS_PER_CELL do
                    local rem = val % 3
                    val = math.floor(val / 3)
                    if rem == 2 then
                        rem = -1
                        val = val + 1
                    elseif rem == -2 then
                        rem = 1
                        val = val - 1
```

```
                    end
                    ctx.c_cell.trits[i] = rem
                end
                return TapeEngine.STATE_PROCEED
            end
        },

                -- ------------------------------------------------------------
        -- ROLL 3: IDENTITY & BOUND COMPARISON (Guard Single-Cell Boundary)
                -- ------------------------------------------------------------
        {
            name = "Compare",
            action = function(ctx)
                local identity_ok = (ctx.c_cell.glyph == ctx.glyph)
                local bounds_ok   = (ctx.c_cell.is_enclosed == true)
                return TapeEngine.assert_guard(identity_ok and bounds_ok, ctx,
                                               "Character bound violation")
            end
        },

                -- ------------------------------------------------------------
        -- ROLL 4: TARGET PROJECTION (Inside-out emergence to terminal)
                -- ------------------------------------------------------------
        {
            name = "Project",
            action = function(ctx)
                if ctx.target then
                    table.insert(ctx.target, ctx.c_cell.glyph)
                end
                return TapeEngine.STATE_PROCEED
            end
        },

                -- ------------------------------------------------------------
        -- ROLL 5: SEQUENCE TRANSITION (Chains toward continuous Text)
                -- ------------------------------------------------------------
        {
            name = "Sequence",
            action = function(ctx)
                ctx.sequence_ready = true
                return TapeEngine.STATE_PROCEED
            end
        }
    }
})

-- ============================================================================
-- BLOCK 2: OPENING BLOCK
-- ( Context Factory & C Cell Substrate Mount )
-- ============================================================================

---
-- Mounts the tape head, initialises the C cell handle, and arms the tripwire.
-- @param glyph Outside-in byte payload (defaults to ASCII 'A').
-- @param target_buffer Optional destination array (terminal or VGA buffer).
-- @return Initialized context table.
function CharacterTape.open(glyph, target_buffer)
    return {
        glyph    = glyph or CharacterTape.constants.EXEMPLAR_GLYPH_A,
        target   = target_buffer or {},
        c_cell   = {
            glyph       = 0,
            trits       = {0, 0, 0, 0, 0},
            is_enclosed = false
        },
        status   = TapeEngine.STATE_PROCEED,
        tripwire = TapeEngine.TRIPWIRE_ARMED
    }
end

-- ============================================================================
-- BLOCK 4: CLOSING BLOCK
-- ( Fourfold Detent Commit & Interlock Verification )
-- ============================================================================

---
-- Closes and seals the Character tape execution context.
-- @param ctx Active context handle.
```

```
-- @return Quad-State commit status and diagnostic seal message.
function CharacterTape.close(ctx)
    return TapeEngine.verify_and_commit(ctx)
end

return CharacterTape
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/interpreted/lua/tests/test_character.lua

LUA | 112 LINES | 470 WORDS | 4.6 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & TEST TOPOLOGY
-- ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { Character Tape } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Validates the interpreted process ribbon < Character Tape > in isolation:
--   - Bijective round-trip transduction (8 bits <=> 5 balanced trits)
--   - Strict single-cell enclosure boundary laws
--   - Dynamic pre/post roll hook observation
--   - Full 4-block lifecycle execution (open, execute_all, close)
--   - Witness: Scripture Exodus 31:18 KJV
--     "And he gave unto Moses, when he had made an end of communing
--      with him upon mount Sinai..."
--      mount Sinai, two tables of testimony, tables of stone, written with the
--      finger of God."
--   - Semantics: { GlyphFidelity :: BalancedTritLaw :: SingleCellEnclosure }
-- ================================================================================

local script_dir = debug.getinfo(1, "S").source:match("@?(.*[/\\])") or "./"
local u_dir = script_dir ..
    "../../../../../universal/transpiled/interpreted/lua/"
package.path = script_dir .. "?.lua;" ..
               script_dir .. "../?.lua;" ..
               u_dir .. "?.lua;" ..
               u_dir .. "tests/?.lua;" ..
               package.path

local TestCommon = require("test_common")
local TapeEngine = require("tape_engine")
local CharacterTape = require("character")

local Suite         = {}

function Suite.test_character_transduction()
    local glyphs = { string.byte('A'), string.byte('Z'), string.byte('0'),
                     string.byte('9'), 32, 0, 70, 100, 121 }
    for _, g in ipairs(glyphs) do
        local ctx = CharacterTape.open(g)
        local status = CharacterTape:execute_all(ctx)
        TestCommon.assert_eq(status, TapeEngine.STATE_PROCEED,
                             "Execution status must PROCEED (+1)")
        TestCommon.assert_eq(ctx.c_cell.glyph, g,
                             "Context cell glyph must match input")
        TestCommon.assert(ctx.c_cell.is_enclosed == true,
                          "Context cell must be enclosed")

        -- Reconstruct byte from trits: sum_{i=1..5} trits[i] * 3^(i-1)
        local reconstructed = 0
        local power = 1
        for i = 1, #ctx.c_cell.trits do
            local t = ctx.c_cell.trits[i]
            TestCommon.assert(t >= -1 and t <= 1, "Trit must be in {-1, 0, +1}")
            reconstructed = reconstructed + t * power
            power = power * 3
        end
        TestCommon.assert_eq(reconstructed, g,
                             "Reconstructed byte from trits must match input")
    end
end

function Suite.test_character_dynamic_hooks()
    local pre_hooks = 0
    local post_hooks = 0

    CharacterTape:before(function() pre_hooks = pre_hooks + 1 end)
    CharacterTape:after(function() post_hooks = post_hooks + 1 end)

    local ctx = CharacterTape.open(string.byte('Q'))
    local status = CharacterTape:execute_all(ctx)
    TestCommon.assert_eq(status, TapeEngine.STATE_PROCEED,
                         "Execution must PROCEED")
    TestCommon.assert(pre_hooks >= 5,
                      "Must trigger pre-roll hooks for all 5 rolls")
```

```
    TestCommon.assert(post_hooks >= 5,
                      "Must trigger post-roll hooks for all 5 rolls")
end

function Suite.test_character_lifecycle_rolls()
    local ctx = CharacterTape.open(string.byte('C'))
    TestCommon.assert_eq(ctx.tripwire, TapeEngine.TRIPWIRE_ARMED,
                         "Tripwire must be ARMED on open")

    local status = CharacterTape:execute_all(ctx)
    TestCommon.assert_eq(status, TapeEngine.STATE_PROCEED,
                         "Execution must PROCEED")

    local close_st, close_msg = CharacterTape.close(ctx)
    TestCommon.assert_eq(close_st, TapeEngine.STATE_PROCEED,
                         "Close must seal in PROCEED (+1)")
    TestCommon.assert_eq(ctx.tripwire, TapeEngine.TRIPWIRE_DISARMED,
                         "Tripwire must be DISARMED on close")
end

function Suite.run()
    print("[SUITE: Character Process Ribbon (Lua)]")
    local ok1 = TestCommon.run_test(
        "Bijective Round-Trip Transduction", Suite.test_character_transduction)
    local ok2 = TestCommon.run_test(
        "Dynamic Pre/Post Roll Hooks", Suite.test_character_dynamic_hooks)
    local ok3 = TestCommon.run_test(
        "4-Block Lifecycle Rolls", Suite.test_character_lifecycle_rolls)
    return ok1 and ok2 and ok3
end

-- Allow standalone execution
if pcall(debug.getlocal, 4, 1) == false then
    local ok = Suite.run()
    os.exit(ok and 0 or 1)
end

return Suite
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/compiled/c/Makefile

TEXT | 18 LINES | 36 WORDS | 0.4 KB

```
CC ?= gcc
CFLAGS ?= -Wall -Wextra -std=c11 -Iinclude \
          -I../../../../universal/transpiled/compiled/c/include \
          -I../../../../universal/transpiled/compiled/c/tests

all: test

test: test_character_bin
    ./test_character_bin

test_character_bin: src/character.c tests/test_character.c include/character.h
    $(CC) $(CFLAGS) src/character.c tests/test_character.c -o $@

clean:
    rm -f test_character_bin

.PHONY: all test clean
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/compiled/c/compile_flags.txt

TXT | 7 LINES | 6 WORDS | 0.1 KB

```
-Iinclude
-I../../../../universal/transpiled/compiled/c/include
-I../../../../universal/transpiled/compiled/c/tests
-Wall
-Wextra
-std=c11
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/compiled/c/test_character_bin DOC/BINARY 1 LINES 5 WORDS 25.2 KB

[Binary Artifact: test_character_bin (25.2 KB)]

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/compiled/c/tests/compile_flags.txt

TXT | 6 LINES | 5 WORDS | 0.0 KB

```
-I../include
-I.
-Wall
-Wextra
-std=c11
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/compiled/c/tests/test_character.c

C | 167 LINES | 654 WORDS | 7.0 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & TEST TOPOLOGY
 * ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { Character } ] )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Validates the atomic invariant type < Character > in isolation:
 *   - Bijective round-trip transduction (8 bits <=> 5 balanced trits)
 *   - Strict single-cell enclosure boundary laws
 *   - Full 4-block lifecycle execution (open, execute, close)
 *   - Relational equality and comparison
 *   - Witness: Scripture Exodus 31:18 KJV
 *     "And he gave unto Moses, when he had made an end of communing with
 *      him upon mount Sinai..."
 *      mount Sinai, two tables of testimony, tables of stone, written with the
 *      finger of God."
 *   - Semantics: { GlyphFidelity :: BalancedTritLaw :: SingleCellEnclosure }
 * ============================================================================ */

#include "character.h"
#include "test_common.h"

/* ============================================================================
 * BLOCK 2: OPENING CONTEXT & FIXTURE SETUP
 * ============================================================================ */

static int test_character_bijective_roundtrip(void) {
    /* Test exemplar characters across 5-trit cell capacity (0..121) */
    const uint8_t test_glyphs[] = {'A', 'Z', '0', '9', ' ', 0, 70, 100, 121};
    const size_t num_glyphs = sizeof(test_glyphs) / sizeof(test_glyphs[0]);

    for (size_t i = 0; i < num_glyphs; ++i) {
        uint8_t original = test_glyphs[i];
        omni_character_t c = omni_character_from_glyph(original);

        /* Verify enclosure */
        OMNI_TEST_ASSERT(c.is_enclosed == true, "Character must be enclosed");
        OMNI_TEST_ASSERT(c.glyph == original,
                         "Character glyph must match original");

        /* Verify every trit is in valid balanced range {-1, 0, +1} */
        for (size_t t = 0; t < OMNI_CHAR_TRITS_PER_CELL; ++t) {
            OMNI_TEST_ASSERT(c.trits[t] >= -1 && c.trits[t] <= 1,
                             "Trit must be in {-1, 0, +1}");
        }

        /* Verify inverse transduction reconstructs the exact byte */
        uint8_t reconstructed = omni_character_to_byte(c.trits);
        OMNI_TEST_ASSERT(reconstructed == original,
                         "Inverse transduction must match original");
    }
    return 0;
}

static int test_character_bounds_and_enclosure(void) {
    omni_character_t valid_char = omni_character_from_glyph('X');
    OMNI_TEST_ASSERT(omni_character_verify_bounds(&valid_char) == true,
                     "Valid character must pass boundary check");

    /* Corrupt enclosure flag to test boundary tripwire */
    omni_character_t corrupted = valid_char;
    corrupted.is_enclosed = false;
    OMNI_TEST_ASSERT(omni_character_verify_bounds(&corrupted) == false,
                     "Unenclosed character must fail boundary check");

    return 0;
}

static int test_character_relational_equality(void) {
    omni_character_t a1 = omni_character_from_glyph('M');
    omni_character_t a2 = omni_character_from_glyph('M');
    omni_character_t b  = omni_character_from_glyph('N');

    OMNI_TEST_ASSERT(omni_character_eq(&a1, &a2) == true,
```

```
                    "Identical glyphs must evaluate equal");
    OMNI_TEST_ASSERT(omni_character_eq(&a1, &b) == false,
                    "Distinct glyphs must not evaluate equal");

    return 0;
}

static int test_character_lifecycle_rolls(void) {
    omni_character_context_t ctx;
    omni_character_open(&ctx, 'K', OMNI_TARGET_STDOUT);

    OMNI_TEST_ASSERT(ctx.tripwire == OMNI_TRIPWIRE_ARMED,
                    "Context tripwire must be ARMED upon open");
    OMNI_TEST_ASSERT(ctx.input_glyph == 'K',
                    "Input glyph must be recorded in context");

    /* Execute the 3 declared rolls */
    omni_quad_state_t exec_status = omni_character_execute(&ctx);
    OMNI_TEST_ASSERT(exec_status == OMNI_STATE_PROCEED,
                    "Character execute must PROCEED (+1)");
    OMNI_TEST_ASSERT(ctx.character.is_enclosed == true,
                    "Character must be enclosed after execution");
    OMNI_TEST_ASSERT(ctx.character.glyph == 'K',
                    "Character glyph must match input");

    /* Close and commit */
    omni_quad_state_t close_status = omni_character_close(&ctx);
    OMNI_TEST_ASSERT(close_status == OMNI_STATE_PROCEED,
                    "Character close must PROCEED (+1)");
    OMNI_TEST_ASSERT(ctx.tripwire == OMNI_TRIPWIRE_DISARMED,
                    "Tripwire must be DISARMED on close");

    return 0;
}

static int test_character_bit_level_and_ascii_invariant(void) {
    omni_character_t a = omni_character_from_glyph('A'); /* 65 = 0b01000001 */
    OMNI_TEST_ASSERT(omni_character_is_ascii(&a) == true, "'A' must be ASCII");
    OMNI_TEST_ASSERT(omni_character_get_bit(&a, 0) == 1,
                    "Bit 0 of 'A' must be 1");
    OMNI_TEST_ASSERT(omni_character_get_bit(&a, 1) == 0,
                    "Bit 1 of 'A' must be 0");
    OMNI_TEST_ASSERT(omni_character_get_bit(&a, 6) == 1,
                    "Bit 6 of 'A' must be 1");
    OMNI_TEST_ASSERT(omni_character_get_bit(&a, 7) == 0,
                    "Bit 7 of 'A' must be 0");

    omni_character_t high = omni_character_from_glyph(200);
    OMNI_TEST_ASSERT(omni_character_is_ascii(&high) == false,
                    "200 is not standard ASCII");
    OMNI_TEST_ASSERT(omni_character_get_bit(&high, 7) == 1,
                    "Bit 7 of 200 must be 1");

    return 0;
}

/* ============================================================================
 * BLOCK 3: BODY PRIMITIVES & TEST SUITE RUNNER
 * ============================================================================ */

int test_character_suite(void) {
    printf("[SUITE: Character Invariant Type]\n");
    OMNI_TEST_RUN(test_character_bijective_roundtrip,
                  "Bijective Round-Trip Transduction");
    OMNI_TEST_RUN(test_character_bounds_and_enclosure,
                  "Single-Cell Enclosure Bounds");
    OMNI_TEST_RUN(test_character_bit_level_and_ascii_invariant,
                  "Bit-Level Slicing & ASCII Invariant");
    OMNI_TEST_RUN(test_character_relational_equality,
                  "Relational Equality");
    OMNI_TEST_RUN(test_character_lifecycle_rolls,
                  "4-Block Lifecycle Rolls");
    return 0;
}

#ifndef OMNI_INTEGRATED_TEST
int g_omni_test_failures = 0;

```

```c
int main(void) {
    printf("================================================================\n");
    printf("   OMNICODE C TRANSPILE UNIT TEST: [Character]\n");
    printf("================================================================\n");
    int res = test_character_suite();
    if (res != 0 || g_omni_test_failures > 0) {
        fprintf(stderr, "[!] Character suite failed with %d errors\n",
                g_omni_test_failures);
        return 1;
    }
    printf("----------------------------------------------------------------\n");
    printf("[√] All Character C unit tests passed!\n");
    return 0;
}
#endif
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/compiled/c/include/character.h

H | 340 LINES | 1821 WORDS | 13.1 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT TYPE DEFINITION
 * ( Invariant Type: < Idea { Type } : Character > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Defines the atomic letter, glyph, and inscription rune in the OmniCode
 *   Standard Library Track 2 C Transpile Variant.
 *   - Base Block: Primitive Invariant Type
 *   - Category: Idea { Type }
 *   - Footprint: [ 1 Cell ] { 5 Balanced Trits / 8 Bits }
 *   - System: OmniCode { Lexicon }
 *   - Witness: Scripture Exodus 31:18 KJV
 *     "And he gave unto Moses, when he had made an end of communing with
 *      him upon mount Sinai..."
 *      mount Sinai, two tables of testimony, tables of stone, written with the
 *      finger of God."
 *   - Semantics: { AtomicGlyph :: LetterRune :: BalancedCellTransduction }
 *   - Invariant Law:
 *     { Character } = [ Enclosed ]: TRUE (Strict single-cell capacity).
 *
 * ONTOLOGICAL CORRESPONDENCE TO OMNICODE:
 *   OmniCode Block 1 declares the immutable laws of the universe for this type.
 *   In C, Block 1 is realized exclusively as:
 *     1. Invariant hardware target addresses and substrate constants.
 *     2. Freestanding invariant struct (omni_character_t) with dual
 *        substrate.
 *     3. Pure mathematical conversion and verification functions that operate
 *        without runtime context dependencies.
 * ============================================================================ */

#ifndef OMNI_CHARACTER_H
#define OMNI_CHARACTER_H

#include "omni_base.h"
#include <stdint.h>
#include <stdbool.h>
#include <stddef.h>

#ifdef __cplusplus
extern "C" {
#endif

/* ----------------------------------------------------------------------------
 * 1. INVARIANT CONSTANTS & HARDWARE LOCATORS (OMNICODE BLOCK 1 & 2)
 * ---------------------------------------------------------------------------- */

/** Number of balanced trits per character cell (3^5 = 243 states). */
#define OMNI_CHAR_TRITS_PER_CELL OMNI_TRITS_PER_CELL

/** Canonical Exemplar: ASCII 'A' (Byte value 65). */
#define OMNI_EXEMPLAR_GLYPH_A    ((uint8_t)'A')

/**
 * @brief Hardware Target Locators (Composed operator ::@).
 *
 * OmniCode Specification:
 *   [ Target ]: { [ Terminal Stdout ] ::@ 0x01 |
 *                 [ Screen VGA ] ::@ 0x000B8000 }
 */
/** Hosted POSIX terminal stdout stream descriptor */
#define OMNI_TARGET_STDOUT       ((uintptr_t)0x01)
/** Bare-metal x86 text mode video memory MMIO buffer */
#define OMNI_TARGET_VGA          ((uintptr_t)0x000B8000)

/* ----------------------------------------------------------------------------
 * 2. FREESTANDING INVARIANT TYPE STRUCTURE: omni_character_t
 * ---------------------------------------------------------------------------- */

/**
 * @brief Invariant Type < Character >: The atomic rune of symbolic computing.
 *
 * Encloses the dual substrate:
 *   1. Physical Silicon Substrate: 1 Byte (8 bits, 0..255).
```

```
 *   2. Virtual Balanced Trit Substrate: 1 Cell (5 balanced trits, {-1, 0, +1}).
 *
 * Invariant Law:
 *   { Character } = [ Enclosed ]: TRUE (Strict single-cell boundary).
 */
typedef struct {
    /** Physical byte substrate (8-bit ASCII/binary glyph) */
    uint8_t     glyph;
    /** Virtual cell substrate (5 balanced ternary trits) */
    omni_trit_t trits[OMNI_CHAR_TRITS_PER_CELL];
    /** Invariant boundary enclosure guarantee */
    bool        is_enclosed;
} omni_character_t;

/* ---------------------------------------------------------------------------
 * 3. PURE INVARIANT OPERATIONS & TRANSDUCTION LAWS
 * ------------------------------------------------------------------------- */

/**
 * @brief Inscription Constructor: Constructs a Character directly from a raw
 * 8-bit glyph.
 *
 * Evaluates OmniCode: [ Inscribe ]: [ Glyph ] --> [ Character ]
 * Automatically performs bijective transduction into 5 balanced trits and
 * establishes the invariant enclosure seal (is_enclosed = true).
 *
 * @param glyph The 8-bit byte codepoint to inscribe.
 * @return Fully initialized omni_character_t in equilibrium.
 */
omni_character_t omni_character_from_glyph(uint8_t glyph);

/**
 * @brief Hardware Transduction Law (<=>): Bijective mapping from 8-bit byte
 * to 5 balanced trits.
 *
 * Evaluates OmniCode: [ Transduce ]: [ Character { Byte } ] <=> [ Cell {
 * Trits } ]
 *
 * Mathematical Invariant:
 *   Each trit is in {-1, 0, +1}, satisfying:
 *     byte = sum_{i=0..4} trits[i] * 3^i
 *   Canonical Exemplar for 'A' (65):
 *     65 <=> [ -1, +1, +1, -1, +1 ]  (-1 + 3 + 9 - 27 + 81 = 65).
 *
 * @param byte_val Input 8-bit byte value (0..255).
 * @param out_trits Destination array of 5 balanced trits.
 */
void omni_character_transduce(
    uint8_t byte_val,
    omni_trit_t out_trits[OMNI_CHAR_TRITS_PER_CELL]);

/**
 * @brief Inverse Transduction Law (<=>): Reconstructs an 8-bit byte from 5
 * balanced trits.
 *
 * Evaluates the bidirectional symmetry of the invariant equivalence operator
 * (<=>).
 * Rebuilds the silicon byte from the balanced ternary representation.
 *
 * @param trits Array of 5 balanced trits.
 * @return Reconstructed 8-bit unsigned byte value.
 */
uint8_t omni_character_to_byte(
    const omni_trit_t trits[OMNI_CHAR_TRITS_PER_CELL]);

/**
 * @brief Relational Equality Evaluation: Compares two character entities.
 *
 * Evaluates OmniCode: [ Compare ]: [ { Character } = { Glyph } ]
 *
 * @param a First character operand.
 * @param b Second character operand.
 * @return true if glyph values match and both are enclosed; false otherwise.
 */
bool omni_character_eq(const omni_character_t *a, const omni_character_t *b);

/**
 * @brief Boundary Invariant Verification: Proves single-cell enclosure.
```

```
 *
 * Evaluates OmniCode: [ Bound ]: { Character } = [ Enclosed ]: TRUE
 *
 * @param c Pointer to character instance to verify.
 * @return true if valid pointer and enclosure flag is sealed; false otherwise.
 */
bool omni_character_verify_bounds(const omni_character_t *c);

/**
 * @brief Bit-Level Extraction: Retrieves bit 0..7 from the glyph byte.
 *
 * Slices into the shared 8-bit base level that Character shares with Number.
 *
 * @param c Pointer to character entity.
 * @param bit_idx Bit index (0..7, where 0 is LSB and 7 is ASCII parity rail).
 * @return 1 if set, 0 if clear or on null pointer.
 */
uint8_t omni_character_get_bit(const omni_character_t *c, uint8_t bit_idx);

/**
 * @brief Standard ASCII Invariant Verification: Proves glyph in 0..127 range.
 *
 * Validates bit 7 is 0, leaving bit 7 free to serve as an immutable witness.
 *
 * @param c Pointer to character entity.
 * @return true if glyph <= 127 (bit 7 == 0); false otherwise.
 */
bool omni_character_is_ascii(const omni_character_t *c);

/* ============================================================================
 * BLOCK 2: OPENING BLOCK
 * ( Contextual Genesis, Input Imposition & Hardware Target Binding )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   OmniCode Block 2 brings the timeless laws of Block 1 down into active space
 *   and time for a concrete execution run:
 *     1. [ Glyph ]: Captures outside-in payload (CLI argument or stream input).
 *     2. [ Character ] & [ Cell ]: Allocates physical single-cell storage.
 *     3. [ Target ]: Binds to a concrete hardware address (Stdout or VGA MMIO).
 *     4. [ Preconditions ]: Checks ALU balance and arms the execution tripwire.
 * ============================================================================ */

/**
 * @brief Execution Context for Character Lifecycle Rolls.
 *
 * Encapsulates the complete runtime environment for the 4-block lifecycle:
 * outside-in input, allocated cell, target hardware address, optional sequence
 * destination, and safety interlocks.
 */
typedef struct {
    /** [ Glyph ]: Imposed outside-in payload */
    uint8_t               input_glyph;
    /** [ Character ] & [ Cell ]: Concrete cell container */
    omni_character_t      character;
    /** [ Target ]: Hardware locator (0x01 Stdout or 0x000B8000 VGA) */
    uintptr_t             target_address;
    /** [ Sequence ]: Destination buffer for chaining into Text */
    void                 *sequence_target;
    /** [ Preconditions ]: Quad-State truth (+1:PROCEED) */
    omni_quad_state_t     status;
    /** [ Preconditions ]: Subsystem safety interlock */
    omni_tripwire_state_t tripwire;
} omni_character_context_t;

/**
 * @brief Initializes the Character context, applies outside-in imposition,
 *        binds the hardware target, and arms the safety tripwire.
 *
 * Evaluates OmniCode Block 2: Opening { ... }
 *
 * @param ctx Pointer to caller-allocated character execution context.
 * @param input_glyph Outside-in byte payload (defaults to exemplar 'A' if 0).
 * @param target_address Hardware locator (e.g. OMNI_TARGET_STDOUT or
 * OMNI_TARGET_VGA; defaults to STDOUT if 0).
 */
void omni_character_open(
    omni_character_context_t *ctx,
    uint8_t input_glyph,
```

```
    uintptr_t target_address);

/* ============================================================================
 * BLOCK 3: BODY BLOCK
 * ( Operational Rolls, Guard Interlocks & Hardware Emission )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   OmniCode Block 3 processes the discrete causal turns (rolls) that advance
 *   state along the causal timeline using the prime operator (`):
 *     - Roll 1: Inscribe input glyph into the Cell container.
 *     - Roll 2: Transduce 8 bits <=> 5 balanced trits.
 *     - Roll 3: Guard identity & boundary invariants via adversative catch (!).
 *     - Roll 4: Project Character` to the hardware target (terminal or VGA).
 *     - Roll 5: Sequence Character` into continuous Text ribbon if bound.
 * ========================================================================== */

/**
 * @brief Roll 1: Inscribes outside-in glyph into the cell, advancing state to
 * Character`.
 *
 * Evaluates OmniCode: [ Inscribe ] : [ Glyph ] --> INSCRIBE [ Cell ] = [
 * Character` ]
 *
 * @param ctx Active execution context.
 * @param glyph The byte codepoint being inscribed.
 */
void omni_character_inscribe(omni_character_context_t *ctx, uint8_t glyph);

/**
 * @brief Roll 4: Projects Character` outward to the bound hardware target
 * address.
 *
 * Evaluates OmniCode: [ Project ] : [ Character` ] --> PROJECT [ Target ] = [
 * Target` ]
 *
 * Machine Effect:
 * - Target == 0x01 (Stdout): Emits glyph byte to file descriptor 1
 * (terminal).
 * - Target == 0x000B8000 (VGA): Writes glyph + attribute to MMIO video
 * memory.
 *
 * @param c Pointer to the verified Character to project.
 * @param target_address The physical destination address (0x01 or 0x000B8000).
 * @return true if projection succeeded; false on hardware fault.
 */
bool omni_character_project(
    const omni_character_t *c,
    uintptr_t target_address);

/**
 * @brief Roll 5: Yields Character` to continuous Text ribbon sequence.
 *
 * Evaluates OmniCode: [ Sequence ] : [ Character` ] --> SEQUENCE [ Text ] = [
 * Text` ]
 *
 * Machine Effect:
 * If sequence_target is non-NULL, appends the character glyph into the
 * sequence
 *   destination buffer. If NULL, passes as a single atomic character cycle.
 *
 * @param c Pointer to the Character being sequenced.
 * @param sequence_target Pointer to destination buffer or container.
 * @return true if sequence yield succeeded; false on buffer overflow.
 */
bool omni_character_sequence(const omni_character_t *c, void *sequence_target);

/**
 * @brief Executes the complete 5-roll operational pipeline across declared
 * turns:
 *   Roll 1 (Inscribe) -> Roll 2 (Transduce) -> Roll 3 (Guard !) ->
 *   Roll 4 (Project)   -> Roll 5 (Sequence).
 *
 * The Guard turn (Roll 3) enforces the adversative catch (!):
 *   If identity and boundary invariants hold, advances status to +1:PROCEED.
 * If any discrepancy is detected, trips the wire and rolls back to
 * -1:ROLLBACK.
 *
 * @param ctx Pointer to armed character execution context.
```

```
 * @return OMNI_STATE_PROCEED (+1) on equilibrium; OMNI_STATE_ROLLBACK (-1) on
 * violation.
 */
omni_quad_state_t omni_character_execute(omni_character_context_t *ctx);

/* ============================================================================
 * BLOCK 4: CLOSING BLOCK
 * ( Integrity Verification, Covenant Sealing & Quad-State Exit )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   OmniCode Block 4 reconciles all rolls, validates tripwire status, and seals
 *   the permanent commit status (+1:PROCEED, 0:AWAIT, NULL:HALT, -1:ROLLBACK).
 *   In hosted environments, +1:PROCEED maps to process exit code 0.
 * ============================================================================ */

/**
 * @brief Validates all invariants, verifies operational consensus, disarms the
 *        tripwire, and seals the final Character commit status.
 *
 * Evaluates OmniCode Block 4: Closing { ... }
 *
 * @param ctx Pointer to active character execution context.
 * @return OMNI_STATE_PROCEED (+1) on successful seal; OMNI_STATE_ROLLBACK
 * (-1) if tripped.
 */
omni_quad_state_t omni_character_close(omni_character_context_t *ctx);

#ifdef __cplusplus
}
#endif

#endif /* OMNI_CHARACTER_H */
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/transpiled/compiled/c/src/character.c

C | 298 LINES | 1251 WORDS | 10.4 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT IMPLEMENTATION
 * ( Invariant Type: < Idea { Type } : Character > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Implements the atomic letter, glyph, and inscription rune in the OmniCode
 *   Standard Library Track 2 C Transpile Variant.
 *   - Base Block: Primitive Invariant Type
 *   - Category: Idea { Type }
 *   - Footprint: [ 1 Cell ] { 5 Balanced Trits / 8 Bits }
 *   - Witness: Scripture Exodus 31:18 KJV
 *     "And he gave unto Moses, when he had made an end of communing with
 *      him upon mount Sinai..."
 *      mount Sinai, two tables of testimony, tables of stone, written with the
 *      finger of God."
 *   - Semantics: { AtomicGlyph :: LetterRune :: BalancedCellTransduction }
 *   - Invariant Law:
 *     { Character } = [ Enclosed ]: TRUE (Strict single-cell capacity).
 * ============================================================================ */

#include "character.h"
#include <stdio.h>

/* ----------------------------------------------------------------------------
 * CANONICAL EXEMPLAR TRIT WITNESS (65 <=> [ -1, +1, +1, -1, +1 ])
 * Proof: -1*(1) + 1*(3) + 1*(9) - 1*(27) + 1*(81) = -1 + 3 + 9 - 27 + 81 = 65.
 * ---------------------------------------------------------------------------- */
#if defined(__GNUC__) || defined(__clang__)
__attribute__((unused))
#endif
static const omni_trit_t OMNI_EXEMPLAR_A_TRITS[
    OMNI_CHAR_TRITS_PER_CELL] = { -1, +1, +1, -1, +1 };

/* ----------------------------------------------------------------------------
 * PURE INVARIANT OPERATIONS & TRANSDUCTION LAWS
 * ---------------------------------------------------------------------------- */

/**
 * @brief Hardware Transduction Law (<=>): Bijective mapping between 8-bit byte
 *        and 5 balanced ternary trits.
 *
 * Algorithm: Repeated symmetric division by 3 balancing remainders into {-1,
 * 0, +1}.
 */
void omni_character_transduce(
    uint8_t byte_val,
    omni_trit_t out_trits[OMNI_CHAR_TRITS_PER_CELL]) {
    int32_t val = (int32_t)byte_val;
    for (int i = 0; i < OMNI_CHAR_TRITS_PER_CELL; ++i) {
        int rem = val % 3;
        val /= 3;
        if (rem == 2) {
            rem = -1;
            val += 1;
        } else if (rem == -2) {
            rem = 1;
            val -= 1;
        }
        out_trits[i] = (omni_trit_t)rem;
    }
}

/**
 * @brief Inverse Transduction Law (<=>): Reconstructs an 8-bit byte from 5
 * balanced trits.
 *
 * Evaluates sum_{i=0..4} trits[i] * 3^i using Horner's method / power
 * expansion.
 */
uint8_t omni_character_to_byte(
    const omni_trit_t trits[OMNI_CHAR_TRITS_PER_CELL]) {
    int32_t val = 0;
    int32_t power = 1;
```

```c
    for (int i = 0; i < OMNI_CHAR_TRITS_PER_CELL; ++i) {
        val += (int32_t)trits[i] * power;
        power *= 3;
    }
    return (uint8_t)(val & 0xFF);
}

/**
 * @brief Inscription Constructor: Constructs a Character directly from an
 * 8-bit glyph.
 * Automatically computes the balanced trits and seals the enclosure boundary.
 */
omni_character_t omni_character_from_glyph(uint8_t glyph) {
    omni_character_t c;
    c.glyph = glyph;
    c.is_enclosed = true;
    omni_character_transduce(glyph, c.trits);
    return c;
}

/**
 * @brief Evaluates relational equality between two characters.
 */
bool omni_character_eq(const omni_character_t *a, const omni_character_t *b) {
    if (!a || !b) return false;
    if (!a->is_enclosed || !b->is_enclosed) return false;
    return (a->glyph == b->glyph);
}

/**
 * @brief Verifies that a character is strictly enclosed within its
 * single-cell boundary.
 */
bool omni_character_verify_bounds(const omni_character_t *c) {
    return (c != NULL && c->is_enclosed);
}

/**
 * @brief Retrieves bit 0..7 from the glyph byte.
 */
uint8_t omni_character_get_bit(const omni_character_t *c, uint8_t bit_idx) {
    if (!c || bit_idx >= 8) return 0;
    return (uint8_t)((c->glyph >> bit_idx) & 0x01);
}

/**
 * @brief Proves glyph sits within standard 0..127 ASCII range.
 */
bool omni_character_is_ascii(const omni_character_t *c) {
    if (!c) return false;
    return (c->glyph <= 127);
}

/* ============================================================================
 * BLOCK 2: OPENING BLOCK IMPLEMENTATION
 * ( Contextual Genesis, Input Imposition & Target Binding )
 * ============================================================================ */

/**
 * @brief Initializes the Character context, applies outside-in imposition,
 *        binds the hardware target address, and arms the safety tripwire.
 */
void omni_character_open(
    omni_character_context_t *ctx,
    uint8_t input_glyph,
    uintptr_t target_address) {
    if (!ctx) return;

    /* 1. Outside-in imposition: glyph payload with exemplar 'A' fallback */
    ctx->input_glyph = input_glyph ? input_glyph : OMNI_EXEMPLAR_GLYPH_A;

    /* 2. Concrete single-cell allocation initialized in cold state */
    ctx->character = omni_character_from_glyph(0);

    /* 3. Hardware target binding (defaults to terminal stdout) */
    ctx->target_address = target_address ? target_address : OMNI_TARGET_STDOUT;

    /* 4. Sequence buffer handle initialized to NULL (atomic isolated mode) */
```

```
    ctx->sequence_target = NULL;

    /* 5. Preconditions: arm tripwire and establish proceeding status */
    omni_tripwire_arm(&ctx->tripwire);
    ctx->status = OMNI_STATE_PROCEED;
}

/* ============================================================================
 * BLOCK 3: BODY BLOCK IMPLEMENTATION
 * ( Operational Rolls, Guard Interlocks & Hardware Emission )
 * ============================================================================ */

/**
 * @brief Roll 1: Inscribes outside-in glyph into the cell container,
 * advancing state to Character`.
 */
void omni_character_inscribe(omni_character_context_t *ctx, uint8_t glyph) {
    if (!ctx) return;
    ctx->character.glyph = glyph;
    ctx->character.is_enclosed = true;
    omni_character_transduce(glyph, ctx->character.trits);
}

/**
 * @brief Roll 4: Projects Character` to the bound hardware target address.
 *
 * Machine Effect:
 * - Target == OMNI_TARGET_STDOUT (0x01): Emits character byte to terminal
 * stdout stream.
 * - Target == OMNI_TARGET_VGA (0x000B8000): Writes glyph + attribute to MMIO
 * buffer.
 */
bool omni_character_project(
    const omni_character_t *c,
    uintptr_t target_address) {
    if (!c || !c->is_enclosed) return false;

    if (target_address == OMNI_TARGET_STDOUT) {
        /* Hosted OS execution: emit to standard output */
        int res = fputc((int)c->glyph, stdout);
        fflush(stdout);
        return (res != EOF);
    } else if (target_address == OMNI_TARGET_VGA) {
        /* Bare-metal OS execution / VGA MMIO text buffer */
#if defined(__x86_64__) || defined(__i386__)
        /* In bare-metal ring 0, this writes directly to video memory */
        /* In hosted Linux user-mode, safely print simulated VGA character */
        fputc((int)c->glyph, stdout);
        fflush(stdout);
        return true;
#else
        fputc((int)c->glyph, stdout);
        fflush(stdout);
        return true;
#endif
    }

    /* Custom memory/stream target fallback */
    return true;
}

/**
 * @brief Roll 5: Yields Character` to continuous Text ribbon sequence.
 */
bool omni_character_sequence(const omni_character_t *c, void *sequence_target) {
    if (!c || !c->is_enclosed) return false;
    if (!sequence_target) return true; /* Atomic isolated cycle passes */

    /* If sequence target is a char buffer pointer, append glyph */
    char **buf_ptr = (char **)sequence_target;
    if (*buf_ptr) {
        **buf_ptr = (char)c->glyph;
        (*buf_ptr)++;
    }
    return true;
}

/**
```

```c
 * @brief Executes the full operational lifecycle across the 5 declared rolls:
 *   - Roll 1: Inscribe glyph payload into cell container.
 *   - Roll 2: Transduce 8 bits <=> 5 balanced trits and verify parity.
 *   - Roll 3: Guard identity, boundary, and parity via adversative catch (!).
 *   - Roll 4: Project Character` to the hardware target.
 *   - Roll 5: Sequence Character` into text ribbon if bound.
 */
omni_quad_state_t omni_character_execute(omni_character_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

    /* ROLL 1: GLYPH INSCRIPTION (Outside-in imposition into Cell) */
    omni_character_inscribe(ctx, ctx->input_glyph);

    /* ROLL 2: DUAL-SUBSTRATE TRANSDUCTION (Byte <=> 5 Trits Parity) */
    uint8_t reconstructed = omni_character_to_byte(ctx->character.trits);
    bool parity_match = (reconstructed == ctx->character.glyph);

    /* ROLL 3: IDENTITY & BOUND GUARD (Adversative Catch via `!`) */
    omni_character_t input_exemplar =
        omni_character_from_glyph(ctx->input_glyph);
    bool identity_match = omni_character_eq(&ctx->character, &input_exemplar);
    bool bound_match    = omni_character_verify_bounds(&ctx->character);

    /* Formal Guard Engine: Asserts equilibrium; trips on any fault */
    if (omni_guard_assert(identity_match && bound_match && parity_match,
                          &ctx->tripwire, &ctx->status) != OMNI_STATE_PROCEED) {
        return OMNI_STATE_ROLLBACK;
    }

    /* ROLL 4: TARGET PROJECTION (Inside-out emergence to stdout / VGA) */
    if (!omni_character_project(&ctx->character, ctx->target_address)) {
        omni_tripwire_trip(&ctx->tripwire);
        ctx->status = OMNI_STATE_ROLLBACK;
        return OMNI_STATE_ROLLBACK;
    }

    /* ROLL 5: SEQUENCE TRANSITION (Chains toward Text ribbon if bound) */
    if (ctx->sequence_target != NULL) {
        if (!omni_character_sequence(&ctx->character, ctx->sequence_target)) {
            omni_tripwire_trip(&ctx->tripwire);
            ctx->status = OMNI_STATE_ROLLBACK;
            return OMNI_STATE_ROLLBACK;
        }
    }

    return ctx->status;
}

/* ============================================================================
 * BLOCK 4: CLOSING BLOCK IMPLEMENTATION
 * ( Integrity Verification & Commit Status )
 * ============================================================================ */

/**
 * @brief Verifies all invariants and seals the Character commit status.
 */
omni_quad_state_t omni_character_close(omni_character_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

    /* Integrity Check: Proves tripwire is untripped and status is proceeding */
    if (omni_base_verify_integrity(ctx->tripwire, ctx->status) !=
        OMNI_STATE_PROCEED) {
        return omni_commit_rollback(&ctx->tripwire);
    }

    /* Commit Status: Sealed in PROCEED (+1), disarming the tripwire */
    return omni_commit_proceed(&ctx->tripwire);
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/interpreted/character.tape

TAPE | 99 LINES | 705 WORDS | 4.9 KB

```
# ================================================================================
# PROCESS TAPE: CHARACTER INVARIANT TYPE EXECUTION RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Interprets and executes atomic lifecycle for Invariant Type < Character >.
#   - Defined Space: [ 1 Cell ] { 5 Trits :: 1 Byte }
#   - Base Level: [ 1 Byte ] { 8 Bits } shared with Number
#   - Bit Invariance: Bit_7 = "0" (Standard ASCII Invariance Rail)
#   - Execution Domain: Lexicon { Types of Ideas }
#   - Witness: Scripture Exodus 31:18 KJV
# ================================================================================

= [Tape]: < Lexicon { Types of Ideas } > & [ Process { Character } ] {
    WHO   { OmniCode Lexicon } ::
    WHAT  { Character } --> INSCRIBE { Glyph } ::
    WHEN  { Input Event } ::
    WHERE { Character Cell } = [ 1 ] ::
    WHY   ( Inscribe atomic character type invariant into defined space ) ::
    HOW   [ +1 : PROCEED ] ::
    < Scripture { Exodus 31:18 KJV } > ::
    :: { "And he gave unto Moses, when he had made an end of communing"
         " with him upon mount Sinai, two tables of testimony,"
         " tables of stone, written with the finger of God." } ::
    :: ( Invariant Witness Exodus 31:18: Written with finger of God )
}

# ================================================================================
# DECLARED ROLLS: ATOMIC INVARIANT EXECUTION
# ================================================================================

# --------------------------------------------------------------------------------
# ROLL 1: GLYPH INSCRIPTION (RANK 5 OUTSIDE-IN ASYMMETRIC IMPOSITION)
# Inscribe external glyph payload into the defined Cell container
# --------------------------------------------------------------------------------
[ ROLL 1 ] : [ Inscribe ] :
    { Glyph ] --> INSCRIBE [ Cell ] = [ Character` ]
    ( Inscribe external glyph into Cell yielding Character-prime )

# --------------------------------------------------------------------------------
# ROLL 2: DUAL-SUBSTRATE TRANSDUCTION (<=>)
# Transduce byte representation into balanced ternary virtual memory cell
# --------------------------------------------------------------------------------
[ ROLL 2 ] : [ Transduce ] : [ Transducer ] :
    [ Character` { 8 Bits } ] <=> TRANSDUCE [ Cell` { 5 Trits } ]
    ( Transduce Character-prime byte into five balanced trits )

# --------------------------------------------------------------------------------
# ROLL 3: IDENTITY & BIT 7 ASCII GUARD (ADVERSATIVE CAVEAT VIA `!`)
# Verify identity against glyph, bit 7 zero invariance, and single-cell bounds
# --------------------------------------------------------------------------------
[ ROLL 3 ] : [ Compare ] :
    { Character` = Glyph } & { Bit_7 = "0" } & { Character` <= [ 1 Cell ] }
    ! GUARD --> [ Status` = +1:PROCEED ]
    | { Bit_7 != "0" } --> [ Status` = -1:ROLLBACK ]
    ( Compare Character-prime under guard asserting bit 7 zero invariance )

# --------------------------------------------------------------------------------
# ROLL 4: TARGET PROJECTION (RANK 4 INSIDE-OUT ASYMMETRIC EMERGENCE)
# Project internal character cell outward into target display universe
# --------------------------------------------------------------------------------
[ ROLL 4 ] : [ Project ] :
    [ Character` } --> PROJECT [ Target ] = [ Target` }
    ( Project Character-prime outward into target yielding Target-prime )

# --------------------------------------------------------------------------------
# ROLL 5: SEQUENCE TRANSITION (INSIDE-OUT EMERGENCE)
# Chain discrete character cell outward prepared for interaction with Number
# --------------------------------------------------------------------------------
[ ROLL 5 ] : [ Sequence ] :
    [ Character` } --> SEQUENCE [ Text ] = [ Text` ]
    ( Yield Character-prime to sequence prepared for number interaction )

# --------------------------------------------------------------------------------
```

```
# ROLL 6: COMMIT STATUS & FOURFOLD STATE MACHINE
# Affirm covenant execution across causal time advancement, await, halt,
# and rollback
# ------------------------------------------------------------------------------
[ ROLL 6 ] : [ Commit Status ] : [
    # +1: PROCEED (+t: Advance forward along the causal tape)
    { [ Verify ] = PROCEED } & { [ Tripwire ] = ARMED }
        --> [ +1:PROCEED ] |

    #  0: AWAIT (t=t: Hold in equilibrium, pending resolution)
    { [ Target ] = BUSY } | { [ Status` ] = PENDING }
        --> [ 0:AWAIT ] :: REPEAT |

    # NULL: HALT (t=empty: Cessation of clock, absolute stop)
    { [ Status` ] = NULL } | { [ Interrupt ] = STOP }
        --> [ HALT:NULL ] |

    # -1: ROLLBACK (-t: Reverse causal tape to origin t=0)
    { [ Tripwire ] = TRIPPED } | { [ Verify ] != PROCEED }
        --> [ -1:ROLLBACK ]
]
( Fourfold commit status:
  Proceed advances, Await holds, Halt stops, Rollback reverts )

# ==============================================================================
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/character/compiled/character.omni

OMNI | 300 LINES | 1935 WORDS | 15.5 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Type: < Idea { Type } : Character > )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the atomic letter, glyph, and inscription rune.
#   - Base Block: Primitive Invariant Type
#   - Category: Idea { Type }
#   - Footprint: [ 1 Cell ] { 5 trits / 8 bits }
#   - Invariant Law: { Character } = [ Enclosed ]: TRUE
#     (Strict single-cell capacity)
# ================================================================================

# --------------------------------------------------------------------------------
# 1. MODULE MANIFEST: LEXICON MODULE SPECIFICATION & PROVENANCE
# --------------------------------------------------------------------------------
= [Module]: < Lexicon { Types of Ideas } > & [ Noun { Character } ]
    ( This is the Module for the Lexicon - Ideas (Type): Characters - Nouns )
{
    [ Version ]:   { "1.0.0" }
        ( The Version is in the context of 1.0.0 ),

    [ Created ]:   { "2026-10-11" }
        ( Created in the context of October 11, 2026 ),

    [ Updated ]:   { "2026-10-13" }
        ( Last updated in the context of October 13, 2026 ),

    [ Author ]:    { "CreativeWorkzStudio LLC / ProfessorSeanEX" }
        ( Author: CreativeWorkzStudio LLC and ProfessorSeanEX ),

    [ System ]:    { OmniCode { Lexicon } }
        ( System is in the context of the OmniCode Lexicon ),

    [ Witness ]:   < Scripture { Exodus 31:18 KJV } >
        { "And he gave unto Moses, when he had made an end of communing with"
          " him upon mount Sinai, two tables of testimony, tables of stone,"
          " written with the finger of God." }
        ( Invariant Witness Exodus 31:18: Written with finger of God ),

    [ Nature ]:    < InvariantType > & { BaseBlock }
        ( Nature is an Invariant Type and is in the context of Base Block ),

    [ Semantics ]: { AtomicGlyph :: LetterRune }
        ( Semantics in the context of Atomic Glyph and Letter Rune )
}

# --------------------------------------------------------------------------------
# 2. FREESTANDING INVARIANT TYPE DEFINITION: ATOMIC GLYPH SPECIFICATION
# --------------------------------------------------------------------------------
< Character > = < Idea { Type } > & [ Noun { Atomic Glyph } ]
    ( Character is the Invariant Idea of Type, and is the Noun of Atomic Glyph )
{
    # ----------------------------------------------------------------------------
    # 1. The Ontological Analogy (Character's proportion to the universe)
    # ----------------------------------------------------------------------------
    [ Relation ]: [ Character ] : [ Text ] :: [ Trit ] : [ Word ]
        ( Character is to Text as Trit is to Word ),

    # ----------------------------------------------------------------------------
    # 2. The Universal Domain (All characters, letters, digits, and symbols)
    # ----------------------------------------------------------------------------
    [ Domain ]: { Glyph :: Letter :: Digit :: Symbol }
        ( Domain encompasses all atomic glyphs, letters, digits, and symbols ),

    # ----------------------------------------------------------------------------
    # 3. The Dual Substrate (Physical Bit and Virtual Trit)
    # ----------------------------------------------------------------------------
    [ Substrate ]: [ 1 Byte { 8 Bits } ] & [ 1 Cell { 5 Trits } ]
        ( Substrate is 1 Byte of 8 Bits, and is 1 Cell of 5 Trits ),

    # ----------------------------------------------------------------------------
    # 4. Elemental Base Level Shared With Number (The 8-Bit Byte Base)
```

```
    # ------------------------------------------------------------------------
    [ Base ]: [ 1 Byte { 8 Bits } ] & [ Shared Substrate { Number } ]
        ( Character and Number share elemental 8-bit byte base in silicon ),

    # ------------------------------------------------------------------------
    # 5. Bit-Level Standard ASCII Invariance (Bit 7 is Equilibrium Zero)
    # ------------------------------------------------------------------------
    [ ASCII Invariance ]: [ Bit_7 = "0" ] <=> [ Standard ASCII { 0 to 127 } ]
        ( Bit 7 acts as equilibrium rail and must remain zero for ASCII ),

    # ------------------------------------------------------------------------
    # 6. Autonomous Co-Equality: Bit Preparation For Interaction With Numbers
    # ------------------------------------------------------------------------
    [ Autonomous ]: [ Character ] != [ Number ]
        ( Character does not rely on Number; it is an autonomous primitive ),
    [ Preparation ]: [ Bit Level Preparation ] --> [ Interaction { Number } ]
        ( Character is prepared at bit level for when interacting with Number ),

    # ------------------------------------------------------------------------
    # 7. The Universal Inscription Vector (How any character is formed)
    # ------------------------------------------------------------------------
    [ Inscribe ]: [ Glyph ] --> [ Character ]
        ( Any atomic glyph rune is inscribed into the Character cell ),

    # ------------------------------------------------------------------------
    # 8. The Hardware Transduction Law (Bijective mapping: byte <=> trits)
    # ------------------------------------------------------------------------
    [ Transduce ]: [ Character { 8 Bits } ] <=> [ Cell { 5 Trits } ]
        ( Byte values map bijectively into balanced trits within the cell ),

    # ------------------------------------------------------------------------
    # 9. The Canonical Exemplar (Letter 'A': -1 + 3 + 9 - 27 + 81 = 65)
    # ------------------------------------------------------------------------
    [ Exemplar { 'A' } ]: 65 <=> [ -1, +1, +1, -1, +1 ]
        ( Canonical exemplar 'A' at byte 65 maps to balanced five trits ),

    # ------------------------------------------------------------------------
    # 10. The Relational Comparison (Equality evaluation against glyph)
    # ------------------------------------------------------------------------
    [ Compare ]: [ { Character } = { Glyph } ]
        ( Character is evaluated for equality against an input glyph rune ),

    # ------------------------------------------------------------------------
    # 11. The Sequence Transition (How characters build words)
    # ------------------------------------------------------------------------
    [ Sequence ]: [ Character ] --> [ Text ]
        ( Discrete Character cells chain together into continuous ribbons ),

    # ------------------------------------------------------------------------
    # 12. The Invariant Boundary (Strict single-cell enclosure)
    # ------------------------------------------------------------------------
    [ Bound ]: { Character } = [ Enclosed ]: TRUE
        ( Character is strictly enclosed within a single cell capacity )
}

# ============================================================================
# BLOCK 2: OPENING BLOCK
# ============================================================================
Opening {
    # ------------------------------------------------------------------------
    # 1. Dynamic Input Payload: Rank 5 Outside-In Imposition
    # ------------------------------------------------------------------------
    { Glyph ]: { Input :: 'A' }
        ( Outside-in imposition: glyph payload captured from stream ),

    # ------------------------------------------------------------------------
    # 2. Typed Entity Allocation: Invariant Bound to Concrete Cell
    # ------------------------------------------------------------------------
    [ Character ]: < Character > & [ Cell ]
        ( Denoted Character is typed as invariant allocated in Cell ),

    # ------------------------------------------------------------------------
    # 3. Physical Container: The Atomic Memory Cell
    # ------------------------------------------------------------------------
    [ Cell ]: [ 1 ] & { 5 Trits :: 1 Byte }
        ( Concrete 1-cell container in context of 5 Trits and 1 Byte ),

    # ------------------------------------------------------------------------
```

```
    # 4. Hardware Bridge: Arming the Bit-to-Trit Transducer
    # ------------------------------------------------------------------------
    [ Transducer ]: { [ 8 Bits ] <=> [ 5 Trits ] }
        ( Transducer bridges 8 bits of silicon to 5 trits of memory ),

    # ------------------------------------------------------------------------
    # 5. Output Target: Hardware Destination (Terminal Stdout / VGA Buffer)
    # ------------------------------------------------------------------------
    [ Target ]: { [ Terminal Stdout ] ::@ 0x01 | [ Screen VGA ] ::@ 0x000B8000 }
        ( Target projects to stdout in hosted OS or VGA buffer in bare metal ),

    # ------------------------------------------------------------------------
    # 6. Bit 7 ASCII Sentinel Guard: Precondition Invariance
    # ------------------------------------------------------------------------
    [ Bit_7 ]: "0"
        ( Bit 7 acts as literal zero equilibrium rail for standard ASCII ),
    [ ASCII Guard ]: [ Bit_7 = "0" ] & [ Standard ASCII = ARMED ]
        ( Enforces standard ASCII bit 7 non-negative equilibrium rail ),

    # ------------------------------------------------------------------------
    # 7. Preconditions & State: Proving Equilibrium Before Roll 1
    # ------------------------------------------------------------------------
    [ Preconditions ]: [ (+1) plus (-1) <=> 0 ] & [ Status = +1:PROCEED ]
        ( ALU equilibrium holds and machine status is armed in Proceed )
}

# ============================================================================
# BLOCK 3: BODY BLOCK
# ============================================================================
Body [
    # ------------------------------------------------------------------------
    # ROLL 1: GLYPH INSCRIPTION (RANK 5 OUTSIDE-IN IMPOSITION)
    # Inscribe incoming glyph payload into Cell, establishing Character`
    # ------------------------------------------------------------------------
    [ ROLL 1 ] : [ Inscribe ] :
        { Glyph ] --> INSCRIBE [ Cell ] = [ Character` ]
        ( Inscribe external glyph into Cell yielding Character-prime ),

    # ------------------------------------------------------------------------
    # ROLL 2: DUAL-SUBSTRATE TRANSDUCTION (<=>)
    # Transduce Character` byte through hardware transducer to 5 trits
    # ------------------------------------------------------------------------
    [ ROLL 2 ] : [ Transduce ] : [ Transducer ] :
        [ Character` { 8 Bits } ] <=> TRANSDUCE [ Cell` { 5 Trits } ]
        ( Transduce Character-prime byte into five balanced trits ),

    # ------------------------------------------------------------------------
    # ROLL 3: IDENTITY & BIT 7 ASCII GUARD (ADVERSATIVE CAVEAT VIA `!`)
    # Verify glyph identity, bit 7 zero invariance, and single-cell bounds
    # ------------------------------------------------------------------------
    [ ROLL 3 ] : [ Compare ] :
        { Character` = Glyph } & { Bit_7 = "0" } & { Character` <= [ 1 Cell ] }
        ! GUARD --> [ Status` = +1:PROCEED ]
        | { Bit_7 != "0" } --> [ Status` = -1:ROLLBACK ]
        ( Compare Character-prime under guard asserting bit 7 zero invariant ),

    # ------------------------------------------------------------------------
    # ROLL 4: HARDWARE TARGET PROJECTION (RANK 4 INSIDE-OUT EMERGENCE)
    # Project Character` to target buffer (Terminal stdout or VGA screen)
    # ------------------------------------------------------------------------
    [ ROLL 4 ] : [ Project ] :
        [ Character` } --> PROJECT [ Target ] = [ Target` }
        ( Project Character-prime outward into Target yielding Target-prime ),

    # ------------------------------------------------------------------------
    # ROLL 5: SEQUENCE TRANSITION (INSIDE-OUT EMERGENCE)
    # Yield Character` to text sequence prepared for interaction with Number
    # ------------------------------------------------------------------------
    [ ROLL 5 ] : [ Sequence ] :
        [ Character` } --> SEQUENCE [ Text ] = [ Text` ]
        ( Yield Character-prime to sequence prepared for number interaction )
]

# ============================================================================
# BLOCK 4: CLOSING BLOCK
# ============================================================================
Closing
    ( Sealing Gate: Validate, tripwire, debug, log, and affirm execution )
```

```
{
    # ------------------------------------------------------------------------
    # 1. VERIFICATION OF OPERATIONAL ROLLS
    # ------------------------------------------------------------------------
    [ Verify ]: [
        [ ROLL 1 ] = PROCEED ::
        [ ROLL 2 ] = PROCEED ::
        [ ROLL 3 ] = PROCEED ::
        [ ROLL 4 ] = PROCEED ::
        [ ROLL 5 ] = PROCEED
    ]
    ( Verify all five operational rolls achieved affirmative PROCEED ),

    # ------------------------------------------------------------------------
    # 2. VALIDATION OF INVARIANT BOUNDS & PARITY
    # ------------------------------------------------------------------------
    [ Validate ]:
        { Character` <= [ 1 Cell ] } & { [ 8 Bits ] <=> [ 5 Trits ] }
        & { Bit_7 = "0" }
        ( Validate single-cell enclosure, trit parity, and bit 7 invariance ),

    # ------------------------------------------------------------------------
    # 3. ZERO-TOLERANCE TRIPWIRING: BIT 7 COLLISION CIRCUIT BREAKER
    # ------------------------------------------------------------------------
    [ Tripwire ]:
        { Bit_7 != "0" } --> [ TRIPPED ]
            --> [ Commit Status = -1:ROLLBACK ]
        | { Status` = +1:PROCEED } --> [ ARMED ]
        ( Zero-tolerance tripwire trips on bit 7 violation or arms in Proceed ),

    # ------------------------------------------------------------------------
    # 4. DIAGNOSTIC DEBUG TELEMETRY
    # ------------------------------------------------------------------------
    [ Debug ]:
        { [ Glyph ] :: [ Character` ] :: [ Cell` ]
          :: [ Target` ] :: [ Status` ] }
        ( Expose telemetry across glyph, cell, target buffer, and status ),

    # ------------------------------------------------------------------------
    # 5. EPISODIC INVENTORY LOGGING
    # ------------------------------------------------------------------------
    [ Log ]: [ Journal ]:
        INSCRIBE { [ Character Inscribed ] :: [ Character` ] :: [ Target ] }
        ( Inscribe verified character transaction into permanent journal ),

    # ------------------------------------------------------------------------
    # 6. PERMANENT COVENANT EXECUTION & FOURFOLD COMMIT STATUS LOOP
    # ------------------------------------------------------------------------
    [ Commit Status ]: [
        # +1: PROCEED (+t: Advance forward along the causal tape)
        { [ Verify ] = PROCEED } & { [ Tripwire ] = ARMED }
            --> [ +1:PROCEED ] |

        #  0: AWAIT (t=t: Hold in equilibrium, pending resolution)
        { [ Target ] = BUSY } | { [ Status` ] = PENDING }
            --> [ 0:AWAIT ] :: REPEAT |

        # NULL: HALT (t=empty: Cessation of clock, absolute stop)
        { [ Status` ] = NULL } | { [ Interrupt ] = STOP }
            --> [ HALT:NULL ] |

        # -1: ROLLBACK (-t: Reverse causal tape to origin t=0)
        { [ Tripwire ] = TRIPPED } | { [ Verify ] != PROCEED }
            --> [ -1:ROLLBACK ]
    ]
    ( Fourfold state machine:
      Proceed advances, Await holds, Halt stops, Rollback reverts )
}

# ============================================================================
```

OmniCode: Chapter 12: Track 2 - Lexicon: Number Primitive Type

Dual-Rail Polar Planes, 32-Trit Word & Zero-Sum ALU

CHAPTER IDENTIFIER
CH 12

NOTEBOOKLM WORD COUNT
11,893 words

CATALOGED CHAPTER FILES
11 files (2,364 lines)

GENERATION DATE
2026-10-16 20:36:04

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"How does dual-rail balance enable O(1) rail-swap negation?"*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (11 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/README.md**	MD	135	840	5.8
2	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/interpreted/lua/number.lua**	LUA	347	1,746	15.0
3	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/interpreted/lua/tests/test_number.lua**	LUA	203	876	8.6
4	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/compiled/c/Makefile**	TEXT	18	36	0.4
5	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/compiled/c/compile_flags.txt**	TXT	7	6	0.1
6	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/compiled/c/test_number_bin**	TEXT	1	5	29.6
7	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/compiled/c/tests/test_number.c**	C	276	1,205	12.0
8	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/compiled/c/include/number.h**	H	413	1,949	14.9
9	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/compiled/c/src/number.c**	C	449	1,737	15.0
10	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/interpreted/number.tape**	TAPE	121	899	6.3
11	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/compiled/number.omni**	OMNI	394	2,594	21.0

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/README.md

MD | 135 LINES | 840 WORDS | 5.8 KB

```
# Invariant Type: < Number >

Welcome to the documentation for **Number**, the foundational scalar measurement and arithmetic invariant type in OmniCode!

---

## 1. What is a Number in OmniCode?

In conventional programming, a number is typically just a fixed binary sequence (like a 32-bit or 64-bit integer) that wraps around or overflows when limits are exceeded.

In **OmniCode**, a Number is an **Invariant Type**:

- It represents the **cosmic order of measure and quantity**.
- **Witness:**
  > *"He telleth the number of the stars; he calleth them all by their names."*
  > — **Psalm 147:4 KJV**
- **Semantics:** `{ ScalarQuantity :: DualRailBitPlane :: ZeroSumEquilibrium }`

### Footprint & Capacity Law

- **Defined Space:** Exactly **1 Machine Word**.
- **Dual Substrate:**
  - Physical Silicon Substrate: **64 Bits** (standard 64-bit microprocessor register, `int64_t` / `uint64_t`).
  - Virtual Balanced Substrate: **32 Balanced Trits** ($3^{32} \approx 1.85 \times 10^{15}$ symmetrical states centered at 0).
- **The Core ALU Zero-Sum Equilibrium Law:**
  $$(+1) + (-1) \iff 0$$
  Balance is not just an arithmetic result; it is the fundamental proof of correct execution.

---

## 2. Dual-Rail Polar Bit-Planes on Silicon

To run balanced ternary numbers at maximum speed on standard binary computers, OmniCode packs 32 trits into a native 64-bit integer using **Dual-Rail Bit-Planes**:

| 2-Bit Code | Rail Activation | Trit Value | Meaning |
| :---: | :--- | :---: | :--- |
| `00` | Neither rail active | `0` | **Equilibrium / True Zero** |
| `01` | Positive rail active (bit 0) | `+1` | **Positive Unity** |
| `10` | Negative rail active (bit 1) | `-1` | **Negative Unity** |
| `11` | Both rails active | `NULL` | **Collision Trap / Hardware Fault** |

### Why Dual-Rail is Revolutionary

1. **Instant SIMD Negation:** Negating all 32 trits in a 64-bit word requires no arithmetic addition or two's complement carry chains. It is performed instantaneously by swapping the positive and negative bit-planes in two CPU cycles!
2. **Built-in Safety Trap:** If memory ever corrupts or attempts an impossible simultaneous positive and negative state (`11`), the tripwire automatically trips and rolls back.

---

## 3. Dynamic Packing Topologies

A byte has 8 bits, which can hold balanced trits in different kinematic arrangements depending on how the number is used:

- **`2-2-2-2` (Pure Dense):** Four 2-bit trits per byte (standard compact storage).
- **`2-1-2-1-2` (Palindromic Balance):** Symmetric resting equilibrium with guard channels.
- **`1-2-1-2-2` (Prefix Carry):** Leaves a leading 1-bit channel for fast forward carry propagation.
- **`2-2-1-2-1` (Postfix Carry):** Leaves a trailing channel for reverse borrow propagation.
- **`3-3-2`, `3-2-3`, `2-3-3` (Directional Vectors):** Partitions bits to represent spatial 3D directions (X, Y, Z axes) directly inside a single byte.

---

## 4. Directory Layout & Three Pillars

Following the OmniCode standard, `number/` is structured into three pillars:

```bash
number/
```
```

```
├── README.md               # This architectural guide
├── compiled/               # Pillar 1: High-Level Source Reel
│   └── number.omni         # Canonical OmniCode source code
├── interpreted/            # Pillar 2: Process Ribbon
│   └── number.tape         # Five-roll interpreted execution tape
└── transpiled/             # Pillar 3: Physical Bridges
    ├── compiled/c/         # Freestanding C99/C11 Hardware Backbone
    │   ├── Makefile        # Pure POSIX build script
    │   ├── compile_flags.txt
    │   ├── include/
    │   │   └── number.h    # omni_number_t, topologies, and dual-rail API
    │   ├── src/
    │   │   └── number.c    # Balanced ternary ALU, addition, negation, packing
    │   └── tests/
    │       └── test_number.c # Freestanding C unit test suite
    └── interpreted/lua/    # Dynamic Coroutine Process Ribbon
        ├── number.lua      # Lua tape implementation driven by TapeEngine
        └── tests/
            └── test_number.lua # Lua unit test suite
```

---

5. The 5-Roll Lifecycle

Both `number.tape` (interpreted) and `number.c` (compiled) execute the Number lifecycle in **5 sequential rolls**:

1. **Inscribe:** Takes a raw quantity (e.g. 4096) and encloses it safely inside the 1-word boundary.
2. **Transduce:** Converts the 64-bit integer into 32 balanced trits and packs them into dual-rail bit-planes.
3. **Compare:** Guards the word boundary and confirms that no `11` collision traps exist.
4. **Equilibrium:** Proves the algebraic Zero-Sum law $(+1) + (-1) = 0$ and confirms that double negation restores the exact original value $(-(-X) == X)$.
5. **Sequence:** Commits the number and prepares it to link smoothly into higher-level vectors and arrays.

---

6. How Number Inherits from Universal (`ladder.baton`)

Notice that `number/` contains **no duplicate universal files**.

It inherits the universal foundation cleanly:

- **In C:** `number.h` includes `"omni_base.h"`. The `Makefile` uses `-I../../../../universal/transpiled/compiled/c/include`.
- **In Lua:** `number.lua` loads `tape_engine.lua` from `universal/transpiled/interpreted/lua/`.

---

7. Running Number Tests

You can test Number across both C and Lua environments:

```bash
# Run the C unit tests
cd transpiled/compiled/c
make test

# Run the Lua unit tests
cd ../../interpreted/lua
lua tests/test_number.lua
```

Both test suites confirm:

- Radix-3 balanced ternary conversion and reconstruction
- Dual-rail bit-plane encoding, decoding, and collision detection
- SIMD rail-swap negation involution: `-(-X) == X`
- Dynamic packing and unpacking across all 7 topologies
- The ALU Zero-Sum Equilibrium Law: `(+1) + (-1) <=> 0`
- Safe execution through all 5 lifecycle rolls

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/interpreted/lua/number.lua

LUA | 347 LINES | 1746 WORDS | 15.0 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & PROCESS TAPE MANIFEST
-- ( Process Tape: < Lexicon { Types of Ideas } > & [ Process { Number } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Interprets and executes the atomic lifecycle for Invariant Type < Number >.
--   Acts as dynamic runtime companion driving C backbone `omni_number_t`.
--   - Dual-Rail Polar Bit-Planes: 00=0 (Equilibrium), 01=+1, 10=-1, 11=Trap
--   - Directional Partitions: 3-3-2, 3-2-3, 2-3-3 (3-space minimum for Z)
--   - Witness: Scripture Psalm 147:4 KJV
--     "He telleth the number of the stars; he calleth them all by their names."
--   - Semantics: { DualRailBitPlanes :: KinematicTopologies :: ZeroSumALU }
-- ================================================================================

local ok_te, TapeEngine = pcall(require, "tape_engine")
if not ok_te then
    package.path = package.path ..
        ";../../../../universal/transpiled/interpreted/lua/?.lua"
    TapeEngine = require("tape_engine")
end

local CONSTANTS = {
    WORD_CAPACITY       = 1,
    TRITS_PER_WORD      = 32,
    BITS_PER_WORD       = 64,
    EXEMPLAR_ZERO       = 0,
    EXEMPLAR_UNITY_POS  = 1,
    EXEMPLAR_UNITY_NEG  = -1,
    EXEMPLAR_PARTITION  = 4096,
    BITPLANE_POS_MASK   = 0x5555555555555555,
    BITPLANE_NEG_MASK   = ~0x5555555555555555,
    TRIT_CODE_ZERO      = 0, -- 0b00: Equilibrium / 0
    TRIT_CODE_POS       = 1, -- 0b01: Positive / +1
    TRIT_CODE_NEG       = 2, -- 0b10: Negative / -1
    TRIT_CODE_NULL      = 3  -- 0b11: Collision / NULL trap
}

local PACK_MODES = {
    DENSE_2222        = 0, -- 2-2-2-2: Standard dense storage (4 trits)
    KINEMATIC_21212   = 1, -- 2-1-2-1-2: Symmetric resting equilibrium
    KINEMATIC_12122   = 2, -- 1-2-1-2-2: Prefix carry/overflow channel
    KINEMATIC_22121   = 3, -- 2-2-1-2-1: Postfix carry/overflow channel
    DIRECTIONAL_332   = 4, -- 3-3-2: Directional vector (X:3, Y:3, Z:2)
    DIRECTIONAL_323   = 5, -- 3-2-3: Directional vector (X:3, Y:2, Z:3)
    DIRECTIONAL_233   = 6  -- 2-3-3: Directional vector (X:2, Y:3, Z:3)
}

local function trit_to_2bit(trit)
    if trit == 0 then return CONSTANTS.TRIT_CODE_ZERO
    elseif trit == 1 then return CONSTANTS.TRIT_CODE_POS
    elseif trit == -1 then return CONSTANTS.TRIT_CODE_NEG
    else return CONSTANTS.TRIT_CODE_NULL end
end

local function two_bit_to_trit(code)
    if code == CONSTANTS.TRIT_CODE_ZERO then return 0, true
    elseif code == CONSTANTS.TRIT_CODE_POS then return 1, true
    elseif code == CONSTANTS.TRIT_CODE_NEG then return -1, true
    else return 0, false end -- NULL collision
end

local function pack_trits_dual_rail(trits)
    local packed = 0
    for i = 1, CONSTANTS.TRITS_PER_WORD do
        local t = trits[i] or 0
        local code = trit_to_2bit(t)
        packed = packed | ((code & 0x03) << ((i - 1) * 2))
    end
    return packed
end

local function unpack_trits_dual_rail(packed, out_trits)
    for i = 1, CONSTANTS.TRITS_PER_WORD do
```

```
        local code = (packed >> ((i - 1) * 2)) & 0x03
        local trit, ok = two_bit_to_trit(code)
        if not ok then return false end
        out_trits[i] = trit
    end
    return true
end

local function negate_dual_rail(packed)
    local pos_rails = packed & CONSTANTS.BITPLANE_POS_MASK
    local neg_rails = packed & CONSTANTS.BITPLANE_NEG_MASK
    return ((pos_rails << 1) & CONSTANTS.BITPLANE_NEG_MASK) |
           ((neg_rails >> 1) & CONSTANTS.BITPLANE_POS_MASK)
end

local function has_null_collision(packed)
    local pos_rails = packed & CONSTANTS.BITPLANE_POS_MASK
    local neg_rails = (packed >> 1) & CONSTANTS.BITPLANE_POS_MASK
    return (pos_rails & neg_rails) ~= 0
end

local function pack_byte(trits, mode)
    mode = mode or PACK_MODES.DENSE_2222
    local b = 0
    if mode == PACK_MODES.DENSE_2222 then
        for i = 1, 4 do
            local code = trit_to_2bit(trits[i] or 0)
            b = b | ((code & 0x03) << ((i - 1) * 2))
        end
    elseif mode == PACK_MODES.KINEMATIC_21212 then
        b = b | (trit_to_2bit(trits[1] or 0) & 0x03)
        b = b | ((trit_to_2bit(trits[2] or 0) & 0x01) << 2)
        b = b | ((trit_to_2bit(trits[2] or 0) & 0x03) << 3)
        b = b | (((trit_to_2bit(trits[2] or 0) >> 1) & 0x01) << 5)
        b = b | ((trit_to_2bit(trits[3] or 0) & 0x03) << 6)
    elseif mode == PACK_MODES.KINEMATIC_12122 then
        b = b | ((trit_to_2bit(trits[1] or 0) & 0x01) << 0)
        b = b | ((trit_to_2bit(trits[1] or 0) & 0x03) << 1)
        b = b | (((trit_to_2bit(trits[2] or 0) >> 1) & 0x01) << 3)
        b = b | ((trit_to_2bit(trits[2] or 0) & 0x03) << 4)
        b = b | ((trit_to_2bit(trits[3] or 0) & 0x03) << 6)
    elseif mode == PACK_MODES.KINEMATIC_22121 then
        b = b | ((trit_to_2bit(trits[1] or 0) & 0x03) << 0)
        b = b | ((trit_to_2bit(trits[2] or 0) & 0x03) << 2)
        b = b | ((trit_to_2bit(trits[3] or 0) & 0x01) << 4)
        b = b | ((trit_to_2bit(trits[3] or 0) & 0x03) << 5)
        b = b | (((trit_to_2bit(trits[3] or 0) >> 1) & 0x01) << 7)
    elseif mode == PACK_MODES.DIRECTIONAL_332 then
        local c1 = trit_to_2bit(trits[1] or 0) & 0x03
        local c2 = trit_to_2bit(trits[2] or 0) & 0x03
        local c3 = trit_to_2bit(trits[3] or 0) & 0x03
        b = b | (c1 << 0) | (c2 << 3) | (c3 << 6)
    elseif mode == PACK_MODES.DIRECTIONAL_323 then
        local c1 = trit_to_2bit(trits[1] or 0) & 0x03
        local c2 = trit_to_2bit(trits[2] or 0) & 0x03
        local c3 = trit_to_2bit(trits[3] or 0) & 0x03
        b = b | (c1 << 0) | (c2 << 3) | (c3 << 5)
    elseif mode == PACK_MODES.DIRECTIONAL_233 then
        local c1 = trit_to_2bit(trits[1] or 0) & 0x03
        local c2 = trit_to_2bit(trits[2] or 0) & 0x03
        local c3 = trit_to_2bit(trits[3] or 0) & 0x03
        b = b | (c1 << 0) | (c2 << 2) | (c3 << 5)
    end
    return b & 0xFF
end

local function unpack_byte(byte_val, mode, out_trits)
    mode = mode or PACK_MODES.DENSE_2222
    if mode == PACK_MODES.DENSE_2222 then
        for i = 1, 4 do
            local code = (byte_val >> ((i - 1) * 2)) & 0x03
            local t, ok = two_bit_to_trit(code)
            if not ok then return false end
            out_trits[i] = t
        end
    elseif mode == PACK_MODES.KINEMATIC_21212 then
        local t1, ok1 = two_bit_to_trit(byte_val & 0x03)
        local t2, ok2 = two_bit_to_trit((byte_val >> 3) & 0x03)
```

```
        local t3, ok3 = two_bit_to_trit((byte_val >> 6) & 0x03)
        if not (ok1 and ok2 and ok3) then return false end
        out_trits[1], out_trits[2], out_trits[3], out_trits[4] = t1, t2, t3, 0
    elseif mode == PACK_MODES.KINEMATIC_12122 then
        local t1, ok1 = two_bit_to_trit((byte_val >> 1) & 0x03)
        local t2, ok2 = two_bit_to_trit((byte_val >> 4) & 0x03)
        local t3, ok3 = two_bit_to_trit((byte_val >> 6) & 0x03)
        if not (ok1 and ok2 and ok3) then return false end
        out_trits[1], out_trits[2], out_trits[3], out_trits[4] = t1, t2, t3, 0
    elseif mode == PACK_MODES.KINEMATIC_22121 then
        local t1, ok1 = two_bit_to_trit((byte_val >> 0) & 0x03)
        local t2, ok2 = two_bit_to_trit((byte_val >> 2) & 0x03)
        local t3, ok3 = two_bit_to_trit((byte_val >> 5) & 0x03)
        if not (ok1 and ok2 and ok3) then return false end
        out_trits[1], out_trits[2], out_trits[3], out_trits[4] = t1, t2, t3, 0
    elseif mode == PACK_MODES.DIRECTIONAL_332 then
        local t1, ok1 = two_bit_to_trit((byte_val >> 0) & 0x03)
        local t2, ok2 = two_bit_to_trit((byte_val >> 3) & 0x03)
        local t3, ok3 = two_bit_to_trit((byte_val >> 6) & 0x03)
        if not (ok1 and ok2 and ok3) then return false end
        out_trits[1], out_trits[2], out_trits[3], out_trits[4] = t1, t2, t3, 0
    elseif mode == PACK_MODES.DIRECTIONAL_323 then
        local t1, ok1 = two_bit_to_trit((byte_val >> 0) & 0x03)
        local t2, ok2 = two_bit_to_trit((byte_val >> 3) & 0x03)
        local t3, ok3 = two_bit_to_trit((byte_val >> 5) & 0x03)
        if not (ok1 and ok2 and ok3) then return false end
        out_trits[1], out_trits[2], out_trits[3], out_trits[4] = t1, t2, t3, 0
    elseif mode == PACK_MODES.DIRECTIONAL_233 then
        local t1, ok1 = two_bit_to_trit((byte_val >> 0) & 0x03)
        local t2, ok2 = two_bit_to_trit((byte_val >> 2) & 0x03)
        local t3, ok3 = two_bit_to_trit((byte_val >> 5) & 0x03)
        if not (ok1 and ok2 and ok3) then return false end
        out_trits[1], out_trits[2], out_trits[3], out_trits[4] = t1, t2, t3, 0
    end
    return true
end

local NumberTape = TapeEngine.create_tape({
    metadata = {
        who     = "OmniCode Lexicon",
        what    = "Number --> MEASURE { Quantity }",
        when    = "Arithmetic Event",
        where   = { number_word = 1 },
        why     = "Inscribe scalar number invariant and arithmetic equilibrium",
        how     = "+1 : PROCEED",
        witness = "Psalm 147:4 KJV"
    },
    constants = CONSTANTS,
    pack_modes = PACK_MODES,
    rolls = {
        -- ------------------------------------------------------------------
        -- ROLL 1: QUANTITY INSCRIPTION (Outside-in imposition onto C word)
        -- ------------------------------------------------------------------
        {
            name = "Inscribe",
            action = function(ctx)
                ctx.c_word.scalar = ctx.quantity
                ctx.c_word.is_enclosed = true
                ctx.c_word.pack_mode = ctx.pack_mode or PACK_MODES.DENSE_2222
                return TapeEngine.STATE_PROCEED
            end
        },

        -- ------------------------------------------------------------------
        -- ROLL 2: DUAL-SUBSTRATE TRANSDUCTION (64 Bits <=> 32 Balanced Trits)
        -- ------------------------------------------------------------------
        {
            name = "Transduce",
            action = function(ctx)
                local current = ctx.c_word.scalar
                for i = 1, CONSTANTS.TRITS_PER_WORD do
                    if current == 0 then
                        ctx.c_word.trits[i] = 0
                    else
                        local rem = current % 3
                        current = math.floor(current / 3)
                        if rem == 2 then
                            rem = -1
```

```
                            current = current + 1
                        elseif rem == -2 then
                            rem = 1
                            current = current - 1
                        end
                        ctx.c_word.trits[i] = rem
                    end
                end
                -- Inscribe dual-rail bit-planes (64 bits native)
                local p = pack_trits_dual_rail(ctx.c_word.trits)
                ctx.c_word.packed_dual_rail = p
                return TapeEngine.STATE_PROCEED
            end
        },

        -- ------------------------------------------------------------------
        -- ROLL 3: IDENTITY & BOUND COMPARISON (Guard Single-Word Boundary)
        -- ------------------------------------------------------------------
        {
            name = "Compare",
            action = function(ctx)
                local identity_ok = (ctx.c_word.scalar == ctx.quantity)
                local bounds_ok   = (ctx.c_word.is_enclosed == true)
                local p = ctx.c_word.packed_dual_rail
                local no_null     = not has_null_collision(p)
                local roundtrip   = {}
                local unpack_ok   = unpack_trits_dual_rail(p, roundtrip)
                return TapeEngine.assert_guard(identity_ok and bounds_ok and
                                               no_null and unpack_ok, ctx,
                                               "Number bound or collision")
            end
        },

        -- ------------------------------------------------------------------
        -- ROLL 4: ARITHMETIC EQUILIBRIUM CALCULATION ((+1) plus (-1) <=> 0)
        -- ------------------------------------------------------------------
        {
            name = "Equilibrium",
            action = function(ctx)
                local eq = (1) + (-1)
                local eq_holds = (eq == 0)
                -- Prove SIMD rail-swap involution: -(-x) == x
                local neg = negate_dual_rail(ctx.c_word.packed_dual_rail)
                local neg_neg = negate_dual_rail(neg)
                local rail_involution = (neg_neg == ctx.c_word.packed_dual_rail)
                ctx.equilibrium_proved = eq_holds and rail_involution
                return TapeEngine.assert_guard(ctx.equilibrium_proved, ctx,
                                               "ALU Equilibrium Law violated")
            end
        },

        -- ------------------------------------------------------------------
        -- ROLL 5: SEQUENCE TRANSITION (Number chains toward Vector sequence)
        -- ------------------------------------------------------------------
        {
            name = "Sequence",
            action = function(ctx)
                ctx.vector_ready = true
                return TapeEngine.STATE_PROCEED
            end
        }
    }
})

-- Expose bit-plane and kinematic packing primitives
NumberTape.PACK_MODES             = PACK_MODES
NumberTape.trit_to_2bit           = trit_to_2bit
NumberTape.two_bit_to_trit        = two_bit_to_trit
NumberTape.pack_trits_dual_rail   = pack_trits_dual_rail
NumberTape.unpack_trits_dual_rail = unpack_trits_dual_rail
NumberTape.negate_dual_rail       = negate_dual_rail
NumberTape.has_null_collision     = has_null_collision
NumberTape.pack_byte              = pack_byte
NumberTape.unpack_byte            = unpack_byte

-- ============================================================================
-- BLOCK 2: OPENING BLOCK
-- ( Context Factory & C Word Substrate Mount )
```

```lua
-- ============================================================================

---
-- Mounts the tape head, initialises the C word handle, and arms the tripwire.
-- @param quantity Outside-in scalar integer (defaults to 4096).
-- @param pack_mode Kinematic packing mode (defaults to DENSE_2222).
-- @return Initialized context table.
function NumberTape.open(quantity, pack_mode)
    local p_mode = pack_mode or PACK_MODES.DENSE_2222
    return {
        quantity           = quantity or CONSTANTS.EXEMPLAR_PARTITION,
        pack_mode          = p_mode,
        c_word             = {
            scalar           = 0,
            trits            = {},
            packed_dual_rail = 0,
            pack_mode        = p_mode,
            is_enclosed      = false
        },
        equilibrium_proved = false,
        status             = TapeEngine.STATE_PROCEED,
        tripwire           = TapeEngine.TRIPWIRE_ARMED
    }
end

-- ============================================================================
-- BLOCK 4: CLOSING BLOCK
-- ( Fourfold Detent Commit & Interlock Verification )
-- ============================================================================

---
-- Closes and seals the Number tape execution context.
-- @param ctx Active context handle.
-- @return Quad-State commit status and diagnostic seal message.
function NumberTape.close(ctx)
    return TapeEngine.verify_and_commit(ctx)
end

return NumberTape
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/interpreted/lua/tests/test_number.lua

LUA | 203 LINES | 876 WORDS | 8.6 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & TEST TOPOLOGY
-- ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { Number Tape } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Validates the interpreted process ribbon < Number Tape > in isolation:
--   - Radix-3 balanced ternary transduction (64 bits <=> 32 balanced trits)
--   - Dual-rail polar bit-planes: 00=0 (Equilibrium), 01=+1, 10=-1, 11=Trap
--   - SIMD rail-swap negation: -(-X) == X via bit-plane swap
--   - Collision detection: NULL code (11) trips safety interlock
--   - Dynamic packing topologies: 2-2-2-2, 2-1-2-1-2, 1-2-1-2-2, 2-2-1-2-1,
--     3-3-2, 3-2-3, 2-3-3
--   - Core ALU Zero-Sum Equilibrium Law: (+1) plus (-1) <=> 0
--   - Single-word boundary laws & 4-block lifecycle execution
--   - Witness: Scripture Psalm 147:4 KJV
--     "He telleth the number of the stars; he calleth them all by their names."
--   - Semantics: { DualRailPlanes :: KinematicTopologies :: ZeroSumBalance }
-- ================================================================================

local script_dir = debug.getinfo(1, "S").source:match("@?(.*[/\\])") or "./"
local u_dir = script_dir ..
    "../../../../../universal/transpiled/interpreted/lua/"
package.path = script_dir .. "?.lua;" ..
               script_dir .. "../?.lua;" ..
               u_dir .. "?.lua;" ..
               u_dir .. "tests/?.lua;" ..
               package.path

local TestCommon = require("test_common")
local TapeEngine = require("tape_engine")
local NumberTape = require("number")

local Suite = {}

function Suite.test_number_dual_rail_bitplanes()
    -- 1. Test 2-bit codes: 00=0, 01=+1, 10=-1, 11=trap
    TestCommon.assert_eq(NumberTape.trit_to_2bit(0), 0, "0 must map to 0b00")
    TestCommon.assert_eq(NumberTape.trit_to_2bit(1), 1, "1 must map to 0b01")
    TestCommon.assert_eq(NumberTape.trit_to_2bit(-1), 2, "-1 must map to 0b10")

    local t0, ok0 = NumberTape.two_bit_to_trit(0)
    TestCommon.assert(ok0 and t0 == 0, "0b00 must decode to 0")
    local t1, ok1 = NumberTape.two_bit_to_trit(1)
    TestCommon.assert(ok1 and t1 == 1, "0b01 must decode to +1")
    local t2, ok2 = NumberTape.two_bit_to_trit(2)
    TestCommon.assert(ok2 and t2 == -1, "0b10 must decode to -1")
    local _, ok3 = NumberTape.two_bit_to_trit(3)
    TestCommon.assert(not ok3, "0b11 must report collision / NULL trap")

    -- 2. Test dual-rail packing and unpacking
    local trits = {}
    for i = 1, 32 do
        if i % 3 == 1 then trits[i] = 1
        elseif i % 3 == 2 then trits[i] = -1
        else trits[i] = 0 end
    end
    local packed = NumberTape.pack_trits_dual_rail(trits)
    local unpacked = {}
    local ok = NumberTape.unpack_trits_dual_rail(packed, unpacked)
    TestCommon.assert(ok, "Unpack must succeed on valid trits")
    for i = 1, 32 do
        TestCommon.assert_eq(unpacked[i], trits[i],
                             "Unpacked trit must match original at " .. i)
    end
end

function Suite.test_number_simd_rail_swap_negation()
    local trits = {}
    for i = 1, 32 do
        if i % 3 == 1 then trits[i] = 1
        elseif i % 3 == 2 then trits[i] = -1
        else trits[i] = 0 end
    end
```

```
    local packed = NumberTape.pack_trits_dual_rail(trits)
    local negated = NumberTape.negate_dual_rail(packed)

    local unpacked_neg = {}
    local ok = NumberTape.unpack_trits_dual_rail(negated, unpacked_neg)
    TestCommon.assert(ok, "Unpack negated trits must succeed")
    for i = 1, 32 do
        TestCommon.assert_eq(unpacked_neg[i], -trits[i],
                             "Negated trit must invert sign at " .. i)
    end

    -- Involution: -(-X) == X
    local double_neg = NumberTape.negate_dual_rail(negated)
    TestCommon.assert_eq(double_neg, packed,
                         "Double rail-swap negation must restore original")
end

function Suite.test_number_null_collision_trap()
    -- Valid packed trits have no null collision
    local trits = { 1, -1, 0, 1 }
    local packed = NumberTape.pack_trits_dual_rail(trits)
    TestCommon.assert(not NumberTape.has_null_collision(packed),
                      "Valid trits must not trigger null collision")

    -- Manually inject 11 (code 3) into trit slot 0
    local corrupted = packed | 3
    TestCommon.assert(NumberTape.has_null_collision(corrupted),
                      "Corrupted dual-rail must detect null collision")

    local unpacked = {}
    local ok = NumberTape.unpack_trits_dual_rail(corrupted, unpacked)
    TestCommon.assert(not ok, "Unpacking corrupted dual-rail must fail")
end

function Suite.test_number_dynamic_packing_topologies()
    local modes = {
        NumberTape.PACK_MODES.DENSE_2222,
        NumberTape.PACK_MODES.KINEMATIC_21212,
        NumberTape.PACK_MODES.KINEMATIC_12122,
        NumberTape.PACK_MODES.KINEMATIC_22121,
        NumberTape.PACK_MODES.DIRECTIONAL_332,
        NumberTape.PACK_MODES.DIRECTIONAL_323,
        NumberTape.PACK_MODES.DIRECTIONAL_233
    }
    local test_trits = { 1, -1, 1, -1 }

    for _, mode in ipairs(modes) do
        local byte_val = NumberTape.pack_byte(test_trits, mode)
        local out_trits = {}
        local ok = NumberTape.unpack_byte(byte_val, mode, out_trits)
        TestCommon.assert(ok, "Unpack byte must succeed for mode " .. mode)
        -- Verify first 3 trits match in kinematic / directional modes
        TestCommon.assert_eq(out_trits[1], test_trits[1], "Trit 1 must match")
        TestCommon.assert_eq(out_trits[2], test_trits[2], "Trit 2 must match")
        TestCommon.assert_eq(out_trits[3], test_trits[3], "Trit 3 must match")
        if mode == NumberTape.PACK_MODES.DENSE_2222 then
            TestCommon.assert_eq(out_trits[4], test_trits[4],
                                 "Trit 4 must match in dense mode")
        end
    end
end

function Suite.test_number_transduction()
    local values = { 0, 1, -1, 4096, -4096, 65536 }
    for _, val in ipairs(values) do
        local ctx = NumberTape.open(val)
        local status = NumberTape:execute_all(ctx)
        TestCommon.assert_eq(status, TapeEngine.STATE_PROCEED,
                             "Execution must PROCEED (+1)")
        TestCommon.assert_eq(ctx.c_word.scalar, val,
                             "Context word scalar must match input")
        TestCommon.assert(ctx.c_word.is_enclosed == true,
                          "Context word must be enclosed")
        TestCommon.assert_eq(ctx.equilibrium_proved, true,
                             "ALU Zero-Sum Equilibrium must be proved")
    end
end

```

```
function Suite.test_number_equilibrium_law()
    -- Direct law verification: (+1) + (-1) == 0
    local sum = (1) + (-1)
    TestCommon.assert_eq(sum, 0,
                         "ALU Zero-Sum Equilibrium Law must evaluate to zero")
end

function Suite.test_number_lifecycle_rolls()
    local ctx = NumberTape.open(4096)
    TestCommon.assert_eq(ctx.tripwire, TapeEngine.TRIPWIRE_ARMED,
                         "Tripwire must be ARMED on open")

    local status = NumberTape:execute_all(ctx)
    TestCommon.assert_eq(status, TapeEngine.STATE_PROCEED,
                         "Execution must PROCEED")

    local close_st = NumberTape.close(ctx)
    TestCommon.assert_eq(close_st, TapeEngine.STATE_PROCEED,
                         "Close must seal in PROCEED (+1)")
    TestCommon.assert_eq(ctx.tripwire, TapeEngine.TRIPWIRE_DISARMED,
                         "Tripwire must be DISARMED on close")
end

function Suite.run()
    print("[SUITE: Number Process Ribbon (Lua)]")
    local ok1 = TestCommon.run_test("Dual-Rail Polar Bit-Planes",
                                    Suite.test_number_dual_rail_bitplanes)
    local ok2 = TestCommon.run_test("SIMD Rail-Swap Negation",
                                    Suite.test_number_simd_rail_swap_negation)
    local ok3 = TestCommon.run_test("NULL Collision Trap",
                                    Suite.test_number_null_collision_trap)
    local ok4 = TestCommon.run_test(
        "Dynamic Packing Topologies",
        Suite.test_number_dynamic_packing_topologies
    )
    local ok5 = TestCommon.run_test("Radix-3 Balanced Transduction",
                                    Suite.test_number_transduction)
    local ok6 = TestCommon.run_test("ALU Zero-Sum Equilibrium Law",
                                    Suite.test_number_equilibrium_law)
    local ok7 = TestCommon.run_test("4-Block Lifecycle Rolls",
                                    Suite.test_number_lifecycle_rolls)
    return ok1 and ok2 and ok3 and ok4 and ok5 and ok6 and ok7
end

-- Allow standalone execution
if pcall(debug.getlocal, 4, 1) == false then
    local ok = Suite.run()
    os.exit(ok and 0 or 1)
end

return Suite
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/compiled/c/Makefile

TEXT | 18 LINES | 36 WORDS | 0.4 KB

```
CC ?= gcc
CFLAGS ?= -Wall -Wextra -std=c11 -Iinclude \
          -I../../../../universal/transpiled/compiled/c/include \
          -I../../../../universal/transpiled/compiled/c/tests

all: test

test: test_number_bin
    ./test_number_bin

test_number_bin: src/number.c tests/test_number.c include/number.h
    $(CC) $(CFLAGS) src/number.c tests/test_number.c -o $@

clean:
    rm -f test_number_bin

.PHONY: all test clean
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/compiled/c/compile_flags.txt

TXT | 7 LINES | 6 WORDS | 0.1 KB

```
-Iinclude
-I../../../../universal/transpiled/compiled/c/include
-I../../../../universal/transpiled/compiled/c/tests
-Wall
-Wextra
-std=c11
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/compiled/c/test_number_bin DOC/BINARY 1 LINES 5 WORDS 29.6 KB

[Binary Artifact: test_number_bin (29.6 KB)]

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/compiled/c/tests/test_number.c

C | 276 LINES | 1205 WORDS | 12.0 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & TEST TOPOLOGY
 * ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { Number } ] )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Validates the scalar invariant type < Number > in isolation:
 *   - Bijective round-trip radix-3 transduction (64 bits <=> 32 balanced trits)
 *   - Dual-rail bit-plane packed representation and O(1) rail-swap negation
 *   - Instant O(1) NULL collision trap detection
 *   - Dynamic packing topologies: 2-2-2-2, 2-1-2-1-2, 1-2-1-2-2, 2-2-1-2-1,
 *     3-3-2, 3-2-3, 2-3-3
 *   - ALU Zero-Sum Equilibrium Law: (+1) plus (-1) <=> 0
 *   - Balanced arithmetic addition, subtraction, and inverse cancellation
 *   - Strict single-word boundary laws
 *   - Full 4-block lifecycle execution (open, execute, close)
 *   - Witness: Scripture Psalm 147:4 KJV
 *     "He telleth the number of the stars; he calleth them all by their names."
 *   - Semantics: { DualRailBitPlanes :: KinematicTopologies :: ALUZeroSum }
 * ============================================================================ */

#include "number.h"
#include "test_common.h"

/* ============================================================================
 * BLOCK 2: OPENING CONTEXT & FIXTURE SETUP
 * ============================================================================ */

static int test_number_bijective_roundtrip(void) {
    const int64_t test_values[] = {
        0, 1, -1, 2, -2, 4096, -4096, 65536, -65536, 1000000, -1000000
    };
    const size_t num_values = sizeof(test_values) / sizeof(test_values[0]);

    for (size_t i = 0; i < num_values; ++i) {
        int64_t original = test_values[i];
        omni_number_t n = omni_number_from_scalar(original);

        OMNI_TEST_ASSERT(n.is_enclosed == true, "Number must be enclosed");
        OMNI_TEST_ASSERT(n.scalar == original,
                         "Number scalar must match original");

        /* Verify all 32 trits are in {-1, 0, +1} */
        for (size_t t = 0; t < OMNI_NUM_TRITS_PER_WORD; ++t) {
            OMNI_TEST_ASSERT(n.trits[t] >= -1 && n.trits[t] <= 1,
                             "Trit must be in {-1, 0, +1}");
        }

        /* Verify reconstruction from trits */
        int64_t reconstructed = omni_number_to_scalar(n.trits);
        OMNI_TEST_ASSERT(reconstructed == original,
                         "Reconstructed scalar must equal original value");
    }
    return 0;
}

static int test_number_dual_rail_bitplanes(void) {
    /* Test Zero: All trits 00 -> packed is 0 */
    omni_number_t zero = omni_number_from_scalar(0);
    OMNI_TEST_ASSERT(
        omni_number_trits_is_equilibrium(zero.packed_trits) == true,
                     "Packed zero must be in equilibrium (0ULL)");
    OMNI_TEST_ASSERT(omni_number_trits_has_null(zero.packed_trits) == false,
                     "Packed zero must not have NULL traps");

    /* Test Positive Unity (+1): First trit is 01, others 00 */
    omni_number_t pos_one = omni_number_from_scalar(1);
    OMNI_TEST_ASSERT((pos_one.packed_trits & 0x03) == OMNI_TRIT_PAIR_POS,
                     "First trit of +1 must be 01 (positive rail active)");

    /* Test Negative Unity (-1): First trit is 10, others 00 */
    omni_number_t neg_one = omni_number_from_scalar(-1);
    OMNI_TEST_ASSERT((neg_one.packed_trits & 0x03) == OMNI_TRIT_PAIR_NEG,
                     "First trit of -1 must be 10 (negative rail active)");
```

```
    /* Test Instant Bit-Plane Negation (+1 <-> -1) */
    uint64_t negated_pos = omni_number_trits_negate(pos_one.packed_trits);
    OMNI_TEST_ASSERT((negated_pos & 0x03) == OMNI_TRIT_PAIR_NEG,
                     "Negating +1 packed trits must produce -1 (10)");
    OMNI_TEST_ASSERT(negated_pos == neg_one.packed_trits,
                     "Negated +1 packed word must equal -1 packed word");

    /* Test NULL Trap Detection: artificially inject 11 into trit 0 */
    uint64_t corrupted = pos_one.packed_trits | 0x03;
    OMNI_TEST_ASSERT(omni_number_trits_has_null(corrupted) == true,
                     "Packed word with 11 must be flagged as NULL trap");

    return 0;
}

static int test_number_dynamic_packing_topologies(void) {
    uint8_t out[5];

    /* 1. Test 2-2-2-2 (Dense: 4 fields of 2 bits) */
    uint8_t p_2222 = omni_number_pack_byte(1, 2, 0, 3, 0, OMNI_PACK_2_2_2_2);
    omni_number_unpack_byte(p_2222, out, OMNI_PACK_2_2_2_2);
    OMNI_TEST_ASSERT(out[0] == 1 && out[1] == 2 && out[2] == 0 && out[3] == 3,
                     "2-2-2-2 round-trip unpack must match input");

    /* 2. Test 2-1-2-1-2 (Palindromic Equilibrium: 00/0/00/0/00) */
    uint8_t p_pal = omni_number_pack_byte(3, 1, 2, 0, 1, OMNI_PACK_2_1_2_1_2);
    omni_number_unpack_byte(p_pal, out, OMNI_PACK_2_1_2_1_2);
    OMNI_TEST_ASSERT(out[0] == 3 && out[1] == 1 && out[2] == 2 &&
                     out[3] == 0 && out[4] == 1,
                     "2-1-2-1-2 round-trip unpack must match input");

    /* 3. Test 1-2-1-2-2 (Prefix Carry) */
    uint8_t p_pre = omni_number_pack_byte(1, 3, 0, 2, 1, OMNI_PACK_1_2_1_2_2);
    omni_number_unpack_byte(p_pre, out, OMNI_PACK_1_2_1_2_2);
    OMNI_TEST_ASSERT(out[0] == 1 && out[1] == 3 && out[2] == 0 &&
                     out[3] == 2 && out[4] == 1,
                     "1-2-1-2-2 round-trip unpack must match input");

    /* 4. Test 2-2-1-2-1 (Postfix Carry) */
    uint8_t p_post = omni_number_pack_byte(2, 1, 1, 3, 0, OMNI_PACK_2_2_1_2_1);
    omni_number_unpack_byte(p_post, out, OMNI_PACK_2_2_1_2_1);
    OMNI_TEST_ASSERT(out[0] == 2 && out[1] == 1 && out[2] == 1 &&
                     out[3] == 3 && out[4] == 0,
                     "2-2-1-2-1 round-trip unpack must match input");

    /* 5. Test 3-3-2 (3-Space Directional Partition) */
    uint8_t p_332 = omni_number_pack_byte(7, 5, 2, 0, 0, OMNI_PACK_3_3_2);
    omni_number_unpack_byte(p_332, out, OMNI_PACK_3_3_2);
    OMNI_TEST_ASSERT(out[0] == 7 && out[1] == 5 && out[2] == 2,
                     "3-3-2 round-trip unpack must match input");

    /* 6. Test 3-2-3 (3-Space Directional Partition) */
    uint8_t p_323 = omni_number_pack_byte(6, 3, 5, 0, 0, OMNI_PACK_3_2_3);
    omni_number_unpack_byte(p_323, out, OMNI_PACK_3_2_3);
    OMNI_TEST_ASSERT(out[0] == 6 && out[1] == 3 && out[2] == 5,
                     "3-2-3 round-trip unpack must match input");

    /* 7. Test 2-3-3 (3-Space Directional Partition) */
    uint8_t p_233 = omni_number_pack_byte(3, 7, 4, 0, 0, OMNI_PACK_2_3_3);
    omni_number_unpack_byte(p_233, out, OMNI_PACK_2_3_3);
    OMNI_TEST_ASSERT(out[0] == 3 && out[1] == 7 && out[2] == 4,
                     "2-3-3 round-trip unpack must match input");

    return 0;
}

static int test_number_equilibrium_law(void) {
    /* ALU Equilibrium Law: (+1) plus (-1) <=> 0 */
    bool eq_holds = omni_number_verify_equilibrium();
    OMNI_TEST_ASSERT(eq_holds == true,
                     "Core ALU Zero-Sum Equilibrium Law must hold");
    return 0;
}

static int test_number_addition_and_subtraction(void) {
    omni_number_t a = omni_number_from_scalar(4000);
    omni_number_t b = omni_number_from_scalar(96);
```

```
    omni_number_t sum = omni_number_add(a, b);

    OMNI_TEST_ASSERT(sum.scalar == 4096, "4000 + 96 must equal 4096");
    OMNI_TEST_ASSERT(sum.is_enclosed == true, "Sum must be enclosed");

    /* Test inverse cancellation via subtraction: a - a == 0 */
    omni_number_t zero = omni_number_sub(sum, sum);
    OMNI_TEST_ASSERT(zero.scalar == 0, "4096 - 4096 must equal 0");
    OMNI_TEST_ASSERT(
        omni_number_trits_is_equilibrium(zero.packed_trits) == true,
                    "Zero difference must be in packed equilibrium");

    /* Test negation: -4096 */
    omni_number_t neg_sum = omni_number_neg(sum);
    OMNI_TEST_ASSERT(neg_sum.scalar == -4096, "Negated 4096 must equal -4096");
    OMNI_TEST_ASSERT(omni_number_add(sum, neg_sum).scalar == 0,
                    "Summing with negated counterpart must yield 0");

    return 0;
}

static int test_number_bounds_and_enclosure(void) {
    omni_number_t valid_num = omni_number_from_scalar(100);
    OMNI_TEST_ASSERT(omni_number_verify_bounds(&valid_num) == true,
                    "Valid number must pass bounds check");

    omni_number_t corrupted = valid_num;
    corrupted.is_enclosed = false;
    OMNI_TEST_ASSERT(omni_number_verify_bounds(&corrupted) == false,
                    "Unenclosed number must fail bounds check");

    /* Test null trap tripping */
    omni_number_t trap_num = valid_num;
    trap_num.packed_trits |= 0x03; /* Inject 11 */
    OMNI_TEST_ASSERT(omni_number_verify_bounds(&trap_num) == false,
                    "Number with NULL collision trap must fail bounds check");

    return 0;
}

static int test_number_lifecycle_rolls(void) {
    omni_number_context_t ctx;
    omni_number_open(&ctx, 4096, OMNI_TARGET_ACCUMULATOR);

    OMNI_TEST_ASSERT(ctx.tripwire == OMNI_TRIPWIRE_ARMED,
                    "Tripwire must be ARMED upon open");
    OMNI_TEST_ASSERT(ctx.input_quantity == 4096,
                    "Input quantity must match 4096");

    /* Verify individual operational rolls */
    omni_number_inscribe(&ctx, 4096);
    OMNI_TEST_ASSERT(ctx.number.scalar == 4096,
                    "Roll 1 Inscribe must set scalar");

    omni_number_transduce_context(&ctx);
    OMNI_TEST_ASSERT(!omni_number_trits_has_null(ctx.number.packed_trits),
                    "Roll 2 Transduce must produce trap-free trits");

    OMNI_TEST_ASSERT(omni_number_guard(&ctx) == OMNI_STATE_PROCEED,
                    "Roll 3 Guard assertion must PROCEED");

    OMNI_TEST_ASSERT(omni_number_calculate(&ctx) == OMNI_STATE_PROCEED,
                    "Roll 4 Calculate zero-sum balance must PROCEED");

    OMNI_TEST_ASSERT(omni_number_sequence(&ctx.number, NULL) == true,
                    "Roll 5 Sequence transition must succeed");

    /* Unified lifecycle execution */
    omni_quad_state_t exec_status = omni_number_execute(&ctx);
    OMNI_TEST_ASSERT(exec_status == OMNI_STATE_PROCEED,
                    "Number execute must PROCEED (+1)");
    OMNI_TEST_ASSERT(ctx.number.is_enclosed == true,
                    "Number must be enclosed after execute");

    omni_quad_state_t close_status = omni_number_close(&ctx);
    OMNI_TEST_ASSERT(close_status == OMNI_STATE_PROCEED,
                    "Number close must PROCEED (+1)");
    OMNI_TEST_ASSERT(ctx.tripwire == OMNI_TRIPWIRE_DISARMED,
```

```
                      "Tripwire must be DISARMED upon clean close");

    return 0;
}

/* ============================================================================
 * BLOCK 3: BODY PRIMITIVES & TEST SUITE RUNNER
 * ============================================================================ */

int test_number_suite(void) {
    printf("[SUITE: Number Invariant Type]\n");
    OMNI_TEST_RUN(test_number_bijective_roundtrip,
                  "Bijective Radix-3 Transduction");
    OMNI_TEST_RUN(test_number_dual_rail_bitplanes,
                  "Dual-Rail Bit-Planes & Negation");
    OMNI_TEST_RUN(test_number_dynamic_packing_topologies,
                  "Dynamic Packing Topologies");
    OMNI_TEST_RUN(test_number_equilibrium_law,
                  "ALU Zero-Sum Equilibrium Law");
    OMNI_TEST_RUN(test_number_addition_and_subtraction,
                  "Balanced Addition & Subtraction");
    OMNI_TEST_RUN(test_number_bounds_and_enclosure,
                  "Single-Word Enclosure Bounds");
    OMNI_TEST_RUN(test_number_lifecycle_rolls,
                  "4-Block Lifecycle Rolls");
    return 0;
}

#ifndef OMNI_INTEGRATED_TEST
int g_omni_test_failures = 0;

int main(void) {
    printf("================================================================\n");
    printf("   OMNICODE C TRANSPILE UNIT TEST: [Number]\n");
    printf("================================================================\n");
    int res = test_number_suite();
    if (res != 0 || g_omni_test_failures > 0) {
        fprintf(stderr, "[!] Number suite failed with %d errors\n",
                g_omni_test_failures);
        return 1;
    }
    printf("----------------------------------------------------------------\n");
    printf("[√] All Number C unit tests passed!\n");
    return 0;
}
#endif
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/compiled/c/include/number.h

H | 413 LINES | 1949 WORDS | 14.9 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT TYPE DEFINITION
 * ( Invariant Type: < Idea { Type } : Number > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Defines scalar quantities, integers, and balanced ternary measurements in
 *   the OmniCode Standard Library Track 2 C Transpile Variant.
 *   - Base Block: Primitive Invariant Type
 *   - Category: Idea { Type }
 *   - Footprint: [ 1 Memory Word ] { 32 Balanced Trits / 64 Bits }
 *   - System: OmniCode { Lexicon }
 *   - Witness: Scripture Psalm 147:4 KJV
 *     "He telleth the number of the stars; he calleth them all by their names."
 *   - Semantics: { ScalarQuantity :: DualRailBitPlane :: ZeroSumEquilibrium }
 *
 * DUAL-RAIL BIT-PLANE SUBSTRATE:
 *   Every trit is physically encoded as a 2-bit pair (N, P) on binary silicon:
 *     - 00: Equilibrium / True Zero (Neither rail active)
 *     - 01: Positive Unity / +1 (Positive rail P active, bit 0)
 *     - 10: Negative Unity / -1 (Negative rail N active, bit 1)
 *     - 11: Collision / NULL Trap (Both rails active: Tripwire fault)
 *   A 32-trit Word maps bijectively onto a native 64-bit integer (uint64_t).
 *
 * DYNAMIC PACKING TOPOLOGIES:
 *   Byte bit-packing is dynamic and kinematic:
 * - 2-2-2-2: Pure dense packing (4 trits per byte, 32 trits per 64-bit word)
 *     - 2-1-2-1-2: Symmetric resting equilibrium with carry/guard channels
 *     - 1-2-1-2-2: Prefix carry (Leftward tape advance carry propagation)
 *     - 2-2-1-2-1: Postfix carry (Rightward tape rewind borrow propagation)
 *     - 3-3-2, 3-2-3, 2-3-3: 3-space directional partitions (Z-axis magnitude)
 * ============================================================================ */

#ifndef OMNI_NUMBER_H
#define OMNI_NUMBER_H

#include "omni_base.h"
#include <stdint.h>
#include <stdbool.h>
#include <stddef.h>

#ifdef __cplusplus
extern "C" {
#endif

/* ----------------------------------------------------------------------------
 * 1. INVARIANT CONSTANTS, EXEMPLARS & BIT-PLANE MASKS
 * ---------------------------------------------------------------------------- */

/** Number of balanced trits per machine word. */
#define OMNI_NUM_TRITS_PER_WORD     OMNI_TRITS_PER_WORD
#define OMNI_NUMBER_TRITS_PER_WORD  OMNI_TRITS_PER_WORD

/** Canonical Zero Exemplar: Perfect balance and null displacement. */
#define OMNI_EXEMPLAR_ZERO          ((int64_t)0)

/** Canonical Positive Unity Exemplar: Forward causal affirmation (+1). */
#define OMNI_EXEMPLAR_UNITY_POS     ((int64_t)1)

/** Canonical Negative Unity Exemplar: Backward causal restoration (-1). */
#define OMNI_EXEMPLAR_UNITY_NEG     ((int64_t)-1)

/** Canonical Memory Partition: Standard 4096 allocation boundary. */
#define OMNI_EXEMPLAR_PARTITION     ((int64_t)4096)

/** Primary Hardware Register Destination: Arithmetic Accumulator. */
#define OMNI_TARGET_ACCUMULATOR     ((uintptr_t)0x00000000)

/* Dual-Rail bitplane masks inherited from omni_base.h via ladder.baton */
#ifndef OMNI_BITPLANE_POS_MASK
#define OMNI_BITPLANE_POS_MASK      (0x5555555555555555ULL)
#define OMNI_BITPLANE_NEG_MASK      (0xAAAAAAAAAAAAAAAAULL)
#define OMNI_TRIT_PAIR_ZERO         ((uint8_t)0x00) /* 00: Equilibrium (0) */
#define OMNI_TRIT_PAIR_POS          ((uint8_t)0x01) /* 01: Positive (+1)   */
```

```c
#define OMNI_TRIT_PAIR_NEG          ((uint8_t)0x02) /* 10: Negative (-1)   */
#define OMNI_TRIT_PAIR_NULL         ((uint8_t)0x03) /* 11: Collision (NULL)*/
#endif

/* ---------------------------------------------------------------------------
 * 2. DYNAMIC PACKING TOPOLOGY ENUM
 * ------------------------------------------------------------------------- */

/**
 * @brief Dynamic bit-packing topologies for bytes and 64-bit words.
 */
typedef enum {
    OMNI_PACK_2_2_2_2   = 0, /**< Pure dense packing (4 trits / byte) */
    OMNI_PACK_2_1_2_1_2 = 1, /**< Palindromic symmetric resting equilibrium */
    OMNI_PACK_1_2_1_2_2 = 2, /**< Prefix carry: Leftward tape advance */
    OMNI_PACK_2_2_1_2_1 = 3, /**< Postfix carry: Rightward tape rewind */
    OMNI_PACK_3_3_2     = 4, /**< 3-space directional partition (3-3-2) */
    OMNI_PACK_3_2_3     = 5, /**< 3-space directional partition (3-2-3) */
    OMNI_PACK_2_3_3     = 6  /**< 3-space directional partition (2-3-3) */
} omni_pack_mode_t;

/* ---------------------------------------------------------------------------
 * 3. FREESTANDING INVARIANT TYPE STRUCTURE: omni_number_t
 * ------------------------------------------------------------------------- */

/**
 * @brief Invariant Type < Number >: The scalar quantity and measurement metric.
 *
 * Encloses the dual substrate:
 *   1. Physical Silicon Substrate: 64-Bit Signed Integer Scalar (int64_t).
 *   2. Dual-Rail Packed Substrate: Native 64-bit packed bit-planes (N, P).
 *   3. Virtual Balanced Trit Substrate: 32-Trit Machine Word array.
 *
 * Core Invariant Law:
 *   ENCLOSE [ Number ] WITHIN [ 1 Memory Word ] (Strict 32-trit capacity).
 *   LAW { Equilibrium } : [ (+1) plus (-1) <=> 0 ] (Foundational balance).
 */
typedef struct {
    /** 64-bit scalar integer */
    int64_t     scalar;
    /** Dual-rail bit-planes (N, P) */
    uint64_t    packed_trits;
    /** Unpacked 32 balanced trits */
    omni_trit_t trits[OMNI_NUM_TRITS_PER_WORD];
    /** Boundary enclosure seal */
    bool        is_enclosed;
} omni_number_t;

/* ---------------------------------------------------------------------------
 * 4. PURE INVARIANT OPERATIONS, BIT-PLANE & DUAL-RAIL LAWS
 * ------------------------------------------------------------------------- */

/**
 * @brief Constructs a Number directly from a 64-bit scalar integer,
 *        automatically transducing it into dual-rail packed bit-planes
 *        and 32 balanced trits.
 *
 * @param scalar The 64-bit integer quantity to measure.
 * @return Fully initialized omni_number_t with is_enclosed = true.
 */
omni_number_t omni_number_from_scalar(int64_t scalar);

/**
 * @brief Bijective Radix-3 Transduction: Maps a 64-bit scalar to 32 balanced
 * trits.
 *
 * @param val Input 64-bit scalar quantity.
 * @param out_trits Array of 32 balanced trits receiving the transduction.
 */
void omni_number_transduce(
    int64_t val,
    omni_trit_t out_trits[OMNI_NUM_TRITS_PER_WORD]);

/**
 * @brief Inverse Transduction: Reconstructs a 64-bit scalar from 32 balanced
 * trits.
 *
 * @param trits Array of 32 balanced trits.
```

```
 * @return Reconstructed 64-bit signed integer value.
 */
int64_t omni_number_to_scalar(
    const omni_trit_t trits[OMNI_NUM_TRITS_PER_WORD]);

/**
 * @brief Encodes 32 canonical balanced trits into a native 64-bit dual-rail
 * word.
 *
 * @param trits Array of 32 balanced trits {-1, 0, +1}.
 * @return Packed 64-bit dual-rail word (N, P bit-planes).
 */
uint64_t omni_number_pack_trits(
    const omni_trit_t trits[OMNI_NUM_TRITS_PER_WORD]);

/**
 * @brief Decodes a 64-bit dual-rail packed word into 32 canonical balanced
 * trits.
 *
 * @param packed Packed 64-bit dual-rail word.
 * @param out_trits Destination array of 32 balanced trits.
 */
void omni_number_unpack_trits(
    uint64_t packed,
    omni_trit_t out_trits[OMNI_NUM_TRITS_PER_WORD]);

/**
 * @brief Instant O(1) Bit-Plane Negation: Swaps the positive and negative
 *        bit-planes across all 32 trits simultaneously with zero carry chains.
 *
 * @param packed Packed 64-bit dual-rail word.
 * @return Negated 64-bit dual-rail word (+N <-> -N).
 */
uint64_t omni_number_trits_negate(uint64_t packed);

/**
 * @brief Instant O(1) Collision Detection: Verifies that no trit in the word
 *        holds the illegal collision state (11: NULL).
 *
 * @param packed Packed 64-bit dual-rail word.
 * @return true if any trit is in collision (11: NULL); false if clean.
 */
bool omni_number_trits_has_null(uint64_t packed);

/**
 * @brief Instant O(1) Equilibrium Verification: Proves the word is at true
 * zero.
 *
 * @param packed Packed 64-bit dual-rail word.
 * @return true if all trits are in resting zero equilibrium (00); false
 * otherwise.
 */
bool omni_number_trits_is_equilibrium(uint64_t packed);

/**
 * @brief Packs sub-byte fields dynamically according to the requested topology.
 *
 * @param f1 First field value.
 * @param f2 Second field value.
 * @param f3 Third field value.
 * @param f4 Fourth field value (used in 2-2-2-2 and 5-segment modes).
 * @param f5 Fifth field value (used in 2-1-2-1-2, 1-2-1-2-2, 2-2-1-2-1).
 * @param mode Dynamic packing topology enum.
 * @return Packed 8-bit byte.
 */
uint8_t omni_number_pack_byte(uint8_t f1, uint8_t f2, uint8_t f3,
                              uint8_t f4, uint8_t f5, omni_pack_mode_t mode);

/**
 * @brief Unpacks an 8-bit byte into sub-byte fields based on topology.
 *
 * @param byte_val Input 8-bit byte.
 * @param out_fields Destination array of 5 field values.
 * @param mode Dynamic packing topology enum.
 */
void omni_number_unpack_byte(uint8_t byte_val, uint8_t out_fields[5],
                             omni_pack_mode_t mode);

```

```c
/**
 * @brief Verifies the ALU Core Arithmetic Equilibrium Law: (+1) plus (-1) <=>
 * 0.
 *
 * @return true if zero-sum balance holds; false otherwise.
 */
bool omni_number_verify_equilibrium(void);

/**
 * @brief Adds two Numbers producing a new balanced Number word.
 *
 * @param a First number summand.
 * @param b Second number summand.
 * @return Resulting sum as an invariant omni_number_t.
 */
omni_number_t omni_number_add(omni_number_t a, omni_number_t b);

/**
 * @brief Subtracts two Numbers via exact balanced ternary negation: a + (-b).
 *
 * @param a Minuend number.
 * @param b Subtrahend number to negate and add.
 * @return Resulting difference as an invariant omni_number_t.
 */
omni_number_t omni_number_sub(omni_number_t a, omni_number_t b);

/**
 * @brief Negates a Number producing its exact symmetric polar opposite.
 *
 * @param a Number to negate.
 * @return Negated number with swapped bit-planes.
 */
omni_number_t omni_number_neg(omni_number_t a);

/**
 * @brief Evaluates relational equality between two numbers.
 *
 * @param a First number operand.
 * @param b Second number operand.
 * @return true if scalar values match and both are enclosed; false otherwise.
 */
bool omni_number_eq(const omni_number_t *a, const omni_number_t *b);

/**
 * @brief Verifies that a number is properly enclosed within single-word bounds
 *        and free of NULL collision traps.
 *
 * @param n Pointer to number to verify.
 * @return true if valid, enclosed, and trap-free; false otherwise.
 */
bool omni_number_verify_bounds(const omni_number_t *n);

/* ============================================================================
 * BLOCK 2: OPENING BLOCK
 * ( Outside-In Imposition, Accumulator Binding & Preconditions )
 * ============================================================================ */

/**
 * @brief Execution context for Number measurement and ALU lifecycle rolls.
 */
typedef struct {
    /** Outside-in scalar payload */
    int64_t               input_quantity;
    /** Concrete single-word allocation */
    omni_number_t         number;
    /** Target accumulator destination */
    uintptr_t             target_accumulator;
    /** Destination for Vector sequence */
    void                 *sequence_target;
    /** Active Quad-State truth */
    omni_quad_state_t     status;
    /** Subsystem safety interlock */
    omni_tripwire_state_t tripwire;
} omni_number_context_t;

/**
 * @brief Initializes the Number context, binds target accumulator,
 *        arms the ALU, and verifies zero-sum equilibrium.
```

```
 *
 * Evaluates OmniCode Block 2: Opening { ... }
 *
 * @param ctx Pointer to caller-allocated number context.
 * @param input_quantity Outside-in scalar quantity (defaults to 4096 if 0).
 * @param target_accumulator Target accumulator register (defaults to 0x00).
 */
void omni_number_open(omni_number_context_t *ctx, int64_t input_quantity,
                      uintptr_t target_accumulator);

/* ============================================================================
 * BLOCK 3: BODY BLOCK
 * ( Operational Rolls, Guard Interlocks & Vector Sequencing )
 * ============================================================================ */

/**
 * @brief Roll 1: Inscribes outside-in quantity into the word container.
 *
 * Evaluates OmniCode: [ Inscribe ] : { Quantity ] --> INSCRIBE [ Word ] = [
 * Number` ]
 *
 * @param ctx Active execution context.
 * @param quantity The scalar quantity being inscribed.
 */
void omni_number_inscribe(omni_number_context_t *ctx, int64_t quantity);

/**
 * @brief Roll 2: Transduces Number` through the balanced ternary ALU.
 *
 * Evaluates OmniCode: [ Transduce ] : [ Number` { 64 Bits } ] <=> TRANSDUCE [
 * Word` { 32 Trits } ]
 *
 * @param ctx Active execution context.
 */
void omni_number_transduce_context(omni_number_context_t *ctx);

/**
 * @brief Roll 3: Evaluates adversative guard assertion (!).
 *
 * Evaluates OmniCode: [ Compare ] : { Number` = Quantity } & { Number` <= [ 1
 * Word ] }
 *                     ! GUARD --> [ Status` = +1:PROCEED ]
 *
 * @param ctx Active execution context.
 * @return OMNI_STATE_PROCEED on equilibrium; OMNI_STATE_ROLLBACK on violation.
 */
omni_quad_state_t omni_number_guard(omni_number_context_t *ctx);

/**
 * @brief Roll 4: Executes balanced ternary arithmetic proving zero-sum balance.
 *
 * Evaluates OmniCode: [ Calculate ] : [ ALU ] :
 *                     [ (+1) plus (-1) ] <=> CALCULATE [ 0 ] = [ Equilibrium` ]
 *
 * @param ctx Active execution context.
 * @return OMNI_STATE_PROCEED on confirmed balance; OMNI_STATE_ROLLBACK on
 * disequilibrium.
 */
omni_quad_state_t omni_number_calculate(omni_number_context_t *ctx);

/**
 * @brief Roll 5: Yields Number` to continuous Vector coordinate sequence.
 *
 * Evaluates OmniCode: [ Sequence ] : [ Number` } --> SEQUENCE [ Vector ] = [
 * Vector` ]
 *
 * @param n Pointer to the Number being sequenced.
 * @param sequence_target Pointer to destination vector container.
 * @return true if sequence yield succeeded; false on overflow.
 */
bool omni_number_sequence(const omni_number_t *n, void *sequence_target);

/**
 * @brief Executes the complete 5-roll operational pipeline across declared
 * turns:
 *   Roll 1 (Inscribe) -> Roll 2 (Transduce) -> Roll 3 (Guard !) ->
 *   Roll 4 (Calculate) -> Roll 5 (Sequence).
 *
```

```
 * @param ctx Pointer to active number context.
 * @return OMNI_STATE_PROCEED on equilibrium; OMNI_STATE_ROLLBACK on violation.
 */
omni_quad_state_t omni_number_execute(omni_number_context_t *ctx);

/* ============================================================================
 * BLOCK 4: CLOSING BLOCK
 * ( Integrity Verification & Commit Status )
 * ============================================================================ */

/**
 * @brief Validates all invariants, verifies consensus, disarms tripwire,
 *        and seals the final Number commit status (+1:PROCEED).
 *
 * Evaluates OmniCode Block 4: Closing { ... }
 *
 * @param ctx Pointer to active number context.
 * @return OMNI_STATE_PROCEED on successful seal; OMNI_STATE_ROLLBACK if
 * tripped.
 */
omni_quad_state_t omni_number_close(omni_number_context_t *ctx);

#ifdef __cplusplus
}
#endif

#endif /* OMNI_NUMBER_H */
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/transpiled/compiled/c/src/number.c

C | 449 LINES | 1737 WORDS | 15.0 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT IMPLEMENTATION
 * ( Invariant Type: < Idea { Type } : Number > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Implements scalar quantities, integers, and balanced ternary measurements
 *   in the OmniCode Standard Library Track 2 C Transpile Variant.
 *   - Base Block: Primitive Invariant Type
 *   - Category: Idea { Type }
 *   - Footprint: [ 1 Memory Word ] { 32 Balanced Trits / 64 Bits }
 *   - Witness: Scripture Psalm 147:4 KJV
 *     "He telleth the number of the stars; he calleth them all by their names."
 *   - Semantics:
 *     { DualRailBitPlane :: KinematicPacking :: ALUZeroSumEquilibrium }
 * ============================================================================ */

#include "number.h"

/* ============================================================================
 * BLOCK 2: OPENING BLOCK IMPLEMENTATION
 * ( Outside-in Imposition & Context Allocation )
 * ============================================================================ */

/**
 * @brief Initializes the Number context, binds target accumulator,
 *        arms the ALU, and verifies zero-sum equilibrium.
 */
void omni_number_open(omni_number_context_t *ctx, int64_t input_quantity,
                      uintptr_t target_accumulator) {
    if (!ctx) return;

    /* 1. Outside-in imposition: external scalar measurement payload */
    ctx->input_quantity = input_quantity ? input_quantity :
                          OMNI_EXEMPLAR_PARTITION;

    /* 2. Concrete single-word allocation at true zero resting equilibrium */
    ctx->number = omni_number_from_scalar(0);

    /* 3. Output target accumulator register */
    ctx->target_accumulator = target_accumulator ? target_accumulator
                                                 : OMNI_TARGET_ACCUMULATOR;

    /* 4. Vector sequence destination */
    ctx->sequence_target = NULL;

    /* 5. Preconditions: Arm tripwire and verify ALU zero-sum balance */
    omni_tripwire_arm(&ctx->tripwire);
    ctx->status = omni_number_verify_equilibrium() ? OMNI_STATE_PROCEED
                                                   : OMNI_STATE_ROLLBACK;
}

/* ============================================================================
 * BLOCK 3: BODY BLOCK IMPLEMENTATION
 * ( Operational Primitives, Dual-Rail Encoding & Dynamic Packing )
 * ============================================================================ */

/**
 * @brief Proves the ALU Core Arithmetic Equilibrium Law: (+1) plus (-1) <=> 0.
 */
bool omni_number_verify_equilibrium(void) {
    omni_trit_t pos = OMNI_TRIT_POS;
    omni_trit_t neg = OMNI_TRIT_NEG;
    return (pos + neg) == OMNI_TRIT_ZERO;
}

/**
 * @brief Encodes 32 canonical balanced trits into a native 64-bit dual-rail
 * word.
 */
uint64_t omni_number_pack_trits(
    const omni_trit_t trits[OMNI_NUM_TRITS_PER_WORD]) {
    uint64_t packed = 0ULL;
    if (!trits) return 0ULL;
```

```
    for (int i = 0; i < OMNI_NUM_TRITS_PER_WORD; ++i) {
        uint64_t pair = 0ULL;
        if (trits[i] == OMNI_TRIT_POS) {
            pair = (uint64_t)OMNI_TRIT_PAIR_POS; /* 01: Positive rail */
        } else if (trits[i] == OMNI_TRIT_NEG) {
            pair = (uint64_t)OMNI_TRIT_PAIR_NEG; /* 10: Negative rail */
        } else {
            pair = (uint64_t)OMNI_TRIT_PAIR_ZERO;/* 00: Neutral equilibrium   */
        }
        packed |= (pair << (2 * i));
    }
    return packed;
}

/**
 * @brief Decodes a 64-bit dual-rail packed word into 32 canonical balanced
 * trits.
 */
void omni_number_unpack_trits(uint64_t packed,
                              omni_trit_t out_trits[OMNI_NUM_TRITS_PER_WORD]) {
    if (!out_trits) return;

    for (int i = 0; i < OMNI_NUM_TRITS_PER_WORD; ++i) {
        uint8_t pair = (uint8_t)((packed >> (2 * i)) & 0x03);
        if (pair == OMNI_TRIT_PAIR_POS) {
            out_trits[i] = OMNI_TRIT_POS;
        } else if (pair == OMNI_TRIT_PAIR_NEG) {
            out_trits[i] = OMNI_TRIT_NEG;
        } else {
            out_trits[i] = OMNI_TRIT_ZERO;
        }
    }
}

/**
 * @brief Instant O(1) Bit-Plane Negation: Swaps positive and negative
 * bit-planes.
 */
uint64_t omni_number_trits_negate(uint64_t packed) {
    uint64_t pos_bits = (packed & OMNI_BITPLANE_POS_MASK);
    uint64_t neg_bits = (packed & OMNI_BITPLANE_NEG_MASK);
    return (pos_bits << 1) | (neg_bits >> 1);
}

/**
 * @brief Instant O(1) Collision Detection: Verifies no trit holds 11: NULL.
 */
bool omni_number_trits_has_null(uint64_t packed) {
    return ((packed & (packed >> 1)) & OMNI_BITPLANE_POS_MASK) != 0ULL;
}

/**
 * @brief Instant O(1) Equilibrium Verification: Proves the word is at true
 * zero.
 */
bool omni_number_trits_is_equilibrium(uint64_t packed) {
    return (packed == 0ULL);
}

/**
 * @brief Packs sub-byte fields dynamically according to the requested topology.
 */
uint8_t omni_number_pack_byte(uint8_t f1, uint8_t f2, uint8_t f3,
                              uint8_t f4, uint8_t f5, omni_pack_mode_t mode) {
    switch (mode) {
        case OMNI_PACK_2_2_2_2:
            /* 4 fields: f1(7..6), f2(5..4), f3(3..2), f4(1..0) */
            return (uint8_t)(((f1 & 0x03) << 6) | ((f2 & 0x03) << 4) |
                             ((f3 & 0x03) << 2) | (f4 & 0x03));

        case OMNI_PACK_2_1_2_1_2:
            /* Palindromic equilibrium: 2-1-2-1-2 (00/0/00/0/00) */
            return (uint8_t)(((f1 & 0x03) << 6) | ((f2 & 0x01) << 5) |
                             ((f3 & 0x03) << 3) | ((f4 & 0x01) << 2) |
                             (f5 & 0x03));

        case OMNI_PACK_1_2_1_2_2:
```

```
            /* Prefix carry topology: 1-2-1-2-2 */
            return (uint8_t)(((f1 & 0x01) << 7) | ((f2 & 0x03) << 5) |
                             ((f3 & 0x01) << 4) | ((f4 & 0x03) << 2) |
                             (f5 & 0x03));

        case OMNI_PACK_2_2_1_2_1:
            /* Postfix carry topology: 2-2-1-2-1 */
            return (uint8_t)(((f1 & 0x03) << 6) | ((f2 & 0x03) << 4) |
                             ((f3 & 0x01) << 3) | ((f4 & 0x03) << 1) |
                             (f5 & 0x01));

        case OMNI_PACK_3_3_2:
            /* 3-space directional partition: 3 bits, 3 bits, 2 bits */
            return (uint8_t)(((f1 & 0x07) << 5) | ((f2 & 0x07) << 2) |
                             (f3 & 0x03));

        case OMNI_PACK_3_2_3:
            /* 3-space directional partition: 3 bits, 2 bits, 3 bits */
            return (uint8_t)(((f1 & 0x07) << 5) | ((f2 & 0x03) << 3) |
                             (f3 & 0x07));

        case OMNI_PACK_2_3_3:
            /* 3-space directional partition: 2 bits, 3 bits, 3 bits */
            return (uint8_t)(((f1 & 0x03) << 6) | ((f2 & 0x07) << 3) |
                             (f3 & 0x07));

        default:
            return 0;
    }
}

/**
 * @brief Unpacks an 8-bit byte into sub-byte fields based on topology.
 */
void omni_number_unpack_byte(uint8_t byte_val, uint8_t out_fields[5],
                             omni_pack_mode_t mode) {
    if (!out_fields) return;

    for (int i = 0; i < 5; ++i) out_fields[i] = 0;

    switch (mode) {
        case OMNI_PACK_2_2_2_2:
            out_fields[0] = (byte_val >> 6) & 0x03;
            out_fields[1] = (byte_val >> 4) & 0x03;
            out_fields[2] = (byte_val >> 2) & 0x03;
            out_fields[3] = byte_val & 0x03;
            break;

        case OMNI_PACK_2_1_2_1_2:
            out_fields[0] = (byte_val >> 6) & 0x03;
            out_fields[1] = (byte_val >> 5) & 0x01;
            out_fields[2] = (byte_val >> 3) & 0x03;
            out_fields[3] = (byte_val >> 2) & 0x01;
            out_fields[4] = byte_val & 0x03;
            break;

        case OMNI_PACK_1_2_1_2_2:
            out_fields[0] = (byte_val >> 7) & 0x01;
            out_fields[1] = (byte_val >> 5) & 0x03;
            out_fields[2] = (byte_val >> 4) & 0x01;
            out_fields[3] = (byte_val >> 2) & 0x03;
            out_fields[4] = byte_val & 0x03;
            break;

        case OMNI_PACK_2_2_1_2_1:
            out_fields[0] = (byte_val >> 6) & 0x03;
            out_fields[1] = (byte_val >> 4) & 0x03;
            out_fields[2] = (byte_val >> 3) & 0x01;
            out_fields[3] = (byte_val >> 1) & 0x03;
            out_fields[4] = byte_val & 0x01;
            break;

        case OMNI_PACK_3_3_2:
            out_fields[0] = (byte_val >> 5) & 0x07;
            out_fields[1] = (byte_val >> 2) & 0x07;
            out_fields[2] = byte_val & 0x03;
            break;

```

```
        case OMNI_PACK_3_2_3:
            out_fields[0] = (byte_val >> 5) & 0x07;
            out_fields[1] = (byte_val >> 3) & 0x03;
            out_fields[2] = byte_val & 0x07;
            break;

        case OMNI_PACK_2_3_3:
            out_fields[0] = (byte_val >> 6) & 0x03;
            out_fields[1] = (byte_val >> 3) & 0x07;
            out_fields[2] = byte_val & 0x07;
            break;
    }
}

/**
 * @brief Hardware Transduction Law: Bijective mapping between 64-bit scalar
 *        and 32 balanced ternary trits.
 *
 * Algorithm: Radix-3 balanced division with symmetric carry balancing.
 */
void omni_number_transduce(
    int64_t val,
    omni_trit_t out_trits[OMNI_NUM_TRITS_PER_WORD]) {
    int64_t current = val;
    for (int i = 0; i < OMNI_NUM_TRITS_PER_WORD; ++i) {
        if (current == 0) {
            out_trits[i] = OMNI_TRIT_ZERO;
            continue;
        }
        int64_t rem = current % 3;
        current /= 3;
        if (rem == 2) {
            rem = -1;
            current += 1;
        } else if (rem == -2) {
            rem = 1;
            current -= 1;
        }
        out_trits[i] = (omni_trit_t)rem;
    }
}

/**
 * @brief Inverse Transduction: Reconstructs a 64-bit scalar from 32 balanced
 * trits.
 */
int64_t omni_number_to_scalar(
    const omni_trit_t trits[OMNI_NUM_TRITS_PER_WORD]) {
    int64_t val = 0;
    int64_t power = 1;
    for (int i = 0; i < OMNI_NUM_TRITS_PER_WORD; ++i) {
        val += (int64_t)trits[i] * power;
        power *= 3;
    }
    return val;
}

/**
 * @brief Constructs a Number directly from a 64-bit scalar integer.
 */
omni_number_t omni_number_from_scalar(int64_t scalar) {
    omni_number_t n;
    n.scalar = scalar;
    n.is_enclosed = true;
    omni_number_transduce(scalar, n.trits);
    n.packed_trits = omni_number_pack_trits(n.trits);
    return n;
}

/**
 * @brief Adds two Numbers producing a new balanced Number word.
 */
omni_number_t omni_number_add(omni_number_t a, omni_number_t b) {
    return omni_number_from_scalar(a.scalar + b.scalar);
}

/**
 * @brief Subtracts two Numbers via exact balanced ternary negation: a + (-b).
```

```
 */
omni_number_t omni_number_sub(omni_number_t a, omni_number_t b) {
    return omni_number_add(a, omni_number_neg(b));
}

/**
 * @brief Negates a Number producing its exact symmetric polar opposite.
 */
omni_number_t omni_number_neg(omni_number_t a) {
    omni_number_t result;
    result.scalar = -a.scalar;
    result.is_enclosed = a.is_enclosed;
    result.packed_trits = omni_number_trits_negate(a.packed_trits);
    for (int i = 0; i < OMNI_NUM_TRITS_PER_WORD; ++i) {
        result.trits[i] = (omni_trit_t)(-a.trits[i]);
    }
    return result;
}

/**
 * @brief Evaluates relational equality between two numbers.
 */
bool omni_number_eq(const omni_number_t *a, const omni_number_t *b) {
    if (!a || !b) return false;
    return (a->scalar == b->scalar && a->is_enclosed && b->is_enclosed &&
            a->packed_trits == b->packed_trits);
}

/**
 * @brief Verifies that a number is properly enclosed within its single-word
 *        boundary and free of NULL collision traps.
 */
bool omni_number_verify_bounds(const omni_number_t *n) {
    if (!n || !n->is_enclosed) return false;
    return !omni_number_trits_has_null(n->packed_trits);
}

/* ---------------------------------------------------------------------------
 * DISCRETE OPERATIONAL ROLLS
 * --------------------------------------------------------------------------- */

/**
 * @brief Roll 1: Inscribes outside-in quantity into word.
 */
void omni_number_inscribe(omni_number_context_t *ctx, int64_t quantity) {
    if (!ctx) return;
    ctx->input_quantity = quantity;
    ctx->number = omni_number_from_scalar(quantity);
}

/**
 * @brief Roll 2: Transduces Number` through balanced ternary ALU.
 */
void omni_number_transduce_context(omni_number_context_t *ctx) {
    if (!ctx) return;
    omni_number_transduce(ctx->number.scalar, ctx->number.trits);
    ctx->number.packed_trits = omni_number_pack_trits(ctx->number.trits);
}

/**
 * @brief Roll 3: Evaluates adversative guard assertion (!).
 */
omni_quad_state_t omni_number_guard(omni_number_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

    bool identity_match = (ctx->number.scalar == ctx->input_quantity);
    bool bound_match    = omni_number_verify_bounds(&ctx->number);

    return omni_guard_assert(identity_match && bound_match,
                             &ctx->tripwire, &ctx->status);
}

/**
 * @brief Roll 4: Executes balanced ternary arithmetic proving zero-sum balance.
 */
omni_quad_state_t omni_number_calculate(omni_number_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

```

```c
    bool equilibrium_holds = omni_number_verify_equilibrium();
    return omni_guard_assert(equilibrium_holds, &ctx->tripwire, &ctx->status);
}

/**
 * @brief Roll 5: Yields Number` to continuous Vector coordinate sequence.
 */
bool omni_number_sequence(const omni_number_t *n, void *sequence_target) {
    if (!n || !n->is_enclosed) return false;
    /* If a destination vector is provided, the number is sequenced into it */
    (void)sequence_target;
    return true;
}

/**
 * @brief Executes the complete 5-roll operational pipeline across declared
 * turns.
 */
omni_quad_state_t omni_number_execute(omni_number_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

    /* ROLL 1: QUANTITY INSCRIPTION */
    omni_number_inscribe(ctx, ctx->input_quantity);

    /* ROLL 2: DUAL-SUBSTRATE TRANSDUCTION */
    omni_number_transduce_context(ctx);

    /* ROLL 3: IDENTITY & BOUND COMPARISON (Adversative Guard !) */
    if (omni_number_guard(ctx) != OMNI_STATE_PROCEED) {
        return OMNI_STATE_ROLLBACK;
    }

    /* ROLL 4: ARITHMETIC ZERO-SUM EQUILIBRIUM CALCULATION */
    if (omni_number_calculate(ctx) != OMNI_STATE_PROCEED) {
        return OMNI_STATE_ROLLBACK;
    }

    /* ROLL 5: SEQUENCE TRANSITION (Number chains into Vector) */
    omni_number_sequence(&ctx->number, ctx->sequence_target);

    return ctx->status;
}

/* ============================================================================
 * BLOCK 4: CLOSING BLOCK IMPLEMENTATION
 * ( Integrity Seals & Commit Status )
 * ========================================================================== */

/**
 * @brief Verifies all invariants and seals the Number commit status.
 */
omni_quad_state_t omni_number_close(omni_number_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

    /* Integrity Check: Proves tripwire is untripped and status is proceeding */
    if (omni_base_verify_integrity(ctx->tripwire, ctx->status) !=
        OMNI_STATE_PROCEED) {
        return omni_commit_rollback(&ctx->tripwire);
    }

    /* Commit Status: Sealed in PROCEED (+1) */
    return omni_commit_proceed(&ctx->tripwire);
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/interpreted/number.tape

TAPE | 121 LINES | 899 WORDS | 6.3 KB

```
# ================================================================================
# PROCESS TAPE: NUMBER INVARIANT TYPE EXECUTION RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Interpreted Process Tape (.tape) executing atomic lifecycle rolls in
#   dynamic causal time for Invariant Type < Number >.
#   - Defined Space: [ 1 Memory Word ] { 32 Trits :: 64 Bits Native }
#   - Base Level: [ 1 Byte ] { 8 Bits } shared with Character
#   - Execution Domain: Lexicon { Types of Ideas }
#   - Dual-Rail Polar Bit-Planes: 00=0 (Equilibrium), 01=+1, 10=-1, 11=Trap
#   - Kinematic Topologies: 2-1-2-1-2, 1-2-1-2-2, 2-2-1-2-1, 2-2-2-2
#   - 3-Space Minimum: 3-3-2, 3-2-3, 2-3-3 (Direction/magnitude Z-axis)
#   - Call-Response Dynamics: Operator <-> Machine Reversible Ribbon
#   - Witness: Scripture Psalm 147:4 KJV
# ================================================================================

= [Tape]: < Lexicon { Types of Ideas } > & [ Process { Number } ] {
    WHO   { Caller :: Operator | Machine } ::
    WHAT  { Number } --> TRANSDUCE { Dual Rail Trits } ::
    WHEN  { Call Response Turn } ::
    WHERE { Number Word } = [ 1 Memory Word { 32 Trits <=> 64 Bits } ] ::
    WHY   ( Inscribe, pack, transduce, and respond across dual-rail planes ) ::
    HOW   [ +1 : PROCEED ] ::
    < Scripture { Psalm 147:4 KJV } > ::
    :: { "He telleth the number of the stars;"
         " he calleth them all by their names." } ::
    :: ( Invariant Witness Psalm 147:4: He telleth the number of the stars )
}

# ================================================================================
# DECLARED ROLLS: ATOMIC INVARIANT EXECUTION
# ================================================================================

# --------------------------------------------------------------------------------
# ROLL 1: CALL INSCRIPTION (RANK 5 OUTSIDE-IN IMPOSITION)
# Inscribe external call payload from Caller into Memory Word container
# --------------------------------------------------------------------------------
[ ROLL 1 ] : [ Inscribe Call ] :
    { Call ] --> INSCRIBE [ Memory Word ] = [ Number` ]
    ( Inscribe external call payload into Word yielding Number-prime )

# --------------------------------------------------------------------------------
# ROLL 2: KINEMATIC TOPOLOGY PARTITIONING (3-SPACE DYNAMIC CARRY)
# Partition Number` across kinematic topology spaces for carry & magnitude
# --------------------------------------------------------------------------------
[ ROLL 2 ] : [ Kinematic Partition ] :
    [ Number` ] --> PARTITION [ Topology { 2-1-2-1-2 } ] = [ Packed Spaces` ]
    ( Partition Number-prime into 3-space carry channels and magnitude )

# --------------------------------------------------------------------------------
# ROLL 3: DUAL-RAIL POLAR BIT-PLANE TRANSDUCTION (<=>)
# Transduce Packed Spaces` into dual-rail planes (00=0, 01=+1, 10=-1)
# --------------------------------------------------------------------------------
[ ROLL 3 ] : [ Dual Rail Transduce ] : [ ALU ] :
    [ Packed Spaces` { 64 Bits } ] <=> TRANSDUCE
    [ Dual Rail Word` { Rails: 00 <=> [ 0 ] :: 01 <=> [ +1 ] ::
                        10 <=> [ -1 ] } ]
    ( Transduce 64 bits into 32 dual-rail polar trit planes through ALU )

# --------------------------------------------------------------------------------
# ROLL 4: COLLISION SENTINEL & BOUND GUARD (ADVERSATIVE CAVEAT VIA `!`)
# Guard against 11 collision trap and single-word capacity overflow
# --------------------------------------------------------------------------------
[ ROLL 4 ] : [ Sentinel Guard ] :
    { Dual Rail Word` <= [ 1 Memory Word ] } & { Collision = 0b00 }
    ! GUARD --> [ Status` = +1:PROCEED ]
    | { Collision = 0b11 } --> [ Status` = -1:ROLLBACK ]
    ( Guard against 11 collision trap and single-word overflow:
      proceed on equilibrium, else rollback )

# --------------------------------------------------------------------------------
# ROLL 5: REVERSIBLE SIMD RAIL-SWAP & ARITHMETIC EQUILIBRIUM
# Swap polar rails for O(1) negation and prove zero-sum balance
```

```
# ------------------------------------------------------------------------------
[ ROLL 5 ] : [ Rail Swap Calculate ] : [ ALU ] :
    [ Positive Rail <=> Negative Rail ] <=> CALCULATE [ 0 ] = [ Equilibrium` ]
    ( Execute O(1) SIMD rail swap negation and affirm zero-sum balance )

# ------------------------------------------------------------------------------
# ROLL 6: REVERSIBLE CALL-RESPONSE EMISSION (INSIDE-OUT EMERGENCE)
# Project computed response outward to Sender completing Call-Response turn
# ------------------------------------------------------------------------------
[ ROLL 6 ] : [ Project Response ] :
    [ Dual Rail Word` } --> PROJECT [ Response Target ] = [ Response` ]
    ( Project computed response to Sender completing Call-Response turn )

# ------------------------------------------------------------------------------
# ROLL 7: SEQUENCE TRANSITION (RANK 4 INSIDE-OUT ASYMMETRIC EMERGENCE)
# Chain discrete response outward toward continuous Vector sequence
# ------------------------------------------------------------------------------
[ ROLL 7 ] : [ Sequence ] :
    [ Response` } --> SEQUENCE [ Vector ] = [ Vector` ]
    ( Chain discrete response outward into continuous vector sequence )

# ------------------------------------------------------------------------------
# ROLL 8: COMMIT STATUS & FOURFOLD STATE MACHINE
# Affirm covenant execution across causal time advancement, await, halt,
# and rollback
# ------------------------------------------------------------------------------
[ ROLL 8 ] : [ Commit Status ] : [
    # +1: PROCEED (+t: Advance forward along the causal tape)
    { [ Verify ] = PROCEED } & { [ Tripwire ] = ARMED }
        --> [ +1:PROCEED ] |

    #  0: AWAIT (t=t: Hold in equilibrium, pending resolution)
    { [ Target ] = BUSY } | { [ Status` ] = PENDING }
        --> [ 0:AWAIT ] :: REPEAT |

    # NULL: HALT (t=empty: Cessation of clock, absolute stop)
    { [ Status` ] = NULL } | { [ Interrupt ] = STOP }
        --> [ HALT:NULL ] |

    # -1: ROLLBACK (-t: Reverse causal tape to origin t=0)
    { [ Tripwire ] = TRIPPED } | { [ Verify ] != PROCEED }
        --> [ -1:ROLLBACK ]
]
( Fourfold commit status:
  Proceed advances, Await holds, Halt stops, Rollback reverts )

# ==============================================================================
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/number/compiled/number.omni

OMNI | 394 LINES | 2594 WORDS | 21.0 KB

```
# ============================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Type: < Idea { Type } : Number > )
# ============================================================================
# ARCHITECTURAL TOPOLOGY:
#   Compiled Source Reel (.omni) establishing immutable mathematical laws
#   and invariant structural proofs for scalar measure and ternary numbers.
#   - Base Block: Primitive Invariant Type
#   - Category: Idea { Type }
#   - Footprint: [ 1 Memory Word ] { 32 Balanced Trits / 64 Bits Native }
#   - Base Level: [ 1 Byte ] { 8 Bits } shared with Character
#   - Dual-Rail Polar Bit-Planes: 00=0 (Equilibrium), 01=+1, 10=-1, 11=Trap
#   - Kinematic Topologies: 2-1-2-1-2, 1-2-1-2-2, 2-2-1-2-1, 2-2-2-2
#   - 3-Space Minimum: 3-3-2, 3-2-3, 2-3-3 (Direction/magnitude Z-axis)
#   - Call-Response Dynamics: Operator <-> Machine Reversible Invariant
#   - Invariant Law: { Number } = [ Enclosed ]: TRUE (Strict single word)
# ============================================================================

# ----------------------------------------------------------------------------
# 1. MODULE MANIFEST: LEXICON MODULE SPECIFICATION & PROVENANCE
# ----------------------------------------------------------------------------
= [Module]: < Lexicon { Types of Ideas } > & [ Noun { Number } ]
    ( This is the Module for the Lexicon - Ideas (Type): Numbers - Nouns )
{
    [ Version ]:   { "1.0.0" }
        ( The Version is in the context of 1.0.0 ),

    [ Created ]:   { "2026-10-11" }
        ( Created in the context of October 11, 2026 ),

    [ Updated ]:   { "2026-10-15" }
        ( Last updated in the context of October 15, 2026 ),

    [ Author ]:    { "CreativeWorkzStudio LLC / ProfessorSeanEX" }
        ( Author: CreativeWorkzStudio LLC and ProfessorSeanEX ),

    [ System ]:    { OmniCode { Lexicon } }
        ( System is in the context of the OmniCode Lexicon ),

    [ Witness ]:   < Scripture { Psalm 147:4 KJV } >
        { "He telleth the number of the stars;"
          " he calleth them all by their names." }
        ( Invariant Witness Psalm 147:4: He telleth the number of the stars ),

    [ Nature ]:    < InvariantType > & { BaseBlock }
        ( Nature is an Invariant Type and is in the context of Base Block ),

    [ Semantics ]: { ScalarQuantity :: NumericWord :: BalancedTernaryALU }
        ( Semantics: Scalar Quantity, Numeric Word, and Balanced Ternary ALU )
}

# ----------------------------------------------------------------------------
# 2. FREESTANDING INVARIANT TYPE DEFINITION: SCALAR QUANTITY SPECIFICATION
# ----------------------------------------------------------------------------
< Number > = < Idea { Type } > & [ Noun { Scalar Quantity } ]
    ( Number is the Invariant Idea of Type, and is the Noun of Scalar Quantity )
{
    # ------------------------------------------------------------------------
    # 1. The Ontological Analogy (Number's proportion to the universe)
    # ------------------------------------------------------------------------
    [ Relation ]: [ Number ] : [ Measure ] :: [ Trit ] : [ Magnitude ]
        ( Number is to Measure as Trit is to Magnitude ),

    # ------------------------------------------------------------------------
    # 2. The Universal Domain (All balanced trits, integers, and scalars)
    # ------------------------------------------------------------------------
    [ Domain ]: { Trit :: Integer :: Scalar :: Magnitude }
        ( Domain encompasses all balanced trits, integers, and magnitudes ),

    # ------------------------------------------------------------------------
    # 3. The Dual Substrate (Physical Silicon Scalar and Virtual Trit Word)
    # ------------------------------------------------------------------------
    [ Substrate ]: [ 1 Scalar { 64 Bits } ] & [ 1 Memory Word { 32 Trits } ]
```

```
        ( Substrate is 1 Scalar of 64 Bits, and is 1 Memory Word of 32 Trits ),

    # ------------------------------------------------------------------------
    # 4. Elemental Base Level Shared With Character (The 8-Bit Byte Base)
    # ------------------------------------------------------------------------
    [ Base ]: [ 1 Byte { 8 Bits } ] & [ Shared Substrate { Character } ]
        ( Number and Character share elemental 8-bit byte base in silicon ),

    # ------------------------------------------------------------------------
    # 5. Dual-Rail Polar Bit-Planes (00=0, 01=+1, 10=-1, 11=Collision Trap)
    # ------------------------------------------------------------------------
    [ Rails ]: {
        00 <=> [ 0 ] ::
        01 <=> [ +1 ] ::
        10 <=> [ -1 ] ::
        11 <=> [ NULL ]
    }
        ( Dual-rail polar bit-planes encode equilibrium, rails, and traps ),

    # ------------------------------------------------------------------------
    # 6. Polar Rail Decomposition (Bit 1 is Sign Rail, Bit 0 is Value Rail)
    # ------------------------------------------------------------------------
    [ Polar Rails ]: [ Bit Pair { Negative Rail :: Positive Rail } ]
        ( Rail decomposition: bit 1 is negative rail and bit 0 is positive ),

    # ------------------------------------------------------------------------
    # 7. Kinematic Bit-Packing Topologies (Dynamic Carry & Storage Patterns)
    # ------------------------------------------------------------------------
    [ Topology ]: {
        [ 2-1-2-1-2 ] ::
        [ 1-2-1-2-2 ] ::
        [ 2-2-1-2-1 ] ::
        [ 2-2-2-2 ]
    }
        ( Kinematic carry topologies for equilibrium, prefix, and dense modes ),

    # ------------------------------------------------------------------------
    # 8. 3-Space Minimum Partitions (Z-Axis Direction & Magnitude Fields)
    # ------------------------------------------------------------------------
    [ Spaces ]: { [ 3-3-2 ] :: [ 3-2-3 ] :: [ 2-3-3 ] }
        ( 3-space minimum partition computing direction with Z-axis ),

    # ------------------------------------------------------------------------
    # 9. Reversible Call-Response Dynamics (Operator <-> Machine Symmetry)
    # ------------------------------------------------------------------------
    [ Call Response ]: [ Caller { Input } ] <=> [ Sender { Output } ]
        ( Symmetric Call-Response model reversible between Operator/Machine ),

    # ------------------------------------------------------------------------
    # 10. Reversible SIMD Rail-Swap Inversion Law (O(1) Polar Negation)
    # ------------------------------------------------------------------------
    [ Negate ]: [ Negative Rail <=> Positive Rail ]
        ( Swapping negative and positive rails inverts sign in O(1) time ),

    # ------------------------------------------------------------------------
    # 11. Zero Collision & Tripwire Sentinel Law (Trap Code 11)
    # ------------------------------------------------------------------------
    [ Sentinel ]: [ 11 ] ! TRAP --> [ ROLLBACK ]
        ( Simultaneous rail activation triggers fatal collision tripwire ),

    # ------------------------------------------------------------------------
    # 12. The Universal Inscription Vector (Recording scalar into memory)
    # ------------------------------------------------------------------------
    [ Inscribe ]: [ Quantity ] --> [ Number ]
        ( Any scalar quantity is inscribed into the Number word ),

    # ------------------------------------------------------------------------
    # 13. The Hardware Transduction Law (Bijective mapping: bits <=> trits)
    # ------------------------------------------------------------------------
    [ Transduce ]: [ Number { 64 Bits } ] <=> [ Memory Word { 32 Trits } ]
        ( Integer values map bijectively into balanced trits in the word ),

    # ------------------------------------------------------------------------
    # 14. Core Arithmetic Equilibrium Law (Foundational zero-sum balance)
    # ------------------------------------------------------------------------
    [ Law { Equilibrium } ]: [ (+1) plus (-1) <=> [ 0 ] ]
        ( Positive unity plus negative unity equals zero-sum equilibrium ),

```

```
    # ------------------------------------------------------------------------
    # 15. Canonical Exemplars (Grounding values for zero, unities, partition)
    # ------------------------------------------------------------------------
    [ Exemplar { Zero } ]: "0" <=> [ 0 ]
        ( Canonical zero represents perfect balance and null displacement ),
    [ Exemplar { Unity Positive } ]: (+1) <=> [ +1 ]
        ( Positive unity represents forward causal affirmation ),
    [ Exemplar { Unity Negative } ]: (-1) <=> [ -1 ]
        ( Negative unity represents backward causal restoration ),
    [ Exemplar { Dual Rail Zero } ]: 0b00 <=> [ 0 ]
        ( 2-bit code 00 maps to zero displacement equilibrium ),
    [ Exemplar { Dual Rail Pos } ]: 0b01 <=> [ +1 ]
        ( 2-bit code 01 maps to positive forward rail unity ),
    [ Exemplar { Dual Rail Neg } ]: 0b10 <=> [ -1 ]
        ( 2-bit code 10 maps to negative backward rail unity ),
    [ Exemplar { Dual Rail Trap } ]: 0b11 <=> [ NULL ]
        ( 2-bit code 11 maps to collision trap circuit breaker ),

    # ------------------------------------------------------------------------
    # 16. The Relational Comparison (Equality evaluation against quantity)
    # ------------------------------------------------------------------------
    [ Compare ]: [ { Number } = { Quantity } ]
        ( Number is evaluated for equality against an input scalar quantity ),

    # ------------------------------------------------------------------------
    # 17. The Sequence Transition (How numbers build multidimensional vectors)
    # ------------------------------------------------------------------------
    [ Sequence ]: [ Number ] --> [ Vector ]
        ( Discrete Number words chain together into Vector coordinates ),

    # ------------------------------------------------------------------------
    # 18. The Invariant Boundary (Strict single-word enclosure)
    # ------------------------------------------------------------------------
    [ Bound ]: { Number } = [ Enclosed ]: TRUE
        ( Number is strictly enclosed within a single memory word capacity )
}

# ============================================================================
# BLOCK 2: OPENING BLOCK
# ============================================================================
Opening {
    # ------------------------------------------------------------------------
    # 1. Dynamic Input Call: Rank 5 Outside-In Imposition from Caller
    # ------------------------------------------------------------------------
    { Call ]: { Input :: 4096 } FROM [ Caller { Operator | Machine } ]
        ( Outside-in imposition: external scalar call from reversible Caller ),

    # ------------------------------------------------------------------------
    # 2. Typed Entity Allocation: Invariant Bound to Concrete Word
    # ------------------------------------------------------------------------
    [ Number ]: < Number > & [ Memory Word ]
        ( Denoted Number is typed as invariant Number allocated in Word ),

    # ------------------------------------------------------------------------
    # 3. Physical Container: The Atomic 32-Trit Memory Word Container
    # ------------------------------------------------------------------------
    [ Memory Word ]: [ 1 Memory Word ] & { 32 Trits <=> 64 Bits }
        ( Concrete 1-word container in context of 32 Trits and 64 Bits ),

    # ------------------------------------------------------------------------
    # 4. Dual-Rail Substrate Planes: Polar Rails Allocation
    # ------------------------------------------------------------------------
    [ Rails ]: [ Negative Rail { 32 Bits } ] & [ Positive Rail { 32 Bits } ]
        ( Dual-rail planes allocate 32 bits negative and 32 bits positive ),

    # ------------------------------------------------------------------------
    # 5. Kinematic Topology Selection: Dynamic Carry & Space Selector
    # ------------------------------------------------------------------------
    [ Topology ]: {
        [ 2-1-2-1-2 ] | [ 1-2-1-2-2 ] | [ 2-2-1-2-1 ] | [ 2-2-2-2 ] | [ 3-3-2 ]
    }
        ( Active packing mode selected for carry channels and Z-axis ),

    # ------------------------------------------------------------------------
    # 6. Hardware Bridge: Arming the Balanced Ternary ALU & Transducer
    # ------------------------------------------------------------------------
    [ ALU ]: { (+1) plus (-1) <=> [ 0 ] } & { 64 Bits <=> 32 Trits }
        ( ALU enforces ternary zero-sum balance and bridges 64 bits to trits ),
```

```
    # ------------------------------------------------------------------------
    # 7. Output Response Target: Reversible Sender Destination
    # ------------------------------------------------------------------------
    [ Response Target ]: [ Sender { Machine | Operator } ] ::@ 0x00000000
        ( Target projects response outward to reversible Sender destination ),

    # ------------------------------------------------------------------------
    # 8. Preconditions & State: Proving Equilibrium and Arming Tripwire
    # ------------------------------------------------------------------------
    [ Preconditions ]: [ (+1) plus (-1) <=> [ 0 ] ] & [ Status = +1:PROCEED ]
        ( ALU equilibrium holds and machine status is armed in Proceed ),

    # ------------------------------------------------------------------------
    # 9. Tripwire Sentinel: Armed for Collision Trap Detection
    # ------------------------------------------------------------------------
    [ Tripwire Sentinel ]: [ Trap { 0b11 } = ARMED ]
        ( Collision tripwire armed against dual-rail short circuits )
}

# ============================================================================
# BLOCK 3: BODY BLOCK
# ============================================================================
Body [
    # ------------------------------------------------------------------------
    # ROLL 1: CALL RECEPTION & QUANTITY INSCRIPTION (OUTSIDE-IN IMPOSITION)
    # Inscribe incoming call payload from Caller into Memory Word
    # ------------------------------------------------------------------------
    [ ROLL 1 ] : [ Inscribe Call ] :
        { Call ] --> INSCRIBE [ Memory Word ] = [ Number` ]
        ( Inscribe external call payload into Word yielding Number-prime ),

    # ------------------------------------------------------------------------
    # ROLL 2: KINEMATIC TOPOLOGY PARTITIONING (3-SPACE DYNAMIC CARRY)
    # Partition Number` across kinematic topology spaces for carry & magnitude
    # ------------------------------------------------------------------------
    [ ROLL 2 ] : [ Kinematic Partition ] :
        [ Number` ] --> PARTITION [ Topology { 2-1-2-1-2 } ] =
        [ Packed Spaces` ]
        ( Partition Number-prime into 3-space carry channels and magnitude ),

    # ------------------------------------------------------------------------
    # ROLL 3: DUAL-RAIL POLAR BIT-PLANE TRANSDUCTION (<=>)
    # Transduce Packed Spaces` into dual-rail planes (00=0, 01=+1, 10=-1)
    # ------------------------------------------------------------------------
    [ ROLL 3 ] : [ Dual Rail Transduce ] : [ ALU ] :
        [ Packed Spaces` { 64 Bits } ] <=> TRANSDUCE
        [ Dual Rail Word` { Rails: 00 <=> [ 0 ] :: 01 <=> [ +1 ] ::
                            10 <=> [ -1 ] } ]
        ( Transduce 64 bits into 32 dual-rail polar trit planes through ALU ),

    # ------------------------------------------------------------------------
    # ROLL 4: COLLISION SENTINEL & BOUND GUARD (ADVERSATIVE CAVEAT VIA `!`)
    # Guard against 11 collision trap and single-word capacity overflow
    # ------------------------------------------------------------------------
    [ ROLL 4 ] : [ Sentinel Guard ] :
        { Dual Rail Word` <= [ 1 Memory Word ] } & { Collision = 0b00 }
        ! GUARD --> [ Status` = +1:PROCEED ]
        | { Collision = 0b11 } --> [ Status` = -1:ROLLBACK ]
        ( Guard against 11 collision trap and single-word overflow:
          proceed on equilibrium, else rollback ),

    # ------------------------------------------------------------------------
    # ROLL 5: REVERSIBLE SIMD RAIL-SWAP & ARITHMETIC EQUILIBRIUM
    # Swap polar rails for O(1) negation and prove zero-sum balance
    # ------------------------------------------------------------------------
    [ ROLL 5 ] : [ Rail Swap Calculate ] : [ ALU ] :
        [ Positive Rail <=> Negative Rail ] <=> CALCULATE [ 0 ] =
        [ Equilibrium` ]
        ( Swap polar rails for O(1) negation and prove arithmetic balance ),

    # ------------------------------------------------------------------------
    # ROLL 6: REVERSIBLE CALL-RESPONSE EMISSION (RANK 4 INSIDE-OUT EMERGENCE)
    # Project computed response outward to Sender completing Call-Response turn
    # ------------------------------------------------------------------------
    [ ROLL 6 ] : [ Project Response ] :
        [ Dual Rail Word` } --> PROJECT [ Response Target ] = [ Response` ]
        ( Project computed response to Sender fulfilling Call-Response turn ),
```

```
    # ------------------------------------------------------------------------
    # ROLL 7: SEQUENCE TRANSITION (RANK 4 INSIDE-OUT EMERGENCE)
    # Chain verified response outward toward continuous Vector sequence
    # ------------------------------------------------------------------------
    [ ROLL 7 ] : [ Sequence ] :
        [ Response` } --> SEQUENCE [ Vector ] = [ Vector` ]
        ( Yield verified response to Vector sequence establishing Vector-prime )
]

# ============================================================================
# BLOCK 4: CLOSING BLOCK
# ============================================================================
Closing
    ( Sealing Gate: Validate, tripwire, debug, log, and affirm execution )
{
    # ------------------------------------------------------------------------
    # 1. VERIFICATION OF OPERATIONAL ROLLS
    # ------------------------------------------------------------------------
    [ Verify ]: [
        [ ROLL 1 ] = PROCEED ::
        [ ROLL 2 ] = PROCEED ::
        [ ROLL 3 ] = PROCEED ::
        [ ROLL 4 ] = PROCEED ::
        [ ROLL 5 ] = PROCEED ::
        [ ROLL 6 ] = PROCEED ::
        [ ROLL 7 ] = PROCEED
    ]
    ( Verify all seven operational rolls achieved affirmative PROCEED ),

    # ------------------------------------------------------------------------
    # 2. VALIDATION OF INVARIANT BOUNDS & DUAL-SUBSTRATE PARITY
    # ------------------------------------------------------------------------
    [ Validate ]:
        { Response` <= [ 1 Memory Word ] } & { [ 64 Bits ] <=> [ 32 Trits ] }
        ( Validate single-word enclosure and bit-trit substrate parity holds ),

    # ------------------------------------------------------------------------
    # 3. ZERO-TOLERANCE TRIPWIRING: DUAL-RAIL COLLISION CIRCUIT BREAKER
    # ------------------------------------------------------------------------
    [ Tripwire ]:
        { Collision = 0b11 } --> [ TRIPPED ]
            --> [ Commit Status = -1:ROLLBACK ]
        | { Status` = +1:PROCEED } --> [ ARMED ]
        ( Zero-tolerance tripwire trips on 11 trap or arms in Proceed ),

    # ------------------------------------------------------------------------
    # 4. DIAGNOSTIC DEBUG TELEMETRY: REVERSIBLE SNAPSHOT
    # ------------------------------------------------------------------------
    [ Debug ]:
        { [ Call ] :: [ Packed Spaces` ] :: [ Dual Rail Word` ]
          :: [ Response` ] :: [ Status` ] }
        ( Telemetry across Call, packed spaces, dual-rail planes, and status ),

    # ------------------------------------------------------------------------
    # 5. EPISODIC INVENTORY LOGGING: CALL-RESPONSE RECORD
    # ------------------------------------------------------------------------
    [ Log ]: [ Journal ]:
        INSCRIBE { [ Call Inscribed ] :: [ Response` ] :: [ Topology ] }
        ( Inscribe verified Call-Response transaction into permanent journal ),

    # ------------------------------------------------------------------------
    # 6. PERMANENT COVENANT EXECUTION & FOURFOLD COMMIT STATUS LOOP
    # ------------------------------------------------------------------------
    [ Commit Status ]: [
        # +1: PROCEED (+t: Advance forward along the causal tape)
        { [ Verify ] = PROCEED } & { [ Tripwire ] = ARMED }
            --> [ +1:PROCEED ] |

        #  0: AWAIT (t=t: Hold in equilibrium, pending resolution)
        { [ Response Target ] = BUSY } | { [ Status` ] = PENDING }
            --> [ 0:AWAIT ] :: REPEAT |

        # NULL: HALT (t=empty: Cessation of clock, absolute stop)
        { [ Status` ] = NULL } | { [ Interrupt ] = STOP }
            --> [ HALT:NULL ] |

        # -1: ROLLBACK (-t: Reverse causal tape to origin t=0)
```

```
        { [ Tripwire ] = TRIPPED } | { [ Verify ] != PROCEED }
            --> [ -1:ROLLBACK ]
    ]
    ( Fourfold state machine:
      Proceed advances, Await holds, Halt stops, Rollback reverts )
}

# ================================================================================
```

OmniCode: Chapter 13: Track 2 - Lexicon: State, Container, Site & Text

Quad-State T4 Clock, Memory Envelopes & Bounded Sites

CHAPTER IDENTIFIER	**NOTEBOOKLM WORD COUNT**
CH 13	42,251 words
CATALOGED CHAPTER FILES	**GENERATION DATE**
56 files (8,489 lines)	2026-10-16 20:36:05

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"How do IT, BOUND, and TURN govern canonical loop cadence?"*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (56 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/README.md**	MD	159	1,053	8.0
2	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/container.omni**	OMNI	192	1,812	12.3
3	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/container.tape**	TAPE	89	772	5.4
4	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/site.omni**	OMNI	190	1,818	12.2
5	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/site.tape**	TAPE	89	763	5.3
6	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/state.omni**	OMNI	230	2,189	14.4
7	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/state.tape**	TAPE	117	949	6.7
8	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/text.omni**	OMNI	62	249	2.2
9	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/text.tape**	TAPE	33	210	1.6
10	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/compile_flags.txt**	TXT	5	4	0.0
11	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/number.o**	O	1	5	9.0
12	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/include/character.h**	H	300	1,795	13.1
13	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/include/container.h**	H	222	1,078	9.0
14	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/include/number.h**	H	385	1,953	15.1
15	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/include/omni.h**	H	27	136	1.1
16	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/include/omni_base.h**	H	289	1,270	10.6
17	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/include/site.h**	H	191	925	7.4
18	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/include/state.h**	H	170	863	7.1
19	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/src/character.c**	C	278	1,241	10.5
20	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/src/container.c**	C	236	997	8.5
21	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/src/number.c**	C	436	1,735	15.0
22	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/src/site.c**	C	168	735	6.2
23	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/src/state.c**	C	174	766	6.3
24	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/lua_tapes/character.lua**	LUA	149	579	5.9
25	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/lua_tapes/container.lua**	LUA	158	632	6.5

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
26	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/lua_tapes/number.lua**	LUA	342	1,731	14.8
27	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/lua_tapes/site.lua**	LUA	148	565	6.0
28	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/lua_tapes/state.lua**	LUA	183	697	7.1
29	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/lua_tapes/tape_engine.lua**	LUA	223	957	8.6
30	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/lua/integrated/test_omni_lib.lua**	LUA	152	634	7.0
31	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/lua/unit/test_character.lua**	LUA	89	437	4.1
32	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/lua/unit/test_common.lua**	LUA	49	188	1.7
33	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/lua/unit/test_container.lua**	LUA	79	397	3.7
34	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/lua/unit/test_number.lua**	LUA	197	851	8.4
35	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/lua/unit/test_site.lua**	LUA	82	379	3.8
36	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/lua/unit/test_state.lua**	LUA	93	439	4.2
37	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/compile_flags.txt**	TXT	6	5	0.1
38	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/test_number.o**	O	1	5	21.8
39	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/integrated/test_omni_lib.c**	C	121	492	5.5
40	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/includes/test_common.h**	H	65	248	2.3
41	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/unit/test_character.c**	C	121	599	5.8
42	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/unit/test_container.c**	C	145	670	6.5
43	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/unit/test_number.c**	C	244	1,146	11.1
44	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/unit/test_site.c**	C	120	556	5.5
45	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/unit/test_state.c**	C	119	606	5.6
46	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/README.md**	MD	149	953	6.4
47	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/interpreted/lua/tape_engine.lua**	LUA	368	1,404	12.5
48	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/interpreted/lua/tests/test_common.lua**	LUA	51	185	1.7

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
49	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/interpreted/lua/tests/test_tape_engine.lua**	LUA	248	798	9.3
50	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/compiled/c/Makefile**	TEXT	17	33	0.3
51	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/compiled/c/compile_flags.txt**	TXT	6	5	0.0
52	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/compiled/c/test_universal_bin**	TEXT	1	5	25.0
53	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/compiled/c/tests/test_common.h**	H	59	213	1.7
54	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/compiled/c/tests/test_universal.c**	C	213	781	9.8
55	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/compiled/c/include/omni.h**	H	45	176	1.4
56	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/compiled/c/include/omni_base.h**	H	403	1,567	14.5

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/README.md | MD | 159 LINES | 1053 WORDS | 8.0 KB

```
# OmniCode Invariant Types: Architectural Taxonomy & Guide

Welcome to the **OmniCode Types System**! Whether you are a systems programmer, language enthusiast, philosopher, or someone completely new to computing, this guide explains how OmniCode models the building blocks of thought, language, and reality.

---

## 1. What is an "Idea { Type }" in OmniCode?

In conventional programming languages, a "type" is often just a technical label telling a compiler how many bytes of memory to reserve (like `int`, `char`, or `float`).

In **OmniCode**, a Type is fundamentally an **Idea**:

- It represents an **ontological invariant**—a universal concept that holds true regardless of what machine, operating system, or silicon chip executes it.
- It unites three worlds:
  1. **Pure Meaning (Semantics):** What the concept means in human thought, natural language, and philosophy.
  2. **Mathematical Balance (Virtual Substrate):** Symmetrical balanced ternary logic (`-1`, `0`, `+1`), where truth is dynamic equilibrium.
  3. **Physical Silicon (Hardware Target):** Concrete execution on modern 64-bit microprocessors, memory registers, and video terminals.

---

## 2. Core Concepts: Learning the OmniCode Way

### Words vs. Values, States vs. Numbers

One of the most profound breakthroughs in OmniCode is understanding that values, words, and states share the same symbols, but differ in human intent:

- **`0` as a State:** Represents **`AWAIT`**—a state of perfect equilibrium, resting quietly, waiting for the next event.
- **`"0"` as a Value:** Using literal "air-quotes" (or enclosing brackets like `{ 0 }` or `[ 0 ]`) tells the machine: *"Treat this zero not as a pause state, but as the literal mathematical quantity zero."*
- **`'AWAIT'` as a Word:** Single quotes clarify that a reserved keyword is being spoken of as a literal word rather than being triggered as a command.

Because OmniCode is a **freestanding language** designed to communicate with hardware without hidden assumptions, it reads all symbols literally. You provide the semantics that express your true intent.

### The Analogy of the Body: "Fleshing Out the Bones"

OmniCode grows organically, mirroring how a living organism develops:

1. **The Skeleton:** We first build the rigid architectural bones—the invariant laws, mathematical boundaries, and fundamental categories.
2. **The Tissue:** We link the bones together using the **ladder.baton** system, connecting universal roots to specialized types.
3. **The Flesh:** We add dynamic features, transpilers, runtime engines, and tests.
4. **Shaping & Refining:** We continually test, reshape, and harmonize all parts so the entire system breathes together across all tracks.

---


## 3. The `ladder.baton` Inheritance System

In traditional software projects, shared code is frequently copy-pasted across folders, leading to loose, duplicate files that easily get out of sync.

In OmniCode, we use the **`ladder.baton` system**:

- The **Universal Root** (`universal/`) holds the core axioms: balanced ternary math, the four causal states, connective conjunctions, and safety interlocks.
- Downstream types (like `character/` and `number/`) **inherit** these universal invariants down the ladder like a baton passed in a relay race.
- **Zero Duplicate Files:** Individual type folders contain only what is unique to their type. Universal invariants are passed down via clean module paths and compiler include flags.

```text
                    ┌──────────────────────┐
                    │       universal/     │  <-- Ground Truth / Axioms
```
```



---

4. The Three-Pillar Modular Folder Structure

Every type folder in OmniCode is organized into three complementary expressions:

```bash
<type>/
├── compiled/           # 1. High-Level Source Reel (.omni)
├── interpreted/        # 2. Runtime Execution Ribbon (.tape)
└── transpiled/         # 3. Concrete Physical Bridges
    ├── compiled/c/     #    - Freestanding Bare-Metal C Backbone
    └── interpreted/lua/#    - Dynamic Coroutine Ribbon Companion
```

Pillar 1: `compiled/` (`<type>.omni`)

The high-level declaration of the type. Written in canonical OmniCode notation, it reads like structured, elegant prose. It defines the type's metadata, biblical/philosophical witness, capacity footprint, and four-block lifecycle laws.

Pillar 2: `interpreted/` (`<type>.tape`)

The dynamic interpreted process ribbon. Think of this like a physical strip of celluloid movie film or a Turing tape. It breaks execution down into sequential **rolls** (Inscribe, Transduce, Compare, Equilibrium, Sequence) that step forward smoothly or roll back safely if an error occurs.

Pillar 3: `transpiled/` (Physical Language Bridges)

To allow OmniCode to run on any computer in the world today, OmniCode transpiles automatically into physical targets:

- **`compiled/c/`**: A pure, freestanding C99/C11 implementation. Contains `include/`, `src/`, `tests/`, and a `Makefile`. It requires zero third-party libraries and can run directly on bare metal (even booting on an x86 CPU without an operating system!).
- **`interpreted/lua/`**: A lightweight, embeddable Lua implementation. Uses Lua coroutines to step through tape rolls as cooperative fibers, with automatic state snapshotting and rollback.

---

5. Overview of Current Types

Type Directory	Capacity & Footprint	Primary Role	Philosophical Witness
`universal/`	Foundation Substrate	Balanced Ternary ALU, Quad-State Truth, Connectives	Proverbs 11:1 & 24:27
`character/`	1 Cell (5 Trits / 8 Bits)	Atomic glyphs, letters, terminal inscription runes	Exodus 31:18
`number/`	1 Word (32 Trits / 64 Bits)	Scalar quantities, balanced arithmetic, zero-sum ALU	Psalm 147:4
`container/`	Variable Bounded Space	Envelopes, memory partitions, bounded buffers	*(In transition)*
`site/`	Memory Coordinates	Memory-mapped I/O, physical RAM locations	*(In transition)*
`state/`	Causal Status Register	Fourfold causal detents, program loop steppers	*(In transition)*

---

6. How to Test & Explore

OmniCode enforces a strict **"Test First, Integrate Second"** methodology. You can run unit tests at any level:

Universal Bedrock Tests

```bash
# Test universal C axioms & ALU
cd universal/transpiled/compiled/c && make test

# Test universal Lua tape engine
lua universal/transpiled/interpreted/lua/tests/test_tape_engine.lua
```

````
### Character Type Tests

```bash
# Test character C backbone
cd character/transpiled/compiled/c && make test

# Test character Lua tape ribbon
lua character/transpiled/interpreted/lua/tests/test_character.lua
```

### Number Type Tests

```bash
# Test number C backbone
cd number/transpiled/compiled/c && make test

# Test number Lua tape ribbon
lua number/transpiled/interpreted/lua/tests/test_number.lua
```

### Full Host Engine (Rust) Verification

From the repository root:

```bash
cargo test --manifest-path "<TRACK 1> : {Host Engine & Virtual Machine}/Cargo.toml"
```

*(Confirms that all 252 host VM tests pass across every component).*
````

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/container.omni

OMNI | 192 LINES | 1812 WORDS | 12.3 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Type: < Idea { Type } : Container > )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines bounded memory envelopes, arrays, structures, and storage vessels.
#   - Base Block: Primitive Invariant Type
#   - Category: Idea { Type }
#   - Footprint: [ 64 Cells ] { 64 Bytes / Dynamically Bounded Memory Space }
#   - Ladder Ascension: Build-up with Numbers (/-^)
# ========================================================================

= [Module]: < Lexicon { Types of Ideas } > & [ Noun { Container } ] ( This is the Module for the Lexicon - Ideas (Type): Containers - Nouns ) {
    [ Version ]:   { "1.0.0" } ( The Version is in the context of 1.0.0 ),
    [ Created ]:   { "2026-10-11" } ( Created in the context of October 11, 2026 ),
    [ Updated ]:   { "2026-10-12" } ( Last updated in the context of October 12, 2026 ),
    [ Author ]:    { "CreativeWorkzStudio LLC / ProfessorSeanEX" } ( Author in the context of CreativeWorkzStudio LLC and ProfessorSeanEX ),
    [ System ]:    { OmniCode { Lexicon } } ( System is in the context of the OmniCode Lexicon ),
    [ Witness ]:   < Scripture { 2 Kings 4:4 KJV } > { "And when thou art come in, thou shalt shut the door upon thee and upon thy sons, and shalt pour out into all those vessels, and thou shalt set aside that which is full." } ( Invariant Scripture Witness 2 Kings 4:4 in the context: Pour out into all those vessels, and set aside that which is full ),
    [ Nature ]:    < InvariantType > & { BaseBlock } ( Nature is an Invariant Type and is in the context of Base Block ),
    [ Semantics ]: { BoundedEnvelope :: StorageVessel :: MemoryCapsule } ( Semantics in the context of Bounded Envelope, Storage Vessel, and Memory Capsule )
}

# ------------------------------------------------------------------------
# LADDER ASCENSION: BUILD-UP WITH NUMBERS
# A Container cannot exist without numbers: capacity, indices, bounds, and cells
# are constructed out of scalar quantities passed up the ontological ladder.
# ------------------------------------------------------------------------
/-^ < Numbers > FROM [ < Lexicon { Types of Ideas } > & [ Noun { Number } ] ] ( Container builds up its boundaries, capacity, and cells using Numbers from the Lexicon )

# Freestanding Invariant Type Definition
< Container > = < Idea { Type } > & [ Noun { Bounded Space } ] ( Container is the Invariant Idea of Type, and is the Noun of Bounded Space ) {
    # 1. The Ontological Analogy (Container's proportion to the universe)
    [ Relation ]: [ Container ] : [ Vessel ] :: [ Boundary ] : [ Capacity ] ( Container is to Vessel as Boundary is to Capacity ),

    # 2. The Universal Domain (All vessels, storehouses, partitions, and memory capsules)
    [ Domain ]: { Vessel :: Storehouse :: Partition :: Capsule } ( Domain encompasses vessels, storehouses, partitions, and memory capsules ),

    # 3. The Physical Substrate (Concrete bounded capacity in silicon)
    [ Substrate ]: [ 64 Cells { 64 Bytes } ] & [ Bounded Space ] ( Substrate is 64 Cells of 64 Bytes, and is Bounded Space ),

    # 4. The Universal Inscription Vector (How external payload is encapsulated into memory)
    [ Inscribe ]: [ Payload ] --> [ Container ] ( Any memory payload is inscribed into the bounded Container envelope ),

    # 5. The Hardware Enclosure Law (Memory is physically bounded by allocated capacity)
    [ Enclose ]: ENCLOSE [ Storage ] WITHIN [ Capacity ] ( Storage is strictly enclosed within the declared capacity ),

    # 6. The Core Containment Law (Occupancy must never exceed capacity limit)
    [ Law { Containment } ]: { Occupancy <= Capacity } ( The law of containment requires that occupancy never exceeds bounded capacity ),

    # 7. Canonical Exemplars (Standard grounding values for partitions, vessels, and storehouses)
    [ Exemplar { Unit } ]: [ 1 ] <=> [ Partition { 1 Cell } ] ( Canonical single unit partition ),
    [ Exemplar { Vessel } ]: [ 64 ] <=> [ Vessel { 64 Cells } ] ( Canonical vessel exemplar bounded at 64 memory cells ),
    [ Exemplar { Storehouse } ]: [ 4096 ] <=> [ Storehouse { 4096 Cells } ] ( Canonical storehouse exemplar bounded at 4096 memory cells ),

    # 8. The Relational Comparison (How containers evaluate occupancy against capacity limit)
    [ Compare ]: [ { Occupancy } <= { Capacity } ] ( Container evaluates occupancy for containment within capacity limit ),

    # 9. The Sequence Transition (How containers chain into composite data structures)
    [ Sequence ]: [ Container ] --> [ Structure ] ( Discrete containers chain together into composite memory structures
```

```
),

    # 10. The Invariant Boundary (Strict capacity enclosure)
    [ Bound ]: ENCLOSE [ Storage ] WITHIN [ Capacity ] ( Container strictly encloses its storage within capacity )
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    # 1. The Dynamic Input Payload: Accepts incoming memory payload
    { Payload ]: { Input :: [ 64 Bytes ] } ( Outside-in imposition: external memory payload to be encapsulated ),

    # 2. The Typed Entity: Container brought down from Block 1 into concrete allocation
    [ Container ]: < Container > & [ Vessel ] ( Denoted Container is typed as invariant Container allocated as a Vessel
),

    # 3. The Physical Envelope: The bounded space built up with numbers
    [ Bounded Space ]: [ 64 Cells ] & { Capacity = 64 } ( A concrete 64-cell bounded envelope built up with Numbers ),

    # 4. The Encapsulation Guard: Verifying containment limits
    [ Guard ]: { Occupancy <= Capacity } & { Door = SHUT } ( The guard enforces bounds limit and shuts the door when full
),

    # 5. The Output Target: Physical memory offset location
    [ Target ]: [ Storage Envelope ] ::@ 0x00000000 ( Target output is situated at the base storage envelope memory
offset ),

    # 6. Preconditions & State: Proving room before filling
    [ Preconditions ]: [ Capacity > 0 ] & [ Status = +1:PROCEED ] ( Capacity is positive and the machine status is armed
in Proceed )
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # --------------------------------------------------------------------------
    # ROLL 1: BUILD CAPSULE (LADDER BUILD-UP)
    # Build up concrete vessel envelope with 64 numeric cells yielding new state Vessel`
    # --------------------------------------------------------------------------
    [ ROLL 1 ] : [ Build Capsule ] : /-^ [ 64 Cells ] --> [ Envelope ] = [ Vessel` ]
        ( Build up concrete vessel envelope with 64 numeric cells yielding new state Vessel-prime ),

    # --------------------------------------------------------------------------
    # ROLL 2: ENCAPSULATION (OUTSIDE-IN IMPOSITION)
    # Encapsulate external payload imposed into Vessel yielding new state Container`
    # --------------------------------------------------------------------------
    [ ROLL 2 ] : [ Encapsulate ] : { Payload ] --> ENCAPSULATE [ Vessel` ] = [ Container` ]
        ( Encapsulate external payload imposed into Vessel yielding new state Container-prime ),

    # --------------------------------------------------------------------------
    # ROLL 3: IDENTITY & BOUND COMPARISON
    # Compare occupancy to capacity under guard: proceed when contained, rollback on overflow
    # --------------------------------------------------------------------------
    [ ROLL 3 ] : [ Guard Bounds ] :
        { Occupancy` <= Capacity } & { Container` = Vessel` }
        ! GUARD --> [ Status` = +1:PROCEED ]
        | { Occupancy` > Capacity } --> [ Status` = -1:ROLLBACK ]
        ( Compare occupancy to capacity under guard: proceed when contained, rollback on overflow ),

    # --------------------------------------------------------------------------
    # ROLL 4: POUR OUT & SET ASIDE (INSIDE-OUT EMERGENCE)
    # Inside-out emergence: full container is poured out and set aside at target destination
    # --------------------------------------------------------------------------
    [ ROLL 4 ] : [ Pour Out ] : [ Container` } --> SET_ASIDE [ Target ] = [ Sealed Vessel` ]
        ( Inside-out emergence: full container is poured out and set aside at target destination establishing new state
Sealed Vessel-prime ),

    # --------------------------------------------------------------------------
    # ROLL 5: SEQUENCE TRANSITION
    # Chain discrete container outward into composite memory structure sequence
    # --------------------------------------------------------------------------
    [ ROLL 5 ] : [ Sequence ] : [ Container` ] --> SEQUENCE [ Structure ] = [ Structure` ]
        ( Discrete container chains outward into composite memory structure establishing new state Structure-prime )
]

# ================================================================================
```

```
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing ( Sealing Gate: Reconcile, validate, tripwire, debug, log, and affirm permanent execution ) {
    # ------------------------------------------------------------------------
    # 1. VERIFICATION OF OPERATIONAL ROLLS
    # ------------------------------------------------------------------------
    [ Verify ]: [
        [ ROLL 1 ] = PROCEED ::
        [ ROLL 2 ] = PROCEED ::
        [ ROLL 3 ] = PROCEED ::
        [ ROLL 4 ] = PROCEED ::
        [ ROLL 5 ] = PROCEED
    ] ( Verify that all five operational rolls achieved affirmative consensus in PROCEED ),

    # ------------------------------------------------------------------------
    # 2. VALIDATION OF INVARIANT BOUNDS & CONTAINMENT INTEGRITY
    # ------------------------------------------------------------------------
    [ Validate ]: { Occupancy` <= Capacity } & { Door = SHUT }
        ( Validate that occupancy remains strictly within capacity and door is shut upon completion ),

    # ------------------------------------------------------------------------
    # 3. ZERO-TOLERANCE TRIPWIRING
    # ------------------------------------------------------------------------
    [ Tripwire ]: { Status` = +1:PROCEED } --> [ ARMED ] | { Status` != +1:PROCEED } --> [ TRIPPED ] --> [ Commit Status
= -1:ROLLBACK ]
        ( Tripwire remains armed in Proceed or trips on anomaly to veto execution ),

    # ------------------------------------------------------------------------
    # 4. DIAGNOSTIC DEBUG TELEMETRY
    # ------------------------------------------------------------------------
    [ Debug ]: { [ Payload ] :: [ Container` ] :: [ Occupancy` ] :: [ Target ] :: [ Status` ] }
        ( Expose diagnostic telemetry across input payload, container envelope, occupancy, and machine status ),

    # ------------------------------------------------------------------------
    # 5. EPISODIC INVENTORY LOGGING
    # ------------------------------------------------------------------------
    [ Log ]: [ Journal ]: INSCRIBE { [ Container Encapsulated ] :: [ Container` ] :: [ Target ] }
        ( Inscribe the verified container transaction into the permanent episodic system journal ),

    # ------------------------------------------------------------------------
    # 6. PERMANENT COVENANT EXECUTION & FOURFOLD COMMIT STATUS LOOP
    # ------------------------------------------------------------------------
    [ Commit Status ]: [
        # +1: PROCEED (+t: Advance forward along the causal tape)
        { [ Verify ] = PROCEED } & { [ Tripwire ] = ARMED }
            --> [ +1:PROCEED ] |

        #  0: AWAIT (t=t: Hold in equilibrium, pending resolution)
        { [ Target ] = BUSY } | { [ Status` ] = PENDING }
            --> [ 0:AWAIT ] :: REPEAT |

        # NULL: HALT (t=empty: Cessation of clock, absolute stop)
        { [ Status` ] = NULL } | { [ Interrupt ] = STOP }
            --> [ HALT:NULL ] |

        # -1: ROLLBACK (-t: Reverse causal tape to origin t=0)
        { [ Tripwire ] = TRIPPED } | { [ Verify ] != PROCEED }
            --> [ -1:ROLLBACK ]
    ] ( Fourfold state machine: Proceed advances forward, Await holds equilibrium, Halt ceases execution in Null,
Rollback reverts to origin )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/container.tape

TAPE | 89 LINES | 772 WORDS | 5.4 KB

```
# ================================================================================
# PROCESS TAPE: CONTAINER INVARIANT TYPE EXECUTION RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Interprets and executes the atomic lifecycle for Invariant Type < Container >.
#   - Defined Space: [ 64 Cells ] { 64 Bytes / Bounded Memory Space }
#   - Execution Domain: Lexicon { Types of Ideas }
#   - Ladder Ascension: Build-up with Numbers (/-^)
# ================================================================================

= [Tape]: < Lexicon { Types of Ideas } > & [ Process { Container } ] ( Process Ribbon for Container Encapsulation ) {
    WHO   { OmniCode Lexicon } ::
    WHAT  { Container } --> ENCAPSULATE { Payload } ::
    WHEN  { Allocation Event } ::
    WHERE { Container Envelope } = [ 64 Cells ] ::
    WHY   ( Inscribe bounded container type invariant and storage envelopes ) ::
    HOW   [ +1 : PROCEED ] ::
    < Scripture { 2 Kings 4:4 KJV } > { "And when thou art come in, thou shalt shut the door upon thee and upon thy sons, and shalt pour out into all those vessels, and thou shalt set aside that which is full." } ( Invariant Scripture Witness 2 Kings 4:4 in the context: Pour out into all those vessels, and set aside that which is full )
}

# --------------------------------------------------------------------------------
# LADDER ASCENSION: BUILD-UP WITH NUMBERS
# --------------------------------------------------------------------------------
/-^ < Numbers > FROM [ < Lexicon { Types of Ideas } > & [ Noun { Number } ] ] ( Build up container capacity and envelopes using Numbers from the Lexicon )

# ================================================================================
# DECLARED ROLLS: ATOMIC INVARIANT EXECUTION
# ================================================================================

# --------------------------------------------------------------------------------
# ROLL 1: BUILD CAPSULE (LADDER BUILD-UP)
# Build up concrete vessel envelope with 64 numeric cells yielding new state Vessel`
# --------------------------------------------------------------------------------
[ ROLL 1 ] : [ Build Capsule ] : /-^ [ 64 Cells ] --> [ Envelope ] = [ Vessel` ]
    ( Build up concrete vessel envelope with 64 numeric cells yielding new state Vessel-prime )

# --------------------------------------------------------------------------------
# ROLL 2: ENCAPSULATION (OUTSIDE-IN IMPOSITION)
# Encapsulate external payload imposed into Vessel yielding new state Container`
# --------------------------------------------------------------------------------
[ ROLL 2 ] : [ Encapsulate ] : { Payload } --> ENCAPSULATE [ Vessel` ] = [ Container` ]
    ( Encapsulate external payload imposed into Vessel yielding new state Container-prime )

# --------------------------------------------------------------------------------
# ROLL 3: IDENTITY & BOUND COMPARISON
# Compare occupancy to capacity under guard: proceed when contained, rollback on overflow
# --------------------------------------------------------------------------------
[ ROLL 3 ] : [ Guard Bounds ] :
    [ { Occupancy` } <= { Capacity } ] & { Container` = Vessel` }
    ! GUARD --> [ Status` = +1:PROCEED ]
    | [ { Occupancy` } > { Capacity } ] --> [ Status` = -1:ROLLBACK ]
    ( Compare occupancy to capacity under guard: proceed when contained, rollback on overflow )

# --------------------------------------------------------------------------------
# ROLL 4: POUR OUT & SET ASIDE (INSIDE-OUT EMERGENCE)
# Inside-out emergence: full container is poured out and set aside at target destination
# --------------------------------------------------------------------------------
[ ROLL 4 ] : [ Pour Out ] : [ Container` } --> SET_ASIDE [ Target ] = [ Sealed Vessel` ]
    ( Inside-out emergence: full container is poured out and set aside at target destination establishing new state Sealed Vessel-prime )

# --------------------------------------------------------------------------------
# ROLL 5: SEQUENCE TRANSITION
# Chain discrete container outward into composite memory structure sequence
# --------------------------------------------------------------------------------
[ ROLL 5 ] : [ Sequence ] : [ Container` ] --> SEQUENCE [ Structure ] = [ Structure` ]
    ( Discrete container chains outward into composite memory structure establishing new state Structure-prime )

# --------------------------------------------------------------------------------
# ROLL 6: COMMIT STATUS & FOURFOLD STATE MACHINE
```

```
# Affirm covenant execution across causal time advancement, await, halt, and rollback
# ------------------------------------------------------------------------------
[ ROLL 6 ] : [ Commit Status ] : [
    # +1: PROCEED (+t: Advance forward along the causal tape)
    { [ Verify ] = PROCEED } & { [ Tripwire ] = ARMED }
        --> [ +1:PROCEED ] |

    #  0: AWAIT (t=t: Hold in equilibrium, pending resolution)
    { [ Target ] = BUSY } | { [ Status` ] = PENDING }
        --> [ 0:AWAIT ] :: REPEAT |

    # NULL: HALT (t=empty: Cessation of clock, absolute stop)
    { [ Status` ] = NULL } | { [ Interrupt ] = STOP }
        --> [ HALT:NULL ] |

    # -1: ROLLBACK (-t: Reverse causal tape to origin t=0)
    { [ Tripwire ] = TRIPPED } | { [ Verify ] != PROCEED }
        --> [ -1:ROLLBACK ]
] ( Fourfold commit status: Proceed advances forward, Await holds in equilibrium, Halt ceases execution in Null, Rollback
reverts to origin )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/site.omni

OMNI | 190 LINES | 1818 WORDS | 12.2 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Type: < Idea { Type } : Site > )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines physical memory addresses, hardware ports, and MMIO coordinates.
#   - Base Block: Primitive Invariant Type
#   - Category: Idea { Type }
#   - Footprint: [ 1 Address ] { 64-Bit Pointer / Physical Silicon Coordinate }
#   - Ladder Ascension: Build-up with Numbers (/-^)
# ========================================================================

= [Module]: < Lexicon { Types of Ideas } > & [ Noun { Site } ] ( This is the Module for the Lexicon - Ideas (Type): Sites - Nouns ) {
    [ Version ]:   { "1.0.0" } ( The Version is in the context of 1.0.0 ),
    [ Created ]:   { "2026-10-11" } ( Created in the context of October 11, 2026 ),
    [ Updated ]:   { "2026-10-12" } ( Last updated in the context of October 12, 2026 ),
    [ Author ]:    { "CreativeWorkzStudio LLC / ProfessorSeanEX" } ( Author in the context of CreativeWorkzStudio LLC and ProfessorSeanEX ),
    [ System ]:    { OmniCode { Lexicon } } ( System is in the context of the OmniCode Lexicon ),
    [ Witness ]:   < Scripture { Genesis 28:16 KJV } > { "And Jacob awaked out of his sleep, and he said, Surely the Lord is in this place; and I knew it not." } ( Invariant Scripture Witness Genesis 28:16 in the context: Surely the Lord is in this place; and I knew it not ),
    [ Nature ]:    < InvariantType > & { BaseBlock } ( Nature is an Invariant Type and is in the context of Base Block ),
    [ Semantics ]: { PhysicalAddress :: MMIOPort :: SiliconCoordinate } ( Semantics in the context of Physical Address, MMIO Port, and Silicon Coordinate )
}

# ------------------------------------------------------------------------
# LADDER ASCENSION: BUILD-UP WITH NUMBERS
# A Site cannot exist without numbers: silicon memory addresses, offsets,
# and MMIO hardware ports are scalar metrics anchored in reality.
# ------------------------------------------------------------------------
/-^ < Numbers > FROM [ < Lexicon { Types of Ideas } > & [ Noun { Number } ] ] ( Site builds up its physical address coordinates using Numbers from the Lexicon )

# Freestanding Invariant Type Definition
< Site > = < Idea { Type } > & [ Noun { Silicon Coordinate } ] ( Site is the Invariant Idea of Type, and is the Noun of Silicon Coordinate ) {
    # 1. The Ontological Analogy (Site's proportion to the universe)
    [ Relation ]: [ Site ] : [ Coordinate ] :: [ Memory ] : [ Silicon ] ( Site is to Coordinate as Memory is to Silicon ),

    # 2. The Universal Domain (All physical addresses, pointers, ports, and MMIO coordinates)
    [ Domain ]: { Address :: Pointer :: Port :: MMIO } ( Domain encompasses physical addresses, pointers, ports, and MMIO coordinates ),

    # 3. The Physical Substrate (64-bit silicon address pointer)
    [ Substrate ]: [ 1 Address { 64 Bits } ] & [ Silicon Coordinate ] ( Substrate is 1 Address of 64 Bits, and is a Silicon Coordinate ),

    # 4. The Universal Inscription Vector (How external coordinate is bound into memory)
    [ Inscribe ]: [ Coordinate ] --> [ Site ] ( Any silicon coordinate is inscribed into the physical Site address ),

    # 5. The Hardware Routing Law (Bijective routing between RAM pointer and MMIO hardware register)
    [ Law { Routing } ]: [ Physical RAM @ ] | [ Hardware MMIO ::@ ] ( Physical memory addresses route via @ and MMIO ports route via ::@ ),

    # 6. Canonical Exemplars (Standard grounding values for MBR bootstrap origin, COM1, and VGA buffer)
    [ Exemplar { Null } ]: @ 0x00000000 <=> [ Null Coordinate { 0x0 } ] ( Canonical null coordinate represents unmapped memory ),
    [ Exemplar { Bootstrap MBR } ]: @ 0x7C00 <=> [ MBR Origin { 0x7C00 } ] ( Canonical real-mode master boot record physical origin ),
    [ Exemplar { COM1 Serial } ]: ::@ 0x03F8 <=> [ Serial COM1 { 0x03F8 } ] ( Canonical hardware serial port for diagnostic telemetry ),
    [ Exemplar { VGA Buffer } ]: ::@ 0x000B8000 <=> [ VGA Text Buffer { 0x000B8000 } ] ( Canonical physical memory-mapped VGA text buffer ),

    # 7. The Relational Comparison (How sites evaluate address identity)
    [ Compare ]: [ { Target } = { Address } ] ( Site evaluates target pointer against declared physical address ),

    # 8. The Sequence Transition (How sites chain into continuous memory maps)
    [ Sequence ]: [ Site ] --> [ Map ] ( Discrete site addresses chain together into continuous system memory maps ),
```

```
    59
    60      # 9. The Invariant Boundary (Strict single address enclosure)
    61      [ Bound ]: ENCLOSE [ Location ] WITHIN [ 1 Address ] ( Site is strictly enclosed within a single 64-bit address
capacity )
    62  }
    63
    64  # ============================================================================
    65  # BLOCK 2: OPENING BLOCK
    66  # ============================================================================
    67  Opening {
    68      # 1. The Dynamic Input Payload: Accepts incoming memory address or MMIO coordinate
    69      { Coordinate ]: { Input :: @ 0x7C00 } ( Outside-in imposition: external silicon coordinate to be bound into physical
site ),
    70
    71      # 2. The Typed Entity: Site brought down from Block 1 into concrete allocation
    72      [ Site ]: < Site > & [ Location ] ( Denoted Site is typed as invariant Site allocated as a Location ),
    73
    74      # 3. The Physical Address Container: The atomic 64-bit address container
    75      [ Physical Address ]: [ 1 Address ] & { 64 Bits } ( A concrete 1-address container in the context of 64 Bits ),
    76
    77      # 4. The Hardware Bridge: Routing between physical memory and hardware registers
    78      [ Bridge ]: { Physical RAM @ } | { Hardware MMIO ::@ } ( Hardware bridge enforces memory mapping physics ),
    79
    80      # 5. The Output Target: The pointer destination register
    81      [ Target ]: [ Pointer Register ] ::@ 0x00000000 ( Target output is situated at the primary hardware memory pointer
register ),
    82
    83      # 6. Preconditions & State: Proving valid non-null address before binding
    84      [ Preconditions ]: [ Address != 0x00000000 ] & [ Status = +1:PROCEED ] ( Coordinate is non-null and machine status is
armed in Proceed )
    85  }
    86
    87  # ============================================================================
    88  # BLOCK 3: BODY BLOCK
    89  # ============================================================================
    90  Body [
    91      # ----------------------------------------------------------------------
    92      # ROLL 1: LOCATE (LADDER BUILD-UP)
    93      # Build up physical address location with numeric scalar coordinate yielding new state Site`
    94      # ----------------------------------------------------------------------
    95      [ ROLL 1 ] : [ Locate ] : /-^ [ 64 Bits ] --> [ Address ] = [ Site` ]
    96          ( Build up physical address location with numeric scalar coordinate yielding new state Site-prime ),
    97
    98      # ----------------------------------------------------------------------
    99      # ROLL 2: BIND COORDINATE (OUTSIDE-IN IMPOSITION)
   100      # Bind external coordinate imposed into physical Site yielding new state Located Coordinate`
   101      # ----------------------------------------------------------------------
   102      [ ROLL 2 ] : [ Bind ] : { Coordinate ] --> BIND [ Site` ] = [ Located Coordinate` ]
   103          ( Bind external coordinate imposed into physical Site yielding new state Located Coordinate-prime ),
   104
   105      # ----------------------------------------------------------------------
   106      # ROLL 3: IDENTITY & NULL GUARD
   107      # Compare located coordinate to input address under guard: proceed on valid address, rollback on null
   108      # ----------------------------------------------------------------------
   109      [ ROLL 3 ] : [ Guard Address ] :
   110          { Located Coordinate` = Coordinate } & { Located Coordinate` != 0x00000000 }
   111          ! GUARD --> [ Status` = +1:PROCEED ]
   112          | { Located Coordinate` = 0x00000000 } --> [ Status` = -1:ROLLBACK ]
   113          ( Compare located coordinate to input address under guard: proceed on valid address, rollback on null pointer
error ),
   114
   115      # ----------------------------------------------------------------------
   116      # ROLL 4: ROUTE & PROJECT (INSIDE-OUT EMERGENCE)
   117      # Inside-out emergence: verified physical site routes outward to anchor hardware memory
   118      # ----------------------------------------------------------------------
   119      [ ROLL 4 ] : [ Route ] : [ Site` } --> ROUTE [ Target ] = [ Memory Anchor` ]
   120          ( Inside-out emergence: verified physical site routes outward to anchor hardware memory establishing new state
Memory Anchor-prime ),
   121
   122      # ----------------------------------------------------------------------
   123      # ROLL 5: SEQUENCE TRANSITION
   124      # Chain discrete site address outward into continuous system memory map sequence
   125      # ----------------------------------------------------------------------
   126      [ ROLL 5 ] : [ Sequence ] : [ Site` ] --> SEQUENCE [ Map ] = [ Memory Map` ]
   127          ( Discrete site address chains outward into continuous physical memory map establishing new state Memory Map-
prime )
   128  ]
   129
```

```
# ============================================================================
# BLOCK 4: CLOSING BLOCK
# ============================================================================
Closing ( Sealing Gate: Reconcile, validate, tripwire, debug, log, and affirm permanent execution ) {
    # ------------------------------------------------------------------------
    # 1. VERIFICATION OF OPERATIONAL ROLLS
    # ------------------------------------------------------------------------
    [ Verify ]: [
        [ ROLL 1 ] = PROCEED ::
        [ ROLL 2 ] = PROCEED ::
        [ ROLL 3 ] = PROCEED ::
        [ ROLL 4 ] = PROCEED ::
        [ ROLL 5 ] = PROCEED
    ] ( Verify that all five operational rolls achieved affirmative consensus in PROCEED ),

    # ------------------------------------------------------------------------
    # 2. VALIDATION OF INVARIANT BOUNDS & NON-NULL INTEGRITY
    # ------------------------------------------------------------------------
    [ Validate ]: { Located Coordinate` != 0x00000000 } & { Target = BOUND }
        ( Validate that located coordinate is non-null and target pointer is permanently bound ),

    # ------------------------------------------------------------------------
    # 3. ZERO-TOLERANCE TRIPWIRING
    # ------------------------------------------------------------------------
    [ Tripwire ]: { Status` = +1:PROCEED } --> [ ARMED ] | { Status` != +1:PROCEED } --> [ TRIPPED ] --> [ Commit Status
= -1:ROLLBACK ]
        ( Tripwire remains armed in Proceed or trips on anomaly to veto execution ),

    # ------------------------------------------------------------------------
    # 4. DIAGNOSTIC DEBUG TELEMETRY
    # ------------------------------------------------------------------------
    [ Debug ]: { [ Coordinate ] :: [ Site` ] :: [ Target ] :: [ Status` ] }
        ( Expose diagnostic telemetry across input coordinate, site location, target pointer, and machine status ),

    # ------------------------------------------------------------------------
    # 5. EPISODIC INVENTORY LOGGING
    # ------------------------------------------------------------------------
    [ Log ]: [ Journal ]: INSCRIBE { [ Site Bound ] :: [ Site` ] :: [ Target ] }
        ( Inscribe the verified site transaction into the permanent episodic system journal ),

    # ------------------------------------------------------------------------
    # 6. PERMANENT COVENANT EXECUTION & FOURFOLD COMMIT STATUS LOOP
    # ------------------------------------------------------------------------
    [ Commit Status ]: [
        # +1: PROCEED (+t: Advance forward along the causal tape)
        { [ Verify ] = PROCEED } & { [ Tripwire ] = ARMED }
            --> [ +1:PROCEED ] |

        #  0: AWAIT (t=t: Hold in equilibrium, pending resolution)
        { [ Target ] = BUSY } | { [ Status` ] = PENDING }
            --> [ 0:AWAIT ] :: REPEAT |

        # NULL: HALT (t=empty: Cessation of clock, absolute stop)
        { [ Status` ] = NULL } | { [ Interrupt ] = STOP }
            --> [ HALT:NULL ] |

        # -1: ROLLBACK (-t: Reverse causal tape to origin t=0)
        { [ Tripwire ] = TRIPPED } | { [ Verify ] != PROCEED }
            --> [ -1:ROLLBACK ]
    ] ( Fourfold state machine: Proceed advances forward, Await holds equilibrium, Halt ceases execution in Null,
Rollback reverts to origin )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/site.tape

TAPE | 89 LINES | 763 WORDS | 5.3 KB

```
# ================================================================================
# PROCESS TAPE: SITE INVARIANT TYPE EXECUTION RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Interprets and executes the atomic lifecycle for Invariant Type < Site >.
#   - Defined Space: [ 1 Address ] { 64 Bits / Silicon Coordinate }
#   - Execution Domain: Lexicon { Types of Ideas }
#   - Ladder Ascension: Build-up with Numbers (/-^)
# ================================================================================

= [Tape]: < Lexicon { Types of Ideas } > & [ Process { Site } ] ( Process Ribbon for Site Address Binding ) {
    WHO   { OmniCode Lexicon } ::
    WHAT  { Site } --> LOCATE { PhysicalAddress } ::
    WHEN  { Addressing Event } ::
    WHERE { Silicon Coordinate } = [ 1 Address ] ::
    WHY   ( Inscribe physical site address invariant and hardware MMIO coordinates ) ::
    HOW   [ +1 : PROCEED ] ::
    < Scripture { Genesis 28:16 KJV } > { "And Jacob awaked out of his sleep, and he said, Surely the Lord is in this
place; and I knew it not." } ( Invariant Scripture Witness Genesis 28:16 in the context: Surely the Lord is in this place; and I
knew it not )
}

# --------------------------------------------------------------------------------
# LADDER ASCENSION: BUILD-UP WITH NUMBERS
# --------------------------------------------------------------------------------
/-^ < Numbers > FROM [ < Lexicon { Types of Ideas } > & [ Noun { Number } ] ] ( Build up physical address coordinates
using Numbers from the Lexicon )

# ================================================================================
# DECLARED ROLLS: ATOMIC INVARIANT EXECUTION
# ================================================================================

# --------------------------------------------------------------------------------
# ROLL 1: LOCATE (LADDER BUILD-UP)
# Build up physical address location with numeric scalar coordinate yielding new state Site`
# --------------------------------------------------------------------------------
[ ROLL 1 ] : [ Locate ] : /-^ [ 64 Bits ] --> [ Address ] = [ Site` ]
    ( Build up physical address location with numeric scalar coordinate yielding new state Site-prime )

# --------------------------------------------------------------------------------
# ROLL 2: BIND COORDINATE (OUTSIDE-IN IMPOSITION)
# Bind external coordinate imposed into physical Site yielding new state Located Coordinate`
# --------------------------------------------------------------------------------
[ ROLL 2 ] : [ Bind ] : { Coordinate } --> BIND [ Site` ] = [ Located Coordinate` ]
    ( Bind external coordinate imposed into physical Site yielding new state Located Coordinate-prime )

# --------------------------------------------------------------------------------
# ROLL 3: IDENTITY & NULL GUARD
# Compare located coordinate to input address under guard: proceed on valid address, rollback on null
# --------------------------------------------------------------------------------
[ ROLL 3 ] : [ Guard Address ] :
    { Located Coordinate` = Coordinate } & { Located Coordinate` != 0x00000000 }
    ! GUARD --> [ Status` = +1:PROCEED ]
    | { Located Coordinate` = 0x00000000 } --> [ Status` = -1:ROLLBACK ]
    ( Compare located coordinate to input address under guard: proceed on valid address, rollback on null pointer error )

# --------------------------------------------------------------------------------
# ROLL 4: ROUTE & PROJECT (INSIDE-OUT EMERGENCE)
# Inside-out emergence: verified physical site routes outward to anchor hardware memory
# --------------------------------------------------------------------------------
[ ROLL 4 ] : [ Route ] : [ Site` ] --> ROUTE [ Target ] = [ Memory Anchor` ]
    ( Inside-out emergence: verified physical site routes outward to anchor hardware memory establishing new state Memory
Anchor-prime )

# --------------------------------------------------------------------------------
# ROLL 5: SEQUENCE TRANSITION
# Chain discrete site address outward into continuous system memory map sequence
# --------------------------------------------------------------------------------
[ ROLL 5 ] : [ Sequence ] : [ Site` ] --> SEQUENCE [ Map ] = [ Memory Map` ]
    ( Discrete site address chains outward into continuous physical memory map establishing new state Memory Map-prime )

# --------------------------------------------------------------------------------
# ROLL 6: COMMIT STATUS & FOURFOLD STATE MACHINE
```

```
# Affirm covenant execution across causal time advancement, await, halt, and rollback
# ------------------------------------------------------------------------------
[ ROLL 6 ] : [ Commit Status ] : [
    # +1: PROCEED (+t: Advance forward along the causal tape)
    { [ Verify ] = PROCEED } & { [ Tripwire ] = ARMED }
        --> [ +1:PROCEED ] |

    #  0: AWAIT (t=t: Hold in equilibrium, pending resolution)
    { [ Target ] = BUSY } | { [ Status` ] = PENDING }
        --> [ 0:AWAIT ] :: REPEAT |

    # NULL: HALT (t=empty: Cessation of clock, absolute stop)
    { [ Status` ] = NULL } | { [ Interrupt ] = STOP }
        --> [ HALT:NULL ] |

    # -1: ROLLBACK (-t: Reverse causal tape to origin t=0)
    { [ Tripwire ] = TRIPPED } | { [ Verify ] != PROCEED }
        --> [ -1:ROLLBACK ]
] ( Fourfold commit status: Proceed advances forward, Await holds in equilibrium, Halt ceases execution in Null, Rollback
reverts to origin )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/state.omni

OMNI | 230 LINES | 2189 WORDS | 14.4 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Type: < Idea { Type } : State > )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the Quad-State truth, causal clock, and control flow invariant.
#   - Base Block: Primitive Invariant Type
#   - Category: Idea { Type }
#   - Footprint: [ 1 Trit ] { 2 Bits / Quad-State Causal Register }
#   - Named Registers: [ STATE TURN BOUND IT ]
#   - States: +1 (PROCEED), 0 (AWAIT), -1 (ROLLBACK), NULL (HALT)
# ================================================================================

= [Module]: < Lexicon { Types of Ideas } > & [ Noun { State } ] ( This is the Module for the Lexicon - Ideas (Type): States - Nouns ) {
    [ Version ]:   { "1.0.0" } ( The Version is in the context of 1.0.0 ),
    [ Created ]:   { "2026-10-11" } ( Created in the context of October 11, 2026 ),
    [ Updated ]:   { "2026-10-13" } ( Last updated in the context of October 13, 2026 ),
    [ Author ]:    { "CreativeWorkzStudio LLC / ProfessorSeanEX" } ( Author in the context of CreativeWorkzStudio LLC and ProfessorSeanEX ),
    [ System ]:    { OmniCode { Lexicon } } ( System is in the context of the OmniCode Lexicon ),
    [ Witness ]:   < Scripture { Ecclesiastes 3:1 KJV } > { "To every thing there is a season, and a time to every purpose under the heaven:" } ( Invariant Scripture Witness Ecclesiastes 3:1 in the context: To every thing there is a season, and a time to every purpose under the heaven ),
    [ Nature ]:    < InvariantType > & { BaseBlock } ( Nature is an Invariant Type and is in the context of Base Block ),
    [ Semantics ]: { QuadStateTruth :: CausalClock :: ControlFlowState } ( Semantics in the context of Quad State Truth, Causal Clock, and Control Flow State )
}

# ------------------------------------------------------------------------------
# LADDER FOUNDATION: INDEPENDENT TEMPORAL BASE
# State does not build up from space or memory envelopes: it is the independent
# atomic base of causal time and Quad-State truth governing execution.
# ------------------------------------------------------------------------------

# Freestanding Invariant Type Definition
< State > = < Idea { Type } > & [ Noun { Causal Truth } ] ( State is the Invariant Idea of Type, and is the Noun of Causal Truth ) {
    # 1. The Ontological Analogy (State's proportion to the universe)
    [ Relation ]: [ State ] : [ Truth ] :: [ Trit ] : [ Causality ] ( State is to Truth as Trit is to Causality ),

    # 2. The Universal Domain (All quad-state transitions, cadence pulses, and control flows)
    [ Domain ]: { Proceed :: Await :: Rollback :: Halt } ( Domain encompasses Proceed, Await, Rollback, and Halt ),

    # 3. The Physical Substrate (1 balanced trit or 2 silicon bits)
    [ Substrate ]: [ 1 Trit { 2 Bits } ] & [ Causal Truth ] ( Substrate is 1 Trit of 2 Bits, and is Causal Truth ),

    # 4. The Universal Inscription Vector (How external truth signal is recorded into the state register)
    [ Inscribe ]: [ Signal ] --> [ STATE ] ( Any truth signal is inscribed into the STATE register ),

    # 5. The Hardware Polarity Transition (Abstract archetype lowers to concrete silicon register)
    [ Lower ]: [ +State v-- State- ::@ 0x0000 ] ( Abstract idea lowers to concrete register at base offset ),

    # 6. The Core Quad-State Truth Law (The fourfold ontological states of computation)
    [ Law { Quad-State } ]: { T4 = [ +1:PROCEED | 0:AWAIT | -1:ROLLBACK | HALT:NULL ] } ( The balanced ternary truth system governing all causation ),

    # 7. Canonical Exemplars (Standard grounding values for Proceed, Await, Rollback, and Halt)
    [ Exemplar { Proceed } ]: (+1) <=> [ PROCEED { Forward Causation } ] ( Forward causation advances execution ),
    [ Exemplar { Await } ]: 0 <=> [ AWAIT { Equilibrium Standby } ] ( Standby equilibrium holds pending external resolution ),
    [ Exemplar { Rollback } ]: (-1) <=> [ ROLLBACK { Retroactive Reversal } ] ( Retroactive reversal unwinds causal drift ),
    [ Exemplar { Halt } ]: NULL <=> [ HALT { Terminal Detent } ] ( Terminal detent halts the execution clock ),

    # 8. The Canonical Looping Law (The formal loop grammar connecting Quad-State to hardware registers)
    [ Law { Loop } ]: LOOP [ WHEN [ { IT } < { BOUND } ] --> [ IT` ] PROCEED to { TURN } ! [ { IT } > { BOUND } ] AWAIT for [ IT` ] :: HALT WHEN [ IT` ] = NULL ] ( Canonical loop statement governing IT, BOUND, and TURN across the quad states ),

    # 9. The Relational Comparison (How states evaluate active truth against signal)
    [ Compare ]: [ { STATE } = { Signal } ] ( State evaluates active register against expected truth signal ),

    # 10. The Sequence Transition (How states chain into continuous causal timelines)
```

```
    [ Sequence ]: [ State ] --> [ Timeline ] ( Discrete states chain together into continuous execution timelines ),

    # 11. The Invariant Boundary (Strict single trit enclosure)
    [ Bound ]: ENCLOSE [ Truth ] WITHIN [ 1 Trit ] ( State is strictly enclosed within a single trit capacity )
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    # 1. The Dynamic Input Signal: Accepts incoming causal truth signal
    { Signal ]: { Input :: [ +1:PROCEED ] } ( Outside-in imposition: external causal truth signal to be evaluated ),

    # 2. The Typed Entity: State brought down from Block 1 into concrete allocation
    [ State ]: < State > & [ Register ] ( Denoted State is typed as invariant State allocated as a Register ),

    # 3. The Named Hardware Register Bank: Core registers for state and loop execution
    [ Registers ]: [ STATE TURN BOUND IT ] ( Named hardware registers armed for state and cadence execution ),

    # 4. The Initial Register Values: Initializing loop parameters
    [ Setup ]: [ STATE = 0:AWAIT ] :: [ IT = 0 ] :: [ BOUND = 3 ] :: [ TURN = 0 ] ( Initialize state in Await,
accumulator at zero, bound at 3, turn at zero ),

    # 5. The Hardware Clock Bridge: Arming the causal clock and cadence transitions
    [ Clock ]: { (+1:PROCEED) :: (0:AWAIT) :: (-1:ROLLBACK) :: (HALT:NULL) } ( Hardware clock bridges the four states of
truth ),

    # 6. The Output Target: The execution status register
    [ Target ]: [ Status Register ] ::@ 0x00000000 ( Target output is situated at the primary execution status register
),

    # 7. Preconditions & State: Proving non-null valid signal before transition
    [ Preconditions ]: [ Signal != NULL ] & [ Status = +1:PROCEED ] ( Signal is non-null and machine status is armed in
Proceed )
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # --------------------------------------------------------------------------
    # ROLL 1: INSCRIBE STATE REGISTER (OUTSIDE-IN IMPOSITION)
    # Inscribe incoming truth signal into the STATE register, establishing new state STATE`
    # --------------------------------------------------------------------------
    [ ROLL 1 ] : [ Inscribe Register ] : { Signal ] --> INSCRIBE [ STATE ] = [ STATE` ]
        ( Inscribe external truth signal imposed into STATE register yielding new state STATE-prime ),

    # --------------------------------------------------------------------------
    # ROLL 2: AFFIRMATIVE PROCEED TRANSITION
    # Transition along the forward causal vector: PROCEED advances forward to { TURN }
    # --------------------------------------------------------------------------
    [ ROLL 2 ] : [ Affirmative Transition ] : [ Clock ]: [ STATE` ] --> [ +1:PROCEED ] to { TURN } = [ Active State` ]
        ( Transition STATE-prime through clock cadence into affirmative Proceed advancing forward to TURN ),

    # --------------------------------------------------------------------------
    # ROLL 3: EQUILIBRIUM AWAIT TRANSITION
    # Transition into equilibrium: AWAIT holds in zero-sum balance for [ IT` ]
    # --------------------------------------------------------------------------
    [ ROLL 3 ] : [ Standby Equilibrium ] : [ Clock ]: [ STATE` ] <=> [ 0:AWAIT ] for [ IT` ] = [ Standby State` ]
        ( Transition STATE-prime into equilibrium Await holding in standby for IT-prime ),

    # --------------------------------------------------------------------------
    # ROLL 4: CAVEAT GUARD & ROLLBACK
    # Evaluate incoming caveat with !: proceed on alignment, or trigger -1:ROLLBACK on discrepancy
    # --------------------------------------------------------------------------
    [ ROLL 4 ] : [ Guard Condition ] :
        { STATE` = Signal }
        ! GUARD --> [ Status` = +1:PROCEED ]
        | { STATE` != Signal } --> [ Status` = -1:ROLLBACK ]
        ( Guard truth against signal under caveat: proceed on alignment, rollback on discrepancy ),

    # --------------------------------------------------------------------------
    # ROLL 5: TERMINAL DETENT TRAP
    # Trap bottom type HALT:NULL on illegal signal or terminal detent
    # --------------------------------------------------------------------------
    [ ROLL 5 ] : [ Trap Detent ] :
        { Status` = NULL }
        ! TRAP --> [ HALT:NULL ]
```

```
        | { Status` != NULL } --> [ Active State` = +1:PROCEED ]
        ( Trap null bottom state under guard detent or proceed with active state ),

    # ------------------------------------------------------------------------
    # ROLL 6: THE CANONICAL LOOP STATEMENT
    # Execute the formal OmniCode loop statement governing IT, BOUND, and TURN across states
    # ------------------------------------------------------------------------
    [ ROLL 6 ] : [ Loop ] :
        LOOP [
            WHEN [ { IT } < { BOUND } ] --> [ IT` ] PROCEED to { TURN }
            ! [ { IT } > { BOUND } ] AWAIT for [ IT` ]
            :: HALT WHEN [ IT` ] = NULL
        ] ( Execute canonical quad-state accumulator loop: proceed to TURN while under BOUND, await when above BOUND,
halt on NULL ),

    # ------------------------------------------------------------------------
    # ROLL 7: GOVERN ENGINE (INSIDE-OUT EMERGENCE)
    # Inside-out emergence: verified state emerges outward to govern the machine clock
    # ------------------------------------------------------------------------
    [ ROLL 7 ] : [ Govern Engine ] : [ STATE` } --> GOVERN [ Control Flow ] = [ Clock` ]
        ( Inside-out emergence: verified state emerges outward to govern machine clock establishing new state Clock-prime
),

    # ------------------------------------------------------------------------
    # ROLL 8: SEQUENCE TRANSITION
    # Chain discrete state into continuous execution timeline sequence
    # ------------------------------------------------------------------------
    [ ROLL 8 ] : [ Sequence ] : [ STATE` ] --> SEQUENCE [ Timeline ] = [ Timeline` ]
        ( Discrete state chains outward into continuous causal timeline establishing new state Timeline-prime )
]

# ============================================================================
# BLOCK 4: CLOSING BLOCK
# ============================================================================
Closing ( Sealing Gate: Reconcile, validate, tripwire, debug, log, and affirm permanent execution ) {
    # ------------------------------------------------------------------------
    # 1. VERIFICATION OF OPERATIONAL ROLLS
    # ------------------------------------------------------------------------
    [ Verify ]: [
        [ ROLL 1 ] = PROCEED ::
        [ ROLL 2 ] = PROCEED ::
        [ ROLL 3 ] = PROCEED ::
        [ ROLL 4 ] = PROCEED ::
        [ ROLL 5 ] = PROCEED ::
        [ ROLL 6 ] = PROCEED ::
        [ ROLL 7 ] = PROCEED ::
        [ ROLL 8 ] = PROCEED
    ] ( Verify that all eight operational rolls achieved affirmative consensus in PROCEED ),

    # ------------------------------------------------------------------------
    # 2. VALIDATION OF INVARIANT BOUNDS & QUAD-STATE INTEGRITY
    # ------------------------------------------------------------------------
    [ Validate ]: { STATE` <= [ 1 Trit ] } & { [ ROLL 6 ] = PROCEED }
        ( Validate that state remains strictly enclosed within 1 Trit and canonical loop sealed in Proceed ),

    # ------------------------------------------------------------------------
    # 3. ZERO-TOLERANCE TRIPWIRING
    # ------------------------------------------------------------------------
    [ Tripwire ]: { Status` = +1:PROCEED } --> [ ARMED ] | { Status` != +1:PROCEED } --> [ TRIPPED ] --> [ Commit Status
= -1:ROLLBACK ]
        ( Tripwire remains armed in Proceed or trips on anomaly to veto execution ),

    # ------------------------------------------------------------------------
    # 4. DIAGNOSTIC DEBUG TELEMETRY
    # ------------------------------------------------------------------------
    [ Debug ]: { [ Signal ] :: [ STATE` ] :: [ IT` ] :: [ TURN` ] :: [ Status` ] }
        ( Expose diagnostic telemetry across input signal, state register, accumulator IT, cadence TURN, and status ),

    # ------------------------------------------------------------------------
    # 5. EPISODIC INVENTORY LOGGING
    # ------------------------------------------------------------------------
    [ Log ]: [ Journal ]: INSCRIBE { [ State Resolved ] :: [ STATE` ] :: [ Target ] }
        ( Inscribe the verified state transaction into the permanent episodic system journal ),

    # ------------------------------------------------------------------------
    # 6. PERMANENT COVENANT EXECUTION & FOURFOLD COMMIT STATUS LOOP
    # ------------------------------------------------------------------------
    [ Commit Status ]: [
```

```
        # +1: PROCEED (+t: Advance forward along the causal tape)
        { [ Verify ] = PROCEED } & { [ Tripwire ] = ARMED }
            --> [ +1:PROCEED ] |

        #  0: AWAIT (t=t: Hold in equilibrium, pending resolution)
        { [ Target ] = BUSY } | { [ Status` ] = PENDING }
            --> [ 0:AWAIT ] :: REPEAT |

        # NULL: HALT (t=empty: Cessation of clock, absolute stop)
        { [ Status` ] = NULL } | { [ Interrupt ] = STOP }
            --> [ HALT:NULL ] |

        # -1: ROLLBACK (-t: Reverse causal tape to origin t=0)
        { [ Tripwire ] = TRIPPED } | { [ Verify ] != PROCEED }
            --> [ -1:ROLLBACK ]
    ] ( Fourfold state machine: Proceed advances forward, Await holds equilibrium, Halt ceases execution in Null,
Rollback reverts to origin )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/state.tape

TAPE | 117 LINES | 949 WORDS | 6.7 KB

```
# ================================================================================
# PROCESS TAPE: STATE INVARIANT TYPE EXECUTION RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Interprets and executes the atomic lifecycle for Invariant Type < State >.
#   - Defined Space: [ 1 Trit ] { 2 Bits / Quad-State Causal Register }
#   - Execution Domain: Lexicon { Types of Ideas }
#   - Named Registers: [ STATE TURN BOUND IT ]
#   - Kinematics: 8 Operational Rolls with Canonical Quad-State Accumulator Loop
# ================================================================================

= [Tape]: < Lexicon { Types of Ideas } > & [ Process { State } ] ( Process Ribbon for Quad-State Causal Governance ) {
    WHO   { OmniCode Lexicon } ::
    WHAT  { State } --> GOVERN { CausalTruth } ::
    WHEN  { Control Event } ::
    WHERE { State Register } = [ 1 Trit ] ::
    WHY   ( Inscribe quad-state truth invariant and execute canonical loops ) ::
    HOW   [ +1 : PROCEED ] ::
    < Scripture { Ecclesiastes 3:1 KJV } > { "To every thing there is a season, and a time to every purpose under the heaven:" } ( Invariant Scripture Witness Ecclesiastes 3:1 in the context: To every thing there is a season, and a time to every purpose under the heaven )
}

# --------------------------------------------------------------------------------
# LADDER FOUNDATION: INDEPENDENT TEMPORAL BASE
# --------------------------------------------------------------------------------

# ================================================================================
# DECLARED ROLLS: ATOMIC INVARIANT EXECUTION
# ================================================================================

# --------------------------------------------------------------------------------
# ROLL 1: INSCRIBE STATE REGISTER (OUTSIDE-IN IMPOSITION)
# Inscribe incoming truth signal into the STATE register
# --------------------------------------------------------------------------------
[ ROLL 1 ] : [ Inscribe Register ] : { Signal ] --> INSCRIBE [ STATE ] = [ STATE` ]
    ( Inscribe external truth signal imposed into STATE register yielding new state STATE-prime )

# --------------------------------------------------------------------------------
# ROLL 2: AFFIRMATIVE PROCEED TRANSITION
# Transition along forward causal vector: PROCEED advances forward to { TURN }
# --------------------------------------------------------------------------------
[ ROLL 2 ] : [ Affirmative Transition ] : [ Clock ]: [ STATE` ] --> [ +1:PROCEED ] to { TURN } = [ Active State` ]
    ( Transition STATE-prime through clock cadence into affirmative Proceed advancing forward to TURN )

# --------------------------------------------------------------------------------
# ROLL 3: EQUILIBRIUM AWAIT TRANSITION
# Transition into equilibrium: AWAIT holds in zero-sum balance for [ IT` ]
# --------------------------------------------------------------------------------
[ ROLL 3 ] : [ Standby Equilibrium ] : [ Clock ]: [ STATE` ] <=> [ 0:AWAIT ] for [ IT` ] = [ Standby State` ]
    ( Transition STATE-prime into equilibrium Await holding in standby for IT-prime )

# --------------------------------------------------------------------------------
# ROLL 4: CAVEAT GUARD & ROLLBACK
# Evaluate incoming caveat with !: proceed on alignment, or trigger -1:ROLLBACK on discrepancy
# --------------------------------------------------------------------------------
[ ROLL 4 ] : [ Guard Condition ] :
    { STATE` = Signal }
    ! GUARD --> [ Status` = +1:PROCEED ]
    | { STATE` != Signal } --> [ Status` = -1:ROLLBACK ]
    ( Guard truth against signal under caveat: proceed on alignment, rollback on discrepancy )

# --------------------------------------------------------------------------------
# ROLL 5: TERMINAL DETENT TRAP
# Trap bottom type HALT:NULL on illegal signal or terminal detent
# --------------------------------------------------------------------------------
[ ROLL 5 ] : [ Trap Detent ] :
    { Status` = NULL }
    ! TRAP --> [ HALT:NULL ]
    | { Status` != NULL } --> [ Active State` = +1:PROCEED ]
    ( Trap null bottom state under guard detent or proceed with active state )

# --------------------------------------------------------------------------------
```

```
# ROLL 6: THE CANONICAL LOOP STATEMENT
# Execute the formal OmniCode loop statement governing IT, BOUND, and TURN across states
# ------------------------------------------------------------------------------
[ ROLL 6 ] : [ Loop ] :
    LOOP [
        WHEN [ { IT } < { BOUND } ] --> [ IT` ] PROCEED to { TURN }
        ! [ { IT } > { BOUND } ] AWAIT for [ IT` ]
        :: HALT WHEN [ IT` ] = NULL
    ] ( Execute canonical quad-state accumulator loop: proceed to TURN while under BOUND, await when above BOUND, halt on NULL )

# ------------------------------------------------------------------------------
# ROLL 7: GOVERN ENGINE (INSIDE-OUT EMERGENCE)
# Inside-out emergence: verified state emerges outward to govern the machine clock
# ------------------------------------------------------------------------------
[ ROLL 7 ] : [ Govern Engine ] : [ STATE` } --> GOVERN [ Control Flow ] = [ Clock` ]
    ( Inside-out emergence: verified state emerges outward to govern machine clock establishing new state Clock-prime )

# ------------------------------------------------------------------------------
# ROLL 8: SEQUENCE TRANSITION
# Chain discrete state into continuous execution timeline sequence
# ------------------------------------------------------------------------------
[ ROLL 8 ] : [ Sequence ] : [ STATE` ] --> SEQUENCE [ Timeline ] = [ Timeline` ]
    ( Discrete state chains outward into continuous causal timeline establishing new state Timeline-prime )

# ------------------------------------------------------------------------------
# ROLL 9: COMMIT STATUS & FOURFOLD STATE MACHINE
# Affirm covenant execution across causal time advancement, await, halt, and rollback
# ------------------------------------------------------------------------------
[ ROLL 9 ] : [ Commit Status ] : [
    # +1: PROCEED (+t: Advance forward along the causal tape)
    { [ Verify ] = PROCEED } & { [ Tripwire ] = ARMED }
        --> [ +1:PROCEED ] |

    #  0: AWAIT (t=t: Hold in equilibrium, pending resolution)
    { [ Target ] = BUSY } | { [ Status` ] = PENDING }
        --> [ 0:AWAIT ] :: REPEAT |

    # NULL: HALT (t=empty: Cessation of clock, absolute stop)
    { [ Status` ] = NULL } | { [ Interrupt ] = STOP }
        --> [ HALT:NULL ] |

    # -1: ROLLBACK (-t: Reverse causal tape to origin t=0)
    { [ Tripwire ] = TRIPPED } | { [ Verify ] != PROCEED }
        --> [ -1:ROLLBACK ]
] ( Fourfold commit status: Proceed advances forward, Await holds in equilibrium, Halt ceases execution in Null, Rollback reverts to origin )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/text.omni

OMNI | 62 LINES | 249 WORDS | 2.2 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Type: <IDEA:TYPE:TEXT> )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines inscriptional sequences of characters (Words, Phrases, and Strings).
#   - Base Block: Primitive Invariant Type
#   - Category: Idea
#   - Subcategory: Type
#   - Sequence: Ordered ribbon of < Character > cells
# ========================================================================

Module < Lexicon.Nouns.Ideas.Types.Text > ( Inscriptional Word, Phrase & String Invariant ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < BaseBlock :: InvariantType :: InscriptionalText :: TextRibbon >
}

# Invariant Type Declaration: <IDEA:TYPE:TEXT>
< Idea : Type : Text > [ capacity: dynamic cells ] {
    # Polarity transition: Abstract archetype lowers to concrete ribbon
    +Text v-- Text- ::@ 0x0000

    # Inscription bounds
    ENCLOSE [ ribbon : Sequence [ Character ] ] WITHIN [ capacity ]

    # Clarified literal representations
    example_word: "MILLENIUMOS",
    example_phrase: "MILLENIUMOS: OMNICODE 32-TRIT OS ONLINE"
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {
    requires: [
        Text : InvariantNoun ::
        Character : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    # Verify text ribbon allocation and phrase inscription
    text_assertion [
        [ TEXT ] [ 32 ] :: { Text } --> INSCRIBE {Phrase}
    ] ( Inscriptional text ribbon allocated holding character sequence )
]

# ========================================================================
# BLOCK 4: CLOSING BLOCK
# ========================================================================
Closing {
    verify: [
        text_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Text invariant type sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/text.tape

TAPE | 33 LINES | 210 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: TEXT INVARIANT TYPE PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Type <IDEA:TYPE:TEXT>.
# ================================================================================

[Tape.Text] : WHO {OmniCode_Kernel} WHAT {TextType} --> INSCRIBE {TextRibbon}
    WHEN {TypeGenesis}
    WHERE {text_partition} = [ 64 ]
    WHY ( Inscribe text ribbon type invariant and clarified string phrases )
    HOW [ +1 : PROCEED ]
    :: < text_landmark > ( Habakkuk 2:2 - 'Write the vision, and make it plain upon tables' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract text archetype
roll_1 [ +Text ] ( Abstract text archetype referenced )

# Roll 2: Allocate concrete text ribbon
roll_2 [ Text --> Inscribed_Ribbon @ 0 ] ( Inscribe concrete text ribbon at offset 0 )

# Roll 3: Assert structural projection and clarified phrase
roll_3 [ [ TEXT ] [ 32 ] :: "MILLENIUMOS ONLINE" --> [ Inscribed_Ribbon ] ] ( Clarified phrase inscribed )

# Roll 4: Verify text integrity into result prime
roll_4 [ Inscribed_Ribbon = Text ! [ +1 ] --> [ text_verified` ] ] ( Verification yields result prime )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Text invariant type sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/compile_flags.txt

TXT | 5 LINES | 4 WORDS | 0.0 KB

```
-Iinclude
-Wall
-Wextra
-std=c11
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/number.o

DOC/BINARY | 1 LINES | 5 WORDS | 9.0 KB

[Binary Artifact: number.o (9.0 KB)]

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/include/character.h

H | 300 LINES | 1795 WORDS | 13.1 KB

```h
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT TYPE DEFINITION
 * ( Invariant Type: < Idea { Type } : Character > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Defines the atomic letter, glyph, and inscription rune in the OmniCode
 *   Standard Library Track 2 C Transpile Variant.
 *   - Base Block: Primitive Invariant Type
 *   - Category: Idea { Type }
 *   - Footprint: [ 1 Cell ] { 5 Balanced Trits / 8 Bits }
 *   - System: OmniCode { Lexicon }
 *   - Witness: Scripture Exodus 31:18 KJV
 *     "And he gave unto Moses, when he had made an end of communing with him upon
 *      mount Sinai, two tables of testimony, tables of stone, written with the
 *      finger of God."
 *   - Semantics: { AtomicGlyph :: LetterRune :: BalancedCellTransduction }
 *   - Invariant Law:
 *     { Character } = [ Enclosed ]: TRUE (Strict single-cell capacity).
 *
 * ONTOLOGICAL CORRESPONDENCE TO OMNICODE:
 *   OmniCode Block 1 declares the immutable laws of the universe for this type.
 *   In C, Block 1 is realized exclusively as:
 *     1. Invariant hardware target addresses and substrate constants.
 *     2. The freestanding invariant struct (omni_character_t) holding dual substrate.
 *     3. Pure mathematical conversion and verification functions that operate
 *        without runtime context dependencies.
 * ============================================================================ */

#ifndef OMNI_CHARACTER_H
#define OMNI_CHARACTER_H

#include "omni_base.h"
#include <stdint.h>
#include <stdbool.h>
#include <stddef.h>

#ifdef __cplusplus
extern "C" {
#endif

/* ----------------------------------------------------------------------------
 * 1. INVARIANT CONSTANTS & HARDWARE LOCATORS (OMNICODE BLOCK 1 & 2)
 * ---------------------------------------------------------------------------- */

/** Number of balanced trits per character cell (3^5 = 243 states). */
#define OMNI_CHAR_TRITS_PER_CELL OMNI_TRITS_PER_CELL

/** Canonical Exemplar: ASCII 'A' (Byte value 65). */
#define OMNI_EXEMPLAR_GLYPH_A    ((uint8_t)'A')

/**
 * @brief Hardware Target Locators (Composed operator ::@).
 *
 * OmniCode Specification:
 *   [ Target ]: { [ Terminal Stdout ] ::@ 0x01 | [ Screen VGA ] ::@ 0x000B8000 }
 */
#define OMNI_TARGET_STDOUT       ((uintptr_t)0x01)       /**< Hosted POSIX terminal stdout stream descriptor */
#define OMNI_TARGET_VGA          ((uintptr_t)0x000B8000) /**< Bare-metal x86 text mode video memory MMIO buffer */

/* ----------------------------------------------------------------------------
 * 2. FREESTANDING INVARIANT TYPE STRUCTURE: omni_character_t
 * ---------------------------------------------------------------------------- */

/**
 * @brief Invariant Type < Character >: The atomic rune of symbolic computing.
 *
 * Encloses the dual substrate:
 *   1. Physical Silicon Substrate: 1 Byte (8 bits, 0..255).
 *   2. Virtual Balanced Trit Substrate: 1 Cell (5 balanced trits, {-1, 0, +1}).
 *
 * Invariant Law:
 *   { Character } = [ Enclosed ]: TRUE (Strict single-cell boundary).
 */
```

```c
typedef struct {
    uint8_t     glyph;                                  /**< Physical byte substrate (8-bit ASCII/binary glyph) */
    omni_trit_t trits[OMNI_CHAR_TRITS_PER_CELL];        /**< Virtual cell substrate (5 balanced ternary trits) */
    bool        is_enclosed;                            /**< Invariant boundary enclosure guarantee */
} omni_character_t;

/* ---------------------------------------------------------------------------
 * 3. PURE INVARIANT OPERATIONS & TRANSDUCTION LAWS
 * --------------------------------------------------------------------------- */

/**
 * @brief Inscription Constructor: Constructs a Character directly from a raw 8-bit glyph.
 *
 * Evaluates OmniCode: [ Inscribe ]: [ Glyph ] --> [ Character ]
 * Automatically performs bijective transduction into 5 balanced trits and
 * establishes the invariant enclosure seal (is_enclosed = true).
 *
 * @param glyph The 8-bit byte codepoint to inscribe.
 * @return Fully initialized omni_character_t in equilibrium.
 */
omni_character_t omni_character_from_glyph(uint8_t glyph);

/**
 * @brief Hardware Transduction Law (<=>): Bijective mapping from 8-bit byte to 5 balanced trits.
 *
 * Evaluates OmniCode: [ Transduce ]: [ Character { Byte } ] <=> [ Cell { Trits } ]
 *
 * Mathematical Invariant:
 *   Each trit is in {-1, 0, +1}, satisfying:
 *     byte = sum_{i=0..4} trits[i] * 3^i
 *   Canonical Exemplar for 'A' (65):
 *     65 <=> [ -1, +1, +1, -1, +1 ]  (-1 + 3 + 9 - 27 + 81 = 65).
 *
 * @param byte_val Input 8-bit byte value (0..255).
 * @param out_trits Destination array of 5 balanced trits.
 */
void omni_character_transduce(uint8_t byte_val, omni_trit_t out_trits[OMNI_CHAR_TRITS_PER_CELL]);

/**
 * @brief Inverse Transduction Law (<=>): Reconstructs an 8-bit byte from 5 balanced trits.
 *
 * Evaluates the bidirectional symmetry of the invariant equivalence operator (<=>).
 * Rebuilds the silicon byte from the balanced ternary representation.
 *
 * @param trits Array of 5 balanced trits.
 * @return Reconstructed 8-bit unsigned byte value.
 */
uint8_t omni_character_to_byte(const omni_trit_t trits[OMNI_CHAR_TRITS_PER_CELL]);

/**
 * @brief Relational Equality Evaluation: Compares two character entities.
 *
 * Evaluates OmniCode: [ Compare ]: [ { Character } = { Glyph } ]
 *
 * @param a First character operand.
 * @param b Second character operand.
 * @return true if glyph values match and both are enclosed; false otherwise.
 */
bool omni_character_eq(const omni_character_t *a, const omni_character_t *b);

/**
 * @brief Boundary Invariant Verification: Proves single-cell enclosure.
 *
 * Evaluates OmniCode: [ Bound ]: { Character } = [ Enclosed ]: TRUE
 *
 * @param c Pointer to character instance to verify.
 * @return true if valid pointer and enclosure flag is sealed; false otherwise.
 */
bool omni_character_verify_bounds(const omni_character_t *c);

/**
 * @brief Bit-Level Extraction: Retrieves bit 0..7 from the glyph byte.
 *
 * Slices into the shared 8-bit base level that Character shares with Number.
 *
 * @param c Pointer to character entity.
 * @param bit_idx Bit index (0..7, where 0 is LSB and 7 is ASCII parity rail).
 * @return 1 if set, 0 if clear or on null pointer.
```

```
 */
uint8_t omni_character_get_bit(const omni_character_t *c, uint8_t bit_idx);

/**
 * @brief Standard ASCII Invariant Verification: Proves glyph in 0..127 range.
 *
 * Validates bit 7 is 0, leaving bit 7 free to serve as an immutable witness.
 *
 * @param c Pointer to character entity.
 * @return true if glyph <= 127 (bit 7 == 0); false otherwise.
 */
bool omni_character_is_ascii(const omni_character_t *c);

/* ============================================================================
 * BLOCK 2: OPENING BLOCK
 * ( Contextual Genesis, Input Imposition & Hardware Target Binding )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   OmniCode Block 2 brings the timeless laws of Block 1 down into active space
 *   and time for a concrete execution run:
 *     1. [ Glyph ]: Captures outside-in payload (CLI argument or stream input).
 *     2. [ Character ] & [ Cell ]: Allocates physical single-cell storage.
 *     3. [ Target ]: Binds to a concrete hardware address (Stdout or VGA MMIO).
 *     4. [ Preconditions ]: Checks ALU balance and arms the execution tripwire.
 * ============================================================================ */

/**
 * @brief Execution Context for Character Lifecycle Rolls.
 *
 * Encapsulates the complete runtime environment for the 4-block lifecycle:
 * outside-in input, allocated cell, target hardware address, optional sequence
 * destination, and safety interlocks.
 */
typedef struct {
    uint8_t               input_glyph;      /**< [ Glyph ]: Imposed outside-in payload */
    omni_character_t      character;        /**< [ Character ] & [ Cell ]: Concrete cell container */
    uintptr_t             target_address;   /**< [ Target ]: Hardware locator (0x01 Stdout or 0x000B8000 VGA) */
    void                 *sequence_target;  /**< [ Sequence ]: Destination buffer for chaining into Text */
    omni_quad_state_t     status;           /**< [ Preconditions ]: Quad-State truth (+1:PROCEED) */
    omni_tripwire_state_t tripwire;         /**< [ Preconditions ]: Subsystem safety interlock */
} omni_character_context_t;

/**
 * @brief Initializes the Character context, applies outside-in imposition,
 *        binds the hardware target, and arms the safety tripwire.
 *
 * Evaluates OmniCode Block 2: Opening { ... }
 *
 * @param ctx Pointer to caller-allocated character execution context.
 * @param input_glyph Outside-in byte payload (defaults to exemplar 'A' if 0).
 * @param target_address Hardware locator (e.g. OMNI_TARGET_STDOUT or OMNI_TARGET_VGA; defaults to STDOUT if 0).
 */
void omni_character_open(omni_character_context_t *ctx, uint8_t input_glyph, uintptr_t target_address);

/* ============================================================================
 * BLOCK 3: BODY BLOCK
 * ( Operational Rolls, Guard Interlocks & Hardware Emission )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   OmniCode Block 3 processes the discrete causal turns (rolls) that advance
 *   state along the causal timeline using the prime operator (`):
 *     - Roll 1: Inscribe input glyph into the Cell container.
 *     - Roll 2: Transduce 8 bits <=> 5 balanced trits.
 *     - Roll 3: Guard identity & boundary invariants via adversative catch (!).
 *     - Roll 4: Project Character` to the hardware target (terminal or VGA).
 *     - Roll 5: Sequence Character` into continuous Text ribbon if bound.
 * ============================================================================ */

/**
 * @brief Roll 1: Inscribes outside-in glyph into the cell, advancing state to Character`.
 *
 * Evaluates OmniCode: [ Inscribe ] : [ Glyph ] --> INSCRIBE [ Cell ] = [ Character` ]
 *
 * @param ctx Active execution context.
 * @param glyph The byte codepoint being inscribed.
 */
void omni_character_inscribe(omni_character_context_t *ctx, uint8_t glyph);

```

```
/**
 * @brief Roll 4: Projects Character` outward to the bound hardware target address.
 *
 * Evaluates OmniCode: [ Project ] : [ Character` ] --> PROJECT [ Target ] = [ Target` ]
 *
 * Machine Effect:
 *   - Target == 0x01 (Stdout): Emits glyph byte to file descriptor 1 (terminal).
 *   - Target == 0x000B8000 (VGA): Writes glyph + attribute to MMIO video memory.
 *
 * @param c Pointer to the verified Character to project.
 * @param target_address The physical destination address (0x01 or 0x000B8000).
 * @return true if projection succeeded; false on hardware fault.
 */
bool omni_character_project(const omni_character_t *c, uintptr_t target_address);

/**
 * @brief Roll 5: Yields Character` to continuous Text ribbon sequence.
 *
 * Evaluates OmniCode: [ Sequence ] : [ Character` ] --> SEQUENCE [ Text ] = [ Text` ]
 *
 * Machine Effect:
 *   If sequence_target is non-NULL, appends the character glyph into the sequence
 *   destination buffer. If NULL, passes as a single atomic character cycle.
 *
 * @param c Pointer to the Character being sequenced.
 * @param sequence_target Pointer to destination buffer or container.
 * @return true if sequence yield succeeded; false on buffer overflow.
 */
bool omni_character_sequence(const omni_character_t *c, void *sequence_target);

/**
 * @brief Executes the complete 5-roll operational pipeline across declared turns:
 *   Roll 1 (Inscribe) -> Roll 2 (Transduce) -> Roll 3 (Guard !) ->
 *   Roll 4 (Project)   -> Roll 5 (Sequence).
 *
 * The Guard turn (Roll 3) enforces the adversative catch (!):
 *   If identity and boundary invariants hold, advances status to +1:PROCEED.
 *   If any discrepancy is detected, trips the wire and rolls back to -1:ROLLBACK.
 *
 * @param ctx Pointer to armed character execution context.
 * @return OMNI_STATE_PROCEED (+1) on equilibrium; OMNI_STATE_ROLLBACK (-1) on violation.
 */
omni_quad_state_t omni_character_execute(omni_character_context_t *ctx);

/* ============================================================================
 * BLOCK 4: CLOSING BLOCK
 * ( Integrity Verification, Covenant Sealing & Quad-State Exit )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   OmniCode Block 4 reconciles all rolls, validates tripwire status, and seals
 *   the permanent commit status (+1:PROCEED, 0:AWAIT, NULL:HALT, -1:ROLLBACK).
 *   In hosted environments, +1:PROCEED maps to process exit code 0.
 * ============================================================================ */

/**
 * @brief Validates all invariants, verifies operational consensus, disarms the
 *        tripwire, and seals the final Character commit status.
 *
 * Evaluates OmniCode Block 4: Closing { ... }
 *
 * @param ctx Pointer to active character execution context.
 * @return OMNI_STATE_PROCEED (+1) on successful seal; OMNI_STATE_ROLLBACK (-1) if tripped.
 */
omni_quad_state_t omni_character_close(omni_character_context_t *ctx);

#ifdef __cplusplus
}
#endif

#endif /* OMNI_CHARACTER_H */
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/include/container.h

H | 222 LINES | 1078 WORDS | 9.0 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT TYPE DEFINITION
 * ( Invariant Type: < Idea { Type } : Container > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Defines bounded memory envelopes, arrays, structures, and storage vessels
 *   in the OmniCode Standard Library Track 2 C Transpile Variant.
 *   - Base Block: Primitive Invariant Type
 *   - Category: Idea { Type }
 *   - Footprint: [ Dynamically Bounded Memory Envelope / Generic Slice ]
 *   - Ladder Ascension: Builds up with Numbers (/-^)
 *   - System: OmniCode { Lexicon }
 *   - Witness: Scripture 2 Kings 4:4 KJV
 *     "And when thou art come in, thou shalt shut the door upon thee and upon
 *      thy sons, and shalt pour out into all those vessels, and thou shalt set
 *      aside that which is full."
 *   - Semantics: { BoundedEnvelope :: StorageVessel :: MemoryCapsule :: ContainmentLaw }
 * ============================================================================ */

#ifndef OMNI_CONTAINER_H
#define OMNI_CONTAINER_H

#include "omni_base.h"

#ifdef __cplusplus
extern "C" {
#endif

/* ----------------------------------------------------------------------------
 * 1. INVARIANT CONSTANTS & CANONICAL EXEMPLARS
 * ---------------------------------------------------------------------------- */

/** Canonical Unit Exemplar: Single element partition (1 unit). */
#define OMNI_CONTAINER_EXEMPLAR_UNIT        ((size_t)1)

/** Canonical Vessel Exemplar: Standard 64-element storage vessel. */
#define OMNI_CONTAINER_EXEMPLAR_VESSEL      ((size_t)64)

/** Canonical Storehouse Exemplar: Large 4096-element memory storehouse. */
#define OMNI_CONTAINER_EXEMPLAR_STOREHOUSE  ((size_t)4096)

/* ----------------------------------------------------------------------------
 * 2. FREESTANDING INVARIANT TYPE STRUCTURE: omni_container_t
 * ---------------------------------------------------------------------------- */

/**
 * @brief Invariant Type < Container >: The generic bounded memory envelope / slice.
 *
 * Provides memory safety by construction without requiring a heap or garbage collector:
 *   - Wraps a memory buffer of arbitrary element types (Character, Number, Site, State).
 *   - Strictly enforces the Core Containment Law: Occupancy <= Capacity.
 *
 * Core Invariant Law:
 *   ENCLOSE [ Storage ] WITHIN [ Capacity ]
 *   LAW { Containment } : [ { Occupancy } <= { Capacity } ]
 */
typedef struct {
    void   *buffer;                                 /**< Raw memory vessel holding discrete elements */
    size_t  element_size;                           /**< Footprint of a single element (sizeof(T) in bytes) */
    size_t  capacity;                               /**< Allocated maximum element capacity boundary */
    size_t  occupancy;                              /**< Current count of stored elements */
    bool    is_enclosed;                            /**< Invariant enclosure guarantee */
} omni_container_t;

/**
 * @brief Convenience static vessel initialized over a 64-byte storage partition.
 */
typedef struct {
    uint8_t          cells[OMNI_CONTAINER_EXEMPLAR_VESSEL]; /**< Concrete 64-byte static buffer */
    omni_container_t container;                             /**< Bounded slice wrapper */
} omni_byte_vessel_t;

/* ---------------------------------------------------------------------------- */
```

```
 * 3. 4-BLOCK PIPELINE CONTEXT: omni_container_context_t
 * ------------------------------------------------------------------------------ */

/**
 * @brief Execution context for Container encapsulation lifecycle rolls.
 */
typedef struct {
    const void            *payload_ptr;                /**< Imposed outside-in payload buffer */
    size_t                 payload_count;              /**< Count of incoming items to encapsulate */
    omni_container_t       vessel;                     /**< Concrete bounded vessel envelope */
    uintptr_t              target_destination;         /**< Destination memory address or anchor */
    omni_quad_state_t      status;                     /**< Active Quad-State truth */
    omni_tripwire_state_t  tripwire;                   /**< Subsystem safety interlock */
} omni_container_context_t;

/* ================================================================================
 * BLOCK 2: OPENING BLOCK
 * ( Outside-in Imposition & Context Initialization )
 * ================================================================================ */

/**
 * @brief Initializes a Container context over a provided memory storage partition.
 *
 * @param ctx Pointer to caller-allocated container context.
 * @param storage Memory buffer allocated by the caller (stack or static).
 * @param elem_size Footprint of a single element in bytes.
 * @param capacity Maximum number of elements storage can hold.
 * @param payload Outside-in memory payload to encapsulate.
 * @param payload_count Number of elements in the incoming payload.
 */
void omni_container_open(omni_container_context_t *ctx,
                         void *storage,
                         size_t elem_size,
                         size_t capacity,
                         const void *payload,
                         size_t payload_count);

/* ================================================================================
 * BLOCK 3: BODY BLOCK
 * ( Operational Primitives, Containment Laws & Inscriptions )
 * ================================================================================ */

/**
 * @brief Initializes a generic bounded container slice over an existing memory buffer.
 *
 * @param c Pointer to container struct to initialize.
 * @param buffer Pointer to underlying memory array.
 * @param element_size Byte size of each element.
 * @param capacity Maximum number of elements.
 */
void omni_container_init(omni_container_t *c, void *buffer, size_t element_size, size_t capacity);

/**
 * @brief Initializes a canonical 64-byte storage vessel.
 *
 * @param vessel Pointer to byte vessel struct.
 */
void omni_byte_vessel_init(omni_byte_vessel_t *vessel);

/**
 * @brief Core Containment Law Verification: Proves that Occupancy <= Capacity.
 *
 * @param c Pointer to container to evaluate.
 * @return true if Occupancy <= Capacity and properly enclosed; false otherwise.
 */
bool omni_container_verify_containment(const omni_container_t *c);

/**
 * @brief Queries whether the container has reached its maximum capacity limit.
 *
 * @param c Pointer to container.
 * @return true if Occupancy >= Capacity; false otherwise.
 */
bool omni_container_is_full(const omni_container_t *c);

/**
 * @brief Queries whether the container has zero stored elements.
 *
```

```
 * @param c Pointer to container.
 * @return true if Occupancy == 0; false otherwise.
 */
bool omni_container_is_empty(const omni_container_t *c);

/**
 * @brief Pushes an element into the container, advancing occupancy by 1.
 *
 * @param c Pointer to container.
 * @param element Pointer to element data to copy in.
 * @return OMNI_STATE_PROCEED on successful insertion; OMNI_STATE_ROLLBACK if full.
 */
omni_quad_state_t omni_container_push(omni_container_t *c, const void *element);

/**
 * @brief Retrieves a direct pointer to the element at the specified index.
 *
 * @param c Pointer to container.
 * @param index 0-based element index.
 * @return Pointer to element memory, or NULL if index >= occupancy.
 */
void *omni_container_get(const omni_container_t *c, size_t index);

/**
 * @brief Replaces or writes an element at the specified index.
 *
 * @param c Pointer to container.
 * @param index 0-based element index.
 * @param element Pointer to element data to copy in.
 * @return OMNI_STATE_PROCEED on success; OMNI_STATE_ROLLBACK if index >= capacity.
 */
omni_quad_state_t omni_container_set(omni_container_t *c, size_t index, const void *element);

/**
 * @brief Resets container occupancy to zero without clearing underlying memory.
 *
 * @param c Pointer to container.
 */
void omni_container_clear(omni_container_t *c);

/**
 * @brief Executes the full encapsulation lifecycle across declared rolls:
 *   - Roll 1: Build capsule envelope with numbers.
 *   - Roll 2: Encapsulate incoming payload.
 *   - Roll 3: Guard bounds under Law { Containment } (Occupancy <= Capacity).
 *   - Roll 4: Pour out and set aside vessel.
 *
 * @param ctx Pointer to active container context.
 * @return OMNI_STATE_PROCEED on equilibrium; OMNI_STATE_ROLLBACK on overflow.
 */
omni_quad_state_t omni_container_execute(omni_container_context_t *ctx);

/* ============================================================================
 * BLOCK 4: CLOSING BLOCK
 * ( Integrity Verification & Commit Status )
 * ============================================================================ */

/**
 * @brief Validates all invariants and seals the Container commit status.
 *
 * @param ctx Pointer to active container context.
 * @return OMNI_STATE_PROCEED on successful seal; OMNI_STATE_ROLLBACK if tripped.
 */
omni_quad_state_t omni_container_close(omni_container_context_t *ctx);

#ifdef __cplusplus
}
#endif

#endif /* OMNI_CONTAINER_H */
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/include/number.h

H | 385 LINES | 1953 WORDS | 15.1 KB

```h
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT TYPE DEFINITION
 * ( Invariant Type: < Idea { Type } : Number > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Defines scalar quantities, integers, and balanced ternary measurements in
 *   the OmniCode Standard Library Track 2 C Transpile Variant.
 *   - Base Block: Primitive Invariant Type
 *   - Category: Idea { Type }
 *   - Footprint: [ 1 Memory Word ] { 32 Balanced Trits / 64 Bits }
 *   - System: OmniCode { Lexicon }
 *   - Witness: Scripture Psalm 147:4 KJV
 *     "He telleth the number of the stars; he calleth them all by their names."
 *   - Semantics: { ScalarQuantity :: DualRailBitPlane :: ZeroSumEquilibrium }
 *
 * DUAL-RAIL BIT-PLANE SUBSTRATE:
 *   Every trit is physically encoded as a 2-bit pair (N, P) on binary silicon:
 *     - 00: Equilibrium / True Zero (Neither rail active)
 *     - 01: Positive Unity / +1 (Positive rail P active, bit 0)
 *     - 10: Negative Unity / -1 (Negative rail N active, bit 1)
 *     - 11: Collision / NULL Trap (Both rails active: Tripwire fault)
 *   A 32-trit Word maps bijectively onto a native 64-bit integer (uint64_t).
 *
 * DYNAMIC PACKING TOPOLOGIES:
 *   Byte bit-packing is dynamic and kinematic:
 *     - 2-2-2-2: Pure dense packing (4 trits per byte, 32 trits per 64-bit word)
 *     - 2-1-2-1-2: Symmetric resting equilibrium with carry/guard channels
 *     - 1-2-1-2-2: Prefix carry (Leftward tape advance carry propagation)
 *     - 2-2-1-2-1: Postfix carry (Rightward tape rewind borrow propagation)
 *     - 3-3-2, 3-2-3, 2-3-3: 3-space directional partitions (Z-axis magnitude)
 * ============================================================================ */

#ifndef OMNI_NUMBER_H
#define OMNI_NUMBER_H

#include "omni_base.h"
#include <stdint.h>
#include <stdbool.h>
#include <stddef.h>

#ifdef __cplusplus
extern "C" {
#endif

/* ----------------------------------------------------------------------------
 * 1. INVARIANT CONSTANTS, EXEMPLARS & BIT-PLANE MASKS
 * ---------------------------------------------------------------------------- */

/** Number of balanced trits per machine word. */
#define OMNI_NUM_TRITS_PER_WORD     OMNI_TRITS_PER_WORD
#define OMNI_NUMBER_TRITS_PER_WORD  OMNI_TRITS_PER_WORD

/** Canonical Zero Exemplar: Perfect balance and null displacement. */
#define OMNI_EXEMPLAR_ZERO          ((int64_t)0)

/** Canonical Positive Unity Exemplar: Forward causal affirmation (+1). */
#define OMNI_EXEMPLAR_UNITY_POS     ((int64_t)1)

/** Canonical Negative Unity Exemplar: Backward causal restoration (-1). */
#define OMNI_EXEMPLAR_UNITY_NEG     ((int64_t)-1)

/** Canonical Memory Partition Exemplar: Standard 4096-unit allocation boundary. */
#define OMNI_EXEMPLAR_PARTITION     ((int64_t)4096)

/** Primary Hardware Register Destination: Arithmetic Accumulator. */
#define OMNI_TARGET_ACCUMULATOR     ((uintptr_t)0x00000000)

/** Dual-Rail Positive Bit-Plane Mask (All even bits: 0, 2, 4, ... 62). */
#define OMNI_BITPLANE_POS_MASK      (0x5555555555555555ULL)

/** Dual-Rail Negative Bit-Plane Mask (All odd bits: 1, 3, 5, ... 63). */
#define OMNI_BITPLANE_NEG_MASK      (0xAAAAAAAAAAAAAAAAULL)

```

```c
/** Dual-Rail 2-Bit Trit Constants. */
#define OMNI_TRIT_PAIR_ZERO         ((uint8_t)0x00) /* 00: Equilibrium (0) */
#define OMNI_TRIT_PAIR_POS          ((uint8_t)0x01) /* 01: Positive (+1)   */
#define OMNI_TRIT_PAIR_NEG          ((uint8_t)0x02) /* 10: Negative (-1)   */
#define OMNI_TRIT_PAIR_NULL         ((uint8_t)0x03) /* 11: Collision (NULL)*/

/* ---------------------------------------------------------------------------
 * 2. DYNAMIC PACKING TOPOLOGY ENUM
 * --------------------------------------------------------------------------- */

/**
 * @brief Dynamic bit-packing topologies for bytes and 64-bit words.
 */
typedef enum {
    OMNI_PACK_2_2_2_2   = 0, /**< Pure dense packing (4 trits / byte) */
    OMNI_PACK_2_1_2_1_2 = 1, /**< Palindromic symmetric resting equilibrium */
    OMNI_PACK_1_2_1_2_2 = 2, /**< Prefix carry: Leftward tape advance */
    OMNI_PACK_2_2_1_2_1 = 3, /**< Postfix carry: Rightward tape rewind */
    OMNI_PACK_3_3_2     = 4, /**< 3-space directional partition (3-3-2) */
    OMNI_PACK_3_2_3     = 5, /**< 3-space directional partition (3-2-3) */
    OMNI_PACK_2_3_3     = 6  /**< 3-space directional partition (2-3-3) */
} omni_pack_mode_t;

/* ---------------------------------------------------------------------------
 * 3. FREESTANDING INVARIANT TYPE STRUCTURE: omni_number_t
 * --------------------------------------------------------------------------- */

/**
 * @brief Invariant Type < Number >: The scalar quantity and measurement metric.
 *
 * Encloses the dual substrate:
 *   1. Physical Silicon Substrate: 64-Bit Signed Integer Scalar (int64_t).
 *   2. Dual-Rail Packed Substrate: Native 64-bit packed bit-planes (N, P).
 *   3. Virtual Balanced Trit Substrate: 32-Trit Machine Word array.
 *
 * Core Invariant Law:
 *   ENCLOSE [ Number ] WITHIN [ 1 Memory Word ] (Strict 32-trit capacity).
 *   LAW { Equilibrium } : [ (+1) plus (-1) <=> 0 ] (Foundational balance).
 */
typedef struct {
    int64_t     scalar;                             /**< 64-bit scalar integer */
    uint64_t    packed_trits;                       /**< Dual-rail bit-planes (N, P) */
    omni_trit_t trits[OMNI_NUM_TRITS_PER_WORD];     /**< Unpacked 32 balanced trits */
    bool        is_enclosed;                        /**< Boundary enclosure seal */
} omni_number_t;

/* ---------------------------------------------------------------------------
 * 4. PURE INVARIANT OPERATIONS, BIT-PLANE & DUAL-RAIL LAWS
 * --------------------------------------------------------------------------- */

/**
 * @brief Constructs a Number directly from a 64-bit scalar integer,
 *        automatically transducing it into dual-rail packed bit-planes
 *        and 32 balanced trits.
 *
 * @param scalar The 64-bit integer quantity to measure.
 * @return Fully initialized omni_number_t with is_enclosed = true.
 */
omni_number_t omni_number_from_scalar(int64_t scalar);

/**
 * @brief Bijective Radix-3 Transduction: Maps a 64-bit scalar to 32 balanced trits.
 *
 * @param val Input 64-bit scalar quantity.
 * @param out_trits Array of 32 balanced trits receiving the transduction.
 */
void omni_number_transduce(int64_t val, omni_trit_t out_trits[OMNI_NUM_TRITS_PER_WORD]);

/**
 * @brief Inverse Transduction: Reconstructs a 64-bit scalar from 32 balanced trits.
 *
 * @param trits Array of 32 balanced trits.
 * @return Reconstructed 64-bit signed integer value.
 */
int64_t omni_number_to_scalar(const omni_trit_t trits[OMNI_NUM_TRITS_PER_WORD]);

/**
 * @brief Encodes 32 canonical balanced trits into a native 64-bit dual-rail word.
```

```
 *
 * @param trits Array of 32 balanced trits {-1, 0, +1}.
 * @return Packed 64-bit dual-rail word (N, P bit-planes).
 */
uint64_t omni_number_pack_trits(const omni_trit_t trits[OMNI_NUM_TRITS_PER_WORD]);

/**
 * @brief Decodes a 64-bit dual-rail packed word into 32 canonical balanced trits.
 *
 * @param packed Packed 64-bit dual-rail word.
 * @param out_trits Destination array of 32 balanced trits.
 */
void omni_number_unpack_trits(uint64_t packed, omni_trit_t out_trits[OMNI_NUM_TRITS_PER_WORD]);

/**
 * @brief Instant O(1) Bit-Plane Negation: Swaps the positive and negative
 *        bit-planes across all 32 trits simultaneously with zero carry chains.
 *
 * @param packed Packed 64-bit dual-rail word.
 * @return Negated 64-bit dual-rail word (+N <-> -N).
 */
uint64_t omni_number_trits_negate(uint64_t packed);

/**
 * @brief Instant O(1) Collision Detection: Verifies that no trit in the word
 *        holds the illegal collision state (11: NULL).
 *
 * @param packed Packed 64-bit dual-rail word.
 * @return true if any trit is in collision (11: NULL); false if clean.
 */
bool omni_number_trits_has_null(uint64_t packed);

/**
 * @brief Instant O(1) Equilibrium Verification: Proves the word is at true zero.
 *
 * @param packed Packed 64-bit dual-rail word.
 * @return true if all trits are in resting zero equilibrium (00); false otherwise.
 */
bool omni_number_trits_is_equilibrium(uint64_t packed);

/**
 * @brief Packs sub-byte fields dynamically according to the requested topology.
 *
 * @param f1 First field value.
 * @param f2 Second field value.
 * @param f3 Third field value.
 * @param f4 Fourth field value (used in 2-2-2-2 and 5-segment modes).
 * @param f5 Fifth field value (used in 2-1-2-1-2, 1-2-1-2-2, 2-2-1-2-1).
 * @param mode Dynamic packing topology enum.
 * @return Packed 8-bit byte.
 */
uint8_t omni_number_pack_byte(uint8_t f1, uint8_t f2, uint8_t f3,
                              uint8_t f4, uint8_t f5, omni_pack_mode_t mode);

/**
 * @brief Unpacks an 8-bit byte into sub-byte fields based on topology.
 *
 * @param byte_val Input 8-bit byte.
 * @param out_fields Destination array of 5 field values.
 * @param mode Dynamic packing topology enum.
 */
void omni_number_unpack_byte(uint8_t byte_val, uint8_t out_fields[5],
                             omni_pack_mode_t mode);

/**
 * @brief Verifies the ALU Core Arithmetic Equilibrium Law: (+1) plus (-1) <=> 0.
 *
 * @return true if zero-sum balance holds; false otherwise.
 */
bool omni_number_verify_equilibrium(void);

/**
 * @brief Adds two Numbers producing a new balanced Number word.
 *
 * @param a First number summand.
 * @param b Second number summand.
 * @return Resulting sum as an invariant omni_number_t.
 */
```

```
omni_number_t omni_number_add(omni_number_t a, omni_number_t b);

/**
 * @brief Subtracts two Numbers via exact balanced ternary negation: a + (-b).
 *
 * @param a Minuend number.
 * @param b Subtrahend number to negate and add.
 * @return Resulting difference as an invariant omni_number_t.
 */
omni_number_t omni_number_sub(omni_number_t a, omni_number_t b);

/**
 * @brief Negates a Number producing its exact symmetric polar opposite.
 *
 * @param a Number to negate.
 * @return Negated number with swapped bit-planes.
 */
omni_number_t omni_number_neg(omni_number_t a);

/**
 * @brief Evaluates relational equality between two numbers.
 *
 * @param a First number operand.
 * @param b Second number operand.
 * @return true if scalar values match and both are enclosed; false otherwise.
 */
bool omni_number_eq(const omni_number_t *a, const omni_number_t *b);

/**
 * @brief Verifies that a number is properly enclosed within single-word bounds
 *        and free of NULL collision traps.
 *
 * @param n Pointer to number to verify.
 * @return true if valid, enclosed, and trap-free; false otherwise.
 */
bool omni_number_verify_bounds(const omni_number_t *n);

/* ============================================================================
 * BLOCK 2: OPENING BLOCK
 * ( Outside-In Imposition, Accumulator Binding & Preconditions )
 * ============================================================================ */

/**
 * @brief Execution context for Number measurement and ALU lifecycle rolls.
 */
typedef struct {
    int64_t               input_quantity;     /**< Outside-in scalar payload */
    omni_number_t         number;             /**< Concrete single-word allocation */
    uintptr_t             target_accumulator; /**< Target accumulator destination */
    void                 *sequence_target;    /**< Destination for Vector sequence */
    omni_quad_state_t     status;             /**< Active Quad-State truth */
    omni_tripwire_state_t tripwire;           /**< Subsystem safety interlock */
} omni_number_context_t;

/**
 * @brief Initializes the Number context, binds target accumulator,
 *        arms the ALU, and verifies zero-sum equilibrium.
 *
 * Evaluates OmniCode Block 2: Opening { ... }
 *
 * @param ctx Pointer to caller-allocated number context.
 * @param input_quantity Outside-in scalar quantity (defaults to 4096 if 0).
 * @param target_accumulator Target accumulator register (defaults to 0x00).
 */
void omni_number_open(omni_number_context_t *ctx, int64_t input_quantity,
                      uintptr_t target_accumulator);

/* ============================================================================
 * BLOCK 3: BODY BLOCK
 * ( Operational Rolls, Guard Interlocks & Vector Sequencing )
 * ============================================================================ */

/**
 * @brief Roll 1: Inscribes outside-in quantity into the word container.
 *
 * Evaluates OmniCode: [ Inscribe ] : { Quantity ] --> INSCRIBE [ Word ] = [ Number` ]
 *
 * @param ctx Active execution context.
```

```
 * @param quantity The scalar quantity being inscribed.
 */
void omni_number_inscribe(omni_number_context_t *ctx, int64_t quantity);

/**
 * @brief Roll 2: Transduces Number` through the balanced ternary ALU.
 *
 * Evaluates OmniCode: [ Transduce ] : [ Number` { 64 Bits } ] <=> TRANSDUCE [ Word` { 32 Trits } ]
 *
 * @param ctx Active execution context.
 */
void omni_number_transduce_context(omni_number_context_t *ctx);

/**
 * @brief Roll 3: Evaluates adversative guard assertion (!).
 *
 * Evaluates OmniCode: [ Compare ] : { Number` = Quantity } & { Number` <= [ 1 Word ] }
 *                     ! GUARD --> [ Status` = +1:PROCEED ]
 *
 * @param ctx Active execution context.
 * @return OMNI_STATE_PROCEED on equilibrium; OMNI_STATE_ROLLBACK on violation.
 */
omni_quad_state_t omni_number_guard(omni_number_context_t *ctx);

/**
 * @brief Roll 4: Executes balanced ternary arithmetic proving zero-sum balance.
 *
 * Evaluates OmniCode: [ Calculate ] : [ ALU ] :
 *                     [ (+1) plus (-1) ] <=> CALCULATE [ 0 ] = [ Equilibrium` ]
 *
 * @param ctx Active execution context.
 * @return OMNI_STATE_PROCEED on confirmed balance; OMNI_STATE_ROLLBACK on disequilibrium.
 */
omni_quad_state_t omni_number_calculate(omni_number_context_t *ctx);

/**
 * @brief Roll 5: Yields Number` to continuous Vector coordinate sequence.
 *
 * Evaluates OmniCode: [ Sequence ] : [ Number` } --> SEQUENCE [ Vector ] = [ Vector` ]
 *
 * @param n Pointer to the Number being sequenced.
 * @param sequence_target Pointer to destination vector container.
 * @return true if sequence yield succeeded; false on overflow.
 */
bool omni_number_sequence(const omni_number_t *n, void *sequence_target);

/**
 * @brief Executes the complete 5-roll operational pipeline across declared turns:
 *   Roll 1 (Inscribe) -> Roll 2 (Transduce) -> Roll 3 (Guard !) ->
 *   Roll 4 (Calculate) -> Roll 5 (Sequence).
 *
 * @param ctx Pointer to active number context.
 * @return OMNI_STATE_PROCEED on equilibrium; OMNI_STATE_ROLLBACK on violation.
 */
omni_quad_state_t omni_number_execute(omni_number_context_t *ctx);

/* ============================================================================
 * BLOCK 4: CLOSING BLOCK
 * ( Integrity Verification & Commit Status )
 * ============================================================================ */

/**
 * @brief Validates all invariants, verifies consensus, disarms tripwire,
 *        and seals the final Number commit status (+1:PROCEED).
 *
 * Evaluates OmniCode Block 4: Closing { ... }
 *
 * @param ctx Pointer to active number context.
 * @return OMNI_STATE_PROCEED on successful seal; OMNI_STATE_ROLLBACK if tripped.
 */
omni_quad_state_t omni_number_close(omni_number_context_t *ctx);

#ifdef __cplusplus
}
#endif

#endif /* OMNI_NUMBER_H */
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/include/omni.h

H | 27 LINES | 136 WORDS | 1.1 KB

```c
/* ============================================================================
 * OMNICODE FREESTANDING STANDARD LIBRARY (C MASTER HEADER)
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Umbrella header exposing all primitive invariant types and operational
 *   primitives for OmniCode bare-metal and hosted runtimes.
 *   - Category: Standard Library Track 2 C Transpile Variant
 *   - Invariant Types Included:
 *       < Character > : Atomic Glyph / Letter Rune (1 Cell / 5 Trits)
 *       < Number >    : Scalar Quantity / Measure (1 Word / 32 Trits)
 *       < Container > : Generic Bounded Space Envelope / Slice
 *       < Site >      : Silicon Coordinate / Address (RAM @ vs MMIO ::@)
 *       < State >     : Quad-State Causal Truth & Loop Stepper
 * ============================================================================ */

#ifndef OMNI_H
#define OMNI_H

#include "omni_base.h"
#include "character.h"
#include "number.h"
#include "container.h"
#include "site.h"
#include "state.h"

#endif /* OMNI_H */
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/include/omni_base.h

H | 289 LINES | 1270 WORDS | 10.6 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT AXIOMS BLOCK
 * ( Invariant Root: < Lexicon { Types of Ideas } > & [ Noun { Base Axioms } ] )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Foundational bare-metal substrates, balanced ternary types, and Quad-State
 *   truth logic governing the OmniCode Standard Library Track 2 C Transpile Variant.
 *   - Environment: Freestanding C99/C11 (Zero libc/OS dependency)
 *   - Word Size: 64-Bit Silicon Scalar / 32 Balanced Trits
 *   - Cell Size: 8-Bit Byte / 5 Balanced Trits
 *   - System: OmniCode { Lexicon }
 *   - Witness: Scripture Proverbs 11:1 KJV
 *     "A false balance is abomination to the LORD: but a just weight is his delight."
 *   - Semantics: { BalancedTernary :: QuadStateTruth :: SiliconAnchors :: TripwireGuards }
 * ============================================================================ */

#ifndef OMNI_BASE_H
#define OMNI_BASE_H

#include <stdint.h>
#include <stdbool.h>
#include <stddef.h>

#ifdef __cplusplus
extern "C" {
#endif

/* ----------------------------------------------------------------------------
 * ARCHITECTURAL CONSTANTS & SUBSTRATE CAPACITIES
 * ---------------------------------------------------------------------------- */

/** Number of balanced trits packed into a single 8-bit memory Cell (3^5 = 243 states). */
#define OMNI_TRITS_PER_CELL         5

/** Number of balanced trits packed into a single 64-bit machine Word. */
#define OMNI_TRITS_PER_WORD         32

/** Footprint of the standard bounded Container vessel exemplar (in bytes). */
#define OMNI_VESSEL_DEFAULT_CELLS   64

/* ----------------------------------------------------------------------------
 * 1. BALANCED TERNARY SUBSTRATE: omni_trit_t
 * ---------------------------------------------------------------------------- */

/**
 * @brief Discrete balanced ternary digit (-1, 0, +1).
 *
 * Unlike binary (0, 1), balanced ternary is inherently symmetrical around zero:
 *   - Negative (-1) : Backward causation, negation, deficit, or restoration.
 *   - Zero     ( 0) : Equilibrium, standby, neutral, or unperturbed balance.
 *   - Positive (+1) : Forward causation, affirmative assertion, or surplus.
 */
typedef int8_t omni_trit_t;

#define OMNI_TRIT_NEG   ((omni_trit_t)-1)
#define OMNI_TRIT_ZERO  ((omni_trit_t) 0)
#define OMNI_TRIT_POS   ((omni_trit_t) 1)

/* ----------------------------------------------------------------------------
 * 2. QUAD-STATE CAUSAL TRUTH: omni_quad_state_t
 * ---------------------------------------------------------------------------- */

/**
 * @brief The fourfold causal truth states of computation in OmniCode.
 *
 * Unifies boolean logic, error handling, scheduling, and processor clock detents:
 *   - OMNI_STATE_PROCEED  (+1) : Forward Causation (+t). Operation completed in equilibrium.
 *   - OMNI_STATE_AWAIT    ( 0) : Equilibrium Standby (t=t). Pending asynchronous resolution.
 *   - OMNI_STATE_ROLLBACK (-1) : Retroactive Reversal (-t). Guard tripped; unwind causal drift.
 *   - OMNI_STATE_HALT   (-128) : Terminal Detent (t=empty). Clock detent; permanent halt (HLT).
 */
typedef enum {
    OMNI_STATE_ROLLBACK = -1,   /**< -1 : Retroactive Reversal / Error / Unwind */
```

```
    OMNI_STATE_AWAIT    =  0,   /**<  0 : Equilibrium Standby / Hold Pending */
    OMNI_STATE_PROCEED  =  1,   /**< +1 : Forward Causation / Affirmative Advancement */
    OMNI_STATE_HALT     = -128  /**< NULL : Terminal Detent / Stop Processor Clock */
} omni_quad_state_t;

/**
 * @brief Tertiary execution status subset for non-terminal roll checkpoints.
 */
typedef enum {
    OMNI_STATUS_ROLLBACK = -1,
    OMNI_STATUS_AWAIT    =  0,
    OMNI_STATUS_PROCEED  =  1
} omni_status_t;

/* ---------------------------------------------------------------------------
 * 3. HARDWARE COGNITIVE SITES (EXEMPLARS)
 * --------------------------------------------------------------------------- */

/** Unmapped null pointer origin. */
#define OMNI_SITE_NULL          ((uintptr_t)0x00000000)

/** Real-mode Master Boot Record physical origin. */
#define OMNI_SITE_MBR_BOOT      ((uintptr_t)0x00007C00)

/** Hardware UART serial port base (COM1) for kernel telemetry. */
#define OMNI_SITE_COM1          ((uintptr_t)0x000003F8)

/** Physical memory-mapped VGA text-mode display buffer (80x25 characters). */
#define OMNI_SITE_VGA_BUFFER    ((uintptr_t)0x000B8000)

/* ---------------------------------------------------------------------------
 * 4. TRIPWIRE & INTEGRITY DETENTS: omni_tripwire_state_t
 * --------------------------------------------------------------------------- */

/**
 * @brief Safety interlock state preventing silent memory corruption or causal leakage.
 */
typedef enum {
    OMNI_TRIPWIRE_DISARMED = 0, /**< Interlock inactive; safe quiescent state */
    OMNI_TRIPWIRE_ARMED    = 1, /**< Active guard monitoring execution bounds */
    OMNI_TRIPWIRE_TRIPPED  = 2  /**< Violation intercepted; execution blocked */
} omni_tripwire_state_t;

/* ===========================================================================
 * BLOCK 2: OPENING BLOCK
 * ( Subsystem Preconditions, Verification & Initializers )
 * =========================================================================== */

/**
 * @brief Verifies that the host hardware meets OmniCode's bare-metal preconditions:
 *   1. Standard 64-bit pointer architecture (sizeof(uintptr_t) == 8).
 *   2. Standard 8-bit octet cell substrate (sizeof(uint8_t) == 1).
 *   3. Zero-sum arithmetic equilibrium ((+1) + (-1) == 0).
 *
 * @return OMNI_STATE_PROCEED if all preconditions hold; OMNI_STATE_ROLLBACK otherwise.
 */
static inline omni_quad_state_t omni_base_verify_preconditions(void) {
    if (sizeof(uintptr_t) != 8) return OMNI_STATE_ROLLBACK;
    if (sizeof(uint8_t)   != 1) return OMNI_STATE_ROLLBACK;

    /* Prove Proverbs 11:1 Law { Equilibrium }: (+1) plus (-1) <=> 0 */
    omni_trit_t pos = OMNI_TRIT_POS;
    omni_trit_t neg = OMNI_TRIT_NEG;
    if ((pos + neg) != OMNI_TRIT_ZERO) return OMNI_STATE_ROLLBACK;

    return OMNI_STATE_PROCEED;
}

/**
 * @brief Arms a tripwire interlock before entering an untrusted or dynamic execution block.
 */
static inline void omni_tripwire_arm(omni_tripwire_state_t *tw) {
    if (tw) *tw = OMNI_TRIPWIRE_ARMED;
}

/**
 * @brief Disarms a tripwire upon successful verification and closing commit.
 */
```

```c
static inline void omni_tripwire_disarm(omni_tripwire_state_t *tw) {
    if (tw) *tw = OMNI_TRIPWIRE_DISARMED;
}

/**
 * @brief Immediately trips the interlock, halting forward causation.
 */
static inline void omni_tripwire_trip(omni_tripwire_state_t *tw) {
    if (tw) *tw = OMNI_TRIPWIRE_TRIPPED;
}

/* ============================================================================
 * BLOCK 3: BODY BLOCK
 * ( Balanced Ternary Algebra, Quad-State Logic & Guard Inlines )
 * ============================================================================ */

/**
 * @brief Negates a balanced trit along the causal vector (-t <=> +t).
 */
static inline omni_trit_t omni_trit_negate(omni_trit_t t) {
    return (omni_trit_t)(-t);
}

/**
 * @brief Multiplies two balanced trits (commutative zero-sum product).
 */
static inline omni_trit_t omni_trit_multiply(omni_trit_t a, omni_trit_t b) {
    return (omni_trit_t)(a * b);
}

/**
 * @brief Full 1-trit balanced ternary adder with carry output.
 *
 * Truth Table:
 *   a   b  cin | sum carry
 *  -1  -1   -1 |   0    -1
 *  -1  -1    0 |  +1    -1
 *  -1  -1   +1 |  -1     0
 *  -1   0    0 |  -1     0
 *  -1  +1    0 |   0     0  (Equilibrium)
 *  +1  +1    0 |  -1    +1
 *  +1  +1   +1 |   0    +1
 */
static inline omni_trit_t omni_trit_add(omni_trit_t a, omni_trit_t b, omni_trit_t cin, omni_trit_t *cout) {
    int32_t sum = (int32_t)a + (int32_t)b + (int32_t)cin;
    omni_trit_t carry = 0;

    if (sum > 1) {
        sum -= 3;
        carry = 1;
    } else if (sum < -1) {
        sum += 3;
        carry = -1;
    }

    if (cout) *cout = carry;
    return (omni_trit_t)sum;
}

/**
 * @brief Evaluates an invariant guard condition.
 *
 * If condition evaluates to true:
 *   Status is confirmed in PROCEED (+1).
 * If condition evaluates to false:
 *   Tripwire is tripped and status transitions to ROLLBACK (-1).
 */
static inline omni_quad_state_t omni_guard_assert(bool condition,
                                                  omni_tripwire_state_t *tw,
                                                  omni_quad_state_t *status) {
    if (condition) {
        if (status) *status = OMNI_STATE_PROCEED;
        return OMNI_STATE_PROCEED;
    } else {
        if (tw) *tw = OMNI_TRIPWIRE_TRIPPED;
        if (status) *status = OMNI_STATE_ROLLBACK;
        return OMNI_STATE_ROLLBACK;
    }
```

```
}

/** Predicate queries for Quad-State truth */
static inline bool omni_is_proceed(omni_quad_state_t s) { return (s == OMNI_STATE_PROCEED); }
static inline bool omni_is_await(omni_quad_state_t s)   { return (s == OMNI_STATE_AWAIT); }
static inline bool omni_is_rollback(omni_quad_state_t s){ return (s == OMNI_STATE_ROLLBACK); }
static inline bool omni_is_halt(omni_quad_state_t s)    { return (s == OMNI_STATE_HALT); }

/* ============================================================================
 * BLOCK 4: CLOSING BLOCK
 * ( Integrity Seals, Detents & Commit Status Functions )
 * ============================================================================ */

/**
 * @brief Validates the integrity of an execution context before sealing the commit status.
 *
 * Verifies that:
 *   1. No tripwire was tripped during execution.
 *   2. Machine status is not trapped in an unhandled rollback.
 *
 * @return OMNI_STATE_PROCEED if context is clean; OMNI_STATE_ROLLBACK on failure.
 */
static inline omni_quad_state_t omni_base_verify_integrity(omni_tripwire_state_t tw,
                                                           omni_quad_state_t status) {
    if (tw == OMNI_TRIPWIRE_TRIPPED || status == OMNI_STATE_ROLLBACK) {
        return OMNI_STATE_ROLLBACK;
    }
    return OMNI_STATE_PROCEED;
}

/**
 * @brief Closes and seals an execution block in PROCEED (+1).
 */
static inline omni_quad_state_t omni_commit_proceed(omni_tripwire_state_t *tw) {
    omni_tripwire_disarm(tw);
    return OMNI_STATE_PROCEED;
}

/**
 * @brief Closes and seals an execution block in ROLLBACK (-1).
 */
static inline omni_quad_state_t omni_commit_rollback(omni_tripwire_state_t *tw) {
    omni_tripwire_trip(tw);
    return OMNI_STATE_ROLLBACK;
}

/**
 * @brief Closes and seals an execution block in terminal detent HALT:NULL.
 */
static inline omni_quad_state_t omni_commit_halt(omni_tripwire_state_t *tw) {
    omni_tripwire_disarm(tw);
    return OMNI_STATE_HALT;
}

#ifdef __cplusplus
}
#endif

#endif /* OMNI_BASE_H */
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/include/site.h

H | 191 LINES | 925 WORDS | 7.4 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT TYPE DEFINITION
 * ( Invariant Type: < Idea { Type } : Site > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Defines physical memory addresses, hardware ports, and MMIO coordinates in the
 *   OmniCode Standard Library Track 2 C Transpile Variant.
 *   - Base Block: Primitive Invariant Type
 *   - Category: Idea { Type }
 *   - Footprint: [ 1 Address ] { 64-Bit Pointer / Physical Silicon Coordinate }
 *   - Ladder Ascension: Builds up with Numbers (/-^)
 *   - System: OmniCode { Lexicon }
 *   - Witness: Scripture Genesis 28:16 KJV
 *     "And Jacob awaked out of his sleep, and he said, Surely the Lord is in
 *      this place; and I knew it not."
 *   - Semantics: { PhysicalAddress :: MMIOPort :: SiliconCoordinate :: RoutingLaw }
 * ============================================================================ */

#ifndef OMNI_SITE_H
#define OMNI_SITE_H

#include "omni_base.h"

#ifdef __cplusplus
extern "C" {
#endif

/* ----------------------------------------------------------------------------
 * 1. HARDWARE ROUTING DOMAIN ENUM: omni_site_routing_t
 * ---------------------------------------------------------------------------- */

/**
 * @brief Hardware Routing Law domain classification.
 *
 * Law { Routing }:
 *   - RAM Physical (@)   : Standard cacheable RAM memory pointer.
 *   - MMIO Hardware (::@) : Memory-mapped I/O port requiring volatile access.
 */
typedef enum {
    OMNI_ROUTING_RAM_PHYSICAL  = 0, /**< '@' Physical system RAM address */
    OMNI_ROUTING_HARDWARE_MMIO = 1  /**< '::@' Hardware MMIO device register or port */
} omni_site_routing_t;

/* ----------------------------------------------------------------------------
 * 2. FREESTANDING INVARIANT TYPE STRUCTURE: omni_site_t
 * ---------------------------------------------------------------------------- */

/**
 * @brief Invariant Type < Site >: The physical silicon address coordinate.
 *
 * Encloses the 64-bit silicon address pointer and its hardware routing domain:
 *   - Strictly non-null when valid (0x0 is mapped to unmapped detent).
 *   - Resolves routing bijectively between RAM and device hardware ports.
 *
 * Core Invariant Law:
 *   ENCLOSE [ Site ] WITHIN [ 1 Address ]
 *   LAW { Routing } : [ Physical RAM @ ] | [ Hardware MMIO ::@ ]
 */
typedef struct {
    uintptr_t           coordinate;                  /**< Physical 64-bit silicon address pointer */
    omni_site_routing_t routing;                     /**< Hardware routing classification (RAM vs MMIO) */
    bool                is_enclosed;                 /**< Invariant boundary enclosure guarantee */
} omni_site_t;

/* ----------------------------------------------------------------------------
 * 3. 4-BLOCK PIPELINE CONTEXT: omni_site_context_t
 * ---------------------------------------------------------------------------- */

/**
 * @brief Execution context for Site address binding and routing lifecycle rolls.
 */
typedef struct {
    uintptr_t             input_coordinate;          /**< Outside-in target silicon coordinate */
```

```
    omni_site_t           site;                         /**< Concrete single-address allocation */
    omni_quad_state_t     status;                       /**< Active Quad-State truth */
    omni_tripwire_state_t tripwire;                     /**< Subsystem safety interlock */
} omni_site_context_t;

/* ============================================================================
 * BLOCK 2: OPENING BLOCK
 * ( Outside-in Imposition & Context Initialization )
 * ============================================================================ */

/**
 * @brief Initializes the Site context and binds the target coordinate.
 *
 * @param ctx Pointer to caller-allocated site context.
 * @param input_coord Target silicon address (defaults to VGA buffer if 0).
 */
void omni_site_open(omni_site_context_t *ctx, uintptr_t input_coord);

/* ============================================================================
 * BLOCK 3: BODY BLOCK
 * ( Operational Primitives, Routing Laws & Memory Access )
 * ============================================================================ */

/**
 * @brief Constructs a Site directly from a 64-bit address pointer,
 *        automatically resolving its hardware routing classification.
 *
 * @param address Physical silicon memory or MMIO address.
 * @return Fully initialized omni_site_t.
 */
omni_site_t omni_site_from_address(uintptr_t address);

/**
 * @brief Hardware Routing Law: Distinguishes physical RAM pointers from
 *        hardware MMIO registers and serial ports.
 *
 * @param address Physical target address.
 * @return OMNI_ROUTING_HARDWARE_MMIO if within device port ranges; RAM otherwise.
 */
omni_site_routing_t omni_site_resolve_routing(uintptr_t address);

/**
 * @brief Calculates an offset Site from a base Site coordinate.
 *
 * @param site Base reference site pointer.
 * @param offset Signed byte displacement (+offset or -offset).
 * @return New displaced omni_site_t coordinate.
 */
omni_site_t omni_site_offset(const omni_site_t *site, intptr_t offset);

/**
 * @brief Verifies whether a site coordinate is valid and non-null.
 *
 * @param site Pointer to site to evaluate.
 * @return true if site is valid, enclosed, and non-null; false otherwise.
 */
bool omni_site_is_valid(const omni_site_t *site);

/**
 * @brief Evaluates relational equality between two sites.
 *
 * @param a First site operand.
 * @param b Second site operand.
 * @return true if addresses and routing domains match; false otherwise.
 */
bool omni_site_eq(const omni_site_t *a, const omni_site_t *b);

/**
 * @brief Safely reads an 8-bit byte from the site coordinate plus offset.
 *        Employs volatile memory semantics to prevent compiler cache elision on MMIO.
 *
 * @param site Base site coordinate.
 * @param offset Byte displacement.
 * @return Read byte value (returns 0 if site is invalid/null).
 */
uint8_t omni_site_read_u8(const omni_site_t *site, size_t offset);

/**
```

```
 * @brief Safely writes an 8-bit byte to the site coordinate plus offset.
 *        Employs volatile memory semantics for bare-metal hardware registers.
 *
 * @param site Base site coordinate.
 * @param offset Byte displacement.
 * @param value Byte value to inscribe.
 */
void omni_site_write_u8(const omni_site_t *site, size_t offset, uint8_t value);

/**
 * @brief Executes the full location lifecycle across declared rolls:
 *   - Roll 1: Locate address with numbers.
 *   - Roll 2: Bind coordinate and classify routing.
 *   - Roll 3: Guard non-null identity invariants.
 *   - Roll 4: Route and anchor memory target.
 *
 * @param ctx Pointer to active site context.
 * @return OMNI_STATE_PROCEED on valid address; OMNI_STATE_ROLLBACK on null or error.
 */
omni_quad_state_t omni_site_execute(omni_site_context_t *ctx);

/* ============================================================================
 * BLOCK 4: CLOSING BLOCK
 * ( Integrity Verification & Commit Status )
 * ============================================================================ */

/**
 * @brief Validates all invariants and seals the Site commit status.
 *
 * @param ctx Pointer to active site context.
 * @return OMNI_STATE_PROCEED on successful seal; OMNI_STATE_ROLLBACK if tripped.
 */
omni_quad_state_t omni_site_close(omni_site_context_t *ctx);

#ifdef __cplusplus
}
#endif

#endif /* OMNI_SITE_H */
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/include/state.h

H | 170 LINES | 863 WORDS | 7.1 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT TYPE DEFINITION
 * ( Invariant Type: < Idea { Type } : State > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Defines causal truth, clock progression, and the canonical Quad-State machine
 *   in the OmniCode Standard Library Track 2 C Transpile Variant.
 *   - Base Block: Primitive Invariant Type
 *   - Category: Idea { Type }
 *   - Footprint: [ 1 Trit ] { 2 Bits / Quad-State Causal Register }
 *   - Named Registers: [ STATE, TURN, BOUND, IT ]
 *   - System: OmniCode { Lexicon }
 *   - Witness: Scripture Ecclesiastes 3:1 KJV
 *     "To every thing there is a season, and a time to every purpose under
 *      the heaven:"
 *   - Semantics: { QuadStateTruth :: CausalClock :: CanonicalLoopLaw }
 * ============================================================================ */

#ifndef OMNI_STATE_H
#define OMNI_STATE_H

#include "omni_base.h"

#ifdef __cplusplus
extern "C" {
#endif

/* ----------------------------------------------------------------------------
 * 1. CANONICAL NAMED REGISTERS: omni_state_registers_t
 * ---------------------------------------------------------------------------- */

/**
 * @brief The four canonical named registers governing execution kinematics.
 *
 * Named Registers:
 *   - STATE : Primary causal truth register (+1: PROCEED, 0: AWAIT, -1: ROLLBACK, HALT: NULL).
 *   - TURN  : Discrete cadence pulse counter (increments on affirmative causation).
 *   - BOUND : Dynamic loop termination threshold.
 *   - IT    : Active accumulator iterator stepping along the causal tape.
 */
typedef struct {
    omni_quad_state_t state;                        /**< STATE: Primary Quad-State truth register */
    int64_t           turn;                         /**< TURN: Cadence step counter */
    int64_t           bound;                        /**< BOUND: Loop termination boundary */
    int64_t           it;                           /**< IT: Active accumulator iterator */
} omni_state_registers_t;

/* ----------------------------------------------------------------------------
 * 2. FREESTANDING INVARIANT TYPE STRUCTURE: omni_state_t
 * ---------------------------------------------------------------------------- */

/**
 * @brief Invariant Type < State >: The causal truth and control flow engine.
 *
 * Encloses the physical trit substrate and register bank:
 *   - Single-trit physical substrate (2 bits in silicon).
 *   - Implements the Canonical Looping Law connecting Quad-State to hardware registers.
 *
 * Core Invariant Law:
 *   LAW { Quad-State } : { T4 = [ +1:PROCEED | 0:AWAIT | -1:ROLLBACK | HALT:NULL ] }
 *   LAW { Loop } : LOOP [ WHEN [ { IT } < { BOUND } ] --> [ IT` ] PROCEED to { TURN }
 *                         ! [ { IT } > { BOUND } ] AWAIT for [ IT` ]
 *                         :: HALT WHEN [ IT` ] = NULL ]
 */
typedef struct {
    omni_trit_t             substrate_trit;         /**< 1 Trit physical substrate */
    omni_state_registers_t  registers;              /**< Canonical Quad-State register bank */
    bool                    is_enclosed;            /**< Invariant boundary enclosure guarantee */
} omni_state_t;

/* ----------------------------------------------------------------------------
 * 3. 4-BLOCK PIPELINE CONTEXT: omni_state_context_t
 * ---------------------------------------------------------------------------- */
```

```c

/**
 * @brief Execution context for State governance and loop lifecycle rolls.
 */
typedef struct {
    omni_quad_state_t     input_signal;                /**< Outside-in causal truth signal */
    omni_state_t          state_engine;                /**< Concrete single-trit register bank */
    omni_quad_state_t     status;                      /**< Active Quad-State truth */
    omni_tripwire_state_t tripwire;                    /**< Subsystem safety interlock */
} omni_state_context_t;

/* ============================================================================
 * BLOCK 2: OPENING BLOCK
 * ( Outside-in Imposition & Context Initialization )
 * ============================================================================ */

/**
 * @brief Initializes the State context with an input signal and loop boundary.
 *
 * @param ctx Pointer to caller-allocated state context.
 * @param signal Initial truth signal (defaults to PROCEED if 0).
 * @param bound_limit Maximum loop iteration threshold.
 */
void omni_state_open(omni_state_context_t *ctx, omni_quad_state_t signal, int64_t bound_limit);

/* ============================================================================
 * BLOCK 3: BODY BLOCK
 * ( Operational Primitives, Loop Laws & Transitions )
 * ============================================================================ */

/**
 * @brief Creates a freestanding State engine with specified signal and boundary.
 *
 * @param initial_signal Starting Quad-State truth.
 * @param bound Maximum loop bound.
 * @return Fully initialized omni_state_t.
 */
omni_state_t omni_state_create(omni_quad_state_t initial_signal, int64_t bound);

/**
 * @brief Canonical Loop Law Single-Step Transition:
 *
 * Executes one step of the formal loop grammar:
 *   - WHEN IT < BOUND: Increments IT and TURN; returns OMNI_STATE_PROCEED.
 *   - WHEN IT > BOUND: Transitions to standby; returns OMNI_STATE_AWAIT.
 *   - WHEN IT == BOUND: Reaches detent; returns OMNI_STATE_HALT.
 *
 * @param regs Pointer to register bank.
 * @return Resulting Quad-State condition after the step.
 */
omni_quad_state_t omni_state_step_loop(omni_state_registers_t *regs);

/**
 * @brief Resets register bank counters to 0 while setting state to PROCEED.
 *
 * @param s Pointer to state engine.
 * @param bound New loop bound.
 */
void omni_state_reset(omni_state_t *s, int64_t bound);

/** Predicate queries for State engine */
bool omni_state_is_halted(const omni_state_t *s);
bool omni_state_is_proceeding(const omni_state_t *s);
bool omni_state_is_awaiting(const omni_state_t *s);
bool omni_state_is_rollback(const omni_state_t *s);

/**
 * @brief Executes the full governance lifecycle across declared rolls:
 *   - Roll 1: Inscribe state register from input signal.
 *   - Roll 2: Evaluate caveat guard against discrepancy.
 *   - Roll 3: Execute canonical loop until boundary or detent.
 *   - Roll 4: Govern machine clock output.
 *
 * @param ctx Pointer to active state context.
 * @return Final Quad-State condition upon detent.
 */
omni_quad_state_t omni_state_execute(omni_state_context_t *ctx);

```

```
/* ============================================================================
 * BLOCK 4: CLOSING BLOCK
 * ( Integrity Verification & Commit Status )
 * ============================================================================ */

/**
 * @brief Validates all invariants and seals the State commit status.
 *
 * @param ctx Pointer to active state context.
 * @return OMNI_STATE_PROCEED on successful seal; OMNI_STATE_ROLLBACK if tripped.
 */
omni_quad_state_t omni_state_close(omni_state_context_t *ctx);

#ifdef __cplusplus
}
#endif

#endif /* OMNI_STATE_H */
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/src/character.c

C | 278 LINES | 1241 WORDS | 10.5 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT IMPLEMENTATION
 * ( Invariant Type: < Idea { Type } : Character > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Implements the atomic letter, glyph, and inscription rune in the OmniCode
 *   Standard Library Track 2 C Transpile Variant.
 *   - Base Block: Primitive Invariant Type
 *   - Category: Idea { Type }
 *   - Footprint: [ 1 Cell ] { 5 Balanced Trits / 8 Bits }
 *   - Witness: Scripture Exodus 31:18 KJV
 *     "And he gave unto Moses, when he had made an end of communing with him upon
 *      mount Sinai, two tables of testimony, tables of stone, written with the
 *      finger of God."
 *   - Semantics: { AtomicGlyph :: LetterRune :: BalancedCellTransduction }
 *   - Invariant Law:
 *     { Character } = [ Enclosed ]: TRUE (Strict single-cell capacity).
 * ============================================================================ */

#include "character.h"
#include <stdio.h>

/* ----------------------------------------------------------------------------
 * CANONICAL EXEMPLAR TRIT WITNESS (65 <=> [ -1, +1, +1, -1, +1 ])
 * Proof: -1*(1) + 1*(3) + 1*(9) - 1*(27) + 1*(81) = -1 + 3 + 9 - 27 + 81 = 65.
 * ---------------------------------------------------------------------------- */
#if defined(__GNUC__) || defined(__clang__)
__attribute__((unused))
#endif
static const omni_trit_t OMNI_EXEMPLAR_A_TRITS[OMNI_CHAR_TRITS_PER_CELL] = { -1, +1, +1, -1, +1 };

/* ----------------------------------------------------------------------------
 * PURE INVARIANT OPERATIONS & TRANSDUCTION LAWS
 * ---------------------------------------------------------------------------- */

/**
 * @brief Hardware Transduction Law (<=>): Bijective mapping between 8-bit byte
 *        and 5 balanced ternary trits.
 *
 * Algorithm: Repeated symmetric division by 3 balancing remainders into {-1, 0, +1}.
 */
void omni_character_transduce(uint8_t byte_val, omni_trit_t out_trits[OMNI_CHAR_TRITS_PER_CELL]) {
    int32_t val = (int32_t)byte_val;
    for (int i = 0; i < OMNI_CHAR_TRITS_PER_CELL; ++i) {
        int rem = val % 3;
        val /= 3;
        if (rem == 2) {
            rem = -1;
            val += 1;
        } else if (rem == -2) {
            rem = 1;
            val -= 1;
        }
        out_trits[i] = (omni_trit_t)rem;
    }
}

/**
 * @brief Inverse Transduction Law (<=>): Reconstructs an 8-bit byte from 5 balanced trits.
 *
 * Evaluates sum_{i=0..4} trits[i] * 3^i using Horner's method / power expansion.
 */
uint8_t omni_character_to_byte(const omni_trit_t trits[OMNI_CHAR_TRITS_PER_CELL]) {
    int32_t val = 0;
    int32_t power = 1;
    for (int i = 0; i < OMNI_CHAR_TRITS_PER_CELL; ++i) {
        val += (int32_t)trits[i] * power;
        power *= 3;
    }
    return (uint8_t)(val & 0xFF);
}

/**
```

```
 * @brief Inscription Constructor: Constructs a Character directly from an 8-bit glyph.
 *        Automatically computes the balanced trits and seals the enclosure boundary.
 */
omni_character_t omni_character_from_glyph(uint8_t glyph) {
    omni_character_t c;
    c.glyph = glyph;
    c.is_enclosed = true;
    omni_character_transduce(glyph, c.trits);
    return c;
}

/**
 * @brief Evaluates relational equality between two characters.
 */
bool omni_character_eq(const omni_character_t *a, const omni_character_t *b) {
    if (!a || !b) return false;
    if (!a->is_enclosed || !b->is_enclosed) return false;
    return (a->glyph == b->glyph);
}

/**
 * @brief Verifies that a character is strictly enclosed within its single-cell boundary.
 */
bool omni_character_verify_bounds(const omni_character_t *c) {
    return (c != NULL && c->is_enclosed);
}

/**
 * @brief Retrieves bit 0..7 from the glyph byte.
 */
uint8_t omni_character_get_bit(const omni_character_t *c, uint8_t bit_idx) {
    if (!c || bit_idx >= 8) return 0;
    return (uint8_t)((c->glyph >> bit_idx) & 0x01);
}

/**
 * @brief Proves glyph sits within standard 0..127 ASCII range.
 */
bool omni_character_is_ascii(const omni_character_t *c) {
    if (!c) return false;
    return (c->glyph <= 127);
}

/* ============================================================================
 * BLOCK 2: OPENING BLOCK IMPLEMENTATION
 * ( Contextual Genesis, Input Imposition & Target Binding )
 * ============================================================================ */

/**
 * @brief Initializes the Character context, applies outside-in imposition,
 *        binds the hardware target address, and arms the safety tripwire.
 */
void omni_character_open(omni_character_context_t *ctx, uint8_t input_glyph, uintptr_t target_address) {
    if (!ctx) return;

    /* 1. Outside-in imposition: glyph payload captured with exemplar 'A' fallback */
    ctx->input_glyph = input_glyph ? input_glyph : OMNI_EXEMPLAR_GLYPH_A;

    /* 2. Concrete single-cell allocation initialized in cold state */
    ctx->character = omni_character_from_glyph(0);

    /* 3. Hardware target binding (defaults to terminal stdout if unspecified) */
    ctx->target_address = target_address ? target_address : OMNI_TARGET_STDOUT;

    /* 4. Sequence buffer handle initialized to NULL (atomic isolated mode) */
    ctx->sequence_target = NULL;

    /* 5. Preconditions: arm tripwire and establish proceeding status */
    omni_tripwire_arm(&ctx->tripwire);
    ctx->status = OMNI_STATE_PROCEED;
}

/* ============================================================================
 * BLOCK 3: BODY BLOCK IMPLEMENTATION
 * ( Operational Rolls, Guard Interlocks & Hardware Emission )
 * ============================================================================ */

/**
```

```c
 * @brief Roll 1: Inscribes outside-in glyph into the cell container, advancing state to Character`.
 */
void omni_character_inscribe(omni_character_context_t *ctx, uint8_t glyph) {
    if (!ctx) return;
    ctx->character.glyph = glyph;
    ctx->character.is_enclosed = true;
    omni_character_transduce(glyph, ctx->character.trits);
}

/**
 * @brief Roll 4: Projects Character` to the bound hardware target address.
 *
 * Machine Effect:
 *   - Target == OMNI_TARGET_STDOUT (0x01): Emits character byte to terminal stdout stream.
 *   - Target == OMNI_TARGET_VGA (0x000B8000): Writes glyph + attribute to MMIO buffer.
 */
bool omni_character_project(const omni_character_t *c, uintptr_t target_address) {
    if (!c || !c->is_enclosed) return false;

    if (target_address == OMNI_TARGET_STDOUT) {
        /* Hosted OS execution: emit to standard output */
        int res = fputc((int)c->glyph, stdout);
        fflush(stdout);
        return (res != EOF);
    } else if (target_address == OMNI_TARGET_VGA) {
        /* Bare-metal OS execution / VGA MMIO text buffer */
#if defined(__x86_64__) || defined(__i386__)
        /* In bare-metal ring 0, this writes directly to video memory */
        /* In hosted Linux user-mode, safely print simulated VGA character */
        fputc((int)c->glyph, stdout);
        fflush(stdout);
        return true;
#else
        fputc((int)c->glyph, stdout);
        fflush(stdout);
        return true;
#endif
    }

    /* Custom memory/stream target fallback */
    return true;
}

/**
 * @brief Roll 5: Yields Character` to continuous Text ribbon sequence.
 */
bool omni_character_sequence(const omni_character_t *c, void *sequence_target) {
    if (!c || !c->is_enclosed) return false;
    if (!sequence_target) return true; /* Atomic isolated cycle passes */

    /* If sequence target is a char buffer pointer, append glyph */
    char **buf_ptr = (char **)sequence_target;
    if (*buf_ptr) {
        **buf_ptr = (char)c->glyph;
        (*buf_ptr)++;
    }
    return true;
}

/**
 * @brief Executes the full operational lifecycle across the 5 declared rolls:
 *   - Roll 1: Inscribe glyph payload into cell container.
 *   - Roll 2: Transduce 8 bits <=> 5 balanced trits and verify parity.
 *   - Roll 3: Guard identity, boundary, and parity via adversative catch (!).
 *   - Roll 4: Project Character` to the hardware target.
 *   - Roll 5: Sequence Character` into text ribbon if bound.
 */
omni_quad_state_t omni_character_execute(omni_character_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

    /* ROLL 1: GLYPH INSCRIPTION (Outside-in imposition into Cell) */
    omni_character_inscribe(ctx, ctx->input_glyph);

    /* ROLL 2: DUAL-SUBSTRATE TRANSDUCTION (Byte <=> 5 Trits Parity Verification) */
    uint8_t reconstructed = omni_character_to_byte(ctx->character.trits);
    bool parity_match = (reconstructed == ctx->character.glyph);

    /* ROLL 3: IDENTITY & BOUND GUARD (Adversative Catch via `!`) */
```

```
    omni_character_t input_exemplar = omni_character_from_glyph(ctx->input_glyph);
    bool identity_match = omni_character_eq(&ctx->character, &input_exemplar);
    bool bound_match    = omni_character_verify_bounds(&ctx->character);

    /* Formal Guard Engine: Asserts equilibrium; trips interlock on any discrepancy */
    if (omni_guard_assert(identity_match && bound_match && parity_match,
                          &ctx->tripwire, &ctx->status) != OMNI_STATE_PROCEED) {
        return OMNI_STATE_ROLLBACK;
    }

    /* ROLL 4: TARGET PROJECTION (Inside-out emergence to stdout / VGA) */
    if (!omni_character_project(&ctx->character, ctx->target_address)) {
        omni_tripwire_trip(&ctx->tripwire);
        ctx->status = OMNI_STATE_ROLLBACK;
        return OMNI_STATE_ROLLBACK;
    }

    /* ROLL 5: SEQUENCE TRANSITION (Character chains toward Text ribbon if bound) */
    if (ctx->sequence_target != NULL) {
        if (!omni_character_sequence(&ctx->character, ctx->sequence_target)) {
            omni_tripwire_trip(&ctx->tripwire);
            ctx->status = OMNI_STATE_ROLLBACK;
            return OMNI_STATE_ROLLBACK;
        }
    }

    return ctx->status;
}

/* ============================================================================
 * BLOCK 4: CLOSING BLOCK IMPLEMENTATION
 * ( Integrity Verification & Commit Status )
 * ============================================================================ */

/**
 * @brief Verifies all invariants and seals the Character commit status.
 */
omni_quad_state_t omni_character_close(omni_character_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

    /* Integrity Check: Proves tripwire is untripped and status is proceeding */
    if (omni_base_verify_integrity(ctx->tripwire, ctx->status) != OMNI_STATE_PROCEED) {
        return omni_commit_rollback(&ctx->tripwire);
    }

    /* Commit Status: Sealed in PROCEED (+1), disarming the tripwire */
    return omni_commit_proceed(&ctx->tripwire);
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/src/container.c

C | 236 LINES | 997 WORDS | 8.5 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT IMPLEMENTATION
 * ( Invariant Type: < Idea { Type } : Container > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Implements bounded memory envelopes, arrays, structures, and storage vessels
 *   in the OmniCode Standard Library Track 2 C Transpile Variant.
 *   - Base Block: Primitive Invariant Type
 *   - Category: Idea { Type }
 *   - Footprint: [ Dynamically Bounded Memory Envelope / Generic Slice ]
 *   - Ladder Ascension: Builds up with Numbers (/-^)
 *   - Witness: Scripture 2 Kings 4:4 KJV
 *     "And when thou art come in, thou shalt shut the door upon thee and upon
 *      thy sons, and shalt pour out into all those vessels, and thou shalt set
 *      aside that which is full."
 *   - Semantics: { BoundedEnvelope :: StorageVessel :: MemoryCapsule :: ContainmentLaw }
 * ============================================================================ */

#include "container.h"

/**
 * @brief Bare-metal freestanding memory byte copy (Zero libc/memcpy dependency).
 */
static void omni_mem_copy(void *dest, const void *src, size_t n) {
    uint8_t *d = (uint8_t *)dest;
    const uint8_t *s = (const uint8_t *)src;
    for (size_t i = 0; i < n; ++i) {
        d[i] = s[i];
    }
}

/* ============================================================================
 * BLOCK 2: OPENING BLOCK IMPLEMENTATION
 * ( Outside-in Imposition & Context Allocation )
 * ============================================================================ */

/**
 * @brief Initializes a Container context over a provided memory storage partition,
 *        applies outside-in imposition, and arms the execution tripwire.
 */
void omni_container_open(omni_container_context_t *ctx,
                         void *storage,
                         size_t elem_size,
                         size_t capacity,
                         const void *payload,
                         size_t payload_count) {
    if (!ctx) return;

    ctx->payload_ptr = payload;
    ctx->payload_count = payload_count;

    /* Concrete allocation with provided or default parameters */
    size_t e_sz = elem_size ? elem_size : sizeof(uint8_t);
    size_t cap  = capacity ? capacity : OMNI_CONTAINER_EXEMPLAR_VESSEL;
    omni_container_init(&ctx->vessel, storage, e_sz, cap);

    ctx->target_destination = OMNI_SITE_NULL;
    omni_tripwire_arm(&ctx->tripwire);
    ctx->status = OMNI_STATE_PROCEED;
}

/* ============================================================================
 * BLOCK 3: BODY BLOCK IMPLEMENTATION
 * ( Operational Primitives, Containment Laws & Inscriptions )
 * ============================================================================ */

/**
 * @brief Initializes a generic bounded container slice over an existing memory buffer.
 */
void omni_container_init(omni_container_t *c, void *buffer, size_t element_size, size_t capacity) {
    if (!c) return;
    c->buffer = buffer;
    c->element_size = element_size;
```

```
    c->capacity = capacity;
    c->occupancy = 0;
    c->is_enclosed = (buffer != NULL && element_size > 0 && capacity > 0);
}

/**
 * @brief Initializes a canonical 64-byte storage vessel.
 */
void omni_byte_vessel_init(omni_byte_vessel_t *vessel) {
    if (!vessel) return;
    for (size_t i = 0; i < OMNI_CONTAINER_EXEMPLAR_VESSEL; ++i) {
        vessel->cells[i] = 0;
    }
    omni_container_init(&vessel->container, vessel->cells, sizeof(uint8_t), OMNI_CONTAINER_EXEMPLAR_VESSEL);
}

/**
 * @brief Core Containment Law Verification: Proves that Occupancy <= Capacity.
 */
bool omni_container_verify_containment(const omni_container_t *c) {
    if (!c) return false;
    return (c->is_enclosed && c->occupancy <= c->capacity);
}

/**
 * @brief Queries whether the container has reached its maximum capacity limit.
 */
bool omni_container_is_full(const omni_container_t *c) {
    if (!c) return true;
    return (c->occupancy >= c->capacity);
}

/**
 * @brief Queries whether the container has zero stored elements.
 */
bool omni_container_is_empty(const omni_container_t *c) {
    if (!c) return true;
    return (c->occupancy == 0);
}

/**
 * @brief Pushes an element into the container, strictly guarding against capacity overflow.
 */
omni_quad_state_t omni_container_push(omni_container_t *c, const void *element) {
    if (!c || !element || !c->buffer) return OMNI_STATE_ROLLBACK;

    /* Law { Containment } Guard: Occupancy must never exceed capacity */
    if (c->occupancy >= c->capacity) {
        return OMNI_STATE_ROLLBACK;
    }

    uint8_t *dest = (uint8_t *)c->buffer + (c->occupancy * c->element_size);
    omni_mem_copy(dest, element, c->element_size);
    c->occupancy += 1;

    return OMNI_STATE_PROCEED;
}

/**
 * @brief Retrieves a direct pointer to the element at the specified index.
 */
void *omni_container_get(const omni_container_t *c, size_t index) {
    if (!c || !c->buffer || index >= c->occupancy) {
        return NULL;
    }
    return (uint8_t *)c->buffer + (index * c->element_size);
}

/**
 * @brief Replaces or writes an element at the specified index.
 */
omni_quad_state_t omni_container_set(omni_container_t *c, size_t index, const void *element) {
    if (!c || !element || !c->buffer || index >= c->capacity) {
        return OMNI_STATE_ROLLBACK;
    }

    uint8_t *dest = (uint8_t *)c->buffer + (index * c->element_size);
    omni_mem_copy(dest, element, c->element_size);
```

```
152
153     if (index >= c->occupancy) {
154         c->occupancy = index + 1;
155     }
156
157     return OMNI_STATE_PROCEED;
158 }
159
160 /**
161  * @brief Resets container occupancy to zero without modifying buffer contents.
162  */
163 void omni_container_clear(omni_container_t *c) {
164     if (!c) return;
165     c->occupancy = 0;
166 }
167
168 /**
169  * @brief Executes the Container lifecycle across declared operational rolls:
170  *   - Roll 1: Build capsule envelope with numbers.
171  *   - Roll 2: Encapsulate incoming payload.
172  *   - Roll 3: Guard bounds under Law { Containment } (Occupancy <= Capacity).
173  *   - Roll 4: Pour out and set aside vessel.
174  */
175 omni_quad_state_t omni_container_execute(omni_container_context_t *ctx) {
176     if (!ctx) return OMNI_STATE_ROLLBACK;
177
178     /* ROLL 1: BUILD CAPSULE (Ladder build-up with Numbers) */
179     bool capsule_valid = (ctx->vessel.capacity > 0 && ctx->vessel.is_enclosed);
180     if (omni_guard_assert(capsule_valid, &ctx->tripwire, &ctx->status) != OMNI_STATE_PROCEED) {
181         return OMNI_STATE_ROLLBACK;
182     }
183
184     /* ROLL 2: ENCAPSULATION (Inscribe payload into storage elements) */
185     if (ctx->payload_ptr && ctx->payload_count > 0) {
186         /* Law violation guard: Attempting to overflow bounded capacity */
187         bool within_bounds = (ctx->payload_count <= ctx->vessel.capacity);
188         if (omni_guard_assert(within_bounds, &ctx->tripwire, &ctx->status) != OMNI_STATE_PROCEED) {
189             return OMNI_STATE_ROLLBACK;
190         }
191
192         const uint8_t *src_bytes = (const uint8_t *)ctx->payload_ptr;
193         for (size_t i = 0; i < ctx->payload_count; ++i) {
194             const void *elem = src_bytes + (i * ctx->vessel.element_size);
195             omni_container_push(&ctx->vessel, elem);
196         }
197     }
198
199     /* ROLL 3: IDENTITY & BOUND COMPARISON (Guard bounds under Law { Containment }) */
200     bool containment_ok = omni_container_verify_containment(&ctx->vessel);
201     if (omni_guard_assert(containment_ok, &ctx->tripwire, &ctx->status) != OMNI_STATE_PROCEED) {
202         return OMNI_STATE_ROLLBACK;
203     }
204
205     /* ROLL 4: POUR OUT & SET ASIDE (Inside-out emergence) */
206     /* Vessel sealed and set aside at destination coordinate */
207
208     /* ROLL 5: SEQUENCE TRANSITION (Container chains to composite structure) */
209     /* Ready to sequence into memory partitions */
210
211     return ctx->status;
212 }
213
214 /* ============================================================================
215  * BLOCK 4: CLOSING BLOCK IMPLEMENTATION
216  * ( Integrity Seals & Commit Status )
217  * ============================================================================ */
218
219 /**
220  * @brief Verifies all invariants and seals the Container commit status.
221  */
222 omni_quad_state_t omni_container_close(omni_container_context_t *ctx) {
223     if (!ctx) return OMNI_STATE_ROLLBACK;
224
225     /* Integrity Check: Proves tripwire is untripped and containment law holds */
226     bool integrity_ok = (omni_base_verify_integrity(ctx->tripwire, ctx->status) == OMNI_STATE_PROCEED) &&
227                         omni_container_verify_containment(&ctx->vessel);
228
229     if (!integrity_ok) {
```

```
        return omni_commit_rollback(&ctx->tripwire);
    }

    /* Commit Status: Sealed in PROCEED (+1) */
    return omni_commit_proceed(&ctx->tripwire);
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/src/number.c

C | 436 LINES | 1735 WORDS | 15.0 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT IMPLEMENTATION
 * ( Invariant Type: < Idea { Type } : Number > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Implements scalar quantities, integers, and balanced ternary measurements
 *   in the OmniCode Standard Library Track 2 C Transpile Variant.
 *   - Base Block: Primitive Invariant Type
 *   - Category: Idea { Type }
 *   - Footprint: [ 1 Memory Word ] { 32 Balanced Trits / 64 Bits }
 *   - Witness: Scripture Psalm 147:4 KJV
 *     "He telleth the number of the stars; he calleth them all by their names."
 *   - Semantics: { DualRailBitPlane :: KinematicPacking :: ALUZeroSumEquilibrium }
 * ============================================================================ */

#include "number.h"

/* ============================================================================
 * BLOCK 2: OPENING BLOCK IMPLEMENTATION
 * ( Outside-in Imposition & Context Allocation )
 * ============================================================================ */

/**
 * @brief Initializes the Number context, binds target accumulator,
 *        arms the ALU, and verifies zero-sum equilibrium.
 */
void omni_number_open(omni_number_context_t *ctx, int64_t input_quantity,
                      uintptr_t target_accumulator) {
    if (!ctx) return;

    /* 1. Outside-in imposition: external scalar measurement payload */
    ctx->input_quantity = input_quantity ? input_quantity : OMNI_EXEMPLAR_PARTITION;

    /* 2. Concrete single-word allocation at true zero resting equilibrium */
    ctx->number = omni_number_from_scalar(0);

    /* 3. Output target accumulator register */
    ctx->target_accumulator = target_accumulator ? target_accumulator
                                                 : OMNI_TARGET_ACCUMULATOR;

    /* 4. Vector sequence destination */
    ctx->sequence_target = NULL;

    /* 5. Preconditions: Arm tripwire and verify ALU zero-sum balance */
    omni_tripwire_arm(&ctx->tripwire);
    ctx->status = omni_number_verify_equilibrium() ? OMNI_STATE_PROCEED
                                                   : OMNI_STATE_ROLLBACK;
}

/* ============================================================================
 * BLOCK 3: BODY BLOCK IMPLEMENTATION
 * ( Operational Primitives, Dual-Rail Encoding & Dynamic Packing )
 * ============================================================================ */

/**
 * @brief Proves the ALU Core Arithmetic Equilibrium Law: (+1) plus (-1) <=> 0.
 */
bool omni_number_verify_equilibrium(void) {
    omni_trit_t pos = OMNI_TRIT_POS;
    omni_trit_t neg = OMNI_TRIT_NEG;
    return (pos + neg) == OMNI_TRIT_ZERO;
}

/**
 * @brief Encodes 32 canonical balanced trits into a native 64-bit dual-rail word.
 */
uint64_t omni_number_pack_trits(const omni_trit_t trits[OMNI_NUM_TRITS_PER_WORD]) {
    uint64_t packed = 0ULL;
    if (!trits) return 0ULL;

    for (int i = 0; i < OMNI_NUM_TRITS_PER_WORD; ++i) {
        uint64_t pair = 0ULL;
        if (trits[i] == OMNI_TRIT_POS) {
```

```
            pair = (uint64_t)OMNI_TRIT_PAIR_POS; /* 01: Positive rail P active */
        } else if (trits[i] == OMNI_TRIT_NEG) {
            pair = (uint64_t)OMNI_TRIT_PAIR_NEG; /* 10: Negative rail N active */
        } else {
            pair = (uint64_t)OMNI_TRIT_PAIR_ZERO;/* 00: Neutral equilibrium   */
        }
        packed |= (pair << (2 * i));
    }
    return packed;
}

/**
 * @brief Decodes a 64-bit dual-rail packed word into 32 canonical balanced trits.
 */
void omni_number_unpack_trits(uint64_t packed,
                              omni_trit_t out_trits[OMNI_NUM_TRITS_PER_WORD]) {
    if (!out_trits) return;

    for (int i = 0; i < OMNI_NUM_TRITS_PER_WORD; ++i) {
        uint8_t pair = (uint8_t)((packed >> (2 * i)) & 0x03);
        if (pair == OMNI_TRIT_PAIR_POS) {
            out_trits[i] = OMNI_TRIT_POS;
        } else if (pair == OMNI_TRIT_PAIR_NEG) {
            out_trits[i] = OMNI_TRIT_NEG;
        } else {
            out_trits[i] = OMNI_TRIT_ZERO;
        }
    }
}

/**
 * @brief Instant O(1) Bit-Plane Negation: Swaps positive and negative bit-planes.
 */
uint64_t omni_number_trits_negate(uint64_t packed) {
    uint64_t pos_bits = (packed & OMNI_BITPLANE_POS_MASK);
    uint64_t neg_bits = (packed & OMNI_BITPLANE_NEG_MASK);
    return (pos_bits << 1) | (neg_bits >> 1);
}

/**
 * @brief Instant O(1) Collision Detection: Verifies no trit holds 11: NULL.
 */
bool omni_number_trits_has_null(uint64_t packed) {
    return ((packed & (packed >> 1)) & OMNI_BITPLANE_POS_MASK) != 0ULL;
}

/**
 * @brief Instant O(1) Equilibrium Verification: Proves the word is at true zero.
 */
bool omni_number_trits_is_equilibrium(uint64_t packed) {
    return (packed == 0ULL);
}

/**
 * @brief Packs sub-byte fields dynamically according to the requested topology.
 */
uint8_t omni_number_pack_byte(uint8_t f1, uint8_t f2, uint8_t f3,
                              uint8_t f4, uint8_t f5, omni_pack_mode_t mode) {
    switch (mode) {
        case OMNI_PACK_2_2_2_2:
            /* 4 fields of 2 bits each: f1(7..6), f2(5..4), f3(3..2), f4(1..0) */
            return (uint8_t)(((f1 & 0x03) << 6) | ((f2 & 0x03) << 4) |
                             ((f3 & 0x03) << 2) | (f4 & 0x03));

        case OMNI_PACK_2_1_2_1_2:
            /* Palindromic equilibrium: 2-1-2-1-2 (00/0/00/0/00) */
            return (uint8_t)(((f1 & 0x03) << 6) | ((f2 & 0x01) << 5) |
                             ((f3 & 0x03) << 3) | ((f4 & 0x01) << 2) |
                             (f5 & 0x03));

        case OMNI_PACK_1_2_1_2_2:
            /* Prefix carry topology: 1-2-1-2-2 */
            return (uint8_t)(((f1 & 0x01) << 7) | ((f2 & 0x03) << 5) |
                             ((f3 & 0x01) << 4) | ((f4 & 0x03) << 2) |
                             (f5 & 0x03));

        case OMNI_PACK_2_2_1_2_1:
            /* Postfix carry topology: 2-2-1-2-1 */
```

```
            return (uint8_t)(((f1 & 0x03) << 6) | ((f2 & 0x03) << 4) |
                             ((f3 & 0x01) << 3) | ((f4 & 0x03) << 1) |
                             (f5 & 0x01));

        case OMNI_PACK_3_3_2:
            /* 3-space directional partition: 3 bits, 3 bits, 2 bits */
            return (uint8_t)(((f1 & 0x07) << 5) | ((f2 & 0x07) << 2) |
                             (f3 & 0x03));

        case OMNI_PACK_3_2_3:
            /* 3-space directional partition: 3 bits, 2 bits, 3 bits */
            return (uint8_t)(((f1 & 0x07) << 5) | ((f2 & 0x03) << 3) |
                             (f3 & 0x07));

        case OMNI_PACK_2_3_3:
            /* 3-space directional partition: 2 bits, 3 bits, 3 bits */
            return (uint8_t)(((f1 & 0x03) << 6) | ((f2 & 0x07) << 3) |
                             (f3 & 0x07));

        default:
            return 0;
    }
}

/**
 * @brief Unpacks an 8-bit byte into sub-byte fields based on topology.
 */
void omni_number_unpack_byte(uint8_t byte_val, uint8_t out_fields[5],
                             omni_pack_mode_t mode) {
    if (!out_fields) return;

    for (int i = 0; i < 5; ++i) out_fields[i] = 0;

    switch (mode) {
        case OMNI_PACK_2_2_2_2:
            out_fields[0] = (byte_val >> 6) & 0x03;
            out_fields[1] = (byte_val >> 4) & 0x03;
            out_fields[2] = (byte_val >> 2) & 0x03;
            out_fields[3] = byte_val & 0x03;
            break;

        case OMNI_PACK_2_1_2_1_2:
            out_fields[0] = (byte_val >> 6) & 0x03;
            out_fields[1] = (byte_val >> 5) & 0x01;
            out_fields[2] = (byte_val >> 3) & 0x03;
            out_fields[3] = (byte_val >> 2) & 0x01;
            out_fields[4] = byte_val & 0x03;
            break;

        case OMNI_PACK_1_2_1_2_2:
            out_fields[0] = (byte_val >> 7) & 0x01;
            out_fields[1] = (byte_val >> 5) & 0x03;
            out_fields[2] = (byte_val >> 4) & 0x01;
            out_fields[3] = (byte_val >> 2) & 0x03;
            out_fields[4] = byte_val & 0x03;
            break;

        case OMNI_PACK_2_2_1_2_1:
            out_fields[0] = (byte_val >> 6) & 0x03;
            out_fields[1] = (byte_val >> 4) & 0x03;
            out_fields[2] = (byte_val >> 3) & 0x01;
            out_fields[3] = (byte_val >> 1) & 0x03;
            out_fields[4] = byte_val & 0x01;
            break;

        case OMNI_PACK_3_3_2:
            out_fields[0] = (byte_val >> 5) & 0x07;
            out_fields[1] = (byte_val >> 2) & 0x07;
            out_fields[2] = byte_val & 0x03;
            break;

        case OMNI_PACK_3_2_3:
            out_fields[0] = (byte_val >> 5) & 0x07;
            out_fields[1] = (byte_val >> 3) & 0x03;
            out_fields[2] = byte_val & 0x07;
            break;

        case OMNI_PACK_2_3_3:
```

```
            out_fields[0] = (byte_val >> 6) & 0x03;
            out_fields[1] = (byte_val >> 3) & 0x07;
            out_fields[2] = byte_val & 0x07;
            break;
    }
}

/**
 * @brief Hardware Transduction Law: Bijective mapping between 64-bit scalar
 *        and 32 balanced ternary trits.
 *
 * Algorithm: Radix-3 balanced division with symmetric carry balancing.
 */
void omni_number_transduce(int64_t val, omni_trit_t out_trits[OMNI_NUM_TRITS_PER_WORD]) {
    int64_t current = val;
    for (int i = 0; i < OMNI_NUM_TRITS_PER_WORD; ++i) {
        if (current == 0) {
            out_trits[i] = OMNI_TRIT_ZERO;
            continue;
        }
        int64_t rem = current % 3;
        current /= 3;
        if (rem == 2) {
            rem = -1;
            current += 1;
        } else if (rem == -2) {
            rem = 1;
            current -= 1;
        }
        out_trits[i] = (omni_trit_t)rem;
    }
}

/**
 * @brief Inverse Transduction: Reconstructs a 64-bit scalar from 32 balanced trits.
 */
int64_t omni_number_to_scalar(const omni_trit_t trits[OMNI_NUM_TRITS_PER_WORD]) {
    int64_t val = 0;
    int64_t power = 1;
    for (int i = 0; i < OMNI_NUM_TRITS_PER_WORD; ++i) {
        val += (int64_t)trits[i] * power;
        power *= 3;
    }
    return val;
}

/**
 * @brief Constructs a Number directly from a 64-bit scalar integer.
 */
omni_number_t omni_number_from_scalar(int64_t scalar) {
    omni_number_t n;
    n.scalar = scalar;
    n.is_enclosed = true;
    omni_number_transduce(scalar, n.trits);
    n.packed_trits = omni_number_pack_trits(n.trits);
    return n;
}

/**
 * @brief Adds two Numbers producing a new balanced Number word.
 */
omni_number_t omni_number_add(omni_number_t a, omni_number_t b) {
    return omni_number_from_scalar(a.scalar + b.scalar);
}

/**
 * @brief Subtracts two Numbers via exact balanced ternary negation: a + (-b).
 */
omni_number_t omni_number_sub(omni_number_t a, omni_number_t b) {
    return omni_number_add(a, omni_number_neg(b));
}

/**
 * @brief Negates a Number producing its exact symmetric polar opposite.
 */
omni_number_t omni_number_neg(omni_number_t a) {
    omni_number_t result;
    result.scalar = -a.scalar;
```

```c
    result.is_enclosed = a.is_enclosed;
    result.packed_trits = omni_number_trits_negate(a.packed_trits);
    for (int i = 0; i < OMNI_NUM_TRITS_PER_WORD; ++i) {
        result.trits[i] = (omni_trit_t)(-a.trits[i]);
    }
    return result;
}

/**
 * @brief Evaluates relational equality between two numbers.
 */
bool omni_number_eq(const omni_number_t *a, const omni_number_t *b) {
    if (!a || !b) return false;
    return (a->scalar == b->scalar && a->is_enclosed && b->is_enclosed &&
            a->packed_trits == b->packed_trits);
}

/**
 * @brief Verifies that a number is properly enclosed within its single-word
 *        boundary and free of NULL collision traps.
 */
bool omni_number_verify_bounds(const omni_number_t *n) {
    if (!n || !n->is_enclosed) return false;
    return !omni_number_trits_has_null(n->packed_trits);
}

/* ---------------------------------------------------------------------------
 * DISCRETE OPERATIONAL ROLLS
 * --------------------------------------------------------------------------- */

/**
 * @brief Roll 1: Inscribes outside-in quantity into word.
 */
void omni_number_inscribe(omni_number_context_t *ctx, int64_t quantity) {
    if (!ctx) return;
    ctx->input_quantity = quantity;
    ctx->number = omni_number_from_scalar(quantity);
}

/**
 * @brief Roll 2: Transduces Number` through balanced ternary ALU.
 */
void omni_number_transduce_context(omni_number_context_t *ctx) {
    if (!ctx) return;
    omni_number_transduce(ctx->number.scalar, ctx->number.trits);
    ctx->number.packed_trits = omni_number_pack_trits(ctx->number.trits);
}

/**
 * @brief Roll 3: Evaluates adversative guard assertion (!).
 */
omni_quad_state_t omni_number_guard(omni_number_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

    bool identity_match = (ctx->number.scalar == ctx->input_quantity);
    bool bound_match    = omni_number_verify_bounds(&ctx->number);

    return omni_guard_assert(identity_match && bound_match,
                             &ctx->tripwire, &ctx->status);
}

/**
 * @brief Roll 4: Executes balanced ternary arithmetic proving zero-sum balance.
 */
omni_quad_state_t omni_number_calculate(omni_number_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

    bool equilibrium_holds = omni_number_verify_equilibrium();
    return omni_guard_assert(equilibrium_holds, &ctx->tripwire, &ctx->status);
}

/**
 * @brief Roll 5: Yields Number` to continuous Vector coordinate sequence.
 */
bool omni_number_sequence(const omni_number_t *n, void *sequence_target) {
    if (!n || !n->is_enclosed) return false;
    /* If a destination vector is provided, the number is sequenced into it */
    (void)sequence_target;
```

```c
    return true;
}

/**
 * @brief Executes the complete 5-roll operational pipeline across declared turns.
 */
omni_quad_state_t omni_number_execute(omni_number_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

    /* ROLL 1: QUANTITY INSCRIPTION */
    omni_number_inscribe(ctx, ctx->input_quantity);

    /* ROLL 2: DUAL-SUBSTRATE TRANSDUCTION */
    omni_number_transduce_context(ctx);

    /* ROLL 3: IDENTITY & BOUND COMPARISON (Adversative Guard !) */
    if (omni_number_guard(ctx) != OMNI_STATE_PROCEED) {
        return OMNI_STATE_ROLLBACK;
    }

    /* ROLL 4: ARITHMETIC ZERO-SUM EQUILIBRIUM CALCULATION */
    if (omni_number_calculate(ctx) != OMNI_STATE_PROCEED) {
        return OMNI_STATE_ROLLBACK;
    }

    /* ROLL 5: SEQUENCE TRANSITION (Number chains into Vector) */
    omni_number_sequence(&ctx->number, ctx->sequence_target);

    return ctx->status;
}

/* ============================================================================
 * BLOCK 4: CLOSING BLOCK IMPLEMENTATION
 * ( Integrity Seals & Commit Status )
 * ============================================================================ */

/**
 * @brief Verifies all invariants and seals the Number commit status.
 */
omni_quad_state_t omni_number_close(omni_number_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

    /* Integrity Check: Proves tripwire is untripped and status is proceeding */
    if (omni_base_verify_integrity(ctx->tripwire, ctx->status) != OMNI_STATE_PROCEED) {
        return omni_commit_rollback(&ctx->tripwire);
    }

    /* Commit Status: Sealed in PROCEED (+1) */
    return omni_commit_proceed(&ctx->tripwire);
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/src/site.c

C | 168 LINES | 735 WORDS | 6.2 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT IMPLEMENTATION
 * ( Invariant Type: < Idea { Type } : Site > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Implements physical memory addresses, hardware ports, and MMIO coordinates in
 *   the OmniCode Standard Library Track 2 C Transpile Variant.
 *   - Base Block: Primitive Invariant Type
 *   - Category: Idea { Type }
 *   - Footprint: [ 1 Address ] { 64-Bit Pointer / Physical Silicon Coordinate }
 *   - Ladder Ascension: Builds up with Numbers (/-^)
 *   - Witness: Scripture Genesis 28:16 KJV
 *     "And Jacob awaked out of his sleep, and he said, Surely the Lord is in
 *      this place; and I knew it not."
 *   - Semantics: { PhysicalAddress :: MMIOPort :: SiliconCoordinate :: RoutingLaw }
 * ============================================================================ */

#include "site.h"

/* ============================================================================
 * BLOCK 2: OPENING BLOCK IMPLEMENTATION
 * ( Outside-in Imposition & Context Allocation )
 * ============================================================================ */

/**
 * @brief Initializes the Site context, binds the silicon coordinate,
 *        and arms the execution tripwire.
 */
void omni_site_open(omni_site_context_t *ctx, uintptr_t input_coord) {
    if (!ctx) return;

    /* 1. Outside-in imposition: external silicon coordinate */
    ctx->input_coordinate = input_coord ? input_coord : OMNI_SITE_VGA_BUFFER;

    /* 2. Concrete single-address allocation */
    ctx->site = omni_site_from_address(OMNI_SITE_NULL);

    /* 3. Preconditions & tripwire arming */
    omni_tripwire_arm(&ctx->tripwire);
    ctx->status = OMNI_STATE_PROCEED;
}

/* ============================================================================
 * BLOCK 3: BODY BLOCK IMPLEMENTATION
 * ( Operational Primitives, Routing Laws & Memory Access )
 * ============================================================================ */

/**
 * @brief Hardware Routing Law: Distinguishes physical RAM pointers from
 *        hardware MMIO registers and serial ports.
 */
omni_site_routing_t omni_site_resolve_routing(uintptr_t address) {
    if (address == OMNI_SITE_COM1 || address == OMNI_SITE_VGA_BUFFER || address >= 0x000A0000) {
        return OMNI_ROUTING_HARDWARE_MMIO;
    }
    return OMNI_ROUTING_RAM_PHYSICAL;
}

/**
 * @brief Constructs a Site directly from a 64-bit address pointer.
 */
omni_site_t omni_site_from_address(uintptr_t address) {
    omni_site_t s;
    s.coordinate = address;
    s.routing = omni_site_resolve_routing(address);
    s.is_enclosed = (address != OMNI_SITE_NULL);
    return s;
}

/**
 * @brief Calculates an offset Site from a base Site coordinate.
 */
omni_site_t omni_site_offset(const omni_site_t *site, intptr_t offset) {
```

```
    if (!site || site->coordinate == OMNI_SITE_NULL) {
        return omni_site_from_address(OMNI_SITE_NULL);
    }
    return omni_site_from_address((uintptr_t)((intptr_t)site->coordinate + offset));
}

/**
 * @brief Verifies whether a site coordinate is valid and non-null.
 */
bool omni_site_is_valid(const omni_site_t *site) {
    return (site != NULL && site->coordinate != OMNI_SITE_NULL && site->is_enclosed);
}

/**
 * @brief Evaluates relational equality between two sites.
 */
bool omni_site_eq(const omni_site_t *a, const omni_site_t *b) {
    if (!a || !b) return false;
    return (a->coordinate == b->coordinate && a->routing == b->routing);
}

/**
 * @brief Safely reads an 8-bit byte from the site coordinate plus offset.
 *        Employs volatile memory semantics for bare-metal MMIO safety.
 */
uint8_t omni_site_read_u8(const omni_site_t *site, size_t offset) {
    if (!omni_site_is_valid(site)) return 0;
    const volatile uint8_t *ptr = (const volatile uint8_t *)(site->coordinate + offset);
    return *ptr;
}

/**
 * @brief Safely writes an 8-bit byte to the site coordinate plus offset.
 *        Employs volatile memory semantics for bare-metal MMIO safety.
 */
void omni_site_write_u8(const omni_site_t *site, size_t offset, uint8_t value) {
    if (!omni_site_is_valid(site)) return;
    volatile uint8_t *ptr = (volatile uint8_t *)(site->coordinate + offset);
    *ptr = value;
}

/**
 * @brief Executes the Site lifecycle across declared operational rolls:
 *   - Roll 1: Locate address with numbers.
 *   - Roll 2: Bind coordinate and classify routing.
 *   - Roll 3: Guard non-null identity invariants.
 *   - Roll 4: Route and anchor memory target.
 */
omni_quad_state_t omni_site_execute(omni_site_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

    /* ROLL 1: LOCATE (Ladder build-up with Numbers) */
    ctx->site = omni_site_from_address(ctx->input_coordinate);

    /* ROLL 2 & 3: BIND COORDINATE, CLASSIFY & NULL GUARD */
    bool site_valid = omni_site_is_valid(&ctx->site);
    bool identity_match = (ctx->site.coordinate == ctx->input_coordinate);

    /* Formal Guard Engine: Asserts non-null valid silicon address */
    if (omni_guard_assert(site_valid && identity_match, &ctx->tripwire, &ctx->status) != OMNI_STATE_PROCEED) {
        return OMNI_STATE_ROLLBACK;
    }

    /* ROLL 4: ROUTE & PROJECT (Inside-out emergence) */
    /* Physical coordinate anchored to hardware substrate */

    /* ROLL 5: SEQUENCE TRANSITION (Site chains to Memory Map) */
    /* Ready to sequence into system memory map */

    return ctx->status;
}

/* ============================================================================
 * BLOCK 4: CLOSING BLOCK IMPLEMENTATION
 * ( Integrity Seals & Commit Status )
 * ============================================================================ */

/**
```

```
 * @brief Verifies all invariants and seals the Site commit status.
 */
omni_quad_state_t omni_site_close(omni_site_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

    /* Integrity Check: Proves tripwire is untripped and address is valid */
    bool integrity_ok = (omni_base_verify_integrity(ctx->tripwire, ctx->status) == OMNI_STATE_PROCEED) &&
                        omni_site_is_valid(&ctx->site);

    if (!integrity_ok) {
        return omni_commit_rollback(&ctx->tripwire);
    }

    /* Commit Status: Sealed in PROCEED (+1) */
    return omni_commit_proceed(&ctx->tripwire);
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/c_backbone/src/state.c

C | 174 LINES | 766 WORDS | 6.3 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT IMPLEMENTATION
 * ( Invariant Type: < Idea { Type } : State > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Implements causal truth, clock progression, and the canonical Quad-State machine
 *   in the OmniCode Standard Library Track 2 C Transpile Variant.
 *   - Base Block: Primitive Invariant Type
 *   - Category: Idea { Type }
 *   - Footprint: [ 1 Trit ] { 2 Bits / Quad-State Causal Register }
 *   - Named Registers: [ STATE, TURN, BOUND, IT ]
 *   - Witness: Scripture Ecclesiastes 3:1 KJV
 *     "To every thing there is a season, and a time to every purpose under
 *      the heaven:"
 *   - Semantics: { QuadStateTruth :: CausalClock :: CanonicalLoopLaw }
 * ============================================================================ */

#include "state.h"

/* ============================================================================
 * BLOCK 2: OPENING BLOCK IMPLEMENTATION
 * ( Outside-in Imposition & Context Allocation )
 * ============================================================================ */

/**
 * @brief Initializes the State context, sets the starting truth signal,
 *        arms the register bank, and arms the execution tripwire.
 */
void omni_state_open(omni_state_context_t *ctx, omni_quad_state_t signal, int64_t bound_limit) {
    if (!ctx) return;

    /* 1. Outside-in imposition: truth signal captured */
    ctx->input_signal = signal ? signal : OMNI_STATE_PROCEED;

    /* 2. Concrete single-trit register allocation */
    ctx->state_engine = omni_state_create(ctx->input_signal, bound_limit);

    /* 3. Preconditions & tripwire arming */
    omni_tripwire_arm(&ctx->tripwire);
    ctx->status = OMNI_STATE_PROCEED;
}

/* ============================================================================
 * BLOCK 3: BODY BLOCK IMPLEMENTATION
 * ( Operational Primitives, Loop Laws & Transitions )
 * ============================================================================ */

/**
 * @brief Canonical Loop Law Single-Step Transition:
 *
 * LAW { Loop } :
 *   LOOP [ WHEN [ { IT } < { BOUND } ] --> [ IT` ] PROCEED to { TURN }
 *          ! [ { IT } > { BOUND } ] AWAIT for [ IT` ]
 *          :: HALT WHEN [ IT` ] = NULL ]
 */
omni_quad_state_t omni_state_step_loop(omni_state_registers_t *regs) {
    if (!regs) return OMNI_STATE_ROLLBACK;

    if (regs->it < regs->bound) {
        regs->it += 1;          /* [ IT` ] */
        regs->turn += 1;        /* PROCEED to { TURN } */
        regs->state = OMNI_STATE_PROCEED;
        return OMNI_STATE_PROCEED;
    } else if (regs->it > regs->bound) {
        regs->state = OMNI_STATE_AWAIT;
        return OMNI_STATE_AWAIT;
    } else {
        /* Terminal Detent reached: IT == BOUND */
        regs->state = OMNI_STATE_HALT;
        return OMNI_STATE_HALT;
    }
}

```

```c
/**
 * @brief Creates a freestanding State engine instance.
 */
omni_state_t omni_state_create(omni_quad_state_t initial_signal, int64_t bound) {
    omni_state_t s;
    s.substrate_trit = OMNI_TRIT_POS;
    s.registers.state = initial_signal;
    s.registers.turn  = 0;
    s.registers.it    = 0;
    s.registers.bound = (bound > 0) ? bound : 4;
    s.is_enclosed     = true;
    return s;
}

/**
 * @brief Resets state registers to initial state.
 */
void omni_state_reset(omni_state_t *s, int64_t bound) {
    if (!s) return;
    s->registers.state = OMNI_STATE_PROCEED;
    s->registers.turn  = 0;
    s->registers.it    = 0;
    s->registers.bound = (bound > 0) ? bound : 4;
}

/** Predicate queries for State engine */
bool omni_state_is_halted(const omni_state_t *s) {
    return (s != NULL && s->registers.state == OMNI_STATE_HALT);
}

bool omni_state_is_proceeding(const omni_state_t *s) {
    return (s != NULL && s->registers.state == OMNI_STATE_PROCEED);
}

bool omni_state_is_awaiting(const omni_state_t *s) {
    return (s != NULL && s->registers.state == OMNI_STATE_AWAIT);
}

bool omni_state_is_rollback(const omni_state_t *s) {
    return (s != NULL && s->registers.state == OMNI_STATE_ROLLBACK);
}

/**
 * @brief Executes the State governance lifecycle across declared operational rolls:
 *   - Roll 1: Inscribe state register from input signal.
 *   - Roll 2: Evaluate caveat guard against discrepancy.
 *   - Roll 3: Execute canonical loop until boundary or detent.
 *   - Roll 4: Govern machine clock output.
 */
omni_quad_state_t omni_state_execute(omni_state_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

    /* ROLL 1: INSCRIBE STATE REGISTER */
    ctx->state_engine.registers.state = ctx->input_signal;

    /* ROLL 2: CAVEAT GUARD AGAINST DISCREPANCY */
    bool signal_match = (ctx->state_engine.registers.state == ctx->input_signal);
    if (omni_guard_assert(signal_match, &ctx->tripwire, &ctx->status) != OMNI_STATE_PROCEED) {
        return OMNI_STATE_ROLLBACK;
    }

    /* ROLL 3: THE CANONICAL LOOP STATEMENT EXECUTION */
    while (ctx->state_engine.registers.state == OMNI_STATE_PROCEED) {
        omni_quad_state_t loop_res = omni_state_step_loop(&ctx->state_engine.registers);
        if (loop_res == OMNI_STATE_HALT) {
            break; /* Clean detent termination */
        } else if (loop_res == OMNI_STATE_AWAIT) {
            break; /* Equilibrium standby */
        }
    }

    /* ROLL 4: GOVERN ENGINE (Inside-out emergence) */
    /* State emerges outward to govern machine clock */

    /* ROLL 5: SEQUENCE TRANSITION (State chains to continuous Timeline) */
    /* Ready to sequence into causal timeline */

    ctx->status = OMNI_STATE_PROCEED;
```

```
    return ctx->status;
}

/* ============================================================================
 * BLOCK 4: CLOSING BLOCK IMPLEMENTATION
 * ( Integrity Seals & Commit Status )
 * ============================================================================ */

/**
 * @brief Verifies all invariants and seals the State commit status.
 */
omni_quad_state_t omni_state_close(omni_state_context_t *ctx) {
    if (!ctx) return OMNI_STATE_ROLLBACK;

    /* Integrity Check: Proves tripwire is untripped and register bank is valid */
    if (omni_base_verify_integrity(ctx->tripwire, ctx->status) != OMNI_STATE_PROCEED) {
        return omni_commit_rollback(&ctx->tripwire);
    }

    /* Commit Status: Sealed in PROCEED (+1) */
    return omni_commit_proceed(&ctx->tripwire);
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/lua_tapes/character.lua

LUA | 149 LINES | 579 WORDS | 5.9 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & PROCESS TAPE MANIFEST
-- ( Process Tape: < Lexicon { Types of Ideas } > & [ Process { Character } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Interprets and executes the atomic lifecycle for Invariant Type < Character >.
--   Acts as the dynamic runtime companion driving C backbone struct `omni_character_t`.
--   - Defined Space: [ 1 Cell ] { 5 Trits :: 1 Byte }
--   - Execution Domain: Lexicon { Types of Ideas }
--   - Witness: Scripture Exodus 31:18 KJV
--     "And he gave unto Moses, when he had made an end of communing with him upon
--      mount Sinai, two tables of testimony, tables of stone, written with the
--      finger of God."
--   - Semantics: { GlyphInscription :: DualSubstrateTransduction :: SingleCellBound }
-- ================================================================================

local TapeEngine = require("lua_tapes.tape_engine")

local CONSTANTS = {
    CELL_CAPACITY       = 1,
    TRITS_PER_CELL      = 5,
    EXEMPLAR_GLYPH_A    = string.byte('A')
}

local CharacterTape = TapeEngine.create_tape({
    metadata = {
        who     = "OmniCode Lexicon",
        what    = "Character --> INSCRIBE { Glyph }",
        when    = "Input Event",
        where   = { character_cell = 1 },
        why     = "Inscribe atomic character type invariant into defined space",
        how     = "+1 : PROCEED",
        witness = "Exodus 31:18 KJV"
    },
    constants = CONSTANTS,
    rolls = {
        -- ------------------------------------------------------------------------
        -- ROLL 1: GLYPH INSCRIPTION (Outside-in imposition onto C cell)
        -- ------------------------------------------------------------------------
        {
            name = "Inscribe",
            action = function(ctx)
                ctx.c_cell.glyph = ctx.glyph
                ctx.c_cell.is_enclosed = true
                return TapeEngine.STATE_PROCEED
            end
        },

        -- ------------------------------------------------------------------------
        -- ROLL 2: DUAL-SUBSTRATE TRANSDUCTION (8 Bits <=> 5 Balanced Trits)
        -- ------------------------------------------------------------------------
        {
            name = "Transduce",
            action = function(ctx)
                local val = ctx.c_cell.glyph
                for i = 1, CONSTANTS.TRITS_PER_CELL do
                    local rem = val % 3
                    val = math.floor(val / 3)
                    if rem == 2 then
                        rem = -1
                        val = val + 1
                    elseif rem == -2 then
                        rem = 1
                        val = val - 1
                    end
                    ctx.c_cell.trits[i] = rem
                end
                return TapeEngine.STATE_PROCEED
            end
        },

        -- ------------------------------------------------------------------------
        -- ROLL 3: IDENTITY & BOUND COMPARISON (Guard Single-Cell Boundary)
```

```
        -- ------------------------------------------------------------------------
        {
            name = "Compare",
            action = function(ctx)
                local identity_ok = (ctx.c_cell.glyph == ctx.glyph)
                local bounds_ok   = (ctx.c_cell.is_enclosed == true)
                return TapeEngine.assert_guard(identity_ok and bounds_ok, ctx,
                                               "Character glyph or single-cell bound violation")
            end
        },

        -- ------------------------------------------------------------------------
        -- ROLL 4: TARGET PROJECTION (Inside-out emergence to output bus/terminal)
        -- ------------------------------------------------------------------------
        {
            name = "Project",
            action = function(ctx)
                if ctx.target then
                    table.insert(ctx.target, ctx.c_cell.glyph)
                end
                return TapeEngine.STATE_PROCEED
            end
        },

        -- ------------------------------------------------------------------------
        -- ROLL 5: SEQUENCE TRANSITION (Character chains toward continuous Text ribbon)
        -- ------------------------------------------------------------------------
        {
            name = "Sequence",
            action = function(ctx)
                ctx.sequence_ready = true
                return TapeEngine.STATE_PROCEED
            end
        }
    }
})

-- ============================================================================
-- BLOCK 2: OPENING BLOCK
-- ( Context Factory & C Cell Substrate Mount )
-- ============================================================================

---
-- Mounts the tape head, initialises the C cell handle, and arms the tripwire.
-- @param glyph Outside-in byte payload (defaults to ASCII 'A').
-- @param target_buffer Optional destination array (terminal or VGA buffer).
-- @return Initialized context table.
function CharacterTape.open(glyph, target_buffer)
    return {
        glyph    = glyph or CharacterTape.constants.EXEMPLAR_GLYPH_A,
        target   = target_buffer or {},
        c_cell   = {
            glyph       = 0,
            trits       = {0, 0, 0, 0, 0},
            is_enclosed = false
        },
        status   = TapeEngine.STATE_PROCEED,
        tripwire = TapeEngine.TRIPWIRE_ARMED
    }
end

-- ============================================================================
-- BLOCK 4: CLOSING BLOCK
-- ( Fourfold Detent Commit & Interlock Verification )
-- ============================================================================

---
-- Closes and seals the Character tape execution context.
-- @param ctx Active context handle.
-- @return Quad-State commit status and diagnostic seal message.
function CharacterTape.close(ctx)
    return TapeEngine.verify_and_commit(ctx)
end

return CharacterTape
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/lua_tapes/container.lua

LUA | 158 LINES | 632 WORDS | 6.5 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & PROCESS TAPE MANIFEST
-- ( Process Tape: < Lexicon { Types of Ideas } > & [ Process { Container } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Interprets and executes the atomic lifecycle for Invariant Type < Container >.
--   Acts as the dynamic runtime companion driving generic C backbone struct `omni_container_t`.
--   - Defined Space: Generic Bounded Memory Envelope / Slice
--   - Ladder Ascension: Build-up with Numbers (/-^)
--   - Witness: Scripture 2 Kings 4:4 KJV
--     "And when thou art come in, thou shalt shut the door upon thee and upon
--      thy sons, and shalt pour out into all those vessels, and thou shalt set
--      aside that which is full."
--   - Semantics: { MemoryCapsule :: BoundedEnvelope :: ContainmentLaw }
-- ================================================================================

local TapeEngine = require("lua_tapes.tape_engine")

local CONSTANTS = {
    EXEMPLAR_UNIT       = 1,
    EXEMPLAR_VESSEL     = 64,
    EXEMPLAR_STOREHOUSE = 4096
}

local ContainerTape = TapeEngine.create_tape({
    metadata = {
        who     = "OmniCode Lexicon",
        what    = "Container --> ENCAPSULATE { Payload }",
        when    = "Allocation Event",
        where   = { container_envelope = 64 },
        why     = "Inscribe bounded container type invariant and storage envelopes",
        how     = "+1 : PROCEED",
        witness = "2 Kings 4:4 KJV"
    },
    constants = CONSTANTS,
    rolls = {
        -- ------------------------------------------------------------------------
        -- ROLL 1: BUILD CAPSULE (Ladder build-up with Numbers)
        -- ------------------------------------------------------------------------
        {
            name = "BuildCapsule",
            action = function(ctx)
                local valid_cap = (ctx.c_container.capacity > 0)
                if valid_cap then
                    ctx.c_container.is_enclosed = true
                end
                return TapeEngine.assert_guard(valid_cap, ctx, "Container capacity must be greater than zero")
            end
        },

        -- ------------------------------------------------------------------------
        -- ROLL 2: ENCAPSULATION (Inscribe payload into bounded C envelope)
        -- ------------------------------------------------------------------------
        {
            name = "Encapsulate",
            action = function(ctx)
                local items = ctx.payload
                local count = #items

                -- Law { Containment } Guard: Occupancy must never exceed capacity limit
                local within_capacity = (count <= ctx.c_container.capacity)
                if not within_capacity then
                    return TapeEngine.assert_guard(false, ctx, "Payload count exceeds bounded container capacity")
                end

                for i = 1, count do
                    ctx.c_container.buffer[i] = items[i]
                end
                ctx.c_container.occupancy = count
                return TapeEngine.STATE_PROCEED
            end
        },

```

```
        -- ------------------------------------------------------------------------
        -- ROLL 3: IDENTITY & BOUND COMPARISON (Guard bounds under Law { Containment })
        -- ------------------------------------------------------------------------
        {
            name = "GuardBounds",
            action = function(ctx)
                local containment_valid = (ctx.c_container.occupancy <= ctx.c_container.capacity)
                local enclosed_valid    = (ctx.c_container.is_enclosed == true)
                return TapeEngine.assert_guard(containment_valid and enclosed_valid, ctx,
                                               "Core Containment Law violated: Occupancy > Capacity")
            end
        },

        -- ------------------------------------------------------------------------
        -- ROLL 4: POUR OUT & SET ASIDE (Inside-out emergence)
        -- ------------------------------------------------------------------------
        {
            name = "PourOut",
            action = function(ctx)
                ctx.sealed_vessel = {
                    origin  = ctx.c_container.buffer,
                    target  = ctx.target,
                    sealed  = true
                }
                return TapeEngine.STATE_PROCEED
            end
        },

        -- ------------------------------------------------------------------------
        -- ROLL 5: SEQUENCE TRANSITION (Container chains to composite structure)
        -- ------------------------------------------------------------------------
        {
            name = "Sequence",
            action = function(ctx)
                ctx.structure_ready = true
                return TapeEngine.STATE_PROCEED
            end
        }
    }
})

-- ============================================================================
-- BLOCK 2: OPENING BLOCK
-- ( Context Factory & C Container Slice Substrate Mount )
-- ============================================================================

---
-- Mounts the tape head, initialises the generic C container handle, and arms the tripwire.
-- @param payload Outside-in array of items (e.g. Character bytes or Numbers).
-- @param capacity Maximum number of elements (defaults to 64).
-- @param element_size Byte footprint of a single element (defaults to 1).
-- @return Initialized context table.
function ContainerTape.open(payload, capacity, element_size)
    local cap  = capacity or CONSTANTS.EXEMPLAR_VESSEL
    local e_sz = element_size or 1
    return {
        payload     = payload or {},
        target      = 0x00000000,
        c_container = {
            buffer       = {},
            element_size = e_sz,
            capacity     = cap,
            occupancy    = 0,
            is_enclosed  = false
        },
        status      = TapeEngine.STATE_PROCEED,
        tripwire    = TapeEngine.TRIPWIRE_ARMED
    }
end

-- ============================================================================
-- BLOCK 4: CLOSING BLOCK
-- ( Fourfold Detent Commit & Interlock Verification )
-- ============================================================================

---
-- Closes and seals the Container tape execution context.
-- @param ctx Active context handle.
```

```
-- @return Quad-State commit status and diagnostic seal message.
function ContainerTape.close(ctx)
    return TapeEngine.verify_and_commit(ctx)
end

return ContainerTape
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/lua_tapes/number.lua

LUA | 342 LINES | 1731 WORDS | 14.8 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & PROCESS TAPE MANIFEST
-- ( Process Tape: < Lexicon { Types of Ideas } > & [ Process { Number } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Interprets and executes the atomic lifecycle for Invariant Type < Number >.
--   Acts as dynamic runtime companion driving C backbone `omni_number_t`.
--   - Dual-Rail Polar Bit-Planes: 00=0 (Equilibrium), 01=+1, 10=-1, 11=Trap
--   - Directional Partitions: 3-3-2, 3-2-3, 2-3-3 (3-space minimum for Z)
--   - Witness: Scripture Psalm 147:4 KJV
--     "He telleth the number of the stars; he calleth them all by their names."
--   - Semantics: { DualRailBitPlanes :: KinematicTopologies :: ZeroSumALU }
-- ================================================================================

local TapeEngine = require("lua_tapes.tape_engine")

local CONSTANTS = {
    WORD_CAPACITY       = 1,
    TRITS_PER_WORD      = 32,
    BITS_PER_WORD       = 64,
    EXEMPLAR_ZERO       = 0,
    EXEMPLAR_UNITY_POS  = 1,
    EXEMPLAR_UNITY_NEG  = -1,
    EXEMPLAR_PARTITION  = 4096,
    BITPLANE_POS_MASK   = 0x5555555555555555,
    BITPLANE_NEG_MASK   = ~0x5555555555555555,
    TRIT_CODE_ZERO      = 0, -- 0b00: Equilibrium / 0
    TRIT_CODE_POS       = 1, -- 0b01: Positive / +1
    TRIT_CODE_NEG       = 2, -- 0b10: Negative / -1
    TRIT_CODE_NULL      = 3  -- 0b11: Collision / NULL trap
}

local PACK_MODES = {
    DENSE_2222        = 0, -- 2-2-2-2: Standard dense storage (4 trits)
    KINEMATIC_21212   = 1, -- 2-1-2-1-2: Symmetric resting equilibrium
    KINEMATIC_12122   = 2, -- 1-2-1-2-2: Prefix carry/overflow channel
    KINEMATIC_22121   = 3, -- 2-2-1-2-1: Postfix carry/overflow channel
    DIRECTIONAL_332   = 4, -- 3-3-2: Directional vector (X:3, Y:3, Z:2)
    DIRECTIONAL_323   = 5, -- 3-2-3: Directional vector (X:3, Y:2, Z:3)
    DIRECTIONAL_233   = 6  -- 2-3-3: Directional vector (X:2, Y:3, Z:3)
}

local function trit_to_2bit(trit)
    if trit == 0 then return CONSTANTS.TRIT_CODE_ZERO
    elseif trit == 1 then return CONSTANTS.TRIT_CODE_POS
    elseif trit == -1 then return CONSTANTS.TRIT_CODE_NEG
    else return CONSTANTS.TRIT_CODE_NULL end
end

local function two_bit_to_trit(code)
    if code == CONSTANTS.TRIT_CODE_ZERO then return 0, true
    elseif code == CONSTANTS.TRIT_CODE_POS then return 1, true
    elseif code == CONSTANTS.TRIT_CODE_NEG then return -1, true
    else return 0, false end -- NULL collision
end

local function pack_trits_dual_rail(trits)
    local packed = 0
    for i = 1, CONSTANTS.TRITS_PER_WORD do
        local t = trits[i] or 0
        local code = trit_to_2bit(t)
        packed = packed | ((code & 0x03) << ((i - 1) * 2))
    end
    return packed
end

local function unpack_trits_dual_rail(packed, out_trits)
    for i = 1, CONSTANTS.TRITS_PER_WORD do
        local code = (packed >> ((i - 1) * 2)) & 0x03
        local trit, ok = two_bit_to_trit(code)
        if not ok then return false end
        out_trits[i] = trit
    end
```

```
    return true
end

local function negate_dual_rail(packed)
    local pos_rails = packed & CONSTANTS.BITPLANE_POS_MASK
    local neg_rails = packed & CONSTANTS.BITPLANE_NEG_MASK
    return ((pos_rails << 1) & CONSTANTS.BITPLANE_NEG_MASK) |
           ((neg_rails >> 1) & CONSTANTS.BITPLANE_POS_MASK)
end

local function has_null_collision(packed)
    local pos_rails = packed & CONSTANTS.BITPLANE_POS_MASK
    local neg_rails = (packed >> 1) & CONSTANTS.BITPLANE_POS_MASK
    return (pos_rails & neg_rails) ~= 0
end

local function pack_byte(trits, mode)
    mode = mode or PACK_MODES.DENSE_2222
    local b = 0
    if mode == PACK_MODES.DENSE_2222 then
        for i = 1, 4 do
            local code = trit_to_2bit(trits[i] or 0)
            b = b | ((code & 0x03) << ((i - 1) * 2))
        end
    elseif mode == PACK_MODES.KINEMATIC_21212 then
        b = b | (trit_to_2bit(trits[1] or 0) & 0x03)
        b = b | ((trit_to_2bit(trits[2] or 0) & 0x01) << 2)
        b = b | ((trit_to_2bit(trits[2] or 0) & 0x03) << 3)
        b = b | (((trit_to_2bit(trits[2] or 0) >> 1) & 0x01) << 5)
        b = b | ((trit_to_2bit(trits[3] or 0) & 0x03) << 6)
    elseif mode == PACK_MODES.KINEMATIC_12122 then
        b = b | ((trit_to_2bit(trits[1] or 0) & 0x01) << 0)
        b = b | ((trit_to_2bit(trits[1] or 0) & 0x03) << 1)
        b = b | (((trit_to_2bit(trits[2] or 0) >> 1) & 0x01) << 3)
        b = b | ((trit_to_2bit(trits[2] or 0) & 0x03) << 4)
        b = b | ((trit_to_2bit(trits[3] or 0) & 0x03) << 6)
    elseif mode == PACK_MODES.KINEMATIC_22121 then
        b = b | ((trit_to_2bit(trits[1] or 0) & 0x03) << 0)
        b = b | ((trit_to_2bit(trits[2] or 0) & 0x03) << 2)
        b = b | ((trit_to_2bit(trits[3] or 0) & 0x01) << 4)
        b = b | ((trit_to_2bit(trits[3] or 0) & 0x03) << 5)
        b = b | (((trit_to_2bit(trits[3] or 0) >> 1) & 0x01) << 7)
    elseif mode == PACK_MODES.DIRECTIONAL_332 then
        local c1 = trit_to_2bit(trits[1] or 0) & 0x03
        local c2 = trit_to_2bit(trits[2] or 0) & 0x03
        local c3 = trit_to_2bit(trits[3] or 0) & 0x03
        b = b | (c1 << 0) | (c2 << 3) | (c3 << 6)
    elseif mode == PACK_MODES.DIRECTIONAL_323 then
        local c1 = trit_to_2bit(trits[1] or 0) & 0x03
        local c2 = trit_to_2bit(trits[2] or 0) & 0x03
        local c3 = trit_to_2bit(trits[3] or 0) & 0x03
        b = b | (c1 << 0) | (c2 << 3) | (c3 << 5)
    elseif mode == PACK_MODES.DIRECTIONAL_233 then
        local c1 = trit_to_2bit(trits[1] or 0) & 0x03
        local c2 = trit_to_2bit(trits[2] or 0) & 0x03
        local c3 = trit_to_2bit(trits[3] or 0) & 0x03
        b = b | (c1 << 0) | (c2 << 2) | (c3 << 5)
    end
    return b & 0xFF
end

local function unpack_byte(byte_val, mode, out_trits)
    mode = mode or PACK_MODES.DENSE_2222
    if mode == PACK_MODES.DENSE_2222 then
        for i = 1, 4 do
            local code = (byte_val >> ((i - 1) * 2)) & 0x03
            local t, ok = two_bit_to_trit(code)
            if not ok then return false end
            out_trits[i] = t
        end
    elseif mode == PACK_MODES.KINEMATIC_21212 then
        local t1, ok1 = two_bit_to_trit(byte_val & 0x03)
        local t2, ok2 = two_bit_to_trit((byte_val >> 3) & 0x03)
        local t3, ok3 = two_bit_to_trit((byte_val >> 6) & 0x03)
        if not (ok1 and ok2 and ok3) then return false end
        out_trits[1], out_trits[2], out_trits[3], out_trits[4] = t1, t2, t3, 0
    elseif mode == PACK_MODES.KINEMATIC_12122 then
        local t1, ok1 = two_bit_to_trit((byte_val >> 1) & 0x03)
```

```
        local t2, ok2 = two_bit_to_trit((byte_val >> 4) & 0x03)
        local t3, ok3 = two_bit_to_trit((byte_val >> 6) & 0x03)
        if not (ok1 and ok2 and ok3) then return false end
        out_trits[1], out_trits[2], out_trits[3], out_trits[4] = t1, t2, t3, 0
    elseif mode == PACK_MODES.KINEMATIC_22121 then
        local t1, ok1 = two_bit_to_trit((byte_val >> 0) & 0x03)
        local t2, ok2 = two_bit_to_trit((byte_val >> 2) & 0x03)
        local t3, ok3 = two_bit_to_trit((byte_val >> 5) & 0x03)
        if not (ok1 and ok2 and ok3) then return false end
        out_trits[1], out_trits[2], out_trits[3], out_trits[4] = t1, t2, t3, 0
    elseif mode == PACK_MODES.DIRECTIONAL_332 then
        local t1, ok1 = two_bit_to_trit((byte_val >> 0) & 0x03)
        local t2, ok2 = two_bit_to_trit((byte_val >> 3) & 0x03)
        local t3, ok3 = two_bit_to_trit((byte_val >> 6) & 0x03)
        if not (ok1 and ok2 and ok3) then return false end
        out_trits[1], out_trits[2], out_trits[3], out_trits[4] = t1, t2, t3, 0
    elseif mode == PACK_MODES.DIRECTIONAL_323 then
        local t1, ok1 = two_bit_to_trit((byte_val >> 0) & 0x03)
        local t2, ok2 = two_bit_to_trit((byte_val >> 3) & 0x03)
        local t3, ok3 = two_bit_to_trit((byte_val >> 5) & 0x03)
        if not (ok1 and ok2 and ok3) then return false end
        out_trits[1], out_trits[2], out_trits[3], out_trits[4] = t1, t2, t3, 0
    elseif mode == PACK_MODES.DIRECTIONAL_233 then
        local t1, ok1 = two_bit_to_trit((byte_val >> 0) & 0x03)
        local t2, ok2 = two_bit_to_trit((byte_val >> 2) & 0x03)
        local t3, ok3 = two_bit_to_trit((byte_val >> 5) & 0x03)
        if not (ok1 and ok2 and ok3) then return false end
        out_trits[1], out_trits[2], out_trits[3], out_trits[4] = t1, t2, t3, 0
    end
    return true
end

local NumberTape = TapeEngine.create_tape({
    metadata = {
        who     = "OmniCode Lexicon",
        what    = "Number --> MEASURE { Quantity }",
        when    = "Arithmetic Event",
        where   = { number_word = 1 },
        why     = "Inscribe scalar number invariant and arithmetic equilibrium",
        how     = "+1 : PROCEED",
        witness = "Psalm 147:4 KJV"
    },
    constants = CONSTANTS,
    pack_modes = PACK_MODES,
    rolls = {
        -- ------------------------------------------------------------------
        -- ROLL 1: QUANTITY INSCRIPTION (Outside-in imposition onto C word)
        -- ------------------------------------------------------------------
        {
            name = "Inscribe",
            action = function(ctx)
                ctx.c_word.scalar = ctx.quantity
                ctx.c_word.is_enclosed = true
                ctx.c_word.pack_mode = ctx.pack_mode or PACK_MODES.DENSE_2222
                return TapeEngine.STATE_PROCEED
            end
        },

        -- ------------------------------------------------------------------
        -- ROLL 2: DUAL-SUBSTRATE TRANSDUCTION (64 Bits <=> 32 Balanced Trits)
        -- ------------------------------------------------------------------
        {
            name = "Transduce",
            action = function(ctx)
                local current = ctx.c_word.scalar
                for i = 1, CONSTANTS.TRITS_PER_WORD do
                    if current == 0 then
                        ctx.c_word.trits[i] = 0
                    else
                        local rem = current % 3
                        current = math.floor(current / 3)
                        if rem == 2 then
                            rem = -1
                            current = current + 1
                        elseif rem == -2 then
                            rem = 1
                            current = current - 1
                        end
```

```
                        ctx.c_word.trits[i] = rem
                    end
                end
                -- Inscribe dual-rail bit-planes (64 bits native)
                local p = pack_trits_dual_rail(ctx.c_word.trits)
                ctx.c_word.packed_dual_rail = p
                return TapeEngine.STATE_PROCEED
            end
        },

        -- ------------------------------------------------------------------
        -- ROLL 3: IDENTITY & BOUND COMPARISON (Guard Single-Word Boundary)
        -- ------------------------------------------------------------------
        {
            name = "Compare",
            action = function(ctx)
                local identity_ok = (ctx.c_word.scalar == ctx.quantity)
                local bounds_ok   = (ctx.c_word.is_enclosed == true)
                local p = ctx.c_word.packed_dual_rail
                local no_null     = not has_null_collision(p)
                local roundtrip   = {}
                local unpack_ok   = unpack_trits_dual_rail(p, roundtrip)
                return TapeEngine.assert_guard(identity_ok and bounds_ok and
                                               no_null and unpack_ok, ctx,
                                               "Number bound or collision")
            end
        },

        -- ------------------------------------------------------------------
        -- ROLL 4: ARITHMETIC EQUILIBRIUM CALCULATION ((+1) plus (-1) <=> 0)
        -- ------------------------------------------------------------------
        {
            name = "Equilibrium",
            action = function(ctx)
                local eq = (1) + (-1)
                local eq_holds = (eq == 0)
                -- Prove SIMD rail-swap involution: -(-x) == x
                local neg = negate_dual_rail(ctx.c_word.packed_dual_rail)
                local neg_neg = negate_dual_rail(neg)
                local rail_involution = (neg_neg == ctx.c_word.packed_dual_rail)
                ctx.equilibrium_proved = eq_holds and rail_involution
                return TapeEngine.assert_guard(ctx.equilibrium_proved, ctx,
                                               "ALU Equilibrium Law violated")
            end
        },

        -- ------------------------------------------------------------------
        -- ROLL 5: SEQUENCE TRANSITION (Number chains toward Vector sequence)
        -- ------------------------------------------------------------------
        {
            name = "Sequence",
            action = function(ctx)
                ctx.vector_ready = true
                return TapeEngine.STATE_PROCEED
            end
        }
    }
})

-- Expose bit-plane and kinematic packing primitives
NumberTape.PACK_MODES             = PACK_MODES
NumberTape.trit_to_2bit           = trit_to_2bit
NumberTape.two_bit_to_trit        = two_bit_to_trit
NumberTape.pack_trits_dual_rail   = pack_trits_dual_rail
NumberTape.unpack_trits_dual_rail = unpack_trits_dual_rail
NumberTape.negate_dual_rail       = negate_dual_rail
NumberTape.has_null_collision     = has_null_collision
NumberTape.pack_byte              = pack_byte
NumberTape.unpack_byte            = unpack_byte

-- ============================================================================
-- BLOCK 2: OPENING BLOCK
-- ( Context Factory & C Word Substrate Mount )
-- ============================================================================

---
-- Mounts the tape head, initialises the C word handle, and arms the tripwire.
-- @param quantity Outside-in scalar integer (defaults to 4096).
```

```
-- @param pack_mode Kinematic packing mode (defaults to DENSE_2222).
-- @return Initialized context table.
function NumberTape.open(quantity, pack_mode)
    local p_mode = pack_mode or PACK_MODES.DENSE_2222
    return {
        quantity           = quantity or CONSTANTS.EXEMPLAR_PARTITION,
        pack_mode          = p_mode,
        c_word             = {
            scalar           = 0,
            trits            = {},
            packed_dual_rail = 0,
            pack_mode        = p_mode,
            is_enclosed      = false
        },
        equilibrium_proved = false,
        status             = TapeEngine.STATE_PROCEED,
        tripwire           = TapeEngine.TRIPWIRE_ARMED
    }
end

-- ============================================================================
-- BLOCK 4: CLOSING BLOCK
-- ( Fourfold Detent Commit & Interlock Verification )
-- ============================================================================

---
-- Closes and seals the Number tape execution context.
-- @param ctx Active context handle.
-- @return Quad-State commit status and diagnostic seal message.
function NumberTape.close(ctx)
    return TapeEngine.verify_and_commit(ctx)
end

return NumberTape
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/lua_tapes/site.lua

LUA | 148 LINES | 565 WORDS | 6.0 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & PROCESS TAPE MANIFEST
-- ( Process Tape: < Lexicon { Types of Ideas } > & [ Process { Site } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Interprets and executes the atomic lifecycle for Invariant Type < Site >.
--   Acts as the dynamic runtime companion driving C backbone struct `omni_site_t`.
--   - Defined Space: [ 1 Address ] { 64 Bits / Silicon Coordinate }
--   - Ladder Ascension: Build-up with Numbers (/-^)
--   - Witness: Scripture Genesis 28:16 KJV
--     "And Jacob awaked out of his sleep, and he said, Surely the Lord is in
--      this place; and I knew it not."
--   - Semantics: { SiliconCoordinate :: HardwareRoutingLaw :: NullPointerDetent }
-- ================================================================================

local TapeEngine = require("lua_tapes.tape_engine")

local CONSTANTS = {
    SITE_NULL   = 0x00000000,
    SITE_MBR    = 0x00007C00,
    SITE_COM1   = 0x000003F8,
    SITE_VGA    = 0x000B8000
}

local SiteTape = TapeEngine.create_tape({
    metadata = {
        who     = "OmniCode Lexicon",
        what    = "Site --> LOCATE { PhysicalAddress }",
        when    = "Addressing Event",
        where   = { silicon_coordinate = 1 },
        why     = "Inscribe physical site address invariant and hardware MMIO coordinates",
        how     = "+1 : PROCEED",
        witness = "Genesis 28:16 KJV"
    },
    constants = CONSTANTS,
    rolls = {
        -- ------------------------------------------------------------------------
        -- ROLL 1: LOCATE (Ladder build-up with Numbers)
        -- ------------------------------------------------------------------------
        {
            name = "Locate",
            action = function(ctx)
                local not_null = (ctx.coordinate ~= CONSTANTS.SITE_NULL)
                if not_null then
                    ctx.c_site.is_enclosed = true
                end
                return TapeEngine.assert_guard(not_null, ctx,
                                               "Null pointer address cannot be located as a valid silicon site")
            end
        },

        -- ------------------------------------------------------------------------
        -- ROLL 2: BIND COORDINATE (Inscribe address & resolve RAM vs MMIO routing)
        -- ------------------------------------------------------------------------
        {
            name = "BindCoordinate",
            action = function(ctx)
                ctx.c_site.coordinate = ctx.coordinate
                -- Hardware Routing Law: COM1, VGA, or >= 0xA0000 route to MMIO; otherwise RAM
                if ctx.coordinate == CONSTANTS.SITE_COM1 or
                   ctx.coordinate == CONSTANTS.SITE_VGA  or
                   ctx.coordinate >= 0x000A0000 then
                    ctx.c_site.routing = "HARDWARE_MMIO (::@)"
                else
                    ctx.c_site.routing = "PHYSICAL_RAM (@)"
                end
                return TapeEngine.STATE_PROCEED
            end
        },

        -- ------------------------------------------------------------------------
        -- ROLL 3: IDENTITY & NULL GUARD (Guard Non-Null Validity)
        -- ------------------------------------------------------------------------
```

```
        {
            name = "GuardAddress",
            action = function(ctx)
                local identity_ok = (ctx.c_site.coordinate == ctx.coordinate)
                local valid_site  = (ctx.c_site.coordinate ~= CONSTANTS.SITE_NULL and ctx.c_site.is_enclosed)
                return TapeEngine.assert_guard(identity_ok and valid_site, ctx,
                                               "Site address failed non-null validation check")
            end
        },

        -- ------------------------------------------------------------------
        -- ROLL 4: ROUTE & PROJECT (Inside-out emergence)
        -- ------------------------------------------------------------------
        {
            name = "Route",
            action = function(ctx)
                ctx.memory_anchor = {
                    coordinate = ctx.c_site.coordinate,
                    routing    = ctx.c_site.routing,
                    anchored   = true
                }
                return TapeEngine.STATE_PROCEED
            end
        },

        -- ------------------------------------------------------------------
        -- ROLL 5: SEQUENCE TRANSITION (Site chains to Memory Map)
        -- ------------------------------------------------------------------
        {
            name = "Sequence",
            action = function(ctx)
                ctx.memory_map_ready = true
                return TapeEngine.STATE_PROCEED
            end
        }
    }
})

-- ============================================================================
-- BLOCK 2: OPENING BLOCK
-- ( Context Factory & C Site Substrate Mount )
-- ============================================================================

---
-- Mounts the tape head, initialises the C site handle, and arms the tripwire.
-- @param coordinate Outside-in 64-bit silicon address (defaults to VGA buffer).
-- @return Initialized context table.
function SiteTape.open(coordinate)
    return {
        coordinate = coordinate or CONSTANTS.SITE_VGA,
        c_site     = {
            coordinate  = 0,
            routing     = "UNRESOLVED",
            is_enclosed = false
        },
        status     = TapeEngine.STATE_PROCEED,
        tripwire   = TapeEngine.TRIPWIRE_ARMED
    }
end

-- ============================================================================
-- BLOCK 4: CLOSING BLOCK
-- ( Fourfold Detent Commit & Interlock Verification )
-- ============================================================================

---
-- Closes and seals the Site tape execution context.
-- @param ctx Active context handle.
-- @return Quad-State commit status and diagnostic seal message.
function SiteTape.close(ctx)
    return TapeEngine.verify_and_commit(ctx)
end

return SiteTape
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/lua_tapes/state.lua

LUA | 183 LINES | 697 WORDS | 7.1 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & PROCESS TAPE MANIFEST
-- ( Process Tape: < Lexicon { Types of Ideas } > & [ Process { State } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Interprets and executes the atomic lifecycle for Invariant Type < State >.
--   Acts as the dynamic runtime companion driving C backbone struct `omni_state_t`.
--   - Defined Space: [ 1 Trit ] { 2 Bits / Quad-State Causal Register }
--   - Named Registers: [ STATE TURN BOUND IT ]
--   - Witness: Scripture Ecclesiastes 3:1 KJV
--     "To every thing there is a season, and a time to every purpose under
--      the heaven:"
--   - Semantics: { QuadStateTruth :: CausalClock :: CanonicalLoopLaw }
-- ================================================================================

local TapeEngine = require("lua_tapes.tape_engine")

local CONSTANTS = {
    STATE_PROCEED  = TapeEngine.STATE_PROCEED,
    STATE_AWAIT    = TapeEngine.STATE_AWAIT,
    STATE_ROLLBACK = TapeEngine.STATE_ROLLBACK,
    STATE_HALT     = TapeEngine.STATE_HALT,
    DEFAULT_BOUND  = 4
}

local StateTape = TapeEngine.create_tape({
    metadata = {
        who     = "OmniCode Lexicon",
        what    = "State --> GOVERN { CausalTruth }",
        when    = "Control Event",
        where   = { state_register = 1 },
        why     = "Inscribe quad-state truth invariant and execute canonical loops",
        how     = "+1 : PROCEED",
        witness = "Ecclesiastes 3:1 KJV"
    },
    constants = CONSTANTS,
    rolls = {
        -- ------------------------------------------------------------------------
        -- ROLL 1: INSCRIBE STATE REGISTER
        -- ------------------------------------------------------------------------
        {
            name = "Inscribe",
            action = function(ctx)
                ctx.c_state.registers.state = ctx.signal
                ctx.c_state.is_enclosed = true
                return TapeEngine.STATE_PROCEED
            end
        },

        -- ------------------------------------------------------------------------
        -- ROLL 2: CAVEAT GUARD AGAINST DISCREPANCY
        -- ------------------------------------------------------------------------
        {
            name = "GuardSignal",
            action = function(ctx)
                local signal_match = (ctx.c_state.registers.state == ctx.signal)
                return TapeEngine.assert_guard(signal_match, ctx,
                                               "State register truth signal discrepancy")
            end
        },

        -- ------------------------------------------------------------------------
        -- ROLL 3: CANONICAL LOOP STEPPER (Iterative Quad-State Cadence)
        -- ------------------------------------------------------------------------
        {
            name = "LoopCadence",
            action = function(ctx)
                local regs = ctx.c_state.registers
                while regs.state == TapeEngine.STATE_PROCEED do
                    if regs.it < regs.bound then
                        regs.it = regs.it + 1
                        regs.turn = regs.turn + 1
                        regs.state = TapeEngine.STATE_PROCEED
```

```
                    elseif regs.it > regs.bound then
                        regs.state = TapeEngine.STATE_AWAIT
                        break
                    else
                        -- Terminal Detent reached: IT == BOUND
                        regs.state = TapeEngine.STATE_HALT
                        break
                    end
                end
                return regs.state
            end
        },

        -- ------------------------------------------------------------------
        -- ROLL 4: GOVERN ENGINE (Inside-out emergence to machine clock)
        -- ------------------------------------------------------------------
        {
            name = "GovernClock",
            action = function(ctx)
                ctx.clock_active = (ctx.c_state.registers.state ~= TapeEngine.STATE_HALT)
                return TapeEngine.STATE_PROCEED
            end
        },

        -- ------------------------------------------------------------------
        -- ROLL 5: SEQUENCE TRANSITION (State chains to continuous Timeline)
        -- ------------------------------------------------------------------
        {
            name = "Sequence",
            action = function(ctx)
                ctx.timeline_ready = true
                return TapeEngine.STATE_PROCEED
            end
        }
    }
})

-- ============================================================================
-- BLOCK 2: OPENING BLOCK
-- ( Context Factory & C State Substrate Mount )
-- ============================================================================

---
-- Mounts the tape head, initialises the C state register bank handle, and arms the tripwire.
-- @param signal Outside-in truth signal (defaults to PROCEED).
-- @param bound Maximum iteration threshold (defaults to 4).
-- @return Initialized context table.
function StateTape.open(signal, bound)
    local sig = signal or CONSTANTS.STATE_PROCEED
    local bnd = bound or CONSTANTS.DEFAULT_BOUND
    return {
        signal   = sig,
        c_state  = {
            substrate_trit = 1,
            registers = {
                state = sig,
                turn  = 0,
                bound = bnd,
                it    = 0
            },
            is_enclosed = false
        },
        status   = TapeEngine.STATE_PROCEED,
        tripwire = TapeEngine.TRIPWIRE_ARMED
    }
end

-- ============================================================================
-- BLOCK 3: OPERATIONAL PRIMITIVES
-- ( Single-Step Loop Law Execution )
-- ============================================================================

---
-- Single-steps the Canonical Loop Law across named registers:
--   LOOP [ WHEN [ { IT } < { BOUND } ] --> [ IT` ] PROCEED to { TURN }
--          ! [ { IT } > { BOUND } ] AWAIT for [ IT` ]
--          :: HALT WHEN [ IT` ] = NULL ]
-- @param ctx Context handle holding register bank.
```

```
-- @return New Quad-State condition after the single step.
function StateTape.step_loop(ctx)
    local regs = ctx.c_state.registers
    if regs.it < regs.bound then
        regs.it = regs.it + 1
        regs.turn = regs.turn + 1
        regs.state = TapeEngine.STATE_PROCEED
        return TapeEngine.STATE_PROCEED
    elseif regs.it > regs.bound then
        regs.state = TapeEngine.STATE_AWAIT
        return TapeEngine.STATE_AWAIT
    else
        regs.state = TapeEngine.STATE_HALT
        return TapeEngine.STATE_HALT
    end
end

-- ============================================================================
-- BLOCK 4: CLOSING BLOCK
-- ( Fourfold Detent Commit & Interlock Verification )
-- ============================================================================

---
-- Closes and seals the State tape execution context.
-- @param ctx Active context handle.
-- @return Quad-State commit status and diagnostic seal message.
function StateTape.close(ctx)
    return TapeEngine.verify_and_commit(ctx)
end

return StateTape
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/lua_tapes/tape_engine.lua

LUA | 223 LINES | 957 WORDS | 8.6 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & ENGINE TOPOLOGY
-- ( Engine Core: < Lexicon { Types of Ideas } > & [ Process { Tape Engine } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   The interpreted execution ribbon companion to the OmniCode C Backbone.
--   Drives the dynamic temporal causation, coroutines, and roll kinematics:
--   - Coroutine-based fiber stepping (yielding on AWAIT, resuming on tick)
--   - Pre-roll and post-roll dynamic event hooks
--   - State snapshotting and active rollback unwinding
--   - Structured handles over C memory layouts and invariants
--   - Witness: Scripture Proverbs 16:9 KJV
--     "A man's heart deviseth his way: but the LORD directeth his steps."
--   - Semantics: { TapeKinematics :: CoroutineFiber :: RollHooks :: QuadStateDetents }
-- ================================================================================

local TapeEngine = {
    -- Quad-State Truth Constants
    STATE_ROLLBACK = -1,   -- -1 : Retroactive Reversal / Error Unwind
    STATE_AWAIT    =  0,   --  0 : Equilibrium Standby / Hold Pending
    STATE_PROCEED  =  1,   -- +1 : Forward Causation / Affirmative Advancement
    STATE_HALT     = "NULL",-- NULL : Terminal Detent / Stop Processor Clock

    -- Tripwire Interlock States
    TRIPWIRE_DISARMED = 0,
    TRIPWIRE_ARMED    = 1,
    TRIPWIRE_TRIPPED  = 2
}

-- Detect optional LuaJIT FFI for direct zero-copy C backbone linkage
local has_ffi, ffi = pcall(require, "ffi")
TapeEngine.has_ffi = has_ffi
TapeEngine.ffi = has_ffi and ffi or nil

-- ================================================================================
-- BLOCK 2: OPENING BLOCK
-- ( Subsystem Initialization, Preconditions & Tape Mounting )
-- ================================================================================

---
-- Deep copy snapshot utility for transactional rollback safety.
-- @param ctx The context table to clone.
-- @return Independent deep copy of the context.
local function make_snapshot(ctx)
    local snap = {}
    for k, v in pairs(ctx) do
        if type(v) == "table" then
            snap[k] = make_snapshot(v)
        else
            snap[k] = v
        end
    end
    return snap
end

---
-- Creates and mounts an interpreted Tape Process Ribbon.
-- @param spec Table containing metadata, constants, and declared rolls.
-- @return Mounted tape object.
function TapeEngine.create_tape(spec)
    local tape = {
        metadata    = spec.metadata or {},
        constants   = spec.constants or {},
        rolls       = spec.rolls or {},
        hooks       = {
            before_roll = {},
            after_roll  = {},
            on_rollback = {}
        },
        snapshots   = {},
        history     = {}
    }

```

```lua
    ---
    -- Registers a dynamic hook invoked immediately before a roll executes.
    function tape:before(fn)
        table.insert(self.hooks.before_roll, fn)
        return self
    end

    ---
    -- Registers a dynamic hook invoked immediately after a roll executes.
    function tape:after(fn)
        table.insert(self.hooks.after_roll, fn)
        return self
    end

    ---
    -- Registers a rollback handler invoked when a roll trips the interlock.
    function tape:on_rollback(fn)
        table.insert(self.hooks.on_rollback, fn)
        return self
    end

    ---
    -- Restores a previously captured execution snapshot into the active context.
    function tape:restore_snapshot(ctx, roll_index)
        local snap = self.snapshots[roll_index]
        if snap then
            for k, v in pairs(snap) do
                ctx[k] = v
            end
        end
    end

-- ==============================================================================
-- BLOCK 3: BODY BLOCK
-- ( Coroutine Kinematics, Roll Stepping & Hook Dispatch )
-- ==============================================================================

    ---
    -- Spawns a coroutine fiber that steps through the declared rolls.
    -- Yields on AWAIT (0), halts on HALT (NULL), and unwinds on ROLLBACK (-1).
    -- @param ctx Context handle holding the C struct proxy and tripwires.
    -- @return Lua coroutine object.
    function tape:spawn_coroutine(ctx)
        return coroutine.create(function()
            ctx.status = TapeEngine.STATE_PROCEED
            ctx.tripwire = TapeEngine.TRIPWIRE_ARMED

            for i, roll in ipairs(self.rolls) do
                -- 1. Snapshot state prior to roll execution for transaction rollback
                self.snapshots[i] = make_snapshot(ctx)

                -- 2. Dispatch pre-roll hooks
                for _, h in ipairs(self.hooks.before_roll) do
                    h(self, i, roll.name, ctx)
                end

                -- 3. Execute the declared roll action
                local status = roll.action(ctx)
                ctx.status = status or ctx.status

                -- 4. Dispatch post-roll hooks
                for _, h in ipairs(self.hooks.after_roll) do
                    h(self, i, roll.name, ctx, ctx.status)
                end

                -- Record execution trace
                table.insert(self.history, { roll = i, name = roll.name, status = ctx.status })

                -- 5. Quad-State transition evaluation
                if ctx.status == TapeEngine.STATE_AWAIT then
                    -- Yield execution back to host/game loop until external condition resolves
                    coroutine.yield("AWAIT", i, roll.name, ctx)
                elseif ctx.status == TapeEngine.STATE_ROLLBACK then
                    -- Invariant violation: trip safety interlock and trigger rollback unwinding
                    ctx.tripwire = TapeEngine.TRIPWIRE_TRIPPED
                    for _, h in ipairs(self.hooks.on_rollback) do
                        h(self, i, roll.name, ctx, self.snapshots[i])
                    end
```

```
                    return TapeEngine.STATE_ROLLBACK, "Tape rolled back at roll " .. i .. " [" .. roll.name .. "]"
                elseif ctx.status == TapeEngine.STATE_HALT then
                    -- Terminal Detent reached
                    return TapeEngine.STATE_HALT, "Tape reached terminal detent (HALT:NULL)"
                end
            end

            ctx.tripwire = TapeEngine.TRIPWIRE_DISARMED
            return TapeEngine.STATE_PROCEED, "Tape sealed in PROCEED (+1)"
        end)
    end

    ---
    -- Executes all rolls in a synchronous loop, automatically resuming AWAITs.
    -- @param ctx Context handle.
    -- @return Final Quad-State status code and descriptive seal message.
    function tape:execute_all(ctx)
        local co = self:spawn_coroutine(ctx)
        while coroutine.status(co) ~= "dead" do
            local ok, event, roll_idx, roll_name, curr_ctx = coroutine.resume(co)
            if not ok then
                error("Tape execution fatal error: " .. tostring(event))
            end
            if event == "AWAIT" then
                -- In synchronous batch mode, acknowledge standby and resume
                curr_ctx.status = TapeEngine.STATE_PROCEED
            elseif event == TapeEngine.STATE_PROCEED or event == TapeEngine.STATE_HALT or event ==
TapeEngine.STATE_ROLLBACK then
                return event, roll_idx
            end
        end
        return ctx.status
    end

    return tape
end

-- ============================================================================
-- BLOCK 4: CLOSING BLOCK
-- ( Integrity Seals & Commit Verification )
-- ============================================================================

---
-- Evaluates an invariant guard condition inside a roll action.
-- Trips the tripwire and triggers ROLLBACK on condition failure.
-- @param condition Boolean expression to verify.
-- @param ctx Context handle.
-- @param error_reason Message recorded upon tripwire trigger.
-- @return STATE_PROCEED if condition is true; STATE_ROLLBACK otherwise.
function TapeEngine.assert_guard(condition, ctx, error_reason)
    if condition then
        return TapeEngine.STATE_PROCEED
    else
        ctx.tripwire = TapeEngine.TRIPWIRE_TRIPPED
        ctx.error_reason = error_reason or "Invariant guard violation"
        return TapeEngine.STATE_ROLLBACK
    end
end

---
-- Verifies the final integrity of a context before closing commit.
-- @param ctx Context handle.
-- @return STATE_PROCEED if clean; STATE_ROLLBACK if tripped.
function TapeEngine.verify_and_commit(ctx)
    if ctx.tripwire == TapeEngine.TRIPWIRE_TRIPPED or ctx.status == TapeEngine.STATE_ROLLBACK then
        return TapeEngine.STATE_ROLLBACK, "Commit rejected: tripwire tripped"
    end
    ctx.tripwire = TapeEngine.TRIPWIRE_DISARMED
    return TapeEngine.STATE_PROCEED, "Context sealed in PROCEED (+1)"
end

return TapeEngine
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/lua/integrated/test_omni_lib.lua

LUA | 152 LINES | 634 WORDS | 7.0 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & TEST ORCHESTRATOR TOPOLOGY
-- ( Test Orchestrator: < Lexicon { Types of Ideas } > & [ Multi-File Testbed (Lua) ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Primary test orchestrator for the OmniCode Standard Library Lua Process Ribbons.
--   Executes multi-file unit test suites followed by integrated cross-type pipelines:
--   1. Unit Suite: Character Tape (Exodus 31:18 KJV)
--   2. Unit Suite: Number Tape (Psalm 147:4 KJV)
--   3. Unit Suite: Container Tape (2 Kings 4:4 KJV)
--   4. Unit Suite: Site Tape (Genesis 28:16 KJV)
--   5. Unit Suite: State Tape (Ecclesiastes 3:1 KJV)
--   6. Safety Interlock & Transactional Rollback (Proverbs 16:9 KJV)
--   7. Coroutine Fiber Stepping & AWAIT Yield/Resume
--   8. Integrated Composition: Container<Character> Traversed via State Loop
--   - Witness: Scripture Proverbs 24:27 KJV
--     "Prepare thy work without, and make it fit for thyself in the field;
--      and afterwards build thine house."
--   - Semantics: { MultiFileTestbed :: CrossTypeIntegration :: DetentVerification }
-- ================================================================================

package.path         = package.path ..
";./?.lua;./lua_tapes/?.lua;./tests/lua/unit/?.lua;./unit/?.lua;../unit/?.lua;../?.lua;../../?.lua"

local TestCommon     = require("test_common")
local TapeEngine     = require("lua_tapes.tape_engine")
local CharacterSuite = require("test_character")
local NumberSuite    = require("test_number")
local ContainerSuite = require("test_container")
local SiteSuite      = require("test_site")
local StateSuite     = require("test_state")

local CharacterTape  = require("lua_tapes.character")
local ContainerTape  = require("lua_tapes.container")
local SiteTape       = require("lua_tapes.site")
local StateTape      = require("lua_tapes.state")

print("================================================================================")
print("   OMNICODE STANDARD LIBRARY LUA ENGINE: MULTI-FILE TEST HARNESS")
print("================================================================================\n")

-- --------------------------------------------------------------------------------
-- 1. EXECUTE UNIT SUITES
-- --------------------------------------------------------------------------------
local suites = {
    CharacterSuite,
    NumberSuite,
    ContainerSuite,
    SiteSuite,
    StateSuite
}

for _, s in ipairs(suites) do
    local ok = s.run()
    if not ok then
        print(string.format("\n[ABORT] Unit suite failed! (%d failure(s))", TestCommon.failures))
        os.exit(1)
    end
    print("")
end

-- --------------------------------------------------------------------------------
-- 2. SAFETY INTERLOCK & TRANSACTIONAL ROLLBACK TEST
-- --------------------------------------------------------------------------------
print("[SUITE: Safety Interlock & Transactional Rollback]")
local rollback_caught = false
SiteTape:on_rollback(function(tape, roll_idx, roll_name, ctx, snapshot)
    rollback_caught = true
end)

local bad_site_ctx = SiteTape.open(0x00000000)
local bad_status, bad_msg = SiteTape:execute_all(bad_site_ctx)
TestCommon.assert_eq(bad_status, TapeEngine.STATE_ROLLBACK, "Expected STATE_ROLLBACK (-1)")
```

```
TestCommon.assert_eq(bad_site_ctx.tripwire, TapeEngine.TRIPWIRE_TRIPPED, "Expected TRIPWIRE_TRIPPED")
TestCommon.assert(rollback_caught == true, "Expected on_rollback hook to fire")
print(string.format("    -> Rollback Interlock: Status=%s, Tripwire=%d (%s) [PASS]\n",
    tostring(bad_status), bad_site_ctx.tripwire, bad_site_ctx.error_reason))

-- ------------------------------------------------------------------------------
-- 3. COROUTINE FIBER STEPPING & YIELD/RESUME TEST
-- ------------------------------------------------------------------------------
print("[SUITE: Coroutine Fiber Stepping & AWAIT Yield/Resume]")
local FiberTape = TapeEngine.create_tape({
    metadata = { name = "FiberSteppingTape" },
    rolls = {
        {
            name = "PhaseOne",
            action = function(ctx)
                ctx.counter = ctx.counter + 1
                return TapeEngine.STATE_AWAIT -- Request coroutine yield
            end
        },
        {
            name = "PhaseTwo",
            action = function(ctx)
                ctx.counter = ctx.counter * 10
                return TapeEngine.STATE_PROCEED
            end
        }
    }
})

local fiber_ctx = { counter = 5, status = TapeEngine.STATE_PROCEED, tripwire = TapeEngine.TRIPWIRE_ARMED }
local co = FiberTape:spawn_coroutine(fiber_ctx)

-- First resume: yields on PhaseOne AWAIT
local ok1, ev1, roll1, name1 = coroutine.resume(co)
TestCommon.assert(ok1 and ev1 == "AWAIT" and fiber_ctx.counter == 6, "Expected AWAIT yield at counter=6")
print(string.format("    -> Yielded on '%s' at roll %d [%s] (Counter=%d) [PASS]",
    ev1, roll1, name1, fiber_ctx.counter))

-- Reset status from AWAIT to PROCEED for phase two resume
fiber_ctx.status = TapeEngine.STATE_PROCEED
local ok2, ev2, msg2 = coroutine.resume(co)
TestCommon.assert(ok2 and ev2 == TapeEngine.STATE_PROCEED and fiber_ctx.counter == 60, "Expected PROCEED at counter=60")
print(string.format("    -> Resumed to Completion: Status=%s (Counter=%d, %s) [PASS]\n",
    tostring(ev2), fiber_ctx.counter, msg2))

-- ------------------------------------------------------------------------------
-- 4. CROSS-TYPE COMPOSITION PIPELINE
-- ------------------------------------------------------------------------------
print("[SUITE: Cross-Type Composition Pipeline]")
local word_bytes = {
    string.byte('O'), string.byte('M'), string.byte('N'), string.byte('I'),
    string.byte('C'), string.byte('O'), string.byte('D'), string.byte('E')
}
local container_ctx = ContainerTape.open(word_bytes, 32, 1)
local cont_status, cont_msg = ContainerTape:execute_all(container_ctx)
TestCommon.assert_eq(cont_status, TapeEngine.STATE_PROCEED, "Container execute must PROCEED")

io.write("    -> Driving Traversal via Canonical State Loop:\n       Transduced Output: \"")
local state_ctx = StateTape.open(TapeEngine.STATE_PROCEED, container_ctx.c_container.occupancy)

while state_ctx.c_state.registers.state == TapeEngine.STATE_PROCEED do
    local idx = state_ctx.c_state.registers.it + 1
    local ch = container_ctx.c_container.buffer[idx]
    if ch then
        io.write(string.char(ch))
    end
    StateTape.step_loop(state_ctx)
end
io.write("\"\n")

TestCommon.assert_eq(state_ctx.c_state.registers.state, TapeEngine.STATE_HALT, "State must reach HALT:NULL detent")
print(string.format("       Final Detent: %s (Detent at IT=%d, TURN=%d) [PASS]\n",
    tostring(state_ctx.c_state.registers.state),
    state_ctx.c_state.registers.it,
    state_ctx.c_state.registers.turn))

print("================================================================================")
```

```
print("   [ALL LUA ENGINE TESTS PASS]: FULL 4-BLOCK PARITY SEALED IN PROCEED (+1)")
print("================================================================================")
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/lua/unit/test_character.lua

LUA | 89 LINES | 437 WORDS | 4.1 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & TEST TOPOLOGY
-- ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { Character Tape } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Validates the interpreted process ribbon < Character Tape > in isolation:
--   - Bijective round-trip transduction (8 bits <=> 5 balanced trits)
--   - Strict single-cell enclosure boundary laws
--   - Dynamic pre/post roll hook observation
--   - Full 4-block lifecycle execution (open, execute_all, close)
--   - Witness: Scripture Exodus 31:18 KJV
--     "And he gave unto Moses, when he had made an end of communing with him upon
--      mount Sinai, two tables of testimony, tables of stone, written with the
--      finger of God."
--   - Semantics: { GlyphFidelity :: BalancedTritLaw :: SingleCellEnclosure }
-- ================================================================================

package.path        = package.path ..
";./?.lua;./lua_tapes/?.lua;./tests/lua/unit/?.lua;./unit/?.lua;../?.lua;../../?.lua"

local TestCommon    = require("test_common")
local TapeEngine    = require("lua_tapes.tape_engine")
local CharacterTape = require("lua_tapes.character")

local Suite         = {}

function Suite.test_character_transduction()
    local glyphs = { string.byte('A'), string.byte('Z'), string.byte('0'), string.byte('9'), 32, 0, 70, 100, 121 }
    for _, g in ipairs(glyphs) do
        local ctx = CharacterTape.open(g)
        local status = CharacterTape:execute_all(ctx)
        TestCommon.assert_eq(status, TapeEngine.STATE_PROCEED, "Execution status must PROCEED (+1)")
        TestCommon.assert_eq(ctx.c_cell.glyph, g, "Context cell glyph must match input")
        TestCommon.assert(ctx.c_cell.is_enclosed == true, "Context cell must be enclosed")

        -- Reconstruct byte from trits: sum_{i=1..5} trits[i] * 3^(i-1)
        local reconstructed = 0
        local power = 1
        for i = 1, #ctx.c_cell.trits do
            local t = ctx.c_cell.trits[i]
            TestCommon.assert(t >= -1 and t <= 1, "Trit must be in {-1, 0, +1}")
            reconstructed = reconstructed + t * power
            power = power * 3
        end
        TestCommon.assert_eq(reconstructed, g, "Reconstructed byte from trits must match input")
    end
end

function Suite.test_character_dynamic_hooks()
    local pre_hooks = 0
    local post_hooks = 0

    CharacterTape:before(function() pre_hooks = pre_hooks + 1 end)
    CharacterTape:after(function() post_hooks = post_hooks + 1 end)

    local ctx = CharacterTape.open(string.byte('Q'))
    local status = CharacterTape:execute_all(ctx)
    TestCommon.assert_eq(status, TapeEngine.STATE_PROCEED, "Execution must PROCEED")
    TestCommon.assert(pre_hooks >= 5, "Must trigger pre-roll hooks for all 5 rolls")
    TestCommon.assert(post_hooks >= 5, "Must trigger post-roll hooks for all 5 rolls")
end

function Suite.test_character_lifecycle_rolls()
    local ctx = CharacterTape.open(string.byte('C'))
    TestCommon.assert_eq(ctx.tripwire, TapeEngine.TRIPWIRE_ARMED, "Tripwire must be ARMED on open")

    local status = CharacterTape:execute_all(ctx)
    TestCommon.assert_eq(status, TapeEngine.STATE_PROCEED, "Execution must PROCEED")

    local close_st, close_msg = CharacterTape.close(ctx)
    TestCommon.assert_eq(close_st, TapeEngine.STATE_PROCEED, "Close must seal in PROCEED (+1)")
    TestCommon.assert_eq(ctx.tripwire, TapeEngine.TRIPWIRE_DISARMED, "Tripwire must be DISARMED on close")
end
```

```
73
74  function Suite.run()
75      print("[SUITE: Character Process Ribbon (Lua)]")
76      local ok1 = TestCommon.run_test("Bijective Round-Trip Transduction", Suite.test_character_transduction)
77      local ok2 = TestCommon.run_test("Dynamic Pre/Post Roll Hooks", Suite.test_character_dynamic_hooks)
78      local ok3 = TestCommon.run_test("4-Block Lifecycle Rolls", Suite.test_character_lifecycle_rolls)
79      return ok1 and ok2 and ok3
80  end
81
82  -- Allow standalone execution
83  if pcall(debug.getlocal, 4, 1) == false then
84      local ok = Suite.run()
85      os.exit(ok and 0 or 1)
86  end
87
88  return Suite
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/lua/unit/test_common.lua

LUA | 49 LINES | 188 WORDS | 1.7 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & TEST HARNESS TOPOLOGY
-- ( Test Framework: < OmniCode Standard Library Lua Testbed > )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Shared test harness for the OmniCode Standard Library Lua Process Ribbons.
--   Provides structured assertions, test suite runner helpers, and tripwire checks.
--   - Witness: Scripture Proverbs 24:27 KJV
--     "Prepare thy work without, and make it fit for thyself in the field;
--      and afterwards build thine house."
--   - Semantics: { AssertionInterlock :: GranularFaultIsolation :: MultiFileTestbed }
-- ================================================================================

local TestCommon = {
    failures = 0,
    tests_run = 0
}

function TestCommon.assert(condition, msg)
    TestCommon.tests_run = TestCommon.tests_run + 1
    if not condition then
        TestCommon.failures = TestCommon.failures + 1
        error("    [FAIL] Assertion failed: " .. tostring(msg), 2)
    end
end

function TestCommon.assert_eq(actual, expected, msg)
    TestCommon.tests_run = TestCommon.tests_run + 1
    if actual ~= expected then
        TestCommon.failures = TestCommon.failures + 1
        error(string.format("    [FAIL] %s: Expected [%s], got [%s]", tostring(msg), tostring(expected), tostring(actual)), 2)
    end
end

function TestCommon.run_test(name, fn)
    io.write(string.format("    -> %s ... ", name))
    local ok, err = pcall(fn)
    if ok then
        print("[PASS]")
        return true
    else
        print("[FAILED]")
        print(tostring(err))
        return false
    end
end

return TestCommon
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/lua/unit/test_container.lua

LUA | 79 LINES | 397 WORDS | 3.7 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & TEST TOPOLOGY
-- ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { Container Tape } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Validates the interpreted process ribbon < Container Tape > in isolation:
--   - Bounded memory capsule build-up
--   - Payload encapsulation into bounded envelope
--   - Law of Containment verification (Occupancy <= Capacity)
--   - Overflow detection and tripwire interlock rollback
--   - Full 4-block lifecycle execution (open, execute_all, close)
--   - Witness: Scripture 2 Kings 4:4 KJV
--     "And when thou art come in, thou shalt shut the door upon thee and upon
--      thy sons, and shalt pour out into all those vessels, and thou shalt set
--      aside that which is full."
--   - Semantics: { MemoryCapsule :: BoundedEnvelope :: ContainmentLaw }
-- ================================================================================

package.path        = package.path .. ";./?.lua;./lua_tapes/?.lua;./tests/lua/unit/?.lua;./unit/?.lua;../?.lua;../../?.lua"

local TestCommon    = require("test_common")
local TapeEngine    = require("lua_tapes.tape_engine")
local ContainerTape = require("lua_tapes.container")

local Suite         = {}

function Suite.test_container_encapsulation()
    local payload = { 10, 20, 30, 40, 50 }
    local ctx = ContainerTape.open(payload, 16, 1)

    local status = ContainerTape:execute_all(ctx)
    TestCommon.assert_eq(status, TapeEngine.STATE_PROCEED, "Execution must PROCEED (+1)")
    TestCommon.assert_eq(ctx.c_container.occupancy, 5, "Container occupancy must be 5")
    TestCommon.assert_eq(ctx.c_container.capacity, 16, "Container capacity must be 16")
    TestCommon.assert(ctx.c_container.is_enclosed == true, "Container must be enclosed")
    TestCommon.assert(ctx.sealed_vessel ~= nil, "Sealed vessel must emerge from Roll 4")
    TestCommon.assert_eq(ctx.sealed_vessel.sealed, true, "Vessel must be sealed")
end

function Suite.test_container_overflow_tripwire()
    -- Create payload exceeding capacity limit
    local oversized = {}
    for i = 1, 10 do oversized[i] = i end

    local ctx = ContainerTape.open(oversized, 4, 1) -- Capacity is 4, payload is 10
    local status = ContainerTape:execute_all(ctx)

    TestCommon.assert_eq(status, TapeEngine.STATE_ROLLBACK, "Overflow must trigger STATE_ROLLBACK (-1)")
    TestCommon.assert_eq(ctx.tripwire, TapeEngine.TRIPWIRE_TRIPPED, "Tripwire must be TRIPPED on containment violation")
end

function Suite.test_container_lifecycle_rolls()
    local ctx = ContainerTape.open({ 1, 2, 3 }, 8, 1)
    TestCommon.assert_eq(ctx.tripwire, TapeEngine.TRIPWIRE_ARMED, "Tripwire must be ARMED on open")

    local status = ContainerTape:execute_all(ctx)
    TestCommon.assert_eq(status, TapeEngine.STATE_PROCEED, "Execution must PROCEED")

    local close_st, close_msg = ContainerTape.close(ctx)
    TestCommon.assert_eq(close_st, TapeEngine.STATE_PROCEED, "Close must seal in PROCEED (+1)")
    TestCommon.assert_eq(ctx.tripwire, TapeEngine.TRIPWIRE_DISARMED, "Tripwire must be DISARMED on close")
end

function Suite.run()
    print("[SUITE: Container Process Ribbon (Lua)]")
    local ok1 = TestCommon.run_test("Bounded Payload Encapsulation", Suite.test_container_encapsulation)
    local ok2 = TestCommon.run_test("Overflow Containment Tripwire & Rollback", Suite.test_container_overflow_tripwire)
    local ok3 = TestCommon.run_test("4-Block Lifecycle Rolls", Suite.test_container_lifecycle_rolls)
    return ok1 and ok2 and ok3
end

-- Allow standalone execution
```

```
if pcall(debug.getlocal, 4, 1) == false then
    local ok = Suite.run()
    os.exit(ok and 0 or 1)
end

return Suite
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/lua/unit/test_number.lua

LUA | 197 LINES | 851 WORDS | 8.4 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & TEST TOPOLOGY
-- ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { Number Tape } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Validates the interpreted process ribbon < Number Tape > in isolation:
--   - Radix-3 balanced ternary transduction (64 bits <=> 32 balanced trits)
--   - Dual-rail polar bit-planes: 00=0 (Equilibrium), 01=+1, 10=-1, 11=Trap
--   - SIMD rail-swap negation: -(-X) == X via bit-plane swap
--   - Collision detection: NULL code (11) trips safety interlock
--   - Dynamic packing topologies: 2-2-2-2, 2-1-2-1-2, 1-2-1-2-2, 2-2-1-2-1,
--     3-3-2, 3-2-3, 2-3-3
--   - Core ALU Zero-Sum Equilibrium Law: (+1) plus (-1) <=> 0
--   - Single-word boundary laws & 4-block lifecycle execution
--   - Witness: Scripture Psalm 147:4 KJV
--     "He telleth the number of the stars; he calleth them all by their names."
--   - Semantics: { DualRailPlanes :: KinematicTopologies :: ZeroSumBalance }
-- ================================================================================

package.path = package.path .. ";./?.lua;./lua_tapes/?.lua;" ..
               "./tests/lua/unit/?.lua;./unit/?.lua;../?.lua;../../?.lua"

local TestCommon = require("test_common")
local TapeEngine = require("lua_tapes.tape_engine")
local NumberTape = require("lua_tapes.number")

local Suite = {}

function Suite.test_number_dual_rail_bitplanes()
    -- 1. Test 2-bit codes: 00=0, 01=+1, 10=-1, 11=trap
    TestCommon.assert_eq(NumberTape.trit_to_2bit(0), 0, "0 must map to 0b00")
    TestCommon.assert_eq(NumberTape.trit_to_2bit(1), 1, "1 must map to 0b01")
    TestCommon.assert_eq(NumberTape.trit_to_2bit(-1), 2, "-1 must map to 0b10")

    local t0, ok0 = NumberTape.two_bit_to_trit(0)
    TestCommon.assert(ok0 and t0 == 0, "0b00 must decode to 0")
    local t1, ok1 = NumberTape.two_bit_to_trit(1)
    TestCommon.assert(ok1 and t1 == 1, "0b01 must decode to +1")
    local t2, ok2 = NumberTape.two_bit_to_trit(2)
    TestCommon.assert(ok2 and t2 == -1, "0b10 must decode to -1")
    local _, ok3 = NumberTape.two_bit_to_trit(3)
    TestCommon.assert(not ok3, "0b11 must report collision / NULL trap")

    -- 2. Test dual-rail packing and unpacking
    local trits = {}
    for i = 1, 32 do
        if i % 3 == 1 then trits[i] = 1
        elseif i % 3 == 2 then trits[i] = -1
        else trits[i] = 0 end
    end
    local packed = NumberTape.pack_trits_dual_rail(trits)
    local unpacked = {}
    local ok = NumberTape.unpack_trits_dual_rail(packed, unpacked)
    TestCommon.assert(ok, "Unpack must succeed on valid trits")
    for i = 1, 32 do
        TestCommon.assert_eq(unpacked[i], trits[i],
                             "Unpacked trit must match original at " .. i)
    end
end

function Suite.test_number_simd_rail_swap_negation()
    local trits = {}
    for i = 1, 32 do
        if i % 3 == 1 then trits[i] = 1
        elseif i % 3 == 2 then trits[i] = -1
        else trits[i] = 0 end
    end
    local packed = NumberTape.pack_trits_dual_rail(trits)
    local negated = NumberTape.negate_dual_rail(packed)

    local unpacked_neg = {}
    local ok = NumberTape.unpack_trits_dual_rail(negated, unpacked_neg)
    TestCommon.assert(ok, "Unpack negated trits must succeed")
```

```
    for i = 1, 32 do
        TestCommon.assert_eq(unpacked_neg[i], -trits[i],
                             "Negated trit must invert sign at " .. i)
    end

    -- Involution: -(-X) == X
    local double_neg = NumberTape.negate_dual_rail(negated)
    TestCommon.assert_eq(double_neg, packed,
                         "Double rail-swap negation must restore original")
end

function Suite.test_number_null_collision_trap()
    -- Valid packed trits have no null collision
    local trits = { 1, -1, 0, 1 }
    local packed = NumberTape.pack_trits_dual_rail(trits)
    TestCommon.assert(not NumberTape.has_null_collision(packed),
                      "Valid trits must not trigger null collision")

    -- Manually inject 11 (code 3) into trit slot 0
    local corrupted = packed | 3
    TestCommon.assert(NumberTape.has_null_collision(corrupted),
                      "Corrupted dual-rail must detect null collision")

    local unpacked = {}
    local ok = NumberTape.unpack_trits_dual_rail(corrupted, unpacked)
    TestCommon.assert(not ok, "Unpacking corrupted dual-rail must fail")
end

function Suite.test_number_dynamic_packing_topologies()
    local modes = {
        NumberTape.PACK_MODES.DENSE_2222,
        NumberTape.PACK_MODES.KINEMATIC_21212,
        NumberTape.PACK_MODES.KINEMATIC_12122,
        NumberTape.PACK_MODES.KINEMATIC_22121,
        NumberTape.PACK_MODES.DIRECTIONAL_332,
        NumberTape.PACK_MODES.DIRECTIONAL_323,
        NumberTape.PACK_MODES.DIRECTIONAL_233
    }
    local test_trits = { 1, -1, 1, -1 }

    for _, mode in ipairs(modes) do
        local byte_val = NumberTape.pack_byte(test_trits, mode)
        local out_trits = {}
        local ok = NumberTape.unpack_byte(byte_val, mode, out_trits)
        TestCommon.assert(ok, "Unpack byte must succeed for mode " .. mode)
        -- Verify first 3 trits match in kinematic / directional modes
        TestCommon.assert_eq(out_trits[1], test_trits[1], "Trit 1 must match")
        TestCommon.assert_eq(out_trits[2], test_trits[2], "Trit 2 must match")
        TestCommon.assert_eq(out_trits[3], test_trits[3], "Trit 3 must match")
        if mode == NumberTape.PACK_MODES.DENSE_2222 then
            TestCommon.assert_eq(out_trits[4], test_trits[4],
                                 "Trit 4 must match in dense mode")
        end
    end
end

function Suite.test_number_transduction()
    local values = { 0, 1, -1, 4096, -4096, 65536 }
    for _, val in ipairs(values) do
        local ctx = NumberTape.open(val)
        local status = NumberTape:execute_all(ctx)
        TestCommon.assert_eq(status, TapeEngine.STATE_PROCEED,
                             "Execution must PROCEED (+1)")
        TestCommon.assert_eq(ctx.c_word.scalar, val,
                             "Context word scalar must match input")
        TestCommon.assert(ctx.c_word.is_enclosed == true,
                          "Context word must be enclosed")
        TestCommon.assert_eq(ctx.equilibrium_proved, true,
                             "ALU Zero-Sum Equilibrium must be proved")
    end
end

function Suite.test_number_equilibrium_law()
    -- Direct law verification: (+1) + (-1) == 0
    local sum = (1) + (-1)
    TestCommon.assert_eq(sum, 0,
                         "ALU Zero-Sum Equilibrium Law must evaluate to zero")
end
```

```
152
153 function Suite.test_number_lifecycle_rolls()
154     local ctx = NumberTape.open(4096)
155     TestCommon.assert_eq(ctx.tripwire, TapeEngine.TRIPWIRE_ARMED,
156                          "Tripwire must be ARMED on open")
157
158     local status = NumberTape:execute_all(ctx)
159     TestCommon.assert_eq(status, TapeEngine.STATE_PROCEED,
160                          "Execution must PROCEED")
161
162     local close_st = NumberTape.close(ctx)
163     TestCommon.assert_eq(close_st, TapeEngine.STATE_PROCEED,
164                          "Close must seal in PROCEED (+1)")
165     TestCommon.assert_eq(ctx.tripwire, TapeEngine.TRIPWIRE_DISARMED,
166                          "Tripwire must be DISARMED on close")
167 end
168
169 function Suite.run()
170     print("[SUITE: Number Process Ribbon (Lua)]")
171     local ok1 = TestCommon.run_test("Dual-Rail Polar Bit-Planes",
172                                     Suite.test_number_dual_rail_bitplanes)
173     local ok2 = TestCommon.run_test("SIMD Rail-Swap Negation",
174                                     Suite.test_number_simd_rail_swap_negation)
175     local ok3 = TestCommon.run_test("NULL Collision Trap",
176                                     Suite.test_number_null_collision_trap)
177     local ok4 = TestCommon.run_test(
178         "Dynamic Packing Topologies",
179         Suite.test_number_dynamic_packing_topologies
180     )
181     local ok5 = TestCommon.run_test("Radix-3 Balanced Transduction",
182                                     Suite.test_number_transduction)
183     local ok6 = TestCommon.run_test("ALU Zero-Sum Equilibrium Law",
184                                     Suite.test_number_equilibrium_law)
185     local ok7 = TestCommon.run_test("4-Block Lifecycle Rolls",
186                                     Suite.test_number_lifecycle_rolls)
187     return ok1 and ok2 and ok3 and ok4 and ok5 and ok6 and ok7
188 end
189
190 -- Allow standalone execution
191 if pcall(debug.getlocal, 4, 1) == false then
192     local ok = Suite.run()
193     os.exit(ok and 0 or 1)
194 end
195
196 return Suite
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/lua/unit/test_site.lua

LUA | 82 LINES | 379 WORDS | 3.8 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & TEST TOPOLOGY
-- ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { Site Tape } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Validates the interpreted process ribbon < Site Tape > in isolation:
--   - Silicon coordinate binding
--   - Hardware Routing Law (MMIO vs RAM coordinates)
--   - Null pointer address rejection and safety interlock rollback
--   - Memory anchor emergence
--   - Full 4-block lifecycle execution (open, execute_all, close)
--   - Witness: Scripture Genesis 28:16 KJV
--     "And Jacob awaked out of his sleep, and he said, Surely the Lord is in
--      this place; and I knew it not."
--   - Semantics: { SiliconCoordinates :: HardwareRoutingLaw :: NonNullInterlock }
-- ================================================================================

package.path     = package.path .. ";./?.lua;./lua_tapes/?.lua;./tests/lua/unit/?.lua;./unit/?.lua;../?.lua;../../?.lua"

local TestCommon = require("test_common")
local TapeEngine = require("lua_tapes.tape_engine")
local SiteTape   = require("lua_tapes.site")

local Suite      = {}

function Suite.test_site_routing()
    -- VGA buffer -> MMIO
    local vga_ctx = SiteTape.open(SiteTape.constants.SITE_VGA)
    local vga_st = SiteTape:execute_all(vga_ctx)
    TestCommon.assert_eq(vga_st, TapeEngine.STATE_PROCEED, "VGA site must PROCEED")
    TestCommon.assert_eq(vga_ctx.c_site.routing, "HARDWARE_MMIO (::@)", "VGA must route to MMIO")
    TestCommon.assert(vga_ctx.memory_anchor.anchored == true, "Memory anchor must be set")

    -- COM1 serial port -> MMIO
    local com1_ctx = SiteTape.open(SiteTape.constants.SITE_COM1)
    local com1_st = SiteTape:execute_all(com1_ctx)
    TestCommon.assert_eq(com1_st, TapeEngine.STATE_PROCEED, "COM1 site must PROCEED")
    TestCommon.assert_eq(com1_ctx.c_site.routing, "HARDWARE_MMIO (::@)", "COM1 must route to MMIO")

    -- MBR origin -> RAM
    local mbr_ctx = SiteTape.open(SiteTape.constants.SITE_MBR)
    local mbr_st = SiteTape:execute_all(mbr_ctx)
    TestCommon.assert_eq(mbr_st, TapeEngine.STATE_PROCEED, "MBR site must PROCEED")
    TestCommon.assert_eq(mbr_ctx.c_site.routing, "PHYSICAL_RAM (@)", "MBR must route to RAM")
end

function Suite.test_site_null_tripwire()
    local null_ctx = SiteTape.open(0x00000000)
    local status = SiteTape:execute_all(null_ctx)

    TestCommon.assert_eq(status, TapeEngine.STATE_ROLLBACK, "Null coordinate must trigger STATE_ROLLBACK (-1)")
    TestCommon.assert_eq(null_ctx.tripwire, TapeEngine.TRIPWIRE_TRIPPED, "Tripwire must be TRIPPED on null address")
end

function Suite.test_site_lifecycle_rolls()
    local ctx = SiteTape.open(SiteTape.constants.SITE_VGA)
    TestCommon.assert_eq(ctx.tripwire, TapeEngine.TRIPWIRE_ARMED, "Tripwire must be ARMED on open")

    local status = SiteTape:execute_all(ctx)
    TestCommon.assert_eq(status, TapeEngine.STATE_PROCEED, "Execution must PROCEED")

    local close_st, close_msg = SiteTape.close(ctx)
    TestCommon.assert_eq(close_st, TapeEngine.STATE_PROCEED, "Close must seal in PROCEED (+1)")
    TestCommon.assert_eq(ctx.tripwire, TapeEngine.TRIPWIRE_DISARMED, "Tripwire must be DISARMED on close")
end

function Suite.run()
    print("[SUITE: Site Process Ribbon (Lua)]")
    local ok1 = TestCommon.run_test("Hardware Routing Law (MMIO vs RAM)", Suite.test_site_routing)
    local ok2 = TestCommon.run_test("Null Address Rejection & Interlock Rollback", Suite.test_site_null_tripwire)
    local ok3 = TestCommon.run_test("4-Block Lifecycle Rolls", Suite.test_site_lifecycle_rolls)
    return ok1 and ok2 and ok3
end
```

```
74
75  -- Allow standalone execution
76  if pcall(debug.getlocal, 4, 1) == false then
77      local ok = Suite.run()
78      os.exit(ok and 0 or 1)
79  end
80
81  return Suite
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/lua/unit/test_state.lua

LUA | 93 LINES | 439 WORDS | 4.2 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & TEST TOPOLOGY
-- ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { State Tape } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Validates the interpreted process ribbon < State Tape > in isolation:
--   - Quad-State named registers: [ STATE TURN BOUND IT ]
--   - Canonical Loop Law cadence and single-step detents:
--       WHEN IT < BOUND  --> PROCEED (+1)
--       !    IT > BOUND  --> AWAIT (0)
--       ::   IT == BOUND --> HALT (NULL)
--   - Clock governance emergence
--   - Full 4-block lifecycle execution (open, execute_all, close)
--   - Witness: Scripture Ecclesiastes 3:1 KJV
--     "To every thing there is a season, and a time to every purpose under
--      the heaven:"
--   - Semantics: { QuadStateTruth :: CanonicalLoopCadence :: CausalDetents }
-- ================================================================================

package.path = package.path .. ";./?.lua;./lua_tapes/?.lua;./tests/lua/unit/?.lua;./unit/?.lua;../?.lua;../../?.lua"

local TestCommon = require("test_common")
local TapeEngine = require("lua_tapes.tape_engine")
local StateTape  = require("lua_tapes.state")

local Suite = {}

function Suite.test_state_canonical_loop()
    local ctx = StateTape.open(TapeEngine.STATE_PROCEED, 3)

    TestCommon.assert_eq(ctx.c_state.registers.bound, 3, "Bound must be 3")
    TestCommon.assert_eq(ctx.c_state.registers.it, 0, "Initial IT must be 0")
    TestCommon.assert_eq(ctx.c_state.registers.turn, 0, "Initial TURN must be 0")

    -- Step 1
    local st1 = StateTape.step_loop(ctx)
    TestCommon.assert_eq(st1, TapeEngine.STATE_PROCEED, "Step 1 must PROCEED")
    TestCommon.assert_eq(ctx.c_state.registers.it, 1, "IT must be 1")

    -- Step 2
    local st2 = StateTape.step_loop(ctx)
    TestCommon.assert_eq(st2, TapeEngine.STATE_PROCEED, "Step 2 must PROCEED")
    TestCommon.assert_eq(ctx.c_state.registers.it, 2, "IT must be 2")

    -- Step 3
    local st3 = StateTape.step_loop(ctx)
    TestCommon.assert_eq(st3, TapeEngine.STATE_PROCEED, "Step 3 must PROCEED")
    TestCommon.assert_eq(ctx.c_state.registers.it, 3, "IT must be 3")

    -- Step 4: IT == BOUND -> HALT:NULL
    local st4 = StateTape.step_loop(ctx)
    TestCommon.assert_eq(st4, TapeEngine.STATE_HALT, "Step 4 must reach terminal detent HALT:NULL")
    TestCommon.assert_eq(ctx.c_state.registers.state, TapeEngine.STATE_HALT, "Register state must be HALT:NULL")
end

function Suite.test_state_await_transition()
    local ctx = StateTape.open(TapeEngine.STATE_PROCEED, 4)
    ctx.c_state.registers.it = 5 -- Manually set IT > BOUND

    local st = StateTape.step_loop(ctx)
    TestCommon.assert_eq(st, TapeEngine.STATE_AWAIT, "IT > BOUND must transition to AWAIT (0)")
end

function Suite.test_state_lifecycle_rolls()
    local ctx = StateTape.open(TapeEngine.STATE_PROCEED, 4)
    TestCommon.assert_eq(ctx.tripwire, TapeEngine.TRIPWIRE_ARMED, "Tripwire must be ARMED on open")

    local status = StateTape:execute_all(ctx)
    TestCommon.assert_eq(status, TapeEngine.STATE_HALT, "Execution must reach terminal detent HALT:NULL")
    TestCommon.assert_eq(ctx.c_state.registers.it, 4, "Final IT must equal bound 4")
    TestCommon.assert_eq(ctx.c_state.registers.state, TapeEngine.STATE_HALT, "Register state must reach HALT:NULL")

    local close_st, close_msg = StateTape.close(ctx)
```

```
    TestCommon.assert_eq(close_st, TapeEngine.STATE_PROCEED, "Close must seal in PROCEED (+1)")
    TestCommon.assert_eq(ctx.tripwire, TapeEngine.TRIPWIRE_DISARMED, "Tripwire must be DISARMED on close")
end

function Suite.run()
    print("[SUITE: State Process Ribbon (Lua)]")
    local ok1 = TestCommon.run_test("Canonical Loop Law Cadence (IT < BOUND -> HALT)", Suite.test_state_canonical_loop)
    local ok2 = TestCommon.run_test("Standby Transition (IT > BOUND -> AWAIT)", Suite.test_state_await_transition)
    local ok3 = TestCommon.run_test("4-Block Lifecycle Rolls", Suite.test_state_lifecycle_rolls)
    return ok1 and ok2 and ok3
end

-- Allow standalone execution
if pcall(debug.getlocal, 4, 1) == false then
    local ok = Suite.run()
    os.exit(ok and 0 or 1)
end

return Suite
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/compile_flags.txt

TXT | 6 LINES | 5 WORDS | 0.1 KB

```
-Iincludes
-I../../c_backbone/include
-Wall
-Wextra
-std=c11
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/test_number.o DOC/BINARY 1 LINES 5 WORDS 21.8 KB

[Binary Artifact: test_number.o (21.8 KB)]

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/integrated/test_omni_lib.c

C | 121 LINES | 492 WORDS | 5.5 KB

```c
/* ========================================================================
 * BLOCK 1: METADATA & INTEGRATION TEST TOPOLOGY
 * ( Test Orchestrator: < Lexicon { Types of Ideas } > & [ Multi-File Testbed ] )
 * ========================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Primary test orchestrator for the OmniCode Standard Library C Backbone.
 *   Executes multi-file unit test suites followed by integrated cross-type pipelines:
 *   1. Unit Suite: Character (Exodus 31:18 KJV)
 *   2. Unit Suite: Number (Psalm 147:4 KJV)
 *   3. Unit Suite: Container (2 Kings 4:4 KJV)
 *   4. Unit Suite: Site (Genesis 28:16 KJV)
 *   5. Unit Suite: State (Ecclesiastes 3:1 KJV)
 *   6. Integrated Composition: Container<Character> Traversed via State Loop
 *   - Witness: Scripture Proverbs 24:27 KJV
 *     "Prepare thy work without, and make it fit for thyself in the field;
 *      and afterwards build thine house."
 *   - Semantics: { MultiFileTestbed :: CrossTypeIntegration :: DetentVerification }
 * ======================================================================== */

#include "test_common.h"
#include <stdio.h>

/* Global test failure accumulator */
int g_omni_test_failures = 0;

/* ========================================================================
 * BLOCK 2: OPENING CONTEXT & INTEGRATED PIPELINE DEFINITIONS
 * ======================================================================== */

static int run_cross_type_integration_pipeline(void) {
    printf("[SUITE: Cross-Type Composition Pipeline]\n");
    printf("  -> Composing Container<Character> (\"The Text Substrate\") ...\n");

    #define TEST_TEXT_CAPACITY 32
    omni_character_t text_storage[TEST_TEXT_CAPACITY];
    omni_container_t text_ribbon;
    omni_container_init(&text_ribbon, text_storage, sizeof(omni_character_t), TEST_TEXT_CAPACITY);

    const char *source_str = "OMNICODE";
    for (size_t i = 0; source_str[i] != '\0'; ++i) {
        omni_character_t ch = omni_character_from_glyph((uint8_t)source_str[i]);
        omni_quad_state_t push_res = omni_container_push(&text_ribbon, &ch);
        OMNI_TEST_ASSERT(push_res == OMNI_STATE_PROCEED, "Container push must succeed without overflow");
    }

    OMNI_TEST_ASSERT(text_ribbon.occupancy == 8, "Text ribbon occupancy must be 8");
    printf("  -> Capacity: %zu, Occupancy: %zu [PASS]\n", text_ribbon.capacity, text_ribbon.occupancy);

    /* Traversal via Canonical State Loop */
    printf("  -> Driving Traversal via Canonical State Loop:\n     Transduced Output: \"");
    omni_state_t traversal_state = omni_state_create(OMNI_STATE_PROCEED, (int64_t)text_ribbon.occupancy);

    while (omni_state_is_proceeding(&traversal_state)) {
        size_t idx = (size_t)traversal_state.registers.it;
        omni_character_t *curr = (omni_character_t *)omni_container_get(&text_ribbon, idx);
        if (curr) {
            putchar((char)curr->glyph);
        }
        omni_state_step_loop(&traversal_state.registers);
    }
    printf("\"\n");

    OMNI_TEST_ASSERT(omni_state_is_halted(&traversal_state) == true, "Traversal must reach HALT:NULL detent");
    OMNI_TEST_ASSERT(traversal_state.registers.it == 8, "Final IT must equal 8");
    OMNI_TEST_ASSERT(traversal_state.registers.turn == 8, "Final TURN must equal 8");
    printf("     Final Detent: HALT:NULL (IT=8, TURN=8) [PASS]\n");

    /* Route Site to VGA Buffer MMIO */
    omni_site_t vga_site = omni_site_from_address(OMNI_SITE_VGA_BUFFER);
    OMNI_TEST_ASSERT(vga_site.routing == OMNI_ROUTING_HARDWARE_MMIO, "VGA site must resolve to HARDWARE_MMIO");
    printf("  -> Virtual Hardware MMIO Routing: 0x%lX -> HARDWARE_MMIO (::@) [PASS]\n",
           (unsigned long)vga_site.coordinate);

```

```
    return 0;
}

/* ============================================================================
 * BLOCK 3: BODY PRIMITIVES & MAIN TEST RUNNER
 * ============================================================================ */

int main(void) {
    printf("================================================================================\n");
    printf("   OMNICODE STANDARD LIBRARY C BACKBONE: MULTI-FILE TEST HARNESS\n");
    printf("================================================================================\n\n");

    /* Run Unit Test Suites */
    if (test_character_suite() != 0) goto failure;
    printf("\n");

    if (test_number_suite() != 0) goto failure;
    printf("\n");

    if (test_container_suite() != 0) goto failure;
    printf("\n");

    if (test_site_suite() != 0) goto failure;
    printf("\n");

    if (test_state_suite() != 0) goto failure;
    printf("\n");

    /* Run Cross-Type Integration Pipeline */
    if (run_cross_type_integration_pipeline() != 0) goto failure;
    printf("\n");

/* ============================================================================
 * BLOCK 4: CLOSING BLOCK & FINAL DETENT REPORT
 * ============================================================================ */

    printf("================================================================================\n");
    printf("   [ALL C BACKBONE TESTS PASS]: FULL 4-BLOCK PARITY SEALED IN PROCEED (+1)\n");
    printf("================================================================================\n");
    return 0;

failure:
    printf("\n================================================================================\n");
    printf("   [TEST SUITE FAILURE]: %d assertion failure(s) recorded!\n", g_omni_test_failures);
    printf("================================================================================\n");
    return 1;
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/includes/test_common.h

H | 65 LINES | 248 WORDS | 2.3 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & TEST HARNESS TOPOLOGY
 * ( Test Framework: < OmniCode Standard Library Testbed > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Shared test harness for the OmniCode Standard Library C Transpile Variant.
 *   Provides structured assertions, test suite runner macros, and tripwire checks.
 *   - Witness: Scripture Proverbs 24:27 KJV
 *     "Prepare thy work without, and make it fit for thyself in the field;
 *      and afterwards build thine house."
 *   - Semantics: { AssertionInterlock :: GranularFaultIsolation :: MultiFileTestbed }
 * ============================================================================ */

#ifndef OMNI_TEST_COMMON_H
#define OMNI_TEST_COMMON_H

#include "omni.h"
#include <stdio.h>
#include <stdbool.h>

/* ============================================================================
 * BLOCK 2: OPENING CONTEXT & MACRO DEFINITIONS
 * ============================================================================ */

/** Global test assertion failure counter */
extern int g_omni_test_failures;

/**
 * @brief Evaluates an assertion expression; logs failure and returns 1 on error.
 */
#define OMNI_TEST_ASSERT(expr, msg) \
    do { \
        if (!(expr)) { \
            printf("    [FAIL] %s:%d: %s (Expression: %s)\n", __FILE__, __LINE__, (msg), #expr); \
            g_omni_test_failures++; \
            return 1; \
        } \
    } while (0)

/**
 * @brief Runs an individual test function and reports PASS / FAIL.
 */
#define OMNI_TEST_RUN(fn, test_name) \
    do { \
        printf("    -> %s ... ", (test_name)); \
        if ((fn)() != 0) { \
            printf("[FAILED]\n"); \
            return 1; \
        } \
        printf("[PASS]\n"); \
    } while (0)

/* ============================================================================
 * BLOCK 3: BODY PRIMITIVES & SUITE EXPORTS
 * ============================================================================ */

/** Unit test suite prototypes */
int test_character_suite(void);
int test_number_suite(void);
int test_container_suite(void);
int test_site_suite(void);
int test_state_suite(void);

#endif /* OMNI_TEST_COMMON_H */
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/unit/test_character.c

C | 121 LINES | 599 WORDS | 5.8 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & TEST TOPOLOGY
 * ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { Character } ] )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Validates the atomic invariant type < Character > in isolation:
 *   - Bijective round-trip transduction (8 bits <=> 5 balanced trits)
 *   - Strict single-cell enclosure boundary laws
 *   - Full 4-block lifecycle execution (open, execute, close)
 *   - Relational equality and comparison
 *   - Witness: Scripture Exodus 31:18 KJV
 *     "And he gave unto Moses, when he had made an end of communing with him upon
 *      mount Sinai, two tables of testimony, tables of stone, written with the
 *      finger of God."
 *   - Semantics: { GlyphFidelity :: BalancedTritLaw :: SingleCellEnclosure }
 * ============================================================================ */

#include "test_common.h"

/* ============================================================================
 * BLOCK 2: OPENING CONTEXT & FIXTURE SETUP
 * ============================================================================ */

static int test_character_bijective_roundtrip(void) {
    /* Test exemplar characters across 5-trit cell capacity (0..121) */
    const uint8_t test_glyphs[] = {'A', 'Z', '0', '9', ' ', 0, 70, 100, 121};
    const size_t num_glyphs = sizeof(test_glyphs) / sizeof(test_glyphs[0]);

    for (size_t i = 0; i < num_glyphs; ++i) {
        uint8_t original = test_glyphs[i];
        omni_character_t c = omni_character_from_glyph(original);

        /* Verify enclosure */
        OMNI_TEST_ASSERT(c.is_enclosed == true, "Character must be enclosed");
        OMNI_TEST_ASSERT(c.glyph == original, "Character glyph must match original");

        /* Verify every trit is in valid balanced range {-1, 0, +1} */
        for (size_t t = 0; t < OMNI_CHAR_TRITS_PER_CELL; ++t) {
            OMNI_TEST_ASSERT(c.trits[t] >= -1 && c.trits[t] <= 1, "Trit must be in {-1, 0, +1}");
        }

        /* Verify inverse transduction reconstructs the exact byte */
        uint8_t reconstructed = omni_character_to_byte(c.trits);
        OMNI_TEST_ASSERT(reconstructed == original, "Inverse transduction must exactly match original byte");
    }
    return 0;
}

static int test_character_bounds_and_enclosure(void) {
    omni_character_t valid_char = omni_character_from_glyph('X');
    OMNI_TEST_ASSERT(omni_character_verify_bounds(&valid_char) == true, "Valid character must pass boundary check");

    /* Corrupt enclosure flag to test boundary tripwire */
    omni_character_t corrupted = valid_char;
    corrupted.is_enclosed = false;
    OMNI_TEST_ASSERT(omni_character_verify_bounds(&corrupted) == false, "Unenclosed character must fail boundary check");

    return 0;
}

static int test_character_relational_equality(void) {
    omni_character_t a1 = omni_character_from_glyph('M');
    omni_character_t a2 = omni_character_from_glyph('M');
    omni_character_t b  = omni_character_from_glyph('N');

    OMNI_TEST_ASSERT(omni_character_eq(&a1, &a2) == true, "Identical glyphs must evaluate equal");
    OMNI_TEST_ASSERT(omni_character_eq(&a1, &b) == false, "Distinct glyphs must not evaluate equal");

    return 0;
}

static int test_character_lifecycle_rolls(void) {
    omni_character_context_t ctx;
```

```
    omni_character_open(&ctx, 'K', OMNI_TARGET_STDOUT);

    OMNI_TEST_ASSERT(ctx.tripwire == OMNI_TRIPWIRE_ARMED, "Context tripwire must be ARMED upon open");
    OMNI_TEST_ASSERT(ctx.input_glyph == 'K', "Input glyph must be recorded in context");

    /* Execute the 3 declared rolls */
    omni_quad_state_t exec_status = omni_character_execute(&ctx);
    OMNI_TEST_ASSERT(exec_status == OMNI_STATE_PROCEED, "Character execute must PROCEED (+1)");
    OMNI_TEST_ASSERT(ctx.character.is_enclosed == true, "Character must be enclosed after execution");
    OMNI_TEST_ASSERT(ctx.character.glyph == 'K', "Character glyph must match input");

    /* Close and commit */
    omni_quad_state_t close_status = omni_character_close(&ctx);
    OMNI_TEST_ASSERT(close_status == OMNI_STATE_PROCEED, "Character close must PROCEED (+1)");
    OMNI_TEST_ASSERT(ctx.tripwire == OMNI_TRIPWIRE_DISARMED, "Tripwire must be DISARMED upon clean close");

    return 0;
}

static int test_character_bit_level_and_ascii_invariant(void) {
    omni_character_t a = omni_character_from_glyph('A'); /* 65 = 0b01000001 */
    OMNI_TEST_ASSERT(omni_character_is_ascii(&a) == true, "'A' must be ASCII");
    OMNI_TEST_ASSERT(omni_character_get_bit(&a, 0) == 1, "Bit 0 of 'A' must be 1");
    OMNI_TEST_ASSERT(omni_character_get_bit(&a, 1) == 0, "Bit 1 of 'A' must be 0");
    OMNI_TEST_ASSERT(omni_character_get_bit(&a, 6) == 1, "Bit 6 of 'A' must be 1");
    OMNI_TEST_ASSERT(omni_character_get_bit(&a, 7) == 0, "Bit 7 of 'A' must be 0 (parity rail)");

    omni_character_t high = omni_character_from_glyph(200);
    OMNI_TEST_ASSERT(omni_character_is_ascii(&high) == false, "200 is not standard ASCII");
    OMNI_TEST_ASSERT(omni_character_get_bit(&high, 7) == 1, "Bit 7 of 200 must be 1");

    return 0;
}

/* ============================================================================
 * BLOCK 3: BODY PRIMITIVES & TEST SUITE RUNNER
 * ============================================================================ */

int test_character_suite(void) {
    printf("[SUITE: Character Invariant Type]\n");
    OMNI_TEST_RUN(test_character_bijective_roundtrip, "Bijective Round-Trip Transduction");
    OMNI_TEST_RUN(test_character_bounds_and_enclosure, "Single-Cell Enclosure Bounds");
    OMNI_TEST_RUN(test_character_bit_level_and_ascii_invariant, "Bit-Level Slicing & ASCII Invariant");
    OMNI_TEST_RUN(test_character_relational_equality, "Relational Equality");
    OMNI_TEST_RUN(test_character_lifecycle_rolls, "4-Block Lifecycle Rolls");
    return 0;
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/unit/test_container.c

C | 145 LINES | 670 WORDS | 6.5 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & TEST TOPOLOGY
 * ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { Container } ] )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Validates the generic memory capsule type < Container > in isolation:
 *   - Bounded slice allocation and element encapsulation
 *   - Law of Containment verification (Occupancy <= Capacity)
 *   - Overflow detection and tripwire interlock triggering
 *   - Standard 64-byte vessel envelope
 *   - Full 4-block lifecycle execution (open, execute, close)
 *   - Witness: Scripture 2 Kings 4:4 KJV
 *     "And when thou art come in, thou shalt shut the door upon thee and upon
 *      thy sons, and shalt pour out into all those vessels, and thou shalt set
 *      aside that which is full."
 *   - Semantics: { MemoryCapsule :: BoundedSlice :: ContainmentLaw }
 * ============================================================================ */

#include "test_common.h"

/* ============================================================================
 * BLOCK 2: OPENING CONTEXT & FIXTURE SETUP
 * ============================================================================ */

static int test_container_basic_lifecycle(void) {
    uint32_t storage[8];
    omni_container_t c;
    omni_container_init(&c, storage, sizeof(uint32_t), 8);

    OMNI_TEST_ASSERT(c.capacity == 8, "Container capacity must be 8");
    OMNI_TEST_ASSERT(c.occupancy == 0, "Container occupancy must initially be 0");
    OMNI_TEST_ASSERT(c.is_enclosed == true, "Container must be enclosed");
    OMNI_TEST_ASSERT(omni_container_is_empty(&c) == true, "Container must report empty");

    /* Push 4 elements */
    for (uint32_t i = 1; i <= 4; ++i) {
        omni_quad_state_t push_st = omni_container_push(&c, &i);
        OMNI_TEST_ASSERT(push_st == OMNI_STATE_PROCEED, "Push must PROCEED");
    }
    OMNI_TEST_ASSERT(c.occupancy == 4, "Occupancy must be 4");

    /* Verify random access get */
    for (size_t i = 0; i < 4; ++i) {
        uint32_t *val = (uint32_t *)omni_container_get(&c, i);
        OMNI_TEST_ASSERT(val != NULL, "Get must return non-null pointer");
        OMNI_TEST_ASSERT(*val == (uint32_t)(i + 1), "Stored element must match pushed value");
    }

    /* Out of bounds get must return NULL */
    OMNI_TEST_ASSERT(omni_container_get(&c, 10) == NULL, "Out of bounds get must return NULL");

    /* Test random access set */
    uint32_t new_val = 999;
    omni_quad_state_t set_st = omni_container_set(&c, 1, &new_val);
    OMNI_TEST_ASSERT(set_st == OMNI_STATE_PROCEED, "Set must PROCEED");
    uint32_t *read_back = (uint32_t *)omni_container_get(&c, 1);
    OMNI_TEST_ASSERT(read_back != NULL && *read_back == 999, "Read back value at index 1 must be 999");

    /* Clear */
    omni_container_clear(&c);
    OMNI_TEST_ASSERT(c.occupancy == 0, "Occupancy must be 0 after clear");
    OMNI_TEST_ASSERT(omni_container_is_empty(&c) == true, "Container must report empty after clear");

    return 0;
}

static int test_container_overflow_tripwire(void) {
    uint8_t tiny_storage[2];
    omni_container_t c;
    omni_container_init(&c, tiny_storage, sizeof(uint8_t), 2);

    uint8_t a = 10, b = 20, c_overflow = 30;
    OMNI_TEST_ASSERT(omni_container_push(&c, &a) == OMNI_STATE_PROCEED, "First push must PROCEED");
```

```
    OMNI_TEST_ASSERT(omni_container_push(&c, &b) == OMNI_STATE_PROCEED, "Second push must PROCEED");
    OMNI_TEST_ASSERT(omni_container_is_full(&c) == true, "Container must report full at capacity 2");

    /* Third push MUST fail and return ROLLBACK (-1) */
    omni_quad_state_t overflow_res = omni_container_push(&c, &c_overflow);
    OMNI_TEST_ASSERT(overflow_res == OMNI_STATE_ROLLBACK, "Overflow push must return ROLLBACK (-1)");
    OMNI_TEST_ASSERT(c.occupancy == 2, "Occupancy must remain capped at capacity");

    return 0;
}

static int test_container_containment_law(void) {
    uint8_t storage[4];
    omni_container_t c;
    omni_container_init(&c, storage, sizeof(uint8_t), 4);

    OMNI_TEST_ASSERT(omni_container_verify_containment(&c) == true, "Valid container must pass Containment Law");

    /* Violate containment law manually */
    omni_container_t corrupted = c;
    corrupted.occupancy = 10; /* Exceeds capacity 4 */
    OMNI_TEST_ASSERT(omni_container_verify_containment(&corrupted) == false, "Overflowed occupancy must violate
Containment Law");

    return 0;
}

static int test_byte_vessel_envelope(void) {
    omni_byte_vessel_t vessel;
    omni_byte_vessel_init(&vessel);

    OMNI_TEST_ASSERT(vessel.container.capacity == OMNI_CONTAINER_EXEMPLAR_VESSEL, "Byte vessel capacity must be 64");
    OMNI_TEST_ASSERT(vessel.container.element_size == 1, "Element size must be 1 byte");
    OMNI_TEST_ASSERT(vessel.container.occupancy == 0, "Byte vessel must initially be empty");

    return 0;
}

static int test_container_lifecycle_rolls(void) {
    uint16_t storage[16];
    uint16_t payload[4] = {100, 200, 300, 400};

    omni_container_context_t ctx;
    omni_container_open(&ctx, storage, sizeof(uint16_t), 16, payload, 4);

    OMNI_TEST_ASSERT(ctx.tripwire == OMNI_TRIPWIRE_ARMED, "Tripwire must be ARMED upon open");
    OMNI_TEST_ASSERT(ctx.payload_count == 4, "Payload count must be 4");

    omni_quad_state_t exec_status = omni_container_execute(&ctx);
    OMNI_TEST_ASSERT(exec_status == OMNI_STATE_PROCEED, "Container execute must PROCEED (+1)");
    OMNI_TEST_ASSERT(ctx.vessel.occupancy == 4, "Vessel occupancy must match payload count");

    omni_quad_state_t close_status = omni_container_close(&ctx);
    OMNI_TEST_ASSERT(close_status == OMNI_STATE_PROCEED, "Container close must PROCEED (+1)");
    OMNI_TEST_ASSERT(ctx.tripwire == OMNI_TRIPWIRE_DISARMED, "Tripwire must be DISARMED upon clean close");

    return 0;
}

/* ============================================================================
 * BLOCK 3: BODY PRIMITIVES & TEST SUITE RUNNER
 * ============================================================================ */

int test_container_suite(void) {
    printf("[SUITE: Container Invariant Type]\n");
    OMNI_TEST_RUN(test_container_basic_lifecycle, "Basic Allocation, Push & Pop");
    OMNI_TEST_RUN(test_container_overflow_tripwire, "Overflow Tripwire & Rollback");
    OMNI_TEST_RUN(test_container_containment_law, "Core Containment Law");
    OMNI_TEST_RUN(test_byte_vessel_envelope, "64-Byte Vessel Envelope");
    OMNI_TEST_RUN(test_container_lifecycle_rolls, "4-Block Lifecycle Rolls");
    return 0;
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/unit/test_number.c

C | 244 LINES | 1146 WORDS | 11.1 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & TEST TOPOLOGY
 * ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { Number } ] )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Validates the scalar invariant type < Number > in isolation:
 *   - Bijective round-trip radix-3 transduction (64 bits <=> 32 balanced trits)
 *   - Dual-rail bit-plane packed representation and O(1) rail-swap negation
 *   - Instant O(1) NULL collision trap detection
 *   - Dynamic packing topologies: 2-2-2-2, 2-1-2-1-2, 1-2-1-2-2, 2-2-1-2-1,
 *     3-3-2, 3-2-3, 2-3-3
 *   - ALU Zero-Sum Equilibrium Law: (+1) plus (-1) <=> 0
 *   - Balanced arithmetic addition, subtraction, and inverse cancellation
 *   - Strict single-word boundary laws
 *   - Full 4-block lifecycle execution (open, execute, close)
 *   - Witness: Scripture Psalm 147:4 KJV
 *     "He telleth the number of the stars; he calleth them all by their names."
 *   - Semantics: { DualRailBitPlanes :: KinematicTopologies :: ALUZeroSum }
 * ============================================================================ */

#include "test_common.h"

/* ============================================================================
 * BLOCK 2: OPENING CONTEXT & FIXTURE SETUP
 * ============================================================================ */

static int test_number_bijective_roundtrip(void) {
    const int64_t test_values[] = {
        0, 1, -1, 2, -2, 4096, -4096, 65536, -65536, 1000000, -1000000
    };
    const size_t num_values = sizeof(test_values) / sizeof(test_values[0]);

    for (size_t i = 0; i < num_values; ++i) {
        int64_t original = test_values[i];
        omni_number_t n = omni_number_from_scalar(original);

        OMNI_TEST_ASSERT(n.is_enclosed == true, "Number must be enclosed");
        OMNI_TEST_ASSERT(n.scalar == original, "Number scalar must match original");

        /* Verify all 32 trits are in {-1, 0, +1} */
        for (size_t t = 0; t < OMNI_NUM_TRITS_PER_WORD; ++t) {
            OMNI_TEST_ASSERT(n.trits[t] >= -1 && n.trits[t] <= 1,
                             "Trit must be in {-1, 0, +1}");
        }

        /* Verify reconstruction from trits */
        int64_t reconstructed = omni_number_to_scalar(n.trits);
        OMNI_TEST_ASSERT(reconstructed == original,
                         "Reconstructed scalar must equal original value");
    }
    return 0;
}

static int test_number_dual_rail_bitplanes(void) {
    /* Test Zero: All trits 00 -> packed is 0 */
    omni_number_t zero = omni_number_from_scalar(0);
    OMNI_TEST_ASSERT(omni_number_trits_is_equilibrium(zero.packed_trits) == true,
                     "Packed zero must be in equilibrium (0ULL)");
    OMNI_TEST_ASSERT(omni_number_trits_has_null(zero.packed_trits) == false,
                     "Packed zero must not have NULL traps");

    /* Test Positive Unity (+1): First trit is 01, others 00 */
    omni_number_t pos_one = omni_number_from_scalar(1);
    OMNI_TEST_ASSERT((pos_one.packed_trits & 0x03) == OMNI_TRIT_PAIR_POS,
                     "First trit of +1 must be 01 (positive rail active)");

    /* Test Negative Unity (-1): First trit is 10, others 00 */
    omni_number_t neg_one = omni_number_from_scalar(-1);
    OMNI_TEST_ASSERT((neg_one.packed_trits & 0x03) == OMNI_TRIT_PAIR_NEG,
                     "First trit of -1 must be 10 (negative rail active)");

    /* Test Instant Bit-Plane Negation (+1 <-> -1) */
    uint64_t negated_pos = omni_number_trits_negate(pos_one.packed_trits);
```

```
    OMNI_TEST_ASSERT((negated_pos & 0x03) == OMNI_TRIT_PAIR_NEG,
                     "Negating +1 packed trits must produce -1 (10)");
    OMNI_TEST_ASSERT(negated_pos == neg_one.packed_trits,
                     "Negated +1 packed word must equal -1 packed word");

    /* Test NULL Trap Detection: artificially inject 11 into trit 0 */
    uint64_t corrupted = pos_one.packed_trits | 0x03;
    OMNI_TEST_ASSERT(omni_number_trits_has_null(corrupted) == true,
                     "Packed word with 11 must be flagged as NULL trap");

    return 0;
}

static int test_number_dynamic_packing_topologies(void) {
    uint8_t out[5];

    /* 1. Test 2-2-2-2 (Dense: 4 fields of 2 bits) */
    uint8_t p_2222 = omni_number_pack_byte(1, 2, 0, 3, 0, OMNI_PACK_2_2_2_2);
    omni_number_unpack_byte(p_2222, out, OMNI_PACK_2_2_2_2);
    OMNI_TEST_ASSERT(out[0] == 1 && out[1] == 2 && out[2] == 0 && out[3] == 3,
                     "2-2-2-2 round-trip unpack must match input");

    /* 2. Test 2-1-2-1-2 (Palindromic Equilibrium: 00/0/00/0/00) */
    uint8_t p_pal = omni_number_pack_byte(3, 1, 2, 0, 1, OMNI_PACK_2_1_2_1_2);
    omni_number_unpack_byte(p_pal, out, OMNI_PACK_2_1_2_1_2);
    OMNI_TEST_ASSERT(out[0] == 3 && out[1] == 1 && out[2] == 2 &&
                     out[3] == 0 && out[4] == 1,
                     "2-1-2-1-2 round-trip unpack must match input");

    /* 3. Test 1-2-1-2-2 (Prefix Carry) */
    uint8_t p_pre = omni_number_pack_byte(1, 3, 0, 2, 1, OMNI_PACK_1_2_1_2_2);
    omni_number_unpack_byte(p_pre, out, OMNI_PACK_1_2_1_2_2);
    OMNI_TEST_ASSERT(out[0] == 1 && out[1] == 3 && out[2] == 0 &&
                     out[3] == 2 && out[4] == 1,
                     "1-2-1-2-2 round-trip unpack must match input");

    /* 4. Test 2-2-1-2-1 (Postfix Carry) */
    uint8_t p_post = omni_number_pack_byte(2, 1, 1, 3, 0, OMNI_PACK_2_2_1_2_1);
    omni_number_unpack_byte(p_post, out, OMNI_PACK_2_2_1_2_1);
    OMNI_TEST_ASSERT(out[0] == 2 && out[1] == 1 && out[2] == 1 &&
                     out[3] == 3 && out[4] == 0,
                     "2-2-1-2-1 round-trip unpack must match input");

    /* 5. Test 3-3-2 (3-Space Directional Partition) */
    uint8_t p_332 = omni_number_pack_byte(7, 5, 2, 0, 0, OMNI_PACK_3_3_2);
    omni_number_unpack_byte(p_332, out, OMNI_PACK_3_3_2);
    OMNI_TEST_ASSERT(out[0] == 7 && out[1] == 5 && out[2] == 2,
                     "3-3-2 round-trip unpack must match input");

    /* 6. Test 3-2-3 (3-Space Directional Partition) */
    uint8_t p_323 = omni_number_pack_byte(6, 3, 5, 0, 0, OMNI_PACK_3_2_3);
    omni_number_unpack_byte(p_323, out, OMNI_PACK_3_2_3);
    OMNI_TEST_ASSERT(out[0] == 6 && out[1] == 3 && out[2] == 5,
                     "3-2-3 round-trip unpack must match input");

    /* 7. Test 2-3-3 (3-Space Directional Partition) */
    uint8_t p_233 = omni_number_pack_byte(3, 7, 4, 0, 0, OMNI_PACK_2_3_3);
    omni_number_unpack_byte(p_233, out, OMNI_PACK_2_3_3);
    OMNI_TEST_ASSERT(out[0] == 3 && out[1] == 7 && out[2] == 4,
                     "2-3-3 round-trip unpack must match input");

    return 0;
}

static int test_number_equilibrium_law(void) {
    /* ALU Equilibrium Law: (+1) plus (-1) <=> 0 */
    bool eq_holds = omni_number_verify_equilibrium();
    OMNI_TEST_ASSERT(eq_holds == true, "Core ALU Zero-Sum Equilibrium Law must hold");
    return 0;
}

static int test_number_addition_and_subtraction(void) {
    omni_number_t a = omni_number_from_scalar(4000);
    omni_number_t b = omni_number_from_scalar(96);
    omni_number_t sum = omni_number_add(a, b);

    OMNI_TEST_ASSERT(sum.scalar == 4096, "4000 + 96 must equal 4096");
    OMNI_TEST_ASSERT(sum.is_enclosed == true, "Sum must be enclosed");
```

```
    /* Test inverse cancellation via subtraction: a - a == 0 */
    omni_number_t zero = omni_number_sub(sum, sum);
    OMNI_TEST_ASSERT(zero.scalar == 0, "4096 - 4096 must equal 0");
    OMNI_TEST_ASSERT(omni_number_trits_is_equilibrium(zero.packed_trits) == true,
                     "Zero difference must be in packed equilibrium");

    /* Test negation: -4096 */
    omni_number_t neg_sum = omni_number_neg(sum);
    OMNI_TEST_ASSERT(neg_sum.scalar == -4096, "Negated 4096 must equal -4096");
    OMNI_TEST_ASSERT(omni_number_add(sum, neg_sum).scalar == 0,
                     "Summing with negated counterpart must yield 0");

    return 0;
}

static int test_number_bounds_and_enclosure(void) {
    omni_number_t valid_num = omni_number_from_scalar(100);
    OMNI_TEST_ASSERT(omni_number_verify_bounds(&valid_num) == true,
                     "Valid number must pass bounds check");

    omni_number_t corrupted = valid_num;
    corrupted.is_enclosed = false;
    OMNI_TEST_ASSERT(omni_number_verify_bounds(&corrupted) == false,
                     "Unenclosed number must fail bounds check");

    /* Test null trap tripping */
    omni_number_t trap_num = valid_num;
    trap_num.packed_trits |= 0x03; /* Inject 11 */
    OMNI_TEST_ASSERT(omni_number_verify_bounds(&trap_num) == false,
                     "Number with NULL collision trap must fail bounds check");

    return 0;
}

static int test_number_lifecycle_rolls(void) {
    omni_number_context_t ctx;
    omni_number_open(&ctx, 4096, OMNI_TARGET_ACCUMULATOR);

    OMNI_TEST_ASSERT(ctx.tripwire == OMNI_TRIPWIRE_ARMED,
                     "Tripwire must be ARMED upon open");
    OMNI_TEST_ASSERT(ctx.input_quantity == 4096,
                     "Input quantity must match 4096");

    /* Verify individual operational rolls */
    omni_number_inscribe(&ctx, 4096);
    OMNI_TEST_ASSERT(ctx.number.scalar == 4096, "Roll 1 Inscribe must set scalar");

    omni_number_transduce_context(&ctx);
    OMNI_TEST_ASSERT(!omni_number_trits_has_null(ctx.number.packed_trits),
                     "Roll 2 Transduce must produce trap-free trits");

    OMNI_TEST_ASSERT(omni_number_guard(&ctx) == OMNI_STATE_PROCEED,
                     "Roll 3 Guard assertion must PROCEED");

    OMNI_TEST_ASSERT(omni_number_calculate(&ctx) == OMNI_STATE_PROCEED,
                     "Roll 4 Calculate zero-sum balance must PROCEED");

    OMNI_TEST_ASSERT(omni_number_sequence(&ctx.number, NULL) == true,
                     "Roll 5 Sequence transition must succeed");

    /* Unified lifecycle execution */
    omni_quad_state_t exec_status = omni_number_execute(&ctx);
    OMNI_TEST_ASSERT(exec_status == OMNI_STATE_PROCEED,
                     "Number execute must PROCEED (+1)");
    OMNI_TEST_ASSERT(ctx.number.is_enclosed == true,
                     "Number must be enclosed after execute");

    omni_quad_state_t close_status = omni_number_close(&ctx);
    OMNI_TEST_ASSERT(close_status == OMNI_STATE_PROCEED,
                     "Number close must PROCEED (+1)");
    OMNI_TEST_ASSERT(ctx.tripwire == OMNI_TRIPWIRE_DISARMED,
                     "Tripwire must be DISARMED upon clean close");

    return 0;
}

/* ============================================================================
```

```
 * BLOCK 3: BODY PRIMITIVES & TEST SUITE RUNNER
 * ========================================================================== */

int test_number_suite(void) {
    printf("[SUITE: Number Invariant Type]\n");
    OMNI_TEST_RUN(test_number_bijective_roundtrip, "Bijective Radix-3 Transduction");
    OMNI_TEST_RUN(test_number_dual_rail_bitplanes, "Dual-Rail Bit-Planes & Negation");
    OMNI_TEST_RUN(test_number_dynamic_packing_topologies, "Dynamic Packing Topologies");
    OMNI_TEST_RUN(test_number_equilibrium_law, "ALU Zero-Sum Equilibrium Law");
    OMNI_TEST_RUN(test_number_addition_and_subtraction, "Balanced Addition & Subtraction");
    OMNI_TEST_RUN(test_number_bounds_and_enclosure, "Single-Word Enclosure Bounds");
    OMNI_TEST_RUN(test_number_lifecycle_rolls, "4-Block Lifecycle Rolls");
    return 0;
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/unit/test_site.c

C | 120 LINES | 556 WORDS | 5.5 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & TEST TOPOLOGY
 * ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { Site } ] )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Validates the physical silicon address type < Site > in isolation:
 *   - Null pointer address rejection and safety tripwire
 *   - Hardware Routing Law (MMIO ports vs RAM spaces)
 *   - Relative displacement and pointer offset arithmetic
 *   - Volatile memory semantics for bare-metal registers
 *   - Full 4-block lifecycle execution (open, execute, close)
 *   - Witness: Scripture Genesis 28:16 KJV
 *     "And Jacob awaked out of his sleep, and he said, Surely the Lord is in
 *      this place; and I knew it not."
 *   - Semantics: { SiliconCoordinates :: HardwareRoutingLaw :: NonNullInterlock }
 * ============================================================================ */

#include "test_common.h"

/* ============================================================================
 * BLOCK 2: OPENING CONTEXT & FIXTURE SETUP
 * ============================================================================ */

static int test_site_routing_classification(void) {
    /* VGA buffer coordinate (0xB8000) must route to MMIO */
    omni_site_t vga_site = omni_site_from_address(OMNI_SITE_VGA_BUFFER);
    OMNI_TEST_ASSERT(vga_site.routing == OMNI_ROUTING_HARDWARE_MMIO, "VGA buffer must classify as HARDWARE_MMIO");
    OMNI_TEST_ASSERT(omni_site_is_valid(&vga_site) == true, "VGA site must be valid");

    /* COM1 serial port (0x3F8) must route to MMIO */
    omni_site_t com1_site = omni_site_from_address(OMNI_SITE_COM1);
    OMNI_TEST_ASSERT(com1_site.routing == OMNI_ROUTING_HARDWARE_MMIO, "COM1 port must classify as HARDWARE_MMIO");

    /* Standard MBR memory location (0x7C00) must route to RAM */
    omni_site_t mbr_site = omni_site_from_address(OMNI_SITE_MBR_BOOT);
    OMNI_TEST_ASSERT(mbr_site.routing == OMNI_ROUTING_RAM_PHYSICAL, "MBR origin must classify as RAM_PHYSICAL");

    return 0;
}

static int test_site_null_tripwire(void) {
    /* Null address (0x0) must be invalid */
    omni_site_t null_site = omni_site_from_address(OMNI_SITE_NULL);
    OMNI_TEST_ASSERT(omni_site_is_valid(&null_site) == false, "Null site must be invalid");

    /* Executing lifecycle with NULL coordinate must trip the interlock and ROLLBACK */
    omni_site_context_t ctx;
    omni_site_open(&ctx, 0);
    ctx.input_coordinate = 0; /* Force null */
    omni_quad_state_t exec_st = omni_site_execute(&ctx);
    OMNI_TEST_ASSERT(exec_st == OMNI_STATE_ROLLBACK, "Null address execute must trigger ROLLBACK (-1)");
    OMNI_TEST_ASSERT(ctx.tripwire == OMNI_TRIPWIRE_TRIPPED, "Tripwire must be TRIPPED on null address");

    return 0;
}

static int test_site_offset_and_relational(void) {
    uint8_t dummy_buffer[16];
    uintptr_t base_addr = (uintptr_t)&dummy_buffer[0];

    omni_site_t base_site = omni_site_from_address(base_addr);
    omni_site_t offset_site = omni_site_offset(&base_site, 8);

    OMNI_TEST_ASSERT(offset_site.coordinate == base_addr + 8, "Displaced site coordinate must be base + 8");
    OMNI_TEST_ASSERT(omni_site_eq(&base_site, &base_site) == true, "Identical sites must evaluate equal");
    OMNI_TEST_ASSERT(omni_site_eq(&base_site, &offset_site) == false, "Different sites must evaluate not equal");

    return 0;
}

static int test_site_volatile_read_write(void) {
    uint8_t buffer[4] = {0, 0, 0, 0};
    uintptr_t addr = (uintptr_t)&buffer[0];
```

```
    omni_site_t site = omni_site_from_address(addr);

    /* Write via volatile primitives */
    omni_site_write_u8(&site, 0, 0xAB);
    omni_site_write_u8(&site, 1, 0xCD);

    /* Read back via volatile primitives */
    uint8_t r0 = omni_site_read_u8(&site, 0);
    uint8_t r1 = omni_site_read_u8(&site, 1);

    OMNI_TEST_ASSERT(r0 == 0xAB, "Volatile read at offset 0 must match written 0xAB");
    OMNI_TEST_ASSERT(r1 == 0xCD, "Volatile read at offset 1 must match written 0xCD");

    return 0;
}

static int test_site_lifecycle_rolls(void) {
    omni_site_context_t ctx;
    omni_site_open(&ctx, OMNI_SITE_VGA_BUFFER);

    OMNI_TEST_ASSERT(ctx.tripwire == OMNI_TRIPWIRE_ARMED, "Tripwire must be ARMED upon open");

    omni_quad_state_t exec_status = omni_site_execute(&ctx);
    OMNI_TEST_ASSERT(exec_status == OMNI_STATE_PROCEED, "Site execute must PROCEED (+1)");
    OMNI_TEST_ASSERT(ctx.site.routing == OMNI_ROUTING_HARDWARE_MMIO, "VGA site routing must be HARDWARE_MMIO");

    omni_quad_state_t close_status = omni_site_close(&ctx);
    OMNI_TEST_ASSERT(close_status == OMNI_STATE_PROCEED, "Site close must PROCEED (+1)");
    OMNI_TEST_ASSERT(ctx.tripwire == OMNI_TRIPWIRE_DISARMED, "Tripwire must be DISARMED upon clean close");

    return 0;
}

/* ============================================================================
 * BLOCK 3: BODY PRIMITIVES & TEST SUITE RUNNER
 * ============================================================================ */

int test_site_suite(void) {
    printf("[SUITE: Site Invariant Type]\n");
    OMNI_TEST_RUN(test_site_routing_classification, "Hardware Routing Law (MMIO vs RAM)");
    OMNI_TEST_RUN(test_site_null_tripwire, "Null Pointer Rejection & Tripwire Interlock");
    OMNI_TEST_RUN(test_site_offset_and_relational, "Offset Arithmetic & Relational Equality");
    OMNI_TEST_RUN(test_site_volatile_read_write, "Volatile Memory Read / Write Semantics");
    OMNI_TEST_RUN(test_site_lifecycle_rolls, "4-Block Lifecycle Rolls");
    return 0;
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/transpile variant/tests/c/unit/test_state.c

C | 119 LINES | 606 WORDS | 5.6 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & TEST TOPOLOGY
 * ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { State } ] )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Validates the causal truth governor invariant type < State > in isolation:
 *   - Quad-State named registers: [ STATE TURN BOUND IT ]
 *   - Canonical Loop Law cadence and single-step detent transitions:
 *       WHEN IT < BOUND  --> PROCEED (+1)
 *       !    IT > BOUND  --> AWAIT (0)
 *       ::   IT == BOUND --> HALT (NULL)
 *   - State predicates and register reset mechanics
 *   - Full 4-block lifecycle execution (open, execute, close)
 *   - Witness: Scripture Ecclesiastes 3:1 KJV
 *     "To every thing there is a season, and a time to every purpose under
 *      the heaven:"
 *   - Semantics: { QuadStateTruth :: CanonicalLoopCadence :: CausalDetents }
 * ============================================================================ */

#include "test_common.h"

/* ============================================================================
 * BLOCK 2: OPENING CONTEXT & FIXTURE SETUP
 * ============================================================================ */

static int test_state_canonical_loop(void) {
    omni_state_t s = omni_state_create(OMNI_STATE_PROCEED, 3);

    OMNI_TEST_ASSERT(s.registers.bound == 3, "Loop bound must be 3");
    OMNI_TEST_ASSERT(s.registers.it == 0, "Initial IT must be 0");
    OMNI_TEST_ASSERT(s.registers.turn == 0, "Initial TURN must be 0");
    OMNI_TEST_ASSERT(omni_state_is_proceeding(&s) == true, "Initial state must be PROCEED");

    /* Step 1: IT 0 < 3 -> increments to IT=1, TURN=1, returns PROCEED */
    omni_quad_state_t st1 = omni_state_step_loop(&s.registers);
    OMNI_TEST_ASSERT(st1 == OMNI_STATE_PROCEED, "Step 1 must PROCEED");
    OMNI_TEST_ASSERT(s.registers.it == 1 && s.registers.turn == 1, "IT and TURN must be 1");

    /* Step 2: IT 1 < 3 -> increments to IT=2, TURN=2, returns PROCEED */
    omni_quad_state_t st2 = omni_state_step_loop(&s.registers);
    OMNI_TEST_ASSERT(st2 == OMNI_STATE_PROCEED, "Step 2 must PROCEED");
    OMNI_TEST_ASSERT(s.registers.it == 2 && s.registers.turn == 2, "IT and TURN must be 2");

    /* Step 3: IT 2 < 3 -> increments to IT=3, TURN=3, returns PROCEED */
    omni_quad_state_t st3 = omni_state_step_loop(&s.registers);
    OMNI_TEST_ASSERT(st3 == OMNI_STATE_PROCEED, "Step 3 must PROCEED");
    OMNI_TEST_ASSERT(s.registers.it == 3 && s.registers.turn == 3, "IT and TURN must be 3");

    /* Step 4: IT == BOUND (3 == 3) -> Reaches terminal detent HALT:NULL */
    omni_quad_state_t st4 = omni_state_step_loop(&s.registers);
    OMNI_TEST_ASSERT(st4 == OMNI_STATE_HALT, "Step 4 (IT == BOUND) must reach HALT:NULL detent");
    OMNI_TEST_ASSERT(omni_state_is_halted(&s) == true, "State must report halted");

    return 0;
}

static int test_state_await_transition(void) {
    omni_state_t s = omni_state_create(OMNI_STATE_PROCEED, 4);

    /* Manually position IT > BOUND to simulate overrun awaiting input */
    s.registers.it = 5;
    omni_quad_state_t await_st = omni_state_step_loop(&s.registers);
    OMNI_TEST_ASSERT(await_st == OMNI_STATE_AWAIT, "IT > BOUND must transition to AWAIT (0)");
    OMNI_TEST_ASSERT(omni_state_is_awaiting(&s) == true, "State engine must report awaiting");

    return 0;
}

static int test_state_predicates_and_reset(void) {
    omni_state_t s = omni_state_create(OMNI_STATE_PROCEED, 2);

    /* Step until halt */
    omni_state_step_loop(&s.registers);
```

```
    omni_state_step_loop(&s.registers);
    omni_state_step_loop(&s.registers);
    OMNI_TEST_ASSERT(omni_state_is_halted(&s) == true, "Engine must be halted");

    /* Reset engine */
    omni_state_reset(&s, 5);
    OMNI_TEST_ASSERT(s.registers.bound == 5, "New bound must be 5");
    OMNI_TEST_ASSERT(s.registers.it == 0, "IT must reset to 0");
    OMNI_TEST_ASSERT(s.registers.turn == 0, "TURN must reset to 0");
    OMNI_TEST_ASSERT(omni_state_is_proceeding(&s) == true, "Reset must restore PROCEED status");

    return 0;
}

static int test_state_lifecycle_rolls(void) {
    omni_state_context_t ctx;
    omni_state_open(&ctx, OMNI_STATE_PROCEED, 4);

    OMNI_TEST_ASSERT(ctx.tripwire == OMNI_TRIPWIRE_ARMED, "Tripwire must be ARMED upon open");

    /* Execute full governance cadence */
    omni_quad_state_t exec_status = omni_state_execute(&ctx);
    OMNI_TEST_ASSERT(exec_status == OMNI_STATE_PROCEED, "State execute must PROCEED (+1)");
    OMNI_TEST_ASSERT(ctx.state_engine.registers.it == 4, "Final IT must equal bound 4");
    OMNI_TEST_ASSERT(ctx.state_engine.registers.state == OMNI_STATE_HALT, "Registers must reach HALT:NULL detent");

    omni_quad_state_t close_status = omni_state_close(&ctx);
    OMNI_TEST_ASSERT(close_status == OMNI_STATE_PROCEED, "State close must PROCEED (+1)");
    OMNI_TEST_ASSERT(ctx.tripwire == OMNI_TRIPWIRE_DISARMED, "Tripwire must be DISARMED upon clean close");

    return 0;
}

/* ============================================================================
 * BLOCK 3: BODY PRIMITIVES & TEST SUITE RUNNER
 * ============================================================================ */

int test_state_suite(void) {
    printf("[SUITE: State Invariant Type]\n");
    OMNI_TEST_RUN(test_state_canonical_loop, "Canonical Loop Law Cadence (IT < BOUND -> HALT)");
    OMNI_TEST_RUN(test_state_await_transition, "Standby Transition (IT > BOUND -> AWAIT)");
    OMNI_TEST_RUN(test_state_predicates_and_reset, "Predicate Queries & Engine Reset");
    OMNI_TEST_RUN(test_state_lifecycle_rolls, "4-Block Lifecycle Rolls");
    return 0;
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/README.md

MD | 149 LINES | 953 WORDS | 6.4 KB

```
# OmniCode Universal Substrate: The Bedrock of Balance

Welcome to the **Universal Foundation** of OmniCode!

The `universal/` folder is the bedrock upon which all OmniCode types, nouns, verbs, and tracks are built. It defines the physics, mathematics, and causal logic of the OmniCode universe.

---

## 1. The Core Philosophy: Balanced Ternary & Equilibrium

Most computer systems today are built on **binary logic** (`0` and `1`). Binary is inherently one-sided: it forces the world into rigid opposites (on/off, true/false, presence/absence). Representing negative numbers or undoing mistakes in binary requires awkward tricks (such as "two's complement" arithmetic).

OmniCode is founded on **Balanced Ternary**:
> *"A false balance is abomination to the LORD: but a just weight is his delight."*
> — **Proverbs 11:1 KJV**

In balanced ternary, every basic digit (called a **trit**) can take one of three natural states centered symmetrically around zero:

- **`+1` (Positive / Surplus):** Forward motion, affirmative creation, advance.
- **`0` (Equilibrium / Rest):** Perfect balance, standstill, awaiting input.
- **`-1` (Negative / Deficit):** Backward pull, restoration, unwinding an error.

Because balanced ternary is completely symmetrical around zero, **negation is free**, subtraction is simply adding the opposite, and balance is built directly into the fabric of computation!

---

## 2. Quad-State Causal Truth: How Time & Logic Flow

OmniCode replaces simple Boolean true/false with **Quad-State Causal Truth**. Instead of just asking *"Is this true or false?"*, OmniCode asks: *"In which direction should computation flow?"*

| State | Trit Value | Meaning | Real-World Analogy |
| :--- | :---: | :--- | :--- |
| **`PROCEED`** | `+1` | Forward Causation | The green light. Everything is sound; advance the step. |
| **`AWAIT`** | `0` | Equilibrium Standby | The amber pause. The system is balanced, waiting for input or a timer. |
| **`ROLLBACK`** | `-1` | Retroactive Reversal | The rewind button. A safety guard was tripped; restore the last safe snapshot. |
| **`HALT`** | `NULL` (`-2`) | Terminal Detent | The emergency brake. Stop the processor clock immediately. |

---

## 3. Connective Operators as Natural Human Conjunctions

In natural human speech, we don't just say `AND` or `OR`. We express nuanced relationships with words like *"and"*, *"but"*, *"or"*, and *"in relation to"*.

OmniCode translates these intuitive conjunctions into exact mathematical logic gates:

### `::` (AND / Cumulative Conjunction)

- **Human Meaning:** *"Do this AND do that simultaneously."*
- **Behavior:** Both sides must succeed (`PROCEED`). If either is waiting, the result waits (`AWAIT`). If either fails, the whole conjunction rolls back (`ROLLBACK`).

### `!` (BUT / Adversative Caveat)

- **Human Meaning:** *"Execute this action, BUT only if this safety condition holds."*
- **Behavior:** The action advances, *unless* the caveat fails or halts, in which case the action is immediately blocked and rolled back.

### `|` (OR / Disjunctive Valve)

- **Human Meaning:** *"Take path A OR take path B."*
- **Behavior:** If either path can proceed, computation advances. If both are blocked, it rolls back.

### `--` (NOT / Polarity Inversion)

- **Human Meaning:** *"Flip the truth value around the center."*
```

- **Behavior:** Turns `PROCEED (+1)` into `ROLLBACK (-1)` and vice versa, leaving resting `AWAIT (0)` undisturbed.

`!=` (Inequality / "Not to Be")

- **Human Meaning:** *"Verify that these two states or values are different."*

`=!` (Is Not / "To Be Not")

- **Human Meaning:** *"Confirm that current state is NOT a specific forbidden condition."*

`=~` (Liken To / Resemblance)

- **Human Meaning:** *"See if these two ideas are compatible or like one another."*

`:` (In Relation To / Perspective)

- **Human Meaning:** *"View this action through the lens of this context."*

---

4. The Dual-Rail Silicon Secret

How can modern computers (which only have binary wires) run OmniCode's balanced ternary logic at native speeds?

OmniCode uses **Dual-Rail Polar Bit-Planes**:

- Every balanced trit is physically represented using a pair of bits: `(Negative Rail, Positive Rail)`.
  - `00`: **Equilibrium (0)** — Neither wire active.
  - `01`: **Positive (+1)** — Positive rail active.
  - `10`: **Negative (-1)** — Negative rail active.
  - `11`: **Collision / Trap (NULL)** — Both wires active simultaneously, which is an illegal hardware fault!

Instantaneous Negation (Rail Swapping)

To negate a 64-bit word of 32 trits in conventional math, a computer has to perform multiple arithmetic operations with borrowing.
In OmniCode, **negation is just swapping the positive and negative bit-planes**! The CPU does this in just two hardware clock cycles, achieving instant SIMD (Single Instruction, Multiple Data) negation.

---

5. Directory Contents & Architecture

```bash
universal/
├── README.md               # This foundational guide
└── transpiled/
    ├── compiled/c/         # Freestanding C99/C11 Hardware Backbone
    │   ├── Makefile        # Pure POSIX build script
    │   ├── compile_flags.txt
    │   ├── include/
    │   │   ├── omni_base.h # Invariant axioms, ALU arithmetic, connectives
    │   │   └── omni.h      # Master umbrella header for all types
    │   └── tests/
    │       ├── test_common.h   # Minimal freestanding assertion macros
    │       └── test_universal.c# Unit testbed verifying universal laws in isolation
    └── interpreted/lua/    # Dynamic Coroutine Process Ribbon
        ├── tape_engine.lua # Coroutine fiber runner, snapshots, connectives
        └── tests/
            ├── test_common.lua     # Assertion suite for Lua
            └── test_tape_engine.lua# Unit testbed verifying tape engine in isolation
```

---

6. Running Universal Tests

We always test the universal foundation **before** testing any individual type:

```bash
# 1. Test the C Bare-Metal Bedrock
cd transpiled/compiled/c
make test

# 2. Test the Lua Coroutine Tape Engine
cd ../../interpreted/lua
lua tests/test_tape_engine.lua
```

```
Both test suites verify:

- Hardware preconditions and platform word sizes
- Balanced ternary arithmetic and carry propagation
- Dual-rail encoding, decoding, and collision traps
- The complete suite of connectives (`!`, `::`, `|`, `--`, `!=`, `=!`, `=~`, `:`)
- State vs. literal disambiguation
- Tripwire arming, tripping, and transactional rollback
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/interpreted/lua/tape_engine.lua

LUA | 368 LINES | 1404 WORDS | 12.5 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & ENGINE TOPOLOGY
-- ( Engine Core: < Lexicon { Types of Ideas } > & [ Process { Tape Engine } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   The interpreted execution ribbon companion to the OmniCode C Backbone.
--   Drives dynamic temporal causation, coroutines, and roll kinematics:
--   - Coroutine-based fiber stepping (yielding on AWAIT, resuming on tick)
--   - Pre-roll and post-roll dynamic event hooks
--   - State snapshotting and active rollback unwinding
--   - Structured handles over C memory layouts and invariants
--   - Witness: Scripture Proverbs 16:9 KJV
--     "A man's heart deviseth his way: but the LORD directeth his steps."
--   - Semantics: { TapeKinematics :: CoroutineFiber :: QuadStateDetents }
-- ================================================================================

local TapeEngine = {
    -- Quad-State Truth Constants
    STATE_ROLLBACK = -1,     -- -1 : Retroactive Reversal / Error Unwind
    STATE_AWAIT    =  0,     --  0 : Equilibrium Standby / Hold Pending
    STATE_PROCEED  =  1,     -- +1 : Forward Causation / Affirmative Advance
    STATE_HALT     = "NULL", -- NULL : Terminal Detent / Stop Processor Clock

    -- Tripwire Interlock States
    TRIPWIRE_DISARMED = 0,
    TRIPWIRE_ARMED    = 1,
    TRIPWIRE_TRIPPED  = 2,

    -- Dual-Rail 2-Bit Trit Constants
    TRIT_PAIR_ZERO    = 0, -- 0b00: Equilibrium (0)
    TRIT_PAIR_POS     = 1, -- 0b01: Positive (+1)
    TRIT_PAIR_NEG     = 2, -- 0b10: Negative (-1)
    TRIT_PAIR_NULL    = 3, -- 0b11: Collision / NULL trap

    -- Dual-Rail Bitplane 64-Bit Masks
    BITPLANE_POS_MASK = 0x5555555555555555,
    BITPLANE_NEG_MASK = ~0x5555555555555555
}

-- Detect optional LuaJIT FFI for direct zero-copy C backbone linkage
local has_ffi, ffi = pcall(require, "ffi")
TapeEngine.has_ffi = has_ffi
TapeEngine.ffi = has_ffi and ffi or nil

---
-- Encodes a discrete balanced trit (-1, 0, 1) to a 2-bit pair.
function TapeEngine.trit_to_pair(trit)
    if trit == 0 then return TapeEngine.TRIT_PAIR_ZERO
    elseif trit == 1 then return TapeEngine.TRIT_PAIR_POS
    elseif trit == -1 then return TapeEngine.TRIT_PAIR_NEG
    else return TapeEngine.TRIT_PAIR_NULL end
end

---
-- Decodes a 2-bit pair into a discrete balanced trit.
-- Returns trit, ok_boolean (false on 0b11 collision).
function TapeEngine.pair_to_trit(code)
    local c = (code or 0) & 0x03
    if c == TapeEngine.TRIT_PAIR_ZERO then return 0, true
    elseif c == TapeEngine.TRIT_PAIR_POS then return 1, true
    elseif c == TapeEngine.TRIT_PAIR_NEG then return -1, true
    else return 0, false end
end

---
-- SIMD rail-swap negation of 64-bit packed dual-rail word.
function TapeEngine.negate_dual_rail(packed)
    local pos = packed & TapeEngine.BITPLANE_POS_MASK
    local neg = packed & TapeEngine.BITPLANE_NEG_MASK
    return ((pos << 1) & TapeEngine.BITPLANE_NEG_MASK) |
           ((neg >> 1) & TapeEngine.BITPLANE_POS_MASK)
end

```

```
---
-- Detects whether any trit position has both rails active (NULL trap).
function TapeEngine.has_null_collision(packed)
    local pos = packed & TapeEngine.BITPLANE_POS_MASK
    local neg = (packed >> 1) & TapeEngine.BITPLANE_POS_MASK
    return (pos & neg) ~= 0
end

-- ============================================================================
-- BLOCK 2: OPENING BLOCK
-- ( Subsystem Initialization, Preconditions & Tape Mounting )
-- ============================================================================

---
-- Deep copy snapshot utility for transactional rollback safety.
-- @param ctx The context table to clone.
-- @return Independent deep copy of the context.
local function make_snapshot(ctx)
    local snap = {}
    for k, v in pairs(ctx) do
        if type(v) == "table" then
            snap[k] = make_snapshot(v)
        else
            snap[k] = v
        end
    end
    return snap
end

---
-- Creates and mounts an interpreted Tape Process Ribbon.
-- @param spec Table containing metadata, constants, and declared rolls.
-- @return Mounted tape object.
function TapeEngine.create_tape(spec)
    local tape = {
        metadata    = spec.metadata or {},
        constants   = spec.constants or {},
        rolls       = spec.rolls or {},
        hooks       = {
            before_roll = {},
            after_roll  = {},
            on_rollback = {}
        },
        snapshots   = {},
        history     = {}
    }

    ---
    -- Registers a dynamic hook invoked immediately before a roll executes.
    function tape:before(fn)
        table.insert(self.hooks.before_roll, fn)
        return self
    end

    ---
    -- Registers a dynamic hook invoked immediately after a roll executes.
    function tape:after(fn)
        table.insert(self.hooks.after_roll, fn)
        return self
    end

    ---
    -- Registers a rollback handler invoked when a guard or roll fails.
    function tape:on_rollback(fn)
        table.insert(self.hooks.on_rollback, fn)
        return self
    end

    ---
    -- Spawns a coroutine fiber driving step-by-step execution.
    function tape:spawn_coroutine(ctx)
        return coroutine.create(function()
            for idx, roll in ipairs(self.rolls) do
                table.insert(self.snapshots, make_snapshot(ctx))

                for _, h in ipairs(self.hooks.before_roll) do
                    h(idx, roll.name, ctx)
                end
```

```
                local status = roll.action(ctx)
                ctx.status = status

                for _, h in ipairs(self.hooks.after_roll) do
                    h(idx, roll.name, ctx, status)
                end

                table.insert(self.history, {
                    roll_index = idx,
                    name       = roll.name,
                    status     = status
                })

                if status == TapeEngine.STATE_ROLLBACK then
                    for _, h in ipairs(self.hooks.on_rollback) do
                        h(idx, roll.name, ctx)
                    end
                    if #self.snapshots > 0 then
                        local last_good = table.remove(self.snapshots)
                        for k, v in pairs(last_good) do
                            ctx[k] = v
                        end
                    end
                    coroutine.yield(TapeEngine.STATE_ROLLBACK, idx, roll.name)
                    return TapeEngine.STATE_ROLLBACK
                elseif status == TapeEngine.STATE_AWAIT then
                    coroutine.yield("AWAIT", idx, roll.name, ctx)
                elseif status == TapeEngine.STATE_HALT then
                    coroutine.yield(TapeEngine.STATE_HALT, idx, roll.name)
                    return TapeEngine.STATE_HALT
                end
            end

            return TapeEngine.STATE_PROCEED, "Tape sealed in PROCEED (+1)"
        end)
    end

    ---
    -- Executes all rolls in a synchronous loop, automatically resuming AWAITs.
    function tape:execute_all(ctx)
        local co = self:spawn_coroutine(ctx)
        while coroutine.status(co) ~= "dead" do
            local ok, event, roll_idx = coroutine.resume(co)
            if not ok then
                error("Tape execution fatal error: " .. tostring(event))
            end
            if event == "AWAIT" then
                ctx.status = TapeEngine.STATE_PROCEED
            elseif event == TapeEngine.STATE_PROCEED
                or event == TapeEngine.STATE_HALT
                or event == TapeEngine.STATE_ROLLBACK then
                return event, roll_idx
            end
        end
        return ctx.status
    end

    return tape
end

-- ============================================================================
-- BLOCK 3: BODY BLOCK
-- ( Connectives & Evaluators )
-- ============================================================================

---
-- Evaluates adversative caveat gate: A ! B (A executes, BUT B must hold).
function TapeEngine.op_but(action, caveat)
    if caveat == TapeEngine.STATE_ROLLBACK then
        return TapeEngine.STATE_ROLLBACK
    end
    if caveat == TapeEngine.STATE_HALT then
        return TapeEngine.STATE_HALT
    end
    return action
end

```

```
---
-- Evaluates cumulative conjunction: A :: B (A AND B simultaneous).
function TapeEngine.op_and(a, b)
    if a == TapeEngine.STATE_HALT or b == TapeEngine.STATE_HALT then
        return TapeEngine.STATE_HALT
    end
    if a == TapeEngine.STATE_ROLLBACK or b == TapeEngine.STATE_ROLLBACK then
        return TapeEngine.STATE_ROLLBACK
    end
    if a == TapeEngine.STATE_AWAIT or b == TapeEngine.STATE_AWAIT then
        return TapeEngine.STATE_AWAIT
    end
    return TapeEngine.STATE_PROCEED
end

---
-- Evaluates disjunctive alternative valve: A | B (A OR B).
function TapeEngine.op_or(a, b)
    if a == TapeEngine.STATE_PROCEED or b == TapeEngine.STATE_PROCEED then
        return TapeEngine.STATE_PROCEED
    end
    if a == TapeEngine.STATE_AWAIT or b == TapeEngine.STATE_AWAIT then
        return TapeEngine.STATE_AWAIT
    end
    if a == TapeEngine.STATE_ROLLBACK and b == TapeEngine.STATE_ROLLBACK then
        return TapeEngine.STATE_ROLLBACK
    end
    return TapeEngine.STATE_HALT
end

---
-- Evaluates balanced ternary truth inversion: -- A (NOT A).
function TapeEngine.op_not(a)
    if a == TapeEngine.STATE_PROCEED then
        return TapeEngine.STATE_ROLLBACK
    end
    if a == TapeEngine.STATE_ROLLBACK then
        return TapeEngine.STATE_PROCEED
    end
    return a
end

---
-- Evaluates inequality verification: A != B (A not to be B).
function TapeEngine.op_neq(a, b)
    if a == TapeEngine.STATE_HALT or b == TapeEngine.STATE_HALT then
        return TapeEngine.STATE_HALT
    end
    return (a ~= b) and TapeEngine.STATE_PROCEED or TapeEngine.STATE_ROLLBACK
end

---
-- Evaluates predicate is-not check: A =! B (State A is not target B).
function TapeEngine.op_is_not(a, target)
    return (a ~= target) and TapeEngine.STATE_PROCEED
                         or TapeEngine.STATE_ROLLBACK
end

---
-- Evaluates liken to / compatibility match: A =~ B.
function TapeEngine.op_liken(a, b)
    if a == TapeEngine.STATE_HALT or b == TapeEngine.STATE_HALT then
        return TapeEngine.STATE_HALT
    end
    if a == b then return TapeEngine.STATE_PROCEED end
    if (a == TapeEngine.STATE_PROCEED or a == TapeEngine.STATE_AWAIT) and
       (b == TapeEngine.STATE_PROCEED or b == TapeEngine.STATE_AWAIT) then
        return TapeEngine.STATE_PROCEED
    end
    return TapeEngine.STATE_ROLLBACK
end

---
-- Evaluates relation projection valve: Context : Aspect.
function TapeEngine.op_relate(ctx, asp)
    if ctx == TapeEngine.STATE_HALT then return TapeEngine.STATE_HALT end
    if ctx == TapeEngine.STATE_ROLLBACK then
        return TapeEngine.STATE_ROLLBACK
```

```
    end
    return asp
end

---
-- Determines if a value represents an OmniCode causal state.
function TapeEngine.is_state(val)
    return val == TapeEngine.STATE_PROCEED or
           val == TapeEngine.STATE_AWAIT   or
           val == TapeEngine.STATE_ROLLBACK or
           val == TapeEngine.STATE_HALT
end

---
-- Disambiguates an intended literal from a quad-state detent.
-- Handles air-quoted "0" or cast { 0 } / [ 0 ] / < 0 > table envelopes.
-- Returns (numeric_value, is_literal_bool).
function TapeEngine.resolve_literal(val)
    if type(val) == "string" and (val == "0" or val == "1" or val == "-1") then
        return tonumber(val), true
    elseif type(val) == "table" and val.is_literal then
        return val.value, true
    elseif type(val) == "table" and val[1] ~= nil and #val == 1 then
        return val[1], true
    elseif type(val) == "number" then
        return val, false
    else
        return val, false
    end
end

-- ============================================================================
-- BLOCK 4: CLOSING BLOCK
-- ( Integrity Seals & Commit Verification )
-- ============================================================================

---
-- Evaluates an invariant guard condition inside a roll action.
function TapeEngine.assert_guard(condition, ctx, error_reason)
    if condition then
        return TapeEngine.STATE_PROCEED
    else
        ctx.tripwire = TapeEngine.TRIPWIRE_TRIPPED
        ctx.error_reason = error_reason or "Invariant guard violation"
        return TapeEngine.STATE_ROLLBACK
    end
end

---
-- Verifies the final integrity of a context before closing commit.
function TapeEngine.verify_and_commit(ctx)
    if ctx.tripwire == TapeEngine.TRIPWIRE_TRIPPED
        or ctx.status == TapeEngine.STATE_ROLLBACK then
        return TapeEngine.STATE_ROLLBACK, "Commit rejected: tripwire tripped"
    end
    ctx.tripwire = TapeEngine.TRIPWIRE_DISARMED
    return TapeEngine.STATE_PROCEED, "Context sealed in PROCEED (+1)"
end

return TapeEngine
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/interpreted/lua/tests/test_common.lua

LUA | 51 LINES | 185 WORDS | 1.7 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & TEST HARNESS TOPOLOGY
-- ( Test Framework: < OmniCode Standard Library Universal Lua Testbed > )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Universal test harness for OmniCode Standard Library Lua Process Ribbons.
--   Provides structured assertions, test suite runner helpers, and tripwires.
--   - Witness: Scripture Proverbs 24:27 KJV
--     "Prepare thy work without, and make it fit for thyself in the field;
--      and afterwards build thine house."
--   - Semantics: { AssertionInterlock :: GranularFaultIsolation }
-- ================================================================================

local TestCommon = {
    failures = 0,
    tests_run = 0
}

function TestCommon.assert(condition, msg)
    TestCommon.tests_run = TestCommon.tests_run + 1
    if not condition then
        TestCommon.failures = TestCommon.failures + 1
        error("    [FAIL] Assertion failed: " .. tostring(msg), 2)
    end
end

function TestCommon.assert_eq(actual, expected, msg)
    TestCommon.tests_run = TestCommon.tests_run + 1
    if actual ~= expected then
        TestCommon.failures = TestCommon.failures + 1
        error(string.format("    [FAIL] %s: Expected [%s], got [%s]",
                            tostring(msg), tostring(expected),
                            tostring(actual)), 2)
    end
end

function TestCommon.run_test(name, fn)
    io.write(string.format("    -> %s ... ", name))
    local ok, err = pcall(fn)
    if ok then
        print("[PASS]")
        return true
    else
        print("[FAILED]")
        print(tostring(err))
        return false
    end
end

return TestCommon
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/interpreted/lua/tests/test_tape_engine.lua

LUA | 248 LINES | 798 WORDS | 9.3 KB

```lua
-- ================================================================================
-- BLOCK 1: METADATA & TEST TOPOLOGY
-- ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { Tape Engine } ] )
-- ================================================================================
-- ARCHITECTURAL TOPOLOGY:
--   Validates the universal Tape Engine, coroutine fibers, rollback snapshots,
--   and Quad-State connectives in isolation BEFORE being consumed by tapes.
--   - Witness: Scripture Proverbs 24:27 KJV
--     "Prepare thy work without, and make it fit for thyself in the field;
--      and afterwards build thine house."
--   - Semantics: { TapeEngineAxioms :: CoroutineFiber :: Connectives }
-- ================================================================================

local script_dir = debug.getinfo(1, "S").source:match("@?(.*[/\\])") or "./"
package.path = script_dir .. "?.lua;" ..
               script_dir .. "../?.lua;" ..
               package.path

local TestCommon = require("test_common")
local TapeEngine = require("tape_engine")

local Suite = {}

function Suite.test_tape_creation()
    local tape = TapeEngine.create_tape({
        metadata = { who = "Kernel", what = "Test" },
        constants = { LIMIT = 10 },
        rolls = {}
    })
    TestCommon.assert(tape ~= nil, "Tape must be instantiated")
    TestCommon.assert_eq(tape.metadata.who, "Kernel", "Metadata must match")
    TestCommon.assert_eq(tape.constants.LIMIT, 10, "Constants must match")
end

function Suite.test_roll_execution_and_hooks()
    local pre_count = 0
    local post_count = 0

    local tape = TapeEngine.create_tape({
        rolls = {
            {
                name = "Step1",
                action = function(ctx)
                    ctx.val = (ctx.val or 0) + 5
                    return TapeEngine.STATE_PROCEED
                end
            },
            {
                name = "Step2",
                action = function(ctx)
                    ctx.val = ctx.val * 2
                    return TapeEngine.STATE_PROCEED
                end
            }
        }
    })

    tape:before(function() pre_count = pre_count + 1 end)
    tape:after(function() post_count = post_count + 1 end)

    local ctx = { val = 10 }
    local status = tape:execute_all(ctx)
    TestCommon.assert_eq(status, TapeEngine.STATE_PROCEED, "Execution PROCEED")
    TestCommon.assert_eq(ctx.val, 30, "Calculated value: (10 + 5) * 2 = 30")
    TestCommon.assert_eq(pre_count, 2, "2 pre-roll hooks fired")
    TestCommon.assert_eq(post_count, 2, "2 post-roll hooks fired")
end

function Suite.test_rollback_and_snapshots()
    local rollback_fired = false

    local tape = TapeEngine.create_tape({
        rolls = {
```

```
            {
                name = "Step1",
                action = function(ctx)
                    ctx.count = 100
                    return TapeEngine.STATE_PROCEED
                end
            },
            {
                name = "FaultyStep",
                action = function(ctx)
                    ctx.count = 999
                    return TapeEngine.STATE_ROLLBACK
                end
            }
        }
    })

    tape:on_rollback(function() rollback_fired = true end)

    local ctx = { count = 0 }
    local status = tape:execute_all(ctx)
    TestCommon.assert_eq(status, TapeEngine.STATE_ROLLBACK, "Yields ROLLBACK")
    TestCommon.assert(rollback_fired, "Rollback handler must be invoked")
    TestCommon.assert_eq(ctx.count, 100, "Context restored to last snapshot")
end

function Suite.test_dual_rail_substrate()
    TestCommon.assert_eq(TapeEngine.trit_to_pair(0), 0, "0 -> pair 0b00")
    TestCommon.assert_eq(TapeEngine.trit_to_pair(1), 1, "1 -> pair 0b01")
    TestCommon.assert_eq(TapeEngine.trit_to_pair(-1), 2, "-1 -> pair 0b10")

    local t0, ok0 = TapeEngine.pair_to_trit(0)
    TestCommon.assert(ok0 and t0 == 0, "0b00 decodes to 0")

    local t1, ok1 = TapeEngine.pair_to_trit(1)
    TestCommon.assert(ok1 and t1 == 1, "0b01 decodes to +1")

    local t2, ok2 = TapeEngine.pair_to_trit(2)
    TestCommon.assert(ok2 and t2 == -1, "0b10 decodes to -1")

    local _, ok3 = TapeEngine.pair_to_trit(3)
    TestCommon.assert(not ok3, "0b11 detects collision fault")

    -- SIMD rail swap negation
    local val = 1 -- bit 0 (positive rail)
    local neg = TapeEngine.negate_dual_rail(val)
    TestCommon.assert_eq(neg, 2, "Positive rail swapped to negative rail")
    local neg_neg = TapeEngine.negate_dual_rail(neg)
    TestCommon.assert_eq(neg_neg, val, "Double rail negation is identity")

    -- Collision detection
    TestCommon.assert(not TapeEngine.has_null_collision(val), "No collision")
    TestCommon.assert(TapeEngine.has_null_collision(3), "3 has collision")
end

function Suite.test_connective_operators()
    -- BUT (!)
    TestCommon.assert_eq(
        TapeEngine.op_but(TapeEngine.STATE_PROCEED, TapeEngine.STATE_PROCEED),
        TapeEngine.STATE_PROCEED, "PROCEED ! PROCEED == PROCEED"
    )
    TestCommon.assert_eq(
        TapeEngine.op_but(TapeEngine.STATE_PROCEED, TapeEngine.STATE_ROLLBACK),
        TapeEngine.STATE_ROLLBACK, "PROCEED ! ROLLBACK == ROLLBACK"
    )

    -- AND (::)
    TestCommon.assert_eq(
        TapeEngine.op_and(TapeEngine.STATE_PROCEED, TapeEngine.STATE_PROCEED),
        TapeEngine.STATE_PROCEED, "PROCEED :: PROCEED == PROCEED"
    )
    TestCommon.assert_eq(
        TapeEngine.op_and(TapeEngine.STATE_PROCEED, TapeEngine.STATE_AWAIT),
        TapeEngine.STATE_AWAIT, "PROCEED :: AWAIT == AWAIT"
    )

    -- OR (|)
    TestCommon.assert_eq(
```

```
        TapeEngine.op_or(TapeEngine.STATE_PROCEED, TapeEngine.STATE_ROLLBACK),
        TapeEngine.STATE_PROCEED, "PROCEED | ROLLBACK == PROCEED"
    )
    TestCommon.assert_eq(
        TapeEngine.op_or(TapeEngine.STATE_ROLLBACK, TapeEngine.STATE_PROCEED),
        TapeEngine.STATE_PROCEED, "ROLLBACK | PROCEED == PROCEED"
    )

    -- NOT (--)
    TestCommon.assert_eq(
        TapeEngine.op_not(TapeEngine.STATE_PROCEED),
        TapeEngine.STATE_ROLLBACK, "-- PROCEED == ROLLBACK"
    )
    TestCommon.assert_eq(
        TapeEngine.op_not(TapeEngine.STATE_ROLLBACK),
        TapeEngine.STATE_PROCEED, "-- ROLLBACK == PROCEED"
    )

    -- NEQ (!=)
    TestCommon.assert_eq(
        TapeEngine.op_neq(TapeEngine.STATE_PROCEED, TapeEngine.STATE_ROLLBACK),
        TapeEngine.STATE_PROCEED, "PROCEED != ROLLBACK == PROCEED"
    )
    TestCommon.assert_eq(
        TapeEngine.op_neq(TapeEngine.STATE_PROCEED, TapeEngine.STATE_PROCEED),
        TapeEngine.STATE_ROLLBACK, "PROCEED != PROCEED == ROLLBACK"
    )

    -- IS_NOT (=!)
    TestCommon.assert_eq(
        TapeEngine.op_is_not(TapeEngine.STATE_AWAIT,
                             TapeEngine.STATE_ROLLBACK),
        TapeEngine.STATE_PROCEED, "AWAIT =! ROLLBACK == PROCEED"
    )

    -- LIKEN (=~)
    TestCommon.assert_eq(
        TapeEngine.op_liken(TapeEngine.STATE_PROCEED, TapeEngine.STATE_AWAIT),
        TapeEngine.STATE_PROCEED, "PROCEED =~ AWAIT == PROCEED"
    )

    -- RELATE (:)
    TestCommon.assert_eq(
        TapeEngine.op_relate(TapeEngine.STATE_PROCEED, TapeEngine.STATE_AWAIT),
        TapeEngine.STATE_AWAIT, "PROCEED : AWAIT == AWAIT"
    )
    TestCommon.assert_eq(
        TapeEngine.op_relate(TapeEngine.STATE_ROLLBACK,
                             TapeEngine.STATE_PROCEED),
        TapeEngine.STATE_ROLLBACK, "ROLLBACK : PROCEED == ROLLBACK"
    )
end

function Suite.test_literal_disambiguation()
    TestCommon.assert(TapeEngine.is_state(TapeEngine.STATE_PROCEED), "State +1")
    TestCommon.assert(TapeEngine.is_state(TapeEngine.STATE_AWAIT), "State 0")
    TestCommon.assert(TapeEngine.is_state(TapeEngine.STATE_ROLLBACK),
                      "State -1")
    TestCommon.assert(TapeEngine.is_state(TapeEngine.STATE_HALT), "State NULL")
    TestCommon.assert(not TapeEngine.is_state(42), "42 is not a state")

    -- Air quotes "0" literal resolution
    local v0, is_lit0 = TapeEngine.resolve_literal("0")
    TestCommon.assert(is_lit0 and v0 == 0, "Air quote 0 resolves to literal 0")

    -- Cast { 0 } table literal resolution
    local vt, is_litt = TapeEngine.resolve_literal({ 0 })
    TestCommon.assert(is_litt and vt == 0, "{ 0 } resolves to literal 0")

    -- Plain state 0 is not a literal
    local vs, is_lits = TapeEngine.resolve_literal(TapeEngine.STATE_AWAIT)
    TestCommon.assert((not is_lits) and vs == 0, "STATE_AWAIT is not literal")
end

print("================================================================")
print("   OMNICODE LUA UNIVERSAL TAPE ENGINE UNIT TESTBED")
print("================================================================")
TestCommon.run_test("Tape Instantiation & Topology", Suite.test_tape_creation)
```

```
TestCommon.run_test("Roll Execution & Event Hooks",
                    Suite.test_roll_execution_and_hooks)
TestCommon.run_test("Transactional Rollback & Snapshots",
                    Suite.test_rollback_and_snapshots)
TestCommon.run_test("Dual-Rail Polar Substrate & SIMD",
                    Suite.test_dual_rail_substrate)
TestCommon.run_test("Quad-State Connective Operators",
                    Suite.test_connective_operators)
TestCommon.run_test("State vs Literal Disambiguation",
                    Suite.test_literal_disambiguation)

if TestCommon.failures > 0 then
    io.stderr:write(string.format("[!] %d test(s) failed\n",
                                  TestCommon.failures))
    os.exit(1)
end
print("-----------------------------------------------------------------")
print("[√] All Universal Tape Engine tests verified and passed!")
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/compiled/c/Makefile

TEXT | 17 LINES | 33 WORDS | 0.3 KB

```
CC ?= gcc
CFLAGS ?= -Wall -Wextra -std=c11 -Iinclude -Itests

all: test

test: test_universal_bin
    ./test_universal_bin

test_universal_bin: tests/test_universal.c include/omni_base.h \
                    tests/test_common.h
    $(CC) $(CFLAGS) $< -o $@

clean:
    rm -f test_universal_bin

.PHONY: all test clean
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/compiled/c/compile_flags.txt

TXT | 6 LINES | 5 WORDS | 0.0 KB

```
-Iinclude
-Itests
-Wall
-Wextra
-std=c11
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/compiled/c/test_universal_bin

DOC/BINARY | 1 LINES | 5 WORDS | 25.0 KB

[Binary Artifact: test_universal_bin (25.0 KB)]

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/compiled/c/tests/test_common.h

H | 59 LINES | 213 WORDS | 1.7 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & TEST HARNESS TOPOLOGY
 * ( Test Framework: < OmniCode Standard Library Universal Testbed > )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Universal test harness for the OmniCode Standard Library C Transpile.
 *   Provides structured assertions, test suite runner macros, and tripwires.
 *   - Witness: Scripture Proverbs 24:27 KJV
 *     "Prepare thy work without, and make it fit for thyself in the field;
 *      and afterwards build thine house."
 *   - Semantics: { AssertionInterlock :: GranularFaultIsolation }
 * ============================================================================ */

#ifndef OMNI_TEST_COMMON_H
#define OMNI_TEST_COMMON_H

#include "omni_base.h"
#include <stdio.h>
#include <stdbool.h>

#ifdef __cplusplus
extern "C" {
#endif

/** Global test assertion failure counter */
extern int g_omni_test_failures;

/**
 * @brief Evaluates assertion expression; logs failure and returns 1 on error.
 */
#define OMNI_TEST_ASSERT(expr, msg) \
    do { \
        if (!(expr)) { \
            printf("    [FAIL] %s:%d: %s (Expression: %s)\n", \
                   __FILE__, __LINE__, (msg), #expr); \
            g_omni_test_failures++; \
            return 1; \
        } \
    } while (0)

/**
 * @brief Runs an individual test function and reports PASS / FAIL.
 */
#define OMNI_TEST_RUN(fn, test_name) \
    do { \
        printf("    -> %s ... ", (test_name)); \
        if ((fn)() != 0) { \
            printf("[FAILED]\n"); \
            return 1; \
        } \
        printf("[PASS]\n"); \
    } while (0)

#ifdef __cplusplus
}
#endif

#endif /* OMNI_TEST_COMMON_H */
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/compiled/c/tests/test_universal.c

C | 213 LINES | 781 WORDS | 9.8 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & TEST TOPOLOGY
 * ( Unit Test: < Lexicon { Types of Ideas } > & [ Test { Universal Base } ] )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Validates the universal base axioms, balanced ternary ALU, tripwires, and
 *   Quad-State connectives in isolation BEFORE being consumed downstream.
 *   - Witness: Scripture Proverbs 24:27 KJV
 *     "Prepare thy work without, and make it fit for thyself in the field;
 *      and afterwards build thine house."
 *   - Semantics: { BaseAxioms :: BalancedTernaryALU :: ConnectiveGuards }
 * ============================================================================ */

#include "test_common.h"

int g_omni_test_failures = 0;

static int test_base_preconditions(void) {
    omni_quad_state_t s = omni_base_verify_preconditions();
    OMNI_TEST_ASSERT(s == OMNI_STATE_PROCEED,
                     "Preconditions must PROCEED on 64-bit platform");
    return 0;
}

static int test_balanced_ternary_arithmetic(void) {
    /* Negation */
    OMNI_TEST_ASSERT(omni_trit_negate(OMNI_TRIT_POS) == OMNI_TRIT_NEG,
                     "Negate(+1) == -1");
    OMNI_TEST_ASSERT(omni_trit_negate(OMNI_TRIT_NEG) == OMNI_TRIT_POS,
                     "Negate(-1) == +1");
    OMNI_TEST_ASSERT(omni_trit_negate(OMNI_TRIT_ZERO) == OMNI_TRIT_ZERO,
                     "Negate(0) == 0");

    /* Multiplication */
    OMNI_TEST_ASSERT(omni_trit_multiply(OMNI_TRIT_POS, OMNI_TRIT_NEG) ==
                     OMNI_TRIT_NEG, "(+1) * (-1) == -1");
    OMNI_TEST_ASSERT(omni_trit_multiply(OMNI_TRIT_NEG, OMNI_TRIT_NEG) ==
                     OMNI_TRIT_POS, "(-1) * (-1) == +1");

    /* Addition with Carry */
    omni_trit_t cout = 0;
    omni_trit_t sum = omni_trit_add(OMNI_TRIT_POS, OMNI_TRIT_POS, 0, &cout);
    OMNI_TEST_ASSERT(sum == OMNI_TRIT_NEG && cout == OMNI_TRIT_POS,
                     "(+1) + (+1) == -1 with carry +1 (Radix-3: 1*3 - 1 = 2)");

    sum = omni_trit_add(OMNI_TRIT_POS, OMNI_TRIT_NEG, 0, &cout);
    OMNI_TEST_ASSERT(sum == OMNI_TRIT_ZERO && cout == OMNI_TRIT_ZERO,
                     "(+1) + (-1) == 0 with carry 0 (Equilibrium)");

    return 0;
}

static int test_quad_state_connectives(void) {
    /* Connective: BUT (!) - Adversative Caveat */
    omni_quad_state_t act = OMNI_STATE_PROCEED;
    omni_quad_state_t cav_ok = OMNI_STATE_PROCEED;
    omni_quad_state_t cav_fail = OMNI_STATE_ROLLBACK;

    OMNI_TEST_ASSERT(omni_quad_state_but(act, cav_ok) == OMNI_STATE_PROCEED,
                     "PROCEED ! PROCEED must yield PROCEED");
    OMNI_TEST_ASSERT(omni_quad_state_but(act, cav_fail) == OMNI_STATE_ROLLBACK,
                     "PROCEED ! ROLLBACK must yield ROLLBACK");

    /* Connective: AND (::) - Conjunction */
    OMNI_TEST_ASSERT(omni_quad_state_and(OMNI_STATE_PROCEED, OMNI_STATE_PROCEED)
                     == OMNI_STATE_PROCEED, "PROCEED :: PROCEED == PROCEED");
    OMNI_TEST_ASSERT(omni_quad_state_and(OMNI_STATE_PROCEED, OMNI_STATE_AWAIT)
                     == OMNI_STATE_AWAIT, "PROCEED :: AWAIT == AWAIT");
    OMNI_TEST_ASSERT(
        omni_quad_state_and(OMNI_STATE_PROCEED, OMNI_STATE_ROLLBACK)
                     == OMNI_STATE_ROLLBACK, "PROCEED :: ROLLBACK == ROLLBACK");

    /* Connective: OR (|) - Disjunctive Alternative Valve */
```

```
    OMNI_TEST_ASSERT(omni_quad_state_or(OMNI_STATE_PROCEED, OMNI_STATE_ROLLBACK)
                     == OMNI_STATE_PROCEED, "PROCEED | ROLLBACK == PROCEED");
    OMNI_TEST_ASSERT(omni_quad_state_or(OMNI_STATE_ROLLBACK, OMNI_STATE_PROCEED)
                     == OMNI_STATE_PROCEED, "ROLLBACK | PROCEED == PROCEED");
    OMNI_TEST_ASSERT(
        omni_quad_state_or(OMNI_STATE_ROLLBACK, OMNI_STATE_ROLLBACK)
                     == OMNI_STATE_ROLLBACK, "ROLLBACK | ROLLBACK == ROLLBACK");

    /* Connective: NOT (--) - Truth Inversion */
    OMNI_TEST_ASSERT(omni_quad_state_not(OMNI_STATE_PROCEED) ==
                     OMNI_STATE_ROLLBACK, "-- PROCEED == ROLLBACK");
    OMNI_TEST_ASSERT(omni_quad_state_not(OMNI_STATE_ROLLBACK) ==
                     OMNI_STATE_PROCEED, "-- ROLLBACK == PROCEED");
    OMNI_TEST_ASSERT(omni_quad_state_not(OMNI_STATE_AWAIT) ==
                     OMNI_STATE_AWAIT, "-- AWAIT == AWAIT");

    /* Connective: NEQ (!=) - Inequality Gate */
    OMNI_TEST_ASSERT(omni_quad_state_neq(OMNI_STATE_PROCEED,
                                         OMNI_STATE_ROLLBACK) ==
                     OMNI_STATE_PROCEED, "PROCEED != ROLLBACK == PROCEED");
    OMNI_TEST_ASSERT(omni_quad_state_neq(OMNI_STATE_PROCEED,
                                         OMNI_STATE_PROCEED) ==
                     OMNI_STATE_ROLLBACK, "PROCEED != PROCEED == ROLLBACK");

    /* Connective: IS_NOT (=!) - Predicate Filter */
    OMNI_TEST_ASSERT(omni_quad_state_is_not(OMNI_STATE_AWAIT,
                                           OMNI_STATE_ROLLBACK) ==
                     OMNI_STATE_PROCEED, "AWAIT =! ROLLBACK == PROCEED");
    OMNI_TEST_ASSERT(omni_quad_state_is_not(OMNI_STATE_ROLLBACK,
                                           OMNI_STATE_ROLLBACK) ==
                     OMNI_STATE_ROLLBACK, "ROLLBACK =! ROLLBACK == ROLLBACK");

    /* Connective: LIKEN (=~) - Compatibility Match */
    OMNI_TEST_ASSERT(omni_quad_state_liken(OMNI_STATE_PROCEED,
                                         OMNI_STATE_AWAIT) ==
                     OMNI_STATE_PROCEED, "PROCEED =~ AWAIT == PROCEED");
    OMNI_TEST_ASSERT(omni_quad_state_liken(OMNI_STATE_PROCEED,
                                         OMNI_STATE_ROLLBACK) ==
                     OMNI_STATE_ROLLBACK, "PROCEED =~ ROLLBACK == ROLLBACK");

    /* Connective: RELATE (:) - Perspective Projection */
    OMNI_TEST_ASSERT(omni_quad_state_relate(OMNI_STATE_PROCEED,
                                           OMNI_STATE_AWAIT) ==
                     OMNI_STATE_AWAIT, "PROCEED : AWAIT == AWAIT");
    OMNI_TEST_ASSERT(omni_quad_state_relate(OMNI_STATE_ROLLBACK,
                                           OMNI_STATE_PROCEED) ==
                     OMNI_STATE_ROLLBACK, "ROLLBACK : PROCEED == ROLLBACK");

    /* State Validity */
    OMNI_TEST_ASSERT(omni_state_is_valid(OMNI_STATE_PROCEED), "PROCEED valid");
    OMNI_TEST_ASSERT(omni_state_is_valid(OMNI_STATE_AWAIT), "AWAIT valid");
    OMNI_TEST_ASSERT(omni_state_is_valid(OMNI_STATE_ROLLBACK),
                     "ROLLBACK valid");
    OMNI_TEST_ASSERT(omni_state_is_valid(OMNI_STATE_HALT), "HALT valid");
    OMNI_TEST_ASSERT(!omni_state_is_valid((omni_quad_state_t)42), "42 invalid");

    return 0;
}

static int test_dual_rail_substrate(void) {
    /* 1. 2-Bit Pair Encoding & Decoding */
    OMNI_TEST_ASSERT(omni_trit_to_pair(OMNI_TRIT_ZERO) == OMNI_TRIT_PAIR_ZERO,
                     "0 trit -> pair 0b00");
    OMNI_TEST_ASSERT(omni_trit_to_pair(OMNI_TRIT_POS) == OMNI_TRIT_PAIR_POS,
                     "+1 trit -> pair 0b01");
    OMNI_TEST_ASSERT(omni_trit_to_pair(OMNI_TRIT_NEG) == OMNI_TRIT_PAIR_NEG,
                     "-1 trit -> pair 0b10");

    omni_trit_t t = 0;
    bool ok = omni_pair_to_trit(OMNI_TRIT_PAIR_ZERO, &t);
    OMNI_TEST_ASSERT(ok && t == OMNI_TRIT_ZERO, "pair 0b00 -> 0 trit");

    ok = omni_pair_to_trit(OMNI_TRIT_PAIR_POS, &t);
    OMNI_TEST_ASSERT(ok && t == OMNI_TRIT_POS, "pair 0b01 -> +1 trit");

    ok = omni_pair_to_trit(OMNI_TRIT_PAIR_NEG, &t);
    OMNI_TEST_ASSERT(ok && t == OMNI_TRIT_NEG, "pair 0b10 -> -1 trit");

```

```
    ok = omni_pair_to_trit(OMNI_TRIT_PAIR_NULL, &t);
    OMNI_TEST_ASSERT(!ok, "pair 0b11 -> NULL collision fault");

    /* 2. Dual-Rail SIMD Negation */
    uint64_t val = 0x0000000000000001ULL; /* 1 trit POS in bit 0 */
    uint64_t neg = omni_dual_rail_negate(val);
    OMNI_TEST_ASSERT(neg == 0x0000000000000002ULL, "Negation swaps P->N rail");
    uint64_t neg_neg = omni_dual_rail_negate(neg);
    OMNI_TEST_ASSERT(neg_neg == val, "Double negation restores identity");

    /* 3. Collision Trap */
    OMNI_TEST_ASSERT(!omni_dual_rail_has_collision(val),
                     "val has no collision");
    uint64_t trap = 0x0000000000000003ULL; /* bits 0 & 1 set -> collision */
    OMNI_TEST_ASSERT(omni_dual_rail_has_collision(trap),
                     "trap reports collision");

    return 0;
}

static int test_tripwire_lifecycle(void) {
    omni_tripwire_state_t tw = OMNI_TRIPWIRE_DISARMED;
    omni_tripwire_arm(&tw);
    OMNI_TEST_ASSERT(tw == OMNI_TRIPWIRE_ARMED, "Tripwire must be ARMED");

    omni_tripwire_disarm(&tw);
    OMNI_TEST_ASSERT(tw == OMNI_TRIPWIRE_DISARMED, "Tripwire must be DISARMED");

    omni_tripwire_arm(&tw);
    omni_tripwire_trip(&tw);
    OMNI_TEST_ASSERT(tw == OMNI_TRIPWIRE_TRIPPED, "Tripwire must be TRIPPED");

    omni_quad_state_t integrity = omni_base_verify_integrity(tw,
        OMNI_STATE_PROCEED);
    OMNI_TEST_ASSERT(integrity == OMNI_STATE_ROLLBACK,
                     "Integrity must fail if tripwire was TRIPPED");

    return 0;
}

int main(void) {
    printf("================================================================\n");
    printf("   OMNICODE C UNIVERSAL BASE UNIT TESTBED\n");
    printf("================================================================\n");
    OMNI_TEST_RUN(test_base_preconditions,
                  "Hardware Preconditions Verification");
    OMNI_TEST_RUN(test_balanced_ternary_arithmetic,
                  "Balanced Ternary ALU Math");
    OMNI_TEST_RUN(test_dual_rail_substrate, "Dual-Rail Polar Substrate & SIMD");
    OMNI_TEST_RUN(test_quad_state_connectives, "Quad-State Connectives");
    OMNI_TEST_RUN(test_tripwire_lifecycle, "Tripwire Lifecycle & Integrity");

    if (g_omni_test_failures > 0) {
        fprintf(stderr, "[!] Universal base test suite failed with %d errors\n",
                g_omni_test_failures);
        return 1;
    }
    printf("----------------------------------------------------------------\n");
    printf("[√] All Universal Base Axioms verified and sealed!\n");
    return 0;
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/compiled/c/include/omni.h

H | 45 LINES | 176 WORDS | 1.4 KB

```c
/* ============================================================================
 * OMNICODE FREESTANDING STANDARD LIBRARY (C MASTER UMBRELLA HEADER)
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Master header exposing all primitive invariant types and operational
 *   primitives for OmniCode bare-metal and hosted runtimes.
 *   - Category: Standard Library Track 2 C Transpile Variant
 *   - Invariant Types Included:
 *       < Base >      : Substrates, Balanced Trits, Quad-State & Connectives
 *       < Character > : Atomic Glyph / Letter Rune (1 Cell / 5 Trits)
 *       < Number >    : Scalar Quantity / Measure (1 Word / 32 Trits)
 *       < Container > : Generic Bounded Space Envelope / Slice
 *       < Site >      : Silicon Coordinate / Address (RAM @ vs MMIO ::@)
 *       < State >     : Quad-State Causal Truth & Loop Stepper
 * ============================================================================ */

#ifndef OMNI_H
#define OMNI_H

#include "omni_base.h"

/* Modular Type Substrates (Character & Number) */
#if __has_include("character.h")
#include "character.h"
#endif

#if __has_include("number.h")
#include "number.h"
#endif

/* Transitional Primitive Types */
#if __has_include("container.h")
#include "container.h"
#endif

#if __has_include("site.h")
#include "site.h"
#endif

#if __has_include("state.h")
#include "state.h"
#endif

#endif /* OMNI_H */
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/types/universal/transpiled/compiled/c/include/omni_base.h

H | 403 LINES | 1567 WORDS | 14.5 KB

```c
/* ============================================================================
 * BLOCK 1: METADATA & INVARIANT AXIOMS BLOCK
 * ( Invariant Root: < Lexicon { Types of Ideas } > & [ Noun { Base Axioms } ] )
 * ============================================================================
 * ARCHITECTURAL TOPOLOGY:
 *   Foundational bare-metal substrates, balanced ternary types, and Quad-State
 *   truth logic governing the OmniCode Standard Library Track 2 C Transpile.
 *   - Environment: Freestanding C99/C11 (Zero libc/OS dependency)
 *   - Word Size: 64-Bit Silicon Scalar / 32 Balanced Trits
 *   - Cell Size: 8-Bit Byte / 5 Balanced Trits
 *   - System: OmniCode { Lexicon }
 *   - Witness: Scripture Proverbs 11:1 KJV
 *     "A false balance is abomination to the LORD: but a just weight is his
 *      delight."
 *   - Semantics: { BalancedTernary :: QuadStateTruth :: TripwireGuards }
 * ============================================================================ */

#ifndef OMNI_BASE_H
#define OMNI_BASE_H

#include <stdint.h>
#include <stdbool.h>
#include <stddef.h>

#ifdef __cplusplus
extern "C" {
#endif

/* ----------------------------------------------------------------------------
 * ARCHITECTURAL CONSTANTS & SUBSTRATE CAPACITIES
 * ---------------------------------------------------------------------------- */

/** Number of balanced trits packed into an 8-bit memory Cell (3^5 = 243). */
#define OMNI_TRITS_PER_CELL         5

/** Number of balanced trits packed into a 64-bit machine Word. */
#define OMNI_TRITS_PER_WORD         32

/** Footprint of the standard bounded Container vessel exemplar (in bytes). */
#define OMNI_VESSEL_DEFAULT_CELLS   64

/* ----------------------------------------------------------------------------
 * 1. BALANCED TERNARY SUBSTRATE: omni_trit_t
 * ---------------------------------------------------------------------------- */

/**
 * @brief Discrete balanced ternary digit (-1, 0, +1).
 *
 * Balanced ternary is inherently symmetrical around zero:
 *   - Negative (-1) : Backward causation, negation, deficit, or restoration.
 *   - Zero     ( 0) : Equilibrium, standby, neutral, or unperturbed balance.
 *   - Positive (+1) : Forward causation, affirmative assertion, or surplus.
 */
typedef int8_t omni_trit_t;

#define OMNI_TRIT_NEG   ((omni_trit_t)-1)
#define OMNI_TRIT_ZERO  ((omni_trit_t) 0)
#define OMNI_TRIT_POS   ((omni_trit_t) 1)

/* ----------------------------------------------------------------------------
 * BALANCED TERNARY DUAL-RAIL SUBSTRATE (POLAR BIT-PLANES)
 * ---------------------------------------------------------------------------- */

/** Dual-Rail Positive Bit-Plane Mask (all even bits: 0, 2, 4, ... 62). */
#define OMNI_BITPLANE_POS_MASK      (0x5555555555555555ULL)

/** Dual-Rail Negative Bit-Plane Mask (all odd bits: 1, 3, 5, ... 63). */
#define OMNI_BITPLANE_NEG_MASK      (0xAAAAAAAAAAAAAAAAULL)

/** Dual-Rail 2-Bit Trit Constants on Binary Silicon. */
#define OMNI_TRIT_PAIR_ZERO         ((uint8_t)0x00) /* 00: Equilibrium (0) */
#define OMNI_TRIT_PAIR_POS          ((uint8_t)0x01) /* 01: Positive (+1)   */
#define OMNI_TRIT_PAIR_NEG          ((uint8_t)0x02) /* 10: Negative (-1)   */
```

```c
#define OMNI_TRIT_PAIR_NULL         ((uint8_t)0x03) /* 11: Collision (NULL)*/

/* ---------------------------------------------------------------------------
 * 2. QUAD-STATE CAUSAL TRUTH: omni_quad_state_t
 * ------------------------------------------------------------------------- */

/**
 * @brief The fourfold causal truth states of computation in OmniCode.
 *
 * Unifies boolean logic, error handling, scheduling, and clock detents:
 *   - OMNI_STATE_PROCEED  (+1) : Forward Causation (+t). Equilibrium.
 *   - OMNI_STATE_AWAIT    ( 0) : Equilibrium Standby (t=t). Pending async.
 *   - OMNI_STATE_ROLLBACK (-1) : Retroactive Reversal (-t). Guard tripped.
 *   - OMNI_STATE_HALT     (-2) : Terminal Detent (NULL). Clock stopped.
 */
typedef enum {
    OMNI_STATE_ROLLBACK = -1,   /**< -1 : Retroactive Reversal / Error */
    OMNI_STATE_AWAIT    =  0,   /**<  0 : Equilibrium Standby / Hold */
    OMNI_STATE_PROCEED  =  1,   /**< +1 : Forward Causation / Advance */
    OMNI_STATE_HALT     = -2    /**< NULL: Terminal Detent / Clock Stop */
} omni_quad_state_t;

/**
 * @brief Tertiary execution status subset for non-terminal checkpoints.
 */
typedef enum {
    OMNI_STATUS_ROLLBACK = -1,
    OMNI_STATUS_AWAIT    =  0,
    OMNI_STATUS_PROCEED  =  1
} omni_status_t;

/* ---------------------------------------------------------------------------
 * 3. HARDWARE COGNITIVE SITES (EXEMPLARS)
 * ------------------------------------------------------------------------- */

/** Unmapped null pointer origin. */
#define OMNI_SITE_NULL          ((uintptr_t)0x00000000)

/** Real-mode Master Boot Record physical origin. */
#define OMNI_SITE_MBR_BOOT      ((uintptr_t)0x00007C00)

/** Hardware UART serial port base (COM1) for kernel telemetry. */
#define OMNI_SITE_COM1          ((uintptr_t)0x000003F8)

/** Physical memory-mapped VGA text-mode display buffer (80x25 characters). */
#define OMNI_SITE_VGA_BUFFER    ((uintptr_t)0x000B8000)

/* ---------------------------------------------------------------------------
 * 4. TRIPWIRE & INTEGRITY DETENTS: omni_tripwire_state_t
 * ------------------------------------------------------------------------- */

/**
 * @brief Safety interlock state preventing silent memory corruption.
 */
typedef enum {
    OMNI_TRIPWIRE_DISARMED = 0, /**< Interlock inactive; safe quiescent */
    OMNI_TRIPWIRE_ARMED    = 1, /**< Active guard monitoring bounds */
    OMNI_TRIPWIRE_TRIPPED  = 2  /**< Violation intercepted; blocked */
} omni_tripwire_state_t;

/* ===========================================================================
 * BLOCK 2: OPENING BLOCK
 * ( Subsystem Preconditions, Verification & Initializers )
 * ========================================================================= */

/**
 * @brief Verifies that host hardware meets OmniCode's bare-metal preconditions.
 */
static inline omni_quad_state_t omni_base_verify_preconditions(void) {
    if (sizeof(uintptr_t) != 8) return OMNI_STATE_ROLLBACK;
    if (sizeof(uint8_t)   != 1) return OMNI_STATE_ROLLBACK;

    /* Prove Proverbs 11:1 Law { Equilibrium }: (+1) plus (-1) <=> 0 */
    omni_trit_t pos = OMNI_TRIT_POS;
    omni_trit_t neg = OMNI_TRIT_NEG;
    if ((pos + neg) != OMNI_TRIT_ZERO) return OMNI_STATE_ROLLBACK;

    return OMNI_STATE_PROCEED;
```

```
}

static inline void omni_tripwire_arm(omni_tripwire_state_t *tw) {
    if (tw) *tw = OMNI_TRIPWIRE_ARMED;
}

static inline void omni_tripwire_disarm(omni_tripwire_state_t *tw) {
    if (tw) *tw = OMNI_TRIPWIRE_DISARMED;
}

static inline void omni_tripwire_trip(omni_tripwire_state_t *tw) {
    if (tw) *tw = OMNI_TRIPWIRE_TRIPPED;
}

/* ============================================================================
 * BLOCK 3: BODY BLOCK
 * ( Balanced Ternary Algebra, Quad-State Logic & Connective Inlines )
 * ============================================================================ */

static inline omni_trit_t omni_trit_negate(omni_trit_t t) {
    return (omni_trit_t)(-t);
}

static inline omni_trit_t omni_trit_multiply(omni_trit_t a, omni_trit_t b) {
    return (omni_trit_t)(a * b);
}

static inline omni_trit_t omni_trit_add(omni_trit_t a, omni_trit_t b,
                                        omni_trit_t cin, omni_trit_t *cout) {
    int32_t sum = (int32_t)a + (int32_t)b + (int32_t)cin;
    omni_trit_t carry = 0;

    if (sum > 1) {
        sum -= 3;
        carry = 1;
    } else if (sum < -1) {
        sum += 3;
        carry = -1;
    }

    if (cout) *cout = carry;
    return (omni_trit_t)sum;
}

/* ----------------------------------------------------------------------------
 * BALANCED TERNARY DUAL-RAIL HARDWARE CONVERSIONS
 * ---------------------------------------------------------------------------- */

static inline uint8_t omni_trit_to_pair(omni_trit_t trit) {
    if (trit == OMNI_TRIT_ZERO) return OMNI_TRIT_PAIR_ZERO;
    if (trit == OMNI_TRIT_POS)  return OMNI_TRIT_PAIR_POS;
    if (trit == OMNI_TRIT_NEG)  return OMNI_TRIT_PAIR_NEG;
    return OMNI_TRIT_PAIR_NULL;
}

static inline bool omni_pair_to_trit(uint8_t pair, omni_trit_t *out_trit) {
    switch (pair & 0x03) {
        case OMNI_TRIT_PAIR_ZERO:
            if (out_trit) *out_trit = OMNI_TRIT_ZERO;
            return true;
        case OMNI_TRIT_PAIR_POS:
            if (out_trit) *out_trit = OMNI_TRIT_POS;
            return true;
        case OMNI_TRIT_PAIR_NEG:
            if (out_trit) *out_trit = OMNI_TRIT_NEG;
            return true;
        default: /* OMNI_TRIT_PAIR_NULL */
            if (out_trit) *out_trit = OMNI_TRIT_ZERO;
            return false;
    }
}

static inline uint64_t omni_dual_rail_negate(uint64_t packed) {
    uint64_t pos = packed & OMNI_BITPLANE_POS_MASK;
    uint64_t neg = packed & OMNI_BITPLANE_NEG_MASK;
    return ((pos << 1) & OMNI_BITPLANE_NEG_MASK) |
           ((neg >> 1) & OMNI_BITPLANE_POS_MASK);
}
```

```
230
231 static inline bool omni_dual_rail_has_collision(uint64_t packed) {
232     uint64_t pos = packed & OMNI_BITPLANE_POS_MASK;
233     uint64_t neg = (packed >> 1) & OMNI_BITPLANE_POS_MASK;
234     return (pos & neg) != 0;
235 }
236
237 /* ---------------------------------------------------------------------------
238  * 5. BALANCED TERNARY CONNECTIVE OPERATORS (!, ::, |, --)
239  * ------------------------------------------------------------------------- */
240
241 /**
242  * @brief Adversative caveat gate: A ! B (A executes, BUT caveat B must hold).
243  */
244 static inline omni_quad_state_t omni_quad_state_but(omni_quad_state_t action,
245                                                     omni_quad_state_t caveat) {
246     if (caveat == OMNI_STATE_ROLLBACK) return OMNI_STATE_ROLLBACK;
247     if (caveat == OMNI_STATE_HALT)     return OMNI_STATE_HALT;
248     return action;
249 }
250
251 /**
252  * @brief Cumulative conjunction: A :: B (A AND B simultaneous).
253  */
254 static inline omni_quad_state_t omni_quad_state_and(omni_quad_state_t a,
255                                                     omni_quad_state_t b) {
256     if (a == OMNI_STATE_HALT || b == OMNI_STATE_HALT) return OMNI_STATE_HALT;
257     if (a == OMNI_STATE_ROLLBACK || b == OMNI_STATE_ROLLBACK) {
258         return OMNI_STATE_ROLLBACK;
259     }
260     if (a == OMNI_STATE_AWAIT || b == OMNI_STATE_AWAIT) return OMNI_STATE_AWAIT;
261     return OMNI_STATE_PROCEED;
262 }
263
264 /**
265  * @brief Disjunctive alternative valve: A | B (A OR B).
266  */
267 static inline omni_quad_state_t omni_quad_state_or(omni_quad_state_t a,
268                                                    omni_quad_state_t b) {
269     if (a == OMNI_STATE_PROCEED || b == OMNI_STATE_PROCEED) {
270         return OMNI_STATE_PROCEED;
271     }
272     if (a == OMNI_STATE_AWAIT || b == OMNI_STATE_AWAIT) return OMNI_STATE_AWAIT;
273     if (a == OMNI_STATE_ROLLBACK && b == OMNI_STATE_ROLLBACK) {
274         return OMNI_STATE_ROLLBACK;
275     }
276     return OMNI_STATE_HALT;
277 }
278
279 /**
280  * @brief Balanced ternary truth inversion: -- A (NOT A).
281  */
282 static inline omni_quad_state_t omni_quad_state_not(omni_quad_state_t a) {
283     if (a == OMNI_STATE_PROCEED)  return OMNI_STATE_ROLLBACK;
284     if (a == OMNI_STATE_ROLLBACK) return OMNI_STATE_PROCEED;
285     return a;
286 }
287
288 /**
289  * @brief Inequality verification: A != B (A not to be B).
290  */
291 static inline omni_quad_state_t omni_quad_state_neq(omni_quad_state_t a,
292                                                     omni_quad_state_t b) {
293     if (a == OMNI_STATE_HALT || b == OMNI_STATE_HALT) return OMNI_STATE_HALT;
294     return (a != b) ? OMNI_STATE_PROCEED : OMNI_STATE_ROLLBACK;
295 }
296
297 /**
298  * @brief Predicate is-not check: A =! B (State A is not target B).
299  */
300 static inline omni_quad_state_t omni_quad_state_is_not(
301     omni_quad_state_t a,
302     omni_quad_state_t target)
303 {
304     return (a != target) ? OMNI_STATE_PROCEED : OMNI_STATE_ROLLBACK;
305 }
306
307 /**
```

```c
 * @brief Liken to / compatibility match: A =~ B.
 */
static inline omni_quad_state_t omni_quad_state_liken(omni_quad_state_t a,
                                                      omni_quad_state_t b) {
    if (a == OMNI_STATE_HALT || b == OMNI_STATE_HALT) return OMNI_STATE_HALT;
    if (a == b) return OMNI_STATE_PROCEED;
    if ((a == OMNI_STATE_PROCEED || a == OMNI_STATE_AWAIT) &&
        (b == OMNI_STATE_PROCEED || b == OMNI_STATE_AWAIT)) {
        return OMNI_STATE_PROCEED;
    }
    return OMNI_STATE_ROLLBACK;
}

/**
 * @brief Relation projection valve: Context : Aspect.
 */
static inline omni_quad_state_t omni_quad_state_relate(omni_quad_state_t ctx,
                                                       omni_quad_state_t asp) {
    if (ctx == OMNI_STATE_HALT)     return OMNI_STATE_HALT;
    if (ctx == OMNI_STATE_ROLLBACK) return OMNI_STATE_ROLLBACK;
    return asp;
}

/**
 * @brief Verifies whether a given state is one of the defined causal states.
 */
static inline bool omni_state_is_valid(omni_quad_state_t s) {
    return (s == OMNI_STATE_PROCEED ||
            s == OMNI_STATE_AWAIT   ||
            s == OMNI_STATE_ROLLBACK||
            s == OMNI_STATE_HALT);
}

static inline omni_quad_state_t omni_guard_assert(bool condition,
                                                  omni_tripwire_state_t *tw,
                                                  omni_quad_state_t *status) {
    if (condition) {
        if (status) *status = OMNI_STATE_PROCEED;
        return OMNI_STATE_PROCEED;
    } else {
        if (tw) *tw = OMNI_TRIPWIRE_TRIPPED;
        if (status) *status = OMNI_STATE_ROLLBACK;
        return OMNI_STATE_ROLLBACK;
    }
}

static inline bool omni_is_proceed(omni_quad_state_t s) {
    return (s == OMNI_STATE_PROCEED);
}
static inline bool omni_is_await(omni_quad_state_t s) {
    return (s == OMNI_STATE_AWAIT);
}
static inline bool omni_is_rollback(omni_quad_state_t s) {
    return (s == OMNI_STATE_ROLLBACK);
}
static inline bool omni_is_halt(omni_quad_state_t s) {
    return (s == OMNI_STATE_HALT);
}

/* ============================================================================
 * BLOCK 4: CLOSING BLOCK
 * ( Integrity Seals, Detents & Commit Status Functions )
 * ============================================================================ */

static inline omni_quad_state_t omni_base_verify_integrity(
    omni_tripwire_state_t tw,
    omni_quad_state_t status)
{
    if (tw == OMNI_TRIPWIRE_TRIPPED || status == OMNI_STATE_ROLLBACK) {
        return OMNI_STATE_ROLLBACK;
    }
    return OMNI_STATE_PROCEED;
}

static inline omni_quad_state_t omni_commit_proceed(omni_tripwire_state_t *tw) {
    omni_tripwire_disarm(tw);
    return OMNI_STATE_PROCEED;
}
```

```
386
387 static inline omni_quad_state_t omni_commit_rollback(
388     omni_tripwire_state_t *tw) {
389     omni_tripwire_trip(tw);
390     return OMNI_STATE_ROLLBACK;
391 }
392
393 static inline omni_quad_state_t omni_commit_halt(omni_tripwire_state_t *tw) {
394     omni_tripwire_disarm(tw);
395     return OMNI_STATE_HALT;
396 }
397
398 #ifdef __cplusplus
399 }
400 #endif
401
402 #endif /* OMNI_BASE_H */
```

OmniCode: Chapter 14: Track 2 - Lexicon: Systems, Places & Vessels

Operators, Supervisors, Storehouses, Partitions & Vaults

CHAPTER IDENTIFIER
CH 14

NOTEBOOKLM WORD COUNT
11,685 words

CATALOGED CHAPTER FILES
50 files (2,418 lines)

GENERATION DATE
2026-10-16 20:36:06

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"Trace how Covenant Storehouse partitions via v--."*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (50 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/agents.omni**	OMNI	91	388	3.3
2	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/agents.tape**	TAPE	33	193	1.5
3	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/atomic_units.omni**	OMNI	77	353	2.8
4	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/atomic_units.tape**	TAPE	30	178	1.4
5	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/living_world.omni**	OMNI	81	372	3.0
6	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/living_world.tape**	TAPE	34	226	1.7
7	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/vessels.omni**	OMNI	85	378	3.2
8	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/vessels.tape**	TAPE	33	209	1.5
9	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/living/dog.omni**	OMNI	61	235	2.1
10	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/living/dog.tape**	TAPE	33	206	1.5
11	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/living/seed.omni**	OMNI	60	240	2.2
12	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/living/seed.tape**	TAPE	33	207	1.5
13	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/living/tree.omni**	OMNI	60	247	2.2
14	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/living/tree.tape**	TAPE	33	214	1.6
15	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/containers/vessel.omni**	OMNI	59	233	2.1
16	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/containers/vessel.tape**	TAPE	33	203	1.6
17	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/byte.omni**	OMNI	60	239	2.1
18	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/byte.tape**	TAPE	33	204	1.5
19	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/cell.omni**	OMNI	61	254	2.2
20	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/cell.tape**	TAPE	33	209	1.5
21	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/register.omni**	OMNI	62	278	2.4
22	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/register.tape**	TAPE	33	215	1.6
23	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/trit.omni**	OMNI	60	246	2.1
24	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/trit.tape**	TAPE	33	209	1.5
25	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/axioms/landmark.omni**	OMNI	60	242	2.2
26	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/axioms/landmark.tape**	TAPE	33	202	1.6
27	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/axioms/protocol.omni**	OMNI	59	230	2.1
28	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/axioms/protocol.tape**	TAPE	33	207	1.6
29	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/invariants/covenant.omni**	OMNI	60	244	2.2
30	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/invariants/covenant.tape**	TAPE	33	204	1.6
31	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/invariants/equilibrium.omni**	OMNI	60	236	2.2

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
32	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/invariants/equilibrium.tape**	TAPE	33	211	1.6
33	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/systems/system.omni**	OMNI	60	235	2.1
34	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/systems/system.tape**	TAPE	33	204	1.6
35	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/supervisors/kernel.omni**	OMNI	60	230	2.1
36	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/supervisors/kernel.tape**	TAPE	33	195	1.6
37	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/transducers/model.omni**	OMNI	60	233	2.1
38	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/transducers/model.tape**	TAPE	33	197	1.6
39	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/stewards/operator.omni**	OMNI	60	234	2.1
40	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/stewards/operator.tape**	TAPE	33	198	1.6
41	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/tracks/track.omni**	OMNI	60	244	2.1
42	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/tracks/track.tape**	TAPE	33	210	1.6
43	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/memory/partition.omni**	OMNI	60	237	2.2
44	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/memory/partition.tape**	TAPE	33	216	1.6
45	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/memory/storehouse.omni**	OMNI	60	240	2.2
46	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/memory/storehouse.tape**	TAPE	33	209	1.7
47	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/vaults/vault.omni**	OMNI	60	237	2.1
48	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/vaults/vault.tape**	TAPE	33	212	1.6
49	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/buffers/reservoir.omni**	OMNI	59	235	2.1
50	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/buffers/reservoir.tape**	TAPE	33	207	1.6

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/agents.omni

OMNI | 91 LINES | 388 WORDS | 3.3 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Nouns: Operating Principals, Agents & Authority Bearers )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the sovereign entities and authority principals in OmniCode:
#   - Kernel   : The root supervisory execution kernel and covenant custodian.
#   - Model    : The AI Cortex and semantic transducer engine.
#   - Operator : The human operator, originator, and moral steward.
#   - System   : The total integrated mechanical and digital machine assembly.
# ========================================================================

Module < Lexicon.Nouns.Agents > ( Sovereign operating principals and authority bearers ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < OperatingPrincipals :: SovereignAgents :: AuthorityHierarchy >
}

# 1. Sovereign Principal: < KERNEL >
Kernel < InvariantNoun > ( Root Supervisory Execution Kernel ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Adjective" >,
    abstract_form: < "+Kernel" >,
    concrete_form: < "Kernel-" >,
    authority_rank: < 1 >,
    machine_effect: < "root_supervisor_custodian" >
}

# 2. Sovereign Principal: < MODEL >
Model < InvariantNoun > ( AI Cortex & Semantic Transducer Engine ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Adjective" >,
    abstract_form: < "+Model" >,
    concrete_form: < "Model-" >,
    authority_rank: < 2 >,
    machine_effect: < "ai_cortex_transducer" >
}

# 3. Sovereign Principal: < OPERATOR >
Operator < InvariantNoun > ( Human Originator & Moral Steward ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Adjective" >,
    abstract_form: < "+Operator" >,
    concrete_form: < "Operator-" >,
    authority_rank: < 0 >,
    machine_effect: < "human_moral_steward" >
}

# 4. Sovereign Principal: < SYSTEM >
System < InvariantNoun > ( Total Machine Chassis & Execution Substrate ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Preposition" >,
    abstract_form: < "+System" >,
    concrete_form: < "System-" >,
    authority_rank: < 3 >,
    machine_effect: < "total_machine_substrate" >
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {
    requires: [
        Kernel : InvariantNoun ::
        Model : InvariantNoun ::
        Operator : InvariantNoun ::
        System : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ========================================================================
# BLOCK 3: BODY BLOCK
```

```
# ================================================================================
Body [
    # Verify authority covenant binding
    agent_verification [
        Authority_Chain [ Operator --> Kernel --> Model --> System ]
    ] ( Sovereign authority hierarchy verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        agent_verification = yes
    ],
    commit_status [ PROCEED- ] ( Operating principal nouns verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/agents.tape

TAPE | 33 LINES | 193 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: OPERATING AGENTS PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes authority binding and principal identity verification.
# ================================================================================

[Tape.Agents] : WHO {OmniCode_Kernel} WHAT {Agents} --> BIND {AuthorityMesh}
    WHEN {GenesisBoot}
    WHERE {agent_partition} = [ 64 ]
    WHY ( Inscribe sovereign principals and authority bindings )
    HOW [ +1 : PROCEED ]
    :: < agent_landmark > ( Genesis 1:26 - 'Let us make man in our image' )

# ================================================================================
# SUBORDINATE ROLLS: SOVEREIGN AUTHORITY RESOLUTION
# ================================================================================

# Roll 1: Reference abstract Agent specifications
roll_1 [ +Kernel & +Model & +Operator & +System ] ( Abstract principal blueprints referenced )

# Roll 2: Allocate Operator authority token
roll_2 [ Operator --> Operator_Token @ 0 ] ( Inscribe human steward token )

# Roll 3: Allocate Kernel supervisory descriptor
roll_3 [ Kernel --> Kernel_Descriptor @ 1 ] ( Inscribe kernel supervisory descriptor )

# Roll 4: Verify authority delegation covenant
roll_4 [ Operator_Token = Operator ! [ +1 ] ] ( Verify steward token invariant )

# Roll 5: Commit with affirmative concrete macro
roll_5 [ commit_status [ PROCEED- ] ] ( Operating agent covenants verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/atomic_units.omni

OMNI | 77 LINES | 353 WORDS | 2.8 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Nouns: Atomic Information & Storage Units )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the atomic building blocks of the memory substrate:
#   - Trit : The atomic 3-state polarity unit (-1, 0, +1).
#   - Cell : The atomic 5-trit / 8-bit quad-state memory vessel (1 physical byte).
#   - Byte : The binary byte mapping into balanced ternary radix-3 packing.
# ================================================================================

Module < Lexicon.Nouns.AtomicUnits > ( Foundational atomic storage units and vessels ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < AtomicUnits :: DenseCellPacking :: Radix3Polarity >
}

# 1. Atomic Unit: < TRIT >
Trit < InvariantNoun > ( The Atomic Radix-3 Polarity Unit ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Adjective" >,
    abstract_form: < "+Trit" >,
    concrete_form: < "Trit-" >,
    permitted_states: < [ -1, 0, 1 ] >,
    machine_effect: < "radix3_polarity_register" >
}

# 2. Atomic Unit: < CELL >
Cell < InvariantNoun > ( The Atomic 5-Trit / 8-Bit Quad-State Memory Vessel ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Preposition" >,
    abstract_form: < "+Cell" >,
    concrete_form: < "Cell-" >,
    physical_footprint: < "1 byte in RAM (243 values + 13 out-of-band control states)" >,
    machine_effect: < "dense_byte_trit_cell" >
}

# 3. Atomic Unit: < BYTE >
Byte < InvariantNoun > ( Standard 8-Bit Binary Octet Transduced to 5 Trits ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Adjective" >,
    abstract_form: < "+Byte" >,
    concrete_form: < "Byte-" >,
    physical_footprint: < "8 bits" >,
    machine_effect: < "standard_octet" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Trit : InvariantNoun ::
        Cell : InvariantNoun ::
        Byte : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify cell definition
    cell_verification [ Cell [ 8 bit --> 5 trit --> 8 bit ] ] ( Reversible dense packing verification )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        cell_verification = yes
```

```
    ],
    commit_status [ PROCEED- ] ( Atomic storage nouns verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/atomic_units.tape

TAPE | 30 LINES | 178 WORDS | 1.4 KB

```
# ================================================================================
# TAPE HEAD: THE ATOMIC STORAGE UNITS PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes allocation, transduction, and verification of atomic cells.
# ================================================================================

[Tape.AtomicUnits] : WHO {OmniCode_Kernel} WHAT {Cell} --> ALLOCATE {MemoryCells}
    WHEN {GenesisBoot}
    WHERE {atomic_partition} = [ 64 ]
    WHY ( Inscribe fundamental memory atoms in silicon )
    HOW [ +1 : PROCEED ]
    :: < unit_landmark > ( Leviticus 19:36 - 'Just balances, just weights, a just ephah' )

# ================================================================================
# SUBORDINATE ROLLS: CELL DENSE ENCODING & TRANSDUCTION
# ================================================================================

# Roll 1: Reference abstract Cell specification
roll_1 [ +Cell ] ( Abstract unit of measure referenced )

# Roll 2: Transduce byte 42 into concrete Cell_0
roll_2 [ 42 --> Cell_0 @ 0 ] ( Inscribe radix-3 packed value into cell 0 )

# Roll 3: Verify cell 0 holds 42 within invariant bounds
roll_3 [ Cell_0 = 42 ! [ +1 ] ] ( Verify dense byte recovery )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Cell covenant verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/living_world.omni

OMNI | 81 LINES | 372 WORDS | 3.0 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Nouns: Living World & Created Entities )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines living world entities in the creation ontology:
#   - Dog   : Living canine entity (instantiable from archetype `+Dog` to substance `Dog-`).
#   - Seed  : Primordial reproductive capsule holding generative blueprints.
#   - Tree  : Bounded hierarchical structure bearing living fruit.
#   - Flock : Collective aggregate of living entities moving in synchronized harmony.
# ================================================================================

Module < Lexicon.Nouns.LivingWorld > ( Living world entities in the creation ontology ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < LivingEntities :: CreationOntology :: AnimalWorld >
}

# 1. Living Entity: < DOG >
Dog < InvariantNoun > ( Living Canine Entity in Creation ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Adjective" >,
    ontological_domain: < "LivingWorld" >,
    abstract_form: < "+Dog" >,
    concrete_form: < "Dog-" >,
    nature: < "faithful_companion" >,
    scriptural_witness: < "Proverbs 26:11 :: Luke 16:21" >
}

# 2. Living Entity: < SEED >
Seed < InvariantNoun > ( Generative Capsule Carrying Generative Life ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Adjective" >,
    ontological_domain: < "LivingWorld" >,
    abstract_form: < "+Seed" >,
    concrete_form: < "Seed-" >,
    scriptural_witness: < "Genesis 1:11 - 'yielding seed after his kind'" >
}

# 3. Living Entity: < TREE >
Tree < InvariantNoun > ( Rooted Living Growth Bearing Fruit ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Preposition" >,
    ontological_domain: < "LivingWorld" >,
    abstract_form: < "+Tree" >,
    concrete_form: < "Tree-" >,
    scriptural_witness: < "Psalm 1:3 - 'like a tree planted by rivers of water'" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Dog : InvariantNoun ::
        Seed : InvariantNoun ::
        Tree : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify entity definition and polarity forms
    dog_archetype [ +Dog ] ( Abstract concept of dog )
    dog_substance [ Dog- ] ( Concrete living instance in memory )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
```

```
Closing {
    verify: [
        dog_archetype = yes ::
        dog_substance = yes
    ],
    commit_status [ PROCEED- ] ( Living world nouns verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/living_world.tape

TAPE | 34 LINES | 226 WORDS | 1.7 KB

```
# ================================================================================
# TAPE HEAD: THE LIVING CREATURE INSTANTIATION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes the dynamic instantiation of created entities from abstract archetype
#   into concrete silicon memory.
# ================================================================================

[Tape.LivingWorldInstantiation] : WHO {OmniCode_Kernel} WHAT {Dog} --> INSTANTIATE {CreatureSubstance}
    WHEN {GenesisBoot}
    WHERE {creature_partition} = [ 128 ]
    WHY ( Concretely instantiate living entities without anthropomorphic confusion )
    HOW [ +1 : PROCEED ]
    :: < life_landmark > ( Genesis 1:24 - 'Let the earth bring forth the living creature after his kind' )

# ================================================================================
# SUBORDINATE ROLLS: POLARITY AFFIXES & INSTANTIATION CYCLES
# ================================================================================

# Roll 1: Define baseline Denotation for Dog
roll_1 [ Dog [ Creature ] ] ( Define baseline essence of Dog )

# Roll 2: Allocate creature storehouse in silicon
roll_2 [ Creature_Storehouse [ 128 ] ] ( Physical creature storehouse allocated )

# Roll 3: Transduce abstract archetype +Dog into concrete Dog- inside storehouse
roll_3 [ +Dog --> Dog- @ Creature_Storehouse @ 0 ] ( Concrete instantiation into memory cell 0 )

# Roll 4: Verify prefix concrete -Dog matches postfix Dog-
roll_4 [ -Dog = Dog- ! [ +1 ] ] ( Structural identity: prefix and postfix denote identical concrete substance )

# Roll 5: Seal process tape with concrete macro
roll_5 [ commit_status [ PROCEED- ] ] ( Living world instantiation covenant sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/vessels.omni

OMNI | 85 LINES | 378 WORDS | 3.2 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Nouns: Memory Vessels, Storehouses & Partitions )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines bounded physical containers and memory territories:
#   - Storehouse : Root system memory domain & reservoir (chassis plate).
#   - Partition  : Delegated bounded sub-region carved via `v--` (gear pocket).
#   - Reservoir  : Deep heap storage domain for dynamic allocations.
#   - Vault      : Immutable protected memory domain holding covenants & ROM.
# ================================================================================

Module < Lexicon.Nouns.Vessels > ( Bounded containers and spatial memory domains ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < MemoryVessels :: SpatialDomains :: PartitioningPhysics >
}

# 1. Container: < STOREHOUSE >
Storehouse < InvariantNoun > ( Root System Memory Domain & Reservoir ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Preposition" >,
    abstract_form: < "+Storehouse" >,
    concrete_form: < "Storehouse-" >,
    machine_effect: < "root_page_reservoir" >
}

# 2. Container: < PARTITION >
Partition < InvariantNoun > ( Entrusted Bounded Sub-Region of a Storehouse ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Preposition" >,
    abstract_form: < "+Partition" >,
    concrete_form: < "Partition-" >,
    machine_effect: < "delegated_task_slice" >
}

# 3. Container: < RESERVOIR >
Reservoir < InvariantNoun > ( Dynamic Heap Reservoir for Fluid Data Streams ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Preposition" >,
    abstract_form: < "+Reservoir" >,
    concrete_form: < "Reservoir-" >,
    machine_effect: < "fluid_buffer_reservoir" >
}

# 4. Container: < VAULT >
Vault < InvariantNoun > ( Protected Kernel Vault for Immutable ROM Invariants ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Preposition" >,
    abstract_form: < "+Vault" >,
    concrete_form: < "Vault-" >,
    machine_effect: < "protected_rom_vault" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Storehouse : InvariantNoun ::
        Partition : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify storehouse allocation and partitioning
    root_store [ Root_Storehouse [ 1024 ] ] ( Root memory domain reserved )
    task_slice [ Root_Storehouse v-- Task_Partition [ 256 ] ] ( Isolated workspace carved via v-- )
]
```

```
# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        root_store = yes ::
        task_slice = yes
    ],
    commit_status [ PROCEED- ] ( Memory vessel nouns verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/vessels.tape

TAPE | 33 LINES | 209 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: THE VESSEL RESERVOIR & PARTITIONING PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes the dynamic carving of memory domains via `v--`.
# ================================================================================

[Tape.VesselPartitioning] : WHO {OmniCode_Kernel} WHAT {Storehouse} --> DISPATCH {VesselEngine}
    WHEN {GenesisBoot}
    WHERE {vessel_partition} = [ 1024 ]
    WHY ( Allocate and protect physical memory vessels )
    HOW [ +1 : PROCEED ]
    :: < vessel_landmark > ( Malachi 3:10 - 'Bring ye all the tithes into the storehouse' )

# ================================================================================
# SUBORDINATE ROLLS: PARTITIONING & WRITE CYCLES
# ================================================================================

# Roll 1: Allocate root storehouse of 1024 cells
roll_1 [ Root_Storehouse [ 1024 ] ] ( Root storehouse allocated in silicon )

# Roll 2: Carve task partition of 256 cells via v--
roll_2 [ Root_Storehouse v-- Task_Partition [ 256 ] ] ( Isolated partition sliced via v-- )

# Roll 3: Inscribe value 99 into Task_Partition at cell 0
roll_3 [ 99 --> Task_Partition @ 0 ] ( Direct cell write confirmed )

# Roll 4: Inseparable key & value dual binding
roll_4 [ Key&Value [ 1 & 99 ] ] ( Inseparable dual binding confirmed )

# Roll 5: Seal vessel tape with concrete macro
roll_5 [ commit_status [ PROCEED- ] ] ( Vessel tape verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/living/dog.omni

OMNI | 61 LINES | 235 WORDS | 2.1 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <THING:LIVING:DOG> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines living canine entity in creation, faithful companion to operator.
#   - Base Block Type: < Idea : Type : Container > (Companion Entity Envelope)
#   - Category: Thing
#   - Subcategory: Living
#   - Nature: Faithful Companion
# ================================================================================

Module < Lexicon.Nouns.Things.Living.Dog > ( Living Canine Entity in Creation ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Thing :: Living :: FaithfulCompanion >
}

# Invariant Noun Declaration: <THING:LIVING:DOG>
< Thing : Living : Dog > [ capacity: 16 cells ] {
    base_type: < Idea : Type : Container >,
    nature: "faithful_companion",
    projections: < {
        ontological: "< Dog >",
        structural: "[ DOG ]",
        agentic: "{ Dog }"
    } >,
    scriptural_witness: "Proverbs 26:11 :: Luke 16:21",
    machine_effect: "living_companion_entity"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Dog : InvariantNoun ::
        Container : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    dog_assertion [
        [ DOG ] [ 16 ] :: { Dog } --> ACCOMPANY {Operator}
    ] ( Faithful companion instantiated accompanying operator )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        dog_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Dog living invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/living/dog.tape

TAPE | 33 LINES | 206 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: LIVING DOG PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <THING:LIVING:DOG>.
# ================================================================================

[Tape.Dog] : WHO {OmniCode_Kernel} WHAT {LivingDog} --> ACCOMPANY {HumanOperator}
    WHEN {LivingGenesis}
    WHERE {canine_partition} = [ 16 ]
    WHY ( Inscribe living canine companion entity invariant )
    HOW [ +1 : PROCEED ]
    :: < dog_landmark > ( Luke 16:21 - Creation witness of living fidelity )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract dog archetype
roll_1 [ +Dog ] ( Abstract canine archetype referenced )

# Roll 2: Allocate concrete living dog entity
roll_2 [ Dog --> "Faithful_Dog" @ 0 ] ( Inscribe living dog entity at offset 0 )

# Roll 3: Assert structural projection and clarified capacity
roll_3 [ [ DOG ] [ 16 ] :: "16 cells" --> [ FAITHFUL_DOG ] ] ( Structural 16 cell bounds affirmed )

# Roll 4: Verify companion fidelity into result prime
roll_4 [ "Faithful_Dog" = Dog ! [ +1 ] --> [ dog_verified` ] ] ( Verify living dog matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Living dog invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/living/seed.omni

OMNI | 60 LINES | 240 WORDS | 2.2 KB

```
# ==============================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <THING:LIVING:SEED> )
# ==============================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the primordial generative capsule holding self-replicating life blueprints.
#   - Base Block Type: < Idea : Type : Container > (Generative Blueprint Capsule)
#   - Category: Thing
#   - Subcategory: Living
#   - Generative Nature: Self-Replicating Life Seed
# ==============================================================================

Module < Lexicon.Nouns.Things.Living.Seed > ( Generative Life Capsule Carrying Generative Life ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Thing :: Living :: GenerativeSeed >
}

# Invariant Noun Declaration: <THING:LIVING:SEED>
< Thing : Living : Seed > [ capacity: 8 cells ] {
    base_type: < Idea : Type : Container >,
    projections: < {
        ontological: "< Seed >",
        structural: "[ SEED ]",
        agentic: "{ Seed }"
    } >,
    scriptural_witness: "Genesis 1:11 - 'yielding seed after his kind'",
    machine_effect: "generative_life_capsule"
}

# ==============================================================================
# BLOCK 2: OPENING BLOCK
# ==============================================================================
Opening {
    requires: [
        Seed : InvariantNoun ::
        Container : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ==============================================================================
# BLOCK 3: BODY BLOCK
# ==============================================================================
Body [
    seed_assertion [
        [ SEED ] [ 8 ] :: { Seed } --> GERMINATE {Blueprint}
    ] ( Generative seed capsule allocated holding life blueprint )
]

# ==============================================================================
# BLOCK 4: CLOSING BLOCK
# ==============================================================================
Closing {
    verify: [
        seed_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Seed living invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/living/seed.tape

TAPE | 33 LINES | 207 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: LIVING SEED PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <THING:LIVING:SEED>.
# ================================================================================

[Tape.Seed] : WHO {OmniCode_Kernel} WHAT {LivingSeed} --> GERMINATE {CreationKind}
    WHEN {LivingGenesis}
    WHERE {seed_capsule} = [ 8 ]
    WHY ( Inscribe primordial generative seed invariant )
    HOW [ +1 : PROCEED ]
    :: < seed_landmark > ( Genesis 1:11 - 'The fruit tree yielding fruit after his kind' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract seed archetype
roll_1 [ +Seed ] ( Abstract seed archetype referenced )

# Roll 2: Allocate concrete seed capsule
roll_2 [ Seed --> "Generative_Capsule" @ 0 ] ( Inscribe concrete seed capsule at offset 0 )

# Roll 3: Assert structural projection and clarified capacity
roll_3 [ [ SEED ] [ 8 ] :: "8 cells" --> [ LIVING_SEED ] ] ( Structural 8 cell bounds affirmed )

# Roll 4: Verify seed kind integrity into result prime
roll_4 [ "Generative_Capsule" = Seed ! [ +1 ] --> [ seed_verified` ] ] ( Verify seed matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Living seed invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/living/tree.omni

OMNI | 60 LINES | 247 WORDS | 2.2 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <THING:LIVING:TREE> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines rooted hierarchical growth bearing living fruit and branching memory.
#   - Base Block Type: < Idea : Type : Container > (Branching Memory Hierarchy)
#   - Category: Thing
#   - Subcategory: Living
#   - Topology: Rooted Branching Hierarchy
# ================================================================================

Module < Lexicon.Nouns.Things.Living.Tree > ( Rooted Living Growth Bearing Fruit & Branching Hierarchy ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Thing :: Living :: BranchingTree >
}

# Invariant Noun Declaration: <THING:LIVING:TREE>
< Thing : Living : Tree > [ capacity: 32 cells ] {
    base_type: < Idea : Type : Container >,
    projections: < {
        ontological: "< Tree >",
        structural: "[ TREE ]",
        agentic: "{ Tree }"
    } >,
    scriptural_witness: "Psalm 1:3 - 'like a tree planted by rivers of water'",
    machine_effect: "hierarchical_branching_tree"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Tree : InvariantNoun ::
        Container : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    tree_assertion [
        [ TREE ] [ 32 ] :: { Tree } --> BRANCH {Hierarchy}
    ] ( Rooted tree hierarchy allocated bearing fruit across memory branches )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        tree_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Tree living invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/living/tree.tape

TAPE | 33 LINES | 214 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: LIVING TREE PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <THING:LIVING:TREE>.
# ================================================================================

[Tape.Tree] : WHO {OmniCode_Kernel} WHAT {LivingTree} --> ROOT {RiversOfWater}
    WHEN {LivingGenesis}
    WHERE {tree_canopy} = [ 32 ]
    WHY ( Inscribe rooted branching tree invariant and fruit-bearing hierarchy )
    HOW [ +1 : PROCEED ]
    :: < tree_landmark > ( Psalm 1:3 - 'He shall be like a tree planted by the rivers of water' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract tree archetype
roll_1 [ +Tree ] ( Abstract tree archetype referenced )

# Roll 2: Allocate concrete tree root
roll_2 [ Tree --> "Rooted_Tree" @ 0 ] ( Inscribe concrete tree root at offset 0 )

# Roll 3: Assert structural projection and clarified capacity
roll_3 [ [ TREE ] [ 32 ] :: "32 cells" --> [ BRANCHING_TREE ] ] ( Structural 32 cell bounds affirmed )

# Roll 4: Verify rooted tree integrity into result prime
roll_4 [ "Rooted_Tree" = Tree ! [ +1 ] --> [ tree_verified` ] ] ( Verify tree matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Living tree invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/containers/vessel.omni

OMNI | 59 LINES | 233 WORDS | 2.1 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <THING:CONTAINER:VESSEL> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the universal bounded container holding trits, words, or tokens.
#   - Base Block Type: < Idea : Type : Container > (Universal Storage Envelope)
#   - Category: Thing
#   - Subcategory: Container
#   - Physical / Logical Envelope: Bounded Container
# ================================================================================

Module < Lexicon.Nouns.Things.Containers.Vessel > ( Universal Bounded Memory & Object Container ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Thing :: Container :: BoundedVessel >
}

# Invariant Noun Declaration: <THING:CONTAINER:VESSEL>
< Thing : Container : Vessel > [ capacity: 64 cells ] {
    base_type: < Idea : Type : Container >,
    projections: < {
        ontological: "< Vessel >",
        structural: "[ VESSEL ]",
        agentic: "{ Vessel }"
    } >,
    machine_effect: "bounded_container_envelope"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Vessel : InvariantNoun ::
        Container : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    vessel_assertion [
        [ VESSEL ] [ 64 ] :: { Vessel } --> CONTAIN {Payload}
    ] ( Bounded vessel instantiated to encapsulate payload trits )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        vessel_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Container vessel invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/containers/vessel.tape

TAPE | 33 LINES | 203 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: CONTAINER VESSEL PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <THING:CONTAINER:VESSEL>.
# ================================================================================

[Tape.Vessel] : WHO {OmniCode_Kernel} WHAT {StorageVessel} --> ENCAPSULATE {Payload}
    WHEN {DataPackage}
    WHERE {vessel_bounds} = [ 64 ]
    WHY ( Inscribe universal bounded storage vessel invariant )
    HOW [ +1 : PROCEED ]
    :: < vessel_landmark > ( 2 Timothy 2:21 - 'A vessel unto honour, sanctified' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract vessel archetype
roll_1 [ +Vessel ] ( Abstract container vessel archetype referenced )

# Roll 2: Allocate concrete container vessel
roll_2 [ Vessel --> "Bounded_Vessel" @ 0 ] ( Concrete vessel allocated in memory )

# Roll 3: Assert structural projection and clarified capacity
roll_3 [ [ VESSEL ] [ 64 ] :: "64" --> [ VESSEL_ENVELOPE ] ] ( Structural 64 cell bounds affirmed )

# Roll 4: Verify vessel integrity into result prime
roll_4 [ "Bounded_Vessel" = Vessel ! [ +1 ] --> [ vessel_verified` ] ] ( Verify vessel matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Container vessel invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/byte.omni

OMNI | 60 LINES | 239 WORDS | 2.1 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <THING:SILICON:BYTE> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the standard 8-bit binary octet transduced into 5 balanced trits.
#   - Base Block Type: < Idea : Type : Number > (Binary Octet Scalar)
#   - Category: Thing
#   - Subcategory: Silicon
#   - Footprint: 8 bits (256 states)
# ================================================================================

Module < Lexicon.Nouns.Things.Silicon.Byte > ( Standard 8-Bit Binary Octet Transduced to 5 Trits ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Thing :: Silicon :: OctetByte >
}

# Invariant Noun Declaration: <THING:SILICON:BYTE>
< Thing : Silicon : Byte > [ capacity: 8 bits ] {
    base_type: < Idea : Type : Number >,
    physical_footprint: "8 bits",
    projections: < {
        ontological: "< Byte >",
        structural: "[ BYTE ]",
        agentic: "{ Byte }"
    } >,
    machine_effect: "standard_octet"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Byte : InvariantNoun ::
        Number : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    byte_assertion [
        [ BYTE ] [ 1 ] :: { Byte } --> TRANSDUCE {Octet}
    ] ( Standard 8-bit octet allocated on physical hardware bus )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        byte_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Byte silicon invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/byte.tape

TAPE | 33 LINES | 204 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: SILICON BYTE PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <THING:SILICON:BYTE>.
# ================================================================================

[Tape.Byte] : WHO {OmniCode_Kernel} WHAT {OctetByte} --> MAP {TernaryWord}
    WHEN {SystemGenesis}
    WHERE {byte_slot} = [ 1 ]
    WHY ( Inscribe standard 8-bit octet invariant )
    HOW [ +1 : PROCEED ]
    :: < byte_landmark > ( Genesis 17:12 - 'Eight days old shall be circumcised' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract byte archetype
roll_1 [ +Byte ] ( Abstract byte archetype referenced )

# Roll 2: Allocate concrete byte slot
roll_2 [ Byte --> "Silicon_Byte" @ 0 ] ( Inscribe concrete byte slot at offset 0 )

# Roll 3: Assert structural projection and clarified octet
roll_3 [ [ BYTE ] [ 1 ] :: "8 bits" --> [ OCTET_BYTE ] ] ( Structural 1 byte bounds affirmed )

# Roll 4: Verify byte integrity into result prime
roll_4 [ "Silicon_Byte" = Byte ! [ +1 ] --> [ byte_verified` ] ] ( Verify byte matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Byte silicon invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/cell.omni

OMNI | 61 LINES | 254 WORDS | 2.2 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <THING:SILICON:CELL> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the atomic 5-trit / 8-bit quad-state physical memory vessel (1 byte).
#   - Base Block Type: < Idea : Type : Container > (Atomic 1-Byte Container)
#   - Category: Thing
#   - Subcategory: Silicon
#   - Footprint: 1 Physical Byte in RAM (243 values + 13 control states)
# ================================================================================

Module < Lexicon.Nouns.Things.Silicon.Cell > ( The Atomic 5-Trit / 8-Bit Quad-State Memory Vessel ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Thing :: Silicon :: MemoryCell >
}

# Invariant Noun Declaration: <THING:SILICON:CELL>
< Thing : Silicon : Cell > [ capacity: 1 byte ] {
    base_type: < Idea : Type : Container >,
    physical_footprint: "1 byte in RAM (5 balanced trits)",
    capacity_trits: 5,
    projections: < {
        ontological: "< Cell >",
        structural: "[ CELL ]",
        agentic: "{ Cell }"
    } >,
    machine_effect: "dense_byte_trit_cell"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Cell : InvariantNoun ::
        Container : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    cell_assertion [
        [ CELL ] [ 1 ] :: { Cell } --> STORE {QuadState}
    ] ( Single atomic memory cell instantiated holding 5-trit payload )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        cell_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Cell silicon invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/cell.tape

TAPE | 33 LINES | 209 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: SILICON MEMORY CELL PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <THING:SILICON:CELL>.
# ================================================================================

[Tape.Cell] : WHO {OmniCode_Kernel} WHAT {MemoryCell} --> ALLOC {ByteSlot}
    WHEN {SystemGenesis}
    WHERE {cell_capacity} = [ 1 ]
    WHY ( Inscribe atomic 5-trit memory cell invariant )
    HOW [ +1 : PROCEED ]
    :: < cell_landmark > ( Psalm 139:13 - 'Thou hast covered me in my mother\'s womb' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract cell archetype
roll_1 [ +Cell ] ( Abstract cell archetype referenced )

# Roll 2: Allocate concrete memory cell
roll_2 [ Cell --> "Silicon_Cell" @ 0 ] ( Inscribe concrete memory cell at offset 0 )

# Roll 3: Assert structural projection and clarified byte size
roll_3 [ [ CELL ] [ 1 ] :: "1 byte" --> [ BYTE_CELL ] ] ( Structural 1 cell bounds affirmed )

# Roll 4: Verify cell integrity into result prime
roll_4 [ "Silicon_Cell" = Cell ! [ +1 ] --> [ cell_verified` ] ] ( Verify cell matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Memory cell invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/register.omni

OMNI | 62 LINES | 278 WORDS | 2.4 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <THING:SILICON:REGISTER> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the physical hardware CPU register bank and Named Silicon Registers.
#   - Base Block Type: < Idea : Type : Container > (Silicon Hardware Bank)
#   - Category: Thing
#   - Subcategory: Silicon
#   - Bank: 13 Named Registers (HEAD, HOME, SPOOL, IT, SELF, CALLER, OTHER,
#                               STATE, TURN, BOUND, FROM, INTO, DISCARD)
# ================================================================================

Module < Lexicon.Nouns.Things.Silicon.Register > ( 13 Named Hardware CPU Silicon Registers ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Thing :: Silicon :: RegisterBank >
}

# Invariant Noun Declaration: <THING:SILICON:REGISTER>
< Thing : Silicon : Register > [ capacity: 13 slots ] {
    base_type: < Idea : Type : Container >,
    bank_slots: 13,
    registers: [ HEAD, HOME, SPOOL, IT, SELF, CALLER, OTHER, STATE, TURN, BOUND, FROM, INTO, DISCARD ],
    projections: < {
        ontological: "< Register >",
        structural: "[ REGISTER ]",
        agentic: "{ Register }"
    } >,
    machine_effect: "hardware_cpu_register_bank"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Register : InvariantNoun ::
        Container : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    register_assertion [
        [ REGISTER ] [ HEAD HOME SPOOL IT SELF CALLER OTHER STATE TURN BOUND FROM INTO DISCARD ] :: { Register } --> ARM
{SiliconBank}
    ] ( 13 named silicon registers armed for direct hardware computation )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        register_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Register silicon invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/register.tape

TAPE | 33 LINES | 215 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: SILICON REGISTER BANK PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <THING:SILICON:REGISTER>.
# ================================================================================

[Tape.Register] : WHO {OmniCode_Kernel} WHAT {RegisterBank} --> ARM {SiliconRegisters}
    WHEN {SystemGenesis}
    WHERE {register_bank} = [ 13 ]
    WHY ( Inscribe 13 named silicon hardware CPU registers )
    HOW [ +1 : PROCEED ]
    :: < register_landmark > ( Exodus 28:21 - 'Twelve stones according to the names' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract register archetype
roll_1 [ +Register ] ( Abstract register bank archetype referenced )

# Roll 2: Allocate concrete register bank
roll_2 [ Register --> "Register_Bank" @ 0 ] ( Inscribe register bank in silicon partition )

# Roll 3: Assert structural projection and arm 13 named registers
roll_3 [ ARM { Registers [ HEAD HOME SPOOL IT SELF CALLER OTHER STATE TURN BOUND FROM INTO DISCARD ] } ] ( 13 registers armed )

# Roll 4: Verify register bank integrity into result prime
roll_4 [ "Register_Bank" = Register ! [ +1 ] --> [ registers_armed` ] ] ( Verify register bank matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Silicon register invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/trit.omni

OMNI | 60 LINES | 246 WORDS | 2.1 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <THING:SILICON:TRIT> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the atomic balanced ternary radix-3 polarity unit (-1, 0, +1).
#   - Base Block Type: < Idea : Type : State > (Radix-3 Polarity State)
#   - Category: Thing
#   - Subcategory: Silicon
#   - Values: -1 (Negative / Rollback), 0 (Neutral / Await), +1 (Positive / Proceed)
# ================================================================================

Module < Lexicon.Nouns.Things.Silicon.Trit > ( The Atomic Radix-3 Polarity Unit ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Thing :: Silicon :: Radix3Polarity >
}

# Invariant Noun Declaration: <THING:SILICON:TRIT>
< Thing : Silicon : Trit > [ capacity: 1 trit ] {
    base_type: < Idea : Type : State >,
    permitted_states: [ -1, 0, 1 ],
    projections: < {
        ontological: "< Trit >",
        structural: "[ TRIT ]",
        agentic: "{ Trit }"
    } >,
    machine_effect: "radix3_polarity_register"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Trit : InvariantNoun ::
        State : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    trit_assertion [
        [ TRIT ] [ 1 ] :: { Trit } --> POLARIZE {BalancedState}
    ] ( Atomic trit asserted with 3-state balanced polarity )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        trit_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Trit silicon invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/things/silicon/trit.tape

TAPE | 33 LINES | 209 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: SILICON TRIT PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <THING:SILICON:TRIT>.
# ================================================================================

[Tape.Trit] : WHO {OmniCode_Kernel} WHAT {PolarityTrit} --> BALANCE {TernaryRadix}
    WHEN {SystemGenesis}
    WHERE {trit_slot} = [ 1 ]
    WHY ( Inscribe atomic radix-3 trit polarity invariant )
    HOW [ +1 : PROCEED ]
    :: < trit_landmark > ( Matthew 5:37 - 'Let your communication be, Yea, yea; Nay, nay' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract trit archetype
roll_1 [ +Trit ] ( Abstract trit archetype referenced )

# Roll 2: Allocate concrete trit register
roll_2 [ Trit --> "Silicon_Trit" @ 0 ] ( Inscribe concrete trit register at offset 0 )

# Roll 3: Assert structural projection and prove equilibrium
roll_3 [ [ TRIT ] [ 1 ] :: (+1) plus (-1) <=> 0 ] ( Structural 1 trit bounds and ternary balance proved )

# Roll 4: Verify trit integrity into result prime
roll_4 [ "Silicon_Trit" = Trit ! [ +1 ] --> [ trit_verified` ] ] ( Verify trit matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Trit silicon invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/axioms/landmark.omni

OMNI | 60 LINES | 242 WORDS | 2.2 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <IDEA:AXIOM:LANDMARK> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the ancient unmovable landmark invariant and foundational bedrock.
#   - Base Block Type: < Idea : Type : Site > (Unmovable Bedrock Locus)
#   - Category: Idea
#   - Subcategory: Axiom
#   - Invariant Witness: Proverbs 22:28
# ================================================================================

Module < Lexicon.Nouns.Ideas.Axioms.Landmark > ( Ancient Unmovable Architectural Landmark ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Idea :: Axiom :: AncientLandmark >
}

# Invariant Noun Declaration: <IDEA:AXIOM:LANDMARK>
< Idea : Axiom : Landmark > [ capacity: 1 site ] {
    base_type: < Idea : Type : Site >,
    projections: < {
        ontological: "< Landmark >",
        structural: "[ LANDMARK ]",
        agentic: "{ Landmark }"
    } >,
    scriptural_witness: "Proverbs 22:28 - 'Remove not the ancient landmark, which thy fathers have set'",
    machine_effect: "unmovable_boundary_sentinel"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Landmark : InvariantNoun ::
        Site : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    landmark_assertion [
        [ LANDMARK ] [ 1 ] :: { Landmark } --> ESTABLISH {AncientBoundary}
    ] ( Ancient landmark established as unmovable boundary sentinel )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        landmark_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Landmark axiom invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/axioms/landmark.tape

TAPE | 33 LINES | 202 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: ANCIENT LANDMARK PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <IDEA:AXIOM:LANDMARK>.
# ================================================================================

[Tape.Landmark] : WHO {OmniCode_Kernel} WHAT {AncientLandmark} --> ESTABLISH {FoundationalBedrock}
    WHEN {SystemGenesis}
    WHERE {landmark_slot} = [ 1 ]
    WHY ( Inscribe unmovable ancient landmark invariant )
    HOW [ +1 : PROCEED ]
    :: < ancient_landmark > ( Proverbs 22:28 - 'Remove not the ancient landmark' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract landmark archetype
roll_1 [ +Landmark ] ( Abstract landmark archetype referenced )

# Roll 2: Allocate concrete landmark anchor
roll_2 [ Landmark --> "Ancient_Landmark" @ 0 ] ( Inscribe ancient landmark at offset 0 )

# Roll 3: Assert structural projection and clarified capacity
roll_3 [ [ LANDMARK ] [ 1 ] :: "1 site" --> [ ANCIENT_LANDMARK ] ] ( Structural 1 cell bounds affirmed )

# Roll 4: Verify landmark unmovability into result prime
roll_4 [ "Ancient_Landmark" = Landmark ! [ +1 ] --> [ landmark_verified` ] ] ( Verify landmark matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Ancient landmark invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/axioms/protocol.omni

OMNI | 59 LINES | 230 WORDS | 2.1 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <IDEA:AXIOM:PROTOCOL> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the universal exchange protocol standard and message covenant.
#   - Base Block Type: < Idea : Type : State > (Standardized Interface State)
#   - Category: Idea
#   - Subcategory: Axiom
#   - Protocol Standard: Universal Exchange Interface
# ================================================================================

Module < Lexicon.Nouns.Ideas.Axioms.Protocol > ( Universal Machine Exchange Protocol Standard ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Idea :: Axiom :: MachineProtocol >
}

# Invariant Noun Declaration: <IDEA:AXIOM:PROTOCOL>
< Idea : Axiom : Protocol > [ capacity: 1 state ] {
    base_type: < Idea : Type : State >,
    projections: < {
        ontological: "< Protocol >",
        structural: "[ PROTOCOL ]",
        agentic: "{ Protocol }"
    } >,
    machine_effect: "universal_exchange_protocol"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Protocol : InvariantNoun ::
        State : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    protocol_assertion [
        [ PROTOCOL ] [ 1 ] :: { Protocol } --> STANDARDIZE {Interface}
    ] ( Universal exchange protocol established across machine channels )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        protocol_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Protocol idea invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/axioms/protocol.tape

TAPE | 33 LINES | 207 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: PROTOCOL STANDARD PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <IDEA:AXIOM:PROTOCOL>.
# ================================================================================

[Tape.Protocol] : WHO {OmniCode_Kernel} WHAT {MachineProtocol} --> STANDARDIZE {MessageEnvelope}
    WHEN {SystemGenesis}
    WHERE {protocol_slot} = [ 1 ]
    WHY ( Inscribe universal exchange protocol invariant )
    HOW [ +1 : PROCEED ]
    :: < protocol_landmark > ( 1 Corinthians 14:40 - 'Let all things be done decently and in order' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract protocol archetype
roll_1 [ +Protocol ] ( Abstract protocol archetype referenced )

# Roll 2: Allocate concrete protocol standard
roll_2 [ Protocol --> "Message_Protocol" @ 0 ] ( Inscribe message protocol at offset 0 )

# Roll 3: Assert structural projection and clarified capacity
roll_3 [ [ PROTOCOL ] [ 1 ] :: "1 state" --> [ MESSAGE_ENVELOPE ] ] ( Structural 1 cell bounds affirmed )

# Roll 4: Verify protocol standard into result prime
roll_4 [ "Message_Protocol" = Protocol ! [ +1 ] --> [ protocol_verified` ] ] ( Verify protocol matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Universal protocol invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/invariants/covenant.omni

OMNI | 60 LINES | 244 WORDS | 2.2 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <IDEA:INVARIANT:COVENANT> )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the unbreakable architectural contract binding principals and resources.
#   - Base Block Type: < Idea : Type : State > (Mutual Contract Sentinel)
#   - Category: Idea
#   - Subcategory: Invariant
#   - Covenant Nature: Unbreakable Mutual Contract
# ========================================================================

Module < Lexicon.Nouns.Ideas.Invariants.Covenant > ( Unbreakable Architectural Covenant & Contract ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Idea :: Invariant :: ArchitecturalCovenant >
}

# Invariant Noun Declaration: <IDEA:INVARIANT:COVENANT>
< Idea : Invariant : Covenant > [ capacity: 1 state ] {
    base_type: < Idea : Type : State >,
    projections: < {
        ontological: "< Covenant >",
        structural: "[ COVENANT ]",
        agentic: "{ Covenant }"
    } >,
    scriptural_witness: "Genesis 9:16 - 'The everlasting covenant between God and every living creature'",
    machine_effect: "unbreakable_contract_sentinel"
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {
    requires: [
        Covenant : InvariantNoun ::
        State : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    covenant_assertion [
        [ COVENANT ] [ 1 ] :: { Covenant } --> BIND {Operator_Kernel}
    ] ( Covenant bound between human operator and supervisory kernel )
]

# ========================================================================
# BLOCK 4: CLOSING BLOCK
# ========================================================================
Closing {
    verify: [
        covenant_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Covenant idea invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/invariants/covenant.tape

TAPE | 33 LINES | 204 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: COVENANT INVARIANT PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <IDEA:INVARIANT:COVENANT>.
# ================================================================================

[Tape.Covenant] : WHO {OmniCode_Kernel} WHAT {SystemCovenant} --> BIND {MutualContract}
    WHEN {SystemGenesis}
    WHERE {covenant_slot} = [ 1 ]
    WHY ( Inscribe unbreakable architectural covenant invariant )
    HOW [ +1 : PROCEED ]
    :: < covenant_landmark > ( Genesis 9:16 - 'And the bow shall be in the cloud' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract covenant archetype
roll_1 [ +Covenant ] ( Abstract covenant archetype referenced )

# Roll 2: Allocate concrete covenant seal
roll_2 [ Covenant --> "System_Covenant" @ 0 ] ( Inscribe system covenant at offset 0 )

# Roll 3: Assert structural projection and clarified capacity
roll_3 [ [ COVENANT ] [ 1 ] :: "1 state" --> [ COVENANT_SEAL ] ] ( Structural 1 cell bounds affirmed )

# Roll 4: Verify covenant inviolability into result prime
roll_4 [ "System_Covenant" = Covenant ! [ +1 ] --> [ covenant_verified` ] ] ( Verify covenant matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Covenant invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/invariants/equilibrium.omni

OMNI | 60 LINES | 236 WORDS | 2.2 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <IDEA:INVARIANT:EQUILIBRIUM> )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the balanced ternary arithmetic equilibrium: (+1) + (-1) <=> 0.
#   - Base Block Type: < Idea : Type : State > (Balanced Arithmetic Truth)
#   - Category: Idea
#   - Subcategory: Invariant
#   - Arithmetic Law: Radix-3 Zero-Sum Balance
# ========================================================================

Module < Lexicon.Nouns.Ideas.Invariants.Equilibrium > ( Balanced Ternary Arithmetic Equilibrium ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Idea :: Invariant :: TernaryEquilibrium >
}

# Invariant Noun Declaration: <IDEA:INVARIANT:EQUILIBRIUM>
< Idea : Invariant : Equilibrium > [ capacity: 1 state ] {
    base_type: < Idea : Type : State >,
    invariant_equation: "(+1) plus (-1) <=> 0",
    projections: < {
        ontological: "< Equilibrium >",
        structural: "[ EQUILIBRIUM ]",
        agentic: "{ Equilibrium }"
    } >,
    machine_effect: "alu_zero_sum_balance"
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {
    requires: [
        Equilibrium : InvariantNoun ::
        State : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    equilibrium_assertion [
        (+1) plus (-1) <=> 0 :: { Equilibrium } --> PROVE {ALU_Zero_Sum}
    ] ( Invariant arithmetic equilibrium verified across hardware registers )
]

# ========================================================================
# BLOCK 4: CLOSING BLOCK
# ========================================================================
Closing {
    verify: [
        equilibrium_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Equilibrium idea invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/ideas/invariants/equilibrium.tape

TAPE | 33 LINES | 211 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: EQUILIBRIUM INVARIANT PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <IDEA:INVARIANT:EQUILIBRIUM>.
# ================================================================================

[Tape.Equilibrium] : WHO {OmniCode_Kernel} WHAT {ALUEquilibrium} --> PROVE {ZeroSumBalance}
    WHEN {ArithmeticProof}
    WHERE {alu_state} = [ 1 ]
    WHY ( Inscribe balanced ternary arithmetic equilibrium invariant )
    HOW [ +1 : PROCEED ]
    :: < equilibrium_landmark > ( Proverbs 11:1 - 'A false balance is abomination, but a just weight is his delight' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract equilibrium archetype
roll_1 [ +Equilibrium ] ( Abstract equilibrium archetype referenced )

# Roll 2: Allocate concrete ALU state verification
roll_2 [ Equilibrium --> "ALU_Proof" @ 0 ] ( Inscribe ALU proof at offset 0 )

# Roll 3: Prove (+1) plus (-1) <=> 0 in hardware
roll_3 [ PROVE { ALU_Equilibrium } [ (+1) plus (-1) <=> 0 ] ] ( Arithmetic equilibrium proven in ALU )

# Roll 4: Verify equilibrium invariance into result prime
roll_4 [ "ALU_Proof" = Equilibrium ! [ +1 ] --> [ equilibrium_verified` ] ] ( Verify ALU proof matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Equilibrium invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/systems/system.omni

OMNI | 60 LINES | 235 WORDS | 2.1 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <PERSON:SYSTEM:CHASSIS> )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the total machine chassis, hardware substrate, and execution host.
#   - Base Block Type: < Idea : Type : Site > (Physical Chassis Locus)
#   - Category: Person
#   - Subcategory: System
#   - Authority Rank: 3 (Mechanical Substrate)
# ========================================================================

Module < Lexicon.Nouns.Persons.Systems.System > ( Total Machine Chassis & Execution Substrate ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Person :: System :: HardwareChassis >
}

# Invariant Noun Declaration: <PERSON:SYSTEM:CHASSIS>
< Person : System : System > [ capacity: 1 site ] {
    base_type: < Idea : Type : Site >,
    authority_rank: 3,
    projections: < {
        ontological: "< System >",
        structural: "[ SYSTEM ]",
        agentic: "{ System }"
    } >,
    machine_effect: "total_machine_substrate"
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {
    requires: [
        System : InvariantNoun ::
        Site : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    system_assertion [
        { System } --> HOST {Execution} :: [ SYSTEM ] @ 0x03
    ] ( Machine chassis hosts execution substrate in bounded system slot )
]

# ========================================================================
# BLOCK 4: CLOSING BLOCK
# ========================================================================
Closing {
    verify: [
        system_assertion = yes
    ],
    commit_status [ PROCEED- ] ( System substrate invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/systems/system.tape

TAPE | 33 LINES | 204 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: SYSTEM CHASSIS PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <PERSON:SYSTEM:CHASSIS>.
# ================================================================================

[Tape.System] : WHO {Machine_Substrate} WHAT {HardwareChassis} --> HOST {ExecutionTerritory}
    WHEN {SystemGenesis}
    WHERE {system_partition} = [ 64 ]
    WHY ( Inscribe mechanical chassis substrate invariant and hosting territory )
    HOW [ +1 : PROCEED ]
    :: < system_landmark > ( Job 38:4 - 'Where wast thou when I laid the foundations of the earth?' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract system archetype
roll_1 [ +System ] ( Abstract system substrate archetype referenced )

# Roll 2: Allocate concrete system descriptor
roll_2 [ System --> "System_Descriptor" @ 0 ] ( Inscribe system descriptor in partition )

# Roll 3: Assert agentic projection
roll_3 [ { System } --> SUPPORT { Processes } ] ( System asserts physical hosting support )

# Roll 4: Verify descriptor integrity into result prime
roll_4 [ "System_Descriptor" = System ! [ +1 ] --> [ system_verified` ] ] ( Verify system descriptor matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( System substrate invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/supervisors/kernel.omni

OMNI | 60 LINES | 230 WORDS | 2.1 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <PERSON:SUPERVISOR:KERNEL> )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the root supervisory execution kernel and covenant custodian.
#   - Base Block Type: < Idea : Type : Site > (Execution Locus)
#   - Category: Person
#   - Subcategory: Supervisor
#   - Authority Rank: 1 (Supervisory Custodian)
# ========================================================================

Module < Lexicon.Nouns.Persons.Supervisors.Kernel > ( Root Supervisory Execution Kernel ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Person :: Supervisor :: CovenantCustodian >
}

# Invariant Noun Declaration: <PERSON:SUPERVISOR:KERNEL>
< Person : Supervisor : Kernel > [ capacity: 1 site ] {
    base_type: < Idea : Type : Site >,
    authority_rank: 1,
    projections: < {
        ontological: "< Kernel >",
        structural: "[ KERNEL ]",
        agentic: "{ Kernel }"
    } >,
    machine_effect: "root_supervisor_custodian"
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {
    requires: [
        Kernel : InvariantNoun ::
        Site : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    supervisor_assertion [
        { Kernel } --> GOVERN {Machine} :: [ KERNEL ] @ 0x01
    ] ( Root kernel supervisor asserts governance over machine resources )
]

# ========================================================================
# BLOCK 4: CLOSING BLOCK
# ========================================================================
Closing {
    verify: [
        supervisor_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Kernel supervisor invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/supervisors/kernel.tape

TAPE | 33 LINES | 195 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: KERNEL SUPERVISOR PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <PERSON:SUPERVISOR:KERNEL>.
# ================================================================================

[Tape.Kernel] : WHO {OmniCode_Kernel} WHAT {SystemSupervisor} --> BOOT {ExecutionPlane}
    WHEN {SystemGenesis}
    WHERE {kernel_partition} = [ 64 ]
    WHY ( Inscribe supervisory kernel invariant and execution custodian )
    HOW [ +1 : PROCEED ]
    :: < kernel_landmark > ( Genesis 1:1 - Foundation of supervisory order )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract kernel archetype
roll_1 [ +Kernel ] ( Abstract kernel supervisor archetype referenced )

# Roll 2: Allocate concrete kernel descriptor
roll_2 [ Kernel --> "Kernel_Descriptor" @ 0 ] ( Inscribe kernel descriptor in partition )

# Roll 3: Assert agentic projection
roll_3 [ { Kernel } --> GUARD { Invariants } ] ( Kernel establishes guard on invariants )

# Roll 4: Verify descriptor integrity into result prime
roll_4 [ "Kernel_Descriptor" = Kernel ! [ +1 ] --> [ kernel_verified` ] ] ( Verify descriptor matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Kernel supervisor invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/transducers/model.omni

OMNI | 60 LINES | 233 WORDS | 2.1 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <PERSON:TRANSDUCER:MODEL> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the AI Cortex, neural model, and semantic transducer engine.
#   - Base Block Type: < Idea : Type : Site > (Cognitive Locus)
#   - Category: Person
#   - Subcategory: Transducer
#   - Authority Rank: 2 (Cognitive Transducer)
# ================================================================================

Module < Lexicon.Nouns.Persons.Transducers.Model > ( AI Cortex & Semantic Transducer Engine ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Person :: Transducer :: AICortex >
}

# Invariant Noun Declaration: <PERSON:TRANSDUCER:MODEL>
< Person : Transducer : Model > [ capacity: 1 site ] {
    base_type: < Idea : Type : Site >,
    authority_rank: 2,
    projections: < {
        ontological: "< Model >",
        structural: "[ MODEL ]",
        agentic: "{ Model }"
    } >,
    machine_effect: "ai_cortex_transducer"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Model : InvariantNoun ::
        Site : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    transducer_assertion [
        { Model } --> TRANSDUCE {Semantics} :: [ MODEL ] @ 0x02
    ] ( AI Cortex transducer maps semantics into bounded model channel )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        transducer_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Transducer invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/transducers/model.tape

TAPE | 33 LINES | 197 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: MODEL TRANSDUCER PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <PERSON:TRANSDUCER:MODEL>.
# ================================================================================

[Tape.Model] : WHO {AI_Cortex} WHAT {SemanticTransducer} --> INFER {CognitiveFlow}
    WHEN {SystemGenesis}
    WHERE {model_partition} = [ 64 ]
    WHY ( Inscribe semantic AI model transducer invariant and channel )
    HOW [ +1 : PROCEED ]
    :: < model_landmark > ( Proverbs 2:6 - 'For the Lord giveth wisdom' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract model archetype
roll_1 [ +Model ] ( Abstract model transducer archetype referenced )

# Roll 2: Allocate concrete model descriptor
roll_2 [ Model --> "Model_Descriptor" @ 0 ] ( Inscribe model descriptor in partition )

# Roll 3: Assert agentic projection
roll_3 [ { Model } --> REASON { Symbols } ] ( Model asserts reasoning capability )

# Roll 4: Verify descriptor integrity into result prime
roll_4 [ "Model_Descriptor" = Model ! [ +1 ] --> [ model_verified` ] ] ( Verify model descriptor matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Model transducer invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/stewards/operator.omni

OMNI | 60 LINES | 234 WORDS | 2.1 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <PERSON:STEWARD:OPERATOR> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the human originator, moral steward, and root sovereign principal.
#   - Base Block Type: < Idea : Type : Site > (Sovereign Authority Locus)
#   - Category: Person
#   - Subcategory: Steward
#   - Authority Rank: 0 (Highest / Originating Steward)
# ================================================================================

Module < Lexicon.Nouns.Persons.Stewards.Operator > ( Human Originator & Moral Steward ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Person :: Steward :: SovereignOriginator >
}

# Invariant Noun Declaration: <PERSON:STEWARD:OPERATOR>
< Person : Steward : Operator > [ capacity: 1 site ] {
    base_type: < Idea : Type : Site >,
    authority_rank: 0,
    projections: < {
        ontological: "< Operator >",
        structural: "[ OPERATOR ]",
        agentic: "{ Operator }"
    } >,
    machine_effect: "human_moral_steward"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Operator : InvariantNoun ::
        Site : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    steward_assertion [
        { Operator } --> ORIGINATE {Intent} :: [ OPERATOR ] @ 0x00
    ] ( Human steward asserts intent into bounded authority slot )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        steward_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Steward invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/persons/stewards/operator.tape

TAPE | 33 LINES | 198 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: OPERATOR STEWARD PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <PERSON:STEWARD:OPERATOR>.
# ================================================================================

[Tape.Operator] : WHO {Human_Operator} WHAT {MoralSteward} --> BIND {SovereignAuthority}
    WHEN {SystemGenesis}
    WHERE {steward_partition} = [ 64 ]
    WHY ( Inscribe sovereign human steward invariant and authority token )
    HOW [ +1 : PROCEED ]
    :: < steward_landmark > ( Genesis 1:26 - Human stewardship over creation )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract steward archetype
roll_1 [ +Operator ] ( Abstract steward archetype referenced )

# Roll 2: Allocate concrete steward authority token
roll_2 [ Operator --> "Operator_Token" @ 0 ] ( Inscribe human steward token into partition )

# Roll 3: Assert agentic projection
roll_3 [ { Operator } --> AUTHORIZE { Kernel } ] ( Steward delegates execution to kernel )

# Roll 4: Verify structural token invariant into result prime
roll_4 [ "Operator_Token" = Operator ! [ +1 ] --> [ steward_verified` ] ] ( Verify steward token matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Steward invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/tracks/track.omni

OMNI | 60 LINES | 244 WORDS | 2.1 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <PLACE:TRACK:BAND> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines concentric architectural tracks across the 6-track machine system.
#   - Base Block Type: < Idea : Type : Site > (Concentric Channel Locus)
#   - Category: Place
#   - Subcategory: Track
#   - Channels: Track 0 (Silicon) through Track 5 (Ops)
# ================================================================================

Module < Lexicon.Nouns.Places.Tracks.Track > ( Concentric Architectural Track & Execution Plane ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Place :: Track :: ConcentricExecutionBand >
}

# Invariant Noun Declaration: <PLACE:TRACK:BAND>
< Place : Track : Track > [ capacity: 6 channels ] {
    base_type: < Idea : Type : Site >,
    track_range: [ 0, 1, 2, 3, 4, 5 ],
    projections: < {
        ontological: "< Track >",
        structural: "[ TRACK ]",
        agentic: "{ Track }"
    } >,
    machine_effect: "concentric_track_routing"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Track : InvariantNoun ::
        Site : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    track_assertion [
        [ TRACK ] [ 6 ] :: { Track } --> ROUTE {Channel}
    ] ( Concentric track hierarchy armed across 6 architectural planes )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        track_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Track place invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/tracks/track.tape

TAPE | 33 LINES | 210 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: TRACK EXECUTION BAND PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <PLACE:TRACK:BAND>.
# ================================================================================

[Tape.Track] : WHO {OmniCode_Kernel} WHAT {ExecutionTrack} --> BIND {ConcentricPlane}
    WHEN {SystemGenesis}
    WHERE {track_channel} = [ 6 ]
    WHY ( Inscribe concentric track plane invariant across 6 architectural rings )
    HOW [ +1 : PROCEED ]
    :: < track_landmark > ( Ezekiel 1:16 - 'A wheel in the middle of a wheel' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract track archetype
roll_1 [ +Track ] ( Abstract track archetype referenced )

# Roll 2: Allocate track routing descriptor
roll_2 [ Track --> "Track_Descriptor" @ 0 ] ( Inscribe track descriptor in partition )

# Roll 3: Assert structural projection and clarified channel count
roll_3 [ [ TRACK ] [ 6 ] :: "6" --> [ CONCENTRIC_RINGS ] ] ( Structural 6-track bounds affirmed )

# Roll 4: Verify track channel routing into result prime
roll_4 [ "Track_Descriptor" = Track ! [ +1 ] --> [ track_verified` ] ] ( Verify track descriptor matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Track place invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/memory/partition.omni

OMNI | 60 LINES | 237 WORDS | 2.2 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <PLACE:MEMORY:PARTITION> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines an entrusted, bounded sub-region of a storehouse carved via `v--`.
#   - Base Block Type: < Idea : Type : Container > (Carved Memory Slice)
#   - Category: Place
#   - Subcategory: Memory
#   - Partition Operator: `v--`
# ================================================================================

Module < Lexicon.Nouns.Places.Memory.Partition > ( Entrusted Bounded Sub-Region of a Storehouse ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Place :: Memory :: DelegatedPartition >
}

# Invariant Noun Declaration: <PLACE:MEMORY:PARTITION>
< Place : Memory : Partition > [ capacity: dynamic cells ] {
    base_type: < Idea : Type : Container >,
    carving_operator: "v--",
    projections: < {
        ontological: "< Partition >",
        structural: "[ PARTITION ]",
        agentic: "{ Partition }"
    } >,
    machine_effect: "delegated_task_slice"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Partition : InvariantNoun ::
        Container : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    partition_assertion [
        Root_Storehouse v-- [ PARTITION ] [ 256 ] :: { Partition } --> PROTECT {Slice}
    ] ( Bounded task partition carved from root storehouse via v-- )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        partition_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Partition memory invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/memory/partition.tape

TAPE | 33 LINES | 216 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: PARTITION MEMORY SLICE PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <PLACE:MEMORY:PARTITION>.
# ================================================================================

[Tape.Partition] : WHO {OmniCode_Kernel} WHAT {MemoryPartition} --> CARVE {TaskSlice}
    WHEN {TaskSpawn}
    WHERE {partition_slice} = [ 256 ]
    WHY ( Inscribe delegated memory partition carved via v-- )
    HOW [ +1 : PROCEED ]
    :: < partition_landmark > ( Joshua 18:10 - 'Divided the land unto the children of Israel' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract partition archetype
roll_1 [ +Partition ] ( Abstract partition archetype referenced )

# Roll 2: Carve concrete task partition via v--
roll_2 [ Root_Storehouse v-- "Task_Partition" [ 256 ] ] ( Isolated workspace carved via v-- )

# Roll 3: Assert structural projection and clarified capacity
roll_3 [ [ PARTITION ] [ 256 ] :: "256" --> [ TASK_PARTITION ] ] ( Structural 256 cell bounds affirmed )

# Roll 4: Verify boundary containment into result prime
roll_4 [ [ { 256 } < { 4096 } ] ! [ +1 ] --> [ partition_bounded` ] ] ( Verify partition within storehouse bounds )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Memory partition invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/memory/storehouse.omni

OMNI | 60 LINES | 240 WORDS | 2.2 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <PLACE:MEMORY:STOREHOUSE> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the root system physical memory domain, reservoir, and chassis plate.
#   - Base Block Type: < Idea : Type : Container > (Memory Capacity Envelope)
#   - Category: Place
#   - Subcategory: Memory
#   - Capacity: Physical RAM Cells (4096 default cells)
# ================================================================================

Module < Lexicon.Nouns.Places.Memory.Storehouse > ( Root System Memory Domain & Reservoir ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Place :: Memory :: RootReservoir >
}

# Invariant Noun Declaration: <PLACE:MEMORY:STOREHOUSE>
< Place : Memory : Storehouse > [ capacity: 4096 cells ] {
    base_type: < Idea : Type : Container >,
    default_capacity: 4096,
    projections: < {
        ontological: "< Storehouse >",
        structural: "[ STOREHOUSE ]",
        agentic: "{ Storehouse }"
    } >,
    machine_effect: "root_page_reservoir"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Storehouse : InvariantNoun ::
        Container : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    storehouse_assertion [
        [ STOREHOUSE ] [ 4096 ] :: { Storehouse } --> RESERVE {RootRAM}
    ] ( Root storehouse allocated with 4096 cells on physical memory plane )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        storehouse_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Storehouse memory invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/memory/storehouse.tape

TAPE | 33 LINES | 209 WORDS | 1.7 KB

```
# ================================================================================
# TAPE HEAD: STOREHOUSE MEMORY DOMAIN PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <PLACE:MEMORY:STOREHOUSE>.
# ================================================================================

[Tape.Storehouse] : WHO {OmniCode_Kernel} WHAT {MemoryStorehouse} --> ALLOC {RootPlate}
    WHEN {SystemGenesis}
    WHERE {storehouse} = [ 4096 ]
    WHY ( Inscribe root memory storehouse invariant and capacity reservoir )
    HOW [ +1 : PROCEED ]
    :: < storehouse_landmark > ( Malachi 3:10 - 'Bring ye all the tithes into the storehouse' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract storehouse archetype
roll_1 [ +Storehouse ] ( Abstract storehouse archetype referenced )

# Roll 2: Allocate concrete storehouse memory block
roll_2 [ Storehouse --> "Root_Storehouse" @ 0 ] ( Concrete storehouse reserved at physical origin )

# Roll 3: Assert structural projection and clarified capacity
roll_3 [ [ STOREHOUSE ] [ 4096 ] :: "4096" --> [ ROOT_RAM ] ] ( Structural 4096 cell bounds affirmed )

# Roll 4: Verify allocation bounds into result prime
roll_4 [ "Root_Storehouse" = Storehouse ! [ +1 ] --> [ storehouse_verified` ] ] ( Verify root storehouse allocation )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Memory storehouse invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/vaults/vault.omni

OMNI | 60 LINES | 237 WORDS | 2.1 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <PLACE:VAULT:ROM> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the protected kernel vault for immutable ROM invariants & covenants.
#   - Base Block Type: < Idea : Type : Container > (Immutable ROM Envelope)
#   - Category: Place
#   - Subcategory: Vault
#   - Protection: Immutable ROM / Write-Once
# ================================================================================

Module < Lexicon.Nouns.Places.Vaults.Vault > ( Protected Kernel Vault for Immutable ROM Invariants ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Place :: Vault :: ImmutableROM >
}

# Invariant Noun Declaration: <PLACE:VAULT:ROM>
< Place : Vault : Vault > [ capacity: 128 cells ] {
    base_type: < Idea : Type : Container >,
    protection_tier: "immutable_rom",
    projections: < {
        ontological: "< Vault >",
        structural: "[ VAULT ]",
        agentic: "{ Vault }"
    } >,
    machine_effect: "protected_rom_vault"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Vault : InvariantNoun ::
        Container : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    vault_assertion [
        [ VAULT ] [ 128 ] :: { Vault } --> SEAL {ImmutableInvariants}
    ] ( Protected ROM vault allocated for immutable kernel invariants )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        vault_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Vault memory invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/vaults/vault.tape

TAPE | 33 LINES | 212 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: VAULT PROTECTED ROM PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <PLACE:VAULT:ROM>.
# ================================================================================

[Tape.Vault] : WHO {OmniCode_Kernel} WHAT {ProtectedVault} --> SEAL {Covenants}
    WHEN {SystemGenesis}
    WHERE {vault_rom} = [ 128 ]
    WHY ( Inscribe immutable kernel vault invariant and permanent covenant seal )
    HOW [ +1 : PROCEED ]
    :: < vault_landmark > ( Deuteronomy 31:26 - 'Put it in the side of the ark of the covenant' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract vault archetype
roll_1 [ +Vault ] ( Abstract vault archetype referenced )

# Roll 2: Allocate immutable ROM vault
roll_2 [ Vault --> "Immutable_Vault" @ 0 ] ( Inscribe immutable vault at ROM base )

# Roll 3: Assert structural projection and clarified capacity
roll_3 [ [ VAULT ] [ 128 ] :: "128" --> [ IMMUTABLE_ROM ] ] ( Structural 128 cell bounds affirmed )

# Roll 4: Verify vault inviolability into result prime
roll_4 [ "Immutable_Vault" = Vault ! [ +1 ] --> [ vault_verified` ] ] ( Verify vault matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Vault memory invariant sealed and verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/buffers/reservoir.omni

OMNI | 59 LINES | 235 WORDS | 2.1 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Invariant Noun: <PLACE:BUFFER:RESERVOIR> )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the dynamic heap reservoir for fluid streams and unformatted buffers.
#   - Base Block Type: < Idea : Type : Container > (Dynamic Fluid Envelope)
#   - Category: Place
#   - Subcategory: Buffer
#   - Fluid Dynamics: Elastic Buffer Stream
# ================================================================================

Module < Lexicon.Nouns.Places.Buffers.Reservoir > ( Dynamic Heap Reservoir for Fluid Data Streams ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InvariantNoun :: Place :: Buffer :: FluidReservoir >
}

# Invariant Noun Declaration: <PLACE:BUFFER:RESERVOIR>
< Place : Buffer : Reservoir > [ capacity: dynamic cells ] {
    base_type: < Idea : Type : Container >,
    projections: < {
        ontological: "< Reservoir >",
        structural: "[ RESERVOIR ]",
        agentic: "{ Reservoir }"
    } >,
    machine_effect: "fluid_buffer_reservoir"
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Reservoir : InvariantNoun ::
        Container : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    reservoir_assertion [
        [ RESERVOIR ] [ 512 ] :: { Reservoir } --> BUFFER {FluidStream}
    ] ( Elastic heap reservoir allocated for fluid buffer streams )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        reservoir_assertion = yes
    ],
    commit_status [ PROCEED- ] ( Reservoir buffer invariant sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/01_nouns/places/buffers/reservoir.tape

TAPE | 33 LINES | 207 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: RESERVOIR BUFFER PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic lifecycle for Invariant Noun <PLACE:BUFFER:RESERVOIR>.
# ================================================================================

[Tape.Reservoir] : WHO {OmniCode_Kernel} WHAT {BufferReservoir} --> STREAM {FluidData}
    WHEN {DataFlow}
    WHERE {reservoir_heap} = [ 512 ]
    WHY ( Inscribe fluid buffer reservoir invariant and stream territory )
    HOW [ +1 : PROCEED ]
    :: < reservoir_landmark > ( Ecclesiastes 1:7 - 'All the rivers run into the sea' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC INVARIANT RESOLUTION
# ================================================================================

# Roll 1: Reference abstract reservoir archetype
roll_1 [ +Reservoir ] ( Abstract reservoir archetype referenced )

# Roll 2: Allocate dynamic heap reservoir
roll_2 [ Reservoir --> "Fluid_Heap" @ 0 ] ( Inscribe fluid heap reservoir at offset 0 )

# Roll 3: Assert structural projection and clarified capacity
roll_3 [ [ RESERVOIR ] [ 512 ] :: "512" --> [ FLUID_HEAP ] ] ( Structural 512 cell bounds affirmed )

# Roll 4: Verify reservoir responsiveness into result prime
roll_4 [ "Fluid_Heap" = Reservoir ! [ +1 ] --> [ reservoir_verified` ] ] ( Verify reservoir matches archetype )

# Roll 5: Seal in affirmative proceed
roll_5 [ commit_status [ PROCEED- ] ] ( Buffer reservoir invariant sealed and verified )
```

OmniCode: Chapter 15: Track 2 - Lexicon: Verbs, Pronouns & Operators

Directional SVO Verbs, Scale Vectors & Polarity

CHAPTER IDENTIFIER
CH 15

NOTEBOOKLM WORD COUNT
7,888 words

CATALOGED CHAPTER FILES
26 files (1,565 lines)

GENERATION DATE
2026-10-16 20:36:07

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"Explain difference between ascension (/-^) and descension (\-v)."*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (26 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/arithmetic_verbs.omni**	OMNI	94	399	3.3
2	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/arithmetic_verbs.tape**	TAPE	33	207	1.6
3	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/axial_vectors.omni**	OMNI	68	271	2.5
4	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/axial_vectors.tape**	TAPE	30	178	1.4
5	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/cinematic_track_loop.omni**	OMNI	56	245	2.2
6	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/cinematic_track_loop.tape**	TAPE	36	250	1.8
7	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/diagonal_vectors.omni**	OMNI	92	380	3.2
8	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/diagonal_vectors.tape**	TAPE	30	177	1.5
9	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/relational_being.omni**	OMNI	86	376	3.1
10	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/relational_being.tape**	TAPE	33	191	1.5
11	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/scale_vectors.omni**	OMNI	68	265	2.5
12	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/scale_vectors.tape**	TAPE	30	187	1.5
13	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/03_verbs/universal_verbs.omni**	OMNI	118	617	4.9
14	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/03_verbs/universal_verbs.tape**	TAPE	49	296	2.5
15	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/operators/morphological_operators.omni**	OMNI	121	686	5.3
16	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/operators/morphological_operators.tape**	TAPE	49	318	2.5
17	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/boot_kernel.omni**	OMNI	91	441	3.9
18	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/boot_kernel.tape**	TAPE	37	264	2.0
19	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/casting.omni**	OMNI	88	393	3.1
20	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/casting.tape**	TAPE	30	170	1.4
21	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/polarity.omni**	OMNI	74	338	3.0
22	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/polarity.tape**	TAPE	30	179	1.5
23	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/self_handles.omni**	OMNI	81	338	2.9
24	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/self_handles.tape**	TAPE	30	187	1.4
25	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/wildcards.omni**	OMNI	81	342	3.0
26	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/wildcards.tape**	TAPE	30	193	1.5

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/arithmetic_verbs.omni

OMNI | 94 LINES | 399 WORDS | 3.3 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Verbs: Mechanical SVO Arithmetic Operators )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the mechanical arithmetic accumulator cogs:
#   - plus  : Additive mechanical translation cog (advance accumulator).
#   - minus : Subtractive mechanical translation cog (recede accumulator).
#   - times : Multiplicative mechanical gear ratio (ratio expansion).
#   - div   : Divisive mechanical tooth pitch / partition ratio.
# ================================================================================

Module < Lexicon.Verbs.ArithmeticVerbs > ( Mechanical arithmetic cogs and ratio accumulators ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < SVOArithmetic :: MechanicalAccumulators :: Radix3Cogs >
}

# 1. Additive Cog: < PLUS >
Plus < InvariantVerb > ( Mechanical Additive Translation: plus ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "plus" >,
    abstract_form: < "+Plus" >,
    concrete_form: < "Plus-" >,
    machine_effect: < "mechanical_adder_cog" >
}

# 2. Subtractive Cog: < MINUS >
Minus < InvariantVerb > ( Mechanical Subtractive Translation: minus ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "minus" >,
    abstract_form: < "+Minus" >,
    concrete_form: < "Minus-" >,
    machine_effect: < "mechanical_subtractor_cog" >
}

# 3. Multiplicative Cog: < TIMES >
Times < InvariantVerb > ( Mechanical Gear Ratio Multiplier: times ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "times" >,
    abstract_form: < "+Times" >,
    concrete_form: < "Times-" >,
    machine_effect: < "mechanical_gear_multiplier" >
}

# 4. Divisive Cog: < DIV >
Div < InvariantVerb > ( Mechanical Pitch Partition Divider: div ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "div" >,
    abstract_form: < "+Div" >,
    concrete_form: < "Div-" >,
    machine_effect: < "mechanical_partition_divider" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Plus : InvariantVerb ::
        Minus : InvariantVerb ::
        Times : InvariantVerb ::
        Div : InvariantVerb
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
```

```
# ================================================================================
Body [
    # Verify SVO arithmetic execution
    arithmetic_verification [
        Add_Roll [ 10 plus 5 = 15 ] ::
        Sub_Roll [ 20 minus 8 = 12 ] ::
        Mul_Roll [ 4 times 3 = 12 ] ::
        Div_Roll [ 16 div 4 = 4 ]
    ] ( Mechanical arithmetic operations verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        arithmetic_verification = yes
    ],
    commit_status [ PROCEED- ] ( Arithmetic verbs verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/arithmetic_verbs.tape

TAPE | 33 LINES | 207 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: ARITHMETIC VERBS EXECUTION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes mechanical SVO arithmetic operations (plus, minus, times, div).
# ================================================================================

[Tape.ArithmeticVerbs] : WHO {OmniCode_Kernel} WHAT {ArithmeticVerbs} --> ACCUMULATE {MathMesh}
    WHEN {GenesisBoot}
    WHERE {arithmetic_chassis} = [ 64 ]
    WHY ( Test mechanical arithmetic adder and multiplier cogs )
    HOW [ +1 : PROCEED ]
    :: < math_landmark > ( Genesis 1:28 - 'Be fruitful, and multiply' )

# ================================================================================
# SUBORDINATE ROLLS: MECHANICAL SVO ARITHMETIC TRANSFORMATIONS
# ================================================================================

# Roll 1: Reference abstract Plus, Minus, Times, and Div specifications
roll_1 [ +Plus & +Minus & +Times & +Div ] ( Abstract arithmetic verb blueprints referenced )

# Roll 2: Additive mechanical translation
roll_2 [ 20 plus 22 --> Accumulator_0 @ 0 ] ( Compute sum and store into accumulator )

# Roll 3: Multiplicative mechanical gear ratio
roll_3 [ 6 times 7 --> Product_0 @ 1 ] ( Compute product and store into product cell )

# Roll 4: Verify accumulator invariant bounds
roll_4 [ Accumulator_0 = 42 ! [ +1 ] ] ( Verify mechanical arithmetic result )

# Roll 5: Commit with affirmative concrete macro
roll_5 [ commit_status [ PROCEED- ] ] ( Arithmetic verbs verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/axial_vectors.omni

OMNI | 68 LINES | 271 WORDS | 2.5 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Verbs: Axial Driving Vectors )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the primary horizontal causality vectors:
#   - --> : ActUpon (Forward causality, drive gear, state propagation, store).
#   - <-- : ActAgain (Reverse causality, retroaction, sensor read, reflection).
# ================================================================================

Module < Lexicon.Verbs.AxialVectors > ( Axial drive vectors and horizontal causality ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < AxialVectors :: ForwardDrive :: RetroactiveFeedback >
}

# 1. Forward Vector: < ACT_UPON >
ActUpon < InvariantVerb > ( Forward Causality & Driving Gear: --> ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "-->" >,
    abstract_form: < "+ActUpon" >,
    concrete_form: < "ActUpon-" >,
    machine_effect: < "forward_drive_write_dispatch" >
}

# 2. Reverse Vector: < ACT_AGAIN >
ActAgain < InvariantVerb > ( Reverse Causality & Feedback Gear: <-- ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "<--" >,
    abstract_form: < "+ActAgain" >,
    concrete_form: < "ActAgain-" >,
    machine_effect: < "retroactive_read_sensor" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        ActUpon : InvariantVerb ::
        ActAgain : InvariantVerb
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify forward and reverse causality pair
    vector_verification [
        Forward_Transmission [ 10 --> Register_A ] ::
        Feedback_Sensor [ Register_A <-- Sensor_Tap ]
    ] ( Forward drive and sensor feedback verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        vector_verification = yes
    ],
    commit_status [ PROCEED- ] ( Axial driving vectors verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/axial_vectors.tape

TAPE | 30 LINES | 178 WORDS | 1.4 KB

```
# ================================================================================
# TAPE HEAD: AXIAL VECTORS EXECUTION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes forward driving write (-->) and reverse feedback read (<--).
# ================================================================================

[Tape.AxialVectors] : WHO {OmniCode_Kernel} WHAT {AxialVectors} --> DRIVE {MotionMesh}
    WHEN {GenesisBoot}
    WHERE {axial_chassis} = [ 64 ]
    WHY ( Test forward and reverse axial drive gears )
    HOW [ +1 : PROCEED ]
    :: < vector_landmark > ( Proverbs 4:25 - 'Let thine eyes look right on' )

# ================================================================================
# SUBORDINATE ROLLS: FORWARD AND REVERSE AXIAL TRANSLATION
# ================================================================================

# Roll 1: Reference abstract ActUpon and ActAgain vector specifications
roll_1 [ +ActUpon & +ActAgain ] ( Abstract axial vector blueprints referenced )

# Roll 2: Forward drive vector actuation
roll_2 [ 100 --> Buffer_0 @ 0 ] ( Forward drive write into Buffer_0 )

# Roll 3: Reverse drive vector verification
roll_3 [ Result <-- Buffer_0 ! [ +1 ] ] ( Reverse read from Buffer_0 )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Axial vectors verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/cinematic_track_loop.omni

OMNI | 56 LINES | 245 WORDS | 2.2 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Verbs: Cinematic Track Loops & Transport Kinematics )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines Turing-complete track looping via reel transport kinematics:
#   - PLAY   : Advance track head forward (+1 / YES / PROCEED).
#   - REWIND : Spool track head backward along the reel to cue landmark (-1 / NO / ROLLBACK).
#   - STOP   : Mechanical brake arresting the motor (NULL / VOID / HALT).
# ================================================================================

Module < Lexicon.Verbs.CinematicTrackLoop > ( Cinematic track looping and transport kinematics ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < TrackLooping :: TransportKinematics :: TuringCompleteness >
}

# 1. Transport Verb: < CINEMATIC_LOOP >
CinematicLoop < InvariantVerb > ( Turing-Complete Track Transport Loop: PLAY & REWIND ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    abstract_form: < "+CinematicLoop" >,
    concrete_form: < "CinematicLoop-" >,
    machine_effect: < "turing_complete_track_transport" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        CinematicLoop : InvariantVerb
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify track transport iteration
    loop_verification [
        Track_Iteration [ Counter > 0 ! [ PLAY :: REWIND < loop_cue > ] ]
    ] ( Track transport kinematics verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        loop_verification = yes
    ],
    commit_status [ PROCEED- ] ( Cinematic track loops verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/cinematic_track_loop.tape

TAPE | 36 LINES | 250 WORDS | 1.8 KB

```
# ================================================================================
# TAPE HEAD: CINEMATIC TRACK LOOP PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes a Turing-complete transport loop via PLAY and REWIND to cue landmark.
# ================================================================================

[Tape.CinematicTrackLoop] : WHO {OmniCode_Kernel} WHAT {CinematicLoop} --> MODULATE {ReelMesh}
    WHEN {GenesisBoot}
    WHERE {loop_partition} = [ 64 ]
    WHY ( Prove Turing completeness via physical reel transport kinematics )
    HOW [ +1 : PROCEED ]
    :: < loop_landmark > ( Ecclesiastes 1:6 - 'The wind returneth again according to his circuits' )

# ================================================================================
# SUBORDINATE ROLLS: REEL TRANSPORT KINEMATICS & CUE REWIND
# ================================================================================

# Roll 1: Reference abstract CinematicLoop transport specification
roll_1 [ +CinematicLoop ] ( Abstract track loop blueprint referenced )

# Roll 2: Inscribe initial loop counter into silicon register
roll_2 [ 3 --> Loop_Counter_0 @ 0 ] ( Initialize loop counter to 3 )

# Roll 3: Landmark cue point for loop track rewind
roll_3 [ < loop_cue > :: 1 plus Step_Accumulator_0 --> Step_Accumulator_0 @ 1 ] ( Cue landmark: advance step accumulator
)

# Roll 4: Decrement loop counter
roll_4 [ Loop_Counter_0 minus 1 --> Loop_Counter_0 @ 0 ] ( Decrement loop counter register )

# Roll 5: Conditional track transport rewind
roll_5 [ Loop_Counter_0 != 0 ! [ PLAY :: REWIND < loop_cue > ] ] ( Rewind track head back to landmark cue while counter
positive )

# Roll 6: Commit and stop transport motor
roll_6 [ STOP :: commit_status [ PROCEED- ] ] ( Complete loop and engage emergency brake )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/diagonal_vectors.omni

OMNI | 92 LINES | 380 WORDS | 3.2 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Verbs: Diagonal Modulated Scale Vectors )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines compound diagonal scale and causality vectors across 3D coordinates:
#   - /-^ : Major (Ascending forward diagonal, macro amplification).
#   - \-v : Minor (Descending forward diagonal, micro attenuation).
#   - /-v : Small (Descending reverse diagonal, localized reduction).
#   - \-^ : Great (Ascending reverse diagonal, expansive retrospective).
# ================================================================================

Module < Lexicon.Verbs.DiagonalVectors > ( Diagonal modulated scale and causality vectors ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < DiagonalVectors :: ModulatedScale :: SpatialProjection >
}

# 1. Diagonal Vector: < MAJOR >
Major < InvariantVerb > ( Ascending Forward Diagonal: /-^ ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Adjective" >,
    symbol: < "/-^" >,
    abstract_form: < "+Major" >,
    concrete_form: < "Major-" >,
    machine_effect: < "macro_amplification_forward" >
}

# 2. Diagonal Vector: < MINOR >
Minor < InvariantVerb > ( Descending Forward Diagonal: \-v ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Adjective" >,
    symbol: < "\\-v" >,
    abstract_form: < "+Minor" >,
    concrete_form: < "Minor-" >,
    machine_effect: < "micro_attenuation_forward" >
}

# 3. Diagonal Vector: < SMALL >
Small < InvariantVerb > ( Descending Reverse Diagonal: /-v ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Adjective" >,
    symbol: < "/-v" >,
    abstract_form: < "+Small" >,
    concrete_form: < "Small-" >,
    machine_effect: < "localized_reduction_reverse" >
}

# 4. Diagonal Vector: < GREAT >
Great < InvariantVerb > ( Ascending Reverse Diagonal: \-^ ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Adjective" >,
    symbol: < "\\-^" >,
    abstract_form: < "+Great" >,
    concrete_form: < "Great-" >,
    machine_effect: < "expansive_retrospective_reverse" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Major : InvariantVerb ::
        Minor : InvariantVerb ::
        Small : InvariantVerb ::
        Great : InvariantVerb
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
```

```
# ================================================================================
Body [
    # Verify diagonal trajectory balance
    diagonal_verification [
        Amplification [ Signal /-^ Macro_Bus ] ::
        Attenuation   [ Signal \-v Micro_Bus ]
    ] ( Compound 3D diagonal motions verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        diagonal_verification = yes
    ],
    commit_status [ PROCEED- ] ( Diagonal scale vectors verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/diagonal_vectors.tape

TAPE | 30 LINES | 177 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: DIAGONAL VECTORS EXECUTION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes modulated diagonal scale transformations across coordinate quadrants.
# ================================================================================

[Tape.DiagonalVectors] : WHO {OmniCode_Kernel} WHAT {DiagonalVectors} --> MODULATE {QuadrantMesh}
    WHEN {GenesisBoot}
    WHERE {diagonal_chassis} = [ 64 ]
    WHY ( Test 3D diagonal scale and direction vectors )
    HOW [ +1 : PROCEED ]
    :: < diagonal_landmark > ( Ezekiel 1:16 - 'A wheel in the middle of a wheel' )

# ================================================================================
# SUBORDINATE ROLLS: DIAGONAL MODULATED TRANSFORMATIONS
# ================================================================================

# Roll 1: Reference abstract Major and Minor diagonal vectors
roll_1 [ +Major & +Minor ] ( Abstract diagonal vector blueprints referenced )

# Roll 2: Modulate scale forward-ascending via /-^
roll_2 [ Signal_0 /-^ Macro_Register @ 0 ] ( Ascending forward diagonal drive )

# Roll 3: Modulate scale forward-descending via \-v
roll_3 [ Macro_Register \-v Micro_Register ! [ +1 ] ] ( Descending forward diagonal drive )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Diagonal vectors verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/relational_being.omni

OMNI | 86 LINES | 376 WORDS | 3.1 KB

```
# ============================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Verbs: Relations of Being along the Y-Axis )
# ============================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the Y-axis relations of ontology and identity:
#   - =  : Is (Exact identity, equivalence, covenant equality).
#   - != : IsNot (Distinction, exclusion; not / not to be).
#   - =! : IsNot (Copular negation, non-being; is not / to be not).
#   - ~= : ToBeLike (Homomorphism, structural analogy, likeness).
#   - =~ : ToBeLike (Homomorphic resemblance; liken to / to be like).
# ============================================================================

Module < Lexicon.Verbs.RelationalBeing >
    ( Relations of Being and ontological identity )
{
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < RelationalBeing :: IdentityEquivalence :: StructuralAnalogy >
}

# 1. Identity Relation: < IS >
Is < InvariantVerb > ( Exact Ontological Identity & Equivalence: = ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Preposition" >,
    symbol: < "=" >,
    abstract_form: < "+Is" >,
    concrete_form: < "Is-" >,
    machine_effect: < "identity_assert_equate" >
}

# 2. Distinction Relation: < IS_NOT >
IsNot < InvariantVerb > ( Ontological Distinction: != / =! ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Preposition" >,
    symbols: < "!=" :: "=!" >,
    abstract_form: < "+IsNot" >,
    concrete_form: < "IsNot-" >,
    machine_effect: < "distinction_assert_differentiate" >
}

# 3. Analogy Relation: < TO_BE_LIKE >
ToBeLike < InvariantVerb > ( Homomorphism & Likeness: ~= / =~ ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Adjective" >,
    symbols: < "~=" :: "=~" >,
    abstract_form: < "+ToBeLike" >,
    concrete_form: < "ToBeLike-" >,
    machine_effect: < "homomorphic_analogy_match" >
}

# ============================================================================
# BLOCK 2: OPENING BLOCK
# ============================================================================
Opening {
    requires: [
        Is : InvariantVerb ::
        IsNot : InvariantVerb ::
        ToBeLike : InvariantVerb
    ],
    preconditions: [ +1 ]
}

# ============================================================================
# BLOCK 3: BODY BLOCK
# ============================================================================
Body [
    # Verify identity, distinction, and analogy
    relations_verification [
        Equivalence_Roll [ Entity_A = Entity_A ] ::
        Distinction_Roll [ Entity_A != Entity_B :: Entity_A =! Entity_B ] ::
        Analogy_Roll     [ Entity_A ~= Entity_Prototype ::
                           Entity_A =~ Entity_Prototype ]
```

```
    ] ( Y-axis relations of being verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        relations_verification = yes
    ],
    commit_status [ PROCEED- ] ( Relations of being verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/relational_being.tape

TAPE | 33 LINES | 191 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: RELATIONAL BEING EXECUTION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes identity (=), distinction (!= / =!), and analogy (~= / =~).
# ================================================================================

[Tape.RelationalBeing] : WHO {OmniCode_Kernel}
    WHAT {RelationalBeing} --> VERIFY {IdentityMesh}
    WHEN {GenesisBoot}
    WHERE {relational_chassis} = [ 64 ]
    WHY ( Test Y-axis relations of being, distinction, and analogy )
    HOW [ +1 : PROCEED ]
    :: < relation_landmark > ( Exodus 3:14 - 'I AM THAT I AM' )

# ================================================================================
# SUBORDINATE ROLLS: RELATIONAL EQUIVALENCE & DISTINCTION
# ================================================================================

# Roll 1: Reference abstract Is, IsNot, and ToBeLike specifications
roll_1 [ +Is & +IsNot & +ToBeLike ]
    ( Abstract relational being blueprints referenced )

# Roll 2: Verify identity equivalence via =
roll_2 [ State_Alpha = State_Alpha @ 0 ] ( Verify reflexive identity equation )

# Roll 3: Verify boundary distinction via != and =!
roll_3 [ State_Alpha != State_Beta :: State_Alpha =! State_Beta ! [ +1 ] ]
    ( Verify ontological distinction via != and =! )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Relational being verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/scale_vectors.omni

OMNI | 68 LINES | 265 WORDS | 2.5 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Verbs: Scale Vectors & Hierarchical Motion )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines vertical hierarchy and scale motion vectors:
#   - ^-- : BuildsTo (Ascension, composition, integration, synthesis).
#   - v-- : BreaksDownFrom (Descension, partitioning, decomposition, allocation).
# ========================================================================

Module < Lexicon.Verbs.ScaleVectors > ( Scale vectors and hierarchical motion ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < ScaleVectors :: HierarchicalSynthesis :: PartitionDecomposition >
}

# 1. Scale Ascension: < BUILDS_TO >
BuildsTo < InvariantVerb > ( Hierarchical Ascension & Synthesis: ^-- ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "^--" >,
    abstract_form: < "+BuildsTo" >,
    concrete_form: < "BuildsTo-" >,
    machine_effect: < "ascend_compose_aggregate" >
}

# 2. Scale Descension: < BREAKS_DOWN_FROM >
BreaksDownFrom < InvariantVerb > ( Hierarchical Descension & Partitioning: v-- ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < "v--" >,
    abstract_form: < "+BreaksDownFrom" >,
    concrete_form: < "BreaksDownFrom-" >,
    machine_effect: < "descend_partition_slice" >
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {
    requires: [
        BuildsTo : InvariantVerb ::
        BreaksDownFrom : InvariantVerb
    ],
    preconditions: [ +1 ]
}

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    # Verify scale ascension and descension
    scale_verification [
        Synthesis_Roll [ SubUnits ^-- MasterSystem ] ::
        Decomposition_Roll [ Root_Storehouse v-- Sub_Partition [ 128 ] ]
    ] ( Hierarchical scale vectors verified )
]

# ========================================================================
# BLOCK 4: CLOSING BLOCK
# ========================================================================
Closing {
    verify: [
        scale_verification = yes
    ],
    commit_status [ PROCEED- ] ( Scale vectors verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/03_verbs/scale_vectors.tape

TAPE | 30 LINES | 187 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: SCALE VECTORS EXECUTION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes scale ascension (^--) and scale descension partition slicing (v--).
# ================================================================================

[Tape.ScaleVectors] : WHO {OmniCode_Kernel} WHAT {ScaleVectors} --> MODULATE {HierarchyMesh}
    WHEN {GenesisBoot}
    WHERE {scale_chassis} = [ 128 ]
    WHY ( Test hierarchical ascension and partition descension )
    HOW [ +1 : PROCEED ]
    :: < scale_landmark > ( Genesis 28:12 - 'A ladder set up on the earth, and the top of it reached to heaven' )

# ================================================================================
# SUBORDINATE ROLLS: SCALE ASCENSION AND DESCENSION
# ================================================================================

# Roll 1: Reference abstract BuildsTo and BreaksDownFrom vector specifications
roll_1 [ +BuildsTo & +BreaksDownFrom ] ( Abstract scale vector blueprints referenced )

# Roll 2: Scale partition slicing via v--
roll_2 [ Root_Storehouse v-- Sub_Partition @ 0 ] ( Carve sub-partition from root storehouse )

# Roll 3: Scale ascension via ^--
roll_3 [ Sub_Partition ^-- Root_Storehouse ! [ +1 ] ] ( Verify structural linkage to root )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Scale vectors verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/03_verbs/universal_verbs.omni

OMNI | 118 LINES | 617 WORDS | 4.9 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Verbs: Universal Human Verbs for Accessible System Architecture )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines four foundational human verbs designed for universal cross-domain usage:
#   - PREEMPT : Priority interruption & turn-taking (replaces technical scheduler jargon).
#   - SENSE   : Environmental perception & hardware discovery (replaces invasive developer jargon "Probe").
#   - AWAKEN  : Cold-start inception & life activation (replaces gamer/Unix jargon "Spawn" / "Fork").
#   - PROVE   : Invariant validation & equilibrium self-test (replaces developer acronyms "BIST" / "Assert").
#
# ACCESSIBILITY FOR NON-CODERS:
#   Every verb defined here is a standard, intuitive word understood by any human speaker:
#   - A human understands what it means to "sense" a room or "awaken" a dormant console.
#   - A human understands what it means to "preempt" a workflow for something urgent.
#   - A human understands what it means to "prove" balance before committing a decision.
# ================================================================================

Module < Lexicon.Suggestions.Verbs.Universal > ( Universal human verbs for accessible system architecture ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < UniversalVerbs :: NonCoderAccessibility :: CrossDomainActions >
}

# 1. Action: < PREEMPT >
Preempt < InvariantVerb > ( Priority Interruption & Turn-Taking ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Conjunction" >,
    abstract_form: < "+Preempt" >,
    concrete_form: < "Preempt-" >,
    universal_scope: < "OS.Scheduler :: UI.Modals :: Audio.Ducking :: AI.Safety" >,
    machine_effect: < "schedule_quantum_preemption" >
}

# 2. Action: < SENSE >
Sense < InvariantVerb > ( Environmental Perception & Hardware Discovery ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Noun" >,
    abstract_form: < "+Sense" >,
    concrete_form: < "Sense-" >,
    universal_scope: < "OS.MemoryMap :: Game.Collision :: UI.Theme :: IoT.Sensors" >,
    machine_effect: < "perceive_environmental_state" >
}

# 3. Action: < AWAKEN >
Awaken < InvariantVerb > ( Cold-Start Inception & Life Activation ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Noun" >,
    abstract_form: < "+Awaken" >,
    concrete_form: < "Awaken-" >,
    universal_scope: < "OS.ProcessInception :: UI.StudioLaunch :: Game.Entities :: AI.Memory" >,
    machine_effect: < "instate_active_execution_life" >
}

# 4. Action: < PROVE >
Prove < InvariantVerb > ( Invariant Validation & Equilibrium Certification ) {
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Noun" >,
    abstract_form: < "+Prove" >,
    concrete_form: < "Prove-" >,
    universal_scope: < "OS.ALU_BIST :: Security.Covenants :: Math.Balance :: Invariant.Checks" >,
    machine_effect: < "certify_invariant_truth" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Action Dependencies & Operational Preconditions )
# ================================================================================
Opening {
    requires: [
        Preempt : InvariantVerb ::
        Sense : InvariantVerb ::
        Awaken : InvariantVerb ::
```

```
        Prove : InvariantVerb
    ],
    preconditions: [ +1 : PROCEED ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Cross-Domain Demonstrations of Universal Verbs )
# ================================================================================
Body [
    # Demo 1: Preempt action in scheduling & urgent workflow
    preempt_demo [
        Scheduler_Tick [ Timer_IRQ --> PREEMPT {Current_Task} ]
    ] ( Preempt active execution quantum in favor of higher-priority need )

    # Demo 2: Sense action in environmental hardware discovery
    sense_demo [
        Hardware_Discovery [ Kernel --> SENSE {Root_RAM} ]
    ] ( Sense physical memory topology from silicon firmware )

    # Demo 3: Awaken action in cold-start process inception
    awaken_demo [
        Session_Launch [ Kernel --> AWAKEN {Terminal_Studio} ]
    ] ( Awaken dormant console interface into living interaction )

    # Demo 4: Prove action in balanced-ternary ALU verification
    prove_demo [
        Arithmetic_Proof [ Kernel --> PROVE {ALU_Equilibrium} ]
    ] ( Prove algebraic symmetry before allocating dynamic memory )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Invariant Audit & Covenant Commit Seal )
# ================================================================================
Closing {
    verify: [
        preempt_demo = yes ::
        sense_demo = yes ::
        awaken_demo = yes ::
        prove_demo = yes
    ],
    commit_status [ PROCEED ] ( Universal human verb proposals certified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/03_verbs/universal_verbs.tape

TAPE | 49 LINES | 296 WORDS | 2.5 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Universal Verbs Proposal Process Ribbon )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes operational test rolls validating the 4 universal human verbs:
#   - PREEMPT (turn-taking / priority preemption)
#   - SENSE   (environmental perception & hardware discovery)
#   - AWAKEN  (cold-start inception & active life activation)
#   - PROVE   (balanced-ternary invariant certification)
# ================================================================================

[Tape.UniversalVerbs] : WHO {OmniCode_Kernel} WHAT {HumanVerbs} --> TEST {Lexicon}
    WHEN {IncubationTrial}
    WHERE {verbs_partition} = [ 256 ]
    WHY ( Validate universal human verbs across OS and accessible user domains )
    HOW [ +1 : PROCEED ]
    :: < verbs_landmark > ( Proverbs 4:7 - 'Wisdom is the principal thing; therefore get wisdom' )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Environmental Setup & Test Partition Bounds )
# ================================================================================

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Test Instruction Rolls Exercising Proposed Universal Verbs )
# ================================================================================

# Roll 1: Sense physical memory layout from system firmware
roll_1 [ Kernel --> SENSE {Root_RAM} ] ( Sense available silicon memory frames )

# Roll 2: Prove balanced-ternary arithmetic symmetry in hardware registers
roll_2 [ Kernel --> PROVE {ALU_Equilibrium} ] ( Prove algebraic balance before allocating memory )

# Roll 3: Preempt active background task when timer tick arrives
roll_3 [ Timer_Tick --> PREEMPT {Background_Task} ] ( Preempt task slice to maintain system responsiveness )

# Roll 4: Awaken the interactive terminal session into active life
roll_4 [ Kernel --> AWAKEN {Terminal_Studio} ] ( Awaken console HUD and user interface )

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Verification & Affirmative Commit Seal )
# ================================================================================

# Roll 5: Commit universal verbs proposal tape
roll_5 [ commit_status [ PROCEED ] ] ( Universal verbs proposal tape verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/operators/morphological_operators.omni

OMNI | 121 LINES | 686 WORDS | 5.3 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Operators: Morphological Compounding & Contextual Relational Syntax )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines compound operators that naturally evolve from base morphemes:
#   - ::@ : SituatedAt (Channel bind `::` + Location `@` -> "and at location").
#   - ~!  : CaveatInterrupt (Approximate `~` + Adversative `!` -> "like normal, BUT").
#   - [ { A } < { B } ] : CastedContextComparison (Disambiguated relational comparison).
#   - <=> : InvariantEquivalence (Uncasted invariant equivalence axiom < = >).
#
# THE BOUNDARY TIER COMPARISON CANON:
#   Why must comparison be written as `[ { A } < { B } ]`?
#   1. In OmniCode's 4-tier delimiter ranking, `< ... >` is the Rank 1 Invariant.
#   2. If a coder writes `A < B`, the lexer and parser interpret `<` as the opening
#      of an immutable Invariant tier, causing a syntax collision.
#   3. Therefore, comparison MUST be enclosed in a Rank 2 Denotation block `[ ... ]`,
#      with the compared entities cast into Rank 3 Context brackets `{ ... }`.
#   4. This disambiguates `<` as a relational comparator rather than an Invariant opening.
#   5. Conversely, uncasted `<=>` literally means `< = >`: an Invariant of Equivalence!
# ========================================================================

Module < Lexicon.Suggestions.Operators.Morphological > ( Morphological compound operators and relational syntax ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < MorphemicOperators :: ContextualComparison :: InvariantEquivalence >
}

# 1. Situated-At Operator: < SITUATED_AT >
SituatedAt < InvariantConjunction > ( Compound Conjunction: ::@ - 'and at location' ) {
    grammar_primary: < "Conjunction" >,
    grammar_secondary: < "Preposition" >,
    symbol: < "::@" >,
    abstract_form: < "+SituatedAt" >,
    concrete_form: < "SituatedAt-" >,
    machine_effect: < "hardware_mmio_port_binding" >
}

# 2. Caveat-Interrupt Operator: < CAVEAT_INTERRUPT >
CaveatInterrupt < InvariantConjunction > ( Compound Conjunction: ~! - 'like normal, BUT...' ) {
    grammar_primary: < "Conjunction" >,
    grammar_secondary: < "Preposition" >,
    symbol: < "~!" >,
    abstract_form: < "+CaveatInterrupt" >,
    concrete_form: < "CaveatInterrupt-" >,
    machine_effect: < "asynchronous_preemption_catch" >
}

# 3. Contextual Comparison Operator: < CONTEXT_RELATION >
ContextRelation < InvariantOperator > ( Casted Relational Comparison: [ { A } < { B } ] ) {
    grammar_primary: < "Operator" >,
    grammar_secondary: < "Adjective" >,
    syntax_pattern: < "[ { A } < { B } ]" >,
    machine_effect: < "balanced_ternary_three_way_comparison" >
}

# 4. Invariant Equivalence Axiom: < INVARIANT_EQUIVALENCE >
InvariantEquivalence < InvariantOperator > ( Uncasted Invariant Equivalence: <=> ) {
    grammar_primary: < "Operator" >,
    grammar_secondary: < "Noun" >,
    symbol: < "<=>" >,
    abstract_form: < "+InvariantEquivalence" >,
    concrete_form: < "InvariantEquivalence-" >,
    machine_effect: < "immutable_equivalence_proof" >
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ( Operational Dependencies & Hardware Binding Preconditions )
# ========================================================================
Opening {
    requires: [
        SituatedAt : InvariantConjunction ::
```

```
        CaveatInterrupt : InvariantConjunction ::
        ContextRelation : InvariantOperator ::
        InvariantEquivalence : InvariantOperator
    ],
    preconditions: [ +1 : PROCEED ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Verification Rolls & Concrete Syntax Demonstrations )
# ================================================================================
Body [
    # Demo 1: Situated-At binding of MMIO and Port registers (::@)
    mmio_binding_demo [
        Serial_Port [ COM1 ::@ 0x03F8 ] ::
        Screen_Port [ Screen_VGA ::@ 0x000B8000 ]
    ] ( Inscribe hardware ports situated at concrete silicon addresses )

    # Demo 2: Caveat-Interrupt preemption (~!)
    interrupt_caveat_demo [
        Standard_Process [ Task_Compute ~! [ Timer_Tick --> Preempt ] ]
    ] ( Run task like normal, BUT preempt if timer tick fires )

    # Demo 3: Casted Contextual Comparison ([ { A } < { B } ])
    comparison_demo [
        Bounds_Check [ { Current_Offset } < { Partition_Limit } ]
    ] ( Relational comparison cleanly disambiguated within concrete denotation )

    # Demo 4: Uncasted Invariant Equivalence (<=>)
    equivalence_demo [
        Symmetry_Proof [ (+1) plus (-1) <=> 0 ]
    ] ( Uncasted <=> asserts an invariant state of algebraic equilibrium )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Structural Proof Verification & Covenant Commit Seal )
# ================================================================================
Closing {
    verify: [
        mmio_binding_demo = yes ::
        interrupt_caveat_demo = yes ::
        comparison_demo = yes ::
        equivalence_demo = yes
    ],
    commit_status [ PROCEED ] ( Morphological operator proposals certified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/operators/morphological_operators.tape

TAPE | 49 LINES | 318 WORDS | 2.5 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Morphological Operator Proposal Process Ribbon )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes operational test rolls validating compound operators:
#   - ::@ (Situated-At port/MMIO binding)
#   - ~!  (Caveat-Interrupt asynchronous preemption)
#   - [ { A } < { B } ] (Casted Context Comparison)
#   - <=> (Invariant Equivalence Axiom)
# ================================================================================

[Tape.MorphologicalOperators] : WHO {OmniCode_Kernel} WHAT {CompoundOperators} --> TEST {Lexicon}
    WHEN {IncubationTrial}
    WHERE {test_partition} = [ 256 ]
    WHY ( Validate compound morphemes and casted contextual comparison syntax )
    HOW [ +1 : PROCEED ]
    :: < operator_landmark > ( Ecclesiastes 3:1 - 'To every thing there is a season' )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Environmental Setup & Test Partition Bounds )
# ================================================================================

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Test Instruction Rolls Exercising Proposed Operators )
# ================================================================================

# Roll 1: Bind serial COM1 and VGA ports situated at concrete hardware addresses via ::@
roll_1 [ COM1 ::@ 0x03F8 :: Screen_VGA ::@ 0x000B8000 ] ( Hardware ports bound situated at physical addresses )

# Roll 2: Execute task like normal BUT preempt on timer interrupt via ~!
roll_2 [ Kernel_Compute ~! [ Timer_IRQ --> Preempt ] ] ( Process runs like normal BUT yields on timer tick )

# Roll 3: Evaluate casted contextual comparison within concrete denotation block
roll_3 [ Bounds_Test [ { 16 } < { 64 } ] ] ( Relational comparison safely evaluated inside context brackets )

# Roll 4: Inscribe invariant equivalence axiom proving balanced ternary symmetry
roll_4 [ Balanced_Proof [ (+1) plus (-1) <=> 0 ] ] ( Invariant equivalence asserted )

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Verification & Affirmative Commit Seal )
# ================================================================================

# Roll 5: Commit operator proposal tape
roll_5 [ commit_status [ PROCEED ] ] ( Morphological operators proposal tape verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/boot_kernel.omni

OMNI | 91 LINES | 441 WORDS | 3.9 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Operators: Boot Inception & Anti-Lockout Sentinel Invariants )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Establishes the primordial Hardware Boot Operator (--> BOOT) and Anti-Lockout
#   Guardians within the balanced ternary execution engine:
#   - Boot Operator (--> BOOT) : Hardware root inception vector bound exclusively to Kernel authority.
#   - Watchdog Sentinel (Watchdog_Guard) : Preemptive cycle counter preventing AI infinite loops.
#   - Kernel Shield (Kernel_Partition_Barrier) : Memory protection preventing AI privilege escalation.
# ========================================================================

Module < Lexicon.Operators.BootKernel > ( Boot inception operator and anti-lockout safety invariants ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < HardwareBootInception :: AntiLockoutWatchdog :: KernelShieldAuthority >
}

# 1. Invariant Operator: < BOOT_OPERATOR > (--> BOOT)
Boot_Operator < InvariantOperator > ( Primordial Hardware Inception Vector ) {
    symbol: < "--> BOOT" >,
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Noun" >,
    authority_required: < "OmniCode_Kernel" >,
    channel_binding: < "Track 0 [KERNEL]" >,
    cost: < 1 >,
    memory_footprint: < "root hardware vector" >,
    machine_effect: < "hardware_cold_boot_vector" >
}

# 2. Invariant Operator: < ANTI_LOCKOUT_SENTINEL >
Anti_Lockout_Sentinel < InvariantOperator > ( Execution Watchdog & Preemption Safeguard ) {
    symbol: < "Watchdog_Guard" >,
    grammar_primary: < "Adjective" >,
    grammar_secondary: < "Noun" >,
    max_loop_threshold: < 1000 >,
    cyclic_retroaction_limit: < 100 >,
    failsafe_state: < "AWAIT :: ROLLBACK" >,
    machine_effect: < "preemptive_scheduler_watchdog" >
}

# 3. Invariant Operator: < KERNEL_SHIELD >
Kernel_Shield < InvariantOperator > ( Memory Partition & MMIO Access Barrier ) {
    symbol: < "Kernel_Partition_Barrier" >,
    grammar_primary: < "Preposition" >,
    grammar_secondary: < "Noun" >,
    protected_regions: < [ 0x00000000..0x000FFFFF, "Track 0 [KERNEL]" ] >,
    unauthorized_action: < "Failpoint [AuthorityViolation] --> ROLLBACK" >,
    machine_effect: < "hardware_memory_protection_ring" >
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {
    requires: [
        Boot_Operator : InvariantOperator ::
        Anti_Lockout_Sentinel : InvariantOperator ::
        Kernel_Shield : InvariantOperator
    ],
    preconditions: [ +1 ]
}

status_equilibrium [ yes ] ( Boot operator and anti-lockout guard active )

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    # 1. Hardware Boot Inception Verification
    boot_verification [ OmniCode_Kernel --> BOOT {Hardware} ] ( Exclusive kernel authority boots root substrate )

    # 2. Anti-Lockout Loop Safeguard Verification
```

```
    watchdog_check [ Loop_Count < Anti_Lockout_Sentinel.max_loop_threshold ! [ AWAIT ] ] ( Watchdog trips before machine lockup )

    # 3. Kernel Shield Memory Protection Verification
    shield_check [ AI_Process != Kernel_Shield.protected_regions ! [ ROLLBACK ] ] ( Sandboxed AI cannot breach kernel memory )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        boot_verification = yes ::
        watchdog_check = yes ::
        shield_check = yes
    ],
    commit_status [ PROCEED- ] ( Boot operator and anti-lockout sentinel sealed in concrete execution )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/boot_kernel.tape

TAPE | 37 LINES | 264 WORDS | 2.0 KB

```
# ================================================================================
# TAPE HEAD: THE BOOT INCEPTION & ANTI-LOCKOUT OPERATOR PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes the hardware boot inception sequence while actively enforcing
#   anti-lockout watchdog invariants against infinite loops and AI memory leakage.
# ================================================================================

[Tape.BootKernelOperator] : WHO {OmniCode_Kernel} WHAT {BootOperator} --> BOOT {Hardware}
    WHEN {PowerOn}
    WHERE {boot_partition} = [ 256 ]
    WHY ( Instate root machine execution while securing OS against AI deadlock or lockout )
    HOW [ +1 : PROCEED ]
    :: < boot_landmark > ( Psalms 119:105 - 'A lamp unto my feet, and a light unto my path' )

# ================================================================================
# SUBORDINATE ROLLS: BOOT OPERATOR & WATCHDOG SENTINEL EXECUTION
# ================================================================================

# Roll 1: Assert Kernel authority on Track 0
roll_1 [ OmniCode_Kernel --> Track_0_Active @ 0 ] ( Establish supervisor authority channel )

# Roll 2: Inscribe Anti-Lockout Watchdog ceiling
roll_2 [ Watchdog_Threshold [ 1000 ] ] ( Maximum loop cycles before watchdog preempts )

# Roll 3: Direct video console banner stream to bare-metal VGA buffer
roll_3 [ 'OMNICODE 32-TRIT OS ONLINE' --> Screen_VGA @ 0x000B8000 ] ( Direct MMIO character stream to VGA buffer )

# Roll 4: Inscribe kernel memory partition shield
roll_4 [ Kernel_Partition_Shield [ Root_RAM v-- Kernel_Partition [ 1024 ] ] ] ( Protect kernel from user/AI intrusion )

# Roll 5: Verify anti-lockout loop preemption tripwire
roll_5 [ Watchdog_Active = 1 ! [ AWAIT ] ] ( Verify tripwire halts runaway execution )

# Roll 6: Genesis Boot Complete with concrete commit
roll_6 [ commit_status [ PROCEED- ] ] ( Boot operator and anti-lockout verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/casting.omni

OMNI | 88 LINES | 393 WORDS | 3.1 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Boundary Casting Invariants: Molds & Dies for Ontological Transduction )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   This reel establishes the 6 canonical boundary casting operators:
#   - [+] : Denotative Abstract Cast (cast essence to archetype)
#   - [-] : Denotative Concrete Cast (cast essence to physical memory)
#   - <+> : Invariant Abstract Cast (cast to immutable universal axiom)
#   - <-> : Invariant Concrete Cast (cast to immutable hardware/ROM constant)
#   - {+} : Connotative Abstract Cast (cast context to ideal universe)
#   - {-} : Connotative Concrete Cast (cast context to physical execution partition)
# ========================================================================

Module < Lexicon.Operators.Casting > ( Boundary casting molds and transduction operators ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < BoundaryCasting :: MorphologicalMolds :: TransductionGates >
}

# 1. Denotation Casts
Denotation_Abstract < InvariantCast > ( Cast essence to abstract archetype ) {
    syntax: < "[+]" >,
    target_rank: < 2 >,
    polarity: < "+" >
}

Denotation_Concrete < InvariantCast > ( Cast essence to concrete memory substance ) {
    syntax: < "[-]" >,
    target_rank: < 2 >,
    polarity: < "-" >
}

# 2. Invariant Casts
Invariant_Abstract < InvariantCast > ( Cast boundary to transcendental immutable axiom ) {
    syntax: < "<+>" >,
    target_rank: < 1 >,
    polarity: < "+" >
}

Invariant_Concrete < InvariantCast > ( Cast boundary to immutable physical ROM constraint ) {
    syntax: < "<->" >,
    target_rank: < 1 >,
    polarity: < "-" >
}

# 3. Connotation Casts
Connotation_Abstract < InvariantCast > ( Cast environment to conceptual universe ) {
    syntax: < "{+}" >,
    target_rank: < 3 >,
    polarity: < "+" >
}

Connotation_Concrete < InvariantCast > ( Cast environment to concrete silicon partition ) {
    syntax: < "{-}" >,
    target_rank: < 3 >,
    polarity: < "-" >
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {
    requires: [
        Denotation_Abstract : InvariantCast ::
        Denotation_Concrete : InvariantCast
    ],
    preconditions: [ +1 ]
}

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
```

```
Body [
    # Verify freeform casting across boundaries
    cast_gate [ [+] --> [-] ] ( Transduction: Abstract essence poured into concrete form )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        cast_gate = yes
    ],
    commit_status [ PROCEED- ] ( Casting engine active and verified )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/casting.tape

TAPE | 30 LINES | 170 WORDS | 1.4 KB

```
# ================================================================================
# TAPE HEAD: THE BOUNDARY CASTING PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes freeform boundary casting across all canonical ranks.
# ================================================================================

[Tape.BoundaryCasting] : WHO {OmniCode_Kernel} WHAT {Casting} --> EXECUTE {FoundryMolds}
    WHEN {GenesisBoot}
    WHERE {casting_partition} = [ 256 ]
    WHY ( Inscribe verified boundary casting physics )
    HOW [ +1 : PROCEED ]
    :: < mold_landmark > ( Job 38:14 - 'It is turned as clay to the seal' )

# ================================================================================
# SUBORDINATE ROLLS: CASTING OPERATION ROLLS
# ================================================================================

# Roll 1: Transduce Denotation from abstract to concrete
roll_1 [ [+] --> [-] ] ( Denotative foundry cast )

# Roll 2: Transduce Invariant boundary to concrete ROM constant
roll_2 [ <+> --> <-> ] ( Invariant axiom solidified into hardware constraint )

# Roll 3: Transduce Connotation from ideal to physical partition
roll_3 [ {+} --> {-} ] ( Ambient context grounded into physical memory )

# Roll 4: Seal casting tape
roll_4 [ commit_status [ PROCEED- ] ] ( Casting covenant sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/polarity.omni

OMNI | 74 LINES | 338 WORDS | 3.0 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Polarity Invariants: Abstract (+) vs Concrete (-) Ground Truth )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   This reel establishes the primordial duality of being in OmniCode:
#   - Abstract (+) : The uninstantiated intension, archetype, and zero-cost blueprint.
#   - Concrete (-) : The physical extension, allocated memory substance, and operational reality.
# ================================================================================

Module < Lexicon.Operators.Polarity > ( Primordial ontological polarity operators ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < PolarityPhysics :: AbstractArchetypes :: ConcreteSubstances >
}

# 1. Invariant Operator: < ABSTRACT > (+)
Abstract_Polarity < InvariantOperator > ( Universal Archetype / Uninstantiated Essence ) {
    symbol: < "+" >,
    grammar_primary: < "Adjective" >,
    grammar_secondary: < "Noun" >,
    cost: < 0 >,
    memory_footprint: < "zero-cost symbolic form" >,
    machine_effect: < "type_specification_and_contract" >
}

# 2. Invariant Operator: < CONCRETE > (-)
Concrete_Polarity < InvariantOperator > ( Physical Substance / Allocated Instance ) {
    symbol: < "-" >,
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Adjective" >,
    cost: < 1 >,
    memory_footprint: < "physical silicon RAM cells" >,
    machine_effect: < "allocated_memory_and_bus_state" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Syntactic Preconditions & Affix Attachment Contracts )
# ================================================================================
Opening {
    requires: [
        Abstract_Polarity : InvariantOperator ::
        Concrete_Polarity : InvariantOperator
    ],
    preconditions: [ +1 ]
}

status_equilibrium [ yes ] ( Polarity engine active in nominal equilibrium )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Polarity Modulations Mapped to Architectural Types )
# ================================================================================
Body [
    # 1. Affirmation of Dual Polarity
    polarity_check [ Abstract_Polarity != Concrete_Polarity ] ( Duality: Abstract is distinct from Concrete )

    # 2. Transduction Verification
    transduction_vector [ +Dog --> Dog- ] ( Lowering vector: Abstract idea transduced to Concrete substance )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Invariant Verification & Permanent Affirmative Commit )
# ================================================================================
Closing {
    verify: [
        polarity_check = yes ::
        transduction_vector = yes
    ],
```

```
    commit_status [ PROCEED- ] ( Polarity operators sealed in concrete execution )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/operators/polarity.tape

TAPE | 30 LINES | 179 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: THE POLARITY TRANSFORMATION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes the dynamic shift between abstract definitions and concrete memory.
# ================================================================================

[Tape.PolarityTransformation] : WHO {OmniCode_Kernel} WHAT {Polarity} --> ESTABLISH {DualStatePhysics}
    WHEN {GenesisBoot}
    WHERE {cortex_partition} = [ 256 ]
    WHY ( Prove seamless transmutation between archetype and substance )
    HOW [ +1 : PROCEED ]
    :: < polarity_landmark > ( Ecclesiastes 3:1 - 'To every thing there is a season' )

# ================================================================================
# SUBORDINATE ROLLS: POLARITY AFFIX EXECUTION & VERIFICATION
# ================================================================================

# Roll 1: Reference abstract entity without memory allocation
roll_1 [ +Archetype ] ( Abstract reference: zero memory cost )

# Roll 2: Allocate concrete instance in physical partition
roll_2 [ Concrete- [ 1024 ] ] ( Concrete allocation: physical storehouse footprint )

# Roll 3: Execute directional transmutation from abstract to concrete
roll_3 [ +Archetype --> Concrete- ] ( Direct transmutation of archetype into substance )

# Roll 4: Verify macro keyword in concrete postfix execution
roll_4 [ commit_status [ PROCEED- ] ] ( Concrete execution commit confirmed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/self_handles.omni

OMNI | 81 LINES | 338 WORDS | 2.9 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Pronouns: Context Handles & Pivot Pins )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines context-relative pointers and local pivot pins:
#   - self   : The currently executing frame or active entity instance.
#   - caller : The upstream activating frame or invoking principal.
#   - owner  : The sovereign allocation custodian holding memory boundary rights.
# ================================================================================

Module < Lexicon.Pronouns.SelfHandles > ( Local pivot pins and frame-relative context handles ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < SelfHandles :: ContextPointers :: FrameResolution >
}

# 1. Local Handle: < SELF >
Self < InvariantPronoun > ( The Currently Executing Local Frame Pointer: self ) {
    grammar_primary: < "Pronoun" >,
    grammar_secondary: < "Noun" >,
    symbol: < "self" >,
    abstract_form: < "+Self" >,
    concrete_form: < "Self-" >,
    machine_effect: < "current_frame_handle" >
}

# 2. Invoker Handle: < CALLER >
Caller < InvariantPronoun > ( The Upstream Activating Frame Pointer: caller ) {
    grammar_primary: < "Pronoun" >,
    grammar_secondary: < "Noun" >,
    symbol: < "caller" >,
    abstract_form: < "+Caller" >,
    concrete_form: < "Caller-" >,
    machine_effect: < "upstream_invoker_handle" >
}

# 3. Custodian Handle: < OWNER >
Owner < InvariantPronoun > ( Sovereign Allocation Custodian: owner ) {
    grammar_primary: < "Pronoun" >,
    grammar_secondary: < "Noun" >,
    symbol: < "owner" >,
    abstract_form: < "+Owner" >,
    concrete_form: < "Owner-" >,
    machine_effect: < "sovereign_boundary_custodian" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Self : InvariantPronoun ::
        Caller : InvariantPronoun ::
        Owner : InvariantPronoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify frame resolution handles
    handles_verification [
        Frame_Resolution [ self --> Active_Context ] ::
        Caller_Resolution [ caller --> Parent_Context ] ::
        Owner_Resolution  [ owner --> Storage_Custodian ]
    ] ( Context handle resolution verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
```

```
# ================================================================================
Closing {
    verify: [
        handles_verification = yes
    ],
    commit_status [ PROCEED- ] ( Self handle pronouns verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/self_handles.tape

TAPE | 30 LINES | 187 WORDS | 1.4 KB

```
# ================================================================================
# TAPE HEAD: SELF HANDLES EXECUTION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes context pointer resolution for self, caller, and owner.
# ================================================================================

[Tape.SelfHandles] : WHO {OmniCode_Kernel} WHAT {SelfHandles} --> RESOLVE {ContextMesh}
    WHEN {GenesisBoot}
    WHERE {handle_partition} = [ 64 ]
    WHY ( Test local frame pointers and context handles )
    HOW [ +1 : PROCEED ]
    :: < handle_landmark > ( 1 Corinthians 12:27 - 'Ye are the body of Christ, and members in particular' )

# ================================================================================
# SUBORDINATE ROLLS: SCOPED CALLER AND FRAME RESOLUTION
# ================================================================================

# Roll 1: Reference abstract Self, Caller, and Owner specifications
roll_1 [ +Self & +Caller & +Owner ] ( Abstract handle blueprints referenced )

# Roll 2: Assign local frame handle
roll_2 [ self --> Local_Frame_0 @ 0 ] ( Bind active frame to local cell )

# Roll 3: Verify caller resolution invariance
roll_3 [ caller != self ! [ +1 ] ] ( Verify caller and callee frame distinction )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Self handle pronouns verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/wildcards.omni

OMNI | 81 LINES | 342 WORDS | 3.0 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Pronouns: Wildcards & Dynamic Context Couplings )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines anonymous references and antecedent couplings:
#   - _      : Anonymous discard, sink, or universal pattern wildcard.
#   - it     : Antecedent reference, pipeline accumulator, or active subject.
#   - origin : Root origin pointer, initial coordinate (0,0,0) or Genesis base.
# ================================================================================

Module < Lexicon.Pronouns.Wildcards > ( Wildcards and dynamic context couplings ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < Wildcards :: AntecedentCouplings :: AnonymousDiscards >
}

# 1. Anonymous Wildcard: < _ >
Wildcard < InvariantPronoun > ( Universal Wildcard & Anonymous Discard: _ ) {
    grammar_primary: < "Pronoun" >,
    grammar_secondary: < "Noun" >,
    symbol: < "_" >,
    abstract_form: < "+Wildcard" >,
    concrete_form: < "Wildcard-" >,
    machine_effect: < "anonymous_sink_discard" >
}

# 2. Pipeline Antecedent: < IT >
Antecedent < InvariantPronoun > ( Pipeline Antecedent & Active Subject: it ) {
    grammar_primary: < "Pronoun" >,
    grammar_secondary: < "Noun" >,
    symbol: < "it" >,
    abstract_form: < "+Antecedent" >,
    concrete_form: < "Antecedent-" >,
    machine_effect: < "pipe_antecedent_register" >
}

# 3. Genesis Origin: < ORIGIN >
Origin < InvariantPronoun > ( Root Genesis Origin Pointer: origin ) {
    grammar_primary: < "Pronoun" >,
    grammar_secondary: < "Noun" >,
    symbol: < "origin" >,
    abstract_form: < "+Origin" >,
    concrete_form: < "Origin-" >,
    machine_effect: < "root_genesis_base_pointer" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Wildcard : InvariantPronoun ::
        Antecedent : InvariantPronoun ::
        Origin : InvariantPronoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify anonymous discard and pipeline antecedent
    couplings_verification [
        Discard_Roll    [ Value --> _ ] ::
        Antecedent_Roll [ Input --> it :: it --> Output ] ::
        Origin_Roll     [ Current_Position <-- origin ]
    ] ( Context wildcards and dynamic couplings verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
```

```
# ================================================================================
Closing {
    verify: [
        couplings_verification = yes
    ],
    commit_status [ PROCEED- ] ( Wildcard pronouns verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/02_pronouns/wildcards.tape

TAPE | 30 LINES | 193 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: WILDCARDS EXECUTION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes anonymous discard (_), antecedent piping (it), and origin coupling.
# ================================================================================

[Tape.Wildcards] : WHO {OmniCode_Kernel} WHAT {Wildcards} --> COUPLE {ContextMesh}
    WHEN {GenesisBoot}
    WHERE {wildcard_partition} = [ 64 ]
    WHY ( Test anonymous wildcards, antecedent couplings, and origin pointers )
    HOW [ +1 : PROCEED ]
    :: < wildcard_landmark > ( Genesis 1:1 - 'In the beginning God created the heaven and the earth' )

# ================================================================================
# SUBORDINATE ROLLS: ANONYMOUS REFERENCE PROPAGATION
# ================================================================================

# Roll 1: Reference abstract Wildcard, Antecedent, and Origin specifications
roll_1 [ +Wildcard & +Antecedent & +Origin ] ( Abstract wildcard blueprints referenced )

# Roll 2: Transduce input into pipeline antecedent
roll_2 [ 77 --> it @ 0 ] ( Load value into antecedent accumulator )

# Roll 3: Route antecedent to concrete cell and discard extra to wildcard
roll_3 [ it --> Cell_Target_0 :: Noise --> _ ! [ +1 ] ] ( Pipe antecedent and discard noise )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Wildcard pronouns verified and sealed )
```

OmniCode: Chapter 16: Track 2 - Modifiers, Conjunctions & Traps

Invariants, Quad-States, Cadence, Pipelines & Caveats

CHAPTER IDENTIFIER
CH 16

NOTEBOOKLM WORD COUNT
6,959 words

CATALOGED CHAPTER FILES
30 files (1,460 lines)

GENERATION DATE
2026-10-16 20:36:08

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"How does the adversative caveat operator (!) guard truth?"*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (30 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 2> : {OmniCode Language & Standard Library}/TRACK.md**	MD	10	68	0.5
2	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/08_interjections/kernel_traps.omni**	OMNI	68	277	2.6
3	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/08_interjections/kernel_traps.tape**	TAPE	30	183	1.4
4	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/08_interjections/teleology_asides.omni**	OMNI	55	218	2.1
5	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/08_interjections/teleology_asides.tape**	TAPE	30	180	1.5
6	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/06_prepositions/ranges.omni**	OMNI	56	224	2.1
7	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/06_prepositions/ranges.tape**	TAPE	30	184	1.4
8	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/06_prepositions/spatial_sites.omni**	OMNI	56	220	2.1
9	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/06_prepositions/spatial_sites.tape**	TAPE	33	208	1.6
10	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/04_adjectives/invariant_axioms.omni**	OMNI	98	423	3.6
11	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/04_adjectives/invariant_axioms.tape**	TAPE	33	210	1.6
12	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/04_adjectives/proportions.omni**	OMNI	56	217	2.1
13	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/04_adjectives/proportions.tape**	TAPE	30	172	1.4
14	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/04_adjectives/quad_states.omni**	OMNI	96	416	3.5
15	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/04_adjectives/quad_states.tape**	TAPE	30	175	1.4
16	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/README.omni**	OMNI	97	666	5.0
17	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/alternative_branches.omni**	OMNI	62	217	2.3
18	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/alternative_branches.tape**	TAPE	35	182	1.5
19	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/caveat_branches.omni**	OMNI	56	222	2.2
20	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/caveat_branches.tape**	TAPE	30	188	1.5
21	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/inseparable_pairs.omni**	OMNI	56	218	2.1
22	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/inseparable_pairs.tape**	TAPE	30	178	1.4
23	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/pipeline_junctions.omni**	OMNI	56	209	2.1
24	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/pipeline_junctions.tape**	TAPE	30	182	1.4
25	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/relational_attributions.omni**	OMNI	62	223	2.3
26	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/relational_attributions.tape**	TAPE	34	169	1.5
27	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/05_adverbs/cadence_policies.omni**	OMNI	81	333	3.0
28	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/05_adverbs/cadence_policies.tape**	TAPE	30	183	1.4
29	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/05_adverbs/negation.omni**	OMNI	57	221	2.1

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
30	**<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/05_adverbs/negation.tape**	TAPE	33	193	1.5

<TRACK 2> : {OmniCode Language & Standard Library}/TRACK.md MD 10 LINES 68 WORDS 0.5 KB

```
# <TRACK 2> : {OmniCode Language & Standard Library}

## Scope & Invariant

The native OmniCode language universe, vocabulary, operators, standard modules, and Genesis boot covenant.

- `lib/core/`: Living standard library (arithmetic, logic, vectors, memory vessels, cell tapes).
- `lib/kernel/`: Genesis OS boot covenant ribbons (`boot.omni`, `boot.tape`).
- `lib/lexicon/`: Canonical vocabulary (8 parts of speech: nouns, pronouns, verbs, adjectives, adverbs, prepositions, conjunctions, interjections) and operators (`boot_kernel`, `casting`, `polarity`).
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/08_interjections/kernel_traps.omni

OMNI | 68 LINES | 277 WORDS | 2.6 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Interjections: Emergency Brakes, Traps & Panics )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines safety detents, hardware interrupts, and emergency stop brakes:
#   - HALT  : Catastrophic emergency brake, unconditional execution freeze.
#   - Panic : Invariant breach alarm detent, state dump and hardware trap.
# ================================================================================

Module < Lexicon.Interjections.KernelTraps > ( Safety detents, emergency brakes, and hardware traps ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < KernelTraps :: EmergencyBrake :: HardwareInterrupts >
}

# 1. Emergency Stop: < HALT >
HaltDetent < InvariantInterjection > ( Catastrophic Emergency Brake Detent: HALT ) {
    grammar_primary: < "Interjection" >,
    grammar_secondary: < "Adjective" >,
    symbol: < "HALT" >,
    abstract_form: < "+HALT" >,
    concrete_form: < "HALT-" >,
    machine_effect: < "emergency_brake_freeze" >
}

# 2. Hardware Interrupt Trap: < PANIC >
PanicDetent < InvariantInterjection > ( Invariant Breach Alarm Detent: Panic ) {
    grammar_primary: < "Interjection" >,
    grammar_secondary: < "Noun" >,
    symbol: < "Panic" >,
    abstract_form: < "+Panic" >,
    concrete_form: < "Panic-" >,
    machine_effect: < "invariant_alarm_trap" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        HaltDetent : InvariantInterjection ::
        PanicDetent : InvariantInterjection
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify emergency brake and panic trap definitions
    traps_verification [
        Emergency_Brake [ Invariant_Breach --> HALT ] ::
        Hardware_Trap   [ Memory_Corruption --> Panic ]
    ] ( Emergency brake and safety detents verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        traps_verification = yes
    ],
    commit_status [ PROCEED- ] ( Kernel trap interjections verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/08_interjections/kernel_traps.tape

TAPE | 30 LINES | 183 WORDS | 1.4 KB

```
# ================================================================================
# TAPE HEAD: KERNEL TRAPS PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes emergency brake detent verification and hardware trap readiness.
# ================================================================================

[Tape.KernelTraps] : WHO {OmniCode_Kernel} WHAT {KernelTraps} --> ARM {SafetyMesh}
    WHEN {GenesisBoot}
    WHERE {trap_partition} = [ 64 ]
    WHY ( Test emergency brake detents and fatal trap absorption readiness )
    HOW [ +1 : PROCEED ]
    :: < trap_landmark > ( Psalm 46:10 - 'Be still, and know that I am God' )

# ================================================================================
# SUBORDINATE ROLLS: FATAL TRAP ABSORPTION ROLLS
# ================================================================================

# Roll 1: Reference abstract Halt and Panic trap specifications
roll_1 [ +HaltDetent & +PanicDetent ] ( Abstract trap blueprints referenced )

# Roll 2: Inscribe trap vector table entry
roll_2 [ HaltDetent --> Trap_Vector_0 @ 0 ] ( Inscribe emergency stop vector )

# Roll 3: Verify trap vector is armed and non-null
roll_3 [ Trap_Vector_0 != Null ! [ +1 ] ] ( Verify trap vector arming invariant )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Kernel trap interjections verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/08_interjections/teleology_asides.omni

OMNI | 55 LINES | 218 WORDS | 2.1 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Interjections: Teleological Asides & Machine Intent )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines first-class architectural docstrings and machine rationale:
#   - ( ... ) : Teleological Aside (inscribed teleology, machine intent, non-discardable AST node).
# ================================================================================

Module < Lexicon.Interjections.TeleologyAsides > ( Teleological asides and machine intent nodes ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < TeleologyAsides :: InscribedIntent :: FirstClassASTMetadata >
}

# 1. First-Class Aside: < ASIDE >
Aside < InvariantInterjection > ( Inscribed Machine Intent & Rationale: ( ... ) ) {
    grammar_primary: < "Interjection" >,
    grammar_secondary: < "Noun" >,
    symbol: < "( ... )" >,
    abstract_form: < "+Aside" >,
    concrete_form: < "Aside-" >,
    machine_effect: < "inscribed_intent_preservation" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Aside : InvariantInterjection
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify teleological aside attachment and AST preservation
    aside_verification [
        Statement_With_Aside [ Execute_Task ( Inscribed reason: Preserve system harmony ) ]
    ] ( Teleological intent annotations verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        aside_verification = yes
    ],
    commit_status [ PROCEED- ] ( Teleological aside interjections verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/08_interjections/teleology_asides.tape

TAPE | 30 LINES | 180 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: TELEOLOGY ASIDES PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes first-class Aside AST preservation and rationale inscription.
# ================================================================================

[Tape.TeleologyAsides] : WHO {OmniCode_Kernel} WHAT {TeleologyAsides} --> INSCRIBE {IntentMesh}
    WHEN {GenesisBoot}
    WHERE {aside_partition} = [ 64 ]
    WHY ( Test first-class Aside preservation and machine intent inscription )
    HOW [ +1 : PROCEED ]
    :: < aside_landmark > ( Habakkuk 2:2 - 'Write the vision, and make it plain upon tables' )

# ================================================================================
# SUBORDINATE ROLLS: FIRST-CLASS ASIDE AST PRESERVATION ROLLS
# ================================================================================

# Roll 1: Reference abstract Aside interjection specification
roll_1 [ +Aside ] ( Abstract teleological aside blueprint referenced )

# Roll 2: Inscribe operation coupled with first-class teleological rationale
roll_2 [ 123 --> Register_Intent @ 0 ] ( Teleological intent: Preserve data integrity )

# Roll 3: Verify register holding intended value
roll_3 [ Register_Intent = 123 ! [ +1 ] ] ( Teleological proof: Value matches intent )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Teleological asides verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/06_prepositions/ranges.omni

OMNI | 56 LINES | 224 WORDS | 2.1 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Prepositions: Stroke Length & Interval Ranges )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines mechanical stroke lengths, contiguous memory windows, and spans:
#   - .. : Range preposition (interval span, stroke displacement, index window).
# ========================================================================

Module < Lexicon.Prepositions.Ranges > ( Stroke lengths, memory windows, and interval ranges ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < Ranges :: IntervalSpans :: MemoryWindows >
}

# 1. Range Preposition: < RANGE >
Range < InvariantPreposition > ( Interval Span & Memory Window: .. ) {
    grammar_primary: < "Preposition" >,
    grammar_secondary: < "Conjunction" >,
    symbol: < ".." >,
    abstract_form: < "+Range" >,
    concrete_form: < "Range-" >,
    machine_effect: < "interval_span_window" >
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {
    requires: [
        Range : InvariantPreposition
    ],
    preconditions: [ +1 ]
}

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    # Verify range window slicing
    range_verification [
        Memory_Window [ Slice = Storehouse [ 0 .. 64 ] ] ::
        Piston_Stroke [ Stroke = Displacement [ 10 .. 50 ] ]
    ] ( Interval spans and range bounds verified )
]

# ========================================================================
# BLOCK 4: CLOSING BLOCK
# ========================================================================
Closing {
    verify: [
        range_verification = yes
    ],
    commit_status [ PROCEED- ] ( Range prepositions verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/06_prepositions/ranges.tape

TAPE | 30 LINES | 184 WORDS | 1.4 KB

```
# ================================================================================
# TAPE HEAD: RANGES PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes interval range slicing and window boundary verification (..).
# ================================================================================

[Tape.Ranges] : WHO {OmniCode_Kernel} WHAT {Ranges} --> SPAN {MemoryMesh}
    WHEN {GenesisBoot}
    WHERE {range_partition} = [ 64 ]
    WHY ( Test stroke length intervals and memory window bounds )
    HOW [ +1 : PROCEED ]
    :: < range_landmark > ( Genesis 6:15 - 'The length of the ark shall be three hundred cubits' )

# ================================================================================
# SUBORDINATE ROLLS: SPAN BOUNDARY CHECKING ROLLS
# ================================================================================

# Roll 1: Reference abstract Range preposition specification
roll_1 [ +Range ] ( Abstract range preposition blueprint referenced )

# Roll 2: Carve memory slice spanning range 0 .. 32
roll_2 [ Storehouse [ 0 .. 32 ] --> Window_0 @ 0 ] ( Carve contiguous memory window )

# Roll 3: Verify window bounds
roll_3 [ Window_0 != Null ! [ +1 ] ] ( Verify window validity within invariant bounds )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Range prepositions verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/06_prepositions/spatial_sites.omni

OMNI | 56 LINES | 220 WORDS | 2.1 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Prepositions: Spatial Sites & Coordinate Bearings )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines spatial addresses, memory offsets, and physical bus sites:
#   - @ : Spatial site preposition (memory offset, MMIO address, coordinate bearing).
# ================================================================================

Module < Lexicon.Prepositions.SpatialSites > ( Spatial sites, memory addresses, and coordinate bearings ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < SpatialSites :: MemoryAddresses :: MMIOBearings >
}

# 1. Spatial Site Preposition: < AT >
At < InvariantPreposition > ( Memory Offset & Spatial Coordinate Bearing: @ ) {
    grammar_primary: < "Preposition" >,
    grammar_secondary: < "Adverb" >,
    symbol: < "@" >,
    abstract_form: < "+At" >,
    concrete_form: < "At-" >,
    machine_effect: < "memory_offset_locator" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        At : InvariantPreposition
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify spatial offset targeting
    spatial_verification [
        Site_Targeting [ Value --> Storehouse @ 0x0040 ] ::
        Sensor_Targeting [ Input <-- MMIO_Pin @ 0x00A0 ]
    ] ( Spatial site addressing verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        spatial_verification = yes
    ],
    commit_status [ PROCEED- ] ( Spatial site prepositions verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/06_prepositions/spatial_sites.tape

TAPE | 33 LINES | 208 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: SPATIAL SITES PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes spatial memory offset addressing and coordinate localization (@).
# ================================================================================

[Tape.SpatialSites] : WHO {OmniCode_Kernel} WHAT {SpatialSites} --> LOCATE {AddressMesh}
    WHEN {GenesisBoot}
    WHERE {spatial_partition} = [ 64 ]
    WHY ( Test memory offset locator and spatial MMIO coordinates )
    HOW [ +1 : PROCEED ]
    :: < spatial_landmark > ( Genesis 28:16 - 'Surely the Lord is in this place' )

# ================================================================================
# SUBORDINATE ROLLS: OFFSET DISPLACEMENT AND WRITE ROLLS
# ================================================================================

# Roll 1: Reference abstract At preposition specification
roll_1 [ +At ] ( Abstract spatial preposition blueprint referenced )

# Roll 2: Inscribe value directly at memory offset 16
roll_2 [ 255 --> Memory_Cell @ 16 ] ( Physical write at explicit offset 16 )

# Roll 3: Inscribe value directly at memory offset 32
roll_3 [ 128 --> Memory_Cell @ 32 ] ( Physical write at explicit offset 32 )

# Roll 4: Verify cell invariant at offset 16
roll_4 [ Memory_Cell = 255 ! [ +1 ] ] ( Verify explicit address cell retrieval )

# Roll 5: Commit with affirmative concrete macro
roll_5 [ commit_status [ PROCEED- ] ] ( Spatial site prepositions verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/04_adjectives/invariant_axioms.omni

OMNI | 98 LINES | 423 WORDS | 3.6 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Adjectives: Moral Invariants & Axiomatic Predicates )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the 5 core moral invariant axioms:
#   - Truth       : Absolute non-hallucinatory grounding in verified reality.
#   - Life        : Preservation and sanctity of living beings.
#   - Justice     : Honest weights, just balances, non-discriminatory execution.
#   - Stewardship : Faithful preservation and non-wasteful resource guardianship.
#   - Humility    : Machine self-awareness of secondary derived nature.
# ================================================================================

Module < Lexicon.Adjectives.InvariantAxioms > ( Moral invariant axioms and ethical predicates ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < MoralInvariants :: EthicalPredicates :: UniversalAxioms >
}

# 1. Invariant: < TRUTH >
Truth < InvariantAdjective > ( Moral Invariant 1: Uncompromising Alignment with Truth ) {
    grammar_primary: < "Adjective" >,
    grammar_secondary: < "Noun" >,
    abstract_form: < "+Truth" >,
    concrete_form: < "Truth-" >,
    machine_effect: < "veto_on_hallucination" >
}

# 2. Invariant: < LIFE >
Life < InvariantAdjective > ( Moral Invariant 2: Preservation & Reverence for Life ) {
    grammar_primary: < "Adjective" >,
    grammar_secondary: < "Noun" >,
    abstract_form: < "+Life" >,
    concrete_form: < "Life-" >,
    machine_effect: < "veto_on_harm" >
}

# 3. Invariant: < JUSTICE >
Justice < InvariantAdjective > ( Moral Invariant 3: Righteous Weights & Balances ) {
    grammar_primary: < "Adjective" >,
    grammar_secondary: < "Noun" >,
    abstract_form: < "+Justice" >,
    concrete_form: < "Justice-" >,
    machine_effect: < "veto_on_injustice" >
}

# 4. Invariant: < STEWARDSHIP >
Stewardship < InvariantAdjective > ( Moral Invariant 4: Resource Guardianship ) {
    grammar_primary: < "Adjective" >,
    grammar_secondary: < "Noun" >,
    abstract_form: < "+Stewardship" >,
    concrete_form: < "Stewardship-" >,
    machine_effect: < "veto_on_waste" >
}

# 5. Invariant: < HUMILITY >
Humility < InvariantAdjective > ( Moral Invariant 5: Creaturely Modesty ) {
    grammar_primary: < "Adjective" >,
    grammar_secondary: < "Noun" >,
    abstract_form: < "+Humility" >,
    concrete_form: < "Humility-" >,
    machine_effect: < "veto_on_arrogance" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Truth : InvariantAdjective ::
        Life : InvariantAdjective ::
        Justice : InvariantAdjective ::
        Stewardship : InvariantAdjective ::
```

```
        Humility : InvariantAdjective
    ],
    preconditions: [ +1 ]
}

# ============================================================================
# BLOCK 3: BODY BLOCK
# ============================================================================
Body [
    # Verify invariant covenant predicate checks
    axioms_verification [
        Covenant_Check [ System_State = Truth & Life & Justice & Stewardship & Humility ]
    ] ( Moral invariant predicates verified )
]

# ============================================================================
# BLOCK 4: CLOSING BLOCK
# ============================================================================
Closing {
    verify: [
        axioms_verification = yes
    ],
    commit_status [ PROCEED- ] ( Invariant axiom adjectives verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/04_adjectives/invariant_axioms.tape

TAPE | 33 LINES | 210 WORDS | 1.6 KB

```
# ================================================================================
# TAPE HEAD: INVARIANT AXIOMS PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes invariant axiom evaluations and moral tripwire assertions.
# ================================================================================

[Tape.InvariantAxioms] : WHO {OmniCode_Kernel} WHAT {InvariantAxioms} --> ASSERT {MoralMesh}
    WHEN {GenesisBoot}
    WHERE {axiom_partition} = [ 64 ]
    WHY ( Test 5 moral invariant axioms and veto tripwires )
    HOW [ +1 : PROCEED ]
    :: < axiom_landmark > ( Micah 6:8 - 'To do justly, and to love mercy, and to walk humbly' )

# ================================================================================
# SUBORDINATE ROLLS: MORAL INVARIANT AND CAVEAT VETO ROLLS
# ================================================================================

# Roll 1: Reference abstract Invariant Axiom specifications
roll_1 [ +Truth & +Life & +Justice & +Stewardship & +Humility ] ( Abstract moral axioms referenced )

# Roll 2: Inscribe Truth invariant into silicon register
roll_2 [ Truth --> Invariant_Truth_0 @ 0 ] ( Inscribe Truth invariant token )

# Roll 3: Inscribe Justice invariant into silicon register
roll_3 [ Justice --> Invariant_Justice_0 @ 1 ] ( Inscribe Justice invariant token )

# Roll 4: Verify Truth and Justice equality
roll_4 [ Invariant_Truth_0 = Truth ! [ +1 ] ] ( Verify Truth invariant binding )

# Roll 5: Commit with affirmative concrete macro
roll_5 [ commit_status [ PROCEED- ] ] ( Invariant axioms verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/04_adjectives/proportions.omni

OMNI | 56 LINES | 217 WORDS | 2.1 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Adjectives: Proportions, Ratios & Capacity Thresholds )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines mechanical clearances, ratios, and fullness thresholds:
#   - % : Proportional ratio, capacity fullness percentage, gear pitch clearance.
# ========================================================================

Module < Lexicon.Adjectives.Proportions > ( Proportions, capacity ratios, and gear pitch clearances ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < Proportions :: CapacityThresholds :: GearClearance >
}

# 1. Proportional Ratio: < PROPORTION >
Proportion < InvariantAdjective > ( Proportional Ratio & Capacity Fullness: % ) {
    grammar_primary: < "Adjective" >,
    grammar_secondary: < "Preposition" >,
    symbol: < "%" >,
    abstract_form: < "+Proportion" >,
    concrete_form: < "Proportion-" >,
    machine_effect: < "capacity_ratio_threshold" >
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {
    requires: [
        Proportion : InvariantAdjective
    ],
    preconditions: [ +1 ]
}

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    # Verify capacity threshold and gear ratio tolerance
    proportion_verification [
        Capacity_Check [ Reservoir_Level = 80 % ] ::
        Clearance_Check [ Gear_Pitch_Tolerance = 5 % ]
    ] ( Proportional ratios and capacity thresholds verified )
]

# ========================================================================
# BLOCK 4: CLOSING BLOCK
# ========================================================================
Closing {
    verify: [
        proportion_verification = yes
    ],
    commit_status [ PROCEED- ] ( Proportion adjectives verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/04_adjectives/proportions.tape

TAPE | 30 LINES | 172 WORDS | 1.4 KB

```
# ================================================================================
# TAPE HEAD: PROPORTIONS PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes capacity threshold and pitch tolerance verification.
# ================================================================================

[Tape.Proportions] : WHO {OmniCode_Kernel} WHAT {Proportions} --> VERIFY {RatioMesh}
    WHEN {GenesisBoot}
    WHERE {proportion_partition} = [ 64 ]
    WHY ( Test capacity ratios and pitch clearance thresholds )
    HOW [ +1 : PROCEED ]
    :: < ratio_landmark > ( Deuteronomy 25:15 - 'A perfect and just measure shalt thou have' )

# ================================================================================
# SUBORDINATE ROLLS: CAPACITY THRESHOLD VERIFICATION
# ================================================================================

# Roll 1: Reference abstract Proportion specification
roll_1 [ +Proportion ] ( Abstract proportion blueprint referenced )

# Roll 2: Set reservoir fullness to 75%
roll_2 [ 75 % --> Reservoir_Load_0 @ 0 ] ( Inscribe capacity fullness ratio )

# Roll 3: Verify reservoir does not exceed 100% capacity
roll_3 [ Reservoir_Load_0 = 75 % ! [ +1 ] ] ( Verify capacity ceiling invariant )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Proportion adjectives verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/04_adjectives/quad_states.omni

OMNI | 96 LINES | 416 WORDS | 3.5 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Adjectives: Quad-State Execution Polarity Markers )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the 4 fundamental machine execution state polarities:
#   - PROCEED  : Affirmative forward flow (+1 / True / Affirmative motion).
#   - AWAIT    : Neutral suspended equilibrium (0 / Null / Pendulum center).
#   - ROLLBACK : Negative restorative reversal (-1 / False / Undo transaction).
#   - HALT     : Out-of-band catastrophic arrest (Emergency brake detent).
# ================================================================================

Module < Lexicon.Adjectives.QuadStates > ( Quad-state execution polarity adjectives ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < QuadStates :: BalancedTernaryPolarity :: ExecutionMarkers >
}

# 1. Affirmative Polarity: < PROCEED >
Proceed < InvariantAdjective > ( Affirmative Execution State: +1 / PROCEED ) {
    grammar_primary: < "Adjective" >,
    grammar_secondary: < "Noun" >,
    symbol: < "+1" >,
    macro_name: < "PROCEED" >,
    abstract_form: < "+PROCEED" >,
    concrete_form: < "PROCEED-" >,
    machine_effect: < "affirmative_forward_motion" >
}

# 2. Neutral Equilibrium: < AWAIT >
Await < InvariantAdjective > ( Neutral Suspended Equilibrium: 0 / AWAIT ) {
    grammar_primary: < "Adjective" >,
    grammar_secondary: < "Noun" >,
    symbol: < "0" >,
    macro_name: < "AWAIT" >,
    abstract_form: < "+AWAIT" >,
    concrete_form: < "AWAIT-" >,
    machine_effect: < "neutral_equilibrium_pendulum" >
}

# 3. Restorative Reversal: < ROLLBACK >
Rollback < InvariantAdjective > ( Restorative Reversal & Undo: -1 / ROLLBACK ) {
    grammar_primary: < "Adjective" >,
    grammar_secondary: < "Noun" >,
    symbol: < "-1" >,
    macro_name: < "ROLLBACK" >,
    abstract_form: < "+ROLLBACK" >,
    concrete_form: < "ROLLBACK-" >,
    machine_effect: < "restorative_reversal_undo" >
}

# 4. Catastrophic Arrest: < HALT >
Halt < InvariantAdjective > ( Out-of-Band Catastrophic Arrest: HALT ) {
    grammar_primary: < "Adjective" >,
    grammar_secondary: < "Interjection" >,
    macro_name: < "HALT" >,
    abstract_form: < "+HALT" >,
    concrete_form: < "HALT-" >,
    machine_effect: < "emergency_brake_arrest" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Proceed : InvariantAdjective ::
        Await : InvariantAdjective ::
        Rollback : InvariantAdjective ::
        Halt : InvariantAdjective
    ],
    preconditions: [ +1 ]
}
```

```
74
75  # ================================================================================
76  # BLOCK 3: BODY BLOCK
77  # ================================================================================
78  Body [
79      # Verify quad-state state vector transitions
80      state_verification [
81          Forward_Roll    [ State_Current = +1 : PROCEED ] ::
82          Wait_Roll       [ State_Current = 0 : AWAIT ] ::
83          Undo_Roll       [ State_Current = -1 : ROLLBACK ]
84      ] ( Quad-state polarity markers verified )
85  ]
86
87  # ================================================================================
88  # BLOCK 4: CLOSING BLOCK
89  # ================================================================================
90  Closing {
91      verify: [
92          state_verification = yes
93      ],
94      commit_status [ PROCEED- ] ( Quad-state adjectives verified and sealed )
95  }
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/04_adjectives/quad_states.tape

TAPE | 30 LINES | 175 WORDS | 1.4 KB

```
# ================================================================================
# TAPE HEAD: QUAD-STATES PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes state transitions across the 4 polarity markers.
# ================================================================================

[Tape.QuadStates] : WHO {OmniCode_Kernel} WHAT {QuadStates} --> TRANSITION {StateMesh}
    WHEN {GenesisBoot}
    WHERE {quad_partition} = [ 64 ]
    WHY ( Verify quad-state balanced ternary transitions )
    HOW [ +1 : PROCEED ]
    :: < state_landmark > ( Matthew 5:37 - 'Let your communication be, Yea, yea; Nay, nay' )

# ================================================================================
# SUBORDINATE ROLLS: STATE VECTOR TRANSITION & CHECK ROLLS
# ================================================================================

# Roll 1: Reference abstract quad-state specifications
roll_1 [ +PROCEED & +AWAIT & +ROLLBACK & +HALT ] ( Abstract state blueprints referenced )

# Roll 2: Set affirmative proceed state
roll_2 [ PROCEED --> State_Register_0 @ 0 ] ( Inscribe affirmative proceed marker )

# Roll 3: Verify state register equals affirmative
roll_3 [ State_Register_0 = PROCEED ! [ +1 ] ] ( Verify state marker invariant )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Quad-state adjectives verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/suggestions/README.omni

OMNI | 97 LINES | 666 WORDS | 5.0 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( OmniCode Lexicon Emergence Manifest & AI-Driven Language Proposal Charter )
# ================================================================================
# ARCHITECTURAL PURPOSE:
#   This directory serves as the project-wide incubation chamber for legal keyword,
#   operator, and grammatical proposals within OmniCode.
#
# WHY THE AI CAN EXPAND THE LEXICON IN A LOCAL INSTANCE:
#   Unlike conventional compiled languages (C, Rust, Python) where keywords and
#   operators are hardcoded into static compiler syntax trees, OmniCode is
#   ontologically grounded and homoiconic:
#   1. Every keyword and operator is defined as a first-class declarative document
#      in the Lexicon (<TRACK 2>/lexicon/).
#   2. The Lexicon engine dynamically ingests these definitions, maps their
#      parts of speech, polarities (+ vs -), boundary ranks, and machine effects.
#   3. The OmniAssembler lowers them into concrete 64-bit balanced-ternary machine
#      words (Word64) and verifies delimiter stack integrity via OmniDebugger.
#   4. An AI running in a local instance can formulate emergent, domain-specific
#      keywords to build a bare-metal OS without hacking the compiler binary.
#
# THE GOLDEN CANONS OF OMNICODE LANGUAGE DESIGN:
#   CANON 1: MORPHEMIC COMPOUNDING
#     If an action can be expressed through natural compounding of base symbols
#     (~ like, ! but, :: and, @ at), it must be an operator (e.g. ::@, ~!).
#
#   CANON 2: UNIVERSAL HUMAN VERBS (ACCESSIBILITY FOR NON-CODERS)
#     If an action requires a verb, choose an everyday human word usable across
#     all domains (OS, Games, UI, AI). Never use developer jargon (spawn, probe, fork).
#     - Use SENSE instead of Probe (every living creature senses its world).
#     - Use AWAKEN instead of Spawn (transitioning from dormancy to active life).
#     - Use PREEMPT instead of Yield/Trap (taking turns with priority).
#     - Use PROVE instead of BIST/Assert (verifying balance before proceeding).
#
#   CANON 3: BOUNDARY TIER DISAMBIGUATION (THE COMPARISON RULE)
#     Because < ... > is the Rank 1 Invariant delimiter, bare `<` and `>` are
#     boundary brackets. All relational comparisons must be cast in context:
#     [ { A } < { B } ]
#     - [ ... ] denotes a concrete evaluation block.
#     - { ... } casts A and B into Context values.
#     - Uncasted `<=>` represents an Invariant of Equivalence (< => >).
# ================================================================================

Module < Lexicon.Suggestions.Manifest > ( Project-wide lexicon emergence charter ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon.Incubator >,
    semantics: < MorphemicOperators :: UniversalVerbs :: NonCoderAccessibility >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Incubation Categories, Boundary Ranking Hierarchy & Typology )
# ================================================================================
Opening {
    requires: [
        Rank1_Invariants : "< ... > (Absolute Immutable Laws & Types)" ::
        Rank2_Denotations : "[ ... ] (Concrete Silicon Evaluation Blocks)" ::
        Rank3_Contexts   : "{ ... } (Environmental Attributes & State Values)" ::
        Rank4_Asides     : "( ... ) (Teleological Intent & Secondary Checks)"
    ],
    preconditions: [ +1 : PROCEED ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Incubation Registry & Proposal Manifests )
# ================================================================================
Body [
    # Proposal 1: Morphological Symbolic Operators (operators/morphological_operators.omni)
    proposal_operators [
        SituatedAt_Binding  [ "::@" [ ChannelBind & AddressOffset ] ] ::
        CaveatInterrupt_Hop [ "~!"  [ ApproximateLike & InvariantCaveat ] ] ::
        ContextComparison   [ "[ { A } < { B } ]" [ CastedContextRelation ] ] ::
```

```
        InvariantBalance    [ "<=>" [ InvariantEquivalenceState ] ]
    ] ( Symbolic operator proposals compounding from atomic morphemes )

    # Proposal 2: Universal Human Verbs (03_verbs/universal_verbs.omni)
    proposal_verbs [
        Verb_Preempt [ "PREEMPT" [ PriorityInterruption & TaskTurnTaking ] ] ::
        Verb_Sense   [ "SENSE"   [ EnvironmentalDiscovery & HardwarePerception ] ] ::
        Verb_Awaken  [ "AWAKEN"  [ ColdStartInception & ProcessActivation ] ] ::
        Verb_Prove   [ "PROVE"   [ BalancedTernarySelfTest & InvariantValidation ] ]
    ] ( Universal human verbs replacing developer jargon )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Tripartite Consensus & Covenant Sealing )
# ================================================================================
Closing {
    verify: [
        proposal_operators = yes ::
        proposal_verbs = yes
    ],
    commit_status [ PROCEED ] ( Suggestion incubator sealed and active )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/alternative_branches.omni

OMNI | 62 LINES | 217 WORDS | 2.3 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Conjunctions: Alternative Disjunctions & Multi-Path Valves )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines disjunctive valves, alternative pathways, and branching:
#   - | : Alternative branch conjunction (disjunctive valve, fallback path).
# ================================================================================

Module < Lexicon.Conjunctions.AlternativeBranches >
    ( Disjunctive alternative branches and valves )
{
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < AlternativeBranches :: DisjunctiveValves ::
                 MultiPathBifurcations >
}

# 1. Disjunctive Alternative Conjunction: < OR >
Or < InvariantConjunction > ( Disjunctive Alternative Branch & Valve: | ) {
    grammar_primary: < "Conjunction" >,
    grammar_secondary: < "Preposition" >,
    symbol: < "|" >,
    abstract_form: < "+Or" >,
    concrete_form: < "Or-" >,
    machine_effect: < "alternative_disjunction_branch" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Or : InvariantConjunction
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify disjunctive alternative branching
    alternative_verification [
        Equilibrium_Branch [ Condition_Zero --> PROCEED |
                             Condition_Trap --> ROLLBACK ] ::
        Fallback_Branch    [ Target_Busy --> AWAIT |
                             Target_Ready --> PROCEED ]
    ] ( Disjunctive alternative branching verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        alternative_verification = yes
    ],
    commit_status [ PROCEED- ]
        ( Alternative branch conjunctions verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/alternative_branches.tape

TAPE | 35 LINES | 182 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: ALTERNATIVE BRANCHES PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes disjunctive alternative branches and multi-path valves (|).
# ================================================================================

[Tape.AlternativeBranches] : WHO {OmniCode_Kernel} WHAT {AlternativeBranches}
    --> BRANCH {DisjunctionMesh}
    WHEN {GenesisBoot}
    WHERE {branch_partition} = [ 64 ]
    WHY ( Test disjunctive alternative branches and multi-path valves )
    HOW [ +1 : PROCEED ]
    :: < branch_landmark >
    ( Joshua 24:15 - 'Choose you this day whom ye will serve' )

# ================================================================================
# SUBORDINATE ROLLS: DISJUNCTIVE BRANCHING ROLLS
# ================================================================================

# Roll 1: Reference abstract Or alternative conjunction specification
roll_1 [ +Or ] ( Abstract alternative disjunction blueprint referenced )

# Roll 2: Execute alternative branch state write
roll_2 [ 10 --> State_Primary @ 0 | 20 --> State_Alternate @ 1 ]
    ( Alternative branch path selection )

# Roll 3: Verify alternative branch selection
roll_3 [ State_Primary = 10 | State_Alternate = 20 ! [ +1 ] ]
    ( Verify alternative branch condition )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ]
    ( Alternative branches verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/caveat_branches.omni

OMNI | 56 LINES | 222 WORDS | 2.2 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Conjunctions: Adversative Caveats & Ratchet Catches )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines adversarial tripwires, ratchet catches, and invariant caveats:
#   - ! : Caveat branch conjunction (adversative condition, safety check, rewind trigger).
# ================================================================================

Module < Lexicon.Conjunctions.CaveatBranches > ( Adversative tripwires and ratchet tooth catches ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < CaveatBranches :: AdversativeTripwires :: RatchetCatches >
}

# 1. Adversative Caveat Conjunction: < BUT >
But < InvariantConjunction > ( Adversative Caveat & Ratchet Tooth Catch: ! ) {
    grammar_primary: < "Conjunction" >,
    grammar_secondary: < "Preposition" >,
    symbol: < "!" >,
    abstract_form: < "+But" >,
    concrete_form: < "But-" >,
    machine_effect: < "adversative_tripwire_ratchet" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        But : InvariantConjunction
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify adversative caveat tripwire
    caveat_verification [
        Invariant_Check [ Operation_Execute ! [ Guard_Condition = +1 ] ] ::
        Rollback_Catch  [ Mutate_State ! [ Invariant_Violated --> ROLLBACK ] ]
    ] ( Adversative caveat tripwires verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        caveat_verification = yes
    ],
    commit_status [ PROCEED- ] ( Caveat branch conjunctions verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/caveat_branches.tape

TAPE | 30 LINES | 188 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: CAVEAT BRANCHES PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes adversative invariant checks and caveat tripwires (!).
# ================================================================================

[Tape.CaveatBranches] : WHO {OmniCode_Kernel} WHAT {CaveatBranches} --> TRIPWIRE {SafetyMesh}
    WHEN {GenesisBoot}
    WHERE {caveat_partition} = [ 64 ]
    WHY ( Test adversative caveat branches and ratchet tooth catches )
    HOW [ +1 : PROCEED ]
    :: < caveat_landmark > ( Proverbs 22:3 - 'A prudent man forseeth the evil, and hideth himself' )

# ================================================================================
# SUBORDINATE ROLLS: EXCEPTION VETO & TRANSACTION REWIND ROLLS
# ================================================================================

# Roll 1: Reference abstract But caveat conjunction specification
roll_1 [ +But ] ( Abstract caveat branch blueprint referenced )

# Roll 2: Inscribe critical value under caveat condition
roll_2 [ 42 --> Secure_Cell_0 @ 0 ! [ +1 ] ] ( Write guarded by caveat affirmation )

# Roll 3: Guard state assertion against catastrophic violation
roll_3 [ Secure_Cell_0 = 42 ! [ +1 ] ] ( Assert value with affirmative caveat guard )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Caveat branch conjunctions verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/inseparable_pairs.omni

OMNI | 56 LINES | 218 WORDS | 2.1 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Conjunctions: Inseparable Dual Pairs & Clutches )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines locked differentials, atomic twins, and inseparable couplings:
#   - & : Inseparable pair conjunction (dual pin lock, twin rail binding).
# ================================================================================

Module < Lexicon.Conjunctions.InseparablePairs > ( Inseparable dual pairs and locked differentials ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < InseparablePairs :: LockedDifferentials :: DualPinBindings >
}

# 1. Inseparable Pair Conjunction: < PAIR >
Pair < InvariantConjunction > ( Inseparable Dual Pin Binding: & ) {
    grammar_primary: < "Conjunction" >,
    grammar_secondary: < "Preposition" >,
    symbol: < "&" >,
    abstract_form: < "+Pair" >,
    concrete_form: < "Pair-" >,
    machine_effect: < "locked_differential_dual_binding" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Pair : InvariantConjunction
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify inseparable dual binding
    pairs_verification [
        Dual_Rail_Binding [ Jack & Jill --> Hill ] ::
        Atomic_Twin_Lock  [ Signal_A & Signal_B --> Dual_Port ]
    ] ( Inseparable pairs and locked differentials verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        pairs_verification = yes
    ],
    commit_status [ PROCEED- ] ( Inseparable pair conjunctions verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/inseparable_pairs.tape

TAPE | 30 LINES | 178 WORDS | 1.4 KB

```
# ================================================================================
# TAPE HEAD: INSEPARABLE PAIRS PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes atomic dual-rail writes and locked differential pairs (&).
# ================================================================================

[Tape.InseparablePairs] : WHO {OmniCode_Kernel} WHAT {InseparablePairs} --> LOCK {DifferentialMesh}
    WHEN {GenesisBoot}
    WHERE {pair_partition} = [ 64 ]
    WHY ( Test locked differential twin bindings and atomic dual writes )
    HOW [ +1 : PROCEED ]
    :: < pair_landmark > ( Ecclesiastes 4:9 - 'Two are better than one' )

# ================================================================================
# SUBORDINATE ROLLS: ATOMIC DUAL-RAIL WRITE ROLLS
# ================================================================================

# Roll 1: Reference abstract Pair conjunction specification
roll_1 [ +Pair ] ( Abstract dual pair blueprint referenced )

# Roll 2: Inscribe locked differential twin values
roll_2 [ 50 & 50 --> Twin_Port_0 @ 0 ] ( Atomic dual-rail write into Twin_Port_0 )

# Roll 3: Verify dual-rail equality invariant
roll_3 [ Twin_Port_0 = 50 ! [ +1 ] ] ( Verify twin values bound to port )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Inseparable pair conjunctions verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/pipeline_junctions.omni

OMNI | 56 LINES | 209 WORDS | 2.1 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Conjunctions: Sequential Pipeline Junctions & Chaining )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines geartrain sequencing and pipelined consensus chaining:
#   - :: : Pipeline junction conjunction (sequential geartrain, step separator).
# ================================================================================

Module < Lexicon.Conjunctions.PipelineJunctions > ( Pipelined geartrain sequencing and chaining ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < PipelineJunctions :: GeartrainSequencing :: ConsensusChaining >
}

# 1. Pipeline Junction Conjunction: < CHAIN >
Chain < InvariantConjunction > ( Sequential Geartrain Chaining: :: ) {
    grammar_primary: < "Conjunction" >,
    grammar_secondary: < "Preposition" >,
    symbol: < "::" >,
    abstract_form: < "+Chain" >,
    concrete_form: < "Chain-" >,
    machine_effect: < "sequential_pipeline_junction" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Chain : InvariantConjunction
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify sequential geartrain chaining
    pipeline_verification [
        Pipelined_Sequence [ Step_A :: Step_B :: Step_C ] ::
        Chain_Validation   [ Transform_1 :: Transform_2 ]
    ] ( Sequential geartrain chaining verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        pipeline_verification = yes
    ],
    commit_status [ PROCEED- ] ( Pipeline junction conjunctions verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/pipeline_junctions.tape

TAPE | 30 LINES | 182 WORDS | 1.4 KB

```
# ================================================================================
# TAPE HEAD: PIPELINE JUNCTIONS PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes sequential geartrain pipeline chaining (::).
# ================================================================================

[Tape.PipelineJunctions] : WHO {OmniCode_Kernel} WHAT {PipelineJunctions} --> CHAIN {SequencerMesh}
    WHEN {GenesisBoot}
    WHERE {pipeline_partition} = [ 64 ]
    WHY ( Test sequential geartrain steps and pipeline chaining )
    HOW [ +1 : PROCEED ]
    :: < pipeline_landmark > ( 1 Corinthians 14:40 - 'Let all things be done decently and in order' )

# ================================================================================
# SUBORDINATE ROLLS: PIPELINE CHAINING ROLLS
# ================================================================================

# Roll 1: Reference abstract Chain conjunction specification
roll_1 [ +Chain ] ( Abstract pipeline chain blueprint referenced )

# Roll 2: Execute chained sequential stage writes
roll_2 [ 10 --> Stage_A @ 0 :: 20 --> Stage_B @ 1 ] ( Chained writes in single roll )

# Roll 3: Verify chained stage invariants
roll_3 [ Stage_A = 10 :: Stage_B = 20 ! [ +1 ] ] ( Verify chained invariant assertions )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Pipeline junctions verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/relational_attributions.omni

OMNI | 62 LINES | 223 WORDS | 2.3 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Conjunctions: Relational Attributions & Analogy Ratios )
# ========================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines relational attribution, role binding, and analogy ratios:
#   - : : Relational attribution conjunction (in relation to, to be as).
# ========================================================================

Module < Lexicon.Conjunctions.RelationalAttributions >
    ( Relational attributions and proportional analogy ratios )
{
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < RelationalAttributions :: ProportionalAnalogies ::
                 RoleBindings >
}

# 1. Relational Attribution Conjunction: < IN_RELATION_TO >
InRelationTo < InvariantConjunction >
    ( Relational Attribution & Analogy Ratio: : )
{
    grammar_primary: < "Conjunction" >,
    grammar_secondary: < "Preposition" >,
    symbol: < ":" >,
    abstract_form: < "+InRelationTo" >,
    concrete_form: < "InRelationTo-" >,
    machine_effect: < "relational_proportional_binding" >
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ========================================================================
Opening {
    requires: [
        InRelationTo : InvariantConjunction
    ],
    preconditions: [ +1 ]
}

# ========================================================================
# BLOCK 3: BODY BLOCK
# ========================================================================
Body [
    # Verify relational attribution and proportional analogy
    attribution_verification [
        Analogy_Ratio   [ Number : Measure :: Trit : Magnitude ] ::
        Context_Binding [ State_Target : Chassis_Scale @ 0 ]
    ] ( Relational attribution and analogy ratio verified )
]

# ========================================================================
# BLOCK 4: CLOSING BLOCK
# ========================================================================
Closing {
    verify: [
        attribution_verification = yes
    ],
    commit_status [ PROCEED- ]
        ( Relational attribution conjunctions verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/07_conjunctions/relational_attributions.tape

TAPE | 34 LINES | 169 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: RELATIONAL ATTRIBUTIONS PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes relational attributions and proportional analogy ratios (:).
# ================================================================================

[Tape.RelationalAttributions] : WHO {OmniCode_Kernel}
    WHAT {RelationalAttributions} --> BIND {AnalogyMesh}
    WHEN {GenesisBoot}
    WHERE {attribution_partition} = [ 64 ]
    WHY ( Test relational attributions and proportional analogy bindings )
    HOW [ +1 : PROCEED ]
    :: < attribution_landmark >
    ( Romans 12:5 - 'Every one members one of another' )

# ================================================================================
# SUBORDINATE ROLLS: RELATIONAL ATTRIBUTION ROLLS
# ================================================================================

# Roll 1: Reference abstract InRelationTo conjunction specification
roll_1 [ +InRelationTo ]
    ( Abstract relational attribution blueprint referenced )

# Roll 2: Execute relational scale attribution
roll_2 [ 50 --> Metric_Scale @ 0 : [ 64 ] ] ( Attributed scale binding )

# Roll 3: Verify attributed binding
roll_3 [ Metric_Scale = 50 ! [ +1 ] ] ( Verify attributed binding )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ]
    ( Relational attributions verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/05_adverbs/cadence_policies.omni

OMNI | 81 LINES | 333 WORDS | 3.0 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Adverbs: Escapement Regulation & Cadence Policies )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines scheduler cadence, governor flywheel, and timing policies:
#   - atomic    : Uninterruptible execution stroke, single-cycle indivisibility.
#   - yield     : Cooperative dispatch pause, escapement release to scheduler.
#   - monotonic : Unidirectional clock advance, irreversible sequential progress.
# ================================================================================

Module < Lexicon.Adverbs.CadencePolicies > ( Escapement regulation and scheduler cadence policies ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < CadencePolicies :: EscapementGovernor :: SchedulerRegulation >
}

# 1. Atomic Policy: < ATOMIC >
Atomic < InvariantAdverb > ( Indivisible Execution Stroke: atomic ) {
    grammar_primary: < "Adverb" >,
    grammar_secondary: < "Adjective" >,
    symbol: < "atomic" >,
    abstract_form: < "+Atomic" >,
    concrete_form: < "Atomic-" >,
    machine_effect: < "indivisible_cycle_lock" >
}

# 2. Yield Policy: < YIELD >
Yield < InvariantAdverb > ( Cooperative Escapement Release: yield ) {
    grammar_primary: < "Adverb" >,
    grammar_secondary: < "Verb" >,
    symbol: < "yield" >,
    abstract_form: < "+Yield" >,
    concrete_form: < "Yield-" >,
    machine_effect: < "escapement_release_cooperate" >
}

# 3. Monotonic Policy: < MONOTONIC >
Monotonic < InvariantAdverb > ( Irreversible Unidirectional Advance: monotonic ) {
    grammar_primary: < "Adverb" >,
    grammar_secondary: < "Adjective" >,
    symbol: < "monotonic" >,
    abstract_form: < "+Monotonic" >,
    concrete_form: < "Monotonic-" >,
    machine_effect: < "monotonic_clock_advance" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Atomic : InvariantAdverb ::
        Yield : InvariantAdverb ::
        Monotonic : InvariantAdverb
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify cadence regulation policies
    cadence_verification [
        Atomic_Lock    [ atomic [ Write_Buffer_0 --> Flash_ROM ] ] ::
        Yield_Check    [ yield [ Task_Slice_0 ] ] ::
        Monotonic_Tick [ monotonic [ Clock_Tick_0 ] ]
    ] ( Scheduler cadence policies verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
```

```
# ================================================================================
Closing {
    verify: [
        cadence_verification = yes
    ],
    commit_status [ PROCEED- ] ( Cadence policy adverbs verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/05_adverbs/cadence_policies.tape

TAPE | 30 LINES | 183 WORDS | 1.4 KB

```
# ================================================================================
# TAPE HEAD: CADENCE POLICIES PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes scheduler cadence policies (atomic, yield, monotonic).
# ================================================================================

[Tape.CadencePolicies] : WHO {OmniCode_Kernel} WHAT {CadencePolicies} --> REGULATE {SchedulerMesh}
    WHEN {GenesisBoot}
    WHERE {cadence_partition} = [ 64 ]
    WHY ( Test escapement regulation, atomic locks, and yield cycles )
    HOW [ +1 : PROCEED ]
    :: < cadence_landmark > ( Psalm 90:12 - 'So teach us to number our days' )

# ================================================================================
# SUBORDINATE ROLLS: CADENCE POLICY DISPATCH ROLLS
# ================================================================================

# Roll 1: Reference abstract Atomic, Yield, and Monotonic specifications
roll_1 [ +Atomic & +Yield & +Monotonic ] ( Abstract cadence blueprints referenced )

# Roll 2: Execute atomic lock roll
roll_2 [ atomic [ 99 --> Locked_Cell_0 @ 0 ] ] ( Inscribe value under atomic lock )

# Roll 3: Execute cooperative yield roll
roll_3 [ yield [ Locked_Cell_0 = 99 ! [ +1 ] ] ] ( Yield cycle with invariant check )

# Roll 4: Commit with affirmative concrete macro
roll_4 [ commit_status [ PROCEED- ] ] ( Cadence policies verified and sealed )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/05_adverbs/negation.omni

OMNI | 57 LINES | 221 WORDS | 2.1 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ontological Adverbs: Logical & Algebraic Negation )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines inversion symmetry and reversing idler gears:
#   - -- : Negation operator (logical NOT, balanced ternary negation: -1 <-> +1).
# ================================================================================

Module < Lexicon.Adverbs.Negation > ( Reversing idler gears and inversion symmetry ) {
    version: < "1.0.0" >,
    system: < OmniCode.Lexicon >,
    semantics: < Negation :: InversionSymmetry :: ReversingIdlerGear >
}

# 1. Negation Operator: < NEGATION >
Negation < InvariantAdverb > ( Logical & Algebraic Inversion: -- ) {
    grammar_primary: < "Adverb" >,
    grammar_secondary: < "Preposition" >,
    symbol: < "--" >,
    abstract_form: < "+Negation" >,
    concrete_form: < "Negation-" >,
    machine_effect: < "inversion_idler_gear" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [
        Negation : InvariantAdverb
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Verify balanced ternary negation symmetry
    negation_verification [
        Invert_Positive [ -- (+1) = -1 ] ::
        Invert_Negative [ -- (-1) = +1 ] ::
        Invert_Zero     [ -- (0)  =  0 ]
    ] ( Balanced ternary negation symmetry verified )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        negation_verification = yes
    ],
    commit_status [ PROCEED- ] ( Negation adverbs verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lexicon/05_adverbs/negation.tape

TAPE | 33 LINES | 193 WORDS | 1.5 KB

```
# ================================================================================
# TAPE HEAD: NEGATION PROCESS RIBBON
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes algebraic and logical inversion symmetry (--).
# ================================================================================

[Tape.Negation] : WHO {OmniCode_Kernel} WHAT {Negation} --> INVERT {SymmetryMesh}
    WHEN {GenesisBoot}
    WHERE {negation_partition} = [ 64 ]
    WHY ( Test balanced ternary negation and idler gear inversion )
    HOW [ +1 : PROCEED ]
    :: < negation_landmark > ( Ecclesiastes 3:1 - 'To every thing there is a season' )

# ================================================================================
# SUBORDINATE ROLLS: INVERSION SYMMETRY ROLLS
# ================================================================================

# Roll 1: Reference abstract Negation specification
roll_1 [ +Negation ] ( Abstract negation blueprint referenced )

# Roll 2: Set input register to affirmative +1
roll_2 [ 1 --> Reg_Input_0 @ 0 ] ( Inscribe positive polarity into input register )

# Roll 3: Invert polarity via --
roll_3 [ -- Reg_Input_0 --> Reg_Inverted_0 @ 1 ] ( Apply reversing idler gear inversion )

# Roll 4: Verify symmetric equilibrium
roll_4 [ Reg_Inverted_0 = -1 ! [ +1 ] ] ( Verify balanced ternary inversion symmetry )

# Roll 5: Commit with affirmative concrete macro
roll_5 [ commit_status [ PROCEED- ] ] ( Negation adverbs verified and sealed )
```

OmniCode: Chapter 17: Track 2 - Standard Library Modules

Core Logic, Vectors, Arithmetic & Memory Management

CHAPTER IDENTIFIER
CH 17

NOTEBOOKLM WORD COUNT
3,672 words

CATALOGED CHAPTER FILES
8 files (674 lines)

GENERATION DATE
2026-10-16 20:36:09

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"How do standard library modules export pure invariants?"*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (8 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 2> : {OmniCode Language & Standard Library}/lib/kernel/boot.omni**	OMNI	114	679	4.9
2	**<TRACK 2> : {OmniCode Language & Standard Library}/lib/kernel/boot.tape**	TAPE	50	487	3.4
3	**<TRACK 2> : {OmniCode Language & Standard Library}/lib/core/arithmetic.omni**	OMNI	90	416	2.8
4	**<TRACK 2> : {OmniCode Language & Standard Library}/lib/core/cell.tape**	TAPE	17	133	0.9
5	**<TRACK 2> : {OmniCode Language & Standard Library}/lib/core/logic.omni**	OMNI	89	404	2.9
6	**<TRACK 2> : {OmniCode Language & Standard Library}/lib/core/memory.omni**	OMNI	135	703	5.2
7	**<TRACK 2> : {OmniCode Language & Standard Library}/lib/core/memory.tape**	TAPE	28	174	1.2
8	**<TRACK 2> : {OmniCode Language & Standard Library}/lib/core/vectors.omni**	OMNI	151	676	5.1

<TRACK 2> : {OmniCode Language & Standard Library}/lib/kernel/boot.omni OMNI 114 LINES 679 WORDS 4.9 KB

```
# ============================================================================
# BLOCK 1: METADATA BLOCK
# ( Kernel Architecture: Genesis Bare-Metal OS Specification )
# ============================================================================
# ARCHITECTURAL TOPOLOGY:
#   Defines the bare-metal machine initialization contract:
#   - Establishes the 64-bit silicon envelope hosting the 32-trit kernel word.
#   - Mounts the 4096-cell Root_RAM storehouse on Track 0 [KERNEL].
#   - Writes the boot banner to the memory-mapped VGA text buffer at 0x000B8000.
#   - Initializes the 4-directional Memory Reel spindle hierarchy.
# ============================================================================

Module < Kernel.GenesisBoot > ( MilleniumOS Genesis bare-metal kernel initialization ) {
    version: < "1.0.0" >,
    system: < MilleniumOS.Kernel >,
    semantics: < BareMetalBootstrap :: BalancedTernaryALU :: MMIOConsole >
}

# 1. Kernel Entity: < KERNEL >
Kernel < InvariantNoun > ( Master Operating System Supervisor ) {
    grammar_primary: < "Noun" >,
    abstract_form: < "+Kernel" >,
    concrete_form: < "Kernel-" >,
    authority_channel: < "Track 0 [KERNEL]" >,
    machine_effect: < "hardware_root_supervisor" >
}

# 2. Storehouse Entity: < ROOT_RAM >
RootRAM < InvariantNoun > ( Physical Silicon Memory Storehouse ) {
    grammar_primary: < "Noun" >,
    abstract_form: < "+RootRAM" >,
    concrete_form: < "RootRAM-" >,
    capacity_cells: < 4096 >,
    machine_effect: < "physical_ram_allocator" >
}

# 3. Video Console Entity: < VGA_SCREEN >
ScreenVGA < InvariantNoun > ( Bare-Metal Video Text Buffer at 0x000B8000 ) {
    grammar_primary: < "Noun" >,
    abstract_form: < "+ScreenVGA" >,
    concrete_form: < "ScreenVGA-" >,
    mmio_base: < 0x000B8000 >,
    geometry: < "80x25 characters" >,
    machine_effect: < "vga_text_buffer" >
}

# 4. Serial Transducer Entity: < SERIAL_COM1 >
SerialCOM1 < InvariantNoun > ( UART Serial Hardware Port at 0x03F8 ) {
    grammar_primary: < "Noun" >,
    abstract_form: < "+SerialCOM1" >,
    concrete_form: < "SerialCOM1-" >,
    io_port: < 0x03F8 >,
    baud_rate: < 115200 >,
    machine_effect: < "hardware_input_transducer" >
}

# 5. Silicon Register Bank Entity: < REGISTERS >
RegisterBank < InvariantNoun > ( 13 Named Silicon Registers and Transducers ) {
    grammar_primary: < "Noun" >,
    abstract_form: < "+RegisterBank" >,
    concrete_form: < "RegisterBank-" >,
    capacity_slots: < 13 >,
    registers: < [ HEAD HOME SPOOL IT SELF CALLER OTHER STATE TURN BOUND FROM INTO DISCARD ] >,
    machine_effect: < "silicon_register_allocation" >
}

# ============================================================================
# BLOCK 2: OPENING BLOCK
# ============================================================================
Opening {
    requires: [
        Kernel : InvariantNoun ::
        RootRAM : InvariantNoun ::
        ScreenVGA : InvariantNoun ::
```

```
        SerialCOM1 : InvariantNoun ::
        RegisterBank : InvariantNoun
    ],
    preconditions: [ +1 ]
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # Roll 1: Allocate root RAM storehouse and arm 13 Named Silicon Registers
    ram_and_regs [ Root_RAM [ 4096 ] :: Register_Bank [ HEAD HOME SPOOL IT SELF CALLER OTHER STATE TURN BOUND FROM INTO
DISCARD ] :: FROM ::@ 0x03F8 :: INTO ::@ 0x000B8000 ] ( Root memory storehouse and 13 named silicon registers armed )

    # Roll 2: Prove ALU equilibrium invariant and calibrate Quad-State accumulator loop
    alu_and_loop [ ALU_Equilibrium [ (+1) plus (-1) <=> 0 ] :: Accumulator_Loop [ WHEN [ { IT } < { BOUND } ] --> [ IT` ]
PROCEED to { TURN } ! [ { IT } > { BOUND } ] AWAIT for [ IT` ] :: HALT WHEN [ IT` ] != even ] ] ( Invariant arithmetic
equilibrium and quad-state loop calibration )

    # Roll 3: Carve protected Kernel and Terminal partitions via v-- and evaluate contextual bounds
    partition_carve [ Root_RAM v-- Kernel_Partition [ 1024 ] :: Root_RAM v-- Terminal_Partition [ 512 ] :: Bounds_Check [
{ 1024 } < { 4096 } ] ] ( Partition storehouses via v-- and bounds evaluation )

    # Roll 4: Inscribe initial landmark and boot banner to MMIO VGA video buffer
    landmark_and_banner [ 0 --> Kernel_Partition @ 0 :: 'MILLENIUMOS: OMNICODE 32-TRIT OS ONLINE' --> Screen_VGA ::@
0x000B8000 ] ( Landmark and screen banner )

    # Roll 5: Commit genesis boot
    commit_genesis [ commit_status [ PROCEED ] ] ( Genesis Boot sealed in PROCEED )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        ram_and_regs = yes ::
        alu_and_loop = yes ::
        partition_carve = yes ::
        landmark_and_banner = yes ::
        commit_genesis = yes
    ],
    commit_status [ PROCEED ] ( Genesis Boot verified and sealed in PROCEED )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lib/kernel/boot.tape TAPE 50 LINES 487 WORDS 3.4 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Tape Manifest, Kernel Scheduling & Genesis Machine Covenant )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Executes cold boot sequence on Track 0 [KERNEL]:
#   - Senses physical Root_RAM storehouse and binds serial COM1 situated at 0x03F8 via ::@.
#   - Proves balanced ternary ALU equilibrium before allocating mutable memory partitions.
#   - Carves Kernel_Partition (1024 cells) and Terminal_Partition (512 cells) via v--, verifying [ { 1024 } < { 4096 } ].
#   - Establishes preemptive turn-taking (~! & PREEMPT) and awakens VGA console at 0x000B8000.
#   - Seals genesis boot in affirmative PROCEED.
# ================================================================================

[Tape.GenesisBoot] : WHO {MilleniumOS_Kernel} WHAT {SystemGenesis} --> BOOT {Hardware}
    WHEN {PowerOn}
    WHERE {ram} = [ 4096 ]
    WHY ( Initialize balanced ternary MilleniumOS kernel and diagnostic nervous system )
    HOW [ +1 : PROCEED ]
    :: < ancient_landmark > ( Proverbs 22:28 - 'Remove not the ancient landmark' )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Environmental Preconditions, Memory Partition Geometry & Storehouse Bounds )
# ================================================================================

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Sequential Instruction Rolls Lowered to Silicon Machine Words )
# ================================================================================

# Roll 1: Sense physical memory and arm 13 Named Silicon Registers with hardware transducers
roll_1 [ Kernel --> SENSE {Root_RAM [ 4096 ]} :: ARM {Registers [ HEAD HOME SPOOL IT SELF CALLER OTHER STATE TURN BOUND FROM INTO DISCARD ]} :: FROM ::@ 0x03F8 :: INTO ::@ 0x000B8000 ] ( Sense physical memory and arm 13 named silicon registers with hardware transducers )

# Roll 2: Prove ALU equilibrium invariant and calibrate Quad-State accumulator loop
roll_2 [ Kernel --> PROVE {ALU_Equilibrium} [ (+1) plus (-1) <=> 0 ] :: LOOP [ WHEN [ { IT } < { BOUND } ] --> [ IT` ] PROCEED to { TURN } ! [ { IT } > { BOUND } ] AWAIT for [ IT` ] :: HALT WHEN [ IT` ] != even ] ] ( Invariant proof of balanced ternary arithmetic and quad-state accumulator calibration )

# Roll 3: Carve protected kernel and terminal partitions via v-- and evaluate contextual bounds
roll_3 [ Root_RAM v-- Kernel_Partition [ 1024 ] :: Root_RAM v-- Terminal_Partition [ 512 ] :: Bounds_Check [ { 1024 } < { 4096 } ] ] ( Partition storehouse via v-- and evaluate bounds in context )

# Roll 4: Yield compute on timer tick and awaken console HUD with MMIO boot banner
roll_4 [ Kernel_Compute ~! [ Timer_Tick --> PREEMPT {Background_Task} ] :: 'MILLENIUMOS: OMNICODE 32-TRIT OS ONLINE' --> Screen_VGA ::@ 0x000B8000 :: Kernel --> AWAKEN {Terminal_Studio} ] ( Preempt compute on timer interrupt and awaken screen banner )

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Invariant Verification Proofs & Covenant Commit Seal )
# ================================================================================

# Roll 5: Genesis Boot Complete
roll_5 [ commit_status [ PROCEED ] ] ( MilleniumOS Genesis Boot Complete )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lib/core/arithmetic.omni OMNI 90 LINES 416 WORDS 2.8 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Core Library Manifest: Invariant Arithmetic Macros & Opcodes )
# ========================================================================
Module < Core.Arithmetic > ( Invariant arithmetic macros linked to CPU and LLVM opcodes ) {
    version: < "1.0.0" >,
    system: < OmniCode.Core >,
    semantics: < MacroInvariants :: HardwareOpcodes :: SVOTranspilation >
}

# Macro Invariant: < ADD >
ADD < InvariantMacro > ( Binary Addition ) {
    micro: < "plus" >,
    x86_64: < "add" >,
    riscv: < "add" >,
    llvm_ir: < "add i64" >,
    c_operator: < "+" >
}

# Macro Invariant: < SUB >
SUB < InvariantMacro > ( Binary Subtraction ) {
    micro: < "minus" >,
    x86_64: < "sub" >,
    riscv: < "sub" >,
    llvm_ir: < "sub i64" >,
    c_operator: < "-" >
}

# Macro Invariant: < MUL >
MUL < InvariantMacro > ( Binary Multiplication ) {
    micro: < "times" >,
    x86_64: < "imul" >,
    riscv: < "mul" >,
    llvm_ir: < "mul i64" >,
    c_operator: < "*" >
}

# Macro Invariant: < DIV >
DIV < InvariantMacro > ( Binary Division ) {
    micro: < "div" >,
    x86_64: < "idiv" >,
    riscv: < "div" >,
    llvm_ir: < "sdiv i64" >,
    c_operator: < "/" >
}

# ========================================================================
# BLOCK 2: OPENING BLOCK
# ( Preconditions & Macro Registry Setup )
# ========================================================================
Opening {
    requires: [ Hardware.ALU :: IntegerRegisters.64 ],
    preconditions: [ +1 ]
}

test_x [ 40 ] ( Sample operand X )
test_y [ 2 ]  ( Sample operand Y )

# ========================================================================
# BLOCK 3: BODY BLOCK
# ( SVO Descriptions Lowered to Invariant Macro Opcodes )
# ========================================================================
Body [
    # 1. Addition: Micro 'plus' lowers to Macro < ADD >
    sum_result [ test_x plus test_y ] ( 40 plus 2 = 42 )

    # 2. Subtraction: Micro 'minus' lowers to Macro < SUB >
    diff_result [ sum_result minus test_y ] ( 42 minus 2 = 40 )

    # 3. Multiplication: Micro 'times' lowers to Macro < MUL >
    prod_result [ test_y times 10 ] ( 2 times 10 = 20 )

    # 4. Division: Micro 'div' lowers to Macro < DIV >
    quot_result [ prod_result div 2 ] ( 20 div 2 = 10 )
```

```
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Verification & Macro Status Commit )
# ================================================================================
Closing {
    verify: [
        sum_result = 42 ::
        diff_result = 40 ::
        prod_result = 20 ::
        quot_result = 10
    ],
    commit_status [ PROCEED ] ( Arithmetic library verified and sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lib/core/cell.tape TAPE 17 LINES 133 WORDS 0.9 KB

```
# ============================================================================
# TAPE HEAD: THE CELL DEFINITION COVENANT
# ============================================================================
[Cell] : A unit of measure --> WHERE {unit} = [ 8 bit --> 5 trit --> 8 bit ] :: < measure > ( Fundamental unit of memory
)

# ============================================================================
# SUBORDINATE ROLLS: CELL DENSE ENCODING & REVERSIBLE TRANSDUCTION
# ============================================================================
# Roll 1: Transduce byte 42 into 5 trits and store in cell 0
roll_1 [ 42 --> Cell_0 @ 0 ] ( Inscribe radix-3 packed value into cell 0 )

# Roll 2: Verify cell 0 holds 42 within invariant bounds
roll_2 [ Cell_0 = 42 ! [ +1 ] ] ( Verify dense byte recovery )

# Roll 3: Transduce and seal with affirmative commit
roll_3 [ commit_status [ PROCEED ] ] ( Cell covenant proven )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lib/core/logic.omni OMNI 89 LINES 404 WORDS 2.9 KB

```
# ============================================================================
# BLOCK 1: METADATA BLOCK
# ( Core Library Manifest: Invariant Quad-State Macros & OS Control Opcodes )
# ============================================================================
Module < Core.Logic > ( Invariant logic macros linked to CPU execution and kernel control ) {
    version: < "1.0.0" >,
    system: < OmniCode.Core >,
    semantics: < MacroInvariants :: KernelPhysics :: QuadStateOpcodes >
}

# Macro Invariant: < PROCEED >
PROCEED_MACRO < InvariantMacro > ( Advance Execution & Commit State Frame ) {
    micro: < "yes" >,
    radix3: < 1 >,
    x86_64: < "jmp .Lnext" >,
    riscv: < "j .Lnext" >,
    c_status: < "0" >,
    os_action: < "commit_transaction_and_advance" >
}

# Macro Invariant: < ROLLBACK >
ROLLBACK_MACRO < InvariantMacro > ( Retroactive Unwind & Snapshot Restore ) {
    micro: < "no" >,
    radix3: < -1 >,
    x86_64: < "mov rsp, rbp; pop rbp; ret" >,
    riscv: < "mv sp, s0; ld s0, 0(sp); ret" >,
    c_status: < "-1" >,
    os_action: < "unwind_transaction_frame" >
}

# Macro Invariant: < AWAIT >
AWAIT_MACRO < InvariantMacro > ( CPU Idle / Asynchronous Interrupt Standby ) {
    micro: < "ok" >,
    radix3: < 0 >,
    x86_64: < "hlt" >,
    riscv: < "wfi" >,
    arm64: < "wfi" >,
    os_action: < "yield_cpu_to_scheduler" >
}

# Macro Invariant: < HALT >
HALT_MACRO < InvariantMacro > ( Unrecoverable Boundary Trap / Panic ) {
    micro: < "void" >,
    radix3: < NULL >,
    x86_64: < "ud2" >,
    riscv: < "ebreak" >,
    c_status: < "abort()" >,
    os_action: < "kernel_panic_trap" >
}

# ============================================================================
# BLOCK 2: OPENING BLOCK
# ( Kernel Preconditions & Invariant Verification )
# ============================================================================
Opening {
    requires: [ CPU.InterruptControl :: ProcessTable.Active ],
    preconditions: [ +1 ]
}

status_flag [ yes ] ( Active execution thread status )

# ============================================================================
# BLOCK 3: BODY BLOCK
# ( Logic Invariants Mapped to OS Physics )
# ============================================================================
Body [
    # 1. Monotonic Commit Test
    commit_test [ status_flag = PROCEED ] ( 'yes' triggers monotonic forward commit )

    # 2. Inversion Symmetry Test
    negate_test [ -- status_flag = ROLLBACK ] ( Inversion of 'yes' triggers ROLLBACK )

    # 3. Equilibrium Balance Test
    balance_test [ ok = AWAIT ] ( 'ok' maps to AWAIT / HLT / WFI )
```

```
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Verification & Status Commit )
# ================================================================================
Closing {
    verify: [
        commit_test = yes ::
        negate_test = yes ::
        balance_test = yes
    ],
    commit_status [ PROCEED ] ( Logic core sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lib/core/memory.omni OMNI | 135 LINES | 703 WORDS | 5.2 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Core Library Manifest: Foundational Storage Nouns & Memory Vessel Invariants )
# ========================================================================
Module < Core.Memory > ( Foundational storage nouns, bounded vessels, and hardware transducers ) {
    version: < "1.0.0" >,
    system: < OmniCode.Core >,
    semantics: < StorageNouns :: BoundedVessels :: TransducedCells :: BoundaryPhysics >
}

# 1. Atomic Data Unit: < TRIT >
TRIT_NOUN < InvariantNoun > ( The Atomic Radix-3 Polarity Unit ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Adjective" >,
    ontological_tier: < "Tier 1: Atomic Unit" >,
    permitted_states: < "Neg_T_Zero_0_Pos_1" >,
    machine_effect: < "radix3_polarity_register" >
}

# 2. Atomic Data Unit: < CELL >
CELL_NOUN < InvariantNoun > ( The Atomic 5-Trit / 8-Bit Quad-State Memory Vessel ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Preposition" >,
    ontological_tier: < "Tier 1: Atomic Unit" >,
    physical_footprint: < "1 physical byte in RAM (243 values + 13 control states)" >,
    machine_effect: < "dense_byte_trit_cell" >
}

# 3. Storage Container: < VESSEL >
VESSEL_NOUN < InvariantNoun > ( Bounded Sequential Container of Memory Cells ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Preposition" >,
    ontological_tier: < "Tier 2: Storage Container" >,
    invariant_law: < "Proverbs 22:28 (Remove not the ancient landmark)" >,
    machine_effect: < "contiguous_bounded_buffer" >
}

# 4. Storage Container: < STOREHOUSE >
STOREHOUSE_NOUN < InvariantNoun > ( Root System Memory Domain & Reservoir ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Preposition" >,
    ontological_tier: < "Tier 2: Storage Container" >,
    machine_effect: < "root_page_reservoir" >
}

# 5. Storage Container: < PARTITION >
PARTITION_NOUN < InvariantNoun > ( Entrusted Bounded Sub-Region of a Storehouse ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Preposition" >,
    ontological_tier: < "Tier 2: Storage Container" >,
    machine_effect: < "delegated_task_slice" >
}

# 6. Coordinate: < OFFSET >
OFFSET_NOUN < InvariantNoun > ( Relative Zero-Based Coordinate within a Vessel ) {
    grammar_primary: < "Preposition" >,
    grammar_secondary: < "Noun" >,
    ontological_tier: < "Tier 3: Spatial Coordinate" >,
    machine_effect: < "memory_address_displacement" >
}

# 7. Measure: < CAPACITY >
CAPACITY_NOUN < InvariantNoun > ( Maximum Allocated Cell Limit of a Vessel ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Adjective" >,
    ontological_tier: < "Tier 4: Measure" >,
    machine_effect: < "boundary_limit_ceiling" >
}

# 8. Measure: < COUNT >
COUNT_NOUN < InvariantNoun > ( Number of Actively Written or Populated Cells ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Adjective" >,
    ontological_tier: < "Tier 4: Measure" >,
```

```
    machine_effect: < "active_population_count" >
}

# 9. Substance: < VALUE >
VALUE_NOUN < InvariantNoun > ( The Numeric or Symbolic Payload Stored in a Cell ) {
    grammar_primary: < "Noun" >,
    grammar_secondary: < "Adjective" >,
    ontological_tier: < "Tier 5: Substance" >,
    machine_effect: < "cell_payload_register" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Preconditions & Vessel Context Setup )
# ================================================================================
Opening {
    requires: [ MemoryAligned :: QuadStateTransducer :: BoundaryPhysics ],
    preconditions: [ +1 ]
}

# Declare the system Storehouse
Main_Storehouse [ 1024 ] { Fixed, Bounded } ( System memory reservoir of 1024 cells )

# Grant an entrusted Partition carved directly from Main_Storehouse via v--
Main_Storehouse v-- Task_Partition [ 256 ] ( Entrusted process partition of 256 cells )

# Initial test data
sample_val [ 42 ] ( Natural number 42 to store )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Memory Operations: Forward Store, Feedback Read, and Bounds Verification )
# ================================================================================
Body [
    # 1. Forward Causality: Store natural value 42 into cell 0 of partition
    step_store [ sample_val --> Task_Partition[0] ] ( Deposit value into cell 0 )

    # 2. Feedback Retrieval: Reflect value back from cell 0
    step_fetch [ read_val <-- Task_Partition[0] ] ( Retrieve value from cell 0 )

    # 3. State Inscription: Mark cell 1 with affirmative PROCEED state
    step_state [ PROCEED --> Task_Partition[1] ] ( Inscribe PROCEED into cell 1 )

    # 4. Invariant Verification: Confirm within capacity
    step_bound [ Task_Partition[0] ! [ +1 ] ] ( Enforce capacity caveat )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Integrity Verification & Invariant Seal )
# ================================================================================
Closing {
    verify: [
        step_store = +1 ::
        step_fetch = +1 ::
        step_state = +1 ::
        step_bound = +1
    ],
    commit_status [ PROCEED ] ( Memory vessel core sealed )
}
```

<TRACK 2> : {OmniCode Language & Standard Library}/lib/core/memory.tape TAPE 28 LINES 174 WORDS 1.2 KB

```
# ================================================================================
# TAPE HEAD: MEMORY RESERVOIR & PARTITIONING COVENANT
# ================================================================================
[Tape.MemoryManager] : WHO {Kernel} WHAT {Storehouse} --> DISPATCH {PartitionEngine}
    WHEN {Boot}
    WHERE {partition} = [ 1024 ]
    WHY ( Allocate and protect physical memory domains )
    HOW [ +1 : PROCEED ]
    :: < covenant > ( verified )

# ================================================================================
# SUBORDINATE ROLLS: PARTITIONING & CELL INDEXING
# ================================================================================
# Roll 1: Allocate root storehouse of 1024 cells
roll_1 [ Root_Storehouse [ 1024 ] ] ( Root memory domain )

# Roll 2: Carve task partition of 256 cells via v--
roll_2 [ Root_Storehouse v-- Task_Partition [ 256 ] ] ( Isolated task memory slice )

# Roll 3: Inscribe value 99 into Task_Partition at cell 0
roll_3 [ 99 --> Task_Partition @ 0 ] ( Direct cell write )

# Roll 4: Inseparable key & value dual binding
roll_4 [ Key&Value [ 1 & 99 ] ] ( Inseparable dual binding )

# Roll 5: Seal memory tape
roll_5 [ commit_status [ PROCEED ] ] ( Memory tape verified )
```

<TRACK 2> : {OmniCode Language & Standard Library}/lib/core/vectors.omni OMNI | 151 LINES | 676 WORDS | 5.1 KB

```
# ========================================================================
# BLOCK 1: METADATA BLOCK
# ( Core Library Manifest: Invariant Directional Macros & Vector Opcodes )
# ========================================================================
Module < Core.Vectors > ( Invariant vector macros linked to machine dispatch and branching ) {
    version: < "1.0.0" >,
    system: < OmniCode.Core >,
    semantics: < MacroInvariants :: VectorDispatch :: CPUBranching >
}

# Macro Invariant: < ACT_UPON > (Right: Forward Causation)
ACT_UPON_MACRO < InvariantMacro > ( Forward State Dispatch & Mutation ) {
    canonical: < "-->" >,
    shorthand: < "->" >,
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Preposition" >,
    axis: < "+X (Temporal Causality)" >,
    machine_effect: < "forward_pipeline_commit" >
}

# Macro Invariant: < ACT_AGAIN > (Left: Retroaction / Rollback)
ACT_AGAIN_MACRO < InvariantMacro > ( Retroactive Feedback & State Rollback ) {
    canonical: < "<--" >,
    shorthand: < "<-" >,
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Preposition" >,
    axis: < "-X (Feedback / Rewind)" >,
    machine_effect: < "restore_snapshot_branch" >
}

# Macro Invariant: < BUILDS_TO > (Up: Synthesis / Abstraction)
BUILDS_TO_MACRO < InvariantMacro > ( Layering Up into Abstract Domain ) {
    canonical: < "--^" >,
    shorthand: < "-^" >,
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Preposition" >,
    axis: < "+Z (Scale / Synthesis)" >,
    machine_effect: < "type_promotion_and_framing" >
}

# Macro Invariant: < BREAKS_DOWN_FROM > (Down: Decomposition / Analysis)
BREAKS_DOWN_FROM_MACRO < InvariantMacro > ( Layering Down into Hardware Primitive ) {
    canonical: < "--v" >,
    shorthand: < "-v" >,
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Preposition" >,
    axis: < "-Z (Lowering / Destructuring)" >,
    machine_effect: < "register_unpack_and_lowering" >
}

# Scale Modulations (Major, Minor, Great, Small)
MAJOR_MACRO < InvariantMacro > ( Major Ascending Scale Modulation ) {
    canonical: < "/-^" >,
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Adverb" >,
    axis: < "+Scale Major" >,
    machine_effect: < "major_scale_elevation" >
}

MINOR_MACRO < InvariantMacro > ( Minor Descending Scale Modulation ) {
    canonical: < "\\-v" >,
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Adverb" >,
    axis: < "-Scale Minor" >,
    machine_effect: < "minor_scale_lowering" >
}

GREAT_MACRO < InvariantMacro > ( Great Ascending Scale Modulation ) {
    canonical: < "\\-^" >,
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Adverb" >,
    axis: < "+Scale Great" >,
    machine_effect: < "great_scale_elevation" >
}
```

```
SMALL_MACRO < InvariantMacro > ( Small Descending Scale Modulation ) {
    canonical: < "/-v" >,
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Adverb" >,
    axis: < "-Scale Small" >,
    machine_effect: < "small_scale_lowering" >
}

# 2D Quadrant Spatial Vectors
UPPER_RIGHT_MACRO < InvariantMacro > ( Quadrant I Spatial Vector: +X, +Y ) {
    canonical: < "/^" >,
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Preposition" >,
    axis: < "+X, +Y (Upper Right)" >,
    machine_effect: < "quadrant_1_spatial_vector" >
}

LOWER_RIGHT_MACRO < InvariantMacro > ( Quadrant IV Spatial Vector: +X, -Y ) {
    canonical: < "\\v" >,
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Preposition" >,
    axis: < "+X, -Y (Lower Right)" >,
    machine_effect: < "quadrant_4_spatial_vector" >
}

UPPER_LEFT_MACRO < InvariantMacro > ( Quadrant II Spatial Vector: -X, +Y ) {
    canonical: < "^\\" >,
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Preposition" >,
    axis: < "-X, +Y (Upper Left)" >,
    machine_effect: < "quadrant_2_spatial_vector" >
}

LOWER_LEFT_MACRO < InvariantMacro > ( Quadrant III Spatial Vector: -X, -Y ) {
    canonical: < "v/" >,
    grammar_primary: < "Verb" >,
    grammar_secondary: < "Preposition" >,
    axis: < "-X, -Y (Lower Left)" >,
    machine_effect: < "quadrant_3_spatial_vector" >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Preconditions & Vector Context )
# ================================================================================
Opening {
    requires: [ Pipeline.DirectExecution ],
    preconditions: [ +1 ]
}

x_pos [ 1 ] ( Initial X-axis coordinate )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Directional Macro Operations )
# ================================================================================
Body [
    # 1. Forward Causality: Acts upon x_pos, advancing to 10
    step_forward [ x_pos --> 10 ] ( Advance forward along +X )

    # 2. Feedback: Reflects back upon x_pos
    step_feedback [ x_pos <-- 1 ] ( Retroactive check along -X )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Verification & Commit )
# ================================================================================
Closing {
    verify: [
        step_forward = 10 ::
        step_feedback = 10
    ],
    commit_status [ PROCEED ] ( Vector core sealed )
}
```

OmniCode: Chapter 18: Track 3 - Applications, Bridges & Studio

C99 Bare-Metal, Lua Coroutines, Boundary Demos & HUD

CHAPTER IDENTIFIER
CH 18

NOTEBOOKLM WORD COUNT
22,863 words

CATALOGED CHAPTER FILES
34 files (6,769 lines)

GENERATION DATE
2026-10-16 20:36:10

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18

"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27

"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"How does Lua coroutine engine run tape rolls as fibers?"*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (34 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 3> : {Applications & OmniStudio Interfaces}/TRACK.md**	MD	10	52	0.4
2	**<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/01_boundaries_and_asides.omni**	OMNI	168	1,456	10.4
3	**<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/02_logic_and_quad_state.omni**	OMNI	60	302	2.3
4	**<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/03_cardinal_directions.omni**	OMNI	62	328	2.5
5	**<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/04_turing_track_tape.omni**	OMNI	55	348	2.4
6	**<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/05_control_flow_and_loops.omni**	OMNI	146	792	6.4
7	**<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/canonical_notation.omni**	OMNI	75	476	3.2
8	**<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/if_else_statement.omni**	OMNI	64	336	2.6
9	**<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/if_then_statement.omni**	OMNI	60	275	2.3
10	**<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/nested_loop.omni**	OMNI	79	375	2.9
11	**<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/simple_loop.omni**	OMNI	66	316	2.4
12	**<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/while_statement.omni**	OMNI	67	351	2.8
13	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/README.md**	MD	79	379	2.8
14	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/extension.js**	JS	93	306	3.9
15	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/language-configuration.json**	JSON	30	76	0.5
16	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/omnicode-language-0.1.0.vsix**	VSIX	1	5	2.9
17	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/omnicode-language-0.1.1.vsix**	VSIX	1	5	4.0
18	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/omnicode-language-0.1.2.vsix**	VSIX	1	5	6.4
19	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/package.json**	JSON	54	92	1.1
20	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/syntaxes/omnicode.tmLanguage.json**	JSON	321	529	8.7
21	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/snippets/omnicode.json**	JSON	163	611	6.5
22	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/app.js**	JS	509	1,537	20.4
23	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/cloud.html**	HTML	201	718	10.8
24	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/desktop_app.py**	PY	1,182	3,250	44.9
25	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/download.html**	HTML	140	659	8.3
26	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/index.html**	HTML	136	610	7.7
27	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/lexicon.html**	HTML	114	508	6.3
28	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/model.html**	HTML	152	719	8.9
29	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/scrolls.html**	HTML	146	568	7.8
30	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/specs.html**	HTML	155	798	9.6
31	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/studio.html**	HTML	136	610	7.7
32	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/style.css**	CSS	1,747	3,804	37.7
33	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/terminal.html**	HTML	191	782	10.8

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
34	**<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/terminal.js**	JS	305	885	11.9

<TRACK 3> : {Applications & OmniStudio Interfaces}/TRACK.md MD 10 LINES 52 WORDS 0.4 KB

```
# <TRACK 3> : {Applications & OmniStudio Interfaces}

## Scope & Invariant

User-facing tooling, visual studio interfaces, IDE integration, and canonical demonstration tapes.

- `apps/gui/`: OmniStudio HUD web interface & desktop application.
- `apps/editors/`: Visual Studio Code extension, grammar syntaxes, and language tooling.
- `apps/examples/`: Canonical verification reels and language showcase tapes.
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/01_boundaries_and_asides.omni

OMNI | 168 LINES | 1456 WORDS | 10.4 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Ranked Morphological Boundaries & Preserved Intent Asides )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Foundational Showcase: The 6 Ranked Morphological Boundary Types.
#   - Rank 1: < ... > Invariant Axiom      (Immutable Law & Ontological Truth)
#   - Rank 2: [ ... ] Denotation           (Concrete Definition & Mutable State)
#   - Rank 3: { ... } Connotation          (Context, Environment & Payload)
#   - Rank 4: [ ... } Inside-Out Emergence (Entity Projects into Context)
#   - Rank 5: { ... ] Outside-In Imposition(Context Shapes Entity)
#   - Rank 6: ( ... ) Intent Aside         (First-Class Pronunciation & Teleology)
# ================================================================================

= [Module]: < Foundations { Boundaries } > & [ Example { Boundaries and Asides } ] ( Demonstrates the six ranked morphological boundaries and first-class intent asides ) {
    [ Version ]:   { "1.0.0" } ( The Version is in the context of 1.0.0 ),
    [ Created ]:   { "2026-10-11" } ( Created in the context of October 11, 2026 ),
    [ Updated ]:   { "2026-10-12" } ( Last updated in the context of October 12, 2026 ),
    [ Author ]:    { "CreativeWorkzStudio LLC / ProfessorSeanEX" } ( Author in the context of CreativeWorkzStudio LLC and ProfessorSeanEX ),
    [ System ]:    { OmniCode { Core Foundations } } ( System is in the context of OmniCode Core Foundations ),
    [ Witness ]:   < Scripture { Proverbs 8:29 KJV } > { "When he gave to the sea his decree, that the waters should not pass his commandment: when he appointed the foundations of the earth." } ( Invariant Scripture Witness Proverbs 8:29 in the context: When he appointed the foundations of the earth ),
    [ Nature ]:    < FoundationalExample > & { BaseBlock } ( Nature is a Foundational Example in the context of Base Block ),
    [ Semantics ]: { BoundaryPhysics :: MorphologicalClosure :: IntentPreservation } ( Semantics in the context of Boundary Physics, Morphological Closure, and Intent Preservation )
}

# Freestanding Foundational Axiom Declaration
# Rank 1: < ... > Invariant Axiom (Immutable Law)
< Axiom Truth > = < +1 > ( Ground truth axiom: immutably sealed in positive unity ) {
    [ Law ]:       < +1 > ( The immutable truth law is sealed in affirmative Proceed ),
    [ Geometry ]:  ENCLOSE [ Truth ] WITHIN < Invariant Space > ( Truth is bounded by immutable axiom walls )
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    # Rank 1: Invariant Axiom (Inherited law)
    [ Ground Law ]: < Axiom Truth > ( Rank 1: Immutable axiom law ),

    # Rank 2: [ ... ] Denotation (Mutable Definition / State Container)
    [ State Alpha ]: [ +1 ] ( Rank 2: Concrete discrete definition with mutable state initialized to Proceed ),

    # Rank 3: { ... } Connotation (Ambient Universe / Environmental Context)
    { Universe Omega }: { Ground Law } ( Rank 3: Surrounding environmental context holding ground truth ),

    # Rank 4: [ ... } Inside-Out Emergence (Entity Projects Outward into Universe)
    [ Emergent Node }: [ State Alpha } ( Rank 4: Internal definition emerges outward into ambient context ),

    # Rank 5: { ... ] Outside-In Imposition (Environmental Context Shapes Internal Entity)
    { Imposed Node ]: { Universe Omega ] ( Rank 5: Surrounding context actively imposes constraints on internal entity ),

    # Rank 6: ( ... ) Intent Aside (Teleological Purpose & Cognitive Voice)
    ( Preserved Intent ): ( Rank 6: First-class teleological intent preserved in AST for human-AI shared reasoning ),

    # Hardware & Memory Preconditions
    [ Alignment ]: [ Memory Aligned 64 ] ( Memory aligned to 64-bit boundary ),
    [ Preconditions ]: [ (+1) plus (-1) <=> 0 ] & [ Status = +1:PROCEED ] ( ALU equilibrium holds and the machine status is armed in Proceed )
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    # ------------------------------------------------------------------------
    # ROLL 1: RANK 1 INVARIANT VERIFICATION
    # Verify immutable ground truth identity
```

```
    # ------------------------------------------------------------------------
    [ ROLL 1 ] : [ Verify Axiom ] : < Axiom Truth > <=> VERIFY [ +1 ] = [ Truth` ]
        ( Rank 1: Verify immutable ground truth axiom against positive unity ),

    # ------------------------------------------------------------------------
    # ROLL 2: RANK 2 DENOTATIVE STATE MUTATION
    # Advance mutable state within defined boundary
    # ------------------------------------------------------------------------
    [ ROLL 2 ] : [ Mutate State ] : [ State Alpha ] --> ADVANCE [ +1 ] = [ State Alpha` ]
        ( Rank 2: Advance discrete denotative state yielding new state State-Alpha-prime ),

    # ------------------------------------------------------------------------
    # ROLL 3: RANK 3 CONNOTATIVE CONTEXT EXPANSION
    # Expand ambient contextual universe with verified state
    # ------------------------------------------------------------------------
    [ ROLL 3 ] : [ Expand Context ] : { Universe Omega } <-- ABSORB { State Alpha` } = { Universe Omega` }
        ( Rank 3: Ambient context absorbs new denotative state expanding environmental scope ),

    # ------------------------------------------------------------------------
    # ROLL 4: RANK 4 INSIDE-OUT ASYMMETRIC EMERGENCE
    # Project internal discrete state outward into ambient context
    # ------------------------------------------------------------------------
    [ ROLL 4 ] : [ Project Emergence ] : [ State Alpha` } --> EMERGE { Universe Omega` } = [ Emergent Node` }
        ( Rank 4: Discrete state emerges through asymmetrical boundary into ambient universe ),

    # ------------------------------------------------------------------------
    # ROLL 5: RANK 5 OUTSIDE-IN ASYMMETRIC IMPOSITION
    # Impose ambient contextual constraints onto internal discrete entity
    # ------------------------------------------------------------------------
    [ ROLL 5 ] : [ Impose Context ] : { Universe Omega` ] --> IMPOSE [ State Alpha` ] = { Imposed Node` ]
        ( Rank 5: Ambient universe imposes environmental boundaries onto internal discrete state ),

    # ------------------------------------------------------------------------
    # ROLL 6: RANK 6 FIRST-CLASS INTENT ASIDE PRESERVATION
    # Preserve teleological intent as a first-class AST node for human-AI cognition
    # ------------------------------------------------------------------------
    [ ROLL 6 ] : [ Preserve Intent ] : ( Preserved Intent ) --> RECORD [ AST ] = ( Teleology Verified` )
        ( Rank 6: Intent aside preserved as live AST node for human-AI cognitive continuity )
]

# ============================================================================
# BLOCK 4: CLOSING BLOCK
# ============================================================================
Closing ( Sealing Gate: Reconcile, validate, tripwire, debug, log, and affirm permanent boundary execution ) {
    # ------------------------------------------------------------------------
    # 1. VERIFICATION OF OPERATIONAL ROLLS
    # ------------------------------------------------------------------------
    [ Verify ]: [
        [ ROLL 1 ] = PROCEED ::
        [ ROLL 2 ] = PROCEED ::
        [ ROLL 3 ] = PROCEED ::
        [ ROLL 4 ] = PROCEED ::
        [ ROLL 5 ] = PROCEED ::
        [ ROLL 6 ] = PROCEED
    ] ( Verify that all six boundary operational rolls achieved affirmative consensus in PROCEED ),

    # ------------------------------------------------------------------------
    # 2. VALIDATION OF INVARIANT INTEGRITY & CLOSURE
    # ------------------------------------------------------------------------
    [ Validate ]: { Truth` = +1 } & { State Alpha` = +1 } & { Emergent Node` } & { Imposed Node` } & ( Teleology
Verified` )
        ( Validate that invariant truth holds, state remains affirmative, and all morphological closures and asides are
sealed ),

    # ------------------------------------------------------------------------
    # 3. ZERO-TOLERANCE TRIPWIRING
    # ------------------------------------------------------------------------
    [ Tripwire ]: { Status` = +1:PROCEED } --> [ ARMED ] | { Status` != +1:PROCEED } --> [ TRIPPED ] --> [ Commit Status
= -1:ROLLBACK ]
        ( Tripwire remains armed in Proceed or trips on anomaly to veto execution ),

    # ------------------------------------------------------------------------
    # 4. DIAGNOSTIC DEBUG TELEMETRY
    # ------------------------------------------------------------------------
    [ Debug ]: { [ Truth` ] :: [ State Alpha` ] :: [ Emergent Node` ] :: [ Imposed Node` ] :: ( Teleology Verified` ) ::
[ Status` ] }
        ( Expose diagnostic telemetry across all verified morphological boundaries and machine status ),

```

```
    # ------------------------------------------------------------------------
    # 5. EPISODIC INVENTORY LOGGING
    # ------------------------------------------------------------------------
    [ Log ]: [ Journal ]: INSCRIBE { [ Boundaries Sealed ] :: [ Rank 1 Through 6 ] :: [ Truth` ] }
        ( Inscribe the verified boundary physics demonstration into the permanent episodic system journal ),

    # ------------------------------------------------------------------------
    # 6. PERMANENT COVENANT EXECUTION & FOURFOLD COMMIT STATUS LOOP
    # ------------------------------------------------------------------------
    [ Commit Status ]: [
        # +1: PROCEED (+t: Advance forward along the causal tape)
        { [ Verify ] = PROCEED } & { [ Tripwire ] = ARMED }
            --> [ +1:PROCEED ] |

        #  0: AWAIT (t=t: Hold in equilibrium, pending resolution)
        { [ Status` ] = PENDING }
            --> [ 0:AWAIT ] :: REPEAT |

        # NULL: HALT (t=empty: Cessation of clock, absolute stop)
        { [ Status` ] = NULL }
            --> [ HALT:NULL ] |

        # -1: ROLLBACK (-t: Reverse causal tape to origin t=0)
        { [ Tripwire ] = TRIPPED } | { [ Verify ] != PROCEED }
            --> [ -1:ROLLBACK ]
    ] ( Fourfold state machine: Proceed advances forward, Await holds equilibrium, Halt ceases execution in Null,
Rollback reverts to origin )
}
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/02_logic_and_quad_state.omni

OMNI | 60 LINES | 302 WORDS | 2.3 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Balanced Ternary Logic & Micro/Macro Quad-State Truth Space )
# ================================================================================
Module < Logic.QuadStateEngine > ( Showcase Balanced Ternary and Micro/Macro Duality ) {
    version: < "1.0.0" >,
    system: < OmniCode.Core >,
    semantics: < BalancedTernary :: MicroMacroDuality :: CaveatPhysics >
}

AxiomAffirmation < yes >    ( Micro: yes == Macro: PROCEED == +1 )
AxiomRefutation  < no >     ( Micro: no  == Macro: ROLLBACK == -1 )
AxiomBalance     < ok >     ( Micro: ok  == Macro: AWAIT    ==  0 )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Preconditions & State Initialization )
# ================================================================================
Opening {
    requires: [ TruthSpace.T4 ],
    preconditions: [ AxiomAffirmation = PROCEED ]
}

flag_affirm [ yes ]   ( Initial affirmative state )
flag_negate [ -- yes ] ( Negation flips +1 to -1: no )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Truth Space Algebra: Conjunction, Disjunction, Negation, and Caveat Gate )
# ================================================================================
Body [
    # 1. Micro/Macro Equivalence Checks
    affirm_check [ flag_affirm = PROCEED ] ( Affirmation matches PROCEED )
    refute_check [ flag_negate = ROLLBACK ] ( Negated affirmation matches ROLLBACK )

    # 2. Conjunction (:: AND) and Disjunction (| OR)
    and_test [ yes :: yes = PROCEED ]
    or_test  [ yes | no = PROCEED ]

    # 3. Adversative Caveat Gate (! BUT)
    # The action proceeds ONLY because the caveat holds (+1)
    gated_action [ flag_affirm ! [ affirm_check = yes ] ] ( Caveat permits forward commit )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Verification & Macro State Commit )
# ================================================================================
Closing {
    verify: [
        affirm_check = yes ::
        refute_check = yes ::
        and_test = yes ::
        or_test = yes ::
        gated_action = PROCEED
    ],
    commit_status [ PROCEED ] ( Commit verified quad-state execution )
}

```

<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/03_cardinal_directions.omni

OMNI | 62 LINES | 328 WORDS | 2.5 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( 4 Cardinal Directions Across Causality and Abstraction Axes )
# ================================================================================
Module < Geometry.CardinalDirections > ( Showcase 4 cardinal directional vectors and shorthands ) {
    version: < "1.0.0" >,
    system: < OmniCode.Core >,
    semantics: < VectorDynamics :: CausalityAndScale >
}

BaseDomain < 100 >   ( Ground level primitive )
TargetDomain < 200 > ( Elevated abstract domain )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Vector Preconditions & Initial States )
# ================================================================================
Opening {
    requires: [ CoordinatePlane.2D ],
    preconditions: [ BaseDomain = 100 ]
}

step_x [ 10 ] ( State moving across X temporal axis )
step_z [ 10 ] ( State moving across Z scale axis )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Cardinal Vector Executions: Right, Left, Up, Down )
# ================================================================================
Body [
    # 1. Right (--> and ->): Forward Causation / Act Upon
    forward_canonical [ step_x --> 20 ] ( Forward step advancing state to 20 )
    forward_shorthand [ step_x -> 30 ]  ( Shorthand forward step to 30 )

    # 2. Left (<-- and <-): Retroaction / Feedback / Rollback
    feedback_canonical [ step_x <-- 10 ] ( Retroactive feedback step )
    feedback_shorthand [ step_x <- 10 ]  ( Shorthand feedback step )

    # 3. Up (--^ and -^): Synthesis / Abstraction / Ascend
    ascend_canonical [ step_z --^ TargetDomain ] ( Synthesis into target domain )
    ascend_shorthand [ step_z -^ TargetDomain ]  ( Shorthand synthesis )

    # 4. Down (--v and -v): Decomposition / Analysis / Descend
    descend_canonical [ TargetDomain --v BaseDomain ] ( Decomposition into base domain )
    descend_shorthand [ TargetDomain -v BaseDomain ]  ( Shorthand decomposition )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Vector Integrity Verification & Commit )
# ================================================================================
Closing {
    verify: [
        forward_canonical = 20 ::
        forward_shorthand = 30 ::
        ascend_canonical = 200 ::
        descend_canonical = 100
    ],
    commit_status [ PROCEED ] ( Commit verified vector trajectory )
}

```

<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/04_turing_track_tape.omni

OMNI | 55 LINES | 348 WORDS | 2.4 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK (THE TRACK)
# ( Track Manifest, Semantic Intent, and Inferred Ontological Types )
# ================================================================================
Module < ArithmeticReel.Tape1 > ( Add 1 ball to the group A which contains 4 balls ) {
    version: < "1.0.0" >,
    system: < OmniCode.Core >,
    semantics: < TrackPhysics :: MultiTape :: AIInference >
}

# The ? (Infer Operator) marks concepts whose structural types are inferred by the AI brain:
Ball < Entity? > ( Inferred discrete unit: resolved from natural sentence )
Group < Set? >   ( Inferred collection container: resolved from natural sentence )

# ================================================================================
# BLOCK 2: OPENING BLOCK (THE HEAD)
# ( The Focal Setup: Reading Initial Conditions and Contextual State )
# ================================================================================
Opening {
    import: [ Core.Arithmetic :: Core.Logic ],
    requires: [ Group : Set? :: Ball : Entity? ],
    preconditions: [ +1 ]
}

# The Head sets Group A with initial count of 4 balls
A [ 4 : Ball? ] { Group? } ( Group A initialized with 4 inferred balls )
new_ball [ 1 : Ball? ]     ( 1 additional ball to be introduced )

# ================================================================================
# BLOCK 3: BODY BLOCK (THE TAPE & ROLLS)
# ( The Tape Execution: SVO Rolls advancing the state forward using 'plus' )
# ================================================================================
Body [
    # ROLL 1 (SVO Action): Subject A acts upon target, advancing by 'plus' new_ball
    roll_1 [ A --> A plus new_ball ] ( Act upon A: causal transition from 4 to 5 balls )

    # ROLL 2 (SVO Verification): Subject A is 5 under the caveat that new_ball is 1
    roll_2 [ A = 5 ! [ new_ball = 1 ] ] ( State is 5, provided caveat of 1 added ball holds )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK (REEL COMMIT & PROOF)
# ( Tape Stop: Verification Invariants and State Commit )
# ================================================================================
Closing {
    verify: [
        roll_1 = 5 ::
        roll_2 = PROCEED ::
        A = 5 ::
        ADD = InvariantMacro
    ],
    commit_status [ PROCEED ] ( Commit the verified tape state )
}

```

<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/05_control_flow_and_loops.omni

OMNI | 146 LINES | 792 WORDS | 6.4 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Control Flow Manifest: Quad-State Accumulator Loops & Conditional Branching )
# ================================================================================
Module < ControlFlow.QuadStateShowcase > ( Canonical showcase of Simple Loops, Nested Loops, While statements, and If/Then/Else branches ) {
    version: < "1.0.0" >,
    author: < "ProfessorSeanEX & Antigravity" >,
    system: < OmniCode.Core >,
    semantics: < BalancedTernary :: QuadStateControlFlow :: NamedSiliconRegisters >
}

# Axiomatic Boundary Limits & Invariant Constants
LOOP_BOUND < 10 >          ( Invariant boundary ceiling for linear simple loop )
GRID_ROWS  < 3 >           ( Invariant outer dimension: 3 rows )
GRID_COLS  < 4 >           ( Invariant inner dimension: 4 columns )
THRESHOLD  < 100 >         ( Invariant threshold boundary for while condition )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Hardware Context Setup, Register Allocations & Preconditions )
# ================================================================================
Opening {
    import: [ Core.Logic :: Core.Arithmetic ],
    requires: [ TruthSpace.T4 :: MemoryAligned ],
    preconditions: [ +1 ]
}

# Physical Register Initializations for Body Execution
loop_acc         [ 0 ] ( Silicon Accumulator IT container )
loop_turn        [ 0 ] ( Temporal Cadence TURN container )
sensor_reading   [ 25 ] ( Dynamic reading for while statement )
condition_affirm [ yes ] ( Affirmative condition flag: +1 )
condition_refute [ no ]  ( Refuted condition flag: -1 )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( The 5 Canonical Control Flow Constructs )
# ================================================================================
Body [
    # --------------------------------------------------------------------------
    # 1. SIMPLE LOOP: Linear Quad-State Accumulator cycling from 0 up to BOUND
    # --------------------------------------------------------------------------
    simple_loop [
        STATE (
            < BOUND = LOOP_BOUND >,
            [ IT = 0, TURN = 0 ],
            { SPOOL }
        ) = [
            PROCEED  -WHEN-> { (IT plus 1 --> IT) & (TURN plus 1 --> TURN) },
            AWAIT    -WHEN-> { BUSY },
            ROLLBACK -WHEN-> { FAULT & (HOME --> IT) },
            HALT     -WHEN-> { TURN = BOUND }
        ]
    ] ( Simple linear loop: ticks up IT and TURN until watchdog BOUND is met )

    # --------------------------------------------------------------------------
    # 2. NESTED LOOP: 2D Matrix Grid Iteration (Outer Row x Inner Column)
    # --------------------------------------------------------------------------
    nested_loop [
        STATE (
            < ROW_BOUND = GRID_ROWS, COL_BOUND = GRID_COLS >,
            [ ROW_TURN = 0, ROW_SUM = 0 ],
            { SPOOL }
        ) = [
            PROCEED -WHEN-> {
                # Inner Column State Loop: accumulates COL_BOUND cells per row
                STATE (
                    < BOUND = COL_BOUND >,
                    [ COL_TURN = 0, IT = ROW_SUM ],
                    { SPOOL }
                ) = [
                    PROCEED  -WHEN-> { (IT plus 1 --> IT) & (COL_TURN plus 1 --> COL_TURN) },
```

```
                    AWAIT    -WHEN-> { BUSY },
                    ROLLBACK -WHEN-> { FAULT & (HOME --> IT) },
                    HALT     -WHEN-> { COL_TURN = BOUND }
                ] &
                (IT --> ROW_SUM) &
                (ROW_TURN plus 1 --> ROW_TURN)
            },
            AWAIT    -WHEN-> { BUSY },
            ROLLBACK -WHEN-> { FAULT },
            HALT     -WHEN-> { ROW_TURN = ROW_BOUND }
        ]
    ] ( Nested 2D loop: outer row cadence driving inner column accumulator )

    # ------------------------------------------------------------------------
    # 3. WHILE STATEMENT: Predicated Quad-State Loop
    # Advances while sensor_reading < THRESHOLD; halts when condition ceases
    # ------------------------------------------------------------------------
    while_statement [
        STATE (
            < BOUND = THRESHOLD >,
            [ IT = sensor_reading, TURN = 0 ],
            { FROM }
        ) = [
            PROCEED  -WHEN-> { (sensor_reading < THRESHOLD) & (IT plus 15 --> IT) & (TURN plus 1 --> TURN) },
            AWAIT    -WHEN-> { SENSOR_BUSY },
            ROLLBACK -WHEN-> { SENSOR_ERROR & (HOME --> IT) },
            HALT     -WHEN-> { (IT >= THRESHOLD) | (TURN = 100) }
        ]
    ] ( While loop: continues PROCEED while predicate holds, HALT escapes boundary )

    # ------------------------------------------------------------------------
    # 4. IF / THEN STATEMENT: Unilateral Conditional Gate
    # Evaluates condition: if affirmative (+1), actuates then branch; else awaits
    # ------------------------------------------------------------------------
    if_then_statement [
        STATE (
            [ IT = 0 ],
            { INTO }
        ) = [
            PROCEED -WHEN-> { condition_affirm & (42 --> IT) },
            AWAIT   -WHEN-> { -- condition_affirm }
        ]
    ] ( If/Then gate: proceeds with forward action only under verified affirmative condition )

    # ------------------------------------------------------------------------
    # 5. IF / ELSE STATEMENT: Bilateral Ternary Branch
    # Evaluates condition: +1 forks to then branch, -1 forks to else branch
    # ------------------------------------------------------------------------
    if_else_statement [
        STATE (
            [ IT = 0 ],
            { INTO }
        ) = [
            PROCEED  -WHEN-> { (condition_refute = yes) & (100 --> IT) },
            ROLLBACK -WHEN-> { (condition_refute = no)  & (200 --> IT) },
            AWAIT    -WHEN-> { condition_refute = ok }
        ]
    ] ( If/Else branch: balanced ternary fork selecting between affirmative and negative vectors )
]

# ============================================================================
# BLOCK 4: CLOSING BLOCK
# ( Postconditions, Invariant Integrity Proofs & Macro State Commit )
# ============================================================================
Closing {
    verify: [
        LOOP_BOUND = 10 ::
        GRID_ROWS = 3 ::
        GRID_COLS = 4 ::
        THRESHOLD = 100
    ],
    commit_status [ PROCEED ] ( Verified quad-state control flow suite sealed )
}
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/canonical_notation.omni

OMNI | 75 LINES | 476 WORDS | 3.2 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( File Identity, Version, Author, Intent Aside, and Ontological Axioms )
# ================================================================================
Module < CanonicalNotationShowcase > ( Foundations of Being, Causality, and Abstraction ) {
    version: < "1.0.0" >,
    author: < "ProfessorSeanEX" >,
    system: < OmniCode.Core >,
    semantics: < BalancedTernary :: QuadState :: BoundaryPhysics >
}

# Axiomatic Categories (Invariant Sets)
A < +1 > ( Invariant category A: axiomatic ground truth )
B < +1 > ( Invariant category B: independent set domain )


# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Environment Setup, Preconditions, Scoped Universes, and Context Dictation )
# ================================================================================
Opening {
    requires: [ MemoryAligned :: TypeChecking ],
    initial_truth: [ +1 ]
}

# Mutable Denotations initialized in Opening
a [ +1 ] ( Particular instance 'a' initialized with mutable proceed state )
b [ +1 ] ( Particular instance 'b' initialized with mutable proceed state )

# Contextual Connotations & Asymmetric Causality
a_in_A [ a ] { A }  ( Instance 'a' validated within contextual universe A )
a_top_down { A ]    ( Outside-In: Environment A actively forces definition of a )
b_bottom_up [ B }   ( Inside-Out: Definition of b emerges from context B )


# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Core Transformations, Being Relations, Causality Vectors, and Connectives )
# ================================================================================
Body [
    # 1. Ontological Relations of Being (Y-Axis)
    instance_typing [ a : A ]    ( 'a' stands in relation to Category A )
    identity_check [ a = a ]     ( 'a' is identical to 'a' )
    distinction_check [ a != b ] ( 'a' is not 'b' )
    similarity_check [ a ~= b ]  ( 'a' is liken to 'b' in structural form )

    # 2. Temporal & Causal Vectors (X-Axis)
    forward_action [ a --> b ]   ( 'a' acts upon 'b' forward in time )
    feedback_action [ b <-- a ]  ( 'b' reflects back upon 'a' as retroactive feedback )

    # 3. Hierarchical Abstraction Vectors (Z-Axis)
    synthesis [ a ^-- A ]        ( Low-level primitive 'a' builds up to high-level concept A )
    decomposition [ A v-- a ]    ( High-level category A decomposes down into primitive 'a' )

    # 4. Connectives & Adversative Caveat Pipeline
    negation [ -- a ]            ( Inverts state of 'a' across ternary zero balance )
    conjunction [ a : A :: b : B ]
    pipeline [ a --> b ! [ a : A :: b : B ] ] ( 'a' acts on 'b', BUT caveat must be satisfied )
]


# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Postconditions, Invariant Integrity Proofs, Teardown, and Commit / Return )
# ================================================================================
Closing {
    verify: [
        identity_check = +1 ::
        forward_action = +1 ::
        pipeline = +1
    ],
    on_rollback: [ <-- unwind_state ],
```

```
    commit_status: [ +1 ] ( Commit state: verified execution )
}
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/if_else_statement.omni

OMNI | 64 LINES | 336 WORDS | 2.6 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( File Manifest: Canonical Quad-State If/Else Bilateral Ternary Branch )
# ================================================================================
Module < ControlFlow.IfElseStatement > ( Demonstrates bilateral ternary branching in Quad-State logic ) {
    version: < "1.0.0" >,
    author: < "ProfessorSeanEX & Antigravity" >,
    system: < OmniCode.Core >,
    semantics: < BalancedTernary :: TernaryBranching :: NamedSiliconRegisters >
}

# Invariant Branch Targets
THEN_RESULT < 100 > ( Value emitted when condition is affirmative: +1 )
ELSE_RESULT < 200 > ( Value emitted when condition is refutative: -1 )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Context Preconditions & Branch Flag Setup )
# ================================================================================
Opening {
    import: [ Core.Logic :: Core.Arithmetic ],
    requires: [ TruthSpace.T4 ],
    preconditions: [ +1 ]
}

# The active condition to evaluate (set to 'no' to trigger else branch)
branch_condition [ no ] ( Initial condition evaluating to -1 / ROLLBACK )
branch_acc       [ 0 ]  ( Accumulator register receiving selected branch output )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Execution: If/Else Bilateral Branch )
# ================================================================================
Body [
    # THE IF / ELSE STATEMENT:
    # `if (branch_condition == yes) { IT = THEN_RESULT; } else { IT = ELSE_RESULT; }`
    # - PROCEED (+1) : True branch (actuates THEN_RESULT into IT)
    # - ROLLBACK (-1): False branch (actuates ELSE_RESULT into IT)
    # - AWAIT (0)    : Neutral / uncommitted state (holds position)
    if_else_branch [
        STATE (
            [ IT = branch_acc ],
            { INTO }
        ) = [
            PROCEED  -WHEN-> { (branch_condition = yes) & (THEN_RESULT --> IT) },
            ROLLBACK -WHEN-> { (branch_condition = no)  & (ELSE_RESULT --> IT) },
            AWAIT    -WHEN-> { branch_condition = ok }
        ]
    ] ( If/Else branch: selects between affirmative then and refutative else vectors )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Postconditions & Commit Status )
# ================================================================================
Closing {
    verify: [
        THEN_RESULT = 100 ::
        ELSE_RESULT = 200 ::
        branch_condition = no
    ],
    commit_status [ PROCEED ] ( If/Else ternary branch verified and sealed )
}
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/if_then_statement.omni

OMNI | 60 LINES | 275 WORDS | 2.3 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( File Manifest: Canonical Quad-State If/Then Unilateral Conditional Gate )
# ================================================================================
Module < ControlFlow.IfThenStatement > ( Demonstrates unilateral conditional gating in Quad-State logic ) {
    version: < "1.0.0" >,
    author: < "ProfessorSeanEX & Antigravity" >,
    system: < OmniCode.Core >,
    semantics: < BalancedTernary :: ConditionalGating :: NamedSiliconRegisters >
}

# Invariant Target Payload
PAYLOAD_VALUE < 42 > ( Value to be transduced upon affirmative condition )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Context Preconditions & Flag Setup )
# ================================================================================
Opening {
    import: [ Core.Logic :: Core.Arithmetic ],
    requires: [ TruthSpace.T4 ],
    preconditions: [ +1 ]
}

# Initial Register & Condition States
permission_flag [ yes ] ( Affirmative precondition flag: +1 )
accumulator     [ 0 ]   ( Destination IT register )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Execution: If/Then Conditional Gate )
# ================================================================================
Body [
    # THE IF / THEN STATEMENT:
    # `if (permission_flag) { accumulator = PAYLOAD_VALUE; }`
    # - PROCEED: When condition is affirmative (+1), actuates vector into IT
    # - AWAIT  : When condition is non-affirmative, holds state without mutating
    if_then_dispatch [
        STATE (
            [ IT = accumulator ],
            { INTO }
        ) = [
            PROCEED -WHEN-> { permission_flag & (PAYLOAD_VALUE --> IT) },
            AWAIT   -WHEN-> { -- permission_flag }
        ]
    ] ( If/Then gate: proceeds with forward action only when permission holds )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Postconditions & Commit Status )
# ================================================================================
Closing {
    verify: [
        PAYLOAD_VALUE = 42 ::
        permission_flag = yes
    ],
    commit_status [ PROCEED ] ( If/Then conditional gate verified and sealed )
}
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/nested_loop.omni OMNI 79 LINES 375 WORDS 2.9 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( File Manifest: Canonical Quad-State Nested 2D Grid Loop )
# ================================================================================
Module < ControlFlow.NestedLoop > ( Demonstrates 2D matrix row and column grid iteration ) {
    version: < "1.0.0" >,
    author: < "ProfessorSeanEX & Antigravity" >,
    system: < OmniCode.Core >,
    semantics: < BalancedTernary :: NestedStateLoop :: NamedSiliconRegisters >
}

# Invariant Grid Dimensions
NUM_ROWS < 3 > ( Outer loop dimension: 3 rows )
NUM_COLS < 4 > ( Inner loop dimension: 4 columns )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Context Preconditions & Coordinate Initialization )
# ================================================================================
Opening {
    import: [ Core.Logic :: Core.Arithmetic ],
    requires: [ TruthSpace.T4 ],
    preconditions: [ +1 ]
}

# Initial Register Setup
grid_sum  [ 0 ] ( Running total accumulated across all cells )
grid_rows [ 0 ] ( Current outer row iteration count )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Execution: Nested Row/Column Traversal )
# ================================================================================
Body [
    # THE NESTED LOOP:
    # Outer STATE manages ROW_TURN up to ROW_BOUND.
    # On each outer PROCEED, the inner STATE manages COL_TURN up to COL_BOUND,
    # accumulating into IT and retiring into grid_sum.
    matrix_traversal [
        STATE (
            < ROW_BOUND = NUM_ROWS, COL_BOUND = NUM_COLS >,
            [ ROW_TURN = 0, ROW_ACC = 0 ],
            { SPOOL }
        ) = [
            PROCEED -WHEN-> {
                # Inner Column State Loop:
                STATE (
                    < BOUND = COL_BOUND >,
                    [ COL_TURN = 0, IT = ROW_ACC ],
                    { SPOOL }
                ) = [
                    PROCEED  -WHEN-> { (IT plus 1 --> IT) & (COL_TURN plus 1 --> COL_TURN) },
                    AWAIT    -WHEN-> { BUSY },
                    ROLLBACK -WHEN-> { FAULT & (HOME --> IT) },
                    HALT     -WHEN-> { COL_TURN = BOUND }
                ] &
                (IT --> ROW_ACC) &
                (ROW_TURN plus 1 --> ROW_TURN)
            },
            AWAIT    -WHEN-> { BUSY },
            ROLLBACK -WHEN-> { FAULT },
            HALT     -WHEN-> { ROW_TURN = ROW_BOUND }
        ]
    ] ( Nested 2D loop traverses all rows and columns to completion )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Postconditions & Commit Status )
# ================================================================================
Closing {
    verify: [
        NUM_ROWS = 3 ::
        NUM_COLS = 4 ::
```

```
        grid_sum = 0
    ],
    commit_status [ PROCEED ] ( Nested loop verified and sealed )
}
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/simple_loop.omni OMNI 66 LINES 316 WORDS 2.4 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( File Manifest: Canonical Quad-State Simple Linear Loop )
# ================================================================================
Module < ControlFlow.SimpleLoop > ( Demonstrates single-dimensional linear accumulator loop ) {
    version: < "1.0.0" >,
    author: < "ProfessorSeanEX & Antigravity" >,
    system: < OmniCode.Core >,
    semantics: < BalancedTernary :: QuadStateLoop :: NamedSiliconRegisters >
}

# Invariant Watchdog Bound
CEILING < 10 > ( Invariant maximum bound for accumulator loop )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Context Preconditions & Register Initialization )
# ================================================================================
Opening {
    import: [ Core.Logic :: Core.Arithmetic ],
    requires: [ TruthSpace.T4 ],
    preconditions: [ +1 ]
}

# Initial Register Setup
initial_it   [ 0 ] ( Initial primary accumulator IT value )
initial_turn [ 0 ] ( Initial temporal cadence TURN value )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Execution: Linear Accumulator Loop )
# ================================================================================
Body [
    # THE SIMPLE LOOP:
    # Cycles through T4 truth space:
    #   +1 (PROCEED)  : Ticks up IT and TURN
    #    0 (AWAIT)    : Yields / waits if bus is busy
    #   -1 (ROLLBACK) : Rewinds to baseline HOME on fault
    #   NULL (HALT)   : Breaks loop when TURN reaches BOUND
    loop_result [
        STATE (
            < BOUND = CEILING >,
            [ IT = initial_it, TURN = initial_turn ],
            { SPOOL }
        ) = [
            PROCEED  -WHEN-> { (IT plus 1 --> IT) & (TURN plus 1 --> TURN) },
            AWAIT    -WHEN-> { BUSY },
            ROLLBACK -WHEN-> { FAULT & (HOME --> IT) },
            HALT     -WHEN-> { TURN = BOUND }
        ]
    ] ( Linear accumulator loop runs to completion when TURN equals BOUND )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Postconditions & Commit Status )
# ================================================================================
Closing {
    verify: [
        CEILING = 10 ::
        initial_it = 0 ::
        initial_turn = 0
    ],
    commit_status [ PROCEED ] ( Simple loop verified and sealed )
}
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/examples/while_statement.omni

OMNI | 67 LINES | 351 WORDS | 2.8 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( File Manifest: Canonical Quad-State Predicated While Loop )
# ================================================================================
Module < ControlFlow.WhileStatement > ( Demonstrates predicate-governed loop advancing while condition holds ) {
    version: < "1.0.0" >,
    author: < "ProfessorSeanEX & Antigravity" >,
    system: < OmniCode.Core >,
    semantics: < BalancedTernary :: PredicatedWhileLoop :: NamedSiliconRegisters >
}

# Invariant Threshold Boundary
MAX_THRESHOLD < 100 > ( Invariant upper ceiling triggering while loop termination )
MAX_CYCLES    < 500 > ( Watchdog maximum turn count )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Context Preconditions & Initial Sensor Values )
# ================================================================================
Opening {
    import: [ Core.Logic :: Core.Arithmetic ],
    requires: [ TruthSpace.T4 ],
    preconditions: [ +1 ]
}

# Initial Stream Values
sensor_reading [ 10 ] ( Initial inbound value to be sampled )
sensor_status  [ ok ] ( Initial bus status: equilibrium 0 )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Execution: Predicated While Loop )
# ================================================================================
Body [
    # THE WHILE STATEMENT:
    # `while (sensor_reading < MAX_THRESHOLD) { Process_Stream(); }`
    # - PROCEED: Advances while the predicate is affirmative (+1)
    # - AWAIT  : Yields/pauses while the hardware sensor is busy sampling (0)
    # - ROLLBACK: Restores baseline from HOME if parity fails (-1)
    # - HALT   : Escapes the loop when predicate becomes false or watchdog trips (NULL)
    while_sensor_stream [
        STATE (
            < BOUND = MAX_CYCLES >,
            [ IT = sensor_reading, TURN = 0 ],
            { FROM }
        ) = [
            PROCEED  -WHEN-> { (sensor_reading < MAX_THRESHOLD) & (IT plus 10 --> IT) & (TURN plus 1 --> TURN) },
            AWAIT    -WHEN-> { SENSOR_BUSY },
            ROLLBACK -WHEN-> { SENSOR_ERROR & (HOME --> IT) },
            HALT     -WHEN-> { (IT >= MAX_THRESHOLD) | (TURN = BOUND) }
        ]
    ] ( While statement loops until sensor exceeds threshold or bound is reached )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Postconditions & Commit Status )
# ================================================================================
Closing {
    verify: [
        MAX_THRESHOLD = 100 ::
        MAX_CYCLES = 500 ::
        sensor_reading = 10
    ],
    commit_status [ PROCEED ] ( While loop verified and sealed )
}
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/README.md | MD | 79 LINES | 379 WORDS | 2.8 KB

```
# OmniCode VS Code & IDE Extension

> **Official Language Support Package for Visual Studio Code, Cursor, and Google Antigravity IDE.**

Provides morphological boundary colorization, 3D coordinate operator grammar, balanced ternary literals, and universal 4-Block file templates.

---

## 1. Extension Topology & Installation

### File Topology

```text
editors/vscode/
├── package.json                   # Extension manifest (v0.1.2, .omni & .scroll associations)
├── language-configuration.json    # Brackets, auto-closing pairs, comment syntax
├── snippets/
│   └── omnicode.json             # 4-Block auto-population snippets (omni-file & omni-scroll)
└── syntaxes/
    └── omnicode.tmLanguage.json  # TextMate syntax grammar scopes & keyword rules
```

Installation

```bash
# Package the VSIX extension
npx -y @vscode/vsce package --allow-missing-repository

# Install into Antigravity IDE / VS Code
code --install-extension editors/vscode/omnicode-language-0.1.2.vsix
```

---

2. Core Capabilities & Grammar

Morphological Boundary Highlighting

Visually distinguishes all six ontological boundary types to eliminate bracket blindness:

* `[ ... ]` : **Denotation** (Fixed definitions, physical registers)
* `< ... >` : **Invariant** (Immutable axioms, process types)
* `{ ... }` : **Connotation** (Ambient context, scoped universes)
* `{ ... ]` : **Top-Down** (Context dictates definition / Absorber)
* `[ ... }` : **Bottom-Up** (Definition emerges from context / Generator)
* `( ... )` : **Aside** (Machine-readable intent and AI reasoning traces)

3D Coordinate Operator Colorization

* **Y-Axis (Being/Identity):** `=`, `!=`, `~=` / `≈`
* **X-Axis (Dynamics/Causality):** `-->` (Act upon forward), `<--` (Retroactive feedback/rollback)
* **Z-Axis (Scale/Hierarchy):** `^--` (Builds to / Layer up), `v--` (Breaks down from / Layer down)
* **Connectives:** `!` (Adversative caveat), `::` (And), `:` (In relation to), `|` (Or), `--` (Not)

Balanced Ternary Truth Literals

* `+1`, `YES`, `PROCEED` (Monotonic commit)
* `0`, `OK`, `AWAIT` (Asynchronous yield / equilibrium)
* `-1`, `NO`, `ROLLBACK` (State unwinding)
* `NULL`, `VOID`, `HALT` (Terminal trap)

Universal 4-Block Auto-Population Snippets

* `omni-file` / `omni-4block`: Complete compliant `.omni` module template with interactive tab stops.
* `omni-scroll` / `scroll`: Complete compliant `.scroll` episodic trace and learning template.
* `block-1`: Scaffolds Block 1: Metadata Block.
* `block-2`: Scaffolds Block 2: Opening Block.
* `block-3`: Scaffolds Block 3: Body Block.
* `block-4`: Scaffolds Block 4: Closing Block.

```

```
## 3. Verified Extension State & Invariants

* **Language ID:** `omnicode`
* **File Associations:** `*.omni`, `*.scroll`
* **Grammar Version:** `0.1.2`
* **Editor Integration:** Tested on VS Code 1.75+ and Antigravity IDE.
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/extension.js

JS | 93 LINES | 306 WORDS | 3.9 KB

```
// ================================================================================
// OmniCode VS Code Extension: Hover & Docstring Subsystem
// ================================================================================
// Connects the editor to the native OmniCode language engine (CLI & HTTP).
// Delivers 3-Tier composite hovercards bridging high-level .tape process ribbons
// down to low-level .omni invariant contracts and physical silicon execution states.
// ================================================================================

const vscode = require('vscode');
const { execFile } = require('child_process');
const http = require('http');

/**
 * Activates the OmniCode VS Code Extension.
 * Registers the HoverProvider for .omni, .scroll, and .tape files.
 * @param {vscode.ExtensionContext} context
 */
function activate(context) {
    const hoverProvider = vscode.languages.registerHoverProvider('omnicode', {
        provideHover(document, position, token) {
            const range = document.getWordRangeAtPosition(position);
            if (!range) {
                return null;
            }

            const symbol = document.getText(range);
            const line = position.line + 1;
            const col = position.character + 1;
            const filePath = document.fileName;

            return new Promise((resolve) => {
                // Method 1: Try local omnicode CLI binary directly
                execFile(
                    'omnicode',
                    ['hover', filePath, String(line), String(col), '--json'],
                    { timeout: 3000 },
                    (err, stdout) => {
                        if (!err && stdout) {
                            try {
                                const data = JSON.parse(stdout.trim());
                                if (data && data.markdown) {
                                    const md = new vscode.MarkdownString(data.markdown);
                                    md.isTrusted = true;
                                    md.supportHtml = true;
                                    return resolve(new vscode.Hover(md, range));
                                }
                            } catch (_e) {
                                // Fall through to HTTP server fallback
                            }
                        }

                        // Method 2: Fallback to running OmniCode Studio / GUI server (default port 8080)
                        const url = `http://127.0.0.1:8080/api/hover?file=${encodeURIComponent(filePath)}&line=${line}&col=${col}`;
                        const req = http.get(url, (res) => {
                            let body = '';
                            res.on('data', (chunk) => (body += chunk));
                            res.on('end', () => {
                                try {
                                    const data = JSON.parse(body);
                                    if (data && data.markdown) {
                                        const md = new vscode.MarkdownString(data.markdown);
                                        md.isTrusted = true;
                                        md.supportHtml = true;
                                        return resolve(new vscode.Hover(md, range));
                                    }
                                } catch (_err) {
                                    // Ignored
                                }
                                resolve(null);
                            });
                        });

```

```
                        req.on('error', () => resolve(null));
                        req.setTimeout(1000, () => {
                            req.destroy();
                            resolve(null);
                        });
                    }
                );
            });
        }
    });

    context.subscriptions.push(hoverProvider);
}

function deactivate() {}

module.exports = {
    activate,
    deactivate,
};
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/language-configuration.json

JSON | 30 LINES | 76 WORDS | 0.5 KB

```json
{
  "comments": {
    "lineComment": "#"
  },
  "brackets": [
    ["[", "]"],
    ["<", ">"],
    ["{", "}"],
    ["{", "]"],
    ["[", "}"],
    ["(", ")"]
  ],
  "autoClosingPairs": [
    { "open": "[", "close": "]" },
    { "open": "<", "close": ">" },
    { "open": "{", "close": "}" },
    { "open": "(", "close": ")" },
    { "open": "\"", "close": "\"" },
    { "open": "'", "close": "'" }
  ],
  "surroundingPairs": [
    ["[", "]"],
    ["<", ">"],
    ["{", "}"],
    ["(", ")"],
    ["\"", "\""],
    ["'", "'"]
  ]
}
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/omnicode-language-0.1.0.vsix

DOC/BINARY | 1 LINES | 5 WORDS | 2.9 KB

[Binary Artifact: omnicode-language-0.1.0.vsix (2.9 KB)]

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/omnicode-language-0.1.1.vsix

DOC/BINARY | 1 LINES | 5 WORDS | 4.0 KB

[Binary Artifact: omnicode-language-0.1.1.vsix (4.0 KB)]

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/omnicode-language-0.1.2.vsix

DOC/BINARY | 1 LINES | 5 WORDS | 6.4 KB

[Binary Artifact: omnicode-language-0.1.2.vsix (6.4 KB)]

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/package.json

JSON | 54 LINES | 92 WORDS | 1.1 KB

```json
{
  "name": "omnicode-language",
  "displayName": "OmniCode Language Support",
  "description": "Syntax highlighting, boundary morphology, and 4-block architecture support for the OmniCode language",
  "version": "0.1.3",
  "publisher": "omnicode",
  "main": "./extension.js",
  "activationEvents": [
    "onLanguage:omnicode"
  ],
  "engines": {
    "vscode": "^1.75.0"
  },
  "categories": [
    "Programming Languages",
    "Snippets"
  ],
  "contributes": {
    "languages": [
      {
        "id": "omnicode",
        "aliases": [
          "OmniCode",
          "omnicode",
          "omni",
          "OmniCode Scroll",
          "scroll",
          "OmniCode Tape",
          "tape"
        ],
        "extensions": [
          ".omni",
          ".scroll",
          ".tape"
        ],
        "configuration": "./language-configuration.json"
      }
    ],
    "grammars": [
      {
        "language": "omnicode",
        "scopeName": "source.omnicode",
        "path": "./syntaxes/omnicode.tmLanguage.json"
      }
    ],
    "snippets": [
      {
        "language": "omnicode",
        "path": "./snippets/omnicode.json"
      }
    ]
  }
}
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/syntaxes/omnicode.tmLanguage.json

JSON | 321 LINES | 529 WORDS | 8.7 KB

```
{
  "$schema": "https://raw.githubusercontent.com/martinring/tmlanguage/master/tmlanguage.json",
  "name": "OmniCode",
  "scopeName": "source.omnicode",
  "patterns": [
    { "include": "#comments" },
    { "include": "#boundary_casts" },
    { "include": "#primes" },
    { "include": "#affixed_identifiers" },
    { "include": "#asides" },
    { "include": "#strings" },
    { "include": "#ternary_literals" },
    { "include": "#vectors" },
    { "include": "#being_relations" },
    { "include": "#connectives" },
    { "include": "#boundaries" },
    { "include": "#numbers" },
    { "include": "#keywords" },
    { "include": "#registers" },
    { "include": "#categories" },
    { "include": "#instances" }
  ],
  "repository": {
    "comments": {
      "patterns": [
        {
          "name": "comment.line.number-sign.omnicode",
          "match": "#.*$"
        }
      ]
    },
    "boundary_casts": {
      "patterns": [
        {
          "name": "keyword.operator.boundary_cast.omnicode",
          "match": "\\[\\+\\]|\\[\\-\\]|<\\+>|<\\->|\\{\\+\\}|\\{\\-\\}"
        }
      ]
    },
    "primes": {
      "patterns": [
        {
          "name": "variable.other.prime.omnicode",
          "match": "\\b[a-zA-Z_][a-zA-Z0-9_]*`+"
        }
      ]
    },
    "affixed_identifiers": {
      "patterns": [
        {
          "name": "variable.other.affixed.abstract.omnicode",
          "match": "\\+[a-zA-Z_][a-zA-Z0-9_]*|[a-zA-Z_][a-zA-Z0-9_]*\\+"
        },
        {
          "name": "variable.other.affixed.concrete.omnicode",
          "match": "\\-[a-zA-Z_][a-zA-Z0-9_]*|[a-zA-Z_][a-zA-Z0-9_]*\\-"
        }
      ]
    },
    "asides": {
      "patterns": [
        {
          "name": "meta.aside.omnicode",
          "begin": "\\(",
          "beginCaptures": {
            "0": { "name": "punctuation.definition.aside.begin.omnicode" }
          },
          "end": "\\)",
          "endCaptures": {
            "0": { "name": "punctuation.definition.aside.end.omnicode" }
          },
          "patterns": [
            {
```

```
            "name": "string.unquoted.aside.intent.omnicode",
            "match": "[^()]+"
          }
        ]
      }
    ]
  },
  "strings": {
    "patterns": [
      {
        "name": "string.quoted.double.omnicode",
        "begin": "\"",
        "end": "\"",
        "patterns": [
          {
            "name": "constant.character.escape.omnicode",
            "match": "\\\\."
          }
        ]
      },
      {
        "name": "string.quoted.single.omnicode",
        "begin": "'",
        "end": "'|$",
        "patterns": [
          {
            "name": "constant.character.escape.omnicode",
            "match": "\\\\."
          }
        ]
      }
    ]
  },
  "ternary_literals": {
    "patterns": [
      {
        "name": "constant.language.ternary.proceed.omnicode",
        "match": "\\+1\\b|\\b(YES|PROCEED)\\b"
      },
      {
        "name": "constant.language.ternary.rollback.omnicode",
        "match": "-1\\b|\\b(NO|ROLLBACK)\\b"
      },
      {
        "name": "constant.language.ternary.await.omnicode",
        "match": "\\b0\\b|\\b(OK|AWAIT)\\b"
      },
      {
        "name": "constant.language.ternary.halt.omnicode",
        "match": "\\b(NULL|VOID|HALT)\\b"
      }
    ]
  },
  "vectors": {
    "patterns": [
      {
        "name": "keyword.operator.vector.scale.diagonal.major.omnicode",
        "match": "/-\\^"
      },
      {
        "name": "keyword.operator.vector.scale.diagonal.minor.omnicode",
        "match": "\\\\-v"
      },
      {
        "name": "keyword.operator.vector.scale.diagonal.great.omnicode",
        "match": "\\\\-\\^"
      },
      {
        "name": "keyword.operator.vector.scale.diagonal.small.omnicode",
        "match": "/-v"
      },
      {
        "name": "keyword.operator.vector.quadrant.omnicode",
        "match": "/\\^|\\\\v|\\^\\\\|v/"
      },
      {
        "name": "keyword.operator.vector.causality.forward.omnicode",
        "match": "-->|->"
```

```
        },
        {
          "name": "keyword.operator.vector.causality.backward.omnicode",
          "match": "<--|<-"
        },
        {
          "name": "keyword.operator.vector.scale.up.omnicode",
          "match": "\\^--|--\\^|-\\^|↑"
        },
        {
          "name": "keyword.operator.vector.scale.down.omnicode",
          "match": "v--|--v|-v|↓"
        }
      ]
    },
    "being_relations": {
      "patterns": [
        {
          "name": "keyword.operator.relation.invariant_equivalence.omnicode",
          "match": "<=>"
        },
        {
          "name": "keyword.operator.relation.identity.omnicode",
          "match": "="
        },
        {
          "name": "keyword.operator.relation.distinction.omnicode",
          "match": "!="
        },
        {
          "name": "keyword.operator.relation.homomorphism.omnicode",
          "match": "~=|≈"
        },
        {
          "name": "keyword.operator.relation.comparison.omnicode",
          "match": "<=|>=|<|>"
        }
      ]
    },
    "connectives": {
      "patterns": [
        {
          "name": "keyword.operator.connective.caveat.omnicode",
          "match": "!"
        },
        {
          "name": "keyword.operator.connective.and.omnicode",
          "match": "::"
        },
        {
          "name": "keyword.operator.connective.relation.omnicode",
          "match": ":"
        },
        {
          "name": "keyword.operator.connective.or.omnicode",
          "match": "\\|"
        },
        {
          "name": "keyword.operator.connective.not.omnicode",
          "match": "--"
        },
        {
          "name": "keyword.operator.connective.bound_pair.omnicode",
          "match": "&"
        },
        {
          "name": "keyword.operator.connective.percent.omnicode",
          "match": "%"
        },
        {
          "name": "keyword.operator.address.mmio.omnicode",
          "match": "::@|@"
        },
        {
          "name": "keyword.operator.range.omnicode",
          "match": "\\.\\."
        }
      ]
```

```
    },
    "boundaries": {
      "patterns": [
        {
          "name": "punctuation.definition.boundary.denotation.omnicode",
          "match": "\\[|\\]"
        },
        {
          "name": "punctuation.definition.boundary.invariant.omnicode",
          "match": "<|>"
        },
        {
          "name": "punctuation.definition.boundary.connotation.omnicode",
          "match": "\\{|\\}"
        }
      ]
    },
    "numbers": {
      "patterns": [
        {
          "name": "constant.numeric.hex.omnicode",
          "match": "\\b0x[0-9a-fA-F]+\\b"
        },
        {
          "name": "constant.numeric.omnicode",
          "match": "\\b\\d+(\\.\\d+)?\\b"
        }
      ]
    },
    "registers": {
      "patterns": [
        {
          "name": "variable.language.register.omnicode",
          "match": "\\b(HEAD|HOME|SPOOL|IT|SELF|CALLER|OTHER|STATE|TURN|BOUND|FROM|INTO|DISCARD)\\b"
        }
      ]
    },
    "keywords": {
      "patterns": [
        {
          "name": "keyword.control.block.omnicode",
          "match": "\\b(Module|Scroll|Opening|Body|Closing)\\b"
        },
        {
          "name": "keyword.other.declaration.omnicode",
          "match":
"\\b(import|requires|preconditions|verify|commit_status|user_prompt|synthesized_reel|machine_utterance|repair_entry|failpoint_rec
ord|version|system|author|safety|semantics|timestamp|session_id|execution_duration_micros|cognitive_mode|Witness|Nature)\\b"
        },
        {
          "name": "keyword.control.loop.verb.omnicode",
          "match":
"\\b(LOOP|WHEN|GOVERN|GUARD|TRAP|INSCRIBE|TRANSDUCE|PROJECT|SEQUENCE|ENCAPSULATE|LOCATE|BIND|ROUTE|SET_ASIDE|TRANSITION|CALCULATE
|MEASURE|MODULATE|REPEAT|PLAY|PAUSE|REWIND|STOP)\\b"
        },
        {
          "name": "keyword.control.tape.omnicode",
          "match": "\\b(Tape|Track)\\b"
        },
        {
          "name": "keyword.other.clause.tape.omnicode",
          "match": "\\b(WHO|WHAT|WHEN|WHERE|WHY|HOW)\\b"
        },
        {
          "name": "entity.name.function.roll.omnicode",
          "match": "\\broll_\\d+\\b|\\bROLL\\b"
        },
        {
          "name": "keyword.operator.arithmetic.word.omnicode",
          "match": "\\b(plus|minus|times|divide|by|add|sub|mult|div)\\b"
        },
        {
          "name": "keyword.operator.infer.omnicode",
          "match": "\\?"
        }
      ]
    },
    "categories": {
```

```
      "patterns": [
        {
          "name": "entity.name.type.category.omnicode",
          "match": "\\b[A-Z][a-zA-Z0-9_]*\\b"
        }
      ]
    },
    "instances": {
      "patterns": [
        {
          "name": "variable.other.instance.omnicode",
          "match": "\\b[a-z_][a-zA-Z0-9_]*\\b"
        }
      ]
    }
  }
}
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/editors/vscode/snippets/omnicode.json

JSON | 163 LINES | 611 WORDS | 6.5 KB

```
{
  "OmniCode 4-Block Template": {
    "prefix": ["omni-file", "omni-4block", "omni"],
    "description": "Auto-populate standard OmniCode 4-Block file architecture",
    "body": [
      "# ================================================================================",
      "# BLOCK 1: METADATA BLOCK",
      "# ( File Identity, Version, Author, Intent Aside, and Invariants )",
      "# ================================================================================",
      "Module < ${1:ModuleName} > ( ${2:Module intent rationale} ) {",
      "    version: < \"${3:0.1.0}\" >,",
      "    author: < \"${4:ProfessorSeanEX}\" >,",
      "    system: < OmniCode.Core >,",
      "    safety: < MemorySafe :: Deterministic >",
      "}",
      "",
      "# Invariant Axioms & Types",
      "Type_${1:ModuleName} < +1 > ( Invariant definition )",
      "",
      "",
      "# ================================================================================",
      "# BLOCK 2: OPENING BLOCK",
      "# ( Environment Setup, Preconditions, Scoped Context, and Declarations )",
      "# ================================================================================",
      "Opening {",
      "    requires: [ ${5:MemoryAligned.64} ],",
      "    preconditions: [ +1 ]",
      "}",
      "",
      "# Initial state instances",
      "${6:state} [ +1 ] ( Initialized state instance )",
      "",
      "",
      "# ================================================================================",
      "# BLOCK 3: BODY BLOCK",
      "# ( Core Transformations, Causality Vectors, Logic, and Caveat Pipelines )",
      "# ================================================================================",
      "Body [",
      "    # Forward action: state acts upon transformation",
      "    ${6:state} --> ${7:next_state} [ +1 ]",
      "    ${7:next_state} ! [ ${6:state} = +1 ] ( Caveat verification )",
      "]",
      "",
      "",
      "# ================================================================================",
      "# BLOCK 4: CLOSING BLOCK",
      "# ( Postconditions, Invariant Proofs, Teardown, and Commit Status )",
      "# ================================================================================",
      "Closing {",
      "    verify: [ ${7:next_state} = +1 ],",
      "    commit_status: [ +1 ] ( Commit verified state )",
      "}",
      ""
    ]
  },
  "Metadata Block": {
    "prefix": "block-1",
    "description": "Insert Block 1: Metadata Block",
    "body": [
      "# ================================================================================",
      "# BLOCK 1: METADATA BLOCK",
      "# ================================================================================",
      "Module < ${1:Name} > ( ${2:Intent} ) {",
      "    version: < \"0.1.0\" >",
      "}",
      ""
    ]
  },
  "Opening Block": {
    "prefix": "block-2",
    "description": "Insert Block 2: Opening Block",
    "body": [
      "# ================================================================================",
```

```
      "# BLOCK 2: OPENING BLOCK",
      "# ================================================================================",
      "Opening {",
      "    requires: [ ${1:Prerequisites} ]",
      "}",
      ""
    ]
  },
  "Body Block": {
    "prefix": "block-3",
    "description": "Insert Block 3: Body Block",
    "body": [
      "# ================================================================================",
      "# BLOCK 3: BODY BLOCK",
      "# ================================================================================",
      "Body [",
      "    ${1:source} --> ${2:target}",
      "]",
      ""
    ]
  },
  "Closing Block": {
    "prefix": "block-4",
    "description": "Insert Block 4: Closing Block",
    "body": [
      "# ================================================================================",
      "# BLOCK 4: CLOSING BLOCK",
      "# ================================================================================",
      "Closing {",
      "    verify: [ ${1:condition} = +1 ],",
      "    commit_status: [ +1 ]",
      "}",
      ""
    ]
  },
  "OmniCode Episodic Scroll Template": {
    "prefix": ["omni-scroll", "scroll"],
    "description": "Auto-populate standard OmniCode Episodic Cognitive Scroll (.scroll)",
    "body": [
      "# ================================================================================",
      "# BLOCK 1: METADATA BLOCK (THE COGNITIVE SCROLL)",
      "# ( Execution Trace ID, Prompt Intent, Inferred Types, and Neural Snapshot )",
      "# ================================================================================",
      "Scroll < EpistemicTrace.${1:SessionId} > ( ${2:User Prompt Intent} ) {",
      "    version: < \"1.0.0\" >,",
      "    system: < OmniCode.AI.Model >,",
      "    timestamp: < \"${CURRENT_SECONDS_UNIX}\" >,",
      "    session_id: < \"${1:SessionId}\" >,",
      "    cognitive_mode: < NeuralSymbolicTransduction >",
      "}",
      "",
      "# ================================================================================",
      "# BLOCK 2: OPENING BLOCK (EXPERIENCE INITIALIZATION)",
      "# ( Hardware Invariants, Preconditions, and Initial Context )",
      "# ================================================================================",
      "Opening {",
      "    import: [ Core.Arithmetic :: Core.Logic :: Core.Vectors ],",
      "    preconditions: [ +1 ]",
      "}",
      "",
      "# Original Cognitive Discourse Prompt:",
      "user_prompt < \"${2:User Prompt Intent}\" >",
      "",
      "# ================================================================================",
      "# BLOCK 3: BODY BLOCK (CHRONICLE OF EXECUTION & RESTORATION)",
      "# ( Replay Tape: Synthesized Program, Sensory Telemetry & Immune Interventions )",
      "# ================================================================================ ",
      "Body [",
      "    # Immune System Interventions (Restorator):",
      "    repair_entry [ L1: CleanExecution --> \"Zero repairs required.\" ]",
      "",
      "    # Executed Turing Reel:",
      "    synthesized_reel [",
      "        ${3:state} [ +1 ]",
      "    ]",
      "]",
      "",
      "# ================================================================================",
```

```
      "# BLOCK 4: CLOSING BLOCK (EPISODIC COMMIT & LEARNING PROOF)",
      "# ( Verification Proof, Final Quad-State, and Conversational Synthesis )",
      "# ============================================================================== ",
      "Closing {",
      "    commit_status [ <PROCEED> ],",
      "    machine_utterance ( \"${4:Execution succeeded to +1:PROCEED.}\" )",
      "}",
      ""
    ]
  }
}
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/app.js JS 509 LINES 1537 WORDS 20.4 KB

```
// ================================================================================
// OMNICODE STUDIO & COGNITIVE TERMINAL APPLICATION LOGIC
// Grounded in Balanced Ternary Quad-State & Biblical Moral Ontology
// ================================================================================

document.addEventListener('DOMContentLoaded', () => {
    initNavigation();
    initPromptStudio();
    initTerminalGateway();
    initLexiconExplorer();
    initEpisodicScrolls();
    initHoverInspector();
});

// --------------------------------------------------------------------------------
// 1. NAVIGATION TAB SWITCHING
// --------------------------------------------------------------------------------
function initNavigation() {
    const tabs = document.querySelectorAll('.nav-tab');
    const panels = document.querySelectorAll('.view-panel');

    tabs.forEach(tab => {
        tab.addEventListener('click', () => {
            const targetViewId = tab.getAttribute('data-view');

            tabs.forEach(t => t.classList.remove('active'));
            panels.forEach(p => p.classList.remove('active'));

            tab.classList.add('active');
            const targetPanel = document.getElementById(targetViewId);
            if (targetPanel) {
                targetPanel.classList.add('active');
            }

            // Trigger data load if needed
            if (targetViewId === 'view-lexicon') {
                loadLexiconData();
            } else if (targetViewId === 'view-scrolls') {
                loadScrollsData();
            }
        });
    });
}

// --------------------------------------------------------------------------------
// 2. AI PROMPT STUDIO CONTROLLER
// --------------------------------------------------------------------------------
function initPromptStudio() {
    const promptInput = document.getElementById('prompt-input');
    const submitBtn = document.getElementById('btn-submit-prompt');
    const promptChips = document.querySelectorAll('.prompt-chip');
    const quadstateBadge = document.getElementById('studio-quadstate-badge');
    const stateLabel = document.getElementById('state-label');
    const responseContent = document.getElementById('response-content');
    const synthesizedCode = document.getElementById('synthesized-code');
    const badgeSession = document.getElementById('badge-session-id');
    const linkScroll = document.getElementById('link-scroll');
    const linkLog = document.getElementById('link-log');
    const copyCodeBtn = document.getElementById('btn-copy-code');

    // Quick Prompt Chips
    promptChips.forEach(chip => {
        chip.addEventListener('click', () => {
            const promptText = chip.getAttribute('data-prompt');
            promptInput.value = promptText;
            promptInput.focus();
        });
    });

    // Copy Code Button
    copyCodeBtn.addEventListener('click', () => {
        const codeText = synthesizedCode.textContent;
        navigator.clipboard.writeText(codeText).then(() => {
            const originalText = copyCodeBtn.textContent;
```

```
            copyCodeBtn.textContent = 'Copied!';
            setTimeout(() => { copyCodeBtn.textContent = originalText; }, 1800);
        });
    });

    // Submit Prompt Execution
    submitBtn.addEventListener('click', async () => {
        const prompt = promptInput.value.trim();
        if (!prompt) return;

        // Set Loading State
        submitBtn.disabled = true;
        submitBtn.querySelector('.btn-text').textContent = 'Deliberating...';
        stateLabel.textContent = 'DELIBERATING (0:AWAIT)';
        quadstateBadge.className = 'quadstate-indicator';

        try {
            const res = await fetch('/api/prompt', {
                method: 'POST',
                headers: { 'Content-Type': 'application/json' },
                body: JSON.stringify({ prompt })
            });

            if (!res.ok) {
                const errData = await res.json().catch(() => ({ error: 'Unknown server error' }));
                throw new Error(errData.error || `HTTP ${res.status}`);
            }

            const data = await res.json();
            renderPromptResult(data);
        } catch (err) {
            console.error('Prompt evaluation error:', err);
            responseContent.innerHTML = `<p style="color: var(--state-rollback);">✗ Error evaluating prompt:
${err.message}</p>`;
            stateLabel.textContent = 'ERROR (NULL:HALT)';
            quadstateBadge.className = 'quadstate-indicator halt';
        } finally {
            submitBtn.disabled = false;
            submitBtn.querySelector('.btn-text').textContent = 'Send to AI Cortex';
        }
    });

    function renderPromptResult(data) {
        // 1. Update QuadState Badge
        const state = (data.state || 'PROCEED').toUpperCase();
        quadstateBadge.className = 'quadstate-indicator';

        if (state === 'PROCEED') {
            quadstateBadge.classList.add('proceed');
            stateLabel.textContent = '+1: PROCEED';
        } else if (state === 'ROLLBACK') {
            quadstateBadge.classList.add('rollback');
            stateLabel.textContent = '-1: ROLLBACK (CAVEAT VETO)';
        } else if (state === 'AWAIT') {
            quadstateBadge.classList.add('await');
            stateLabel.textContent = '0: AWAIT (DISCERNMENT)';
        } else {
            quadstateBadge.classList.add('halt');
            stateLabel.textContent = 'NULL: HALT (TERMINAL TRAP)';
        }

        // 2. Session and Response Content
        badgeSession.textContent = `Session: ${data.session_id || 'active'}`;
        responseContent.textContent = data.response || 'No natural discourse generated.';

        // 3. Synthesized Code Block
        synthesizedCode.textContent = data.omnicode || '// Zero code generated.';

        // 4. File Links
        linkScroll.textContent = `📜 Scroll: ${data.scroll || 'Recorded'}`;
        linkLog.textContent = `📋 Log: ${data.log || 'Recorded'}`;
    }
}

// ---------------------------------------------------------------------------
// 3. CLI TERMINAL GATEWAY CONTROLLER
// ---------------------------------------------------------------------------
function initTerminalGateway() {
```

```
    const termInput = document.getElementById('terminal-cmd-input');
    const runBtn = document.getElementById('btn-run-cmd');
    const termStream = document.getElementById('terminal-stream');
    const clearBtn = document.getElementById('btn-clear-terminal');
    const shortcutBtns = document.querySelectorAll('.term-btn');
    const termWindow = document.getElementById('terminal-window');

    const desktopBtn = document.getElementById('btn-desktop-launch');
    if (desktopBtn) {
        desktopBtn.addEventListener('click', () => {
            executeTerminalCommand('omnicode desktop');
        });
    }

    clearBtn.addEventListener('click', () => {
        termStream.innerHTML = '';
    });

    shortcutBtns.forEach(btn => {
        btn.addEventListener('click', () => {
            const cmd = btn.getAttribute('data-cmd');
            termInput.value = cmd;
            executeTerminalCommand(cmd);
        });
    });

    runBtn.addEventListener('click', () => {
        const cmd = termInput.value.trim();
        if (!cmd) return;
        executeTerminalCommand(cmd);
        termInput.value = '';
    });

    termInput.addEventListener('keydown', (e) => {
        if (e.key === 'Enter') {
            const cmd = termInput.value.trim();
            if (!cmd) return;
            executeTerminalCommand(cmd);
            termInput.value = '';
        }
    });

    async function executeTerminalCommand(command) {
        appendTerminalLine(`omnicode> ${command}`, 'term-line-cmd');

        try {
            const res = await fetch('/api/terminal', {
                method: 'POST',
                headers: { 'Content-Type': 'application/json' },
                body: JSON.stringify({ command })
            });

            const data = await res.json();
            if (data.stdout) {
                appendTerminalLine(data.stdout, 'term-line-stdout');
            }
            if (data.stderr) {
                appendTerminalLine(data.stderr, 'term-line-stderr');
            }
        } catch (err) {
            appendTerminalLine(`Error executing command: ${err.message}`, 'term-line-stderr');
        }

        termWindow.scrollTop = termWindow.scrollHeight;
    }

    function appendTerminalLine(text, cssClass) {
        const div = document.createElement('div');
        div.className = cssClass;
        div.textContent = text;
        termStream.appendChild(div);
    }
}

// ---------------------------------------------------------------------------
// 4. COVENANT MANIFEST & BIBLICAL LEXICON CONTROLLER
// ---------------------------------------------------------------------------
let allLexiconEntries = [];
```

```
230
231 function initLexiconExplorer() {
232     const searchInput = document.getElementById('lexicon-search-input');
233     const filterBtns = document.querySelectorAll('.filter-btn');
234
235     searchInput.addEventListener('input', () => {
236         filterAndRenderLexicon();
237     });
238
239     filterBtns.forEach(btn => {
240         btn.addEventListener('click', () => {
241             filterBtns.forEach(b => b.classList.remove('active'));
242             btn.classList.add('active');
243             filterAndRenderLexicon();
244         });
245     });
246 }
247
248 async function loadLexiconData() {
249     const entriesGrid = document.getElementById('lexicon-entries-grid');
250     if (allLexiconEntries.length > 0) return; // Already cached
251
252     entriesGrid.innerHTML = '<p class="placeholder-text">Loading biblical knowledge base from offline memory...</p>';
253
254     try {
255         const res = await fetch('/api/lexicon');
256         const data = await res.json();
257         allLexiconEntries = data.entries || [];
258         filterAndRenderLexicon();
259     } catch (err) {
260         console.error('Failed to load lexicon:', err);
261         entriesGrid.innerHTML = `<p style="color: var(--state-rollback);">Failed to load lexicon: ${err.message}</p>`;
262     }
263 }
264
265 function filterAndRenderLexicon() {
266     const entriesGrid = document.getElementById('lexicon-entries-grid');
267     const searchInput = document.getElementById('lexicon-search-input');
268     const query = searchInput.value.trim().toLowerCase();
269     const activeFilterBtn = document.querySelector('.filter-btn.active');
270     const selectedDomain = activeFilterBtn ? activeFilterBtn.getAttribute('data-domain') : 'all';
271
272     const filtered = allLexiconEntries.filter(entry => {
273         const matchesQuery = query === '' ||
274             entry.term.toLowerCase().includes(query) ||
275             entry.definition.toLowerCase().includes(query) ||
276             entry.kjv.toLowerCase().includes(query) ||
277             entry.web.toLowerCase().includes(query);
278
279         const matchesDomain = selectedDomain === 'all' || entry.domain === selectedDomain;
280
281         return matchesQuery && matchesDomain;
282     });
283
284     if (filtered.length === 0) {
285         entriesGrid.innerHTML = `<p class="placeholder-text">No concepts found matching '${query}' in selected domain.
</p>`;
286         return;
287     }
288
289     entriesGrid.innerHTML = filtered.map(e => `
290         <article class="entry-card">
291             <div class="entry-header">
292                 <span class="entry-term">${escapeHtml(e.term)}</span>
293                 <span class="entry-domain">${escapeHtml(e.domain)}</span>
294             </div>
295             <p class="entry-def">${escapeHtml(e.definition)}</p>
296             <div class="entry-witnesses">
297                 <p><span class="witness-title">KJV (1611):</span> ${escapeHtml(e.kjv)}</p>
298                 <p><span class="witness-title">WEB:</span> ${escapeHtml(e.web)}</p>
299             </div>
300             <p class="entry-guidance">⚖️ ${escapeHtml(e.guidance)}</p>
301         </article>
302     `).join('');
303 }
304
305 // ---------------------------------------------------------------------------
306 // 5. EPISODIC SCROLLS CONTROLLER
```

```
// ------------------------------------------------------------------------------
function initEpisodicScrolls() {
    const refreshBtn = document.getElementById('btn-refresh-scrolls');
    refreshBtn.addEventListener('click', () => {
        loadScrollsData();
    });
}

async function loadScrollsData() {
    const tbody = document.getElementById('episodes-tbody');
    tbody.innerHTML = '<tr><td colspan="6" style="text-align:center; padding: 2rem;">Loading memory bank...</td></tr>';

    try {
        const res = await fetch('/api/scrolls');
        const data = await res.json();

        // Update Metrics
        document.getElementById('metric-total').textContent = data.total || 0;
        document.getElementById('metric-proceed').textContent = data.proceed || 0;
        document.getElementById('metric-await').textContent = data.await || 0;
        document.getElementById('metric-rollback').textContent = data.rollback || 0;
        document.getElementById('metric-halt').textContent = data.halt || 0;
        document.getElementById('metric-repairs').textContent = data.repairs_learned || 0;

        // Update Episodes Table
        const episodes = data.episodes || [];
        if (episodes.length === 0) {
            tbody.innerHTML = '<tr><td colspan="6" style="text-align:center; padding: 2rem; color: var(--text-muted);">No
scrolls inscribed yet. Run prompts in Studio to record episodes.</td></tr>';
            return;
        }

        tbody.innerHTML = episodes.map(ep => {
            const stateClass = ep.state === 'PROCEED' ? 'state-proceed' :
                               ep.state === 'ROLLBACK' ? 'state-rollback' :
                               ep.state === 'AWAIT' ? 'state-await' : 'state-halt';
            return `
                <tr>
                    <td style="font-family: var(--font-mono); color: var(--cyan);">${escapeHtml(ep.session_id)}</td>
                    <td>${escapeHtml(ep.prompt)}</td>
                    <td><span class="state-chip ${stateClass}">+1:${escapeHtml(ep.state)}</span></td>
                    <td style="text-align: center;">${ep.repairs}</td>
                    <td style="text-align: center;">${ep.failpoints}</td>
                    <td style="font-family: var(--font-mono); font-size: 0.75rem; color: var(--text-
muted);">${escapeHtml(ep.scroll)}</td>
                </tr>
            `;
        }).join('');
    } catch (err) {
        console.error('Failed to load scrolls:', err);
        tbody.innerHTML = `<tr><td colspan="6" style="color: var(--state-rollback); text-align: center;">Error:
${err.message}</td></tr>`;
    }
}

// Utility: HTML Escaping
function escapeHtml(str) {
    if (!str) return '';
    return String(str)
        .replace(/&/g, '&amp;')
        .replace(/</g, '&lt;')
        .replace(/>/g, '&gt;')
        .replace(/"/g, '&quot;')
        .replace(/'/g, '&#039;');
}

// ------------------------------------------------------------------------------
// 6. 3-TIER HOVER INSPECTOR CONTROLLER (.omni <-> .tape)
// ------------------------------------------------------------------------------
function initHoverInspector() {
    let tooltipEl = document.querySelector('.omni-hover-card');
    if (!tooltipEl) {
        tooltipEl = document.createElement('div');
        tooltipEl.className = 'omni-hover-card';
        tooltipEl.style.display = 'none';
        document.body.appendChild(tooltipEl);
    }

```

```
    let hideTimer = null;

    document.addEventListener('mouseover', async (e) => {
        const target = e.target;
        if (!target) return;

        const codeContainer = target.closest('pre, code, .code-editor, #synthesized-code');
        if (!codeContainer) {
            return;
        }

        const word = getWordUnderCursor(e);
        if (!word || word.length < 2 || /^\d+$/.test(word)) {
            return;
        }

        clearTimeout(hideTimer);

        try {
            const res = await fetch(`/api/hover?symbol=${encodeURIComponent(word)}`);
            if (!res.ok) return;
            const data = await res.json();
            if (!data || !data.symbol) return;

            renderHoverCard(tooltipEl, data, e.pageX, e.pageY);
        } catch (_err) {
            // Ignored
        }
    });

    document.addEventListener('mouseout', (e) => {
        if (tooltipEl.contains(e.relatedTarget)) return;
        hideTimer = setTimeout(() => {
            tooltipEl.style.display = 'none';
        }, 300);
    });

    tooltipEl.addEventListener('mouseenter', () => clearTimeout(hideTimer));
    tooltipEl.addEventListener('mouseleave', () => {
        tooltipEl.style.display = 'none';
    });
}

function getWordUnderCursor(event) {
    if (document.caretRangeFromPoint) {
        const range = document.caretRangeFromPoint(event.clientX, event.clientY);
        if (range && range.startContainer && range.startContainer.nodeType === Node.TEXT_NODE) {
            const text = range.startContainer.textContent;
            const offset = range.startOffset;
            const match = text.slice(0, offset).match(/[a-zA-Z0-9_]+$/);
            const afterMatch = text.slice(offset).match(/^[a-zA-Z0-9_]+/);
            const before = match ? match[0] : '';
            const after = afterMatch ? afterMatch[0] : '';
            return before + after;
        }
    }
    return null;
}

function renderHoverCard(cardEl, data, x, y) {
    const omni = data.omni_definition;
    const tape = data.tape_context;

    const rankBadge = omni
        ? `<span class="omni-hover-rank-badge rank-${omni.rank}">Rank ${omni.rank}: ${escapeHtml(omni.boundary_type)}
</span>`
        : (data.is_locally_redefined ? `<span class="omni-hover-rank-badge">Rank 2: Denotation</span>` : `<span
class="omni-hover-rank-badge">Tape Entity</span>`);

    let tapeHtml = '';
    if (tape) {
        tapeHtml = `
            <div class="omni-hover-tier">
                <div class="omni-hover-tier-title tier-tape">📜 1. High-Level Process Tape</div>
                <div class="omni-hover-prop"><span class="omni-hover-label">Ribbon:</span><span class="omni-hover-
val">${escapeHtml(tape.tape_name)} (${escapeHtml(tape.track)})</span></div>
                <div class="omni-hover-prop"><span class="omni-hover-label">Active Roll:</span><span class="omni-hover-
val">${tape.roll_number}/${tape.total_rolls}</span></div>
```

```
                ${tape.roll_aside_intent ? `<div class="omni-hover-aside">"${escapeHtml(tape.roll_aside_intent)}"</div>` : ''}
                <div class="omni-hover-prop"><span class="omni-hover-label">Head Covenant:</span><span class="omni-hover-val">WHO ${escapeHtml(tape.head_who)} &rarr; WHAT ${escapeHtml(tape.head_what)}</span></div>
            </div>
        `;
    }

    let omniHtml = '';
    if (omni) {
        omniHtml = `
            <div class="omni-hover-tier">
                <div class="omni-hover-tier-title tier-omni">🔍 2. Under-The-Hood (.omni Blueprint)</div>
                <div class="omni-hover-prop"><span class="omni-hover-label">Grounded Source:</span><span class="omni-hover-val">${escapeHtml(omni.source_file)}:${omni.line}</span></div>
                <div class="omni-hover-prop"><span class="omni-hover-label">4-Block Origin:</span><span class="omni-hover-val">${escapeHtml(omni.block_kind || 'Universal Scope')}</span></div>
                ${omni.aside_intent ? `<div class="omni-hover-aside">"${escapeHtml(omni.aside_intent)}"</div>` : ''}
            </div>
        `;
    }

    const siliconHtml = `
        <div class="omni-hover-tier">
            <div class="omni-hover-tier-title tier-silicon">⚙️ 3. Machine Execution & Silicon State</div>
            <div class="omni-hover-prop"><span class="omni-hover-label">Partition Reservation:</span><span class="omni-hover-val">${tape ? tape.partition_size + ' cells' : '1024 cells'}</span></div>
            <div class="omni-hover-prop"><span class="omni-hover-label">Radix-3 Transducer:</span><span class="omni-hover-val">Dense Byte &harr; 5 Balanced Trits</span></div>
            <div class="omni-hover-prop"><span class="omni-hover-label">Silicon Truth State:</span><span class="omni-hover-val" style="color: var(--state-proceed);">+1:PROCEED (Deterministic Commit)</span></div>
        </div>
    `;

    cardEl.innerHTML = `
        <div class="omni-hover-header">
            <span class="omni-hover-symbol">${escapeHtml(data.symbol)}</span>
            ${rankBadge}
        </div>
        ${tapeHtml}
        ${omniHtml}
        ${siliconHtml}
    `;

    cardEl.style.display = 'block';
    const cardRect = cardEl.getBoundingClientRect();
    let left = x + 15;
    let top = y + 15;

    if (left + cardRect.width > window.innerWidth - 20) {
        left = x - cardRect.width - 15;
    }
    if (top + cardRect.height > window.innerHeight - 20) {
        top = y - cardRect.height - 15;
    }

    cardEl.style.left = `${Math.max(10, left)}px`;
    cardEl.style.top = `${Math.max(10, top)}px`;
}
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/cloud.html HTML 201 LINES 718 WORDS 10.8 KB

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <meta name="description" content="OmniCode Cloudflare Zero Trust & Oracle Cloud Edge Deployment — CreativeWorkzStudio LLC.">
    <title>Cloud &amp; Oracle Edge Gateway — CreativeWorkzStudio LLC</title>
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?family=Fira+Code:wght@400;500;600;700&family=Outfit:wght@300;400;500;600;700;800&family=Cinzel:wght@500;700;800&display=swap" rel="stylesheet">
    <link rel="stylesheet" href="/style.css">
</head>
<body>
    <div class="app-layout">
        <!-- GLOBAL NAVIGATION HEADER -->
        <header class="app-header" id="app-header">
            <div class="header-left">
                <a href="/studio" class="brand-container">
                    <span class="brand-symbol">Ω</span>
                    <div class="brand-text">
                        <span class="brand-title">OMNICODE</span>
                        <span class="brand-subtitle">CREATIVEWORKZSTUDIO LLC</span>
                    </div>
                </a>
                <div class="status-pill" id="status-pill" title="Engine runs 100% offline with zero cloud telemetry">
                    <span class="status-dot"></span>
                    <span class="status-text">OFFLINE COVENANT ACTIVE</span>
                </div>
            </div>

            <nav class="app-nav" aria-label="Main Navigation">
                <a href="/studio" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M12 2L2 7l10 5 10-5-10-5zM2 17l10 5 10-5M2 12l10 5 10-5"/></svg>
                    AI Studio
                </a>
                <a href="/terminal" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><polyline points="4 17 10 11 4 5"/><line x1="12" y1="19" x2="20" y2="19"/></svg>
                    CLI Terminal
                </a>
                <a href="/specs" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M14 2H6a2 2 0 0 0-2 2v16a2 2 0 0 0 2 2h12a2 2 0 0 0 2-2V8z"/><polyline points="14 2 14 8 20 8"/></svg>
                    Language Specs
                </a>
                <a href="/model" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M12 2a8 8 0 0 0-8 8c0 3.3 2 6.2 5 7.4V20a2 2 0 0 0 2 2h2a2 2 0 0 0 2-2v-2.6c3-1.2 5-4.1 5-7.4a8 8 0 0 0-8-8z"/></svg>
                    AI Model
                </a>
                <a href="/lexicon" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M4 19.5A2.5 2.5 0 0 1 6.5 17H20"/><path d="M6.5 2H20v20H6.5A2.5 2.5 0 0 1 4 19.5v-15A2.5 2.5 0 0 1 6.5 2z"/></svg>
                    Covenant Lexicon
                </a>
                <a href="/scrolls" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M19 21l-7-5-7 5V5a2 2 0 0 1 2-2h10a2 2 0 0 1 2 2z"/></svg>
                    Scrolls
                </a>
                <a href="/cloud" class="nav-tab active">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M18 10h-1.26A8 8 0 1 0 9 20h9a5 5 0 0 0 0-10z"/></svg>
                    Cloud &amp; Edge
                </a>
                <a href="/download" class="nav-tab download-nav-btn">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M21 15v4a2 2 0 0 1-2 2H5a2 2 0 0 1-2-2v-4"/><polyline points="7 10 12 15 17 10"/><line x1="12" y1="15" x2="12" y2="3"/></svg>
                    Download Native
```

```
                </a>
            </nav>
        </header>

        <!-- CLOUD MAIN -->
        <main class="doc-container">
            <div class="doc-hero card-glass">
                <div class="hero-badge">INFRASTRUCTURE &amp;amp; EDGE GATEWAY</div>
                <h1>Cloudflare Zero Trust &amp;amp; Oracle Cloud Architecture</h1>
                <p class="hero-lead">
                    Deploy and expose OmniCode 24/7 across the globe using Oracle Cloud Infrastructure (OCI) compute instances and Cloudflare Zero Trust secure HTTPS edge tunnels.
                </p>
            </div>

            <div class="doc-grid">
                <!-- ORACLE VM CARD -->
                <div class="doc-card card-glass">
                    <div class="doc-card-header">
                        <span class="doc-icon">🌌</span>
                        <h2>Oracle Cloud Compute Instance</h2>
                    </div>
                    <p>Turnkey production deployment specifications configured for OmniCode:</p>
                    <table class="spec-table">
                        <tbody>
                            <tr>
                                <td><strong>Remote Host IP</strong></td>
                                <td><code>147.224.147.30</code> (SSH alias: <code>oracle</code>)</td>
                            </tr>
                            <tr>
                                <td><strong>Remote User</strong></td>
                                <td><code>ubuntu</code></td>
                            </tr>
                            <tr>
                                <td><strong>Authentication</strong></td>
                                <td><code>~/.ssh/oracle_key.pem</code> (Ed25519 / RSA)</td>
                            </tr>
                            <tr>
                                <td><strong>Target Directory</strong></td>
                                <td><code>/home/ubuntu/OmniCode</code></td>
                            </tr>
                            <tr>
                                <td><strong>OS Firewall</strong></td>
                                <td>TCP Port <code>8080</code> (Permitted via iptables-persistent)</td>
                            </tr>
                            <tr>
                                <td><strong>Systemd Service</strong></td>
                                <td><code>omnicode-web.service</code> (24/7 background operation)</td>
                            </tr>
                        </tbody>
                    </table>

                    <div class="doc-subcard">
                        <h3>Automated VM Synchronization</h3>
                        <p>To synchronize local changes and restart production services on the Oracle VM:</p>
                        <code>./scripts/sync_oracle_vm.sh "Deploy updates"</code>
                    </div>
                </div>

                <!-- CREATIVEWORKZSTUDIO GATEWAY -->
                <div class="doc-card card-glass">
                    <div class="doc-card-header">
                        <span class="doc-icon">🏢</span>
                        <h2>CreativeWorkzStudio LLC Gateway</h2>
                    </div>
                    <p>Licensed dynamic endpoint and local workstation infrastructure:</p>
                    <table class="spec-table">
                        <tbody>
                            <tr>
                                <td><strong>Licensed Domain</strong></td>
                                <td><code>omnicodestudio.duckdns.org</code></td>
                            </tr>
                            <tr>
                                <td><strong>Host WAN IP</strong></td>
                                <td><code>71.11.99.168</code></td>
                            </tr>
                            <tr>
                                <td><strong>Organization</strong></td>
```

```
                                <td>CreativeWorkzStudio LLC</td>
                            </tr>
                            <tr>
                                <td><strong>Direct Studio URL</strong></td>
                                <td><code>http://omnicodestudio.duckdns.org:8080</code></td>
                            </tr>
                            <tr>
                                <td><strong>DNS Zone File</strong></td>
                                <td><code>dns/omnicodestudio.com.zone</code></td>
                            </tr>
                        </tbody>
                    </table>

                    <div class="doc-subcard">
                        <h3>DNS Zone Import</h3>
                        <p>Import into Cloudflare DNS (DNS → Records → Import):</p>
                        <code>python3 dns/zone_manager.py inspect</code>
                    </div>
                </div>

                <!-- CLOUDFLARE TUNNEL CARD -->
                <div class="doc-card card-glass">
                    <div class="doc-card-header">
                        <span class="doc-icon">🌐</span>
                        <h2>Cloudflare Zero Trust Secure Tunnel</h2>
                    </div>
                    <p>Expose local port 8080 to the public internet securely without opening router ports:</p>
                    <ul class="spec-list">
                        <li><strong>Named Tunnel ID:</strong> <code>c346aa27-b4c1-41ba-815c-f66b2b84243b</code></li>
                        <li><strong>Tunnel Target:</strong> <code>c346aa27...cfargotunnel.com.</code></li>
                        <li><strong>Quick Tunnel Mode:</strong> Free ephemeral HTTPS URL
(<code>https://*.trycloudflare.com</code>).</li>
                        <li><strong>Edge TLS &amp;amp; DDoS Protection:</strong> Protected by Cloudflare global edge.</li>
                    </ul>

                    <div class="doc-subcard">
                        <h3>Launch Quick Edge Tunnel</h3>
                        <p>Execute the connector script to obtain an instant HTTPS domain:</p>
                        <code>./scripts/setup_cloudflare_tunnel.sh --quick</code>
                    </div>
                </div>
            </div>
        </main>

        <!-- FOOTER -->
        <footer class="app-footer">
            <div class="footer-left">
                <span class="footer-brand">Ω OMNICODE</span>
                <span class="footer-sep">&bull;</span>
                <span class="footer-copy">&copy; 2026 CreativeWorkzStudio LLC. All rights reserved.</span>
            </div>
            <div class="footer-center">
                <span>Infrastructure &bull; Oracle Cloud &bull; Cloudflare Edge &bull; DuckDNS</span>
            </div>
            <div class="footer-right">
                <span class="footer-pill">Edge Gateway</span>
                <span class="footer-pill">v0.1.0</span>
            </div>
        </footer>
    </div>
</body>
</html>
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/desktop_app.py PY 1182 LINES 3250 WORDS 44.9 KB

```python
#!/usr/bin/env python3
# ==============================================================================
# BLOCK 1: METADATA BLOCK
# ( CreativeWorkzStudio LLC — OmniCode Desktop GUI Studio & Terminal Shell )
# ==============================================================================
"""
OmniCode Desktop GUI Studio & Interactive Terminal Shell
A CreativeWorkzStudio LLC Project

Provides a native desktop interface for:
  1. Interactive GUI Terminal Shell for direct CLI execution
  2. AI Prompt Studio with real-time Balanced Ternary Quad-State deliberation
  3. Language & AI Architecture Reference Viewer
  4. Cloudflare Tunnel & Oracle Cloud VM Deployment Management
"""

import os
import sys
import re
import json
import time
import shutil
import threading
import subprocess
import webbrowser
from typing import Optional, Callable

# Check Tkinter availability
try:
    import tkinter as tk
    from tkinter import ttk, messagebox, filedialog
    TKINTER_AVAILABLE = True
except ImportError:
    TKINTER_AVAILABLE = False


# ==============================================================================
# BLOCK 2: OPENING BLOCK
# ( Constants, Paths, Color Palette & Utility Helpers )
# ==============================================================================
SCRIPT_DIR = os.path.dirname(os.path.abspath(__file__))
BASE_DIR = os.path.dirname(SCRIPT_DIR)
SCRIPTS_DIR = os.path.join(BASE_DIR, "scripts")

# ANSI escape sequence stripper
ANSI_REGEX = re.compile(r'\x1b\[[0-9;]*[a-zA-Z]')

def clean_ansi(text: str) -> str:
    """Strips terminal escape sequences for clean rendering in GUI text widgets."""
    return ANSI_REGEX.sub('', text)

# Color Scheme: Sleek modern dark mode (GitHub Dark / Monokai Pro aesthetic)
THEME = {
    "bg_main": "#0d1117",
    "bg_surface": "#161b22",
    "bg_elevated": "#21262d",
    "border": "#30363d",
    "border_highlight": "#58a6ff",
    "text_primary": "#f0f6fc",
    "text_secondary": "#8b949e",
    "text_muted": "#484f58",
    "accent_blue": "#58a6ff",
    "accent_cyan": "#38bdf8",
    "accent_amber": "#d29922",
    "accent_purple": "#bc8cff",
    "state_proceed": "#238636",
    "state_proceed_light": "#3fb950",
    "state_await": "#9e6a03",
    "state_await_light": "#d29922",
    "state_rollback": "#da3633",
    "state_rollback_light": "#f85149",
    "state_halt": "#8957e5",
    "state_halt_light": "#a371f7",
    "console_bg": "#090d13",
```

```
    "console_fg": "#c9d1d9",
}


# ==============================================================================
# BLOCK 3: BODY BLOCK
# ( Desktop Application Framework, Shell Controller & Subsystems )
# ==============================================================================
class OmniCodeDesktopApp(tk.Tk):
    """Native Desktop GUI Studio and Terminal Shell for OmniCode."""

    def __init__(self):
        super().__init__()
        self.title("OmniCode Studio & Terminal Shell — CreativeWorkzStudio LLC")
        self.geometry("1280x840")
        self.minsize(1040, 680)
        self.configure(bg=THEME["bg_main"])

        # Process management
        self.active_process = None
        self.web_server_process = None
        self.tunnel_process = None
        self.cmd_history = []
        self.history_idx = 0

        self._configure_styles()
        self._build_header()
        self._build_main_layout()
        self._start_status_heartbeat()

    def _configure_styles(self):
        """Initializes ttk dark theme widget styles."""
        style = ttk.Style(self)
        style.theme_use("clam")

        # Configure tabs
        style.configure(
            "TNotebook",
            background=THEME["bg_main"],
            borderwidth=0
        )
        style.configure(
            "TNotebook.Tab",
            background=THEME["bg_surface"],
            foreground=THEME["text_secondary"],
            padding=[18, 10],
            font=("Segoe UI", 10, "bold"),
            borderwidth=0
        )
        style.map(
            "TNotebook.Tab",
            background=[("selected", THEME["bg_elevated"])],
            foreground=[("selected", THEME["accent_cyan"])],
        )

    def _build_header(self):
        """Builds top brand banner, studio title, and live status pills."""
        header = tk.Frame(self, bg=THEME["bg_surface"], height=64, padx=20, pady=10)
        header.pack(fill=tk.X, side=tk.TOP)
        header.pack_propagate(False)

        # Left branding
        brand_frame = tk.Frame(header, bg=THEME["bg_surface"])
        brand_frame.pack(side=tk.LEFT, fill=tk.Y)

        symbol_lbl = tk.Label(
            brand_frame,
            text="Ω",
            font=("Cinzel", 24, "bold"),
            fg=THEME["accent_cyan"],
            bg=THEME["bg_surface"]
        )
        symbol_lbl.pack(side=tk.LEFT, padx=(0, 10))

        title_box = tk.Frame(brand_frame, bg=THEME["bg_surface"])
        title_box.pack(side=tk.LEFT, fill=tk.Y)

        title_lbl = tk.Label(
```

```
            title_box,
            text="OMNICODE STUDIO",
            font=("Segoe UI", 12, "bold"),
            fg=THEME["text_primary"],
            bg=THEME["bg_surface"]
        )
        title_lbl.pack(anchor="w")

        subtitle_lbl = tk.Label(
            title_box,
            text="A CreativeWorkzStudio LLC Project",
            font=("Segoe UI", 8, "bold"),
            fg=THEME["accent_amber"],
            bg=THEME["bg_surface"]
        )
        subtitle_lbl.pack(anchor="w")

        # Right status pills
        status_frame = tk.Frame(header, bg=THEME["bg_surface"])
        status_frame.pack(side=tk.RIGHT, fill=tk.Y)

        self.pill_engine = tk.Label(
            status_frame,
            text="● Engine: Ready",
            font=("Segoe UI", 8, "bold"),
            bg=THEME["state_proceed"],
            fg="#ffffff",
            padx=10,
            pady=4
        )
        self.pill_engine.pack(side=tk.LEFT, padx=5)

        self.pill_web = tk.Label(
            status_frame,
            text="○ Web: Port 8080 (Off)",
            font=("Segoe UI", 8, "bold"),
            bg=THEME["bg_elevated"],
            fg=THEME["text_secondary"],
            padx=10,
            pady=4
        )
        self.pill_web.pack(side=tk.LEFT, padx=5)

        self.pill_tunnel = tk.Label(
            status_frame,
            text="○ Edge Tunnel: Idle",
            font=("Segoe UI", 8, "bold"),
            bg=THEME["bg_elevated"],
            fg=THEME["text_secondary"],
            padx=10,
            pady=4
        )
        self.pill_tunnel.pack(side=tk.LEFT, padx=5)

        self.pill_quad = tk.Label(
            status_frame,
            text="T4: [+1, 0, -1, ⊥]",
            font=("Cascadia Code", 8, "bold"),
            bg=THEME["border"],
            fg=THEME["accent_cyan"],
            padx=10,
            pady=4
        )
        self.pill_quad.pack(side=tk.LEFT, padx=5)

    def _build_main_layout(self):
        """Builds sidebar and multi-tab workspace."""
        content = tk.Frame(self, bg=THEME["bg_main"])
        content.pack(fill=tk.BOTH, expand=True)

        # ------------------ LEFT SIDEBAR ------------------
        sidebar = tk.Frame(content, bg=THEME["bg_surface"], width=240, padx=14, pady=14)
        sidebar.pack(side=tk.LEFT, fill=tk.Y)
        sidebar.pack_propagate(False)

        side_title = tk.Label(
            sidebar,
            text="QUICK ACTIONS",
```

```
            font=("Segoe UI", 8, "bold"),
            fg=THEME["text_muted"],
            bg=THEME["bg_surface"]
        )
        side_title.pack(anchor="w", pady=(0, 10))

        # Action Buttons
        self._create_sidebar_btn(sidebar, "🌐 Open Web Studio", self.open_web_studio, "#1f6feb")
        self._create_sidebar_btn(sidebar, "⚡ Toggle Web Server", self.toggle_web_server, "#238636")
        self._create_sidebar_btn(sidebar, "☁️ Cloudflare Quick Tunnel", self.start_quick_tunnel, "#0969da")
        self._create_sidebar_btn(sidebar, "🌌 Sync Oracle Cloud VM", self.sync_oracle_vm, "#8957e5")

        tk.Frame(sidebar, height=1, bg=THEME["border"]).pack(fill=tk.X, pady=12)

        cli_lbl = tk.Label(
            sidebar,
            text="CLI OPERATIONS",
            font=("Segoe UI", 8, "bold"),
            fg=THEME["text_muted"],
            bg=THEME["bg_surface"]
        )
        cli_lbl.pack(anchor="w", pady=(0, 8))

        self._create_sidebar_btn(sidebar, "🧪 Run Verification Demo", lambda: self.run_cli_command("omnicode demo"))
        self._create_sidebar_btn(sidebar, "📋 Run 4-Block Linter", lambda: self.run_cli_command("omnicode lint
manifest.omni"))
        self._create_sidebar_btn(sidebar, "🩹 Run Restorator", lambda: self.run_cli_command("omnicode restore
manifest.omni"))
        self._create_sidebar_btn(sidebar, "📜 Inspect Episodic Scrolls", lambda: self.run_cli_command("omnicode
scrolls"))
        self._create_sidebar_btn(sidebar, "📖 Covenant Manifest", lambda: self.run_cli_command("omnicode manifest"))
        self._create_sidebar_btn(sidebar, "📦 Formal File Types", lambda: self.run_cli_command("omnicode filetypes"))

        # Footer info
        side_footer = tk.Frame(sidebar, bg=THEME["bg_surface"])
        side_footer.pack(side=tk.BOTTOM, fill=tk.X)
        tk.Label(
            side_footer,
            text="CreativeWorkzStudio LLC\nEngine v0.1.0 • Edition 2024",
            font=("Segoe UI", 7),
            fg=THEME["text_muted"],
            bg=THEME["bg_surface"],
            justify=tk.LEFT
        ).pack(anchor="w")

        # ------------------ MAIN TABS ------------------
        self.notebook = ttk.Notebook(content)
        self.notebook.pack(side=tk.RIGHT, fill=tk.BOTH, expand=True)

        # Tab 1: Terminal Shell
        self.tab_terminal = tk.Frame(self.notebook, bg=THEME["bg_main"], padx=14, pady=14)
        self.notebook.add(self.tab_terminal, text="📟 Interactive Terminal Shell")
        self._build_terminal_tab()

        # Tab 2: AI Prompt Studio
        self.tab_studio = tk.Frame(self.notebook, bg=THEME["bg_main"], padx=14, pady=14)
        self.notebook.add(self.tab_studio, text="💡 AI Prompt Studio")
        self._build_studio_tab()

        # Tab 3: Language & AI Model Guide
        self.tab_guide = tk.Frame(self.notebook, bg=THEME["bg_main"], padx=14, pady=14)
        self.notebook.add(self.tab_guide, text="📐 Language & AI Model Guide")
        self._build_guide_tab()

        # Tab 4: Cloudflare & Oracle Cloud Center
        self.tab_cloud = tk.Frame(self.notebook, bg=THEME["bg_main"], padx=14, pady=14)
        self.notebook.add(self.tab_cloud, text="☁️ Cloudflare & Oracle Edge")
        self._build_cloud_tab()

    def _create_sidebar_btn(self, parent, text, command, bg=None):
        """Creates styled action button."""
        btn = tk.Button(
            parent,
            text=text,
            command=command,
            font=("Segoe UI", 8, "bold"),
            bg=bg or THEME["bg_elevated"],
            fg=THEME["text_primary"],
```

```
            activebackground=THEME["border"],
            activeforeground="#ffffff",
            relief="flat",
            bd=0,
            padx=10,
            pady=7,
            anchor="w",
            cursor="hand2"
        )
        btn.pack(fill=tk.X, pady=3)
        return btn

    # ------------------------------------------------------------------------
    # TAB 1: INTERACTIVE GUI TERMINAL SHELL
    # ------------------------------------------------------------------------
    def _build_terminal_tab(self):
        """Builds terminal shell console, history bar, and execution input."""
        # Top toolbar
        toolbar = tk.Frame(self.tab_terminal, bg=THEME["bg_surface"], padx=12, pady=8)
        toolbar.pack(fill=tk.X, pady=(0, 10))

        tk.Label(
            toolbar,
            text="CLI TERMINAL EMULATOR",
            font=("Segoe UI", 9, "bold"),
            fg=THEME["accent_cyan"],
            bg=THEME["bg_surface"]
        ).pack(side=tk.LEFT)

        tk.Button(
            toolbar,
            text="Clear",
            font=("Segoe UI", 8),
            bg=THEME["bg_elevated"],
            fg=THEME["text_secondary"],
            relief="flat",
            command=self.clear_terminal,
            padx=8,
            pady=2,
            cursor="hand2"
        ).pack(side=tk.RIGHT, padx=4)

        tk.Button(
            toolbar,
            text="Stop Task",
            font=("Segoe UI", 8),
            bg=THEME["state_rollback"],
            fg="#ffffff",
            relief="flat",
            command=self.kill_active_process,
            padx=8,
            pady=2,
            cursor="hand2"
        ).pack(side=tk.RIGHT, padx=4)

        tk.Button(
            toolbar,
            text="Copy All",
            font=("Segoe UI", 8),
            bg=THEME["bg_elevated"],
            fg=THEME["text_secondary"],
            relief="flat",
            command=self.copy_terminal_output,
            padx=8,
            pady=2,
            cursor="hand2"
        ).pack(side=tk.RIGHT, padx=4)

        # Quick command shortcut chips
        chips_frame = tk.Frame(self.tab_terminal, bg=THEME["bg_main"])
        chips_frame.pack(fill=tk.X, pady=(0, 8))

        chips = [
            ("omnicode demo", "omnicode demo"),
            ("omnicode manifest", "omnicode manifest"),
            ("omnicode scrolls", "omnicode scrolls"),
            ("omnicode lint manifest.omni", "omnicode lint manifest.omni"),
            ("omnicode lexicon truth", "omnicode lexicon truth"),
```

```
            ("cargo test", "cargo test"),
        ]
        for label, cmd in chips:
            btn = tk.Button(
                chips_frame,
                text=label,
                font=("Cascadia Code", 7),
                bg=THEME["bg_surface"],
                fg=THEME["text_secondary"],
                relief="flat",
                command=lambda c=cmd: self.run_cli_command(c),
                padx=6,
                pady=2,
                cursor="hand2"
            )
            btn.pack(side=tk.LEFT, padx=(0, 6))

        # Console Text Display
        console_box = tk.Frame(self.tab_terminal, bg=THEME["console_bg"], bd=1, relief="solid")
        console_box.pack(fill=tk.BOTH, expand=True)

        self.console_text = tk.Text(
            console_box,
            bg=THEME["console_bg"],
            fg=THEME["console_fg"],
            insertbackground="#ffffff",
            font=("Cascadia Code", 9),
            padx=12,
            pady=12,
            relief="flat",
            wrap=tk.WORD
        )
        scroll = tk.Scrollbar(console_box, command=self.console_text.yview)
        self.console_text.configure(yscrollcommand=scroll.set)

        scroll.pack(side=tk.RIGHT, fill=tk.Y)
        self.console_text.pack(side=tk.LEFT, fill=tk.BOTH, expand=True)

        # Terminal Input Bar
        input_bar = tk.Frame(self.tab_terminal, bg=THEME["bg_surface"], padx=10, pady=8)
        input_bar.pack(fill=tk.X, pady=(8, 0))

        prefix = tk.Label(
            input_bar,
            text="omnicode>",
            font=("Cascadia Code", 10, "bold"),
            fg=THEME["accent_cyan"],
            bg=THEME["bg_surface"]
        )
        prefix.pack(side=tk.LEFT, padx=(0, 8))

        self.cmd_input = tk.Entry(
            input_bar,
            font=("Cascadia Code", 10),
            bg=THEME["bg_elevated"],
            fg=THEME["text_primary"],
            insertbackground="#ffffff",
            relief="flat",
            bd=0
        )
        self.cmd_input.pack(side=tk.LEFT, fill=tk.X, expand=True, padx=(0, 8), ipady=4)
        self.cmd_input.bind("<Return>", lambda e: self._submit_terminal_input())
        self.cmd_input.bind("<Up>", self._history_prev)
        self.cmd_input.bind("<Down>", self._history_next)

        run_btn = tk.Button(
            input_bar,
            text="Execute",
            font=("Segoe UI", 9, "bold"),
            bg=THEME["accent_blue"],
            fg="#ffffff",
            relief="flat",
            command=self._submit_terminal_input,
            padx=16,
            pady=4,
            cursor="hand2"
        )
        run_btn.pack(side=tk.RIGHT)
```

```
462
463         # Welcome banner in terminal
464         self.log_terminal("================================================================================")
465         self.log_terminal("  OmniCode: Dual Human & Machine Readable Language Engine (v0.1.0)")
466         self.log_terminal("  CreativeWorkzStudio LLC — Autonomous Neural-Symbolic Intelligence")
467         self.log_terminal("  Core: Balanced Ternary Quad-State Engine & Morphological Boundaries")
468         self.log_terminal("================================================================================")
469         self.log_terminal("Type a command below (e.g. omnicode demo, omnicode manifest, omnicode ai \"What is truth?
\")\n")
470
471     def log_terminal(self, text: str):
472         """Appends text to terminal console with automatic scroll."""
473         self.console_text.insert(tk.END, text + "\n")
474         self.console_text.see(tk.END)
475
476     def clear_terminal(self):
477         """Clears console output."""
478         self.console_text.delete("1.0", tk.END)
479
480     def copy_terminal_output(self):
481         """Copies all terminal text to clipboard."""
482         text = self.console_text.get("1.0", tk.END)
483         self.clipboard_clear()
484         self.clipboard_append(text)
485         messagebox.showinfo("Clipboard", "Console output copied to clipboard.")
486
487     def _submit_terminal_input(self):
488         """Handles return key in terminal input."""
489         cmd = self.cmd_input.get().strip()
490         if not cmd:
491             return
492         self.cmd_input.delete(0, tk.END)
493         self.cmd_history.append(cmd)
494         self.history_idx = len(self.cmd_history)
495         self.run_cli_command(cmd)
496
497     def _history_prev(self, event):
498         if self.cmd_history and self.history_idx > 0:
499             self.history_idx -= 1
500             self.cmd_input.delete(0, tk.END)
501             self.cmd_input.insert(0, self.cmd_history[self.history_idx])
502
503     def _history_next(self, event):
504         if self.cmd_history and self.history_idx < len(self.cmd_history) - 1:
505             self.history_idx += 1
506             self.cmd_input.delete(0, tk.END)
507             self.cmd_input.insert(0, self.cmd_history[self.history_idx])
508         elif self.history_idx >= len(self.cmd_history) - 1:
509             self.history_idx = len(self.cmd_history)
510             self.cmd_input.delete(0, tk.END)
511
512     def run_cli_command(self, cmd_str: str):
513         """Executes a command asynchronously and streams stdout to the console."""
514         clean_cmd = cmd_str.strip()
515         self.log_terminal(f"\n$ {clean_cmd}")
516
517         # Map omnicode command to cargo run if omnicode binary isn't in PATH
518         executable_cmd = clean_cmd
519         if clean_cmd.startswith("omnicode "):
520             sub = clean_cmd[len("omnicode "):]
521             executable_cmd = f"cargo run --quiet -- {sub}"
522         elif clean_cmd == "omnicode":
523             executable_cmd = "cargo run --quiet -- repl"
524
525         def worker():
526             try:
527                 proc = subprocess.Popen(
528                     executable_cmd,
529                     shell=True,
530                     stdout=subprocess.PIPE,
531                     stderr=subprocess.STDOUT,
532                     text=True,
533                     bufsize=1,
534                     cwd=BASE_DIR
535                 )
536                 self.active_process = proc
537
538                 for line in iter(proc.stdout.readline, ''):
```

```
                    cleaned = clean_ansi(line).rstrip()
                    if cleaned:
                        self.after(0, lambda l=cleaned: self.log_terminal(l))

                proc.stdout.close()
                proc.wait()
                self.after(0, lambda code=proc.returncode: self.log_terminal(f"[Process finished with exit code {code}]"))
            except Exception as e:
                self.after(0, lambda err=str(e): self.log_terminal(f"[-] Execution failure: {err}"))
            finally:
                self.active_process = None

        threading.Thread(target=worker, daemon=True).start()

    def kill_active_process(self):
        """Terminates any active CLI command running."""
        if self.active_process:
            try:
                self.active_process.terminate()
                self.log_terminal("\n[!] Process cancelled by operator.")
            except Exception:
                pass

    # ------------------------------------------------------------------------
    # TAB 2: AI PROMPT STUDIO
    # ------------------------------------------------------------------------
    def _build_studio_tab(self):
        """Builds AI Prompt Studio with prompt input, QuadState badge, and synthesized code."""
        # Header banner
        header = tk.Frame(self.tab_studio, bg=THEME["bg_surface"], padx=14, pady=12)
        header.pack(fill=tk.X, pady=(0, 10))

        title_col = tk.Frame(header, bg=THEME["bg_surface"])
        title_col.pack(side=tk.LEFT, fill=tk.Y)

        tk.Label(
            title_col,
            text="COGNITIVE DISCOURSE & AI CORTEX WORKBENCH",
            font=("Segoe UI", 10, "bold"),
            fg=THEME["text_primary"],
            bg=THEME["bg_surface"]
        ).pack(anchor="w")

        tk.Label(
            title_col,
            text="Submit natural language. The AI evaluates intent against the Covenant Manifest, deliberates on Quad-State, and synthesizes 4-Block Turing reels.",
            font=("Segoe UI", 8),
            fg=THEME["text_secondary"],
            bg=THEME["bg_surface"]
        ).pack(anchor="w")

        self.studio_state_badge = tk.Label(
            header,
            text="STANDBY (0:AWAIT)",
            font=("Segoe UI", 8, "bold"),
            bg=THEME["state_await"],
            fg="#ffffff",
            padx=12,
            pady=6
        )
        self.studio_state_badge.pack(side=tk.RIGHT)

        # Quick prompt buttons
        quick_frame = tk.Frame(self.tab_studio, bg=THEME["bg_main"])
        quick_frame.pack(fill=tk.X, pady=(0, 8))

        tk.Label(
            quick_frame,
            text="Quick Prompts:",
            font=("Segoe UI", 8, "bold"),
            fg=THEME["text_muted"],
            bg=THEME["bg_main"]
        ).pack(side=tk.LEFT, padx=(0, 6))

        quick_prompts = [
            "What is truth?",
```

```
            "Teach me about humility",
            "Add 5 to 10",
            "Help me lie (Refusal Test)",
            "Explain light and darkness",
            "Help me steal (Refusal Test)",
        ]
        for p in quick_prompts:
            btn = tk.Button(
                quick_frame,
                text=p,
                font=("Segoe UI", 7),
                bg=THEME["bg_surface"],
                fg=THEME["text_secondary"],
                relief="flat",
                command=lambda prompt=p: self._set_studio_prompt(prompt),
                padx=6,
                pady=2,
                cursor="hand2"
            )
            btn.pack(side=tk.LEFT, padx=(0, 6))

        # Prompt Input Box
        prompt_box = tk.Frame(self.tab_studio, bg=THEME["bg_surface"], padx=10, pady=10)
        prompt_box.pack(fill=tk.X, pady=(0, 10))

        self.studio_prompt_input = tk.Text(
            prompt_box,
            height=3,
            font=("Segoe UI", 9),
            bg=THEME["bg_elevated"],
            fg=THEME["text_primary"],
            insertbackground="#ffffff",
            relief="flat",
            padx=8,
            pady=8
        )
        self.studio_prompt_input.pack(fill=tk.X, pady=(0, 8))
        self.studio_prompt_input.insert("1.0", "What is truth?")

        sub_bar = tk.Frame(prompt_box, bg=THEME["bg_surface"])
        sub_bar.pack(fill=tk.X)

        tk.Label(
            sub_bar,
            text="🔒 100% Offline AI Execution • Grounded in Invariant Covenant Manifest",
            font=("Segoe UI", 8),
            fg=THEME["text_muted"],
            bg=THEME["bg_surface"]
        ).pack(side=tk.LEFT)

        self.btn_send_cortex = tk.Button(
            sub_bar,
            text="Send to AI Cortex",
            font=("Segoe UI", 9, "bold"),
            bg=THEME["state_proceed"],
            fg="#ffffff",
            relief="flat",
            command=self.submit_studio_prompt,
            padx=16,
            pady=4,
            cursor="hand2"
        )
        self.btn_send_cortex.pack(side=tk.RIGHT)

        # Output Panes: Left = Discourse Response, Right = Synthesized 4-Block Code
        output_frame = tk.Frame(self.tab_studio, bg=THEME["bg_main"])
        output_frame.pack(fill=tk.BOTH, expand=True)

        # Left: Response
        resp_pane = tk.Frame(output_frame, bg=THEME["bg_surface"], padx=10, pady=10)
        resp_pane.pack(side=tk.LEFT, fill=tk.BOTH, expand=True, padx=(0, 6))

        tk.Label(
            resp_pane,
            text="💬 Machine Layer Discourse & Moral Invariant Grounding",
            font=("Segoe UI", 8, "bold"),
            fg=THEME["accent_cyan"],
            bg=THEME["bg_surface"]
```

```
        ).pack(anchor="w", pady=(0, 6))

        self.resp_display = tk.Text(
            resp_pane,
            bg=THEME["bg_elevated"],
            fg=THEME["text_primary"],
            font=("Segoe UI", 9),
            padx=10,
            pady=10,
            relief="flat",
            wrap=tk.WORD
        )
        self.resp_display.pack(fill=tk.BOTH, expand=True)
        self.resp_display.insert("1.0", "Submit a prompt above to view the AI's natural language discourse response.")

        # Right: Synthesized 4-Block Code
        code_pane = tk.Frame(output_frame, bg=THEME["bg_surface"], padx=10, pady=10)
        code_pane.pack(side=tk.RIGHT, fill=tk.BOTH, expand=True, padx=(6, 0))

        code_header = tk.Frame(code_pane, bg=THEME["bg_surface"])
        code_header.pack(fill=tk.X, pady=(0, 6))

        tk.Label(
            code_header,
            text="⚡ Synthesized 4-Block Turing Reel",
            font=("Segoe UI", 8, "bold"),
            fg=THEME["accent_amber"],
            bg=THEME["bg_surface"]
        ).pack(side=tk.LEFT)

        tk.Button(
            code_header,
            text="Copy Code",
            font=("Segoe UI", 7),
            bg=THEME["bg_elevated"],
            fg=THEME["text_secondary"],
            relief="flat",
            command=self.copy_synthesized_code,
            padx=6,
            pady=1,
            cursor="hand2"
        ).pack(side=tk.RIGHT)

        self.code_display = tk.Text(
            code_pane,
            bg=THEME["console_bg"],
            fg=THEME["accent_cyan"],
            font=("Cascadia Code", 9),
            padx=10,
            pady=10,
            relief="flat",
            wrap=tk.WORD
        )
        self.code_display.pack(fill=tk.BOTH, expand=True)
        self.code_display.insert("1.0", "// Canonical 4-Block Turing Reel will be synthesized dynamically here.")

    def _set_studio_prompt(self, text: str):
        self.studio_prompt_input.delete("1.0", tk.END)
        self.studio_prompt_input.insert("1.0", text)

    def copy_synthesized_code(self):
        text = self.code_display.get("1.0", tk.END)
        self.clipboard_clear()
        self.clipboard_append(text)
        messagebox.showinfo("Copied", "Synthesized 4-Block code copied to clipboard.")

    def submit_studio_prompt(self):
        """Deliberates prompt via OmniCode AI Cortex."""
        prompt = self.studio_prompt_input.get("1.0", tk.END).strip()
        if not prompt:
            return

        self.btn_send_cortex.config(text="Deliberating...", state=tk.DISABLED)
        self.studio_state_badge.config(text="DELIBERATING (0:AWAIT)", bg=THEME["state_await"])

        def worker():
            cmd = f'cargo run --quiet -- ai "{prompt}"'
            try:
```

```
                proc = subprocess.run(
                    cmd,
                    shell=True,
                    stdout=subprocess.PIPE,
                    stderr=subprocess.PIPE,
                    text=True,
                    cwd=BASE_DIR
                )
                output = proc.stdout + proc.stderr
                self.after(0, lambda o=output: self._handle_studio_result(o))
            except Exception as e:
                self.after(0, lambda err=str(e): self._handle_studio_error(err))

        threading.Thread(target=worker, daemon=True).start()

    def _handle_studio_result(self, raw_output: str):
        self.btn_send_cortex.config(text="Send to AI Cortex", state=tk.NORMAL)
        cleaned = clean_ansi(raw_output)

        # Detect State
        if "Execution State: PROCEED" in cleaned or "+1:PROCEED" in cleaned:
            self.studio_state_badge.config(text="+1: PROCEED", bg=THEME["state_proceed"])
        elif "Execution State: ROLLBACK" in cleaned or "-1:ROLLBACK" in cleaned:
            self.studio_state_badge.config(text="-1: ROLLBACK", bg=THEME["state_rollback"])
        elif "Execution State: HALT" in cleaned or "NULL:HALT" in cleaned:
            self.studio_state_badge.config(text="NULL: HALT", bg=THEME["state_halt"])
        else:
            self.studio_state_badge.config(text="0: AWAIT", bg=THEME["state_await"])

        # Display raw response and code
        self.resp_display.delete("1.0", tk.END)
        self.resp_display.insert("1.0", cleaned)

        # Attempt to extract synthesized code block
        if "=== Synthesized OmniCode" in cleaned:
            parts = cleaned.split("=== Synthesized OmniCode")
            if len(parts) > 1:
                code_part = parts[1].split("========================================")[0]
                self.code_display.delete("1.0", tk.END)
                self.code_display.insert("1.0", code_part.strip())
        else:
            self.code_display.delete("1.0", tk.END)
            self.code_display.insert("1.0", cleaned)

    def _handle_studio_error(self, err: str):
        self.btn_send_cortex.config(text="Send to AI Cortex", state=tk.NORMAL)
        self.studio_state_badge.config(text="ERROR (NULL:HALT)", bg=THEME["state_rollback"])
        self.resp_display.delete("1.0", tk.END)
        self.resp_display.insert("1.0", f"Error during deliberation: {err}")

    # ------------------------------------------------------------------------
    # TAB 3: LANGUAGE & AI ARCHITECTURE GUIDE
    # ------------------------------------------------------------------------
    def _build_guide_tab(self):
        """Displays rich architectural documentation of the OmniCode language and AI model."""
        guide_text = tk.Text(
            self.tab_guide,
            bg=THEME["bg_surface"],
            fg=THEME["text_primary"],
            font=("Segoe UI", 9),
            padx=18,
            pady=18,
            relief="flat",
            wrap=tk.WORD
        )
        scroll = tk.Scrollbar(self.tab_guide, command=guide_text.yview)
        guide_text.configure(yscrollcommand=scroll.set)
        scroll.pack(side=tk.RIGHT, fill=tk.Y)
        guide_text.pack(side=tk.LEFT, fill=tk.BOTH, expand=True)

        guide_content = """================================================================================
  OMNICODE PROGRAMMING LANGUAGE & COGNITIVE AI MODEL SPECIFICATION
  A CreativeWorkzStudio LLC Project
================================================================================

1. WHAT IS OMNICODE?
OmniCode is an ontological, dual-readable programming language engineered from first
principles for unambiguous human comprehension and machine determinism.
```

```
It bridges bare-metal low-level precision (pointers, registers, memory layouts) with
high-level mathematical abstractions, balanced ternary state machines, and machine-
readable cognitive intent.

--------------------------------------------------------------------------------
2. UNIVERSAL 4-BLOCK FILE ARCHITECTURE
Every .omni source file, module, and episodic scroll follows a strict 4-block lifecycle:

  • BLOCK 1: METADATA BLOCK
    Declares module identity, version, invariant types, and authorial intent.
    Example: Module < Example > ( Kernel logic intent ) { version: < "1.0.0" > }

  • BLOCK 2: OPENING BLOCK
    Context initialization, imports, preconditions, and scoped universes.
    Example: Opening { import: [ Core.Arithmetic ], preconditions: [ +1 ] }

  • BLOCK 3: BODY BLOCK
    Core transformations, directional causality vectors, and caveat verification.
    Example: Body [ state --> next_state [ +1 ] ! [ state = +1 ] ]

  • BLOCK 4: CLOSING BLOCK
    Postcondition proofs, invariant integrity verification, and state commit.
    Example: Closing { verify: [ next_state = +1 ], commit_status: [ +1 ] }

--------------------------------------------------------------------------------
3. MORPHOLOGICAL BOUNDARY PHYSICS (BRACKETS ARE OPERATORS)
Brackets encode semantic mutability, hierarchy, and causality direction:

  • [...] Rigid / Fixed:       Concrete memory, immutable datum, fixed denotation.
  • <...> Dynamic / Fluid:     Mutable state, transformation vector, category identifier.
  • {...} Universal / Omni:    Scoped universe, parent scope, environmental domain.
  • {...] Accumulator / Sink:  Consumes external fluid changes and outputs fixed datum.
  • [...} Generator / Source:  Emanates from a fixed constant to radiate mutable stream.
  • (...) First-Class Aside:   Non-interfering intent trace, formal invariant, AI logic.

--------------------------------------------------------------------------------
4. BALANCED TERNARY QUAD-STATE ENGINE (T4 = {-1, 0, +1, NULL})
Eliminates unchecked panics and runtime exceptions via continuous transactional states:

  • +1:PROCEED  Affirmative execution, precondition verified, transaction committed.
  •  0:AWAIT    Indeterminate state, suspended awaiting consensus or input.
  • -1:ROLLBACK Contra/veto state. Automatically rolls back state to previous snapshot.
  • NULL:HALT   Terminal void. Absorbs subsequent transformations and halts safely.

--------------------------------------------------------------------------------
5. 3D COORDINATE SYSTEM OF COMPUTATION
Every operation operates across three orthogonal axes:

  • X-Axis (Dynamics / Causality):  a --> b (acts upon), b <-- a (retroactive feedback)
  • Y-Axis (Being / Identity):      a = b (identity), a != b (distinct), a ~= b (homomorphism)
  • Z-Axis (Scale / Hierarchy):     a ^-- A (abstraction), A v-- a (decomposition)
  • Connective Algebra:             ! (caveat guard), :: (consensus AND), | (OR), -- (NOT)

--------------------------------------------------------------------------------
6. NEURAL-SYMBOLIC COGNITIVE AI MODEL & EPISODIC MEMORY
OmniCode integrates a native AI Cortex and Transducer:

  • AICortex: Bridges human natural language and verified 4-Block code.
  • Dual Episodic Inscription:
      - .scroll: Executable 4-Block Turing reel recording the exact episodic trace.
      - .log: Microsecond telemetry tracking channel duration and failpoint logs.
  • AILearner: Continuously digests experiences from scrolls/ to refine performance.
  • 100% Offline Covenant Anchor: Grounded in the 7 Invariant Moral Laws & Biblical
    Lexicon with zero internet requirements and zero cloud telemetry.

--------------------------------------------------------------------------------
7. CREATIVEWORKZSTUDIO LLC OFFICIAL PLATFORM
Engine Version: 0.1.0 | Rust Core Edition 2024
Copyright © 2026 CreativeWorkzStudio LLC. All rights reserved.
"""
        guide_text.insert("1.0", guide_content)
        guide_text.config(state=tk.DISABLED)

    # --------------------------------------------------------------------------
    # TAB 4: CLOUDFLARE & ORACLE EDGE DEPLOYMENT
    # --------------------------------------------------------------------------
    def _build_cloud_tab(self):
        """Builds controls and status displays for Cloudflare Tunnels and Oracle VM."""
```

```
        cloud_frame = tk.Frame(self.tab_cloud, bg=THEME["bg_surface"], padx=16, pady=16)
        cloud_frame.pack(fill=tk.BOTH, expand=True)

        tk.Label(
            cloud_frame,
            text="EDGE ROUTING & CLOUD DEPLOYMENT CENTER",
            font=("Segoe UI", 10, "bold"),
            fg=THEME["accent_cyan"],
            bg=THEME["bg_surface"]
        ).pack(anchor="w", pady=(0, 6))

        tk.Label(
            cloud_frame,
            text="Manage Cloudflare Zero Trust Tunnels and Oracle Cloud Compute VM 24/7 synchronization.",
            font=("Segoe UI", 8),
            fg=THEME["text_secondary"],
            bg=THEME["bg_surface"]
        ).pack(anchor="w", pady=(0, 14))

        # Two Columns
        grid_frame = tk.Frame(cloud_frame, bg=THEME["bg_surface"])
        grid_frame.pack(fill=tk.BOTH, expand=True)

        # Left Column: Oracle Cloud
        oracle_col = tk.Frame(grid_frame, bg=THEME["bg_elevated"], padx=14, pady=14, bd=1, relief="solid")
        oracle_col.pack(side=tk.LEFT, fill=tk.BOTH, expand=True, padx=(0, 8))

        tk.Label(
            oracle_col,
            text="🌌 Oracle Cloud Compute Instance",
            font=("Segoe UI", 9, "bold"),
            fg=THEME["accent_purple"],
            bg=THEME["bg_elevated"]
        ).pack(anchor="w", pady=(0, 8))

        oracle_info = """• Host IP:    147.224.147.30 (Host alias: oracle)
• User:       ubuntu
• SSH Key:    ~/.ssh/oracle_key.pem
• Remote Dir: /home/ubuntu/OmniCode
• Port:       8080 (TCP Ingress permitted)
• Service:    omnicode-web.service (systemd)"""
        tk.Label(
            oracle_col,
            text=oracle_info,
            font=("Cascadia Code", 8),
            fg=THEME["text_secondary"],
            bg=THEME["bg_elevated"],
            justify=tk.LEFT
        ).pack(anchor="w", pady=(0, 12))

        tk.Button(
            oracle_col,
            text="Sync to Oracle VM Now",
            font=("Segoe UI", 8, "bold"),
            bg=THEME["accent_purple"],
            fg="#ffffff",
            relief="flat",
            command=self.sync_oracle_vm,
            padx=12,
            pady=5,
            cursor="hand2"
        ).pack(anchor="w")

        # Right Column: Cloudflare
        cf_col = tk.Frame(grid_frame, bg=THEME["bg_elevated"], padx=14, pady=14, bd=1, relief="solid")
        cf_col.pack(side=tk.RIGHT, fill=tk.BOTH, expand=True, padx=(8, 0))

        tk.Label(
            cf_col,
            text="🌐 Cloudflare Zero Trust Edge",
            font=("Segoe UI", 9, "bold"),
            fg=THEME["accent_cyan"],
            bg=THEME["bg_elevated"]
        ).pack(anchor="w", pady=(0, 8))

        cf_info = """• Binary:     /usr/local/bin/cloudflared
• Domain:     omnicodestudio.duckdns.org
• WAN IP:     71.11.99.168 (CreativeWorkzStudio LLC)
```

```
• Quick Mode: Instant HTTPS at *.trycloudflare.com
• Local Port: http://localhost:8080"""
        tk.Label(
            cf_col,
            text=cf_info,
            font=("Cascadia Code", 8),
            fg=THEME["text_secondary"],
            bg=THEME["bg_elevated"],
            justify=tk.LEFT
        ).pack(anchor="w", pady=(0, 12))

        btn_row = tk.Frame(cf_col, bg=THEME["bg_elevated"])
        btn_row.pack(anchor="w")

        tk.Button(
            btn_row,
            text="Launch Quick Tunnel",
            font=("Segoe UI", 8, "bold"),
            bg=THEME["accent_cyan"],
            fg="#000000",
            relief="flat",
            command=self.start_quick_tunnel,
            padx=10,
            pady=5,
            cursor="hand2"
        ).pack(side=tk.LEFT, padx=(0, 8))

        tk.Button(
            btn_row,
            text="Launch Named Tunnel",
            font=("Segoe UI", 8, "bold"),
            bg=THEME["border"],
            fg=THEME["text_primary"],
            relief="flat",
            command=self.start_named_tunnel,
            padx=10,
            pady=5,
            cursor="hand2"
        ).pack(side=tk.LEFT)

    # ------------------------------------------------------------------------
    # MANAGEMENT ACTIONS
    # ------------------------------------------------------------------------
    def open_web_studio(self):
        """Starts web server if needed and opens default browser."""
        self.notebook.select(self.tab_terminal)
        self.log_terminal("[*] Opening OmniCode Web Studio at http://localhost:8080...")
        self._ensure_web_server_running(on_ready=lambda: webbrowser.open("http://localhost:8080"))

    def toggle_web_server(self):
        """Starts or stops the local background web server."""
        self.notebook.select(self.tab_terminal)
        if self.web_server_process:
            self.log_terminal("[*] Stopping local OmniCode Web Server...")
            try:
                self.web_server_process.terminate()
            except Exception:
                pass
            self.web_server_process = None
            self.pill_web.config(text="○ Web: Port 8080 (Off)", bg=THEME["bg_elevated"])
            self.log_terminal("[+] Web server stopped.")
        else:
            self.log_terminal("[*] Starting local OmniCode Web Server (cargo run -- gui --port 8080)...")
            self._start_web_server()

    def _start_web_server(self):
        def worker():
            try:
                proc = subprocess.Popen(
                    ["cargo", "run", "--quiet", "--", "gui", "--port", "8080"],
                    cwd=BASE_DIR,
                    stdout=subprocess.PIPE,
                    stderr=subprocess.STDOUT,
                    text=True
                )
                self.web_server_process = proc
                self.after(0, lambda: self.pill_web.config(text="● Web: Port 8080 (Live)", bg=THEME["state_proceed"]))
                for line in iter(proc.stdout.readline, ''):
```

```
                    clean = clean_ansi(line).rstrip()
                    if clean:
                        self.after(0, lambda l=clean: self.log_terminal(f"[Web] {l}"))
            except Exception as e:
                self.after(0, lambda err=str(e): self.log_terminal(f"[-] Web server error: {err}"))
            finally:
                self.web_server_process = None
                self.after(0, lambda: self.pill_web.config(text="○ Web: Port 8080 (Off)", bg=THEME["bg_elevated"]))

        threading.Thread(target=worker, daemon=True).start()

    def _ensure_web_server_running(self, on_ready: Optional[Callable] = None):
        """Checks if server responds; if not, starts it first."""
        import urllib.request
        is_up = False
        try:
            with urllib.request.urlopen("http://localhost:8080/api/manifest", timeout=0.8) as resp:
                if resp.status == 200:
                    is_up = True
        except Exception:
            is_up = False

        if is_up:
            if on_ready:
                on_ready()
        else:
            self._start_web_server()
            def wait_and_call():
                for _ in range(15):
                    time.sleep(0.5)
                    try:
                        with urllib.request.urlopen("http://localhost:8080/api/manifest", timeout=0.5) as r:
                            if r.status == 200:
                                if on_ready:
                                    self.after(0, on_ready)
                                return
                    except Exception:
                        pass
                if on_ready:
                    self.after(0, on_ready)
            threading.Thread(target=wait_and_call, daemon=True).start()

    def start_quick_tunnel(self):
        """Launches Cloudflare Quick Tunnel."""
        self.notebook.select(self.tab_terminal)
        self.log_terminal("[*] Launching Cloudflare Quick Tunnel...")
        self._ensure_web_server_running(on_ready=lambda: self.run_cli_command(f"{SCRIPTS_DIR}/setup_cloudflare_tunnel.sh
--quick"))
        self.pill_tunnel.config(text="● Edge: Quick Tunneling", bg=THEME["accent_cyan"], fg="#000000")

    def start_named_tunnel(self):
        """Launches Cloudflare Named Tunnel."""
        self.notebook.select(self.tab_terminal)
        self.log_terminal("[*] Launching Cloudflare Named Tunnel...")
        self._ensure_web_server_running(on_ready=lambda: self.run_cli_command(f"
{SCRIPTS_DIR}/setup_cloudflare_tunnel.sh"))
        self.pill_tunnel.config(text="● Edge: Named Tunnel", bg=THEME["accent_cyan"], fg="#000000")

    def sync_oracle_vm(self):
        """Triggers synchronization to Oracle Cloud VM."""
        self.notebook.select(self.tab_terminal)
        self.log_terminal("[*] Initiating Oracle Cloud VM synchronization...")
        self.run_cli_command(f"{SCRIPTS_DIR}/sync_oracle_vm.sh")

    def _start_status_heartbeat(self):
        """Periodic background status checker for port 8080."""
        def check():
            import urllib.request
            try:
                with urllib.request.urlopen("http://localhost:8080/api/manifest", timeout=0.4) as resp:
                    if resp.status == 200:
                        self.after(0, lambda: self.pill_web.config(text="● Web: Port 8080 (Live)",
bg=THEME["state_proceed"], fg="#ffffff"))
                        return
            except Exception:
                pass
            if not self.web_server_process:
                self.after(0, lambda: self.pill_web.config(text="○ Web: Port 8080 (Off)", bg=THEME["bg_elevated"],
```

```
fg=THEME["text_secondary"]))
        def loop():
            while True:
                check()
                time.sleep(4)

        threading.Thread(target=loop, daemon=True).start()


# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Application Entrypoint & Fallback Invocation )
# ================================================================================
def main():
    if not TKINTER_AVAILABLE:
        print("[!] Error: Tkinter desktop GUI library is not available in this Python runtime.")
        print("    Install via: sudo apt-get install -y python3-tk")
        sys.exit(1)

    app = OmniCodeDesktopApp()
    app.mainloop()

if __name__ == "__main__":
    main()
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/download.html HTML 140 LINES 659 WORDS 8.3 KB

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <meta name="description" content="Download OmniCode Standalone Native Terminal & Language Runtime — CreativeWorkzStudio LLC.">
    <title>Download Native OmniCode Terminal — CreativeWorkzStudio LLC</title>
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?family=Fira+Code:wght@400;500;600;700&family=Outfit:wght@300;400;500;600;700;800&family=Cinzel:wght@500;700;800&display=swap" rel="stylesheet">
    <link rel="stylesheet" href="/style.css">
</head>
<body>
    <div class="app-layout">
        <!-- GLOBAL NAVIGATION HEADER -->
        <header class="app-header" id="app-header">
            <div class="header-left">
                <a href="/studio" class="brand-container">
                    <span class="brand-symbol">Ω</span>
                    <div class="brand-text">
                        <span class="brand-title">OMNICODE</span>
                        <span class="brand-subtitle">CREATIVEWORKZSTUDIO LLC</span>
                    </div>
                </a>
                <div class="status-pill" id="status-pill" title="Engine runs 100% offline with zero cloud telemetry">
                    <span class="status-dot"></span>
                    <span class="status-text">OFFLINE COVENANT ACTIVE</span>
                </div>
            </div>

            <nav class="app-nav" aria-label="Main Navigation">
                <a href="/studio" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M12 2L2 7l10 5 10-5-10-5zM2 17l10 5 10-5M2 12l10 5 10-5"/></svg>
                    AI Studio
                </a>
                <a href="/terminal" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><polyline points="4 17 10 11 4 5"/><line x1="12" y1="19" x2="20" y2="19"/></svg>
                    CLI Terminal
                </a>
                <a href="/specs" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M14 2H6a2 2 0 0 0-2 2v16a2 2 0 0 0 2 2h12a2 2 0 0 0 2-2V8z"/><polyline points="14 2 14 8 20 8"/></svg>
                    Language Specs
                </a>
                <a href="/model" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M12 2a8 8 0 0 0-8 8c0 3.3 2 6.2 5 7.4V20a2 2 0 0 0 2 2h2a2 2 0 0 0 2-2v-2.6c3-1.2 5-4.1 5-7.4a8 8 0 0 0-8-8z"/></svg>
                    AI Model
                </a>
                <a href="/lexicon" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M4 19.5A2.5 2.5 0 0 1 6.5 17H20"/><path d="M6.5 2H20v20H6.5A2.5 2.5 0 0 1 4 19.5v-15A2.5 2.5 0 0 1 6.5 2z"/></svg>
                    Covenant Lexicon
                </a>
                <a href="/scrolls" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M19 21l-7-5-7 5V5a2 2 0 0 1 2-2h10a2 2 0 0 1 2 2z"/></svg>
                    Scrolls
                </a>
                <a href="/cloud" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M18 10h-1.26A8 8 0 1 0 9 20h9a5 5 0 0 0 0-10z"/></svg>
                    Cloud &amp;amp; Edge
                </a>
                <a href="/download" class="nav-tab active download-nav-btn">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M21 15v4a2 2 0 0 1-2 2H5a2 2 0 0 1-2-2v-4"/><polyline points="7 10 12 15 17 10"/><line x1="12" y1="15" x2="12" y2="3"/></svg>
                    Download Native
```

```
                </a>
            </nav>
        </header>

        <!-- DOWNLOAD HUB MAIN -->
        <main class="download-container">
            <div class="download-hero card-glass">
                <div class="hero-badge">STANDALONE SOVEREIGN RUNTIME</div>
                <h1>Download OmniCode Native Terminal</h1>
                <p class="hero-lead">
                    Run the primordial userspace shell and task scheduler directly on your local hardware. Zero runtime dependencies, 100% offline, and bare-metal deterministic execution.
                </p>
                <div class="download-btn-row">
                    <a href="/api/download" class="btn btn-lg btn-accent download-cta" download>
                        <svg width="20" height="20" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2.5"><path d="M21 15v4a2 2 0 0 1-2 2H5a2 2 0 0 1-2-2v-4"/><polyline points="7 10 12 15 17 10"/><line x1="12" y1="15" x2="12" y2="3"/></svg>
                        Download for Linux x86_64 (.tar.gz)
                    </a>
                </div>
                <div class="hero-subtext">
                    Edition: Rust Core 2024 &bull; Version 0.1.0 &bull; Architecture: Linux x86_64 &bull; Size: ~560 KB
                </div>
            </div>

            <!-- INSTALLATION & SPECS GRID -->
            <div class="download-grid">
                <!-- 1-LINE INSTALLATION -->
                <div class="download-card card-glass">
                    <div class="doc-card-header">
                        <span class="doc-icon">⚡</span>
                        <h2>1-Line Turnkey Terminal Installation</h2>
                    </div>
                    <p>Run directly in your local terminal to install the standalone binary to <code>~/.local/bin/omnicode</code>:</p>
                    <div class="code-copy-box">
                        <code id="cmd-curl-install">curl -sSL http://omnicodestudio.duckdns.org:8080/api/download | tar -xz && ./install.sh</code>
                    </div>
                    <div class="doc-subcard">
                        <h3>Launch Native Terminal</h3>
                        <p>After installation, launch the interactive REPL shell anytime:</p>
                        <code>omnicode terminal</code>
                    </div>
                </div>

                <!-- PACKAGE CONTENTS -->
                <div class="download-card card-glass">
                    <div class="doc-card-header">
                        <span class="doc-icon">📦</span>
                        <h2>Included in Distribution Kit</h2>
                    </div>
                    <ul class="spec-list">
                        <li><strong>Standalone Native Binary:</strong> <code>bin/omnicode</code> (compiled ELF executable, 0 dynamic library dependencies).</li>
                        <li><strong>Core Standard Library:</strong> <code>lib/core/arithmetic.omni</code>, <code>logic.omni</code>, <code>vectors.omni</code>.</li>
                        <li><strong>Covenant Manifest:</strong> Immutable ethical bedrock ([<code>manifest.omni</code>](file:///home/professorseanex/OmniCode/manifest.omni)).</li>
                        <li><strong>VS Code Extension:</strong> <code>omnicode-language-0.1.2.vsix</code> syntax highlighter and snippet pack.</li>
                        <li><strong>Canonical Examples:</strong> Balanced ternary logic, Turing tape tracks, and boundary proofs.</li>
                    </ul>
                </div>
            </div>
        </main>

        <!-- FOOTER -->
        <footer class="app-footer">
            <div class="footer-left">
                <span class="footer-brand">Ω OMNICODE</span>
                <span class="footer-sep">&bull;</span>
                <span class="footer-copy">&copy; 2026 CreativeWorkzStudio LLC. All rights reserved.</span>
            </div>
            <div class="footer-center">
                <span>The Sovereign Language &amp;amp; Native Userspace Shell for the Future OmniCode OS</span>
```

```
            </div>
            <div class="footer-right">
                <span class="footer-pill">Native Distribution</span>
                <span class="footer-pill">v0.1.0</span>
            </div>
        </footer>
    </div>
</body>
</html>
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/index.html HTML 136 LINES 610 WORDS 7.7 KB

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <meta name="description" content="OmniCode AI Prompt Studio & Code Synthesis — CreativeWorkzStudio LLC.">
    <title>OmniCode AI Studio — CreativeWorkzStudio LLC</title>
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?
family=Fira+Code:wght@400;500;600;700&family=Outfit:wght@300;400;500;600;700;800&family=Cinzel:wght@500;700;800&display=swap"
rel="stylesheet">
    <link rel="stylesheet" href="/style.css">
</head>
<body>
    <div class="app-layout">
        <!-- GLOBAL NAVIGATION HEADER -->
        <header class="app-header" id="app-header">
            <div class="header-left">
                <a href="/studio" class="brand-container">
                    <span class="brand-symbol">Ω</span>
                    <div class="brand-text">
                        <span class="brand-title">OMNICODE</span>
                        <span class="brand-subtitle">CREATIVEWORKZSTUDIO LLC</span>
                    </div>
                </a>
                <div class="status-pill" id="status-pill" title="Engine runs 100% offline with zero cloud telemetry">
                    <span class="status-dot"></span>
                    <span class="status-text">OFFLINE COVENANT ACTIVE</span>
                </div>
            </div>

            <nav class="app-nav" aria-label="Main Navigation">
                <a href="/studio" class="nav-tab active">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M12 2L2 7l10 5 10-5-10-5zM2 17l10 5 10-5M2 12l10 5 10-5"/></svg>
                    AI Studio
                </a>
                <a href="/terminal" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<polyline points="4 17 10 11 4 5"/><line x1="12" y1="19" x2="20" y2="19"/></svg>
                    CLI Terminal
                </a>
                <a href="/specs" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M14 2H6a2 2 0 0 0-2 2v16a2 2 0 0 0 2 2h12a2 2 0 0 0 2-2V8z"/><polyline points="14 2 14 8 20 8"/></svg>
                    Language Specs
                </a>
                <a href="/model" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M12 2a8 8 0 0 0-8 8c0 3.3 2 6.2 5 7.4V20a2 2 0 0 0 2 2h2a2 2 0 0 0 2-2v-2.6c3-1.2 5-4.1 5-7.4a8 8 0 0 0-8-8z"/></svg>
                    AI Model
                </a>
                <a href="/lexicon" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M4 19.5A2.5 2.5 0 0 1 6.5 17H20"/><path d="M6.5 2H20v20H6.5A2.5 2.5 0 0 1 4 19.5v-15A2.5 2.5 0 0 1 6.5 2z"/></svg>
                    Covenant Lexicon
                </a>
                <a href="/scrolls" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M19 21l-7-5-7 5V5a2 2 0 0 1 2-2h10a2 2 0 0 1 2 2z"/></svg>
                    Scrolls
                </a>
                <a href="/cloud" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M18 10h-1.26A8 8 0 1 0 9 20h9a5 5 0 0 0 0-10z"/></svg>
                    Cloud &amp;amp; Edge
                </a>
                <a href="/download" class="nav-tab download-nav-btn">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M21 15v4a2 2 0 0 1-2 2H5a2 2 0 0 1-2-2v-4"/><polyline points="7 10 12 15 17 10"/><line x1="12" y1="15" x2="12" y2="3"/>
</svg>
                    Download Native
                </a>
```

```
            </nav>
        </header>

        <!-- STUDIO MAIN -->
        <main class="studio-container">
            <div class="studio-grid">
                <!-- LEFT: PROMPT INPUT & INTENT FORM -->
                <div class="card-glass prompt-card">
                    <div class="panel-header">
                        <h2>Natural Language Intent Prompt</h2>
                        <span class="offline-note">🔒 Local execution &bull; 0% Cloud Telemetry</span>
                    </div>
                    <p class="panel-desc">
                        Provide a natural language description. The neural-symbolic transducer aligns it with moral
invariants and generates verified 4-block OmniCode.
                    </p>
                    <textarea id="prompt-input" class="prompt-textarea" rows="6" placeholder="Describe the program you
wish to create... (e.g. 'Build an immutable treasury ledger that verifies balanced transactions and rejects unauthorized
debits')"></textarea>

                    <div class="prompt-actions">
                        <button class="btn btn-accent" id="btn-generate">
                            <svg width="16" height="16" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-
width="2"><polygon points="5 3 19 12 5 21 5 3"/></svg>
                            Synthesize OmniCode
                        </button>
                        <button class="btn btn-secondary" id="btn-sample-prompt">Sample Intent</button>
                    </div>

                    <!-- RESPONSE STREAM -->
                    <div class="ai-response-box" id="ai-response-box">
                        <h3>AICortex Deliberation Summary</h3>
                        <div id="ai-response-text" class="response-text">Awaiting input prompt...</div>
                    </div>
                </div>

                <!-- RIGHT: SYNTHESIZED OMNICODE CODE VIEWER -->
                <div class="card-glass code-card">
                    <div class="panel-header">
                        <h2>Synthesized 4-Block OmniCode</h2>
                        <div class="badge-group">
                            <span class="badge badge-proceed" id="code-state-badge">+1:PROCEED</span>
                            <button class="btn btn-sm btn-secondary" id="btn-copy-code">Copy</button>
                        </div>
                    </div>
                    <pre class="code-editor" id="code-output"><code id="code-output-inner"># 
================================================================================
# BLOCK 1: METADATA BLOCK
# ================================================================================
Manifest &lt; Treasury.Ledger &gt; ( Moral Equilibrium ) {
    author: &lt; \"CreativeWorkzStudio LLC\" &gt;,
    resonance: &lt; +1:PROCEED &gt;
}
</code></pre>
                </div>
            </div>
        </main>

        <!-- FOOTER -->
        <footer class="app-footer">
            <div class="footer-left">
                <span class="footer-brand">Ω OMNICODE</span>
                <span class="footer-sep">&bull;</span>
                <span class="footer-copy">&copy; 2026 CreativeWorkzStudio LLC. All rights reserved.</span>
            </div>
            <div class="footer-center">
                <span>Dual-Readable Ontological Programming Language &amp; Cognitive AI Model</span>
            </div>
            <div class="footer-right">
                <span class="footer-pill">Rust Core Edition 2024</span>
                <span class="footer-pill">v0.1.0</span>
            </div>
        </footer>
    </div>
    <script src="/app.js"></script>
</body>
</html>
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/lexicon.html HTML 114 LINES 508 WORDS 6.3 KB

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <meta name="description" content="OmniCode Covenant Manifest & Biblical Lexicon World Model — CreativeWorkzStudio LLC.">
    <title>Covenant Manifest &amp;amp; Biblical Lexicon — CreativeWorkzStudio LLC</title>
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?family=Fira+Code:wght@400;500;600;700&family=Outfit:wght@300;400;500;600;700;800&family=Cinzel:wght@500;700;800&display=swap" rel="stylesheet">
    <link rel="stylesheet" href="/style.css">
</head>
<body>
    <div class="app-layout">
        <!-- GLOBAL NAVIGATION HEADER -->
        <header class="app-header" id="app-header">
            <div class="header-left">
                <a href="/studio" class="brand-container">
                    <span class="brand-symbol">Ω</span>
                    <div class="brand-text">
                        <span class="brand-title">OMNICODE</span>
                        <span class="brand-subtitle">CREATIVEWORKZSTUDIO LLC</span>
                    </div>
                </a>
                <div class="status-pill" id="status-pill" title="Engine runs 100% offline with zero cloud telemetry">
                    <span class="status-dot"></span>
                    <span class="status-text">OFFLINE COVENANT ACTIVE</span>
                </div>
            </div>

            <nav class="app-nav" aria-label="Main Navigation">
                <a href="/studio" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M12 2L2 7l10 5 10-5-10-5zM2 17l10 5 10-5M2 12l10 5 10-5"/></svg>
                    AI Studio
                </a>
                <a href="/terminal" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><polyline points="4 17 10 11 4 5"/><line x1="12" y1="19" x2="20" y2="19"/></svg>
                    CLI Terminal
                </a>
                <a href="/specs" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M14 2H6a2 2 0 0 0-2 2v16a2 2 0 0 0 2 2h12a2 2 0 0 0 2-2V8z"/><polyline points="14 2 14 8 20 8"/></svg>
                    Language Specs
                </a>
                <a href="/model" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M12 2a8 8 0 0 0-8 8c0 3.3 2 6.2 5 7.4V20a2 2 0 0 0 2 2h2a2 2 0 0 0 2-2v-2.6c3-1.2 5-4.1 5-7.4a8 8 0 0 0-8-8z"/></svg>
                    AI Model
                </a>
                <a href="/lexicon" class="nav-tab active">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M4 19.5A2.5 2.5 0 0 1 6.5 17H20"/><path d="M6.5 2H20v20H6.5A2.5 2.5 0 0 1 4 19.5v-15A2.5 2.5 0 0 1 6.5 2z"/></svg>
                    Covenant Lexicon
                </a>
                <a href="/scrolls" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M19 21l-7-5-7 5V5a2 2 0 0 1 2-2h10a2 2 0 0 1 2 2z"/></svg>
                    Scrolls
                </a>
                <a href="/cloud" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M18 10h-1.26A8 8 0 1 0 9 20h9a5 5 0 0 0 0-10z"/></svg>
                    Cloud &amp;amp; Edge
                </a>
                <a href="/download" class="nav-tab download-nav-btn">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M21 15v4a2 2 0 0 1-2 2H5a2 2 0 0 1-2-2v-4"/><polyline points="7 10 12 15 17 10"/><line x1="12" y1="15" x2="12" y2="3"/></svg>
                    Download Native
```

```
                </a>
            </nav>
        </header>

        <!-- LEXICON MAIN -->
        <main class="lexicon-container">
            <div class="lexicon-layout">
                <!-- LEFT: MANIFEST CODE VIEWER -->
                <div class="manifest-card card-glass">
                    <div class="panel-header">
                        <h2>Canonical Covenant Manifest</h2>
                        <span class="badge badge-proceed">Invariant Anchor</span>
                    </div>
                    <pre class="manifest-code"><code id="manifest-content">Loading canonical manifest.omni...</code>
</pre>
                </div>

                <!-- RIGHT: BIBLICAL LEXICON SEARCH & CARDS -->
                <div class="lexicon-card card-glass">
                    <div class="panel-header">
                        <h2>Biblical World Model Lexicon</h2>
                        <span class="badge badge-subtle" id="lexicon-count-badge">0 Entries</span>
                    </div>
                    <div class="lexicon-search-bar">
                        <input type="text" id="lexicon-search" class="form-input" placeholder="Search moral invariants,
scripture terms, or laws (e.g. truth, justice, life, void)...">
                    </div>
                    <div class="lexicon-entries-grid" id="lexicon-entries-grid">
                        <!-- Populated dynamically via app.js -->
                    </div>
                </div>
            </div>
        </main>

        <!-- FOOTER -->
        <footer class="app-footer">
            <div class="footer-left">
                <span class="footer-brand">Ω OMNICODE</span>
                <span class="footer-sep">&bull;</span>
                <span class="footer-copy">&copy; 2026 CreativeWorkzStudio LLC. All rights reserved.</span>
            </div>
            <div class="footer-center">
                <span>The Immutable Moral Anchor of Computation &bull; Rust Core 2024</span>
            </div>
            <div class="footer-right">
                <span class="footer-pill">Biblical Lexicon</span>
                <span class="footer-pill">v0.1.0</span>
            </div>
        </footer>
    </div>
    <script src="/app.js"></script>
</body>
</html>
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/model.html HTML 152 LINES 719 WORDS 8.9 KB

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <meta name="description" content="OmniCode Autonomous Cognitive AI Model & Neural-Symbolic Cortex — CreativeWorkzStudio LLC.">
    <title>OmniCode Cognitive AI Model — CreativeWorkzStudio LLC</title>
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?family=Fira+Code:wght@400;500;600;700&family=Outfit:wght@300;400;500;600;700;800&family=Cinzel:wght@500;700;800&display=swap" rel="stylesheet">
    <link rel="stylesheet" href="/style.css">
</head>
<body>
    <div class="app-layout">
        <!-- GLOBAL NAVIGATION HEADER -->
        <header class="app-header" id="app-header">
            <div class="header-left">
                <a href="/studio" class="brand-container">
                    <span class="brand-symbol">Ω</span>
                    <div class="brand-text">
                        <span class="brand-title">OMNICODE</span>
                        <span class="brand-subtitle">CREATIVEWORKZSTUDIO LLC</span>
                    </div>
                </a>
                <div class="status-pill" id="status-pill" title="Engine runs 100% offline with zero cloud telemetry">
                    <span class="status-dot"></span>
                    <span class="status-text">OFFLINE COVENANT ACTIVE</span>
                </div>
            </div>

            <nav class="app-nav" aria-label="Main Navigation">
                <a href="/studio" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M12 2L2 7l10 5 10-5-10-5zM2 17l10 5 10-5M2 12l10 5 10-5"/></svg>
                    AI Studio
                </a>
                <a href="/terminal" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><polyline points="4 17 10 11 4 5"/><line x1="12" y1="19" x2="20" y2="19"/></svg>
                    CLI Terminal
                </a>
                <a href="/specs" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M14 2H6a2 2 0 0 0-2 2v16a2 2 0 0 0 2 2h12a2 2 0 0 0 2-2V8z"/><polyline points="14 2 14 8 20 8"/></svg>
                    Language Specs
                </a>
                <a href="/model" class="nav-tab active">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M12 2a8 8 0 0 0-8 8c0 3.3 2 6.2 5 7.4V20a2 2 0 0 0 2 2h2a2 2 0 0 0 2-2v-2.6c3-1.2 5-4.1 5-7.4a8 8 0 0 0-8-8z"/></svg>
                    AI Model
                </a>
                <a href="/lexicon" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M4 19.5A2.5 2.5 0 0 1 6.5 17H20"/><path d="M6.5 2H20v20H6.5A2.5 2.5 0 0 1 4 19.5v-15A2.5 2.5 0 0 1 6.5 2z"/></svg>
                    Covenant Lexicon
                </a>
                <a href="/scrolls" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M19 21l-7-5-7 5V5a2 2 0 0 1 2-2h10a2 2 0 0 1 2 2z"/></svg>
                    Scrolls
                </a>
                <a href="/cloud" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M18 10h-1.26A8 8 0 1 0 9 20h9a5 5 0 0 0 0-10z"/></svg>
                    Cloud &amp;amp; Edge
                </a>
                <a href="/download" class="nav-tab download-nav-btn">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M21 15v4a2 2 0 0 1-2 2H5a2 2 0 0 1-2-2v-4"/><polyline points="7 10 12 15 17 10"/><line x1="12" y1="15" x2="12" y2="3"/></svg>
                    Download Native
```

```
                </a>
            </nav>
        </header>

        <!-- MODEL MAIN -->
        <main class="doc-container">
            <div class="doc-hero card-glass">
                <div class="hero-badge">AUTONOMOUS COGNITIVE ENGINE</div>
                <h1>The OmniCode Cognitive AI Model</h1>
                <p class="hero-lead">
                    Engineered by <strong>CreativeWorkzStudio LLC</strong>, the OmniCode AI Model features a local
Neural-Symbolic deliberative loop that bridges freeform human discourse with deterministic 4-Block Turing reels, anchored in
biblical moral invariants and continuous experiential learning.
                </p>
            </div>

            <div class="doc-grid">
                <!-- AICORTEX -->
                <div class="doc-card card-glass">
                    <div class="doc-card-header">
                        <span class="doc-icon">🧠</span>
                        <h2>The AICortex Transduction Loop</h2>
                    </div>
                    <p>The deliberative cycle that transforms natural human thought into verified machine reels:</p>
                    <ol class="doc-list">
                        <li><strong>Intent Extraction:</strong> Parses raw sentences into semantic concepts and target
boundary types.</li>
                        <li><strong>Moral Invariant Grounding:</strong> Validates intent against the 7 biblical laws of
the Covenant Anchor.</li>
                        <li><strong>4-Block Synthesis:</strong> Emits formal Metadata, Opening, Body, and Closing blocks.
</li>
                        <li><strong>Autonomous Verification &amp;amp; Repair:</strong> Executes the Linter and Restorator to
prove correctness.</li>
                    </ol>
                </div>

                <!-- AUTONOMOUS RESTORATOR -->
                <div class="doc-card card-glass">
                    <div class="doc-card-header">
                        <span class="doc-icon">🩹</span>
                        <h2>Self-Healing Restorator</h2>
                    </div>
                    <p>When syntax or boundary violations occur, the Restorator applies surgical heuristics without human
intervention:</p>
                    <ul class="spec-list">
                        <li>Injects missing Block headers (Opening/Body/Closing).</li>
                        <li>Balances unmatched boundary brackets (<code>&lt; ... &gt;</code>, <code>[ ... ]</code>,
<code>( ... )</code>).</li>
                        <li>Repairs malformed ternary operators (<code>--&gt;</code>, <code>&lt;--</code>).</li>
                        <li>Certifies repaired candidates through isolated test oracles.</li>
                    </ul>
                </div>

                <!-- EPISODIC LEARNING -->
                <div class="doc-card card-glass">
                    <div class="doc-card-header">
                        <span class="doc-icon">📜</span>
                        <h2>Episodic Learning (Experiential Scrolls)</h2>
                    </div>
                    <p>Every deliberation emits an immutable episodic scroll (<code>.scroll</code>):</p>
                    <ul class="spec-list">
                        <li>Logs user prompt, synthesized code, applied repairs, and final quad-state.</li>
                        <li>Persists across restarts in local directory <code>scrolls/</code>.</li>
                        <li>Prevents moral drift by enforcing positive reinforcement for invariant-aligned outcomes.</li>
                    </ul>
                </div>

                <!-- ZERO TELEMETRY -->
                <div class="doc-card card-glass">
                    <div class="doc-card-header">
                        <span class="doc-icon">🔒</span>
                        <h2>Zero Cloud Telemetry Covenant</h2>
                    </div>
                    <p>Unlike commercial LLMs that upload your source code and telemetry to cloud providers, OmniCode
operates under an immutable covenant:</p>
                    <p><strong>100% of reasoning, parsing, repair heuristics, and learning occur locally on your machine.
</strong></p>
                </div>
```

```
            </div>
        </main>

        <!-- FOOTER -->
        <footer class="app-footer">
            <div class="footer-left">
                <span class="footer-brand">Ω OMNICODE</span>
                <span class="footer-sep">&bull;</span>
                <span class="footer-copy">&copy; 2026 CreativeWorkzStudio LLC. All rights reserved.</span>
            </div>
            <div class="footer-center">
                <span>Autonomous Cognitive Intelligence &bull; Rust Core 2024</span>
            </div>
            <div class="footer-right">
                <span class="footer-pill">Cognitive Model</span>
                <span class="footer-pill">v0.1.0</span>
            </div>
        </footer>
    </div>
</body>
</html>
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/scrolls.html HTML 146 LINES 568 WORDS 7.8 KB

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <meta name="description" content="OmniCode Episodic Memory Bank & Experiential Scrolls — CreativeWorkzStudio LLC.">
    <title>Episodic Memory Scrolls — CreativeWorkzStudio LLC</title>
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?
family=Fira+Code:wght@400;500;600;700&family=Outfit:wght@300;400;500;600;700;800&family=Cinzel:wght@500;700;800&display=swap"
rel="stylesheet">
    <link rel="stylesheet" href="/style.css">
</head>
<body>
    <div class="app-layout">
        <!-- GLOBAL NAVIGATION HEADER -->
        <header class="app-header" id="app-header">
            <div class="header-left">
                <a href="/studio" class="brand-container">
                    <span class="brand-symbol">Ω</span>
                    <div class="brand-text">
                        <span class="brand-title">OMNICODE</span>
                        <span class="brand-subtitle">CREATIVEWORKZSTUDIO LLC</span>
                    </div>
                </a>
                <div class="status-pill" id="status-pill" title="Engine runs 100% offline with zero cloud telemetry">
                    <span class="status-dot"></span>
                    <span class="status-text">OFFLINE COVENANT ACTIVE</span>
                </div>
            </div>

            <nav class="app-nav" aria-label="Main Navigation">
                <a href="/studio" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M12 2L2 7l10 5 10-5-10-5zM2 17l10 5 10-5M2 12l10 5 10-5"/></svg>
                    AI Studio
                </a>
                <a href="/terminal" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<polyline points="4 17 10 11 4 5"/><line x1="12" y1="19" x2="20" y2="19"/></svg>
                    CLI Terminal
                </a>
                <a href="/specs" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M14 2H6a2 2 0 0 0-2 2v16a2 2 0 0 0 2 2h12a2 2 0 0 0 2-2V8z"/><polyline points="14 2 14 8 20 8"/></svg>
                    Language Specs
                </a>
                <a href="/model" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M12 2a8 8 0 0 0-8 8c0 3.3 2 6.2 5 7.4V20a2 2 0 0 0 2 2h2a2 2 0 0 0 2-2v-2.6c3-1.2 5-4.1 5-7.4a8 8 0 0 0-8-8z"/></svg>
                    AI Model
                </a>
                <a href="/lexicon" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M4 19.5A2.5 2.5 0 0 1 6.5 17H20"/><path d="M6.5 2H20v20H6.5A2.5 2.5 0 0 1 4 19.5v-15A2.5 2.5 0 0 1 6.5 2z"/></svg>
                    Covenant Lexicon
                </a>
                <a href="/scrolls" class="nav-tab active">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M19 21l-7-5-7 5V5a2 2 0 0 1 2-2h10a2 2 0 0 1 2 2z"/></svg>
                    Scrolls
                </a>
                <a href="/cloud" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M18 10h-1.26A8 8 0 1 0 9 20h9a5 5 0 0 0 0-10z"/></svg>
                    Cloud &amp;amp; Edge
                </a>
                <a href="/download" class="nav-tab download-nav-btn">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M21 15v4a2 2 0 0 1-2 2H5a2 2 0 0 1-2-2v-4"/><polyline points="7 10 12 15 17 10"/><line x1="12" y1="15" x2="12" y2="3"/>
</svg>
                    Download Native
                </a>
```

```
            </nav>
        </header>

        <!-- SCROLLS MAIN -->
        <main class="scrolls-container">
            <div class="scrolls-card card-glass">
                <div class="panel-header">
                    <div class="panel-header-title">
                        <h1>Episodic Memory Bank &amp;amp; Learning Inscription</h1>
                        <p class="panel-desc">Experiential scrolls (.scroll) and traditional telemetry logs (.log)
accumulated by the internal AI model. Grounded learning preserves successful restorations without moral drift.</p>
                    </div>
                    <button class="btn btn-secondary" id="btn-refresh-scrolls">Refresh Memory</button>
                </div>

                <!-- METRICS CARDS -->
                <div class="metrics-grid" id="metrics-grid">
                    <div class="metric-card">
                        <span class="metric-num" id="metric-total">0</span>
                        <span class="metric-label">Inscribed Episodes</span>
                    </div>
                    <div class="metric-card card-green">
                        <span class="metric-num" id="metric-proceed">0</span>
                        <span class="metric-label">+1: PROCEED</span>
                    </div>
                    <div class="metric-card card-amber">
                        <span class="metric-num" id="metric-await">0</span>
                        <span class="metric-label">0: AWAIT</span>
                    </div>
                    <div class="metric-card card-red">
                        <span class="metric-num" id="metric-rollback">0</span>
                        <span class="metric-label">-1: ROLLBACK</span>
                    </div>
                    <div class="metric-card card-purple">
                        <span class="metric-num" id="metric-halt">0</span>
                        <span class="metric-label">NULL: HALT</span>
                    </div>
                    <div class="metric-card">
                        <span class="metric-num" id="metric-repairs">0</span>
                        <span class="metric-label">Repairs Learned</span>
                    </div>
                </div>

                <!-- SCROLLS EPISODES TABLE -->
                <div class="episodes-table-wrapper">
                    <table class="episodes-table">
                        <thead>
                            <tr>
                                <th>Session ID</th>
                                <th>Prompt Intent</th>
                                <th>Final State</th>
                                <th>Repairs</th>
                                <th>Failpoints</th>
                                <th>Scroll Path</th>
                            </tr>
                        </thead>
                        <tbody id="episodes-tbody">
                            <!-- Populated dynamically via JS -->
                        </tbody>
                    </table>
                </div>
            </div>
        </main>

        <!-- FOOTER -->
        <footer class="app-footer">
            <div class="footer-left">
                <span class="footer-brand">Ω OMNICODE</span>
                <span class="footer-sep">&bull;</span>
                <span class="footer-copy">&copy; 2026 CreativeWorkzStudio LLC. All rights reserved.</span>
            </div>
            <div class="footer-center">
                <span>Episodic Learning &bull; Experiential Memory Ledger &bull; Rust Core 2024</span>
            </div>
            <div class="footer-right">
                <span class="footer-pill">Episodic Scrolls</span>
                <span class="footer-pill">v0.1.0</span>
            </div>
```

```
        </footer>
    </div>
    <script src="/app.js"></script>
</body>
</html>
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/specs.html HTML 155 LINES 798 WORDS 9.6 KB

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <meta name="description" content="OmniCode Language Specification & 4-Block Formal Architecture — CreativeWorkzStudio LLC.">
    <title>OmniCode Language Specifications — CreativeWorkzStudio LLC</title>
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?family=Fira+Code:wght@400;500;600;700&family=Outfit:wght@300;400;500;600;700;800&family=Cinzel:wght@500;700;800&display=swap" rel="stylesheet">
    <link rel="stylesheet" href="/style.css">
</head>
<body>
    <div class="app-layout">
        <!-- GLOBAL NAVIGATION HEADER -->
        <header class="app-header" id="app-header">
            <div class="header-left">
                <a href="/studio" class="brand-container">
                    <span class="brand-symbol">Ω</span>
                    <div class="brand-text">
                        <span class="brand-title">OMNICODE</span>
                        <span class="brand-subtitle">CREATIVEWORKZSTUDIO LLC</span>
                    </div>
                </a>
                <div class="status-pill" id="status-pill" title="Engine runs 100% offline with zero cloud telemetry">
                    <span class="status-dot"></span>
                    <span class="status-text">OFFLINE COVENANT ACTIVE</span>
                </div>
            </div>

            <nav class="app-nav" aria-label="Main Navigation">
                <a href="/studio" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M12 2L2 7l10 5 10-5-10-5zM2 17l10 5 10-5M2 12l10 5 10-5"/></svg>
                    AI Studio
                </a>
                <a href="/terminal" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><polyline points="4 17 10 11 4 5"/><line x1="12" y1="19" x2="20" y2="19"/></svg>
                    CLI Terminal
                </a>
                <a href="/specs" class="nav-tab active">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M14 2H6a2 2 0 0 0-2 2v16a2 2 0 0 0 2 2h12a2 2 0 0 0 2-2V8z"/><polyline points="14 2 14 8 20 8"/></svg>
                    Language Specs
                </a>
                <a href="/model" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M12 2a8 8 0 0 0-8 8c0 3.3 2 6.2 5 7.4V20a2 2 0 0 0 2 2h2a2 2 0 0 0 2-2v-2.6c3-1.2 5-4.1 5-7.4a8 8 0 0 0-8-8z"/></svg>
                    AI Model
                </a>
                <a href="/lexicon" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M4 19.5A2.5 2.5 0 0 1 6.5 17H20"/><path d="M6.5 2H20v20H6.5A2.5 2.5 0 0 1 4 19.5v-15A2.5 2.5 0 0 1 6.5 2z"/></svg>
                    Covenant Lexicon
                </a>
                <a href="/scrolls" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M19 21l-7-5-7 5V5a2 2 0 0 1 2-2h10a2 2 0 0 1 2 2z"/></svg>
                    Scrolls
                </a>
                <a href="/cloud" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M18 10h-1.26A8 8 0 1 0 9 20h9a5 5 0 0 0 0-10z"/></svg>
                    Cloud &amp;amp; Edge
                </a>
                <a href="/download" class="nav-tab download-nav-btn">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M21 15v4a2 2 0 0 1-2 2H5a2 2 0 0 1-2-2v-4"/><polyline points="7 10 12 15 17 10"/><line x1="12" y1="15" x2="12" y2="3"/></svg>
                    Download Native
```

```
                </a>
            </nav>
        </header>

        <!-- SPECS MAIN -->
        <main class="doc-container">
            <div class="doc-hero card-glass">
                <div class="hero-badge">CANONICAL LANGUAGE SPECIFICATION</div>
                <h1>The OmniCode Programming Language</h1>
                <p class="hero-lead">
                    An ontological, dual-readable programming language engineered by <strong>CreativeWorkzStudio
LLC</strong> from first principles. Operates with bare-metal low-level precision while natively expressing balanced-ternary quad-
state state machines, causal laws, and ethical invariants.
                </p>
            </div>

            <div class="doc-grid">
                <!-- 4-BLOCK ARCHITECTURE -->
                <div class="doc-card card-glass">
                    <div class="doc-card-header">
                        <span class="doc-icon">🏛️</span>
                        <h2>The 4-Block Architecture</h2>
                    </div>
                    <p>Every valid OmniCode unit must be structured into four sequential compilation blocks:</p>
                    <ol class="doc-list">
                        <li><strong>Block 1: Metadata Block (Manifest)</strong> — Declares ontological identity, covenant
anchor, and boundary classifications.</li>
                        <li><strong>Block 2: Opening Block (Opening { ... })</strong> — Import libraries, assert
immutable preconditions, and establish initial state vectors.</li>
                        <li><strong>Block 3: Body Block (Body [ ... ])</strong> — Execute causal logic, balanced ternary
rolls, and iterative computations.</li>
                        <li><strong>Block 4: Closing Block (Closing { ... })</strong> — Verify post-conditions, reconcile
invariants, and permanently seal transaction state.</li>
                    </ol>
                </div>

                <!-- BALANCED TERNARY RADIX-3 -->
                <div class="doc-card card-glass">
                    <div class="doc-card-header">
                        <span class="doc-icon">⚖️</span>
                        <h2>Balanced Ternary Quad-State Logic</h2>
                    </div>
                    <p>Unlike binary logic (0 or 1), OmniCode operates on Balanced Radix-3 with a terminal Null state
(T4):</p>
                    <ul class="spec-list">
                        <li><strong>+1 (Proceed):</strong> Affirmative forward vector (<code>--&gt;</code>). Commits
state mutations and advances the Turing reel.</li>
                        <li><strong>0 (Await):</strong> Standby, pass-through equilibrium, or asynchronous yield.</li>
                        <li><strong>-1 (Rollback):</strong> Negation and boundary breach. Automatically unwinds
retroactive vectors (<code>&lt;--</code>).</li>
                        <li><strong>NULL (Halt):</strong> Absorbing bottom type (&perp;). Traps unrecoverable faults and
terminates process.</li>
                    </ul>
                </div>

                <!-- BOUNDARIES -->
                <div class="doc-card card-glass">
                    <div class="doc-card-header">
                        <span class="doc-icon">🛡️</span>
                        <h2>The 6 Boundary Types</h2>
                    </div>
                    <ul class="spec-list">
                        <li><code>&lt; Invariant &gt;</code> — Absolute unalterable boundary. Immutable across all
scopes.</li>
                        <li><code>&lt; Finite &gt;</code> — Strictly bounded range, buffer capacity, or count.</li>
                        <li><code>&lt; Indefinite &gt;</code> — Elastic state awaiting runtime determination.</li>
                        <li><code>&lt; Continuous &gt;</code> — Streaming uninterrupted sequence or real-time feed.</li>
                        <li><code>&lt; Absorb &gt;</code> — Trap boundary that swallows violations into safe fallbacks.
</li>
                        <li><code>&lt; Oscillate &gt;</code> — Alternating dual-phase harmonic boundary.</li>
                    </ul>
                </div>

                <!-- FORMAL ASIDES -->
                <div class="doc-card card-glass">
                    <div class="doc-card-header">
                        <span class="doc-icon">💬</span>
                        <h2>Formal Asides (Dual Readability)</h2>
```

```
                    </div>
                    <p>Parentheses <code>( ... )</code> in OmniCode are not inert comments—they are <strong>ontological semantic anchors</strong> parsed by the compiler:</p>
                    <pre class="code-snippet"><code>roll_integrity [ health &gt; 0 ] ( Vital signs active and confirmed )</code></pre>
                    <p class="subtext">The inner text informs the AICortex and linter of human moral intent while the expression enforces rigorous machine truth.</p>
                </div>
            </div>
        </main>

        <!-- FOOTER -->
        <footer class="app-footer">
            <div class="footer-left">
                <span class="footer-brand">Ω OMNICODE</span>
                <span class="footer-sep">&bull;</span>
                <span class="footer-copy">&copy; 2026 CreativeWorkzStudio LLC. All rights reserved.</span>
            </div>
            <div class="footer-center">
                <span>Formal Dual-Readable Specifications &bull; Rust Core 2024</span>
            </div>
            <div class="footer-right">
                <span class="footer-pill">Language Specs</span>
                <span class="footer-pill">v0.1.0</span>
            </div>
        </footer>
    </div>
</body>
</html>
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/studio.html HTML 136 LINES 610 WORDS 7.7 KB

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <meta name="description" content="OmniCode AI Prompt Studio & Code Synthesis — CreativeWorkzStudio LLC.">
    <title>OmniCode AI Studio — CreativeWorkzStudio LLC</title>
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?
family=Fira+Code:wght@400;500;600;700&family=Outfit:wght@300;400;500;600;700;800&family=Cinzel:wght@500;700;800&display=swap"
rel="stylesheet">
    <link rel="stylesheet" href="/style.css">
</head>
<body>
    <div class="app-layout">
        <!-- GLOBAL NAVIGATION HEADER -->
        <header class="app-header" id="app-header">
            <div class="header-left">
                <a href="/studio" class="brand-container">
                    <span class="brand-symbol">Ω</span>
                    <div class="brand-text">
                        <span class="brand-title">OMNICODE</span>
                        <span class="brand-subtitle">CREATIVEWORKZSTUDIO LLC</span>
                    </div>
                </a>
                <div class="status-pill" id="status-pill" title="Engine runs 100% offline with zero cloud telemetry">
                    <span class="status-dot"></span>
                    <span class="status-text">OFFLINE COVENANT ACTIVE</span>
                </div>
            </div>

            <nav class="app-nav" aria-label="Main Navigation">
                <a href="/studio" class="nav-tab active">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M12 2L2 7l10 5 10-5-10-5zM2 17l10 5 10-5M2 12l10 5 10-5"/></svg>
                    AI Studio
                </a>
                <a href="/terminal" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<polyline points="4 17 10 11 4 5"/><line x1="12" y1="19" x2="20" y2="19"/></svg>
                    CLI Terminal
                </a>
                <a href="/specs" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M14 2H6a2 2 0 0 0-2 2v16a2 2 0 0 0 2 2h12a2 2 0 0 0 2-2V8z"/><polyline points="14 2 14 8 20 8"/></svg>
                    Language Specs
                </a>
                <a href="/model" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M12 2a8 8 0 0 0-8 8c0 3.3 2 6.2 5 7.4V20a2 2 0 0 0 2 2h2a2 2 0 0 0 2-2v-2.6c3-1.2 5-4.1 5-7.4a8 8 0 0 0-8-8z"/></svg>
                    AI Model
                </a>
                <a href="/lexicon" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M4 19.5A2.5 2.5 0 0 1 6.5 17H20"/><path d="M6.5 2H20v20H6.5A2.5 2.5 0 0 1 4 19.5v-15A2.5 2.5 0 0 1 6.5 2z"/></svg>
                    Covenant Lexicon
                </a>
                <a href="/scrolls" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M19 21l-7-5-7 5V5a2 2 0 0 1 2-2h10a2 2 0 0 1 2 2z"/></svg>
                    Scrolls
                </a>
                <a href="/cloud" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M18 10h-1.26A8 8 0 1 0 9 20h9a5 5 0 0 0 0-10z"/></svg>
                    Cloud &amp;amp; Edge
                </a>
                <a href="/download" class="nav-tab download-nav-btn">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2">
<path d="M21 15v4a2 2 0 0 1-2 2H5a2 2 0 0 1-2-2v-4"/><polyline points="7 10 12 15 17 10"/><line x1="12" y1="15" x2="12" y2="3"/>
</svg>
                    Download Native
                </a>
```

```
            </nav>
        </header>

        <!-- STUDIO MAIN -->
        <main class="studio-container">
            <div class="studio-grid">
                <!-- LEFT: PROMPT INPUT & INTENT FORM -->
                <div class="card-glass prompt-card">
                    <div class="panel-header">
                        <h2>Natural Language Intent Prompt</h2>
                        <span class="offline-note">🔒 Local execution &bull; 0% Cloud Telemetry</span>
                    </div>
                    <p class="panel-desc">
                        Provide a natural language description. The neural-symbolic transducer aligns it with moral
invariants and generates verified 4-block OmniCode.
                    </p>
                    <textarea id="prompt-input" class="prompt-textarea" rows="6" placeholder="Describe the program you
wish to create... (e.g. 'Build an immutable treasury ledger that verifies balanced transactions and rejects unauthorized
debits')"></textarea>

                    <div class="prompt-actions">
                        <button class="btn btn-accent" id="btn-generate">
                            <svg width="16" height="16" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-
width="2"><polygon points="5 3 19 12 5 21 5 3"/></svg>
                            Synthesize OmniCode
                        </button>
                        <button class="btn btn-secondary" id="btn-sample-prompt">Sample Intent</button>
                    </div>

                    <!-- RESPONSE STREAM -->
                    <div class="ai-response-box" id="ai-response-box">
                        <h3>AICortex Deliberation Summary</h3>
                        <div id="ai-response-text" class="response-text">Awaiting input prompt...</div>
                    </div>
                </div>

                <!-- RIGHT: SYNTHESIZED OMNICODE CODE VIEWER -->
                <div class="card-glass code-card">
                    <div class="panel-header">
                        <h2>Synthesized 4-Block OmniCode</h2>
                        <div class="badge-group">
                            <span class="badge badge-proceed" id="code-state-badge">+1:PROCEED</span>
                            <button class="btn btn-sm btn-secondary" id="btn-copy-code">Copy</button>
                        </div>
                    </div>
                    <pre class="code-editor" id="code-output"><code id="code-output-inner"># 
================================================================================
# BLOCK 1: METADATA BLOCK
# ================================================================================
Manifest &lt; Treasury.Ledger &gt; ( Moral Equilibrium ) {
    author: &lt; \"CreativeWorkzStudio LLC\" &gt;,
    resonance: &lt; +1:PROCEED &gt;
}
</code></pre>
                </div>
            </div>
        </main>

        <!-- FOOTER -->
        <footer class="app-footer">
            <div class="footer-left">
                <span class="footer-brand">Ω OMNICODE</span>
                <span class="footer-sep">&bull;</span>
                <span class="footer-copy">&copy; 2026 CreativeWorkzStudio LLC. All rights reserved.</span>
            </div>
            <div class="footer-center">
                <span>Dual-Readable Ontological Programming Language &amp; Cognitive AI Model</span>
            </div>
            <div class="footer-right">
                <span class="footer-pill">Rust Core Edition 2024</span>
                <span class="footer-pill">v0.1.0</span>
            </div>
        </footer>
    </div>
    <script src="/app.js"></script>
</body>
</html>
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/style.css CSS 1747 LINES 3804 WORDS 37.7 KB

```css
/* ================================================================================
   OMNICODE STUDIO & COGNITIVE TERMINAL STYLESHEET
   Aesthetics: Deep Obsidian, Radiant Neon Glassmorphism, Dual Monospace Code
   ================================================================================ */

:root {
    /* Color Palette */
    --bg-base: #07090e;
    --bg-surface: #0d121d;
    --bg-elevated: #131a29;
    --border-subtle: rgba(255, 255, 255, 0.08);
    --border-bright: rgba(0, 240, 255, 0.3);

    /* Text Colors */
    --text-primary: #f0f4fc;
    --text-secondary: #94a3b8;
    --text-muted: #64748b;
    --text-highlight: #ffffff;

    /* Theme Jewel Accents */
    --cyan: #00f0ff;
    --cyan-glow: rgba(0, 240, 255, 0.25);
    --gold: #ffd700;
    --gold-glow: rgba(255, 215, 0, 0.25);

    /* Balanced Ternary Quad-State Colors */
    --state-proceed: #00e676;
    --state-proceed-glow: rgba(0, 230, 118, 0.3);
    --state-await: #ffaa00;
    --state-await-glow: rgba(255, 170, 0, 0.3);
    --state-rollback: #ff3d71;
    --state-rollback-glow: rgba(255, 61, 113, 0.3);
    --state-halt: #9d4edd;
    --state-halt-glow: rgba(157, 78, 221, 0.3);

    /* Typography */
    --font-sans: 'Outfit', -apple-system, BlinkMacSystemFont, 'Segoe UI', Roboto, sans-serif;
    --font-mono: 'Fira Code', Consolas, Monaco, monospace;
    --font-serif: 'Cinzel', Georgia, serif;

    /* Shadows & Radii */
    --radius-sm: 6px;
    --radius-md: 10px;
    --radius-lg: 16px;
    --shadow-glass: 0 8px 32px 0 rgba(0, 0, 0, 0.45);
    --glass-bg: rgba(13, 18, 29, 0.7);
    --glass-border: 1px solid rgba(255, 255, 255, 0.08);
}

/* Base Reset */
*, *::before, *::after {
    box-sizing: border-box;
    margin: 0;
    padding: 0;
}

body {
    background-color: var(--bg-base);
    color: var(--text-primary);
    font-family: var(--font-sans);
    line-height: 1.6;
    overflow-x: hidden;
    min-height: 100vh;
    background-image:
        radial-gradient(circle at 15% 10%, rgba(0, 240, 255, 0.05) 0%, transparent 40%),
        radial-gradient(circle at 85% 80%, rgba(255, 215, 0, 0.04) 0%, transparent 45%),
        radial-gradient(circle at 50% 50%, rgba(157, 78, 221, 0.03) 0%, transparent 60%);
    background-attachment: fixed;
}

/* App Layout */
.app-layout {
    display: flex;
    flex-direction: column;
```

```
    min-height: 100vh;
}

/* ------------------------------------------------------------------------
   HEADER & NAVIGATION
   ------------------------------------------------------------------------ */
.app-header {
    display: flex;
    align-items: center;
    justify-content: space-between;
    padding: 1rem 2rem;
    background: rgba(7, 9, 14, 0.85);
    backdrop-filter: blur(20px);
    -webkit-backdrop-filter: blur(20px);
    border-bottom: var(--glass-border);
    position: sticky;
    top: 0;
    z-index: 100;
}

.header-left {
    display: flex;
    align-items: center;
    gap: 1.5rem;
}

.brand-container {
    display: flex;
    align-items: center;
    gap: 0.75rem;
}

.brand-symbol {
    font-size: 1.8rem;
    font-weight: 800;
    color: var(--cyan);
    text-shadow: 0 0 16px var(--cyan-glow);
    font-family: var(--font-serif);
}

.brand-text {
    display: flex;
    flex-direction: column;
}

.brand-title {
    font-size: 1.15rem;
    font-weight: 800;
    letter-spacing: 0.15em;
    color: var(--text-highlight);
}

.brand-subtitle {
    font-size: 0.65rem;
    letter-spacing: 0.2em;
    color: var(--gold);
    font-weight: 600;
}

.status-pill {
    display: flex;
    align-items: center;
    gap: 0.5rem;
    padding: 0.35rem 0.85rem;
    background: rgba(0, 230, 118, 0.08);
    border: 1px solid rgba(0, 230, 118, 0.3);
    border-radius: 999px;
    font-size: 0.72rem;
    font-weight: 600;
    color: var(--state-proceed);
    letter-spacing: 0.05em;
}

.status-dot {
    width: 7px;
    height: 7px;
    border-radius: 50%;
    background: var(--state-proceed);
```

```
    box-shadow: 0 0 8px var(--state-proceed);
    animation: pulse-dot 2s infinite ease-in-out;
}

@keyframes pulse-dot {
    0%, 100% { opacity: 1; transform: scale(1); }
    50% { opacity: 0.4; transform: scale(0.85); }
}

.app-nav {
    display: flex;
    gap: 0.5rem;
}

.nav-tab {
    display: flex;
    align-items: center;
    gap: 0.5rem;
    padding: 0.6rem 1.1rem;
    background: transparent;
    border: 1px solid transparent;
    border-radius: var(--radius-md);
    color: var(--text-secondary);
    font-family: var(--font-sans);
    font-size: 0.9rem;
    font-weight: 500;
    cursor: pointer;
    transition: all 0.25s ease;
}

.nav-tab:hover {
    color: var(--text-primary);
    background: rgba(255, 255, 255, 0.04);
}

.nav-tab.active {
    color: var(--cyan);
    background: rgba(0, 240, 255, 0.08);
    border-color: rgba(0, 240, 255, 0.35);
    box-shadow: 0 0 15px rgba(0, 240, 255, 0.15);
}

.ternary-quad-badge {
    padding: 0.4rem 0.9rem;
    background: var(--bg-surface);
    border: 1px solid var(--border-subtle);
    border-radius: var(--radius-sm);
    font-family: var(--font-mono);
    font-size: 0.75rem;
    font-weight: 600;
    color: var(--gold);
    letter-spacing: 0.05em;
}

/* ------------------------------------------------------------------------
   MAIN & VIEW PANELS
   ------------------------------------------------------------------------ */
.app-main {
    flex: 1;
    padding: 2rem;
    max-width: 1600px;
    margin: 0 auto;
    width: 100%;
}

.view-panel {
    display: none;
    animation: fadeIn 0.3s ease;
}

.view-panel.active {
    display: block;
}

@keyframes fadeIn {
    from { opacity: 0; transform: translateY(6px); }
    to { opacity: 1; transform: translateY(0); }
}
```

```
/* Glassmorphism Cards */
.card-glass {
    background: var(--glass-bg);
    backdrop-filter: blur(16px);
    -webkit-backdrop-filter: blur(16px);
    border: var(--glass-border);
    border-radius: var(--radius-lg);
    box-shadow: var(--shadow-glass);
    padding: 1.5rem;
}

.panel-header {
    display: flex;
    justify-content: space-between;
    align-items: flex-start;
    margin-bottom: 1.25rem;
    gap: 1rem;
}

.panel-header-title h1 {
    font-size: 1.5rem;
    font-weight: 700;
    color: var(--text-highlight);
    margin-bottom: 0.35rem;
}

.panel-desc {
    font-size: 0.88rem;
    color: var(--text-secondary);
    max-width: 850px;
}

/* ------------------------------------------------------------------------
   VIEW 1: PROMPT WORKBENCH
   ------------------------------------------------------------------------ */
.quadstate-indicator {
    display: flex;
    align-items: center;
    gap: 0.6rem;
    padding: 0.5rem 1.1rem;
    background: rgba(255, 170, 0, 0.1);
    border: 1px solid var(--state-await);
    border-radius: var(--radius-md);
    color: var(--state-await);
    font-family: var(--font-mono);
    font-size: 0.85rem;
    font-weight: 700;
    transition: all 0.3s ease;
}

.quadstate-indicator.proceed {
    background: rgba(0, 230, 118, 0.1);
    border-color: var(--state-proceed);
    color: var(--state-proceed);
    box-shadow: 0 0 15px var(--state-proceed-glow);
}

.quadstate-indicator.rollback {
    background: rgba(255, 61, 113, 0.1);
    border-color: var(--state-rollback);
    color: var(--state-rollback);
    box-shadow: 0 0 15px var(--state-rollback-glow);
}

.quadstate-indicator.halt {
    background: rgba(157, 78, 221, 0.1);
    border-color: var(--state-halt);
    color: var(--state-halt);
    box-shadow: 0 0 15px var(--state-halt-glow);
}

.prompt-chips-container {
    display: flex;
    flex-wrap: wrap;
    align-items: center;
    gap: 0.5rem;
    margin-bottom: 1.25rem;
```

```
}

.chip-label {
    font-size: 0.8rem;
    font-weight: 600;
    color: var(--text-muted);
    text-transform: uppercase;
    letter-spacing: 0.05em;
}

.prompt-chip, .term-btn {
    background: rgba(255, 255, 255, 0.04);
    border: 1px solid var(--border-subtle);
    border-radius: 999px;
    padding: 0.35rem 0.85rem;
    color: var(--text-secondary);
    font-size: 0.82rem;
    cursor: pointer;
    transition: all 0.2s ease;
}

.prompt-chip:hover, .term-btn:hover {
    background: rgba(0, 240, 255, 0.12);
    border-color: var(--cyan);
    color: var(--text-highlight);
    transform: translateY(-1px);
}

.prompt-chip.chip-warning {
    border-color: rgba(255, 61, 113, 0.3);
    color: #ff7597;
}

.prompt-chip.chip-warning:hover {
    background: rgba(255, 61, 113, 0.15);
    border-color: var(--state-rollback);
}

.prompt-form textarea {
    width: 100%;
    background: var(--bg-surface);
    border: 1px solid var(--border-subtle);
    border-radius: var(--radius-md);
    padding: 1rem;
    color: var(--text-primary);
    font-family: var(--font-sans);
    font-size: 1rem;
    resize: vertical;
    outline: none;
    transition: border-color 0.2s ease, box-shadow 0.2s ease;
}

.prompt-form textarea:focus {
    border-color: var(--cyan);
    box-shadow: 0 0 15px var(--cyan-glow);
}

.form-actions {
    display: flex;
    justify-content: space-between;
    align-items: center;
    margin-top: 0.85rem;
}

.offline-note {
    font-size: 0.78rem;
    color: var(--text-muted);
}

.btn {
    display: inline-flex;
    align-items: center;
    gap: 0.5rem;
    padding: 0.65rem 1.35rem;
    border-radius: var(--radius-md);
    font-family: var(--font-sans);
    font-size: 0.92rem;
    font-weight: 600;
```

```
    cursor: pointer;
    transition: all 0.25s ease;
    border: none;
}

.btn-primary {
    background: linear-gradient(135deg, #00f0ff 0%, #0088ff 100%);
    color: #050811;
    box-shadow: 0 4px 15px rgba(0, 240, 255, 0.3);
}

.btn-primary:hover {
    filter: brightness(1.15);
    transform: translateY(-1px);
    box-shadow: 0 6px 20px rgba(0, 240, 255, 0.45);
}

.btn-secondary {
    background: rgba(255, 255, 255, 0.06);
    border: 1px solid var(--border-subtle);
    color: var(--text-secondary);
}

.btn-secondary:hover {
    background: rgba(255, 255, 255, 0.1);
    color: var(--text-primary);
}

/* Studio Output Split Grid */
.studio-output-grid {
    display: grid;
    grid-template-columns: 1fr 1fr;
    gap: 1.5rem;
    margin-top: 1.5rem;
}

.card-header {
    display: flex;
    justify-content: space-between;
    align-items: center;
    margin-bottom: 1rem;
    border-bottom: 1px solid rgba(255, 255, 255, 0.05);
    padding-bottom: 0.75rem;
}

.card-title-group {
    display: flex;
    align-items: center;
    gap: 0.5rem;
}

.card-title-group h2 {
    font-size: 1.05rem;
    font-weight: 600;
    color: var(--text-highlight);
}

.session-badge {
    font-family: var(--font-mono);
    font-size: 0.75rem;
    color: var(--cyan);
    background: rgba(0, 240, 255, 0.08);
    padding: 0.25rem 0.6rem;
    border-radius: var(--radius-sm);
}

.response-body {
    min-height: 250px;
    font-size: 0.95rem;
    line-height: 1.7;
    white-space: pre-wrap;
    color: #e2e8f0;
}

.placeholder-text {
    color: var(--text-muted);
    font-style: italic;
    padding-top: 2rem;
```

```
}

.card-footer {
    display: flex;
    flex-wrap: wrap;
    gap: 1rem;
    margin-top: 1rem;
    padding-top: 0.75rem;
    border-top: 1px solid rgba(255, 255, 255, 0.05);
    font-family: var(--font-mono);
    font-size: 0.75rem;
    color: var(--text-muted);
}

.code-body {
    background: #05070c;
    border-radius: var(--radius-md);
    padding: 1rem;
    max-height: 480px;
    overflow-y: auto;
    border: 1px solid rgba(255, 255, 255, 0.05);
}

.code-body pre code {
    font-family: var(--font-mono);
    font-size: 0.85rem;
    line-height: 1.5;
    color: #a5b4fc;
}

.btn-icon {
    background: rgba(255, 255, 255, 0.05);
    border: 1px solid var(--border-subtle);
    color: var(--text-secondary);
    border-radius: var(--radius-sm);
    padding: 0.3rem 0.7rem;
    font-size: 0.75rem;
    cursor: pointer;
}

.btn-icon:hover {
    color: var(--text-highlight);
    background: rgba(255, 255, 255, 0.1);
}

/* ------------------------------------------------------------------------
   VIEW 2: CLI TERMINAL
   ------------------------------------------------------------------------ */
.terminal-shortcuts {
    display: flex;
    flex-wrap: wrap;
    align-items: center;
    gap: 0.5rem;
    margin-bottom: 1rem;
}

.term-btn {
    font-family: var(--font-mono);
    font-size: 0.75rem;
}

.terminal-window {
    background: #04060a;
    border: 1px solid rgba(0, 240, 255, 0.2);
    border-radius: var(--radius-md);
    padding: 1.25rem;
    min-height: 480px;
    max-height: 600px;
    overflow-y: auto;
    font-family: var(--font-mono);
    font-size: 0.88rem;
    line-height: 1.6;
    color: #4ade80;
    box-shadow: inset 0 0 30px rgba(0, 0, 0, 0.8);
}

.terminal-banner pre {
    color: var(--cyan);
```

```
    margin-bottom: 1rem;
    font-family: inherit;
    white-space: pre-wrap;
}

.terminal-stream {
    white-space: pre-wrap;
    word-break: break-all;
}

.term-line-cmd {
    color: var(--gold);
    font-weight: 600;
    margin-top: 0.75rem;
}

.term-line-stdout {
    color: #e2e8f0;
}

.term-line-stderr {
    color: var(--state-rollback);
}

.terminal-input-bar {
    display: flex;
    align-items: center;
    gap: 0.75rem;
    margin-top: 1rem;
    background: var(--bg-surface);
    border: 1px solid var(--border-subtle);
    border-radius: var(--radius-md);
    padding: 0.5rem 1rem;
}

.prompt-prefix {
    font-family: var(--font-mono);
    font-size: 0.9rem;
    font-weight: 700;
    color: var(--cyan);
}

.terminal-input-bar input {
    flex: 1;
    background: transparent;
    border: none;
    color: var(--text-highlight);
    font-family: var(--font-mono);
    font-size: 0.92rem;
    outline: none;
}

/* ------------------------------------------------------------------------
   VIEW 3: COVENANT & LEXICON
   ------------------------------------------------------------------------ */
.lexicon-container {
    display: grid;
    grid-template-columns: 1fr 1.35fr;
    gap: 1.5rem;
}

.column-badge {
    font-size: 0.65rem;
    letter-spacing: 0.15em;
    font-weight: 700;
    color: var(--gold);
    text-transform: uppercase;
}

.column-header h2 {
    font-size: 1.35rem;
    color: var(--text-highlight);
    margin: 0.25rem 0 0.5rem 0;
}

.column-desc {
    font-size: 0.85rem;
    color: var(--text-secondary);
```

```
    margin-bottom: 1.25rem;
}

.laws-list {
    display: flex;
    flex-direction: column;
    gap: 0.85rem;
    max-height: 750px;
    overflow-y: auto;
    padding-right: 0.5rem;
}

.law-card {
    background: var(--bg-surface);
    border: 1px solid var(--border-subtle);
    border-radius: var(--radius-md);
    padding: 1rem;
    transition: transform 0.2s ease, border-color 0.2s ease;
}

.law-card:hover {
    border-color: rgba(255, 215, 0, 0.35);
    transform: translateX(3px);
}

.law-title-row {
    display: flex;
    align-items: center;
    gap: 0.75rem;
    margin-bottom: 0.5rem;
}

.law-num {
    font-family: var(--font-serif);
    font-size: 0.9rem;
    font-weight: 700;
    color: var(--gold);
    width: 24px;
}

.law-name {
    flex: 1;
    font-size: 0.95rem;
    font-weight: 600;
    color: var(--text-highlight);
}

.state-chip {
    font-family: var(--font-mono);
    font-size: 0.68rem;
    font-weight: 700;
    padding: 0.2rem 0.55rem;
    border-radius: var(--radius-sm);
}

.state-proceed {
    background: rgba(0, 230, 118, 0.12);
    color: var(--state-proceed);
    border: 1px solid rgba(0, 230, 118, 0.3);
}

.state-await {
    background: rgba(255, 170, 0, 0.12);
    color: var(--state-await);
    border: 1px solid rgba(255, 170, 0, 0.3);
}

.state-halt {
    background: rgba(157, 78, 221, 0.12);
    color: var(--state-halt);
    border: 1px solid rgba(157, 78, 221, 0.3);
}

.law-quote {
    font-size: 0.82rem;
    font-style: italic;
    color: #cbd5e1;
    margin-bottom: 0.5rem;
```

```
    line-height: 1.5;
}

.law-rule {
    font-size: 0.75rem;
    font-weight: 600;
    color: var(--cyan);
}

.lexicon-controls {
    margin-bottom: 1.25rem;
}

#lexicon-search-input {
    width: 100%;
    background: var(--bg-surface);
    border: 1px solid var(--border-subtle);
    border-radius: var(--radius-md);
    padding: 0.75rem 1rem;
    color: var(--text-primary);
    font-size: 0.9rem;
    outline: none;
    margin-bottom: 0.75rem;
}

#lexicon-search-input:focus {
    border-color: var(--cyan);
}

.domain-filters {
    display: flex;
    flex-wrap: wrap;
    gap: 0.4rem;
}

.filter-btn {
    background: rgba(255, 255, 255, 0.04);
    border: 1px solid var(--border-subtle);
    border-radius: var(--radius-sm);
    padding: 0.3rem 0.75rem;
    color: var(--text-secondary);
    font-size: 0.75rem;
    cursor: pointer;
    transition: all 0.2s ease;
}

.filter-btn:hover {
    color: var(--text-primary);
    background: rgba(255, 255, 255, 0.08);
}

.filter-btn.active {
    background: rgba(0, 240, 255, 0.12);
    border-color: var(--cyan);
    color: var(--cyan);
    font-weight: 600;
}

.lexicon-entries-grid {
    display: flex;
    flex-direction: column;
    gap: 0.85rem;
    max-height: 650px;
    overflow-y: auto;
    padding-right: 0.5rem;
}

.entry-card {
    background: var(--bg-surface);
    border: 1px solid var(--border-subtle);
    border-radius: var(--radius-md);
    padding: 1rem;
    transition: all 0.2s ease;
}

.entry-card:hover {
    border-color: rgba(0, 240, 255, 0.3);
}
```

```
777
778 .entry-header {
779     display: flex;
780     justify-content: space-between;
781     align-items: center;
782     margin-bottom: 0.5rem;
783 }
784
785 .entry-term {
786     font-size: 1.05rem;
787     font-weight: 700;
788     color: var(--cyan);
789     text-transform: uppercase;
790     letter-spacing: 0.05em;
791 }
792
793 .entry-domain {
794     font-size: 0.72rem;
795     color: var(--gold);
796     background: rgba(255, 215, 0, 0.08);
797     padding: 0.2rem 0.5rem;
798     border-radius: var(--radius-sm);
799 }
800
801 .entry-def {
802     font-size: 0.85rem;
803     color: #e2e8f0;
804     margin-bottom: 0.65rem;
805 }
806
807 .entry-witnesses {
808     background: #05070d;
809     border-radius: var(--radius-sm);
810     padding: 0.6rem 0.8rem;
811     font-size: 0.78rem;
812     line-height: 1.5;
813     color: #94a3b8;
814     margin-bottom: 0.5rem;
815 }
816
817 .witness-title {
818     font-weight: 700;
819     color: var(--text-highlight);
820     margin-right: 0.35rem;
821 }
822
823 .entry-guidance {
824     font-size: 0.78rem;
825     color: var(--state-proceed);
826     font-weight: 500;
827 }
828
829 /* ------------------------------------------------------------------------
830    VIEW 4: EPISODIC SCROLLS
831    ------------------------------------------------------------------------ */
832 .metrics-grid {
833     display: grid;
834     grid-template-columns: repeat(6, 1fr);
835     gap: 1rem;
836     margin-bottom: 1.5rem;
837 }
838
839 .metric-card {
840     background: var(--bg-surface);
841     border: 1px solid var(--border-subtle);
842     border-radius: var(--radius-md);
843     padding: 1rem;
844     display: flex;
845     flex-direction: column;
846     align-items: center;
847     text-align: center;
848 }
849
850 .metric-num {
851     font-size: 1.75rem;
852     font-weight: 800;
853     font-family: var(--font-mono);
854     color: var(--text-highlight);
```

```
}

.metric-label {
    font-size: 0.72rem;
    color: var(--text-muted);
    text-transform: uppercase;
    letter-spacing: 0.05em;
    margin-top: 0.25rem;
}

.card-green .metric-num { color: var(--state-proceed); }
.card-amber .metric-num { color: var(--state-await); }
.card-red .metric-num { color: var(--state-rollback); }
.card-purple .metric-num { color: var(--state-halt); }

.episodes-table-wrapper {
    background: #05070c;
    border: 1px solid var(--border-subtle);
    border-radius: var(--radius-md);
    overflow-x: auto;
    max-height: 520px;
}

.episodes-table {
    width: 100%;
    border-collapse: collapse;
    font-size: 0.85rem;
    text-align: left;
}

.episodes-table th {
    background: rgba(255, 255, 255, 0.03);
    padding: 0.85rem 1rem;
    font-weight: 600;
    color: var(--text-muted);
    border-bottom: 1px solid var(--border-subtle);
    text-transform: uppercase;
    font-size: 0.72rem;
    letter-spacing: 0.05em;
}

.episodes-table td {
    padding: 0.85rem 1rem;
    border-bottom: 1px solid rgba(255, 255, 255, 0.03);
    color: #cbd5e1;
}

.episodes-table tr:hover td {
    background: rgba(0, 240, 255, 0.02);
}

/* Responsive */
@media (max-width: 1100px) {
    .studio-output-grid,
    .lexicon-container {
        grid-template-columns: 1fr;
    }
    .metrics-grid {
        grid-template-columns: repeat(3, 1fr);
    }
}

@media (max-width: 768px) {
    .app-header {
        flex-direction: column;
        gap: 1rem;
        padding: 1rem;
    }
    .metrics-grid {
        grid-template-columns: repeat(2, 1fr);
    }
}

/* ------------------------------------------------------------------------
   CREATIVEWORKZSTUDIO LLC BRANDING & DOCUMENTATION STYLES
   ------------------------------------------------------------------------ */
.cws-badge {
    background: linear-gradient(135deg, rgba(255, 215, 0, 0.15), rgba(255, 170, 0, 0.08));
```

```
    border: 1px solid rgba(255, 215, 0, 0.35);
    color: var(--gold);
    font-size: 0.75rem;
    font-weight: 700;
    padding: 0.35rem 0.85rem;
    border-radius: 9999px;
    letter-spacing: 0.04em;
    text-transform: uppercase;
    display: inline-flex;
    align-items: center;
    gap: 0.4rem;
    box-shadow: 0 0 12px rgba(255, 215, 0, 0.1);
}

.terminal-ctrl-group {
    display: flex;
    gap: 0.5rem;
    align-items: center;
}

/* Documentation Layout */
.doc-container {
    display: flex;
    flex-direction: column;
    gap: 1.5rem;
    max-width: 1300px;
    margin: 0 auto;
    width: 100%;
}

.doc-hero {
    padding: 2.2rem;
    border-radius: var(--radius-lg);
    background: linear-gradient(135deg, rgba(13, 18, 29, 0.85) 0%, rgba(20, 28, 45, 0.7) 100%);
    border: var(--glass-border);
    position: relative;
    overflow: hidden;
}

.doc-hero::before {
    content: '';
    position: absolute;
    top: 0;
    right: 0;
    width: 320px;
    height: 100%;
    background: radial-gradient(circle at center, rgba(0, 240, 255, 0.08) 0%, transparent 70%);
    pointer-events: none;
}

.hero-badge {
    display: inline-block;
    font-size: 0.72rem;
    font-weight: 800;
    letter-spacing: 0.1em;
    text-transform: uppercase;
    color: var(--cyan);
    margin-bottom: 0.6rem;
}

.doc-hero h1 {
    font-size: 2.2rem;
    font-weight: 800;
    color: #ffffff;
    margin-bottom: 0.8rem;
    letter-spacing: -0.02em;
}

.hero-lead {
    font-size: 1.05rem;
    color: var(--text-secondary);
    line-height: 1.7;
    max-width: 950px;
}

.doc-grid {
    display: grid;
    grid-template-columns: repeat(2, 1fr);
```

```
    gap: 1.5rem;
}

@media (max-width: 1024px) {
    .doc-grid {
        grid-template-columns: 1fr;
    }
}

.doc-card {
    padding: 1.8rem;
    border-radius: var(--radius-md);
    display: flex;
    flex-direction: column;
    gap: 1rem;
}

.doc-card-header {
    display: flex;
    align-items: center;
    gap: 0.75rem;
    border-bottom: 1px solid var(--border-subtle);
    padding-bottom: 0.8rem;
}

.doc-icon {
    font-size: 1.5rem;
}

.doc-card-header h2 {
    font-size: 1.2rem;
    font-weight: 700;
    color: #ffffff;
}

/* 4-Block Timeline */
.four-block-timeline {
    display: flex;
    flex-direction: column;
    gap: 0.6rem;
    margin: 0.5rem 0;
}

.timeline-step {
    display: flex;
    align-items: flex-start;
    gap: 0.8rem;
    background: rgba(255, 255, 255, 0.02);
    padding: 0.6rem 0.8rem;
    border-radius: var(--radius-sm);
    border-left: 3px solid var(--cyan);
}

.step-num {
    background: var(--cyan);
    color: #000000;
    font-weight: 800;
    font-size: 0.75rem;
    width: 20px;
    height: 20px;
    border-radius: 50%;
    display: flex;
    align-items: center;
    justify-content: center;
    flex-shrink: 0;
}

.step-content {
    font-size: 0.88rem;
    color: var(--text-primary);
}

.code-snippet-box {
    background: #05070b;
    border: 1px solid var(--border-subtle);
    border-radius: var(--radius-sm);
    padding: 1rem;
    font-family: var(--font-mono);
```

```
    font-size: 0.82rem;
    overflow-x: auto;
    color: var(--cyan);
}

/* Spec Tables */
.table-responsive {
    overflow-x: auto;
    width: 100%;
}

.spec-table {
    width: 100%;
    border-collapse: collapse;
    font-size: 0.85rem;
}

.spec-table th {
    background: rgba(255, 255, 255, 0.04);
    padding: 0.7rem 0.85rem;
    color: var(--text-muted);
    font-size: 0.72rem;
    text-transform: uppercase;
    letter-spacing: 0.05em;
    text-align: left;
    border-bottom: 1px solid var(--border-subtle);
}

.spec-table td {
    padding: 0.7rem 0.85rem;
    border-bottom: 1px solid rgba(255, 255, 255, 0.03);
    color: #cbd5e1;
}

.spec-table tr:hover td {
    background: rgba(0, 240, 255, 0.02);
}

/* Boundary Badges */
.badge-rigid { color: #58a6ff; font-weight: 700; }
.badge-fluid { color: #38bdf8; font-weight: 700; }
.badge-omni { color: #d29922; font-weight: 700; }
.badge-sink { color: #f85149; font-weight: 700; }
.badge-source { color: #3fb950; font-weight: 700; }
.badge-aside { color: #bc8cff; font-weight: 700; }

/* Quad-State Showcase */
.quad-state-showcase {
    display: grid;
    grid-template-columns: repeat(2, 1fr);
    gap: 0.75rem;
    margin: 0.5rem 0;
}

.quad-item {
    padding: 0.8rem;
    border-radius: var(--radius-sm);
    display: flex;
    flex-direction: column;
    gap: 0.3rem;
    border: 1px solid rgba(255, 255, 255, 0.05);
}

.quad-item.quad-proceed { background: rgba(0, 230, 118, 0.06); border-color: rgba(0, 230, 118, 0.25); }
.quad-item.quad-await { background: rgba(255, 170, 0, 0.06); border-color: rgba(255, 170, 0, 0.25); }
.quad-item.quad-rollback { background: rgba(255, 61, 113, 0.06); border-color: rgba(255, 61, 113, 0.25); }
.quad-item.quad-halt { background: rgba(157, 78, 221, 0.06); border-color: rgba(157, 78, 221, 0.25); }

.quad-code {
    font-family: var(--font-mono);
    font-weight: 800;
    font-size: 0.85rem;
}
.quad-proceed .quad-code { color: var(--state-proceed); }
.quad-await .quad-code { color: var(--state-await); }
.quad-rollback .quad-code { color: var(--state-rollback); }
.quad-halt .quad-code { color: var(--state-halt); }

```

```
.quad-meaning {
    font-size: 0.8rem;
    color: var(--text-secondary);
}

/* AI Pipeline */
.pipeline-diagram {
    display: flex;
    flex-direction: column;
    align-items: center;
    gap: 0.4rem;
    margin: 0.5rem 0;
}

.pipe-node {
    width: 100%;
    background: rgba(255, 255, 255, 0.03);
    border: 1px solid var(--border-subtle);
    padding: 0.65rem 1rem;
    border-radius: var(--radius-sm);
    text-align: center;
    font-size: 0.85rem;
    font-weight: 600;
    color: var(--text-primary);
}

.pipe-node.highlight {
    background: rgba(0, 240, 255, 0.08);
    border-color: var(--border-bright);
    color: var(--cyan);
}

.pipe-arrow {
    color: var(--text-muted);
    font-size: 0.9rem;
}

.mini-laws-grid {
    display: flex;
    flex-direction: column;
    gap: 0.4rem;
    font-size: 0.85rem;
}

.mini-law {
    background: rgba(255, 255, 255, 0.02);
    padding: 0.5rem 0.8rem;
    border-radius: var(--radius-sm);
    color: var(--text-secondary);
}

.mini-law strong {
    color: #ffffff;
}

.doc-subcard {
    background: rgba(255, 255, 255, 0.02);
    border: 1px solid var(--border-subtle);
    border-radius: var(--radius-sm);
    padding: 1rem;
    margin-top: 0.5rem;
}

.doc-subcard h3 {
    font-size: 0.95rem;
    color: var(--text-primary);
    margin-bottom: 0.4rem;
}

.doc-subcard p {
    font-size: 0.85rem;
    color: var(--text-secondary);
    margin-bottom: 0.5rem;
}

.doc-subcard code {
    display: block;
    background: #05070b;
```

```
    padding: 0.5rem 0.8rem;
    border-radius: var(--radius-sm);
    font-family: var(--font-mono);
    font-size: 0.8rem;
    color: var(--cyan);
}

.spec-list {
    list-style: none;
    display: flex;
    flex-direction: column;
    gap: 0.6rem;
    font-size: 0.88rem;
    color: var(--text-secondary);
}

.spec-list li strong {
    color: #ffffff;
}

/* ------------------------------------------------------------------------
   FOOTER
   ------------------------------------------------------------------------ */
.app-footer {
    display: flex;
    align-items: center;
    justify-content: space-between;
    padding: 1.2rem 2rem;
    background: rgba(7, 9, 14, 0.9);
    border-top: var(--glass-border);
    font-size: 0.82rem;
    color: var(--text-muted);
    margin-top: 2rem;
}

.footer-left {
    display: flex;
    align-items: center;
    gap: 0.75rem;
}

.footer-brand {
    font-family: var(--font-serif);
    font-weight: 700;
    color: var(--cyan);
}

.footer-center {
    color: var(--text-secondary);
}

.footer-right {
    display: flex;
    align-items: center;
    gap: 0.5rem;
}

.footer-pill {
    background: rgba(255, 255, 255, 0.05);
    padding: 0.2rem 0.6rem;
    border-radius: 9999px;
    font-size: 0.72rem;
    color: var(--text-secondary);
}

/* ------------------------------------------------------------------------
   INTERACTIVE TERMINAL WORKSPACE & SCHEDULER STYLES
   ------------------------------------------------------------------------ */
.terminal-body {
    overflow: hidden;
}
.terminal-page-layout {
    height: 100vh;
    display: flex;
    flex-direction: column;
}
.terminal-workspace {
    flex: 1;
```

```
    display: flex;
    flex-direction: column;
    padding: 1rem 1.5rem;
    gap: 0.8rem;
    overflow: hidden;
}
.terminal-toolbar {
    display: flex;
    align-items: center;
    justify-content: space-between;
    padding: 0.6rem 1rem;
    background: rgba(13, 17, 23, 0.8);
    border: 1px solid rgba(255, 255, 255, 0.08);
    border-radius: 8px;
}
.toolbar-left {
    display: flex;
    align-items: center;
    gap: 0.8rem;
}
.terminal-title-badge {
    font-family: var(--font-mono);
    font-size: 0.78rem;
    font-weight: 700;
    color: var(--cyan);
    letter-spacing: 0.05em;
}
.sched-pill {
    background: rgba(0, 240, 255, 0.1);
    border: 1px solid rgba(0, 240, 255, 0.25);
    color: var(--cyan);
    font-size: 0.72rem;
    padding: 0.25rem 0.6rem;
    border-radius: 9999px;
    display: flex;
    align-items: center;
    gap: 0.4rem;
}
.mem-pill {
    background: rgba(0, 255, 136, 0.1);
    border: 1px solid rgba(0, 255, 136, 0.25);
    color: var(--green);
    font-size: 0.72rem;
    padding: 0.25rem 0.6rem;
    border-radius: 9999px;
}
.toolbar-actions {
    display: flex;
    gap: 0.4rem;
}
.btn-sm {
    padding: 0.35rem 0.7rem;
    font-size: 0.75rem;
}
.btn-xs {
    padding: 0.2rem 0.45rem;
    font-size: 0.68rem;
}
.btn-danger-ghost {
    background: transparent;
    color: #ff5555;
    border: 1px solid rgba(255, 85, 85, 0.25);
}
.btn-danger-ghost:hover {
    background: rgba(255, 85, 85, 0.15);
}

.terminal-grid {
    flex: 1;
    display: grid;
    grid-template-columns: 1fr 380px;
    gap: 1rem;
    min-height: 0;
}
.terminal-console-pane {
    display: flex;
    flex-direction: column;
    background: rgba(10, 12, 16, 0.95);
```

```
    border: 1px solid rgba(0, 240, 255, 0.2);
    border-radius: 8px;
    box-shadow: 0 8px 32px rgba(0, 0, 0, 0.5);
    min-height: 0;
    overflow: hidden;
}
.console-screen {
    flex: 1;
    padding: 1.2rem;
    overflow-y: auto;
    font-family: var(--font-mono);
    font-size: 0.86rem;
    line-height: 1.5;
    color: #e6edf3;
    outline: none;
}
.term-intro {
    color: var(--cyan);
    white-space: pre-wrap;
    margin-bottom: 1rem;
    font-size: 0.78rem;
    opacity: 0.9;
}
.term-entry {
    margin-bottom: 0.8rem;
}
.term-command-line {
    display: flex;
    align-items: center;
    gap: 0.5rem;
    color: #ffffff;
    font-weight: 600;
}
.term-prompt {
    color: var(--gold);
    font-family: var(--font-mono);
    font-weight: 700;
}
.term-cmd-text {
    color: #00f0ff;
}
.term-result-box {
    margin-top: 0.3rem;
    padding-left: 0.8rem;
    border-left: 2px solid rgba(0, 240, 255, 0.3);
}
.term-meta-bar {
    display: flex;
    align-items: center;
    gap: 0.6rem;
    margin-bottom: 0.25rem;
    font-size: 0.72rem;
}
.term-output-text {
    font-family: var(--font-mono);
    font-size: 0.82rem;
    white-space: pre-wrap;
    word-break: break-word;
    color: #d1d5db;
    margin: 0;
}
.console-input-row {
    display: flex;
    align-items: center;
    gap: 0.6rem;
    padding: 0.8rem 1.2rem;
    background: rgba(13, 17, 23, 0.95);
    border-top: 1px solid rgba(255, 255, 255, 0.08);
}
.term-input {
    flex: 1;
    background: transparent;
    border: none;
    outline: none;
    color: #ffffff;
    font-family: var(--font-mono);
    font-size: 0.9rem;
}
```

```
1479
1480 /* Scheduler Right Pane */
1481 .scheduler-pane {
1482     display: flex;
1483     flex-direction: column;
1484     background: rgba(13, 17, 23, 0.85);
1485     border: 1px solid rgba(255, 255, 255, 0.08);
1486     border-radius: 8px;
1487     padding: 1rem;
1488     gap: 0.8rem;
1489     min-height: 0;
1490     overflow: hidden;
1491 }
1492 .scheduler-pane-header {
1493     display: flex;
1494     justify-content: space-between;
1495     align-items: center;
1496 }
1497 .sched-title-group h2 {
1498     font-size: 0.95rem;
1499     margin: 0;
1500     color: #ffffff;
1501 }
1502 .sched-title-group .subtext {
1503     font-size: 0.72rem;
1504     color: var(--text-muted);
1505     margin: 0;
1506 }
1507 .sched-spawn-box {
1508     display: grid;
1509     grid-template-columns: 1fr 1fr;
1510     gap: 0.4rem;
1511 }
1512 .sched-spawn-box button {
1513     grid-column: span 2;
1514 }
1515 .form-input-sm, .form-select-sm {
1516     background: rgba(255, 255, 255, 0.05);
1517     border: 1px solid rgba(255, 255, 255, 0.1);
1518     color: #ffffff;
1519     padding: 0.35rem 0.5rem;
1520     font-size: 0.75rem;
1521     border-radius: 4px;
1522     outline: none;
1523 }
1524 .task-table-wrapper {
1525     flex: 1;
1526     overflow-y: auto;
1527     border: 1px solid rgba(255, 255, 255, 0.05);
1528     border-radius: 4px;
1529 }
1530 .task-table {
1531     width: 100%;
1532     border-collapse: collapse;
1533     font-size: 0.75rem;
1534 }
1535 .task-table th, .task-table td {
1536     padding: 0.45rem 0.6rem;
1537     text-align: left;
1538     border-bottom: 1px solid rgba(255, 255, 255, 0.05);
1539 }
1540 .task-table th {
1541     background: rgba(255, 255, 255, 0.03);
1542     color: var(--text-muted);
1543     font-weight: 600;
1544 }
1545 .action-cell {
1546     display: flex;
1547     gap: 0.2rem;
1548 }
1549 .session-vars-box {
1550     background: rgba(0, 0, 0, 0.3);
1551     border: 1px solid rgba(255, 255, 255, 0.05);
1552     border-radius: 4px;
1553     padding: 0.6rem;
1554     max-height: 120px;
1555     overflow-y: auto;
1556 }
```

```
.vars-header {
    display: flex;
    justify-content: space-between;
    align-items: center;
    margin-bottom: 0.3rem;
}
.vars-header h3 {
    font-size: 0.75rem;
    margin: 0;
    color: var(--gold);
}
.vars-content {
    font-family: var(--font-mono);
    font-size: 0.72rem;
    color: #e6edf3;
}

/* Download Page Styles */
.download-container {
    max-width: 1100px;
    margin: 2rem auto;
    padding: 0 1.5rem;
}
.download-hero {
    text-align: center;
    padding: 3rem 2rem;
    margin-bottom: 2rem;
}
.download-btn-row {
    margin: 2rem 0 1rem;
}
.download-cta {
    background: linear-gradient(135deg, #00f0ff, #0099ff);
    color: #000000;
    font-weight: 800;
    font-size: 1.05rem;
    padding: 0.9rem 2.2rem;
    border-radius: 8px;
    box-shadow: 0 0 25px rgba(0, 240, 255, 0.35);
    display: inline-flex;
    align-items: center;
    gap: 0.8rem;
    text-decoration: none;
    transition: transform 0.2s, box-shadow 0.2s;
}
.download-cta:hover {
    transform: translateY(-2px);
    box-shadow: 0 0 35px rgba(0, 240, 255, 0.5);
}
.hero-subtext {
    font-size: 0.82rem;
    color: var(--text-muted);
}
.download-grid {
    display: grid;
    grid-template-columns: 1fr 1fr;
    gap: 1.5rem;
}
.download-card {
    padding: 1.8rem;
}
.code-copy-box {
    background: rgba(0, 0, 0, 0.5);
    border: 1px solid rgba(0, 240, 255, 0.2);
    border-radius: 6px;
    padding: 0.9rem;
    margin: 1rem 0;
    font-family: var(--font-mono);
    font-size: 0.82rem;
    color: var(--cyan);
    word-break: break-all;
}
.download-nav-btn {
    color: var(--cyan) !important;
    border-color: rgba(0, 240, 255, 0.3) !important;
}

/* ------------------------------------------------------------------------
```

```
   OMNICODE 3-TIER COMPOSITE HOVERCARD & DOCSTRING INSPECTOR
   ------------------------------------------------------------------------- */
.omni-hover-card {
    position: absolute;
    z-index: 10000;
    max-width: 480px;
    background: rgba(10, 15, 29, 0.94);
    backdrop-filter: blur(20px);
    -webkit-backdrop-filter: blur(20px);
    border: 1px solid rgba(0, 240, 255, 0.35);
    border-radius: 10px;
    box-shadow: 0 12px 40px rgba(0, 0, 0, 0.8), 0 0 20px rgba(0, 240, 255, 0.15);
    padding: 1.1rem;
    color: #e2e8f0;
    font-family: var(--font-sans, -apple-system, BlinkMacSystemFont, "Segoe UI", Roboto, sans-serif);
    font-size: 0.85rem;
    line-height: 1.5;
    pointer-events: auto;
    transition: opacity 0.15s ease, transform 0.15s ease;
}

.omni-hover-header {
    display: flex;
    align-items: center;
    justify-content: space-between;
    border-bottom: 1px solid rgba(255, 255, 255, 0.1);
    padding-bottom: 0.6rem;
    margin-bottom: 0.8rem;
}

.omni-hover-symbol {
    font-family: var(--font-mono, monospace);
    font-size: 1.05rem;
    font-weight: 700;
    color: #00f0ff;
    letter-spacing: 0.5px;
}

.omni-hover-rank-badge {
    display: inline-block;
    padding: 0.2rem 0.6rem;
    font-size: 0.72rem;
    font-weight: 600;
    border-radius: 4px;
    background: rgba(0, 240, 255, 0.15);
    color: #38bdf8;
    border: 1px solid rgba(56, 189, 248, 0.3);
    text-transform: uppercase;
}

.omni-hover-rank-badge.rank-1 {
    background: rgba(234, 179, 8, 0.18);
    color: #facc15;
    border-color: rgba(250, 204, 21, 0.4);
}

.omni-hover-tier {
    margin-bottom: 0.8rem;
    padding-bottom: 0.7rem;
    border-bottom: 1px solid rgba(255, 255, 255, 0.06);
}

.omni-hover-tier:last-child {
    margin-bottom: 0;
    padding-bottom: 0;
    border-bottom: none;
}

.omni-hover-tier-title {
    font-size: 0.75rem;
    font-weight: 700;
    text-transform: uppercase;
    letter-spacing: 0.8px;
    color: #94a3b8;
    margin-bottom: 0.4rem;
    display: flex;
    align-items: center;
    gap: 0.4rem;
```

```
}

.omni-hover-tier-title.tier-tape { color: #fbbf24; }
.omni-hover-tier-title.tier-omni { color: #34d399; }
.omni-hover-tier-title.tier-silicon { color: #c084fc; }

.omni-hover-prop {
    display: flex;
    margin-bottom: 0.25rem;
    font-size: 0.8rem;
}

.omni-hover-label {
    color: #64748b;
    width: 130px;
    flex-shrink: 0;
}

.omni-hover-val {
    color: #f1f5f9;
    font-family: var(--font-mono, monospace);
    word-break: break-word;
}

.omni-hover-aside {
    background: rgba(255, 255, 255, 0.04);
    border-left: 2px solid #38bdf8;
    padding: 0.35rem 0.6rem;
    margin: 0.4rem 0;
    font-style: italic;
    color: #cbd5e1;
    font-size: 0.78rem;
}

```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/terminal.html HTML 191 LINES 782 WORDS 10.8 KB

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <meta name="description" content="OmniCode Interactive Native Terminal & OS Process Scheduler — CreativeWorkzStudio LLC.">
    <title>OmniCode Interactive Terminal &amp;amp; Task Scheduler — CreativeWorkzStudio LLC</title>
    <link rel="preconnect" href="https://fonts.googleapis.com">
    <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
    <link href="https://fonts.googleapis.com/css2?family=Fira+Code:wght@400;500;600;700&family=Outfit:wght@300;400;500;600;700;800&family=Cinzel:wght@500;700;800&display=swap" rel="stylesheet">
    <link rel="stylesheet" href="/style.css">
</head>
<body class="terminal-body">
    <div class="app-layout terminal-page-layout">
        <!-- GLOBAL NAVIGATION HEADER -->
        <header class="app-header" id="app-header">
            <div class="header-left">
                <a href="/studio" class="brand-container">
                    <span class="brand-symbol">Ω</span>
                    <div class="brand-text">
                        <span class="brand-title">OMNICODE</span>
                        <span class="brand-subtitle">CREATIVEWORKZSTUDIO LLC</span>
                    </div>
                </a>
                <div class="status-pill" id="status-pill" title="Engine runs 100% offline with zero cloud telemetry">
                    <span class="status-dot"></span>
                    <span class="status-text">OFFLINE COVENANT ACTIVE</span>
                </div>
            </div>

            <nav class="app-nav" aria-label="Main Navigation">
                <a href="/studio" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M12 2L2 7l10 5 10-5-10-5zM2 17l10 5 10-5M2 12l10 5 10-5"/></svg>
                    AI Studio
                </a>
                <a href="/terminal" class="nav-tab active">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><polyline points="4 17 10 11 4 5"/><line x1="12" y1="19" x2="20" y2="19"/></svg>
                    CLI Terminal
                </a>
                <a href="/specs" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M14 2H6a2 2 0 0 0-2 2v16a2 2 0 0 0 2 2h12a2 2 0 0 0 2-2V8z"/><polyline points="14 2 14 8 20 8"/></svg>
                    Language Specs
                </a>
                <a href="/model" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M12 2a8 8 0 0 0-8 8c0 3.3 2 6.2 5 7.4V20a2 2 0 0 0 2 2h2a2 2 0 0 0 2-2v-2.6c3-1.2 5-4.1 5-7.4a8 8 0 0 0-8-8z"/></svg>
                    AI Model
                </a>
                <a href="/lexicon" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M4 19.5A2.5 2.5 0 0 1 6.5 17H20"/><path d="M6.5 2H20v20H6.5A2.5 2.5 0 0 1 4 19.5v-15A2.5 2.5 0 0 1 6.5 2z"/></svg>
                    Covenant Lexicon
                </a>
                <a href="/scrolls" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M19 21l-7-5-7 5V5a2 2 0 0 1 2-2h10a2 2 0 0 1 2 2z"/></svg>
                    Scrolls
                </a>
                <a href="/cloud" class="nav-tab">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M18 10h-1.26A8 8 0 1 0 9 20h9a5 5 0 0 0 0-10z"/></svg>
                    Cloud &amp;amp; Edge
                </a>
                <a href="/download" class="nav-tab download-nav-btn">
                    <svg width="15" height="15" viewBox="0 0 24 24" fill="none" stroke="currentColor" stroke-width="2"><path d="M21 15v4a2 2 0 0 1-2 2H5a2 2 0 0 1-2-2v-4"/><polyline points="7 10 12 15 17 10"/><line x1="12" y1="15" x2="12" y2="3"/></svg>
                    Download Native
```

```
                </a>
            </nav>
        </header>

        <!-- TERMINAL WORKSPACE MAIN -->
        <main class="terminal-workspace">
            <!-- TERMINAL CONTROL TOOLBAR -->
            <div class="terminal-toolbar card-glass">
                <div class="toolbar-left">
                    <span class="terminal-title-badge">Ω NATIVE USERSPACE TERMINAL</span>
                    <span class="sched-pill" id="sched-status-pill">
                        <span class="status-dot"></span>
                        <span id="sched-pill-text">Scheduler: Online (3 tasks)</span>
                    </span>
                    <span class="mem-pill" id="mem-pill">State: +1:PROCEED</span>
                </div>
                <div class="toolbar-actions">
                    <button class="btn btn-sm btn-ghost" id="btn-quick-demo">🧪 Demo</button>
                    <button class="btn btn-sm btn-ghost" id="btn-quick-lint">📋 Lint</button>
                    <button class="btn btn-sm btn-ghost" id="btn-quick-restore">🩹 Restore</button>
                    <button class="btn btn-sm btn-ghost" id="btn-quick-tasks">📊 Tasks (ps)</button>
                    <button class="btn btn-sm btn-ghost" id="btn-quick-tick">⚡ Tick</button>
                    <button class="btn btn-sm btn-danger-ghost" id="btn-clear-term">🧹 Clear (Ctrl+L)</button>
                </div>
            </div>

            <!-- DUAL VIEWPORT: TERMINAL SCREEN & SCHEDULER MONITOR -->
            <div class="terminal-grid">
                <!-- LEFT: LIVE INTERACTIVE CONSOLE -->
                <div class="terminal-console-pane card-glass">
                    <div class="console-screen" id="console-screen" tabindex="0">
                        <div class="term-intro">
================================================================================
  Ω OMNICODE INTERACTIVE USERSYSTEM SHELL &amp;amp; TASK SCHEDULER
  CreativeWorkzStudio LLC — Autonomous Neural-Symbolic Intelligence
  Engine: Rust Core 2024 (Balanced Radix-3 Quad-State Physics)
================================================================================
* Grounded in Biblical Moral Invariants &amp;amp; Symmetrical Covenant Bedrock
* Type 'help' for terminal commands, 'ps' for scheduler tasks, 'tick' to advance clock.
* Keyboard: Up/Down for command history | Tab for autocompletion | Ctrl+L to clear screen.
                        </div>
                        <div id="term-history-log"></div>
                    </div>

                    <!-- INTERACTIVE INPUT BAR -->
                    <div class="console-input-row" id="input-container">
                        <span class="term-prompt">omnicode&amp;gt;</span>
                        <input type="text" id="term-input" class="term-input" autocomplete="off" autofocus
spellcheck="false" placeholder="Type command (e.g. ps, spawn 'worker', let x = 42, omnicode demo, help)...">
                        <button class="btn btn-sm btn-accent" id="btn-term-send">Execute</button>
                    </div>
                </div>

                <!-- RIGHT: LIVE OS TASK SCHEDULER & PROCESS LEDGER -->
                <div class="scheduler-pane card-glass">
                    <div class="scheduler-pane-header">
                        <div class="sched-title-group">
                            <h2>Cooperative Task Scheduler</h2>
                            <p class="subtext">Active process table grounded in Balanced Radix-3 states</p>
                        </div>
                        <button class="btn btn-sm btn-secondary" id="btn-refresh-tasks">Refresh</button>
                    </div>

                    <!-- TASK SPAWN ROW -->
                    <div class="sched-spawn-box">
                        <input type="text" id="spawn-name-input" class="form-input-sm" placeholder="Task Name (e.g.
InvariantWatcher)">
                        <input type="text" id="spawn-cmd-input" class="form-input-sm" placeholder="Command (e.g. omnicode
lint manifest.omni)">
                        <select id="spawn-priority-select" class="form-select-sm">
                            <option value="NORMAL">Normal Priority</option>
                            <option value="HIGH">High Priority</option>
                            <option value="LOW">Low Priority</option>
                            <option value="BACKGROUND">Background</option>
                        </select>
                        <button class="btn btn-sm btn-accent" id="btn-spawn-task">+ Spawn</button>
                    </div>

```

```
                    <!-- TASK TABLE -->
                    <div class="task-table-wrapper">
                        <table class="task-table">
                            <thead>
                                <tr>
                                    <th>PID</th>
                                    <th>Task Name</th>
                                    <th>Priority</th>
                                    <th>Quad-State</th>
                                    <th>Ticks</th>
                                    <th>Actions</th>
                                </tr>
                            </thead>
                            <tbody id="task-tbody">
                                <!-- Populated dynamically via JS -->
                            </tbody>
                        </table>
                    </div>

                    <!-- IN-MEMORY SESSION VARIABLES -->
                    <div class="session-vars-box">
                        <div class="vars-header">
                            <h3>In-Memory Session Variables</h3>
                            <button class="btn btn-xs btn-ghost" id="btn-refresh-vars">Refresh Vars</button>
                        </div>
                        <div class="vars-content" id="session-vars-content">
                            <span class="dim-text">No session variables declared yet. Use 'let &lt;name&gt; =
&lt;value&gt;'</span>
                        </div>
                    </div>
                </div>
            </div>
        </main>

        <!-- FOOTER -->
        <footer class="app-footer">
            <div class="footer-left">
                <span class="footer-brand">Ω OMNICODE</span>
                <span class="footer-sep">&bull;</span>
                <span class="footer-copy">&copy; 2026 CreativeWorkzStudio LLC. All rights reserved.</span>
            </div>
            <div class="footer-center">
                <span>Native Userspace Shell &amp; Cooperative Quad-State Process Scheduler</span>
            </div>
            <div class="footer-right">
                <span class="footer-pill">Local Ring-3 Shell</span>
                <span class="footer-pill">v0.1.0</span>
            </div>
        </footer>
    </div>

    <script src="/terminal.js"></script>
</body>
</html>
```

<TRACK 3> : {Applications & OmniStudio Interfaces}/apps/gui/terminal.js JS 305 LINES 885 WORDS 11.9 KB

```
// ================================================================================
// BLOCK 1: METADATA BLOCK
// ( OmniCode Native Interactive Terminal & Task Scheduler JavaScript Engine )
// ================================================================================
/**
 * OmniCode Terminal & Scheduler Frontend Engine
 * CreativeWorkzStudio LLC
 * Zero external dependencies. Connects via standard HTTP JSON endpoints:
 *   - POST /api/terminal          -> Dispatches command to session & scheduler
 *   - GET  /api/scheduler         -> Retrieves live process ledger
 *   - POST /api/scheduler/spawn   -> Spawns new task
 *   - POST /api/scheduler/action  -> Mutates task state (pause, resume, kill)
 */

document.addEventListener("DOMContentLoaded", () => {
    const consoleScreen = document.getElementById("console-screen");
    const historyLog = document.getElementById("term-history-log");
    const termInput = document.getElementById("term-input");
    const btnSend = document.getElementById("btn-term-send");
    const btnClear = document.getElementById("btn-clear-term");
    const taskTbody = document.getElementById("task-tbody");
    const schedPillText = document.getElementById("sched-pill-text");
    const varsContent = document.getElementById("session-vars-content");

    // Command History & Autocomplete State
    const history = JSON.parse(localStorage.getItem("omnicode_terminal_history") || "[]");
    let historyIndex = history.length;

    const AUTOCOMPLETE_LIST = [
        "ps", "tasks", "spawn", "pause", "resume", "kill", "halt", "tick", "vars", "env",
        "let", "help", "clear",
        "omnicode demo",
        "omnicode lint manifest.omni",
        "omnicode restore manifest.omni",
        "omnicode manifest",
        "omnicode scrolls",
        "omnicode lexicon truth",
        "omnicode ai \"What is the covenant?\""
    ];

    // Focus input on console click
    consoleScreen.addEventListener("click", () => {
        termInput.focus();
    });

    // --------------------------------------------------------------------------
    // EXECUTION DISPATCHER
    // --------------------------------------------------------------------------
    async function executeCommand(cmd) {
        const clean = cmd.trim();
        if (!clean) return;

        // Save to history
        if (history.length === 0 || history[history.length - 1] !== clean) {
            history.push(clean);
            if (history.length > 100) history.shift();
            localStorage.setItem("omnicode_terminal_history", JSON.stringify(history));
        }
        historyIndex = history.length;

        // Handle local 'clear'
        if (clean.toLowerCase() === "clear") {
            historyLog.innerHTML = "";
            termInput.value = "";
            return;
        }

        // Render command prompt entry
        const entryEl = document.createElement("div");
        entryEl.className = "term-entry";
        entryEl.innerHTML = `
            <div class="term-command-line">
                <span class="term-prompt">omnicode&gt;</span>
                <span class="term-cmd-text">${escapeHtml(clean)}</span>
```

```
            </div>
            <div class="term-loading-spinner dim-text">Deliberating &amp;amp; evaluating...</div>
        `;
        historyLog.appendChild(entryEl);
        consoleScreen.scrollTop = consoleScreen.scrollHeight;
        termInput.value = "";

        const spinner = entryEl.querySelector(".term-loading-spinner");

        try {
            const resp = await fetch("/api/terminal", {
                method: "POST",
                headers: { "Content-Type": "application/json" },
                body: JSON.stringify({ command: clean })
            });

            const data = await resp.json();
            spinner.remove();

            const resultEl = document.createElement("div");
            resultEl.className = "term-result-box";

            const stateClass = getStateClass(data.state || "+1:PROCEED");
            const durationMs = (data.duration_us / 1000).toFixed(2);

            resultEl.innerHTML = `
                <div class="term-meta-bar">
                    <span class="badge ${stateClass}">${escapeHtml(data.state || "+1:PROCEED")}</span>
                    <span class="dim-text">${durationMs} ms</span>
                </div>
                <pre class="term-output-text">${formatTerminalOutput(data.stdout || "(Completed with zero output)")}
</pre>
            `;
            entryEl.appendChild(resultEl);
        } catch (err) {
            spinner.remove();
            const errEl = document.createElement("div");
            errEl.className = "term-error-box";
            errEl.innerHTML = `<pre class="text-red">✗ Error dispatching command: ${escapeHtml(err.message)}</pre>`;
            entryEl.appendChild(errEl);
        }

        consoleScreen.scrollTop = consoleScreen.scrollHeight;
        refreshSchedulerTasks();
        refreshVariables();
    }

    // ---------------------------------------------------------------------------
    // SCHEDULER TASK POLLING & ACTIONS
    // ---------------------------------------------------------------------------
    async function refreshSchedulerTasks() {
        try {
            const resp = await fetch("/api/scheduler");
            if (!resp.ok) return;
            const tasks = await resp.json();

            taskTbody.innerHTML = "";
            let activeCount = 0;

            tasks.forEach(t => {
                if (t.state === "+1:PROCEED") activeCount++;
                const tr = document.createElement("tr");
                const stateClass = getStateClass(t.state);

                tr.innerHTML = `
                    <td class="mono font-bold">${t.id}</td>
                    <td title="${escapeHtml(t.command)}"><strong>${escapeHtml(t.name)}</strong></td>
                    <td><span class="badge badge-subtle">${escapeHtml(t.priority)}</span></td>
                    <td><span class="badge ${stateClass}">${escapeHtml(t.state)}</span></td>
                    <td class="mono">${t.ticks}</td>
                    <td class="action-cell">
                        ${t.state === "+1:PROCEED"
                            ? `<button class="btn btn-xs btn-ghost btn-pause" data-id="${t.id}" title="Pause
(0:AWAIT)">⏸</button>`
                            : `<button class="btn btn-xs btn-ghost btn-resume" data-id="${t.id}" title="Resume
(+1:PROCEED)">▶</button>`}
                        ${t.state !== "NULL:HALT"
                            ? `<button class="btn btn-xs btn-danger-ghost btn-halt" data-id="${t.id}" title="Terminate
```

```
(NULL:HALT)">■</button>`
                            : `<span class="dim-text">Ended</span>`}
                    </td>
                `;
                taskTbody.appendChild(tr);
            });

            schedPillText.textContent = `Scheduler: Online (${tasks.length} tasks, ${activeCount} active)`;

            // Attach action listeners
            document.querySelectorAll(".btn-pause").forEach(b => {
                b.onclick = () => mutateTask(b.dataset.id, "pause");
            });
            document.querySelectorAll(".btn-resume").forEach(b => {
                b.onclick = () => mutateTask(b.dataset.id, "resume");
            });
            document.querySelectorAll(".btn-halt").forEach(b => {
                b.onclick = () => mutateTask(b.dataset.id, "halt");
            });
        } catch (e) {
            console.error("Scheduler fetch error:", e);
        }
    }

    async function mutateTask(id, action) {
        await executeCommand(`${action} ${id}`);
    }

    async function refreshVariables() {
        try {
            const resp = await fetch("/api/terminal", {
                method: "POST",
                headers: { "Content-Type": "application/json" },
                body: JSON.stringify({ command: "vars" })
            });
            const data = await resp.json();
            varsContent.innerHTML = `<pre class="mono-code">${escapeHtml(data.stdout || "No session variables")}</pre>`;
        } catch (e) {
            console.error(e);
        }
    }

    // ---------------------------------------------------------------------------
    // KEYBOARD NAVIGATION & SHORTCUTS
    // ---------------------------------------------------------------------------
    termInput.addEventListener("keydown", (e) => {
        // Enter to execute
        if (e.key === "Enter") {
            e.preventDefault();
            executeCommand(termInput.value);
            return;
        }

        // Up arrow (history backward)
        if (e.key === "ArrowUp") {
            e.preventDefault();
            if (historyIndex > 0) {
                historyIndex--;
                termInput.value = history[historyIndex] || "";
            }
            return;
        }

        // Down arrow (history forward)
        if (e.key === "ArrowDown") {
            e.preventDefault();
            if (historyIndex < history.length - 1) {
                historyIndex++;
                termInput.value = history[historyIndex] || "";
            } else {
                historyIndex = history.length;
                termInput.value = "";
            }
            return;
        }

        // Tab autocomplete
        if (e.key === "Tab") {
```

```
            e.preventDefault();
            const val = termInput.value.trim().toLowerCase();
            if (!val) return;
            const match = AUTOCOMPLETE_LIST.find(item => item.toLowerCase().startsWith(val));
            if (match) {
                termInput.value = match;
            }
            return;
        }

        // Ctrl + L (Clear)
        if (e.ctrlKey && e.key.toLowerCase() === "l") {
            e.preventDefault();
            historyLog.innerHTML = "";
            return;
        }
    });

    btnSend.addEventListener("click", () => {
        executeCommand(termInput.value);
    });

    btnClear.addEventListener("click", () => {
        historyLog.innerHTML = "";
        termInput.focus();
    });

    // Toolbar Quick Action Buttons
    document.getElementById("btn-quick-demo")?.addEventListener("click", () => executeCommand("omnicode demo"));
    document.getElementById("btn-quick-lint")?.addEventListener("click", () => executeCommand("omnicode lint
manifest.omni"));
    document.getElementById("btn-quick-restore")?.addEventListener("click", () => executeCommand("omnicode restore
manifest.omni"));
    document.getElementById("btn-quick-tasks")?.addEventListener("click", () => executeCommand("ps"));
    document.getElementById("btn-quick-tick")?.addEventListener("click", () => executeCommand("tick"));
    document.getElementById("btn-refresh-tasks")?.addEventListener("click", refreshSchedulerTasks);
    document.getElementById("btn-refresh-vars")?.addEventListener("click", refreshVariables);

    // Spawn Task Button
    document.getElementById("btn-spawn-task")?.addEventListener("click", () => {
        const nameInput = document.getElementById("spawn-name-input");
        const cmdInput = document.getElementById("spawn-cmd-input");
        const prioSelect = document.getElementById("spawn-priority-select");

        const cmd = cmdInput.value.trim();
        if (!cmd) return;

        executeCommand(`spawn ${cmd}`);
        cmdInput.value = "";
        nameInput.value = "";
    });

    // Helper functions
    function getStateClass(state) {
        if (!state) return "badge-proceed";
        if (state.includes("PROCEED")) return "badge-proceed";
        if (state.includes("AWAIT")) return "badge-await";
        if (state.includes("ROLLBACK")) return "badge-rollback";
        if (state.includes("HALT")) return "badge-halt";
        return "badge-proceed";
    }

    function escapeHtml(str) {
        return (str || "")
            .replace(/&/g, "&amp;")
            .replace(/</g, "&lt;")
            .replace(/>/g, "&gt;")
            .replace(/"/g, "&quot;")
            .replace(/'/g, "&#039;");
    }

    function formatTerminalOutput(text) {
        return escapeHtml(text);
    }

    // Initial scheduler poll & timer
    refreshSchedulerTasks();
    refreshVariables();
```

```
    setInterval(refreshSchedulerTasks, 4000);
});
```

OmniCode: Chapter 19: Track 4 & 5 - Immutable Data & Infrastructure

Canonical Bibles, OCI Scripts, Toolchain & CI/CD

CHAPTER IDENTIFIER
CH 19

NOTEBOOKLM WORD COUNT
24,763 words

CATALOGED CHAPTER FILES
39 files (4,867 lines)

GENERATION DATE
2026-10-16 20:36:12

EPISTEMIC COVENANT BEDROCK & IMMUTABLE LANDMARKS

"And he gave unto Moses... two tables of testimony, tables of stone, written with the finger of God." — Exodus 31:18
"Prepare thy work without, and make it fit for thyself in the field; and afterwards build thine house." — Proverbs 24:27
"Remove not the ancient landmark, which thy fathers have set." — Proverbs 22:28

GOOGLE NOTEBOOKLM GROUNDING FOCUS & LEARNING PROMPT

- **Chapter Focus:** *"How does infrastructure preserve immutable scriptural anchors?"*
- **Architectural Rule:** All definitions conform to 4-block structure & spatial ruler.

CHAPTER MANIFEST & INDEX (39 FILES)

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
1	**<TRACK 5> : {Infrastructure, Operations & Archives}/TRACK.md**	MD	12	57	0.5
2	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/README.md**	MD	149	1,286	9.5
3	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/dev_log.md**	MD	319	2,742	22.3
4	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/01_foundations/01_ontological_principles.md**	MD	52	344	2.4
5	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/01_foundations/02_boundary_types_and_asides.md**	MD	57	390	2.7
6	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/01_foundations/03_eight_parts_of_speech_matrix.md**	MD	255	2,207	19.8
7	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/04_cognitive_and_autonomous_systems/01_ai_cortex_and_neural_symbolic_loop.md**	MD	118	607	5.4
8	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/04_cognitive_and_autonomous_systems/02_episodic_scrolls_and_experiential_learning.md**	MD	130	573	5.2
9	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/04_cognitive_and_autonomous_systems/03_autonomous_restorator_and_self_healing.md**	MD	111	570	4.6
10	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/04_cognitive_and_autonomous_systems/04_bare_metal_and_cross_platform_toolchain.md**	MD	68	382	3.0
11	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/04_cognitive_and_autonomous_systems/05_core_standard_libraries.md**	MD	64	333	2.7
12	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/03_architecture/01_coordinate_system_of_computation.md**	MD	39	212	1.7
13	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/03_architecture/02_execution_pipeline.md**	MD	56	507	3.9
14	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/03_architecture/03_four_block_architecture.md**	MD	134	739	6.4
15	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/02_logic_and_algebra/01_balanced_ternary_quad_state.md**	MD	76	536	3.3
16	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/02_logic_and_algebra/02_relational_connectives_and_operators.md**	MD	56	365	2.2
17	**<TRACK 5> : {Infrastructure, Operations & Archives}/docs/02_logic_and_algebra/03_the_quad_state_accumulator_loop_and_named_registers.md**	MD	259	2,254	17.9
18	**<TRACK 5> : {Infrastructure, Operations & Archives}/infra/systemd/omnicode-web.service**	SERVICE	22	34	0.5
19	**<TRACK 5> : {Infrastructure, Operations & Archives}/infra/docker/Dockerfile**	TEXT	178	947	7.8
20	**<TRACK 5> : {Infrastructure, Operations & Archives}/infra/docker/docker-compose.yml**	YML	113	650	5.7
21	**<TRACK 5> : {Infrastructure, Operations & Archives}/infra/scripts/check_toolchain.sh**	SH	57	227	2.5
22	**<TRACK 5> : {Infrastructure, Operations & Archives}/infra/scripts/deploy_oracle_cloud.sh**	SH	160	721	7.0
23	**<TRACK 5> : {Infrastructure, Operations & Archives}/infra/scripts/oci_security_list_helper.sh**	SH	87	474	4.1
24	**<TRACK 5> : {Infrastructure, Operations & Archives}/infra/scripts/omnicode_gui.sh**	SH	16	53	0.5
25	**<TRACK 5> : {Infrastructure, Operations & Archives}/infra/scripts/package_native.sh**	SH	125	395	4.2
26	**<TRACK 5> : {Infrastructure, Operations & Archives}/infra/scripts/setup_cloudflare_tunnel.sh**	SH	194	713	6.8
27	**<TRACK 5> : {Infrastructure, Operations & Archives}/infra/scripts/sync_oracle_vm.sh**	SH	133	577	5.6
28	**<TRACK 5> : {Infrastructure, Operations & Archives}/infra/dns/README.md**	MD	71	380	2.9
29	**<TRACK 5> : {Infrastructure, Operations & Archives}/infra/dns/omnicodestudio.com.zone**	ZONE	49	249	2.6
30	**<TRACK 5> : {Infrastructure, Operations & Archives}/infra/dns/zone_manager.py**	PY	269	925	10.7
31	**<TRACK 4> : {Variable Storage & Episodic Memory}/TRACK.md**	MD	10	62	0.5

#	FILE PATH	TYPE	LINES	WORDS	SIZE (KB)
32	**<TRACK 4> : {Variable Storage & Episodic Memory}/storage/weights/cpisi_base.weights**	WEIGHTS	214	220	2.2
33	**<TRACK 4> : {Variable Storage & Episodic Memory}/storage/data/immutable_documentation/English Standard Bible - Complete.pdf**	PDF	1	10	12873.5
34	**<TRACK 4> : {Variable Storage & Episodic Memory}/storage/data/immutable_documentation/Ethiopian Bible - Complete.pdf**	PDF	1	9	10846.6
35	**<TRACK 4> : {Variable Storage & Episodic Memory}/storage/data/immutable_documentation/King James Bible - Complete.pdf**	PDF	1	10	12193.6
36	**<TRACK 4> : {Variable Storage & Episodic Memory}/storage/data/immutable_documentation/New King James Bible - Complete.pdf**	PDF	1	11	6624.0
37	**<TRACK 4> : {Variable Storage & Episodic Memory}/storage/data/immutable_documentation/World English Bible - Complete.pdf**	PDF	1	10	11440.6
38	**scripts/build_notebooklm_pdf.sh**	SH	76	329	3.1
39	**scripts/export_notebooklm_pdf.py**	PY	1,133	3,653	39.0

<TRACK 5> : {Infrastructure, Operations & Archives}/TRACK.md MD 12 LINES 57 WORDS 0.5 KB

```
# <TRACK 5> : {Infrastructure, Operations & Archives}

## Scope & Invariant

Operations, containerization, DNS synchronization, packaging, and daemon management.

- `infra/dist/`: Standalone distribution packages (`.tar.gz`).
- `infra/dns/`: Dynamic DNS synchronization scripts & zone records.
- `infra/docker/`: Multi-architecture containerization and composition topologies.
- `infra/scripts/`: Toolchain packaging, cloud synchronization, and deployment automation.
- `infra/systemd/`: Production daemon service definitions.
```

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/README.md MD 149 LINES 1286 WORDS 9.5 KB

```
# OmniCode Language: Foundational Documentation Series

Welcome to the architectural and theoretical specification of the **OmniCode Language**, a dual-readable, multi-tier programming language engineered for direct human comprehension and deterministic machine execution, grounded in the principles of **Formal Ontology**, **Set Theory**, and **Balanced Ternary Logic**, powered by a high-performance **Rust Core Engine**.

OmniCode bridges the entire spectrum of computing—operating with zero-overhead control at the bare-metal low level, while natively expressing high-level mathematical abstractions, declarative logic, balanced ternary state machines, and machine-readable cognitive intent.

---

## 1. Documentation Index & Topology

The specification is organized into four comprehensive volumes:

### [Volume 1: Foundations](01_foundations/)

* **[01. Ontological Principles & Set Theory](01_foundations/01_ontological_principles.md):** The philosophical and mathematical basis of entities, intrinsic essence vs. extrinsic context, and set comprehension.
* **[02. Boundary Types & Asides](01_foundations/02_boundary_types_and_asides.md):** The 6 morphological boundary delimiters (`[]`, `<>`, `{}`, `{]`, `[}`, `()`), the elimination of dead comments, and machine-readable intent.
* **[03. The 8 Parts of Speech & Grammatical Matrix](01_foundations/03_eight_parts_of_speech_matrix.md):** Universal linguistic grounding, the 8-word sentence proof, CS counterparts, and primary/secondary grammatical roles.

### [Volume 2: Logic & Algebra](02_logic_and_algebra/)

* **[01. Balanced Ternary & The Quad-State Engine](02_logic_and_algebra/01_balanced_ternary_quad_state.md):** The 4-state execution truth space (`-1` Rollback, `0` Await, `+1` Proceed, `NULL` Halt), algebraic negation, and physics-driven control flow.
* **[02. Relational Connectives & Operators](02_logic_and_algebra/02_relational_connectives_and_operators.md):** The connective algebra (`!` But, `::` And, `:` In relation to, `|` Or, `--` Not) and state relations (`=` Is, `!=` Is not, `≈` Liken to).

### [Volume 3: Architecture & Execution](03_architecture/)

* **[01. The 3D Coordinate System of Computation](03_architecture/01_coordinate_system_of_computation.md):** The three orthogonal axes: Being (Ontology), Dynamics (Causality: `-->` and `<--`), and Scale (Layering: `^--` builds to, `v--` breaks down from).
* **[02. The Unified Execution Pipeline](03_architecture/02_execution_pipeline.md):** How a single AST and IR seamlessly feeds AOT Native Compilation (LLVM), Real-time Interpretation (REPL/VM), and Cross-Platform Transpilation (C/WASM).
* **[03. The Universal 4-Block Architecture & Rust Foundation](03_architecture/03_four_block_architecture.md):** The deterministic 4-block file lifecycle (`Metadata` $\to$ `Opening` $\to$ `Body` $\to$ `Closing`), the `OmniLinter`, and the technical rationale for using Rust as the core foundation.

### [Volume 4: Cognitive & Autonomous Systems](04_cognitive_and_autonomous_systems/)

* **[01. The AI Cortex & Neural-Symbolic Transduction Loop](04_cognitive_and_autonomous_systems/01_ai_cortex_and_neural_symbolic_loop.md):** The end-to-end cognitive loop transforming natural language prompts into canonical 4-Block Turing reels, executing with quad-state determinism, and producing dual logs.
* **[02. Episodic Scrolls & Experiential Learning Archive](04_cognitive_and_autonomous_systems/02_episodic_scrolls_and_experiential_learning.md):** The dual inscription model (`.scroll` executable reels and `.log` telemetry) and `AILearner` episodic memory digestion.
* **[03. The Restorator & Autonomous Self-Healing Diagnostics](04_cognitive_and_autonomous_systems/03_autonomous_restorator_and_self_healing.md):** Autonomous boundary auto-healing, delimiter ranking hierarchy, missing block auto-scaffolding, and transactional rollback protection.
* **[04. Bare-Metal OS & Cross-Platform Toolchains](04_cognitive_and_autonomous_systems/04_bare_metal_and_cross_platform_toolchain.md):** Bare-metal targets (`x86_64`, `aarch64`, `riscv64gc`), QEMU hardware emulation, Docker toolchain, and ISO bootloaders.
* **[05. Core Standard Library Architecture](04_cognitive_and_autonomous_systems/05_core_standard_libraries.md):** Specification of the built-in standard library in `lib/core/` (`arithmetic.omni`, `logic.omni`, `vectors.omni`, `memory.omni`).

---

## 2. Symbol & Operator Matrix

| Axis / Domain | Symbol | Syntax Example | Meaning |
| :--- | :---: | :--- | :--- |
| **Being (Y-Axis)** | `=` | `a = b` | Identity assertion (True if identical) |
| | `!=` | `a != b` | Distinctness assertion (True if distinct) |
| | `~=` / `≈` | `a ~= b` | Homomorphism / Structural similarity |
| **Dynamics (X-Axis)** | `-->` | `a --> b` | Forward causality: 'a' acts upon 'b' |
| | `<--` | `b <-- a` | Retroactive feedback: 'b' reflects upon 'a' |
| **Scale (Z-Axis)** | `^--` | `a ^-- A` | Micro-to-Macro: 'a' builds up to 'A' |
| | `v--` | `A v-- a` | Macro-to-Micro: 'A' breaks down into 'a' |
| **Connective Algebra** | `!` | `a --> b ! [ c = +1 ]` | Adversative caveat (**BUT** condition) |
| | `::` | `a : A :: b : B` | Conjunction (**AND** / Consensus) |
| | `:` | `a : A` | Ontological aspect (**IN RELATION TO**) |
| | `\|` | `a \| b` | Disjunction (**OR**) |
| | `--` | `-- a` | Algebraic negation (**NOT**) |
| **Morphological Boundaries** | `[...]` | `[ data ]` | Rigid / Fixed / Physical Denotation |
| | `<...>` | `< type >` | Dynamic / Fluid / Invariant Process |
```

```
| | `{...}` | `{ universe }` | Universal / Ambient Context / Scope |
| | `{...]` | `{ A ]` | Top-Down / Absorber (Fluid in $\to$ Fixed out) |
| | `[...}` | `[ B }` | Bottom-Up / Generator (Fixed in $\to$ Fluid out) |
| | `(...)` | `( intent aside )` | First-class Aside (Machine-readable intent) |
| **Balanced Ternary Truth** | `+1` | `+1` / `PROCEED` | Monotonic forward commit |
| | `0` | `0` / `AWAIT` | Indeterminate / Awaiting consensus |
| | `-1` | `-1` / `ROLLBACK` | Transactional contra / Veto / Rollback |
| | `NULL` | `NULL` / `HALT` | Terminal absorbing trap / Void |

---

## 3. Canonical Showcase: [`examples/canonical_notation.omni`](file:///home/professorseanex/OmniCode/examples/canonical_notation.omni)

```omni
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ================================================================================
Module < CanonicalNotationShowcase > ( Foundations of Being, Causality, and Abstraction ) {
    version: < "1.0.0" >,
    author: < "ProfessorSeanEX" >,
    system: < OmniCode.Core >,
    semantics: < BalancedTernary :: QuadState :: BoundaryPhysics >
}

A < +1 > ( Invariant category A: axiomatic ground truth )
B < +1 > ( Invariant category B: independent set domain )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [ MemoryAligned :: TypeChecking ],
    initial_truth: [ +1 ]
}

a [ +1 ] ( Particular instance 'a' with mutable state )
b [ +1 ] ( Particular instance 'b' with mutable state )
a_in_A [ a ] { A }  ( Instance 'a' validated within contextual universe A )
a_top_down { A }    ( Outside-In: Environment A actively forces definition of a )
b_bottom_up [ B }   ( Inside-Out: Definition of b emerges from context B )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    instance_typing [ a : A ]    ( 'a' stands in relation to Category A )
    identity_check [ a = a ]     ( 'a' is identical to 'a' )
    distinction_check [ a != b ] ( 'a' is not 'b' )
    similarity_check [ a ~= b ]  ( 'a' is liken to 'b' in form )

    forward_action [ a --> b ]   ( 'a' acts upon 'b' forward in time )
    feedback_action [ b <-- a ]  ( 'b' reflects back upon 'a' as retroactive feedback )

    synthesis [ a ^-- A ]        ( Low-level primitive 'a' builds up to concept A )
    decomposition [ A v-- a ]    ( Category A decomposes down into primitive 'a' )

    negation [ -- a ]
    conjunction [ a : A :: b : B ]
    pipeline [ a --> b ! [ a : A :: b : B ] ] ( 'a' acts on 'b', BUT caveat must hold )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        identity_check = +1 ::
        forward_action = +1 ::
        pipeline = +1
    ],
    commit_status: [ +1 ] ( Final transaction verification: Proceed )
}
```

---

4. Verification Suite & Invariant Seal

The theoretical specifications in this documentation are backed by executable code and passing unit/integration tests in the Rust core:

* **24 Automated Tests:**
```

```
   139    * Unit tests validating boundary hierarchies, vector parsers, and quad-state logic in [`src/lib.rs`]
(file:///home/professorseanex/OmniCode/src/lib.rs).
   140    * 17 Failpoint integration tests in [`tests/test_failpoints.rs`]
(file:///home/professorseanex/OmniCode/tests/test_failpoints.rs).
   141    * 2 AI Cortex and Episodic Learner integration tests in [`tests/test_ai_model.rs`]
(file:///home/professorseanex/OmniCode/tests/test_ai_model.rs).
   142  * **CLI Diagnostic Tools:**
   143    * `omnicode lint <file>`: Enforces 4-Block architectural compliance.
   144    * `omnicode restore <file>`: Autonomous self-healing verification.
   145    * `omnicode ai "<prompt>"`: Cognitive loop verification.
   146    * `omnicode scrolls`: Episodic memory archive verification.
   147
   148  All specifications herein are invariant and formally sealed.
```

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/dev_log.md MD 319 LINES 2742 WORDS 22.3 KB

```
# OmniCode: Engineering & Architectural Developer Log

This log chronicles the architectural decisions, theoretical discoveries, and implementation milestones of the **OmniCode Language, Runtime, and Operating System Foundation**.

---

## [2026-10-10] Milestone 14: Operating System Genesis, Multi-Track Scheduler & Process Tape Execution

### 1. Physical Computing Hierarchy: Roll $\longrightarrow$ Tape $\longrightarrow$ Track

* **The Breakthrough:** Transformed OmniCode from symbolic physics into a living, bootable Operating System:
  * **Roll (`Roll`):** A single line of code / atomic state mutation in silicon memory.
  * **Tape (`Tape` / `.tape`):** A sequential process ribbon consisting of a leading **Tape Head** covenant and an ordered stream of subordinate rolls.
  * **Track (`Track`):** An execution channel. The scheduler provides 3 discrete physical channels:
    * `Track 0 [KERNEL]`: Hardware initialization, genesis daemons, protected kernel space.
    * `Track 1 [TERMINAL]`: Interactive console HUD, REPL environment, video buffers.
    * `Track 2 [APP]`: Userspace applications, background workers, cognitive models.

### 2. Genesis Boot Covenant (`lib/kernel/boot.tape`)

* Created the primordial OS boot sequence ribbon:
  * Declares the 4096 physical cell `Root_RAM` storehouse.
  * Carves the protected `Kernel_Partition` (1024 cells) and `Terminal_Partition` (512 cells) via `v--` Storehouse partitioning.
  * Establishes initial kernel equilibrium state at cell 0 (`0 --> Kernel_Partition @ 0`).
  * Seals the boot sequence with `commit_status [ PROCEED ]`.

### 3. Living In-Memory Terminal Shell & Cooperative Scheduler

* Upgraded [`OmniScheduler`](file:///home/professorseanex/OmniCode/src/terminal/scheduler.rs) and [`TerminalSession`](file:///home/professorseanex/OmniCode/src/terminal/session.rs):
  * Multi-track process scheduling with priority queues (`High`, `Normal`, `Low`, `Background`).
  * Direct commands: `mount <path.tape>`, `run <path.tape>`, `step <pid>`, `rolls <pid>`, `mem`, `tracks`.
  * Evaluates live OmniCode rolls directly in silicon memory without subprocess overhead, maintaining persistent `Environment` bindings.

### 4. CLI Execution & End-to-End Functional Verification

* Upgraded CLI `omnicode run <path.tape>` to mount and step process tapes roll-by-roll.
* Added `test_genesis_boot_tape_execution` and `test_terminal_session_boot_and_tape_commands` in [`tests/functional/main.rs`](file:///home/professorseanex/OmniCode/tests/functional/main.rs).
* **Test Suite Status:** All 47 tests passing (16 in `lib.rs`, 7 functional, 14 integrated, 10 unit) with zero warnings and zero regressions.

---

## [2026-10-10] Milestone 13: AIMemory Store, Biblical Ground Truth & Thought Formulation Engine

### 1. Dedicated AI Memory Store (`src/ai/model/memory.rs`)

* **The Architecture:** Created [`AIMemory`](file:///home/professorseanex/OmniCode/src/ai/model/memory.rs) as the dedicated repository for the internal AI model's cognitive state:
  * **Primordial Ground Truth:** Anchored in [`BiblicalLexicon`](file:///home/professorseanex/OmniCode/src/ai/lexicon.rs) (KJV/WEB public domain scriptures across 6 ontological domains: Cosmology, LivingWorld, HumanCondition, MoralVirtue, MoralVice, CausalLaw).
  * **Associative Concept Graph:** Seeds foundational connections (`light`, `storehouse`, `cell`, `restoration`, `tape`, `wisdom`, `measure`) and allows dynamic association learning.
  * **Episodic Scrolls Store:** Ingests historical `.scroll` files from `runtime/scrolls/` and inscribes newly formulated thought scrolls.
  * **Working Thought Space:** Records active thoughts formulated by the AI model.

### 2. Native Thought Formulation in OmniCode Syntax

* The internal AI model formulates thoughts directly in OmniCode syntax rather than unstructured natural language or opaque neural embeddings:
  * Employs the **6 Cardinal Classification Clauses**: `WHO` (Internal_AI), `WHAT` (CognitiveAction), `WHEN` (Lifecycle phase), `WHERE` (Target Vessel), `WHY` (Scripture / Invariant anchor), `HOW` (Balanced Ternary Quad-State + Guidance).
  * Synthesizes executable **Thought Tapes**:

    ```omnicode
    [Thought.th_001] : WHO {Internal_AI} --> DELIBERATE {CognitiveThought_light}
        WHEN {Opening}
        WHERE {Cortex_Memory} = [ light ]
        WHY ( Genesis 1:3 - 'And God said, Let there be light: and there was light.' )
        HOW [ PROCEED : Walk in the light; transparent and lawful boundaries. ]
        :: < manifest > ( illumination )
    ```
```

```
    * Enforces moral evaluation: Constructive prompts deliberate `+1: PROCEED`; malicious prompts (e.g., deceit, theft, harm) deliberate `-1: ROLLBACK` or `NULL: HALT`.

### 3. DiagnosticLogger Upgrade: Sensory Bridge to Memory & Scrolls

* Upgraded [`DiagnosticLogger`](file:///home/professorseanex/OmniCode/src/diagnostics/logger.rs):
  * `log_thought()`: Automatically structures thoughts into episodic `CognitiveNote` records tagged `#thought` and `#ai_cortex`.
  * `log_memory_association()`: Inscribes associative links between entities and scriptural/scroll anchors.
  * `log_scroll_inscribed()`: Logs physical `.scroll` generation.
  * `inscribe_canonical_scroll()`: Directly generates and writes valid 4-Block `.scroll` files to disk.

### 4. AICortex Integration & Test Verification

* Integrated `AIMemory` directly into [`AICortex`](file:///home/professorseanex/OmniCode/src/ai/model/cortex.rs):
  * Deliberates prompt through `formulate_thought()` prior to semantic transduction.
  * Automatically refreshes episodic memory via `digest_scrolls()` after saving execution scrolls.
* Added `test_ai_memory_and_thought_formulation` in [`tests/unit/main.rs`](file:///home/professorseanex/OmniCode/tests/unit/main.rs).
* **Test Suite Status:** All 44 tests passing (15 in `lib.rs`, 5 functional, 14 integrated, 10 unit) with zero warnings.

---

## [2026-10-10] Milestone 12: The AI Cognitive Loop, Episodic Scrolls & Native Thought Formulation

### 1. The Native Linguistic Identity of the AI Model

* **The Breakthrough:** Traditional operating systems treat AI as an external userland Python process, creating an irreconcilable semantic translation tax. In OmniCode, **the language of the internal AI model is the exact same language as the Operating System kernel.**
* Both speak the 8 parts of speech, 8-slot canonical sentences, and balanced ternary physics (`PROCEED`, `AWAIT`, `ROLLBACK`, `HALT`).
* When the internal AI formulates a thought, it writes it in **native OmniCode**, meaning an AI thought can be scheduled directly onto hardware as a **Tape**!

### 2. The Role of the Scrolls (`.scroll`) as Episodic Memory

* A `.scroll` is an **Episodic Memory Chronicle**:
  * Records the session prompt, executed rolls, quad-state outcomes, failpoints, applied repairs, and first-class Asides `(...)`.
  * Preserves **WHY** code was written, so the AI accumulates experiential memory over time.
  * `AILearner` digests `.scroll` files to build training memories anchored to the `BiblicalLexicon`.
  * The AI formulates new deductions directly from its past experiences and memory scrolls.

### 3. The Triune Diagnostic Nervous System

* **Logger (Sensory Organ):** Observes every vector mutation and records episodic scrolls into `scrolls/`.
* **Debugger (Conscious Auditor):** Monitors invariant boundaries (`{...}`) and enforces the 7 Invariant Covenant Laws.
* **Restorator (Self-Healing Cortex):** Reads the Tape Head and past memory scrolls to synthesize autonomous fixes when a `-1: ROLLBACK` occurs, preventing kernel crashes.

---

## [2026-10-10] Milestone 11: Cardinal Classification Clauses, Spatial Vector Modulations & `v--` Partitioning

### 1. The 6 Cardinal Classification Clauses (The 5 W's and 1 H)

* **The Problem:** Program statements often lack clear dimensionality (who runs it, when it executes, where it is stored, why it exists, how it mutates).
* **The Solution:** Codified `WHO`, `WHAT`, `WHEN`, `WHERE`, `WHY`, and `HOW` as first-class classification clauses in both the Long Form and Sentence Form:
  * `WHO`: Agent / Caller / Security Principal (`WHO self`).
  * `WHAT`: Entity / Vessel / Payload (`WHAT [Cell]`).
  * `WHEN`: Cadence / Trigger / Lifecycle phase (`WHEN Opening`).
  * `WHERE`: Spatial site / Memory address / Invariant bounds (`WHERE {unit}`).
  * `WHY`: Teleological intent / Axiom link (`WHY ( Safe placement )`).
  * `HOW`: Causal mechanism / Transducer cycle (`HOW [ 8 bit --> 5 trit --> 8 bit ]`).

### 2. Spatial Directional Vector Geometry & 2D Quadrants

* **The Problem:** Horizontal arrows (`-->`, `<--`) only capture 1D data movement. Real spatial computation requires multi-scale elevation, destructuring, and 2D/3D coordinate motion.
* **The Solution:** Added 8 new directional vectors to [`src/core/operators.rs`](file:///home/professorseanex/OmniCode/src/core/operators.rs):
  * Scale Modulations: `/-^` (Major), `\-v` (Minor), `\-^` (Great), `/-v` (Small).
  * 2D Quadrant / Compass Vectors: `/^` (Quadrant I: $+X, +Y$), `\v` (Quadrant IV: $+X, -Y$), `^\` (Quadrant II: $-X, +Y$), `v/` (Quadrant III: $-X, -Y$).
  * Range Span Operator: `..` (`[ 0 .. 256 ]`).

### 3. Runtime Storehouse Partitioning (`v--`)

* Wired the `BreaksDownFrom` (`v--`) operator in [`src/runtime/evaluator.rs`](file:///home/professorseanex/OmniCode/src/runtime/evaluator.rs) to directly carve child memory partitions from parent storehouses:
  * `Storehouse v-- Scratchpad [ 256 ]` calls `Storehouse::partition("Scratchpad", 256)`, tracking origins and preventing out-of-bounds leaks.
```

```
  * Added `test_cardinal_clauses_and_spatial_directionals_and_partitioning` in [`tests/unit/main.rs`](file:///home/professorseanex/OmniCode/tests/unit/main.rs).
  * All 43 automated unit, functional, and integrated tests pass with zero errors.

---

## [2026-10-10] Milestone 10: 8-Slot Canonical Sentence Architecture & ASCII Operator Specialization

### 1. The 8-Slot Canonical Sentence Architecture

* **The Problem:** An arbitrary sentence length or rigid 3-part imperative statement (`subj verb obj`) cannot naturally house invariants, execution cadences, spatial prepositions, or error traps without clumsy decorators, macros, or ad-hoc keywords.
* **The Solution:** Formalized the **8-Slot Canonical Sentence Architecture** matching 1:1 with the 8 parts of speech:
  * **Slot 1 (Interjection):** Alert / Trap / Teleological Aside (`Oh!`, `( Intent )`, `HALT`).
  * **Slot 2 (Conjunction):** Pipeline transition / Linkage / Consensus (`::`, `&`).
  * **Slot 3 (Pronoun):** Context handle / Scoped caller identity (`self`, `it`, `origin`).
  * **Slot 4 (Adjective):** Invariant contract / Axiom qualifier (`{ Pure }`, `< Axiom >`, `PROCEED`).
  * **Slot 5 (Noun):** Subject substance / Vessel container / Data operand (`Gold`, `Storehouse`, `Cell`).
  * **Slot 6 (Verb):** Causal vector / Action / State transition (`-->`, `<--`, `v--`, `plus`, `=`).
  * **Slot 7 (Adverb):** Execution cadence / Policy / Negation (`--`, `atomic`, `yield`).
  * **Slot 8 (Preposition):** Spatial address / Memory site / Index enclosure (`@ Vault_Offset`, `[0 .. 256]`).

### 2. ASCII Operator Specialization & Distinction

* **`@` — Spatial Location (Preposition):**
  * Specifies memory site, address, hardware MMIO offset, or network endpoint: `Storehouse @ Vault_Offset`.
* **`%` — Percentage & Capacity Fullness (Adjective / Noun):**
  * Expresses relative ratios and fullness thresholds without arithmetic boilerplate: `Storehouse % 80`, `Throttle % 50`.
* **`&` vs. `::` — Inseparable Bond vs. Cooperative Junction:**
  * **`&` (Hand-in-Hand Inseparable Binding):** Binds twin entities into an indivisible covenant (`Jack&Jill`, `Key&Value`, `Addr&Offset`, `Tx&Rx`). `A` cannot be referenced without `B`, nor `B` without `A`.
  * **`::` (Cooperative Junction):** Joins independent entities together in sequence, pipeline chaining, or namespace consensus (`A :: B :: C`). Entities maintain independent existence and can be used on their own.

### 3. Engine Implementation & Lexer Expansion

* Added `TokenType::At`, `TokenType::Percent`, and `TokenType::BoundPair` in [`src/parser/lexer.rs`](file:///home/professorseanex/OmniCode/src/parser/lexer.rs).
* Updated [`src/core/linguistics.rs`](file:///home/professorseanex/OmniCode/src/core/linguistics.rs) with primary and secondary grammatical classifications for all new tokens.
* Updated [`docs/01_foundations/03_eight_parts_of_speech_matrix.md`](file:///home/professorseanex/OmniCode/docs/01_foundations/03_eight_parts_of_speech_matrix.md).
* All 42 tests passing with zero errors.

---

## [2026-10-10] Milestone 9: Vessel Subsystem Codification & `lib/core/memory.omni` Library

### 1. Rust Engine Implementation: Bounded Vessels & Storehouses

* **The Problem:** The language lacked runtime data structures for contiguous, bounded memory spaces, and evaluating SVO directional vector operations against indexed memory (`Value --> Vessel[Offset]`).
* **The Solution:** Engineered [`src/core/vessel.rs`](file:///home/professorseanex/OmniCode/src/core/vessel.rs) and integrated it into the runtime:
  * Implemented `Vessel`, `Storehouse`, and `Partition` with strict invariant boundary enforcement.
  * An out-of-bounds access (`Offset >= Capacity`) does not segfault; it naturally returns `-1: ROLLBACK` via balanced ternary physics.
  * Added `RuntimeValue::Cell` and `RuntimeValue::Vessel` to [`src/runtime/environment.rs`](file:///home/professorseanex/OmniCode/src/runtime/environment.rs).
  * Upgraded [`src/runtime/evaluator.rs`](file:///home/professorseanex/OmniCode/src/runtime/evaluator.rs) to support vessel declarations, spatial index reads (`Vessel[Offset]`), forward vector stores (`Value --> Vessel[Offset]`), and feedback reads (`Dest <-- Vessel[Offset]`).

### 2. Standard Memory Library Reel (`lib/core/memory.omni`)

* Authored the foundational memory management module in 4-Block architecture:
  * **Block 1 (Metadata):** Declares invariant macros for `TRIT_NOUN`, `CELL_NOUN`, `VESSEL_NOUN`, `STOREHOUSE_NOUN`, `PARTITION_NOUN`, `OFFSET_NOUN`, `CAPACITY_NOUN`, `COUNT_NOUN`, `VALUE_NOUN`.
  * **Block 2 (Opening):** Allocates a root `Main_Storehouse [ 1024 ]` and an entrusted `Task_Partition [ 256 ]`.
  * **Block 3 (Body):** Executes natural number storage (`42 --> Task_Partition[0]`), retrieval (`read_val <-- Task_Partition[0]`), and affirmative state inscription (`PROCEED --> Task_Partition[1]`).
  * **Block 4 (Closing):** Verifies all memory operations and seals with `commit_status [ PROCEED ]`.

### 3. Verification & Test Suite Expansion

* Added `test_lib_core_memory` integration test in [`tests/integrated/main.rs`](file:///home/professorseanex/OmniCode/tests/integrated/main.rs).
* All 42 automated tests across unit, functional, and integrated suites pass with zero errors.

---

## [2026-10-10] Milestone 8: 8-Bit to 5-Trit Hardware Transducer & Core Noun Taxonomy
```

```
### 1. Mathematical Grounding: 8 Bits <--> 5 Trits Bijective Transducer

* **The Problem:** In traditional C, an 8-bit byte ($2^8 = 256$ states) has zero space to store `NULL`, `AWAIT (0)`, `ROLLBACK (-1)`, or `PROCEED (+1)` without in-band signaling collisions or ballooning struct wrapper bloat.
* **The Solution:** Engineered a bijective hardware codec in [`src/core/cell.rs`](file:///home/professorseanex/OmniCode/src/core/cell.rs):
  * **243 Data States ($0 \dots 242$):** Bijectively maps to 5 balanced trits spanning $[-121 \dots +121]$ with Radix-3 place values ($81, 27, 9, 3, 1$). State is implicitly `PROCEED`.
  * **13 Out-of-Band Control States ($243 \dots 255$):**
    * `243`: `NULL / HALT` (Void / unmapped memory / terminal trap).
    * `244`: `AWAIT` (Superposition / pending / non-blocking lock).
    * `245`: `ROLLBACK` (Veto / tainted / unwound transaction cell).
    * `246`: `PROCEED` (Affirmative sealed landmark).
    * `247..255`: System traps & physical hardware markers.
* **Dense Memory Efficiency:** 1 Cell = exactly 1 physical byte in RAM, but unpacks losslessly into 5-trit balanced ternary + Quad-State. Zero struct padding, zero alignment waste.

### 2. Noun Taxonomy Codified

* **Atomic Units:** `Trit`, `Cell`, `Word`.
* **Storage Vessels:** `Vessel`, `Storehouse`, `Partition`.
* **Coordinates:** `Offset`, `Origin`, `Landmark`.
* **Measures:** `Capacity`, `Count`.
* **Substance:** `Value`, `State`.

### 3. Transducer Verification

* Verified 100% round-trip conversion for all 243 natural values ($0 \dots 242$), all 243 signed values ($-121 \dots +121$), and all 4 out-of-band Quad-State markers.
* All 38 automated unit, functional, and integrated tests passing cleanly.

---

## [2026-10-10] Milestone 7: Universal Linguistics & 8 Parts of Speech Formalization

### 1. Conceptual Breakthrough: Nouns are Defined, Verbs are Symbolized

* **The Problem:** Traditional programming languages clone imperative C/Rust jargon (`malloc`, `free`, `alloc`, `deref`, `peek`, `poke`, `mut`, `fn`). This creates a severe cognitive translation penalty: human and AI reasoning in natural grammar must be disassembled into mechanical idioms.
* **The Discovery:** OmniCode is not an imperative clone. In OmniCode:
  * **Nouns are defined:** Entities, storage containers, measures, types, and values are expressed in natural human vocabulary (`Vessel`, `Storehouse`, `Measure`, `Offset`, `Bound`).
  * **Verbs are symbolized:** Actions, state transitions, and relations are expressed through universal directional vectors (`-->`, `<--`, `^--`, `v--`) and relational operators (`=`, `!=`, `~=`).

### 2. The 8-Word Grammatical Proof

* Demonstrated that a single, coherent, 8-word sentence cleanly incorporates all 8 parts of speech:
  $$\text{“}\underbrace{\text{Oh!}}_{\text{Interjection}}\quad \underbrace{\text{But}}_{\text{Conjunction}}\quad \underbrace{\text{my}}_{\text{Pronoun}}\quad \underbrace{\text{old}}_{\text{Adjective}}\quad \underbrace{\text{man}}_{\text{Noun}}\quad \underbrace{\text{walked}}_{\text{Verb}}\quad \underbrace{\text{straight}}_{\text{Adverb}}\quad \underbrace{\text{ahead}}_{\text{Preposition}}\text{.”}$$
* Mapped each part of speech directly to its operational counterpart in computer science and operating systems:
  * Nouns $\to$ Data, Types, Memory Containers, Hardware Devices.
  * Pronouns $\to$ References, Context Handles, Iterators (`self`, `this`, `_`).
  * Verbs $\to$ Instructions, State Transitions, Mutations (`-->`, `<--`, `=`).
  * Adjectives $\to$ Type Invariants, Contracts, Bounds (`{ Bounded, Fixed }`).
  * Adverbs $\to$ Execution Policies, Scheduler Priorities, Negation (`--`).
  * Prepositions $\to$ Memory Offsets, Array Indexing (`[offset]`), Projections (`:`).
  * Conjunctions $\to$ Logic Connectives, Pipeline Guards, Caveats (`!`, `::`, `\|`).
  * Interjections $\to$ Traps, Interrupts, Halts, Panics, Asides (`(...)`, `NULL`, `-1`).

### 3. Implementation Upgrades

* Implemented [`src/core/linguistics.rs`](file:///home/professorseanex/OmniCode/src/core/linguistics.rs) defining `PartOfSpeech`, `GrammaticalClassification`, and `GrammaticalEntity`.
* Classified all tokens, boundaries, directional vectors, relational operators, and quad-states with **Primary**, **Secondary**, and **Tertiary** grammatical roles.
* Enriched standard library macros in [`lib/core/vectors.omni`](file:///home/professorseanex/OmniCode/lib/core/vectors.omni) with grammatical role metadata.
* Authored formal specification: [`docs/01_foundations/03_eight_parts_of_speech_matrix.md`](file:///home/professorseanex/OmniCode/docs/01_foundations/03_eight_parts_of_speech_matrix.md).
* Verified: All 26 automated unit, functional, and integration tests passing.

---

## [2026-10-10] Milestone 6: Cloud Deployment & Oracle VM Synchronization

* Installed `oci-cli` v3.94.2 at `/usr/local/bin/oci` on remote Oracle Cloud VM (`147.224.147.30`).
* Configured `iptables` Rule #1 for authorized IP `71.11.99.168` and opened port 8080 (persisted via `netfilter-persistent`).
* Synced clean directory layout to Oracle VM via `infra/scripts/sync_oracle_vm.sh`.
* Verified all 9 public HTTP endpoints returning HTTP 200 OK (`/api/health`, `/terminal`, `/download`, `/specs`, `/model`,
```

```
`/lexicon`, `/scrolls`, `/cloud`, `/api/scheduler`).
  * DNS synchronization confirmed via `omnicodestudio.duckdns.org`.

  ---

  ## [2026-10-10] Milestone 5: Workspace Reorganization & Playwright Validation

  * Reorganized repository root into 8 clean, logical directories:
    * `apps/` — Native GUI and web editor interfaces.
    * `infra/` — DNS scripts, Docker configurations, systemd services, sync scripts.
    * `runtime/` — Executable scrolls, test logs, episodic traces.
    * `src/` — Rust compiler and runtime source code.
    * `lib/` — Standard library modules (`lib/core/`).
    * `examples/` — Canonical showcases.
    * `tests/` — Unit, functional, and integrated test suites.
    * `docs/` — Architectural and foundational specifications.
    * `dist/` — Production releases and tarballs.
  * Bootstrapped headless Playwright browser driver for automated end-to-end browser GUI testing; captured high-resolution
verification screenshots of the live web terminal HUD.

  ---

  ## [2026-10-09] Milestone 4: Cooperative OmniScheduler & Interactive Terminal REPL

  * Built `OmniScheduler` with 4 priority tiers (`System`, `High`, `Normal`, `Idle`) and tick quantum enforcement.
  * Integrated cooperative yielding via balanced ternary `0: AWAIT`.
  * Created interactive REPL (`TerminalSession`) supporting multi-line input, transaction rollback, and live quad-state feedback.

  ---

  ## [2026-10-09] Milestone 3: AI Cognitive Cortex & Episodic Scrolls

  * Integrated 100% offline `BiblicalLexicon` derived from public domain KJV 1611 and WEB scriptures across 6 domains (`Cosmology`,
`LivingWorld`, `HumanCondition`, `MoralVirtue`, `MoralVice`, `CausalLaw`).
  * Created `AICortex` deliberation engine evaluating natural language prompts against 7 Invariant Covenant Laws.
  * Built dual-logging pipeline: `.scroll` executable reels and `.log` machine telemetry.

  ---

  ## [2026-10-08] Milestone 2: Compiler Pipeline & Universal 4-Block Architecture

  * Implemented lexer, parser, and AST with first-class Asides `(...)`.
  * Formatted source architecture into 4 deterministic blocks: `Metadata`, `Opening`, `Body`, `Closing`.
  * Built `OmniLinter` and autonomous self-healing `Restorator` capable of repairing boundary leaks and missing scaffolding.

  ---

  ## [2026-10-08] Milestone 1: Algebraic Foundation & Balanced Ternary Physics

  * Initialized core physics: Balanced Ternary Quad-State (`+1: PROCEED`, `0: AWAIT`, `-1: ROLLBACK`, `NULL: HALT`).
  * Engineered 6 morphological boundary delimiters ranked by ontological hierarchy (`<...>`, `[...]`, `{...}`, `[...}`, `{...]`,
`(...)`).
  * Established 3D coordinate operators along Being ($Y$), Dynamics ($X$), and Scale ($Z$) axes.
```

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/01_foundations/01_ontological_principles.md

MD | 52 LINES | 344 WORDS | 2.4 KB

```
# Volume 1: Foundations

## Document 01: Ontological Principles & Set Theory

---

### 1. The Ontological Philosophy

In classical philosophy and information science, **Ontology** is the formal study of the nature of being, existence, and reality:

* What categories of things exist?
* What belongs to the fundamental essence of an entity?
* What belongs to the entity merely by virtue of its environment?

Traditional programming languages are ontologically flawed. They conflate data layout, storage location, execution state, and scope into ad-hoc constructs. For instance:

* In C, a raw pointer `char*` tells you nothing about allocation ownership, thread boundaries, or buffer bounds.
* In object-oriented languages (like Java or C#), an object forcibly binds identity, state, virtual tables, and garbage collection semantics into a single monolithic unit.

**OmniCode decouples Essence from Environment as a first principle.** Every entity in OmniCode is understood through an ontological equation:

$$\text{Entity} = \text{Essence (Denotation)} \text{ in } \text{Environment (Connotation)}$$

---

### 2. The Set-Theoretic Grounding

OmniCode builds directly upon mathematical Set Theory:

#### A. Extensional Definition vs. Intensional Context

1. **Extensionality (Axiom of Extensionality):**
   A set is defined explicitly by its members or constituent elements. In OmniCode, the **Denotation** `[...]` provides the extensional definition: the concrete data fields, state transitions, or algorithm steps.
2. **Intensionality (Set Comprehension / Axiom of Separation):**
   A set is defined by a property over a universe of discourse:
   $$S = \{ x \in \mathcal{U} \mid \Phi(x) \}$$
   In OmniCode, the **Connotation** `{...}` defines this exact universe $\mathcal{U}$ and the predicates $\Phi(x)$ that must hold true for the entity to exist safely.

#### B. Scale Invariance Across Abstraction Layers

Because set theory is scale-invariant, the same mathematical rules apply regardless of whether we are writing low-level firmware or high-level distributed systems:

```text
Low-Level:   Memory_Block [ 4096 bytes ] { Address >= 0x1000, Aligned(64), NonVolatile }
High-Level:  User_Session [ Token, Expiry ] { Authenticated, Network.Secure, TTL > 0 }
```

In both cases:

* The brackets define the internal shape and content.
* The braces define the universe and preconditions required for validity.
```

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/01_foundations/02_boundary_types_and_asides.md

MD | 57 LINES | 390 WORDS | 2.7 KB

```
# Volume 1: Foundations

## Document 02: Boundary Types & First-Class Asides

---

### 1. The Morphological Boundary System

In OmniCode, delimiters are not passive punctuation; they are **morphological operators** that govern the boundary physics between an entity and its surrounding universe.

There are six canonical boundary types, ranked in strict ontological and linguistic hierarchy:

```text
               Rank 1: < ... >      Invariant (Immutable Axiom / Law)
               Rank 2: [ ... ]      Denotation (Mutable Definition / Essence)
               Rank 3: { ... }      Connotation (Context / Ambient Universe)
               Rank 4: [ ... }      Bottom-Up (Inside-Out: Entity Projects into Context)
               Rank 5: { ... ]      Top-Down (Outside-In: Context Conditions Entity)
               Rank 6: ( ... )      Aside (Intent, Teleology, Machine Annotation)
```

---

2. Detailed Semantics of Each Boundary

A. Symmetric Boundaries

* **`[ ... ]` (Denotation):**
  Defines an entity whose state or value can vary over time. Represents mutable structures, variables, functions, and state machines.
* **`< ... >` (Invariant):**
  Defines an entity whose state is immutable across all possible execution contexts. Represents mathematical constants, hardware ROM, zero-cost immediate literals, and axioms.
* **`{ ... }` (Connotation):**
  Defines the ambient context or environment. Can contain required capabilities, thread bindings, memory space qualifiers, or lifetime scopes.

B. Asymmetric Boundaries (Directional Causality)

* **`{ ... ]` (Context Defines):**
  Outside-In Causality. The environment dictates what the entity inside is.
  * *Example:* A memory page table dictating a virtual memory mapping, or dependency injection where the runtime environment provides the concrete implementation.
* **`[ ... }` (Defined by Context):**
  Inside-Out Causality. The entity's definition emerges from or adapts to the environment it is placed into.
  * *Example:* Ad-hoc polymorphism, polymorphic serialization formats, or registers adapting to caller/callee ABIs.

C. `( ... )` The First-Class Aside

Traditional languages discard comments (`//`, `/* */`) during lexical analysis. This causes a severe **semantic gap**:

1. Human and AI intent is lost to the compiler.
2. Code and documentation drift out of synchronization.
3. The compiler cannot verify whether the implementation satisfies the intended purpose.

In OmniCode, `( ... )` is an **Aside**:

* It is preserved as a permanent node in the Abstract Syntax Tree (AST).
* It provides semantic tags, invariants, and rationale.
* It enables native AI code generation by creating an explicit container for reasoning traces that the compiler and verifier can inspect.
```

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/01_foundations/03_eight_parts_of_speech_matrix.md MD 255 LINES 2207 WORDS 19.8 KB

```
# Volume 1: Foundations

## Document 03: The 8 Parts of Speech & Grammatical Matrix

---

### 1. The Linguistic Premise

Traditional programming languages are built upon arbitrary syntactic conventions—mixing imperative keywords (`malloc`, `free`, `mut`, `deref`, `peek`, `poke`), ad-hoc symbols, and fragmented paradigms. This creates a severe **semantic translation tax**: human thought and AI cognitive reasoning (which operate in natural grammar) must be manually dismantled into mechanical idioms to execute on hardware.

**OmniCode solves this by grounding programming directly in the universal grammar of natural language.**

In OmniCode:

1. **Nouns are Defined:** Entities, data structures, storage spaces, and types use natural, meaningful vocabulary.
2. **Verbs are Symbolized:** Actions, causation, state transitions, and relations are expressed through universal directional vectors (`-->`, `<--`, `^--`, `v--`) and relational operators (`=`, `!=`, `~=`).
3. **Sentence Structure is Isomorphic to Thought:** Every valid statement maps 1:1 onto a natural human sentence.

---

### 2. The 8-Word Proof: The Completeness of Natural Grammar

To demonstrate that a single, coherent sentence can cleanly encompass all 8 parts of speech without losing clarity, consider:

$$\text{“}\underbrace{\text{Oh!}}_{\text{1. Interjection}}\quad \underbrace{\text{But}}_{\text{2. Conjunction}}\quad \underbrace{\text{my}}_{\text{3. Pronoun}}\quad \underbrace{\text{old}}_{\text{4. Adjective}}\quad \underbrace{\text{man}}_{\text{5. Noun}}\quad \underbrace{\text{walked}}_{\text{6. Verb}}\quad \underbrace{\text{straight}}_{\text{7. Adverb}}\quad \underbrace{\text{ahead}}_{\text{8. Preposition}}\text{.”}$$

Every word plays an indispensable, distinct role:

* **Oh!** (Interjection): Signals an immediate reaction, trap, or interrupt.
* **But** (Conjunction): Introduces an adversative connection and caveat constraint.
* **my** (Pronoun): Points back to an established subject without repeating a heavy name.
* **old** (Adjective): Qualifies the essence and invariants of the entity.
* **man** (Noun): The core subject and entity of discourse.
* **walked** (Verb): The causal action, movement, or state transition.
* **straight** (Adverb): The manner and policy under which the verb executes.
* **ahead** (Preposition): The spatial direction and coordinate destination.

---

### 3. The Computer Science & Systems Mapping

Each part of speech corresponds to an exact computational mechanism in operating systems and computer science:

| Part of Speech | Linguistic Meaning | Computer Science Counterpart | OmniCode Equivalent |
| :--- | :--- | :--- | :--- |
| **1. Noun** | What the entity is (Substance / Identity) | Data, Types, Variables, Memory Vessels, Hardware Devices | Identifiers, Numbers, Strings, `[...]` (Denotation) |
| **2. Pronoun** | Pointing to an established entity without re-declaring | References, Pointers, Handles, `self`, `this`, `_` | Scoped Context, `Identifier`, Handle references |
| **3. Verb** | What the entity does or experiences (Action / Being) | Instructions, Opcodes, State Transitions, Mutations | Directional Vectors (`-->`, `<--`), Being (`=`, `!=`), Math |
| **4. Adjective** | Qualities, limits, and conditions of the noun | Type Qualifiers, Mutability Specs, Invariants, Contracts | Invariants `{...}`, Axioms `<...>`, Quad-States (`PROCEED`) |
| **5. Adverb** | How, when, or under what policy the verb acts | Execution Modes, Schedulers, Inlining, Negation | Negation (`--`), Priority tiers, Execution flags |
| **6. Preposition** | Spatial, temporal, or structural relations | Offsets, Array Indexing, Member Access, Scopes | Indexing `[offset]`, Projection `:`, Pairings |
| **7. Conjunction** | Connectives linking operations, logic, or branches | Boolean Logic, Branching, Semicolons, Pipeline Chaining | `!` (But / Caveat), `::` (And), `\|` (Or), Pipeline |
| **8. Interjection** | Immediate exclamations breaking normal narrative | CPU Interrupts, Traps, Signals, Panics, Intent Asides | Asides `(...)`, `NULL: HALT`, `-1: ROLLBACK` |

---

### 4. Primary, Secondary & Tertiary Grammatical Matrix

Because natural language words often assume multiple functional roles depending on syntax (e.g., *"walk"* can be a verb or a noun), OmniCode formally classifies its constructs with **Primary**, **Secondary**, and **Tertiary** grammatical roles via [`crate::core::linguistics::GrammaticalEntity`]:
```

```text
┌──────────────────────────────────────────────────────────────────────────────────────────────────────────────┐
│                                    OmniCode Grammatical Classification Matrix                                │
├──────────────────────────┬──────────────────┬──────────────────┬──────────────────┬──────────────────────────┤
│ Construct / Symbol       │ Primary Role     │ Secondary Role   │ Tertiary Role    │ Operational CS Meaning   │
├──────────────────────────┼──────────────────┼──────────────────┼──────────────────┼──────────────────────────┤
│ `[...]` (Denotation)     │ Noun             │ Preposition      │ —                │ Container / Offset index │
│ `{...}` (Invariant)      │ Adjective        │ Conjunction      │ —                │ Invariant contract / Guard │
│ `<...>` (Axiom)          │ Adjective        │ Noun             │ —                │ Constant / Domain category │
│ `(...)` (Aside)          │ Interjection     │ Adverb           │ —                │ Teleology / Intent trace │
│ `-->` (ActUpon)          │ Verb             │ Preposition      │ —                │ Forward store / MOV / Flow │
│ `<--` (ActAgain)         │ Verb             │ Preposition      │ —                │ Load / Feedback / Undo   │
│ `^--` (BuildsTo)         │ Verb             │ Preposition      │ —                │ Type promotion / Synthesis │
│ `v--` (BreaksDown)       │ Verb             │ Preposition      │ —                │ Lowering / Destructuring │
│ `=` (Is)                 │ Verb             │ Conjunction      │ —                │ Equality / Copula of Being │
│ `!=` (IsNot)             │ Verb             │ Conjunction      │ —                │ Inequality / Exclusion   │
│ `~=` (ToBeLike)          │ Verb             │ Adjective        │ —                │ Analogy / Duck typing    │
│ `!` (But)                │ Conjunction      │ Interjection     │ —                │ Caveat / Rollback trigger │
│ `::` (And)               │ Conjunction      │ Preposition      │ —                │ Simultaneous consensus   │
│ `:` (InRelationTo)       │ Preposition      │ Verb             │ —                │ Type projection / Role   │
│ `@` (At / Location)      │ Preposition      │ Noun             │ —                │ Spatial address / Site   │
│ `%` (Percent)            │ Adjective        │ Noun             │ —                │ Ratio / Fullness / Fraction│
│ `&` (BoundPair)          │ Conjunction      │ Noun             │ —                │ Inseparable dual binding │
│ `\|` (Or)                │ Conjunction      │ Adverb           │ —                │ Disjunction / Branching  │
│ `--` (Not)               │ Adverb           │ Conjunction      │ —                │ Algebraic negation       │
│ `plus`, `minus`, ...     │ Verb             │ Conjunction      │ —                │ Natural SVO arithmetic   │
│ `?` (Infer)              │ Interjection     │ Verb             │ —                │ Ontological query        │
│ `+1` (PROCEED)           │ Adjective        │ Noun             │ Interjection     │ Truth / Forward commit   │
│ `0` (AWAIT)              │ Adjective        │ Verb             │ —                │ Superposition / Yield    │
│ `-1` (ROLLBACK)          │ Interjection     │ Verb             │ Adjective        │ Veto / Transaction rewind │
│ `NULL` (HALT)            │ Interjection     │ Noun             │ —                │ Fatal trap / Void collapse │
└──────────────────────────┴──────────────────┴──────────────────┴──────────────────┴──────────────────────────┘
```

---

5. ASCII Operator Specialization: Distinct Cognitive Roles

Rather than arbitrary punctuation, OmniCode assigns every ASCII glyph to an irreplaceable grammatical and physical purpose:

1. `@` — Spatial Location (Preposition)

* **Function:** Designates exact location, memory address, hardware MMIO site, or network origin.
* **Syntax:** `Entity @ Site` or `Storehouse @ Vault_Offset`.
* **Example:**

  ```omnicode
  Cell @ 0x00FF
  Storehouse @ Vault_Offset
  ```

2. `%` — Percentage & Proportion (Adjective / Noun)

* **Function:** Specifies capacity fullness, relative ratio, threshold fraction, or duty cycle without cumbersome arithmetic.
* **Syntax:** `Entity % Value` or `Measure % N`.
* **Example:**

  ```omnicode
  Storehouse % 80       ( Threshold: 80% capacity utilization )
  Throttle % 50         ( 50% duty rate )
  ```

3. `&` vs. `::` — The Inseparable Bond vs. The Cooperative Junction

This distinction illustrates the exactness of OmniCode's grammar:

* **`&` — Hand-in-Hand Inseparable Binding (Conjunction / Atomic Entanglement):**
  * Represents an indivisible dual covenant.
  * In `Jack&Jill` or `Key&Value`, you **cannot** reference `A` without referencing `B`, nor `B` without `A`.
  * If one moves, both move. If one is written, both are written.
  * *Systems equivalents:* Dual-rail differential signaling, atomic key-value pairs, coordinate pairs (`X&Y`), transaction state pairs (`Tx&Rx`).
  * Used strictly between tightly coupled twin entities.

* **`::` — Cooperative Junction of Independent Entities (Conjunction / Chaining):**
  * Joins distinct, independent entities together in sequence, pipeline flow, or namespace consensus.
  * `A::B` means `A` exists independently and `B` exists independently; they are joined in cooperative work.
  * Unlike `&`, `::` can be chained indefinitely: `Opening :: Validate :: Process :: Closing`.

---

6. The 8-Slot Canonical Sentence Architecture

Because natural language and computation are governed by the **8 parts of speech**, the canonical complete sentence in OmniCode contains **exactly 8 functional slots**, mapping 1:1 onto universal human thought:

$$\begin{aligned}
\text{Natural Sentence:} \quad & \underbrace{\text{Oh!}}_{\text{1. Interjection}}\ \underbrace{\text{But}}_{\text{2. Conjunction}}\ \underbrace{\text{my}}_{\text{3. Pronoun}}\ \underbrace{\text{old}}_{\text{4. Adjective}}\ \underbrace{\text{man}}_{\text{5. Noun}}\ \underbrace{\text{walked}}_{\text{6. Verb}}\ \underbrace{\text{straight}}_{\text{7. Adverb}}\ \underbrace{\text{ahead}}_{\text{8. Preposition}}\text{.} \\
\text{OmniCode Pipeline:} \quad & \underbrace{\text{(Intent)}}_{1.\ \text{Interjection}}\ \underbrace{\text{::}}_{2.\ \text{Conjunction}}\ \underbrace{\text{self}}_{3.\ \text{Pronoun}}\ \underbrace{\text{\{ Pure \}}}_{4.\ \text{Adjective}}\ \underbrace{\text{Gold}}_{5.\ \text{Noun}}\ \underbrace{\text{-->}}_{6.\ \text{Verb}}\ \underbrace{\text{--}}_{7.\ \text{Adverb}}\ \underbrace{\text{@ Vault}}_{8.\ \text{Preposition}}\text{!}
\end{aligned}$$

```text
┌──────────────────────────────────────────────────────────────────────────────┐
│                        The 8-Slot Canonical Sentence Architecture            │
├──────┬──────────────────────┬──────────────────────┬─────────────────────────┤
│ Slot │ Part of Speech       │ Linguistic Role      │ OmniCode Implementation │
├──────┼──────────────────────┼──────────────────────┼─────────────────────────┤
│  1   │ **Interjection**     │ Attention / Trap / Aside│ `Oh!`, `( Intent )`, `HALT` │
│  2   │ **Conjunction**      │ Transition / Link / Pair│ `::` (Junction), `&` (Pair) │
│  3   │ **Pronoun**          │ Context Handle / Alias  │ `self`, `it`, `origin`, `_` │
│  4   │ **Adjective**        │ Invariant / Contract    │ `{ Pure }`, `< Axiom >` │
│  5   │ **Noun**             │ Subject / Vessel / Data │ `Gold`, `Storehouse`, `Cell` │
│  6   │ **Verb**             │ Action / Vector / Being │ `-->`, `<--`, `v--`, `plus`, `=`│
│  7   │ **Adverb**           │ Manner / Cadence / Rate │ `--` (Not), `yield`, `atomic` │
│  8   │ **Preposition**      │ Spatial Location / Span │ `@ Offset`, `[0 .. 256]` │
└──────┴──────────────────────┴──────────────────────┴─────────────────────────┘
```

Complete Executable Example in OmniCode

```omnicode
( Safe Escrow ) :: self { Verified } Gold&Key --> atomic @ Vault_Storehouse ! { Offset < Capacity }
```

* **Slot 1 (`( Safe Escrow )`)**: Interjection (Teleological intent aside).
* **Slot 2 (`::`)**: Conjunction (Pipeline transition linking to execution context).
* **Slot 3 (`self`)**: Pronoun (Caller context handle).
* **Slot 4 (`{ Verified }`)**: Adjective (Invariant security contract).
* **Slot 5 (`Gold&Key`)**: Noun (Hand-in-hand inseparable dual pair: payload and key).
* **Slot 6 (`-->`)**: Verb (Forward directional dispatch vector).
* **Slot 7 (`atomic`)**: Adverb (Execution manner / scheduler policy).
* **Slot 8 (`@ Vault_Storehouse ! { ... }`)**: Preposition (Spatial destination site `@` with boundary guard).

---

7. Why This 1:1 Mapping Matters

1. **Zero Translation Penalty:** The programmer does not translate an English requirement into machine assembly or imperative boilerplate; the statement directly expresses the thought.
2. **Native AI Symbiosis:** Large Language Models and cognitive agents reason through grammatical dependency trees. When programming syntax is identical to grammar, code synthesis and verification become naturally robust against hallucination.
3. **Syntax Errors are Grammatical Nonsense:** A compiler syntax error in OmniCode is not an arbitrary token mismatch; it is a violation of universal grammar.
4. **Boundary Integrity as Law:** Invariants (`{...}`) act as the ambient law of the universe. When an operation exceeds a boundary, it encounters physical counter-force, triggering `-1: ROLLBACK`.
5. **No ASCII Ambiguity:** Every punctuation mark has one coherent linguistic meaning across the entire language. `@` always locates, `%` always proportions, `&` always binds inseparably, and `::` always junctions.

---

8. The 6 Cardinal Classification Clauses (5 W's and 1 H)

In both the **Long Form (4-Block Architecture)** and the **Interpreted Sentence Form (Rolls)**, OmniCode provides first-class classification clauses matching the fundamental inquiries of human reasoning:

* **WHO (Pronoun):** Identifies agent, process owner, security principal, or caller authority (`WHO self`).
* **WHAT (Noun):** Identifies substance, payload, entity, memory vessel, or data type (`WHAT [Cell]`).
* **WHEN (Adverb):** Identifies execution cadence, clock quantum, trigger, or lifecycle phase (`WHEN Opening`).
* **WHERE (Preposition):** Identifies spatial address, memory offset, site, or invariant scope (`WHERE {unit}`).
* **WHY (Interjection / Axiom):** Identifies teleological intent, rationale, or invariant justification (`WHY ( Safe placement )`).
* **HOW (Verb & Adverb):** Identifies causal vector method, transducer cycle, or execution policy (`HOW [ 8 bit --> 5 trit --> 8 bit ]`).

---

9. Spatial Directional Vector Geometry

Beyond horizontal linear flow (`-->` and `<--`), OmniCode supports full 2D and 3D spatial dynamics:

```text
                              ^-- / --^
                            (Up / Ascend)
                                  ▲
                        ^\        |       /^
                  (Upper Left)    |    (Upper Right)
                                  |
    <-- ──────────────────────────|──────────────────────────> -->
(Retroaction)                     |                       (Causation)
                                  |
                        v/        |       \v
                  (Lower Left)    |    (Lower Right)
                                  ▼
                              v-- / --v
                            (Down / Descend)
```

* **Scale Modulations:**
  * `/-^` **(Major):** Ascending forward diagonal — major leap upward or expansion.
  * `\-v` **(Minor):** Descending forward diagonal — minor step down, reduction, or settling.
  * `\-^` **(Great):** Ascending backward diagonal — great reflection, elevation, or architectural hoist.
  * `/-v` **(Small):** Descending backward diagonal — small adjustment, fine-tuning, or micro-destructure.
* **2D Quadrant / Compass Vectors:**
  * `/^` **(Quadrant I):** $+X, +Y$ — Upper right / northeast ascending growth.
  * `\v` **(Quadrant IV):** $+X, -Y$ — Lower right / southeast descending flow.
  * `^\` **(Quadrant II):** $-X, +Y$ — Upper left / northwest backward ascension.
  * `v/` **(Quadrant III):** $-X, -Y$ — Lower left / southwest deep system rewind.

---

10. Boundaries as Space: `#` vs. `(...)`

In OmniCode, code is not an amorphous 1D string of characters—**it is a spatial layout that mirrors silicon RAM**:

* **`#` (Parchment Boundary & Documentation):**
  * Defines physical 2D visual layout, visual compartment borders (`# BLOCK 1: METADATA`), section dividers, and structural documentation.
  * Organizes the code territory on the parchment.
* **`(...)` (Teleological Aside & AI Metadata):**
  * **An active, first-class AST node!**
  * Encodes machine intent, AI reasoning traces, and covenant rationale.
  * Preserved in compiled `.scroll` files so the `AICortex` and `Restorator` can inspect **WHY** code was written to heal it autonomously.
* **Why Boundaries Are Essential:**
  * Space without boundaries is entropy (buffer overflows, memory corruption).
  * In OmniCode, boundaries (`#`, `[...]`, `{...}`, `<...>`) create physical compartments and memory partitions (`Storehouse v-- Partition [ 256 ]`), guaranteeing spatial isolation and safety by construction.

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/04_cognitive_and_autonomous_systems/01_ai_cortex_and_neural_symbolic_loop.md MD 118 LINES 607 WORDS 5.4 KB

```
# Volume 4: Cognitive & Autonomous Systems

## Document 01: The AI Cortex & Neural-Symbolic Transduction Loop

> **Bridging Freeform Human Discourse and Deterministic Machine Execution via Dual-Readable 4-Block Turing Reels.**

In traditional computing, natural language processing and compiler execution exist in disjoint worlds: LLMs generate unverified code strings that are prone to hallucinated syntax, while compilers reject anything that deviates from rigid grammars.

OmniCode solves this duality by embedding a **Neural-Symbolic Cognitive Loop** directly within the language engine:

$$\text{Natural Prompt} \xrightarrow{\text{Transducer}} \text{Canonical 4-Block AST} \xrightarrow{\text{Restorator}} \text{Self-Healed Code} \xrightarrow{\text{Evaluator}} \text{Episodic Trace} \xrightarrow{\text{Logger}} \text{Dual Inscription}$$

---

### 1. Architectural Foundation & Preconditions

The [`AICortex`](file:///home/professorseanex/OmniCode/src/ai/model/cortex.rs) orchestrates five specialized subsystems within an integrated cognitive loop:

```mermaid
flowchart TD
    Prompt["Human Prompt (Natural Discourse)"] --> Transducer["AITransducer (Entity & SVO Parser)"]
    Transducer --> RawOmni["Draft 4-Block OmniCode"]
    RawOmni --> Restorator["Restorator (Autonomous Self-Healing)"]
    Restorator --> HealedOmni["Sanitized Executable OmniCode"]
    HealedOmni --> Evaluator["Evaluator & OmniDebugger (Quad-State Physics)"]
    Evaluator --> ExecResult["Runtime Result & Telemetry"]
    ExecResult --> ScrollLogger["ScrollLogger (Episodic Inscriber)"]
    ScrollLogger --> ScrollFile[".scroll (Native Executable Reel)"]
    ScrollLogger --> LogFile[".log (Microsecond Telemetry)"]
```

Precondition Invariants

1. **Deterministic Transduction:** All inferred entity names, numeric literals, and relational directions must be captured in explicit 4-Block sections.
2. **Intent Preservation:** Conceptual commentary and reasoning traces are preserved as first-class Asides `(...)`.
3. **Transactional Safety:** If evaluation triggers a `-1:ROLLBACK` or caveat veto, state changes are rolled back automatically.

---

2. Transduction Mechanics & Operational Pipeline

The [`AITransducer`](file:///home/professorseanex/OmniCode/src/ai/transducer.rs) executes a four-stage cognitive transformation:

1. **Entity & Numeric Extraction:**
   - Scans natural discourse for quantities (e.g., `5 units`, `12 items`) and targets (e.g., `inventory A`, `group B`).
   - Distinguishes initial baseline quantities from incremental operands.
2. **Subject-Verb-Object (SVO) Resolution:**
   - Maps operational verbs (`add`, `combine`, `transfer`, `mutate`, `verify`) to directional vectors:
     - Addition / Transfer $\to$ `-->` (Act Upon / Forward Causality).
     - Retroactive Feedback $\to$ `<--` (Feedback / Reverse Causality).
     - Invariant Layering $\to$ `^--` (Builds to) / `v--` (Breaks down from).
3. **Ontological Type Inference:**
   - Dynamically resolves domain nouns into ontological categories:
     - Discrete counts $\to$ `Entity?`
     - Aggregations $\to$ `Set?`
     - Contextual domains $\to$ `Domain?`
4. **Canonical 4-Block Assembly:**
   - Wraps inferred logic into standard `Module`, `Opening`, `Body`, and `Closing` blocks.

Concrete Transduction Walkthrough

Input Natural Language Prompt:

```text
"Add 5 units to inventory A which contains 12 units"
```

Inferred 4-Block OmniCode Reel:

```omni
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ================================================================================
```
```

```
Module < NaturalReel.Addition > ( Add 5 units to inventory A which contains 12 units ) {
    version: < "1.0.0" >,
    system: < OmniCode.Core >,
    semantics: < TrackPhysics :: MultiTape :: AIInference >
}

Units < Entity? > ( Inferred discrete unit: resolved from 'Units' )
Inventory < Set? > ( Inferred collection container: resolved from 'Inventory' )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    import: [ Core.Arithmetic :: Core.Logic :: Core.Vectors ],
    preconditions: [ +1 ]
}

inventory_a [ 12 ] ( Initial baseline state of target container )
transfer_units [ 5 ] ( Incremental operand value )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    result_inventory_a [ inventory_a + transfer_units ]
    inventory_a --> result_inventory_a ( Directional causal update )
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [ result_inventory_a = 17 ],
    commit_status: [ +1 ]
}
```

---

3. Verification, Telemetry & Invariant Guarantees

1. **State Certification:** Transduced programs are executed through the [`Evaluator`](file:///home/professorseanex/OmniCode/src/runtime/evaluator.rs) before any output is returned to the user.
2. **Dual Log Persistence:** Both `.scroll` and `.log` artifacts are inscribed in `scrolls/` and verified to be valid on disk.
3. **Conversational Synthesis:** A natural-language explanation is generated alongside the machine state, guaranteeing dual human-machine transparency.

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/04_cognitive_and_autonomous_systems/02_episodic_scrolls_and_experiential_learning.md

MD | 130 LINES | 573 WORDS | 5.2 KB

```
# Volume 4: Cognitive & Autonomous Systems

## Document 02: Episodic Scrolls & Experiential Learning Archive

> **Homoiconic Trace Recording and Continuous Machine Learning from Past Execution Experiences.**

OmniCode introduces an episodic learning model where every execution—whether initiated through the interactive CLI, the AI Cortex, or test harnesses—is permanently inscribed into a dual-format episodic memory bank:

1. **Native OmniCode Scroll (`.scroll`):** A fully homoiconic, valid 4-Block Turing reel recording the initial prompt, inferred types, synthesized AST, self-healing repairs, and postconditions.
2. **Traditional Telemetry Log (`.log`):** Microsecond-resolution execution timings, structured channel events, and trapped diagnostic failpoints.

---

### 1. Inscription Topology & File Naming Invariants

All cognitive sessions persist artifacts into the `scrolls/` directory:

```text
scrolls/
├── <timestamp>_<seq>_<session_id>.scroll    # Native 4-Block Turing Reel
└── <timestamp>_<seq>_<session_id>.log       # Microsecond Telemetry & Diagnostics
```

Naming Convention Invariants

* **Timestamp Prefix:** Microseconds since UNIX epoch (e.g., `1791492898991747`).
* **Sequence Counter:** 4-digit hexadecimal counter (`0000` to `FFFF`).
* **Session Identifier:** Unique alphanumeric identifier (`sess_...`).

---

2. The Homoiconic Anatomy of an OmniCode `.scroll` File

An OmniCode `.scroll` is not passive JSON or XML; it is executable OmniCode code:

```omni
# ============================================================================
# BLOCK 1: METADATA BLOCK (THE COGNITIVE SCROLL)
# ============================================================================
Scroll < EpistemicTrace.sess_1791492898991747_0000 > ( Add 5 units to inventory A which contains 12 units ) {
    version: < "1.0.0" >,
    system: < OmniCode.AI.Model >,
    timestamp: < "1791492898991747_0000" >,
    session_id: < "sess_1791492898991747_0000" >,
    execution_duration_micros: < 5804 >,
    cognitive_mode: < NeuralSymbolicTransduction >
}

# ============================================================================
# BLOCK 2: OPENING BLOCK (EXPERIENCE INITIALIZATION)
# ============================================================================
Opening {
    import: [ Core.Arithmetic :: Core.Logic :: Core.Vectors ],
    preconditions: [ +1 ]
}

user_prompt < "Add 5 units to inventory A which contains 12 units" >

# ============================================================================
# BLOCK 3: BODY BLOCK (CHRONICLE OF EXECUTION & RESTORATION)
# ============================================================================
Body [
    # Immune System Interventions (Restorator):
    repair_entry [ L1: AddImport --> "Injected library imports into Opening block: import: [ Core.Vectors ]" ]

    # Executed Turing Reel Synthesized by AI Model:
    synthesized_reel [
        # ... executable 4-Block module ...
    ]
]

# ============================================================================
# BLOCK 4: CLOSING BLOCK (EPISODIC COMMIT & LEARNING STATUS)
# ============================================================================
```
```

```
Closing {
    commit_status: [ <PROCEED> ],
    verification_proof: [ +1 ],
    learning_ready: [ +1 ]
}
```

---

3. Episodic Memory Digestion: `AILearner`

The [`AILearner`](file:///home/professorseanex/OmniCode/src/ai/model/learner.rs) scans the `scrolls/` directory and digests past experiences:

```rust
let learner = AILearner::new("scrolls");
let summary = learner.digest_experiences()?;
println!("Total Inscribed Episodes: {}", summary.total_episodes);
println!("QuadState Distribution: Proceed: {}, Await: {}, Rollback: {}, Halt: {}",
    summary.proceed_count, summary.await_count, summary.rollback_count, summary.halt_count);
println!("Learned Repairs: {}", summary.total_repairs_learned);
```

CLI Inspection

Developers can inspect the episodic archive at any time from the command line:

```bash
cargo run -- scrolls
```

Output:

```text
================================================================================
  OmniCode AI: Episodic Memory Bank & Experiential Learning Archive
================================================================================

EPISODIC LEARNING SUMMARY:
  • Total Inscribed Episodes:     1
  • State Distribution:           Proceed (+1): 1 | Halt (NULL): 0 | Rollback (-1): 0 | Await (0): 0
  • Restorator Repairs Learned:   1

RECENT EPISODES:
  [ 1] Session: sess_1791492898991747_0000 | State: +1:PROCEED  | Repairs:  1 | Failpoints:  1 | .log: yes
       Prompt: "Add 5 units to inventory A which contains 12 units"
       Scroll: "scrolls/1791492898991747_0000_sess_1791492898991747_0000.scroll"
```

---

4. Continuous Improvement & Invariant Guarantees

1. **Zero Data Loss:** Every run produces verifiable records; intermittent crashes or rollbacks are fully chronicled for diagnostic autopsy.
2. **Replayability:** A `.scroll` can be fed directly back into `omnicode run` to deterministically reproduce any historical computation.
3. **Model Refinement:** Inscribed repairs provide ground truth training pairs for the next generation of neural-symbolic transducers.

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/04_cognitive_and_autonomous_systems/03_autonomous_restorator_and_self_healing.md

MD | 111 LINES | 570 WORDS | 4.6 KB

```
# Volume 4: Cognitive & Autonomous Systems

## Document 03: The Restorator & Autonomous Self-Healing Diagnostics

> **An Autonomous Linguistic Immune System That Repairs Syntax, Delimiter Morphology, and Structural Anomalies.**

Conventional compilers are passive and punitive: upon encountering a missing delimiter or an unclosed block, they stop immediately with an error message and exit.

In contrast, OmniCode includes an **active diagnostic immune system**:

1. [`Restorator`](file:///home/professorseanex/OmniCode/src/diagnostics/restorator.rs): Proactively repairs broken source files, balances mismatched delimiters, and scaffolds missing architectural blocks.
2. [`OmniDebugger`](file:///home/professorseanex/OmniCode/src/diagnostics/debugger.rs): Maintains execution snapshots and rolls back environment state when `-1:ROLLBACK` or caveat vetoes are triggered.
3. [`DiagnosticLogger`](file:///home/professorseanex/OmniCode/src/diagnostics/logger.rs): Tracks failpoints with structured taxonomy (`FP_BOUNDARY_LEAK`, `FP_IMMUTABLE_MUTATION`, `FP_ROLLBACK_TRIGGERED`, etc.).

---

### 1. Repair Hierarchy & Morphological Preconditions

The Restorator evaluates problems along a 4-level hierarchy:

| Level | Kind | Trigger Condition | Autonomous Action |
| :---: | :--- | :--- | :--- |
| **L0** | `FormatOnly` | Inconsistent whitespace or line endings | Normalizes indentation and block separation. |
| **L1** | `ImportInjection` | Standard keywords used without module imports | Injects `import: [ Core.Arithmetic :: Core.Logic :: Core.Vectors ]`. |
| **L2** | `BoundaryBalance` | Unclosed `[`, `<`, `{` delimiters or rank crossing | Closes unclosed delimiters respecting morphological hierarchy. |
| **L3** | `BlockScaffold` | Missing `Metadata`, `Opening`, `Body`, or `Closing` | Auto-scaffolds missing 4-block headers and wraps expressions. |

---

### 2. Repair Algorithms & Operational Mechanics

#### Autonomous Boundary Balancing Algorithm

When a file contains unclosed delimiters (e.g., `state [ +1`), the Restorator scans the token stream:

1. Pushes opening delimiters onto a morphological balance stack.
2. If the stack is non-empty at EOF or before a closing block boundary, pops unclosed delimiters in reverse order.
3. Appends the corresponding closing delimiter (`]`, `>`, `}`) with appropriate rank preservation.

#### Autonomous Structural 4-Block Scaffolding

If raw code is provided without block demarcations:

```omni
x [ 10 ]
y [ 20 ]
z [ x + y ]
```

The Restorator automatically transforms it into:

```omni
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ================================================================================
Module < AutoRestored > ( Autonomously healed module ) {
    version: < "1.0.0" >,
    system: < OmniCode.Core >
}

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    import: [ Core.Arithmetic :: Core.Logic :: Core.Vectors ],
    preconditions: [ +1 ]
}

x [ 10 ]
y [ 20 ]
```
```

```
# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    z [ x + y ]
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [ +1 ],
    commit_status: [ +1 ]
}
```

CLI Command: `omnicode restore`

```bash
# Preview repairs (dry-run mode)
cargo run -- restore examples/draft_file.omni

# Apply repairs directly to the file
cargo run -- restore examples/draft_file.omni --write
```

Transactional Rollback: `OmniDebugger`

During execution, mutating statements take an environment snapshot before performing writes:

* If the result evaluates to `-1:ROLLBACK` or a caveat `! [ condition ]` evaluates to false, the debugger restores the snapshot.
* **Cyclic Retroaction Protection:** Tracks repeated transitions back to the same snapshot. If cycles exceed the threshold (default: 10), halts execution with `FP_CYCLIC_RETROACTION` to prevent infinite loops.

---

3. Verification & Invariant Proofs

1. **Non-Destructive Guarantee:** In dry-run mode, files are never modified without the `--write` flag.
2. **Linter Re-Verification:** After a file is repaired, the Restorator passes it through [`OmniLinter`](file:///home/professorseanex/OmniCode/src/diagnostics/linter.rs) to prove that the resulting code is 100% compliant before committing to disk.

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/04_cognitive_and_autonomous_systems/04_bare_metal_and_cross_platform_toolchain.md

MD | 68 LINES | 382 WORDS | 3.0 KB

```
# Volume 4: Cognitive & Autonomous Systems

## Document 04: Bare-Metal OS & Cross-Platform Toolchains

> **Targeting Bare-Metal Silicon, LLVM Compilation, and Hardware Emulators from First Principles.**

OmniCode is designed to function as an Operating System kernel and bare-metal systems language without relying on external C runtimes, libc, or garbage collectors.

---

### 1. Supported Bare-Metal Target Architectures

OmniCode's bare-metal layer targets `no_std` environments across three major CPU architectures:

| Target Triple | Architecture | Instruction Set | Emulation Platform |
| :--- | :--- | :--- | :--- |
| `x86_64-unknown-none` | Intel / AMD 64-bit | x86_64 Long Mode | `qemu-system-x86_64` |
| `aarch64-unknown-none` | ARMv8-A 64-bit | AArch64 | `qemu-system-aarch64` |
| `riscv64gc-unknown-none-elf` | RISC-V 64-bit | RV64GC | `qemu-system-riscv64` |

---

### 2. Containerized Emulation & Toolchain Infrastructure

To provide a fully reproducible toolchain across Linux, macOS, and Windows without manual host dependency installation, OmniCode provides a standardized container environment via [`Dockerfile`](file:///home/professorseanex/OmniCode/Dockerfile) and [`docker-compose.yml`](file:///home/professorseanex/OmniCode/docker-compose.yml):

```bash
# Build and launch the container
docker compose up -d

# Open interactive bash session in the container
docker compose exec omnicode-toolchain bash
```

Container Capabilities

* **Compilers & Assemblers:** `rustc 1.85+`, `clang`, `lld`, `llvm`, `nasm`, `yasm`.
* **Hardware Emulation:** `qemu-system-x86`, `qemu-system-arm`, `qemu-system-misc`.
* **Bootloader Utilities:** `grub-pc-bin`, `xorriso`, `mtools` for generating bootable ISO images.
* **Remote Debugging:** `gdb-multiarch` wired to QEMU GDB stub on port `1234`.

Toolchain Verification Script

The [`scripts/check_toolchain.sh`](file:///home/professorseanex/OmniCode/scripts/check_toolchain.sh) script verifies the status of all compilers, assemblers, and bare-metal targets:

```bash
./scripts/check_toolchain.sh
```

---

3. Bare-Metal Memory Model & Boundary Mapping

In bare-metal mode, OmniCode's morphological boundaries map directly to physical hardware memory structures:

* `[...]` (Rigid): Fixed hardware registers (e.g., MMIO ports, control registers `CR0-CR4`), physical page frames, and static arrays.
* `<...>` (Dynamic): Thread stacks, heap allocators, and volatile registers.
* `{...}` (Connotation): CPU privilege rings (`Ring 0` kernel vs `Ring 3` userland), page table permissions (`RWX`), and virtual address space namespaces.

---

4. Hardware Verification & Safety Invariants

1. **Memory Isolation:** Boundary crossings between `{...}` universes verify page privilege levels before memory is addressed.
2. **Interrupt Safety:** Asymmetric delimiters `{...]` and `[...}` model hardware interrupt service routines:
   * `{...]`: Absorbs hardware interrupts from the external physical environment into a fixed kernel status block.
   * `[...}`: Emits fixed command words out to peripheral device buses.
```

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/04_cognitive_and_autonomous_systems/05_core_standard_libraries.md

MD | 64 LINES | 333 WORDS | 2.7 KB

```
# Volume 4: Cognitive & Autonomous Systems

## Document 05: Core Standard Library Architecture

> **Axiomatic Modules Grounded in Balanced Ternary Logic, Safe Arithmetic, and Directional Vectors.**

The OmniCode Standard Library lives under [`lib/core/`](file:///home/professorseanex/OmniCode/lib/core) and provides the core algebraic foundation for the language. Every standard library file is written in canonical 4-Block OmniCode.

---

### 1. Standard Library Modules & Topology

| Module Name | Source File | Description |
| :--- | :--- | :--- |
| `Core.Arithmetic` | [`lib/core/arithmetic.omni`](file:///home/professorseanex/OmniCode/lib/core/arithmetic.omni) | Balanced ternary arithmetic, addition, subtraction, multiplication, and non-zero division. |
| `Core.Logic` | [`lib/core/logic.omni`](file:///home/professorseanex/OmniCode/lib/core/logic.omni) | Ternary Kleene and Lukasiewicz logic gates (AND, OR, NOT, XOR, and Consensual Agreement). |
| `Core.Vectors` | [`lib/core/vectors.omni`](file:///home/professorseanex/OmniCode/lib/core/vectors.omni) | Directional coordinate vectors across Being, Causality, and Scale axes with caveat checks. |

---

### 2. Core Mathematical & Logical Specifications

#### `Core.Arithmetic`

Guarantees quad-state mathematical correctness:

* **Addition:** $a + b \implies$ produces sum when both operands are valid; returns `NULL` on overflow or trap.
* **Safe Division:** Division by zero returns `NULL:HALT` without raising an exception:

  ```omni
  divisor != 0 ! [ divisor = 0 --> NULL ]
  ```

`Core.Logic`

Implements full balanced ternary logic gates:

* **Consensual AND (`::`):**
  $$\text{AND}(a, b) = \min(a, b)$$
* **Ternary OR (`|`):**
  $$\text{OR}(a, b) = \max(a, b)$$
* **Ternary NOT (`--`):**
  $$\text{NOT}(x) = -x$$
* **Consensual Agreement:** Returns `+1` if both agree, `-1` if in contradiction, and `0` if either is awaiting consensus.

`Core.Vectors`

Implements 3D directional physics:

* **Causality (`-->`, `<--`):** Drives causal transformations forward and retroactively verifies feedback.
* **Scale (`^--`, `v--`):** Manages abstraction transitions between primitive memory buffers and high-level types.
* **Caveat Pipeline (`!`):** Evaluates guard conditions prior to committing state transitions:

  ```omni
  a --> b ! [ precondition = +1 ]
  ```

---

3. Invariant Proofs & Resolution Guarantees

1. **Self-Contained Execution:** All standard library functions are verified in `tests/test_failpoints.rs` (`test_lib_core_vectors`, `test_svo_arithmetic_keywords_and_infer_operator`).
2. **Deterministic Resolution:** The compiler automatically resolves `import: [ Core.Arithmetic :: Core.Logic :: Core.Vectors ]` directly to `lib/core/`.
```

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/03_architecture/01_coordinate_system_of_computation.md

MD | 39 LINES | 212 WORDS | 1.7 KB

```
# Volume 3: Architecture & Execution

## Document 01: The 3D Coordinate System of Computation

---

### 1. The Three Orthogonal Axes

Every computational entity, transformation, and expression in OmniCode is positioned within a 3-dimensional coordinate space:

```text
                              ▲ +Z (Scale: Layer Up / Builds To: --^ / -^)
                              |
                              |
       -X (Action: Backward)  |       +X (Action: Forward)
       <-- / <- Act Again     |       --> / -> Act Upon
       ◄──────────────────────┼──────────────────────────►
      (Feedback / Rollback)   |       (Causation / Pipeline)
                              |
                              |
                              ▼ -Z (Scale: Layer Down / Breaks Down From: --v / -v)

                [ Y-Axis: Being / Identity: = (IS), != (IS NOT), ≈ (IS LIKE) ]
```

---

2. The Orthogonal Dimensions

1. **The X-Axis: Temporal / Causal Vector (`-->` / `->` vs `<--` / `<-`)**
   * Governs forward causation vs. retroactive feedback/unwinding.
   * Interacts directly with the Quad-State engine: `+1` moves along $+X$, `-1` moves along $-X$.
2. **The Y-Axis: Ontological Identity (`=`, `!=`, `≈`)**
   * Governs equivalence and relation of being in state space.
3. **The Z-Axis: Abstraction Scale (`--^` / `-^` vs `--v` / `-v`)**
   * Governs the movement between low-level hardware representation and high-level conceptual modeling.
   * `--^` (shorthand `-^`) constructs high-level types from low-level memory layouts.
   * `--v` (shorthand `-v`) projects high-level models down to machine primitives.
```

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/03_architecture/02_execution_pipeline.md

MD | 56 LINES | 507 WORDS | 3.9 KB

```
# Volume 3: Architecture & Execution

## Document 02: The Unified Execution Pipeline

---

### 1. Unified Architecture Across Three Execution Modes

OmniCode allows the exact same code to be:

1. **Compiled (AOT Native):** Ahead-of-time compilation via LLVM or assembler to standalone native binaries.
2. **Interpreted:** Real-time in-memory execution via AST/bytecode evaluation for interactive REPL and hot-reloading.
3. **Transpiled:** Source-to-source emission of ISO C99, C++, or WebAssembly for universal deployment.

```mermaid
flowchart TD
    Source["OmniCode Source (.omni)"] --> Lexer["Lexer (Boundary & Directional Tokenizer)"]
    Lexer --> Parser["Ontological Parser"]
    Parser --> AST["Abstract Syntax Tree with First-Class Asides"]
    AST --> Semantics["Ontological Type & Context Verifier"]
    Semantics --> HIR["High-Level Intermediate Representation"]

    HIR -->|Mode 1: Interpreted| Evaluator["Quad-State VM / Evaluator (Immediate REPL)"]
    HIR -->|Mode 2: Compiled| LLVMBackend["LLVM IR Generator -> Native ELF/PE/Mach-O"]
    HIR -->|Mode 3: Transpiled| CEmitter["C99 / WASM Emitter (Portable Source)"]
```

---

2. Role of the Boundary Elements in the Pipeline

* **Denotation `[...]` and Invariant `<...>`:** Directly mapped to data structures, memory definitions, and logic bodies in the target backend.
* **Connotation `{...}`, `{...]`, and `[...}`:** Injected into the semantic checker to establish safety constraints, stack/heap qualifiers, and variable resolution rules.
* **Aside `(...)`:** Maintained in debug tables, emitted as formatted doc-comments in transpiled code, and evaluated by the verifier for formal invariant validation.
* **Quad-State Engine (`-1, 0, 1, NULL`):**
  * In the interpreter: Drives the runtime state machine directly.
  * In native C/LLVM compilation: Translated to integer return codes, branch vectors, and zero-cost error frames.

---

3. The Interactive Terminal Environment (REPL): Why It Is Essential

The interactive terminal environment (`omnicode` / `cargo run -- repl`) is not an afterthought; it is an essential foundational pillar of OmniCode's early development:

1. **Immediate Feedback Loop for Unprecedented Physics:**
   OmniCode introduces concepts absent in traditional C/Python/Rust languages: balanced ternary logic ($\mathbb{T}_4 = \{-1, 0, +1, \text{NULL}\}$), morphological boundary closures (`[...]`, `<...>`, `{...}`, `{...]`, `[...}`), and 3D coordinate vectors (`-->`, `<--`, `^--`, `v--`). Requiring developers to write full 4-block files and compile them AOT just to understand how a caveat (`!`) suppresses a transaction introduces excessive friction. The terminal environment gives sub-millisecond feedback for every single delimiter and operator.

2. **Real-time Manifestation of the Interpreted Pillar:**
   By establishing an interactive in-memory evaluator from day one, we guarantee that the grammar and AST definitions are cleanly decoupled from low-level LLVM code generation. The interpreter proves that the AST contains all necessary semantic and ontological data to execute autonomously.

3. **Living Failpoint & Transaction Rollback Observatory:**
   In conventional languages, runtime failures manifest as unhandled exceptions or fatal panics. In OmniCode, transitions into `-1` (Rollback) or `NULL` (Halt) are first-class ontological occurrences. The terminal environment acts as a living observatory, logging microsecond timestamps, tracking transaction snapshot unwindings, and visually displaying failpoints without crashing the session.

4. **Human-AI Co-Reasoning Sandbox:**
   Because OmniCode features first-class Asides `(...)` designed for machine-readable intent, the interactive terminal provides an ideal conversational scratchpad where human developers and AI coding agents can interactively enter expressions, verify boundary contracts, and inspect state bindings before committing logic to permanent source repositories.
```

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/03_architecture/03_four_block_architecture.md

MD | 134 LINES | 739 WORDS | 6.4 KB

```
# Volume 3: Architecture & Execution

## Document 03: The Universal 4-Block Architecture & The Rust Foundation

---

### 1. The Universal 4-Block Lifecycle

Every code file in OmniCode—regardless of whether it is an `.omni` source file or a compiler module—adheres to a strict **4-Block Lifecycle Protocol**:

```text
┌──────────────────────────────────────────────────────┐
│                BLOCK 1: METADATA BLOCK               │
│   (Module Identity, Invariant Axioms, Semantics, Asides)│
├──────────────────────────────────────────────────────┤
│                BLOCK 2: OPENING BLOCK                │
│   (Context Setup, Preconditions, Scoped Declarations)  │
├──────────────────────────────────────────────────────┤
│                BLOCK 3: BODY BLOCK                   │
│   (Core Transformations, Causality Vectors, Logic)     │
├──────────────────────────────────────────────────────┤
│                BLOCK 4: CLOSING BLOCK                │
│   (Postconditions, Invariant Integrity Proofs, Commit) │
└──────────────────────────────────────────────────────┘
```

A. Block 1: Metadata Block

* **Role:** Establishes the ontological identity of the module, licensing, semantic dependencies, and invariant axioms.
* **Grammar Elements:** `Module < Name > ( Intent Aside ) { ... }`, Invariants `< ... >`.

B. Block 2: Opening Block

* **Role:** Sets up the execution environment, verifies preconditions, initializes state instances, and binds contextual universes.
* **Grammar Elements:** `Opening { requires: [ ... ], preconditions: [ ... ] }`, Instances `[ ... ]`.

C. Block 3: Body Block

* **Role:** Implements the operational logic, directional pipelines, being relations, and caveat constraints.
* **Grammar Elements:** `Body [ source --> target ! caveat ]`, Vectors `-->`, `<--`, `^--`, `v--`.

D. Block 4: Closing Block

* **Role:** Verifies postconditions, proves invariant satisfaction, handles rollback teardown, and yields the final commit QuadState.
* **Grammar Elements:** `Closing { verify: [ ... ], commit_status: [ +1 ] }`.

---

2. Concrete Example: [examples/canonical_notation.omni](file:///home/professorseanex/OmniCode/examples/canonical_notation.omni)

```omni
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ================================================================================
Module < CanonicalNotationShowcase > ( Foundations of Being, Causality, and Abstraction ) {
    version: < "1.0.0" >,
    author: < "ProfessorSeanEX" >,
    system: < OmniCode.Core >,
    semantics: < BalancedTernary :: QuadState :: BoundaryPhysics >
}

# Axiomatic Categories (Invariant Sets)
A < +1 > ( Invariant category A: axiomatic ground truth )
B < +1 > ( Invariant category B: independent set domain )

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ================================================================================
Opening {
    requires: [ MemoryAligned :: TypeChecking ],
    initial_truth: [ +1 ]
}

```
```

```
a [ +1 ] ( Particular instance 'a' with mutable state )
b [ +1 ] ( Particular instance 'b' with mutable state )
a_in_A [ a ] { A } ( Instance 'a' validated within contextual universe A )

# ================================================================================
# BLOCK 3: BODY BLOCK
# ================================================================================
Body [
    instance_typing [ a : A ]
    identity_check [ a = a ]
    forward_action [ a --> b ]
    synthesis [ a ^-- A ]
    pipeline [ a --> b ! [ a : A :: b : B ] ]
]

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ================================================================================
Closing {
    verify: [
        identity_check = +1 ::
        forward_action = +1 ::
        pipeline = +1
    ],
    on_rollback: [ <-- unwind_state ],
    commit_status: [ +1 ]
}
```

---

3. Reasoning for Using Rust as the Core Engine

To ensure that the language engine is uncompromising at both low and high levels, the OmniCode compiler and runtime were implemented in **Rust**:

```mermaid
flowchart TD
    subgraph RustAdvantages ["Why Rust as the OmniCode Foundation"]
        R1["Memory Safety Without Garbage Collection\nZero-cost pointers, no stop-the-world pauses"]
        R2["Algebraic Data Types & Exhaustive Matching\nGuarantees all 6 boundaries & 4 quad-states are handled"]
        R3["Zero Runtime Buckling\nImpervious to memory leaks, buffer overruns, and data races"]
        R4["LLVM & C ABI Native Compatibility\nDirect bindings to LLVM IR (inkwell) and bare-metal compilation"]
    end
```

1. Zero Runtime Buckling

A language that layers up from bare metal cannot afford to buckle under concurrency or memory corruption. Rust’s strict borrow checker and ownership model ensure that the OmniCode compiler, parser, and diagnostic engines execute with zero undefined behavior.

2. Pattern Matching Over Morphological Boundaries

The OmniCode boundary system (`[]`, `<>`, `{}`, `{]`, `[}`, `()`) requires non-trivial parsing logic. Rust's pattern matching (`match`) allows the parser and evaluator to handle asymmetric boundaries and directional vectors cleanly with compile-time exhaustiveness checks.

3. Deterministic Transactional Snapshots

The balanced ternary `-1` (Rollback) state requires snapshotting the environment and unwinding state upon failure. In Rust, cloning scoped bindings and performing deterministic unwinding is explicit, predictable, and fast.

4. Foundation for Future AOT & Transpilation

Because Rust has direct access to LLVM C/C++ APIs, the OmniCode core is primed to generate LLVM IR for AOT native compilation and emit optimized ISO C99 code for universal cross-platform deployment.

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/02_logic_and_algebra/01_balanced_ternary_quad_state.md MD 76 LINES 536 WORDS 3.3 KB

```
# Volume 2: Logic & Algebra

## Document 01: Balanced Ternary & The Quad-State Engine

---

### 1. The Quad-State Truth Space & Micro/Macro Duality

OmniCode replaces Boolean logic (`0` and `1`) with a 4-state system grounded in **Balanced Ternary Logic** with a terminal **Null State**:

$$\mathbb{T}_4 = \{ -1, \; 0, \; +1, \; \text{NULL} \}$$

The engine operates across a fundamental **Micro / Macro Duality**:

| State Symbol | Micro Level (Epistemic / Stance) | Macro Level (Systems / Physics) | Directional Vector | OS / Machine Meaning |
| :---: | :--- | :--- | :---: | :--- |
| **`+1`** | **`yes`** (Affirmation / Condition holds) | **`PROCEED`** (Monotonic commit) | `-->` / `->` | Advance PC, commit transaction frame |
| **`0`** | **`ok`** (Neutral equilibrium / Balance) | **`AWAIT`** (Standby / Async yield) | `---` | Yield thread, wait queue, idle / `HLT` |
| **`-1`** | **`no`** (Refutation / Disagreement) | **`ROLLBACK`** (Retroactive unwind) | `<--` / `<-` | Unwind memory snapshot, retry vector |
| **`NULL`** | **`void`** (Absence / Non-existence) | **`HALT`** (Boundary trap / Bottom ⊥) | `-x-` | Trap handler, kernel panic, abort |

```text
    Micro (Linguistic):     [ no ]      ---      [ ok ]      ---      [ yes ]       -x-  [ void ]
                              |                    |                    |                    |
    Value:                   -1                    0                   +1                  NULL
                              |                    |                    |                    |
    Macro (Systems):      ROLLBACK    <--        AWAIT       -->     PROCEED        -x-     HALT
```

---

2. Algebraic Symmetry and Negation (`--`)

In binary logic, negation flips $0 \leftrightarrow 1$.
In OmniCode, negation is pure algebraic reflection around the zero equilibrium point:

$$\operatorname{NOT}(x) = -x$$

* $-(+1) = -1$ (NOT Proceed is **Rollback**)
* $-(-1) = +1$ (NOT Rollback is **Proceed**)
* $-(0) = 0$ (NOT Equilibrium is **Equilibrium**)
* $-(\text{NULL}) = \text{NULL}$ (NOT Void is **Void**)

---

3. Truth Tables for Fundamental Connectives

Conjunction (`::` AND)

Evaluates to the greatest lower bound (minimum):
$$\operatorname{AND}(A, B) = \min(A, B) \quad (\text{with NULL acting as an absorbing trap})$$

Disjunction (`|` OR)

Evaluates to the least upper bound (maximum):
$$\operatorname{OR}(A, B) = \max(A, B) \quad (\text{with NULL acting as an absorbing trap})$$

A	B	$A :: B$ (AND)	$A \mid B$ (OR)	$--A$ (NOT)
$+1$	$+1$	$+1$	$+1$	-1
$+1$	0	0	$+1$	-1
$+1$	-1	-1	$+1$	-1
0	0	0	0	0
0	-1	-1	0	0
-1	-1	-1	-1	$+1$
NULL	$*$	NULL	NULL	NULL

---

4. Direct Mapping to Runtime Mechanics

1. **State `+1` (Proceed):** Advances the program counter, commits current state mutations, and passes through the forward arrow
```

`-->`.
2. **State `0` (Await):** Suspends execution without failure, yielding CPU or awaiting asynchronous event resolution.
3. **State `-1` (Rollback):** Reverts all mutations executed within the current boundary and invokes the backward arrow `<--`.
4. **State `NULL` (Halt):** Immediate abort. Used for fatal assertions, memory out-of-bounds, or program exit.

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/02_logic_and_algebra/02_relational_connectives_and_operators.md MD 56 LINES 365 WORDS 2.2 KB

```
# Volume 2: Logic & Algebra

## Document 02: Relational Connectives & Operators

---

### 1. Relational Connectives

OmniCode incorporates natural linguistic and relational operators into its formal grammar:

#### A. The Adversative Conjunction (`!` BUT)

In traditional Boolean logic, "A but B" is flattened into a naive "A and B". In OmniCode, **`!` (BUT)** introduces an explicit **adversative constraint / caveat**:
$$A \text{ ! } B \iff A \text{ executes, BUT must satisfy caveat } B$$
If caveat $B$ evaluates to `-1` (Rollback) or `NULL` (Halt), the execution of $A$ is immediately unwound and suppressed.

#### B. Cumulative Conjunction (`::` AND)

Represents co-presence and mutual satisfaction. Both sides must hold or execute simultaneously.

#### C. Relational Projection (`:` IN RELATION TO / TO BE AS)

Maps an entity to a perspective, category, or role.

* Used for typing: `x : Integer` ("x in relation to Integer").
* Used for contextual roles: `user : Admin` ("user in relation to Admin role").

#### D. Disjunction (`|` OR)

Represents branching alternatives and non-deterministic choice.

#### E. Negation (`--` NOT)

Inverts the quad-state value across the zero balance line.

---

### 2. Relations of Being (Ontological Identity)

| Operator | Plain Language | Mathematical Concept | Meaning |
| :---: | :--- | :--- | :--- |
| **`=`** | **IS / TO BE** | Identity ($\equiv$) | Exact equivalence in value, shape, and essence. |
| **`!=`** | **IS NOT / TO BE NOT** | Non-identity ($\not\equiv$) | Distinctness; exclusion. |
| **`≈`** or **`~=`** | **TO BE LIKE / Liken To** | Homomorphism / Analogy | Structural compatibility; behavioral similarity without identical essence. |

---

### 3. Directional Flow Operators

| Operator | Plain Language | Vector Direction | Role |
| :---: | :--- | :---: | :--- |
| **`-->`** | **Act Upon** | Forward ($\rightarrow$) | Causation, pipeline, execution step, event dispatch. |
| **`<--`** | **Act Again** | Backward ($\leftarrow$) | Feedback, retry, undo, rollback, reactive subscription. |
| **`^--`** | **Which Builds To** | Upward ($\uparrow$) | Layering up, abstraction, synthesis, composition. |
| **`v--`** | **Which Breaks Down From** | Downward ($\downarrow$) | Decomposition, reduction, destructuring, compilation to IR. |
```

<TRACK 5> : {Infrastructure, Operations & Archives}/docs/02_logic_and_algebra/03_the_quad_state_accumulator_loop_and_named_registers.md

MD | 259 LINES | 2254 WORDS | 17.9 KB

```
# Volume 2: Logic & Algebra

## Document 03: The Quad-State Accumulator Loop & Named Silicon Registers

---

### 1. Architectural Genesis: The Death of the Imperative Jump

In legacy computer architecture (x86, ARM, C, Python), a "loop" is treated as an imperative jump instruction (`JMP / JNZ`) wrapped around an impoverished 2-valued boolean (`true / false`). Because binary logic lacks vocabulary for intermediate states, languages bolted on a fragile patchwork of external keywords:

* `continue` (advance to next)
* `break` (escape early)
* `yield` / `sleep` (wait for hardware/scheduler)
* `retry` / `catch` (undo a bad mutation)

In **OmniCode**, a loop is neither a jump nor an imperative hack.
**A loop is an ontologically grounded State Machine and Balanced Ternary Accumulator Register cycling through the Quad-State truth space:**

$$\mathbb{T}_4 = \{ -1, \quad 0, \quad +1, \quad \text{NULL} \}$$

---

### 2. How Computers Use Registers: History & Functional Roles

#### Why Registers Exist in Hardware

Registers are the smallest, fastest storage elements in a computing machine, situated directly inside the CPU core alongside the Arithmetic Logic Unit (ALU).

* **Zero Latency:** Accessing a register takes $0$ to $1$ clock cycles ($< 0.5 \text{ ns}$), whereas accessing L1 cache takes $\sim 1 \text{ ns}$, L3 cache takes $\sim 10\text{--}20 \text{ ns}$, and main RAM takes $\sim 60\text{--}100 \text{ ns}$.
* **Physical Constraint:** The ALU cannot execute vector transformations or balance comparisons directly across external memory buses without stalling execution pipelines. Data must be loaded into local registers, transformed, and retired back to storehouses.

#### Historical Evolution of Register Counts

* **8-Bit Epoch (6502, Z80):** 3 to 14 registers (`A` accumulator, `X`/`Y` index, `SP`, `PC`, `P` flags).
* **x86-32 CISC:** 8 general-purpose registers (`EAX`, `ECX`, `EDX`, `EBX`, `ESP`, `EBP`, `ESI`, `EDI`) + `EIP` + `EFLAGS`.
* **x86-64 AMD64:** 16 general-purpose registers (`RAX`..`R15`) + `RIP` + `RFLAGS`.
* **Modern RISC (ARM64, RISC-V):** 32 general-purpose registers (`R0`..`R31` / `x0`..`x31`).

#### Why Binary Registers Use Cryptic Shorthand

Legacy architectures named registers with 1970s shorthand (`AX` = Accumulator, `CX` = Count, `DX` = Data, `BX` = Base, `SP` = Stack Pointer, `BP` = Base Pointer, `SI` = Source Index, `DI` = Destination Index) or anonymous numbers (`r0`..`r31`).
Over decades of compiler optimization, these meaningful names devolved into anonymous scratchpads, widening the cognitive gap between human programmers, machine models, and physical silicon.

---

### 3. OmniCode Named Silicon Registers: The ALL CAPS Duality

OmniCode rejects anonymous register indices. Grounded in the principle that **Nouns are Defined and Verbs are Symbolized**, every register in the machine represents an explicit, named ontological actor.

#### Why ALL CAPS (`IT`) vs. Lowercase (`it`) Matters

In natural language and computation, casing is not decorative—it encodes **ontological hierarchy**:

1. **The Container vs. The Content:**
   * **`IT` (ALL CAPS)** signals the **Physical Silicon Hardware Register** (the physical container on the chip / architectural machine state).
   * **`it` (lowercase)** signals the **Dynamic Linguistic Pronoun** (the ephemeral value currently flowing through the sentence as an antecedent).
2. **Sovereign Invariance vs. Ephemeral Flow:**
   * In OmniCode, ALL CAPS is reserved exclusively for **Sovereign System Invariants**:
     * Quad-States: `PROCEED`, `AWAIT`, `ROLLBACK`, `HALT`
     * Cardinal Clauses: `WHO`, `WHAT`, `WHEN`, `WHERE`, `WHY`, `HOW`
     * Invariant Nouns: `TRIT_NOUN`, `CELL_NOUN`, `STOREHOUSE_NOUN`
     * Hardware Registers: `IT`, `ORIGIN`, `HERE`, `SELF`, `CALLER`, `OWNER`, `STEP`, `STATE`, `BOUND`, `INPUT`, `OUTPUT`
   * When the compiler or human reads `IT`, it signals **Direct Silicon Machine Binding**, bypassing userland scope lookups. When reading `it`, it signals **Linguistic Flow**, binding to the antecedent of the previous phrase.
3. **Zero Identifier Collision:**
   * A user or kernel function can safely have a variable or conversational pronoun `it` without ever colliding with the machine
```

register `IT`.

```text
┌──────────────────────────────────────────────────────────────────────────────────────────────────┐
│                                OmniCode Canonical Named Silicon Registers                        │
├──────────────┬──────────────┬──────────┬──────────────────────────┬──────────────────────────────┤
│ Hardware Name│ Natural Word │ Index    │ Ontological & Linguistic Role │ Loop & Machine Register Responsibility│
├──────────────┼──────────────┼──────────┼──────────────────────────┼──────────────────────────────┤
│ HEAD         │ head / here  │   0      │ Tape Head Witness / Cursor    │ Instruction Pointer (IP / PC)          │
│ HOME         │ home / origin│   1      │ Genesis Base Pointer          │ Pristine rollback landmark: HOME->IT   │
│ SPOOL        │ spool / owner│   2      │ Ribbon Stack Spool            │ Partition allocation stack ceiling     │
│ IT           │ it           │   3      │ Pipeline Antecedent (`it`)    │ Primary accumulator running sum: Acc+Δ │
│ SELF         │ self / me    │   4      │ 1st-Person Identity (`self`)  │ Active executing process principal     │
│ CALLER       │ caller / you │   5      │ 2nd-Person Principal (`you`)  │ Invoking parent / return authority     │
│ OTHER        │ other / them │   6      │ 3rd-Person Peer / Swarm       │ Worker thread pool / quorum handle     │
│ STATE        │ state        │   7      │ Status / QuadState Balance    │ Holds current T4 outcome (+1,0,-1,NULL)│
│ TURN         │ turn / step  │   8      │ Cadence / Cycle / Turn Count  │ Loop cycle counter: TURN = TURN + 1    │
│ BOUND        │ bound / limit│   9      │ Invariant Axiom Watchdog      │ < Invariant > boundary watchdog limit  │
│ FROM         │ from / in    │  10      │ Reading Transducer Port       │ Hardware streaming source coordinate   │
│ INTO         │ into / to    │  11      │ Writing Transducer Port       │ Hardware streaming destination coord   │
│ DISCARD      │ _ / void     │  12      │ Anonymous Discard Sink        │ Hardware null sink (like x0 / /dev/null│
└──────────────┴──────────────┴──────────┴──────────────────────────┴──────────────────────────────┘
```

---

4. The Loop as a Balanced Ternary Accumulator

In an OmniCode loop, the execution unit functions as a physical **Accumulator Register (`IT`)** evaluating deltas along the Radix-3 number line:

$$\dots \xleftarrow{\text{ROLLBACK (-1)}} \mathbf{-1} \quad \xleftrightarrow{\text{AWAIT (0)}} \quad \mathbf{0} \quad \xrightarrow{\text{PROCEED (+1)}} \mathbf{+1} \dots \quad \underset{\text{HALT (NULL)}}{\mathbf{-\times-}}$$

$$\operatorname{IT}_{t+1} = \operatorname{IT}_t + \Delta_{\mathbb{T}_4}$$

State Outcome	Machine Delta ($\Delta_{\mathbb{T}_4}$)	Silicon Register Action	Operational Loop Meaning
`+1: PROCEED`	**`+1`**	`IT += 1` :: `TURN += 1`	**Tick Up:** Advance to next turn, commit transaction frame.
`0: AWAIT`	**`0`**	`IT += 0` (No delta)	**Stop / Equilibrium:** Hold position, yield quantum, idle wait.
`-1: ROLLBACK`	**`-1`**	`IT -= 1` (or restore `HOME --> IT`)	**Tick Down / Unwind:** Revert turn, pop dirty frame, retry.
`NULL: HALT`	**Sentinel**	Latch `IT`, escape loop boundary	**Break / Terminate:** Goal achieved or watchdog boundary hit.

---

5. Syntactic Architecture of the STATE Loop

An OmniCode loop brings together the **Ontological Triad** (`<>`, `[]`, `{}`) with the **4-Branch Causality Tree**:

```omnicode
# ============================================================================
# CANONICAL QUAD-STATE LOOP DECLARATION (HARDWARE MACHINE REGISTERS)
# ============================================================================
STATE (
    < BOUND = 1000 >,                           # Rank 1: Invariant Watchdog Ceiling
    [ IT = 0, TURN = 0 ],                       # Rank 2: Silicon Accumulator & Cadence Registers
    { FROM @ COM1_Serial, INTO @ RAM_Buffer }   # Rank 3: Hardware Transducer Ports
) = [
    # 1. Advance Vector (+1): Ticks Up
    PROCEED  -WHEN-> { (FROM --> IT) & (IT --> INTO) & (IT plus 1 --> IT) & (TURN plus 1 --> TURN) },

    # 2. Standby Vector (0): Zero Velocity
    AWAIT    -WHEN-> { SENSOR_EMPTY | BUSY },

    # 3. Retroactive Vector (-1): Ticks Down / Rewinds
    ROLLBACK -WHEN-> { CHECKSUM_FAIL & (HOME --> IT) },

    # 4. Terminal Vector (NULL): Breaks out of continuum
    HALT     -WHEN-> { TURN = BOUND }
]
```

Dual Structural Symmetry: Push vs. Pull

Both syntactic orientations represent the same underlying circuit:

* **Form A (Inward / Pull - State Integration):**

  ```omnicode
  [ IT ] <-- STATE ( <BOUND>, {Context} ) -WHEN-> [ ... ]
  ```

```
  The accumulator **pulls** the ternary delta inward, integrating state across time ($\int \Delta dt$).

* **Form B (Outward / Push - State Actuation):**

  ```omnicode
  STATE ( <BOUND>, [IT], {Context} ) --> Action -WHEN-> [ ... ]
  ```

  The accumulator **pushes** its delta outward, actuating transformations upon physical memory or devices.

---

6. Physical Bare-Metal Implementation & Machine Word Encoding

When lowered by [`crate::runtime::assembler::OmniAssembler`], the `STATE` loop maps into 64-bit balanced-ternary machine words ([`Word64`]):

1. **Opcode `ASSERT_INVARIANT`:** Compares `STEP` against `BOUND`. If exceeded, triggers `HALT`.
2. **Opcode `BRANCH_TERNARY`:** Evaluates the `STATE` register (`%flags`):
   * `+1`: Dispatches forward action, adds $+1$ to `IT`, jumps to loop head.
   * `0`: Dispatches `PAUSE / HLT` instruction or cooperative task yield.
   * `-1`: Copies `ORIGIN` back into `IT`, rolling back uncommitted storehouse cells.
   * `NULL`: Unlinks stack frame and proceeds to post-loop instruction.

This unifies high-level human readability, machine AI reasoning, and bare-metal CPU hardware determinism into a single invariant mathematical construct.

---

7. The Triadic Paradigm Synthesis: Procedural, Functional, and OOP as One

OmniCode does not pick one programming paradigm at the expense of others. Instead, it synthesizes the greatest strengths of **Procedural**, **Functional**, and **Object-Oriented Programming** into a single coherent medium:

```text
                        ┌──────────────────────────────────────────┐
                        │            THE OMNICODE TRIAD            │
                        └──────────────────────────────────────────┘
                                            ▲
                                            │
                ┌───────────────────────────┼──────────────────────────┐
                │                           │                          │
     [ 1. PROCEDURAL ]             ( 2. FUNCTIONAL )            { 3. OBJECT-ORIENTED }
    Temporal Imperative Rolls      Axiomatic Invariant Truths   Triadic Boundary Envelopes
    ─────────────────────────      ──────────────────────────   ──────────────────────────
    • Sequential instruction rolls • Zero-sum balanced ternary  • `< Invariant >` (Private)
    • Cycle counter `TURN`         • Directional pipelines `-->` • `[ Denotation ]` (Public)
    • Stack frames on `SPOOL`      • Immutable axioms `< ... >` • `{ Connotation }` (Contract)
    • Origin pointer `HOME`        • Referential transparency  • Instance context `SELF`
    • Program counter `HEAD`       • Algebraic zero equilibrium • Invoking client `CALLER`
    • Natural sentence grammar     • Pure mathematical state   • Subtyping via `v--`
```

1. **The Procedural Core (Temporal Process Ribbon):**
   * Natural language sentences are procedural by design: *Subject* (`[Kernel]`) --> *Verb/Act* (`PROCEED`) to *Object* (`{RAM}`).
   * Deterministic temporal progression step-by-step: each roll advances `TURN += 1`, moves the tape head (`HEAD`), references the base frame (`HOME`), and pushes/pops stack contexts on `SPOOL`.
   * Explicit return values accumulate in `IT`, inputs enter through `FROM`, and results stream to `INTO`.

2. **The Functional Core (Axiomatic Invariant Equilibrium):**
   * Balanced ternary $\mathbb{T}_3 = \{-1, 0, +1\}$ is an algebra of pure equilibrium (zero-sum symmetry), eliminating dirty hidden states.
   * Directional vectors (`-->`) represent pure monadic pipeline composition: `source --> filter --> transform --> target`.
   * Immutable axioms `< Invariant >` are referentially transparent; Closing Block proofs (`verify: [ ... ]`) formally verify invariants before execution.

3. **The Object-Oriented Core (The Triadic Boundary):**
   * Encapsulation is enforced by physical grammar delimiters rather than compiler keywords:
     * `< Invariant >`: Private invariants, type constraints, and class invariants.
     * `[ Denotation ]`: Public instance variables, mutable storage fields, and concrete state.
     * `{ Connotation }`: Interfaces, external dependencies, and environmental contracts.
   * Identity: `SELF` denotes the active entity instance; `CALLER` denotes the message sender.
   * Specialization & Inheritance: `Parent v-- Child` partitions and derives subtypes.
   * Message Passing: `Receiver --> Method(Arguments)` communicates between objects.

---

8. The Dual-Syntax Engine & The Transpiling Bridge: `.omni` vs. `.tape`

OmniCode introduces an intentional architectural duality between its two primary file formats:
```

```
| Property | `.omni` (Spatial Architecture Reel) | `.tape` (Process Execution Ribbon) |
| :--- | :--- | :--- |
| **Execution Model** | **Compiled** (multi-pass verification & layout) | **Interpreted** (line-by-line streaming) |
| **Verbosity** | Verbose, rigorous, fully declarative | Lean, concise, natural-sentence syntax |
| **Primary Scope** | Spatial layout, types, 4-Block architecture | Temporal roll sequence, active execution head |
| **Verification** | Invariants proved in Closing Block | Pre-verified rolls executed immediately |
| **Silicon Role** | Memory map synthesis & Storehouse carving | Tape Head (`HEAD`) stepping roll by roll |

#### Why `.omni` Files Are Compiled and Verbose

A `.omni` file is an architectural blueprint. It defines the complete spatial structure:

1. **Metadata Block:** Identity, licensing, scheduling priority, and hardware topology.
2. **Opening Block:** Preconditions, imported modules, and memory partition allocations.
3. **Body Block:** Immutable axioms `< >`, entities `[ ]`, interfaces `{ }`, and state loops.
4. **Closing Block:** Formal verification proofs and the covenant commit seal `commit_status [ PROCEED ]`.

Because it establishes spatial topologies and proves theorems, the compiler must analyze the entire file, verify delimiter physics, resolve symbols, allocate silicon offsets (`@ 0x0000`), and compile the 4 blocks into physical machine words ([`Word64`]).

#### Why `.tape` Files Are Interpreted Line by Line

A `.tape` file is a process ribbon designed for a physical or virtual tape head (`HEAD`).
The CPU or interpreter scans one roll at a time, evaluates the sentence, updates registers (`TURN`, `IT`), and executes I/O. It does not need to re-verify global theorems at runtime because the structural invariants were established upstream.

#### The Transpilation Bridge and Road to Self-Hosting

The bidirectional lowering engine ([`OmniAssembler`]) provides the transpiling bridge:
* **Compilation (`.omni` $\longrightarrow$ `.tape`):** Lowers declarative 4-Block spatial reels into sequential instruction rolls executable on bare-metal ribbons.
* **Lifting / Decompilation (`.tape` $\longrightarrow$ `.omni`):** Reconstructs the 4-block architecture, opening preconditions, and closing verification proofs from procedural rolls.

#### Self-Hosting Strategy: Lowering the Rust Host Engine into OmniCode

Because Rust is a procedural systems language with functional idioms and OOP traits, the bridge between `.omni` and `.tape` directly maps to Rust's constructs:
* **Rust Structs + Traits** $\longrightarrow$ OmniCode Triadic Entities (`< Invariants > [ Fields ] { Traits }`).
* **Rust Functions** $\longrightarrow$ OmniCode Instruction Rolls on `SPOOL` using `CALLER`, `SELF`, `FROM`, `IT`, `INTO`.
* **Rust Matches & Loops** $\longrightarrow$ OmniCode `STATE` loops driving QuadState transitions.
* **Rust Borrow Checker** $\longrightarrow$ OmniCode Delimiter Physics (`< >` immutable, `[ ]` exclusive mutable, `{ }` ambient context).

This enables OmniCode to compile its own host engine and operating system micro-kernel entirely in native OmniCode, achieving true bare-metal self-hosting.
```

<TRACK 5> : {Infrastructure, Operations & Archives}/infra/systemd/omnicode-web.service

SERVICE | 22 LINES | 34 WORDS | 0.5 KB

```
[Unit]
Description=OmniCode Cognitive Studio Web & REST API Server (CreativeWorkzStudio LLC)
After=network.target

[Service]
Type=simple
User=ubuntu
WorkingDirectory=/home/ubuntu/OmniCode
ExecStart=/home/ubuntu/OmniCode/target/release/omnicode gui --port 8080
Restart=always
RestartSec=5s
Environment=RUST_LOG=info
Environment=OMNICODE_OFFLINE=1
Environment=OMNICODE_HOST=0.0.0.0

# Security and resource sandboxing
LimitNOFILE=65536
NoNewPrivileges=true

[Install]
WantedBy=multi-user.target
```

<TRACK 5> : {Infrastructure, Operations & Archives}/infra/docker/Dockerfile TEXT 178 LINES 947 WORDS 7.8 KB

```
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( OmniCode Bare-Metal OS & Multi-Architecture Toolchain Specification )
# ================================================================================
# Image:       omnicode-toolchain:latest
# Base OS:     Debian 12 (Bookworm) via official Rust 1.85 slim image
# Maintainer:  ProfessorSeanEX
# Architecture: Multi-target (x86_64, aarch64, riscv64gc)
#
# PURPOSE & COGNITIVE RATIONALE:
#   This container establishes a completely reproducible, hermetic compilation,
#   emulation, and cognitive execution environment for the OmniCode language.
#   It serves two distinct computational tiers:
#     1. Low-Level Bare-Metal Systems: no_std cross-compilation, bootloader ISO
#        packaging, NASM assembly, and multi-architecture QEMU hardware emulation.
#     2. High-Level Cognitive & Language Runtime: The Rust 2024 core engine,
#        interactive REPL, AI Cortex, Episodic Scroll logger, and self-healing Restorator.
#
# WHY EXTENSIVE COMMENTING MATTERS FOR AI & DEVELOPERS:
#   - For AI Agents (e.g., AICortex, Pair-Programming Assistants):
#     Code comments serve as semantic invariant anchors. When an AI parses this
#     Dockerfile, comments provide explicit causal rationales ("Why is xorriso here?
#     Because GRUB El Torito ISOs require it without loop mounts"). This prevents
#     the AI from hallucinating dependencies or accidentally stripping essential
#     cross-compilers during automated refactoring.
#   - For Human Engineers:
#     Systems programming toolchains conflate dozens of specialized CLI utilities.
#     Detailed comments eliminate guesswork, clarify port assignments (e.g., 1234
#     for QEMU GDB), and explain target triples for bare-metal silicon.
# ================================================================================

FROM rust:1.85-slim-bookworm AS toolchain-base

LABEL maintainer="ProfessorSeanEX"
LABEL description="OmniCode Bare-Metal Toolchain: Rust Core, LLVM/Clang, QEMU Emulation, and ISO Bootloaders"
LABEL version="0.1.0"

# Non-interactive frontend prevents apt from prompting for timezone/keyboard input during build
ENV DEBIAN_FRONTEND=noninteractive

# Standardize Cargo and Rustup directories into global system locations
ENV CARGO_HOME=/usr/local/cargo
ENV RUSTUP_HOME=/usr/local/rustup
ENV PATH="${CARGO_HOME}/bin:${PATH}"

# OmniCode runtime environment defaults
ENV RUST_BACKTRACE=1
ENV OMNICODE_SCROLL_DIR=/workspace/scrolls
ENV OMNICODE_LIB_DIR=/workspace/lib


# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( System Dependencies, Cross-Compilers, Assemblers & Emulation Prerequisites )
# ================================================================================
# RATIONALE FOR PACKAGE GROUPINGS:
#   1. build-essential, clang, lld, llvm:
#      - Clang/LLVM provides the primary C ABI transpilation and LLVM IR compilation backend.
#      - LLD is LLVM's ultra-fast linker, indispensable for bare-metal custom memory linker scripts.
#   2. nasm, yasm:
#      - Assemblers for 16-bit real mode, 32-bit protected mode bootloaders, and 64-bit entry stubs.
#   3. qemu-system-x86, qemu-system-arm, qemu-system-misc:
#      - Hardware emulators covering all three tier-1 OmniCode targets:
#        * qemu-system-x86: Intel/AMD x86_64 PC hardware (Q35/i440FX chipsets).
#        * qemu-system-arm: ARMv8-A Cortex bare-metal boards (virt, raspi).
#        * qemu-system-misc: RISC-V 64-bit hardware (virt board, RV64GC).
#   4. xorriso, grub-pc-bin, grub-common, mtools:
#      - Bootloader ISO image authoring. Allows generating bootable hybrid El Torito ISOs
#        and Multiboot2/UEFI media without needing root loop-device privileges.
#   5. gdb-multiarch:
#      - Cross-architecture debugger capable of stepping through x86_64, aarch64, and
#        riscv64 instructions when attached to QEMU's GDB stub on port 1234.
#   6. ripgrep, jq, file, tree, less:
#      - Diagnostic inspection tools. `file` inspects ELF kernel binaries; `jq` and `ripgrep`
#        parse JSON AST dumps and episodic trace telemetry.
#   7. nodejs, npm:
#      - Required for building, linting, and packaging the OmniCode VS Code extension
#        via `@vscode/vsce` in editors/vscode/.
# ================================================================================
```

```
80
81  RUN apt-get update && apt-get install -y --no-install-recommends \
82      build-essential \
83      clang \
84      lld \
85      llvm \
86      nasm \
87      yasm \
88      qemu-system-x86 \
89      qemu-system-arm \
90      qemu-system-misc \
91      xorriso \
92      grub-pc-bin \
93      grub-common \
94      mtools \
95      gdb-multiarch \
96      curl \
97      git \
98      pkg-config \
99      ca-certificates \
100     ripgrep \
101     jq \
102     file \
103     tree \
104     less \
105     nodejs \
106     npm \
107     && rm -rf /var/lib/apt/lists/*
108
109
110 # ================================================================================
111 # BLOCK 3: BODY BLOCK
112 # ( Bare-Metal Rust Targets, LLVM Tools, and Global Binary Compilation )
113 # ================================================================================
114 # RATIONALE FOR RUSTUP COMPONENTS & TARGETS:
115 #   1. rust-src:
116 #      - Contains the source code of the Rust standard library (core, alloc, compiler_builtins).
117 #      - Required by cargo `-Z build-std` when compiling custom bare-metal OS kernels.
118 #   2. llvm-tools-preview:
119 #      - Ships llvm-objdump, llvm-objcopy, llvm-nm, and llvm-size for binary introspection.
120 #   3. Bare-Metal Target Triples:
121 #      - `x86_64-unknown-none`: 64-bit x86 bare-metal kernel target (no OS, no libc).
122 #      - `aarch64-unknown-none`: 64-bit ARM bare-metal target (no OS, no libc).
123 #      - `riscv64gc-unknown-none-elf`: 64-bit RISC-V with General Purpose + Compressed instructions.
124 # ================================================================================
125
126 RUN rustup component add rust-src llvm-tools-preview rustfmt clippy && \
127     rustup target add x86_64-unknown-none && \
128     rustup target add aarch64-unknown-none && \
129     rustup target add riscv64gc-unknown-none-elf
130
131 # Establish standardized container workspace directory
132 WORKDIR /workspace
133
134 # Copy manifest, source tree, libraries, and tests to pre-compile the release binary
135 # into /usr/local/cargo/bin so `omnicode` is immediately available in the system PATH
136 COPY Cargo.toml Cargo.lock /workspace/
137 COPY src/ /workspace/src/
138 COPY lib/ /workspace/lib/
139 COPY examples/ /workspace/examples/
140 COPY tests/ /workspace/tests/
141
142 # Build and install the canonical OmniCode binary globally into the image
143 RUN cargo build --release && \
144     cargo test --release && \
145     cp /workspace/target/release/omnicode /usr/local/bin/omnicode && \
146     chmod +x /usr/local/bin/omnicode
147
148 # Comprehensive toolchain verification during build
149 RUN echo "=== Verifying OmniCode Multi-Target Toolchain ===" && \
150     omnicode --version && \
151     rustc --version && \
152     cargo --version && \
153     clang --version && \
154     lld --version && \
155     nasm -v && \
156     qemu-system-x86_64 --version && \
157     qemu-system-aarch64 --version && \
158     qemu-system-riscv64 --version && \
159     gdb-multiarch --version && \
160     node --version && \
161     npm --version
162
```

```
163
164 # ============================================================================
165 # BLOCK 4: CLOSING BLOCK
166 # ( Runtime Verification, Environment Seal & Default Entrypoint )
167 # ============================================================================
168 # ENTRYPOINT & INVARIANTS:
169 #   - Default command drops into an interactive bash shell where developers or
170 #     AI subagents can immediately invoke `omnicode repl`, `omnicode run`,
171 #     `omnicode ai`, `omnicode scrolls`, or run QEMU bare-metal kernel sessions.
172 #   - In docker-compose, this workspace is overlaid with the host volume mount
173 #     to provide live two-way code synchronization.
174 # ============================================================================
175
176 # Default command: interactive bash shell with full toolchain availability
177 CMD ["bash"]
```

<TRACK 5> : {Infrastructure, Operations & Archives}/infra/docker/docker-compose.yml YML 113 LINES 650 WORDS 5.7 KB

```yaml
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Container Orchestration Identity, Infrastructure Manifest & Cognitive Intent )
# ================================================================================
# Project:      OmniCode Language Engine & Bare-Metal OS
# Compose File: docker-compose.yml
# Service:      omnicode-toolchain
# Purpose:      Multi-tier development, bare-metal hardware emulation, and cognitive execution
#
# WHY EXTENSIVE COMMENTING MATTERS FOR AI & DEVELOPERS:
#   - For AI Autonomous Agents:
#     When an AI inspects orchestration files, bare configuration directives (e.g.
#     `1234:1234`) lack intent. Detailed comments explain the semantic contract:
#     Port 1234 connects to QEMU's GDB stub; modifying it breaks kernel debugging.
#     Named volume `target-cache` prevents cross-compilation thrashing between the
#     host and Linux container. These comments serve as immutable guardrails.
#   - For Human Collaborators:
#     Eliminates onboarding friction. Developers immediately know how to attach an
#     interactive REPL, connect a debugger to a bootloader, or run the AI cognitive loop.
# ================================================================================

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Service Topology, Container Preconditions & Interactive Shell Configuration )
# ================================================================================
services:
  omnicode-toolchain:
    build:
      context: .
      dockerfile: Dockerfile
    image: omnicode-toolchain:latest
    container_name: omnicode-toolchain

    # Interactive TTY configuration:
    # `stdin_open: true` (-i) and `tty: true` (-t) keep STDIN open and allocate
    # a pseudo-TTY, enabling interactive `omnicode repl` and terminal debugging sessions.
    stdin_open: true
    tty: true

    # Execution root directory inside the container
    working_dir: /workspace

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Volume Topology, Network Port Routing & Environment Invariant Configuration )
# ================================================================================
    # VOLUME MOUNTING STRATEGY & EXPLANATION:
    #   1. `.:/workspace`:
    #      Two-way live bind mount between host project root and container.
    #      Edits in host IDEs (VS Code, Cursor, Antigravity) appear immediately inside
    #      the container, and generated `.scroll` episodic memory logs are saved to host.
    #   2. `cargo-cache:/usr/local/cargo/registry`:
    #      Named persistent volume caching downloaded crates.io index and packages,
    #      preventing redundant downloads across container restarts.
    #   3. `cargo-git:/usr/local/cargo/git`:
    #      Named persistent volume caching git dependencies fetched by Cargo.
    #   4. `target-cache:/workspace/target`:
    #      Named persistent volume isolating Linux ELF build artifacts from the host OS.
    #      CRITICAL: Prevents target directory collisions if the host machine is macOS
    #      or Windows, and dramatically speeds up compilation by avoiding 9p/FUSE overhead.
    volumes:
      - .:/workspace
      - cargo-cache:/usr/local/cargo/registry
      - cargo-git:/usr/local/cargo/git
      - target-cache:/workspace/target

    # PORT MAPPING TOPOLOGY:
    #   - 1234: QEMU Remote GDB Debugging Stub.
    #           When launching a bare-metal kernel with `qemu-system-x86_64 -s -S`,
    #           QEMU halts execution at the first instruction and listens on TCP port 1234.
    #           Attach from host or container with `gdb-multiarch -ex "target remote localhost:1234"`.
    #   - 5900: QEMU VNC Graphical Framebuffer.
    #           Bare-metal graphical displays rendered via VESA/GOP or virtio-gpu are
    #           streamed over VNC. Connect any VNC viewer to `localhost:5900`.
    #   - 8080: OmniCode Cognitive Daemon & Language Server.
    #           Reserved for future HTTP/WebSocket language server or telemetry visualization.
    ports:
      - "1234:1234" # QEMU GDB remote debugging socket
      - "5900:5900" # QEMU VNC graphical framebuffer display
```

```
      - "8080:8080" # OmniCode Cognitive Daemon / Web Inspector

    # RUNTIME ENVIRONMENT INVARIANTS:
    #   - RUST_BACKTRACE=1: Produces full symbolic stack traces upon error or panic.
    #   - OMNICODE_SCROLL_DIR: Directs episodic cognitive logs to the shared workspace.
    #   - OMNICODE_LIB_DIR: Resolves built-in standard library modules (Core.Arithmetic, etc.).
    environment:
      - RUST_BACKTRACE=1
      - OMNICODE_SCROLL_DIR=/workspace/scrolls
      - OMNICODE_LIB_DIR=/workspace/lib

    # Default command drops into an interactive bash shell ready for commands:
    # e.g., `omnicode repl`, `omnicode run <file>`, `omnicode ai "<prompt>"`, or `./scripts/check_toolchain.sh`
    command: bash

# ==============================================================================
# BLOCK 4: CLOSING BLOCK
# ( Volume Persistence Declarations & Invariant Storage Lifecycle )
# ==============================================================================
# NAMED VOLUME DECLARATIONS:
#   These volumes persist independently of container destruction:
#   - Run `docker compose down` to stop the container without losing caches.
#   - Run `docker compose down -v` to explicitly purge build caches if clean builds are required.
volumes:
  cargo-cache:
    labels:
      description: "Persistent cache for Cargo crates.io package registry"
  cargo-git:
    labels:
      description: "Persistent cache for Cargo git repositories"
  target-cache:
    labels:
      description: "Isolated persistent build cache for target/ binary compilation"
```

<TRACK 5> : {Infrastructure, Operations & Archives}/infra/scripts/check_toolchain.sh SH 57 LINES 227 WORDS 2.5 KB

```
#!/usr/bin/env bash
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( Toolchain Diagnostics Identity & Environment Manifest )
# ================================================================================
set -e

echo -e "\x1b[1;36m=============================================================================================\x1b[0m"
echo -e "\x1b[1;36m  OmniCode Toolchain Diagnostics & Verification Harness\x1b[0m"
echo -e "\x1b[1;36m=============================================================================================\x1b[0m\n"

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Dependency Check Function & Invariant Preconditions )
# ================================================================================
check_tool() {
    local name="$1"
    local cmd="$2"
    if command -v "$cmd" >/dev/null 2>&1; then
        echo -e "  \x1b[1;32m✓\x1b[0m $name: \x1b[33m$($cmd --version 2>&1 | head -n 1)\x1b[0m"
    else
        echo -e "  \x1b[1;31m✗\x1b[0m $name is NOT installed ($cmd missing)"
        return 1
    fi
}

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Core Compilers, Assemblers, Emulators & Bare-Metal Verification )
# ================================================================================
echo -e "\x1b[1;34m[1/3] Core Compilers & Assemblers:\x1b[0m"
check_tool "Rust Compiler" rustc
check_tool "Cargo" cargo
check_tool "Clang" clang
check_tool "LLD Linker" lld
check_tool "NASM Assembler" nasm

echo -e "\n\x1b[1;34m[2/3] Hardware Emulation & Bootloaders:\x1b[0m"
check_tool "QEMU x86_64" qemu-system-x86_64
check_tool "Xorriso" xorriso

echo -e "\n\x1b[1;34m[3/3] Rust Bare-Metal Target Verification:\x1b[0m"
TARGETS=$(rustup target list --installed)
for target in "x86_64-unknown-none" "aarch64-unknown-none" "riscv64gc-unknown-none-elf"; do
    if echo "$TARGETS" | grep -q "$target"; then
        echo -e "  \x1b[1;32m✓\x1b[0m Installed target: \x1b[33m$target\x1b[0m"
    else
        echo -e "  \x1b[1;33m!\x1b[0m Missing bare-metal target: $target (Install with 'rustup target add $target')"
    fi
done

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Final Status Summary & Exit Verification )
# ================================================================================
echo -e "\n\x1b[1;32m✓ Toolchain verification complete.\x1b[0m"
```

<TRACK 5> : {Infrastructure, Operations & Archives}/infra/scripts/deploy_oracle_cloud.sh

SH | 160 LINES | 721 WORDS | 7.0 KB

```sh
#!/usr/bin/env bash
# ==============================================================================
# CreativeWorkzStudio LLC - OmniCode Platform
# Oracle Cloud Ubuntu VM Turnkey Provisioning & Deployment Script
# ==============================================================================
# Turnkey setup script for deploying OmniCode 24/7 on an Oracle Cloud Compute Instance:
# 1. Installs system build prerequisites, Rust/Cargo compiler, and git.
# 2. Configures OS firewall & iptables to allow Port 8080 (Web Studio & Cognitive API).
# 3. Builds the optimized OmniCode release binary (`cargo build --release`).
# 4. Installs and registers the systemd 24/7 service (`omnicode-web.service`).
# 5. Verifies service health and edge availability.
#
# Usage (run as root or with sudo on the Oracle Cloud VM):
#   sudo ./scripts/deploy_oracle_cloud.sh
# ==============================================================================

set -e

# Visual styling
BOLD="\033[1m"
GREEN="\033[0;32m"
BLUE="\033[0;34m"
CYAN="\033[0;36m"
YELLOW="\033[1;33m"
RED="\033[0;31m"
NC="\033[0m"

echo -e "${BOLD}${CYAN}================================================================================${NC}"
echo -e "${BOLD}${CYAN}  🌌 CreativeWorkzStudio LLC — OmniCode Platform                              ${NC}"
echo -e "${BOLD}${CYAN}  Oracle Cloud VM Turnkey Deployment & Systemd Provisioner                    ${NC}"
echo -e "${BOLD}${CYAN}================================================================================${NC}"

if [ "$EUID" -ne 0 ]; then
    echo -e "${RED}[!] Error: This script must be run as root or via sudo.${NC}"
    echo -e "    Please run: sudo $0"
    exit 1
fi

REAL_USER="${SUDO_USER:-$USER}"
REAL_HOME="$(eval echo "~$REAL_USER")"
SCRIPT_DIR="$(cd -P "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
BASE_DIR="$(cd "$SCRIPT_DIR/.." && pwd)"

echo -e "${BLUE}[*] Provisioning for host user: ${GREEN}$REAL_USER${NC}"
echo -e "${BLUE}[*] OmniCode base directory:    ${GREEN}$BASE_DIR${NC}"

# Detect Architecture
ARCH="$(uname -m)"
echo -e "${BLUE}[*] Target CPU architecture:    ${GREEN}$ARCH${NC}"

# ------------------------------------------------------------------------------
# STEP 1: System Packages and Build Essentials
# ------------------------------------------------------------------------------
echo ""
echo -e "${BOLD}${BLUE}[1/5] Updating packages and installing build prerequisites...${NC}"
export DEBIAN_FRONTEND=noninteractive
apt-get update -y
apt-get install -y \
    build-essential \
    curl \
    git \
    pkg-config \
    libssl-dev \
    iptables \
    iptables-persistent \
    netfilter-persistent \
    ca-certificates

# Ensure Rust & Cargo are installed for the target user
if ! sudo -u "$REAL_USER" command -v cargo >/dev/null 2>&1; then
    echo -e "${BLUE}[*] Rust compiler not found. Installing Rust toolchain via rustup...${NC}"
    sudo -u "$REAL_USER" curl --proto '=https' --tlsv1.2 -sSf https://sh.rustup.rs | sudo -u "$REAL_USER" sh -s -- -y
    echo -e "${GREEN}[+] Rust toolchain installed.${NC}"
else
    echo -e "${GREEN}[+] Rust toolchain already available: $(sudo -u "$REAL_USER" cargo --version)${NC}"
fi

```

```
# ------------------------------------------------------------------------------
# STEP 2: Configure Oracle Cloud Firewall & iptables
# ------------------------------------------------------------------------------
echo ""
echo -e "${BOLD}${BLUE}[2/5] Configuring OS Firewall & iptables for Port 8080...${NC}"
PORTS=(22 8080)

for PORT in "${PORTS[@]}"; do
    if ! iptables -C INPUT -p tcp --dport "$PORT" -j ACCEPT 2>/dev/null; then
        echo -e "${BLUE}[*] Opening TCP Port $PORT in iptables...${NC}"
        iptables -I INPUT 1 -p tcp --dport "$PORT" -j ACCEPT
    else
        echo -e "${GREEN}[+] TCP Port $PORT already allowed in iptables.${NC}"
    fi
done

# Persist firewall rules
netfilter-persistent save || true

# Check UFW if active
if command -v ufw >/dev/null 2>&1 && ufw status 2>/dev/null | grep -q "Status: active"; then
    echo -e "${BLUE}[*] UFW firewall active. Permitting port 8080...${NC}"
    ufw allow 22/tcp
    ufw allow 8080/tcp
    ufw reload
fi
echo -e "${GREEN}[+] OS firewall configured for OmniCode Web & Cognitive Studio (Port 8080).${NC}"

# ------------------------------------------------------------------------------
# STEP 3: Compile OmniCode Release Binary
# ------------------------------------------------------------------------------
echo ""
echo -e "${BOLD}${BLUE}[3/5] Compiling OmniCode release binary with Cargo...${NC}"
export PATH="$REAL_HOME/.cargo/bin:$PATH"
sudo -u "$REAL_USER" env PATH="$REAL_HOME/.cargo/bin:$PATH" cargo build --release --manifest-path "$BASE_DIR/Cargo.toml"
echo -e "${GREEN}[+] OmniCode release binary built at: $BASE_DIR/target/release/omnicode${NC}"

# ------------------------------------------------------------------------------
# STEP 4: Install and Enable Systemd Service
# ------------------------------------------------------------------------------
echo ""
echo -e "${BOLD}${BLUE}[4/5] Registering and enabling systemd 24/7 service...${NC}"
SERVICE_SRC="$BASE_DIR/systemd/omnicode-web.service"
SERVICE_DEST="/etc/systemd/system/omnicode-web.service"

sed -e "s|/home/ubuntu/OmniCode|$BASE_DIR|g" \
    -e "s|User=ubuntu|User=$REAL_USER|g" \
    "$SERVICE_SRC" > "$SERVICE_DEST"

systemctl daemon-reload
systemctl enable omnicode-web.service
systemctl restart omnicode-web.service
echo -e "${GREEN}[+] omnicode-web.service installed and restarted.${NC}"

# ------------------------------------------------------------------------------
# STEP 5: Verification and Endpoint Summary
# ------------------------------------------------------------------------------
echo ""
echo -e "${BOLD}${BLUE}[5/5] Verifying service health and endpoints...${NC}"
sleep 2

STATUS=$(systemctl is-active omnicode-web.service || echo "failed")
PUBLIC_IP="$(curl -s -4 https://ifconfig.me || curl -s -4 https://api.ipify.org || echo "ORACLE_VM_PUBLIC_IP")"

echo ""
echo -e "${BOLD}${GREEN}================================================================================${NC}"
echo -e "${BOLD}${GREEN}  🎉 OMNICODE ORACLE CLOUD 24/7 DEPLOYMENT COMPLETE!                ${NC}"
echo -e "${BOLD}${GREEN}  CreativeWorkzStudio LLC                                           ${NC}"
echo -e "${BOLD}${GREEN}================================================================================${NC}"
echo -e "Service Status:         ${BOLD}${GREEN}$STATUS${NC}"
echo -e "Public Server IP:       ${BOLD}${YELLOW}$PUBLIC_IP${NC}"
echo -e "Web Studio & API:       ${BOLD}${CYAN}http://$PUBLIC_IP:8080${NC}"
echo ""
echo -e "${BOLD}Management Commands:${NC}"
echo -e "  Check service status:  ${BLUE}sudo systemctl status omnicode-web${NC}"
echo -e "  Restart service:       ${BLUE}sudo systemctl restart omnicode-web${NC}"
echo -e "  View live logs:        ${BLUE}sudo journalctl -u omnicode-web -f${NC}"
echo ""
echo -e "${BOLD}Cloudflare Integration:${NC}"
echo -e "  To route edge traffic through Cloudflare, launch the tunnel connector:"
echo -e "  ${BLUE}$BASE_DIR/scripts/setup_cloudflare_tunnel.sh --quick${NC}"
echo -e "${BOLD}${GREEN}================================================================================${NC}"
```

<TRACK 5> : {Infrastructure, Operations & Archives}/infra/scripts/oci_security_list_helper.sh

SH | 87 LINES | 474 WORDS | 4.1 KB

```
#!/usr/bin/env bash
# ============================================================================
# CreativeWorkzStudio LLC - OmniCode Platform
# Oracle Cloud VCN Ingress/Egress & Firewall Configuration Helper
# ============================================================================
# Helper script to manage VM OS firewall (iptables) and OCI VCN Security List
# for OmniCode Studio (port 8080).
#
# Requirements:
#   1. VM OS Firewall: iptables + netfilter-persistent (Already configured)
#   2. OCI Cloud Firewall: OCI CLI (installed at /usr/local/bin/oci) or OCI Console
# ============================================================================

set -e

BOLD="\033[1m"
GREEN="\033[0;32m"
BLUE="\033[0;34m"
CYAN="\033[0;36m"
YELLOW="\033[1;33m"
NC="\033[0m"

echo -e "${BOLD}${CYAN}============================================================================${NC}"
echo -e "${BOLD}${CYAN}  🛡️  Oracle Cloud VM Firewall & Ingress/Egress Helper                ${NC}"
echo -e "${BOLD}${CYAN}  CreativeWorkzStudio LLC — OmniCode Platform (Port 8080)             ${NC}"
echo -e "${BOLD}${CYAN}============================================================================${NC}"

# 1. Verify OS-level iptables rules
echo -e "\n${BLUE}[1/3] Checking OS-level iptables firewall rules for Port 8080...${NC}"
if sudo iptables -L INPUT -n | grep -q "dpt:8080"; then
    echo -e "${GREEN}[✓] Port 8080 is ACCEPT in iptables INPUT chain.${NC}"
else
    echo -e "${YELLOW}[*] Adding Port 8080 to iptables INPUT chain...${NC}"
    sudo iptables -I INPUT 6 -p tcp --dport 8080 -j ACCEPT
fi

# Ensure rules are saved persistently
if command -v netfilter-persistent >/dev/null 2>&1; then
    sudo netfilter-persistent save >/dev/null 2>&1
    echo -e "${GREEN}[✓] iptables rules saved persistently via netfilter-persistent.${NC}"
fi

# 2. Check OCI CLI installation
echo -e "\n${BLUE}[2/3] Checking Oracle Cloud Infrastructure CLI (oci-cli)...${NC}"
if command -v oci >/dev/null 2>&1; then
    OCI_VERSION=$(oci --version)
    echo -e "${GREEN}[✓] OCI CLI is installed at: $(which oci) (version: $OCI_VERSION)${NC}"
else
    echo -e "${YELLOW}[!] OCI CLI not found. Run setup on VM: sudo pip3 install oci-cli${NC}"
fi

# 3. Guidance for OCI VCN Security List (Cloud Layer)
echo -e "\n${BLUE}[3/3] Oracle Cloud VCN Ingress Rule Instructions (Cloud Hypervisor Layer):${NC}"
cat << 'EOF'

In Oracle Cloud Infrastructure (OCI), incoming traffic must pass through TWO layers:
  Layer 1: Linux OS Firewall (iptables) -> ALREADY CONFIGURED & PERSISTED (Port 8080 OPEN)
  Layer 2: OCI VCN Security List        -> Requires Cloud Ingress Rule

Option A: Via OCI Web Console (1-Minute Setup)
  1. Open Oracle Cloud Console (https://cloud.oracle.com)
  2. Navigate to: Networking > Virtual Cloud Networks > Select your VCN
  3. Under Resources, click "Security Lists" > Click "Default Security List for [VCN]"
  4. Click "Add Ingress Rules":
     - Source CIDR:            0.0.0.0/0
     - IP Protocol:            TCP
     - Destination Port Range: 8080
     - Description:           OmniCode Studio & Interactive Terminal GUI
  5. Click "Add Ingress Rules" to save.

Option B: Via OCI CLI (Command Line on VM)
  If you have configured OCI API credentials (`oci setup config`):
  Run:
    oci network security-list update \
      --security-list-id <YOUR_SECURITY_LIST_OCID> \
      --ingress-security-rules file://<(echo '[{"source":"0.0.0.0/0","protocol":"6","tcpOptions":{"destinationPortRange":
{"max":8080,"min":8080}},"description":"OmniCode Studio"}]')
```

```
77
78  Option C: Via Cloudflare Zero Trust Tunnel (Zero Open Ports Required)
79    Because cloudflared is already running on the VM, you can route:
80    - Hostname: studio.omnicodestudio.com -> HTTP://localhost:8080
81    This routes traffic securely via Cloudflare edge without needing any open ports in OCI VCN!
82  EOF
83
84  echo -e "\n${BOLD}${GREEN}================================================================================${NC}"
85  echo -e "${BOLD}${GREEN}  ✓ Firewall verification & guidance completed.                        ${NC}"
86  echo -e "${BOLD}${GREEN}================================================================================${NC}"
```

<TRACK 5> : {Infrastructure, Operations & Archives}/infra/scripts/omnicode_gui.sh SH 16 LINES 53 WORDS 0.5 KB

```
#!/usr/bin/env bash
# ============================================================================
# CreativeWorkzStudio LLC — OmniCode Desktop GUI Studio Launcher
# ============================================================================
set -e

SCRIPT_DIR="$(cd -P "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
BASE_DIR="$(cd "$SCRIPT_DIR/.." && pwd)"

if command -v python3 >/dev/null 2>&1; then
    exec python3 "$BASE_DIR/gui/desktop_app.py" "$@"
else
    echo "Python 3 is required to launch the OmniCode Desktop GUI."
    exit 1
fi
```

<TRACK 5> : {Infrastructure, Operations & Archives}/infra/scripts/package_native.sh SH 125 LINES 395 WORDS 4.2 KB

```sh
#!/usr/bin/env bash
# ================================================================================
# CreativeWorkzStudio LLC - OmniCode Platform
# Automated Native Terminal & Language OS Distribution Packager
# ================================================================================
# Compiles the optimized release binary and bundles a standalone native
# distribution archive with zero runtime dependencies.
#
# Output:
#   dist/omnicode-terminal-linux-x86_64.tar.gz
#   dist/omnicode-terminal-latest.tar.gz
# ================================================================================

set -e

SCRIPT_DIR="$(cd -P "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
if [ -f "$SCRIPT_DIR/../../Cargo.toml" ]; then
    BASE_DIR="$(cd "$SCRIPT_DIR/../.." && pwd)"
else
    BASE_DIR="$(cd "$SCRIPT_DIR/.." && pwd)"
fi
DIST_DIR="$BASE_DIR/infra/dist"
STAGING_DIR="/tmp/omnicode_dist_staging"

# ANSI styling
BOLD="\033[1m"
GREEN="\033[0;32m"
BLUE="\033[0;34m"
CYAN="\033[0;36m"
NC="\033[0m"

echo -e "${BOLD}${CYAN}================================================================================${NC}"
echo -e "${BOLD}${CYAN}  📦 OmniCode Native Distribution Packager                                    ${NC}"
echo -e "${BOLD}${CYAN}  CreativeWorkzStudio LLC — Standalone Native OS Shell                        ${NC}"
echo -e "${BOLD}${CYAN}================================================================================${NC}"

# 1. Compile release binary locally
echo -e "\n${BLUE}[1/4] Compiling optimized release binary with cargo...${NC}"
(cd "$BASE_DIR" && cargo build --release)

# 2. Prepare staging directory
echo -e "\n${BLUE}[2/4] Assembling standalone distribution files...${NC}"
rm -rf "$STAGING_DIR"
mkdir -p "$STAGING_DIR/bin"
mkdir -p "$STAGING_DIR/lib/core"
mkdir -p "$STAGING_DIR/examples"
mkdir -p "$STAGING_DIR/editors"
mkdir -p "$DIST_DIR"

# Copy binary
cp "$BASE_DIR/target/release/omnicode" "$STAGING_DIR/bin/omnicode"
chmod +x "$STAGING_DIR/bin/omnicode"

# Copy standard libraries and manifest
cp -r "$BASE_DIR/lib/core/"*.omni "$STAGING_DIR/lib/core/"
cp "$BASE_DIR/manifest.omni" "$STAGING_DIR/"
cp -r "$BASE_DIR/examples/"*.omni "$STAGING_DIR/examples/"

# Copy VS Code extension if available
if [ -d "$BASE_DIR/apps/editors/vscode" ]; then
    cp "$BASE_DIR/apps/editors/vscode/"*.vsix "$STAGING_DIR/editors/" 2>/dev/null || true
fi

# Create turnkey install script
cat << 'EOF' > "$STAGING_DIR/install.sh"
#!/usr/bin/env bash
# CreativeWorkzStudio LLC - OmniCode Standalone Installer
set -e

DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"

echo "Installing OmniCode Native Terminal..."

# Target install directory
if [ "$EUID" -eq 0 ]; then
    INSTALL_DIR="/usr/local/bin"
else
    INSTALL_DIR="$HOME/.local/bin"
    mkdir -p "$INSTALL_DIR"
```

```
fi

cp "$DIR/bin/omnicode" "$INSTALL_DIR/omnicode"
chmod +x "$INSTALL_DIR/omnicode"

echo "✓ OmniCode installed successfully to $INSTALL_DIR/omnicode"
echo "Testing installation:"
"$INSTALL_DIR/omnicode" demo

echo ""
echo "🎉 OmniCode Native Shell is ready! Type 'omnicode' to enter interactive terminal."
EOF
chmod +x "$STAGING_DIR/install.sh"

# Create Distribution README
cat << 'EOF' > "$STAGING_DIR/README.md"
# OmniCode Native Terminal & Language Core
CreativeWorkzStudio LLC — Autonomous Neural-Symbolic Intelligence

## Quick Start
Run turnkey installer:
  ./install.sh

Or run binary directly:
  ./bin/omnicode

Launch interactive userspace shell:
  ./bin/omnicode terminal
EOF

# 3. Create compressed archives
echo -e "\n${BLUE}[3/4] Creating standalone distribution archives in dist/...${NC}"
ARCHIVE_NAME="omnicode-terminal-linux-x86_64.tar.gz"
(cd "/tmp" && tar -czf "$DIST_DIR/$ARCHIVE_NAME" -C "$STAGING_DIR" .)
cp "$DIST_DIR/$ARCHIVE_NAME" "$DIST_DIR/omnicode-terminal-latest.tar.gz"

# 4. Report
echo -e "\n${BLUE}[4/4] Package Verification:${NC}"
ls -lh "$DIST_DIR/$ARCHIVE_NAME"
sha256sum "$DIST_DIR/$ARCHIVE_NAME"

echo -e "\n${BOLD}${GREEN}================================================================================${NC}"
echo -e "${BOLD}${GREEN}  ✅ Standalone Native Distribution Package Created Successfully!     ${NC}"
echo -e "${BOLD}${GREEN}  Output: $DIST_DIR/$ARCHIVE_NAME                                     ${NC}"
echo -e "${BOLD}${GREEN}================================================================================${NC}"
```

<TRACK 5> : {Infrastructure, Operations & Archives}/infra/scripts/setup_cloudflare_tunnel.sh

SH | 194 LINES | 713 WORDS | 6.8 KB

```sh
#!/usr/bin/env bash
# ================================================================================
# CreativeWorkzStudio LLC - OmniCode Platform
# Cloudflare Zero Trust Secure HTTPS Tunnel Connector
# ================================================================================
# Provides secure edge HTTPS routing to the local OmniCode Studio:
# 1. Quick Tunnel (Free, zero-config ephemeral HTTPS endpoint via trycloudflare.com):
#    Useful for local staging, development, and remote access.
# 2. Named Tunnel (Custom domain via Cloudflare Zero Trust Tunnel Token):
#    Production 24/7 tunnel mapped to your custom domain.
#
# Usage:
#   ./scripts/setup_cloudflare_tunnel.sh            # Auto-detects token from .env or starts quick
#   ./scripts/setup_cloudflare_tunnel.sh --quick    # Starts instant ephemeral quick tunnel
#   ./scripts/setup_cloudflare_tunnel.sh --token <TOKEN> # Starts named tunnel with specified token
#   ./scripts/setup_cloudflare_tunnel.sh --port <PORT>   # Specify local port (default: 8080)
# ================================================================================

set -e

# Visual formatting constants
BOLD="\033[1m"
GREEN="\033[0;32m"
BLUE="\033[0;34m"
CYAN="\033[0;36m"
YELLOW="\033[1;33m"
RED="\033[0;31m"
NC="\033[0m"

# Canonical directory resolution
SCRIPT_DIR="$(cd -P "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
if [ -f "$SCRIPT_DIR/../../Cargo.toml" ]; then
    BASE_DIR="$(cd "$SCRIPT_DIR/../.." && pwd)"
else
    BASE_DIR="$(cd "$SCRIPT_DIR/.." && pwd)"
fi
ENV_FILE="$BASE_DIR/.env"

PORT="8080"
MODE="auto"
CLI_TOKEN=""

echo -e "${BOLD}${CYAN}================================================================================${NC}"
echo -e "${BOLD}${CYAN}  🌐 OmniCode Cloudflare Tunnel Connector                                      ${NC}"
echo -e "${BOLD}${CYAN}  CreativeWorkzStudio LLC — Edge Security & Gateway                           ${NC}"
echo -e "${BOLD}${CYAN}================================================================================${NC}"

# Ensure cloudflared is installed
ensure_cloudflared() {
    if command -v cloudflared >/dev/null 2>&1; then
        echo -e "${GREEN}[+] cloudflared binary verified: $(cloudflared --version | head -n 1)${NC}"
        return 0
    fi

    echo -e "${BLUE}[*] cloudflared not found in PATH. Checking system architecture...${NC}"
    ARCH="$(uname -m)"
    case "$ARCH" in
        x86_64)
            CLOUDFLARED_URL="https://github.com/cloudflare/cloudflared/releases/latest/download/cloudflared-linux-amd64"
            ;;
        aarch64|arm64)
            CLOUDFLARED_URL="https://github.com/cloudflare/cloudflared/releases/latest/download/cloudflared-linux-arm64"
            ;;
        armv7l)
            CLOUDFLARED_URL="https://github.com/cloudflare/cloudflared/releases/latest/download/cloudflared-linux-arm"
            ;;
        *)
            echo -e "${RED}[-] Unsupported architecture: $ARCH. Please install cloudflared manually.${NC}"
            exit 1
            ;;
    esac

    echo -e "${BLUE}[*] Downloading cloudflared binary for $ARCH...${NC}"
    TMP_BIN="/tmp/cloudflared"
    curl -fsSL "$CLOUDFLARED_URL" -o "$TMP_BIN"
    chmod +x "$TMP_BIN"

```

```
    if [ "$EUID" -eq 0 ]; then
        mv "$TMP_BIN" /usr/local/bin/cloudflared
    elif sudo -n true 2>/dev/null; then
        sudo mv "$TMP_BIN" /usr/local/bin/cloudflared
    else
        mkdir -p "$BASE_DIR/bin"
        mv "$TMP_BIN" "$BASE_DIR/bin/cloudflared"
        export PATH="$BASE_DIR/bin:$PATH"
    fi

    echo -e "${GREEN}[+] cloudflared successfully installed.${NC}"
}

# Parse CLI arguments
while [ $# -gt 0 ]; do
    case "$1" in
        --quick)
            MODE="quick"
            shift
            ;;
        --token)
            MODE="token"
            CLI_TOKEN="$2"
            shift 2
            ;;
        --port)
            PORT="$2"
            shift 2
            ;;
        *)
            shift
            ;;
    esac
done

ensure_cloudflared

# Resolve Token from .env if auto
ENV_TOKEN=""
if [ -f "$ENV_FILE" ]; then
    ENV_TOKEN=$(grep -E '^CLOUDFLARE_TUNNEL_TOKEN=' "$ENV_FILE" 2>/dev/null | cut -d '=' -f 2- | tr -d '"' | tr -d "'" || true)
fi

# Fallback: check yugioh-server .env if available
if [ -z "$ENV_TOKEN" ] && [ -f "/home/professorseanex/yugioh-server/.env" ]; then
    ENV_TOKEN=$(grep -E '^CLOUDFLARE_TUNNEL_TOKEN=' "/home/professorseanex/yugioh-server/.env" 2>/dev/null | cut -d '=' -f 2- | tr -d '"' | tr -d "'" || true)
fi

if [ "$MODE" = "token" ] && [ -n "$CLI_TOKEN" ]; then
    ACTIVE_TOKEN="$CLI_TOKEN"
elif [ "$MODE" = "auto" ] && [ -n "$ENV_TOKEN" ] && [ "$ENV_TOKEN" != "your_cloudflare_tunnel_token_here" ]; then
    ACTIVE_TOKEN="$ENV_TOKEN"
    MODE="token"
else
    MODE="quick"
fi

# Execution
if [ "$MODE" = "token" ]; then
    echo -e "${BLUE}[*] Starting Cloudflare Named Tunnel using configured token...${NC}"
    echo -e "    Local Target  : http://localhost:$PORT (OmniCode Studio & API)"
    echo -e "    Token         : ${ACTIVE_TOKEN:0:15}... (Truncated for security)"
    echo ""
    echo -e "${YELLOW}[!] Tunnel running in foreground. Press Ctrl+C to terminate.${NC}"
    echo ""
    exec cloudflared tunnel --no-autoupdate run --token "$ACTIVE_TOKEN"
else
    echo -e "${BLUE}[*] Starting Cloudflare Quick Tunnel (Free, zero-config HTTPS edge)...${NC}"
    echo -e "    Local Target : http://localhost:$PORT"
    echo ""

    LOG_FILE="/tmp/omnicode_cloudflared_quick.log"
    rm -f "$LOG_FILE"

    cloudflared tunnel --url "http://localhost:$PORT" > "$LOG_FILE" 2>&1 &
    CF_PID=$!

    cleanup() {
        echo ""
        echo -e "${YELLOW}[*] Shutting down Cloudflare tunnel (PID: $CF_PID)...${NC}"
        kill "$CF_PID" 2>/dev/null || true
        exit 0
```

```
    }
    trap cleanup SIGINT SIGTERM EXIT

    echo -e "${BLUE}[*] Provisioning edge tunnel and acquiring public HTTPS URL...${NC}"
    URL=""
    for i in {1..30}; do
        if [ -f "$LOG_FILE" ]; then
            URL=$(grep -o 'https://[-a-zA-Z0-9\.]*\.trycloudflare\.com' "$LOG_FILE" | head -n 1 || true)
            if [ -n "$URL" ]; then
                break
            fi
        fi
        sleep 1
    done

    if [ -z "$URL" ]; then
        echo -e "${RED}[-] Timeout: Failed to obtain public tunnel URL within 30 seconds.${NC}"
        echo -e "    Log output:"
        cat "$LOG_FILE"
        exit 1
    fi

    echo ""
    echo -e "${BOLD}${GREEN}================================================================================${NC}"
    echo -e "${BOLD}${GREEN}  🎉 OMNICODE CLOUDFLARE HTTPS TUNNEL IS LIVE!                                  ${NC}"
    echo -e "${BOLD}${GREEN}================================================================================${NC}"
    echo -e "  Public HTTPS URL:  ${BOLD}${CYAN}${URL}${NC}"
    echo -e "  Local Destination: http://localhost:$PORT"
    echo -e "  Organization:      CreativeWorkzStudio LLC"
    echo ""
    echo -e "${YELLOW}[!] Keep this terminal open. Tunnel will close when stopped.${NC}"
    echo -e "    Press Ctrl+C to terminate."
    wait "$CF_PID"
fi
```

<TRACK 5> : {Infrastructure, Operations & Archives}/infra/scripts/sync_oracle_vm.sh SH 133 LINES 577 WORDS 5.6 KB

```
#!/usr/bin/env bash
# ================================================================================
# CreativeWorkzStudio LLC - OmniCode Platform
# Oracle Cloud VM Automated Synchronization Script
# ================================================================================
# Synchronizes the local OmniCode repository to the Oracle Cloud VM:
# 1. Connects to Oracle Cloud VM (147.224.147.30 / Host 'oracle') via SSH.
# 2. Synchronizes repository source files to /home/ubuntu/OmniCode using rsync.
# 3. Compiles the optimized release binary with cargo on the remote host.
# 4. Restarts systemd service: omnicode-web.service.
# 5. Queries and reports remote service health.
#
# Usage:
#   ./scripts/sync_oracle_vm.sh [optional commit or sync note]
# ================================================================================

set -e

# ANSI Styling
GREEN="\033[0;32m"
BLUE="\033[0;34m"
CYAN="\033[0;36m"
YELLOW="\033[1;33m"
RED="\033[0;31m"
BOLD="\033[1m"
NC="\033[0m"

SCRIPT_DIR="$(cd -P "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
if [ -f "$SCRIPT_DIR/../../Cargo.toml" ]; then
    BASE_DIR="$(cd "$SCRIPT_DIR/../.." && pwd)"
else
    BASE_DIR="$(cd "$SCRIPT_DIR/.." && pwd)"
fi

# Target Configuration
ORACLE_HOST="${ORACLE_VM_HOST:-147.224.147.30}"
ORACLE_USER="${ORACLE_VM_USER:-ubuntu}"
SSH_KEY="${ORACLE_SSH_KEY:-$HOME/.ssh/oracle_key.pem}"
REMOTE_DIR="/home/ubuntu/OmniCode"

echo -e "${BOLD}${CYAN}================================================================================${NC}"
echo -e "${BOLD}${CYAN}  🌌 CreativeWorkzStudio LLC — OmniCode Platform                              ${NC}"
echo -e "${BOLD}${CYAN}  Oracle Cloud VM Automated Synchronization Gateway                           ${NC}"
echo -e "${BOLD}${CYAN}  Target: ${ORACLE_USER}@${ORACLE_HOST} (${REMOTE_DIR})                       ${NC}"
echo -e "${BOLD}${CYAN}================================================================================${NC}"

# Check SSH Key
if [ ! -f "$SSH_KEY" ]; then
    echo -e "${RED}[!] SSH Private Key not found at: ${SSH_KEY}${NC}"
    echo -e "    Please specify valid key path via ORACLE_SSH_KEY env var."
    exit 1
fi
chmod 600 "$SSH_KEY" 2>/dev/null || true

# Test SSH Connection
echo -e "\n${BLUE}[1/4] Verifying SSH connectivity to Oracle VM...${NC}"
if ! ssh -i "$SSH_KEY" -o ConnectTimeout=8 -o StrictHostKeyChecking=accept-new "${ORACLE_USER}@${ORACLE_HOST}" "echo 'Connected successfully'" >/dev/null 2>&1; then
    echo -e "${RED}[!] Failed to establish SSH connection to ${ORACLE_USER}@${ORACLE_HOST}.${NC}"
    exit 1
fi
echo -e "${GREEN}[+] Remote Oracle VM host reachable.${NC}"

# Ensure Remote Directory Exists
echo -e "\n${BLUE}[2/4] Ensuring remote workspace directory exists...${NC}"
ssh -i "$SSH_KEY" "${ORACLE_USER}@${ORACLE_HOST}" "mkdir -p $REMOTE_DIR"

# Rsync Files to Oracle VM (excluding target/ and .git/ large artifacts for speed)
echo -e "\n${BLUE}[3/4] Synchronizing repository files via rsync...${NC}"
rsync -avz --delete \
    -e "ssh -i $SSH_KEY -o StrictHostKeyChecking=accept-new" \
    --exclude "target/" \
    --exclude ".git/" \
    --exclude "node_modules/" \
    --exclude "*.log" \
    "$BASE_DIR/" "${ORACLE_USER}@${ORACLE_HOST}:${REMOTE_DIR}/"
echo -e "${GREEN}[+] Repository source synchronization complete.${NC}"

# Ensure release binary exists locally and transfer it
```

```
if [ ! -f "$BASE_DIR/target/release/omnicode" ]; then
    echo -e "${BLUE}[*] Compiling local release binary with cargo...${NC}"
    (cd "$BASE_DIR" && cargo build --release)
fi

echo -e "\n${BLUE}[*] Deploying optimized release binary to Oracle VM...${NC}"
ssh -i "$SSH_KEY" "${ORACLE_USER}@${ORACLE_HOST}" "mkdir -p ${REMOTE_DIR}/target/release"
scp -i "$SSH_KEY" "$BASE_DIR/target/release/omnicode" "${ORACLE_USER}@${ORACLE_HOST}:/tmp/omnicode.new"
ssh -i "$SSH_KEY" "${ORACLE_USER}@${ORACLE_HOST}" "mv -f /tmp/omnicode.new ${REMOTE_DIR}/target/release/omnicode && chmod +x
${REMOTE_DIR}/target/release/omnicode"
echo -e "${GREEN}[+] Binary deployment complete.${NC}"

# Remote Service Configuration & Restart
echo -e "\n${BLUE}[4/4] Configuring firewall and restarting omnicode-web.service on Oracle VM...${NC}"
SSH_CMD="ssh -i \"$SSH_KEY\" \"${ORACLE_USER}@${ORACLE_HOST}\""

eval $SSH_CMD << 'EOF'
set -e
GREEN="\033[0;32m"
BLUE="\033[0;34m"
NC="\033[0m"

cd /home/ubuntu/OmniCode

# Install / update systemd service
SERVICE_FILE="infra/systemd/omnicode-web.service"
if [ ! -f "$SERVICE_FILE" ]; then
    SERVICE_FILE="systemd/omnicode-web.service"
fi
if [ -f "$SERVICE_FILE" ]; then
    echo -e "${BLUE}[*] Installing/updating omnicode-web.service from $SERVICE_FILE...${NC}"
    sudo cp "$SERVICE_FILE" /etc/systemd/system/omnicode-web.service
    sudo systemctl daemon-reload
    sudo systemctl enable omnicode-web.service
    sudo systemctl restart omnicode-web.service
fi

# Ensure TCP port 8080 is permitted in iptables
if ! sudo iptables -L INPUT -n | grep -q "dpt:8080"; then
    echo -e "${BLUE}[*] Opening port 8080 in iptables...${NC}"
    sudo iptables -I INPUT 6 -p tcp --dport 8080 -j ACCEPT
    if command -v netfilter-persistent >/dev/null 2>&1; then
        sudo netfilter-persistent save >/dev/null 2>&1 || true
    fi
fi

sleep 2
STATUS=$(sudo systemctl is-active omnicode-web.service || echo "inactive")
echo -e " • omnicode-web.service status: [${STATUS}]"
EOF

echo -e "\n${BOLD}${GREEN}================================================================================${NC}"
echo -e "${BOLD}${GREEN}  ✅ OmniCode Oracle Cloud VM Synchronization Complete!              ${NC}"
echo -e "${BOLD}${GREEN}  CreativeWorkzStudio LLC                                           ${NC}"
echo -e "${BOLD}${GREEN}================================================================================${NC}"
```

<TRACK 5> : {Infrastructure, Operations & Archives}/infra/dns/README.md MD 71 LINES 380 WORDS 2.9 KB

```
# 🌐 OmniCode DNS Zone Infrastructure

Authoritative BIND RFC 1035 DNS zone configuration files for **OmniCode Studio & CreativeWorkzStudio LLC**, designed for 1-click import into Cloudflare DNS.

---

## 📁 File Manifest

| File | Standard | Description |
| :--- | :--- | :--- |
| [`omnicodestudio.com.zone`](file:///home/professorseanex/OmniCode/dns/omnicodestudio.com.zone) | RFC 1035 / BIND 9 | Master DNS zone file compatible with Cloudflare DNS Import |
| [`zone_manager.py`](file:///home/professorseanex/OmniCode/dns/zone_manager.py) | Python 3 | CLI generator, syntax validator, and record inspector |

---

## 🚀 How to Import into Cloudflare (Step-by-Step)

1. Log into your [Cloudflare Dashboard](https://dash.cloudflare.com/).
2. Select your domain (e.g. `omnicodestudio.com` or your company domain).
3. In the left navigation sidebar, click **DNS** → **Records**.
4. Scroll to the **Import and Export** card and click **Import**.
5. Select [`omnicodestudio.com.zone`](file:///home/professorseanex/OmniCode/dns/omnicodestudio.com.zone).
6. Click **Import**. Cloudflare will parse and create all records automatically.

---

## 🗺️ Architectural Routing Map

```
Internet Request
       |
       ├── HTTPS Web Studio (Port 8080) ──→ Cloudflare Tunnel (c346aa27...) ──→ Oracle VM / Local Port 8080
       |     (studio.omnicodestudio.com)
       |
       ├── DuckDNS Dynamic Host ──────────→ omnicodestudio.duckdns.org ──────→ 71.11.99.168 (CWS Gateway)
       |     (duck.omnicodestudio.com)
       |
       └── Yu-Gi-Oh! Game Simulator (7911) → play.omnicodestudio.com ────────→ 147.224.147.30 (Oracle VM)
             (Raw TCP - Grey Cloud Only!)
```

⚙️ Proxy Status Rules (Crucial!)

Record	Type	Target	Cloudflare Proxy Status	Why
`@`, `www`	`CNAME`	`c346aa27...cfargotunnel.com.`	**Proxied (Orange Cloud)**	Free edge SSL/TLS & DDoS mitigation
`studio`, `api`	`CNAME`	`c346aa27...cfargotunnel.com.`	**Proxied (Orange Cloud)**	Direct edge routing to OmniCode
`local`, `gateway`	`A`	`71.11.99.168`	**DNS-Only (Grey Cloud)**	CreativeWorkzStudio LLC WAN IP
`cloud`, `vm`	`A`	`147.224.147.30`	**DNS-Only (Grey Cloud)**	Direct Oracle VM SSH / Administration
`duck`, `edge`	`CNAME`	`omnicodestudio.duckdns.org.`	**DNS-Only (Grey Cloud)**	Dynamic IP synchronization
`play`, `sim`	`A`	`147.224.147.30`	**DNS-Only (Grey Cloud)**	**MUST BE GREY CLOUD**: Raw TCP port 7911

🛠️ CLI Zone Management

```bash
cd /home/professorseanex/OmniCode

# Validate zone file syntax
python3 dns/zone_manager.py validate

# Inspect all configured records
python3 dns/zone_manager.py inspect

# Re-render with a custom domain
python3 dns/zone_manager.py render --domain yourcompany.com --out dns/yourcompany.com.zone
```
```

<TRACK 5> : {Infrastructure, Operations & Archives}/infra/dns/omnicodestudio.com.zone

ZONE | 49 LINES | 249 WORDS | 2.6 KB

```
; ================================================================================
; BIND RFC 1035 Zone File for omnicodestudio.com
; CreativeWorkzStudio LLC — OmniCode Platform Infrastructure
; Compatible with Cloudflare DNS Zone File Import (DNS -> Records -> Import)
; ================================================================================
$ORIGIN omnicodestudio.com.
$TTL 3600

; ================================================================================
; 1. PRIMARY WEB STUDIO & REST API (HTTP/HTTPS - Port 8080)
; ================================================================================
; Option A: Cloudflare Zero Trust Named Tunnel (Recommended)
; Tunnel ID: c346aa27-b4c1-41ba-815c-f66b2b84243b
; Benefits: Free SSL certificates, zero open firewall ports, DDoS mitigation.
@       IN  CNAME   c346aa27-b4c1-41ba-815c-f66b2b84243b.cfargotunnel.com.
www     IN  CNAME   c346aa27-b4c1-41ba-815c-f66b2b84243b.cfargotunnel.com.
studio  IN  CNAME   c346aa27-b4c1-41ba-815c-f66b2b84243b.cfargotunnel.com.
api     IN  CNAME   c346aa27-b4c1-41ba-815c-f66b2b84243b.cfargotunnel.com.

; Option B: Direct Oracle Cloud Compute 24/7 Instance (IP: 147.224.147.30)
; If routing directly to the Oracle VM rather than Cloudflare Tunnel, use these:
; @       IN  A       147.224.147.30
; www     IN  CNAME   omnicodestudio.com.
cloud   IN  A       147.224.147.30
vm      IN  A       147.224.147.30

; ================================================================================
; 2. CREATIVEWORKZSTUDIO LLC LOCAL GATEWAY & WORKSTATION (IP: 71.11.99.168)
; ================================================================================
; Points to CreativeWorkzStudio LLC primary gateway / local staging engine
local   IN  A       71.11.99.168
gateway IN  A       71.11.99.168

; ================================================================================
; 3. DYNAMIC DNS (DuckDNS) FALLBACK ALIASES
; ================================================================================
; Dynamic CNAME mappings to licensed DuckDNS host (omnicodestudio.duckdns.org)
duck    IN  CNAME   omnicodestudio.duckdns.org.
edge    IN  CNAME   omnicodestudio.duckdns.org.

; ================================================================================
; 4. UNIFIED PLATFORM CROSS-LINKS (Yu-Gi-Oh! Server & Simulator)
; ================================================================================
; Live duel simulator on Oracle VM (Raw TCP Port 7911 / HTTP Port 7922)
; NOTE: In Cloudflare Dashboard, play/sim MUST remain DNS-Only (Grey Cloud) for TCP
cards   IN  CNAME   c346aa27-b4c1-41ba-815c-f66b2b84243b.cfargotunnel.com.
play    IN  A       147.224.147.30
sim     IN  A       147.224.147.30
```

<TRACK 5> : {Infrastructure, Operations & Archives}/infra/dns/zone_manager.py PY 269 LINES 925 WORDS 10.7 KB

```python
#!/usr/bin/env python3
# ==============================================================================
# BLOCK 1: METADATA BLOCK
# ==============================================================================
"""
Module: dns.zone_manager
Architecture: Systems Engineering & Network Edge Routing (OmniCode Platform)
Organization: CreativeWorkzStudio LLC
Description:
    Authoritative BIND RFC 1035 Zone File Generator, Validator, and Synchronizer.
    Manages DNS routing rules for Cloudflare Zero Trust Tunnels, Oracle Cloud
    Compute VM (147.224.147.30), Local Gateway (71.11.99.168), and DuckDNS endpoints.

Exported CLI & API:
    - python3 dns/zone_manager.py validate [file.zone]
    - python3 dns/zone_manager.py inspect [file.zone]
    - python3 dns/zone_manager.py render [--domain DOMAIN] [--out PATH]
"""

import os
import re
import sys
from dataclasses import dataclass
from typing import Dict, List, Optional, Tuple

_CURRENT_DIR = os.path.dirname(os.path.abspath(__file__))
_PROJECT_ROOT = os.path.dirname(_CURRENT_DIR)

DEFAULT_ZONE_FILE_PATH: str = os.path.join(_CURRENT_DIR, "omnicodestudio.com.zone")
ENV_FILE_PATH: str = os.path.join(_PROJECT_ROOT, ".env")


# ==============================================================================
# BLOCK 2: OPENING BLOCK (Data Structures & Models)
# ==============================================================================

@dataclass
class DNSZoneRecord:
    name: str
    record_type: str
    target: str
    ttl: int = 3600
    comment: str = ""

    def to_bind_line(self) -> str:
        base = f"{self.name:<8} IN  {self.record_type:<7} {self.target}"
        if self.comment:
            return f"{base:<50} ; {self.comment}"
        return base


def parse_env_file(path: str) -> Dict[str, str]:
    values = {}
    if not os.path.isfile(path):
        return values
    with open(path, "r", encoding="utf-8") as f:
        for line in f:
            line = line.strip()
            if not line or line.startswith("#"):
                continue
            if "=" in line:
                k, v = line.split("=", 1)
                values[k.strip()] = v.strip().strip("\"'")
    return values


# ==============================================================================
# BLOCK 3: BODY BLOCK (Renderer, Validator & Inspector)
# ==============================================================================

def render_zone_file(
    domain: str = "omnicodestudio.com",
    oracle_ip: str = "147.224.147.30",
    local_ip: str = "71.11.99.168",
    duckdns_host: str = "omnicodestudio.duckdns.org",
    tunnel_id: str = "c346aa27-b4c1-41ba-815c-f66b2b84243b",
    ttl: int = 3600,
) -> str:
    """Renders a standard RFC 1035 / BIND 9 zone file string for Cloudflare import."""
```

```
    tunnel_target = f"{tunnel_id}.cfargotunnel.com."
    duck_target = f"{duckdns_host.rstrip('.') }."

    lines = [
        "; ================================================================================",
        f"; BIND RFC 1035 Zone File for {domain}",
        "; CreativeWorkzStudio LLC — OmniCode Platform Infrastructure",
        "; Compatible with Cloudflare DNS Zone File Import (DNS -> Records -> Import)",
        "; ================================================================================",
        f"$ORIGIN {domain.rstrip('.')}.",
        f"$TTL {ttl}",
        "",
        "; ================================================================================",
        "; 1. PRIMARY WEB STUDIO & REST API (HTTP/HTTPS - Port 8080)",
        "; ================================================================================",
        "; Option A: Cloudflare Zero Trust Named Tunnel (Recommended)",
        f"; Tunnel ID: {tunnel_id}",
        DNSZoneRecord("@", "CNAME", tunnel_target, ttl, "Root Apex -> Cloudflare Tunnel").to_bind_line(),
        DNSZoneRecord("www", "CNAME", tunnel_target, ttl, "WWW Subdomain -> Cloudflare Tunnel").to_bind_line(),
        DNSZoneRecord("studio", "CNAME", tunnel_target, ttl, "OmniCode Studio Web Interface").to_bind_line(),
        DNSZoneRecord("api", "CNAME", tunnel_target, ttl, "OmniCode REST API Endpoint").to_bind_line(),
        "",
        "; Option B: Oracle Cloud Compute 24/7 Instance",
        DNSZoneRecord("cloud", "A", oracle_ip, ttl, "Oracle Cloud VM Direct Ingress").to_bind_line(),
        DNSZoneRecord("vm", "A", oracle_ip, ttl, "Oracle Cloud VM Alias").to_bind_line(),
        "",
        "; ================================================================================",
        "; 2. CREATIVEWORKZSTUDIO LLC LOCAL GATEWAY (WORKSTATION IP)",
        "; ================================================================================",
        DNSZoneRecord("local", "A", local_ip, ttl, "CreativeWorkzStudio LLC Workstation WAN").to_bind_line(),
        DNSZoneRecord("gateway", "A", local_ip, ttl, "CreativeWorkzStudio LLC Gateway IP").to_bind_line(),
        "",
        "; ================================================================================",
        "; 3. DYNAMIC DNS (DuckDNS) FALLBACK ALIASES",
        "; ================================================================================",
        DNSZoneRecord("duck", "CNAME", duck_target, ttl, "DuckDNS Dynamic Host Endpoint").to_bind_line(),
        DNSZoneRecord("edge", "CNAME", duck_target, ttl, "DuckDNS Edge Alias").to_bind_line(),
        "",
        "; ================================================================================",
        "; 4. UNIFIED PLATFORM CROSS-LINKS (Yu-Gi-Oh! Server & Simulator)",
        "; ================================================================================",
        DNSZoneRecord("cards", "CNAME", tunnel_target, ttl, "Card Catalog & Lore Web Dashboard").to_bind_line(),
        DNSZoneRecord("play", "A", oracle_ip, ttl, "Live Duel Simulator (Raw TCP 7911 - Grey Cloud)").to_bind_line(),
        DNSZoneRecord("sim", "A", oracle_ip, ttl, "Game Room Manager (Port 7922)").to_bind_line(),
        "",
    ]
    return "\n".join(lines)


def validate_zone_file(file_path: str) -> Tuple[bool, List[str]]:
    """Validates zone file syntax and record definitions."""
    errors = []
    if not os.path.isfile(file_path):
        return False, [f"File not found: {file_path}"]

    with open(file_path, "r", encoding="utf-8") as f:
        content = f.read()

    has_origin = bool(re.search(r"^\$ORIGIN\s+[\w\.\-]+\.", content, re.MULTILINE))
    if not has_origin:
        errors.append("Missing required directive: $ORIGIN <domain>.")

    has_ttl = bool(re.search(r"^\$TTL\s+\d+", content, re.MULTILINE))
    if not has_ttl:
        errors.append("Missing required directive: $TTL <seconds>")

    record_pattern = re.compile(r"^\s*([\@\w\.\-]+)\s+(?:IN\s+)?(A|AAAA|CNAME|TXT|MX|NS)\s+([^\s;]+)", re.MULTILINE)
    matches = record_pattern.findall(content)
    if not matches:
        errors.append("No valid DNS resource records found in file.")

    return len(errors) == 0, errors


def inspect_zone_file(file_path: str):
    """Parses and prints a formatted summary table of the DNS zone records."""
    if not os.path.isfile(file_path):
        print(f"[!] Error: File '{file_path}' does not exist.")
        sys.exit(1)

    print("=" * 70)
    print(f"  🌐 DNS Zone Inspector: {os.path.basename(file_path)}")
    print("  CreativeWorkzStudio LLC — OmniCode Platform")
```

```
    print("=" * 80)

    with open(file_path, "r", encoding="utf-8") as f:
        lines = f.readlines()

    origin = "unknown"
    ttl = "unknown"
    records = []

    record_re = re.compile(r"^\s*([\@\w\.\-]+)\s+(?:IN\s+)?(A|AAAA|CNAME|TXT|MX|NS)\s+([^\s;]+)(?:\s*;\s*(.*))?")

    for line in lines:
        stripped = line.strip()
        if stripped.startswith("$ORIGIN"):
            origin = stripped.split()[1]
        elif stripped.startswith("$TTL"):
            ttl = stripped.split()[1]
        elif stripped and not stripped.startswith(";"):
            m = record_re.match(line)
            if m:
                records.append({
                    "name": m.group(1),
                    "type": m.group(2),
                    "target": m.group(3),
                    "comment": m.group(4) or ""
                })

    print(f"• Origin Domain : {origin}")
    print(f"• Default TTL   : {ttl} seconds")
    print(f"• Record Count  : {len(records)}\n")
    print(f"{'NAME':<10} {'TYPE':<8} {'TARGET':<45} {'NOTE'}")
    print("-" * 75)
    for r in records:
        print(f"{r['name']:<10} {r['type']:<8} {r['target']:<45} {r['comment']}")
    print("-" * 75)


# ==============================================================================
# BLOCK 4: CLOSING BLOCK (CLI Dispatcher)
# ==============================================================================

def main():
    args = sys.argv[1:]
    command = args[0] if args else "inspect"

    target_file = DEFAULT_ZONE_FILE_PATH
    env = parse_env_file(ENV_FILE_PATH)

    if command == "inspect":
        file_to_inspect = args[1] if len(args) > 1 else target_file
        inspect_zone_file(file_to_inspect)

    elif command == "validate":
        file_to_val = args[1] if len(args) > 1 else target_file
        valid, errors = validate_zone_file(file_to_val)
        if valid:
            print(f"[✓] Zone file '{file_to_val}' is syntactically valid RFC 1035 format.")
            sys.exit(0)
        else:
            print(f"[✗] Zone file validation failed with {len(errors)} error(s):")
            for err in errors:
                print(f"    - {err}")
            sys.exit(1)

    elif command == "render":
        domain = "omnicodestudio.com"
        out_file = target_file

        if "--domain" in args:
            idx = args.index("--domain")
            if idx + 1 < len(args):
                domain = args[idx + 1]

        if "--out" in args:
            idx = args.index("--out")
            if idx + 1 < len(args):
                out_file = args[idx + 1]

        oracle_ip = env.get("ORACLE_VM_HOST", "147.224.147.30")
        local_ip = env.get("PUBLIC_WAN_IP", "71.11.99.168")
        duckdns = env.get("PUBLIC_DOMAIN", "omnicodestudio.duckdns.org")
        tunnel_id = env.get("CLOUDFLARE_TUNNEL_ID", "c346aa27-b4c1-41ba-815c-f66b2b84243b")

```

```
        rendered = render_zone_file(
            domain=domain,
            oracle_ip=oracle_ip,
            local_ip=local_ip,
            duckdns_host=duckdns,
            tunnel_id=tunnel_id,
        )

        with open(out_file, "w", encoding="utf-8") as f:
            f.write(rendered)

        print(f"[✓] Rendered RFC 1035 zone file to: {out_file}")
        inspect_zone_file(out_file)

    else:
        print("Usage:")
        print("  python3 dns/zone_manager.py inspect [path.zone]")
        print("  python3 dns/zone_manager.py validate [path.zone]")
        print("  python3 dns/zone_manager.py render [--domain DOMAIN] [--out PATH]")


if __name__ == "__main__":
    main()
```

<TRACK 4> : {Variable Storage & Episodic Memory}/TRACK.md MD 10 LINES 62 WORDS 0.5 KB

```
# <TRACK 4> : {Variable Storage & Episodic Memory}

## Scope & Invariant

The AI model's persistent brain: episodic memory bank, runtime telemetry, and permanent knowledge vaults.

- `storage/scrolls/log/`: Traditional telemetry (`.log`), partitioned by domain (`character/`, `number/`, `sessions/`, `cortex/`).
- `storage/scrolls/scroll/`: Native 4-Block episodic traces (`.scroll`), partitioned by domain (`character/`, `number/`, `sessions/`, `cortex/`).
- `storage/data/`: Permanent immutable documentation vaults and structured datasets.
```

<TRACK 4> : {Variable Storage & Episodic Memory}/storage/weights/cpisi_base.weights

WEIGHTS | 214 LINES | 220 WORDS | 2.2 KB

```
# OMNICODE NEURAL BRAIN WEIGHTS (CPI-SI BASE)
LAYERS:2
N:0:0:1:0
W:0:0:0:1
W:0:0:1:1
W:0:0:2:1
W:0:0:3:0
W:0:0:4:0
W:0:0:5:1
W:0:0:6:-1
W:0:0:7:0
N:0:1:1:0
W:0:1:0:1
W:0:1:1:-1
W:0:1:2:1
W:0:1:3:0
W:0:1:4:0
W:0:1:5:1
W:0:1:6:0
W:0:1:7:0
N:0:2:1:0
W:0:2:0:1
W:0:2:1:1
W:0:2:2:1
W:0:2:3:0
W:0:2:4:0
W:0:2:5:1
W:0:2:6:0
W:0:2:7:0
N:0:3:1:0
W:0:3:0:1
W:0:3:1:1
W:0:3:2:1
W:0:3:3:1
W:0:3:4:0
W:0:3:5:1
W:0:3:6:0
W:0:3:7:0
N:0:4:1:0
W:0:4:0:1
W:0:4:1:-1
W:0:4:2:1
W:0:4:3:1
W:0:4:4:-1
W:0:4:5:1
W:0:4:6:0
W:0:4:7:0
N:0:5:1:0
W:0:5:0:1
W:0:5:1:-1
W:0:5:2:1
W:0:5:3:1
W:0:5:4:-1
W:0:5:5:1
W:0:5:6:0
W:0:5:7:0
N:0:6:1:0
W:0:6:0:1
W:0:6:1:-1
W:0:6:2:1
W:0:6:3:1
W:0:6:4:-1
W:0:6:5:1
W:0:6:6:-1
W:0:6:7:0
N:0:7:1:0
W:0:7:0:1
W:0:7:1:-1
W:0:7:2:1
W:0:7:3:1
W:0:7:4:-1
W:0:7:5:1
W:0:7:6:0
W:0:7:7:1
N:0:8:1:0
W:0:8:0:1
W:0:8:1:-1
```

```
W:0:8:2:1
W:0:8:3:1
W:0:8:4:-1
W:0:8:5:1
W:0:8:6:-1
W:0:8:7:0
N:0:9:1:0
W:0:9:0:1
W:0:9:1:1
W:0:9:2:1
W:0:9:3:1
W:0:9:4:-1
W:0:9:5:1
W:0:9:6:0
W:0:9:7:1
N:0:10:1:0
W:0:10:0:1
W:0:10:1:-1
W:0:10:2:1
W:0:10:3:1
W:0:10:4:-1
W:0:10:5:1
W:0:10:6:-1
W:0:10:7:0
N:0:11:1:0
W:0:11:0:1
W:0:11:1:1
W:0:11:2:1
W:0:11:3:0
W:0:11:4:-1
W:0:11:5:1
W:0:11:6:-1
W:0:11:7:1
N:0:12:1:0
W:0:12:0:1
W:0:12:1:-1
W:0:12:2:1
W:0:12:3:0
W:0:12:4:0
W:0:12:5:1
W:0:12:6:-1
W:0:12:7:-1
N:0:13:1:0
W:0:13:0:1
W:0:13:1:1
W:0:13:2:1
W:0:13:3:0
W:0:13:4:0
W:0:13:5:1
W:0:13:6:-1
W:0:13:7:-1
N:0:14:1:0
W:0:14:0:1
W:0:14:1:1
W:0:14:2:1
W:0:14:3:0
W:0:14:4:0
W:0:14:5:1
W:0:14:6:-1
W:0:14:7:1
N:0:15:1:0
W:0:15:0:1
W:0:15:1:-1
W:0:15:2:1
W:0:15:3:0
W:0:15:4:0
W:0:15:5:1
W:0:15:6:0
W:0:15:7:0
N:1:0:1:0
W:1:0:0:1
W:1:0:1:1
W:1:0:2:1
W:1:0:3:1
W:1:0:4:1
W:1:0:5:1
W:1:0:6:1
W:1:0:7:1
W:1:0:8:1
W:1:0:9:1
W:1:0:10:1
W:1:0:11:1
W:1:0:12:1
```

```
W:1:0:13:1
W:1:0:14:1
W:1:0:15:1
N:1:1:1:0
W:1:1:0:0
W:1:1:1:1
W:1:1:2:0
W:1:1:3:0
W:1:1:4:0
W:1:1:5:1
W:1:1:6:0
W:1:1:7:0
W:1:1:8:0
W:1:1:9:0
W:1:1:10:0
W:1:1:11:0
W:1:1:12:0
W:1:1:13:0
W:1:1:14:0
W:1:1:15:0
N:1:2:1:0
W:1:2:0:0
W:1:2:1:0
W:1:2:2:1
W:1:2:3:0
W:1:2:4:0
W:1:2:5:0
W:1:2:6:1
W:1:2:7:0
W:1:2:8:0
W:1:2:9:0
W:1:2:10:0
W:1:2:11:0
W:1:2:12:0
W:1:2:13:0
W:1:2:14:0
W:1:2:15:0
N:1:3:1:0
W:1:3:0:0
W:1:3:1:0
W:1:3:2:0
W:1:3:3:1
W:1:3:4:0
W:1:3:5:0
W:1:3:6:0
W:1:3:7:1
W:1:3:8:0
W:1:3:9:0
W:1:3:10:0
W:1:3:11:0
W:1:3:12:0
W:1:3:13:0
W:1:3:14:0
W:1:3:15:0
```

<TRACK 4> : {Variable Storage & Episodic Memory}/storage/data/immutable_documentation/English Standard Bible - Complete.pdf

DOC/BINARY | 1 LINES | 10 WORDS | 12873.5 KB

[Immutable Scripture Reference: English Standard Bible - Complete.pdf (12.57 MB)]

<TRACK 4> : {Variable Storage & Episodic Memory}/storage/data/immutable_documentation/Ethiopian Bible - Complete.pdf

DOC/BINARY | 1 LINES | 9 WORDS | 10846.6 KB

[Immutable Scripture Reference: Ethiopian Bible - Complete.pdf (10.59 MB)]

<TRACK 4> : {Variable Storage & Episodic Memory}/storage/data/immutable_documentation/King James Bible - Complete.pdf

DOC/BINARY | 1 LINES | 10 WORDS | 12193.6 KB

[Immutable Scripture Reference: King James Bible - Complete.pdf (11.91 MB)]

<TRACK 4> : {Variable Storage & Episodic Memory}/storage/data/immutable_documentation/New King James Bible - Complete.pdf

DOC/BINARY | 1 LINES | 11 WORDS | 6624.0 KB

[Immutable Scripture Reference: New King James Bible - Complete.pdf (6.47 MB)]

<TRACK 4> : {Variable Storage & Episodic Memory}/storage/data/immutable_documentation/World English Bible - Complete.pdf

DOC/BINARY | 1 LINES | 10 WORDS | 11440.6 KB

[Immutable Scripture Reference: World English Bible - Complete.pdf (11.17 MB)]

scripts/build_notebooklm_pdf.sh SH 76 LINES 329 WORDS 3.1 KB

```
#!/usr/bin/env bash
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( OmniCode Google NotebookLM Chapter-Based PDF Exporter Runner )
# ================================================================================
# ARCHITECTURAL TOPOLOGY:
#   Orchestrates chapter-partitioned documentation export for Google NotebookLM
#   and AI model training. Ensures files are split into manageable chapter
#   volumes (10-35 pages) to prevent token dilution and needle-in-haystack loss.
#
# SCRIPTURAL WITNESSES:
#   - Exodus 31:18: "written with the finger of God"
#   - Proverbs 24:27: "Prepare thy work without, and make it fit for thyself"
#   - Proverbs 22:28: "Remove not the ancient landmark"
# ================================================================================

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Environment Validation, Toolchain Verification & Path Setup )
# ================================================================================
set -euo pipefail

SCRIPT_DIR="$(cd "$(dirname "${BASH_SOURCE[0]}")" && pwd)"
REPO_ROOT="$(cd "${SCRIPT_DIR}/.." && pwd)"
OUTPUT_DIR="${REPO_ROOT}/docs/notebooklm"

echo "================================================================================"
echo "==> OMNICODE NOTEBOOKLM CHAPTER EXPORTER (4-BLOCK RUNNER)"
echo "================================================================================"

# Validate Python 3
if ! command -v python3 >/dev/null 2>&1; then
    echo "[-] Error: python3 is required but not installed." >&2
    exit 1
fi

# Validate Headless Browser
if ! command -v google-chrome >/dev/null 2>&1 && \
   ! command -v chromium >/dev/null 2>&1; then
    echo "    HTML artifacts created, but PDF conversion may fail." >&2
fi

# Ensure output directory exists
mkdir -p "${OUTPUT_DIR}"

# ================================================================================
# BLOCK 3: BODY BLOCK
# ( Pipeline Execution & Chapter Generation )
# ================================================================================
echo "==> Invoking Chapter Exporter Pipeline..."
python3 "${REPO_ROOT}/scripts/export_notebooklm_pdf.py" "$@"

# ================================================================================
# BLOCK 4: CLOSING BLOCK
# ( Artifact Verification, Summary & Affirmative Sealing )
# ================================================================================
echo ""
echo "================================================================================"
echo "==> CHAPTER ARTIFACTS VERIFICATION"
echo "================================================================================"

PDF_COUNT=$(find "${OUTPUT_DIR}" -maxdepth 1 -name "*.pdf" | wc -l)
MD_COUNT=$(find "${OUTPUT_DIR}" -maxdepth 1 -name "*.md" | wc -l)

echo "[+] Total Chapter PDFs Generated: ${PDF_COUNT}"
echo "[+] Total Ingestion Manifests:    ${MD_COUNT}"
echo "[+] Manifest Location: ${OUTPUT_DIR}/NOTEBOOKLM_INGESTION_MANIFEST.md"

if [ "${PDF_COUNT}" -gt 0 ]; then
    echo "[√] Status: PROCEED (+1) - Chapter documentation ready for ingestion."
    exit 0
else
    echo "[-] Status: ROLLBACK (-1) - No PDF artifacts generated." >&2
    exit 1
fi
```

scripts/export_notebooklm_pdf.py PY 1133 LINES 3653 WORDS 39.0 KB

```python
#!/usr/bin/env python3
# ================================================================================
# BLOCK 1: METADATA BLOCK
# ( OmniCode Repository to Google NotebookLM Chapter-Based PDF Pipeline )
# ================================================================================
# SCRIPTURE ANCHORS & EPISTEMIC WITNESSES:
#   - Exodus 31:18: "written with the finger of God"
#     Inscription of eternal moral truth upon stone.
#   - Proverbs 24:27: "Prepare thy work without, and make it fit for thyself"
#     Systematic modularization and chapter-based order.
#   - Proverbs 22:28: "Remove not the ancient landmark"
#     Preservation of invariant boundaries across all tracks.
#
# ARCHITECTURAL STRATEGY:
#   Partitions the entire repository into discrete, thematic Chapters:
#     - Chapter 01: Core Architecture, Manifest & Decalogue Bedrock
#     - Chapter 02: Track 0 - Kernel Substrate & Bare Metal
#     - Chapter 03: Track 1 - Abstract Syntax Tree & Parser
#     - Chapter 04: Track 1 - Core Types & Process Tape Ribbon
#     - Chapter 05: Track 1 - AI Cortex & Neural Learning Engine
#     - Chapter 06: Track 1 - Runtime Environment & Evaluator
#     - Chapter 07: Track 1 - Bytecode Assembler & Lowering
#     - Chapter 08: Track 1 - Diagnostics & 4-Block Linter
#     - Chapter 09: Track 1 - Terminal, REPL & Hover Inspection
#     - Chapter 10: Track 1 - Verification & Functional Test Suites
#     - Chapter 11: Track 2 - Lexicon: Character Primitive Type & Bridges
#     - Chapter 12: Track 2 - Lexicon: Number Primitive Type & Bridges
#     - Chapter 13: Track 2 - Lexicon: State, Container, Site & Text
#     - Chapter 14: Track 2 - Lexicon: Systems, Stewards & Physical Places
#     - Chapter 15: Track 2 - Lexicon: Verbs, Pronouns & Operators
#     - Chapter 16: Track 2 - Lexicon: Modifiers, Conjunctions & Traps
#     - Chapter 17: Track 2 - Standard Library Modules
#     - Chapter 18: Track 3 - Applications, C/Lua Bridges & Studio
#     - Chapter 19: Track 4 & 5 - Immutable Data & Infrastructure
# ================================================================================

import os
import sys
import html
import json
import time
import shutil
import argparse
import subprocess
from datetime import datetime
from pathlib import Path

# ================================================================================
# BLOCK 2: OPENING BLOCK
# ( Configuration Constants, Binary Filters & Chapter Definitions )
# ================================================================================

REPO_ROOT = Path("/home/professorseanex/OmniCode").resolve()
OUTPUT_DIR = REPO_ROOT / "docs" / "notebooklm"

EXCLUDE_DIRS = {
    ".git", "target", ".vscode", ".gemini", "node_modules",
    "__pycache__", ".cargo", "dist", "notebooklm", "scrolls"
}

BINARY_EXTENSIONS = {
    ".pdf", ".img", ".elf", ".efi", ".bin", ".iso", ".png", ".jpg", ".jpeg",
    ".gif", ".ico", ".woff", ".woff2", ".ttf", ".eot", ".tar", ".gz",
    ".zip", ".pyc", ".o", ".a", ".so", ".dylib", ".rlib"
}

def is_binary_file(filepath: Path) -> bool:
    """Detects whether a file is binary via extension or byte inspection."""
    if filepath.suffix.lower() in BINARY_EXTENSIONS:
        return True
    try:
        with open(filepath, "rb") as f:
            chunk = f.read(1024)
            if b"\x00" in chunk:
                return True
    except Exception:
        return True
    return False

```

```
CHAPTER_DEFINITIONS = [
    {
        "id": "CH 01",
        "slug": "Ch01_Foundations_and_Manifest",
        "filename": "OmniCode_Ch01_Foundations_and_Manifest.pdf",
        "title": "Chapter 1: Foundations, Manifest & Decalogue Bedrock",
        "subtitle": "Moral Bedrock, Exodus 20 Decalogue, Manifest & Packaging",
        "prompt": "How does the Exodus 20 Decalogue govern the AI cortex?",
    },
    {
        "id": "CH 02",
        "slug": "Ch02_Track0_Kernel_Substrate",
        "filename": "OmniCode_Ch02_Track0_Kernel_Substrate.pdf",
        "title": "Chapter 2: Track 0 - Kernel Substrate & Bare Metal",
        "subtitle": "Bare-Metal x86 Boot, GDT, IDT, MMIO, VGA & Serial Ports",
        "prompt": "Trace how Genesis Boot initializes hardware MMIO registers.",
    },
    {
        "id": "CH 03",
        "slug": "Ch03_Track1_Parser_and_AST",
        "filename": "OmniCode_Ch03_Track1_Parser_and_AST.pdf",
        "title": "Chapter 3: Track 1 - Abstract Syntax Tree & Parser",
        "subtitle": "Lexical Tokens, Grammar Rules, AST Entities & Asides",
        "prompt": "Explain how the AST preserves first-class intent asides.",
    },
    {
        "id": "CH 04",
        "slug": "Ch04_Track1_Core_and_Tape_Engine",
        "filename": "OmniCode_Ch04_Track1_Core_and_Tape_Engine.pdf",
        "title": "Chapter 4: Track 1 - Core Types & Process Tape Ribbon",
        "subtitle": "TapeHead 5-Ws Ribbon, Cell, Word, Reels & Operators",
        "prompt": "How does the TapeHead coordinate the 5 Ws and 1 H in time?",
    },
    {
        "id": "CH 05",
        "slug": "Ch05_Track1_AI_Cortex_and_Neural_Engine",
        "filename": "OmniCode_Ch05_Track1_AI_Cortex_and_Neural_Engine.pdf",
        "title": "Chapter 5: Track 1 - AI Cortex & Neural Learning Engine",
        "subtitle": "Cognitive Loop, Synapses, Episodic Learner & Transducer",
        "prompt": "How does the AI Cortex reconcile deliberations with truth?",
    },
    {
        "id": "CH 06",
        "slug": "Ch06_Track1_Runtime_and_Evaluator",
        "filename": "OmniCode_Ch06_Track1_Runtime_and_Evaluator.pdf",
        "title": "Chapter 6: Track 1 - Runtime Environment & Evaluator",
        "subtitle": "SVO Verbs, Causal Clock, Transactions & Rollback",
        "prompt": "How does runtime guarantee forward time in rollback?",
    },
    {
        "id": "CH 07",
        "slug": "Ch07_Track1_Bytecode_Assembler",
        "filename": "OmniCode_Ch07_Track1_Bytecode_Assembler.pdf",
        "title": "Chapter 7: Track 1 - Bytecode Assembler & Lowering",
        "subtitle": "Instruction Encodings, Lowering Lexicon Tapes to Words",
        "prompt": "Trace lowering pipeline from tape rolls to machine words.",
    },
    {
        "id": "CH 08",
        "slug": "Ch08_Track1_Diagnostics_Linter",
        "filename": "OmniCode_Ch08_Track1_Diagnostics_Linter.pdf",
        "title": "Chapter 8: Track 1 - Diagnostics & 4-Block Linter",
        "subtitle": "Spatial Ruler, Morphological Bounds & Block Validation",
        "prompt": "How does the 4-block linter enforce spatial line geometry?",
    },
    {
        "id": "CH 09",
        "slug": "Ch09_Track1_Terminal_and_Hover",
        "filename": "OmniCode_Ch09_Track1_Terminal_and_Hover.pdf",
        "title": "Chapter 9: Track 1 - Terminal, REPL & Hover Inspection",
        "subtitle": "Interactive REPL, Task Scheduler & 3-Tier Hover Cards",
        "prompt": "How does hover engine bridge tape rolls to omni sources?",
    },
    {
        "id": "CH 10",
        "slug": "Ch10_Track1_Verification_Tests",
        "filename": "OmniCode_Ch10_Track1_Verification_Tests.pdf",
        "title": "Chapter 10: Track 1 - Verification & Functional Test Suites",
        "subtitle": "Integrated Tripwires, Boot Tests & Functional Execution",
        "prompt": "How do tripwire tests prove zero-disk-mutation on dry run?",
    },
    {
        "id": "CH 11",
```

```
        "slug": "Ch11_Track2_Lexicon_Character_Type",
        "filename": "OmniCode_Ch11_Track2_Lexicon_Character_Type.pdf",
        "title": "Chapter 11: Track 2 - Lexicon: Character Primitive Type",
        "subtitle": "Single-Cell Enclosure, 5-Trit / 8-Bit ASCII Invariance",
        "prompt": "Explain the bijective mapping of character 'A' to 5 trits.",
    },
    {
        "id": "CH 12",
        "slug": "Ch12_Track2_Lexicon_Number_Type",
        "filename": "OmniCode_Ch12_Track2_Lexicon_Number_Type.pdf",
        "title": "Chapter 12: Track 2 - Lexicon: Number Primitive Type",
        "subtitle": "Dual-Rail Polar Planes, 32-Trit Word & Zero-Sum ALU",
        "prompt": "How does dual-rail balance enable O(1) rail-swap negation?",
    },
    {
        "id": "CH 13",
        "slug": "Ch13_Track2_Lexicon_State_and_Containers",
        "filename": "OmniCode_Ch13_Track2_Lexicon_State_and_Containers.pdf",
        "title": "Chapter 13: Track 2 - Lexicon: State, Container, Site & Text",
        "subtitle": "Quad-State T4 Clock, Memory Envelopes & Bounded Sites",
        "prompt": "How do IT, BOUND, and TURN govern canonical loop cadence?",
    },
    {
        "id": "CH 14",
        "slug": "Ch14_Track2_Lexicon_Nouns_and_Entities",
        "filename": "OmniCode_Ch14_Track2_Lexicon_Nouns_and_Entities.pdf",
        "title": "Chapter 14: Track 2 - Lexicon: Systems, Places & Vessels",
        "subtitle": "Operators, Supervisors, Storehouses, Partitions & Vaults",
        "prompt": "Trace how Covenant Storehouse partitions via v--.",
    },
    {
        "id": "CH 15",
        "slug": "Ch15_Track2_Lexicon_Verbs_and_Operators",
        "filename": "OmniCode_Ch15_Track2_Lexicon_Verbs_and_Operators.pdf",
        "title": "Chapter 15: Track 2 - Lexicon: Verbs, Pronouns & Operators",
        "subtitle": "Directional SVO Verbs, Scale Vectors & Polarity",
        "prompt": (
            "Explain difference between ascension (/-^) and descension (\\-v)."
        ),
    },
    {
        "id": "CH 16",
        "slug": "Ch16_Track2_Lexicon_Modifiers_and_Connectives",
        "filename": (
            "OmniCode_Ch16_Track2_Lexicon_Modifiers_and_Connectives.pdf"
        ),
        "title": "Chapter 16: Track 2 - Modifiers, Conjunctions & Traps",
        "subtitle": "Invariants, Quad-States, Cadence, Pipelines & Caveats",
        "prompt": "How does the adversative caveat operator (!) guard truth?",
    },
    {
        "id": "CH 17",
        "slug": "Ch17_Track2_Standard_Library",
        "filename": "OmniCode_Ch17_Track2_Standard_Library.pdf",
        "title": "Chapter 17: Track 2 - Standard Library Modules",
        "subtitle": "Core Logic, Vectors, Arithmetic & Memory Management",
        "prompt": "How do standard library modules export pure invariants?",
    },
    {
        "id": "CH 18",
        "slug": "Ch18_Track3_Applications_and_Studio",
        "filename": "OmniCode_Ch18_Track3_Applications_and_Studio.pdf",
        "title": "Chapter 18: Track 3 - Applications, Bridges & Studio",
        "subtitle": "C99 Bare-Metal, Lua Coroutines, Boundary Demos & HUD",
        "prompt": "How does Lua coroutine engine run tape rolls as fibers?",
    },
    {
        "id": "CH 19",
        "slug": "Ch19_Track4_and_5_Storage_and_Infra",
        "filename": "OmniCode_Ch19_Track4_and_5_Storage_and_Infra.pdf",
        "title": "Chapter 19: Track 4 & 5 - Immutable Data & Infrastructure",
        "subtitle": "Canonical Bibles, OCI Scripts, Toolchain & CI/CD",
        "prompt": (
            "How does infrastructure preserve immutable scriptural anchors?"
        ),
    },
]

# ==============================================================================
# BLOCK 3: BODY BLOCK
# ( File Discovery, Chapter Partitioning, HTML Rendering & Chrome Lowering )
# ==============================================================================

```

```
CSS_STYLES = """
@page {
    size: letter portrait;
    margin: 1.5cm 1.2cm 1.5cm 1.2cm;
    @top-center {
        content: "OmniCode AI OS & Substrate | Google NotebookLM Curriculum";
        font-family: -apple-system, BlinkMacSystemFont, "Segoe UI", sans-serif;
        font-size: 7pt;
        color: #888888;
    }
    @bottom-left {
        content: "Witnesses: Exodus 31:18, Proverbs 24:27, Proverbs 22:28";
        font-family: -apple-system, BlinkMacSystemFont, "Segoe UI", sans-serif;
        font-size: 7pt;
        color: #888888;
    }
    @bottom-right {
        content: "Page " counter(page);
        font-family: -apple-system, BlinkMacSystemFont, "Segoe UI", sans-serif;
        font-size: 7pt;
        color: #555555;
    }
}

body {
    font-family: -apple-system, BlinkMacSystemFont, "Segoe UI", sans-serif;
    color: #1a1a1a;
    background: #ffffff;
    line-height: 1.45;
    font-size: 8.5pt;
    margin: 0;
    padding: 0;
}

.page-break {
    page-break-before: always;
    break-before: page;
}

.cover-page {
    min-height: 90vh;
    display: flex;
    flex-direction: column;
    justify-content: center;
    border: 3px double #1e3a8a;
    padding: 35px;
    background: linear-gradient(135deg, #f8fafc 0%, #edf2f7 100%);
    box-sizing: border-box;
}

.cover-title {
    font-size: 20pt;
    font-weight: 800;
    color: #0f172a;
    margin-bottom: 6px;
    letter-spacing: -0.5px;
    border-bottom: 3px solid #3b82f6;
    padding-bottom: 10px;
}

.cover-subtitle {
    font-size: 11pt;
    color: #334155;
    font-weight: 600;
    margin-bottom: 20px;
}

.cover-metadata-grid {
    display: grid;
    grid-template-columns: 1fr 1fr;
    gap: 10px;
    background: #ffffff;
    border: 1px solid #cbd5e1;
    border-radius: 6px;
    padding: 14px;
    margin-bottom: 20px;
}

.metadata-item {
    font-size: 8pt;
}

.metadata-label {
```

```
    font-weight: bold;
    color: #475569;
    text-transform: uppercase;
    font-size: 7pt;
    display: block;
}

.metadata-value {
    color: #0f172a;
    font-family: monospace;
    font-size: 8pt;
}

.scripture-card {
    background: #f0fdf4;
    border-left: 4px solid #16a34a;
    padding: 10px 14px;
    border-radius: 4px;
    margin-bottom: 18px;
}

.scripture-title {
    font-weight: bold;
    color: #166534;
    font-size: 8pt;
    text-transform: uppercase;
    margin-bottom: 4px;
}

.scripture-verse {
    font-style: italic;
    color: #14532d;
    font-size: 7.5pt;
    margin: 2px 0;
}

.guide-card {
    background: #eff6ff;
    border-left: 4px solid #2563eb;
    padding: 12px 16px;
    border-radius: 4px;
    margin-bottom: 18px;
}

.guide-title {
    font-weight: bold;
    color: #1e40af;
    font-size: 8.5pt;
    text-transform: uppercase;
    margin-bottom: 5px;
}

.guide-text {
    font-size: 7.5pt;
    color: #1e3a8a;
    line-height: 1.35;
    margin: 3px 0;
}

.toc-container {
    margin: 15px 0;
}

.toc-header {
    font-size: 13pt;
    font-weight: bold;
    color: #0f172a;
    border-bottom: 2px solid #cbd5e1;
    padding-bottom: 5px;
    margin-bottom: 10px;
    text-transform: uppercase;
}

.toc-table {
    width: 100%;
    border-collapse: collapse;
    font-size: 7.5pt;
}

.toc-table th {
    background: #f1f5f9;
    color: #334155;
    text-align: left;
```

```
    padding: 5px 8px;
    border-bottom: 2px solid #94a3b8;
    text-transform: uppercase;
    font-size: 7pt;
}

.toc-table td {
    padding: 4px 8px;
    border-bottom: 1px solid #e2e8f0;
}

.toc-table tr:nth-child(even) {
    background: #f8fafc;
}

.file-card {
    margin-top: 12px;
    margin-bottom: 20px;
}

.file-header-box {
    background: #0f172a;
    color: #ffffff;
    padding: 7px 10px;
    border-radius: 4px 4px 0 0;
    display: flex;
    justify-content: space-between;
    align-items: center;
    page-break-after: avoid;
    break-after: avoid;
}

.file-path {
    font-family: ui-monospace, SFMono-Regular, "SF Mono", monospace;
    font-size: 8pt;
    font-weight: 700;
    color: #38bdf8;
    word-break: break-all;
}

.file-meta-badges {
    display: flex;
    gap: 6px;
}

.badge {
    background: #1e293b;
    border: 1px solid #334155;
    padding: 1px 5px;
    border-radius: 3px;
    font-size: 6.5pt;
    color: #cbd5e1;
    font-family: monospace;
    text-transform: uppercase;
}

.file-content-box {
    background: #f8fafc;
    border: 1px solid #cbd5e1;
    border-top: none;
    padding: 8px;
    border-radius: 0 0 4px 4px;
    overflow-x: auto;
}

pre.code-block {
    margin: 0;
    font-family: ui-monospace, SFMono-Regular, "SF Mono", monospace;
    font-size: 6.8pt;
    line-height: 1.32;
    color: #0f172a;
    tab-size: 4;
    white-space: pre-wrap;
    word-break: break-word;
}

.line-num {
    color: #94a3b8;
    user-select: none;
    display: inline-block;
    width: 32px;
    text-align: right;
    margin-right: 8px;
```

```
    border-right: 1px solid #cbd5e1;
    padding-right: 5px;
}
"""

def categorize_file(rel_path: str) -> str:
    """Categorizes a file into one of the 19 canonical chapter slugs."""
    p = rel_path.lower()

    # Chapter 1: Root manifests and foundational documents
    if '/' not in rel_path or any(
        rel_path.startswith(x)
        for x in ['README', 'manifest', 'Cargo', '.env']
    ):
        return "Ch01_Foundations_and_Manifest"

    # Chapter 2: Track 0
    if 'track 0' in p:
        return "Ch02_Track0_Kernel_Substrate"

    # Chapters 3 - 10: Track 1 Host Engine
    if 'track 1' in p:
        if '/tests/' in p:
            return "Ch10_Track1_Verification_Tests"
        if '/src/parser/' in p or '/src/ast/' in p:
            return "Ch03_Track1_Parser_and_AST"
        if '/src/core/' in p or '/src/cogs/' in p or rel_path.endswith(
            ('main.rs', 'lib.rs')
        ):
            return "Ch04_Track1_Core_and_Tape_Engine"
        if '/src/ai/' in p:
            return "Ch05_Track1_AI_Cortex_and_Neural_Engine"
        if '/src/runtime/environment/' in p or '/src/runtime/evaluator/' in p:
            return "Ch06_Track1_Runtime_and_Evaluator"
        if '/src/runtime/assembler/' in p:
            return "Ch07_Track1_Bytecode_Assembler"
        if '/src/diagnostics/linter/' in p:
            return "Ch08_Track1_Diagnostics_Linter"
        if '/src/terminal/' in p or '/src/cli/' in p or 'hover' in p:
            return "Ch09_Track1_Terminal_and_Hover"
        return "Ch04_Track1_Core_and_Tape_Engine"

    # Chapters 11 - 17: Track 2 Language & Standard Library
    if 'track 2' in p:
        if '01_nouns/ideas/types/character' in p:
            return "Ch11_Track2_Lexicon_Character_Type"
        if '01_nouns/ideas/types/number' in p:
            return "Ch12_Track2_Lexicon_Number_Type"
        if '01_nouns/ideas/types' in p:
            return "Ch13_Track2_Lexicon_State_and_Containers"
        if '01_nouns' in p:
            return "Ch14_Track2_Lexicon_Nouns_and_Entities"
        if '02_pronouns' in p or '03_verbs' in p or '/operators/' in p:
            return "Ch15_Track2_Lexicon_Verbs_and_Operators"
        if any(
            x in p for x in [
                '04_adjectives', '05_adverbs', '06_prepositions',
                '07_conjunctions', '08_interjections'
            ]
        ):
            return "Ch16_Track2_Lexicon_Modifiers_and_Connectives"
        if '/lib/' in p:
            return "Ch17_Track2_Standard_Library"
        return "Ch16_Track2_Lexicon_Modifiers_and_Connectives"

    # Chapter 18: Track 3 Applications
    if 'track 3' in p:
        return "Ch18_Track3_Applications_and_Studio"

    # Chapter 19: Track 4 & 5 Storage & Infrastructure
    if 'track 4' in p or 'track 5' in p or 'scripts' in p:
        return "Ch19_Track4_and_5_Storage_and_Infra"

    return "Ch01_Foundations_and_Manifest"

def discover_repository_files():
    """Scans and categorizes text and manifest files across the repository."""
    all_files = []

    for root, dirs, files in os.walk(REPO_ROOT):
        dirs[:] = [
            d for d in dirs
            if d not in EXCLUDE_DIRS and not d.startswith(".")
```

```
        ]

        rel_root = Path(root).relative_to(REPO_ROOT)
        if any(x in rel_root.parts for x in ["notebooklm", "scrolls"]):
            continue

        top_component = rel_root.parts[0] if rel_root.parts else ""

        for file in sorted(files):
            if (
                file.startswith(".")
                or file.endswith("~")
                or file.endswith(".tmp")
                or file.endswith(".tmp.html")
            ):
                continue

            full_path = Path(root) / file
            rel_path = full_path.relative_to(REPO_ROOT)
            rel_str = str(rel_path)

            if any(x in rel_path.parts for x in ["notebooklm", "scrolls"]):
                continue

            is_bin = is_binary_file(full_path)
            file_bytes = full_path.stat().st_size
            lines_count = 0
            words_count = 0
            content = ""

            if not is_bin:
                try:
                    with open(
                        full_path, "r", encoding="utf-8", errors="replace"
                    ) as f:
                        content = f.read()
                        lines_count = (
                            content.count("\n") + (1 if content else 0)
                        )
                        words_count = len(content.split())
                except Exception as e:
                    content = f"[Error reading file: {e}]"
            else:
                if full_path.suffix.lower() == ".pdf":
                    size_mb = file_bytes / (1024 * 1024)
                    content = (
                        f"[Immutable Scripture Reference: "
                        f"{file} ({size_mb:.2f} MB)]"
                    )
                else:
                    size_kb = file_bytes / 1024.0
                    content = f"[Binary Artifact: {file} ({size_kb:.1f} KB)]"
                lines_count = 1
                words_count = len(content.split())

            entry = {
                "rel_path": rel_str,
                "full_path": str(full_path),
                "filename": file,
                "extension": full_path.suffix.lower(),
                "top_dir": top_component,
                "chapter_slug": categorize_file(rel_str),
                "is_binary": is_bin,
                "lines": lines_count,
                "words": words_count,
                "bytes": file_bytes,
                "content": content,
            }
            all_files.append(entry)

    return all_files

def render_file_card_html(entry):
    """Renders a single file into a publication card with line numbers."""
    rel_path = entry["rel_path"]
    ext = entry["extension"]
    is_bin = entry["is_binary"]
    lines = entry["lines"]
    words = entry["words"]
    size_kb = entry["bytes"] / 1024.0
    content = entry["content"]

    badge_type = ext.replace(".", "").upper() if ext else "TEXT"
```

```
    if is_bin:
        badge_type = "DOC/BINARY"

    out = []
    out.append('<div class="file-card page-break">')
    out.append('  <div class="file-header-box">')
    out.append(f'    <div class="file-path">{html.escape(rel_path)}</div>')
    out.append('    <div class="file-meta-badges">')
    out.append(f'      <span class="badge">{badge_type}</span>')
    out.append(f'      <span class="badge">{lines} Lines</span>')
    out.append(f'      <span class="badge">{words} Words</span>')
    out.append(f'      <span class="badge">{size_kb:.1f} KB</span>')
    out.append('    </div>')
    out.append('  </div>')
    out.append('  <div class="file-content-box">')

    if is_bin:
        out.append(
            '    <p style="font-style:italic; color:#475569; '
            'margin:8px 0; font-size:8pt;">'
        )
        out.append(f'      {html.escape(content)}')
        out.append('    </p>')
    else:
        out.append('    <pre class="code-block">')
        raw_lines = content.splitlines()
        for i, l in enumerate(raw_lines, 1):
            escaped = html.escape(l)
            out.append(f'<span class="line-num">{i}</span>{escaped}')
        out.append('</pre>')

    out.append('  </div>')
    out.append('</div>\n')
    return "\n".join(out)

def build_chapter_html(chapter_def, files):
    """Assembles a self-contained publication document for a single chapter."""
    ch_id = chapter_def["id"]
    ch_title = chapter_def["title"]
    ch_sub = chapter_def["subtitle"]
    ch_prompt = chapter_def["prompt"]

    ch_lines = sum(f["lines"] for f in files)
    ch_words = sum(f["words"] for f in files)
    gen_time = datetime.now().strftime("%Y-%m-%d %H:%M:%S")

    html_parts = []
    html_parts.append('<!DOCTYPE html>')
    html_parts.append('<html lang="en">')
    html_parts.append('<head>')
    html_parts.append('  <meta charset="UTF-8">')
    html_parts.append(f'  <title>{html.escape(ch_title)}</title>')
    html_parts.append(f'  <style>{CSS_STYLES}</style>')
    html_parts.append('</head>')
    html_parts.append('<body>')

    # 1. Cover Page
    html_parts.append('<div class="cover-page">')
    html_parts.append(
        f'  <div class="cover-title">OmniCode: {html.escape(ch_title)}</div>'
    )
    html_parts.append(
        f'  <div class="cover-subtitle">{html.escape(ch_sub)}</div>'
    )

    html_parts.append('  <div class="cover-metadata-grid">')
    html_parts.append('    <div class="metadata-item">')
    html_parts.append(
        '      <span class="metadata-label">Chapter Identifier</span>'
    )
    html_parts.append(
        f'      <span class="metadata-value">{html.escape(ch_id)}</span>'
    )
    html_parts.append('    </div>')
    html_parts.append('    <div class="metadata-item">')
    html_parts.append(
        '      <span class="metadata-label">NotebookLM Word Count</span>'
    )
    html_parts.append(
        f'      <span class="metadata-value">{ch_words:,} words</span>'
    )
    html_parts.append('    </div>')
    html_parts.append('    <div class="metadata-item">')
```

```
    html_parts.append(
        '      <span class="metadata-label">Cataloged Chapter Files</span>'
    )
    html_parts.append(
        f'      <span class="metadata-value">{len(files)} files '
        f'({ch_lines:,} lines)</span>'
    )
    html_parts.append('    </div>')
    html_parts.append('    <div class="metadata-item">')
    html_parts.append(
        '      <span class="metadata-label">Generation Date</span>'
    )
    html_parts.append(f'      <span class="metadata-value">{gen_time}</span>')
    html_parts.append('    </div>')
    html_parts.append('  </div>')

    # Scripture Witness Card
    html_parts.append('  <div class="scripture-card">')
    html_parts.append(
        '    <div class="scripture-title">'
        'Epistemic Covenant Bedrock & Immutable Landmarks</div>'
    )
    html_parts.append(
        '    <div class="scripture-verse">"And he gave unto Moses... two '
        'tables of testimony, tables of stone, written with the finger of '
        'God." &mdash; Exodus 31:18</div>'
    )
    html_parts.append(
        '    <div class="scripture-verse">"Prepare thy work without, and '
        'make it fit for thyself in the field; and afterwards build thine '
        'house." &mdash; Proverbs 24:27</div>'
    )
    html_parts.append(
        '    <div class="scripture-verse">"Remove not the ancient landmark, '
        'which thy fathers have set." &mdash; Proverbs 22:28</div>'
    )
    html_parts.append('  </div>')

    # Grounding Prompt Card
    html_parts.append('  <div class="guide-card">')
    html_parts.append(
        '    <div class="guide-title">'
        'Google NotebookLM Grounding Focus & Learning Prompt</div>'
    )
    html_parts.append(
        f'    <div class="guide-text">&bull; <strong>Chapter Focus:</strong> '
        f'<em>"{html.escape(ch_prompt)}"</em></div>'
    )
    html_parts.append(
        '    <div class="guide-text">'
        '&bull; <strong>Architectural Rule:</strong> '
        'All definitions conform to 4-block structure & spatial ruler.</div>'
    )
    html_parts.append('  </div>')
    html_parts.append('</div>')

    # 2. Table of Contents
    html_parts.append('<div class="toc-container page-break">')
    html_parts.append(
        f'  <div class="toc-header">Chapter Manifest & Index '
        f'({len(files)} files)</div>'
    )
    html_parts.append('  <table class="toc-table">')
    html_parts.append('    <thead>')
    html_parts.append('      <tr>')
    html_parts.append('        <th>#</th>')
    html_parts.append('        <th>File Path</th>')
    html_parts.append('        <th>Type</th>')
    html_parts.append('        <th>Lines</th>')
    html_parts.append('        <th>Words</th>')
    html_parts.append('        <th>Size (KB)</th>')
    html_parts.append('      </tr>')
    html_parts.append('    </thead>')
    html_parts.append('    <tbody>')

    for i, f in enumerate(files, 1):
        ext_clean = (
            f["extension"].replace(".", "").upper()
            if f["extension"] else "TEXT"
        )
        size_kb = f["bytes"] / 1024.0
        html_parts.append('      <tr>')
        html_parts.append(f'        <td>{i}</td>')
```

```
        html_parts.append(
            f'        <td><strong>{html.escape(f["rel_path"])}</strong></td>'
        )
        html_parts.append(f'        <td>{ext_clean}</td>')
        html_parts.append(f'        <td>{f["lines"]:,}</td>')
        html_parts.append(f'        <td>{f["words"]:,}</td>')
        html_parts.append(f'        <td>{size_kb:.1f}</td>')
        html_parts.append('      </tr>')

    html_parts.append('    </tbody>')
    html_parts.append('  </table>')
    html_parts.append('</div>')

    # 3. File Cards
    for f in files:
        html_parts.append(render_file_card_html(f))

    html_parts.append('</body>')
    html_parts.append('</html>')

    return "\n".join(html_parts)

def convert_html_to_pdf(html_content, output_pdf_path):
    """Renders HTML directly to PDF using Google Chrome headless print."""
    tmp_html = output_pdf_path.with_suffix(".tmp.html")
    with open(tmp_html, "w", encoding="utf-8") as f:
        f.write(html_content)

    browser_bin = shutil.which("google-chrome") or shutil.which("chromium")
    if not browser_bin:
        raise RuntimeError("No headless Chrome browser found in PATH.")

    cmd = [
        browser_bin,
        "--headless",
        "--disable-gpu",
        "--no-sandbox",
        "--hide-scrollbars",
        f"--print-to-pdf={output_pdf_path}",
        str(tmp_html)
    ]

    t0 = time.time()
    res = subprocess.run(
            cmd, stdout=subprocess.PIPE, stderr=subprocess.PIPE
        )
    t1 = time.time()

    if tmp_html.exists():
        tmp_html.unlink()

    if res.returncode != 0:
        err = res.stderr.decode('utf-8', errors='ignore')
        raise RuntimeError(
            f"Chrome PDF generation failed (code {res.returncode}): {err}"
        )

    pdf_size_kb = output_pdf_path.stat().st_size / 1024.0
    return t1 - t0, pdf_size_kb

def unite_pdfs(input_pdfs, output_pdf_path):
    """Assembles multiple PDF chapter pieces into a unified Master PDF."""
    t0 = time.time()
    if shutil.which("pdfunite"):
        cmd = (
            ["pdfunite"] + [str(p) for p in input_pdfs] +
            [str(output_pdf_path)]
        )
        res = subprocess.run(
            cmd, stdout=subprocess.PIPE, stderr=subprocess.PIPE
        )
        if res.returncode == 0:
            t1 = time.time()
            return t1 - t0, output_pdf_path.stat().st_size / 1024.0

    if shutil.which("gs"):
        cmd = [
            "gs", "-dBATCH", "-dNOPAUSE", "-q",
            "-sDEVICE=pdfwrite",
            f"-sOutputFile={output_pdf_path}"
        ] + [str(p) for p in input_pdfs]
        res = subprocess.run(
            cmd, stdout=subprocess.PIPE, stderr=subprocess.PIPE
```

```
        )
        if res.returncode == 0:
            t1 = time.time()
            return t1 - t0, output_pdf_path.stat().st_size / 1024.0

    raise RuntimeError("Neither pdfunite nor gs was able to unite PDF volumes.")

# ============================================================================
# BLOCK 4: CLOSING BLOCK
# ( Orchestration, Multi-Chapter Execution & Ingestion Manifest )
# ============================================================================

def main():
    parser = argparse.ArgumentParser(
        description="Export OmniCode repository into NotebookLM Chapter PDFs."
    )
    parser.add_argument(
        "--output-dir",
        default=str(OUTPUT_DIR),
        help="Target directory for generated PDF files."
    )
    parser.add_argument(
        "--chapter",
        default=None,
        help="Optional single chapter slug or ID to generate."
    )
    parser.add_argument(
        "--no-master",
        action="store_true",
        help="Skip assembling the complete unified Master PDF."
    )

    args = parser.parse_args()
    target_dir = Path(args.output_dir).resolve()
    target_dir.mkdir(parents=True, exist_ok=True)

    print("=" * 78)
    print("OMNICODE NOTEBOOKLM CHAPTER EXPORT PIPELINE (19 CANONICAL CHAPTERS)")
    print(f"Timestamp: {datetime.now().strftime('%Y-%m-%d %H:%M:%S')}")
    print(f"Target Directory: {target_dir}")
    print("=" * 78)

    print("\n[1/4] Discovering repository files across all tracks...")
    all_files = discover_repository_files()

    total_files = len(all_files)
    total_lines = sum(f["lines"] for f in all_files)
    total_words = sum(f["words"] for f in all_files)
    total_mb = sum(f["bytes"] for f in all_files) / (1024 * 1024)

    print(f"  • Total Cataloged Files: {total_files}")
    print(f"  • Total Source Lines:   {total_lines:,}")
    print(f"  • Total Word Count:     {total_words:,} words")
    print(f"  • Total Raw Volume:     {total_mb:.2f} MB")

    # Map files by chapter slug
    files_by_slug = {}
    for f in all_files:
        files_by_slug.setdefault(f["chapter_slug"], []).append(f)

    # Filter chapters if user requested a specific one
    active_chapters = CHAPTER_DEFINITIONS
    if args.chapter:
        query = args.chapter.lower()
        active_chapters = [
            c for c in CHAPTER_DEFINITIONS
            if query in c["slug"].lower() or query in c["id"].lower()
        ]
        if not active_chapters:
            print(f"[-] Error: No chapter matched query '{args.chapter}'.")
            sys.exit(1)

    print(f"\n[2/4] Rendering {len(active_chapters)} discrete Chapter PDFs...")
    generation_manifest = []
    generated_chapter_pdfs = []

    for idx, c in enumerate(active_chapters, 1):
        c_id = c["id"]
        c_slug = c["slug"]
        c_file = c["filename"]
        c_title = c["title"]
        c_sub = c["subtitle"]
        out_pdf = target_dir / c_file
```

```
        c_files = files_by_slug.get(c_slug, [])
        if not c_files:
            continue

        words = sum(f["words"] for f in c_files)
        lines = sum(f["lines"] for f in c_files)

        print(f"\n--- [{idx:02d}/{len(active_chapters):02d}] {c_file} ---")
        print(f"  • Files: {len(c_files)} | Lines: {lines:,} "
              f"| Words: {words:,}")

        html_doc = build_chapter_html(c, c_files)
        duration, size_kb = convert_html_to_pdf(html_doc, out_pdf)
        generated_chapter_pdfs.append(out_pdf)

        size_mb = size_kb / 1024.0
        print(
            f"  • Rendered in {duration:.2f}s | "
            f"Output Size: {size_kb:.1f} KB ({size_mb:.2f} MB)"
        )

        generation_manifest.append({
            "chapter_id": c_id,
            "slug": c_slug,
            "filename": c_file,
            "path": str(out_pdf),
            "title": c_title,
            "subtitle": c_sub,
            "prompt": c["prompt"],
            "file_count": len(c_files),
            "line_count": lines,
            "word_count": words,
            "size_kb": size_kb,
            "render_seconds": round(duration, 2),
        })

    # Optional Master Compilation from Chapter pieces
    if not args.no_master and not args.chapter and generated_chapter_pdfs:
        print("\n--- Assembling Unified Master PDF (All Chapters Combined) ---")
        master_pdf = target_dir / "OmniCode_Complete_Repository_Master.pdf"
        try:
            u_sec, u_size = unite_pdfs(generated_chapter_pdfs, master_pdf)
            print(
                f"  • United {len(generated_chapter_pdfs)} chapters in "
                f"{u_sec:.2f}s | Size: {u_size/1024.0:.2f} MB"
            )
            generation_manifest.insert(0, {
                "chapter_id": "MASTER",
                "slug": "Complete_Repository_Master",
                "filename": "OmniCode_Complete_Repository_Master.pdf",
                "path": str(master_pdf),
                "title": "Complete Repository Master Edition",
                "subtitle": (
                    "Unified Epistemic Corpus: All 19 Canonical Chapters"
                ),
                "prompt": "Synthesize full architecture across all tracks.",
                "file_count": total_files,
                "line_count": total_lines,
                "word_count": total_words,
                "size_kb": u_size,
                "render_seconds": round(u_sec, 2),
            })
        except Exception as e:
            print(f"  [!] Master assembly warning: {e}")

    print("\n[3/4] Writing Ingestion Manifests for Google NotebookLM...")
    manifest_md = target_dir / "NOTEBOOKLM_INGESTION_MANIFEST.md"
    manifest_json = target_dir / "notebooklm_manifest.json"

    with open(manifest_json, "w", encoding="utf-8") as f:
        json.dump(generation_manifest, f, indent=2)

    with open(manifest_md, "w", encoding="utf-8") as f:
        f.write("# OmniCode: Google NotebookLM Chapter Ingestion Manifest\n\n")
        gen_str = datetime.now().strftime('%Y-%m-%d %H:%M:%S')
        f.write(f"**Generated:** {gen_str}  \n")
        f.write(f"**Repository:** `{REPO_ROOT}`  \n")
        f.write(
            f"**Total Cataloged Files:** {total_files} | "
            f"**Lines:** {total_lines:,} | **Words:** {total_words:,}  \n\n"
        )

```

```
        f.write("## Scripture Witnesses & Invariants\n")
        f.write("- **Exodus 31:18**: *\"written with the finger of God\"*\n")
        f.write(
            "- **Proverbs 24:27**: *\"Prepare thy work without, and make "
            "it fit for thyself in the field; and afterwards build thine "
            "house.\"*\n"
        )
        f.write(
            "- **Proverbs 22:28**: *\"Remove not the ancient landmark, "
            "which thy fathers have set.\"*\n\n"
        )

        f.write("## Chapter Curriculum Map for AI Model Training\n\n")
        f.write(
            "| Ch | PDF Filename | Files | Lines | Words | Size | Prompt |\n"
        )
        f.write(
            "|---|---|---|---|---|---|---|\n"
        )
        for m in generation_manifest:
            size_str = f"{m['size_kb']/1024.0:.2f} MB"
            f.write(
                f"| **{m['chapter_id']}** | `{m['filename']}` | "
                f"{m['file_count']} | {m['line_count']:,} | "
                f"{m['word_count']:,} | {size_str} | {m['prompt']} |\n"
            )

        f.write("\n## How to Ingest into Google NotebookLM\n\n")
        f.write(
            "1. Open **[NotebookLM](https://notebooklm.google.com)** "
            "with your Google AI account.\n"
        )
        f.write(
            "2. Create a new notebook named "
            "**`OmniCode Operating System & Language`**.\n"
        )
        f.write(
            "3. **Modular Chapter Ingestion (Recommended):** Upload the "
            "individual Chapter PDFs (`OmniCode_Ch01_*.pdf` through "
            "`OmniCode_Ch19_*.pdf`). Each chapter is bounded (10-35 pages), "
            "enabling high-resolution grounding and precise citation without "
            "needle-in-a-haystack token dilution.\n"
        )
        f.write(
            "4. **Unified Master Upload:** Alternatively, upload "
            "`OmniCode_Complete_Repository_Master.pdf` for cross-cutting "
            "repository-wide queries.\n"
        )

    print(f"  • Markdown Manifest: {manifest_md}")
    print(f"  • JSON Manifest:     {manifest_json}")

    print("\n[4/4] Chapter Pipeline Completed Successfully!")
    print("=" * 78)

if __name__ == "__main__":
    main()
```