

---

# Sub-query and Nested query

# Subqueries

---

- ◆ Some SQL statements can have a SELECT embedded within them.
- ◆ A subselect can be used in WHERE and HAVING clauses of an outer SELECT, where it is called a *subquery* or *nested query*.
- ◆ Subselects may also appear in INSERT, UPDATE, and DELETE statements.

## **Example : Subquery with Equality**

---

**List staff who work in branch at ‘163 Main St’.**

```
SELECT staffNo, fName, lName, position  
FROM Staff  
WHERE branchNo =  
    (SELECT branchNo  
        FROM Branch  
        WHERE street = ‘163 Main St’);
```

## Example : Subquery with Equality

---

- ◆ Inner SELECT finds branch number for branch at '163 Main St' ('B003').
- ◆ Outer SELECT then retrieves details of all staff who work at this branch.
- ◆ Outer SELECT then becomes:

```
SELECT staffNo, fName, lName, position  
FROM Staff  
WHERE branchNo = 'B003';
```

## Example : Subquery with Equality

---

staffNo	fName	lName	position
SG37	Ann	Beech	Assistant
SG14	David	Ford	Supervisor
SG5	Susan	Brand	Manager

## Example : Subquery with Aggregate

---

List all staff whose salary is greater than the average salary, and show by how much.

```
SELECT staffNo, fName, lName, position,  
       salary – (SELECT AVG(salary) FROM Staff) As SalDiff  
FROM Staff  
WHERE salary >  
       (SELECT AVG(salary)  
        FROM Staff);
```

## Example : Subquery with Aggregate

---

- ◆ Cannot write 'WHERE salary > AVG(salary)'
- ◆ Instead, use subquery to find average salary (17000), and then use outer SELECT to find those staff with salary greater than this:

```
SELECT staffNo, fName, lName, position,  
       salary – 17000 As salDiff  
FROM Staff  
WHERE salary > 17000;
```

## Example : Subquery with Aggregate

---

staffNo	fName	lName	position	salDiff
SL21	John	White	Manager	13000.00
SG14	David	Ford	Supervisor	1000.00
SG5	Susan	Brand	Manager	7000.00



# Subquery Rules

---

- ◆ **ORDER BY** clause may not be used in a subquery (although it may be used in outermost **SELECT**).
- ◆ Subquery **SELECT** list must consist of a single column name or expression, except for subqueries that use **EXISTS**.
- ◆ By default, column names refer to table name in **FROM** clause of subquery. Can refer to a table in **FROM** clause of outer query using an *alias*.

# Subquery Rules

---

- ◆ When subquery is an operand in a comparison, subquery must appear on right-hand side.

The SQL below is invalid:

```
SELECT staffNo, fName, lName, position,  
       salary – (SELECT AVG(salary) FROM Staff) As SalDiff  
FROM Staff  
WHERE    (SELECT AVG(salary) FROM Staff) < salary ;
```

## **Example : Nested subquery: use of IN**

---

**List properties handled by staff at ‘163 Main St’.**

```
SELECT propertyNo, street, city, postcode, type, rooms, rent  
FROM PropertyForRent  
WHERE staffNo IN  
    (SELECT staffNo  
        FROM Staff  
        WHERE branchNo =  
            (SELECT branchNo  
                FROM Branch  
                WHERE street = ‘163 Main St’));
```

## Example : Nested subquery: use of IN

---

propertyNo	street	city	postcode	type	rooms	rent
PG16	5 Novar Dr	Glasgow	G12 9AX	Flat	4	450
PG36	2 Manor Rd	Glasgow	G32 4QX	Flat	3	375
PG21	18 Dale Rd	Glasgow	G12	House	5	600

## ANY and ALL

---

- ◆ ANY and ALL may be used with subqueries that produce a single column of numbers.
- ◆ With ALL, condition will only be true if it is satisfied by *all* values produced by subquery.
- ◆ With ANY, condition will be true if it is satisfied by *any* values produced by subquery.
- ◆ If subquery is empty, ALL returns true, ANY returns false.
- ◆ SOME may be used in place of ANY.

## **Example : Use of ANY**

---

**Find staff whose salary is larger than salary of at least one member of staff at branch B003.**

```
SELECT staffNo, fName, lName, position, salary  
FROM Staff  
WHERE salary > ANY  
      (SELECT salary  
        FROM Staff  
        WHERE branchNo = 'B003');
```

## Example : Use of ANY/SOME

---

- ◆ Inner query produces set {12000, 18000, 24000} and outer query selects those staff whose salaries are greater than any of the values in this set.

staffNo	fName	lName	position	salary
SL21	John	White	Manager	30000.00
SG14	David	Ford	Supervisor	18000.00
SG5	Susan	Brand	Manager	24000.00

## Example : Use of ALL

---

**Find staff whose salary is larger than salary of every member of staff at branch B003.**

```
SELECT staffNo, fName, lName, position, salary  
FROM Staff  
WHERE salary > ALL  
      (SELECT salary  
        FROM Staff  
        WHERE branchNo = 'B003');
```



## Example : Use of ALL

---

staffNo	fName	lName	position	salary
SL21	John	White	Manager	30000.00