

Data Mining:

Concepts and Techniques


(3rd ed.)

— Chapter 10 —

Jiawei Han, Micheline Kamber, and Jian Pei
University of Illinois at Urbana-Champaign &
Simon Fraser University

©2011 Han, Kamber & Pei. All rights reserved.

Chapter 10. Cluster Analysis: Basic Concepts and Methods

- Cluster Analysis: Basic Concepts 
- Partitioning Methods
- Hierarchical Methods
- Density-Based Methods
- Evaluation of Clustering
- Summary

What is Cluster Analysis?

- Cluster: A collection of data objects
 - similar (or related) to one another within the same group
 - dissimilar (or unrelated) to the objects in other groups
- Cluster analysis (or *clustering*, *data segmentation*, ...)
 - Finding similarities between data according to the characteristics found in the data and grouping similar data objects into clusters
- **Unsupervised learning**: no predefined classes (i.e., *learning by observations* vs. learning by examples: supervised)
- Typical applications
 - As a **stand-alone tool** to get insight into data distribution
 - As a **preprocessing step** for other algorithms

Clustering for Data Understanding and Applications

- Biology: taxonomy of living things: kingdom, phylum, class, order, family, genus and species
- Information retrieval: document clustering
- Land use: Identification of areas of similar land use in an earth observation database
- Marketing: Help marketers discover distinct groups in their customer bases, and then use this knowledge to develop targeted marketing programs
- City-planning: Identifying groups of houses according to their house type, value, and geographical location
- Earth-quake studies: Observed earth quake epicenters should be clustered along continent faults
- Climate: understanding earth climate, find patterns of atmospheric and ocean
- Economic Science: market research

Clustering as a Preprocessing Tool (Utility)

- Summarization:
 - Preprocessing for regression, PCA, classification, and association analysis
- Compression:
 - Image processing: vector quantization
- Finding K-nearest Neighbors
 - Localizing search to one or a small number of clusters
- Outlier detection
 - Outliers are often viewed as those “far away” from any cluster

Quality: What Is Good Clustering?

- A good clustering method will produce high quality clusters
 - high intra-class similarity: **cohesive** within clusters
 - low inter-class similarity: **distinctive** between clusters
- The quality of a clustering method depends on
 - the similarity measure used by the method
 - its implementation, and
 - Its ability to discover some or all of the hidden patterns

Measure the Quality of Clustering

- Dissimilarity/Similarity metric
 - Similarity is expressed in terms of a distance function, typically metric: $d(i, j)$
 - The definitions of distance functions are usually rather different for interval-scaled, boolean, categorical, ordinal ratio, and vector variables
 - Weights should be associated with different variables based on applications and data semantics
- Quality of clustering:
 - There is usually a separate “quality” function that measures the “goodness” of a cluster.
 - It is hard to define “similar enough” or “good enough”
 - The answer is typically highly subjective

Considerations for Cluster Analysis

- Partitioning criteria
 - Single level vs. hierarchical partitioning (often, multi-level hierarchical partitioning is desirable)
- Separation of clusters
 - Exclusive (e.g., one customer belongs to only one region) vs. non-exclusive (e.g., one document may belong to more than one class)
- Similarity measure
 - Distance-based (e.g., Euclidian, road network, vector) vs. connectivity-based (e.g., density or contiguity)
- Clustering space
 - Full space (often when low dimensional) vs. subspaces (often in high-dimensional clustering)


Requirements and Challenges

- Scalability
 - Clustering all the data instead of only on samples
- Ability to deal with different types of attributes
 - Numerical, binary, categorical, ordinal, linked, and mixture of these
- Constraint-based clustering
 - User may give inputs on constraints
 - Use domain knowledge to determine input parameters
- Interpretability and usability
- Others
 - Discovery of clusters with arbitrary shape
 - Ability to deal with noisy data
 - Incremental clustering and insensitivity to input order
 - High dimensionality

Major Clustering Approaches (I)

- Partitioning approach:
 - Construct various partitions and then evaluate them by some criterion, e.g., minimizing the sum of square errors
 - Typical methods: k-means, k-medoids, CLARANS
- Hierarchical approach:
 - Create a hierarchical decomposition of the set of data (or objects) using some criterion
 - Typical methods: Diana, Agnes, BIRCH, CAMELEON
- Density-based approach:
 - Based on connectivity and density functions
 - Typical methods: DBSACN, OPTICS, DenClue
- Grid-based approach:
 - based on a multiple-level granularity structure
 - Typical methods: STING, WaveCluster, CLIQUE

Chapter 10. Cluster Analysis: Basic Concepts and Methods

- Cluster Analysis: Basic Concepts
- Partitioning Methods 
- Hierarchical Methods
- Density-Based Methods
- Evaluation of Clustering
- Summary

Partitioning Algorithms: Basic Concept

- Partitioning method: Partitioning a database ***D*** of ***n*** objects into a set of ***k*** clusters, such that the sum of squared distances is minimized (where c_i is the centroid or medoid of cluster C_i)


$$E = \sum_{i=1}^k \sum_{p \in C_i} (p - c_i)^2$$

- Given k , find a partition of k clusters that optimizes the chosen partitioning criterion
 - Global optimal: exhaustively enumerate all partitions
 - Heuristic methods: *k-means* and *k-medoids* algorithms
 - *k-means* (MacQueen'67, Lloyd'57/'82): Each cluster is represented by the center of the cluster
 - *k-medoids* or PAM (Partition Around Medoids) (Kaufman & Rousseeuw'87): Each cluster is represented by one of the objects in the cluster

The *K-Means* Clustering Method

- Given k , the *k-means* algorithm is implemented in four steps:
 - Partition objects into k nonempty subsets
 - Compute seed points as the centroids of the clusters of the current partitioning (the centroid is the center, i.e., *mean point*, of the cluster)
 - Assign each object to the cluster with the nearest seed point
 - Go back to Step 2, stop when the assignment does not change

An Example of *K-Means* Clustering




- Partition objects into k nonempty subsets
- Repeat
 - Compute centroid (i.e., mean point) for each partition
 - Assign each object to the cluster of its nearest centroid
- Until no change

Comments on the *K-Means* Method

- Strength: *Efficient*. $O(nkt)$, where n is # objects, k is # clusters, and t is # iterations. Normally, $k, t \ll n$.
 - Comparing: PAM: $O(k(n-k)^2)$, CLARA: $O(ks^2 + k(n-k))$
- Comment: Often terminates at a *local optimal*.
- Weakness
 - Applicable only to objects in a continuous n -dimensional space
 - Using the k -modes method for categorical data
 - In comparison, k -medoids can be applied to a wide range of data
 - Need to specify k , the *number* of clusters, in advance (there are ways to automatically determine the best k (see Hastie et al., 2009))
 - Sensitive to noisy data and *outliers*
 - Not suitable to discover clusters with *non-convex shapes*

What Is the Problem of the K-Means Method?


- The k-means algorithm is sensitive to outliers !
 - Since an object with an extremely large value may substantially distort the distribution of the data
- K-Medoids: Instead of taking the **mean** value of the object in a cluster as a reference point, **medoids** can be used, which is the **most centrally located** object in a cluster




The K-Medoid Clustering Method

- *K-Medoids* Clustering: Find *representative* objects (medoids) in clusters
 - *PAM* (Partitioning Around Medoids, Kaufmann & Rousseeuw 1987)
 - Starts from an initial set of medoids.
 - Iteratively replaces one of the medoids by one of the non-medoids if it improves the total distance (sum of squared errors) of the resulting clustering.
 - *PAM* works effectively for small data sets, but does not scale well for large data sets (due to the computational complexity)
- Computational Complexity: PAM: $O(k(n-k)^2)$

PAM: A Typical K-Medoids Algorithm




Chapter 10. Cluster Analysis: Basic Concepts and Methods

- Cluster Analysis: Basic Concepts
- Partitioning Methods
- Hierarchical Methods 
- Density-Based Methods
- Evaluation of Clustering
- Summary




Hierarchical Clustering

- Use distance matrix as clustering criteria. This method does not require the number of clusters k as an input, but needs a termination condition



AGNES (Agglomerative Nesting)


- Introduced in Kaufmann and Rousseeuw (1990)
- Implemented in statistical packages, e.g., Splus
- Use the **single-link** method and the dissimilarity matrix
- Merge nodes that have the least dissimilarity
- Go on in a non-descending fashion
- Eventually all nodes belong to the same cluster



Dendrogram: Shows How Clusters are Merged


Decompose data objects into a several levels of nested partitioning (tree of clusters), called a dendrogram

A clustering of the data objects is obtained by cutting the dendrogram at the desired level, then each connected component forms a cluster





DIANA (Divisive Analysis)

- Introduced in Kaufmann and Rousseeuw (1990)
- Implemented in statistical analysis packages, e.g., Splus
- Inverse order of AGNES
- Eventually each node forms a cluster on its own



Distance between Clusters




- Minimum Distance(Single link): Smallest distance between an element in one cluster and an element in the other, i.e., $\text{dist}(K_i, K_j) = \min(t_{ip}, t_{jq})$
- Maximum Distance(Complete link): Largest distance between an element in one cluster and an element in the other, i.e., $\text{dist}(K_i, K_j) = \max(t_{ip}, t_{jq})$
- Average: avg distance between an element in one cluster and an element in the other, i.e., $\text{dist}(K_i, K_j) = \text{avg}(t_{ip}, t_{jq})$
- Centroid: distance between the centroids of two clusters, i.e., $\text{dist}(K_i, K_j) = \text{dist}(C_i, C_j)$
- Medoid: distance between the medoids of two clusters, i.e., $\text{dist}(K_i, K_j) = \text{dist}(M_i, M_j)$
 - Medoid: a chosen, centrally located object in the cluster

Extensions to Hierarchical Clustering

- Major weakness of agglomerative clustering methods
 - Can never undo what was done previously
 - Do not scale well: time complexity of at least $O(n^2)$, where n is the number of total objects
- Integration of hierarchical & distance-based clustering
 - BIRCH (1996): uses CF-tree and incrementally adjusts the quality of sub-clusters
 - CHAMELEON (1999): hierarchical clustering using dynamic modeling

Chapter 10. Cluster Analysis: Basic Concepts and Methods

- Cluster Analysis: Basic Concepts
- Partitioning Methods
- Hierarchical Methods
- Density-Based Methods 
- Evaluation of Clustering
- Summary


Density-Based Clustering Methods

- Clustering based on density (local cluster criterion), such as density-connected points
- Major features:
 - Discover clusters of arbitrary shape
 - Handle noise
 - One scan
 - Need density parameters as termination condition
- Several interesting studies:
 - DBSCAN: Ester, et al. (KDD'96)
 - OPTICS: Ankerst, et al (SIGMOD'99).
 - DENCLUE: Hinneburg & D. Keim (KDD'98)
 - CLIQUE: Agrawal, et al. (SIGMOD'98) (more grid-based)

Density-Based Clustering: Basic Concepts

- Two parameters:
 - **Eps**: Maximum radius of the neighborhood
 - **MinPts**: Minimum number of points in an Eps-neighborhood of that point
- $N_{Eps}(p)$: $\{q \text{ belongs to } D \mid \text{dist}(p,q) \leq Eps\}$
- **Directly density-reachable**: A point p is directly density-reachable from a point q w.r.t. Eps , $MinPts$ if
 - p belongs to $N_{Eps}(q)$
 - core point condition:

$$|N_{Eps}(q)| \geq MinPts$$




MinPts = 5

Eps = 1 cm

Density-Based Clustering: Basic Concepts


Density-Based Spatial Clustering of Applications with Noise (DBSCAN)



Density-Reachable and Density-Connected


- Density-reachable:

- A point p is **density-reachable** from a point q w.r.t. Eps , $MinPts$ if there is a chain of points p_1, \dots, p_n , $p_1 = q$, $p_n = p$ such that p_{i+1} is directly density-reachable from p_i




- Density-connected

- A point p is **density-connected** to a point q w.r.t. Eps , $MinPts$ if there is a point O such that both, p and q are density-reachable from O w.r.t. Eps and $MinPts$



DBSCAN: Density-Based Spatial Clustering of Applications with Noise

- Relies on a *density-based* notion of cluster: A *cluster* is defined as a maximal set of density-connected points
- Discovers clusters of arbitrary shape in spatial databases with noise



DBSCAN: The Algorithm

- Arbitrary select a point p
- Retrieve all points density-reachable from p w.r.t. Eps and $MinPts$
 - If p is a core point, a cluster is formed
 - If p is a border point, no points are density-reachable from p and DBSCAN visits the next point of the database
- Continue the process until all of the points have been processed

DBSCAN: Sensitive to Parameters

Figure 8. DBScan results for DS1 with MinPts at 4 and Eps at (a) 0.5 and (b) 0.4.






Figure 9. DBScan results for DS2 with MinPts at 4 and Eps at (a) 5.0, (b) 3.5, and (c) 3.0.





Chapter 10. Cluster Analysis: Basic Concepts and Methods

- Cluster Analysis: Basic Concepts
- Partitioning Methods
- Hierarchical Methods
- Density-Based Methods
- Evaluation of Clustering 
- Summary

Determine the Number of Clusters

- Empirical method
 - # of clusters $\approx \sqrt{n/2}$ for a dataset of n points
- Elbow method
 - Use the turning point in the curve of sum of within cluster variance w.r.t the # of clusters
- We now define the following:
- **Distortion:** It is calculated as the average of the squared distances from the cluster centers of the respective clusters. Typically, the Euclidean distance metric is used.
- **Inertia:** It is the sum of squared distances of samples to their closest cluster center.



Determine the Number of Clusters

- Cross validation method
 - Divide a given data set into m parts
 - Use $m - 1$ parts to obtain a clustering model
 - Use the remaining part to test the quality of the clustering
 - E.g., For each point in the test set, find the closest centroid, and use the sum of squared distance between all points in the test set and the closest centroids to measure how well the model fits the test set.
 - For any $k > 0$, repeat it m times, compare the overall quality measure w.r.t. different k 's, and find # of clusters that fits the data the best

Measuring Clustering Quality

- Two methods: extrinsic vs. intrinsic
- Extrinsic: supervised, i.e., the ground truth is available
 - Compare a clustering against the ground truth using certain clustering quality measure
 - Ex. BCubed precision and recall metrics
- Intrinsic: unsupervised, i.e., the ground truth is unavailable
 - Evaluate the goodness of a clustering by considering how well the clusters are separated, and how compact the clusters are
 - Ex. Silhouette coefficient

Measuring Clustering Quality: Extrinsic Methods

- Clustering quality measure: $Q(C, C_g)$, for a clustering C given the ground truth C_g .
- Q is good if it satisfies the following 4 essential criteria
 - **Cluster homogeneity**: the more pure the clusters in a clustered space, the better the clustering algm is.
 - **Cluster completeness**: if any two objects belong to the same category according to ground truth, then they should be assigned to the same cluster.
 - **Rag bag**: putting a heterogeneous object into a pure cluster should be penalized more than putting it into a *rag bag* (i.e., “miscellaneous” or “other” category)
 - **Small cluster preservation**: splitting a small category into pieces is more harmful than splitting a large category into pieces.

Measuring Clustering Quality: Intrinsic Methods

- **The silhouette coefficient** is such a measure. For a data set, D , of n objects, suppose D is partitioned into k clusters, C_1, \dots, C_k . For each object $o \in D$, we calculate $a(o)$ as the average distance between o and all other objects in the cluster to which o belongs. Similarly, $b(o)$ is the minimum average distance from o to all clusters to which o does not belong. Formally, suppose $o \in C_i$ ($1 \leq i \leq k$); then

$$a(o) = \frac{\sum_{o' \in C_i, o' \neq o} \text{dist}(o, o')}{|C_i| - 1}$$

and


$$b(o) = \min_{C_j: 1 \leq j \leq k, j \neq i} \left\{ \frac{\sum_{o' \in C_j} \text{dist}(o, o')}{|C_j|} \right\}.$$

The **silhouette coefficient** of o is then defined as

$$s(o) = \frac{b(o) - a(o)}{\max\{a(o), b(o)\}}.$$

- The value of the silhouette coefficient is between -1 and 1 . The value of $a(o)$ reflects the compactness of the cluster to which o belongs. The smaller the value, the more compact the cluster. The value of $b(o)$ captures the degree to which o is separated from other clusters. The larger $b(o)$ is, the more separated o is from other clusters. Therefore, when the silhouette coefficient value of o approaches 1 , the cluster containing o is compact and o is far away from other clusters, which is the preferable case.

Chapter 10. Cluster Analysis: Basic Concepts and Methods

- Cluster Analysis: Basic Concepts
- Partitioning Methods
- Hierarchical Methods
- Density-Based Methods
- Grid-Based Methods
- Evaluation of Clustering
- Summary 

Summary

- **Cluster analysis** groups objects based on their **similarity** and has wide applications
- Measure of similarity can be computed for **various types of data**
- Clustering algorithms can be **categorized** into partitioning methods, hierarchical methods, density-based methods, grid-based methods, and model-based methods
- **K-means** and **K-medoids** algorithms are popular partitioning-based clustering algorithms
- **DBSCAN**, **OPTICS**, and **DENCLU** are interesting density-based algorithms
- **STING** and **CLIQUE** are grid-based methods, where CLIQUE is also a subspace clustering algorithm
- Quality of clustering results can be evaluated in various ways

References (1)

- R. Agrawal, J. Gehrke, D. Gunopulos, and P. Raghavan. Automatic subspace clustering of high dimensional data for data mining applications. SIGMOD'98
- M. R. Anderberg. Cluster Analysis for Applications. Academic Press, 1973.
- M. Ankerst, M. Breunig, H.-P. Kriegel, and J. Sander. Optics: Ordering points to identify the clustering structure, SIGMOD'99.
- Beil F., Ester M., Xu X.: "Frequent Term-Based Text Clustering", KDD'02
- M. M. Breunig, H.-P. Kriegel, R. Ng, J. Sander. LOF: Identifying Density-Based Local Outliers. SIGMOD 2000.
- M. Ester, H.-P. Kriegel, J. Sander, and X. Xu. A density-based algorithm for discovering clusters in large spatial databases. KDD'96.
- M. Ester, H.-P. Kriegel, and X. Xu. Knowledge discovery in large spatial databases: Focusing techniques for efficient class identification. SSD'95.
- D. Fisher. Knowledge acquisition via incremental conceptual clustering. Machine Learning, 2:139-172, 1987.
- D. Gibson, J. Kleinberg, and P. Raghavan. Clustering categorical data: An approach based on dynamic systems. VLDB'98.
- V. Ganti, J. Gehrke, R. Ramakrishan. CACTUS Clustering Categorical Data Using Summaries. KDD'99.