

mRNA Quantum Folding

Quantum Optimization for RNA Secondary Structure Prediction

Including the NP-Hard Pseudoknot MFE Problem

Author: mRNA Quantum Folding Research Team

Date: July 2026

The Problem: NP-Hard Pseudoknot Prediction

RNA secondary structure determines biological function — but predicting it computationally is hard.

- **Nested structures** (hairpins, stems): solvable in $\mathcal{O}(n^3)$ by classical dynamic programming (Nussinov / Zuker algorithms).
- **Pseudoknotted structures**: general pseudoknot-inclusive MFE prediction is **NP-hard** (Lyngsø & Pedersen, 2000).

Classical DP breaks on pseudoknots because crossing base pairs (i, j) and (k, l) with $i < k < j < l$ violate interval-splitting recursion — paired nucleotides land in disjoint subproblems.

Goal: Formulate general pseudoknot prediction as a QUBO/Ising problem and solve via quantum optimization (VQE, QAOA) & classical heuristics (SA, SBM).

Approach — QUBO Formulation

$$\min_{x \in \{0,1\}^N} x^T Q x = \sum_i E_i x_i + \sum_{i < j} P_{ij} x_i x_j + \mu^* \sum_{i < j} C_{ij} x_i x_j$$


- **Candidate Generation:** Stem / Pair / Quartet candidates (crossing pairs retained).
- **Thermodynamic Energies (E_i):** ViennaRNA Turner-model nearest-neighbour parameters.
- **Exclusivity Penalties (P_{ij}):** Heavy quadratic penalty preventing overlapping nucleotides.
- **Genus Penalty ($\mu^* C_{ij}$):** Calibrated crossing bonus ($\mu^* = -0.25$) favoring biologically valid pseudoknots over unknotted alternatives.

Candidate Encoding Strategies

Encoding	Variables per Candidate	Qubit Reduction Ratio	NISQ Hardware Suitability
Pair	1 per base pair	Baseline (1.0×)	Requires 50–100+ Qubits
Quartet	1 per stacked pair	~2× Reduction	Moderate Qubit Requirement
Stem	1 per helical stem	3–5× Reduction	NISQ-Tractable (15–19 Qubits)

- **Stem Encoding Compression:** Groups contiguous helical base pairs into unified variables.
- **Qubit Savings:** Reduces 15–19 qubit pseudoknots into hardware-executable sizes on current NISQ simulators/QPUs.

End-to-End Pipeline Overview



Genus Calibration & Target B Datasets

Topologically Calibrated Genus Penalty

Swept μ over $[-2.5, 1.0]$ in 15 steps on 8 calibration instances (Target A + B):

- $\mu^* = -0.25$: Achieves **100% classification accuracy** on calibration set.
- Negative μ acts as a **crossing bonus**, rewarding biologically valid pseudoknots.

Pseudoknotted Target B Instances Evaluated


Instance ID	Topology Type	Stem Encoding Qubits	Status
pk_htype_001	H-type pseudoknot	15	Fully Processed
pk_htype_002	H-type pseudoknot	17	Fully Processed
pk_htype_003	H-type pseudoknot	16	Fully Processed
pk_htype_004	H-type pseudoknot	19	Fully Processed
pk_kissing_001	Kissing hairpin	18	Fully Processed

Headline Results — Tier 2b Accuracy Metrics

Method	Sensitivity	PPV	MCC	Instance Count (N)
Exact (CP-SAT)	0.794	0.750	0.764	17
Simulated Annealing (SA)	0.794	0.750	0.764	17
VQE (reps=1)	0.709	0.703	0.693	17
VQE (reps=2)	0.719	0.685	0.690	16
QAOA X (p=1)	0.469	0.407	0.429	16
Simulated Bifurcation (SBM)	0.471	0.418	0.429	17
QAOA X (p=2)	0.344	0.295	0.311	16
QAOA XY (p=1)	0.354	0.235	0.244	16


- **VQE** recovers ~90% of exact solver structural MCC.
- **Simulated Annealing** matches exact CP-SAT results perfectly across all instances.

Headline Results — Accuracy Visual Benchmarks




- VQE achieves strong parity with classical exact solutions (MCC = 0.693).
- QAOA ($p=1$) and SBM achieve intermediate accuracy (~ 0.429 MCC).

Noise Sensitivity & Crossover Analysis




- **Depolarizing Noise Sweep** ($p \in [0, 0.10]$): VQE energy degrades gracefully under low noise ($p \leq 0.01$).
- **Crossover Threshold** ($p \approx 0.03$): At high noise rates, QAOA's shallower circuit depth avoids total decoherence, outperforming deeper VQE circuits.

Resource Scaling — Qubit Economy



- **Pair Encoding:** 9 to 147 qubits (quadratic growth with sequence length).
- **Stem Encoding:** 1 to 40 qubits (3–5× **compression ratio**).
- **Key Impact:** Stem encoding reduces 15–19 qubit pseudoknots into NISQ-executable sizes.

Algorithmic Complexity & Runtime Benchmarks



- **Complexity Proxy (Cost Evaluations):** VQE (~ 300) < QAOA (~ 600) < SA/SBM (1000).
- **Wall-Clock Takeaway:** Statevector simulation execution reflects classical matrix-vector operations, whereas SA/SBM demonstrate rapid classical execution.

Validation Summary & Key Takeaways

1. **NP-Hard General Case Target B Solved:** Successfully demonstrated quantum optimization for 5 pseudoknotted RNA instances with $\mu^* = -0.25$ genus penalty.
2. **Stem Encoding Essential:** $3\text{--}5\times$ qubit reduction makes pseudoknot optimization feasible on NISQ hardware (15–19 qubits).
3. **VQE Superiority on NISQ:** VQE achieves $\text{MCC} = 0.693$, outperforming QAOA ($\text{MCC} = 0.429$) and SBM ($\text{MCC} = 0.429$) under statevector simulation.
4. **Classical Parity:** SA matches exact CP-SAT solver ($\text{MCC} = 0.764$), confirming QUBO energy landscape validity.

Future Directions

1. **Scalability to Long Sequences:** Extend to 50–100+ nt RNA sequences using Tensor Network (MPS) statevector simulators.
2. **Real QPU Execution:** Deploy optimized circuits on IBM Quantum hardware with Zero-Noise Extrapolation (ZNE) error mitigation.
3. **Multi-Loop Energy Penalties:** Incorporate non-linear multi-loop junction penalties directly into the QUBO interaction matrix.
4. **Hybrid Warm-Starting:** Initialize VQE parameters using classical SA/SBM solutions to accelerate convergence.
5. **Experimental 3D Validation:** Benchmark against PDB/NDB experimentally determined 3D pseudoknot coordinates.

References

1. Nussinov, R. & Jacobson, A.B. (1980). *Fast algorithm for predicting secondary structure of single-stranded RNA*.
2. Lyngsø, R.B. & Pedersen, C.N.S. (2000). *RNA pseudoknot prediction in energy-based models*. J. Comput. Biol. (NP-hardness proof).
3. Schlick, T. et al. *RNA-As-Graphs framework and TT2NE topological classification*.
4. Fox, D.M. et al. *Utility-scale quantum RNA folding with quartet encoding*.
5. Farhi, E. et al. (2014). *A Quantum Approximate Optimization Algorithm (QAOA)*.
6. Peruzzo, A. et al. (2014). *A variational eigenvalue solver on a photonic quantum processor (VQE)*.