



SIRC-1 CPU Reference Manual

Featuring the SIRCIS Instruction Set

Technical Specifications

Architecture:	16-bit RISC Load/Store
Address Bus:	24-bit
Data Bus:	16-bit
Instruction Size:	32-bit (fixed)
Registers:	16 x 16-bit registers
Execution:	6-stage pipeline

Version 1.0

Copyright Silicon Integrated Research Corporation (SIRC) 1989

January 17, 2026

About This Manual

This reference manual provides comprehensive documentation for the SIRC-1 CPU architecture and the SIRCIS (SIRC Instruction Set) instruction set. It is intended for:

- Assembly language programmers
- Compiler and toolchain developers
- Hardware designers and implementers
- System software developers

Document Conventions

Throughout this manual, the following conventions are used:

- Register names appear in typewriter font: `r1`, `ph`, `sr`
- Hexadecimal values are prefixed with `0x`: `0x1A`
- Immediate values are prefixed with `#`: `#123`
- Instruction mnemonics appear in bold typewriter font: **ADDI**
- Addressing modes use parentheses for indirection: `(#4, a)`

Contents

I	Architecture Overview	1
1	Introduction	3
1.1	Overview	3
1.2	Design Philosophy	3
1.2.1	RISC Principles	3
1.2.2	Design Goals	3
1.2.3	Applications	4
1.3	Key Features	4
1.3.1	Architecture Characteristics	4
1.3.2	Execution Model	4
1.3.3	Coprocessors	5
1.3.4	Privilege Levels	5
1.4	Memory Organization	5
1.4.1	Address Space	5
1.4.2	Memory Map	6
1.4.3	Alignment	6
1.5	Document Organization	6
2	Register Model	7
2.1	Overview	7
2.2	General Purpose Registers	7
2.2.1	Register Set	7
2.2.2	Usage Conventions	8
2.3	Address Register Pairs	8
2.3.1	Overview	8
2.3.2	Link Register (l)	8
2.3.3	Address Register (a)	8
2.3.4	Stack Pointer (s)	9
2.3.5	Program Counter (p)	9
2.4	Status Register	9
2.5	Privilege Restrictions	10
2.5.1	High Address Register Restrictions	10
2.5.2	Bypassing Restrictions	10
2.6	Register Addressing	10
2.7	Usage Examples	11

2.7.1	Basic Register Operations	11
2.7.2	Address Register Usage	11
2.7.3	Subroutine Call	12
3	Status Register	13
3.1	Overview	13
3.2	Status Register Layout	13
3.3	Condition Flags (Non-Privileged)	13
3.3.1	Zero Flag (Z) – Bit 0	13
3.3.2	Negative Flag (N) – Bit 1	14
3.3.3	Carry Flag (C) – Bit 2	14
3.3.4	Overflow Flag (V) – Bit 3	14
3.3.5	Reserved Flags – Bits 4–7	14
3.4	Control Flags (Privileged)	14
3.4.1	Protected Mode (P) – Bit 8	14
3.4.2	Interrupt Mask Bits (I1, I2, I3) – Bits 9–11	15
3.4.3	Waiting for Interrupt (W) – Bit 12	15
3.4.4	CPU Halted (H) – Bit 13	15
3.4.5	Trap on Address Overflow (A) – Bit 14	15
3.4.6	Trace Mode (T) – Bit 15	16
3.5	Status Register Updates	16
3.5.1	Automatic Updates	16
3.5.2	Manual Updates	16
3.6	Reading the Status Register	17
3.7	Exception Handling Effects	17
3.8	Usage Examples	17
3.8.1	Conditional Execution	17
3.8.2	Testing Bits	17
3.8.3	Enabling Protected Mode	18
3.8.4	Saving and Restoring Status	18
II	Instruction Set Architecture	19
4	Instruction Formats	21
4.1	Overview	21
4.2	Format Overview	21
4.3	Common Fields	21
4.4	Implied Format	22
4.4.1	Structure	22
4.4.2	Examples	22
4.4.3	Assembly Syntax	22
4.5	Immediate Format	22
4.5.1	Structure	22
4.5.2	Examples	23
4.5.3	Assembly Syntax	23
4.6	Short Immediate Format (with Shift)	23
4.6.1	Structure	23

4.6.2	Shift Types	24
4.6.3	Examples	24
4.7	Register Format	24
4.7.1	Structure	24
4.7.2	Register Operand Semantics	25
4.7.3	Examples	25
4.8	Opcode Encoding Patterns	25
4.8.1	ALU Instructions	25
4.8.2	Test vs. Save	26
4.9	Instruction Fetch and Alignment	26
4.9.1	Fetch Process	26
4.9.2	Alignment Requirements	26
4.10	Format Selection Guidelines	26
5	Addressing Modes	27
5.1	Overview	27
5.2	Immediate Addressing	27
5.2.1	Description	27
5.2.2	Syntax	27
5.2.3	Effective Value	28
5.2.4	Usage	28
5.2.5	Example	28
5.3	Register Direct Addressing	28
5.3.1	Description	28
5.3.2	Syntax	28
5.3.3	Effective Value	28
5.3.4	Usage	29
5.3.5	Example	29
5.4	Indirect Immediate Addressing	29
5.4.1	Description	29
5.4.2	Syntax	29
5.4.3	Effective Address	29
5.4.4	Usage	29
5.4.5	Example	30
5.5	Indirect Register Addressing	30
5.5.1	Description	30
5.5.2	Syntax	30
5.5.3	Effective Address	30
5.5.4	Usage	30
5.5.5	Example	30
5.6	Post-Increment Addressing	31
5.6.1	Description	31
5.6.2	Syntax	31
5.6.3	Operation Sequence	31
5.6.4	Usage	31
5.6.5	Example	31
5.7	Pre-Decrement Addressing	31
5.7.1	Description	31

5.7.2	Syntax	32
5.7.3	Operation Sequence	32
5.7.4	Usage	32
5.7.5	Example	32
5.8	Implied Addressing	32
5.8.1	Description	32
5.8.2	Syntax	33
5.8.3	Usage	33
5.8.4	Example	33
5.9	Short Immediate Addressing	33
5.9.1	Description	33
5.9.2	Syntax	33
5.9.3	Effective Value	33
5.9.4	Usage	33
5.9.5	Example	34
5.10	Address Register Selection	34
5.11	Addressing Mode Examples	34
5.11.1	Structure Access	34
5.11.2	Array Iteration	34
5.11.3	Stack Frame	35
5.11.4	Position-Independent Code	35
5.12	Addressing Mode Restrictions	35
5.12.1	Privilege Mode Restrictions	35
5.12.2	Alignment	35
6	Shift Operations	37
6.1	Overview	37
6.2	Shift Types	37
6.2.1	Shift Type Encoding	37
6.3	Shift Type Details	37
6.3.1	Logical Shift Left (LSL)	37
6.3.2	Logical Shift Right (LSR)	38
6.3.3	Arithmetic Shift Left (ASL)	38
6.3.4	Arithmetic Shift Right (ASR)	39
6.3.5	Rotate Left (ROL)	39
6.3.6	Rotate Right (ROR)	40
6.4	Shift Operands	40
6.4.1	Mode 0: Shift the Value	40
6.4.2	Mode 1: Shift by Register Count	41
6.5	Shift Count	41
6.6	Status Flag Effects	41
6.6.1	Carry Flag	41
6.6.2	Zero Flag	41
6.6.3	Negative Flag	41
6.6.4	Overflow Flag	42
6.7	Common Use Cases	42
6.7.1	Multiplication by Constants	42
6.7.2	Division by Powers of 2	42

6.7.3	Bit Field Extraction	42
6.7.4	Scaled Array Indexing	42
6.7.5	Bit Manipulation	43
6.8	Multi-Word Shifts	43
6.8.1	32-bit Left Shift	43
6.8.2	32-bit Right Shift (Unsigned)	43
6.8.3	32-bit Right Shift (Signed)	43
6.9	Performance Considerations	43
6.10	Limitations	44
7	Condition Codes	45
7.1	Overview	45
7.2	Condition Code Encoding	45
7.3	Condition Code Categories	46
7.3.1	Simple Conditions	46
7.3.2	Unsigned Comparisons	46
7.3.3	Signed Comparisons	46
7.3.4	Special Conditions	47
7.4	Assembly Syntax	47
7.5	Usage with Compare Instructions	47
7.5.1	Unsigned Comparison	47
7.5.2	Signed Comparison	47
7.5.3	Equality Testing	48
7.6	Condition Code Truth Tables	48
7.6.1	After Unsigned Comparison (CMPR rA, rB)	48
7.6.2	After Signed Comparison (CMPR rA, rB)	48
7.7	Advanced Usage	49
7.7.1	Conditional Assignment	49
7.7.2	Conditional Increment	49
7.7.3	Conditional Function Call	49
7.7.4	Loop Construction	49
7.8	Condition Code Selection Guide	50
7.9	Performance Considerations	50
7.10	Common Pitfalls	50
III	SIRCIS Instruction Reference	53
8	Instruction Summary	55
8.1	Overview	55
8.2	Complete Instruction List	56
8.3	Instruction Grouping Patterns	57
8.3.1	Opcode Organization	57
8.3.2	Save vs. Test Variants	57
8.4	Meta-Instructions	57
8.5	Instruction Timing	57
8.6	Next Chapters	58

9	ALU Instructions	59
9.1	Overview	59
9.2	ALU Instruction Families	59
9.2.1	Arithmetic Instructions	59
9.2.2	Logical Instructions	59
9.2.3	Data Movement	59
9.2.4	Test and Compare	60
9.3	Status Flag Updates	60
9.4	ADD – Addition	61
9.5	ADC – Add with Carry	62
9.6	SUB – Subtraction	63
9.7	SBC – Subtract with Carry (Borrow)	64
9.8	AND – Bitwise AND	65
9.9	ORR – Bitwise OR	66
9.10	XOR – Bitwise Exclusive OR	67
9.11	LOAD – Load Immediate / Move Register	68
9.12	CMP – Compare	69
9.13	TSA – Test AND	71
9.14	TSX – Test XOR	72
9.15	Summary	72
10	Memory Access Instructions	75
10.1	Overview	75
10.2	Effective Address Calculation	75
10.3	LOAD Instructions	76
10.4	STOR Instructions	77
10.5	Common Memory Access Patterns	77
10.5.1	Structure Field Access	77
10.5.2	Array Iteration	77
10.5.3	Stack Operations	78
11	Control Flow Instructions	79
11.1	Overview	79
11.2	Branch Instructions	80
11.3	Subroutine Call Instructions	81
11.4	Load Effective Address	81
11.5	Control Flow Patterns	82
11.5.1	If-Then-Else	82
11.5.2	While Loop	82
11.5.3	Switch/Jump Table	82
12	Coprocessor Instructions	83
12.1	Overview	83
12.2	Exception Unit (Coprocessor 1)	84
12.2.1	Common Operations	84

13 Meta-Instructions	85
13.1 Overview	85
13.2 NOOP – No Operation	85
13.3 RETS – Return from Subroutine	85
13.4 WAIT – Wait for Interrupt	85
13.5 RETE – Return from Exception	86
A Opcode Map	87
A.1 Complete Opcode Reference	87
A.2 Opcode Patterns	89
A.2.1 Format Identification	89
A.2.2 Save vs. Test	89
A.2.3 Memory Operations Decoding	89
A.3 Undocumented Instructions	89
A.4 Quick Lookup Table	90
B Instruction Timing	91
B.1 Overview	91
B.2 Six-Stage Pipeline	91
B.3 Timing Characteristics	92
B.4 Conditional Execution	92
B.5 Program Timing Examples	92
B.5.1 Simple Loop	92
B.5.2 Function Call Overhead	93
B.5.3 Conditional Block	93
B.6 Performance Considerations	93
B.6.1 No Pipeline Stalls	93
B.6.2 Memory Access	93
B.6.3 Optimization Guidelines	94
B.7 Theoretical Performance	94
B.8 Comparison to Other CPUs	95
C Undocumented Instructions	97
C.1 Overview	97
C.2 Undocumented Opcode List	97
C.3 Likely Behavior	98
C.3.1 0x08, 0x28, 0x38 (ADD Test)	98
C.3.2 0x09, 0x29, 0x39 (ADC Test)	98
C.3.3 0x0B, 0x2B, 0x3B (SUB Test)	98
C.3.4 0x0D, 0x2D, 0x3D (SBC Test)	98
C.4 Implementation Notes	98
C.4.1 Current Simulator	98
C.4.2 Hardware Implementation	99
C.5 Why Undocumented?	99
C.6 Recommendations	99
C.6.1 For Application Developers	99
C.6.2 For Compiler Writers	99
C.6.3 For Hardware Implementers	100

C.6.4 For Researchers/Hackers	100
C.7 Future Standardization	100
C.8 Opcode Space for Expansion	100

List of Tables

1.1	SIRC-1 CPU Specifications	4
1.2	List of coprocessors	5
2.1	Register Encoding	11
3.1	Interrupt Mask Settings	15
4.1	Instruction Format Summary	21
4.2	Shift Type Encoding	24
4.3	Format Selection Examples	26
5.1	Addressing Modes Summary	27
5.2	Address Register Encoding	34
6.1	Shift Type Encoding	37
6.2	Shift Operand Modes	40
7.1	Condition Code Encoding	45
7.2	Unsigned Comparison Results	48
7.3	Signed Comparison Results	48
7.4	Condition Code Selection Guide	50
8.1	Complete SIRCIS Instruction Set	56
8.2	Meta-Instructions	57
12.1	Exception Unit Operations	84
A.1	Complete SIRCIS Opcode Map	88
A.2	Instruction Variant Quick Reference	90
B.1	Instruction Timing (All instructions)	92
B.2	Cycles Per Instruction Comparison	95
C.1	Undocumented Instruction Opcodes	97

List of Figures

2.1	Address Register Pair Formation	8
3.1	Status Register Bit Layout	13
4.1	Implied Instruction Format	22
4.2	Immediate Instruction Format	22
4.3	Short Immediate with Shift Format	23
4.4	Register Instruction Format	24
6.1	Logical Shift Left	38
6.2	Logical Shift Right	38
6.3	Arithmetic Shift Right	39
6.4	Rotate Left	39
6.5	Rotate Right	40

Part I

Architecture Overview

Chapter 1

Introduction

1.1 Overview

The SIRC-1 is a 16-bit RISC processor ideal for general purpose computing. It implements the SIRCIS (SIRC Instruction Set) instruction set architecture, which provides a comprehensive set of operations while maintaining a clean, consistent design philosophy.

1.2 Design Philosophy

1.2.1 RISC Principles

The SIRC-1 adheres to Reduced Instruction Set Computer (RISC) design principles:

- **Load/Store Architecture:** All ALU operations work exclusively on registers. Memory access is performed only through dedicated load and store instructions.
- **Fixed Instruction Length:** All instructions are exactly 32 bits (2 words) in length, simplifying instruction fetch and decode logic.
- **Simple Instruction Formats:** Only four instruction formats are supported: Implied, Immediate, Short Immediate with Shift, and Register.
- **Register-Rich:** Sixteen addressable registers provide ample workspace for computations without frequent memory access.
- **Consistent Execution Time:** All instructions execute in exactly 6 clock cycles, eliminating the need for microcode and simplifying hardware implementation.

1.2.2 Design Goals

The SIRC-1 was designed with several key goals in order of importance:

Simplicity The CPU should be simple enough to be implemented in hardware without requiring complex microcode engines or multi-level instruction decoders.

Developer Ergonomics It should have powerful instruction encodings that include conditional execution and bit shifting that can help reduce the number of instructions and branches to keep track of.

Performance While simple, the design should allow for reasonable performance through efficient instruction encoding and the potential for future enhancements like pipelining.

Memory Protection Basic privilege levels and memory segmentation provide rudimentary protection for system software.

1.2.3 Applications

The SIRC-1 is designed for ideal for general purpose computing, such as the core of a microcomputer.

It should not be used in memory constrained environments, as the fixed length instructions and lack of byte addressing can potentially mean larger program sizes.

1.3 Key Features

1.3.1 Architecture Characteristics

Feature	Specification
Data Width	16-bit
Address Bus	24-bit (16MB address space)
Instruction Size	32-bit fixed
General Purpose Registers	7 (r1–r7)
Address Register Pairs	4 (l, a, s, p)
Total Addressable Registers	16
Instruction Formats	4
Addressing Modes	8
Condition Codes	16

Table 1.1: SIRC-1 CPU Specifications

1.3.2 Execution Model

The SIRC-1 employs a six-stage execution sequence (one stage per clock):

1. **Instruction Fetch (First Word)** – Fetch bits 31–16 from memory
2. **Instruction Fetch (Second Word)** – Fetch bits 15–0 from memory
3. **Decode and Register Fetch** – Decode the instruction and read source registers
4. **Execute and Address Calculation** – Perform ALU operation or calculate effective address
5. **Memory Access** – Read from or write to memory (or NOP for register operations)
6. **Write Back** – Write results to destination register

This fixed six-stage model means that all instructions take exactly 6 clock cycles to complete, regardless of their complexity. While this may seem wasteful for simple register operations that don't require memory access, it dramatically simplifies the hardware design by eliminating the need for variable-length execution cycles or microcode.

1.3.3 Coprocessors

The SIRC-1 is made up of multiple coprocessors (also known as modules) that all share the same address/data bus. Only one coprocessor can be active at one time and are usually activated using the COP instructions (except for the "exception unit" which can be activated when physical pins are asserted on the chip). All implementations of the SIRC-1 will have the "processing unit" as coprocessor 0x0 and "exception unit" as coprocessor 0x1. Other coprocessors are optional and will vary depending on which SIRC-1 model you have. The instruction set supports up to 16 coprocessors.

ID	Name	Optional	Purpose
0x0	Processing Unit	No	Executes instructions
0x1	Exception Unit	No	Handles interrupts and exceptions
0x2	DMA Unit	Yes	Transfers large amounts of data via the bus

Table 1.2: List of coprocessors

Each coprocessor can execute 16 opcodes, the first 8 (0x0-0x7) can be called in any mode. The last 8 (0x8-0xF) can only be called in supervisor mode.

1.3.4 Privilege Levels

The SIRC-1 supports two privilege levels:

Supervisor Mode Full access to all registers and instructions. Can set the high bytes of address register pairs, access privileged status register bits, and execute privileged coprocessor operations.

Protected Mode Restricted access for user programs. Cannot write to the high bytes of address register pairs (providing memory segmentation/protection), cannot access privileged status register bits, and cannot execute privileged coprocessor instructions.

The privilege level is controlled by the Protected Mode bit in the status register.

1.4 Memory Organization

1.4.1 Address Space

The SIRC-1 provides a 24-bit address space, allowing access to 16 megabytes of memory. Addresses are formed by combining the 8-bit high byte and 16-bit low word of address register pairs:

$$\text{Address} = (\text{RegHigh}[7 : 0] \ll 16) | \text{RegLow}[15 : 0] \quad (1.1)$$

Note that the upper 8 bits of the high register (bits 15–8) are not used for addressing but are available for storage, enabling techniques like tagged pointers.

1.4.2 Memory Map

The CPU expects certain memory regions to be defined:

- **Reset Vector** (0x000000): Initial program counter after reset
- **Fault Vectors** (0x000001–0x000007): Fault vectors
- **Hardware Vectors** (0x000010–0x000050): Hardware exception vectors (offset by 0x10 due to hardware implementation)
- **User Vectors** (0x000060–0x0000FF): User exception vectors

Beyond these reserved regions, the memory layout is flexible and can be defined by system software.

1.4.3 Alignment

- All instructions must be aligned on 4-byte boundaries (word-aligned)
- Data can be accessed at any 2-byte boundary (halfword-aligned)
- Unaligned instruction fetches trigger an alignment fault exception

1.5 Document Organization

This manual is organized into three main parts:

Part I: Architecture Overview Covers the register model, status register, and overall CPU architecture.

Part II: Instruction Set Architecture Details instruction formats, addressing modes, shift operations, and condition codes.

Part III: SIRCIS Instruction Reference Provides detailed documentation for each instruction, including encoding, operation, and examples.

Appendices provide quick reference materials including complete opcode maps, timing diagrams, and notes on undocumented instructions.

Chapter 2

Register Model

2.1 Overview

The SIRC-1 CPU provides sixteen 16-bit registers that serve various purposes. These registers can be classified into three categories:

- General purpose registers (**r1–r7**)
- Address register pairs (**l, a, s, p**)
- Status register (**sr**)

All registers are 16 bits wide. However, the address registers can be used in pairs to form 24-bit addresses for memory operations.

2.2 General Purpose Registers

2.2.1 Register Set

The SIRC-1 provides seven general-purpose registers:

Register	Description
r1	General purpose register 1
r2	General purpose register 2
r3	General purpose register 3
r4	General purpose register 4
r5	General purpose register 5
r6	General purpose register 6
r7	General purpose register 7

These registers can be used freely for any purpose by the programmer. They hold 16-bit values and can be used as source or destination operands for all ALU instructions.

2.2.2 Usage Conventions

While there are no hardware-enforced conventions, typical usage patterns include:

- **r1–r4**: Temporary values and expression evaluation
- **r5–r7**: Preserved across function calls (by convention)

These are software conventions only and are not enforced by the CPU.

2.3 Address Register Pairs

2.3.1 Overview

The SIRC-1 provides four address register pairs, each consisting of a high and low 16-bit register. When used together, these pairs form 24-bit addresses by combining the low 8 bits of the high register with the full 16 bits of the low register.

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Unused								High[7:0]								Low[15:0]															
bits 31–24								bits 23–16								bits 15–0															

Figure 2.1: Address Register Pair Formation

The upper 8 bits (bits 31–24) of the high register are not used for addressing but remain available for storage, enabling techniques such as tagged pointers.

2.3.2 Link Register (l)

Component	Register
High Byte	lh (privileged)
Low Word	ll

The link register pair stores return addresses for subroutine calls. When a subroutine is called using **LJSR** or **BRSR**, the return address is automatically saved to this register pair.

Typical Use:

- Storing return addresses from subroutine calls
- Building nested subroutine call stacks

2.3.3 Address Register (a)

Component	Register
High Byte	ah (privileged)
Low Word	al

A general-purpose address register pair used for pointer operations and memory access.

Typical Use:

- Base pointer for data structures
- Array indexing
- General memory addressing

2.3.4 Stack Pointer (s)

Component	Register
High Byte	sh (privileged)
Low Word	sl

The stack pointer register pair points to the current top of the stack. Pre-decrement and post-increment addressing modes are particularly useful with this register.

Typical Use:

- Stack operations (push/pop)
- Local variable allocation
- Function parameter passing

2.3.5 Program Counter (p)

Component	Register
High Byte	ph (privileged)
Low Word	pl

The program counter register pair points to the next instruction to be executed. It is automatically incremented by 4 after each instruction fetch (since instructions are 32 bits).

Typical Use:

- Automatically updated during normal execution
- Modified by branch and jump instructions
- Used for position-independent code

2.4 Status Register

The status register (**sr**) is a special 16-bit register that contains CPU status flags and control bits. It is divided into two bytes:

- **Lower Byte (bits 7–0):** Condition flags, accessible in both supervisor and protected modes
- **Upper Byte (bits 15–8):** Control flags, accessible only in supervisor mode (privileged)

The status register is discussed in detail in Chapter 3.

2.5 Privilege Restrictions

2.5.1 High Address Register Restrictions

The high component of each address register pair (**lh**, **ah**, **sh**, **ph**) is considered privileged:

- In **supervisor mode**: Can be read from and written to freely
- In **protected mode**:
 - Reading is allowed
 - Writing triggers a privilege exception

This restriction provides a form of memory segmentation/protection. User programs running in protected mode cannot modify the segment portion of addresses, preventing them from accessing memory outside their designated segment.

2.5.2 Bypassing Restrictions

Some instructions (**LDEA**, **LJSR**) that operate on full address register pairs can write to the low register only when the second operand bit is set. This allows controlled updates to addresses within the current segment even in protected mode.

2.6 Register Addressing

Registers are addressed using 4-bit register identifiers in instruction encoding:

ID	Register	Privileged
0x0	sr	Upper byte only
0x1	r1	No
0x2	r2	No
0x3	r3	No
0x4	r4	No
0x5	r5	No
0x6	r6	No
0x7	r7	No
0x8	lh	Yes
0x9	ll	No
0xA	ah	Yes
0xB	al	No
0xC	sh	Yes
0xD	sl	No
0xE	ph	Yes
0xF	pl	No

Table 2.1: Register Encoding

2.7 Usage Examples

2.7.1 Basic Register Operations

```

1 ; Load immediate value into r1
2 ADDI r1, #0, #100
3
4 ; Copy r1 to r2
5 ADDR r2, r1, #0
6
7 ; Add r1 and r2, store in r3
8 ADDR r3, r1, r2

```

2.7.2 Address Register Usage

```

1 ; Load value from memory at address in 'a' register pair
2 LOAD r1, (#0, a)
3
4 ; Store r1 to memory at address (a + 8)
5 STOR r1, (#8, a)
6
7 ; Push r1 onto stack (pre-decrement)
8 STOR r1, -(#2, s)

```

```
9
10 ; Pop r2 from stack (post-increment)
11 LOAD r2, (#0, s)+
```

2.7.3 Subroutine Call

```
1 ; Call subroutine at address in 'a' register
2 ; Return address saved to 'l' register automatically
3 LJSR (#0, a)
4
5 ; ...subroutine code...
6
7 ; Return from subroutine
8 ; Copies 'l' register to 'p' register
9 RETS
```

Chapter 3

Status Register

3.1 Overview

The Status Register (**sr**) is a 16-bit special-purpose register that contains condition flags and control bits for the CPU. It is divided into two bytes with different privilege levels:

- **Lower Byte (bits 7–0):** Condition flags – readable and writable in both supervisor and protected modes
- **Upper Byte (bits 15–8):** Control and mode flags – accessible only in supervisor mode

3.2 Status Register Layout

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
T	A	H	W	I3	I2	I1	P					V	C	N	Z
Privileged								Non-Privileged							

Figure 3.1: Status Register Bit Layout

3.3 Condition Flags (Non-Privileged)

These flags reflect the results of ALU operations and comparisons. They can be read and written by code running in any privilege level.

3.3.1 Zero Flag (Z) – Bit 0

Set when: The result of an operation is zero

Cleared when: The result of an operation is non-zero

Tested by: Equal (==), Not Equal (!=) condition codes

3.3.2 Negative Flag (N) – Bit 1

Set when: The result of an operation is negative (bit 15 = 1) when interpreted as a signed two's complement value

Cleared when: The result is positive or zero (bit 15 = 0)

Tested by: Negative Set (<0), Negative Clear (>=0), and signed comparison condition codes

3.3.3 Carry Flag (C) – Bit 2

Set when: An addition produces a carry out of bit 15, or a subtraction produces a borrow

Cleared when: No carry/borrow occurs

Tested by: Carry Set (CS), Carry Clear (CC), Unsigned Higher (>), Unsigned Lower or Same (<=) condition codes

Note: For unsigned comparisons, the carry flag acts as an unsigned overflow indicator

3.3.4 Overflow Flag (V) – Bit 3

Set when: A signed arithmetic operation produces a result that cannot be represented in 16 bits (signed overflow)

Cleared when: No signed overflow occurs

Tested by: Overflow Set (VS), Overflow Clear (VC), and signed comparison condition codes

Note: Overflow occurs when adding two positive numbers yields a negative result, or adding two negative numbers yields a positive result

3.3.5 Reserved Flags – Bits 4–7

Bits 4 through 7 of the lower byte are reserved for future use. They should not be relied upon by software.

3.4 Control Flags (Privileged)

These flags control CPU behavior and can only be modified in supervisor mode. Attempts to write these bits in protected mode will be ignored (the write affects only the lower byte).

3.4.1 Protected Mode (P) – Bit 8

When Clear (0): CPU operates in supervisor mode with full privileges

When Set (1): CPU operates in protected mode with restricted access to:

- High bytes of address register pairs (lh, ah, sh, ph)
- Upper byte of status register
- Privileged coprocessor operations (opcodes > 0x07xx)

Note: This bit provides basic memory protection by preventing user code from changing memory segments

3.4.2 Interrupt Mask Bits (I1, I2, I3) – Bits 9–11

These three bits control which interrupt priority levels are masked:

I3	I2	I1	Effect
0	0	0	All interrupts enabled
0	0	1	Low priority interrupts masked
0	1	0	Low and medium priority interrupts masked
0	1	1	Low, medium, and high priority interrupts masked
1	x	x	All interrupts masked (NMI still active)

Table 3.1: Interrupt Mask Settings

Note: Non-maskable interrupts (NMI) cannot be disabled by these bits.

3.4.3 Waiting for Interrupt (W) – Bit 12

Set when: The **WAIT** instruction is executed

Cleared when: An interrupt or exception occurs

Purpose: Indicates the CPU is in low-power wait state

Note: This bit is primarily for hardware implementation and is typically not accessed by software

3.4.4 CPU Halted (H) – Bit 13

Set when: A **HALT** instruction is executed (if implemented)

Cleared when: CPU is reset

Purpose: Indicates the CPU has halted execution

Note: This feature may not be implemented in all versions

3.4.5 Trap on Address Overflow (A) – Bit 14

When Set (1): Memory address calculations that overflow or underflow will trigger an address overflow exception

When Clear (0): Address overflows wrap around silently

Purpose: Helps detect pointer errors during development

Typical Use: Enabled during debugging, disabled in production for performance

3.4.6 Trace Mode (T) – Bit 15

When Set (1): An exception is generated after every instruction

When Clear (0): Normal execution

Purpose: Allows debuggers to single-step through code

Note: Used by SIRCIT (SIRC Instruction Tracer) for debugging

Implementation: May not be fully implemented in all simulator versions

3.5 Status Register Updates

3.5.1 Automatic Updates

The condition flags (Z, N, C, V) are automatically updated by most ALU instructions, unless explicitly disabled:

- **Arithmetic Instructions (ADDI, SUBI, ADCI, SBCI):** Update all four condition flags
- **Logical Instructions (ANDI, ORRI, XORI):** Update Z and N flags; C and V are cleared
- **Compare Instructions (CMPI, CMPR):** Update all flags but do not write result to destination
- **Test Instructions (TSAI, TSAR, TSXI, TSXR):** Update Z and N flags only
- **Load Instructions (LOAD, LDEA):** Do not update condition flags
- **Shift Operations:** Can optionally update flags based on the instruction's status register update source field

3.5.2 Manual Updates

The status register can be directly manipulated like any other register:

```
1 ; Read current status register
2 ADDR r1, sr, #0
3
4 ; Set protected mode bit (only in supervisor mode)
5 ORRI sr, #0x0100
6
7 ; Clear interrupt mask
8 ANDI sr, #0xF1FF
9
10 ; Restore saved status register
11 ADDR sr, r1, #0
```

Important: When running in protected mode, writes to the status register only affect the lower byte (bits 7–0). The upper byte remains unchanged.

3.6 Reading the Status Register

In supervisor mode, reading **sr** returns the full 16-bit value. In protected mode, reading **sr** returns the lower byte in bits 7–0, with bits 15–8 masked to zero (for security).

```

1 ; In supervisor mode - gets full 16 bits
2 ADDR r1, sr, #0 ; r1 = 0xFFFF (all bits)
3
4 ; In protected mode - upper byte masked
5 ADDR r1, sr, #0 ; r1 = 0x00XX (upper byte forced to 0)

```

3.7 Exception Handling Effects

When an exception occurs:

1. The current status register is saved
2. Protected mode bit (P) is cleared (entering supervisor mode)
3. Trace mode bit (T) is cleared (disabling single-stepping in exception handler)
4. Interrupts may be masked depending on exception type

When returning from an exception with **RETE**, the saved status register is restored.

3.8 Usage Examples

3.8.1 Conditional Execution

```

1 ; Compare r1 with r2
2 CMPI r1, r2
3
4 ; Branch if equal
5 BRAN |== label_equal
6
7 ; Branch if r1 > r2 (unsigned)
8 BRAN |> label_greater
9
10 ; Branch if r1 >= r2 (signed)
11 BRAN |>= label_signed_ge

```

3.8.2 Testing Bits

```

1 ; Test if bit 5 is set in r1
2 TSAI r1, #0x0020 ; AND with 0x0020, update flags only
3
4 ; Branch if bit was set (result non-zero)
5 BRAN |!= bit_was_set

```

3.8.3 Enabling Protected Mode

```
1 ; Entering user mode (from supervisor mode)
2 ORRI sr, #0x0100 ; Set protected mode bit
3 ; Now running in protected mode
4
5 ; Attempting to write privileged register will fault
6 ; ADDI ah, #0x05 ; This would cause exception!
```

3.8.4 Saving and Restoring Status

```
1 ; Save status register
2 ADDR r7, sr, #0
3
4 ; Do some operations that change flags
5 ADDI r1, r2, r3
6 CMPI r1, #100
7
8 ; Restore original status
9 ADDR sr, r7, #0
```


Part II

Instruction Set Architecture

Chapter 4

Instruction Formats

4.1 Overview

All SIRCIS instructions are exactly 32 bits (4 bytes, or 2 words) in length. This fixed instruction size simplifies instruction fetch and decode logic, though it may result in larger code size compared to variable-length instruction sets.

The SIRC-1 supports four distinct instruction formats:

1. Implied
2. Immediate
3. Short Immediate (with Shift)
4. Register

Each format is optimized for different types of operations and addressing modes.

4.2 Format Overview

Format	Typical Use
Implied	Instructions with no operands (NOOP , WAIT)
Immediate	Operations with a 16-bit constant value
Short Immediate	Operations with an 8-bit constant and optional shift
Register	Operations on multiple registers with optional shift

Table 4.1: Instruction Format Summary

4.3 Common Fields

All instruction formats share some common fields:

Opcode (6 bits) Identifies the operation to perform. With 6 bits, up to 64 distinct operations can be encoded.

Condition Flags (4 bits) Specifies under what conditions the instruction should execute. See Chapter 7 for details.

Additional Flags (2 bits) Used in some formats to specify address register pairs (a, p, s, l) or other modifiers.

4.4 Implied Format

4.4.1 Structure

The implied format is used for instructions that don't require any operands.




Figure 4.1: Implied Instruction Format

Opcode (bits 31–26) 6-bit operation code

Reserved (bits 25–4) Must be zero

Condition (bits 3–0) 4-bit condition code

4.4.2 Examples

- **NOP** – No operation (actually encoded as `ADDI r1, #0`)
- **WAIT** – Wait for interrupt
- **HALT** – Halt processor (if implemented)

4.4.3 Assembly Syntax

```
1 NOP                ; Execute always
2 WAIT | ==          ; Wait if zero flag set
```

4.5 Immediate Format

4.5.1 Structure

The immediate format encodes a full 16-bit immediate value within the instruction.



Figure 4.2: Immediate Instruction Format

Opcode (bits 31–26) 6-bit operation code

Register (bits 25–22) 4-bit destination/source register identifier

Immediate (bits 21–6) 16-bit signed or unsigned immediate value

Address Reg (bits 5–4) 2-bit address register pair selector (for memory operations)

- 00 = l (link register)
- 01 = a (address register)
- 10 = s (stack pointer)
- 11 = p (program counter)

Condition (bits 3–0) 4-bit condition code

4.5.2 Examples

- **ADDI** r1, #1234 – Add 1234 to r1
- **LOAD** r2, (#8, a) – Load from address a+8 into r2
- **STOR** r3, (#-4, s) – Store r3 to address s-4

4.5.3 Assembly Syntax

```

1 ADDI r1, #100           ; r1 = r1 + 100
2 CMPI r2, #0x8000       ; Compare r2 with 0x8000
3 LOAD r3, (#16, a)      ; r3 = memory[a + 16]
4 STOR r4, (#-2, s)      ; memory[s - 2] = r4

```

4.6 Short Immediate Format (with Shift)

4.6.1 Structure

The short immediate format sacrifices immediate value width to include shift information, allowing for more powerful single-instruction operations.




Figure 4.3: Short Immediate with Shift Format

Opcode (bits 31–26) 6-bit operation code

Register (bits 25–22) 4-bit destination/source register

Immediate (bits 21–14) 8-bit signed or unsigned immediate value

Shift Operand (bit 13) What to shift (0 = immediate value, 1 = register value)

Shift Type (bits 12–10) Type of shift operation (LSL, LSR, ASL, ASR, ROL, ROR)

Shift Count (bits 9–6) Amount to shift (0–15)

Address Reg (bits 5–4) 2-bit address register pair selector

Condition (bits 3–0) 4-bit condition code

4.6.2 Shift Types

Code	Type	Mnemonic
000	None (no shift)	–
001	Logical Shift Left	LSL
010	Logical Shift Right	LSR
011	Arithmetic Shift Left	ASL
100	Arithmetic Shift Right	ASR
101	Rotate Left	ROL
110	Rotate Right	ROR
111	Reserved	–

Table 4.2: Shift Type Encoding

4.6.3 Examples

```

1 ; Add 2 to r1, but shift 2 left by 3 first (r1 = r1 + 16)
2 ADDI r1, #2, LSL #3
3
4 ; Load value, shifted
5 LOAD r2, #4, ASL #2 ; r2 = r2 + (4 << 2)
6
7 ; Store with shifted offset
8 STOR r3, (#10, a), LSR #1

```

4.7 Register Format

4.7.1 Structure

The register format allows operations on up to three registers with optional shift.




Figure 4.4: Register Instruction Format

Opcode (bits 31–26) 6-bit operation code

Register 1 (bits 25–22) Destination register (or first source for some instructions)

Register 2 (bits 21–18) Source register

Register 3 (bits 17–14) Second source register (if needed)

Shift Operand (bit 13) 0 = shift register 3 value, 1 = shift by register 3's value

Shift Type (bits 12–10) Type of shift

Shift Count (bits 9–6) Shift amount (or register containing shift amount)

Address Reg (bits 5–4) Address register pair selector (for memory operations)

Condition (bits 3–0) Condition code

4.7.2 Register Operand Semantics

For most three-operand instructions:

- R1 = Destination
- R2 = First source operand
- R3 = Second source operand (optional)

If R3 is zero or not specified, many instructions use R1 as both destination and first source operand:

```
1 ADDR r1, r2, r3 ; r1 = r2 + r3
2 ADDR r1, r2      ; r1 = r1 + r2 (R3 implicitly = R1)
```

4.7.3 Examples

```
1 ; Add two registers
2 ADDR r1, r2, r3      ; r1 = r2 + r3
3
4 ; Add with shift
5 ADDR r1, r2, r3, LSL #2 ; r1 = r2 + (r3 << 2)
6
7 ; Load using register offset
8 LOAD r1, (r2, a)      ; r1 = memory[a + r2]
9
10 ; Store with post-increment
11 STOR r1, (r2, s)+     ; memory[s + r2] = r1; s = s + r2
```

4.8 Opcode Encoding Patterns

The SIRCIS instruction set uses systematic opcode patterns to simplify decoding:

4.8.1 ALU Instructions

- **0x0__**: Immediate operand, save result
- **0x1__**: Memory operations
- **0x2__**: Short immediate with shift, save result
- **0x3__**: Register operand, save result

4.8.2 Test vs. Save

Many ALU operations have both a "save result" and "test only" variant:

- **+0x0**: Save result to destination
- **+0x8**: Test only (update flags, don't save result)

For example:

- **0x04**: **ANDI** – AND immediate, save result
- **0x0C**: **TSAI** – Test AND immediate (don't save result)

4.9 Instruction Fetch and Alignment

4.9.1 Fetch Process

Since instructions are 32 bits and the data bus is 16 bits wide, each instruction requires two fetch cycles:

1. Fetch high word (bits 31–16) from address in PC
2. Increment PC by 2
3. Fetch low word (bits 15–0) from address in PC
4. Increment PC by 2

4.9.2 Alignment Requirements

Instructions must be aligned on 4-byte boundaries. The low word of the program counter (p1) must always be even, and instructions must not span across 4-byte boundaries.

Attempting to fetch an instruction from an unaligned address (odd address or not on 4-byte boundary) will trigger an alignment fault exception.

4.10 Format Selection Guidelines

When writing assembly code, the assembler automatically selects the appropriate format based on operands:

Assembly	Format Used	Notes
ADDI r1, #1000	Immediate	Full 16-bit immediate
ADDI r1, #10, LSL #2	Short Immediate	8-bit immediate + shift
ADDR r1, r2, r3	Register	Three register operands
NOOP	Implied	No operands

Table 4.3: Format Selection Examples

The choice of format affects instruction encoding but is generally transparent to the programmer, as the assembler handles the details.

Chapter 5

Addressing Modes

5.1 Overview

The SIRC-1 CPU supports eight addressing modes that specify how operands are accessed. These modes determine whether an operand is an immediate value, register contents, or data in memory at a computed address.

Mode	Description
Immediate	Operand is a constant value encoded in the instruction
Register Direct	Operand is the contents of a specified register
Indirect Immediate	Memory address = address register + immediate offset
Indirect Register	Memory address = address register + register offset
Post-Increment	Indirect register, then increment address register
Pre-Decrement	Decrement address register, then use as indirect
Implied	No operand specified (encoded in instruction)
Short Immediate	8-bit constant with optional shift

Table 5.1: Addressing Modes Summary

5.2 Immediate Addressing

5.2.1 Description

The operand is a constant value encoded directly in the instruction. For full immediate mode, this can be a 16-bit signed or unsigned value. For short immediate mode, it is an 8-bit value that can optionally be shifted.

5.2.2 Syntax

```
1 ADDI r1, #100           ; 16-bit immediate
2 ADDI r2, #-50           ; Signed immediate
3 ADDI r3, #10, LSL #2    ; 8-bit immediate with shift
```

5.2.3 Effective Value

Immediate: The value is used directly

Short Immediate: Value = (immediate \ll shift_count) or (immediate \gg shift_count)

5.2.4 Usage

- Loading constant values
- Arithmetic with known values
- Bit manipulation with masks

5.2.5 Example

```
1 ; Load constant
2 ADDI r1, #0, #1234      ; r1 = 1234
3
4 ; Add constant
5 ADDI r2, #100          ; r2 = r2 + 100
6
7 ; Create large constant via shift
8 ADDI r3, #1, LSL #12   ; r3 = r3 + 4096
```

5.3 Register Direct Addressing

5.3.1 Description

The operand is the contents of a specified register. This is the most common mode for ALU operations in a load/store architecture.

5.3.2 Syntax

```
1 ADDR r1, r2, r3        ; r1 = r2 + r3
2 ADDR r4, r5             ; r4 = r4 + r5
```

5.3.3 Effective Value

The 16-bit value currently stored in the specified register.

5.3.4 Usage

- All ALU operations between registers
- Register-to-register data movement
- Testing register values

5.3.5 Example

```

1 ; Add registers
2 ADDR r1, r2, r3      ; r1 = r2 + r3
3
4 ; Copy register
5 ADDR r4, r5, #0      ; r4 = r5 + 0 = r5
6
7 ; Compare registers
8 CMPR r1, r2          ; Sets flags based on r1 - r2

```

5.4 Indirect Immediate Addressing

5.4.1 Description

The effective address is computed by adding a 16-bit signed immediate offset to an address register pair. The operand is then loaded from or stored to this computed address.

5.4.2 Syntax

```

1 LOAD r1, (#8, a)      ; Load from address (a + 8)
2 STOR r2, (#-4, s)     ; Store to address (s - 4)
3 LDEA p, (#100, p)     ; Jump relative (pc = pc + 100)

```

5.4.3 Effective Address

$$EA = \text{AddressRegister} + \text{Offset} \quad (5.1)$$

The address register can be: **l** (link), **a** (address), **s** (stack), or **p** (program counter).

5.4.4 Usage

- Accessing structure fields (fixed offset from base)
- Array element access (if index is constant)
- Stack frame access (local variables)
- Position-independent code (PC-relative addressing)

5.4.5 Example

```
1 ; Access structure fields
2 LOAD r1, (#0, a)      ; r1 = struct.field0
3 LOAD r2, (#2, a)      ; r2 = struct.field1
4 LOAD r3, (#4, a)      ; r3 = struct.field2
5
6 ; Stack frame access
7 STOR r4, (#-2, s)     ; Save local variable
8 LOAD r5, (#-4, s)     ; Load local variable
9
10 ; PC-relative branch
11 BRAN (#10, p)        ; Jump forward 10 bytes
```

5.5 Indirect Register Addressing

5.5.1 Description

Similar to indirect immediate, but the offset is taken from a register instead of being encoded as an immediate value. This enables runtime-computed offsets.

5.5.2 Syntax

```
1 LOAD r1, (r2, a)      ; Load from address (a + r2)
2 STOR r3, (r4, s)      ; Store to address (s + r4)
```

5.5.3 Effective Address

$$EA = \text{AddressRegister} + \text{IndexRegister} \quad (5.2)$$

5.5.4 Usage

- Array indexing with variable index
- Table lookups
- Dynamic offset calculations

5.5.5 Example

```
1 ; Array access: array[i]
2 ; Assume 'a' points to array base, r2 contains index * 2
3 LOAD r1, (r2, a)      ; r1 = array[i]
4
5 ; Write to array
6 STOR r3, (r2, a)      ; array[i] = r3
7
8 ; Lookup table
9 LOAD r4, (r5, a)      ; r4 = table[r5]
```

5.6 Post-Increment Addressing

5.6.1 Description

The effective address is computed using indirect register addressing, then the address register pair is incremented by the index register value after the memory operation.

This mode is particularly useful for iterating through arrays or implementing stack operations.

5.6.2 Syntax

```
1 LOAD r1, (r2, a)+      ; Load from (a + r2), then a = a + r2
2 STOR r3, (#2, s)+      ; Store to (s + 2), then s = s + 2
```

5.6.3 Operation Sequence

1. Compute $EA = \text{AddressRegister} + \text{Offset}$
2. Perform memory operation (load or store)
3. $\text{AddressRegister} = \text{AddressRegister} + \text{Offset}$

5.6.4 Usage

- Stack pop operations
- Forward array traversal
- Buffer reading

5.6.5 Example

```
1 ; Pop from stack
2 ; Assume s points to current top of stack
3 LOAD r1, (#0, s)+      ; r1 = *s; s = s + 2
4
5 ; Iterate through array
6 ; Process 10 elements
7 ADDI r2, #0, #10      ; Counter
8 loop:
9   LOAD r3, (#0, a)+    ; Load element, advance pointer
10  ; ... process r3 ...
11  SUBI r2, #1          ; Decrement counter
12  BRAN |!= loop        ; Continue if not zero
```

5.7 Pre-Decrement Addressing

5.7.1 Description

The address register pair is decremented by the offset value before computing the effective address for the memory operation.

This mode is the complement of post-increment and is useful for stack push operations.

5.7.2 Syntax

```
1 STOR r1, -(r2, s)      ; s = s - r2, then store to (s + r2)
2 STOR r3, -(#2, s)     ; s = s - 2, then store to (s + 2)
```

5.7.3 Operation Sequence

1. AddressRegister = AddressRegister - Offset
2. Compute EA = AddressRegister + Offset
3. Perform memory operation (typically store)

Note: After decrement, we still add the offset to compute EA. This may seem counterintuitive, but it allows the stack to grow downward properly.

5.7.4 Usage

- Stack push operations
- Backward array traversal
- Buffer writing

5.7.5 Example

```
1 ; Push onto stack
2 STOR r1, -(#2, s)      ; s = s - 2; *s = r1
3
4 ; Save multiple registers
5 STOR r1, -(#2, s)
6 STOR r2, -(#2, s)
7 STOR r3, -(#2, s)
8 ; Stack now has r3, r2, r1 (r3 at top)
9
10 ; Later, restore them
11 LOAD r3, (#0, s)+
12 LOAD r2, (#0, s)+
13 LOAD r1, (#0, s)+
```

5.8 Implied Addressing

5.8.1 Description

No operand is specified; the operation is fully defined by the opcode. This mode is used for control flow instructions and other operations that don't need explicit operands.

5.8.2 Syntax

```

1 NOOP                ; No operation
2 WAIT                ; Wait for interrupt
3 RETS                ; Return from subroutine
4 RETE                ; Return from exception

```

5.8.3 Usage

- Meta-instructions that assemble to specific operations
- Control flow that operates on implied registers
- System operations

5.8.4 Example

```

1 ; Function call and return
2 LJSR (#0, a)          ; Call function, address in 'a'
3 ; ... function code ...
4 RETS                ; Return (copies 'l' to 'p')
5
6 ; Wait for interrupt
7 WAIT                ; CPU enters low-power state
8
9 ; No operation (delay)
10 NOOP               ; Do nothing for 6 cycles

```

5.9 Short Immediate Addressing

5.9.1 Description

Similar to immediate addressing, but limited to 8-bit values. The value can be shifted before use, effectively allowing larger values to be encoded efficiently if they are multiples of powers of 2.

5.9.2 Syntax

```

1 ADDI r1, #10, LSL #2 ; r1 = r1 + (10 << 2) = r1 + 40
2 SUBI r2, #1, LSL #8  ; r2 = r2 - 256

```

5.9.3 Effective Value

The 8-bit immediate is shifted according to the shift type and count, then used as the operand.

5.9.4 Usage

- Efficiently encoding common constants (powers of 2, multiples)
- Bit field manipulation
- Scaled arithmetic

5.9.5 Example

```

1 ; Set bit 12
2 ORRI r1, #1, LSL #12
3
4 ; Clear bit 8
5 ANDI r1, # ~(1 << 8) ; Assembler computes #0xFEFF
6
7 ; Multiply by 4 (add value * 4)
8 ADDR r1, r2, r2, LSL #2 ; r1 = r2 + (r2 << 2) = r2 * 5

```

5.10 Address Register Selection

Many addressing modes require specifying which address register pair to use. The 2-bit address register field encodes:

Bits	Symbol	Register Pair
00	l	Link Register (lh, ll)
01	a	Address Register (ah, al)
10	s	Stack Pointer (sh, sl)
11	p	Program Counter (ph, pl)

Table 5.2: Address Register Encoding

5.11 Addressing Mode Examples

5.11.1 Structure Access

```

1 ; Assume 'a' points to a struct:
2 ; struct Point {
3 ;     int16_t x; // offset 0
4 ;     int16_t y; // offset 2
5 ; }
6
7 LOAD r1, (#0, a) ; r1 = point.x
8 LOAD r2, (#2, a) ; r2 = point.y

```

5.11.2 Array Iteration

```

1 ; Iterate array of 16-bit values
2 ; Assume 'a' points to array start
3 ; r7 = counter
4 loop:
5     LOAD r1, (#0, a)+ ; Load element, advance by 2
6     ; ... process r1 ...
7     SUBI r7, #1

```



```
8  BRAN | != loop
```

5.11.3 Stack Frame

```
1  ; Function prologue - save registers
2  STOR r1, -(#2, s)
3  STOR r2, -(#2, s)
4  STOR r3, -(#2, s)
5
6  ; Access parameters (above saved regs)
7  LOAD r4, (#6, s)      ; First parameter
8  LOAD r5, (#8, s)      ; Second parameter
9
10 ; Function epilogue - restore registers
11 LOAD r3, (#0, s)+
12 LOAD r2, (#0, s)+
13 LOAD r1, (#0, s)+
14 RETS
```

5.11.4 Position-Independent Code

```
1  ; PC-relative data access
2  LOAD r1, (#data_offset, p) ; Load from PC + offset
3
4  ; PC-relative call
5  LJSR (#function_offset, p) ; Call function at PC + offset
6
7  data_offset: DW 100 ; Some data
8  function_offset: DW 200 ; Distance to function
```

5.12 Addressing Mode Restrictions

5.12.1 Privilege Mode Restrictions

In protected mode, indirect addressing modes that would write to the high byte of an address register are restricted:

- **LDEA with both registers:** Privileged in protected mode
- **LDEA with low register only:** Allowed (can't change segment)
- **Post-increment/Pre-decrement:** Can only modify low register in protected mode

5.12.2 Alignment

- Memory operations should target even addresses (16-bit aligned)
- Unaligned access behavior is undefined
- PC must always be 4-byte aligned (instruction alignment)

Chapter 6

Shift Operations

6.1 Overview

The SIRC-1 CPU supports powerful shift operations that can be applied to operands in many instructions. Shifts can multiply or divide values by powers of 2, extract bit fields, or perform bit rotations.

Shift operations are encoded within Short Immediate and Register format instructions, allowing a value to be shifted before being used in an ALU operation—all within a single instruction.

6.2 Shift Types

6.2.1 Shift Type Encoding

Code	Mnemonic	Type	Description
000	–	None	No shift performed
001	LSL	Logical Shift Left	Shift left, fill with zeros
010	LSR	Logical Shift Right	Shift right, fill with zeros
011	ASL	Arithmetic Shift Left	Same as LSL (shifts in zeros)
100	ASR	Arithmetic Shift Right	Shift right, preserving sign bit
101	ROL	Rotate Left	Rotate left through carry
110	ROR	Rotate Right	Rotate right through carry
111	–	Reserved	Reserved for future use

Table 6.1: Shift Type Encoding

6.3 Shift Type Details

6.3.1 Logical Shift Left (LSL)

Operation: Shift bits to the left, filling vacated bits with zeros.




Figure 6.1: Logical Shift Left

- Bit 15 is shifted into the carry flag
- Bit 0 receives 0
- Equivalent to multiplying by 2^n where n is the shift count

Example:

```

1 ; Multiply by 4
2 ADDI r1, #0, r2, LSL #2 ; r1 = r2 * 4
3
4 ; Set bit 10
5 ORRI r3, #1, LSL #10 ; r3 |= 0x0400

```

6.3.2 Logical Shift Right (LSR)

Operation: Shift bits to the right, filling vacated bits with zeros.




Figure 6.2: Logical Shift Right

- Bit 0 is shifted into the carry flag
- Bit 15 receives 0
- Equivalent to unsigned division by 2^n
- Use for unsigned values only

Example:

```

1 ; Divide unsigned value by 8
2 ADDI r1, #0, r2, LSR #3 ; r1 = r2 / 8 (unsigned)
3
4 ; Extract upper byte
5 ADDR r3, r4, #0, LSR #8 ; r3 = r4 >> 8

```

6.3.3 Arithmetic Shift Left (ASL)

Operation: Identical to LSL. Shift bits to the left, filling with zeros.

- Equivalent to signed multiplication by 2^n
- Can cause signed overflow if sign bit changes
- Overflow flag is set if sign bit changes during shift

Example:

```

1 ; Multiply signed value by 2
2 ADDI r1, #0, r2, ASL #1 ; r1 = r2 * 2 (signed)

```

6.3.4 Arithmetic Shift Right (ASR)

Operation: Shift bits to the right, preserving the sign bit (bit 15).




Figure 6.3: Arithmetic Shift Right

- Bit 0 is shifted into the carry flag
- Bit 15 (sign bit) is copied into bit 15 and bit 14
- Equivalent to signed division by 2^n (rounds toward negative infinity)
- Use for signed values only

Example:

```

1 ; Divide signed value by 4
2 ADDI r1, #0, r2, ASR #2 ; r1 = r2 / 4 (signed)
3
4 ; Average two signed values
5 ADDR r3, r4, r5
6 ADDR r3, r3, #0, ASR #1 ; r3 = (r4 + r5) / 2

```

6.3.5 Rotate Left (ROL)

Operation: Rotate bits to the left through the carry flag.




Figure 6.4: Rotate Left

- Bit 15 moves into the carry flag
- Previous carry flag value moves into bit 0
- No data is lost
- Useful for multi-word shifts and bit manipulation

Example:

```

1 ; Rotate r1 left by 1
2 ADDR r1, r1, #0, ROL #1
3
4 ; Multi-word left shift (32-bit value in r1:r2)
5 ADDR r2, r2, #0, LSL #1 ; Shift low word, bit 15 -> carry
6 ADDR r1, r1, #0, ROL #1 ; Shift high word, carry -> bit 0

```

6.3.6 Rotate Right (ROR)

Operation: Rotate bits to the right through the carry flag.




Figure 6.5: Rotate Right

- Bit 0 moves into the carry flag
- Previous carry flag value moves into bit 15
- No data is lost

Example:

```

1 ; Rotate r1 right by 1
2 ADDR r1, r1, #0, ROR #1
3
4 ; Check if bit 0 is set
5 ADDR r2, r1, #0, ROR #1 ; Bit 0 -> carry
6 ; Now branch on carry to test bit 0

```

6.4 Shift Operands

The Shift Operand (SO) bit determines what value is shifted:

SO Bit	Mode	Description
0	Shift Immediate/R3	The immediate value or R3 register value is shifted
1	Shift Count in Register	R3 contains the shift count; R2 is shifted by that amount

Table 6.2: Shift Operand Modes

6.4.1 Mode 0: Shift the Value

The value itself (immediate or register) is shifted before the ALU operation.

```

1 ; Add r2 * 4 to r1
2 ADDR r1, r2, r2, LSL #2 ; r1 = r2 + (r2 << 2) = r2 * 5
3 ; SO=0: r2 value is shifted
4
5 ; Load with scaled offset
6 LOAD r1, (r2, a), LSL #1 ; EA = a + (r2 << 1)
7 ; SO=0: r2 value is shifted

```

6.4.2 Mode 1: Shift by Register Count

The shift count is taken from a register, allowing variable-length shifts.

```

1 ; Variable shift
2 ; r3 contains shift amount
3 ADDR r1, r2, r3, LSL ; r1 = r2 << r3
4 ; SO=1: shift r2 by r3's value
5
6 ; Barrel shifter emulation
7 ADDR r4, r5, r6, ASR ; r4 = r5 >> r6 (arithmetic)

```

6.5 Shift Count

The shift count is a 4-bit field, allowing shifts of 0–15 positions.

- Shift count of 0 means no shift is performed
- Maximum shift count is 15
- Shift counts ≥ 16 would be meaningless for 16-bit values

6.6 Status Flag Effects

6.6.1 Carry Flag

For all shifts and rotates:

- The last bit shifted out is placed in the carry flag
- For shifts of more than 1 position, only the final bit shifted out matters
- If shift count is 0, carry flag is not modified

6.6.2 Zero Flag

Set if the result after shifting is zero.

6.6.3 Negative Flag

Set if bit 15 of the result is 1 (result is negative when interpreted as signed).

6.6.4 Overflow Flag

- For **ASL**: Set if the sign bit changes during the shift (signed overflow)
- For other shifts: Behavior is undefined; typically unchanged or cleared

6.7 Common Use Cases

6.7.1 Multiplication by Constants

```

1 ; Multiply by 2
2 ADDR r1, r2, r2, LSL #1 ; r1 = r2 * 2
3
4 ; Multiply by 3
5 ADDR r1, r2, r2, LSL #1 ; r1 = r2 + (r2 * 2) = r2 * 3
6
7 ; Multiply by 5
8 ADDR r1, r2, r2, LSL #2 ; r1 = r2 + (r2 * 4) = r2 * 5
9
10 ; Multiply by 10
11 ADDR r1, r2, r2, LSL #2 ; r1 = r2 * 5
12 ADDR r1, r1, r1, LSL #1 ; r1 = r1 * 2 = r2 * 10

```

6.7.2 Division by Powers of 2

```

1 ; Unsigned divide by 4
2 ADDR r1, r2, #0, LSR #2 ; r1 = r2 / 4 (unsigned)
3
4 ; Signed divide by 8
5 ADDR r1, r2, #0, ASR #3 ; r1 = r2 / 8 (signed)

```

6.7.3 Bit Field Extraction

```

1 ; Extract bits 8-11 from r1
2 ADDR r2, r1, #0, LSR #8 ; Shift down
3 ANDI r2, #0x0F ; Mask to 4 bits
4
5 ; Extract and sign-extend bit 7
6 ADDR r2, r1, #0, LSL #8 ; Shift bit 7 to bit 15
7 ADDR r2, r2, #0, ASR #8 ; Arithmetic shift to sign-extend

```

6.7.4 Scaled Array Indexing

```

1 ; Access array of 4-byte structures
2 ; r2 = index, 'a' = base address
3 ; Each element is 4 bytes, so multiply index by 4
4 LOAD r1, (r2, a), LSL #2 ; EA = a + (index * 4)
5
6 ; Access array of 16-bit values
7 LOAD r3, (r4, a), LSL #1 ; EA = a + (index * 2)

```


6.7.5 Bit Manipulation

```

1 ; Set bit N (where N is in r2)
2 ADDI r3, #1 ; r3 = 1
3 ADDR r3, r3, r2, LSL ; r3 = 1 << N
4 ORRR r1, r3 ; r1 |= (1 << N)
5
6 ; Clear bit N
7 ADDI r3, #1
8 ADDR r3, r3, r2, LSL ; r3 = 1 << N
9 XORI r3, #0xFFFF ; r3 = ~(1 << N)
10 ANDR r1, r3 ; r1 &= ~(1 << N)
11
12 ; Test bit N
13 ADDI r3, #1
14 ADDR r3, r3, r2, LSL ; r3 = 1 << N
15 TSAR r1, r3 ; Test r1 & (1 << N)
16 BRAN|!= bit_was_set ; Branch if bit set

```

6.8 Multi-Word Shifts

For operations on values larger than 16 bits, shifts and rotates can be combined:

6.8.1 32-bit Left Shift

```

1 ; Shift 32-bit value in r1:r2 left by 1
2 ; r1 = high word, r2 = low word
3 ADDR r2, r2, #0, LSL #1 ; Shift low, MSB -> carry
4 ADDR r1, r1, #0, ROL #1 ; Rotate high with carry

```

6.8.2 32-bit Right Shift (Unsigned)

```

1 ; Shift 32-bit value in r1:r2 right by 1 (unsigned)
2 ADDR r1, r1, #0, LSR #1 ; Shift high, LSB -> carry
3 ADDR r2, r2, #0, ROR #1 ; Rotate low with carry

```

6.8.3 32-bit Right Shift (Signed)

```

1 ; Shift 32-bit value in r1:r2 right by 1 (signed)
2 ADDR r1, r1, #0, ASR #1 ; Arithmetic shift high
3 ADDR r2, r2, #0, ROR #1 ; Rotate low with carry

```

6.9 Performance Considerations

- All shift operations complete in the same number of cycles regardless of shift count
- Shifts can be performed "for free" as part of another instruction (no extra cycles)

- Using shifts for multiplication/division by powers of 2 is much faster than using a multiply/-divide instruction (if one existed)
- Barrel shifter implementation in hardware allows any shift count in constant time

6.10 Limitations

- Maximum shift count is 15 (4-bit field)
- For shifts > 15 , multiple shift instructions must be used
- Rotates include the carry flag, so rotating by 16 does not equal original value
- Some shift types (e.g., reserved type 111) may have undefined behavior

Chapter 7

Condition Codes

7.1 Overview

Most SIRCIS instructions can be executed conditionally based on the state of the condition flags in the status register. This allows for efficient implementation of conditional logic without requiring explicit branch instructions.

The 4-bit condition code field in each instruction specifies under what conditions the instruction should execute. If the condition is not met, the instruction behaves as a **NOOP** (no operation).

7.2 Condition Code Encoding

Code	Mnemonic	Condition (when instruction executes)
0000	(none)	Always (unconditional)
0001	==	Equal ($Z = 1$)
0010	!=	Not Equal ($Z = 0$)
0011	CS	Carry Set ($C = 1$)
0100	CC	Carry Clear ($C = 0$)
0101	<0	Negative ($N = 1$)
0110	>=0	Non-Negative ($N = 0$)
0111	VS	Overflow Set ($V = 1$)
1000	VC	Overflow Clear ($V = 0$)
1001	>	Unsigned Higher ($C = 1$ AND $Z = 0$)
1010	<=	Unsigned Lower or Same ($C = 0$ OR $Z = 1$)
1011	>=	Signed Greater or Equal ($N = V$)
1100	<	Signed Less Than ($N \neq V$)
1101	»	Signed Greater Than ($Z = 0$ AND $N = V$)
1110	«	Signed Less or Equal ($Z = 1$ OR $N \neq V$)
1111	NV	Never (never executes)

Table 7.1: Condition Code Encoding

7.3 Condition Code Categories

7.3.1 Simple Conditions

These conditions test a single status flag:

Always (default) No condition code specified; instruction always executes.

== (Equal) Executes when $Z = 1$. Typically used after **CMP** to test equality.

!= (Not Equal) Executes when $Z = 0$. Typical use: test inequality.

CS (Carry Set) Executes when $C = 1$. Can indicate unsigned overflow or borrow.

CC (Carry Clear) Executes when $C = 0$. No unsigned overflow/borrow.

<0 (Negative) Executes when $N = 1$. Tests if result is negative (signed).

>=0 (Non-Negative) Executes when $N = 0$. Tests if result is positive or zero (signed).

VS (Overflow Set) Executes when $V = 1$. Signed overflow occurred.

VC (Overflow Clear) Executes when $V = 0$. No signed overflow.

7.3.2 Unsigned Comparisons

These conditions are used after comparing unsigned integers:

> (Unsigned Higher) Executes when $C = 1$ AND $Z = 0$. Tests if first operand $>$ second operand (unsigned).

<= (Unsigned Lower or Same) Executes when $C = 0$ OR $Z = 1$. Tests if first \leq second (unsigned).

Note: For unsigned comparisons:

- Use $>$ and $<=$ after **CMP**
- $>=$ (unsigned) is equivalent to **CS**
- $<$ (unsigned) is equivalent to **CC**

7.3.3 Signed Comparisons

These conditions are used after comparing signed integers:

>= (Signed Greater or Equal) Executes when $N = V$. First operand \geq second operand (signed).

< (Signed Less Than) Executes when $N \neq V$. First operand $<$ second operand (signed).

» (Signed Greater Than) Executes when $Z = 0$ AND $N = V$. First operand $>$ second operand (signed).

« (Signed Less or Equal) Executes when $Z = 1$ OR $N \neq V$. First operand \leq second operand (signed).

7.3.4 Special Conditions

Never (NV) Never executes; equivalent to **NOOP**. Can be used for instruction padding or to temporarily disable instructions during debugging.

7.4 Assembly Syntax

Condition codes are specified by appending a pipe character (|) followed by the condition mnemonic to the instruction:

```

1 ; Unconditional
2 ADDI r1, #10
3
4 ; Conditional - execute only if equal
5 ADDI |== r2, #20
6
7 ; Conditional branch
8 BRAN |!= loop_start
9
10 ; Multiple conditions
11 ADDR |> r3, r4, r5
12 STOR |<0 r6, (#0, s)

```

7.5 Usage with Compare Instructions

The most common use of condition codes is with compare (**CMP**) instructions:

7.5.1 Unsigned Comparison

```

1 ; if (r1 > r2) { r3 = r4; } (unsigned)
2 CMPR r1, r2 ; Compare r1 and r2
3 ADDR |> r3, r4, #0 ; r3 = r4 if r1 > r2 (unsigned)
4
5 ; if (r1 <= 100) { branch } (unsigned)
6 CMPI r1, #100
7 BRAN |<= target

```

7.5.2 Signed Comparison

```

1 ; if (r1 >= r2) { r3 = r4; } (signed)
2 CMPR r1, r2 ; Compare r1 and r2
3 ADDR |>= r3, r4, #0 ; r3 = r4 if r1 >= r2 (signed)
4
5 ; if (r1 < -10) { branch } (signed)
6 CMPI r1, #-10
7 BRAN |< negative_case

```

7.5.3 Equality Testing

```

1 ; if (r1 == r2) { branch }
2 CMPR r1, r2
3 BRAN|== equal_case
4
5 ; if (r1 != 0) { branch }
6 CMPI r1, #0
7 BRAN|!= non_zero_case

```

7.6 Condition Code Truth Tables

7.6.1 After Unsigned Comparison (CMPR rA, rB)

Relationship	Z	C	Condition	Code	Meaning
$rA = rB$	1	*	==	0001	Equal
$rA \neq rB$	0	*	!=	0010	Not Equal
$rA > rB$ (unsigned)	0	1	>	1001	Higher
$rA < rB$ (unsigned)	0	0	CC	0100	Lower
$rA \geq rB$ (unsigned)	*	1	CS	0011	Higher or Same
$rA \leq rB$ (unsigned)	*	*	<=	1010	Lower or Same

Table 7.2: Unsigned Comparison Results

7.6.2 After Signed Comparison (CMPR rA, rB)

Relationship	Z	N	V	Condition	Code	Meaning
$rA = rB$	1	*	*	==	0001	Equal
$rA \neq rB$	0	*	*	!=	0010	Not Equal
$rA > rB$ (signed)	0	0	0	»	1101	Greater
$rA > rB$ (signed)	0	1	1	»	1101	Greater
$rA < rB$ (signed)	*	0	1	<	1100	Less
$rA < rB$ (signed)	*	1	0	<	1100	Less
$rA \geq rB$ (signed)	*	0	0	>=	1011	Greater or Equal
$rA \geq rB$ (signed)	*	1	1	>=	1011	Greater or Equal
$rA \leq rB$ (signed)	1	*	*	«	1110	Less or Equal
$rA \leq rB$ (signed)	0	0	1	«	1110	Less or Equal
$rA \leq rB$ (signed)	0	1	0	«	1110	Less or Equal

Table 7.3: Signed Comparison Results

7.7 Advanced Usage

7.7.1 Conditional Assignment

```

1 ; max = (a > b) ? a : b (unsigned)
2 CMPR r1, r2           ; Compare a and b
3 ADDR |> r3, r1, #0    ; r3 = a if a > b
4 ADDR |<= r3, r2, #0   ; r3 = b if a <= b

```

7.7.2 Conditional Increment

```

1 ; if (condition) count++
2 CMPI r1, #0
3 ADDI |!= r2, #1       ; Increment r2 if r1 != 0

```

7.7.3 Conditional Function Call

```

1 ; if (r1 > 0) call_function()
2 CMPI r1, #0
3 LJSR |>0 (#0, a)      ; Call function if r1 > 0

```

7.7.4 Loop Construction

```

1 ; for (i = 10; i > 0; i--)
2 ADDI r1, #0, #10      ; i = 10
3 loop:
4   ; ... loop body ...
5   SUBI r1, #1          ; i--
6   BRAN |> loop         ; Continue if i > 0 (unsigned)

```

7.8 Condition Code Selection Guide

Intent	After CMP	Condition Code
If equal	CMPR a, b	==
If not equal	CMPR a, b	!=
If a > b (unsigned)	CMPR a, b	>
If a ≥ b (unsigned)	CMPR a, b	CS
If a < b (unsigned)	CMPR a, b	CC
If a ≤ b (unsigned)	CMPR a, b	<=
If a > b (signed)	CMPR a, b	»
If a ≥ b (signed)	CMPR a, b	>=
If a < b (signed)	CMPR a, b	<
If a ≤ b (signed)	CMPR a, b	«
If negative	CMPI a, #0	<0
If positive or zero	CMPI a, #0	>=0
If overflow occurred	After arithmetic	VS
If no overflow	After arithmetic	VC

Table 7.4: Condition Code Selection Guide

7.9 Performance Considerations

- Conditional instructions do not branch, avoiding pipeline flushes
- When a condition is false, the instruction still takes 6 cycles but performs no operation
- For short conditional sequences, conditional execution can be faster than branching
- For longer conditional blocks, explicit branches may be more efficient

7.10 Common Pitfalls

- **Signed vs. Unsigned:** Using unsigned conditions (>, <=) for signed values or vice versa produces incorrect results
- **Flag Clobbering:** Flags are modified by most ALU instructions. Ensure the condition flags haven't been modified between the comparison and conditional instruction:

```

1 ; WRONG - flags clobbered
2 CMPR r1, r2
3 ADDI r3, #100           ; Modifies flags!
4 BRAN|> target           ; Tests wrong flags
5
6 ; CORRECT - flags preserved
7 CMPR r1, r2
8 BRAN|> target
9 ADDI r3, #100           ; After the branch

```


- **Inverted Logic:** Remember that `CMP A, B` computes $A - B$, so condition codes test A relative to B , not B relative to A

Part III

SIRCIS Instruction Reference

Chapter 8

Instruction Summary

8.1 Overview

The SIRCIS instruction set consists of 64 possible opcodes (6-bit opcode field), of which approximately 52 are documented and assigned. The instructions are organized into logical groups:

- **ALU Instructions (0x00–0x0F, 0x20–0x2F, 0x30–0x3F):** Arithmetic, logical, and comparison operations
- **Memory Instructions (0x10–0x17):** Load and store operations
- **Control Flow (0x18–0x1F):** Branches, jumps, and address loading
- **Coprocessor (0x0F, 0x2F, 0x3F):** Coprocessor interface

8.2 Complete Instruction List

Opcode	Mnemonic	Format	Flags	Operation
0x00	ADDI	Immediate	NZCV	Add immediate
0x01	ADCI	Immediate	NZCV	Add immediate with carry
0x02	SUBI	Immediate	NZCV	Subtract immediate
0x03	SBCI	Immediate	NZCV	Subtract immediate with carry
0x04	ANDI	Immediate	NZ	AND immediate
0x05	ORRI	Immediate	NZ	OR immediate
0x06	XORI	Immediate	NZ	XOR immediate
0x07	LOAD	Immediate	–	Load immediate (move)
0x08	–	–	–	Undocumented
0x09	–	–	–	Undocumented
0x0A	CMPI	Immediate	NZCV	Compare immediate
0x0B	–	–	–	Undocumented
0x0C	TSAI	Immediate	NZ	Test AND immediate
0x0D	–	–	–	Undocumented
0x0E	TSXI	Immediate	NZ	Test XOR immediate
0x0F	COPI	Immediate	–	Coprocessor call immediate
0x10	STOR	Indirect Imm	–	Store to (addr + imm)
0x11	STOR	Indirect Reg	–	Store to (addr + reg)
0x12	STOR	Pre-Dec	–	Store with pre-decrement
0x13	STOR	Pre-Dec Reg	–	Store with pre-dec (reg)
0x14	LOAD	Indirect Imm	–	Load from (addr + imm)
0x15	LOAD	Indirect Reg	–	Load from (addr + reg)
0x16	LOAD	Post-Inc	–	Load with post-increment
0x17	LOAD	Post-Inc Reg	–	Load with post-inc (reg)
0x18	LDEA	Indirect Imm	–	Load effective address
0x19	LDEA	Indirect Reg	–	Load effective address (reg)
0x1A	BRAN	Indirect Imm	–	Branch (imm displacement)
0x1B	BRAN	Indirect Reg	–	Branch (reg displacement)
0x1C	LJSR	Indirect Imm	–	Long jump to subroutine
0x1D	LJSR	Indirect Reg	–	Long jump to subroutine (reg)
0x1E	BRSR	Indirect Imm	–	Branch to subroutine
0x1F	BRSR	Indirect Reg	–	Branch to subroutine (reg)
0x20	ADDI	Short Imm+Shift	NZCV	Add short immediate
0x21	ADCI	Short Imm+Shift	NZCV	Add short imm with carry
0x22	SUBI	Short Imm+Shift	NZCV	Subtract short immediate
0x23	SBCI	Short Imm+Shift	NZCV	Subtract short imm with carry
0x24	ANDI	Short Imm+Shift	NZ	AND short immediate
0x25	ORRI	Short Imm+Shift	NZ	OR short immediate
0x26	XORI	Short Imm+Shift	NZ	XOR short immediate
0x27	LOAD	Short Imm+Shift	–	Load short immediate
0x28	–	–	–	Undocumented
0x29	–	–	–	Undocumented
0x2A	CMPI	Short Imm+Shift	NZCV	Compare short immediate
0x2B	–	–	–	Undocumented
0x2C	TSAI	Short Imm+Shift	NZ	Test AND short immediate
0x2D	–	–	–	Undocumented
0x2E	TSXI	Short Imm+Shift	NZ	Test XOR short immediate
0x2F	COPI	Short Imm+Shift	–	Coprocessor call short imm
0x30	ADDR	Register	NZCV	Add register
0x31	ADCR	Register	NZCV	Add register with carry
0x32	SUBR	Register	NZCV	Subtract register
0x33	SBCR	Register	NZCV	Subtract register with carry
0x34	ANDR	Register	NZ	AND register
0x35	ORRR	Register	NZ	OR register
0x36	XORR	Register	NZ	XOR register
0x37	LOAD	Register	–	Load from register (move)
0x38	–	–	–	Undocumented
0x39	–	–	–	Undocumented
0x3A	CMPR	Register	NZCV	Compare register
0x3B	–	–	–	Undocumented
0x3C	TSAR	Register	NZ	Test AND register
0x3D	–	–	–	Undocumented
0x3E	TSXR	Register	NZ	Test XOR register
0x3F	COPR	Register	–	Coprocessor call register

8.3 Instruction Grouping Patterns

8.3.1 Opcode Organization

The opcode space is systematically organized:

- **0x0__**: Immediate operand format
- **0x1__**: Memory and control flow operations
- **0x2__**: Short immediate with shift format
- **0x3__**: Register operand format

8.3.2 Save vs. Test Variants

Many ALU instructions have two variants:

- **+0x00 to +0x07**: Save result to destination register
- **+0x08 to +0x0F**: Test only (update flags, discard result)

Examples:

- 0x04 = **ANDI** (save result), 0x0C = **TSAI** (test only)
- 0x06 = **XORI** (save result), 0x0E = **TSXI** (test only)

8.4 Meta-Instructions

Several commonly-used operations are implemented as meta-instructions (pseudo-instructions) that assemble to specific opcodes:

Meta-Instruction	Assembles To	Purpose
NOOP	<code>ADDI r1, #0</code>	No operation
RETS	<code>LDEA p, (#0, 1)</code>	Return from subroutine
WAIT	<code>COP #0x1F00</code>	Wait for interrupt
RETE	<code>COP #0x1A00</code>	Return from exception

Table 8.2: Meta-Instructions

8.5 Instruction Timing

All instructions execute in exactly 6 clock cycles:

1. Instruction Fetch (High Word)
2. Instruction Fetch (Low Word)

3. Decode and Register Fetch
4. Execute/Address Calculate
5. Memory Access (or NOP)
6. Write Back

This fixed timing simplifies hardware design and makes execution time predictable.

8.6 Next Chapters

The following chapters provide detailed documentation for each instruction group:

- **Chapter 9:** ALU instructions (arithmetic, logical, compare)
- **Chapter 10:** Load and store operations
- **Chapter 11:** Branches, jumps, and address operations
- **Chapter 12:** Coprocessor interface
- **Chapter 13:** Meta-instructions and pseudo-ops

Chapter 9

ALU Instructions

9.1 Overview

The ALU (Arithmetic Logic Unit) instructions perform arithmetic and logical operations on register operands. All ALU instructions follow the load/store architecture principle: they operate only on registers, not directly on memory.

ALU instructions are available in three format variants:

- **Immediate:** Operation with 16-bit constant
- **Short Immediate with Shift:** Operation with 8-bit constant and optional shift
- **Register:** Operation between registers with optional shift

9.2 ALU Instruction Families

9.2.1 Arithmetic Instructions

- **ADD** – Addition
- **ADC** – Add with Carry
- **SUB** – Subtraction
- **SBC** – Subtract with Carry (Borrow)

9.2.2 Logical Instructions

- **AND** – Bitwise AND
- **ORR** – Bitwise OR
- **XOR** – Bitwise XOR (Exclusive OR)

9.2.3 Data Movement

- **LOAD** – Load immediate or copy register

9.2.4 Test and Compare

- **CMP** – Compare (subtract without saving result)
- **TSA** – Test AND (AND without saving result)
- **TSX** – Test XOR (XOR without saving result)

9.3 Status Flag Updates

Most ALU instructions update the status register flags:

Arithmetic (ADD, ADC, SUB, SBC, CMP) Update all four flags: N, Z, C, V

Logical (AND, ORR, XOR, TSA, TSX) Update N and Z; clear C and V

Load (LOAD) Do not update flags

9.4 ADD – Addition

ADDI / ADDR – Add Immediate / Add Register

Opcodes: 0x00 (Imm), 0x20 (Short Imm), 0x30 (Reg)

Syntax:

1	ADDI rD, #imm16	<i>; rD = rD + imm16</i>
2	ADDI rD, #imm8, shift	<i>; rD = rD + (imm8 << shift)</i>
3	ADDR rD, rS1, rS2	<i>; rD = rS1 + rS2</i>
4	ADDR rD, rS1, rS2, shift	<i>; rD = rS1 + (rS2 << shift)</i>

Operation:

```
result = operand1 + operand2
destination = result
SR.N = result[15]
SR.Z = (result == 0)
SR.C = carry_out
SR.V = signed_overflow
```

Description:

Adds two values and stores the result in the destination register. The carry flag is set if an unsigned overflow occurs (carry out of bit 15). The overflow flag is set if a signed overflow occurs (the sign of the result is incorrect for the operation).

Flags: N Z C V

Example:

```
1 ; Simple addition
2 ADDI r1, #100           ; r1 = r1 + 100
3
4 ; Add two registers
5 ADDR r3, r1, r2         ; r3 = r1 + r2
6
7 ; Scaled addition (multiply by 3)
8 ADDR r4, r5, r5, LSL #1 ; r4 = r5 + (r5 * 2) = r5 * 3
9
10 ; Build large constant
11 ADDI r1, #1, LSL #12   ; r1 = r1 + 4096
```

Notes:

- For multi-precision arithmetic, use **ADC** to propagate carry
- Adding zero (**ADDI** r1, #0) can be used to move values or test flags
- Shift operations allow efficient constant multiplication

9.5 ADC – Add with Carry

ADCI / ADCR – Add with Carry

Opcodes: 0x01 (Imm), 0x21 (Short Imm), 0x31 (Reg)

Syntax:

```

1 ADCI rD, #imm16                ; rD = rD + imm16 + C
2 ADCI rD, #imm8, shift          ; rD = rD + (imm8 << shift) + C
3 ADCR rD, rS1, rS2              ; rD = rS1 + rS2 + C

```

Operation:

```

result = operand1 + operand2 + SR.C
destination = result
SR.N = result[15]
SR.Z = (result == 0)
SR.C = carry_out
SR.V = signed_overflow

```

Description:

Adds two values plus the carry flag and stores the result. This instruction is used for multi-precision (32-bit, 48-bit, etc.) arithmetic to propagate the carry from lower-order additions to higher-order additions.

Flags: N Z C V

Example:

```

1 ; 32-bit addition (r1:r2 = r3:r4 + r5:r6)
2 ; Low words
3 ADDR r2, r4, r6                ; r2 = r4 + r6, set carry
4
5 ; High words (with carry propagation)
6 ADCR r1, r3, r5                ; r1 = r3 + r5 + carry

```

Notes:

- Always use after **ADD** for multi-word arithmetic
- The carry flag must be in the correct state before **ADC**
- Can be used to add 1 conditionally based on carry flag

9.6 SUB – Subtraction

SUBI / SUBR – Subtract Immediate / Subtract Register

Opcodes: 0x02 (Imm), 0x22 (Short Imm), 0x32 (Reg)

Syntax:

```

1 SUBI rD, #imm16                ; rD = rD - imm16
2 SUBI rD, #imm8, shift          ; rD = rD - (imm8 << shift)
3 SUBR rD, rS1, rS2              ; rD = rS1 - rS2

```

Operation:

```

result = operand1 - operand2
destination = result
SR.N = result[15]
SR.Z = (result == 0)
SR.C = NOT(borrow) ; Set if no borrow
SR.V = signed_overflow

```

Description:

Subtracts the second operand from the first and stores the result. The carry flag is cleared if a borrow occurs (operand2 > operand1 for unsigned). The overflow flag indicates signed overflow.

Flags: N Z C V

Example:

```

1 ; Decrement by 1
2 SUBI r1, #1                ; r1 = r1 - 1
3
4 ; Subtract registers
5 SUBR r3, r1, r2            ; r3 = r1 - r2
6
7 ; Loop counter
8 SUBI r7, #1                ; Decrement counter
9 BRAN != loop               ; Branch if not zero

```

Notes:

- Carry flag behavior is inverted compared to ADD (set when no borrow)
- For multi-precision subtraction, use **SBC**
- Subtracting a value from itself (**SUBR r1, r1, r1**) clears the register

9.7 SBC – Subtract with Carry (Borrow)

SBCI / SBCR – Subtract with Carry

Opcodes: 0x03 (Imm), 0x23 (Short Imm), 0x33 (Reg)

Syntax:

```
1 SBCI rD, #imm16           ; rD = rD - imm16 - !C
2 SBCR rD, rS1, rS2         ; rD = rS1 - rS2 - !C
```

Operation:

```
result = operand1 - operand2 - (1 - SR.C)
destination = result
SR.N = result[15]
SR.Z = (result == 0)
SR.C = NOT(borrow)
SR.V = signed_overflow
```

Description:

Subtracts the second operand and borrow (inverse of carry) from the first operand. Used for multi-precision subtraction to propagate borrows from lower-order to higher-order subtractions.

Flags: N Z C V

Example:

```
1 ; 32-bit subtraction (r1:r2 = r3:r4 - r5:r6)
2 ; Low words
3 SUBR r2, r4, r6           ; r2 = r4 - r6, set/clear carry
4
5 ; High words (with borrow propagation)
6 SBCR r1, r3, r5           ; r1 = r3 - r5 - borrow
```

Notes:

- Always use after **SUB** for multi-word subtraction
- Remember: carry flag is inverted for subtraction (C=1 means no borrow)

9.8 AND – Bitwise AND

ANDI / ANDR – AND Immediate / AND Register

Opcodes: 0x04 (Imm), 0x24 (Short Imm), 0x34 (Reg)

Syntax:

```

1 ANDI rD, #imm16                ; rD = rD & imm16
2 ANDI rD, #imm8, shift          ; rD = rD & (imm8 << shift)
3 ANDR rD, rS1, rS2              ; rD = rS1 & rS2

```

Operation:

```

result = operand1 AND operand2
destination = result
SR.N = result[15]
SR.Z = (result == 0)
SR.C = 0
SR.V = 0

```

Description:

Performs bitwise AND operation. Each bit in the result is 1 only if the corresponding bits in both operands are 1. Commonly used for bit masking and clearing specific bits.

Flags: N Z (C and V cleared)

Example:

```

1 ; Mask lower byte
2 ANDI r1, #0x00FF                ; r1 = r1 & 0xFF
3
4 ; Clear bit 5
5 ANDI r2, # ~(1<<5)              ; r2 = r2 & 0xFFDF
6
7 ; Check if two registers share any set bits
8 ANDR r3, r1, r2                  ; r3 = r1 & r2
9 CMPI r3, #0
10 BRAN != common_bits             ; Branch if any bits in common

```

Notes:

- ANDing with 0xFFFF leaves value unchanged
- ANDing with 0x0000 clears the register
- Use **TSA** to test bits without modifying the register

9.9 ORR – Bitwise OR

ORRI / ORRR – OR Immediate / OR Register

Opcodes: 0x05 (Imm), 0x25 (Short Imm), 0x35 (Reg)

Syntax:

```

1 ORRI rD, #imm16           ; rD = rD | imm16
2 ORRI rD, #imm8, shift     ; rD = rD | (imm8 << shift)
3 ORRR rD, rS1, rS2         ; rD = rS1 | rS2

```

Operation:

result = operand1 OR operand2

destination = result

SR.N = result[15]

SR.Z = (result == 0)

SR.C = 0

SR.V = 0

Description:

Performs bitwise OR operation. Each bit in the result is 1 if either corresponding bit in the operands is 1. Commonly used for setting specific bits.

Flags: N Z (C and V cleared)

Example:

```

1 ; Set bit 7
2 ORRI r1, #0x0080           ; r1 = r1 | 0x80
3
4 ; Set multiple bits
5 ORRI r2, #0xF000           ; Set upper nibble
6
7 ; Combine two registers
8 ORRR r3, r1, r2            ; r3 = r1 | r2
9
10 ; Set bit N (variable)
11 ADDI r4, #1
12 ADDR r4, r4, r5, LSL       ; r4 = 1 << r5
13 ORRR r1, r4                ; r1 |= (1 << r5)

```

Notes:

- ORing with 0x0000 leaves value unchanged
- ORing with 0xFFFF sets all bits
- Use for enabling flag bits or combining bit fields

9.10 XOR – Bitwise Exclusive OR

XORI / XORR – XOR Immediate / XOR Register

Opcodes: 0x06 (Imm), 0x26 (Short Imm), 0x36 (Reg)

Syntax:

```

1 XORI rD, #imm16                ; rD = rD ^ imm16
2 XORI rD, #imm8, shift          ; rD = rD ^ (imm8 << shift)
3 XORR rD, rS1, rS2              ; rD = rS1 ^ rS2

```

Operation:

```

result = operand1 XOR operand2
destination = result
SR.N = result[15]
SR.Z = (result == 0)
SR.C = 0
SR.V = 0

```

Description:

Performs bitwise XOR (exclusive OR) operation. Each bit in the result is 1 if the corresponding bits in the operands are different. Used for toggling bits, bitwise comparison, and simple encryption.

Flags: N Z (C and V cleared)

Example:

```

1 ; Toggle bit 3
2 XORI r1, #0x0008                ; r1 = r1 ^ 0x08
3
4 ; Invert all bits
5 XORI r2, #0xFFFF                ; r2 = ~r2
6
7 ; Check if registers are equal
8 XORR r3, r1, r2                  ; r3 = r1 ^ r2
9 ; If r3 == 0, then r1 == r2
10
11 ; Swap using XOR (no temporary)
12 XORR r1, r1, r2                  ; r1 = r1 ^ r2
13 XORR r2, r1, r2                  ; r2 = r1 ^ r2 = (r1 ^ r2) ^ r2 = r1
14 XORR r1, r1, r2                  ; r1 = (r1 ^ r2) ^ r1 = r2

```

Notes:

- XORing with 0x0000 leaves value unchanged
- XORing with 0xFFFF inverts all bits (bitwise NOT)
- XORing a value with itself always gives 0
- Use **TSX** to check for differences without modifying register

9.11 LOAD – Load Immediate / Move Register

LOAD – Load/Move

Opcodes: 0x07 (Imm), 0x27 (Short Imm), 0x37 (Reg)

Syntax:

```

1 LOAD rD, #imm16           ; rD = imm16 (via add)
2 LOAD rD, #imm8, shift     ; rD = imm8 << shift
3 LOAD rD, rS               ; rD = rS (via add)

```

Operation:

; Implemented as: $rD = 0 + \text{operand}$
 destination = operand
 ; Flags NOT updated

Description:

Loads an immediate value into a register or copies a register value. This is actually implemented as an ADD with an implicit zero operand, but flags are not updated. This is the primary way to load constants or move data between registers.

Flags: None

Example:

```

1 ; Load constant
2 LOAD r1, #1234           ; r1 = 1234
3
4 ; Copy register
5 LOAD r2, r1              ; r2 = r1
6
7 ; Load with shift
8 LOAD r3, #1, LSL #8      ; r3 = 256
9
10 ; Zero a register
11 LOAD r4, #0             ; r4 = 0
12
13 ; Load large constant (combine)
14 LOAD r5, #0x12, LSL #8   ; r5 = 0x1200
15 ORRI r5, #0x34          ; r5 = 0x1234

```

Notes:

- Does not update flags, unlike **ADD**
- Most efficient way to move data between registers
- For 16-bit constants, use immediate form
- For larger or shifted constants, use short immediate with shift

9.12 CMP – Compare

CMPI / CMPR – Compare Immediate / Compare Register

Opcodes: 0x0A (Imm), 0x2A (Short Imm), 0x3A (Reg)

Syntax:

```

1 CMPI rS, #imm16                ; Compare rS with imm16
2 CMPI rS, #imm8, shift          ; Compare rS with (imm8 << shift)
3 CMPR rS1, rS2                  ; Compare rS1 with rS2

```

Operation:

```

result = operand1 - operand2
; Result is discarded, only flags updated
SR.N = result[15]
SR.Z = (result == 0)
SR.C = NOT(borrow)
SR.V = signed_overflow

```

Description:

Performs subtraction but discards the result, only updating the status flags. This is the primary instruction for implementing conditional execution and branches. The flags can be tested with condition codes to determine the relationship between the operands.

Flags: N Z C V

Example:

```

1 ; Test if r1 is zero
2 CMPI r1, #0
3 BRAN |== is_zero           ; Branch if r1 == 0
4
5 ; Test if r1 > r2 (unsigned)
6 CMPR r1, r2
7 BRAN |> r1_greater
8
9 ; Test if r1 >= r2 (signed)
10 CMPR r1, r2
11 BRAN |>= r1_greater_or_equal
12
13 ; Range check: if (r1 >= 10 && r1 < 20)
14 CMPI r1, #10
15 BRAN |< out_of_range      ; Branch if r1 < 10
16 CMPI r1, #20
17 BRAN |>= out_of_range     ; Branch if r1 >= 20
18 ; r1 is in range [10, 20)

```

Notes:

- Does not modify any register, only flags
- Use with conditional instructions or branches
- Remember: CMP A, B computes A - B
- For signed comparisons, use >=, <, >, <
- For unsigned comparisons, use >, CS, CC, <=

9.13 TSA – Test AND

TSAI / TSAR – Test AND Immediate / Test AND Register

Opcodes: 0x0C (Imm), 0x2C (Short Imm), 0x3C (Reg)

Syntax:

```

1 TSAI rS, #imm16                ; Test rS & imm16
2 TSAI rS, #imm8, shift          ; Test rS & (imm8 << shift)
3 TSAR rS1, rS2                  ; Test rS1 & rS2

```

Operation:

```

result = operand1 AND operand2
; Result is discarded, only flags updated
SR.N = result[15]
SR.Z = (result == 0)
SR.C = 0
SR.V = 0

```

Description:

Performs bitwise AND but discards the result, only updating flags. Used to test if specific bits are set without modifying the register. The zero flag indicates whether any tested bits were set.

Flags: N Z (C and V cleared)

Example:

```

1 ; Test if bit 5 is set
2 TSAI r1, #0x0020                ; Test r1 & 0x20
3 BRAN != bit5_set                ; Branch if bit 5 was set
4
5 ; Test if any upper byte bits are set
6 TSAI r2, #0xFF00
7 BRAN != has_upper_bits
8
9 ; Test if r1 and r2 have any bits in common
10 TSAR r1, r2
11 BRAN == no_common_bits          ; Branch if no bits in common
12
13 ; Test multiple bits
14 TSAI r3, #0xF000                ; Test upper nibble
15 BRAN == upper_clear             ; Branch if all tested bits clear

```

Notes:

- Does not modify any register, only flags
- Z=1 means all tested bits were 0
- Z=0 means at least one tested bit was 1
- Use for bit testing without side effects
- More efficient than AND + CMP for simple tests

9.14 TSX – Test XOR

TSXI / TSXR – Test XOR Immediate / Test XOR Register

Opcodes: 0x0E (Imm), 0x2E (Short Imm), 0x3E (Reg)

Syntax:

```

1 TSXI rS, #imm16                ; Test rS ^ imm16
2 TSXI rS, #imm8, shift          ; Test rS ^ (imm8 << shift)
3 TSXR rS1, rS2                  ; Test rS1 ^ rS2

```

Operation:

```

result = operand1 XOR operand2
; Result is discarded, only flags updated
SR.N = result[15]
SR.Z = (result == 0)
SR.C = 0
SR.V = 0

```

Description:

Performs bitwise XOR but discards the result, only updating flags. Used to test if bits match a specific pattern or to compare values for equality. Z=1 indicates the values are identical.

Flags: N Z (C and V cleared)

Example:

```

1 ; Test if r1 equals specific value
2 TSXI r1, #0x1234                ; Test r1 ^ 0x1234
3 BRAN |== is_0x1234              ; Branch if r1 == 0x1234
4
5 ; Test if two registers are equal
6 TSXR r1, r2                     ; Test r1 ^ r2
7 BRAN |== registers_equal        ; Branch if r1 == r2
8
9 ; Test if bit pattern matches
10 TSAI r3, #0xFF                 ; Mask to lower byte
11 TSXI r3, #0xAA                 ; Test if lower byte == 0xAA
12 BRAN |== pattern_match

```

Notes:

- Does not modify any register, only flags
- Z=1 means values are identical (all bits match)
- Can be used as equality test (alternative to CMP for == only)
- More efficient than XOR + CMP for simple equality tests

9.15 Summary

The ALU instructions form the computational core of the SIRCIS instruction set. Key points:

- All ALU operations work only on registers (load/store architecture)
- Three format variants provide flexibility (immediate, short+shift, register)
- Test variants (CMP, TSA, TSX) allow non-destructive testing
- Shift operations can be combined with ALU ops for powerful single-cycle operations
- Consistent flag behavior makes conditional execution predictable

Chapter 10

Memory Access Instructions

10.1 Overview

Memory access instructions transfer data between registers and memory. Following the load/store architecture, these are the only instructions that can access memory—all arithmetic and logical operations must work on registers.

The SIRC-1 provides two primary memory operations:

- **LOAD** – Read from memory into a register
- **STOR** – Write from a register to memory

Both instructions support multiple addressing modes:

- Indirect with immediate offset: (**#offset**, **addr**)
- Indirect with register offset: (**reg**, **addr**)
- Post-increment: (**#offset**, **addr**)**+**
- Pre-decrement: **-(#offset, addr)**

10.2 Effective Address Calculation

For all memory operations, the effective address (EA) is calculated as:

$$EA = \text{AddressRegister} + \text{Offset} \quad (10.1)$$

Where:

- Address Register is one of: **l**, **a**, **s**, or **p**
- Offset is either an immediate value or register contents

The resulting 24-bit address is used to access memory.

10.3 LOAD Instructions

LOAD – Load from Memory

Opcodes: 0x14 (Indirect Imm), 0x15 (Indirect Reg), 0x16 (Post-Inc Imm), 0x17 (Post-Inc Reg)

Syntax:

```

1 LOAD rD, (#offset, addr)      ; rD = memory[addr + offset]
2 LOAD rD, (rS, addr)           ; rD = memory[addr + rS]
3 LOAD rD, (#offset, addr)+     ; rD = memory[addr + offset]; addr +=
    offset
4 LOAD rD, (rS, addr)+         ; rD = memory[addr + rS]; addr += rS

```

Description:

Loads a 16-bit value from memory into the destination register. Post-increment forms update the address register after the load, useful for array traversal.

Examples:

```

1 ; Load from fixed offset
2 LOAD r1, (#4, a)              ; r1 = memory[a + 4]
3
4 ; Load using variable offset
5 LOAD r2, (r3, a)              ; r2 = memory[a + r3]
6
7 ; Array iteration
8 LOAD r4, (#0, a)+             ; r4 = *a; a += 2
9
10 ; Stack pop
11 LOAD r5, (#0, s)+            ; r5 = *s; s += 2

```

10.4 STOR Instructions

STOR – Store to Memory

Opcodes: 0x10 (Indirect Imm), 0x11 (Indirect Reg), 0x12 (Pre-Dec Imm), 0x13 (Pre-Dec Reg)

Syntax:

```

1 STOR rS, (#offset, addr)      ; memory[addr + offset] = rS
2 STOR rS, (rD, addr)          ; memory[addr + rD] = rS
3 STOR rS, -(#offset, addr)     ; addr -= offset; memory[addr +
    offset] = rS
4 STOR rS, -(rD, addr)          ; addr -= rD; memory[addr + rD] = rS

```

Description:

Stores a 16-bit value from a register into memory. Pre-decrement forms update the address register before the store, useful for stack push operations.

Examples:

```

1 ; Store to fixed offset
2 STOR r1, (#8, a)              ; memory[a + 8] = r1
3
4 ; Store using variable offset
5 STOR r2, (r3, a)              ; memory[a + r3] = r2
6
7 ; Stack push
8 STOR r4, -(#2, s)             ; s -= 2; memory[s] = r4

```

10.5 Common Memory Access Patterns

10.5.1 Structure Field Access

```

1 ; struct { int16_t x, y, z; } point;
2 ; 'a' points to point
3 LOAD r1, (#0, a)              ; r1 = point.x
4 LOAD r2, (#2, a)              ; r2 = point.y
5 LOAD r3, (#4, a)              ; r3 = point.z

```

10.5.2 Array Iteration

```

1 ; Process array of 16-bit values
2 ; 'a' = array base, r7 = count
3 loop:
4     LOAD r1, (#0, a)+          ; Load element, advance
5     ; ... process r1 ...
6     SUBI r7, #1
7     BRAN != loop

```

10.5.3 Stack Operations

```
1 ; Push registers
2 STOR r1, -(#2, s)
3 STOR r2, -(#2, s)
4 STOR r3, -(#2, s)
5
6 ; Pop registers (reverse order)
7 LOAD r3, (#0, s)+
8 LOAD r2, (#0, s)+
9 LOAD r1, (#0, s)+
```

(Additional memory instruction details would follow in a complete manual)

Chapter 11

Control Flow Instructions

11.1 Overview

Control flow instructions modify the program counter to change the execution flow. The SIRC-1 provides several types of control flow operations:

- **BRAN** – Branch (unconditional or conditional jump)
- **LJSR** – Long Jump to Subroutine (with link)
- **BRSR** – Branch to Subroutine (relative, with link)
- **LDEA** – Load Effective Address (can be used for jumps)

All control flow instructions can be conditional, allowing efficient implementation of if-then-else and loop constructs.

11.2 Branch Instructions

BRAN – Branch

Opcodes: 0x1A (Imm Displacement), 0x1B (Reg Displacement)

Syntax:

```

1 BRAN (#disp, p)           ; PC = PC + disp
2 BRAN (rS, p)              ; PC = PC + rS
3 BRAN|cond (#disp, p)      ; Conditional branch

```

Description:

Branches to a new location by adding a displacement to the program counter. The displacement can be an immediate value (for fixed jumps) or a register value (for computed jumps). Branches are typically PC-relative.

Examples:

```

1 ; Unconditional branch forward
2 BRAN (#20, p)              ; Jump ahead 20 bytes
3
4 ; Backward branch (loop)
5 loop:
6     ; ... loop body ...
7     BRAN != (#-16, p)       ; Jump back if not zero
8
9 ; Conditional branch
10 CMPI r1, #10
11 BRAN >= (#8, p)           ; Branch if r1 >= 10

```

11.3 Subroutine Call Instructions

LJSR – Long Jump to Subroutine

Opcodes: 0x1C (Imm), 0x1D (Reg)

Syntax:

```
1 LJSR (#addr, a)           ; l = PC; PC = a + addr
2 LJSR (#addr, p)           ; l = PC; PC = PC + addr (rel call)
```

Description:

Calls a subroutine by saving the return address to the link register (l) and jumping to the target address. The return address can later be restored using **RETS**.

Examples:

```
1 ; Call function at address in 'a'
2 LJSR (#0, a)
3
4 ; PC-relative call
5 LJSR (#function_offset, p)
6
7 ; Return from subroutine
8 RETS                      ; Assembles to: LDEA p, (#0, l)
```

11.4 Load Effective Address

LDEA – Load Effective Address

Opcodes: 0x18 (Imm), 0x19 (Reg)

Syntax:

```
1 LDEA dest, (#offset, src) ; dest = src + offset
2 LDEA dest, (rS, src)      ; dest = src + rS
```

Description:

Computes an effective address and loads it into the destination address register pair. Can be used for pointer arithmetic or, when the destination is the program counter, as a jump instruction.

Examples:

```
1 ; Pointer arithmetic
2 LDEA a, (#16, a)           ; a = a + 16
3
4 ; Computed jump
5 LDEA p, (r1, p)            ; PC = PC + r1 (jump table)
6
7 ; Return from subroutine
8 LDEA p, (#0, l)            ; PC = l (RETS pseudo-instruction)
```

11.5 Control Flow Patterns

11.5.1 If-Then-Else

```
1 ; if (r1 > r2) { ... } else { ... }
2 CMPR r1, r2
3 BRAN |<= else_part
4 ; Then part
5 ; ...
6 BRAN (#end, p)
7 else_part:
8 ; Else part
9 ; ...
10 end:
```

11.5.2 While Loop

```
1 ; while (r1 > 0) { ... }
2 while_start:
3     CMPI r1, #0
4     BRAN |<= while_end
5     ; Loop body
6     ; ...
7     BRAN (#while_start, p)
8 while_end:
```

11.5.3 Switch/Jump Table

```
1 ; Switch on r1 (0-3)
2 ADDR r2, r1, r1, LSL #1          ; r2 = r1 * 2 (word size)
3 LDEA p, (r2, p)                  ; Jump via table
4
5 jump_table:
6     DW case0 - jump_table
7     DW case1 - jump_table
8     DW case2 - jump_table
9     DW case3 - jump_table
```

(Additional control flow details would follow)

Chapter 12

Coprocessor Instructions

12.1 Overview

The SIRC-1 CPU includes a coprocessor interface that allows delegation of certain operations to specialized coprocessors. The primary coprocessor is the Exception Unit (Coprocessor 1), which handles exceptions, interrupts, and privileged operations.

COP – Coprocessor Call

Opcodes: 0x0F (Imm), 0x2F (Short Imm), 0x3F (Reg)

Syntax:

```
1 COP #opcode                ; Call coprocessor with 16-bit opcode
2 COP rS                      ; Call coprocessor with register
   value
```

Description:

Transfers control to a coprocessor. The coprocessor ID and operation code are encoded in the immediate value or register. Coprocessor operations may be privileged.

Format:

- Bits 15–12: Coprocessor ID
- Bits 11–0: Operation code

Examples:

```
1 ; Wait for interrupt (Exception Unit)
2 COP #0x1F00                ; Coprocessor 1, opcode 0xF00
3 ; Assembled as WAIT pseudo-instruction
4
5 ; Return from exception
6 COP #0x1A00                ; Coprocessor 1, opcode 0xA00
7 ; Assembled as RETE pseudo-instruction
```

12.2 Exception Unit (Coprocessor 1)

The Exception Unit handles:

- Hardware exceptions (faults, traps)
- Software exceptions
- Interrupts (multiple priority levels)
- Privileged operations

12.2.1 Common Operations

Opcode	Operation
0x1A00	Return from exception (RETE)
0x1F00	Wait for interrupt (WAIT)

Table 12.1: Exception Unit Operations

(Additional coprocessor details would follow)

Chapter 13

Meta-Instructions

13.1 Overview

Meta-instructions (also called pseudo-instructions) are assembly mnemonics that don't directly correspond to unique opcodes. Instead, they assemble to specific forms of existing instructions, providing more intuitive syntax for common operations.

13.2 NOOP – No Operation

Syntax: NOOP

Assembles to: ADDI r1, #0

Description: Does nothing for 6 cycles. Useful for timing delays, instruction padding, or placeholders during development.

Example:

```
1 NOOP                ; Wait 6 cycles
2 NOOP
3 NOOP                ; Total 18 cycles delay
```

13.3 RETS – Return from Subroutine

Syntax: RETS

Assembles to: LDEA p, (#0, 1)

Description: Returns from a subroutine by copying the link register to the program counter. Used after LJSR or BRSR.

Example:

```
1 my_function:
2   ; ... function body ...
3   RETS                ; Return to caller
```

13.4 WAIT – Wait for Interrupt

Syntax: WAIT

Assembles to: COP #0x1F00

Description: Puts the CPU into a low-power wait state until an interrupt occurs. Sets the Waiting for Interrupt bit in the status register.

Example:

```
1 main_loop:
2     WAIT                ; Sleep until interrupt
3     ; ... process interrupt ...
4     BRAN (#main_loop, p)
```

13.5 RETE – Return from Exception

Syntax: RETE

Assembles to: COP #0x1A00

Description: Returns from an exception handler by restoring the saved program counter and status register. Only valid in supervisor mode.

Example:

```
1 exception_handler:
2     ; ... handle exception ...
3     RETE                ; Return to interrupted code
```

(Note: Check assembler documentation for supported pseudo-instructions)

Appendix A

Opcode Map

A.1 Complete Opcode Reference

This appendix provides a complete map of all 64 possible opcodes in the SIRCIS instruction set.

Hex	Binary	Mnemonic	Description
ALU Immediate (0x00–0x0F)			
00	000000	ADDI	Add Immediate
01	000001	ADCI	Add with Carry Immediate
02	000010	SUBI	Subtract Immediate
03	000011	SBCI	Subtract with Carry Immediate
04	000100	ANDI	AND Immediate
05	000101	ORRI	OR Immediate
06	000110	XORI	XOR Immediate
07	000111	LOAD	Load Immediate
08	001000	–	Undocumented
09	001001	–	Undocumented
0A	001010	CMPI	Compare Immediate
0B	001011	–	Undocumented
0C	001100	TSAI	Test AND Immediate
0D	001101	–	Undocumented
0E	001110	TSXI	Test XOR Immediate
0F	001111	COPI	Coprocessor Immediate
Memory and Control (0x10–0x1F)			
10	010000	STOR	Store Indirect Immediate
11	010001	STOR	Store Indirect Register
12	010010	STOR	Store Pre-Decrement Immediate
13	010011	STOR	Store Pre-Decrement Register
14	010100	LOAD	Load Indirect Immediate
15	010101	LOAD	Load Indirect Register
16	010110	LOAD	Load Post-Increment Immediate
17	010111	LOAD	Load Post-Increment Register
18	011000	LDEA	Load Effective Address Immediate
19	011001	LDEA	Load Effective Address Register
1A	011010	BRAN	Branch Immediate
1B	011011	BRAN	Branch Register
1C	011100	LJSR	Long Jump to Subroutine Immediate
1D	011101	LJSR	Long Jump to Subroutine Register
1E	011110	BRSR	Branch to Subroutine Immediate
1F	011111	BRSR	Branch to Subroutine Register
ALU Short Immediate (0x20–0x2F)			
20	100000	ADDI	Add Short Immediate
21	100001	ADCI	Add with Carry Short Immediate
22	100010	SUBI	Subtract Short Immediate
23	100011	SBCI	Subtract with Carry Short Immediate
24	100100	ANDI	AND Short Immediate
25	100101	ORRI	OR Short Immediate
26	100110	XORI	XOR Short Immediate
27	100111	LOAD	Load Short Immediate
28	101000	–	Undocumented
29	101001	–	Undocumented
2A	101010	CMPI	Compare Short Immediate
2B	101011	–	Undocumented
2C	101100	TSAI	Test AND Short Immediate
2D	101101	–	Undocumented
2E	101110	TSXI	Test XOR Short Immediate
2F	101111	COPI	Coprocessor Short Immediate

A.2 Opcode Patterns

A.2.1 Format Identification

- Bits 5–4 = 00: Immediate format (0x00–0x0F)
- Bits 5–4 = 01: Memory/Control operations (0x10–0x1F)
- Bits 5–4 = 10: Short Immediate with Shift (0x20–0x2F)
- Bits 5–4 = 11: Register format (0x30–0x3F)

A.2.2 Save vs. Test

- Bit 3 = 0: Save result (0x00–0x07, 0x20–0x27, 0x30–0x37)
- Bit 3 = 1: Test only, discard result (0x08–0x0F, 0x28–0x2F, 0x38–0x3F)

A.2.3 Memory Operations Decoding

For opcodes 0x10–0x1F, bits encode memory operation type:

- Bit 4 = 1: Always set for memory/control section
- Bits 3–2: Operation type
 - 00 = Store
 - 01 = Load
 - 10 = Load Effective Address
 - 11 = Load EA with Link (jump to subroutine)
- Bit 1: Determines if both registers in address pair are updated
- Bit 0: Immediate (0) or Register (1) offset

A.3 Undocumented Instructions

The following opcodes are undocumented and should not be used in production code:

- 0x08, 0x09, 0x0B, 0x0D (Immediate format, test variants)
- 0x28, 0x29, 0x2B, 0x2D (Short Immediate format, test variants)
- 0x38, 0x39, 0x3B, 0x3D (Register format, test variants)

These opcodes may execute in hardware but their behavior is implementation-defined and may change between CPU revisions. See Appendix C for details.

A.4 Quick Lookup Table

Operation	Immediate	Short+Shift	Register
ADD	0x00	0x20	0x30
ADC	0x01	0x21	0x31
SUB	0x02	0x22	0x32
SBC	0x03	0x23	0x33
AND	0x04	0x24	0x34
OR	0x05	0x25	0x35
XOR	0x06	0x26	0x36
LOAD	0x07	0x27	0x37
CMP	0x0A	0x2A	0x3A
TSA	0x0C	0x2C	0x3C
TSX	0x0E	0x2E	0x3E
COP	0x0F	0x2F	0x3F

Table A.2: Instruction Variant Quick Reference

Appendix B

Instruction Timing

B.1 Overview

All SIRCIS instructions execute in exactly 6 clock cycles, following the six-stage pipeline architecture. This fixed timing greatly simplifies software development and hardware design.

B.2 Six-Stage Pipeline

1. **Instruction Fetch (High Word)** – 1 cycle
 - Fetch bits 31–16 from memory address in PC
 - Increment PC by 2
2. **Instruction Fetch (Low Word)** – 1 cycle
 - Fetch bits 15–0 from memory address in PC
 - Increment PC by 2
 - Instruction is now fully available for decode
3. **Decode and Register Fetch** – 1 cycle
 - Decode instruction opcode and operands
 - Read source registers
 - Evaluate condition codes
4. **Execute and Address Calculation** – 1 cycle
 - Perform ALU operation, or
 - Calculate effective memory address
 - Apply shift operations if specified
5. **Memory Access** – 1 cycle
 - Read from memory (LOAD), or
 - Write to memory (STOR), or

- No operation (register-only instructions)

6. **Write Back** – 1 cycle

- Write result to destination register
- Update status register flags if applicable
- Update address registers for post-increment/pre-decrement

B.3 Timing Characteristics

Instruction Type	Cycles
ALU (Register)	6
ALU (Immediate)	6
Load from Memory	6
Store to Memory	6
Branch (taken)	6
Branch (not taken)	6
Conditional (executed)	6
Conditional (not executed)	6
NOOP	6

Table B.1: Instruction Timing (All instructions)

B.4 Conditional Execution

When a conditional instruction's condition is not met:

- The instruction still takes 6 cycles to complete
- All pipeline stages execute normally
- The write-back stage is disabled (no register or memory modification)
- Status flags are not updated

This means conditional instructions do not branch and avoid pipeline stalls, but failed conditions still consume execution time.

B.5 Program Timing Examples

B.5.1 Simple Loop

```

1 ; Process 10 elements
2 ADDI r7, #0, #10 ; 6 cycles
3 loop:
4     LOAD r1, (#0, a)+ ; 6 cycles
5     ADDI r1, #1 ; 6 cycles
6     STOR r1, (#-2, a) ; 6 cycles
7     SUBI r7, #1 ; 6 cycles
8     BRAN != (#loop, p) ; 6 cycles
9 ; Total per iteration: 30 cycles
10 ; Total for 10 iterations: 6 + (10 * 30) = 306 cycles

```

B.5.2 Function Call Overhead

```

1 ; Call function
2 LJSR (#0, a) ; 6 cycles
3
4 ; Function body executes...
5
6 ; Return
7 RETS ; 6 cycles
8 ; Total overhead: 12 cycles

```

B.5.3 Conditional Block

```

1 CMPR r1, r2 ; 6 cycles
2 ADDR |> r3, r4, r5 ; 6 cycles (exec if r1 > r2)
3 ADDR |<= r3, r6, r7 ; 6 cycles (exec if r1 <= r2)
4 ; Total: 18 cycles (one conditional executes, one doesn't)

```

B.6 Performance Considerations

B.6.1 No Pipeline Stalls

The SIRC-1 does not implement pipelining in the traditional sense where multiple instructions are in flight simultaneously. Instead:

- Each instruction completes fully before the next begins
- No data hazards or pipeline bubbles
- No branch prediction penalties
- Execution time is completely predictable

B.6.2 Memory Access

- Memory access always takes 1 cycle within the instruction
- No wait states or cache misses (in the simulation)
- Real hardware implementations may have variable memory timing

B.6.3 Optimization Guidelines

1. Use conditional execution for short sequences

```
1 ; Instead of:
2 CMPR r1, r2
3 BRAN|<= skip
4 ADDI r3, #1
5 skip:
6
7 ; Use:
8 CMPR r1, r2
9 ADDI|> r3, #1 ; Saves branch overhead
```

2. Combine operations with shifts

```
1 ; Instead of:
2 ADDR r1, r2, r2
3 ADDR r1, r1, #0, LSL #1
4
5 ; Use:
6 ADDR r1, r2, r2, LSL #1 ; Multiply by 3 in one instruction
```

3. Use post-increment/pre-decrement for iteration

```
1 ; Instead of:
2 LOAD r1, (#0, a)
3 ADDI a, #2
4
5 ; Use:
6 LOAD r1, (#0, a)+ ; Same result, fewer cycles
```

4. Loop unrolling reduces overhead

```
1 ; Instead of processing one item per iteration,
2 ; process multiple items to reduce branch overhead
3 loop:
4     LOAD r1, (#0, a)+
5     LOAD r2, (#0, a)+
6     LOAD r3, (#0, a)+
7     LOAD r4, (#0, a)+
8     ; Process 4 items...
9     SUBI r7, #4
10    BRAN|> loop
```

B.7 Theoretical Performance

At a given clock frequency:

- **Instructions per second:** $f_{clock}/6$
- **At 10 MHz:** ≈ 1.67 million instructions/second

- **At 25 MHz:** \approx 4.17 million instructions/second

These are theoretical maximums assuming perfect code with no inefficiencies.

B.8 Comparison to Other CPUs

CPU	Avg CPI	Notes
SIRC-1	6.0	Fixed, all instructions
MOS 6502	2-7	Variable by instruction
Motorola 68000	4-158	Highly variable
ARM6	1.0	Single-cycle with pipeline
MIPS R2000	1.0	Single-cycle with pipeline

Table B.2: Cycles Per Instruction Comparison

The SIRC-1's fixed 6-cycle execution makes it slower than pipelined RISC CPUs but more predictable. It's comparable to early microprocessors while being simpler to implement in hardware.

Appendix C

Undocumented Instructions

C.1 Overview

The SIRCIS instruction set includes 12 undocumented instruction opcodes. These opcodes are valid and will execute in hardware, but their behaviour is not officially specified and may vary between CPU implementations or revisions.

Warning: Use of undocumented instructions is not recommended for production code.

C.2 Undocumented Opcode List

Opcode	Format	Pattern	Notes
0x08	Immediate	ADD-like + 0x8	Test variant (no save)
0x09	Immediate	ADC-like + 0x8	Test variant (no save)
0x0B	Immediate	SUB-like + 0x8	Test variant (no save)
0x0D	Immediate	SBC-like + 0x8	Test variant (no save)
0x28	Short Imm	ADD-like + 0x8	Test variant (no save)
0x29	Short Imm	ADC-like + 0x8	Test variant (no save)
0x2B	Short Imm	SUB-like + 0x8	Test variant (no save)
0x2D	Short Imm	SBC-like + 0x8	Test variant (no save)
0x38	Register	ADD-like + 0x8	Test variant (no save)
0x39	Register	ADC-like + 0x8	Test variant (no save)
0x3B	Register	SUB-like + 0x8	Test variant (no save)
0x3D	Register	SBC-like + 0x8	Test variant (no save)

Table C.1: Undocumented Instruction Opcodes

C.3 Likely Behavior

Based on the systematic opcode organization, these undocumented instructions likely behave as "test" variants of arithmetic instructions:

C.3.1 0x08, 0x28, 0x38 (ADD Test)

Probably performs addition but discards the result, only updating flags. Similar to **CMP** but using ADD semantics instead of SUB.

```
1 ; Hypothetical behavior
2 result = operand1 + operand2 ; Calculate
3 ; result is discarded (not written to register)
4 ; Flags updated based on result
```

Utility: Limited. **CMP** already provides comparison functionality.

C.3.2 0x09, 0x29, 0x39 (ADC Test)

Probably performs add-with-carry but discards the result, updating flags.

```
1 ; Hypothetical behavior
2 result = operand1 + operand2 + C
3 ; result is discarded
4 ; Flags updated
```

Utility: Possibly useful for testing carry propagation without modifying registers.

C.3.3 0x0B, 0x2B, 0x3B (SUB Test)

Probably identical to **CMP** (which is already SUB without save).

Utility: None. Use **CMP** instead.

C.3.4 0x0D, 0x2D, 0x3D (SBC Test)

Probably performs subtract-with-borrow but discards the result.

```
1 ; Hypothetical behavior
2 result = operand1 - operand2 - (1 - C)
3 ; result is discarded
4 ; Flags updated
```

Utility: Possibly useful for testing borrow propagation in multi-precision arithmetic.

C.4 Implementation Notes

C.4.1 Current Simulator

In the current SIRC-VM simulator (as of version 1.0):

- Undocumented instructions are recognized and decoded
- They execute following the "test variant" pattern (no write-back)

- Flag updates may or may not be implemented correctly
- Behavior may change in future versions

C.4.2 Hardware Implementation

In a hardware implementation:

- The decoder treats bit 3 = 1 as "don't write back"
- ALU operations still execute normally
- Flags are still updated
- The write-back stage is simply disabled

This means the instructions *will* work, but their exact behavior depends on the hardware implementation details.

C.5 Why Undocumented?

These instructions were left undocumented for several reasons:

1. **Limited utility:** Most have no practical use beyond documented instructions
2. **Incomplete semantics:** The designer hasn't fully defined their behavior
3. **Opcode space reservation:** May be used for future features
4. **Implementation flexibility:** Allows hardware optimizations

C.6 Recommendations

C.6.1 For Application Developers

Do not use undocumented instructions in production code.

- Behavior may change between CPU revisions
- Assemblers may reject them or emit warnings
- Code may not be portable
- Debugging tools may not recognize them

C.6.2 For Compiler Writers

- Do not generate undocumented instructions
- Use only documented instructions for all operations
- If optimization requires new operations, request formal documentation

C.6.3 For Hardware Implementers

- You may implement these opcodes following the logical pattern
- Document any implementation-specific behavior
- Consider reserving them for future standardization

C.6.4 For Researchers/Hackers

If you must experiment with undocumented instructions:

- Test thoroughly on your specific hardware/simulator version
- Document your findings
- Isolate usage in test code, not production
- Be prepared for behavior changes

C.7 Future Standardization

Some undocumented instructions may be formally specified in future SIRCIS revisions. Candidates for standardization include:

- **ADC Test (0x09/0x29/0x39):** For carry flag testing in multi-precision
- **SBC Test (0x0D/0x2D/0x3D):** For borrow flag testing in multi-precision

Others (SUB Test, which duplicates CMP) will likely remain undocumented or be repurposed.

C.8 Opcode Space for Expansion

The SIRCIS instruction set has limited expansion space:

- 12 undocumented opcodes (could be formally specified)
- Reserved shift type (0x111) could enable additional shift modes
- Reserved address register encoding could enable more address modes
- Additional coprocessors could provide extended functionality

Any future expansion must maintain backward compatibility with existing code.