Main features of well U1

True vertical depth (m)

0

500

800

1000

1300

13 ⅝" 5K Wellhead
8,78 m RKB

13 ⅜" Cement data
Class G 1,90 sg

13 ⅜" Surface casing
13 ⅜"x 0,514", 72 lbs N-80
ID: 313,6mm / 12,347"
No centralizers
Shoe @354m MD

Near point with U2 at 500 m MD

PHYLLITE

800M

GRANITTIC
AUGEN GNEISS

12 ¼" hole drilled to 1261,3m MD
(Actual bore hole diameter from 12 ¼" up to 16" between 354 m MD to 825 m MD)
Below 1100m MD: narrow hole < 12 ¼" open hole

9 ½" Open hole to 1288,8m MD

7 ⅞" Open hole to 1306,5m MD

5 ½" open hole to 1324m MD

Rev. 1.3

For further information, please contact:

Kristian Vik	Project Manager	+47 51 87 54 56	E-mail: krvi@norceresearch.no
Per Simensen	Senior Project Manager	+47 51 87 52 81	E-mail: pesi@norceresearch.no

SURVEY DATA (SINGLE SHOT) WELL U1

AHD (M)	INC (DEG)	AZ (DEG)	TVD (M)	E-W (M)	N-S (M)
0.0	0.0	0.0	0.0	0.0	0.0
50.0	1.5	143.7	50.0	0.3	-0.4
100.0	4.4	154.2	99.9	1.6	-2.6
150.0	6.3	153.3	149.7	3.7	-6.9
200.0	7.0	150.7	199.3	6.5	-12.1
250.0	5.5	151.0	249.0	9.2	-17.0
300.0	5.2	155.9	298.8	11.4	-20.9
350.0	4.7	175.7	348.6	12.2	-25.1
400.0	1.7	175.9	398.6	12.3	-27.9
450.0	1.3	173.6	448.5	12.6	-29.1
500.0	1.4	-175.0	498.5	12.2	-29.9
550.0	3.6	-170.4	548.5	12.1	-32.1
600.0	4.5	-149.9	598.4	11.0	-35.4
650.0	2.9	-132.9	648.2	8.8	-37.9
700.0	1.1	-131.8	698.2	7.5	-39.1
750.0	0.2	236.5	748.2	7.2	-39.3
800.0	1.7	-127.8	798.2	6.7	-39.7
850.0	1.8	-112.5	848.2	5.3	-40.7
900.0	1.4	-47.5	898.1	3.9	-40.6
950.0	2.4	50.5	948.1	4.5	-39.3

Professor Olav Hanssensvei 15, N-4068 STAVANGER, Norway.
Phone: (+47) 51 87 50 00 Internet: www.ullrigg.no E-mail: post@norceresearch.no