Main features of well U2

True vertical depth (m)

0

300

500

800

1200

1340

1520

1700

2020

13 ⅝” 5K Wellhead
8,75 m RKB

10 ¾” Wear string
45,5 lbs N-80

13 ⅜” Cement data
Class G 1,61sg lead 1,89sg tail
TOC: Surface

10 ¾” x 9 ⅝” X-over
at 229m MD

9 ⅝” Wear string
47 lbs N-80

First kick-off point at 300m MD

Near point with U1 at 500 m MD

Build-up at 3°/30 m

PHYLLITE

800M

GRANITTIC
AUGEN GNEISS

13 ⅜” Surface casing
13 ⅜”x 0,514”, 72 lbs N-80
ID: 313,6mm / 12,347”

Shoe @1520m MD

17 ½” hole

Tangential section at 60-63°

9 ⅝” bullnose at 2010m MD

12 ¼” hole drilled to 2020m MD

Rev. 1.4

For further information, please contact:

Kristian Vik	Project Manager	+47 51 87 54 56	E-mail: krvi@norceresearch.no
Per Simensen	Senior Project Manager	+47 51 87 52 81	E-mail: pesi@norceresearch.no

SURVEY DATA (MWD) WELL U2

AHD (M)	INC (DEG)	AZ (DEG)	TVD (M)	E-W (M)	N-S (M)
0.0	0.0	0.0	0.0	-1.9	2.3
50.0	0.9	-29.7	50.0	-2.1	2.7
100.0	0.4	-95.1	100.0	-2.6	3.3
150.0	0.7	142.5	150.0	-2.3	2.6
200.0	0.9	58.2	200.0	-1.8	2.5
250.0	0.6	173.2	250.0	-1.7	2.5
300.0	1.3	143.6	300.0	-1.1	2.0
350.0	6.6	155.6	349.8	0.6	-1.4
400.0	11.2	143.7	399.2	4.4	-8.1
450.0	12.7	145.2	448.0	10.8	-17.0
500.0	12.0	150.8	496.9	16.3	-25.8
550.0	12.5	154.7	545.8	21.0	-35.2
600.0	12.2	158.4	594.6	25.3	-45.1
650.0	13.1	159.0	643.4	29.1	-55.1
700.0	14.6	153.9	692.0	33.9	-66.0
750.0	16.2	152.2	740.3	39.7	-77.7
800.0	16.4	146.1	788.3	46.8	-89.8
850.0	20.7	138.3	835.7	56.5	-102.2
900.0	24.6	129.8	881.8	70.5	-115.6
950.0	27.8	123.2	926.6	88.3	-128.6
1000.0	31.0	119.2	970.2	109.2	-141.3
1050.0	32.8	115.6	1012.7	132.6	-153.4
1100.0	36.5	113.7	1053.8	158.6	-164.9
1150.0	38.5	109.1	1093.3	187.0	-176.4
1200.0	40.3	106.5	1132.1	217.2	-185.9
1250.0	43.0	104.0	1169.3	249.3	-194.8
1300.0	46.2	104.0	1204.9	283.4	-203.2
1350.0	50.5	100.6	1238.0	319.8	-212.0
1400.0	52.3	102.4	1269.0	358.1	-220.0
1450.0	55.1	100.5	1298.8	397.5	-227.7
1500.0	58.6	100.2	1326.4	438.6	-235.2
1550.0	61.8	90.6	1351.2	481.8	-238.5
1600.0	61.9	88.8	1374.6	526.0	-238.9
1650.0	63.4	88.4	1397.3	570.4	-237.0
1700.0	60.1	91.7	1420.9	614.5	-237.1
1750.0	57.8	93.5	1446.9	657.2	-239.1
1800.0	57.6	98.9	1473.9	699.0	-243.8
1850.0	58.2	102.7	1500.1	740.8	-251.6
1900.0	59.9	105.8	1526.1	782.2	-262.4
1950.0	60.8	110.5	1550.9	823.4	-276.0
2000.0	61.3	116.6	1575.0	863.5	-295.6

Test Well U2 can be pressured to 326 bar surface pressure with freshwater column in hole.
Test Well U2 was pressure tested to 326 bar 17.12.2021.

Professor Olav Hanssensvei 15, N-4068 STAVANGER, Norway.
Phone: (+47) 51 87 50 00 Internet: www.ullrigg.no E-mail: post@norceresearch.no