

Descriptive Analysis

R for Stata Users

Luiza Andrade, Rob Marty, Rony Rodriguez-Ramirez, Luis Eduardo San Martin, Leonardo Viotti, Marc-Andrea Fiorina

DIME |The World Bank

27 March 2023



Introduction

Initial Setup

If You Attended Session 2

If You Did Not Attend Session 2

-
1. Go to the `dime-r-training-mar2023` folder that you created yesterday, and open the `dime-r-training-mar2023` R project that you created there.

Introduction

Initial Setup

If You Attended Session 2

If You Did Not Attend Session 2

1. Create a folder named `dime-r-training-mar2023` in your preferred location in your computer.
2. Go to the [OSF page of the course](#) and download the file in: `R for Stata Users - 2023 March` > `Data` > `dime-r-training-mar2023.zip`.
3. Unzip `dime-r-training-mar2023.zip`.
4. Open the `dime-r-training-mar2023` R project.


Table of contents

1. Quick summary statistics
2. Descriptive statistics tables
3. Exporting descriptive statistics tables
4. Formatting tables
5. Aggregating observations
6. Running regressions
7. Exporting regression tables

Workflows for outputs


Not reproducible


Anything that requires

 Copy-pasting

 Manual formatting after exported

Reproducible

 R Markdown: dynamic document containing code and text that is exported directly from R into PDF, HTML, Word, Power Point and other formats

 LaTeX: typesetting system used for scientific publications that automatically reloads tables and figures every time the document is rendered

Setting the stage

Load the packages that we will use today

```
# Install new packages  
install.packages("modelsummary")  
install.packages("fixest")  
install.packages("janitor")  
install.packages("huxtable")  
install.packages("openxlsx")
```

```
# Load packages  
library(here)  
library(tidyverse)  
library(modelsummary)  
library(fixest)  
library(janitor)  
library(huxtable)  
library(openxlsx)
```

Setting the stage

Load the data that we will use today: Stata's `census` dataset

```
# Load data
census <-
  read_rds(
    here(
      "DataWork",
      "DataSets",
      "Final",
      "census.rds"
    )
  )
```

02:00

Taking a peek at the data

```
glimpse(census)
```

```
## Rows: 50
## Columns: 13
## $ state      <chr> "Alabama", "Alaska", "Arizona", "Arkansas", "California", "Co...
## $ state2     <chr> "AL", "AK", "AZ", "AR", "CA", "CO", "CT", "DE", "FL", "GA", "...
## $ region     <fct> South, West, West, South, West, West, NE, South, South, South...
## $ pop        <int> 3893888, 401851, 2718215, 2286435, 23667902, 2889964, 3107576...
## $ poplt5     <int> 296412, 38949, 213883, 175592, 1708400, 216495, 185188, 41151...
## $ pop5_17    <int> 865836, 91796, 577604, 495782, 4680558, 592318, 637731, 12544...
## $ pop18p     <int> 2731640, 271106, 1926728, 1615061, 17278944, 2081151, 2284657...
## $ pop65p     <int> 440015, 11547, 307362, 312477, 2414250, 247325, 364864, 59179...
## $ popurban   <int> 2337713, 258567, 2278728, 1179556, 21607606, 2329869, 2449774...
## $ medage     <dbl> 29.3, 26.1, 29.2, 30.6, 29.9, 28.6, 32.0, 29.8, 34.7, 28.7, 2...
## $ death      <int> 35305, 1604, 21226, 22676, 186428, 18925, 26005, 5123, 104190...
## $ marriage   <int> 49018, 5361, 30223, 26513, 210864, 34917, 26048, 4437, 108344...
## $ divorce    <int> 26745, 3517, 19908, 15882, 133541, 18571, 13488, 2313, 71579,...
```


Quick summary statistics

Exploring a dataset

```
summary(x, digits)
```

Equivalent to Stata's `codebook`. Its arguments are:

- **x**: the object you want to summarize, usually a vector or data frame
- *digits*: the number of decimal digits to be displayed

Exercise 1

Use the `summary()` function to describe the `census` data frame.

00:45

Exploring a dataset

```
summary(census)
```

```
##      state      state2      region      pop
## Length:50      Length:50      NE      : 9      Min.    : 401851
## Class :character Class :character N Cntrl:12      1st Qu.: 1169218
## Mode  :character Mode  :character South  :16      Median : 3066433
##                                           West   :13      Mean   : 4518149
##                                           3rd Qu.: 5434033
##                                           Max.   :23667902
##      poplt5      pop5_17      pop18p      pop65p
## Min.    : 35998      Min.    : 91796      Min.    : 271106      Min.    : 11547
## 1st Qu.: 98831      1st Qu.: 257949      1st Qu.: 823702      1st Qu.: 118660
## Median : 227468      Median : 629654      Median : 2175130      Median : 370495
## Mean    : 326278      Mean    : 945952      Mean    : 3245920      Mean    : 509503
## 3rd Qu.: 361321      3rd Qu.:1143292      3rd Qu.: 3858173      3rd Qu.: 580087
## Max.    :1708400      Max.    :4680558      Max.    :17278944      Max.    :2414250
##      popurban      medage      death      marriage
## Min.    : 172735      Min.    :24.20      Min.    : 1604      Min.    : 4437
## 1st Qu.: 826651      1st Qu.:28.73      1st Qu.: 9087      1st Qu.: 14840
## Median : 2156905      Median :29.75      Median : 26177      Median : 36279
## Mean    : 3328253      Mean    :29.54      Mean    : 39474      Mean    : 47701
## 3rd Qu.: 3403450      3rd Qu.:30.20      3rd Qu.: 46533      3rd Qu.: 57338
## Max.    :21607606      Max.    :34.70      Max.    :186428      Max.    :210864
##      divorce
## Min.    : 2142
## 1st Qu.: 6898
## Median : 17113
## Mean    : 23679
## 3rd Qu.: 27987
## Max.    :133541
```

Summarizing continuous variables

- `summary()` can also be used with a single variable.
- When used with continuous variables, it works similarly to `summarize` in Stata.
- When used with categorical variables, it works similarly to `tabulate`.

Summarizing continuous variables

Exercise 2

Use the `summary()` function to display summary statistics for a continuous variable in the `census` data frame.

00:45

Summarizing continuous variables

Exercise 3

Use the `summary()` function to display summary statistics for a continuous variable in the `census` data frame.

```
summary(census$pop)
```

```
##      Min.   1st Qu.   Median     Mean  3rd Qu.     Max.
##  401851  1169218  3066433  4518149  5434033 23667902
```

Summarizing categorical variables

`tabyl()`

Equivalent to `tabulate` in Stata, creates a frequency table. Its main arguments are vectors to be tabulated.

Exercise 4

Use the `tabyl()` function to display frequency tables for:

1. The variable `region` in the `census` data frame
2. The variables `region` and `state` in the `census` data frame, simultaneously

01:00

Summarizing categorical variables

One way tabulation

```
census %>%  
  tabyl(region)
```

region	n	percent
NE	9	0.18
N Cntrl	12	0.24
South	16	0.32
West	13	0.26

Summarizing categorical variables

Two way tabulation

```
census %>%  
  tabyl(state, region)
```

state	NE	N Cntrl	South	West
Alabama	0	0	1	0
Alaska	0	0	0	1
Arizona	0	0	0	1
Arkansas	0	0	1	0
California	0	0	0	1
Colorado	0	0	0	1
Connecticut	1	0	0	0

Descriptives tables

Descriptives tables

What if you want to...

- ...export the summary statistics to another software?
- ...customize which statistics to display?
- ...format the table?

Well, then you will need a few more packages

- There are many packages that can be used both for displaying and exporting summary statistics
- Today we will show you a combination of two packages: `modelsummary` and `huxtable`
- We chose this combination because together, they can perform all the tasks we are interested in
- In fact, `modelsummary` can perform most of them by itself -- with the exception of exporting formatted tables to Excel

Exploring datasets with *modelsummary*

The package *modelsummary* contains a family of functions called `datasummary` which can be used to create different types of summary statistics tables. These include:

- `datasummary_skim`, to create descriptive statistics tables
- `datasummary_balance`, to create balance tables
- `datasummary_correlation`, to create a correlation table
- `datasummary_crosstab`, to create a twoway tabulation
- `datasummary`, to create customized descriptive statistics tables

Exploring datasets with *modelsummary*

`datasummary_skim()`

- **data:** the data set to be summarized, the only required argument
- *output:* the type of output desired
- ...: additional options allow for formatting customization, such as including notes and titles

```
datasummary_skim(  
  data,  
  type = "numeric",  
  output = "default",  
  histogram = TRUE,  
  title = NULL,  
  notes = NULL,  
  ...  
)
```

Exploring datasets with *modelsummary*




Exercise 5

Use `datasummary_skim()` to create a descriptive statistics table for the `census` data.

00:45

Exploring datasets with *modelsummary*

```
datasummary_skim(census)
```

	Unique (#)	Missing (%)	Mean	SD	Min	Median	Max	
pop	50	0	4518149.4	4715037.8	401851.0	3066433.0	23667902.0	
poplt5	50	0	326277.8	331585.1	35998.0	227467.5	1708400.0	
pop5_17	50	0	945951.6	959372.8	91796.0	629654.0	4680558.0	
pop18p	50	0	3245920.1	3430531.3	271106.0	2175130.0	17278944.0	
pop65p	50	0	509502.8	538932.4	11547.0	370495.0	2414250.0	
popurban	50	0	3328253.2	4090177.9	172735.0	2156905.0	21607606.0	
medage	37	0	29.5	1.7	24.2	29.8	34.7	
death	50	0	39474.3	41742.3	1604.0	26176.5	186428.0	
marriage	50	0	47701.4	45130.4	4437.0	36279.0	210864.0	
divorce	50	0	23679.4	25094.0	2142.0	17112.5	133541.0	

Exploring datasets with *modelsummary*

- *modelsummary* summarizes only numeric variables by default.
- To summarize categorical variables, use the argument `type`

```
datasummary_skim(census, type = "categorical")
```

data	N	%
NE	9	18.0
N Cntrl	12	24.0
South	16	32.0
West	13	26.0

Exploring datasets with *modelsummary*

You can also customize the variables and statistics to include using a **formula** with the `datasummary()` function.

`datasummary()`

- **formula:** a two-sided formula to describe the table: rows ~ columns
- **data:** the data set to be summarized
- *output:* the type of output desired
- ...: additional options allow for formatting customization

```
datasummary(  
  var1 + var2 + var3 ~ stat1 + stat2 + stat3 + stat4,  
  data = data  
)
```

Exploring datasets with *modelsummary*

Exercise 6

Create a table showing the number of observations, mean, standard deviation, minimum, maximum and median value for all the population, number of deaths, number of marriage and number of divorces in the `census` data.

```
datasummary(  
  var1 + var2 + var3 ~ stat1 + stat2 + stat3 + stat4,  
  data = data  
)
```

Tip: some of the allowed statistics are N, Mean, SD, Min, Max, Median, P0, P25, P50, P75, P100, Histogram

01:30

Exploring datasets with *modelsummary*

```
datasummary(  
  pop + death + marriage + divorce ~ N + Mean + SD + Median + Min + Max,  
  data = census  
)
```

	N	Mean	SD	Median	Min	Max
pop	50	4518149.44	4715037.75	3066433.00	401851.00	23667902.00
death	50	39474.26	41742.35	26176.50	1604.00	186428.00
marriage	50	47701.40	45130.42	36279.00	4437.00	210864.00
divorce	50	23679.44	25094.01	17112.50	2142.00	133541.00

Exploring datasets with *modelsummary*

```
datasummary(  
  All(census) ~ N + Mean + SD + Median + Min + Max,  
  data = census  
)
```

	N	Mean	SD	Median	Min	Max
pop	50	4518149.44	4715037.75	3066433.00	401851.00	23667902.00
poplt5	50	326277.78	331585.14	227467.50	35998.00	1708400.00
pop5_17	50	945951.60	959372.83	629654.00	91796.00	4680558.00
pop18p	50	3245920.06	3430531.31	2175130.00	271106.00	17278944.00
pop65p	50	509502.80	538932.38	370495.00	11547.00	2414250.00
popurban	50	3328253.18	4090177.93	2156905.00	172735.00	21607606.00
medage	50	29.54	1.69	29.75	24.20	34.70
death	50	39474.26	41742.35	26176.50	1604.00	186428.00
marriage	50	47701.40	45130.42	36279.00	4437.00	210864.00
divorce	50	23679.44	25094.01	17112.50	2142.00	133541.00

Balance tables with *modelsummary*

```
census_rct <-  
  census %>%  
  mutate(  
    treatment = as.numeric(runif(n()) > 0.5)  
  ) %>%  
  select(  
    -starts_with("state")  
  )  
  
datasummary_balance(  
  ~ treatment,  
  data = census_rct  
)
```

Balance tables with *modelsummary*

		0		1			
		Mean	Std. Dev.	Mean	Std. Dev.	Diff. in Means	Std. Error
pop		5340096.3	5517931.5	3553255.3	3424883.0	-1786841.1	1279718.7
poplt5		375358.9	376855.3	268660.8	265738.6	-106698.1	91270.5
pop5_17		1101506.9	1103227.8	763343.2	739601.6	-338163.7	262414.3
pop18p		3863230.6	4043212.3	2521251.2	2423884.2	-1341979.3	927852.1
pop65p		613940.5	643906.1	386902.0	357501.3	-227038.4	144613.1
popurban		4017263.7	4868323.3	2519414.8	2825761.8	-1497848.9	1106783.5
medage		29.9	1.6	29.1	1.7	-0.9	0.5
death		47395.1	49542.4	30175.9	28508.7	-17219.2	11235.8
marriage		55210.6	48418.7	38886.2	40191.3	-16324.4	12532.4
divorce		27510.2	27920.2	19182.5	21026.4	-8327.7	6935.0
		N	Pct.	N	Pct.		
region	NE	5	18.5	4	17.4		
	N Cntrl	5	18.5	7	30.4		
	South	9	33.3	7	30.4		
	West	8	29.6	5	21.7		

Exporting tables

Exporting *modelsummary* table to LaTeX

To export the tables we created, we can simply use the option `output`:

```
descriptives <-  
  All(census) ~ N + Mean + SD + Median + Min + Max  
  
datasummary(  
  descriptives,  
  data = census,  
  output = here( # file path to output file  
    "DataWork",  
    "Output",  
    "Raw",  
    "summary-stats.tex"  
  )  
)
```


Exporting *modelsummary* table

Other valid output formats include:

- `.docx`
- `.pptx`
- `.html`
- `.md`

Exporting *modelsummary* table

Other valid output formats include:

- `.docx`
- `.pptx`
- `.html`
- `.md`
- ... but not `.xls`

Exporting *modelsummary* table to Excel

- To export the table to Excel, we will first convert it into an object of type *huxtable*
- **huxtable** is another R package, one that allows not only for exporting tables, but also for extensive customization
- Before getting to the customization part, however, let's export this table:

```
# Create the huxtable object
summary_stats_table <-
  datasummary(
    descriptives,
    data = census,
    output = "huxtable"
  )

# Export it to Excel
quick_xlsx(
  summary_stats_table, # object to be exported
  file = here( # file path to output file
    "DataWork",
    "Output",
    "Raw",
    "summary-stats.xlsx"
  )
)
```

Exporting tables

A similar code can also export the same table to a self-standing LaTeX document

```
# Export to LaTeX
quick_latex(
  summary_stats_table,
  file = here(
    "DataWork",
    "Output",
    "Raw",
    "summary-stats.tex"
  )
)
```

Exporting tables to different Excel tabs

```
# Start a new workbook
wb <- createWorkbook()

# Add one sheet to it
wb <-
  as_Workbook(
    summary_stats_table,
    Workbook = wb,
    sheet = "Summary stats"
  )

# Add another sheet to it
wb <-
  as_Workbook(
    hux("Mock", "table"),
    Workbook = wb,
    sheet = "Other sheet"
  )

# Save the workbook
saveWorkbook(
  wb, # object to be saved
  file = here( # file path to output file
    "DataWork",
    "Output",
    "Raw",
    "summary-stats.xlsx"
  ),
  overwrite = TRUE # replace existing file
)
```

Exporting tables to LaTeX fragment

```
summary_stats_table %>%  
  print_latex() %>% # See LaTeX code  
  # Save LaTeX code  
  capture.output(  
    file = here(  
      "DataWork",  
      "Output",  
      "Raw",  
      "summary-stats.tex"  
    )  
  )
```

You will also need to load the required LaTeX packages. To copy the code that creates a preamble with all of them, use this code:

```
report_latex_dependencies()
```

Formatting tables

Beautifying tables

- `huxtable` also allows you to customize table formatting so it can be exported with the same layout to multiple software
- Before we do that, however, we will create a version of the data where the variable names are the Stata labels

```
# Extract variable labels from data frame
labels <- names(census)
names(labels) <- attributes(census)$var.labels

# Rename the variables
census_labelled <-
  census %>%
  rename(
    labels
  )

# Create a labelled summary table
summary_stats_table <-
  datasummary(
    All(census_labelled) ~ N + Mean + SD + Median + Min + Max,
    data = census_labelled,
    output = "huxtable"
  )
```


Beautifying tables

The code below shows the table `summary_stats_table` can be formatted

```
# Format table
summary_stats_table %>%
  # Use first row as table header
  set_header_rows(1, TRUE) %>%
  # Use first column as row header
  set_header_cols(1, TRUE) %>%
  # Don't round large numbers
  set_number_format(everywhere, 2:ncol(.), "%9.0f") %>%
  # Centralize cells in first row
  set_align(1, everywhere, "center") %>%
  # Set a theme for quick formatting
  theme_basic()
```

	N	Mean	SD	Median	Min	Max
Population	50	4518149	4715038	3066433	401851	23667902
Pop, < 5 year	50	326278	331585	227468	35998	1708400
Pop, 5 to 17 years	50	945952	959373	629654	91796	4680558
Pop, 18 and older	50	3245920	3430531	2175130	271106	17278944
Pop, 65 and older	50	509503	538932	370495	11547	2414250
Urban population	50	3328253	4090178	2156905	172735	21607606
Median age	50	30	2	30	24	35
Number of deaths	50	39474	41742	26177	1604	186428
Number of marriages	50	47701	45130	36279	4437	210864
Number of divorces	50	23679	25094	17113	2142	133541

Export beautified tables

```
# Format table
summary_stats_table <-
  summary_stats_table %>%
  set_header_rows(1, TRUE) %>% # Use first row as table header
  set_header_cols(1, TRUE) %>% # Use first column as row header
  set_number_format(everywhere, 2:ncol(.), "%9.0f") %>% # Don't round large numbers
  set_align(1, everywhere, "center") %>% # Centralize cells in first row
  theme_basic() # Set a theme for quick formatting

quick_xlsx(
  summary_stats_table,
  file = here(
    "DataWork",
    "Output",
    "Raw",
    "summary-stats-basic.xlsx"
  )
)
```

Export beautified tables

Before

	A	B	C	D	E	F
1	skim_varia	Mean	Median	SD	Min	Max
2	pop	4520000	3070000	4720000	402000	23700000
3	poplt5	326000	227000	332000	36000	1710000
4	pop5_17	946000	630000	959000	91800	4680000
5	pop18p	3250000	2180000	3430000	271000	17300000
6	pop65p	510000	370000	539000	11500	2410000
7	popurban	3330000	2160000	4090000	173000	21600000
8	medage	29.5	29.8	1.69	24.2	34.7
9	death	39500	26200	41700	1600	186000
10	marriage	47700	36300	45100	4440	211000
11	divorce	23700	17100	25100	2140	134000

After

	A	B	C	D	E	F	G
1		N	Mean	SD	Median	Min	Max
2	Population	50	4518149	4715038	3066433	401851	23667902
3	Pop, < 5 year	50	326278	331585	227468	35998	1708400
4	Pop, 5 to 17 years	50	945952	959373	629654	91796	4680558
5	Pop, 18 and older	50	3245920	3430531	2175130	271106	17278944
6	Pop, 65 and older	50	509503	538932	370495	11547	2414250
7	Urban population	50	3328253	4090178	2156905	172735	21607606
8	Median age	50	30	2	30	24	35
9	Number of deaths	50	39474	41742	26177	1604	186428
10	Number of marriages	50	47701	45130	36279	4437	210864
11	Number of divorces	50	23679	25094	17113	2142	133541

Other themes to play with

jams

Type	Price	Sugar content
Strawberry	1.90	40.00%
Raspberry	2.10	35.00%
Plum	1.80	50.00%

theme_plain

Type	Price	Sugar content
Strawberry	1.90	40.00%
Raspberry	2.10	35.00%
Plum	1.80	50.00%

theme_basic

Type	Price	Sugar content
Strawberry	1.90	40.00%
Raspberry	2.10	35.00%
Plum	1.80	50.00%

theme_compact

Type	Price	Sugar content
Strawberry	1.90	40.00%
Raspberry	2.10	35.00%
Plum	1.80	50.00%

theme_article

Type	Price	Sugar content
Strawberry	1.90	40.00%
Raspberry	2.10	35.00%
Plum	1.80	50.00%

theme_bright

Type	Price	Sugar content
Strawberry	1.90	40.00%
Raspberry	2.10	35.00%
Plum	1.80	50.00%

theme_grey

Type	Price	Sugar content
Strawberry	1.90	40.00%
Raspberry	2.10	35.00%
Plum	1.80	50.00%

theme_blue

Type	Price	Sugar content
Strawberry	1.90	40.00%
Raspberry	2.10	35.00%
Plum	1.80	50.00%

theme_green

Type	Price	Sugar content
Strawberry	1.90	40.00%
Raspberry	2.10	35.00%
Plum	1.80	50.00%

theme_mondrian

Type	Price	Sugar content
Strawberry	1.90	40.00%
Raspberry	2.10	35.00%
Plum	1.80	50.00%

theme_orange

Type	Price	Sugar content
Strawberry	1.90	40.00%
Raspberry	2.10	35.00%
Plum	1.80	50.00%

theme_stripped

Type	Price	Sugar content
Strawberry	1.90	40.00%
Raspberry	2.10	35.00%
Plum	1.80	50.00%

Ok, can we run some regressions now?!

Running regressions

The base R command for linear regressions is called `lm`

`lm(formula, data, subset, weights, ...)`

- **formula:** an object of class "formula" containing a symbolic description of the model
- **data:** a data frame containing the variables indicated in the formula
- *subset:* an optional vector specifying a subset of observations to be used in the regression
- *weights:* an optional vector of weights to be used in the regression

Formulas can take three specifications:

- `y ~ x1 + x2` regresses variable `y` on covariates `x1` and `x2`
- `y ~ x1:x2` regresses variable `y` on the interaction of covariates `x1` and `x2`
- `y ~ x1*x2` is equivalent to `y ~ x1 + x2 + x1:x2`

Running regressions

Exercise 7

Using the `census` data, run a regression of the number of divorces on population, urban population and number of marriages.

```
lm(y ~ x1 + x2,  
    data)
```

01:00

Running regressions

Exercise 8

Using the `census` data, run a regression of the number of divorces on population, urban population and number of marriages.

```
reg1 <-  
  lm(  
    divorce ~ pop + popurban + marriage,  
    census  
  )
```


Running regressions

- The output of regression commands is a list of relevant information.
- By default, it prints only a small portion of this information.
- The best way to visualize results is to store this list in an object and then access its contents using the function `summary`

Running regressions

```
reg1 <-  
  lm(  
    divorce ~ pop + popurban + marriage,  
    census  
  )  
  
summary(reg1)  
  
##  
## Call:  
## lm(formula = divorce ~ pop + popurban + marriage, data = census)  
##  
## Residuals:  
##      Min       1Q   Median       3Q      Max   
## -22892.3  -1665.1    796.5   4138.0  17212.2   
##  
## Coefficients:  
##              Estimate Std. Error t value Pr(>|t|)      
## (Intercept)  1.207e+02  1.838e+03   0.066   0.948      
## pop          1.044e-03  1.633e-03   0.639   0.526      
## popurban     1.954e-03  1.796e-03   1.088   0.282      
## marriage     2.587e-01  5.958e-02   4.342  7.7e-05 ***  
## ---  
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1  
##  
## Residual standard error: 7466 on 46 degrees of freedom  
## Multiple R-squared:  0.9169,    Adjusted R-squared:  0.9115   
## F-statistic: 169.2 on 3 and 46 DF,  p-value: < 2.2e-16
```

Running regressions

The `feols` command from package `fixest` allows for more flexibility in model specification

`feols(formula, data, subset, weights, ...)`

- **formula:** an object of class "formula" containing a symbolic description of the model
- **data:** a data frame containing the variables indicated in the formula
- **vcov:** one of "iid", "hetero" (or "HC1"), "cluster", "twoway", "NW" (or "newey_west"), "DK" (or "driscoll_kraay"), or "conley"
- **subset:** an optional vector specifying a subset of observations to be used in the regression
- **weights:** an optional vector of weights to be used in the regression
- **cluster:** a list of vectors, a character vector of variable names, a formula or an integer vector specifying how to cluster standard errors
- ...

Running regressions

Formulas for `feols` are more complex, and take the following format: `y ~ x1 + x2 | fe1 + fe2 | x3 ~ iv3`

- `y ~ x1 + x2` takes all the same formulas as `lm`
- `fe1 + fe2` list the variables to be included as fixed effects
- `x3 ~ iv3` uses instrument `iv3` for variable `x3`

Running regressions

Exercise 9

Using the `census` data, run a regression of the number of divorces on population, urban population and number of marriages controlling for region fixed effects.

```
feols(  
  y ~ x1 + x2 | fe1 + fe2,  
  data  
)
```

01:00

Running regressions

Exercise 10

Using the `census` data, run a regression of divorce on population, urban population and number of marriages controlling for region fixed effects.

```
reg2 <-  
  feols(  
    divorce ~ pop + popurban + marriage | region,  
    census,  
    se = "iid"  
  )  
  
summary(reg2)
```

Running regressions

```
reg2 <-  
  feols(  
    divorce ~ pop + popurban + marriage | region,  
    census,  
    se = "iid"  
  )  
  
summary(reg2)
```

```
## OLS estimation, Dep. Var.: divorce
```

```
## Observations: 50
```

```
## Fixed-effects: region: 4
```

```
## Standard-errors: IID
```

```
##           Estimate Std. Error  t value  Pr(>|t|)
```

```
## pop          0.000395   0.001788  0.220981  0.8261531
```

```
## popurban 0.003553   0.001998  1.778249  0.0824344 .
```

```
## marriage 0.183659   0.058027  3.165064  0.0028471 **
```

```
## ---
```

```
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
## RMSE: 6,257.6      Adj. R2: 0.927695
```

```
##                Within R2: 0.935434
```

Some notes on regressions

- Whenever a factor is included in the list of covariates, it is treated as a categorical variable, i.e., as if you had written `i.x` in Stata.
- Whenever a boolean is included in the list of covariates, it is treated as a dummy variable, where `TRUE` is `1` and `FALSE` is `0`.

Exporting regression tables

Exporting regression tables

`huxtable` also has a quick wrapper for regression tables

`huxreg(...)`

- `...`: Models, or a single list of models. Names will be used as column headings.
- `number_format`: Format for numbering. See `number_format()` for details.
- `stars`: Levels for p value stars.
- `bold_signif`: Where p values are below this number, cells will be displayed in bold.
- `note`: Footnote for bottom cell, which spans all columns.
- `statistics`: A vector of summary statistics to display.
- `coefs`: A vector of coefficients to display. To change display names, name the coef vector: `c("Displayed title" = "coefficient_name", ...)`

Exporting regression tables

```
huxreg(reg1, reg2)
```

	(1)	(2)
(Intercept)	120.730	
	(1838.216)	
pop	0.001	0.000
	(0.002)	(0.002)
popurban	0.002	0.004
	(0.002)	(0.002)
marriage	0.259 ***	0.184 **
	(0.060)	(0.058)
N	50	50
R2	0.917	0.937
logLik	-514.766	-508.024
AIC	1039.531	1030.048
*** p < 0.001; ** p < 0.01; * p < 0.05.		

Formatting regression tables

```
huxreg(  
  reg1, reg2,  
  # Show variable labels instead of names  
  coefs = c(  
    "Population" = "pop",  
    "Urban population" = "popurban",  
    "Number of marriages" = "marriage"  
  ),  
  statistics = c("N. obs." = "nobs")) %>%  
  add_rows(  
    c("Region FE", "No", "Yes"),  
    after = 7  
  )
```

	(1)	(2)
Population	0.001 (0.002)	0.000 (0.002)
Urban population	0.002 (0.002)	0.004 (0.002)
Number of marriages	0.259 *** (0.060)	0.184 ** (0.058)
Region FE	No	Yes
N. obs.	50	50
*** p < 0.001; ** p < 0.01; * p < 0.05.		

Exporting regression tables

Exercise 11

Export a regression table with the results of your estimations using `lm` and `feols`:

- Use `huxreg` to combine `reg1` and `reg2`.
- Use `quick_xlsx` or `quick_latex` to export the output of `huxreg` to your preferred format.

References and recommendations

- Econometrics with R <https://www.econometrics-with-r.org/index.html>
- `modelsummary` documentation: <https://vincentarelbundock.github.io/modelsummary/index.html>
- Introduction to `huxtable`: <https://cran.r-project.org/web/packages/huxtable/vignettes/huxtable.html>
- Using `huxtable` for regression tables: <https://cran.r-project.org/web/packages/huxtable/vignettes/huxreg.html>
- Sample code for tables in R: <https://github.com/RRMaximiliano/r-latex-tables-sum-stats>
- More sample code for tables in R: <https://evalsp20.classes.andrewheiss.com/reference/regtables/>
- Johns Hopkins Exploratory Data Analysis at Coursera: <https://www.coursera.org/learn/exploratory-data-analysis>
- Udacity's Data Analysis with R: <https://www.udacity.com/course/data-analysis-with-r--ud651>

Since we talked about LaTeX so much...

- DIME LaTeX templates and trainings: <https://github.com/worldbank/DIME-LaTeX-Templates>
- All you need to know about LaTeX: <https://en.wikibooks.org/wiki/LaTeX>

Thank you!

Appendix

Aggregating observations

Aggregating observations

- If you want to show aggregated statistics, the function `summarise` is a powerful tool.
- It is similar to `datasummary` in that it calculates a series of statistics for a data frame.
- However, it does not have pre-defined statistics, so it requires more manual input.
- On the other hand, its output is a regular data frame, so it is also useful to create constructed data sets.
- Its Stata equivalent would be `collapse`

Aggregating observations

```
summarise(.data, ...,)
```

- **data**: the data frame to be summarized
- **...**: Name-value pairs of summary functions. The name will be the name of the variable in the result.

The "name-value" pairs mentioned under `...` look like this: `new_variable = function(existing_variable)`, where possible functions include:

- Center: `mean()`, `median()`
- Spread: `sd()`, `IQR()`, `mad()`
- Range: `min()`, `max()`, `quantile()`
- Count: `n()`, `n_distinct()`

Aggregating observations

```
region_stats <-  
  census %>%  
  group_by(region) %>%  
  summarise(  
    `Number of States` = n_distinct(state),  
    `Total Population` = sum(pop)  
  )
```

region	Number of States	Total Population
NE	9	49135283
N Cntrl	12	58865670
South	16	74734029
West	13	43172490

Aggregating observations

Exercise 12

Recreate the `region_stats` data set, now including the average and the standard deviation of the population.

01:30

Aggregating observations

```
region_stats <-  
  census %>%  
  group_by(region) %>%  
  summarise(  
    `Number of States` = n_distinct(state),  
    `Total Population` = sum(pop),  
    `Average Population` = mean(pop),  
    `SD of Population` = sd(pop)  
  )
```

region	Number of States	Total Population	Average Population	SD of Population
NE	9	49135283	5459476	5925235
N Cntrl	12	58865670	4905473	3750094
South	16	74734029	4670877	3277853
West	13	43172490	3320961	6217177

Aggregating observations

Exercise 13

Use `huxtable` to format and export the object `region_stats`.

02:00

Aggregating observations

```
region_stats_table <-  
  region_stats %>%  
  rename(Region = region) %>%  
  as_hux %>%  
  set_header_cols("Region", TRUE) %>%  
  theme_bright()  
  
quick_xlsx(  
  region_stats_table,  
  file = here(  
    "DataWork",  
    "Output",  
    "Raw",  
    "region-stats.xlsx"  
  )  
)
```