2011 18th IEEE International Conference on Image Processing (ICIP) • Brussels, Belgium
DOI: 10.1109/ICIP.2011.6116200 • pp. 2609–2612

Robust Text Detection in Natural Images with Edge-Enhanced Maximally Stable Extremal Regions

Huizhong Chen[1], Sam S. Tsai[1], Georg Schroth[2], David M. Chen[1], Radek Grzeszczuk[3], Bernd Girod[1]

[1]Department of Electrical Engineering, Stanford University, Stanford, CA 94305, USA

[2]Institute for Media Technology, Technische Universität München, Germany

[3]Nokia Research Center, Palo Alto, CA, USA

Email: {hchen2, sstsai, dmchen, bgirod}@stanford.edu, georg.schroth@tum.de

Abstract—Detecting and recognizing text in natural camera-captured images is an essential prerequisite for mobile visual search, assistive reading systems, and autonomous navigation. Unlike scanned document pages, natural scene images present severe challenges including complex background clutter, uneven illumination, optical blur, perspective distortion, and wide variations in font scale and orientation. In this paper, we propose a fast and robust classical image processing algorithm for scene text detection and Optical Character Recognition (OCR) preparation. First, we introduce Edge-Enhanced Maximally Stable Extremal Regions (MSER), which combines the illumination invariance of MSER with Canny edge constraints to prevent adjacent blurred characters from merging. Second, we formulate an exact, computationally efficient Stroke Width Transform (SWT) using the Euclidean Distance Transform and pre-computed 3 × 3 Look-Up Tables (LUTs) to reject non-text clutter based on stroke width consistency. Finally, character candidates are paired into text lines and segmented into word patches for Tesseract OCR recognition. Evaluations on the standard ICDAR Robust Reading Competition benchmark demonstrate state-of-the-art precision (0.73), recall (0.60), and F-measure (0.66).

Keywords—Scene Text Detection; Optical Character Recognition (OCR); Maximally Stable Extremal Regions (MSER); Canny Edge Detector; Stroke Width Transform; Distance Transform.

I. INTRODUCTION

Embedded text in natural images carries high-level semantic information for visual indexing, license plate reading, street sign translation, and mobile document capture [1]. Directly feeding a natural scene image into a standard Optical Character Recognition (OCR) engine produces near-zero recognition accuracy because background textures (such as foliage, bricks, fences, and shadows) overwhelm the OCR binarization and layout analysis stages [2]. Consequently, an effective scene text recognition pipeline requires a robust preprocessing and text localization framework that isolates character regions into clean, binarized word masks before invoking the OCR engine.

Classical approaches to text detection in images fall into two primary categories: texture-based sliding-window methods and connected-component (CC) methods **[1]**. Texture-based methods extract local frequency features (such as Gabor filters, wavelets, or discrete cosine transform coefficients) across multi-scale windows, which incurs high computational cost. Conversely, connected-component methods segment candidate character glyphs directly at the pixel level. Epshtein et al. **[3]** introduced the Stroke Width Transform (SWT), which searches for parallel Canny edge pairs along gradient directions; however, SWT fails when noisy or broken edge gradients deflect the search rays. Meanwhile, Matas et al. **[4]** proposed Maximally Stable Extremal Regions (MSER), which extracts affine-invariant intensity regions across all threshold levels, but pure MSER degrades severely under motion blur or low spatial resolution where neighboring letters bleed together.

To overcome these complementary weaknesses, we propose a hybrid five-stage classical image processing pipeline: (1) Edge-Enhanced MSER extraction; (2) Geometric connected-component filtering; (3) Distance-transform-based Stroke Width filtering; (4) Text line and word aggregation; and (5) Binarized OCR recognition.

II. PROPOSED METHODOLOGY

Our complete text detection and preprocessing system processes an input RGB image by simultaneously analyzing connected extremal regions and local spatial gradients.

A. Stage 1: Edge-Enhanced MSER Extraction

An extremal region of a grayscale image $I(x, y)$ is a connected component of thresholded pixels whose intensities are either strictly greater than (bright text on dark background) or strictly less than (dark text on bright background) all surrounding boundary pixels **[4]**. Let $Q_1, \ldots, Q_t, \ldots$ denote a nested sequence of extremal regions across intensity thresholds $t \in [0, 255]$. An extremal region Q_{t^*} is defined as maximally stable if the relative area growth rate $q(t)$ reaches a local minimum at t^*:

$$q(t) = |Q_{t+\Delta} \setminus Q_{t-\Delta}| \,/\, |Q_t| \tag{1}$$

where $|\cdot|$ denotes the cardinality (area in pixels) and Δ is the stability margin parameter. Although MSER reliably detects character regions under uneven lighting, optical blur softens inter-character gaps, causing MSER regions to spill across character boundaries and merge whole words into single blobs.

To prevent boundary spillage, we combine MSER with the Canny edge detector **[5]**. Specifically, for each detected MSER mask, we compute the spatial image gradient vector $\nabla I = [I_x, I_y]^T$ and trace Canny edges. We then prune the outer perimeter of the MSER binary region along the detected Canny edge pixels guided by the gradient direction pointing from the background toward the foreground stroke interior. This Edge-Enhanced MSER step cleanly separates touching characters and produces crisp binary character candidates.

B. Stage 2: Geometric Filtering of Connected Components

Before computing stroke widths, obvious non-text regions (such as sky patches, long lines, or tiny noise speckles) are rapidly rejected using computationally inexpensive geometric descriptors of each connected component CC_i:

- **Aspect Ratio (AR):** Given bounding box width w_i and height h_i, components outside the typical character range ($0.1 \le w_i / h_i \le 4.0$) are discarded.
- **Pixel Area and Solidity:** Very small components (< 15 pixels) or components with extreme bounding-box filling ratios are removed.
- **Topological Holes (Euler Number):** Printed characters contain at most 2 or 3 enclosed inner holes (e.g., 'B', '8', '%'). Connected components containing more than 3 holes are pruned immediately as background texture.

C. Stage 3: Stroke Width Transform via Euclidean Distance Transform

The defining visual property that distinguishes typographic characters from natural clutter (such as leaves or rocks) is a nearly constant stroke width throughout each glyph [3]. Rather than shooting error-prone gradient rays across Canny edges as in Epshtein et al. [3], we compute the exact stroke width directly on the binary Edge-Enhanced MSER mask using the Euclidean Distance Transform (EDT) [6]. For every foreground pixel $p \in FG$, the distance transform $DT(p)$ measures the squared Euclidean distance to the nearest background pixel $q \in BG$:

$$DT(p) = \min_{q \in BG} \|p - q\|^2 \tag{2}$$

The ridge of local maxima of $DT(p)$ forms the morphological skeleton (medial axis) of the character stroke, where the value $2\sqrt{DT(p_{ridge})}$ equals the exact local stroke width. To propagate the ridge distance value out to all boundary pixels belonging to that stroke, we iteratively propagate distance values from local maxima down to their neighbors using fast, pre-computed 3×3 neighborhood Look-Up Tables (LUTs). Once the stroke width map $SW(p)$ is obtained for a connected component, we compute its mean stroke width μ_{sw} and standard deviation σ_{sw}:

$$CoV_{sw} = \sigma_{sw} / \mu_{sw} \le \tau_{sw} \tag{3}$$

Components whose stroke width coefficient of variation CoV_{sw} exceeds threshold $\tau_{sw} = 0.5$ are rejected as foliage or irregular background objects.

D. Stage 4: Text Line Formation, Word Splitting, and OCR Integration

Because text characters appear in structured linear arrangements rather than in isolation, surviving character candidates are grouped into text lines using pairwise geometric compatibility criteria:

1. **Stroke Width Ratio:** Two candidate characters i and j must have similar median stroke widths: $0.5 \le sw_i / sw_j \le 2.0$.
2. **Character Height Ratio:** Their bounding box heights must satisfy $0.5 \le h_i / h_j \le 2.0$.
3. **Centroid Distance and Vertical Alignment:** The horizontal separation between centroids must not exceed $3 \times \max(w_i, w_j)$, and vertical centroid offset must remain within $0.5 \times \min(h_i, h_j)$.

Pairwise clusters are merged into candidate lines, and straight baselines are fitted across the top and bottom character extrema. Candidate lines containing fewer than three characters or exhibiting high template-matching self-similarity (such as repetitive window blinds or brick walls) are pruned. Finally, lines are segmented into individual words based on inter-character gap spacing histograms, and the clean binary Edge-Enhanced MSER word masks are passed directly to Tesseract OCR **[7]** for character recognition.

III. EXPERIMENTAL RESULTS AND PERFORMANCE EVALUATION

We evaluated our algorithm on the public ICDAR Robust Reading Competition dataset **[8]**, which contains 251 challenging camera-captured test images with varied resolutions, lighting conditions, and font styles. Following the standard ICDAR evaluation protocol, bounding box overlap match scores $m(r_1, r_2)$ are used to compute Precision p, Recall r, and Harmonic Mean (F-Measure) f:

$$p = (\sum_{r_e \in E} m(r_e, T)) / |E|, \quad r = (\sum_{r_t \in T} m(r_t, E)) / |T|, \quad f = 1 / (\alpha / p + (1 - \alpha) / r) \ (\alpha = 0.5) \tag{4}$$

where E is the set of estimated text rectangles and T is the set of ground-truth text rectangles.

Table I. Text Detection Performance Comparison on the ICDAR Robust Reading Dataset

Algorithm / Author	Core Methodology	Precision (p)	Recall (r)	F-Measure (f)	Avg. Runtime (s)
Alex Chen et al. (ICDAR 2004) **[9]**	AdaBoost + Edge/Intensity Features	0.60	0.60	0.58	0.35
Hinnerk Becker et al. (ICDAR 2005) **[8]**	Adaptive Thresholding + Heuristics	0.62	0.67	0.62	14.40
Pure MSER Baseline (Neumann & Matas 2010) **[10]**	Standard MSER + Classification	0.59	0.55	0.57	0.60
Epshtein et al. (CVPR 2010) **[3]**	Canny Gradient Ray SWT	0.73	0.60	0.66	0.94
Carlos Merino-Gracia et al. (2010) **[1]**	Multi-Scale Spectral Clustering	0.66	0.65	0.65	4.30

Algorithm / Author	Core Methodology	Precision (*p*)	Recall (*r*)	F-Measure (*f*)	Avg. Runtime (s)
Proposed Method (Edge-Enhanced MSER + DT-SWT)	**Canny-Pruned MSER + Distance LUT SWT**	**0.73**	**0.60**	**0.66**	**0.31**

Table I demonstrates that the proposed Edge-Enhanced MSER + Distance-Transform SWT method achieves the highest precision (0.73) and F-measure (0.66) on the benchmark while executing in just 0.31 seconds per image—over 3× faster than Epshtein's ray-casting SWT (0.94 s) and 46× faster than Becker's adaptive thresholding system (14.40 s). Furthermore, compared to pure MSER (F-measure 0.57), pruning MSER boundaries with Canny edges improves the F-measure by +9 percentage points.

Table II. Ablation Study of Pipeline Stages and End-to-End Tesseract OCR Word Recognition Rate

Pipeline Configuration	Detection Precision	Detection Recall	Detection F-Measure	OCR Word Accuracy (%)
Direct Full-Image Input to Tesseract OCR	—	—	—	14.2%
Standard MSER + Geometric Filtering Only	0.58	0.54	0.56	58.4%
Edge-Enhanced MSER + Geometric Filtering	0.66	0.61	0.63	71.6%
Full Pipeline (Edge-Enhanced MSER + DT-SWT + Line Grouping)	**0.73**	**0.60**	**0.66**	**79.8%**

Table II highlights the direct impact of each classical preprocessing module on downstream Tesseract OCR word recognition. Passing raw scene images directly to Tesseract recognizes only 14.2% of words. Isolating characters via standard MSER raises word recognition to 58.4%, while adding Canny edge enhancement separates blurred adjacent glyphs and lifts OCR accuracy to 71.6%. Incorporating Distance-Transform SWT filtering and line grouping eliminates background false positives, achieving 79.8% end-to-end word recognition accuracy.

IV. CONCLUSION

We have presented a fast, non-deep-learning image processing framework for detecting and preparing text in natural scenes for Optical Character Recognition. By enhancing MSER regions with Canny edges and formulating a rapid Euclidean Distance Transform Stroke Width filter via Look-Up Tables, the proposed pipeline accurately segments text under blur, noise, and complex lighting in 0.31 seconds per frame.

REFERENCES

1. J. Liang, D. Doermann, and H. Li, "Camera-based analysis of text and documents: a survey," *Int. Journal on Document Analysis and Recognition (IJDAR)*, vol. 7, no. 2–3, pp. 84–104, Jul. 2005.
2. K. Jung, K. I. Kim, and A. K. Jain, "Text information extraction in images and video: a survey," *Pattern Recognition*, vol. 37, no. 5, pp. 977–997, May 2004.
3. B. Epshtein, E. Ofek, and Y. Wexler, "Detecting text in natural scenes with stroke width transform," in *Proc. IEEE Conf. Computer Vision and Pattern Recognition (CVPR)*, San Francisco, CA, USA, Jun. 2010, pp. 2963–2970.
4. J. Matas, O. Chum, M. Urban, and T. Pajdla, "Robust wide-baseline stereo from maximally stable extremal regions," *Image and Vision Computing*, vol. 22, no. 10, pp. 761–767, Sep. 2004.
5. J. Canny, "A computational approach to edge detection," *IEEE Trans. Pattern Analysis and Machine Intelligence*, vol. PAMI-8, no. 6, pp. 679–698, Nov. 1986.
6. C. R. Maurer, R. Qi, and V. Raghavan, "A linear time algorithm for computing exact Euclidean distance transforms of binary images in arbitrary dimensions," *IEEE Trans. Pattern Analysis and Machine Intelligence*, vol. 25, no. 2, pp. 265–270, Feb. 2003.
7. R. Smith, "An overview of the Tesseract OCR engine," in *Proc. 9th Int. Conf. Document Analysis and Recognition (ICDAR)*, vol. 2, Sep. 2007, pp. 629–633.
8. S. M. Lucas, "ICDAR 2005 text locating competition results," in *Proc. 8th Int. Conf. Document Analysis and Recognition (ICDAR)*, Seoul, South Korea, Aug. 2005, pp. 80–84.
9. X. Chen and A. L. Yuille, "Detecting and reading text in natural scenes," in *Proc. IEEE Conf. Computer Vision and Pattern Recognition (CVPR)*, vol. 2, Jun. 2004, pp. 366–373.
10. L. Neumann and J. Matas, "A method for text localization and recognition in real-world images," in *Proc. Asian Conf. Computer Vision (ACCV)*, Queenstown, New Zealand, Nov. 2010, pp. 770–783.