

NAME

mkdir – make directories

SYNOPSIS

mkdir [*OPTION*]... *DIRECTORY*...

DESCRIPTION

Create the *DIRECTORY*(ies), if they do not already exist.

Mandatory arguments to long options are mandatory for short options too.

-m, --mode=MODE

set file mode (as in chmod), not a=rwx – umask

-p, --parents

no error if existing, make parent directories as needed

-v, --verbose

print a message for each created directory

-Z

set SELinux security context of each created directory to the default type

--context[=CTX]

like **-Z**, or if CTX is specified then set the SELinux or SMACK security context to CTX

--help display this help and exit

--version

output version information and exit

AUTHOR

Written by David MacKenzie.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report mkdir translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright © 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

mkdir(2)

Full documentation at: <<https://www.gnu.org/software/coreutils/mkdir>>
or available locally via: info '(coreutils) mkdir invocation'