NAME

ls – list directory contents

SYNOPSIS

ls [*OPTION*]... [*FILE*]...

DESCRIPTION

List information about the FILEs (the current directory by default). Sort entries alphabetically if none of **-cftuvSUX** nor **--sort** is specified.

Mandatory arguments to long options are mandatory for short options too.

-a, --all

do not ignore entries starting with .

-A, --almost-all

do not list implied . and ..

--author

with -1, print the author of each file

-b, --escape

print C-style escapes for nongraphic characters

--block-size=SIZE

with -l, scale sizes by SIZE when printing them; e.g., '--block-size=M'; see SIZE format below

-B, --ignore-backups

do not list implied entries ending with ~

- -c with -lt: sort by, and show, ctime (time of last modification of file status information); with -l: show ctime and sort by name; otherwise: sort by ctime, newest first
- **-C** list entries by columns

--color[=WHEN]

colorize the output; WHEN can be 'always' (default if omitted), 'auto', or 'never'; more info below

-d, --directory

list directories themselves, not their contents

-D, --dired

generate output designed for Emacs' dired mode

-f do not sort, enable -aU, disable -ls --color

-F, --classify

append indicator (one of */=>@|) to entries

--file-type

likewise, except do not append '*'

--format=WORD

across -x, commas -m, horizontal -x, long -l, single-column -1, verbose -l, vertical -C

--full-time

like **-l --time-style**= full-iso

-g like **-l**, but do not list owner

--group-directories-first

group directories before files;

can be augmented with a **--sort** option, but any use of **--sort**=*none* (**-U**) disables grouping

-G, --no-group

in a long listing, don't print group names

-h, --human-readable

with -1 and -s, print sizes like 1K 234M 2G etc.

--si likewise, but use powers of 1000 not 1024

-H, --dereference-command-line

follow symbolic links listed on the command line

--dereference-command-line-symlink-to-dir

follow each command line symbolic link

that points to a directory

--hide=PATTERN

do not list implied entries matching shell PATTERN (overridden by -a or -A)

--hyperlink[=WHEN]

hyperlink file names; WHEN can be 'always' (default if omitted), 'auto', or 'never'

--indicator-style=WORD

append indicator with style WORD to entry names: none (default), slash (-p), file-type (--file-type), classify (-F)

-i, --inode

print the index number of each file

-I, --ignore=PATTERN

do not list implied entries matching shell PATTERN

-k, --kibibytes

default to 1024-byte blocks for disk usage; used only with -s and per directory totals

-l use a long listing format

-L, --dereference

when showing file information for a symbolic link, show information for the file the link references rather than for the link itself

-m fill width with a comma separated list of entries

-n, --numeric-uid-gid

like -I, but list numeric user and group IDs

-N, --literal

print entry names without quoting

−o like **−l**, but do not list group information

-p, --indicator-style=slash

append / indicator to directories

-q, --hide-control-chars

print? instead of nongraphic characters

--show-control-chars

show nongraphic characters as-is (the default, unless program is 'ls' and output is a terminal)

-Q, --quote-name

enclose entry names in double quotes

--quoting-style=WORD

use quoting style WORD for entry names: literal, locale, shell, shell-always, shell-escape, shell-escape-always, c, escape (overrides QUOTING_STYLE environment variable)

-r, --reverse

reverse order while sorting

-R, --recursive

list subdirectories recursively

-s, --size

print the allocated size of each file, in blocks

-S sort by file size, largest first

--sort=WORD

sort by WORD instead of name: none $(-\mathbf{U})$, size $(-\mathbf{S})$, time $(-\mathbf{t})$, version $(-\mathbf{v})$, extension $(-\mathbf{X})$

--time=WORD

with $-\mathbf{l}$, show time as WORD instead of default modification time: atime or access or use $(-\mathbf{u})$; ctime or status $(-\mathbf{c})$; also use specified time as sort key if $--\mathbf{sort} = time$ (newest first)

--time-style=TIME_STYLE

time/date format with -l; see TIME_STYLE below

-t sort by modification time, newest first

-T. --tabsize=COLS

assume tab stops at each COLS instead of 8

- -u with -lt: sort by, and show, access time; with -l: show access time and sort by name; otherwise: sort by access time, newest first
- **-U** do not sort; list entries in directory order
- -v natural sort of (version) numbers within text

-w, --width=COLS

set output width to COLS. 0 means no limit

- -x list entries by lines instead of by columns
- -X sort alphabetically by entry extension

-Z, --context

print any security context of each file

- -1 list one file per line. Avoid '\n' with $-\mathbf{q}$ or $-\mathbf{b}$
- --help display this help and exit

--version

output version information and exit

The SIZE argument is an integer and optional unit (example: 10K is 10*1024). Units are K,M,G,T,P,E,Z,Y (powers of 1024) or KB,MB,... (powers of 1000).

The TIME_STYLE argument can be full—iso, long—iso, iso, locale, or +FORMAT. FORMAT is interpreted like in date(1). If FORMAT is FORMAT1<newline>FORMAT2, then FORMAT1 applies to non—recent files and FORMAT2 to recent files. TIME_STYLE prefixed with 'posix—' takes effect only outside the POSIX locale. Also the TIME_STYLE environment variable sets the default style to use.

Using color to distinguish file types is disabled both by default and with **--color**=*never*. With **--color**=*auto*, ls emits color codes only when standard output is connected to a terminal. The LS_COLORS environment variable can change the settings. Use the directors command to set it.

Exit status:

- 0 if OK.
- 1 if minor problems (e.g., cannot access subdirectory),
- 2 if serious trouble (e.g., cannot access command–line argument).

AUTHOR

Written by Richard M. Stallman and David MacKenzie.

REPORTING BUGS

GNU coreutils online help: https://www.gnu.org/software/coreutils/ Report ls translation bugs to https://translationproject.org/team/

COPYRIGHT

Copyright © 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later https://gnu.org/licenses/gpl.html.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

Full documentation at: https://www.gnu.org/software/coreutils/ls or available locally via: info '(coreutils) ls invocation'