

**NAME**

head – output the first part of files

**SYNOPSIS**

**head** [*OPTION*]... [*FILE*]...

**DESCRIPTION**

Print the first 10 lines of each FILE to standard output. With more than one FILE, precede each with a header giving the file name.

With no FILE, or when FILE is –, read standard input.

Mandatory arguments to long options are mandatory for short options too.

**-c, --bytes=[-]*NUM***

print the first NUM bytes of each file; with the leading '-', print all but the last NUM bytes of each file

**-n, --lines=[-]*NUM***

print the first NUM lines instead of the first 10; with the leading '-', print all but the last NUM lines of each file

**-q, --quiet, --silent**

never print headers giving file names

**-v, --verbose**

always print headers giving file names

**-z, --zero-terminated**

line delimiter is NUL, not newline

**--help** display this help and exit

**--version**

output version information and exit

NUM may have a multiplier suffix: b 512, kB 1000, K 1024, MB 1000\*1000, M 1024\*1024, GB 1000\*1000\*1000, G 1024\*1024\*1024, and so on for T, P, E, Z, Y.

**AUTHOR**

Written by David MacKenzie and Jim Meyering.

**REPORTING BUGS**

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report head translation bugs to <<https://translationproject.org/team/>>

**COPYRIGHT**

Copyright © 2018 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

**SEE ALSO**

tail(1)

Full documentation at: <<https://www.gnu.org/software/coreutils/head>>  
or available locally via: info '(coreutils) head invocation'