NMSIS

Release 1.2.0

Nuclei

Nov 03, 2023

CONTENTS:

1 Nuclei MCU Software Interface Standard(NMSIS) 1
- 1.1 About NMSIS . . . 1
- 1.2 NMSIS Components . . . 1
- 1.3 NMSIS Design . . . 1
- 1.4 How to Access . . . 2
- 1.5 Coding Rules . . . 2
- 1.6 Validation . . . 3
- 1.7 License . . . 3

2 NMSIS Core 5
- 2.1 Overview . . . 5
  - 2.1.1 Introduction . . . 5
  - 2.1.2 Processor Support . . . 6
  - 2.1.3 Toolchain Support . . . 6
- 2.2 Using NMSIS in Embedded Applications . . . 6
  - 2.2.1 Introduction . . . 6
  - 2.2.2 Basic NMSIS Example . . . 9
  - 2.2.3 Using Interrupt and Exception/NMI . . . 11
  - 2.2.4 Using NMSIS with generic Nuclei Processors . . . 11
  - 2.2.5 Create generic Libraries with NMSIS . . . 11
- 2.3 NMSIS-Core Device Templates . . . 12
  - 2.3.1 Introduction . . . 12
  - 2.3.2 NMSIS-Core Processor Files . . . 13
  - 2.3.3 Device Examples . . . 13
  - 2.3.4 Template Files . . . 13
  - 2.3.5 Adapt Template Files to a Device . . . 14
  - 2.3.6 Device Templates Explaination . . . 14
- 2.4 Register Mapping . . . 75
- 2.5 NMSIS Core API . . . 76
  - 2.5.1 Version Control . . . 76
  - 2.5.2 Compiler Control . . . 78
  - 2.5.3 Core CSR Register Access . . . 80
  - 2.5.4 Core CSR Encoding . . . 84
  - 2.5.5 Register Define and Type Definitions . . . 126
  - 2.5.6 CPU Intrinsic Functions . . . 147
  - 2.5.7 Intrinsic Functions for SIMD Instructions . . . 156
  - 2.5.8 Peripheral Access . . . 540
  - 2.5.9 Systick Timer(SysTimer) . . . 542
  - 2.5.10 Interrupts and Exceptions . . . 554
  - 2.5.11 FPU Functions . . . 589

2.5.12 PMP Functions . . . 593
2.5.13 SPMP Functions . . . 596
2.5.14 Cache Functions . . . 599
2.5.15 System Device Configuration . . . 628
2.5.16 ARM Compatiable Functions . . . 635

3 NMSIS DSP **639**
3.1 Overview . . . 639
3.1.1 Introduction . . . 639
3.1.2 Using the Library . . . 640
3.1.3 Examples . . . 640
3.1.4 Toolchain Support . . . 640
3.1.5 Building the Library . . . 640
3.1.6 Preprocessor Macros . . . 640
3.2 Using NMSIS-DSP . . . 640
3.2.1 Preparation . . . 640
3.2.2 Tool Setup . . . 641
3.2.3 Build NMSIS DSP Library . . . 641
3.2.4 How to run . . . 644
3.3 NMSIS DSP API . . . 645
3.3.1 Basic Math Functions . . . 645
3.3.2 Bayesian estimators . . . 669
3.3.3 Complex Math Functions . . . 670
3.3.4 Controller Functions . . . 681
3.3.5 Distance functions . . . 692
3.3.6 Fast Math Functions . . . 704
3.3.7 Filtering Functions . . . 712
3.3.8 Interpolation Functions . . . 791
3.3.9 Matrix Functions . . . 797
3.3.10 Quaternion Math Functions . . . 829
3.3.11 Statistics Functions . . . 833
3.3.12 Support Functions . . . 861
3.3.13 SVM Functions . . . 880
3.3.14 Transform Functions . . . 887
3.3.15 Window Functions . . . 991
3.3.16 Examples . . . 1017
3.4 Changelog . . . 1031
3.4.1 V1.2.0 . . . 1031
3.4.2 V1.1.1 . . . 1031
3.4.3 V1.1.0 . . . 1032
3.4.4 V1.0.3 . . . 1032
3.4.5 V1.0.2 . . . 1032
3.4.6 V1.0.1 . . . 1032
3.4.7 V1.0.0 . . . 1032

4 NMSIS NN **1033**
4.1 Overview . . . 1033
4.1.1 Introduction . . . 1033
4.1.2 Block Diagram . . . 1034
4.1.3 Examples . . . 1034
4.1.4 Pre-processor Macros . . . 1034
4.2 Using NMSIS-NN . . . 1034
4.2.1 Preparation . . . 1034
4.2.2 Tool Setup . . . 1035

4.2.3 Build NMSIS NN Library 1035
4.2.4 How to run 1037
4.3 NMSIS NN API 1039
4.3.1 Convolutional Neural Network Example 1039
4.3.2 Gated Recurrent Unit Example 1040
4.3.3 Public 1041
4.3.4 Private 1106
4.4 Changelog 1125
4.4.1 V1.2.0 1125
4.4.2 V1.1.1 1125
4.4.3 V1.1.0 1126
4.4.4 V1.0.3 1126
4.4.5 V1.0.2 1126
4.4.6 V1.0.1 1126
4.4.7 V1.0.0 1126

5 Changelog **1127**
5.1 V1.2.0 1127
5.2 V1.1.1 1129
5.3 V1.1.0 1130
5.4 V1.0.4 1131
5.5 V1.0.3 1131
5.6 V1.0.2 1132
5.7 V1.0.2-RC2 1133
5.8 V1.0.2-RC1 1133
5.9 V1.0.1 1133
5.10 V1.0.1-RC1 1134
5.11 V1.0.0-beta1 1134
5.12 V1.0.0-beta 1135
5.13 V1.0.0-alpha.1 1135
5.14 V1.0.0-alpha 1135

6 Glossary **1137**

7 Appendix **1139**

8 Indices and tables **1141**

Index **1143**

CHAPTER

ONE

NUCLEI MCU SOFTWARE INTERFACE STANDARD(NMSIS)

1.1 About NMSIS

The **NMSIS** is a vendor-independent hardware abstraction layer for micro-controllers that are based on Nuclei Processors[1].

The **NMSIS** defines generic tool interfaces and enables consistent device support. It provides simple software interfaces to the processor and the peripherals, simplifying software re-use, reducing the learning curve for micro-controller developers, and reducing the time to market for new devices.

1.2 NMSIS Components

NMSIS CORE All Nuclei N/NX Class Processors Standardized API for the Nuclei processor core and peripherals.

NMSIS DSP All Nuclei N/NX Class Processors DSP library collection with a lot of functions for various data types: fixed-point (fractional q7, q15, q31) and single precision floating-point (32-bit). Implementations optimized for the Nuclei Processors which has P-ext or V-ext instruction set.

NMSIS NN All Nuclei N/NX Class Processors Collection of efficient neural network kernels developed to maximize the performance and minimize the memory footprint Nuclei processor cores.

1.3 NMSIS Design

NMSIS is designed to help the Nuclei N/NX Class Processors processors in standardization. It enables consistent software layers and device support across a wide range of development tools and micro-controllers.

NMSIS is a lightweight software interface layer that tried to standardize common Nuclei processor-based SOC, and it didn't define any standard peripherals. The silicon industry can therefore support the wide variations of Nuclei processor-based devices with this common standard.

We can achieve the following benefits of **NMSIS**:

- **NMSIS** reduces the learning curve, development costs, and time-to-market. Developers can write software quicker through a variety of easy-to-use, standardized software interfaces.
- Consistent software interfaces improve the software portability and re-usability. Generic software libraries and interfaces provide consistent software framework.
- It provides interfaces for debug connectivity, debug peripheral views, software delivery, and device support to reduce time-to-market for new micro-controller deployment.

[1] https://www.nucleisys.com/product.php



Fig. 1: NMSIS Design Diagram

- Being a compiler independent layer, it allows to use the compiler of your choice. Thus, it is supported by mainstream compilers.
- It enhances program debugging with peripheral information for debuggers.

1.4 How to Access

If you want to access the code of **NMSIS**, you can visit our opensource NMSIS Github Repository[2].

1.5 Coding Rules

The **NMSIS** uses the following essential coding rules and conventions:

- Compliant with ANSI C (C99) and C++ (C++03).
- Uses ANSI C standard data types defined in **stdint.h**.
- Variables and parameters have a complete data type.
- Expressions for *#define* constants are enclosed in parenthesis.

In addition, the **NMSIS** recommends the following conventions for identifiers:

- **CAPITAL** names to identify Core Registers, Peripheral Registers, and CPU Instructions.
- **CamelCase** names to identify function names and interrupt functions.
- **Namespace_** prefixes avoid clashes with user identifiers and provide functional groups (i.e. for peripherals, RTOS, or DSP Library).

The **NMSIS** is documented within the source files with:

[2] https://github.com/Nuclei-Software/NMSIS

- Comments that use the C or C++ style.
- Doxygen compliant comments, which provide:
  - brief function, variable, macro overview.
  - detailed description of the function, variable, macro.
  - detailed parameter explanation.
  - detailed information about return values.

1.6 Validation

Nuclei uses RISC-V GCC/Clang/IAR Compiler in the various tests of **NMSIS**, and if more compiler is added, it could be easily supported by following the **NMSIS** compiler independent layer. For each component, the section **Validation** describes the scope of the various verifications.

NMSIS components are compatible with a range of C and C++ language standards.

As **NMSIS** defines API interfaces and functions that scale to a wide range of processors and devices, the scope of the run-time test coverage is limited. However, several components are validated using dedicated test suites.

1.7 License

This **NMSIS** is modified based on open-source project **CMSIS** to match Nuclei requirements.

This **NMSIS** is provided free of charge by Nuclei under the Apache 2.0 License[3].

[3] http://www.apache.org/licenses/LICENSE-2.0

CHAPTER

TWO

NMSIS CORE

2.1 Overview

2.1.1 Introduction

NMSIS-Core implements the basic run-time system for a Nuclei N/NX Class Processors based device and gives the user access to the processor core and the device peripherals. In detail it defines:

- **Hardware Abstraction Layer (HAL)** for Nuclei processor registers with standardized definitions for the **CSR Registers**, **TIMER**, **ECLIC**, **PMP Registers**, **DSP Registers**, **FPU registers**, and **Core Access Functions**.
- **Standard core exception/interrupt names** to interface to system exceptions or interrupts without having compatibility issues.
- **Methods to organize header files** that makes it easy to learn new Nuclei micro-controller products and improve software portability. This includes naming conventions for device-specific interrupts.
- **Methods for system initialization** to be used by each Device vendor. For example, the standardized `SystemInit()` (page 629) function is essential for configuring the clock system of the device.
- **Intrinsic functions** used to generate CPU instructions that are not supported by standard C functions.
- A variable `SystemCoreClock` (page 631) to determine the **system clock frequency** which simplifies the setup the timer.

The following sections provide details about the **NMSIS-Core**:

- *Using NMSIS in Embedded Applications* (page 6) describes the project setup and shows a simple program example
- *NMSIS-Core Device Templates* (page 12) describes the files of the *NMSIS Core* (page 5) in detail and explains how to adapt template files provided by Nuclei to silicon vendor devices.
- *NMSIS Core API* (page 76) describe the features and functions of the *Device Header File <Device.h>* (page 63) in detail.
- *Register Define and Type Definitions* (page 126) describe the data structures of the *Device Header File <Device.h>* (page 63) in detail.

2.1.2 Processor Support

NMSIS have provided support for all the Nuclei N/NX Class Processors.

Nuclei ISA Spec:

Please contact with our sales about Nuclei Process Core Instruction Set Architecture Spec `Nuclei_RISC-V_ISA_Spec.pdf`.

Nuclei Processor Reference Manuals:

- 200 series[4]
- 300 series[5]
- 600 series[6]
- 900 series[7]

2.1.3 Toolchain Support

The *NMSIS-Core Device Templates* (page 12) provided by Nuclei have been tested and verified using these toolchains:

- GNU GCC/LLVM Clang Toolchain for RISC-V modified by Nuclei, see https://www.nucleisys.com/download.php#tools
- IAR Compiler for RISC-V, see https://www.iar.com/riscv

2.2 Using NMSIS in Embedded Applications

2.2.1 Introduction

To use the **NMSIS-Core**, the following files are added to the embedded application:

- *Startup File startup_<Device>.S* (page 14), which provided asm startup code and vector table.
- *Interrupt and Exception Handling File: intexc_<Device>.S* (page 25), which provided general exception handling code for non-vector interrupts and exceptions.
- *Device Linker Script: gcc_<device>.ld* (page 36), which provided linker script for the device.
- *System Configuration Files system_<Device>.c and system_<Device>.h* (page 42), which provided general device configuration (i.e. for clock and BUS setup).
- *Device Header File <Device.h>* (page 63) gives access to processor core and all peripherals.

Note: The best example usage of NMSIS device template is our Nuclei SDK project's evalsoc support source code, it is modified based on NMSIS device template and may contains newer experimental features not in this device template, and it also provided very good user experience for both command line and IDE itegration like Nuclei Studio and IAR Workbench.

The files *Startup File startup_<Device>.S* (page 14), *Interrupt and Exception Handling File: intexc_<Device>.S* (page 25), *Device Linker Script: gcc_<device>.ld* (page 36) and *System Configuration Files system_<Device>.c and*

[4] https://www.nucleisys.com/product/200.php
[5] https://www.nucleisys.com/product/300.php
[6] https://www.nucleisys.com/product/600.php
[7] https://www.nucleisys.com/product/900.php

system_<Device>.h (page 42) may require application specific adaptations and therefore should be copied into the application project folder prior configuration.

The *Device Header File <Device.h>* (page 63) is included in all source files that need device access and can be stored on a central include folder that is generic for all projects.

The *Startup File startup_<Device>.S* (page 14) is executed right after device reset, it will do necessary stack pointer initialization, exception and interrupt entry configuration, then call `SystemInit()` (page 629), after system initialization, will return to assemble startup code and do c/c++ runtime initialization which includes data, bss section initialization, c++ runtime initialization, then it will call `main()` function in the application code.

In the *Interrupt and Exception Handling File: intexc_<Device>.S* (page 25), it will contain all exception and interrupt vectors and implements a default function for every interrupt. It may also contain stack and heap configurations for the user application.

The *System Configuration Files system_<Device>.c and system_<Device>.h* (page 42) performs the setup for the processor clock. The variable `SystemCoreClock` (page 631) indicates the CPU clock speed. *Systick Timer(SysTimer)* (page 542) describes the minimum feature set. In addition the file may contain functions for the memory BUS setup and clock re-configuration.

The *Device Header File <Device.h>* (page 63) is the central include file that the application programmer is using in the C source code. It provides the following features:

- *Peripheral Access* (page 540) provides a standardized register layout for all peripherals. Optionally functions for device-specific peripherals may be available.
- *Interrupts and Exceptions* (page 554) can be accessed with standardized symbols and functions for the **ECLIC** are provided.
- *CPU Intrinsic Functions* (page 147) allow to access special instructions, for example for activating sleep mode or the NOP instruction.
- *Intrinsic Functions for SIMD Instructions* (page 156) provide access to the DSP-oriented instructions.
- *Systick Timer(SysTimer)* (page 542) function to configure and start a periodic timer interrupt.
- *Core CSR Register Access* (page 80) function to access the core csr registers.
- *Cache Functions* (page 599) to access the I-CACHE and D-CACHE unit
- *FPU Functions* (page 589) to access the Floating point unit.
- *PMP Functions* (page 593) to access the Physical Memory Protection unit
- *Version Control* (page 76) which defines NMSIS release specific macros.
- *Compiler Control* (page 78) is compiler agnostic *#define* symbols for generic C/C++ source code

The NMSIS-Core system files are device specific.

In addition, the *Startup File startup_<Device>.S* (page 14) is also compiler vendor specific, currently only GCC version is provided. The versions provided by NMSIS are only generic templates. The adopted versions for a concrete device are typically provided by the device vendor through the according device familiy package.

For example, the following files are provided by the **GD32VF103** device family pack:



Fig. 1: NMSIS-Core User Files

Table 1: Files provided by GD32VF103 device family pack

File	Description
./Device/Source/GCC/startup_gd32vf103.S	Startup File startup_<device>.S for the GD32VF103 device variants.
./Device/Source/GCC/intexc_gd32vf103.S	Exception and Interrupt Handling File intexc_<device>.S for the GD32VF103 device variants.
./Device/Source/GCC/gcc_gd32vf103.ld	Linker script File gcc_<device>.ld for the GD32VF103 device variants.
./Device/Source/system_gd32vf103.c	System Configuration File system_<device>.c for the GD32VF103 device families
./Device/Include/system_gd32vf103.h	System Configuration File system_<device>.h for the GD32VF103 device families
./Device/Include/gd32vf103.h	Device Header File <device.h> for the GD32VF103 device families.

Note: The silicon vendors create these device-specific NMSIS-Core files based on *NMSIS-Core Device Templates* (page 12) provided by Nuclei.

Thereafter, the functions described under *NMSIS Core API* (page 76) can be used in the application.

2.2.2 Basic NMSIS Example

A typical example for using the NMSIS layer is provided below. The example is based on a GD32VF103 Device.

Listing 1: gd32vf103_example.c

```c
#include <gd32vf103.h>                              // File name depends on device used

uint32_t volatile msTicks;                          // Counter for millisecond Interval
#define SysTick_Handler     eclic_mtip_handler
#define CONFIG_TICKS        (SOC_TIMER_FREQ / 1000)

void SysTick_Handler (void) {                       // SysTick Interrupt Handler
  SysTick_Reload(CONFIG_TICKS);
```

(continues on next page)

(continued from previous page)

```c
  msTicks++;                                             // Increment Counter
}

void WaitForTick (void)  {
  uint32_t curTicks;

  curTicks = msTicks;                                    // Save Current SysTick Value
  while (msTicks == curTicks)  {                         // Wait for next SysTick Interrupt
    __WFI ();                                            // Power-Down until next Event/Interrupt
  }
}

void TIMER0_UP_IRQHandler (void) {                       // Timer Interrupt Handler
  ;                                                      // Add user code here
}

void timer0_init(int frequency) {                        // Set up Timer (device specific)
  ECLIC_SetPriorityIRQ (TIMER0_UP_IRQn, 1);              // Set Timer priority
  ECLIC_EnableIRQ (TIMER0_UP_IRQn);                      // Enable Timer Interrupt
}


void Device_Initialization (void)  {                     // Configure & Initialize MCU
  if (SysTick_Config (CONFIG_TICKS)) {
       ; // Handle Error
  }
  timer0_init ();                                        // setup device-specific timer
}

// The processor clock is initialized by NMSIS startup + system file
void main (void) {                                       // user application starts here
  Device_Initialization ();                              // Configure & Initialize MCU
  while (1)  {                                           // Endless Loop (the Super-Loop)
    __disable_irq ();                                    // Disable all interrupts
    Get_InputValues ();                                  // Read Values
    __enable_irq ();                                     // Enable all interrupts
    Calculation_Response ();                             // Calculate Results
    Output_Response ();                                  // Output Results
    WaitForTick ();                                      // Synchronize to SysTick Timer
  }
}
```

2.2.3 Using Interrupt and Exception/NMI

Nuclei processors provide **NMI(Non-Maskable Interrupt)**, **Exception**, **Vector Interrupt** and **Non-Vector Interrupt** features.

2.2.4 Using NMSIS with generic Nuclei Processors

Nuclei provides NMSIS-Core Device template files for the supported Nuclei Processors and for various compiler vendors. These files can be used as templates, and you can modify based on it to match your processor design.

And you can also refer to Nuclei SDK[8] project for an quick and easily startup project to work with Nuclei RISC-V processor, it is based on NMSIS project and support build/debug c/c++ project in both command line or many different IDEs such as Nuclei Studio.

The table below lists the template folder.

Table 2: NMSIS Device Templates for the Nuclei processors

Folder	Processor	RISC-V	Description
./Device/_Template_Vendor	• 200 • 300 • 600 • 900	RV32 RV64	Contains Include and Source template files configured for the Nuclei RISC-V processor.

2.2.5 Create generic Libraries with NMSIS

The NMSIS Processor and Core Peripheral files allow also to create generic libraries. The **NMSIS-DSP** Libraries are an example for such a generic library.

To build a generic library set the define **__NMSIS_GENERIC** and include the *nmsis_core.h* NMSIS CPU & Core Access header file for the processor.

The define **__NMSIS_GENERIC** disables device-dependent features such as the **SysTick timer** and the **Interrupt System**.

Example

The following code section shows the usage of the *nmsis_core.h* header files to build a generic library for N200, N300, N600, NX600.

One of these defines needs to be provided on the compiler command line.

By using this header file, the source code can access the functions for *Core CSR Register Access* (page 80), *CPU Intrinsic Functions* (page 147) and *Intrinsic Functions for SIMD Instructions* (page 156).

[8] https://github.com/Nuclei-Software/nuclei-sdk

Listing 2: core_generic.h

```
#define __NMSIS_GENERIC   // Disable Eclic and Systick functions
#include <nmsis_core.h>
```

2.3 NMSIS-Core Device Templates

2.3.1 Introduction

Nuclei supplies NMSIS-Core device template files for the all supported Nuclei N/NX Class Processors and various compiler vendors. Refer to the list of *supported toolchain* (page 6) for compliance.

These NMSIS-Core device template files include the following:

- Register names of the Core Peripherals and names of the Core Exception/Interrupt Vectors.
- Functions to access core peripherals, special CPU instructions and SIMD instructions
- Generic startup code and system configuration code.

The detailed file structure of the NMSIS-Core device templates is shown in the following picture.



Fig. 2: NMSIS-Core Device Templates

Nuclei SDK is an open source Nuclei RISC-V processor software development kit which is based on NMSIS project, using NMSIS Core/DSP/NN header files and prebuilt NMSIS DSP/NN library, and also create Nuclei FPGA evaluation SoC called evalsoc support package based on NMSIS device template, if you want to know how to use NMSIS, it is a good startup.

2.3.2 NMSIS-Core Processor Files

The NMSIS-Core processor files provided by Nuclei are in the directory *NMSIS/Core/Include*.

These header files define all processor specific attributes do not need any modifications.

The *nmsis_core.h* defines the core peripherals and provides helper functions that access the core registers.

2.3.3 Device Examples

The NMSIS Software Pack defines several devices that are based on the Nuclei N/NX/U/UX processors.

The device related NMSIS-Core files are in the directory *Device/Nuclei*, but it is removed since NMSIS 1.2.0 release, and please directly refer to the **Template Files** or Nuclei SDK project's `SoC/evalsoc` support code.

2.3.4 Template Files

To simplify the creation of NMSIS-Core device files, the following template files are provided that should be extended by the silicon vendor to reflect the actual device and device peripherals.

Silicon vendors add to these template files the following information:

- **Device Peripheral Access Layer** that provides definitions for device-specific peripherals.
- **Access Functions for Peripherals** (optional) that provides additional helper functions to access device-specific peripherals.
- **Interrupt vectors** in the startup file that are device specific.

Table 3: NMSIS-Core Device Template Files

Template File (Under ./Device/_Template_Vendor/Vendor/)	**Description**
Device/Source/GCC/startup_Device.S	Startup file template for GCC/Clang RISC-V Embedded Compiler.
Device/Source/GCC/gcc_Device.ld	Link Script file template for GCC/Clang RISC-V Embedded Compiler.
Device/Source/GCC/intexc_Device.S	Exception and Interrupt handling file template(machine mode) for GCC/Clang RISC-V Embedded Compiler.
Device/Source/GCC/intexc_Device_s.S	Exception and Interrupt handling file template(supervisor mode) for GCC/Clang RISC-V Embedded Compiler.
Device/Source/IAR/startup_Device.c	Startup file template for IAR RISC-V Compiler.
Device/Source/IAR/iar_Device.icf	Link Script file template for IAR RISC-V Compiler.
Device/Source/IAR/intexc_Device.S	Exception and Interrupt handling file template(machine mode) for IAR RISC-V Compiler.
Device/Source/IAR/intexc_Device_s.S	Exception and Interrupt handling file template(supervisor mode) for IAR RISC-V Compiler.
Device/Source/system_Device.c	Generic system_Device.c file for system configuration (i.e. processor clock and memory bus system).
Device/Include/Device.h	Generic device header file. Needs to be extended with the device-specific peripheral registers. Optionally functions that access the peripherals can be part of that file.
Device/Include/system_Device.h	Generic system device configuration include file.

Note: The template files for silicon vendors are placed under *./Device/_Template_Vendor/Vendor/*.

Please goto that folder to find the file list in the above table.

2.3.5 Adapt Template Files to a Device

The following steps describe how to adopt the template files to a specific device or device family.

Copy the complete all files in the template directory and replace:

- directory name `Vendor` with the abbreviation for the device vendor e.g.: **GD**.
- directory name `Device` with the specific device name e.g.: **GD32VF103**.
- in the file names `Device` with the specific device name e.g.: **GD32VF103**.

Each template file contains comments that start with **TODO**: that describe a required modification.

The template files contain place holders:

Table 4: Placeholders of Template files

Placeholder	Replaced with
<Device>	the specific device name or device family name; i.e. GD32VF103.
<DeviceInterrupt>	a specific interrupt name of the device; i.e. TIM1 for Timer 1.
<DeviceAbbreviation>	short name or abbreviation of the device family; i.e. GD32VF.
Nuclei-N#	the specific Nuclei Class name; i.e. Nuclei N or Nuclei NX.

2.3.6 Device Templates Explaination

The device configuration of the template files is described in detail on the following pages:

We only explain machine mode intexc_Device.S template, its supervisor mode version is similar, please directly check the code, and for the IAR device templates, the flow is also similar, but it reused startup code provided in IAR compiler, and implement Nuclei dependent boot code in `__low_level_init` function.

Startup File startup_<Device>.S

The Startup File startup_<device>.S contains:

- The reset handler which is executed after CPU reset and typically calls the `SystemInit()` (page 629) function.
- The setup values for the stack pointer SP and global pointor GP for small data access.
- Exception vectors of the Nuclei Processor with weak functions that implement default routines.
- Interrupt vectors that are device specific with weak functions that implement default routines.

The processer level start flow is implemented in the *startup_<Device>.S*. Detail description as below picture:

The IAR version of startup code located in *startup_<Device>.c*.

Stage1: Interrupt and Exception initialization

- Disable Interrupt
- Initialize GP, SP for single core or smp core if existed

- Initialize NMI entry and set default NMI handler
- Initialize exception entry to early exception entry in `startup_<Device>.S`
- Initialize vector table entry and set default interrupt handler
- Initialize Interrupt mode as ECLIC mode. (ECLIC mode is proposed. Default mode is CLINT mode)

Stage2: Hardware initialization

- Enable FPU if necessary
- Enable VPU if necessary
- Enable Zc if necessary

Stage3: Section initialization

- Copy section, e.g. data section, text section if necessary.
- Clear Block Started by Symbol (BSS) section
- Call user defined *SystemInit()* (page 629) for system clock initialization.
- Call `__libc_fini_array` and `__libc_init_array` functions to do C library initialization
- Call `_premain_init` function to do initialization steps before main function
- Initialize exception entry to exception entry in `intexc_<Device>.S`
- Enable BPU of Nuclei CPU
- Jump Main

The file exists for each supported toolchain and is the only toolchain specific NMSIS file.

To adapt the file to a new device only the interrupt vector table needs to be extended with the device-specific interrupt handlers.

The naming convention for the interrupt handler names are `eclic_<interrupt_name>_handler`.

This table needs to be consistent with `IRQn_Type` that defines all the IRQ numbers for each interrupt.

The following example shows the extension of the interrupt vector table for the GD32VF103 device family.

```
    .section .text.vtable

    .weak  eclic_msip_handler
    .weak  eclic_mtip_handler
    .weak  eclic_pmaf_handler
    /* Adjusted for GD32VF103 interrupt handlers */
    .weak  eclic_wwdgt_handler
    .weak  eclic_lvd_handler
    .weak  eclic_tamper_handler
        :     :
        :     :
    .weak  eclic_can1_ewmc_handler
    .weak  eclic_usbfs_handler

    .globl vector_base
    .type vector_base, @object
vector_base:
    /* Run in FlashXIP download mode */
    j _start                                              /* 0: Reserved, Jump to _
↪start when reset for vector table not remapped cases.*/
```

(continues on next page)

(continued from previous page)

```
    .align LOG_REGBYTES                                         /*    Need to align 4 byte for RV32, 8 Byte for RV64 */
    DECLARE_INT_HANDLER     default_intexc_handler              /* 1: Reserved */
    DECLARE_INT_HANDLER     default_intexc_handler              /* 2: Reserved */
    DECLARE_INT_HANDLER     eclic_msip_handler                  /* 3: Machine software interrupt */
                     :          :
                     :          :
    /* Adjusted for Vendor Defined External Interrupts */
    DECLARE_INT_HANDLER     eclic_wwdgt_handler                 /* 19: Window watchDog timer interrupt */

    DECLARE_INT_HANDLER     eclic_lvd_handler                   /* 20: LVD through EXTI line detect interrupt */
    DECLARE_INT_HANDLER     eclic_tamper_handler                /* 21: tamper through EXTI line detect */
                     :          :
                     :          :
    DECLARE_INT_HANDLER     eclic_can1_ewmc_handler             /* 85: CAN1 EWMC interrupt */
    DECLARE_INT_HANDLER     eclic_usbfs_handler                 /* 86: USBFS global interrupt */
```

startup_Device.S Template File

Here provided a riscv-gcc template startup assemble code template file as below. The files for other compilers can slightly differ from this version.

```
/*
 * Copyright (c) 2019 Nuclei Limited. All rights reserved.
 *
 * SPDX-License-Identifier: Apache-2.0
 *
 * Licensed under the Apache License, Version 2.0 (the License); you may
 * not use this file except in compliance with the License.
 * You may obtain a copy of the License at
 *
 * www.apache.org/licenses/LICENSE-2.0
 *
 * Unless required by applicable law or agreed to in writing, software
 * distributed under the License is distributed on an AS IS BASIS, WITHOUT
 * WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 * See the License for the specific language governing permissions and
 * limitations under the License.
 */
/******************************************************************************
 * \file     startup_<Device>.S
 * \brief    NMSIS Nuclei N/NX Class Core based Core Device Startup File for
 *           Device <Device>
 * \version  V2.1.0
 * \date     19. Dec 2023
 *
```

(continues on next page)

(continued from previous page)

```
 ******************************************************************************/

#include "riscv_encoding.h"

/* TODO: If BOOT_HARTID is not defined, default value is 0, change it to your desired default boot hartid */
#ifndef BOOT_HARTID
    .equ BOOT_HARTID,    0
#endif

.macro DECLARE_INT_HANDLER  INT_HDL_NAME
#if defined(__riscv_xlen) && (__riscv_xlen == 32)
    .word \INT_HDL_NAME
#else
    .dword \INT_HDL_NAME
#endif
.endm

    .section .text.vtable

    /* TODO: Add your interrupt handler in this vector table */
    .weak eclic_msip_handler
    .weak eclic_mtip_handler
    .weak eclic_inter_core_int_handler
    .globl vector_base
    .type vector_base, @object
    .option push
    .option norelax
vector_base:
#ifndef VECTOR_TABLE_REMAPPED
    j _start                                                /* 0: Reserved, Jump to _start when reset for vector table not remapped cases.*/
    .align LOG_REGBYTES                                     /*    Need to align 4 byte for RV32, 8 Byte for RV64 */
#else
    DECLARE_INT_HANDLER     default_intexc_handler          /* 0: Reserved, default handler for vector table remapped cases */
#endif
    DECLARE_INT_HANDLER     default_intexc_handler          /* 1: Reserved */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 2: Reserved */
    DECLARE_INT_HANDLER     eclic_msip_handler              /* 3: Machine software interrupt */

    DECLARE_INT_HANDLER     default_intexc_handler          /* 4: Reserved */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 5: Reserved */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 6: Reserved */
    DECLARE_INT_HANDLER     eclic_mtip_handler              /* 7: Machine timer interrupt */

    DECLARE_INT_HANDLER     default_intexc_handler          /* 8: Reserved */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 9: Reserved */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 10: Reserved */
```

(continues on next page)

(continued from previous page)

```
    DECLARE_INT_HANDLER     default_intexc_handler          /* 11: Reserved */

    DECLARE_INT_HANDLER     default_intexc_handler          /* 12: Reserved */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 13: Reserved */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 14: Reserved */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 15: Reserved */

    DECLARE_INT_HANDLER     eclic_inter_core_int_handler    /* 16: Reserved */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 17: Reserved */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 18: Reserved */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 19: Interrupt 19 */

    DECLARE_INT_HANDLER     default_intexc_handler          /* 20: Interrupt 20 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 21: Interrupt 21 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 22: Interrupt 22 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 23: Interrupt 23 */

    DECLARE_INT_HANDLER     default_intexc_handler          /* 24: Interrupt 24 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 25: Interrupt 25 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 26: Interrupt 26 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 27: Interrupt 27 */

    DECLARE_INT_HANDLER     default_intexc_handler          /* 28: Interrupt 28 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 29: Interrupt 29 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 30: Interrupt 30 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 31: Interrupt 31 */

    DECLARE_INT_HANDLER     default_intexc_handler          /* 32: Interrupt 32 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 33: Interrupt 33 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 34: Interrupt 34 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 35: Interrupt 35 */

    DECLARE_INT_HANDLER     default_intexc_handler          /* 36: Interrupt 36 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 37: Interrupt 37 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 38: Interrupt 38 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 39: Interrupt 39 */

    DECLARE_INT_HANDLER     default_intexc_handler          /* 40: Interrupt 40 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 41: Interrupt 41 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 42: Interrupt 42 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 43: Interrupt 43 */

    DECLARE_INT_HANDLER     default_intexc_handler          /* 44: Interrupt 44 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 45: Interrupt 45 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 46: Interrupt 46 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 47: Interrupt 47 */

    DECLARE_INT_HANDLER     default_intexc_handler          /* 48: Interrupt 48 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 49: Interrupt 49 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 50: Interrupt 50 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 51: Interrupt 51 */

```

(continues on next page)

(continued from previous page)

```
    DECLARE_INT_HANDLER     default_intexc_handler          /* 52: Interrupt 52 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 53: Interrupt 53 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 54: Interrupt 54 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 55: Interrupt 55 */

    DECLARE_INT_HANDLER     default_intexc_handler          /* 56: Interrupt 56 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 57: Interrupt 57 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 58: Interrupt 58 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 59: Interrupt 59 */

    DECLARE_INT_HANDLER     default_intexc_handler          /* 60: Interrupt 60 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 61: Interrupt 61 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 62: Interrupt 62 */
    DECLARE_INT_HANDLER     default_intexc_handler          /* 63: Interrupt 63 */

    .option pop


    .section .text.init
    .globl _start
    .type _start, @function

/**
 * Reset Handler called on controller reset
 */
_start:
    /* ===== Startup Stage 1 ===== */
    /* Disable Global Interrupt */
    csrc CSR_MSTATUS, MSTATUS_MIE

    /* If SMP_CPU_CNT is not defined,
     * assume that only 1 core is allowed to run,
     * the core hartid is defined via BOOT_HARTID.
     * other harts if run to here, just do wfi in __amp_wait
     */
#ifndef SMP_CPU_CNT
    /* take bit 0-7 for hart id in a local cluster */
    csrr a0, CSR_MHARTID
    andi a0, a0, 0xFF
    /* BOOT_HARTID is configurable in Makefile via BOOT_HARTID variable */
    li a1, BOOT_HARTID
    bne a0, a1, __amp_wait
#endif

    /* Initialize GP and TP and jump table base when zcmt enabled */
    .option push
    .option norelax
    la gp, __global_pointer$
    la tp, __tls_base
#if defined(__riscv_zcmt)
    la t0, __jvt_base$
    csrw CSR_JVT, t0
```

(continues on next page)

(continued from previous page)

```
#endif
    .option pop

#if defined(SMP_CPU_CNT) && (SMP_CPU_CNT > 1)
    /* Set correct sp for each cpu
     * each stack size is __STACK_SIZE
     * defined in linker script */
    lui t0, %hi(__STACK_SIZE)
    addi t0, t0, %lo(__STACK_SIZE)
    la sp, _sp
    csrr a0, CSR_MHARTID
    andi a0, a0, 0xFF
    li a1, 0
1:
    beq a0, a1, 2f
    sub sp, sp, t0
    addi a1, a1, 1
    j 1b
2:
#else
    /* Set correct sp for current cpu */
    la sp, _sp
#endif

    /*
     * Set the the NMI base mnvec to share
     * with mtvec by setting CSR_MMISC_CTL
     * bit 9 NMI_CAUSE_FFF to 1
     */
    li t0, MMISC_CTL_NMI_CAUSE_FFF
    csrs CSR_MMISC_CTL, t0

    /*
     * Enable Zc feature when compiled zcmp & zcmt
     */
#if defined(__riscv_zcmp) || defined(__riscv_zcmt)
    li t0, MMISC_CTL_ZC
    csrs CSR_MMISC_CTL, t0
#endif

    /*
     * Intialize ECLIC vector interrupt
     * base address mtvt to vector_base
     */
    la t0, vector_base
    csrw CSR_MTVT, t0

    /*
     * Set ECLIC non-vector entry to be controlled
     * by mtvt2 CSR register.
     * Intialize ECLIC non-vector interrupt
     * base address mtvt2 to irq_entry.
```

(continues on next page)

(continued from previous page)

```
     */
    la t0, irq_entry
    csrw CSR_MTVT2, t0
    csrs CSR_MTVT2, 0x1

    /*
     * Set Exception Entry MTVEC to early_exc_entry
     * Due to settings above, Exception and NMI
     * will share common entry.
     * This early_exc_entry is only used during early
     * boot stage before main
     */
    la t0, early_exc_entry
    csrw CSR_MTVEC, t0

    /* Set the interrupt processing mode to ECLIC mode */
    li t0, 0x3f
    csrc CSR_MTVEC, t0
    csrs CSR_MTVEC, 0x3

    /* ===== Startup Stage 2 ===== */

    /* Enable FPU and Vector Unit if f/d/v exist in march */
#if defined(__riscv_flen) && __riscv_flen > 0
    /* Enable FPU, and set state to initial */
    li t0, MSTATUS_FS
    csrc mstatus, t0
    li t0, MSTATUS_FS_INITIAL
    csrs mstatus, t0
#endif

#if defined(__riscv_vector)
    /* Enable Vector, and set state to initial */
    li t0, MSTATUS_VS
    csrc mstatus, t0
    li t0, MSTATUS_VS_INITIAL
    csrs mstatus, t0
#endif

    /* Enable mcycle and minstret counter */
    csrci CSR_MCOUNTINHIBIT, 0x5

#if defined(SMP_CPU_CNT) && (SMP_CPU_CNT > 1)
    csrr a0, CSR_MHARTID
    li a1, BOOT_HARTID
    bne a0, a1, __skip_init
#endif

__init_common:
    /* ===== Startup Stage 3 ===== */
    /*
     * Load text section from CODE ROM to CODE RAM
```

(continues on next page)

(continued from previous page)

```
     * when text LMA is different with VMA
     */
    la a0, _text_lma
    la a1, _text
    /* If text LMA and VMA are equal
     * then no need to copy text section */
    beq a0, a1, 2f
    la a2, _etext
    bgeu a1, a2, 2f

1:
    /* Load code section if necessary */
    lw t0, (a0)
    sw t0, (a1)
    addi a0, a0, 4
    addi a1, a1, 4
    bltu a1, a2, 1b
2:
    /* Load data section */
    la a0, _data_lma
    la a1, _data
    /* If data vma=lma, no need to copy */
    beq a0, a1, 2f
    la a2, _edata
    bgeu a1, a2, 2f
1:
    lw t0, (a0)
    sw t0, (a1)
    addi a0, a0, 4
    addi a1, a1, 4
    bltu a1, a2, 1b
2:
    /* Clear bss section */
    la a0, __bss_start
    la a1, _end
    bgeu a0, a1, 2f
1:
    sw zero, (a0)
    addi a0, a0, 4
    bltu a0, a1, 1b
2:

.globl _start_premain
.type _start_premain, @function
_start_premain:
    /*
     * Call vendor defined SystemInit to
     * initialize the micro-controller system
     * SystemInit will just be called by boot cpu
     */
    call SystemInit

```

(continues on next page)

(continued from previous page)

```
    /*
     * Call C/C++ constructor start up code,
     * __libc_fini is defined in linker script,
     * so register_fini function will be called
     * and will run atexit (__libc_fini_array)
     * to do previous call atexit function
     */
    call __libc_init_array

__skip_init:
    /* Sync all harts at this function */
    call __sync_harts

    /* do pre-init steps before main */
    /* _premain_init will be called by each cpu
     * please make sure the implementation of __premain_int
     * considered this
     */
    call _premain_init

    /*
     * When all initialization steps done
     * set exception entry to correct exception
     * entry and jump to main.
     * And set the interrupt processing mode to
     * ECLIC mode
     */
    la t0, exc_entry
    csrw CSR_MTVEC, t0
    li t0, 0x3f
    csrc CSR_MTVEC, t0
    csrs CSR_MTVEC, 0x3

    /* BPU cold bringup need time, so enable BPU before enter to main */
    li t0, MMISC_CTL_BPU
    csrs CSR_MMISC_CTL, t0

    /* ===== Call SMP Main Function  ===== */
    /* argc = argv = 0 */
    li a0, 0
    li a1, 0
#if defined(SMP_CPU_CNT) && (SMP_CPU_CNT > 1)
    /* The weak implementation of smp_main is in this file */
    call smp_main
#else
#ifdef RTOS_RTTHREAD
    // Call entry function when using RT-Thread
    call entry
#else
    call main
#endif
#endif
```

(continues on next page)

(continued from previous page)

```
    /* do post-main steps after main
     * this function will be called by each cpu */
    call _postmain_fini

__amp_wait:
1:
    wfi
    j 1b

#if defined(SMP_CPU_CNT) && (SMP_CPU_CNT > 1)
/*
 * You can re-implement smp_main function in your code
 * to do smp boot process and handle multi harts
 */
.weak smp_main
.type smp_main, @function
smp_main:
    addi sp, sp, -2*REGBYTES
    STORE ra, 0*REGBYTES(sp)
    /* only boot hart goto main, other harts do wfi */
    csrr t0, CSR_MHARTID
    li t1, BOOT_HARTID
    beq t0, t1, 2f
1:
    wfi
    j 1b
2:
#ifdef RTOS_RTTHREAD
    // Call entry function when using RT-Thread
    call entry
#else
    call main
#endif
    LOAD ra, 0*REGBYTES(sp)
    addi sp, sp, 2*REGBYTES
    ret
#endif

/* Early boot exception entry before main */
.align 6
.global early_exc_entry
.type early_exc_entry, @function
early_exc_entry:
    wfi
    j early_exc_entry
```

Interrupt and Exception Handling File: intexc_<Device>.S

The intexc File intexc_<Device>.S contains:

- Macro to save caller register.
- Macro to restore caller register.
- Default Exception/NMI routine implementation.
- Default Non-Vector Interrupt routine implementation.

Nuclei processors provide **NMI(Non-Maskable Interrupt)**, **Exception**, **Vector Interrupt** and **Non-Vector Interrupt** features.

Note: To provide S-Mode interrupt and exception handling feature, we also provide a template file called intexc_<Device>_s.S

NMI(Non-Maskable Interrupt)

Click NMI[9] to learn about Nuclei Processor Core NMI in Nuclei ISA Spec.

NMI is used for urgent external HW error. It can't be masked and disabled.

When NMI happened, bit 9 of CSR `MMSIC_CTL` will be checked. If this bit value is 1, then NMI entry address will be the same as exception(CSR_MTVEC), and exception code for NMI will be 0xFFF, otherwise NMI entry will be same as reset_vector.

In NMSIS-Core, the bit 9 of CSR `MMISC_CTL` is set to 1 during core startup, so NMI will be treated as Exception and handled.

Exception

Click Exception[10] to learn about Nuclei Processor Core Exception in Nuclei ISA Spec.

For CPU exception, the entry for exception will be `exc_entry`, in this entry code, it will call default exception handler *`core_exception_handler()`* (page 633).

In the common exception routine(`exc_entry`) to get more information like exception code. Exception handle flow show as below picture:

NMI and exception could support nesting. Two levels of NMI/Exception state save stacks are supported.

We support three nesting mode as below:

- NMI nesting exception
- Exception nesting exception
- Exception nesting NMI

For software, we have provided the common entry for NMI and exception. Silicon vendor only need adapt the interface defined in *Interrupt Exception NMI Handling* (page 632).

Context save and restore have been handled by `exc_entry` interface.

[9] https://doc.nucleisys.com/nuclei_spec/isa/nmi.html
[10] https://doc.nucleisys.com/nuclei_spec/isa/exception.html



Fig. 3: Exception Handling Flow

When exception exception return it will run the instruction which trigger the exception again. It will cause software dead loop. So in the exception handler for each exception code, we propose to set CSR `MEPC` to be `MEPC+4`, then it will start from next instruction of MEPC.

Interrupt

Click Interrupt[11] to learn about Nuclei Processor Core Interrupt in Nuclei Spec.

Interrupt could be configured as **CLINT** mode or **ECILC** mode.

In NMSIS-Core, Interrupt has been configured as **ECLIC** mode during startup in *startup_<Devices>.S*, which is also recommended setting using Nuclei Processors.

ECLIC managed interrupt could configured as **vector** and **non-vector** mode.

Detail interrupt handling process as below picture:



Fig. 4: Interrupt Handling Flow

[11] https://doc.nucleisys.com/nuclei_spec/isa/interrupt.html

To get highest priority interrupt we need compare the interrupt level first.If level is the same then compare the priority. High level interrupt could interrupt low level ISR and trigger interrupt nesting. If different priority with same level interrupt pending higher priority will be served first. Interrupt could be configured as vector mode and non-vector mode by vendor. For non-vector mode interrupt handler entry get from MTVT2 and exception/NMI handler entry get from MTVEC. If Vendor need set non vector mode interrupt handler entry from `MTVVEC` you need set `MTVT2.BIT0` as 0.

Non-Vector Interrupt SW handler

For **non-vector** mode interrupt it will make the necessary CSR registers and context save and restore. Non-vector mode software handle flow show as below pciture:



Fig. 5: Non-vector mode interrupt software handle flow

Detail description for non-vector mode interrupt handler as below steps:

1. Get non-vector mode handler entry from `MTVT2` if `MTVT2.BIT0` is 1(proposed configuration).
2. Context save to stack for cpu registers.
3. Save CSR registers `MEPC/MCAUSE/MSUBM` to stack.

4. Run instruction `csrrw ra, CSR_JALMNXTI, ra`. It will enable interrupt, check interrupt pending. If interrupt is pending then get highest priority interrupt and jump to interrupt handler entry in the vector table, otherwise it will go to step 6.

5. Execute the interrupt handler routine, when return from isr routine it will jump to step 4.
6. Global interrupt disable.

7. Restore CSR registers `MEPC/MCAUSE/MSUBM`.
8. Context restore from stack for cpu registers.
9. Execute `mret` to return from handler.

For **non-vector** mode iterrupt it could support **interrupt nesting**.

Interrupt nesting handle flow show as below picture:



Fig. 6: Nesting interrupt handling flow

Vector Interrupt SW handler

If vector interrupt handler need support nesting or making function call Vector mode software handling flow show as below picture:



Fig. 7: Vector mode nesting interrupt handling flow

Detail description for nested vector mode interrupt handler as below steps:

1. Get vector mode handler from address of vector table entry `MTVT` added offset.
2. Context save to stack for cpu registers, done in each vector interrupt handler via `__INTERRUPT` (page 79)
3. Save CSR registers `MEPC/MCAUSE/MSUBM` to stack, done in each vector interrupt handler by read and save these CSRs into variables.
4. Execute the interrupt handling.
5. Restore CSR registers `MEPC/MCAUSE/MSUBM` from stack.
6. CSR registers restore from saved variables used in step 3.
7. Execute `mret` to return from handler

Here is sample code for above nested vector interrupt handling process:

```
// Vector interrupt handler for on-board button
__INTERRUPT void SOC_BUTTON_1_HANDLER(void)
{
    // save mepc,mcause,msubm enable interrupts
    SAVE_IRQ_CSR_CONTEXT();

    printf("%s", "----Begin button1 handler----Vector mode\r\n");

    // Green LED toggle
    gpio_toggle(GPIO, SOC_LED_GREEN_GPIO_MASK);

    // Clear the GPIO Pending interrupt by writing 1.
    gpio_clear_interrupt(GPIO, SOC_BUTTON_1_GPIO_OFS, GPIO_INT_RISE);

    wait_seconds(1); // Wait for a while

    printf("%s", "----End button1 handler\r\n");

    // disable interrupts,restore mepc,mcause,msubm
    RESTORE_IRQ_CSR_CONTEXT();
}
```

Detail description for non-nested vector mode interrupt handler as below

To improve the software response latency for vector mode vendor could remove context save/restore and **MEPC/MCAUSE/MSUBM** save/restore.

If so vector mode interrupt will not support nesting and interrupt handler can only be a leaf function which doesn't make any function calls.

Then the vector mode interrupt software flow will be described as below:

1. Get vector mode handler from address of vector table entry `MTVT` added offset.
2. Execute the interrupt handler(leaf function).
3. Execute `mret` to return from handler

Here is sample code for above non-nested vector interrupt handler which is a leaf function handling process:

```
static uint32_t btn_pressed = 0;
// Vector interrupt handler for on-board button
// This function is an leaf function, no function call is allowed
```

(continues on next page)

(continued from previous page)

```
__INTERRUPT void SOC_BUTTON_1_HANDLER(void)
{
    btn_pressed ++;
}
```

intexc_Device.S Template File

The file exists for each supported toolchain and is the only toolchain specific NMSIS file.

Normally this file needn't adapt for different device. If CPU CSR registers have done some changes you may need some adaption.

Here we provided `intexc_Device.S` template file as below:

```
/*
 * Copyright (c) 2019 Nuclei Limited. All rights reserved.
 *
 * SPDX-License-Identifier: Apache-2.0
 *
 * Licensed under the Apache License, Version 2.0 (the License); you may
 * not use this file except in compliance with the License.
 * You may obtain a copy of the License at
 *
 * www.apache.org/licenses/LICENSE-2.0
 *
 * Unless required by applicable law or agreed to in writing, software
 * distributed under the License is distributed on an AS IS BASIS, WITHOUT
 * WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 * See the License for the specific language governing permissions and
 * limitations under the License.
 */
/******************************************************************************
 * \file     intexc_<Device>.S
 * \brief    NMSIS Interrupt and Exception Handling Template File
 *           for Device <Device>
 * \version  V2.1.0
 * \date     19. Dec 2023
 *
 ******************************************************************************/

#include "riscv_encoding.h"

/**
 * \brief  Global interrupt disabled
 * \details
 *  This function disable global interrupt.
 * \remarks
 *  - All the interrupt requests will be ignored by CPU.
 */
.macro DISABLE_MIE
    csrc CSR_MSTATUS, MSTATUS_MIE
.endm
```

(continues on next page)

(continued from previous page)

```

/**
 * \brief  Macro for context save
 * \details
 * This macro save ABI defined caller saved registers in the stack.
 * \remarks
 * - This Macro could use to save context when you enter to interrupt
 * or exception
*/
/* Save caller registers */
.macro SAVE_CONTEXT
    /* Allocate stack space for context saving */
#ifndef __riscv_32e
    addi sp, sp, -20*REGBYTES
#else
    addi sp, sp, -14*REGBYTES
#endif /* __riscv_32e */

    STORE x1, 0*REGBYTES(sp)
    STORE x4, 1*REGBYTES(sp)
    STORE x5, 2*REGBYTES(sp)
    STORE x6, 3*REGBYTES(sp)
    STORE x7, 4*REGBYTES(sp)
    STORE x10, 5*REGBYTES(sp)
    STORE x11, 6*REGBYTES(sp)
    STORE x12, 7*REGBYTES(sp)
    STORE x13, 8*REGBYTES(sp)
    STORE x14, 9*REGBYTES(sp)
    STORE x15, 10*REGBYTES(sp)
#ifndef __riscv_32e
    STORE x16, 14*REGBYTES(sp)
    STORE x17, 15*REGBYTES(sp)
    STORE x28, 16*REGBYTES(sp)
    STORE x29, 17*REGBYTES(sp)
    STORE x30, 18*REGBYTES(sp)
    STORE x31, 19*REGBYTES(sp)
#endif /* __riscv_32e */
.endm

/**
 * \brief  Macro for restore caller registers
 * \details
 * This macro restore ABI defined caller saved registers from stack.
 * \remarks
 * - You could use this macro to restore context before you want return
 * from interrupt or exeception
 */
/* Restore caller registers */
.macro RESTORE_CONTEXT
    LOAD x1, 0*REGBYTES(sp)
    LOAD x4, 1*REGBYTES(sp)
    LOAD x5, 2*REGBYTES(sp)
```

(continues on next page)

(continued from previous page)

```
    LOAD x6, 3*REGBYTES(sp)
    LOAD x7, 4*REGBYTES(sp)
    LOAD x10, 5*REGBYTES(sp)
    LOAD x11, 6*REGBYTES(sp)
    LOAD x12, 7*REGBYTES(sp)
    LOAD x13, 8*REGBYTES(sp)
    LOAD x14, 9*REGBYTES(sp)
    LOAD x15, 10*REGBYTES(sp)
#ifndef __riscv_32e
    LOAD x16, 14*REGBYTES(sp)
    LOAD x17, 15*REGBYTES(sp)
    LOAD x28, 16*REGBYTES(sp)
    LOAD x29, 17*REGBYTES(sp)
    LOAD x30, 18*REGBYTES(sp)
    LOAD x31, 19*REGBYTES(sp)

    /* De-allocate the stack space */
    addi sp, sp, 20*REGBYTES
#else
    /* De-allocate the stack space */
    addi sp, sp, 14*REGBYTES
#endif /* __riscv_32e */

.endm

/**
 * \brief  Macro for save necessary CSRs to stack
 * \details
 * This macro store MCAUSE, MEPC, MSUBM to stack.
 */
.macro SAVE_CSR_CONTEXT
    /* Store CSR mcause to stack using pushmcause */
    csrrwi  x0, CSR_PUSHMCAUSE, 11
    /* Store CSR mepc to stack using pushmepc */
    csrrwi  x0, CSR_PUSHMEPC, 12
    /* Store CSR msub to stack using pushmsub */
    csrrwi  x0, CSR_PUSHMSUBM, 13
.endm

/**
 * \brief  Macro for restore necessary CSRs from stack
 * \details
 * This macro restore MSUBM, MEPC, MCAUSE from stack.
 */
.macro RESTORE_CSR_CONTEXT
    LOAD x5,  13*REGBYTES(sp)
    csrw CSR_MSUBM, x5
    LOAD x5,  12*REGBYTES(sp)
    csrw CSR_MEPC, x5
    LOAD x5,  11*REGBYTES(sp)
    csrw CSR_MCAUSE, x5
.endm
```

(continues on next page)

(continued from previous page)

```

/**
 * \brief  Exception/NMI Entry
 * \details
 * This function provide common entry functions for exception/nmi.
 * \remarks
 * This function provide a default exception/nmi entry.
 * ABI defined caller save register and some CSR registers
 * to be saved before enter interrupt handler and be restored before return.
 */
.section .text.trap
/* In CLIC mode, the exeception entry must be 64bytes aligned */
.align 6
# gnu let .weak override .globl, but llvm will show warning
# see https://reviews.llvm.org/D90108
.weak exc_entry
exc_entry:
    /* Save the caller saving registers (context) */
    SAVE_CONTEXT
    /* Save the necessary CSR registers */
    SAVE_CSR_CONTEXT

    /*
     * Set the exception handler function arguments
     * argument 1: mcause value
     * argument 2: current stack point(SP) value
     */
    csrr a0, mcause
    mv a1, sp
    /*
     * TODO: Call the exception handler function
     * By default, the function template is provided in
     * system_Device.c, you can adjust it as you want
     */
    call core_exception_handler

    /* Restore the necessary CSR registers */
    RESTORE_CSR_CONTEXT
    /* Restore the caller saving registers (context) */
    RESTORE_CONTEXT

    /* Return to regular code */
    mret

/**
 * \brief  Non-Vector Interrupt Entry
 * \details
 * This function provide common entry functions for handling
 * non-vector interrupts
 * \remarks
 * This function provide a default non-vector interrupt entry.
 * ABI defined caller save register and some CSR registers need
```

(continues on next page)

(continued from previous page)

```
 * to be saved before enter interrupt handler and be restored before return.
 */
.section      .text.irq
/* In CLIC mode, the interrupt entry must be 4bytes aligned */
.align 2
# gnu let .weak override .globl, but llvm will show warning
# see https://reviews.llvm.org/D90108
.weak irq_entry
/* This label will be set to MTVT2 register */
irq_entry:
    /* Save the caller saving registers (context) */
    SAVE_CONTEXT
    /* Save the necessary CSR registers */
    SAVE_CSR_CONTEXT

    /* This special CSR read/write operation, which is actually
     * claim the CLIC to find its pending highest ID, if the ID
     * is not 0, then automatically enable the mstatus.MIE, and
     * jump to its vector-entry-label, and update the link register
     */
    csrrw ra, CSR_JALMNXTI, ra

    /* Critical section with interrupts disabled */
    DISABLE_MIE

    /* Restore the necessary CSR registers */
    RESTORE_CSR_CONTEXT
    /* Restore the caller saving registers (context) */
    RESTORE_CONTEXT

    /* Return to regular code */
    mret

/* Default Handler for Exceptions / Interrupts */
# gnu let .weak override .globl, but llvm will show warning
# see https://reviews.llvm.org/D90108
.weak default_intexc_handler
Undef_Handler:
default_intexc_handler:
1:
    j 1b
```

Device Linker Script: gcc_<device>.ld

The Linker Script File gcc_<device>.ld contains:

- Memory base address and size.
- Code, data section, vector table etc. location.
- Stack & heap location and size.

The file exists for each supported toolchain and is the only toolchain specific NMSIS file.

To adapt the file to a new device only when you need change the memory base address, size, data and code location etc.

gcc_Device.ld Template File

Here we provided `gcc_Device.ld` template file as below:

```
/*
 * Copyright (c) 2019 Nuclei Limited. All rights reserved.
 *
 * SPDX-License-Identifier: Apache-2.0
 *
 * Licensed under the Apache License, Version 2.0 (the License); you may
 * not use this file except in compliance with the License.
 * You may obtain a copy of the License at
 *
 * www.apache.org/licenses/LICENSE-2.0
 *
 * Unless required by applicable law or agreed to in writing, software
 * distributed under the License is distributed on an AS IS BASIS, WITHOUT
 * WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 * See the License for the specific language governing permissions and
 * limitations under the License.
 */
/******************************************************************************
 * @file     gcc_<Device>.ld
 * @brief    GNU Linker Script for Device <Device>
 * @version  V2.1.0
 * @date     19. Dec 2023
 ******************************************************************************/

/*********** Use Configuration Wizard in Context Menu *************************/

OUTPUT_ARCH( "riscv" )
/********************* Flash Configuration ************************************
 * <h> Flash Configuration
 * <o0> Flash Base Address <0x0-0xFFFFFFFF:8>
 * <o1> Flash Size (in Bytes) <0x0-0xFFFFFFFF:8>
 * </h>
 */
__ROM_BASE = 0x20000000;
__ROM_SIZE = 0x00400000;

/*--------------------- ILM RAM Configuration ---------------------------
```

(continues on next page)

(continued from previous page)

```
 * <h> ILM RAM Configuration
 * <o0> ILM RAM Base Address    <0x0-0xFFFFFFFF:8>
 * <o1> ILM RAM Size (in Bytes) <0x0-0xFFFFFFFF:8>
 * </h>
 */
__ILM_RAM_BASE = 0x80000000;
__ILM_RAM_SIZE = 0x00010000;

/*--------------------- Embedded RAM Configuration ---------------------------
 * <h> RAM Configuration
 * <o0> RAM Base Address    <0x0-0xFFFFFFFF:8>
 * <o1> RAM Size (in Bytes) <0x0-0xFFFFFFFF:8>
 * </h>
*/
__RAM_BASE = 0x90000000;
__RAM_SIZE = 0x00010000;

/******************** Stack / Heap Configuration ****************************
 * <h> Stack / Heap Configuration
 * <o0> Stack Size (in Bytes) <0x0-0xFFFFFFFF:8>
 * <o1> Heap Size (in Bytes) <0x0-0xFFFFFFFF:8>
 * </h>
 */
__STACK_SIZE = 0x00000800;
__HEAP_SIZE  = 0x00000800;

/**************************** end of configuration section ********************/

/* Define entry label of program */
ENTRY(_start)
/* Define base address and length of flash and ram */
MEMORY
{
  flash (rxa!w) : ORIGIN = __ROM_BASE, LENGTH = __ROM_SIZE
  ram (wxa!r) : ORIGIN = __RAM_BASE, LENGTH = __RAM_SIZE
}

REGION_ALIAS("ROM", flash)
REGION_ALIAS("RAM", ram)

/* Linker script to place sections and symbol values. Should be used together
 * with other linker script that defines memory regions FLASH,ILM and RAM.
 * It references following symbols, which must be defined in code:
 *   _start : Entry of reset handler
 *
 * It defines following symbols, which code can use without definition:
 *   _ilm_lma ; deprecated
 *   _ilm     ; deprecated
 *   _eilm    ; deprecated
 *   _text_lma
 *   _text
 *   _etext
```

(continues on next page)

(continued from previous page)

```
 *   __etext
 *   etext
 *   __preinit_array_start
 *   __preinit_array_end
 *   __init_array_start
 *   __init_array_end
 *   __fini_array_start
 *   __fini_array_end
 *   _data_lma
 *   _edata
 *   edata
 *   __data_end__
 *   __bss_start
 *   __fbss
 *   _end
 *   end
 *   __heap_start
 *   __heap_end
 *   __heap_limit
 *   __StackLimit
 *   __StackBottom
 *   __StackTop
 *   __HEAP_SIZE
 *   __STACK_SIZE
 */

SECTIONS
{
  /* To provide symbol __STACK_SIZE, __HEAP_SIZE and __SMP_CPU_CNT */
  PROVIDE(__STACK_SIZE = 2K);
  PROVIDE(__HEAP_SIZE = 2K);
  PROVIDE(__SMP_CPU_CNT = 1);
  __TOT_STACK_SIZE = __STACK_SIZE * __SMP_CPU_CNT;

  .init           :
  {
    /* vector table locate at ROM */
    *(.text.vtable)
    *(.text.vtable_s)
    *(.text.init)
    KEEP (*(SORT_NONE(.init)))
    . = ALIGN(4);
  } >ROM AT>ROM

  /* Code section located at ROM */
  .text           :
  {
    *(.text.unlikely .text.unlikely.*)
    *(.text.startup .text.startup.*)
    . = ALIGN(8);
    PROVIDE( __jvt_base$ = . );
    *(.text.tbljal .text.tbljal.*)
```

(continues on next page)

(continued from previous page)

```
    *(.text .text.*)
    *(.gnu.linkonce.t.*)
    /* readonly data placed in ROM */
    . = ALIGN(8);
    *(.srodata.cst16)
    *(.srodata.cst8)
    *(.srodata.cst4)
    *(.srodata.cst2)
    *(.srodata .srodata.*)
    *(.rdata)
    *(.rodata .rodata.*)
    *(.gnu.linkonce.r.*)
    /* rtt */
    . = ALIGN(8);
    __rt_init_start = .;
    KEEP(*(SORT(.rti_fn*)))
    __rt_init_end = .;
    . = ALIGN(8);
    __fsymtab_start = .;
    KEEP(*(FSymTab))
    __fsymtab_end = .;
    . = ALIGN(8);
    __vsymtab_start = .;
    KEEP(*(VSymTab))
    __vsymtab_end = .;
    /* .fini */
    . = ALIGN(8);
    KEEP (*(SORT_NONE(.fini)))
    /* .preinit_array */
    . = ALIGN(8);
    PROVIDE_HIDDEN (__preinit_array_start = .);
    KEEP (*(.preinit_array))
    PROVIDE_HIDDEN (__preinit_array_end = .);
    /* .init_array */
    . = ALIGN(8);
    PROVIDE_HIDDEN (__init_array_start = .);
    KEEP (*(SORT_BY_INIT_PRIORITY(.init_array.*) SORT_BY_INIT_PRIORITY(.ctors.*)))
    KEEP (*(.init_array EXCLUDE_FILE (*crtbegin.o *crtbegin?.o *crtend.o *crtend?.o ) .
↪ctors))
    PROVIDE_HIDDEN (__init_array_end = .);
    /* .fini_array */
    . = ALIGN(8);
    PROVIDE_HIDDEN (__fini_array_start = .);
    PROVIDE_HIDDEN (__libc_fini = _fini);
    KEEP (*(SORT_BY_INIT_PRIORITY(.fini_array.*) SORT_BY_INIT_PRIORITY(.dtors.*)))
    KEEP (*(.fini_array EXCLUDE_FILE (*crtbegin.o *crtbegin?.o *crtend.o *crtend?.o ) .
↪dtors))
    PROVIDE_HIDDEN (__fini_array_end = .);
    /* .ctors */
    . = ALIGN(8);
    KEEP (*crtbegin.o(.ctors))
    KEEP (*crtbegin?.o(.ctors))
```

(continues on next page)

(continued from previous page)

```
    KEEP (*(EXCLUDE_FILE (*crtend.o *crtend?.o ) .ctors))
    KEEP (*(SORT(.ctors.*)))
    KEEP (*(.ctors))
    /* .dtors */
    . = ALIGN(8);
    KEEP (*crtbegin.o(.dtors))
    KEEP (*crtbegin?.o(.dtors))
    KEEP (*(EXCLUDE_FILE (*crtend.o *crtend?.o ) .dtors))
    KEEP (*(SORT(.dtors.*)))
    KEEP (*(.dtors))
  } >ROM AT>ROM

  PROVIDE( _ilm_lma = LOADADDR(.text) );
  PROVIDE( _ilm = ADDR(.text) );
  PROVIDE( _eilm = . );
  PROVIDE( _text_lma = LOADADDR(.text) );
  PROVIDE( _text = ADDR(.text) );
  PROVIDE (_etext = .);
  PROVIDE (__etext = .);
  PROVIDE (etext = .);

  .data            : ALIGN(8)
  {
    KEEP(*(.data.ctest*))
    *(.data .data.*)
    *(.gnu.linkonce.d.*)
    . = ALIGN(8);
    PROVIDE( __global_pointer$ = . + 0x800 );
    *(.sdata .sdata.* .sdata*)
    *(.gnu.linkonce.s.*)
    . = ALIGN(8);
  } >RAM AT>ROM

  .tdata           : ALIGN(8)
  {
    PROVIDE( __tls_base = . );
    *(.tdata .tdata.* .gnu.linkonce.td.*)
  } >RAM AT>ROM

  PROVIDE( _data_lma = LOADADDR(.data) );
  PROVIDE( _data = ADDR(.data) );
  PROVIDE( _edata = . );
  PROVIDE( edata = . );

  PROVIDE( _fbss = . );
  PROVIDE( __bss_start = . );

  .tbss (NOLOAD)   : ALIGN(8)
  {
    *(.tbss .tbss.* .gnu.linkonce.tb.*)
    *(.tcommon)
    PROVIDE( __tls_end = . );
```

(continues on next page)

(continued from previous page)

```
  } >RAM AT>RAM

  .tbss_space (NOLOAD) : ALIGN(8)
  {
    . = . + SIZEOF(.tbss);
  } >RAM AT>RAM

  .bss (NOLOAD)   : ALIGN(8)
  {
    *(.sbss*)
    *(.gnu.linkonce.sb.*)
    *(.bss .bss.*)
    *(.gnu.linkonce.b.*)
    *(COMMON)
    . = ALIGN(4);
  } >RAM AT>RAM

  PROVIDE( _end = . );
  PROVIDE( end = . );

  /* Nuclei C Runtime Library requirements:
   * 1. heap need to be align at 16 bytes
   * 2. __heap_start and __heap_end symbol need to be defined
   * 3. reserved at least __HEAP_SIZE space for heap
   */
  .heap (NOLOAD)   : ALIGN(16)
  {
    . = ALIGN(16);
    PROVIDE( __heap_start = . );
    . += __HEAP_SIZE;
    . = ALIGN(16);
    PROVIDE( __heap_limit = . );
  } >RAM AT>RAM

  .stack ORIGIN(RAM) + LENGTH(RAM) - __TOT_STACK_SIZE (NOLOAD) :
  {
    . = ALIGN(16);
    PROVIDE( _heap_end = . );
    PROVIDE( __heap_end = . );
    PROVIDE( __StackLimit = . );
    PROVIDE( __StackBottom = . );
    . += __TOT_STACK_SIZE;
    . = ALIGN(16);
    PROVIDE( __StackTop = . );
    PROVIDE( _sp = . );
  } >RAM AT>RAM
}
```

System Configuration Files system_<Device>.c and system_<Device>.h

The **System Configuration Files system_<device>.c and system_<device>.h** provides as a minimum the functions described under *System Device Configuration* (page 628).

These functions are device specific and need adaptations. In addition, the file might have configuration settings for the device such as XTAL frequency or PLL prescaler settings, necessary system initialization, vendor customized interrupt, exception and nmi handling code, refer to *System Device Configuration* (page 628) for more details.

For devices with external memory BUS the `system_<Device>.c` also configures the BUS system.

The silicon vendor might expose other functions (i.e. for power configuration) in the `system_<Device>.c` file. In case of additional features the function prototypes need to be added to the `system_<Device>.h` header file.

system_Device.c Template File

Here we provided `system_Device.c` template file as below:

```
/*
 * Copyright (c) 2009-2018 Arm Limited. All rights reserved.
 * Copyright (c) 2019 Nuclei Limited. All rights reserved.
 *
 * SPDX-License-Identifier: Apache-2.0
 *
 * Licensed under the Apache License, Version 2.0 (the License); you may
 * not use this file except in compliance with the License.
 * You may obtain a copy of the License at
 *
 * www.apache.org/licenses/LICENSE-2.0
 *
 * Unless required by applicable law or agreed to in writing, software
 * distributed under the License is distributed on an AS IS BASIS, WITHOUT
 * WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 * See the License for the specific language governing permissions and
 * limitations under the License.
 */
/******************************************************************************
 * @file     system_<Device>.c
 * @brief    NMSIS Nuclei N/NX Device Peripheral Access Layer Source File for
 *           Device <Device>
 * @version  V2.0.0
 * @date     30. Dec 2022
 ******************************************************************************/

#include <stdint.h>
#include "<Device>.h"
#include <stdio.h>

/*----------------------------------------------------------------------------
  Define clocks
 *----------------------------------------------------------------------------*/
/* ToDo: add here your necessary defines for device initialization
         following is an example for different system frequencies */
#ifndef SYSTEM_CLOCK
```

(continues on next page)

(continued from previous page)

```
#define SYSTEM_CLOCK    (80000000UL)
#endif

/**
 * \defgroup  NMSIS_Core_SystemConfig       System Device Configuration
 * \brief Functions for system and clock setup available in system_<device>.c.
 * \details
 * Nuclei provides a template file **system_Device.c** that must be adapted by
 * the silicon vendor to match their actual device. As a <b>minimum requirement</b>,
 * this file must provide:
 *  -  A device-specific system configuration function, \ref SystemInit.
 *  -  Global c library \ref _premain_init and \ref _postmain_fini functions called right before calling main function.
 *     -  A global variable that contains the system frequency, \ref SystemCoreClock.
 *     -  A global eclic configuration initialization, \ref ECLIC_Init.
 *     -  A global exception and trap configuration initialization, \ref Trap_Init and \ref Exception_Init.
 *  -  Vendor customized interrupt, exception and nmi handling code, see \ref NMSIS_Core_IntExcNMI_Handling
 *
 * The file configures the device and, typically, initializes the oscillator (PLL) that is part
 * of the microcontroller device. This file might export other functions or variables that provide
 * a more flexible configuration of the microcontroller system.
 *
 * And this file also provided common interrupt, exception and NMI exception handling framework template,
 * Silicon vendor can customize these template code as they want.
 *
 * \note Please pay special attention to the static variable \c SystemCoreClock. This variable might be
 * used throughout the whole system initialization and runtime to calculate frequency/time related values.
 * Thus one must assure that the variable always reflects the actual system clock speed.
 *
 * \attention
 * Be aware that a value stored to \c SystemCoreClock during low level initialization (i.e. \c SystemInit()) might get
 * overwritten by C libray startup code and/or .bss section initialization.
 * Thus its highly recommended to call \ref SystemCoreClockUpdate at the beginning of the user \c main() routine.
 *
 * @{
 */
#if defined(__TEE_PRESENT) && (__TEE_PRESENT == 1)

typedef void (*fnptr)(void);

/* for the following variables, see intexc_evalsoc.S and intexc_evalsoc_s.S */
/** default entry for s-mode non-vector irq entry */
extern fnptr irq_entry_s;
```

(continues on next page)

(continued from previous page)

```
/** default entry for s-mode exception entry */
extern fnptr exc_entry_s;
/** default eclic interrupt or exception interrupt handler */
extern void default_intexc_handler(void);

/** eclic s-mode software interrupt handler in eclic mode */
extern void eclic_ssip_handler(void) __WEAK;
/** eclic s-mode time interrupt handler in eclic mode */
extern void eclic_stip_handler(void) __WEAK;

/* default s-mode exception handler, which user can modify it at your need */
static void system_default_exception_handler_s(unsigned long scause, unsigned long sp);

#ifndef __ICCRISCV__
#define __SMODE_VECTOR_ATTR   __attribute__((section (".text.vtable_s"), aligned(512)))
#else
#define __SMODE_VECTOR_ATTR   __attribute__((section (".sintvec"), aligned(512)))
#endif
// TODO: change the aligned(512) to match stvt alignment requirement according to your eclic max interrupt number
// TODO: place your interrupt handler into this vector table, important if your vector table is in flash
/**
 * \var unsigned long vector_table_s[SOC_INT_MAX]
 * \brief vector interrupt storing ISRs for supervisor mode
 * \details
 *  vector_table_s is hold by stvt register, the address must align according
 *  to actual interrupt numbers as below, now align to 512 bytes considering we put up to 128 interrupts here
 *  alignment must comply to table below if you increase or decrease vector interrupt number
 *  interrupt number      alignment
 *    0 to 16               64-byte
 *    17 to 32              128-byte
 *    33 to 64              256-byte
 *    65 to 128             512-byte
 *    129 to 256              1KB
 *    257 to 512              2KB
 *    513 to 1024             4KB
 */
const unsigned long vector_table_s[SOC_INT_MAX] __SMODE_VECTOR_ATTR =
{
    (unsigned long)(default_intexc_handler),        /* 0: Reserved */
    (unsigned long)(default_intexc_handler),        /* 1: Reserved */
    (unsigned long)(default_intexc_handler),        /* 2: Reserved */

    (unsigned long)(eclic_ssip_handler),            /* 3: supervisor software interrupt in eclic mode */

    (unsigned long)(default_intexc_handler),        /* 4: Reserved */
    (unsigned long)(default_intexc_handler),        /* 5: Reserved */
    (unsigned long)(default_intexc_handler),        /* 6: Reserved */
```

(continues on next page)

(continued from previous page)

```c

    (unsigned long)(eclic_stip_handler),          /* 7: supervisor timer interrupt in␣
↪eclic mode */

    (unsigned long)(default_intexc_handler),      /* 8: Reserved */
    (unsigned long)(default_intexc_handler),      /* 9: Reserved */
    (unsigned long)(default_intexc_handler),      /* 10: Reserved */
    (unsigned long)(default_intexc_handler),      /* 11: Reserved */

    (unsigned long)(default_intexc_handler),      /* 12: Reserved */
    (unsigned long)(default_intexc_handler),      /* 13: Reserved */
    (unsigned long)(default_intexc_handler),      /* 14: Reserved */
    (unsigned long)(default_intexc_handler),      /* 15: Reserved */

    (unsigned long)(default_intexc_handler),      /* 16: Reserved */
    (unsigned long)(default_intexc_handler),      /* 17: Reserved */
    (unsigned long)(default_intexc_handler),      /* 18: Reserved */
    (unsigned long)(default_intexc_handler),      /* 19: Interrupt 19 */

    (unsigned long)(default_intexc_handler),      /* 20: Interrupt 20 */
    (unsigned long)(default_intexc_handler),      /* 21: Interrupt 21 */
    (unsigned long)(default_intexc_handler),      /* 22: Interrupt 22 */
    (unsigned long)(default_intexc_handler),      /* 23: Interrupt 23 */

    (unsigned long)(default_intexc_handler),      /* 24: Interrupt 24 */
    (unsigned long)(default_intexc_handler),      /* 25: Interrupt 25 */
    (unsigned long)(default_intexc_handler),      /* 26: Interrupt 26 */
    (unsigned long)(default_intexc_handler),      /* 27: Interrupt 27 */

    (unsigned long)(default_intexc_handler),      /* 28: Interrupt 28 */
    (unsigned long)(default_intexc_handler),      /* 29: Interrupt 29 */
    (unsigned long)(default_intexc_handler),      /* 30: Interrupt 30 */
    (unsigned long)(default_intexc_handler),      /* 31: Interrupt 31 */

    (unsigned long)(default_intexc_handler),      /* 32: Interrupt 32 */
    (unsigned long)(default_intexc_handler),      /* 33: Interrupt 33 */
    (unsigned long)(default_intexc_handler),      /* 34: Interrupt 34 */
    (unsigned long)(default_intexc_handler),      /* 35: Interrupt 35 */

    (unsigned long)(default_intexc_handler),      /* 36: Interrupt 36 */
    (unsigned long)(default_intexc_handler),      /* 37: Interrupt 37 */
    (unsigned long)(default_intexc_handler),      /* 38: Interrupt 38 */
    (unsigned long)(default_intexc_handler),      /* 39: Interrupt 39 */

    (unsigned long)(default_intexc_handler),      /* 40: Interrupt 40 */
    (unsigned long)(default_intexc_handler),      /* 41: Interrupt 41 */
    (unsigned long)(default_intexc_handler),      /* 42: Interrupt 42 */
    (unsigned long)(default_intexc_handler),      /* 43: Interrupt 43 */

    (unsigned long)(default_intexc_handler),      /* 44: Interrupt 44 */
    (unsigned long)(default_intexc_handler),      /* 45: Interrupt 45 */
    (unsigned long)(default_intexc_handler),      /* 46: Interrupt 46 */
```

(continues on next page)

(continued from previous page)

```
    (unsigned long)(default_intexc_handler),        /* 47: Interrupt 47 */

    (unsigned long)(default_intexc_handler),        /* 48: Interrupt 48 */
    (unsigned long)(default_intexc_handler),        /* 49: Interrupt 49 */
    (unsigned long)(default_intexc_handler),        /* 50: Interrupt 50 */
    (unsigned long)(default_intexc_handler),        /* 51: Interrupt 51 */

    (unsigned long)(default_intexc_handler),        /* 52: Interrupt 52 */
    (unsigned long)(default_intexc_handler),        /* 53: Interrupt 53 */
    (unsigned long)(default_intexc_handler),        /* 54: Interrupt 54 */
    (unsigned long)(default_intexc_handler),        /* 55: Interrupt 55 */

    (unsigned long)(default_intexc_handler),        /* 56: Interrupt 56 */
    (unsigned long)(default_intexc_handler),        /* 57: Interrupt 57 */
    (unsigned long)(default_intexc_handler),        /* 58: Interrupt 58 */
    (unsigned long)(default_intexc_handler),        /* 59: Interrupt 59 */

    (unsigned long)(default_intexc_handler),        /* 60: Interrupt 60 */
    (unsigned long)(default_intexc_handler),        /* 61: Interrupt 61 */
    (unsigned long)(default_intexc_handler),        /* 62: Interrupt 62 */
    (unsigned long)(default_intexc_handler),        /* 63: Interrupt 63 */
};
#endif
/*----------------------------------------------------------------------------
  System Core Clock Variable
 *----------------------------------------------------------------------------*/
/* ToDo: initialize SystemCoreClock with the system core clock frequency value
         achieved after system intitialization.
         This means system core clock frequency after call to SystemInit() */
/**
 * \brief      Variable to hold the system core clock value
 * \details
 * Holds the system core clock, which is the system clock frequency supplied to the SysTick
 * timer and the processor core clock. This variable can be used by debuggers to query the
 * frequency of the debug timer or to configure the trace clock speed.
 *
 * \attention
 * Compilers must be configured to avoid removing this variable in case the application
 * program is not using it. Debugging systems require the variable to be physically
 * present in memory so that it can be examined to configure the debugger.
 */
volatile uint32_t SystemCoreClock = SYSTEM_CLOCK;  /* System Clock Frequency (Core Clock) */

/*----------------------------------------------------------------------------
  Clock functions
 *----------------------------------------------------------------------------*/

/**
 * \brief      Function to update the variable \ref SystemCoreClock
```

(continues on next page)

(continued from previous page)

```
 * \details
 * Updates the variable \ref SystemCoreClock and must be called whenever the core clock is changed
 * during program execution. The function evaluates the clock register settings and calculates
 * the current core clock.
 */
void SystemCoreClockUpdate(void)             /* Get Core Clock Frequency */
{
    /* ToDo: add code to calculate the system frequency based upon the current
     *    register settings.
     * Note: This function can be used to retrieve the system core clock frequeny
     *    after user changed register settings.
     */
    SystemCoreClock = SYSTEM_CLOCK;
}

/**
 * \brief      Function to Initialize the system.
 * \details
 * Initializes the microcontroller system. Typically, this function configures the
 * oscillator (PLL) that is part of the microcontroller device. For systems
 * with a variable clock speed, it updates the variable \ref SystemCoreClock.
 * SystemInit is called from the file <b>startup<i>_device</i></b>.
 */
void SystemInit(void)
{
    /* ToDo: add code to initialize the system
     * Warn: do not use global variables because this function is called before
     * reaching pre-main. RW section maybe overwritten afterwards.
     */
    SystemCoreClock = SYSTEM_CLOCK;
}

/**
 * \defgroup  NMSIS_Core_IntExcNMI_Handling   Interrupt and Exception and NMI Handling
 * \brief Functions for interrupt, exception and nmi handle available in system_<device>.c.
 * \details
 * Nuclei provide a template for interrupt, exception and NMI handling. Silicon Vendor could adapat according
 * to their requirement. Silicon vendor could implement interface for different exception code and
 * replace current implementation.
 *
 * @{
 */
/** \brief Max exception handler number, don't include the NMI(0xFFF) one */
#define MAX_SYSTEM_EXCEPTION_NUM        26
/**
 * \brief      Store the exception handlers for each exception ID
 * \note
```

(continues on next page)

(continued from previous page)

```c
 * - This SystemExceptionHandlers are used to store all the handlers for all
 * the exception codes Nuclei N/NX core provided.
 * - Exception code 0 - 25, totally 26 exceptions are mapped to SystemExceptionHandlers[0:25]
 * - Exception for NMI is also re-routed to exception handling(exception code 0xFFF) in startup code configuration, the handler itself is mapped to SystemExceptionHandlers[MAX_SYSTEM_EXCEPTION_NUM]
 */
static unsigned long SystemExceptionHandlers[MAX_SYSTEM_EXCEPTION_NUM + 1];

/**
 * \brief      Store the exception handlers for each exception ID in supervisor mode
 * \note
 * - This SystemExceptionHandlers_S are used to store all the handlers for all
 * the exception codes Nuclei N/NX core provided.
 * - Exception code 0 - 11, totally 12 exceptions are mapped to SystemExceptionHandlers_S[0:11]
 * - The NMI (Non-maskable-interrupt) cannot be trapped to the supervisor-mode or user-mode for any configuration
 */
#if defined(__TEE_PRESENT) && (__TEE_PRESENT == 1)
static unsigned long SystemExceptionHandlers_S[MAX_SYSTEM_EXCEPTION_NUM];
#endif
/**
 * \brief      Exception Handler Function Typedef
 * \note
 * This typedef is only used internal in this system_<Device>.c file.
 * It is used to do type conversion for registered exception handler before calling it.
 */
typedef void (*EXC_HANDLER)(unsigned long cause, unsigned long sp);

/**
 * \brief      System Default Exception Handler
 * \details
 * This function provides a default exception and NMI handler for all exception ids.
 * By default, It will just print some information for debug, Vendor can customize it according to its requirements.
 * \param [in]  mcause    code indicating the reason that caused the trap in machine mode
 * \param [in]  sp        stack pointer
 */
static void system_default_exception_handler(unsigned long mcause, unsigned long sp)
{
    /* TODO: Uncomment this if you have implement printf function */
    printf("MCAUSE : 0x%lx\r\n", mcause);
    printf("MDCAUSE: 0x%lx\r\n", __RV_CSR_READ(CSR_MDCAUSE));
    printf("MEPC   : 0x%lx\r\n", __RV_CSR_READ(CSR_MEPC));
    printf("MTVAL  : 0x%lx\r\n", __RV_CSR_READ(CSR_MTVAL));
    printf("HARTID : %u\r\n", (unsigned int)__get_hart_id());
    Exception_DumpFrame(sp, PRV_M);
#if defined(SIMULATION_MODE)
    // directly exit if in SIMULATION
    extern void simulation_exit(int status);
```

(continues on next page)

(continued from previous page)

```c
    simulation_exit(1);
#else
    while (1);
#endif
}

/**
 * \brief      Initialize all the default core exception handlers
 * \details
 * The core exception handler for each exception id will be initialized to \ref system_default_exception_handler.
 * \note
 * Called in \ref _init function, used to initialize default exception handlers for all exception IDs
 * SystemExceptionHandlers contains NMI, but SystemExceptionHandlers_S not, because NMI can't be delegated to S-mode.
 */
static void Exception_Init(void)
{
    for (int i = 0; i < MAX_SYSTEM_EXCEPTION_NUM; i++) {
        SystemExceptionHandlers[i] = (unsigned long)system_default_exception_handler;
#if defined(__TEE_PRESENT) && (__TEE_PRESENT == 1)
        SystemExceptionHandlers_S[i] = (unsigned long)system_default_exception_handler_s;
#endif
    }
    SystemExceptionHandlers[MAX_SYSTEM_EXCEPTION_NUM] = (unsigned long)system_default_exception_handler;
}

/**
 * \brief      Dump Exception Frame
 * \details
 * This function provided feature to dump exception frame stored in stack.
 * \param [in]  sp    stackpoint
 * \param [in]  mode  privileged mode to decide whether to dump msubm CSR
 */
void Exception_DumpFrame(unsigned long sp, uint8_t mode)
{
    EXC_Frame_Type *exc_frame = (EXC_Frame_Type *)sp;

#ifndef __riscv_32e
    printf("ra: 0x%lx, tp: 0x%lx, t0: 0x%lx, t1: 0x%lx, t2: 0x%lx, t3: 0x%lx, t4: 0x%lx, t5: 0x%lx, t6: 0x%lx\n" \
           "a0: 0x%lx, a1: 0x%lx, a2: 0x%lx, a3: 0x%lx, a4: 0x%lx, a5: 0x%lx, a6: 0x%lx, a7: 0x%lx\n" \
           "cause: 0x%lx, epc: 0x%lx\n", exc_frame->ra, exc_frame->tp, exc_frame->t0, \
           exc_frame->t1, exc_frame->t2, exc_frame->t3, exc_frame->t4, exc_frame->t5, exc_frame->t6, \
           exc_frame->a0, exc_frame->a1, exc_frame->a2, exc_frame->a3, exc_frame->a4, exc_frame->a5, \
           exc_frame->a6, exc_frame->a7, exc_frame->cause, exc_frame->epc);
#else
```

(continues on next page)

(continued from previous page)

```c
    printf("ra: 0x%lx, tp: 0x%lx, t0: 0x%lx, t1: 0x%lx, t2: 0x%lx\n" \
           "a0: 0x%lx, a1: 0x%lx, a2: 0x%lx, a3: 0x%lx, a4: 0x%lx, a5: 0x%lx\n" \
           "cause: 0x%lx, epc: 0x%lx\n", exc_frame->ra, exc_frame->tp, exc_frame->t0, \
           exc_frame->t1, exc_frame->t2, exc_frame->a0, exc_frame->a1, exc_frame->a2, exc_frame->a3, \
           exc_frame->a4, exc_frame->a5, exc_frame->cause, exc_frame->epc);
#endif

    if (PRV_M == mode) {
        /* msubm is exclusive to machine mode */
        printf("msubm: 0x%lx\n", exc_frame->msubm);
    }
}

/**
 * \brief       Register an exception handler for exception code EXCn
 * \details
 * - For EXCn < \ref MAX_SYSTEM_EXCEPTION_NUM, it will be registered into SystemExceptionHandlers[EXCn-1].
 * - For EXCn == NMI_EXCn, it will be registered into SystemExceptionHandlers[MAX_SYSTEM_EXCEPTION_NUM].
 * \param [in]  EXCn    See \ref EXCn_Type
 * \param [in]  exc_handler     The exception handler for this exception code EXCn
 */
void Exception_Register_EXC(uint32_t EXCn, unsigned long exc_handler)
{
    if (EXCn < MAX_SYSTEM_EXCEPTION_NUM) {
        SystemExceptionHandlers[EXCn] = exc_handler;
    } else if (EXCn == NMI_EXCn) {
        SystemExceptionHandlers[MAX_SYSTEM_EXCEPTION_NUM] = exc_handler;
    }
}

/**
 * \brief       Get current exception handler for exception code EXCn
 * \details
 * - For EXCn < \ref MAX_SYSTEM_EXCEPTION_NUM, it will return SystemExceptionHandlers[EXCn-1].
 * - For EXCn == NMI_EXCn, it will return SystemExceptionHandlers[MAX_SYSTEM_EXCEPTION_NUM].
 * \param [in]  EXCn    See \ref EXCn_Type
 * \return  Current exception handler for exception code EXCn, if not found, return 0.
 */
unsigned long Exception_Get_EXC(uint32_t EXCn)
{
    if (EXCn < MAX_SYSTEM_EXCEPTION_NUM) {
        return SystemExceptionHandlers[EXCn];
    } else if (EXCn == NMI_EXCn) {
        return SystemExceptionHandlers[MAX_SYSTEM_EXCEPTION_NUM];
    } else {
        return 0;
    }
```

(continues on next page)

(continued from previous page)

```c
}

/**
 * \brief      Common NMI and Exception handler entry
 * \details
 * This function provided a command entry for NMI and exception. Silicon Vendor could modify
 * this template implementation according to requirement.
 * \param [in]  mcause    code indicating the reason that caused the trap in machine mode
 * \param [in]  sp        stack pointer
 * \remarks
 * - RISCV provided common entry for all types of exception. This is proposed code template
 *   for exception entry function, Silicon Vendor could modify the implementation.
 * - For the core_exception_handler template, we provided exception register function \ref Exception_Register_EXC
 *   which can help developer to register your exception handler for specific exception number.
 */
uint32_t core_exception_handler(unsigned long mcause, unsigned long sp)
{
    uint32_t EXCn = (uint32_t)(mcause & 0X00000fff);
    EXC_HANDLER exc_handler;

    if (EXCn < MAX_SYSTEM_EXCEPTION_NUM) {
        exc_handler = (EXC_HANDLER)SystemExceptionHandlers[EXCn];
    } else if (EXCn == NMI_EXCn) {
        exc_handler = (EXC_HANDLER)SystemExceptionHandlers[MAX_SYSTEM_EXCEPTION_NUM];
    } else {
        exc_handler = (EXC_HANDLER)system_default_exception_handler;
    }
    if (exc_handler != NULL) {
        exc_handler(mcause, sp);
    }
    return 0;
}

#if defined(__TEE_PRESENT) && (__TEE_PRESENT == 1)
/**
 * \brief      Supervisor mode system Default Exception Handler
 * \details
 * This function provided a default supervisor mode exception and NMI handling code for all exception ids.
 * By default, It will just print some information for debug, Vendor can customize it according to its requirements.
 * \param [in]  scause    code indicating the reason that caused the trap in supervisor mode
 * \param [in]  sp        stack pointer
 */
static void system_default_exception_handler_s(unsigned long scause, unsigned long sp)
{
    /* TODO: Uncomment this if you have implement printf function */
```

(continues on next page)

(continued from previous page)

```
    printf("SCAUSE : 0x%lx\r\n", scause);
    printf("SDCAUSE: 0x%lx\r\n", __RV_CSR_READ(CSR_SDCAUSE));
    printf("SEPC   : 0x%lx\r\n", __RV_CSR_READ(CSR_SEPC));
    printf("STVAL  : 0x%lx\r\n", __RV_CSR_READ(CSR_STVAL));
    Exception_DumpFrame(sp, PRV_S);
#if defined(SIMULATION_MODE)
    // directly exit if in SIMULATION
    extern void simulation_exit(int status);
    simulation_exit(1);
#else
    while (1);
#endif
}

/**
 * \brief       Register an exception handler for exception code EXCn of supervisor mode
 * \details
 * -For EXCn < \ref MAX_SYSTEM_EXCEPTION_NUM, it will be registered into␣
↪SystemExceptionHandlers_S[EXCn-1].
 * -For EXCn == NMI_EXCn, The NMI (Non-maskable-interrupt) cannot be trapped to the␣
↪supervisor-mode or user-mode for any
 *    configuration, so NMI won't be registered into SystemExceptionHandlers_S.
 * \param [in]  EXCn            See \ref EXCn_Type
 * \param [in]  exc_handler     The exception handler for this exception code EXCn
 */
void Exception_Register_EXC_S(uint32_t EXCn, unsigned long exc_handler)
{
    if (EXCn < MAX_SYSTEM_EXCEPTION_NUM) {
        SystemExceptionHandlers_S[EXCn] = exc_handler;
    }
}

/**
 * \brief       Get current exception handler for exception code EXCn of supervisor mode
 * \details
 * - For EXCn < \ref MAX_SYSTEM_EXCEPTION_NUM, it will return SystemExceptionHandlers_
↪S[EXCn-1].
 * \param [in]  EXCn    See \ref EXCn_Type
 * \return  Current exception handler for exception code EXCn, if not found, return 0.
 */
unsigned long Exception_Get_EXC_S(uint32_t EXCn)
{
    if (EXCn < MAX_SYSTEM_EXCEPTION_NUM) {
        return SystemExceptionHandlers[EXCn];
    } else {
        return 0;
    }
}

/**
 * \brief      common Exception handler entry of supervisor mode
 * \details
```

(continues on next page)

(continued from previous page)

```c
 * This function provided a supervisor mode common entry for exception. Silicon Vendor␣
↪could modify
 * this template implementation according to requirement.
 * \param [in]  scause    code indicating the reason that caused the trap in supervisor␣
↪mode
 * \param [in]  sp        stack pointer
 * \remarks
 * - RISCV provided supervisor mode common entry for all types of exception. This is␣
↪proposed code template
 *   for exception entry function, Silicon Vendor could modify the implementation.
 * - For the core_exception_handler_s template, we provided exception register function \
↪ref Exception_Register_EXC_S
 *   which can help developer to register your exception handler for specific exception␣
↪number.
 */
uint32_t core_exception_handler_s(unsigned long scause, unsigned long sp)
{
    uint32_t EXCn = (uint32_t)(scause & 0X00000fff);
    EXC_HANDLER exc_handler;

    if (EXCn < MAX_SYSTEM_EXCEPTION_NUM) {
        exc_handler = (EXC_HANDLER)SystemExceptionHandlers_S[EXCn];
    } else {
        exc_handler = (EXC_HANDLER)system_default_exception_handler_s;
    }
    if (exc_handler != NULL) {
        exc_handler(scause, sp);
    }
    return 0;
}
#endif

/** @} */ /* End of Doxygen Group NMSIS_Core_ExceptionAndNMI */

/** Banner Print for Nuclei SDK */
void SystemBannerPrint(void)
{
#if defined(NUCLEI_BANNER) && (NUCLEI_BANNER == 1)
    printf("Nuclei SDK Build Time: %s, %s\r\n", __DATE__, __TIME__);
#ifdef DOWNLOAD_MODE_STRING
    printf("Download Mode: %s\r\n", DOWNLOAD_MODE_STRING);
#endif
    printf("CPU Frequency %u Hz\r\n", (unsigned int)SystemCoreClock);
    printf("CPU HartID: %u\r\n", (unsigned int)__get_hart_id());
#endif
}

/**
 * \brief initialize eclic config
 * \details
 * ECLIC needs be initialized after boot up,
 * Vendor could also change the initialization
```

(continues on next page)

(continued from previous page)

```
 * configuration.
 */
void ECLIC_Init(void)
{
    /* Global Configuration about MTH and NLBits.
     * TODO: Please adapt it according to your system requirement.
     * This function is called in _init function */
    ECLIC_SetMth(0);
    ECLIC_SetCfgNlbits(__ECLIC_INTCTLBITS);

#if defined(__TEE_PRESENT) && (__TEE_PRESENT == 1)
    /* Global Configuration about STH */
    ECLIC_SetSth(0);
#endif
}

/**
 * \brief  Initialize a specific IRQ and register the handler
 * \details
 * This function set vector mode, trigger mode and polarity, interrupt level and priority,
 * assign handler for specific IRQn.
 * \param [in]  IRQn        NMI interrupt handler address
 * \param [in]  shv         \ref ECLIC_NON_VECTOR_INTERRUPT means non-vector mode, and \ref ECLIC_VECTOR_INTERRUPT is vector mode
 * \param [in]  trig_mode   see \ref ECLIC_TRIGGER_Type
 * \param [in]  lvl         interupt level
 * \param [in]  priority    interrupt priority
 * \param [in]  handler     interrupt handler, if NULL, handler will not be installed
 * \return       -1 means invalid input parameter. 0 means successful.
 * \remarks
 * - This function use to configure specific eclic interrupt and register its interrupt handler and enable its interrupt.
 * - If the vector table is placed in read-only section(FLASHXIP mode), handler could not be installed
 */
int32_t ECLIC_Register_IRQ(IRQn_Type IRQn, uint8_t shv, ECLIC_TRIGGER_Type trig_mode, uint8_t lvl, uint8_t priority, void* handler)
{
    if ((IRQn > SOC_INT_MAX) || (shv > ECLIC_VECTOR_INTERRUPT) \
        || (trig_mode > ECLIC_NEGTIVE_EDGE_TRIGGER)) {
        return -1;
    }

    /* set interrupt vector mode */
    ECLIC_SetShvIRQ(IRQn, shv);
    /* set interrupt trigger mode and polarity */
    ECLIC_SetTrigIRQ(IRQn, trig_mode);
    /* set interrupt level */
    ECLIC_SetLevelIRQ(IRQn, lvl);
    /* set interrupt priority */
    ECLIC_SetPriorityIRQ(IRQn, priority);
```

(continues on next page)

(continued from previous page)

```c
    if (handler != NULL) {
        /* set interrupt handler entry to vector table */
        ECLIC_SetVector(IRQn, (rv_csr_t)handler);
    }
    /* enable interrupt */
    ECLIC_EnableIRQ(IRQn);
    return 0;
}

#if defined(__TEE_PRESENT) && (__TEE_PRESENT == 1)
/**
 * \brief  Initialize a specific IRQ and register the handler for supervisor mode
 * \details
 * This function set vector mode, trigger mode and polarity, interrupt level and priority,
 * assign handler for specific IRQn.
 * \param [in]  IRQn        NMI interrupt handler address
 * \param [in]  shv         \ref ECLIC_NON_VECTOR_INTERRUPT means non-vector mode, and \ref ECLIC_VECTOR_INTERRUPT is vector mode
 * \param [in]  trig_mode   see \ref ECLIC_TRIGGER_Type
 * \param [in]  lvl         interupt level
 * \param [in]  priority    interrupt priority
 * \param [in]  handler     interrupt handler, if NULL, handler will not be installed
 * \return       -1 means invalid input parameter. 0 means successful.
 * \remarks
 * - This function use to configure specific eclic S-mode interrupt and register its interrupt handler and enable its interrupt.
 * - If the vector table is placed in read-only section (FLASHXIP mode), handler could not be installed.
 */
int32_t ECLIC_Register_IRQ_S(IRQn_Type IRQn, uint8_t shv, ECLIC_TRIGGER_Type trig_mode, uint8_t lvl, uint8_t priority, void* handler)
{
    if ((IRQn > SOC_INT_MAX) || (shv > ECLIC_VECTOR_INTERRUPT) \
        || (trig_mode > ECLIC_NEGTIVE_EDGE_TRIGGER)) {
        return -1;
    }

    /* set interrupt vector mode */
    ECLIC_SetShvIRQ_S(IRQn, shv);
    /* set interrupt trigger mode and polarity */
    ECLIC_SetTrigIRQ_S(IRQn, trig_mode);
    /* set interrupt level */
    ECLIC_SetLevelIRQ_S(IRQn, lvl);
    /* set interrupt priority */
    ECLIC_SetPriorityIRQ_S(IRQn, priority);
    if (handler != NULL) {
        /* set interrupt handler entry to vector table */
        ECLIC_SetVector_S(IRQn, (rv_csr_t)handler);
    }
    /* enable interrupt */
    ECLIC_EnableIRQ_S(IRQn);
```

(continues on next page)

(continued from previous page)

```
    return 0;
}
#endif

#define FALLBACK_DEFAULT_ECLIC_BASE             0x0C000000UL
#define FALLBACK_DEFAULT_SYSTIMER_BASE          0x02000000UL

/** Nuclei RISC-V CPU IRegion Information Variable used to store probed info */
volatile IRegion_Info_Type SystemIRegionInfo;
/**
 * \brief Get Nuclei Internal Region Information
 * \details
 * This function is used to get nuclei cpu internal region
 * information, such as iregion base, eclic base, smp base,
 * timer base and idu base, and fallback to old evalsoc
 * timer and eclic base if no iregion feature found
 */
static void _get_iregion_info(IRegion_Info_Type *iregion)
{
    unsigned long mcfg_info;
    if (iregion == NULL) {
        return;
    }
    mcfg_info = __RV_CSR_READ(CSR_MCFG_INFO);
    if (mcfg_info & MCFG_INFO_IREGION_EXIST) { // IRegion Info present
        iregion->iregion_base = (__RV_CSR_READ(CSR_MIRGB_INFO) >> 10) << 10;
        iregion->eclic_base = iregion->iregion_base + IREGION_ECLIC_OFS;
        iregion->systimer_base = iregion->iregion_base + IREGION_TIMER_OFS;
        iregion->smp_base = iregion->iregion_base + IREGION_SMP_OFS;
        iregion->idu_base = iregion->iregion_base + IREGION_IDU_OFS;
    } else {
        iregion->eclic_base = FALLBACK_DEFAULT_ECLIC_BASE;
        iregion->systimer_base = FALLBACK_DEFAULT_SYSTIMER_BASE;
    }
}

#define CLINT_MSIP(base, hartid)    (*(volatile uint32_t *)((uintptr_t)((base) +
↪((hartid) * 4))))
#define SMP_CTRLREG(base, ofs)      (*(volatile uint32_t *)((uintptr_t)((base) + (ofs))))

void __sync_harts(void) __attribute__((section(".text.init")));
/**
 * \brief Synchronize all harts
 * \details
 * This function is used to synchronize all the harts,
 * especially to wait the boot hart finish initialization of
 * data section, bss section and c runtines initialization
 * This function must be placed in .text.init section, since
 * section initialization is not ready, global variable
 * and static variable should be avoid to use in this function,
 * and avoid to call other functions
 */
```

(continues on next page)

(continued from previous page)

```c
void __sync_harts(void)
{
// Only do synchronize when SMP_CPU_CNT is defined and number > 0
#if defined(SMP_CPU_CNT) && (SMP_CPU_CNT > 1)
    unsigned long hartid = __get_hart_id();
    unsigned long tmr_hartid = __get_hart_index();
    unsigned long clint_base, irgb_base, smp_base;
    unsigned long mcfg_info;

    mcfg_info = __RV_CSR_READ(CSR_MCFG_INFO);
    if (mcfg_info & MCFG_INFO_IREGION_EXIST) { // IRegion Info present
        // clint base = system timer base + 0x1000
        irgb_base = (__RV_CSR_READ(CSR_MIRGB_INFO) >> 10) << 10;
        clint_base = irgb_base + IREGION_TIMER_OFS + 0x1000;
        smp_base = irgb_base + IREGION_SMP_OFS;
    } else {
        clint_base = FALLBACK_DEFAULT_SYSTIMER_BASE + 0x1000;
        smp_base = (__RV_CSR_READ(CSR_MSMPCFG_INFO) >> 4) << 4;
    }
    // Enable SMP and L2, disable cluster local memory
    SMP_CTRLREG(smp_base, 0xc) = 0xFFFFFFFF;
    SMP_CTRLREG(smp_base, 0x10) = 0x1;
    SMP_CTRLREG(smp_base, 0xd8) = 0x0;
    __SMP_RWMB();

    // pre-condition: interrupt must be disabled, this is done before calling this function
    // BOOT_HARTID is defined <Device.h>
    if (hartid == BOOT_HARTID) { // boot hart
        // clear msip pending
        for (int i = 0; i < SMP_CPU_CNT; i ++) {
            CLINT_MSIP(clint_base, i) = 0;
        }
        __SMP_RWMB();
    } else {
        // Set machine software interrupt pending to 1
        CLINT_MSIP(clint_base, tmr_hartid) = 1;
        __SMP_RWMB();
        // wait for pending bit cleared by boot hart
        while (CLINT_MSIP(clint_base, tmr_hartid) == 1);
    }
#endif
}

/**
 * \brief do the init for trap(interrupt and exception) entry for supervisor mode
 * \details
 * This function provide initialization of CSR_STVT CSR_STVT2 and CSR_STVEC.
 */
static void Trap_Init(void)
{
#if defined(__TEE_PRESENT) && (__TEE_PRESENT == 1)
```

(continues on next page)

(continued from previous page)

```
    /*
     * Intialize ECLIC supervisor mode vector interrupt
     * base address stvt to vector_table_s
     */
    __RV_CSR_WRITE(CSR_STVT, (unsigned long)&vector_table_s);
    /*
     * Set ECLIC supervisor mode non-vector entry to be controlled
     * by stvt2 CSR register.
     * Intialize supervisor mode ECLIC non-vector interrupt
     * base address stvt2 to irq_entry_s.
    */
    __RV_CSR_WRITE(CSR_STVT2, (unsigned long)&irq_entry_s);
    __RV_CSR_SET(CSR_STVT2, 0x01);
    /*
     * Set supervisor exception entry stvec to exc_entry_s */
    __RV_CSR_WRITE(CSR_STVEC, (unsigned long)&exc_entry_s);
#endif
}

/**
 * \brief early init function before main
 * \details
 * This function is executed right before main function.
 * For RISC-V gnu toolchain, _init function might not be called
 * by __libc_init_array function, so we defined a new function
 * to do initialization.
 */
void _premain_init(void)
{
    // TODO to make it possible for configurable boot hartid
    unsigned long hartid = __get_hart_id();

    // BOOT_HARTID is defined <Device.h>
    if (hartid == BOOT_HARTID) { // only done in boot hart
        // IREGION INFO MUST BE SET BEFORE ANY PREMAIN INIT STEPS
        _get_iregion_info((IRegion_Info_Type *)(&SystemIRegionInfo));
    }
    /* TODO: Add your own initialization code here, called before main */
    // This code located in RUNMODE_CONTROL ifdef endif block just for internal usage
    // No need to use in your code
#ifdef RUNMODE_CONTROL
#if defined(RUNMODE_ILM_EN) && RUNMODE_ILM_EN == 0
    // Only disable ilm when it is present
    if (__RV_CSR_READ(CSR_MCFG_INFO) & MCFG_INFO_ILM) {
        __RV_CSR_CLEAR(CSR_MILM_CTL, MILM_CTL_ILM_EN);
    }
#endif
#if defined(RUNMODE_DLM_EN) && RUNMODE_DLM_EN == 0
    // Only disable dlm when it is present
    if (__RV_CSR_READ(CSR_MCFG_INFO) & MCFG_INFO_DLM) {
        __RV_CSR_CLEAR(CSR_MDLM_CTL, MDLM_CTL_DLM_EN);
    }
```

(continues on next page)

(continued from previous page)

```c
#endif
#endif

    /* __ICACHE_PRESENT and __DCACHE_PRESENT are defined in demosoc.h */
    // For our internal cpu testing, they want to set demosoc __ICACHE_PRESENT/__DCACHE_PRESENT to be 1
    // __CCM_PRESENT is still default to 0 in demosoc.h, since it is used in core_feature_eclic.h to register interrupt, if set to 1, it might cause exception
    // but in the cpu, icache or dcache might not exist due to cpu configuration, so here
    // we need to check whether icache/dcache really exist, if yes, then turn on it
#if defined(__ICACHE_PRESENT) && (__ICACHE_PRESENT == 1)
    if (ICachePresent()) { // Check whether icache real present or not
        EnableICache();
    }
#endif
#if defined(__DCACHE_PRESENT) && (__DCACHE_PRESENT == 1)
    if (DCachePresent()) { // Check whether dcache real present or not
        EnableDCache();
    }
#endif

    /* Do fence and fence.i to make sure previous ilm/dlm/icache/dcache control done */
    __RWMB();
    __FENCE_I();

    if (hartid == BOOT_HARTID) { // only required for boot hartid
        // TODO implement get_cpu_freq function to get real cpu clock freq in HZ or directly give the real cpu HZ
        SystemCoreClock = get_cpu_freq();
        uart_init(SOC_DEBUG_UART, 115200);
        /* Display banner after UART initialized */
        SystemBannerPrint();
        /* Initialize exception default handlers */
        Exception_Init();
        /* ECLIC initialization, mainly MTH and NLBIT */
        ECLIC_Init();
        Trap_Init();
        // TODO: internal usage for Nuclei
#ifdef RUNMODE_CONTROL
        printf("Current RUNMODE=%s, ilm:%d, dlm %d, icache %d, dcache %d, ccm %d\n", \
            RUNMODE_STRING, RUNMODE_ILM_EN, RUNMODE_DLM_EN, \
            RUNMODE_IC_EN, RUNMODE_DC_EN, RUNMODE_CCM_EN);
        printf("CSR: MILM_CTL 0x%x, MDLM_CTL 0x%x, MCACHE_CTL 0x%x\n", \
            __RV_CSR_READ(CSR_MILM_CTL), __RV_CSR_READ(CSR_MDLM_CTL), \
            __RV_CSR_READ(CSR_MCACHE_CTL));
#endif
    }
}

/**
 * \brief finish function after main
 * \param [in]  status     status code return from main
```

(continues on next page)

(continued from previous page)

```
 * \details
 * This function is executed right after main function.
 * For RISC-V gnu toolchain, _fini function might not be called
 * by __libc_fini_array function, so we defined a new function
 * to do initialization
 */
void _postmain_fini(int status)
{
    /* TODO: Add your own finishing code here, called after main */
    extern void simulation_exit(int status);
    simulation_exit(status);
}

/**
 * \brief _init function called in __libc_init_array()
 * \details
 * This `__libc_init_array()` function is called during startup code,
 * user need to implement this function, otherwise when link it will
 * error init.c:(.text.__libc_init_array+0x26): undefined reference to `_init'
 * \note
 * Please use \ref _premain_init function now
 */
void _init(void)
{
    /* Don't put any code here, please use _premain_init now */
}

/**
 * \brief _fini function called in __libc_fini_array()
 * \details
 * This `__libc_fini_array()` function is called when exit main.
 * user need to implement this function, otherwise when link it will
 * error fini.c:(.text.__libc_fini_array+0x28): undefined reference to `_fini'
 * \note
 * Please use \ref _postmain_fini function now
 */
void _fini(void)
{
    /* Don't put any code here, please use _postmain_fini now */
}

/** @} */ /* End of Doxygen Group NMSIS_Core_SystemConfig */
```

system_Device.h Template File

Here we provided `system_Device.h` template file as below:

```c
/*
 * Copyright (c) 2009-2018 Arm Limited. All rights reserved.
 * Copyright (c) 2019 Nuclei Limited. All rights reserved.
 *
 * SPDX-License-Identifier: Apache-2.0
 *
 * Licensed under the Apache License, Version 2.0 (the License); you may
 * not use this file except in compliance with the License.
 * You may obtain a copy of the License at
 *
 * www.apache.org/licenses/LICENSE-2.0
 *
 * Unless required by applicable law or agreed to in writing, software
 * distributed under the License is distributed on an AS IS BASIS, WITHOUT
 * WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 * See the License for the specific language governing permissions and
 * limitations under the License.
 */
/*******************************************************************************
 * @file     system_<Device>.h
 * @brief    NMSIS Nuclei N/NX Device Peripheral Access Layer Header File for
 *           Device <Device>
 * @version  V2.0.0
 * @date     30. Dec 2022
 ******************************************************************************/

#ifndef __SYSTEM_<Device>_H__   /* TODO: replace '<Device>' with your device name */
#define __SYSTEM_<Device>_H__

#ifdef __cplusplus
extern "C" {
#endif

#include <stdint.h>

extern volatile uint32_t SystemCoreClock;     /*!< System Clock Frequency (Core Clock) */

typedef struct EXC_Frame {
    unsigned long ra;                /* ra: x1, return address for jump */
    unsigned long tp;                /* tp: x4, thread pointer */
    unsigned long t0;                /* t0: x5, temporary register 0 */
    unsigned long t1;                /* t1: x6, temporary register 1 */
    unsigned long t2;                /* t2: x7, temporary register 2 */
    unsigned long a0;                /* a0: x10, return value or function argument 0 */
    unsigned long a1;                /* a1: x11, return value or function argument 1 */
    unsigned long a2;                /* a2: x12, function argument 2 */
    unsigned long a3;                /* a3: x13, function argument 3 */
    unsigned long a4;                /* a4: x14, function argument 4 */
    unsigned long a5;                /* a5: x15, function argument 5 */
```

(continues on next page)

(continued from previous page)

```
    unsigned long cause;             /* cause: machine/supervisor mode cause csr␣
↪register */
    unsigned long epc;               /* epc: machine/ supervisor mode exception program␣
↪counter csr register */
    unsigned long msubm;             /* msubm: machine sub-mode csr register, nuclei␣
↪customized, exclusive to machine mode */
#ifndef __riscv_32e
    unsigned long a6;                /* a6: x16, function argument 6 */
    unsigned long a7;                /* a7: x17, function argument 7 */
    unsigned long t3;                /* t3: x28, temporary register 3 */
    unsigned long t4;                /* t4: x29, temporary register 4 */
    unsigned long t5;                /* t5: x30, temporary register 5 */
    unsigned long t6;                /* t6: x31, temporary register 6 */
#endif
} EXC_Frame_Type;

/**
 * \brief Setup the microcontroller system.
 * \details
 * Initialize the System and update the SystemCoreClock variable.
 */
extern void SystemInit(void);

/**
 * \brief  Update SystemCoreClock variable.
 * \details
 * Updates the SystemCoreClock with current core Clock retrieved from cpu registers.
 */
extern void SystemCoreClockUpdate(void);

/**
 * \brief Dump Exception Frame
 */
void Exception_DumpFrame(unsigned long sp, uint8_t mode);

/**
 * \brief Register an exception handler for exception code EXCn
 */
extern void Exception_Register_EXC(uint32_t EXCn, unsigned long exc_handler);

/**
 * \brief Get current exception handler for exception code EXCn
 */
extern unsigned long Exception_Get_EXC(uint32_t EXCn);

/**
 * \brief Initialize eclic config
 */
extern void ECLIC_Init(void);

/**
 * \brief  Initialize a specific IRQ and register the handler
```

(continues on next page)

(continued from previous page)

```c
 * \details
 * This function set vector mode, trigger mode and polarity, interrupt level and␣
↪priority,
 * assign handler for specific IRQn.
 */
extern int32_t ECLIC_Register_IRQ(IRQn_Type IRQn, uint8_t shv, ECLIC_TRIGGER_Type trig_
↪mode, uint8_t lvl, uint8_t priority, void* handler);

#if defined(__TEE_PRESENT) && (__TEE_PRESENT == 1)
/**
 * \brief Register an exception handler for exception code EXCn of supervisor mode
 */
extern void Exception_Register_EXC_S(uint32_t EXCn, unsigned long exc_handler);

/**
 * \brief Get current exception handler for exception code EXCn of supervisor mode
 */
extern unsigned long Exception_Get_EXC_S(uint32_t EXCn);

/**
 * \brief  Initialize a specific IRQ and register the handler of supervisor mode
 * \details
 * This function set vector mode, trigger mode and polarity, interrupt level and␣
↪priority,
 * assign handler for specific IRQn.
 */
extern int32_t ECLIC_Register_IRQ_S(IRQn_Type IRQn, uint8_t shv, ECLIC_TRIGGER_Type trig_
↪mode, uint8_t lvl, uint8_t priority, void* handler);

#endif

#ifdef __cplusplus
}
#endif

#endif /* __SYSTEM_<Device>_H__ */
```

Device Header File <Device.h>

The *Device Header File <Device.h>* (page 63) contains the following sections that are device specific:

- *Interrupt Number Definition* (page 64) provides interrupt numbers (IRQn) for all exceptions and interrupts of the device.
- *Configuration of the Processor and Core Peripherals* (page 65) reflect the features of the device.
- *Device Peripheral Access Layer* (page 67) provides definitions for the *Peripheral Access* (page 540) to all device peripherals. It contains all data structures and the address mapping for device-specific peripherals.
- **Access Functions for Peripherals (optional)** provide additional helper functions for peripherals that are useful for programming of these peripherals. Access Functions may be provided as inline functions or can be extern references to a device-specific library provided by the silicon vendor.

NMSIS Core API (page 76) describes the standard features and functions of the *Device Header File <Device.h>* (page 63) in detail.

Interrupt Number Definition

***Device Header File <Device.h>* (page 63) contains the enumeration IRQn_Type that defines all exceptions and interrupts of the d**

- Negative IRQn values represent processor core exceptions (internal interrupts).
- Positive IRQn values represent device-specific exceptions (external interrupts). The first device-specific interrupt has the IRQn value 0. The IRQn values needs extension to reflect the device-specific interrupt vector table in the *Startup File startup_<Device>.S* (page 14).

The following example shows the extension of the interrupt vector table for the GD32VF103 device family.

```
typedef enum IRQn {
    /******  N200 Processor Exceptions Numbers *******************************************/
    Reserved0_IRQn              =   0,     /*!<  Internal reserved                    */
    Reserved1_IRQn              =   1,     /*!<  Internal reserved                    */
    Reserved2_IRQn              =   2,     /*!<  Internal reserved                    */
    SysTimerSW_IRQn             =   3,     /*!<  System Timer SW interrupt            */
    Reserved3_IRQn              =   4,     /*!<  Internal reserved                    */
    Reserved4_IRQn              =   5,     /*!<  Internal reserved                    */
    Reserved5_IRQn              =   6,     /*!<  Internal reserved                    */
    SysTimer_IRQn               =   7,     /*!<  System Timer Interrupt               */
    Reserved6_IRQn              =   8,     /*!<  Internal reserved                    */
    Reserved7_IRQn              =   9,     /*!<  Internal reserved                    */
    Reserved8_IRQn              =  10,     /*!<  Internal reserved                    */
    Reserved9_IRQn              =  11,     /*!<  Internal reserved                    */
    Reserved10_IRQn             =  12,     /*!<  Internal reserved                    */
    Reserved11_IRQn             =  13,     /*!<  Internal reserved                    */
    Reserved12_IRQn             =  14,     /*!<  Internal reserved                    */
    Reserved13_IRQn             =  15,     /*!<  Internal reserved                    */
    Reserved14_IRQn             =  16,     /*!<  Internal reserved                    */
    HardFault_IRQn              =  17,     /*!<  Hard Fault, storage access error     */
```

(continues on next page)

(continued from previous page)

```
    Reserved15_IRQn              =  18,     /*!<  Internal reserved                  */

    /******  GD32VF103 Specific Interrupt Numbers *******************************************/
    WWDGT_IRQn                   =  19,     /*!< window watchDog timer interrupt     */
    LVD_IRQn                     =  20,     /*!< LVD through EXTI line detect interrupt */
    TAMPER_IRQn                  =  21,     /*!< tamper through EXTI line detect     */
                         :         :
                         :         :
    CAN1_EWMC_IRQn               =  85,     /*!< CAN1 EWMC interrupt                 */
    USBFS_IRQn                   =  86,     /*!< USBFS global interrupt              */
    SOC_INT_MAX,                            /*!< Number of total Interrupts          */
} IRQn_Type;
```

Configuration of the Processor and Core Peripherals

The *Device Header File <Device.h>* (page 63) configures the Nuclei N/NX Class Processors and the core peripherals with `#define` that are set prior to including the file *nmsis_core.h*.

For recently released Nuclei 200/300/600/900 RISC-V CPU, the cpu private peripherals are also called internal regions(IREGION) and the address spaces are continuous with fixed size, cpu will be configured with only the base address of IREGION, such as ECLIC, TIMER, SMP, Cluster Cache, CIDU, PLIC unit, for more details, please check Nuclei ISA Spec and related CPU databook.

The following tables list the `#define` along with the possible values for N200, N300, N600, NX600. If these `#define` are missing default values are used.

nmsis_core.h

Note:

- `__NUCLEI_N_REV` and `__NUCLEI_NX_REV` are deprecated since 1.2.0, please use `__NUCLEI_CPU_REV` and `__NUCLEI_CPU_SERIES` now.
- `__HARTID_OFFSET` and `__SYSTIMER_HARTID` is added since 1.2.0

Table 5: Macros used in nmsis_core.h

#define	Value Range	Default	Description
__NUCLEI_N_REV OR __NUCLEI_NX_REV	0x0100 | 0x0104	0x0100	• For Nuclei N class device, define __NUCLEI_N_REV, for NX class device, define __NUCLEI_NX_REV. • Core revision number ([15:8] revision number, [7:0] patch number), 0x0100 -> 1.0, 0x0104 -> 1.4
__NUCLEI_CPU_REV	•	•	Define Nuclei CPU Revision Number, such as 0x030A01 means v3.10.1.
__NUCLEI_CPU_SERIES	•	•	Define Nuclei CPU Series, such as 0x0200, 0x0300, 0x0600, 0x0900 for 200/300/600/900 series.
__HARTID_OFFSET	•	•	Define the offset of the first cpu hart's hartid vs hart index, eg, cpu first hartid is 3, set it to 3.
__SYSTIMER_PRESENT	0 .. 1	1	Define whether Priviate System Timer is present or not. This SysTimer is a Memory Mapped Unit.
__SYSTIMER_BASEADDR	•	0x18030000	Base address of the System Timer Unit.
__SYSTIMER_HARTID	•	•	Optional, if you cpu system only has one hart, and the timer hartid is known, you can set it to known value
__ECLIC_PRESENT	0 .. 1	1	Define whether Enhanced Core Local Interrupt Controller (ECLIC) Unit is present or not
__ECLIC_BASEADDR	•	0x18020000	Base address of the ECLIC unit.
__CIDU_PRESENT	0 .. 1	0	Define whether Cluster Interrupt Distribution Unit (CIDU) is present or not
__CIDU_BASEADDR	•	0x18050000	Base address of the CIDU unit.
__ECLIC_INTCTLBITS	1 .. 8	1	Define the number of hardware bits are actually implemented in the clicintctl registers.
__ECLIC_INTNUM	1 .. 1024	1	Define the total interrupt number(including the internal core interrupts) of ECLIC Unit
__PMP_PRESENT	0 .. 1	0	Define whether Physical Memory Protection (PMP) Unit is present or not.
__PMP_ENTRY_NUM	8 or 16	8	Define the numbers of PMP entries.
__SPMP_PRESENT	0 .. 1	0	Define whether SMode Physical Memory Protection (sPMP) Unit is present or not.
__SPMP_ENTRY_NUM	8 or 16	8	Define the numbers of sPMP entries.
__FPU_PRESENT	0 .. 2	0	Define whether Floating Point Unit (FPU) is present or not. • 0: Not present • 1: Single precision FPU present • 2: Double precision FPU present
__BITMANIP_PRESENT	0 .. 1	0	Define whether Bitmainp Unit is present or not.
__DSP_PRESENT	0 .. 1	0	Define whether Digital Signal Processing Unit (DSP) is present or not.
__VECTOR_PRESENT	0 .. 1	0	Define whether Vector Unit is present or not.
__ICACHE_PRESENT	0 .. 1	0	Define whether I-Cache Unit is present or not.
__DCACHE_PRESENT	0 .. 1	0	Define whether D-Cache Unit is present or not.
__CCM_PRESENT	0 .. 1	0	Define whether Nuclei Cache Control and Maintainence Unit is present or not.
__INC_INTRINSIC_API	0 .. 1	0	Define whether toolchain provided intrinsic api

NMSIS Version and Processor Information

The following shows the defines in the *nmsis_core.h* file that may be used in the *NMSIS-Core Device Templates* (page 12) to verify a minimum version or ensure that the right Nuclei N/NX/U/UX class is used.

Device Peripheral Access Layer

The *Device Header File <Device.h>* (page 63) contains for each peripheral:

- Register Layout Typedef
- Base Address
- Access Definitions

The section *Peripheral Access* (page 540) shows examples for peripheral definitions.

Device.h Template File

Here we provided `Device.h` template file as below:

```c
/*
 * Copyright (c) 2009-2019 Arm Limited. All rights reserved.
 * Copyright (c) 2019 Nuclei Limited. All rights reserved.
 *
 * SPDX-License-Identifier: Apache-2.0
 *
 * Licensed under the Apache License, Version 2.0 (the License); you may
 * not use this file except in compliance with the License.
 * You may obtain a copy of the License at
 *
 * www.apache.org/licenses/LICENSE-2.0
 *
 * Unless required by applicable law or agreed to in writing, software
 * distributed under the License is distributed on an AS IS BASIS, WITHOUT
 * WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
 * See the License for the specific language governing permissions and
 * limitations under the License.
 */
/******************************************************************************
 * @file     <Device>.h
 * @brief    NMSIS Nuclei N/NX Core Peripheral Access Layer Header File for
 *           Device <Device>
 * @version  V2.1.0
 * @date     19. Dec 2023
 ******************************************************************************/

#ifndef __<Device>_H__     /* TODO: replace '<Device>' with your device name */
#define __<Device>_H__

#ifdef __cplusplus
extern "C" {
#endif
```

(continues on next page)

(continued from previous page)

```c

/* TODO: replace '<Vendor>' with vendor name; add your doxygen comment   */
/** @addtogroup <Vendor>
  * @{
  */


/* TODO: replace '<Device>' with device name; add your doxygen comment   */
/** @addtogroup <Device>
  * @{
  */


/** @addtogroup Configuration_of_NMSIS
  * @{
  */

/** \brief SoC Download mode definition */
/* TODO: device vendor can extend more download modes */
typedef enum {
    DOWNLOAD_MODE_FLASHXIP = 0,         /*!< Flashxip download mode */
    DOWNLOAD_MODE_FLASH = 1,            /*!< Flash download mode */
    DOWNLOAD_MODE_ILM = 2,              /*!< ilm download mode */
    DOWNLOAD_MODE_DDR = 3,              /*!< ddr download mode */
    DOWNLOAD_MODE_SRAM = 4,             /*!< sram download mode */
    DOWNLOAD_MODE_MAX,
} DownloadMode_Type;

/** \brief CPU Internal Region Information */
typedef struct IRegion_Info {
    unsigned long iregion_base;         /*!< Internal region base address */
    unsigned long eclic_base;           /*!< eclic base address */
    unsigned long systimer_base;        /*!< system timer base address */
    unsigned long smp_base;             /*!< smp base address */
    unsigned long idu_base;             /*!< idu base address */
} IRegion_Info_Type;

/* 
↪=========================================================================================================
↪*/
/* ================                                Interrupt Number Definition                                
↪                    ================ */
/* 
↪=========================================================================================================
↪*/

typedef enum IRQn {
/* ========================================  Nuclei N/NX Specific Interrupt Numbers 
↪======================================== */

/* TODO: use this N/NX interrupt numbers if your device is a Nuclei N/NX device */
    Reserved0_IRQn            =   0,              /*!<  Internal reserved */
```

(continues on next page)

(continued from previous page)

```
    Reserved1_IRQn              =   1,              /*!<  Internal reserved */
    Reserved2_IRQn              =   2,              /*!<  Internal reserved */
    SysTimerSW_IRQn             =   3,              /*!<  System Timer SW interrupt for both M/S mode in ECLIC */
    Reserved3_IRQn              =   4,              /*!<  Internal reserved */
    Reserved4_IRQn              =   5,              /*!<  Internal reserved */
    Reserved5_IRQn              =   6,              /*!<  Internal reserved */
    SysTimer_IRQn               =   7,              /*!<  System Timer Interrupt for both M/S mode in ECLIC */
    Reserved6_IRQn              =   8,              /*!<  Internal reserved */
    Reserved7_IRQn              =   9,              /*!<  Internal reserved */
    Reserved8_IRQn              =  10,              /*!<  Internal reserved */
    Reserved9_IRQn              =  11,              /*!<  Internal reserved */
    Reserved10_IRQn             =  12,              /*!<  Internal reserved */
    Reserved11_IRQn             =  13,              /*!<  Internal reserved */
    Reserved12_IRQn             =  14,              /*!<  Internal reserved */
    Reserved13_IRQn             =  15,              /*!<  Internal reserved */
    InterCore_IRQn              =  16,              /*!<  CIDU Inter Core Interrupt */
    Reserved15_IRQn             =  17,              /*!<  Internal reserved */
    Reserved16_IRQn             =  18,              /*!<  Internal reserved */

/* ===========================================  <Device> Specific Interrupt Numbers  ========================================= */
/* TODO: add here your device specific external interrupt numbers. 19~1023 is reserved number for user. Maxmum interrupt supported
         could get from clicinfo.NUM_INTERRUPT. According the interrupt handlers defined in startup_Device.s
         eg.: Interrupt for Timer#1       eclic_tim0_handler   ->   TIM0_IRQn */
    <DeviceInterrupt>_IRQn     = 19,                /*!< Device Interrupt */

    SOC_INT_MAX,                                    /* Max SoC interrupt Number */
} IRQn_Type;

/* ========================================================================================================================================== */
/* ================                                  Exception Code Definition                                        ================ */
/* ========================================================================================================================================== */

typedef enum EXCn {
/* =======================================  Nuclei N/NX Specific Exception Code  ======================================== */
    InsUnalign_EXCn          =   0,              /*!<  Instruction address misaligned */
    InsAccFault_EXCn         =   1,              /*!<  Instruction access fault */
    IlleIns_EXCn             =   2,              /*!<  Illegal instruction */
    Break_EXCn               =   3,              /*!<  Beakpoint */
    LdAddrUnalign_EXCn       =   4,              /*!<  Load address misaligned */
    LdFault_EXCn             =   5,              /*!<  Load access fault */
    StAddrUnalign_EXCn       =   6,              /*!<  Store or AMO address misaligned */
```

(continues on next page)

(continued from previous page)

```
    StAccessFault_EXCn       =   7,            /*!<  Store or AMO access fault */
    UmodeEcall_EXCn          =   8,            /*!<  Environment call from User mode */
    SmodeEcall_EXCn          =   9,            /*!<  Environment call from S-mode */
    MmodeEcall_EXCn          =  11,            /*!<  Environment call from Machine mode */
    InsPageFault_EXCn        =  12,            /*!<  Instruction page fault */
    LdPageFault_EXCn         =  13,            /*!<  Load page fault */
    StPageFault_EXCn         =  15,            /*!<  Store or AMO page fault */
    StackOverflow_EXCn       =  24,            /*!<  Stack overflow fault */
    StackUnderflow_EXCn      =  25,            /*!<  Stack underflow fault */
    NMI_EXCn                 =  0xfff,         /*!<  NMI interrupt */
} EXCn_Type;

/* ====================================================================================================
*/
/* ================                              Processor and Core Peripheral Section                  ================ */
/* ====================================================================================================
*/
extern volatile IRegion_Info_Type SystemIRegionInfo;
/* ===========================  Configuration of the Nuclei N/NX Processor and Core Peripherals  =========================== */
/* TODO: set the defines according your Device */
/* TODO: define the correct core revision
 *       __NUCLEI_N_REV if your device is a Nuclei-N Class device, which is 32bit CPU
 *       __NUCLEI_NX_REV if your device is a Nuclei-NX Class device, which is 64bit CPU
 */
#define __NUCLEI_N#_REV          0x0100               /*!< Core Revision rXpY, version X.Y, change N# to N for Nuclei N class cores, change N# to NX for Nuclei NX cores */
#define __NUCLEI_CPU_REV         0x030600             /*!< Nuclei CPU Core Revision, version X.Y.Z, this is for the CPU Core Version, you get from Nuclei, eg. N300 v3.10.1, it should be 0x030A01 */
#define __NUCLEI_CPU_SERIES      0x0300               /*!< Nuclei CPU Series, such as 200/300/600/900, eg. 900 will be 0x0900 */
/* TODO: define the correct core features for the <Device> */
/**
 * If your hart index is different to your hartid, you must define this __HARTID_OFFSET macro.
 * For example, if your cpu has 4 harts, and hartid start from 3, so the __HARTID_OFFSET should set to 3.
 * Which means hartid 3-6 means hart index 0-3, this is useful for the timer software interrupt and timer interrupt trigger register location
 */
#ifndef __HARTID_OFFSET
#define __HARTID_OFFSET          0
#endif
#define __ECLIC_PRESENT          1                    /*!< Set to 1 if ECLIC is present */
#define __ECLIC_BASEADDR         SystemIRegionInfo.eclic_base          /*!< Set to ECLIC baseaddr of your device */
```

(continues on next page)

(continued from previous page)

```
#define __ECLIC_INTCTLBITS        8                    /*!< Set to 1 - 8, the number of␣
↪hardware bits are actually implemented in the clicintctl registers. */
#define __ECLIC_INTNUM            64                   /*!< Set to 1 - 1024, total␣
↪interrupt number of ECLIC Unit */
#define __SYSTIMER_PRESENT        1                    /*!< Set to 1 if System Timer is␣
↪present */
#define __SYSTIMER_BASEADDR       SystemIRegionInfo.systimer_base          /*!< Set to␣
↪SysTimer baseaddr of your device */
//#define __SYSTIMER_HARTID         0                    /*!< Set this timer hartid if␣
↪you have only 1 hart in your cpu, and you know the timer hartid, just set it */
#define __CIDU_PRESENT            0                    /*!< Set to 1 if CIDU is present␣
↪*/
#define __CIDU_BASEADDR           SystemIRegionInfo.idu_base              /*!< Set to␣
↪cidu baseaddr of your device */
#define __FPU_PRESENT             1                    /*!< Set to 0, 1, or 2, 0 not␣
↪present, 1 single floating point unit present, 2 double floating point unit present */
#define __BITMANIP_PRESENT        1                    /*!< Set to 1 if Bitmainpulation␣
↪extension is present */
#define __DSP_PRESENT             1                    /*!< Set to 1 if DSP is present␣
↪*/
#define __VECTOR_PRESENT          1                    /*!< Set to 1 if Vector␣
↪extension is present */
#define __PMP_PRESENT             1                    /*!< Set to 1 if PMP is present␣
↪*/
#define __PMP_ENTRY_NUM           16                   /*!< Set to 8 or 16, the number␣
↪of PMP entries */
#define __SPMP_PRESENT            1                    /*!< Set to 1 if SPMP is present␣
↪*/
#define __SPMP_ENTRY_NUM          16                   /*!< Set to 8 or 16, the number␣
↪of SPMP entries */
#define __TEE_PRESENT             0                    /*!< Set to 1 if TEE is present␣
↪*/
#define __ICACHE_PRESENT          0                    /*!< Set to 1 if I-Cache is␣
↪present */
#define __DCACHE_PRESENT          0                    /*!< Set to 1 if D-Cache is␣
↪present */
#define __CCM_PRESENT             0                    /*!< Set to 1 if Cache Control␣
↪and Mantainence Unit is present */
#define __INC_INTRINSIC_API       0                    /*!< Set to 1 if intrinsic api␣
↪header files need to be included */
#define __Vendor_SysTickConfig    0                    /*!< Set to 1 if different␣
↪SysTick Config is used */
#define __Vendor_EXCEPTION        0                    /*!< Set to 1 if vendor␣
↪exception hander is present */

/** @} */ /* End of group Configuration_of_NMSIS */


#include <nmsis_core.h>
/* TODO: include your system_<Device>.h file
         replace '<Device>' with your device name */
#include "system_<Device>.h"                   /*!< <Device> System */
```

(continues on next page)

(continued from previous page)

```


/* ========================================  Start of section using anonymous unions ========================================= */


/* ================================================================================================================================= */
/* ================                                Device Specific Peripheral Section                                ================ */
/* ================================================================================================================================= */
/* Macros for memory access operations */
#define _REG8P(p, i)                            ((volatile uint8_t *) ((uintptr_t)((p) + (i))))
#define _REG16P(p, i)                           ((volatile uint16_t *) ((uintptr_t)((p) + (i))))
#define _REG32P(p, i)                           ((volatile uint32_t *) ((uintptr_t)((p) + (i))))
#define _REG64P(p, i)                           ((volatile uint64_t *) ((uintptr_t)((p) + (i))))
#define _REG8(p, i)                             (*(_REG8P(p, i)))
#define _REG16(p, i)                            (*(_REG16P(p, i)))
#define _REG32(p, i)                            (*(_REG32P(p, i)))
#define _REG64(p, i)                            (*(_REG64P(p, i)))
#define REG8(addr)                              _REG8((addr), 0)
#define REG16(addr)                             _REG16((addr), 0)
#define REG32(addr)                             _REG32((addr), 0)
#define REG64(addr)                             _REG64((addr), 0)

/* Macros for address type convert and access operations */
#define ADDR16(addr)                            ((uint16_t)(uintptr_t)(addr))
#define ADDR32(addr)                            ((uint32_t)(uintptr_t)(addr))
#define ADDR64(addr)                            ((uint64_t)(uintptr_t)(addr))
#define ADDR8P(addr)                            ((uint8_t *)(uintptr_t)(addr))
#define ADDR16P(addr)                           ((uint16_t *)(uintptr_t)(addr))
#define ADDR32P(addr)                           ((uint32_t *)(uintptr_t)(addr))
#define ADDR64P(addr)                           ((uint64_t *)(uintptr_t)(addr))

/* Macros for Bit Operations */
#if __riscv_xlen == 32
#define BITMASK_MAX                             0xFFFFFFFFUL
#define BITOFS_MAX                              31
#else
#define BITMASK_MAX                             0xFFFFFFFFFFFFFFFFULL
#define BITOFS_MAX                              63
#endif

// BIT/BITS only support bit mask for __riscv_xlen
// For RISC-V 32 bit, it support mask 32 bit wide
```

(continues on next page)

(continued from previous page)

```
// For RISC-V 64 bit, it support mask 64 bit wide
#define BIT(ofs)                                (0x1UL << (ofs))
#define BITS(start, end)                        ((BITMASK_MAX) << (start) & (BITMASK_MAX) >> (BITOFS_MAX - (end)))
#define GET_BIT(regval, bitofs)                 (((regval) >> (bitofs)) & 0x1)
#define SET_BIT(regval, bitofs)                 ((regval) |= BIT(bitofs))
#define CLR_BIT(regval, bitofs)                 ((regval) &= (~BIT(bitofs)))
#define FLIP_BIT(regval, bitofs)                ((regval) ^= BIT(bitofs))
#define WRITE_BIT(regval, bitofs, val)          CLR_BIT(regval, bitofs); ((regval) |= ((val) << bitofs) & BIT(bitofs))
#define CHECK_BIT(regval, bitofs)               (!!((regval) & (0x1UL<<(bitofs))))
#define GET_BITS(regval, start, end)            (((regval) & BITS((start), (end))) >> (start))
#define SET_BITS(regval, start, end)            ((regval) |= BITS((start), (end)))
#define CLR_BITS(regval, start, end)            ((regval) &= (~BITS((start), (end))))
#define FLIP_BITS(regval, start, end)           ((regval) ^= BITS((start), (end)))
#define WRITE_BITS(regval, start, end, val)     CLR_BITS(regval, start, end); ((regval) |= ((val) << start) & BITS((start), (end)))
#define CHECK_BITS_ALL(regval, start, end)      (!((~(regval)) & BITS((start), (end))))
#define CHECK_BITS_ANY(regval, start, end)      ((regval) & BITS((start), (end)))

#define BITMASK_SET(regval, mask)               ((regval) |= (mask))
#define BITMASK_CLR(regval, mask)               ((regval) &= (~(mask)))
#define BITMASK_FLIP(regval, mask)              ((regval) ^= (mask))
#define BITMASK_CHECK_ALL(regval, mask)         (!((~(regval)) & (mask)))
#define BITMASK_CHECK_ANY(regval, mask)         ((regval) & (mask))

/** @addtogroup Device_Peripheral_peripherals
  * @{
  */

/* TODO: add here your device specific peripheral access structure typedefs
         following is an example for UART */

/* =========================================================================================================================== */
/* ================                                            UART                                           ================ */
/* =========================================================================================================================== */

/**
  * @brief UART (UART)
  */
typedef struct {                                /*!< (@ 0x40000000) UART Structure                                             */
  __IOM uint32_t   TXFIFO;                      /*!< (@ 0x00000000) UART TX FIFO                                               */
  __IM  uint32_t   RXFIFO;                      /*!< (@ 0x00000004) UART RX FIFO                                               */
```

(continues on next page)

(continued from previous page)

```
  __IOM uint32_t   TXCTRL;                     /*!< (@ 0x00000008) UART TX FIFO control          */
  __OM  uint32_t   RXCTRL;                     /*!< (@ 0x0000000C) UART RX FIFO control          */
  __IM  uint32_t   IE;                         /*!< (@ 0x00000010) UART Interrupt Enable flag       */
  __IM  uint32_t   IP;                         /*!< (@ 0x00000018) TART Interrupt Pending flag      */
  __IM  uint32_t   DIV;                        /*!< (@ 0x00000018) UART Baudrate Divider          */
} <DeviceAbbreviation>_UART_TypeDef;

/*@}*/ /* end of group <Device>_Peripherals */


/* =========================================  End of section using anonymous unions =========================================== */

/* ========================================================================================================================== */
/* ================                          Device Specific Peripheral Address Map                          ================ */
/* ========================================================================================================================== */


/* TODO: add here your device peripherals base addresses
         following is an example for timer */
/** @addtogroup Device_Peripheral_peripheralAddr
  * @{
  */

/* Peripheral and SRAM base address */
#define <DeviceAbbreviation>_FLASH_BASE         (0x00000000UL)                              /*!< (FLASH     ) Base Address */
#define <DeviceAbbreviation>_SRAM_BASE          (0x20000000UL)                              /*!< (SRAM      ) Base Address */
#define <DeviceAbbreviation>_PERIPH_BASE        (0x40000000UL)                              /*!< (Peripheral) Base Address */

/* Peripheral memory map */
#define <DeviceAbbreviation>UART0_BASE          (<DeviceAbbreviation>_PERIPH_BASE)          /*!< (UART 0  ) Base Address */
#define <DeviceAbbreviation>I2C_BASE            (<DeviceAbbreviation>_PERIPH_BASE + 0x0800) /*!< (I2C     ) Base Address */
#define <DeviceAbbreviation>GPIO_BASE           (<DeviceAbbreviation>_PERIPH_BASE + 0x1000) /*!< (GPIO     ) Base Address */

/** @} */ /* End of group Device_Peripheral_peripheralAddr */

```

(continues on next page)

(continued from previous page)

```

/*␣
↪===========================================================================================
↪*/
/* ================                                  Peripheral declaration            ␣
↪                       ================ */
/*␣
↪===========================================================================================
↪*/


/* TODO: add here your device peripherals pointer definitions
         following is an example for uart0 */
/** @addtogroup Device_Peripheral_declaration
  * @{
  */
#define <DeviceAbbreviation>_UART0              ((<DeviceAbbreviation>_TMR_TypeDef *)
↪<DeviceAbbreviation>UART0_BASE)


/** @} */ /* End of group <Device> */

/** @} */ /* End of group <Vendor> */

#ifdef __cplusplus
}
#endif

#endif  /* __<Device>_H__ */
```

2.4 Register Mapping

The table below associates some common register names used in NMSIS to the register names used in Nuclei ISA Spec.

Note: The below register mapping maybe out of date, please refer to Nuclei ISA Spec for an updated version.

Table 6: Register names used in NMSIS related with the register names in ISA

NMSIS Register Name	200, 300, 600, 900	Register Description
Enhanced Core Local Interrupt Controller(ECLIC)		
ECLIC->CFG	cliccfg	ECLIC Global Configuration Register
ECLIC->INFO	clicinfo	ECLIC Global Information Register
ECLIC->MTH	mth	ECLIC Global Machine Mode Threshold Register
ECLIC->CTRL[i].INTIP	clicintip[i]	ECLIC Interrupt Pending Register
ECLIC->CTRL[i].INTIE	clicintie[i]	ECLIC Interrupt Enable Register
ECLIC->CTRL[i].INTATTR	clicintattr[i]	ECLIC Interrupt Attribute Register
ECLIC->CTRL[i].INTCTRL	clicintctl[i]	ECLIC Interrupt Input Control Register
System Timer Unit(SysTimer)		
SysTimer->MTIMER	mtime_hi<<32 + mtime_lo	System Timer current value 64bits Register
SysTimer->MTIMERCMP	mtimecmp_hi<<32 + mtimecmp_lo	System Timer compare value 64bits Register
SysTimer->MSTOP	mstop	System Timer Stop Register
SysTimer->MSIP	msip	System Timer SW interrupt Register

2.5 NMSIS Core API

If you want to access doxygen generated NMSIS Core API, please click NMSIS Core Doxygen API Documentation.

2.5.1 Version Control

group `NMSIS_Core_VersionControl`

Version #define symbols for NMSIS release specific C/C++ source code.

We followed the semantic versioning 2.0.0[12] to control NMSIS version. The version format is **MAJOR.MINOR.PATCH**, increment the:

1. MAJOR version when you make incompatible API changes,
2. MINOR version when you add functionality in a backwards compatible manner, and
3. PATCH version when you make backwards compatible bug fixes.

The header file `nmsis_version.h` is included by each core header so that these definitions are available.

Example Usage for NMSIS Version Check:

```
#if defined(__NMSIS_VERSION) && (__NMSIS_VERSION >= 0x00010105)
   #warning "Yes, we have NMSIS 1.1.5 or later"
#else
   #error "We need NMSIS 1.1.5 or later!"
#endif
```

Unnamed Group

__NUCLEI_N_REV (0x0309)

Nuclei N class core revision number.

Reversion number format: [15:8] revision number, [7:0] patch number

Attention Deprecated, this define is exclusive with *__NUCLEI_NX_REV* (page 77)

__NUCLEI_NX_REV (0x0207)

Nuclei NX class core revision number.

Reversion number format: [15:8] revision number, [7:0] patch number

Attention Deprecated, this define is exclusive with *__NUCLEI_N_REV* (page 77)

__NUCLEI_CPU_REV (0x030A01)

Nuclei CPU core revision number.

Nuclei RISC-V CPU Revision Number vX.Y.Z, eg. v3.10.1

Attention This define is exclusive with *__NUCLEI_CPU_SERIES* (page 77)

__NUCLEI_CPU_SERIES (0x0200)

Nuclei CPU core series.

Nuclei RISC-V CPU Series Number, eg, 0x200, 0x300, 0x600, 0x900 for 200, 300, 600, 900 series.

Attention This define is used together with *__NUCLEI_CPU_REV* (page 77)

Defines

__NMSIS_VERSION_MAJOR (1U)

Represent the NMSIS major version.

The NMSIS major version can be used to differentiate between NMSIS major releases.

__NMSIS_VERSION_MINOR (2U)

Represent the NMSIS minor version.

The NMSIS minor version can be used to query a NMSIS release update including new features.

__NMSIS_VERSION_PATCH (0U)

Represent the NMSIS patch version.

The NMSIS patch version can be used to show bug fixes in this package.

__NMSIS_VERSION ((*__NMSIS_VERSION_MAJOR* (page 77) << 16U) | (*__NMSIS_VERSION_MINOR* (page 77) << 8) | *__NMSIS_VERSION_PATCH* (page 77))

Represent the NMSIS Version.

NMSIS Version format: **MAJOR.MINOR.PATCH**

- MAJOR: *__NMSIS_VERSION_MAJOR* (page 77), stored in `bits [31:16]` of *__NMSIS_VERSION* (page 77)

- MINOR: *__NMSIS_VERSION_MINOR* (page 77), stored in `bits [15:8]` of *__NMSIS_VERSION* (page 77)
- PATCH: *__NMSIS_VERSION_PATCH* (page 77), stored in `bits [7:0]` of *__NMSIS_VERSION* (page 77)

2.5.2 Compiler Control

group **NMSIS_Core_CompilerControl**

Compiler agnostic #define symbols for generic c/c++ source code.

The NMSIS-Core provides the header file **nmsis_compiler.h** with consistent #define symbols for generate C or C++ source files that should be compiler agnostic. Each NMSIS compliant compiler should support the functionality described in this section.

The header file **nmsis_compiler.h** is also included by each Device Header File <device.h> so that these definitions are available.

Defines

__has_builtin(x) (0)

__ASM __asm

Pass information from the compiler to the assembler.

__INLINE inline

Recommend that function should be inlined by the compiler.

__STATIC_INLINE static inline

Define a static function that may be inlined by the compiler.

__STATIC_FORCEINLINE __attribute__((always_inline)) static inline

Define a static function that should be always inlined by the compiler.

__NO_RETURN __attribute__((__noreturn__))

Inform the compiler that a function does not return.

__USED __attribute__((used))

Inform that a variable shall be retained in executable image.

__WEAK __attribute__((weak))

restrict pointer qualifier to enable additional optimizations.

__VECTOR_SIZE(x) __attribute__((vector_size(x)))

specified the vector size of the variable, measured in bytes

[12] https://semver.org/

__PACKED __attribute__((packed, aligned(1)))

Request smallest possible alignment.

__PACKED_STRUCT struct __attribute__((packed, aligned(1)))

Request smallest possible alignment for a structure.

__PACKED_UNION union __attribute__((packed, aligned(1)))

Request smallest possible alignment for a union.

__UNALIGNED_UINT16_WRITE(addr, val) (void)((((struct *T_UINT16_WRITE* (page 80) *)(void *)(addr))->v) = (val))

Pointer for unaligned write of a uint16_t variable.

__UNALIGNED_UINT16_READ(addr) (((const struct *T_UINT16_READ* (page 80) *)(const void *)(addr))->v)

Pointer for unaligned read of a uint16_t variable.

__UNALIGNED_UINT32_WRITE(addr, val) (void)((((struct *T_UINT32_WRITE* (page 80) *)(void *)(addr))->v) = (val))

Pointer for unaligned write of a uint32_t variable.

__UNALIGNED_UINT32_READ(addr) (((const struct *T_UINT32_READ* (page 80) *)(const void *)(addr))->v)

Pointer for unaligned read of a uint32_t variable.

__ALIGNED(x) __attribute__((aligned(x)))

Minimum `x` bytes alignment for a variable.

__RESTRICT __restrict

restrict pointer qualifier to enable additional optimizations.

__COMPILER_BARRIER() *__ASM* (page 78) volatile("":::"memory")

Barrier to prevent compiler from reordering instructions.

__USUALLY(exp) __builtin_expect((exp), 1)

provide the compiler with branch prediction information, the branch is usually true

__RARELY(exp) __builtin_expect((exp), 0)

provide the compiler with branch prediction information, the branch is rarely true

__INTERRUPT __attribute__((interrupt))

Use this attribute to indicate that the specified function is an interrupt handler run in Machine Mode.

__MACHINE_INTERRUPT __attribute__ ((interrupt ("machine")))

Use this attribute to indicate that the specified function is an interrupt handler run in Machine Mode.

__SUPERVISOR_INTERRUPT __attribute__ ((interrupt ("supervisor")))

Use this attribute to indicate that the specified function is an interrupt handler run in Supervisor Mode.

__USER_INTERRUPT __attribute__ ((interrupt ("user")))

Use this attribute to indicate that the specified function is an interrupt handler run in User Mode.

Variables

__PACKED_STRUCT **T_UINT16_WRITE**

Packed struct for unaligned uint16_t write access.

__PACKED_STRUCT **T_UINT16_READ**

Packed struct for unaligned uint16_t read access.

__PACKED_STRUCT **T_UINT32_WRITE**

Packed struct for unaligned uint32_t write access.

__PACKED_STRUCT **T_UINT32_READ**

Packed struct for unaligned uint32_t read access.

2.5.3 Core CSR Register Access

Click Nuclei Core CSR[13] to learn about Core CSR in Nuclei ISA Spec.

group **NMSIS_Core_CSR_Register_Access**

Functions to access the Core CSR Registers.

The following functions or macros provide access to Core CSR registers.

- *Core CSR Encodings* (page 109)
- *Core CSR Registers* (page 84)

Defines

__RV_CSR_SWAP(csr, val)

CSR operation Macro for csrrw instruction.

Read the content of csr register to __v, then write content of val into csr register, then return __v

Parameters

- **csr** – CSR macro definition defined in *Core CSR Registers* (page 84), eg. *CSR_MSTATUS* (page 90)
- **val** – value to store into the CSR register

Returns the CSR register value before written

__RV_CSR_READ(csr)

CSR operation Macro for csrr instruction.

Read the content of csr register to __v and return it

Parameters

- **csr** – CSR macro definition defined in *Core CSR Registers* (page 84), eg. *CSR_MSTATUS* (page 90)

Returns the CSR register value

[13] https://doc.nucleisys.com/nuclei_spec/isa/core_csr.html

__RV_CSR_WRITE(csr, val)

CSR operation Macro for csrw instruction.

Write the content of val to csr register

Parameters

- **csr** – CSR macro definition defined in *Core CSR Registers* (page 84), eg. *CSR_MSTATUS* (page 90)
- **val** – value to store into the CSR register

__RV_CSR_READ_SET(csr, val)

CSR operation Macro for csrrs instruction.

Read the content of csr register to __v, then set csr register to be __v | val, then return __v

Parameters

- **csr** – CSR macro definition defined in *Core CSR Registers* (page 84), eg. *CSR_MSTATUS* (page 90)
- **val** – Mask value to be used wih csrrs instruction

Returns the CSR register value before written

__RV_CSR_SET(csr, val)

CSR operation Macro for csrs instruction.

Set csr register to be csr_content | val

Parameters

- **csr** – CSR macro definition defined in *Core CSR Registers* (page 84), eg. *CSR_MSTATUS* (page 90)
- **val** – Mask value to be used wih csrs instruction

__RV_CSR_READ_CLEAR(csr, val)

CSR operation Macro for csrrc instruction.

Read the content of csr register to __v, then set csr register to be __v & ~val, then return __v

Parameters

- **csr** – CSR macro definition defined in *Core CSR Registers* (page 84), eg. *CSR_MSTATUS* (page 90)
- **val** – Mask value to be used wih csrrc instruction

Returns the CSR register value before written

__RV_CSR_CLEAR(csr, val)

CSR operation Macro for csrc instruction.

Set csr register to be csr_content & ~val

Parameters

- **csr** – CSR macro definition defined in *Core CSR Registers* (page 84), eg. *CSR_MSTATUS* (page 90)
- **val** – Mask value to be used wih csrc instruction

Functions

`__STATIC_FORCEINLINE void __switch_mode (uint8_t mode, uintptr_t stack, void(*entry_point)(void))`

switch privilege from machine mode to others.

Execute into entry_point in mode(supervisor or user) with given stack

Parameters

- `mode` – privilege mode
- `stack` – predefined stack, size should set enough
- `entry_point` – a function pointer to execute

`__STATIC_FORCEINLINE void __enable_irq (void)`

Enable IRQ Interrupts.

Enables IRQ interrupts by setting the MIE-bit in the MSTATUS Register.

Remark

Can only be executed in Privileged modes.

`__STATIC_FORCEINLINE void __disable_irq (void)`

Disable IRQ Interrupts.

Disables IRQ interrupts by clearing the MIE-bit in the MSTATUS Register.

Remark

Can only be executed in Privileged modes.

`__STATIC_FORCEINLINE void __enable_irq_s (void)`

Enable IRQ Interrupts in supervisor mode.

Enables IRQ interrupts by setting the SIE-bit in the SSTATUS Register.

Remark

Can only be executed in Privileged modes.

`__STATIC_FORCEINLINE void __disable_irq_s (void)`

Disable IRQ Interrupts in supervisor mode.

Disables IRQ interrupts by clearing the SIE-bit in the SSTATUS Register.

Remark

Can only be executed in Privileged modes.

`__STATIC_FORCEINLINE uint64_t __get_rv_cycle (void)`

Read whole 64 bits value of mcycle counter.

This function will read the whole 64 bits of MCYCLE register

Remark

It will work for both RV32 and RV64 to get full 64bits value of MCYCLE

Returns The whole 64 bits value of MCYCLE

`__STATIC_FORCEINLINE uint64_t __get_rv_instret (void)`

Read whole 64 bits value of machine instruction-retired counter.

This function will read the whole 64 bits of MINSTRET register

Remark

It will work for both RV32 and RV64 to get full 64bits value of MINSTRET

Returns The whole 64 bits value of MINSTRET

`__STATIC_FORCEINLINE uint64_t __get_rv_time (void)`

Read whole 64 bits value of real-time clock.

This function will read the whole 64 bits of TIME register

Remark

It will work for both RV32 and RV64 to get full 64bits value of TIME

Attention only available when user mode available

Returns The whole 64 bits value of TIME CSR

`__STATIC_FORCEINLINE unsigned long __get_cluster_id (void)`

Get cluster id of current cluster.

This function will get cluster id of current cluster in a multiple cluster system

Remark

mhartid bit 15-8 is designed for cluster id in nuclei subsystem reference design

Attention function is allowed in machine mode only

Returns The cluster id of current cluster

`__STATIC_FORCEINLINE unsigned long __get_hart_index (void)`

Get hart index of current cluster.

This function will get hart index of current cluster in a multiple cluster system, hart index is hartid - hartid offset, for example if your hartid is 1, and offset is 1, then hart index is 0

Attention function is allowed in machine mode only

Returns The hart index of current cluster

`__STATIC_FORCEINLINE unsigned long __get_hart_id (void)`

Get hart id of current cluster.

This function will get hart id of current cluster in a multiple cluster system

---

Remark

it will return full hartid not part of it for reference subsystem design, if your reference subsystem design has hartid offset, please define __HARTID_OFFSET in <Device>.h

---

Attention function is allowed in machine mode only

Returns The hart id of current cluster

2.5.4 Core CSR Encoding

Click Nuclei Core CSR[14] to learn about Core CSR in Nuclei ISA Spec.

Core CSR Register Definitions

group **`NMSIS_Core_CSR_Registers`**

NMSIS Core CSR Register Definitions.

The following macros are used for CSR Register Defintions.

Defines

`CSR_USTATUS` 0x0

`CSR_FFLAGS` 0x1

`CSR_FRM` 0x2

`CSR_FCSR` 0x3

[14] https://doc.nucleisys.com/nuclei_spec/isa/core_csr.html

CSR_VSTART 0x8

CSR_VXSAT 0x9

CSR_VXRM 0xa

CSR_VCSR 0xf

CSR_SEED 0x15

CSR_JVT 0x17

CSR_CYCLE 0xc00

CSR_TIME 0xc01

CSR_INSTRET 0xc02

CSR_HPMCOUNTER3 0xc03

CSR_HPMCOUNTER4 0xc04

CSR_HPMCOUNTER5 0xc05

CSR_HPMCOUNTER6 0xc06

CSR_HPMCOUNTER7 0xc07

CSR_HPMCOUNTER8 0xc08

CSR_HPMCOUNTER9 0xc09

CSR_HPMCOUNTER10 0xc0a

CSR_HPMCOUNTER11 0xc0b

CSR_HPMCOUNTER12 0xc0c

CSR_HPMCOUNTER13 0xc0d

CSR_HPMCOUNTER14 0xc0e

CSR_HPMCOUNTER15 0xc0f

CSR_HPMCOUNTER16 0xc10

CSR_HPMCOUNTER17 0xc11

CSR_HPMCOUNTER18 0xc12

CSR_HPMCOUNTER19 0xc13

CSR_HPMCOUNTER20 0xc14

CSR_HPMCOUNTER21 0xc15

CSR_HPMCOUNTER22 0xc16

CSR_HPMCOUNTER23 0xc17

CSR_HPMCOUNTER24 0xc18

CSR_HPMCOUNTER25 0xc19

CSR_HPMCOUNTER26 0xc1a

CSR_HPMCOUNTER27 0xc1b

CSR_HPMCOUNTER28 0xc1c

CSR_HPMCOUNTER29 0xc1d

CSR_HPMCOUNTER30 0xc1e

CSR_HPMCOUNTER31 0xc1f

CSR_VL 0xc20

CSR_VTYPE 0xc21

CSR_VLENB 0xc22

CSR_SSTATUS 0x100

CSR_SEDELEG 0x102

CSR_SIDELEG 0x103

CSR_SIE 0x104

CSR_STVEC 0x105

CSR_STVT 0x107

CSR_STVT 0x107

CSR_SCOUNTEREN 0x106

CSR_SENVCFG 0x10a

CSR_SSTATEEN0 0x10c

CSR_SSTATEEN1 0x10d

CSR_SSTATEEN2 0x10e

CSR_SSTATEEN3 0x10f

CSR_SSCRATCH 0x140

CSR_SEPC 0x141

CSR_SCAUSE 0x142

CSR_STVAL 0x143

CSR_SIP 0x144

CSR_STIMECMP 0x14d

CSR_SATP 0x180

CSR_SCONTEXT 0x5a8

CSR_VSSTATUS 0x200

`CSR_VSIE` 0x204

`CSR_VSTVEC` 0x205

`CSR_VSSCRATCH` 0x240

`CSR_VSEPC` 0x241

`CSR_VSCAUSE` 0x242

`CSR_VSTVAL` 0x243

`CSR_VSIP` 0x244

`CSR_VSTIMECMP` 0x24d

`CSR_VSATP` 0x280

`CSR_HSTATUS` 0x600

`CSR_HEDELEG` 0x602

`CSR_HIDELEG` 0x603

`CSR_HIE` 0x604

`CSR_HTIMEDELTA` 0x605

`CSR_HCOUNTEREN` 0x606

`CSR_HGEIE` 0x607

`CSR_HENVCFG` 0x60a

`CSR_HSTATEEN0` 0x60c

`CSR_HSTATEEN1` 0x60d

`CSR_HSTATEEN2` 0x60e

`CSR_HSTATEEN3` 0x60f

`CSR_HTVAL` 0x643

`CSR_HIP` 0x644

`CSR_HVIP` 0x645

`CSR_HTINST` 0x64a

`CSR_HGATP` 0x680

`CSR_HCONTEXT` 0x6a8

`CSR_HGEIP` 0xe12

`CSR_SCOUNTOVF` 0xda0

`CSR_UTVT` 0x7

`CSR_UNXTI` 0x45

`CSR_UINTSTATUS` 0x46

`CSR_USCRATCHCSW` 0x48

`CSR_USCRATCHCSWL` 0x49

`CSR_SNXTI` 0x145

`CSR_SINTSTATUS` 0x146

`CSR_SSCRATCHCSW` 0x148

`CSR_SSCRATCHCSWL` 0x149

`CSR_MTVT` 0x307

`CSR_MTVT` 0x307

`CSR_MNXTI` 0x345

`CSR_MNXTI` 0x345

`CSR_MINTSTATUS` 0x346

`CSR_MINTSTATUS` 0x346

`CSR_MSCRATCHCSW` 0x348

`CSR_MSCRATCHCSW` 0x348

`CSR_MSCRATCHCSWL` 0x349

`CSR_MSCRATCHCSWL` 0x349

`CSR_MSTATUS` 0x300

`CSR_MISA` 0x301

`CSR_MEDELEG` 0x302

`CSR_MIDELEG` 0x303

`CSR_MIE` 0x304

`CSR_MTVEC` 0x305

`CSR_MCOUNTEREN` 0x306

`CSR_MENVCFG` 0x30a

`CSR_MSTATEEN0` 0x30c

`CSR_MSTATEEN1` 0x30d

`CSR_MSTATEEN2` 0x30e

`CSR_MSTATEEN3` 0x30f

`CSR_MCOUNTINHIBIT` 0x320

`CSR_MSCRATCH` 0x340

`CSR_MEPC` 0x341

CSR_MCAUSE 0x342

CSR_MTVAL 0x343

CSR_MBADADDR 0x343

CSR_MIP 0x344

CSR_MTINST 0x34a

CSR_MTVAL2 0x34b

CSR_PMPCFG0 0x3a0

CSR_PMPCFG1 0x3a1

CSR_PMPCFG2 0x3a2

CSR_PMPCFG3 0x3a3

CSR_PMPCFG4 0x3a4

CSR_PMPCFG5 0x3a5

CSR_PMPCFG6 0x3a6

CSR_PMPCFG7 0x3a7

CSR_PMPCFG8 0x3a8

CSR_PMPCFG9 0x3a9

CSR_PMPCFG10 0x3aa

CSR_PMPCFG11 0x3ab

CSR_PMPCFG12 0x3ac

CSR_PMPCFG13 0x3ad

CSR_PMPCFG14 0x3ae

`CSR_PMPCFG15` 0x3af

`CSR_PMPADDR0` 0x3b0

`CSR_PMPADDR1` 0x3b1

`CSR_PMPADDR2` 0x3b2

`CSR_PMPADDR3` 0x3b3

`CSR_PMPADDR4` 0x3b4

`CSR_PMPADDR5` 0x3b5

`CSR_PMPADDR6` 0x3b6

`CSR_PMPADDR7` 0x3b7

`CSR_PMPADDR8` 0x3b8

`CSR_PMPADDR9` 0x3b9

`CSR_PMPADDR10` 0x3ba

`CSR_PMPADDR11` 0x3bb

`CSR_PMPADDR12` 0x3bc

`CSR_PMPADDR13` 0x3bd

`CSR_PMPADDR14` 0x3be

`CSR_PMPADDR15` 0x3bf

`CSR_PMPADDR16` 0x3c0

`CSR_PMPADDR17` 0x3c1

`CSR_PMPADDR18` 0x3c2

`CSR_PMPADDR19` 0x3c3

CSR_PMPADDR20 0x3c4

CSR_PMPADDR21 0x3c5

CSR_PMPADDR22 0x3c6

CSR_PMPADDR23 0x3c7

CSR_PMPADDR24 0x3c8

CSR_PMPADDR25 0x3c9

CSR_PMPADDR26 0x3ca

CSR_PMPADDR27 0x3cb

CSR_PMPADDR28 0x3cc

CSR_PMPADDR29 0x3cd

CSR_PMPADDR30 0x3ce

CSR_PMPADDR31 0x3cf

CSR_PMPADDR32 0x3d0

CSR_PMPADDR33 0x3d1

CSR_PMPADDR34 0x3d2

CSR_PMPADDR35 0x3d3

CSR_PMPADDR36 0x3d4

CSR_PMPADDR37 0x3d5

CSR_PMPADDR38 0x3d6

CSR_PMPADDR39 0x3d7

CSR_PMPADDR40 0x3d8

CSR_PMPADDR41 0x3d9

CSR_PMPADDR42 0x3da

CSR_PMPADDR43 0x3db

CSR_PMPADDR44 0x3dc

CSR_PMPADDR45 0x3dd

CSR_PMPADDR46 0x3de

CSR_PMPADDR47 0x3df

CSR_PMPADDR48 0x3e0

CSR_PMPADDR49 0x3e1

CSR_PMPADDR50 0x3e2

CSR_PMPADDR51 0x3e3

CSR_PMPADDR52 0x3e4

CSR_PMPADDR53 0x3e5

CSR_PMPADDR54 0x3e6

CSR_PMPADDR55 0x3e7

CSR_PMPADDR56 0x3e8

CSR_PMPADDR57 0x3e9

CSR_PMPADDR58 0x3ea

CSR_PMPADDR59 0x3eb

CSR_PMPADDR60 0x3ec

CSR_PMPADDR61 0x3ed

CSR_PMPADDR62 0x3ee

CSR_PMPADDR63 0x3ef

CSR_MSECCFG 0x747

CSR_TSELECT 0x7a0

CSR_TDATA1 0x7a1

CSR_TDATA2 0x7a2

CSR_TDATA3 0x7a3

CSR_TINFO 0x7a4

CSR_TCONTROL 0x7a5

CSR_MCONTEXT 0x7a8

CSR_MSCONTEXT 0x7aa

CSR_DCSR 0x7b0

CSR_DPC 0x7b1

CSR_DSCRATCH0 0x7b2

CSR_DSCRATCH1 0x7b3

CSR_MCYCLE 0xb00

CSR_MINSTRET 0xb02

CSR_MHPMCOUNTER3 0xb03

CSR_MHPMCOUNTER4 0xb04

CSR_MHPMCOUNTER5 0xb05

CSR_MHPMCOUNTER6 0xb06

CSR_MHPMCOUNTER7 0xb07

CSR_MHPMCOUNTER8 0xb08

CSR_MHPMCOUNTER9 0xb09

CSR_MHPMCOUNTER10 0xb0a

CSR_MHPMCOUNTER11 0xb0b

CSR_MHPMCOUNTER12 0xb0c

CSR_MHPMCOUNTER13 0xb0d

CSR_MHPMCOUNTER14 0xb0e

CSR_MHPMCOUNTER15 0xb0f

CSR_MHPMCOUNTER16 0xb10

CSR_MHPMCOUNTER17 0xb11

CSR_MHPMCOUNTER18 0xb12

CSR_MHPMCOUNTER19 0xb13

CSR_MHPMCOUNTER20 0xb14

CSR_MHPMCOUNTER21 0xb15

CSR_MHPMCOUNTER22 0xb16

CSR_MHPMCOUNTER23 0xb17

CSR_MHPMCOUNTER24 0xb18

CSR_MHPMCOUNTER25 0xb19

CSR_MHPMCOUNTER26 0xb1a

CSR_MHPMCOUNTER27 0xb1b

CSR_MHPMCOUNTER28 0xb1c

CSR_MHPMCOUNTER29 0xb1d

CSR_MHPMCOUNTER30 0xb1e

CSR_MHPMCOUNTER31 0xb1f

CSR_MHPMEVENT3 0x323

CSR_MHPMEVENT4 0x324

CSR_MHPMEVENT5 0x325

CSR_MHPMEVENT6 0x326

CSR_MHPMEVENT7 0x327

CSR_MHPMEVENT8 0x328

CSR_MHPMEVENT9 0x329

CSR_MHPMEVENT10 0x32a

CSR_MHPMEVENT11 0x32b

CSR_MHPMEVENT12 0x32c

CSR_MHPMEVENT13 0x32d

CSR_MHPMEVENT14 0x32e

CSR_MHPMEVENT15 0x32f

CSR_MHPMEVENT16 0x330

CSR_MHPMEVENT17 0x331

CSR_MHPMEVENT18 0x332

CSR_MHPMEVENT19 0x333

CSR_MHPMEVENT20 0x334

CSR_MHPMEVENT21 0x335

CSR_MHPMEVENT22 0x336

CSR_MHPMEVENT23 0x337

CSR_MHPMEVENT24 0x338

CSR_MHPMEVENT25 0x339

CSR_MHPMEVENT26 0x33a

CSR_MHPMEVENT27 0x33b

CSR_MHPMEVENT28 0x33c

CSR_MHPMEVENT29 0x33d

CSR_MHPMEVENT30 0x33e

CSR_MHPMEVENT31 0x33f

CSR_MVENDORID 0xf11

CSR_MARCHID 0xf12

CSR_MIMPID 0xf13

CSR_MHARTID 0xf14

CSR_MCONFIGPTR 0xf15

CSR_STIMECMPH 0x15d

CSR_VSTIMECMPH 0x25d

CSR_HTIMEDELTAH 0x615

CSR_HENVCFGH 0x61a

CSR_HSTATEEN0H 0x61c

CSR_HSTATEEN1H 0x61d

CSR_HSTATEEN2H 0x61e

CSR_HSTATEEN3H 0x61f

CSR_CYCLEH 0xc80

CSR_TIMEH 0xc81

CSR_INSTRETH 0xc82

CSR_HPMCOUNTER3H 0xc83

CSR_HPMCOUNTER4H 0xc84

CSR_HPMCOUNTER5H 0xc85

CSR_HPMCOUNTER6H 0xc86

CSR_HPMCOUNTER7H 0xc87

CSR_HPMCOUNTER8H 0xc88

CSR_HPMCOUNTER9H 0xc89

CSR_HPMCOUNTER10H 0xc8a

CSR_HPMCOUNTER11H 0xc8b

CSR_HPMCOUNTER12H 0xc8c

CSR_HPMCOUNTER13H 0xc8d

CSR_HPMCOUNTER14H 0xc8e

CSR_HPMCOUNTER15H 0xc8f

CSR_HPMCOUNTER16H 0xc90

CSR_HPMCOUNTER17H 0xc91

CSR_HPMCOUNTER18H 0xc92

CSR_HPMCOUNTER19H 0xc93

CSR_HPMCOUNTER20H 0xc94

CSR_HPMCOUNTER21H 0xc95

CSR_HPMCOUNTER22H 0xc96

CSR_HPMCOUNTER23H 0xc97

CSR_HPMCOUNTER24H 0xc98

CSR_HPMCOUNTER25H 0xc99

CSR_HPMCOUNTER26H 0xc9a

CSR_HPMCOUNTER27H 0xc9b

CSR_HPMCOUNTER28H 0xc9c

CSR_HPMCOUNTER29H 0xc9d

CSR_HPMCOUNTER30H 0xc9e

CSR_HPMCOUNTER31H 0xc9f

CSR_MSTATUSH 0x310

CSR_MENVCFGH 0x31a

CSR_MSTATEEN0H 0x31c

CSR_MSTATEEN1H 0x31d

CSR_MSTATEEN2H 0x31e

CSR_MSTATEEN3H 0x31f

CSR_MHPMEVENT3H 0x723

CSR_MHPMEVENT4H 0x724

CSR_MHPMEVENT5H 0x725

CSR_MHPMEVENT6H 0x726

CSR_MHPMEVENT7H 0x727

CSR_MHPMEVENT8H 0x728

CSR_MHPMEVENT9H 0x729

CSR_MHPMEVENT10H 0x72a

CSR_MHPMEVENT11H 0x72b

CSR_MHPMEVENT12H 0x72c

CSR_MHPMEVENT13H 0x72d

CSR_MHPMEVENT14H 0x72e

CSR_MHPMEVENT15H 0x72f

CSR_MHPMEVENT16H 0x730

CSR_MHPMEVENT17H 0x731

CSR_MHPMEVENT18H 0x732

CSR_MHPMEVENT19H 0x733

CSR_MHPMEVENT20H 0x734

CSR_MHPMEVENT21H 0x735

CSR_MHPMEVENT22H 0x736

CSR_MHPMEVENT23H 0x737

CSR_MHPMEVENT24H 0x738

CSR_MHPMEVENT25H 0x739

CSR_MHPMEVENT26H 0x73a

CSR_MHPMEVENT27H 0x73b

CSR_MHPMEVENT28H 0x73c

CSR_MHPMEVENT29H 0x73d

CSR_MHPMEVENT30H 0x73e

CSR_MHPMEVENT31H 0x73f

CSR_MSECCFGH 0x757

CSR_MCYCLEH 0xb80

CSR_MINSTRETH 0xb82

CSR_MHPMCOUNTER3H 0xb83

CSR_MHPMCOUNTER4H 0xb84

CSR_MHPMCOUNTER5H 0xb85

CSR_MHPMCOUNTER6H 0xb86

CSR_MHPMCOUNTER7H 0xb87

CSR_MHPMCOUNTER8H 0xb88

CSR_MHPMCOUNTER9H 0xb89

CSR_MHPMCOUNTER10H 0xb8a

CSR_MHPMCOUNTER11H 0xb8b

CSR_MHPMCOUNTER12H 0xb8c

`CSR_MHPMCOUNTER13H` 0xb8d

`CSR_MHPMCOUNTER14H` 0xb8e

`CSR_MHPMCOUNTER15H` 0xb8f

`CSR_MHPMCOUNTER16H` 0xb90

`CSR_MHPMCOUNTER17H` 0xb91

`CSR_MHPMCOUNTER18H` 0xb92

`CSR_MHPMCOUNTER19H` 0xb93

`CSR_MHPMCOUNTER20H` 0xb94

`CSR_MHPMCOUNTER21H` 0xb95

`CSR_MHPMCOUNTER22H` 0xb96

`CSR_MHPMCOUNTER23H` 0xb97

`CSR_MHPMCOUNTER24H` 0xb98

`CSR_MHPMCOUNTER25H` 0xb99

`CSR_MHPMCOUNTER26H` 0xb9a

`CSR_MHPMCOUNTER27H` 0xb9b

`CSR_MHPMCOUNTER28H` 0xb9c

`CSR_MHPMCOUNTER29H` 0xb9d

`CSR_MHPMCOUNTER30H` 0xb9e

`CSR_MHPMCOUNTER31H` 0xb9f

`CSR_SPMPCFG0` 0x1A0

`CSR_SPMPCFG1` 0x1A1

CSR_SPMPCFG2 0x1A2

CSR_SPMPCFG3 0x1A3

CSR_SPMPADDR0 0x1B0

CSR_SPMPADDR1 0x1B1

CSR_SPMPADDR2 0x1B2

CSR_SPMPADDR3 0x1B3

CSR_SPMPADDR4 0x1B4

CSR_SPMPADDR5 0x1B5

CSR_SPMPADDR6 0x1B6

CSR_SPMPADDR7 0x1B7

CSR_SPMPADDR8 0x1B8

CSR_SPMPADDR9 0x1B9

CSR_SPMPADDR10 0x1BA

CSR_SPMPADDR11 0x1BB

CSR_SPMPADDR12 0x1BC

CSR_SPMPADDR13 0x1BD

CSR_SPMPADDR14 0x1BE

CSR_SPMPADDR15 0x1BF

CSR_SPMUCFG0 0x1A0

CSR_SPMUCFG1 0x1A1

CSR_SPMUCFG2 0x1A2

`CSR_SPMUCFG3` 0x1A3

`CSR_SPMUADDR0` 0x1B0

`CSR_SPMUADDR1` 0x1B1

`CSR_SPMUADDR2` 0x1B2

`CSR_SPMUADDR3` 0x1B3

`CSR_SPMUADDR4` 0x1B4

`CSR_SPMUADDR5` 0x1B5

`CSR_SPMUADDR6` 0x1B6

`CSR_SPMUADDR7` 0x1B7

`CSR_SPMUADDR8` 0x1B8

`CSR_SPMUADDR9` 0x1B9

`CSR_SPMUADDR10` 0x1BA

`CSR_SPMUADDR11` 0x1BB

`CSR_SPMUADDR12` 0x1BC

`CSR_SPMUADDR13` 0x1BD

`CSR_SPMUADDR14` 0x1BE

`CSR_SPMUADDR15` 0x1BF

`CSR_SPMUSWITCH0` 0x170

`CSR_SPMUSWITCH1` 0x171

`CSR_MCLICBASE` 0x350

`CSR_UCODE` 0x801

CSR_MILM_CTL 0x7C0

CSR_MDLM_CTL 0x7C1

CSR_MECC_CODE 0x7C2

CSR_MNVEC 0x7C3

CSR_MSUBM 0x7C4

CSR_MDCAUSE 0x7C9

CSR_MCACHE_CTL 0x7CA

CSR_MMISC_CTL 0x7D0

CSR_MSAVESTATUS 0x7D6

CSR_MSAVEEPC1 0x7D7

CSR_MSAVECAUSE1 0x7D8

CSR_MSAVEEPC2 0x7D9

CSR_MSAVECAUSE2 0x7DA

CSR_MSAVEDCAUSE1 0x7DB

CSR_MSAVEDCAUSE2 0x7DC

CSR_MTLB_CTL 0x7DD

CSR_MECC_LOCK 0x7DE

CSR_MFP16MODE 0x7E2

CSR_LSTEPFORC 0x7E9

CSR_PUSHMSUBM 0x7EB

CSR_MTVT2 0x7EC

CSR_JALMNXTI 0x7ED

CSR_PUSHMCAUSE 0x7EE

CSR_PUSHMEPC 0x7EF

CSR_MPPICFG_INFO 0x7F0

CSR_MFIOCFG_INFO 0x7F1

CSR_MDEVB 0x7F3

CSR_MDEVM 0x7F4

CSR_MNOCB 0x7F5

CSR_MNOCM 0x7F6

CSR_MATTRI0_BASE 0x7F3

CSR_MATTRI0_MASK 0x7F4

CSR_MATTRI1_BASE 0x7F5

CSR_MATTRI1_MASK 0x7F6

CSR_MATTRI2_BASE 0x7F9

CSR_MATTRI2_MASK 0x7FA

CSR_MATTRI3_BASE 0x7FB

CSR_MATTRI3_MASK 0x7FC

CSR_MATTRI4_BASE 0x7FD

CSR_MATTRI4_MASK 0x7FE

CSR_MSMPCFG_INFO 0x7F7

CSR_MIRGB_INFO 0x7F7

CSR_SLEEPVALUE 0x811

CSR_TXEVT 0x812

CSR_WFE 0x810

CSR_JALSNXTI 0x947

CSR_STVT2 0x948

CSR_PUSHSCAUSE 0x949

CSR_PUSHSEPC 0x94A

CSR_SDCAUSE 0x9C0

CSR_MICFG_INFO 0xFC0

CSR_MDCFG_INFO 0xFC1

CSR_MCFG_INFO 0xFC2

CSR_MTLBCFG_INFO 0xFC3

CSR_MECC_STATUS 0xBC4

CSR_MSTACK_CTRL 0x7C6

CSR_MSTACK_BOUND 0x7C7

CSR_MSTACK_BASE 0x7C8

CSR_CCM_MBEGINADDR 0x7CB

CSR_CCM_MCOMMAND 0x7CC

CSR_CCM_MDATA 0x7CD

CSR_CCM_SUEN 0x7CE

CSR_CCM_SBEGINADDR 0x5CB

`CSR_CCM_SCOMMAND` 0x5CC

`CSR_CCM_SDATA` 0x5CD

`CSR_CCM_UBEGINADDR` 0x4CB

`CSR_CCM_UCOMMAND` 0x4CC

`CSR_CCM_UDATA` 0x4CD

`CSR_CCM_FPIPE` 0x4CF

Other Core Related Macros

group `NMSIS_Core_CSR_Encoding`

NMSIS Core CSR Encodings.

The following macros are used for CSR encodings

Defines

`MSTATUS_UIE` 0x00000001

`MSTATUS_SIE` 0x00000002

`MSTATUS_HIE` 0x00000004

`MSTATUS_MIE` 0x00000008

`MSTATUS_UPIE` 0x00000010

`MSTATUS_SPIE` 0x00000020

`MSTATUS_UBE` 0x00000040

`MSTATUS_MPIE` 0x00000080

`MSTATUS_SPP` 0x00000100

`MSTATUS_VS` 0x00000600

`MSTATUS_MPP` 0x00001800

MSTATUS_FS 0x00006000

MSTATUS_XS 0x00018000

MSTATUS_MPRV 0x00020000

MSTATUS_SUM 0x00040000

MSTATUS_MXR 0x00080000

MSTATUS_TVM 0x00100000

MSTATUS_TW 0x00200000

MSTATUS_TSR 0x00400000

MSTATUS32_SD 0x80000000

MSTATUS_UXL 0x0000000300000000

MSTATUS_SXL 0x0000000C00000000

MSTATUS_SBE 0x0000001000000000

MSTATUS_MBE 0x0000002000000000

MSTATUS_GVA 0x0000004000000000

MSTATUS_MPV 0x0000008000000000

MSTATUS64_SD 0x8000000000000000

MSTATUS_FS_INITIAL 0x00002000

MSTATUS_FS_CLEAN 0x00004000

MSTATUS_FS_DIRTY 0x00006000

MSTATUS_VS_INITIAL 0x00000200

MSTATUS_VS_CLEAN 0x00000400

MSTATUS_VS_DIRTY 0x00000600

MSTATUSH_SBE 0x00000010

MSTATUSH_MBE 0x00000020

MSTATUSH_GVA 0x00000040

MSTATUSH_MPV 0x00000080

SSTATUS_UIE 0x00000001

SSTATUS_SIE 0x00000002

SSTATUS_UPIE 0x00000010

SSTATUS_SPIE 0x00000020

SSTATUS_UBE 0x00000040

SSTATUS_SPP 0x00000100

SSTATUS_VS 0x00000600

SSTATUS_FS 0x00006000

SSTATUS_XS 0x00018000

SSTATUS_SUM 0x00040000

SSTATUS_MXR 0x00080000

SSTATUS32_SD 0x80000000

SSTATUS_UXL 0x0000000300000000

SSTATUS64_SD 0x8000000000000000

USTATUS_UIE 0x00000001

USTATUS_UPIE 0x00000010

DCSR_XDEBUGVER (3U<<30)

DCSR_NDRESET (1<<29)

DCSR_FULLRESET (1<<28)

DCSR_EBREAKM (1<<15)

DCSR_EBREAKH (1<<14)

DCSR_EBREAKS (1<<13)

DCSR_EBREAKU (1<<12)

DCSR_STOPCYCLE (1<<10)

DCSR_STOPTIME (1<<9)

DCSR_CAUSE (7<<6)

DCSR_DEBUGINT (1<<5)

DCSR_HALT (1<<3)

DCSR_STEP (1<<2)

DCSR_PRV (3<<0)

DCSR_CAUSE_NONE 0

DCSR_CAUSE_SWBP 1

DCSR_CAUSE_HWBP 2

DCSR_CAUSE_DEBUGINT 3

DCSR_CAUSE_STEP 4

DCSR_CAUSE_HALT 5

MCONTROL_TYPE(xlen) (0xfULL<<((xlen)-4))

MCONTROL_DMODE(xlen) (1ULL<<((xlen)-5))

MCONTROL_MASKMAX(xlen) (0x3fULL<<((xlen)-11))

MCONTROL_SELECT (1<<19)

MCONTROL_TIMING (1<<18)

MCONTROL_ACTION (0x3f<<12)

MCONTROL_CHAIN (1<<11)

MCONTROL_MATCH (0xf<<7)

MCONTROL_M (1<<6)

MCONTROL_H (1<<5)

MCONTROL_S (1<<4)

MCONTROL_U (1<<3)

MCONTROL_EXECUTE (1<<2)

MCONTROL_STORE (1<<1)

MCONTROL_LOAD (1<<0)

MCONTROL_TYPE_NONE 0

MCONTROL_TYPE_MATCH 2

MCONTROL_ACTION_DEBUG_EXCEPTION 0

MCONTROL_ACTION_DEBUG_MODE 1

MCONTROL_ACTION_TRACE_START 2

MCONTROL_ACTION_TRACE_STOP 3

MCONTROL_ACTION_TRACE_EMIT 4

MCONTROL_MATCH_EQUAL 0

MCONTROL_MATCH_NAPOT 1

MCONTROL_MATCH_GE 2

MCONTROL_MATCH_LT 3

MCONTROL_MATCH_MASK_LOW 4

MCONTROL_MATCH_MASK_HIGH 5

MIP_SSIP (1 << *IRQ_S_SOFT* (page 121))

MIP_HSIP (1 << *IRQ_H_SOFT* (page 121))

MIP_MSIP (1 << *IRQ_M_SOFT* (page 121))

MIP_STIP (1 << *IRQ_S_TIMER* (page 121))

MIP_HTIP (1 << *IRQ_H_TIMER* (page 121))

MIP_MTIP (1 << *IRQ_M_TIMER* (page 121))

MIP_SEIP (1 << *IRQ_S_EXT* (page 121))

MIP_HEIP (1 << *IRQ_H_EXT* (page 121))

MIP_MEIP (1 << *IRQ_M_EXT* (page 122))

MIE_SSIE *MIP_SSIP* (page 114)

MIE_HSIE *MIP_HSIP* (page 114)

MIE_MSIE *MIP_MSIP* (page 114)

MIE_STIE *MIP_STIP* (page 114)

MIE_HTIE *MIP_HTIP* (page 114)

MIE_MTIE *MIP_MTIP* (page 114)

MIE_SEIE *MIP_SEIP* (page 114)

MIE_HEIE *MIP_HEIP* (page 114)

MIE_MEIE *MIP_MEIP* (page 114)

MCAUSE_INTR (1ULL << (__riscv_xlen - 1))

MCAUSE_CAUSE 0x00000FFFUL

SCAUSE_INTR *MCAUSE_INTR* (page 115)

SCAUSE_CAUSE 0x000003FFUL

MENVCFG_CBIE_EN (0x11 << 4)

MENVCFG_CBIE_FLUSH (0x01 << 4)

MENVCFG_CBIE_INVAL (0x11 << 4)

MENVCFG_CBCFE (0x1 << 6)

MENVCFG_CBZE (0x1 << 7)

SENVCFG_CBIE_EN (0x11 << 4)

SENVCFG_CBIE_FLUSH (0x01 << 4)

SENVCFG_CBIE_INVAL (0x11 << 4)

SENVCFG_CBCFE (0x1 << 6)

SENVCFG_CBZE (0x1 << 7)

UCODE_OV (0x1)

CSR_MCACHE_CTL_IE 0x00000001

CSR_MCACHE_CTL_DE 0x00010000

WFE_WFE (0x1)

TXEVT_TXEVT (0x1)

SLEEPVALUE_SLEEPVALUE (0x1)

MCOUNTINHIBIT_IR (1<<2)

MCOUNTINHIBIT_CY (1<<0)

MILM_CTL_ILM_BPA (((1ULL<<((__riscv_xlen)-10))-1)<<10)

MILM_CTL_ILM_RWECC (1<<3)

MILM_CTL_ILM_ECC_EXCP_EN (1<<2)

MILM_CTL_ILM_ECC_EN (1<<1)

MILM_CTL_ILM_EN (1<<0)

MDLM_CTL_DLM_BPA (((1ULL<<((__riscv_xlen)-10))-1)<<10)

MDLM_CTL_DLM_RWECC (1<<3)

MDLM_CTL_DLM_ECC_EXCP_EN (1<<2)

MDLM_CTL_DLM_ECC_EN (1<<1)

MDLM_CTL_DLM_EN (1<<0)

MSUBM_PTYP (0x3<<8)

MSUBM_TYP (0x3<<6)

MDCAUSE_MDCAUSE (0x3)

MMISC_CTL_LDSPEC_ENABLE (1<<12)

MMISC_CTL_SIJUMP_ENABLE (1<<11)

MMISC_CTL_IMRETURN_ENABLE (1<<10)

MMISC_CTL_NMI_CAUSE_FFF (1<<9)

MMISC_CTL_CODE_BUS_ERR (1<<8)

MMISC_CTL_MISALIGN (1<<6)

MMISC_CTL_ZC (1<<7)

MMISC_CTL_BPU (1<<3)

MCACHE_CTL_IC_EN (1<<0)

MCACHE_CTL_IC_SCPD_MOD (1<<1)

MCACHE_CTL_IC_ECC_EN (1<<2)

MCACHE_CTL_IC_ECC_EXCP_EN (1<<3)

MCACHE_CTL_IC_RWTECC (1<<4)

MCACHE_CTL_IC_RWDECC (1<<5)

MCACHE_CTL_IC_PF_EN (1<<6)

MCACHE_CTL_IC_CANCEL_EN (1<<7)

MCACHE_CTL_DC_EN (1<<16)

MCACHE_CTL_DC_ECC_EN (1<<17)

MCACHE_CTL_DC_ECC_EXCP_EN (1<<18)

MCACHE_CTL_DC_RWTECC (1<<19)

MCACHE_CTL_DC_RWDECC (1<<20)

MTVT2_MTVT2EN (1<<0)

MTVT2_COMMON_CODE_ENTRY (((1ULL<<((__riscv_xlen)-2))-1)<<2)

MCFG_INFO_TEE (1<<0)

MCFG_INFO_ECC (1<<1)

MCFG_INFO_CLIC (1<<2)

`MCFG_INFO_PLIC` (1<<3)

`MCFG_INFO_FIO` (1<<4)

`MCFG_INFO_PPI` (1<<5)

`MCFG_INFO_NICE` (1<<6)

`MCFG_INFO_ILM` (1<<7)

`MCFG_INFO_DLM` (1<<8)

`MCFG_INFO_ICACHE` (1<<9)

`MCFG_INFO_DCACHE` (1<<10)

`MCFG_INFO_SMP` (1<<11)

`MCFG_INFO_DSP_N1` (1<<12)

`MCFG_INFO_DSP_N2` (1<<13)

`MCFG_INFO_DSP_N3` (1<<14)

`MCFG_INFO_IREGION_EXIST` (1<<16)

`MCFG_INFO_VP` (0x3<<17)

`MICFG_IC_SET` (0xF<<0)

`MICFG_IC_WAY` (0x7<<4)

`MICFG_IC_LSIZE` (0x7<<7)

`MICFG_IC_ECC` (0x1<<10)

`MICFG_ILM_SIZE` (0x1F<<16)

`MICFG_ILM_XONLY` (0x1<<21)

`MICFG_ILM_ECC` (0x1<<22)

MDCFG_DC_SET (0xF<<0)

MDCFG_DC_WAY (0x7<<4)

MDCFG_DC_LSIZE (0x7<<7)

MDCFG_DC_ECC (0x1<<10)

MDCFG_DLM_SIZE (0x1F<<16)

MDCFG_DLM_ECC (0x1<<21)

MIRGB_INFO_IRG_BASE_ADDR_BOFS (10)

MIRGB_INFO_IREGION_SIZE_BOFS (1)

MPPICFG_INFO_PPI_SIZE (0x1F<<1)

MPPICFG_INFO_PPI_BPA (((1ULL<<((__riscv_xlen)-10))-1)<<10)

MFIOCFG_INFO_FIO_SIZE (0x1F<<1)

MFIOCFG_INFO_FIO_BPA (((1ULL<<((__riscv_xlen)-10))-1)<<10)

MECC_LOCK_ECC_LOCK (0x1)

MECC_CODE_CODE (0x1FF)

MECC_CODE_RAMID (0x1F<<16)

MECC_CODE_SRAMID (0x1F<<24)

CCM_SUEN_SUEN (0x1<<0)

CCM_DATA_DATA (0x7<<0)

CCM_COMMAND_COMMAND (0x1F<<0)

IREGION_IINFO_OFS (0x0)

IREGION_DEBUG_OFS (0x10000)

`IREGION_ECLIC_OFS` (0x20000)

`IREGION_TIMER_OFS` (0x30000)

`IREGION_SMP_OFS` (0x40000)

`IREGION_IDU_OFS` (0x50000)

`IREGION_PL2_OFS` (0x60000)

`IREGION_DPREFETCH_OFS` (0x70000)

`IREGION_PLIC_OFS` (0x4000000)

`MSTACK_CTRL_MODE` (0x1<<2)

`MSTACK_CTRL_UDF_EN` (0x1<<1)

`MSTACK_CTRL_OVF_TRACK_EN` (0x1)

`SIP_SSIP` *MIP_SSIP* (page 114)

`SIP_STIP` *MIP_STIP* (page 114)

`PRV_U` 0

`PRV_S` 1

`PRV_H` 2

`PRV_M` 3

`VM_MBARE` 0

`VM_MBB` 1

`VM_MBBID` 2

`VM_SV32` 8

`VM_SV39` 9

`VM_SV48` 10

`SATP32_MODE` 0x80000000

`SATP32_ASID` 0x7FC00000

`SATP32_PPN` 0x003FFFFF

`SATP64_MODE` 0xF000000000000000

`SATP64_ASID` 0x0FFFF00000000000

`SATP64_PPN` 0x00000FFFFFFFFFFF

`SATP_MODE_OFF` 0

`SATP_MODE_SV32` 1

`SATP_MODE_SV39` 8

`SATP_MODE_SV48` 9

`SATP_MODE_SV57` 10

`SATP_MODE_SV64` 11

`IRQ_S_SOFT` 1

`IRQ_H_SOFT` 2

`IRQ_M_SOFT` 3

`IRQ_S_TIMER` 5

`IRQ_H_TIMER` 6

`IRQ_M_TIMER` 7

`IRQ_S_EXT` 9

`IRQ_H_EXT` 10

IRQ_M_EXT 11

IRQ_COP 12

IRQ_HOST 13

FRM_RNDMODE_RNE 0x0

FPU Round to Nearest, ties to Even.

FRM_RNDMODE_RTZ 0x1

FPU Round Towards Zero.

FRM_RNDMODE_RDN 0x2

FPU Round Down (towards -inf)

FRM_RNDMODE_RUP 0x3

FPU Round Up (towards +inf)

FRM_RNDMODE_RMM 0x4

FPU Round to nearest, ties to Max Magnitude.

FRM_RNDMODE_DYN 0x7

In instruction's rm, selects dynamic rounding mode.

In Rounding Mode register, Invalid

FFLAGS_AE_NX (1<<0)

FPU Inexact.

FFLAGS_AE_UF (1<<1)

FPU Underflow.

FFLAGS_AE_OF (1<<2)

FPU Overflow.

FFLAGS_AE_DZ (1<<3)

FPU Divide by Zero.

FFLAGS_AE_NV (1<<4)

FPU Invalid Operation.

FREG(idx) f##idx

Floating Point Register f0-f31, eg.

f0 -> *FREG(0)* (page 122)

PMP_R 0x01

PMP_W 0x02

PMP_X 0x04

PMP_A 0x18

PMP_A_TOR 0x08

PMP_A_NA4 0x10

PMP_A_NAPOT 0x18

PMP_L 0x80

PMP_SHIFT 2

PMP_COUNT 16

SPMP_R *PMP_R* (page 123)

SPMP_W *PMP_W* (page 123)

SPMP_X *PMP_X* (page 123)

SPMP_A *PMP_A* (page 123)

SPMP_A_TOR *PMP_A_TOR* (page 123)

SPMP_A_NA4 *PMP_A_NA4* (page 123)

SPMP_A_NAPOT *PMP_A_NAPOT* (page 123)

SPMP_U 0x40

SPMP_L *PMP_L* (page 123)

SPMP_SHIFT *PMP_SHIFT* (page 123)

SPMP_COUNT 16

`PTE_V` 0x001

`PTE_R` 0x002

`PTE_W` 0x004

`PTE_X` 0x008

`PTE_U` 0x010

`PTE_G` 0x020

`PTE_A` 0x040

`PTE_D` 0x080

`PTE_SOFT` 0x300

`PTE_PPN_SHIFT` 10

`PTE_TABLE(PTE)` (((PTE) & (*PTE_V* (page 124) | *PTE_R* (page 124) | *PTE_W* (page 124) | *PTE_X* (page 124))) == *PTE_V* (page 124))

`CAUSE_MISALIGNED_FETCH` 0x0

End of Doxygen Group NMSIS_Core_CSR_Registers.

`CAUSE_FAULT_FETCH` 0x1

`CAUSE_ILLEGAL_INSTRUCTION` 0x2

`CAUSE_BREAKPOINT` 0x3

`CAUSE_MISALIGNED_LOAD` 0x4

`CAUSE_FAULT_LOAD` 0x5

`CAUSE_MISALIGNED_STORE` 0x6

`CAUSE_FAULT_STORE` 0x7

`CAUSE_USER_ECALL` 0x8

`CAUSE_SUPERVISOR_ECALL` 0x9

CAUSE_HYPERVISOR_ECALL 0xa

CAUSE_MACHINE_ECALL 0xb

CAUSE_FETCH_PAGE_FAULT 0xc

CAUSE_LOAD_PAGE_FAULT 0xd

CAUSE_STORE_PAGE_FAULT 0xf

MISALIGNED_FETCH (1 << *CAUSE_MISALIGNED_FETCH* (page 124))

FAULT_FETCH (1 << *CAUSE_FAULT_FETCH* (page 124))

ILLEGAL_INSTRUCTION (1 << *CAUSE_ILLEGAL_INSTRUCTION* (page 124))

BREAKPOINT (1 << *CAUSE_BREAKPOINT* (page 124))

MISALIGNED_LOAD (1 << *CAUSE_MISALIGNED_LOAD* (page 124))

FAULT_LOAD (1 << *CAUSE_FAULT_LOAD* (page 124))

MISALIGNED_STORE (1 << *CAUSE_MISALIGNED_STORE* (page 124))

FAULT_STORE (1 << *CAUSE_FAULT_STORE* (page 124))

USER_ECALL (1 << *CAUSE_USER_ECALL* (page 124))

FETCH_PAGE_FAULT (1 << *CAUSE_FETCH_PAGE_FAULT* (page 125))

LOAD_PAGE_FAULT (1 << *CAUSE_LOAD_PAGE_FAULT* (page 125))

STORE_PAGE_FAULT (1 << *CAUSE_STORE_PAGE_FAULT* (page 125))

DCAUSE_FAULT_FETCH_PMP 0x1

DCAUSE_FAULT_FETCH_INST 0x2

DCAUSE_FAULT_LOAD_PMP 0x1

DCAUSE_FAULT_LOAD_INST 0x2

DCAUSE_FAULT_LOAD_NICE 0x3

DCAUSE_FAULT_STORE_PMP 0x1

DCAUSE_FAULT_STORE_INST 0x2

2.5.5 Register Define and Type Definitions

group **NMSIS_Core_Registers**

Type definitions and defines for core registers.

Defines

__RISCV_XLEN 32

Refer to the width of an integer register in bits(either 32 or 64)

Typedefs

typedef unsigned long **rv_csr_t**

Type of Control and Status Register(CSR), depends on the XLEN defined in RISC-V.

Core

group **NMSIS_Core_Base_Registers**

Type definitions and defines for base core registers.

Typedefs

typedef *CSR_MMISCCTRL_Type* (page 132) **CSR_MMISCCTL_Type**

union **CSR_MISA_Type**

#include <core_feature_base.h> Union type to access MISA CSR register.

Public Members

rv_csr_t (page 126) **a**

bit: 0 Atomic extension

rv_csr_t (page 126) **b**

bit: 1 Tentatively reserved for Bit-Manipulation extension

rv_csr_t (page 126) **c**

bit: 2 Compressed extension

rv_csr_t (page 126) **d**

bit: 3 Double-precision floating-point extension

Type used for csr data access.

rv_csr_t (page 126) **e**

bit: 4 RV32E base ISA

rv_csr_t (page 126) **f**

bit: 5 Single-precision floating-point extension

rv_csr_t (page 126) **g**

bit: 6 Additional standard extensions present

rv_csr_t (page 126) **h**

bit: 7 Hypervisor extension

rv_csr_t (page 126) **i**

bit: 8 RV32I/64I/128I base ISA

rv_csr_t (page 126) **j**

bit: 9 Tentatively reserved for Dynamically Translated Languages extension

rv_csr_t (page 126) **_reserved1**

bit: 10 Reserved

rv_csr_t (page 126) **l**

bit: 11 Tentatively reserved for Decimal Floating-Point extension

rv_csr_t (page 126) **m**

bit: 12 Integer Multiply/Divide extension

rv_csr_t (page 126) **n**

bit: 13 User-level interrupts supported

rv_csr_t (page 126) **_reserved2**

bit: 14 Reserved

rv_csr_t (page 126) **p**

bit: 15 Tentatively reserved for Packed-SIMD extension

rv_csr_t (page 126) **q**

bit: 16 Quad-precision floating-point extension

rv_csr_t (page 126) **_resreved3**

bit: 17 Reserved

rv_csr_t (page 126) **s**

bit: 18 Supervisor mode implemented

rv_csr_t (page 126) **t**

bit: 19 Tentatively reserved for Transactional Memory extension

rv_csr_t (page 126) **u**

bit: 20 User mode implemented

rv_csr_t (page 126) **v**

bit: 21 Tentatively reserved for Vector extension

rv_csr_t (page 126) **_reserved4**

bit: 22 Reserved

rv_csr_t (page 126) **x**

bit: 23 Non-standard extensions present

rv_csr_t (page 126) **_reserved5**

bit: 24..29 Reserved

rv_csr_t (page 126) **mxl**

bit: 30..31 Machine XLEN

struct *CSR_MISA_Type* (page 126)::[anonymous] **b**

Structure used for bit access.

union **CSR_MSTATUS_Type**

#include <core_feature_base.h> Union type to access MSTATUS CSR register.

Public Members

rv_csr_t (page 126) **_reserved0**

bit: 0 Reserved

rv_csr_t (page 126) **sie**

bit: 1 supervisor interrupt enable flag

rv_csr_t (page 126) **_reserved1**

bit: 2 Reserved

rv_csr_t (page 126) **mie**

bit: 3 Machine mode interrupt enable flag

rv_csr_t (page 126) **_reserved2**

bit: 4 Reserved

rv_csr_t (page 126) **spie**

bit: 3 Supervisor Privilede mode interrupt enable flag

rv_csr_t (page 126) **_reserved3**

bit: Reserved

rv_csr_t (page 126) **mpie**

bit: mirror of MIE flag

rv_csr_t (page 126) **_reserved4**

bit: Reserved

rv_csr_t (page 126) **mpp**

bit: mirror of Privilege Mode

rv_csr_t (page 126) **fs**

bit: FS status flag

rv_csr_t (page 126) **xs**

bit: XS status flag

rv_csr_t (page 126) **mprv**

bit: Machine mode PMP

rv_csr_t (page 126) **sum**

bit: Supervisor Mode load and store protection

rv_csr_t (page 126) **_reserved6**

bit: 19..30 Reserved

rv_csr_t (page 126) **sd**

bit: Dirty status for XS or FS

struct *CSR_MSTATUS_Type* (page 128)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MTVEC_Type**

#include <core_feature_base.h> Union type to access MTVEC CSR register.

Public Members

rv_csr_t (page 126) **mode**

bit: 0..5 interrupt mode control

rv_csr_t (page 126) **addr**

bit: 6..31 mtvec address

struct *CSR_MTVEC_Type* (page 130)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MCAUSE_Type**

#include <core_feature_base.h> Union type to access MCAUSE CSR register.

Public Members

rv_csr_t (page 126) **exccode**

bit: 11..0 exception or interrupt code

rv_csr_t (page 126) **_reserved0**

bit: 15..12 Reserved

rv_csr_t (page 126) **mpil**

bit: 23..16 Previous interrupt level

rv_csr_t (page 126) **_reserved1**

bit: 26..24 Reserved

rv_csr_t (page 126) **mpie**

bit: 27 Interrupt enable flag before enter interrupt

rv_csr_t (page 126) **mpp**

bit: 29..28 Privilede mode flag before enter interrupt

rv_csr_t (page 126) **minhv**

bit: 30 Machine interrupt vector table

rv_csr_t (page 126) **interrupt**

bit: 31 trap type.

0 means exception and 1 means interrupt

struct *CSR_MCAUSE_Type* (page 130)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MCOUNTINHIBIT_Type**

#include <core_feature_base.h> Union type to access MCOUNTINHIBIT CSR register.

Public Members

rv_csr_t (page 126) **cy**

bit: 0 1 means disable mcycle counter

rv_csr_t (page 126) **_reserved0**

bit: 1 Reserved

rv_csr_t (page 126) **ir**

bit: 2 1 means disable minstret counter

rv_csr_t (page 126) **_reserved1**

bit: 3..31 Reserved

struct *CSR_MCOUNTINHIBIT_Type* (page 131)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MSUBM_Type**

#include <core_feature_base.h> Union type to access MSUBM CSR register.

Public Members

rv_csr_t (page 126) **_reserved0**

bit: 0..5 Reserved

rv_csr_t (page 126) **typ**

bit: 6..7 current trap type

rv_csr_t (page 126) **ptyp**

bit: 8..9 previous trap type

rv_csr_t (page 126) **_reserved1**

bit: 10..31 Reserved

struct *CSR_MSUBM_Type* (page 131)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MDCAUSE_Type**

#include <core_feature_base.h> Union type to access MDCAUSE CSR register.

Public Members

rv_csr_t (page 126) **mdcause**

bit: 0..1 More detailed exception information as MCAUSE supplement

rv_csr_t (page 126) **_reserved0**

bit: 2..XLEN-1 Reserved

struct *CSR_MDCAUSE_Type* (page 132)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MMISCCTRL_Type**

#include <core_feature_base.h> Union type to access MMISC_CTRL CSR register.

Public Members

rv_csr_t (page 126) **_reserved0**

bit: 0..2 Reserved

rv_csr_t (page 126) **bpu**

bit: 3 dynamic prediction enable flag

rv_csr_t (page 126) **_reserved1**

bit: 4..5 Reserved

rv_csr_t (page 126) **misalign**

bit: 6 misaligned access support flag

rv_csr_t (page 126) **_reserved2**

bit: 7..8 Reserved

rv_csr_t (page 126) **nmi_cause**

bit: 9 mnvec control and nmi mcase exccode

rv_csr_t (page 126) **_reserved3**

bit: 10..31 Reserved

struct *CSR_MMISCCTRL_Type* (page 132)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MCACHECTL_Type**

#include <core_feature_base.h> Union type to access MCACHE_CTL CSR register.

Public Members

rv_csr_t (page 126) **ic_en**

I-Cache enable.

rv_csr_t (page 126) **ic_scpd_mod**

Scratchpad mode, 0: Scratchpad as ICache Data RAM, 1: Scratchpad as ILM SRAM.

rv_csr_t (page 126) **ic_ecc_en**

I-Cache ECC enable.

rv_csr_t (page 126) **ic_ecc_excp_en**

I-Cache 2bit ECC error exception enable.

rv_csr_t (page 126) **ic_rwtecc**

Control I-Cache Tag Ram ECC code injection.

rv_csr_t (page 126) **ic_rwdecc**

Control I-Cache Data Ram ECC code injection.

rv_csr_t (page 126) **_reserved0**

rv_csr_t (page 126) **dc_en**

DCache enable.

rv_csr_t (page 126) **dc_ecc_en**

D-Cache ECC enable.

rv_csr_t (page 126) **dc_ecc_excp_en**

D-Cache 2bit ECC error exception enable.

rv_csr_t (page 126) **dc_rwtecc**

Control D-Cache Tag Ram ECC code injection.

rv_csr_t (page 126) **dc_rwdecc**

Control D-Cache Data Ram ECC code injection.

rv_csr_t (page 126) **_reserved1**

struct *CSR_MCACHECTL_Type* (page 133)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MSAVESTATUS_Type**

#include <core_feature_base.h> Union type to access MSAVESTATUS CSR register.

Public Members

rv_csr_t (page 126) **mpie1**

bit: 0 interrupt enable flag of fisrt level NMI/exception nestting

rv_csr_t (page 126) **mpp1**

bit: 1..2 privilede mode of fisrt level NMI/exception nestting

rv_csr_t (page 126) **_reserved0**

bit: 3..5 Reserved

rv_csr_t (page 126) **ptyp1**

bit: 6..7 NMI/exception type of before first nestting

rv_csr_t (page 126) **mpie2**

bit: 8 interrupt enable flag of second level NMI/exception nestting

rv_csr_t (page 126) **mpp2**

bit: 9..10 privilede mode of second level NMI/exception nestting

rv_csr_t (page 126) **_reserved1**

bit: 11..13 Reserved

rv_csr_t (page 126) **ptyp2**

bit: 14..15 NMI/exception type of before second nestting

rv_csr_t (page 126) **_reserved2**

bit: 16..31 Reserved

struct *CSR_MSAVESTATUS_Type* (page 134)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **w**

Type used for csr data access.

union **CSR_MILMCTL_Type**

#include <core_feature_base.h> Union type to access MILM_CTL CSR register.

Public Members

rv_csr_t (page 126) **ilm_en**

ILM enable.

rv_csr_t (page 126) **ilm_ecc_en**

ILM ECC eanble.

rv_csr_t (page 126) **ilm_ecc_excp_en**

ILM ECC exception enable.

rv_csr_t (page 126) **ilm_rwecc**

Control mecc_code write to ilm, simulate error injection.

rv_csr_t (page 126) **_reserved0**

Reserved.

rv_csr_t (page 126) **ilm_bpa**

ILM base address.

struct *CSR_MILMCTL_Type* (page 135)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MDLMCTL_Type**

#include <core_feature_base.h> Union type to access MDLM_CTL CSR register.

Public Members

rv_csr_t (page 126) **dlm_en**

DLM enable.

rv_csr_t (page 126) **dlm_ecc_en**

DLM ECC eanble.

rv_csr_t (page 126) **dlm_ecc_excp_en**

DLM ECC exception enable.

rv_csr_t (page 126) **dlm_rwecc**

Control mecc_code write to dlm, simulate error injection.

rv_csr_t (page 126) **_reserved0**

Reserved.

rv_csr_t (page 126) **dlm_bpa**

DLM base address.

struct *CSR_MDLMCTL_Type* (page 136)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MCFGINFO_Type**

#include <core_feature_base.h> Union type to access MCFG_INFO CSR register.

Public Members

rv_csr_t (page 126) **tee**

TEE present.

rv_csr_t (page 126) **ecc**

ECC present.

rv_csr_t (page 126) **clic**

CLIC present.

rv_csr_t (page 126) **plic**

PLIC present.

rv_csr_t (page 126) **fio**

FIO present.

rv_csr_t (page 126) **ppi**

PPI present.

rv_csr_t (page 126) **nice**

NICE present.

rv_csr_t (page 126) **ilm**

ILM present.

rv_csr_t (page 126) **dlm**

DLM present.

rv_csr_t (page 126) **icache**

ICache present.

rv_csr_t (page 126) **dcache**

DCache present.

rv_csr_t (page 126) **_reserved0**

struct *CSR_MCFGINFO_Type* (page 136)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MICFGINFO_Type**

#include <core_feature_base.h> Union type to access MICFG_INFO CSR register.

Public Members

rv_csr_t (page 126) **set**

I-Cache sets per way.

rv_csr_t (page 126) **way**

I-Cache way.

rv_csr_t (page 126) **lsize**

I-Cache line size.

rv_csr_t (page 126) **cache_ecc**

I-Cache ECC present.

rv_csr_t (page 126) **_reserved0**

rv_csr_t (page 126) **lm_size**

ILM size, need to be 2^n size.

rv_csr_t (page 126) **lm_xonly**

ILM Execute only permission.

rv_csr_t (page 126) **lm_ecc**

ILM ECC present.

rv_csr_t (page 126) **_reserved1**

struct *CSR_MICFGINFO_Type* (page 137)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MDCFGINFO_Type**

#include <core_feature_base.h> Union type to access MDCFG_INFO CSR register.

Public Members

rv_csr_t (page 126) **set**

D-Cache sets per way.

rv_csr_t (page 126) **way**

D-Cache way.

rv_csr_t (page 126) **lsize**

D-Cache line size.

rv_csr_t (page 126) **cache_ecc**

D-Cache ECC present.

rv_csr_t (page 126) **_reserved0**

rv_csr_t (page 126) **lm_size**

DLM size, need to be 2^n size.

rv_csr_t (page 126) **lm_xonly**

DLM Execute only permission.

rv_csr_t (page 126) **lm_ecc**

DLM ECC present.

rv_csr_t (page 126) **_reserved1**

struct *CSR_MDCFGINFO_Type* (page 138)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MPPICFGINFO_Type**

#include <core_feature_base.h> Union type to access MPPICFG_INFO CSR register.

Public Members

rv_csr_t (page 126) **_reserved0**

Reserved.

rv_csr_t (page 126) **ppi_size**

PPI size, need to be 2^n size.

rv_csr_t (page 126) **_reserved1**

Reserved.

rv_csr_t (page 126) **ppi_bpa**

PPI base address.

struct *CSR_MPPICFGINFO_Type* (page 139)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MFIOCFGINFO_Type**

#include <core_feature_base.h> Union type to access MFIOCFG_INFO CSR register.

Public Members

rv_csr_t (page 126) **_reserved0**

Reserved.

rv_csr_t (page 126) **fio_size**

FIO size, need to be 2^n size.

rv_csr_t (page 126) **_reserved1**

Reserved.

rv_csr_t (page 126) **fio_bpa**

FIO base address.

struct *CSR_MFIOCFGINFO_Type* (page 140)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MECCLOCK_Type**

#include <core_feature_base.h> Union type to access MECC_LOCK CSR register.

Public Members

rv_csr_t (page 126) **ecc_lock**

RW permission, ECC Lock configure.

rv_csr_t (page 126) **_reserved0**

Reserved.

struct *CSR_MECCLOCK_Type* (page 140)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

union **CSR_MECCCODE_Type**

#include <core_feature_base.h> Union type to access MECC_CODE CSR register.

Public Members

rv_csr_t (page 126) **code**

Used to inject ECC check code.

rv_csr_t (page 126) **_reserved0**

Reserved.

rv_csr_t (page 126) **ramid**

Indicate 2bit ECC error, software can clear these bits.

rv_csr_t (page 126) **_reserved1**

Reserved.

rv_csr_t (page 126) **sramid**

Indicate 1bit ECC error, software can clear these bits.

rv_csr_t (page 126) **_reserved2**

Reserved.

struct *CSR_MECCCODE_Type* (page 140)::[anonymous] **b**

Structure used for bit access.

rv_csr_t (page 126) **d**

Type used for csr data access.

ECLIC

group **NMSIS_Core_ECLIC_Registers**

Type definitions and defines for eclic registers.

Defines

CLIC_CLICCFG_NLBIT_Pos 1U

CLIC CLICCFG: NLBIT Position.

CLIC_CLICCFG_NLBIT_Msk (0xFUL << *CLIC_CLICCFG_NLBIT_Pos* (page 141))

CLIC CLICCFG: NLBIT Mask.

CLIC_CLICINFO_CTLBIT_Pos 21U

CLIC INTINFO: __ECLIC_GetInfoCtlbits() Position.

CLIC_CLICINFO_CTLBIT_Msk (0xFUL << *CLIC_CLICINFO_CTLBIT_Pos* (page 141))

CLIC INTINFO: __ECLIC_GetInfoCtlbits() Mask.

CLIC_CLICINFO_VER_Pos 13U

CLIC CLICINFO: VERSION Position.

CLIC_CLICINFO_VER_Msk (0xFFUL << *CLIC_CLICCFG_NLBIT_Pos* (page 141))

CLIC CLICINFO: VERSION Mask.

CLIC_CLICINFO_NUM_Pos 0U

CLIC CLICINFO: NUM Position.

CLIC_CLICINFO_NUM_Msk (0xFFFUL << *CLIC_CLICINFO_NUM_Pos* (page 142))

CLIC CLICINFO: NUM Mask.

CLIC_INTIP_IP_Pos 0U

CLIC INTIP: IP Position.

CLIC_INTIP_IP_Msk (0x1UL << *CLIC_INTIP_IP_Pos* (page 142))

CLIC INTIP: IP Mask.

CLIC_INTIE_IE_Pos 0U

CLIC INTIE: IE Position.

CLIC_INTIE_IE_Msk (0x1UL << *CLIC_INTIE_IE_Pos* (page 142))

CLIC INTIE: IE Mask.

CLIC_INTATTR_MODE_Pos 6U

CLIC INTATTA: Mode Position.

CLIC_INTATTR_MODE_Msk (0x3U << *CLIC_INTATTR_MODE_Pos* (page 142))

CLIC INTATTA: Mode Mask.

CLIC_INTATTR_TRIG_Pos 1U

CLIC INTATTR: TRIG Position.

CLIC_INTATTR_TRIG_Msk (0x3UL << *CLIC_INTATTR_TRIG_Pos* (page 142))

CLIC INTATTR: TRIG Mask.

CLIC_INTATTR_SHV_Pos 0U

CLIC INTATTR: SHV Position.

CLIC_INTATTR_SHV_Msk (0x1UL << *CLIC_INTATTR_SHV_Pos* (page 142))

CLIC INTATTR: SHV Mask.

ECLIC_MAX_NLBITS 8U

Max nlbit of the CLICINTCTLBITS.

ECLIC_MODE_MTVEC_Msk 3U
ECLIC Mode mask for MTVT CSR Register.

ECLIC_NON_VECTOR_INTERRUPT 0x0
Non-Vector Interrupt Mode of ECLIC.

ECLIC_VECTOR_INTERRUPT 0x1
Vector Interrupt Mode of ECLIC.

ECLIC_BASE __ECLIC_BASEADDR
ECLIC Base Address.

ECLIC ((*CLIC_Type* (page 144) *) *ECLIC_BASE* (page 143))
CLIC configuration struct.

Enums

enum **ECLIC_TRIGGER**
ECLIC Trigger Enum for different Trigger Type.

Values:

enumerator **ECLIC_LEVEL_TRIGGER**
Level Triggerred, trig[0] = 0.

enumerator **ECLIC_POSTIVE_EDGE_TRIGGER**
Postive/Rising Edge Triggered, trig[0] = 1, trig[1] = 0.

enumerator **ECLIC_NEGTIVE_EDGE_TRIGGER**
Negtive/Falling Edge Triggered, trig[0] = 1, trig[1] = 1.

enumerator **ECLIC_MAX_TRIGGER**
MAX Supported Trigger Mode.

union **CLICCFG_Type**
#include <core_feature_eclic.h> Union type to access CLICFG configure register.

Public Members

__IM uint8_t _reserved0

__IOM uint8_t nlbits
bit: 1..4 specified the bit-width of level and priority in the register clicintctl[i]

__IM uint8_t nmbits

bit: 5..6 ties to 1 if supervisor-level interrupt supported, or else it's reserved

__IM uint8_t _reserved1

struct *CLICCFG_Type* (page 143)::[anonymous] **b**

Structure used for bit access.

uint8_t **w**

Type used for byte access.

union **CLICINFO_Type**

#include <core_feature_eclic.h> Union type to access CLICINFO information register.

Public Members

__IM uint32_t numint

bit: 0..12 number of maximum interrupt inputs supported

__IM uint32_t version

bit: 13..20 20:17 for architecture version,16:13 for implementation version

__IM uint32_t intctlbits

bit: 21..24 specifies how many hardware bits are actually implemented in the clicintctl registers

__IM uint32_t _reserved0

bit: 25..31 Reserved

struct *CLICINFO_Type* (page 144)::[anonymous] **b**

Structure used for bit access.

__IM uint32_t w

Type used for word access.

struct **CLIC_CTRL_Type**

#include <core_feature_eclic.h> Access to the machine mode register structure of INTIP, INTIE, INTATTR, INTCTL.

struct **CLIC_Type**

#include <core_feature_eclic.h> Access to the structure of ECLIC Memory Map, which is compatible with TEE.

SysTimer

group `NMSIS_Core_SysTimer_Registers`

Type definitions and defines for system timer registers.

Defines

`SysTimer_MTIMECTL_TIMESTOP_Pos` 0U
SysTick Timer MTIMECTL: TIMESTOP bit Position.

`SysTimer_MTIMECTL_TIMESTOP_Msk` (1UL << *SysTimer_MTIMECTL_TIMESTOP_Pos* (page 145))
SysTick Timer MTIMECTL: TIMESTOP Mask.

`SysTimer_MTIMECTL_CMPCLREN_Pos` 1U
SysTick Timer MTIMECTL: CMPCLREN bit Position.

`SysTimer_MTIMECTL_CMPCLREN_Msk` (1UL << *SysTimer_MTIMECTL_CMPCLREN_Pos* (page 145))
SysTick Timer MTIMECTL: CMPCLREN Mask.

`SysTimer_MTIMECTL_CLKSRC_Pos` 2U
SysTick Timer MTIMECTL: CLKSRC bit Position.

`SysTimer_MTIMECTL_CLKSRC_Msk` (1UL << *SysTimer_MTIMECTL_CLKSRC_Pos* (page 145))
SysTick Timer MTIMECTL: CLKSRC Mask.

`SysTimer_MSIP_MSIP_Pos` 0U
SysTick Timer MSIP: MSIP bit Position.

`SysTimer_MSIP_MSIP_Msk` (1UL << *SysTimer_MSIP_MSIP_Pos* (page 145))
SysTick Timer MSIP: MSIP Mask.

`SysTimer_MTIMER_Msk` (0xFFFFFFFFFFFFFFFFULL)
SysTick Timer MTIMER value Mask.

`SysTimer_MTIMERCMP_Msk` (0xFFFFFFFFFFFFFFFFULL)
SysTick Timer MTIMERCMP value Mask.

`SysTimer_MTIMECTL_Msk` (0xFFFFFFFFUL)
SysTick Timer MTIMECTL/MSTOP value Mask.

`SysTimer_MSIP_Msk` (0xFFFFFFFFUL)
SysTick Timer MSIP value Mask.

`SysTimer_MSFTRST_Msk` (0xFFFFFFFFUL)
SysTick Timer MSFTRST value Mask.

SysTimer_MSFRST_KEY (0x80000A5FUL)

SysTick Timer Software Reset Request Key.

SysTimer_CLINT_MSIP_OFS (0x1000UL)

Software interrupt register offset of clint mode in SysTick Timer.

SysTimer_CLINT_MTIMECMP_OFS (0x5000UL)

MTIMECMP register offset of clint mode in SysTick Timer.

SysTimer_CLINT_MTIME_OFS (0xCFF8UL)

MTIME register offset of clint mode in SysTick Timer.

SysTimer_BASE __SYSTIMER_BASEADDR

SysTick Base Address.

SysTimer ((*SysTimer_Type* (page 146) *) *SysTimer_BASE* (page 146))

SysTick configuration struct.

SysTimer_CLINT_MSIP_BASE(hartid) (unsigned long)((*SysTimer_BASE* (page 146)) + (*SysTimer_CLINT_MSIP_OFS* (page 146)) + ((hartid) << 2))

SysTimer_CLINT_MTIMECMP_BASE(hartid) (unsigned long)((*SysTimer_BASE* (page 146)) + (*SysTimer_CLINT_MTIMECMP_OFS* (page 146)) + ((hartid) << 3))

SysTimer_CLINT_MTIME_BASE (unsigned long)((*SysTimer_BASE* (page 146)) + (*SysTimer_CLINT_MTIME_OFS* (page 146)))

struct **SysTimer_Type**

#include <core_feature_timer.h> Structure type to access the System Timer (SysTimer).

Structure definition to access the system timer(SysTimer).

Remark

- MSFTRST register is introduced in Nuclei N Core version 1.3(*__NUCLEI_N_REV* (page 77) >= 0x0103)
- MSTOP register is renamed to MTIMECTL register in Nuclei N Core version 1.4(*__NUCLEI_N_REV* (page 77) >= 0x0104)
- CMPCLREN and CLKSRC bit in MTIMECTL register is introduced in Nuclei N Core version 1.4(*__NUCLEI_N_REV* (page 77) >= 0x0104)

2.5.6 CPU Intrinsic Functions

enum **WFI_SleepMode**

Values:

enumerator **WFI_SHALLOW_SLEEP**

enumerator **WFI_DEEP_SLEEP**

`__STATIC_FORCEINLINE void __NOP (void)`

`__STATIC_FORCEINLINE void __WFI (void)`

`__STATIC_FORCEINLINE void __WFE (void)`

`__STATIC_FORCEINLINE void __EBREAK (void)`

`__STATIC_FORCEINLINE void __ECALL (void)`

`__STATIC_FORCEINLINE void __set_wfi_sleepmode (WFI_SleepMode_Type mode)`

`__STATIC_FORCEINLINE void __TXEVT (void)`

`__STATIC_FORCEINLINE void __enable_mcycle_counter (void)`

`__STATIC_FORCEINLINE void __disable_mcycle_counter (void)`

`__STATIC_FORCEINLINE void __enable_minstret_counter (void)`

`__STATIC_FORCEINLINE void __disable_minstret_counter (void)`

`__STATIC_FORCEINLINE void __enable_mhpm_counter (unsigned long idx)`

`__STATIC_FORCEINLINE void __disable_mhpm_counter (unsigned long idx)`

`__STATIC_FORCEINLINE void __enable_mhpm_counters (unsigned long mask)`

`__STATIC_FORCEINLINE void __disable_mhpm_counters (unsigned long mask)`

`__STATIC_FORCEINLINE void __enable_all_counter (void)`

`__STATIC_FORCEINLINE void __disable_all_counter (void)`

__STATIC_FORCEINLINE void __set_hpm_event (unsigned long idx, unsigned long event)

__STATIC_FORCEINLINE unsigned long __get_hpm_event (unsigned long idx)

__STATIC_FORCEINLINE void __set_hpm_counter (unsigned long idx, uint64_t value)

__STATIC_FORCEINLINE unsigned long __get_hpm_counter (unsigned long idx)

__STATIC_FORCEINLINE void __set_medeleg (unsigned long mask)

__STATIC_FORCEINLINE void __FENCE_I (void)

__STATIC_FORCEINLINE uint8_t __LB (volatile void *addr)

__STATIC_FORCEINLINE uint16_t __LH (volatile void *addr)

__STATIC_FORCEINLINE uint32_t __LW (volatile void *addr)

__STATIC_FORCEINLINE void __SB (volatile void *addr, uint8_t val)

__STATIC_FORCEINLINE void __SH (volatile void *addr, uint16_t val)

__STATIC_FORCEINLINE void __SW (volatile void *addr, uint32_t val)

__STATIC_FORCEINLINE uint32_t __CAS_W (volatile uint32_t *addr, uint32_t oldval, uint32_t newval)

__STATIC_FORCEINLINE uint32_t __AMOSWAP_W (volatile uint32_t *addr, uint32_t newval)

__STATIC_FORCEINLINE int32_t __AMOADD_W (volatile int32_t *addr, int32_t value)

__STATIC_FORCEINLINE int32_t __AMOAND_W (volatile int32_t *addr, int32_t value)

__STATIC_FORCEINLINE int32_t __AMOOR_W (volatile int32_t *addr, int32_t value)

__STATIC_FORCEINLINE int32_t __AMOXOR_W (volatile int32_t *addr, int32_t value)

__STATIC_FORCEINLINE uint32_t __AMOMAXU_W (volatile uint32_t *addr, uint32_t value)

__STATIC_FORCEINLINE int32_t __AMOMAX_W (volatile int32_t *addr, int32_t value)

__STATIC_FORCEINLINE uint32_t __AMOMINU_W (volatile uint32_t *addr, uint32_t value)

__STATIC_FORCEINLINE int32_t __AMOMIN_W (volatile int32_t *addr, int32_t value)

__FENCE(p, s) *__ASM* (page 78) volatile ("fence " #p "," #s : : : "memory")

__RWMB() __FENCE(iorw,iorw)

__RMB() __FENCE(ir,ir)

__WMB() __FENCE(ow,ow)

__SMP_RWMB() __FENCE(rw,rw)

__SMP_RMB() __FENCE(r,r)

__SMP_WMB() __FENCE(w,w)

__CPU_RELAX() *__ASM* (page 78) volatile ("" : : : "memory")

group **NMSIS_Core_CPU_Intrinsic**

Functions that generate RISC-V CPU instructions.

The following functions generate specified RISC-V instructions that cannot be directly accessed by compiler.

Defines

__FENCE(p, s) *__ASM* (page 78) volatile ("fence " #p "," #s : : : "memory")

Execute fence instruction, p -> pred, s -> succ.

the FENCE instruction ensures that all memory accesses from instructions preceding the fence in program order (the `predecessor set`) appear earlier in the global memory order than memory accesses from instructions appearing after the fence in program order (the `successor set`). For details, please refer to The RISC-V Instruction Set Manual

Parameters

- **p** – predecessor set, such as iorw, rw, r, w
- **s** – successor set, such as iorw, rw, r, w

__RWMB() __FENCE(iorw,iorw)

Read & Write Memory barrier.

__RMB() __FENCE(ir,ir)

Read Memory barrier.

__WMB() __FENCE(ow,ow)

Write Memory barrier.

__SMP_RWMB() __FENCE(rw,rw)

SMP Read & Write Memory barrier.

__SMP_RMB() __FENCE(r,r)

SMP Read Memory barrier.

__SMP_WMB() __FENCE(w,w)

SMP Write Memory barrier.

__CPU_RELAX() *__ASM* (page 78) volatile ("" : : : "memory")

CPU relax for busy loop.

Enums

enum **WFI_SleepMode**

WFI Sleep Mode enumeration.

Values:

enumerator **WFI_SHALLOW_SLEEP**

Shallow sleep mode, the core_clk will poweroff.

enumerator **WFI_DEEP_SLEEP**

Deep sleep mode, the core_clk and core_ano_clk will poweroff.

Functions

__STATIC_FORCEINLINE void __NOP (void)

NOP Instruction.

No Operation does nothing. This instruction can be used for code alignment purposes.

__STATIC_FORCEINLINE void __WFI (void)

Wait For Interrupt.

Wait For Interrupt is is executed using CSR_WFE.WFE=0 and WFI instruction. It will suspends execution until interrupt, NMI or Debug happened. When Core is waked up by interrupt, if

a. mstatus.MIE == 1(interrupt enabled), Core will enter ISR code
b. mstatus.MIE == 0(interrupt disabled), Core will resume previous execution

__STATIC_FORCEINLINE void __WFE (void)

Wait For Event.

Wait For Event is executed using CSR_WFE.WFE=1 and WFI instruction. It will suspends execution until event, NMI or Debug happened. When Core is waked up, Core will resume previous execution

__STATIC_FORCEINLINE void __EBREAK (void)

Breakpoint Instruction.

Causes the processor to enter Debug state. Debug tools can use this to investigate system state when the instruction at a particular address is reached.

__STATIC_FORCEINLINE void __ECALL (void)

Environment Call Instruction.

The ECALL instruction is used to make a service request to the execution environment.

__STATIC_FORCEINLINE void __set_wfi_sleepmode (WFI_SleepMode_Type mode)

Set Sleep mode of WFI.

Set the SLEEPVALUE CSR register to control the WFI Sleep mode.

Parameters **mode** – **[in]** The sleep mode to be set

`__STATIC_FORCEINLINE void __TXEVT (void)`

Send TX Event.

Set the CSR TXEVT to control send a TX Event. The Core will output signal tx_evt as output event signal.

`__STATIC_FORCEINLINE void __enable_mcycle_counter (void)`

Enable MCYCLE counter.

Clear the CY bit of MCOUNTINHIBIT to 0 to enable MCYCLE Counter

`__STATIC_FORCEINLINE void __disable_mcycle_counter (void)`

Disable MCYCLE counter.

Set the CY bit of MCOUNTINHIBIT to 1 to disable MCYCLE Counter

`__STATIC_FORCEINLINE void __enable_minstret_counter (void)`

Enable MINSTRET counter.

Clear the IR bit of MCOUNTINHIBIT to 0 to enable MINSTRET Counter

`__STATIC_FORCEINLINE void __disable_minstret_counter (void)`

Disable MINSTRET counter.

Set the IR bit of MCOUNTINHIBIT to 1 to disable MINSTRET Counter

`__STATIC_FORCEINLINE void __enable_mhpm_counter (unsigned long idx)`

Enable selected hardware performance monitor counter.

enable selected hardware performance monitor counter mhpmcounterx.

Parameters `idx` – **[in]** the index of the hardware performance monitor counter

`__STATIC_FORCEINLINE void __disable_mhpm_counter (unsigned long idx)`

Disable selected hardware performance monitor counter.

Disable selected hardware performance monitor counter mhpmcounterx.

Parameters `idx` – **[in]** the index of the hardware performance monitor counter

`__STATIC_FORCEINLINE void __enable_mhpm_counters (unsigned long mask)`

Enable hardware performance counters with mask.

enable mhpmcounterx with mask, only the masked ones will be enabled. mhpmcounter3-mhpmcount31 are for high performance monitor counters.

Parameters `mask` – **[in]** mask of selected hardware performance monitor counters

`__STATIC_FORCEINLINE void __disable_mhpm_counters (unsigned long mask)`

Disable hardware performance counters with mask.

Disable mhpmcounterx with mask, only the masked ones will be disabled. mhpmcounter3-mhpmcount31 are for high performance monitor counters.

Parameters `mask` – **[in]** mask of selected hardware performance monitor counters

`__STATIC_FORCEINLINE void __enable_all_counter (void)`

Enable all MCYCLE & MINSTRET & MHPMCOUNTER counter.

Clear all to zero to enable all counters, such as cycle, instret, high performance monitor counters

`__STATIC_FORCEINLINE void __disable_all_counter (void)`

Disable all MCYCLE & MINSTRET & MHPMCOUNTER counter.

Set all to one to disable all counters, such as cycle, instret, high performance monitor counters

`__STATIC_FORCEINLINE void __set_hpm_event (unsigned long idx, unsigned long event)`

Set event for selected high performance monitor event.

Set event for high performance monitor event register

Parameters

- `idx` – **[in]** HPMEVENTx CSR index(3-31)
- `event` – **[in]** HPMEVENTx Register value to set

`__STATIC_FORCEINLINE unsigned long __get_hpm_event (unsigned long idx)`

Get event for selected high performance monitor event.

Get high performance monitor event register value

Parameters

- `idx` – **[in]** HPMEVENTx CSR index(3-31)
- `event` – **[in]** HPMEVENTx Register value to set

Returns HPMEVENTx Register value

`__STATIC_FORCEINLINE void __set_hpm_counter (unsigned long idx, uint64_t value)`

Set value for selected high performance monitor counter.

Set value for high performance monitor couner register

Parameters

- `idx` – **[in]** HPMCOUNTERx CSR index(3-31)
- `value` – **[in]** HPMCOUNTERx Register value to set

`__STATIC_FORCEINLINE unsigned long __get_hpm_counter (unsigned long idx)`

Get value of selected high performance monitor couner.

Get high performance monitor counter register value

Parameters

- **`idx`** – **[in]** HPMCOUNTERx CSR index(3-31)
- **`event`** – **[in]** HPMCOUNTERx Register value to set

Returns HPMCOUNTERx Register value

`__STATIC_FORCEINLINE void __set_medeleg (unsigned long mask)`

Set exceptions delegation to S mode.

Set certain exceptions of supervisor mode or user mode delegated from machined mode to supervisor mode.

Remark

Exception should trigger in supervisor mode or user mode.

`__STATIC_FORCEINLINE void __FENCE_I (void)`

Fence.i Instruction.

The FENCE.I instruction is used to synchronize the instruction and data streams.

`__STATIC_FORCEINLINE uint8_t __LB (volatile void *addr)`

Load 8bit value from address (8 bit)

Load 8 bit value.

Parameters **`addr`** – **[in]** Address pointer to data

Returns value of type uint8_t at (*addr)

`__STATIC_FORCEINLINE uint16_t __LH (volatile void *addr)`

Load 16bit value from address (16 bit)

Load 16 bit value.

Parameters **`addr`** – **[in]** Address pointer to data

Returns value of type uint16_t at (*addr)

`__STATIC_FORCEINLINE uint32_t __LW (volatile void *addr)`

Load 32bit value from address (32 bit)

Load 32 bit value.

Parameters **`addr`** – **[in]** Address pointer to data

Returns value of type uint32_t at (*addr)

`__STATIC_FORCEINLINE void __SB (volatile void *addr, uint8_t val)`

Write 8bit value to address (8 bit)

Write 8 bit value.

Parameters

- `addr` – **[in]** Address pointer to data
- `val` – **[in]** Value to set

`__STATIC_FORCEINLINE void __SH (volatile void *addr, uint16_t val)`

Write 16bit value to address (16 bit)

Write 16 bit value.

Parameters

- `addr` – **[in]** Address pointer to data
- `val` – **[in]** Value to set

`__STATIC_FORCEINLINE void __SW (volatile void *addr, uint32_t val)`

Write 32bit value to address (32 bit)

Write 32 bit value.

Parameters

- `addr` – **[in]** Address pointer to data
- `val` – **[in]** Value to set

`__STATIC_FORCEINLINE uint32_t __CAS_W (volatile uint32_t *addr, uint32_t oldval, uint32_t newval)`

Compare and Swap 32bit value using LR and SC.

Compare old value with memory, if identical, store new value in memory. Return the initial value in memory. Success is indicated by comparing return value with OLD. memory address, return 0 if successful, otherwise return !0

Parameters

- `addr` – **[in]** Address pointer to data, address need to be 4byte aligned
- `oldval` – **[in]** Old value of the data in address
- `newval` – **[in]** New value to be stored into the address

Returns return the initial value in memory

`__STATIC_FORCEINLINE uint32_t __AMOSWAP_W (volatile uint32_t *addr, uint32_t newval)`

Atomic Swap 32bit value into memory.

Atomically swap new 32bit value into memory using amoswap.d.

Parameters

- `addr` – **[in]** Address pointer to data, address need to be 4byte aligned
- `newval` – **[in]** New value to be stored into the address

Returns return the original value in memory

`__STATIC_FORCEINLINE int32_t __AMOADD_W (volatile int32_t *addr, int32_t value)`

Atomic Add with 32bit value.

Atomically ADD 32bit value with value in memory using amoadd.d.

Parameters

- `addr` – **[in]** Address pointer to data, address need to be 4byte aligned
- `value` – **[in]** value to be ADDed

Returns return memory value + add value

`__STATIC_FORCEINLINE int32_t __AMOAND_W (volatile int32_t *addr, int32_t value)`

Atomic And with 32bit value.

Atomically AND 32bit value with value in memory using amoand.d.

Parameters

- `addr` – **[in]** Address pointer to data, address need to be 4byte aligned
- `value` – **[in]** value to be ANDed

Returns return memory value & and value

`__STATIC_FORCEINLINE int32_t __AMOOR_W (volatile int32_t *addr, int32_t value)`

Atomic OR with 32bit value.

Atomically OR 32bit value with value in memory using amoor.d.

Parameters

- `addr` – **[in]** Address pointer to data, address need to be 4byte aligned
- `value` – **[in]** value to be ORed

Returns return memory value | and value

`__STATIC_FORCEINLINE int32_t __AMOXOR_W (volatile int32_t *addr, int32_t value)`

Atomic XOR with 32bit value.

Atomically XOR 32bit value with value in memory using amoxor.d.

Parameters

- `addr` – **[in]** Address pointer to data, address need to be 4byte aligned
- `value` – **[in]** value to be XORed

Returns return memory value ^ and value

`__STATIC_FORCEINLINE uint32_t __AMOMAXU_W (volatile uint32_t *addr, uint32_t value)`

Atomic unsigned MAX with 32bit value.

Atomically unsigned max compare 32bit value with value in memory using amomaxu.d.

Parameters

- `addr` – **[in]** Address pointer to data, address need to be 4byte aligned

- **value** – **[in]** value to be compared

Returns return the bigger value

`__STATIC_FORCEINLINE int32_t __AMOMAX_W (volatile int32_t *addr, int32_t value)`

Atomic signed MAX with 32bit value.

Atomically signed max compare 32bit value with value in memory using amomax.d.

Parameters

- **addr** – **[in]** Address pointer to data, address need to be 4byte aligned
- **value** – **[in]** value to be compared

Returns the bigger value

`__STATIC_FORCEINLINE uint32_t __AMOMINU_W (volatile uint32_t *addr, uint32_t value)`

Atomic unsigned MIN with 32bit value.

Atomically unsigned min compare 32bit value with value in memory using amominu.d.

Parameters

- **addr** – **[in]** Address pointer to data, address need to be 4byte aligned
- **value** – **[in]** value to be compared

Returns the smaller value

`__STATIC_FORCEINLINE int32_t __AMOMIN_W (volatile int32_t *addr, int32_t value)`

Atomic signed MIN with 32bit value.

Atomically signed min compare 32bit value with value in memory using amomin.d.

Parameters

- **addr** – **[in]** Address pointer to data, address need to be 4byte aligned
- **value** – **[in]** value to be compared

Returns the smaller value

2.5.7 Intrinsic Functions for SIMD Instructions

Click Nuclei DSP Feature[15] to learn about Core DSP in Nuclei ISA Spec.

SIMD Data Processing Instructions

SIMD 16-bit Add/Subtract Instructions

`__STATIC_FORCEINLINE unsigned long __RV_ADD16 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_CRAS16 (unsigned long a, unsigned long b)`

[15] https://doc.nucleisys.com/nuclei_spec/isa/dsp.html

__STATIC_FORCEINLINE unsigned long __RV_CRSA16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KADD16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KCRAS16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KCRSA16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KSTAS16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KSTSA16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KSUB16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_RADD16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_RCRAS16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_RCRSA16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_RSTAS16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_RSTSA16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_RSUB16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_STAS16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_STSA16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_SUB16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UKADD16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UKCRAS16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UKCRSA16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UKSTAS16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UKSTSA16 (unsigned long a, unsigned long b)

`__STATIC_FORCEINLINE unsigned long __RV_UKSUB16 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_URADD16 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_URCRAS16 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_URCRSA16 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_URSTAS16 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_URSTSA16 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_URSUB16 (unsigned long a, unsigned long b)`

group `NMSIS_Core_DSP_Intrinsic_SIMD_16B_ADDSUB`

SIMD 16-bit Add/Subtract Instructions.

Based on the combination of the types of the two 16-bit arithmetic operations, the SIMD 16-bit add/subtract instructions can be classified into 6 main categories: Addition (two 16-bit addition), Subtraction (two 16-bit subtraction), Crossed Add & Sub (one addition and one subtraction), and Crossed Sub & Add (one subtraction and one addition), Straight Add & Sub (one addition and one subtraction), and Straight Sub & Add (one subtraction and one addition). Based on the way of how an overflow condition is handled, the SIMD 16-bit add/subtract instructions can be classified into 5 groups: Wrap-around (dropping overflow), Signed Halving (keeping overflow by dropping 1 LSB bit), Unsigned Halving, Signed Saturation (clipping overflow), and Unsigned Saturation. Together, there are 30 SIMD 16-bit add/subtract instructions.

Functions

`__STATIC_FORCEINLINE unsigned long __RV_ADD16 (unsigned long a, unsigned long b)`

ADD16 (SIMD 16-bit Addition)

Type: SIMD

Syntax:

```
ADD16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit integer element additions simultaneously.

Description :

This instruction adds the 16-bit integer elements in Rs1 with the 16-bit integer elements in Rs2, and then writes the 16-bit element results to Rd.

Note :

This instruction can be used for either signed or unsigned addition.

Operations:

```
Rd.H[x] = Rs1.H[x] + Rs2.H[x];
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_CRAS16 (unsigned long a, unsigned long b)

CRAS16 (SIMD 16-bit Cross Addition & Subtraction)

Type: SIMD

Syntax:

```
CRAS16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit integer element addition and 16-bit integer element subtraction in a 32-bit chunk simultaneously. Operands are from crossed positions in 32-bit chunks.

Description :

This instruction adds the 16-bit integer element in [31:16] of 32-bit chunks in Rs1 with the 16-bit integer element in [15:0] of 32-bit chunks in Rs2, and writes the result to [31:16] of 32-bit chunks in Rd; at the same time, it subtracts the 16-bit integer element in [31:16] of 32-bit chunks in Rs2 from the 16-bit integer element in [15:0] of 32-bit chunks, and writes the result to [15:0] of 32- bit chunks in Rd.

Note :

This instruction can be used for either signed or unsigned operations.

Operations:

```
Rd.W[x][31:16] = Rs1.W[x][31:16] + Rs2.W[x][15:0];
Rd.W[x][15:0] = Rs1.W[x][15:0] - Rs2.W[x][31:16];
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_CRSA16 (unsigned long a, unsigned long b)

CRSA16 (SIMD 16-bit Cross Subtraction & Addition)

Type: SIMD

Syntax:

```
CRSA16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit integer element subtraction and 16-bit integer element addition in a 32-bit chunk simultaneously. Operands are from crossed positions in 32-bit chunks.

Description :

This instruction subtracts the 16-bit integer element in [15:0] of 32-bit chunks in Rs2 from the 16-bit integer element in [31:16] of 32-bit chunks in Rs1, and writes the result to [31:16] of 32-bit chunks in Rd; at the same time, it adds the 16-bit integer element in [31:16] of 32-bit chunks in Rs2 with the 16-bit integer element in [15:0] of 32-bit chunks in Rs1, and writes the result to [15:0] of 32-bit chunks in Rd.

Note :

This instruction can be used for either signed or unsigned operations.

Operations:

```
Rd.W[x][31:16] = Rs1.W[x][31:16] - Rs2.W[x][15:0];
Rd.W[x][15:0] = Rs1.W[x][15:0] + Rs2.W[x][31:16];
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_KADD16 (unsigned long a, unsigned long b)`

KADD16 (SIMD 16-bit Signed Saturating Addition)

Type: SIMD

Syntax:

```
KADD16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer element saturating additions simultaneously.

Description :

This instruction adds the 16-bit signed integer elements in Rs1 with the 16-bit signed integer elements in Rs2. If any of the results are beyond the Q15 number range (-2^15 <= Q15 <= 2^15-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.H[x] + Rs2.H[x];
if (res[x] > 32767) {
  res[x] = 32767;
  OV = 1;
} else if (res[x] < -32768) {
  res[x] = -32768;
```

(continues on next page)

(continued from previous page)

```
  OV = 1;
}
Rd.H[x] = res[x];
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KCRAS16 (unsigned long a, unsigned long b)

KCRAS16 (SIMD 16-bit Signed Saturating Cross Addition & Subtraction)

Type: SIMD

Syntax:

```
KCRAS16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer element saturating addition and 16-bit signed integer element saturating subtraction in a 32-bit chunk simultaneously. Operands are from crossed positions in 32- bit chunks.

Description :

This instruction adds the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs1 with the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs2; at the same time, it subtracts the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs2 from the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs1. If any of the results are beyond the Q15 number range (-2^15 <= Q15 <= 2^15-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [31:16] of 32-bit chunks in Rd for addition and [15:0] of 32-bit chunks in Rd for subtraction.

Operations:

```
res1 = Rs1.W[x][31:16] + Rs2.W[x][15:0];
res2 = Rs1.W[x][15:0] - Rs2.W[x][31:16];
for (res in [res1, res2]) {
  if (res > (2^15)-1) {
    res = (2^15)-1;
    OV = 1;
  } else if (res < -2^15) {
    res = -2^15;
    OV = 1;
  }
}
Rd.W[x][31:16] = res1;
Rd.W[x][15:0] = res2;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KCRSA16 (unsigned long a, unsigned long b)

KCRSA16 (SIMD 16-bit Signed Saturating Cross Subtraction & Addition)

Type: SIMD

Syntax:

```
KCRSA16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer element saturating subtraction and 16-bit signed integer element saturating addition in a 32-bit chunk simultaneously. Operands are from crossed positions in 32-bit chunks.

Description :

This instruction subtracts the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs2 from the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs1; at the same time, it adds the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs2 with the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs1. If any of the results are beyond the Q15 number range (-2^15 <= Q15 <= 2^15-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [31:16] of 32-bit chunks in Rd for subtraction and [15:0] of 32-bit chunks in Rd for addition.

Operations:

```
res1 = Rs1.W[x][31:16] - Rs2.W[x][15:0];
res2 = Rs1.W[x][15:0] + Rs2.W[x][31:16];
for (res in [res1, res2]) {
  if (res > (2^15)-1) {
    res = (2^15)-1;
    OV = 1;
  } else if (res < -2^15) {
    res = -2^15;
    OV = 1;
  }
}
Rd.W[x][31:16] = res1;
Rd.W[x][15:0] = res2;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KSTAS16 (unsigned long a, unsigned long b)

KSTAS16 (SIMD 16-bit Signed Saturating Straight Addition & Subtraction)

Type: SIMD

Syntax:

```
KSTAS16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer element saturating addition and 16-bit signed integer element saturating subtraction in a 32-bit chunk simultaneously. Operands are from corresponding positions in 32-bit chunks.

Description :

This instruction adds the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs1 with the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs2; at the same time, it subtracts the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs2 from the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs1. If any of the results are beyond the Q15 number range (-2^15 <= Q15 <= 2^15-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [31:16] of 32-bit chunks in Rd for addition and [15:0] of 32-bit chunks in Rd for subtraction.

Operations:

```
res1 = Rs1.W[x][31:16] + Rs2.W[x][31:16];
res2 = Rs1.W[x][15:0] - Rs2.W[x][15:0];
for (res in [res1, res2]) {
  if (res > (2^15)-1) {
    res = (2^15)-1;
    OV = 1;
  } else if (res < -2^15) {
    res = -2^15;
    OV = 1;
  }
}
Rd.W[x][31:16] = res1;
Rd.W[x][15:0] = res2;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KSTSA16 (unsigned long a, unsigned long b)

KSTSA16 (SIMD 16-bit Signed Saturating Straight Subtraction & Addition)

Type: SIMD

Syntax:

```
KSTSA16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer element saturating subtraction and 16-bit signed integer element saturating addition in a 32-bit chunk simultaneously. Operands are from corresponding positions in 32-bit chunks.

Description :

This instruction subtracts the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs2 from the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs1; at the same time, it adds the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs2 with the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs1. If any of the results are beyond the Q15 number range (-2^15 <= Q15 <= 2^15-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [31:16] of 32-bit chunks in Rd for subtraction and [15:0] of 32-bit chunks in Rd for addition.

Operations:

```
res1 = Rs1.W[x][31:16] - Rs2.W[x][31:16];
res2 = Rs1.W[x][15:0] + Rs2.W[x][15:0];
for (res in [res1, res2]) {
  if (res > (2^15)-1) {
    res = (2^15)-1;
    OV = 1;
  } else if (res < -2^15) {
    res = -2^15;
    OV = 1;
  }
}
Rd.W[x][31:16] = res1;
Rd.W[x][15:0] = res2;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KSUB16 (unsigned long a, unsigned long b)

KSUB16 (SIMD 16-bit Signed Saturating Subtraction)

Type: SIMD

Syntax:

```
KSUB16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer elements saturating subtractions simultaneously.

Description :

This instruction subtracts the 16-bit signed integer elements in Rs2 from the 16-bit signed integer elements in Rs1. If any of the results are beyond the Q15 number range (-2^15 <= Q15 <= 2^15-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.H[x] - Rs2.H[x];
if (res[x] > (2^15)-1) {
  res[x] = (2^15)-1;
  OV = 1;
```

(continues on next page)

(continued from previous page)

```
} else if (res[x] < -2^15) {
  res[x] = -2^15;
  OV = 1;
}
Rd.H[x] = res[x];
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_RADD16 (unsigned long a, unsigned long b)

RADD16 (SIMD 16-bit Signed Halving Addition)

Type: SIMD

Syntax:

```
RADD16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer element additions simultaneously. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 16-bit signed integer elements in Rs1 with the 16-bit signed integer elements in Rs2. The results are first arithmetically right-shifted by 1 bit and then written to Rd.

Examples:

```
* Rs1 = 0x7FFF, Rs2 = 0x7FFF, Rd = 0x7FFF
* Rs1 = 0x8000, Rs2 = 0x8000, Rd = 0x8000
* Rs1 = 0x4000, Rs2 = 0x8000, Rd = 0xE000
```

Operations:

```
Rd.H[x] = (Rs1.H[x] + Rs2.H[x]) s>> 1; for RV32: x=1...0, for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_RCRAS16 (unsigned long a, unsigned long b)

RCRAS16 (SIMD 16-bit Signed Halving Cross Addition & Subtraction)

Type: SIMD

Syntax:

```
RCRAS16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer element addition and 16-bit signed integer element subtraction in a 32-bit chunk simultaneously. Operands are from crossed positions in 32-bit chunks. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs1 with the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs2, and subtracts the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs2 from the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs1. The element results are first arithmetically right-shifted by 1 bit and then written to [31:16] of 32-bit chunks in Rd and [15:0] of 32-bit chunks in Rd.

Examples:

```
Please see `RADD16` and `RSUB16` instructions.
```

Operations:

```
Rd.W[x][31:16] = (Rs1.W[x][31:16] + Rs2.W[x][15:0]) s>> 1;
Rd.W[x][15:0] = (Rs1.W[x][15:0] - Rs2.W[x][31:16]) s>> 1;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_RCRSA16 (unsigned long a, unsigned long b)

RCRSA16 (SIMD 16-bit Signed Halving Cross Subtraction & Addition)

Type: SIMD

Syntax:

```
RCRSA16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer element subtraction and 16-bit signed integer element addition in a 32-bit chunk simultaneously. Operands are from crossed positions in 32-bit chunks. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs2 from the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs1, and adds the 16-bit signed element integer in [15:0] of 32-bit chunks in Rs1 with the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs2. The two results are first arithmetically right-shifted by 1 bit and then written to [31:16] of 32-bit chunks in Rd and [15:0] of 32-bit chunks in Rd.

Examples:

```
Please see `RADD16` and `RSUB16` instructions.
```

Operations:

```
Rd.W[x][31:16] = (Rs1.W[x][31:16] - Rs2.W[x][15:0]) s>> 1;
Rd.W[x][15:0] = (Rs1.W[x][15:0] + Rs2.W[x][31:16]) s>> 1;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_RSTAS16 (unsigned long a, unsigned long b)

RSTAS16 (SIMD 16-bit Signed Halving Straight Addition & Subtraction)

Type: SIMD

Syntax:

```
RSTAS16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer element addition and 16-bit signed integer element subtraction in a 32-bit chunk simultaneously. Operands are from corresponding positions in 32-bit chunks. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs1 with the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs2, and subtracts the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs2 from the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs1. The element results are first arithmetically right-shifted by 1 bit and then written to [31:16] of 32-bit chunks in Rd and [15:0] of 32-bit chunks in Rd.

Examples:

```
Please see `RADD16` and `RSUB16` instructions.
```

Operations:

```
Rd.W[x][31:16] = (Rs1.W[x][31:16] + Rs2.W[x][31:16]) s>> 1;
Rd.W[x][15:0] = (Rs1.W[x][15:0] - Rs2.W[x][15:0]) s>> 1;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_RSTSA16 (unsigned long a, unsigned long b)

RSTSA16 (SIMD 16-bit Signed Halving Straight Subtraction & Addition)

Type: SIMD

Syntax:

```
RSTSA16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer element subtraction and 16-bit signed integer element addition in a 32-bit chunk simultaneously. Operands are from corresponding positions in 32-bit chunks. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs2 from the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs1, and adds the 16-bit signed element integer in [15:0] of 32-bit chunks in Rs1 with the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs2. The two results are first arithmetically right-shifted by 1 bit and then written to [31:16] of 32-bit chunks in Rd and [15:0] of 32-bit chunks in Rd.

Examples:

```
Please see `RADD16` and `RSUB16` instructions.
```

Operations:

```
Rd.W[x][31:16] = (Rs1.W[x][31:16] - Rs2.W[x][31:16]) s>> 1;
Rd.W[x][15:0] = (Rs1.W[x][15:0] + Rs2.W[x][15:0]) s>> 1;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_RSUB16 (unsigned long a, unsigned long b)

RSUB16 (SIMD 16-bit Signed Halving Subtraction)

Type: SIMD

Syntax:

```
RSUB16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer element subtractions simultaneously. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 16-bit signed integer elements in Rs2 from the 16-bit signed integer elements in Rs1. The results are first arithmetically right-shifted by 1 bit and then written to Rd.

Examples:

```
* Ra = 0x7FFF, Rb = 0x8000, Rt = 0x7FFF
* Ra = 0x8000, Rb = 0x7FFF, Rt = 0x8000
* Ra = 0x8000, Rb = 0x4000, Rt = 0xA000
```

Operations:

```
Rd.H[x] = (Rs1.H[x] - Rs2.H[x]) s>> 1;
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_STAS16 (unsigned long a, unsigned long b)`

STAS16 (SIMD 16-bit Straight Addition & Subtraction)

Type: SIMD

Syntax:

```
STAS16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit integer element addition and 16-bit integer element subtraction in a 32-bit chunk simultaneously. Operands are from corresponding positions in 32-bit chunks.

Description :

This instruction adds the 16-bit integer element in [31:16] of 32-bit chunks in Rs1 with the 16-bit integer element in [31:16] of 32-bit chunks in Rs2, and writes the result to [31:16] of 32-bit chunks in Rd; at the same time, it subtracts the 16-bit integer element in [15:0] of 32-bit chunks in Rs2 from the 16-bit integer element in [15:0] of 32-bit chunks, and writes the result to [15:0] of 32- bit chunks in Rd.

Note :

This instruction can be used for either signed or unsigned operations.

Operations:

```
Rd.W[x][31:16] = Rs1.W[x][31:16] + Rs2.W[x][31:16];
Rd.W[x][15:0] = Rs1.W[x][15:0] - Rs2.W[x][15:0];
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_STSA16 (unsigned long a, unsigned long b)

STSA16 (SIMD 16-bit Straight Subtraction & Addition)

Type: SIMD

Syntax:

```
STSA16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit integer element subtraction and 16-bit integer element addition in a 32-bit chunk simultaneously. Operands are from corresponding positions in 32-bit chunks.

Description :

This instruction subtracts the 16-bit integer element in [31:16] of 32-bit chunks in Rs2 from the 16-bit integer element in [31:16] of 32-bit chunks in Rs1, and writes the result to [31:16] of 32-bit chunks in Rd; at the same time, it adds the 16-bit integer element in [15:0] of 32-bit chunks in Rs2 with the 16-bit integer element in [15:0] of 32-bit chunks in Rs1, and writes the result to [15:0] of 32-bit chunks in Rd.

Note :

This instruction can be used for either signed or unsigned operations.

Operations:

```
Rd.W[x][31:16] = Rs1.W[x][31:16] - Rs2.W[x][31:16];
Rd.W[x][15:0] = Rs1.W[x][15:0] + Rs2.W[x][15:0];
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SUB16 (unsigned long a, unsigned long b)

SUB16 (SIMD 16-bit Subtraction)

Type: SIMD

Syntax:

```
SUB16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit integer element subtractions simultaneously.

Description :

This instruction subtracts the 16-bit integer elements in Rs2 from the 16-bit integer elements in Rs1, and then writes the result to Rd.

Note :

This instruction can be used for either signed or unsigned subtraction.

Operations:

```
Rd.H[x] = Rs1.H[x] - Rs2.H[x];
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UKADD16 (unsigned long a, unsigned long b)

UKADD16 (SIMD 16-bit Unsigned Saturating Addition)

Type: SIMD

Syntax:

```
UKADD16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit unsigned integer element saturating additions simultaneously.

Description :

This instruction adds the 16-bit unsigned integer elements in Rs1 with the 16-bit unsigned integer elements in Rs2. If any of the results are beyond the 16-bit unsigned number range (0 <= RES <= 2^16-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.H[x] + Rs2.H[x];
if (res[x] > (2^16)-1) {
  res[x] = (2^16)-1;
  OV = 1;
}
Rd.H[x] = res[x];
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UKCRAS16 (unsigned long a, unsigned long b)

UKCRAS16 (SIMD 16-bit Unsigned Saturating Cross Addition & Subtraction)

Type: SIMD

Syntax:

```
UKCRAS16 Rd, Rs1, Rs2
```

Purpose :

Do one 16-bit unsigned integer element saturating addition and one 16-bit unsigned integer element saturating subtraction in a 32-bit chunk simultaneously. Operands are from crossed positions in 32-bit chunks.

Description :

This instruction adds the 16-bit unsigned integer element in [31:16] of 32-bit chunks in Rs1 with the 16-bit unsigned integer element in [15:0] of 32-bit chunks in Rs2; at the same time, it subtracts the 16-bit unsigned integer element in [31:16] of 32-bit chunks in Rs2 from the 16-bit unsigned integer element in [15:0] of 32-bit chunks in Rs1. If any of the results are beyond the 16-bit unsigned number range (0 <= RES <= 2^16-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [31:16] of 32-bit chunks in Rd for addition and [15:0] of 32-bit chunks in Rd for subtraction.

Operations:

```
res1 = Rs1.W[x][31:16] + Rs2.W[x][15:0];
res2 = Rs1.W[x][15:0] - Rs2.W[x][31:16];
if (res1 > (2^16)-1) {
  res1 = (2^16)-1;
  OV = 1;
}
if (res2 < 0) {
  res2 = 0;
  OV = 1;
}
Rd.W[x][31:16] = res1;
Rd.W[x][15:0] = res2;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_UKCRSA16 (unsigned long a, unsigned long b)`

UKCRSA16 (SIMD 16-bit Unsigned Saturating Cross Subtraction & Addition)

Type: SIMD

Syntax:

```
UKCRSA16 Rd, Rs1, Rs2
```

Purpose :

Do one 16-bit unsigned integer element saturating subtraction and one 16-bit unsigned integer element saturating addition in a 32-bit chunk simultaneously. Operands are from crossed positions in 32-bit chunks.

Description :

This instruction subtracts the 16-bit unsigned integer element in [15:0] of 32-bit chunks in Rs2 from the 16-bit unsigned integer element in [31:16] of 32-bit chunks in Rs1; at the same time, it adds the 16-bit unsigned integer element in [31:16] of 32-bit chunks in Rs2 with the 16- bit unsigned integer element in [15:0] of 32-bit chunks in Rs1. If any of the results are beyond the 16-bit unsigned number range (0 <= RES <= 2^16-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [31:16] of 32-bit chunks in Rd for subtraction and [15:0] of 32-bit chunks in Rd for addition.

Operations:

```
res1 = Rs1.W[x][31:16] - Rs2.W[x][15:0];
res2 = Rs1.W[x][15:0] + Rs2.W[x][31:16];
if (res1 < 0) {
  res1 = 0;
  OV = 1;
} else if (res2 > (2^16)-1) {
  res2 = (2^16)-1;
  OV = 1;
}
Rd.W[x][31:16] = res1;
Rd.W[x][15:0] = res2;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UKSTAS16 (unsigned long a, unsigned long b)

UKSTAS16 (SIMD 16-bit Unsigned Saturating Straight Addition & Subtraction)

Type: SIMD

Syntax:

```
UKSTAS16 Rd, Rs1, Rs2
```

Purpose :

Do one 16-bit unsigned integer element saturating addition and one 16-bit unsigned integer element saturating subtraction in a 32-bit chunk simultaneously. Operands are from corresponding positions in 32-bit chunks.

Description :

This instruction adds the 16-bit unsigned integer element in [31:16] of 32-bit chunks in Rs1 with the 16-bit unsigned integer element in [31:16] of 32-bit chunks in Rs2; at the same time, it subtracts the 16-bit unsigned integer element in [15:0] of 32-bit chunks in Rs2 from the 16-bit unsigned integer element in [15:0] of 32-bit chunks in Rs1. If any of the results are beyond the 16-bit unsigned number range (0 <= RES <= 2^16-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [31:16] of 32-bit chunks in Rd for addition and [15:0] of 32-bit chunks in Rd for subtraction.

Operations:

```
res1 = Rs1.W[x][31:16] + Rs2.W[x][31:16];
res2 = Rs1.W[x][15:0] - Rs2.W[x][15:0];
if (res1 > (2^16)-1) {
```

(continues on next page)

(continued from previous page)

```
  res1 = (2^16)-1;
  OV = 1;
}
if (res2 < 0) {
  res2 = 0;
  OV = 1;
}
Rd.W[x][31:16] = res1;
Rd.W[x][15:0] = res2;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UKSTSA16 (unsigned long a, unsigned long b)

UKSTSA16 (SIMD 16-bit Unsigned Saturating Straight Subtraction & Addition)

Type: SIMD

Syntax:

```
UKSTSA16 Rd, Rs1, Rs2
```

Purpose :

Do one 16-bit unsigned integer element saturating subtraction and one 16-bit unsigned integer element saturating addition in a 32-bit chunk simultaneously. Operands are from corresponding positions in 32-bit chunks.

Description :

This instruction subtracts the 16-bit unsigned integer element in [31:16] of 32-bit chunks in Rs2 from the 16-bit unsigned integer element in [31:16] of 32-bit chunks in Rs1; at the same time, it adds the 16-bit unsigned integer element in [15:0] of 32-bit chunks in Rs2 with the 16- bit unsigned integer element in [15:0] of 32-bit chunks in Rs1. If any of the results are beyond the 16-bit unsigned number range (0 <= RES <= 2^16-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [31:16] of 32-bit chunks in Rd for subtraction and [15:0] of 32-bit chunks in Rd for addition.

Operations:

```
res1 = Rs1.W[x][31:16] - Rs2.W[x][31:16];
res2 = Rs1.W[x][15:0] + Rs2.W[x][15:0];
if (res1 < 0) {
  res1 = 0;
  OV = 1;
} else if (res2 > (2^16)-1) {
  res2 = (2^16)-1;
  OV = 1;
}
Rd.W[x][31:16] = res1;
```

(continues on next page)

(continued from previous page)

```
Rd.W[x][15:0] = res2;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UKSUB16 (unsigned long a, unsigned long b)

UKSUB16 (SIMD 16-bit Unsigned Saturating Subtraction)

Type: SIMD

Syntax:

```
UKSUB16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit unsigned integer elements saturating subtractions simultaneously.

Description :

This instruction subtracts the 16-bit unsigned integer elements in Rs2 from the 16-bit unsigned integer elements in Rs1. If any of the results are beyond the 16-bit unsigned number range (0 <= RES <= 2^16-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.H[x] - Rs2.H[x];
if (res[x] < 0) {
  res[x] = 0;
  OV = 1;
}
Rd.H[x] = res[x];
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_URADD16 (unsigned long a, unsigned long b)

URADD16 (SIMD 16-bit Unsigned Halving Addition)

Type: SIMD

Syntax:

```
URADD16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit unsigned integer element additions simultaneously. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 16-bit unsigned integer elements in Rs1 with the 16-bit unsigned integer elements in Rs2. The results are first logically right-shifted by 1 bit and then written to Rd.

Examples:

```
* Ra = 0x7FFF, Rb = 0x7FFF Rt = 0x7FFF
* Ra = 0x8000, Rb = 0x8000 Rt = 0x8000
* Ra = 0x4000, Rb = 0x8000 Rt = 0x6000
```

Operations:

```
Rd.H[x] = (Rs1.H[x] + Rs2.H[x]) u>> 1;
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_URCRAS16 (unsigned long a, unsigned long b)

URCRAS16 (SIMD 16-bit Unsigned Halving Cross Addition & Subtraction)

Type: SIMD

Syntax:

```
URCRAS16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit unsigned integer element addition and 16-bit unsigned integer element subtraction in a 32-bit chunk simultaneously. Operands are from crossed positions in 32-bit chunks. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 16-bit unsigned integer in [31:16] of 32-bit chunks in Rs1 with the 16-bit unsigned integer in [15:0] of 32-bit chunks in Rs2, and subtracts the 16-bit unsigned integer in [31:16] of 32-bit chunks in Rs2 from the 16-bit unsigned integer in [15:0] of 32-bit chunks in Rs1. The element results are first logically right-shifted by 1 bit and then written to [31:16] of 32- bit chunks in Rd and [15:0] of 32-bit chunks in Rd.

Examples:

```
Please see `URADD16` and `URSUB16` instructions.
```

Operations:

```
Rd.W[x][31:16] = (Rs1.W[x][31:16] + Rs2.W[x][15:0]) u>> 1;
Rd.W[x][15:0] = (Rs1.W[x][15:0] - Rs2.W[x][31:16]) u>> 1;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_URCRSA16 (unsigned long a, unsigned long b)

URCRSA16 (SIMD 16-bit Unsigned Halving Cross Subtraction & Addition)

Type: SIMD

Syntax:

```
URCRSA16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit unsigned integer element subtraction and 16-bit unsigned integer element addition in a 32-bit chunk simultaneously. Operands are from crossed positions in 32-bit chunks. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 16-bit unsigned integer in [15:0] of 32-bit chunks in Rs2 from the 16-bit unsigned integer in [31:16] of 32-bit chunks in Rs1, and adds the 16-bit unsigned integer in [15:0] of 32-bit chunks in Rs1 with the 16-bit unsigned integer in [31:16] of 32-bit chunks in Rs2. The two results are first logically right-shifted by 1 bit and then written to [31:16] of 32-bit chunks in Rd and [15:0] of 32-bit chunks in Rd.

Examples:

```
Please see `URADD16` and `URSUB16` instructions.
```

Operations:

```
Rd.W[x][31:16] = (Rs1.W[x][31:16] - Rs2.W[x][15:0]) u>> 1;
Rd.W[x][15:0] = (Rs1.W[x][15:0] + Rs2.W[x][31:16]) u>> 1;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_URSTAS16 (unsigned long a, unsigned long b)

URSTAS16 (SIMD 16-bit Unsigned Halving Straight Addition & Subtraction)

Type: SIMD

Syntax:

```
URSTAS16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit unsigned integer element addition and 16-bit unsigned integer element subtraction in a 32-bit chunk simultaneously. Operands are from corresponding positions in 32-bit chunks. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 16-bit unsigned integer in [31:16] of 32-bit chunks in Rs1 with the 16-bit unsigned integer in [31:16] of 32-bit chunks in Rs2, and subtracts the 16-bit unsigned integer in [15:0] of 32-bit chunks in Rs2 from the 16-bit unsigned integer in [15:0] of 32-bit chunks in Rs1. The element results are first logically right-shifted by 1 bit and then written to [31:16] of 32- bit chunks in Rd and [15:0] of 32-bit chunks in Rd.

Examples:

```
Please see `URADD16` and `URSUB16` instructions.
```

Operations:

```
Rd.W[x][31:16] = (Rs1.W[x][31:16] + Rs2.W[x][31:16]) u>> 1;
Rd.W[x][15:0] = (Rs1.W[x][15:0] - Rs2.W[x][15:0]) u>> 1;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_URSTSA16 (unsigned long a, unsigned long b)

URSTSA16 (SIMD 16-bit Unsigned Halving Straight Subtraction & Addition)

Type: SIMD

Syntax:

```
URCRSA16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit unsigned integer element subtraction and 16-bit unsigned integer element addition in a 32-bit chunk simultaneously. Operands are from corresponding positions in 32-bit chunks. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 16-bit unsigned integer in [31:16] of 32-bit chunks in Rs2 from the 16-bit unsigned integer in [31:16] of 32-bit chunks in Rs1, and adds the 16-bit unsigned integer in [15:0] of 32-bit chunks in Rs1 with the 16-bit unsigned integer in [15:0] of 32-bit chunks in Rs2. The two results are first logically right-shifted by 1 bit and then written to [31:16] of 32-bit chunks in Rd and [15:0] of 32-bit chunks in Rd.

Examples:

```
Please see `URADD16` and `URSUB16` instructions.
```

Operations:

```
Rd.W[x][31:16] = (Rs1.W[x][31:16] - Rs2.W[x][31:16]) u>> 1;
Rd.W[x][15:0] = (Rs1.W[x][15:0] + Rs2.W[x][15:0]) u>> 1;
for RV32, x=0
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_URSUB16 (unsigned long a, unsigned long b)

URSUB16 (SIMD 16-bit Unsigned Halving Subtraction)

Type: SIMD

Syntax:

```
URSUB16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit unsigned integer element subtractions simultaneously. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 16-bit unsigned integer elements in Rs2 from the 16-bit unsigned integer elements in Rs1. The results are first logically right-shifted by 1 bit and then written to Rd.

Examples:

```
* Ra = 0x7FFF, Rb = 0x8000 Rt = 0xFFFF
* Ra = 0x8000, Rb = 0x7FFF Rt = 0x0000
* Ra = 0x8000, Rb = 0x4000 Rt = 0x2000
```

Operations:

```
Rd.H[x] = (Rs1.H[x] - Rs2.H[x]) u>> 1;
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

SIMD 8-bit Addition & Subtraction Instructions

`__STATIC_FORCEINLINE unsigned long __RV_ADD8 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_KADD8 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_KSUB8 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_RADD8 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_RSUB8 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_SUB8 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_UKADD8 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_UKSUB8 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_URADD8 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_URSUB8 (unsigned long a, unsigned long b)`

group `NMSIS_Core_DSP_Intrinsic_SIMD_8B_ADDSUB`

SIMD 8-bit Addition & Subtraction Instructions.

Based on the types of the four 8-bit arithmetic operations, the SIMD 8-bit add/subtract instructions can be classified into 2 main categories: Addition (four 8-bit addition), and Subtraction (four 8-bit subtraction). Based on the way of how an overflow condition is handled for singed or unsigned operation, the SIMD 8-bit add/subtract instructions can be classified into 5 groups: Wrap-around (dropping overflow), Signed Halving (keeping overflow by dropping 1 LSB bit), Unsigned Halving, Signed Saturation (clipping overflow), and Unsigned Saturation. Together, there are 10 SIMD 8-bit add/subtract instructions.

Functions

`__STATIC_FORCEINLINE unsigned long __RV_ADD8 (unsigned long a, unsigned long b)`

ADD8 (SIMD 8-bit Addition)

Type: SIMD

Syntax:

```
ADD8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit integer element additions simultaneously.

Description :

This instruction adds the 8-bit integer elements in Rs1 with the 8-bit integer elements in Rs2, and then writes the 8-bit element results to Rd.

Note :

This instruction can be used for either signed or unsigned addition.

Operations:

```
Rd.B[x] = Rs1.B[x] + Rs2.B[x];
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KADD8 (unsigned long a, unsigned long b)

KADD8 (SIMD 8-bit Signed Saturating Addition)

Type: SIMD

Syntax:

```
KADD8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit signed integer element saturating additions simultaneously.

Description :

This instruction adds the 8-bit signed integer elements in Rs1 with the 8-bit signed integer elements in Rs2. If any of the results are beyond the Q7 number range (-2^7 <= Q7 <= 2^7-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.B[x] + Rs2.B[x];
if (res[x] > 127) {
  res[x] = 127;
  OV = 1;
} else if (res[x] < -128) {
  res[x] = -128;
  OV = 1;
}
Rd.B[x] = res[x];
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KSUB8 (unsigned long a, unsigned long b)

KSUB8 (SIMD 8-bit Signed Saturating Subtraction)

Type: SIMD

Syntax:

```
KSUB8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit signed elements saturating subtractions simultaneously.

Description :

This instruction subtracts the 8-bit signed integer elements in Rs2 from the 8-bit signed integer elements in Rs1. If any of the results are beyond the Q7 number range (-2^7 <= Q7 <= 27 -1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.B[x] - Rs2.B[x];
if (res[x] > (2^7)-1) {
  res[x] = (2^7)-1;
  OV = 1;
} else if (res[x] < -2^7) {
  res[x] = -2^7;
  OV = 1;
}
Rd.B[x] = res[x];
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_RADD8 (unsigned long a, unsigned long b)

RADD8 (SIMD 8-bit Signed Halving Addition)

Type: SIMD

Syntax:

```
RADD8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit signed integer element additions simultaneously. The element results are halved to avoid overflow or saturation.

Description :

This instruction adds the 8-bit signed integer elements in Rs1 with the 8-bit signed integer elements in Rs2. The results are first arithmetically right-shifted by 1 bit and then written to Rd.

Examples:

```
* Rs1 = 0x7F, Rs2 = 0x7F, Rd = 0x7F
* Rs1 = 0x80, Rs2 = 0x80, Rd = 0x80
* Rs1 = 0x40, Rs2 = 0x80, Rd = 0xE0
```

Operations:

```
Rd.B[x] = (Rs1.B[x] + Rs2.B[x]) s>> 1; for RV32: x=3...0, for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_RSUB8 (unsigned long a, unsigned long b)

RSUB8 (SIMD 8-bit Signed Halving Subtraction)

Type: SIMD

Syntax:

```
RSUB8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit signed integer element subtractions simultaneously. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 8-bit signed integer elements in Rs2 from the 8-bit signed integer elements in Rs1. The results are first arithmetically right-shifted by 1 bit and then written to Rd.

Examples:

```
* Rs1 = 0x7F, Rs2 = 0x80, Rd = 0x7F
* Rs1 = 0x80, Rs2 = 0x7F, Rd = 0x80
* Rs1= 0x80, Rs2 = 0x40, Rd = 0xA0
```

Operations:

```
Rd.B[x] = (Rs1.B[x] - Rs2.B[x]) s>> 1;
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_SUB8 (unsigned long a, unsigned long b)`

SUB8 (SIMD 8-bit Subtraction)

Type: SIMD

Syntax:

```
SUB8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit integer element subtractions simultaneously.

Description :

This instruction subtracts the 8-bit integer elements in Rs2 from the 8-bit integer elements in Rs1, and then writes the result to Rd.

Note :

This instruction can be used for either signed or unsigned subtraction.

Operations:

```
Rd.B[x] = Rs1.B[x] - Rs2.B[x];
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_UKADD8 (unsigned long a, unsigned long b)`

UKADD8 (SIMD 8-bit Unsigned Saturating Addition)

Type: SIMD

Syntax:

```
UKADD8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit unsigned integer element saturating additions simultaneously.

Description :

This instruction adds the 8-bit unsigned integer elements in Rs1 with the 8-bit unsigned integer elements in Rs2. If any of the results are beyond the 8-bit unsigned number range (0 <= RES <= 28-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.B[x] + Rs2.B[x];
if (res[x] > (2^8)-1) {
  res[x] = (2^8)-1;
```

(continues on next page)

(continued from previous page)

```
  OV = 1;
}
Rd.B[x] = res[x];
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UKSUB8 (unsigned long a, unsigned long b)

UKSUB8 (SIMD 8-bit Unsigned Saturating Subtraction)

Type: SIMD

Syntax:

```
UKSUB8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit unsigned integer elements saturating subtractions simultaneously.

Description :

This instruction subtracts the 8-bit unsigned integer elements in Rs2 from the 8-bit unsigned integer elements in Rs1. If any of the results are beyond the 8-bit unsigned number range (0 <= RES <= 28-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.B[x] - Rs2.B[x];
if (res[x] < 0) {
  res[x] = 0;
  OV = 1;
}
Rd.B[x] = res[x];
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_URADD8 (unsigned long a, unsigned long b)

URADD8 (SIMD 8-bit Unsigned Halving Addition)

Type: SIMD

Syntax:

```
URADD8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit unsigned integer element additions simultaneously. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 8-bit unsigned integer elements in Rs1 with the 8-bit unsigned integer elements in Rs2. The results are first logically right-shifted by 1 bit and then written to Rd.

Examples:

```
* Ra = 0x7F, Rb = 0x7F, Rt = 0x7F
* Ra = 0x80, Rb = 0x80, Rt = 0x80
* Ra = 0x40, Rb = 0x80, Rt = 0x60
```

Operations:

```
Rd.B[x] = (Rs1.B[x] + Rs2.B[x]) u>> 1;
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_URSUB8 (unsigned long a, unsigned long b)

URSUB8 (SIMD 8-bit Unsigned Halving Subtraction)

Type: SIMD

Syntax:

```
URSUB8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit unsigned integer element subtractions simultaneously. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 8-bit unsigned integer elements in Rs2 from the 8-bit unsigned integer elements in Rs1. The results are first logically right-shifted by 1 bit and then written to Rd.

Examples:

```
* Ra = 0x7F, Rb = 0x80 Rt = 0xFF
* Ra = 0x80, Rb = 0x7F Rt = 0x00
* Ra = 0x80, Rb = 0x40 Rt = 0x20
```

Operations:

```
Rd.B[x] = (Rs1.B[x] - Rs2.B[x]) u>> 1;
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

SIMD 16-bit Shift Instructions

`__STATIC_FORCEINLINE unsigned long __RV_KSLL16 (unsigned long a, unsigned int b)`

`__STATIC_FORCEINLINE unsigned long __RV_KSLRA16 (unsigned long a, int b)`

`__STATIC_FORCEINLINE unsigned long __RV_KSLRA16_U (unsigned long a, int b)`

`__STATIC_FORCEINLINE unsigned long __RV_SLL16 (unsigned long a, unsigned int b)`

`__STATIC_FORCEINLINE unsigned long __RV_SRA16 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_SRA16_U (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_SRL16 (unsigned long a, unsigned int b)`

`__STATIC_FORCEINLINE unsigned long __RV_SRL16_U (unsigned long a, unsigned int b)`

`__RV_KSLLI16`(a, b)

`__RV_SLLI16`(a, b)

`__RV_SRAI16`(a, b)

`__RV_SRAI16_U`(a, b)

`__RV_SRLI16`(a, b)

`__RV_SRLI16_U`(a, b)

group **`NMSIS_Core_DSP_Intrinsic_SIMD_16B_SHIFT`**

SIMD 16-bit Shift Instructions.

there are 14 SIMD 16-bit shift instructions.

Defines

__RV_KSLLI16(a, b)

KSLLI16 (SIMD 16-bit Saturating Shift Left Logical Immediate)

Type: SIMD

Syntax:

```
KSLLI16 Rd, Rs1, imm4u
```

Purpose :

Do 16-bit elements logical left shift operations with saturation simultaneously. The shift amount is an immediate value.

Description :

The 16-bit data elements in Rs1 are left-shifted logically. The shifted out bits are filled with zero and the shift amount is specified by the imm4u constant. Any shifted value greater than 2^15-1 is saturated to 2^15-1. Any shifted value smaller than -2^15 is saturated to -2^15. And the saturated results are written to Rd. If any saturation is performed, set OV bit to 1.

Operations:

```
sa = imm4u[3:0];
if (sa != 0) {
  res[(15+sa):0] = Rs1.H[x] << sa;
  if (res > (2^15)-1) {
    res = 0x7fff; OV = 1;
  } else if (res < -2^15) {
    res = 0x8000; OV = 1;
  }
  Rd.H[x] = res[15:0];
} else {
  Rd = Rs1;
}
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__RV_SLLI16(a, b)

SLLI16 (SIMD 16-bit Shift Left Logical Immediate)

Type: SIMD

Syntax:

```
SLLI16 Rd, Rs1, imm4[3:0]
```

Purpose :

Do 16-bit element logical left shift operations simultaneously. The shift amount is an immediate value.

Description :

The 16-bit elements in Rs1 are left-shifted logically. The shifted out bits are filled with zero and the shift amount is specified by the imm4[3:0] constant. And the results are written to Rd.

Operations:

```
sa = imm4[3:0];
Rd.H[x] = Rs1.H[x] << sa;
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__RV_SRAI16(a, b)

SRAI16 (SIMD 16-bit Shift Right Arithmetic Immediate)

Type: SIMD

Syntax:

```
SRAI16 Rd, Rs1, imm4u
SRAI16.u Rd, Rs1, imm4u
```

Purpose :

Do 16-bit elements arithmetic right shift operations simultaneously. The shift amount is an immediate value. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 16-bit data elements in Rs1 are right-shifted arithmetically, that is, the shifted out bits are filled with the sign-bit of the 16-bit data elements. The shift amount is specified by the imm4u constant. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 16-bit data to calculate the final results. And the results are written to Rd.

Operations:

```
sa = imm4u[3:0];
if (sa > 0) {
  if (`.u` form) { // SRAI16.u
    res[15:-1] = SE17(Rs1.H[x][15:sa-1]) + 1;
    Rd.H[x] = res[15:0];
  } else { // SRAI16
    Rd.H[x] = SE16(Rs1.H[x][15:sa]);
  }
} else {
  Rd = Rs1;
}
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__RV_SRAI16_U(a, b)

SRAI16.u (SIMD 16-bit Rounding Shift Right Arithmetic Immediate)

Type: SIMD

Syntax:

```
SRAI16 Rd, Rs1, imm4u
SRAI16.u Rd, Rs1, imm4u
```

Purpose :

Do 16-bit elements arithmetic right shift operations simultaneously. The shift amount is an immediate value. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 16-bit data elements in Rs1 are right-shifted arithmetically, that is, the shifted out bits are filled with the sign-bit of the 16-bit data elements. The shift amount is specified by the imm4u constant. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 16-bit data to calculate the final results. And the results are written to Rd.

Operations:

```
sa = imm4u[3:0];
if (sa > 0) {
  if (`.u` form) { // SRAI16.u
    res[15:-1] = SE17(Rs1.H[x][15:sa-1]) + 1;
    Rd.H[x] = res[15:0];
  } else { // SRAI16
    Rd.H[x] = SE16(Rs1.H[x][15:sa]);
  }
} else {
  Rd = Rs1;
}
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__RV_SRLI16(a, b)

SRLI16 (SIMD 16-bit Shift Right Logical Immediate)

Type: SIMD

Syntax:

```
SRLI16 Rt, Ra, imm4u
SRLI16.u Rt, Ra, imm4u
```

Purpose :

Do 16-bit elements logical right shift operations simultaneously. The shift amount is an immediate value. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 16-bit data elements in Rs1 are right-shifted logically, that is, the shifted out bits are filled with zero. The shift amount is specified by the imm4u constant. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 16-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = imm4u;
if (sa > 0) {
  if (`.u` form) { // SRLI16.u
    res[16:0] = ZE17(Rs1.H[x][15:sa-1]) + 1;
    Rd.H[x] = res[16:1];
  } else { // SRLI16
    Rd.H[x] = ZE16(Rs1.H[x][15:sa]);
  }
} else {
  Rd = Rs1;
}
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__RV_SRLI16_U(a, b)

SRLI16.u (SIMD 16-bit Rounding Shift Right Logical Immediate)

Type: SIMD

Syntax:

```
SRLI16 Rt, Ra, imm4u
SRLI16.u Rt, Ra, imm4u
```

Purpose :

Do 16-bit elements logical right shift operations simultaneously. The shift amount is an immediate value. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 16-bit data elements in Rs1 are right-shifted logically, that is, the shifted out bits are filled with zero. The shift amount is specified by the imm4u constant. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 16-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = imm4u;
if (sa > 0) {
  if (`.u` form) { // SRLI16.u
    res[16:0] = ZE17(Rs1.H[x][15:sa-1]) + 1;
    Rd.H[x] = res[16:1];
  } else { // SRLI16
    Rd.H[x] = ZE16(Rs1.H[x][15:sa]);
  }
} else {
  Rd = Rs1;
}
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

Functions

__STATIC_FORCEINLINE unsigned long __RV_KSLL16 (unsigned long a, unsigned int b)

KSLL16 (SIMD 16-bit Saturating Shift Left Logical)

Type: SIMD

Syntax:

```
KSLL16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit elements logical left shift operations with saturation simultaneously. The shift amount is a variable from a GPR.

Description :

The 16-bit data elements in Rs1 are left-shifted logically. The shifted out bits are filled with zero and the shift amount is specified by the low-order 4-bits of the value in the Rs2 register. Any shifted value greater than 2^15-1 is saturated to 2^15-1. Any shifted value smaller than -2^15 is saturated to -2^15. And the saturated results are written to Rd. If any saturation is performed, set OV bit to 1.

Operations:

```
sa = Rs2[3:0];
if (sa != 0) {
  res[(15+sa):0] = Rs1.H[x] << sa;
  if (res > (2^15)-1) {
```

(continues on next page)

(continued from previous page)

```
    res = 0x7fff; OV = 1;
  } else if (res < -2^15) {
    res = 0x8000; OV = 1;
  }
  Rd.H[x] = res[15:0];
} else {
  Rd = Rs1;
}
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KSLRA16 (unsigned long a, int b)

KSLRA16 (SIMD 16-bit Shift Left Logical with Saturation or Shift Right Arithmetic)

Type: SIMD

Syntax:

```
KSLRA16 Rd, Rs1, Rs2
KSLRA16.u Rd, Rs1, Rs2
```

Purpose :

Do 16-bit elements logical left (positive) or arithmetic right (negative) shift operation with Q15 saturation for the left shift. The `.u` form performs additional rounding up operations for the right shift.

Description :

The 16-bit data elements of Rs1 are left-shifted logically or right-shifted arithmetically based on the value of Rs2[4:0]. Rs2[4:0] is in the signed range of [-2^4, 2^4-1]. A positive Rs2[4:0] means logical left shift and a negative Rs2[4:0] means arithmetic right shift. The shift amount is the absolute value of Rs2[4:0]. However, the behavior of `Rs2[4:0]==-2^4 (0x10)` is defined to be equivalent to the behavior of `Rs2[4:0]==-(2^4-1) (0x11)`. The left-shifted results are saturated to the 16-bit signed integer range of [-2^15, 2^15-1]. For the `.u` form of the instruction, the right-shifted results are added a 1 to the most significant discarded bit position for rounding effect. After the shift, saturation, or rounding, the final results are written to Rd. If any saturation happens, this instruction sets the OV flag. The value of Rs2[31:5] will not affect this instruction.

Operations:

```
if (Rs2[4:0] < 0) {
  sa = -Rs2[4:0];
  sa = (sa == 16)? 15 : sa;
  if (`.u` form) {
    res[15:-1] = SE17(Rs1.H[x][15:sa-1]) + 1;
    Rd.H[x] = res[15:0];
  } else {
    Rd.H[x] = SE16(Rs1.H[x][15:sa]);
```

(continues on next page)

(continued from previous page)

```
  }
} else {
  sa = Rs2[3:0];
  res[(15+sa):0] = Rs1.H[x] <<(logic) sa;
  if (res > (2^15)-1) {
    res[15:0] = 0x7fff; OV = 1;
  } else if (res < -2^15) {
    res[15:0] = 0x8000; OV = 1;
  }
  d.H[x] = res[15:0];
}
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- `a` – **[in]** unsigned long type of value stored in a
- `b` – **[in]** int type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_KSLRA16_U (unsigned long a, int b)`

KSLRA16.u (SIMD 16-bit Shift Left Logical with Saturation or Rounding Shift Right Arithmetic)

Type: SIMD

Syntax:

```
KSLRA16 Rd, Rs1, Rs2
KSLRA16.u Rd, Rs1, Rs2
```

Purpose :

Do 16-bit elements logical left (positive) or arithmetic right (negative) shift operation with Q15 saturation for the left shift. The `.u` form performs additional rounding up operations for the right shift.

Description :

The 16-bit data elements of Rs1 are left-shifted logically or right-shifted arithmetically based on the value of Rs2[4:0]. Rs2[4:0] is in the signed range of [-2^4, 2^4-1]. A positive Rs2[4:0] means logical left shift and a negative Rs2[4:0] means arithmetic right shift. The shift amount is the absolute value of Rs2[4:0]. However, the behavior of `Rs2[4:0]==-2^4 (0x10)` is defined to be equivalent to the behavior of `Rs2[4:0]==-(2^4-1) (0x11)`. The left-shifted results are saturated to the 16-bit signed integer range of [-2^15, 2^15-1]. For the `.u` form of the instruction, the right-shifted results are added a 1 to the most significant discarded bit position for rounding effect. After the shift, saturation, or rounding, the final results are written to Rd. If any saturation happens, this instruction sets the OV flag. The value of Rs2[31:5] will not affect this instruction.

Operations:

```
if (Rs2[4:0] < 0) {
  sa = -Rs2[4:0];
  sa = (sa == 16)? 15 : sa;
  if (`.u` form) {
    res[15:-1] = SE17(Rs1.H[x][15:sa-1]) + 1;
```

(continues on next page)

(continued from previous page)

```
    Rd.H[x] = res[15:0];
  } else {
    Rd.H[x] = SE16(Rs1.H[x][15:sa]);
  }
} else {
  sa = Rs2[3:0];
  res[(15+sa):0] = Rs1.H[x] <<(logic) sa;
  if (res > (2^15)-1) {
    res[15:0] = 0x7fff; OV = 1;
  } else if (res < -2^15) {
    res[15:0] = 0x8000; OV = 1;
  }
  d.H[x] = res[15:0];
}
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SLL16 (unsigned long a, unsigned int b)

SLL16 (SIMD 16-bit Shift Left Logical)

Type: SIMD

Syntax:

```
SLL16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit elements logical left shift operations simultaneously. The shift amount is a variable from a GPR.

Description :

The 16-bit elements in Rs1 are left-shifted logically. And the results are written to Rd. The shifted out bits are filled with zero and the shift amount is specified by the low-order 4-bits of the value in the Rs2 register.

Operations:

```
sa = Rs2[3:0];
Rd.H[x] = Rs1.H[x] << sa;
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SRA16 (unsigned long a, unsigned long b)

SRA16 (SIMD 16-bit Shift Right Arithmetic)

Type: SIMD

Syntax:

```
SRA16 Rd, Rs1, Rs2
SRA16.u Rd, Rs1, Rs2
```

Purpose :

Do 16-bit element arithmetic right shift operations simultaneously. The shift amount is a variable from a GPR. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 16-bit data elements in Rs1 are right-shifted arithmetically, that is, the shifted out bits are filled with the sign-bit of the data elements. The shift amount is specified by the low-order 4-bits of the value in the Rs2 register. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 16-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = Rs2[3:0];
if (sa != 0) {
  if (`.u` form) { // SRA16.u
    res[15:-1] = SE17(Rs1.H[x][15:sa-1]) + 1;
    Rd.H[x] = res[15:0];
  } else { // SRA16
    Rd.H[x] = SE16(Rs1.H[x][15:sa])
  }
} else {
  Rd = Rs1;
}
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SRA16_U (unsigned long a, unsigned long b)

SRA16.u (SIMD 16-bit Rounding Shift Right Arithmetic)

Type: SIMD

Syntax:

```
SRA16 Rd, Rs1, Rs2
SRA16.u Rd, Rs1, Rs2
```

Purpose :

Do 16-bit element arithmetic right shift operations simultaneously. The shift amount is a variable from a GPR. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 16-bit data elements in Rs1 are right-shifted arithmetically, that is, the shifted out bits are filled with the sign-bit of the data elements. The shift amount is specified by the low-order 4-bits of the value in the Rs2 register. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 16-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = Rs2[3:0];
if (sa != 0) {
  if (`.u` form) { // SRA16.u
    res[15:-1] = SE17(Rs1.H[x][15:sa-1]) + 1;
    Rd.H[x] = res[15:0];
  } else { // SRA16
    Rd.H[x] = SE16(Rs1.H[x][15:sa])
  }
} else {
  Rd = Rs1;
}
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SRL16 (unsigned long a, unsigned int b)

SRL16 (SIMD 16-bit Shift Right Logical)

Type: SIMD

Syntax:

```
SRL16 Rt, Ra, Rb
 SRL16.u Rt, Ra, Rb
```

Purpose :

Do 16-bit elements logical right shift operations simultaneously. The shift amount is a variable from a GPR. The `.u` form performs additional rounding upoperations on the shifted results.

Description :

The 16-bit data elements in Rs1 are right-shifted logically, that is, the shifted out bits are filled with zero. The shift amount is specified by the low-order 4-bits of the value in the Rs2 register. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 16-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = Rs2[3:0];
if (sa > 0) {
  if (`.u` form) { // SRL16.u
    res[16:0] = ZE17(Rs1.H[x][15:sa-1]) + 1;
    Rd.H[x] = res[16:1];
  } else { // SRL16
    Rd.H[x] = ZE16(Rs1.H[x][15:sa]);
  }
} else {
  Rd = Rs1;
}
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SRL16_U (unsigned long a, unsigned int b)

SRL16.u (SIMD 16-bit Rounding Shift Right Logical)

Type: SIMD

Syntax:

```
SRL16 Rt, Ra, Rb
 SRL16.u Rt, Ra, Rb
```

Purpose :

Do 16-bit elements logical right shift operations simultaneously. The shift amount is a variable from a GPR. The `.u` form performs additional rounding upoperations on the shifted results.

Description :

The 16-bit data elements in Rs1 are right-shifted logically, that is, the shifted out bits are filled with zero. The shift amount is specified by the low-order 4-bits of the value in the Rs2 register. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 16-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = Rs2[3:0];
if (sa > 0) {
  if (`.u` form) { // SRL16.u
    res[16:0] = ZE17(Rs1.H[x][15:sa-1]) + 1;
    Rd.H[x] = res[16:1];
  } else { // SRL16
    Rd.H[x] = ZE16(Rs1.H[x][15:sa]);
  }
} else {
  Rd = Rs1;
```

(continues on next page)

(continued from previous page)

```
}
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

SIMD 8-bit Shift Instructions

`__STATIC_FORCEINLINE unsigned long __RV_KSLL8 (unsigned long a, unsigned int b)`

`__STATIC_FORCEINLINE unsigned long __RV_KSLRA8 (unsigned long a, int b)`

`__STATIC_FORCEINLINE unsigned long __RV_KSLRA8_U (unsigned long a, int b)`

`__STATIC_FORCEINLINE unsigned long __RV_SLL8 (unsigned long a, unsigned int b)`

`__STATIC_FORCEINLINE unsigned long __RV_SRA8 (unsigned long a, unsigned int b)`

`__STATIC_FORCEINLINE unsigned long __RV_SRA8_U (unsigned long a, unsigned int b)`

`__STATIC_FORCEINLINE unsigned long __RV_SRL8 (unsigned long a, unsigned int b)`

`__STATIC_FORCEINLINE unsigned long __RV_SRL8_U (unsigned long a, unsigned int b)`

`__RV_KSLLI8`(a, b)

`__RV_SLLI8`(a, b)

`__RV_SRAI8`(a, b)

`__RV_SRAI8_U`(a, b)

`__RV_SRLI8`(a, b)

`__RV_SRLI8_U`(a, b)

group **`NMSIS_Core_DSP_Intrinsic_SIMD_8B_SHIFT`**

SIMD 8-bit Shift Instructions.

there are 14 SIMD 8-bit shift instructions.

Defines

__RV_KSLLI8(a, b)

KSLLI8 (SIMD 8-bit Saturating Shift Left Logical Immediate)

Type: SIMD

Syntax:

```
KSLLI8 Rd, Rs1, imm3u
```

Purpose :

Do 8-bit elements logical left shift operations with saturation simultaneously. The shift amount is an immediate value.

Description :

The 8-bit data elements in Rs1 are left-shifted logically. The shifted out bits are filled with zero and the shift amount is specified by the imm3u constant. Any shifted value greater than 2^7-1 is saturated to 2^7-1. Any shifted value smaller than -2^7 is saturated to -2^7. And the saturated results are written to Rd. If any saturation is performed, set OV bit to 1.

Operations:

```
sa = imm3u[2:0];
if (sa != 0) {
  res[(7+sa):0] = Rs1.B[x] << sa;
  if (res > (2^7)-1) {
    res = 0x7f; OV = 1;
  } else if (res < -2^7) {
    res = 0x80; OV = 1;
  }
  Rd.B[x] = res[7:0];
} else {
  Rd = Rs1;
}
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__RV_SLLI8(a, b)

SLLI8 (SIMD 8-bit Shift Left Logical Immediate)

Type: SIMD

Syntax:

```
SLLI8 Rd, Rs1, imm3u
```

Purpose :

Do 8-bit elements logical left shift operations simultaneously. The shift amount is an immediate value.

Description :

The 8-bit elements in Rs1 are left-shifted logically. And the results are written to Rd. The shifted out bits are filled with zero and the shift amount is specified by the imm3u constant.

Operations:

```
sa = imm3u[2:0];
Rd.B[x] = Rs1.B[x] << sa;
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__RV_SRAI8(a, b)

SRAI8 (SIMD 8-bit Shift Right Arithmetic Immediate)

Type: SIMD

Syntax:

```
SRAI8 Rd, Rs1, imm3u
SRAI8.u Rd, Rs1, imm3u
```

Purpose :

Do 8-bit element arithmetic right shift operations simultaneously. The shift amount is an immediate value. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 8-bit data elements in Rs1 are right-shifted arithmetically, that is, the shifted out bits are filled with the sign-bit of the data elements. The shift amount is specified by the imm3u constant. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 8-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = imm3u[2:0];
if (sa > 0) {
  if (`.u` form) { // SRA8.u
    res[7:-1] = SE9(Rs1.B[x][7:sa-1]) + 1;
    Rd.B[x] = res[7:0];
  } else { // SRA8
    Rd.B[x] = SE8(Rd.B[x][7:sa])
  }
} else {
  Rd = Rs1;
}
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__RV_SRAI8_U(a, b)

SRAI8.u (SIMD 8-bit Rounding Shift Right Arithmetic Immediate)

Type: SIMD

Syntax:

```
SRAI8 Rd, Rs1, imm3u
SRAI8.u Rd, Rs1, imm3u
```

Purpose :

Do 8-bit element arithmetic right shift operations simultaneously. The shift amount is an immediate value. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 8-bit data elements in Rs1 are right-shifted arithmetically, that is, the shifted out bits are filled with the sign-bit of the data elements. The shift amount is specified by the imm3u constant. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 8-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = imm3u[2:0];
if (sa > 0) {
  if (`.u` form) { // SRA8.u
    res[7:-1] = SE9(Rs1.B[x][7:sa-1]) + 1;
    Rd.B[x] = res[7:0];
  } else { // SRA8
    Rd.B[x] = SE8(Rd.B[x][7:sa])
  }
} else {
  Rd = Rs1;
}
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__RV_SRLI8(a, b)

SRLI8 (SIMD 8-bit Shift Right Logical Immediate)

Type: SIMD

Syntax:

```
SRLI8 Rt, Ra, imm3u
SRLI8.u Rt, Ra, imm3u
```

Purpose :

Do 8-bit elements logical right shift operations simultaneously. The shift amount is an immediate value. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 8-bit data elements in Rs1 are right-shifted logically, that is, the shifted out bits are filled with zero. The shift amount is specified by the imm3u constant. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 8-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = imm3u[2:0];
if (sa > 0) {
  if (`.u` form) { // SRLI8.u
    res[8:0] = ZE9(Rs1.B[x][7:sa-1]) + 1;
    Rd.B[x] = res[8:1];
  } else { // SRLI8
    Rd.B[x] = ZE8(Rs1.B[x][7:sa]);
  }
} else {
  Rd = Rs1;
}
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__RV_SRLI8_U(a, b)

SRLI8.u (SIMD 8-bit Rounding Shift Right Logical Immediate)

Type: SIMD

Syntax:

```
SRLI8 Rt, Ra, imm3u
SRLI8.u Rt, Ra, imm3u
```

Purpose :

Do 8-bit elements logical right shift operations simultaneously. The shift amount is an immediate value. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 8-bit data elements in Rs1 are right-shifted logically, that is, the shifted out bits are filled with zero. The shift amount is specified by the imm3u constant. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 8-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = imm3u[2:0];
if (sa > 0) {
  if (`.u` form) { // SRLI8.u
    res[8:0] = ZE9(Rs1.B[x][7:sa-1]) + 1;
    Rd.B[x] = res[8:1];
  } else { // SRLI8
    Rd.B[x] = ZE8(Rs1.B[x][7:sa]);
  }
} else {
  Rd = Rs1;
}
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

Functions

__STATIC_FORCEINLINE unsigned long __RV_KSLL8 (unsigned long a, unsigned int b)

KSLL8 (SIMD 8-bit Saturating Shift Left Logical)

Type: SIMD

Syntax:

```
KSLL8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit elements logical left shift operations with saturation simultaneously. The shift amount is a variable from a GPR.

Description :

The 8-bit data elements in Rs1 are left-shifted logically. The shifted out bits are filled with zero and the shift amount is specified by the low-order 3-bits of the value in the Rs2 register. Any shifted value greater than 2^7-1 is saturated to 2^7-1. Any shifted value smaller than -2^7 is saturated to -2^7. And the saturated results are written to Rd. If any saturation is performed, set OV bit to 1.

Operations:

```
sa = Rs2[2:0];
if (sa != 0) {
  res[(7+sa):0] = Rs1.B[x] << sa;
  if (res > (2^7)-1) {
```

(continues on next page)

(continued from previous page)

```
    res = 0x7f; OV = 1;
  } else if (res < -2^7) {
    res = 0x80; OV = 1;
  }
  Rd.B[x] = res[7:0];
} else {
  Rd = Rs1;
}
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KSLRA8 (unsigned long a, int b)

KSLRA8 (SIMD 8-bit Shift Left Logical with Saturation or Shift Right Arithmetic)

Type: SIMD

Syntax:

```
KSLRA8 Rd, Rs1, Rs2
KSLRA8.u Rd, Rs1, Rs2
```

Purpose :

Do 8-bit elements logical left (positive) or arithmetic right (negative) shift operation with Q7 saturation for the left shift. The `.u` form performs additional rounding up operations for the right shift.

Description :

The 8-bit data elements of Rs1 are left-shifted logically or right-shifted arithmetically based on the value of Rs2[3:0]. Rs2[3:0] is in the signed range of [-2^3, 2^3-1]. A positive Rs2[3:0] means logical left shift and a negative Rs2[3:0] means arithmetic right shift. The shift amount is the absolute value of Rs2[3:0]. However, the behavior of `Rs2[3:0]==-2^3 (0x8)` is defined to be equivalent to the behavior of `Rs2[3:0]==-(2^3-1) (0x9)`. The left-shifted results are saturated to the 8-bit signed integer range of [-2^7, 2^7-1]. For the `.u` form of the instruction, the right-shifted results are added a 1 to the most significant discarded bit position for rounding effect. After the shift, saturation, or rounding, the final results are written to Rd. If any saturation happens, this instruction sets the OV flag. The value of Rs2[31:4] will not affect this instruction.

Operations:

```
if (Rs2[3:0] < 0) {
  sa = -Rs2[3:0];
  sa = (sa == 8)? 7 : sa;
  if (`.u` form) {
    res[7:-1] = SE9(Rs1.B[x][7:sa-1]) + 1;
    Rd.B[x] = res[7:0];
  } else {
    Rd.B[x] = SE8(Rs1.B[x][7:sa]);
```

(continues on next page)

(continued from previous page)

```
  }
} else {
  sa = Rs2[2:0];
  res[(7+sa):0] = Rs1.B[x] <<(logic) sa;
  if (res > (2^7)-1) {
    res[7:0] = 0x7f; OV = 1;
  } else if (res < -2^7) {
    res[7:0] = 0x80; OV = 1;
  }
  Rd.B[x] = res[7:0];
}
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_KSLRA8_U (unsigned long a, int b)`

KSLRA8.u (SIMD 8-bit Shift Left Logical with Saturation or Rounding Shift Right Arithmetic)

Type: SIMD

Syntax:

```
KSLRA8 Rd, Rs1, Rs2
KSLRA8.u Rd, Rs1, Rs2
```

Purpose :

Do 8-bit elements logical left (positive) or arithmetic right (negative) shift operation with Q7 saturation for the left shift. The `.u` form performs additional rounding up operations for the right shift.

Description :

The 8-bit data elements of Rs1 are left-shifted logically or right-shifted arithmetically based on the value of Rs2[3:0]. Rs2[3:0] is in the signed range of [-2^3, 2^3-1]. A positive Rs2[3:0] means logical left shift and a negative Rs2[3:0] means arithmetic right shift. The shift amount is the absolute value of Rs2[3:0]. However, the behavior of `Rs2[3:0]==-2^3 (0x8)` is defined to be equivalent to the behavior of `Rs2[3:0]==-(2^3-1) (0x9)`. The left-shifted results are saturated to the 8-bit signed integer range of [-2^7, 2^7-1]. For the `.u` form of the instruction, the right-shifted results are added a 1 to the most significant discarded bit position for rounding effect. After the shift, saturation, or rounding, the final results are written to Rd. If any saturation happens, this instruction sets the OV flag. The value of Rs2[31:4] will not affect this instruction.

Operations:

```
if (Rs2[3:0] < 0) {
  sa = -Rs2[3:0];
  sa = (sa == 8)? 7 : sa;
  if (`.u` form) {
    res[7:-1] = SE9(Rs1.B[x][7:sa-1]) + 1;
```

(continues on next page)

(continued from previous page)

```
    Rd.B[x] = res[7:0];
  } else {
    Rd.B[x] = SE8(Rs1.B[x][7:sa]);
  }
} else {
  sa = Rs2[2:0];
  res[(7+sa):0] = Rs1.B[x] <<(logic) sa;
  if (res > (2^7)-1) {
    res[7:0] = 0x7f; OV = 1;
  } else if (res < -2^7) {
    res[7:0] = 0x80; OV = 1;
  }
  Rd.B[x] = res[7:0];
}
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SLL8 (unsigned long a, unsigned int b)

SLL8 (SIMD 8-bit Shift Left Logical)

Type: SIMD

Syntax:

```
SLL8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit elements logical left shift operations simultaneously. The shift amount is a variable from a GPR.

Description :

The 8-bit elements in Rs1 are left-shifted logically. And the results are written to Rd. The shifted out bits are filled with zero and the shift amount is specified by the low-order 3-bits of the value in the Rs2 register.

Operations:

```
sa = Rs2[2:0];
Rd.B[x] = Rs1.B[x] << sa;
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SRA8 (unsigned long a, unsigned int b)

SRA8 (SIMD 8-bit Shift Right Arithmetic)

Type: SIMD

Syntax:

```
SRA8 Rd, Rs1, Rs2
SRA8.u Rd, Rs1, Rs2
```

Purpose :

Do 8-bit element arithmetic right shift operations simultaneously. The shift amount is a variable from a GPR. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 8-bit data elements in Rs1 are right-shifted arithmetically, that is, the shifted out bits are filled with the sign-bit of the data elements. The shift amount is specified by the low-order 3-bits of the value in the Rs2 register. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 8-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = Rs2[2:0];
if (sa > 0) {
  if (`.u` form) { // SRA8.u
    res[7:-1] = SE9(Rs1.B[x][7:sa-1]) + 1;
    Rd.B[x] = res[7:0];
  } else { // SRA8
    Rd.B[x] = SE8(Rd.B[x][7:sa])
  }
} else {
  Rd = Rs1;
}
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- `a` – **[in]** unsigned long type of value stored in a
- `b` – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SRA8_U (unsigned long a, unsigned int b)

SRA8.u (SIMD 8-bit Rounding Shift Right Arithmetic)

Type: SIMD

Syntax:

```
SRA8 Rd, Rs1, Rs2
SRA8.u Rd, Rs1, Rs2
```

Purpose :

Do 8-bit element arithmetic right shift operations simultaneously. The shift amount is a variable from a GPR. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 8-bit data elements in Rs1 are right-shifted arithmetically, that is, the shifted out bits are filled with the sign-bit of the data elements. The shift amount is specified by the low-order 3-bits of the value in the Rs2 register. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 8-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = Rs2[2:0];
if (sa > 0) {
  if (`.u` form) { // SRA8.u
    res[7:-1] = SE9(Rs1.B[x][7:sa-1]) + 1;
    Rd.B[x] = res[7:0];
  } else { // SRA8
    Rd.B[x] = SE8(Rd.B[x][7:sa])
  }
} else {
  Rd = Rs1;
}
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_SRL8 (unsigned long a, unsigned int b)`

SRL8 (SIMD 8-bit Shift Right Logical)

Type: SIMD

Syntax:

```
SRL8 Rt, Ra, Rb
SRL8.u Rt, Ra, Rb
```

Purpose :

Do 8-bit elements logical right shift operations simultaneously. The shift amount is a variable from a GPR. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 8-bit data elements in Rs1 are right-shifted logically, that is, the shifted out bits are filled with zero. The shift amount is specified by the low-order 3-bits of the value in the Rs2 register. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 8-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = Rs2[2:0];
if (sa > 0) {
  if (`.u` form) { // SRL8.u
    res[8:0] = ZE9(Rs1.B[x][7:sa-1]) + 1;
    Rd.B[x] = res[8:1];
  } else { // SRL8
    Rd.B[x] = ZE8(Rs1.B[x][7:sa]);
  }
} else {
  Rd = Rs1;
}
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SRL8_U (unsigned long a, unsigned int b)

SRL8.u (SIMD 8-bit Rounding Shift Right Logical)

Type: SIMD

Syntax:

```
SRL8 Rt, Ra, Rb
SRL8.u Rt, Ra, Rb
```

Purpose :

Do 8-bit elements logical right shift operations simultaneously. The shift amount is a variable from a GPR. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 8-bit data elements in Rs1 are right-shifted logically, that is, the shifted out bits are filled with zero. The shift amount is specified by the low-order 3-bits of the value in the Rs2 register. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 8-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = Rs2[2:0];
if (sa > 0) {
  if (`.u` form) { // SRL8.u
    res[8:0] = ZE9(Rs1.B[x][7:sa-1]) + 1;
    Rd.B[x] = res[8:1];
  } else { // SRL8
    Rd.B[x] = ZE8(Rs1.B[x][7:sa]);
  }
} else {
  Rd = Rs1;
```

(continues on next page)

(continued from previous page)

```
}
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

SIMD 16-bit Compare Instructions

__STATIC_FORCEINLINE unsigned long __RV_CMPEQ16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_SCMPLE16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_SCMPLT16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UCMPLE16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UCMPLT16 (unsigned long a, unsigned long b)

group NMSIS_Core_DSP_Intrinsic_SIMD_16B_CMP

SIMD 16-bit Compare Instructions.

there are 5 SIMD 16-bit Compare instructions.

Functions

__STATIC_FORCEINLINE unsigned long __RV_CMPEQ16 (unsigned long a, unsigned long b)

CMPEQ16 (SIMD 16-bit Integer Compare Equal)

Type: SIMD

Syntax:

```
CMPEQ16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit integer elements equal comparisons simultaneously.

Description :

This instruction compares the 16-bit integer elements in Rs1 with the 16-bit integer elements in Rs2 to see if they are equal. If they are equal, the result is 0xFFFF; otherwise, the result is 0x0. The 16-bit element comparison results are written to Rt.

Note :

This instruction can be used for either signed or unsigned numbers.

Operations:

```
Rd.H[x] = (Rs1.H[x] == Rs2.H[x])? 0xffff : 0x0;
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SCMPLE16 (unsigned long a, unsigned long b)

SCMPLE16 (SIMD 16-bit Signed Compare Less Than & Equal)

Type: SIMD

Syntax:

```
SCMPLE16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer elements less than & equal comparisons simultaneously.

Description :

This instruction compares the 16-bit signed integer elements in Rs1 with the 16-bit signed integer elements in Rs2 to see if the one in Rs1 is less than or equal to the one in Rs2. If it is true, the result is 0xFFFF; otherwise, the result is 0x0. The element comparison results are written to Rd.

Operations:

```
Rd.H[x] = (Rs1.H[x] {le} Rs2.H[x])? 0xffff : 0x0;
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SCMPLT16 (unsigned long a, unsigned long b)

SCMPLT16 (SIMD 16-bit Signed Compare Less Than)

Type: SIMD

Syntax:

```
SCMPLT16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer elements less than comparisons simultaneously.

Description :

This instruction compares the 16-bit signed integer elements in Rs1 with the two 16- bit signed integer elements in Rs2 to see if the one in Rs1 is less than the one in Rs2. If it is true, the result is 0xFFFF; otherwise, the result is 0x0. The element comparison results are written to Rd.

Operations:

```
Rd.H[x] = (Rs1.H[x] < Rs2.H[x])? 0xffff : 0x0;
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- `a` – **[in]** unsigned long type of value stored in a
- `b` – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_UCMPLE16 (unsigned long a, unsigned long b)`

UCMPLE16 (SIMD 16-bit Unsigned Compare Less Than & Equal)

Type: SIMD

Syntax:

```
UCMPLE16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit unsigned integer elements less than & equal comparisons simultaneously.

Description :

This instruction compares the 16-bit unsigned integer elements in Rs1 with the 16-bit unsigned integer elements in Rs2 to see if the one in Rs1 is less than or equal to the one in Rs2. If it is true, the result is 0xFFFF; otherwise, the result is 0x0. The element comparison results are written to Rd.

Operations:

```
Rd.H[x] = (Rs1.H[x] <=u Rs2.H[x])? 0xffff : 0x0;
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- `a` – **[in]** unsigned long type of value stored in a
- `b` – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_UCMPLT16 (unsigned long a, unsigned long b)`

UCMPLT16 (SIMD 16-bit Unsigned Compare Less Than)

Type: SIMD

Syntax:

```
UCMPLT16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit unsigned integer elements less than comparisons simultaneously.

Description :

This instruction compares the 16-bit unsigned integer elements in Rs1 with the 16-bit unsigned integer elements in Rs2 to see if the one in Rs1 is less than the one in Rs2. If it is true, the result is 0xFFFF; otherwise, the result is 0x0. The element comparison results are written to Rd.

Operations:

```
Rd.H[x] = (Rs1.H[x] <u Rs2.H[x])? 0xffff : 0x0;
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

SIMD 8-bit Compare Instructions

`__STATIC_FORCEINLINE unsigned long __RV_CMPEQ8 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_SCMPLE8 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_SCMPLT8 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_UCMPLE8 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_UCMPLT8 (unsigned long a, unsigned long b)`

group `NMSIS_Core_DSP_Intrinsic_SIMD_8B_CMP`

SIMD 8-bit Compare Instructions.

there are 5 SIMD 8-bit Compare instructions.

Functions

__STATIC_FORCEINLINE unsigned long __RV_CMPEQ8 (unsigned long a, unsigned long b)

CMPEQ8 (SIMD 8-bit Integer Compare Equal)

Type: SIMD

Syntax:

```
CMPEQ8 Rs, Rs1, Rs2
```

Purpose :

Do 8-bit integer elements equal comparisons simultaneously.

Description :

This instruction compares the 8-bit integer elements in Rs1 with the 8-bit integer elements in Rs2 to see if they are equal. If they are equal, the result is 0xFF; otherwise, the result is 0x0. The 8-bit element comparison results are written to Rd.

Note :

This instruction can be used for either signed or unsigned numbers.

Operations:

```
Rd.B[x] = (Rs1.B[x] == Rs2.B[x])? 0xff : 0x0;
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SCMPLE8 (unsigned long a, unsigned long b)

SCMPLE8 (SIMD 8-bit Signed Compare Less Than & Equal)

Type: SIMD

Syntax:

```
SCMPLE8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit signed integer elements less than & equal comparisons simultaneously.

Description :

This instruction compares the 8-bit signed integer elements in Rs1 with the 8-bit signed integer elements in Rs2 to see if the one in Rs1 is less than or equal to the one in Rs2. If it is true, the result is 0xFF; otherwise, the result is 0x0. The element comparison results are written to Rd

Operations:

```
Rd.B[x] = (Rs1.B[x] {le} Rs2.B[x])? 0xff : 0x0;
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SCMPLT8 (unsigned long a, unsigned long b)

SCMPLT8 (SIMD 8-bit Signed Compare Less Than)

Type: SIMD

Syntax:

```
SCMPLT8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit signed integer elements less than comparisons simultaneously.

Description :

This instruction compares the 8-bit signed integer elements in Rs1 with the 8-bit signed integer elements in Rs2 to see if the one in Rs1 is less than the one in Rs2. If it is true, the result is 0xFF; otherwise, the result is 0x0. The element comparison results are written to Rd.

Operations:

```
Rd.B[x] = (Rs1.B[x] < Rs2.B[x])? 0xff : 0x0;
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UCMPLE8 (unsigned long a, unsigned long b)

UCMPLE8 (SIMD 8-bit Unsigned Compare Less Than & Equal)

Type: SIMD

Syntax:

```
UCMPLE8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit unsigned integer elements less than & equal comparisons simultaneously.

Description :

This instruction compares the 8-bit unsigned integer elements in Rs1 with the 8-bit unsigned integer elements in Rs2 to see if the one in Rs1 is less than or equal to the one in Rs2. If it is true, the result is 0xFF; otherwise, the result is 0x0. The four comparison results are written to Rd.

Operations:

```
Rd.B[x] = (Rs1.B[x] <=u Rs2.B[x])? 0xff : 0x0;
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- a – **[in]** unsigned long type of value stored in a
- b – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UCMPLT8 (unsigned long a, unsigned long b)

UCMPLT8 (SIMD 8-bit Unsigned Compare Less Than)

Type: SIMD

Syntax:

```
UCMPLT8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit unsigned integer elements less than comparisons simultaneously.

Description :

This instruction compares the 8-bit unsigned integer elements in Rs1 with the 8-bit unsigned integer elements in Rs2 to see if the one in Rs1 is less than the one in Rs2. If it is true, the result is 0xFF; otherwise, the result is 0x0. The element comparison results are written to Rd.

Operations:

```
Rd.B[x] = (Rs1.B[x] <u Rs2.B[x])? 0xff : 0x0;
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- a – **[in]** unsigned long type of value stored in a
- b – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

SIMD 16-bit Multiply Instructions

__STATIC_FORCEINLINE unsigned long __RV_KHM16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KHMX16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long long __RV_SMUL16 (unsigned int a, unsigned int b)

__STATIC_FORCEINLINE unsigned long long __RV_SMULX16 (unsigned int a, unsigned int b)

__STATIC_FORCEINLINE unsigned long long __RV_UMUL16 (unsigned int a, unsigned int b)

__STATIC_FORCEINLINE unsigned long long __RV_UMULX16 (unsigned int a, unsigned int b)

group NMSIS_Core_DSP_Intrinsic_SIMD_16B_MULTIPLY

SIMD 16-bit Multiply Instructions.

there are 6 SIMD 16-bit Multiply instructions.

Functions

__STATIC_FORCEINLINE unsigned long __RV_KHM16 (unsigned long a, unsigned long b)

KHM16 (SIMD Signed Saturating Q15 Multiply)

Type: SIMD

Syntax:

```
KHM16 Rd, Rs1, Rs2
KHMX16 Rd, Rs1, Rs2
```

Purpose :

Do Q15xQ15 element multiplications simultaneously. The Q30 results are then reduced to Q15 numbers again.

Description :

For the KHM16 instruction, multiply the top 16-bit Q15 content of 32-bit chunks in Rs1 with the top 16-bit Q15 content of 32-bit chunks in Rs2. At the same time, multiply the bottom 16-bit Q15 content of 32-bit chunks in Rs1 with the bottom 16-bit Q15 content of 32-bit chunks in Rs2. For the KHMX16 instruction, multiply the top 16-bit Q15 content of 32-bit chunks in Rs1 with the bottom 16-bit Q15 content of 32-bit chunks in Rs2. At the same time, multiply the bottom 16-bit Q15 content of 32-bit chunks in Rs1 with the top 16-bit Q15 content of 32-bit chunks in Rs2. The Q30 results are then right-shifted 15-bits and saturated into Q15 values. The Q15 results are then written into Rd. When both the two Q15 inputs of a multiplication are 0x8000, saturation will happen. The result will be saturated to 0x7FFF and the overflow flag OV will be set.

Operations:

```
if (is `KHM16`) {
  op1t = Rs1.H[x+1]; op2t = Rs2.H[x+1]; // top
  op1b = Rs1.H[x]; op2b = Rs2.H[x]; // bottom
} else if (is `KHMX16`) {
  op1t = Rs1.H[x+1]; op2t = Rs2.H[x]; // Rs1 top
  op1b = Rs1.H[x]; op2b = Rs2.H[x+1]; // Rs1 bottom
}
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  if (0x8000 != aop | 0x8000 != bop) {
    res = (aop s* bop) >> 15;
  } else {
    res= 0x7FFF;
    OV = 1;
  }
}
Rd.W[x/2] = concat(rest, resb);
for RV32: x=0
for RV64: x=0,2
```

Parameters

- `a` – **[in]** unsigned long type of value stored in a
- `b` – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_KHMX16 (unsigned long a, unsigned long b)`

KHMX16 (SIMD Signed Saturating Crossed Q15 Multiply)

Type: SIMD

Syntax:

```
KHM16 Rd, Rs1, Rs2
KHMX16 Rd, Rs1, Rs2
```

Purpose :

Do Q15xQ15 element multiplications simultaneously. The Q30 results are then reduced to Q15 numbers again.

Description :

For the `KHM16` instruction, multiply the top 16-bit Q15 content of 32-bit chunks in Rs1 with the top 16-bit Q15 content of 32-bit chunks in Rs2. At the same time, multiply the bottom 16-bit Q15 content of 32-bit chunks in Rs1 with the bottom 16-bit Q15 content of 32-bit chunks in Rs2. For the `KHMX16` instruction, multiply the top 16-bit Q15 content of 32-bit chunks in Rs1 with the bottom 16-bit Q15 content of 32-bit chunks in Rs2. At the same time, multiply the bottom 16-bit Q15 content of 32-bit chunks in Rs1 with the top 16-bit Q15 content of 32-bit chunks in Rs2. The Q30 results are then right-shifted 15-bits and saturated into Q15 values. The Q15 results are then written into Rd. When both the two Q15 inputs of a multiplication are 0x8000, saturation will happen. The result will be saturated to 0x7FFF and the overflow flag OV will be set.

Operations:

```
if (is `KHM16`) {
  op1t = Rs1.H[x+1]; op2t = Rs2.H[x+1]; // top
  op1b = Rs1.H[x]; op2b = Rs2.H[x]; // bottom
} else if (is `KHMX16`) {
  op1t = Rs1.H[x+1]; op2t = Rs2.H[x]; // Rs1 top
  op1b = Rs1.H[x]; op2b = Rs2.H[x+1]; // Rs1 bottom
}
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  if (0x8000 != aop | 0x8000 != bop) {
    res = (aop s* bop) >> 15;
  } else {
    res= 0x7FFF;
    OV = 1;
  }
}
Rd.W[x/2] = concat(rest, resb);
for RV32: x=0
for RV64: x=0,2
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long long __RV_SMUL16 (unsigned int a, unsigned int b)

SMUL16 (SIMD Signed 16-bit Multiply)

Type: SIMD

Syntax:

```
SMUL16 Rd, Rs1, Rs2
SMULX16 Rd, Rs1, Rs2
```

Purpose :

Do signed 16-bit multiplications and generate two 32-bit results simultaneously.

RV32 Description :

For the SMUL16 instruction, multiply the top 16-bit Q15 content of Rs1 with the top 16-bit Q15 content of Rs2. At the same time, multiply the bottom 16-bit Q15 content of Rs1 with the bottom 16-bit Q15 content of Rs2. For the SMULX16 instruction, multiply the top 16-bit Q15 content of Rs1 with the bottom 16-bit Q15 content of Rs2. At the same time, multiply the bottom 16-bit Q15 content of Rs1 with the top 16- bit Q15 content of Rs2. The two Q30 results are then written into an even/odd pair of registers specified by Rd(4,1). Rd(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd 2d+1 register of the pair contains the 32-bit result calculated from the top part of Rs1 and the even 2d register of the pair contains the 32-bit result calculated from the bottom part of Rs1.

RV64 Description :

For the SMUL16 instruction, multiply the top 16-bit Q15 content of the lower 32-bit word in Rs1 with the top 16-bit Q15 content of the lower 32-bit word in Rs2. At the same time, multiply the bottom 16-bit Q15 content of the lower 32-bit word in Rs1 with the bottom 16-bit Q15 content of the lower 32-bit word in Rs2.

For the SMULX16 instruction, multiply the top 16-bit Q15 content of the lower 32-bit word in Rs1 with the bottom 16-bit Q15 content of the lower 32-bit word in Rs2. At the same time, multiply the bottom 16-bit Q15 content of the lower 32-bit word in Rs1 with the top 16-bit Q15 content of the lower 32-bit word in Rs2. The two 32-bit Q30 results are then written into Rd. The result calculated from the top 16-bit of the lower 32-bit word in Rs1 is written to Rd.W[1]. And the result calculated from the bottom 16-bit of the lower 32-bit word in Rs1 is written to Rd.W[0]

Operations:

```
* RV32:
if (is `SMUL16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[1]; // top
  op1b = Rs1.H[0]; op2b = Rs2.H[0]; // bottom
} else if (is `SMULX16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[0]; // Rs1 top
  op1b = Rs1.H[0]; op2b = Rs2.H[1]; // Rs1 bottom
}
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  res = aop s* bop;
}
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
R[t_H] = rest;
R[t_L] = resb;
* RV64:
if (is `SMUL16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[1]; // top
  op1b = Rs1.H[0]; op2b = Rs2.H[0]; // bottom
} else if (is `SMULX16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[0]; // Rs1 top
  op1b = Rs1.H[0]; op2b = Rs2.H[1]; // Rs1 bottom
}
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  res = aop s* bop;
}
Rd.W[1] = rest;
Rd.W[0] = resb;
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_SMULX16 (unsigned int a, unsigned int b)

SMULX16 (SIMD Signed Crossed 16-bit Multiply)

Type: SIMD

Syntax:

```
SMUL16 Rd, Rs1, Rs2
SMULX16 Rd, Rs1, Rs2
```

Purpose :

Do signed 16-bit multiplications and generate two 32-bit results simultaneously.

RV32 Description :

For the `SMUL16` instruction, multiply the top 16-bit Q15 content of Rs1 with the top 16-bit Q15 content of Rs2. At the same time, multiply the bottom 16-bit Q15 content of Rs1 with the bottom 16-bit Q15 content of Rs2. For the `SMULX16` instruction, multiply the top 16-bit Q15 content of Rs1 with the bottom 16-bit Q15 content of Rs2. At the same time, multiply the bottom 16-bit Q15 content of Rs1 with the top 16- bit Q15 content of Rs2. The two Q30 results are then written into an even/odd pair of registers specified by Rd(4,1). Rd(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the 32-bit result calculated from the top part of Rs1 and the even `2d` register of the pair contains the 32-bit result calculated from the bottom part of Rs1.

RV64 Description :

For the `SMUL16` instruction, multiply the top 16-bit Q15 content of the lower 32-bit word in Rs1 with the top 16-bit Q15 content of the lower 32-bit word in Rs2. At the same time, multiply the bottom 16-bit Q15 content of the lower 32-bit word in Rs1 with the bottom 16-bit Q15 content of the lower 32-bit word in Rs2. For the `SMULX16` instruction, multiply the top 16-bit Q15 content of the lower 32-bit word in Rs1 with the bottom 16-bit Q15 content of the lower 32-bit word in Rs2. At the same time, multiply the bottom 16-bit Q15 content of the lower 32-bit word in Rs1 with the top 16-bit Q15 content of the lower 32-bit word in Rs2. The two 32-bit Q30 results are then written into Rd. The result calculated from the top 16-bit of the lower 32-bit word in Rs1 is written to Rd.W[1]. And the result calculated from the bottom 16-bit of the lower 32-bit word in Rs1 is written to Rd.W[0]

Operations:

```
* RV32:
if (is `SMUL16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[1]; // top
  op1b = Rs1.H[0]; op2b = Rs2.H[0]; // bottom
} else if (is `SMULX16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[0]; // Rs1 top
  op1b = Rs1.H[0]; op2b = Rs2.H[1]; // Rs1 bottom
}
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  res = aop s* bop;
}
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
R[t_H] = rest;
R[t_L] = resb;
* RV64:
if (is `SMUL16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[1]; // top
  op1b = Rs1.H[0]; op2b = Rs2.H[0]; // bottom
} else if (is `SMULX16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[0]; // Rs1 top
  op1b = Rs1.H[0]; op2b = Rs2.H[1]; // Rs1 bottom
}
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  res = aop s* bop;
}
Rd.W[1] = rest;
Rd.W[0] = resb;
```

Parameters

- `a` – **[in]** unsigned int type of value stored in a
- `b` – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long long type

`__STATIC_FORCEINLINE unsigned long long __RV_UMUL16 (unsigned int a, unsigned int b)`

UMUL16 (SIMD Unsigned 16-bit Multiply)

Type: SIMD

Syntax:

```
UMUL16 Rd, Rs1, Rs2
UMULX16 Rd, Rs1, Rs2
```

Purpose :

Do unsigned 16-bit multiplications and generate two 32-bit results simultaneously.

RV32 Description :

For the `UMUL16` instruction, multiply the top 16-bit U16 content of Rs1 with the top 16-bit U16 content of Rs2. At the same time, multiply the bottom 16-bit U16 content of Rs1 with the bottom 16-bit U16 content of Rs2. For the `UMULX16` instruction, multiply the top 16-bit U16 content of Rs1 with the bottom 16-bit U16 content of Rs2. At the same time, multiply the bottom 16-bit U16 content of Rs1 with the top 16- bit U16 content of Rs2. The two U32 results are then written into an even/odd pair of registers specified by Rd(4,1). Rd(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the 32-bit result calculated from the top part of Rs1 and the even `2d` register of the pair contains the 32-bit result calculated from the bottom part of Rs1.

RV64 Description :

For the `UMUL16` instruction, multiply the top 16-bit U16 content of the lower 32-bit word in Rs1 with the top 16-bit U16 content of the lower 32-bit word in Rs2. At the same time, multiply the bottom 16-bit U16 content of the lower 32-bit word in Rs1 with the bottom 16-bit U16 content of the lower 32-bit word in Rs2. For the `UMULX16` instruction, multiply the top 16-bit U16 content of the lower 32-bit word in Rs1 with the bottom 16-bit U16 content of the lower 32-bit word in Rs2. At the same time, multiply the bottom 16-bit U16 content of the lower 32-bit word in Rs1 with the top 16-bit U16 content of the lower 32-bit word in Rs2. The two 32-bit U32 results are then written into Rd. The result calculated from the top 16-bit of the lower 32-bit word in Rs1 is written to Rd.W[1]. And the result calculated from the bottom 16-bit of the lower 32-bit word in Rs1 is written to Rd.W[0]

Operations:

```
* RV32:
if (is `UMUL16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[1]; // top
  op1b = Rs1.H[0]; op2b = Rs2.H[0]; // bottom
} else if (is `UMULX16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[0]; // Rs1 top
  op1b = Rs1.H[0]; op2b = Rs2.H[1]; // Rs1 bottom
}
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  res = aop u* bop;
```

(continues on next page)

(continued from previous page)

```
}
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
R[t_H] = rest;
R[t_L] = resb;
* RV64:
if (is `UMUL16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[1]; // top
  op1b = Rs1.H[0]; op2b = Rs2.H[0]; // bottom
} else if (is `UMULX16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[0]; // Rs1 top
  op1b = Rs1.H[0]; op2b = Rs2.H[1]; // Rs1 bottom
}
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  res = aop u* bop;
}
Rd.W[1] = rest;
Rd.W[0] = resb;
```

Parameters

- `a` – **[in]** unsigned int type of value stored in a
- `b` – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long long type

`__STATIC_FORCEINLINE unsigned long long __RV_UMULX16 (unsigned int a, unsigned int b)`

UMULX16 (SIMD Unsigned Crossed 16-bit Multiply)

Type: SIMD

Syntax:

```
UMUL16 Rd, Rs1, Rs2
UMULX16 Rd, Rs1, Rs2
```

Purpose :

Do unsigned 16-bit multiplications and generate two 32-bit results simultaneously.

RV32 Description :

For the `UMUL16` instruction, multiply the top 16-bit U16 content of Rs1 with the top 16-bit U16 content of Rs2. At the same time, multiply the bottom 16-bit U16 content of Rs1 with the bottom 16-bit U16 content of Rs2. For the `UMULX16` instruction, multiply the top 16-bit U16 content of Rs1 with the bottom 16-bit U16 content of Rs2. At the same time, multiply the bottom 16-bit U16 content of Rs1 with the top 16- bit U16 content of Rs2. The two U32 results are then written into an even/odd pair of registers specified by Rd(4,1). Rd(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the 32-bit result calculated from the top part of Rs1 and the even `2d` register of the pair contains the 32-bit result calculated from the bottom part of Rs1.

RV64 Description :

For the `UMUL16` instruction, multiply the top 16-bit U16 content of the lower 32-bit word in Rs1 with the top 16-bit U16 content of the lower 32-bit word in Rs2. At the same time, multiply the bottom 16-bit U16 content of the lower 32-bit word in Rs1 with the bottom 16-bit U16 content of the lower 32-bit word in Rs2. For the UMULX16 instruction, multiply the top 16-bit U16 content of the lower 32-bit word in Rs1 with the bottom 16-bit U16 content of the lower 32-bit word in Rs2. At the same time, multiply the bottom 16-bit U16 content of the lower 32-bit word in Rs1 with the top 16-bit U16 content of the lower 32-bit word in Rs2. The two 32-bit U32 results are then written into Rd. The result calculated from the top 16-bit of the lower 32-bit word in Rs1 is written to Rd.W[1]. And the result calculated from the bottom 16-bit of the lower 32-bit word in Rs1 is written to Rd.W[0]

Operations:

```
* RV32:
if (is `UMUL16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[1]; // top
  op1b = Rs1.H[0]; op2b = Rs2.H[0]; // bottom
} else if (is `UMULX16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[0]; // Rs1 top
  op1b = Rs1.H[0]; op2b = Rs2.H[1]; // Rs1 bottom
}
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  res = aop u* bop;
}
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
R[t_H] = rest;
R[t_L] = resb;
* RV64:
if (is `UMUL16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[1]; // top
  op1b = Rs1.H[0]; op2b = Rs2.H[0]; // bottom
} else if (is `UMULX16`) {
  op1t = Rs1.H[1]; op2t = Rs2.H[0]; // Rs1 top
  op1b = Rs1.H[0]; op2b = Rs2.H[1]; // Rs1 bottom
}
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  res = aop u* bop;
}
Rd.W[1] = rest;
Rd.W[0] = resb;
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long long type

SIMD 8-bit Multiply Instructions

__STATIC_FORCEINLINE unsigned long __RV_KHM8 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KHMX8 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long long __RV_SMUL8 (unsigned int a, unsigned int b)

__STATIC_FORCEINLINE unsigned long long __RV_SMULX8 (unsigned int a, unsigned int b)

__STATIC_FORCEINLINE unsigned long long __RV_UMUL8 (unsigned int a, unsigned int b)

__STATIC_FORCEINLINE unsigned long long __RV_UMULX8 (unsigned int a, unsigned int b)

group NMSIS_Core_DSP_Intrinsic_SIMD_8B_MULTIPLY

SIMD 8-bit Multiply Instructions.

there are 6 SIMD 8-bit Multiply instructions.

Functions

__STATIC_FORCEINLINE unsigned long __RV_KHM8 (unsigned long a, unsigned long b)

KHM8 (SIMD Signed Saturating Q7 Multiply)

Type: SIMD

Syntax:

```
KHM8 Rd, Rs1, Rs2
KHMX8 Rd, Rs1, Rs2
```

Purpose :

Do Q7xQ7 element multiplications simultaneously. The Q14 results are then reduced to Q7 numbers again.

Description :

For the KHM8 instruction, multiply the top 8-bit Q7 content of 16-bit chunks in Rs1 with the top 8-bit Q7 content of 16-bit chunks in Rs2. At the same time, multiply the bottom 8-bit Q7 content of 16-bit chunks in Rs1 with the bottom 8-bit Q7 content of 16-bit chunks in Rs2. For the KHMX16 instruction, multiply the top 8-bit Q7 content of 16-bit chunks in Rs1 with the bottom 8-bit Q7 content of 16-bit chunks in Rs2. At the same time, multiply the bottom 8-bit Q7 content of 16-bit chunks in Rs1 with the top 8-bit Q7 content of 16-bit chunks in Rs2. The Q14 results are then right-shifted 7-bits and saturated into Q7 values. The Q7 results are then written into Rd. When both the two Q7 inputs of a multiplication are 0x80, saturation will happen. The result will be saturated to 0x7F and the overflow flag OV will be set.

Operations:

```
if (is `KHM8`) {
  op1t = Rs1.B[x+1]; op2t = Rs2.B[x+1]; // top
  op1b = Rs1.B[x]; op2b = Rs2.B[x]; // bottom
```

(continues on next page)

(continued from previous page)

```
} else if (is `KHMX8`) {
  op1t = Rs1.H[x+1]; op2t = Rs2.H[x]; // Rs1 top
  op1b = Rs1.H[x]; op2b = Rs2.H[x+1]; // Rs1 bottom
}
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  if (0x80 != aop | 0x80 != bop) {
    res = (aop s* bop) >> 7;
  } else {
    res= 0x7F;
    OV = 1;
  }
}
Rd.H[x/2] = concat(rest, resb);
for RV32, x=0,2
for RV64, x=0,2,4,6
```

Parameters

- `a` – **[in]** unsigned long type of value stored in a
- `b` – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_KHMX8 (unsigned long a, unsigned long b)`

KHMX8 (SIMD Signed Saturating Crossed Q7 Multiply)

Type: SIMD

Syntax:

```
KHM8 Rd, Rs1, Rs2
KHMX8 Rd, Rs1, Rs2
```

Purpose :

Do Q7xQ7 element multiplications simultaneously. The Q14 results are then reduced to Q7 numbers again.

Description :

For the `KHM8` instruction, multiply the top 8-bit Q7 content of 16-bit chunks in Rs1 with the top 8-bit Q7 content of 16-bit chunks in Rs2. At the same time, multiply the bottom 8-bit Q7 content of 16-bit chunks in Rs1 with the bottom 8-bit Q7 content of 16-bit chunks in Rs2. For the `KHMX16` instruction, multiply the top 8-bit Q7 content of 16-bit chunks in Rs1 with the bottom 8-bit Q7 content of 16-bit chunks in Rs2. At the same time, multiply the bottom 8-bit Q7 content of 16-bit chunks in Rs1 with the top 8-bit Q7 content of 16-bit chunks in Rs2. The Q14 results are then right-shifted 7-bits and saturated into Q7 values. The Q7 results are then written into Rd. When both the two Q7 inputs of a multiplication are 0x80, saturation will happen. The result will be saturated to 0x7F and the overflow flag OV will be set.

Operations:

```
if (is `KHM8`) {
  op1t = Rs1.B[x+1]; op2t = Rs2.B[x+1]; // top
  op1b = Rs1.B[x]; op2b = Rs2.B[x]; // bottom
} else if (is `KHMX8`) {
  op1t = Rs1.H[x+1]; op2t = Rs2.H[x]; // Rs1 top
```

(continues on next page)

(continued from previous page)

```
  op1b = Rs1.H[x]; op2b = Rs2.H[x+1]; // Rs1 bottom
}
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  if (0x80 != aop | 0x80 != bop) {
    res = (aop s* bop) >> 7;
  } else {
    res= 0x7F;
    OV = 1;
  }
}
Rd.H[x/2] = concat(rest, resb);
for RV32, x=0,2
for RV64, x=0,2,4,6
```

Parameters

- a – **[in]** unsigned long type of value stored in a
- b – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long long __RV_SMUL8 (unsigned int a, unsigned int b)`

SMUL8 (SIMD Signed 8-bit Multiply)

Type: SIMD

Syntax:

```
SMUL8 Rd, Rs1, Rs2
SMULX8 Rd, Rs1, Rs2
```

Purpose :

Do signed 8-bit multiplications and generate four 16-bit results simultaneously.

RV32 Description :

For the `SMUL8` instruction, multiply the 8-bit data elements of Rs1 with the corresponding 8-bit data elements of Rs2. For the `SMULX8` instruction, multiply the first and second 8-bit data elements of Rs1 with the second and first 8-bit data elements of Rs2. At the same time, multiply the third and fourth 8-bit data elements of Rs1 with the fourth and third 8-bit data elements of Rs2. The four 16-bit results are then written into an even/odd pair of registers specified by Rd(4,1). Rd(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the two 16-bit results calculated from the top part of Rs1 and the even `2d` register of the pair contains the two 16-bit results calculated from the bottom part of Rs1.

RV64 Description :

For the `SMUL8` instruction, multiply the 8-bit data elements of Rs1 with the corresponding 8-bit data elements of Rs2. For the `SMULX8` instruction, multiply the first and second 8-bit data elements of Rs1 with the second and first 8-bit data elements of Rs2. At the same time, multiply the third and fourth 8-bit data elements of Rs1 with the fourth and third 8-bit data elements of Rs2. The four 16-bit results are then written into Rd. The Rd.W[1] contains the two 16-bit results calculated from the top part of Rs1 and the Rd.W[0] contains the two 16-bit results calculated from the bottom part of Rs1.

Operations:

```
* RV32:
if (is `SMUL8`) {
  op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x+1]; // top
  op1b[x/2] = Rs1.B[x]; op2b[x/2] = Rs2.B[x]; // bottom
} else if (is `SMULX8`) {
  op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x]; // Rs1 top
  op1b[x/2] = Rs1.B[x]; op2b[x/2] = Rs2.B[x+1]; // Rs1 bottom
}
rest[x/2] = op1t[x/2] s* op2t[x/2];
resb[x/2] = op1b[x/2] s* op2b[x/2];
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
R[t_H].H[1] = rest[1]; R[t_H].H[0] = resb[1];
R[t_L].H[1] = rest[0]; R[t_L].H[0] = resb[0];
x = 0 and 2
* RV64:
if (is `SMUL8`) {
  op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x+1]; // top
  op1b[x/2] = Rs1.B[x]; op2b[x/2] = Rs2.B[x]; // bottom
} else if (is `SMULX8`) {
  op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x]; // Rs1 top
  op1b[x/2] = Rs1.B[x]; op2b[x/2] = Rs2.B[x+1]; // Rs1 bottom
}
rest[x/2] = op1t[x/2] s* op2t[x/2];
resb[x/2] = op1b[x/2] s* op2b[x/2];
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
Rd.W[1].H[1] = rest[1]; Rd.W[1].H[0] = resb[1];
Rd.W[0].H[1] = rest[0]; Rd.W[0].H[0] = resb[0];
x = 0 and 2
```

Parameters

- `a` – **[in]** unsigned int type of value stored in a
- `b` – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long long type

`__STATIC_FORCEINLINE unsigned long long __RV_SMULX8 (unsigned int a, unsigned int b)`

SMULX8 (SIMD Signed Crossed 8-bit Multiply)

Type: SIMD

Syntax:

```
SMUL8 Rd, Rs1, Rs2
SMULX8 Rd, Rs1, Rs2
```

Purpose :

Do signed 8-bit multiplications and generate four 16-bit results simultaneously.

RV32 Description :

For the `SMUL8` instruction, multiply the 8-bit data elements of Rs1 with the corresponding 8-bit data elements of Rs2. For the `SMULX8` instruction, multiply the first and second 8-bit data elements of Rs1 with the second and first 8-bit data elements of Rs2. At the same time, multiply the third and fourth 8-bit data elements of Rs1 with the fourth and third 8-bit data elements of Rs2. The four 16-bit results are then written into an even/odd pair of registers specified by Rd(4,1). Rd(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd 2d+1 register of the pair contains the two 16-bit results calculated from the top part of Rs1 and the even 2d register of the pair contains the two 16-bit results calculated from the bottom part of Rs1.

RV64 Description :

For the SMUL8 instruction, multiply the 8-bit data elements of Rs1 with the corresponding 8-bit data elements of Rs2. For the SMULX8 instruction, multiply the first and second 8-bit data elements of Rs1 with the second and first 8-bit data elements of Rs2. At the same time, multiply the third and fourth 8-bit data elements of Rs1 with the fourth and third 8-bit data elements of Rs2. The four 16-bit results are then written into Rd. The Rd.W[1] contains the two 16-bit results calculated from the top part of Rs1 and the Rd.W[0] contains the two 16-bit results calculated from the bottom part of Rs1.

Operations:

```
* RV32:
if (is `SMUL8`) {
  op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x+1]; // top
  op1b[x/2] = Rs1.B[x]; op2b[x/2] = Rs2.B[x]; // bottom
} else if (is `SMULX8`) {
  op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x]; // Rs1 top
  op1b[x/2] = Rs1.B[x]; op2b[x/2] = Rs2.B[x+1]; // Rs1 bottom
}
rest[x/2] = op1t[x/2] s* op2t[x/2];
resb[x/2] = op1b[x/2] s* op2b[x/2];
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
R[t_H].H[1] = rest[1]; R[t_H].H[0] = resb[1];
R[t_L].H[1] = rest[0]; R[t_L].H[0] = resb[0];
x = 0 and 2
* RV64:
if (is `SMUL8`) {
  op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x+1]; // top
  op1b[x/2] = Rs1.B[x]; op2b[x/2] = Rs2.B[x]; // bottom
} else if (is `SMULX8`) {
  op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x]; // Rs1 top
  op1b[x/2] = Rs1.B[x]; op2b[x/2] = Rs2.B[x+1]; // Rs1 bottom
}
rest[x/2] = op1t[x/2] s* op2t[x/2];
resb[x/2] = op1b[x/2] s* op2b[x/2];
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
Rd.W[1].H[1] = rest[1]; Rd.W[1].H[0] = resb[1];
Rd.W[0].H[1] = rest[0]; Rd.W[0].H[0] = resb[0];
x = 0 and 2
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_UMUL8 (unsigned int a, unsigned int b)

UMUL8 (SIMD Unsigned 8-bit Multiply)

Type: SIMD

Syntax:

```
UMUL8 Rd, Rs1, Rs2
UMULX8 Rd, Rs1, Rs2
```

Purpose :

Do unsigned 8-bit multiplications and generate four 16-bit results simultaneously.

RV32 Description :

For the UMUL8 instruction, multiply the unsigned 8-bit data elements of Rs1 with the corresponding unsigned 8-bit data elements of Rs2. For the UMULX8 instruction, multiply the first and second unsigned 8-bit data elements of Rs1 with the second and first unsigned 8-bit data elements of Rs2. At the same time, multiply the third and fourth unsigned 8-bit data elements of Rs1 with the fourth and third unsigned 8-bit data elements of Rs2. The four 16-bit results are then written into an even/odd pair of registers specified by Rd(4,1). Rd(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd 2d+1 register of the pair contains the two 16-bit results calculated from the top part of Rs1 and the even 2d register of the pair contains the two 16-bit results calculated from the bottom part of Rs1.

RV64 Description :

For the UMUL8 instruction, multiply the unsigned 8-bit data elements of Rs1 with the corresponding unsigned 8-bit data elements of Rs2. For the UMULX8 instruction, multiply the first and second unsigned 8-bit data elements of Rs1 with the second and first unsigned 8-bit data elements of Rs2. At the same time, multiply the third and fourth unsigned 8-bit data elements of Rs1 with the fourth and third unsigned 8-bit data elements of Rs2. The four 16-bit results are then written into Rd. The Rd.W[1] contains the two 16-bit results calculated from the top part of Rs1 and the Rd.W[0] contains the two 16-bit results calculated from the bottom part of Rs1.

Operations:

```
* RV32:
if (is `UMUL8`) {
  op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x+1]; // top
  op1b[x/2] = Rs1.B[x]; op2b[x/2] = Rs2.B[x]; // bottom
} else if (is `UMULX8`) {
  op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x]; // Rs1 top
  op1b[x/2] = Rs1.B[x]; op2b[x/2] = Rs2.B[x+1]; // Rs1 bottom
}
rest[x/2] = op1t[x/2] u* op2t[x/2];
resb[x/2] = op1b[x/2] u* op2b[x/2];
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
R[t_H].H[1] = rest[1]; R[t_H].H[0] = resb[1];
R[t_L].H[1] = rest[0]; R[t_L].H[0] = resb[0];
x = 0 and 2
* RV64:
if (is `UMUL8`) {
    op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x+1]; // top
    op1b[x/2] = Rs1.B[x]; op2b[x/2] = Rs2.B[x]; // bottom
} else if (is `UMULX8`) {
    op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x]; // Rs1 top
    op1b[x/2]  =  Rs1.B[x]; op2b[x/2]  =  Rs2.B[x+1];  //  Rs1  bottom
}
rest[x/2]  =  op1t[x/2]  u*  op2t[x/2];
resb[x/2]  =  op1b[x/2]  u*  op2b[x/2];
```

(continues on next page)

(continued from previous page)

```
t_L  =  CONCAT(Rd(4,1),1'b0); t_H  =  CONCAT(Rd(4,1),1'b1);
Rd.W[1].H[1] = rest[1]; Rd.W[1].H[0] = resb[1];
Rd.W[0].H[1] = rest[0]; Rd.W[0].H[0] = resb[0]; x = 0 and 2
```

Parameters

- `a` – **[in]** unsigned int type of value stored in a
- `b` – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_UMULX8 (unsigned int a, unsigned int b)

UMULX8 (SIMD Unsigned Crossed 8-bit Multiply)

Type: SIMD

Syntax:

```
UMUL8 Rd, Rs1, Rs2
UMULX8 Rd, Rs1, Rs2
```

Purpose :

Do unsigned 8-bit multiplications and generate four 16-bit results simultaneously.

RV32 Description :

For the `UMUL8` instruction, multiply the unsigned 8-bit data elements of Rs1 with the corresponding unsigned 8-bit data elements of Rs2. For the `UMULX8` instruction, multiply the first and second unsigned 8-bit data elements of Rs1 with the second and first unsigned 8-bit data elements of Rs2. At the same time, multiply the third and fourth unsigned 8-bit data elements of Rs1 with the fourth and third unsigned 8-bit data elements of Rs2. The four 16-bit results are then written into an even/odd pair of registers specified by Rd(4,1). Rd(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the two 16-bit results calculated from the top part of Rs1 and the even `2d` register of the pair contains the two 16-bit results calculated from the bottom part of Rs1.

RV64 Description :

For the `UMUL8` instruction, multiply the unsigned 8-bit data elements of Rs1 with the corresponding unsigned 8-bit data elements of Rs2. For the `UMULX8` instruction, multiply the first and second unsigned 8-bit data elements of Rs1 with the second and first unsigned 8-bit data elements of Rs2. At the same time, multiply the third and fourth unsigned 8-bit data elements of Rs1 with the fourth and third unsigned 8-bit data elements of Rs2. The four 16-bit results are then written into Rd. The Rd.W[1] contains the two 16-bit results calculated from the top part of Rs1 and the Rd.W[0] contains the two 16-bit results calculated from the bottom part of Rs1.

Operations:

```
* RV32:
if (is `UMUL8`) {
  op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x+1]; // top
  op1b[x/2] = Rs1.B[x]; op2b[x/2] = Rs2.B[x]; // bottom
} else if (is `UMULX8`) {
  op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x]; // Rs1 top
  op1b[x/2] = Rs1.B[x]; op2b[x/2] = Rs2.B[x+1]; // Rs1 bottom
```

(continues on next page)

(continued from previous page)

```
}
rest[x/2] = op1t[x/2] u* op2t[x/2];
resb[x/2] = op1b[x/2] u* op2b[x/2];
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
R[t_H].H[1] = rest[1]; R[t_H].H[0] = resb[1];
R[t_L].H[1] = rest[0]; R[t_L].H[0] = resb[0];
x = 0 and 2
* RV64:
if (is `UMUL8`) {
    op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x+1]; // top
    op1b[x/2] = Rs1.B[x]; op2b[x/2] = Rs2.B[x]; // bottom
} else if (is `UMULX8`) {
    op1t[x/2] = Rs1.B[x+1]; op2t[x/2] = Rs2.B[x]; // Rs1 top
    op1b[x/2]  =  Rs1.B[x]; op2b[x/2]  =  Rs2.B[x+1];  //  Rs1  bottom
}
rest[x/2]  =  op1t[x/2]  u*  op2t[x/2];
resb[x/2]  =  op1b[x/2]  u*  op2b[x/2];
t_L  =  CONCAT(Rd(4,1),1'b0); t_H  =  CONCAT(Rd(4,1),1'b1);
Rd.W[1].H[1] = rest[1]; Rd.W[1].H[0] = resb[1];
Rd.W[0].H[1] = rest[0]; Rd.W[0].H[0] = resb[0]; x = 0 and 2
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long long type

SIMD 16-bit Miscellaneous Instructions

__STATIC_FORCEINLINE unsigned long __RV_CLRS16 (unsigned long a)

__STATIC_FORCEINLINE unsigned long __RV_CLO16 (unsigned long a)

__STATIC_FORCEINLINE unsigned long __RV_CLZ16 (unsigned long a)

__STATIC_FORCEINLINE unsigned long __RV_KABS16 (unsigned long a)

__STATIC_FORCEINLINE unsigned long __RV_SMAX16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_SMIN16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UMAX16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UMIN16 (unsigned long a, unsigned long b)

__RV_SCLIP16(a, b)

`__RV_UCLIP16`(a, b)

group `NMSIS_Core_DSP_Intrinsic_SIMD_16B_MISC`

SIMD 16-bit Miscellaneous Instructions.

there are 10 SIMD 16-bit Misc instructions.

Defines

`__RV_SCLIP16`(a, b)

SCLIP16 (SIMD 16-bit Signed Clip Value)

Type: SIMD

Syntax:

```
SCLIP16 Rd, Rs1, imm4u[3:0]
```

Purpose :

Limit the 16-bit signed integer elements of a register into a signed range simultaneously.

Description :

This instruction limits the 16-bit signed integer elements stored in Rs1 into a signed integer range between 2imm4u-1 and -2imm4u, and writes the limited results to Rd. For example, if imm4u is 3, the 16-bit input values should be saturated between 7 and -8. If saturation is performed, set OV bit to 1.

Operations:

```
src = Rs1.H[x];
if (src > (2^imm4u)-1) {
  src = (2^imm4u)-1;
  OV = 1;
} else if (src < -2^imm4u) {
  src = -2^imm4u;
  OV = 1;
}
Rd.H[x] = src
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

`__RV_UCLIP16`(a, b)

UCLIP16 (SIMD 16-bit Unsigned Clip Value)

Type: SIMD

Syntax:

```
UCLIP16 Rt, Ra, imm4u
```

Purpose :

Limit the 16-bit signed elements of a register into an unsigned range simultaneously.

Description :

This instruction limits the 16-bit signed elements stored in Rs1 into an unsigned integer range between 2imm4u-1 and 0, and writes the limited results to Rd. For example, if imm4u is 3, the 16-bit input values should be saturated between 7 and 0. If saturation is performed, set OV bit to 1.

Operations:

```
src = Rs1.H[x];
if (src > (2^imm4u)-1) {
  src = (2^imm4u)-1;
  OV = 1;
} else if (src < 0) {
  src = 0;
  OV = 1;
}
Rd.H[x] = src;
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

Functions

__STATIC_FORCEINLINE unsigned long __RV_CLRS16 (unsigned long a)

CLRS16 (SIMD 16-bit Count Leading Redundant Sign)

Type: SIMD

Syntax:

```
CLRS16 Rd, Rs1
```

Purpose :

Count the number of redundant sign bits of the 16-bit elements of a general register.

Description :

Starting from the bits next to the sign bits of the 16-bit elements of Rs1, this instruction counts the number of redundant sign bits and writes the result to the corresponding 16- bit elements of Rd.

Operations:

```
snum[x] = Rs1.H[x];
cnt[x] = 0;
for (i = 14 to 0) {
  if (snum[x](i) == snum[x](15)) {
    cnt[x] = cnt[x] + 1;
  } else {
    break;
  }
}
Rd.H[x] = cnt[x];
for RV32: x=1...0
for RV64: x=3...0
```

Parameters **a** – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_CLO16 (unsigned long a)

CLO16 (SIMD 16-bit Count Leading One)

Type: SIMD

Syntax:

```
CLO16 Rd, Rs1
```

Purpose :

Count the number of leading one bits of the 16-bit elements of a general register.

Description :

Starting from the most significant bits of the 16-bit elements of Rs1, this instruction counts the number of leading one bits and writes the results to the corresponding 16-bit elements of Rd.

Operations:

```
snum[x] = Rs1.H[x];
cnt[x] = 0;
for (i = 15 to 0) {
  if (snum[x](i) == 1) {
    cnt[x] = cnt[x] + 1;
  } else {
    break;
  }
}
Rd.H[x] = cnt[x];
for RV32: x=1...0
for RV64: x=3...0
```

Parameters **a** – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_CLZ16 (unsigned long a)

CLZ16 (SIMD 16-bit Count Leading Zero)

Type: SIMD

Syntax:

```
CLZ16 Rd, Rs1
```

Purpose :

Count the number of leading zero bits of the 16-bit elements of a general register.

Description :

Starting from the most significant bits of the 16-bit elements of Rs1, this instruction counts the number of leading zero bits and writes the results to the corresponding 16-bit elements of Rd.

Operations:

```
snum[x] = Rs1.H[x];
cnt[x] = 0;
for (i = 15 to 0) {
  if (snum[x](i) == 0) {
    cnt[x] = cnt[x] + 1;
  } else {
    break;
  }
}
Rd.H[x] = cnt[x];
for RV32: x=1...0
for RV64: x=3...0
```

Parameters `a` – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_KABS16 (unsigned long a)`

KABS16 (SIMD 16-bit Saturating Absolute)

Type: SIMD

Syntax:

```
KABS16 Rd, Rs1
```

Purpose :

Get the absolute value of 16-bit signed integer elements simultaneously.

Description :

This instruction calculates the absolute value of 16-bit signed integer elements stored in Rs1 and writes the element results to Rd. If the input number is 0x8000, this instruction generates 0x7fff as the output and sets the OV bit to 1.

Operations:

```
src = Rs1.H[x];
if (src == 0x8000) {
  src = 0x7fff;
  OV = 1;
} else if (src[15] == 1)
  src = -src;
}
Rd.H[x] = src;
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters **a** – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SMAX16 (unsigned long a, unsigned long b)

SMAX16 (SIMD 16-bit Signed Maximum)

Type: SIMD

Syntax:

```
SMAX16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer elements finding maximum operations simultaneously.

Description :

This instruction compares the 16-bit signed integer elements in Rs1 with the 16-bit signed integer elements in Rs2 and selects the numbers that is greater than the other one. The selected results are written to Rd.

Operations:

```
Rd.H[x] = (Rs1.H[x] > Rs2.H[x])? Rs1.H[x] : Rs2.H[x];
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SMIN16 (unsigned long a, unsigned long b)

SMIN16 (SIMD 16-bit Signed Minimum)

Type: SIMD

Syntax:

```
SMIN16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit signed integer elements finding minimum operations simultaneously.

Description :

This instruction compares the 16-bit signed integer elements in Rs1 with the 16-bit signed integer elements in Rs2 and selects the numbers that is less than the other one. The selected results are written to Rd.

Operations:

```
Rd.H[x] = (Rs1.H[x] < Rs2.H[x])? Rs1.H[x] : Rs2.H[x];
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UMAX16 (unsigned long a, unsigned long b)

UMAX16 (SIMD 16-bit Unsigned Maximum)

Type: SIMD

Syntax:

```
UMAX16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit unsigned integer elements finding maximum operations simultaneously.

Description :

This instruction compares the 16-bit unsigned integer elements in Rs1 with the 16-bit unsigned integer elements in Rs2 and selects the numbers that is greater than the other one. The selected results are written to Rd.

Operations:

```
Rd.H[x] = (Rs1.H[x] >u Rs2.H[x])? Rs1.H[x] : Rs2.H[x];
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UMIN16 (unsigned long a, unsigned long b)

UMIN16 (SIMD 16-bit Unsigned Minimum)

Type: SIMD

Syntax:

```
UMIN16 Rd, Rs1, Rs2
```

Purpose :

Do 16-bit unsigned integer elements finding minimum operations simultaneously.

Description :

This instruction compares the 16-bit unsigned integer elements in Rs1 with the 16-bit unsigned integer elements in Rs2 and selects the numbers that is less than the other one. The selected results are written to Rd.

Operations:

```
Rd.H[x] = (Rs1.H[x] <u Rs2.H[x])? Rs1.H[x] : Rs2.H[x];
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

SIMD 8-bit Miscellaneous Instructions

__STATIC_FORCEINLINE unsigned long __RV_CLRS8 (unsigned long a)

__STATIC_FORCEINLINE unsigned long __RV_CLO8 (unsigned long a)

__STATIC_FORCEINLINE unsigned long __RV_CLZ8 (unsigned long a)

__STATIC_FORCEINLINE unsigned long __RV_KABS8 (unsigned long a)

__STATIC_FORCEINLINE unsigned long __RV_SMAX8 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_SMIN8 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UMAX8 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UMIN8 (unsigned long a, unsigned long b)

__RV_SCLIP8(a, b)

__RV_UCLIP8(a, b)

group **NMSIS_Core_DSP_Intrinsic_SIMD_8B_MISC**

SIMD 8-bit Miscellaneous Instructions.

there are 10 SIMD 8-bit Miscellaneous instructions.

Defines

__RV_SCLIP8(a, b)

SCLIP8 (SIMD 8-bit Signed Clip Value)

Type: SIMD

Syntax:

```
SCLIP8 Rd, Rs1, imm3u[2:0]
```

Purpose :

Limit the 8-bit signed integer elements of a register into a signed range simultaneously.

Description :

This instruction limits the 8-bit signed integer elements stored in Rs1 into a signed integer range between 2^imm3u-1 and -2^imm3u, and writes the limited results to Rd. For example, if imm3u is 3, the 8-bit input values should be saturated between 7 and -8. If saturation is performed, set OV bit to 1.

Operations:

```
src = Rs1.B[x];
if (src > (2^imm3u)-1) {
  src = (2^imm3u)-1;
  OV = 1;
} else if (src < -2^imm3u) {
  src = -2^imm3u;
  OV = 1;
}
Rd.B[x] = src
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__RV_UCLIP8(a, b)

UCLIP8 (SIMD 8-bit Unsigned Clip Value)

Type: SIMD

Syntax:

```
UCLIP8 Rt, Ra, imm3u
```

Purpose :

Limit the 8-bit signed elements of a register into an unsigned range simultaneously.

Description :

This instruction limits the 8-bit signed elements stored in Rs1 into an unsigned integer range between 2^imm3u-1 and 0, and writes the limited results to Rd. For example, if imm3u is 3, the 8- bit input values should be saturated between 7 and 0. If saturation is performed, set OV bit to 1.

Operations:

```
src = Rs1.H[x];
if (src > (2^imm3u)-1) {
  src = (2^imm3u)-1;
  OV = 1;
} else if (src < 0) {
  src = 0;
  OV = 1;
}
Rd.H[x] = src;
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

Functions

__STATIC_FORCEINLINE unsigned long __RV_CLRS8 (unsigned long a)

CLRS8 (SIMD 8-bit Count Leading Redundant Sign)

Type: SIMD

Syntax:

```
CLRS8 Rd, Rs1
```

Purpose :

Count the number of redundant sign bits of the 8-bit elements of a general register.

Description :

Starting from the bits next to the sign bits of the 8-bit elements of Rs1, this instruction counts the number of redundant sign bits and writes the result to the corresponding 8-bit elements of Rd.

Operations:

```
snum[x] = Rs1.B[x];
cnt[x] = 0;
for (i = 6 to 0) {
  if (snum[x](i) == snum[x](7)) {
    cnt[x] = cnt[x] + 1;
  } else {
    break;
  }
}
Rd.B[x] = cnt[x];
for RV32: x=3...0
for RV64: x=7...0
```

Parameters a – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_CLO8 (unsigned long a)

CLO8 (SIMD 8-bit Count Leading One)

Type: SIMD

Syntax:

```
CLO8 Rd, Rs1
```

Purpose :

Count the number of leading one bits of the 8-bit elements of a general register.

Description :

Starting from the most significant bits of the 8-bit elements of Rs1, this instruction counts the number of leading one bits and writes the results to the corresponding 8-bit elements of Rd.

Operations:

```
snum[x] = Rs1.B[x];
cnt[x] = 0;
  for (i = 7 to 0) {
  if (snum[x](i) == 1) {
    cnt[x] = cnt[x] + 1;
  } else {
    break;
  }
}
Rd.B[x] = cnt[x];
for RV32: x=3...0
for RV64: x=7...0
```

Parameters a – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_CLZ8 (unsigned long a)

CLZ8 (SIMD 8-bit Count Leading Zero)

Type: SIMD

Syntax:

```
CLZ8 Rd, Rs1
```

Purpose :

Count the number of leading zero bits of the 8-bit elements of a general register.

Description :

Starting from the most significant bits of the 8-bit elements of Rs1, this instruction counts the number of leading zero bits and writes the results to the corresponding 8-bit elements of Rd.

Operations:

```
snum[x] = Rs1.B[x];
cnt[x] = 0;
for (i = 7 to 0) {
  if (snum[x](i) == 0) {
    cnt[x] = cnt[x] + 1;
  } else {
    break;
  }
}
Rd.B[x] = cnt[x];
for RV32: x=3...0
for RV64: x=7...0
```

Parameters **a** – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KABS8 (unsigned long a)

KABS8 (SIMD 8-bit Saturating Absolute)

Type: SIMD

Syntax:

```
KABS8 Rd, Rs1
```

Purpose :

Get the absolute value of 8-bit signed integer elements simultaneously.

Description :

This instruction calculates the absolute value of 8-bit signed integer elements stored in Rs1 and writes the element results to Rd. If the input number is 0x80, this instruction generates 0x7f as the output and sets the OV bit to 1.

Operations:

```
src = Rs1.B[x];
if (src == 0x80) {
  src = 0x7f;
  OV = 1;
} else if (src[7] == 1)
  src = -src;
}
Rd.B[x] = src;
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters **a** – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SMAX8 (unsigned long a, unsigned long b)

SMAX8 (SIMD 8-bit Signed Maximum)

Type: SIMD

Syntax:

```
SMAX8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit signed integer elements finding maximum operations simultaneously.

Description :

This instruction compares the 8-bit signed integer elements in Rs1 with the 8-bit signed integer elements in Rs2 and selects the numbers that is greater than the other one. The selected results are written to Rd.

Operations:

```
Rd.B[x] = (Rs1.B[x] > Rs2.B[x])? Rs1.B[x] : Rs2.B[x];
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SMIN8 (unsigned long a, unsigned long b)

SMIN8 (SIMD 8-bit Signed Minimum)

Type: SIMD

Syntax:

```
SMIN8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit signed integer elements finding minimum operations simultaneously.

Description :

This instruction compares the 8-bit signed integer elements in Rs1 with the 8-bit signed integer elements in Rs2 and selects the numbers that is less than the other one. The selected results are written to Rd.

Operations:

```
Rd.B[x] = (Rs1.B[x] < Rs2.B[x])? Rs1.B[x] : Rs2.B[x];
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_UMAX8 (unsigned long a, unsigned long b)`

UMAX8 (SIMD 8-bit Unsigned Maximum)

Type: SIMD

Syntax:

```
UMAX8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit unsigned integer elements finding maximum operations simultaneously.

Description :

This instruction compares the 8-bit unsigned integer elements in Rs1 with the four 8- bit unsigned integer elements in Rs2 and selects the numbers that is greater than the other one. The two selected results are written to Rd.

Operations:

```
Rd.B[x] = (Rs1.B[x] >u Rs2.B[x])? Rs1.B[x] : Rs2.B[x];
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_UMIN8 (unsigned long a, unsigned long b)`

UMIN8 (SIMD 8-bit Unsigned Minimum)

Type: SIMD

Syntax:

```
UMIN8 Rd, Rs1, Rs2
```

Purpose :

Do 8-bit unsigned integer elements finding minimum operations simultaneously.

Description :

This instruction compares the 8-bit unsigned integer elements in Rs1 with the 8-bit unsigned integer elements in Rs2 and selects the numbers that is less than the other one. The selected results are written to Rd.

Operations:

```
Rd.B[x] = (Rs1.B[x] <u Rs2.B[x])? Rs1.B[x] : Rs2.B[x];
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

SIMD 8-bit Unpacking Instructions

`__STATIC_FORCEINLINE unsigned long __RV_SUNPKD810 (unsigned long a)`

`__STATIC_FORCEINLINE unsigned long __RV_SUNPKD820 (unsigned long a)`

`__STATIC_FORCEINLINE unsigned long __RV_SUNPKD830 (unsigned long a)`

`__STATIC_FORCEINLINE unsigned long __RV_SUNPKD831 (unsigned long a)`

`__STATIC_FORCEINLINE unsigned long __RV_SUNPKD832 (unsigned long a)`

`__STATIC_FORCEINLINE unsigned long __RV_ZUNPKD810 (unsigned long a)`

`__STATIC_FORCEINLINE unsigned long __RV_ZUNPKD820 (unsigned long a)`

`__STATIC_FORCEINLINE unsigned long __RV_ZUNPKD830 (unsigned long a)`

`__STATIC_FORCEINLINE unsigned long __RV_ZUNPKD831 (unsigned long a)`

`__STATIC_FORCEINLINE unsigned long __RV_ZUNPKD832 (unsigned long a)`

group `NMSIS_Core_DSP_Intrinsic_SIMD_8B_UNPACK`

SIMD 8-bit Unpacking Instructions.

there are 8 SIMD 8-bit Unpacking instructions.

Functions

`__STATIC_FORCEINLINE unsigned long __RV_SUNPKD810 (unsigned long a)`

SUNPKD810 (Signed Unpacking Bytes 1 & 0)

Type: DSP

Syntax:

```
SUNPKD8xy Rd, Rs1
xy = {10, 20, 30, 31, 32}
```

Purpose :

Unpack byte *x and byte y* of 32-bit chunks in a register into two 16-bit signed halfwords of 32-bit chunks in a register.

Description :

For the `SUNPKD8(x)(*y*)` instruction, it unpacks byte *x and byte y* of 32-bit chunks in Rs1 into two 16-bit signed halfwords and writes the results to the top part and the bottom part of 32-bit chunks in Rd.

Operations:

```
Rd.W[m].H[1] = SE16(Rs1.W[m].B[x])
Rd.W[m].H[0] = SE16(Rs1.W[m].B[y])
// SUNPKD810, x=1,y=0
// SUNPKD820, x=2,y=0
// SUNPKD830, x=3,y=0
// SUNPKD831, x=3,y=1
// SUNPKD832, x=3,y=2
for RV32: m=0,
for RV64: m=1...0
```

Parameters `a` – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_SUNPKD820 (unsigned long a)`

SUNPKD820 (Signed Unpacking Bytes 2 & 0)

Type: DSP

Syntax:

```
SUNPKD8xy Rd, Rs1
xy = {10, 20, 30, 31, 32}
```

Purpose :

Unpack byte *x and byte y* of 32-bit chunks in a register into two 16-bit signed halfwords of 32-bit chunks in a register.

Description :

For the `SUNPKD8(x)(*y*)` instruction, it unpacks byte *x and byte y* of 32-bit chunks in Rs1 into two 16-bit signed halfwords and writes the results to the top part and the bottom part of 32-bit chunks in Rd.

Operations:

```
Rd.W[m].H[1] = SE16(Rs1.W[m].B[x])
Rd.W[m].H[0] = SE16(Rs1.W[m].B[y])
// SUNPKD810, x=1,y=0
// SUNPKD820, x=2,y=0
// SUNPKD830, x=3,y=0
// SUNPKD831, x=3,y=1
// SUNPKD832, x=3,y=2
for RV32: m=0,
for RV64: m=1...0
```

Parameters `a` – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SUNPKD830 (unsigned long a)

SUNPKD830 (Signed Unpacking Bytes 3 & 0)

Type: DSP

Syntax:

```
SUNPKD8xy Rd, Rs1
xy = {10, 20, 30, 31, 32}
```

Purpose :

Unpack byte *x and byte y* of 32-bit chunks in a register into two 16-bit signed halfwords of 32-bit chunks in a register.

Description :

For the `SUNPKD8(x)(*y*)` instruction, it unpacks byte *x and byte y* of 32-bit chunks in Rs1 into two 16-bit signed halfwords and writes the results to the top part and the bottom part of 32-bit chunks in Rd.

Operations:

```
Rd.W[m].H[1] = SE16(Rs1.W[m].B[x])
Rd.W[m].H[0] = SE16(Rs1.W[m].B[y])
// SUNPKD810, x=1,y=0
// SUNPKD820, x=2,y=0
// SUNPKD830, x=3,y=0
// SUNPKD831, x=3,y=1
// SUNPKD832, x=3,y=2
for RV32: m=0,
for RV64: m=1...0
```

Parameters `a` – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SUNPKD831 (unsigned long a)

SUNPKD831 (Signed Unpacking Bytes 3 & 1)

Type: DSP

Syntax:

```
SUNPKD8xy Rd, Rs1
xy = {10, 20, 30, 31, 32}
```

Purpose :

Unpack byte *x and byte y* of 32-bit chunks in a register into two 16-bit signed halfwords of 32-bit chunks in a register.

Description :

For the `SUNPKD8(x)(*y*)` instruction, it unpacks byte *x and byte y* of 32-bit chunks in Rs1 into two 16-bit signed halfwords and writes the results to the top part and the bottom part of 32-bit chunks in Rd.

Operations:

```
Rd.W[m].H[1] = SE16(Rs1.W[m].B[x])
Rd.W[m].H[0] = SE16(Rs1.W[m].B[y])
// SUNPKD810, x=1,y=0
// SUNPKD820, x=2,y=0
// SUNPKD830, x=3,y=0
// SUNPKD831, x=3,y=1
// SUNPKD832, x=3,y=2
for RV32: m=0,
for RV64: m=1...0
```

Parameters `a` – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_SUNPKD832 (unsigned long a)`

SUNPKD832 (Signed Unpacking Bytes 3 & 2)

Type: DSP

Syntax:

```
SUNPKD8xy Rd, Rs1
xy = {10, 20, 30, 31, 32}
```

Purpose :

Unpack byte *x and byte y* of 32-bit chunks in a register into two 16-bit signed halfwords of 32-bit chunks in a register.

Description :

For the `SUNPKD8(x)(*y*)` instruction, it unpacks byte *x and byte y* of 32-bit chunks in Rs1 into two 16-bit signed halfwords and writes the results to the top part and the bottom part of 32-bit chunks in Rd.

Operations:

```
Rd.W[m].H[1] = SE16(Rs1.W[m].B[x])
Rd.W[m].H[0] = SE16(Rs1.W[m].B[y])
// SUNPKD810, x=1,y=0
// SUNPKD820, x=2,y=0
// SUNPKD830, x=3,y=0
// SUNPKD831, x=3,y=1
// SUNPKD832, x=3,y=2
for RV32: m=0,
for RV64: m=1...0
```

Parameters `a` – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_ZUNPKD810 (unsigned long a)`

ZUNPKD810 (Unsigned Unpacking Bytes 1 & 0)

Type: DSP

Syntax:

```
ZUNPKD8xy Rd, Rs1
xy = {10, 20, 30, 31, 32}
```

Purpose :

Unpack byte x and byte y of 32-bit chunks in a register into two 16-bit unsigned halfwords of 32-bit chunks in a register.

Description :

For the `ZUNPKD8(x)(*y*)` instruction, it unpacks byte *x and byte y* of 32-bit chunks in Rs1 into two 16-bit unsigned halfwords and writes the results to the top part and the bottom part of 32-bit chunks in Rd.

Operations:

```
Rd.W[m].H[1] = ZE16(Rs1.W[m].B[x])
Rd.W[m].H[0] = ZE16(Rs1.W[m].B[y])
// ZUNPKD810, x=1,y=0
// ZUNPKD820, x=2,y=0
// ZUNPKD830, x=3,y=0
// ZUNPKD831, x=3,y=1
// ZUNPKD832, x=3,y=2
for RV32: m=0,
for RV64: m=1...0
```

Parameters `a` – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_ZUNPKD820 (unsigned long a)`

ZUNPKD820 (Unsigned Unpacking Bytes 2 & 0)

Type: DSP

Syntax:

```
ZUNPKD8xy Rd, Rs1
xy = {10, 20, 30, 31, 32}
```

Purpose :

Unpack byte x and byte y of 32-bit chunks in a register into two 16-bit unsigned halfwords of 32-bit chunks in a register.

Description :

For the `ZUNPKD8(x)(*y*)` instruction, it unpacks byte *x and byte y* of 32-bit chunks in Rs1 into two 16-bit unsigned halfwords and writes the results to the top part and the bottom part of 32-bit chunks in Rd.

Operations:

```
Rd.W[m].H[1] = ZE16(Rs1.W[m].B[x])
Rd.W[m].H[0] = ZE16(Rs1.W[m].B[y])
// ZUNPKD810, x=1,y=0
// ZUNPKD820, x=2,y=0
// ZUNPKD830, x=3,y=0
// ZUNPKD831, x=3,y=1
// ZUNPKD832, x=3,y=2
```

(continues on next page)

(continued from previous page)

```
for RV32: m=0,
for RV64: m=1...0
```

Parameters **a** – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_ZUNPKD830 (unsigned long a)

ZUNPKD830 (Unsigned Unpacking Bytes 3 & 0)

Type: DSP

Syntax:

```
ZUNPKD8xy Rd, Rs1
xy = {10, 20, 30, 31, 32}
```

Purpose :

Unpack byte x and byte y of 32-bit chunks in a register into two 16-bit unsigned halfwords of 32-bit chunks in a register.

Description :

For the `ZUNPKD8(x)(*y*)` instruction, it unpacks byte *x and byte y* of 32-bit chunks in Rs1 into two 16-bit unsigned halfwords and writes the results to the top part and the bottom part of 32-bit chunks in Rd.

Operations:

```
Rd.W[m].H[1] = ZE16(Rs1.W[m].B[x])
Rd.W[m].H[0] = ZE16(Rs1.W[m].B[y])
// ZUNPKD810, x=1,y=0
// ZUNPKD820, x=2,y=0
// ZUNPKD830, x=3,y=0
// ZUNPKD831, x=3,y=1
// ZUNPKD832, x=3,y=2
for RV32: m=0,
for RV64: m=1...0
```

Parameters **a** – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_ZUNPKD831 (unsigned long a)

ZUNPKD831 (Unsigned Unpacking Bytes 3 & 1)

Type: DSP

Syntax:

```
ZUNPKD8xy Rd, Rs1
xy = {10, 20, 30, 31, 32}
```

Purpose :

Unpack byte x and byte y of 32-bit chunks in a register into two 16-bit unsigned halfwords of 32-bit chunks in a register.

Description :

For the ZUNPKD8(x)(*y*) instruction, it unpacks byte *x and byte y* of 32-bit chunks in Rs1 into two 16-bit unsigned halfwords and writes the results to the top part and the bottom part of 32-bit chunks in Rd.

Operations:

```
Rd.W[m].H[1] = ZE16(Rs1.W[m].B[x])
Rd.W[m].H[0] = ZE16(Rs1.W[m].B[y])
// ZUNPKD810, x=1,y=0
// ZUNPKD820, x=2,y=0
// ZUNPKD830, x=3,y=0
// ZUNPKD831, x=3,y=1
// ZUNPKD832, x=3,y=2
for RV32: m=0,
for RV64: m=1...0
```

Parameters **a** – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_ZUNPKD832 (unsigned long a)

ZUNPKD832 (Unsigned Unpacking Bytes 3 & 2)

Type: DSP

Syntax:

```
ZUNPKD8xy Rd, Rs1
xy = {10, 20, 30, 31, 32}
```

Purpose :

Unpack byte x and byte y of 32-bit chunks in a register into two 16-bit unsigned halfwords of 32-bit chunks in a register.

Description :

For the ZUNPKD8(x)(*y*) instruction, it unpacks byte *x and byte y* of 32-bit chunks in Rs1 into two 16-bit unsigned halfwords and writes the results to the top part and the bottom part of 32-bit chunks in Rd.

Operations:

```
Rd.W[m].H[1] = ZE16(Rs1.W[m].B[x])
Rd.W[m].H[0] = ZE16(Rs1.W[m].B[y])
// ZUNPKD810, x=1,y=0
// ZUNPKD820, x=2,y=0
// ZUNPKD830, x=3,y=0
// ZUNPKD831, x=3,y=1
// ZUNPKD832, x=3,y=2
for RV32: m=0,
for RV64: m=1...0
```

Parameters **a** – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

group `NMSIS_Core_DSP_Intrinsic_SIMD_DATA_PROCESS`

SIMD Data Processing Instructions.

Non-SIMD Instructions

Non-SIMD Q15 saturation ALU Instructions

__STATIC_FORCEINLINE long __RV_KADDH (int a, int b)

__STATIC_FORCEINLINE long __RV_KHMBB (unsigned int a, unsigned int b)

__STATIC_FORCEINLINE long __RV_KHMBT (unsigned int a, unsigned int b)

__STATIC_FORCEINLINE long __RV_KHMTT (unsigned int a, unsigned int b)

__STATIC_FORCEINLINE long __RV_KSUBH (int a, int b)

__STATIC_FORCEINLINE unsigned long __RV_UKADDH (unsigned int a, unsigned int b)

__STATIC_FORCEINLINE unsigned long __RV_UKSUBH (unsigned int a, unsigned int b)

group `NMSIS_Core_DSP_Intrinsic_NON_SIMD_Q15_SAT_ALU`

Non-SIMD Q15 saturation ALU Instructions.

there are 7 Non-SIMD Q15 saturation ALU Instructions

Functions

__STATIC_FORCEINLINE long __RV_KADDH (int a, int b)

KADDH (Signed Addition with Q15 Saturation)

Type: DSP

Syntax:

```
KADDH Rd, Rs1, Rs2
```

Purpose :

Add the signed lower 32-bit content of two registers with Q15 saturation.

Description :

The signed lower 32-bit content of Rs1 is added with the signed lower 32-bit content of Rs2. And the result is saturated to the 16-bit signed integer range of [-2^15, 2^15-1] and then sign- extended and written to Rd. If saturation happens, this instruction sets the OV flag.

Operations:

```
tmp = Rs1.W[0] + Rs2.W[0];
if (tmp > 32767) {
  res = 32767;
  OV = 1;
} else if (tmp < -32768) {
  res = -32768;
  OV = 1
} else {
  res = tmp;
}
Rd = SE(tmp[15:0]);
```

Parameters

- **a** – **[in]** int type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KHMBB (unsigned int a, unsigned int b)

KHMBB (Signed Saturating Half Multiply B16 x B16)

Type: DSP

Syntax:

```
KHMxy Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 number contents of two 16-bit data in the corresponding portion of the lower 32-bit chunk in registers and then right-shift 15 bits to turn the Q30 result into a Q15 number again and saturate the Q15 result into the destination register. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs1 with the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs2. The Q30 result is then right- shifted 15-bits and saturated into a Q15 value. The Q15 value is then sing-extended and written into Rd. When both the two Q15 inputs are 0x8000, saturation will happen. The result will be saturated to 0x7FFF and the overflow flag OV will be set.

Operations:

```
aop = Rs1.H[0]; bop = Rs2.H[0]; // KHMBB
aop = Rs1.H[0]; bop = Rs2.H[1]; // KHMBT
aop = Rs1.H[1]; bop = Rs2.H[1]; // KHMTT
If (0x8000 != aop | 0x8000 != bop) {
  Mresult[31:0] = aop * bop;
  res[15:0] = Mresult[30:15];
} else {
  res[15:0] = 0x7FFF;
  OV = 1;
}
Rd = SE32(res[15:0]); // Rv32
Rd = SE64(res[15:0]); // RV64
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KHMBT (unsigned int a, unsigned int b)

KHMBT (Signed Saturating Half Multiply B16 x T16)

Type: DSP

Syntax:

```
KHMxy Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 number contents of two 16-bit data in the corresponding portion of the lower 32-bit chunk in registers and then right-shift 15 bits to turn the Q30 result into a Q15 number again and saturate the Q15 result into the destination register. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs1 with the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs2. The Q30 result is then right- shifted 15-bits and saturated into a Q15 value. The Q15 value is then sing-extended and written into Rd. When both the two Q15 inputs are 0x8000, saturation will happen. The result will be saturated to 0x7FFF and the overflow flag OV will be set.

Operations:

```
aop = Rs1.H[0]; bop = Rs2.H[0]; // KHMBB
aop = Rs1.H[0]; bop = Rs2.H[1]; // KHMBT
aop = Rs1.H[1]; bop = Rs2.H[1]; // KHMTT
If (0x8000 != aop | 0x8000 != bop) {
  Mresult[31:0] = aop * bop;
  res[15:0] = Mresult[30:15];
} else {
  res[15:0] = 0x7FFF;
  OV = 1;
}
Rd = SE32(res[15:0]); // Rv32
Rd = SE64(res[15:0]); // RV64
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KHMTT (unsigned int a, unsigned int b)

KHMTT (Signed Saturating Half Multiply T16 x T16)

Type: DSP

Syntax:

```
KHMxy Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 number contents of two 16-bit data in the corresponding portion of the lower 32-bit chunk in registers and then right-shift 15 bits to turn the Q30 result into a Q15 number again and saturate the Q15 result into the destination register. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs1 with the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs2. The Q30 result is then right- shifted 15-bits and saturated into a Q15 value. The Q15 value is then sing-extended and written into Rd. When both the two Q15 inputs are 0x8000, saturation will happen. The result will be saturated to 0x7FFF and the overflow flag OV will be set.

Operations:

```
aop = Rs1.H[0]; bop = Rs2.H[0]; // KHMBB
aop = Rs1.H[0]; bop = Rs2.H[1]; // KHMBT
aop = Rs1.H[1]; bop = Rs2.H[1]; // KHMTT
If (0x8000 != aop | 0x8000 != bop) {
  Mresult[31:0] = aop * bop;
  res[15:0] = Mresult[30:15];
} else {
  res[15:0] = 0x7FFF;
  OV = 1;
}
Rd = SE32(res[15:0]); // Rv32
Rd = SE64(res[15:0]); // RV64
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KSUBH (int a, int b)

KSUBH (Signed Subtraction with Q15 Saturation)

Type: DSP

Syntax:

```
KSUBH Rd, Rs1, Rs2
```

Purpose :

Subtract the signed lower 32-bit content of two registers with Q15 saturation.

Description :

The signed lower 32-bit content of Rs2 is subtracted from the signed lower 32-bit content of Rs1. And the result is saturated to the 16-bit signed integer range of [-2^15, 2^15-1] and then sign-extended and written to Rd. If saturation happens, this instruction sets the OV flag.

Operations:

```
tmp = Rs1.W[0] - Rs2.W[0];
if (tmp > (2^15)-1) {
  res = (2^15)-1;
  OV = 1;
} else if (tmp < -2^15) {
  res = -2^15;
  OV = 1
} else {
  res = tmp;
}
Rd = SE(res[15:0]);
```

Parameters

- **a** – **[in]** int type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE unsigned long __RV_UKADDH (unsigned int a, unsigned int b)`

UKADDH (Unsigned Addition with U16 Saturation)

Type: DSP

Syntax:

```
UKADDH Rd, Rs1, Rs2
```

Purpose :

Add the unsigned lower 32-bit content of two registers with U16 saturation.

Description :

The unsigned lower 32-bit content of Rs1 is added with the unsigned lower 32-bit content of Rs2. And the result is saturated to the 16-bit unsigned integer range of [0, 2^16-1] and then sign-extended and written to Rd. If saturation happens, this instruction sets the OV flag.

Operations:

```
tmp = Rs1.W[0] + Rs2.W[0];
if (tmp > (2^16)-1) {
  tmp = (2^16)-1;
  OV = 1;
}
Rd = SE(tmp[15:0]);
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UKSUBH (unsigned int a, unsigned int b)

UKSUBH (Unsigned Subtraction with U16 Saturation)

Type: DSP

Syntax:

```
UKSUBH Rd, Rs1, Rs2
```

Purpose :

Subtract the unsigned lower 32-bit content of two registers with U16 saturation.

Description :

The unsigned lower 32-bit content of Rs2 is subtracted from the unsigned lower 32-bit content of Rs1. And the result is saturated to the 16-bit unsigned integer range of [0, 2^16-1] and then sign-extended and written to Rd. If saturation happens, this instruction sets the OV flag.

Operations:

```
tmp = Rs1.W[0] - Rs2.W[0];
if (tmp > (2^16)-1) {
  tmp = (2^16)-1;
  OV = 1;
}
else if (tmp < 0) {
  tmp = 0;
  OV = 1;
}
Rd = SE(tmp[15:0]);
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

Non-SIMD Q31 saturation ALU Instructions

__STATIC_FORCEINLINE unsigned long __RV_KABSW (signed long a)

__STATIC_FORCEINLINE long __RV_KADDW (int a, int b)

__STATIC_FORCEINLINE long __RV_KDMBB (unsigned int a, unsigned int b)

__STATIC_FORCEINLINE long __RV_KDMBT (unsigned int a, unsigned int b)

__STATIC_FORCEINLINE long __RV_KDMTT (unsigned int a, unsigned int b)

__STATIC_FORCEINLINE long __RV_KDMABB (long t, unsigned int a, unsigned int b)

__STATIC_FORCEINLINE long __RV_KDMABT (long t, unsigned int a, unsigned int b)

__STATIC_FORCEINLINE long __RV_KDMATT (long t, unsigned int a, unsigned int b)

__STATIC_FORCEINLINE long __RV_KSLLW (long a, unsigned int b)

__STATIC_FORCEINLINE long __RV_KSLRAW (int a, int b)

__STATIC_FORCEINLINE long __RV_KSLRAW_U (int a, int b)

__STATIC_FORCEINLINE long __RV_KSUBW (int a, int b)

__STATIC_FORCEINLINE unsigned long __RV_UKADDW (unsigned int a, unsigned int b)

__STATIC_FORCEINLINE unsigned long __RV_UKSUBW (unsigned int a, unsigned int b)

__RV_KSLLIW(a, b)

group **NMSIS_Core_DSP_Intrinsic_NON_SIMD_Q31_SAT_ALU**

Non-SIMD Q31 saturation ALU Instructions.

there are Non-SIMD Q31 saturation ALU Instructions

Defines

__RV_KSLLIW(a, b)

KSLLIW (Saturating Shift Left Logical Immediate for Word)

Type: DSP

Syntax:

```
KSLLIW Rd, Rs1, imm5u
```

Purpose :

Do logical left shift operation with saturation on a 32-bit word. The shift amount is an immediate value.

Description :

The first word data in Rs1 is left-shifted logically. The shifted out bits are filled with zero and the shift amount is specified by the imm5u constant. Any shifted value greater than 2^31-1 is saturated to 2^31-1. Any shifted value smaller than -2^31 is saturated to -2^31. And the saturated result is sign-extended and written to Rd. If any saturation is performed, set OV bit to 1.

Operations:

```
sa = imm5u;
res[(31+sa):0] = Rs1.W[0] << sa;
if (res > (2^31)-1) {
  res = 0x7fffffff; OV = 1;
} else if (res < -2^31) {
  res = 0x80000000; OV = 1;
}
Rd[31:0] = res[31:0]; // RV32
Rd[63:0] = SE(res[31:0]); // RV64
```

Parameters

- **a** – **[in]** long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in long type

Functions

__STATIC_FORCEINLINE unsigned long __RV_KABSW (signed long a)

KABSW (Scalar 32-bit Absolute Value with Saturation)

Type: DSP

Syntax:

```
KABSW Rd, Rs1
```

Purpose :

Get the absolute value of a signed 32-bit integer in a general register.

Description :

This instruction calculates the absolute value of a signed 32-bit integer stored in Rs1. The result is sign-extended (for RV64) and written to Rd. This instruction with the minimum negative integer input of 0x80000000 will produce a saturated output of maximum positive integer of 0x7fffffff and the OV flag will be set to 1.

Operations:

```
if (Rs1.W[0] >= 0) {
  res = Rs1.W[0];
} else {
  If (Rs1.W[0] == 0x80000000) {
    res = 0x7fffffff;
    OV = 1;
  } else {
    res = -Rs1.W[0];
  }
}
Rd = SE32(res);
```

Parameters **a** – **[in]** signed long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE long __RV_KADDW (int a, int b)

KADDW (Signed Addition with Q31 Saturation)

Type: DSP

Syntax:

```
KADDW Rd, Rs1, Rs2
```

Purpose :

Add the lower 32-bit signed content of two registers with Q31 saturation.

Description :

The lower 32-bit signed content of Rs1 is added with the lower 32-bit signed content of Rs2. And the result is saturated to the 32-bit signed integer range of [-2^31, 2^31-1] and then sign- extended and written to Rd. If saturation happens, this instruction sets the OV flag.

Operations:

```
tmp = Rs1.W[0] + Rs2.W[0];
if (tmp > (2^31)-1) {
  res = (2^31)-1;
  OV = 1;
} else if (tmp < -2^31) {
  res = -2^31;
  OV = 1
} else {
  res = tmp;
}
Rd = res[31:0]; // RV32
Rd = SE(res[31:0]) // RV64
```

Parameters

- **a** – **[in]** int type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KDMBB (unsigned int a, unsigned int b)

KDMBB (Signed Saturating Double Multiply B16 x B16)

Type: DSP

Syntax:

```
KDMxy Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 integer contents of two 16-bit data in the corresponding portion of the lower 32-bit chunk in registers and then double and saturate the Q31 result. The result is written into the destination register for RV32 or sign-extended to 64-bits and written into the destination register for RV64. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs1 with the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs2. The Q30 result is then doubled and saturated into a Q31 value. The Q31 value is then written into Rd (sign-extended in RV64). When both the two Q15 inputs are 0x8000, saturation will happen. The result will be saturated to 0x7FFFFFFF and the overflow flag OV will be set.

Operations:

```
aop = Rs1.H[0]; bop = Rs2.H[0]; // KDMBB
aop = Rs1.H[0]; bop = Rs2.H[1]; // KDMBT
aop = Rs1.H[1]; bop = Rs2.H[1]; // KDMTT
If (0x8000 != aop | 0x8000 != bop) {
  Mresult = aop * bop;
  resQ31 = Mresult << 1;
  Rd = resQ31; // RV32
  Rd = SE(resQ31); // RV64
} else {
  resQ31 = 0x7FFFFFFF;
  Rd = resQ31; // RV32
  Rd = SE(resQ31); // RV64
  OV = 1;
}
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KDMBT (unsigned int a, unsigned int b)

KDMBT (Signed Saturating Double Multiply B16 x T16)

Type: DSP

Syntax:

```
KDMxy Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 integer contents of two 16-bit data in the corresponding portion of the lower 32-bit chunk in registers and then double and saturate the Q31 result. The result is written into the destination register for RV32 or sign-extended to 64-bits and written into the destination register for RV64. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs1 with the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs2. The Q30 result is then doubled and saturated into a Q31 value. The Q31 value is then written into Rd (sign-extended in RV64). When both the two Q15 inputs are 0x8000, saturation will happen. The result will be saturated to 0x7FFFFFFF and the overflow flag OV will be set.

Operations:

```
aop = Rs1.H[0]; bop = Rs2.H[0]; // KDMBB
aop = Rs1.H[0]; bop = Rs2.H[1]; // KDMBT
aop = Rs1.H[1]; bop = Rs2.H[1]; // KDMTT
If (0x8000 != aop | 0x8000 != bop) {
  Mresult = aop * bop;
  resQ31 = Mresult << 1;
  Rd = resQ31; // RV32
  Rd = SE(resQ31); // RV64
} else {
  resQ31 = 0x7FFFFFFF;
  Rd = resQ31; // RV32
  Rd = SE(resQ31); // RV64
  OV = 1;
}
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KDMTT (unsigned int a, unsigned int b)

KDMTT (Signed Saturating Double Multiply T16 x T16)

Type: DSP

Syntax:

```
KDMxy Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 integer contents of two 16-bit data in the corresponding portion of the lower 32-bit chunk in registers and then double and saturate the Q31 result. The result is written into the destination register for RV32 or sign-extended to 64-bits and written into the destination register for RV64. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs1 with the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs2. The Q30 result is then doubled and saturated into a Q31 value. The Q31 value is then written into Rd (sign-extended in RV64). When both the two Q15 inputs are 0x8000, saturation will happen. The result will be saturated to 0x7FFFFFFF and the overflow flag OV will be set.

Operations:

```
aop = Rs1.H[0]; bop = Rs2.H[0]; // KDMBB
aop = Rs1.H[0]; bop = Rs2.H[1]; // KDMBT
aop = Rs1.H[1]; bop = Rs2.H[1]; // KDMTT
If (0x8000 != aop | 0x8000 != bop) {
  Mresult = aop * bop;
  resQ31 = Mresult << 1;
  Rd = resQ31; // RV32
```

(continues on next page)

(continued from previous page)

```
  Rd = SE(resQ31); // RV64
} else {
  resQ31 = 0x7FFFFFFF;
  Rd = resQ31; // RV32
  Rd = SE(resQ31); // RV64
  OV = 1;
}
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KDMABB (long t, unsigned int a, unsigned int b)

KDMABB (Signed Saturating Double Multiply Addition B16 x B16)

Type: DSP

Syntax:

```
KDMAxy Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 integer contents of two 16-bit data in the corresponding portion of the lower 32-bit chunk in registers and then double and saturate the Q31 result, add the result with the sign-extended lower 32-bit chunk destination register and write the saturated addition result into the destination register. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs1 with the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs2. The Q30 result is then doubled and saturated into a Q31 value. The Q31 value is then added with the content of Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV flag is set to 1. The result after saturation is written to Rd. When both the two Q15 inputs are 0x8000, saturation will happen and the overflow flag OV will be set.

Operations:

```
aop = Rs1.H[0]; bop = Rs2.H[0]; // KDMABB
aop = Rs1.H[0]; bop = Rs2.H[1]; // KDMABT
aop = Rs1.H[1]; bop = Rs2.H[1]; // KDMATT
If (0x8000 != aop | 0x8000 != bop) {
  Mresult = aop * bop;
  resQ31 = Mresult << 1;
} else {
  resQ31 = 0x7FFFFFFF;
  OV = 1;
}
resadd = Rd + resQ31; // RV32
resadd = Rd.W[0] + resQ31; // RV64
if (resadd > (2^31)-1) {
```

(continues on next page)

(continued from previous page)

```
  resadd = (2^31)-1;
  OV = 1;
} else if (resadd < -2^31) {
  resadd = -2^31;
  OV = 1;
}
Rd = resadd; // RV32
Rd = SE(resadd); // RV64
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KDMABT (long t, unsigned int a, unsigned int b)

KDMABT (Signed Saturating Double Multiply Addition B16 x T16)

Type: DSP

Syntax:

```
KDMAxy Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 integer contents of two 16-bit data in the corresponding portion of the lower 32-bit chunk in registers and then double and saturate the Q31 result, add the result with the sign-extended lower 32-bit chunk destination register and write the saturated addition result into the destination register. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs1 with the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs2. The Q30 result is then doubled and saturated into a Q31 value. The Q31 value is then added with the content of Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV flag is set to 1. The result after saturation is written to Rd. When both the two Q15 inputs are 0x8000, saturation will happen and the overflow flag OV will be set.

Operations:

```
aop = Rs1.H[0]; bop = Rs2.H[0]; // KDMABB
aop = Rs1.H[0]; bop = Rs2.H[1]; // KDMABT
aop = Rs1.H[1]; bop = Rs2.H[1]; // KDMATT
If (0x8000 != aop | 0x8000 != bop) {
  Mresult = aop * bop;
  resQ31 = Mresult << 1;
} else {
  resQ31 = 0x7FFFFFFF;
  OV = 1;
}
```

(continues on next page)

(continued from previous page)

```
resadd = Rd + resQ31; // RV32
resadd = Rd.W[0] + resQ31; // RV64
if (resadd > (2^31)-1) {
  resadd = (2^31)-1;
  OV = 1;
} else if (resadd < -2^31) {
  resadd = -2^31;
  OV = 1;
}
Rd = resadd; // RV32
Rd = SE(resadd); // RV64
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KDMATT (long t, unsigned int a, unsigned int b)

KDMATT (Signed Saturating Double Multiply Addition T16 x T16)

Type: DSP

Syntax:

```
KDMAxy Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 integer contents of two 16-bit data in the corresponding portion of the lower 32-bit chunk in registers and then double and saturate the Q31 result, add the result with the sign-extended lower 32-bit chunk destination register and write the saturated addition result into the destination register. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs1 with the top or bottom 16-bit Q15 content of the lower 32-bit portion in Rs2. The Q30 result is then doubled and saturated into a Q31 value. The Q31 value is then added with the content of Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV flag is set to 1. The result after saturation is written to Rd. When both the two Q15 inputs are 0x8000, saturation will happen and the overflow flag OV will be set.

Operations:

```
aop = Rs1.H[0]; bop = Rs2.H[0]; // KDMABB
aop = Rs1.H[0]; bop = Rs2.H[1]; // KDMABT
aop = Rs1.H[1]; bop = Rs2.H[1]; // KDMATT
If (0x8000 != aop | 0x8000 != bop) {
  Mresult = aop * bop;
  resQ31 = Mresult << 1;
} else {
```

(continues on next page)

(continued from previous page)

```
  resQ31 = 0x7FFFFFFF;
  OV = 1;
}
resadd = Rd + resQ31; // RV32
resadd = Rd.W[0] + resQ31; // RV64
if (resadd > (2^31)-1) {
  resadd = (2^31)-1;
  OV = 1;
} else if (resadd < -2^31) {
  resadd = -2^31;
  OV = 1;
}
Rd = resadd; // RV32
Rd = SE(resadd); // RV64
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KSLLW (long a, unsigned int b)

KSLLW (Saturating Shift Left Logical for Word)

Type: DSP

Syntax:

```
KSLLW Rd, Rs1, Rs2
```

Purpose :

Do logical left shift operation with saturation on a 32-bit word. The shift amount is a variable from a GPR.

Description :

The first word data in Rs1 is left-shifted logically. The shifted out bits are filled with zero and the shift amount is specified by the low-order 5-bits of the value in the Rs2 register. Any shifted value greater than 2^31-1 is saturated to 2^31-1. Any shifted value smaller than -2^31 is saturated to -2^31. And the saturated result is sign-extended and written to Rd. If any saturation is performed, set OV bit to 1.

Operations:

```
sa = Rs2[4:0];
res[(31+sa):0] = Rs1.W[0] << sa;
if (res > (2^31)-1) {
  res = 0x7fffffff; OV = 1;
} else if (res < -2^31) {
  res = 0x80000000; OV = 1;
}
Rd[31:0] = res[31:0]; // RV32
Rd[63:0] = SE(res[31:0]); // RV64
```

Parameters

- a – **[in]** long type of value stored in a
- b – **[in]** unsigned int type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_KSLRAW (int a, int b)`

KSLRAW (Shift Left Logical with Q31 Saturation or Shift Right Arithmetic)

Type: DSP

Syntax:

```
KSLRAW Rd, Rs1, Rs2
```

Purpose :

Perform a logical left (positive) or arithmetic right (negative) shift operation with Q31 saturation for the left shift on a 32-bit data.

Description :

The lower 32-bit content of Rs1 is left-shifted logically or right-shifted arithmetically based on the value of Rs2[5:0]. Rs2[5:0] is in the signed range of [-25, 25-1]. A positive Rs2[5:0] means logical left shift and a negative Rs2[5:0] means arithmetic right shift. The shift amount is the absolute value of Rs2[5:0] clamped to the actual shift range of [0, 31]. The left-shifted result is saturated to the 32-bit signed integer range of [-2^31, 2^31-1]. After the shift operation, the final result is bit-31 sign-extended and written to Rd. If any saturation happens, this instruction sets the OV flag. The value of Rs2[31:6] will not affected the operation of this instruction.

Operations:

```
if (Rs2[5:0] < 0) {
  sa = -Rs2[5:0];
  sa = (sa == 32)? 31 : sa;
  res[31:0] = Rs1.W[0] >>(arith) sa;
} else {
  sa = Rs2[5:0];
  tmp = Rs1.W[0] <<(logic) sa;
  if (tmp > (2^31)-1) {
    res[31:0] = (2^31)-1;
    OV = 1;
  } else if (tmp < -2^31) {
    res[31:0] = -2^31;
    OV = 1
  } else {
    res[31:0] = tmp[31:0];
  }
}
Rd = res[31:0]; // RV32
Rd = SE64(res[31:0]); // RV64
```

Parameters

- a – **[in]** int type of value stored in a
- b – **[in]** int type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_KSLRAW_U (int a, int b)`

KSLRAW.u (Shift Left Logical with Q31 Saturation or Rounding Shift Right Arithmetic)

Type: DSP

Syntax:

```
KSLRAW.u Rd, Rs1, Rs2
```

Purpose :

Perform a logical left (positive) or arithmetic right (negative) shift operation with Q31 saturation for the left shift and a rounding up operation for the right shift on a 32-bit data.

Description :

The lower 32-bit content of Rs1 is left-shifted logically or right-shifted arithmetically based on the value of Rs2[5:0]. Rs2[5:0] is in the signed range of [-25, 25-1]. A positive Rs2[5:0] means logical left shift and a negative Rs2[5:0] means arithmetic right shift. The shift amount is the absolute value of Rs2[5:0] clamped to the actual shift range of [0, 31]. The left-shifted result is saturated to the 32-bit signed integer range of [-2^31, 2^31-1]. The right-shifted result is added a 1 to the most significant discarded bit position for rounding effect. After the shift, saturation, or rounding, the final result is bit-31 sign-extended and written to Rd. If any saturation happens, this instruction sets the OV flag. The value of Rs2[31:6] will not affect the operation of this instruction.

Operations:

```
if (Rs2[5:0] < 0) {
  sa = -Rs2[5:0];
  sa = (sa == 32)? 31 : sa;
  res[31:-1] = SE33(Rs1[31:(sa-1)]) + 1;
  rst[31:0] = res[31:0];
} else {
  sa = Rs2[5:0];
  tmp = Rs1.W[0] <<(logic) sa;
  if (tmp > (2^31)-1) {
    rst[31:0] = (2^31)-1;
    OV = 1;
  } else if (tmp < -2^31) {
    rst[31:0] = -2^31;
    OV = 1
  } else {
    rst[31:0] = tmp[31:0];
  }
}
Rd = rst[31:0]; // RV32
Rd = SE64(rst[31:0]); // RV64
```

Parameters

- **a** – **[in]** int type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KSUBW (int a, int b)

KSUBW (Signed Subtraction with Q31 Saturation)

Type: DSP

Syntax:

```
KSUBW Rd, Rs1, Rs2
```

Purpose :

Subtract the signed lower 32-bit content of two registers with Q31 saturation.

Description :

The signed lower 32-bit content of Rs2 is subtracted from the signed lower 32-bit content of Rs1. And the result is saturated to the 32-bit signed integer range of [-2^31, 2^31-1] and then sign-extened and written to Rd. If saturation happens, this instruction sets the OV flag.

Operations:

```
tmp = Rs1.W[0] - Rs2.W[0];
if (tmp > (2^31)-1) {
  res = (2^31)-1;
  OV = 1;
} else if (tmp < -2^31) {
res = -2^31;
  OV = 1
} else {
  res = tmp;
}
Rd = res[31:0]; // RV32
Rd = SE(res[31:0]); // RV64
```

Parameters

- **a** – **[in]** int type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE unsigned long __RV_UKADDW (unsigned int a, unsigned int b)

UKADDW (Unsigned Addition with U32 Saturation)

Type: DSP

Syntax:

```
UKADDW Rd, Rs1, Rs2
```

Purpose :

Add the unsigned lower 32-bit content of two registers with U32 saturation.

Description :

The unsigned lower 32-bit content of Rs1 is added with the unsigned lower 32-bit content of Rs2. And the result is saturated to the 32-bit unsigned integer range of [0, 2^32-1] and then sign-extended and written to Rd. If saturation happens, this instruction sets the OV flag.

Operations:

```
tmp = Rs1.W[0] + Rs2.W[0];
if (tmp > (2^32)-1) {
  tmp[31:0] = (2^32)-1;
  OV = 1;
}
Rd = tmp[31:0]; // RV32
Rd = SE(tmp[31:0]); // RV64
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UKSUBW (unsigned int a, unsigned int b)

UKSUBW (Unsigned Subtraction with U32 Saturation)

Type: DSP

Syntax:

```
UKSUBW Rd, Rs1, Rs2
```

Purpose :

Subtract the unsigned lower 32-bit content of two registers with unsigned 32-bit saturation.

Description :

The unsigned lower 32-bit content of Rs2 is subtracted from the unsigned lower 32-bit content of Rs1. And the result is saturated to the 32-bit unsigned integer range of [0, 2^32-1] and then sign-extended and written to Rd. If saturation happens, this instruction sets the OV flag.

Operations:

```
tmp = Rs1.W[0] - Rs2.W[0];
if (tmp < 0) {
  tmp[31:0] = 0;
  OV = 1;
}
Rd = tmp[31:0]; // RV32
Rd = SE(tmp[31:0]); // RV64
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

32-bit Computation Instructions

`__STATIC_FORCEINLINE long __RV_MAXW (int a, int b)`

`__STATIC_FORCEINLINE long __RV_MINW (int a, int b)`

`__STATIC_FORCEINLINE unsigned long long __RV_MULR64 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long long __RV_MULSR64 (long a, long b)`

`__STATIC_FORCEINLINE long __RV_RADDW (int a, int b)`

`__STATIC_FORCEINLINE long __RV_RSUBW (int a, int b)`

`__STATIC_FORCEINLINE unsigned long __RV_URADDW (unsigned int a, unsigned int b)`

`__STATIC_FORCEINLINE unsigned long __RV_URSUBW (unsigned int a, unsigned int b)`

group `NMSIS_Core_DSP_Intrinsic_32B_COMPUTATION`

32-bit Computation Instructions

there are 8 32-bit Computation Instructions

Functions

`__STATIC_FORCEINLINE long __RV_MAXW (int a, int b)`

MAXW (32-bit Signed Word Maximum)

Type: DSP

Syntax:

```
MAXW Rd, Rs1, Rs2
```

Purpose :

Get the larger value from the 32-bit contents of two general registers.

Description :

This instruction compares two signed 32-bit integers stored in Rs1 and Rs2, picks the larger value as the result, and writes the result to Rd.

Operations:

```
if (Rs1.W[0] >= Rs2.W[0]) {
  Rd = SE(Rs1.W[0]);
} else {
  Rd = SE(Rs2.W[0]);
}
```

Parameters

- **a** – **[in]** int type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_MINW (int a, int b)

MINW (32-bit Signed Word Minimum)

Type: DSP

Syntax:

```
MINW Rd, Rs1, Rs2
```

Purpose :

Get the smaller value from the 32-bit contents of two general registers.

Description :

This instruction compares two signed 32-bit integers stored in Rs1 and Rs2, picks the smaller value as the result, and writes the result to Rd.

Operations:

```
if (Rs1.W[0] >= Rs2.W[0]) { Rd = SE(Rs2.W[0]); } else { Rd = SE(Rs1.W[0]); }
```

Parameters

- **a** – **[in]** int type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE unsigned long long __RV_MULR64 (unsigned long a, unsigned long b)

MULR64 (Multiply Word Unsigned to 64-bit Data)

Type: DSP

Syntax:

```
MULR64 Rd, Rs1, Rs2
```

Purpose :

Multiply the 32-bit unsigned integer contents of two registers and write the 64-bit result.

RV32 Description :

This instruction multiplies the 32-bit content of Rs1 with that of Rs2 and writes the 64-bit multiplication result to an even/odd pair of registers containing Rd. Rd(4,1) index d determines the even/odd pair group of the two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result. The lower 32-bit contents of Rs1 and Rs2 are treated as unsigned integers.

RV64 Description :

This instruction multiplies the lower 32-bit content of Rs1 with that of Rs2 and writes the 64-bit multiplication result to Rd. The lower 32-bit contents of Rs1 and Rs2 are treated as unsigned integers.

Operations:

```
RV32:
Mresult = CONCAT(1`b0,Rs1) u* CONCAT(1`b0,Rs2);
R[Rd(4,1).1(0)][31:0] = Mresult[63:32];
R[Rd(4,1).0(0)][31:0] = Mresult[31:0];
RV64:
Rd = Mresult[63:0];
Mresult = CONCAT(1`b0,Rs1.W[0]) u* CONCAT(1`b0,Rs2.W[0]);
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE long long __RV_MULSR64 (long a, long b)

MULSR64 (Multiply Word Signed to 64-bit Data)

Type: DSP

Syntax:

```
MULSR64 Rd, Rs1, Rs2
```

Purpose :

Multiply the 32-bit signed integer contents of two registers and write the 64-bit result.

RV32 Description :

This instruction multiplies the lower 32-bit content of Rs1 with the lower 32-bit content of Rs2 and writes the 64-bit multiplication result to an even/odd pair of registers containing Rd. Rd(4,1) index d determines the even/odd pair group of the two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result. The lower 32-bit contents of Rs1 and Rs2 are treated as signed integers.

RV64 Description :

This instruction multiplies the lower 32-bit content of Rs1 with the lower 32-bit content of Rs2 and writes the 64-bit multiplication result to Rd. The lower 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
RV32:
Mresult = Ra s* Rb;
R[Rd(4,1).1(0)][31:0] = Mresult[63:32];
R[Rd(4,1).0(0)][31:0] = Mresult[31:0];
RV64:
Mresult = Ra.W[0] s* Rb.W[0];
Rd = Mresult[63:0];
```

Parameters

- **a** – **[in]** long type of value stored in a
- **b** – **[in]** long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long __RV_RADDW (int a, int b)

RADDW (32-bit Signed Halving Addition)

Type: DSP

Syntax:

```
RADDW Rd, Rs1, Rs2
```

Purpose :

Add 32-bit signed integers and the results are halved to avoid overflow or saturation.

Description :

This instruction adds the first 32-bit signed integer in Rs1 with the first 32-bit signed integer in Rs2. The result is first arithmetically right-shifted by 1 bit and then sign-extended and written to Rd.

Examples:

```
* Rs1 = 0x7FFFFFFF, Rs2 = 0x7FFFFFFF, Rd = 0x7FFFFFFF
* Rs1 = 0x80000000, Rs2 = 0x80000000, Rd = 0x80000000
* Rs1 = 0x40000000, Rs2 = 0x80000000, Rd = 0xE0000000
```

Operations:

```
RV32:
Rd[31:0] = (Rs1[31:0] + Rs2[31:0]) s>> 1;
RV64:
resw[31:0] = (Rs1[31:0] + Rs2[31:0]) s>> 1;
Rd[63:0] = SE(resw[31:0]);
```

Parameters

- **a** – **[in]** int type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_RSUBW (int a, int b)

RSUBW (32-bit Signed Halving Subtraction)

Type: DSP

Syntax:

```
RSUBW Rd, Rs1, Rs2
```

Purpose :

Subtract 32-bit signed integers and the result is halved to avoid overflow or saturation.

Description :

This instruction subtracts the first 32-bit signed integer in Rs2 from the first 32-bit signed integer in Rs1. The result is first arithmetically right-shifted by 1 bit and then sign-extended and written to Rd.

Examples:

```
* Rs1 = 0x7FFFFFFF, Rs2 = 0x80000000, Rd = 0x7FFFFFFF
* Rs1 = 0x80000000, Rs2 = 0x7FFFFFFF, Rd = 0x80000000
* Rs1 = 0x80000000, Rs2 = 0x40000000, Rd = 0xA0000000
```

Operations:

```
RV32:
Rd[31:0] = (Rs1[31:0] - Rs2[31:0]) s>> 1;
RV64:
resw[31:0] = (Rs1[31:0] - Rs2[31:0]) s>> 1;
Rd[63:0] = SE(resw[31:0]);
```

Parameters

- **a** – **[in]** int type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE unsigned long __RV_URADDW (unsigned int a, unsigned int b)`

URADDW (32-bit Unsigned Halving Addition)

Type: DSP

Syntax:

```
URADDW Rd, Rs1, Rs2
```

Purpose :

Add 32-bit unsigned integers and the results are halved to avoid overflow or saturation.

Description :

This instruction adds the first 32-bit unsigned integer in Rs1 with the first 32-bit unsigned integer in Rs2. The result is first logically right-shifted by 1 bit and then sign-extended and written to Rd.

Examples:

```
* Ra = 0x7FFFFFFF, Rb = 0x7FFFFFFF Rt = 0x7FFFFFFF
* Ra = 0x80000000, Rb = 0x80000000 Rt = 0x80000000
* Ra = 0x40000000, Rb = 0x80000000 Rt = 0x60000000
```

Operations:

```
* RV32:
Rd[31:0] = (Rs1[31:0] + Rs2[31:0]) u>> 1;
* RV64:
resw[31:0] = (Rs1[31:0] + Rs2[31:0]) u>> 1;
Rd[63:0] = SE(resw[31:0]);
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_URSUBW (unsigned int a, unsigned int b)

URSUBW (32-bit Unsigned Halving Subtraction)

Type: DSP

Syntax:

```
URSUBW Rd, Rs1, Rs2
```

Purpose :

Subtract 32-bit unsigned integers and the result is halved to avoid overflow or saturation.

Description :

This instruction subtracts the first 32-bit signed integer in Rs2 from the first 32-bit signed integer in Rs1. The result is first logically right-shifted by 1 bit and then sign-extended and written to Rd.

Examples:

```
* Ra = 0x7FFFFFFF, Rb = 0x80000000 Rt = 0xFFFFFFFF
* Ra = 0x80000000, Rb = 0x7FFFFFFF Rt = 0x00000000
* Ra = 0x80000000, Rb = 0x40000000 Rt = 0x20000000
```

Operations:

```
* RV32:
Rd[31:0] = (Rs1[31:0] - Rs2[31:0]) u>> 1;
* RV64:
resw[31:0] = (Rs1[31:0] - Rs2[31:0]) u>> 1;
Rd[63:0] = SE(resw[31:0]);
```

Parameters

- **a** – **[in]** unsigned int type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

OV (Overflow) flag Set/Clear Instructions

__STATIC_FORCEINLINE void __RV_CLROV (void)

__STATIC_FORCEINLINE unsigned long __RV_RDOV (void)

group **NMSIS_Core_DSP_Intrinsic_OV_FLAG_SC**

OV (Overflow) flag Set/Clear Instructions.

The following table lists the user instructions related to Overflow (OV) flag manipulation. there are 2 OV (Overflow) flag Set/Clear Instructions

Functions

__STATIC_FORCEINLINE void __RV_CLROV (void)

CLROV (Clear OV flag)

Type: DSP

Syntax:

```
CLROV # pseudo mnemonic
```

Purpose :

This pseudo instruction is an alias to `CSRRCI x0, ucode, 1` instruction.

__STATIC_FORCEINLINE unsigned long __RV_RDOV (void)

RDOV (Read OV flag)

Type: DSP

Syntax:

```
RDOV Rd   # pseudo mnemonic
```

Purpose :

This pseudo instruction is an alias to `CSRR Rd, ucode` instruction which maps to the real instruction of `CSRRS Rd, ucode, x0`.

Returns value stored in unsigned long type

Non-SIMD Miscellaneous Instructions

__STATIC_FORCEINLINE long __RV_AVE (long a, long b)

__STATIC_FORCEINLINE unsigned long __RV_BITREV (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_BPICK (unsigned long a, unsigned long b, unsigned long c)

__STATIC_FORCEINLINE unsigned long __RV_MADDR32 (unsigned long t, unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_MSUBR32 (unsigned long t, unsigned long a, unsigned long b)

__STATIC_FORCEINLINE long __RV_SRA_U (long a, unsigned int b)

__STATIC_FORCEINLINE unsigned long __RV_SWAP8 (unsigned long a)

__STATIC_FORCEINLINE unsigned long __RV_SWAP16 (unsigned long a)

__STATIC_FORCEINLINE unsigned long __RV_WEXT (long long a, unsigned int b)

__RV_BITREVI(a, b)

__RV_INSB(t, a, b)

__RV_SRAI_U(a, b)

__RV_WEXTI(a, b)

group **NMSIS_Core_DSP_Intrinsic_NON_SIMD_MISC**

Non-SIMD Miscellaneous Instructions.

There are 13 Miscellaneous Instructions here.

Defines

__RV_BITREVI(a, b)

BITREVI (Bit Reverse Immediate)

Type: DSP

Syntax:

```
(RV32) BITREVI Rd, Rs1, imm[4:0]
(RV64) BITREVI Rd, Rs1, imm[5:0]
```

Purpose :

Reverse the bit positions of the source operand within a specified width starting from bit 0. The reversed width is an immediate value.

Description :

This instruction reverses the bit positions of the content of Rs1. The reversed bit width is calculated as imm[4:0]+1 (RV32) or imm[5:0]+1 (RV64). The upper bits beyond the reversed width are filled with zeros. After the bit reverse operation, the result is written to Rd.

Operations:

```
msb = imm[4:0]; (RV32)
msb = imm[5:0]; (RV64)
rev[0:msb] = Rs1[msb:0];
Rd = ZE(rev[msb:0]);
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__RV_INSB(t, a, b)

INSB (Insert Byte)

Type: DSP

Syntax:

```
(RV32) INSB Rd, Rs1, imm[1:0]
(RV64) INSB Rd, Rs1, imm[2:0]
```

Purpose :

Insert byte 0 of a 32-bit or 64-bit register into one of the byte elements of another register.

Description :

This instruction inserts byte 0 of Rs1 into byte `imm[1:0]` (RV32) or `imm[2:0]` (RV64) of Rd.

Operations:

```
bpos = imm[1:0]; (RV32)
bpos = imm[2:0]; (RV64)
Rd.B[bpos] = Rs1.B[0]
```

Parameters

- **t** – **[in]** unsigned long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__RV_SRAI_U(a, b)

SRAI.u (Rounding Shift Right Arithmetic Immediate)

Type: DSP

Syntax:

```
SRAI.u Rd, Rs1, imm6u[4:0] (RV32)
SRAI.u Rd, Rs1, imm6u[5:0] (RV64)
```

Purpose :

Perform an arithmetic right shift operation with rounding. The shift amount is an immediate value.

Description :

This instruction right-shifts the content of Rs1 arithmetically. The shifted out bits are filled with the sign-bit and the shift amount is specified by the imm6u[4:0] (RV32) or imm6u[5:0] (RV64) constant . For the rounding operation, a value of 1 is added to the most significant discarded bit of the data to calculate the final result. And the result is written to Rd.

Operations:

```
* RV32:
sa = imm6u[4:0];
if (sa > 0) {
  res[31:-1] = SE33(Rs1[31:(sa-1)]) + 1;
```

(continues on next page)

(continued from previous page)

```
  Rd = res[31:0];
} else {
  Rd = Rs1;
}
* RV64:
sa = imm6u[5:0];
if (sa > 0) {
  res[63:-1] = SE65(Rs1[63:(sa-1)]) + 1;
  Rd = res[63:0];
} else {
  Rd = Rs1;
}
```

Parameters

- **a** – **[in]** long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in long type

__RV_WEXTI(a, b)

WEXTI (Extract Word from 64-bit Immediate)

Type: DSP

Syntax:

```
WEXTI Rd, Rs1, #LSBloc
```

Purpose :

Extract a 32-bit word from a 64-bit value stored in an even/odd pair of registers (RV32) or a register (RV64) starting from a specified immediate LSB bit position.

RV32 Description :

This instruction extracts a 32-bit word from a 64-bit value of an even/odd pair of registers specified by Rs1(4,1) starting from a specified immediate LSB bit position, #LSBloc. The extracted word is written to Rd. Rs1(4,1), i.e., d, determines the even/odd pair group of the two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the 64-bit value and the even `2d` register of the pair contains the low 32-bit of the 64-bit value.

RV64 Description :

This instruction extracts a 32-bit word from a 64-bit value in Rs1 starting from a specified immediate LSB bit position, #LSBloc. The extracted word is sign-extended and written to lower 32- bit of Rd.

Operations:

```
* RV32:
Idx0 = CONCAT(Rs1(4,1),1'b0); Idx1 = CONCAT(Rs2(4,1),1'b1);
src[63:0] = Concat(R[Idx1], R[Idx0]);
Rd = src[31+LSBloc:LSBloc];
* RV64:
ExtractW = Rs1[31+LSBloc:LSBloc];
Rd = SE(ExtractW)
```

Parameters

- **a** – **[in]** long long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

Functions

__STATIC_FORCEINLINE long __RV_AVE (long a, long b)

AVE (Average with Rounding)

Type: DSP

Syntax:

```
AVE Rd, Rs1, Rs2
```

Purpose :

Calculate the average of the contents of two general registers.

Description :

This instruction calculates the average value of two signed integers stored in Rs1 and Rs2, rounds up a half-integer result to the nearest integer, and writes the result to Rd.

Operations:

```
Sum = CONCAT(Rs1[MSB],Rs1[MSB:0]) + CONCAT(Rs2[MSB],Rs2[MSB:0]) + 1;
Rd = Sum[(MSB+1):1];
for RV32: MSB=31,
for RV64: MSB=63
```

Parameters

- **a** – **[in]** long type of value stored in a
- **b** – **[in]** long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE unsigned long __RV_BITREV (unsigned long a, unsigned long b)

BITREV (Bit Reverse)

Type: DSP

Syntax:

```
BITREV Rd, Rs1, Rs2
```

Purpose :

Reverse the bit positions of the source operand within a specified width starting from bit 0. The reversed width is a variable from a GPR.

Description :

This instruction reverses the bit positions of the content of Rs1. The reversed bit width is calculated as Rs2[4:0]+1 (RV32) or Rs2[5:0]+1 (RV64). The upper bits beyond the reversed width are filled with zeros. After the bit reverse operation, the result is written to Rd.

Operations:

```
msb = Rs2[4:0]; (for RV32)
msb = Rs2[5:0]; (for RV64)
rev[0:msb] = Rs1[msb:0];
Rd = ZE(rev[msb:0]);
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_BPICK (unsigned long a, unsigned long b, unsigned long c)

BPICK (Bit-wise Pick)

Type: DSP

Syntax:

```
BPICK Rd, Rs1, Rs2, Rc
```

Purpose :

Select from two source operands based on a bit mask in the third operand.

Description :

This instruction selects individual bits from Rs1 or Rs2, based on the bit mask value in Rc. If a bit in Rc is 1, the corresponding bit is from Rs1; otherwise, the corresponding bit is from Rs2. The selection results are written to Rd.

Operations:

```
Rd[x] = Rc[x]? Rs1[x] : Rs2[x];
for RV32, x=31...0
for RV64, x=63...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b
- **c** – **[in]** unsigned long type of value stored in c

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_MADDR32 (unsigned long t, unsigned long a, unsigned long b)

MADDR32 (Multiply and Add to 32-Bit Word)

Type: DSP

Syntax:

```
MADDR32 Rd, Rs1, Rs2
```

Purpose :

Multiply the 32-bit contents of two registers and add the lower 32-bit multiplication result to the 32-bit content of a destination register. Write the final result back to the destination register.

Description :

This instruction multiplies the lower 32-bit content of Rs1 with that of Rs2. It adds the lower 32-bit multiplication result to the lower 32-bit content of Rd and writes the final result (RV32) or sign-extended result (RV64) back to Rd. The contents of Rs1 and Rs2 can be either signed or unsigned integers.

Operations:

```
RV32:
Mresult = Rs1 * Rs2;
Rd = Rd + Mresult.W[0];
RV64:
Mresult = Rs1.W[0] * Rs2.W[0];
tres[31:0] = Rd.W[0] + Mresult.W[0];
Rd = SE64(tres[31:0]);
```

Parameters

- **t** – **[in]** unsigned long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_MSUBR32 (unsigned long t, unsigned long a, unsigned long b)

MSUBR32 (Multiply and Subtract from 32-Bit Word)

Type: DSP

Syntax:

```
MSUBR32 Rd, Rs1, Rs2
```

Purpose :

Multiply the 32-bit contents of two registers and subtract the lower 32-bit multiplication result from the 32-bit content of a destination register. Write the final result back to the destination register.

Description :

This instruction multiplies the lower 32-bit content of Rs1 with that of Rs2, subtracts the lower 32-bit multiplication result from the lower 32-bit content of Rd, then writes the final result (RV32) or sign-extended result (RV64) back to Rd. The contents of Rs1 and Rs2 can be either signed or unsigned integers.

Operations:

```
RV32:
Mresult = Rs1 * Rs2;
Rd = Rd - Mresult.W[0];
RV64:
Mresult = Rs1.W[0] * Rs2.W[0];
tres[31:0] = Rd.W[0] - Mresult.W[0];
Rd = SE64(tres[31:0]);
```

Parameters

- **t** – **[in]** unsigned long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE long __RV_SRA_U (long a, unsigned int b)

SRA.u (Rounding Shift Right Arithmetic)

Type: DSP

Syntax:

```
SRA.u Rd, Rs1, Rs2
```

Purpose :

Perform an arithmetic right shift operation with rounding. The shift amount is a variable from a GPR.

Description :

This instruction right-shifts the content of Rs1 arithmetically. The shifted out bits are filled with the sign-bit and the shift amount is specified by the low-order 5-bits (RV32) or 6-bits (RV64) of the Rs2 register. For the rounding operation, a value of 1 is added to the most significant discarded bit of the data to calculate the final result. And the result is written to Rd.

Operations:

```
* RV32:
sa = Rs2[4:0];
if (sa > 0) {
  res[31:-1] = SE33(Rs1[31:(sa-1)]) + 1;
  Rd = res[31:0];
} else {
  Rd = Rs1;
}
* RV64:
sa = Rs2[5:0];
if (sa > 0) {
  res[63:-1] = SE65(Rs1[63:(sa-1)]) + 1;
  Rd = res[63:0];
} else {
  Rd = Rs1;
}
```

Parameters

- **a** – **[in]** long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE unsigned long __RV_SWAP8 (unsigned long a)

SWAP8 (Swap Byte within Halfword)

Type: DSP

Syntax:

```
SWAP8 Rd, Rs1
```

Purpose :

Swap the bytes within each halfword of a register.

Description :

This instruction swaps the bytes within each halfword of Rs1 and writes the result to Rd.

Operations:

```
Rd.H[x] = CONCAT(Rs1.H[x][7:0],Rs1.H[x][15:8]);
for RV32: x=1...0,
for RV64: x=3...0
```

Parameters **a** – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SWAP16 (unsigned long a)

SWAP16 (Swap Halfword within Word)

Type: DSP

Syntax:

```
SWAP16 Rd, Rs1
```

Purpose :

Swap the 16-bit halfwords within each word of a register.

Description :

This instruction swaps the 16-bit halfwords within each word of Rs1 and writes the result to Rd.

Operations:

```
Rd.W[x] = CONCAT(Rs1.W[x][15:0],Rs1.H[x][31:16]);
for RV32: x=0,
for RV64: x=1...0
```

Parameters **a** – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_WEXT (long long a, unsigned int b)

WEXT (Extract Word from 64-bit)

Type: DSP

Syntax:

```
WEXT Rd, Rs1, Rs2
```

Purpose :

Extract a 32-bit word from a 64-bit value stored in an even/odd pair of registers (RV32) or a register (RV64) starting from a specified LSB bit position in a register.

RV32 Description :

This instruction extracts a 32-bit word from a 64-bit value of an even/odd pair of registers specified by Rs1(4,1) starting from a specified LSB bit position, specified in Rs2[4:0]. The extracted word is written to Rd. Rs1(4,1), i.e., d, determines the even/odd pair group of the two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the 64-bit value and the even `2d` register of the pair contains the low 32-bit of the 64-bit value.

Operations:

```
* RV32:
Idx0 = CONCAT(Rs1(4,1),1'b0); Idx1 = CONCAT(Rs1(4,1),1'b1);
src[63:0] = Concat(R[Idx1], R[Idx0]);
LSBloc = Rs2[4:0];
Rd = src[31+LSBloc:LSBloc];
* RV64:
LSBloc = Rs2[4:0];
ExtractW = Rs1[31+LSBloc:LSBloc];
Rd = SE(ExtractW)
```

Parameters

- **a** – **[in]** long long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

group **NMSIS_Core_DSP_Intrinsic_NON_SIMD**

Non-SIMD Instructions.

Partial-SIMD Data Processing Instructions

SIMD 16-bit Packing Instructions

__STATIC_FORCEINLINE unsigned long __RV_PKBB16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_PKBT16 (unsigned long a, unsigned long b)

`__STATIC_FORCEINLINE unsigned long __RV_PKTT16 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_PKTB16 (unsigned long a, unsigned long b)`

group `NMSIS_Core_DSP_Intrinsic_SIMD_16B_PACK`

SIMD 16-bit Packing Instructions.

there are 4 SIMD16-bit Packing Instructions.

Functions

`__STATIC_FORCEINLINE unsigned long __RV_PKBB16 (unsigned long a, unsigned long b)`

PKBB16 (Pack Two 16-bit Data from Both Bottom Half)

Type: DSP

Syntax:

```
PKBB16 Rd, Rs1, Rs2
PKBT16 Rd, Rs1, Rs2
PKTT16 Rd, Rs1, Rs2
PKTB16 Rd, Rs1, Rs2
```

Purpose :

Pack 16-bit data from 32-bit chunks in two registers.

- PKBB16: bottom.bottom
- PKBT16 bottom.top
- PKTT16 top.top
- PKTB16 top.bottom

Description :

(PKBB16) moves Rs1.W[x][15:0] to Rd.W[x][31:16] and moves Rs2.W[x] [15:0] to Rd.W[x] [15:0]. (PKBT16) moves Rs1.W[x] [15:0] to Rd.W[x] [31:16] and moves Rs2.W[x] [31:16] to Rd.W[x] [15:0]. (PKTT16) moves Rs1.W[x] [31:16] to Rd.W[x] [31:16] and moves Rs2.W[x] [31:16] to Rd.W[x] [15:0]. (PKTB16) moves Rs1.W[x] [31:16] to Rd.W[x] [31:16] and moves Rs2.W[x] [15:0] to Rd.W[x] [15:0].

Operations:

```
Rd.W[x][31:0] = CONCAT(Rs1.W[x][15:0], Rs2.W[x][15:0]); // PKBB16
Rd.W[x][31:0] = CONCAT(Rs1.W[x][15:0], Rs2.W[x][31:16]); // PKBT16
Rd.W[x][31:0] = CONCAT(Rs1.W[x][31:16], Rs2.W[x][15:0]); // PKTB16
Rd.W[x][31:0] = CONCAT(Rs1.W[x][31:16], Rs2.W[x][31:16]); // PKTT16
for RV32: x=0,
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_PKBT16 (unsigned long a, unsigned long b)

PKBT16 (Pack Two 16-bit Data from Bottom and Top Half)

Type: DSP

Syntax:

```
PKBB16 Rd, Rs1, Rs2
PKBT16 Rd, Rs1, Rs2
PKTT16 Rd, Rs1, Rs2
PKTB16 Rd, Rs1, Rs2
```

Purpose :

Pack 16-bit data from 32-bit chunks in two registers.

- PKBB16: bottom.bottom
- PKBT16 bottom.top
- PKTT16 top.top
- PKTB16 top.bottom

Description :

(PKBB16) moves Rs1.W[x][15:0] to Rd.W[x][31:16] and moves Rs2.W[x] [15:0] to Rd.W[x] [15:0]. (PKBT16) moves Rs1.W[x] [15:0] to Rd.W[x] [31:16] and moves Rs2.W[x] [31:16] to Rd.W[x] [15:0]. (PKTT16) moves Rs1.W[x] [31:16] to Rd.W[x] [31:16] and moves Rs2.W[x] [31:16] to Rd.W[x] [15:0]. (PKTB16) moves Rs1.W[x] [31:16] to Rd.W[x] [31:16] and moves Rs2.W[x] [15:0] to Rd.W[x] [15:0].

Operations:

```
Rd.W[x][31:0] = CONCAT(Rs1.W[x][15:0], Rs2.W[x][15:0]); // PKBB16
Rd.W[x][31:0] = CONCAT(Rs1.W[x][15:0], Rs2.W[x][31:16]); // PKBT16
Rd.W[x][31:0] = CONCAT(Rs1.W[x][31:16], Rs2.W[x][15:0]); // PKTB16
Rd.W[x][31:0] = CONCAT(Rs1.W[x][31:16], Rs2.W[x][31:16]); // PKTT16
for RV32: x=0,
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_PKTT16 (unsigned long a, unsigned long b)

PKTT16 (Pack Two 16-bit Data from Both Top Half)

Type: DSP

Syntax:

```
PKBB16 Rd, Rs1, Rs2
PKBT16 Rd, Rs1, Rs2
```

(continues on next page)

(continued from previous page)

```
PKTT16 Rd, Rs1, Rs2
PKTB16 Rd, Rs1, Rs2
```

Purpose :

Pack 16-bit data from 32-bit chunks in two registers.

- PKBB16: bottom.bottom
- PKBT16 bottom.top
- PKTT16 top.top
- PKTB16 top.bottom

Description :

(PKBB16) moves Rs1.W[x][15:0] to Rd.W[x][31:16] and moves Rs2.W[x] [15:0] to Rd.W[x] [15:0]. (PKBT16) moves Rs1.W[x] [15:0] to Rd.W[x] [31:16] and moves Rs2.W[x] [31:16] to Rd.W[x] [15:0]. (PKTT16) moves Rs1.W[x] [31:16] to Rd.W[x] [31:16] and moves Rs2.W[x] [31:16] to Rd.W[x] [15:0]. (PKTB16) moves Rs1.W[x] [31:16] to Rd.W[x] [31:16] and moves Rs2.W[x] [15:0] to Rd.W[x] [15:0].

Operations:

```
Rd.W[x][31:0] = CONCAT(Rs1.W[x][15:0], Rs2.W[x][15:0]); // PKBB16
Rd.W[x][31:0] = CONCAT(Rs1.W[x][15:0], Rs2.W[x][31:16]); // PKBT16
Rd.W[x][31:0] = CONCAT(Rs1.W[x][31:16], Rs2.W[x][15:0]); // PKTB16
Rd.W[x][31:0] = CONCAT(Rs1.W[x][31:16], Rs2.W[x][31:16]); // PKTT16
for RV32: x=0,
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_PKTB16 (unsigned long a, unsigned long b)

PKTB16 (Pack Two 16-bit Data from Top and Bottom Half)

Type: DSP

Syntax:

```
PKBB16 Rd, Rs1, Rs2
PKBT16 Rd, Rs1, Rs2
PKTT16 Rd, Rs1, Rs2
PKTB16 Rd, Rs1, Rs2
```

Purpose :

Pack 16-bit data from 32-bit chunks in two registers.

- PKBB16: bottom.bottom
- PKBT16 bottom.top
- PKTT16 top.top

- PKTB16 top.bottom

Description :

(PKBB16) moves Rs1.W[x][15:0] to Rd.W[x][31:16] and moves Rs2.W[x] [15:0] to Rd.W[x] [15:0]. (PKBT16) moves Rs1.W[x] [15:0] to Rd.W[x] [31:16] and moves Rs2.W[x] [31:16] to Rd.W[x] [15:0]. (PKTT16) moves Rs1.W[x] [31:16] to Rd.W[x] [31:16] and moves Rs2.W[x] [31:16] to Rd.W[x] [15:0]. (PKTB16) moves Rs1.W[x] [31:16] to Rd.W[x] [31:16] and moves Rs2.W[x] [15:0] to Rd.W[x] [15:0].

Operations:

```
Rd.W[x][31:0] = CONCAT(Rs1.W[x][15:0], Rs2.W[x][15:0]); // PKBB16
Rd.W[x][31:0] = CONCAT(Rs1.W[x][15:0], Rs2.W[x][31:16]); // PKBT16
Rd.W[x][31:0] = CONCAT(Rs1.W[x][31:16], Rs2.W[x][15:0]); // PKTB16
Rd.W[x][31:0] = CONCAT(Rs1.W[x][31:16], Rs2.W[x][31:16]); // PKTT16
for RV32: x=0,
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

Signed MSW 32x32 Multiply and Add Instructions

__STATIC_FORCEINLINE long __RV_KMMAC (long t, long a, long b)

__STATIC_FORCEINLINE long __RV_KMMAC_U (long t, long a, long b)

__STATIC_FORCEINLINE long __RV_KMMSB (long t, long a, long b)

__STATIC_FORCEINLINE long __RV_KMMSB_U (long t, long a, long b)

__STATIC_FORCEINLINE long __RV_KWMMUL (long a, long b)

__STATIC_FORCEINLINE long __RV_KWMMUL_U (long a, long b)

__STATIC_FORCEINLINE long __RV_SMMUL (long a, long b)

__STATIC_FORCEINLINE long __RV_SMMUL_U (long a, long b)

group **NMSIS_Core_DSP_Intrinsic_SIGNED_MSW_32X32_MAC**

Signed MSW 32x32 Multiply and Add Instructions.

there are 8 Signed MSW 32x32 Multiply and Add Instructions

Functions

__STATIC_FORCEINLINE long __RV_KMMAC (long t, long a, long b)

KMMAC (SIMD Saturating MSW Signed Multiply Word and Add)

Type: SIMD

Syntax:

```
KMMAC Rd, Rs1, Rs2
KMMAC.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of two registers and add the most significant 32-bit results with the signed 32-bit integer elements of a third register. The addition results are saturated first and then written back to the third register. The `.u` form performs an additional rounding up operation on the multiplication results before adding the most significant 32-bit part of the results.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the signed 32-bit elements of Rs2 and adds the most significant 32-bit multiplication results with the signed 32-bit elements of Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to Rd. The `.u` form of the instruction additionally rounds up the most significant 32-bit of the 64-bit multiplication results by adding a 1 to bit 31 of the results.

Operations:

```
Mres[x][63:0] = Rs1.W[x] * Rs2.W[x];
if (`.u` form) {
  Round[x][32:0] = Mres[x][63:31] + 1;
  res[x] = Rd.W[x] + Round[x][32:1];
} else {
  res[x] = Rd.W[x] + Mres[x][63:32];
}
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** long type of value stored in a
- **b** – **[in]** long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_KMMAC_U (long t, long a, long b)`

KMMAC.u (SIMD Saturating MSW Signed Multiply Word and Add with Rounding)

Type: SIMD

Syntax:

```
KMMAC Rd, Rs1, Rs2
KMMAC.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of two registers and add the most significant 32-bit results with the signed 32-bit integer elements of a third register. The addition results are saturated first and then written back to the third register. The `.u` form performs an additional rounding up operation on the multiplication results before adding the most significant 32-bit part of the results.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the signed 32-bit elements of Rs2 and adds the most significant 32-bit multiplication results with the signed 32-bit elements of Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to Rd. The `.u` form of the instruction additionally rounds up the most significant 32-bit of the 64-bit multiplication results by adding a 1 to bit 31 of the results.

Operations:

```
Mres[x][63:0] = Rs1.W[x] * Rs2.W[x];
if (`.u` form) {
  Round[x][32:0] = Mres[x][63:31] + 1;
  res[x] = Rd.W[x] + Round[x][32:1];
} else {
  res[x] = Rd.W[x] + Mres[x][63:32];
}
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- `t` – **[in]** long type of value stored in t
- `a` – **[in]** long type of value stored in a
- `b` – **[in]** long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_KMMSB (long t, long a, long b)`

KMMSB (SIMD Saturating MSW Signed Multiply Word and Subtract)

Type: SIMD

Syntax:

```
KMMSB Rd, Rs1, Rs2
KMMSB.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of two registers and subtract the most significant 32-bit results from the signed 32-bit elements of a third register. The subtraction results are written to the third register. The `.u` form performs an additional rounding up operation on the multiplication results before subtracting the most significant 32-bit part of the results.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the signed 32-bit elements of Rs2 and subtracts the most significant 32-bit multiplication results from the signed 32-bit elements of Rd. If the subtraction result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to Rd. The `.u` form of the instruction additionally rounds up the most significant 32-bit of the 64-bit multiplication results by adding a 1 to bit 31 of the results.

Operations:

```
Mres[x][63:0] = Rs1.W[x] * Rs2.W[x];
if (`.u` form) {
  Round[x][32:0] = Mres[x][63:31] + 1;
  res[x] = Rd.W[x] - Round[x][32:1];
} else {
  res[x] = Rd.W[x] - Mres[x][63:32];
}
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** long type of value stored in a
- **b** – **[in]** long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMMSB_U (long t, long a, long b)

KMMSB.u (SIMD Saturating MSW Signed Multiply Word and Subtraction with Rounding)

Type: SIMD

Syntax:

```
KMMSB Rd, Rs1, Rs2
KMMSB.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of two registers and subtract the most significant 32-bit results from the signed 32-bit elements of a third register. The subtraction results are written to the third register. The `.u` form performs an additional rounding up operation on the multiplication results before subtracting the most significant 32-bit part of the results.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the signed 32-bit elements of Rs2 and subtracts the most significant 32-bit multiplication results from the signed 32-bit elements of Rd. If the subtraction result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to Rd. The `.u` form of the instruction additionally rounds up the most significant 32-bit of the 64-bit multiplication results by adding a 1 to bit 31 of the results.

Operations:

```
Mres[x][63:0] = Rs1.W[x] * Rs2.W[x];
if (`.u` form) {
  Round[x][32:0] = Mres[x][63:31] + 1;
  res[x] = Rd.W[x] - Round[x][32:1];
} else {
  res[x] = Rd.W[x] - Mres[x][63:32];
}
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** long type of value stored in a
- **b** – **[in]** long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_KWMMUL (long a, long b)`

KWMMUL (SIMD Saturating MSW Signed Multiply Word & Double)

Type: SIMD

Syntax:

```
KWMMUL Rd, Rs1, Rs2
KWMMUL.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of two registers, shift the results left 1-bit, saturate, and write the most significant 32-bit results to a register. The `.u` form additionally rounds up the multiplication results from the most signification discarded bit.

Description :

This instruction multiplies the 32-bit elements of Rs1 with the 32-bit elements of Rs2. It then shifts the multiplication results one bit to the left and takes the most significant 32-bit results. If the shifted result is greater than 2^31-1, it is saturated to 2^31-1 and the OV flag is set to 1. The final element result is written to Rd. The 32-bit elements of Rs1 and Rs2 are treated as signed integers. The `.u` form of the instruction additionally rounds up the 64-bit multiplication results by adding a 1 to bit 30 before the shift and saturation operations.

Operations:

```
if ((0x80000000 != Rs1.W[x]) | (0x80000000 != Rs2.W[x])) {
  Mres[x][63:0] = Rs1.W[x] * Rs2.W[x];
  if (`.u` form) {
    Round[x][33:0] = Mres[x][63:30] + 1;
    Rd.W[x] = Round[x][32:1];
  } else {
    Rd.W[x] = Mres[x][62:31];
  }
} else {
  Rd.W[x] = 0x7fffffff;
  OV = 1;
}
for RV32: x=0
for RV64: x=1...0
```

Parameters

- `a` – **[in]** long type of value stored in a
- `b` – **[in]** long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_KWMMUL_U (long a, long b)`

KWMMUL.u (SIMD Saturating MSW Signed Multiply Word & Double with Rounding)

Type: SIMD

Syntax:

```
KWMMUL Rd, Rs1, Rs2
KWMMUL.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of two registers, shift the results left 1-bit, saturate, and write the most significant 32-bit results to a register. The `.u` form additionally rounds up the multiplication results from the most signification discarded bit.

Description :

This instruction multiplies the 32-bit elements of Rs1 with the 32-bit elements of Rs2. It then shifts the multiplication results one bit to the left and takes the most significant 32-bit results. If the shifted result is greater than 2^31-1, it is saturated to 2^31-1 and the OV flag is set to 1. The final element result is written to Rd. The 32-bit elements of Rs1 and Rs2 are treated as signed integers. The `.u` form of the instruction additionally rounds up the 64-bit multiplication results by adding a 1 to bit 30 before the shift and saturation operations.

Operations:

```
if ((0x80000000 != Rs1.W[x]) | (0x80000000 != Rs2.W[x])) {
  Mres[x][63:0] = Rs1.W[x] * Rs2.W[x];
  if (`.u` form) {
    Round[x][33:0] = Mres[x][63:30] + 1;
    Rd.W[x] = Round[x][32:1];
  } else {
    Rd.W[x] = Mres[x][62:31];
  }
} else {
  Rd.W[x] = 0x7fffffff;
  OV = 1;
}
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **a** – **[in]** long type of value stored in a
- **b** – **[in]** long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_SMMUL (long a, long b)`

SMMUL (SIMD MSW Signed Multiply Word)

Type: SIMD

Syntax:

```
SMMUL Rd, Rs1, Rs2
SMMUL.u Rd, Rs1, Rs2
```

Purpose :

Multiply the 32-bit signed integer elements of two registers and write the most significant 32-bit results to the corresponding 32-bit elements of a register. The `.u` form performs an additional rounding up operation on the multiplication results before taking the most significant 32-bit part of the results.

Description :

This instruction multiplies the 32-bit elements of Rs1 with the 32-bit elements of Rs2 and writes the most significant 32-bit multiplication results to the corresponding 32-bit elements of Rd. The 32-bit elements of Rs1 and Rs2 are treated as signed integers. The `.u` form of the instruction rounds up the most significant 32-bit of the 64-bit multiplication results by adding a 1 to bit 31 of the results.

- For `smmul/RV32` instruction, it is an alias to `mulh/RV32` instruction.

Operations:

```
Mres[x][63:0] = Rs1.W[x] * Rs2.W[x];
if (`.u` form) {
  Round[x][32:0] = Mres[x][63:31] + 1;
  Rd.W[x] = Round[x][32:1];
} else {
  Rd.W[x] = Mres[x][63:32];
}
for RV32: x=0
for RV64: x=1...0
```

Parameters

- a – **[in]** long type of value stored in a
- b – **[in]** long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_SMMUL_U (long a, long b)

SMMUL.u (SIMD MSW Signed Multiply Word with Rounding)

Type: SIMD

Syntax:

```
SMMUL Rd, Rs1, Rs2
SMMUL.u Rd, Rs1, Rs2
```

Purpose :

Multiply the 32-bit signed integer elements of two registers and write the most significant 32-bit results to the corresponding 32-bit elements of a register. The `.u` form performs an additional rounding up operation on the multiplication results before taking the most significant 32-bit part of the results.

Description :

This instruction multiplies the 32-bit elements of Rs1 with the 32-bit elements of Rs2 and writes the most significant 32-bit multiplication results to the corresponding 32-bit elements of Rd. The 32-bit elements of Rs1 and Rs2 are treated as signed integers. The `.u` form of the instruction rounds up the most significant 32-bit of the 64-bit multiplication results by adding a 1 to bit 31 of the results.

- For `smmul/RV32` instruction, it is an alias to `mulh/RV32` instruction.

Operations:

```
Mres[x][63:0] = Rs1.W[x] * Rs2.W[x];
if (`.u` form) {
  Round[x][32:0] = Mres[x][63:31] + 1;
  Rd.W[x] = Round[x][32:1];
} else {
  Rd.W[x] = Mres[x][63:32];
}
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **a** – **[in]** long type of value stored in a
- **b** – **[in]** long type of value stored in b

Returns value stored in long type

Signed MSW 32x16 Multiply and Add Instructions

`__STATIC_FORCEINLINE long __RV_KMMAWB (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMMAWB_U (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMMAWB2 (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMMAWB2_U (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMMAWT (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMMAWT_U (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMMAWT2 (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMMAWT2_U (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMMWB2 (long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMMWB2_U (long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMMWT2 (long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMMWT2_U (long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_SMMWB (long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_SMMWB_U (long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_SMMWT (long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_SMMWT_U (long a, unsigned long b)`

group `NMSIS_Core_DSP_Intrinsic_SIGNED_MSW_32X16_MAC`

Signed MSW 32x16 Multiply and Add Instructions.

there are 15 Signed MSW 32x16 Multiply and Add Instructions

Functions

`__STATIC_FORCEINLINE long __RV_KMMAWB (long t, unsigned long a, unsigned long b)`

KMMAWB (SIMD Saturating MSW Signed Multiply Word and Bottom Half and Add)

Type: SIMD

Syntax:

```
KMMAWB Rd, Rs1, Rs2
KMMAWB.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of one register and the bottom 16-bit of the corresponding 32-bit elements of another register and add the most significant 32-bit results with the corresponding signed 32-bit elements of a third register. The addition result is written to the corresponding 32-bit elements of the third register. The `.u` form rounds up the multiplication results from the most significant discarded bit before the addition operations.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the signed bottom 16-bit content of the corresponding 32-bit elements of Rs2 and adds the most significant 32-bit multiplication results with the corresponding signed 32-bit elements of Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit multiplication results by adding a 1 to bit 15 of the result before the addition operations.

Operations:

```
Mres[x][47:0] = Rs1.W[x] * Rs2.W[x].H[0];
if (`.u` form) {
  Round[x][32:0] = Mres[x][47:15] + 1;
  res[x] = Rd.W[x] + Round[x][32:1];
} else {
  res[x] = Rd.W[x] + Mres[x][47:16];
}
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_KMMAWB_U (long t, unsigned long a, unsigned long b)`

KMMAWB.u (SIMD Saturating MSW Signed Multiply Word and Bottom Half and Add with Rounding)

Type: SIMD

Syntax:

```
KMMAWB Rd, Rs1, Rs2
KMMAWB.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of one register and the bottom 16-bit of the corresponding 32-bit elements of another register and add the most significant 32-bit results with the corresponding signed 32-bit elements of a third register. The addition result is written to the corresponding 32-bit elements of the third register. The `.u` form rounds up the multiplication results from the most significant discarded bit before the addition operations.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the signed bottom 16-bit content of the corresponding 32-bit elements of Rs2 and adds the most significant 32-bit multiplication results with the corresponding signed 32-bit elements of Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit multiplication results by adding a 1 to bit 15 of the result before the addition operations.

Operations:

```
Mres[x][47:0] = Rs1.W[x] * Rs2.W[x].H[0];
if (`.u` form) {
  Round[x][32:0] = Mres[x][47:15] + 1;
  res[x] = Rd.W[x] + Round[x][32:1];
} else {
  res[x] = Rd.W[x] + Mres[x][47:16];
}
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- `t` – **[in]** long type of value stored in t
- `a` – **[in]** unsigned long type of value stored in a
- `b` – **[in]** unsigned long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_KMMAWB2 (long t, unsigned long a, unsigned long b)`

KMMAWB2 (SIMD Saturating MSW Signed Multiply Word and Bottom Half & 2 and Add)

Type: SIMD

Syntax:

```
KMMAWB2 Rd, Rs1, Rs2
KMMAWB2.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit elements of one register and the bottom 16-bit of the corresponding 32-bit elements of another register, double the multiplication results and add the saturated most significant 32-bit results with the corresponding signed 32-bit elements of a third register. The saturated addition result is written to the corresponding 32-bit elements of the third register. The `.u` form rounds up the multiplication results from the most significant discarded bit before the addition operations.

Description :

This instruction multiplies the signed 32-bit Q31 elements of Rs1 with the signed bottom 16-bit Q15 content of the corresponding 32-bit elements of Rs2, doubles the Q46 results to Q47 numbers and adds the saturated most significant 32-bit Q31 multiplication results with the corresponding signed 32-bit elements of Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit Q47 multiplication results by adding a 1 to bit 15 (i.e., bit 14 before doubling) of the result before the addition operations.

Operations:

```
if ((Rs1.W[x] == 0x80000000) & (Rs2.W[x].H[0] == 0x8000)) {
  addop.W[x] = 0x7fffffff;
  OV = 1;
} else {
  Mres[x][47:0] = Rs1.W[x] s* Rs2.W[x].H[0];
  if (`.u` form) {
    Mres[x][47:14] = Mres[x][47:14] + 1;
  }
  addop.W[x] = Mres[x][46:15]; // doubling
}
res[x] = Rd.W[x] + addop.W[x];
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_KMMAWB2_U (long t, unsigned long a, unsigned long b)`

KMMAWB2.u (SIMD Saturating MSW Signed Multiply Word and Bottom Half & 2 and Add with Rounding)

Type: SIMD

Syntax:

```
KMMAWB2 Rd, Rs1, Rs2
KMMAWB2.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit elements of one register and the bottom 16-bit of the corresponding 32-bit elements of another register, double the multiplication results and add the saturated most significant 32-bit results with the corresponding signed 32-bit elements of a third register. The saturated addition result is written to the corresponding 32-bit elements of the third register. The `.u` form rounds up the multiplication results from the most significant discarded bit before the addition operations.

Description :

This instruction multiplies the signed 32-bit Q31 elements of Rs1 with the signed bottom 16-bit Q15 content of the corresponding 32-bit elements of Rs2, doubles the Q46 results to Q47 numbers and adds the saturated most significant 32-bit Q31 multiplication results with the corresponding signed 32-bit elements of Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit Q47 multiplication results by adding a 1 to bit 15 (i.e., bit 14 before doubling) of the result before the addition operations.

Operations:

```
if ((Rs1.W[x] == 0x80000000) & (Rs2.W[x].H[0] == 0x8000)) {
  addop.W[x] = 0x7fffffff;
  OV = 1;
} else {
  Mres[x][47:0] = Rs1.W[x] s* Rs2.W[x].H[0];
  if (`.u` form) {
    Mres[x][47:14] = Mres[x][47:14] + 1;
  }
  addop.W[x] = Mres[x][46:15]; // doubling
}
res[x] = Rd.W[x] + addop.W[x];
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
```

(continues on next page)

(continued from previous page)

```
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMMAWT (long t, unsigned long a, unsigned long b)

KMMAWT (SIMD Saturating MSW Signed Multiply Word and Top Half and Add)

Type: SIMD

Syntax:

```
KMMAWT Rd, Rs1, Rs2
KMMAWT.u Rd Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of one register and the signed top 16-bit of the corresponding 32-bit elements of another register and add the most significant 32-bit results with the corresponding signed 32-bit elements of a third register. The addition results are written to the corresponding 32-bit elements of the third register. The `.u` form rounds up the multiplication results from the most significant discarded bit before the addition operations.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the signed top 16-bit of the corresponding 32-bit elements of Rs2 and adds the most significant 32-bit multiplication results with the corresponding signed 32-bit elements of Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit multiplication results by adding a 1 to bit 15 of the result before the addition operations.

Operations:

```
Mres[x][47:0] = Rs1.W[x] * Rs2.W[x].H[1];
if (`.u` form) {
  Round[x][32:0] = Mres[x][47:15] + 1;
  res[x] = Rd.W[x] + Round[x][32:1];
} else {
  res[x] = Rd.W[x] + Mres[x][47:16];
}
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
```

(continues on next page)

(continued from previous page)

```
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMMAWT_U (long t, unsigned long a, unsigned long b)

KMMAWT.u (SIMD Saturating MSW Signed Multiply Word and Top Half and Add with Rounding)

Type: SIMD

Syntax:

```
KMMAWT Rd, Rs1, Rs2
KMMAWT.u Rd Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of one register and the signed top 16-bit of the corresponding 32-bit elements of another register and add the most significant 32-bit results with the corresponding signed 32-bit elements of a third register. The addition results are written to the corresponding 32-bit elements of the third register. The `.u` form rounds up the multiplication results from the most significant discarded bit before the addition operations.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the signed top 16-bit of the corresponding 32-bit elements of Rs2 and adds the most significant 32-bit multiplication results with the corresponding signed 32-bit elements of Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit multiplication results by adding a 1 to bit 15 of the result before the addition operations.

Operations:

```
Mres[x][47:0] = Rs1.W[x] * Rs2.W[x].H[1];
if (`.u` form) {
  Round[x][32:0] = Mres[x][47:15] + 1;
  res[x] = Rd.W[x] + Round[x][32:1];
} else {
  res[x] = Rd.W[x] + Mres[x][47:16];
}
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
```

(continues on next page)

(continued from previous page)

```
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMMAWT2 (long t, unsigned long a, unsigned long b)

KMMAWT2 (SIMD Saturating MSW Signed Multiply Word and Top Half & 2 and Add)

Type: SIMD

Syntax:

```
KMMAWT2 Rd, Rs1, Rs2
KMMAWT2.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit elements of one register and the top 16-bit of the corresponding 32-bit elements of another register, double the multiplication results and add the saturated most significant 32-bit results with the corresponding signed 32-bit elements of a third register. The saturated addition result is written to the corresponding 32-bit elements of the third register. The `.u` form rounds up the multiplication results from the most significant discarded bit before the addition operations.

Description :

This instruction multiplies the signed 32-bit Q31 elements of Rs1 with the signed top 16-bit Q15 content of the corresponding 32-bit elements of Rs2, doubles the Q46 results to Q47 numbers and adds the saturated most significant 32-bit Q31 multiplication results with the corresponding signed 32-bit elements of Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit Q47 multiplication results by adding a 1 to bit 15 (i.e., bit 14 before doubling) of the result before the addition operations.

Operations:

```
if ((Rs1.W[x] == 0x80000000) & (Rs2.W[x].H[1] == 0x8000)) {
  addop.W[x] = 0x7fffffff;
  OV = 1;
} else {
  Mres[x][47:0] = Rs1.W[x] s* Rs2.W[x].H[1];
  if (`.u` form) {
    Mres[x][47:14] = Mres[x][47:14] + 1;
  }
  addop.W[x] = Mres[x][46:15]; // doubling
}
res[x] = Rd.W[x] + addop.W[x];
```

(continues on next page)

(continued from previous page)

```
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMMAWT2_U (long t, unsigned long a, unsigned long b)

KMMAWT2.u (SIMD Saturating MSW Signed Multiply Word and Top Half & 2 and Add with Rounding)

Type: SIMD

Syntax:

```
KMMAWT2 Rd, Rs1, Rs2
KMMAWT2.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit elements of one register and the top 16-bit of the corresponding 32-bit elements of another register, double the multiplication results and add the saturated most significant 32-bit results with the corresponding signed 32-bit elements of a third register. The saturated addition result is written to the corresponding 32-bit elements of the third register. The `.u` form rounds up the multiplication results from the most significant discarded bit before the addition operations.

Description :

This instruction multiplies the signed 32-bit Q31 elements of Rs1 with the signed top 16-bit Q15 content of the corresponding 32-bit elements of Rs2, doubles the Q46 results to Q47 numbers and adds the saturated most significant 32-bit Q31 multiplication results with the corresponding signed 32-bit elements of Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit Q47 multiplication results by adding a 1 to bit 15 (i.e., bit 14 before doubling) of the result before the addition operations.

Operations:

```
if ((Rs1.W[x] == 0x80000000) & (Rs2.W[x].H[1] == 0x8000)) {
  addop.W[x] = 0x7fffffff;
  OV = 1;
} else {
  Mres[x][47:0] = Rs1.W[x] s* Rs2.W[x].H[1];
```

(continues on next page)

(continued from previous page)

```
  if (`.u` form) {
    Mres[x][47:14] = Mres[x][47:14] + 1;
  }
  addop.W[x] = Mres[x][46:15]; // doubling
}
res[x] = Rd.W[x] + addop.W[x];
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMMWB2 (long a, unsigned long b)

KMMWB2 (SIMD Saturating MSW Signed Multiply Word and Bottom Half & 2)

Type: SIMD

Syntax:

```
KMMWB2 Rd, Rs1, Rs2
KMMWB2.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of one register and the bottom 16-bit of the corresponding 32-bit elements of another register, double the multiplication results and write the saturated most significant 32-bit results to the corresponding 32-bit elements of a register. The `.u` form rounds up the results from the most significant discarded bit.

Description :

This instruction multiplies the signed 32-bit Q31 elements of Rs1 with the signed bottom 16-bit Q15 content of the corresponding 32-bit elements of Rs2, doubles the Q46 results to Q47 numbers and writes the saturated most significant 32-bit Q31 multiplication results to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit Q47 multiplication results by adding a 1 to bit 15 (i.e., bit 14 before doubling) of the results.

Operations:

```
if ((Rs1.W[x] == 0x80000000) & (Rs2.W[x].H[0] == 0x8000)) {
  Rd.W[x] = 0x7fffffff;
```

(continues on next page)

(continued from previous page)

```
  OV = 1;
} else {
  Mres[x][47:0] = Rs1.W[x] s* Rs2.W[x].H[0];
  if (`.u` form) {
    Round[x][32:0] = Mres[x][46:14] + 1;
    Rd.W[x] = Round[x][32:1];
  } else {
    Rd.W[x] = Mres[x][46:15];
  }
}
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **a** – **[in]** long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMMWB2_U (long a, unsigned long b)

KMMWB2.u (SIMD Saturating MSW Signed Multiply Word and Bottom Half & 2 with Rounding)

Type: SIMD

Syntax:

```
KMMWB2 Rd, Rs1, Rs2
KMMWB2.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of one register and the bottom 16-bit of the corresponding 32-bit elements of another register, double the multiplication results and write the saturated most significant 32-bit results to the corresponding 32-bit elements of a register. The `.u` form rounds up the results from the most significant discarded bit.

Description :

This instruction multiplies the signed 32-bit Q31 elements of Rs1 with the signed bottom 16-bit Q15 content of the corresponding 32-bit elements of Rs2, doubles the Q46 results to Q47 numbers and writes the saturated most significant 32-bit Q31 multiplication results to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit Q47 multiplication results by adding a 1 to bit 15 (i.e., bit 14 before doubling) of the results.

Operations:

```
if ((Rs1.W[x] == 0x80000000) & (Rs2.W[x].H[0] == 0x8000)) {
  Rd.W[x] = 0x7fffffff;
  OV = 1;
} else {
  Mres[x][47:0] = Rs1.W[x] s* Rs2.W[x].H[0];
  if (`.u` form) {
    Round[x][32:0] = Mres[x][46:14] + 1;
    Rd.W[x] = Round[x][32:1];
```

(continues on next page)

(continued from previous page)

```
  } else {
    Rd.W[x] = Mres[x][46:15];
  }
}
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **a** – **[in]** long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMMWT2 (long a, unsigned long b)

KMMWT2 (SIMD Saturating MSW Signed Multiply Word and Top Half & 2)

Type: SIMD

Syntax:

```
KMMWT2 Rd, Rs1, Rs2
KMMWT2.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of one register and the top 16-bit of the corresponding 32-bit elements of another register, double the multiplication results and write the saturated most significant 32-bit results to the corresponding 32-bit elements of a register. The `.u` form rounds up the results from the most significant discarded bit.

Description :

This instruction multiplies the signed 32-bit Q31 elements of Rs1 with the signed top 16-bit Q15 content of the corresponding 32-bit elements of Rs2, doubles the Q46 results to Q47 numbers and writes the saturated most significant 32-bit Q31 multiplication results to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit Q47 multiplication results by adding a 1 to bit 15 (i.e., bit 14 before doubling) of the results.

Operations:

```
if ((Rs1.W[x] == 0x80000000) & (Rs2.W[x].H[1] == 0x8000)) {
  Rd.W[x] = 0x7fffffff;
  OV = 1;
} else {
  Mres[x][47:0] = Rs1.W[x] s* Rs2.W[x].H[1];
  if (`.u` form) {
    Round[x][32:0] = Mres[x][46:14] + 1;
    Rd.W[x] = Round[x][32:1];
  } else {
    Rd.W[x] = Mres[x][46:15];
  }
}
for RV32: x=0
for RV64: x=1...0
```

Parameters

- a – **[in]** long type of value stored in a
- b – **[in]** unsigned long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_KMMWT2_U (long a, unsigned long b)`

KMMWT2.u (SIMD Saturating MSW Signed Multiply Word and Top Half & 2 with Rounding)

Type: SIMD

Syntax:

```
KMMWT2 Rd, Rs1, Rs2
KMMWT2.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of one register and the top 16-bit of the corresponding 32-bit elements of another register, double the multiplication results and write the saturated most significant 32-bit results to the corresponding 32-bit elements of a register. The `.u` form rounds up the results from the most significant discarded bit.

Description :

This instruction multiplies the signed 32-bit Q31 elements of Rs1 with the signed top 16-bit Q15 content of the corresponding 32-bit elements of Rs2, doubles the Q46 results to Q47 numbers and writes the saturated most significant 32-bit Q31 multiplication results to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit Q47 multiplication results by adding a 1 to bit 15 (i.e., bit 14 before doubling) of the results.

Operations:

```
if ((Rs1.W[x] == 0x80000000) & (Rs2.W[x].H[1] == 0x8000)) {
  Rd.W[x] = 0x7fffffff;
  OV = 1;
} else {
  Mres[x][47:0] = Rs1.W[x] s* Rs2.W[x].H[1];
  if (`.u` form) {
    Round[x][32:0] = Mres[x][46:14] + 1;
    Rd.W[x] = Round[x][32:1];
  } else {
    Rd.W[x] = Mres[x][46:15];
  }
}
for RV32: x=0
for RV64: x=1...0
```

Parameters

- a – **[in]** long type of value stored in a
- b – **[in]** unsigned long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_SMMWB (long a, unsigned long b)`

SMMWB (SIMD MSW Signed Multiply Word and Bottom Half)

Type: SIMD

Syntax:

```
SMMWB Rd, Rs1, Rs2
SMMWB.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of one register and the bottom 16-bit of the corresponding 32-bit elements of another register, and write the most significant 32-bit results to the corresponding 32-bit elements of a register. The `.u` form rounds up the results from the most significant discarded bit.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the signed bottom 16-bit content of the corresponding 32-bit elements of Rs2 and writes the most significant 32-bit multiplication results to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit multiplication results by adding a 1 to bit 15 of the results.

Operations:

```
Mres[x][47:0] = Rs1.W[x] * Rs2.W[x].H[0];
if (`.u` form) {
  Round[x][32:0] = Mres[x][47:15] + 1;
  Rd.W[x] = Round[x][32:1];
} else {
  Rd.W[x] = Mres[x][47:16];
}
for RV32: x=0
for RV64: x=1...0
```

Parameters

- `a` – **[in]** long type of value stored in a
- `b` – **[in]** unsigned long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_SMMWB_U (long a, unsigned long b)`

SMMWB.u (SIMD MSW Signed Multiply Word and Bottom Half with Rounding)

Type: SIMD

Syntax:

```
SMMWB Rd, Rs1, Rs2
SMMWB.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of one register and the bottom 16-bit of the corresponding 32-bit elements of another register, and write the most significant 32-bit results to the corresponding 32-bit elements of a register. The `.u` form rounds up the results from the most significant discarded bit.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the signed bottom 16-bit content of the corresponding 32-bit elements of Rs2 and writes the most significant 32-bit multiplication results to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit multiplication results by adding a 1 to bit 15 of the results.

Operations:

```
Mres[x][47:0] = Rs1.W[x] * Rs2.W[x].H[0];
if (`.u` form) {
  Round[x][32:0] = Mres[x][47:15] + 1;
  Rd.W[x] = Round[x][32:1];
} else {
  Rd.W[x] = Mres[x][47:16];
}
for RV32: x=0
for RV64: x=1...0
```

Parameters

- `a` – **[in]** long type of value stored in a
- `b` – **[in]** unsigned long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_SMMWT (long a, unsigned long b)`

SMMWT (SIMD MSW Signed Multiply Word and Top Half)

Type: SIMD

Syntax:

```
SMMWT Rd, Rs1, Rs2
SMMWT.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of one register and the top 16-bit of the corresponding 32-bit elements of another register, and write the most significant 32-bit results to the corresponding 32-bit elements of a register. The `.u` form rounds up the results from the most significant discarded bit.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the top signed 16-bit content of the corresponding 32-bit elements of Rs2 and writes the most significant 32-bit multiplication results to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit multiplication results by adding a 1 to bit 15 of the results.

Operations:

```
Mres[x][47:0] = Rs1.W[x] * Rs2.W[x].H[1];
if (`.u` form) {
  Round[x][32:0] = Mres[x][47:15] + 1;
  Rd.W[x] = Round[x][32:1];
} else {
  Rd.W[x] = Mres[x][47:16];
```

(continues on next page)

(continued from previous page)

```
}
for RV32: x=0
for RV64: x=1...0
```

Parameters

- a – **[in]** long type of value stored in a
- b – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_SMMWT_U (long a, unsigned long b)

SMMWT.u (SIMD MSW Signed Multiply Word and Top Half with Rounding)

Type: SIMD

Syntax:

```
SMMWT Rd, Rs1, Rs2
SMMWT.u Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit integer elements of one register and the top 16-bit of the corresponding 32-bit elements of another register, and write the most significant 32-bit results to the corresponding 32-bit elements of a register. The `.u` form rounds up the results from the most significant discarded bit.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the top signed 16-bit content of the corresponding 32-bit elements of Rs2 and writes the most significant 32-bit multiplication results to the corresponding 32-bit elements of Rd. The `.u` form of the instruction rounds up the most significant 32-bit of the 48-bit multiplication results by adding a 1 to bit 15 of the results.

Operations:

```
Mres[x][47:0] = Rs1.W[x] * Rs2.W[x].H[1];
if (`.u` form) {
  Round[x][32:0] = Mres[x][47:15] + 1;
  Rd.W[x] = Round[x][32:1];
} else {
  Rd.W[x] = Mres[x][47:16];
}
for RV32: x=0
for RV64: x=1...0
```

Parameters

- a – **[in]** long type of value stored in a
- b – **[in]** unsigned long type of value stored in b

Returns value stored in long type

Signed 16-bit Multiply 32-bit Add/Subtract Instructions

`__STATIC_FORCEINLINE long __RV_KMABB (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMABT (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMATT (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMADA (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMAXDA (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMADS (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMADRS (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMAXDS (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMDA (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMXDA (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMSDA (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMSXDA (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_SMBB16 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_SMBT16 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_SMTT16 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_SMDS (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_SMDRS (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_SMXDS (unsigned long a, unsigned long b)`

group `NMSIS_Core_DSP_Intrinsic_SIGNED_16B_MULT_32B_ADDSUB`

Signed 16-bit Multiply 32-bit Add/Subtract Instructions.

there are 18 Signed 16-bit Multiply 32-bit Add/Subtract Instructions

Functions

__STATIC_FORCEINLINE long __RV_KMABB (long t, unsigned long a, unsigned long b)

KMABB (SIMD Saturating Signed Multiply Bottom Halfs & Add)

Type: SIMD

Syntax:

```
KMABB Rd, Rs1, Rs2
KMABT Rd, Rs1, Rs2
KMATT Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 16-bit content of 32-bit elements in a register with the 16-bit content of 32-bit elements in another register and add the result to the content of 32-bit elements in the third register. The addition result may be saturated and is written to the third register.

- KMABB: rd.W[x] + bottom*bottom (per 32-bit element)
- KMABT rd.W[x] + bottom*top (per 32-bit element)
- KMATT rd.W[x] + top*top (per 32-bit element)

Description :

For the `KMABB` instruction, it multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2. For the `KMABT` instruction, it multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2. For the `KMATT` instruction, it multiplies the top 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2. The multiplication result is added to the content of 32-bit elements in Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to

a. The results after saturation are written to Rd. The 16-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res[x] = Rd.W[x] + (Rs1.W[x].H[0] * Rs2.W[x].H[0]); // KMABB
res[x] = Rd.W[x] + (Rs1.W[x].H[0] * Rs2.W[x].H[1]); // KMABT
res[x] = Rd.W[x] + (Rs1.W[x].H[1] * Rs2.W[x].H[1]); // KMATT
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a

- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMABT (long t, unsigned long a, unsigned long b)

KMABT (SIMD Saturating Signed Multiply Bottom & Top Halfs & Add)

Type: SIMD

Syntax:

```
KMABB Rd, Rs1, Rs2
KMABT Rd, Rs1, Rs2
KMATT Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 16-bit content of 32-bit elements in a register with the 16-bit content of 32-bit elements in another register and add the result to the content of 32-bit elements in the third register. The addition result may be saturated and is written to the third register.

- KMABB: rd.W[x] + bottom*bottom (per 32-bit element)
- KMABT rd.W[x] + bottom*top (per 32-bit element)
- KMATT rd.W[x] + top*top (per 32-bit element)

Description :

For the KMABB instruction, it multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2. For the KMABT instruction, it multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2. For the KMATT instruction, it multiplies the top 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2. The multiplication result is added to the content of 32-bit elements in Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to

a. The results after saturation are written to Rd. The 16-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res[x] = Rd.W[x] + (Rs1.W[x].H[0] * Rs2.W[x].H[0]); // KMABB
res[x] = Rd.W[x] + (Rs1.W[x].H[0] * Rs2.W[x].H[1]); // KMABT
res[x] = Rd.W[x] + (Rs1.W[x].H[1] * Rs2.W[x].H[1]); // KMATT
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMATT (long t, unsigned long a, unsigned long b)

KMATT (SIMD Saturating Signed Multiply Top Halfs & Add)

Type: SIMD

Syntax:

```
KMABB Rd, Rs1, Rs2
KMABT Rd, Rs1, Rs2
KMATT Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 16-bit content of 32-bit elements in a register with the 16-bit content of 32-bit elements in another register and add the result to the content of 32-bit elements in the third register. The addition result may be saturated and is written to the third register.

- KMABB: rd.W[x] + bottom*bottom (per 32-bit element)
- KMABT rd.W[x] + bottom*top (per 32-bit element)
- KMATT rd.W[x] + top*top (per 32-bit element)

Description :

For the KMABB instruction, it multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2. For the KMABT instruction, it multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2. For the KMATT instruction, it multiplies the top 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2. The multiplication result is added to the content of 32-bit elements in Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to

a. The results after saturation are written to Rd. The 16-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res[x] = Rd.W[x] + (Rs1.W[x].H[0] * Rs2.W[x].H[0]); // KMABB
res[x] = Rd.W[x] + (Rs1.W[x].H[0] * Rs2.W[x].H[1]); // KMABT
res[x] = Rd.W[x] + (Rs1.W[x].H[1] * Rs2.W[x].H[1]); // KMATT
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMADA (long t, unsigned long a, unsigned long b)

KMADA (SIMD Saturating Signed Multiply Two Halfs and Two Adds)

Type: SIMD

Syntax:

```
KMADA Rd, Rs1, Rs2
KMAXDA Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from 32-bit elements in two registers; and then adds the two 32-bit results and 32-bit elements in a third register together. The addition result may be saturated.

- KMADA: rd.W[x] + top*top + bottom*bottom (per 32-bit element)
- KMAXDA: rd.W[x] + top*bottom + bottom*top (per 32-bit element)

Description :

For the `KMADA instruction, it multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2 and then adds the result to the result of multiplying the top 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2. For the `KMAXDA` instruction, it multiplies the top 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2 and then adds the result to the result of multiplying the bottom 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2. The result is added to the content of 32-bit elements in Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The 32-bit results after saturation are written to Rd. The 16-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
// KMADA
res[x] = Rd.W[x] + (Rs1.W[x].H[1] * Rs2.W[x].H[1]) + (Rs1.W[x].H[0] * Rs2.W[x].
↪H[0]);
// KMAXDA
res[x] = Rd.W[x] + (Rs1.W[x].H[1] * Rs2.W[x].H[0]) + (Rs1.W[x].H[0] * Rs2.W[x].
↪H[1]);
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMAXDA (long t, unsigned long a, unsigned long b)

KMAXDA (SIMD Saturating Signed Crossed Multiply Two Halfs and Two Adds)

Type: SIMD

Syntax:

```
KMADA Rd, Rs1, Rs2
KMAXDA Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from 32-bit elements in two registers; and then adds the two 32-bit results and 32-bit elements in a third register together. The addition result may be saturated.

- KMADA: rd.W[x] + top*top + bottom*bottom (per 32-bit element)
- KMAXDA: rd.W[x] + top*bottom + bottom*top (per 32-bit element)

Description :

For the `KMADA instruction, it multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2 and then adds the result to the result of multiplying the top 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2. For the KMAXDA instruction, it multiplies the top 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2 and then adds the result to the result of multiplying the bottom 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2. The result is added to the content of 32-bit elements in Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The 32-bit results after saturation are written to Rd. The 16-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
// KMADA
res[x] = Rd.W[x] + (Rs1.W[x].H[1] * Rs2.W[x].H[1]) + (Rs1.W[x].H[0] * Rs2.W[x].
↪H[0]);
// KMAXDA
res[x] = Rd.W[x] + (Rs1.W[x].H[1] * Rs2.W[x].H[0]) + (Rs1.W[x].H[0] * Rs2.W[x].
↪H[1]);
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMADS (long t, unsigned long a, unsigned long b)

KMADS (SIMD Saturating Signed Multiply Two Halfs & Subtract & Add)

Type: SIMD

Syntax:

```
KMADS Rd, Rs1, Rs2
KMADRS Rd, Rs1, Rs2
KMAXDS Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from 32-bit elements in two registers; and then perform a subtraction operation between the two 32-bit results. Then add the subtraction result to the corresponding 32-bit elements in a third register. The addition result may be saturated.

- KMADS: rd.W[x] + (top*top - bottom*bottom) (per 32-bit element)
- KMADRS: rd.W[x] + (bottom*bottom - top*top) (per 32-bit element)
- KMAXDS: rd.W[x] + (top*bottom - bottom*top) (per 32-bit element)

Description :

For the `KMADS` instruction, it multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2. For the `KMADRS` instruction, it multiplies the top 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2 and then subtracts the result from the result of multiplying the bottom 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32- bit elements in Rs2. For the `KMAXDS` instruction, it multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2. The subtraction result is then added to the content of the corresponding 32-bit elements in Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The 32-bit results after saturation are written to Rd. The 16-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
// KMADS
res[x] = Rd.W[x] + (Rs1.W[x].H[1] * Rs2.W[x].H[1]) - (Rs1.W[x].H[0] * Rs2.W[x].
→H[0]);
// KMADRS
res[x] = Rd.W[x] + (Rs1.W[x].H[0] * Rs2.W[x].H[0]) - (Rs1.W[x].H[1] * Rs2.W[x].
→H[1]);
// KMAXDS
res[x] = Rd.W[x] + (Rs1.W[x].H[1] * Rs2.W[x].H[0]) - (Rs1.W[x].H[0] * Rs2.W[x].
→H[1]);
if (res[x] > (2^31)-1) {
```

(continues on next page)

(continued from previous page)

```
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMADRS (long t, unsigned long a, unsigned long b)

KMADRS (SIMD Saturating Signed Multiply Two Halfs & Reverse Subtract & Add)

Type: SIMD

Syntax:

```
KMADS Rd, Rs1, Rs2
KMADRS Rd, Rs1, Rs2
KMAXDS Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from 32-bit elements in two registers; and then perform a subtraction operation between the two 32-bit results. Then add the subtraction result to the corresponding 32-bit elements in a third register. The addition result may be saturated.

- KMADS: rd.W[x] + (top*top - bottom*bottom) (per 32-bit element)
- KMADRS: rd.W[x] + (bottom*bottom - top*top) (per 32-bit element)
- KMAXDS: rd.W[x] + (top*bottom - bottom*top) (per 32-bit element)

Description :

For the `KMADS` instruction, it multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2. For the `KMADRS` instruction, it multiplies the top 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2 and then subtracts the result from the result of multiplying the bottom 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32- bit elements in Rs2. For the `KMAXDS` instruction, it multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2. The subtraction result is then added to the content of the corresponding 32-bit elements in Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The 32-bit results after saturation are written to Rd. The 16-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
// KMADS
res[x] = Rd.W[x] + (Rs1.W[x].H[1] * Rs2.W[x].H[1]) - (Rs1.W[x].H[0] * Rs2.W[x].
↪H[0]);
// KMADRS
res[x] = Rd.W[x] + (Rs1.W[x].H[0] * Rs2.W[x].H[0]) - (Rs1.W[x].H[1] * Rs2.W[x].
↪H[1]);
// KMAXDS
res[x] = Rd.W[x] + (Rs1.W[x].H[1] * Rs2.W[x].H[0]) - (Rs1.W[x].H[0] * Rs2.W[x].
↪H[1]);
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMAXDS (long t, unsigned long a, unsigned long b)

KMAXDS (SIMD Saturating Signed Crossed Multiply Two Halfs & Subtract & Add)

Type: SIMD

Syntax:

```
KMADS Rd, Rs1, Rs2
KMADRS Rd, Rs1, Rs2
KMAXDS Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from 32-bit elements in two registers; and then perform a subtraction operation between the two 32-bit results. Then add the subtraction result to the corresponding 32-bit elements in a third register. The addition result may be saturated.

- KMADS: rd.W[x] + (top*top - bottom*bottom) (per 32-bit element)
- KMADRS: rd.W[x] + (bottom*bottom - top*top) (per 32-bit element)
- KMAXDS: rd.W[x] + (top*bottom - bottom*top) (per 32-bit element)

Description :

For the `KMADS` instruction, it multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2. For the KMADRS instruction, it multiplies the top 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2 and then subtracts the result from the result of multiplying the bottom 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32- bit elements in Rs2. For the KMAXDS instruction, it multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2. The subtraction result is then added to the content of the corresponding 32-bit elements in Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The 32-bit results after saturation are written to Rd. The 16-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
// KMADS
res[x] = Rd.W[x] + (Rs1.W[x].H[1] * Rs2.W[x].H[1]) - (Rs1.W[x].H[0] * Rs2.W[x].
↪H[0]);
// KMADRS
res[x] = Rd.W[x] + (Rs1.W[x].H[0] * Rs2.W[x].H[0]) - (Rs1.W[x].H[1] * Rs2.W[x].
↪H[1]);
// KMAXDS
res[x] = Rd.W[x] + (Rs1.W[x].H[1] * Rs2.W[x].H[0]) - (Rs1.W[x].H[0] * Rs2.W[x].
↪H[1]);
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_KMDA (unsigned long a, unsigned long b)`

KMDA (SIMD Signed Multiply Two Halfs and Add)

Type: SIMD

Syntax:

```
KMDA Rd, Rs1, Rs2
KMXDA Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then adds the two 32-bit results together. The addition result may be saturated.

- KMDA: top*top + bottom*bottom (per 32-bit element)
- KMXDA: top*bottom + bottom*top (per 32-bit element)

Description :

For the KMDA instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and then adds the result to the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32- bit elements of Rs2. For the KMXDA instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then adds the result to the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. The addition result is checked for saturation. If saturation happens, the result is saturated to 2^31-1. The final results are written to Rd. The 16-bit contents are treated as signed integers.

Operations:

```
if  Rs1.W[x]  !=  0x80008000)  or  (Rs2.W[x]  !=  0x80008000  {  //  KMDA  Rd.
↪W[x]  =  Rs1.W[x].H[1]  *
Rs2.W[x].H[1]) + (Rs1.W[x].H[0] * Rs2.W[x].H[0]; // KMXDA Rd.W[x] = Rs1.W[x].
↪H[1] * Rs2.W[x].H[0])
+  (Rs1.W[x].H[0]  *  Rs2.W[x].H[1];  }  else  {  Rd.W[x]  =  0x7fffffff;  OV ␣
↪=  1;  }  for  RV32:  x=0  for  RV64:
x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMXDA (unsigned long a, unsigned long b)

KMXDA (SIMD Signed Crossed Multiply Two Halfs and Add)

Type: SIMD

Syntax:

```
KMDA Rd, Rs1, Rs2
KMXDA Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then adds the two 32-bit results together. The addition result may be saturated.

- KMDA: top*top + bottom*bottom (per 32-bit element)
- KMXDA: top*bottom + bottom*top (per 32-bit element)

Description :

For the KMDA instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and then adds the result to the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32- bit elements of Rs2. For the KMXDA instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then adds the result to the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. The addition result is checked for saturation. If saturation happens, the result is saturated to 2^31-1. The final results are written to Rd. The 16-bit contents are treated as signed integers.

Operations:

```
if Rs1.W[x] != 0x80008000) or (Rs2.W[x] != 0x80008000 { // KMDA Rd.
↪W[x] = Rs1.W[x].H[1] *
Rs2.W[x].H[1]) + (Rs1.W[x].H[0] * Rs2.W[x].H[0]; // KMXDA Rd.W[x] = Rs1.W[x].
↪H[1] * Rs2.W[x].H[0])
+ (Rs1.W[x].H[0] * Rs2.W[x].H[1]; } else { Rd.W[x] = 0x7fffffff; OV ␣
↪= 1; } for RV32: x=0 for RV64:
x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMSDA (long t, unsigned long a, unsigned long b)

KMSDA (SIMD Saturating Signed Multiply Two Halfs & Add & Subtract)

Type: SIMD

Syntax:

```
KMSDA Rd, Rs1, Rs2
KMSXDA Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then subtracts the two 32-bit results from the corresponding 32-bit elements of a third register. The subtraction result may be saturated.

- KMSDA: rd.W[x] - top*top - bottom*bottom (per 32-bit element)
- KMSXDA: rd.W[x] - top*bottom - bottom*top (per 32-bit element)

Description :

For the `KMSDA` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. For the `KMSXDA` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and multiplies the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. The two 32-bit multiplication results are then subtracted from the content of the corresponding 32- bit elements of Rd. If the subtraction result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to Rd. The 16-bit contents are treated as signed integers.

Operations:

```
// KMSDA
res[x] = Rd.W[x] - (Rs1.W[x].H[1] * Rs2.W[x].H[1]) - (Rs1.W[x].H[0] * Rs2.W[x].
↪H[0]);
// KMSXDA
res[x] = Rd.W[x] - (Rs1.W[x].H[1] * Rs2.W[x].H[0]) - (Rs1.W[x].H[0] * Rs2.W[x].
↪H[1]);
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMSXDA (long t, unsigned long a, unsigned long b)

KMSXDA (SIMD Saturating Signed Crossed Multiply Two Halfs & Add & Subtract)

Type: SIMD

Syntax:

```
KMSDA Rd, Rs1, Rs2
KMSXDA Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then subtracts the two 32-bit results from the corresponding 32-bit elements of a third register. The subtraction result may be saturated.

- KMSDA: rd.W[x] - top*top - bottom*bottom (per 32-bit element)
- KMSXDA: rd.W[x] - top*bottom - bottom*top (per 32-bit element)

Description :

For the `KMSDA` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. For the `KMSXDA` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and multiplies the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. The two 32-bit multiplication results are then subtracted from the content of the corresponding 32- bit elements of Rd. If the subtraction result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to Rd. The 16-bit contents are treated as signed integers.

Operations:

```
// KMSDA
res[x] = Rd.W[x] - (Rs1.W[x].H[1] * Rs2.W[x].H[1]) - (Rs1.W[x].H[0] * Rs2.W[x].
↪H[0]);
// KMSXDA
res[x] = Rd.W[x] - (Rs1.W[x].H[1] * Rs2.W[x].H[0]) - (Rs1.W[x].H[0] * Rs2.W[x].
↪H[1]);
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_SMBB16 (unsigned long a, unsigned long b)

SMBB16 (SIMD Signed Multiply Bottom Half & Bottom Half)

Type: SIMD

Syntax:

```
SMBB16 Rd, Rs1, Rs2
SMBT16 Rd, Rs1, Rs2
SMTT16 Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 16-bit content of the 32-bit elements of a register with the signed 16- bit content of the 32-bit elements of another register and write the result to a third register.

- SMBB16: W[x].bottom*W[x].bottom
- SMBT16: W[x].bottom *W[x].top
- SMTT16: W[x].top * W[x].top

Description :

For the SMBB16 instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. For the SMBT16 instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. For the SMTT16 instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. The multiplication results are written to Rd. The 16-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
Rd.W[x] = Rs1.W[x].H[0] * Rs2.W[x].H[0]; // SMBB16
Rd.W[x] = Rs1.W[x].H[0] * Rs2.W[x].H[1]; // SMBT16
Rd.W[x] = Rs1.W[x].H[1] * Rs2.W[x].H[1]; // SMTT16
for RV32: x=0,
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_SMBT16 (unsigned long a, unsigned long b)

SMBT16 (SIMD Signed Multiply Bottom Half & Top Half)

Type: SIMD

Syntax:

```
SMBB16 Rd, Rs1, Rs2
SMBT16 Rd, Rs1, Rs2
SMTT16 Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 16-bit content of the 32-bit elements of a register with the signed 16- bit content of the 32-bit elements of another register and write the result to a third register.

- SMBB16: W[x].bottom*W[x].bottom
- SMBT16: W[x].bottom *W[x].top
- SMTT16: W[x].top * W[x].top

Description :

For the `SMBB16` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. For the `SMBT16` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. For the `SMTT16` instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. The multiplication results are written to Rd. The 16-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
Rd.W[x] = Rs1.W[x].H[0] * Rs2.W[x].H[0]; // SMBB16
Rd.W[x] = Rs1.W[x].H[0] * Rs2.W[x].H[1]; // SMBT16
Rd.W[x] = Rs1.W[x].H[1] * Rs2.W[x].H[1]; // SMTT16
for RV32: x=0,
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_SMTT16 (unsigned long a, unsigned long b)

SMTT16 (SIMD Signed Multiply Top Half & Top Half)

Type: SIMD

Syntax:

```
SMBB16 Rd, Rs1, Rs2
SMBT16 Rd, Rs1, Rs2
SMTT16 Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 16-bit content of the 32-bit elements of a register with the signed 16- bit content of the 32-bit elements of another register and write the result to a third register.

- SMBB16: W[x].bottom*W[x].bottom
- SMBT16: W[x].bottom *W[x].top
- SMTT16: W[x].top * W[x].top

Description :

For the `SMBB16` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. For the `SMBT16` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. For the `SMTT16` instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. The multiplication results are written to Rd. The 16-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
Rd.W[x] = Rs1.W[x].H[0] * Rs2.W[x].H[0]; // SMBB16
Rd.W[x] = Rs1.W[x].H[0] * Rs2.W[x].H[1]; // SMBT16
Rd.W[x] = Rs1.W[x].H[1] * Rs2.W[x].H[1]; // SMTT16
for RV32: x=0,
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_SMDS (unsigned long a, unsigned long b)

SMDS (SIMD Signed Multiply Two Halfs and Subtract)

Type: SIMD

Syntax:

```
SMDS Rd, Rs1, Rs2
SMDRS Rd, Rs1, Rs2
SMXDS Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then perform a subtraction operation between the two 32-bit results.

- SMDS: top*top - bottom*bottom (per 32-bit element)
- SMDRS: bottom*bottom - top*top (per 32-bit element)
- SMXDS: top*bottom - bottom*top (per 32-bit element)

Description :

For the `SMDS` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. For the `SMDRS` instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. For the `SMXDS` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. The subtraction result is written to the corresponding 32-bit element of Rd. The 16-bit contents of multiplication are treated as signed integers.

Operations:

```
* SMDS:
Rd.W[x] = (Rs1.W[x].H[1] * Rs2.W[x].H[1]) - (Rs1.W[x].H[0] * Rs2.W[x].H[0]);
* SMDRS:
Rd.W[x] = (Rs1.W[x].H[0] * Rs2.W[x].H[0]) - (Rs1.W[x].H[1] * Rs2.W[x].H[1]);
* SMXDS:
Rd.W[x] = (Rs1.W[x].H[1] * Rs2.W[x].H[0]) - (Rs1.W[x].H[0] * Rs2.W[x].H[1]);
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_SMDRS (unsigned long a, unsigned long b)

SMDRS (SIMD Signed Multiply Two Halfs and Reverse Subtract)

Type: SIMD

Syntax:

```
SMDS Rd, Rs1, Rs2
SMDRS Rd, Rs1, Rs2
SMXDS Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then perform a subtraction operation between the two 32-bit results.

- SMDS: top*top - bottom*bottom (per 32-bit element)
- SMDRS: bottom*bottom - top*top (per 32-bit element)

- SMXDS: top*bottom - bottom*top (per 32-bit element)

Description :

For the SMDS instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. For the SMDRS instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. For the SMXDS instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. The subtraction result is written to the corresponding 32-bit element of Rd. The 16-bit contents of multiplication are treated as signed integers.

Operations:

```
* SMDS:
Rd.W[x] = (Rs1.W[x].H[1] * Rs2.W[x].H[1]) - (Rs1.W[x].H[0] * Rs2.W[x].H[0]);
* SMDRS:
Rd.W[x] = (Rs1.W[x].H[0] * Rs2.W[x].H[0]) - (Rs1.W[x].H[1] * Rs2.W[x].H[1]);
* SMXDS:
Rd.W[x] = (Rs1.W[x].H[1] * Rs2.W[x].H[0]) - (Rs1.W[x].H[0] * Rs2.W[x].H[1]);
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_SMXDS (unsigned long a, unsigned long b)`

SMXDS (SIMD Signed Crossed Multiply Two Halfs and Subtract)

Type: SIMD

Syntax:

```
SMDS Rd, Rs1, Rs2
SMDRS Rd, Rs1, Rs2
SMXDS Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then perform a subtraction operation between the two 32-bit results.

- SMDS: top*top - bottom*bottom (per 32-bit element)
- SMDRS: bottom*bottom - top*top (per 32-bit element)
- SMXDS: top*bottom - bottom*top (per 32-bit element)

Description :

For the SMDS instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of

Rs2. For the SMDRS instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. For the SMXDS instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. The subtraction result is written to the corresponding 32-bit element of Rd. The 16-bit contents of multiplication are treated as signed integers.

Operations:

```
* SMDS:
Rd.W[x] = (Rs1.W[x].H[1] * Rs2.W[x].H[1]) - (Rs1.W[x].H[0] * Rs2.W[x].H[0]);
* SMDRS:
Rd.W[x] = (Rs1.W[x].H[0] * Rs2.W[x].H[0]) - (Rs1.W[x].H[1] * Rs2.W[x].H[1]);
* SMXDS:
Rd.W[x] = (Rs1.W[x].H[1] * Rs2.W[x].H[0]) - (Rs1.W[x].H[0] * Rs2.W[x].H[1]);
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

Partial-SIMD Miscellaneous Instructions

__STATIC_FORCEINLINE unsigned long __RV_CLRS32 (unsigned long a)

__STATIC_FORCEINLINE unsigned long __RV_CLO32 (unsigned long a)

__STATIC_FORCEINLINE unsigned long __RV_CLZ32 (unsigned long a)

__STATIC_FORCEINLINE unsigned long __RV_PBSAD (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_PBSADA (unsigned long t, unsigned long a, unsigned long b)

__RV_SCLIP32(a, b)

__RV_UCLIP32(a, b)

group **NMSIS_Core_DSP_Intrinsic_PART_SIMD_MISC**

Partial-SIMD Miscellaneous Instructions.

there are 7 Partial-SIMD Miscellaneous Instructions

Defines

__RV_SCLIP32(a, b)

SCLIP32 (SIMD 32-bit Signed Clip Value)

Type: DSP

Syntax:

```
SCLIP32 Rd, Rs1, imm5u[4:0]
```

Purpose :

Limit the 32-bit signed integer elements of a register into a signed range simultaneously.

Description :

This instruction limits the 32-bit signed integer elements stored in Rs1 into a signed integer range between 2imm5u-1 and -2imm5u, and writes the limited results to Rd. For example, if imm5u is 3, the 32-bit input values should be saturated between 7 and -8. If saturation is performed, set OV bit to 1.

Operations:

```
src = Rs1.W[x];
if (src > (2^imm5u)-1) {
  src = (2^imm5u)-1;
  OV = 1;
} else if (src < -2^imm5u) {
  src = -2^imm5u;
  OV = 1;
}
Rd.W[x] = src
for RV32: x=0,
for RV64: x=1...0
```

Parameters

- **a** – **[in]** long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in long type

__RV_UCLIP32(a, b)

UCLIP32 (SIMD 32-bit Unsigned Clip Value)

Type: SIMD

Syntax:

```
UCLIP32 Rd, Rs1, imm5u[4:0]
```

Purpose :

Limit the 32-bit signed integer elements of a register into an unsigned range simultaneously.

Description :

This instruction limits the 32-bit signed integer elements stored in Rs1 into an unsigned integer range between 2imm5u-1 and 0, and writes the limited results to Rd. For example, if imm5u is 3, the 32-bit input values should be saturated between 7 and 0. If saturation is performed, set OV bit to 1.

Operations:

```
src = Rs1.W[x];
if (src > (2^imm5u)-1) {
  src = (2^imm5u)-1;
  OV = 1;
} else if (src < 0) {
  src = 0;
  OV = 1;
}
Rd.W[x] = src
for RV32: x=0,
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

Functions

`__STATIC_FORCEINLINE unsigned long __RV_CLRS32 (unsigned long a)`

CLRS32 (SIMD 32-bit Count Leading Redundant Sign)

Type: SIMD

Syntax:

```
CLRS32 Rd, Rs1
```

Purpose :

Count the number of redundant sign bits of the 32-bit elements of a general register.

Description :

Starting from the bits next to the sign bits of the 32-bit elements of Rs1, this instruction counts the number of redundant sign bits and writes the result to the corresponding 32- bit elements of Rd.

Operations:

```
snum[x] = Rs1.W[x];
cnt[x] = 0;
for (i = 30 to 0) {
  if (snum[x](i) == snum[x](31)) {
    cnt[x] = cnt[x] + 1;
  } else {
    break;
  }
}
Rd.W[x] = cnt[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters `a` – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_CLO32 (unsigned long a)`

CLO32 (SIMD 32-bit Count Leading One)

Type: SIMD

Syntax:

```
CLO32 Rd, Rs1
```

Purpose :

Count the number of leading one bits of the 32-bit elements of a general register.

Description :

Starting from the most significant bits of the 32-bit elements of Rs1, this instruction counts the number of leading one bits and writes the results to the corresponding 32-bit elements of Rd.

Operations:

```
snum[x] = Rs1.W[x];
cnt[x] = 0;
for (i = 31 to 0) {
  if (snum[x](i) == 1) {
    cnt[x] = cnt[x] + 1;
  } else {
    break;
  }
}
Rd.W[x] = cnt[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters `a` – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_CLZ32 (unsigned long a)`

CLZ32 (SIMD 32-bit Count Leading Zero)

Type: SIMD

Syntax:

```
CLZ32 Rd, Rs1
```

Purpose :

Count the number of leading zero bits of the 32-bit elements of a general register.

Description :

Starting from the most significant bits of the 32-bit elements of Rs1, this instruction counts the number of leading zero bits and writes the results to the corresponding 32-bit elements of Rd.

Operations:

```
snum[x] = Rs1.W[x];
cnt[x] = 0;
for (i = 31 to 0) {
  if (snum[x](i) == 0) {
    cnt[x] = cnt[x] + 1;
  } else {
    break;
  }
}
Rd.W[x] = cnt[x];
for RV32: x=0
for RV64: x=1...0
```

Parameters `a` – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_PBSAD (unsigned long a, unsigned long b)`

PBSAD (Parallel Byte Sum of Absolute Difference)

Type: DSP

Syntax:

```
PBSAD Rd, Rs1, Rs2
```

Purpose :

Calculate the sum of absolute difference of unsigned 8-bit data elements.

Description :

This instruction subtracts the un-signed 8-bit elements of Rs2 from those of Rs1. Then it adds the absolute value of each difference together and writes the result to Rd.

Operations:

```
absdiff[x] = ABS(Rs1.B[x] - Rs2.B[x]);
Rd = SUM(absdiff[x]);
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- `a` – **[in]** unsigned long type of value stored in a
- `b` – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_PBSADA (unsigned long t, unsigned long a, unsigned long b)`

PBSADA (Parallel Byte Sum of Absolute Difference Accum)

Type: DSP

Syntax:

```
PBSADA Rd, Rs1, Rs2
```

Purpose :

Calculate the sum of absolute difference of four unsigned 8-bit data elements and accumulate it into a register.

Description :

This instruction subtracts the un-signed 8-bit elements of Rs2 from those of Rs1. It then adds the absolute value of each difference together along with the content of Rd and writes the accumulated result back to Rd.

Operations:

```
absdiff[x] = ABS(Rs1.B[x] - Rs2.B[x]);
Rd = Rd + SUM(absdiff[x]);
for RV32: x=3...0,
for RV64: x=7...0
```

Parameters

- **t** – **[in]** unsigned long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

8-bit Multiply with 32-bit Add Instructions

__STATIC_FORCEINLINE long __RV_SMAQA (long t, unsigned long a, unsigned long b)

__STATIC_FORCEINLINE long __RV_SMAQA_SU (long t, unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UMAQA (unsigned long t, unsigned long a, unsigned long b)

group NMSIS_Core_DSP_Intrinsic_8B_MULT_32B_ADD

8-bit Multiply with 32-bit Add Instructions

there are 3 8-bit Multiply with 32-bit Add Instructions

Functions

`__STATIC_FORCEINLINE long __RV_SMAQA (long t, unsigned long a, unsigned long b)`

SMAQA (Signed Multiply Four Bytes with 32-bit Adds)

Type: Partial-SIMD (Reduction)

Syntax:

```
SMAQA Rd, Rs1, Rs2
```

Purpose :

Do four signed 8-bit multiplications from 32-bit chunks of two registers; and then adds the four 16-bit results and the content of corresponding 32-bit chunks of a third register together.

Description :

This instruction multiplies the four signed 8-bit elements of 32-bit chunks of Rs1 with the four signed 8-bit elements of 32-bit chunks of Rs2 and then adds the four results together with the signed content of the corresponding 32-bit chunks of Rd. The final results are written back to the corresponding 32-bit chunks in Rd.

Operations:

```
res[x] = Rd.W[x] +
   (Rs1.W[x].B[3] s* Rs2.W[x].B[3]) + (Rs1.W[x].B[2] s* Rs2.W[x].B[2]) +
   (Rs1.W[x].B[1] s* Rs2.W[x].B[1]) + (Rs1.W[x].B[0] s* Rs2.W[x].B[0]);
Rd.W[x] = res[x];
for RV32: x=0,
for RV64: x=1,0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_SMAQA_SU (long t, unsigned long a, unsigned long b)`

SMAQA.SU (Signed and Unsigned Multiply Four Bytes with 32-bit Adds)

Type: Partial-SIMD (Reduction)

Syntax:

```
SMAQA.SU Rd, Rs1, Rs2
```

Purpose :

Do four `signed x unsigned` 8-bit multiplications from 32-bit chunks of two registers; and then adds the four 16-bit results and the content of corresponding 32-bit chunks of a third register together.

Description :

This instruction multiplies the four signed 8-bit elements of 32-bit chunks of Rs1 with the four unsigned 8-bit elements of 32-bit chunks of Rs2 and then adds the four results together with the signed content of the corresponding 32-bit chunks of Rd. The final results are written back to the corresponding 32-bit chunks in Rd.

Operations:

```
res[x] = Rd.W[x] +
   (Rs1.W[x].B[3] su* Rs2.W[x].B[3]) + (Rs1.W[x].B[2] su* Rs2.W[x].B[2]) +
   (Rs1.W[x].B[1] su* Rs2.W[x].B[1]) + (Rs1.W[x].B[0] su* Rs2.W[x].B[0]);
Rd.W[x] = res[x];
for RV32: x=0,
for RV64: x=1...0
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE unsigned long __RV_UMAQA (unsigned long t, unsigned long a, unsigned long b)

UMAQA (Unsigned Multiply Four Bytes with 32- bit Adds)

Type: DSP

Syntax:

```
UMAQA Rd, Rs1, Rs2
```

Purpose :

Do four unsigned 8-bit multiplications from 32-bit chunks of two registers; and then adds the four 16-bit results and the content of corresponding 32-bit chunks of a third register together.

Description :

This instruction multiplies the four unsigned 8-bit elements of 32-bit chunks of Rs1 with the four unsigned 8-bit elements of 32-bit chunks of Rs2 and then adds the four results together with the unsigned content of the corresponding 32-bit chunks of Rd. The final results are written back to the corresponding 32-bit chunks in Rd.

Operations:

```
res[x] = Rd.W[x] + (Rs1.W[x].B[3] u* Rs2.W[x].B[3]) +
         (Rs1.W[x].B[2] u* Rs2.W[x].B[2]) + (Rs1.W[x].B[1] u* Rs2.W[x].B[1]) +
         (Rs1.W[x].B[0] u* Rs2.W[x].B[0]);
Rd.W[x] = res[x];
for RV32: x=0,
for RV64: x=1...0
```

Parameters

- **t** – **[in]** unsigned long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

group `NMSIS_Core_DSP_Intrinsic_PART_SIMD_DATA_PROCESS`

Partial-SIMD Data Processing Instructions.

64-bit Profile Instructions

64-bit Addition & Subtraction Instructions

`__STATIC_FORCEINLINE unsigned long long __RV_ADD64 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_KADD64 (long long a, long long b)`

`__STATIC_FORCEINLINE long long __RV_KSUB64 (long long a, long long b)`

`__STATIC_FORCEINLINE long long __RV_RADD64 (long long a, long long b)`

`__STATIC_FORCEINLINE long long __RV_RSUB64 (long long a, long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_SUB64 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_UKADD64 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_UKSUB64 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_URADD64 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_URSUB64 (unsigned long long a, unsigned long long b)`

group `NMSIS_Core_DSP_Intrinsic_64B_ADDSUB`

64-bit Addition & Subtraction Instructions

there are 10 64-bit Addition & Subtraction Instructions.

Functions

__STATIC_FORCEINLINE unsigned long long __RV_ADD64 (unsigned long long a, unsigned long long b)

ADD64 (64-bit Addition)

Type: 64-bit Profile

Syntax:

```
ADD64 Rd, Rs1, Rs2
```

Purpose :

Add two 64-bit signed or unsigned integers.

RV32 Description :

This instruction adds the 64-bit integer of an even/odd pair of registers specified by Rs1(4,1) with the 64-bit integer of an even/odd pair of registers specified by Rs2(4,1), and then writes the 64-bit result to an even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., value d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

This instruction has the same behavior as the ADD instruction in RV64I.

Note :

This instruction can be used for either signed or unsigned addition.

Operations:

```
RV32:
 t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
 a_L = CONCAT(Rs1(4,1),1'b0); a_H = CONCAT(Rs1(4,1),1'b1);
 b_L = CONCAT(Rs2(4,1),1'b0); b_H = CONCAT(Rs2(4,1),1'b1);
 R[t_H].R[t_L] = R[a_H].R[a_L] + R[b_H].R[b_L];
RV64:
 Rd = Rs1 + Rs2;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE long long __RV_KADD64 (long long a, long long b)

KADD64 (64-bit Signed Saturating Addition)

Type: DSP (64-bit Profile)

Syntax:

```
KADD64 Rd, Rs1, Rs2
```

Purpose :

Add two 64-bit signed integers. The result is saturated to the Q63 range.

RV32 Description :

This instruction adds the 64-bit signed integer of an even/odd pair of registers specified by Rs1(4,1) with the 64-bit signed integer of an even/odd pair of registers specified by Rs2(4,1). If the 64-bit result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The saturated result is written to an even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., value d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

This instruction adds the 64-bit signed integer in Rs1 with the 64-bit signed integer in Rs2. If the result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The saturated result is written to Rd.

Operations:

```
RV32:
 t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
 a_L = CONCAT(Rs1(4,1),1'b0); a_H = CONCAT(Rs1(4,1),1'b1);
 b_L = CONCAT(Rs2(4,1),1'b0); b_H = CONCAT(Rs2(4,1),1'b1);
 result = R[a_H].R[a_L] + R[b_H].R[b_L];
 if (result > (2^63)-1) {
   result = (2^63)-1; OV = 1;
 } else if (result < -2^63) {
   result = -2^63; OV = 1;
 }
 R[t_H].R[t_L] = result;
RV64:
 result = Rs1 + Rs2;
 if (result > (2^63)-1) {
   result = (2^63)-1; OV = 1;
 } else if (result < -2^63) {
   result = -2^63; OV = 1;
 }
 Rd = result;
```

Parameters

- **a** – **[in]** long long type of value stored in a
- **b** – **[in]** long long type of value stored in b

Returns value stored in long long type

`__STATIC_FORCEINLINE long long __RV_KSUB64 (long long a, long long b)`

KSUB64 (64-bit Signed Saturating Subtraction)

Type: DSP (64-bit Profile)

Syntax:

```
KSUB64 Rd, Rs1, Rs2
```

Purpose :

Perform a 64-bit signed integer subtraction. The result is saturated to the Q63 range.

RV32 Description :

This instruction subtracts the 64-bit signed integer of an even/odd pair of registers specified by Rs2(4,1) from the 64-bit signed integer of an even/odd pair of registers specified by Rs1(4,1). If the 64-bit result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The saturated result is then written to an even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the operand and the even `2d` register of the pair contains the low 32-bit of the operand.

RV64 Description :

This instruction subtracts the 64-bit signed integer of Rs2 from the 64-bit signed integer of Rs1. If the 64-bit result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The saturated result is then written to Rd.

Operations:

```
RV32:
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
a_L = CONCAT(Rs1(4,1),1'b0); a_H = CONCAT(Rs1(4,1),1'b1);
b_L = CONCAT(Rs2(4,1),1'b0); b_H = CONCAT(Rs2(4,1),1'b1);
result = R[a_H].R[a_L] - R[b_H].R[b_L];
if (result > (2^63)-1) {
  result = (2^63)-1; OV = 1;
} else if (result < -2^63) {
  result = -2^63; OV = 1;
}
R[t_H].R[t_L] = result;
RV64:
result = Rs1 - Rs2;
if (result > (2^63)-1) {
  result = (2^63)-1; OV = 1;
} else if (result < -2^63) {
  result = -2^63; OV = 1;
}
Rd = result;
```

Parameters

- **a** – **[in]** long long type of value stored in a
- **b** – **[in]** long long type of value stored in b

Returns value stored in long long type

`__STATIC_FORCEINLINE long long __RV_RADD64 (long long a, long long b)`

RADD64 (64-bit Signed Halving Addition)

Type: DSP (64-bit Profile)

Syntax:

```
RADD64 Rd, Rs1, Rs2
```

Purpose :

Add two 64-bit signed integers. The result is halved to avoid overflow or saturation.

RV32 Description :

This instruction adds the 64-bit signed integer of an even/odd pair of registers specified by Rs1(4,1) with the 64-bit signed integer of an even/odd pair of registers specified by Rs2(4,1). The 64-bit addition result is first arithmetically right-shifted by 1 bit and then written to an even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., value d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

This instruction adds the 64-bit signed integer in Rs1 with the 64-bit signed integer in Rs2. The 64-bit addition result is first arithmetically right-shifted by 1 bit and then written to Rd.

Operations:

```
RV32:
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
a_L = CONCAT(Rs1(4,1),1'b0); a_H = CONCAT(Rs1(4,1),1'b1);
b_L = CONCAT(Rs2(4,1),1'b0); b_H = CONCAT(Rs2(4,1),1'b1);
R[t_H].R[t_L] = (R[a_H].R[a_L] + R[b_H].R[b_L]) s>> 1;
RV64:
Rd = (Rs1 + Rs2) s>> 1;
```

Parameters

- **a** – **[in]** long long type of value stored in a
- **b** – **[in]** long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_RSUB64 (long long a, long long b)

RSUB64 (64-bit Signed Halving Subtraction)

Type: DSP (64-bit Profile)

Syntax:

```
RSUB64 Rd, Rs1, Rs2
```

Purpose :

Perform a 64-bit signed integer subtraction. The result is halved to avoid overflow or saturation.

RV32 Description :

This instruction subtracts the 64-bit signed integer of an even/odd pair of registers specified by Rb(4,1) from the 64-bit signed integer of an even/odd pair of registers specified by Ra(4,1). The subtraction result is first arithmetically right-shifted by 1 bit and then written to an even/odd pair of registers specified by Rt(4,1). Rx(4,1), i.e., value d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

This instruction subtracts the 64-bit signed integer in Rs2 from the 64-bit signed integer in Rs1. The 64-bit subtraction result is first arithmetically right-shifted by 1 bit and then written to Rd.

Operations:

```
RV32:
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
a_L = CONCAT(Rs1(4,1),1'b0); a_H = CONCAT(Rs1(4,1),1'b1);
b_L = CONCAT(Rs2(4,1),1'b0); b_H = CONCAT(Rs2(4,1),1'b1);
R[t_H].R[t_L] = (R[a_H].R[a_L] - R[b_H].R[b_L]) s>> 1;
RV64:
Rd = (Rs1 - Rs2) s>> 1;
```

Parameters

- **a** – **[in]** long long type of value stored in a
- **b** – **[in]** long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE unsigned long long __RV_SUB64 (unsigned long long a, unsigned long long b)

SUB64 (64-bit Subtraction)

Type: DSP (64-bit Profile)

Syntax:

```
SUB64 Rd, Rs1, Rs2
```

Purpose :

Perform a 64-bit signed or unsigned integer subtraction.

RV32 Description :

This instruction subtracts the 64-bit integer of an even/odd pair of registers specified by Rs2(4,1) from the 64-bit integer of an even/odd pair of registers specified by Rs1(4,1), and then writes the 64-bit result to an even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the operand and the even `2d` register of the pair contains the low 32-bit of the operand.

RV64 Description :

This instruction subtracts the 64-bit integer of Rs2 from the 64-bit integer of Rs1, and then writes the 64-bit result to Rd.

Note :

This instruction can be used for either signed or unsigned subtraction.

Operations:

```
* RV32:
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
a_L = CONCAT(Rs1(4,1),1'b0); a_H = CONCAT(Rs1(4,1),1'b1);
b_L = CONCAT(Rs2(4,1),1'b0); b_H = CONCAT(Rs2(4,1),1'b1);
R[t_H].R[t_L] = R[a_H].R[a_L] - R[b_H].R[b_L];
```

(continues on next page)

(continued from previous page)

```
* RV64:
Rd = Rs1 - Rs2;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_UKADD64 (unsigned long long a, unsigned long long b)

UKADD64 (64-bit Unsigned Saturating Addition)

Type: DSP (64-bit Profile)

Syntax:

```
UKADD64 Rd, Rs1, Rs2
```

Purpose :

Add two 64-bit unsigned integers. The result is saturated to the U64 range.

RV32 Description :

This instruction adds the 64-bit unsigned integer of an even/odd pair of registers specified by Rs1(4,1) with the 64-bit unsigned integer of an even/odd pair of registers specified by Rs2(4,1). If the 64-bit result is beyond the U64 number range (0 <= U64 <= 2^64-1), it is saturated to the range and the OV bit is set to 1. The saturated result is written to an even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

This instruction adds the 64-bit unsigned integer in Rs1 with the 64-bit unsigned integer in Rs2. If the 64-bit result is beyond the U64 number range (0 <= U64 <= 2^64-1), it is saturated to the range and the OV bit is set to 1. The saturated result is written to Rd.

Operations:

```
* RV32:
t_L = CONCAT(Rt(4,1),1'b0); t_H = CONCAT(Rt(4,1),1'b1);
a_L = CONCAT(Ra(4,1),1'b0); a_H = CONCAT(Ra(4,1),1'b1);
b_L = CONCAT(Rb(4,1),1'b0); b_H = CONCAT(Rb(4,1),1'b1);
result = R[a_H].R[a_L] + R[b_H].R[b_L];
if (result > (2^64)-1) {
  result = (2^64)-1; OV = 1;
}
R[t_H].R[t_L] = result;
* RV64:
result = Rs1 + Rs2;
if (result > (2^64)-1) {
  result = (2^64)-1; OV = 1;
```

(continues on next page)

(continued from previous page)

```
}
Rd = result;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_UKSUB64 (unsigned long long a, unsigned long long b)

UKSUB64 (64-bit Unsigned Saturating Subtraction)

Type: DSP (64-bit Profile)

Syntax:

```
UKSUB64 Rd, Rs1, Rs2
```

Purpose :

Perform a 64-bit signed integer subtraction. The result is saturated to the U64 range.

RV32 Description :

This instruction subtracts the 64-bit unsigned integer of an even/odd pair of registers specified by Rs2(4,1) from the 64-bit unsigned integer of an even/odd pair of registers specified by Rs1(4,1). If the 64-bit result is beyond the U64 number range (0 <= U64 <= 2^64-1), it is saturated to the range and the OV bit is set to 1. The saturated result is then written to an even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the operand and the even `2d` register of the pair contains the low 32-bit of the operand.

RV64 Description :

This instruction subtracts the 64-bit unsigned integer of Rs2 from the 64-bit unsigned integer of an even/odd pair of Rs1. If the 64-bit result is beyond the U64 number range (0 <= U64 <= 2^64-1), it is saturated to the range and the OV bit is set to 1. The saturated result is then written to Rd.

Operations:

```
* RV32:
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
a_L = CONCAT(Rs1(4,1),1'b0); a_H = CONCAT(Rs1(4,1),1'b1);
b_L = CONCAT(Rs2(4,1),1'b0); b_H = CONCAT(Rs2(4,1),1'b1);
result = R[a_H].R[a_L] - R[b_H].R[b_L];
if (result < 0) {
  result = 0; OV = 1;
}
R[t_H].R[t_L] = result;
* RV64
result = Rs1 - Rs2;
if (result < 0) {
  result = 0; OV = 1;
```

(continues on next page)

(continued from previous page)

```
}
Rd = result;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_URADD64 (unsigned long long a, unsigned long long b)

URADD64 (64-bit Unsigned Halving Addition)

Type: DSP (64-bit Profile)

Syntax:

```
URADD64 Rd, Rs1, Rs2
```

Purpose :

Add two 64-bit unsigned integers. The result is halved to avoid overflow or saturation.

RV32 Description :

This instruction adds the 64-bit unsigned integer of an even/odd pair of registers specified by Rs1(4,1) with the 64-bit unsigned integer of an even/odd pair of registers specified by Rs2(4,1). The 64-bit addition result is first logically right-shifted by 1 bit and then written to an even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

This instruction adds the 64-bit unsigned integer in Rs1 with the 64-bit unsigned integer Rs2. The 64-bit addition result is first logically right-shifted by 1 bit and then written to Rd.

Operations:

```
* RV32:
t_L = CONCAT(Rt(4,1),1'b0); t_H = CONCAT(Rt(4,1),1'b1);
a_L = CONCAT(Ra(4,1),1'b0); a_H = CONCAT(Ra(4,1),1'b1);
b_L = CONCAT(Rb(4,1),1'b0); b_H = CONCAT(Rb(4,1),1'b1);
R[t_H].R[t_L] = (R[a_H].R[a_L] + R[b_H].R[b_L]) u>> 1;
* RV64:
Rd = (Rs1 + Rs2) u>> 1;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_URSUB64 (unsigned long long a, unsigned long long b)

URSUB64 (64-bit Unsigned Halving Subtraction)

Type: DSP (64-bit Profile)

Syntax:

```
URSUB64 Rd, Rs1, Rs2
```

Purpose :

Perform a 64-bit unsigned integer subtraction. The result is halved to avoid overflow or saturation.

RV32 Description :

This instruction subtracts the 64-bit unsigned integer of an even/odd pair of registers specified by Rs2(4,1) from the 64-bit unsigned integer of an even/odd pair of registers specified by Rs1(4,1). The subtraction result is first logically right-shifted by 1 bit and then written to an even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

This instruction subtracts the 64-bit unsigned integer in Rs2 from the 64-bit unsigned integer in Rs1. The subtraction result is first logically right-shifted by 1 bit and then written to Rd.

Operations:

```
* RV32:
t_L = CONCAT(Rt(4,1),1'b0); t_H = CONCAT(Rt(4,1),1'b1);
a_L = CONCAT(Ra(4,1),1'b0); a_H = CONCAT(Ra(4,1),1'b1);
b_L = CONCAT(Rb(4,1),1'b0); b_H = CONCAT(Rb(4,1),1'b1);
R[t_H].R[t_L] = (R[a_H].R[a_L] - R[b_H].R[b_L]) u>> 1;
* RV64:
Rd = (Rs1 - Rs2) u>> 1;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

32-bit Multiply with 64-bit Add/Subtract Instructions

__STATIC_FORCEINLINE long long __RV_KMAR64 (long long t, long a, long b)

__STATIC_FORCEINLINE long long __RV_KMSR64 (long long t, long a, long b)

__STATIC_FORCEINLINE long long __RV_SMAR64 (long long t, long a, long b)

`__STATIC_FORCEINLINE long long __RV_SMSR64 (long long t, long a, long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_UKMAR64 (unsigned long long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_UKMSR64 (unsigned long long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_UMAR64 (unsigned long long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_UMSR64 (unsigned long long t, unsigned long a, unsigned long b)`

group `NMSIS_Core_DSP_Intrinsic_32B_MULT_64B_ADDSUB`

32-bit Multiply with 64-bit Add/Subtract Instructions

there are 32-bit Multiply 64-bit Add/Subtract Instructions

Functions

`__STATIC_FORCEINLINE long long __RV_KMAR64 (long long t, long a, long b)`

KMAR64 (Signed Multiply and Saturating Add to 64-Bit Data)

Type: DSP (64-bit Profile)

Syntax:

```
KMAR64 Rd, Rs1, Rs2
```

Purpose :

Multiply the 32-bit signed elements in two registers and add the 64-bit multiplication results to the 64-bit signed data of a pair of registers (RV32) or a register (RV64). The result is saturated to the Q63 range and written back to the pair of registers (RV32) or the register (RV64).

RV32 Description :

This instruction multiplies the 32-bit signed data of Rs1 with that of Rs2. It adds the 64-bit multiplication result to the 64-bit signed data of an even/odd pair of registers specified by Rd(4,1) with unlimited precision. If the 64-bit addition result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The saturated result is written back to the even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., value d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

This instruction multiplies the 32-bit signed elements of Rs1 with that of Rs2. It adds the 64-bit multiplication results to the 64-bit signed data of Rd with unlimited precision. If the 64-bit addition result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The saturated result is written back to Rd.

Operations:

```
RV32:
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
result = R[t_H].R[t_L] + (Rs1 * Rs2);
if (result > (2^63)-1) {
  result = (2^63)-1; OV = 1;
} else if (result < -2^63) {
  result = -2^63; OV = 1;
}
R[t_H].R[t_L] = result;
RV64:
// `result` has unlimited precision
result = Rd + (Rs1.W[0] * Rs2.W[0]) + (Rs1.W[1] * Rs2.W[1]);
if (result > (2^63)-1) {
  result = (2^63)-1; OV = 1;
} else if (result < -2^63) {
  result = -2^63; OV = 1;
}
Rd = result;
```

Parameters

- `t` – **[in]** long long type of value stored in t
- `a` – **[in]** long type of value stored in a
- `b` – **[in]** long type of value stored in b

Returns value stored in long long type

`__STATIC_FORCEINLINE long long __RV_KMSR64 (long long t, long a, long b)`

KMSR64 (Signed Multiply and Saturating Subtract from 64-Bit Data)

Type: DSP (64-bit Profile)

Syntax:

```
KMSR64 Rd, Rs1, Rs2
```

Purpose :

Multiply the 32-bit signed elements in two registers and subtract the 64-bit multiplication results from the 64-bit signed data of a pair of registers (RV32) or a register (RV64). The result is saturated to the Q63 range and written back to the pair of registers (RV32) or the register (RV64).

RV32 Description :

This instruction multiplies the 32-bit signed data of Rs1 with that of Rs2. It subtracts the 64-bit multiplication result from the 64-bit signed data of an even/odd pair of registers specified by Rd(4,1) with unlimited precision. If the 64-bit subtraction result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The saturated result is written back to the even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

This instruction multiplies the 32-bit signed elements of Rs1 with that of Rs2. It subtracts the 64-bit multiplication results from the 64-bit signed data in Rd with unlimited precision. If the 64-bit subtraction result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The saturated result is written back to Rd.

Operations:

```
RV32:
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
result = R[t_H].R[t_L] - (Rs1 * Rs2);
if (result > (2^63)-1) {
  result = (2^63)-1; OV = 1;
} else if (result < -2^63) {
  result = -2^63; OV = 1;
}
R[t_H].R[t_L] = result;
RV64:
// `result` has unlimited precision
result = Rd - (Rs1.W[0] * Rs2.W[0]) - (Rs1.W[1] * Rs2.W[1]);
if (result > (2^63)-1) {
  result = (2^63)-1; OV = 1;
} else if (result < -2^63) {
  result = -2^63; OV = 1;
}
Rd = result;
```

Parameters

- `t` – **[in]** long long type of value stored in t
- `a` – **[in]** long type of value stored in a
- `b` – **[in]** long type of value stored in b

Returns value stored in long long type

`__STATIC_FORCEINLINE long long __RV_SMAR64 (long long t, long a, long b)`

SMAR64 (Signed Multiply and Add to 64-Bit Data)

Type: DSP (64-bit Profile)

Syntax:

```
SMAR64 Rd, Rs1, Rs2
```

Purpose :

Multiply the 32-bit signed elements in two registers and add the 64-bit multiplication result to the 64-bit signed data of a pair of registers (RV32) or a register (RV64). The result is written back to the pair of registers (RV32) or a register (RV64).

RV32 Description :

This instruction multiplies the 32-bit signed data of Rs1 with that of Rs2. It adds the 64-bit multiplication result to the 64-bit signed data of an even/odd pair of registers specified by Rd(4,1). The addition result is written back to the even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

This instruction multiplies the 32-bit signed elements of Rs1 with that of Rs2. It adds the 64-bit multiplication results to the 64-bit signed data of Rd. The addition result is written back to Rd.

Operations:

```
* RV32:
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
R[t_H].R[t_L] = R[t_H].R[t_L] + (Rs1 * Rs2);
* RV64:
Rd = Rd + (Rs1.W[0] * Rs2.W[0]) + (Rs1.W[1] * Rs2.W[1]);
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** long type of value stored in a
- **b** – **[in]** long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_SMSR64 (long long t, long a, long b)

SMSR64 (Signed Multiply and Subtract from 64- Bit Data)

Type: DSP (64-bit Profile)

Syntax:

```
SMSR64 Rd, Rs1, Rs2
```

Purpose :

Multiply the 32-bit signed elements in two registers and subtract the 64-bit multiplication results from the 64-bit signed data of a pair of registers (RV32) or a register (RV64). The result is written back to the pair of registers (RV32) or a register (RV64).

RV32 Description :

This instruction multiplies the 32-bit signed data of Rs1 with that of Rs2. It subtracts the 64-bit multiplication result from the 64-bit signed data of an even/odd pair of registers specified by Rd(4,1). The subtraction result is written back to the even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

This instruction multiplies the 32-bit signed elements of Rs1 with that of Rs2. It subtracts the 64-bit multiplication results from the 64-bit signed data of Rd. The subtraction result is written back to Rd.

Operations:

```
* RV32:
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
R[t_H].R[t_L] = R[t_H].R[t_L] - (Rs1 * Rs2);
* RV64:
Rd = Rd - (Rs1.W[0] * Rs2.W[0]) - (Rs1.W[1] * Rs2.W[1]);
```

Parameters

- t – **[in]** long long type of value stored in t
- a – **[in]** long type of value stored in a
- b – **[in]** long type of value stored in b

Returns value stored in long long type

`__STATIC_FORCEINLINE unsigned long long __RV_UKMAR64 (unsigned long long t, unsigned long a, unsigned long b)`

UKMAR64 (Unsigned Multiply and Saturating Add to 64-Bit Data)

Type: DSP (64-bit Profile)

Syntax:

```
UKMAR64 Rd, Rs1, Rs2
```

Purpose :

Multiply the 32-bit unsigned elements in two registers and add the 64-bit multiplication results to the 64-bit unsigned data of a pair of registers (RV32) or a register (RV64). The result is saturated to the U64 range and written back to the pair of registers (RV32) or the register (RV64).

RV32 Description :

This instruction multiplies the 32-bit unsigned data of Rs1 with that of Rs2. It adds the 64-bit multiplication result to the 64-bit unsigned data of an even/odd pair of registers specified by Rd(4,1) with unlimited precision. If the 64-bit addition result is beyond the U64 number range (0 <= U64 <= 2^64-1), it is saturated to the range and the OV bit is set to 1. The saturated result is written back to the even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

This instruction multiplies the 32-bit unsigned elements of Rs1 with that of Rs2. It adds the 64-bit multiplication results to the 64-bit unsigned data in Rd with unlimited precision. If the 64-bit addition result is beyond the U64 number range (0 <= U64 <= 2^64-1), it is saturated to the range and the OV bit is set to 1. The saturated result is written back to Rd.

Operations:

```
* RV32:
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
result = R[t_H].R[t_L] + (Rs1 * Rs2);
if (result > (2^64)-1) {
  result = (2^64)-1; OV = 1;
}
R[t_H].R[t_L] = result;
* RV64:
// `result` has unlimited precision
result = Rd + (Rs1.W[0] u* Rs2.W[0]) + (Rs1.W[1] u* Rs2.W[1]);
if (result > (2^64)-1) {
  result = (2^64)-1; OV = 1;
}
Rd = result;
```

Parameters

- `t` – **[in]** unsigned long long type of value stored in t
- `a` – **[in]** unsigned long type of value stored in a
- `b` – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_UKMSR64 (unsigned long long t, unsigned long a, unsigned long b)

UKMSR64 (Unsigned Multiply and Saturating Subtract from 64-Bit Data)

Type: DSP (64-bit Profile)

Syntax:

```
UKMSR64 Rd, Rs1, Rs2
```

Purpose :

Multiply the 32-bit unsigned elements in two registers and subtract the 64-bit multiplication results from the 64-bit unsigned data of a pair of registers (RV32) or a register (RV64). The result is saturated to the U64 range and written back to the pair of registers (RV32) or a register (RV64).

RV32 Description :

This instruction multiplies the 32-bit unsigned data of Rs1 with that of Rs2. It subtracts the 64-bit multiplication result from the 64-bit unsigned data of an even/odd pair of registers specified by Rd(4,1) with unlimited precision. If the 64-bit subtraction result is beyond the U64 number range (0 <= U64 <= 2^64-1), it is saturated to the range and the OV bit is set to 1. The saturated result is written back to the even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

This instruction multiplies the 32-bit unsigned elements of Rs1 with that of Rs2. It subtracts the 64-bit multiplication results from the 64-bit unsigned data of Rd with unlimited precision. If the 64-bit subtraction result is beyond the U64 number range (0 <= U64 <= 2^64-1), it is saturated to the range and the OV bit is set to 1. The saturated result is written back to Rd.

Operations:

```
* RV32:
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
result = R[t_H].R[t_L] - (Rs1 u* Rs2);
if (result < 0) {
  result = 0; OV = 1;
}
R[t_H].R[t_L] = result;
* RV64:
// `result` has unlimited precision
result = Rd - (Rs1.W[0] u* Rs2.W[0]) - (Rs1.W[1] u* Rs2.W[1]);
if (result < 0) {
  result = 0; OV = 1;
}
Rd = result;
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_UMAR64 (unsigned long long t, unsigned long a, unsigned long b)

UMAR64 (Unsigned Multiply and Add to 64-Bit Data)

Type: DSP (64-bit Profile)

Syntax:

```
UMAR64 Rd, Rs1, Rs2
```

Purpose :

Multiply the 32-bit unsigned elements in two registers and add the 64-bit multiplication results to the 64-bit unsigned data of a pair of registers (RV32) or a register (RV64). The result is written back to the pair of registers (RV32) or a register (RV64).

RV32 Description :

This instruction multiplies the 32-bit unsigned data of Rs1 with that of Rs2. It adds the 64-bit multiplication result to the 64-bit unsigned data of an even/odd pair of registers specified by Rd(4,1). The addition result is written back to the even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

This instruction multiplies the 32-bit unsigned elements of Rs1 with that of Rs2. It adds the 64-bit multiplication results to the 64-bit unsigned data of Rd. The addition result is written back to Rd.

Operations:

```
* RV32:
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
R[t_H].R[t_L] = R[t_H].R[t_L] + (Rs1 * Rs2);
* RV64:
Rd = Rd + (Rs1.W[0] u* Rs2.W[0]) + (Rs1.W[1] u* Rs2.W[1]);
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_UMSR64 (unsigned long long t, unsigned long a, unsigned long b)

UMSR64 (Unsigned Multiply and Subtract from 64-Bit Data)

Type: DSP (64-bit Profile)

Syntax:

```
UMSR64 Rd, Rs1, Rs2
```

Purpose :

Multiply the 32-bit unsigned elements in two registers and subtract the 64-bit multiplication results from the 64-bit unsigned data of a pair of registers (RV32) or a register (RV64). The result is written back to the pair of registers (RV32) or a register (RV64).

RV32 Description :

This instruction multiplies the 32-bit unsigned data of Rs1 with that of Rs2. It subtracts the 64-bit multiplication result from the 64-bit unsigned data of an even/odd pair of registers specified by Rd(4,1). The subtraction result is written back to the even/odd pair of registers specified by Rd(4,1). Rx(4,1), i.e., d, determines the even/odd pair group of two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

This instruction multiplies the 32-bit unsigned elements of Rs1 with that of Rs2. It subtracts the 64-bit multiplication results from the 64-bit unsigned data of Rd. The subtraction result is written back to Rd.

Operations:

```
* RV32:
t_L = CONCAT(Rd(4,1),1'b0); t_H = CONCAT(Rd(4,1),1'b1);
R[t_H].R[t_L] = R[t_H].R[t_L] - (Rs1 * Rs2);
* RV64:
Rd = Rd - (Rs1.W[0] u* Rs2.W[0]) - (Rs1.W[1] u* Rs2.W[1]);
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long long type

Signed 16-bit Multiply 64-bit Add/Subtract Instructions

__STATIC_FORCEINLINE long long __RV_SMAL (long long a, unsigned long b)

__STATIC_FORCEINLINE long long __RV_SMALBB (long long t, unsigned long a, unsigned long b)

__STATIC_FORCEINLINE long long __RV_SMALBT (long long t, unsigned long a, unsigned long b)

__STATIC_FORCEINLINE long long __RV_SMALTT (long long t, unsigned long a, unsigned long b)

`__STATIC_FORCEINLINE long long __RV_SMALDA (long long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long long __RV_SMALXDA (long long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long long __RV_SMALDS (long long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long long __RV_SMALDRS (long long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long long __RV_SMALXDS (long long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long long __RV_SMSLDA (long long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long long __RV_SMSLXDA (long long t, unsigned long a, unsigned long b)`

group `NMSIS_Core_DSP_Intrinsic_SIGNED_16B_MULT_64B_ADDSUB`

Signed 16-bit Multiply 64-bit Add/Subtract Instructions.

Signed 16-bit Multiply with 64-bit Add/Subtract Instructions.

there is Signed 16-bit Multiply 64-bit Add/Subtract Instructions

there are 10 Signed 16-bit Multiply with 64-bit Add/Subtract Instructions

Functions

`__STATIC_FORCEINLINE long long __RV_SMAL (long long a, unsigned long b)`

SMAL (Signed Multiply Halfs & Add 64-bit)

Type: Partial-SIMD

Syntax:

```
SMAL Rd, Rs1, Rs2
```

Purpose :

Multiply the signed bottom 16-bit content of the 32-bit elements of a register with the top 16-bit content of the same 32-bit elements of the same register, and add the results with a 64-bit value of an even/odd pair of registers (RV32) or a register (RV64). The addition result is written back to another even/odd pair of registers (RV32) or a register (RV64).

RV32 Description :

This instruction multiplies the bottom 16-bit content of the lower 32-bit of Rs2 with the top 16-bit content of the lower 32-bit of Rs2 and adds the result with the 64-bit value of an even/odd pair of registers specified by Rs1(4,1). The 64-bit addition result is written back to an even/odd pair of registers specified by Rd(4,1).

The 16-bit values of Rs2, and the 64-bit value of the Rs1(4,1) register- pair are treated as signed integers. Rx(4,1), i.e., d, determines the even/odd pair group of the two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the operand and the even `2d` register of the pair contains the low 32-bit of the operand.

RV64 Description :

This instruction multiplies the bottom 16-bit content of the 32-bit elements of Rs2 with the top 16-bit content of the same 32-bit elements of Rs2 and adds the results with the 64-bit value of Rs1. The 64- bit addition result is written back to Rd. The 16-bit values of Rs2, and the 64-bit value of Rs1 are treated as signed integers.

Operations:

```
RV32:
Mres[31:0] = Rs2.H[1] * Rs2.H[0];
Idx0 = CONCAT(Rs1(4,1),1'b0); Idx1 = CONCAT(Rs1(4,1),1'b1); +
Idx2 = CONCAT(Rd(4,1),1'b0); Idx3 = CONCAT(Rd(4,1),1'b1);
R[Idx3].R[Idx2] = R[Idx1].R[Idx0] + SE64(Mres[31:0]);
RV64:
Mres[0][31:0] = Rs2.W[0].H[1] * Rs2.W[0].H[0];
Mres[1][31:0] = Rs2.W[1].H[1] * Rs2.W[1].H[0];
Rd = Rs1 + SE64(Mres[1][31:0]) + SE64(Mres[0][31:0]);
```

Parameters

- **a** – **[in]** long long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long long type

`__STATIC_FORCEINLINE long long __RV_SMALBB (long long t, unsigned long a, unsigned long b)`

SMALBB (Signed Multiply Bottom Halfs & Add 64-bit)

Type: DSP (64-bit Profile)

Syntax:

```
SMALBB Rd, Rs1, Rs2
SMALBT Rd, Rs1, Rs2
SMALTT Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 16-bit content of the 32-bit elements of a register with the 16-bit content of the corresponding 32-bit elements of another register and add the results with a 64-bit value of an even/odd pair of registers (RV32) or a register (RV64). The addition result is written back to the register-pair (RV32) or the register (RV64).

- SMALBB: rt pair + bottom*bottom (all 32-bit elements)
- SMALBT rt pair + bottom*top (all 32-bit elements)
- SMALTT rt pair + top*top (all 32-bit elements)

RV32 Description :

For the `SMALBB` instruction, it multiplies the bottom 16-bit content of Rs1 with the bottom 16-bit content of Rs2. For the `SMALBT` instruction, it multiplies the bottom 16-bit content of Rs1 with the top 16-bit content of Rs2. For the SMALTT instruction, it multiplies the top 16-bit content of Rs1 with the top 16-bit content of Rs2. The multiplication result is added with the 64-bit value of an even/odd pair of registers specified by Rd(4,1). The 64-bit addition result is written back to the register-pair. The 16-bit values of Rs1 and Rs2, and the 64-bit value of the register-pair are treated as signed integers. Rd(4,1), i.e., d, determines the even/odd pair group of the two registers. Specifically, the register pair includes register 2d and 2d+1. The odd 2d+1 register of the pair contains the high 32-bit of the operand and the even 2d register of the pair contains the low 32-bit of the operand.

RV64 Description :

For the SMALBB instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. For the SMALBT instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. For the SMALTT instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. The multiplication results are added with the 64-bit value of Rd. The 64-bit addition result is written back to Rd. The 16-bit values of Rs1 and Rs2, and the 64-bit value of Rd are treated as signed integers.

Operations:

```
RV32:
Mres[31:0] = Rs1.H[0] * Rs2.H[0]; // SMALBB
Mres[31:0] = Rs1.H[0] * Rs2.H[1]; // SMALBT
Mres[31:0] = Rs1.H[1] * Rs2.H[1]; // SMALTT
Idx0 = CONCAT(Rd(4,1),1'b0); Idx1 = CONCAT(Rd(4,1),1'b1);
R[Idx1].R[Idx0] = R[Idx1].R[Idx0] + SE64(Mres[31:0]);
RV64:
// SMALBB
Mres[0][31:0] = Rs1.W[0].H[0] * Rs2.W[0].H[0];
Mres[1][31:0] = Rs1.W[1].H[0] * Rs2.W[1].H[0];
// SMALBT
Mres[0][31:0] = Rs1.W[0].H[0] * Rs2.W[0].H[1];
Mres[1][31:0] = Rs1.W[1].H[0] * Rs2.W[1].H[1];
// SMALTT
Mres[0][31:0] = Rs1.W[0].H[1] * Rs2.W[0].H[1];
Mres[1][31:0] = Rs1.W[1].H[1] * Rs2.W[1].H[1];
Rd = Rd + SE64(Mres[0][31:0]) + SE64(Mres[1][31:0]);
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_SMALBT (long long t, unsigned long a, unsigned long b)

SMALBT (Signed Multiply Bottom Half & Top Half & Add 64-bit)

Type: DSP (64-bit Profile)

Syntax:

```
SMALBB Rd, Rs1, Rs2
SMALBT Rd, Rs1, Rs2
SMALTT Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 16-bit content of the 32-bit elements of a register with the 16-bit content of the corresponding 32-bit elements of another register and add the results with a 64-bit value of an even/odd pair of registers (RV32) or a register (RV64). The addition result is written back to the register-pair (RV32) or the register (RV64).

- SMALBB: rt pair + bottom*bottom (all 32-bit elements)
- SMALBT rt pair + bottom*top (all 32-bit elements)
- SMALTT rt pair + top*top (all 32-bit elements)

RV32 Description :

For the `SMALBB` instruction, it multiplies the bottom 16-bit content of Rs1 with the bottom 16-bit content of Rs2. For the `SMALBT` instruction, it multiplies the bottom 16-bit content of Rs1 with the top 16-bit content of Rs2. For the `SMALTT` instruction, it multiplies the top 16-bit content of Rs1 with the top 16-bit content of Rs2. The multiplication result is added with the 64-bit value of an even/odd pair of registers specified by Rd(4,1). The 64-bit addition result is written back to the register-pair. The 16-bit values of Rs1 and Rs2, and the 64-bit value of the register-pair are treated as signed integers. Rd(4,1), i.e., d, determines the even/odd pair group of the two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the operand and the even `2d` register of the pair contains the low 32-bit of the operand.

RV64 Description :

For the `SMALBB` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. For the `SMALBT` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. For the `SMALTT` instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. The multiplication results are added with the 64-bit value of Rd. The 64-bit addition result is written back to Rd. The 16-bit values of Rs1 and Rs2, and the 64-bit value of Rd are treated as signed integers.

Operations:

```
RV32:
Mres[31:0] = Rs1.H[0] * Rs2.H[0]; // SMALBB
Mres[31:0] = Rs1.H[0] * Rs2.H[1]; // SMALBT
Mres[31:0] = Rs1.H[1] * Rs2.H[1]; // SMALTT
Idx0 = CONCAT(Rd(4,1),1'b0); Idx1 = CONCAT(Rd(4,1),1'b1);
R[Idx1].R[Idx0] = R[Idx1].R[Idx0] + SE64(Mres[31:0]);
RV64:
// SMALBB
Mres[0][31:0] = Rs1.W[0].H[0] * Rs2.W[0].H[0];
Mres[1][31:0] = Rs1.W[1].H[0] * Rs2.W[1].H[0];
// SMALBT
Mres[0][31:0] = Rs1.W[0].H[0] * Rs2.W[0].H[1];
Mres[1][31:0] = Rs1.W[1].H[0] * Rs2.W[1].H[1];
// SMALTT
Mres[0][31:0] = Rs1.W[0].H[1] * Rs2.W[0].H[1];
Mres[1][31:0] = Rs1.W[1].H[1] * Rs2.W[1].H[1];
Rd = Rd + SE64(Mres[0][31:0]) + SE64(Mres[1][31:0]);
```

Parameters

- `t` – **[in]** long long type of value stored in t
- `a` – **[in]** unsigned long type of value stored in a
- `b` – **[in]** unsigned long type of value stored in b

Returns value stored in long long type

`__STATIC_FORCEINLINE long long __RV_SMALTT (long long t, unsigned long a, unsigned long b)`

SMALTT (Signed Multiply Top Halfs & Add 64-bit)

Type: DSP (64-bit Profile)

Syntax:

```
SMALBB Rd, Rs1, Rs2
SMALBT Rd, Rs1, Rs2
SMALTT Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 16-bit content of the 32-bit elements of a register with the 16-bit content of the corresponding 32-bit elements of another register and add the results with a 64-bit value of an even/odd pair of registers (RV32) or a register (RV64). The addition result is written back to the register-pair (RV32) or the register (RV64).

- SMALBB: rt pair + bottom*bottom (all 32-bit elements)
- SMALBT rt pair + bottom*top (all 32-bit elements)
- SMALTT rt pair + top*top (all 32-bit elements)

RV32 Description :

For the `SMALBB` instruction, it multiplies the bottom 16-bit content of Rs1 with the bottom 16-bit content of Rs2. For the `SMALBT` instruction, it multiplies the bottom 16-bit content of Rs1 with the top 16-bit content of Rs2. For the `SMALTT` instruction, it multiplies the top 16-bit content of Rs1 with the top 16-bit content of Rs2. The multiplication result is added with the 64-bit value of an even/odd pair of registers specified by Rd(4,1). The 64-bit addition result is written back to the register-pair. The 16-bit values of Rs1 and Rs2, and the 64-bit value of the register-pair are treated as signed integers. Rd(4,1), i.e., d, determines the even/odd pair group of the two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the operand and the even `2d` register of the pair contains the low 32-bit of the operand.

RV64 Description :

For the `SMALBB` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. For the `SMALBT` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. For the `SMALTT` instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. The multiplication results are added with the 64-bit value of Rd. The 64-bit addition result is written back to Rd. The 16-bit values of Rs1 and Rs2, and the 64-bit value of Rd are treated as signed integers.

Operations:

```
RV32:
Mres[31:0] = Rs1.H[0] * Rs2.H[0]; // SMALBB
Mres[31:0] = Rs1.H[0] * Rs2.H[1]; // SMALBT
Mres[31:0] = Rs1.H[1] * Rs2.H[1]; // SMALTT
Idx0 = CONCAT(Rd(4,1),1'b0); Idx1 = CONCAT(Rd(4,1),1'b1);
R[Idx1].R[Idx0] = R[Idx1].R[Idx0] + SE64(Mres[31:0]);
RV64:
// SMALBB
Mres[0][31:0] = Rs1.W[0].H[0] * Rs2.W[0].H[0];
Mres[1][31:0] = Rs1.W[1].H[0] * Rs2.W[1].H[0];
// SMALBT
Mres[0][31:0] = Rs1.W[0].H[0] * Rs2.W[0].H[1];
Mres[1][31:0] = Rs1.W[1].H[0] * Rs2.W[1].H[1];
// SMALTT
Mres[0][31:0] = Rs1.W[0].H[1] * Rs2.W[0].H[1];
Mres[1][31:0] = Rs1.W[1].H[1] * Rs2.W[1].H[1];
Rd = Rd + SE64(Mres[0][31:0]) + SE64(Mres[1][31:0]);
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_SMALDA (long long t, unsigned long a, unsigned long b)

SMALDA (Signed Multiply Two Halfs and Two Adds 64-bit)

Type: DSP (64-bit Profile)

Syntax:

```
SMALDA Rd, Rs1, Rs2
SMALXDA Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then adds the two 32-bit results and the 64-bit value of an even/odd pair of registers together.

- SMALDA: rt pair+ top*top + bottom*bottom (all 32-bit elements)
- SMALXDA: rt pair+ top*bottom + bottom*top (all 32-bit elements)

RV32 Description :

For the `SMALDA` instruction, it multiplies the bottom 16-bit content of Rs1 with the bottom 16-bit content of Rs2 and then adds the result to the result of multiplying the top 16-bit content of Rs1 with the top 16-bit content of Rs2 with unlimited precision. For the `SMALXDA` instruction, it multiplies the top 16-bit content of Rs1 with the bottom 16-bit content of Rs2 and then adds the result to the result of multiplying the bottom 16-bit content of Rs1 with the top 16-bit content of Rs2 with unlimited precision. The result is added to the 64-bit value of an even/odd pair of registers specified by Rd(4,1). The 64- bit addition result is written back to the register-pair. The 16-bit values of Rs1 and Rs2, and the 64- bit value of the register-pair are treated as signed integers. Rd(4,1), i.e., d, determines the even/odd pair group of the two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the operand and the even `2d` register of the pair contains the low 32-bit of the operand.

RV64 Description :

For the `SMALDA` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and then adds the result to the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32- bit elements of Rs2 with unlimited precision. For the `SMALXDA` instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and then adds the result to the result of multiplying the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 with unlimited precision. The results are added to the 64-bit value of Rd. The 64-bit addition result is written back to Rd. The 16-bit values of Rs1 and Rs2, and the 64-bit value of Rd are treated as signed integers.

Operations:

```
RV32:
// SMALDA
Mres0[31:0] = (Rs1.H[0] * Rs2.H[0]);
Mres1[31:0] = (Rs1.H[1] * Rs2.H[1]);
// SMALXDA
Mres0[31:0] = (Rs1.H[0] * Rs2.H[1]);
Mres1[31:0] = (Rs1.H[1] * Rs2.H[0]);
Idx0 = CONCAT(Rd(4,1),1'b0); Idx1 = CONCAT(Rd(4,1),1'b1);
R[Idx1].R[Idx0] = R[Idx1].R[Idx0] + SE64(Mres0[31:0]) + SE64(Mres1[31:0]);
RV64:
// SMALDA
Mres0[0][31:0] = (Rs1.W[0].H[0] * Rs2.W[0].H[0]);
Mres1[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[1]);
Mres0[1][31:0] = (Rs1.W[1].H[0] * Rs2.W[1].H[0]);
Mres1[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[1].H[1]);
// SMALXDA
Mres0[0][31:0] = (Rs1.W[0].H[0] * Rs2.W[0].H[1]);
Mres1[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[0]);
Mres0[1][31:0] = (Rs1.W[1].H[0] * Rs2.W[1].H[1]);
Mres1[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[1].H[0]);
Rd = Rd + SE64(Mres0[0][31:0]) + SE64(Mres1[0][31:0]) + SE64(Mres0[1][31:0]) +
SE64(Mres1[1][31:0]);
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long long type

`__STATIC_FORCEINLINE long long __RV_SMALXDA (long long t, unsigned long a, unsigned long b)`

SMALXDA (Signed Crossed Multiply Two Halfs and Two Adds 64-bit)

Type: DSP (64-bit Profile)

Syntax:

```
SMALDA Rd, Rs1, Rs2
SMALXDA Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then adds the two 32-bit results and the 64-bit value of an even/odd pair of registers together.

- SMALDA: rt pair+ top*top + bottom*bottom (all 32-bit elements)
- SMALXDA: rt pair+ top*bottom + bottom*top (all 32-bit elements)

RV32 Description :

For the SMALDA instruction, it multiplies the bottom 16-bit content of Rs1 with the bottom 16-bit content of Rs2 and then adds the result to the result of multiplying the top 16-bit content of Rs1 with the top 16-bit content of Rs2 with unlimited precision. For the SMALXDA instruction, it multiplies the top 16-bit content of Rs1 with the bottom 16-bit content of Rs2 and then adds the result to the result of multiplying the bottom 16-bit content of Rs1 with the top 16-bit content of Rs2 with unlimited precision. The result is added to the 64-bit value of an even/odd pair of registers specified by Rd(4,1). The 64- bit addition result is written back to the register-pair. The 16-bit values of Rs1 and Rs2, and the 64- bit value of the register-pair are treated as signed integers. Rd(4,1), i.e., d, determines the even/odd pair group of the two registers. Specifically, the register pair includes register 2d and 2d+1. The odd 2d+1 register of the pair contains the high 32-bit of the operand and the even 2d register of the pair contains the low 32-bit of the operand.

RV64 Description :

For the SMALDA instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and then adds the result to the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32- bit elements of Rs2 with unlimited precision. For the SMALXDA instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and then adds the result to the result of multiplying the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 with unlimited precision. The results are added to the 64-bit value of Rd. The 64-bit addition result is written back to Rd. The 16-bit values of Rs1 and Rs2, and the 64-bit value of Rd are treated as signed integers.

Operations:

```
RV32:
// SMALDA
Mres0[31:0] = (Rs1.H[0] * Rs2.H[0]);
Mres1[31:0] = (Rs1.H[1] * Rs2.H[1]);
// SMALXDA
Mres0[31:0] = (Rs1.H[0] * Rs2.H[1]);
Mres1[31:0] = (Rs1.H[1] * Rs2.H[0]);
Idx0 = CONCAT(Rd(4,1),1'b0); Idx1 = CONCAT(Rd(4,1),1'b1);
R[Idx1].R[Idx0] = R[Idx1].R[Idx0] + SE64(Mres0[31:0]) + SE64(Mres1[31:0]);
RV64:
// SMALDA
Mres0[0][31:0] = (Rs1.W[0].H[0] * Rs2.W[0].H[0]);
Mres1[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[1]);
Mres0[1][31:0] = (Rs1.W[1].H[0] * Rs2.W[1].H[0]);
Mres1[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[1].H[1]);
// SMALXDA
Mres0[0][31:0] = (Rs1.W[0].H[0] * Rs2.W[0].H[1]);
Mres1[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[0]);
```

(continues on next page)

(continued from previous page)

```
Mres0[1][31:0] = (Rs1.W[1].H[0] * Rs2.W[1].H[1]);
Mres1[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[1].H[0]);
Rd = Rd + SE64(Mres0[0][31:0]) + SE64(Mres1[0][31:0]) + SE64(Mres0[1][31:0]) +
SE64(Mres1[1][31:0]);
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_SMALDS (long long t, unsigned long a, unsigned long b)

SMALDS (Signed Multiply Two Halfs & Subtract & Add 64-bit)

Type: DSP (64-bit Profile)

Syntax:

```
SMALDS Rd, Rs1, Rs2
SMALDRS Rd, Rs1, Rs2
SMALXDS Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then perform a subtraction operation between the two 32-bit results. Then add the subtraction result to the 64-bit value of an even/odd pair of registers (RV32) or a register (RV64). The addition result is written back to the register-pair.

- SMALDS: rt pair + (top*top - bottom*bottom) (all 32-bit elements)
- SMALDRS: rt pair + (bottom*bottom - top*top) (all 32-bit elements)
- SMALXDS: rt pair + (top*bottom - bottom*top) (all 32-bit elements)

RV32 Description :

For the `SMALDS` instruction, it multiplies the bottom 16-bit content of Rs1 with the bottom 16-bit content of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of Rs1 with the top 16-bit content of Rs2. For the `SMALDRS` instruction, it multiplies the top 16-bit content of Rs1 with the top 16-bit content of Rs2 and then subtracts the result from the result of multiplying the bottom 16-bit content of Rs1 with the bottom 16-bit content of Rs2. For the `SMALXDS` instruction, it multiplies the bottom 16-bit content of Rs1 with the top 16-bit content of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of Rs1 with the bottom 16-bit content of Rs2. The subtraction result is then added to the 64-bit value of an even/odd pair of registers specified by Rd(4,1). The 64-bit addition result is written back to the register-pair. The 16-bit values of Rs1 and Rs2, and the 64-bit value of the register-pair are treated as signed integers. Rd(4,1), i.e., d, determines the even/odd pair group of the two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the operand and the even `2d` register of the pair contains the low 32-bit of the operand.

RV64 Description :

For the SMALDS instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. For the SMALDRS instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. For the SMALXDS instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. The subtraction results are then added to the 64-bit value of Rd. The 64-bit addition result is written back to Rd. The 16-bit values of Rs1 and Rs2, and the 64-bit value of Rd are treated as signed integers.

Operations:

```
* RV32:
Mres[31:0] = (Rs1.H[1] * Rs2.H[1]) - (Rs1.H[0] * Rs2.H[0]); // SMALDS
Mres[31:0] = (Rs1.H[0] * Rs2.H[0]) - (Rs1.H[1] * Rs2.H[1]); // SMALDRS
Mres[31:0] = (Rs1.H[1] * Rs2.H[0]) - (Rs1.H[0] * Rs2.H[1]); // SMALXDS
Idx0 = CONCAT(Rd(4,1),1'b0); Idx1 = CONCAT(Rd(4,1),1'b1);
R[Idx1].R[Idx0] = R[Idx1].R[Idx0] + SE64(Mres[31:0]);
* RV64:
// SMALDS
Mres[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[1]) - (Rs1.W[0].H[0] * Rs2.W[0].
↪H[0]);
Mres[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[0].H[1]) - (Rs1.W[1].H[0] * Rs2.W[1].
↪H[0]);
// SMALDRS
Mres[0][31:0] = (Rs1.W[0].H[0] * Rs2.W[0].H[0]) - (Rs1.W[0].H[1] * Rs2.W[0].
↪H[1]);
Mres[1][31:0] = (Rs1.W[1].H[0] * Rs2.W[0].H[0]) - (Rs1.W[1].H[1] * Rs2.W[1].
↪H[1]);
// SMALXDS
Mres[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[0]) - (Rs1.W[0].H[0] * Rs2.W[0].
↪H[1]);
Mres[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[0].H[0]) - (Rs1.W[1].H[0] * Rs2.W[1].
↪H[1]);
Rd = Rd + SE64(Mres[0][31:0]) + SE64(Mres[1][31:0]);
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_SMALDRS (long long t, unsigned long a, unsigned long b)

SMALDRS (Signed Multiply Two Halfs & Reverse Subtract & Add 64- bit)

Type: DSP (64-bit Profile)

Syntax:

```
SMALDS Rd, Rs1, Rs2
SMALDRS Rd, Rs1, Rs2
SMALXDS Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then perform a subtraction operation between the two 32-bit results. Then add the subtraction result to the 64-bit value of an even/odd pair of registers (RV32) or a register (RV64). The addition result is written back to the register-pair.

- SMALDS: rt pair + (top*top - bottom*bottom) (all 32-bit elements)
- SMALDRS: rt pair + (bottom*bottom - top*top) (all 32-bit elements)
- SMALXDS: rt pair + (top*bottom - bottom*top) (all 32-bit elements)

RV32 Description :

For the `SMALDS` instruction, it multiplies the bottom 16-bit content of Rs1 with the bottom 16-bit content of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of Rs1 with the top 16-bit content of Rs2. For the `SMALDRS` instruction, it multiplies the top 16-bit content of Rs1 with the top 16-bit content of Rs2 and then subtracts the result from the result of multiplying the bottom 16-bit content of Rs1 with the bottom 16-bit content of Rs2. For the `SMALXDS` instruction, it multiplies the bottom 16-bit content of Rs1 with the top 16-bit content of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of Rs1 with the bottom 16-bit content of Rs2. The subtraction result is then added to the 64-bit value of an even/odd pair of registers specified by Rd(4,1). The 64-bit addition result is written back to the register-pair. The 16-bit values of Rs1 and Rs2, and the 64-bit value of the register-pair are treated as signed integers. Rd(4,1), i.e., d, determines the even/odd pair group of the two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the operand and the even `2d` register of the pair contains the low 32-bit of the operand.

RV64 Description :

For the `SMALDS` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. For the `SMALDRS` instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. For the `SMALXDS` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. The subtraction results are then added to the 64-bit value of Rd. The 64-bit addition result is written back to Rd. The 16-bit values of Rs1 and Rs2, and the 64-bit value of Rd are treated as signed integers.

Operations:

```
* RV32:
Mres[31:0] = (Rs1.H[1] * Rs2.H[1]) - (Rs1.H[0] * Rs2.H[0]); // SMALDS
Mres[31:0] = (Rs1.H[0] * Rs2.H[0]) - (Rs1.H[1] * Rs2.H[1]); // SMALDRS
Mres[31:0] = (Rs1.H[1] * Rs2.H[0]) - (Rs1.H[0] * Rs2.H[1]); // SMALXDS
Idx0 = CONCAT(Rd(4,1),1'b0); Idx1 = CONCAT(Rd(4,1),1'b1);
R[Idx1].R[Idx0] = R[Idx1].R[Idx0] + SE64(Mres[31:0]);
* RV64:
```

(continues on next page)

(continued from previous page)

```
// SMALDS
Mres[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[1]) - (Rs1.W[0].H[0] * Rs2.W[0].
↪H[0]);
Mres[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[0].H[1]) - (Rs1.W[1].H[0] * Rs2.W[1].
↪H[0]);
// SMALDRS
Mres[0][31:0] = (Rs1.W[0].H[0] * Rs2.W[0].H[0]) - (Rs1.W[0].H[1] * Rs2.W[0].
↪H[1]);
Mres[1][31:0] = (Rs1.W[1].H[0] * Rs2.W[0].H[0]) - (Rs1.W[1].H[1] * Rs2.W[1].
↪H[1]);
// SMALXDS
Mres[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[0]) - (Rs1.W[0].H[0] * Rs2.W[0].
↪H[1]);
Mres[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[0].H[0]) - (Rs1.W[1].H[0] * Rs2.W[1].
↪H[1]);
Rd = Rd + SE64(Mres[0][31:0]) + SE64(Mres[1][31:0]);
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_SMALXDS (long long t, unsigned long a, unsigned long b)

SMALXDS (Signed Crossed Multiply Two Halfs & Subtract & Add 64- bit)

Type: DSP (64-bit Profile)

Syntax:

```
SMALDS Rd, Rs1, Rs2
SMALDRS Rd, Rs1, Rs2
SMALXDS Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then perform a subtraction operation between the two 32-bit results. Then add the subtraction result to the 64-bit value of an even/odd pair of registers (RV32) or a register (RV64). The addition result is written back to the register-pair.

- SMALDS: rt pair + (top*top - bottom*bottom) (all 32-bit elements)
- SMALDRS: rt pair + (bottom*bottom - top*top) (all 32-bit elements)
- SMALXDS: rt pair + (top*bottom - bottom*top) (all 32-bit elements)

RV32 Description :

For the `SMALDS` instruction, it multiplies the bottom 16-bit content of Rs1 with the bottom 16-bit content of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of Rs1 with the top 16-bit content of Rs2. For the `SMALDRS` instruction, it multiplies the top 16-bit content of Rs1 with the top 16-bit content of Rs2 and then subtracts the result from the result of multiplying the bottom 16-bit content of Rs1 with the bottom 16-bit content of Rs2. For the SMALXDS instruction, it multiplies the bottom 16-bit content of Rs1 with the top 16-bit content of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of Rs1 with the bottom 16-bit content of Rs2. The subtraction result is then added to the 64-bit value of an even/odd pair of registers specified by Rd(4,1). The 64-bit addition result is written back to the register-pair. The 16-bit values of Rs1 and Rs2, and the 64-bit value of the register-pair are treated as signed integers. Rd(4,1), i.e., d, determines the even/odd pair group of the two registers. Specifically, the register pair includes register 2d and 2d+1. The odd 2d+1 register of the pair contains the high 32-bit of the operand and the even 2d register of the pair contains the low 32-bit of the operand.

RV64 Description :

For the SMALDS instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. For the SMALDRS instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. For the SMALXDS instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. The subtraction results are then added to the 64-bit value of Rd. The 64-bit addition result is written back to Rd. The 16-bit values of Rs1 and Rs2, and the 64-bit value of Rd are treated as signed integers.

Operations:

```
* RV32:
Mres[31:0] = (Rs1.H[1] * Rs2.H[1]) - (Rs1.H[0] * Rs2.H[0]); // SMALDS
Mres[31:0] = (Rs1.H[0] * Rs2.H[0]) - (Rs1.H[1] * Rs2.H[1]); // SMALDRS
Mres[31:0] = (Rs1.H[1] * Rs2.H[0]) - (Rs1.H[0] * Rs2.H[1]); // SMALXDS
Idx0 = CONCAT(Rd(4,1),1'b0); Idx1 = CONCAT(Rd(4,1),1'b1);
R[Idx1].R[Idx0] = R[Idx1].R[Idx0] + SE64(Mres[31:0]);
* RV64:
// SMALDS
Mres[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[1]) - (Rs1.W[0].H[0] * Rs2.W[0].
↪H[0]);
Mres[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[0].H[1]) - (Rs1.W[1].H[0] * Rs2.W[1].
↪H[0]);
// SMALDRS
Mres[0][31:0] = (Rs1.W[0].H[0] * Rs2.W[0].H[0]) - (Rs1.W[0].H[1] * Rs2.W[0].
↪H[1]);
Mres[1][31:0] = (Rs1.W[1].H[0] * Rs2.W[0].H[0]) - (Rs1.W[1].H[1] * Rs2.W[1].
↪H[1]);
// SMALXDS
Mres[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[0]) - (Rs1.W[0].H[0] * Rs2.W[0].
↪H[1]);
Mres[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[0].H[0]) - (Rs1.W[1].H[0] * Rs2.W[1].
↪H[1]);
Rd = Rd + SE64(Mres[0][31:0]) + SE64(Mres[1][31:0]);
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a

- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_SMSLDA (long long t, unsigned long a, unsigned long b)

SMSLDA (Signed Multiply Two Halfs & Add & Subtract 64-bit)

Type: DSP (64-bit Profile)

Syntax:

```
SMSLDA Rd, Rs1, Rs2
SMSLXDA Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then subtracts the two 32-bit results from the 64-bit value of an even/odd pair of registers (RV32) or a register (RV64). The subtraction result is written back to the register-pair.

- SMSLDA: rd pair - top*top - bottom*bottom (all 32-bit elements)
- SMSLXDA: rd pair - top*bottom - bottom*top (all 32-bit elements)

RV32 Description :

For the `SMSLDA` instruction, it multiplies the bottom 16-bit content of Rs1 with the bottom 16-bit content Rs2 and multiplies the top 16-bit content of Rs1 with the top 16-bit content of Rs2. For the `SMSLXDA` instruction, it multiplies the top 16-bit content of Rs1 with the bottom 16-bit content of Rs2 and multiplies the bottom 16-bit content of Rs1 with the top 16-bit content of Rs2. The two multiplication results are subtracted from the 64-bit value of an even/odd pair of registers specified by Rd(4,1). The 64-bit subtraction result is written back to the register-pair. The 16-bit values of Rs1 and Rs2, and the 64-bit value of the register-pair are treated as signed integers. Rd(4,1), i.e., d, determines the even/odd pair group of the two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

For the `SMSLDA` instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. For the `SMSLXDA` instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. The four multiplication results are subtracted from the 64-bit value of Rd. The 64-bit subtraction result is written back to Rd. The 16-bit values of Rs1 and Rs2, and the 64-bit value of Rd are treated as signed integers.

Operations:

```
* RV32:
// SMSLDA
Mres0[31:0] = (Rs1.H[0] * Rs2.H[0]);
Mres1[31:0] = (Rs1.H[1] * Rs2.H[1]);
// SMSLXDA
Mres0[31:0] = (Rs1.H[0] * Rs2.H[1]);
Mres1[31:0] = (Rs1.H[1] * Rs2.H[0]);
Idx0 = CONCAT(Rd(4,1),1'b0); Idx1 = CONCAT(Rd(4,1),1'b1);
R[Idx1].R[Idx0] = R[Idx1].R[Idx0] - SE64(Mres0[31:0]) - SE64(Mres1[31:0]);
```

(continues on next page)

(continued from previous page)

```
* RV64:
// SMSLDA
Mres0[0][31:0] = (Rs1.W[0].H[0] * Rs2.W[0].H[0]);
Mres1[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[1]);
Mres0[1][31:0] = (Rs1.W[1].H[0] * Rs2.W[1].H[0]);
Mres1[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[1].H[1]);
// SMSLXDA
Mres0[0][31:0] = (Rs1.W[0].H[0] * Rs2.W[0].H[1]);
Mres1[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[0]);
Mres0[1][31:0] = (Rs1.W[1].H[0] * Rs2.W[1].H[1]);
Mres1[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[1].H[0]);
Rd = Rd - SE64(Mres0[0][31:0]) - SE64(Mres1[0][31:0]) - SE64(Mres0[1][31:0]) -
SE64(Mres1[1][31:0]);
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_SMSLXDA (long long t, unsigned long a, unsigned long b)

SMSLXDA (Signed Crossed Multiply Two Halfs & Add & Subtract 64- bit)

Type: DSP (64-bit Profile)

Syntax:

```
SMSLDA Rd, Rs1, Rs2
SMSLXDA Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then subtracts the two 32-bit results from the 64-bit value of an even/odd pair of registers (RV32) or a register (RV64). The subtraction result is written back to the register-pair.

- SMSLDA: rd pair - top*top - bottom*bottom (all 32-bit elements)
- SMSLXDA: rd pair - top*bottom - bottom*top (all 32-bit elements)

RV32 Description :

For the `SMSLDA` instruction, it multiplies the bottom 16-bit content of Rs1 with the bottom 16-bit content Rs2 and multiplies the top 16-bit content of Rs1 with the top 16-bit content of Rs2. For the `SMSLXDA` instruction, it multiplies the top 16-bit content of Rs1 with the bottom 16-bit content of Rs2 and multiplies the bottom 16-bit content of Rs1 with the top 16-bit content of Rs2. The two multiplication results are subtracted from the 64-bit value of an even/odd pair of registers specified by Rd(4,1). The 64-bit subtraction result is written back to the register-pair. The 16-bit values of Rs1 and Rs2, and the 64-bit value of the register-pair are treated as signed integers. Rd(4,1), i.e., d, determines the even/odd pair group of the two registers. Specifically, the register pair includes register 2d and 2d+1. The odd `2d+1` register of the pair contains the high 32-bit of the result and the even `2d` register of the pair contains the low 32-bit of the result.

RV64 Description :

For the SMSLDA instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. For the SMSLXDA instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. The four multiplication results are subtracted from the 64-bit value of Rd. The 64-bit subtraction result is written back to Rd. The 16-bit values of Rs1 and Rs2, and the 64-bit value of Rd are treated as signed integers.

Operations:

```
* RV32:
// SMSLDA
Mres0[31:0] = (Rs1.H[0] * Rs2.H[0]);
Mres1[31:0] = (Rs1.H[1] * Rs2.H[1]);
// SMSLXDA
Mres0[31:0] = (Rs1.H[0] * Rs2.H[1]);
Mres1[31:0] = (Rs1.H[1] * Rs2.H[0]);
Idx0 = CONCAT(Rd(4,1),1'b0); Idx1 = CONCAT(Rd(4,1),1'b1);
R[Idx1].R[Idx0] = R[Idx1].R[Idx0] - SE64(Mres0[31:0]) - SE64(Mres1[31:0]);
* RV64:
// SMSLDA
Mres0[0][31:0] = (Rs1.W[0].H[0] * Rs2.W[0].H[0]);
Mres1[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[1]);
Mres0[1][31:0] = (Rs1.W[1].H[0] * Rs2.W[1].H[0]);
Mres1[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[1].H[1]);
// SMSLXDA
Mres0[0][31:0] = (Rs1.W[0].H[0] * Rs2.W[0].H[1]);
Mres1[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[0]);
Mres0[1][31:0] = (Rs1.W[1].H[0] * Rs2.W[1].H[1]);
Mres1[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[1].H[0]);
Rd = Rd - SE64(Mres0[0][31:0]) - SE64(Mres1[0][31:0]) - SE64(Mres0[1][31:0]) -
SE64(Mres1[1][31:0]);
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long long type

group **NMSIS_Core_DSP_Intrinsic_64B_PROFILE**

64-bit Profile Instructions

RV64 Only Instructions

(RV64 Only) SIMD 32-bit Add/Subtract Instructions

`__STATIC_FORCEINLINE unsigned long __RV_ADD32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_CRAS32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_CRSA32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_KADD32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_KCRAS32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_KCRSA32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_KSTAS32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_KSTSA32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_KSUB32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_RADD32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_RCRAS32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_RCRSA32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_RSTAS32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_RSTSA32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_RSUB32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_STAS32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_STSA32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_SUB32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long __RV_UKADD32 (unsigned long a, unsigned long b)`

__STATIC_FORCEINLINE unsigned long __RV_UKCRAS32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UKCRSA32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UKSTAS32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UKSTSA32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UKSUB32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_URADD32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_URCRAS32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_URCRSA32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_URSTAS32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_URSTSA32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_URSUB32 (unsigned long a, unsigned long b)

group NMSIS_Core_DSP_Intrinsic_RV64_SIMD_32B_ADDSUB

(RV64 Only) SIMD 32-bit Add/Subtract Instructions

The following tables list instructions that are only present in RV64. There are 30 SIMD 32-bit addition or subtraction instructions.there are 4 SIMD16-bit Packing Instructions.

Functions

__STATIC_FORCEINLINE unsigned long __RV_ADD32 (unsigned long a, unsigned long b)

ADD32 (SIMD 32-bit Addition)

Type: SIMD (RV64 Only)

Syntax:

```
ADD32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit integer element additions simultaneously.

Description :

This instruction adds the 32-bit integer elements in Rs1 with the 32-bit integer elements in Rs2, and then writes the 32-bit element results to Rd.

Note :

This instruction can be used for either signed or unsigned addition.

Operations:

```
Rd.W[x] = Rs1.W[x] + Rs2.W[x];
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_CRAS32 (unsigned long a, unsigned long b)

CRAS32 (SIMD 32-bit Cross Addition & Subtraction)

Type: SIMD (RV64 Only)

Syntax:

```
CRAS32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit integer element addition and 32-bit integer element subtraction in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements.

Description :

This instruction adds the 32-bit integer element in [63:32] of Rs1 with the 32-bit integer element in [31:0] of Rs2, and writes the result to [63:32] of Rd; at the same time, it subtracts the 32-bit integer element in [63:32] of Rs2 from the 32-bit integer element in [31:0] of Rs1, and writes the result to [31:0] of Rd.

Note :

This instruction can be used for either signed or unsigned operations.

Operations:

```
Rd.W[1] = Rs1.W[1] + Rs2.W[0];
Rd.W[0] = Rs1.W[0] - Rs2.W[1];
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_CRSA32 (unsigned long a, unsigned long b)

CRSA32 (SIMD 32-bit Cross Subtraction & Addition)

Type: SIMD (RV64 Only)

Syntax:

```
CRSA32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit integer element subtraction and 32-bit integer element addition in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements. *Description: * This instruction subtracts the 32-bit integer element in [31:0] of Rs2 from the 32-bit integer element in [63:32] of Rs1, and writes the result to [63:32] of Rd; at the same time, it adds the 32-bit integer element in [31:0] of Rs1 with the 32-bit integer element in [63:32] of Rs2, and writes the result to [31:0] of Rd

Note :

This instruction can be used for either signed or unsigned operations.

Operations:

```
Rd.W[1] = Rs1.W[1] - Rs2.W[0];
Rd.W[0] = Rs1.W[0] + Rs2.W[1];
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KADD32 (unsigned long a, unsigned long b)

KADD32 (SIMD 32-bit Signed Saturating Addition)

Type: SIMD (RV64 Only)

Syntax:

```
KADD32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit signed integer element saturating additions simultaneously.

Description :

This instruction adds the 32-bit signed integer elements in Rs1 with the 32-bit signed integer elements in Rs2. If any of the results are beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.W[x] + Rs2.W[x];
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a

- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KCRAS32 (unsigned long a, unsigned long b)

KCRAS32 (SIMD 32-bit Signed Saturating Cross Addition & Subtraction)

Type: SIM (RV64 Only)

Syntax:

```
KCRAS32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit signed integer element saturating addition and 32-bit signed integer element saturating subtraction in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements.

Description :

This instruction adds the 32-bit integer element in [63:32] of Rs1 with the 32-bit integer element in [31:0] of Rs2; at the same time, it subtracts the 32-bit integer element in [63:32] of Rs2 from the 32-bit integer element in [31:0] of Rs1. If any of the results are beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [63:32] of Rd for addition and [31:0] of Rd for subtraction.

Operations:

```
res[1] = Rs1.W[1] + Rs2.W[0];
res[0] = Rs1.W[0] - Rs2.W[1];
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[1] = res[1];
Rd.W[0] = res[0];
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KCRSA32 (unsigned long a, unsigned long b)

KCRSA32 (SIMD 32-bit Signed Saturating Cross Subtraction & Addition)

Type: SIMD (RV64 Only)

Syntax:

```
KCRSA32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit signed integer element saturating subtraction and 32-bit signed integer element saturating addition in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements. *Description: * This instruction subtracts the 32-bit integer element in [31:0] of Rs2 from the 32-bit integer element in [63:32] of Rs1; at the same time, it adds the 32-bit integer element in [31:0] of Rs1 with the 32-bit integer element in [63:32] of Rs2. If any of the results are beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [63:32] of Rd for subtraction and [31:0] of Rd for addition.

Operations:

```
res[1] = Rs1.W[1] - Rs2.W[0];
res[0] = Rs1.W[0] + Rs2.W[1];
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[1] = res[1];
Rd.W[0] = res[0];
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KSTAS32 (unsigned long a, unsigned long b)

KSTAS32 (SIMD 32-bit Signed Saturating Straight Addition & Subtraction)

Type: SIMD (RV64 Only)

Syntax:

```
KSTAS32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit signed integer element saturating addition and 32-bit signed integer element saturating subtraction in a 64-bit chunk simultaneously. Operands are from corresponding 32-bit elements.

Description :

This instruction adds the 32-bit integer element in [63:32] of Rs1 with the 32-bit integer element in [63:32] of Rs2; at the same time, it subtracts the 32-bit integer element in [31:0] of Rs2 from the 32-bit integer element in [31:0] of Rs1. If any of the results are beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [63:32] of Rd for addition and [31:0] of Rd for subtraction.

Operations:

```
res[1] = Rs1.W[1] + Rs2.W[1];
res[0] = Rs1.W[0] - Rs2.W[0];
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[1] = res[1];
Rd.W[0] = res[0];
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KSTSA32 (unsigned long a, unsigned long b)

KSTSA32 (SIMD 32-bit Signed Saturating Straight Subtraction & Addition)

Type: SIM (RV64 Only)

Syntax:

```
KSTSA32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit signed integer element saturating subtraction and 32-bit signed integer element saturating addition in a 64-bit chunk simultaneously. Operands are from corresponding 32-bit elements. *Description: * This instruction subtracts the 32-bit integer element in [63:32] of Rs2 from the 32-bit integer element in [63:32] of Rs1; at the same time, it adds the 32-bit integer element in [31:0] of Rs1 with the 32-bit integer element in [31:0] of Rs2. If any of the results are beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [63:32] of Rd for subtraction and [31:0] of Rd for addition.

Operations:

```
res[1] = Rs1.W[1] - Rs2.W[1];
res[0] = Rs1.W[0] + Rs2.W[0];
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[1] = res[1];
Rd.W[0] = res[0];
for RV64, x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KSUB32 (unsigned long a, unsigned long b)

KSUB32 (SIMD 32-bit Signed Saturating Subtraction)

Type: SIMD (RV64 Only)

Syntax:

```
KSUB32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit signed integer elements saturating subtractions simultaneously.

Description :

This instruction subtracts the 32-bit signed integer elements in Rs2 from the 32-bit signed integer elements in Rs1. If any of the results are beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.W[x] - Rs2.W[x];
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_RADD32 (unsigned long a, unsigned long b)

RADD32 (SIMD 32-bit Signed Halving Addition)

Type: SIMD (RV64 Only)

Syntax:

```
RADD32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit signed integer element additions simultaneously. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 32-bit signed integer elements in Rs1 with the 32-bit signed integer elements in Rs2. The results are first arithmetically right-shifted by 1 bit and then written to Rd.

Examples:

```
* Rs1 = 0x7FFFFFFF, Rs2 = 0x7FFFFFFF Rd = 0x7FFFFFFF
* Rs1 = 0x80000000, Rs2 = 0x80000000 Rd = 0x80000000
* Rs1 = 0x40000000, Rs2 = 0x80000000 Rd = 0xE0000000
```

Operations:

```
Rd.W[x] = (Rs1.W[x] + Rs2.W[x]) s>> 1;
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_RCRAS32 (unsigned long a, unsigned long b)

RCRAS32 (SIMD 32-bit Signed Halving Cross Addition & Subtraction)

Type: SIMD (RV64 Only)

Syntax:

```
RCRAS32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit signed integer element addition and 32-bit signed integer element subtraction in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 32-bit signed integer element in [63:32] of Rs1 with the 32-bit signed integer element in [31:0] of Rs2, and subtracts the 32-bit signed integer element in [63:32] of Rs2 from the 32-bit signed integer element in [31:0] of Rs1. The element results are first arithmetically right-shifted by 1 bit and then written to [63:32] of Rd for addition and [31:0] of Rd for subtraction.

Examples:

```
Please see `RADD32` and `RSUB32` instructions.
```

Operations:

```
Rd.W[1] = (Rs1.W[1] + Rs2.W[0]) s>> 1;
Rd.W[0] = (Rs1.W[0] - Rs2.W[1]) s>> 1;
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_RCRSA32 (unsigned long a, unsigned long b)

RCRSA32 (SIMD 32-bit Signed Halving Cross Subtraction & Addition)

Type: SIMD (RV64 Only)

Syntax:

```
RCRSA32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit signed integer element subtraction and 32-bit signed integer element addition in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 32-bit signed integer element in [31:0] of Rs2 from the 32-bit signed integer element in [63:32] of Rs1, and adds the 32-bit signed element integer in [31:0] of Rs1 with the 32-bit signed integer element in [63:32] of Rs2. The two results are first arithmetically right-shifted by 1 bit and then written to [63:32] of Rd for subtraction and [31:0] of Rd for addition.

Examples:

```
Please see `RADD32` and `RSUB32` instructions.
```

Operations:

```
Rd.W[1] = (Rs1.W[1] - Rs2.W[0]) s>> 1;
Rd.W[0] = (Rs1.W[0] + Rs2.W[1]) s>> 1;
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_RSTAS32 (unsigned long a, unsigned long b)

RSTAS32 (SIMD 32-bit Signed Halving Straight Addition & Subtraction)

Type: SIMD (RV64 Only)

Syntax:

```
RSTAS32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit signed integer element addition and 32-bit signed integer element subtraction in a 64-bit chunk simultaneously. Operands are from corresponding 32-bit elements. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 32-bit signed integer element in [63:32] of Rs1 with the 32-bit signed integer element in [63:32] of Rs2, and subtracts the 32-bit signed integer element in [31:0] of Rs2 from the 32-bit signed integer element in [31:0] of Rs1. The element results are first arithmetically right-shifted by 1 bit and then written to [63:32] of Rd for addition and [31:0] of Rd for subtraction.

Examples:

```
Please see `RADD32` and `RSUB32` instructions.
```

Operations:

```
Rd.W[1] = (Rs1.W[1] + Rs2.W[1]) s>> 1;
Rd.W[0] = (Rs1.W[0] - Rs2.W[0]) s>> 1;
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_RSTSA32 (unsigned long a, unsigned long b)

RSTSA32 (SIMD 32-bit Signed Halving Straight Subtraction & Addition)

Type: SIMD (RV64 Only)

Syntax:

```
RSTSA32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit signed integer element subtraction and 32-bit signed integer element addition in a 64-bit chunk simultaneously. Operands are from corresponding 32-bit elements. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 32-bit signed integer element in [63:32] of Rs2 from the 32-bit signed integer element in [63:32] of Rs1, and adds the 32-bit signed element integer in [31:0] of Rs1 with the 32-bit signed integer element in [31:0] of Rs2. The two results are first arithmetically right-shifted by 1 bit and then written to [63:32] of Rd for subtraction and [31:0] of Rd for addition.

Examples:

```
Please see `RADD32` and `RSUB32` instructions.
```

Operations:

```
Rd.W[1] = (Rs1.W[1] - Rs2.W[1]) s>> 1;
Rd.W[0] = (Rs1.W[0] + Rs2.W[0]) s>> 1;
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_RSUB32 (unsigned long a, unsigned long b)

RSUB32 (SIMD 32-bit Signed Halving Subtraction)

Type: SIMD (RV64 Only)

Syntax:

```
RSUB32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit signed integer element subtractions simultaneously. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 32-bit signed integer elements in Rs2 from the 32-bit signed integer elements in Rs1. The results are first arithmetically right-shifted by 1 bit and then written to Rd.

Examples:

```
* Ra = 0x7FFFFFFF, Rb = 0x80000000 Rt = 0x7FFFFFFF
* Ra = 0x80000000, Rb = 0x7FFFFFFF Rt = 0x80000000
* Ra = 0x80000000, Rb = 0x40000000 Rt = 0xA0000000
```

Operations:

```
Rd.W[x] = (Rs1.W[x] - Rs2.W[x]) s>> 1;
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_STAS32 (unsigned long a, unsigned long b)

STAS32 (SIMD 32-bit Straight Addition & Subtraction)

Type: SIMD (RV64 Only)

Syntax:

```
STAS32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit integer element addition and 32-bit integer element subtraction in a 64-bit chunk simultaneously. Operands are from corresponding 32-bit elements.

Description :

This instruction adds the 32-bit integer element in [63:32] of Rs1 with the 32-bit integer element in [63:32] of Rs2, and writes the result to [63:32] of Rd; at the same time, it subtracts the 32-bit integer element in [31:0] of Rs2 from the 32-bit integer element in [31:0] of Rs1, and writes the result to [31:0] of Rd.

Note :

This instruction can be used for either signed or unsigned operations.

Operations:

```
Rd.W[1] = Rs1.W[1] + Rs2.W[1];
Rd.W[0] = Rs1.W[0] - Rs2.W[0];
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_STSA32 (unsigned long a, unsigned long b)

STSA32 (SIMD 32-bit Straight Subtraction & Addition)

Type: SIMD (RV64 Only)

Syntax:

```
STSA32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit integer element subtraction and 32-bit integer element addition in a 64-bit chunk simultaneously. Operands are from corresponding 32-bit elements. *Description: * This instruction subtracts the 32-bit integer element in [63:32] of Rs2 from the 32-bit integer element in [63:32] of Rs1, and writes the result to [63:32] of Rd; at the same time, it adds the 32-bit integer element in [31:0] of Rs1 with the 32-bit integer element in [31:0] of Rs2, and writes the result to [31:0] of Rd

Note :

This instruction can be used for either signed or unsigned operations.

Operations:

```
Rd.W[1] = Rs1.W[1] - Rs2.W[1];
Rd.W[0] = Rs1.W[0] + Rs2.W[0];
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SUB32 (unsigned long a, unsigned long b)

SUB32 (SIMD 32-bit Subtraction)

Type: DSP (RV64 Only)

Syntax:

```
SUB32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit integer element subtractions simultaneously.

Description :

This instruction subtracts the 32-bit integer elements in Rs2 from the 32-bit integer elements in Rs1, and then writes the results to Rd.

Note :

This instruction can be used for either signed or unsigned subtraction.

Operations:

```
Rd.W[x] = Rs1.W[x] - Rs2.W[x];
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UKADD32 (unsigned long a, unsigned long b)

UKADD32 (SIMD 32-bit Unsigned Saturating Addition)

Type: SIMD (RV64 Only)

Syntax:

```
UKADD32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit unsigned integer element saturating additions simultaneously.

Description :

This instruction adds the 32-bit unsigned integer elements in Rs1 with the 32-bit unsigned integer elements in Rs2. If any of the results are beyond the 32-bit unsigned number range (0 <= RES <= 2^32-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.W[x] + Rs2.W[x];
if (res[x] > (2^32)-1) {
  res[x] = (2^32)-1;
  OV = 1;
}
Rd.W[x] = res[x];
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UKCRAS32 (unsigned long a, unsigned long b)

UKCRAS32 (SIMD 32-bit Unsigned Saturating Cross Addition & Subtraction)

Type: SIMD (RV64 Only)

Syntax:

```
UKCRAS32 Rd, Rs1, Rs2
```

Purpose :

Do one 32-bit unsigned integer element saturating addition and one 32-bit unsigned integer element saturating subtraction in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements.

Description :

This instruction adds the 32-bit unsigned integer element in [63:32] of Rs1 with the 32- bit unsigned integer element in [31:0] of Rs2; at the same time, it subtracts the 32-bit unsigned integer element in [63:32] of Rs2 from the 32-bit unsigned integer element in [31:0] Rs1. If any of the results are beyond the 32-bit unsigned number range (0 <= RES <= 2^32-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [63:32] of Rd for addition and [31:0] of Rd for subtraction.

Operations:

```
res1 = Rs1.W[1] + Rs2.W[0];
res2 = Rs1.W[0] - Rs2.W[1];
if (res1 > (2^32)-1) {
  res1 = (2^32)-1;
  OV = 1;
}
if (res2 < 0) {
  res2 = 0;
  OV = 1;
}
Rd.W[1] = res1;
Rd.W[0] = res2;
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_UKCRSA32 (unsigned long a, unsigned long b)`

UKCRSA32 (SIMD 32-bit Unsigned Saturating Cross Subtraction & Addition)

Type: SIMD (RV64 Only)

Syntax:

```
UKCRSA32 Rd, Rs1, Rs2
```

Purpose :

Do one 32-bit unsigned integer element saturating subtraction and one 32-bit unsigned integer element saturating addition in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements.

Description :

This instruction subtracts the 32-bit unsigned integer element in [31:0] of Rs2 from the 32-bit unsigned integer element in [63:32] of Rs1; at the same time, it adds the 32-bit unsigned integer element in [63:32] of Rs2 with the 32-bit unsigned integer element in [31:0] Rs1. If any of the results are beyond the 32-bit unsigned number range (0 <= RES <= 2^32-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [63:32] of Rd for subtraction and [31:0] of Rd for addition.

Operations:

```
res1 = Rs1.W[1] - Rs2.W[0];
res2 = Rs1.W[0] + Rs2.W[1];
if (res1 < 0) {
  res1 = 0;
  OV = 1;
} else if (res2 > (2^32)-1) {
  res2 = (2^32)-1;
  OV = 1;
}
Rd.W[1] = res1;
Rd.W[0] = res2;
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UKSTAS32 (unsigned long a, unsigned long b)

UKSTAS32 (SIMD 32-bit Unsigned Saturating Straight Addition & Subtraction)

Type: SIMD (RV64 Only)

Syntax:

```
UKSTAS32 Rd, Rs1, Rs2
```

Purpose :

Do one 32-bit unsigned integer element saturating addition and one 32-bit unsigned integer element saturating subtraction in a 64-bit chunk simultaneously. Operands are from corresponding 32-bit elements.

Description :

This instruction adds the 32-bit unsigned integer element in [63:32] of Rs1 with the 32- bit unsigned integer element in [63:32] of Rs2; at the same time, it subtracts the 32-bit unsigned integer element in [31:0] of Rs2 from the 32-bit unsigned integer element in [31:0] Rs1. If any of the results are beyond the 32-bit unsigned number range (0 <= RES <= 2^32-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [63:32] of Rd for addition and [31:0] of Rd for subtraction.

Operations:

```
res1 = Rs1.W[1] + Rs2.W[1];
res2 = Rs1.W[0] - Rs2.W[0];
if (res1 > (2^32)-1) {
  res1 = (2^32)-1;
  OV = 1;
}
if (res2 < 0) {
  res2 = 0;
  OV = 1;
```

(continues on next page)

(continued from previous page)

```
}
Rd.W[1] = res1;
Rd.W[0] = res2;
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_UKSTSA32 (unsigned long a, unsigned long b)

UKSTSA32 (SIMD 32-bit Unsigned Saturating Straight Subtraction & Addition)

Type: SIMD (RV64 Only)

Syntax:

```
UKSTSA32 Rd, Rs1, Rs2
```

Purpose :

Do one 32-bit unsigned integer element saturating subtraction and one 32-bit unsigned integer element saturating addition in a 64-bit chunk simultaneously. Operands are from corresponding 32-bit elements.

Description :

This instruction subtracts the 32-bit unsigned integer element in [63:32] of Rs2 from the 32-bit unsigned integer element in [63:32] of Rs1; at the same time, it adds the 32-bit unsigned integer element in [31:0] of Rs2 with the 32-bit unsigned integer element in [31:0] Rs1. If any of the results are beyond the 32-bit unsigned number range (0 <= RES <= 2^32-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [63:32] of Rd for subtraction and [31:0] of Rd for addition.

Operations:

```
res1 = Rs1.W[1] - Rs2.W[1];
res2 = Rs1.W[0] + Rs2.W[0];
if (res1 < 0) {
  res1 = 0;
  OV = 1;
} else if (res2 > (2^32)-1) {
  res2 = (2^32)-1;
  OV = 1;
}
Rd.W[1] = res1;
Rd.W[0] = res2;
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_UKSUB32 (unsigned long a, unsigned long b)`

UKSUB32 (SIMD 32-bit Unsigned Saturating Subtraction)

Type: SIMD (RV64 Only)

Syntax:

```
UKSUB32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit unsigned integer elements saturating subtractions simultaneously.

Description :

This instruction subtracts the 32-bit unsigned integer elements in Rs2 from the 32-bit unsigned integer elements in Rs1. If any of the results are beyond the 32-bit unsigned number range (0 <= RES <= 2^32-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.W[x] - Rs2.W[x];
if (res[x] < 0) {
  res[x] = 0;
  OV = 1;
}
Rd.W[x] = res[x];
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_URADD32 (unsigned long a, unsigned long b)`

URADD32 (SIMD 32-bit Unsigned Halving Addition)

Type: SIMD (RV64 Only)

Syntax:

```
URADD32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit unsigned integer element additions simultaneously. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 32-bit unsigned integer elements in Rs1 with the 32-bit unsigned integer elements in Rs2. The results are first logically right-shifted by 1 bit and then written to Rd.

Examples:

```
* Ra = 0x7FFFFFFF, Rb = 0x7FFFFFFF Rt = 0x7FFFFFFF
* Ra = 0x80000000, Rb = 0x80000000 Rt = 0x80000000
* Ra = 0x40000000, Rb = 0x80000000 Rt = 0x60000000
```

Operations:

```
Rd.W[x] = (Rs1.W[x] + Rs2.W[x]) u>> 1;
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_URCRAS32 (unsigned long a, unsigned long b)

URCRAS32 (SIMD 32-bit Unsigned Halving Cross Addition & Subtraction)

Type: SIMD (RV64 Only)

Syntax:

```
URCRAS32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit unsigned integer element addition and 32-bit unsigned integer element subtraction in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 32-bit unsigned integer element in [63:32] of Rs1 with the 32- bit unsigned integer element in [31:0] of Rs2, and subtracts the 32-bit unsigned integer element in [63:32] of Rs2 from the 32-bit unsigned integer element in [31:0] of Rs1. The element results are first logically right-shifted by 1 bit and then written to [63:32] of Rd for addition and [31:0] of Rd for subtraction.

Examples:

```
Please see `URADD32` and `URSUB32` instructions.
```

Operations:

```
Rd.W[1] = (Rs1.W[1] + Rs2.W[0]) u>> 1;
Rd.W[0] = (Rs1.W[0] - Rs2.W[1]) u>> 1;
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_URCRSA32 (unsigned long a, unsigned long b)`

URCRSA32 (SIMD 32-bit Unsigned Halving Cross Subtraction & Addition)

Type: SIMD (RV64 Only)

Syntax:

```
URCRSA32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit unsigned integer element subtraction and 32-bit unsigned integer element addition in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 32-bit unsigned integer element in [31:0] of Rs2 from the 32-bit unsigned integer element in [63:32] of Rs1, and adds the 32-bit unsigned element integer in [31:0] of Rs1 with the 32-bit unsigned integer element in [63:32] of Rs2. The two results are first logically right-shifted by 1 bit and then written to [63:32] of Rd for subtraction and [31:0] of Rd for addition.

Examples:

```
Please see `URADD32` and `URSUB32` instructions.
```

Operations:

```
Rd.W[1] = (Rs1.W[1] - Rs2.W[0]) u>> 1;
Rd.W[0] = (Rs1.W[0] + Rs2.W[1]) u>> 1;
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_URSTAS32 (unsigned long a, unsigned long b)`

URSTAS32 (SIMD 32-bit Unsigned Halving Straight Addition & Subtraction)

Type: SIMD (RV64 Only)

Syntax:

```
URSTAS32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit unsigned integer element addition and 32-bit unsigned integer element subtraction in a 64-bit chunk simultaneously. Operands are from corresponding 32-bit elements. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 32-bit unsigned integer element in [63:32] of Rs1 with the 32- bit unsigned integer element in [63:32] of Rs2, and subtracts the 32-bit unsigned integer element in [31:0] of Rs2 from the 32-bit unsigned integer element in [31:0] of Rs1. The element results are first logically right-shifted by 1 bit and then written to [63:32] of Rd for addition and [31:0] of Rd for subtraction.

Examples:

```
Please see `URADD32` and `URSUB32` instructions.
```

Operations:

```
Rd.W[1] = (Rs1.W[1] + Rs2.W[1]) u>> 1;
Rd.W[0] = (Rs1.W[0] - Rs2.W[0]) u>> 1;
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_URSTSA32 (unsigned long a, unsigned long b)

URSTSA32 (SIMD 32-bit Unsigned Halving Straight Subtraction & Addition)

Type: SIMD (RV64 Only)

Syntax:

```
URSTSA32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit unsigned integer element subtraction and 32-bit unsigned integer element addition in a 64-bit chunk simultaneously. Operands are from corresponding 32-bit elements. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 32-bit unsigned integer element in [63:32] of Rs2 from the 32-bit unsigned integer element in [63:32] of Rs1, and adds the 32-bit unsigned element integer in [31:0] of Rs1 with the 32-bit unsigned integer element in [31:0] of Rs2. The two results are first logically right-shifted by 1 bit and then written to [63:32] of Rd for subtraction and [31:0] of Rd for addition.

Examples:

```
Please see `URADD32` and `URSUB32` instructions.
```

Operations:

```
Rd.W[1] = (Rs1.W[1] - Rs2.W[1]) u>> 1;
Rd.W[0] = (Rs1.W[0] + Rs2.W[0]) u>> 1;
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_URSUB32 (unsigned long a, unsigned long b)

URSUB32 (SIMD 32-bit Unsigned Halving Subtraction)

Type: SIMD (RV64 Only)

Syntax:

```
URSUB32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit unsigned integer element subtractions simultaneously. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 32-bit unsigned integer elements in Rs2 from the 32-bit unsigned integer elements in Rs1. The results are first logically right-shifted by 1 bit and then written to Rd.

Examples:

```
* Ra = 0x7FFFFFFF, Rb = 0x80000000, Rt = 0xFFFFFFFF
* Ra = 0x80000000, Rb = 0x7FFFFFFF, Rt = 0x00000000
* Ra = 0x80000000, Rb = 0x40000000, Rt = 0x20000000
```

Operations:

```
Rd.W[x] = (Rs1.W[x] - Rs2.W[x]) u>> 1;
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

(RV64 Only) SIMD 32-bit Shift Instructions

__STATIC_FORCEINLINE unsigned long __RV_KSLL32 (unsigned long a, unsigned int b)

__STATIC_FORCEINLINE unsigned long __RV_KSLRA32 (unsigned long a, int b)

__STATIC_FORCEINLINE unsigned long __RV_KSLRA32_U (unsigned long a, int b)

__STATIC_FORCEINLINE unsigned long __RV_SLL32 (unsigned long a, unsigned int b)

__STATIC_FORCEINLINE unsigned long __RV_SRA32 (unsigned long a, unsigned int b)

__STATIC_FORCEINLINE unsigned long __RV_SRA32_U (unsigned long a, unsigned int b)

__STATIC_FORCEINLINE unsigned long __RV_SRL32 (unsigned long a, unsigned int b)

__STATIC_FORCEINLINE unsigned long __RV_SRL32_U (unsigned long a, unsigned int b)

__RV_KSLLI32(a, b)

__RV_SLLI32(a, b)

__RV_SRAI32(a, b)

__RV_SRAI32_U(a, b)

__RV_SRLI32(a, b)

__RV_SRLI32_U(a, b)

group **NMSIS_Core_DSP_Intrinsic_RV64_SIMD_32B_SHIFT**

(RV64 Only) SIMD 32-bit Shift Instructions

there are 14 (RV64 Only) SIMD 32-bit Shift Instructions

Defines

__RV_KSLLI32(a, b)

KSLLI32 (SIMD 32-bit Saturating Shift Left Logical Immediate)

Type: SIMD (RV64 Only)

Syntax:

```
KSLLI32 Rd, Rs1, imm5u
```

Purpose :

Do 32-bit elements logical left shift operations with saturation simultaneously. The shift amount is an immediate value.

Description :

The 32-bit data elements in Rs1 are left-shifted logically. The shifted out bits are filled with zero and the shift amount is specified by the imm5u constant. Any shifted value greater than 2^31-1 is saturated to 2^31-1. Any shifted value smaller than -2^31 is saturated to -2^31. And the saturated results are written to Rd. If any saturation is performed, set OV bit to 1.

Operations:

```
sa = imm5u[4:0];
if (sa != 0) {
  res[(31+sa):0] = Rs1.W[x] << sa;
  if (res > (2^31)-1) {
    res = 0x7fffffff; OV = 1;
  } else if (res < -2^31) {
    res = 0x80000000; OV = 1;
  }
  Rd.W[x] = res[31:0];
} else {
  Rd = Rs1;
}
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__RV_SLLI32(a, b)

SLLI32 (SIMD 32-bit Shift Left Logical Immediate)

Type: SIMD (RV64 Only)

Syntax:

```
SLLI32 Rd, Rs1, imm5u[4:0]
```

Purpose :

Do 32-bit element logical left shift operations simultaneously. The shift amount is an immediate value.

Description :

The 32-bit elements in Rs1 are left-shifted logically. The shifted out bits are filled with zero and the shift amount is specified by the imm5u[4:0] constant. And the results are written to Rd.

Operations:

```
sa = imm5u[4:0];
Rd.W[x] = Rs1.W[x] << sa;
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__RV_SRAI32(a, b)

SRAI32 (SIMD 32-bit Shift Right Arithmetic Immediate)

Type: DSP (RV64 Only)

Syntax:

```
SRAI32 Rd, Rs1, imm5u
SRAI32.u Rd, Rs1, imm5u
```

Purpose :

Do 32-bit elements arithmetic right shift operations simultaneously. The shift amount is an immediate value. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 32-bit data elements in Rs1 are right-shifted arithmetically, that is, the shifted out bits are filled with the sign-bit of the 32-bit data elements. The shift amount is specified by the imm5u constant. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 32-bit data to calculate the final results. And the results are written to Rd.

Operations:

```
sa = imm5u[4:0];
  if (sa > 0) {
  if (`.u` form) { // SRAI32.u
    res[31:-1] = SE33(Rs1.W[x][31:sa-1]) + 1;
    Rd.W[x] = res[31:0];
  else { // SRAI32
    Rd.W[x] = SE32(Rs1.W[x][31:sa]);
  }
} else {
  Rd = Rs1;
}
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__RV_SRAI32_U(a, b)

SRAI32.u (SIMD 32-bit Rounding Shift Right Arithmetic Immediate)

Type: DSP (RV64 Only)

Syntax:

```
SRAI32 Rd, Rs1, imm5u
SRAI32.u Rd, Rs1, imm5u
```

Purpose :

Do 32-bit elements arithmetic right shift operations simultaneously. The shift amount is an immediate value. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 32-bit data elements in Rs1 are right-shifted arithmetically, that is, the shifted out bits are filled with the sign-bit of the 32-bit data elements. The shift amount is specified by the imm5u constant. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 32-bit data to calculate the final results. And the results are written to Rd.

Operations:

```
sa = imm5u[4:0];
  if (sa > 0) {
  if (`.u` form) { // SRAI32.u
    res[31:-1] = SE33(Rs1.W[x][31:sa-1]) + 1;
    Rd.W[x] = res[31:0];
  else { // SRAI32
    Rd.W[x] = SE32(Rs1.W[x][31:sa]);
  }
} else {
  Rd = Rs1;
}
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__RV_SRLI32(a, b)

SRLI32 (SIMD 32-bit Shift Right Logical Immediate)

Type: SIMD (RV64 Only)

Syntax:

```
SRLI32 Rd, Rs1, imm5u
SRLI32.u Rd, Rs1, imm5u
```

Purpose :

Do 32-bit elements logical right shift operations simultaneously. The shift amount is an immediate value. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 32-bit data elements in Rs1 are right-shifted logically, that is, the shifted out bits are filled with zero. The shift amount is specified by the imm5u constant. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 32-bit data to calculate the final results. And the results are written to Rd.

Operations:

```
sa = imm5u[4:0];
if (sa > 0) {
  if (`.u` form) { // SRLI32.u
    res[31:-1] = ZE33(Rs1.W[x][31:sa-1]) + 1;
    Rd.W[x] = res[31:0];
  else { // SRLI32
    Rd.W[x] = ZE32(Rs1.W[x][31:sa]);
  }
} else {
  Rd = Rs1;
}
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__RV_SRLI32_U(a, b)

SRLI32.u (SIMD 32-bit Rounding Shift Right Logical Immediate)

Type: SIMD (RV64 Only)

Syntax:

```
SRLI32 Rd, Rs1, imm5u
SRLI32.u Rd, Rs1, imm5u
```

Purpose :

Do 32-bit elements logical right shift operations simultaneously. The shift amount is an immediate value. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 32-bit data elements in Rs1 are right-shifted logically, that is, the shifted out bits are filled with zero. The shift amount is specified by the imm5u constant. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 32-bit data to calculate the final results. And the results are written to Rd.

Operations:

```
sa = imm5u[4:0];
if (sa > 0) {
  if (`.u` form) { // SRLI32.u
    res[31:-1] = ZE33(Rs1.W[x][31:sa-1]) + 1;
    Rd.W[x] = res[31:0];
  else { // SRLI32
    Rd.W[x] = ZE32(Rs1.W[x][31:sa]);
  }
} else {
  Rd = Rs1;
}
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

Functions

__STATIC_FORCEINLINE unsigned long __RV_KSLL32 (unsigned long a, unsigned int b)

KSLL32 (SIMD 32-bit Saturating Shift Left Logical)

Type: SIMD (RV64 Only)

Syntax:

```
KSLL32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit elements logical left shift operations with saturation simultaneously. The shift amount is a variable from a GPR.

Description :

The 32-bit data elements in Rs1 are left-shifted logically. The shifted out bits are filled with zero and the shift amount is specified by the low-order 5-bits of the value in the Rs2 register. Any shifted value greater than 2^31-1 is saturated to 2^31-1. Any shifted value smaller than -2^31 is saturated to -2^31. And the saturated results are written to Rd. If any saturation is performed, set OV bit to 1.

Operations:

```
sa = Rs2[4:0];
if (sa != 0) {
  res[(31+sa):0] = Rs1.W[x] << sa;
  if (res > (2^31)-1) {
    res = 0x7fffffff; OV = 1;
  } else if (res < -2^31) {
    res = 0x80000000; OV = 1;
  }
  Rd.W[x] = res[31:0];
} else {
  Rd = Rs1;
}
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KSLRA32 (unsigned long a, int b)

KSLRA32 (SIMD 32-bit Shift Left Logical with Saturation or Shift Right Arithmetic)

Type: SIMD (RV64 Only)

Syntax:

```
KSLRA32 Rd, Rs1, Rs2
KSLRA32.u Rd, Rs1, Rs2
```

Purpose :

Do 32-bit elements logical left (positive) or arithmetic right (negative) shift operation with Q31 saturation for the left shift. The `.u` form performs additional rounding up operations for the right shift.

Description :

The 32-bit data elements of Rs1 are left-shifted logically or right-shifted arithmetically based on the value of Rs2[5:0]. Rs2[5:0] is in the signed range of [-25, 25-1]. A positive Rs2[5:0] means logical left shift and a negative Rs2[5:0] means arithmetic right shift. The shift amount is the absolute value of Rs2[5:0]. However, the behavior of `Rs2[5:0]==-25 (0x20)` is defined to be equivalent to the behavior of `Rs2[5:0]==-(25-1) (0x21)`. The left-shifted results are saturated to the 32-bit signed integer range of [-2^31, 2^31-1]. For the `.u` form of the instruction, the right-shifted results are added a 1 to the most significant discarded bit position for rounding effect. After the shift, saturation, or rounding, the final results are written to Rd. If any saturation happens, this instruction sets the OV flag. The value of Rs2[31:6] will not affect this instruction.

Operations:

```
if (Rs2[5:0] < 0) {
  sa = -Rs2[5:0];
```

(continues on next page)

(continued from previous page)

```
  sa = (sa == 32)? 31 : sa;
  if (`.u` form) {
    res[31:-1] = SE33(Rs1.W[x][31:sa-1]) + 1;
    Rd.W[x] = res[31:0];
  } else {
    Rd.W[x] = SE32(Rs1.W[x][31:sa]);
  }
} else {
  sa = Rs2[4:0];
  res[(31+sa):0] = Rs1.W[x] <<(logic) sa;
  if (res > (2^31)-1) {
    res[31:0] = 0x7fffffff; OV = 1;
  } else if (res < -2^31) {
    res[31:0] = 0x80000000; OV = 1;
  }
  Rd.W[x] = res[31:0];
}
for RV64: x=1...0
```

Parameters

- `a` – **[in]** unsigned long type of value stored in a
- `b` – **[in]** int type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_KSLRA32_U (unsigned long a, int b)`

KSLRA32.u (SIMD 32-bit Shift Left Logical with Saturation or Rounding Shift Right Arithmetic)

Type: SIMD (RV64 Only)

Syntax:

```
KSLRA32 Rd, Rs1, Rs2
KSLRA32.u Rd, Rs1, Rs2
```

Purpose :

Do 32-bit elements logical left (positive) or arithmetic right (negative) shift operation with Q31 saturation for the left shift. The `.u` form performs additional rounding up operations for the right shift.

Description :

The 32-bit data elements of Rs1 are left-shifted logically or right-shifted arithmetically based on the value of Rs2[5:0]. Rs2[5:0] is in the signed range of [-25, 25-1]. A positive Rs2[5:0] means logical left shift and a negative Rs2[5:0] means arithmetic right shift. The shift amount is the absolute value of Rs2[5:0]. However, the behavior of `Rs2[5:0]==-25 (0x20)` is defined to be equivalent to the behavior of `Rs2[5:0]==-(25-1) (0x21)`. The left-shifted results are saturated to the 32-bit signed integer range of [-2^31, 2^31-1]. For the `.u` form of the instruction, the right-shifted results are added a 1 to the most significant discarded bit position for rounding effect. After the shift, saturation, or rounding, the final results are written to Rd. If any saturation happens, this instruction sets the OV flag. The value of Rs2[31:6] will not affect this instruction.

Operations:

```
if (Rs2[5:0] < 0) {
  sa = -Rs2[5:0];
  sa = (sa == 32)? 31 : sa;
  if (`.u` form) {
    res[31:-1] = SE33(Rs1.W[x][31:sa-1]) + 1;
    Rd.W[x] = res[31:0];
  } else {
    Rd.W[x] = SE32(Rs1.W[x][31:sa]);
  }
} else {
  sa = Rs2[4:0];
  res[(31+sa):0] = Rs1.W[x] <<(logic) sa;
  if (res > (2^31)-1) {
    res[31:0] = 0x7fffffff; OV = 1;
  } else if (res < -2^31) {
    res[31:0] = 0x80000000; OV = 1;
  }
  Rd.W[x] = res[31:0];
}
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SLL32 (unsigned long a, unsigned int b)

SLL32 (SIMD 32-bit Shift Left Logical)

Type: SIMD (RV64 Only)

Syntax:

```
SLL32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit elements logical left shift operations simultaneously. The shift amount is a variable from a GPR.

Description :

The 32-bit elements in Rs1 are left-shifted logically. And the results are written to Rd. The shifted out bits are filled with zero and the shift amount is specified by the low-order 5-bits of the value in the Rs2 register.

Operations:

```
sa = Rs2[4:0];
Rd.W[x] = Rs1.W[x] << sa;
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SRA32 (unsigned long a, unsigned int b)

SRA32 (SIMD 32-bit Shift Right Arithmetic)

Type: SIMD (RV64 Only)

Syntax:

```
SRA32 Rd, Rs1, Rs2
SRA32.u Rd, Rs1, Rs2
```

Purpose :

Do 32-bit element arithmetic right shift operations simultaneously. The shift amount is a variable from a GPR. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 32-bit data elements in Rs1 are right-shifted arithmetically, that is, the shifted out bits are filled with the sign-bit of the data elements. The shift amount is specified by the low-order 5-bits of the value in the Rs2 register. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 32-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = Rs2[4:0];
if (sa > 0) {
  if (`.u` form) { // SRA32.u
    res[31:-1] = SE33(Rs1.W[x][31:sa-1]) + 1;
    Rd.W[x] = res[31:0];
  else { // SRA32
    Rd.W[x] = SE32(Rs1.W[x][31:sa])
  }
} else {
  Rd = Rs1;
}
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SRA32_U (unsigned long a, unsigned int b)

SRA32.u (SIMD 32-bit Rounding Shift Right Arithmetic)

Type: SIMD (RV64 Only)

Syntax:

```
SRA32 Rd, Rs1, Rs2
SRA32.u Rd, Rs1, Rs2
```

Purpose :

Do 32-bit element arithmetic right shift operations simultaneously. The shift amount is a variable from a GPR. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 32-bit data elements in Rs1 are right-shifted arithmetically, that is, the shifted out bits are filled with the sign-bit of the data elements. The shift amount is specified by the low-order 5-bits of the value in the Rs2 register. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 32-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = Rs2[4:0];
if (sa > 0) {
  if (`.u` form) { // SRA32.u
    res[31:-1] = SE33(Rs1.W[x][31:sa-1]) + 1;
    Rd.W[x] = res[31:0];
  else { // SRA32
    Rd.W[x] = SE32(Rs1.W[x][31:sa])
  }
} else {
  Rd = Rs1;
}
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_SRL32 (unsigned long a, unsigned int b)`

SRL32 (SIMD 32-bit Shift Right Logical)

Type: SIMD (RV64 Only)

Syntax:

```
SRL32 Rd, Rs1, Rs2
SRL32.u Rd, Rs1, Rs2
```

Purpose :

Do 32-bit element logical right shift operations simultaneously. The shift amount is a variable from a GPR. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 32-bit data elements in Rs1 are right-shifted logically, that is, the shifted out bits are filled with zero. The shift amount is specified by the low-order 5-bits of the value in the Rs2 register. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 32-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = Rs2[4:0];
if (sa > 0) {
  if (`.u` form) { // SRA32.u
    res[31:-1] = ZE33(Rs1.W[x][31:sa-1]) + 1;
    Rd.W[x] = res[31:0];
  else { // SRA32
    Rd.W[x] = ZE32(Rs1.W[x][31:sa])
  }
} else {
  Rd = Rs1;
}
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SRL32_U (unsigned long a, unsigned int b)

SRL32.u (SIMD 32-bit Rounding Shift Right Logical)

Type: SIMD (RV64 Only)

Syntax:

```
SRL32 Rd, Rs1, Rs2
SRL32.u Rd, Rs1, Rs2
```

Purpose :

Do 32-bit element logical right shift operations simultaneously. The shift amount is a variable from a GPR. The `.u` form performs additional rounding up operations on the shifted results.

Description :

The 32-bit data elements in Rs1 are right-shifted logically, that is, the shifted out bits are filled with zero. The shift amount is specified by the low-order 5-bits of the value in the Rs2 register. For the rounding operation of the `.u` form, a value of 1 is added to the most significant discarded bit of each 32-bit data element to calculate the final results. And the results are written to Rd.

Operations:

```
sa = Rs2[4:0];
if (sa > 0) {
  if (`.u` form) { // SRA32.u
    res[31:-1] = ZE33(Rs1.W[x][31:sa-1]) + 1;
    Rd.W[x] = res[31:0];
  else { // SRA32
    Rd.W[x] = ZE32(Rs1.W[x][31:sa])
  }
} else {
  Rd = Rs1;
}
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned int type of value stored in b

Returns value stored in unsigned long type

(RV64 Only) SIMD 32-bit Miscellaneous Instructions

__STATIC_FORCEINLINE unsigned long __RV_KABS32 (unsigned long a)

__STATIC_FORCEINLINE unsigned long __RV_SMAX32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_SMIN32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UMAX32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_UMIN32 (unsigned long a, unsigned long b)

group **NMSIS_Core_DSP_Intrinsic_RV64_SIMD_32B_MISC**

(RV64 Only) SIMD 32-bit Miscellaneous Instructions

there are 5 (RV64 Only) SIMD 32-bit Miscellaneous Instructions

Functions

__STATIC_FORCEINLINE unsigned long __RV_KABS32 (unsigned long a)

KABS32 (Scalar 32-bit Absolute Value with Saturation)

Type: DSP (RV64 Only) 24 20 19 15 14 12 11 7 KABS32 10010 Rs1 000 Rd 6 0 GE80B 1111111

Syntax:

```
KABS32 Rd, Rs1
```

Purpose :

Get the absolute value of signed 32-bit integer elements in a general register.

Description :

This instruction calculates the absolute value of signed 32-bit integer elements stored in Rs1. The results are written to Rd. This instruction with the minimum negative integer input of 0x80000000 will produce a saturated output of maximum positive integer of 0x7fffffff and the OV flag will be set to 1.

Operations:

```
if (Rs1.W[x] >= 0) {
  res[x] = Rs1.W[x];
} else {
  If (Rs1.W[x] == 0x80000000) {
```

(continues on next page)

(continued from previous page)

```
    res[x] = 0x7fffffff;
    OV = 1;
  } else {
    res[x] = -Rs1.W[x];
  }
}
Rd.W[x] = res[x];
for RV64: x=1...0
```

Parameters **a** – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SMAX32 (unsigned long a, unsigned long b)

SMAX32 (SIMD 32-bit Signed Maximum)

Type: SIMD (RV64 Only)

Syntax:

```
SMAX32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit signed integer elements finding maximum operations simultaneously.

Description :

This instruction compares the 32-bit signed integer elements in Rs1 with the 32-bit signed integer elements in Rs2 and selects the numbers that is greater than the other one. The selected results are written to Rd.

Operations:

```
Rd.W[x] = (Rs1.W[x] > Rs2.W[x])? Rs1.W[x] : Rs2.W[x];
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_SMIN32 (unsigned long a, unsigned long b)

SMIN32 (SIMD 32-bit Signed Minimum)

Type: SIMD (RV64 Only)

Syntax:

```
SMIN32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit signed integer elements finding minimum operations simultaneously.

Description :

This instruction compares the 32-bit signed integer elements in Rs1 with the 32-bit signed integer elements in Rs2 and selects the numbers that is less than the other one. The selected results are written to Rd.

Operations:

```
Rd.W[x] = (Rs1.W[x] < Rs2.W[x])? Rs1.W[x] : Rs2.W[x];
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_UMAX32 (unsigned long a, unsigned long b)`

UMAX32 (SIMD 32-bit Unsigned Maximum)

Type: SIMD (RV64 Only)

Syntax:

```
UMAX32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit unsigned integer elements finding maximum operations simultaneously.

Description :

This instruction compares the 32-bit unsigned integer elements in Rs1 with the 32-bit unsigned integer elements in Rs2 and selects the numbers that is greater than the other one. The selected results are written to Rd.

Operations:

```
Rd.W[x] = (Rs1.W[x] u> Rs2.W[x])? Rs1.W[x] : Rs2.W[x];
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

`__STATIC_FORCEINLINE unsigned long __RV_UMIN32 (unsigned long a, unsigned long b)`

UMIN32 (SIMD 32-bit Unsigned Minimum)

Type: SIMD (RV64 Only)

Syntax:

```
UMIN32 Rd, Rs1, Rs2
```

Purpose :

Do 32-bit unsigned integer elements finding minimum operations simultaneously.

Description :

This instruction compares the 32-bit unsigned integer elements in Rs1 with the 32-bit unsigned integer elements in Rs2 and selects the numbers that is less than the other one. The selected results are written to Rd.

Operations:

```
Rd.W[x] = (Rs1.W[x] <u Rs2.W[x])? Rs1.W[x] : Rs2.W[x];
for RV64: x=1...0
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

(RV64 Only) SIMD Q15 Saturating Multiply Instructions

__STATIC_FORCEINLINE unsigned long __RV_KDMBB16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KDMBT16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KDMTT16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KDMABB16 (unsigned long t, unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KDMABT16 (unsigned long t, unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KDMATT16 (unsigned long t, unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KHMBB16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KHMBT16 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_KHMTT16 (unsigned long a, unsigned long b)

group **NMSIS_Core_DSP_Intrinsic_RV64_SIMD_Q15_SAT_MULT**

(RV64 Only) SIMD Q15 Saturating Multiply Instructions

there are 9 (RV64 Only) SIMD Q15 saturating Multiply Instructions

Functions

__STATIC_FORCEINLINE unsigned long __RV_KDMBB16 (unsigned long a, unsigned long b)

KDMBB16 (SIMD Signed Saturating Double Multiply B16 x B16)

Type: SIMD (RV64 only)

Syntax:

```
KDMxy16 Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 integer contents of two 16-bit data in the corresponding portion of the 32-bit chunks in registers and then double and saturate the Q31 results into the 32-bit chunks in the destination register. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the 32-bit portions in Rs1 with the top or bottom 16-bit Q15 content of the 32-bit portions in Rs2. The Q30 results are then doubled and saturated into Q31 values. The Q31 values are then written into the 32-bit chunks in Rd. When both the two Q15 inputs are 0x8000, saturation will happen. The result will be saturated to 0x7FFFFFFF and the overflow flag OV will be set.

Operations:

```
// KDMBB16: (x,y,z)=(0,0,0),(2,2,1)
// KDMBT16: (x,y,z)=(0,1,0),(2,3,1)
// KDMTT16: (x,y,z)=(1,1,0),(3,3,1)
aop[z] = Rs1.H[x]; bop[z] = Rs2.H[y];
If (0x8000 != aop[z] | 0x8000 != bop[z]) {
  Mresult[z] = aop[z] * bop[z];
  resQ31[z] = Mresult[z] << 1;
} else {
  resQ31[z] = 0x7FFFFFFF;
  OV = 1;
}
Rd.W[z] = resQ31[z];
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KDMBT16 (unsigned long a, unsigned long b)

KDMBT16 (SIMD Signed Saturating Double Multiply B16 x T16)

Type: SIMD (RV64 only)

Syntax:

```
KDMxy16 Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 integer contents of two 16-bit data in the corresponding portion of the 32-bit chunks in registers and then double and saturate the Q31 results into the 32-bit chunks in the destination register. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the 32-bit portions in Rs1 with the top or bottom 16-bit Q15 content of the 32-bit portions in Rs2. The Q30 results are then doubled and saturated into Q31 values. The Q31 values are then written into the 32-bit chunks in Rd. When both the two Q15 inputs are 0x8000, saturation will happen. The result will be saturated to 0x7FFFFFFF and the overflow flag OV will be set.

Operations:

```
// KDMBB16: (x,y,z)=(0,0,0),(2,2,1)
// KDMBT16: (x,y,z)=(0,1,0),(2,3,1)
// KDMTT16: (x,y,z)=(1,1,0),(3,3,1)
aop[z] = Rs1.H[x]; bop[z] = Rs2.H[y];
If (0x8000 != aop[z] | 0x8000 != bop[z]) {
  Mresult[z] = aop[z] * bop[z];
  resQ31[z] = Mresult[z] << 1;
} else {
  resQ31[z] = 0x7FFFFFFF;
  OV = 1;
}
Rd.W[z] = resQ31[z];
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KDMTT16 (unsigned long a, unsigned long b)

KDMTT16 (SIMD Signed Saturating Double Multiply T16 x T16)

Type: SIMD (RV64 only)

Syntax:

```
KDMxy16 Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 integer contents of two 16-bit data in the corresponding portion of the 32-bit chunks in registers and then double and saturate the Q31 results into the 32-bit chunks in the destination register. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the 32-bit portions in Rs1 with the top or bottom 16-bit Q15 content of the 32-bit portions in Rs2. The Q30 results are then doubled and saturated into Q31 values. The Q31 values are then written into the 32-bit chunks in Rd. When both the two Q15 inputs are 0x8000, saturation will happen. The result will be saturated to 0x7FFFFFFF and the overflow flag OV will be set.

Operations:

```
// KDMBB16: (x,y,z)=(0,0,0),(2,2,1)
// KDMBT16: (x,y,z)=(0,1,0),(2,3,1)
// KDMTT16: (x,y,z)=(1,1,0),(3,3,1)
aop[z] = Rs1.H[x]; bop[z] = Rs2.H[y];
If (0x8000 != aop[z] | 0x8000 != bop[z]) {
  Mresult[z] = aop[z] * bop[z];
  resQ31[z] = Mresult[z] << 1;
} else {
  resQ31[z] = 0x7FFFFFFF;
  OV = 1;
}
Rd.W[z] = resQ31[z];
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KDMABB16 (unsigned long t, unsigned long a, unsigned long b)

KDMABB16 (SIMD Signed Saturating Double Multiply Addition B16 x B16)

Type: SIMD (RV64 only)

Syntax:

```
KDMAxy16 Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 integer contents of two 16-bit data in the corresponding portion of the 32-bit chunks in registers and then double and saturate the Q31 results, add the results with the values of the corresponding 32-bit chunks from the destination register and write the saturated addition results back into the corresponding 32-bit chunks of the destination register. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the 32-bit portions in Rs1 with the top or bottom 16-bit Q15 content of the corresponding 32-bit portions in Rs2. The Q30 results are then doubled and saturated into Q31 values. The Q31 values are then added with the content of the corresponding 32-bit portions of Rd. If the addition results are beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), they are saturated to the range and the OV flag is set to 1. The results after saturation are written back to Rd. When both the two Q15 inputs are 0x8000, saturation will happen and the overflow flag OV will be set.

Operations:

```
// KDMABB16: (x,y,z)=(0,0,0),(2,2,1)
// KDMABT16: (x,y,z)=(0,1,0),(2,3,1)
// KDMATT16: (x,y,z)=(1,1,0),(3,3,1)
aop[z] = Rs1.H[x]; bop[z] = Rs2.H[y];
If (0x8000 != aop[z] | 0x8000 != bop[z]) {
  Mresult[z] = aop[z] * bop[z];
  resQ31[z] = Mresult[z] << 1;
```

(continues on next page)

(continued from previous page)

```
} else {
  resQ31[z] = 0x7FFFFFFF;
  OV = 1;
}
resadd[z] = Rd.W[z] + resQ31[z];
if (resadd[z] > (2^31)-1) {
  resadd[z] = (2^31)-1;
  OV = 1;
} else if (resadd[z] < -2^31) {
  resadd[z] = -2^31;
  OV = 1;
}
Rd.W[z] = resadd[z];
```

Parameters

- **t** – **[in]** unsigned long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KDMABT16 (unsigned long t, unsigned long a, unsigned long b)

KDMABT16 (SIMD Signed Saturating Double Multiply Addition B16 x T16)

Type: SIMD (RV64 only)

Syntax:

```
KDMAxy16 Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 integer contents of two 16-bit data in the corresponding portion of the 32-bit chunks in registers and then double and saturate the Q31 results, add the results with the values of the corresponding 32-bit chunks from the destination register and write the saturated addition results back into the corresponding 32-bit chunks of the destination register. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the 32-bit portions in Rs1 with the top or bottom 16-bit Q15 content of the corresponding 32-bit portions in Rs2. The Q30 results are then doubled and saturated into Q31 values. The Q31 values are then added with the content of the corresponding 32-bit portions of Rd. If the addition results are beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), they are saturated to the range and the OV flag is set to 1. The results after saturation are written back to Rd. When both the two Q15 inputs are 0x8000, saturation will happen and the overflow flag OV will be set.

Operations:

```
// KDMABB16: (x,y,z)=(0,0,0),(2,2,1)
// KDMABT16: (x,y,z)=(0,1,0),(2,3,1)
// KDMATT16: (x,y,z)=(1,1,0),(3,3,1)
```

(continues on next page)

(continued from previous page)

```
aop[z] = Rs1.H[x]; bop[z] = Rs2.H[y];
If (0x8000 != aop[z] | 0x8000 != bop[z]) {
  Mresult[z] = aop[z] * bop[z];
  resQ31[z] = Mresult[z] << 1;
} else {
  resQ31[z] = 0x7FFFFFFF;
  OV = 1;
}
resadd[z] = Rd.W[z] + resQ31[z];
if (resadd[z] > (2^31)-1) {
  resadd[z] = (2^31)-1;
  OV = 1;
} else if (resadd[z] < -2^31) {
  resadd[z] = -2^31;
  OV = 1;
}
Rd.W[z] = resadd[z];
```

Parameters

- **t** – **[in]** unsigned long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KDMATT16 (unsigned long t, unsigned long a, unsigned long b)

KDMATT16 (SIMD Signed Saturating Double Multiply Addition T16 x T16)

Type: SIMD (RV64 only)

Syntax:

```
KDMAxy16 Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 integer contents of two 16-bit data in the corresponding portion of the 32-bit chunks in registers and then double and saturate the Q31 results, add the results with the values of the corresponding 32-bit chunks from the destination register and write the saturated addition results back into the corresponding 32-bit chunks of the destination register. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the 32-bit portions in Rs1 with the top or bottom 16-bit Q15 content of the corresponding 32-bit portions in Rs2. The Q30 results are then doubled and saturated into Q31 values. The Q31 values are then added with the content of the corresponding 32-bit portions of Rd. If the addition results are beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), they are saturated to the range and the OV flag is set to 1. The results after saturation are written back to Rd. When both the two Q15 inputs are 0x8000, saturation will happen and the overflow flag OV will be set.

Operations:

```
// KDMABB16: (x,y,z)=(0,0,0),(2,2,1)
// KDMABT16: (x,y,z)=(0,1,0),(2,3,1)
// KDMATT16: (x,y,z)=(1,1,0),(3,3,1)
aop[z] = Rs1.H[x]; bop[z] = Rs2.H[y];
If (0x8000 != aop[z] | 0x8000 != bop[z]) {
  Mresult[z] = aop[z] * bop[z];
  resQ31[z] = Mresult[z] << 1;
} else {
  resQ31[z] = 0x7FFFFFFF;
  OV = 1;
}
resadd[z] = Rd.W[z] + resQ31[z];
if (resadd[z] > (2^31)-1) {
  resadd[z] = (2^31)-1;
  OV = 1;
} else if (resadd[z] < -2^31) {
  resadd[z] = -2^31;
  OV = 1;
}
Rd.W[z] = resadd[z];
```

Parameters

- **t** – **[in]** unsigned long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KHMBB16 (unsigned long a, unsigned long b)

KHMBB16 (SIMD Signed Saturating Half Multiply B16 x B16)

Type: SIMD (RV64 Only)

Syntax:

```
KHMxy16 Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 integer contents of two 16-bit data in the corresponding portion of the 32-bit chunks in registers and then right-shift 15 bits to turn the Q30 results into Q15 numbers again and saturate the Q15 results into the destination register. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the 32-bit portions in Rs1 with the top or bottom 16-bit Q15 content of the 32-bit portion in Rs2. The Q30 results are then right-shifted 15- bits and saturated into Q15 values. The 32-bit Q15 values are then written into the 32-bit chunks in Rd. When both the two Q15 inputs are 0x8000, saturation will happen. The result will be saturated to 0x7FFF and the overflow flag OV will be set.

Operations:

```
// KHMBB16: (x,y,z)=(0,0,0),(2,2,1)
// KHMBT16: (x,y,z)=(0,1,0),(2,3,1)
// KHMTT16: (x,y,z)=(1,1,0),(3,3,1)
aop = Rs1.H[x]; bop = Rs2.H[y];
If (0x8000 != aop | 0x8000 != bop) {
  Mresult[31:0] = aop * bop;
  res[15:0] = Mresult[30:15];
} else {
  res[15:0] = 0x7FFF;
  OV = 1;
}
Rd.W[z] = SE32(res[15:0]);
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KHMBT16 (unsigned long a, unsigned long b)

KHMBT16 (SIMD Signed Saturating Half Multiply B16 x T16)

Type: SIMD (RV64 Only)

Syntax:

```
KHMxy16 Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 integer contents of two 16-bit data in the corresponding portion of the 32-bit chunks in registers and then right-shift 15 bits to turn the Q30 results into Q15 numbers again and saturate the Q15 results into the destination register. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the 32-bit portions in Rs1 with the top or bottom 16-bit Q15 content of the 32-bit portion in Rs2. The Q30 results are then right-shifted 15- bits and saturated into Q15 values. The 32-bit Q15 values are then written into the 32-bit chunks in Rd. When both the two Q15 inputs are 0x8000, saturation will happen. The result will be saturated to 0x7FFF and the overflow flag OV will be set.

Operations:

```
// KHMBB16: (x,y,z)=(0,0,0),(2,2,1)
// KHMBT16: (x,y,z)=(0,1,0),(2,3,1)
// KHMTT16: (x,y,z)=(1,1,0),(3,3,1)
aop = Rs1.H[x]; bop = Rs2.H[y];
If (0x8000 != aop | 0x8000 != bop) {
  Mresult[31:0] = aop * bop;
  res[15:0] = Mresult[30:15];
} else {
  res[15:0] = 0x7FFF;
  OV = 1;
```

(continues on next page)

(continued from previous page)

```
}
Rd.W[z] = SE32(res[15:0]);
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_KHMTT16 (unsigned long a, unsigned long b)

KHMTT16 (SIMD Signed Saturating Half Multiply T16 x T16)

Type: SIMD (RV64 Only)

Syntax:

```
KHMxy16 Rd, Rs1, Rs2 (xy = BB, BT, TT)
```

Purpose :

Multiply the signed Q15 integer contents of two 16-bit data in the corresponding portion of the 32-bit chunks in registers and then right-shift 15 bits to turn the Q30 results into Q15 numbers again and saturate the Q15 results into the destination register. If saturation happens, an overflow flag OV will be set.

Description :

Multiply the top or bottom 16-bit Q15 content of the 32-bit portions in Rs1 with the top or bottom 16-bit Q15 content of the 32-bit portion in Rs2. The Q30 results are then right-shifted 15- bits and saturated into Q15 values. The 32-bit Q15 values are then written into the 32-bit chunks in Rd. When both the two Q15 inputs are 0x8000, saturation will happen. The result will be saturated to 0x7FFF and the overflow flag OV will be set.

Operations:

```
// KHMBB16: (x,y,z)=(0,0,0),(2,2,1)
// KHMBT16: (x,y,z)=(0,1,0),(2,3,1)
// KHMTT16: (x,y,z)=(1,1,0),(3,3,1)
aop = Rs1.H[x]; bop = Rs2.H[y];
If (0x8000 != aop | 0x8000 != bop) {
  Mresult[31:0] = aop * bop;
  res[15:0] = Mresult[30:15];
} else {
  res[15:0] = 0x7FFF;
  OV = 1;
}
Rd.W[z] = SE32(res[15:0]);
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

(RV64 Only) 32-bit Multiply Instructions

__STATIC_FORCEINLINE long __RV_SMBB32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE long __RV_SMBT32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE long __RV_SMTT32 (unsigned long a, unsigned long b)

group **NMSIS_Core_DSP_Intrinsic_RV64_32B_MULT**

(RV64 Only) 32-bit Multiply Instructions

there is 3 RV64 Only) 32-bit Multiply Instructions

Functions

__STATIC_FORCEINLINE long __RV_SMBB32 (unsigned long a, unsigned long b)

SMBB32 (Signed Multiply Bottom Word & Bottom Word)

Type: DSP (RV64 Only)

Syntax:

```
SMBB32 Rd, Rs1, Rs2
SMBT32 Rd, Rs1, Rs2
SMTT32 Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit element of a register with the signed 32-bit element of another register and write the 64-bit result to a third register.

- SMBB32: bottom*bottom
- SMBT32: bottom*top
- SMTT32: top*top

Description :

For the SMBB32 instruction, it multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2. It is actually an alias of MULSR64 instruction. For the SMBT32 instruction, it multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2. For the SMTT32 instruction, it multiplies the top 32-bit element of Rs1 with the top 32-bit element of Rs2. The 64-bit multiplication result is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rs1.W[0] * Rs2.W[0]; // SMBB32 res = Rs1.W[0] * Rs2.w[1]; // SMBT32 res =␣
↪Rs1.W[1] * Rs2.W[1];
// SMTT32 Rd = res;
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a

- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_SMBT32 (unsigned long a, unsigned long b)

SMBT32 (Signed Multiply Bottom Word & Top Word)

Type: DSP (RV64 Only)

Syntax:

```
SMBB32 Rd, Rs1, Rs2
SMBT32 Rd, Rs1, Rs2
SMTT32 Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit element of a register with the signed 32-bit element of another register and write the 64-bit result to a third register.

- SMBB32: bottom*bottom
- SMBT32: bottom*top
- SMTT32: top*top

Description :

For the SMBB32 instruction, it multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2. It is actually an alias of MULSR64 instruction. For the SMBT32 instruction, it multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2. For the SMTT32 instruction, it multiplies the top 32-bit element of Rs1 with the top 32-bit element of Rs2. The 64-bit multiplication result is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rs1.W[0] * Rs2.W[0]; // SMBB32 res = Rs1.W[0] * Rs2.w[1]; // SMBT32 res =␣
↪Rs1.W[1] * Rs2.W[1];
// SMTT32 Rd = res;
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_SMTT32 (unsigned long a, unsigned long b)

SMTT32 (Signed Multiply Top Word & Top Word)

Type: DSP (RV64 Only)

Syntax:

```
SMBB32 Rd, Rs1, Rs2
SMBT32 Rd, Rs1, Rs2
SMTT32 Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit element of a register with the signed 32-bit element of another register and write the 64-bit result to a third register.

- SMBB32: bottom*bottom
- SMBT32: bottom*top
- SMTT32: top*top

Description :

For the `SMBB32` instruction, it multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2. It is actually an alias of `MULSR64` instruction. For the `SMBT32` instruction, it multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2. For the `SMTT32` instruction, it multiplies the top 32-bit element of Rs1 with the top 32-bit element of Rs2. The 64-bit multiplication result is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rs1.W[0] * Rs2.W[0]; // SMBB32 res = Rs1.W[0] * Rs2.w[1]; // SMBT32 res =
↪Rs1.W[1] * Rs2.W[1];
// SMTT32 Rd = res;
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

(RV64 Only) 32-bit Multiply & Add Instructions

__STATIC_FORCEINLINE long __RV_KMABB32 (long t, unsigned long a, unsigned long b)

__STATIC_FORCEINLINE long __RV_KMABT32 (long t, unsigned long a, unsigned long b)

__STATIC_FORCEINLINE long __RV_KMATT32 (long t, unsigned long a, unsigned long b)

group **NMSIS_Core_DSP_Intrinsic_RV64_32B_MULT_ADD**

(RV64 Only) 32-bit Multiply & Add Instructions

there are 3 (RV64 Only) 32-bit Multiply & Add Instructions

Functions

`__STATIC_FORCEINLINE long __RV_KMABB32 (long t, unsigned long a, unsigned long b)`

KMABB32 (Saturating Signed Multiply Bottom Words & Add)

Type: DSP (RV64 Only)

Syntax:

```
KMABB32 Rd, Rs1, Rs2
KMABT32 Rd, Rs1, Rs2
KMATT32 Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit element in a register with the 32-bit element in another register and add the result to the content of 64-bit data in the third register. The addition result may be saturated and is written to the third register.

- KMABB32: rd + bottom*bottom
- KMABT32: rd + bottom*top
- KMATT32: rd + top*top

Description :

For the `KMABB32` instruction, it multiplies the bottom 32-bit element in Rs1 with the bottom 32-bit element in Rs2. For the `KMABT32` instruction, it multiplies the bottom 32-bit element in Rs1 with the top 32-bit element in Rs2. For the `KMATT32` instruction, it multiplies the top 32-bit element in Rs1 with the top 32-bit element in Rs2. The multiplication result is added to the content of 64-bit data in Rd. If the addition result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The result after saturation is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rd + (Rs1.W[0] * Rs2.W[0]); // KMABB32
 res = Rd + (Rs1.W[0] * Rs2.W[1]); // KMABT32
 res = Rd + (Rs1.W[1] * Rs2.W[1]); // KMATT32
 if (res > (2^63)-1) {
   res = (2^63)-1;
   OV = 1;
 } else if (res < -2^63) {
   res = -2^63;
   OV = 1;
 }
 Rd = res;
*Exceptions:* None
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_KMABT32 (long t, unsigned long a, unsigned long b)`

KMABT32 (Saturating Signed Multiply Bottom & Top Words & Add)

Type: DSP (RV64 Only)

Syntax:

```
KMABB32 Rd, Rs1, Rs2
KMABT32 Rd, Rs1, Rs2
KMATT32 Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit element in a register with the 32-bit element in another register and add the result to the content of 64-bit data in the third register. The addition result may be saturated and is written to the third register.

- KMABB32: rd + bottom*bottom
- KMABT32: rd + bottom*top
- KMATT32: rd + top*top

Description :

For the `KMABB32` instruction, it multiplies the bottom 32-bit element in Rs1 with the bottom 32-bit element in Rs2. For the `KMABT32` instruction, it multiplies the bottom 32-bit element in Rs1 with the top 32-bit element in Rs2. For the `KMATT32` instruction, it multiplies the top 32-bit element in Rs1 with the top 32-bit element in Rs2. The multiplication result is added to the content of 64-bit data in Rd. If the addition result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The result after saturation is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rd + (Rs1.W[0] * Rs2.W[0]); // KMABB32
 res = Rd + (Rs1.W[0] * Rs2.W[1]); // KMABT32
 res = Rd + (Rs1.W[1] * Rs2.W[1]); // KMATT32
 if (res > (2^63)-1) {
   res = (2^63)-1;
   OV = 1;
 } else if (res < -2^63) {
   res = -2^63;
   OV = 1;
 }
 Rd = res;
*Exceptions:* None
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_KMATT32 (long t, unsigned long a, unsigned long b)`

KMATT32 (Saturating Signed Multiply Top Words & Add)

Type: DSP (RV64 Only)

Syntax:

```
KMABB32 Rd, Rs1, Rs2
KMABT32 Rd, Rs1, Rs2
KMATT32 Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit element in a register with the 32-bit element in another register and add the result to the content of 64-bit data in the third register. The addition result may be saturated and is written to the third register.

- KMABB32: rd + bottom*bottom
- KMABT32: rd + bottom*top
- KMATT32: rd + top*top

Description :

For the `KMABB32` instruction, it multiplies the bottom 32-bit element in Rs1 with the bottom 32-bit element in Rs2. For the `KMABT32` instruction, it multiplies the bottom 32-bit element in Rs1 with the top 32-bit element in Rs2. For the `KMATT32` instruction, it multiplies the top 32-bit element in Rs1 with the top 32-bit element in Rs2. The multiplication result is added to the content of 64-bit data in Rd. If the addition result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The result after saturation is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rd + (Rs1.W[0] * Rs2.W[0]); // KMABB32
 res = Rd + (Rs1.W[0] * Rs2.W[1]); // KMABT32
 res = Rd + (Rs1.W[1] * Rs2.W[1]); // KMATT32
 if (res > (2^63)-1) {
   res = (2^63)-1;
   OV = 1;
 } else if (res < -2^63) {
   res = -2^63;
   OV = 1;
 }
 Rd = res;
*Exceptions:* None
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

(RV64 Only) 32-bit Parallel Multiply & Add Instructions

`__STATIC_FORCEINLINE long __RV_KMADA32 (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMAXDA32 (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMDA32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMXDA32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMADS32 (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMADRS32 (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMAXDS32 (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMSDA32 (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_KMSXDA32 (long t, unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_SMDS32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_SMDRS32 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE long __RV_SMXDS32 (unsigned long a, unsigned long b)`

group `NMSIS_Core_DSP_Intrinsic_RV64_32B_PARALLEL_MAC`

(RV64 Only) 32-bit Parallel Multiply & Add Instructions

there are 12 (RV64 Only) 32-bit Parallel Multiply & Add Instructions

Functions

`__STATIC_FORCEINLINE long __RV_KMADA32 (long t, unsigned long a, unsigned long b)`

KMADA32 (Saturating Signed Multiply Two Words and Two Adds)

Type: DSP (RV64 Only)

Syntax:

```
KMADA32 Rd, Rs1, Rs2
KMAXDA32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32-bit multiplications from 32-bit data in two registers; and then adds the two 64-bit results and 64-bit data in a third register together. The addition result may be saturated.

- KMADA32: rd + top*top + bottom*bottom
- KMAXDA32: rd + top*bottom + bottom*top

Description :

For the KMADA32 instruction, it multiplies the bottom 32-bit element in Rs1 with the bottom 32- bit element in Rs2 and then adds the result to the result of multiplying the top 32-bit element in Rs1 with the top 32-bit element in Rs2. It is actually an alias of the KMAR64 instruction. For the KMAXDA32 instruction, it multiplies the top 32-bit element in Rs1 with the bottom 32-bit element in Rs2 and then adds the result to the result of multiplying the bottom 32-bit element in Rs1 with the top 32-bit element in Rs2. The result is added to the content of 64-bit data in Rd. If the addition result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The 64-bit result is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rd + (Rs1.W[1] * Rs2.w[1]) + (Rs1.W[0] * Rs2.W[0]); // KMADA32
res = Rd + (Rs1.W[1] * Rs2.W[0]) + (Rs1.W[0] * Rs2.W[1]); // KMAXDA32
if (res > (2^63)-1) {
  res = (2^63)-1;
  OV = 1;
} else if (res < -2^63) {
  res = -2^63;
  OV = 1;
}
Rd = res;
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMAXDA32 (long t, unsigned long a, unsigned long b)

KMAXDA32 (Saturating Signed Crossed Multiply Two Words and Two Adds)

Type: DSP (RV64 Only)

Syntax:

```
KMADA32 Rd, Rs1, Rs2
KMAXDA32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32-bit multiplications from 32-bit data in two registers; and then adds the two 64-bit results and 64-bit data in a third register together. The addition result may be saturated.

- KMADA32: rd + top*top + bottom*bottom
- KMAXDA32: rd + top*bottom + bottom*top

Description :

For the KMADA32 instruction, it multiplies the bottom 32-bit element in Rs1 with the bottom 32- bit element in Rs2 and then adds the result to the result of multiplying the top 32-bit element in Rs1 with the top 32-bit element in Rs2. It is actually an alias of the KMAR64 instruction. For the KMAXDA32 instruction, it multiplies the top 32-bit element in Rs1 with the bottom 32-bit element in Rs2 and then adds the result to the result of multiplying the bottom 32-bit element in Rs1 with the top 32-bit element in Rs2. The result is added to the content of 64-bit data in Rd. If the addition result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The 64-bit result is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rd + (Rs1.W[1] * Rs2.w[1]) + (Rs1.W[0] * Rs2.W[0]); // KMADA32
res = Rd + (Rs1.W[1] * Rs2.W[0]) + (Rs1.W[0] * Rs2.W[1]); // KMAXDA32
if (res > (2^63)-1) {
  res = (2^63)-1;
  OV = 1;
} else if (res < -2^63) {
  res = -2^63;
  OV = 1;
}
Rd = res;
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMDA32 (unsigned long a, unsigned long b)

KMDA32 (Signed Multiply Two Words and Add)

Type: DSP (RV64 Only)

Syntax:

```
KMDA32 Rd, Rs1, Rs2
KMXDA32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32-bit multiplications from the 32-bit element of two registers; and then adds the two 64-bit results together. The addition result may be saturated.

- KMDA32: top*top + bottom*bottom
- KMXDA32: top*bottom + bottom*top

Description :

For the KMDA32 instruction, it multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2 and then adds the result to the result of multiplying the top 32-bit element of Rs1 with the top 32-bit element of Rs2. For the KMXDA32 instruction, it multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2 and then adds the result to the result of multiplying the top 32-bit element of Rs1 with the bottom 32-bit element of Rs2. The addition result is checked for saturation. If saturation happens, the result is saturated to 2^63-1. The final result is written to Rd. The 32-bit contents are treated as signed integers.

Operations:

```
if ((Rs1 != 0x8000000080000000) or (Rs2 != 0x8000000080000000)) {
  Rd = (Rs1.W[1] * Rs2.W[1]) + (Rs1.W[0] * Rs2.W[0]); // KMDA32
  Rd = (Rs1.W[1] * Rs2.W[0]) + (Rs1.W[0] * Rs2.W[1]); // KMXDA32
} else {
  Rd = 0x7fffffffffffffff;
  OV = 1;
}
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMXDA32 (unsigned long a, unsigned long b)

KMXDA32 (Signed Crossed Multiply Two Words and Add)

Type: DSP (RV64 Only)

Syntax:

```
KMDA32 Rd, Rs1, Rs2
KMXDA32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32-bit multiplications from the 32-bit element of two registers; and then adds the two 64-bit results together. The addition result may be saturated.

- KMDA32: top*top + bottom*bottom
- KMXDA32: top*bottom + bottom*top

Description :

For the `KMDA32` instruction, it multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2 and then adds the result to the result of multiplying the top 32-bit element of Rs1 with the top 32-bit element of Rs2. For the `KMXDA32` instruction, it multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2 and then adds the result to the result of multiplying the top 32-bit element of Rs1 with the bottom 32-bit element of Rs2. The addition result is checked for saturation. If saturation happens, the result is saturated to 2^63-1. The final result is written to Rd. The 32-bit contents are treated as signed integers.

Operations:

```
if ((Rs1 != 0x8000000080000000) or (Rs2 != 0x8000000080000000)) {
  Rd = (Rs1.W[1] * Rs2.W[1]) + (Rs1.W[0] * Rs2.W[0]); // KMDA32
  Rd = (Rs1.W[1] * Rs2.W[0]) + (Rs1.W[0] * Rs2.W[1]); // KMXDA32
} else {
  Rd = 0x7fffffffffffffff;
  OV = 1;
}
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a

- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMADS32 (long t, unsigned long a, unsigned long b)

KMADS32 (Saturating Signed Multiply Two Words & Subtract & Add)

Type: DSP (RV64 Only)

Syntax:

```
KMADS32 Rd, Rs1, Rs2
KMADRS32 Rd, Rs1, Rs2
KMAXDS32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32-bit multiplications from 32-bit elements in two registers; and then perform a subtraction operation between the two 64-bit results. Then add the subtraction result to 64-bit data in a third register. The addition result may be saturated.

- KMADS32: rd + (top*top - bottom*bottom)
- KMADRS32: rd + (bottom*bottom - top*top)
- KMAXDS32: rd + (top*bottom - bottom*top)

Description :

For the `KMADS32` instruction, it multiplies the bottom 32-bit element in Rs1 with the bottom 32-bit element in Rs2 and then subtracts the result from the result of multiplying the top 32-bit element in Rs1 with the top 32-bit element in Rs2. For the `KMADRS32` instruction, it multiplies the top 32-bit element in Rs1 with the top 32-bit element in Rs2 and then subtracts the result from the result of multiplying the bottom 32-bit element in Rs1 with the bottom 32-bit element in Rs2. For the `KMAXDS32` instruction, it multiplies the bottom 32-bit element in Rs1 with the top 32-bit element in Rs2 and then subtracts the result from the result of multiplying the top 32-bit element in Rs1 with the bottom 32-bit element in Rs2. The subtraction result is then added to the content of 64-bit data in Rd. If the addition result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to

a. The 64-bit result after saturation is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rd + (Rs1.W[1] * Rs2.W[1]) - (Rs1.W[0] * Rs2.W[0]); // KMADS32
res = Rd + (Rs1.W[0] * Rs2.W[0]) - (Rs1.W[1] * Rs2.W[1]); // KMADRS32
res = Rd + (Rs1.W[1] * Rs2.W[0]) - (Rs1.W[0] * Rs2.W[1]); // KMAXDS32
if (res > (2^63)-1) {
  res = (2^63)-1;
  OV = 1;
} else if (res < -2^63) {
  res = -2^63;
  OV = 1;
}
Rd = res;
```

Parameters

- **t** – **[in]** long type of value stored in t

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMADRS32 (long t, unsigned long a, unsigned long b)

KMADRS32 (Saturating Signed Multiply Two Words & Reverse Subtract & Add)

Type: DSP (RV64 Only)

Syntax:

```
KMADS32 Rd, Rs1, Rs2
KMADRS32 Rd, Rs1, Rs2
KMAXDS32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32-bit multiplications from 32-bit elements in two registers; and then perform a subtraction operation between the two 64-bit results. Then add the subtraction result to 64-bit data in a third register. The addition result may be saturated.

- KMADS32: rd + (top*top - bottom*bottom)
- KMADRS32: rd + (bottom*bottom - top*top)
- KMAXDS32: rd + (top*bottom - bottom*top)

Description :

For the `KMADS32` instruction, it multiplies the bottom 32-bit element in Rs1 with the bottom 32-bit element in Rs2 and then subtracts the result from the result of multiplying the top 32-bit element in Rs1 with the top 32-bit element in Rs2. For the `KMADRS32` instruction, it multiplies the top 32-bit element in Rs1 with the top 32-bit element in Rs2 and then subtracts the result from the result of multiplying the bottom 32-bit element in Rs1 with the bottom 32-bit element in Rs2. For the `KMAXDS32` instruction, it multiplies the bottom 32-bit element in Rs1 with the top 32-bit element in Rs2 and then subtracts the result from the result of multiplying the top 32-bit element in Rs1 with the bottom 32-bit element in Rs2. The subtraction result is then added to the content of 64-bit data in Rd. If the addition result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to

a. The 64-bit result after saturation is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rd + (Rs1.W[1] * Rs2.W[1]) - (Rs1.W[0] * Rs2.W[0]); // KMADS32
res = Rd + (Rs1.W[0] * Rs2.W[0]) - (Rs1.W[1] * Rs2.W[1]); // KMADRS32
res = Rd + (Rs1.W[1] * Rs2.W[0]) - (Rs1.W[0] * Rs2.W[1]); // KMAXDS32
if (res > (2^63)-1) {
  res = (2^63)-1;
  OV = 1;
} else if (res < -2^63) {
  res = -2^63;
  OV = 1;
}
Rd = res;
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMAXDS32 (long t, unsigned long a, unsigned long b)

KMAXDS32 (Saturating Signed Crossed Multiply Two Words & Subtract & Add)

Type: DSP (RV64 Only)

Syntax:

```
KMADS32 Rd, Rs1, Rs2
KMADRS32 Rd, Rs1, Rs2
KMAXDS32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32-bit multiplications from 32-bit elements in two registers; and then perform a subtraction operation between the two 64-bit results. Then add the subtraction result to 64-bit data in a third register. The addition result may be saturated.

- KMADS32: rd + (top*top - bottom*bottom)
- KMADRS32: rd + (bottom*bottom - top*top)
- KMAXDS32: rd + (top*bottom - bottom*top)

Description :

For the `KMADS32` instruction, it multiplies the bottom 32-bit element in Rs1 with the bottom 32-bit element in Rs2 and then subtracts the result from the result of multiplying the top 32-bit element in Rs1 with the top 32-bit element in Rs2. For the `KMADRS32` instruction, it multiplies the top 32-bit element in Rs1 with the top 32-bit element in Rs2 and then subtracts the result from the result of multiplying the bottom 32-bit element in Rs1 with the bottom 32-bit element in Rs2. For the `KMAXDS32` instruction, it multiplies the bottom 32-bit element in Rs1 with the top 32-bit element in Rs2 and then subtracts the result from the result of multiplying the top 32-bit element in Rs1 with the bottom 32-bit element in Rs2. The subtraction result is then added to the content of 64-bit data in Rd. If the addition result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to

a. The 64-bit result after saturation is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rd + (Rs1.W[1] * Rs2.W[1]) - (Rs1.W[0] * Rs2.W[0]); // KMADS32
res = Rd + (Rs1.W[0] * Rs2.W[0]) - (Rs1.W[1] * Rs2.W[1]); // KMADRS32
res = Rd + (Rs1.W[1] * Rs2.W[0]) - (Rs1.W[0] * Rs2.W[1]); // KMAXDS32
if (res > (2^63)-1) {
  res = (2^63)-1;
  OV = 1;
} else if (res < -2^63) {
  res = -2^63;
  OV = 1;
}
Rd = res;
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_KMSDA32 (long t, unsigned long a, unsigned long b)

KMSDA32 (Saturating Signed Multiply Two Words & Add & Subtract)

Type: DSP (RV64 Only)

Syntax:

```
KMSDA32 Rd, Rs1, Rs2
KMSXDA32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32-bit multiplications from the 32-bit element of two registers; and then subtracts the two 64-bit results from a third register. The subtraction result may be saturated.

- KMSDA: rd - top*top - bottom*bottom
- KMSXDA: rd - top*bottom - bottom*top

Description :

For the `KMSDA32` instruction, it multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2 and multiplies the top 32-bit element of Rs1 with the top 32-bit element of Rs2. For the `KMSXDA32` instruction, it multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2 and multiplies the top 32-bit element of Rs1 with the bottom 32-bit element of Rs2. The two 64-bit multiplication results are then subtracted from the content of Rd. If the subtraction result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The result after saturation is written to Rd. The 32-bit contents are treated as signed integers.

Operations:

```
res = Rd - (Rs1.W[1] * Rs2.W[1]) - (Rs1.W[0] * Rs2.W[0]); // KMSDA32
res = Rd - (Rs1.W[1] * Rs2.W[0]) - (Rs1.W[0] * Rs2.W[1]); // KMSXDA32
if (res > (2^63)-1) {
  res = (2^63)-1;
  OV = 1;
} else if (res < -2^63) {
  res = -2^63;
  OV = 1;
}
Rd = res;
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_KMSXDA32 (long t, unsigned long a, unsigned long b)`

KMSXDA32 (Saturating Signed Crossed Multiply Two Words & Add & Subtract)

Type: DSP (RV64 Only)

Syntax:

```
KMSDA32 Rd, Rs1, Rs2
KMSXDA32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32-bit multiplications from the 32-bit element of two registers; and then subtracts the two 64-bit results from a third register. The subtraction result may be saturated.

- KMSDA: rd - top*top - bottom*bottom
- KMSXDA: rd - top*bottom - bottom*top

Description :

For the `KMSDA32` instruction, it multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2 and multiplies the top 32-bit element of Rs1 with the top 32-bit element of Rs2. For the `KMSXDA32` instruction, it multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2 and multiplies the top 32-bit element of Rs1 with the bottom 32-bit element of Rs2. The two 64-bit multiplication results are then subtracted from the content of Rd. If the subtraction result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The result after saturation is written to Rd. The 32-bit contents are treated as signed integers.

Operations:

```
res = Rd - (Rs1.W[1] * Rs2.W[1]) - (Rs1.W[0] * Rs2.W[0]); // KMSDA32
res = Rd - (Rs1.W[1] * Rs2.W[0]) - (Rs1.W[0] * Rs2.W[1]); // KMSXDA32
if (res > (2^63)-1) {
  res = (2^63)-1;
  OV = 1;
} else if (res < -2^63) {
  res = -2^63;
  OV = 1;
}
Rd = res;
```

Parameters

- **t** – **[in]** long type of value stored in t
- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_SMDS32 (unsigned long a, unsigned long b)`

SMDS32 (Signed Multiply Two Words and Subtract)

Type: DSP (RV64 Only)

Syntax:

```
SMDS32 Rd, Rs1, Rs2
SMDRS32 Rd, Rs1, Rs2
SMXDS32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32-bit multiplications from the l 32-bit element of two registers; and then perform a subtraction operation between the two 64-bit results.

- SMDS32: top*top - bottom*bottom
- SMDRS32: bottom*bottom - top*top
- SMXDS32: top*bottom - bottom*top

Description :

For the `SMDS32` instruction, it multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2 and then subtracts the result from the result of multiplying the top 32-bit element of Rs1 with the top 32-bit element of Rs2. For the `SMDRS32` instruction, it multiplies the top 32-bit element of Rs1 with the top 32-bit element of Rs2 and then subtracts the result from the result of multiplying the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2. For the `SMXDS32` instruction, it multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2 and then subtracts the result from the result of multiplying the top 32-bit element of Rs1 with the bottom 32-bit element of Rs2. The subtraction result is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
Rt = (Rs1.W[1] * Rs2.W[1]) - (Rs1.W[0] * Rs2.W[0]); // SMDS32
Rt = (Rs1.W[0] * Rs2.W[0]) - (Rs1.W[1] * Rs2.W[1]); // SMDRS32
Rt = (Rs1.W[1] * Rs2.W[0]) - (Rs1.W[0] * Rs2.W[1]); // SMXDS32
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_SMDRS32 (unsigned long a, unsigned long b)

SMDRS32 (Signed Multiply Two Words and Reverse Subtract)

Type: DSP (RV64 Only)

Syntax:

```
SMDS32 Rd, Rs1, Rs2
SMDRS32 Rd, Rs1, Rs2
SMXDS32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32-bit multiplications from the l 32-bit element of two registers; and then perform a subtraction operation between the two 64-bit results.

- SMDS32: top*top - bottom*bottom
- SMDRS32: bottom*bottom - top*top
- SMXDS32: top*bottom - bottom*top

Description :

For the SMDS32 instruction, it multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2 and then subtracts the result from the result of multiplying the top 32-bit element of Rs1 with the top 32-bit element of Rs2. For the SMDRS32 instruction, it multiplies the top 32-bit element of Rs1 with the top 32-bit element of Rs2 and then subtracts the result from the result of multiplying the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2. For the SMXDS32 instruction, it multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2 and then subtracts the result from the result of multiplying the top 32-bit element of Rs1 with the bottom 32-bit element of Rs2. The subtraction result is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
Rt = (Rs1.W[1] * Rs2.W[1]) - (Rs1.W[0] * Rs2.W[0]); // SMDS32
Rt = (Rs1.W[0] * Rs2.W[0]) - (Rs1.W[1] * Rs2.W[1]); // SMDRS32
Rt = (Rs1.W[1] * Rs2.W[0]) - (Rs1.W[0] * Rs2.W[1]); // SMXDS32
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_SMXDS32 (unsigned long a, unsigned long b)

SMXDS32 (Signed Crossed Multiply Two Words and Subtract)

Type: DSP (RV64 Only)

Syntax:

```
SMDS32 Rd, Rs1, Rs2
SMDRS32 Rd, Rs1, Rs2
SMXDS32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32-bit multiplications from the l 32-bit element of two registers; and then perform a subtraction operation between the two 64-bit results.

- SMDS32: top*top - bottom*bottom
- SMDRS32: bottom*bottom - top*top
- SMXDS32: top*bottom - bottom*top

Description :

For the SMDS32 instruction, it multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2 and then subtracts the result from the result of multiplying the top 32-bit element of Rs1 with the top 32-bit element of Rs2. For the SMDRS32 instruction, it multiplies the top 32-bit element of Rs1 with the top 32-bit element of Rs2 and then subtracts the result from the result of multiplying the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2. For the SMXDS32 instruction, it multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2 and then subtracts the result from the result of multiplying the top 32-bit element of Rs1 with the bottom 32-bit element of Rs2. The subtraction result is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
Rt = (Rs1.W[1] * Rs2.W[1]) - (Rs1.W[0] * Rs2.W[0]); // SMDS32
Rt = (Rs1.W[0] * Rs2.W[0]) - (Rs1.W[1] * Rs2.W[1]); // SMDRS32
Rt = (Rs1.W[1] * Rs2.W[0]) - (Rs1.W[0] * Rs2.W[1]); // SMXDS32
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in long type

(RV64 Only) Non-SIMD 32-bit Shift Instructions

__RV_SRAIW_U(a, b)

group **NMSIS_Core_DSP_Intrinsic_RV64_NON_SIMD_32B_SHIFT**

(RV64 Only) Non-SIMD 32-bit Shift Instructions

there are 1 (RV64 Only) Non-SIMD 32-bit Shift Instructions

Defines

__RV_SRAIW_U(a, b)

SRAIW.u (Rounding Shift Right Arithmetic Immediate Word)

Type: DSP (RV64 only)

Syntax:

```
SRAIW.u Rd, Rs1, imm5u
```

Purpose :

Perform a 32-bit arithmetic right shift operation with rounding. The shift amount is an immediate value.

Description :

This instruction right-shifts the lower 32-bit content of Rs1 arithmetically. The shifted out bits are filled with the sign-bit Rs1(31) and the shift amount is specified by the imm5u constant. For the rounding operation, a value of 1 is added to the most significant discarded bit of the data to calculate the final result. And the result is sign-extended and written to Rd.

Operations:

```
sa = imm5u;
if (sa != 0) {
  res[31:-1] = SE33(Rs1[31:(sa-1)]) + 1;
  Rd = SE32(res[31:0]);
} else {
  Rd = SE32(Rs1.W[0]);
}
```

Parameters

- **a** – **[in]** int type of value stored in a

- b – **[in]** unsigned int type of value stored in b

Returns value stored in long type

32-bit Packing Instructions

__STATIC_FORCEINLINE unsigned long __RV_PKBB32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_PKBT32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_PKTT32 (unsigned long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long __RV_PKTB32 (unsigned long a, unsigned long b)

group NMSIS_Core_DSP_Intrinsic_RV64_32B_PACK

32-bit Packing Instructions

There are four 32-bit packing instructions here

Functions

__STATIC_FORCEINLINE unsigned long __RV_PKBB32 (unsigned long a, unsigned long b)

PKBB32 (Pack Two 32-bit Data from Both Bottom Half)

Type: DSP (RV64 Only)

Syntax:

```
PKBB32 Rd, Rs1, Rs2
PKBT32 Rd, Rs1, Rs2
PKTT32 Rd, Rs1, Rs2
PKTB32 Rd, Rs1, Rs2
```

Purpose :

Pack 32-bit data from 64-bit chunks in two registers.

- PKBB32: bottom.bottom
- PKBT32: bottom.top
- PKTT32: top.top
- PKTB32: top.bottom

Description :

(PKBB32) moves Rs1.W[0] to Rd.W[1] and moves Rs2.W[0] to Rd.W[0]. (PKBT32) moves Rs1.W[0] to Rd.W[1] and moves Rs2.W[1] to Rd.W[0]. (PKTT32) moves Rs1.W[1] to Rd.W[1] and moves Rs2.W[1] to Rd.W[0]. (PKTB32) moves Rs1.W[1] to Rd.W[1] and moves Rs2.W[0] to Rd.W[0].

Operations:

```
Rd = CONCAT(Rs1.W[_*0*_], Rs2.W[_*0*_]); // PKBB32
Rd = CONCAT(Rs1.W[_*0*_], Rs2.W[_*1*_]); // PKBT32
Rd = CONCAT(Rs1.W[_*1*_], Rs2.W[_*1*_]); // PKTT32
Rd = CONCAT(Rs1.W[_*1*_], Rs2.W[_*0*_]); // PKTB32
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_PKBT32 (unsigned long a, unsigned long b)

PKBT32 (Pack Two 32-bit Data from Bottom and Top Half)

Type: DSP (RV64 Only)

Syntax:

```
PKBB32 Rd, Rs1, Rs2
PKBT32 Rd, Rs1, Rs2
PKTT32 Rd, Rs1, Rs2
PKTB32 Rd, Rs1, Rs2
```

Purpose :

Pack 32-bit data from 64-bit chunks in two registers.

- PKBB32: bottom.bottom
- PKBT32: bottom.top
- PKTT32: top.top
- PKTB32: top.bottom

Description :

(PKBB32) moves Rs1.W[0] to Rd.W[1] and moves Rs2.W[0] to Rd.W[0]. (PKBT32) moves Rs1.W[0] to Rd.W[1] and moves Rs2.W[1] to Rd.W[0]. (PKTT32) moves Rs1.W[1] to Rd.W[1] and moves Rs2.W[1] to Rd.W[0]. (PKTB32) moves Rs1.W[1] to Rd.W[1] and moves Rs2.W[0] to Rd.W[0].

Operations:

```
Rd = CONCAT(Rs1.W[_*0*_], Rs2.W[_*0*_]); // PKBB32
Rd = CONCAT(Rs1.W[_*0*_], Rs2.W[_*1*_]); // PKBT32
Rd = CONCAT(Rs1.W[_*1*_], Rs2.W[_*1*_]); // PKTT32
Rd = CONCAT(Rs1.W[_*1*_], Rs2.W[_*0*_]); // PKTB32
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_PKTT32 (unsigned long a, unsigned long b)

PKTT32 (Pack Two 32-bit Data from Both Top Half)

Type: DSP (RV64 Only)

Syntax:

```
PKBB32 Rd, Rs1, Rs2
PKBT32 Rd, Rs1, Rs2
PKTT32 Rd, Rs1, Rs2
PKTB32 Rd, Rs1, Rs2
```

Purpose :

Pack 32-bit data from 64-bit chunks in two registers.

- PKBB32: bottom.bottom
- PKBT32: bottom.top
- PKTT32: top.top
- PKTB32: top.bottom

Description :

(PKBB32) moves Rs1.W[0] to Rd.W[1] and moves Rs2.W[0] to Rd.W[0]. (PKBT32) moves Rs1.W[0] to Rd.W[1] and moves Rs2.W[1] to Rd.W[0]. (PKTT32) moves Rs1.W[1] to Rd.W[1] and moves Rs2.W[1] to Rd.W[0]. (PKTB32) moves Rs1.W[1] to Rd.W[1] and moves Rs2.W[0] to Rd.W[0].

Operations:

```
Rd = CONCAT(Rs1.W[_*0*_], Rs2.W[_*0*_]); // PKBB32
Rd = CONCAT(Rs1.W[_*0*_], Rs2.W[_*1*_]); // PKBT32
Rd = CONCAT(Rs1.W[_*1*_], Rs2.W[_*1*_]); // PKTT32
Rd = CONCAT(Rs1.W[_*1*_], Rs2.W[_*0*_]); // PKTB32
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_PKTB32 (unsigned long a, unsigned long b)

PKTB32 (Pack Two 32-bit Data from Top and Bottom Half)

Type: DSP (RV64 Only)

Syntax:

```
PKBB32 Rd, Rs1, Rs2
PKBT32 Rd, Rs1, Rs2
PKTT32 Rd, Rs1, Rs2
PKTB32 Rd, Rs1, Rs2
```

Purpose :

Pack 32-bit data from 64-bit chunks in two registers.

- PKBB32: bottom.bottom
- PKBT32: bottom.top
- PKTT32: top.top
- PKTB32: top.bottom

Description :

(PKBB32) moves Rs1.W[0] to Rd.W[1] and moves Rs2.W[0] to Rd.W[0]. (PKBT32) moves Rs1.W[0] to Rd.W[1] and moves Rs2.W[1] to Rd.W[0]. (PKTT32) moves Rs1.W[1] to Rd.W[1] and moves Rs2.W[1] to Rd.W[0]. (PKTB32) moves Rs1.W[1] to Rd.W[1] and moves Rs2.W[0] to Rd.W[0].

Operations:

```
Rd = CONCAT(Rs1.W[_*0*_], Rs2.W[_*0*_]); // PKBB32
Rd = CONCAT(Rs1.W[_*0*_], Rs2.W[_*1*_]); // PKBT32
Rd = CONCAT(Rs1.W[_*1*_], Rs2.W[_*1*_]); // PKTT32
Rd = CONCAT(Rs1.W[_*1*_], Rs2.W[_*0*_]); // PKTB32
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long type

group `NMSIS_Core_DSP_Intrinsic_RV64_ONLY`

RV64 Only Instructions.

Nuclei Customized Default DSP Instructions

`__STATIC_FORCEINLINE unsigned long __RV_EXPD80 (unsigned long a)`

`__STATIC_FORCEINLINE unsigned long __RV_EXPD81 (unsigned long a)`

`__STATIC_FORCEINLINE unsigned long __RV_EXPD82 (unsigned long a)`

`__STATIC_FORCEINLINE unsigned long __RV_EXPD83 (unsigned long a)`

group `NMSIS_Core_DSP_Intrinsic_NUCLEI_Default`

(RV32 & RV64)Nuclei Customized DSP Instructions

This is Nuclei customized DSP instructions for both RV32 and RV64

Functions

__STATIC_FORCEINLINE unsigned long __RV_EXPD80 (unsigned long a)

EXPD80 (Expand and Copy Byte 0 to 32bit(when rv32) or 64bit(when rv64))

Type: DSP

Syntax:

```
EXPD80 Rd, Rs1
```

Purpose :

When rv32, Copy 8-bit data from 32-bit chunks into 4 bytes in a register. When rv64, Copy 8-bit data from 64-bit chunks into 8 bytes in a register.

Description :

Moves Rs1.B[0][7:0] to Rd.[0][7:0], Rd.[1][7:0], Rd.[2][7:0], Rd.[3][7:0]

Operations:

```
Rd.W[x][31:0] = CONCAT(Rs1.B[0][7:0], Rs1.B[0][7:0], Rs1.B[0][7:0], Rs1.
↪B[0][7:0]);
for RV32: x=0
```

Parameters a – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_EXPD81 (unsigned long a)

EXPD81 (Expand and Copy Byte 1 to 32bit(rv32) or 64bit(when rv64))

Type: DSP

Syntax:

```
EXPD81 Rd, Rs1
```

Purpose :

Copy 8-bit data from 32-bit chunks into 4 bytes in a register.

Description :

Moves Rs1.B[1][7:0] to Rd.[0][7:0], Rd.[1][7:0], Rd.[2][7:0], Rd.[3][7:0]

Operations:

```
Rd.W[x][31:0] = CONCAT(Rs1.B[1][7:0], Rs1.B[1][7:0], Rs1.B[1][7:0], Rs1.
↪B[1][7:0]);
for RV32: x=0
```

Parameters a – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_EXPD82 (unsigned long a)

EXPD82 (Expand and Copy Byte 2 to 32bit(rv32) or 64bit(when rv64))

Type: DSP

Syntax:

```
EXPD82 Rd, Rs1
```

Purpose :

Copy 8-bit data from 32-bit chunks into 4 bytes in a register.

Description :

Moves Rs1.B[2][7:0] to Rd.[0][7:0], Rd.[1][7:0], Rd.[2][7:0], Rd.[3][7:0]

Operations:

```
Rd.W[x][31:0] = CONCAT(Rs1.B[2][7:0], Rs1.B[2][7:0], Rs1.B[2][7:0], Rs1.
↪B[2][7:0]);
for RV32: x=0
```

Parameters **a** – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_EXPD83 (unsigned long a)

EXPD83 (Expand and Copy Byte 3 to 32bit(rv32) or 64bit(when rv64))

Type: DSP

Syntax:

```
EXPD83 Rd, Rs1
```

Purpose :

Copy 8-bit data from 32-bit chunks into 4 bytes in a register.

Description :

Moves Rs1.B[3][7:0] to Rd.[0][7:0], Rd.[1][7:0], Rd.[2][7:0], Rd.[3][7:0]

Operations:

```
Rd.W[x][31:0] = CONCAT(Rs1.B[3][7:0], Rs1.B[3][7:0], Rs1.B[3][7:0], Rs1.
↪B[3][7:0]);
for RV32: x=0
```

Parameters **a** – **[in]** unsigned long type of value stored in a

Returns value stored in unsigned long type

Nuclei Customized N1/N2/N3 DSP Instructions

`__STATIC_FORCEINLINE unsigned long long __RV_DKHM8 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKHM16 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKABS8 (unsigned long long a)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKABS16 (unsigned long long a)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKSLRA8 (unsigned long long a, int b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKSLRA16 (unsigned long long a, int b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKADD8 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKADD16 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKSUB8 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKSUB16 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKHMX8 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKHMX16 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DSMMUL (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DSMMUL_U (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKWMMUL (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKWMMUL_U (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKABS32 (unsigned long long a)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKSLRA32 (unsigned long long a, int b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKADD32 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKSUB32 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DRADD16 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DSUB16 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DRADD32 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DSUB32 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DMSR16 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DMSR17 (unsigned long a, unsigned long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DMSR33 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DMXSR33 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long __RV_DREDAS16 (unsigned long long a)`

`__STATIC_FORCEINLINE unsigned long __RV_DREDSA16 (unsigned long long a)`

`__STATIC_FORCEINLINE int16_t __RV_DKCLIP64 (unsigned long long a)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKMDA (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKMXDA (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DSMDRS (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DSMXDS (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_DSMBB32 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_DSMBB32_SRA14 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_DSMBB32_SRA32 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_DSMBT32 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_DSMBT32_SRA14 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_DSMBT32_SRA32 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_DSMTT32 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_DSMTT32_SRA14 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_DSMTT32_SRA32 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DPKBB32 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DPKBT32 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DPKTT32 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DPKTB32 (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DPKTB16 (unsigned long long a, unsigned long long b)`

__STATIC_FORCEINLINE unsigned long long __RV_DPKBB16 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DPKBT16 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DPKTT16 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DSRA16 (unsigned long long a, unsigned long b)

__STATIC_FORCEINLINE unsigned long long __RV_DADD16 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DADD32 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DSMBB16 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DSMBT16 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DSMTT16 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DRCRSA16 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DRCRSA32 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DRCRAS16 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DRCRAS32 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKCRAS16 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKCRSA16 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DRSUB16 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DSTSA32 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DSTAS32 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKCRSA32 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKCRAS32 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DCRSA32 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DCRAS32 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKSTSA16 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKSTAS16 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DRSUB32 (unsigned long long a, unsigned long long b)

__RV_DSCLIP8(a, b)

__RV_DSCLIP16(a, b)

__RV_DSCLIP32(a, b)

__STATIC_FORCEINLINE unsigned long long __RV_DKMMAC (unsigned long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKMMAC_U (unsigned long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKMMSB (unsigned long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKMMSB_U (unsigned long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKMADA (unsigned long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKMAXDA (unsigned long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKMADS (unsigned long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKMADRS (unsigned long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKMAXDS (unsigned long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKMSDA (unsigned long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DKMSXDA (unsigned long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DSMAQA (unsigned long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DSMAQA_SU (unsigned long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE unsigned long long __RV_DUMAQA (unsigned long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DKMDA32 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DKMXDA32 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DKMADA32 (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DKMAXDA32 (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DKMADS32 (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DKMADRS32 (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DKMAXDS32 (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DKMSDA32 (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DKMSXDA32 (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DSMDS32 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DSMDRS32 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DSMXDS32 (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DSMALDA (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DSMALXDA (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DSMALDS (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DSMALDRS (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DSMALXDS (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DSMSLDA (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DSMSLXDA (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DDSMAQA (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DDSMAQASU (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long long __RV_DDUMAQA (long long t, unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long __RV_DSMA32_U (unsigned long long a, unsigned long long b)

__STATIC_FORCEINLINE long __RV_DSMXS32_U (unsigned long long a, unsigned long long b)

`__STATIC_FORCEINLINE long __RV_DSMXA32_U (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long __RV_DSMS32_U (unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long __RV_DSMADA16 (long long t, unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long __RV_DSMAXDA16 (long long t, unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE unsigned long long __RV_DKSMS32_U (unsigned long long t, unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long __RV_DMADA32 (long long t, unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_DSMALBB (long long t, unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_DSMALBT (long long t, unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_DSMALTT (long long t, unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_DKMABB32 (long long t, unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_DKMABT32 (long long t, unsigned long long a, unsigned long long b)`

`__STATIC_FORCEINLINE long long __RV_DKMATT32 (long long t, unsigned long long a, unsigned long long b)`

group `NMSIS_Core_DSP_Intrinsic_NUCLEI_N1`

(RV32 only)Nuclei Customized N1 DSP Instructions

This is Nuclei customized DSP N1 instructions only for RV32

Functions

__STATIC_FORCEINLINE unsigned long long __RV_DKHM8 (unsigned long long a, unsigned long long b)

DKHM8 (64-bit SIMD Signed Saturating Q7 Multiply)

Type: SIMD

Syntax:

```
DKHM8 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do Q7xQ7 element multiplications simultaneously. The Q14 results are then reduced to Q7 numbers again.

Description :

For the DKHM8 instruction, multiply the top 8-bit Q7 content of 16-bit chunks in Rs1 with the top 8-bit Q7 content of 16-bit chunks in Rs2. At the same time, multiply the bottom 8-bit Q7 content of 16-bit chunks in Rs1 with the bottom 8-bit Q7 content of 16-bit chunks in Rs2.

The Q14 results are then right-shifted 7-bits and saturated into Q7 values. The Q7 results are then written into Rd. When both the two Q7 inputs of a multiplication are 0x80, saturation will happen. The result will be saturated to 0x7F and the overflow flag OV will be set.

Operations:

```
op1t = Rs1.B[x+1]; op2t = Rs2.B[x+1]; // top
op1b = Rs1.B[x]; op2b = Rs2.B[x]; // bottom
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  if (0x80 != aop | 0x80 != bop) {
    res = (aop s* bop) >> 7;
  } else {
    res= 0x7F;
    OV = 1;
  }
}
Rd.H[x/2] = concat(rest, resb);
for RV32, x=0,2,4,6
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKHM16 (unsigned long long a, unsigned long long b)

DKHM16 (64-bit SIMD Signed Saturating Q15 Multiply)

Type: SIMD

Syntax:

```
DKHM16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do Q15xQ15 element multiplications simultaneously. The Q30 results are then reduced to Q15 numbers again.

Description :

For the DKHM16 instruction, multiply the top 16-bit Q15 content of 32-bit chunks in Rs1 with the top 16-bit Q15 content of 32-bit chunks in Rs2. At the same time, multiply the bottom 16-bit Q15 content of 32-bit chunks in Rs1 with the bottom 16-bit Q15 content of 32-bit chunks in Rs2.

The Q30 results are then right-shifted 15-bits and saturated into Q15 values. The Q15 results are then written into Rd. When both the two Q15 inputs of a multiplication are 0x8000, saturation will happen. The result will be saturated to 0x7FFF and the overflow flag OV will be set.

Operations:

```
op1t = Rs1.H[x+1]; op2t = Rs2.H[x+1]; // top
op1b = Rs1.H[x]; op2b = Rs2.H[x]; // bottom
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  if (0x8000 != aop | 0x8000 != bop) {
    res = (aop s* bop) >> 15;
  } else {
    res= 0x7FFF;
    OV = 1;
  }
}
Rd.W[x/2] = concat(rest, resb);
for RV32: x=0, 2
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKABS8 (unsigned long long a)

DKABS8 (64-bit SIMD 8-bit Saturating Absolute)

Type: SIMD

Syntax:

```
DKABS8 Rd, Rs1
# Rd, Rs1 are all even/odd pair of registers
```

Purpose :

Get the absolute value of 8-bit signed integer elements simultaneously.

Description :

This instruction calculates the absolute value of 8-bit signed integer elements stored in Rs1 and writes the element results to Rd. If the input number is 0x80, this instruction generates 0x7f as the output and sets the OV bit to 1.

Operations:

```
src = Rs1.B[x];
if (src == 0x80) {
  src = 0x7f;
  OV = 1;
} else if (src[7] == 1)
  src = -src;
}
Rd.B[x] = src;
for RV32: x=7...0,
```

Parameters **a** – **[in]** unsigned long long type of value stored in a

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKABS16 (unsigned long long a)

DKABS16 (64-bit SIMD 16-bit Saturating Absolute)

Type: SIMD

Syntax:

```
DKABS16 Rd, Rs1
# Rd, Rs1 are all even/odd pair of registers
```

Purpose :

Get the absolute value of 16-bit signed integer elements simultaneously.

Description :

This instruction calculates the absolute value of 16-bit signed integer elements stored in Rs1 and writes the element results to Rd. If the input number is 0x8000, this instruction generates 0x7fff as the output and sets the OV bit to 1.

Operations:

```
src = Rs1.H[x];
if (src == 0x8000) {
  src = 0x7fff;
  OV = 1;
} else if (src[15] == 1)
  src = -src;
}
Rd.H[x] = src;
for RV32: x=3...0,
```

Parameters **a** – **[in]** unsigned long long type of value stored in a

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKSLRA8 (unsigned long long a, int b)

DKSLRA8 (64-bit SIMD 8-bit Shift Left Logical with Saturation or Shift Right Arithmetic)

Type: SIMD

Syntax:

```
DKSLRA8 Rd, Rs1, Rs2
# Rd, Rs1 are all even/odd pair of registers
```

Purpose :

Do 8-bit elements logical left (positive) or arithmetic right (negative) shift operation with Q7 saturation for the left shift.

Description :

The 8-bit data elements of Rs1 are left-shifted logically or right-shifted arithmetically based on the value of Rs2[3:0]. Rs2[3:0] is in the signed range of [-2^3, 2^3-1]. A positive Rs2[3:0] means logical left shift and a negative Rs2[3:0] means arithmetic right shift. The shift amount is the absolute value of Rs2[3:0]. However, the behavior of `Rs2[3:0]==-2^3 (0x8)` is defined to be equivalent to the behavior of `Rs2[3:0]==-(2^3-1) (0x9)`. The left-shifted results are saturated to the 8-bit signed integer range of [-2^7, 2^7-1]. If any saturation happens, this instruction sets the OV flag. The value of Rs2[31:4] will not affect this instruction.

Operations:

```
if (Rs2[3:0] < 0) {
  sa = -Rs2[3:0];
  sa = (sa == 8)? 7 : sa;
  Rd.B[x] = SE8(Rs1.B[x][7:sa]);
} else {
  sa = Rs2[2:0];
  res[(7+sa):0] = Rs1.B[x] <<(logic) sa;
  if (res > (2^7)-1) {
    res[7:0] = 0x7f; OV = 1;
  } else if (res < -2^7) {
    res[7:0] = 0x80; OV = 1;
  }
  Rd.B[x] = res[7:0];
}
for RV32: x=7...0,
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKSLRA16 (unsigned long long a, int b)

DKSLRA16 (64-bit SIMD 16-bit Shift Left Logical with Saturation or Shift Right Arithmetic)

Type: SIMD

Syntax:

```
DKSLRA16 Rd, Rs1, Rs2
# Rd, Rs1 are all even/odd pair of registers
```

Purpose :

Do 16-bit elements logical left (positive) or arithmetic right (negative) shift operation with Q15 saturation for the left shift.

Description :

The 16-bit data elements of Rs1 are left-shifted logically or right-shifted arithmetically based on the value of Rs2[4:0]. Rs2[4:0] is in the signed range of [-2^4, 2^4-1]. A positive Rs2[4:0] means logical left shift and a negative Rs2[4:0] means arithmetic right shift. The shift amount is the absolute value of Rs2[4:0]. However, the behavior of `Rs2[4:0]==-2^4 (0x10)` is defined to be equivalent to the behavior of `Rs2[4:0]==-(2^4-1) (0x11)`. The left-shifted results are saturated to the 16-bit signed integer range of [-2^15, 2^15-1]. After the shift, saturation, or rounding, the final results are written to Rd. If any saturation happens, this instruction sets the OV flag. The value of Rs2[31:5] will not affect this instruction.

Operations:

```
if (Rs2[4:0] < 0) {
  sa = -Rs2[4:0];
  sa = (sa == 16)? 15 : sa;
  Rd.H[x] = SE16(Rs1.H[x][15:sa]);
} else {
  sa = Rs2[3:0];
  res[(15+sa):0] = Rs1.H[x] <<(logic) sa;
  if (res > (2^15)-1) {
    res[15:0] = 0x7fff; OV = 1;
  } else if (res < -2^15) {
    res[15:0] = 0x8000; OV = 1;
  }
  d.H[x] = res[15:0];
}
for RV32: x=3...0,
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in unsigned long long type

`__STATIC_FORCEINLINE unsigned long long __RV_DKADD8 (unsigned long long a, unsigned long long b)`

DKADD8 (64-bit SIMD 8-bit Signed Saturating Addition)

Type: SIMD

Syntax:

```
DKADD8 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 8-bit signed integer element saturating additions simultaneously.

Description :

This instruction adds the 8-bit signed integer elements in Rs1 with the 8-bit signed integer elements in Rs2. If any of the results are beyond the Q7 number range (-2^7 <= Q7 <= 2^7-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.B[x] + Rs2.B[x];
if (res[x] > 127) {
  res[x] = 127;
  OV = 1;
} else if (res[x] < -128) {
  res[x] = -128;
  OV = 1;
}
Rd.B[x] = res[x];
for RV32: x=7...0,
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKADD16 (unsigned long long a, unsigned long long b)

DKADD16 (64-bit SIMD 16-bit Signed Saturating Addition)

Type: SIMD

Syntax:

```
DKADD16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 16-bit signed integer element saturating additions simultaneously.

Description :

This instruction adds the 16-bit signed integer elements in Rs1 with the 16-bit signed integer elements in Rs2. If any of the results are beyond the Q15 number range (-2^15 <= Q15 <= 2^15-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.H[x] + Rs2.H[x];
if (res[x] > 32767) {
  res[x] = 32767;
  OV = 1;
} else if (res[x] < -32768) {
  res[x] = -32768;
  OV = 1;
}
```

(continues on next page)

(continued from previous page)

```
Rd.H[x] = res[x];
for RV32: x=3...0,
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKSUB8 (unsigned long long a, unsigned long long b)

DKSUB8 (64-bit SIMD 8-bit Signed Saturating Subtraction)

Type: SIMD

Syntax:

```
DKSUB8 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 8-bit signed elements saturating subtractions simultaneously.

Description :

This instruction subtracts the 8-bit signed integer elements in Rs2 from the 8-bit signed integer elements in Rs1. If any of the results are beyond the Q7 number range (-2^7 <= Q7 <= 2^7-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.B[x] - Rs2.B[x];
if (res[x] > (2^7)-1) {
  res[x] = (2^7)-1;
  OV = 1;
} else if (res[x] < -2^7) {
  res[x] = -2^7;
  OV = 1;
}
Rd.B[x] = res[x];
for RV32: x=7...0,
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKSUB16 (unsigned long long a, unsigned long long b)

DKSUB16 (64-bit SIMD 16-bit Signed Saturating Subtraction)

Type: SIMD

Syntax:

```
DKSUB16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 16-bit signed integer elements saturating subtractions simultaneously.

Description :

This instruction subtracts the 16-bit signed integer elements in Rs2 from the 16-bit signed integer elements in Rs1. If any of the results are beyond the Q15 number range (-2^15 <= Q15 <= 2^15-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.H[x] - Rs2.H[x];
if (res[x] > (2^15)-1) {
  res[x] = (2^15)-1;
  OV = 1;
} else if (res[x] < -2^15) {
  res[x] = -2^15;
  OV = 1;
}
Rd.H[x] = res[x];
for RV32: x=3...0,
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

group **NMSIS_Core_DSP_Intrinsic_NUCLEI_N2**

(RV32 only)Nuclei Customized N2 DSP Instructions

This is Nuclei customized DSP N2 instructions only for RV32

Defines

__RV_DSCLIP8(a, b)

DSCLIP8 (8-bit Signed Saturation and Clip)

Type: SIMD

Syntax:

```
DSCLIP8 Rd, Rs1, imm3u[2:0]
# Rd, Rs1 are all even/odd pair of registers
```

Purpose :

Limit the 8-bit signed integer elements of a register into a signed range simultaneously.

Description :

This instruction limits the 8-bit signed integer elements stored in Rs1 into a signed integer range between -2^imm3u and 2^imm3u-1, and writes the limited results to Rd. For example, if imm3u is 3, the 8-bit input values should be saturated between 7 and -8. If saturation is performed, set OV bit to 1.

Operations:

```
src = Rs1.B[x];
if (src > (2^imm3u)-1) {
  src = (2^imm3u)-1;
  OV = 1;
} else if (src < -2^imm3u) {
  src = -2^imm3u;
  OV = 1;
}
Rd.B[x] = src
x=7...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__RV_DSCLIP16(a, b)

DSCLIP16 (16-bit Signed Saturation and Clip)

Type: SIMD

Syntax:

```
DSCLIP16 Rd, Rs1, imm4u[3:0]
# Rd, Rs1 are all even/odd pair of registers
```

Purpose :

Limit the 16-bit signed integer elements of a register into a signed range simultaneously.

Description :

This instruction limits the 16-bit signed integer elements stored in Rs1 into a signed integer range between -2^imm4u and 2^imm4u-1, and writes the limited results to Rd. For example, if imm4u is 3, the 32-bit input values should be saturated between 7 and -8. If saturation is performed, set OV bit to 1.

Operations:

```
src = Rs1.H[x];
if (src > (2^imm4u)-1) {
  src = (2^imm4u)-1;
  OV = 1;
} else if (src < -2^imm4u) {
  src = -2^imm4u;
  OV = 1;
}
Rd.H[x] = src
x=3...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__RV_DSCLIP32(a, b)

DSCLIP32 (32-bit Signed Saturation and Clip)

Type: SIMD

Syntax:

```
DSCLIP32 Rd, Rs1, imm5u[4:0]
# Rd, Rs1 are all even/odd pair of registers
```

Purpose :

Limit the 32-bit signed integer elements of a register into a signed range simultaneously.

Description :

This instruction limits the 32-bit signed integer elements stored in Rs1 into a signed integer range between -2^imm5u and 2^imm5u-1, and writes the limited results to Rd. For example, if imm5u is 3, the 32-bit input values should be saturated between 7 and -8. If saturation is performed, set OV bit to 1.

Operations:

```
src = Rs1.W[x];
if (src > (2^imm5u)-1) {
  src = (2^imm5u)-1;
  OV = 1;
} else if (src < -2^imm5u) {
  src = -2^imm5u;
  OV = 1;
}
Rd.W[x] = src
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

Functions

__STATIC_FORCEINLINE unsigned long long __RV_DKHMX8 (unsigned long long a, unsigned long long b)

DKHMX8 (64-bit SIMD Signed Crossed Saturating Q7 Multiply)

Type: SIMD

Syntax:

```
DKHMX8 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do Q7xQ7 element crossed multiplications simultaneously. The Q15 results are then reduced to Q7 numbers again.

Description :

For the KHM8 instruction, multiply the top 8-bit Q7 content of 16-bit chunks in Rs1 with the bottom 8-bit Q7 content of 16-bit chunks in Rs2. At the same time, multiply the bottom 8-bit Q7 content of 16-bit chunks in Rs1 with the top 8-bit Q7 content of 16-bit chunks in Rs2.

The Q14 results are then right-shifted 7-bits and saturated into Q7 values. The Q7 results are then written into Rd. When both the two Q7 inputs of a multiplication are 0x80, saturation will happen. The result will be saturated to 0x7F and the overflow flag OV will be set.

Operations:

```
op1t = Rs1.B[x+1]; op2t = Rs2.B[x]; // top
op1b = Rs1.B[x]; op2b = Rs2.B[x+1]; // bottom
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  if (0x80 != aop | 0x80 != bop) {
    res = (aop s* bop) >> 7;
  } else {
    res= 0x7F;
    OV = 1;
  }
}
Rd.H[x/2] = concat(rest, resb);
for RV32, x=0,2,4,6
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKHMX16 (unsigned long long a, unsigned long long b)

DKHMX16 (64-bit SIMD Signed Crossed Saturating Q15 Multiply)

Type: SIMD

Syntax:

```
DKHMX16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do Q15xQ15 element crossed multiplications simultaneously. The Q31 results are then reduced to Q15 numbers again.

Description :

For the KHMX16 instruction, multiply the top 16-bit Q15 content of 32-bit chunks in Rs1 with the bottom 16-bit Q15 content of 32-bit chunks in Rs2. At the same time, multiply the bottom 16-bit Q15 content of 32-bit chunks in Rs1 with the top 16-bit Q15 content of 32-bit chunks in Rs2.

The Q30 results are then right-shifted 15-bits and saturated into Q15 values. The Q15 results are then written into Rd. When both the two Q15 inputs of a multiplication are 0x8000, saturation will happen. The result will be saturated to 0x7FFF and the overflow flag OV will be set.

Operations:

```
op1t = Rs1.H[x+1]; op2t = Rs2.H[x]; // top
op1b = Rs1.H[x]; op2b = Rs2.H[x+1]; // bottom
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  if (0x8000 != aop | 0x8000 != bop) {
    res = (aop s* bop) >> 15;
  } else {
    res= 0x7FFF;
    OV = 1;
  }
}
Rd.W[x/2] = concat(rest, resb);
for RV32, x=0,2
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DSMMUL (unsigned long long a, unsigned long long b)

DSMMUL (64-bit MSW 32x32 Signed Multiply)

Type: SIMD

Syntax:

```
DSMMUL Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do MSW 32x32 element signed multiplications simultaneously. The results are written into Rd.

Description :

This instruction multiplies the 32-bit elements of Rs1 with the 32-bit elements of Rs2 and writes the most significant 32-bit multiplication results to the corresponding 32-bit elements of Rd. The 32-bit elements of Rs1 and Rs2 are treated as signed integers. The .u form of the instruction rounds up the most significant 32-bit of the 64-bit multiplication results by adding a 1 to bit 31 of the results.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
```

(continues on next page)

(continued from previous page)

```
  res = (aop s* bop)[63:32];
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DSMMUL_U (unsigned long long a, unsigned long long b)

DSMMULU (64-bit MSW 32x32 Unsigned Multiply)

Type: SIMD

Syntax:

```
DSMMUL.U Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do MSW 32x32 element unsigned multiplications simultaneously. The results are written into Rd.

Description :

This instruction multiplies the 32-bit elements of Rs1 with the 32-bit elements of Rs2 and writes the most significant 32-bit multiplication results to the corresponding 32-bit elements of Rd. The 32-bit elements of Rs1 and Rs2 are treated as unsigned integers. The .u form of the instruction rounds up the most significant 32-bit of the 64-bit multiplication results by adding a 1 to bit 31 of the results.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  res = RUND(aop u* bop)[63:32];
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKWMMUL (unsigned long long a, unsigned long long b)

DKWMMUL (64-bit MSW 32x32 Signed Multiply & Double)

Type: SIMD

Syntax:

```
DKWMMUL Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do MSW 32x32 element signed multiplications simultaneously and double. The results are written into Rd.

Description :

This instruction multiplies the 32-bit elements of Rs1 with the 32-bit elements of Rs2. It then shifts the multiplication results one bit to the left and takes the most significant 32-bit results. If the shifted result is greater than 2^31-1, it is saturated to 2^31-1 and the OV flag is set to 1. The final element result is written to Rd. The 32-bit elements of Rs1 and Rs2 are treated as signed integers. The .u form of the instruction additionally rounds up the 64-bit multiplication results by adding a 1 to bit 30 before the shift and saturation operations.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
    res = sat.q31((aop s* bop) << 1)[63:32];
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

`__STATIC_FORCEINLINE unsigned long long __RV_DKWMMUL_U (unsigned long long a, unsigned long long b)`

DKWMMULU (64-bit MSW 32x32 Unsigned Multiply & Double)

Type: SIMD

Syntax:

```
DKWMMUL.U Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do MSW 32x32 element unsigned multiplications simultaneously and double. The results are written into Rd.

Description :

This instruction multiplies the 32-bit elements of Rs1 with the 32-bit elements of Rs2. It then shifts the multiplication results one bit to the left and takes the most significant 32-bit results. If the shifted result is greater than 2^31-1, it is saturated to 2^31-1 and the OV flag is set to 1. The final element result is written to Rd. The 32-bit elements of Rs1 and Rs2 are treated as signed integers. The .u form of the instruction additionally rounds up the 64-bit multiplication results by adding a 1 to bit 30 before the shift and saturation operations.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom
for ((aop,bop,res) in [(op1t,op2t,rest), (op1b,op2b,resb)]) {
  res = sat.q31(RUND(aop u* bop) << 1)[63:32];
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKABS32 (unsigned long long a)

DKABS32 (64-bit SIMD 32-bit Saturating Absolute)

Type: SIMD

Syntax:

```
DKABS32 Rd, Rs1
# Rd, Rs1 are all even/odd pair of registers
```

Purpose :

Get the absolute value of 32-bit signed integer elements simultaneously.

Description :

This instruction calculates the absolute value of 32-bit signed integer elements stored in Rs1 and writes the element results to Rd. If the input number is 0x8000_0000, this instruction generates 0x7fff_ffff as the output and sets the OV bit to 1.

Operations:

```
src = Rs1.W[x];
if (src == 0x8000_0000) {
  src = 0x7fff_ffff;
  OV = 1;
} else if (src[31] == 1)
  src = -src;
}
Rd.W[x] = src;
x=1...0
```

Parameters **a** – **[in]** unsigned long long type of value stored in a

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKSLRA32 (unsigned long long a, int b)

DKSLRA32 (64-bit SIMD 32-bit Shift Left Logical with Saturation or Shift Right Arithmetic)

Type: SIMD

Syntax:

```
DKSLRA32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 31-bit elements logical left (positive) or arithmetic right (negative) shift operation with Q31 saturation for the left shift.

Description :

The 31-bit data elements of Rs1 are left-shifted logically or right-shifted arithmetically based on the value of Rs2[5:0]. Rs2[5:0] is in the signed range of [-2^5, 2^5-1]. A positive Rs2[5:0] means logical left shift and a negative Rs2[4:0] means arithmetic right shift. The shift amount is the absolute value of Rs2[5:0]. However, the behavior of Rs2[5:0]==- 2^5 (0x20) is defined to be equivalent to the behavior of Rs2[5:0]==-(2^5-1) (0x21).

Operations:

```
if (Rs2[5:0] < 0) {
  sa = -Rs2[5:0];
  sa = (sa == 32)? 31 : sa;
  Rd.W[x] = SE32(Rs1.W[x][31:sa]);
} else {
  sa = Rs2[4:0];
  res[(31+sa):0] = Rs1.W[x] <<(logic) sa;
  if (res > (2^31)-1) {
  res[31:0] = 0x7fff_ffff; OV = 1;
} else if (res < -2^31) {
  res[31:0] = 0x8000_0000; OV = 1;
}
  Rd.W[x] = res[31:0];
}
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** int type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKADD32 (unsigned long long a, unsigned long long b)

DKADD32(64-bit SIMD 32-bit Signed Saturating Addition)

Type: SIMD

Syntax:

```
DKADD32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 32-bit signed integer element saturating additions simultaneously.

Description :

This instruction adds the 32-bit signed integer elements in Rs1 with the 32-bit signed integer elements in Rs2. If any of the results are beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.W[x] + Rs2.W[x];
if (res[x] > 0x7fff_ffff) {
  res[x] = 0x7fff_ffff;
  OV = 1;
} else if (res[x] < 0x8000_0000) {
  res[x] = 0x8000_0000;
  OV = 1;
}
Rd.W[x] = res[x];
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKSUB32 (unsigned long long a, unsigned long long b)

DKSUB32 (64-bit SIMD 32-bit Signed Saturating Subtraction)

Type: SIMD

Syntax:

```
DKSUB32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 32-bit signed integer element saturating subtractions simultaneously.

Description :

This instruction subtracts the 32-bit signed integer elements in Rs2 from the 32-bit signed integer elements in Rs1. If any of the results are beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to Rd.

Operations:

```
res[x] = Rs1.W[x] - Rs2.W[x];
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res[x] < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[x] = res[x];
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DRADD16 (unsigned long long a, unsigned long long b)

DRADD16 (64-bit SIMD 16-bit Halving Signed Addition)

Type: SIMD

Syntax:

```
DRADD16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 16-bit signed integer element additions simultaneously. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 16-bit signed integer elements in Rs1 with the 16-bit signed integer elements in Rs2. The results are first arithmetically right-shifted by 1 bit and then written to Rd.

Operations:

```
Rd.H[x] = [(Rs1.H[x]) + (Rs2.H[x])] s>> 1;
x=3...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DSUB16 (unsigned long long a, unsigned long long b)

DSUB16 (64-bit SIMD 16-bit Halving Signed Subtraction)

Type: SIMD

Syntax:

```
DSUB16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 16-bit integer element subtractions simultaneously.

Description :

This instruction adds the 16-bit signed integer elements in Rs1 with the 16-bit signed integer elements in Rs2. The results are first arithmetically right-shifted by 1 bit and then written to Rd.

Operations:

```
Rd.H[x] = [(Rs1.H[x]) - (Rs2.H[x])] ;
x=3...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DRADD32 (unsigned long long a, unsigned long long b)

DRADD32 (64-bit SIMD 32-bit Halving Signed Addition)

Type: SIMD

Syntax:

```
DRADD32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 32-bit signed integer element additions simultaneously. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 32-bit signed integer elements in Rs1 with the 32-bit signed integer elements in Rs2. The results are first arithmetically right-shifted by 1 bit and then written to Rd.

Operations:

```
Rd.W[x] = [(Rs1.W[x]) + (Rs2.W[x])] s>> 1;
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DSUB32 (unsigned long long a, unsigned long long b)

DSUB32 (64-bit SIMD 32-bit Halving Signed Subtraction)

Type: SIMD

Syntax:

```
DSUB32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 32-bit integer element subtractions simultaneously.

Description :

This instruction subtracts the 32-bit signed integer elements in Rs2 from the 32-bit signed integer elements in Rs1 . The results are written to Rd.

Operations:

```
Rd.W[x] = [(Rs1.E[x]) - (Rs2.E[x])] ;
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DMSR16 (unsigned long a, unsigned long b)

DMSR16 (Signed Multiply Halfs with Right Shift 16-bit and Cross Multiply Halfs with Right Shift 16-bit)

Type: SIMD

Syntax:

```
DMSR16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do two signed 16-bit multiplications and cross multiplications from the 16-bit elements of two registers; and each multiplications performs a right shift operation.

Description :

For the DMSR16 instruction, multiply the top 16-bit Q15 content of 32-bit chunks in Rs1 with the top 16-bit Q15 content of 32-bit chunks in Rs2, multiply the bottom 16-bit Q15 content of 32-bit chunks in Rs1 with the bottom 16-bit Q15 content of 32-bit chunks in Rs2. At the same time, multiply the top 16-bit Q15 content of 32-bit chunks in Rs1 with the bottom16-bit Q15 content of 32-bit chunks in Rs2 and multiply the bottom16-bit Q15 content of 32-bit chunks in Rs1 with the top16-bit Q15 content of 32-bit chunks in Rs2. The Q31 results are then right-shifted 16-bits and clipped to Q15 values. The Q15 results are then written into Rd.

Operations:

```
Rd.H[0] = (Rs1.H[0] s* Rs2.H[0]) s>> 16
Rd.H[1] = (Rs1.H[1] s* Rs2.H[1]) s>> 16
Rd.H[2] = (Rs1.H[1] s* Rs2.H[0]) s>> 16
Rd.H[3] = (Rs1.H[0] s* Rs2.H[1]) s>> 16
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DMSR17 (unsigned long a, unsigned long b)

DMSR17 (Signed Multiply Halfs with Right Shift 17-bit and Cross Multiply Halfs with Right Shift 17-bit)

Type: SIMD

Syntax:

```
DMSR17 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do two signed 16-bit multiplications and cross multiplications from the 16-bit elements of two registers; and each multiplications performs a right shift operation.

Description :

For the DMSR17 instruction, multiply the top 16-bit Q15 content of 32-bit chunks in Rs1 with the top 16-bit Q15 content of 32-bit chunks in Rs2, multiply the bottom 16-bit Q15 content of 32-bit chunks in Rs1 with the bottom 16-bit Q15 content of 32-bit chunks in Rs2. At the same time, multiply the top 16-bit Q15 content of 32-bit chunks in Rs1 with the bottom 16-bit Q15 content of 32-bit chunks in Rs2 and multiply the bottom 16-bit Q15 content of 32-bit chunks in Rs1 with the top 16-bit Q15 content of 32-bit chunks in Rs2. The Q31 results are then right-shifted 17-bits and clipped to Q15 values. The Q15 results are then written into Rd.

Operations:

```
Rd.H[0] = (Rs1.H[0] s* Rs2.H[0]) s>> 17
Rd.H[1] = (Rs1.H[1] s* Rs2.H[1]) s>> 17
Rd.H[2] = (Rs1.H[1] s* Rs2.H[0]) s>> 17
Rd.H[3] = (Rs1.H[0] s* Rs2.H[1]) s>> 17
```

Parameters

- **a** – **[in]** unsigned long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DMSR33 (unsigned long long a, unsigned long long b)

DMSR33 (Signed Multiply with Right Shift 33-bit and Cross Multiply with Right Shift 33-bit)

Type: SIMD

Syntax:

```
DMSR33 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do two signed 32-bit multiplications from the 32-bit elements of two registers, and each multiplications performs a right shift operation.

Description :

For the `DMSR33` instruction, multiply the top 32-bit Q31 content of 64-bit chunks in Rs1 with the top 32-bit Q31 content of 64-bit chunks in Rs2. At the same time, multiply the bottom 32-bit Q31 content of 64bit chunks in Rs1 with the bottom 32-bit Q31 content of 64-bit. The Q64 results are then right-shifted 33-bits and clipped to Q31 values. The Q31 results are then written into Rd.

Operations:

```
Rd.W[0] = (Rs1.W[0] s* Rs2.W[0]) s>> 33
Rd.W[1] = (Rs1.W[1] s* Rs2.W[1]) s>> 33
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

`__STATIC_FORCEINLINE unsigned long long __RV_DMXSR33 (unsigned long long a, unsigned long long b)`

DMXSR33 (Signed Multiply with Right Shift 33-bit and Cross Multiply with Right Shift 33-bit)

Type: SIMD

Syntax:

```
DMXSR33 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do two signed 32-bit cross multiplications from the 32-bit elements of two registers, and each multiplications performs a right shift operation.

Description :

For the `DMXSR33` instruction, multiply the top 32-bit Q31 content of 64-bit chunks in Rs1 with the bottom 32-bit Q31 content of 64-bit chunks in Rs2. At the same time, multiply the bottom 32-bit Q31 content of 64-bit chunks in Rs1 with the top 32-bit Q31 content of 64-bit chunks in Rs2. The Q63 results are then right-shifted 33-bits and clipped to Q31 values. The Q31 results are then written into Rd.

Operations:

```
Rd.W[0] = (Rs1.W[0] s* Rs2.W[1]) s>> 33
Rd.W[1] = (Rs1.W[1] s* Rs2.W[0]) s>> 33
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long __RV_DREDAS16 (unsigned long long a)

DREDAS16 (Reduced Addition and Reduced Subtraction)

Type: SIMD

Syntax:

```
DREDAS16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do halfs reduced subtraction and halfs reduced addition from a register. The result is written to Rd.

Description :

For the DREDAS16 instruction, subtract the top 16-bit Q15 element from the bottom 16-bit Q15 element of the bottom 32-bit Q31 content of 64-bit chunks in Rs1. At the same time, add the the top16-bit Q15 element with the bottom16-bit Q15 element of the top 32-bit Q31 content of 64-bit chunks in Rs1. The two Q15 results are then written into Rd.

Operations:

```
Rd.H[0] = Rs1.H[0] - Rs1.H[1]
Rd.H[1] = Rs1.H[2] + Rs1.H[3]
```

Parameters **a** – **[in]** unsigned long long type of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE unsigned long __RV_DREDSA16 (unsigned long long a)

DREDSA16 (Reduced Subtraction and Reduced Addition)

Type: SIMD

Syntax:

```
DREDSA16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do halfs reduced subtraction and halfs reduced addition from a register. The result is written to Rd.

Description :

For the DREDSA16 instruction, add the top 16-bit Q15 element from the bottom 16-bit Q15 element of the bottom 32-bit Q31 content of 64-bit chunks in Rs1. At the same time, subtract the the top16-bit Q15 element with the bottom16-bit Q15 element of the top 32-bit Q31 content of 64-bit chunks in Rs1. The two Q15 results are then written into Rd.

Operations:

```
Rd.H[0] = Rs1.H[0] + Rs1.H[1]
Rd.H[1] = Rs1.H[2] - Rs1.H[3]
```

Parameters a – **[in]** unsigned long longtype of value stored in a

Returns value stored in unsigned long type

__STATIC_FORCEINLINE int16_t __RV_DKCLIP64 (unsigned long long a)

DKCLIP64 (64-bit Clipped to 16-bit Saturation Value)

Type: SIMD

Syntax:

```
DKCLIP64 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 15-bit element arithmetic right shift operations and limit result into 32-bit int,then do saturate operation to 16-bit and clip result to 16-bit Q15.

Description :

For the DKCLIP64 instruction, shift the input 15 bits to the right and data convert the result to 32-bit int type, after which the input is saturated to limit the data to between 2^15-1 and -2^15. the result is converted to 16-bits q15 type. The final results are written to Rd.

Operations:

```
const int32_t max = (int32_t)((1U << 15U) - 1U);
const int32_t min = -1 - max ;
int32_t val = (int32_t)(Rs s>> 15);
if (val > max) {
  Rd = max;
} else if (val < min) {
  Rd = min;
} else {
  Rd = (int16_t)val;
}
```

Parameters a – **[in]** unsigned long long type of value stored in a

Returns value stored in int16_t type

__STATIC_FORCEINLINE unsigned long long __RV_DKMDA (unsigned long long a, unsigned long long b)

DKMDA (Signed Multiply Two Halfs and Add)

Type: SIMD

Syntax:

```
DKMDA Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then adds the two 32-bit results together. The addition result may be saturated.

Description :

This instruction multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and then adds the result to the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. The addition result is checked for saturation. If saturation happens, the result is saturated to 2^31-1 The final results are written to Rd. The 16-bit contents are treated as signed integers

Operations:

```
if (Rs1.W[x] != 0x80008000) or (Rs2.W[x] != 0x80008000){
  Rd.W[x] = (Rs1.W[x].H[1] * Rs2.W[x].H[1]) + (Rs1.W[x].H[0] * Rs2.W[x].H[0]);
} else {
  Rd.W[x] = 0x7fffffff;
  OV = 1;
}
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKMXDA (unsigned long long a, unsigned long long b)

DKMXDA (Signed Crossed Multiply Two Halfs and Add)

Type: SIMD

Syntax:

```
DKMXDA Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then adds the two 32-bit results together. The addition result may be saturated.

- DKMXDA: top*bottom + top*bottom (per 32-bit element)

Description :

This instruction multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then adds the result to the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. The addition result is checked for saturation.If saturation happens, the result is saturated to 2^31-1 The final results are written to Rd. The 16-bit contents are treated as signed integers.

Operations:

```
if (Rs1.W[x] != 0x80008000) or (Rs2.W[x] != 0x80008000){
Rd.W[x] = (Rs1.W[x].H[1] * Rs2.W[x].H[0]) + (Rs1.W[x].H[0] * Rs2.W[x].H[1]);
} else {
Rd.W[x] = 0x7fffffff;
OV = 1;
}
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DSMDRS (unsigned long long a, unsigned long long b)

DSMDRS (Signed Multiply Two Halfs and Reverse Subtract)

Type: SIMD

Syntax:

```
DSMDRS Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then perform a subtraction operation between the two 32-bit results.

- DSMDRS: bottom*bottom - top*top (per 32-bit element)

Description :

This instruction multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. The subtraction result is written to the corresponding 32-bit element of Rd (The 16-bit contents of multiplication are treated as signed integers).

Operations:

```
Rd.W[x] = (Rs1.W[x].H[0] * Rs2.W[x].H[0]) - (Rs1.W[x].H[1] * Rs2.W[x].H[1]); x␣
↪= 1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DSMXDS (unsigned long long a, unsigned long long b)

DSMXDS (Signed Crossed Multiply Two Halfs and Subtract)

Type: SIMD

Syntax:

```
DSMXDS Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications from the 32-bit elements of two registers; and then perform a subtraction operation between the two 32-bit results.

- DSMXDS: top*bottom - bottom*top (per 32-bit element)

Description :

This instruction multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. The subtraction result is written to the corresponding 32-bit element of Rd. The 16-bit contents of multiplication are treated as signed integers.

Operations:

```
Rd.W[x] = (Rs1.W[x].H[1] * Rs2.W[x].H[0]) - (Rs1.W[x].H[0] * Rs2.W[x].H[1]); x␣
↪= 1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE long long __RV_DSMBB32 (unsigned long long a, unsigned long long b)

DSMBB32 (Signed Multiply Bottom Word & Bottom Word)

Type: SIMD

Syntax:

```
DSMBB32 Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit element of a register with the signed 32-bit element of another register and write the 64-bit result to a third register.

- DSMBB32: bottom*bottom

Description :

This instruction multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2. The 64-bit multiplication result is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = (Rs1.W[0] * Rs2.W[0]);
Rd = res;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMBB32_SRA14 (unsigned long long a, unsigned long long b)

DSMBB32.sra14 (Signed Crossed Multiply Two Halfs and Subtract with Right Shift 14)

Type: SIMD

Syntax:

```
DSMBB32.sra14 Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit element of a register with the signed 32-bit element of another register, then right shift 14- bit,finally write the 64-bit result to a third register.

- DSMBB32.SRL14: bottom*bottom s>> 14

Description :

This instruction multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2. The 64-bit multiplication result is written to Rd after right shift 14-bit. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = (Rs1.W[0] * Rs2.W[0]) s>> 14;
Rd = res;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMBB32_SRA32 (unsigned long long a, unsigned long long b)

DSMBB32.sra32 (Signed Crossed Multiply Two Halfs and Subtract with Right Shift 32)

Type: SIMD

Syntax:

```
DSMBB32.sra32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Multiply the signed 32-bit element of a register with the signed 32-bit element of another register, then right shift 32- bit,finally write the 64-bit result to a third register.

- DSMBB32.SRL32: bottom*bottom s >> 32

Description :

This instruction multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2. The 64-bit multiplication result is written to Rd after right shift 32-bit. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = (Rs1.W[0] * Rs2.W[0]) s>> 32;
Rd = res;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

`__STATIC_FORCEINLINE long long __RV_DSMBT32 (unsigned long long a, unsigned long long b)`

SMBT32 (Signed Multiply Bottom Word & Top Word)

Type: SIMD

Syntax:

```
DSMBT32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Multiply the signed 32-bit element of a register with the signed 32-bit element of another register and write the 64-bit result to a third register.

- DSMBT32: bottom*top

Description :

This instruction multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2. The 64-bit multiplication result is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = (Rs1.W[0] * Rs2.W[0]);
Rd = res;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

`__STATIC_FORCEINLINE long long __RV_DSMBT32_SRA14 (unsigned long long a, unsigned long long b)`

DSMBT32.sra14 (Signed Multiply Bottom Word & Top Word with Right Shift 14)

Type: SIMD

Syntax:

```
DSMBT32.sra14 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Multiply the signed 32-bit element of a register with the signed 32-bit element of another register, then right shift 14- bit,finally write the 64-bit result to a third register.

- DSMBT32.SRL14: bottom*bottom s>> 14

Description :

This instruction multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2. The 64-bit multiplication result is written to Rd after right shift 14-bit. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = (Rs1.W[0] * Rs2.W[0]) s>> 14;
Rd = res;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMBT32_SRA32 (unsigned long long a, unsigned long long b)

DSMBT32.sra32 (Signed Crossed Multiply Two Halfs and Subtract with Right Shift 32)

Type: SIMD

Syntax:

```
DSMBT32.sra32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Multiply the signed 32-bit element of a register with the signed 32-bit element of another register, then right shift 32- bit,finally write the 64-bit result to a third register.

- DSMBT32.SRL32: bottom*bottom s>> 32

Description :

This instruction multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2. The 64-bit multiplication result is written to Rd after right shift 32-bit. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = (Rs1.W[0] * Rs2.W[0]) s>> 14;
Rd = res;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMTT32 (unsigned long long a, unsigned long long b)

DSMTT32 (Signed Multiply Top Word & Top Word)

Type: SIMD

Syntax:

```
DSMTT32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Multiply the signed 32-bit element of a register with the signed 32-bit element of another register and write the 64-bit result to a third register.

- DSMTT32: top*top

Description :

This instruction multiplies the top 32-bit element of Rs1 with the top 32-bit element of Rs2. The 64-bit multiplication result is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rs1.W[1] * Rs2.W[1];
Rd = res;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMTT32_SRA14 (unsigned long long a, unsigned long long b)

DSMTT32.sra14 (Signed Multiply Top Word & Top Word with Right Shift 14-bit)

Type: SIMD

Syntax:

```
DSMTT32.sra14 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Multiply the signed 32-bit element of a register with the signed 32-bit element of another register,then right shift 14-bit, finally write the 64-bit result to a third register.

- DSMTT32.SRL14: top*top s>> 14

Description :

This instruction multiplies the top 32-bit element of Rs1 with the top 32-bit element of Rs2. The 64-bit multiplication result is written to Rd after right shift 14-bit. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rs1.W[1] * Rs2.W[1] >> 14;
Rd = res;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMTT32_SRA32 (unsigned long long a, unsigned long long b)

DSMTT32.sra32 (Signed Multiply Top Word & Top Word with Right Shift 32-bit)

Type: SIMD

Syntax:

```
DSMTT32.sra32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Multiply the signed 32-bit element of a register with the signed 32-bit element of another register,then right shift 32-bit, finally write the 64-bit result to a third register.

- DSMTT32.SRL14: top*top s>> 32

Description :

This instruction multiplies the top 32-bit element of Rs1 with the top 32-bit element of Rs2. The 64-bit multiplication result is written to Rd after right shift 32-bit. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rs1.W[1] * Rs2.W[1] >> 32;
Rd = res;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE unsigned long long __RV_DPKBB32 (unsigned long long a, unsigned long long b)

DPKBB32 (Pack Two 32-bit Data from Both Bottom Half)

Type: SIMD

Syntax:

```
DPKBB32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Pack 32-bit data from 64-bit chunks in two registers.

- DPKBB32: bottom.bottom

Description :

This instruction moves Rs1.W[0] to Rd.W[1] and moves Rs2.W[0] to Rd.W[0].

Operations:

```
Rd = CONCAT(Rs1.W[0], Rs2.W[0]);
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DPKBT32 (unsigned long long a, unsigned long long b)

DPKBT32 (Pack Two 32-bit Data from Bottom and Top Half)

Type: SIMD

Syntax:

```
DPKBT32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Pack 32-bit data from 64-bit chunks in two registers.

- DPKBT32: bottom.top

Description :

This instruction moves Rs1.W[0] to Rd.W[1] and moves Rs2.W[1] to Rd.W[0].

Operations:

```
Rd = CONCAT(Rs1.W[0], Rs2.W[1]);
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DPKTT32 (unsigned long long a, unsigned long long b)

DPKTT32 (Pack Two 32-bit Data from Both Top Half)

Type: SIMD

Syntax:

```
DPKTT32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Pack 32-bit data from 64-bit chunks in two registers.

- DPKTT32: top.top

Description :

This instruction moves Rs1.W[1] to Rd.W[0] and moves Rs2.W[1] to Rd.W[0].

Operations:

```
Rd = CONCAT(Rs1.W[1], Rs2.W[1]);
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DPKTB32 (unsigned long long a, unsigned long long b)

DPKTB32 (Pack Two 32-bit Data from Top and Bottom Half)

Type: SIMD

Syntax:

```
DPKTB32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Pack 32-bit data from 64-bit chunks in two registers.

- DPKTB32: top.bottom

Description :

This instruction moves Rs1.W[1] to Rd.W[1] and moves Rs2.W[0] to Rd.W[0].

Operations:

```
Rd = CONCAT(Rs1.W[1], Rs2.W[0]);
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a

- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DPKTB16 (unsigned long long a, unsigned long long b)

DPKTB16 (Pack Two 32-bit Data from Top and Bottom Half)

Type: SIMD

Syntax:

```
DPKTB16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Pack 16-bit data from 32-bit chunks in two registers.

- DPKTB16: top.bottom

Description :

This instruction moves Rs1.W[x] [31:16] to Rd.W[x] [31:16] and moves Rs2.W[x] [15:0] to Rd.W[x] [15:0].

Operations:

```
Rd.W[x][31:0] = CONCAT(Rs1.W[x][31:16], Rs2.W[x][15:0]);
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DPKBB16 (unsigned long long a, unsigned long long b)

DPKBB16 (Pack Two 16-bit Data from Both Bottom Half)

Type: SIMD

Syntax:

```
DPKBB16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Pack 16-bit data from 32-bit chunks in two registers.

- PKBB16: bottom.bottom

Description :

This instruction moves Rs1.W[x][15:0] to Rd.W[x][31:16] and moves Rs2.W[x] [15:0] to Rd.W[x] [15:0].

Operations:

```
Rd.W[x][31:0] = CONCAT(Rs1.W[x][15:0], Rs2.W[x][15:0]);
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DPKBT16 (unsigned long long a, unsigned long long b)

DPKBT16 (Pack Two 16-bit Data from Bottom and Top Half)

Type: SIMD

Syntax:

```
DPKBT16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Pack 16-bit data from 32-bit chunks in two registers.

- PKBT16: bottom.top

Description :

This instruction moves Rs1.W[x] [15:0] to Rd.W[x] [31:16] and moves Rs2.W[x] [31:16] to Rd.W[x] [15:0].

Operations:

```
Rd.W[x][31:0] = CONCAT(Rs1.W[x][15:0], Rs2.W[x][31:16]);
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DPKTT16 (unsigned long long a, unsigned long long b)

DPKTT16 (Pack Two 16-bit Data from Both Top Half)

Type: SIMD

Syntax:

```
DPKTT16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Pack 16-bit data from 32-bit chunks in two registers.

- PKTT16 top.top

Description :

This instruction moves Rs1.W[x] [31:16] to Rd.W[x] [31:16] and moves Rs2.W[x] [31:16] to Rd.W[x] [15:0].

Operations:

```
Rd.W[x][31:0] = CONCAT(Rs1.W[x][31:16], Rs2.W[x][31:16]);
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DSRA16 (unsigned long long a, unsigned long b)

DSRA16 (32-bit Signed Saturating Cross Addition & Subtraction)

Type: SIMD

Syntax:

```
DSRA16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 16-bit element arithmetic right shift operations simultaneously. The shift amount is a variable from a GPR.

Description :

The 16-bit data elements in Rs1 are right-shifted arithmetically, that is, the shifted out bits are filled with the sign-bit of the data elements. The shift amount is specified by the low-order 4-bits of the value in the Rs2 register. And the results are written to Rd.

Operations:

```
sa = Rs2[3:0];
if (sa != 0)
{
Rd.H[x] = SE16(Rs1.H[x][15:sa]);
} else {
Rd = Rs1;
}
x=3...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DADD16 (unsigned long long a, unsigned long long b)

DADD16 (16-bit Addition)

Type: SIMD

Syntax:

```
DADD16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 16-bit integer element additions simultaneously.

Description :

This instruction adds the 16-bit unsigned integer elements in Rs1 with the 16-bit unsigned integer elements in Rs2. And the results are written to Rd.

Operations:

```
Rd.H[x] = Rs1.H[x] + Rs2.H[x];
x=3...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DADD32 (unsigned long long a, unsigned long long b)

DADD32 (32-bit Addition)

Type: SIMD

Syntax:

```
DADD32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 32-bit integer element additions simultaneously.

Description :

This instruction adds the 32-bit integer elements in Rs1 with the 32-bit integer elements in Rs2, and then writes the 32-bit element results to Rd.

Operations:

```
Rd.W[x] = Rs1.W[x] + Rs2.W[x];
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DSMBB16 (unsigned long long a, unsigned long long b)

DSMBB16 (Signed Multiply Bottom Half & Bottom Half)

Type: SIMD

Syntax:

```
DSMBB16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Multiply the signed 16-bit content of the 32-bit elements of a register with the signed 16-bit content of the 32-bit elements of another register and write the result to a third register.

- DSMBB16: W[x].bottom*W[x].bottom

Description :

For the DSMBB16 instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2. The multiplication results are written to Rd. The 16-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
Rd.W[x] = Rs1.W[x].H[0] * Rs2.W[x].H[0];
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DSMBT16 (unsigned long long a, unsigned long long b)

DSMBT16 (Signed Multiply Bottom Half & Top Half)

Type: SIMD

Syntax:

```
DSMBT16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Multiply the signed 16-bit content of the 32-bit elements of a register with the signed 16-bit content of the 32-bit elements of another register and write the result to a third register.

- DSMBT16: W[x].bottom *W[x].top

Description :

For the DSMBT16 instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. The multiplication results are written to Rd. The 16-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
Rd.W[x] = Rs1.W[x].H[0] * Rs2.W[x].H[1];
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DSMTT16 (unsigned long long a, unsigned long long b)

DSMTT16 (Signed Multiply Top Half & Top Half)

Type: SIMD

Syntax:

```
DSMTT16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Multiply the signed 16-bit content of the 32-bit elements of a register with the signed 16-bit content of the 32-bit elements of another register and write the result to a third register.

- DSMTT16: W[x].top * W[x].top

Description :

For the DSMTT16 instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. The multiplication results are written to Rd. The 16-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
Rd.W[x] = Rs1.W[x].H[1] * Rs2.W[x].H[1];
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DRCRSA16 (unsigned long long a, unsigned long long b)

DRCRSA16 (16-bit Signed Halving Cross Subtraction & Addition)

Type: SIMD

Syntax:

```
DRCRSA16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 16-bit signed integer element subtraction and 16-bit signed integer element addition in a 32-bit chunk simultaneously. Operands are from crossed positions in 32-bit chunks. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 16-bit signed integer in [31:16] of 32-bit chunks in Rs1 with the 16-bit signed integer in [15:0] of 32-bit chunks in Rs2, and adds the 16-bit signed integer in [31:16] of 32-bit chunks in Rs2 from the 16-bit signed integer in [15:0] of 32-bit chunks in Rs1. The element results are first logically right-shifted by 1 bit and then written to [31:16] of 32- bit chunks in Rd and [15:0] of 32-bit chunks in Rd.

Operations:

```
Rd.W[x][31:16] = (Rs1.W[x][31:16] - Rs2.W[x][15:0]) s>> 1;
Rd.W[x][15:0] = (Rs1.W[x][15:0] + Rs2.W[x][31:16]) s>> 1;
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

`__STATIC_FORCEINLINE unsigned long long __RV_DRCRSA32 (unsigned long long a, unsigned long long b)`

DRCRSA32 (32-bit Signed Halving CrossSubtraction & Addition)

Type: SIMD

Syntax:

```
DRCRSA32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 32-bit signed integer element subtraction and 32-bit signed integer element addition in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 32-bit signed integer element in [63:32] of Rs1 with the 32-bit signed integer element in [31:0] of Rs2, and adds the 32-bit signed integer element in [63:32] of Rs2 from the 32-bit signed integer element in [31:0] of Rs1. The element results are first arithmetically right-shifted by 1 bit and then written to [63:32] of Rd for addition and [31:0] of Rd for subtraction.

Operations:

```
Rd.W[1] = (Rs1.W[1] - Rs2.W[0]) s>> 1;
Rd.W[0] = (Rs1.W[0] + Rs2.W[1]) s>> 1;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DRCRAS16 (unsigned long long a, unsigned long long b)

DRCRAS16 (16-bit Signed Halving Cross Addition & Subtraction)

Type: SIMD

Syntax:

```
DRCRAS16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 16-bit signed integer element subtraction and 16-bit signed integer element addition in a 32-bit chunk simultaneously. Operands are from crossed positions in 32-bit chunks. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 16-bit unsigned integer in [31:16] of 32-bit chunks in Rs1 with the 16-bit unsigned integer in [15:0] of 32-bit chunks in Rs2, and subtracts the 16-bit unsigned integer in [31:16] of 32-bit chunks in Rs2 from the 16-bit unsigned integer in [15:0] of 32-bit chunks in Rs1. The element results are first logically right-shifted by 1 bit and then written to [31:16] of 32-bit chunks in Rd and [15:0] of 32-bit chunks in Rd.

Operations:

```
Rd.W[x][31:16] = (Rs1.W[x][31:16] + Rs2.W[x][15:0]) s>> 1;
Rd.W[x][15:0] = (Rs1.W[x][15:0] - Rs2.W[x][31:16]) s>> 1;
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DRCRAS32 (unsigned long long a, unsigned long long b)

DRCRAS32 (32-bit Signed Cross Addition & Subtraction)

Type: SIMD

Syntax:

```
DRCRAS32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 32-bit signed integer element addition and 32-bit signed integer element subtraction in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements. The results are halved to avoid overflow or saturation.

Description :

This instruction adds the 32-bit signed integer element in [63:32] of Rs1 with the 32-bit signed integer element in [31:0] of Rs2, and subtracts the 32-bit signed integer element in [63:32] of Rs2 from the 32-bit signed integer element in [31:0] of Rs1. The element results are first arithmetically right-shifted by 1 bit and then written to [63:32] of Rd for addition and [31:0] of Rd for subtraction.

Operations:

```
Rd.W[1] = (Rs1.W[1] + Rs2.W[0]) s>> 1;
Rd.W[0] = (Rs1.W[0] - Rs2.W[1]) s>> 1;
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKCRAS16 (unsigned long long a, unsigned long long b)

DKCRAS16 (16-bit Signed Saturating Cross Addition & Subtraction)

Type: SIMD

Syntax:

```
DKCRAS16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 16-bit signed integer element saturating addition and 16-bit signed integer element saturating subtraction in a 32-bit chunk simultaneously. Operands are from crossed positions in 32-bit chunks.

Description :

This instruction adds the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs1 with the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs2; at the same time, it subtracts the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs2 from the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs1. If any of the results are beyond the Q15 number range (-2^15 <= Q15 <= 2^15-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [31:16] of 32-bit chunks in Rd for subtraction and [15:0] of 32-bit chunks in Rd for addition.

Operations:

```
res1 = Rs1.W[x][31:16] - Rs2.W[x][15:0];
res2 = Rs1.W[x][15:0] + Rs2.W[x][31:16];
for (res in [res1, res2]) {
  if (res > (2^15)-1) {
    res = (2^15)-1;
    OV = 1;
  } else if (res < -2^15) {
    res = -2^15;
```

(continues on next page)

(continued from previous page)

```
    OV = 1;
  }
}
Rd.W[x][31:16] = res1;
Rd.W[x][15:0] = res2;
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKCRSA16 (unsigned long long a, unsigned long long b)

DKCRSA16 (16-bit Signed Saturating Cross Subtraction & Addition)

Type: SIMD

Syntax:

```
DKCRSA16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 16-bit signed integer element saturating subtraction and 16-bit signed integer element saturating addition in a 32-bit chunk simultaneously. Operands are from crossed positions in 32-bit chunks.

Description :

This instruction subtracts the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs2 from the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs1; at the same time, it adds the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs2 with the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs1. If any of the results are beyond the Q15 number range (-2^15 <= Q15 <= 2^15-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [31:16] of 32-bit chunks in Rd for addition and [15:0] of 32-bit chunks in Rd for subtraction.

Operations:

```
res1 = Rs1.W[x][31:16] + Rs2.W[x][15:0];
res2 = Rs1.W[x][15:0] - Rs2.W[x][31:16];
for (res in [res1, res2]) {
  if (res > (2^15)-1) {
    res = (2^15)-1;
    OV = 1;
  } else if (res < -2^15) {
    res = -2^15;
    OV = 1;
  }
}
Rd.W[x][31:16] = res1;
Rd.W[x][15:0] = res2;
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DRSUB16 (unsigned long long a, unsigned long long b)

DRSUB16 (16-bit Signed Halving Subtraction)

Type: SIMD

Syntax:

```
DRSUB16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 16-bit signed integer element subtractions simultaneously. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 16-bit signed integer elements in Rs2 from the 16-bit signed integer elements in Rs1. The results are first arithmetically right-shifted by 1 bit and then written to Rd.

Operations:

```
Rd.H[x] = (Rs1.H[x] - Rs2.H[x]) s>> 1;
x=3...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DSTSA32 (unsigned long long a, unsigned long long b)

DSTSA32 (32-bit Straight Subtraction & Addition)

Type: SIMD

Syntax:

```
DSTSA32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 32-bit integer element subtraction and 32-bit integer element addition in a 64-bit chunk simultaneously. Operands are from corresponding 32-bit elements.

Description :

This instruction subtracts the 32-bit integer element in [63:32] of Rs2 from the 32-bit integer element in [63:32] of Rs1, and writes the result to [63:32] of Rd; at the same time, it adds the 32-bit integer element in [31:0] of Rs1 with the 32-bit integer element in [31:0] of Rs2, and writes the result to [31:0] of Rd.

Operations:

```
Rd.W[1] = Rs1.W[1] - Rs2.W[1];
Rd.W[0] = Rs1.W[0] + Rs2.W[0];
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DSTAS32 (unsigned long long a, unsigned long long b)

DSTAS32 (SIMD 32-bit Straight Addition & Subtractionn)

Type: SIMD

Syntax:

```
DSTAS32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 32-bit integer element addition and 32-bit integer element subtraction in a 64-bit chunk simultaneously. Operands are from corresponding 32-bit elements.

Description :

This instruction adds the 32-bit integer element in [63:32] of Rs1 with the 32-bit integer element in [63:32] of Rs2, and writes the result to [63:32] of Rd; at the same time, it subtracts the 32-bit integer element in [31:0] of Rs2 from the 32-bit integer element in [31:0] of Rs1, and writes the result to [31:0] of Rd.

Operations:

```
Rd.W[1] = Rs1.W[1] + Rs2.W[1];
Rd.W[0] = Rs1.W[0] - Rs2.W[0];
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKCRSA32 (unsigned long long a, unsigned long long b)

DKCRSA32 (32-bit Signed Saturating Cross Subtraction & Addition)

Type: SIMD

Syntax:

```
DKCRSA32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 32-bit signed integer element saturating subtraction and 32-bit signed integer element saturating addition in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements.

Description :

This instruction subtracts the 32-bit integer element in [31:0] of Rs2 from the 32-bit integer element in [63:32] of Rs1; at the same time, it adds the 32-bit integer element in [31:0] of Rs1 with the 32-bit integer element in [63:32] of Rs2. If any of the results are beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [63:32] of Rd for subtraction and [31:0] of Rd for addition.

Operations:

```
res[1] = Rs1.W[1] - Rs2.W[0];
res[0] = Rs1.W[0] + Rs2.W[1];
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[1] = res[1];
Rd.W[0] = res[0];
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKCRAS32 (unsigned long long a, unsigned long long b)

DKCRAS32 (32-bit Signed Saturating Cross Addition & Subtraction)

Type: SIMD

Syntax:

```
DKCRAS32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 32-bit signed integer element saturating subtraction and 32-bit signed integer element saturating addition in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements.

Description :

This instruction adds the 32-bit integer element in [31:0] of Rs2 from the 32-bit integer element in [63:32] of Rs1; at the same time, it subtracts the 32-bit integer element in [31:0] of Rs1 with the 32-bit integer element in [63:32] of Rs2. If any of the results are beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [63:32] of Rd for subtraction and [31:0] of Rd for addition.

Operations:

```
res[1] = Rs1.W[1] + Rs2.W[0];
res[0] = Rs1.W[0] - Rs2.W[1];
if (res[x] > (2^31)-1) {
  res[x] = (2^31)-1;
  OV = 1;
} else if (res < -2^31) {
  res[x] = -2^31;
  OV = 1;
}
Rd.W[1] = res[1];
Rd.W[0] = res[0];
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DCRSA32 (unsigned long long a, unsigned long long b)

DCRSA32 (32-bit Cross Subtraction & Addition)

Type: SIMD

Syntax:

```
DCRSA32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 32-bit integer element subtraction and 32-bit integer element addition in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements.

Description :

This instruction adds the 32-bit integer element in [63:32] of Rs1 with the 32-bit integer element in [31:0] of Rs2, and writes the result to [63:32] of Rd; at the same time, it subtracts the 32-bit integer element in [63:32] of Rs2 from the 32-bit integer element in [31:0] of Rs1, and writes the result to [31:0] of Rd.

Operations:

```
res[1] = Rs1.W[1] - Rs2.W[0];
res[0] = Rs1.W[0] + Rs2.W[1];
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DCRAS32 (unsigned long long a, unsigned long long b)

DCRAS32 (32-bit Cross Addition & Subtraction)

Type: SIMD

Syntax:

```
DCRAS32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 32-bit integer element addition and 32-bit integer element subtraction in a 64-bit chunk simultaneously. Operands are from crossed 32-bit elements.

Description :

This instruction subtracts the 32-bit integer element in [63:32] of Rs1 with the 32-bit integer element in [31:0] of Rs2, and writes the result to [63:32] of Rd; at the same time, it adds the 32-bit integer element in [63:32] of Rs2 from the 32-bit integer element in [31:0] of Rs1, and writes the result to [31:0] of Rd.

Operations:

```
res[1] = Rs1.W[1] - Rs2.W[0];
res[0] = Rs1.W[0] + Rs2.W[1];
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKSTSA16 (unsigned long long a, unsigned long long b)

DKSTSA16 (16-bit Signed Saturating Straight Subtraction & Addition)

Type: SIMD

Syntax:

```
DKSTSA16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 16-bit signed integer element saturating subtraction and 16-bit signed integer element saturating addition in a 32-bit chunk simultaneously. Operands are from corresponding positions in 32-bit chunks.

Description :

This instruction subtracts the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs2 from the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs1; at the same time, it adds the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs2 with the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs1. If any of the results are beyond the Q15 number range (-2^15 <= Q15 <= 2^15-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [31:16] of 32-bit chunks in Rd for subtraction and [15:0] of 32-bit chunks in Rd for addition.

Operations:

```
res1 = Rs1.W[x][31:16] - Rs2.W[x][31:16];
res2 = Rs1.W[x][15:0] + Rs2.W[x][15:0];
for (res in [res1, res2]) {
  if (res > (2^15)-1) {
    res = (2^15)-1;
    OV = 1;
  } else if (res < -2^15) {
    res = -2^15;
    OV = 1;
  }
}
Rd.W[x][31:16] = res1;
Rd.W[x][15:0] = res2;
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKSTAS16 (unsigned long long a, unsigned long long b)

DKSTAS16 (16-bit Signed Saturating Straight Addition & Subtraction)

Type: SIMD

Syntax:

```
DKSTAS16 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 16-bit signed integer element saturating addition and 16-bit signed integer element saturating subtraction in a 32-bit chunk simultaneously. Operands are from corresponding positions in 32-bit chunks.

Description :

This instruction adds the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs1 with the 16-bit signed integer element in [31:16] of 32-bit chunks in Rs2; at the same time, it subtracts the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs2 from the 16-bit signed integer element in [15:0] of 32-bit chunks in Rs1. If any of the results are beyond the Q15 number range (-2^15 <= Q15 <= 2^15-1), they are saturated to the range and the OV bit is set to 1. The saturated results are written to [31:16] of 32-bit chunks in Rd for subtraction and [15:0] of 32-bit chunks in Rd for addition.

Operations:

```
res1 = Rs1.W[x][31:16] + Rs2.W[x][31:16];
res2 = Rs1.W[x][15:0] - Rs2.W[x][15:0];
for (res in [res1, res2]) {
  if (res > (2^15)-1) {
    res = (2^15)-1;
```

(continues on next page)

(continued from previous page)

```
    OV = 1;
  } else if (res < -2^15) {
    res = -2^15;
    OV = 1;
  }
}
Rd.W[x][31:16] = res1;
Rd.W[x][15:0] = res2;
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DRSUB32 (unsigned long long a, unsigned long long b)

DRSUB32 (32-bit Signed Halving Subtraction)

Type: SIMD

Syntax:

```
DRSUB32 Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do 32-bit signed integer element subtractions simultaneously. The results are halved to avoid overflow or saturation.

Description :

This instruction subtracts the 32-bit signed integer elements in Rs2 from the 32-bit signed integer elements in Rs1. The results are first arithmetically right-shifted by 1 bit and then written to Rd.

Operations:

```
Rd.W[x] = (Rs1.W[x] - Rs2.W[x]) s>> 1;
x=1...0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

group **NMSIS_Core_DSP_Intrinsic_NUCLEI_N3**

(RV32 only)Nuclei Customized N3 DSP Instructions

This is Nuclei customized DSP N3 instructions only for RV32

Functions

__STATIC_FORCEINLINE unsigned long long __RV_DKMMAC (unsigned long long t, unsigned long long a, unsigned long long b)

DKMMAC (64-bit MSW 32x32 Signed Multiply and Saturating Add)

Type: SIMD

Syntax:

```
DKMMAC Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do MSW 32x32 element signed multiplications and saturating addition simultaneously. The results are written into Rd.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the signed 32-bit elements of Rs2 and adds the most significant 32-bit multiplication results with the signed 32-bit elements of Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to Rd. The .u form of the instruction additionally rounds up the most significant 32-bit of the 64-bit multiplication results by adding a 1 to bit 31 of the results.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; op3t = Rd.W[x+1] // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; op3b = Rd.W[x] // bottom
for ((aop,bop,dop,res) in [(op1t,op2t,op3t,rest), (op1b,op2b,op3b,resb)]) {
   res = sat.q31(dop + (aop s* bop)[63:32]);
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKMMAC_U (unsigned long long t, unsigned long long a, unsigned long long b)

DKMMACU (64-bit MSW 32x32 Unsigned Multiply and Saturating Add)

Type: SIMD

Syntax:

```
DKMMACU Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do MSW 32x32 element unsigned multiplications and saturating addition simultaneously. The results are written into Rd.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the signed 32-bit elements of Rs2 and adds the most significant 32-bit multiplication results with the signed 32-bit elements of Rd. If the addition result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to Rd. The .u form of the instruction additionally rounds up the most significant 32-bit of the 64-bit multiplication results by adding a 1 to bit 31 of the results.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; op3t = Rd.W[x+1] // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; op3b = Rd.W[x] // bottom
for ((aop,bop,dop,res) in [(op1t,op2t,op3t,rest), (op1b,op2b,op3b,resb)]) {
  res = sat.q31(dop + RUND(aop u* bop)[63:32]);
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKMMSB (unsigned long long t, unsigned long long a, unsigned long long b)

DKMMSB (64-bit MSW 32x32 Signed Multiply and Saturating Sub)

Type: SIMD

Syntax:

```
DKMMSB Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do MSW 32x32 element signed multiplications and saturating subtraction simultaneously. The results are written into Rd.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the signed 32-bit elements of Rs2 and subtracts the most significant 32-bit multiplication results from the signed 32-bit elements of Rd. If the subtraction result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to Rd. The .u form of the instruction additionally rounds up the most significant 32-bit of the 64-bit multiplication results by adding a 1 to bit 31 of the results.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; op3t = Rd.W[x+1] // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; op3b = Rd.W[x] // bottom
for ((aop,bop,dop,res) in [(op1t,op2t,op3t,rest), (op1b,op2b,op3b,resb)]) {
   res = sat.q31(dop - (aop s* bop)[63:32]);
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKMMSB_U (unsigned long long t, unsigned long long a, unsigned long long b)

DKMMSBU (64-bit MSW 32x32 Unsigned Multiply and Saturating Sub)

Type: SIMD

Syntax:

```
DKMMSBU Rd, Rs1, Rs2
# Rd, Rs1, Rs2 are all even/odd pair of registers
```

Purpose :

Do MSW 32x32 element unsigned multiplications and saturating subtraction simultaneously. The results are written into Rd.

Description :

This instruction multiplies the signed 32-bit elements of Rs1 with the signed 32-bit elements of Rs2 and subtracts the most significant 32-bit multiplication results from the signed 32-bit elements of Rd. If the subtraction result is beyond the Q31 number range (-2^31 <= Q31 <= 2^31-1), it is saturated to the range and the OV bit is set to 1. The results after saturation are written to Rd. The .u form of the instruction additionally rounds up the most significant 32-bit of the 64-bit multiplication results by adding a 1 to bit 31 of the results.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; op3t = Rd.W[x+1] // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; op3b = Rd.W[x] // bottom
for ((aop,bop,dop,res) in [(op1t,op2t,op3t,rest), (op1b,op2b,op3b,resb)]) {
   res = sat.q31(dop - (aop u* bop)[63:32]);
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a

- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKMADA (unsigned long long t, unsigned long long a, unsigned long long b)

DKMADA (Saturating Signed Multiply Two Halfs and Two Adds)

Type: DSP

Syntax:

```
DKMADA Rd, Rs1, Rs2
```

Purpose :

Do two 16x16 with 32-bit signed double addition simultaneously. The results are written into Rd.

Description :

It multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2 and then adds the result to the result of multiplying the top 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; op3t = Rd.W[x+1] // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; op3b = Rd.W[x] // bottom

for ((aop,bop,dop,res) in [(op1t,op2t,op3t,rest), (op1b,op2b,op3b,resb)]) {
  mul1 = aop.H[1] s* bop.H[1];
  mul2 = aop.H[0] s* bop.H[0];
  res = sat.q31(dop + mul1 + mul2);
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKMAXDA (unsigned long long t, unsigned long long a, unsigned long long b)

DKMAXDA (Two Cross 16x16 with 32-bit Signed Double Add)

Type: DSP

Syntax:

```
DKMAXDA Rd, Rs1, Rs2
```

Purpose :

Do two cross 16x16 with 32-bit signed double addition simultaneously. The results are written into Rd.

Description :

It multiplies the top 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2 and then adds the result to the result of multiplying the bottom 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in elements in Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; op3t = Rd.W[x+1] // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; op3b = Rd.W[x] // bottom

for ((aop,bop,dop,res) in [(op1t,op2t,op3t,rest), (op1b,op2b,op3b,resb)]) {
  mul1 = aop.H[1] s* bop.H[0];
  mul2 = aop.H[0] s* bop.H[1];
  res = sat.q31(dop + mul1 + mul2);
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKMADS (unsigned long long t, unsigned long long a, unsigned long long b)

DKMADS (Two 16x16 with 32-bit Signed Add and Sub)

Type: DSP

Syntax:

```
DKMADS Rd, Rs1, Rs2
```

Purpose :

Do two 16x16 with 32-bit signed addition and subtraction simultaneously. The results are written into Rd.

Description :

It multiplies the bottom 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32-bit elements in Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; op3t = Rd.W[x+1] // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; op3b = Rd.W[x] // bottom

for ((aop,bop,dop,res) in [(op1t,op2t,op3t,rest), (op1b,op2b,op3b,resb)]) {
  mul1 = aop.H[1] s* bop.H[1];
  mul2 = aop.H[0] s* bop.H[0];
  res = sat.q31(dop + mul1 - mul2);
}
```

(continues on next page)

(continued from previous page)

```
Rd = concat(rest, resb);
x=0
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKMADRS (unsigned long long t, unsigned long long a, unsigned long long b)

DKMADRS (Two 16x16 with 32-bit Signed Add and Reversed Sub)

Type: DSP

Syntax:

```
DKMADRS Rd, Rs1, Rs2
```

Purpose :

Do two 16x16 with 32-bit signed addition and revered subtraction simultaneously. The results are written into Rd.

Description :

it multiplies the top 16-bit content of 32-bit elements in Rs1 with the top 16-bit content of 32-bit elements in Rs2 and then subtracts the result from the result of multiplying the bottom 16-bit content of 32-bit elements in Rs1 with the bottom 16-bit content of 32- bit elements in Rs2

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; op3t = Rd.W[x+1] // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; op3b = Rd.W[x] // bottom

for ((aop,bop,dop,res) in [(op1t,op2t,op3t,rest), (op1b,op2b,op3b,resb)]) {
  mul1 = aop.H[1] s* bop.H[1];
  mul2 = aop.H[0] s* bop.H[0];
  res = sat.q31(dop - mul1 + mul2);
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKMAXDS (unsigned long long t, unsigned long long a, unsigned long long b)

DKMAXDS (Saturating Signed Crossed Multiply Two Halfs & Subtract & Add)

Type: DSP

Syntax:

```
DKMAXDS Rd, Rs1, Rs2
```

Purpose :

Do two cross 16x16 with 32-bit signed addition and subtraction simultaneously. The results are written into Rd.

Description :

Do two signed 16-bit multiplications from 32-bit elements in two registers; and then perform a subtraction operation between the two 32-bit results. Then add the subtraction result to the corresponding 32-bit elements in a third register. The addition result may be saturated.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; op3t = Rd.W[x+1] // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; op3b = Rd.W[x] // bottom

for ((aop,bop,dop,res) in [(op1t,op2t,op3t,rest), (op1b,op2b,op3b,resb)]) {
  mul1 = aop.H[1] s* bop.H[0];
  mul2 = aop.H[0] s* bop.H[1];
  res = sat.q31(dop + mul1 - mul2);
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKMSDA (unsigned long long t, unsigned long long a, unsigned long long b)

DKMSDA (Two 16x16 with 32-bit Signed Double Sub)

Type: DSP

Syntax:

```
DKMSDA Rd, Rs1, Rs2
```

Purpose :

Do two 16x16 with 32-bit signed double subtraction simultaneously. The results are written into Rd.

Description :

it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; op3t = Rd.W[x+1] // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; op3b = Rd.W[x] // bottom

for ((aop,bop,dop,res) in [(op1t,op2t,op3t,rest), (op1b,op2b,op3b,resb)]) {
  mul1 = aop.H[1] s* bop.H[0];
  mul2 = aop.H[0] s* bop.H[1];
  res = sat.q31(dop - mul1 - mul2);
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DKMSXDA (unsigned long long t, unsigned long long a, unsigned long long b)

DKMSXDA (Two Cross 16x16 with 32-bit Signed Double Sub)

Type: DSP

Syntax:

```
DKMSXDA Rd, Rs1, Rs2
```

Purpose :

Do two cross 16x16 with 32-bit signed double subtraction simultaneously. The results are written into Rd.

Description :

It multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 and multiplies the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; op3t = Rd.W[x+1] // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; op3b = Rd.W[x] // bottom

for ((aop,bop,dop,res) in [(op1t,op2t,op3t,rest), (op1b,op2b,op3b,resb)]) {
  mul1 = aop.H[1] s* bop.H[0];
  mul2 = aop.H[0] s* bop.H[1];
  res = sat.q31(dop - mul1 - mul2);
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DSMAQA (unsigned long long t, unsigned long long a, unsigned long long b)

DSMAQA (Four Signed 8x8 with 32-bit Signed Add)

Type: DSP

Syntax:

```
DSMAQA Rd, Rs1, Rs2
```

Purpose :

Do four signed 8x8 with 32-bit signed addition simultaneously. The results are written into Rd.

Description :

This instruction multiplies the four signed 8-bit elements of 32-bit chunks of Rs1 with the four signed 8-bit elements of 32-bit chunks of Rs2 and then adds the four results together with the signed content of the corresponding 32-bit chunks of Rd. The final results are written back to the corresponding 32-bit chunks in Rd.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; op3t = Rd.W[x+1] // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; op3b = Rd.W[x] // bottom

for ((aop,bop,dop,res) in [(op1t,op2t,op3t,rest), (op1b,op2b,op3b,resb)]) {
  m0 = aop.B[0] s* bop.B[0];
  m1 = aop.B[1] s* bop.B[1];
  m2 = aop.B[2] s* bop.B[2];
  m3 = aop.B[3] s* bop.B[3];
  res = dop + m0 + m1 + m2 + m3;
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE unsigned long long __RV_DSMAQA_SU (unsigned long long t, unsigned long long a, unsigned long long b)

DSMAQASU (Four Signed 8 x Unsigned 8 with 32-bit Signed Add)

Type: DSP

Syntax:

```
DSMAQASU Rd, Rs1, Rs2
```

Purpose :

Do four Signed 8 x Unsigned 8 with 32-bit unsigned addition simultaneously. The results are written into Rd.

Description :

This instruction multiplies the four unsigned 8-bit elements of 32-bit chunks of Rs1 with the four signed 8-bit elements of 32-bit chunks of Rs2 and then adds the four results together with the unsigned content of the corresponding 32-bit chunks of Rd. The final results are written back to the corresponding 32-bit chunks in Rd.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; op3t = Rd.W[x+1] // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; op3b = Rd.W[x] // bottom

for ((aop,bop,dop,res) in [(op1t,op2t,op3t,rest), (op1b,op2b,op3b,resb)]) {
  m0 = aop.B[0] su* bop.B[0];
  m1 = aop.B[1] su* bop.B[1];
  m2 = aop.B[2] su* bop.B[2];
  m3 = aop.B[3] su* bop.B[3];
  res = dop + m0 + m1 + m2 + m3;
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

`__STATIC_FORCEINLINE unsigned long long __RV_DUMAQA (unsigned long long t, unsigned long long a, unsigned long long b)`

DUMAQA (Four Unsigned 8x8 with 32-bit Unsigned Add)

Type: DSP

Syntax:

```
DUMAQA Rd, Rs1, Rs2
```

Purpose :

Do four unsigned 8x8 with 32-bit unsigned addition simultaneously. The results are written into Rd.

Description :

This instruction multiplies the four unsigned 8-bit elements of 32-bit chunks of Rs1 with the four unsigned 8-bit elements of 32-bit chunks of Rs2 and then adds the four results together with the unsigned content of the corresponding 32-bit chunks of Rd. The final results are written back to the corresponding 32-bit chunks in Rd.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; op3t = Rd.W[x+1] // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; op3b = Rd.W[x] // bottom

for ((aop,bop,dop,res) in [(op1t,op2t,op3t,rest), (op1b,op2b,op3b,resb)]) {
  m0 = aop.B[0] su* bop.B[0];
  m1 = aop.B[1] su* bop.B[1];
  m2 = aop.B[2] su* bop.B[2];
  m3 = aop.B[3] su* bop.B[3];
  res = dop + m0 + m1 + m2 + m3;
}
Rd = concat(rest, resb);
x=0
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE long long __RV_DKMDA32 (unsigned long long a, unsigned long long b)

DKMDA32 (Two Signed 32x32 with 64-bit Saturation Add)

Type: DSP

Syntax:

```
DKMDA32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32x32 add the signed multiplication results with Q63 saturation. The results are written into Rd.

Description :

For the `KMDA32` instruction, it multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2 and then adds the result to the result of multiplying the top 32-bit element of Rs1 with the top 32-bit element of Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom
t0 = op1b s* op2b;
t1 = op1t s* op2t;
Rd = concat(rest, resb);
x=0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DKMXDA32 (unsigned long long a, unsigned long long b)

DKMXDA32 (Two Cross Signed 32x32 with 64-bit Saturation Add)

Type: DSP

Syntax:

```
DKMXDA32 Rd, Rs1, Rs2
```

Purpose :

Do two cross signed 32x32 and add the signed multiplication results with Q63 saturation. The results are written into Rd.

Description :

It multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2 and then adds the result to the result of multiplying the top 32-bit element of Rs1 with the bottom 32-bit element of Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom
t01 = op1b s* op2t;
t10 = op1t s* op2b;
Rd = sat.q63(t01 + t10);
x=0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DKMADA32 (long long t, unsigned long long a, unsigned long long b)

DKMADA32 (Two Signed 32x32 with 64-bit Saturation Add)

Type: DSP

Syntax:

```
DKMADA32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32x32 and add the signed multiplication results and a third register with Q63 saturation. The results are written into Rd.

Description :

It multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2 and then adds the result to the result of multiplying the top 32-bit element of Rs1 with the top 32-bit element of Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom
t01 = op1b s* op2b;
t10 = op1t s* op2t;
Rd = sat.q63(t01 + t10);
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DKMAXDA32 (long long t, unsigned long long a, unsigned long long b)

DKMAXDA32 (Two Cross Signed 32x32 with 64-bit Saturation Add)

Type: DSP

Syntax:

```
DKMAXDA32 Rd, Rs1, Rs2
```

Purpose :

Do two cross signed 32x32 and add the signed multiplication results and a third register with Q63 saturation. The results are written into Rd.

Description :

It multiplies the top 32-bit element in Rs1 with the bottom 32-bit element in Rs2 and then adds the result to the result of multiplying the bottom 32-bit element in Rs1 with the top 32-bit element in Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom
t01 = op1b s* op2t;
t10 = op1t s* op2b;
Rd = sat.q63(Rd + t01 + t10);
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DKMADS32 (long long t, unsigned long long a, unsigned long long b)

DKMADS32 (Two Signed 32x32 with 64-bit Saturation Add and Sub)

Type: DSP

Syntax:

```
DKMADS32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32x32 and add the top signed multiplication results and subtraction bottom signed multiplication results and add a third register with Q63 saturation. The results are written into Rd.

Description :

It multiplies the top 32-bit element in Rs1 with the bottom 32-bit element in Rs2 and then subtracts the result to the result of multiplying the top 32-bit element in Rs1 with the top 32-bit element in Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

t0 = op1b s* op2b;
t1 = op1t s* op2t;
Rd = sat.q63(Rd - t0 + t1);
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DKMADRS32 (long long t, unsigned long long a, unsigned long long b)

DKMADRS32 (Two Signed 32x32 with 64-bit Saturation Revered Add and Sub)

Type: DSP

Syntax:

```
DKMADRS32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32x32 and add the signed multiplication results and a third register with Q63 saturation. The results are written into Rd.Do two signed 32x32 and subtraction the top signed multiplication results and add bottom signed multiplication results and add a third register with Q63 saturation. The results are written into Rd.

Description :

It multiplies the top 32-bit element in Rs1 with the top 32-bit element in Rs2 and then subtracts the result from the result of multiplying the bottom 32-bit element in Rs1 with the bottom 32-bit element in Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom
t0 = op1b s* op2b;
t1 = op1t s* op2t;
Rd = sat.q63(Rd + t0 - t1);
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DKMAXDS32 (long long t, unsigned long long a, unsigned long long b)

DKMAXDS32 (Two Cross Signed 32x32 with 64-bit Saturation Add and Sub)

Type: DSP

Syntax:

```
DKMAXDS32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32x32 and add the top signed multiplication results and subtraction bottom signed multiplication results and add a third register with Q63 saturation. The results are written into Rd.

Description :

It multiplies the bottom 32-bit element in Rs1 with the top 32-bit element in Rs2 and then subtracts the result from the result of multiplying the top 32-bit element in Rs1 with the bottom 32-bit element in Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

t01 = op1b s* op2t;
t10 = op1t s* op2b;
Rd = sat.q63(Rd - t01 + t10);
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DKMSDA32 (long long t, unsigned long long a, unsigned long long b)

DKMSDA32 (Two Signed 32x32 with 64-bit Saturation Sub)

Type: DSP

Syntax:

```
DKMSDA32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32x32 and subtraction the top signed multiplication results and subtraction bottom signed multiplication results and add a third register with Q63 saturation. The results are written into Rd.

Description :

It multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2 and multiplies the top 32-bit element of Rs1 with the top 32-bit element of Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

t0 = op1b s* op2b;
t1 = op1t s* op2t;
Rd = sat.q63(Rd - t0 - t1);
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DKMSXDA32 (long long t, unsigned long long a, unsigned long long b)

DKMSXDA32 (Two Cross Signed 32x32 with 64-bit Saturation Sub)

Type: DSP

Syntax:

```
DKMSXDA32 Rd, Rs1, Rs2
```

Purpose :

Do two cross signed 32x32 and subtraction the top signed multiplication results and subtraction bottom signed multiplication results and add a third register with Q63 saturation. The results are written into Rd.

Description :

It multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2 and multiplies the top 32-bit element of Rs1 with the bottom 32-bit element of Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

t0 = op1b s* op2t;
t1 = op1t s* op2b;
Rd = sat.q63(Rd - t0 - t1);
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMDS32 (unsigned long long a, unsigned long long b)

DSMDS32 (Two Signed 32x32 with 64-bit Sub)

Type: DSP

Syntax:

```
DSMDS32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32x32 and add the top signed multiplication results and subtraction bottom signed multiplication. The results are written into Rd.

Description :

It multiplies the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2 and then subtracts the result from the result of multiplying the top 32-bit element of Rs1 with the top 32-bit element of Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

t0 = op1b s* op2t;
t1 = op1t s* op2b;
Rd = t1 - t0;
x=0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMDRS32 (unsigned long long a, unsigned long long b)

DSMDRS32 (Two Signed 32x32 with 64-bit Revered Sub)

Type: DSP

Syntax:

```
DSMDRS32 Rd, Rs1, Rs2
```

Purpose :

Do two signed 32x32 and subtraction the top signed multiplication results and add bottom signed multiplication. The results are written into Rd

Description :

It multiplies the top 32-bit element of Rs1 with the top 32-bit element of Rs2 and then subtracts the result from the result of multiplying the bottom 32-bit element of Rs1 with the bottom 32-bit element of Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

t0 = op1b s* op2b;
t1 = op1t s* op2t;
Rd = t1 - t0;
x=0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

`__STATIC_FORCEINLINE long long __RV_DSMXDS32 (unsigned long long a, unsigned long long b)`

DSMXDS32 (Two Cross Signed 32x32 with 64-bit Sub)

Type: DSP

Syntax:

```
DSMXDS32 Rd, Rs1, Rs2
```

Purpose :

Do two cross signed 32x32 and add the top signed multiplication results and subtraction bottom signed multiplication. The results are written into Rd.

Description :

It multiplies the bottom 32-bit element of Rs1 with the top 32-bit element of Rs2 and then subtracts the result from the result of multiplying the top 32-bit element of Rs1 with the bottom 32-bit element of Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

t01 = op1b s* op2t;
t10 = op1t s* op2b;
Rd = t1 - t0;
x=0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMALDA (long long t, unsigned long long a, unsigned long long b)

DSMALDA (Four Signed 16x16 with 64-bit Add)

Type: DSP

Syntax:

```
DSMALDA Rd, Rs1, Rs2
```

Purpose :

Do four signed 16x16 and add signed multiplication results and a third register. The results are written into Rd.

Description :

It multiplies the bottom 16-bit content of Rs1 with the bottom 16-bit content of Rs2 and then adds the result to the result of multiplying the top 16-bit content of Rs1 with the top 16-bit content of Rs2 with unlimited precision

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

m0 = op1b.H[0] s* op2b.H[0];
m1 = op1b.H[1] s* op2b.H[1];
m2 = op1t.H[0] s* op2t.H[0];
m3 = op1t.H[1] s* op2t.H[1];

Rd = Rd + m0 + m1 + m2 + m3;
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMALXDA (long long t, unsigned long long a, unsigned long long b)

DSMALXDA (Four Signed 16x16 with 64-bit Add)

Type: DSP

Syntax:

```
DSMALXDA Rd, Rs1, Rs2
```

Purpose :

Do four cross signed 16x16 and add signed multiplication results and a third register. The results are written into Rd.

Description :

It multiplies the top 16-bit content of Rs1 with the bottom 16-bit content of Rs2 and then adds the result to the result of multiplying the bottom 16-bit content of Rs1 with the top 16-bit content of Rs2 with unlimited precision.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

m0 = op1b.H[0] s* op2b.H[1];
m1 = op1b.H[1] s* op2b.H[0];
m2 = op1t.H[0] s* op2t.H[1];
m3 = op1t.H[1] s* op2t.H[0];

Rd = Rd + m0 + m1 + m2 + m3;
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMALDS (long long t, unsigned long long a, unsigned long long b)

DSMALDS (Four Signed 16x16 with 64-bit Add and Sub)

Type: DSP

Syntax:

```
DSMALDS Rd, Rs1, Rs2
```

Purpose :

Do four signed 16x16 and add and subtraction signed multiplication results and a third register. The results are written into Rd.

Description :

It multiplies the bottom 16-bit content of Rs1 with the bottom 16-bit content of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of Rs1 with the top 16-bit content of Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

m0 = op1b.H[1] s* op2b.H[1];
m1 = op1b.H[0] s* op2b.H[0];
m2 = op1t.H[1] s* op2t.H[1];
m3 = op1t.H[0] s* op2t.H[0];

Rd = Rd + m0 - m1 + m2 - m3;
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMALDRS (long long t, unsigned long long a, unsigned long long b)

DSMALDRS (Four Signed 16x16 with 64-bit Add and Revered Sub)

Type: DSP

Syntax:

```
DSMALDRS Rd, Rs1, Rs2
```

Purpose :

Do two signed 16x16 and add and revered subtraction signed multiplication results and a third register. The results are written into Rd.

Description :

It multiplies the top 16-bit content of Rs1 with the top 16-bit content of Rs2 and then subtracts the result from the result of multiplying the bottom 16-bit content of Rs1 with the bottom 16-bit content of Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

m0 = op1b.H[0] s* op2b.H[0];
m1 = op1b.H[1] s* op2b.H[1];
m2 = op1t.H[0] s* op2t.H[0];
m3 = op1t.H[1] s* op2t.H[1];

Rd = Rd + m0 - m1 + m2 - m3;
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMALXDS (long long t, unsigned long long a, unsigned long long b)

DSMALXDS (Four Cross Signed 16x16 with 64-bit Add and Sub)

Type: DSP

Syntax:

```
DSMALXDS Rd, Rs1, Rs2
```

Purpose :

Do four cross signed 16x16 and add and subtraction signed multiplication results and a third register. The results are written into Rd.

Description :

It multiplies the bottom 16-bit content of Rs1 with the top 16-bit content of Rs2 and then subtracts the result from the result of multiplying the top 16-bit content of Rs1 with the bottom 16-bit content of Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

m0 = op1b.H[1] s* op2b.H[0];
m1 = op1b.H[0] s* op2b.H[1];
m2 = op1t.H[1] s* op2t.H[0];
m3 = op1t.H[0] s* op2t.H[1];

Rd = Rd + m0 - m1 + m2 - m3;
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMSLDA (long long t, unsigned long long a, unsigned long long b)

DSMSLDA (Four Signed 16x16 with 64-bit Sub)

Type: DSP

Syntax:

```
DSMSLDA Rd, Rs1, Rs2
```

Purpose :

Do four signed 16x16 and subtraction signed multiplication results and add a third register. The results are written into Rd.

Description :

It multiplies the bottom 16-bit content of Rs1 with the bottom 16-bit content Rs2 and multiplies the top 16-bit content of Rs1 with the top 16-bit content of Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

m0 = op1b.H[0] s* op2b.H[0];
m1 = op1b.H[1] s* op2b.H[1];
m2 = op1t.H[0] s* op2t.H[0];
m3 = op1t.H[1] s* op2t.H[1];

Rd = Rd - m0 - m1 - m2 - m3;
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

`__STATIC_FORCEINLINE long long __RV_DSMSLXDA (long long t, unsigned long long a, unsigned long long b)`

DSMSLXDA (Four Cross Signed 16x16 with 64-bit Sub)

Type: DSP

Syntax:

```
DSMSLXDA Rd, Rs1, Rs2
```

Purpose :

Do four signed 16x16 and subtraction signed multiplication results and add a third register. The results are written into Rd.

Description :

It multiplies the top 16-bit content of Rs1 with the bottom 16-bit content of Rs2 and multiplies the bottom 16-bit content of Rs1 with the top 16-bit content of Rs2.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

m0 = op1b.H[0] s* op2b.H[1];
m1 = op1b.H[1] s* op2b.H[0];
m2 = op1t.H[0] s* op2t.H[1];
m3 = op1t.H[1] s* op2t.H[0];

Rd = Rd - m0 - m1 - m2 - m3;
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DDSMAQA (long long t, unsigned long long a, unsigned long long b)

DDSMAQA (Eight Signed 8x8 with 64-bit Add)

Type: DSP

Syntax:

```
DDSMAQA Rd, Rs1, Rs2
```

Purpose :

Do eight signed 8x8 and add signed multiplication results and a third register. The results are written into Rd.

Description :

Do eight signed 8-bit multiplications from eight 8-bit chunks of two registers; and then adds the eight 16-bit results and the content of 64-bit chunks of a third register.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

m0 = op1b.B[0] s* op2b.B[0];
m1 = op1b.B[1] s* op2b.B[1];
m2 = op1b.B[2] s* op2b.B[2];
m3 = op1b.B[3] s* op2b.B[3];
m4 = op1t.B[0] s* op2t.B[0];
m5 = op1t.B[1] s* op2t.B[1];
m6 = op1t.B[2] s* op2t.B[2];
m7 = op1t.B[3] s* op2t.B[3];

s0 = m0 + m1 + m2 + m3;
s1 = m4 + m5 + m6 + m7;
```

(continues on next page)

(continued from previous page)

```
Rd = Rd + s0 + s1;
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DDSMAQASU (long long t, unsigned long long a, unsigned long long b)

DDSMAQASU (Eight Signed 8 x Unsigned 8 with 64-bit Add)

Type: DSP

Syntax:

```
DDSMAQASU Rd, Rs1, Rs2
```

Purpose :

Do eight signed 8 x unsigned 8 and add signed multiplication results and a third register. The results are written into Rd.

Description :

Do eight signed 8 x unsigned 8 and add signed multiplication results and a third register; and then adds the eight 16-bit results and the content of 64-bit chunks of a third register.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

m0 = op1b.B[0] su* op2b.B[0];
m1 = op1b.B[1] su* op2b.B[1];
m2 = op1b.B[2] su* op2b.B[2];
m3 = op1b.B[3] su* op2b.B[3];
m4 = op1t.B[0] su* op2t.B[0];
m5 = op1t.B[1] su* op2t.B[1];
m6 = op1t.B[2] su* op2t.B[2];
m7 = op1t.B[3] su* op2t.B[3];

s0 = m0 + m1 + m2 + m3;
s1 = m4 + m5 + m6 + m7;
Rd = Rd + s0 + s1;
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a

- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DDUMAQA (long long t, unsigned long long a, unsigned long long b)

DDUMAQA (Eight Unsigned 8x8 with 64-bit Unsigned Add)

Type: DSP

Syntax:

```
DDUMAQA Rd, Rs1, Rs2
```

Purpose :

Do eight unsigned 8x8 and add unsigned multiplication results and a third register. The results are written into Rd.

Description :

Do eight unsigned 8x8 and add unsigned multiplication results and a third register; and then adds the eight 16-bit results and the content of 64-bit chunks of a third register.

Operations:

```
op1t = Rs1.W[x+1]; op2t = Rs2.W[x+1]; // top
op1b = Rs1.W[x]; op2b = Rs2.W[x]; // bottom

m0 = op1b.B[0] u* op2b.B[0];
m1 = op1b.B[1] u* op2b.B[1];
m2 = op1b.B[2] u* op2b.B[2];
m3 = op1b.B[3] u* op2b.B[3];
m4 = op1t.B[0] u* op2t.B[0];
m5 = op1t.B[1] u* op2t.B[1];
m6 = op1t.B[2] u* op2t.B[2];
m7 = op1t.B[3] u* op2t.B[3];

s0 = m0 + m1 + m2 + m3;
s1 = m4 + m5 + m6 + m7;
Rd = Rd + s0 + s1;
x=0
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long __RV_DSMA32_U (unsigned long long a, unsigned long long b)

DSMA32.u (64-bit SIMD 32-bit Signed Multiply Addition With Rounding and Clip)

Type: DSP

Syntax:

```
DSMA32.u Rd, Rs1, Rs2
```

Purpose :

Do two signed 32x32 and add signed multiplication results with Rounding, then right shift 32-bit and clip q63 to q31. The result is written to Rd.

Description :

For the `DSMA32.u` instruction, multiply the top 32-bit Q31 content of 64-bit chunks in Rs1 with the top 32-bit Q31 content of 64-bit chunks in Rs2. At the same time, multiply the bottom 32-bit Q31 content of 64-bit chunks in Rs1 with the bottom 32-bit Q31 content of 64-bit chunks in Rs2. Then, do the addtion for the results above and perform the addtional rounding operations, and then move the data to the right by 32-bit, and clip the 64-bit data into 32-bit.The result is written to Rd.

Operations:

```
Rd = (q31_t)((Rs1.W[x] s* Rs2.W[x] + Rs1.W[x + 1] s* Rs2.W[x + 1] +␣
↪0x80000000LL) s>> 32);
x=0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_DSMXS32_U (unsigned long long a, unsigned long long b)

DSMXS32.u (64-bit SIMD 32-bit Signed Multiply Cross Subtraction With Rounding and Clip)

Type: DSP

Syntax:

```
DSMXS32.u Rd, Rs1, Rs2
```

Purpose :

Do two cross signed 32x32 and sub signed multiplication results with Rounding, then right shift 32-bit and clip q63 to q31. The result is written to Rd.

Description :

For the `DSMXS32.u` instruction, multiply the top 32-bit Q31 content of 64-bit chunks in Rs1 with the bottom 32-bit Q31 content of 64-bit chunks in Rs2. At the same time, multiply the bottom 32-bit Q31 content of 64-bit chunks in Rs1 with the top 32-bit Q31 content of 64-bit chunks in Rs2. Then, do the subtraction for the results above and perform the addtional rounding operations, and then move the data to the right by 32-bit, and clip the 64-bit data into 32-bit.The result is written to Rd.

Operations:

```
Rd = (q31_t)((Rs1.W[x + 1] s* Rs2.W[x] - Rs1.W[x] s* Rs2.W[x + 1] +␣
↪0x80000000LL) s>> 32);
x=0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_DSMXA32_U (unsigned long long a, unsigned long long b)

DSMXA32.u (64-bit SIMD 32-bit Signed Cross Multiply Addition with Rounding and Clip)

Type: DSP

Syntax:

```
DSMXA32.u Rd, Rs1, Rs2
```

Purpose :

Do two cross signed 32x32 and add signed multiplication results with Rounding, then right shift 32-bit and clip q63 to q31. The result is written to Rd.

Description :

For the `DSMXA32.u` instruction,multiply the top 32-bit Q31 content of 64-bit chunks in Rs1 with the bottom 32-bit Q31 content of 64-bit chunks in Rs2. At the same time, multiply the bottom 32-bit Q31 content of 64-bit chunks in Rs1 with the top 32-bit Q31 content of 64-bit chunks in Rs2. Then, do the addtion for the results above and perform the addtional rounding operations, and then move the data to the right by 32-bit, and clip the 64-bit data into 32-bit.The result is written to Rd.

Operations:

```
Rd = (q31_t)((Rs1.W[x + 1] s* Rs2.W[x] + Rs1.W[x] s* Rs2.W[x + 1] +␣
↪0x80000000LL) s>> 32);
x=0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_DSMS32_U (unsigned long long a, unsigned long long b)

DSMS32.u (64-bit SIMD 32-bit Signed Multiply Subtraction with Rounding and Clip)

Type: DSP

Syntax:

```
DSMS32.u Rd, Rs1, Rs2
```

Purpose :

Do two signed 32x32 and sub signed multiplication results with Rounding, then right shift 32-bit and clip q63 to q31. The result is written to Rd.

Description :

For the `DSMS32.u` instruction, multiply the bottom 32-bit Q31 content of 64-bit chunks in Rs1 with the bottom 32-bit Q31 content of 64-bit chunks in Rs2. At the same time, multiply the top 32-bit Q31 content of 64-bit chunks in Rs1 with the top 32-bit Q31 content of 64-bit chunks in Rs2. Then, do the subtraction for the results above and perform the addtional rounding operations, and then move the data to the right by 32-bit, and clip the 64-bit data into 32-bit.The result is written to Rd.

Operations:

```
Rd = (q31_t)((Rs1.W[x] s* Rs2.W[x] - Rs1.W[x + 1] s* Rs2.W[x + 1] +␣
↪0x80000000LL) s>> 32);
x=0
```

Parameters

- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long type

`__STATIC_FORCEINLINE long __RV_DSMADA16 (long long t, unsigned long long a, unsigned long long b)`

DSMADA16 (Signed Multiply Two Halfs and Two Adds 32-bit)

Type: SIMD

Syntax:

```
DSMADA16 Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications of two 32-bit registers; and then adds the 32-bit results and the 32-bit value of an even/odd pair of registers together.

- DSMADA16: rt pair+ top*top + bottom*bottom

Description :

This instruction multiplies the per 16-bit content of the 32-bit elements of Rs1 with the corresponding 16-bit content of the 32-bit elements of Rs2. The result is added to the 32-bit value of an even/odd pair of registers specified by Rd(4,1). The 32-bit addition result is written back to the register-pair. The 16-bit values of Rs1 and Rs2, and the 32-bit value of the register-pair are treated as signed integers.

Operations:

```
Mres0[0][31:0] = (Rs1.W[0].H[0] * Rs2.W[0].H[0]);
Mres1[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[1]);
Mres0[1][31:0] = (Rs1.W[1].H[0] * Rs2.W[1].H[0]);
Mres1[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[1].H[1]);
Rd.W = Rd.W + SE32(Mres0[0][31:0]) + SE32(Mres1[0][31:0]) +␣
↪SE32(Mres0[1][31:0]) + SE32(Mres1[1][31:0]);
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long __RV_DSMAXDA16 (long long t, unsigned long long a, unsigned long long b)

DSMAXDA16 (Signed Crossed Multiply Two Halfs and Two Adds 32-bit)

Type: SIMD

Syntax:

```
DSMAXDA16 Rd, Rs1, Rs2
```

Purpose :

Do two signed 16-bit multiplications of two 32-bit registers; and then adds the 32-bit results and the 32-bit value of an even/odd pair of registers together.

- DSMAXDA: rt pair+ top*bottom + bottom*top (all 32-bit elements)

Description :

This instruction crossly multiplies the top 16-bit content of the 32-bit elements of Rs1 with the bottom 16-bit content of the 32-bit elements of Rs2 and then adds the result to the result of multiplying the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2 with unlimited precision. The result is added to the 64-bit value of an even/odd pair of registers specified by Rd(4,1).The 64-bit addition result is clipped to 32-bit result.

Operations:

```
Mres0[0][31:0] = (Rs1.W[0].H[0] * Rs2.W[0].H[1]);
Mres1[0][31:0] = (Rs1.W[0].H[1] * Rs2.W[0].H[0]);
Mres0[1][31:0] = (Rs1.W[1].H[0] * Rs2.W[1].H[1]);
Mres1[1][31:0] = (Rs1.W[1].H[1] * Rs2.W[1].H[0]);
Rd.W = Rd.W + SE32(Mres0[0][31:0]) + SE32(Mres1[0][31:0]) +
→SE32(Mres0[1][31:0]) + SE32(Mres1[1][31:0]);
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE unsigned long long __RV_DKSMS32_U (unsigned long long t, unsigned long long a, unsigned long long b)

DKSMS32.u (Two Signed Multiply Shift-clip and Saturation with Rounding)

Type: SIMD

Syntax:

```
DKSMS32.u Rd, Rs1, Rs2
```

Purpose :

Computes saturated multiplication of two pairs of q31 type with shifted rounding.

Description :

Compute the multiplication of Rs1 and Rs2 of type q31_t, intercept [47:16] for the resulting 64-bit product to get the 32-bit number, then add 1 to it to do rounding, and finally saturate the result after rounding.

Operations:

```
Mres[x][63:0] = Rs1.W[x] s* Rs2.W[x];
Round[x][32:0] = Mres[x][47:15] + 1;
Rd.W[x] = sat.31(Rd.W[x] + Round[x][32:1]);
x=1...0
```

Parameters

- **t** – **[in]** unsigned long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

__STATIC_FORCEINLINE long __RV_DMADA32 (long long t, unsigned long long a, unsigned long long b)

DMADA32 ((Two Cross Signed 32x32 with 64-bit Add and Clip to 32-bit)

Type: SIMD

Syntax:

```
DMADA32 Rd, Rs1, Rs2
```

Purpose :

Do two cross signed 32x32 and add the signed multiplication results to q63, then clip the q63 result to q31 , the final results are written into Rd.

Description :

For the DMADA32 instruction, it multiplies the top 32-bit element in Rs1 with the bottom 32-bit element in Rs2 and then adds the result to the result of multiplying the bottom 32-bit element in Rs1 with the top 32-bit element in Rs2, then clip the q63 result to q31.

Operations:

```
res = (q31_t)((((q63_t) Rd.w[0] << 32) + (q63_t)Rs1.w[0] s*  Rs2.w[1] + (q63_
↪t)Rs1.w[1] s*  Rs2.w[0]) s>> 32);
rd = res;
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long type

__STATIC_FORCEINLINE long long __RV_DSMALBB (long long t, unsigned long long a, unsigned long long b)

DSMALBB (Signed Multiply Bottom Halfs & Add 64-bit)

Type: SIMD

Syntax:

```
DSMALBB Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 16-bit content of the 32-bit elements of a register with the 16-bit content of the corresponding 32-bit elements of another register and add the results with a 64-bit value of an even/odd pair of registers. The addition result is written back to the register-pair.

- DSMALBB: rt pair + bottom*bottom (all 32-bit elements)

Description :

For the DSMALBB instruction, it multiplies the bottom 16-bit content of Rs1 with the bottom 16-bit content of Rs2.The multiplication results are added with the 64-bit value of Rd. The 64-bit addition result is written back to Rd.

Operations:

```
Mres[0][31:0] = Rs1.W[0].H[0] * Rs2.W[0].H[0];
Mres[1][31:0] = Rs1.W[1].H[0] * Rs2.W[1].H[0];
Rd = Rd + SE64(Mres[0][31:0]) + SE64(Mres[1][31:0]);
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMALBT (long long t, unsigned long long a, unsigned long long b)

DSMALBT (Signed Multiply Bottom Half & Top Half & Add 64-bit)

Type: SIMD

Syntax:

```
DSMALBT Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 16-bit content of the 32-bit elements of a register with the 16-bit content of the corresponding 32-bit elements of another register and add the results with a 64-bit value of an even/odd pair of registers. The addition result is written back to the register-pair.

- DSMALBT: rt pair + bottom*top (all 32-bit elements)

Description :

For the DSMALBT instruction, it multiplies the bottom 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. The multiplication results are added with the 64-bit value of Rd. The 64-bit addition result is written back to Rd. The 16-bit values of Rs1 and Rs2, and the 64-bit value of Rd are treated as signed integers

Operations:

```
Mres[0][31:0] = Rs1.W[0].H[0] * Rs2.W[0].H[1];
Mres[1][31:0] = Rs1.W[1].H[0] * Rs2.W[1].H[1];
Rd = Rd + SE64(Mres[0][31:0]) + SE64(Mres[1][31:0]);
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DSMALTT (long long t, unsigned long long a, unsigned long long b)

DSMALTT (Signed Multiply Top Half & Add 64-bit)

Type: SIMD

Syntax:

```
DSMALTT Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 16-bit content of the 32-bit elements of a register with the 16-bit content of the corresponding 32-bit elements of another register and add the results with a 64-bit value of an even/odd pair of registers. The addition result is written back to the register-pair.

- DSMALTT: DSMALTT rt pair + top*top (all 32-bit elements)

Description :

For the `DSMALTT` instruction, it multiplies the top 16-bit content of the 32-bit elements of Rs1 with the top 16-bit content of the 32-bit elements of Rs2. The multiplication results are added with the 64-bit value of Rd. The 64-bit addition result is written back to Rd. The 16-bit values of Rs1 and Rs2, and the 64-bit value of Rd are treated as signed integers.

Operations:

```
Mres[0][31:0] = Rs1.W[0].H[1] * Rs2.W[0].H[1];
Mres[1][31:0] = Rs1.W[1].H[1] * Rs2.W[1].H[1];
Rd = Rd + SE64(Mres[0][31:0]) + SE64(Mres[1][31:0]);
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DKMABB32 (long long t, unsigned long long a, unsigned long long b)

DKMABB32 (Saturating Signed Multiply Bottom Words & Add)

Type: SIMD

Syntax:

```
DKMABB32 Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit element in a register with the 32-bit element in another register and add the result to the content of 64-bit data in the third register. The addition result may besaturated and is written to the third register.

- DKMABB32: rd + bottom*bottom

Description :

For the `DKMABB32` instruction, it multiplies the bottom 32-bit element in Rs1 with the bottom 32-bit element in Rs2 The multiplication result is added to the content of 64-bit data in Rd. If the addition result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The result after saturation is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rd + (Rs1.W[0] * Rs2.W[0]);
if (res > (2^63)-1) {
  res = (2^63)-1;
  OV = 1;
} else if (res < -2^63) {
  res = -2^63;
  OV = 1;
}
Rd = res;
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DKMABT32 (long long t, unsigned long long a, unsigned long long b)

DKMABT32 (Saturating Signed Multiply Bottom & Top Words & Add)

Type: SIMD

Syntax:

```
DKMABT32 Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit element in a register with the 32-bit element in another register and add the result to the content of 64-bit data in the third register. The addition result may be saturated and is written to the third register.

- DKMABT32: rd + bottom*top

Description :

For the `DKMABT32` instruction, it multiplies the bottom 32-bit element in Rs1 with the top 32-bit element in Rs2 The multiplication result is added to the content of 64-bit data in Rd. If the addition result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The result after saturation is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rd + (Rs1.W[0] * Rs2.W[1]);
if (res > (2^63)-1) {
  res = (2^63)-1;
  OV = 1;
} else if (res < -2^63) {
  res = -2^63;
  OV = 1;
}
Rd = res;
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in long long type

__STATIC_FORCEINLINE long long __RV_DKMATT32 (long long t, unsigned long long a, unsigned long long b)

DKMATT32 (Saturating Signed Multiply Bottom & Top Words & Add)

Type: SIMD

Syntax:

```
DKMATT32 Rd, Rs1, Rs2
```

Purpose :

Multiply the signed 32-bit element in a register with the 32-bit element in another register and add the result to the content of 64-bit data in the third register. The addition result may be saturated and is written to the third register.

- DKMATT32: rd + top*top

Description :

For the `DKMATT32` instruction, it multiplies the top 32-bit element in Rs1 with the top 32-bit element in Rs2 The multiplication result is added to the content of 64-bit data in Rd. If the addition result is beyond the Q63 number range (-2^63 <= Q63 <= 2^63-1), it is saturated to the range and the OV bit is set to 1. The result after saturation is written to Rd. The 32-bit contents of Rs1 and Rs2 are treated as signed integers.

Operations:

```
res = Rd + (Rs1.W[1] * Rs2.W[1]);
if (res > (2^63)-1) {
  res = (2^63)-1;
  OV = 1;
} else if (res < -2^63) {
  res = -2^63;
  OV = 1;
}
Rd = res;
```

Parameters

- **t** – **[in]** long long type of value stored in t
- **a** – **[in]** unsigned long long type of value stored in a
- **b** – **[in]** unsigned long long type of value stored in b

Returns value stored in unsigned long long type

group **NMSIS_Core_DSP_Intrinsic**

Functions that generate RISC-V DSP SIMD instructions.

The following functions generate specified RISC-V SIMD instructions that cannot be directly accessed by compiler.

- **DSP ISA Extension Instruction Summary**
  - **Shorthand Definitions**
    - r.H == rH1: r[31:16], r.L == r.H0: r[15:0]
    - r.B3: r[31:24], r.B2: r[23:16], r.B1: r[15:8], r.B0: r[7:0]
    - r.B[x]: r[(x*8+7):(x*8+0)]
    - r.H[x]: r[(x*16+7):(x*16+0)]
    - r.W[x]: r[(x*32+31):(x*32+0)]
    - r[xU]: the upper 32-bit of a 64-bit number; xU represents the GPR number that contains this upper part 32-bit value.
    - r[xL]: the lower 32-bit of a 64-bit number; xL represents the GPR number that contains this lower part 32-bit value.
    - r[xU].r[xL]: a 64-bit number that is formed from a pair of GPRs.
    - s>>: signed arithmetic right shift:
    - u>>: unsigned logical right shift
    - SAT.Qn(): Saturate to the range of [-2^n, 2^n-1], if saturation happens, set PSW.OV.
    - SAT.Um(): Saturate to the range of [0, 2^m-1], if saturation happens, set PSW.OV.
    - RUND(): Indicate `rounding`, i.e., add 1 to the most significant discarded bit for right shift or MSW-type multiplication instructions.
    - Sign or Zero Extending functions:
      - SEm(data): Sign-Extend data to m-bit.:
      - ZEm(data): Zero-Extend data to m-bit.

- ABS(x): Calculate the absolute value of `x`.
- CONCAT(x,y): Concatinate `x` and `y` to form a value.
- u<: Unsinged less than comparison.
- u<=: Unsinged less than & equal comparison.
- u>: Unsinged greater than comparison.
- s*: Signed multiplication.
- u*: Unsigned multiplication.

2.5.8 Peripheral Access

`__I` volatile const

`__O` volatile

`__IO` volatile

`__IM` volatile const

`__OM` volatile

`__IOM` volatile

`_VAL2FLD`(field, value) (((uint32_t)(value) << field ## _Pos) & field ## _Msk)

`_FLD2VAL`(field, value) (((uint32_t)(value) & field ## _Msk) >> field ## _Pos)

group **`NMSIS_Core_PeriphAccess`**

Naming conventions and optional features for accessing peripherals.

The section below describes the naming conventions, requirements, and optional features for accessing device specific peripherals. Most of the rules also apply to the core peripherals.

The **Device Header File <device.h>** contains typically these definition and also includes the core specific header files.

Defines

`__I` volatile const

Defines 'read only' permissions.

`__O` volatile

Defines 'write only' permissions.

`__IO` volatile

Defines 'read / write' permissions.

`__IM` volatile const

Defines 'read only' structure member permissions.

`__OM` volatile

Defines 'write only' structure member permissions.

`__IOM` volatile

Defines 'read/write' structure member permissions.

`_VAL2FLD`(field, value) (((uint32_t)(value) << field ## _Pos) & field ## _Msk)

Mask and shift a bit field value for use in a register bit range.

The macro _VAL2FLD uses the #define's _Pos and _Msk of the related bit field to shift bit-field values for assigning to a register.

Example:

```
ECLIC->CFG = _VAL2FLD(CLIC_CLICCFG_NLBIT, 3);
```

Parameters

- **field** – **[in]** Name of the register bit field.
- **value** – **[in]** Value of the bit field. This parameter is interpreted as an uint32_t type.

Returns Masked and shifted value.

`_FLD2VAL`(field, value) (((uint32_t)(value) & field ## _Msk) >> field ## _Pos)

Mask and shift a register value to extract a bit filed value.

The macro _FLD2VAL uses the #define's _Pos and _Msk of the related bit field to extract the value of a bit field from a register.

Example:

```
nlbits = _FLD2VAL(CLIC_CLICCFG_NLBIT, ECLIC->CFG);
```

Parameters

- **field** – **[in]** Name of the register bit field.
- **value** – **[in]** Value of register. This parameter is interpreted as an uint32_t type.

Returns Masked and shifted bit field value.

2.5.9 Systick Timer(SysTimer)

Click Nuclei Timer Unit[16] to learn about Core Timer Unit in Nuclei ISA Spec.

SysTimer API

__STATIC_FORCEINLINE void SysTimer_SetLoadValue (uint64_t value)

__STATIC_FORCEINLINE uint64_t SysTimer_GetLoadValue (void)

__STATIC_FORCEINLINE void SysTimer_SetHartCompareValue (uint64_t value, unsigned long hartid)

__STATIC_FORCEINLINE void SysTimer_SetCompareValue (uint64_t value)

__STATIC_FORCEINLINE uint64_t SysTimer_GetHartCompareValue (unsigned long hartid)

__STATIC_FORCEINLINE uint64_t SysTimer_GetCompareValue (void)

__STATIC_FORCEINLINE void SysTimer_Start (void)

__STATIC_FORCEINLINE void SysTimer_Stop (void)

__STATIC_FORCEINLINE void SysTimer_SetControlValue (uint32_t mctl)

__STATIC_FORCEINLINE uint32_t SysTimer_GetControlValue (void)

__STATIC_FORCEINLINE void SysTimer_SetHartSWIRQ (unsigned long hartid)

__STATIC_FORCEINLINE void SysTimer_SetSWIRQ (void)

__STATIC_FORCEINLINE void SysTimer_ClearHartSWIRQ (unsigned long hartid)

__STATIC_FORCEINLINE void SysTimer_ClearSWIRQ (void)

__STATIC_FORCEINLINE uint32_t SysTimer_GetHartMsipValue (unsigned long hartid)

__STATIC_FORCEINLINE uint32_t SysTimer_GetMsipValue (void)

__STATIC_FORCEINLINE void SysTimer_SetHartMsipValue (uint32_t msip, unsigned long hartid)

[16] https://doc.nucleisys.com/nuclei_spec/isa/timer.html

`__STATIC_FORCEINLINE void SysTimer_SetMsipValue (uint32_t msip)`

`__STATIC_FORCEINLINE void SysTimer_SoftwareReset (void)`

`__STATIC_FORCEINLINE void SysTimer_SendIPI (unsigned long hartid)`

`__STATIC_FORCEINLINE void SysTimer_ClearIPI (unsigned long hartid)`

`__STATIC_INLINE uint32_t SysTick_Config (uint64_t ticks)`

`__STATIC_INLINE uint32_t SysTick_HartConfig (uint64_t ticks, unsigned long hartid)`

`__STATIC_FORCEINLINE uint32_t SysTick_Reload (uint64_t ticks)`

`__STATIC_FORCEINLINE uint32_t SysTick_HartReload (uint64_t ticks, unsigned long hartid)`

`SysTimer_GetHartID()` (*__get_hart_index* (page 84)())

group `NMSIS_Core_SysTimer`

Functions that configure the Core System Timer.

Defines

`SysTimer_GetHartID()` (*__get_hart_index* (page 84)())

SysTimer_GetHartID() is used to get timer hartid which might not be the same as cpu hart id, for example, cpu hartid may be 1, but timer hartid may be 0, then timer hartid offset is 1.

If defined __SYSTIMER_HARTID, it will use __SYSTIMER_HARTID as timer hartid, otherwise, it will use *__get_hart_index()* (page 84). The cpu hartid is get by using __get_hart_id function

Functions

`__STATIC_FORCEINLINE void SysTimer_SetLoadValue (uint64_t value)`

Set system timer load value.

This function set the system timer load value in MTIMER register.

Remark

- Load value is 64bits wide.
- SysTimer_GetLoadValue

Parameters `value` – **[in]** value to set system timer MTIMER register.

`__STATIC_FORCEINLINE uint64_t SysTimer_GetLoadValue (void)`

Get system timer load value.

This function get the system timer current value in MTIMER register.

Remark

- Load value is 64bits wide.
- SysTimer_SetLoadValue

Returns current value(64bit) of system timer MTIMER register.

`__STATIC_FORCEINLINE void SysTimer_SetHartCompareValue (uint64_t value, unsigned long hartid)`

Set system timer compare value by hartid.

This function set the system Timer compare value in MTIMERCMP register.

Remark

- Compare value is 64bits wide.
- If compare value is larger than current value timer interrupt generate.
- Modify the load value or compare value less to clear the interrupt.
- In S-mode, hartid can't be get by using __get_hart_id function, so this api suits S-mode particularly.
- SysTimer_GetHartCompareValue

Parameters

- `value` – **[in]** compare value to set system timer MTIMERCMP register.
- `hartid` – **[in]** hart ID, one hart is required to have a known hart ID of 0, other harts ID can be in 1~1023.

`__STATIC_FORCEINLINE void SysTimer_SetCompareValue (uint64_t value)`

Set system timer compare value in machine mode.

This function set the system Timer compare value in MTIMERCMP register.

Remark

- Compare value is 64bits wide.
- If compare value is larger than current value timer interrupt generate.
- Modify the load value or compare value less to clear the interrupt.
- __get_hart_id function can only be accessed in machine mode, or else exception will occur.

- SysTimer_GetCompareValue

Parameters `value` – **[in]** compare value to set system timer MTIMERCMP register.

`__STATIC_FORCEINLINE uint64_t SysTimer_GetHartCompareValue (unsigned long hartid)`

Get system timer compare value by hartid.

This function get the system timer compare value in MTIMERCMP register.

Remark

- Compare value is 64bits wide.
- In S-mode, hartid can't be get by using __get_hart_id function, so this api suits S-mode particularly.
- SysTimer_SetHartCompareValue

Parameters `hartid` – **[in]** hart ID, one hart is required to have a known hart ID of 0, other harts ID can be in 1~1023.

Returns compare value of system timer MTIMERCMP register.

`__STATIC_FORCEINLINE uint64_t SysTimer_GetCompareValue (void)`

Get system timer compare value in machine mode.

This function get the system timer compare value in MTIMERCMP register.

Remark

- Compare value is 64bits wide.
- SysTimer_SetCompareValue

Returns compare value of system timer MTIMERCMP register.

`__STATIC_FORCEINLINE void SysTimer_Start (void)`

Enable system timer counter running.

Enable system timer counter running by clear TIMESTOP bit in MTIMECTL register.

`__STATIC_FORCEINLINE void SysTimer_Stop (void)`

Stop system timer counter running.

Stop system timer counter running by set TIMESTOP bit in MTIMECTL register.

`__STATIC_FORCEINLINE void SysTimer_SetControlValue (uint32_t mctl)`

Set system timer control value.

This function set the system timer MTIMECTL register value.

Remark

- Bit TIMESTOP is used to start and stop timer. Clear TIMESTOP bit to 0 to start timer, otherwise to stop timer.
- Bit CMPCLREN is used to enable auto MTIMER clear to zero when MTIMER >= MTIMERCMP. Clear CMPCLREN bit to 0 to stop auto clear MTIMER feature, otherwise to enable it.
- Bit CLKSRC is used to select timer clock source. Clear CLKSRC bit to 0 to use *mtime_toggle_a*, otherwise use *core_clk_aon*
- SysTimer_GetControlValue

Parameters `mctl` – **[in]** value to set MTIMECTL register

`__STATIC_FORCEINLINE uint32_t SysTimer_GetControlValue (void)`

Get system timer control value.

This function get the system timer MTIMECTL register value.

Remark

- SysTimer_SetControlValue

Returns MTIMECTL register value

`__STATIC_FORCEINLINE void SysTimer_SetHartSWIRQ (unsigned long hartid)`

Trigger or set software interrupt via system timer by hartid.

This function set the system timer MSIP bit in MSIP register.

Remark

- Set system timer MSIP bit and generate a SW interrupt.
- In S-mode, hartid can't be get by using __get_hart_id function, so this api suits S-mode particularly.
- SysTimer_ClearHartSWIRQ
- SysTimer_GetHartMsipValue

Parameters `hartid` – **[in]** hart ID, one hart is required to have a known hart ID of 0, other harts ID can be in 1~1023.

`__STATIC_FORCEINLINE void SysTimer_SetSWIRQ (void)`

Trigger or set software interrupt via system timer in machine mode.

This function set the system timer MSIP bit in MSIP register.

Remark

- Set system timer MSIP bit and generate a SW interrupt.
- SysTimer_ClearSWIRQ
- SysTimer_GetMsipValue

`__STATIC_FORCEINLINE void SysTimer_ClearHartSWIRQ (unsigned long hartid)`

Clear system timer software interrupt pending request by hartid.

This function clear the system timer MSIP bit in MSIP register.

Remark

- Clear system timer MSIP bit in MSIP register to clear the software interrupt pending.
- In S-mode, hartid can't be get by using __get_hart_id function, so this api suits S-mode particularly.
- SysTimer_SetHartSWIRQ
- SysTimer_GetHartMsipValue

Parameters `hartid` – **[in]** hart ID, one hart is required to have a known hart ID of 0, other harts ID can be in 1~1023.

`__STATIC_FORCEINLINE void SysTimer_ClearSWIRQ (void)`

Clear system timer software interrupt pending request in machine mode.

This function clear the system timer MSIP bit in MSIP register.

Remark

- Clear system timer MSIP bit in MSIP register to clear the software interrupt pending.
- SysTimer_SetSWIRQ
- SysTimer_GetMsipValue

`__STATIC_FORCEINLINE uint32_t SysTimer_GetHartMsipValue (unsigned long hartid)`

Get system timer MSIP register value by hartid.

This function get the system timer MSIP register value.

Remark

- Bit0 is SW interrupt flag. Bit0 is 1 then SW interrupt set. Bit0 is 0 then SW interrupt clear.

- In S-mode, hartid can't be get by using __get_hart_id function, so this api suits S-mode particularly.
- SysTimer_SetHartSWIRQ
- SysTimer_ClearHartSWIRQ
- SysTimer_SetHartMsipValue

Parameters `hartid` – **[in]** hart ID, one hart is required to have a known hart ID of 0, other harts ID can be in 1~1023.

Returns Value of Timer MSIP register.

`__STATIC_FORCEINLINE uint32_t SysTimer_GetMsipValue (void)`

Get system timer MSIP register value in machine mode.

This function get the system timer MSIP register value.

Remark

- Bit0 is SW interrupt flag. Bit0 is 1 then SW interrupt set. Bit0 is 0 then SW interrupt clear.
- SysTimer_SetSWIRQ
- SysTimer_ClearSWIRQ
- SysTimer_SetMsipValue

Returns Value of Timer MSIP register.

`__STATIC_FORCEINLINE void SysTimer_SetHartMsipValue (uint32_t msip, unsigned long hartid)`

Set system timer MSIP register value by hartid.

This function set the system timer MSIP register value.

Remark

- In S-mode, hartid can't be get using __get_hart_id function, so this api suits S-mode particularly.
- SysTimer_GetHartMsipValue

Parameters

- `msip` – **[in]** value to set MSIP register
- `hartid` – **[in]** hart ID, one hart is required to have a known hart ID of 0, other harts ID can be in 1~1023.

`__STATIC_FORCEINLINE void SysTimer_SetMsipValue (uint32_t msip)`

Set system timer MSIP register value in machine mode.

This function set the system timer MSIP register value.

Parameters **msip** – **[in]** value to set MSIP register

- SysTimer_GetMsipValue

__STATIC_FORCEINLINE void SysTimer_SoftwareReset (void)

Do software reset request.

This function will do software reset request through MTIMER

- Software need to write *SysTimer_MSFRST_KEY* (page 146) to generate software reset request
- The software request flag can be cleared by reset operation to clear

Remark

- The software reset is sent to SoC, SoC need to generate reset signal and send back to Core
- This function will not return, it will do while(1) to wait the Core reset happened

__STATIC_FORCEINLINE void SysTimer_SendIPI (unsigned long hartid)

send ipi to target hart using Systimer Clint

This function send ipi using clint timer.

Parameters **hart** – **[in]** target hart

__STATIC_FORCEINLINE void SysTimer_ClearIPI (unsigned long hartid)

clear ipi to target hart using Systimer Clint

This function clear ipi using Systimer clint timer.

Parameters **hart** – **[in]** target hart

__STATIC_INLINE uint32_t SysTick_Config (uint64_t ticks)

System Tick Configuration.

Initializes the System Timer and its non-vector interrupt, and starts the System Tick Timer.

In our default implementation, the timer counter will be set to zero, and it will start a timer compare non-vector interrupt when it matchs the ticks user set, during the timer interrupt user should reload the system tick using SysTick_Reload function or similar function written by user, so it can produce period timer interrupt.

Remark

- For *__NUCLEI_N_REV* (page 77) >= 0x0104, the CMPCLREN bit in MTIMECTL is introduced, but we assume that the CMPCLREN bit is set to 0, so MTIMER register will not be auto cleared to 0 when MTIMER >= MTIMERCMP.
- When the variable __Vendor_SysTickConfig is set to 1, then the function SysTick_Config is not included.
- In this case, the file **<Device>.h** must contain a vendor-specific implementation of this function.

- If user need this function to start a period timer interrupt, then in timer interrupt handler routine code, user should call SysTick_Reload with ticks to reload the timer.
- This function only available when __SYSTIMER_PRESENT == 1 and __ECLIC_PRESENT == 1 and __Vendor_SysTickConfig == 0

See also:

- SysTimer_SetCompareValue; SysTimer_SetLoadValue

Parameters `ticks` – **[in]** Number of ticks between two interrupts.

Returns 0 Function succeeded.

Returns 1 Function failed.

`__STATIC_INLINE uint32_t SysTick_HartConfig (uint64_t ticks, unsigned long hartid)`

System Tick Configuration By hartid.

Initializes the System Timer and its non-vector interrupt, and starts the System Tick Timer.

In our default implementation, the timer counter will be set to zero, and it will start a timer compare non-vector interrupt when it matchs the ticks user set, during the timer interrupt user should reload the system tick using SysTick_Reload function or similar function written by user, so it can produce period timer interrupt.

Remark

- For *__NUCLEI_N_REV* (page 77) >= 0x0104, the CMPCLREN bit in MTIMECTL is introduced, but we assume that the CMPCLREN bit is set to 0, so MTIMER register will not be auto cleared to 0 when MTIMER >= MTIMERCMP.
- When the variable __Vendor_SysTickConfig is set to 1, then the function SysTick_Config is not included.
- In this case, the file **<Device>.h** must contain a vendor-specific implementation of this function.
- If user need this function to start a period timer interrupt, then in timer interrupt handler routine code, user should call SysTick_Reload with ticks to reload the timer.
- This function only available when __SYSTIMER_PRESENT == 1 and __ECLIC_PRESENT == 1 and __Vendor_SysTickConfig == 0
- In S-mode, hartid can't be get by using __get_hart_id function, so this api suits S-mode particularly.

See also:

- SysTimer_SetCompareValue; SysTimer_SetLoadValue

Parameters

- `ticks` – **[in]** Number of ticks between two interrupts.
- `hartid` – **[in]** hart ID, one hart is required to have a known hart ID of 0, other harts ID can be in 1~1023.

Returns 0 Function succeeded.

Returns 1 Function failed.

`__STATIC_FORCEINLINE uint32_t SysTick_Reload (uint64_t ticks)`

System Tick Reload.

Reload the System Timer Tick when the MTIMECMP reached TIME value

Remark

- For *__NUCLEI_N_REV* (page 77) >= 0x0104, the CMPCLREN bit in MTIMECTL is introduced, but for this SysTick_Config function, we assume this CMPCLREN bit is set to 0, so in interrupt handler function, user still need to set the MTIMERCMP or MTIMER to reload the system tick, if vendor want to use this timer's auto clear feature, they can define __Vendor_SysTickConfig to 1, and implement SysTick_Config and SysTick_Reload functions.
- When the variable __Vendor_SysTickConfig is set to 1, then the function SysTick_Reload is not included.
- In this case, the file **<Device>.h** must contain a vendor-specific implementation of this function.
- This function only available when __SYSTIMER_PRESENT == 1 and __ECLIC_PRESENT == 1 and __Vendor_SysTickConfig == 0
- Since the MTIMERCMP value might overflow, if overflowed, MTIMER will be set to 0, and MTIMERCMP set to ticks

See also:

- SysTimer_SetCompareValue
- SysTimer_SetLoadValue

Parameters `ticks` – **[in]** Number of ticks between two interrupts.

Returns 0 Function succeeded.

Returns 1 Function failed.

`__STATIC_FORCEINLINE uint32_t SysTick_HartReload (uint64_t ticks, unsigned long hartid)`

System Tick Reload.

Reload the System Timer Tick when the MTIMECMP reached TIME value

Remark

- For *__NUCLEI_N_REV* (page 77) >= 0x0104, the CMPCLREN bit in MTIMECTL is introduced, but for this SysTick_Config function, we assume this CMPCLREN bit is set to 0, so in interrupt handler function, user still need to set the MTIMERCMP or MTIMER to reload the system tick, if vendor want to use this timer's auto clear feature, they can define __Vendor_SysTickConfig to 1, and implement SysTick_Config and SysTick_Reload functions.

- When the variable __Vendor_SysTickConfig is set to 1, then the function SysTick_Reload is not included.
- In this case, the file **<Device>.h** must contain a vendor-specific implementation of this function.
- This function only available when __SYSTIMER_PRESENT == 1 and __ECLIC_PRESENT == 1 and __Vendor_SysTickConfig == 0
- Since the MTIMERCMP value might overflow, if overflowed, MTIMER will be set to 0, and MTIMERCMP set to ticks
- In S-mode, hartid can't be get by using __get_hart_id function, so this api suits S-mode particularly.

See also:

- SysTimer_SetCompareValue
- SysTimer_SetLoadValue

Parameters

- **ticks** – **[in]** Number of ticks between two interrupts.
- **hartid** – **[in]** hart ID, one hart is required to have a known hart ID of 0, other harts ID can be in 1~1023.

Returns 0 Function succeeded.

Returns 1 Function failed.

SysTick Code Example

The code below shows the usage of the function `SysTick_Config()` and `SysTick_Reload()` with an GD32VF103 SoC.

Listing 3: gd32vf103_systick_example.c

```
#include "gd32vf103.h"

volatile uint32_t msTicks = 0;                          /* Variable to store␣
↪millisecond ticks */

#define CONFIG_TICKS        (SOC_TIMER_FREQ / 1000)
#define SysTick_Handler     eclic_mtip_handler

void SysTick_Handler(void) {                            /* SysTick interrupt Handler.
↪ */
  SysTimer_Reload(CONFIG_TICKS);                        /* Call SysTick_Reload to␣
↪reload timer. */
  msTicks++;                                            /* See startup file startup_
↪gd32vf103.S for SysTick vector */
}
```

(continues on next page)

(continued from previous page)

```c

int main (void) {
  uint32_t returnCode;

  returnCode = SysTick_Config(CONFIG_TICKS);                /* Configure SysTick to generate an interrupt every millisecond */

  if (returnCode != 0) {                                    /* Check return code for errors */
    // Error Handling
  }

  while(1);
}
```

SysTimer Interrupt Code Example

The code below shows the usage of various NMSIS Timer Interrupt functions with an GD32VF103 device.

Listing 4: gd32vf103_timer_example1.c

```c
#include "gd32vf103.h"

void eclic_mtip_handler(void)
{
    uint64_t now =  SysTimer_GetLoadValue();
    SysTimer_SetCompareValue(now + SOC_TIMER_FREQ/100);
}

static uint32_t int_cnt = 0;
void eclic_msip_handler(void)
{
    SysTimer_ClearSWIRQ();
    int_cnt++;
}

void eclic_global_initialize(void)
{
    ECLIC_SetMth(0);
    ECLIC_SetCfgNlbits(3);
}

int eclic_register_interrupt(IRQn_Type IRQn, uint8_t shv, uint32_t trig_mode, uint32 lvl, uint32_t priority, void * handler)
{
    ECLIC_SetShvIRQ(IRQn, shv);
    ECLIC_SetTrigIRQ(IRQn, trig_mode);
    ECLIC_SetLevelIRQ(IRQn, lvl);
    ECLIC_SetPriorityIRQ(IRQn, priority);
    ECLIC_SetVector(IRQn, (rv_csr_t)(handler));
    ECLIC_EnableIRQ(IRQn);
```

(continues on next page)

(continued from previous page)

```c
    return 0;
}

void setup_timer(void)
{
    SysTimer_SetLoadValue(0);
    SysTimer_SetCompareValue(SOC_TIMER_FREQ/100);
}

int main (void)
{
    uint32_t returnCode;

    eclic_global_initialize();                                  /* initialize ECLIC */

    setup_timer();                                              /* initialize timer */

    returnCode = eclic_register_interrupt(SysTimer_IRQn,1,2,8,0,eclic_mtip_handler);  /* register system timer interrupt */

    returnCode = eclic_register_interrupt(SysTimerSW_IRQn,1,2,8,0,eclic_msip_handler);  /* register system timer SW interrupt */

    __enable_irq();                                             /* enable global interrupt */

    SysTimer_SetSWIRQ();                                        /* trigger timer SW interrupt */

    if (returnCode != 0) {                                      /* Check return code for errors */
      // Error Handling
    }

    while(1);
}
```

2.5.10 Interrupts and Exceptions

Description

This section explains how to use interrupts and exceptions and access functions for the Enhanced Core Local Interrupt Controller(ECLIC)[17].

Nuclei provides a template file startup_device for each supported compiler. The file must be adapted by the silicon vendor to include interrupt vectors for all device-specific interrupt handlers. Each interrupt handler is defined as a weak function to an dummy handler. These interrupt handlers can be used directly in application software without being adapted by the programmer.

Click Interrupt[18] to learn more about interrupt handling in Nuclei processor core.

[17] https://doc.nucleisys.com/nuclei_spec/isa/eclic.html

[18] https://doc.nucleisys.com/nuclei_spec/isa/interrupt.html

NMI Interrupt

NMI interrupt[19] entry is stored by **CSR_MNVEC**. If CSR_MMSIC[9] is 1 then NMI entry is the same as **Exception** which get from CSR_MTVEC. If CSR_MMSIC[9] is 1 NMI entry is reset vector.

Exception

Exception[20] has only 1 entry address which stored by CSR_MTVEC. All the exceptions will jump to the same entry `exc_entry` defined in `intexc_<Device>.S`.

The table below lists the core exception code of the Nuclei N/NX processors.

Table 7: Core exception code of the Nuclei N/NX processors

Exception Code	Value	Description
InsUnalign_EXCn	0	Instruction address misaligned
InsAccFault_EXCn	1	Instruction access fault
IlleIns_EXCn	2	Illegal instruction
Break_EXCn	3	Beakpoint
LdAddrUnalign_EXCn	4	Load address misaligned
LdFault_EXCn	5	Load access fault
StAddrUnalign_EXCn	6	Store or AMO address misaligned
StAccessFault_EXCn	7	Store or AMO access fault
UmodeEcall_EXCn	8	Environment call from User mode
SmodeEcall_EXCn	9	Environment call from Supervisor Mode
MmodeEcall_EXCn	11	Environment call from Machine mode
InsPageFault_EXCn	12	Instruction page fault
LdPageFault_EXCn	13	Load page fault
StPageFault_EXCn	15	Store or AMO page fault
StackOverflow_EXCn	24	Stack overflow fault
StackUnderflow_EXCn	25	Stack overflow fault
NMI_EXCn	0xfff	NMI interrupt

Vector Table

The Vector Table defines the entry addresses of the ECLIC managed interrupts.

It is typically located at the beginning of the program memory, and you can modify CSR MTVT to reallocate the base address of this vector table, but you need to take care of the base address alignment according to the number of interrupts.

Table 8: base address alignment according to the number of interrupts

Number of Interrupt	Alignment Requirements of CSR MTVT
0 to 16	64-byte
17 to 32	128-byte
33 to 64	256-byte
65 to 128	512-byte
129 to 256	1KB
257 to 512	2KB
513 to 1024	4KB

[19] https://doc.nucleisys.com/nuclei_spec/isa/nmi.html
[20] https://doc.nucleisys.com/nuclei_spec/isa/exception.html

Interrupt number 0~18 is reserved by Nuclei Core. 19~1023 could be used by Silicon Vendor Device.

Below is an example interrupt allocated table:

```
typedef enum IRQn {
    /******  Nuclei N/NX Processor Core Internal Interrupt Numbers *************************/
    Reserved0_IRQn            =   0,     /*!<  Internal reserved                  */
    Reserved1_IRQn            =   1,     /*!<  Internal reserved                  */
    Reserved2_IRQn            =   2,     /*!<  Internal reserved                  */
    SysTimerSW_IRQn           =   3,     /*!<  System Timer SW interrupt          */
    Reserved3_IRQn            =   4,     /*!<  Internal reserved                  */
    Reserved4_IRQn            =   5,     /*!<  Internal reserved                  */
    Reserved5_IRQn            =   6,     /*!<  Internal reserved                  */
    SysTimer_IRQn             =   7,     /*!<  System Timer Interrupt             */
    Reserved6_IRQn            =   8,     /*!<  Internal reserved                  */
    Reserved7_IRQn            =   9,     /*!<  Internal reserved                  */
    Reserved8_IRQn            =  10,     /*!<  Internal reserved                  */
    Reserved9_IRQn            =  11,     /*!<  Internal reserved                  */
    Reserved10_IRQn           =  12,     /*!<  Internal reserved                  */
    Reserved11_IRQn           =  13,     /*!<  Internal reserved                  */
    Reserved12_IRQn           =  14,     /*!<  Internal reserved                  */
    Reserved13_IRQn           =  15,     /*!<  Internal reserved                  */
    Reserved14_IRQn           =  16,     /*!<  Internal reserved                  */
    HardFault_IRQn            =  17,     /*!<  Hard Fault, storage access error   */
    Reserved15_IRQn           =  18,     /*!<  Internal reserved                  */

    /******  GD32VF103 Specific External Interrupt Numbers *********************************/
    WWDGT_IRQn                =  19,     /*!< window watchDog timer interrupt     */
    LVD_IRQn                  =  20,     /*!< LVD through EXTI line detect interrupt */
    TAMPER_IRQn               =  21,     /*!< tamper through EXTI line detect     */
```

(continues on next page)

(continued from previous page)

```
                    :        :
                    :        :
    CAN1_EWMC_IRQn                = 85,     /*!< CAN1 EWMC interrupt                    ␣
↪   */
    USBFS_IRQn                    = 86,     /*!< USBFS global interrupt                 ␣
↪   */
    SOC_INT_MAX,                            /*!< Number of total Interrupts             ␣
↪   */
} IRQn_Type;
```

ECLIC API Definitions

When macro NMSIS_ECLIC_VIRTUAL is defined, the ECLIC access functions in the table below must be implemented for virtualizing ECLIC access.

These functions should be implemented in a separate source module. The original NMSIS-Core __ECLIC_xxx functions are always available independent of NMSIS_ECLIC_VIRTUAL macro.

Table 9: ECLIC Access Functions

ECLIC ACCESS FUNCTIONS	NMSIS-CORE FUNCTIONS FOR ECLIC
ECLIC_SetCfgNlbits (page 562)	__ECLIC_SetCfgNlbits()
ECLIC_GetCfgNlbits (page 562)	__ECLIC_GetCfgNlbits()
ECLIC_GetInfoVer (page 563)	__ECLIC_GetInfoVer()
ECLIC_GetInfoCtlbits (page 563)	__ECLIC_GetInfoCtlbits()
ECLIC_GetInfoNum (page 563)	__ECLIC_GetInfoNum()
ECLIC_SetMth (page 563)	__ECLIC_SetMth()
ECLIC_GetMth (page 563)	__ECLIC_GetMth()
ECLIC_EnableIRQ (page 563)	__ECLIC_EnableIRQ()
ECLIC_GetEnableIRQ (page 563)	__ECLIC_GetEnableIRQ()
ECLIC_DisableIRQ (page 563)	__ECLIC_DisableIRQ()
ECLIC_SetPendingIRQ (page 563)	__ECLIC_SetPendingIRQ()
ECLIC_GetPendingIRQ (page 563)	__ECLIC_GetPendingIRQ()
ECLIC_ClearPendingIRQ (page 563)	__ECLIC_ClearPendingIRQ()
ECLIC_SetTrigIRQ (page 563)	__ECLIC_SetTrigIRQ()
ECLIC_GetTrigIRQ (page 563)	__ECLIC_GetTrigIRQ()
ECLIC_SetShvIRQ (page 563)	__ECLIC_SetShvIRQ()
ECLIC_GetShvIRQ (page 563)	__ECLIC_GetShvIRQ()
ECLIC_SetCtrlIRQ (page 563)	__ECLIC_SetCtrlIRQ()
ECLIC_GetCtrlIRQ (page 563)	__ECLIC_GetCtrlIRQ()
ECLIC_SetLevelIRQ (page 563)	__ECLIC_SetLevelIRQ()
ECLIC_GetLevelIRQ (page 563)	__ECLIC_GetLevelIRQ()
ECLIC_SetPriorityIRQ (page 563)	__ECLIC_SetPriorityIRQ()
ECLIC_GetPriorityIRQ (page 563)	__ECLIC_GetPriorityIRQ()

When NMSIS_VECTAB_VIRTUAL macro is defined, the functions in the table below must be replaced to virtualize the API access functions to the interrupt vector table.

The ECLIC vector table API should be implemented in a separate source module.

This allows, for example, alternate implementations to relocate the vector table from flash to RAM on the first vector table update.

The original NMSIS-Core functions are always available, but prefixed with `__ECLIC`.

Table 10: ECLIC Vector Access Functions

ECLIC Vector Table Access	NMSIS-CORE FUNCTIONS
ECLIC_SetVector (page 564)	`__ECLIC_SetVector()`
ECLIC_GetVector (page 564)	`__ECLIC_GetVector()`

ECLIC Function Usage

The code below shows the usage of various NMSIS ECLIC flow with an GD32VF103 device.

Listing 5: gd32vf103_interrupt_example1.c

```c
#include "gd32vf103.h"

// Vector interrupt which could be nested
__INTERRUPT void eclic_button1_handler(void)
{
    SAVE_IRQ_CSR_CONTEXT();                                              /* save mepc,mcause,msubm enable interrupts */

    GPIO_REG(GPIO_OUTPUT_VAL) |= (1 << GREEN_LED_GPIO_OFFSET);           /* Green LED On */
    GPIO_REG(GPIO_RISE_IP) = (0x1 << BUTTON_1_GPIO_OFFSET);              /* Clear the GPIO Pending interrupt by writing 1. */

    RESTORE_IRQ_CSR_CONTEXT();                                           /* disable interrupts,restore mepc,mcause,msubm */
}

// Non-vector interrupt
void eclic_button2_handler(void)
{
    GPIO_REG(GPIO_OUTPUT_VAL) |= (1 << GREEN_LED_GPIO_OFFSET);           /* Green LED On */
    GPIO_REG(GPIO_RISE_IP) = (0x1 << BUTTON_2_GPIO_OFFSET);              /* Clear the GPIO Pending interrupt by writing 1. */
}

void eclic_global_initialize(void)
{
    ECLIC_SetMth(0);
    ECLIC_SetCfgNlbits(3);
}

int eclic_register_interrupt(IRQn_Type IRQn, uint8_t shv, uint32_t trig_mode, uint32 lvl, uint32_t priority, void * handler)
{
    ECLIC_SetShvIRQ(IRQn, shv);
    ECLIC_SetTrigIRQ(IRQn, trig_mode);
    ECLIC_SetLevelIRQ(IRQn, lvl);
    ECLIC_SetPriorityIRQ(IRQn, priority);
    ECLIC_SetVector(IRQn, (rv_csr_t)(handler));
    ECLIC_EnableIRQ(IRQn);
```

(continues on next page)

(continued from previous page)

```c
    return 0;
}

int main (void)
{
    uint32_t returnCode;

    eclic_global_initialize();                              /* initialize ECLIC */

    GPIO_init();                                            /* initialize GPIO */

    returnCode = eclic_register_interrupt(BTN1_IRQn,1,2,1,0,Button1_IRQHandler);  /*␣
↪register system button1 interrupt */
    returnCode = eclic_register_interrupt(BTN2_IRQn,0,2,2,0,Button2_IRQHandler);  /*␣
↪register system button2 interrupt */

    __enable_irq();                                         /* enable global interrupt␣
↪*/

    if (returnCode != 0)  {                                 /* Check return code for␣
↪errors */
      // Error Handling
    }

    while(1);
}
```

Interrupt and Exception API

enum **IRQn**

Values:

enumerator **Reserved0_IRQn**

enumerator **Reserved1_IRQn**

enumerator **Reserved2_IRQn**

enumerator **SysTimerSW_IRQn**

enumerator **Reserved3_IRQn**

enumerator **Reserved4_IRQn**

enumerator **Reserved5_IRQn**

enumerator SysTimer_IRQn

enumerator Reserved6_IRQn

enumerator Reserved7_IRQn

enumerator Reserved8_IRQn

enumerator Reserved9_IRQn

enumerator Reserved10_IRQn

enumerator Reserved11_IRQn

enumerator Reserved12_IRQn

enumerator Reserved13_IRQn

enumerator Reserved14_IRQn

enumerator Reserved15_IRQn

enumerator Reserved16_IRQn

enumerator FirstDeviceSpecificInterrupt_IRQn

enumerator SOC_INT_MAX

__STATIC_FORCEINLINE void __ECLIC_SetCfgNlbits (uint32_t nlbits)

__STATIC_FORCEINLINE uint32_t __ECLIC_GetCfgNlbits (void)

__STATIC_FORCEINLINE uint32_t __ECLIC_GetInfoVer (void)

__STATIC_FORCEINLINE uint32_t __ECLIC_GetInfoCtlbits (void)

__STATIC_FORCEINLINE uint32_t __ECLIC_GetInfoNum (void)

__STATIC_FORCEINLINE void __ECLIC_SetMth (uint8_t mth)

__STATIC_FORCEINLINE uint8_t __ECLIC_GetMth (void)

```
__STATIC_FORCEINLINE void __ECLIC_EnableIRQ (IRQn_Type IRQn)

__STATIC_FORCEINLINE uint32_t __ECLIC_GetEnableIRQ (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_DisableIRQ (IRQn_Type IRQn)

__STATIC_FORCEINLINE int32_t __ECLIC_GetPendingIRQ (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_SetPendingIRQ (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_ClearPendingIRQ (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_SetTrigIRQ (IRQn_Type IRQn, uint32_t trig)

__STATIC_FORCEINLINE uint32_t __ECLIC_GetTrigIRQ (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_SetShvIRQ (IRQn_Type IRQn, uint32_t shv)

__STATIC_FORCEINLINE uint32_t __ECLIC_GetShvIRQ (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_SetCtrlIRQ (IRQn_Type IRQn, uint8_t intctrl)

__STATIC_FORCEINLINE uint8_t __ECLIC_GetCtrlIRQ (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_SetLevelIRQ (IRQn_Type IRQn, uint8_t lvl_abs)

__STATIC_FORCEINLINE uint8_t __ECLIC_GetLevelIRQ (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_SetPriorityIRQ (IRQn_Type IRQn, uint8_t pri)

__STATIC_FORCEINLINE uint8_t __ECLIC_GetPriorityIRQ (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_SetVector (IRQn_Type IRQn, rv_csr_t vector)

__STATIC_FORCEINLINE rv_csr_t __ECLIC_GetVector (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_SetModeIRQ (IRQn_Type IRQn, uint32_t mode)

__STATIC_FORCEINLINE void __ECLIC_SetSth (uint8_t sth)

__STATIC_FORCEINLINE uint8_t __ECLIC_GetSth (void)
```

__STATIC_FORCEINLINE void __ECLIC_SetTrigIRQ_S (IRQn_Type IRQn, uint32_t trig)

__STATIC_FORCEINLINE uint8_t __ECLIC_GetTrigIRQ_S (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_SetShvIRQ_S (IRQn_Type IRQn, uint32_t shv)

__STATIC_FORCEINLINE uint8_t __ECLIC_GetShvIRQ_S (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_SetCtrlIRQ_S (IRQn_Type IRQn, uint8_t intctrl)

__STATIC_FORCEINLINE uint8_t __ECLIC_GetCtrlIRQ_S (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_SetLevelIRQ_S (IRQn_Type IRQn, uint8_t lvl_abs)

__STATIC_FORCEINLINE uint8_t __ECLIC_GetLevelIRQ_S (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_SetPriorityIRQ_S (IRQn_Type IRQn, uint8_t pri)

__STATIC_FORCEINLINE uint8_t __ECLIC_GetPriorityIRQ_S (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_EnableIRQ_S (IRQn_Type IRQn)

__STATIC_FORCEINLINE uint8_t __ECLIC_GetEnableIRQ_S (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_DisableIRQ_S (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __ECLIC_SetVector_S (IRQn_Type IRQn, rv_csr_t vector)

__STATIC_FORCEINLINE rv_csr_t __ECLIC_GetVector_S (IRQn_Type IRQn)

__STATIC_FORCEINLINE void __set_exc_entry (rv_csr_t addr)

__STATIC_FORCEINLINE rv_csr_t __get_exc_entry (void)

__STATIC_FORCEINLINE void __set_nonvec_entry (rv_csr_t addr)

__STATIC_FORCEINLINE rv_csr_t __get_nonvec_entry (void)

__STATIC_FORCEINLINE rv_csr_t __get_nmi_entry (void)

ECLIC_SetCfgNlbits __ECLIC_SetCfgNlbits

ECLIC_GetCfgNlbits __ECLIC_GetCfgNlbits

ECLIC_GetInfoVer __ECLIC_GetInfoVer

ECLIC_GetInfoCtlbits __ECLIC_GetInfoCtlbits

ECLIC_GetInfoNum __ECLIC_GetInfoNum

ECLIC_SetMth __ECLIC_SetMth

ECLIC_GetMth __ECLIC_GetMth

ECLIC_EnableIRQ __ECLIC_EnableIRQ

ECLIC_GetEnableIRQ __ECLIC_GetEnableIRQ

ECLIC_DisableIRQ __ECLIC_DisableIRQ

ECLIC_SetPendingIRQ __ECLIC_SetPendingIRQ

ECLIC_GetPendingIRQ __ECLIC_GetPendingIRQ

ECLIC_ClearPendingIRQ __ECLIC_ClearPendingIRQ

ECLIC_SetTrigIRQ __ECLIC_SetTrigIRQ

ECLIC_GetTrigIRQ __ECLIC_GetTrigIRQ

ECLIC_SetShvIRQ __ECLIC_SetShvIRQ

ECLIC_GetShvIRQ __ECLIC_GetShvIRQ

ECLIC_SetCtrlIRQ __ECLIC_SetCtrlIRQ

ECLIC_GetCtrlIRQ __ECLIC_GetCtrlIRQ

ECLIC_SetLevelIRQ __ECLIC_SetLevelIRQ

ECLIC_GetLevelIRQ __ECLIC_GetLevelIRQ

ECLIC_SetPriorityIRQ __ECLIC_SetPriorityIRQ

ECLIC_GetPriorityIRQ __ECLIC_GetPriorityIRQ

ECLIC_SetModeIRQ __ECLIC_SetModeIRQ

ECLIC_SetSth __ECLIC_SetSth

ECLIC_GetSth __ECLIC_GetSth

ECLIC_SetTrigIRQ_S __ECLIC_SetTrigIRQ_S

ECLIC_GetTrigIRQ_S __ECLIC_GetTrigIRQ_S

ECLIC_SetShvIRQ_S __ECLIC_SetShvIRQ_S

ECLIC_GetShvIRQ_S __ECLIC_GetShvIRQ_S

ECLIC_SetCtrlIRQ_S __ECLIC_SetCtrlIRQ_S

ECLIC_GetCtrlIRQ_S __ECLIC_GetCtrlIRQ_S

ECLIC_SetLevelIRQ_S __ECLIC_SetLevelIRQ_S

ECLIC_GetLevelIRQ_S __ECLIC_GetLevelIRQ_S

ECLIC_SetPriorityIRQ_S __ECLIC_SetPriorityIRQ_S

ECLIC_GetPriorityIRQ_S __ECLIC_GetPriorityIRQ_S

ECLIC_EnableIRQ_S __ECLIC_EnableIRQ_S

ECLIC_GetEnableIRQ_S __ECLIC_GetEnableIRQ_S

ECLIC_DisableIRQ_S __ECLIC_DisableIRQ_S

ECLIC_SetVector __ECLIC_SetVector

ECLIC_GetVector __ECLIC_GetVector

ECLIC_SetVector_S __ECLIC_SetVector_S

ECLIC_GetVector_S __ECLIC_GetVector_S

SAVE_IRQ_CSR_CONTEXT()

SAVE_IRQ_CSR_CONTEXT_S()

RESTORE_IRQ_CSR_CONTEXT()

RESTORE_IRQ_CSR_CONTEXT_S()

group **NMSIS_Core_IntExc**

Functions that manage interrupts and exceptions via the ECLIC.

Defines

ECLIC_SetCfgNlbits __ECLIC_SetCfgNlbits

ECLIC_GetCfgNlbits __ECLIC_GetCfgNlbits

ECLIC_GetInfoVer __ECLIC_GetInfoVer

ECLIC_GetInfoCtlbits __ECLIC_GetInfoCtlbits

ECLIC_GetInfoNum __ECLIC_GetInfoNum

ECLIC_SetMth __ECLIC_SetMth

ECLIC_GetMth __ECLIC_GetMth

ECLIC_EnableIRQ __ECLIC_EnableIRQ

ECLIC_GetEnableIRQ __ECLIC_GetEnableIRQ

ECLIC_DisableIRQ __ECLIC_DisableIRQ

ECLIC_SetPendingIRQ __ECLIC_SetPendingIRQ

ECLIC_GetPendingIRQ __ECLIC_GetPendingIRQ

ECLIC_ClearPendingIRQ __ECLIC_ClearPendingIRQ

ECLIC_SetTrigIRQ __ECLIC_SetTrigIRQ

ECLIC_GetTrigIRQ __ECLIC_GetTrigIRQ

ECLIC_SetShvIRQ __ECLIC_SetShvIRQ

ECLIC_GetShvIRQ __ECLIC_GetShvIRQ

ECLIC_SetCtrlIRQ __ECLIC_SetCtrlIRQ

ECLIC_GetCtrlIRQ __ECLIC_GetCtrlIRQ

ECLIC_SetLevelIRQ __ECLIC_SetLevelIRQ

ECLIC_GetLevelIRQ __ECLIC_GetLevelIRQ

ECLIC_SetPriorityIRQ __ECLIC_SetPriorityIRQ

ECLIC_GetPriorityIRQ __ECLIC_GetPriorityIRQ

ECLIC_SetModeIRQ __ECLIC_SetModeIRQ

ECLIC_SetSth __ECLIC_SetSth

ECLIC_GetSth __ECLIC_GetSth

ECLIC_SetTrigIRQ_S __ECLIC_SetTrigIRQ_S

ECLIC_GetTrigIRQ_S __ECLIC_GetTrigIRQ_S

ECLIC_SetShvIRQ_S __ECLIC_SetShvIRQ_S

ECLIC_GetShvIRQ_S __ECLIC_GetShvIRQ_S

ECLIC_SetCtrlIRQ_S __ECLIC_SetCtrlIRQ_S

ECLIC_GetCtrlIRQ_S __ECLIC_GetCtrlIRQ_S

ECLIC_SetLevelIRQ_S __ECLIC_SetLevelIRQ_S

ECLIC_GetLevelIRQ_S __ECLIC_GetLevelIRQ_S

ECLIC_SetPriorityIRQ_S __ECLIC_SetPriorityIRQ_S

ECLIC_GetPriorityIRQ_S __ECLIC_GetPriorityIRQ_S

ECLIC_EnableIRQ_S __ECLIC_EnableIRQ_S

ECLIC_GetEnableIRQ_S __ECLIC_GetEnableIRQ_S

ECLIC_DisableIRQ_S __ECLIC_DisableIRQ_S

ECLIC_SetVector __ECLIC_SetVector

ECLIC_GetVector __ECLIC_GetVector

ECLIC_SetVector_S __ECLIC_SetVector_S

ECLIC_GetVector_S __ECLIC_GetVector_S

SAVE_IRQ_CSR_CONTEXT()

Save necessary CSRs into variables for vector interrupt nesting.

This macro is used to declare variables which are used for saving CSRs(MCAUSE, MEPC, MSUB), and it will read these CSR content into these variables, it need to be used in a vector-interrupt if nesting is required.

Remark

- Interrupt will be enabled after this macro is called
- It need to be used together with RESTORE_IRQ_CSR_CONTEXT
- Don't use variable names __mcause, __mpec, __msubm in your ISR code
- If you want to enable interrupt nesting feature for vector interrupt, you can do it like this:

```
// __INTERRUPT attribute will generates function entry and exit sequences␣
↪suitable
// for use in an interrupt handler when this attribute is present
__INTERRUPT void eclic_mtip_handler(void)
{
    // Must call this to save CSRs
    SAVE_IRQ_CSR_CONTEXT();
    // !!!Interrupt is enabled here!!!
    // !!!Higher priority interrupt could nest it!!!

    // put you own interrupt handling code here

    // Must call this to restore CSRs
    RESTORE_IRQ_CSR_CONTEXT();
}
```

SAVE_IRQ_CSR_CONTEXT_S()

Save necessary CSRs into variables for vector interrupt nesting in supervisor mode.

`RESTORE_IRQ_CSR_CONTEXT()`

Restore necessary CSRs from variables for vector interrupt nesting.

This macro is used restore CSRs(MCAUSE, MEPC, MSUB) from pre-defined variables in SAVE_IRQ_CSR_CONTEXT macro.

Remark

- Interrupt will be disabled after this macro is called
- It need to be used together with SAVE_IRQ_CSR_CONTEXT

`RESTORE_IRQ_CSR_CONTEXT_S()`

Restore necessary CSRs from variables for vector interrupt nesting in supervisor mode.

Enums

enum **IRQn**

Definition of IRQn numbers.

The core interrupt enumeration names for IRQn values are defined in the file **<Device>.h**.

- Interrupt ID(IRQn) from 0 to 18 are reserved for core internal interrupts.
- Interrupt ID(IRQn) start from 19 represent device-specific external interrupts.
- The first device-specific interrupt has the IRQn value 19.

The table below describes the core interrupt names and their availability in various Nuclei Cores.

Values:

enumerator **Reserved0_IRQn**

Internal reserved.

enumerator **Reserved1_IRQn**

Internal reserved.

enumerator **Reserved2_IRQn**

Internal reserved.

enumerator **SysTimerSW_IRQn**

System Timer SW interrupt.

enumerator **Reserved3_IRQn**

Internal reserved.

enumerator **Reserved4_IRQn**

Internal reserved.

enumerator `Reserved5_IRQn`

Internal reserved.

enumerator `SysTimer_IRQn`

System Timer Interrupt.

enumerator `Reserved6_IRQn`

Internal reserved.

enumerator `Reserved7_IRQn`

Internal reserved.

enumerator `Reserved8_IRQn`

Internal reserved.

enumerator `Reserved9_IRQn`

Internal reserved.

enumerator `Reserved10_IRQn`

Internal reserved.

enumerator `Reserved11_IRQn`

Internal reserved.

enumerator `Reserved12_IRQn`

Internal reserved.

enumerator `Reserved13_IRQn`

Internal reserved.

enumerator `Reserved14_IRQn`

Internal reserved.

enumerator `Reserved15_IRQn`

Internal reserved.

enumerator `Reserved16_IRQn`

Internal reserved.

enumerator `FirstDeviceSpecificInterrupt_IRQn`

First Device Specific Interrupt.

enumerator `SOC_INT_MAX`

Number of total interrupts.

Functions

`__STATIC_FORCEINLINE void __ECLIC_SetCfgNlbits (uint32_t nlbits)`

Set nlbits value.

This function set the nlbits value of CLICCFG register.

Remark

- nlbits is used to set the width of level in the CLICINTCTL[i].

See also:

- ECLIC_GetCfgNlbits

Parameters **`nlbits`** – **[in]** nlbits value

`__STATIC_FORCEINLINE uint32_t __ECLIC_GetCfgNlbits (void)`

Get nlbits value.

This function get the nlbits value of CLICCFG register.

Remark

- nlbits is used to set the width of level in the CLICINTCTL[i].

See also:

- ECLIC_SetCfgNlbits

Returns nlbits value of CLICCFG register

`__STATIC_FORCEINLINE uint32_t __ECLIC_GetInfoVer (void)`

Get the ECLIC version number.

This function gets the hardware version information from CLICINFO register.

Remark

- This function gets harware version information from CLICINFO register.
- Bit 20:17 for architecture version, bit 16:13 for implementation version.

See also:

- ECLIC_GetInfoNum

  Returns hardware version number in CLICINFO register.

`__STATIC_FORCEINLINE uint32_t __ECLIC_GetInfoCtlbits (void)`

Get CLICINTCTLBITS.

This function gets CLICINTCTLBITS from CLICINFO register.

Remark

- In the CLICINTCTL[i] registers, with 2 <= CLICINTCTLBITS <= 8.
- The implemented bits are kept left-justified in the most-significant bits of each 8-bit CLICINTCTL[I] register, with the lower unimplemented bits treated as hardwired to 1.

See also:

- ECLIC_GetInfoNum

  Returns CLICINTCTLBITS from CLICINFO register.

`__STATIC_FORCEINLINE uint32_t __ECLIC_GetInfoNum (void)`

Get number of maximum interrupt inputs supported.

This function gets number of maximum interrupt inputs supported from CLICINFO register.

Remark

- This function gets number of maximum interrupt inputs supported from CLICINFO register.
- The num_interrupt field specifies the actual number of maximum interrupt inputs supported in this implementation.

See also:

- ECLIC_GetInfoCtlbits

  Returns number of maximum interrupt inputs supported from CLICINFO register.

`__STATIC_FORCEINLINE void __ECLIC_SetMth (uint8_t mth)`

Set Machine Mode Interrupt Level Threshold.

This function sets machine mode interrupt level threshold.

See also:

- ECLIC_GetMth

Parameters `mth` – **[in]** Interrupt Level Threshold.

`__STATIC_FORCEINLINE uint8_t __ECLIC_GetMth (void)`

Get Machine Mode Interrupt Level Threshold.

This function gets machine mode interrupt level threshold.

See also:

- ECLIC_SetMth

Returns Interrupt Level Threshold.

`__STATIC_FORCEINLINE void __ECLIC_EnableIRQ (IRQn_Type IRQn)`

Enable a specific interrupt.

This function enables the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_DisableIRQ

Parameters `IRQn` – **[in]** Interrupt number

`__STATIC_FORCEINLINE uint32_t __ECLIC_GetEnableIRQ (IRQn_Type IRQn)`

Get a specific interrupt enable status.

This function returns the interrupt enable status for the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_EnableIRQ
- ECLIC_DisableIRQ

Parameters `IRQn` – **[in]** Interrupt number

Returns

- 0 Interrupt is not enabled

- 1 Interrupt is pending

`__STATIC_FORCEINLINE void __ECLIC_DisableIRQ (IRQn_Type IRQn)`

Disable a specific interrupt.

This function disables the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_EnableIRQ

Parameters `IRQn` – **[in]** Number of the external interrupt to disable

`__STATIC_FORCEINLINE int32_t __ECLIC_GetPendingIRQ (IRQn_Type IRQn)`

Get the pending specific interrupt.

This function returns the pending status of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_SetPendingIRQ
- ECLIC_ClearPendingIRQ

Parameters `IRQn` – **[in]** Interrupt number

Returns

- 0 Interrupt is not pending
- 1 Interrupt is pending

`__STATIC_FORCEINLINE void __ECLIC_SetPendingIRQ (IRQn_Type IRQn)`

Set a specific interrupt to pending.

This function sets the pending bit for the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_GetPendingIRQ
- ECLIC_ClearPendingIRQ

Parameters **IRQn** – **[in]** Interrupt number

`__STATIC_FORCEINLINE void __ECLIC_ClearPendingIRQ (IRQn_Type IRQn)`

Clear a specific interrupt from pending.

This function removes the pending state of the specific interrupt *IRQn*. *IRQn* cannot be a negative number.

Remark

- IRQn must not be negative.

See also:

- ECLIC_SetPendingIRQ
- ECLIC_GetPendingIRQ

Parameters **IRQn** – **[in]** Interrupt number

`__STATIC_FORCEINLINE void __ECLIC_SetTrigIRQ (IRQn_Type IRQn, uint32_t trig)`

Set trigger mode and polarity for a specific interrupt.

This function set trigger mode and polarity of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_GetTrigIRQ

Parameters

- **IRQn** – **[in]** Interrupt number
- **trig** – **[in]**
  - 00 level trigger, *ECLIC_LEVEL_TRIGGER* (page 143)
  - 01 positive edge trigger, *ECLIC_POSTIVE_EDGE_TRIGGER* (page 143)
  - 02 level trigger, *ECLIC_LEVEL_TRIGGER* (page 143)

- 03 negative edge trigger, *ECLIC_NEGTIVE_EDGE_TRIGGER* (page 143)

`__STATIC_FORCEINLINE uint32_t __ECLIC_GetTrigIRQ (IRQn_Type IRQn)`

Get trigger mode and polarity for a specific interrupt.

This function get trigger mode and polarity of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_SetTrigIRQ

Parameters **`IRQn`** – **[in]** Interrupt number

Returns

- 00 level trigger, *ECLIC_LEVEL_TRIGGER* (page 143)
- 01 positive edge trigger, *ECLIC_POSTIVE_EDGE_TRIGGER* (page 143)
- 02 level trigger, *ECLIC_LEVEL_TRIGGER* (page 143)
- 03 negative edge trigger, *ECLIC_NEGTIVE_EDGE_TRIGGER* (page 143)

`__STATIC_FORCEINLINE void __ECLIC_SetShvIRQ (IRQn_Type IRQn, uint32_t shv)`

Set interrupt working mode for a specific interrupt.

This function set selective hardware vector or non-vector working mode of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_GetShvIRQ

Parameters

- **`IRQn`** – **[in]** Interrupt number
- **`shv`** – **[in]**
  - 0 non-vector mode, *ECLIC_NON_VECTOR_INTERRUPT* (page 143)
  - 1 vector mode, *ECLIC_VECTOR_INTERRUPT* (page 143)

`__STATIC_FORCEINLINE uint32_t __ECLIC_GetShvIRQ (IRQn_Type IRQn)`

Get interrupt working mode for a specific interrupt.

This function get selective hardware vector or non-vector working mode of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_SetShvIRQ

Parameters **IRQn** – **[in]** Interrupt number

Returns shv

- 0 non-vector mode, *ECLIC_NON_VECTOR_INTERRUPT* (page 143)
- 1 vector mode, *ECLIC_VECTOR_INTERRUPT* (page 143)

`__STATIC_FORCEINLINE void __ECLIC_SetCtrlIRQ (IRQn_Type IRQn, uint8_t intctrl)`

Modify ECLIC Interrupt Input Control Register for a specific interrupt.

This function modify ECLIC Interrupt Input Control(CLICINTCTL[i]) register of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_GetCtrlIRQ

Parameters

- **IRQn** – **[in]** Interrupt number
- **intctrl** – **[in]** Set value for CLICINTCTL[i] register

`__STATIC_FORCEINLINE uint8_t __ECLIC_GetCtrlIRQ (IRQn_Type IRQn)`

Get ECLIC Interrupt Input Control Register value for a specific interrupt.

This function modify ECLIC Interrupt Input Control register of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_SetCtrlIRQ

Parameters `IRQn` – **[in]** Interrupt number

Returns value of ECLIC Interrupt Input Control register

`__STATIC_FORCEINLINE void __ECLIC_SetLevelIRQ (IRQn_Type IRQn, uint8_t lvl_abs)`

Set ECLIC Interrupt level of a specific interrupt.

This function set interrupt level of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.
- If lvl_abs to be set is larger than the max level allowed, it will be force to be max level.
- When you set level value you need use clciinfo.nlbits to get the width of level. Then we could know the maximum of level. CLICINTCTLBITS is how many total bits are present in the CLICINTCTL register.

See also:

- ECLIC_GetLevelIRQ

Parameters

- `IRQn` – **[in]** Interrupt number
- `lvl_abs` – **[in]** Interrupt level

`__STATIC_FORCEINLINE uint8_t __ECLIC_GetLevelIRQ (IRQn_Type IRQn)`

Get ECLIC Interrupt level of a specific interrupt.

This function get interrupt level of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_SetLevelIRQ

Parameters `IRQn` – **[in]** Interrupt number

Returns Interrupt level

`__STATIC_FORCEINLINE void __ECLIC_SetPriorityIRQ (IRQn_Type IRQn, uint8_t pri)`

Get ECLIC Interrupt priority of a specific interrupt.

This function get interrupt priority of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.
- If pri to be set is larger than the max priority allowed, it will be force to be max priority.
- Priority width is CLICINTCTLBITS minus clciinfo.nlbits if clciinfo.nlbits is less than CLICINTCTLBITS. Otherwise priority width is 0.

See also:

- ECLIC_GetPriorityIRQ

Parameters

- **IRQn** – **[in]** Interrupt number
- **pri** – **[in]** Interrupt priority

`__STATIC_FORCEINLINE uint8_t __ECLIC_GetPriorityIRQ (IRQn_Type IRQn)`

Get ECLIC Interrupt priority of a specific interrupt.

This function get interrupt priority of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_SetPriorityIRQ

Parameters **IRQn** – **[in]** Interrupt number

Returns Interrupt priority

`__STATIC_FORCEINLINE void __ECLIC_SetVector (IRQn_Type IRQn, rv_csr_t vector)`

Set Interrupt Vector of a specific interrupt.

This function set interrupt handler address of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.
- You can set the CSR_CSR_MTVT to set interrupt vector table entry address.
- If your vector table is placed in readonly section, the vector for IRQn will not be modified. For this case, you need to use the correct irq handler name defined in your vector table as your irq handler function name.
- This function will only work correctly when the vector table is placed in an read-write enabled section.

See also:

- ECLIC_GetVector

  Parameters

  - `IRQn` – **[in]** Interrupt number
  - `vector` – **[in]** Interrupt handler address

`__STATIC_FORCEINLINE rv_csr_t __ECLIC_GetVector (IRQn_Type IRQn)`

Get Interrupt Vector of a specific interrupt.

This function get interrupt handler address of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.
- You can read CSR_CSR_MTVT to get interrupt vector table entry address.

See also:

- ECLIC_SetVector

  Parameters `IRQn` – **[in]** Interrupt number

  Returns Interrupt handler address

`__STATIC_FORCEINLINE void __ECLIC_SetModeIRQ (IRQn_Type IRQn, uint32_t mode)`

Set privilege mode of a specific interrupt.

This function set in which privilege mode the interrupts *IRQn* should be taken.

Remark

- IRQn must not be negative.
- mode must be 1(Supervisor Mode) or 3(Machine Mode), other values are ignored.

- M-mode can R/W this field, but S-mode can only read.And ECLIC with TEE does not reply on CSR mideleg to delegate interrupts.
- Mode of S-mode ECLIC region's clicintattr can be omitted to set, which is mirror to M-mode ECLIC region's. Only the low 6 bits of clicintattr [i] can be written via the S-mode memory region.

Parameters

- `IRQn` – **[in]** Interrupt number
- `mode` – **[in]** Privilege mode

`__STATIC_FORCEINLINE void __ECLIC_SetSth (uint8_t sth)`

Set supervisor-mode Interrupt Level Threshold in supervisor mode.

This function sets supervisor-mode interrupt level threshold.

Remark

- S-mode ECLIC region sintthresh'sth is a mirror to M-mode ECLIC region's mintthresh.sth, and will be updated synchronously, here operate on mintthresh.sth.

See also:

- ECLIC_GetSth

Parameters `sth` – **[in]** Interrupt Level Threshold.

`__STATIC_FORCEINLINE uint8_t __ECLIC_GetSth (void)`

Get supervisor-mode Interrupt Level Threshold in supervisor mode.

This function gets supervisor mode interrupt level threshold.

Remark

- S-mode ECLIC region sintthresh'sth is a mirror to M-mode ECLIC region's mintthresh.sth, and will be updated synchronously, here operate on mintthresh.sth.

See also:

- ECLIC_SetSth

Returns Interrupt Level Threshold.

`__STATIC_FORCEINLINE void __ECLIC_SetTrigIRQ_S (IRQn_Type IRQn, uint32_t trig)`

Set trigger mode and polarity for a specific interrupt in supervisor mode.

This function set trigger mode and polarity of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_GetTrigIRQ_S

  Parameters

  - `IRQn` – **[in]** Interrupt number
  - `trig` – **[in]**
    - 00 level trigger, *ECLIC_LEVEL_TRIGGER* (page 143)
    - 01 positive edge trigger, *ECLIC_POSTIVE_EDGE_TRIGGER* (page 143)
    - 02 level trigger, *ECLIC_LEVEL_TRIGGER* (page 143)
    - 03 negative edge trigger, *ECLIC_NEGTIVE_EDGE_TRIGGER* (page 143)

`__STATIC_FORCEINLINE uint8_t __ECLIC_GetTrigIRQ_S (IRQn_Type IRQn)`

Get trigger mode and polarity for a specific interrupt in supervisor mode.

This function get trigger mode and polarity of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_SetTrigIRQ_S

  Parameters `IRQn` – **[in]** Interrupt number

  Returns

  - 00 level trigger, *ECLIC_LEVEL_TRIGGER* (page 143)
  - 01 positive edge trigger, *ECLIC_POSTIVE_EDGE_TRIGGER* (page 143)
  - 02 level trigger, *ECLIC_LEVEL_TRIGGER* (page 143)
  - 03 negative edge trigger, *ECLIC_NEGTIVE_EDGE_TRIGGER* (page 143)

`__STATIC_FORCEINLINE void __ECLIC_SetShvIRQ_S (IRQn_Type IRQn, uint32_t shv)`

Set interrupt working mode for a specific interrupt in supervisor mode.

This function set selective hardware vector or non-vector working mode of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_GetShvIRQ_S

  Parameters

  - **IRQn** – **[in]** Interrupt number
  - **shv** – **[in]**
    - 0 non-vector mode, *ECLIC_NON_VECTOR_INTERRUPT* (page 143)
    - 1 vector mode, *ECLIC_VECTOR_INTERRUPT* (page 143)

__STATIC_FORCEINLINE uint8_t __ECLIC_GetShvIRQ_S (IRQn_Type IRQn)

Get interrupt working mode for a specific interrupt in supervisor mode.

This function get selective hardware vector or non-vector working mode of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_SMODE_SetShvIRQ

  Parameters **IRQn** – **[in]** Interrupt number

  Returns shv

  - 0 non-vector mode, *ECLIC_NON_VECTOR_INTERRUPT* (page 143)
  - 1 vector mode, *ECLIC_VECTOR_INTERRUPT* (page 143)

__STATIC_FORCEINLINE void __ECLIC_SetCtrlIRQ_S (IRQn_Type IRQn, uint8_t intctrl)

Modify ECLIC Interrupt Input Control Register for a specific interrupt in supervisor mode.

This function modify ECLIC Interrupt Input Control(CLICINTCTL[i]) register of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_GetCtrlIRQ_S

  Parameters

  - `IRQn` – **[in]** Interrupt number
  - `intctrl` – **[in]** Set value for CLICINTCTL[i] register

`__STATIC_FORCEINLINE uint8_t __ECLIC_GetCtrlIRQ_S (IRQn_Type IRQn)`

Get ECLIC Interrupt Input Control Register value for a specific interrupt in supervisor mode.

This function modify ECLIC Interrupt Input Control register of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_SetCtrlIRQ_S

  Parameters `IRQn` – **[in]** Interrupt number

  Returns value of ECLIC Interrupt Input Control register

`__STATIC_FORCEINLINE void __ECLIC_SetLevelIRQ_S (IRQn_Type IRQn, uint8_t lvl_abs)`

Set ECLIC Interrupt level of a specific interrupt in supervisor mode.

This function set interrupt level of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.
- If lvl_abs to be set is larger than the max level allowed, it will be force to be max level.
- When you set level value you need use clciinfo.nlbits to get the width of level. Then we could know the maximum of level. CLICINTCTLBITS is how many total bits are present in the CLICINTCTL register.

See also:

- ECLIC_GetLevelIRQ_S

  Parameters

- `IRQn` – **[in]** Interrupt number
- `lvl_abs` – **[in]** Interrupt level

`__STATIC_FORCEINLINE uint8_t __ECLIC_GetLevelIRQ_S (IRQn_Type IRQn)`

Get ECLIC Interrupt level of a specific interrupt.

This function get interrupt level of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_SetLevelIRQ_S

Parameters `IRQn` – **[in]** Interrupt number

Returns Interrupt level

`__STATIC_FORCEINLINE void __ECLIC_SetPriorityIRQ_S (IRQn_Type IRQn, uint8_t pri)`

Set ECLIC Interrupt priority of a specific interrupt in supervisor mode.

This function get interrupt priority of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.
- If pri to be set is larger than the max priority allowed, it will be force to be max priority.
- Priority width is CLICINTCTLBITS minus clciinfo.nlbits if clciinfo.nlbits is less than CLICINTCTL-BITS. Otherwise priority width is 0.

See also:

- ECLIC_GetPriorityIRQ_S

Parameters

- `IRQn` – **[in]** Interrupt number
- `pri` – **[in]** Interrupt priority

`__STATIC_FORCEINLINE uint8_t __ECLIC_GetPriorityIRQ_S (IRQn_Type IRQn)`

Get ECLIC Interrupt priority of a specific interrupt in supervisor mode.

This function get interrupt priority of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_SetPriorityIRQ_S

Parameters `IRQn` – **[in]** Interrupt number

Returns Interrupt priority

`__STATIC_FORCEINLINE void __ECLIC_EnableIRQ_S (IRQn_Type IRQn)`

Enable a specific interrupt in supervisor mode.

This function enables the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_DisableIRQ

Parameters `IRQn` – **[in]** Interrupt number

`__STATIC_FORCEINLINE uint8_t __ECLIC_GetEnableIRQ_S (IRQn_Type IRQn)`

Get a specific interrupt enable status in supervisor mode.

This function returns the interrupt enable status for the specific interrupt *IRQn* in S MODE.

Remark

- IRQn must not be negative.

See also:

- ECLIC_EnableIRQ_S
- ECLIC_DisableIRQ_S

Parameters `IRQn` – **[in]** Interrupt number

Returns

- 0 Interrupt is not masked
- 1 Interrupt is enabled

`__STATIC_FORCEINLINE void __ECLIC_DisableIRQ_S (IRQn_Type IRQn)`

Disable a specific interrupt in supervisor mode.

This function disables the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.

See also:

- ECLIC_EnableIRQ

Parameters `IRQn` – **[in]** Number of the external interrupt to disable

`__STATIC_FORCEINLINE void __ECLIC_SetVector_S (IRQn_Type IRQn, rv_csr_t vector)`

Set Interrupt Vector of a specific interrupt in supervisor mode.

This function set interrupt handler address of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.
- You can set the CSR_CSR_MTVT to set interrupt vector table entry address.
- If your vector table is placed in readonly section, the vector for IRQn will not be modified. For this case, you need to use the correct irq handler name defined in your vector table as your irq handler function name.
- This function will only work correctly when the vector table is placed in an read-write enabled section.

See also:

- ECLIC_GetVector_S

Parameters

- `IRQn` – **[in]** Interrupt number
- `vector` – **[in]** Interrupt handler address

`__STATIC_FORCEINLINE rv_csr_t __ECLIC_GetVector_S (IRQn_Type IRQn)`

Get Interrupt Vector of a specific interrupt in supervisor mode.

This function get interrupt handler address of the specific interrupt *IRQn*.

Remark

- IRQn must not be negative.
- You can read CSR_CSR_MTVT to get interrupt vector table entry address.

See also:

- ECLIC_SMODE_SetVector

  Parameters `IRQn` – **[in]** Interrupt number

  Returns Interrupt handler address

`__STATIC_FORCEINLINE void __set_exc_entry (rv_csr_t addr)`

Set Exception entry address.

This function set exception handler address to 'CSR_MTVEC'.

Remark

- This function use to set exception handler address to 'CSR_MTVEC'. Address need to be aligned to 64 bytes.

See also:

- __get_exc_entry

  Parameters `addr` – **[in]** Exception handler address

`__STATIC_FORCEINLINE rv_csr_t __get_exc_entry (void)`

Get Exception entry address.

This function get exception handler address from 'CSR_MTVEC'.

Remark

- This function use to get exception handler address from 'CSR_MTVEC'. Address need to be aligned to 64 bytes.

See also:

- __set_exc_entry

  Returns Exception handler address

__STATIC_FORCEINLINE void __set_nonvec_entry (rv_csr_t addr)

Set Non-vector interrupt entry address.

This function set Non-vector interrupt address.

Remark

- This function use to set non-vector interrupt entry address to 'CSR_MTVT2' if
- CSR_MTVT2 bit0 is 1. If 'CSR_MTVT2' bit0 is 0 then set address to 'CSR_MTVEC'

See also:

- __get_nonvec_entry

Parameters `addr` – **[in]** Non-vector interrupt entry address

__STATIC_FORCEINLINE rv_csr_t __get_nonvec_entry (void)

Get Non-vector interrupt entry address.

This function get Non-vector interrupt address.

Remark

- This function use to get non-vector interrupt entry address from 'CSR_MTVT2' if
- CSR_MTVT2 bit0 is 1. If 'CSR_MTVT2' bit0 is 0 then get address from 'CSR_MTVEC'.

See also:

- __set_nonvec_entry

Returns Non-vector interrupt handler address

__STATIC_FORCEINLINE rv_csr_t __get_nmi_entry (void)

Get NMI interrupt entry from 'CSR_MNVEC'.

This function get NMI interrupt address from 'CSR_MNVEC'.

Remark

- This function use to get NMI interrupt handler address from 'CSR_MNVEC'. If CSR_MMISC_CTL[9] = 1 'CSR_MNVEC'
- will be equal as mtvec. If CSR_MMISC_CTL[9] = 0 'CSR_MNVEC' will be equal as reset vector.
- NMI entry is defined via *CSR_MMISC_CTL* (page 106), writing to *CSR_MNVEC* (page 106) will be ignored.

Returns NMI interrupt handler address

2.5.11 FPU Functions

group **NMSIS_Core_FPU_Functions**

Functions that related to the RISC-V FPU (F and D extension).

Nuclei provided floating point unit by RISC-V F and D extension.

- `F extension` adds single-precision floating-point computational instructions compliant with the IEEE 754-2008 arithmetic standard, __RISCV_FLEN = 32. The F extension adds 32 floating-point registers, f0-f31, each 32 bits wide, and a floating-point control and status register fcsr, which contains the operating mode and exception status of the floating-point unit.
- `D extension` adds double-precision floating-point computational instructions compliant with the IEEE 754-2008 arithmetic standard. The D extension widens the 32 floating-point registers, f0-f31, to 64 bits, __RISCV_FLEN = 64

Defines

__RISCV_FLEN 64

__get_FCSR() *__RV_CSR_READ* (page 80)(*CSR_FCSR* (page 84))

Get FCSR CSR Register.

__set_FCSR(val) *__RV_CSR_WRITE* (page 81)(*CSR_FCSR* (page 84), (val))

Set FCSR CSR Register with val.

__get_FRM() *__RV_CSR_READ* (page 80)(*CSR_FRM* (page 84))

Get FRM CSR Register.

__set_FRM(val) *__RV_CSR_WRITE* (page 81)(*CSR_FRM* (page 84), (val))

Set FRM CSR Register with val.

__get_FFLAGS() *__RV_CSR_READ* (page 80)(*CSR_FFLAGS* (page 84))

Get FFLAGS CSR Register.

__set_FFLAGS(val) *__RV_CSR_WRITE* (page 81)(*CSR_FFLAGS* (page 84), (val))

Set FFLAGS CSR Register with val.

__enable_FPU()

Enable FPU Unit, and set state to initial.

__disable_FPU() *__RV_CSR_CLEAR* (page 81)(*CSR_MSTATUS* (page 90), *MSTATUS_FS* (page 110))

Disable FPU Unit.

- We can save power by disable FPU Unit.
- When FPU Unit is disabled, any access to FPU related CSR registers and FPU instructions will cause illegal Instuction Exception.

__RV_FLW(freg, addr, ofs)

Load a single-precision value from memory into float point register freg using flw instruction.

The FLW instruction loads a single-precision floating point value from memory address (addr + ofs) into floating point register freg(f0-f31)

Remark

- FLW and FSW operations need to make sure the address is 4 bytes aligned, otherwise it will cause exception code 4(Load address misaligned) or 6 (Store/AMO address misaligned)
- FLW and FSW do not modify the bits being transferred; in particular, the payloads of non-canonical NaNs are preserved

---

Parameters

- **freg** – **[in]** The floating point register, eg. *FREG(0)* (page 122), f0
- **addr** – **[in]** The memory base address, 4 byte aligned required
- **ofs** – **[in]** a 12-bit immediate signed byte offset value, should be an const value

__RV_FSW(freg, addr, ofs)

Store a single-precision value from float point freg into memory using fsw instruction.

The FSW instruction stores a single-precision value from floating point register to memory

---

Remark

- FLW and FSW operations need to make sure the address is 4 bytes aligned, otherwise it will cause exception code 4(Load address misaligned) or 6 (Store/AMO address misaligned)
- FLW and FSW do not modify the bits being transferred; in particular, the payloads of non-canonical NaNs are preserved

---

Parameters

- **freg** – **[in]** The floating point register(f0-f31), eg. *FREG(0)* (page 122), f0
- **addr** – **[in]** The memory base address, 4 byte aligned required
- **ofs** – **[in]** a 12-bit immediate signed byte offset value, should be an const value

__RV_FLD(freg, addr, ofs)

Load a double-precision value from memory into float point register freg using fld instruction.

The FLD instruction loads a double-precision floating point value from memory address (addr + ofs) into floating point register freg(f0-f31)

Remark

- FLD and FSD operations need to make sure the address is 8 bytes aligned, otherwise it will cause exception code 4(Load address misaligned) or 6 (Store/AMO address misaligned)
- FLD and FSD do not modify the bits being transferred; in particular, the payloads of non-canonical NaNs are preserved.

Attention

- Function only available for double precision floating point unit, FLEN = 64

Parameters

- **freg** – **[in]** The floating point register, eg. *FREG(0)* (page 122), f0
- **addr** – **[in]** The memory base address, 8 byte aligned required
- **ofs** – **[in]** a 12-bit immediate signed byte offset value, should be an const value

__RV_FSD(freg, addr, ofs)

Store a double-precision value from float point freg into memory using fsd instruction.

The FSD instruction stores double-precision value from floating point register to memory

Remark

- FLD and FSD operations need to make sure the address is 8 bytes aligned, otherwise it will cause exception code 4(Load address misaligned) or 6 (Store/AMO address misaligned)
- FLD and FSD do not modify the bits being transferred; in particular, the payloads of non-canonical NaNs are preserved.

Attention

- Function only available for double precision floating point unit, FLEN = 64

Parameters

- **freg** – **[in]** The floating point register(f0-f31), eg. *FREG(0)* (page 122), f0
- **addr** – **[in]** The memory base address, 8 byte aligned required
- **ofs** – **[in]** a 12-bit immediate signed byte offset value, should be an const value

__RV_FLOAD *__RV_FLD* (page 590)

Load a float point value from memory into float point register freg using flw/fld instruction.

- For Single-Precison Floating-Point Mode(__FPU_PRESENT == 1, __RISCV_FLEN == 32): It will call *__RV_FLW* (page 590) to load a single-precision floating point value from memory to floating point register
- For Double-Precison Floating-Point Mode(__FPU_PRESENT == 2, __RISCV_FLEN == 64): It will call *__RV_FLD* (page 590) to load a double-precision floating point value from memory to floating point register

Attention Function behaviour is different for __FPU_PRESENT = 1 or 2, please see the real function this macro represent

__RV_FSTORE *__RV_FSD* (page 591)

Store a float value from float point freg into memory using fsw/fsd instruction.

- For Single-Precison Floating-Point Mode(__FPU_PRESENT == 1, __RISCV_FLEN == 32): It will call *__RV_FSW* (page 590) to store floating point register into memory
- For Double-Precison Floating-Point Mode(__FPU_PRESENT == 2, __RISCV_FLEN == 64): It will call *__RV_FSD* (page 591) to store floating point register into memory

Attention Function behaviour is different for __FPU_PRESENT = 1 or 2, please see the real function this macro represent

SAVE_FPU_CONTEXT()

Save FPU context into variables for interrupt nesting.

This macro is used to declare variables which are used for saving FPU context, and it will store the nessary fpu registers into these variables, it need to be used in a interrupt when in this interrupt fpu registers are used.

Remark

- It need to be used together with *RESTORE_FPU_CONTEXT* (page 592)
- Don't use variable names __fpu_context in your ISR code
- If you isr code will use fpu registers, and this interrupt is nested. Then you can do it like this:

```
void eclic_mtip_handler(void)
{
    // !!!Interrupt is enabled here!!!
    // !!!Higher priority interrupt could nest it!!!

    // Necessary only when you need to use fpu registers
    // in this isr handler functions
    SAVE_FPU_CONTEXT();

    // put you own interrupt handling code here

    // pair of SAVE_FPU_CONTEXT()
    RESTORE_FPU_CONTEXT();
}
```

RESTORE_FPU_CONTEXT()

Restore necessary fpu registers from variables for interrupt nesting.

This macro is used restore necessary fpu registers from pre-defined variables in *SAVE_FPU_CONTEXT* (page 592) macro.

Remark

- It need to be used together with *SAVE_FPU_CONTEXT* (page 592)

Typedefs

typedef uint64_t **rv_fpu_t**

Type of FPU register, depends on the FLEN defined in RISC-V.

2.5.12 PMP Functions

Click Nuclei PMP Unit[21] to learn about Core PMP Unit in Nuclei ISA Spec.

__STATIC_INLINE rv_csr_t __get_PMPCFGx (uint32_t csr_idx)

__STATIC_INLINE void __set_PMPCFGx (uint32_t csr_idx, rv_csr_t pmpcfg)

__STATIC_INLINE uint8_t __get_PMPxCFG (uint32_t entry_idx)

__STATIC_INLINE void __set_PMPxCFG (uint32_t entry_idx, uint8_t pmpxcfg)

__STATIC_INLINE rv_csr_t __get_PMPADDRx (uint32_t csr_idx)

__STATIC_INLINE void __set_PMPADDRx (uint32_t csr_idx, rv_csr_t pmpaddr)

__STATIC_INLINE void __set_PMPENTRYx (uint32_t entry_idx, const pmp_config *pmp_cfg)

__STATIC_INLINE int __get_PMPENTRYx (unsigned int entry_idx, pmp_config *pmp_cfg)

struct **PMP_CONFIG**

group **NMSIS_Core_PMP_Functions**

Functions that related to the RISCV Phyiscal Memory Protection.

Optional physical memory protection (PMP) unit provides per-hart machine-mode control registers to allow physical memory access privileges (read, write, execute) to be specified for each physical memory region.

The PMP can supports region access control settings as small as four bytes.

[21] https://doc.nucleisys.com/nuclei_spec/isa/pmp.html

Functions

`__STATIC_INLINE rv_csr_t __get_PMPCFGx (uint32_t csr_idx)`

Get PMPCFGx Register by csr index.

Return the content of the PMPCFGx Register.

Remark

- For RV64, only csr_idx = 0 and csr_idx = 2 is allowed. pmpcfg0 and pmpcfg2 hold the configurations for the 16 PMP entries, pmpcfg1 and pmpcfg3 are illegal
- For RV32, pmpcfg0–pmpcfg3, hold the configurations pmp0cfg–pmp15cfg for the 16 PMP entries

Parameters `csr_idx` – **[in]** PMPCFG CSR index(0-3)

Returns PMPCFGx Register value

`__STATIC_INLINE void __set_PMPCFGx (uint32_t csr_idx, rv_csr_t pmpcfg)`

Set PMPCFGx by csr index.

Write the given value to the PMPCFGx Register.

Remark

- For RV64, only csr_idx = 0 and csr_idx = 2 is allowed. pmpcfg0 and pmpcfg2 hold the configurations for the 16 PMP entries, pmpcfg1 and pmpcfg3 are illegal
- For RV32, pmpcfg0–pmpcfg3, hold the configurations pmp0cfg–pmp15cfg for the 16 PMP entries

Parameters

- `csr_idx` – **[in]** PMPCFG CSR index(0-3)
- `pmpcfg` – **[in]** PMPCFGx Register value to set

`__STATIC_INLINE uint8_t __get_PMPxCFG (uint32_t entry_idx)`

Get 8bit PMPxCFG Register by PMP entry index.

Return the content of the PMPxCFG Register.

Parameters `entry_idx` – **[in]** PMP region index(0-15)

Returns PMPxCFG Register value

`__STATIC_INLINE void __set_PMPxCFG (uint32_t entry_idx, uint8_t pmpxcfg)`

Set 8bit PMPxCFG by pmp entry index.

Set the given pmpxcfg value to the PMPxCFG Register.

Remark

- For RV32, 4 pmpxcfgs are densely packed into one CSR in order For RV64, 8 pmpxcfgs are densely packed into one CSR in order

Parameters

- `entry_idx` – **[in]** PMPx region index(0-15)
- `pmpxcfg` – **[in]** PMPxCFG register value to set

`__STATIC_INLINE rv_csr_t __get_PMPADDRx (uint32_t csr_idx)`

Get PMPADDRx Register by CSR index.

Return the content of the PMPADDRx Register.

Parameters `csr_idx` – **[in]** PMP region CSR index(0-15)

Returns PMPADDRx Register value

`__STATIC_INLINE void __set_PMPADDRx (uint32_t csr_idx, rv_csr_t pmpaddr)`

Set PMPADDRx by CSR index.

Write the given value to the PMPADDRx Register.

Parameters

- `csr_idx` – **[in]** PMP region CSR index(0-15)
- `pmpaddr` – **[in]** PMPADDRx Register value to set

`__STATIC_INLINE void __set_PMPENTRYx (uint32_t entry_idx, const pmp_config *pmp_cfg)`

Set PMP entry by entry idx.

Write the given value to the PMPxCFG Register and PMPADDRx.

Remark

- If the size of memory region is 2^12(4KB) range, pmp_cfg->order makes 12, and the like.
- Suppose the size of memory region is 2^X bytes range, if X >=3, the NA4 mode is not selectable, NAPOT is selected.
- TOR of A field in PMP configuration register is not considered here.

Parameters

- `entry_idx` – **[in]** PMP entry index(0-15)
- `pmp_cfg` – **[in]** structure of L, X, W, R field of PMP configuration register, memory region base address and size of memory region as power of 2

`__STATIC_INLINE int __get_PMPENTRYx (unsigned int entry_idx, pmp_config *pmp_cfg)`

Get PMP entry by entry idx.

Write the given value to the PMPxCFG Register and PMPADDRx.

Remark

- If the size of memory region is 2^12(4KB) range, pmp_cfg->order makes 12, and the like.
- TOR of A field in PMP configuration register is not considered here.

Parameters

- **entry_idx** – **[in]** PMP entry index(0-15)
- **pmp_cfg** – **[out]** structure of L, X, W, R, A field of PMP configuration register, memory region base address and size of memory region as power of 2

Returns -1 failure, else 0 success

struct **PMP_CONFIG**

#include <core_feature_pmp.h>

2.5.13 SPMP Functions

Click TEE Introduction[22] to learn about Core SPMP Unit in Nuclei ISA Spec.

__STATIC_INLINE rv_csr_t __get_sPMPCFGx (uint32_t csr_idx)

__STATIC_INLINE void __set_sPMPCFGx (uint32_t csr_idx, rv_csr_t spmpcfg)

__STATIC_INLINE uint8_t __get_sPMPxCFG (uint32_t entry_idx)

__STATIC_INLINE void __set_sPMPxCFG (uint32_t entry_idx, uint8_t spmpxcfg)

__STATIC_INLINE rv_csr_t __get_sPMPADDRx (uint32_t csr_idx)

__STATIC_INLINE void __set_sPMPADDRx (uint32_t csr_idx, rv_csr_t spmpaddr)

__STATIC_INLINE void __set_sPMPENTRYx (uint32_t entry_idx, const spmp_config *spmp_cfg)

__STATIC_INLINE int __get_sPMPENTRYx (unsigned int entry_idx, spmp_config *spmp_cfg)

struct **SPMP_CONFIG**

[22] https://doc.nucleisys.com/nuclei_spec/isa/tee.html

group `NMSIS_Core_SPMP_Functions`

Functions that related to the RISCV supervisor-mode Phyiscal Memory Protection.

Optional superviosr physical memory protection (sPMP) unit provides per-hart supervisor-mode control registers to allow physical memory access privileges (read, write, execute) to be specified for each physical memory region. The sPMP values are checked after the physical address to be accessed pass PMP checks described in the RISC-V privileged spec.

Like PMP, the sPMP can supports region access control settings as small as four bytes.

Functions

`__STATIC_INLINE rv_csr_t __get_sPMPCFGx (uint32_t csr_idx)`

Get sPMPCFGx Register by csr index.

Return the content of the sPMPCFGx Register.

Remark

- For RV64, only csr_idx = 0 and csr_idx = 2 is allowed. spmpcfg0 and spmpcfg2 hold the configurations for the 16 sPMP entries, spmpcfg1 and spmpcfg3 are illegal
- For RV32, spmpcfg0–spmpcfg3, hold the configurations spmp0cfg–spmp15cfg for the 16 sPMP entries

Parameters `csr_idx` – **[in]** sPMPCFG CSR index(0-3)

Returns sPMPCFGx Register value

`__STATIC_INLINE void __set_sPMPCFGx (uint32_t csr_idx, rv_csr_t spmpcfg)`

Set sPMPCFGx by csr index.

Write the given value to the sPMPCFGx Register.

Remark

- For RV64, only csr_idx = 0 and csr_idx = 2 is allowed. spmpcfg0 and spmpcfg2 hold the configurations for the 16 sPMP entries, spmpcfg1 and spmpcfg3 are illegal
- For RV32, spmpcfg0–spmpcfg3, hold the configurations spmp0cfg–spmp15cfg for the 16 sPMP entries

Parameters

- `csr_idx` – **[in]** sPMPCFG CSR index(0-3)
- `spmpcfg` – **[in]** sPMPCFGx Register value to set

`__STATIC_INLINE uint8_t __get_sPMPxCFG (uint32_t entry_idx)`

Get 8bit sPMPxCFG Register by sPMP entry index.

Return the content of the sPMPxCFG Register.

Parameters `entry_idx` – **[in]** sPMP region index(0-15)

Returns sPMPxCFG Register value

`__STATIC_INLINE void __set_sPMPxCFG (uint32_t entry_idx, uint8_t spmpxcfg)`

Set 8bit sPMPxCFG by spmp entry index.

Set the given spmpxcfg value to the sPMPxCFG Register.

Remark

- For RV32, 4 spmpxcfgs are densely packed into one CSR in order For RV64, 8 spmpxcfgs are densely packed into one CSR in order

Parameters

- `entry_idx` – **[in]** sPMPx region index(0-15)
- `spmpxcfg` – **[in]** sPMPxCFG register value to set

`__STATIC_INLINE rv_csr_t __get_sPMPADDRx (uint32_t csr_idx)`

Get sPMPADDRx Register by CSR index.

Return the content of the sPMPADDRx Register.

Parameters `csr_idx` – **[in]** sPMP region CSR index(0-15)

Returns sPMPADDRx Register value

`__STATIC_INLINE void __set_sPMPADDRx (uint32_t csr_idx, rv_csr_t spmpaddr)`

Set sPMPADDRx by CSR index.

Write the given value to the sPMPADDRx Register.

Parameters

- `csr_idx` – **[in]** sPMP region CSR index(0-15)
- `spmpaddr` – **[in]** sPMPADDRx Register value to set

`__STATIC_INLINE void __set_sPMPENTRYx (uint32_t entry_idx, const spmp_config *spmp_cfg)`

Set sPMP entry by entry idx.

Write the given value to the sPMPxCFG Register and sPMPADDRx.

Remark

- If the size of memory region is 2^12(4KB) range, spmp_cfg->order makes 12, and the like.

- Suppose the size of memory region is 2^X bytes range, if X >=3, the NA4 mode is not selectable, NAPOT is selected.
- TOR of A field in sPMP configuration register is not considered here.

Parameters

- **entry_idx** – **[in]** sPMP entry index(0-15)
- **spmp_cfg** – **[in]** structure of L,U,X,W,R field of sPMP configuration register, memory region base address and size of memory region as power of 2

`__STATIC_INLINE int __get_sPMPENTRYx (unsigned int entry_idx, spmp_config *spmp_cfg)`

Get sPMP entry by entry idx.

Write the given value to the PMPxCFG Register and PMPADDRx.

Remark

- If the size of memory region is 2^12(4KB) range, spmp_cfg->order makes 12, and the like.
- TOR of A field in PMP configuration register is not considered here.

Parameters

- **entry_idx** – **[in]** sPMP entry index(0-15)
- **spmp_cfg** – **[out]** structure of L, U, X, W, R, A field of sPMP configuration register, memory region base address and size of memory region as power of 2

Returns -1 failure, else 0 success

struct **SPMP_CONFIG**

#include <core_feature_spmp.h>

2.5.14 Cache Functions

General

enum **CCM_OP_FINFO**

Values:

enumerator **CCM_OP_SUCCESS**

enumerator **CCM_OP_EXCEED_ERR**

enumerator **CCM_OP_PERM_CHECK_ERR**

enumerator `CCM_OP_REFILL_BUS_ERR`

enumerator `CCM_OP_ECC_ERR`

enum `CCM_CMD`

Values:

enumerator `CCM_DC_INVAL`

enumerator `CCM_DC_WB`

enumerator `CCM_DC_WBINVAL`

enumerator `CCM_DC_LOCK`

enumerator `CCM_DC_UNLOCK`

enumerator `CCM_DC_WBINVAL_ALL`

enumerator `CCM_DC_WB_ALL`

enumerator `CCM_DC_INVAL_ALL`

enumerator `CCM_IC_INVAL`

enumerator `CCM_IC_LOCK`

enumerator `CCM_IC_UNLOCK`

enumerator `CCM_IC_INVAL_ALL`

`__STATIC_FORCEINLINE void EnableSUCCM (void)`

`__STATIC_FORCEINLINE void DisableSUCCM (void)`

`__STATIC_FORCEINLINE void FlushPipeCCM (void)`

`CCM_SUEN_SUEN_Msk` (0xFFFFFFFFFFFFFFFFUL)

struct `CacheInfo`

group `NMSIS_Core_Cache`

Functions that configure Instruction and Data Cache.

Nuclei provide Cache Control and Maintainence(CCM) for software to control and maintain the internal L1 I/D Cache of the RISC-V Core, software can manage the cache flexibly to meet the actual application scenarios.

The CCM operations have 3 types: by single address, by all and flush pipeline. The CCM operations are done via CSR registers, M/S/U mode has its own CSR registers to do CCM operations. By default, CCM operations are not allowed in S/U mode, you can execute EnableSUCCM in M-Mode to enable it.

- API names started with M<operations>, such as MInvalICacheLine must be called in M-Mode only.
- API names started with S<operations>, such as SInvalICacheLine should be called in S-Mode.
- API names started with U<operations>, such as UInvalICacheLine should be called in U-Mode.

Defines

`CCM_SUEN_SUEN_Msk` (0xFFFFFFFFFFFFFFFFUL)

CSR CCM_SUEN: SUEN Mask.

Enums

enum `CCM_OP_FINFO`

Cache CCM Operation Fail Info.

Values:

enumerator `CCM_OP_SUCCESS`

Lock Succeed.

enumerator `CCM_OP_EXCEED_ERR`

Exceed the the number of lockable ways(N-Way I/D-Cache, lockable is N-1)

enumerator `CCM_OP_PERM_CHECK_ERR`

PMP/sPMP/Page-Table X(I-Cache)/R(D-Cache) permission check failed, or belong to Device/Non-Cacheable address range.

enumerator `CCM_OP_REFILL_BUS_ERR`

Refill has Bus Error.

enumerator `CCM_OP_ECC_ERR`

Deprecated, ECC Error, this error code is removed in later Nuclei CCM RTL design, please don't use it.

enum `CCM_CMD`

Cache CCM Command Types.

Values:

enumerator **CCM_DC_INVAL**

Unlock and invalidate D-Cache line specified by CSR CCM_XBEGINADDR.

enumerator **CCM_DC_WB**

Flush the specific D-Cache line specified by CSR CCM_XBEGINADDR.

enumerator **CCM_DC_WBINVAL**

Unlock, flush and invalidate the specific D-Cache line specified by CSR CCM_XBEGINADDR.

enumerator **CCM_DC_LOCK**

Lock the specific D-Cache line specified by CSR CCM_XBEGINADDR.

enumerator **CCM_DC_UNLOCK**

Unlock the specific D-Cache line specified by CSR CCM_XBEGINADDR.

enumerator **CCM_DC_WBINVAL_ALL**

Unlock and flush and invalidate all the valid and dirty D-Cache lines.

enumerator **CCM_DC_WB_ALL**

Flush all the valid and dirty D-Cache lines.

enumerator **CCM_DC_INVAL_ALL**

Unlock and invalidate all the D-Cache lines.

enumerator **CCM_IC_INVAL**

Unlock and invalidate I-Cache line specified by CSR CCM_XBEGINADDR.

enumerator **CCM_IC_LOCK**

Lock the specific I-Cache line specified by CSR CCM_XBEGINADDR.

enumerator **CCM_IC_UNLOCK**

Unlock the specific I-Cache line specified by CSR CCM_XBEGINADDR.

enumerator **CCM_IC_INVAL_ALL**

Unlock and invalidate all the I-Cache lines.

Functions

__STATIC_FORCEINLINE void EnableSUCCM (void)

Enable CCM operation in Supervisor/User Mode.

This function enable CCM operation in Supervisor/User Mode. If enabled, CCM operations in supervisor/user mode will be allowed.

Remark

- This function can be called in M-Mode only.

See also:

- DisableSUCCM

__STATIC_FORCEINLINE void DisableSUCCM (void)

Disable CCM operation in Supervisor/User Mode.

This function disable CCM operation in Supervisor/User Mode. If not enabled, CCM operations in supervisor/user mode will trigger a *illegal intruction* exception.

Remark

- This function can be called in M-Mode only.

See also:

- EnableSUCCM

__STATIC_FORCEINLINE void FlushPipeCCM (void)

Flush pipeline after CCM operation.

This function is used to flush pipeline after CCM operations on Cache, it will ensure latest instructions or data can be seen by pipeline.

Remark

- This function can be called in M/S/U-Mode only.

struct **CacheInfo**

#include <core_feature_cache.h> Cache Information Type.

I-Cache Functions

__STATIC_FORCEINLINE int32_t ICachePresent (void)

__STATIC_FORCEINLINE void EnableICache (void)

__STATIC_FORCEINLINE void DisableICache (void)

__STATIC_FORCEINLINE void EnableICacheECC (void)

```
__STATIC_FORCEINLINE void DisableICacheECC (void)

__STATIC_FORCEINLINE int32_t GetICacheInfo (CacheInfo_Type *info)

__STATIC_FORCEINLINE void MInvalICacheLine (unsigned long addr)

__STATIC_FORCEINLINE void MInvalICacheLines (unsigned long addr, unsigned long cnt)

__STATIC_FORCEINLINE void SInvalICacheLine (unsigned long addr)

__STATIC_FORCEINLINE void SInvalICacheLines (unsigned long addr, unsigned long cnt)

__STATIC_FORCEINLINE void UInvalICacheLine (unsigned long addr)

__STATIC_FORCEINLINE void UInvalICacheLines (unsigned long addr, unsigned long cnt)

__STATIC_FORCEINLINE unsigned long MLockICacheLine (unsigned long addr)

__STATIC_FORCEINLINE unsigned long MLockICacheLines (unsigned long addr,
unsigned long cnt)

__STATIC_FORCEINLINE unsigned long SLockICacheLine (unsigned long addr)

__STATIC_FORCEINLINE unsigned long SLockICacheLines (unsigned long addr,
unsigned long cnt)

__STATIC_FORCEINLINE unsigned long ULockICacheLine (unsigned long addr)

__STATIC_FORCEINLINE unsigned long ULockICacheLines (unsigned long addr,
unsigned long cnt)

__STATIC_FORCEINLINE void MUnlockICacheLine (unsigned long addr)

__STATIC_FORCEINLINE void MUnlockICacheLines (unsigned long addr, unsigned long cnt)

__STATIC_FORCEINLINE void SUnlockICacheLine (unsigned long addr)

__STATIC_FORCEINLINE void SUnlockICacheLines (unsigned long addr, unsigned long cnt)

__STATIC_FORCEINLINE void UUnlockICacheLine (unsigned long addr)

__STATIC_FORCEINLINE void UUnlockICacheLines (unsigned long addr, unsigned long cnt)
```

`__STATIC_FORCEINLINE void MInvalICache (void)`

`__STATIC_FORCEINLINE void SInvalICache (void)`

`__STATIC_FORCEINLINE void UInvalICache (void)`

group `NMSIS_Core_ICache`

Functions that configure Instruction Cache.

Functions

`__STATIC_FORCEINLINE int32_t ICachePresent (void)`

Check ICache Unit Present or Not.

This function check icache unit present or not via mcfg_info csr

Remark

- This function might not work for some old nuclei processors
- Please make sure the version of your nuclei processor contain ICACHE bit in mcfg_info

Returns 1 if present otherwise 0

`__STATIC_FORCEINLINE void EnableICache (void)`

Enable ICache.

This function enable I-Cache

Remark

- This function can be called in M-Mode only.
- This *CSR_MCACHE_CTL* (page 106) register control I Cache enable.

See also:

- DisableICache

`__STATIC_FORCEINLINE void DisableICache (void)`

Disable ICache.

This function Disable I-Cache

Remark

- This function can be called in M-Mode only.
- This *CSR_MCACHE_CTL* (page 106) register control I Cache enable.

See also:

- EnableICache

`__STATIC_FORCEINLINE void EnableICacheECC (void)`

Enable ICache ECC.

This function enable I-Cache ECC

Remark

- This function can be called in M-Mode only.
- This *CSR_MCACHE_CTL* (page 106) register control I Cache ECC enable.

See also:

- DisableICacheECC

`__STATIC_FORCEINLINE void DisableICacheECC (void)`

Disable ICache ECC.

This function disable I-Cache ECC

Remark

- This function can be called in M-Mode only.
- This *CSR_MCACHE_CTL* (page 106) register control I Cache ECC enable.

See also:

- EnableICacheECC

`__STATIC_FORCEINLINE int32_t GetICacheInfo (CacheInfo_Type *info)`

Get I-Cache Information.

This function get I-Cache Information

Remark

- This function can be called in M-Mode only.
- You can use this function in combination with cache lines operations

See also:

- GetDCacheInfo

`__STATIC_FORCEINLINE void MInvalICacheLine (unsigned long addr)`

Invalidate one I-Cache line specified by address in M-Mode.

This function unlock and invalidate one I-Cache line specified by the address. Command CCM_IC_INVAL is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters `addr` – **[in]** start address to be invalidated

`__STATIC_FORCEINLINE void MInvalICacheLines (unsigned long addr, unsigned long cnt)`

Invalidate several I-Cache lines specified by address in M-Mode.

This function unlock and invalidate several I-Cache lines specified by the address and line count. Command CCM_IC_INVAL is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters

- `addr` – **[in]** start address to be invalidated
- `cnt` – **[in]** count of cache lines to be invalidated

`__STATIC_FORCEINLINE void SInvalICacheLine (unsigned long addr)`

Invalidate one I-Cache line specified by address in S-Mode.

This function unlock and invalidate one I-Cache line specified by the address. Command CCM_IC_INVAL is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters `addr` – **[in]** start address to be invalidated

`__STATIC_FORCEINLINE void SInvalICacheLines (unsigned long addr, unsigned long cnt)`

Invalidate several I-Cache lines specified by address in S-Mode.

This function unlock and invalidate several I-Cache lines specified by the address and line count. Command CCM_IC_INVAL is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters

- **addr** – **[in]** start address to be invalidated
- **cnt** – **[in]** count of cache lines to be invalidated

`__STATIC_FORCEINLINE void UInvalICacheLine (unsigned long addr)`

Invalidate one I-Cache line specified by address in U-Mode.

This function unlock and invalidate one I-Cache line specified by the address. Command CCM_IC_INVAL is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters **addr** – **[in]** start address to be invalidated

`__STATIC_FORCEINLINE void UInvalICacheLines (unsigned long addr, unsigned long cnt)`

Invalidate several I-Cache lines specified by address in U-Mode.

This function unlock and invalidate several I-Cache lines specified by the address and line count. Command CCM_IC_INVAL is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters

- **addr** – **[in]** start address to be invalidated
- **cnt** – **[in]** count of cache lines to be invalidated

`__STATIC_FORCEINLINE unsigned long MLockICacheLine (unsigned long addr)`

Lock one I-Cache line specified by address in M-Mode.

This function lock one I-Cache line specified by the address. Command CCM_IC_LOCK is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters `addr` – **[in]** start address to be locked

Returns result of CCM lock operation, see enum CCM_OP_FINFO

`__STATIC_FORCEINLINE unsigned long MLockICacheLines (unsigned long addr, unsigned long cnt)`

Lock several I-Cache lines specified by address in M-Mode.

This function lock several I-Cache lines specified by the address and line count. Command CCM_IC_LOCK is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters

- `addr` – **[in]** start address to be locked
- `cnt` – **[in]** count of cache lines to be locked

Returns result of CCM lock operation, see enum CCM_OP_FINFO

`__STATIC_FORCEINLINE unsigned long SLockICacheLine (unsigned long addr)`

Lock one I-Cache line specified by address in S-Mode.

This function lock one I-Cache line specified by the address. Command CCM_IC_LOCK is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters `addr` – **[in]** start address to be locked

Returns result of CCM lock operation, see enum CCM_OP_FINFO

`__STATIC_FORCEINLINE unsigned long SLockICacheLines (unsigned long addr, unsigned long cnt)`

Lock several I-Cache lines specified by address in S-Mode.

This function lock several I-Cache lines specified by the address and line count. Command CCM_IC_LOCK is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters

- `addr` – **[in]** start address to be locked

- **cnt** – **[in]** count of cache lines to be locked

Returns result of CCM lock operation, see enum CCM_OP_FINFO

__STATIC_FORCEINLINE unsigned long ULockICacheLine (unsigned long addr)

Lock one I-Cache line specified by address in U-Mode.

This function lock one I-Cache line specified by the address. Command CCM_IC_LOCK is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters **addr** – **[in]** start address to be locked

Returns result of CCM lock operation, see enum CCM_OP_FINFO

__STATIC_FORCEINLINE unsigned long ULockICacheLines (unsigned long addr, unsigned long cnt)

Lock several I-Cache lines specified by address in U-Mode.

This function lock several I-Cache lines specified by the address and line count. Command CCM_IC_LOCK is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters

- **addr** – **[in]** start address to be locked
- **cnt** – **[in]** count of cache lines to be locked

Returns result of CCM lock operation, see enum CCM_OP_FINFO

__STATIC_FORCEINLINE void MUnlockICacheLine (unsigned long addr)

Unlock one I-Cache line specified by address in M-Mode.

This function unlock one I-Cache line specified by the address. Command CCM_IC_UNLOCK is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters **addr** – **[in]** start address to be unlocked

__STATIC_FORCEINLINE void MUnlockICacheLines (unsigned long addr, unsigned long cnt)

Unlock several I-Cache lines specified by address in M-Mode.

This function unlock several I-Cache lines specified by the address and line count. Command CCM_IC_UNLOCK is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters

- `addr` – **[in]** start address to be unlocked
- `cnt` – **[in]** count of cache lines to be unlocked

`__STATIC_FORCEINLINE void SUnlockICacheLine (unsigned long addr)`

Unlock one I-Cache line specified by address in S-Mode.

This function unlock one I-Cache line specified by the address. Command CCM_IC_UNLOCK is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters `addr` – **[in]** start address to be unlocked

`__STATIC_FORCEINLINE void SUnlockICacheLines (unsigned long addr, unsigned long cnt)`

Unlock several I-Cache lines specified by address in S-Mode.

This function unlock several I-Cache lines specified by the address and line count. Command CCM_IC_UNLOCK is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters

- `addr` – **[in]** start address to be unlocked
- `cnt` – **[in]** count of cache lines to be unlocked

`__STATIC_FORCEINLINE void UUnlockICacheLine (unsigned long addr)`

Unlock one I-Cache line specified by address in U-Mode.

This function unlock one I-Cache line specified by the address. Command CCM_IC_UNLOCK is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters `addr` – **[in]** start address to be unlocked

__STATIC_FORCEINLINE void UUnlockICacheLines (unsigned long addr, unsigned long cnt)

Unlock several I-Cache lines specified by address in U-Mode.

This function unlock several I-Cache lines specified by the address and line count. Command CCM_IC_UNLOCK is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters

- **addr** – **[in]** start address to be unlocked
- **cnt** – **[in]** count of cache lines to be unlocked

__STATIC_FORCEINLINE void MInvalICache (void)

Invalidate all I-Cache lines in M-Mode.

This function invalidate all I-Cache lines. Command CCM_IC_INVAL_ALL is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters **addr** – **[in]** start address to be invalidated

__STATIC_FORCEINLINE void SInvalICache (void)

Invalidate all I-Cache lines in S-Mode.

This function invalidate all I-Cache lines. Command CCM_IC_INVAL_ALL is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters **addr** – **[in]** start address to be invalidated

__STATIC_FORCEINLINE void UInvalICache (void)

Invalidate all I-Cache lines in U-Mode.

This function invalidate all I-Cache lines. Command CCM_IC_INVAL_ALL is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters **addr** – **[in]** start address to be invalidated

D-Cache Functions

`__STATIC_FORCEINLINE int32_t DCachePresent (void)`

`__STATIC_FORCEINLINE void EnableDCache (void)`

`__STATIC_FORCEINLINE void DisableDCache (void)`

`__STATIC_FORCEINLINE void EnableDCacheECC (void)`

`__STATIC_FORCEINLINE void DisableDCacheECC (void)`

`__STATIC_FORCEINLINE int32_t GetDCacheInfo (CacheInfo_Type *info)`

`__STATIC_FORCEINLINE void MInvalDCacheLine (unsigned long addr)`

`__STATIC_FORCEINLINE void MInvalDCacheLines (unsigned long addr, unsigned long cnt)`

`__STATIC_FORCEINLINE void SInvalDCacheLine (unsigned long addr)`

`__STATIC_FORCEINLINE void SInvalDCacheLines (unsigned long addr, unsigned long cnt)`

`__STATIC_FORCEINLINE void UInvalDCacheLine (unsigned long addr)`

`__STATIC_FORCEINLINE void UInvalDCacheLines (unsigned long addr, unsigned long cnt)`

`__STATIC_FORCEINLINE void MFlushDCacheLine (unsigned long addr)`

`__STATIC_FORCEINLINE void MFlushDCacheLines (unsigned long addr, unsigned long cnt)`

`__STATIC_FORCEINLINE void SFlushDCacheLine (unsigned long addr)`

`__STATIC_FORCEINLINE void SFlushDCacheLines (unsigned long addr, unsigned long cnt)`

`__STATIC_FORCEINLINE void UFlushDCacheLine (unsigned long addr)`

`__STATIC_FORCEINLINE void UFlushDCacheLines (unsigned long addr, unsigned long cnt)`

`__STATIC_FORCEINLINE void MFlushInvalDCacheLine (unsigned long addr)`

`__STATIC_FORCEINLINE void MFlushInvalDCacheLines (unsigned long addr, unsigned long cnt)`

__STATIC_FORCEINLINE void SFlushInvalDCacheLine (unsigned long addr)

__STATIC_FORCEINLINE void SFlushInvalDCacheLines (unsigned long addr, unsigned long cnt)

__STATIC_FORCEINLINE void UFlushInvalDCacheLine (unsigned long addr)

__STATIC_FORCEINLINE void UFlushInvalDCacheLines (unsigned long addr, unsigned long cnt)

__STATIC_FORCEINLINE unsigned long MLockDCacheLine (unsigned long addr)

__STATIC_FORCEINLINE unsigned long MLockDCacheLines (unsigned long addr,
unsigned long cnt)

__STATIC_FORCEINLINE unsigned long SLockDCacheLine (unsigned long addr)

__STATIC_FORCEINLINE unsigned long SLockDCacheLines (unsigned long addr,
unsigned long cnt)

__STATIC_FORCEINLINE unsigned long ULockDCacheLine (unsigned long addr)

__STATIC_FORCEINLINE unsigned long ULockDCacheLines (unsigned long addr,
unsigned long cnt)

__STATIC_FORCEINLINE void MUnlockDCacheLine (unsigned long addr)

__STATIC_FORCEINLINE void MUnlockDCacheLines (unsigned long addr, unsigned long cnt)

__STATIC_FORCEINLINE void SUnlockDCacheLine (unsigned long addr)

__STATIC_FORCEINLINE void SUnlockDCacheLines (unsigned long addr, unsigned long cnt)

__STATIC_FORCEINLINE void UUnlockDCacheLine (unsigned long addr)

__STATIC_FORCEINLINE void UUnlockDCacheLines (unsigned long addr, unsigned long cnt)

__STATIC_FORCEINLINE void MInvalDCache (void)

__STATIC_FORCEINLINE void SInvalDCache (void)

__STATIC_FORCEINLINE void UInvalDCache (void)

__STATIC_FORCEINLINE void MFlushDCache (void)

`__STATIC_FORCEINLINE void SFlushDCache (void)`

`__STATIC_FORCEINLINE void UFlushDCache (void)`

`__STATIC_FORCEINLINE void MFlushInvalDCache (void)`

`__STATIC_FORCEINLINE void SFlushInvalDCache (void)`

`__STATIC_FORCEINLINE void UFlushInvalDCache (void)`

group `NMSIS_Core_DCache`

Functions that configure Data Cache.

Functions

`__STATIC_FORCEINLINE int32_t DCachePresent (void)`

Check DCache Unit Present or Not.

This function check dcache unit present or not via mcfg_info csr

---

Remark

- This function might not work for some old nuclei processors
- Please make sure the version of your nuclei processor contain DCACHE bit in mcfg_info

---

Returns 1 if present otherwise 0

`__STATIC_FORCEINLINE void EnableDCache (void)`

Enable DCache.

This function enable D-Cache

Remark

- This function can be called in M-Mode only.
- This *CSR_MCACHE_CTL* (page 106) register control D Cache enable.

See also:

- DisableDCache

`__STATIC_FORCEINLINE void DisableDCache (void)`

Disable DCache.

This function Disable D-Cache

Remark

- This function can be called in M-Mode only.
- This *CSR_MCACHE_CTL* (page 106) register control D Cache enable.

See also:

- EnableDCache

`__STATIC_FORCEINLINE void EnableDCacheECC (void)`

Enable DCache ECC.

This function enable D-Cache ECC

Remark

- This function can be called in M-Mode only.
- This *CSR_MCACHE_CTL* (page 106) register control D Cache ECC enable.

See also:

- DisableDCacheECC

`__STATIC_FORCEINLINE void DisableDCacheECC (void)`

Disable DCache ECC.

This function disable D-Cache ECC

Remark

- This function can be called in M-Mode only.
- This *CSR_MCACHE_CTL* (page 106) register control D Cache ECC enable.

See also:

- EnableDCacheECC

`__STATIC_FORCEINLINE int32_t GetDCacheInfo (CacheInfo_Type *info)`

Get D-Cache Information.

This function get D-Cache Information

Remark

- This function can be called in M-Mode only.
- You can use this function in combination with cache lines operations

See also:

- GetICacheInfo

`__STATIC_FORCEINLINE void MInvalDCacheLine (unsigned long addr)`

Invalidate one D-Cache line specified by address in M-Mode.

This function unlock and invalidate one D-Cache line specified by the address. Command CCM_DC_INVAL is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters **addr** – **[in]** start address to be invalidated

`__STATIC_FORCEINLINE void MInvalDCacheLines (unsigned long addr, unsigned long cnt)`

Invalidate several D-Cache lines specified by address in M-Mode.

This function unlock and invalidate several D-Cache lines specified by the address and line count. Command CCM_DC_INVAL is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters

- **addr** – **[in]** start address to be invalidated
- **cnt** – **[in]** count of cache lines to be invalidated

`__STATIC_FORCEINLINE void SInvalDCacheLine (unsigned long addr)`

Invalidate one D-Cache line specified by address in S-Mode.

This function unlock and invalidate one D-Cache line specified by the address. Command CCM_DC_INVAL is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M/S-Mode only.

Parameters **addr** – **[in]** start address to be invalidated

`__STATIC_FORCEINLINE void SInvalDCacheLines (unsigned long addr, unsigned long cnt)`

Invalidate several D-Cache lines specified by address in S-Mode.

This function unlock and invalidate several D-Cache lines specified by the address and line count. Command CCM_DC_INVAL is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters

- **addr** – **[in]** start address to be invalidated
- **cnt** – **[in]** count of cache lines to be invalidated

`__STATIC_FORCEINLINE void UInvalDCacheLine (unsigned long addr)`

Invalidate one D-Cache line specified by address in U-Mode.

This function unlock and invalidate one D-Cache line specified by the address. Command CCM_DC_INVAL is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters **addr** – **[in]** start address to be invalidated

`__STATIC_FORCEINLINE void UInvalDCacheLines (unsigned long addr, unsigned long cnt)`

Invalidate several D-Cache lines specified by address in U-Mode.

This function unlock and invalidate several D-Cache lines specified by the address and line count. Command CCM_DC_INVAL is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters

- **addr** – **[in]** start address to be invalidated
- **cnt** – **[in]** count of cache lines to be invalidated

`__STATIC_FORCEINLINE void MFlushDCacheLine (unsigned long addr)`

Flush one D-Cache line specified by address in M-Mode.

This function flush one D-Cache line specified by the address. Command CCM_DC_WB is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters **addr** – **[in]** start address to be flushed

`__STATIC_FORCEINLINE void MFlushDCacheLines (unsigned long addr, unsigned long cnt)`

Flush several D-Cache lines specified by address in M-Mode.

This function flush several D-Cache lines specified by the address and line count. Command CCM_DC_WB is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters

- **addr** – **[in]** start address to be flushed
- **cnt** – **[in]** count of cache lines to be flushed

`__STATIC_FORCEINLINE void SFlushDCacheLine (unsigned long addr)`

Flush one D-Cache line specified by address in S-Mode.

This function flush one D-Cache line specified by the address. Command CCM_DC_WB is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters **addr** – **[in]** start address to be flushed

`__STATIC_FORCEINLINE void SFlushDCacheLines (unsigned long addr, unsigned long cnt)`

Flush several D-Cache lines specified by address in S-Mode.

This function flush several D-Cache lines specified by the address and line count. Command CCM_DC_WB is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters

- **addr** – **[in]** start address to be flushed
- **cnt** – **[in]** count of cache lines to be flushed

`__STATIC_FORCEINLINE void UFlushDCacheLine (unsigned long addr)`

Flush one D-Cache line specified by address in U-Mode.

This function flush one D-Cache line specified by the address. Command CCM_DC_WB is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters **addr** – **[in]** start address to be flushed

`__STATIC_FORCEINLINE void UFlushDCacheLines (unsigned long addr, unsigned long cnt)`

Flush several D-Cache lines specified by address in U-Mode.

This function flush several D-Cache lines specified by the address and line count. Command CCM_DC_WB is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters

- **addr** – **[in]** start address to be flushed
- **cnt** – **[in]** count of cache lines to be flushed

`__STATIC_FORCEINLINE void MFlushInvalDCacheLine (unsigned long addr)`

Flush and invalidate one D-Cache line specified by address in M-Mode.

This function flush and invalidate one D-Cache line specified by the address. Command CCM_DC_WBINVAL is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters **addr** – **[in]** start address to be flushed and invalidated

`__STATIC_FORCEINLINE void MFlushInvalDCacheLines (unsigned long addr, unsigned long cnt)`

Flush and invalidate several D-Cache lines specified by address in M-Mode.

This function flush and invalidate several D-Cache lines specified by the address and line count. Command CCM_DC_WBINVAL is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters

- `addr` – **[in]** start address to be flushed and invalidated
- `cnt` – **[in]** count of cache lines to be flushed and invalidated

`__STATIC_FORCEINLINE void SFlushInvalDCacheLine (unsigned long addr)`

Flush and invalidate one D-Cache line specified by address in S-Mode.

This function flush and invalidate one D-Cache line specified by the address. Command CCM_DC_WBINVAL is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters `addr` – **[in]** start address to be flushed and invalidated

`__STATIC_FORCEINLINE void SFlushInvalDCacheLines (unsigned long addr, unsigned long cnt)`

Flush and invalidate several D-Cache lines specified by address in S-Mode.

This function flush and invalidate several D-Cache lines specified by the address and line count. Command CCM_DC_WBINVAL is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters

- `addr` – **[in]** start address to be flushed and invalidated
- `cnt` – **[in]** count of cache lines to be flushed and invalidated

`__STATIC_FORCEINLINE void UFlushInvalDCacheLine (unsigned long addr)`

Flush and invalidate one D-Cache line specified by address in U-Mode.

This function flush and invalidate one D-Cache line specified by the address. Command CCM_DC_WBINVAL is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters `addr` – **[in]** start address to be flushed and invalidated

__STATIC_FORCEINLINE void UFlushInvalDCacheLines (unsigned long addr, unsigned long cnt)

Flush and invalidate several D-Cache lines specified by address in U-Mode.

This function flush and invalidate several D-Cache lines specified by the address and line count. Command CCM_DC_WBINVAL is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters

- **addr** – **[in]** start address to be flushed and invalidated
- **cnt** – **[in]** count of cache lines to be flushed and invalidated

__STATIC_FORCEINLINE unsigned long MLockDCacheLine (unsigned long addr)

Lock one D-Cache line specified by address in M-Mode.

This function lock one D-Cache line specified by the address. Command CCM_DC_LOCK is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters **addr** – **[in]** start address to be locked

Returns result of CCM lock operation, see enum CCM_OP_FINFO

__STATIC_FORCEINLINE unsigned long MLockDCacheLines (unsigned long addr, unsigned long cnt)

Lock several D-Cache lines specified by address in M-Mode.

This function lock several D-Cache lines specified by the address and line count. Command CCM_DC_LOCK is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters

- **addr** – **[in]** start address to be locked
- **cnt** – **[in]** count of cache lines to be locked

Returns result of CCM lock operation, see enum CCM_OP_FINFO

__STATIC_FORCEINLINE unsigned long SLockDCacheLine (unsigned long addr)

Lock one D-Cache line specified by address in S-Mode.

This function lock one D-Cache line specified by the address. Command CCM_DC_LOCK is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters **addr** – **[in]** start address to be locked

Returns result of CCM lock operation, see enum CCM_OP_FINFO

`__STATIC_FORCEINLINE unsigned long SLockDCacheLines (unsigned long addr, unsigned long cnt)`

Lock several D-Cache lines specified by address in S-Mode.

This function lock several D-Cache lines specified by the address and line count. Command CCM_DC_LOCK is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters

- **addr** – **[in]** start address to be locked
- **cnt** – **[in]** count of cache lines to be locked

Returns result of CCM lock operation, see enum CCM_OP_FINFO

`__STATIC_FORCEINLINE unsigned long ULockDCacheLine (unsigned long addr)`

Lock one D-Cache line specified by address in U-Mode.

This function lock one D-Cache line specified by the address. Command CCM_DC_LOCK is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters **addr** – **[in]** start address to be locked

Returns result of CCM lock operation, see enum CCM_OP_FINFO

`__STATIC_FORCEINLINE unsigned long ULockDCacheLines (unsigned long addr, unsigned long cnt)`

Lock several D-Cache lines specified by address in U-Mode.

This function lock several D-Cache lines specified by the address and line count. Command CCM_DC_LOCK is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters

- **addr** – **[in]** start address to be locked
- **cnt** – **[in]** count of cache lines to be locked

Returns result of CCM lock operation, see enum CCM_OP_FINFO

`__STATIC_FORCEINLINE void MUnlockDCacheLine (unsigned long addr)`

Unlock one D-Cache line specified by address in M-Mode.

This function unlock one D-Cache line specified by the address. Command CCM_DC_UNLOCK is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters **addr** – **[in]** start address to be unlocked

`__STATIC_FORCEINLINE void MUnlockDCacheLines (unsigned long addr, unsigned long cnt)`

Unlock several D-Cache lines specified by address in M-Mode.

This function unlock several D-Cache lines specified by the address and line count. Command CCM_DC_UNLOCK is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters

- **addr** – **[in]** start address to be unlocked
- **cnt** – **[in]** count of cache lines to be unlocked

`__STATIC_FORCEINLINE void SUnlockDCacheLine (unsigned long addr)`

Unlock one D-Cache line specified by address in S-Mode.

This function unlock one D-Cache line specified by the address. Command CCM_DC_UNLOCK is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters **addr** – **[in]** start address to be unlocked

`__STATIC_FORCEINLINE void SUnlockDCacheLines (unsigned long addr, unsigned long cnt)`

Unlock several D-Cache lines specified by address in S-Mode.

This function unlock several D-Cache lines specified by the address and line count. Command CCM_DC_UNLOCK is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters

- **addr** – **[in]** start address to be unlocked
- **cnt** – **[in]** count of cache lines to be unlocked

`__STATIC_FORCEINLINE void UUnlockDCacheLine (unsigned long addr)`

Unlock one D-Cache line specified by address in U-Mode.

This function unlock one D-Cache line specified by the address. Command CCM_DC_UNLOCK is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters **addr** – **[in]** start address to be unlocked

`__STATIC_FORCEINLINE void UUnlockDCacheLines (unsigned long addr, unsigned long cnt)`

Unlock several D-Cache lines specified by address in U-Mode.

This function unlock several D-Cache lines specified by the address and line count. Command CCM_DC_UNLOCK is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters

- **addr** – **[in]** start address to be unlocked
- **cnt** – **[in]** count of cache lines to be unlocked

`__STATIC_FORCEINLINE void MInvalDCache (void)`

Invalidate all D-Cache lines in M-Mode.

This function invalidate all D-Cache lines. Command CCM_DC_INVAL_ALL is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters `addr` – **[in]** start address to be invalidated

`__STATIC_FORCEINLINE void SInvalDCache (void)`

Invalidate all D-Cache lines in S-Mode.

This function invalidate all D-Cache lines. Command CCM_DC_INVAL_ALL is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters `addr` – **[in]** start address to be invalidated

`__STATIC_FORCEINLINE void UInvalDCache (void)`

Invalidate all D-Cache lines in U-Mode.

This function invalidate all D-Cache lines. In U-Mode, this operation will be automatically translated to flush and invalidate operations by hardware. Command CCM_DC_INVAL_ALL is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters `addr` – **[in]** start address to be invalidated

`__STATIC_FORCEINLINE void MFlushDCache (void)`

Flush all D-Cache lines in M-Mode.

This function flush all D-Cache lines. Command CCM_DC_WB_ALL is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters `addr` – **[in]** start address to be flushed

`__STATIC_FORCEINLINE void SFlushDCache (void)`

Flush all D-Cache lines in S-Mode.

This function flush all D-Cache lines. Command CCM_DC_WB_ALL is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters `addr` – **[in]** start address to be flushed

`__STATIC_FORCEINLINE void UFlushDCache (void)`

Flush all D-Cache lines in U-Mode.

This function flush all D-Cache lines. Command CCM_DC_WB_ALL is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters `addr` – **[in]** start address to be flushed

`__STATIC_FORCEINLINE void MFlushInvalDCache (void)`

Flush and invalidate all D-Cache lines in M-Mode.

This function flush and invalidate all D-Cache lines. Command CCM_DC_WBINVAL_ALL is written to CSR *CSR_CCM_MCOMMAND* (page 108).

Remark

This function must be executed in M-Mode only.

Parameters `addr` – **[in]** start address to be flushed and locked

`__STATIC_FORCEINLINE void SFlushInvalDCache (void)`

Flush and invalidate all D-Cache lines in S-Mode.

This function flush and invalidate all D-Cache lines. Command CCM_DC_WBINVAL_ALL is written to CSR *CSR_CCM_SCOMMAND* (page 109).

Remark

This function must be executed in M/S-Mode only.

Parameters `addr` – **[in]** start address to be flushed and locked

`__STATIC_FORCEINLINE void UFlushInvalDCache (void)`

Flush and invalidate all D-Cache lines in U-Mode.

This function flush and invalidate all D-Cache lines. Command CCM_DC_WBINVAL_ALL is written to CSR *CSR_CCM_UCOMMAND* (page 109).

Remark

This function must be executed in M/S/U-Mode only.

Parameters `addr` – **[in]** start address to be flushed and locked

2.5.15 System Device Configuration

group `NMSIS_Core_SystemConfig`

Functions for system and clock setup available in system_<device>.c.

Nuclei provides a template file **system_Device.c** that must be adapted by the silicon vendor to match their actual device. As a **minimum requirement**, this file must provide:

- A device-specific system configuration function, *SystemInit* (page 629).
- Global c library *_premain_init* (page 631) and *_postmain_fini* (page 631) functions called right before calling main function.
  - A global variable that contains the system frequency, *SystemCoreClock* (page 631).
  - A global eclic configuration initialization, *ECLIC_Init* (page 629).
  - A global exception and trap configuration initialization, *Trap_Init* (page 630) and *Exception_Init* (page 632).
- Vendor customized interrupt, exception and nmi handling code, see *Interrupt and Exception and NMI Handling* (page 632)

The file configures the device and, typically, initializes the oscillator (PLL) that is part of the microcontroller device. This file might export other functions or variables that provide a more flexible configuration of the microcontroller system.

And this file also provided common interrupt, exception and NMI exception handling framework template, Silicon vendor can customize these template code as they want.

Attention Be aware that a value stored to `SystemCoreClock` during low level initialization (i.e. `SystemInit()` (page 629)) might get overwritten by C libray startup code and/or .bss section initialization. Thus its highly recommended to call *SystemCoreClockUpdate* (page 629) at the beginning of the user `main()` routine.

Note: Please pay special attention to the static variable `SystemCoreClock`. This variable might be used throughout the whole system initialization and runtime to calculate frequency/time related values. Thus one must assure that the variable always reflects the actual system clock speed.

Defines

`FALLBACK_DEFAULT_ECLIC_BASE` 0x0C000000UL

`FALLBACK_DEFAULT_SYSTIMER_BASE` 0x02000000UL

`CLINT_MSIP`(base, hartid) (*(volatile uint32_t *)((uintptr_t)((base) + ((hartid) * 4))))

`SMP_CTRLREG`(base, ofs) (*(volatile uint32_t *)((uintptr_t)((base) + (ofs))))

Typedefs

typedef void (***fnptr**)(void)

Functions

void **default_intexc_handler**(void)

default eclic interrupt or exception interrupt handler

void **SystemCoreClockUpdate**(void)

Function to update the variable *SystemCoreClock* (page 631).

Updates the variable *SystemCoreClock* (page 631) and must be called whenever the core clock is changed during program execution. The function evaluates the clock register settings and calculates the current core clock.

void **SystemInit**(void)

Function to Initialize the system.

Initializes the microcontroller system. Typically, this function configures the oscillator (PLL) that is part of the microcontroller device. For systems with a variable clock speed, it updates the variable *SystemCoreClock* (page 631). SystemInit is called from the file **startup**.

void **SystemBannerPrint**(void)

Banner Print for Nuclei SDK.

void **ECLIC_Init**(void)

initialize eclic config

ECLIC needs be initialized after boot up, Vendor could also change the initialization configuration.

int32_t **ECLIC_Register_IRQ**(IRQn_Type IRQn, uint8_t shv, ECLIC_TRIGGER_Type trig_mode, uint8_t lvl, uint8_t priority, void *handler)

Initialize a specific IRQ and register the handler.

This function set vector mode, trigger mode and polarity, interrupt level and priority, assign handler for specific IRQn.

Remark

- This function use to configure specific eclic interrupt and register its interrupt handler and enable its interrupt.
- If the vector table is placed in read-only section(FLASHXIP mode), handler could not be installed

Parameters

- **IRQn** – **[in]** NMI interrupt handler address
- **shv** – **[in]** *ECLIC_NON_VECTOR_INTERRUPT* (page 143) means non-vector mode, and *ECLIC_VECTOR_INTERRUPT* (page 143) is vector mode
- **trig_mode** – **[in]** see ECLIC_TRIGGER_Type
- **lvl** – **[in]** interupt level

- **priority** – **[in]** interrupt priority
- **handler** – **[in]** interrupt handler, if NULL, handler will not be installed

Returns -1 means invalid input parameter. 0 means successful.

int32_t **ECLIC_Register_IRQ_S**(IRQn_Type IRQn, uint8_t shv, ECLIC_TRIGGER_Type trig_mode, uint8_t lvl, uint8_t priority, void *handler)

Initialize a specific IRQ and register the handler for supervisor mode.

This function set vector mode, trigger mode and polarity, interrupt level and priority, assign handler for specific IRQn.

Remark

- This function use to configure specific eclic S-mode interrupt and register its interrupt handler and enable its interrupt.
- If the vector table is placed in read-only section (FLASHXIP mode), handler could not be installed.

Parameters

- **IRQn** – **[in]** NMI interrupt handler address
- **shv** – **[in]** *ECLIC_NON_VECTOR_INTERRUPT* (page 143) means non-vector mode, and *ECLIC_VECTOR_INTERRUPT* (page 143) is vector mode
- **trig_mode** – **[in]** see ECLIC_TRIGGER_Type
- **lvl** – **[in]** interupt level
- **priority** – **[in]** interrupt priority
- **handler** – **[in]** interrupt handler, if NULL, handler will not be installed

Returns -1 means invalid input parameter. 0 means successful.

static void **_get_iregion_info**(IRegion_Info_Type *iregion)

Get Nuclei Internal Region Information.

This function is used to get nuclei cpu internal region information, such as iregion base, eclic base, smp base, timer base and idu base, and fallback to old evalsoc timer and eclic base if no iregion feature found

void **__sync_harts**(void)

Synchronize all harts.

This function is used to synchronize all the harts, especially to wait the boot hart finish initialization of data section, bss section and c runtines initialization This function must be placed in .text.init section, since section initialization is not ready, global variable and static variable should be avoid to use in this function, and avoid to call other functions

static void **Trap_Init**(void)

do the init for trap(interrupt and exception) entry for supervisor mode

This function provide initialization of CSR_STVT CSR_STVT2 and CSR_STVEC.

void **_premain_init**(void)

early init function before main

This function is executed right before main function. For RISC-V gnu toolchain, _init function might not be called by __libc_init_array function, so we defined a new function to do initialization.

void **_postmain_fini**(int status)

finish function after main

This function is executed right after main function. For RISC-V gnu toolchain, _fini function might not be called by __libc_fini_array function, so we defined a new function to do initialization

Parameters **status** – **[in]** status code return from main

void **_init**(void)

_init function called in __libc_init_array()

This `__libc_init_array()` function is called during startup code, user need to implement this function, otherwise when link it will error init.c:(.text.__libc_init_array+0x26): undefined reference to _init

Note: Please use *_premain_init* (page 631) function now

void **_fini**(void)

_fini function called in __libc_fini_array()

This `__libc_fini_array()` function is called when exit main. user need to implement this function, otherwise when link it will error fini.c:(.text.__libc_fini_array+0x28): undefined reference to _fini

Note: Please use *_postmain_fini* (page 631) function now

Variables

fnptr (page 629) **irq_entry_s**

default entry for s-mode non-vector irq entry

fnptr (page 629) **exc_entry_s**

default entry for s-mode exception entry

uint32_t **SystemCoreClock** = SYSTEM_CLOCK

Variable to hold the system core clock value.

Holds the system core clock, which is the system clock frequency supplied to the SysTick timer and the processor core clock. This variable can be used by debuggers to query the frequency of the debug timer or to configure the trace clock speed.

Attention Compilers must be configured to avoid removing this variable in case the application program is not using it. Debugging systems require the variable to be physically present in memory so that it can be examined to configure the debugger.

IRegion_Info_Type **SystemIRegionInfo**

Nuclei RISC-V CPU IRegion Information Variable used to store probed info.

Interrupt Exception NMI Handling

group **NMSIS_Core_IntExcNMI_Handling**

Functions for interrupt, exception and nmi handle available in system_<device>.c.

Nuclei provide a template for interrupt, exception and NMI handling. Silicon Vendor could adapat according to their requirement. Silicon vendor could implement interface for different exception code and replace current implementation.

Defines

MAX_SYSTEM_EXCEPTION_NUM 26

Max exception handler number, don't include the NMI(0xFFF) one.

Typedefs

typedef void (***EXC_HANDLER**)(unsigned long cause, unsigned long sp)

Exception Handler Function Typedef.

Note: This typedef is only used internal in this system_<Device>.c file. It is used to do type conversion for registered exception handler before calling it.

Functions

static void **system_default_exception_handler**(unsigned long mcause, unsigned long sp)

System Default Exception Handler.

This function provides a default exception and NMI handler for all exception ids. By default, It will just print some information for debug, Vendor can customize it according to its requirements.

Parameters

- **mcause** – **[in]** code indicating the reason that caused the trap in machine mode
- **sp** – **[in]** stack pointer

static void **Exception_Init**(void)

Initialize all the default core exception handlers.

The core exception handler for each exception id will be initialized to *system_default_exception_handler* (page 632).

Note: Called in *_init* (page 631) function, used to initialize default exception handlers for all exception IDs SystemExceptionHandlers contains NMI, but SystemExceptionHandlers_S not, because NMI can't be delegated to S-mode.

void **Exception_DumpFrame**(unsigned long sp, uint8_t mode)

Dump Exception Frame.

This function provided feature to dump exception frame stored in stack.

Parameters

- **sp** – **[in]** stackpoint
- **mode** – **[in]** privileged mode to decide whether to dump msubm CSR

void **Exception_Register_EXC**(uint32_t EXCn, unsigned long exc_handler)

Register an exception handler for exception code EXCn.

- For EXCn < *MAX_SYSTEM_EXCEPTION_NUM* (page 632), it will be registered into SystemExceptionHandlers[EXCn-1].
- For EXCn == NMI_EXCn, it will be registered into SystemExceptionHandlers[MAX_SYSTEM_EXCEPTION_NUM].

Parameters

- **EXCn** – **[in]** See EXCn_Type
- **exc_handler** – **[in]** The exception handler for this exception code EXCn

unsigned long **Exception_Get_EXC**(uint32_t EXCn)

Get current exception handler for exception code EXCn.

- For EXCn < *MAX_SYSTEM_EXCEPTION_NUM* (page 632), it will return SystemExceptionHandlers[EXCn-1].
- For EXCn == NMI_EXCn, it will return SystemExceptionHandlers[MAX_SYSTEM_EXCEPTION_NUM].

Parameters **EXCn** – **[in]** See EXCn_Type

Returns Current exception handler for exception code EXCn, if not found, return 0.

uint32_t **core_exception_handler**(unsigned long mcause, unsigned long sp)

Common NMI and Exception handler entry.

This function provided a command entry for NMI and exception. Silicon Vendor could modify this template implementation according to requirement.

Remark

- RISCV provided common entry for all types of exception. This is proposed code template for exception entry function, Silicon Vendor could modify the implementation.
- For the core_exception_handler template, we provided exception register function *Exception_Register_EXC* (page 633) which can help developer to register your exception handler for specific exception number.

Parameters

- **mcause** – **[in]** code indicating the reason that caused the trap in machine mode
- **sp** – **[in]** stack pointer

static void **system_default_exception_handler_s**(unsigned long scause, unsigned long sp)

Supervisor mode system Default Exception Handler.

This function provided a default supervisor mode exception and NMI handling code for all exception ids. By default, It will just print some information for debug, Vendor can customize it according to its requirements.

Parameters

- **scause** – **[in]** code indicating the reason that caused the trap in supervisor mode
- **sp** – **[in]** stack pointer

void **Exception_Register_EXC_S**(uint32_t EXCn, unsigned long exc_handler)

Register an exception handler for exception code EXCn of supervisor mode.

-For EXCn < *MAX_SYSTEM_EXCEPTION_NUM* (page 632), it will be registered into SystemExceptionHandlers_S[EXCn-1]. -For EXCn == NMI_EXCn, The NMI (Non-maskable-interrupt) cannot be trapped to the supervisor-mode or user-mode for any configuration, so NMI won't be registered into SystemExceptionHandlers_S.

Parameters

- **EXCn** – **[in]** See EXCn_Type
- **exc_handler** – **[in]** The exception handler for this exception code EXCn

unsigned long **Exception_Get_EXC_S**(uint32_t EXCn)

Get current exception handler for exception code EXCn of supervisor mode.

- For EXCn < *MAX_SYSTEM_EXCEPTION_NUM* (page 632), it will return SystemExceptionHandlers_S[EXCn-1].

Parameters **EXCn** – **[in]** See EXCn_Type

Returns Current exception handler for exception code EXCn, if not found, return 0.

uint32_t **core_exception_handler_s**(unsigned long scause, unsigned long sp)

common Exception handler entry of supervisor mode

This function provided a supervisor mode common entry for exception. Silicon Vendor could modify this template implementation according to requirement.

Remark

- RISCV provided supervisor mode common entry for all types of exception. This is proposed code template for exception entry function, Silicon Vendor could modify the implementation.
- For the core_exception_handler_s template, we provided exception register function *Exception_Register_EXC_S* (page 634) which can help developer to register your exception handler for specific exception number.

Parameters

- **scause** – **[in]** code indicating the reason that caused the trap in supervisor mode
- **sp** – **[in]** stack pointer

Variables

static unsigned long **SystemExceptionHandlers**[MAX_SYSTEM_EXCEPTION_NUM + 1]

Store the exception handlers for each exception ID.

Note:

- This SystemExceptionHandlers are used to store all the handlers for all the exception codes Nuclei N/NX core provided.
- Exception code 0 - 25, totally 26 exceptions are mapped to SystemExceptionHandlers[0:25]
- Exception for NMI is also re-routed to exception handling(exception code 0xFFF) in startup code configuration, the handler itself is mapped to SystemExceptionHandlers[MAX_SYSTEM_EXCEPTION_NUM]

static unsigned long **SystemExceptionHandlers_S**[MAX_SYSTEM_EXCEPTION_NUM]

Store the exception handlers for each exception ID in supervisor mode.

Note:

- This SystemExceptionHandlers_S are used to store all the handlers for all the exception codes Nuclei N/NX core provided.
- Exception code 0 - 11, totally 12 exceptions are mapped to SystemExceptionHandlers_S[0:11]
- The NMI (Non-maskable-interrupt) cannot be trapped to the supervisor-mode or user-mode for any configuration

2.5.16 ARM Compatiable Functions

group **NMSIS_Core_ARMCompatiable_Functions**

A few functions that compatiable with ARM CMSIS-Core.

Here we provided a few functions that compatiable with ARM CMSIS-Core, mostly used in the DSP and NN library.

Defines

__ISB() __RWMB()
Instruction Synchronization Barrier, compatiable with ARM.

__DSB() __RWMB()
Data Synchronization Barrier, compatiable with ARM.

__DMB() __RWMB()
Data Memory Barrier, compatiable with ARM.

__LDRBT(ptr) __LB((ptr))
LDRT Unprivileged (8 bit), ARM Compatiable.

__LDRHT(ptr) __LH((ptr))
LDRT Unprivileged (16 bit), ARM Compatiable.

__LDRT(ptr) __LW((ptr))
LDRT Unprivileged (32 bit), ARM Compatiable.

__STRBT(val, ptr) __SB((ptr), (val))
STRT Unprivileged (8 bit), ARM Compatiable.

__STRHT(val, ptr) __SH((ptr), (val))
STRT Unprivileged (16 bit), ARM Compatiable.

__STRT(val, ptr) __SW((ptr), (val))
STRT Unprivileged (32 bit), ARM Compatiable.

__SSAT(val, sat) __RV_SCLIP32((val), (sat-1))
Signed Saturate.

Saturates a signed value.

Parameters

- **value** – **[in]** Value to be saturated
- **sat** – **[in]** Bit position to saturate to (1..32)

Returns Saturated value

__USAT(val, sat) __RV_UCLIP32((val), (sat))
Unsigned Saturate.

Saturates an unsigned value.

Parameters

- **value** – **[in]** Value to be saturated
- **sat** – **[in]** Bit position to saturate to (0..31)

Returns Saturated value

__RBIT(value) __RV_BITREVI((value), 31)
Reverse bit order of value.

Reverses the bit order of the given value.

Parameters

- **value** – **[in]** Value to reverse

Returns Reversed value

__CLZ(data) __RV_CLZ32(data)

Count leading zeros.

Counts the number of leading zeros of a data value.

Parameters

- **data** – **[in]** Value to count the leading zeros

Returns number of leading zeros in value

__EXPD_BYTE(x)

Expand byte to unsigned long value.

Expand byte value x to unsigned long value's each byte.

Parameters

- **x** – **[in]** the byte value to be expand, the input must be uint8_t type

Returns Expanded value in unsigned long

Functions

__STATIC_FORCEINLINE uint32_t __REV (uint32_t value)

Reverse byte order (32 bit)

Reverses the byte order in unsigned integer value. For example, 0x12345678 becomes 0x78563412.

Parameters **value** – **[in]** Value to reverse

Returns Reversed value

__STATIC_FORCEINLINE uint32_t __REV16 (uint32_t value)

Reverse byte order (16 bit)

Reverses the byte order within each halfword of a word. For example, 0x12345678 becomes 0x34127856.

Parameters **value** – **[in]** Value to reverse

Returns Reversed value

__STATIC_FORCEINLINE int16_t __REVSH (int16_t value)

Reverse byte order (16 bit)

Reverses the byte order in a 16-bit value and returns the signed 16-bit result. For example, 0x0080 becomes 0x8000.

Parameters **value** – **[in]** Value to reverse

Returns Reversed value

__STATIC_FORCEINLINE uint32_t __ROR (uint32_t op1, uint32_t op2)

Rotate Right in unsigned value (32 bit)

Rotate Right (immediate) provides the value of the contents of a register rotated by a variable number of bits.

Parameters

- `op1` – **[in]** Value to rotate
- `op2` – **[in]** Number of Bits to rotate(0-31)

Returns Rotated value

`__STATIC_FORCEINLINE unsigned long __CTZ (unsigned long data)`

Count tailing zero.

Return the count of least-significant bit zero.for example, return 3 if x=0bxxx1000

Parameters `data` – **[in]** Value to count the tailing zeros

Returns number of tailing zeros in value

CHAPTER

THREE

NMSIS DSP

3.1 Overview

3.1.1 Introduction

This user manual describes the NMSIS DSP software library, a suite of common signal processing functions for use on Nuclei N/NX Class Processors based devices.

The library is divided into a number of functions each covering a specific category:

- Basic math functions
- Bayes functions
- Complex math functions
- Controler functions
- Distance functions
- Fast math functions
- Filtering functions
- Interpolation functions
- Matrix functions
- Quaternion math functions
- Statistical functions
- Support functions
- SVM functions
- Transform functions
- Window functions

The library has separate functions for operating on 8-bit integers, 16-bit integers, 32-bit integers and 32-bit floating-point values.

3.1.2 Using the Library

The library functions are declared in the public file `riscv_math.h` which is placed in the `NMSIS/DSP/Include` and `NMSIS/DSP/PrivateInclude` folder.

Simply include this file and link the appropriate library in the application and begin calling the library functions.

The Library supports single public header file `riscv_math.h` for Nuclei N/NX Class Processors cores with little endian. Same header file will be used for floating point unit(FPU) variants.

3.1.3 Examples

The library ships with *a number of examples* (page 1017) which demonstrate how to use the library functions.

3.1.4 Toolchain Support

The library has been developed and tested with RISC-V GCC Toolchain.

The library is being tested in GCC toolchain and updates on this activity will be made available shortly.

3.1.5 Building the Library

The library installer contains a **Makefile** to rebuild libraries on Nuclei RISC-V GCC toolchain in the **NMSIS/** folder.

The library can be built by run `make gen_dsp_lib`, it will build and install DSP library into **Library/DSP/GCC** folder.

3.1.6 Preprocessor Macros

Each library project have different pre-processor macros controlled via CMakeLists.txt.

This library is only built for little endian targets.

3.2 Using NMSIS-DSP

Here we will describe how to run the nmsis dsp examples in Nuclei QEMU.

3.2.1 Preparation

- Nuclei SDK, `master` branch(>= 0.5.0 release)
- Nuclei RISC-V GNU Toolchain 2023.10
- Nuclei QEMU 2023.10
- CMake >= 3.14
- Python 3 and pip package requirements located in
  - <nuclei-sdk>/tools/scripts/requirements.txt
  - <NMSIS>/NMSIS/Scripts/requirements.txt

3.2.2 Tool Setup

1. Export **PATH** correctly for `qemu` and `riscv64-unknown-elf-gcc`

```
export PATH=/path/to/qemu/bin:/path/to/gcc/bin:$PATH
```

3.2.3 Build NMSIS DSP Library

1. Download or clone NMSIS source code into **NMSIS** directory.
2. cd to *NMSIS/NMSIS/* directory
3. Build NMSIS DSP library and strip debug information using `make gen_dsp_lib`
4. The dsp library will be generated into `./Library/DSP/GCC` folder
5. The dsp libraries will be look like this:

```
$ ls -lhgG Library/DSP/GCC/
total 361M
-rw-rw-r-- 1 3.8M Oct 20 11:52 libnmsis_dsp_rv32imac.a
-rw-rw-r-- 1 4.0M Oct 20 11:52 libnmsis_dsp_rv32imac_xxldsp.a
-rw-rw-r-- 1 4.0M Oct 20 11:52 libnmsis_dsp_rv32imac_xxldspn1x.a
-rw-rw-r-- 1 4.0M Oct 20 11:52 libnmsis_dsp_rv32imac_xxldspn2x.a
-rw-rw-r-- 1 4.0M Oct 20 11:52 libnmsis_dsp_rv32imac_xxldspn3x.a
-rw-rw-r-- 1 3.8M Oct 20 11:52 libnmsis_dsp_rv32imac_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 4.0M Oct 20 11:52 libnmsis_dsp_rv32imac_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 4.0M Oct 20 11:52 libnmsis_dsp_rv32imac_zba_zbb_zbc_zbs_xxldspn1x.a
-rw-rw-r-- 1 4.0M Oct 20 11:52 libnmsis_dsp_rv32imac_zba_zbb_zbc_zbs_xxldspn2x.a
-rw-rw-r-- 1 4.0M Oct 20 11:52 libnmsis_dsp_rv32imac_zba_zbb_zbc_zbs_xxldspn3x.a
-rw-rw-r-- 1 3.5M Oct 20 11:52 libnmsis_dsp_rv32imafc.a
-rw-rw-r-- 1 3.7M Oct 20 11:52 libnmsis_dsp_rv32imafc_xxldsp.a
-rw-rw-r-- 1 3.7M Oct 20 11:52 libnmsis_dsp_rv32imafc_xxldspn1x.a
-rw-rw-r-- 1 3.7M Oct 20 11:52 libnmsis_dsp_rv32imafc_xxldspn2x.a
-rw-rw-r-- 1 3.7M Oct 20 11:52 libnmsis_dsp_rv32imafc_xxldspn3x.a
-rw-rw-r-- 1 3.5M Oct 20 11:52 libnmsis_dsp_rv32imafc_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 3.7M Oct 20 11:52 libnmsis_dsp_rv32imafc_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 3.7M Oct 20 11:52 libnmsis_dsp_rv32imafc_zba_zbb_zbc_zbs_xxldspn1x.a
-rw-rw-r-- 1 3.7M Oct 20 11:52 libnmsis_dsp_rv32imafc_zba_zbb_zbc_zbs_xxldspn2x.a
-rw-rw-r-- 1 3.7M Oct 20 11:52 libnmsis_dsp_rv32imafc_zba_zbb_zbc_zbs_xxldspn3x.a
-rw-rw-r-- 1 3.9M Oct 20 11:52 libnmsis_dsp_rv32imafc_zfh.a
-rw-rw-r-- 1 3.6M Oct 20 11:52 libnmsis_dsp_rv32imafc_zfh_zvfh_zve32f.a
-rw-rw-r-- 1 3.7M Oct 20 11:52 libnmsis_dsp_rv32imafc_zfh_zvfh_zve32f_xxldsp.a
-rw-rw-r-- 1 3.7M Oct 20 11:52 libnmsis_dsp_rv32imafc_zfh_zvfh_zve32f_xxldspn1x.a
-rw-rw-r-- 1 3.6M Oct 20 11:52 libnmsis_dsp_rv32imafc_zfh_zvfh_zve32f_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 3.7M Oct 20 11:52 libnmsis_dsp_rv32imafc_zfh_zvfh_zve32f_zba_zbb_zbc_zbs_
↪xxldsp.a
-rw-rw-r-- 1 3.7M Oct 20 11:52 libnmsis_dsp_rv32imafc_zfh_zvfh_zve32f_zba_zbb_zbc_zbs_
↪xxldspn1x.a
-rw-rw-r-- 1 3.2M Oct 20 11:52 libnmsis_dsp_rv32imafc_zve32f.a
-rw-rw-r-- 1 3.3M Oct 20 11:52 libnmsis_dsp_rv32imafc_zve32f_xxldsp.a
-rw-rw-r-- 1 3.3M Oct 20 11:52 libnmsis_dsp_rv32imafc_zve32f_xxldspn1x.a
-rw-rw-r-- 1 3.3M Oct 20 11:52 libnmsis_dsp_rv32imafc_zve32f_xxldspn2x.a
-rw-rw-r-- 1 3.3M Oct 20 11:52 libnmsis_dsp_rv32imafc_zve32f_xxldspn3x.a
```

(continues on next page)

(continued from previous page)

```
-rw-rw-r-- 1 3.2M Oct 20 11:52 libnmsis_dsp_rv32imafc_zve32f_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 3.3M Oct 20 11:52 libnmsis_dsp_rv32imafc_zve32f_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 3.3M Oct 20 11:52 libnmsis_dsp_rv32imafc_zve32f_zba_zbb_zbc_zbs_xxldspn1x.a
-rw-rw-r-- 1 3.3M Oct 20 11:52 libnmsis_dsp_rv32imafc_zve32f_zba_zbb_zbc_zbs_xxldspn2x.a
-rw-rw-r-- 1 3.3M Oct 20 11:52 libnmsis_dsp_rv32imafc_zve32f_zba_zbb_zbc_zbs_xxldspn3x.a
-rw-rw-r-- 1 3.5M Oct 20 11:52 libnmsis_dsp_rv32imafdc.a
-rw-rw-r-- 1 3.6M Oct 20 11:52 libnmsis_dsp_rv32imafdc_xxldsp.a
-rw-rw-r-- 1 3.6M Oct 20 11:52 libnmsis_dsp_rv32imafdc_xxldspn1x.a
-rw-rw-r-- 1 3.6M Oct 20 11:52 libnmsis_dsp_rv32imafdc_xxldspn2x.a
-rw-rw-r-- 1 3.6M Oct 20 11:52 libnmsis_dsp_rv32imafdc_xxldspn3x.a
-rw-rw-r-- 1 3.4M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 3.6M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 3.6M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zba_zbb_zbc_zbs_xxldspn1x.a
-rw-rw-r-- 1 3.7M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zba_zbb_zbc_zbs_xxldspn2x.a
-rw-rw-r-- 1 3.7M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zba_zbb_zbc_zbs_xxldspn3x.a
-rw-rw-r-- 1 3.8M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zfh.a
-rw-rw-r-- 1 3.5M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zfh_zvfh_zve32f.a
-rw-rw-r-- 1 3.6M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zfh_zvfh_zve32f_xxldsp.a
-rw-rw-r-- 1 3.6M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zfh_zvfh_zve32f_xxldspn1x.a
-rw-rw-r-- 1 3.5M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zfh_zvfh_zve32f_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 3.6M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zfh_zvfh_zve32f_zba_zbb_zbc_zbs_
↪xxldsp.a
-rw-rw-r-- 1 3.6M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zfh_zvfh_zve32f_zba_zbb_zbc_zbs_
↪xxldspn1x.a
-rw-rw-r-- 1 3.1M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zve32f.a
-rw-rw-r-- 1 3.2M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zve32f_xxldsp.a
-rw-rw-r-- 1 3.2M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zve32f_xxldspn1x.a
-rw-rw-r-- 1 3.2M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zve32f_xxldspn2x.a
-rw-rw-r-- 1 3.2M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zve32f_xxldspn3x.a
-rw-rw-r-- 1 3.1M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zve32f_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 3.2M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zve32f_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 3.2M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zve32f_zba_zbb_zbc_zbs_xxldspn1x.a
-rw-rw-r-- 1 3.2M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zve32f_zba_zbb_zbc_zbs_xxldspn2x.a
-rw-rw-r-- 1 3.3M Oct 20 11:52 libnmsis_dsp_rv32imafdc_zve32f_zba_zbb_zbc_zbs_xxldspn3x.a
-rw-rw-r-- 1 5.0M Oct 20 11:52 libnmsis_dsp_rv64imac.a
-rw-rw-r-- 1 5.4M Oct 20 11:52 libnmsis_dsp_rv64imac_xxldsp.a
-rw-rw-r-- 1 4.9M Oct 20 11:52 libnmsis_dsp_rv64imac_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 5.4M Oct 20 11:52 libnmsis_dsp_rv64imac_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 4.6M Oct 20 11:52 libnmsis_dsp_rv64imafc.a
-rw-rw-r-- 1 5.0M Oct 20 11:52 libnmsis_dsp_rv64imafc_xxldsp.a
-rw-rw-r-- 1 4.5M Oct 20 11:52 libnmsis_dsp_rv64imafc_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 5.0M Oct 20 11:52 libnmsis_dsp_rv64imafc_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 5.1M Oct 20 11:52 libnmsis_dsp_rv64imafc_zfh.a
-rw-rw-r-- 1 4.5M Oct 20 11:52 libnmsis_dsp_rv64imafc_zfh_zvfh_zve64f.a
-rw-rw-r-- 1 4.7M Oct 20 11:52 libnmsis_dsp_rv64imafc_zfh_zvfh_zve64f_xxldsp.a
-rw-rw-r-- 1 4.5M Oct 20 11:52 libnmsis_dsp_rv64imafc_zfh_zvfh_zve64f_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 4.7M Oct 20 11:52 libnmsis_dsp_rv64imafc_zfh_zvfh_zve64f_zba_zbb_zbc_zbs_
↪xxldsp.a
-rw-rw-r-- 1 4.0M Oct 20 11:52 libnmsis_dsp_rv64imafc_zve64f.a
-rw-rw-r-- 1 4.1M Oct 20 11:52 libnmsis_dsp_rv64imafc_zve64f_xxldsp.a
-rw-rw-r-- 1 4.0M Oct 20 11:52 libnmsis_dsp_rv64imafc_zve64f_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 4.1M Oct 20 11:52 libnmsis_dsp_rv64imafc_zve64f_zba_zbb_zbc_zbs_xxldsp.a
```

(continues on next page)

(continued from previous page)

```
-rw-rw-r-- 1 4.5M Oct 20 11:52 libnmsis_dsp_rv64imafdc.a
-rw-rw-r-- 1 3.9M Oct 20 11:52 libnmsis_dsp_rv64imafdcv.a
-rw-rw-r-- 1 4.1M Oct 20 11:52 libnmsis_dsp_rv64imafdcv_xxldsp.a
-rw-rw-r-- 1 3.9M Oct 20 11:52 libnmsis_dsp_rv64imafdcv_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 4.1M Oct 20 11:52 libnmsis_dsp_rv64imafdcv_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 4.5M Oct 20 11:52 libnmsis_dsp_rv64imafdcv_zfh_zvfh.a
-rw-rw-r-- 1 4.6M Oct 20 11:52 libnmsis_dsp_rv64imafdcv_zfh_zvfh_xxldsp.a
-rw-rw-r-- 1 4.4M Oct 20 11:52 libnmsis_dsp_rv64imafdcv_zfh_zvfh_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 4.6M Oct 20 11:52 libnmsis_dsp_rv64imafdcv_zfh_zvfh_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 4.9M Oct 20 11:52 libnmsis_dsp_rv64imafdc_xxldsp.a
-rw-rw-r-- 1 4.4M Oct 20 11:52 libnmsis_dsp_rv64imafdc_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 4.9M Oct 20 11:52 libnmsis_dsp_rv64imafdc_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 5.0M Oct 20 11:52 libnmsis_dsp_rv64imafdc_zfh.a
```

7. library name with extra `_xxldsp` `_xxldspn1x` `_xxldspn2x` `_xxldspn3x` is built with RISC-V DSP enabled

   The examples are as follows:

   - `libnmsis_dsp_rv32imac.a`: Build for **RISCV_ARCH=rv32imac** without DSP
   - `libnmsis_dsp_rv32imac_xxldsp.a`: Build for **RISCV_ARCH=rv32imac_xxldsp** with Nuclei DSP enabled
   - `libnmsis_dsp_rv32imac_xxldspn1x.a`: Build for **RISCV_ARCH=rv32imac_xxldspn1x** with Nuclei N1 DSP extension enabled
   - `libnmsis_dsp_rv32imac_xxldspn2x.a`: Build for **RISCV_ARCH=rv32imac_xxldspn2x** with Nuclei N1/N2 DSP extension enabled
   - `libnmsis_dsp_rv32imac_xxldspn3x.a`: Build for **RISCV_ARCH=rv32imac_xxldspn3x** with Nuclei N1/N2/N3 DSP extension enabled

8. library name with extra `_zve32f` `_zve64f` `v` is built with RISC-V Vector enabled

   The examples are as follows:

   - `libnmsis_dsp_rv32imafc_zve32f.a`: Build for **RISCV_ARCH=rv32imafc_zve32f** with Vector enabled
   - `libnmsis_dsp_rv32imafdc_zve32f.a`: Build for **RISCV_ARCH=rv32imafdc_zve32f** with Vector enabled
   - `libnmsis_dsp_rv64imafc_zve64f.a`: Build for **RISCV_ARCH=rv64imafc_zve64f** with Vector enabled
   - `libnmsis_dsp_rv64imafdcv.a`: Build for **RISCV_ARCH=rv64imafdcv** with Vector enabled

9. library name with extra `_zfh` is built for float16

   The examples are as follows:

   - `libnmsis_dsp_rv32imafc_zfh.a`: Build for **RISCV_ARCH=rv32imafc_zfh**.
   - `libnmsis_dsp_rv32imafdc_zfh_zve32f.a`: Build for **RISCV_ARCH=rv32imafdc_zfh_zve32f** with Vector enabled.
   - `libnmsis_dsp_rv64imafc_zfh_zvfh_zve64f.a`: Build for **RISCV_ARCH=rv64imafc_zfh_zvfh_zve64f** with Vector enabled.
   - `libnmsis_dsp_rv64imafdcv_zfh_zvfh.a`: Build for **RISCV_ARCH=rv64imafdcv_zfh_zvfh** with Vector enabled

Note:

- This NMSIS 1.2.0 is a big change version, will no longer support old gcc 10 verison, and it now only support Nuclei Toolchain 2023.10. The `--march` option has changed a lot, such as:
  - `b` extension changed to `_zba_zbb_zbc_zbs` extension,
  - `p` extension changed to `_xxldsp` , `_xxldspn1x` , `_xxldspn2x` , `_xxldspn3x` extensions which means stardard DSP extension, Nuclei N1, N2, N3 DSP extensions
  - `v` extension changed to `v`, `_zve32f`, `_zve64f` extensions
- The name of Libraries has changed with `-march`, for examples, the library named `libnmsis_dsp_rv32imacb.a` is now named `libnmsis_dsp_rv32imac_zba_zbb_zbc_zbs.a` since `b` extension changed to `_zba_zbb_zbc_zbs`
- `_xxldspn1x _xxldspn2x _xxldspn3x` only valid for RISC-V 32bit processor. `_xxldsp` is valid for RISC-V 32/64 bit processor
- You can also directly build both DSP and NN library using `make gen`
- DSP and Vector extension can be combined, such as `_xxldsp`, `v` and `v_xxldsp`, should notice the extension order
- Vector extension currently enabled for RISC-V 32/64 bit processor

3.2.4 How to run

1. Set environment variables `NUCLEI_SDK_ROOT` and `NUCLEI_SDK_NMSIS`, and set Nuclei SDK SoC to *evalsoc*, and change ilm/dlm size from 64K to 512K.

```
export NUCLEI_SDK_ROOT=/path/to/nuclei_sdk
export NUCLEI_SDK_NMSIS=/path/to/NMSIS/NMSIS
# Setup SDK development environment
cd $NUCLEI_SDK_ROOT
source setup.sh
cd -
# !!!!Take Care!!!!
# change this link script will make compiled example can only run on bitstream which has␣
↪512K ILM/DLM
sed -i "s/64K/512K/g" $NUCLEI_SDK_ROOT/SoC/evalsoc/Board/nuclei_fpga_eval/Source/GCC/gcc_
↪evalsoc_ilm.ld
export SOC=evalsoc
```

2. Due to many of the examples could not be placed in 64K ILM and 64K DLM, and we are running using qemu, the ILM/DLM size in it are set to be 32MB, so we can change ilm/dlm to 512K/512K in the link script `$NUCLEI_SDK_ROOT/SoC/evalsoc/Board/nuclei_fpga_eval/Source/GCC/gcc_evalsoc_ilm.ld`

```
--- a/SoC/evalsoc/Board/nuclei_fpga_eval/Source/GCC/gcc_evalsoc_ilm.ld
+++ b/SoC/evalsoc/Board/nuclei_fpga_eval/Source/GCC/gcc_evalsoc_ilm.ld
@@ -30,8 +30,8 @@ __HEAP_SIZE  = 2K;

MEMORY
{
-  ilm (rxa!w) : ORIGIN = 0x80000000, LENGTH = 64K
```

(continues on next page)

(continued from previous page)

```
-  ram (wxa!r) : ORIGIN = 0x90000000, LENGTH = 64K
+  ilm (rxa!w) : ORIGIN = 0x80000000, LENGTH = 512K
+  ram (wxa!r) : ORIGIN = 0x90000000, LENGTH = 512K
}
```

3. Let us take `riscv_class_marks_example` for example:

```
cd $NUCLEI_SDK_NMSIS/DSP/Examples/RISCV/riscv_class_marks_example
```

4. Run with RISCV DSP enabled and Vector enabled NMSIS-DSP library for CORE `nx900fd`

```
# Clean project
make ARCH_EXT=v_xxldsp CORE=nx900fd clean
# Build project, enable ``v`` and ``xxldsp`` optimize
make ARCH_EXT=v_xxldsp CORE=nx900fd all
# Run application using qemu
make ARCH_EXT=v_xxldsp CORE=nx900fd run_qemu
```

5. Run with RISCV DSP disabled and Vector disabled NMSIS-DSP library for CORE `nx900fd`

```
make ARCH_EXT= CORE=nx900fd clean
make ARCH_EXT= CORE=nx900fd all
make ARCH_EXT= CORE=nx900fd run_qemu
```

Note:

- You can easily run this example in your hardware, if you have enough memory to run it, just modify the `SOC` to the one your are using in step 1.

3.3 NMSIS DSP API

If you want to access doxygen generated NMSIS DSP API, please click NMSIS DSP API Doxygen Documentation.

3.3.1 Basic Math Functions

Vector Absolute Value

void **riscv_abs_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

void **riscv_abs_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_abs_f64**(const float64_t *pSrc, float64_t *pDst, uint32_t blockSize)

void **riscv_abs_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_abs_q31**(const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

void **riscv_abs_q7**(const q7_t *pSrc, q7_t *pDst, uint32_t blockSize) *group* **BasicAbs**

Computes the absolute value of a vector on an element-by-element basis.

The functions support in-place computation allowing the source and destination pointers to reference the same memory buffer. There are separate functions for floating-point, Q7, Q15, and Q31 data types.

Functions

void **riscv_abs_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

Floating-point vector absolute value.

Parameters

- **pSrc** – **[in]** points to the input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_abs_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Floating-point vector absolute value.

Parameters

- **pSrc** – **[in]** points to the input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_abs_f64**(const float64_t *pSrc, float64_t *pDst, uint32_t blockSize)

Floating-point vector absolute value.

Parameters

- **pSrc** – **[in]** points to the input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_abs_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

Q15 vector absolute value.

Scaling and Overflow Behavior The function uses saturating arithmetic. The Q15 value -1 (0x8000) will be saturated to the maximum allowable positive value 0x7FFF.

Parameters

- **pSrc** – **[in]** points to the input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_abs_q31**(const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

Q31 vector absolute value.

Scaling and Overflow Behavior The function uses saturating arithmetic. The Q31 value -1 (0x80000000) will be saturated to the maximum allowable positive value 0x7FFFFFFF.

Parameters

- **pSrc** – **[in]** points to the input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_abs_q7**(const q7_t *pSrc, q7_t *pDst, uint32_t blockSize)

Q7 vector absolute value.

Conditions for optimum performance Input and output buffers should be aligned by 32-bit

Scaling and Overflow Behavior The function uses saturating arithmetic. The Q7 value -1 (0x80) will be saturated to the maximum allowable positive value 0x7F.

Parameters

- **pSrc** – **[in]** points to the input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Vector Addition

void **riscv_add_f16**(const float16_t *pSrcA, const float16_t *pSrcB, float16_t *pDst, uint32_t blockSize)

void **riscv_add_f32**(const float32_t *pSrcA, const float32_t *pSrcB, float32_t *pDst, uint32_t blockSize)

void **riscv_add_f64**(const float64_t *pSrcA, const float64_t *pSrcB, float64_t *pDst, uint32_t blockSize)

void **riscv_add_q15**(const q15_t *pSrcA, const q15_t *pSrcB, q15_t *pDst, uint32_t blockSize)

void **riscv_add_q31**(const q31_t *pSrcA, const q31_t *pSrcB, q31_t *pDst, uint32_t blockSize)

void **riscv_add_q7**(const q7_t *pSrcA, const q7_t *pSrcB, q7_t *pDst, uint32_t blockSize)

group **BasicAdd**

Element-by-element addition of two vectors.

There are separate functions for floating-point, Q7, Q15, and Q31 data types.

Functions

void **riscv_add_f16**(const float16_t *pSrcA, const float16_t *pSrcB, float16_t *pDst, uint32_t blockSize)

Floating-point vector addition.

Parameters

- **pSrcA** – **[in]** points to first input vector
- **pSrcB** – **[in]** points to second input vector
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_add_f32**(const float32_t *pSrcA, const float32_t *pSrcB, float32_t *pDst, uint32_t blockSize)

Floating-point vector addition.

Parameters

- **pSrcA** – **[in]** points to first input vector
- **pSrcB** – **[in]** points to second input vector
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_add_f64**(const float64_t *pSrcA, const float64_t *pSrcB, float64_t *pDst, uint32_t blockSize)

Floating-point vector addition.

Parameters

- **pSrcA** – **[in]** points to first input vector
- **pSrcB** – **[in]** points to second input vector
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_add_q15**(const q15_t *pSrcA, const q15_t *pSrcB, q15_t *pDst, uint32_t blockSize)

Q15 vector addition.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q15 range [0x8000 0x7FFF] are saturated.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_add_q31**(const q31_t *pSrcA, const q31_t *pSrcB, q31_t *pDst, uint32_t blockSize)

Q31 vector addition.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q31 range [0x80000000 0x7FFFFFFF] are saturated.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_add_q7**(const q7_t *pSrcA, const q7_t *pSrcB, q7_t *pDst, uint32_t blockSize)

Q7 vector addition.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q7 range [0x80 0x7F] are saturated.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Vector bitwise AND

void **riscv_and_u16**(const uint16_t *pSrcA, const uint16_t *pSrcB, uint16_t *pDst, uint32_t blockSize)

void **riscv_and_u32**(const uint32_t *pSrcA, const uint32_t *pSrcB, uint32_t *pDst, uint32_t blockSize)

void **riscv_and_u8**(const uint8_t *pSrcA, const uint8_t *pSrcB, uint8_t *pDst, uint32_t blockSize)

group **And**

Compute the logical bitwise AND.

There are separate functions for uint32_t, uint16_t, and uint7_t data types.

Functions

void **riscv_and_u16**(const uint16_t *pSrcA, const uint16_t *pSrcB, uint16_t *pDst, uint32_t blockSize)

Compute the logical bitwise AND of two fixed-point vectors.

Parameters

- **pSrcA** – **[in]** points to input vector A
- **pSrcB** – **[in]** points to input vector B
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_and_u32**(const uint32_t *pSrcA, const uint32_t *pSrcB, uint32_t *pDst, uint32_t blockSize)

Compute the logical bitwise AND of two fixed-point vectors.

Parameters

- **pSrcA** – **[in]** points to input vector A
- **pSrcB** – **[in]** points to input vector B
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_and_u8**(const uint8_t *pSrcA, const uint8_t *pSrcB, uint8_t *pDst, uint32_t blockSize)

Compute the logical bitwise AND of two fixed-point vectors.

Parameters

- **pSrcA** – **[in]** points to input vector A
- **pSrcB** – **[in]** points to input vector B
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Elementwise clipping

void **riscv_clip_f16**(const float16_t *pSrc, float16_t *pDst, float16_t low, float16_t high, uint32_t numSamples)

void **riscv_clip_f32**(const float32_t *pSrc, float32_t *pDst, float32_t low, float32_t high, uint32_t numSamples)

void **riscv_clip_q15**(const q15_t *pSrc, q15_t *pDst, q15_t low, q15_t high, uint32_t numSamples)

void **riscv_clip_q31**(const q31_t *pSrc, q31_t *pDst, q31_t low, q31_t high, uint32_t numSamples)

void **riscv_clip_q7**(const q7_t *pSrc, q7_t *pDst, q7_t low, q7_t high, uint32_t numSamples) *group* `BasicClip`

Element-by-element clipping of a value.

The value is constrained between 2 bounds.

There are separate functions for floating-point, Q7, Q15, and Q31 data types.

Functions

void **riscv_clip_f16**(const float16_t *pSrc, float16_t *pDst, float16_t low, float16_t high, uint32_t numSamples)

Elementwise floating-point clipping.

Parameters

- **pSrc** – **[in]** points to input values
- **pDst** – **[out]** points to output clipped values
- **low** – **[in]** lower bound
- **high** – **[in]** higher bound
- **numSamples** – **[in]** number of samples to clip

Returns none

void **riscv_clip_f32**(const float32_t *pSrc, float32_t *pDst, float32_t low, float32_t high, uint32_t numSamples)

Elementwise floating-point clipping.

Parameters

- **pSrc** – **[in]** points to input values
- **pDst** – **[out]** points to output clipped values
- **low** – **[in]** lower bound
- **high** – **[in]** higher bound
- **numSamples** – **[in]** number of samples to clip

Returns none

void **riscv_clip_q15**(const q15_t *pSrc, q15_t *pDst, q15_t low, q15_t high, uint32_t numSamples)

Elementwise fixed-point clipping.

Parameters

- **pSrc** – **[in]** points to input values
- **pDst** – **[out]** points to output clipped values
- **low** – **[in]** lower bound
- **high** – **[in]** higher bound
- **numSamples** – **[in]** number of samples to clip

Returns none

void **riscv_clip_q31**(const q31_t *pSrc, q31_t *pDst, q31_t low, q31_t high, uint32_t numSamples)

Elementwise fixed-point clipping.

Parameters

- **pSrc** – **[in]** points to input values
- **pDst** – **[out]** points to output clipped values
- **low** – **[in]** lower bound
- **high** – **[in]** higher bound
- **numSamples** – **[in]** number of samples to clip

Returns none

void **riscv_clip_q7**(const q7_t *pSrc, q7_t *pDst, q7_t low, q7_t high, uint32_t numSamples)

Elementwise fixed-point clipping.

Parameters

- **pSrc** – **[in]** points to input values
- **pDst** – **[out]** points to output clipped values
- **low** – **[in]** lower bound
- **high** – **[in]** higher bound
- **numSamples** – **[in]** number of samples to clip

Returns none

Vector Dot Product

void **riscv_dot_prod_f16**(const float16_t *pSrcA, const float16_t *pSrcB, uint32_t blockSize, float16_t *result)

void **riscv_dot_prod_f32**(const float32_t *pSrcA, const float32_t *pSrcB, uint32_t blockSize, float32_t *result)

void **riscv_dot_prod_f64**(const float64_t *pSrcA, const float64_t *pSrcB, uint32_t blockSize, float64_t *result)

void **riscv_dot_prod_q15**(const q15_t *pSrcA, const q15_t *pSrcB, uint32_t blockSize, q63_t *result)

void **riscv_dot_prod_q31**(const q31_t *pSrcA, const q31_t *pSrcB, uint32_t blockSize, q63_t *result)

void **riscv_dot_prod_q7**(const q7_t *pSrcA, const q7_t *pSrcB, uint32_t blockSize, q31_t *result)

group **BasicDotProd**

Computes the dot product of two vectors. The vectors are multiplied element-by-element and then summed.

There are separate functions for floating-point, Q7, Q15, and Q31 data types.

Functions

void **riscv_dot_prod_f16**(const float16_t *pSrcA, const float16_t *pSrcB, uint32_t blockSize, float16_t *result)

Dot product of floating-point vectors.

Parameters

- **pSrcA** – **[in]** points to the first input vector.
- **pSrcB** – **[in]** points to the second input vector.
- **blockSize** – **[in]** number of samples in each vector.
- **result** – **[out]** output result returned here.

Returns none

void **riscv_dot_prod_f32**(const float32_t *pSrcA, const float32_t *pSrcB, uint32_t blockSize, float32_t *result)

Dot product of floating-point vectors.

Parameters

- **pSrcA** – **[in]** points to the first input vector.
- **pSrcB** – **[in]** points to the second input vector.
- **blockSize** – **[in]** number of samples in each vector.
- **result** – **[out]** output result returned here.

Returns none

void **riscv_dot_prod_f64**(const float64_t *pSrcA, const float64_t *pSrcB, uint32_t blockSize, float64_t *result)

Dot product of floating-point vectors.

Parameters

- **pSrcA** – **[in]** points to the first input vector.
- **pSrcB** – **[in]** points to the second input vector.
- **blockSize** – **[in]** number of samples in each vector.
- **result** – **[out]** output result returned here.

Returns none

void **riscv_dot_prod_q15**(const q15_t *pSrcA, const q15_t *pSrcB, uint32_t blockSize, q63_t *result)

Dot product of Q15 vectors.

Scaling and Overflow Behavior The intermediate multiplications are in 1.15 x 1.15 = 2.30 format and these results are added to a 64-bit accumulator in 34.30 format. Nonsaturating additions are used and given that there are 33 guard bits in the accumulator there is no risk of overflow. The return result is in 34.30 format.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector

- **blockSize** – **[in]** number of samples in each vector
- **result** – **[out]** output result returned here

Returns none

void **riscv_dot_prod_q31**(const q31_t *pSrcA, const q31_t *pSrcB, uint32_t blockSize, q63_t *result)

Dot product of Q31 vectors.

Scaling and Overflow Behavior The intermediate multiplications are in 1.31 x 1.31 = 2.62 format and these are truncated to 2.48 format by discarding the lower 14 bits. The 2.48 result is then added without saturation to a 64-bit accumulator in 16.48 format. There are 15 guard bits in the accumulator and there is no risk of overflow as long as the length of the vectors is less than 2^16 elements. The return result is in 16.48 format.

Parameters

- **pSrcA** – **[in]** points to the first input vector.
- **pSrcB** – **[in]** points to the second input vector.
- **blockSize** – **[in]** number of samples in each vector.
- **result** – **[out]** output result returned here.

Returns none

void **riscv_dot_prod_q7**(const q7_t *pSrcA, const q7_t *pSrcB, uint32_t blockSize, q31_t *result)

Dot product of Q7 vectors.

Scaling and Overflow Behavior The intermediate multiplications are in 1.7 x 1.7 = 2.14 format and these results are added to an accumulator in 18.14 format. Nonsaturating additions are used and there is no danger of wrap around as long as the vectors are less than 2^18 elements long. The return result is in 18.14 format.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **blockSize** – **[in]** number of samples in each vector
- **result** – **[out]** output result returned here

Returns none

Vector Multiplication

void **riscv_mult_f16**(const float16_t *pSrcA, const float16_t *pSrcB, float16_t *pDst, uint32_t blockSize)

void **riscv_mult_f32**(const float32_t *pSrcA, const float32_t *pSrcB, float32_t *pDst, uint32_t blockSize)

void **riscv_mult_f64**(const float64_t *pSrcA, const float64_t *pSrcB, float64_t *pDst, uint32_t blockSize)

void **riscv_mult_q15**(const q15_t *pSrcA, const q15_t *pSrcB, q15_t *pDst, uint32_t blockSize) void **riscv_mult_q31**(const q31_t *pSrcA, const q31_t *pSrcB, q31_t *pDst, uint32_t blockSize)

void **riscv_mult_q7**(const q7_t *pSrcA, const q7_t *pSrcB, q7_t *pDst, uint32_t blockSize)

group **BasicMult**

Element-by-element multiplication of two vectors.

There are separate functions for floating-point, Q7, Q15, and Q31 data types.

Functions

void **riscv_mult_f16**(const float16_t *pSrcA, const float16_t *pSrcB, float16_t *pDst, uint32_t blockSize)

Floating-point vector multiplication.

Parameters

- **pSrcA** – **[in]** points to the first input vector.
- **pSrcB** – **[in]** points to the second input vector.
- **pDst** – **[out]** points to the output vector.
- **blockSize** – **[in]** number of samples in each vector.

Returns none

void **riscv_mult_f32**(const float32_t *pSrcA, const float32_t *pSrcB, float32_t *pDst, uint32_t blockSize)

Floating-point vector multiplication.

Parameters

- **pSrcA** – **[in]** points to the first input vector.
- **pSrcB** – **[in]** points to the second input vector.
- **pDst** – **[out]** points to the output vector.
- **blockSize** – **[in]** number of samples in each vector.

Returns none

void **riscv_mult_f64**(const float64_t *pSrcA, const float64_t *pSrcB, float64_t *pDst, uint32_t blockSize)

Floating-point vector multiplication.

Parameters

- **pSrcA** – **[in]** points to the first input vector.
- **pSrcB** – **[in]** points to the second input vector.
- **pDst** – **[out]** points to the output vector.
- **blockSize** – **[in]** number of samples in each vector.

Returns none

void **riscv_mult_q15**(const q15_t *pSrcA, const q15_t *pSrcB, q15_t *pDst, uint32_t blockSize)

Q15 vector multiplication.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q15 range [0x8000 0x7FFF] are saturated.

Parameters

- **pSrcA** – **[in]** points to first input vector
- **pSrcB** – **[in]** points to second input vector
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_mult_q31**(const q31_t *pSrcA, const q31_t *pSrcB, q31_t *pDst, uint32_t blockSize)

Q31 vector multiplication.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q31 range[0x80000000 0x7FFFFFFF] are saturated.

Parameters

- **pSrcA** – **[in]** points to the first input vector.
- **pSrcB** – **[in]** points to the second input vector.
- **pDst** – **[out]** points to the output vector.
- **blockSize** – **[in]** number of samples in each vector.

Returns none

void **riscv_mult_q7**(const q7_t *pSrcA, const q7_t *pSrcB, q7_t *pDst, uint32_t blockSize)

Q7 vector multiplication.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q7 range [0x80 0x7F] are saturated.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Vector Negate

void **riscv_negate_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

void **riscv_negate_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_negate_f64**(const float64_t *pSrc, float64_t *pDst, uint32_t blockSize)

void **riscv_negate_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t blockSize) void **riscv_negate_q31**(const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

void **riscv_negate_q7**(const q7_t *pSrc, q7_t *pDst, uint32_t blockSize)

group **BasicNegate**

Negates the elements of a vector.

The functions support in-place computation allowing the source and destination pointers to reference the same memory buffer. There are separate functions for floating-point, Q7, Q15, and Q31 data types.

Functions

void **riscv_negate_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

Negates the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to input vector.
- **pDst** – **[out]** points to output vector.
- **blockSize** – **[in]** number of samples in each vector.

Returns none

void **riscv_negate_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Negates the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to input vector.
- **pDst** – **[out]** points to output vector.
- **blockSize** – **[in]** number of samples in each vector.

Returns none

void **riscv_negate_f64**(const float64_t *pSrc, float64_t *pDst, uint32_t blockSize)

Negates the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to input vector.
- **pDst** – **[out]** points to output vector.
- **blockSize** – **[in]** number of samples in each vector.

Returns none

void **riscv_negate_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

Negates the elements of a Q15 vector.

Conditions for optimum performance Input and output buffers should be aligned by 32-bit

Scaling and Overflow Behavior The function uses saturating arithmetic. The Q15 value -1 (0x8000) is saturated to the maximum allowable positive value 0x7FFF.

Parameters

- **pSrc** – **[in]** points to the input vector.
- **pDst** – **[out]** points to the output vector.
- **blockSize** – **[in]** number of samples in each vector.

Returns none

void **riscv_negate_q31**(const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

Negates the elements of a Q31 vector.

Scaling and Overflow Behavior The function uses saturating arithmetic. The Q31 value -1 (0x80000000) is saturated to the maximum allowable positive value 0x7FFFFFFF.

Parameters

- **pSrc** – **[in]** points to the input vector.
- **pDst** – **[out]** points to the output vector.
- **blockSize** – **[in]** number of samples in each vector.

Returns none

void **riscv_negate_q7**(const q7_t *pSrc, q7_t *pDst, uint32_t blockSize)

Negates the elements of a Q7 vector.

Scaling and Overflow Behavior The function uses saturating arithmetic. The Q7 value -1 (0x80) is saturated to the maximum allowable positive value 0x7F.

Parameters

- **pSrc** – **[in]** points to the input vector.
- **pDst** – **[out]** points to the output vector.
- **blockSize** – **[in]** number of samples in each vector.

Returns none

Vector bitwise NOT

void **riscv_not_u16**(const uint16_t *pSrc, uint16_t *pDst, uint32_t blockSize)

void **riscv_not_u32**(const uint32_t *pSrc, uint32_t *pDst, uint32_t blockSize)

void **riscv_not_u8**(const uint8_t *pSrc, uint8_t *pDst, uint32_t blockSize)

group **Not**

Compute the logical bitwise NOT.

There are separate functions for uint32_t, uint16_t, and uint8_t data types.

Functions

void **riscv_not_u16**(const uint16_t *pSrc, uint16_t *pDst, uint32_t blockSize)

Compute the logical bitwise NOT of a fixed-point vector.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_not_u32**(const uint32_t *pSrc, uint32_t *pDst, uint32_t blockSize)

Compute the logical bitwise NOT of a fixed-point vector.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_not_u8**(const uint8_t *pSrc, uint8_t *pDst, uint32_t blockSize)

Compute the logical bitwise NOT of a fixed-point vector.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Vector Offset

void **riscv_offset_f16**(const float16_t *pSrc, float16_t offset, float16_t *pDst, uint32_t blockSize)

void **riscv_offset_f32**(const float32_t *pSrc, float32_t offset, float32_t *pDst, uint32_t blockSize)

void **riscv_offset_f64**(const float64_t *pSrc, float64_t offset, float64_t *pDst, uint32_t blockSize)

void **riscv_offset_q15**(const q15_t *pSrc, q15_t offset, q15_t *pDst, uint32_t blockSize)

void **riscv_offset_q31**(const q31_t *pSrc, q31_t offset, q31_t *pDst, uint32_t blockSize)

void **riscv_offset_q7**(const q7_t *pSrc, q7_t offset, q7_t *pDst, uint32_t blockSize)

group **BasicOffset**

Adds a constant offset to each element of a vector.

The functions support in-place computation allowing the source and destination pointers to reference the same memory buffer. There are separate functions for floating-point, Q7, Q15, and Q31 data types.

Functions

void **riscv_offset_f16**(const float16_t *pSrc, float16_t offset, float16_t *pDst, uint32_t blockSize)

Adds a constant offset to a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **offset** – **[in]** is the offset to be added
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_offset_f32**(const float32_t *pSrc, float32_t offset, float32_t *pDst, uint32_t blockSize)

Adds a constant offset to a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **offset** – **[in]** is the offset to be added
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_offset_f64**(const float64_t *pSrc, float64_t offset, float64_t *pDst, uint32_t blockSize)

Adds a constant offset to a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **offset** – **[in]** is the offset to be added
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_offset_q15**(const q15_t *pSrc, q15_t offset, q15_t *pDst, uint32_t blockSize)

Adds a constant offset to a Q15 vector.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q15 range [0x8000 0x7FFF] are saturated.

Parameters

- **pSrc** – **[in]** points to the input vector
- **offset** – **[in]** is the offset to be added
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_offset_q31**(const q31_t *pSrc, q31_t offset, q31_t *pDst, uint32_t blockSize)

Adds a constant offset to a Q31 vector.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q31 range [0x80000000 0x7FFFFFFF] are saturated.

Parameters

- **pSrc** – **[in]** points to the input vector
- **offset** – **[in]** is the offset to be added
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_offset_q7**(const q7_t *pSrc, q7_t offset, q7_t *pDst, uint32_t blockSize)

Adds a constant offset to a Q7 vector.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q7 range [0x80 0x7F] are saturated.

Parameters

- **pSrc** – **[in]** points to the input vector
- **offset** – **[in]** is the offset to be added
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Vector bitwise inclusive OR

void **riscv_or_u16**(const uint16_t *pSrcA, const uint16_t *pSrcB, uint16_t *pDst, uint32_t blockSize)

void **riscv_or_u32**(const uint32_t *pSrcA, const uint32_t *pSrcB, uint32_t *pDst, uint32_t blockSize)

void **riscv_or_u8**(const uint8_t *pSrcA, const uint8_t *pSrcB, uint8_t *pDst, uint32_t blockSize)

group **Or**

Compute the logical bitwise OR.

There are separate functions for uint32_t, uint16_t, and uint8_t data types.

Functions

void **riscv_or_u16**(const uint16_t *pSrcA, const uint16_t *pSrcB, uint16_t *pDst, uint32_t blockSize)

Compute the logical bitwise OR of two fixed-point vectors.

Parameters

- **pSrcA** – **[in]** points to input vector A
- **pSrcB** – **[in]** points to input vector B
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_or_u32**(const uint32_t *pSrcA, const uint32_t *pSrcB, uint32_t *pDst, uint32_t blockSize)

Compute the logical bitwise OR of two fixed-point vectors.

Parameters

- **pSrcA** – **[in]** points to input vector A
- **pSrcB** – **[in]** points to input vector B
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_or_u8**(const uint8_t *pSrcA, const uint8_t *pSrcB, uint8_t *pDst, uint32_t blockSize)

Compute the logical bitwise OR of two fixed-point vectors.

Parameters

- **pSrcA** – **[in]** points to input vector A
- **pSrcB** – **[in]** points to input vector B
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Vector Scale

void **riscv_scale_f16**(const float16_t *pSrc, float16_t scale, float16_t *pDst, uint32_t blockSize)

void **riscv_scale_f32**(const float32_t *pSrc, float32_t scale, float32_t *pDst, uint32_t blockSize)

void **riscv_scale_f64**(const float64_t *pSrc, float64_t scale, float64_t *pDst, uint32_t blockSize)

void **riscv_scale_q15**(const q15_t *pSrc, q15_t scaleFract, int8_t shift, q15_t *pDst, uint32_t blockSize)

void **riscv_scale_q31**(const q31_t *pSrc, q31_t scaleFract, int8_t shift, q31_t *pDst, uint32_t blockSize)

void **riscv_scale_q7**(const q7_t *pSrc, q7_t scaleFract, int8_t shift, q7_t *pDst, uint32_t blockSize) *group* `BasicScale`

Multiply a vector by a scalar value. For floating-point data, the algorithm used is:

In the fixed-point Q7, Q15, and Q31 functions, `scale` is represented by a fractional multiplication `scaleFract` and an arithmetic shift `shift`. The shift allows the gain of the scaling operation to exceed 1.0. The algorithm used with fixed-point data is:

The overall scale factor applied to the fixed-point data is

The functions support in-place computation allowing the source and destination pointers to reference the same memory buffer.

Functions

void **riscv_scale_f16**(const float16_t *pSrc, float16_t scale, float16_t *pDst, uint32_t blockSize)

Multiplies a floating-point vector by a scalar.

Parameters

- **pSrc** – **[in]** points to the input vector
- **scale** – **[in]** scale factor to be applied
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_scale_f32**(const float32_t *pSrc, float32_t scale, float32_t *pDst, uint32_t blockSize)

Multiplies a floating-point vector by a scalar.

Parameters

- **pSrc** – **[in]** points to the input vector
- **scale** – **[in]** scale factor to be applied
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_scale_f64**(const float64_t *pSrc, float64_t scale, float64_t *pDst, uint32_t blockSize)

Multiplies a floating-point vector by a scalar.

Parameters

- **pSrc** – **[in]** points to the input vector
- **scale** – **[in]** scale factor to be applied
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_scale_q15**(const q15_t *pSrc, q15_t scaleFract, int8_t shift, q15_t *pDst, uint32_t blockSize)

Multiplies a Q15 vector by a scalar.

Scaling and Overflow Behavior The input data `*pSrc` and `scaleFract` are in 1.15 format. These are multiplied to yield a 2.30 intermediate result and this is shifted with saturation to 1.15 format.

Parameters

- **`pSrc`** – **[in]** points to the input vector
- **`scaleFract`** – **[in]** fractional portion of the scale value
- **`shift`** – **[in]** number of bits to shift the result by
- **`pDst`** – **[out]** points to the output vector
- **`blockSize`** – **[in]** number of samples in each vector

Returns none

void **`riscv_scale_q31`**(const q31_t *pSrc, q31_t scaleFract, int8_t shift, q31_t *pDst, uint32_t blockSize)

Multiplies a Q31 vector by a scalar.

Scaling and Overflow Behavior The input data `*pSrc` and `scaleFract` are in 1.31 format. These are multiplied to yield a 2.62 intermediate result and this is shifted with saturation to 1.31 format. There is an intermediate shift by 32 to go from the 2.62 to 1.31 format. The shift argument is applied on the 1.31 result and not to the intermediate 2.62 format.

Parameters

- **`pSrc`** – **[in]** points to the input vector
- **`scaleFract`** – **[in]** fractional portion of the scale value
- **`shift`** – **[in]** number of bits to shift the result by
- **`pDst`** – **[out]** points to the output vector
- **`blockSize`** – **[in]** number of samples in each vector

Returns none

void **`riscv_scale_q7`**(const q7_t *pSrc, q7_t scaleFract, int8_t shift, q7_t *pDst, uint32_t blockSize)

Multiplies a Q7 vector by a scalar.

Scaling and Overflow Behavior The input data `*pSrc` and `scaleFract` are in 1.7 format. These are multiplied to yield a 2.14 intermediate result and this is shifted with saturation to 1.7 format.

Parameters

- **`pSrc`** – **[in]** points to the input vector
- **`scaleFract`** – **[in]** fractional portion of the scale value
- **`shift`** – **[in]** number of bits to shift the result by
- **`pDst`** – **[out]** points to the output vector
- **`blockSize`** – **[in]** number of samples in each vector

Returns none

Vector Shift

void **riscv_shift_q15**(const q15_t *pSrc, int8_t shiftBits, q15_t *pDst, uint32_t blockSize)

void **riscv_shift_q31**(const q31_t *pSrc, int8_t shiftBits, q31_t *pDst, uint32_t blockSize)

void **riscv_shift_q7**(const q7_t *pSrc, int8_t shiftBits, q7_t *pDst, uint32_t blockSize)

group `BasicShift`

Shifts the elements of a fixed-point vector by a specified number of bits. There are separate functions for Q7, Q15, and Q31 data types. The underlying algorithm used is:

If `shift` is positive then the elements of the vector are shifted to the left. If `shift` is negative then the elements of the vector are shifted to the right.

The functions support in-place computation allowing the source and destination pointers to reference the same memory buffer.

Functions

void **riscv_shift_q15**(const q15_t *pSrc, int8_t shiftBits, q15_t *pDst, uint32_t blockSize)

Shifts the elements of a Q15 vector a specified number of bits.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q15 range [0x8000 0x7FFF] are saturated.

Parameters

- **pSrc** – **[in]** points to the input vector
- **shiftBits** – **[in]** number of bits to shift. A positive value shifts left; a negative value shifts right.
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_shift_q31**(const q31_t *pSrc, int8_t shiftBits, q31_t *pDst, uint32_t blockSize)

Shifts the elements of a Q31 vector a specified number of bits.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q31 range [0x80000000 0x7FFFFFFF] are saturated.

Parameters

- **pSrc** – **[in]** points to the input vector
- **shiftBits** – **[in]** number of bits to shift. A positive value shifts left; a negative value shifts right.
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in the vector

Returns none

void **riscv_shift_q7**(const q7_t *pSrc, int8_t shiftBits, q7_t *pDst, uint32_t blockSize)

Shifts the elements of a Q7 vector a specified number of bits.

onditions for optimum performance Input and output buffers should be aligned by 32-bit

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q7 range [0x80 0x7F] are saturated.

Parameters

- **pSrc** – **[in]** points to the input vector
- **shiftBits** – **[in]** number of bits to shift. A positive value shifts left; a negative value shifts right.
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Vector Subtraction

void **riscv_sub_f16**(const float16_t *pSrcA, const float16_t *pSrcB, float16_t *pDst, uint32_t blockSize)

void **riscv_sub_f32**(const float32_t *pSrcA, const float32_t *pSrcB, float32_t *pDst, uint32_t blockSize)

void **riscv_sub_f64**(const float64_t *pSrcA, const float64_t *pSrcB, float64_t *pDst, uint32_t blockSize)

void **riscv_sub_q15**(const q15_t *pSrcA, const q15_t *pSrcB, q15_t *pDst, uint32_t blockSize)

void **riscv_sub_q31**(const q31_t *pSrcA, const q31_t *pSrcB, q31_t *pDst, uint32_t blockSize)

void **riscv_sub_q7**(const q7_t *pSrcA, const q7_t *pSrcB, q7_t *pDst, uint32_t blockSize)

group **BasicSub**

Element-by-element subtraction of two vectors.

There are separate functions for floating-point, Q7, Q15, and Q31 data types.

Functions

void **riscv_sub_f16**(const float16_t *pSrcA, const float16_t *pSrcB, float16_t *pDst, uint32_t blockSize)

Floating-point vector subtraction.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void `riscv_sub_f32`(const float32_t *pSrcA, const float32_t *pSrcB, float32_t *pDst, uint32_t blockSize)

Floating-point vector subtraction.

Parameters

- `pSrcA` – **[in]** points to the first input vector
- `pSrcB` – **[in]** points to the second input vector
- `pDst` – **[out]** points to the output vector
- `blockSize` – **[in]** number of samples in each vector

Returns none

void `riscv_sub_f64`(const float64_t *pSrcA, const float64_t *pSrcB, float64_t *pDst, uint32_t blockSize)

Floating-point vector subtraction.

Parameters

- `pSrcA` – **[in]** points to the first input vector
- `pSrcB` – **[in]** points to the second input vector
- `pDst` – **[out]** points to the output vector
- `blockSize` – **[in]** number of samples in each vector

Returns none

void `riscv_sub_q15`(const q15_t *pSrcA, const q15_t *pSrcB, q15_t *pDst, uint32_t blockSize)

Q15 vector subtraction.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q15 range [0x8000 0x7FFF] are saturated.

Parameters

- `pSrcA` – **[in]** points to the first input vector
- `pSrcB` – **[in]** points to the second input vector
- `pDst` – **[out]** points to the output vector
- `blockSize` – **[in]** number of samples in each vector

Returns none

void `riscv_sub_q31`(const q31_t *pSrcA, const q31_t *pSrcB, q31_t *pDst, uint32_t blockSize)

Q31 vector subtraction.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q31 range [0x80000000 0x7FFFFFFF] are saturated.

Parameters

- `pSrcA` – **[in]** points to the first input vector
- `pSrcB` – **[in]** points to the second input vector
- `pDst` – **[out]** points to the output vector

- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_sub_q7**(const q7_t *pSrcA, const q7_t *pSrcB, q7_t *pDst, uint32_t blockSize)

Q7 vector subtraction.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q7 range [0x80 0x7F] will be saturated.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Vector bitwise exclusive OR

void **riscv_xor_u16**(const uint16_t *pSrcA, const uint16_t *pSrcB, uint16_t *pDst, uint32_t blockSize)

void **riscv_xor_u32**(const uint32_t *pSrcA, const uint32_t *pSrcB, uint32_t *pDst, uint32_t blockSize)

void **riscv_xor_u8**(const uint8_t *pSrcA, const uint8_t *pSrcB, uint8_t *pDst, uint32_t blockSize)

group **Xor**

Compute the logical bitwise XOR.

There are separate functions for uint32_t, uint16_t, and uint8_t data types.

Functions

void **riscv_xor_u16**(const uint16_t *pSrcA, const uint16_t *pSrcB, uint16_t *pDst, uint32_t blockSize)

Compute the logical bitwise XOR of two fixed-point vectors.

Parameters

- **pSrcA** – **[in]** points to input vector A
- **pSrcB** – **[in]** points to input vector B
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_xor_u32**(const uint32_t *pSrcA, const uint32_t *pSrcB, uint32_t *pDst, uint32_t blockSize)

Compute the logical bitwise XOR of two fixed-point vectors.

Parameters

- **pSrcA** – **[in]** points to input vector A

- **pSrcB** – **[in]** points to input vector B
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_xor_u8**(const uint8_t *pSrcA, const uint8_t *pSrcB, uint8_t *pDst, uint32_t blockSize)

Compute the logical bitwise XOR of two fixed-point vectors.

Parameters

- **pSrcA** – **[in]** points to input vector A
- **pSrcB** – **[in]** points to input vector B
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

group **groupMath**

3.3.2 Bayesian estimators

uint32_t **riscv_gaussian_naive_bayes_predict_f16**(const riscv_gaussian_naive_bayes_instance_f16 *S, const float16_t *in, float16_t *pOutputProbabilities, float16_t *pBufferB)

uint32_t **riscv_gaussian_naive_bayes_predict_f32**(const riscv_gaussian_naive_bayes_instance_f32 *S, const float32_t *in, float32_t *pOutputProbabilities, float32_t *pBufferB)

group **groupBayes**

Implement the naive gaussian Bayes estimator. The training must be done from scikit-learn.

The parameters can be easily generated from the scikit-learn object. Some examples are given in DSP/Testing/PatternGeneration/Bayes.py

Functions

uint32_t **riscv_gaussian_naive_bayes_predict_f16**(const riscv_gaussian_naive_bayes_instance_f16 *S, const float16_t *in, float16_t *pOutputProbabilities, float16_t *pBufferB)

Naive Gaussian Bayesian Estimator.

Parameters

- ***S** – **[in]** points to a naive bayes instance structure
- ***in** – **[in]** points to the elements of the input vector.
- ***pOutputProbabilities** – **[out]** points to a buffer of length numberOfClasses containing estimated probabilities
- ***pBufferB** – **[out]** points to a temporary buffer of length numberOfClasses

Returns The predicted class

uint32_t **riscv_gaussian_naive_bayes_predict_f32**(const riscv_gaussian_naive_bayes_instance_f32 *S, const float32_t *in, float32_t *pOutputProbabilities, float32_t *pBufferB)

Naive Gaussian Bayesian Estimator.

Parameters

- ***S** – **[in]** points to a naive bayes instance structure
- ***in** – **[in]** points to the elements of the input vector.
- ***pOutputProbabilities** – **[out]** points to a buffer of length numberOfClasses containing estimated probabilities
- ***pBufferB** – **[out]** points to a temporary buffer of length numberOfClasses

Returns The predicted class

3.3.3 Complex Math Functions

Complex Conjugate

void **riscv_cmplx_conj_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t numSamples)

void **riscv_cmplx_conj_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t numSamples)

void **riscv_cmplx_conj_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t numSamples)

void **riscv_cmplx_conj_q31**(const q31_t *pSrc, q31_t *pDst, uint32_t numSamples)

group **cmplx_conj**

Conjugates the elements of a complex data vector.

The `pSrc` points to the source data and `pDst` points to the destination data where the result should be written. `numSamples` specifies the number of complex samples and the data in each array is stored in an interleaved fashion (real, imag, real, imag, …). Each array has a total of `2*numSamples` values.

The underlying algorithm is used:

There are separate functions for floating-point, Q15, and Q31 data types.

Functions

void **riscv_cmplx_conj_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t numSamples)

Floating-point complex conjugate.

Parameters

- **pSrc** – **[in]** points to the input vector
- **pDst** – **[out]** points to the output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_conj_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t numSamples)

Floating-point complex conjugate.

Parameters

- **pSrc** – **[in]** points to the input vector
- **pDst** – **[out]** points to the output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_conj_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t numSamples)

Q15 complex conjugate.

Scaling and Overflow Behavior The function uses saturating arithmetic. The Q15 value -1 (0x8000) is saturated to the maximum allowable positive value 0x7FFF.

Parameters

- **pSrc** – **[in]** points to the input vector
- **pDst** – **[out]** points to the output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_conj_q31**(const q31_t *pSrc, q31_t *pDst, uint32_t numSamples)

Q31 complex conjugate.

Scaling and Overflow Behavior The function uses saturating arithmetic. The Q31 value -1 (0x80000000) is saturated to the maximum allowable positive value 0x7FFFFFFF.

Parameters

- **pSrc** – **[in]** points to the input vector
- **pDst** – **[out]** points to the output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

Complex Dot Product

void **riscv_cmplx_dot_prod_f16**(const float16_t *pSrcA, const float16_t *pSrcB, uint32_t numSamples, float16_t *realResult, float16_t *imagResult)

void **riscv_cmplx_dot_prod_f32**(const float32_t *pSrcA, const float32_t *pSrcB, uint32_t numSamples, float32_t *realResult, float32_t *imagResult)

void **riscv_cmplx_dot_prod_q15**(const q15_t *pSrcA, const q15_t *pSrcB, uint32_t numSamples, q31_t *realResult, q31_t *imagResult) void **riscv_cmplx_dot_prod_q31**(const q31_t *pSrcA, const q31_t *pSrcB, uint32_t numSamples, q63_t *realResult, q63_t *imagResult)

group **cmplx_dot_prod**

Computes the dot product of two complex vectors. The vectors are multiplied element-by-element and then summed.

The `pSrcA` points to the first complex input vector and `pSrcB` points to the second complex input vector. `numSamples` specifies the number of complex samples and the data in each array is stored in an interleaved fashion (real, imag, real, imag, . . .). Each array has a total of `2*numSamples` values.

The underlying algorithm is used:

There are separate functions for floating-point, Q15, and Q31 data types.

Functions

void **riscv_cmplx_dot_prod_f16**(const float16_t *pSrcA, const float16_t *pSrcB, uint32_t numSamples, float16_t *realResult, float16_t *imagResult)

Floating-point complex dot product.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **numSamples** – **[in]** number of samples in each vector
- **realResult** – **[out]** real part of the result returned here
- **imagResult** – **[out]** imaginary part of the result returned here

Returns none

void **riscv_cmplx_dot_prod_f32**(const float32_t *pSrcA, const float32_t *pSrcB, uint32_t numSamples, float32_t *realResult, float32_t *imagResult)

Floating-point complex dot product.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **numSamples** – **[in]** number of samples in each vector
- **realResult** – **[out]** real part of the result returned here
- **imagResult** – **[out]** imaginary part of the result returned here

Returns none

void **riscv_cmplx_dot_prod_q15**(const q15_t *pSrcA, const q15_t *pSrcB, uint32_t numSamples, q31_t *realResult, q31_t *imagResult)

Q15 complex dot product.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The intermediate 1.15 by 1.15 multiplications are performed with full precision and yield a 2.30 result.

These are accumulated in a 64-bit accumulator with 34.30 precision. As a final step, the accumulators are converted to 8.24 format. The return results `realResult` and `imagResult` are in 8.24 format.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **numSamples** – **[in]** number of samples in each vector
- **realResult** – **[out]** real part of the result returned here
- **imagResult** – **[out]** imaginary part of the result returned her

Returns none

void **riscv_cmplx_dot_prod_q31**(const q31_t *pSrcA, const q31_t *pSrcB, uint32_t numSamples, q63_t *realResult, q63_t *imagResult)

Q31 complex dot product.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The intermediate 1.31 by 1.31 multiplications are performed with 64-bit precision and then shifted to 16.48 format. The internal real and imaginary accumulators are in 16.48 format and provide 15 guard bits. Additions are nonsaturating and no overflow will occur as long as `numSamples` is less than 32768. The return results `realResult` and `imagResult` are in 16.48 format. Input down scaling is not required.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **numSamples** – **[in]** number of samples in each vector
- **realResult** – **[out]** real part of the result returned here
- **imagResult** – **[out]** imaginary part of the result returned here

Returns none

Complex Magnitude

void **riscv_cmplx_mag_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t numSamples)

void **riscv_cmplx_mag_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t numSamples)

void **riscv_cmplx_mag_f64**(const float64_t *pSrc, float64_t *pDst, uint32_t numSamples)

void **riscv_cmplx_mag_fast_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t numSamples)

void **riscv_cmplx_mag_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t numSamples)

void **riscv_cmplx_mag_q31**(const q31_t *pSrc, q31_t *pDst, uint32_t numSamples) *group* `cmplx_mag`

Computes the magnitude of the elements of a complex data vector.

The `pSrc` points to the source data and `pDst` points to the where the result should be written. `numSamples` specifies the number of complex samples in the input array and the data is stored in an interleaved fashion (real, imag, real, imag, …). The input array has a total of `2*numSamples` values; the output array has a total of `numSamples` values.

The underlying algorithm is used:

There are separate functions for floating-point, Q15, and Q31 data types.

Functions

void **riscv_cmplx_mag_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t numSamples)

Floating-point complex magnitude.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mag_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t numSamples)

Floating-point complex magnitude.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mag_f64**(const float64_t *pSrc, float64_t *pDst, uint32_t numSamples)

Floating-point complex magnitude.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mag_fast_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t numSamples)

Q15 complex magnitude.

Scaling and Overflow Behavior The function implements 1.15 by 1.15 multiplications and finally output is converted into 2.14 format. Fast functions are less accurate. This function will tend to clamp to 0 the too small values. So sqrt(x*x) = x will not always be true.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mag_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t numSamples)

Q15 complex magnitude.

Scaling and Overflow Behavior The function implements 1.15 by 1.15 multiplications and finally output is converted into 2.14 format.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mag_q31**(const q31_t *pSrc, q31_t *pDst, uint32_t numSamples)

Q31 complex magnitude.

Scaling and Overflow Behavior The function implements 1.31 by 1.31 multiplications and finally output is converted into 2.30 format. Input down scaling is not required.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

Complex Magnitude Squared

void **riscv_cmplx_mag_squared_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t numSamples)

void **riscv_cmplx_mag_squared_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t numSamples)

void **riscv_cmplx_mag_squared_f64**(const float64_t *pSrc, float64_t *pDst, uint32_t numSamples)

void **riscv_cmplx_mag_squared_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t numSamples)

void **riscv_cmplx_mag_squared_q31**(const q31_t *pSrc, q31_t *pDst, uint32_t numSamples) *group* `cmplx_mag_squared`

Computes the magnitude squared of the elements of a complex data vector.

The `pSrc` points to the source data and `pDst` points to the where the result should be written. `numSamples` specifies the number of complex samples in the input array and the data is stored in an interleaved fashion (real, imag, real, imag, …). The input array has a total of `2*numSamples` values; the output array has a total of `numSamples` values.

The underlying algorithm is used:

There are separate functions for floating-point, Q15, and Q31 data types.

Functions

void **riscv_cmplx_mag_squared_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t numSamples)

Floating-point complex magnitude squared.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mag_squared_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t numSamples)

Floating-point complex magnitude squared.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mag_squared_f64**(const float64_t *pSrc, float64_t *pDst, uint32_t numSamples)

Floating-point complex magnitude squared.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mag_squared_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t numSamples)

Q15 complex magnitude squared.

Scaling and Overflow Behavior The function implements 1.15 by 1.15 multiplications and finally output is converted into 3.13 format.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mag_squared_q31**(const q31_t *pSrc, q31_t *pDst, uint32_t numSamples)

Q31 complex magnitude squared.

Scaling and Overflow Behavior The function implements 1.31 by 1.31 multiplications and finally output is converted into 3.29 format. Input down scaling is not required.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

Complex-by-Complex Multiplication

void **riscv_cmplx_mult_cmplx_f16**(const float16_t *pSrcA, const float16_t *pSrcB, float16_t *pDst, uint32_t numSamples)

void **riscv_cmplx_mult_cmplx_f32**(const float32_t *pSrcA, const float32_t *pSrcB, float32_t *pDst, uint32_t numSamples)

void **riscv_cmplx_mult_cmplx_f64**(const float64_t *pSrcA, const float64_t *pSrcB, float64_t *pDst, uint32_t numSamples)

void **riscv_cmplx_mult_cmplx_q15**(const q15_t *pSrcA, const q15_t *pSrcB, q15_t *pDst, uint32_t numSamples)

void **riscv_cmplx_mult_cmplx_q31**(const q31_t *pSrcA, const q31_t *pSrcB, q31_t *pDst, uint32_t numSamples)

group **CmplxByCmplxMult**

Multiplies a complex vector by another complex vector and generates a complex result. The data in the complex arrays is stored in an interleaved fashion (real, imag, real, imag, …). The parameter `numSamples` represents the number of complex samples processed. The complex arrays have a total of `2*numSamples` real values.

The underlying algorithm is used:

There are separate functions for floating-point, Q15, and Q31 data types.

Functions

void **riscv_cmplx_mult_cmplx_f16**(const float16_t *pSrcA, const float16_t *pSrcB, float16_t *pDst, uint32_t numSamples)

Floating-point complex-by-complex multiplication.

Parameters

- **pSrcA** – **[in]** points to first input vector
- **pSrcB** – **[in]** points to second input vector
- **pDst** – **[out]** points to output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mult_cmplx_f32**(const float32_t *pSrcA, const float32_t *pSrcB, float32_t *pDst, uint32_t numSamples)

Floating-point complex-by-complex multiplication.

Parameters

- **pSrcA** – **[in]** points to first input vector
- **pSrcB** – **[in]** points to second input vector
- **pDst** – **[out]** points to output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mult_cmplx_f64**(const float64_t *pSrcA, const float64_t *pSrcB, float64_t *pDst, uint32_t numSamples)

Floating-point complex-by-complex multiplication.

Parameters

- **pSrcA** – **[in]** points to first input vector
- **pSrcB** – **[in]** points to second input vector
- **pDst** – **[out]** points to output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mult_cmplx_q15**(const q15_t *pSrcA, const q15_t *pSrcB, q15_t *pDst, uint32_t numSamples)

Q15 complex-by-complex multiplication.

Scaling and Overflow Behavior The function implements 1.15 by 1.15 multiplications and finally output is converted into 3.13 format.

Parameters

- **pSrcA** – **[in]** points to first input vector
- **pSrcB** – **[in]** points to second input vector
- **pDst** – **[out]** points to output vector

- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mult_cmplx_q31**(const q31_t *pSrcA, const q31_t *pSrcB, q31_t *pDst, uint32_t numSamples)

Q31 complex-by-complex multiplication.

Scaling and Overflow Behavior The function implements 1.31 by 1.31 multiplications and finally output is converted into 3.29 format. Input down scaling is not required.

Parameters

- **pSrcA** – **[in]** points to first input vector
- **pSrcB** – **[in]** points to second input vector
- **pDst** – **[out]** points to output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

Complex-by-Real Multiplication

void **riscv_cmplx_mult_real_f16**(const float16_t *pSrcCmplx, const float16_t *pSrcReal, float16_t *pCmplxDst, uint32_t numSamples)

void **riscv_cmplx_mult_real_f32**(const float32_t *pSrcCmplx, const float32_t *pSrcReal, float32_t *pCmplxDst, uint32_t numSamples)

void **riscv_cmplx_mult_real_q15**(const q15_t *pSrcCmplx, const q15_t *pSrcReal, q15_t *pCmplxDst, uint32_t numSamples)

void **riscv_cmplx_mult_real_q31**(const q31_t *pSrcCmplx, const q31_t *pSrcReal, q31_t *pCmplxDst, uint32_t numSamples)

group **CmplxByRealMult**

Multiplies a complex vector by a real vector and generates a complex result. The data in the complex arrays is stored in an interleaved fashion (real, imag, real, imag, …). The parameter `numSamples` represents the number of complex samples processed. The complex arrays have a total of `2*numSamples` real values while the real array has a total of `numSamples` real values.

The underlying algorithm is used:

There are separate functions for floating-point, Q15, and Q31 data types.

Functions

void **riscv_cmplx_mult_real_f16**(const float16_t *pSrcCmplx, const float16_t *pSrcReal, float16_t *pCmplxDst, uint32_t numSamples)

Floating-point complex-by-real multiplication.

Parameters

- **pSrcCmplx** – **[in]** points to complex input vector
- **pSrcReal** – **[in]** points to real input vector
- **pCmplxDst** – **[out]** points to complex output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mult_real_f32**(const float32_t *pSrcCmplx, const float32_t *pSrcReal, float32_t *pCmplxDst, uint32_t numSamples)

Floating-point complex-by-real multiplication.

Parameters

- **pSrcCmplx** – **[in]** points to complex input vector
- **pSrcReal** – **[in]** points to real input vector
- **pCmplxDst** – **[out]** points to complex output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mult_real_q15**(const q15_t *pSrcCmplx, const q15_t *pSrcReal, q15_t *pCmplxDst, uint32_t numSamples)

Q15 complex-by-real multiplication.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q15 range [0x8000 0x7FFF] are saturated.

Parameters

- **pSrcCmplx** – **[in]** points to complex input vector
- **pSrcReal** – **[in]** points to real input vector
- **pCmplxDst** – **[out]** points to complex output vector
- **numSamples** – **[in]** number of samples in each vector

Returns none

void **riscv_cmplx_mult_real_q31**(const q31_t *pSrcCmplx, const q31_t *pSrcReal, q31_t *pCmplxDst, uint32_t numSamples)

Q31 complex-by-real multiplication.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q31 range[0x80000000 0x7FFFFFFF] are saturated.

Parameters

- `pSrcCmplx` – **[in]** points to complex input vector
- `pSrcReal` – **[in]** points to real input vector
- `pCmplxDst` – **[out]** points to complex output vector
- `numSamples` – **[in]** number of samples in each vector

Returns none

group `groupCmplxMath`

This set of functions operates on complex data vectors. The data in the complex arrays is stored in an interleaved fashion (real, imag, real, imag, . . .). In the API functions, the number of samples in a complex array refers to the number of complex values; the array contains twice this number of real values.

3.3.4 Controller Functions

Sine Cosine

void **riscv_sin_cos_f32**(float32_t theta, float32_t *pSinVal, float32_t *pCosVal)

void **riscv_sin_cos_q31**(q31_t theta, q31_t *pSinVal, q31_t *pCosVal)

group `SinCos`

Computes the trigonometric sine and cosine values using a combination of table lookup and linear interpolation. There are separate functions for Q31 and floating-point data types. The input to the floating-point version is in degrees while the fixed-point Q31 have a scaled input with the range [-1 0.9999] mapping to [-180 +180] degrees.

The floating point function also allows values that are out of the usual range. When this happens, the function will take extra time to adjust the input value to the range of [-180 180].

The result is accurate to 5 digits after the decimal point.

The implementation is based on table lookup using 360 values together with linear interpolation. The steps used are:

1. Calculation of the nearest integer table index.
2. Compute the fractional portion (fract) of the input.
3. Fetch the value corresponding to `index` from sine table to `y0` and also value from `index+1` to `y1`.
4. Sine value is computed as `*psinVal = y0 + (fract * (y1 - y0))`.
5. Fetch the value corresponding to `index` from cosine table to `y0` and also value from `index+1` to `y1`.
6. Cosine value is computed as `*pcosVal = y0 + (fract * (y1 - y0))`.

Functions

void **riscv_sin_cos_f32**(float32_t theta, float32_t *pSinVal, float32_t *pCosVal)

Floating-point sin_cos function.

Parameters

- **theta** – **[in]** input value in degrees
- **pSinVal** – **[out]** points to processed sine output
- **pCosVal** – **[out]** points to processed cosine output

Returns none

void **riscv_sin_cos_q31**(q31_t theta, q31_t *pSinVal, q31_t *pCosVal)

Q31 sin_cos function.

The Q31 input value is in the range [-1 0.999999] and is mapped to a degree value in the range [-180 179].

Parameters

- **theta** – **[in]** scaled input value in degrees
- **pSinVal** – **[out]** points to processed sine output
- **pCosVal** – **[out]** points to processed cosine output

Returns none

PID Motor Control

__STATIC_FORCEINLINE float32_t riscv_pid_f32 (riscv_pid_instance_f32 *S, float32_t in)

__STATIC_FORCEINLINE q31_t riscv_pid_q31 (riscv_pid_instance_q31 *S, q31_t in)

__STATIC_FORCEINLINE q15_t riscv_pid_q15 (riscv_pid_instance_q15 *S, q15_t in)

void **riscv_pid_init_f32**(*riscv_pid_instance_f32* (page 682) *S, int32_t resetStateFlag)

void **riscv_pid_init_q15**(*riscv_pid_instance_q15* (page 682) *S, int32_t resetStateFlag)

void **riscv_pid_init_q31**(*riscv_pid_instance_q31* (page 682) *S, int32_t resetStateFlag)

void **riscv_pid_reset_f32**(*riscv_pid_instance_f32* (page 682) *S)

void **riscv_pid_reset_q15**(*riscv_pid_instance_q15* (page 682) *S)

void **riscv_pid_reset_q31**(*riscv_pid_instance_q31* (page 682) *S)

struct **riscv_pid_instance_q15**

struct **riscv_pid_instance_q31**

struct **riscv_pid_instance_f32**

group **PID**

A Proportional Integral Derivative (PID) controller is a generic feedback control loop mechanism widely used in industrial control systems. A PID controller is the most commonly used type of feedback controller.

This set of functions implements (PID) controllers for Q15, Q31, and floating-point data types. The functions operate on a single sample of data and each call to the function returns a single processed value. `S` points to an instance of the PID control data structure. `in` is the input sample value. The functions return the output value.

Algorithm:

where `Kp` is proportional constant, `Ki` is Integral constant and `Kd` is Derivative constant



The PID controller calculates an "error" value as the difference between the measured output and the reference input. The controller attempts to minimize the error by adjusting the process control inputs. The proportional value determines the reaction to the current error, the integral value determines the reaction based on the sum of recent errors, and the derivative value determines the reaction based on the rate at which the error has been changing.

Instance Structure The Gains A0, A1, A2 and state variables for a PID controller are stored together in an instance data structure. A separate instance structure must be defined for each PID Controller. There are separate instance structure declarations for each of the 3 supported data types.

Reset Functions There is also an associated reset function for each data type which clears the state array.

Initialization Functions There is also an associated initialization function for each data type. The initialization function performs the following operations:

- Initializes the Gains A0, A1, A2 from Kp,Ki, Kd gains.
- Zeros out the values in the state buffer.

Instance structure cannot be placed into a const data section and it is recommended to use the initialization function.

Fixed-Point Behavior Care must be taken when using the fixed-point versions of the PID Controller functions. In particular, the overflow and saturation behavior of the accumulator used in each function must be considered. Refer to the function specific documentation below for usage guidelines.

Functions

__STATIC_FORCEINLINE float32_t riscv_pid_f32 (riscv_pid_instance_f32 *S, float32_t in)

Process function for the floating-point PID Control.

Parameters

- **S** – **[inout]** is an instance of the floating-point PID Control structure
- **in** – **[in]** input sample to process

Returns processed output sample.

__STATIC_FORCEINLINE q31_t riscv_pid_q31 (riscv_pid_instance_q31 *S, q31_t in)

Process function for the Q31 PID Control.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The accumulator has a 2.62 format and maintains full precision of the intermediate multiplication results but provides only a single guard bit. Thus, if the accumulator result overflows it wraps around rather than clip. In order to avoid overflows completely the input signal must be scaled down by 2 bits as there are four additions. After all multiply-accumulates are performed, the 2.62 accumulator is truncated to 1.32 format and then saturated to 1.31 format.

Parameters

- **S** – **[inout]** points to an instance of the Q31 PID Control structure
- **in** – **[in]** input sample to process

Returns processed output sample.

__STATIC_FORCEINLINE q15_t riscv_pid_q15 (riscv_pid_instance_q15 *S, q15_t in)

Process function for the Q15 PID Control.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. Both Gains and state variables are represented in 1.15 format and multiplications yield a 2.30 result. The 2.30 intermediate results are accumulated in a 64-bit accumulator in 34.30 format. There is no risk of internal overflow with this approach and the full precision of intermediate multiplications is preserved. After all additions have been performed, the accumulator is truncated to 34.15 format by discarding low 15 bits. Lastly, the accumulator is saturated to yield a result in 1.15 format.

Parameters

- **S** – **[inout]** points to an instance of the Q15 PID Control structure
- **in** – **[in]** input sample to process

Returns processed output sample.

void **riscv_pid_init_f32**(*riscv_pid_instance_f32* (page 682) *S, int32_t resetStateFlag)

Initialization function for the floating-point PID Control.

Details The `resetStateFlag` specifies whether to set state to zero or not.

The function computes the structure fields: `A0`, `A1` `A2` using the proportional gain(`Kp`), integral gain(`Ki`) and derivative gain(`Kd`) also sets the state variables to all zeros.

Parameters

- `S` – **[inout]** points to an instance of the PID structure
- `resetStateFlag` – **[in]**
  - value = 0: no change in state
  - value = 1: reset state

Returns none

void **riscv_pid_init_q15**(*riscv_pid_instance_q15* (page 682) *S, int32_t resetStateFlag)

Initialization function for the Q15 PID Control.

Details The `resetStateFlag` specifies whether to set state to zero or not.

The function computes the structure fields: `A0`, `A1` `A2` using the proportional gain(`Kp`), integral gain(`Ki`) and derivative gain(`Kd`) also sets the state variables to all zeros.

Parameters

- `S` – **[inout]** points to an instance of the Q15 PID structure
- `resetStateFlag` – **[in]**
  - value = 0: no change in state
  - value = 1: reset state

Returns none

void **riscv_pid_init_q31**(*riscv_pid_instance_q31* (page 682) *S, int32_t resetStateFlag)

Initialization function for the Q31 PID Control.

Details The `resetStateFlag` specifies whether to set state to zero or not.

The function computes the structure fields: `A0`, `A1` `A2` using the proportional gain(`Kp`), integral gain(`Ki`) and derivative gain(`Kd`) also sets the state variables to all zeros.

Parameters

- `S` – **[inout]** points to an instance of the Q31 PID structure
- `resetStateFlag` – **[in]**
  - value = 0: no change in state
  - value = 1: reset state

Returns none

void **riscv_pid_reset_f32**(*riscv_pid_instance_f32* (page 682) *S)

Reset function for the floating-point PID Control.

Details The function resets the state buffer to zeros.

Parameters S – **[inout]** points to an instance of the floating-point PID structure

Returns none

void **riscv_pid_reset_q15**(*riscv_pid_instance_q15* (page 682) *S)

Reset function for the Q15 PID Control.

Details The function resets the state buffer to zeros.

Parameters S – **[inout]** points to an instance of the Q15 PID structure

Returns none

void **riscv_pid_reset_q31**(*riscv_pid_instance_q31* (page 682) *S)

Reset function for the Q31 PID Control.

Details The function resets the state buffer to zeros.

Parameters S – **[inout]** points to an instance of the Q31 PID structure

Returns none

struct **riscv_pid_instance_q15**

#include <> Instance structure for the Q15 PID Control.

struct **riscv_pid_instance_q31**

#include <> Instance structure for the Q31 PID Control.

struct **riscv_pid_instance_f32**

#include <> Instance structure for the floating-point PID Control.

Vector Park Transform

__STATIC_FORCEINLINE void riscv_park_f32 (float32_t Ialpha, float32_t Ibeta, float32_t *pId, float32_t *pIq, float32_t sinVal, float32_t cosVal)

__STATIC_FORCEINLINE void riscv_park_q31 (q31_t Ialpha, q31_t Ibeta, q31_t *pId, q31_t *pIq, q31_t sinVal, q31_t cosVal)

group **park**

Forward Park transform converts the input two-coordinate vector to flux and torque components. The Park transform can be used to realize the transformation of the `Ialpha` and the `Ibeta` currents from the stationary to the moving reference frame and control the spatial relationship between the stator vector current and rotor flux vector. If we consider the d axis aligned with the rotor flux, the diagram below shows the current vector and the relationship from the two reference frames:



The function operates on a single sample of data and each call to the function returns the processed output. The library provides separate functions for Q31 and floating-point data types.

Algorithm

where `Ialpha` and `Ibeta` are the stator vector components, `pId` and `pIq` are rotor vector components and `cosVal` and `sinVal` are the cosine and sine values of theta (rotor flux position).

$$\begin{aligned} \text{pId} &= \text{Ialpha} * \text{cosVal} + \text{Ibeta} * \text{sinVal} \\ \text{pIq} &= -\ \text{Ialpha sinVal} + \text{Ibeta} * \text{cosVal} \end{aligned}$$

Fixed-Point Behavior Care must be taken when using the Q31 version of the Park transform. In particular, the overflow and saturation behavior of the accumulator used must be considered. Refer to the function specific documentation below for usage guidelines.

Functions

`__STATIC_FORCEINLINE void riscv_park_f32 (float32_t Ialpha, float32_t Ibeta, float32_t *pId, float32_t *pIq, float32_t sinVal, float32_t cosVal)`

Floating-point Park transform.

The function implements the forward Park transform.

Parameters

- **`Ialpha`** – **[in]** input two-phase vector coordinate alpha
- **`Ibeta`** – **[in]** input two-phase vector coordinate beta
- **`pId`** – **[out]** points to output rotor reference frame d
- **`pIq`** – **[out]** points to output rotor reference frame q
- **`sinVal`** – **[in]** sine value of rotation angle theta

- **cosVal** – **[in]** cosine value of rotation angle theta

Returns none

__STATIC_FORCEINLINE void riscv_park_q31 (q31_t Ialpha, q31_t Ibeta, q31_t *pId, q31_t *pIq, q31_t sinVal, q31_t cosVal)

Park transform for Q31 version.

Scaling and Overflow Behavior The function is implemented using an internal 32-bit accumulator. The accumulator maintains 1.31 format by truncating lower 31 bits of the intermediate multiplication in 2.62 format. There is saturation on the addition and subtraction, hence there is no risk of overflow.

Parameters

- **Ialpha** – **[in]** input two-phase vector coordinate alpha
- **Ibeta** – **[in]** input two-phase vector coordinate beta
- **pId** – **[out]** points to output rotor reference frame d
- **pIq** – **[out]** points to output rotor reference frame q
- **sinVal** – **[in]** sine value of rotation angle theta
- **cosVal** – **[in]** cosine value of rotation angle theta

Returns none

Vector Inverse Park transform

__STATIC_FORCEINLINE void riscv_inv_park_f32 (float32_t Id, float32_t Iq, float32_t *pIalpha, float32_t *pIbeta, float32_t sinVal, float32_t cosVal)

__STATIC_FORCEINLINE void riscv_inv_park_q31 (q31_t Id, q31_t Iq, q31_t *pIalpha, q31_t *pIbeta, q31_t sinVal, q31_t cosVal)

group **inv_park**

Inverse Park transform converts the input flux and torque components to two-coordinate vector.

The function operates on a single sample of data and each call to the function returns the processed output. The library provides separate functions for Q31 and floating-point data types.

Algorithm

where `pIalpha` and `pIbeta` are the stator vector components, `Id` and `Iq` are rotor vector components and `cosVal` and `sinVal` are the cosine and sine values of theta (rotor flux position).

$$pIalpha = Id * cosVal - Iq * sinVal$$
$$pIbeta = Id * sinVal + Iq * cosVal$$

Fixed-Point Behavior Care must be taken when using the Q31 version of the Park transform. In particular, the overflow and saturation behavior of the accumulator used must be considered. Refer to the function specific documentation below for usage guidelines.

Functions

__STATIC_FORCEINLINE void riscv_inv_park_f32 (float32_t Id, float32_t Iq, float32_t *pIalpha, float32_t *pIbeta, float32_t sinVal, float32_t cosVal)

Floating-point Inverse Park transform.

Parameters

- **Id** – **[in]** input coordinate of rotor reference frame d
- **Iq** – **[in]** input coordinate of rotor reference frame q
- **pIalpha** – **[out]** points to output two-phase orthogonal vector axis alpha
- **pIbeta** – **[out]** points to output two-phase orthogonal vector axis beta
- **sinVal** – **[in]** sine value of rotation angle theta
- **cosVal** – **[in]** cosine value of rotation angle theta

Returns none

__STATIC_FORCEINLINE void riscv_inv_park_q31 (q31_t Id, q31_t Iq, q31_t *pIalpha, q31_t *pIbeta, q31_t sinVal, q31_t cosVal)

Inverse Park transform for Q31 version.

Scaling and Overflow Behavior The function is implemented using an internal 32-bit accumulator. The accumulator maintains 1.31 format by truncating lower 31 bits of the intermediate multiplication in 2.62 format. There is saturation on the addition, hence there is no risk of overflow.

Parameters

- **Id** – **[in]** input coordinate of rotor reference frame d
- **Iq** – **[in]** input coordinate of rotor reference frame q
- **pIalpha** – **[out]** points to output two-phase orthogonal vector axis alpha
- **pIbeta** – **[out]** points to output two-phase orthogonal vector axis beta
- **sinVal** – **[in]** sine value of rotation angle theta
- **cosVal** – **[in]** cosine value of rotation angle theta

Returns none

Vector Clarke Transform

__STATIC_FORCEINLINE void riscv_clarke_f32 (float32_t Ia, float32_t Ib, float32_t *pIalpha, float32_t *pIbeta)

__STATIC_FORCEINLINE void riscv_clarke_q31 (q31_t Ia, q31_t Ib, q31_t *pIalpha, q31_t *pIbeta)

group **clarke**

Forward Clarke transform converts the instantaneous stator phases into a two-coordinate time invariant vector. Generally the Clarke transform uses three-phase currents `Ia, Ib and Ic` to calculate currents in the two-phase orthogonal stator axis `Ialpha` and `Ibeta`. When `Ialpha` is superposed with `Ia` as shown in the figure below.

and `Ia + Ib + Ic = 0`, in this condition `Ialpha` and `Ibeta` can be calculated using only `Ia` and



`Ib`.

The function operates on a single sample of data and each call to the function returns the processed output. The library provides separate functions for Q31 and floating-point data types.

Algorithm

where `Ia` and `Ib` are the instantaneous stator phases and `pIalpha` and `pIbeta` are the two coordinates of

$$\mathrm{pIalpha} = \mathrm{Ia}$$

$$\mathrm{pIbeta} = (1/\sqrt{3})\,\mathrm{Ia} + (2/\sqrt{3})\,\mathrm{Ib}$$

time invariant vector.

Fixed-Point Behavior Care must be taken when using the Q31 version of the Clarke transform. In particular, the overflow and saturation behavior of the accumulator used must be considered. Refer to the function specific documentation below for usage guidelines.

Functions

`__STATIC_FORCEINLINE void riscv_clarke_f32 (float32_t Ia, float32_t Ib, float32_t *pIalpha, float32_t *pIbeta)`

Floating-point Clarke transform.

Parameters

- **`Ia`** – **[in]** input three-phase coordinate a
- **`Ib`** – **[in]** input three-phase coordinate b
- **`pIalpha`** – **[out]** points to output two-phase orthogonal vector axis alpha

- **pIbeta** – **[out]** points to output two-phase orthogonal vector axis beta

Returns none

__STATIC_FORCEINLINE void riscv_clarke_q31 (q31_t Ia, q31_t Ib, q31_t *pIalpha, q31_t *pIbeta)

Clarke transform for Q31 version.

Scaling and Overflow Behavior The function is implemented using an internal 32-bit accumulator. The accumulator maintains 1.31 format by truncating lower 31 bits of the intermediate multiplication in 2.62 format. There is saturation on the addition, hence there is no risk of overflow.

Parameters

- **Ia** – **[in]** input three-phase coordinate a
- **Ib** – **[in]** input three-phase coordinate b
- **pIalpha** – **[out]** points to output two-phase orthogonal vector axis alpha
- **pIbeta** – **[out]** points to output two-phase orthogonal vector axis beta

Returns none

Vector Inverse Clarke Transform

__STATIC_FORCEINLINE void riscv_inv_clarke_f32 (float32_t Ialpha, float32_t Ibeta, float32_t *pIa, float32_t *pIb)

__STATIC_FORCEINLINE void riscv_inv_clarke_q31 (q31_t Ialpha, q31_t Ibeta, q31_t *pIa, q31_t *pIb)

group **inv_clarke**

Inverse Clarke transform converts the two-coordinate time invariant vector into instantaneous stator phases.

The function operates on a single sample of data and each call to the function returns the processed output. The library provides separate functions for Q31 and floating-point data types.

Algorithm

where `pIa` and `pIb` are the instantaneous stator phases and `Ialpha` and `Ibeta` are the two coordinates of

$$\mathrm{pIa} = \mathrm{Ialpha}$$

$$\mathrm{pIb} = (-1/2)\,\mathrm{Ialpha} + (\sqrt{3}/2)\,\mathrm{Ibeta}$$

time invariant vector.

Fixed-Point Behavior Care must be taken when using the Q31 version of the Clarke transform. In particular, the overflow and saturation behavior of the accumulator used must be considered. Refer to the function specific documentation below for usage guidelines.

Functions

__STATIC_FORCEINLINE void riscv_inv_clarke_f32 (float32_t Ialpha, float32_t Ibeta, float32_t *pIa, float32_t *pIb)

Floating-point Inverse Clarke transform.

Parameters

- **Ialpha** – **[in]** input two-phase orthogonal vector axis alpha
- **Ibeta** – **[in]** input two-phase orthogonal vector axis beta
- **pIa** – **[out]** points to output three-phase coordinate a
- **pIb** – **[out]** points to output three-phase coordinate b

Returns none

__STATIC_FORCEINLINE void riscv_inv_clarke_q31 (q31_t Ialpha, q31_t Ibeta, q31_t *pIa, q31_t *pIb)

Inverse Clarke transform for Q31 version.

Scaling and Overflow Behavior The function is implemented using an internal 32-bit accumulator. The accumulator maintains 1.31 format by truncating lower 31 bits of the intermediate multiplication in 2.62 format. There is saturation on the subtraction, hence there is no risk of overflow.

Parameters

- **Ialpha** – **[in]** input two-phase orthogonal vector axis alpha
- **Ibeta** – **[in]** input two-phase orthogonal vector axis beta
- **pIa** – **[out]** points to output three-phase coordinate a
- **pIb** – **[out]** points to output three-phase coordinate b

Returns none

group **groupController**

3.3.5 Distance functions

Float Distances

Bray-Curtis distance

float16_t **riscv_braycurtis_distance_f16**(const float16_t *pA, const float16_t *pB, uint32_t blockSize)

float32_t **riscv_braycurtis_distance_f32**(const float32_t *pA, const float32_t *pB, uint32_t blockSize)

group **braycurtis**

Bray-Curtis distance between two vectors.

Functions

float16_t **riscv_braycurtis_distance_f16**(const float16_t *pA, const float16_t *pB, uint32_t blockSize)

Bray-Curtis distance between two vectors.

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

float32_t **riscv_braycurtis_distance_f32**(const float32_t *pA, const float32_t *pB, uint32_t blockSize)

Bray-Curtis distance between two vectors.

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

Canberra distance

float16_t **riscv_canberra_distance_f16**(const float16_t *pA, const float16_t *pB, uint32_t blockSize)

float32_t **riscv_canberra_distance_f32**(const float32_t *pA, const float32_t *pB, uint32_t blockSize)

group **Canberra**

Canberra distance.

Functions

float16_t **riscv_canberra_distance_f16**(const float16_t *pA, const float16_t *pB, uint32_t blockSize)

Canberra distance between two vectors.

This function may divide by zero when samples pA[i] and pB[i] are both zero. The result of the computation will be correct. So the division per zero may be ignored.

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

float32_t **riscv_canberra_distance_f32**(const float32_t *pA, const float32_t *pB, uint32_t blockSize)

Canberra distance between two vectors.

This function may divide by zero when samples pA[i] and pB[i] are both zero. The result of the computation will be correct. So the division per zero may be ignored.

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

Chebyshev distance

float16_t **riscv_chebyshev_distance_f16**(const float16_t *pA, const float16_t *pB, uint32_t blockSize)

float32_t **riscv_chebyshev_distance_f32**(const float32_t *pA, const float32_t *pB, uint32_t blockSize)

float64_t **riscv_chebyshev_distance_f64**(const float64_t *pA, const float64_t *pB, uint32_t blockSize)

group **Chebyshev**

Chebyshev distance.

Functions

float16_t **riscv_chebyshev_distance_f16**(const float16_t *pA, const float16_t *pB, uint32_t blockSize)

Chebyshev distance between two vectors.

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

float32_t **riscv_chebyshev_distance_f32**(const float32_t *pA, const float32_t *pB, uint32_t blockSize)

Chebyshev distance between two vectors.

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

float64_t **riscv_chebyshev_distance_f64**(const float64_t *pA, const float64_t *pB, uint32_t blockSize)

Chebyshev distance between two vectors.

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

Cityblock (Manhattan) distance

float16_t **riscv_cityblock_distance_f16**(const float16_t *pA, const float16_t *pB, uint32_t blockSize)

float32_t **riscv_cityblock_distance_f32**(const float32_t *pA, const float32_t *pB, uint32_t blockSize)

float64_t **riscv_cityblock_distance_f64**(const float64_t *pA, const float64_t *pB, uint32_t blockSize)

group **Manhattan**

Cityblock (Manhattan) distance.

Functions

float16_t **riscv_cityblock_distance_f16**(const float16_t *pA, const float16_t *pB, uint32_t blockSize)

Cityblock (Manhattan) distance between two vectors.

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

float32_t **riscv_cityblock_distance_f32**(const float32_t *pA, const float32_t *pB, uint32_t blockSize)

Cityblock (Manhattan) distance between two vectors.

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

float64_t **riscv_cityblock_distance_f64**(const float64_t *pA, const float64_t *pB, uint32_t blockSize)

Cityblock (Manhattan) distance between two vectors.

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

Correlation distance

float16_t **riscv_correlation_distance_f16**(float16_t *pA, float16_t *pB, uint32_t blockSize)

float32_t **riscv_correlation_distance_f32**(float32_t *pA, float32_t *pB, uint32_t blockSize)

group **Correlation**

Correlation distance.

Functions

float16_t **riscv_correlation_distance_f16**(float16_t *pA, float16_t *pB, uint32_t blockSize)

Correlation distance between two vectors.

The input vectors are modified in place !

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

float32_t **riscv_correlation_distance_f32**(float32_t *pA, float32_t *pB, uint32_t blockSize)

Correlation distance between two vectors.

The input vectors are modified in place !

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

Cosine distance

float16_t **riscv_cosine_distance_f16**(const float16_t *pA, const float16_t *pB, uint32_t blockSize)

float32_t **riscv_cosine_distance_f32**(const float32_t *pA, const float32_t *pB, uint32_t blockSize)

float64_t **riscv_cosine_distance_f64**(const float64_t *pA, const float64_t *pB, uint32_t blockSize)

group **CosineDist**

Cosine distance.

Functions

float16_t **riscv_cosine_distance_f16**(const float16_t *pA, const float16_t *pB, uint32_t blockSize)
Cosine distance between two vectors.

Description cosine_distance(u,v) is 1 - u . v / (Norm(u) Norm(v))

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

float32_t **riscv_cosine_distance_f32**(const float32_t *pA, const float32_t *pB, uint32_t blockSize)
Cosine distance between two vectors.

Description cosine_distance(u,v) is 1 - u . v / (Norm(u) Norm(v))

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

float64_t **riscv_cosine_distance_f64**(const float64_t *pA, const float64_t *pB, uint32_t blockSize)
Cosine distance between two vectors.

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

Dynamic Time Warping Distance

riscv_status **riscv_dtw_distance_f32**(const riscv_matrix_instance_f32 *pDistance, const riscv_matrix_instance_q7 *pWindow, riscv_matrix_instance_f32 *pDTW, float32_t *distance)

riscv_status **riscv_dtw_init_window_q7**(const riscv_dtw_window windowType, const int32_t windowSize, riscv_matrix_instance_q7 *pWindow)

void **riscv_dtw_path_f32**(const riscv_matrix_instance_f32 *pDTW, int16_t *pPath, uint32_t *pathLength) *group* **DTW**

Dynamic Time Warping Distance.

This is not really a distance since triangular inequality is not respected.

The step pattern used is symmetric2. Future versions of this function will provide more customization options.

Functions

riscv_status **riscv_dtw_distance_f32**(const riscv_matrix_instance_f32 *pDistance, const riscv_matrix_instance_q7 *pWindow, riscv_matrix_instance_f32 *pDTW, float32_t *distance)

Dynamic Time Warping distance.

The windowing matrix is used to impose some constraints on the search for a path. The algorithm will run faster (smaller search path) but may not be able to find a solution.

Windowing matrix

The distance matrix must be initialized only where the windowing matrix is containing 1. Thus, use of a window also decreases the number of distances which must be computed.

Parameters

- **pDistance** – **[in]** Distance matrix (Query rows * Template columns)
- **pWindow** – **[in]** Windowing matrix (can be NULL if no windowing used)
- **pDTW** – **[out]** Temporary cost buffer (same size)
- **distance** – **[out]** Distance

Returns RISCV_MATH_ARGUMENT_ERROR in case no path can be found with window constraint

riscv_status **riscv_dtw_init_window_q7**(const riscv_dtw_window windowType, const int32_t windowSize, riscv_matrix_instance_q7 *pWindow)

Window for dynamic time warping computation.

The input matrix must already contain a buffer and the number of rows (query length) and columns (template length) must be initialized. The function will fill the matrix with 0 and 1.

Windowing matrix The window matrix will contain 1 for the position which are accepted and 0 for the positions which are rejected.

Parameters

- **windowType** – **[in]** Type of window
- **windowSize** – **[in]** Window size
- **pWindow** – **[inout]** Window

Returns Error if window type not recognized void **riscv_dtw_path_f32**(const riscv_matrix_instance_f32 *pDTW, int16_t *pPath, uint32_t *pathLength)

Mapping between query and template.

The warping path has length which is at most 2*(query length + template length) in float. 2 because it is a list of coordinates : (query index, template index) coordinate.

Warping path

The buffer pPath must be big enough to contain the warping path.

pathLength is the number of points in the returned path. The resturned path may be smaller than query + template.

Parameters

- **pDTW** – **[in]** Cost matrix (Query rows * Template columns)
- **pPath** – **[out]** Warping path in cost matrix 2*(nb rows + nb columns)
- **pathLength** – **[out]** Length of path in number of points

Returns none

Euclidean distance

float16_t **riscv_euclidean_distance_f16**(const float16_t *pA, const float16_t *pB, uint32_t blockSize)

float32_t **riscv_euclidean_distance_f32**(const float32_t *pA, const float32_t *pB, uint32_t blockSize)

float64_t **riscv_euclidean_distance_f64**(const float64_t *pA, const float64_t *pB, uint32_t blockSize)

group **Euclidean**

Euclidean distance.

Functions

float16_t **riscv_euclidean_distance_f16**(const float16_t *pA, const float16_t *pB, uint32_t blockSize)

Euclidean distance between two vectors.

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

float32_t **riscv_euclidean_distance_f32**(const float32_t *pA, const float32_t *pB, uint32_t blockSize)

Euclidean distance between two vectors.

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

float64_t **riscv_euclidean_distance_f64**(const float64_t *pA, const float64_t *pB, uint32_t blockSize)

Euclidean distance between two vectors.

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

Jensen-Shannon distance

float16_t **riscv_jensenshannon_distance_f16**(const float16_t *pA, const float16_t *pB, uint32_t blockSize)

float32_t **riscv_jensenshannon_distance_f32**(const float32_t *pA, const float32_t *pB, uint32_t blockSize)

group **JensenShannon**

Jensen-Shannon distance.

Functions

__STATIC_INLINE float16_t rel_entr (float16_t x, float16_t y)

float16_t **riscv_jensenshannon_distance_f16**(const float16_t *pA, const float16_t *pB, uint32_t blockSize)

Jensen-Shannon distance between two vectors.

This function is assuming that elements of second vector are > 0 and 0 only when the corresponding element of first vector is 0. Otherwise the result of the computation does not make sense and for speed reasons, the cases returning NaN or Infinity are not managed.

When the function is computing x log (x / y) with x == 0 and y == 0, it will compute the right result (0) but a division by zero will occur and should be ignored in client code.

Parameters

- **pA** – **[in]** First vector
- **pB** – **[in]** Second vector
- **blockSize** – **[in]** vector length

Returns distance

__STATIC_INLINE float32_t rel_entr (float32_t x, float32_t y)

float32_t **riscv_jensenshannon_distance_f32**(const float32_t *pA, const float32_t *pB, uint32_t blockSize)

Jensen-Shannon distance between two vectors.

This function is assuming that elements of second vector are > 0 and 0 only when the corresponding element of first vector is 0. Otherwise the result of the computation does not make sense and for speed reasons, the cases returning NaN or Infinity are not managed.

When the function is computing x log (x / y) with x == 0 and y == 0, it will compute the right result (0) but a division by zero will occur and should be ignored in client code.

Parameters

- **`pA`** – **[in]** First vector
- **`pB`** – **[in]** Second vector
- **`blockSize`** – **[in]** vector length

Returns distance

Minkowski distance

float16_t **`riscv_minkowski_distance_f16`**(const float16_t *pA, const float16_t *pB, int32_t order, uint32_t blockSize)

float32_t **`riscv_minkowski_distance_f32`**(const float32_t *pA, const float32_t *pB, int32_t order, uint32_t blockSize)

group **`Minkowski`**

Minkowski distance.

Functions

float16_t **`riscv_minkowski_distance_f16`**(const float16_t *pA, const float16_t *pB, int32_t order, uint32_t blockSize)

Minkowski distance between two vectors.

Parameters

- **`pA`** – **[in]** First vector
- **`pB`** – **[in]** Second vector
- **`order`** – **[in]** Distance order
- **`blockSize`** – **[in]** Number of samples

Returns distance

float32_t **`riscv_minkowski_distance_f32`**(const float32_t *pA, const float32_t *pB, int32_t order, uint32_t blockSize)

Minkowski distance between two vectors.

Parameters

- **`pA`** – **[in]** First vector
- **`pB`** – **[in]** Second vector
- **`order`** – **[in]** Distance order
- **`blockSize`** – **[in]** Number of samples

Returns distance

group **`FloatDist`**

Distances between two vectors of float values.

Boolean Distances

float32_t **riscv_dice_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

float32_t **riscv_hamming_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

float32_t **riscv_jaccard_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

float32_t **riscv_kulsinski_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

float32_t **riscv_rogerstanimoto_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

float32_t **riscv_russellrao_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

float32_t **riscv_sokalmichener_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

float32_t **riscv_sokalsneath_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

float32_t **riscv_yule_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

group **BoolDist**

Distances between two vectors of boolean values.

Booleans are packed in 32 bit words. numberOfBooleans argument is the number of booleans and not the number of words.

Bits are packed in big-endian mode (because of behavior of numpy packbits in in version < 1.17)

Unnamed Group

float32_t **riscv_dice_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

Dice distance between two vectors.

Parameters

- **pA** – **[in]** First vector of packed booleans
- **pB** – **[in]** Second vector of packed booleans
- **numberOfBools** – **[in]** Number of booleans

Returns distance

Functions

float32_t **riscv_hamming_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

Hamming distance between two vectors.

Parameters

- **pA** – **[in]** First vector of packed booleans
- **pB** – **[in]** Second vector of packed booleans
- **numberOfBools** – **[in]** Number of booleans

Returns distance

float32_t **riscv_jaccard_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

Jaccard distance between two vectors.

Parameters

- **pA** – **[in]** First vector of packed booleans
- **pB** – **[in]** Second vector of packed booleans
- **numberOfBools** – **[in]** Number of booleans

Returns distance

float32_t **riscv_kulsinski_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

Kulsinski distance between two vectors.

Parameters

- **pA** – **[in]** First vector of packed booleans
- **pB** – **[in]** Second vector of packed booleans
- **numberOfBools** – **[in]** Number of booleans

Returns distance

float32_t **riscv_rogerstanimoto_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

Rogers Tanimoto distance between two vectors.

Roger Stanimoto distance between two vectors.

Parameters

- **pA** – **[in]** First vector of packed booleans
- **pB** – **[in]** Second vector of packed booleans
- **numberOfBools** – **[in]** Number of booleans

Returns distance

float32_t **riscv_russellrao_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

Russell-Rao distance between two vectors.

Parameters

- **pA** – **[in]** First vector of packed booleans
- **pB** – **[in]** Second vector of packed booleans
- **numberOfBools** – **[in]** Number of booleans

Returns distance

float32_t **riscv_sokalmichener_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

Sokal-Michener distance between two vectors.

Parameters

- **pA** – **[in]** First vector of packed booleans
- **pB** – **[in]** Second vector of packed booleans
- **numberOfBools** – **[in]** Number of booleans

Returns distance

float32_t **riscv_sokalsneath_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

Sokal-Sneath distance between two vectors.

Parameters

- **pA** – **[in]** First vector of packed booleans
- **pB** – **[in]** Second vector of packed booleans
- **numberOfBools** – **[in]** Number of booleans

Returns distance

float32_t **riscv_yule_distance**(const uint32_t *pA, const uint32_t *pB, uint32_t numberOfBools)

Yule distance between two vectors.

Parameters

- **pA** – **[in]** First vector of packed booleans
- **pB** – **[in]** Second vector of packed booleans
- **numberOfBools** – **[in]** Number of booleans

Returns distance

group **groupDistance**

Distance functions for use with clustering algorithms. There are distance functions for float vectors and boolean vectors.

3.3.6 Fast Math Functions

ArcTan2

riscv_status **riscv_atan2_f16**(float16_t y, float16_t x, float16_t *result)

riscv_status **riscv_atan2_f32**(float32_t y, float32_t x, float32_t *result)

riscv_status **riscv_atan2_q15**(q15_t y, q15_t x, q15_t *result)

riscv_status **riscv_atan2_q31**(q31_t y, q31_t x, q31_t *result)

group **atan2**

Computing Arc tangent only using the ratio y/x is not enough to determine the angle since there is an indeterminacy. Opposite quadrants are giving the same ratio.

ArcTan2 is not using y/x to compute the angle but y and x and use the sign of y and x to determine the quadrant.

Functions

riscv_status **riscv_atan2_f16**(float16_t y, float16_t x, float16_t *result)

Arc Tangent of y/x using sign of y and x to get right quadrant.

Arc tangent in radian of y/x using sign of x and y to determine right quadrant.

Compute the Arc tangent of y/x: The sign of y and x are used to determine the right quadrant and compute the right angle.

Parameters

- **y** – **[in]** y coordinate
- **x** – **[in]** x coordinate
- **result** – **[out]** Result

Returns error status.

riscv_status **riscv_atan2_f32**(float32_t y, float32_t x, float32_t *result)

Arc Tangent of y/x using sign of y and x to get right quadrant.

Arc tangent in radian of y/x using sign of x and y to determine right quadrant.

Compute the Arc tangent of y/x: The sign of y and x are used to determine the right quadrant and compute the right angle.

Parameters

- **y** – **[in]** y coordinate
- **x** – **[in]** x coordinate
- **result** – **[out]** Result

Returns error status.

riscv_status **riscv_atan2_q15**(q15_t y, q15_t x, q15_t *result)

Arc Tangent of y/x using sign of y and x to get right quadrant.

Arc tangent in radian of y/x using sign of x and y to determine right quadrant.

Compute the Arc tangent of y/x: The sign of y and x are used to determine the right quadrant and compute the right angle.

Parameters

- **y** – **[in]** y coordinate
- **x** – **[in]** x coordinate
- **result** – **[out]** Result in Q2.13

Returns error status.

riscv_status **riscv_atan2_q31**(q31_t y, q31_t x, q31_t *result)

Arc Tangent of y/x using sign of y and x to get right quadrant.

Arc tangent in radian of y/x using sign of x and y to determine right quadrant.

Compute the Arc tangent of y/x: The sign of y and x are used to determine the right quadrant and compute the right angle.

Parameters

- **y** – **[in]** y coordinate
- **x** – **[in]** x coordinate
- **result** – **[out]** Result in Q2.29

Returns error status.

Cosine

float32_t **riscv_cos_f32**(float32_t x)

q15_t **riscv_cos_q15**(q15_t x)

q31_t **riscv_cos_q31**(q31_t x)

group **cos**

Computes the trigonometric cosine function using a combination of table lookup and linear interpolation. There are separate functions for Q15, Q31, and floating-point data types. The input to the floating-point version is in radians while the fixed-point Q15 and Q31 have a scaled input with the range [0 +0.9999] mapping to [0 2*pi). The fixed-point range is chosen so that a value of 2*pi wraps around to 0.

The implementation is based on table lookup using 512 values together with linear interpolation. The steps used are:

1. Calculation of the nearest integer table index
2. Compute the fractional portion (fract) of the table index.
3. The final result equals `(1.0f-fract)*a + fract*b;`

where

Functions

float32_t **riscv_cos_f32**(float32_t x)

Fast approximation to the trigonometric cosine function for floating-point data.

Parameters **x** – **[in]** input value in radians

Returns cos(x)

q15_t **riscv_cos_q15**(q15_t x)

Fast approximation to the trigonometric cosine function for Q15 data.

The Q15 input value is in the range [0 +0.9999] and is mapped to a radian value in the range [0 2*PI).

Parameters **x** – **[in]** Scaled input value in radians

Returns cos(x)

q31_t **riscv_cos_q31**(q31_t x)

Fast approximation to the trigonometric cosine function for Q31 data.

The Q31 input value is in the range [0 +0.9999] and is mapped to a radian value in the range [0 2*PI).

Parameters **x** – **[in]** Scaled input value in radians

Returns cos(x)

Fixed point division

riscv_status **riscv_divide_q15**(q15_t numerator, q15_t denominator, q15_t *quotient, int16_t *shift)

riscv_status **riscv_divide_q31**(q31_t numerator, q31_t denominator, q31_t *quotient, int16_t *shift)

group **divide**

Functions

riscv_status **riscv_divide_q15**(q15_t numerator, q15_t denominator, q15_t *quotient, int16_t *shift)

Fixed point division.

When dividing by 0, an error RISCV_MATH_NANINF is returned. And the quotient is forced to the saturated negative or positive value.

Parameters

- **numerator** – **[in]** Numerator
- **denominator** – **[in]** Denominator
- **quotient** – **[out]** Quotient value normalized between -1.0 and 1.0
- **shift** – **[out]** Shift left value to get the unnormalized quotient

Returns error status

riscv_status **riscv_divide_q31**(q31_t numerator, q31_t denominator, q31_t *quotient, int16_t *shift)

Fixed point division.

When dividing by 0, an error RISCV_MATH_NANINF is returned. And the quotient is forced to the saturated negative or positive value.

Parameters

- **numerator** – **[in]** Numerator
- **denominator** – **[in]** Denominator
- **quotient** – **[out]** Quotient value normalized between -1.0 and 1.0
- **shift** – **[out]** Shift left value to get the unnormalized quotient

Returns error status

Sine

float32_t **riscv_sin_f32**(float32_t x)

q15_t **riscv_sin_q15**(q15_t x)

q31_t **riscv_sin_q31**(q31_t x)

group **sin**

Computes the trigonometric sine function using a combination of table lookup and linear interpolation. There are separate functions for Q15, Q31, and floating-point data types. The input to the floating-point version is in radians while the fixed-point Q15 and Q31 have a scaled input with the range [0 +0.9999] mapping to [0 2*pi). The fixed-point range is chosen so that a value of 2*pi wraps around to 0.

The implementation is based on table lookup using 512 values together with linear interpolation. The steps used are:

1. Calculation of the nearest integer table index
2. Compute the fractional portion (fract) of the table index.
3. The final result equals `(1.0f-fract)*a + fract*b;`

where

Functions

float32_t **riscv_sin_f32**(float32_t x)

Fast approximation to the trigonometric sine function for floating-point data.

Parameters **x** – **[in]** input value in radians.

Returns sin(x)

q15_t **riscv_sin_q15**(q15_t x)

Fast approximation to the trigonometric sine function for Q15 data.

The Q15 input value is in the range [0 +0.9999] and is mapped to a radian value in the range [0 2*PI).

Parameters **x** – **[in]** Scaled input value in radians

Returns sin(x)

q31_t **riscv_sin_q31**(q31_t x)

Fast approximation to the trigonometric sine function for Q31 data.

The Q31 input value is in the range [0 +0.9999] and is mapped to a radian value in the range [0 2*PI).

Parameters **x** – **[in]** Scaled input value in radians

Returns sin(x)

Vector Exponential

void **riscv_vexp_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

void **riscv_vexp_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

group **vexp**

Compute the exp values of a vector of samples.

Functions

void **riscv_vexp_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

Floating-point vector of exp values.

Parameters

- **pSrc** – **[in]** points to the input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_vexp_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Floating-point vector of exp values.

Parameters

- **pSrc** – **[in]** points to the input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Vector Log

void **riscv_vlog_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

void **riscv_vlog_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_vlog_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_vlog_q31**(const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

group **vlog**

Compute the log values of a vector of samples.

Functions

void **riscv_vlog_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

Floating-point vector of log values.

Parameters

- **pSrc** – **[in]** points to the input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_vlog_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Floating-point vector of log values.

Parameters

- **pSrc** – **[in]** points to the input vector
- **pDst** – **[out]** points to the output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_vlog_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

q15 vector of log values.

Parameters

- **pSrc** – **[in]** points to the input vector in q15
- **pDst** – **[out]** points to the output vector in q4.11
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_vlog_q31**(const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

q31 vector of log values.

Parameters

- **pSrc** – **[in]** points to the input vector in q31
- **pDst** – **[out]** points to the output vector q5.26
- **blockSize** – **[in]** number of samples in each vector

Returns none

Square Root

__STATIC_FORCEINLINE riscv_status riscv_sqrt_f32 (const float32_t in, float32_t *pOut)

riscv_status **riscv_sqrt_q31**(q31_t in, q31_t *pOut)

riscv_status **riscv_sqrt_q15**(q15_t in, q15_t *pOut)

`__STATIC_FORCEINLINE riscv_status riscv_sqrt_f16 (float16_t in, float16_t *pOut)`

group `SQRT`

Computes the square root of a number. There are separate functions for Q15, Q31, and floating-point data types. The square root function is computed using the Newton-Raphson algorithm. This is an iterative algorithm of the form:

where `x1` is the current estimate, `x0` is the previous estimate, and `f'(x0)` is the derivative of `f()` evaluated at `x0`. For the square root function, the algorithm reduces to:

Functions

`__STATIC_FORCEINLINE riscv_status riscv_sqrt_f32 (const float32_t in, float32_t *pOut)`

Floating-point square root function.

Parameters

- **`in`** – **[in]** input value
- **`pOut`** – **[out]** square root of input value

Returns execution status

- RISCV_MATH_SUCCESS : input value is positive
- RISCV_MATH_ARGUMENT_ERROR : input value is negative; *pOut is set to 0

riscv_status **`riscv_sqrt_q31`**(q31_t in, q31_t *pOut)

Q31 square root function.

Parameters

- **`in`** – **[in]** input value. The range of the input value is [0 +1) or 0x00000000 to 0x7FFFFFFF
- **`pOut`** – **[out]** points to square root of input value

Returns execution status

- RISCV_MATH_SUCCESS : input value is positive
- RISCV_MATH_ARGUMENT_ERROR : input value is negative; *pOut is set to 0

riscv_status **`riscv_sqrt_q15`**(q15_t in, q15_t *pOut)

Q15 square root function.

Parameters

- **`in`** – **[in]** input value. The range of the input value is [0 +1) or 0x0000 to 0x7FFF
- **`pOut`** – **[out]** points to square root of input value

Returns execution status

- RISCV_MATH_SUCCESS : input value is positive
- RISCV_MATH_ARGUMENT_ERROR : input value is negative; *pOut is set to 0

`__STATIC_FORCEINLINE riscv_status riscv_sqrt_f16 (float16_t in, float16_t *pOut)`

Floating-point square root function.

Parameters

- **in** – **[in]** input value
- **pOut** – **[out]** square root of input value

Returns execution status

- RISCV_MATH_SUCCESS : input value is positive
- RISCV_MATH_ARGUMENT_ERROR : input value is negative; *pOut is set to 0

group **groupFastMath**

This set of functions provides a fast approximation to sine, cosine, and square root. As compared to most of the other functions in the NMSIS math library, the fast math functions operate on individual values and not arrays. There are separate functions for Q15, Q31, and floating-point data.

3.3.7 Filtering Functions

High Precision Q31 Biquad Cascade Filter

void **riscv_biquad_cas_df1_32x64_init_q31**(riscv_biquad_cas_df1_32x64_ins_q31 *S, uint8_t numStages, const q31_t *pCoeffs, q63_t *pState, uint8_t postShift)

void **riscv_biquad_cas_df1_32x64_q31**(const riscv_biquad_cas_df1_32x64_ins_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

group **BiquadCascadeDF1_32x64**

This function implements a high precision Biquad cascade filter which operates on Q31 data values. The filter coefficients are in 1.31 format and the state variables are in 1.63 format. The double precision state variables reduce quantization noise in the filter and provide a cleaner output. These filters are particularly useful when implementing filters in which the singularities are close to the unit circle. This is common for low pass or high pass filters with very low cutoff frequencies.

The function operates on blocks of input and output data and each call to the function processes `blockSize` samples through the filter. `pSrc` and `pDst` points to input and output arrays containing `blockSize` Q31 values.

Algorithm

Each Biquad stage implements a second order filter using the difference equation: A Direct Form I algorithm is used with 5 coefficients and 4 state variables per stage.

Coefficients `b0, b1 and b2` multiply the input signal `x[n]` and are referred to as the feedforward coefficients. Coefficients `a1` and `a2` multiply the output signal `y[n]` and are referred to as the feedback coefficients. Pay careful attention to the sign of the feedback coefficients. Some design tools use the difference equation In this case the feedback coefficients `a1` and `a2` must be negated when used with the NMSIS DSP



Library.

Higher order filters are realized as a cascade of second order sections. `numStages` refers to the number of second order stages used. For example, an 8th order filter would be realized with `numStages=4` second order stages.

A 9th order filter would be realized with `numStages=5` second order stages with the coefficients for one of the stages configured as a first order filter (`b2=0` and `a2=0`).



The `pState` points to state variables array. Each Biquad stage has 4 state variables `x[n-1], x[n-2], y[n-1],` and `y[n-2]` and each state variable in 1.63 format to improve precision. The state variables are arranged in the array as:

The 4 state variables for stage 1 are first, then the 4 state variables for stage 2, and so on. The state array has a total length of `4*numStages` values of data in 1.63 format. The state variables are updated after each block of data is processed, the coefficients are untouched.

Instance Structure The coefficients and state variables for a filter are stored together in an instance data structure. A separate instance structure must be defined for each filter. Coefficient arrays may be shared among several instances while state variable arrays cannot be shared.

Init Function There is also an associated initialization function which performs the following operations:

- Sets the values of the internal structure fields.
- Zeros out the values in the state buffer. To do this manually without calling the init function, assign the follow subfields of the instance structure: numStages, pCoeffs, postShift, pState. Also set all of the values in pState to zero.

Use of the initialization function is optional. However, if the initialization function is used, then the instance structure cannot be placed into a const data section. To place an instance structure into a const data section, the instance structure must be manually initialized. Set the values in the state buffer to zeros before static initialization. For example, to statically initialize the filter instance structure use where `numStages` is the number of Biquad stages in the filter; `pState` is the address of the state buffer; `pCoeffs` is the address of the coefficient buffer; `postShift` shift to be applied which is described in detail below.

Fixed-Point Behavior Care must be taken while using Biquad Cascade 32x64 filter function. Following issues must be considered:

- Scaling of coefficients
- Filter gain
- Overflow and saturation

Filter coefficients are represented as fractional values and restricted to lie in the range `[-1 +1)`. The processing function has an additional scaling parameter `postShift` which allows the filter coefficients to exceed the range `[+1 -1)`. At the output of the filter's accumulator is a shift register which shifts the result by `postShift` bits.

This essentially scales the filter coefficients by `2^postShift`. For example, to realize the coefficients set the Coefficient array to: and set `postShift=1`



The second thing to keep in mind is the gain through the filter. The frequency response of a Biquad filter is a function of its coefficients. It is possible for the gain through the filter to exceed 1.0 meaning that the filter increases the amplitude of certain frequencies. This means that an input signal with amplitude < 1.0 may result in an output > 1.0 and these are saturated or overflowed based on the implementation of the filter. To avoid this behavior the filter needs to be scaled down such that its peak gain < 1.0 or the input signal must be scaled down so that the combination of input and filter are never overflowed.

The third item to consider is the overflow and saturation behavior of the fixed-point Q31 version. This is described in the function specific documentation below.

Functions

void **riscv_biquad_cas_df1_32x64_init_q31**(riscv_biquad_cas_df1_32x64_ins_q31 *S, uint8_t numStages, const q31_t *pCoeffs, q63_t *pState, uint8_t postShift)

Initialization function for the Q31 Biquad cascade 32x64 filter.

Coefficient and State Ordering The coefficients are stored in the array `pCoeffs` in the following order: where `b1x` and `a1x` are the coefficients for the first stage, `b2x` and `a2x` are the coefficients for the second stage, and so on. The `pCoeffs` array contains a total of `5*numStages` values.

The `pState` points to state variables array and size of each state variable is 1.63 format. Each Biquad stage has 4 state variables `x[n-1], x[n-2], y[n-1],` and `y[n-2]`. The state variables are arranged in the state array as: The 4 state variables for stage 1 are first, then the 4 state variables for stage 2, and so on. The state array has a total length of `4*numStages` values. The state variables are updated after each block of data is processed; the coefficients are untouched.

Parameters

- `S` – **[inout]** points to an instance of the high precision Q31 Biquad cascade filter structure
- `numStages` – **[in]** number of 2nd order stages in the filter
- `pCoeffs` – **[in]** points to the filter coefficients
- `pState` – **[in]** points to the state buffer
- `postShift` – **[in]** Shift to be applied after the accumulator. Varies according to the coefficients format

Returns none

void **`riscv_biquad_cas_df1_32x64_q31`**(const riscv_biquad_cas_df1_32x64_ins_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

Processing function for the Q31 Biquad cascade 32x64 filter.

Details The function is implemented using an internal 64-bit accumulator. The accumulator has a 2.62 format and maintains full precision of the intermediate multiplication results but provides only a single guard bit. Thus, if the accumulator result overflows it wraps around rather than clip. In order to avoid overflows completely the input signal must be scaled down by 2 bits and lie in the range [-0.25 +0.25). After all 5 multiply-accumulates are performed, the 2.62 accumulator is shifted by `postShift` bits and the result truncated to 1.31 format by discarding the low 32 bits.

Two related functions are provided in the NMSIS DSP library.

- riscv_biquad_cascade_df1_q31() implements a Biquad cascade with 32-bit coefficients and state variables with a Q63 accumulator.
- riscv_biquad_cascade_df1_fast_q31() implements a Biquad cascade with 32-bit coefficients and state variables with a Q31 accumulator.

Parameters

- `S` – **[in]** points to an instance of the high precision Q31 Biquad cascade filter
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process

Returns none

Biquad Cascade IIR Filters Using Direct Form I Structure

void **riscv_biquad_cascade_df1_f16**(const riscv_biquad_casd_df1_inst_f16 *S, const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

void **riscv_biquad_cascade_df1_f32**(const riscv_biquad_casd_df1_inst_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_biquad_cascade_df1_fast_q15**(const riscv_biquad_casd_df1_inst_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_biquad_cascade_df1_fast_q31**(const riscv_biquad_casd_df1_inst_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

void **riscv_biquad_cascade_df1_init_f16**(riscv_biquad_casd_df1_inst_f16 *S, uint8_t numStages, const float16_t *pCoeffs, float16_t *pState)

void **riscv_biquad_cascade_df1_init_f32**(riscv_biquad_casd_df1_inst_f32 *S, uint8_t numStages, const float32_t *pCoeffs, float32_t *pState)

void **riscv_biquad_cascade_df1_init_q15**(riscv_biquad_casd_df1_inst_q15 *S, uint8_t numStages, const q15_t *pCoeffs, q15_t *pState, int8_t postShift)

void **riscv_biquad_cascade_df1_init_q31**(riscv_biquad_casd_df1_inst_q31 *S, uint8_t numStages, const q31_t *pCoeffs, q31_t *pState, int8_t postShift)

void **riscv_biquad_cascade_df1_q15**(const riscv_biquad_casd_df1_inst_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_biquad_cascade_df1_q31**(const riscv_biquad_casd_df1_inst_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

group **BiquadCascadeDF1**

This set of functions implements arbitrary order recursive (IIR) filters. The filters are implemented as a cascade of second order Biquad sections. The functions support Q15, Q31 and floating-point data types. Fast version of Q15 and Q31 also available.

The functions operate on blocks of input and output data and each call to the function processes `blockSize` samples through the filter. `pSrc` points to the array of input data and `pDst` points to the array of output data. Both arrays contain `blockSize` values.

Algorithm

Each Biquad stage implements a second order filter using the difference equation: A Direct Form I algorithm is used with 5 coefficients and 4 state variables per stage.

Coefficients `b0, b1 and b2` multiply the input signal `x[n]` and are referred to as the feedforward coefficients. Coefficients `a1` and `a2` multiply the output signal `y[n]` and are referred to as the feedback coefficients. Pay careful attention to the sign of the feedback coefficients. Some design tools use the difference equation In this case the feedback coefficients `a1` and `a2` must be negated when used with the NMSIS DSP



Library.

Higher order filters are realized as a cascade of second order sections. `numStages` refers to the number of second order stages used. For example, an 8th order filter would be realized with `numStages=4` second order stages.

A 9th order filter would be realized with `numStages=5` second order stages with the coefficients for one of the stages configured as a first order filter (`b2=0` and



`a2=0`).

The `pState` points to state variables array. Each Biquad stage has 4 state variables `x[n-1], x[n-2], y[n-1],` and `y[n-2]`. The state variables are arranged in the `pState` array as:

The 4 state variables for stage 1 are first, then the 4 state variables for stage 2, and so on. The state array has a total length of `4*numStages` values. The state variables are updated after each block of data is processed, the coefficients are untouched.

Instance Structure The coefficients and state variables for a filter are stored together in an instance data structure. A separate instance structure must be defined for each filter. Coefficient arrays may be shared among several instances while state variable arrays cannot be shared. There are separate instance structure declarations for each of the 3 supported data types.

Init Function There is also an associated initialization function for each data type. The initialization function performs following operations:

- Sets the values of the internal structure fields.
- Zeros out the values in the state buffer. To do this manually without calling the init function, assign the follow subfields of the instance structure: numStages, pCoeffs, pState. Also set all of the values in pState to zero.

Use of the initialization function is optional. However, if the initialization function is used, then the instance structure cannot be placed into a const data section. To place an instance structure into a const data section, the instance structure must be manually initialized. Set the values in the state buffer to zeros before static initialization. The code below statically initializes each of the 3 different data type filter instance structures where `numStages` is the number of Biquad stages in the filter; `pState` is the address of the state buffer; `pCoeffs` is the address of the coefficient buffer; `postShift` shift to be applied.

Fixed-Point Behavior Care must be taken when using the Q15 and Q31 versions of the Biquad Cascade filter functions. Following issues must be considered:

- Scaling of coefficients
- Filter gain
- Overflow and saturation

Scaling of coefficients Filter coefficients are represented as fractional values and coefficients are restricted to lie in the range `[-1 +1)`. The fixed-point functions have an additional scaling parameter `postShift` which allow the filter coefficients to exceed the range `[+1 -1)`. At the output of the filter's accumulator is a shift register which shifts the result by `postShift` bits.

This essentially scales the filter coefficients by `2^postShift`. For example, to realize the coefficients set the pCoeffs array to: and set



`postShift=1`

Filter gain The frequency response of a Biquad filter is a function of its coefficients. It is possible for the gain through the filter to exceed 1.0 meaning that the filter increases the amplitude of certain frequencies. This means that an input signal with amplitude < 1.0 may result in an output > 1.0 and these are saturated or overflowed based on the implementation of the filter. To avoid this behavior the filter needs to be scaled down such that its peak gain < 1.0 or the input signal must be scaled down so that the combination of input and filter are never overflowed.

Overflow and saturation For Q15 and Q31 versions, it is described separately as part of the function specific documentation below.

Functions

void **riscv_biquad_cascade_df1_f16**(const riscv_biquad_casd_df1_inst_f16 *S, const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

Processing function for the floating-point Biquad cascade filter.

Parameters

- **S** – **[in]** points to an instance of the floating-point Biquad cascade structure
- **pSrc** – **[in]** points to the block of input data
- **pDst** – **[out]** points to the block of output data

- `blockSize` – **[in]** number of samples to process

Returns none

void **`riscv_biquad_cascade_df1_f32`**(const riscv_biquad_casd_df1_inst_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Processing function for the floating-point Biquad cascade filter.

Parameters

- `S` – **[in]** points to an instance of the floating-point Biquad cascade structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process

Returns none

void **`riscv_biquad_cascade_df1_fast_q15`**(const riscv_biquad_casd_df1_inst_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

Processing function for the Q15 Biquad cascade filter (fast variant).

Fast but less precise processing function for the Q15 Biquad cascade filter for RISC-V Core with DSP enabled.

Remark

Refer to riscv_biquad_cascade_df1_q15() for a slower implementation of this function which uses 64-bit accumulation to avoid wrap around distortion. Both the slow and the fast versions use the same instance structure. Use the function riscv_biquad_cascade_df1_init_q15() to initialize the filter structure.

Scaling and Overflow Behavior This fast version uses a 32-bit accumulator with 2.30 format. The accumulator maintains full precision of the intermediate multiplication results but provides only a single guard bit. Thus, if the accumulator result overflows it wraps around and distorts the result. In order to avoid overflows completely the input signal must be scaled down by two bits and lie in the range [-0.25 +0.25). The 2.30 accumulator is then shifted by `postShift` bits and the result truncated to 1.15 format by discarding the low 16 bits.

Parameters

- `S` – **[in]** points to an instance of the Q15 Biquad cascade structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process per call

Returns none

void **`riscv_biquad_cascade_df1_fast_q31`**(const riscv_biquad_casd_df1_inst_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

Processing function for the Q31 Biquad cascade filter (fast variant).

Fast but less precise processing function for the Q31 Biquad cascade filter for RISC-V Core with DSP enabled.

Remark

Refer to riscv_biquad_cascade_df1_q31() for a slower implementation of this function which uses 64-bit accumulation to provide higher precision. Both the slow and the fast versions use the same instance structure. Use the function riscv_biquad_cascade_df1_init_q31() to initialize the filter structure.

Scaling and Overflow Behavior This function is optimized for speed at the expense of fixed-point precision and overflow protection. The result of each 1.31 x 1.31 multiplication is truncated to 2.30 format. These intermediate results are added to a 2.30 accumulator. Finally, the accumulator is saturated and converted to a 1.31 result. The fast version has the same overflow behavior as the standard version and provides less precision since it discards the low 32 bits of each multiplication result. In order to avoid overflows completely the input signal must be scaled down by two bits and lie in the range [-0.25 +0.25). Use the intialization function riscv_biquad_cascade_df1_init_q31() to initialize filter structure.

Parameters

- `S` – **[in]** points to an instance of the Q31 Biquad cascade structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process per call

Returns none

void **riscv_biquad_cascade_df1_init_f16**(riscv_biquad_casd_df1_inst_f16 *S, uint8_t numStages, const float16_t *pCoeffs, float16_t *pState)

Initialization function for the floating-point Biquad cascade filter.

The initialization function which must be used is riscv_biquad_cascade_df1_mve_init_f16.

Coefficient and State Ordering The coefficients are stored in the array `pCoeffs` in the following order:

where `b1x` and `a1x` are the coefficients for the first stage, `b2x` and `a2x` are the coefficients for the second stage, and so on. The `pCoeffs` array contains a total of `5*numStages` values.

The `pState` is a pointer to state array. Each Biquad stage has 4 state variables `x[n-1], x[n-2], y[n-1],` and `y[n-2]`. The state variables are arranged in the `pState` array as: The 4 state variables for stage 1 are first, then the 4 state variables for stage 2, and so on. The state array has a total length of `4*numStages` values. The state variables are updated after each block of data is processed; the coefficients are untouched.

For MVE code, an additional buffer of modified coefficients is required. Its size is numStages and each element of this buffer has type riscv_biquad_mod_coef_f16. So, its total size is 96*numStages float16_t elements.

Parameters

- `S` – **[inout]** points to an instance of the floating-point Biquad cascade structure.
- `numStages` – **[in]** number of 2nd order stages in the filter.
- `pCoeffs` – **[in]** points to the filter coefficients.

- `pState` – **[in]** points to the state buffer.

Returns none

void **riscv_biquad_cascade_df1_init_f32**(riscv_biquad_casd_df1_inst_f32 *S, uint8_t numStages, const float32_t *pCoeffs, float32_t *pState)

Initialization function for the floating-point Biquad cascade filter.

The initialization function which must be used is riscv_biquad_cascade_df1_mve_init_f32.

Coefficient and State Ordering The coefficients are stored in the array `pCoeffs` in the following order:

where `b1x` and `a1x` are the coefficients for the first stage, `b2x` and `a2x` are the coefficients for the second stage, and so on. The `pCoeffs` array contains a total of `5*numStages` values.

The `pState` is a pointer to state array. Each Biquad stage has 4 state variables `x[n-1], x[n-2], y[n-1],` and `y[n-2]`. The state variables are arranged in the `pState` array as: The 4 state variables for stage 1 are first, then the 4 state variables for stage 2, and so on. The state array has a total length of `4*numStages` values. The state variables are updated after each block of data is processed; the coefficients are untouched.

For MVE code, an additional buffer of modified coefficients is required. Its size is numStages and each element of this buffer has type riscv_biquad_mod_coef_f32. So, its total size is 32*numStages float32_t elements.

Parameters

- `S` – **[inout]** points to an instance of the floating-point Biquad cascade structure.
- `numStages` – **[in]** number of 2nd order stages in the filter.
- `pCoeffs` – **[in]** points to the filter coefficients.
- `pState` – **[in]** points to the state buffer.

Returns none

void **riscv_biquad_cascade_df1_init_q15**(riscv_biquad_casd_df1_inst_q15 *S, uint8_t numStages, const q15_t *pCoeffs, q15_t *pState, int8_t postShift)

Initialization function for the Q15 Biquad cascade filter.

Coefficient and State Ordering The coefficients are stored in the array `pCoeffs` in the following order:

where `b1x` and `a1x` are the coefficients for the first stage, `b2x` and `a2x` are the coefficients for the second stage, and so on. The `pCoeffs` array contains a total of `6*numStages` values. The zero coefficient between `b1` and `b2` facilities use of 16-bit SIMD instructions on the RISC-V Core with DSP.

The state variables are stored in the array `pState`. Each Biquad stage has 4 state variables `x[n-1], x[n-2], y[n-1],` and `y[n-2]`. The state variables are arranged in the `pState` array as: The 4 state variables for stage 1 are first, then the 4 state variables for stage 2, and so on. The state array has a total length of `4*numStages` values. The state variables are updated after each block of data is processed; the coefficients are untouched.

Parameters

- `S` – **[inout]** points to an instance of the Q15 Biquad cascade structure.
- `numStages` – **[in]** number of 2nd order stages in the filter.

- pCoeffs – **[in]** points to the filter coefficients.
- pState – **[in]** points to the state buffer.
- postShift – **[in]** Shift to be applied to the accumulator result. Varies according to the coefficients format

Returns none

void **riscv_biquad_cascade_df1_init_q31**(riscv_biquad_casd_df1_inst_q31 *S, uint8_t numStages, const q31_t *pCoeffs, q31_t *pState, int8_t postShift)

Initialization function for the Q31 Biquad cascade filter.

Coefficient and State Ordering The coefficients are stored in the array pCoeffs in the following order:

where b1x and a1x are the coefficients for the first stage, b2x and a2x are the coefficients for the second stage, and so on. The pCoeffs array contains a total of 5*numStages values.

The pState points to state variables array. Each Biquad stage has 4 state variables x[n-1], x[n-2], y[n-1], and y[n-2]. The state variables are arranged in the pState array as: The 4 state variables for stage 1 are first, then the 4 state variables for stage 2, and so on. The state array has a total length of 4*numStages values. The state variables are updated after each block of data is processed; the coefficients are untouched.

Parameters

- S – **[inout]** points to an instance of the Q31 Biquad cascade structure.
- numStages – **[in]** number of 2nd order stages in the filter.
- pCoeffs – **[in]** points to the filter coefficients.
- pState – **[in]** points to the state buffer.
- postShift – **[in]** Shift to be applied after the accumulator. Varies according to the coefficients format

Returns none

void **riscv_biquad_cascade_df1_q15**(const riscv_biquad_casd_df1_inst_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

Processing function for the Q15 Biquad cascade filter.

Remark

Refer to riscv_biquad_cascade_df1_fast_q15() for a faster but less precise implementation of this filter.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. Both coefficients and state variables are represented in 1.15 format and multiplications yield a 2.30 result. The 2.30 intermediate results are accumulated in a 64-bit accumulator in 34.30 format. There is no risk of internal overflow with this approach and the full precision of intermediate multiplications is preserved. The accumulator is then shifted by postShift bits to truncate the result to 1.15 format by discarding the low 16 bits. Finally, the result is saturated to 1.15 format.

Parameters

- `S` – **[in]** points to an instance of the Q15 Biquad cascade structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the location where the output result is written
- `blockSize` – **[in]** number of samples to process

Returns none

void **riscv_biquad_cascade_df1_q31**(const riscv_biquad_casd_df1_inst_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

Processing function for the Q31 Biquad cascade filter.

Remark

Refer to riscv_biquad_cascade_df1_fast_q31() for a faster but less precise implementation of this filter.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The accumulator has a 2.62 format and maintains full precision of the intermediate multiplication results but provides only a single guard bit. Thus, if the accumulator result overflows it wraps around rather than clip. In order to avoid overflows completely the input signal must be scaled down by 2 bits and lie in the range [-0.25 +0.25). After all 5 multiply-accumulates are performed, the 2.62 accumulator is shifted by `postShift` bits and the result truncated to 1.31 format by discarding the low 32 bits.

Parameters

- `S` – **[in]** points to an instance of the Q31 Biquad cascade structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process

Returns none

Biquad Cascade IIR Filters Using a Direct Form II Transposed Structure

void **riscv_biquad_cascade_df2T_f16**(const riscv_biquad_cascade_df2T_instance_f16 *S, const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

void **riscv_biquad_cascade_df2T_f32**(const riscv_biquad_cascade_df2T_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_biquad_cascade_df2T_f64**(const riscv_biquad_cascade_df2T_instance_f64 *S, const float64_t *pSrc, float64_t *pDst, uint32_t blockSize)

void **riscv_biquad_cascade_df2T_init_f16**(riscv_biquad_cascade_df2T_instance_f16 *S, uint8_t numStages, const float16_t *pCoeffs, float16_t *pState)

void **riscv_biquad_cascade_df2T_init_f32**(riscv_biquad_cascade_df2T_instance_f32 *S, uint8_t numStages, const float32_t *pCoeffs, float32_t *pState) void **riscv_biquad_cascade_df2T_init_f64**(riscv_biquad_cascade_df2T_instance_f64 *S, uint8_t numStages, const float64_t *pCoeffs, float64_t *pState)

void **riscv_biquad_cascade_stereo_df2T_f16**(const riscv_biquad_cascade_stereo_df2T_instance_f16 *S, const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

void **riscv_biquad_cascade_stereo_df2T_f32**(const riscv_biquad_cascade_stereo_df2T_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_biquad_cascade_stereo_df2T_init_f16**(riscv_biquad_cascade_stereo_df2T_instance_f16 *S, uint8_t numStages, const float16_t *pCoeffs, float16_t *pState)

void **riscv_biquad_cascade_stereo_df2T_init_f32**(riscv_biquad_cascade_stereo_df2T_instance_f32 *S, uint8_t numStages, const float32_t *pCoeffs, float32_t *pState)

group **BiquadCascadeDF2T**

This set of functions implements arbitrary order recursive (IIR) filters using a transposed direct form II structure. The filters are implemented as a cascade of second order Biquad sections. These functions provide a slight memory savings as compared to the direct form I Biquad filter functions. Only floating-point data is supported.

This function operate on blocks of input and output data and each call to the function processes `blockSize` samples through the filter. `pSrc` points to the array of input data and `pDst` points to the array of output data. Both arrays contain `blockSize` values.

Algorithm Each Biquad stage implements a second order filter using the difference equation: where d1 and d2 represent the two state values.

A Biquad filter using a transposed Direct Form II structure is shown below.

Coefficients `b0, b1, and b2` multiply the input signal `x[n]` and are referred to as the feedforward coefficients. Coefficients `a1` and `a2` multiply the output signal `y[n]` and are referred to as the feedback coefficients. Pay careful attention to the sign of the feedback coefficients. Some design tools flip the sign of the feedback coefficients: In this case the feedback coefficients `a1` and `a2` must be negated when used with the



NMSIS DSP Library.

Higher order filters are realized as a cascade of second order sections. `numStages` refers to the number of second order stages used. For example, an 8th order filter would be realized with `numStages=4` second order stages. A 9th order filter would be realized with `numStages=5` second order stages with the coefficients for one of the stages configured as a first order filter (`b2=0` and `a2=0`).

`pState` points to the state variable array. Each Biquad stage has 2 state variables `d1` and `d2`. The state variables are arranged in the `pState` array as: where `d1x` refers to the state variables for the first Biquad and `d2x` refers to the state variables for the second Biquad. The state array has a total length of `2*numStages` values. The state variables are updated after each block of data is processed; the coefficients are untouched.

The NMSIS library contains Biquad filters in both Direct Form I and transposed Direct Form II. The advantage of the Direct Form I structure is that it is numerically more robust for fixed-point data types. That is why the Direct Form I structure supports Q15 and Q31 data types. The transposed Direct Form II structure, on the other hand, requires a wide dynamic range for the state variables `d1` and `d2`. Because of this, the NMSIS library only has a floating-point version of the Direct Form II Biquad. The advantage of the Direct Form II Biquad is that it requires half the number of state variables, 2 rather than 4, per Biquad stage.

Instance Structure The coefficients and state variables for a filter are stored together in an instance data structure. A separate instance structure must be defined for each filter. Coefficient arrays may be shared among several instances while state variable arrays cannot be shared.

Init Functions There is also an associated initialization function. The initialization function performs following operations:

- Sets the values of the internal structure fields.
- Zeros out the values in the state buffer. To do this manually without calling the init function, assign the follow subfields of the instance structure: numStages, pCoeffs, pState. Also set all of the values in pState to zero.

Use of the initialization function is optional. However, if the initialization function is used, then the instance structure cannot be placed into a const data section. To place an instance structure into a const data section, the instance structure must be manually initialized. Set the values in the state buffer to zeros before static initialization. For example, to statically initialize the instance structure use where `numStages` is the number of Biquad stages in the filter; `pState` is the address of the state buffer. `pCoeffs` is the address of the coefficient buffer;

Functions

void **riscv_biquad_cascade_df2T_f16**(const riscv_biquad_cascade_df2T_instance_f16 *S, const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

Processing function for the floating-point transposed direct form II Biquad cascade filter.

Parameters

- **S** – **[in]** points to an instance of the filter data structure
- **pSrc** – **[in]** points to the block of input data
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of samples to process

Returns none

void **riscv_biquad_cascade_df2T_f32**(const riscv_biquad_cascade_df2T_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Processing function for the floating-point transposed direct form II Biquad cascade filter.

Parameters

- **S** – **[in]** points to an instance of the filter data structure
- **pSrc** – **[in]** points to the block of input data
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of samples to process

Returns none

void **riscv_biquad_cascade_df2T_f64**(const riscv_biquad_cascade_df2T_instance_f64 *S, const float64_t *pSrc, float64_t *pDst, uint32_t blockSize)

Processing function for the floating-point transposed direct form II Biquad cascade filter.

Parameters

- **S** – **[in]** points to an instance of the filter data structure
- **pSrc** – **[in]** points to the block of input data
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of samples to process

Returns none

void **riscv_biquad_cascade_df2T_init_f16**(riscv_biquad_cascade_df2T_instance_f16 *S, uint8_t numStages, const float16_t *pCoeffs, float16_t *pState)

Initialization function for the floating-point transposed direct form II Biquad cascade filter.

For Neon version, this array is bigger. If numstages = 4x + y, then the array has size: 32*x + 5*y and it must be initialized using the function riscv_biquad_cascade_df2T_compute_coefs_f16 which is taking the standard array coefficient as parameters.

Coefficient and State Ordering The coefficients are stored in the array `pCoeffs` in the following order in the not Neon version.

where `b1x` and `a1x` are the coefficients for the first stage, `b2x` and `a2x` are the coefficients for the second stage, and so on. The `pCoeffs` array contains a total of `5*numStages` values.

But, an array of 8*numstages is a good approximation.

Then, the initialization can be done with:

In this example, neonCoefs is a bigger array of size 8 * numStages. coefs is the standard array:

The `pState` is a pointer to state array. Each Biquad stage has 2 state variables `d1,` and `d2`. The 2 state variables for stage 1 are first, then the 2 state variables for stage 2, and so on. The state array has a total length of `2*numStages` values. The state variables are updated after each block of data is processed; the coefficients are untouched.

Parameters

- `S` – **[inout]** points to an instance of the filter data structure.
- `numStages` – **[in]** number of 2nd order stages in the filter.
- `pCoeffs` – **[in]** points to the filter coefficients.
- `pState` – **[in]** points to the state buffer.

Returns none

void **riscv_biquad_cascade_df2T_init_f32**(riscv_biquad_cascade_df2T_instance_f32 *S, uint8_t numStages, const float32_t *pCoeffs, float32_t *pState)

Initialization function for the floating-point transposed direct form II Biquad cascade filter.

For Neon version, this array is bigger. If numstages = 4x + y, then the array has size: 32*x + 5*y and it must be initialized using the function riscv_biquad_cascade_df2T_compute_coefs_f32 which is taking the standard array coefficient as parameters.

Coefficient and State Ordering The coefficients are stored in the array `pCoeffs` in the following order in the not Neon version.

where `b1x` and `a1x` are the coefficients for the first stage, `b2x` and `a2x` are the coefficients for the second stage, and so on. The `pCoeffs` array contains a total of `5*numStages` values.

But, an array of 8*numstages is a good approximation.

Then, the initialization can be done with:

In this example, computedCoefs is a bigger array of size 8 * numStages. coefs is the standard array:

The `pState` is a pointer to state array. Each Biquad stage has 2 state variables `d1,` and `d2`. The 2 state variables for stage 1 are first, then the 2 state variables for stage 2, and so on. The state array has a total length of `2*numStages` values. The state variables are updated after each block of data is processed; the coefficients are untouched.

Parameters

- `S` – **[inout]** points to an instance of the filter data structure.
- `numStages` – **[in]** number of 2nd order stages in the filter.
- `pCoeffs` – **[in]** points to the filter coefficients.
- `pState` – **[in]** points to the state buffer.

Returns none

void **riscv_biquad_cascade_df2T_init_f64**(riscv_biquad_cascade_df2T_instance_f64 *S, uint8_t numStages, const float64_t *pCoeffs, float64_t *pState)

Initialization function for the floating-point transposed direct form II Biquad cascade filter.

Coefficient and State Ordering The coefficients are stored in the array `pCoeffs` in the following order:

where `b1x` and `a1x` are the coefficients for the first stage, `b2x` and `a2x` are the coefficients for the second stage, and so on. The `pCoeffs` array contains a total of `5*numStages` values.

The `pState` is a pointer to state array. Each Biquad stage has 2 state variables `d1,` and `d2`. The 2 state variables for stage 1 are first, then the 2 state variables for stage 2, and so on. The state array has a total length of `2*numStages` values. The state variables are updated after each block of data is processed; the coefficients are untouched.

Parameters

- `S` – **[inout]** points to an instance of the filter data structure
- `numStages` – **[in]** number of 2nd order stages in the filter
- `pCoeffs` – **[in]** points to the filter coefficients
- `pState` – **[in]** points to the state buffer

Returns none

void **riscv_biquad_cascade_stereo_df2T_f16**(const riscv_biquad_cascade_stereo_df2T_instance_f16 *S, const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

Processing function for the floating-point transposed direct form II Biquad cascade filter.

Processing function for the floating-point transposed direct form II Biquad cascade filter. 2 channels.

Parameters

- `S` – **[in]** points to an instance of the filter data structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process

Returns none

void **riscv_biquad_cascade_stereo_df2T_f32**(const riscv_biquad_cascade_stereo_df2T_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Processing function for the floating-point transposed direct form II Biquad cascade filter.

Processing function for the floating-point transposed direct form II Biquad cascade filter. 2 channels.

Parameters

- `S` – **[in]** points to an instance of the filter data structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process

Returns none

void **riscv_biquad_cascade_stereo_df2T_init_f16**(riscv_biquad_cascade_stereo_df2T_instance_f16 *S, uint8_t numStages, const float16_t *pCoeffs, float16_t *pState)

Initialization function for the floating-point transposed direct form II Biquad cascade filter.

Coefficient and State Ordering The coefficients are stored in the array `pCoeffs` in the following order:

where `b1x` and `a1x` are the coefficients for the first stage, `b2x` and `a2x` are the coefficients for the second stage, and so on. The `pCoeffs` array contains a total of `5*numStages` values.

The `pState` is a pointer to state array. Each Biquad stage has 2 state variables `d1,` and `d2` for each channel. The 2 state variables for stage 1 are first, then the 2 state variables for stage 2, and so on. The state array has a total length of `2*numStages` values. The state variables are updated after each block of data is processed; the coefficients are untouched.

Parameters

- `S` – **[inout]** points to an instance of the filter data structure.
- `numStages` – **[in]** number of 2nd order stages in the filter.
- `pCoeffs` – **[in]** points to the filter coefficients.
- `pState` – **[in]** points to the state buffer.

Returns none

void **riscv_biquad_cascade_stereo_df2T_init_f32**(riscv_biquad_cascade_stereo_df2T_instance_f32 *S, uint8_t numStages, const float32_t *pCoeffs, float32_t *pState)

Initialization function for the floating-point transposed direct form II Biquad cascade filter.

Coefficient and State Ordering The coefficients are stored in the array `pCoeffs` in the following order:

where `b1x` and `a1x` are the coefficients for the first stage, `b2x` and `a2x` are the coefficients for the second stage, and so on. The `pCoeffs` array contains a total of `5*numStages` values.

The `pState` is a pointer to state array. Each Biquad stage has 2 state variables `d1,` and `d2` for each channel. The 2 state variables for stage 1 are first, then the 2 state variables for stage 2, and so on. The state array has a total length of `2*numStages` values. The state variables are updated after each block of data is processed; the coefficients are untouched.

Parameters

- `S` – **[inout]** points to an instance of the filter data structure.
- `numStages` – **[in]** number of 2nd order stages in the filter.

- **pCoeffs** – **[in]** points to the filter coefficients.
- **pState** – **[in]** points to the state buffer.

Returns none

Convolution

void **riscv_conv_f32**(const float32_t *pSrcA, uint32_t srcALen, const float32_t *pSrcB, uint32_t srcBLen, float32_t *pDst)

void **riscv_conv_fast_opt_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, q15_t *pScratch1, q15_t *pScratch2)

void **riscv_conv_fast_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst)

void **riscv_conv_fast_q31**(const q31_t *pSrcA, uint32_t srcALen, const q31_t *pSrcB, uint32_t srcBLen, q31_t *pDst)

void **riscv_conv_opt_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, q15_t *pScratch1, q15_t *pScratch2)

void **riscv_conv_opt_q7**(const q7_t *pSrcA, uint32_t srcALen, const q7_t *pSrcB, uint32_t srcBLen, q7_t *pDst, q15_t *pScratch1, q15_t *pScratch2)

void **riscv_conv_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst)

void **riscv_conv_q31**(const q31_t *pSrcA, uint32_t srcALen, const q31_t *pSrcB, uint32_t srcBLen, q31_t *pDst)

void **riscv_conv_q7**(const q7_t *pSrcA, uint32_t srcALen, const q7_t *pSrcB, uint32_t srcBLen, q7_t *pDst)

group **Conv**

Convolution is a mathematical operation that operates on two finite length vectors to generate a finite length output vector. Convolution is similar to correlation and is frequently used in filtering and data analysis. The NMSIS DSP library contains functions for convolving Q7, Q15, Q31, and floating-point data types. The library also provides fast versions of the Q15 and Q31 functions.

Algorithm Let `a[n]` and `b[n]` be sequences of length `srcALen` and `srcBLen` samples respectively. Then the convolution

$$c[n] = a[n] * b[n]$$

is defined as

$$c[n] = \sum_{k=0}^{srcALen} a[k]b[n-k]$$

Note that `c[n]` is of length `srcALen + srcBLen - 1` and is defined over the interval `n=0, 1, 2, ..., srcALen + srcBLen - 2`. `pSrcA` points to the first input vector of length `srcALen` and `pSrcB` points to the second input vector of length `srcBLen`. The output result is written to `pDst` and the calling function must allocate `srcALen+srcBLen-1` words for the result.

Conceptually, when two signals `a[n]` and `b[n]` are convolved, the signal `b[n]` slides over `a[n]`. For each offset `n`, the overlapping portions of a[n] and b[n] are multiplied and summed together.

Note that convolution is a commutative operation:

$$a[n] * b[n] = b[n] * a[n].$$

This means that switching the A and B arguments to the convolution functions has no effect.

Fixed-Point Behavior Convolution requires summing up a large number of intermediate products. As such, the Q7, Q15, and Q31 functions run a risk of overflow and saturation. Refer to the function specific documentation below for further details of the particular algorithm used.

Fast Versions Fast versions are supported for Q31 and Q15. Cycles for Fast versions are less compared to Q31 and Q15 of conv and the design requires the input signals should be scaled down to avoid intermediate overflows.

Opt Versions Opt versions are supported for Q15 and Q7. Design uses internal scratch buffer for getting good optimisation. These versions are optimised in cycles and consumes more memory (Scratch memory) compared to Q15 and Q7 versions

Long versions: For convolution of long vectors, those functions are no more adapted and will be very slow. An implementation based upon FFTs should be used.

Functions

void **riscv_conv_f32**(const float32_t *pSrcA, uint32_t srcALen, const float32_t *pSrcB, uint32_t srcBLen, float32_t *pDst)

Convolution of floating-point sequences.

Parameters

- **pSrcA** – **[in]** points to the first input sequence
- **srcALen** – **[in]** length of the first input sequence
- **pSrcB** – **[in]** points to the second input sequence
- **srcBLen** – **[in]** length of the second input sequence
- **pDst** – **[out]** points to the location where the output result is written. Length srcALen+srcBLen-1.

Returns none

void **riscv_conv_fast_opt_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, q15_t *pScratch1, q15_t *pScratch2)

Convolution of Q15 sequences (fast version).

Convolution of Q15 sequences (fast version) for RISC-V Core with DSP enabled.

Remark

Refer to riscv_conv_q15() for a slower implementation of this function which uses 64-bit accumulation to avoid wrap around distortion.

Scaling and Overflow Behavior This fast version uses a 32-bit accumulator with 2.30 format. The accumulator maintains full precision of the intermediate multiplication results but provides only a single guard bit. There is no saturation on intermediate additions. Thus, if the accumulator overflows it wraps around and distorts the result. The input signals should be scaled down to avoid intermediate overflows. Scale down the inputs by log2(min(srcALen, srcBLen)) (log2 is read as log to the base 2) times to avoid overflows, as maximum of min(srcALen, srcBLen) number of additions are carried internally. The 2.30 accumulator is right shifted by 15 bits and then saturated to 1.15 format to yield the final result.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written. Length srcALen+srcBLen-1
- `pScratch1` – **[in]** points to scratch buffer of size max(srcALen, srcBLen) + 2*min(srcALen, srcBLen) - 2
- `pScratch2` – **[in]** points to scratch buffer of size min(srcALen, srcBLen

Returns none

void **riscv_conv_fast_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst)

Convolution of Q15 sequences (fast version).

Convolution of Q15 sequences (fast version) for RISC-V Core with DSP enabled.

Remark

Refer to riscv_conv_q15() for a slower implementation of this function which uses 64-bit accumulation to avoid wrap around distortion.

Scaling and Overflow Behavior This fast version uses a 32-bit accumulator with 2.30 format. The accumulator maintains full precision of the intermediate multiplication results but provides only a single guard bit. There is no saturation on intermediate additions. Thus, if the accumulator overflows it wraps around and distorts the result. The input signals should be scaled down to avoid intermediate overflows. Scale down the inputs by log2(min(srcALen, srcBLen)) (log2 is read as log to the base 2) times to avoid overflows, as maximum of min(srcALen, srcBLen) number of additions are carried internally. The 2.30 accumulator is right shifted by 15 bits and then saturated to 1.15 format to yield the final result.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence

- **pDst** – **[out]** points to the location where the output result is written. Length srcALen+srcBLen-1

Returns none

void **riscv_conv_fast_q31**(const q31_t *pSrcA, uint32_t srcALen, const q31_t *pSrcB, uint32_t srcBLen, q31_t *pDst)

Convolution of Q31 sequences (fast version).

Convolution of Q31 sequences (fast version) for RISC-V Core with DSP enabled.

Remark

Refer to riscv_conv_q31() for a slower implementation of this function which uses 64-bit accumulation to provide higher precision.

Scaling and Overflow Behavior This function is optimized for speed at the expense of fixed-point precision and overflow protection. The result of each 1.31 x 1.31 multiplication is truncated to 2.30 format. These intermediate results are accumulated in a 32-bit register in 2.30 format. Finally, the accumulator is saturated and converted to a 1.31 result.

The fast version has the same overflow behavior as the standard version but provides less precision since it discards the low 32 bits of each multiplication result. In order to avoid overflows completely the input signals must be scaled down. Scale down the inputs by log2(min(srcALen, srcBLen)) (log2 is read as log to the base 2) times to avoid overflows, as maximum of min(srcALen, srcBLen) number of additions are carried internally.

Parameters

- **pSrcA** – **[in]** points to the first input sequence.
- **srcALen** – **[in]** length of the first input sequence.
- **pSrcB** – **[in]** points to the second input sequence.
- **srcBLen** – **[in]** length of the second input sequence.
- **pDst** – **[out]** points to the location where the output result is written. Length srcALen+srcBLen-1.

Returns none

void **riscv_conv_opt_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, q15_t *pScratch1, q15_t *pScratch2)

Convolution of Q15 sequences.

Remark

Refer to riscv_conv_fast_q15() for a faster but less precise version of this function.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. Both inputs are in 1.15 format and multiplications yield a 2.30 result. The 2.30 intermediate results are accumulated in a 64-bit accumulator in 34.30 format. This approach provides 33 guard bits and there is no risk of overflow. The 34.30 result is then truncated to 34.15 format by discarding the low 15 bits and then saturated to 1.15 format.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written. Length srcALen+srcBLen-1.
- `pScratch1` – **[in]** points to scratch buffer of size max(srcALen, srcBLen) + 2*min(srcALen, srcBLen) - 2.
- `pScratch2` – **[in]** points to scratch buffer of size min(srcALen, srcBLen).

Returns none

void **riscv_conv_opt_q7**(const q7_t *pSrcA, uint32_t srcALen, const q7_t *pSrcB, uint32_t srcBLen, q7_t *pDst, q15_t *pScratch1, q15_t *pScratch2)

Convolution of Q7 sequences.

Scaling and Overflow Behavior The function is implemented using a 32-bit internal accumulator. Both the inputs are represented in 1.7 format and multiplications yield a 2.14 result. The 2.14 intermediate results are accumulated in a 32-bit accumulator in 18.14 format. This approach provides 17 guard bits and there is no risk of overflow as long as `max(srcALen, srcBLen)<131072`. The 18.14 result is then truncated to 18.7 format by discarding the low 7 bits and then saturated to 1.7 format.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written. Length srcALen+srcBLen-1.
- `pScratch1` – **[in]** points to scratch buffer(of type q15_t) of size max(srcALen, srcBLen) + 2*min(srcALen, srcBLen) - 2.
- `pScratch2` – **[in]** points to scratch buffer (of type q15_t) of size min(srcALen, srcBLen).

Returns none

void **riscv_conv_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst)

Convolution of Q15 sequences.

Remark

Refer to riscv_conv_fast_q15() for a faster but less precise version of this function.

Remark

Refer to riscv_conv_opt_q15() for a faster implementation of this function using scratch buffers.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. Both inputs are in 1.15 format and multiplications yield a 2.30 result. The 2.30 intermediate results are accumulated in a 64-bit accumulator in 34.30 format. This approach provides 33 guard bits and there is no risk of overflow. The 34.30 result is then truncated to 34.15 format by discarding the low 15 bits and then saturated to 1.15 format.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written. Length srcALen+srcBLen-1.

Returns none

void **riscv_conv_q31**(const q31_t *pSrcA, uint32_t srcALen, const q31_t *pSrcB, uint32_t srcBLen, q31_t *pDst)

Convolution of Q31 sequences.

Remark

Refer to riscv_conv_fast_q31() for a faster but less precise implementation of this function.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The accumulator has a 2.62 format and maintains full precision of the intermediate multiplication results but provides only a single guard bit. There is no saturation on intermediate additions. Thus, if the accumulator overflows it wraps around and distorts the result. The input signals should be scaled down to avoid intermediate overflows. Scale down the inputs by log2(min(srcALen, srcBLen)) (log2 is read as log to the base 2) times to avoid overflows, as maximum of min(srcALen, srcBLen) number of additions are carried internally. The 2.62 accumulator is right shifted by 31 bits and saturated to 1.31 format to yield the final result.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence

- **pDst** – **[out]** points to the location where the output result is written. Length srcALen+srcBLen-1.

Returns none

void **riscv_conv_q7**(const q7_t *pSrcA, uint32_t srcALen, const q7_t *pSrcB, uint32_t srcBLen, q7_t *pDst)

Convolution of Q7 sequences.

Remark

Refer to riscv_conv_opt_q7() for a faster implementation of this function.

Scaling and Overflow Behavior The function is implemented using a 32-bit internal accumulator. Both the inputs are represented in 1.7 format and multiplications yield a 2.14 result. The 2.14 intermediate results are accumulated in a 32-bit accumulator in 18.14 format. This approach provides 17 guard bits and there is no risk of overflow as long as `max(srcALen, srcBLen)<131072`. The 18.14 result is then truncated to 18.7 format by discarding the low 7 bits and then saturated to 1.7 format.

Parameters

- **pSrcA** – **[in]** points to the first input sequence
- **srcALen** – **[in]** length of the first input sequence
- **pSrcB** – **[in]** points to the second input sequence
- **srcBLen** – **[in]** length of the second input sequence
- **pDst** – **[out]** points to the location where the output result is written. Length srcALen+srcBLen-1.

Returns none

Partial Convolution

riscv_status **riscv_conv_partial_f32**(const float32_t *pSrcA, uint32_t srcALen, const float32_t *pSrcB, uint32_t srcBLen, float32_t *pDst, uint32_t firstIndex, uint32_t numPoints)

riscv_status **riscv_conv_partial_fast_opt_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, uint32_t firstIndex, uint32_t numPoints, q15_t *pScratch1, q15_t *pScratch2)

riscv_status **riscv_conv_partial_fast_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, uint32_t firstIndex, uint32_t numPoints)

riscv_status **riscv_conv_partial_fast_q31**(const q31_t *pSrcA, uint32_t srcALen, const q31_t *pSrcB, uint32_t srcBLen, q31_t *pDst, uint32_t firstIndex, uint32_t numPoints) riscv_status **riscv_conv_partial_opt_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, uint32_t firstIndex, uint32_t numPoints, q15_t *pScratch1, q15_t *pScratch2)

riscv_status **riscv_conv_partial_opt_q7**(const q7_t *pSrcA, uint32_t srcALen, const q7_t *pSrcB, uint32_t srcBLen, q7_t *pDst, uint32_t firstIndex, uint32_t numPoints, q15_t *pScratch1, q15_t *pScratch2)

riscv_status **riscv_conv_partial_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, uint32_t firstIndex, uint32_t numPoints)

riscv_status **riscv_conv_partial_q31**(const q31_t *pSrcA, uint32_t srcALen, const q31_t *pSrcB, uint32_t srcBLen, q31_t *pDst, uint32_t firstIndex, uint32_t numPoints)

riscv_status **riscv_conv_partial_q7**(const q7_t *pSrcA, uint32_t srcALen, const q7_t *pSrcB, uint32_t srcBLen, q7_t *pDst, uint32_t firstIndex, uint32_t numPoints)

group **PartialConv**

Partial Convolution is equivalent to Convolution except that a subset of the output samples is generated. Each function has two additional arguments. `firstIndex` specifies the starting index of the subset of output samples. `numPoints` is the number of output samples to compute. The function computes the output in the range `[firstIndex, ..., firstIndex+numPoints-1]`. The output array `pDst` contains `numPoints` values.

The allowable range of output indices is [0 srcALen+srcBLen-2]. If the requested subset does not fall in this range then the functions return RISCV_MATH_ARGUMENT_ERROR. Otherwise the functions return RISCV_MATH_SUCCESS.

Fast Versions Fast versions are supported for Q31 and Q15 of partial convolution. Cycles for Fast versions are less compared to Q31 and Q15 of partial conv and the design requires the input signals should be scaled down to avoid intermediate overflows.

Opt Versions Opt versions are supported for Q15 and Q7. Design uses internal scratch buffer for getting good optimisation. These versions are optimised in cycles and consumes more memory (Scratch memory) compared to Q15 and Q7 versions of partial convolution

Long versions: For convolution of long vectors, those functions are no more adapted and will be very slow. An implementation based upon FFTs should be used.

Note: Refer to riscv_conv_f32() for details on fixed point behavior.

Functions

riscv_status **riscv_conv_partial_f32**(const float32_t *pSrcA, uint32_t srcALen, const float32_t *pSrcB, uint32_t srcBLen, float32_t *pDst, uint32_t firstIndex, uint32_t numPoints)

Partial convolution of floating-point sequences.

Parameters

- **pSrcA** – **[in]** points to the first input sequence
- **srcALen** – **[in]** length of the first input sequence
- **pSrcB** – **[in]** points to the second input sequence
- **srcBLen** – **[in]** length of the second input sequence

- **pDst** – **[out]** points to the location where the output result is written
- **firstIndex** – **[in]** is the first output sample to start with
- **numPoints** – **[in]** is the number of output points to be computed

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : requested subset is not in the range [0 srcALen+srcBLen-2]

riscv_status **riscv_conv_partial_fast_opt_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, uint32_t firstIndex, uint32_t numPoints, q15_t *pScratch1, q15_t *pScratch2)

Partial convolution of Q15 sequences (fast version).

Partial convolution of Q15 sequences (fast version) for RISC-V Core with DSP enabled.

Remark

Refer to riscv_conv_partial_q15() for a slower implementation of this function which uses a 64-bit accumulator to avoid wrap around distortion.

Parameters

- **pSrcA** – **[in]** points to the first input sequence
- **srcALen** – **[in]** length of the first input sequence
- **pSrcB** – **[in]** points to the second input sequence
- **srcBLen** – **[in]** length of the second input sequence
- **pDst** – **[out]** points to the location where the output result is written
- **firstIndex** – **[in]** is the first output sample to start with
- **numPoints** – **[in]** is the number of output points to be computed
- **pScratch1** – **[in]** points to scratch buffer of size max(srcALen, srcBLen) + 2*min(srcALen, srcBLen) - 2
- **pScratch2** – **[in]** points to scratch buffer of size min(srcALen, srcBLen)

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : requested subset is not in the range [0 srcALen+srcBLen-2]

riscv_status **riscv_conv_partial_fast_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, uint32_t firstIndex, uint32_t numPoints)

Partial convolution of Q15 sequences (fast version).

Partial convolution of Q15 sequences (fast version) for RISC-V Core with DSP enabled.

Remark

Refer to riscv_conv_partial_q15() for a slower implementation of this function which uses a 64-bit accumulator to avoid wrap around distortion.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written
- `firstIndex` – **[in]** is the first output sample to start with
- `numPoints` – **[in]** is the number of output points to be computed

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : requested subset is not in the range [0 srcALen+srcBLen-2]

riscv_status **riscv_conv_partial_fast_q31**(const q31_t *pSrcA, uint32_t srcALen, const q31_t *pSrcB, uint32_t srcBLen, q31_t *pDst, uint32_t firstIndex, uint32_t numPoints)

Partial convolution of Q31 sequences (fast version).

Partial convolution of Q31 sequences (fast version) for RISC-V Core with DSP enabled.

Remark

Refer to riscv_conv_partial_q31() for a slower implementation of this function which uses a 64-bit accumulator to provide higher precision.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written
- `firstIndex` – **[in]** is the first output sample to start with
- `numPoints` – **[in]** is the number of output points to be computed

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : requested subset is not in the range [0 srcALen+srcBLen-2]

riscv_status **riscv_conv_partial_opt_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, uint32_t firstIndex, uint32_t numPoints, q15_t *pScratch1, q15_t *pScratch2)

Partial convolution of Q15 sequences.

Remark

Refer to riscv_conv_partial_fast_q15() for a faster but less precise version of this function.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written
- `firstIndex` – **[in]** is the first output sample to start with
- `numPoints` – **[in]** is the number of output points to be computed
- `pScratch1` – **[in]** points to scratch buffer of size max(srcALen, srcBLen) + 2*min(srcALen, srcBLen) - 2.
- `pScratch2` – **[in]** points to scratch buffer of size min(srcALen, srcBLen).

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : requested subset is not in the range [0 srcALen+srcBLen-2]

riscv_status **riscv_conv_partial_opt_q7**(const q7_t *pSrcA, uint32_t srcALen, const q7_t *pSrcB, uint32_t srcBLen, q7_t *pDst, uint32_t firstIndex, uint32_t numPoints, q15_t *pScratch1, q15_t *pScratch2)

Partial convolution of Q7 sequences.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written
- `firstIndex` – **[in]** is the first output sample to start with

- **numPoints** – **[in]** is the number of output points to be computed
- **pScratch1** – **[in]** points to scratch buffer(of type q15_t) of size max(srcALen, srcBLen) + 2*min(srcALen, srcBLen) - 2.
- **pScratch2** – **[in]** points to scratch buffer (of type q15_t) of size min(srcALen, srcBLen).

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : requested subset is not in the range [0 srcALen+srcBLen-2]

riscv_status **riscv_conv_partial_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, uint32_t firstIndex, uint32_t numPoints)

Partial convolution of Q15 sequences.

Remark

Refer to riscv_conv_partial_fast_q15() for a faster but less precise version of this function.

Remark

Refer to riscv_conv_partial_opt_q15() for a faster implementation of this function using scratch buffers.

Parameters

- **pSrcA** – **[in]** points to the first input sequence
- **srcALen** – **[in]** length of the first input sequence
- **pSrcB** – **[in]** points to the second input sequence
- **srcBLen** – **[in]** length of the second input sequence
- **pDst** – **[out]** points to the location where the output result is written
- **firstIndex** – **[in]** is the first output sample to start with
- **numPoints** – **[in]** is the number of output points to be computed

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : requested subset is not in the range [0 srcALen+srcBLen-2]

riscv_status **riscv_conv_partial_q31**(const q31_t *pSrcA, uint32_t srcALen, const q31_t *pSrcB, uint32_t srcBLen, q31_t *pDst, uint32_t firstIndex, uint32_t numPoints)

Partial convolution of Q31 sequences.

Remark

Refer to riscv_conv_partial_fast_q31() for a faster but less precise implementation of this function.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written
- `firstIndex` – **[in]** is the first output sample to start with
- `numPoints` – **[in]** is the number of output points to be computed

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : requested subset is not in the range [0 srcALen+srcBLen-2]

riscv_status **riscv_conv_partial_q7**(const q7_t *pSrcA, uint32_t srcALen, const q7_t *pSrcB, uint32_t srcBLen, q7_t *pDst, uint32_t firstIndex, uint32_t numPoints)

Partial convolution of Q7 sequences.

Remark

Refer to riscv_conv_partial_opt_q7() for a faster implementation of this function.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written
- `firstIndex` – **[in]** is the first output sample to start with
- `numPoints` – **[in]** is the number of output points to be computed

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : requested subset is not in the range [0 srcALen+srcBLen-2]

Correlation

void **riscv_correlate_f16**(const float16_t *pSrcA, uint32_t srcALen, const float16_t *pSrcB, uint32_t srcBLen, float16_t *pDst)

void **riscv_correlate_f32**(const float32_t *pSrcA, uint32_t srcALen, const float32_t *pSrcB, uint32_t srcBLen, float32_t *pDst)

void **riscv_correlate_f64**(const float64_t *pSrcA, uint32_t srcALen, const float64_t *pSrcB, uint32_t srcBLen, float64_t *pDst)

void **riscv_correlate_fast_opt_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, q15_t *pScratch)

void **riscv_correlate_fast_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst)

void **riscv_correlate_fast_q31**(const q31_t *pSrcA, uint32_t srcALen, const q31_t *pSrcB, uint32_t srcBLen, q31_t *pDst)

void **riscv_correlate_opt_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, q15_t *pScratch)

void **riscv_correlate_opt_q7**(const q7_t *pSrcA, uint32_t srcALen, const q7_t *pSrcB, uint32_t srcBLen, q7_t *pDst, q15_t *pScratch1, q15_t *pScratch2)

void **riscv_correlate_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst)

void **riscv_correlate_q31**(const q31_t *pSrcA, uint32_t srcALen, const q31_t *pSrcB, uint32_t srcBLen, q31_t *pDst)

void **riscv_correlate_q7**(const q7_t *pSrcA, uint32_t srcALen, const q7_t *pSrcB, uint32_t srcBLen, q7_t *pDst)

group **Corr**

Correlation is a mathematical operation that is similar to convolution. As with convolution, correlation uses two signals to produce a third signal. The underlying algorithms in correlation and convolution are identical except that one of the inputs is flipped in convolution. Correlation is commonly used to measure the similarity between two signals. It has applications in pattern recognition, cryptanalysis, and searching. The NMSIS library provides correlation functions for Q7, Q15, Q31 and floating-point data types. Fast versions of the Q15 and Q31 functions are also provided.

In correlation, one of the signals is flipped in time

Algorithm Let `a[n]` and `b[n]` be sequences of length `srcALen` and `srcBLen` samples respectively. The convolution of the two signals is denoted by

$$c[n] = a[n] * b[n]$$

$$c[n] = a[n] * b[-n]$$

and this is mathematically defined as

$$c[n] = \sum_{k=0}^{srcALen} a[k]b[k-n]$$

The `pSrcA` points to the first input vector of length `srcALen` and `pSrcB` points to the second input vector of length `srcBLen`. The result `c[n]` is of length `2 * max(srcALen, srcBLen) - 1` and is defined over the interval `n=0, 1, 2, ..., (2 * max(srcALen, srcBLen) - 2)`. The output result is written to `pDst` and the calling function must allocate `2 * max(srcALen, srcBLen) - 1` words for the result.

Fixed-Point Behavior Correlation requires summing up a large number of intermediate products. As such, the Q7, Q15, and Q31 functions run a risk of overflow and saturation. Refer to the function specific documentation below for further details of the particular algorithm used.

Fast Versions Fast versions are supported for Q31 and Q15. Cycles for Fast versions are less compared to Q31 and Q15 of correlate and the design requires the input signals should be scaled down to avoid intermediate overflows.

Opt Versions Opt versions are supported for Q15 and Q7. Design uses internal scratch buffer for getting good optimisation. These versions are optimised in cycles and consumes more memory (Scratch memory) compared to Q15 and Q7 versions of correlate

Long versions: For convolution of long vectors, those functions are no more adapted and will be very slow. An implementation based upon FFTs should be used.

Note: The `pDst` should be initialized to all zeros before being used.

Functions

void **riscv_correlate_f16**(const float16_t *pSrcA, uint32_t srcALen, const float16_t *pSrcB, uint32_t srcBLen, float16_t *pDst)

Correlation of floating-point sequences.

Parameters

- **pSrcA** – **[in]** points to the first input sequence
- **srcALen** – **[in]** length of the first input sequence
- **pSrcB** – **[in]** points to the second input sequence
- **srcBLen** – **[in]** length of the second input sequence
- **pDst** – **[out]** points to the location where the output result is written. Length 2 * max(srcALen, srcBLen) - 1.

Returns none

void **riscv_correlate_f32**(const float32_t *pSrcA, uint32_t srcALen, const float32_t *pSrcB, uint32_t srcBLen, float32_t *pDst)

Correlation of floating-point sequences.

Parameters

- **pSrcA** – **[in]** points to the first input sequence
- **srcALen** – **[in]** length of the first input sequence
- **pSrcB** – **[in]** points to the second input sequence

- **srcBLen** – **[in]** length of the second input sequence
- **pDst** – **[out]** points to the location where the output result is written. Length 2 * max(srcALen, srcBLen) - 1.

Returns none

void **riscv_correlate_f64**(const float64_t *pSrcA, uint32_t srcALen, const float64_t *pSrcB, uint32_t srcBLen, float64_t *pDst)

Correlation of floating-point sequences.

Parameters

- **pSrcA** – **[in]** points to the first input sequence
- **srcALen** – **[in]** length of the first input sequence
- **pSrcB** – **[in]** points to the second input sequence
- **srcBLen** – **[in]** length of the second input sequence
- **pDst** – **[out]** points to the location where the output result is written. Length 2 * max(srcALen, srcBLen) - 1.

Returns none

void **riscv_correlate_fast_opt_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, q15_t *pScratch)

Correlation of Q15 sequences (fast version).

Remark

Refer to riscv_correlate_q15() for a slower implementation of this function which uses a 64-bit accumulator to avoid wrap around distortion.

Scaling and Overflow Behavior This fast version uses a 32-bit accumulator with 2.30 format. The accumulator maintains full precision of the intermediate multiplication results but provides only a single guard bit. There is no saturation on intermediate additions. Thus, if the accumulator overflows it wraps around and distorts the result. The input signals should be scaled down to avoid intermediate overflows. Scale down one of the inputs by 1/min(srcALen, srcBLen) to avoid overflow since a maximum of min(srcALen, srcBLen) number of additions is carried internally. The 2.30 accumulator is right shifted by 15 bits and then saturated to 1.15 format to yield the final result.

Parameters

- **pSrcA** – **[in]** points to the first input sequence
- **srcALen** – **[in]** length of the first input sequence
- **pSrcB** – **[in]** points to the second input sequence
- **srcBLen** – **[in]** length of the second input sequence.
- **pDst** – **[out]** points to the location where the output result is written. Length 2 * max(srcALen, srcBLen) - 1.
- **pScratch** – **[in]** points to scratch buffer of size max(srcALen, srcBLen) + 2*min(srcALen, srcBLen) - 2.

Returns none

void **riscv_correlate_fast_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst)

Correlation of Q15 sequences (fast version).

Remark

Refer to riscv_correlate_q15() for a slower implementation of this function which uses a 64-bit accumulator to avoid wrap around distortion.

Scaling and Overflow Behavior This fast version uses a 32-bit accumulator with 2.30 format. The accumulator maintains full precision of the intermediate multiplication results but provides only a single guard bit. There is no saturation on intermediate additions. Thus, if the accumulator overflows it wraps around and distorts the result. The input signals should be scaled down to avoid intermediate overflows. Scale down one of the inputs by 1/min(srcALen, srcBLen) to avoid overflow since a maximum of min(srcALen, srcBLen) number of additions is carried internally. The 2.30 accumulator is right shifted by 15 bits and then saturated to 1.15 format to yield the final result.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written. Length 2 * max(srcALen, srcBLen) - 1.

Returns none

void **riscv_correlate_fast_q31**(const q31_t *pSrcA, uint32_t srcALen, const q31_t *pSrcB, uint32_t srcBLen, q31_t *pDst)

Correlation of Q31 sequences (fast version).

Remark

Refer to riscv_correlate_q31() for a slower implementation of this function which uses 64-bit accumulation to provide higher precision.

Scaling and Overflow Behavior This function is optimized for speed at the expense of fixed-point precision and overflow protection. The result of each 1.31 x 1.31 multiplication is truncated to 2.30 format. These intermediate results are accumulated in a 32-bit register in 2.30 format. Finally, the accumulator is saturated and converted to a 1.31 result.

The fast version has the same overflow behavior as the standard version but provides less precision since it discards the low 32 bits of each multiplication result. In order to avoid overflows completely the input signals must be scaled down. The input signals should be scaled down to avoid intermediate overflows. Scale down one of the inputs by 1/min(srcALen, srcBLen)to avoid overflows since a maximum of min(srcALen, srcBLen) number of additions is carried internally.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written. Length 2 * max(srcALen, srcBLen) - 1.

Returns none

void **riscv_correlate_opt_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst, q15_t *pScratch)

Correlation of Q15 sequences.

Remark

Refer to riscv_correlate_fast_q15() for a faster but less precise version of this function.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. Both inputs are in 1.15 format and multiplications yield a 2.30 result. The 2.30 intermediate results are accumulated in a 64-bit accumulator in 34.30 format. This approach provides 33 guard bits and there is no risk of overflow. The 34.30 result is then truncated to 34.15 format by discarding the low 15 bits and then saturated to 1.15 format.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written. Length 2 * max(srcALen, srcBLen) - 1.
- `pScratch` – **[in]** points to scratch buffer of size max(srcALen, srcBLen) + 2*min(srcALen, srcBLen) - 2.

Returns none

void **riscv_correlate_opt_q7**(const q7_t *pSrcA, uint32_t srcALen, const q7_t *pSrcB, uint32_t srcBLen, q7_t *pDst, q15_t *pScratch1, q15_t *pScratch2)

Correlation of Q7 sequences.

Scaling and Overflow Behavior The function is implemented using a 32-bit internal accumulator. Both the inputs are represented in 1.7 format and multiplications yield a 2.14 result. The 2.14 intermediate results are accumulated in a 32-bit accumulator in 18.14 format. This approach provides 17 guard bits and there is no risk of overflow as long as `max(srcALen, srcBLen)<131072`. The 18.14 result is then truncated to 18.7 format by discarding the low 7 bits and then saturated to 1.7 format.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written. Length 2 * max(srcALen, srcBLen) - 1.
- `pScratch1` – **[in]** points to scratch buffer(of type q15_t) of size max(srcALen, srcBLen) + 2*min(srcALen, srcBLen) - 2.
- `pScratch2` – **[in]** points to scratch buffer (of type q15_t) of size min(srcALen, srcBLen).

Returns none

void **riscv_correlate_q15**(const q15_t *pSrcA, uint32_t srcALen, const q15_t *pSrcB, uint32_t srcBLen, q15_t *pDst)

Correlation of Q15 sequences.

Remark

Refer to riscv_correlate_fast_q15() for a faster but less precise version of this function.

Remark

Refer to riscv_correlate_opt_q15() for a faster implementation of this function using scratch buffers.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. Both inputs are in 1.15 format and multiplications yield a 2.30 result. The 2.30 intermediate results are accumulated in a 64-bit accumulator in 34.30 format. This approach provides 33 guard bits and there is no risk of overflow. The 34.30 result is then truncated to 34.15 format by discarding the low 15 bits and then saturated to 1.15 format.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written. Length 2 * max(srcALen, srcBLen) - 1.

Returns none

void **riscv_correlate_q31**(const q31_t *pSrcA, uint32_t srcALen, const q31_t *pSrcB, uint32_t srcBLen, q31_t *pDst)

Correlation of Q31 sequences.

Remark

Refer to riscv_correlate_fast_q31() for a faster but less precise implementation of this function.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The accumulator has a 2.62 format and maintains full precision of the intermediate multiplication results but provides only a single guard bit. There is no saturation on intermediate additions. Thus, if the accumulator overflows it wraps around and distorts the result. The input signals should be scaled down to avoid intermediate overflows. Scale down one of the inputs by 1/min(srcALen, srcBLen)to avoid overflows since a maximum of min(srcALen, srcBLen) number of additions is carried internally. The 2.62 accumulator is right shifted by 31 bits and saturated to 1.31 format to yield the final result.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence
- `pDst` – **[out]** points to the location where the output result is written. Length 2 * max(srcALen, srcBLen) - 1.

Returns none

void **riscv_correlate_q7**(const q7_t *pSrcA, uint32_t srcALen, const q7_t *pSrcB, uint32_t srcBLen, q7_t *pDst)

Correlation of Q7 sequences.

Remark

Refer to riscv_correlate_opt_q7() for a faster implementation of this function.

Scaling and Overflow Behavior The function is implemented using a 32-bit internal accumulator. Both the inputs are represented in 1.7 format and multiplications yield a 2.14 result. The 2.14 intermediate results are accumulated in a 32-bit accumulator in 18.14 format. This approach provides 17 guard bits and there is no risk of overflow as long as `max(srcALen, srcBLen)<131072`. The 18.14 result is then truncated to 18.7 format by discarding the low 7 bits and saturated to 1.7 format.

Parameters

- `pSrcA` – **[in]** points to the first input sequence
- `srcALen` – **[in]** length of the first input sequence
- `pSrcB` – **[in]** points to the second input sequence
- `srcBLen` – **[in]** length of the second input sequence

- **pDst** – **[out]** points to the location where the output result is written. Length 2 * max(srcALen, srcBLen) - 1.

Returns none

Finite Impulse Response (FIR) Decimator

void **riscv_fir_decimate_f32**(const riscv_fir_decimate_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_fir_decimate_fast_q15**(const riscv_fir_decimate_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_fir_decimate_fast_q31**(const riscv_fir_decimate_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

riscv_status **riscv_fir_decimate_init_f32**(riscv_fir_decimate_instance_f32 *S, uint16_t numTaps, uint8_t M, const float32_t *pCoeffs, float32_t *pState, uint32_t blockSize)

riscv_status **riscv_fir_decimate_init_q15**(riscv_fir_decimate_instance_q15 *S, uint16_t numTaps, uint8_t M, const q15_t *pCoeffs, q15_t *pState, uint32_t blockSize)

riscv_status **riscv_fir_decimate_init_q31**(riscv_fir_decimate_instance_q31 *S, uint16_t numTaps, uint8_t M, const q31_t *pCoeffs, q31_t *pState, uint32_t blockSize)

void **riscv_fir_decimate_q15**(const riscv_fir_decimate_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_fir_decimate_q31**(const riscv_fir_decimate_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

group `FIR_decimate`

These functions combine an FIR filter together with a decimator. They are used in multirate systems for reducing the sample rate of a signal without introducing aliasing distortion. Conceptually, the functions are equivalent to the block diagram below:

When decimating by a factor of `M`, the signal should be prefiltered by a lowpass filter with a normalized cutoff frequency of `1/M` in order to prevent aliasing distortion. The user of the function is responsible for providing the



filter coefficients.

The FIR decimator functions provided in the NMSIS DSP Library combine the FIR filter and the decimator in an efficient manner. Instead of calculating all of the FIR filter outputs and discarding `M-1` out of every `M`, only the samples output by the decimator are computed. The functions operate on blocks of input and output data. `pSrc` points to an array of `blockSize` input values and `pDst` points to an array of `blockSize/M` output values. In order to have an integer number of output samples `blockSize` must always be a multiple of the decimation factor `M`.

The library provides separate functions for Q15, Q31 and floating-point data types.

Algorithm: The FIR portion of the algorithm uses the standard form filter: where, `b[n]` are the filter coefficients.

The `pCoeffs` points to a coefficient array of size `numTaps`. Coefficients are stored in time reversed order.

`pState` points to a state array of size `numTaps + blockSize - 1`. Samples in the state buffer are stored in the order:

The state variables are updated after each block of data is processed, the coefficients are untouched.

Instance Structure The coefficients and state variables for a filter are stored together in an instance data structure. A separate instance structure must be defined for each filter. Coefficient arrays may be shared among several instances while state variable array should be allocated separately. There are separate instance structure declarations for each of the 3 supported data types.

Initialization Functions There is also an associated initialization function for each data type. The initialization function performs the following operations:

- Sets the values of the internal structure fields.
- Zeros out the values in the state buffer.
- Checks to make sure that the size of the input is a multiple of the decimation factor. To do this manually without calling the init function, assign the follow subfields of the instance structure: numTaps, pCoeffs, M (decimation factor), pState. Also set all of the values in pState to zero.

Use of the initialization function is optional. However, if the initialization function is used, then the instance structure cannot be placed into a const data section. To place an instance structure into a const data section, the instance structure must be manually initialized. The code below statically initializes each of the 3 different data type filter instance structures where `M` is the decimation factor; `numTaps` is the number of filter coefficients in the filter; `pCoeffs` is the address of the coefficient buffer; `pState` is the address of the state buffer. Be sure to set the values in the state buffer to zeros when doing static initialization.

Fixed-Point Behavior Care must be taken when using the fixed-point versions of the FIR decimate filter functions. In particular, the overflow and saturation behavior of the accumulator used in each function must be considered. Refer to the function specific documentation below for usage guidelines.

Functions

void **`riscv_fir_decimate_f32`**(const riscv_fir_decimate_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Processing function for floating-point FIR decimator.

Parameters

- **`S`** – **[in]** points to an instance of the floating-point FIR decimator structure
- **`pSrc`** – **[in]** points to the block of input data
- **`pDst`** – **[out]** points to the block of output data
- **`blockSize`** – **[in]** number of input samples to process

Returns none

void **`riscv_fir_decimate_fast_q15`**(const riscv_fir_decimate_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

Processing function for the Q15 FIR decimator (fast variant).

Processing function for the Q15 FIR decimator (fast variant) for RISC-V Core with DSP enabled.

Remark

Refer to riscv_fir_decimate_q15() for a slower implementation of this function which uses 64-bit accumulation to avoid wrap around distortion. Both the slow and the fast versions use the same instance structure. Use function riscv_fir_decimate_init_q15() to initialize the filter structure.

Scaling and Overflow Behavior This fast version uses a 32-bit accumulator with 2.30 format. The accumulator maintains full precision of the intermediate multiplication results but provides only a single guard bit. Thus, if the accumulator result overflows it wraps around and distorts the result. In order to avoid overflows completely the input signal must be scaled down by log2(numTaps) bits (log2 is read as log to the base 2). The 2.30 accumulator is then truncated to 2.15 format and saturated to yield the 1.15 result.

Parameters

- `S` – **[in]** points to an instance of the Q15 FIR decimator structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of input samples to process per call

Returns none

void **riscv_fir_decimate_fast_q31**(const riscv_fir_decimate_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

Processing function for the Q31 FIR decimator (fast variant).

Processing function for the Q31 FIR decimator (fast variant) for RISC-V Core with DSP enabled.

Remark

Refer to riscv_fir_decimate_q31() for a slower implementation of this function which uses a 64-bit accumulator to provide higher precision. Both the slow and the fast versions use the same instance structure. Use function riscv_fir_decimate_init_q31() to initialize the filter structure.

Scaling and Overflow Behavior This function is optimized for speed at the expense of fixed-point precision and overflow protection. The result of each 1.31 x 1.31 multiplication is truncated to 2.30 format. These intermediate results are added to a 2.30 accumulator. Finally, the accumulator is saturated and converted to a 1.31 result. The fast version has the same overflow behavior as the standard version and provides less precision since it discards the low 32 bits of each multiplication result. In order to avoid overflows completely the input signal must be scaled down by log2(numTaps) bits (where log2 is read as log to the base 2).

Parameters

- `S` – **[in]** points to an instance of the Q31 FIR decimator structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process

Returns none

riscv_status **riscv_fir_decimate_init_f32**(riscv_fir_decimate_instance_f32 *S, uint16_t numTaps, uint8_t M, const float32_t *pCoeffs, float32_t *pState, uint32_t blockSize)

Initialization function for the floating-point FIR decimator.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order:

`pState` points to the array of state variables. `pState` is of length `numTaps+blockSize-1` words where `blockSize` is the number of input samples passed to `riscv_fir_decimate_f32()`. `M` is the decimation factor.

Parameters

- **S** – **[inout]** points to an instance of the floating-point FIR decimator structure
- **numTaps** – **[in]** number of coefficients in the filter
- **M** – **[in]** decimation factor
- **pCoeffs** – **[in]** points to the filter coefficients
- **pState** – **[in]** points to the state buffer
- **blockSize** – **[in]** number of input samples to process per call

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_LENGTH_ERROR : `blockSize` is not a multiple of `M`

riscv_status **riscv_fir_decimate_init_q15**(riscv_fir_decimate_instance_q15 *S, uint16_t numTaps, uint8_t M, const q15_t *pCoeffs, q15_t *pState, uint32_t blockSize)

Initialization function for the Q15 FIR decimator.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order:

`pState` points to the array of state variables. `pState` is of length `numTaps+blockSize-1` words where `blockSize` is the number of input samples to the call `riscv_fir_decimate_q15()`. `M` is the decimation factor.

Parameters

- **S** – **[inout]** points to an instance of the Q15 FIR decimator structure
- **numTaps** – **[in]** number of coefficients in the filter
- **M** – **[in]** decimation factor
- **pCoeffs** – **[in]** points to the filter coefficients
- **pState** – **[in]** points to the state buffer
- **blockSize** – **[in]** number of input samples to process

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful

- RISCV_MATH_LENGTH_ERROR : `blockSize` is not a multiple of `M`

riscv_status **riscv_fir_decimate_init_q31**(riscv_fir_decimate_instance_q31 *S, uint16_t numTaps, uint8_t M, const q31_t *pCoeffs, q31_t *pState, uint32_t blockSize)

Initialization function for the Q31 FIR decimator.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order:

`pState` points to the array of state variables. `pState` is of length `numTaps+blockSize-1` words where `blockSize` is the number of input samples passed to `riscv_fir_decimate_q31()`. `M` is the decimation factor.

Parameters

- **S** – **[inout]** points to an instance of the Q31 FIR decimator structure
- **numTaps** – **[in]** number of coefficients in the filter
- **M** – **[in]** decimation factor
- **pCoeffs** – **[in]** points to the filter coefficients
- **pState** – **[in]** points to the state buffer
- **blockSize** – **[in]** number of input samples to process

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_LENGTH_ERROR : `blockSize` is not a multiple of `M`

void **riscv_fir_decimate_q15**(const riscv_fir_decimate_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

Processing function for the Q15 FIR decimator.

Remark

Refer to riscv_fir_decimate_fast_q15() for a faster but less precise implementation of this function.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. Both coefficients and state variables are represented in 1.15 format and multiplications yield a 2.30 result. The 2.30 intermediate results are accumulated in a 64-bit accumulator in 34.30 format. There is no risk of internal overflow with this approach and the full precision of intermediate multiplications is preserved. After all additions have been performed, the accumulator is truncated to 34.15 format by discarding low 15 bits. Lastly, the accumulator is saturated to yield a result in 1.15 format.

Parameters

- **S** – **[in]** points to an instance of the Q15 FIR decimator structure
- **pSrc** – **[in]** points to the block of input data
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of input samples to process per call

Returns none

void **riscv_fir_decimate_q31**(const riscv_fir_decimate_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

Processing function for the Q31 FIR decimator.

Remark

Refer to riscv_fir_decimate_fast_q31() for a faster but less precise implementation of this function.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The accumulator has a 2.62 format and maintains full precision of the intermediate multiplication results but provides only a single guard bit. Thus, if the accumulator result overflows it wraps around rather than clip. In order to avoid overflows completely the input signal must be scaled down by log2(numTaps) bits (where log2 is read as log to the base 2). After all multiply-accumulates are performed, the 2.62 accumulator is truncated to 1.32 format and then saturated to 1.31 format.

Parameters

- **S** – **[in]** points to an instance of the Q31 FIR decimator structure
- **pSrc** – **[in]** points to the block of input data
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of input samples to process

Returns none

Finite Impulse Response (FIR) Filters

void **riscv_fir_f16**(const riscv_fir_instance_f16 *S, const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

void **riscv_fir_f32**(const riscv_fir_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_fir_f64**(const riscv_fir_instance_f64 *S, const float64_t *pSrc, float64_t *pDst, uint32_t blockSize)

void **riscv_fir_fast_q15**(const riscv_fir_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_fir_fast_q31**(const riscv_fir_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

void **riscv_fir_init_f16**(riscv_fir_instance_f16 *S, uint16_t numTaps, const float16_t *pCoeffs, float16_t *pState, uint32_t blockSize)

void **riscv_fir_init_f32**(riscv_fir_instance_f32 *S, uint16_t numTaps, const float32_t *pCoeffs, float32_t *pState, uint32_t blockSize)

void **riscv_fir_init_f64**(riscv_fir_instance_f64 *S, uint16_t numTaps, const float64_t *pCoeffs, float64_t *pState, uint32_t blockSize)

riscv_status **riscv_fir_init_q15**(riscv_fir_instance_q15 *S, uint16_t numTaps, const q15_t *pCoeffs, q15_t *pState, uint32_t blockSize) void **riscv_fir_init_q31**(riscv_fir_instance_q31 *S, uint16_t numTaps, const q31_t *pCoeffs, q31_t *pState, uint32_t blockSize)

void **riscv_fir_init_q7**(riscv_fir_instance_q7 *S, uint16_t numTaps, const q7_t *pCoeffs, q7_t *pState, uint32_t blockSize)

void **riscv_fir_q15**(const riscv_fir_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_fir_q31**(const riscv_fir_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

void **riscv_fir_q7**(const riscv_fir_instance_q7 *S, const q7_t *pSrc, q7_t *pDst, uint32_t blockSize)

group **FIR**

This set of functions implements Finite Impulse Response (FIR) filters for Q7, Q15, Q31, and floating-point data types. Fast versions of Q15 and Q31 are also provided. The functions operate on blocks of input and output data and each call to the function processes `blockSize` samples through the filter. `pSrc` and `pDst` points to input and output arrays containing `blockSize` values.

The array length L must be a multiple of x. L = x * a :

- x is 4 for f32
- x is 4 for q31
- x is 4 for f16 (so managed like the f32 version and not like the q15 one)
- x is 8 for q15
- x is 16 for q7

Algorithm The FIR filter algorithm is based upon a sequence of multiply-accumulate (MAC) operations. Each filter coefficient `b[n]` is multiplied by a state variable which equals a previous input sample `x[n]`.



`pCoeffs` points to a coefficient array of size `numTaps`. Coefficients are stored in time reversed order.

`pState` points to a state array of size `numTaps + blockSize - 1`. Samples in the state buffer are stored in the following order.

Note that the length of the state buffer exceeds the length of the coefficient array by `blockSize-1`. The increased state buffer length allows circular addressing, which is traditionally used in the FIR filters, to be avoided and yields a significant speed improvement. The state variables are updated after each block of data is processed; the coefficients are untouched.

Instance Structure The coefficients and state variables for a filter are stored together in an instance data structure. A separate instance structure must be defined for each filter. Coefficient arrays may be shared among several instances while state variable arrays cannot be shared. There are separate instance structure declarations for each of the 4 supported data types.

Initialization Functions There is also an associated initialization function for each data type. The initialization function performs the following operations:

- Sets the values of the internal structure fields.
- Zeros out the values in the state buffer. To do this manually without calling the init function, assign the follow subfields of the instance structure: numTaps, pCoeffs, pState. Also set all of the values in pState to zero.

Use of the initialization function is optional. However, if the initialization function is used, then the instance structure cannot be placed into a const data section. To place an instance structure into a const data section, the instance structure must be manually initialized. Set the values in the state buffer to zeros before static initialization. The code below statically initializes each of the 4 different data type filter instance structures where `numTaps` is the number of filter coefficients in the filter; `pState` is the address of the state buffer; `pCoeffs` is the address of the coefficient buffer.

Initialization of Helium version For Helium version the array of coefficients must be padded with zero to contain a full number of lanes.

The additional coefficients (x * a - numTaps) must be set to 0. numTaps is still set to its right value in the init function. It means that the implementation may require to read more coefficients due to the vectorization and to avoid having to manage too many different cases in the code.

Helium state buffer The state buffer must contain some additional temporary data used during the computation but which is not the state of the FIR. The first A samples are temporary data. The remaining samples are the state of the FIR filter.

So the state buffer has size `numTaps + A + blockSize - 1` :

- A is blockSize for f32
- A is 8*ceil(blockSize/8) for f16
- A is 8*ceil(blockSize/4) for q31
- A is 0 for other datatypes (q15 and q7)

Fixed-Point Behavior Care must be taken when using the fixed-point versions of the FIR filter functions. In particular, the overflow and saturation behavior of the accumulator used in each function must be considered. Refer to the function specific documentation below for usage guidelines.

Functions

void **riscv_fir_f16**(const riscv_fir_instance_f16 *S, const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

Processing function for floating-point FIR filter.

Processing function for the floating-point FIR filter.

Parameters

- **S** – **[in]** points to an instance of the floating-point FIR filter structure
- **pSrc** – **[in]** points to the block of input data
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of samples to process

Returns none

void **riscv_fir_f32**(const riscv_fir_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Processing function for floating-point FIR filter.

Processing function for the floating-point FIR filter.

Parameters

- **S** – **[in]** points to an instance of the floating-point FIR filter structure
- **pSrc** – **[in]** points to the block of input data
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of samples to process

Returns none

void **riscv_fir_f64**(const riscv_fir_instance_f64 *S, const float64_t *pSrc, float64_t *pDst, uint32_t blockSize)

Processing function for floating-point FIR filter.

Processing function for the floating-point FIR filter.

Parameters

- **S** – **[in]** points to an instance of the floating-point FIR filter structure
- **pSrc** – **[in]** points to the block of input data
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of samples to process

Returns none

void **riscv_fir_fast_q15**(const riscv_fir_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

Processing function for the Q15 FIR filter (fast version).

Processing function for the fast Q15 FIR filter (fast version).

Remark

Refer to riscv_fir_q15() for a slower implementation of this function which uses 64-bit accumulation to avoid wrap around distortion. Both the slow and the fast versions use the same instance structure. Use function riscv_fir_init_q15() to initialize the filter structure.

Scaling and Overflow Behavior This fast version uses a 32-bit accumulator with 2.30 format. The accumulator maintains full precision of the intermediate multiplication results but provides only a single guard bit. Thus, if the accumulator result overflows it wraps around and distorts the result. In order to avoid overflows completely the input signal must be scaled down by log2(numTaps) bits. The 2.30 accumulator is then truncated to 2.15 format and saturated to yield the 1.15 result.

Parameters

- `S` – **[in]** points to an instance of the Q15 FIR filter structure
- **`pSrc`** – **[in]** points to the block of input data
- **`pDst`** – **[out]** points to the block of output data
- **`blockSize`** – **[in]** number of samples to process

Returns none

void **`riscv_fir_fast_q31`**(const riscv_fir_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

Processing function for the Q31 FIR filter (fast version).

Processing function for the fast Q31 FIR filter (fast version).

Remark

Refer to riscv_fir_q31() for a slower implementation of this function which uses a 64-bit accumulator to provide higher precision. Both the slow and the fast versions use the same instance structure. Use function riscv_fir_init_q31() to initialize the filter structure.

Scaling and Overflow Behavior This function is optimized for speed at the expense of fixed-point precision and overflow protection. The result of each 1.31 x 1.31 multiplication is truncated to 2.30 format. These intermediate results are added to a 2.30 accumulator. Finally, the accumulator is saturated and converted to a 1.31 result. The fast version has the same overflow behavior as the standard version and provides less precision since it discards the low 32 bits of each multiplication result. In order to avoid overflows completely the input signal must be scaled down by log2(numTaps) bits.

Parameters

- `S` – **[in]** points to an instance of the Q31 structure
- **`pSrc`** – **[in]** points to the block of input data
- **`pDst`** – **[out]** points to the block of output data
- **`blockSize`** – **[in]** number of samples to process

Returns none

void **riscv_fir_init_f16**(riscv_fir_instance_f16 *S, uint16_t numTaps, const float16_t *pCoeffs, float16_t *pState, uint32_t blockSize)

Initialization function for the floating-point FIR filter.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order:

`pState` points to the array of state variables. `pState` is of length `numTaps+blockSize-1` samples (except for Helium - see below), where `blockSize` is the number of input samples processed by each call to `riscv_fir_f16()`.

Initialization of Helium version For Helium version the array of coefficients must be a multiple of 4 (4a) even if less then 4a coefficients are defined in the FIR. The additional coefficients (4a - numTaps) must be set to 0. numTaps is still set to its right value in the init function. It means that the implementation may require to read more coefficients due to the vectorization and to avoid having to manage too many different cases in the code.

Helium state buffer The state buffer must contain some additional temporary data used during the computation but which is not the state of the FIR. The first 8*ceil(blockSize/8) samples are temporary data. The remaining samples are the state of the FIR filter. So the state buffer has size `numTaps + 8*ceil(blockSize/8) + blockSize - 1`

Parameters

- `S` – **[inout]** points to an instance of the floating-point FIR filter structure
- `numTaps` – **[in]** number of filter coefficients in the filter
- `pCoeffs` – **[in]** points to the filter coefficients buffer
- `pState` – **[in]** points to the state buffer
- `blockSize` – **[in]** number of samples processed per call

Returns none

void **riscv_fir_init_f32**(riscv_fir_instance_f32 *S, uint16_t numTaps, const float32_t *pCoeffs, float32_t *pState, uint32_t blockSize)

Initialization function for the floating-point FIR filter.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order:

`pState` points to the array of state variables and some working memory for the Helium version. `pState` is of length `numTaps+blockSize-1` samples (except for Helium - see below), where `blockSize` is the number of input samples processed by each call to `riscv_fir_f32()`.

Initialization of Helium version For Helium version the array of coefficients must be a multiple of 4 (4a) even if less then 4a coefficients are defined in the FIR. The additional coefficients (4a - numTaps) must be set to 0. numTaps is still set to its right value in the init function. It means that the implementation may require to read more coefficients due to the vectorization and to avoid having to manage too many different cases in the code.

Helium state buffer The state buffer must contain some additional temporary data used during the computation but which is not the state of the FIR. The first blockSize samples are temporary data. The remaining samples are the state of the FIR filter. So the state buffer has size `numTaps + 2 * blockSize - 1`

Parameters

- `S` – **[inout]** points to an instance of the floating-point FIR filter structure
- `numTaps` – **[in]** number of filter coefficients in the filter
- `pCoeffs` – **[in]** points to the filter coefficients buffer
- `pState` – **[in]** points to the state buffer
- `blockSize` – **[in]** number of samples processed per call

Returns none

void **riscv_fir_init_f64**(riscv_fir_instance_f64 *S, uint16_t numTaps, const float64_t *pCoeffs, float64_t *pState, uint32_t blockSize)

Initialization function for the floating-point FIR filter.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order:

`pState` points to the array of state variables. `pState` is of length `numTaps+blockSize-1` samples, where `blockSize` is the number of input samples processed by each call to `riscv_fir_f64()`.

There is no Helium version of the fir F64.

Parameters

- `S` – **[inout]** points to an instance of the floating-point FIR filter structure
- `numTaps` – **[in]** number of filter coefficients in the filter
- `pCoeffs` – **[in]** points to the filter coefficients buffer
- `pState` – **[in]** points to the state buffer
- `blockSize` – **[in]** number of samples processed per call

Returns none

riscv_status **riscv_fir_init_q15**(riscv_fir_instance_q15 *S, uint16_t numTaps, const q15_t *pCoeffs, q15_t *pState, uint32_t blockSize)

Initialization function for the Q15 FIR filter.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order: Note that `numTaps` must be even and greater than or equal to 4. To implement an odd length filter simply increase `numTaps` by 1 and set the last coefficient to zero. For example, to implement a filter with `numTaps=3` and coefficients set `numTaps=4` and use the coefficients: Similarly, to implement a two point filter set `numTaps=4` and use the coefficients: `pState` points to the array of state variables. `pState` is of length `numTaps+blockSize`, when running on RISC-V Core with DSP enabled and is of length `numTaps+blockSize-1`, when running on RISC-V Core without DSP where `blockSize` is the number of input samples processed by each call to `riscv_fir_q15()`.

Initialization of Helium version For Helium version the array of coefficients must be a multiple of 8 (8a) even if less then 8a coefficients are defined in the FIR. The additional coefficients (8a - numTaps) must be set to 0. numTaps is still set to its right value in the init function. It means that the implementation may require to read more coefficients due to the vectorization and to avoid having to manage too many different cases in the code.

Parameters

- `S` – **[inout]** points to an instance of the Q15 FIR filter structure.

- **numTaps** – **[in]** number of filter coefficients in the filter. Must be even and greater than or equal to 4.
- **pCoeffs** – **[in]** points to the filter coefficients buffer.
- **pState** – **[in]** points to the state buffer.
- **blockSize** – **[in]** number of samples processed per call.

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `numTaps` is not greater than or equal to 4 and even

void **riscv_fir_init_q31**(riscv_fir_instance_q31 *S, uint16_t numTaps, const q31_t *pCoeffs, q31_t *pState, uint32_t blockSize)

Initialization function for the Q31 FIR filter.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order: `pState` points to the array of state variables. `pState` is of length `numTaps+blockSize-1` samples (except for Helium - see below), where `blockSize` is the number of input samples processed by each call to `riscv_fir_q31()`.

Initialization of Helium version For Helium version the array of coefficients must be a multiple of 4 (4a) even if less then 4a coefficients are defined in the FIR. The additional coefficients (4a - numTaps) must be set to 0. numTaps is still set to its right value in the init function. It means that the implementation may require to read more coefficients due to the vectorization and to avoid having to manage too many different cases in the code.

Helium state buffer The state buffer must contain some additional temporary data used during the computation but which is not the state of the FIR. The first 2*4*ceil(blockSize/4) samples are temporary data. The remaining samples are the state of the FIR filter. So the state buffer has size `numTaps + 8*ceil(blockSize/4) + blockSize - 1`

Parameters

- **S** – **[inout]** points to an instance of the Q31 FIR filter structure
- **numTaps** – **[in]** number of filter coefficients in the filter
- **pCoeffs** – **[in]** points to the filter coefficients buffer
- **pState** – **[in]** points to the state buffer
- **blockSize** – **[in]** number of samples processed

Returns none

void **riscv_fir_init_q7**(riscv_fir_instance_q7 *S, uint16_t numTaps, const q7_t *pCoeffs, q7_t *pState, uint32_t blockSize)

Initialization function for the Q7 FIR filter.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order:

`pState` points to the array of state variables. `pState` is of length `numTaps+blockSize-1` samples, where `blockSize` is the number of input samples processed by each call to `riscv_fir_q7()`.

Initialization of Helium version For Helium version the array of coefficients must be a multiple of 16 (16a) even if less then 16a coefficients are defined in the FIR. The additional coefficients (16a - numTaps) must be set to 0. numTaps is still set to its right value in the init function. It means that the implementation may require to read more coefficients due to the vectorization and to avoid having to manage too many different cases in the code.

Parameters

- `S` – **[inout]** points to an instance of the Q7 FIR filter structure
- `numTaps` – **[in]** number of filter coefficients in the filter
- `pCoeffs` – **[in]** points to the filter coefficients buffer
- `pState` – **[in]** points to the state buffer
- `blockSize` – **[in]** number of samples processed

Returns none

void **riscv_fir_q15**(const riscv_fir_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

Processing function for the Q15 FIR filter.

Remark

Refer to riscv_fir_fast_q15() for a faster but less precise implementation of this function.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. Both coefficients and state variables are represented in 1.15 format and multiplications yield a 2.30 result. The 2.30 intermediate results are accumulated in a 64-bit accumulator in 34.30 format. There is no risk of internal overflow with this approach and the full precision of intermediate multiplications is preserved. After all additions have been performed, the accumulator is truncated to 34.15 format by discarding low 15 bits. Lastly, the accumulator is saturated to yield a result in 1.15 format.

Parameters

- `S` – **[in]** points to an instance of the Q15 FIR filter structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process

Returns none

void **riscv_fir_q31**(const riscv_fir_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

Processing function for Q31 FIR filter.

Processing function for the Q31 FIR filter.

Remark

Refer to riscv_fir_fast_q31() for a faster but less precise implementation of this filter.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The accumulator has a 2.62 format and maintains full precision of the intermediate multiplication results but provides only a single guard bit. Thus, if the accumulator result overflows it wraps around rather than clip. In order to avoid overflows completely the input signal must be scaled down by log2(numTaps) bits. After all multiply-accumulates are performed, the 2.62 accumulator is right shifted by 31 bits and saturated to 1.31 format to yield the final result.

Parameters

- `S` – **[in]** points to an instance of the Q31 FIR filter structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process

Returns none

void **riscv_fir_q7**(const riscv_fir_instance_q7 *S, const q7_t *pSrc, q7_t *pDst, uint32_t blockSize)

Processing function for Q7 FIR filter.

Processing function for the Q7 FIR filter.

Scaling and Overflow Behavior The function is implemented using a 32-bit internal accumulator. Both coefficients and state variables are represented in 1.7 format and multiplications yield a 2.14 result. The 2.14 intermediate results are accumulated in a 32-bit accumulator in 18.14 format. There is no risk of internal overflow with this approach and the full precision of intermediate multiplications is preserved. The accumulator is converted to 18.7 format by discarding the low 7 bits. Finally, the result is truncated to 1.7 format.

Parameters

- `S` – **[in]** points to an instance of the Q7 FIR filter structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process

Returns none

Finite Impulse Response (FIR) Lattice Filters

void **riscv_fir_lattice_f32**(const riscv_fir_lattice_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_fir_lattice_init_f32**(riscv_fir_lattice_instance_f32 *S, uint16_t numStages, const float32_t *pCoeffs, float32_t *pState)

void **riscv_fir_lattice_init_q15**(riscv_fir_lattice_instance_q15 *S, uint16_t numStages, const q15_t *pCoeffs, q15_t *pState)

void **riscv_fir_lattice_init_q31**(riscv_fir_lattice_instance_q31 *S, uint16_t numStages, const q31_t *pCoeffs, q31_t *pState) void **riscv_fir_lattice_q15**(const riscv_fir_lattice_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_fir_lattice_q31**(const riscv_fir_lattice_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

group **FIR_Lattice**

Deprecated:

Those functions are no more tested nor maintained and will be removed in a future version.

This set of functions implements Finite Impulse Response (FIR) lattice filters for Q15, Q31 and floating-point data types. Lattice filters are used in a variety of adaptive filter applications. The filter structure is feedforward and the net impulse response is finite length. The functions operate on blocks of input and output data and each call to the function processes `blockSize` samples through the filter. `pSrc` and `pDst` point to input and output arrays containing `blockSize` values.

Algorithm

The following difference equation is implemented:



`pCoeffs` points to tha array of reflection coefficients of size `numStages`. Reflection Coefficients are stored in the following order.

where M is number of stages

`pState` points to a state array of size `numStages`. The state variables (g values) hold previous inputs and are stored in the following order. The state variables are updated after each block of data is processed; the coefficients are untouched.

Instance Structure The coefficients and state variables for a filter are stored together in an instance data structure. A separate instance structure must be defined for each filter. Coefficient arrays may be shared among several instances while state variable arrays cannot be shared. There are separate instance structure declarations for each of the 3 supported data types.

Initialization Functions There is also an associated initialization function for each data type. The initialization function performs the following operations:

- Sets the values of the internal structure fields.
- Zeros out the values in the state buffer. To do this manually without calling the init function, assign the follow subfields of the instance structure: numStages, pCoeffs, pState. Also set all of the values in pState to zero.

Use of the initialization function is optional. However, if the initialization function is used, then the instance structure cannot be placed into a const data section. To place an instance structure into a const data section, the instance structure must be manually initialized. Set the values in the state buffer to zeros and then manually initialize the instance structure as follows:

where `numStages` is the number of stages in the filter; `pState` is the address of the state buffer; `pCoeffs` is the address of the coefficient buffer.

Fixed-Point Behavior Care must be taken when using the fixed-point versions of the FIR Lattice filter functions. In particular, the overflow and saturation behavior of the accumulator used in each function must be considered. Refer to the function specific documentation below for usage guidelines.

Functions

void **riscv_fir_lattice_f32**(const riscv_fir_lattice_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Processing function for the floating-point FIR lattice filter.

Parameters

- **S** – **[in]** points to an instance of the floating-point FIR lattice structure
- **pSrc** – **[in]** points to the block of input data
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of samples to process

Returns none

void **riscv_fir_lattice_init_f32**(riscv_fir_lattice_instance_f32 *S, uint16_t numStages, const float32_t *pCoeffs, float32_t *pState)

Initialization function for the floating-point FIR lattice filter.

Parameters

- **S** – **[in]** points to an instance of the floating-point FIR lattice structure
- **numStages** – **[in]** number of filter stages
- **pCoeffs** – **[in]** points to the coefficient buffer. The array is of length numStages
- **pState** – **[in]** points to the state buffer. The array is of length numStages

Returns none

void **riscv_fir_lattice_init_q15**(riscv_fir_lattice_instance_q15 *S, uint16_t numStages, const q15_t *pCoeffs, q15_t *pState)

Initialization function for the Q15 FIR lattice filter.

Parameters

- **S** – **[in]** points to an instance of the Q15 FIR lattice structure
- **numStages** – **[in]** number of filter stages
- **pCoeffs** – **[in]** points to the coefficient buffer. The array is of length numStages
- **pState** – **[in]** points to the state buffer. The array is of length numStages

Returns none

void **riscv_fir_lattice_init_q31**(riscv_fir_lattice_instance_q31 *S, uint16_t numStages, const q31_t *pCoeffs, q31_t *pState)

Initialization function for the Q31 FIR lattice filter.

Parameters

- **S** – **[in]** points to an instance of the Q31 FIR lattice structure

- **numStages** – **[in]** number of filter stages
- **pCoeffs** – **[in]** points to the coefficient buffer. The array is of length numStages
- **pState** – **[in]** points to the state buffer. The array is of length numStages

Returns none

void **riscv_fir_lattice_q15**(const riscv_fir_lattice_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

Processing function for Q15 FIR lattice filter.

Processing function for the Q15 FIR lattice filter.

Parameters

- **S** – **[in]** points to an instance of the Q15 FIR lattice structure
- **pSrc** – **[in]** points to the block of input data
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of samples to process

Returns none

void **riscv_fir_lattice_q31**(const riscv_fir_lattice_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

Processing function for the Q31 FIR lattice filter.

Scaling and Overflow Behavior In order to avoid overflows the input signal must be scaled down by 2*log2(numStages) bits.

Parameters

- **S** – **[in]** points to an instance of the Q31 FIR lattice structure
- **pSrc** – **[in]** points to the block of input data
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of samples to process

Returns none

Finite Impulse Response (FIR) Sparse Filters

void **riscv_fir_sparse_f32**(riscv_fir_sparse_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, float32_t *pScratchIn, uint32_t blockSize)

void **riscv_fir_sparse_init_f32**(riscv_fir_sparse_instance_f32 *S, uint16_t numTaps, const float32_t *pCoeffs, float32_t *pState, int32_t *pTapDelay, uint16_t maxDelay, uint32_t blockSize)

void **riscv_fir_sparse_init_q15**(riscv_fir_sparse_instance_q15 *S, uint16_t numTaps, const q15_t *pCoeffs, q15_t *pState, int32_t *pTapDelay, uint16_t maxDelay, uint32_t blockSize)

void **riscv_fir_sparse_init_q31**(riscv_fir_sparse_instance_q31 *S, uint16_t numTaps, const q31_t *pCoeffs, q31_t *pState, int32_t *pTapDelay, uint16_t maxDelay, uint32_t blockSize) void **riscv_fir_sparse_init_q7**(riscv_fir_sparse_instance_q7 *S, uint16_t numTaps, const q7_t *pCoeffs, q7_t *pState, int32_t *pTapDelay, uint16_t maxDelay, uint32_t blockSize)

void **riscv_fir_sparse_q15**(riscv_fir_sparse_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, q15_t *pScratchIn, q31_t *pScratchOut, uint32_t blockSize)

void **riscv_fir_sparse_q31**(riscv_fir_sparse_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, q31_t *pScratchIn, uint32_t blockSize)

void **riscv_fir_sparse_q7**(riscv_fir_sparse_instance_q7 *S, const q7_t *pSrc, q7_t *pDst, q7_t *pScratchIn, q31_t *pScratchOut, uint32_t blockSize)

group **FIR_Sparse**

Deprecated:

Those functions are no more tested nor maintained and will be removed in a future version.

This group of functions implements sparse FIR filters. Sparse FIR filters are equivalent to standard FIR filters except that most of the coefficients are equal to zero. Sparse filters are used for simulating reflections in communications and audio applications.

There are separate functions for Q7, Q15, Q31, and floating-point data types. The functions operate on blocks of input and output data and each call to the function processes `blockSize` samples through the filter. `pSrc` and `pDst` points to input and output arrays respectively containing `blockSize` values.

Algorithm The sparse filter instant structure contains an array of tap indices `pTapDelay` which specifies the locations of the non-zero coefficients. This is in addition to the coefficient array `b`. The implementation essentially skips the multiplications by zero and leads to an efficient realization.



`pCoeffs` points to a coefficient array of size `numTaps`; `pTapDelay` points to an array of nonzero indices and is also of size `numTaps`; `pState` points to a state array of size `maxDelay + blockSize`, where `maxDelay` is the largest offset value that is ever used in the `pTapDelay` array. Some of the processing functions also require temporary working buffers.

Instance Structure The coefficients and state variables for a filter are stored together in an instance data structure. A separate instance structure must be defined for each filter. Coefficient and offset arrays may be shared among several instances while state variable arrays cannot be shared. There are separate instance structure declarations for each of the 4 supported data types.

Initialization Functions There is also an associated initialization function for each data type. The initialization function performs the following operations:

- Sets the values of the internal structure fields.
- Zeros out the values in the state buffer. To do this manually without calling the init function, assign the follow subfields of the instance structure: numTaps, pCoeffs, pTapDelay, maxDelay, stateIndex, pState. Also set all of the values in pState to zero.

Use of the initialization function is optional. However, if the initialization function is used, then the instance structure cannot be placed into a const data section. To place an instance structure into a const data section, the instance structure must be manually initialized. Set the values in the state buffer to zeros before static initialization. The code below statically initializes each of the 4 different data type filter instance structures

Fixed-Point Behavior Care must be taken when using the fixed-point versions of the sparse FIR filter functions. In particular, the overflow and saturation behavior of the accumulator used in each function must be considered. Refer to the function specific documentation below for usage guidelines.

Functions

void **riscv_fir_sparse_f32**(riscv_fir_sparse_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, float32_t *pScratchIn, uint32_t blockSize)

Processing function for the floating-point sparse FIR filter.

Parameters

- `S` – **[in]** points to an instance of the floating-point sparse FIR structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `pScratchIn` – **[in]** points to a temporary buffer of size blockSize
- `blockSize` – **[in]** number of input samples to process

Returns none

void **riscv_fir_sparse_init_f32**(riscv_fir_sparse_instance_f32 *S, uint16_t numTaps, const float32_t *pCoeffs, float32_t *pState, int32_t *pTapDelay, uint16_t maxDelay, uint32_t blockSize)

Initialization function for the floating-point sparse FIR filter.

Details `pCoeffs` holds the filter coefficients and has length `numTaps`. `pState` holds the filter's state variables and must be of length `maxDelay + blockSize`, where `maxDelay` is the maximum number of delay line values. `blockSize` is the number of samples processed by the `riscv_fir_sparse_f32()` function.

Parameters

- `S` – **[inout]** points to an instance of the floating-point sparse FIR structure
- `numTaps` – **[in]** number of nonzero coefficients in the filter
- `pCoeffs` – **[in]** points to the array of filter coefficients
- `pState` – **[in]** points to the state buffer

- `pTapDelay` – **[in]** points to the array of offset times
- `maxDelay` – **[in]** maximum offset time supported
- `blockSize` – **[in]** number of samples that will be processed per block

Returns none

void **riscv_fir_sparse_init_q15**(riscv_fir_sparse_instance_q15 *S, uint16_t numTaps, const q15_t *pCoeffs, q15_t *pState, int32_t *pTapDelay, uint16_t maxDelay, uint32_t blockSize)

Initialization function for the Q15 sparse FIR filter.

Details `pCoeffs` holds the filter coefficients and has length `numTaps`. `pState` holds the filter's state variables and must be of length `maxDelay + blockSize`, where `maxDelay` is the maximum number of delay line values. `blockSize` is the number of words processed by `riscv_fir_sparse_q15()` function.

Parameters

- `S` – **[inout]** points to an instance of the Q15 sparse FIR structure
- `numTaps` – **[in]** number of nonzero coefficients in the filter
- `pCoeffs` – **[in]** points to the array of filter coefficients
- `pState` – **[in]** points to the state buffer
- `pTapDelay` – **[in]** points to the array of offset times
- `maxDelay` – **[in]** maximum offset time supported
- `blockSize` – **[in]** number of samples that will be processed per block

Returns none

void **riscv_fir_sparse_init_q31**(riscv_fir_sparse_instance_q31 *S, uint16_t numTaps, const q31_t *pCoeffs, q31_t *pState, int32_t *pTapDelay, uint16_t maxDelay, uint32_t blockSize)

Initialization function for the Q31 sparse FIR filter.

Details `pCoeffs` holds the filter coefficients and has length `numTaps`. `pState` holds the filter's state variables and must be of length `maxDelay + blockSize`, where `maxDelay` is the maximum number of delay line values. `blockSize` is the number of words processed by `riscv_fir_sparse_q31()` function.

Parameters

- `S` – **[inout]** points to an instance of the Q31 sparse FIR structure
- `numTaps` – **[in]** number of nonzero coefficients in the filter
- `pCoeffs` – **[in]** points to the array of filter coefficients
- `pState` – **[in]** points to the state buffer
- `pTapDelay` – **[in]** points to the array of offset times
- `maxDelay` – **[in]** maximum offset time supported

- `blockSize` – **[in]** number of samples that will be processed per block

Returns none

void **riscv_fir_sparse_init_q7**(riscv_fir_sparse_instance_q7 *S, uint16_t numTaps, const q7_t *pCoeffs, q7_t *pState, int32_t *pTapDelay, uint16_t maxDelay, uint32_t blockSize)

Initialization function for the Q7 sparse FIR filter.

Details `pCoeffs` holds the filter coefficients and has length `numTaps`. `pState` holds the filter's state variables and must be of length `maxDelay + blockSize`, where `maxDelay` is the maximum number of delay line values. `blockSize` is the number of samples processed by the `riscv_fir_sparse_q7()` function.

Parameters

- `S` – **[inout]** points to an instance of the Q7 sparse FIR structure
- `numTaps` – **[in]** number of nonzero coefficients in the filter
- `pCoeffs` – **[in]** points to the array of filter coefficients
- `pState` – **[in]** points to the state buffer
- `pTapDelay` – **[in]** points to the array of offset times
- `maxDelay` – **[in]** maximum offset time supported
- `blockSize` – **[in]** number of samples that will be processed per block

Returns none

void **riscv_fir_sparse_q15**(riscv_fir_sparse_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, q15_t *pScratchIn, q31_t *pScratchOut, uint32_t blockSize)

Processing function for the Q15 sparse FIR filter.

Scaling and Overflow Behavior The function is implemented using an internal 32-bit accumulator. The 1.15 x 1.15 multiplications yield a 2.30 result and these are added to a 2.30 accumulator. Thus the full precision of the multiplications is maintained but there is only a single guard bit in the accumulator. If the accumulator result overflows it will wrap around rather than saturate. After all multiply-accumulates are performed, the 2.30 accumulator is truncated to 2.15 format and then saturated to 1.15 format. In order to avoid overflows the input signal or coefficients must be scaled down by log2(numTaps) bits.

Parameters

- `S` – **[in]** points to an instance of the Q15 sparse FIR structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `pScratchIn` – **[in]** points to a temporary buffer of size blockSize
- `pScratchOut` – **[in]** points to a temporary buffer of size blockSize
- `blockSize` – **[in]** number of input samples to process per call

Returns none

void **riscv_fir_sparse_q31**(riscv_fir_sparse_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, q31_t *pScratchIn, uint32_t blockSize)

Processing function for the Q31 sparse FIR filter.

Scaling and Overflow Behavior The function is implemented using an internal 32-bit accumulator. The 1.31 x 1.31 multiplications are truncated to 2.30 format. This leads to loss of precision on the intermediate multiplications and provides only a single guard bit. If the accumulator result overflows, it wraps around rather than saturate. In order to avoid overflows the input signal or coefficients must be scaled down by log2(numTaps) bits.

Parameters

- `S` – **[in]** points to an instance of the Q31 sparse FIR structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `pScratchIn` – **[in]** points to a temporary buffer of size blockSize
- `blockSize` – **[in]** number of input samples to process

Returns none

void **riscv_fir_sparse_q7**(riscv_fir_sparse_instance_q7 *S, const q7_t *pSrc, q7_t *pDst, q7_t *pScratchIn, q31_t *pScratchOut, uint32_t blockSize)

Processing function for the Q7 sparse FIR filter.

Scaling and Overflow Behavior The function is implemented using a 32-bit internal accumulator. Both coefficients and state variables are represented in 1.7 format and multiplications yield a 2.14 result. The 2.14 intermediate results are accumulated in a 32-bit accumulator in 18.14 format. There is no risk of internal overflow with this approach and the full precision of intermediate multiplications is preserved. The accumulator is then converted to 18.7 format by discarding the low 7 bits. Finally, the result is truncated to 1.7 format.

Parameters

- `S` – **[in]** points to an instance of the Q7 sparse FIR structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `pScratchIn` – **[in]** points to a temporary buffer of size blockSize
- `pScratchOut` – **[in]** points to a temporary buffer of size blockSize
- `blockSize` – **[in]** number of input samples to process

Returns none

Infinite Impulse Response (IIR) Lattice Filters

void **riscv_iir_lattice_f32**(const riscv_iir_lattice_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_iir_lattice_init_f32**(riscv_iir_lattice_instance_f32 *S, uint16_t numStages, float32_t *pkCoeffs, float32_t *pvCoeffs, float32_t *pState, uint32_t blockSize)

void **riscv_iir_lattice_init_q15**(riscv_iir_lattice_instance_q15 *S, uint16_t numStages, q15_t *pkCoeffs, q15_t *pvCoeffs, q15_t *pState, uint32_t blockSize)

void **riscv_iir_lattice_init_q31**(riscv_iir_lattice_instance_q31 *S, uint16_t numStages, q31_t *pkCoeffs, q31_t *pvCoeffs, q31_t *pState, uint32_t blockSize)

void **riscv_iir_lattice_q15**(const riscv_iir_lattice_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_iir_lattice_q31**(const riscv_iir_lattice_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

group **IIR_Lattice**

This set of functions implements lattice filters for Q15, Q31 and floating-point data types. Lattice filters are used in a variety of adaptive filter applications. The filter structure has feedforward and feedback components and the net impulse response is infinite length. The functions operate on blocks of input and output data and each call to the function processes `blockSize` samples through the filter. `pSrc` and `pDst` point to input and output arrays containing `blockSize` values.

Algorithm



`pkCoeffs` points to array of reflection coefficients of size `numStages`. Reflection Coefficients are stored in time-reversed order.

`pvCoeffs` points to the array of ladder coefficients of size `(numStages+1)`. Ladder coefficients are stored in time-reversed order.

`pState` points to a state array of size `numStages + blockSize`. The state variables shown in the figure above (the g values) are stored in the `pState` array. The state variables are updated after each block of data is processed; the coefficients are untouched.

Instance Structure The coefficients and state variables for a filter are stored together in an instance data structure. A separate instance structure must be defined for each filter. Coefficient arrays may be shared among several instances while state variable arrays cannot be shared. There are separate instance structure declarations for each of the 3 supported data types.

Initialization Functions There is also an associated initialization function for each data type. The initialization function performs the following operations:

- Sets the values of the internal structure fields.
- Zeros out the values in the state buffer. To do this manually without calling the init function, assign the follow subfields of the instance structure: numStages, pkCoeffs, pvCoeffs, pState. Also set all of the values in pState to zero.

Use of the initialization function is optional. However, if the initialization function is used, then the instance structure cannot be placed into a const data section. To place an instance structure into a const data section, the instance structure must be manually initialized. Set the values in the state buffer to zeros and then manually initialize the instance structure as follows:

where `numStages` is the number of stages in the filter; `pState` points to the state buffer array; `pkCoeffs` points to array of the reflection coefficients; `pvCoeffs` points to the array of ladder coefficients.

Fixed-Point Behavior Care must be taken when using the fixed-point versions of the IIR lattice filter functions. In particular, the overflow and saturation behavior of the accumulator used in each function must be considered. Refer to the function specific documentation below for usage guidelines.

Functions

void **riscv_iir_lattice_f32**(const riscv_iir_lattice_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Processing function for the floating-point IIR lattice filter.

Parameters

- **S** – **[in]** points to an instance of the floating-point IIR lattice structure
- **pSrc** – **[in]** points to the block of input data
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of samples to process

Returns none

void **riscv_iir_lattice_init_f32**(riscv_iir_lattice_instance_f32 *S, uint16_t numStages, float32_t *pkCoeffs, float32_t *pvCoeffs, float32_t *pState, uint32_t blockSize)

Initialization function for the floating-point IIR lattice filter.

Parameters

- **S** – **[in]** points to an instance of the floating-point IIR lattice structure
- **numStages** – **[in]** number of stages in the filter
- **pkCoeffs** – **[in]** points to reflection coefficient buffer. The array is of length numStages
- **pvCoeffs** – **[in]** points to ladder coefficient buffer. The array is of length numStages+1
- **pState** – **[in]** points to state buffer. The array is of length numStages+blockSize
- **blockSize** – **[in]** number of samples to process

Returns none

void **riscv_iir_lattice_init_q15**(riscv_iir_lattice_instance_q15 *S, uint16_t numStages, q15_t *pkCoeffs, q15_t *pvCoeffs, q15_t *pState, uint32_t blockSize)

Initialization function for the Q15 IIR lattice filter.

Parameters

- `S` – **[in]** points to an instance of the Q15 IIR lattice structure
- `numStages` – **[in]** number of stages in the filter
- `pkCoeffs` – **[in]** points to reflection coefficient buffer. The array is of length numStages
- `pvCoeffs` – **[in]** points to ladder coefficient buffer. The array is of length numStages+1
- `pState` – **[in]** points to state buffer. The array is of length numStages+blockSize
- `blockSize` – **[in]** number of samples to process

Returns none

void **riscv_iir_lattice_init_q31**(riscv_iir_lattice_instance_q31 *S, uint16_t numStages, q31_t *pkCoeffs, q31_t *pvCoeffs, q31_t *pState, uint32_t blockSize)

Initialization function for the Q31 IIR lattice filter.

Parameters

- `S` – **[in]** points to an instance of the Q31 IIR lattice structure
- `numStages` – **[in]** number of stages in the filter
- `pkCoeffs` – **[in]** points to reflection coefficient buffer. The array is of length numStages
- `pvCoeffs` – **[in]** points to ladder coefficient buffer. The array is of length numStages+1
- `pState` – **[in]** points to state buffer. The array is of length numStages+blockSize
- `blockSize` – **[in]** number of samples to process

Returns none

void **riscv_iir_lattice_q15**(const riscv_iir_lattice_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

Processing function for the Q15 IIR lattice filter.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. Both coefficients and state variables are represented in 1.15 format and multiplications yield a 2.30 result. The 2.30 intermediate results are accumulated in a 64-bit accumulator in 34.30 format. There is no risk of internal overflow with this approach and the full precision of intermediate multiplications is preserved. After all additions have been performed, the accumulator is truncated to 34.15 format by discarding low 15 bits. Lastly, the accumulator is saturated to yield a result in 1.15 format.

Parameters

- `S` – **[in]** points to an instance of the Q15 IIR lattice structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process

Returns none

void **riscv_iir_lattice_q31**(const riscv_iir_lattice_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

Processing function for the Q31 IIR lattice filter.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The accumulator has a 2.62 format and maintains full precision of the intermediate multiplication results but provides only a single guard bit. Thus, if the accumulator result overflows it wraps around rather than clip. In order to avoid overflows completely the input signal must be scaled down by 2*log2(numStages) bits. After all multiply-accumulates are performed, the 2.62 accumulator is saturated to 1.32 format and then truncated to 1.31 format.

Parameters

- `S` – **[in]** points to an instance of the Q31 IIR lattice structure
- `pSrc` – **[in]** points to the block of input data
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process

Returns none

Levinson Durbin Algorithm

void **riscv_levinson_durbin_f16**(const float16_t *phi, float16_t *a, float16_t *err, int nbCoefs)

void **riscv_levinson_durbin_f32**(const float32_t *phi, float32_t *a, float32_t *err, int nbCoefs)

void **riscv_levinson_durbin_q31**(const q31_t *phi, q31_t *a, q31_t *err, int nbCoefs)

group `LD`

Functions

void **riscv_levinson_durbin_f16**(const float16_t *phi, float16_t *a, float16_t *err, int nbCoefs)

Levinson Durbin.

Parameters

- `phi` – **[in]** autocovariance vector starting with lag 0 (length is nbCoefs + 1)
- `a` – **[out]** autoregressive coefficients
- `err` – **[out]** prediction error (variance)
- `nbCoefs` – **[in]** number of autoregressive coefficients

Returns none

void **riscv_levinson_durbin_f32**(const float32_t *phi, float32_t *a, float32_t *err, int nbCoefs)

Levinson Durbin.

Parameters

- `phi` – **[in]** autocovariance vector starting with lag 0 (length is nbCoefs + 1)
- `a` – **[out]** autoregressive coefficients

- **err** – **[out]** prediction error (variance)
- **nbCoefs** – **[in]** number of autoregressive coefficients

Returns none

void **riscv_levinson_durbin_q31**(const q31_t *phi, q31_t *a, q31_t *err, int nbCoefs)

Levinson Durbin.

Parameters

- **phi** – **[in]** autocovariance vector starting with lag 0 (length is nbCoefs + 1)
- **a** – **[out]** autoregressive coefficients
- **err** – **[out]** prediction error (variance)
- **nbCoefs** – **[in]** number of autoregressive coefficients

Returns none

Least Mean Square (LMS) Filters

void **riscv_lms_f32**(const riscv_lms_instance_f32 *S, const float32_t *pSrc, float32_t *pRef, float32_t *pOut, float32_t *pErr, uint32_t blockSize)

void **riscv_lms_init_f32**(riscv_lms_instance_f32 *S, uint16_t numTaps, float32_t *pCoeffs, float32_t *pState, float32_t mu, uint32_t blockSize)

void **riscv_lms_init_q15**(riscv_lms_instance_q15 *S, uint16_t numTaps, q15_t *pCoeffs, q15_t *pState, q15_t mu, uint32_t blockSize, uint32_t postShift)

void **riscv_lms_init_q31**(riscv_lms_instance_q31 *S, uint16_t numTaps, q31_t *pCoeffs, q31_t *pState, q31_t mu, uint32_t blockSize, uint32_t postShift)

void **riscv_lms_q15**(const riscv_lms_instance_q15 *S, const q15_t *pSrc, q15_t *pRef, q15_t *pOut, q15_t *pErr, uint32_t blockSize)

void **riscv_lms_q31**(const riscv_lms_instance_q31 *S, const q31_t *pSrc, q31_t *pRef, q31_t *pOut, q31_t *pErr, uint32_t blockSize)

group **LMS**

LMS filters are a class of adaptive filters that are able to "learn" an unknown transfer functions. LMS filters use a gradient descent method in which the filter coefficients are updated based on the instantaneous error signal. Adaptive filters are often used in communication systems, equalizers, and noise removal. The NMSIS DSP Library contains LMS filter functions that operate on Q15, Q31, and floating-point data types. The library also contains normalized LMS filters in which the filter coefficient adaptation is indepedent of the level of the input signal.

An LMS filter consists of two components as shown below. The first component is a standard transversal or FIR filter. The second component is a coefficient update mechanism. The LMS filter has two input signals. The "input" feeds the FIR filter while the "reference input" corresponds to the desired output of the FIR filter. That is, the FIR filter coefficients are updated so that the output of the FIR filter matches the reference input. The filter coefficient update mechanism is based on the difference between the FIR filter output and the reference input. This "error signal" tends towards zero as the filter adapts. The LMS processing functions accept the input and reference input signals and generate the filter output and error signal.



The functions operate on blocks of data and each call to the function processes `blockSize` samples through the filter. `pSrc` points to input signal, `pRef` points to reference signal, `pOut` points to output signal and `pErr` points to error signal. All arrays contain `blockSize` values.

The functions operate on a block-by-block basis. Internally, the filter coefficients `b[n]` are updated on a sample-by-sample basis. The convergence of the LMS filter is slower compared to the normalized LMS algorithm.

Algorithm The output signal `y[n]` is computed by a standard FIR filter:

The error signal equals the difference between the reference signal `d[n]` and the filter output:

After each sample of the error signal is computed, the filter coefficients `b[k]` are updated on a sample-by-sample basis: where `mu` is the step size and controls the rate of coefficient convergence.

In the APIs, `pCoeffs` points to a coefficient array of size `numTaps`. Coefficients are stored in time reversed order.

`pState` points to a state array of size `numTaps + blockSize - 1`. Samples in the state buffer are stored in the order:

Note that the length of the state buffer exceeds the length of the coefficient array by `blockSize-1` samples. The increased state buffer length allows circular addressing, which is traditionally used in FIR filters, to be avoided and yields a significant speed improvement. The state variables are updated after each block of data is processed.

Instance Structure The coefficients and state variables for a filter are stored together in an instance data structure. A separate instance structure must be defined for each filter and coefficient and state arrays cannot be shared among instances. There are separate instance structure declarations for each of the 3 supported data types.

Initialization Functions There is also an associated initialization function for each data type. The initialization function performs the following operations:

- Sets the values of the internal structure fields.

- Zeros out the values in the state buffer. To do this manually without calling the init function, assign the follow subfields of the instance structure: numTaps, pCoeffs, mu, postShift (not for f32), pState. Also set all of the values in pState to zero.

Use of the initialization function is optional. However, if the initialization function is used, then the instance structure cannot be placed into a const data section. To place an instance structure into a const data section, the instance structure must be manually initialized. Set the values in the state buffer to zeros before static initialization. The code below statically initializes each of the 3 different data type filter instance structures where `numTaps` is the number of filter coefficients in the filter; `pState` is the address of the state buffer; `pCoeffs` is the address of the coefficient buffer; `mu` is the step size parameter; and `postShift` is the shift applied to coefficients.

Fixed-Point Behavior Care must be taken when using the Q15 and Q31 versions of the LMS filter. The following issues must be considered:

- Scaling of coefficients
- Overflow and saturation

Scaling of Coefficients Filter coefficients are represented as fractional values and coefficients are restricted to lie in the range `[-1 +1)`. The fixed-point functions have an additional scaling parameter `postShift`. At the output of the filter's accumulator is a shift register which shifts the result by `postShift` bits. This essentially scales the filter coefficients by `2^postShift` and allows the filter coefficients to exceed the range `[+1 -1)`. The value of `postShift` is set by the user based on the expected gain through the system being modeled.

Overflow and Saturation Overflow and saturation behavior of the fixed-point Q15 and Q31 versions are described separately as part of the function specific documentation below.

Functions

void **riscv_lms_f32**(const riscv_lms_instance_f32 *S, const float32_t *pSrc, float32_t *pRef, float32_t *pOut, float32_t *pErr, uint32_t blockSize)

Processing function for floating-point LMS filter.

Parameters

- **S** – **[in]** points to an instance of the floating-point LMS filter structure
- **pSrc** – **[in]** points to the block of input data
- **pRef** – **[in]** points to the block of reference data
- **pOut** – **[out]** points to the block of output data
- **pErr** – **[out]** points to the block of error data
- **blockSize** – **[in]** number of samples to process

Returns none

void **riscv_lms_init_f32**(riscv_lms_instance_f32 *S, uint16_t numTaps, float32_t *pCoeffs, float32_t *pState, float32_t mu, uint32_t blockSize)

Initialization function for floating-point LMS filter.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order: The initial filter coefficients serve as a starting point for the adaptive filter. `pState` points to an array of length `numTaps+blockSize-1` samples, where `blockSize` is the number of input samples processed by each call to `riscv_lms_f32()`.

Parameters

- S – **[in]** points to an instance of the floating-point LMS filter structure
- numTaps – **[in]** number of filter coefficients
- pCoeffs – **[in]** points to coefficient buffer
- pState – **[in]** points to state buffer
- mu – **[in]** step size that controls filter coefficient updates
- blockSize – **[in]** number of samples to process

Returns none

void **riscv_lms_init_q15**(riscv_lms_instance_q15 *S, uint16_t numTaps, q15_t *pCoeffs, q15_t *pState, q15_t mu, uint32_t blockSize, uint32_t postShift)

Initialization function for the Q15 LMS filter.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order: The initial filter coefficients serve as a starting point for the adaptive filter. `pState` points to the array of state variables and size of array is `numTaps+blockSize-1` samples, where `blockSize` is the number of input samples processed by each call to `riscv_lms_q15()`.

Parameters

- S – **[in]** points to an instance of the Q15 LMS filter structure.
- numTaps – **[in]** number of filter coefficients.
- pCoeffs – **[in]** points to coefficient buffer.
- pState – **[in]** points to state buffer.
- mu – **[in]** step size that controls filter coefficient updates.
- blockSize – **[in]** number of samples to process.
- postShift – **[in]** bit shift applied to coefficients.

Returns none

void **riscv_lms_init_q31**(riscv_lms_instance_q31 *S, uint16_t numTaps, q31_t *pCoeffs, q31_t *pState, q31_t mu, uint32_t blockSize, uint32_t postShift)

Initialization function for Q31 LMS filter.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order: The initial filter coefficients serve as a starting point for the adaptive filter. `pState` points to an array of length `numTaps+blockSize-1` samples, where `blockSize` is the number of input samples processed by each call to `riscv_lms_q31()`.

Parameters

- S – **[in]** points to an instance of the Q31 LMS filter structure
- numTaps – **[in]** number of filter coefficients
- pCoeffs – **[in]** points to coefficient buffer
- pState – **[in]** points to state buffer

- `mu` – **[in]** step size that controls filter coefficient updates
- `blockSize` – **[in]** number of samples to process
- `postShift` – **[in]** bit shift applied to coefficients

Returns none

void **riscv_lms_q15**(const riscv_lms_instance_q15 *S, const q15_t *pSrc, q15_t *pRef, q15_t *pOut, q15_t *pErr, uint32_t blockSize)

Processing function for Q15 LMS filter.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. Both coefficients and state variables are represented in 1.15 format and multiplications yield a 2.30 result. The 2.30 intermediate results are accumulated in a 64-bit accumulator in 34.30 format. There is no risk of internal overflow with this approach and the full precision of intermediate multiplications is preserved. After all additions have been performed, the accumulator is truncated to 34.15 format by discarding low 15 bits. Lastly, the accumulator is saturated to yield a result in 1.15 format.

In this filter, filter coefficients are updated for each sample and the updation of filter cofficients are saturted.

Parameters

- `S` – **[in]** points to an instance of the Q15 LMS filter structure
- `pSrc` – **[in]** points to the block of input data
- `pRef` – **[in]** points to the block of reference data
- `pOut` – **[out]** points to the block of output data
- `pErr` – **[out]** points to the block of error data
- `blockSize` – **[in]** number of samples to process

Returns none

void **riscv_lms_q31**(const riscv_lms_instance_q31 *S, const q31_t *pSrc, q31_t *pRef, q31_t *pOut, q31_t *pErr, uint32_t blockSize)

Processing function for Q31 LMS filter.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The accumulator has a 2.62 format and maintains full precision of the intermediate multiplication results but provides only a single guard bit. Thus, if the accumulator result overflows it wraps around rather than clips. In order to avoid overflows completely the input signal must be scaled down by log2(numTaps) bits. The reference signal should not be scaled down. After all multiply-accumulates are performed, the 2.62 accumulator is shifted and saturated to 1.31 format to yield the final result. The output signal and error signal are in 1.31 format.

In this filter, filter coefficients are updated for each sample and the updation of filter cofficients are saturted.

Parameters

- `S` – **[in]** points to an instance of the Q31 LMS filter structure.
- `pSrc` – **[in]** points to the block of input data.
- `pRef` – **[in]** points to the block of reference data.

- **pOut** – **[out]** points to the block of output data.
- **pErr** – **[out]** points to the block of error data.
- **blockSize** – **[in]** number of samples to process.

Returns none

Normalized LMS Filters

void **riscv_lms_norm_f32**(riscv_lms_norm_instance_f32 *S, const float32_t *pSrc, float32_t *pRef, float32_t *pOut, float32_t *pErr, uint32_t blockSize)

void **riscv_lms_norm_init_f32**(riscv_lms_norm_instance_f32 *S, uint16_t numTaps, float32_t *pCoeffs, float32_t *pState, float32_t mu, uint32_t blockSize)

void **riscv_lms_norm_init_q15**(riscv_lms_norm_instance_q15 *S, uint16_t numTaps, q15_t *pCoeffs, q15_t *pState, q15_t mu, uint32_t blockSize, uint8_t postShift)

void **riscv_lms_norm_init_q31**(riscv_lms_norm_instance_q31 *S, uint16_t numTaps, q31_t *pCoeffs, q31_t *pState, q31_t mu, uint32_t blockSize, uint8_t postShift)

void **riscv_lms_norm_q15**(riscv_lms_norm_instance_q15 *S, const q15_t *pSrc, q15_t *pRef, q15_t *pOut, q15_t *pErr, uint32_t blockSize)

void **riscv_lms_norm_q31**(riscv_lms_norm_instance_q31 *S, const q31_t *pSrc, q31_t *pRef, q31_t *pOut, q31_t *pErr, uint32_t blockSize)

group **LMS_NORM**

This set of functions implements a commonly used adaptive filter. It is related to the Least Mean Square (LMS) adaptive filter and includes an additional normalization factor which increases the adaptation rate of the filter. The NMSIS DSP Library contains normalized LMS filter functions that operate on Q15, Q31, and floating-point data types.

A normalized least mean square (NLMS) filter consists of two components as shown below. The first component is a standard transversal or FIR filter. The second component is a coefficient update mechanism. The NLMS filter has two input signals. The “input” feeds the FIR filter while the “reference input” corresponds to the desired output of the FIR filter. That is, the FIR filter coefficients are updated so that the output of the FIR filter matches the reference input. The filter coefficient update mechanism is based on the difference between the FIR filter output and the reference input. This “error signal” tends towards zero as the filter adapts. The NLMS processing functions accept the input and reference input signals and generate the filter output and error signal.



The functions operate on blocks of data and each call to the function processes `blockSize` samples through the filter. `pSrc` points to input signal, `pRef` points to reference signal, `pOut` points to output signal and `pErr` points to error signal. All arrays contain `blockSize` values.

The functions operate on a block-by-block basis. Internally, the filter coefficients `b[n]` are updated on a sample-by-sample basis. The convergence of the LMS filter is slower compared to the normalized LMS algorithm.

Algorithm The output signal `y[n]` is computed by a standard FIR filter:

The error signal equals the difference between the reference signal `d[n]` and the filter output:

After each sample of the error signal is computed the instanteous energy of the filter state variables is calculated: The filter coefficients `b[k]` are then updated on a sample-by-sample basis: where `mu` is the step size and controls the rate of coefficient convergence.

In the APIs, `pCoeffs` points to a coefficient array of size `numTaps`. Coefficients are stored in time reversed order.

`pState` points to a state array of size `numTaps + blockSize - 1`. Samples in the state buffer are stored in the order:

Note that the length of the state buffer exceeds the length of the coefficient array by `blockSize-1` samples. The increased state buffer length allows circular addressing, which is traditionally used in FIR filters, to be avoided and yields a significant speed improvement. The state variables are updated after each block of data is processed.

Instance Structure The coefficients and state variables for a filter are stored together in an instance data structure. A separate instance structure must be defined for each filter and coefficient and state arrays cannot be shared among instances. There are separate instance structure declarations for each of the 3 supported data types.

Initialization Functions There is also an associated initialization function for each data type. The initialization function performs the following operations:

- Sets the values of the internal structure fields.
- Zeros out the values in the state buffer. To do this manually without calling the init function, assign the follow subfields of the instance structure: numTaps, pCoeffs, mu, energy, x0, pState. Also set all

of the values in pState to zero. For Q7, Q15, and Q31 the following fields must also be initialized; recipTable, postShift

Instance structure cannot be placed into a const data section and it is recommended to use the initialization function.

Fixed-Point Behavior Care must be taken when using the Q15 and Q31 versions of the normalised LMS filter. The following issues must be considered:

- Scaling of coefficients
- Overflow and saturation

Scaling of Coefficients (fixed point versions) Filter coefficients are represented as fractional values and coefficients are restricted to lie in the range `[-1 +1)`. The fixed-point functions have an additional scaling parameter `postShift`. At the output of the filter's accumulator is a shift register which shifts the result by `postShift` bits. This essentially scales the filter coefficients by `2^postShift` and allows the filter coefficients to exceed the range `[+1 -1)`. The value of `postShift` is set by the user based on the expected gain through the system being modeled.

Overflow and Saturation (fixed point versions) Overflow and saturation behavior of the fixed-point Q15 and Q31 versions are described separately as part of the function specific documentation below.

Functions

void **riscv_lms_norm_f32**(riscv_lms_norm_instance_f32 *S, const float32_t *pSrc, float32_t *pRef, float32_t *pOut, float32_t *pErr, uint32_t blockSize)

Processing function for floating-point normalized LMS filter.

Parameters

- **S** – **[in]** points to an instance of the floating-point normalized LMS filter structure
- **pSrc** – **[in]** points to the block of input data
- **pRef** – **[in]** points to the block of reference data
- **pOut** – **[out]** points to the block of output data
- **pErr** – **[out]** points to the block of error data
- **blockSize** – **[in]** number of samples to process

Returns none

void **riscv_lms_norm_init_f32**(riscv_lms_norm_instance_f32 *S, uint16_t numTaps, float32_t *pCoeffs, float32_t *pState, float32_t mu, uint32_t blockSize)

Initialization function for floating-point normalized LMS filter.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order: The initial filter coefficients serve as a starting point for the adaptive filter. `pState` points to an array of length `numTaps+blockSize-1` samples, where `blockSize` is the number of input samples processed by each call to `riscv_lms_norm_f32()`.

Parameters

- **S** – **[in]** points to an instance of the floating-point LMS filter structure
- **numTaps** – **[in]** number of filter coefficients
- **pCoeffs** – **[in]** points to coefficient buffer

- `pState` – **[in]** points to state buffer
- `mu` – **[in]** step size that controls filter coefficient updates
- `blockSize` – **[in]** number of samples to process

Returns none

void **riscv_lms_norm_init_q15**(riscv_lms_norm_instance_q15 *S, uint16_t numTaps, q15_t *pCoeffs, q15_t *pState, q15_t mu, uint32_t blockSize, uint8_t postShift)

Initialization function for Q15 normalized LMS filter.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order: The initial filter coefficients serve as a starting point for the adaptive filter. `pState` points to the array of state variables and size of array is `numTaps+blockSize-1` samples, where `blockSize` is the number of input samples processed by each call to `riscv_lms_norm_q15()`.

Parameters

- `S` – **[in]** points to an instance of the Q15 normalized LMS filter structure.
- `numTaps` – **[in]** number of filter coefficients.
- `pCoeffs` – **[in]** points to coefficient buffer.
- `pState` – **[in]** points to state buffer.
- `mu` – **[in]** step size that controls filter coefficient updates.
- `blockSize` – **[in]** number of samples to process.
- `postShift` – **[in]** bit shift applied to coefficients.

Returns none

void **riscv_lms_norm_init_q31**(riscv_lms_norm_instance_q31 *S, uint16_t numTaps, q31_t *pCoeffs, q31_t *pState, q31_t mu, uint32_t blockSize, uint8_t postShift)

Initialization function for Q31 normalized LMS filter.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order: The initial filter coefficients serve as a starting point for the adaptive filter. `pState` points to an array of length `numTaps+blockSize-1` samples, where `blockSize` is the number of input samples processed by each call to `riscv_lms_norm_q31()`.

Parameters

- `S` – **[in]** points to an instance of the Q31 normalized LMS filter structure.
- `numTaps` – **[in]** number of filter coefficients.
- `pCoeffs` – **[in]** points to coefficient buffer.
- `pState` – **[in]** points to state buffer.
- `mu` – **[in]** step size that controls filter coefficient updates.
- `blockSize` – **[in]** number of samples to process.
- `postShift` – **[in]** bit shift applied to coefficients.

Returns none

void **riscv_lms_norm_q15**(riscv_lms_norm_instance_q15 *S, const q15_t *pSrc, q15_t *pRef, q15_t *pOut, q15_t *pErr, uint32_t blockSize)

Processing function for Q15 normalized LMS filter.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. Both coefficients and state variables are represented in 1.15 format and multiplications yield a 2.30 result. The 2.30 intermediate results are accumulated in a 64-bit accumulator in 34.30 format. There is no risk of internal overflow with this approach and the full precision of intermediate multiplications is preserved. After all additions have been performed, the accumulator is truncated to 34.15 format by discarding low 15 bits. Lastly, the accumulator is saturated to yield a result in 1.15 format.

In this filter, filter coefficients are updated for each sample and the updation of filter cofficients are saturted.

Parameters

- `S` – **[in]** points to an instance of the Q15 normalized LMS filter structure
- `pSrc` – **[in]** points to the block of input data
- `pRef` – **[in]** points to the block of reference data
- `pOut` – **[out]** points to the block of output data
- `pErr` – **[out]** points to the block of error data
- `blockSize` – **[in]** number of samples to process

Returns none

void **riscv_lms_norm_q31**(riscv_lms_norm_instance_q31 *S, const q31_t *pSrc, q31_t *pRef, q31_t *pOut, q31_t *pErr, uint32_t blockSize)

Processing function for Q31 normalized LMS filter.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The accumulator has a 2.62 format and maintains full precision of the intermediate multiplication results but provides only a single guard bit. Thus, if the accumulator result overflows it wraps around rather than clip. In order to avoid overflows completely the input signal must be scaled down by log2(numTaps) bits. The reference signal should not be scaled down. After all multiply-accumulates are performed, the 2.62 accumulator is shifted and saturated to 1.31 format to yield the final result. The output signal and error signal are in 1.31 format.

In this filter, filter coefficients are updated for each sample and the updation of filter cofficients are saturted.

Parameters

- `S` – **[in]** points to an instance of the Q31 normalized LMS filter structure
- `pSrc` – **[in]** points to the block of input data
- `pRef` – **[in]** points to the block of reference data
- `pOut` – **[out]** points to the block of output data
- `pErr` – **[out]** points to the block of error data
- `blockSize` – **[in]** number of samples to process

Returns none

Finite Impulse Response (FIR) Interpolator

void **riscv_fir_interpolate_f32**(const riscv_fir_interpolate_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

riscv_status **riscv_fir_interpolate_init_f32**(riscv_fir_interpolate_instance_f32 *S, uint8_t L, uint16_t numTaps, const float32_t *pCoeffs, float32_t *pState, uint32_t blockSize)

riscv_status **riscv_fir_interpolate_init_q15**(riscv_fir_interpolate_instance_q15 *S, uint8_t L, uint16_t numTaps, const q15_t *pCoeffs, q15_t *pState, uint32_t blockSize)

riscv_status **riscv_fir_interpolate_init_q31**(riscv_fir_interpolate_instance_q31 *S, uint8_t L, uint16_t numTaps, const q31_t *pCoeffs, q31_t *pState, uint32_t blockSize)

void **riscv_fir_interpolate_q15**(const riscv_fir_interpolate_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_fir_interpolate_q31**(const riscv_fir_interpolate_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

group **FIR_Interpolate**

These functions combine an upsampler (zero stuffer) and an FIR filter. They are used in multirate systems for increasing the sample rate of a signal without introducing high frequency images. Conceptually, the functions are equivalent to the block diagram below:

After upsampling by a factor of `L`, the signal should be filtered by a lowpass filter with a normalized cutoff frequency of `1/L` in order to eliminate high frequency copies of the spectrum. The user of the function is



responsible for providing the filter coefficients.

The FIR interpolator functions provided in the NMSIS DSP Library combine the upsampler and FIR filter in an efficient manner. The upsampler inserts `L-1` zeros between each sample. Instead of multiplying by these zero values, the FIR filter is designed to skip them. This leads to an efficient implementation without any wasted effort. The functions operate on blocks of input and output data. `pSrc` points to an array of `blockSize` input values and `pDst` points to an array of `blockSize*L` output values.

The library provides separate functions for Q15, Q31, and floating-point data types.

Algorithm The functions use a polyphase filter structure: This approach is more efficient than straightforward upsample-then-filter algorithms. With this method the computation is reduced by a factor of `1/L` when compared to using a standard FIR filter.

`pCoeffs` points to a coefficient array of size `numTaps`. `numTaps` must be a multiple of the interpolation factor `L` and this is checked by the initialization functions. Internally, the function divides the FIR filter's impulse response into shorter filters of length `phaseLength=numTaps/L`. Coefficients are stored in time reversed order.

`pState` points to a state array of size `blockSize + phaseLength - 1`. Samples in the state buffer are stored in the order:

The state variables are updated after each block of data is processed, the coefficients are untouched.

Instance Structure The coefficients and state variables for a filter are stored together in an instance data structure. A separate instance structure must be defined for each filter. Coefficient arrays may be shared among several instances while state variable array should be allocated separately. There are separate instance structure declarations for each of the 3 supported data types.

Initialization Functions There is also an associated initialization function for each data type. The initialization function performs the following operations:

- Sets the values of the internal structure fields.
- Zeros out the values in the state buffer.
- Checks to make sure that the length of the filter is a multiple of the interpolation factor. To do this manually without calling the init function, assign the follow subfields of the instance structure: L (interpolation factor), pCoeffs, phaseLength (numTaps / L), pState. Also set all of the values in pState to zero.

Use of the initialization function is optional. However, if the initialization function is used, then the instance structure cannot be placed into a const data section. To place an instance structure into a const data section, the instance structure must be manually initialized. The code below statically initializes each of the 3 different data type filter instance structures

where `L` is the interpolation factor; `phaseLength=numTaps/L` is the length of each of the shorter FIR filters used internally, `pCoeffs` is the address of the coefficient buffer; `pState` is the address of the state buffer. Be sure to set the values in the state buffer to zeros when doing static initialization.

Fixed-Point Behavior Care must be taken when using the fixed-point versions of the FIR interpolate filter functions. In particular, the overflow and saturation behavior of the accumulator used in each function must be considered. Refer to the function specific documentation below for usage guidelines.

Functions

void **`riscv_fir_interpolate_f32`**(const riscv_fir_interpolate_instance_f32 *S, const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Processing function for floating-point FIR interpolator.

Processing function for the floating-point FIR interpolator.

Parameters

- **`S`** – **[in]** points to an instance of the floating-point FIR interpolator structure
- **`pSrc`** – **[in]** points to the block of input data
- **`pDst`** – **[out]** points to the block of output data
- **`blockSize`** – **[in]** number of input samples to process

Returns none

riscv_status **`riscv_fir_interpolate_init_f32`**(riscv_fir_interpolate_instance_f32 *S, uint8_t L, uint16_t numTaps, const float32_t *pCoeffs, float32_t *pState, uint32_t blockSize)

Initialization function for the floating-point FIR interpolator.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order:

The length of the filter `numTaps` must be a multiple of the interpolation factor `L`.

`pState` points to the array of state variables. `pState` is of length `(numTaps/L)+blockSize-1` words where `blockSize` is the number of input samples processed by each call to `riscv_fir_interpolate_f32()`.

Parameters

- **S** – **[inout]** points to an instance of the floating-point FIR interpolator structure
- **L** – **[in]** upsample factor
- **numTaps** – **[in]** number of filter coefficients in the filter
- **pCoeffs** – **[in]** points to the filter coefficient buffer
- **pState** – **[in]** points to the state buffer
- **blockSize** – **[in]** number of input samples to process per call

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : filter length `numTaps` is not a multiple of the interpolation factor `L`

riscv_status **riscv_fir_interpolate_init_q15**(riscv_fir_interpolate_instance_q15 *S, uint8_t L, uint16_t numTaps, const q15_t *pCoeffs, q15_t *pState, uint32_t blockSize)

Initialization function for the Q15 FIR interpolator.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order: The length of the filter `numTaps` must be a multiple of the interpolation factor `L`.

`pState` points to the array of state variables. `pState` is of length `(numTaps/L)+blockSize-1` words where `blockSize` is the number of input samples processed by each call to `riscv_fir_interpolate_q15()`.

Parameters

- **S** – **[inout]** points to an instance of the Q15 FIR interpolator structure
- **L** – **[in]** upsample factor
- **numTaps** – **[in]** number of filter coefficients in the filter
- **pCoeffs** – **[in]** points to the filter coefficient buffer
- **pState** – **[in]** points to the state buffer
- **blockSize** – **[in]** number of input samples to process per call

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : filter length `numTaps` is not a multiple of the interpolation factor `L`

riscv_status **riscv_fir_interpolate_init_q31**(riscv_fir_interpolate_instance_q31 *S, uint8_t L, uint16_t numTaps, const q31_t *pCoeffs, q31_t *pState, uint32_t blockSize)

Initialization function for the Q31 FIR interpolator.

Details `pCoeffs` points to the array of filter coefficients stored in time reversed order: The length of the filter `numTaps` must be a multiple of the interpolation factor `L`.

`pState` points to the array of state variables. `pState` is of length `(numTaps/L)+blockSize-1` words where `blockSize` is the number of input samples processed by each call to `riscv_fir_interpolate_q31()`.

Parameters

- **S** – **[inout]** points to an instance of the Q31 FIR interpolator structure
- **L** – **[in]** upsample factor
- **numTaps** – **[in]** number of filter coefficients in the filter
- **pCoeffs** – **[in]** points to the filter coefficient buffer
- **pState** – **[in]** points to the state buffer
- **blockSize** – **[in]** number of input samples to process per call

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : filter length `numTaps` is not a multiple of the interpolation factor `L`

void **riscv_fir_interpolate_q15**(const riscv_fir_interpolate_instance_q15 *S, const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

Processing function for the Q15 FIR interpolator.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. Both coefficients and state variables are represented in 1.15 format and multiplications yield a 2.30 result. The 2.30 intermediate results are accumulated in a 64-bit accumulator in 34.30 format. There is no risk of internal overflow with this approach and the full precision of intermediate multiplications is preserved. After all additions have been performed, the accumulator is truncated to 34.15 format by discarding low 15 bits. Lastly, the accumulator is saturated to yield a result in 1.15 format.

Parameters

- **S** – **[in]** points to an instance of the Q15 FIR interpolator structure
- **pSrc** – **[in]** points to the block of input data
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of input samples to process

Returns none

void **riscv_fir_interpolate_q31**(const riscv_fir_interpolate_instance_q31 *S, const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

Processing function for the Q31 FIR interpolator.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The accumulator has a 2.62 format and maintains full precision of the intermediate multiplication results but provides only a single guard bit. Thus, if the accumulator result overflows it wraps around rather than clip. In order to avoid overflows completely the input signal must be scaled down by `1/(numTaps/L)`. since `numTaps/L` additions occur per output sample. After all multiply-accumulates are performed, the 2.62 accumulator is truncated to 1.32 format and then saturated to 1.31 format.

Parameters

- **S** – **[in]** points to an instance of the Q31 FIR interpolator structure
- **pSrc** – **[in]** points to the block of input data
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of input samples to process

Returns none

group **groupFilters**

3.3.8 Interpolation Functions

Bilinear Interpolation

float16_t **riscv_bilinear_interp_f16**(const riscv_bilinear_interp_instance_f16 *S, float16_t X, float16_t Y)

float32_t **riscv_bilinear_interp_f32**(const riscv_bilinear_interp_instance_f32 *S, float32_t X, float32_t Y)

q15_t **riscv_bilinear_interp_q15**(riscv_bilinear_interp_instance_q15 *S, q31_t X, q31_t Y)

q31_t **riscv_bilinear_interp_q31**(riscv_bilinear_interp_instance_q31 *S, q31_t X, q31_t Y)

q7_t **riscv_bilinear_interp_q7**(riscv_bilinear_interp_instance_q7 *S, q31_t X, q31_t Y)

group **BilinearInterpolate**

Bilinear interpolation is an extension of linear interpolation applied to a two dimensional grid. The underlying function `f(x, y)` is sampled on a regular grid and the interpolation process determines values between the grid points. Bilinear interpolation is equivalent to two step linear interpolation, first in the x-dimension and then in the y-dimension. Bilinear interpolation is often used in image processing to rescale images. The NMSIS DSP library provides bilinear interpolation functions for Q7, Q15, Q31, and floating-point data types.

Algorithm end of LinearInterpolate group

The instance structure used by the bilinear interpolation functions describes a two dimensional data table. For floating-point, the instance structure is defined as:

where `numRows` specifies the number of rows in the table; `numCols` specifies the number of columns in the table; and `pData` points to an array of size `numRows*numCols` values. The data table `pTable` is organized in row order and the supplied data values fall on integer indexes. That is, table element (x,y) is located at `pTable[x + y*numCols]` where x and y are integers.

Let `(x, y)` specify the desired interpolation point. Then define:

The interpolated output point is computed as: Note that the coordinates (x, y) contain integer and fractional components. The integer components specify which portion of the table to use while the fractional components control the interpolation processor.

if (x,y) are outside of the table boundary, Bilinear interpolation returns zero output.

Functions

float16_t **riscv_bilinear_interp_f16**(const riscv_bilinear_interp_instance_f16 *S, float16_t X, float16_t Y)

Floating-point bilinear interpolation.

Parameters

- **S** – **[inout]** points to an instance of the interpolation structure.
- **X** – **[in]** interpolation coordinate.
- **Y** – **[in]** interpolation coordinate.

Returns out interpolated value.

float32_t **riscv_bilinear_interp_f32**(const riscv_bilinear_interp_instance_f32 *S, float32_t X, float32_t Y)

Floating-point bilinear interpolation.

Parameters

- **S** – **[inout]** points to an instance of the interpolation structure.
- **X** – **[in]** interpolation coordinate.
- **Y** – **[in]** interpolation coordinate.

Returns out interpolated value.

q15_t **riscv_bilinear_interp_q15**(riscv_bilinear_interp_instance_q15 *S, q31_t X, q31_t Y)

Q15 bilinear interpolation.

Parameters

- **S** – **[inout]** points to an instance of the interpolation structure.
- **X** – **[in]** interpolation coordinate in 12.20 format.
- **Y** – **[in]** interpolation coordinate in 12.20 format.

Returns out interpolated value.

q31_t **riscv_bilinear_interp_q31**(riscv_bilinear_interp_instance_q31 *S, q31_t X, q31_t Y)

Q31 bilinear interpolation.

Parameters

- **S** – **[inout]** points to an instance of the interpolation structure.
- **X** – **[in]** interpolation coordinate in 12.20 format.
- **Y** – **[in]** interpolation coordinate in 12.20 format.

Returns out interpolated value.

q7_t **riscv_bilinear_interp_q7**(riscv_bilinear_interp_instance_q7 *S, q31_t X, q31_t Y)

Q7 bilinear interpolation.

Parameters

- **S** – **[inout]** points to an instance of the interpolation structure.
- **X** – **[in]** interpolation coordinate in 12.20 format.
- **Y** – **[in]** interpolation coordinate in 12.20 format.

Returns out interpolated value.

Linear Interpolation

float16_t **riscv_linear_interp_f16**(riscv_linear_interp_instance_f16 *S, float16_t x)

float32_t **riscv_linear_interp_f32**(riscv_linear_interp_instance_f32 *S, float32_t x)

q15_t **riscv_linear_interp_q15**(const q15_t *pYData, q31_t x, uint32_t nValues)

q31_t **riscv_linear_interp_q31**(const q31_t *pYData, q31_t x, uint32_t nValues)

q7_t **riscv_linear_interp_q7**(const q7_t *pYData, q31_t x, uint32_t nValues)

group **LinearInterpolate**

Linear interpolation is a method of curve fitting using linear polynomials. Linear interpolation works by effectively drawing a straight line between two neighboring samples and returning the appropriate point along that line.



A Linear Interpolate function calculates an output value(y), for the input(x) using linear interpolation of the input values x0, x1(nearest input values) and the output values y0 and y1(nearest output values)

Algorithm:

This set of functions implements Linear interpolation process for Q7, Q15, Q31, and floating-point data types. The functions operate on a single sample of data and each call to the function returns a single processed value. S points to an instance of the Linear Interpolate function data structure. `x` is the input sample value. The functions returns the output value.

if x is outside of the table boundary, Linear interpolation returns first value of the table if x is below input range and returns last value of table if x is above range.

Functions

float16_t **riscv_linear_interp_f16**(riscv_linear_interp_instance_f16 *S, float16_t x)

Process function for the floating-point Linear Interpolation Function.

Parameters

- `S` – **[inout]** is an instance of the floating-point Linear Interpolation structure
- **`x`** – **[in]** input sample to process

Returns y processed output sample.

float32_t **riscv_linear_interp_f32**(riscv_linear_interp_instance_f32 *S, float32_t x)

Process function for the floating-point Linear Interpolation Function.

Parameters

- `S` – **[inout]** is an instance of the floating-point Linear Interpolation structure
- **`x`** – **[in]** input sample to process

Returns y processed output sample.

q15_t **riscv_linear_interp_q15**(const q15_t *pYData, q31_t x, uint32_t nValues)

Process function for the Q15 Linear Interpolation Function.

Input sample `x` is in 12.20 format which contains 12 bits for table index and 20 bits for fractional part. This function can support maximum of table size 2^12.

Parameters

- **`pYData`** – **[in]** pointer to Q15 Linear Interpolation table
- **`x`** – **[in]** input sample to process
- **`nValues`** – **[in]** number of table values

Returns y processed output sample.

q31_t **riscv_linear_interp_q31**(const q31_t *pYData, q31_t x, uint32_t nValues)

Process function for the Q31 Linear Interpolation Function.

Input sample `x` is in 12.20 format which contains 12 bits for table index and 20 bits for fractional part. This function can support maximum of table size 2^12.

Parameters

- **pYData** – **[in]** pointer to Q31 Linear Interpolation table
- **x** – **[in]** input sample to process
- **nValues** – **[in]** number of table values

Returns y processed output sample.

q7_t **riscv_linear_interp_q7**(const q7_t *pYData, q31_t x, uint32_t nValues)

Process function for the Q7 Linear Interpolation Function.

Input sample `x` is in 12.20 format which contains 12 bits for table index and 20 bits for fractional part. This function can support maximum of table size 2^12.

Parameters

- **pYData** – **[in]** pointer to Q7 Linear Interpolation table
- **x** – **[in]** input sample to process
- **nValues** – **[in]** number of table values

Returns y processed output sample.

Cubic Spline Interpolation

void **riscv_spline_f32**(riscv_spline_instance_f32 *S, const float32_t *xq, float32_t *pDst, uint32_t blockSize)

void **riscv_spline_init_f32**(riscv_spline_instance_f32 *S, riscv_spline_type type, const float32_t *x, const float32_t *y, uint32_t n, float32_t *coeffs, float32_t *tempBuffer)

group **SplineInterpolate**

Spline interpolation is a method of interpolation where the interpolant is a piecewise-defined polynomial called "spline".

Given a function f defined on the interval [a,b], a set of n nodes x(i) where a=x(1)<x(2)<…<x(n)=b and a set of n values y(i) = f(x(i)), a cubic spline interpolant S(x) is defined as:

Introduction

where

Having defined h(i) = x(i+1) - x(i)

Algorithm

It is possible to write the previous conditions in matrix form (Ax=B). In order to solve the system two boundary conidtions are needed.

- Natural spline: S1"(x1)=2*c(1)=0 ; Sn"(xn)=2*c(n)=0 In matrix form:
- Parabolic runout spline: S1"(x1)=2*c(1)=S2"(x2)=2*c(2) ; Sn-1"(xn-1)=2*c(n-1)=Sn"(xn)=2*c(n) In matrix form:

A is a tridiagonal matrix (a band matrix of bandwidth 3) of size N=n+1. The factorization algorithms (A=LU) can be simplified considerably because a large number of zeros appear in regular patterns. The Crout method has been used: 1) Solve LZ=B

2) Solve UX=Z

c(i) for i=1, …, n-1 are needed to compute the n-1 polynomials. b(i) and d(i) are computed as:

- b(i) = [y(i+1)-y(i)]/h(i)-h(i)*[c(i+1)+2*c(i)]/3
- d(i) = [c(i+1)-c(i)]/[3*h(i)] Moreover, a(i)=y(i).

It is possible to compute the interpolated vector for x values outside the input range (xq<x(1); xq>x(n)). The coefficients used to compute the y values for xq<x(1) are going to be the ones used for the first interval, while for xq>x(n) the coefficients used for the last interval.

Behaviour outside the given intervals

The initialization function takes as input two arrays that the user has to allocate: `coeffs` will contain the b, c, and d coefficients for the (n-1) intervals (n is the number of known points), hence its size must be 3*(n-1); `tempBuffer` is temporally used for internal computations and its size is n+n-1.

Initialization function

The x input array must be strictly sorted in ascending order and it must not contain twice the same value (x(i)<x(i+1)).

Functions

void **riscv_spline_f32**(riscv_spline_instance_f32 *S, const float32_t *xq, float32_t *pDst, uint32_t blockSize)

Processing function for the floating-point cubic spline interpolation.

Parameters

- **S** – **[in]** points to an instance of the floating-point spline structure.
- **xq** – **[in]** points to the x values of the interpolated data points.
- **pDst** – **[out]** points to the block of output data.
- **blockSize** – **[in]** number of samples of output data.

void **riscv_spline_init_f32**(riscv_spline_instance_f32 *S, riscv_spline_type type, const float32_t *x, const float32_t *y, uint32_t n, float32_t *coeffs, float32_t *tempBuffer)

Initialization function for the floating-point cubic spline interpolation.

Parameters

- **S** – **[inout]** points to an instance of the floating-point spline structure.
- **type** – **[in]** type of cubic spline interpolation (boundary conditions)
- **x** – **[in]** points to the x values of the known data points.
- **y** – **[in]** points to the y values of the known data points.

- **n** – **[in]** number of known data points.
- **coeffs** – **[in]** coefficients array for b, c, and d
- **tempBuffer** – **[in]** buffer array for internal computations

group **groupInterpolation**

These functions perform 1- and 2-dimensional interpolation of data. Linear interpolation is used for 1-dimensional data and bilinear interpolation is used for 2-dimensional data.

3.3.9 Matrix Functions

Householder transform of a vector

float16_t **riscv_householder_f16**(const float16_t *pSrc, const float16_t threshold, uint32_t blockSize, float16_t *pOut)

float32_t **riscv_householder_f32**(const float32_t *pSrc, const float32_t threshold, uint32_t blockSize, float32_t *pOut)

float64_t **riscv_householder_f64**(const float64_t *pSrc, const float64_t threshold, uint32_t blockSize, float64_t *pOut)

group **MatrixHouseholder**

Computes the Householder transform of a vector x.

The Householder transform of x is a vector v with

$$v_0 = 1$$

and a scalar β such that:

$$P = I - \beta vv^T$$

is an orthogonal matrix and

$$Px = ||x||_2 e_1$$

So P is an hyperplane reflection such that the image of x is proportional to e_1.

e_1 is the vector of coordinates:

$$\begin{pmatrix} 1 \\ 0 \\ \vdots \end{pmatrix}$$

If x is already proportional to e_1 then the matrix P should be the identity.

Thus, β should be 0 and in this case the vector v can also be null.

But how do we detect that x is already proportional to e_1.

If x

$$x = \begin{pmatrix} x_0 \\ xr \end{pmatrix}$$

where xr is a vector.

The algorithm is computing the norm squared of this vector:

$$||xr||^2$$

and this value is compared to a `threshold`. If the value is smaller than the `threshold`, the algorithm is returning 0 for β and the householder vector.

This `threshold` is an argument of the function.

Default values are provided in the header `dsp/matrix_functions.h` like for instance `DEFAULT_HOUSEHOLDER_THRESHOLD_F32`

Functions

float16_t **riscv_householder_f16**(const float16_t *pSrc, const float16_t threshold, uint32_t blockSize, float16_t *pOut)

Householder transform of a half floating point vector.

Parameters

- **pSrc** – **[in]** points to the input vector.
- **threshold** – **[in]** norm2 threshold.
- **blockSize** – **[in]** dimension of the vector space.
- **pOut** – **[out]** points to the output vector.

Returns beta return the scaling factor beta

float32_t **riscv_householder_f32**(const float32_t *pSrc, const float32_t threshold, uint32_t blockSize, float32_t *pOut)

Householder transform of a floating point vector.

Parameters

- **pSrc** – **[in]** points to the input vector.
- **threshold** – **[in]** norm2 threshold.
- **blockSize** – **[in]** dimension of the vector space.
- **pOut** – **[out]** points to the output vector.

Returns beta return the scaling factor beta float64_t **riscv_householder_f64**(const float64_t *pSrc, const float64_t threshold, uint32_t blockSize, float64_t *pOut)

Householder transform of a double floating point vector.

Parameters

- **pSrc** – **[in]** points to the input vector.
- **threshold** – **[in]** norm2 threshold.
- **blockSize** – **[in]** dimension of the vector space.
- **pOut** – **[out]** points to the output vector.

Returns beta return the scaling factor beta

Matrix Addition

riscv_status **riscv_mat_add_f16**(const riscv_matrix_instance_f16 *pSrcA, const riscv_matrix_instance_f16 *pSrcB, riscv_matrix_instance_f16 *pDst)

riscv_status **riscv_mat_add_f32**(const riscv_matrix_instance_f32 *pSrcA, const riscv_matrix_instance_f32 *pSrcB, riscv_matrix_instance_f32 *pDst)

riscv_status **riscv_mat_add_q15**(const riscv_matrix_instance_q15 *pSrcA, const riscv_matrix_instance_q15 *pSrcB, riscv_matrix_instance_q15 *pDst)

riscv_status **riscv_mat_add_q31**(const riscv_matrix_instance_q31 *pSrcA, const riscv_matrix_instance_q31 *pSrcB, riscv_matrix_instance_q31 *pDst)

group **MatrixAdd**

Adds two matrices.

$$\begin{pmatrix} a_{1,1} & a_{1,2} & a_{1,3} \\ a_{2,1} & a_{2,2} & a_{2,3} \\ a_{3,1} & a_{3,2} & a_{3,3} \end{pmatrix} + \begin{pmatrix} b_{1,1} & b_{1,2} & b_{1,3} \\ b_{2,1} & b_{2,2} & b_{2,3} \\ b_{3,1} & b_{3,2} & b_{3,3} \end{pmatrix} = \begin{pmatrix} a_{1,1}+b_{1,1} & a_{1,2}+b_{1,2} & a_{1,3}+b_{1,3} \\ a_{2,1}+b_{2,1} & a_{2,2}+b_{2,2} & a_{2,3}+b_{2,3} \\ a_{3,1}+b_{3,1} & a_{3,2}+b_{3,2} & a_{3,3}+b_{3,3} \end{pmatrix}$$

Addition of two 3 x 3 matrices

The functions check to make sure that `pSrcA`, `pSrcB`, and `pDst` have the same number of rows and columns.

Functions

riscv_status **riscv_mat_add_f16**(const riscv_matrix_instance_f16 *pSrcA, const riscv_matrix_instance_f16 *pSrcB, riscv_matrix_instance_f16 *pDst)

Floating-point matrix addition.

Parameters

- **pSrcA** – **[in]** points to first input matrix structure
- **pSrcB** – **[in]** points to second input matrix structure
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_add_f32**(const riscv_matrix_instance_f32 *pSrcA, const riscv_matrix_instance_f32 *pSrcB, riscv_matrix_instance_f32 *pDst)

Floating-point matrix addition.

Parameters

- **pSrcA** – **[in]** points to first input matrix structure
- **pSrcB** – **[in]** points to second input matrix structure
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_add_q15**(const riscv_matrix_instance_q15 *pSrcA, const riscv_matrix_instance_q15 *pSrcB, riscv_matrix_instance_q15 *pDst)

Q15 matrix addition.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q15 range [0x8000 0x7FFF] are saturated.

Parameters

- **pSrcA** – **[in]** points to first input matrix structure
- **pSrcB** – **[in]** points to second input matrix structure
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_add_q31**(const riscv_matrix_instance_q31 *pSrcA, const riscv_matrix_instance_q31 *pSrcB, riscv_matrix_instance_q31 *pDst)

Q31 matrix addition.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q31 range [0x80000000 0x7FFFFFFF] are saturated.

Parameters

- **pSrcA** – **[in]** points to first input matrix structure
- **pSrcB** – **[in]** points to second input matrix structure
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful

- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

Cholesky and LDLT decompositions

riscv_status **riscv_mat_cholesky_f16**(const riscv_matrix_instance_f16 *pSrc, riscv_matrix_instance_f16 *pDst)

riscv_status **riscv_mat_cholesky_f32**(const riscv_matrix_instance_f32 *pSrc, riscv_matrix_instance_f32 *pDst)

riscv_status **riscv_mat_cholesky_f64**(const riscv_matrix_instance_f64 *pSrc, riscv_matrix_instance_f64 *pDst)

riscv_status **riscv_mat_ldlt_f32**(const riscv_matrix_instance_f32 *pSrc, riscv_matrix_instance_f32 *pl, riscv_matrix_instance_f32 *pd, uint16_t *pp)

riscv_status **riscv_mat_ldlt_f64**(const riscv_matrix_instance_f64 *pSrc, riscv_matrix_instance_f64 *pl, riscv_matrix_instance_f64 *pd, uint16_t *pp)

group **MatrixChol**

Computes the Cholesky or LL^t decomposition of a matrix.

If the input matrix does not have a decomposition, then the algorithm terminates and returns error status RISCV_MATH_DECOMPOSITION_FAILURE.

Functions

riscv_status **riscv_mat_cholesky_f16**(const riscv_matrix_instance_f16 *pSrc, riscv_matrix_instance_f16 *pDst)

Floating-point Cholesky decomposition of positive-definite matrix.

Floating-point Cholesky decomposition of Symmetric Positive Definite Matrix.

If the matrix is ill conditioned or only semi-definite, then it is better using the LDL^t decomposition. The decomposition of A is returning a lower triangular matrix U such that A = L L^t

Parameters

- **pSrc** – **[in]** points to the instance of the input floating-point matrix structure.
- **pDst** – **[out]** points to the instance of the output floating-point matrix structure.

Returns The function returns RISCV_MATH_SIZE_MISMATCH, if the dimensions do not match.

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed
- RISCV_MATH_DECOMPOSITION_FAILURE : Input matrix cannot be decomposed

riscv_status **riscv_mat_cholesky_f32**(const riscv_matrix_instance_f32 *pSrc, riscv_matrix_instance_f32 *pDst)

Floating-point Cholesky decomposition of positive-definite matrix.

Floating-point Cholesky decomposition of Symmetric Positive Definite Matrix.

If the matrix is ill conditioned or only semi-definite, then it is better using the LDL^t decomposition. The decomposition of A is returning a lower triangular matrix L such that A = L L^t

Parameters

- `pSrc` – **[in]** points to the instance of the input floating-point matrix structure.
- `pDst` – **[out]** points to the instance of the output floating-point matrix structure.

Returns The function returns RISCV_MATH_SIZE_MISMATCH, if the dimensions do not match.

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed
- RISCV_MATH_DECOMPOSITION_FAILURE : Input matrix cannot be decomposed

riscv_status **riscv_mat_cholesky_f64**(const riscv_matrix_instance_f64 *pSrc, riscv_matrix_instance_f64 *pDst)

Floating-point Cholesky decomposition of positive-definite matrix.

Floating-point Cholesky decomposition of Symmetric Positive Definite Matrix.

If the matrix is ill conditioned or only semi-definite, then it is better using the LDL^t decomposition. The decomposition of A is returning a lower triangular matrix L such that A = L L^t

Parameters

- `pSrc` – **[in]** points to the instance of the input floating-point matrix structure.
- `pDst` – **[out]** points to the instance of the output floating-point matrix structure.

Returns The function returns RISCV_MATH_SIZE_MISMATCH, if the dimensions do not match.

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed
- RISCV_MATH_DECOMPOSITION_FAILURE : Input matrix cannot be decomposed

riscv_status **riscv_mat_ldlt_f32**(const riscv_matrix_instance_f32 *pSrc, riscv_matrix_instance_f32 *pl, riscv_matrix_instance_f32 *pd, uint16_t *pp)

Floating-point LDL^t decomposition of positive semi-definite matrix.

Floating-point LDL decomposition of Symmetric Positive Semi-Definite Matrix.

Computes the LDL^t decomposition of a matrix A such that P A P^t = L D L^t.

Parameters

- `pSrc` – **[in]** points to the instance of the input floating-point matrix structure.
- `pl` – **[out]** points to the instance of the output floating-point triangular matrix structure.
- `pd` – **[out]** points to the instance of the output floating-point diagonal matrix structure.

- **pp** – **[out]** points to the instance of the output floating-point permutation vector.

Returns The function returns RISCV_MATH_SIZE_MISMATCH, if the dimensions do not match.

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed
- RISCV_MATH_DECOMPOSITION_FAILURE : Input matrix cannot be decomposed

riscv_status **riscv_mat_ldlt_f64**(const riscv_matrix_instance_f64 *pSrc, riscv_matrix_instance_f64 *pl, riscv_matrix_instance_f64 *pd, uint16_t *pp)

Floating-point LDL^t decomposition of positive semi-definite matrix.

Floating-point LDL decomposition of Symmetric Positive Semi-Definite Matrix.

Computes the LDL^t decomposition of a matrix A such that P A P^t = L D L^t.

Parameters

- **pSrc** – **[in]** points to the instance of the input floating-point matrix structure.
- **pl** – **[out]** points to the instance of the output floating-point triangular matrix structure.
- **pd** – **[out]** points to the instance of the output floating-point diagonal matrix structure.
- **pp** – **[out]** points to the instance of the output floating-point permutation vector.

Returns The function returns RISCV_MATH_SIZE_MISMATCH, if the dimensions do not match.

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed
- RISCV_MATH_DECOMPOSITION_FAILURE : Input matrix cannot be decomposed

Complex Matrix Multiplication

riscv_status **riscv_mat_cmplx_mult_f16**(const riscv_matrix_instance_f16 *pSrcA, const riscv_matrix_instance_f16 *pSrcB, riscv_matrix_instance_f16 *pDst)

riscv_status **riscv_mat_cmplx_mult_f32**(const riscv_matrix_instance_f32 *pSrcA, const riscv_matrix_instance_f32 *pSrcB, riscv_matrix_instance_f32 *pDst)

riscv_status **riscv_mat_cmplx_mult_q15**(const riscv_matrix_instance_q15 *pSrcA, const riscv_matrix_instance_q15 *pSrcB, riscv_matrix_instance_q15 *pDst, q15_t *pScratch)

riscv_status **riscv_mat_cmplx_mult_q31**(const riscv_matrix_instance_q31 *pSrcA, const riscv_matrix_instance_q31 *pSrcB, riscv_matrix_instance_q31 *pDst) *group* `CmplxMatrixMult`

Complex Matrix multiplication is only defined if the number of columns of the first matrix equals the number of rows of the second matrix. Multiplying an `M x N` matrix with an `N x P` matrix results in an `M x P` matrix.

When matrix size checking is enabled, the functions check:

- that the inner dimensions of `pSrcA` and `pSrcB` are equal;
- that the size of the output matrix equals the outer dimensions of `pSrcA` and `pSrcB`.

Functions

riscv_status **riscv_mat_cmplx_mult_f16**(const riscv_matrix_instance_f16 *pSrcA, const riscv_matrix_instance_f16 *pSrcB, riscv_matrix_instance_f16 *pDst)

Floating-point Complex matrix multiplication.

Floating-point, complex, matrix multiplication.

Parameters

- **pSrcA** – **[in]** points to first input complex matrix structure
- **pSrcB** – **[in]** points to second input complex matrix structure
- **pDst** – **[out]** points to output complex matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_cmplx_mult_f32**(const riscv_matrix_instance_f32 *pSrcA, const riscv_matrix_instance_f32 *pSrcB, riscv_matrix_instance_f32 *pDst)

Floating-point Complex matrix multiplication.

Floating-point, complex, matrix multiplication.

Parameters

- **pSrcA** – **[in]** points to first input complex matrix structure
- **pSrcB** – **[in]** points to second input complex matrix structure
- **pDst** – **[out]** points to output complex matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_cmplx_mult_q15**(const riscv_matrix_instance_q15 *pSrcA, const riscv_matrix_instance_q15 *pSrcB, riscv_matrix_instance_q15 *pDst, q15_t *pScratch)

Q15 Complex matrix multiplication.

Q15, complex, matrix multiplication.

Conditions for optimum performance Input, output and state buffers should be aligned by 32-bit

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The inputs to the multiplications are in 1.15 format and multiplications yield a 2.30 result. The 2.30 intermediate results are accumulated in a 64-bit accumulator in 34.30 format. This approach provides 33 guard bits and there is no risk of overflow. The 34.30 result is then truncated to 34.15 format by discarding the low 15 bits and then saturated to 1.15 format.

Parameters

- `pSrcA` – **[in]** points to first input complex matrix structure
- `pSrcB` – **[in]** points to second input complex matrix structure
- `pDst` – **[out]** points to output complex matrix structure
- `pScratch` – **[in]** points to an array for storing intermediate results

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_cmplx_mult_q31**(const riscv_matrix_instance_q31 *pSrcA, const riscv_matrix_instance_q31 *pSrcB, riscv_matrix_instance_q31 *pDst)

Q31 Complex matrix multiplication.

Q31, complex, matrix multiplication.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The accumulator has a 2.62 format and maintains full precision of the intermediate multiplication results but provides only a single guard bit. There is no saturation on intermediate additions. Thus, if the accumulator overflows it wraps around and distorts the result. The input signals should be scaled down to avoid intermediate overflows. The input is thus scaled down by log2(numColsA) bits to avoid overflows, as a total of numColsA additions are performed internally. The 2.62 accumulator is right shifted by 31 bits and saturated to 1.31 format to yield the final result.

Parameters

- `pSrcA` – **[in]** points to first input complex matrix structure
- `pSrcB` – **[in]** points to second input complex matrix structure
- `pDst` – **[out]** points to output complex matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

Complex Matrix Transpose

riscv_status **riscv_mat_cmplx_trans_f16**(const riscv_matrix_instance_f16 *pSrc, riscv_matrix_instance_f16 *pDst)

riscv_status **riscv_mat_cmplx_trans_f32**(const riscv_matrix_instance_f32 *pSrc, riscv_matrix_instance_f32 *pDst)

riscv_status **riscv_mat_cmplx_trans_q15**(const riscv_matrix_instance_q15 *pSrc, riscv_matrix_instance_q15 *pDst)

riscv_status **riscv_mat_cmplx_trans_q31**(const riscv_matrix_instance_q31 *pSrc, riscv_matrix_instance_q31 *pDst)

group **MatrixComplexTrans**

Tranposes a complex matrix.

Transposing an `M x N` matrix flips it around the center diagonal and results in an `N x M` matrix.

$$\begin{pmatrix} a_{1,1} & a_{1,2} & a_{1,3} \\ a_{2,1} & a_{2,2} & a_{2,3} \\ a_{3,1} & a_{3,2} & a_{3,3} \end{pmatrix}^T = \begin{pmatrix} a_{1,1} & a_{2,1} & a_{3,1} \\ a_{1,2} & a_{2,2} & a_{3,2} \\ a_{1,3} & a_{2,3} & a_{3,3} \end{pmatrix}$$

Transpose of a 3 x 3 matrix

Functions

riscv_status **riscv_mat_cmplx_trans_f16**(const riscv_matrix_instance_f16 *pSrc, riscv_matrix_instance_f16 *pDst)

Floating-point matrix transpose.

Floating-point complex matrix transpose.

Parameters

- **pSrc** – **[in]** points to input matrix
- **pDst** – **[out]** points to output matrix

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_cmplx_trans_f32**(const riscv_matrix_instance_f32 *pSrc, riscv_matrix_instance_f32 *pDst)

Floating-point matrix transpose.

Floating-point complex matrix transpose.

Parameters

- **pSrc** – **[in]** points to input matrix
- **pDst** – **[out]** points to output matrix

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_cmplx_trans_q15**(const riscv_matrix_instance_q15 *pSrc, riscv_matrix_instance_q15 *pDst)

Q15 complex matrix transpose.

Parameters

- **pSrc** – **[in]** points to input matrix
- **pDst** – **[out]** points to output matrix

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_cmplx_trans_q31**(const riscv_matrix_instance_q31 *pSrc, riscv_matrix_instance_q31 *pDst)

Q31 complex matrix transpose.

Parameters

- **pSrc** – **[in]** points to input matrix
- **pDst** – **[out]** points to output matrix

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

Matrix Initialization

void **riscv_mat_init_f16**(riscv_matrix_instance_f16 *S, uint16_t nRows, uint16_t nColumns, float16_t *pData)

void **riscv_mat_init_f32**(riscv_matrix_instance_f32 *S, uint16_t nRows, uint16_t nColumns, float32_t *pData)

void **riscv_mat_init_f64**(riscv_matrix_instance_f64 *S, uint16_t nRows, uint16_t nColumns, float64_t *pData)

void **riscv_mat_init_q15**(riscv_matrix_instance_q15 *S, uint16_t nRows, uint16_t nColumns, q15_t *pData)

void **riscv_mat_init_q31**(riscv_matrix_instance_q31 *S, uint16_t nRows, uint16_t nColumns, q31_t *pData)

void **riscv_mat_init_q7**(riscv_matrix_instance_q7 *S, uint16_t nRows, uint16_t nColumns, q7_t *pData)

group `MatrixInit`

Initializes the underlying matrix data structure. The functions set the `numRows`, `numCols`, and `pData` fields of the matrix data structure.

Functions

void **riscv_mat_init_f16**(riscv_matrix_instance_f16 *S, uint16_t nRows, uint16_t nColumns, float16_t *pData)

Floating-point matrix initialization.

Parameters

- `S` – **[inout]** points to an instance of the floating-point matrix structure
- `nRows` – **[in]** number of rows in the matrix
- `nColumns` – **[in]** number of columns in the matrix
- `pData` – **[in]** points to the matrix data array

Returns none

void **riscv_mat_init_f32**(riscv_matrix_instance_f32 *S, uint16_t nRows, uint16_t nColumns, float32_t *pData)

Floating-point matrix initialization.

Parameters

- `S` – **[inout]** points to an instance of the floating-point matrix structure
- `nRows` – **[in]** number of rows in the matrix
- `nColumns` – **[in]** number of columns in the matrix
- `pData` – **[in]** points to the matrix data array

Returns none

void **riscv_mat_init_f64**(riscv_matrix_instance_f64 *S, uint16_t nRows, uint16_t nColumns, float64_t *pData)

Floating-point matrix initialization.

Parameters

- `S` – **[inout]** points to an instance of the floating-point matrix structure
- `nRows` – **[in]** number of rows in the matrix
- `nColumns` – **[in]** number of columns in the matrix
- `pData` – **[in]** points to the matrix data array

Returns none

void **riscv_mat_init_q15**(riscv_matrix_instance_q15 *S, uint16_t nRows, uint16_t nColumns, q15_t *pData)

Q15 matrix initialization.

Parameters

- `S` – **[inout]** points to an instance of the floating-point matrix structure
- `nRows` – **[in]** number of rows in the matrix
- `nColumns` – **[in]** number of columns in the matrix
- `pData` – **[in]** points to the matrix data array

Returns none

void **riscv_mat_init_q31**(riscv_matrix_instance_q31 *S, uint16_t nRows, uint16_t nColumns, q31_t *pData)

Q31 matrix initialization.

Parameters

- **S** – **[inout]** points to an instance of the Q31 matrix structure
- **nRows** – **[in]** number of rows in the matrix
- **nColumns** – **[in]** number of columns in the matrix
- **pData** – **[in]** points to the matrix data array

Returns none

void **riscv_mat_init_q7**(riscv_matrix_instance_q7 *S, uint16_t nRows, uint16_t nColumns, q7_t *pData)

Q7 matrix initialization.

Parameters

- **S** – **[inout]** points to an instance of the floating-point matrix structure
- **nRows** – **[in]** number of rows in the matrix
- **nColumns** – **[in]** number of columns in the matrix
- **pData** – **[in]** points to the matrix data array

Returns none

Matrix Inverse

riscv_status **riscv_mat_inverse_f16**(const riscv_matrix_instance_f16 *pSrc, riscv_matrix_instance_f16 *pDst)

riscv_status **riscv_mat_inverse_f32**(const riscv_matrix_instance_f32 *pSrc, riscv_matrix_instance_f32 *pDst)

riscv_status **riscv_mat_inverse_f64**(const riscv_matrix_instance_f64 *pSrc, riscv_matrix_instance_f64 *pDst)

riscv_status **riscv_mat_solve_lower_triangular_f16**(const riscv_matrix_instance_f16 *lt, const riscv_matrix_instance_f16 *a, riscv_matrix_instance_f16 *dst)

riscv_status **riscv_mat_solve_lower_triangular_f32**(const riscv_matrix_instance_f32 *lt, const riscv_matrix_instance_f32 *a, riscv_matrix_instance_f32 *dst)

riscv_status **riscv_mat_solve_lower_triangular_f64**(const riscv_matrix_instance_f64 *lt, const riscv_matrix_instance_f64 *a, riscv_matrix_instance_f64 *dst)

riscv_status **riscv_mat_solve_upper_triangular_f16**(const riscv_matrix_instance_f16 *ut, const riscv_matrix_instance_f16 *a, riscv_matrix_instance_f16 *dst)

riscv_status **riscv_mat_solve_upper_triangular_f32**(const riscv_matrix_instance_f32 *ut, const riscv_matrix_instance_f32 *a, riscv_matrix_instance_f32 *dst) riscv_status **riscv_mat_solve_upper_triangular_f64**(const riscv_matrix_instance_f64 *ut, const riscv_matrix_instance_f64 *a, riscv_matrix_instance_f64 *dst)

group **MatrixInv**

Computes the inverse of a matrix.

The inverse is defined only if the input matrix is square and non-singular (the determinant is non-zero). The function checks that the input and output matrices are square and of the same size.

Matrix inversion is numerically sensitive and the NMSIS DSP library only supports matrix inversion of floating-point matrices.

$$\begin{pmatrix} a_{1,1} & a_{1,2} & a_{1,3} & | & 1 & 0 & 0 \\ a_{2,1} & a_{2,2} & a_{2,3} & | & 0 & 1 & 0 \\ a_{3,1} & a_{3,2} & a_{3,3} & | & 0 & 0 & 1 \end{pmatrix} \rightarrow \begin{pmatrix} 1 & 0 & 0 & | & x_{1,1} & x_{2,1} & x_{3,1} \\ 0 & 1 & 0 & | & x_{1,2} & x_{2,2} & x_{3,2} \\ 0 & 0 & 1 & | & x_{1,3} & x_{2,3} & x_{3,3} \end{pmatrix}$$

Algorithm The Gauss-Jordan method is used to find the inverse. The algorithm performs a sequence of elementary row-operations until it reduces the input matrix to an identity matrix. Applying the same sequence of elementary row-operations to an identity matrix yields the inverse matrix. If the input matrix is singular, then the algorithm terminates and returns error status `RISCV_MATH_SINGULAR`.

Matrix Inverse of a 3 x 3 matrix using Gauss-Jordan Method

Functions

riscv_status **riscv_mat_inverse_f16**(const riscv_matrix_instance_f16 *pSrc, riscv_matrix_instance_f16 *pDst)

Floating-point matrix inverse.

Parameters

- **pSrc** – **[in]** points to input matrix structure. The source matrix is modified by the function.
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed
- RISCV_MATH_SINGULAR : Input matrix is found to be singular (non-invertible)

riscv_status **riscv_mat_inverse_f32**(const riscv_matrix_instance_f32 *pSrc, riscv_matrix_instance_f32 *pDst)

Floating-point matrix inverse.

Parameters

- **pSrc** – **[in]** points to input matrix structure. The source matrix is modified by the function.
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

- RISCV_MATH_SINGULAR : Input matrix is found to be singular (non-invertible)

riscv_status **riscv_mat_inverse_f64**(const riscv_matrix_instance_f64 *pSrc, riscv_matrix_instance_f64 *pDst)

Floating-point (64 bit) matrix inverse.

Floating-point matrix inverse.

Parameters

- **pSrc** – **[in]** points to input matrix structure. The source matrix is modified by the function.
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed
- RISCV_MATH_SINGULAR : Input matrix is found to be singular (non-invertible)

riscv_status **riscv_mat_solve_lower_triangular_f16**(const riscv_matrix_instance_f16 *lt, const riscv_matrix_instance_f16 *a, riscv_matrix_instance_f16 *dst)

Solve LT . X = A where LT is a lower triangular matrix.

Parameters

- **lt** – **[in]** The lower triangular matrix
- **a** – **[in]** The matrix a
- **dst** – **[out]** The solution X of LT . X = A

Returns The function returns RISCV_MATH_SINGULAR, if the system can't be solved.

riscv_status **riscv_mat_solve_lower_triangular_f32**(const riscv_matrix_instance_f32 *lt, const riscv_matrix_instance_f32 *a, riscv_matrix_instance_f32 *dst)

Solve LT . X = A where LT is a lower triangular matrix.

Parameters

- **lt** – **[in]** The lower triangular matrix
- **a** – **[in]** The matrix a
- **dst** – **[out]** The solution X of LT . X = A

Returns The function returns RISCV_MATH_SINGULAR, if the system can't be solved. Notice: The instruction vfredusum may introduce errors. So, if we use the V-extension implementation, we have to accept the errors that may happen in this function.

riscv_status **riscv_mat_solve_lower_triangular_f64**(const riscv_matrix_instance_f64 *lt, const riscv_matrix_instance_f64 *a, riscv_matrix_instance_f64 *dst)

Solve LT . X = A where LT is a lower triangular matrix.

Parameters

- **lt** – **[in]** The lower triangular matrix
- **a** – **[in]** The matrix a
- **dst** – **[out]** The solution X of LT . X = A

Returns The function returns RISCV_MATH_SINGULAR, if the system can't be solved. Notice: The instruction vfredusum may introduce errors. So, if we use the V-extension implementation, we have to accept the errors that may happen in this function.

riscv_status **riscv_mat_solve_upper_triangular_f16**(const riscv_matrix_instance_f16 *ut, const riscv_matrix_instance_f16 *a, riscv_matrix_instance_f16 *dst)

Solve UT . X = A where UT is an upper triangular matrix.

Parameters

- **ut** – **[in]** The upper triangular matrix
- **a** – **[in]** The matrix a
- **dst** – **[out]** The solution X of UT . X = A

Returns The function returns RISCV_MATH_SINGULAR, if the system can't be solved.

riscv_status **riscv_mat_solve_upper_triangular_f32**(const riscv_matrix_instance_f32 *ut, const riscv_matrix_instance_f32 *a, riscv_matrix_instance_f32 *dst)

Solve UT . X = A where UT is an upper triangular matrix.

Parameters

- **ut** – **[in]** The upper triangular matrix
- **a** – **[in]** The matrix a
- **dst** – **[out]** The solution X of UT . X = A

Returns The function returns RISCV_MATH_SINGULAR, if the system can't be solved. Notice: The instruction vfredusum may introduce errors. So, if we use the V-extension implementation, we have to accept the errors that may happen in this function.

riscv_status **riscv_mat_solve_upper_triangular_f64**(const riscv_matrix_instance_f64 *ut, const riscv_matrix_instance_f64 *a, riscv_matrix_instance_f64 *dst)

Solve UT . X = A where UT is an upper triangular matrix.

Parameters

- **ut** – **[in]** The upper triangular matrix
- **a** – **[in]** The matrix a
- **dst** – **[out]** The solution X of UT . X = A

Returns The function returns RISCV_MATH_SINGULAR, if the system can't be solved. Notice: The instruction vfredusum may introduce errors. So, if we use the V-extension implementation, we have to accept the errors that may happen in this function.

Matrix Multiplication

riscv_status **riscv_mat_mult_f16**(const riscv_matrix_instance_f16 *pSrcA, const riscv_matrix_instance_f16 *pSrcB, riscv_matrix_instance_f16 *pDst)

riscv_status **riscv_mat_mult_f32**(const riscv_matrix_instance_f32 *pSrcA, const riscv_matrix_instance_f32 *pSrcB, riscv_matrix_instance_f32 *pDst)

riscv_status **riscv_mat_mult_f64**(const riscv_matrix_instance_f64 *pSrcA, const riscv_matrix_instance_f64 *pSrcB, riscv_matrix_instance_f64 *pDst)

riscv_status **riscv_mat_mult_fast_q15**(const riscv_matrix_instance_q15 *pSrcA, const riscv_matrix_instance_q15 *pSrcB, riscv_matrix_instance_q15 *pDst, q15_t *pState)

riscv_status **riscv_mat_mult_fast_q31**(const riscv_matrix_instance_q31 *pSrcA, const riscv_matrix_instance_q31 *pSrcB, riscv_matrix_instance_q31 *pDst)

riscv_status **riscv_mat_mult_opt_q31**(const riscv_matrix_instance_q31 *pSrcA, const riscv_matrix_instance_q31 *pSrcB, riscv_matrix_instance_q31 *pDst, q31_t *pState)

riscv_status **riscv_mat_mult_q15**(const riscv_matrix_instance_q15 *pSrcA, const riscv_matrix_instance_q15 *pSrcB, riscv_matrix_instance_q15 *pDst, q15_t *pState)

riscv_status **riscv_mat_mult_q31**(const riscv_matrix_instance_q31 *pSrcA, const riscv_matrix_instance_q31 *pSrcB, riscv_matrix_instance_q31 *pDst)

riscv_status **riscv_mat_mult_q7**(const riscv_matrix_instance_q7 *pSrcA, const riscv_matrix_instance_q7 *pSrcB, riscv_matrix_instance_q7 *pDst, q7_t *pState)

group **MatrixMult**

Multiplies two matrices.

$$\begin{pmatrix} a_{1,1} & a_{1,2} & a_{1,3} \\ a_{2,1} & a_{2,2} & a_{2,3} \\ a_{3,1} & a_{3,2} & a_{3,3} \end{pmatrix} \begin{pmatrix} b_{1,1} & b_{1,2} & b_{1,3} \\ b_{2,1} & b_{2,2} & b_{2,3} \\ b_{3,1} & b_{3,2} & b_{3,3} \end{pmatrix} = \begin{pmatrix} a_{1,1}b_{1,1} + a_{1,2}b_{2,1} + a_{1,3}b_{3,1} & a_{1,1}b_{1,2} + a_{1,2}b_{2,2} + a_{1,3}b_{3,2} & a_{1,1}b_{1,3} + a_{1,2}b_2 \\ a_{2,1}b_{1,1} + a_{2,2}b_{2,1} + a_{2,3}b_{3,1} & a_{2,1}b_{1,2} + a_{2,2}b_{2,2} + a_{2,3}b_{3,2} & a_{2,1}b_{1,3} + a_{2,2}b_2 \\ a_{3,1}b_{1,1} + a_{3,2}b_{2,1} + a_{3,3}b_{3,1} & a_{3,1}b_{1,2} + a_{3,2}b_{2,2} + a_{3,3}b_{3,2} & a_{3,1}b_{1,3} + a_{3,2}b_2 \end{pmatrix}$$

Multiplication of two 3x3 matrices:

Matrix multiplication is only defined if the number of columns of the first matrix equals the number of rows of the second matrix. Multiplying an `M x N` matrix with an `N x P` matrix results in an `M x P` matrix. When matrix size checking is enabled, the functions check: (1) that the inner dimensions of `pSrcA` and `pSrcB` are equal; and (2) that the size of the output matrix equals the outer dimensions of `pSrcA` and `pSrcB`.

$$\begin{bmatrix} a_{11} & a_{12} & a_{13} \\ a_{21} & a_{22} & a_{23} \\ a_{31} & a_{32} & a_{33} \end{bmatrix} \times \begin{bmatrix} b_{11} & b_{12} & b_{13} \\ b_{21} & b_{22} & b_{23} \\ b_{31} & b_{32} & b_{33} \end{bmatrix} = \begin{bmatrix} a_{11}\times b_{11}+a_{12}\times b_{21}+a_{13}\times b_{31} & a_{11}\times b_{12}+a_{12}\times b_{22}+a_{13}\times b_{32} & a_{11}\times b_{13}+a_{12}\times b_{23}+a_{13}\times b_{33} \\ a_{21}\times b_{11}+a_{22}\times b_{21}+a_{23}\times b_{31} & a_{21}\times b_{12}+a_{22}\times b_{22}+a_{23}\times b_{32} & a_{21}\times b_{13}+a_{22}\times b_{23}+a_{23}\times b_{33} \\ a_{31}\times b_{11}+a_{32}\times b_{21}+a_{33}\times b_{31} & a_{31}\times b_{12}+a_{32}\times b_{22}+a_{33}\times b_{32} & a_{31}\times b_{13}+a_{32}\times b_{23}+a_{33}\times b_{33} \end{bmatrix}$$

Matrix multiplication is only defined if the number of columns of the first matrix equals the number of rows of the second matrix. Multiplying an `M x N` matrix with an `N x P` matrix results in an `M x P` matrix. When matrix size checking is enabled, the functions check: (1) that the inner dimensions of `pSrcA` and `pSrcB` are equal; and (2) that the size of the output matrix equals the outer dimensions of `pSrcA` and `pSrcB`.

Functions

riscv_status **riscv_mat_mult_f16**(const riscv_matrix_instance_f16 *pSrcA, const riscv_matrix_instance_f16 *pSrcB, riscv_matrix_instance_f16 *pDst)

Floating-point matrix multiplication.

Parameters

- **`*pSrcA`** – **[in]** points to the first input matrix structure
- **`*pSrcB`** – **[in]** points to the second input matrix structure
- **`*pDst`** – **[out]** points to output matrix structure

Returns The function returns either `RISCV_MATH_SIZE_MISMATCH` or `RISCV_MATH_SUCCESS` based on the outcome of size checking.

riscv_status **riscv_mat_mult_f32**(const riscv_matrix_instance_f32 *pSrcA, const riscv_matrix_instance_f32 *pSrcB, riscv_matrix_instance_f32 *pDst)

Floating-point matrix multiplication.

Parameters

- **`*pSrcA`** – **[in]** points to the first input matrix structure
- **`*pSrcB`** – **[in]** points to the second input matrix structure
- **`*pDst`** – **[out]** points to output matrix structure

Returns The function returns either `RISCV_MATH_SIZE_MISMATCH` or `RISCV_MATH_SUCCESS` based on the outcome of size checking.

riscv_status **riscv_mat_mult_f64**(const riscv_matrix_instance_f64 *pSrcA, const riscv_matrix_instance_f64 *pSrcB, riscv_matrix_instance_f64 *pDst)

Floating-point matrix multiplication.

Parameters

- **`*pSrcA`** – **[in]** points to the first input matrix structure
- **`*pSrcB`** – **[in]** points to the second input matrix structure
- **`*pDst`** – **[out]** points to output matrix structure

Returns The function returns either `RISCV_MATH_SIZE_MISMATCH` or `RISCV_MATH_SUCCESS` based on the outcome of size checking.

riscv_status **riscv_mat_mult_fast_q15**(const riscv_matrix_instance_q15 *pSrcA, const riscv_matrix_instance_q15 *pSrcB, riscv_matrix_instance_q15 *pDst, q15_t *pState)

Q15 matrix multiplication (fast variant).

Q15 matrix multiplication (fast variant) for RISC-V Core with DSP enabled.

Remark

Refer to riscv_mat_mult_q15() for a slower implementation of this function which uses 64-bit accumulation to provide higher precision.

Scaling and Overflow Behavior The difference between the function riscv_mat_mult_q15() and this fast variant is that the fast variant use a 32-bit rather than a 64-bit accumulator. The result of each 1.15 x 1.15 multiplication is truncated to 2.30 format. These intermediate results are accumulated in a 32-bit register in 2.30 format. Finally, the accumulator is saturated and converted to a 1.15 result.

The fast version has the same overflow behavior as the standard version but provides less precision since it discards the low 16 bits of each multiplication result. In order to avoid overflows completely the input signals must be scaled down. Scale down one of the input matrices by log2(numColsA) bits to avoid overflows, as a total of numColsA additions are computed internally for each output element.

Parameters

- `pSrcA` – **[in]** points to the first input matrix structure
- `pSrcB` – **[in]** points to the second input matrix structure
- `pDst` – **[out]** points to output matrix structure
- `pState` – **[in]** points to the array for storing intermediate results

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_mult_fast_q31**(const riscv_matrix_instance_q31 *pSrcA, const riscv_matrix_instance_q31 *pSrcB, riscv_matrix_instance_q31 *pDst)

Q31 matrix multiplication (fast variant).

Q31 matrix multiplication (fast variant) for RISC-V Core with DSP enabled.

Remark

Refer to riscv_mat_mult_q31() for a slower implementation of this function which uses 64-bit accumulation to provide higher precision.

Scaling and Overflow Behavior The difference between the function riscv_mat_mult_q31() and this fast variant is that the fast variant use a 32-bit rather than a 64-bit accumulator. The result of each 1.31 x 1.31 multiplication is truncated to 2.30 format. These intermediate results are accumulated in a 32-bit register in 2.30 format. Finally, the accumulator is saturated and converted to a 1.31 result.

The fast version has the same overflow behavior as the standard version but provides less precision since it discards the low 32 bits of each multiplication result. In order to avoid overflows completely the input signals must be scaled down. Scale down one of the input matrices by log2(numColsA) bits to avoid overflows, as a total of numColsA additions are computed internally for each output element.

Parameters

- `pSrcA` – **[in]** points to the first input matrix structure
- `pSrcB` – **[in]** points to the second input matrix structure
- `pDst` – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful

- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_mult_opt_q31**(const riscv_matrix_instance_q31 *pSrcA, const riscv_matrix_instance_q31 *pSrcB, riscv_matrix_instance_q31 *pDst, q31_t *pState)

Q31 matrix multiplication.

Remark

Refer to riscv_mat_mult_fast_q31() for a faster but less precise implementation of this function.

Remark

This function is a faster implementation of riscv_mat_mult_q31 for MVE but it is requiring additional storage for intermediate results.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The accumulator has a 2.62 format and maintains full precision of the intermediate multiplication results but provides only a single guard bit. There is no saturation on intermediate additions. Thus, if the accumulator overflows it wraps around and distorts the result. The input signals should be scaled down to avoid intermediate overflows. The input is thus scaled down by log2(numColsA) bits to avoid overflows, as a total of numColsA additions are performed internally. The 2.62 accumulator is right shifted by 31 bits and saturated to 1.31 format to yield the final result.

Parameters

- **pSrcA** – **[in]** points to the first input matrix structure
- **pSrcB** – **[in]** points to the second input matrix structure
- **pDst** – **[out]** points to output matrix structure
- **pState** – **[in]** points to the array for storing intermediate results

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_mult_q15**(const riscv_matrix_instance_q15 *pSrcA, const riscv_matrix_instance_q15 *pSrcB, riscv_matrix_instance_q15 *pDst, q15_t *pState)

Q15 matrix multiplication.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The inputs to the multiplications are in 1.15 format and multiplications yield a 2.30 result. The 2.30 intermediate results are accumulated in a 64-bit accumulator in 34.30 format. This approach provides 33 guard bits and there is no risk of overflow. The 34.30 result is then truncated to 34.15 format by discarding the low 15 bits and then saturated to 1.15 format.

Refer to riscv_mat_mult_fast_q15() for a faster but less precise version of this function.

Parameters

- **pSrcA** – **[in]** points to the first input matrix structure
- **pSrcB** – **[in]** points to the second input matrix structure
- **pDst** – **[out]** points to output matrix structure
- **pState** – **[in]** points to the array for storing intermediate results

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_mult_q31**(const riscv_matrix_instance_q31 *pSrcA, const riscv_matrix_instance_q31 *pSrcB, riscv_matrix_instance_q31 *pDst)

Q31 matrix multiplication.

Remark

Refer to riscv_mat_mult_fast_q31() for a faster but less precise implementation of this function.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The accumulator has a 2.62 format and maintains full precision of the intermediate multiplication results but provides only a single guard bit. There is no saturation on intermediate additions. Thus, if the accumulator overflows it wraps around and distorts the result. The input signals should be scaled down to avoid intermediate overflows. The input is thus scaled down by log2(numColsA) bits to avoid overflows, as a total of numColsA additions are performed internally. The 2.62 accumulator is right shifted by 31 bits and saturated to 1.31 format to yield the final result.

Parameters

- **pSrcA** – **[in]** points to the first input matrix structure
- **pSrcB** – **[in]** points to the second input matrix structure
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_mult_q7**(const riscv_matrix_instance_q7 *pSrcA, const riscv_matrix_instance_q7 *pSrcB, riscv_matrix_instance_q7 *pDst, q7_t *pState)

Q7 matrix multiplication.

Scaling and Overflow Behavior:

The function is implemented using a 32-bit internal accumulator saturated to 1.7 format.

Parameters

- ***pSrcA** – **[in]** points to the first input matrix structure

- ***pSrcB** – **[in]** points to the second input matrix structure
- ***pDst** – **[out]** points to output matrix structure
- ***pState** – **[in]** points to the array for storing intermediate results (Unused in some versions)

Returns The function returns either `RISCV_MATH_SIZE_MISMATCH` or `RISCV_MATH_SUCCESS` based on the outcome of size checking.

QR decomposition of a Matrix

riscv_status **riscv_mat_qr_f16**(const riscv_matrix_instance_f16 *pSrc, const float16_t threshold, riscv_matrix_instance_f16 *pOutR, riscv_matrix_instance_f16 *pOutQ, float16_t *pOutTau, float16_t *pTmpA, float16_t *pTmpB)

riscv_status **riscv_mat_qr_f32**(const riscv_matrix_instance_f32 *pSrc, const float32_t threshold, riscv_matrix_instance_f32 *pOutR, riscv_matrix_instance_f32 *pOutQ, float32_t *pOutTau, float32_t *pTmpA, float32_t *pTmpB)

riscv_status **riscv_mat_qr_f64**(const riscv_matrix_instance_f64 *pSrc, const float64_t threshold, riscv_matrix_instance_f64 *pOutR, riscv_matrix_instance_f64 *pOutQ, float64_t *pOutTau, float64_t *pTmpA, float64_t *pTmpB)

group **MatrixQR**

Computes the QR decomposition of a matrix M using Householder algorithm.

$$M = QR$$

where Q is an orthogonal matrix and R is upper triangular. No pivoting strategy is used.

The returned value for R is using a format a bit similar to LAPACK : it is not just containing the matrix R but also the Householder reflectors.

The function is also returning a vector τ that is containing the scaling factor for the reflectors.

Returned value R has the structure:

$$\begin{pmatrix} r_{11} & r_{12} & \dots & r_{1n} \\ v_{12} & r_{22} & \dots & r_{2n} \\ v_{13} & v_{22} & \dots & r_{3n} \\ \vdots & \vdots & \ddots & \vdots \\ v_{1m} & v_{2(m-1)} & \dots & r_{mn} \end{pmatrix}$$

where

$$v_1 = \begin{pmatrix} 1 \\ v_{12} \\ \vdots \\ v_{1m} \end{pmatrix}$$

is the first householder reflector.

The Householder Matrix is given by H_1

$$H_1 = I - \tau_1 v_1 v_1^T$$

The Matrix Q is the product of the Householder matrices:

$$Q = H_1 H_2 \dots H_n$$

The computation of the matrix Q by this function is optional.

And the matrix R, would be the returned value R without the householder reflectors:

$$\begin{pmatrix} r_{11} & r_{12} & \dots & r_{1n} \\ 0 & r_{22} & \dots & r_{2n} \\ 0 & 0 & \dots & r_{3n} \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \dots & r_{mn} \end{pmatrix}$$

Functions

riscv_status **`riscv_mat_qr_f16`**(const riscv_matrix_instance_f16 *pSrc, const float16_t threshold, riscv_matrix_instance_f16 *pOutR, riscv_matrix_instance_f16 *pOutQ, float16_t *pOutTau, float16_t *pTmpA, float16_t *pTmpB)

QR decomposition of a m x n half floating point matrix with m >= n.

QR decomposition of a m x n floating point matrix with m >= n.

pOutQ is optional: pOutQ can be a NULL pointer. In this case, the argument will be ignored and the output Q matrix won't be computed.

f16 implementation The f16 implementation is not very accurate.

Norm2 threshold For the meaning of this argument please refer to the *Householder transform of a vector* (page 797) documentation

Parameters

- **`pSrc`** – **[in]** points to input matrix structure. The source matrix is modified by the function.
- **`threshold`** – **[in]** norm2 threshold.
- **`pOutR`** – **[out]** points to output R matrix structure of dimension m x n
- **`pOutQ`** – **[out]** points to output Q matrix structure of dimension m x m (can be NULL)
- **`pOutTau`** – **[out]** points to Householder scaling factors of dimension n
- **`pTmpA`** – **[inout]** points to a temporary vector of dimension m.
- **`pTmpB`** – **[inout]** points to a temporary vector of dimension m.

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_qr_f32**(const riscv_matrix_instance_f32 *pSrc, const float32_t threshold, riscv_matrix_instance_f32 *pOutR, riscv_matrix_instance_f32 *pOutQ, float32_t *pOutTau, float32_t *pTmpA, float32_t *pTmpB)

QR decomposition of a m x n floating point matrix with m >= n.

pOutQ is optional: pOutQ can be a NULL pointer. In this case, the argument will be ignored and the output Q matrix won't be computed.

Norm2 threshold For the meaning of this argument please refer to the *Householder transform of a vector* (page 797) documentation

Parameters

- **pSrc** – **[in]** points to input matrix structure. The source matrix is modified by the function.
- **threshold** – **[in]** norm2 threshold.
- **pOutR** – **[out]** points to output R matrix structure of dimension m x n
- **pOutQ** – **[out]** points to output Q matrix structure of dimension m x m (can be NULL)
- **pOutTau** – **[out]** points to Householder scaling factors of dimension n
- **pTmpA** – **[inout]** points to a temporary vector of dimension m.
- **pTmpB** – **[inout]** points to a temporary vector of dimension m.

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_qr_f64**(const riscv_matrix_instance_f64 *pSrc, const float64_t threshold, riscv_matrix_instance_f64 *pOutR, riscv_matrix_instance_f64 *pOutQ, float64_t *pOutTau, float64_t *pTmpA, float64_t *pTmpB)

QR decomposition of a m x n double floating point matrix with m >= n.

QR decomposition of a m x n floating point matrix with m >= n.

pOutQ is optional: pOutQ can be a NULL pointer. In this case, the argument will be ignored and the output Q matrix won't be computed.

Norm2 threshold For the meaning of this argument please refer to the *Householder transform of a vector* (page 797) documentation

Parameters

- **pSrc** – **[in]** points to input matrix structure. The source matrix is modified by the function.
- **threshold** – **[in]** norm2 threshold.
- **pOutR** – **[out]** points to output R matrix structure of dimension m x n
- **pOutQ** – **[out]** points to output Q matrix structure of dimension m x m (can be NULL)

- **pOutTau** – **[out]** points to Householder scaling factors of dimension n
- **pTmpA** – **[inout]** points to a temporary vector of dimension m.
- **pTmpB** – **[inout]** points to a temporary vector of dimension m.

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

Matrix Scale

riscv_status **riscv_mat_scale_f16**(const riscv_matrix_instance_f16 *pSrc, float16_t scale, riscv_matrix_instance_f16 *pDst)

riscv_status **riscv_mat_scale_f32**(const riscv_matrix_instance_f32 *pSrc, float32_t scale, riscv_matrix_instance_f32 *pDst)

riscv_status **riscv_mat_scale_q15**(const riscv_matrix_instance_q15 *pSrc, q15_t scaleFract, int32_t shift, riscv_matrix_instance_q15 *pDst)

riscv_status **riscv_mat_scale_q31**(const riscv_matrix_instance_q31 *pSrc, q31_t scaleFract, int32_t shift, riscv_matrix_instance_q31 *pDst)

group **MatrixScale**

Multiplies a matrix by a scalar. This is accomplished by multiplying each element in the matrix by the scalar. For example:

$$\begin{pmatrix} a_{1,1} & a_{1,2} & a_{1,3} \\ a_{2,1} & a_{2,2} & a_{2,3} \\ a_{3,1} & a_{3,2} & a_{3,3} \end{pmatrix} K = \begin{pmatrix} Ka_{1,1} & Ka_{1,2} & Ka_{1,3} \\ Ka_{2,1} & Ka_{2,2} & Ka_{2,3} \\ Ka_{3,1} & Ka_{3,2} & Ka_{3,3} \end{pmatrix}$$

Matrix Scaling of a 3 x 3 matrix

The function checks to make sure that the input and output matrices are of the same size.

In the fixed-point Q15 and Q31 functions, `scale` is represented by a fractional multiplication `scaleFract` and an arithmetic shift `shift`. The shift allows the gain of the scaling operation to exceed 1.0. The overall scale factor applied to the fixed-point data is

Functions

riscv_status **riscv_mat_scale_f16**(const riscv_matrix_instance_f16 *pSrc, float16_t scale, riscv_matrix_instance_f16 *pDst)

Floating-point matrix scaling.

Parameters

- **pSrc** – **[in]** points to input matrix
- **scale** – **[in]** scale factor to be applied
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_scale_f32**(const riscv_matrix_instance_f32 *pSrc, float32_t scale, riscv_matrix_instance_f32 *pDst)

Floating-point matrix scaling.

Parameters

- **pSrc** – **[in]** points to input matrix
- **scale** – **[in]** scale factor to be applied
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_scale_q15**(const riscv_matrix_instance_q15 *pSrc, q15_t scaleFract, int32_t shift, riscv_matrix_instance_q15 *pDst)

Q15 matrix scaling.

Scaling and Overflow Behavior The input data `*pSrc` and `scaleFract` are in 1.15 format. These are multiplied to yield a 2.30 intermediate result and this is shifted with saturation to 1.15 format.

Parameters

- **pSrc** – **[in]** points to input matrix
- **scaleFract** – **[in]** fractional portion of the scale factor
- **shift** – **[in]** number of bits to shift the result by
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_scale_q31**(const riscv_matrix_instance_q31 *pSrc, q31_t scaleFract, int32_t shift, riscv_matrix_instance_q31 *pDst)

Q31 matrix scaling.

Scaling and Overflow Behavior The input data `*pSrc` and `scaleFract` are in 1.31 format. These are multiplied to yield a 2.62 intermediate result which is shifted with saturation to 1.31 format.

Parameters

- **pSrc** – **[in]** points to input matrix
- **scaleFract** – **[in]** fractional portion of the scale factor
- **shift** – **[in]** number of bits to shift the result by
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

Matrix Subtraction

riscv_status **riscv_mat_sub_f16**(const riscv_matrix_instance_f16 *pSrcA, const riscv_matrix_instance_f16 *pSrcB, riscv_matrix_instance_f16 *pDst)

riscv_status **riscv_mat_sub_f32**(const riscv_matrix_instance_f32 *pSrcA, const riscv_matrix_instance_f32 *pSrcB, riscv_matrix_instance_f32 *pDst)

riscv_status **riscv_mat_sub_f64**(const riscv_matrix_instance_f64 *pSrcA, const riscv_matrix_instance_f64 *pSrcB, riscv_matrix_instance_f64 *pDst)

riscv_status **riscv_mat_sub_q15**(const riscv_matrix_instance_q15 *pSrcA, const riscv_matrix_instance_q15 *pSrcB, riscv_matrix_instance_q15 *pDst)

riscv_status **riscv_mat_sub_q31**(const riscv_matrix_instance_q31 *pSrcA, const riscv_matrix_instance_q31 *pSrcB, riscv_matrix_instance_q31 *pDst)

group **MatrixSub**

Subtract two matrices.

$$\begin{pmatrix} a_{1,1} & a_{1,2} & a_{1,3} \\ a_{2,1} & a_{2,2} & a_{2,3} \\ a_{3,1} & a_{3,2} & a_{3,3} \end{pmatrix} - \begin{pmatrix} b_{1,1} & b_{1,2} & b_{1,3} \\ b_{2,1} & b_{2,2} & b_{2,3} \\ b_{3,1} & b_{3,2} & b_{3,3} \end{pmatrix} = \begin{pmatrix} a_{1,1}-b_{1,1} & a_{1,2}-b_{1,2} & a_{1,3}-b_{1,3} \\ a_{2,1}-b_{2,1} & a_{2,2}-b_{2,2} & a_{2,3}-b_{2,3} \\ a_{3,1}-b_{3,1} & a_{3,2}-b_{3,2} & a_{3,3}-b_{3,3} \end{pmatrix}$$

The functions check to make sure that `pSrcA`, `pSrcB`, and `pDst` have the same number of rows and columns.

Subraction of two 3 x 3 matrices

Functions

riscv_status **riscv_mat_sub_f16**(const riscv_matrix_instance_f16 *pSrcA, const riscv_matrix_instance_f16 *pSrcB, riscv_matrix_instance_f16 *pDst)

Floating-point matrix subtraction.

Parameters

- **pSrcA** – **[in]** points to the first input matrix structure
- **pSrcB** – **[in]** points to the second input matrix structure
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_sub_f32**(const riscv_matrix_instance_f32 *pSrcA, const riscv_matrix_instance_f32 *pSrcB, riscv_matrix_instance_f32 *pDst)

Floating-point matrix subtraction.

Parameters

- **pSrcA** – **[in]** points to the first input matrix structure
- **pSrcB** – **[in]** points to the second input matrix structure
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_sub_f64**(const riscv_matrix_instance_f64 *pSrcA, const riscv_matrix_instance_f64 *pSrcB, riscv_matrix_instance_f64 *pDst)

Floating-point matrix subtraction.

Parameters

- **pSrcA** – **[in]** points to the first input matrix structure
- **pSrcB** – **[in]** points to the second input matrix structure
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_sub_q15**(const riscv_matrix_instance_q15 *pSrcA, const riscv_matrix_instance_q15 *pSrcB, riscv_matrix_instance_q15 *pDst)

Q15 matrix subtraction.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q15 range [0x8000 0x7FFF] are saturated.

Parameters

- **pSrcA** – **[in]** points to the first input matrix structure
- **pSrcB** – **[in]** points to the second input matrix structure
- **pDst** – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_sub_q31**(const riscv_matrix_instance_q31 *pSrcA, const riscv_matrix_instance_q31 *pSrcB, riscv_matrix_instance_q31 *pDst)

Q31 matrix subtraction.

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q31 range [0x80000000 0x7FFFFFFF] are saturated.

Parameters

- `pSrcA` – **[in]** points to the first input matrix structure
- `pSrcB` – **[in]** points to the second input matrix structure
- `pDst` – **[out]** points to output matrix structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

Matrix Transpose

riscv_status **riscv_mat_trans_f16**(const riscv_matrix_instance_f16 *pSrc, riscv_matrix_instance_f16 *pDst)

riscv_status **riscv_mat_trans_f32**(const riscv_matrix_instance_f32 *pSrc, riscv_matrix_instance_f32 *pDst)

riscv_status **riscv_mat_trans_f64**(const riscv_matrix_instance_f64 *pSrc, riscv_matrix_instance_f64 *pDst)

riscv_status **riscv_mat_trans_q15**(const riscv_matrix_instance_q15 *pSrc, riscv_matrix_instance_q15 *pDst)

riscv_status **riscv_mat_trans_q31**(const riscv_matrix_instance_q31 *pSrc, riscv_matrix_instance_q31 *pDst)

riscv_status **riscv_mat_trans_q7**(const riscv_matrix_instance_q7 *pSrc, riscv_matrix_instance_q7 *pDst)

group **MatrixTrans**

Tranposes a matrix.

Transposing an `M x N` matrix flips it around the center diagonal and results in an `N x M` matrix.

$$\begin{pmatrix} a_{1,1} & a_{1,2} & a_{1,3} \\ a_{2,1} & a_{2,2} & a_{2,3} \\ a_{3,1} & a_{3,2} & a_{3,3} \end{pmatrix}^T = \begin{pmatrix} a_{1,1} & a_{2,1} & a_{3,1} \\ a_{1,2} & a_{2,2} & a_{3,2} \\ a_{1,3} & a_{2,3} & a_{3,3} \end{pmatrix}$$

Transpose of a 3 x 3 matrix

Transposing an `M x N` matrix flips it around the center diagonal and results in an `N x M` matrix.



Functions

riscv_status **riscv_mat_trans_f16**(const riscv_matrix_instance_f16 *pSrc, riscv_matrix_instance_f16 *pDst)

Floating-point matrix transpose.

Parameters

- **pSrc** – **[in]** points to input matrix
- **pDst** – **[out]** points to output matrix

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_trans_f32**(const riscv_matrix_instance_f32 *pSrc, riscv_matrix_instance_f32 *pDst)

Floating-point matrix transpose.

Parameters

- **pSrc** – **[in]** points to input matrix
- **pDst** – **[out]** points to output matrix

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_trans_f64**(const riscv_matrix_instance_f64 *pSrc, riscv_matrix_instance_f64 *pDst)

Floating-point matrix transpose.

Parameters

- **pSrc** – **[in]** points to input matrix
- **pDst** – **[out]** points to output matrix

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_trans_q15**(const riscv_matrix_instance_q15 *pSrc, riscv_matrix_instance_q15 *pDst)

Q15 matrix transpose.

Parameters

- **pSrc** – **[in]** points to input matrix
- **pDst** – **[out]** points to output matrix

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_trans_q31**(const riscv_matrix_instance_q31 *pSrc, riscv_matrix_instance_q31 *pDst)

Q31 matrix transpose.

Parameters

- **pSrc** – **[in]** points to input matrix
- **pDst** – **[out]** points to output matrix

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

riscv_status **riscv_mat_trans_q7**(const riscv_matrix_instance_q7 *pSrc, riscv_matrix_instance_q7 *pDst)

Q7 matrix transpose.

Parameters

- **pSrc** – **[in]** points to input matrix
- **pDst** – **[out]** points to output matrix

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_SIZE_MISMATCH : Matrix size check failed

Matrix Vector Multiplication

void **riscv_mat_vec_mult_f16**(const riscv_matrix_instance_f16 *pSrcMat, const float16_t *pVec, float16_t *pDst)

void **riscv_mat_vec_mult_f32**(const riscv_matrix_instance_f32 *pSrcMat, const float32_t *pVec, float32_t *pDst)

void **riscv_mat_vec_mult_q15**(const riscv_matrix_instance_q15 *pSrcMat, const q15_t *pVec, q15_t *pDst)

void **riscv_mat_vec_mult_q31**(const riscv_matrix_instance_q31 *pSrcMat, const q31_t *pVec, q31_t *pDst)

void **riscv_mat_vec_mult_q7**(const riscv_matrix_instance_q7 *pSrcMat, const q7_t *pVec, q7_t *pDst)

group **MatrixVectMult**

Multiplies a matrix and a vector.

Functions

void **riscv_mat_vec_mult_f16**(const riscv_matrix_instance_f16 *pSrcMat, const float16_t *pVec, float16_t *pDst)

Floating-point matrix and vector multiplication.

Parameters

- ***pSrcMat** – **[in]** points to the input matrix structure
- ***pVec** – **[in]** points to input vector

- `*pDst` – **[out]** points to output vector

void **riscv_mat_vec_mult_f32**(const riscv_matrix_instance_f32 *pSrcMat, const float32_t *pVec, float32_t *pDst)

Floating-point matrix and vector multiplication.

Parameters

- `*pSrcMat` – **[in]** points to the input matrix structure
- `*pVec` – **[in]** points to input vector
- `*pDst` – **[out]** points to output vector

void **riscv_mat_vec_mult_q15**(const riscv_matrix_instance_q15 *pSrcMat, const q15_t *pVec, q15_t *pDst)

Q15 matrix and vector multiplication.

Parameters

- `*pSrcMat` – **[in]** points to the input matrix structure
- `*pVec` – **[in]** points to input vector
- `*pDst` – **[out]** points to output vector

void **riscv_mat_vec_mult_q31**(const riscv_matrix_instance_q31 *pSrcMat, const q31_t *pVec, q31_t *pDst)

Q31 matrix and vector multiplication.

Parameters

- `*pSrcMat` – **[in]** points to the input matrix structure
- `*pVec` – **[in]** points to the input vector
- `*pDst` – **[out]** points to the output vector

void **riscv_mat_vec_mult_q7**(const riscv_matrix_instance_q7 *pSrcMat, const q7_t *pVec, q7_t *pDst)

Q7 matrix and vector multiplication.

Parameters

- `*pSrcMat` – **[in]** points to the input matrix structure
- `*pVec` – **[in]** points to the input vector
- `*pDst` – **[out]** points to the output vector

group **groupMatrix**

This set of functions provides basic matrix math operations. The functions operate on matrix data structures. For example, the type definition for the floating-point matrix structure is shown below:

There are similar definitions for Q15 and Q31 data types.

The structure specifies the size of the matrix and then points to an array of data. The array is of size `numRows X numCols` and the values are arranged in row order. That is, the matrix element (i, j) is stored at:

Init Functions There is an associated initialization function for each type of matrix data structure. The initialization function sets the values of the internal structure fields. Refer to riscv_mat_init_f32(), riscv_mat_init_q31() and riscv_mat_init_q15() for floating-point, Q31 and Q15 types, respectively.

Use of the initialization function is optional. However, if initialization function is used then the instance structure cannot be placed into a const data section. To place the instance structure in a const data section, manually initialize the data structure. For example: where `nRows` specifies the number of rows, `nColumns` specifies the number of columns, and `pData` points to the data array.

Size Checking By default all of the matrix functions perform size checking on the input and output matrices. For example, the matrix addition function verifies that the two input matrices and the output matrix all have the same number of rows and columns. If the size check fails the functions return: Otherwise the functions return There is some overhead associated with this matrix size checking. The matrix size checking is enabled via the #define within the library project settings. By default this macro is defined and size checking is enabled. By changing the project settings and undefining this macro size checking is eliminated and the functions run a bit faster. With size checking disabled the functions always return `RISCV_MATH_SUCCESS`.

3.3.10 Quaternion Math Functions

Quaternion conversions

Quaternion to Rotation

void **riscv_quaternion2rotation_f32**(const float32_t *pInputQuaternions, float32_t *pOutputRotations, uint32_t nbQuaternions)

group **QuatRot**

Conversions from quaternion to rotation.

Functions

void **riscv_quaternion2rotation_f32**(const float32_t *pInputQuaternions, float32_t *pOutputRotations, uint32_t nbQuaternions)

Conversion of quaternion to equivalent rotation matrix.

The quaternion a + ib + jc + kd is converted into rotation matrix: Rotation matrix is saved in row order : R00 R01 R02 R10 R11 R12 R20 R21 R22

Format of rotation matrix

Parameters

- **pInputQuaternions** – **[in]** points to an array of normalized quaternions
- **pOutputRotations** – **[out]** points to an array of 3x3 rotations (in row order)
- **nbQuaternions** – **[in]** number of quaternions in the array

Returns none.

Rotation to Quaternion

void **riscv_rotation2quaternion_f32**(const float32_t *pInputRotations, float32_t *pOutputQuaternions, uint32_t nbQuaternions)

group **RotQuat**

Conversions from rotation to quaternion.

Functions

void **riscv_rotation2quaternion_f32**(const float32_t *pInputRotations, float32_t *pOutputQuaternions, uint32_t nbQuaternions)

Conversion of a rotation matrix to an equivalent quaternion.

Conversion of a rotation matrix to equivalent quaternion.

q and -q are representing the same rotation. This ambiguity must be taken into account when using the output of this function.

Parameters

- **pInputRotations** – **[in]** points to an array 3x3 rotation matrix (in row order)
- **pOutputQuaternions** – **[out]** points to an array quaternions
- **nbQuaternions** – **[in]** number of quaternions in the array

Returns none.

group **QuatConv**

Conversions between quaternion and rotation representations.

Quaternion Conjugate

void **riscv_quaternion_conjugate_f32**(const float32_t *pInputQuaternions, float32_t *pConjugateQuaternions, uint32_t nbQuaternions)

group **QuatConjugate**

Compute the conjugate of a quaternion.

Functions

void **riscv_quaternion_conjugate_f32**(const float32_t *pInputQuaternions, float32_t *pConjugateQuaternions, uint32_t nbQuaternions)

Floating-point quaternion conjugates.

Parameters

- **pInputQuaternions** – **[in]** points to the input vector of quaternions
- **pConjugateQuaternions** – **[out]** points to the output vector of conjugate quaternions
- **nbQuaternions** – **[in]** number of quaternions in each vector

Returns none

Quaternion Inverse

void **riscv_quaternion_inverse_f32**(const float32_t *pInputQuaternions, float32_t *pInverseQuaternions, uint32_t nbQuaternions)

group **QuatInverse**

Compute the inverse of a quaternion.

Functions

void **riscv_quaternion_inverse_f32**(const float32_t *pInputQuaternions, float32_t *pInverseQuaternions, uint32_t nbQuaternions)

Floating-point quaternion inverse.

Parameters

- **pInputQuaternions** – **[in]** points to the input vector of quaternions
- **pInverseQuaternions** – **[out]** points to the output vector of inverse quaternions
- **nbQuaternions** – **[in]** number of quaternions in each vector

Returns none

Quaternion Norm

void **riscv_quaternion_norm_f32**(const float32_t *pInputQuaternions, float32_t *pNorms, uint32_t nbQuaternions)

group **QuatNorm**

Compute the norm of a quaternion.

Functions

void **riscv_quaternion_norm_f32**(const float32_t *pInputQuaternions, float32_t *pNorms, uint32_t nbQuaternions)

Floating-point quaternion Norm.

Parameters

- **pInputQuaternions** – **[in]** points to the input vector of quaternions
- **pNorms** – **[out]** points to the output vector of norms
- **nbQuaternions** – **[in]** number of quaternions in the input vector

Returns none

Quaternion normalization

void **riscv_quaternion_normalize_f32**(const float32_t *pInputQuaternions, float32_t *pNormalizedQuaternions, uint32_t nbQuaternions)

group `QuatNormalized`

Compute a normalized quaternion.

Functions

void **riscv_quaternion_normalize_f32**(const float32_t *pInputQuaternions, float32_t *pNormalizedQuaternions, uint32_t nbQuaternions)

Floating-point normalization of quaternions.

Parameters

- **pInputQuaternions** – **[in]** points to the input vector of quaternions
- **pNormalizedQuaternions** – **[out]** points to the output vector of normalized quaternions
- **nbQuaternions** – **[in]** number of quaternions in each vector

Returns none

Quaternion Product

Elementwise Quaternion Product

void **riscv_quaternion_product_f32**(const float32_t *qa, const float32_t *qb, float32_t *qr, uint32_t nbQuaternions)

group `QuatProdVect`

Compute the elementwise product of quaternions.

Functions

void **riscv_quaternion_product_f32**(const float32_t *qa, const float32_t *qb, float32_t *qr, uint32_t nbQuaternions)

Floating-point elementwise product two quaternions.

Parameters

- **qa** – **[in]** first array of quaternions
- **qb** – **[in]** second array of quaternions
- **qr** – **[out]** elementwise product of quaternions
- **nbQuaternions** – **[in]** number of quaternions in the array

Returns none

Quaternion Product

void **riscv_quaternion_product_single_f32**(const float32_t *qa, const float32_t *qb, float32_t *qr)

group **QuatProdSingle**

Compute the product of two quaternions.

Functions

void **riscv_quaternion_product_single_f32**(const float32_t *qa, const float32_t *qb, float32_t *qr)

Floating-point product of two quaternions.

Parameters

- **qa** – **[in]** first quaternion
- **qb** – **[in]** second quaternion
- **qr** – **[out]** product of two quaternions

Returns none

group **QuatProd**

Compute the product of quaternions.

group **groupQuaternionMath**

Functions to operates on quaternions and convert between a rotation and quaternion representation.

3.3.11 Statistics Functions

Absolute Maximum

void **riscv_absmax_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult, uint32_t *pIndex)

void **riscv_absmax_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult, uint32_t *pIndex)

void **riscv_absmax_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult, uint32_t *pIndex)

void **riscv_absmax_no_idx_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

void **riscv_absmax_no_idx_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

void **riscv_absmax_no_idx_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

void **riscv_absmax_no_idx_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

void **riscv_absmax_no_idx_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

void **riscv_absmax_no_idx_q7**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult)

void **riscv_absmax_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult, uint32_t *pIndex)

void **riscv_absmax_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult, uint32_t *pIndex)

void **riscv_absmax_q7**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult, uint32_t *pIndex)

group **AbsMax**

Computes the maximum value of absolute values of an array of data. The function returns both the maximum value and its position within the array. There are separate functions for floating-point, Q31, Q15, and Q7 data types.

Functions

void **riscv_absmax_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult, uint32_t *pIndex)

Maximum value of absolute values of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here
- **pIndex** – **[out]** index of maximum value returned here

Returns none

void **riscv_absmax_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult, uint32_t *pIndex)

Maximum value of absolute values of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here
- **pIndex** – **[out]** index of maximum value returned here

Returns none

void **riscv_absmax_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult, uint32_t *pIndex)

Maximum value of absolute values of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here
- **pIndex** – **[out]** index of maximum value returned here

Returns none

void **riscv_absmax_no_idx_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

Maximum value of absolute values of a floating-point vector.

Maximum value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector

- `pResult` – **[out]** maximum value returned here

Returns none

void `riscv_absmax_no_idx_f32`(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

Maximum value of absolute values of a floating-point vector.

Parameters

- `pSrc` – **[in]** points to the input vector
- `blockSize` – **[in]** number of samples in input vector
- `pResult` – **[out]** maximum value returned here

Returns none

void `riscv_absmax_no_idx_f64`(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

Maximum value of absolute values of a floating-point vector.

Parameters

- `pSrc` – **[in]** points to the input vector
- `blockSize` – **[in]** number of samples in input vector
- `pResult` – **[out]** maximum value returned here

Returns none

void `riscv_absmax_no_idx_q15`(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

Maximum value of absolute values of a Q15 vector.

Parameters

- `pSrc` – **[in]** points to the input vector
- `blockSize` – **[in]** number of samples in input vector
- `pResult` – **[out]** maximum value returned here

Returns none

void `riscv_absmax_no_idx_q31`(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

Maximum value of absolute values of a Q31 vector.

Parameters

- `pSrc` – **[in]** points to the input vector
- `blockSize` – **[in]** number of samples in input vector
- `pResult` – **[out]** maximum value returned here

Returns none

void `riscv_absmax_no_idx_q7`(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult)

Maximum value of absolute values of a Q7 vector.

Parameters

- `pSrc` – **[in]** points to the input vector
- `blockSize` – **[in]** number of samples in input vector
- `pResult` – **[out]** maximum value returned here

Returns none

void **riscv_absmax_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult, uint32_t *pIndex)

Maximum value of absolute values of a Q15 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here
- **pIndex** – **[out]** index of maximum value returned here

Returns none

void **riscv_absmax_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult, uint32_t *pIndex)

Maximum value of absolute values of a Q31 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here
- **pIndex** – **[out]** index of maximum value returned here

Returns none

void **riscv_absmax_q7**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult, uint32_t *pIndex)

Maximum value of absolute values of a Q7 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here
- **pIndex** – **[out]** index of maximum value returned here

Returns none

Absolute Minimum

void **riscv_absmin_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult, uint32_t *pIndex)

void **riscv_absmin_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult, uint32_t *pIndex)

void **riscv_absmin_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult, uint32_t *pIndex)

void **riscv_absmin_no_idx_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

void **riscv_absmin_no_idx_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

void **riscv_absmin_no_idx_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

void **riscv_absmin_no_idx_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

void **riscv_absmin_no_idx_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

void **riscv_absmin_no_idx_q7**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult) void **riscv_absmin_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult, uint32_t *pIndex)

void **riscv_absmin_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult, uint32_t *pIndex)

void **riscv_absmin_q7**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult, uint32_t *pIndex)

group **AbsMin**

Computes the minimum value of absolute values of an array of data. The function returns both the minimum value and its position within the array. There are separate functions for floating-point, Q31, Q15, and Q7 data types.

Functions

void **riscv_absmin_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult, uint32_t *pIndex)

Minimum value of absolute values of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here
- **pIndex** – **[out]** index of minimum value returned here

Returns none

void **riscv_absmin_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult, uint32_t *pIndex)

Minimum value of absolute values of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here
- **pIndex** – **[out]** index of minimum value returned here

Returns none

void **riscv_absmin_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult, uint32_t *pIndex)

Minimum value of absolute values of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here
- **pIndex** – **[out]** index of minimum value returned here

Returns none

void **riscv_absmin_no_idx_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

Minimum value of absolute values of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector

- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here

Returns none

void **riscv_absmin_no_idx_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

Minimum value of absolute values of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here

Returns none

void **riscv_absmin_no_idx_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

Minimum value of absolute values of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here

Returns none

void **riscv_absmin_no_idx_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

Minimum value of absolute values of a Q15 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here

Returns none

void **riscv_absmin_no_idx_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

Minimum value of absolute values of a Q31 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here

Returns none

void **riscv_absmin_no_idx_q7**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult)

Minimum value of absolute values of a Q7 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here

Returns none

void **riscv_absmin_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult, uint32_t *pIndex)

Minimum value of absolute values of a Q15 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here
- **pIndex** – **[out]** index of minimum value returned here

Returns none

void **riscv_absmin_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult, uint32_t *pIndex)

Minimum value of absolute values of a Q31 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here
- **pIndex** – **[out]** index of minimum value returned here

Returns none

void **riscv_absmin_q7**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult, uint32_t *pIndex)

Minimum value of absolute values of a Q7 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here
- **pIndex** – **[out]** index of minimum value returned here

Returns none

Accumulation functions

void **riscv_accumulate_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

void **riscv_accumulate_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

void **riscv_accumulate_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

group **Accumulation**

Calculates the accumulation of the input vector. Sum is defined as the addition of the elements in the vector. The underlying algorithm is used:

There are separate functions for floating-point, Q31, Q15, and Q7 data types.

Functions

void **riscv_accumulate_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

accumulate value of a floating-point vector.

Sum value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector.
- **blockSize** – **[in]** number of samples in input vector.
- **pResult** – **[out]** sum of values in input vector.

Returns none

void **riscv_accumulate_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

Accumulation value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector.
- **blockSize** – **[in]** number of samples in input vector.
- **pResult** – **[out]** sum of values in input vector.

Returns none

void **riscv_accumulate_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

Accumulation value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector.
- **blockSize** – **[in]** number of samples in input vector.
- **pResult** – **[out]** sum of values in input vector.

Returns none

Entropy

float16_t **riscv_entropy_f16**(const float16_t *pSrcA, uint32_t blockSize)

float32_t **riscv_entropy_f32**(const float32_t *pSrcA, uint32_t blockSize)

float64_t **riscv_entropy_f64**(const float64_t *pSrcA, uint32_t blockSize)

group **Entropy**

Computes the entropy of a distribution.

Functions

float16_t **riscv_entropy_f16**(const float16_t *pSrcA, uint32_t blockSize)

Entropy.

Parameters

- **pSrcA** – **[in]** Array of input values.
- **blockSize** – **[in]** Number of samples in the input array.

Returns Entropy -Sum(p ln p)

float32_t **riscv_entropy_f32**(const float32_t *pSrcA, uint32_t blockSize)

Entropy.

Parameters

- **pSrcA** – **[in]** Array of input values.
- **blockSize** – **[in]** Number of samples in the input array.

Returns Entropy -Sum(p ln p)

float64_t **riscv_entropy_f64**(const float64_t *pSrcA, uint32_t blockSize)

Entropy.

Parameters

- **pSrcA** – **[in]** Array of input values.
- **blockSize** – **[in]** Number of samples in the input array.

Returns Entropy -Sum(p ln p)

Kullback-Leibler divergence

float16_t **riscv_kullback_leibler_f16**(const float16_t *pSrcA, const float16_t *pSrcB, uint32_t blockSize)

float32_t **riscv_kullback_leibler_f32**(const float32_t *pSrcA, const float32_t *pSrcB, uint32_t blockSize)

float64_t **riscv_kullback_leibler_f64**(const float64_t *pSrcA, const float64_t *pSrcB, uint32_t blockSize)

group **Kullback-Leibler**

Computes the Kullback-Leibler divergence between two distributions.

Functions

float16_t **riscv_kullback_leibler_f16**(const float16_t *pSrcA, const float16_t *pSrcB, uint32_t blockSize)

Kullback-Leibler.

Distribution A may contain 0 with Neon version. Result will be right but some exception flags will be set.

Distribution B must not contain 0 probability.

Parameters

- ***pSrcA** – **[in]** points to an array of input values for probaility distribution A.
- ***pSrcB** – **[in]** points to an array of input values for probaility distribution B.

- **blockSize** – **[in]** number of samples in the input array.

Returns Kullback-Leibler divergence D(A || B)

float32_t **riscv_kullback_leibler_f32**(const float32_t *pSrcA, const float32_t *pSrcB, uint32_t blockSize)

Kullback-Leibler.

Distribution A may contain 0 with Neon version. Result will be right but some exception flags will be set.

Distribution B must not contain 0 probability.

Parameters

- ***pSrcA** – **[in]** points to an array of input values for probaility distribution A.
- ***pSrcB** – **[in]** points to an array of input values for probaility distribution B.
- **blockSize** – **[in]** number of samples in the input array.

Returns Kullback-Leibler divergence D(A || B)

float64_t **riscv_kullback_leibler_f64**(const float64_t *pSrcA, const float64_t *pSrcB, uint32_t blockSize)

Kullback-Leibler.

Parameters

- ***pSrcA** – **[in]** points to an array of input values for probaility distribution A.
- ***pSrcB** – **[in]** points to an array of input values for probaility distribution B.
- **blockSize** – **[in]** number of samples in the input array.

Returns Kullback-Leibler divergence D(A || B)

LogSumExp

float16_t **riscv_logsumexp_dot_prod_f16**(const float16_t *pSrcA, const float16_t *pSrcB, uint32_t blockSize, float16_t *pTmpBuffer)

float32_t **riscv_logsumexp_dot_prod_f32**(const float32_t *pSrcA, const float32_t *pSrcB, uint32_t blockSize, float32_t *pTmpBuffer)

float16_t **riscv_logsumexp_f16**(const float16_t *in, uint32_t blockSize)

float32_t **riscv_logsumexp_f32**(const float32_t *in, uint32_t blockSize)

group **LogSumExp**

LogSumExp optimizations to compute sum of probabilities with Gaussian distributions.

Functions

float16_t **riscv_logsumexp_dot_prod_f16**(const float16_t *pSrcA, const float16_t *pSrcB, uint32_t blockSize, float16_t *pTmpBuffer)

Dot product with log arithmetic.

Vectors are containing the log of the samples

Parameters

- **`*pSrcA`** – **[in]** points to the first input vector
- **`*pSrcB`** – **[in]** points to the second input vector
- **`blockSize`** – **[in]** number of samples in each vector
- **`*pTmpBuffer`** – **[in]** temporary buffer of length blockSize

Returns The log of the dot product.

float32_t **riscv_logsumexp_dot_prod_f32**(const float32_t *pSrcA, const float32_t *pSrcB, uint32_t blockSize, float32_t *pTmpBuffer)

Dot product with log arithmetic.

Vectors are containing the log of the samples

Parameters

- **`*pSrcA`** – **[in]** points to the first input vector
- **`*pSrcB`** – **[in]** points to the second input vector
- **`blockSize`** – **[in]** number of samples in each vector
- **`*pTmpBuffer`** – **[in]** temporary buffer of length blockSize

Returns The log of the dot product.

float16_t **riscv_logsumexp_f16**(const float16_t *in, uint32_t blockSize)

Computation of the LogSumExp.

In probabilistic computations, the dynamic of the probability values can be very wide because they come from gaussian functions. To avoid underflow and overflow issues, the values are represented by their log. In this representation, multiplying the original exp values is easy : their logs are added. But adding the original exp values is requiring some special handling and it is the goal of the LogSumExp function.

If the values are x1…xn, the function is computing:

ln(exp(x1) + … + exp(xn)) and the computation is done in such a way that rounding issues are minimised.

The max xm of the values is extracted and the function is computing: xm + ln(exp(x1 - xm) + … + exp(xn - xm))

Parameters

- **`*in`** – **[in]** Pointer to an array of input values.
- **`blockSize`** – **[in]** Number of samples in the input array.

Returns LogSumExp

float32_t **riscv_logsumexp_f32**(const float32_t *in, uint32_t blockSize)

Computation of the LogSumExp.

In probabilistic computations, the dynamic of the probability values can be very wide because they come from gaussian functions. To avoid underflow and overflow issues, the values are represented by their log.

In this representation, multiplying the original exp values is easy : their logs are added. But adding the original exp values is requiring some special handling and it is the goal of the LogSumExp function.

If the values are x1. . . xn, the function is computing:

ln(exp(x1) + . . . + exp(xn)) and the computation is done in such a way that rounding issues are minimised.

The max xm of the values is extracted and the function is computing: xm + ln(exp(x1 - xm) + . . . + exp(xn - xm))

Parameters

- **`*in`** – **[in]** Pointer to an array of input values.
- **`blockSize`** – **[in]** Number of samples in the input array.

Returns LogSumExp

Maximum

void **`riscv_max_f16`**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult, uint32_t *pIndex)

void **`riscv_max_f32`**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult, uint32_t *pIndex)

void **`riscv_max_f64`**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult, uint32_t *pIndex)

void **`riscv_max_no_idx_f16`**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

void **`riscv_max_no_idx_f32`**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

void **`riscv_max_no_idx_f64`**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

void **`riscv_max_no_idx_q15`**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

void **`riscv_max_no_idx_q31`**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

void **`riscv_max_no_idx_q7`**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult)

void **`riscv_max_q15`**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult, uint32_t *pIndex)

void **`riscv_max_q31`**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult, uint32_t *pIndex)

void **`riscv_max_q7`**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult, uint32_t *pIndex)

group **`Max`**

Computes the maximum value of an array of data. The function returns both the maximum value and its position within the array. There are separate functions for floating-point, Q31, Q15, and Q7 data types.

Functions

void **`riscv_max_f16`**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult, uint32_t *pIndex)

Maximum value of a floating-point vector.

Parameters

- **`pSrc`** – **[in]** points to the input vector
- **`blockSize`** – **[in]** number of samples in input vector
- **`pResult`** – **[out]** maximum value returned here

- **pIndex** – **[out]** index of maximum value returned here

Returns none

void **riscv_max_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult, uint32_t *pIndex)

Maximum value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here
- **pIndex** – **[out]** index of maximum value returned here

Returns none

void **riscv_max_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult, uint32_t *pIndex)

Maximum value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here
- **pIndex** – **[out]** index of maximum value returned here

Returns none

void **riscv_max_no_idx_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

Maximum value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here

Returns none

void **riscv_max_no_idx_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

Maximum value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here

Returns none

void **riscv_max_no_idx_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

Maximum value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector

- **pResult** – **[out]** maximum value returned here

Returns none

void **riscv_max_no_idx_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

Maximum value of a q15 vector without index.

Maximum value of a q15 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here

Returns none

void **riscv_max_no_idx_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

Maximum value of a q31 vector without index.

Maximum value of a q31 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here

Returns none

void **riscv_max_no_idx_q7**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult)

Maximum value of a q7 vector without index.

Maximum value of a q7 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here

Returns none

void **riscv_max_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult, uint32_t *pIndex)

Maximum value of a Q15 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here
- **pIndex** – **[out]** index of maximum value returned here

Returns none

void **riscv_max_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult, uint32_t *pIndex)

Maximum value of a Q31 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here
- **pIndex** – **[out]** index of maximum value returned here

Returns none

void **riscv_max_q7**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult, uint32_t *pIndex)

Maximum value of a Q7 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** maximum value returned here
- **pIndex** – **[out]** index of maximum value returned here

Returns none

Mean

void **riscv_mean_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

void **riscv_mean_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

void **riscv_mean_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

void **riscv_mean_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

void **riscv_mean_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

void **riscv_mean_q7**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult)

group **mean**

Calculates the mean of the input vector. Mean is defined as the average of the elements in the vector. The underlying algorithm is used:

There are separate functions for floating-point, Q31, Q15, and Q7 data types.

Functions

void **riscv_mean_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

Mean value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector.
- **blockSize** – **[in]** number of samples in input vector.
- **pResult** – **[out]** mean value returned here.

Returns none

void **riscv_mean_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

Mean value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector.
- **blockSize** – **[in]** number of samples in input vector.
- **pResult** – **[out]** mean value returned here.

Returns none

void **riscv_mean_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

Mean value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector.
- **blockSize** – **[in]** number of samples in input vector.
- **pResult** – **[out]** mean value returned here.

Returns none

void **riscv_mean_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

Mean value of a Q15 vector.

Scaling and Overflow Behavior The function is implemented using a 32-bit internal accumulator. The input is represented in 1.15 format and is accumulated in a 32-bit accumulator in 17.15 format. There is no risk of internal overflow with this approach, and the full precision of intermediate result is preserved. Finally, the accumulator is truncated to yield a result of 1.15 format.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** mean value returned here

Returns none

void **riscv_mean_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

Mean value of a Q31 vector.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. The input is represented in 1.31 format and is accumulated in a 64-bit accumulator in 33.31 format. There is no risk of internal overflow with this approach, and the full precision of intermediate result is preserved. Finally, the accumulator is truncated to yield a result of 1.31 format.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** mean value returned here

Returns none

void **riscv_mean_q7**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult)

Mean value of a Q7 vector.

Scaling and Overflow Behavior The function is implemented using a 32-bit internal accumulator. The input is represented in 1.7 format and is accumulated in a 32-bit accumulator in 25.7 format. There is no risk of internal overflow with this approach, and the full precision of intermediate result is preserved. Finally, the accumulator is truncated to yield a result of 1.7 format.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** mean value returned here

Returns none

Minimum

void **riscv_min_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult, uint32_t *pIndex)

void **riscv_min_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult, uint32_t *pIndex)

void **riscv_min_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult, uint32_t *pIndex)

void **riscv_min_no_idx_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

void **riscv_min_no_idx_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

void **riscv_min_no_idx_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

void **riscv_min_no_idx_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

void **riscv_min_no_idx_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

void **riscv_min_no_idx_q7**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult)

void **riscv_min_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult, uint32_t *pIndex)

void **riscv_min_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult, uint32_t *pIndex)

void **riscv_min_q7**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult, uint32_t *pIndex)

group **Min**

Computes the minimum value of an array of data. The function returns both the minimum value and its position within the array. There are separate functions for floating-point, Q31, Q15, and Q7 data types.

Functions

void **riscv_min_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult, uint32_t *pIndex)

Minimum value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here
- **pIndex** – **[out]** index of minimum value returned here

Returns none

void **riscv_min_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult, uint32_t *pIndex)

Minimum value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here
- **pIndex** – **[out]** index of minimum value returned here

Returns none

void **riscv_min_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult, uint32_t *pIndex)

Minimum value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here
- **pIndex** – **[out]** index of minimum value returned here

Returns none

void **riscv_min_no_idx_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

Minimum value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here

Returns none

void **riscv_min_no_idx_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

Minimum value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector

- **pResult** – **[out]** minimum value returned here

Returns none

void **riscv_min_no_idx_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

Maximum value of a floating-point vector.

Minimum value of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here

Returns none

void **riscv_min_no_idx_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

Minimum value of a q15 vector without index.

Minimum value of a q15 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here

Returns none

void **riscv_min_no_idx_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

Minimum value of a q31 vector without index.

Minimum value of a q31 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here

Returns none

void **riscv_min_no_idx_q7**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult)

Minimum value of a q7 vector without index.

Minimum value of a q7 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here

Returns none

void **riscv_min_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult, uint32_t *pIndex)

Minimum value of a Q15 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here
- **pIndex** – **[out]** index of minimum value returned here

Returns none

void **riscv_min_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult, uint32_t *pIndex)

Minimum value of a Q31 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here
- **pIndex** – **[out]** index of minimum value returned here

Returns none

void **riscv_min_q7**(const q7_t *pSrc, uint32_t blockSize, q7_t *pResult, uint32_t *pIndex)

Minimum value of a Q7 vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** minimum value returned here
- **pIndex** – **[out]** index of minimum value returned here

Returns none

Mean Square Error

void **riscv_mse_f16**(const float16_t *pSrcA, const float16_t *pSrcB, uint32_t blockSize, float16_t *result)

void **riscv_mse_f32**(const float32_t *pSrcA, const float32_t *pSrcB, uint32_t blockSize, float32_t *pResult)

void **riscv_mse_f64**(const float64_t *pSrcA, const float64_t *pSrcB, uint32_t blockSize, float64_t *pResult)

void **riscv_mse_q15**(const q15_t *pSrcA, const q15_t *pSrcB, uint32_t blockSize, q15_t *pResult)

void **riscv_mse_q31**(const q31_t *pSrcA, const q31_t *pSrcB, uint32_t blockSize, q31_t *pResult)

void **riscv_mse_q7**(const q7_t *pSrcA, const q7_t *pSrcB, uint32_t blockSize, q7_t *pResult)

group MSE

Calculates the mean square error between two vectors.

Functions

void **riscv_mse_f16**(const float16_t *pSrcA, const float16_t *pSrcB, uint32_t blockSize, float16_t *result)

Mean square error between two half floating point vectors.

Mean square error between two half precision float vectors.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **blockSize** – **[in]** number of samples in input vector
- **result** – **[out]** mean square error

Returns none

void **riscv_mse_f32**(const float32_t *pSrcA, const float32_t *pSrcB, uint32_t blockSize, float32_t *pResult)

Mean square error between two floating point vectors.

Mean square error between two single precision float vectors.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** mean square error

Returns none

void **riscv_mse_f64**(const float64_t *pSrcA, const float64_t *pSrcB, uint32_t blockSize, float64_t *pResult)

Mean square error between two double floating point vectors.

Mean square error between two double precision float vectors.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** mean square error

Returns none

void **riscv_mse_q15**(const q15_t *pSrcA, const q15_t *pSrcB, uint32_t blockSize, q15_t *pResult)

Mean square error between two Q15 vectors.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** mean square error

Returns none

void **riscv_mse_q31**(const q31_t *pSrcA, const q31_t *pSrcB, uint32_t blockSize, q31_t *pResult)

Mean square error between two Q31 vectors.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** mean square error

Returns none

void **riscv_mse_q7**(const q7_t *pSrcA, const q7_t *pSrcB, uint32_t blockSize, q7_t *pResult)

Mean square error between two Q7 vectors.

Parameters

- **pSrcA** – **[in]** points to the first input vector
- **pSrcB** – **[in]** points to the second input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** mean square error

Returns none

Power

void **riscv_power_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

void **riscv_power_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

void **riscv_power_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

void **riscv_power_q15**(const q15_t *pSrc, uint32_t blockSize, q63_t *pResult)

void **riscv_power_q31**(const q31_t *pSrc, uint32_t blockSize, q63_t *pResult)

void **riscv_power_q7**(const q7_t *pSrc, uint32_t blockSize, q31_t *pResult)

group **power**

Calculates the sum of the squares of the elements in the input vector. The underlying algorithm is used:

There are separate functions for floating point, Q31, Q15, and Q7 data types.

Since the result is not divided by the length, those functions are in fact computing something which is more an energy than a power.

Functions

void **riscv_power_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

Sum of the squares of the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** sum of the squares value returned here

Returns none

void **riscv_power_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

Sum of the squares of the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** sum of the squares value returned here

Returns none

void **riscv_power_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

Sum of the squares of the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** sum of the squares value returned here

Returns none

void **riscv_power_q15**(const q15_t *pSrc, uint32_t blockSize, q63_t *pResult)

Sum of the squares of the elements of a Q15 vector.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. The input is represented in 1.15 format. Intermediate multiplication yields a 2.30 format, and this result is added without saturation to a 64-bit accumulator in 34.30 format. With 33 guard bits in the accumulator, there is no risk of overflow, and the full precision of the intermediate multiplication is preserved. Finally, the return result is in 34.30 format.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** sum of the squares value returned here

Returns none

void **riscv_power_q31**(const q31_t *pSrc, uint32_t blockSize, q63_t *pResult)

Sum of the squares of the elements of a Q31 vector.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. The input is represented in 1.31 format. Intermediate multiplication yields a 2.62 format, and this result is truncated to 2.48 format by discarding the lower 14 bits. The 2.48 result is then added without saturation to a 64-bit accumulator in 16.48 format. With 15 guard bits in the accumulator, there is no risk of overflow, and the full precision of the intermediate multiplication is preserved. Finally, the return result is in 16.48 format.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** sum of the squares value returned here

Returns none

void **riscv_power_q7**(const q7_t *pSrc, uint32_t blockSize, q31_t *pResult)

Sum of the squares of the elements of a Q7 vector.

Scaling and Overflow Behavior The function is implemented using a 32-bit internal accumulator. The input is represented in 1.7 format. Intermediate multiplication yields a 2.14 format, and this result is added without saturation to an accumulator in 18.14 format. With 17 guard bits in the accumulator, there is no risk of overflow, and the full precision of the intermediate multiplication is preserved. Finally, the return result is in 18.14 format.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** sum of the squares value returned here

Returns none

Root mean square (RMS)

void **riscv_rms_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

void **riscv_rms_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

void **riscv_rms_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

void **riscv_rms_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

group **RMS**

Calculates the Root Mean Square of the elements in the input vector. The underlying algorithm is used:

There are separate functions for floating point, Q31, and Q15 data types.

Functions

void **riscv_rms_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

Root Mean Square of the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** root mean square value returned here

Returns none

void **riscv_rms_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

Root Mean Square of the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** root mean square value returned here

Returns none

void **riscv_rms_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

Root Mean Square of the elements of a Q15 vector.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. The input is represented in 1.15 format. Intermediate multiplication yields a 2.30 format, and this result is added without saturation to a 64-bit accumulator in 34.30 format. With 33 guard bits in the accumulator, there is no risk of overflow, and the full precision of the intermediate multiplication is preserved. Finally, the 34.30 result is truncated to 34.15 format by discarding the lower 15 bits, and then saturated to yield a result in 1.15 format.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** root mean square value returned here

Returns none

void **riscv_rms_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

Root Mean Square of the elements of a Q31 vector.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The input is represented in 1.31 format, and intermediate multiplication yields a 2.62 format. The accumulator maintains full precision of the intermediate multiplication results, but provides only a single guard bit. There is no saturation on intermediate additions. If the accumulator overflows, it wraps around and distorts the result. In order to avoid overflows completely, the input signal must be scaled down by log2(blockSize) bits, as a total of blockSize additions are performed internally. Finally, the 2.62 accumulator is right shifted by 31 bits to yield a 1.31 format value.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** root mean square value returned here

Returns none

Standard deviation

void **riscv_std_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

void **riscv_std_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

void **riscv_std_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

void **riscv_std_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

void **riscv_std_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

group **STD**

Calculates the standard deviation of the elements in the input vector.

The float implementation is relying on riscv_var_f32 which is using a two-pass algorithm to avoid problem of numerical instabilities and cancellation errors.

Fixed point versions are using the standard textbook algorithm since the fixed point numerical behavior is different from the float one.

Algorithm for fixed point versions is summarized below:

There are separate functions for floating point, Q31, and Q15 data types.

Functions

void **riscv_std_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

Standard deviation of the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** standard deviation value returned here

Returns none

void **riscv_std_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

Standard deviation of the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** standard deviation value returned here

Returns none

void **riscv_std_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

Standard deviation of the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** standard deviation value returned here

Returns none

void **riscv_std_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

Standard deviation of the elements of a Q15 vector.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. The input is represented in 1.15 format. Intermediate multiplication yields a 2.30 format, and this result is added without saturation to a 64-bit accumulator in 34.30 format. With 33 guard bits in the accumulator, there is no risk of overflow, and the full precision of the intermediate multiplication is preserved. Finally, the 34.30 result is truncated to 34.15 format by discarding the lower 15 bits, and then saturated to yield a result in 1.15 format.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** standard deviation value returned here

Returns none

void **riscv_std_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

Standard deviation of the elements of a Q31 vector.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The input is represented in 1.31 format, which is then downshifted by 8 bits which yields 1.23, and intermediate multiplication yields a 2.46 format. The accumulator maintains full precision of the intermediate multiplication results, but provides only a 16 guard bits. There is no saturation on intermediate additions. If the accumulator overflows it wraps around and distorts the result. In order to avoid overflows completely the input signal must be scaled down by log2(blockSize)-8 bits, as a total of blockSize additions are performed internally. After division, internal variables should be Q18.46 Finally, the 18.46 accumulator is right shifted by 15 bits to yield a 1.31 format value.

Parameters

- **pSrc** – **[in]** points to the input vector.
- **blockSize** – **[in]** number of samples in input vector.
- **pResult** – **[out]** standard deviation value returned here.

Returns none

Variance

void **riscv_var_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

void **riscv_var_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

void **riscv_var_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

void **riscv_var_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

void **riscv_var_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

group **variance**

Calculates the variance of the elements in the input vector. The underlying algorithm used is the direct method sometimes referred to as the two-pass method:

There are separate functions for floating point, Q31, and Q15 data types.

Functions

void **riscv_var_f16**(const float16_t *pSrc, uint32_t blockSize, float16_t *pResult)

Variance of the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** variance value returned here

Returns none

void **riscv_var_f32**(const float32_t *pSrc, uint32_t blockSize, float32_t *pResult)

Variance of the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** variance value returned here

Returns none

void **riscv_var_f64**(const float64_t *pSrc, uint32_t blockSize, float64_t *pResult)

Variance of the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** variance value returned here

Returns none

void **riscv_var_q15**(const q15_t *pSrc, uint32_t blockSize, q15_t *pResult)

Variance of the elements of a Q15 vector.

Scaling and Overflow Behavior The function is implemented using a 64-bit internal accumulator. The input is represented in 1.15 format. Intermediate multiplication yields a 2.30 format, and this result is added without saturation to a 64-bit accumulator in 34.30 format. With 33 guard bits in the accumulator, there is no risk of overflow, and the full precision of the intermediate multiplication is preserved. Finally, the 34.30 result is truncated to 34.15 format by discarding the lower 15 bits, and then saturated to yield a result in 1.15 format.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** variance value returned here

Returns none

void **riscv_var_q31**(const q31_t *pSrc, uint32_t blockSize, q31_t *pResult)

Variance of the elements of a Q31 vector.

Scaling and Overflow Behavior The function is implemented using an internal 64-bit accumulator. The input is represented in 1.31 format, which is then downshifted by 8 bits which yields 1.23, and intermediate multiplication yields a 2.46 format. The accumulator maintains full precision of the intermediate multiplication results, and as a consequence has only 16 guard bits. There is no saturation on intermediate additions. If the accumulator overflows it wraps around and distorts the result. In order to avoid overflows completely the input signal must be scaled down by log2(blockSize)-8 bits, as a total of blockSize additions are performed internally. After division, internal variables should be Q18.46 Finally, the 18.46 accumulator is right shifted by 15 bits to yield a 1.31 format value.

Parameters

- **pSrc** – **[in]** points to the input vector
- **blockSize** – **[in]** number of samples in input vector
- **pResult** – **[out]** variance value returned here

Returns none

group **groupStats**

3.3.12 Support Functions

Typecasting

__STATIC_INLINE int16_t riscv_typecast_s16_f16 (float16_t x)

__STATIC_INLINE float16_t riscv_typecast_f16_s16 (int16_t x)

group `typecast`

Functions

`__STATIC_INLINE int16_t riscv_typecast_s16_f16 (float16_t x)`

Interpret a f16 as an s16 value.

Description It is a typecast. No conversion of the float to int is done. The memcpy will be optimized out by the compiler. memcpy is used to prevent type punning issues. With gcc, -fno-builtins MUST not be used or the memcpy will not be optimized out.

Parameters `x` – **[in]** input value.

Returns return value.

`__STATIC_INLINE float16_t riscv_typecast_f16_s16 (int16_t x)`

Interpret an s16 as an f16 value.

Description It is a typecast. No conversion of the int to float is done. The memcpy will be optimized out by the compiler. memcpy is used to prevent type punning issues. With gcc, -fno-builtins MUST not be used or the memcpy will not be optimized out.

Parameters `x` – **[in]** input value.

Returns return value.

Barycenter

void **`riscv_barycenter_f32`**(const float32_t *in, const float32_t *weights, float32_t *out, uint32_t nbVectors, uint32_t vecDim)

void **`riscv_barycenter_f16`**(const float16_t *in, const float16_t *weights, float16_t *out, uint32_t nbVectors, uint32_t vecDim)

group `barycenter`

Barycenter of weighted vectors.

Unnamed Group

void **`riscv_barycenter_f32`**(const float32_t *in, const float32_t *weights, float32_t *out, uint32_t nbVectors, uint32_t vecDim)

Barycenter.

Parameters

- **`*in`** – **[in]** List of vectors
- **`*weights`** – **[in]** Weights of the vectors

- ***out** – **[out]** Barycenter
- **nbVectors** – **[in]** Number of vectors
- **vecDim** – **[in]** Dimension of space (vector dimension)

Returns None

Functions

void **riscv_barycenter_f16**(const float16_t *in, const float16_t *weights, float16_t *out, uint32_t nbVectors, uint32_t vecDim)

Barycenter.

Parameters

- ***in** – **[in]** List of vectors
- ***weights** – **[in]** Weights of the vectors
- ***out** – **[out]** Barycenter
- **nbVectors** – **[in]** Number of vectors
- **vecDim** – **[in]** Dimension of space (vector dimension)

Returns None

Vector sorting algorithms

void **riscv_merge_sort_f32**(const riscv_merge_sort_instance_f32 *S, float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_merge_sort_init_f32**(riscv_merge_sort_instance_f32 *S, riscv_sort_dir dir, float32_t *buffer)

void **riscv_sort_f32**(const riscv_sort_instance_f32 *S, float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_sort_init_f32**(riscv_sort_instance_f32 *S, riscv_sort_alg alg, riscv_sort_dir dir)

group **Sorting**

Sort the elements of a vector.

There are separate functions for floating-point, Q31, Q15, and Q7 data types.

Functions

void **riscv_bitonic_sort_f32**(const riscv_sort_instance_f32 *S, float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Parameters

- **S** – **[in]** points to an instance of the sorting structure.
- **pSrc** – **[in]** points to the block of input data.
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of samples to process.

void **riscv_bubble_sort_f32**(const riscv_sort_instance_f32 *S, float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Algorithm The bubble sort algorithm is a simple comparison algorithm that reads the elements of a vector from the beginning to the end, compares the adjacent ones and swaps them if they are in the wrong order. The procedure is repeated until there is nothing left to swap. Bubble sort is fast for input vectors that are nearly sorted.

It's an in-place algorithm. In order to obtain an out-of-place function, a memcpy of the source vector is performed

Parameters

- `S` – **[in]** points to an instance of the sorting structure.
- `pSrc` – **[in]** points to the block of input data.
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process.

void **riscv_heap_sort_f32**(const riscv_sort_instance_f32 *S, float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Algorithm The heap sort algorithm is a comparison algorithm that divides the input array into a sorted and an unsorted region, and shrinks the unsorted region by extracting the largest element and moving it to the sorted region. A heap data structure is used to find the maximum.

It's an in-place algorithm. In order to obtain an out-of-place function, a memcpy of the source vector is performed.

Parameters

- `S` – **[in]** points to an instance of the sorting structure.
- `pSrc` – **[in]** points to the block of input data.
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process.

void **riscv_insertion_sort_f32**(const riscv_sort_instance_f32 *S, float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Algorithm The insertion sort is a simple sorting algorithm that reads all the element of the input array and removes one element at a time, finds the location it belongs in the final sorted list, and inserts it there.

It's an in-place algorithm. In order to obtain an out-of-place function, a memcpy of the source vector is performed.

Parameters

- `S` – **[in]** points to an instance of the sorting structure.
- `pSrc` – **[in]** points to the block of input data.
- `pDst` – **[out]** points to the block of output data
- `blockSize` – **[in]** number of samples to process.

void **riscv_merge_sort_f32**(const riscv_merge_sort_instance_f32 *S, float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Algorithm The merge sort algorithm is a comparison algorithm that divide the input array in sublists and merge them to produce longer sorted sublists until there is only one list remaining.

A work array is always needed. It must be allocated by the user linked to the instance at initialization time.

It's an in-place algorithm. In order to obtain an out-of-place function, a memcpy of the source vector is performed

Parameters

- **S** – **[in]** points to an instance of the sorting structure.
- **pSrc** – **[in]** points to the block of input data.
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of samples to process.

void **riscv_merge_sort_init_f32**(riscv_merge_sort_instance_f32 *S, riscv_sort_dir dir, float32_t *buffer)

Parameters

- **S** – **[inout]** points to an instance of the sorting structure.
- **dir** – **[in]** Sorting order.
- **buffer** – **[in]** Working buffer.

void **riscv_quick_sort_f32**(const riscv_sort_instance_f32 *S, float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Algorithm The quick sort algorithm is a comparison algorithm that divides the input array into two smaller sub-arrays and recursively sort them. An element of the array (the pivot) is chosen, all the elements with values smaller than the pivot are moved before the pivot, while all elements with values greater than the pivot are moved after it (partition).

In this implementation the Hoare partition scheme has been used [Hoare, C. A. R. (1 January 1962). "Quicksort". The Computer Journal. 5 (1): 10…16.] The first element has always been chosen as the pivot. The partition algorithm guarantees that the returned pivot is never placed outside the vector, since it is returned only when the pointers crossed each other. In this way it isn't possible to obtain empty partitions and infinite recursion is avoided.

It's an in-place algorithm. In order to obtain an out-of-place function, a memcpy of the source vector is performed.

Parameters

- **S** – **[in]** points to an instance of the sorting structure.
- **pSrc** – **[inout]** points to the block of input data.
- **pDst** – **[out]** points to the block of output data.
- **blockSize** – **[in]** number of samples to process.

void **riscv_selection_sort_f32**(const riscv_sort_instance_f32 *S, float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Algorithm The Selection sort algorithm is a comparison algorithm that divides the input array into a sorted and an unsorted sublist (initially the sorted sublist is empty and the unsorted sublist is the input array), looks for the smallest (or biggest) element in the unsorted sublist, swapping it with the leftmost one, and moving the sublists boundary one element to the right.

It's an in-place algorithm. In order to obtain an out-of-place function, a memcpy of the source vector is performed.

Parameters

- **S** – **[in]** points to an instance of the sorting structure.
- **pSrc** – **[in]** points to the block of input data.
- **pDst** – **[out]** points to the block of output data
- **blockSize** – **[in]** number of samples to process.

void **riscv_sort_f32**(const riscv_sort_instance_f32 *S, float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Generic sorting function.

Parameters

- **S** – **[in]** points to an instance of the sorting structure.
- **pSrc** – **[in]** points to the block of input data.
- **pDst** – **[out]** points to the block of output data.
- **blockSize** – **[in]** number of samples to process.

void **riscv_sort_init_f32**(riscv_sort_instance_f32 *S, riscv_sort_alg alg, riscv_sort_dir dir)

Parameters

- **S** – **[inout]** points to an instance of the sorting structure.
- **alg** – **[in]** Selected algorithm.
- **dir** – **[in]** Sorting order.

Vector Copy

void **riscv_copy_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

void **riscv_copy_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_copy_f64**(const float64_t *pSrc, float64_t *pDst, uint32_t blockSize)

void **riscv_copy_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_copy_q31**(const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

void **riscv_copy_q7**(const q7_t *pSrc, q7_t *pDst, uint32_t blockSize) *group* **copy**

Copies sample by sample from source vector to destination vector.

There are separate functions for floating point, Q31, Q15, and Q7 data types.

Functions

void **riscv_copy_f16**(const float16_t *pSrc, float16_t *pDst, uint32_t blockSize)

Copies the elements of a f16 vector.

Copies the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_copy_f32**(const float32_t *pSrc, float32_t *pDst, uint32_t blockSize)

Copies the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_copy_f64**(const float64_t *pSrc, float64_t *pDst, uint32_t blockSize)

Copies the elements of a floating-point vector.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_copy_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

Copies the elements of a Q15 vector.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_copy_q31**(const q31_t *pSrc, q31_t *pDst, uint32_t blockSize)

Copies the elements of a Q31 vector.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_copy_q7**(const q7_t *pSrc, q7_t *pDst, uint32_t blockSize)

Copies the elements of a Q7 vector.

Parameters

- **pSrc** – **[in]** points to input vector
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Convert 16-bit floating point value

void **riscv_f16_to_f64**(const float16_t *pSrc, float64_t *pDst, uint32_t blockSize)

void **riscv_f16_to_float**(const float16_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_f16_to_q15**(const float16_t *pSrc, q15_t *pDst, uint32_t blockSize)

group **f16_to_x**

Functions

void **riscv_f16_to_f64**(const float16_t *pSrc, float64_t *pDst, uint32_t blockSize)

Converts the elements of the f16 vector to f64 vector.

Converts the elements of the 16 bit floating-point vector to 64 bit floating-point vector.

Parameters

- **pSrc** – **[in]** points to the f16 input vector
- **pDst** – **[out]** points to the f64 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_f16_to_float**(const float16_t *pSrc, float32_t *pDst, uint32_t blockSize)

Converts the elements of the f16 vector to f32 vector.

Converts the elements of the floating-point vector to Q31 vector.

Parameters

- **pSrc** – **[in]** points to the f16 input vector

- **pDst** – **[out]** points to the f32 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_f16_to_q15**(const float16_t *pSrc, q15_t *pDst, uint32_t blockSize)

Converts the elements of the f16 vector to Q15 vector.

Converts the elements of the floating-point vector to Q31 vector.

Details The equation used for the conversion process is:

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q15 range [0x8000 0x7FFF] are saturated.

Note: In order to apply rounding in scalar version, the library should be rebuilt with the ROUNDING macro defined in the preprocessor section of project options.

Parameters

- **pSrc** – **[in]** points to the f16 input vector
- **pDst** – **[out]** points to the Q15 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Convert 64-bit floating point value

void **riscv_f64_to_f16**(const float64_t *pSrc, float16_t *pDst, uint32_t blockSize)

void **riscv_f64_to_float**(const float64_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_f64_to_q15**(const float64_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_f64_to_q31**(const float64_t *pSrc, q31_t *pDst, uint32_t blockSize)

void **riscv_f64_to_q7**(const float64_t *pSrc, q7_t *pDst, uint32_t blockSize)

group **f64_to_x**

Functions

void **riscv_f64_to_f16**(const float64_t *pSrc, float16_t *pDst, uint32_t blockSize)

Converts the elements of the f64 vector to f16 vector.

Converts the elements of the 64 bit floating-point vector to 16 bit floating-point vector.

Parameters

- **pSrc** – **[in]** points to the f64 input vector
- **pDst** – **[out]** points to the f16 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_f64_to_float**(const float64_t *pSrc, float32_t *pDst, uint32_t blockSize)

Converts the elements of the f64 vector to f32 vector.

Converts the elements of the 64 bit floating-point vector to floating-point vector.

Parameters

- **pSrc** – **[in]** points to the f64 input vector
- **pDst** – **[out]** points to the f32 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_f64_to_q15**(const float64_t *pSrc, q15_t *pDst, uint32_t blockSize)

Converts the elements of the 64 bit floating-point vector to Q15 vector.

Details The equation used for the conversion process is:

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q15 range [0x8000 0x7FFF] are saturated.

Note: In order to apply rounding, the library should be rebuilt with the ROUNDING macro defined in the preprocessor section of project options.

Parameters

- **pSrc** – **[in]** points to the 64 bit floating-point input vector
- **pDst** – **[out]** points to the Q15 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_f64_to_q31**(const float64_t *pSrc, q31_t *pDst, uint32_t blockSize)

Converts the elements of the 64 bit floating-point vector to Q31 vector.

Details The equation used for the conversion process is:

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q31 range[0x80000000 0x7FFFFFFF] are saturated.

Note: In order to apply rounding, the library should be rebuilt with the ROUNDING macro defined in the preprocessor section of project options.

Parameters

- **pSrc** – **[in]** points to the 64 bit floating-point input vector
- **pDst** – **[out]** points to the Q31 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_f64_to_q7**(const float64_t *pSrc, q7_t *pDst, uint32_t blockSize)

Converts the elements of the 64 bit floating-point vector to Q7 vector.

Description:

The equation used for the conversion process is:

Scaling and Overflow Behavior:

The function uses saturating arithmetic. Results outside of the allowable Q7 range [0x80 0x7F] will be saturated.

Note: In order to apply rounding, the library should be rebuilt with the ROUNDING macro defined in the preprocessor section of project options.

Parameters

- ***pSrc** – **[in]** points to the 64 bit floating-point input vector
- ***pDst** – **[out]** points to the Q7 output vector
- **blockSize** – **[in]** length of the input vector

Returns none.

Vector Fill

void **riscv_fill_f16**(float16_t value, float16_t *pDst, uint32_t blockSize)

void **riscv_fill_f32**(float32_t value, float32_t *pDst, uint32_t blockSize)

void **riscv_fill_f64**(float64_t value, float64_t *pDst, uint32_t blockSize)

void **riscv_fill_q15**(q15_t value, q15_t *pDst, uint32_t blockSize)

void **riscv_fill_q31**(q31_t value, q31_t *pDst, uint32_t blockSize)

void **riscv_fill_q7**(q7_t value, q7_t *pDst, uint32_t blockSize)

group **Fill**

Fills the destination vector with a constant value.

There are separate functions for floating point, Q31, Q15, and Q7 data types.

Functions

void **riscv_fill_f16**(float16_t value, float16_t *pDst, uint32_t blockSize)

Fills a constant value into a f16 vector.

Fills a constant value into a floating-point vector.

Parameters

- **value** – **[in]** input value to be filled
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_fill_f32**(float32_t value, float32_t *pDst, uint32_t blockSize)

Fills a constant value into a floating-point vector.

Parameters

- **value** – **[in]** input value to be filled
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_fill_f64**(float64_t value, float64_t *pDst, uint32_t blockSize)

Fills a constant value into a floating-point vector.

Parameters

- **value** – **[in]** input value to be filled
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_fill_q15**(q15_t value, q15_t *pDst, uint32_t blockSize)

Fills a constant value into a Q15 vector.

Parameters

- **value** – **[in]** input value to be filled
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_fill_q31**(q31_t value, q31_t *pDst, uint32_t blockSize)

Fills a constant value into a Q31 vector.

Parameters

- **value** – **[in]** input value to be filled
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_fill_q7**(q7_t value, q7_t *pDst, uint32_t blockSize)

Fills a constant value into a Q7 vector.

Parameters

- **value** – **[in]** input value to be filled
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Convert 32-bit floating point value

void **riscv_float_to_f16**(const float32_t *pSrc, float16_t *pDst, uint32_t blockSize)

void **riscv_float_to_f64**(const float32_t *pSrc, float64_t *pDst, uint32_t blockSize)

void **riscv_float_to_q15**(const float32_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_float_to_q31**(const float32_t *pSrc, q31_t *pDst, uint32_t blockSize)

void **riscv_float_to_q7**(const float32_t *pSrc, q7_t *pDst, uint32_t blockSize)

group **float_to_x**

Functions

void **riscv_float_to_f16**(const float32_t *pSrc, float16_t *pDst, uint32_t blockSize)

Converts the elements of the floating-point vector to f16 vector.

Converts the elements of the floating-point vector to Q31 vector.

Parameters

- **pSrc** – **[in]** points to the f32 input vector
- **pDst** – **[out]** points to the f16 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_float_to_f64**(const float32_t *pSrc, float64_t *pDst, uint32_t blockSize)

Converts the elements of the floating-point vector to f64 vector.

Converts the elements of the floating-point vector to 64 bit floating-point vector.

Parameters

- **pSrc** – **[in]** points to the f32 input vector
- **pDst** – **[out]** points to the f64 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_float_to_q15**(const float32_t *pSrc, q15_t *pDst, uint32_t blockSize)

Converts the elements of the floating-point vector to Q15 vector.

Details The equation used for the conversion process is:

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q15 range [0x8000 0x7FFF] are saturated.

Note: In order to apply rounding, the library should be rebuilt with the ROUNDING macro defined in the preprocessor section of project options.

Parameters

- **pSrc** – **[in]** points to the floating-point input vector
- **pDst** – **[out]** points to the Q15 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_float_to_q31**(const float32_t *pSrc, q31_t *pDst, uint32_t blockSize)

Converts the elements of the floating-point vector to Q31 vector.

Details The equation used for the conversion process is:

Scaling and Overflow Behavior The function uses saturating arithmetic. Results outside of the allowable Q31 range[0x80000000 0x7FFFFFFF] are saturated.

Note: In order to apply rounding, the library should be rebuilt with the ROUNDING macro defined in the preprocessor section of project options.

Parameters

- **pSrc** – **[in]** points to the floating-point input vector
- **pDst** – **[out]** points to the Q31 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_float_to_q7**(const float32_t *pSrc, q7_t *pDst, uint32_t blockSize)

Converts the elements of the floating-point vector to Q7 vector.

Description:

The equation used for the conversion process is:

Scaling and Overflow Behavior:

The function uses saturating arithmetic. Results outside of the allowable Q7 range [0x80 0x7F] will be saturated.

Note: In order to apply rounding, the library should be rebuilt with the ROUNDING macro defined in the preprocessor section of project options.

Parameters

- **`*pSrc`** – **[in]** points to the floating-point input vector
- **`*pDst`** – **[out]** points to the Q7 output vector
- **`blockSize`** – **[in]** length of the input vector

Returns none.

Convert 16-bit fixed point value

void **`riscv_q15_to_f16`**(const q15_t *pSrc, float16_t *pDst, uint32_t blockSize)

void **`riscv_q15_to_f64`**(const q15_t *pSrc, float64_t *pDst, uint32_t blockSize)

void **`riscv_q15_to_float`**(const q15_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **`riscv_q15_to_q31`**(const q15_t *pSrc, q31_t *pDst, uint32_t blockSize)

void **`riscv_q15_to_q7`**(const q15_t *pSrc, q7_t *pDst, uint32_t blockSize)

group **`q15_to_x`**

Functions

void **`riscv_q15_to_f16`**(const q15_t *pSrc, float16_t *pDst, uint32_t blockSize)

Converts the elements of the Q15 vector to f16 vector.

Converts the elements of the floating-point vector to Q31 vector.

Details The equation used for the conversion process is:

Parameters

- **`pSrc`** – **[in]** points to the Q15 input vector
- **`pDst`** – **[out]** points to the f16 output vector
- **`blockSize`** – **[in]** number of samples in each vector

Returns none

void **`riscv_q15_to_f64`**(const q15_t *pSrc, float64_t *pDst, uint32_t blockSize)

Converts the elements of the Q15 vector to 64 bit floating-point vector.

Details The equation used for the conversion process is:

Parameters

- **pSrc** – **[in]** points to the Q15 input vector
- **pDst** – **[out]** points to the 64 bit floating-point output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_q15_to_float**(const q15_t *pSrc, float32_t *pDst, uint32_t blockSize)

Converts the elements of the Q15 vector to floating-point vector.

Details The equation used for the conversion process is:

Parameters

- **pSrc** – **[in]** points to the Q15 input vector
- **pDst** – **[out]** points to the floating-point output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_q15_to_q31**(const q15_t *pSrc, q31_t *pDst, uint32_t blockSize)

Converts the elements of the Q15 vector to Q31 vector.

Details The equation used for the conversion process is:

Parameters

- **pSrc** – **[in]** points to the Q15 input vector
- **pDst** – **[out]** points to the Q31 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_q15_to_q7**(const q15_t *pSrc, q7_t *pDst, uint32_t blockSize)

Converts the elements of the Q15 vector to Q7 vector.

Details The equation used for the conversion process is:

Parameters

- **pSrc** – **[in]** points to the Q15 input vector
- **pDst** – **[out]** points to the Q7 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Convert 32-bit fixed point value

void **riscv_q31_to_f64**(const q31_t *pSrc, float64_t *pDst, uint32_t blockSize)

void **riscv_q31_to_float**(const q31_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_q31_to_q15**(const q31_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_q31_to_q7**(const q31_t *pSrc, q7_t *pDst, uint32_t blockSize)

group **q31_to_x**

Functions

void **riscv_q31_to_f64**(const q31_t *pSrc, float64_t *pDst, uint32_t blockSize)

Converts the elements of the Q31 vector to 64 bit floating-point vector.

Details The equation used for the conversion process is:

Parameters

- **pSrc** – **[in]** points to the Q31 input vector
- **pDst** – **[out]** points to the 64 bit floating-point output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_q31_to_float**(const q31_t *pSrc, float32_t *pDst, uint32_t blockSize)

Converts the elements of the Q31 vector to floating-point vector.

Details The equation used for the conversion process is:

Parameters

- **pSrc** – **[in]** points to the Q31 input vector
- **pDst** – **[out]** points to the floating-point output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_q31_to_q15**(const q31_t *pSrc, q15_t *pDst, uint32_t blockSize)

Converts the elements of the Q31 vector to Q15 vector.

Details The equation used for the conversion process is:

Parameters

- **pSrc** – **[in]** points to the Q31 input vector
- **pDst** – **[out]** points to the Q15 output vector

- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_q31_to_q7**(const q31_t *pSrc, q7_t *pDst, uint32_t blockSize)
Converts the elements of the Q31 vector to Q7 vector.

Details The equation used for the conversion process is:

Parameters

- **pSrc** – **[in]** points to the Q31 input vector
- **pDst** – **[out]** points to the Q7 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Convert 8-bit fixed point value

void **riscv_q7_to_f64**(const q7_t *pSrc, float64_t *pDst, uint32_t blockSize)

void **riscv_q7_to_float**(const q7_t *pSrc, float32_t *pDst, uint32_t blockSize)

void **riscv_q7_to_q15**(const q7_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_q7_to_q31**(const q7_t *pSrc, q31_t *pDst, uint32_t blockSize)

group **q7_to_x**

Functions

void **riscv_q7_to_f64**(const q7_t *pSrc, float64_t *pDst, uint32_t blockSize)
Converts the elements of the Q7 vector to 64 bit floating-point vector.

Details The equation used for the conversion process is:

Parameters

- **pSrc** – **[in]** points to the Q7 input vector
- **pDst** – **[out]** points to the 64 bit floating-point output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_q7_to_float**(const q7_t *pSrc, float32_t *pDst, uint32_t blockSize)
Converts the elements of the Q7 vector to floating-point vector.

Details The equation used for the conversion process is:

Parameters

- **pSrc** – **[in]** points to the Q7 input vector
- **pDst** – **[out]** points to the floating-point output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_q7_to_q15**(const q7_t *pSrc, q15_t *pDst, uint32_t blockSize)

Converts the elements of the Q7 vector to Q15 vector.

Details The equation used for the conversion process is:

Parameters

- **pSrc** – **[in]** points to the Q7 input vector
- **pDst** – **[out]** points to the Q15 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_q7_to_q31**(const q7_t *pSrc, q31_t *pDst, uint32_t blockSize)

Converts the elements of the Q7 vector to Q31 vector.

Details The equation used for the conversion process is:

Parameters

- **pSrc** – **[in]** points to the Q7 input vector
- **pDst** – **[out]** points to the Q31 output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Weighted Sum

float16_t **riscv_weighted_sum_f16**(const float16_t *in, const float16_t *weigths, uint32_t blockSize)

float32_t **riscv_weighted_sum_f32**(const float32_t *in, const float32_t *weigths, uint32_t blockSize)

group **weightedsum**

Weighted sum of values.

Functions

float16_t **riscv_weighted_sum_f16**(const float16_t *in, const float16_t *weigths, uint32_t blockSize)

Weighted sum.

Parameters

- ***in** – **[in]** Array of input values.
- ***weigths** – **[in]** Weights
- **blockSize** – **[in]** Number of samples in the input array.

Returns Weighted sum

float32_t **riscv_weighted_sum_f32**(const float32_t *in, const float32_t *weigths, uint32_t blockSize)

Weighted sum.

Parameters

- ***in** – **[in]** Array of input values.
- ***weigths** – **[in]** Weights
- **blockSize** – **[in]** Number of samples in the input array.

Returns Weighted sum

group **groupSupport**

3.3.13 SVM Functions

Linear SVM

void **riscv_svm_linear_init_f16**(riscv_svm_linear_instance_f16 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float16_t intercept, const float16_t *dualCoefficients, const float16_t *supportVectors, const int32_t *classes)

void **riscv_svm_linear_init_f32**(riscv_svm_linear_instance_f32 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float32_t intercept, const float32_t *dualCoefficients, const float32_t *supportVectors, const int32_t *classes)

void **riscv_svm_linear_predict_f16**(const riscv_svm_linear_instance_f16 *S, const float16_t *in, int32_t *pResult)

void **riscv_svm_linear_predict_f32**(const riscv_svm_linear_instance_f32 *S, const float32_t *in, int32_t *pResult)

group **linearsvm**

Linear SVM classifier.

Functions

void **riscv_svm_linear_init_f16**(riscv_svm_linear_instance_f16 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float16_t intercept, const float16_t *dualCoefficients, const float16_t *supportVectors, const int32_t *classes)

SVM linear instance init function.

Classes are integer used as output of the function (instead of having -1,1 as class values).

Parameters

- `S` – **[in]** Parameters for the SVM function
- `nbOfSupportVectors` – **[in]** Number of support vectors
- `vectorDimension` – **[in]** Dimension of vector space
- `intercept` – **[in]** Intercept
- `dualCoefficients` – **[in]** Array of dual coefficients
- `supportVectors` – **[in]** Array of support vectors
- `classes` – **[in]** Array of 2 classes ID

Returns none.

void **riscv_svm_linear_init_f32**(riscv_svm_linear_instance_f32 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float32_t intercept, const float32_t *dualCoefficients, const float32_t *supportVectors, const int32_t *classes)

SVM linear instance init function.

Classes are integer used as output of the function (instead of having -1,1 as class values).

Parameters

- `S` – **[in]** Parameters for the SVM function
- `nbOfSupportVectors` – **[in]** Number of support vectors
- `vectorDimension` – **[in]** Dimension of vector space
- `intercept` – **[in]** Intercept
- `dualCoefficients` – **[in]** Array of dual coefficients
- `supportVectors` – **[in]** Array of support vectors
- `classes` – **[in]** Array of 2 classes ID

Returns none.

void **riscv_svm_linear_predict_f16**(const riscv_svm_linear_instance_f16 *S, const float16_t *in, int32_t *pResult)

SVM linear prediction.

Parameters

- `S` – **[in]** Pointer to an instance of the linear SVM structure.
- `in` – **[in]** Pointer to input vector
- `pResult` – **[out]** Decision value

Returns none.

void **riscv_svm_linear_predict_f32**(const riscv_svm_linear_instance_f32 *S, const float32_t *in, int32_t *pResult)

SVM linear prediction.

Parameters

- **S** – **[in]** Pointer to an instance of the linear SVM structure.
- **in** – **[in]** Pointer to input vector
- **pResult** – **[out]** Decision value

Returns none.

Polynomial SVM

void **riscv_svm_polynomial_init_f16**(riscv_svm_polynomial_instance_f16 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float16_t intercept, const float16_t *dualCoefficients, const float16_t *supportVectors, const int32_t *classes, int32_t degree, float16_t coef0, float16_t gamma)

void **riscv_svm_polynomial_init_f32**(riscv_svm_polynomial_instance_f32 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float32_t intercept, const float32_t *dualCoefficients, const float32_t *supportVectors, const int32_t *classes, int32_t degree, float32_t coef0, float32_t gamma)

void **riscv_svm_polynomial_predict_f16**(const riscv_svm_polynomial_instance_f16 *S, const float16_t *in, int32_t *pResult)

void **riscv_svm_polynomial_predict_f32**(const riscv_svm_polynomial_instance_f32 *S, const float32_t *in, int32_t *pResult)

group **polysvm**

Polynomial SVM classifier.

Functions

void **riscv_svm_polynomial_init_f16**(riscv_svm_polynomial_instance_f16 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float16_t intercept, const float16_t *dualCoefficients, const float16_t *supportVectors, const int32_t *classes, int32_t degree, float16_t coef0, float16_t gamma)

SVM polynomial instance init function.

Classes are integer used as output of the function (instead of having -1,1 as class values).

Parameters

- **S** – **[in]** points to an instance of the polynomial SVM structure.
- **nbOfSupportVectors** – **[in]** Number of support vectors
- **vectorDimension** – **[in]** Dimension of vector space
- **intercept** – **[in]** Intercept

- **dualCoefficients** – **[in]** Array of dual coefficients
- **supportVectors** – **[in]** Array of support vectors
- **classes** – **[in]** Array of 2 classes ID
- **degree** – **[in]** Polynomial degree
- **coef0** – **[in]** coeff0 (scikit-learn terminology)
- **gamma** – **[in]** gamma (scikit-learn terminology)

Returns none.

void **riscv_svm_polynomial_init_f32**(riscv_svm_polynomial_instance_f32 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float32_t intercept, const float32_t *dualCoefficients, const float32_t *supportVectors, const int32_t *classes, int32_t degree, float32_t coef0, float32_t gamma)

SVM polynomial instance init function.

Classes are integer used as output of the function (instead of having -1,1 as class values).

Parameters

- **S** – **[in]** points to an instance of the polynomial SVM structure.
- **nbOfSupportVectors** – **[in]** Number of support vectors
- **vectorDimension** – **[in]** Dimension of vector space
- **intercept** – **[in]** Intercept
- **dualCoefficients** – **[in]** Array of dual coefficients
- **supportVectors** – **[in]** Array of support vectors
- **classes** – **[in]** Array of 2 classes ID
- **degree** – **[in]** Polynomial degree
- **coef0** – **[in]** coeff0 (scikit-learn terminology)
- **gamma** – **[in]** gamma (scikit-learn terminology)

Returns none.

void **riscv_svm_polynomial_predict_f16**(const riscv_svm_polynomial_instance_f16 *S, const float16_t *in, int32_t *pResult)

SVM polynomial prediction.

Parameters

- **S** – **[in]** Pointer to an instance of the polynomial SVM structure.
- **in** – **[in]** Pointer to input vector
- **pResult** – **[out]** Decision value

Returns none.

void **riscv_svm_polynomial_predict_f32**(const riscv_svm_polynomial_instance_f32 *S, const float32_t *in, int32_t *pResult)

SVM polynomial prediction.

Parameters

- **S** – **[in]** Pointer to an instance of the polynomial SVM structure.
- **in** – **[in]** Pointer to input vector
- **pResult** – **[out]** Decision value

Returns none.

RBF SVM

void **riscv_svm_rbf_init_f16**(riscv_svm_rbf_instance_f16 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float16_t intercept, const float16_t *dualCoefficients, const float16_t *supportVectors, const int32_t *classes, float16_t gamma)

void **riscv_svm_rbf_init_f32**(riscv_svm_rbf_instance_f32 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float32_t intercept, const float32_t *dualCoefficients, const float32_t *supportVectors, const int32_t *classes, float32_t gamma)

void **riscv_svm_rbf_predict_f16**(const riscv_svm_rbf_instance_f16 *S, const float16_t *in, int32_t *pResult)

void **riscv_svm_rbf_predict_f32**(const riscv_svm_rbf_instance_f32 *S, const float32_t *in, int32_t *pResult)

group **rbfsvm**

RBF SVM classifier.

Functions

void **riscv_svm_rbf_init_f16**(riscv_svm_rbf_instance_f16 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float16_t intercept, const float16_t *dualCoefficients, const float16_t *supportVectors, const int32_t *classes, float16_t gamma)

SVM radial basis function instance init function.

Classes are integer used as output of the function (instead of having -1,1 as class values).

Parameters

- **S** – **[in]** points to an instance of the polynomial SVM structure.
- **nbOfSupportVectors** – **[in]** Number of support vectors
- **vectorDimension** – **[in]** Dimension of vector space
- **intercept** – **[in]** Intercept
- **dualCoefficients** – **[in]** Array of dual coefficients
- **supportVectors** – **[in]** Array of support vectors
- **classes** – **[in]** Array of 2 classes ID
- **gamma** – **[in]** gamma (scikit-learn terminology)

Returns none.

void **riscv_svm_rbf_init_f32**(riscv_svm_rbf_instance_f32 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float32_t intercept, const float32_t *dualCoefficients, const float32_t *supportVectors, const int32_t *classes, float32_t gamma)

SVM radial basis function instance init function.

Classes are integer used as output of the function (instead of having -1,1 as class values).

Parameters

- **S** – **[in]** points to an instance of the polynomial SVM structure.
- **nbOfSupportVectors** – **[in]** Number of support vectors
- **vectorDimension** – **[in]** Dimension of vector space
- **intercept** – **[in]** Intercept
- **dualCoefficients** – **[in]** Array of dual coefficients
- **supportVectors** – **[in]** Array of support vectors
- **classes** – **[in]** Array of 2 classes ID
- **gamma** – **[in]** gamma (scikit-learn terminology)

Returns none.

void **riscv_svm_rbf_predict_f16**(const riscv_svm_rbf_instance_f16 *S, const float16_t *in, int32_t *pResult)

SVM rbf prediction.

Parameters

- **S** – **[in]** Pointer to an instance of the rbf SVM structure.
- **in** – **[in]** Pointer to input vector
- **pResult** – **[out]** decision value

Returns none.

void **riscv_svm_rbf_predict_f32**(const riscv_svm_rbf_instance_f32 *S, const float32_t *in, int32_t *pResult)

SVM rbf prediction.

Parameters

- **S** – **[in]** Pointer to an instance of the rbf SVM structure.
- **in** – **[in]** Pointer to input vector
- **pResult** – **[out]** decision value

Returns none.

Sigmoid SVM

void **riscv_svm_sigmoid_init_f16**(riscv_svm_sigmoid_instance_f16 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float16_t intercept, const float16_t *dualCoefficients, const float16_t *supportVectors, const int32_t *classes, float16_t coef0, float16_t gamma)

void **riscv_svm_sigmoid_init_f32**(riscv_svm_sigmoid_instance_f32 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float32_t intercept, const float32_t *dualCoefficients, const float32_t *supportVectors, const int32_t *classes, float32_t coef0, float32_t gamma)

void **riscv_svm_sigmoid_predict_f16**(const riscv_svm_sigmoid_instance_f16 *S, const float16_t *in, int32_t *pResult) void **riscv_svm_sigmoid_predict_f32**(const riscv_svm_sigmoid_instance_f32 *S, const float32_t *in, int32_t *pResult)

group **sigmoidsvm**

Sigmoid SVM classifier.

Functions

void **riscv_svm_sigmoid_init_f16**(riscv_svm_sigmoid_instance_f16 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float16_t intercept, const float16_t *dualCoefficients, const float16_t *supportVectors, const int32_t *classes, float16_t coef0, float16_t gamma)

SVM sigmoid instance init function.

Classes are integer used as output of the function (instead of having -1,1 as class values).

Parameters

- **S** – **[in]** points to an instance of the rbf SVM structure.
- **nbOfSupportVectors** – **[in]** Number of support vectors
- **vectorDimension** – **[in]** Dimension of vector space
- **intercept** – **[in]** Intercept
- **dualCoefficients** – **[in]** Array of dual coefficients
- **supportVectors** – **[in]** Array of support vectors
- **classes** – **[in]** Array of 2 classes ID
- **coef0** – **[in]** coeff0 (scikit-learn terminology)
- **gamma** – **[in]** gamma (scikit-learn terminology)

Returns none.

void **riscv_svm_sigmoid_init_f32**(riscv_svm_sigmoid_instance_f32 *S, uint32_t nbOfSupportVectors, uint32_t vectorDimension, float32_t intercept, const float32_t *dualCoefficients, const float32_t *supportVectors, const int32_t *classes, float32_t coef0, float32_t gamma)

SVM sigmoid instance init function.

Classes are integer used as output of the function (instead of having -1,1 as class values).

Parameters

- **S** – **[in]** points to an instance of the rbf SVM structure.
- **nbOfSupportVectors** – **[in]** Number of support vectors
- **vectorDimension** – **[in]** Dimension of vector space
- **intercept** – **[in]** Intercept
- **dualCoefficients** – **[in]** Array of dual coefficients
- **supportVectors** – **[in]** Array of support vectors
- **classes** – **[in]** Array of 2 classes ID
- **coef0** – **[in]** coeff0 (scikit-learn terminology)

- **gamma** – **[in]** gamma (scikit-learn terminology)

Returns none.

void **riscv_svm_sigmoid_predict_f16**(const riscv_svm_sigmoid_instance_f16 *S, const float16_t *in, int32_t *pResult)

SVM sigmoid prediction.

Parameters

- **S** – **[in]** Pointer to an instance of the rbf SVM structure.
- **in** – **[in]** Pointer to input vector
- **pResult** – **[out]** Decision value

Returns none.

void **riscv_svm_sigmoid_predict_f32**(const riscv_svm_sigmoid_instance_f32 *S, const float32_t *in, int32_t *pResult)

SVM sigmoid prediction.

Parameters

- **S** – **[in]** Pointer to an instance of the rbf SVM structure.
- **in** – **[in]** Pointer to input vector
- **pResult** – **[out]** Decision value

Returns none.

group **groupSVM**

This set of functions is implementing SVM classification on 2 classes. The training must be done from scikit-learn. The parameters can be easily generated from the scikit-learn object. Some examples are given in DSP/Testing/PatternGeneration/SVM.py.

If more than 2 classes are needed, the functions in this folder will have to be used, as building blocks, to do multi-class classification.

No multi-class classification is provided in this SVM folder.

3.3.14 Transform Functions

Complex FFT Functions

Complex FFT Tables

const uint16_t **riscvBitRevTable**[1024]

const uint64_t **twiddleCoefF64_16**[32]

const uint64_t **twiddleCoefF64_32**[64]

const uint64_t **twiddleCoefF64_64**[128]

const uint64_t **twiddleCoefF64_128**[256]

const uint64_t **twiddleCoefF64_256**[512]

const uint64_t **twiddleCoefF64_512**[1024]

const uint64_t **twiddleCoefF64_1024**[2048]

const uint64_t **twiddleCoefF64_2048**[4096]

const uint64_t **twiddleCoefF64_4096**[8192]

const float32_t **twiddleCoef_16**[32]

const float32_t **twiddleCoef_32**[64]

const float32_t **twiddleCoef_64**[128]

const float32_t **twiddleCoef_128**[256]

const float32_t **twiddleCoef_256**[512]

const float32_t **twiddleCoef_512**[1024]

const float32_t **twiddleCoef_1024**[2048]

const float32_t **twiddleCoef_2048**[4096]

const float32_t **twiddleCoef_4096**[8192]

const q31_t **twiddleCoef_16_q31**[24]

const q31_t **twiddleCoef_32_q31**[48]

const q31_t **twiddleCoef_64_q31**[96]

const q31_t **twiddleCoef_128_q31**[192]

const q31_t **twiddleCoef_256_q31**[384]

const q31_t **twiddleCoef_512_q31**[768]

const q31_t **twiddleCoef_1024_q31**[1536]

const q31_t **twiddleCoef_2048_q31**[3072]

const q31_t **twiddleCoef_4096_q31**[6144]

const q15_t **twiddleCoef_16_q15**[24]

const q15_t **twiddleCoef_32_q15**[48]

const q15_t **twiddleCoef_64_q15**[96]

const q15_t **twiddleCoef_128_q15**[192]

const q15_t **twiddleCoef_256_q15**[384]

const q15_t **twiddleCoef_512_q15**[768]

const q15_t **twiddleCoef_1024_q15**[1536]

const q15_t **twiddleCoef_2048_q15**[3072]

const q15_t **twiddleCoef_4096_q15**[6144]

const float16_t **twiddleCoefF16_16**[32]

const float16_t **twiddleCoefF16_32**[64]

const float16_t **twiddleCoefF16_64**[128]

const float16_t **twiddleCoefF16_128**[256]

const float16_t **twiddleCoefF16_256**[512]

const float16_t **twiddleCoefF16_512**[1024]

const float16_t **twiddleCoefF16_1024**[2048]

const float16_t **twiddleCoefF16_2048**[4096]

const float16_t **twiddleCoefF16_4096**[8192]

const float16_t **twiddleCoefF16_rfft_32**[32]

const float16_t **twiddleCoefF16_rfft_64**[64]

const float16_t **twiddleCoefF16_rfft_128**[128]

const float16_t **twiddleCoefF16_rfft_256**[256]

const float16_t **twiddleCoefF16_rfft_512**[512]

const float16_t **twiddleCoefF16_rfft_1024**[1024]

const float16_t **twiddleCoefF16_rfft_2048**[2048]

const float16_t **twiddleCoefF16_rfft_4096**[4096]

group **CFFT_CIFFT**

Variables

const uint16_t **riscvBitRevTable**[1024]

Table for bit reversal process.

Pseudo code for Generation of Bit reversal Table is

where N = 4096, logN2 = 12

N is the maximum FFT Size supported

const uint64_t **twiddleCoefF64_16**[32]

Double Precision Floating-point Twiddle factors Table Generation.

Example code for Double Precision Floating-point Twiddle factors Generation:

where N = 16, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const uint64_t **twiddleCoefF64_32**[64]

Example code for Double Precision Floating-point Twiddle factors Generation:

where N = 32, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const uint64_t **twiddleCoefF64_64**[128]

Example code for Double Precision Floating-point Twiddle factors Generation:

where N = 64, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const uint64_t **twiddleCoefF64_128**[256]

Example code for Double Precision Floating-point Twiddle factors Generation:

where N = 128, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const uint64_t **twiddleCoefF64_256**[512]

Example code for Double Precision Floating-point Twiddle factors Generation:

where N = 256, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const uint64_t **twiddleCoefF64_512**[1024]

Example code for Double Precision Floating-point Twiddle factors Generation:

where N = 512, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const uint64_t **twiddleCoefF64_1024**[2048]

Example code for Double Precision Floating-point Twiddle factors Generation:

where N = 1024, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const uint64_t **twiddleCoefF64_2048**[4096]

Example code for Double Precision Floating-point Twiddle factors Generation:

where N = 2048, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const uint64_t **twiddleCoefF64_4096**[8192]

Example code for Double Precision Floating-point Twiddle factors Generation:

where N = 4096, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float32_t **twiddleCoef_16**[32]

Example code for Floating-point Twiddle factors Generation:

where N = 16, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float32_t **twiddleCoef_32**[64]

Example code for Floating-point Twiddle factors Generation:

where N = 32, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float32_t **twiddleCoef_64**[128]

Example code for Floating-point Twiddle factors Generation:

where N = 64, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float32_t **twiddleCoef_128**[256]

Example code for Floating-point Twiddle factors Generation:

where N = 128, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float32_t **twiddleCoef_256**[512]

Example code for Floating-point Twiddle factors Generation:

where N = 256, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float32_t **twiddleCoef_512**[1024]

Example code for Floating-point Twiddle factors Generation:

where N = 512, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float32_t **twiddleCoef_1024**[2048]

Example code for Floating-point Twiddle factors Generation:

where N = 1024, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float32_t **twiddleCoef_2048**[4096]

Example code for Floating-point Twiddle factors Generation:

where N = 2048, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float32_t **twiddleCoef_4096**[8192]

Example code for Floating-point Twiddle factors Generation:

where N = 4096, PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const q31_t **twiddleCoef_16_q31**[24]

Q31 Twiddle factors Table.

Example code for Q31 Twiddle factors Generation::

where N = 16, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to Q31(Fixed point 1.31): round(twiddleCoefQ31(i) * pow(2, 31))

const q31_t **twiddleCoef_32_q31**[48]

Example code for Q31 Twiddle factors Generation::

where N = 32, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to Q31(Fixed point 1.31): round(twiddleCoefQ31(i) * pow(2, 31))

const q31_t **twiddleCoef_64_q31**[96]

Example code for Q31 Twiddle factors Generation::

where N = 64, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to Q31(Fixed point 1.31): round(twiddleCoefQ31(i) * pow(2, 31))

const q31_t **twiddleCoef_128_q31**[192]

Example code for Q31 Twiddle factors Generation::

where N = 128, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to Q31(Fixed point 1.31): round(twiddleCoefQ31(i) * pow(2, 31))

const q31_t **twiddleCoef_256_q31**[384]

Example code for Q31 Twiddle factors Generation::

where N = 256, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to Q31(Fixed point 1.31): round(twiddleCoefQ31(i) * pow(2, 31))

const q31_t **twiddleCoef_512_q31**[768]

Example code for Q31 Twiddle factors Generation::

where N = 512, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to Q31(Fixed point 1.31): round(twiddleCoefQ31(i) * pow(2, 31))

const q31_t **twiddleCoef_1024_q31**[1536]

Example code for Q31 Twiddle factors Generation::

where N = 1024, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to Q31(Fixed point 1.31): round(twiddleCoefQ31(i) * pow(2, 31))

const q31_t **twiddleCoef_2048_q31**[3072]

Example code for Q31 Twiddle factors Generation::

where N = 2048, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to Q31(Fixed point 1.31): round(twiddleCoefQ31(i) * pow(2, 31))

const q31_t **twiddleCoef_4096_q31**[6144]

Example code for Q31 Twiddle factors Generation::

where N = 4096, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to Q31(Fixed point 1.31): round(twiddleCoefQ31(i) * pow(2, 31))

const q15_t **twiddleCoef_16_q15**[24]

q15 Twiddle factors Table

Example code for q15 Twiddle factors Generation::

where N = 16, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to q15(Fixed point 1.15): round(twiddleCoefq15(i) * pow(2, 15))

const q15_t **twiddleCoef_32_q15**[48]

Example code for q15 Twiddle factors Generation::

where N = 32, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to q15(Fixed point 1.15): round(twiddleCoefq15(i) * pow(2, 15))

const q15_t **twiddleCoef_64_q15**[96]

Example code for q15 Twiddle factors Generation::

where N = 64, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to q15(Fixed point 1.15): round(twiddleCoefq15(i) * pow(2, 15))

const q15_t **twiddleCoef_128_q15**[192]

Example code for q15 Twiddle factors Generation::

where N = 128, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to q15(Fixed point 1.15): round(twiddleCoefq15(i) * pow(2, 15))

const q15_t **twiddleCoef_256_q15**[384]

Example code for q15 Twiddle factors Generation::

where N = 256, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to q15(Fixed point 1.15): round(twiddleCoefq15(i) * pow(2, 15))

const q15_t **twiddleCoef_512_q15**[768]

Example code for q15 Twiddle factors Generation::

where N = 512, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to q15(Fixed point 1.15): round(twiddleCoefq15(i) * pow(2, 15))

const q15_t **twiddleCoef_1024_q15**[1536]

Example code for q15 Twiddle factors Generation::

where N = 1024, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to q15(Fixed point 1.15): round(twiddleCoefq15(i) * pow(2, 15))

const q15_t **twiddleCoef_2048_q15**[3072]

Example code for q15 Twiddle factors Generation::

where N = 2048, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to q15(Fixed point 1.15): round(twiddleCoefq15(i) * pow(2, 15))

const q15_t **twiddleCoef_4096_q15**[6144]

Example code for q15 Twiddle factors Generation::

where N = 4096, PI = 3.14159265358979

Cos and Sin values are interleaved fashion

Convert Floating point to q15(Fixed point 1.15): round(twiddleCoefq15(i) * pow(2, 15))

const float16_t **twiddleCoefF16_16**[32]

Floating-point Twiddle factors Table Generation.

Example code for Floating-point Twiddle factors Generation:

where N = 16 and PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float16_t **twiddleCoefF16_32**[64]

Example code for Floating-point Twiddle factors Generation:

where N = 32 and PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float16_t **twiddleCoefF16_64**[128]

Example code for Floating-point Twiddle factors Generation:

where N = 64 and PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float16_t **twiddleCoefF16_128**[256]

Example code for Floating-point Twiddle factors Generation:

where N = 128 and PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float16_t **twiddleCoefF16_256**[512]

Example code for Floating-point Twiddle factors Generation:

where N = 256 and PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float16_t **twiddleCoefF16_512**[1024]

Example code for Floating-point Twiddle factors Generation:

where N = 512 and PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float16_t **twiddleCoefF16_1024**[2048]

Example code for Floating-point Twiddle factors Generation:

where N = 1024 and PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float16_t **twiddleCoefF16_2048**[4096]

Example code for Floating-point Twiddle factors Generation:

where N = 2048 and PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float16_t **twiddleCoefF16_4096**[8192]

Example code for Floating-point Twiddle factors Generation:

where N = 4096 and PI = 3.14159265358979

Cos and Sin values are in interleaved fashion

const float16_t **twiddleCoefF16_rfft_32**[32]

Example code for Floating-point RFFT Twiddle factors Generation:

Real and Imag values are in interleaved fashion

const float16_t **twiddleCoefF16_rfft_64**[64]

const float16_t **twiddleCoefF16_rfft_128**[128]

const float16_t **twiddleCoefF16_rfft_256**[256]

const float16_t **twiddleCoefF16_rfft_512**[512]

const float16_t **twiddleCoefF16_rfft_1024**[1024]

const float16_t **twiddleCoefF16_rfft_2048**[2048]

const float16_t **twiddleCoefF16_rfft_4096**[4096]

Complex FFT F16

void **riscv_cfft_f16**(const riscv_cfft_instance_f16 *S, float16_t *p1, uint8_t ifftFlag, uint8_t bitReverseFlag)

CFFTINIT_F16 (4096, 4096)

CFFTINIT_F16 (2048, 1024)

CFFTINIT_F16 (1024, 1024)

CFFTINIT_F16 (512, 256)

CFFTINIT_F16 (256, 256)

CFFTINIT_F16 (128, 64)

CFFTINIT_F16 (64, 64)

CFFTINIT_F16 (32, 16)

CFFTINIT_F16 (16, 16)

riscv_status **riscv_cfft_init_f16**(riscv_cfft_instance_f16 *S, uint16_t fftLen)

FFTINIT(EXT, SIZE)

CFFTINIT_F16(LEN, LENTWIDDLE)

group **ComplexFFTF16**

Defines

FFTINIT(EXT, SIZE)

CFFTINIT_F16(LEN, LENTWIDDLE)

Functions

void **riscv_cfft_f16**(const riscv_cfft_instance_f16 *S, float16_t *p1, uint8_t ifftFlag, uint8_t bitReverseFlag)

Processing function for the floating-point complex FFT.

Parameters

- `S` – **[in]** points to an instance of the floating-point CFFT structure
- `p1` – **[inout]** points to the complex data buffer of size `2*fftLen`. Processing occurs in-place
- `ifftFlag` – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- `bitReverseFlag` – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns none

CFFTINIT_F16 (4096, 4096)

Initialization function for the cfft f16 function with 4096 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using. variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

CFFTINIT_F16 (2048, 1024)

Initialization function for the cfft f16 function with 2048 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using. variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

CFFTINIT_F16 (1024, 1024)

Initialization function for the cfft f16 function with 1024 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using. variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F16 (512, 256)`

Initialization function for the cfft f16 function with 512 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using. variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F16 (256, 256)`

Initialization function for the cfft f16 function with 256 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using. variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F16 (128, 64)`

Initialization function for the cfft f16 function with 128 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using. variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F16 (64, 64)`

Initialization function for the cfft f16 function with 64 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using. variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F16 (32, 16)`

Initialization function for the cfft f16 function with 32 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using. variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F16 (16, 16)`

Initialization function for the cfft f16 function with 16 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using. variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **`riscv_cfft_init_f16`**(riscv_cfft_instance_f16 *S, uint16_t fftLen)

Generic initialization function for the cfft f16 function.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using. variables declared in riscv_const_structs.h

This function should be used only if you don't know the FFT sizes that. you'll need at build time. The use of this function will prevent the. linker from removing the FFT tables that are not needed and the library. code size will be bigger than needed.

If you use NMSIS-DSP as a static library, and if you know the FFT sizes. that you need at build time, then it is better to use the initialization functions defined for each FFT size.

Parameters

- **S** – **[inout]** points to an instance of the floating-point CFFT structure
- **fftLen** – **[in]** fft length (number of complex samples)

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

Complex FFT F32

void **riscv_cfft_f32**(const riscv_cfft_instance_f32 *S, float32_t *p1, uint8_t ifftFlag, uint8_t bitReverseFlag)

CFFTINIT_F32 (4096, 4096)

CFFTINIT_F32 (2048, 1024)

CFFTINIT_F32 (1024, 1024)

CFFTINIT_F32 (512, 256)

CFFTINIT_F32 (256, 256)

CFFTINIT_F32 (128, 64)

CFFTINIT_F32 (64, 64)

CFFTINIT_F32 (32, 16)

CFFTINIT_F32 (16, 16)

riscv_status **riscv_cfft_init_f32**(riscv_cfft_instance_f32 *S, uint16_t fftLen)

FFTINIT(EXT, SIZE)

CFFTINIT_F32(LEN, LENTWIDDLE)

group **ComplexFFTF32**

Defines

`FFTINIT`(EXT, SIZE)

`CFFTINIT_F32`(LEN, LENTWIDDLE)

Functions

void **riscv_cfft_f32**(const riscv_cfft_instance_f32 *S, float32_t *p1, uint8_t ifftFlag, uint8_t bitReverseFlag)

Processing function for the floating-point complex FFT.

Parameters

- `S` – **[in]** points to an instance of the floating-point CFFT structure
- `p1` – **[inout]** points to the complex data buffer of size `2*fftLen`. Processing occurs in-place
- **`ifftFlag`** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **`bitReverseFlag`** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns none

CFFTINIT_F32 (4096, 4096)

Initialization function for the cfft f32 function with 4096 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

CFFTINIT_F32 (2048, 1024)

Initialization function for the cfft f32 function with 2048 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F32 (1024, 1024)`

Initialization function for the cfft f32 function with 1024 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F32 (512, 256)`

Initialization function for the cfft f32 function with 512 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F32 (256, 256)`

Initialization function for the cfft f32 function with 256 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F32 (128, 64)`

Initialization function for the cfft f32 function with 128 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F32 (64, 64)`

Initialization function for the cfft f32 function with 64 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F32 (32, 16)`

Initialization function for the cfft f32 function with 32 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F32 (16, 16)`

Initialization function for the cfft f32 function with 16 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_cfft_init_f32**(riscv_cfft_instance_f32 *S, uint16_t fftLen)

Generic initialization function for the cfft f32 function.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

This function should be used only if you don't know the FFT sizes that you'll need at build time. The use of this function will prevent the linker from removing the FFT tables that are not needed and the library code size will be bigger than needed.

If you use NMSIS-DSP as a static library, and if you know the FFT sizes that you need at build time, then it is better to use the initialization functions defined for each FFT size.

Parameters

- `S` – **[inout]** points to an instance of the floating-point CFFT structure
- `fftLen` – **[in]** fft length (number of complex samples)

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

Complex FFT F64

void **riscv_cfft_f64**(const riscv_cfft_instance_f64 *S, float64_t *p1, uint8_t ifftFlag, uint8_t bitReverseFlag)

CFFTINIT_F64 (4096)

CFFTINIT_F64 (2048)

CFFTINIT_F64 (1024)

CFFTINIT_F64 (512)

CFFTINIT_F64 (256)

CFFTINIT_F64 (128)

CFFTINIT_F64 (64)

CFFTINIT_F64 (32)

CFFTINIT_F64 (16)

riscv_status **riscv_cfft_init_f64**(riscv_cfft_instance_f64 *S, uint16_t fftLen)

CFFTINIT_F64(LEN)

group **ComplexFFTF64**

Defines

`CFFTINIT_F64`(LEN)

Functions

void `riscv_cfft_f64`(const riscv_cfft_instance_f64 *S, float64_t *p1, uint8_t ifftFlag, uint8_t bitReverseFlag)

Processing function for the Double Precision floating-point complex FFT.

Parameters

- `S` – **[in]** points to an instance of the Double Precision floating-point CFFT structure
- `p1` – **[inout]** points to the complex data buffer of size `2*fftLen`. Processing occurs in-place
- `ifftFlag` – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- `bitReverseFlag` – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns none

`CFFTINIT_F64 (4096)`

Initialization function for the cfft f64 function with 4096 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F64 (2048)`

Initialization function for the cfft f64 function with 2048 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F64 (1024)`

Initialization function for the cfft f64 function with 1024 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F64 (512)`

Initialization function for the cfft f64 function with 512 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F64 (256)`

Initialization function for the cfft f64 function with 256 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_F64 (128)`

Initialization function for the cfft f64 function with 128 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful

- RISCV_MATH_ARGUMENT_ERROR : an error is detected

CFFTINIT_F64 (64)

Initialization function for the cfft f64 function with 64 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters S – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

CFFTINIT_F64 (32)

Initialization function for the cfft f64 function with 32 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters S – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

CFFTINIT_F64 (16)

Initialization function for the cfft f64 function with 16 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters S – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_cfft_init_f64**(riscv_cfft_instance_f64 *S, uint16_t fftLen)

Generic initialization function for the cfft f64 function.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

This function should be used only if you don't know the FFT sizes that you'll need at build time. The use of this function will prevent the linker from removing the FFT tables that are not needed and the library code size will be bigger than needed.

If you use NMSIS-DSP as a static library, and if you know the FFT sizes that you need at build time, then it is better to use the initialization functions defined for each FFT size.

Parameters

- `S` – **[inout]** points to an instance of the floating-point CFFT structure
- `fftLen` – **[in]** fft length (number of complex samples)

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

Complex FFT Q15

CFFTINIT_Q15 (4096, 4096)

CFFTINIT_Q15 (2048, 1024)

CFFTINIT_Q15 (1024, 1024)

CFFTINIT_Q15 (512, 256)

CFFTINIT_Q15 (256, 256)

CFFTINIT_Q15 (128, 64)

CFFTINIT_Q15 (64, 64)

CFFTINIT_Q15 (32, 16)

CFFTINIT_Q15 (16, 16)

riscv_status **riscv_cfft_init_q15**(riscv_cfft_instance_q15 *S, uint16_t fftLen)

void **riscv_cfft_q15**(const riscv_cfft_instance_q15 *S, q15_t *p1, uint8_t ifftFlag, uint8_t bitReverseFlag)

FFTINIT(EXT, SIZE)

CFFTINIT_Q15(LEN, LENTWIDDLE)

group **ComplexFFTQ15**

Defines

FFTINIT(EXT, SIZE)

CFFTINIT_Q15(LEN, LENTWIDDLE)

Functions

CFFTINIT_Q15 (4096, 4096)

Initialization function for the cfft q15 function for 4096 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters S – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

CFFTINIT_Q15 (2048, 1024)

Initialization function for the cfft q15 function for 2048 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters S – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

CFFTINIT_Q15 (1024, 1024)

Initialization function for the cfft q15 function for 1024 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters S – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_Q15 (512, 256)`

Initialization function for the cfft q15 function for 512 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_Q15 (256, 256)`

Initialization function for the cfft q15 function for 256 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_Q15 (128, 64)`

Initialization function for the cfft q15 function for 128 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_Q15 (64, 64)`

Initialization function for the cfft q15 function for 64 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful

- RISCV_MATH_ARGUMENT_ERROR : an error is detected

CFFTINIT_Q15 (32, 16)

Initialization function for the cfft q15 function for 32 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters **S** – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

CFFTINIT_Q15 (16, 16)

Initialization function for the cfft q15 function for 16 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters **S** – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_cfft_init_q15**(riscv_cfft_instance_q15 *S, uint16_t fftLen)

Generic initialization function for the cfft q15 function.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

This function should be used only if you don't know the FFT sizes that you'll need at build time. The use of this function will prevent the linker from removing the FFT tables that are not needed and the library code size will be bigger than needed.

If you use NMSIS-DSP as a static library, and if you know the FFT sizes that you need at build time, then it is better to use the initialization functions defined for each FFT size.

Parameters

- **S** – **[inout]** points to an instance of the floating-point CFFT structure
- **fftLen** – **[in]** fft length (number of complex samples)

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

void **riscv_cfft_q15**(const riscv_cfft_instance_q15 *S, q15_t *p1, uint8_t ifftFlag, uint8_t bitReverseFlag)

Processing function for Q15 complex FFT.

Parameters

- `S` – **[in]** points to an instance of Q15 CFFT structure
- `p1` – **[inout]** points to the complex data buffer of size `2*fftLen`. Processing occurs in-place
- `ifftFlag` – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- `bitReverseFlag` – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns none

Complex FFT Q31

CFFTINIT_Q31 (4096, 4096)

CFFTINIT_Q31 (2048, 1024)

CFFTINIT_Q31 (1024, 1024)

CFFTINIT_Q31 (512, 256)

CFFTINIT_Q31 (256, 256)

CFFTINIT_Q31 (128, 64)

CFFTINIT_Q31 (64, 64)

CFFTINIT_Q31 (32, 16)

CFFTINIT_Q31 (16, 16)

riscv_status **riscv_cfft_init_q31**(riscv_cfft_instance_q31 *S, uint16_t fftLen)

void **riscv_cfft_q31**(const riscv_cfft_instance_q31 *S, q31_t *p1, uint8_t ifftFlag, uint8_t bitReverseFlag)

FFTINIT(EXT, SIZE)

CFFTINIT_Q31(LEN, LENTWIDDLE)

group **ComplexFFTQ31**

Defines

FFTINIT(EXT, SIZE)

CFFTINIT_Q31(LEN, LENTWIDDLE)

Functions

CFFTINIT_Q31 (4096, 4096)

Initialization function for the cfft q31 function for 4096 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

CFFTINIT_Q31 (2048, 1024)

Initialization function for the cfft q31 function for 2048 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

CFFTINIT_Q31 (1024, 1024)

Initialization function for the cfft q31 function for 1024 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_Q31 (512, 256)`

Initialization function for the cfft q31 function for 512 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_Q31 (256, 256)`

Initialization function for the cfft q31 function for 256 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_Q31 (128, 64)`

Initialization function for the cfft q31 function for 128 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_Q31 (64, 64)`

Initialization function for the cfft q31 function for 64 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful

- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_Q31 (32, 16)`

Initialization function for the cfft q31 function for 32 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

`CFFTINIT_Q31 (16, 16)`

Initialization function for the cfft q31 function for 16 samples.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

Parameters `S` – **[inout]** points to an instance of the floating-point CFFT structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_cfft_init_q31**(riscv_cfft_instance_q31 *S, uint16_t fftLen)

Generic initialization function for the cfft q31 function.

Use of this function is mandatory only for the MVE version of the FFT. Other versions can still initialize directly the data structure using variables declared in riscv_const_structs.h

This function should be used only if you don't know the FFT sizes that you'll need at build time. The use of this function will prevent the linker from removing the FFT tables that are not needed and the library code size will be bigger than needed.

If you use NMSIS-DSP as a static library, and if you know the FFT sizes that you need at build time, then it is better to use the initialization functions defined for each FFT size.

Parameters

- `S` – **[inout]** points to an instance of the floating-point CFFT structure
- `fftLen` – **[in]** fft length (number of complex samples)

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

void **riscv_cfft_q31**(const riscv_cfft_instance_q31 *S, q31_t *p1, uint8_t ifftFlag, uint8_t bitReverseFlag)

Processing function for the Q31 complex FFT.

Parameters

- **S** – **[in]** points to an instance of the fixed-point CFFT structure
- **p1** – **[inout]** points to the complex data buffer of size `2*fftLen`. Processing occurs in-place
- **ifftFlag** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns none

Deprecated Complex FFT functions

void **riscv_cfft_radix2_f16**(const riscv_cfft_radix2_instance_f16 *S, float16_t *pSrc)

void **riscv_cfft_radix2_f32**(const riscv_cfft_radix2_instance_f32 *S, float32_t *pSrc)

riscv_status **riscv_cfft_radix2_init_f16**(riscv_cfft_radix2_instance_f16 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

riscv_status **riscv_cfft_radix2_init_f32**(riscv_cfft_radix2_instance_f32 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

riscv_status **riscv_cfft_radix2_init_q15**(riscv_cfft_radix2_instance_q15 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

riscv_status **riscv_cfft_radix2_init_q31**(riscv_cfft_radix2_instance_q31 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

void **riscv_cfft_radix2_q15**(const riscv_cfft_radix2_instance_q15 *S, q15_t *pSrc)

void **riscv_cfft_radix2_q31**(const riscv_cfft_radix2_instance_q31 *S, q31_t *pSrc)

void **riscv_cfft_radix4by2_f16**(float16_t *pSrc, uint32_t fftLen, const float16_t *pCoef)

void **riscv_cfft_radix4_f16**(const riscv_cfft_radix4_instance_f16 *S, float16_t *pSrc)

void **riscv_cfft_radix4_f32**(const riscv_cfft_radix4_instance_f32 *S, float32_t *pSrc)

riscv_status **riscv_cfft_radix4_init_f16**(riscv_cfft_radix4_instance_f16 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

riscv_status **riscv_cfft_radix4_init_f32**(riscv_cfft_radix4_instance_f32 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

riscv_status **riscv_cfft_radix4_init_q15**(riscv_cfft_radix4_instance_q15 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

riscv_status **riscv_cfft_radix4_init_q31**(riscv_cfft_radix4_instance_q31 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

void **riscv_cfft_radix4_q15**(const riscv_cfft_radix4_instance_q15 *S, q15_t *pSrc)

void **riscv_cfft_radix4_q31**(const riscv_cfft_radix4_instance_q31 *S, q31_t *pSrc)

group **ComplexFFTDeprecated**

Functions

void **riscv_cfft_radix2_f16**(const riscv_cfft_radix2_instance_f16 *S, float16_t *pSrc)

Radix-2 CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superseded by riscv_cfft_f16 and will be removed in the future

Parameters

- `S` – **[in]** points to an instance of the floating-point Radix-2 CFFT/CIFFT structure
- `pSrc` – **[inout]** points to the complex data buffer of size `2*fftLen`. Processing occurs in-place

Returns none

void **riscv_cfft_radix2_f32**(const riscv_cfft_radix2_instance_f32 *S, float32_t *pSrc)

Radix-2 CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superseded by riscv_cfft_f32 and will be removed in the future

Parameters

- `S` – **[in]** points to an instance of the floating-point Radix-2 CFFT/CIFFT structure
- `pSrc` – **[inout]** points to the complex data buffer of size `2*fftLen`. Processing occurs in-place

Returns none

riscv_status **riscv_cfft_radix2_init_f16**(riscv_cfft_radix2_instance_f16 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

Initialization function for the floating-point CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superseded by riscv_cfft_f16 and will be removed in the future.

Details The parameter `ifftFlag` controls whether a forward or inverse transform is computed. Set(=1) ifftFlag for calculation of CIFFT otherwise CFFT is calculated

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

The parameter `fftLen` Specifies length of CFFT/CIFFT process. Supported FFT Lengths are 16, 64, 256, 1024.

This Function also initializes Twiddle factor table pointer and Bit reversal table pointer.

Parameters

- **S** – **[inout]** points to an instance of the floating-point CFFT/CIFFT structure
- **fftLen** – **[in]** length of the FFT
- **ifftFlag** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLen` is not a supported length

riscv_status **riscv_cfft_radix2_init_f32**(riscv_cfft_radix2_instance_f32 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

Initialization function for the floating-point CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superseded by riscv_cfft_f32 and will be removed in the future.

Details The parameter `ifftFlag` controls whether a forward or inverse transform is computed. Set(=1) ifftFlag for calculation of CIFFT otherwise CFFT is calculated

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

The parameter `fftLen` Specifies length of CFFT/CIFFT process. Supported FFT Lengths are 16, 64, 256, 1024.

This Function also initializes Twiddle factor table pointer and Bit reversal table pointer.

Parameters

- **S** – **[inout]** points to an instance of the floating-point CFFT/CIFFT structure
- **fftLen** – **[in]** length of the FFT
- **ifftFlag** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output

- value = 0: disables bit reversal of output
- value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLen` is not a supported length

riscv_status **riscv_cfft_radix2_init_q15**(riscv_cfft_radix2_instance_q15 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

Initialization function for the Q15 CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superseded by riscv_cfft_q15 and will be removed

Details The parameter `ifftFlag` controls whether a forward or inverse transform is computed. Set(=1) ifftFlag for calculation of CIFFT otherwise CFFT is calculated

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

The parameter `fftLen` Specifies length of CFFT/CIFFT process. Supported FFT Lengths are 16, 64, 256, 1024.

This Function also initializes Twiddle factor table pointer and Bit reversal table pointer.

Parameters

- **S** – **[inout]** points to an instance of the Q15 CFFT/CIFFT structure.
- **fftLen** – **[in]** length of the FFT.
- **ifftFlag** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLen` is not a supported length

riscv_status **riscv_cfft_radix2_init_q31**(riscv_cfft_radix2_instance_q31 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

Initialization function for the Q31 CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superseded by riscv_cfft_q31 and will be removed in the future.

Details The parameter `ifftFlag` controls whether a forward or inverse transform is computed. Set(=1) ifftFlag for calculation of CIFFT otherwise CFFT is calculated

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

The parameter `fftLen` Specifies length of CFFT/CIFFT process. Supported FFT Lengths are 16, 64, 256, 1024.

This Function also initializes Twiddle factor table pointer and Bit reversal table pointer.

Parameters

- **S** – **[inout]** points to an instance of the Q31 CFFT/CIFFT structure
- **fftLen** – **[in]** length of the FFT
- **ifftFlag** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLen` is not a supported length

void **riscv_cfft_radix2_q15**(const riscv_cfft_radix2_instance_q15 *S, q15_t *pSrc)

Processing function for the fixed-point CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superseded by riscv_cfft_q15 and will be removed in the future.

Parameters

- **S** – **[in]** points to an instance of the fixed-point CFFT/CIFFT structure
- **pSrc** – **[inout]** points to the complex data buffer of size `2*fftLen`. Processing occurs in-place

Returns none

void **riscv_cfft_radix2_q31**(const riscv_cfft_radix2_instance_q31 *S, q31_t *pSrc)

Processing function for the fixed-point CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superseded by riscv_cfft_q31 and will be removed in the future.

Parameters

- **S** – **[in]** points to an instance of the fixed-point CFFT/CIFFT structure

- **pSrc** – **[inout]** points to the complex data buffer of size `2*fftLen`. Processing occurs in-place

Returns none

void **riscv_cfft_radix4by2_f16**(float16_t *pSrc, uint32_t fftLen, const float16_t *pCoef)

void **riscv_cfft_radix4_f16**(const riscv_cfft_radix4_instance_f16 *S, float16_t *pSrc)

Processing function for the floating-point Radix-4 CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superseded by riscv_cfft_f16 and will be removed in the future.

Parameters

- **S** – **[in]** points to an instance of the floating-point Radix-4 CFFT/CIFFT structure
- **pSrc** – **[inout]** points to the complex data buffer of size `2*fftLen`. Processing occurs in-place

Returns none

void **riscv_cfft_radix4_f32**(const riscv_cfft_radix4_instance_f32 *S, float32_t *pSrc)

Processing function for the floating-point Radix-4 CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superseded by riscv_cfft_f32 and will be removed in the future.

Parameters

- **S** – **[in]** points to an instance of the floating-point Radix-4 CFFT/CIFFT structure
- **pSrc** – **[inout]** points to the complex data buffer of size `2*fftLen`. Processing occurs in-place

Returns none

riscv_status **riscv_cfft_radix4_init_f16**(riscv_cfft_radix4_instance_f16 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

Initialization function for the floating-point CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superceded by riscv_cfft_f16 and will be removed in the future.

Details The parameter `ifftFlag` controls whether a forward or inverse transform is computed. Set(=1) ifftFlag for calculation of CIFFT otherwise CFFT is calculated

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

The parameter `fftLen` Specifies length of CFFT/CIFFT process. Supported FFT Lengths are 16, 64, 256, 1024.

This Function also initializes Twiddle factor table pointer and Bit reversal table pointer.

Parameters

- `S` – **[inout]** points to an instance of the floating-point CFFT/CIFFT structure
- `fftLen` – **[in]** length of the FFT
- `ifftFlag` – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- `bitReverseFlag` – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLen` is not a supported length

riscv_status **`riscv_cfft_radix4_init_f32`**(riscv_cfft_radix4_instance_f32 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

Initialization function for the floating-point CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superceded by riscv_cfft_f32 and will be removed in the future.

Details The parameter `ifftFlag` controls whether a forward or inverse transform is computed. Set(=1) ifftFlag for calculation of CIFFT otherwise CFFT is calculated

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

The parameter `fftLen` Specifies length of CFFT/CIFFT process. Supported FFT Lengths are 16, 64, 256, 1024.

This Function also initializes Twiddle factor table pointer and Bit reversal table pointer.

Parameters

- `S` – **[inout]** points to an instance of the floating-point CFFT/CIFFT structure
- `fftLen` – **[in]** length of the FFT
- `ifftFlag` – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- `bitReverseFlag` – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLen` is not a supported length

riscv_status **riscv_cfft_radix4_init_q15**(riscv_cfft_radix4_instance_q15 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

Initialization function for the Q15 CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superseded by riscv_cfft_q15 and will be removed in the future.

Details The parameter `ifftFlag` controls whether a forward or inverse transform is computed. Set(=1) ifftFlag for calculation of CIFFT otherwise CFFT is calculated

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

The parameter `fftLen` Specifies length of CFFT/CIFFT process. Supported FFT Lengths are 16, 64, 256, 1024.

This Function also initializes Twiddle factor table pointer and Bit reversal table pointer.

Parameters

- **S** – **[inout]** points to an instance of the Q15 CFFT/CIFFT structure
- **fftLen** – **[in]** length of the FFT
- **ifftFlag** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLen` is not a supported length

riscv_status **riscv_cfft_radix4_init_q31**(riscv_cfft_radix4_instance_q31 *S, uint16_t fftLen, uint8_t ifftFlag, uint8_t bitReverseFlag)

Initialization function for the Q31 CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superseded by riscv_cfft_q31 and will be removed in the future.

Details The parameter `ifftFlag` controls whether a forward or inverse transform is computed. Set(=1) ifftFlag for calculation of CIFFT otherwise CFFT is calculated

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

The parameter `fftLen` Specifies length of CFFT/CIFFT process. Supported FFT Lengths are 16, 64, 256, 1024.

This Function also initializes Twiddle factor table pointer and Bit reversal table pointer.

Parameters

- `S` – **[inout]** points to an instance of the Q31 CFFT/CIFFT structure.
- `fftLen` – **[in]** length of the FFT.
- `ifftFlag` – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- `bitReverseFlag` – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLen` is not a supported length

void **riscv_cfft_radix4_q15**(const riscv_cfft_radix4_instance_q15 *S, q15_t *pSrc)

Processing function for the Q15 CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superseded by riscv_cfft_q15 and will be removed in the future.

CFFT Size	Input format	Output format	Number of bits to upscale
16	1.15	5.11	4
64	1.15	7.9	6
256	1.15	9.7	8
1024	1.15	11.5	10

Input and output formats: Internally input is downscaled by 2 for every stage to avoid saturations inside CFFT/CIFFT process. Hence the output format is different for different FFT sizes. The input and output formats for different FFT sizes and number of bits to upscale are mentioned in the tables below for CFFT and CIFFT:

CIFFT Size	Input format	Output format	Number of bits to upscale
16	1.15	5.11	0
64	1.15	7.9	0
256	1.15	9.7	0
1024	1.15	11.5	0

Parameters

- `S` – **[in]** points to an instance of the Q15 CFFT/CIFFT structure.
- `pSrc` – **[inout]** points to the complex data buffer. Processing occurs in-place.

Returns none

void **riscv_cfft_radix4_q31**(const riscv_cfft_radix4_instance_q31 *S, q31_t *pSrc)

Processing function for the Q31 CFFT/CIFFT.

Deprecated:

Do not use this function. It has been superseded by riscv_cfft_q31 and will be removed in the future.

CFFT Size	Input format	Output format	Number of bits to upscale
16	1.31	5.27	4
64	1.31	7.25	6
256	1.31	9.23	8
1024	1.31	11.21	10

Input and output formats: Internally input is downscaled by 2 for every stage to avoid saturations inside CFFT/CIFFT process. Hence the output format is different for different FFT sizes. The input and output formats for different FFT sizes and number of bits to upscale are mentioned in the tables below for CFFT and CIFFT:

CIFFT Size	Input format	Output format	Number of bits to upscale
16	1.31	5.27	0
64	1.31	7.25	0
256	1.31	9.23	0
1024	1.31	11.21	0

Parameters

- `S` – **[in]** points to an instance of the Q31 CFFT/CIFFT structure
- `pSrc` – **[inout]** points to the complex data buffer of size `2*fftLen`. Processing occurs in-place

Returns none

group **ComplexFFT**

The Fast Fourier Transform (FFT) is an efficient algorithm for computing the Discrete Fourier Transform (DFT). The FFT can be orders of magnitude faster than the DFT, especially for long lengths. The algorithms described in this section operate on complex data. A separate set of functions is devoted to handling of real sequences.

There are separate algorithms for handling floating-point, Q15, and Q31 data types. The algorithms available for each data type are described next.

The FFT functions operate in-place. That is, the array holding the input data will also be used to hold the corresponding result. The input data is complex and contains `2*fftLen` interleaved values as shown below. The FFT result will be contained in the same array and the frequency domain values will have the same interleaving.

Floating-point The floating-point complex FFT uses a mixed-radix algorithm. Multiple radix-8 stages are performed along with a single radix-2 or radix-4 stage, as needed. The algorithm supports lengths of [16, 32, 64, …, 4096] and each length uses a different twiddle factor table.

The function uses the standard FFT definition and output values may grow by a factor of `fftLen` when computing the forward transform. The inverse transform includes a scale of `1/fftLen` as part of the calculation and this matches the textbook definition of the inverse FFT.

For the MVE version, the new riscv_cfft_init_f32 initialization function is **mandatory**. **Compilation flags are available to include only the required tables for the needed FFTs.** Other FFT versions can continue to be initialized as explained below.

For not MVE versions, pre-initialized data structures containing twiddle factors and bit reversal tables are provided and defined in `riscv_const_structs.h`. Include this header in your function and then pass one of the constant structures as an argument to riscv_cfft_f32. For example:

`riscv_cfft_f32(riscv_cfft_sR_f32_len64, pSrc, 1, 1)`

computes a 64-point inverse complex FFT including bit reversal. The data structures are treated as constant data and not modified during the calculation. The same data structure can be reused for multiple transforms including mixing forward and inverse transforms.

Earlier releases of the library provided separate radix-2 and radix-4 algorithms that operated on floating-point data. These functions are still provided but are deprecated. The older functions are slower and less general than the new functions.

An example of initialization of the constants for the riscv_cfft_f32 function follows:

```
const static riscv_cfft_instance_f32 *S;
...
switch (length) {
  case 16:
    S = &riscv_cfft_sR_f32_len16;
    break;
  case 32:
    S = &riscv_cfft_sR_f32_len32;
    break;
  case 64:
    S = &riscv_cfft_sR_f32_len64;
    break;
  case 128:
    S = &riscv_cfft_sR_f32_len128;
    break;
  case 256:
    S = &riscv_cfft_sR_f32_len256;
    break;
  case 512:
    S = &riscv_cfft_sR_f32_len512;
    break;
  case 1024:
    S = &riscv_cfft_sR_f32_len1024;
    break;
  case 2048:
    S = &riscv_cfft_sR_f32_len2048;
    break;
  case 4096:
    S = &riscv_cfft_sR_f32_len4096;
    break;
}
```

The new riscv_cfft_init_f32 can also be used.

Q15 and Q31 The floating-point complex FFT uses a mixed-radix algorithm. Multiple radix-4 stages are performed along with a single radix-2 stage, as needed. The algorithm supports lengths of [16, 32, 64, ..., 4096] and each length uses a different twiddle factor table.

The function uses the standard FFT definition and output values may grow by a factor of `fftLen` when computing the forward transform. The inverse transform includes a scale of `1/fftLen` as part of the calculation and this matches the textbook definition of the inverse FFT.

Pre-initialized data structures containing twiddle factors and bit reversal tables are provided and defined in `riscv_const_structs.h`. Include this header in your function and then pass one of the constant structures as an argument to riscv_cfft_q31. For example:

`riscv_cfft_q31(riscv_cfft_sR_q31_len64, pSrc, 1, 1)`

computes a 64-point inverse complex FFT including bit reversal. The data structures are treated as constant data and not modified during the calculation. The same data structure can be reused for multiple transforms including mixing forward and inverse transforms.

Earlier releases of the library provided separate radix-2 and radix-4 algorithms that operated on floating-point data. These functions are still provided but are deprecated. The older functions are slower and less general than the new functions.

An example of initialization of the constants for the riscv_cfft_q31 function follows:

```
const static riscv_cfft_instance_q31 *S;
...
  switch (length) {
    case 16:
      S = &riscv_cfft_sR_q31_len16;
      break;
    case 32:
      S = &riscv_cfft_sR_q31_len32;
      break;
    case 64:
      S = &riscv_cfft_sR_q31_len64;
      break;
    case 128:
      S = &riscv_cfft_sR_q31_len128;
      break;
    case 256:
      S = &riscv_cfft_sR_q31_len256;
      break;
    case 512:
      S = &riscv_cfft_sR_q31_len512;
      break;
    case 1024:
      S = &riscv_cfft_sR_q31_len1024;
      break;
    case 2048:
      S = &riscv_cfft_sR_q31_len2048;
      break;
    case 4096:
      S = &riscv_cfft_sR_q31_len4096;
      break;
  }
```

DCT Type IV Functions

DCT Type IV Tables

const float32_t **Weights_128**[256]

const float32_t **cos_factors_128**[128]

const float32_t **Weights_512**[1024]

const float32_t **cos_factors_512**[512]

const float32_t **Weights_2048**[4096]

const float32_t **cos_factors_2048**[2048]

const float32_t **Weights_8192**[16384]

const float32_t **cos_factors_8192**[8192]

const q31_t **WeightsQ31_128**[256]

const q31_t **cos_factorsQ31_128**[128]

const q31_t **WeightsQ31_512**[1024]

const q31_t **cos_factorsQ31_512**[512]

const q31_t **WeightsQ31_2048**[4096]

const q31_t **cos_factorsQ31_2048**[2048]

const q31_t **WeightsQ31_8192**[16384]

const q31_t **cos_factorsQ31_8192**[8192]

group **DCT4_IDCT4_Table**

end of RealFFT_Table group

Variables

const float32_t **Weights_128**[256]

Weights Table.

Weights tables are generated using the formula :

C command to generate the table

where `N` is the Number of weights to be calculated and `c` is `pi/(2*N)`

In the tables below the real and imaginary values are placed alternatively, hence the array length is `2*N`.

cosFactor tables are generated using the formula :

C command to generate the table

where `N` is the number of factors to generate and `c` is `pi/(2*N)`

const float32_t **cos_factors_128**[128]

const float32_t **Weights_512**[1024]

const float32_t **cos_factors_512**[512]

const float32_t **Weights_2048**[4096]

const float32_t **cos_factors_2048**[2048]

const float32_t **Weights_8192**[16384]

const float32_t **cos_factors_8192**[8192]

const q31_t **WeightsQ31_128**[256]

Weights tables are generated using the formula :

C command to generate the table

where `N` is the Number of weights to be calculated and `c` is `pi/(2*N)`

Convert the output to q31 format by multiplying with 2^31 and saturated if required.

In the tables below the real and imaginary values are placed alternatively, hence the array length is `2*N`.

cosFactor tables are generated using the formula :

C command to generate the table

where `N` is the number of factors to generate and `c` is `pi/(2*N)`

Then converted to q31 format by multiplying with 2^31 and saturated if required.

const q31_t **cos_factorsQ31_128**[128]

const q31_t **WeightsQ31_512**[1024]

const q31_t **cos_factorsQ31_512**[512]

const q31_t **WeightsQ31_2048**[4096]

const q31_t **cos_factorsQ31_2048**[2048]

const q31_t **WeightsQ31_8192**[16384]

const q31_t **cos_factorsQ31_8192**[8192]

DCT4 F32

void **riscv_dct4_f32**(const riscv_dct4_instance_f32 *S, float32_t *pState, float32_t *pInlineBuffer)

riscv_status **riscv_dct4_init_f32**(riscv_dct4_instance_f32 *S, riscv_rfft_instance_f32 *S_RFFT, riscv_cfft_radix4_instance_f32 *S_CFFT, uint16_t N, uint16_t Nby2, float32_t normalize)

group **DCT4F32**

Functions

void **riscv_dct4_f32**(const riscv_dct4_instance_f32 *S, float32_t *pState, float32_t *pInlineBuffer)

Processing function for the floating-point DCT4/IDCT4.

Deprecated:

Do not use this function. It is using a deprecated version of the RFFT.

Parameters

- **S** – **[in]** points to an instance of the floating-point DCT4/IDCT4 structure
- **pState** – **[in]** points to state buffer
- **pInlineBuffer** – **[inout]** points to the in-place input and output buffer

Returns none

riscv_status **riscv_dct4_init_f32**(riscv_dct4_instance_f32 *S, riscv_rfft_instance_f32 *S_RFFT, riscv_cfft_radix4_instance_f32 *S_CFFT, uint16_t N, uint16_t Nby2, float32_t normalize)

Initialization function for the floating-point DCT4/IDCT4.

Deprecated:

Do not use this function. It is using a deprecated version of the RFFT.

DCT Size	Normalizing factor value
2048	0.03125
512	0.0625
128	0.125

Normalizing factor The normalizing factor is `sqrt(2/N)`, which depends on the size of transform `N`. Floating-point normalizing factors are mentioned in the table below for different DCT sizes:

Parameters

- **S** – **[inout]** points to an instance of floating-point DCT4/IDCT4 structure
- **S_RFFT** – **[in]** points to an instance of floating-point RFFT/RIFFT structure
- **S_CFFT** – **[in]** points to an instance of floating-point CFFT/CIFFT structure
- **N** – **[in]** length of the DCT4
- **Nby2** – **[in]** half of the length of the DCT4
- **normalize** – **[in]** normalizing factor.

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `N` is not a supported transform length

DCT4 Q15

riscv_status **riscv_dct4_init_q15**(riscv_dct4_instance_q15 *S, riscv_rfft_instance_q15 *S_RFFT, riscv_cfft_radix4_instance_q15 *S_CFFT, uint16_t N, uint16_t Nby2, q15_t normalize)

void **riscv_dct4_q15**(const riscv_dct4_instance_q15 *S, q15_t *pState, q15_t *pInlineBuffer)

group **DCT4Q15**

Functions

riscv_status **riscv_dct4_init_q15**(riscv_dct4_instance_q15 *S, riscv_rfft_instance_q15 *S_RFFT, riscv_cfft_radix4_instance_q15 *S_CFFT, uint16_t N, uint16_t Nby2, q15_t normalize)

Initialization function for the Q15 DCT4/IDCT4.

Deprecated:

Do not use this function. It will be removed in future versions.

DCT Size	Normalizing factor value (hexadecimal)
2048	0x400
512	0x800
128	0x1000

Normalizing factor The normalizing factor is `sqrt(2/N)`, which depends on the size of transform `N`. Normalizing factors in 1.15 format are mentioned in the table below for different DCT sizes:

Parameters

- `S` – **[inout]** points to an instance of Q15 DCT4/IDCT4 structure
- `S_RFFT` – **[in]** points to an instance of Q15 RFFT/RIFFT structure
- `S_CFFT` – **[in]** points to an instance of Q15 CFFT/CIFFT structure
- `N` – **[in]** length of the DCT4
- `Nby2` – **[in]** half of the length of the DCT4
- `normalize` – **[in]** normalizing factor

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `N` is not a supported transform length

void **riscv_dct4_q15**(const riscv_dct4_instance_q15 *S, q15_t *pState, q15_t *pInlineBuffer)

Processing function for the Q15 DCT4/IDCT4.

Deprecated:

Do not use this function. It will be removed in future versions.

DCT Size	Input format	Output format	Number of bits to upscale
2048	1.15	11.5	10
512	1.15	9.7	8
128	1.15	7.9	6

Input an output formats Internally inputs are downscaled in the RFFT process function to avoid overflows. Number of bits downscaled, depends on the size of the transform. The input and output formats for different DCT sizes and number of bits to upscale are mentioned in the table below:

Parameters

- `S` – **[in]** points to an instance of the Q15 DCT4 structure.
- `pState` – **[in]** points to state buffer.
- `pInlineBuffer` – **[inout]** points to the in-place input and output buffer.

Returns none

DCT4 Q31

riscv_status **riscv_dct4_init_q31**(riscv_dct4_instance_q31 *S, riscv_rfft_instance_q31 *S_RFFT, riscv_cfft_radix4_instance_q31 *S_CFFT, uint16_t N, uint16_t Nby2, q31_t normalize)

void **riscv_dct4_q31**(const riscv_dct4_instance_q31 *S, q31_t *pState, q31_t *pInlineBuffer)

group **DCT4Q31**

Functions

riscv_status **riscv_dct4_init_q31**(riscv_dct4_instance_q31 *S, riscv_rfft_instance_q31 *S_RFFT, riscv_cfft_radix4_instance_q31 *S_CFFT, uint16_t N, uint16_t Nby2, q31_t normalize)

Initialization function for the Q31 DCT4/IDCT4.

Deprecated:

Do not use this function. It will be removed in future versions.

DCT Size	Normalizing factor value (hexadecimal)
2048	0x4000000
512	0x8000000
128	0x10000000

Normalizing factor: The normalizing factor is `sqrt(2/N)`, which depends on the size of transform `N`. Normalizing factors in 1.31 format are mentioned in the table below for different DCT sizes:

Parameters

- **S** – **[inout]** points to an instance of Q31 DCT4/IDCT4 structure.
- **S_RFFT** – **[in]** points to an instance of Q31 RFFT/RIFFT structure
- **S_CFFT** – **[in]** points to an instance of Q31 CFFT/CIFFT structure
- **N** – **[in]** length of the DCT4.
- **Nby2** – **[in]** half of the length of the DCT4.
- **normalize** – **[in]** normalizing factor.

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `N` is not a supported transform length

void **riscv_dct4_q31**(const riscv_dct4_instance_q31 *S, q31_t *pState, q31_t *pInlineBuffer)

Processing function for the Q31 DCT4/IDCT4.

Deprecated:

Do not use this function. It will be removed in future versions.

DCT Size	Input format	Output format	Number of bits to upscale
2048	2.30	12.20	11
512	2.30	10.22	9
128	2.30	8.24	7

Input an output formats Input samples need to be downscaled by 1 bit to avoid saturations in the Q31 DCT process, as the conversion from DCT2 to DCT4 involves one subtraction. Internally inputs are downscaled in the RFFT process function to avoid overflows. Number of bits downscaled, depends on the size of the transform. The input and output formats for different DCT sizes and number of bits to upscale are mentioned in the table below:

Parameters

- **`S`** – **[in]** points to an instance of the Q31 DCT4 structure.
- **`pState`** – **[in]** points to state buffer.
- **`pInlineBuffer`** – **[inout]** points to the in-place input and output buffer.

Returns none

group **`DCT4_IDCT4`**

Representation of signals by minimum number of values is important for storage and transmission. The possibility of large discontinuity between the beginning and end of a period of a signal in DFT can be avoided by extending the signal so that it is even-symmetric. Discrete Cosine Transform (DCT) is constructed such that its energy is heavily concentrated in the lower part of the spectrum and is very widely used in signal and image coding applications. The family of DCTs (DCT type- 1,2,3,4) is the outcome of different combinations of homogeneous boundary conditions. DCT has an excellent energy-packing capability, hence has many applications and in data compression in particular.

DCT is essentially the Discrete Fourier Transform(DFT) of an even-extended real signal. Reordering of the input data makes the computation of DCT just a problem of computing the DFT of a real signal with a few additional operations. This approach provides regular, simple, and very efficient DCT algorithms for practical hardware and software implementations.

DCT type-II can be implemented using Fast fourier transform (FFT) internally, as the transform is applied on real values, Real FFT can be used. DCT4 is implemented using DCT2 as their implementations are similar except with some added pre-processing and post-processing. DCT2 implementation can be described in the following steps:

- Re-ordering input
- Calculating Real FFT
- Multiplication of weights and Real FFT output and getting real part from the product.



This process is explained by the block diagram below:

Algorithm The N-point type-IV DCT is defined as a real, linear transformation by the formula:

$$X_c(k) = \sqrt{\frac{2}{N}} \sum_{n=0}^{N-1} x(n)cos\Big[\Big(n+\frac{1}{2}\Big)\Big(k+\frac{1}{2}\Big)\frac{\pi}{N}\Big]$$

where `k = 0, 1, 2, ..., N-1`

Its inverse is defined as follows:

$$x(n) = \sqrt{\frac{2}{N}} \sum_{k=0}^{N-1} X_c(k)cos\Big[\Big(n+\frac{1}{2}\Big)\Big(k+\frac{1}{2}\Big)\frac{\pi}{N}\Big]$$

where `n = 0, 1, 2, ..., N-1`

The DCT4 matrices become involutory (i.e. they are self-inverse) by multiplying with an overall scale factor of sqrt(2/N). The symmetry of the transform matrix indicates that the fast algorithms for the forward and inverse transform computation are identical. Note that the implementation of Inverse DCT4 and DCT4 is same, hence same process function can be used for both.

Lengths supported by the transform: As DCT4 internally uses Real FFT, it supports all the lengths 128, 512, 2048 and 8192. The library provides separate functions for Q15, Q31, and floating-point data types.

Instance Structure The instances for Real FFT and FFT, cosine values table and twiddle factor table are stored in an instance data structure. A separate instance structure must be defined for each transform. There are separate instance structure declarations for each of the 3 supported data types.

Initialization Functions There is also an associated initialization function for each data type. The initialization function performs the following operations:

- Sets the values of the internal structure fields.
- Initializes Real FFT as its process function is used internally in DCT4, by calling riscv_rfft_init_f32().

Use of the initialization function is optional. However, if the initialization function is used, then the instance structure cannot be placed into a const data section. To place an instance structure into a const data section, the instance structure must be manually initialized. Manually initialize the instance structure as follows: where `N` is the length of the DCT4; `Nby2` is half of the length of the DCT4; `normalize` is normalizing factor used and is equal to `sqrt(2/N)`; `pTwiddle` points to the twiddle factor table; `pCosFactor` points to the cosFactor table; `pRfft` points to the real FFT instance; `pCfft` points to the complex FFT instance; The CFFT and RFFT structures also needs to be initialized, refer to riscv_cfft_radix4_f32() and riscv_rfft_f32() respectively for details regarding static initialization.

Fixed-Point Behavior Care must be taken when using the fixed-point versions of the DCT4 transform functions. In particular, the overflow and saturation behavior of the accumulator used in each function must be considered. Refer to the function specific documentation below for usage guidelines.

MFCC

MFCC F32

void **`riscv_mfcc_f32`**(const riscv_mfcc_instance_f32 *S, float32_t *pSrc, float32_t *pDst, float32_t *pTmp)

group **`MFCCF32`**

Functions

void **riscv_mfcc_f32**(const riscv_mfcc_instance_f32 *S, float32_t *pSrc, float32_t *pDst, float32_t *pTmp)

MFCC F32.

The temporary buffer has a 2*fft length size when MFCC is implemented with CFFT. It has length FFT Length + 2 when implemented with RFFT (default implementation).

Description The number of input samples if the FFT length used when initializing the instance data structure.

The source buffer is modified by this function.

Parameters

- `S` – **[in]** points to the mfcc instance structure
- `pSrc` – **[in]** points to the input samples
- `pDst` – **[out]** points to the output MFCC values
- `pTmp` – **[inout]** points to a temporary buffer of complex

Returns none

MFCC F16

void **riscv_mfcc_f16**(const riscv_mfcc_instance_f16 *S, float16_t *pSrc, float16_t *pDst, float16_t *pTmp)

riscv_status **riscv_mfcc_init_f16**(riscv_mfcc_instance_f16 *S, uint32_t fftLen, uint32_t nbMelFilters, uint32_t nbDctOutputs, const float16_t *dctCoefs, const uint32_t *filterPos, const uint32_t *filterLengths, const float16_t *filterCoefs, const float16_t *windowCoefs)

MFCC_INIT_F16 (32)

MFCC_INIT_F16 (64)

MFCC_INIT_F16 (128)

MFCC_INIT_F16 (256)

MFCC_INIT_F16 (512)

MFCC_INIT_F16 (1024)

MFCC_INIT_F16 (2048)

MFCC_INIT_F16 (4096)

MFCC_INIT_F16(LEN)

group **MFCCF16**

Defines

MFCC_INIT_F16(LEN)

Functions

void **riscv_mfcc_f16**(const riscv_mfcc_instance_f16 *S, float16_t *pSrc, float16_t *pDst, float16_t *pTmp)

MFCC F16.

The temporary buffer has a 2*fft length size when MFCC is implemented with CFFT. It has length FFT Length + 2 when implemented with RFFT (default implementation).

Description The number of input samples if the FFT length used when initializing the instance data structure.

The source buffer is modified by this function.

Parameters

- **S** – **[in]** points to the mfcc instance structure
- **pSrc** – **[in]** points to the input samples
- **pDst** – **[out]** points to the output MFCC values
- **pTmp** – **[inout]** points to a temporary buffer of complex

Returns none

riscv_status **riscv_mfcc_init_f16**(riscv_mfcc_instance_f16 *S, uint32_t fftLen, uint32_t nbMelFilters, uint32_t nbDctOutputs, const float16_t *dctCoefs, const uint32_t *filterPos, const uint32_t *filterLengths, const float16_t *filterCoefs, const float16_t *windowCoefs)

Initialization of the MFCC F16 instance structure.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script that can be used to generate the filter, dct and window arrays.

This function should be used only if you don't know the FFT sizes that you'll need at build time. The use of this function will prevent the linker from removing the FFT tables that are not needed and the library code size will be bigger than needed.

If you use NMSIS-DSP as a static library, and if you know the MFCC sizes that you need at build time, then it is better to use the initialization functions defined for each MFCC size.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `fftLen` – **[in]** fft length
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_F16 (32)`

Initialization of the MFCC F16 instance structure for 32 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script that can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_F16 (64)`

Initialization of the MFCC F16 instance structure for 64 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script that can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_F16 (128)`

Initialization of the MFCC F16 instance structure for 128 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script that can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_F16 (256)`

Initialization of the MFCC F16 instance structure for 256 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script that can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_F16 (512)`

Initialization of the MFCC F16 instance structure for 512 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script that can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths

- **filterCoefs** – **[in]** points to the array of filter coefficients
- **windowCoefs** – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_F16 (1024)`

Initialization of the MFCC F16 instance structure for 1024 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script that can be used to generate the filter, dct and window arrays.

Parameters

- **S** – **[out]** points to the mfcc instance structure
- **nbMelFilters** – **[in]** number of Mel filters
- **nbDctOutputs** – **[in]** number of Dct outputs
- **dctCoefs** – **[in]** points to an array of DCT coefficients
- **filterPos** – **[in]** points of the array of filter positions
- **filterLengths** – **[in]** points to the array of filter lengths
- **filterCoefs** – **[in]** points to the array of filter coefficients
- **windowCoefs** – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_F16 (2048)`

Initialization of the MFCC F16 instance structure for 2048 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script that can be used to generate the filter, dct and window arrays.

Parameters

- **S** – **[out]** points to the mfcc instance structure
- **nbMelFilters** – **[in]** number of Mel filters
- **nbDctOutputs** – **[in]** number of Dct outputs

- **dctCoefs** – **[in]** points to an array of DCT coefficients
- **filterPos** – **[in]** points of the array of filter positions
- **filterLengths** – **[in]** points to the array of filter lengths
- **filterCoefs** – **[in]** points to the array of filter coefficients
- **windowCoefs** – **[in]** points to the array of window coefficients

Returns error status

MFCC_INIT_F16 (4096)

Initialization of the MFCC F16 instance structure for 4096 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script that can be used to generate the filter, dct and window arrays.

Parameters

- **S** – **[out]** points to the mfcc instance structure
- **nbMelFilters** – **[in]** number of Mel filters
- **nbDctOutputs** – **[in]** number of Dct outputs
- **dctCoefs** – **[in]** points to an array of DCT coefficients
- **filterPos** – **[in]** points of the array of filter positions
- **filterLengths** – **[in]** points to the array of filter lengths
- **filterCoefs** – **[in]** points to the array of filter coefficients
- **windowCoefs** – **[in]** points to the array of window coefficients

Returns error status

MFCC Q15

riscv_status **riscv_mfcc_init_q15**(riscv_mfcc_instance_q15 *S, uint32_t fftLen, uint32_t nbMelFilters, uint32_t nbDctOutputs, const q15_t *dctCoefs, const uint32_t *filterPos, const uint32_t *filterLengths, const q15_t *filterCoefs, const q15_t *windowCoefs)

MFCC_INIT_Q15 (32)

MFCC_INIT_Q15 (64)

MFCC_INIT_Q15 (128)

MFCC_INIT_Q15 (256)

MFCC_INIT_Q15 (512)

MFCC_INIT_Q15 (1024)

MFCC_INIT_Q15 (2048)

MFCC_INIT_Q15 (4096)

riscv_status **riscv_mfcc_q15**(const riscv_mfcc_instance_q15 *S, q15_t *pSrc, q15_t *pDst, q31_t *pTmp)

MFCC_INIT_Q15(LEN)

group **MFCCQ15**

Defines

MFCC_INIT_Q15(LEN)

Functions

riscv_status **riscv_mfcc_init_q15**(riscv_mfcc_instance_q15 *S, uint32_t fftLen, uint32_t nbMelFilters, uint32_t nbDctOutputs, const q15_t *dctCoefs, const uint32_t *filterPos, const uint32_t *filterLengths, const q15_t *filterCoefs, const q15_t *windowCoefs)

Generic initialization of the MFCC Q15 instance structure.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

This function should be used only if you don't know the FFT sizes that you'll need at build time. The use of this function will prevent the linker from removing the FFT tables that are not needed and the library code size will be bigger than needed.

If you use NMSIS-DSP as a static library, and if you know the MFCC sizes that you need at build time, then it is better to use the initialization functions defined for each MFCC size.

Parameters

- **S** – **[out]** points to the mfcc instance structure

- **fftLen** – **[in]** fft length
- **nbMelFilters** – **[in]** number of Mel filters
- **nbDctOutputs** – **[in]** number of Dct outputs
- **dctCoefs** – **[in]** points to an array of DCT coefficients
- **filterPos** – **[in]** points of the array of filter positions
- **filterLengths** – **[in]** points to the array of filter lengths
- **filterCoefs** – **[in]** points to the array of filter coefficients
- **windowCoefs** – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q15 (32)`

Initialization of the MFCC Q15 instance structure for 32 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- **S** – **[out]** points to the mfcc instance structure
- **nbMelFilters** – **[in]** number of Mel filters
- **nbDctOutputs** – **[in]** number of Dct outputs
- **dctCoefs** – **[in]** points to an array of DCT coefficients
- **filterPos** – **[in]** points of the array of filter positions
- **filterLengths** – **[in]** points to the array of filter lengths
- **filterCoefs** – **[in]** points to the array of filter coefficients
- **windowCoefs** – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q15 (64)`

Initialization of the MFCC Q15 instance structure for 64 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q15 (128)`

Initialization of the MFCC Q15 instance structure for 128 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q15 (256)`

Initialization of the MFCC Q15 instance structure for 256 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q15 (512)`

Initialization of the MFCC Q15 instance structure for 512 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths

- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q15 (1024)`

Initialization of the MFCC Q15 instance structure for 1024 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q15 (2048)`

Initialization of the MFCC Q15 instance structure for 2048 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs

- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q15 (4096)`

Initialization of the MFCC Q15 instance structure for 4096 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

riscv_status **riscv_mfcc_q15**(const riscv_mfcc_instance_q15 *S, q15_t *pSrc, q15_t *pDst, q31_t *pTmp)

MFCC Q15.

The temporary buffer has a 2*fft length.

Description The number of input samples is the FFT length used when initializing the instance data structure.

The source buffer is modified by this function.

The function may saturate. If the FFT length is too big and the number of MEL filters too small then the fixed point computations may saturate.

Parameters

- `S` – **[in]** points to the mfcc instance structure

- **pSrc** – **[in]** points to the input samples in Q15
- **pDst** – **[out]** points to the output MFCC values in q8.7 format
- **pTmp** – **[inout]** points to a temporary buffer of complex

Returns none

MFCC Q31

riscv_status **riscv_mfcc_init_q31**(riscv_mfcc_instance_q31 *S, uint32_t fftLen, uint32_t nbMelFilters, uint32_t nbDctOutputs, const q31_t *dctCoefs, const uint32_t *filterPos, const uint32_t *filterLengths, const q31_t *filterCoefs, const q31_t *windowCoefs)

MFCC_INIT_Q31 (32)

MFCC_INIT_Q31 (64)

MFCC_INIT_Q31 (128)

MFCC_INIT_Q31 (256)

MFCC_INIT_Q31 (512)

MFCC_INIT_Q31 (1024)

MFCC_INIT_Q31 (2048)

MFCC_INIT_Q31 (4096)

riscv_status **riscv_mfcc_q31**(const riscv_mfcc_instance_q31 *S, q31_t *pSrc, q31_t *pDst, q31_t *pTmp)

MFCC_INIT_Q31(LEN)

group **MFCCQ31**

Defines

MFCC_INIT_Q31(LEN)

Functions

riscv_status **riscv_mfcc_init_q31**(riscv_mfcc_instance_q31 *S, uint32_t fftLen, uint32_t nbMelFilters, uint32_t nbDctOutputs, const q31_t *dctCoefs, const uint32_t *filterPos, const uint32_t *filterLengths, const q31_t *filterCoefs, const q31_t *windowCoefs)

Generic initialization of the MFCC Q31 instance structure.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

This function should be used only if you don't know the FFT sizes that you'll need at build time. The use of this function will prevent the linker from removing the FFT tables that are not needed and the library code size will be bigger than needed.

If you use NMSIS-DSP as a static library, and if you know the MFCC sizes that you need at build time, then it is better to use the initialization functions defined for each MFCC size.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `fftLen` – **[in]** fft length
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q31 (32)`

Initialization of the MFCC Q31 instance structure for 32 sample MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q31 (64)`

Initialization of the MFCC Q31 instance structure for 64 sample MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q31 (128)`

Initialization of the MFCC Q31 instance structure for 128 sample MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q31 (256)`

Initialization of the MFCC Q31 instance structure for 256 sample MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q31 (512)`

Initialization of the MFCC Q31 instance structure for 512 sample MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q31 (1024)`

Initialization of the MFCC Q31 instance structure for 1024 sample MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths

- **filterCoefs** – **[in]** points to the array of filter coefficients
- **windowCoefs** – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q31 (2048)`

Initialization of the MFCC Q31 instance structure for 2048 sample MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- **S** – **[out]** points to the mfcc instance structure
- **nbMelFilters** – **[in]** number of Mel filters
- **nbDctOutputs** – **[in]** number of Dct outputs
- **dctCoefs** – **[in]** points to an array of DCT coefficients
- **filterPos** – **[in]** points of the array of filter positions
- **filterLengths** – **[in]** points to the array of filter lengths
- **filterCoefs** – **[in]** points to the array of filter coefficients
- **windowCoefs** – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_Q31 (4096)`

Initialization of the MFCC Q31 instance structure for 4096 sample MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- **S** – **[out]** points to the mfcc instance structure
- **nbMelFilters** – **[in]** number of Mel filters
- **nbDctOutputs** – **[in]** number of Dct outputs

- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

riscv_status **riscv_mfcc_q31**(const riscv_mfcc_instance_q31 *S, q31_t *pSrc, q31_t *pDst, q31_t *pTmp)

MFCC Q31.

The temporary buffer has a 2*fft length.

Description The number of input samples is the FFT length used when initializing the instance data structure.

The source buffer is modified by this function.

The function may saturate. If the FFT length is too big and the number of MEL filters too small then the fixed point computations may saturate.

Parameters

- `S` – **[in]** points to the mfcc instance structure
- `pSrc` – **[in]** points to the input samples in Q31
- `pDst` – **[out]** points to the output MFCC values in q8.23 format
- `pTmp` – **[inout]** points to a temporary buffer of complex

Returns none

riscv_status **riscv_mfcc_init_f32**(riscv_mfcc_instance_f32 *S, uint32_t fftLen, uint32_t nbMelFilters, uint32_t nbDctOutputs, const float32_t *dctCoefs, const uint32_t *filterPos, const uint32_t *filterLengths, const float32_t *filterCoefs, const float32_t *windowCoefs)

MFCC_INIT_F32 (32)

MFCC_INIT_F32 (64)

MFCC_INIT_F32 (128)

MFCC_INIT_F32 (256)

MFCC_INIT_F32 (512)

MFCC_INIT_F32 (1024)

MFCC_INIT_F32 (2048)

MFCC_INIT_F32 (4096)

MFCC_INIT_F32(LEN)

group **MFCC**

MFCC Transform.

There are separate functions for floating-point, Q15, and Q31 data types.

Defines

MFCC_INIT_F32(LEN)

Functions

riscv_status **riscv_mfcc_init_f32**(riscv_mfcc_instance_f32 *S, uint32_t fftLen, uint32_t nbMelFilters, uint32_t nbDctOutputs, const float32_t *dctCoefs, const uint32_t *filterPos, const uint32_t *filterLengths, const float32_t *filterCoefs, const float32_t *windowCoefs)

Generic initialization of the MFCC F32 instance structure.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

This function should be used only if you don't know the FFT sizes that you'll need at build time. The use of this function will prevent the linker from removing the FFT tables that are not needed and the library code size will be bigger than needed.

If you use NMSIS-DSP as a static library, and if you know the MFCC sizes that you need at build time, then it is better to use the initialization functions defined for each MFCC size.

Parameters

- **S** – **[out]** points to the mfcc instance structure
- **fftLen** – **[in]** fft length
- **nbMelFilters** – **[in]** number of Mel filters
- **nbDctOutputs** – **[in]** number of Dct outputs
- **dctCoefs** – **[in]** points to an array of DCT coefficients
- **filterPos** – **[in]** points of the array of filter positions
- **filterLengths** – **[in]** points to the array of filter lengths

- **filterCoefs** – **[in]** points to the array of filter coefficients
- **windowCoefs** – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_F32 (32)`

Initialization of the MFCC F32 instance structure for 32 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- **S** – **[out]** points to the mfcc instance structure
- **nbMelFilters** – **[in]** number of Mel filters
- **nbDctOutputs** – **[in]** number of Dct outputs
- **dctCoefs** – **[in]** points to an array of DCT coefficients
- **filterPos** – **[in]** points of the array of filter positions
- **filterLengths** – **[in]** points to the array of filter lengths
- **filterCoefs** – **[in]** points to the array of filter coefficients
- **windowCoefs** – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_F32 (64)`

Initialization of the MFCC F32 instance structure for 64 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- **S** – **[out]** points to the mfcc instance structure
- **nbMelFilters** – **[in]** number of Mel filters
- **nbDctOutputs** – **[in]** number of Dct outputs

- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_F32 (128)`

Initialization of the MFCC F32 instance structure for 128 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_F32 (256)`

Initialization of the MFCC F32 instance structure for 256 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_F32 (512)`

Initialization of the MFCC F32 instance structure for 512 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_F32 (1024)`

Initialization of the MFCC F32 instance structure for 1024 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

`MFCC_INIT_F32 (2048)`

Initialization of the MFCC F32 instance structure for 2048 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- `S` – **[out]** points to the mfcc instance structure
- `nbMelFilters` – **[in]** number of Mel filters
- `nbDctOutputs` – **[in]** number of Dct outputs
- `dctCoefs` – **[in]** points to an array of DCT coefficients
- `filterPos` – **[in]** points of the array of filter positions
- `filterLengths` – **[in]** points to the array of filter lengths
- `filterCoefs` – **[in]** points to the array of filter coefficients
- `windowCoefs` – **[in]** points to the array of window coefficients

Returns error status

MFCC_INIT_F32 (4096)

Initialization of the MFCC F32 instance structure for 4096 samples MFCC.

window coefficients can describe (for instance) a Hamming window. The array has the same size as the FFT length.

Description The matrix of Mel filter coefficients is sparse. Most of the coefficients are zero. To avoid multiplying the spectrogram by those zeros, the filter is applied only to a given position in the spectrogram and on a given number of FFT bins (the filter length). It is the reason for the arrays filterPos and filterLengths.

The folder Scripts is containing a Python script which can be used to generate the filter, dct and window arrays.

Parameters

- **S** – **[out]** points to the mfcc instance structure
- **nbMelFilters** – **[in]** number of Mel filters
- **nbDctOutputs** – **[in]** number of Dct outputs
- **dctCoefs** – **[in]** points to an array of DCT coefficients
- **filterPos** – **[in]** points of the array of filter positions
- **filterLengths** – **[in]** points to the array of filter lengths
- **filterCoefs** – **[in]** points to the array of filter coefficients
- **windowCoefs** – **[in]** points to the array of window coefficients

Returns error status

Real FFT Functions

Real FFT F16 Functions

void **riscv_rfft_fast_f16**(const riscv_rfft_fast_instance_f16 *S, float16_t *p, float16_t *pOut, uint8_t ifftFlag)

riscv_status **riscv_rfft_fast_init_32_f16**(riscv_rfft_fast_instance_f16 *S)

riscv_status **riscv_rfft_fast_init_64_f16**(riscv_rfft_fast_instance_f16 *S)

riscv_status **riscv_rfft_fast_init_128_f16**(riscv_rfft_fast_instance_f16 *S)

riscv_status **riscv_rfft_fast_init_256_f16**(riscv_rfft_fast_instance_f16 *S)

riscv_status **riscv_rfft_fast_init_512_f16**(riscv_rfft_fast_instance_f16 *S)

riscv_status **riscv_rfft_fast_init_1024_f16**(riscv_rfft_fast_instance_f16 *S)

riscv_status **riscv_rfft_fast_init_2048_f16**(riscv_rfft_fast_instance_f16 *S)

riscv_status **riscv_rfft_fast_init_4096_f16**(riscv_rfft_fast_instance_f16 *S)

riscv_status **riscv_rfft_fast_init_f16**(riscv_rfft_fast_instance_f16 *S, uint16_t fftLen)

group **RealFFTF16**

Functions

void **riscv_rfft_fast_f16**(const riscv_rfft_fast_instance_f16 *S, float16_t *p, float16_t *pOut, uint8_t ifftFlag)

Processing function for the floating-point real FFT.

Parameters

- **S** – **[in]** points to an riscv_rfft_fast_instance_f16 structure
- **p** – **[in]** points to input buffer (Source buffer is modified by this function.)
- **pOut** – **[in]** points to output buffer
- **ifftFlag** – **[in]**
  - value = 0: RFFT
  - value = 1: RIFFT

Returns none

riscv_status **riscv_rfft_fast_init_32_f16**(riscv_rfft_fast_instance_f16 *S)

Initialization function for the 32pt floating-point real FFT.

Parameters **S** – **[inout]** points to an riscv_rfft_fast_instance_f16 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_64_f16**(riscv_rfft_fast_instance_f16 *S)

Initialization function for the 64pt floating-point real FFT.

Parameters **S** – **[inout]** points to an riscv_rfft_fast_instance_f16 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_128_f16**(riscv_rfft_fast_instance_f16 *S)

Initialization function for the 128pt floating-point real FFT.

Parameters **S** – **[inout]** points to an riscv_rfft_fast_instance_f16 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_256_f16**(riscv_rfft_fast_instance_f16 *S)

Initialization function for the 256pt floating-point real FFT.

Parameters **S** – **[inout]** points to an riscv_rfft_fast_instance_f16 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_512_f16**(riscv_rfft_fast_instance_f16 *S)

Initialization function for the 512pt floating-point real FFT.

Parameters S – **[inout]** points to an riscv_rfft_fast_instance_f16 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_1024_f16**(riscv_rfft_fast_instance_f16 *S)

Initialization function for the 1024pt floating-point real FFT.

Parameters S – **[inout]** points to an riscv_rfft_fast_instance_f16 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_2048_f16**(riscv_rfft_fast_instance_f16 *S)

Initialization function for the 2048pt floating-point real FFT.

Parameters S – **[inout]** points to an riscv_rfft_fast_instance_f16 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_4096_f16**(riscv_rfft_fast_instance_f16 *S)

Initialization function for the 4096pt floating-point real FFT.

Parameters S – **[inout]** points to an riscv_rfft_fast_instance_f16 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_f16**(riscv_rfft_fast_instance_f16 *S, uint16_t fftLen)

Generic initialization function for the floating-point real FFT.

Description The parameter `fftLen` specifies the length of RFFT/CIFFT process. Supported FFT Lengths are 32, 64, 128, 256, 512, 1024, 2048, 4096.

This Function also initializes Twiddle factor table pointer and Bit reversal table pointer.

This function should be used only if you don't know the FFT sizes that you'll need at build time. The use of this function will prevent the linker from removing the FFT tables that are not needed and the library code size will be bigger than needed.

If you use NMSIS-DSP as a static library, and if you know the FFT sizes that you need at build time, then it is better to use the initialization functions defined for each FFT size.

Parameters

- **S** – **[inout]** points to an riscv_rfft_fast_instance_f16 structure
- **fftLen** – **[in]** length of the Real Sequence

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLen` is not a supported length

Real FFT F64 Functions

void **riscv_rfft_fast_f64**(riscv_rfft_fast_instance_f64 *S, float64_t *p, float64_t *pOut, uint8_t ifftFlag)

riscv_status **riscv_rfft_fast_init_32_f64**(riscv_rfft_fast_instance_f64 *S)

riscv_status **riscv_rfft_fast_init_64_f64**(riscv_rfft_fast_instance_f64 *S)

riscv_status **riscv_rfft_fast_init_128_f64**(riscv_rfft_fast_instance_f64 *S)

riscv_status **riscv_rfft_fast_init_256_f64**(riscv_rfft_fast_instance_f64 *S)

riscv_status **riscv_rfft_fast_init_512_f64**(riscv_rfft_fast_instance_f64 *S)

riscv_status **riscv_rfft_fast_init_1024_f64**(riscv_rfft_fast_instance_f64 *S)

riscv_status **riscv_rfft_fast_init_2048_f64**(riscv_rfft_fast_instance_f64 *S)

riscv_status **riscv_rfft_fast_init_4096_f64**(riscv_rfft_fast_instance_f64 *S)

riscv_status **riscv_rfft_fast_init_f64**(riscv_rfft_fast_instance_f64 *S, uint16_t fftLen)

group **RealFFTF64**

Functions

void **riscv_rfft_fast_f64**(riscv_rfft_fast_instance_f64 *S, float64_t *p, float64_t *pOut, uint8_t ifftFlag)

Processing function for the Double Precision floating-point real FFT.

Parameters

- **S** – **[in]** points to an riscv_rfft_fast_instance_f64 structure
- **p** – **[in]** points to input buffer (Source buffer is modified by this function.)
- **pOut** – **[in]** points to output buffer
- **ifftFlag** – **[in]**
  - value = 0: RFFT
  - value = 1: RIFFT

Returns none

riscv_status **riscv_rfft_fast_init_32_f64**(riscv_rfft_fast_instance_f64 *S)

Initialization function for the 32pt double precision floating-point real FFT.

Parameters **S** – **[inout]** points to an riscv_rfft_fast_instance_f64 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_64_f64**(riscv_rfft_fast_instance_f64 *S)

Initialization function for the 64pt Double Precision floating-point real FFT.

Parameters S – **[inout]** points to an riscv_rfft_fast_instance_f64 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_128_f64**(riscv_rfft_fast_instance_f64 *S)

Initialization function for the 128pt Double Precision floating-point real FFT.

Parameters S – **[inout]** points to an riscv_rfft_fast_instance_f64 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_256_f64**(riscv_rfft_fast_instance_f64 *S)

Initialization function for the 256pt Double Precision floating-point real FFT.

Parameters S – **[inout]** points to an riscv_rfft_fast_instance_f64 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_512_f64**(riscv_rfft_fast_instance_f64 *S)

Initialization function for the 512pt Double Precision floating-point real FFT.

Parameters S – **[inout]** points to an riscv_rfft_fast_instance_f64 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_1024_f64**(riscv_rfft_fast_instance_f64 *S)

Initialization function for the 1024pt Double Precision floating-point real FFT.

Parameters S – **[inout]** points to an riscv_rfft_fast_instance_f64 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_2048_f64**(riscv_rfft_fast_instance_f64 *S)

Initialization function for the 2048pt Double Precision floating-point real FFT.

Parameters S – **[inout]** points to an riscv_rfft_fast_instance_f64 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_4096_f64**(riscv_rfft_fast_instance_f64 *S)

Initialization function for the 4096pt Double Precision floating-point real FFT.

Parameters S – **[inout]** points to an riscv_rfft_fast_instance_f64 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_f64**(riscv_rfft_fast_instance_f64 *S, uint16_t fftLen)

Generic initialization function for the Double Precision floating-point real FFT.

Description The parameter `fftLen` specifies the length of RFFT/CIFFT process. Supported FFT Lengths are 32, 64, 128, 256, 512, 1024, 2048, 4096.

This Function also initializes Twiddle factor table pointer and Bit reversal table pointer.

This function should be used only if you don't know the FFT sizes that you'll need at build time. The use of this function will prevent the linker from removing the FFT tables that are not needed and the library code size will be bigger than needed.

If you use NMSIS-DSP as a library, and if you know the FFT sizes that you need at build time, then it is better to use the initialization functions defined for each FFT size.

Parameters

- **S** – **[inout]** points to an riscv_rfft_fast_instance_f64 structure
- **fftLen** – **[in]** length of the Real Sequence

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLen` is not a supported length

Real FFT Q15 Functions

RFFTINIT_Q15 (8192, 4096, 1)

RFFTINIT_Q15 (4096, 2048, 2)

RFFTINIT_Q15 (2048, 1024, 4)

RFFTINIT_Q15 (1024, 512, 8)

RFFTINIT_Q15 (512, 256, 16)

RFFTINIT_Q15 (256, 128, 32)

RFFTINIT_Q15 (128, 64, 64)

RFFTINIT_Q15 (64, 32, 128)

RFFTINIT_Q15 (32, 16, 256)

riscv_status **riscv_rfft_init_q15**(riscv_rfft_instance_q15 *S, uint32_t fftLenReal, uint32_t ifftFlagR, uint32_t bitReverseFlag)

RFFTINIT_Q15(LEN, CFFTLEN, TWIDMOD)

group **RealFFTQ15**

Defines

RFFTINIT_Q15(LEN, CFFTLEN, TWIDMOD)

Functions

RFFTINIT_Q15 (8192, 4096, 1)

Initialization function for the 8192 pt Q15 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- **S** – **[inout]** points to an instance of the Q15 RFFT/RIFFT structure
- **ifftFlagR** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

RFFTINIT_Q15 (4096, 2048, 2)

Initialization function for the 4096 pt Q15 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- **S** – **[inout]** points to an instance of the Q15 RFFT/RIFFT structure
- **ifftFlagR** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

`RFFTINIT_Q15 (2048, 1024, 4)`

Initialization function for the 2048 pt Q15 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- **S** – **[inout]** points to an instance of the Q15 RFFT/RIFFT structure
- **ifftFlagR** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

`RFFTINIT_Q15 (1024, 512, 8)`

Initialization function for the 1024 pt Q15 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- **`S`** – **[inout]** points to an instance of the Q15 RFFT/RIFFT structure
- **`ifftFlagR`** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **`bitReverseFlag`** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

`RFFTINIT_Q15 (512, 256, 16)`

Initialization function for the 512 pt Q15 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- **`S`** – **[inout]** points to an instance of the Q15 RFFT/RIFFT structure
- **`ifftFlagR`** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **`bitReverseFlag`** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

`RFFTINIT_Q15 (256, 128, 32)`

Initialization function for the 256 pt Q15 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- **`S`** – **[inout]** points to an instance of the Q15 RFFT/RIFFT structure
- **`ifftFlagR`** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **`bitReverseFlag`** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

`RFFTINIT_Q15 (128, 64, 64)`

Initialization function for the 128 pt Q15 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- **`S`** – **[inout]** points to an instance of the Q15 RFFT/RIFFT structure
- **`ifftFlagR`** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **`bitReverseFlag`** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output

- value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

`RFFTINIT_Q15 (64, 32, 128)`

Initialization function for the 64 pt Q15 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- **S** – **[inout]** points to an instance of the Q15 RFFT/RIFFT structure
- **ifftFlagR** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

`RFFTINIT_Q15 (32, 16, 256)`

Initialization function for the 32 pt Q15 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- **S** – **[inout]** points to an instance of the Q15 RFFT/RIFFT structure
- **ifftFlagR** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform

- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : fftLenReal is not a supported length

riscv_status **riscv_rfft_init_q15**(riscv_rfft_instance_q15 *S, uint32_t fftLenReal, uint32_t ifftFlagR, uint32_t bitReverseFlag)

Generic initialization function for the Q15 RFFT/RIFFT.

Details The parameter fftLenReal specifies length of RFFT/RIFFT Process. Supported FFT Lengths are 32, 64, 128, 256, 512, 1024, 2048, 4096, 8192.

The parameter ifftFlagR controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter bitReverseFlag controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

This function should be used only if you don't know the FFT sizes that you'll need at build time. The use of this function will prevent the linker from removing the FFT tables that are not needed and the library code size will be bigger than needed.

If you use NMSIS-DSP as a static library, and if you know the FFT sizes that you need at build time, then it is better to use the initialization functions defined for each FFT size.

Parameters

- **S** – **[inout]** points to an instance of the Q15 RFFT/RIFFT structure
- **fftLenReal** – **[in]** length of the FFT
- **ifftFlagR** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : fftLenReal is not a supported length

Real FFT Q31 Functions

RFFTINIT_Q31 (8192, 4096, 1)

RFFTINIT_Q31 (4096, 2048, 2)

RFFTINIT_Q31 (2048, 1024, 4)

RFFTINIT_Q31 (1024, 512, 8)

RFFTINIT_Q31 (512, 256, 16)

RFFTINIT_Q31 (256, 128, 32)

RFFTINIT_Q31 (128, 64, 64)

RFFTINIT_Q31 (64, 32, 128)

RFFTINIT_Q31 (32, 16, 256)

riscv_status **riscv_rfft_init_q31**(riscv_rfft_instance_q31 *S, uint32_t fftLenReal, uint32_t ifftFlagR, uint32_t bitReverseFlag)

void **riscv_rfft_q31**(const riscv_rfft_instance_q31 *S, q31_t *pSrc, q31_t *pDst)

RFFTINIT_Q31(LEN, CFFTLEN, TWIDMOD)

group **RealFFTQ31**

Defines

RFFTINIT_Q31(LEN, CFFTLEN, TWIDMOD)

Functions

RFFTINIT_Q31 (8192, 4096, 1)

Initialization function for the 8192 pt Q31 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- `S` – **[inout]** points to an instance of the Q31 RFFT/RIFFT structure
- `ifftFlagR` – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- `bitReverseFlag` – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

`RFFTINIT_Q31 (4096, 2048, 2)`

Initialization function for the 4096 pt Q31 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- `S` – **[inout]** points to an instance of the Q31 RFFT/RIFFT structure
- `ifftFlagR` – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- `bitReverseFlag` – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

`RFFTINIT_Q31 (2048, 1024, 4)`

Initialization function for the 2048 pt Q31 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- **S** – **[inout]** points to an instance of the Q31 RFFT/RIFFT structure
- **ifftFlagR** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

RFFTINIT_Q31 (1024, 512, 8)

Initialization function for the 1024 pt Q31 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- **S** – **[inout]** points to an instance of the Q31 RFFT/RIFFT structure
- **ifftFlagR** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

RFFTINIT_Q31 (512, 256, 16)

Initialization function for the 512 pt Q31 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- **S** – **[inout]** points to an instance of the Q31 RFFT/RIFFT structure
- **ifftFlagR** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

`RFFTINIT_Q31 (256, 128, 32)`

Initialization function for the 256 pt Q31 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- **S** – **[inout]** points to an instance of the Q31 RFFT/RIFFT structure
- **ifftFlagR** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

`RFFTINIT_Q31 (128, 64, 64)`

Initialization function for the 128 pt Q31 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- **S** – **[inout]** points to an instance of the Q31 RFFT/RIFFT structure
- **ifftFlagR** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

`RFFTINIT_Q31 (64, 32, 128)`

Initialization function for the 64 pt Q31 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- **S** – **[inout]** points to an instance of the Q31 RFFT/RIFFT structure
- **ifftFlagR** – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- **bitReverseFlag** – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

RFFTINIT_Q31 (32, 16, 256)

Initialization function for the 32 pt Q31 real FFT.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- `S` – **[inout]** points to an instance of the Q31 RFFT/RIFFT structure
- `ifftFlagR` – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- `bitReverseFlag` – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

riscv_status **riscv_rfft_init_q31**(riscv_rfft_instance_q31 *S, uint32_t fftLenReal, uint32_t ifftFlagR, uint32_t bitReverseFlag)

Generic initialization function for the Q31 RFFT/RIFFT.

Details The parameter `fftLenReal` specifies length of RFFT/RIFFT Process. Supported FFT Lengths are 32, 64, 128, 256, 512, 1024, 2048, 4096, 8192.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

This function should be used only if you don't know the FFT sizes that you'll need at build time. The use of this function will prevent the linker from removing the FFT tables that are not needed and the library code size will be bigger than needed.

If you use NMSIS-DSP as a static library, and if you know the FFT sizes that you need at build time, then it is better to use the initialization functions defined for each FFT size.

Parameters

- `S` – **[inout]** points to an instance of the Q31 RFFT/RIFFT structure
- `fftLenReal` – **[in]** length of the FFT
- `ifftFlagR` – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- `bitReverseFlag` – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

void **riscv_rfft_q31**(const riscv_rfft_instance_q31 *S, q31_t *pSrc, q31_t *pDst)

Processing function for the Q31 RFFT/RIFFT.

RFFT Size	Input Format	Output Format	Number of bits to upscale
32	1.31	6.26	5
64	1.31	7.25	6
128	1.31	8.24	7
256	1.31	9.23	8
512	1.31	10.22	9
1024	1.31	11.21	10
2048	1.31	12.20	11
4096	1.31	13.19	12
8192	1.31	14.18	13

Input an output formats Internally input is downscaled by 2 for every stage to avoid saturations inside CFFT/CIFFT process. Hence the output format is different for different RFFT sizes. The input and output formats for different RFFT sizes and number of bits to upscale are mentioned in the tables below for RFFT and RIFFT:

Input and Output formats for RFFT Q31

RIFFT Size	Input Format	Output Format	Number of bits to upscale
32	1.31	6.26	0
64	1.31	7.25	0
128	1.31	8.24	0
256	1.31	9.23	0
512	1.31	10.22	0
1024	1.31	11.21	0
2048	1.31	12.20	0
4096	1.31	13.19	0
8192	1.31	14.18	0

Input and Output formats for RIFFT Q31

If the input buffer is of length N (fftLenReal), the output buffer must have length 2N since it is containing the conjugate part. The input buffer is modified by this function.

For the RIFFT, the source buffer must have length N+2 since the Nyquist frequency value is needed but conjugate part is ignored. It is not using the packing trick of the float version.

Parameters

- `S` – **[in]** points to an instance of the Q31 RFFT/RIFFT structure
- `pSrc` – **[in]** points to input buffer (Source buffer is modified by this function)
- `pDst` – **[out]** points to output buffer

Returns none

Real FFT Tables

const float32_t **realCoefA**[8192]

const float32_t **realCoefB**[8192]

const q31_t **realCoefAQ31**[8192]

const q31_t **realCoefBQ31**[8192]

const q15_t __ALIGNED (4)

group `RealFFT_Table`

Functions

const q15_t __ALIGNED (4)

Weights Table.

Q15 table for reciprocal.

end of DCT4_IDCT4_Table group

Generation fixed-point realCoefAQ15 array in Q15 format:

n = 4096

Convert to fixed point Q15 format round(pATable[i] * pow(2, 15))

Generation of real_CoefB array:

n = 4096

Convert to fixed point Q15 format round(pBTable[i] * pow(2, 15))

Weights tables are generated using the formula :

C command to generate the table

where `N` is the Number of weights to be calculated and `c` is `pi/(2*N)`

Converted the output to q15 format by multiplying with 2^31 and saturated if required.

In the tables below the real and imaginary values are placed alternatively, hence the array length is `2*N`.

cosFactor tables are generated using the formula :

C command to generate the table

where `N` is the number of factors to generate and `c` is `pi/(2*N)`

Then converted to q15 format by multiplying with 2^31 and saturated if required.

Variables

const float32_t **realCoefA**[8192]

Generation of realCoefA array:

n = 4096

const float32_t **realCoefB**[8192]

Generation of realCoefB array:

n = 4096

const q31_t **realCoefAQ31**[8192]

Generation fixed-point realCoefAQ31 array in Q31 format:

n = 4096

Convert to fixed point Q31 format round(pATable[i] * pow(2, 31))

const q31_t **realCoefBQ31**[8192]

Generation of realCoefBQ31 array:

n = 4096

Convert to fixed point Q31 format round(pBTable[i] * pow(2, 31))

Real FFT F32 Functions

void **riscv_rfft_fast_f32**(const riscv_rfft_fast_instance_f32 *S, float32_t *p, float32_t *pOut, uint8_t ifftFlag)

riscv_status **riscv_rfft_fast_init_32_f32**(riscv_rfft_fast_instance_f32 *S)

riscv_status **riscv_rfft_fast_init_64_f32**(riscv_rfft_fast_instance_f32 *S)

riscv_status **riscv_rfft_fast_init_128_f32**(riscv_rfft_fast_instance_f32 *S)

riscv_status **riscv_rfft_fast_init_256_f32**(riscv_rfft_fast_instance_f32 *S)

riscv_status **riscv_rfft_fast_init_512_f32**(riscv_rfft_fast_instance_f32 *S)

riscv_status **riscv_rfft_fast_init_1024_f32**(riscv_rfft_fast_instance_f32 *S)

riscv_status **riscv_rfft_fast_init_2048_f32**(riscv_rfft_fast_instance_f32 *S)

riscv_status **riscv_rfft_fast_init_4096_f32**(riscv_rfft_fast_instance_f32 *S)

riscv_status **riscv_rfft_fast_init_f32**(riscv_rfft_fast_instance_f32 *S, uint16_t fftLen)

group **RealFFTF32**

Functions

void **riscv_rfft_fast_f32**(const riscv_rfft_fast_instance_f32 *S, float32_t *p, float32_t *pOut, uint8_t ifftFlag)

Processing function for the floating-point real FFT.

Parameters

- **S** – **[in]** points to an riscv_rfft_fast_instance_f32 structure
- **p** – **[in]** points to input buffer (Source buffer is modified by this function.)
- **pOut** – **[in]** points to output buffer
- **ifftFlag** – **[in]**
  - value = 0: RFFT
  - value = 1: RIFFT

Returns none

riscv_status **riscv_rfft_fast_init_32_f32**(riscv_rfft_fast_instance_f32 *S)

Initialization function for the 32pt floating-point real FFT.

Parameters **S** – **[inout]** points to an riscv_rfft_fast_instance_f32 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_64_f32**(riscv_rfft_fast_instance_f32 *S)

Initialization function for the 64pt floating-point real FFT.

Parameters **S** – **[inout]** points to an riscv_rfft_fast_instance_f32 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_128_f32**(riscv_rfft_fast_instance_f32 *S)

Initialization function for the 128pt floating-point real FFT.

Parameters **S** – **[inout]** points to an riscv_rfft_fast_instance_f32 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_256_f32**(riscv_rfft_fast_instance_f32 *S)

Initialization function for the 256pt floating-point real FFT.

Parameters **S** – **[inout]** points to an riscv_rfft_fast_instance_f32 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_512_f32**(riscv_rfft_fast_instance_f32 *S)

Initialization function for the 512pt floating-point real FFT.

Parameters **S** – **[inout]** points to an riscv_rfft_fast_instance_f32 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_1024_f32**(riscv_rfft_fast_instance_f32 *S)

Initialization function for the 1024pt floating-point real FFT.

Parameters **S** – **[inout]** points to an riscv_rfft_fast_instance_f32 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_2048_f32**(riscv_rfft_fast_instance_f32 *S)

Initialization function for the 2048pt floating-point real FFT.

Parameters **S** – **[inout]** points to an riscv_rfft_fast_instance_f32 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_4096_f32**(riscv_rfft_fast_instance_f32 *S)

Initialization function for the 4096pt floating-point real FFT.

Parameters S – **[inout]** points to an riscv_rfft_fast_instance_f32 structure

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : an error is detected

riscv_status **riscv_rfft_fast_init_f32**(riscv_rfft_fast_instance_f32 *S, uint16_t fftLen)

Generic initialization function for the floating-point real FFT.

Description The parameter `fftLen` specifies the length of RFFT/CIFFT process. Supported FFT Lengths are 32, 64, 128, 256, 512, 1024, 2048, 4096.

This Function also initializes Twiddle factor table pointer and Bit reversal table pointer.

This function should be used only if you don't know the FFT sizes that you'll need at build time. The use of this function will prevent the linker from removing the FFT tables that are not needed and the library code size will be bigger than needed.

If you use NMSIS-DSP as a static library, and if you know the FFT sizes that you need at build time, then it is better to use the initialization functions defined for each FFT size.

Parameters

- **S** – **[inout]** points to an riscv_rfft_fast_instance_f32 structure
- **fftLen** – **[in]** length of the Real Sequence

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLen` is not a supported length

Deprecated Real FFT Functions

void **riscv_rfft_f32**(const riscv_rfft_instance_f32 *S, float32_t *pSrc, float32_t *pDst)

riscv_status **riscv_rfft_init_f32**(riscv_rfft_instance_f32 *S, riscv_cfft_radix4_instance_f32 *S_CFFT, uint32_t fftLenReal, uint32_t ifftFlagR, uint32_t bitReverseFlag)

group **DeprecatedRealFFT**

Functions

void **riscv_rfft_f32**(const riscv_rfft_instance_f32 *S, float32_t *pSrc, float32_t *pDst)

Processing function for the floating-point RFFT/RIFFT. Source buffer is modified by this function.

Deprecated:

Do not use this function. It has been superceded by riscv_rfft_fast_f32 and will be removed in the future.

Parameters

- `S` – **[in]** points to an instance of the floating-point RFFT/RIFFT structure
- `pSrc` – **[in]** points to the input buffer
- `pDst` – **[out]** points to the output buffer

Returns none

riscv_status **`riscv_rfft_init_f32`**(riscv_rfft_instance_f32 *S, riscv_cfft_radix4_instance_f32 *S_CFFT, uint32_t fftLenReal, uint32_t ifftFlagR, uint32_t bitReverseFlag)

Initialization function for the floating-point RFFT/RIFFT.

Deprecated:

Do not use this function. It has been superceded by riscv_rfft_fast_init_f32 and will be removed in the future.

Description The parameter `fftLenReal`specifies length of RFFT/RIFFT Process. Supported FFT Lengths are 128, 512, 2048.

The parameter `ifftFlagR` controls whether a forward or inverse transform is computed. Set(=1) ifftFlagR to calculate RIFFT, otherwise RFFT is calculated.

The parameter `bitReverseFlag` controls whether output is in normal order or bit reversed order. Set(=1) bitReverseFlag for output to be in normal order otherwise output is in bit reversed order.

This function also initializes Twiddle factor table.

Parameters

- `S` – **[inout]** points to an instance of the floating-point RFFT/RIFFT structure
- `S_CFFT` – **[inout]** points to an instance of the floating-point CFFT/CIFFT structure
- `fftLenReal` – **[in]** length of the FFT.
- `ifftFlagR` – **[in]** flag that selects transform direction
  - value = 0: forward transform
  - value = 1: inverse transform
- `bitReverseFlag` – **[in]** flag that enables / disables bit reversal of output
  - value = 0: disables bit reversal of output
  - value = 1: enables bit reversal of output

Returns execution status

- RISCV_MATH_SUCCESS : Operation successful
- RISCV_MATH_ARGUMENT_ERROR : `fftLenReal` is not a supported length

void **`riscv_rfft_q15`**(const riscv_rfft_instance_q15 *S, q15_t *pSrc, q15_t *pDst) *group* **RealFFT**

The NMSIS DSP library includes specialized algorithms for computing the FFT of real data sequences. The FFT is defined over complex data but in many applications the input is real. Real FFT algorithms take advantage of the symmetry properties of the FFT and have a speed advantage over complex algorithms of the same length.

The Fast RFFT algorithm relays on the mixed radix CFFT that save processor usage.

The real length N forward FFT of a sequence is computed using the steps shown below.



The real sequence is initially treated as if it were complex to perform a CFFT. Later, a processing stage reshapes the data to obtain half of the frequency spectrum in complex format.

The input for the inverse RFFT should keep the same format as the output of the forward RFFT. A first processing stage pre-process the data to later perform an inverse CFFT.



The algorithms for floating-point, Q15, and Q31 data are slightly different and we describe each algorithm in turn.

Floating-point The main functions are riscv_rfft_fast_f32() and riscv_rfft_fast_init_f32(). The older functions riscv_rfft_f32() and riscv_rfft_init_f32() have been deprecated but are still documented. For f16, the functions are riscv_rfft_fast_f16() and riscv_rfft_fast_init_f16(). For f64, the functions are riscv_rfft_fast_f64() and riscv_rfft_fast_init_f64().

The FFT of a real N-point sequence has even symmetry in the frequency domain. The second half of the data equals the conjugate of the first half flipped in frequency. This conjugate part is not computed by the float RFFT. As consequence, the output of a N point real FFT should be a N//2 + 1 complex numbers so N + 2 floats.

It happens that the first complex of number of the RFFT output is actually all real. Its real part represents the DC offset. The value at Nyquist frequency is also real.

Those two complex numbers can be encoded with 2 floats rather than using two numbers with an imaginary part set to zero.

The implementation is using a trick so that the output buffer can be N float : the last real is packaged in the imaginary part of the first complex (since this imaginary part is not used and is zero).

The real FFT functions pack the frequency domain data in this fashion. The forward transform outputs the data in this form and the inverse transform expects input data in this form. The function always performs the needed bitreversal so that the input and output data is always in normal order. The functions support lengths of [32, 64, 128, …, 4096] samples.

Q15 and Q31 The real algorithms are defined in a similar manner and utilize N/2 complex transforms behind the scenes.

But warning, contrary to the float version, the fixed point implementation RFFT is also computing the conjugate part (except for MVE version) so the output buffer must be bigger. Also the fixed point RFFTs are not using any trick to pack the DC and Nyquist frequency in the same complex number. The RIFFT is not using the conjugate part but it is still using the Nyquist frequency value. The details are given in the documentation for the functions.

The complex transforms used internally include scaling to prevent fixed-point overflows. The overall scaling equals 1/(fftLen/2). Due to the use of complex transform internally, the source buffer is modified by the rfft.

A separate instance structure must be defined for each transform used but twiddle factor and bit reversal tables can be reused.

There is also an associated initialization function for each data type. The initialization function performs the following operations:

- Sets the values of the internal structure fields.
- Initializes twiddle factor table and bit reversal table pointers.
- Initializes the internal complex FFT data structure.

Use of the initialization function is optional **except for MVE versions where it is mandatory**. If you don't use the initialization functions, then the structures should be initialized with code similar to the one below: where `fftLenReal` is the length of the real transform; `fftLenBy2` length of the internal complex transform (fftLenReal/2). `ifftFlagR` Selects forward (=0) or inverse (=1) transform. `bitReverseFlagR` Selects bit reversed output (=0) or normal order output (=1). `twidCoefRModifier` stride modifier for the twiddle factor table. The value is based on the FFT length; `pTwiddleAReal`points to the A array of twiddle coefficients; `pTwiddleBReal`points to the B array of twiddle coefficients; `pCfft` points to the CFFT Instance structure. The CFFT structure must also be initialized.

Note that with MVE versions you can't initialize instance structures directly and **must use the initialization function**.

Functions

void **riscv_rfft_q15**(const riscv_rfft_instance_q15 *S, q15_t *pSrc, q15_t *pDst)

Processing function for the Q15 RFFT/RIFFT.

RFFT Size	Input Format	Output Format	Number of bits to upscale
32	1.15	6.10	5
64	1.15	7.9	6
128	1.15	8.8	7
256	1.15	9.7	8
512	1.15	10.6	9
1024	1.15	11.5	10
2048	1.15	12.4	11
4096	1.15	13.3	12
8192	1.15	14.2	13

Input an output formats Internally input is downscaled by 2 for every stage to avoid saturations inside CFFT/CIFFT process. Hence the output format is different for different RFFT sizes. The input and output formats for different RFFT sizes and number of bits to upscale are mentioned in the tables below for RFFT and RIFFT:

Input and Output formats for RFFT Q15

RIFFT Size	Input Format	Output Format	Number of bits to upscale
32	1.15	6.10	0
64	1.15	7.9	0
128	1.15	8.8	0
256	1.15	9.7	0
512	1.15	10.6	0
1024	1.15	11.5	0
2048	1.15	12.4	0
4096	1.15	13.3	0
8192	1.15	14.2	0

Input and Output formats for RIFFT Q15

If the input buffer is of length N (fftLenReal), the output buffer must have length 2N since it is containing the conjugate part. The input buffer is modified by this function.

For the RIFFT, the source buffer must have length N+2 since the Nyquist frequency value is needed but conjugate part is ignored. It is not using the packing trick of the float version.

Parameters

- **S** – **[in]** points to an instance of the Q15 RFFT/RIFFT structure
- **pSrc** – **[in]** points to input buffer (Source buffer is modified by this function.)
- **pDst** – **[out]** points to output buffer

Returns none

group **groupTransforms**

3.3.15 Window Functions

Flat-top window functions

Hft116d window function (116.8 dB)

void **riscv_hft116d_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_hft116d_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowHFT116D**

Functions

void **riscv_hft116d_f32**(float32_t *pDst, uint32_t blockSize)

Hft116d window generating function (f32).

Hft116d window (float).

Parameter	Value
Peak sidelobe level	116.8 dB
Normalized equivalent noise bandwidth	4.2186 bins
3 dB bandwidth	4.1579 bins
Flatness	-0.0028 dB
Recommended overlap	78.2 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_hft116d_f64**(float64_t *pDst, uint32_t blockSize)

Hft116d window generating function (f64).

Hft116d window (double).

Parameter	Value
Peak sidelobe level	116.8 dB
Normalized equivalent noise bandwidth	4.2186 bins
3 dB bandwidth	4.1579 bins
Flatness	-0.0028 dB
Recommended overlap	78.2 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Hft144d window function (144.1 dB)

void **riscv_hft144d_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_hft144d_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowHFT144D**

Functions

void **riscv_hft144d_f32**(float32_t *pDst, uint32_t blockSize)

Hft144d window generating function (f32).

Hft144d window (float).

Parameter	Value
Peak sidelobe level	144.1 dB
Normalized equivalent noise bandwidth	4.5386 bins
3 dB bandwidth	4.4697 bins
Flatness	0.0021 dB
Recommended overlap	79.9 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_hft144d_f64**(float64_t *pDst, uint32_t blockSize)

Hft144d window generating function (f64).

Hft144d window (double).

Parameter	Value
Peak sidelobe level	144.1 dB
Normalized equivalent noise bandwidth	4.5386 bins
3 dB bandwidth	4.4697 bins
Flatness	0.0021 dB
Recommended overlap	79.9 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Hft169d window function (169.5 dB)

void **riscv_hft169d_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_hft169d_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowHFT169D**

Functions

void **riscv_hft169d_f32**(float32_t *pDst, uint32_t blockSize)

Hft169d window generating function (f32).

Hft169d window (float).

Parameter	Value
Peak sidelobe level	169.5 dB
Normalized equivalent noise bandwidth	4.8347 bins
3 dB bandwidth	4.7588 bins
Flatness	0.0017 dB
Recommended overlap	81.2 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_hft169d_f64**(float64_t *pDst, uint32_t blockSize)

Hft169d window generating function (f64).

Hft169d window (double).

Parameter	Value
Peak sidelobe level	169.5 dB
Normalized equivalent noise bandwidth	4.8347 bins
3 dB bandwidth	4.7588 bins
Flatness	0.0017 dB
Recommended overlap	81.2 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Hft196d window function (196.2 dB)

void **riscv_hft196d_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_hft196d_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowHFT196D**

Functions

void **riscv_hft196d_f32**(float32_t *pDst, uint32_t blockSize)

Hft196d window generating function (f32).

Hft196d window (float).

Parameter	Value
Peak sidelobe level	196.2 dB
Normalized equivalent noise bandwidth	5.1134 bins
3 dB bandwidth	5.0308 bins
Flatness	0.0013 dB
Recommended overlap	82.3 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_hft196d_f64**(float64_t *pDst, uint32_t blockSize)

Hft196d window generating function (f64).

Hft196d window (double).

Parameter	Value
Peak sidelobe level	196.2 dB
Normalized equivalent noise bandwidth	5.1134 bins
3 dB bandwidth	5.0308 bins
Flatness	0.0013 dB
Recommended overlap	82.3 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Hft223d window function (223.0 dB)

void **riscv_hft223d_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_hft223d_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowHFT223D**

Functions

void **riscv_hft223d_f32**(float32_t *pDst, uint32_t blockSize)

Hft223d window generating function (f32).

Hft223d window (float).

Parameter	Value
Peak sidelobe level	223.0 dB
Normalized equivalent noise bandwidth	5.3888 bins
3 dB bandwidth	5.3000 bins
Flatness	-0.0011 dB
Recommended overlap	83.3 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_hft223d_f64**(float64_t *pDst, uint32_t blockSize)

Hft223d window generating function (f64).

Hft223d window (double).

Parameter	Value
Peak sidelobe level	223.0 dB
Normalized equivalent noise bandwidth	5.3888 bins
3 dB bandwidth	5.3000 bins
Flatness	0.0011 dB
Recommended overlap	83.3 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Hft248d window function (248.4 dB)

void **riscv_hft248d_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_hft248d_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowHFT248D**

Functions

void **riscv_hft248d_f32**(float32_t *pDst, uint32_t blockSize)

Hft248d window generating function (f32).

Hft248d window (float).

Parameter	Value
Peak sidelobe level	248.4 dB
Normalized equivalent noise bandwidth	5.6512 bins
3 dB bandwidth	5.5567 bins
Flatness	0.0009 dB
Recommended overlap	84.1 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_hft248d_f64**(float64_t *pDst, uint32_t blockSize)

Hft248d window generating function (f64).

Hft248d window (double).

Parameter	Value
Peak sidelobe level	248.4 dB
Normalized equivalent noise bandwidth	5.6512 bins
3 dB bandwidth	5.5567 bins
Flatness	0.0009 dB
Recommended overlap	84.1 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Hft90d window function (90.2 dB)

void **riscv_hft90d_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_hft90d_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowHFT90D**

Functions

void **riscv_hft90d_f32**(float32_t *pDst, uint32_t blockSize)

Hft90d window generating function (f32).

Hft90d window (float).

Parameter	Value
Peak sidelobe level	90.2 dB
Normalized equivalent noise bandwidth	3.8832 bins
3 dB bandwidth	3.8320 bins
Flatness	-0.0039 dB
Recommended overlap	76.0 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_hft90d_f64**(float64_t *pDst, uint32_t blockSize)

Hft90d window generating function (f64).

Hft90d window (double).

Parameter	Value
Peak sidelobe level	90.2 dB
Normalized equivalent noise bandwidth	3.8832 bins
3 dB bandwidth	3.8320 bins
Flatness	-0.0039 dB
Recommended overlap	76.0 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Hft95 window function (95.0 dB)

void **riscv_hft95_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_hft95_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowHFT95**

Functions

void **riscv_hft95_f32**(float32_t *pDst, uint32_t blockSize)

Hft95 window generating function (f32).

Hft95 window (float).

Parameter	Value
Peak sidelobe level	95.0 dB
Normalized equivalent noise bandwidth	3.8112 bins
3 dB bandwidth	3.7590 bins
Flatness	0.0044 dB
Recommended overlap	75.6 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_hft95_f64**(float64_t *pDst, uint32_t blockSize)

Hft95 window generating function (f64).

Hft95 window (double).

Parameter	Value
Peak sidelobe level	95.0 dB
Normalized equivalent noise bandwidth	3.8112 bins
3 dB bandwidth	3.7590 bins
Flatness	0.0044 dB
Recommended overlap	75.6 %

Parameters of the window

Included in NMSIS-DSP with authorization from professor Gerhard Heinzel.

Original article: Spectrum and spectral density estimation by the Discrete Fourier transform (DFT), including a comprehensive list of window functions and some new flat-top windows.

Authors: G. Heinzel, A. Rudiger and R. Schilling, Max-Planck-Institut fur Gravitationsphysik (Albert-Einstein-Institut) Teilinstitut Hannover

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

group **WindowFlat**

Use those windows when you need to estimate the amplitude of a tone.

If just just need to detect a tone or estimate the noise, you can use the regular windows.

Regular window functions

Bartlett window function (26.5 dB)

void **riscv_bartlett_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_bartlett_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowBARTLETT**

Functions

void **riscv_bartlett_f32**(float32_t *pDst, uint32_t blockSize)

Bartlett window generating function (f32).

Bartlett window (float).

Parameter	Value
Peak sidelobe level	26.5 dB
Normalized equivalent noise bandwidth	1.3333 bins
3 dB bandwidth	1.2736 bins
Flatness	-1.8242 dB
Recommended overlap	50.0 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_bartlett_f64**(float64_t *pDst, uint32_t blockSize)

Bartlett window generating function (f64).

Bartlett window (double).

Parameter	Value
Peak sidelobe level	26.5 dB
Normalized equivalent noise bandwidth	1.3333 bins
3 dB bandwidth	1.2736 bins
Flatness	-1.8242 dB
Recommended overlap	50.0 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Blackman Harris window function (92 dB)

void **riscv_blackman_harris_92db_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_blackman_harris_92db_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowBLACKMAN_HARRIS_92DB**

Functions

void **riscv_blackman_harris_92db_f32**(float32_t *pDst, uint32_t blockSize)

92 dB Blackman Harris window generating function (f32).

92 db blackman harris window (float).

Parameter	Value
Peak sidelobe level	92.0 dB
Normalized equivalent noise bandwidth	2.0044 bins
3 dB bandwidth	1.8962 bins
Flatness	-0.8256 dB
Recommended overlap	66.1 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_blackman_harris_92db_f64**(float64_t *pDst, uint32_t blockSize)

92 dB Blackman Harris window generating function (f64).

92 db blackman harris window (double).

Parameter	Value
Peak sidelobe level	92.0 dB
Normalized equivalent noise bandwidth	2.0044 bins
3 dB bandwidth	1.8962 bins
Flatness	-0.8256 dB
Recommended overlap	66.1 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Hamming window function (42.7 dB)

void **riscv_hamming_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_hamming_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowHAMMING**

Functions

void **riscv_hamming_f32**(float32_t *pDst, uint32_t blockSize)

Hamming window generating function (f32).

Hamming window (float).

Parameter	Value
Peak sidelobe level	42.7 dB
Normalized equivalent noise bandwidth	1.3628 bins
3 dB bandwidth	1.3008 bins
Flatness	-1.7514 dB
Recommended overlap	50 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_hamming_f64**(float64_t *pDst, uint32_t blockSize)

Hamming window generating function (f64).

Hamming window (double).

Parameter	Value
Peak sidelobe level	42.7 dB
Normalized equivalent noise bandwidth	1.3628 bins
3 dB bandwidth	1.3008 bins
Flatness	-1.7514 dB
Recommended overlap	50 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Hanning window function (31.5 dB)

void **riscv_hanning_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_hanning_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowHANNING**

Functions

void **riscv_hanning_f32**(float32_t *pDst, uint32_t blockSize)

Hanning window generating function (f32).

Hanning window (float).

Parameter	Value
Peak sidelobe level	31.5 dB
Normalized equivalent noise bandwidth	1.5 bins
3 dB bandwidth	1.4382 bins
Flatness	-1.4236 dB
Recommended overlap	50 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_hanning_f64**(float64_t *pDst, uint32_t blockSize)

Hanning window generating function (f64).

Hanning window (double).

Parameter	Value
Peak sidelobe level	31.5 dB
Normalized equivalent noise bandwidth	1.5 bins
3 dB bandwidth	1.4382 bins
Flatness	-1.4236 dB
Recommended overlap	50 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Nuttall3 window function (46.7 dB)

void **riscv_nuttall3_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_nuttall3_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowNUTTALL3**

Functions

void **riscv_nuttall3_f32**(float32_t *pDst, uint32_t blockSize)

Nuttall3 window generating function (f32).

Nuttall3 window (float).

Parameter	Value
Peak sidelobe level	46.7 dB
Normalized equivalent noise bandwidth	1.9444 bins
3 dB bandwidth	1.8496 bins
Flatness	-0.8630 dB
Recommended overlap	64.7 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_nuttall3_f64**(float64_t *pDst, uint32_t blockSize)

Nuttall3 window generating function (f64).

Nuttall3 window (double).

Parameter	Value
Peak sidelobe level	46.7 dB
Normalized equivalent noise bandwidth	1.9444 bins
3 dB bandwidth	1.8496 bins
Flatness	-0.863 dB
Recommended overlap	64.7 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Nuttall3a window function (64.2 dB)

void **riscv_nuttall3a_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_nuttall3a_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowNUTTALL3A**

Functions

void **riscv_nuttall3a_f32**(float32_t *pDst, uint32_t blockSize)

Nuttall3a window generating function (f32).

Nuttall3a window (float).

Parameter	Value
Peak sidelobe level	64.2 dB
Normalized equivalent noise bandwidth	1.7721 bins
3 dB bandwidth	1.6828 bins
Flatness	-1.0453 dB
Recommended overlap	61.2 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_nuttall3a_f64**(float64_t *pDst, uint32_t blockSize)

Nuttall3a window generating function (f64).

Nuttall3a window (double).

Parameter	Value
Peak sidelobe level	64.2 dB
Normalized equivalent noise bandwidth	1.7721 bins
3 dB bandwidth	1.6828 bins
Flatness	-1.0453 dB
Recommended overlap	61.2 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Nuttall3b window function (71.5 dB)

void **riscv_nuttall3b_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_nuttall3b_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowNUTTALL3B**

Functions

void **riscv_nuttall3b_f32**(float32_t *pDst, uint32_t blockSize)

Nuttall3b window generating function (f32).

Nuttall3b window (float).

Parameter	Value
Peak sidelobe level	71.5 dB
Normalized equivalent noise bandwidth	1.7037 bins
3 dB bandwidth	1.6162 bins
Flatness	-1.1352 dB
Recommended overlap	59.8 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_nuttall3b_f64**(float64_t *pDst, uint32_t blockSize)

Nuttall3b window generating function (f64).

Nuttall3b window (double).

Parameter	Value
Peak sidelobe level	71.5 dB
Normalized equivalent noise bandwidth	1.7037 bins
3 dB bandwidth	1.6162 bins
Flatness	-1.1352 dB
Recommended overlap	59.8 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Nuttall4 window function (60.9 dB)

void **riscv_nuttall4_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_nuttall4_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowNUTTALL4**

Functions

void **riscv_nuttall4_f32**(float32_t *pDst, uint32_t blockSize)

Nuttall4 window generating function (f32).

Nuttall4 window (float).

Parameter	Value
Peak sidelobe level	60.9 dB
Normalized equivalent noise bandwidth	2.31 bins
3 dB bandwidth	2.1884 bins
Flatness	-0.6184 dB
Recommended overlap	70.5 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window

- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_nuttall4_f64**(float64_t *pDst, uint32_t blockSize)

Nuttall4 window generating function (f64).

Nuttall4 window (double).

Parameter	Value
Peak sidelobe level	60.9 dB
Normalized equivalent noise bandwidth	2.31 bins
3 dB bandwidth	2.1884 bins
Flatness	-0.6184 dB
Recommended overlap	70.5 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Nuttall4a window function (82.6 dB)

void **riscv_nuttall4a_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_nuttall4a_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowNUTTALL4A**

Functions

void **riscv_nuttall4a_f32**(float32_t *pDst, uint32_t blockSize)

Nuttall4a window generating function (f32).

Nuttall4a window (float).

Parameter	Value
Peak sidelobe level	82.6 dB
Normalized equivalent noise bandwidth	2.1253 bins
3 dB bandwidth	2.0123 bins
Flatness	-0.7321 dB
Recommended overlap	68.0 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_nuttall4a_f64**(float64_t *pDst, uint32_t blockSize)

Nuttall4a window generating function (f64).

Nuttall4a window (double).

Parameter	Value
Peak sidelobe level	82.6 dB
Normalized equivalent noise bandwidth	2.1253 bins
3 dB bandwidth	2.0123 bins
Flatness	-0.7321 dB
Recommended overlap	68.0 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Nuttall4b window function (93.3 dB)

void **riscv_nuttall4b_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_nuttall4b_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowNUTTALL4B**

Functions

void **riscv_nuttall4b_f32**(float32_t *pDst, uint32_t blockSize)

Nuttall4b window generating function (f32).

Nuttall4b window (float).

Parameter	Value
Peak sidelobe level	93.3 dB
Normalized equivalent noise bandwidth	2.0212 bins
3 dB bandwidth	1.9122 bins
Flatness	-0.8118 dB
Recommended overlap	66.3 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_nuttall4b_f64**(float64_t *pDst, uint32_t blockSize)

Nuttall4b window generating function (f64).

Nuttall4b window (double).

Parameter	Value
Peak sidelobe level	93.3 dB
Normalized equivalent noise bandwidth	2.0212 bins
3 dB bandwidth	1.9122 bins
Flatness	-0.8118 dB
Recommended overlap	66.3 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Nuttall4c window function (98.1 dB)

void **riscv_nuttall4c_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_nuttall4c_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowNUTTALL4C**

Functions

void **riscv_nuttall4c_f32**(float32_t *pDst, uint32_t blockSize)

Nuttall4c window generating function (f32).

Nuttall4c window (float).

Parameter	Value
Peak sidelobe level	98.1 dB
Normalized equivalent noise bandwidth	1.9761 bins
3 dB bandwidth	1.8687 bins
Flatness	-0.8506 dB
Recommended overlap	65.6 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_nuttall4c_f64**(float64_t *pDst, uint32_t blockSize)

Nuttall4c window generating function (f64).

Nuttall4c window (double).

Parameter	Value
Peak sidelobe level	98.1 dB
Normalized equivalent noise bandwidth	1.9761 bins
3 dB bandwidth	1.8687 bins
Flatness	-0.8506 dB
Recommended overlap	65.6 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

Welch window function (21.3 dB)

void **riscv_welch_f32**(float32_t *pDst, uint32_t blockSize)

void **riscv_welch_f64**(float64_t *pDst, uint32_t blockSize)

group **WindowWELCH**

Functions

void **riscv_welch_f32**(float32_t *pDst, uint32_t blockSize)

Welch window generating function (f32).

Welch window (float).

Parameter	Value
Peak sidelobe level	21.3 dB
Normalized equivalent noise bandwidth	1.2 bins
3 dB bandwidth	1.1535 bins
Flatness	-2.2248 dB
Recommended overlap	29.3 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

void **riscv_welch_f64**(float64_t *pDst, uint32_t blockSize)

Welch window generating function (f64).

Welch window (double).

Parameter	Value
Peak sidelobe level	21.3 dB
Normalized equivalent noise bandwidth	1.2 bins
3 dB bandwidth	1.1535 bins
Flatness	-2.2248 dB
Recommended overlap	29.3 %

Parameters of the window

Parameters

- **pDst** – **[out]** points to the output generated window
- **blockSize** – **[in]** number of samples in the window

Returns none

group **WindowNormal**

Regular window functions that can be used for detecting tones or estimating the noise. If you need to estimate the amplitude of a tones, prefer a flat top window.

group **groupWindow**

3.3.16 Examples

Bayes Example

group **BayesExample**

Description:

Demonstrates the use of Bayesian classifier functions. It is complementing the tutorial about classical ML with CMSIS-DSP and python scikit-learn: https://developer.arm.com/solutions/machine-learning-on-arm/developer-material/how-to-guides/implement-classical-ml-with-arm-cmsis-dsp-libraries

Class Marks Example

group **ClassMarks**

Refer riscv_class_marks_example_f32.c

Description:

Demonstrates the use the Maximum, Minimum, Mean, Standard Deviation, Variance and Matrix functions to calculate statistical values of marks obtained in a class.

Variables Description:

- `testMarks_f32` points to the marks scored by 20 students in 4 subjects
- `max_marks` Maximum of all marks
- `min_marks` Minimum of all marks
- `mean` Mean of all marks
- `var` Variance of the marks
- `std` Standard deviation of the marks
- `numStudents` Total number of students in the class

NMSIS DSP Software Library Functions Used:

- riscv_mat_init_f32()
- riscv_mat_mult_f32()
- riscv_max_f32()
- riscv_min_f32()
- riscv_mean_f32()
- riscv_std_f32()
- riscv_var_f32()

Note: This example also demonstrates the usage of static initialization.

Convolution Example

group **ConvolutionExample**

Refer riscv_convolution_example_f32.c

Description:

Demonstrates the convolution theorem with the use of the Complex FFT, Complex-by-Complex Multiplication, and Support Functions.

Algorithm:

The convolution theorem states that convolution in the time domain corresponds to multiplication in the frequency domain. Therefore, the Fourier transform of the convoution of two signals is equal to the product of their individual Fourier transforms. The Fourier transform of a signal can be evaluated efficiently using the Fast Fourier Transform (FFT).

Two input signals, `a[n]` and `b[n]`, with lengths `n1` and `n2` respectively, are zero padded so that their lengths become `N`, which is greater than or equal to `(n1+n2-1)` and is a power of 4 as FFT implementation is radix-4. The convolution of `a[n]` and `b[n]` is obtained by taking the FFT of the input signals, multiplying the Fourier transforms of the two signals, and taking the inverse FFT of the multiplied result.

This is denoted by the following equations: where `A[k]` and `B[k]` are the N-point FFTs of the signals `a[n]` and `b[n]` respectively. The length of the convolved signal is `(n1+n2-1)`.

Block Diagram:



Variables Description:

- `testInputA_f32` points to the first input sequence
- `srcALen` length of the first input sequence
- `testInputB_f32` points to the second input sequence
- `srcBLen` length of the second input sequence
- `outLen` length of convolution output sequence, `(srcALen + srcBLen - 1)`
- `AxB` points to the output array where the product of individual FFTs of inputs is stored.

NMSIS DSP Software Library Functions Used:

- riscv_fill_f32()
- riscv_copy_f32()

- riscv_cfft_radix4_init_f32()
- riscv_cfft_radix4_f32()
- riscv_cmplx_mult_cmplx_f32()

Dot Product Example

group **DotproductExample**

Refer riscv_dotproduct_example_f32.c

Description:

Demonstrates the use of the Multiply and Add functions to perform the dot product. The dot product of two vectors is obtained by multiplying corresponding elements and summing the products.

Algorithm:

The two input vectors `A` and `B` with length `n`, are multiplied element-by-element and then added to obtain dot product.

This is denoted by the following equation:

Block Diagram:



Variables Description:

- `srcA_buf_f32` points to first input vector
- `srcB_buf_f32` points to second input vector
- `testOutput` stores dot product of the two input vectors.

NMSIS DSP Software Library Functions Used:

- riscv_mult_f32()
- riscv_add_f32()

Frequency Bin Example

group **FrequencyBin**

Refer riscv_fft_bin_example_f32.c

Description

Demonstrates the calculation of the maximum energy bin in the frequency domain of the input signal with the use of Complex FFT, Complex Magnitude, and Maximum functions.

Algorithm:

The input test signal contains a 10 kHz signal with uniformly distributed white noise. Calculating the FFT of the input signal will give us the maximum energy of the bin corresponding to the input frequency of 10 kHz.



Block Diagram:

The figure below shows the time domain signal of 10 kHz signal with uniformly distributed white noise, and the next figure shows the input in the frequency domain. The bin with maximum energy corresponds to 10 kHz signal.



Variables Description:

- `testInput_f32_10khz` points to the input data
- `testOutput` points to the output data
- `fftSize` length of FFT
- `ifftFlag` flag for the selection of CFFT/CIFFT
- `doBitReverse` Flag for selection of normal order or bit reversed order
- `refIndex` reference index value at which maximum energy of bin ocuurs
- `testIndex` calculated index value at which maximum energy of bin ocuurs

NMSIS DSP Software Library Functions Used:

- riscv_cfft_f32()

- riscv_cmplx_mag_f32()
- riscv_max_f32()

FIR Lowpass Filter Example

group **FIRLPF**

Refer riscv_fir_example_f32.c

Description:

Removes high frequency signal components from the input using an FIR lowpass filter. The example demonstrates how to configure an FIR filter and then pass data through it in a block-by-block fashion.

Algorithm:

The input signal is a sum of two sine waves: 1 kHz and 15 kHz. This is processed by an FIR lowpass filter with cutoff frequency 6 kHz. The lowpass filter eliminates the 15 kHz signal leaving only the 1 kHz sine wave at the output.

The lowpass filter was designed using MATLAB with a sample rate of 48 kHz and a length of 29 points. The MATLAB code to generate the filter coefficients is shown below: The first argument is the "order" of the filter and is always one less than the desired length. The second argument is the normalized cutoff frequency. This is in the range 0 (DC) to 1.0 (Nyquist). A 6 kHz cutoff with a Nyquist frequency of 24 kHz lies at a normalized frequency of 6/24 = 0.25. The NMSIS FIR filter function requires the coefficients to be in time reversed order. The resulting filter coefficients and are shown below. Note that the filter is symmetric (a property of linear phase FIR filters) and the point of symmetry is sample 14. Thus the filter will have a delay of 14 samples for all frequencies.



The frequency response of the filter is shown next. The passband gain of the filter is 1.0 and it reaches 0.5 at the cutoff frequency 6 kHz.



The input signal is shown below. The left hand side shows the signal in the time domain while the right hand side is a frequency domain representation. The two sine wave components can be clearly seen.



The output of the filter is shown below. The 15 kHz component has been eliminated.



Variables Description:

- `testInput_f32_1kHz_15kHz` points to the input data

- `refOutput` points to the reference output data
- `testOutput` points to the test output data
- `firStateF32` points to state buffer
- `firCoeffs32` points to coefficient buffer
- `blockSize` number of samples processed at a time
- `numBlocks` number of frames

NMSIS DSP Software Library Functions Used:

- riscv_fir_init_f32()
- riscv_fir_f32()

Graphic Audio Equalizer Example

group **GEQ5Band**

Refer riscv_graphic_equalizer_example_q31.c

Description:

This example demonstrates how a 5-band graphic equalizer can be constructed using the Biquad cascade functions. A graphic equalizer is used in audio applications to vary the tonal quality of the audio.

Block Diagram:

The design is based on a cascade of 5 filter sections.

Each filter section is 4th order and consists of a cascade of two Biquads. Each filter has a nominal gain of 0 dB (1.0 in linear units) and boosts or cuts signals within a specific frequency range. The edge frequencies between the 5 bands are 100, 500, 2000, and 6000 Hz. Each band has an adjustable boost or cut in the range of +/- 9 dB. For example, the band that extends from 500 to 2000 Hz has the response shown below:





With 1 dB steps, each filter has a total of 19 different settings. The filter coefficients for all possible 19 settings were precomputed in MATLAB and stored in a table. With 5 different tables, there are a total of 5 x 19 = 95 different 4th order filters. All 95 responses are shown below:



Each 4th order filter has 10 coefficents for a grand total of 950 different filter coefficients that must be tabulated. The input and output data is in Q31 format. For better noise performance, the two low frequency bands are implemented using the high precision 32x64-bit Biquad filters. The remaining 3 high frequency bands use standard 32x32-bit Biquad filters. The input signal used in the example is a logarithmic chirp.



The array `bandGains` specifies the gain in dB to apply in each band. For example, if `bandGains={0, -3, 6, 4, -6};` then the output signal will be:



Variables Description:

- `testInput_f32` points to the input data
- `testRefOutput_f32` points to the reference output data
- `testOutput` points to the test output data
- `inputQ31` temporary input buffer
- `outputQ31` temporary output buffer
- `biquadStateBand1Q31` points to state buffer for band1
- `biquadStateBand2Q31` points to state buffer for band2
- `biquadStateBand3Q31` points to state buffer for band3
- `biquadStateBand4Q31` points to state buffer for band4
- `biquadStateBand5Q31` points to state buffer for band5
- `coeffTable` points to coefficient buffer for all bands
- `gainDB` gain buffer which has gains applied for all the bands

NMSIS DSP Software Library Functions Used:

- riscv_biquad_cas_df1_32x64_init_q31()
- riscv_biquad_cas_df1_32x64_q31()
- riscv_biquad_cascade_df1_init_q31()
- riscv_biquad_cascade_df1_q31()
- riscv_scale_q31()
- riscv_scale_f32()
- riscv_float_to_q31()
- riscv_q31_to_float()

Note: The output chirp signal follows the gain or boost of each band.

Linear Interpolate Example

group **`LinearInterpExample`**

NMSIS DSP Software Library Linear Interpolate Example

Description This example demonstrates usage of linear interpolate modules and fast math modules. Method 1 uses fast math sine function to calculate sine values using cubic interpolation and method 2 uses linear interpolation function and results are compared to reference output. Example shows linear interpolation function can be used to get higher precision compared to fast math sin calculation.

Refer riscv_linear_interp_example_f32.c

Block Diagram:



Variables Description:

- `testInputSin_f32` points to the input values for sine calculation
- `testRefSinOutput32_f32` points to the reference values caculated from sin() matlab function
- `testOutput` points to output buffer calculation from cubic interpolation
- `testLinIntOutput` points to output buffer calculation from linear interpolation
- `snr1` Signal to noise ratio for reference and cubic interpolation output
- `snr2` Signal to noise ratio for reference and linear interpolation output

NMSIS DSP Software Library Functions Used:

- riscv_sin_f32()
- riscv_linear_interp_f32()

Matrix Example

group **`MatrixExample`**

Refer riscv_matrix_example_f32.c

Description:

Demonstrates the use of Matrix Transpose, Matrix Muliplication, and Matrix Inverse functions to apply least squares fitting to input data. Least squares fitting is the procedure for finding the best-fitting curve that minimizes the sum of the squares of the offsets (least square error) from a given set of data.

Algorithm:

The linear combination of parameters considered is as follows:

`A * X = B`, where `X` is the unknown value and can be estimated from `A` & `B`.

The least squares estimate `X` is given by the following equation:

`X = Inverse(A * A) * A * B`

Block Diagram:



Variables Description:

- `A_f32` input matrix in the linear combination equation
- `B_f32` output matrix in the linear combination equation
- `X_f32` unknown matrix estimated using `A_f32` & `B_f32` matrices

NMSIS DSP Software Library Functions Used:

- riscv_mat_init_f32()
- riscv_mat_trans_f32()
- riscv_mat_mult_f32()
- riscv_mat_inverse_f32()

Signal Convergence Example

group `SignalConvergence`

Refer riscv_signal_converge_example_f32.c

Description:

Demonstrates the ability of an adaptive filter to "learn" the transfer function of a FIR lowpass filter using the Normalized LMS Filter, Finite Impulse Response (FIR) Filter, and Basic Math Functions.

Algorithm:

The figure below illustrates the signal flow in this example. Uniformly distributed white noise is passed through an FIR lowpass filter. The output of the FIR filter serves as the reference input of the adaptive filter (normalized LMS filter). The white noise is input to the adaptive filter. The adaptive filter learns the transfer function of the FIR filter. The filter outputs two signals: (1) the output of the internal adaptive FIR filter, and (2) the error signal which is the difference between the adaptive filter and the reference output of the FIR filter. Over time as the adaptive filter learns the transfer function of the FIR filter, the first output approaches the reference output of the FIR filter, and the error signal approaches zero.

The adaptive filter converges properly even if the input signal has a large dynamic range (i.e., varies from small to large values). The coefficients of the adaptive filter are initially zero, and then converge over 1536 samples. The internal function test_signal_converge() implements the stopping condition. The function checks if all of the values of the error signal have a magnitude below a threshold DELTA.

Block Diagram:



Variables Description:

- `testInput_f32` points to the input data
- `firStateF32` points to FIR state buffer
- `lmsStateF32` points to Normalised Least mean square FIR filter state buffer
- `FIRCoeff_f32` points to coefficient buffer
- `lmsNormCoeff_f32` points to Normalised Least mean square FIR filter coefficient buffer
- `wire1`, wir2, wire3 temporary buffers
- `errOutput`, err_signal temporary error buffers

NMSIS DSP Software Library Functions Used:

- riscv_lms_norm_init_f32()
- riscv_fir_init_f32()
- riscv_fir_f32()
- riscv_lms_norm_f32()
- riscv_scale_f32()
- riscv_abs_f32()
- riscv_sub_f32()
- riscv_min_f32()
- riscv_copy_f32()

SineCosine Example

group `SinCosExample`

Refer riscv_sin_cos_example_f32.c

Description:

Demonstrates the Pythagorean trignometric identity with the use of Cosine, Sine, Vector Multiplication, and Vector Addition functions.

Algorithm:

Mathematically, the Pythagorean trignometric identity is defined by the following equation: where `x` is the angle in radians.

Block Diagram:



Variables Description:

- `testInput_f32` array of input angle in radians
- `testOutput` stores sum of the squares of sine and cosine values of input angle

NMSIS DSP Software Library Functions Used:

- riscv_cos_f32()
- riscv_sin_f32()
- riscv_mult_f32()
- riscv_add_f32()

SVM Example

group **`SVMExample`**

Description:

Demonstrates the use of SVM functions. It is complementing the tutorial about classical ML with CMSIS-DSP and python scikit-learn: https://developer.arm.com/solutions/machine-learning-on-arm/developer-material/how-to-guides/implement-classical-ml-with-arm-cmsis-dsp-libraries

Variance Example

group **`VarianceExample`**

Refer riscv_variance_example_f32.c

Description:

Demonstrates the use of Basic Math and Support Functions to calculate the variance of an input sequence with N samples. Uniformly distributed white noise is taken as input.

Algorithm:

The variance of a sequence is the mean of the squared deviation of the sequence from its mean.

This is denoted by the following equation: where, `x[n]` is the input sequence, `N` is the number of input samples, and `x'` is the mean value of the input sequence, `x[n]`.

The mean value `x'` is defined as:

Block Diagram:



Variables Description:

- `testInput_f32` points to the input data
- `wire1`, `wir2`, `wire3` temporary buffers
- `blockSize` number of samples processed at a time
- `refVarianceOut` reference variance value

NMSIS DSP Software Library Functions Used:

- riscv_dot_prod_f32()
- riscv_mult_f32()
- riscv_sub_f32()
- riscv_fill_f32()
- riscv_copy_f32()

group **`groupExamples`**

3.4 Changelog

3.4.1 V1.2.0

Note:

- This 1.2.0 version will no longer support old gcc 10 verison, and it now only support Nuclei Toolchain 2023.10(gcc13 and clang17) or later. The major changes that can be felt are as follows:
- The prefix of toolchain has changed from `riscv-nuclei-elf-` to `riscv64-unknown-elf-`
- The `-march` option has changed a lot, for example:
  - `b` extension changed to `_zba_zbb_zbc_zbs` extension,
  - `p` extension changed to `_xxldsp` or `_xxldspn1x` or `_xxldspn2x` or `_xxldspn3x` extensions which means stardard DSP extension, Nuclei N1, N2, N3 DSP extensions
  - `v` extension changed to `v` or `_zve32f` or `_zve64f` extensions according to the riscv cpu isa used

  These extensions need be combined in a certain order to get a correct arch name to match the prebuilt library name, please be cautious
- The name of libraries changed due to `-march` in gcc13 updated, for example, the library named `libnmsis_dsp_rv32imacb.a` is now named `libnmsis_dsp_rv32imac_zba_zbb_zbc_zbs.a` since `b` extension changed to `_zba_zbb_zbc_zbs`

This is release `1.2.0` version of NMSIS-DSP library.

- Defined `NUCLEI_DSP_DEFAULT`, `NUCLEI_DSP_N1`, `NUCLEI_DSP_N2`, `NUCLEI_DSP_N3` in `riscv_math_types.h` according to gcc options. This means that if compile with `--march=rv32imafc_xxldspn1x`, the `NUCLEI_DSP_N1` will defined, if compile with `--march=rv32imafc_xxldspn2x`, the `NUCLEI_DSP_N1` and `NUCLEI_DSP_N2` will defined, and so on
- Optimize some functions with DSP N1/N2/N3 (such as FilteringFunctions, TransformFunctions, ComplexMathFunctions)
- RVV intrinsic APIs is update to v0.12.0
- Add f16 support(include f16 rvv extension support)
- Fix the use of expd80 instruction(Nuclei default dsp instruction)
- Fix some testcases bugs(such as MatrixFunctions, TransformFunctions)

3.4.2 V1.1.1

This is release `1.1.1` version of NMSIS-DSP library.

- Sync changes from CMSIS DSP commit 1d9e38a, version after v1.14.4
- Optimized more for RVP/RVV
- Add support for RV32 Vector
- Some bugfix(riscv_mat_inverse_f32.c rvv fix, riscv_offset_q15.c p fix, riscv_fir_q15.c rvv fix etc.)

3.4.3 V1.1.0

This is release `1.1.0` version of NMSIS-DSP library.

- Sync changes from CMSIS 5.9.0 release
- Optimized more for RVP/RVV
- Add experimental support for RV32 Vector

3.4.4 V1.0.3

This is release `1.0.3` version of NMSIS-DSP library.

- Update build system for NMSIS-DSP library
- Rename `RISCV_VECTOR` to `RISCV_MATH_VECTOR` in header file and source code
- Using new python script to generate NMSIS-DSP library
- Fix riscv_float_to_q31 function for rv64imafcv target
- Change vfredsum to vfredusum when using vector intrinsic function due to vector spec 1.0
- Support Nuclei RISC-V GCC 10.2

3.4.5 V1.0.2

This is release `1.0.2` version of NMSIS-DSP library.

- Sync up to CMSIS DSP library 1.9.0
- Adding initial support for RISC-V vector extension support
- **Caution**: `riscv_math.h` is separated into several header files. Extra `PrivateInclude` folder is included as header folder.

3.4.6 V1.0.1

This is release `V1.0.1` version of NMSIS-DSP library.

- Both Nuclei RISC-V 32 and 64 bit cores are supported now.
- Libraries are optimized for RISC-V 32 and 64 bit DSP instructions.
- The NN examples are now using Nuclei SDK as running environment.

3.4.7 V1.0.0

This is the first version of NMSIS-DSP library.

We adapt the CMSIS-DSP v1.6.0 library to use RISCV DSP instructions, all the API names now are renamed from `arm_xxx` to `riscv_xxx`.

CHAPTER

FOUR

NMSIS NN

4.1 Overview

4.1.1 Introduction

This user manual describes the NMSIS NN software library, a collection of efficient neural network kernels developed to maximize the performance and minimize the memory footprint of neural networks on Nuclei N/NX Class Processors cores.

The library is divided into a number of functions each covering a specific category:

- Activation Functions
- BasicMath Functions
- Concatenation Functions
- Convolution Functions
- Fully-Connected Functions
- LSTM Functions
- NNSupport Functions
- Pooling Functions
- Reshape Functions
- Softmax Functions
- SVD Functions

The library has separate functions for operating on different weight and activation data types including 8-bit integers (q7_t) and 16-bit integers (q15_t). The descrition of the kernels are included in the function description.

The implementation details are also described in this paper CMSIS-NN: Efficient Neural Network Kernels for Arm Cortex-M CPUs[23] .

[23] https://arxiv.org/abs/1801.06601

4.1.2 Block Diagram



Fig. 1: NMSIS NN Block Diagram

4.1.3 Examples

The library ships with a number of examples which demonstrate how to use the library functions.

- *Convolutional Neural Network Example* (page 1039)
- *Gated Recurrent Unit Example* (page 1040)

4.1.4 Pre-processor Macros

Each library project have different pre-processor macros controlled via CMakeLists.txt.

This library is only built for little endian targets.

4.2 Using NMSIS-NN

Here we will describe how to run the nmsis nn examples in Nuclei QEMU.

4.2.1 Preparation

- Nuclei SDK, `master` branch(>= 0.5.0 release)
- Nuclei RISC-V GNU Toolchain 2023.10
- Nuclei QEMU 2023.10
- CMake >= 3.14
- Python 3 and pip package requirements located in
  - <nuclei-sdk>/tools/scripts/requirements.txt
  - <NMSIS>/NMSIS/Scripts/requirements.txt

4.2.2 Tool Setup

1. Export **PATH** correctly for `qemu` and `riscv64-unknown-elf-gcc`

```
export PATH=/path/to/qemu/bin:/path/to/gcc/bin:$PATH
```

4.2.3 Build NMSIS NN Library

1. Download or clone NMSIS source code into **NMSIS** directory.
2. cd to *NMSIS/NMSIS/* directory
3. Build NMSIS NN library and strip debug information using `make gen_nn_lib`
4. The nn library will be generated into `./Library/NN/GCC` folder
5. The nn libraries will be look like this:

```
$ ls -lhgG Library/NN/GCC/
total 64M
-rw-rw-r-- 1 619K Oct 20 11:55 libnmsis_nn_rv32imac.a
-rw-rw-r-- 1 983K Oct 20 11:55 libnmsis_nn_rv32imac_xxldsp.a
-rw-rw-r-- 1 986K Oct 20 11:55 libnmsis_nn_rv32imac_xxldspn1x.a
-rw-rw-r-- 1 989K Oct 20 11:55 libnmsis_nn_rv32imac_xxldspn2x.a
-rw-rw-r-- 1 992K Oct 20 11:55 libnmsis_nn_rv32imac_xxldspn3x.a
-rw-rw-r-- 1 607K Oct 20 11:55 libnmsis_nn_rv32imac_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 961K Oct 20 11:55 libnmsis_nn_rv32imac_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 964K Oct 20 11:55 libnmsis_nn_rv32imac_zba_zbb_zbc_zbs_xxldspn1x.a
-rw-rw-r-- 1 966K Oct 20 11:55 libnmsis_nn_rv32imac_zba_zbb_zbc_zbs_xxldspn2x.a
-rw-rw-r-- 1 969K Oct 20 11:55 libnmsis_nn_rv32imac_zba_zbb_zbc_zbs_xxldspn3x.a
-rw-rw-r-- 1 620K Oct 20 11:55 libnmsis_nn_rv32imafc.a
-rw-rw-r-- 1 984K Oct 20 11:55 libnmsis_nn_rv32imafc_xxldsp.a
-rw-rw-r-- 1 987K Oct 20 11:55 libnmsis_nn_rv32imafc_xxldspn1x.a
-rw-rw-r-- 1 990K Oct 20 11:55 libnmsis_nn_rv32imafc_xxldspn2x.a
-rw-rw-r-- 1 993K Oct 20 11:55 libnmsis_nn_rv32imafc_xxldspn3x.a
-rw-rw-r-- 1 608K Oct 20 11:55 libnmsis_nn_rv32imafc_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 962K Oct 20 11:55 libnmsis_nn_rv32imafc_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 965K Oct 20 11:55 libnmsis_nn_rv32imafc_zba_zbb_zbc_zbs_xxldspn1x.a
-rw-rw-r-- 1 968K Oct 20 11:55 libnmsis_nn_rv32imafc_zba_zbb_zbc_zbs_xxldspn2x.a
-rw-rw-r-- 1 970K Oct 20 11:55 libnmsis_nn_rv32imafc_zba_zbb_zbc_zbs_xxldspn3x.a
-rw-rw-r-- 1 716K Oct 20 11:55 libnmsis_nn_rv32imafc_zve32f.a
-rw-rw-r-- 1 848K Oct 20 11:55 libnmsis_nn_rv32imafc_zve32f_xxldsp.a
-rw-rw-r-- 1 851K Oct 20 11:55 libnmsis_nn_rv32imafc_zve32f_xxldspn1x.a
-rw-rw-r-- 1 854K Oct 20 11:55 libnmsis_nn_rv32imafc_zve32f_xxldspn2x.a
-rw-rw-r-- 1 856K Oct 20 11:55 libnmsis_nn_rv32imafc_zve32f_xxldspn3x.a
-rw-rw-r-- 1 695K Oct 20 11:55 libnmsis_nn_rv32imafc_zve32f_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 825K Oct 20 11:55 libnmsis_nn_rv32imafc_zve32f_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 828K Oct 20 11:55 libnmsis_nn_rv32imafc_zve32f_zba_zbb_zbc_zbs_xxldspn1x.a
-rw-rw-r-- 1 831K Oct 20 11:55 libnmsis_nn_rv32imafc_zve32f_zba_zbb_zbc_zbs_xxldspn2x.a
-rw-rw-r-- 1 834K Oct 20 11:55 libnmsis_nn_rv32imafc_zve32f_zba_zbb_zbc_zbs_xxldspn3x.a
-rw-rw-r-- 1 621K Oct 20 11:55 libnmsis_nn_rv32imafdc.a
-rw-rw-r-- 1 985K Oct 20 11:55 libnmsis_nn_rv32imafdc_xxldsp.a
-rw-rw-r-- 1 988K Oct 20 11:55 libnmsis_nn_rv32imafdc_xxldspn1x.a
-rw-rw-r-- 1 991K Oct 20 11:55 libnmsis_nn_rv32imafdc_xxldspn2x.a
```

(continues on next page)

(continued from previous page)

```
-rw-rw-r-- 1 994K Oct 20 11:55 libnmsis_nn_rv32imafdc_xxldspn3x.a
-rw-rw-r-- 1 609K Oct 20 11:55 libnmsis_nn_rv32imafdc_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 963K Oct 20 11:55 libnmsis_nn_rv32imafdc_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 966K Oct 20 11:55 libnmsis_nn_rv32imafdc_zba_zbb_zbc_zbs_xxldspn1x.a
-rw-rw-r-- 1 969K Oct 20 11:55 libnmsis_nn_rv32imafdc_zba_zbb_zbc_zbs_xxldspn2x.a
-rw-rw-r-- 1 972K Oct 20 11:55 libnmsis_nn_rv32imafdc_zba_zbb_zbc_zbs_xxldspn3x.a
-rw-rw-r-- 1 718K Oct 20 11:55 libnmsis_nn_rv32imafdc_zve32f.a
-rw-rw-r-- 1 847K Oct 20 11:55 libnmsis_nn_rv32imafdc_zve32f_xxldsp.a
-rw-rw-r-- 1 850K Oct 20 11:55 libnmsis_nn_rv32imafdc_zve32f_xxldspn1x.a
-rw-rw-r-- 1 852K Oct 20 11:55 libnmsis_nn_rv32imafdc_zve32f_xxldspn2x.a
-rw-rw-r-- 1 855K Oct 20 11:55 libnmsis_nn_rv32imafdc_zve32f_xxldspn3x.a
-rw-rw-r-- 1 697K Oct 20 11:55 libnmsis_nn_rv32imafdc_zve32f_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 824K Oct 20 11:55 libnmsis_nn_rv32imafdc_zve32f_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 827K Oct 20 11:55 libnmsis_nn_rv32imafdc_zve32f_zba_zbb_zbc_zbs_xxldspn1x.a
-rw-rw-r-- 1 830K Oct 20 11:55 libnmsis_nn_rv32imafdc_zve32f_zba_zbb_zbc_zbs_xxldspn2x.a
-rw-rw-r-- 1 832K Oct 20 11:55 libnmsis_nn_rv32imafdc_zve32f_zba_zbb_zbc_zbs_xxldspn3x.a
-rw-rw-r-- 1 852K Oct 20 11:55 libnmsis_nn_rv64imac.a
-rw-rw-r-- 1 1.4M Oct 20 11:55 libnmsis_nn_rv64imac_xxldsp.a
-rw-rw-r-- 1 826K Oct 20 11:55 libnmsis_nn_rv64imac_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 1.4M Oct 20 11:55 libnmsis_nn_rv64imac_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 854K Oct 20 11:55 libnmsis_nn_rv64imafc.a
-rw-rw-r-- 1 1.4M Oct 20 11:55 libnmsis_nn_rv64imafc_xxldsp.a
-rw-rw-r-- 1 827K Oct 20 11:55 libnmsis_nn_rv64imafc_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 1.4M Oct 20 11:55 libnmsis_nn_rv64imafc_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 965K Oct 20 11:55 libnmsis_nn_rv64imafc_zve64f.a
-rw-rw-r-- 1 1.2M Oct 20 11:55 libnmsis_nn_rv64imafc_zve64f_xxldsp.a
-rw-rw-r-- 1 932K Oct 20 11:55 libnmsis_nn_rv64imafc_zve64f_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 1.2M Oct 20 11:55 libnmsis_nn_rv64imafc_zve64f_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 855K Oct 20 11:55 libnmsis_nn_rv64imafdc.a
-rw-rw-r-- 1 972K Oct 20 11:55 libnmsis_nn_rv64imafdcv.a
-rw-rw-r-- 1 1.2M Oct 20 11:55 libnmsis_nn_rv64imafdcv_xxldsp.a
-rw-rw-r-- 1 939K Oct 20 11:55 libnmsis_nn_rv64imafdcv_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 1.2M Oct 20 11:55 libnmsis_nn_rv64imafdcv_zba_zbb_zbc_zbs_xxldsp.a
-rw-rw-r-- 1 1.4M Oct 20 11:55 libnmsis_nn_rv64imafdc_xxldsp.a
-rw-rw-r-- 1 828K Oct 20 11:55 libnmsis_nn_rv64imafdc_zba_zbb_zbc_zbs.a
-rw-rw-r-- 1 1.4M Oct 20 11:55 libnmsis_nn_rv64imafdc_zba_zbb_zbc_zbs_xxldsp.a
```

7. library name with extra `_xxldsp` `_xxldspn1x` `_xxldspn2x` `_xxldspn3x` is built with RISC-V DSP enabled

   The examples are as follows:

   - `libnmsis_dsp_rv32imac.a`: Build for **RISCV_ARCH=rv32imac** without DSP
   - `libnmsis_dsp_rv32imac_xxldsp.a`: Build for **RISCV_ARCH=rv32imac_xxldsp** with Nuclei DSP enabled
   - `libnmsis_dsp_rv32imac_xxldspn1x.a`: Build for **RISCV_ARCH=rv32imac_xxldspn1x** with Nuclei N1 DSP extension enabled
   - `libnmsis_dsp_rv32imac_xxldspn2x.a`: Build for **RISCV_ARCH=rv32imac_xxldspn2x** with Nuclei N1/N2 DSP extension enabled
   - `libnmsis_dsp_rv32imac_xxldspn3x.a`: Build for **RISCV_ARCH=rv32imac_xxldspn3x** with Nuclei N1/N2/N3 DSP extension enabled

8. library name with extra `_zve32f` `_zve64f` `v` is built with RISC-V Vector enabled

The examples are as follows:

- `libnmsis_dsp_rv32imafc_zve32f.a`: Build for **RISCV_ARCH=rv32imafc_zve32f** with Vector enabled
- `libnmsis_dsp_rv32imafdc_zve32f.a`: Build for **RISCV_ARCH=rv32imafdc_zve32f** with Vector enabled
- `libnmsis_dsp_rv64imafc_zve64f.a`: Build for **RISCV_ARCH=rv64imafc_zve64f** with Vector enabled
- `libnmsis_dsp_rv64imafdcv.a`: Build for **RISCV_ARCH=rv64imafdcv** with Vector enabled

Note:

- This NMSIS 1.2.0 is a big change version, will no longer support old gcc 10 verison, and it now only support Nuclei Toolchain 2023.10. The `--march` option has changed a lot, such as:
  - `b` extension changed to `_zba_zbb_zbc_zbs` extension,
  - `p` extension changed to `_xxldsp` , `_xxldspn1x` , `_xxldspn2x` , `_xxldspn3x` extensions which means stardard DSP extension, Nuclei N1, N2, N3 DSP extensions
  - `v` extension changed to `v`, `_zve32f`, `_zve64f` extensions
- The name of Libraries has changed with `-march`, for examples, the library named `libnmsis_dsp_rv32imacb.a` is now named `libnmsis_dsp_rv32imac_zba_zbb_zbc_zbs.a` since `b` extension changed to `_zba_zbb_zbc_zbs`
- `_xxldspn1x _xxldspn2x _xxldspn3x` only valid for RISC-V 32bit processor. `_xxldsp` is valid for RISC-V 32/64 bit processor
- You can also directly build both DSP and NN library using `make gen`
- You can strip the generated DSP and NN library using `make strip`
- DSP and Vector extension can be combined, such as `_xxldsp`, `v` and `v_xxldsp`, should notice the extension order
- Vector extension currently enabled for RISC-V 32/64 bit processor
- NN library has no float16 data type, so here have no need to build float16 library

4.2.4 How to run

1. Set environment variables `NUCLEI_SDK_ROOT` and `NUCLEI_SDK_NMSIS`, and set Nuclei SDK SoC to *evalsoc*, and change ilm/dlm size from 64K to 512K.

```
export NUCLEI_SDK_ROOT=/path/to/nuclei_sdk
export NUCLEI_SDK_NMSIS=/path/to/NMSIS/NMSIS
# Setup SDK development environment
cd $NUCLEI_SDK_ROOT
source setup.sh
cd -
# !!!!Take Care!!!!
# change this link script will make compiled example can only run on bitstream which has␣
↪512K ILM/DLM
```

(continues on next page)

(continued from previous page)

```
sed -i "s/64K/512K/g" $NUCLEI_SDK_ROOT/SoC/evalsoc/Board/nuclei_fpga_eval/Source/GCC/gcc_
↪evalsoc_ilm.ld
export SOC=evalsoc
```

2. Due to many of the examples could not be placed in 64K ILM and 64K DLM, and we are running using qemu, the ILM/DLM size in it are set to be 32MB, so we can change ilm/dlm to 512K/512K in the link script `$NUCLEI_SDK_ROOT/SoC/evalsoc/Board/nuclei_fpga_eval/Source/GCC/gcc_evalsoc_ilm.ld`

```
--- a/SoC/evalsoc/Board/nuclei_fpga_eval/Source/GCC/gcc_evalsoc_ilm.ld
+++ b/SoC/evalsoc/Board/nuclei_fpga_eval/Source/GCC/gcc_evalsoc_ilm.ld
@@ -30,8 +30,8 @@ __HEAP_SIZE  = 2K;

MEMORY
{
-  ilm (rxa!w) : ORIGIN = 0x80000000, LENGTH = 64K
-  ram (wxa!r) : ORIGIN = 0x90000000, LENGTH = 64K
+  ilm (rxa!w) : ORIGIN = 0x80000000, LENGTH = 512K
+  ram (wxa!r) : ORIGIN = 0x90000000, LENGTH = 512K
}
```

3. Let us take `cifar10` for example:

```
cd $NUCLEI_SDK_NMSIS/NN/Examples/RISCV/cifar10/
```

4. Run with RISCV DSP enabled and Vector enabled NMSIS-NN library for CORE `nx900fd`

```
# Clean project
make ARCH_EXT=v_xxldsp CORE=nx900fd clean
# Build project, enable ``v`` and ``xxldsp`` optimize
make ARCH_EXT=v_xxldsp CORE=nx900fd all
# Run application using qemu
make ARCH_EXT=v_xxldsp CORE=nx900fd run_qemu
```

5. Run with RISCV DSP disabled and Vector disabled NMSIS-NN library for CORE `nx900fd`

```
make ARCH_EXT= CORE=nx900fd clean
make ARCH_EXT= CORE=nx900fd all
make ARCH_EXT= CORE=nx900fd run_qemu
```

Note:

- You can easily run this example in your hardware, if you have enough memory to run it, just modify the `SOC` to the one your are using in step 1.

4.3 NMSIS NN API

If you want to access doxygen generated NMSIS NN API, please click NMSIS NN API Doxygen Documentation.

4.3.1 Convolutional Neural Network Example

group **CNNExample**



Description:

Demonstrates a convolutional neural network (CNN) example with the use of convolution, ReLU activation, pooling and fully-connected functions.

Model definition:

The CNN used in this example is based on CIFAR-10 example from Caffe [1]. The neural network consists of 3 convolution layers interspersed by ReLU activation and max pooling layers, followed by a fully-connected layer at the end. The input to the network is a 32x32 pixel color image, which will be classified into one of the 10 output classes. This example model implementation needs 32.3 KB to store weights, 40 KB for activations and 3.1 KB for storing the `im2col` data.

Refer riscv_nnexamples_cifar10.cpp

Variables Description:

- `conv1_wt`, `conv2_wt`, `conv3_wt` are convolution layer weight matrices
- `conv1_bias`, `conv2_bias`, `conv3_bias` are convolution layer bias arrays
- `ip1_wt`, ip1_bias point to fully-connected layer weights and biases
- `input_data` points to the input image data
- `output_data` points to the classification output
- `col_buffer` is a buffer to store the `im2col` output
- `scratch_buffer` is used to store the activation data (intermediate layer outputs)

NMSIS DSP Software Library Functions Used:

- riscv_convolve_HWC_q7_RGB()
- riscv_convolve_HWC_q7_fast()
- riscv_relu_q7()
- riscv_maxpool_q7_HWC()

- riscv_avepool_q7_HWC()
- riscv_fully_connected_q7_opt()
- riscv_fully_connected_q7()

[1] https://github.com/BVLC/caffe

4.3.2 Gated Recurrent Unit Example

group **GRUExample**

Refer riscv_nnexamples_gru.cpp

Description:

Demonstrates a gated recurrent unit (GRU) example with the use of fully-connected, Tanh/Sigmoid activation functions.

Model definition:

GRU is a type of recurrent neural network (RNN). It contains two sigmoid gates and one hidden state.



The computation can be summarized as:

Variables Description:

- `update_gate_weights`, `reset_gate_weights`, `hidden_state_weights` are weights corresponding to update gate (W_z), reset gate (W_r), and hidden state (W_n).
- `update_gate_bias`, `reset_gate_bias`, `hidden_state_bias` are layer bias arrays
- `test_input1`, `test_input2`, `test_history` are the inputs and initial history

The buffer is allocated as:

| reset | input | history | update | hidden_state |

In this way, the concatination is automatically done since (reset, input) and (input, history) are physically concatinated in memory.

The ordering of the weight matrix should be adjusted accordingly.

NMSIS DSP Software Library Functions Used:

- riscv_fully_connected_mat_q7_vec_q15_opt()
- riscv_nn_activations_direct_q15()
- riscv_mult_q15()
- riscv_offset_q15()
- riscv_sub_q15()
- riscv_copy_q15()

4.3.3 Public

Activation Functions

void **riscv_nn_activation_s16**(const int16_t *input, int16_t *output, const uint16_t size, const uint16_t left_shift, const riscv_nn_activation_type type)

void **riscv_nn_activations_direct_q15**(q15_t *data, uint16_t size, uint16_t int_width, riscv_nn_activation_type type)

void **riscv_nn_activations_direct_q7**(q7_t *data, uint16_t size, uint16_t int_width, riscv_nn_activation_type type)

void **riscv_relu6_s8**(int8_t *data, uint16_t size)

void **riscv_relu_q15**(int16_t *data, uint16_t size)

void **riscv_relu_q7**(int8_t *data, uint16_t size)

group **Acti**

Perform activation layers, including ReLU (Rectified Linear Unit), sigmoid and tanh.

Functions

void **riscv_nn_activation_s16**(const int16_t *input, int16_t *output, const uint16_t size, const uint16_t left_shift, const riscv_nn_activation_type type)

s16 neural network activation function using direct table look-up

Supported framework: TensorFlow Lite for Microcontrollers. This activation function must be bit precise congruent with the corresponding TFLM tanh and sigmoid actication functions

Parameters

- **input** – **[in]** pointer to input data
- **output** – **[out]** pointer to output
- **size** – **[in]** number of elements
- **left_shift** – **[in]** bit-width of the integer part, assume to be smaller than 3
- **type** – **[in]** type of activation functions

void **riscv_nn_activations_direct_q15**(q15_t *data, uint16_t size, uint16_t int_width, riscv_nn_activation_type type)

neural network activation function using direct table look-up

Q15 neural network activation function using direct table look-up.

Note: Refer header file for details.

void **riscv_nn_activations_direct_q7**(q7_t *data, uint16_t size, uint16_t int_width, riscv_nn_activation_type type)

Q7 neural network activation function using direct table look-up.

This is the direct table look-up approach.

Assume here the integer part of the fixed-point is <= 3. More than 3 just not making much sense, makes no difference with saturation followed by any of these activation functions.

Parameters

- `data` – **[inout]** pointer to input
- `size` – **[in]** number of elements
- `int_width` – **[in]** bit-width of the integer part, assume to be smaller than 3
- `type` – **[in]** type of activation functions

void **riscv_relu6_s8**(int8_t *data, uint16_t size)

s8 ReLU6 function

Parameters

- `data` – **[inout]** pointer to input
- `size` – **[in]** number of elements

void **riscv_relu_q15**(int16_t *data, uint16_t size)

Q15 RELU function.

Parameters

- `data` – **[inout]** pointer to input
- `size` – **[in]** number of elements

void **riscv_relu_q7**(int8_t *data, uint16_t size)

Q7 RELU function.

Parameters

- `data` – **[inout]** pointer to input
- `size` – **[in]** number of elements

GroupElementwise

riscv_nmsis_nn_status **riscv_elementwise_add_s16**(const int16_t *input_1_vect, const int16_t *input_2_vect, const int32_t input_1_offset, const int32_t input_1_mult, const int32_t input_1_shift, const int32_t input_2_offset, const int32_t input_2_mult, const int32_t input_2_shift, const int32_t left_shift, int16_t *output, const int32_t out_offset, const int32_t out_mult, const int32_t out_shift, const int32_t out_activation_min, const int32_t out_activation_max, const int32_t block_size)

riscv_nmsis_nn_status **riscv_elementwise_add_s8**(const int8_t *input_1_vect, const int8_t *input_2_vect, const int32_t input_1_offset, const int32_t input_1_mult, const int32_t input_1_shift, const int32_t input_2_offset, const int32_t input_2_mult, const int32_t input_2_shift, const int32_t left_shift, int8_t *output, const int32_t out_offset, const int32_t out_mult, const int32_t out_shift, const int32_t out_activation_min, const int32_t out_activation_max, const int32_t block_size)

riscv_nmsis_nn_status **riscv_elementwise_mul_s16**(const int16_t *input_1_vect, const int16_t *input_2_vect, const int32_t input_1_offset, const int32_t input_2_offset, int16_t *output, const int32_t out_offset, const int32_t out_mult, const int32_t out_shift, const int32_t out_activation_min, const int32_t out_activation_max, const int32_t block_size)

riscv_nmsis_nn_status **riscv_elementwise_mul_s8**(const int8_t *input_1_vect, const int8_t *input_2_vect, const int32_t input_1_offset, const int32_t input_2_offset, int8_t *output, const int32_t out_offset, const int32_t out_mult, const int32_t out_shift, const int32_t out_activation_min, const int32_t out_activation_max, const int32_t block_size)

group **GroupElementwise**

Functions

riscv_nmsis_nn_status **riscv_elementwise_add_s16**(const int16_t *input_1_vect, const int16_t *input_2_vect, const int32_t input_1_offset, const int32_t input_1_mult, const int32_t input_1_shift, const int32_t input_2_offset, const int32_t input_2_mult, const int32_t input_2_shift, const int32_t left_shift, int16_t *output, const int32_t out_offset, const int32_t out_mult, const int32_t out_shift, const int32_t out_activation_min, const int32_t out_activation_max, const int32_t block_size)

s16 elementwise add of two vectors

Parameters

- **input_1_vect** – **[in]** pointer to input vector 1
- **input_2_vect** – **[in]** pointer to input vector 2

- `input_1_offset` – **[in]** offset for input 1. Not used.
- `input_1_mult` – **[in]** multiplier for input 1
- `input_1_shift` – **[in]** shift for input 1
- `input_2_offset` – **[in]** offset for input 2. Not used.
- `input_2_mult` – **[in]** multiplier for input 2
- `input_2_shift` – **[in]** shift for input 2
- `left_shift` – **[in]** input left shift
- `output` – **[inout]** pointer to output vector
- `out_offset` – **[in]** output offset. Not used.
- `out_mult` – **[in]** output multiplier
- `out_shift` – **[in]** output shift
- `out_activation_min` – **[in]** minimum value to clamp output to. Min: -32768
- `out_activation_max` – **[in]** maximum value to clamp output to. Max: 32767
- `block_size` – **[in]** number of samples

Returns The function returns RISCV_NMSIS_NN_SUCCESS

riscv_nmsis_nn_status **`riscv_elementwise_add_s8`**(const int8_t *input_1_vect, const int8_t *input_2_vect, const int32_t input_1_offset, const int32_t input_1_mult, const int32_t input_1_shift, const int32_t input_2_offset, const int32_t input_2_mult, const int32_t input_2_shift, const int32_t left_shift, int8_t *output, const int32_t out_offset, const int32_t out_mult, const int32_t out_shift, const int32_t out_activation_min, const int32_t out_activation_max, const int32_t block_size)

s8 elementwise add of two vectors

Parameters

- `input_1_vect` – **[in]** pointer to input vector 1
- `input_2_vect` – **[in]** pointer to input vector 2
- `input_1_offset` – **[in]** offset for input 1. Range: -127 to 128
- `input_1_mult` – **[in]** multiplier for input 1
- `input_1_shift` – **[in]** shift for input 1
- `input_2_offset` – **[in]** offset for input 2. Range: -127 to 128
- `input_2_mult` – **[in]** multiplier for input 2
- `input_2_shift` – **[in]** shift for input 2
- `left_shift` – **[in]** input left shift
- `output` – **[inout]** pointer to output vector
- `out_offset` – **[in]** output offset. Range: -128 to 127
- `out_mult` – **[in]** output multiplier
- `out_shift` – **[in]** output shift

- **out_activation_min** – **[in]** minimum value to clamp output to. Min: -128
- **out_activation_max** – **[in]** maximum value to clamp output to. Max: 127
- **block_size** – **[in]** number of samples

Returns The function returns RISCV_NMSIS_NN_SUCCESS

riscv_nmsis_nn_status **riscv_elementwise_mul_s16**(const int16_t *input_1_vect, const int16_t *input_2_vect, const int32_t input_1_offset, const int32_t input_2_offset, int16_t *output, const int32_t out_offset, const int32_t out_mult, const int32_t out_shift, const int32_t out_activation_min, const int32_t out_activation_max, const int32_t block_size)

s16 element wise multiplication of two vectors

s16 elementwise multiplication

Note: Refer header file for details.

---

riscv_nmsis_nn_status **riscv_elementwise_mul_s8**(const int8_t *input_1_vect, const int8_t *input_2_vect, const int32_t input_1_offset, const int32_t input_2_offset, int8_t *output, const int32_t out_offset, const int32_t out_mult, const int32_t out_shift, const int32_t out_activation_min, const int32_t out_activation_max, const int32_t block_size)

s8 elementwise multiplication

Supported framework: TensorFlow Lite micro

Parameters

- **input_1_vect** – **[in]** pointer to input vector 1
- **input_2_vect** – **[in]** pointer to input vector 2
- **input_1_offset** – **[in]** offset for input 1. Range: -127 to 128
- **input_2_offset** – **[in]** offset for input 2. Range: -127 to 128
- **output** – **[inout]** pointer to output vector
- **out_offset** – **[in]** output offset. Range: -128 to 127
- **out_mult** – **[in]** output multiplier
- **out_shift** – **[in]** output shift
- **out_activation_min** – **[in]** minimum value to clamp output to. Min: -128
- **out_activation_max** – **[in]** maximum value to clamp output to. Max: 127
- **block_size** – **[in]** number of samples

Returns The function returns RISCV_NMSIS_NN_SUCCESS

Concatenation Functions

void **riscv_concatenation_s8_w**(const int8_t *input, const uint16_t input_x, const uint16_t input_y, const uint16_t input_z, const uint16_t input_w, int8_t *output, const uint32_t offset_w)

void **riscv_concatenation_s8_x**(const int8_t *input, const uint16_t input_x, const uint16_t input_y, const uint16_t input_z, const uint16_t input_w, int8_t *output, const uint16_t output_x, const uint32_t offset_x)

void **riscv_concatenation_s8_y**(const int8_t *input, const uint16_t input_x, const uint16_t input_y, const uint16_t input_z, const uint16_t input_w, int8_t *output, const uint16_t output_y, const uint32_t offset_y)

void **riscv_concatenation_s8_z**(const int8_t *input, const uint16_t input_x, const uint16_t input_y, const uint16_t input_z, const uint16_t input_w, int8_t *output, const uint16_t output_z, const uint32_t offset_z)

group `Concatenation`

Functions

void **riscv_concatenation_s8_w**(const int8_t *input, const uint16_t input_x, const uint16_t input_y, const uint16_t input_z, const uint16_t input_w, int8_t *output, const uint32_t offset_w)

int8/uint8 concatenation function to be used for concatenating N-tensors along the W axis (Batch size) This function should be called for each input tensor to concatenate. The argument offset_w will be used to store the input tensor in the correct position in the output tensor

i.e. offset_w = 0 for(i = 0 i < num_input_tensors; ++i) { riscv_concatenation_s8_w(&input[i], . . . , &output, . . . , . . . , offset_w) offset_w += input_w[i] }

This function assumes that the output tensor has:

a. The same width of the input tensor

b. The same height of the input tensor

c. The same number o channels of the input tensor

Unless specified otherwise, arguments are mandatory.

Note: This function, data layout independent, can be used to concatenate either int8 or uint8 tensors because it does not involve any arithmetic operation

Parameters

- **input** – **[in]** Pointer to input tensor
- **input_x** – **[in]** Width of input tensor
- **input_y** – **[in]** Height of input tensor
- **input_z** – **[in]** Channels in input tensor
- **input_w** – **[in]** Batch size in input tensor

- **output** – **[out]** Pointer to output tensor. Expected to be at least input_x * input_y * input_z * input_w bytes.
- **offset_w** – **[in]** The offset on the W axis to start concatenating the input tensor It is user responsibility to provide the correct value

void **riscv_concatenation_s8_x**(const int8_t *input, const uint16_t input_x, const uint16_t input_y, const uint16_t input_z, const uint16_t input_w, int8_t *output, const uint16_t output_x, const uint32_t offset_x)

int8/uint8 concatenation function to be used for concatenating N-tensors along the X axis This function should be called for each input tensor to concatenate. The argument offset_x will be used to store the input tensor in the correct position in the output tensor

i.e. offset_x = 0 for(i = 0 i < num_input_tensors; ++i) { riscv_concatenation_s8_x(&input[i], …, &output, …, …, offset_x) offset_x += input_x[i] }

This function assumes that the output tensor has:

a. The same height of the input tensor
b. The same number of channels of the input tensor
c. The same batch size of the input tensor

Unless specified otherwise, arguments are mandatory.

Input constraints offset_x is less than output_x

Note: This function, data layout independent, can be used to concatenate either int8 or uint8 tensors because it does not involve any arithmetic operation

---

Parameters

- **input** – **[in]** Pointer to input tensor. Input tensor must not overlap with the output tensor.
- **input_x** – **[in]** Width of input tensor
- **input_y** – **[in]** Height of input tensor
- **input_z** – **[in]** Channels in input tensor
- **input_w** – **[in]** Batch size in input tensor
- **output** – **[out]** Pointer to output tensor. Expected to be at least (input_x * input_y * input_z * input_w) + offset_x bytes.
- **output_x** – **[in]** Width of output tensor
- **offset_x** – **[in]** The offset (in number of elements) on the X axis to start concatenating the input tensor It is user responsibility to provide the correct value

void **riscv_concatenation_s8_y**(const int8_t *input, const uint16_t input_x, const uint16_t input_y, const uint16_t input_z, const uint16_t input_w, int8_t *output, const uint16_t output_y, const uint32_t offset_y)

int8/uint8 concatenation function to be used for concatenating N-tensors along the Y axis This function should be called for each input tensor to concatenate. The argument offset_y will be used to store the input tensor in the correct position in the output tensor

i.e. offset_y = 0 for(i = 0 i < num_input_tensors; ++i) { riscv_concatenation_s8_y(&input[i], …, &output, …, …, offset_y) offset_y += input_y[i] }

This function assumes that the output tensor has:

a. The same width of the input tensor

b. The same number of channels of the input tensor

c. The same batch size of the input tensor

Unless specified otherwise, arguments are mandatory.

Input constraints offset_y is less than output_y

Note: This function, data layout independent, can be used to concatenate either int8 or uint8 tensors because it does not involve any arithmetic operation

---

Parameters

- **input** – **[in]** Pointer to input tensor. Input tensor must not overlap with the output tensor.
- **input_x** – **[in]** Width of input tensor
- **input_y** – **[in]** Height of input tensor
- **input_z** – **[in]** Channels in input tensor
- **input_w** – **[in]** Batch size in input tensor
- **output** – **[out]** Pointer to output tensor. Expected to be at least (input_z * input_w * input_x * input_y) + offset_y bytes.
- **output_y** – **[in]** Height of output tensor
- **offset_y** – **[in]** The offset on the Y axis to start concatenating the input tensor It is user responsibility to provide the correct value

void **riscv_concatenation_s8_z**(const int8_t *input, const uint16_t input_x, const uint16_t input_y, const uint16_t input_z, const uint16_t input_w, int8_t *output, const uint16_t output_z, const uint32_t offset_z)

int8/uint8 concatenation function to be used for concatenating N-tensors along the Z axis This function should be called for each input tensor to concatenate. The argument offset_z will be used to store the input tensor in the correct position in the output tensor

i.e. offset_z = 0 for(i = 0 i < num_input_tensors; ++i) { riscv_concatenation_s8_z(&input[i], …, &output, …, …, offset_z) offset_z += input_z[i] }

This function assumes that the output tensor has:

a. The same width of the input tensor

b. The same height of the input tensor

c. The same batch size of the input tensor

Unless specified otherwise, arguments are mandatory.

Input constraints offset_z is less than output_z

Note: This function, data layout independent, can be used to concatenate either int8 or uint8 tensors because it does not involve any arithmetic operation

---

Parameters

- **input** – **[in]** Pointer to input tensor. Input tensor must not overlap with output tensor.
- **input_x** – **[in]** Width of input tensor
- **input_y** – **[in]** Height of input tensor
- **input_z** – **[in]** Channels in input tensor
- **input_w** – **[in]** Batch size in input tensor
- **output** – **[out]** Pointer to output tensor. Expected to be at least (input_x * input_y * input_z * input_w) + offset_z bytes.
- **output_z** – **[in]** Channels in output tensor
- **offset_z** – **[in]** The offset on the Z axis to start concatenating the input tensor It is user responsibility to provide the correct value

Convolution Functions

GetBufferSizeNNConv

__STATIC_INLINE int32_t riscv_convolve_fast_s16_get_buffer_size_dsp (const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims)

int32_t **riscv_convolve_fast_s16_get_buffer_size**(const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims)

int32_t **riscv_convolve_s16_get_buffer_size**(const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims)

int32_t **riscv_convolve_wrapper_s16_get_buffer_size**(const nmsis_nn_conv_params *conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

int32_t **riscv_convolve_wrapper_s16_get_buffer_size_dsp**(const nmsis_nn_conv_params *conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

int32_t **riscv_convolve_s8_get_buffer_size**(const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims)

int32_t **riscv_convolve_1_x_n_s8_get_buffer_size**(const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims)

int32_t **riscv_convolve_1x1_s8_fast_get_buffer_size**(const nmsis_nn_dims *input_dims)

int32_t **riscv_convolve_wrapper_s8_get_buffer_size**(const nmsis_nn_conv_params *conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

int32_t **riscv_convolve_wrapper_s8_get_buffer_size_dsp**(const nmsis_nn_conv_params *conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

__STATIC_INLINE int32_t riscv_depthwise_conv_fast_s16_get_buffer_size_dsp (const nmsis_nn_dims *input_di const nmsis_nn_dims *filter_dims)

int32_t **riscv_depthwise_conv_fast_s16_get_buffer_size**(const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims)

int32_t **riscv_depthwise_conv_wrapper_s16_get_buffer_size**(const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

int32_t **riscv_depthwise_conv_wrapper_s16_get_buffer_size_dsp**(const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

__STATIC_INLINE int32_t riscv_depthwise_conv_s8_opt_get_buffer_size_dsp (const nmsis_nn_dims *input_dims const nmsis_nn_dims *filter_dims)

int32_t **riscv_depthwise_conv_s8_opt_get_buffer_size**(const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims)

int32_t **riscv_depthwise_conv_wrapper_s8_get_buffer_size**(const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

int32_t **riscv_depthwise_conv_wrapper_s8_get_buffer_size_dsp**(const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

group GetBufferSizeNNConv

Functions

__STATIC_INLINE int32_t riscv_convolve_fast_s16_get_buffer_size_dsp (const nmsis_nn_dims *input_dir const nmsis_nn_dims *filter_dims)

int32_t **riscv_convolve_fast_s16_get_buffer_size**(const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims)

Get the required buffer size for fast s16 convolution function.

Parameters

- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN]
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [C_OUT, HK, WK, C_IN] where HK and WK are the spatial filter dimensions

Returns The function returns required buffer size(bytes)

int32_t **riscv_convolve_s16_get_buffer_size**(const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims)

Get the required buffer size for s16 convolution function.

Parameters

- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN]
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [C_OUT, HK, WK, C_IN] where HK and WK are the spatial filter dimensions

Returns The function returns required buffer size(bytes)

int32_t **riscv_convolve_wrapper_s16_get_buffer_size**(const nmsis_nn_conv_params *conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

Get the required buffer size for riscv_convolve_wrapper_s16.

Parameters

- **conv_params** – **[in]** Convolution parameters (e.g. strides, dilations, pads,…). conv_params->input_offset : Not used conv_params->output_offset : Not used
- **input_dims** – **[in]** Input (activation) dimensions. Format: [N, H, W, C_IN]
- **filter_dims** – **[in]** Filter dimensions. Format: [C_OUT, HK, WK, C_IN] where HK and WK are the spatial filter dimensions
- **output_dims** – **[in]** Output tensor dimensions. Format: [N, H, W, C_OUT]

Returns The function returns required buffer size(bytes)

int32_t **riscv_convolve_wrapper_s16_get_buffer_size_dsp**(const nmsis_nn_conv_params *conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

Get the required buffer size for riscv_convolve_wrapper_s16 for for processors with DSP extension. Refer to riscv_convolve_wrapper_s16_get_buffer_size() for function argument details.

Note: Intended for compilation on Host. If compiling for an Arm target, use riscv_convolve_wrapper_s16_get_buffer_size().

int32_t **riscv_convolve_s8_get_buffer_size**(const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims)

Get the required buffer size for s8 convolution function.

Parameters

- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN]
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [C_OUT, HK, WK, C_IN] where HK and WK are the spatial filter dimensions

Returns The function returns required buffer size(bytes) int32_t **riscv_convolve_1_x_n_s8_get_buffer_size**(const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims)

Get the required additional buffer size for 1xn convolution.

Parameters

- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN]
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [C_OUT, 1, WK, C_IN] where WK is the horizontal spatial filter dimension

Returns The function returns required buffer size(bytes)

int32_t **riscv_convolve_1x1_s8_fast_get_buffer_size**(const nmsis_nn_dims *input_dims)

Get the required buffer size for riscv_convolve_1x1_s8_fast.

Parameters **input_dims** – **[in]** Input (activation) dimensions

Returns The function returns the required buffer size in bytes

int32_t **riscv_convolve_wrapper_s8_get_buffer_size**(const nmsis_nn_conv_params *conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

Get the required buffer size for riscv_convolve_wrapper_s8.

Parameters

- **conv_params** – **[in]** Convolution parameters (e.g. strides, dilations, pads,…). Range of conv_params->input_offset : [-127, 128] Range of conv_params->output_offset : [-128, 127]
- **input_dims** – **[in]** Input (activation) dimensions. Format: [N, H, W, C_IN]
- **filter_dims** – **[in]** Filter dimensions. Format: [C_OUT, HK, WK, C_IN] where HK and WK are the spatial filter dimensions
- **output_dims** – **[in]** Output tensor dimensions. Format: [N, H, W, C_OUT]

Returns The function returns required buffer size(bytes)

int32_t **riscv_convolve_wrapper_s8_get_buffer_size_dsp**(const nmsis_nn_conv_params *conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

Get the required buffer size for riscv_convolve_wrapper_s8 for processors with DSP extension. Refer to riscv_convolve_wrapper_s8_get_buffer_size() for function argument details.

Note: Intended for compilation on Host. If compiling for an Arm target, use riscv_convolve_wrapper_s8_get_buffer_size().

__STATIC_INLINE int32_t riscv_depthwise_conv_fast_s16_get_buffer_size_dsp (const nmsis_nn_dims *inp const nmsis_nn_dims *filter_dims)

int32_t **riscv_depthwise_conv_fast_s16_get_buffer_size**(const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims)

Get the required buffer size for optimized s16 depthwise convolution function with constraint that in_channel equals out_channel.

Parameters

- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [1, H, W, C_IN] Batch argument N is not used.
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [1, H, W, C_OUT]

Returns The function returns required buffer size in bytes

int32_t **riscv_depthwise_conv_wrapper_s16_get_buffer_size**(const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

Get size of additional buffer required by riscv_depthwise_conv_wrapper_s16()

Parameters

- **dw_conv_params** – **[in]** Depthwise convolution parameters (e.g. strides, dilations, pads,…) Range of dw_conv_params->input_offset : Not used Range of dw_conv_params->input_offset : Not used
- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [H, W, C_IN] Batch argument N is not used and assumed to be 1.
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [1, H, W, C_OUT]
- **output_dims** – **[in]** Output tensor dimensions. Format: [1, H, W, C_OUT]

Returns Size of additional memory required for optimizations in bytes.

int32_t **riscv_depthwise_conv_wrapper_s16_get_buffer_size_dsp**(const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

__STATIC_INLINE int32_t riscv_depthwise_conv_s8_opt_get_buffer_size_dsp (const nmsis_nn_dims *input const nmsis_nn_dims *filter_dims)

int32_t **riscv_depthwise_conv_s8_opt_get_buffer_size**(const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims)

Get the required buffer size for optimized s8 depthwise convolution function with constraint that in_channel equals out_channel.

Parameters

- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [1, H, W, C_IN] Batch argument N is not used.
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [1, H, W, C_OUT]

Returns The function returns required buffer size in bytes

int32_t **riscv_depthwise_conv_wrapper_s8_get_buffer_size**(const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

Get size of additional buffer required by riscv_depthwise_conv_wrapper_s8()

Parameters

- **dw_conv_params** – **[in]** Depthwise convolution parameters (e.g. strides, dilations, pads,…) Range of dw_conv_params->input_offset : [-127, 128] Range of dw_conv_params->input_offset : [-128, 127]
- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [H, W, C_IN] Batch argument N is not used and assumed to be 1.
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [1, H, W, C_OUT]
- **output_dims** – **[in]** Output tensor dimensions. Format: [1, H, W, C_OUT]

Returns Size of additional memory required for optimizations in bytes.

int32_t **riscv_depthwise_conv_wrapper_s8_get_buffer_size_dsp**(const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_dims *input_dims, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims)

riscv_nmsis_nn_status **riscv_convolve_1_x_n_s8**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int32_t *bias_data, const nmsis_nn_dims *output_dims, int8_t *output_data)

riscv_nmsis_nn_status **riscv_convolve_1x1_HWC_q7_fast_nonsquare**(const q7_t *Im_in, const uint16_t dim_im_in_x, const uint16_t dim_im_in_y, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel_x, const uint16_t dim_kernel_y, const uint16_t padding_x, const uint16_t padding_y, const uint16_t stride_x, const uint16_t stride_y, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out_x, const uint16_t dim_im_out_y, q15_t *bufferA, q7_t *bufferB)

riscv_nmsis_nn_status **riscv_convolve_1x1_s8**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int32_t *bias_data, const nmsis_nn_dims *output_dims, int8_t *output_data) riscv_nmsis_nn_status **riscv_convolve_1x1_s8_fast**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int32_t *bias_data, const nmsis_nn_dims *output_dims, int8_t *output_data)

riscv_nmsis_nn_status **riscv_convolve_fast_s16**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int16_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int64_t *bias_data, const nmsis_nn_dims *output_dims, int16_t *output_data)

riscv_nmsis_nn_status **riscv_convolve_HWC_q15_basic**(const q15_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const q15_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const q15_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q15_t *Im_out, const uint16_t dim_im_out, q15_t *bufferA, q7_t *bufferB)

riscv_nmsis_nn_status **riscv_convolve_HWC_q15_fast**(const q15_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const q15_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const q15_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q15_t *Im_out, const uint16_t dim_im_out, q15_t *bufferA, q7_t *bufferB)

riscv_nmsis_nn_status **riscv_convolve_HWC_q15_fast_nonsquare**(const q15_t *Im_in, const uint16_t dim_im_in_x, const uint16_t dim_im_in_y, const uint16_t ch_im_in, const q15_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel_x, const uint16_t dim_kernel_y, const uint16_t padding_x, const uint16_t padding_y, const uint16_t stride_x, const uint16_t stride_y, const q15_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q15_t *Im_out, const uint16_t dim_im_out_x, const uint16_t dim_im_out_y, q15_t *bufferA, q7_t *bufferB)

riscv_nmsis_nn_status **riscv_convolve_HWC_q7_basic**(const q7_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out, q15_t *bufferA, q7_t *bufferB) riscv_nmsis_nn_status **riscv_convolve_HWC_q7_basic_nonsquare**(const q7_t *Im_in, const uint16_t dim_im_in_x, const uint16_t dim_im_in_y, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel_x, const uint16_t dim_kernel_y, const uint16_t padding_x, const uint16_t padding_y, const uint16_t stride_x, const uint16_t stride_y, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out_x, const uint16_t dim_im_out_y, q15_t *bufferA, q7_t *bufferB)

riscv_nmsis_nn_status **riscv_convolve_HWC_q7_fast**(const q7_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out, q15_t *bufferA, q7_t *bufferB)

riscv_nmsis_nn_status **riscv_convolve_HWC_q7_fast_nonsquare**(const q7_t *Im_in, const uint16_t dim_im_in_x, const uint16_t dim_im_in_y, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel_x, const uint16_t dim_kernel_y, const uint16_t padding_x, const uint16_t padding_y, const uint16_t stride_x, const uint16_t stride_y, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out_x, const uint16_t dim_im_out_y, q15_t *bufferA, q7_t *bufferB)

riscv_nmsis_nn_status **riscv_convolve_HWC_q7_RGB**(const q7_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out, q15_t *bufferA, q7_t *bufferB)

riscv_nmsis_nn_status **riscv_convolve_s16**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int16_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int64_t *bias_data, const nmsis_nn_dims *output_dims, int16_t *output_data)

riscv_nmsis_nn_status **riscv_convolve_s8**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int32_t *bias_data, const nmsis_nn_dims *output_dims, int8_t *output_data) riscv_nmsis_nn_status **riscv_convolve_wrapper_s16**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int16_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int64_t *bias_data, const nmsis_nn_dims *output_dims, int16_t *output_data)

riscv_nmsis_nn_status **riscv_convolve_wrapper_s8**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int32_t *bias_data, const nmsis_nn_dims *output_dims, int8_t *output_data)

riscv_nmsis_nn_status **riscv_depthwise_conv_3x3_s8**(const nmsis_nn_context *ctx, const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input, const nmsis_nn_dims *filter_dims, const int8_t *kernel, const nmsis_nn_dims *bias_dims, const int32_t *bias, const nmsis_nn_dims *output_dims, int8_t *output)

riscv_nmsis_nn_status **riscv_depthwise_conv_fast_s16**(const nmsis_nn_context *ctx, const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int16_t *input, const nmsis_nn_dims *filter_dims, const int8_t *kernel, const nmsis_nn_dims *bias_dims, const int64_t *bias, const nmsis_nn_dims *output_dims, int16_t *output)

static void __attribute__ ((unused))

static void **depthwise_conv_s16_generic_s16**(const int16_t *input, const uint16_t input_batches, const uint16_t input_x, const uint16_t input_y, const uint16_t input_ch, const int8_t *kernel, const uint16_t ch_mult, const uint16_t kernel_x, const uint16_t kernel_y, const uint16_t pad_x, const uint16_t pad_y, const uint16_t stride_x, const uint16_t stride_y, const int64_t *bias, int16_t *output, const int32_t *output_shift, const int32_t *output_mult, const uint16_t output_x, const uint16_t output_y, const int32_t output_activation_min, const int32_t output_activation_max, const uint16_t dilation_x, const uint16_t dilation_y)

riscv_nmsis_nn_status **riscv_depthwise_conv_s16**(const nmsis_nn_context *ctx, const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int16_t *input, const nmsis_nn_dims *filter_dims, const int8_t *kernel, const nmsis_nn_dims *bias_dims, const int64_t *bias, const nmsis_nn_dims *output_dims, int16_t *output) static void **depthwise_conv_s8_mult_4**(const int8_t *input, const int32_t input_x, const int32_t input_y, const int32_t input_ch, const int8_t *kernel, const int32_t output_ch, const int32_t ch_mult, const int32_t kernel_x, const int32_t kernel_y, const int32_t pad_x, const int32_t pad_y, const int32_t stride_x, const int32_t stride_y, const int32_t *bias, int8_t *output, const int32_t *output_shift, const int32_t *output_mult, const int32_t output_x, const int32_t output_y, const int32_t output_offset, const int32_t input_offset, const int32_t output_activation_min, const int32_t output_activation_max)

static void **depthwise_conv_s8_generic**(const int8_t *input, const uint16_t input_batches, const uint16_t input_x, const uint16_t input_y, const uint16_t input_ch, const int8_t *kernel, const uint16_t output_ch, const uint16_t ch_mult, const uint16_t kernel_x, const uint16_t kernel_y, const uint16_t pad_x, const uint16_t pad_y, const uint16_t stride_x, const uint16_t stride_y, const int32_t *bias, int8_t *output, const int32_t *output_shift, const int32_t *output_mult, const uint16_t output_x, const uint16_t output_y, const int32_t output_offset, const int32_t input_offset, const int32_t output_activation_min, const int32_t output_activation_max, const uint16_t dilation_x, const uint16_t dilation_y)

riscv_nmsis_nn_status **riscv_depthwise_conv_s8**(const nmsis_nn_context *ctx, const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input, const nmsis_nn_dims *filter_dims, const int8_t *kernel, const nmsis_nn_dims *bias_dims, const int32_t *bias, const nmsis_nn_dims *output_dims, int8_t *output)

riscv_nmsis_nn_status **riscv_depthwise_conv_s8_opt**(const nmsis_nn_context *ctx, const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input, const nmsis_nn_dims *filter_dims, const int8_t *kernel, const nmsis_nn_dims *bias_dims, const int32_t *bias, const nmsis_nn_dims *output_dims, int8_t *output)

static void **depthwise_conv_u8_mult_4**(const uint8_t *input, const int32_t input_x, const int32_t input_y, const int32_t input_ch, const uint8_t *kernel, const int32_t output_ch, const int32_t ch_mult, const int32_t kernel_x, const int32_t kernel_y, const int32_t pad_x, const int32_t pad_y, const int32_t stride_x, const int32_t stride_y, const int32_t *bias, uint8_t *output, const int32_t output_shift, const int32_t output_mult, const int32_t output_x, const int32_t output_y, const int32_t output_offset, const int32_t input_offset, const int32_t filter_offset, const int32_t output_activation_min, const int32_t output_activation_max) static void **depthwise_conv_u8_generic**(const uint8_t *input, const int32_t input_x, const int32_t input_y, const int32_t input_ch, const uint8_t *kernel, const int32_t output_ch, const int32_t ch_mult, const int32_t kernel_x, const int32_t kernel_y, const int32_t pad_x, const int32_t pad_y, const int32_t stride_x, const int32_t stride_y, const int32_t *bias, uint8_t *output, const int32_t output_shift, const int32_t output_mult, const int32_t output_x, const int32_t output_y, const int32_t output_offset, const int32_t input_offset, const int32_t filter_offset, const int32_t output_activation_min, const int32_t output_activation_max)

riscv_nmsis_nn_status **riscv_depthwise_conv_u8_basic_ver1**(const uint8_t *input, const uint16_t input_x, const uint16_t input_y, const uint16_t input_ch, const uint8_t *kernel, const uint16_t kernel_x, const uint16_t kernel_y, const int16_t ch_mult, const int16_t pad_x, const int16_t pad_y, const int16_t stride_x, const int16_t stride_y, const int16_t dilation_x, const int16_t dilation_y, const int32_t *bias, const int32_t input_offset, const int32_t filter_offset, const int32_t output_offset, uint8_t *output, const uint16_t output_x, const uint16_t output_y, const int32_t output_activation_min, const int32_t output_activation_max, const int32_t output_shift, const int32_t output_mult)

riscv_nmsis_nn_status **riscv_depthwise_conv_wrapper_s16**(const nmsis_nn_context *ctx, const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int16_t *input, const nmsis_nn_dims *filter_dims, const int8_t *filter, const nmsis_nn_dims *bias_dims, const int64_t *bias, const nmsis_nn_dims *output_dims, int16_t *output)

riscv_nmsis_nn_status **riscv_depthwise_conv_wrapper_s8**(const nmsis_nn_context *ctx, const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input, const nmsis_nn_dims *filter_dims, const int8_t *filter, const nmsis_nn_dims *bias_dims, const int32_t *bias, const nmsis_nn_dims *output_dims, int8_t *output)

riscv_nmsis_nn_status **riscv_depthwise_separable_conv_HWC_q7**(const q7_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out, q15_t *bufferA, q7_t *bufferB) riscv_nmsis_nn_status **riscv_depthwise_separable_conv_HWC_q7_nonsquare**(const q7_t *Im_in, const uint16_t dim_im_in_x, const uint16_t dim_im_in_y, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel_x, const uint16_t dim_kernel_y, const uint16_t padding_x, const uint16_t padding_y, const uint16_t stride_x, const uint16_t stride_y, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out_x, const uint16_t dim_im_out_y, q15_t *bufferA, q7_t *bufferB)

group **NNConv**

Collection of convolution, depthwise convolution functions and their variants.

The convolution is implemented in 2 steps: im2col and General Matrix Multiplication(GEMM)

im2col is a process of converting each patch of image data into a column. After im2col, the convolution is computed as matrix-matrix multiplication.

To reduce the memory footprint, the im2col is performed partially. Each iteration, only a few column (i.e., patches) are generated followed by GEMM.

Functions

riscv_nmsis_nn_status **riscv_convolve_1_x_n_s8**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int32_t *bias_data, const nmsis_nn_dims *output_dims, int8_t *output_data)

1xn convolution

- Supported framework : TensorFlow Lite Micro
- The following constrains on the arguments apply
  a. input_dims->n equals 1
  b. ouput_dims->w is a multiple of 4
  c. Explicit constraints(since it is for 1xN convolution) -## input_dims->h equals 1 -## output_dims->h equals 1 -## filter_dims->h equals 1

     Todo:

     Remove constraint on output_dims->w to make the function generic.

Parameters

- **ctx** – **[inout]** Function context that contains the additional buffer if required by the function. riscv_convolve_1_x_n_s8_get_buffer_size will return the buffer_size if required The caller is expected to clear the buffer ,if applicable, for security reasons.
- **conv_params** – **[in]** Convolution parameters (e.g. strides, dilations, pads,…). Range of conv_params->input_offset : [-127, 128] Range of conv_params->output_offset : [-128, 127]
- **quant_params** – **[in]** Per-channel quantization info. It contains the multiplier and shift values to be applied to each output channel
- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN]
- **input_data** – **[in]** Input (activation) data pointer. Data type: int8
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [C_OUT, 1, WK, C_IN] where WK is the horizontal spatial filter dimension
- **filter_data** – **[in]** Filter data pointer. Data type: int8
- **bias_dims** – **[in]** Bias tensor dimensions. Format: [C_OUT]
- **bias_data** – **[in]** Optional bias data pointer. Data type: int32
- **output_dims** – **[in]** Output tensor dimensions. Format: [N, H, W, C_OUT]
- **output_data** – **[out]** Output data pointer. Data type: int8

Returns The function returns either `RISCV_NMSIS_NN_ARG_ERROR` if argument constraints fail. or, `RISCV_NMSIS_NN_SUCCESS` on successful completion.

riscv_nmsis_nn_status **riscv_convolve_1x1_HWC_q7_fast_nonsquare**(const q7_t *Im_in, const uint16_t dim_im_in_x, const uint16_t dim_im_in_y, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel_x, const uint16_t dim_kernel_y, const uint16_t padding_x, const uint16_t padding_y, const uint16_t stride_x, const uint16_t stride_y, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out_x, const uint16_t dim_im_out_y, q15_t *bufferA, q7_t *bufferB)

Fast Q7 version of 1x1 convolution (non-sqaure shape)

This function is optimized for convolution with 1x1 kernel size (i.e., dim_kernel_x=1 and dim_kernel_y=1). It can be used for the second half of MobileNets [1] after depthwise separable convolution.

This function is the version with full list of optimization tricks, but with some constraints: ch_im_in is multiple of 4 ch_im_out is multiple of 2

[1] MobileNets: Efficient Convolutional Neural Networks for Mobile Vision Applications https://arxiv.org/abs/1704.04861

Parameters

- **Im_in** – **[in]** pointer to input tensor
- **dim_im_in_x** – **[in]** input tensor dimention x
- **dim_im_in_y** – **[in]** input tensor dimention y
- **ch_im_in** – **[in]** number of input tensor channels
- **wt** – **[in]** pointer to kernel weights
- **ch_im_out** – **[in]** number of filters, i.e., output tensor channels
- **dim_kernel_x** – **[in]** filter kernel size x
- **dim_kernel_y** – **[in]** filter kernel size y
- **padding_x** – **[in]** padding size x
- **padding_y** – **[in]** padding size y
- **stride_x** – **[in]** convolution stride x
- **stride_y** – **[in]** convolution stride y
- **bias** – **[in]** pointer to bias
- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **Im_out** – **[inout]** pointer to output tensor
- **dim_im_out_x** – **[in]** output tensor dimension x
- **dim_im_out_y** – **[in]** output tensor dimension y
- **bufferA** – **[inout]** pointer to buffer space for input
- **bufferB** – **[inout]** pointer to buffer space for output

Returns The function returns either `RISCV_NMSIS_NN_SIZE_MISMATCH` or `RISCV_NMSIS_NN_SUCCESS` based on the outcome of size checking.

riscv_nmsis_nn_status **riscv_convolve_1x1_s8**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int32_t *bias_data, const nmsis_nn_dims *output_dims, int8_t *output_data)

s8 version for 1x1 convolution with support for non-unity stride values

- Supported framework : TensorFlow Lite Micro
- The following constrains on the arguments apply
  a. conv_params->padding.w = conv_params->padding.h = 0

Parameters

- **ctx** – **[inout]** Function context that contains the additional buffer if required by the function. None is required by this function.

- **conv_params** – **[in]** Convolution parameters (e.g. strides, dilations, pads,…). Range of conv_params->input_offset : [-127, 128] Range of conv_params->output_offset : [-128, 127]
- **quant_params** – **[in]** Per-channel quantization info. It contains the multiplier and shift values to be applied to each output channel
- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN]
- **input_data** – **[in]** Input (activation) data pointer. Data type: int8
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [C_OUT, 1, 1, C_IN]
- **filter_data** – **[in]** Filter data pointer. Data type: int8
- **bias_dims** – **[in]** Bias tensor dimensions. Format: [C_OUT]
- **bias_data** – **[in]** Optional bias data pointer. Data type: int32
- **output_dims** – **[in]** Output tensor dimensions. Format: [N, H, W, C_OUT]
- **output_data** – **[out]** Output data pointer. Data type: int8

Returns The function returns either `RISCV_NMSIS_NN_ARG_ERROR` if argument constraints fail. or, `RISCV_NMSIS_NN_SUCCESS` on successful completion.

riscv_nmsis_nn_status **riscv_convolve_1x1_s8_fast**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int32_t *bias_data, const nmsis_nn_dims *output_dims, int8_t *output_data)

Fast s8 version for 1x1 convolution (non-square shape)

- Supported framework : TensorFlow Lite Micro
- The following constrains on the arguments apply
  a. conv_params->padding.w = conv_params->padding.h = 0
  b. conv_params->stride.w = conv_params->stride.h = 1

- Supported framework : TensorFlow Lite Micro
- The following constrains on the arguments apply
  a. input_dims->c is a multiple of 4
  b. conv_params->padding.w = conv_params->padding.h = 0
  c. conv_params->stride.w = conv_params->stride.h = 1

Parameters

- **ctx** – **[inout]** Function context that contains the additional buffer if required by the function. riscv_convolve_1x1_s8_fast_get_buffer_size will return the buffer_size if required. The caller is expected to clear the buffer ,if applicable, for security reasons.

- **conv_params** – **[in]** Convolution parameters (e.g. strides, dilations, pads,…). Range of conv_params->input_offset : [-127, 128] Range of conv_params->output_offset : [-128, 127]
- **quant_params** – **[in]** Per-channel quantization info. It contains the multiplier and shift values to be applied to each output channel
- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN]
- **input_data** – **[in]** Input (activation) data pointer. Data type: int8
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [C_OUT, 1, 1, C_IN]
- **filter_data** – **[in]** Filter data pointer. Data type: int8
- **bias_dims** – **[in]** Bias tensor dimensions. Format: [C_OUT]
- **bias_data** – **[in]** Optional bias data pointer. Data type: int32
- **output_dims** – **[in]** Output tensor dimensions. Format: [N, H, W, C_OUT]
- **output_data** – **[out]** Output data pointer. Data type: int8
- **ctx** – **[inout]** Function context that contains the additional buffer if required by the function. riscv_convolve_1x1_s8_fast_get_buffer_size will return the buffer_size if required
- **conv_params** – **[in]** Convolution parameters (e.g. strides, dilations, pads,…). Range of conv_params->input_offset : [-127, 128] Range of conv_params->output_offset : [-128, 127]
- **quant_params** – **[in]** Per-channel quantization info. It contains the multiplier and shift values to be applied to each output channel
- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN]
- **input_data** – **[in]** Input (activation) data pointer. Data type: int8
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [C_OUT, 1, 1, C_IN]
- **filter_data** – **[in]** Filter data pointer. Data type: int8
- **bias_dims** – **[in]** Bias tensor dimensions. Format: [C_OUT]
- **bias_data** – **[in]** Optional bias data pointer. Data type: int32
- **output_dims** – **[in]** Output tensor dimensions. Format: [N, H, W, C_OUT]
- **output_data** – **[out]** Output data pointer. Data type: int8

Returns The function returns either `RISCV_NMSIS_NN_ARG_ERROR` if argument constraints fail. or, `RISCV_NMSIS_NN_SUCCESS` on successful completion.

Returns The function returns either `RISCV_NMSIS_NN_SIZE_MISMATCH` if argument constraints fail. or, `RISCV_NMSIS_NN_SUCCESS` on successful completion.

riscv_nmsis_nn_status **riscv_convolve_fast_s16**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int16_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int64_t *bias_data, const nmsis_nn_dims *output_dims, int16_t *output_data)

Optimized s16 convolution function.

a. Supported framework: TensorFlow Lite micro
b. Additional memory is required for optimization. Refer to argument 'ctx' for details.
c. Implementation supports kernel volumes (filter width * filter height * input channels) < 512.

Parameters

- `ctx` – **[inout]** Function context that contains the additional buffer if required by the function. riscv_convolve_fast_s16_get_buffer_size will return the buffer_size if required. The caller is expected to clear the buffer ,if applicable, for security reasons.
- `conv_params` – **[in]** Convolution parameters (e.g. strides, dilations, pads,…). conv_params->input_offset : Not used conv_params->output_offset : Not used
- `quant_params` – **[in]** Per-channel quantization info. It contains the multiplier and shift values to be applied to each output channel
- `input_dims` – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN]
- `input_data` – **[in]** Input (activation) data pointer. Data type: int16
- `filter_dims` – **[in]** Filter tensor dimensions. Format: [C_OUT, HK, WK, C_IN] where HK and WK are the spatial filter dimensions. (filter_dims->w * filter_dims->h * input_dims->c) must not exceed 512
- `filter_data` – **[in]** Filter data pointer. Data type: int8
- `bias_dims` – **[in]** Bias tensor dimensions. Format: [C_OUT]
- `bias_data` – **[in]** Optional bias data pointer. Data type: int64
- `output_dims` – **[in]** Output tensor dimensions. Format: [N, H, W, C_OUT]
- `output_data` – **[out]** Output data pointer. Data type: int16

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

riscv_nmsis_nn_status **`riscv_convolve_HWC_q15_basic`**(const q15_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const q15_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const q15_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q15_t *Im_out, const uint16_t dim_im_out, q15_t *bufferA, q7_t *bufferB)

Basic Q15 convolution function.

Buffer size:

bufferA size: ch_im_in*dim_kernel*dim_kernel

bufferB size: 0

This basic version is designed to work for any input tensor and weight dimension.

Parameters

- `Im_in` – **[in]** pointer to input tensor
- `dim_im_in` – **[in]** input tensor dimention

- **ch_im_in** – **[in]** number of input tensor channels
- **wt** – **[in]** pointer to kernel weights
- **ch_im_out** – **[in]** number of filters, i.e., output tensor channels
- **dim_kernel** – **[in]** filter kernel size
- **padding** – **[in]** padding sizes
- **stride** – **[in]** convolution stride
- **bias** – **[in]** pointer to bias
- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **Im_out** – **[inout]** pointer to output tensor
- **dim_im_out** – **[in]** output tensor dimension
- **bufferA** – **[inout]** pointer to buffer space for input
- **bufferB** – **[inout]** pointer to buffer space for output

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

riscv_nmsis_nn_status **riscv_convolve_HWC_q15_fast**(const q15_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const q15_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const q15_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q15_t *Im_out, const uint16_t dim_im_out, q15_t *bufferA, q7_t *bufferB)

Fast Q15 convolution function.

Buffer size:

bufferA size: 2*ch_im_in*dim_kernel*dim_kernel

bufferB size: 0

Input dimension constraints:

ch_im_in is multiple of 2

ch_im_out is multiple of 2

dim_im_out is a multiple of 2

Parameters

- **Im_in** – **[in]** pointer to input tensor
- **dim_im_in** – **[in]** input tensor dimention
- **ch_im_in** – **[in]** number of input tensor channels
- **wt** – **[in]** pointer to kernel weights
- **ch_im_out** – **[in]** number of filters, i.e., output tensor channels
- **dim_kernel** – **[in]** filter kernel size
- **padding** – **[in]** padding sizes
- **stride** – **[in]** convolution stride

- **bias** – **[in]** pointer to bias
- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **Im_out** – **[inout]** pointer to output tensor
- **dim_im_out** – **[in]** output tensor dimension
- **bufferA** – **[inout]** pointer to buffer space for input
- **bufferB** – **[inout]** pointer to buffer space for output

Returns The function returns either RISCV_NMSIS_NN_SIZE_MISMATCH or RISCV_NMSIS_NN_SUCCESS based on the outcome of size checking.

riscv_nmsis_nn_status **riscv_convolve_HWC_q15_fast_nonsquare**(const q15_t *Im_in, const uint16_t dim_im_in_x, const uint16_t dim_im_in_y, const uint16_t ch_im_in, const q15_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel_x, const uint16_t dim_kernel_y, const uint16_t padding_x, const uint16_t padding_y, const uint16_t stride_x, const uint16_t stride_y, const q15_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q15_t *Im_out, const uint16_t dim_im_out_x, const uint16_t dim_im_out_y, q15_t *bufferA, q7_t *bufferB)

Fast Q15 convolution function (non-sqaure shape)

Buffer size:

bufferA size: 2*ch_im_in*dim_kernel*dim_kernel

bufferB size: 0

Input dimension constraints:

ch_im_in is multiple of 2

ch_im_out is multiple of 2

Parameters

- **Im_in** – **[in]** pointer to input tensor
- **dim_im_in_x** – **[in]** input tensor dimention x
- **dim_im_in_y** – **[in]** input tensor dimention y
- **ch_im_in** – **[in]** number of input tensor channels
- **wt** – **[in]** pointer to kernel weights
- **ch_im_out** – **[in]** number of filters, i.e., output tensor channels
- **dim_kernel_x** – **[in]** filter kernel size x
- **dim_kernel_y** – **[in]** filter kernel size y
- **padding_x** – **[in]** padding size x

- **padding_y** – **[in]** padding size y
- **stride_x** – **[in]** convolution stride x
- **stride_y** – **[in]** convolution stride y
- **bias** – **[in]** pointer to bias
- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **Im_out** – **[inout]** pointer to output tensor
- **dim_im_out_x** – **[in]** output tensor dimension x
- **dim_im_out_y** – **[in]** output tensor dimension y
- **bufferA** – **[inout]** pointer to buffer space for input
- **bufferB** – **[inout]** pointer to buffer space for output

Returns The function returns either `RISCV_NMSIS_NN_SIZE_MISMATCH` or `RISCV_NMSIS_NN_SUCCESS` based on the outcome of size checking.

riscv_nmsis_nn_status **riscv_convolve_HWC_q7_basic**(const q7_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out, q15_t *bufferA, q7_t *bufferB)

Basic Q7 convolution function.

Buffer size:

bufferA size: 2*ch_im_in*dim_kernel*dim_kernel

bufferB size: 0

This basic version is designed to work for any input tensor and weight dimension.

Parameters

- **Im_in** – **[in]** pointer to input tensor
- **dim_im_in** – **[in]** input tensor dimention
- **ch_im_in** – **[in]** number of input tensor channels
- **wt** – **[in]** pointer to kernel weights
- **ch_im_out** – **[in]** number of filters, i.e., output tensor channels
- **dim_kernel** – **[in]** filter kernel size
- **padding** – **[in]** padding sizes
- **stride** – **[in]** convolution stride
- **bias** – **[in]** pointer to bias
- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **Im_out** – **[inout]** pointer to output tensor
- **dim_im_out** – **[in]** output tensor dimension

- **bufferA** – **[inout]** pointer to buffer space for input
- **bufferB** – **[inout]** pointer to buffer space for output

Returns The function returns RISCV_NMSIS_NN_SUCCESS

riscv_nmsis_nn_status **riscv_convolve_HWC_q7_basic_nonsquare**(const q7_t *Im_in, const uint16_t dim_im_in_x, const uint16_t dim_im_in_y, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel_x, const uint16_t dim_kernel_y, const uint16_t padding_x, const uint16_t padding_y, const uint16_t stride_x, const uint16_t stride_y, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out_x, const uint16_t dim_im_out_y, q15_t *bufferA, q7_t *bufferB)

Basic Q7 convolution function (non-sqaure shape)

Basic Q7 convolution function (non-square shape)

Parameters

- **Im_in** – **[in]** pointer to input tensor
- **dim_im_in_x** – **[in]** input tensor dimention x
- **dim_im_in_y** – **[in]** input tensor dimention y
- **ch_im_in** – **[in]** number of input tensor channels
- **wt** – **[in]** pointer to kernel weights
- **ch_im_out** – **[in]** number of filters, i.e., output tensor channels
- **dim_kernel_x** – **[in]** filter kernel size x
- **dim_kernel_y** – **[in]** filter kernel size y
- **padding_x** – **[in]** padding size x
- **padding_y** – **[in]** padding size y
- **stride_x** – **[in]** convolution stride x
- **stride_y** – **[in]** convolution stride y
- **bias** – **[in]** pointer to bias
- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **Im_out** – **[inout]** pointer to output tensor
- **dim_im_out_x** – **[in]** output tensor dimension x
- **dim_im_out_y** – **[in]** output tensor dimension y
- **bufferA** – **[inout]** pointer to buffer space for input
- **bufferB** – **[inout]** pointer to buffer space for output

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

riscv_nmsis_nn_status **riscv_convolve_HWC_q7_fast**(const q7_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out, q15_t *bufferA, q7_t *bufferB)

Fast Q7 convolution function.

Buffer size:

bufferA size: 2*ch_im_in*dim_kernel*dim_kernel

bufferB size: 0

Input dimension constraints:

ch_im_in is multiple of 4 (because of the SIMD32 read and swap)

ch_im_out is multiple of 2 (bacause 2x2 mat_mult kernel)

The im2col converts the Q7 tensor input into Q15 column, which is stored in bufferA. There is reordering happenning during this im2col process with riscv_q7_to_q15_reordered_no_shift. For every four elements, the second and third elements are swapped.

The computation kernel riscv_nn_mat_mult_kernel_q7_q15_reordered does the GEMM computation with the reordered columns.

To speed-up the determination of the padding condition, we split the computation into 3x3 parts, i.e., {top, mid, bottom} X {left, mid, right}. This reduces the total number of boundary condition checks and improves the data copying performance.

Parameters

- **Im_in** – **[in]** pointer to input tensor
- **dim_im_in** – **[in]** input tensor dimention
- **ch_im_in** – **[in]** number of input tensor channels
- **wt** – **[in]** pointer to kernel weights
- **ch_im_out** – **[in]** number of filters, i.e., output tensor channels
- **dim_kernel** – **[in]** filter kernel size
- **padding** – **[in]** padding sizes
- **stride** – **[in]** convolution stride
- **bias** – **[in]** pointer to bias
- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **Im_out** – **[inout]** pointer to output tensor
- **dim_im_out** – **[in]** output tensor dimension
- **bufferA** – **[inout]** pointer to buffer space for input
- **bufferB** – **[inout]** pointer to buffer space for output

Returns The function returns either `RISCV_NMSIS_NN_SIZE_MISMATCH` or `RISCV_NMSIS_NN_SUCCESS` based on the outcome of size checking.

riscv_nmsis_nn_status **riscv_convolve_HWC_q7_fast_nonsquare**(const q7_t *Im_in, const uint16_t dim_im_in_x, const uint16_t dim_im_in_y, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel_x, const uint16_t dim_kernel_y, const uint16_t padding_x, const uint16_t padding_y, const uint16_t stride_x, const uint16_t stride_y, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out_x, const uint16_t dim_im_out_y, q15_t *bufferA, q7_t *bufferB)

Fast Q7 convolution function (non-sqaure shape)

This function is the version with full list of optimization tricks, but with some constraints: ch_im_in is multiple of 4 ch_im_out is multiple of 2

Parameters

- **Im_in** – **[in]** pointer to input tensor
- **dim_im_in_x** – **[in]** input tensor dimention x
- **dim_im_in_y** – **[in]** input tensor dimention y
- **ch_im_in** – **[in]** number of input tensor channels
- **wt** – **[in]** pointer to kernel weights
- **ch_im_out** – **[in]** number of filters, i.e., output tensor channels
- **dim_kernel_x** – **[in]** filter kernel size x
- **dim_kernel_y** – **[in]** filter kernel size y
- **padding_x** – **[in]** padding size x
- **padding_y** – **[in]** padding size y
- **stride_x** – **[in]** convolution stride x
- **stride_y** – **[in]** convolution stride y
- **bias** – **[in]** pointer to bias
- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **Im_out** – **[inout]** pointer to output tensor
- **dim_im_out_x** – **[in]** output tensor dimension x
- **dim_im_out_y** – **[in]** output tensor dimension y
- **bufferA** – **[inout]** pointer to buffer space for input
- **bufferB** – **[inout]** pointer to buffer space for output

Returns The function returns either `RISCV_NMSIS_NN_SIZE_MISMATCH` or `RISCV_NMSIS_NN_SUCCESS` based on the outcome of size checking.

riscv_nmsis_nn_status **riscv_convolve_HWC_q7_RGB**(const q7_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out, q15_t *bufferA, q7_t *bufferB)

Q7 convolution function for RGB image.

Q7 version of convolution for RGB image.

Buffer size:

bufferA size: 2*ch_im_in*dim_kernel*dim_kernel

bufferB size: 0

Input dimension constraints:

ch_im_in equals 3

This kernel is written exclusively for convolution with ch_im_in equals 3. This applies on the first layer of CNNs which has input image with RGB format.

Parameters

- **Im_in** – **[in]** pointer to input tensor
- **dim_im_in** – **[in]** input tensor dimention
- **ch_im_in** – **[in]** number of input tensor channels
- **wt** – **[in]** pointer to kernel weights
- **ch_im_out** – **[in]** number of filters, i.e., output tensor channels
- **dim_kernel** – **[in]** filter kernel size
- **padding** – **[in]** padding sizes
- **stride** – **[in]** convolution stride
- **bias** – **[in]** pointer to bias
- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **Im_out** – **[inout]** pointer to output tensor
- **dim_im_out** – **[in]** output tensor dimension
- **bufferA** – **[inout]** pointer to buffer space for input
- **bufferB** – **[inout]** pointer to buffer space for output

Returns The function returns either `RISCV_NMSIS_NN_SIZE_MISMATCH` or `RISCV_NMSIS_NN_SUCCESS` based on the outcome of size checking.

riscv_nmsis_nn_status **riscv_convolve_s16**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int16_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int64_t *bias_data, const nmsis_nn_dims *output_dims, int16_t *output_data)

Basic s16 convolution function.

a. Supported framework: TensorFlow Lite micro

b. Additional memory is required for optimization. Refer to argument 'ctx' for details.

Parameters

- **ctx** – **[inout]** Function context that contains the additional buffer if required by the function. riscv_convolve_s16_get_buffer_size will return the buffer_size if required. The caller is expected to clear the buffer ,if applicable, for security reasons.
- **conv_params** – **[in]** Convolution parameters (e.g. strides, dilations, pads,…). conv_params->input_offset : Not used conv_params->output_offset : Not used
- **quant_params** – **[in]** Per-channel quantization info. It contains the multiplier and shift values to be applied to each output channel
- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN]
- **input_data** – **[in]** Input (activation) data pointer. Data type: int16
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [C_OUT, HK, WK, C_IN] where HK and WK are the spatial filter dimensions
- **filter_data** – **[in]** Filter data pointer. Data type: int8
- **bias_dims** – **[in]** Bias tensor dimensions. Format: [C_OUT]
- **bias_data** – **[in]** Optional bias data pointer. Data type: int64
- **output_dims** – **[in]** Output tensor dimensions. Format: [N, H, W, C_OUT]
- **output_data** – **[out]** Output data pointer. Data type: int16

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

riscv_nmsis_nn_status **riscv_convolve_s8**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int32_t *bias_data, const nmsis_nn_dims *output_dims, int8_t *output_data)

Basic s8 convolution function.

a. Supported framework: TensorFlow Lite micro

b. Additional memory is required for optimization. Refer to argument 'ctx' for details.

Parameters

- `ctx` – **[inout]** Function context that contains the additional buffer if required by the function. riscv_convolve_s8_get_buffer_size will return the buffer_size if required. The caller is expected to clear the buffer ,if applicable, for security reasons.
- `conv_params` – **[in]** Convolution parameters (e.g. strides, dilations, pads,…). Range of conv_params->input_offset : [-127, 128] Range of conv_params->output_offset : [-128, 127]
- `quant_params` – **[in]** Per-channel quantization info. It contains the multiplier and shift values to be applied to each output channel
- `input_dims` – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN]
- `input_data` – **[in]** Input (activation) data pointer. Data type: int8
- `filter_dims` – **[in]** Filter tensor dimensions. Format: [C_OUT, HK, WK, C_IN] where HK and WK are the spatial filter dimensions
- `filter_data` – **[in]** Filter data pointer. Data type: int8
- `bias_dims` – **[in]** Bias tensor dimensions. Format: [C_OUT]
- `bias_data` – **[in]** Optional bias data pointer. Data type: int32
- `output_dims` – **[in]** Output tensor dimensions. Format: [N, H, W, C_OUT]
- `output_data` – **[out]** Output data pointer. Data type: int8

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

riscv_nmsis_nn_status **`riscv_convolve_wrapper_s16`**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int16_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int64_t *bias_data, const nmsis_nn_dims *output_dims, int16_t *output_data)

s16 convolution layer wrapper function with the main purpose to call the optimal kernel available in nmsis-nn to perform the convolution.

Parameters

- `ctx` – **[inout]** Function context that contains the additional buffer if required by the function. riscv_convolve_wrapper_s8_get_buffer_size will return the buffer_size if required The caller is expected to clear the buffer ,if applicable, for security reasons.
- `conv_params` – **[in]** Convolution parameters (e.g. strides, dilations, pads,…). conv_params->input_offset : Not used conv_params->output_offset : Not used
- `quant_params` – **[in]** Per-channel quantization info. It contains the multiplier and shift values to be applied to each output channel
- `input_dims` – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN]
- `input_data` – **[in]** Input (activation) data pointer. Data type: int16
- `filter_dims` – **[in]** Filter tensor dimensions. Format: [C_OUT, HK, WK, C_IN] where HK and WK are the spatial filter dimensions
- `filter_data` – **[in]** Filter data pointer. Data type: int8
- `bias_dims` – **[in]** Bias tensor dimensions. Format: [C_OUT]

- **bias_data** – **[in]** Bias data pointer. Data type: int64
- **output_dims** – **[in]** Output tensor dimensions. Format: [N, H, W, C_OUT]
- **output_data** – **[out]** Output data pointer. Data type: int16

Returns The function returns either `RISCV_NMSIS_NN_ARG_ERROR` if argument constraints fail. or, `RISCV_NMSIS_NN_SUCCESS` on successful completion.

riscv_nmsis_nn_status **riscv_convolve_wrapper_s8**(const nmsis_nn_context *ctx, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input_data, const nmsis_nn_dims *filter_dims, const int8_t *filter_data, const nmsis_nn_dims *bias_dims, const int32_t *bias_data, const nmsis_nn_dims *output_dims, int8_t *output_data)

s8 convolution layer wrapper function with the main purpose to call the optimal kernel available in nmsis-nn to perform the convolution.

Parameters

- **ctx** – **[inout]** Function context that contains the additional buffer if required by the function. riscv_convolve_wrapper_s8_get_buffer_size will return the buffer_size if required. The caller is expected to clear the buffer ,if applicable, for security reasons.
- **conv_params** – **[in]** Convolution parameters (e.g. strides, dilations, pads,…). Range of conv_params->input_offset : [-127, 128] Range of conv_params->output_offset : [-128, 127]
- **quant_params** – **[in]** Per-channel quantization info. It contains the multiplier and shift values to be applied to each output channel
- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN]
- **input_data** – **[in]** Input (activation) data pointer. Data type: int8
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [C_OUT, HK, WK, C_IN] where HK and WK are the spatial filter dimensions
- **filter_data** – **[in]** Filter data pointer. Data type: int8
- **bias_dims** – **[in]** Bias tensor dimensions. Format: [C_OUT]
- **bias_data** – **[in]** Bias data pointer. Data type: int32
- **output_dims** – **[in]** Output tensor dimensions. Format: [N, H, W, C_OUT]
- **output_data** – **[out]** Output data pointer. Data type: int8

Returns The function returns either `RISCV_NMSIS_NN_ARG_ERROR` if argument constraints fail. or, `RISCV_NMSIS_NN_SUCCESS` on successful completion.

riscv_nmsis_nn_status **riscv_depthwise_conv_3x3_s8**(const nmsis_nn_context *ctx, const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input, const nmsis_nn_dims *filter_dims, const int8_t *kernel, const nmsis_nn_dims *bias_dims, const int32_t *bias, const nmsis_nn_dims *output_dims, int8_t *output)

Optimized s8 depthwise convolution function for 3x3 kernel size with some constraints on the input arguments(documented below). Refer riscv_depthwise_conv_s8() for function argument details.

- Supported framework : TensorFlow Lite Micro
- The following constrains on the arguments apply
  a. Number of input channel equals number of output channels
  b. Filter height and width equals 3
  c. Padding along x is either 0 or 1.

Returns The function returns one of the following `RISCV_NMSIS_NN_ARG_ERROR` - Unsupported dimension of tensors

- Unsupported pad size along the x axis `RISCV_NMSIS_NN_SUCCESS` - Successful operation

riscv_nmsis_nn_status **riscv_depthwise_conv_fast_s16**(const nmsis_nn_context *ctx, const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int16_t *input, const nmsis_nn_dims *filter_dims, const int8_t *kernel, const nmsis_nn_dims *bias_dims, const int64_t *bias, const nmsis_nn_dims *output_dims, int16_t *output)

Optimized s16 depthwise convolution function with constraint that in_channel equals out_channel. Refer riscv_depthwise_conv_s16() for function argument details.

`RISCV_NMSIS_NN_SUCCESS` - Successful operation

- Supported framework: TensorFlow Lite
- The following constrains on the arguments apply
  a. Number of input channel equals number of output channels or ch_mult equals 1
- Reccomended when number of channels is 4 or greater.

Returns The function returns one of the following `RISCV_NMSIS_NN_ARG_ERROR` - ctx-buff == NULL and riscv_depthwise_conv_fast_s16_get_buffer_size() > 0 or input channel != output channel or ch_mult != 1

static void __attribute__ ((unused))

static void **depthwise_conv_s16_generic_s16**(const int16_t *input, const uint16_t input_batches, const uint16_t input_x, const uint16_t input_y, const uint16_t input_ch, const int8_t *kernel, const uint16_t ch_mult, const uint16_t kernel_x, const uint16_t kernel_y, const uint16_t pad_x, const uint16_t pad_y, const uint16_t stride_x, const uint16_t stride_y, const int64_t *bias, int16_t *output, const int32_t *output_shift, const int32_t *output_mult, const uint16_t output_x, const uint16_t output_y, const int32_t output_activation_min, const int32_t output_activation_max, const uint16_t dilation_x, const uint16_t dilation_y)

riscv_nmsis_nn_status **riscv_depthwise_conv_s16**(const nmsis_nn_context *ctx, const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int16_t *input, const nmsis_nn_dims *filter_dims, const int8_t *kernel, const nmsis_nn_dims *bias_dims, const int64_t *bias, const nmsis_nn_dims *output_dims, int16_t *output)

Basic s16 depthwise convolution function that doesn't have any constraints on the input dimensions.

- Supported framework: TensorFlow Lite

Parameters

- `ctx` – **[inout]** Function context (e.g. temporary buffer). Check the function definition file to see if an additional buffer is required. Optional function {API}_get_buffer_size() provides the buffer size if an additional buffer is required. exists if additional memory is. The caller is expected to clear the buffer ,if applicable, for security reasons.
- `dw_conv_params` – **[in]** Depthwise convolution parameters (e.g. strides, dilations, pads,…) conv_params->input_offset : Not used conv_params->output_offset : Not used
- `quant_params` – **[in]** Per-channel quantization info. It contains the multiplier and shift values to be applied to each output channel
- `input_dims` – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN] Batch argument N is not used.
- `input_data` – **[in]** Input (activation) data pointer. Data type: int8
- `filter_dims` – **[in]** Filter tensor dimensions. Format: [1, H, W, C_OUT]
- `filter_data` – **[in]** Filter data pointer. Data type: int8
- `bias_dims` – **[in]** Bias tensor dimensions. Format: [C_OUT]
- `bias_data` – **[in]** Bias data pointer. Data type: int64
- `output_dims` – **[in]** Output tensor dimensions. Format: [N, H, W, C_OUT]
- `output_data` – **[inout]** Output data pointer. Data type: int16

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

static void **depthwise_conv_s8_mult_4**(const int8_t *input, const int32_t input_x, const int32_t input_y, const int32_t input_ch, const int8_t *kernel, const int32_t output_ch, const int32_t ch_mult, const int32_t kernel_x, const int32_t kernel_y, const int32_t pad_x, const int32_t pad_y, const int32_t stride_x, const int32_t stride_y, const int32_t *bias, int8_t *output, const int32_t *output_shift, const int32_t *output_mult, const int32_t output_x, const int32_t output_y, const int32_t output_offset, const int32_t input_offset, const int32_t output_activation_min, const int32_t output_activation_max)

static void **depthwise_conv_s8_generic**(const int8_t *input, const uint16_t input_batches, const uint16_t input_x, const uint16_t input_y, const uint16_t input_ch, const int8_t *kernel, const uint16_t output_ch, const uint16_t ch_mult, const uint16_t kernel_x, const uint16_t kernel_y, const uint16_t pad_x, const uint16_t pad_y, const uint16_t stride_x, const uint16_t stride_y, const int32_t *bias, int8_t *output, const int32_t *output_shift, const int32_t *output_mult, const uint16_t output_x, const uint16_t output_y, const int32_t output_offset, const int32_t input_offset, const int32_t output_activation_min, const int32_t output_activation_max, const uint16_t dilation_x, const uint16_t dilation_y)

riscv_nmsis_nn_status **riscv_depthwise_conv_s8**(const nmsis_nn_context *ctx, const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input, const nmsis_nn_dims *filter_dims, const int8_t *kernel, const nmsis_nn_dims *bias_dims, const int32_t *bias, const nmsis_nn_dims *output_dims, int8_t *output)

Basic s8 depthwise convolution function that doesn't have any constraints on the input dimensions.

- Supported framework: TensorFlow Lite

Parameters

- **ctx** – **[inout]** Function context (e.g. temporary buffer). Check the function definition file to see if an additional buffer is required. Optional function {API}_get_buffer_size() provides the buffer size if an additional buffer is required exists if additional memory is. The caller is expected to clear the buffer ,if applicable, for security reasons.
- **dw_conv_params** – **[in]** Depthwise convolution parameters (e.g. strides, dilations, pads,…) dw_conv_params->dilation is not used. Range of dw_conv_params->input_offset : [-127, 128] Range of dw_conv_params->input_offset : [-128, 127]
- **quant_params** – **[in]** Per-channel quantization info. It contains the multiplier and shift values to be applied to each output channel
- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN] Batch argument N is not used.
- **input_data** – **[in]** Input (activation) data pointer. Data type: int8
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [1, H, W, C_OUT]
- **filter_data** – **[in]** Filter data pointer. Data type: int8
- **bias_dims** – **[in]** Bias tensor dimensions. Format: [C_OUT]

- **bias_data** – **[in]** Bias data pointer. Data type: int32
- **output_dims** – **[in]** Output tensor dimensions. Format: [N, H, W, C_OUT]
- **output_data** – **[inout]** Output data pointer. Data type: int8

Returns The function returns RISCV_NMSIS_NN_SUCCESS

riscv_nmsis_nn_status **riscv_depthwise_conv_s8_opt**(const nmsis_nn_context *ctx, const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input, const nmsis_nn_dims *filter_dims, const int8_t *kernel, const nmsis_nn_dims *bias_dims, const int32_t *bias, const nmsis_nn_dims *output_dims, int8_t *output)

Optimized s8 depthwise convolution function with constraint that in_channel equals out_channel. Refer riscv_depthwise_conv_s8() for function argument details.

- Supported framework: TensorFlow Lite
- The following constrains on the arguments apply
  a. Number of input channel equals number of output channels or ch_mult equals 1
- Reccomended when number of channels is 4 or greater.

Note: If number of channels is not a multiple of 4, upto 3 elements outside the boundary will be read out for the following if MVE optimizations(Arm Helium Technology) are used.

- Output shift
- Output multiplier
- Output bias
- kernel

Returns The function returns one of the following RISCV_NMSIS_NN_ARG_ERROR - input channel != output channel or ch_mult != 1 RISCV_NMSIS_NN_SUCCESS - Successful operation

static void **depthwise_conv_u8_mult_4**(const uint8_t *input, const int32_t input_x, const int32_t input_y, const int32_t input_ch, const uint8_t *kernel, const int32_t output_ch, const int32_t ch_mult, const int32_t kernel_x, const int32_t kernel_y, const int32_t pad_x, const int32_t pad_y, const int32_t stride_x, const int32_t stride_y, const int32_t *bias, uint8_t *output, const int32_t output_shift, const int32_t output_mult, const int32_t output_x, const int32_t output_y, const int32_t output_offset, const int32_t input_offset, const int32_t filter_offset, const int32_t output_activation_min, const int32_t output_activation_max) static void **depthwise_conv_u8_generic**(const uint8_t *input, const int32_t input_x, const int32_t input_y, const int32_t input_ch, const uint8_t *kernel, const int32_t output_ch, const int32_t ch_mult, const int32_t kernel_x, const int32_t kernel_y, const int32_t pad_x, const int32_t pad_y, const int32_t stride_x, const int32_t stride_y, const int32_t *bias, uint8_t *output, const int32_t output_shift, const int32_t output_mult, const int32_t output_x, const int32_t output_y, const int32_t output_offset, const int32_t input_offset, const int32_t filter_offset, const int32_t output_activation_min, const int32_t output_activation_max)

riscv_nmsis_nn_status **riscv_depthwise_conv_u8_basic_ver1**(const uint8_t *input, const uint16_t input_x, const uint16_t input_y, const uint16_t input_ch, const uint8_t *kernel, const uint16_t kernel_x, const uint16_t kernel_y, const int16_t ch_mult, const int16_t pad_x, const int16_t pad_y, const int16_t stride_x, const int16_t stride_y, const int16_t dilation_x, const int16_t dilation_y, const int32_t *bias, const int32_t input_offset, const int32_t filter_offset, const int32_t output_offset, uint8_t *output, const uint16_t output_x, const uint16_t output_y, const int32_t output_activation_min, const int32_t output_activation_max, const int32_t output_shift, const int32_t output_mult)

uint8 depthwise convolution function with asymmetric quantization

uint8 depthwise convolution function with asymmetric quantization Unless specified otherwise, arguments are mandatory.

Parameters

- **input** – **[in]** Pointer to input tensor
- **input_x** – **[in]** Width of input tensor
- **input_y** – **[in]** Height of input tensor
- **input_ch** – **[in]** Channels in input tensor
- **kernel** – **[in]** Pointer to kernel weights
- **kernel_x** – **[in]** Width of kernel
- **kernel_y** – **[in]** Height of kernel
- **ch_mult** – **[in]** Number of channel multiplier
- **pad_x** – **[in]** Padding sizes x
- **pad_y** – **[in]** Padding sizes y
- **stride_x** – **[in]** Convolution stride along the width
- **stride_y** – **[in]** Convolution stride along the height
- **dilation_x** – **[in]** Dilation along width. Not used and intended for future enhancement.
- **dilation_y** – **[in]** Dilation along height. Not used and intended for future enhancement.

- **bias** – **[in]** Pointer to optional bias values. If no bias is available, NULL is expected
- **input_offset** – **[in]** Input tensor zero offset
- **filter_offset** – **[in]** Kernel tensor zero offset
- **output_offset** – **[in]** Output tensor zero offset
- **output** – **[inout]** Pointer to output tensor
- **output_x** – **[in]** Width of output tensor
- **output_y** – **[in]** Height of output tensor
- **output_activation_min** – **[in]** Minimum value to clamp the output to. Range : {0, 255}
- **output_activation_max** – **[in]** Minimum value to clamp the output to. Range : {0, 255}
- **output_shift** – **[in]** Amount of right-shift for output
- **output_mult** – **[in]** Output multiplier for requantization

Returns The function returns one of the following `RISCV_NMSIS_NN_SIZE_MISMATCH` - Not supported dimension of tensors `RISCV_NMSIS_NN_SUCCESS` - Successful operation `RISCV_NMSIS_NN_ARG_ERROR` - Implementation not available

riscv_nmsis_nn_status **riscv_depthwise_conv_wrapper_s16**(const nmsis_nn_context *ctx, const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int16_t *input, const nmsis_nn_dims *filter_dims, const int8_t *filter, const nmsis_nn_dims *bias_dims, const int64_t *bias, const nmsis_nn_dims *output_dims, int16_t *output)

Wrapper function to pick the right optimized s16 depthwise convolution function.

- Supported framework: TensorFlow Lite
- Picks one of the the following functions
  a. riscv_depthwise_conv_s16()
  b. riscv_depthwise_conv_fast_s16() - RISC-V CPUs with DSP extension only

Parameters

- **ctx** – **[inout]** Function context (e.g. temporary buffer). Check the function definition file to see if an additional buffer is required. Optional function {API}_get_buffer_size() provides the buffer size if required. The caller is expected to clear the buffer ,if applicable, for security reasons.
- **dw_conv_params** – **[in]** Depthwise convolution parameters (e.g. strides, dilations, pads,…) dw_conv_params->dilation is not used. Range of dw_conv_params->input_offset : Not used Range of dw_conv_params->output_offset : Not used
- **quant_params** – **[in]** Per-channel quantization info. It contains the multiplier and shift values to be applied to each output channel

- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [H, W, C_IN] Batch argument N is not used and assumed to be 1.
- **input_data** – **[in]** Input (activation) data pointer. Data type: int16
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [1, H, W, C_OUT]
- **filter_data** – **[in]** Filter data pointer. Data type: int8
- **bias_dims** – **[in]** Bias tensor dimensions. Format: [C_OUT]
- **bias_data** – **[in]** Bias data pointer. Data type: int64
- **output_dims** – **[in]** Output tensor dimensions. Format: [1, H, W, C_OUT]
- **output_data** – **[inout]** Output data pointer. Data type: int16

Returns The function returns `RISCV_NMSIS_NN_SUCCESS` - Successful completion.

riscv_nmsis_nn_status **riscv_depthwise_conv_wrapper_s8**(const nmsis_nn_context *ctx, const nmsis_nn_dw_conv_params *dw_conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input, const nmsis_nn_dims *filter_dims, const int8_t *filter, const nmsis_nn_dims *bias_dims, const int32_t *bias, const nmsis_nn_dims *output_dims, int8_t *output)

Wrapper function to pick the right optimized s8 depthwise convolution function.

- Supported framework: TensorFlow Lite
- Picks one of the the following functions
  a. riscv_depthwise_conv_s8()
  b. riscv_depthwise_conv_3x3_s8() - RISC-V CPUs with DSP extension only
  c. riscv_depthwise_conv_s8_opt()
- Check details of riscv_depthwise_conv_s8_opt() for potential data that can be accessed outside of the boundary.

Parameters

- **ctx** – **[inout]** Function context (e.g. temporary buffer). Check the function definition file to see if an additional buffer is required. Optional function {API}_get_buffer_size() provides the buffer size if required. The caller is expected to clear the buffer ,if applicable, for security reasons.
- **dw_conv_params** – **[in]** Depthwise convolution parameters (e.g. strides, dilations, pads,…) dw_conv_params->dilation is not used. Range of dw_conv_params->input_offset : [-127, 128] Range of dw_conv_params->output_offset : [-128, 127]
- **quant_params** – **[in]** Per-channel quantization info. It contains the multiplier and shift values to be applied to each output channel
- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [H, W, C_IN] Batch argument N is not used and assumed to be 1.
- **input_data** – **[in]** Input (activation) data pointer. Data type: int8

- **filter_dims** – **[in]** Filter tensor dimensions. Format: [1, H, W, C_OUT]
- **filter_data** – **[in]** Filter data pointer. Data type: int8
- **bias_dims** – **[in]** Bias tensor dimensions. Format: [C_OUT]
- **bias_data** – **[in]** Bias data pointer. Data type: int32
- **output_dims** – **[in]** Output tensor dimensions. Format: [1, H, W, C_OUT]
- **output_data** – **[inout]** Output data pointer. Data type: int8

Returns The function returns `RISCV_NMSIS_NN_SUCCESS` - Successful completion.

riscv_nmsis_nn_status **riscv_depthwise_separable_conv_HWC_q7**(const q7_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out, q15_t *bufferA, q7_t *bufferB)

Q7 depthwise separable convolution function.

Buffer size:

bufferA size: 2*ch_im_in*dim_kernel*dim_kernel

bufferB size: 0

Input dimension constraints:

ch_im_in equals ch_im_out

Implementation: There are 3 nested loop here: Inner loop: calculate each output value with MAC instruction over an accumulator Mid loop: loop over different output channel Outer loop: loop over different output (x, y)

Parameters

- **Im_in** – **[in]** pointer to input tensor
- **dim_im_in** – **[in]** input tensor dimension
- **ch_im_in** – **[in]** number of input tensor channels
- **wt** – **[in]** pointer to kernel weights
- **ch_im_out** – **[in]** number of filters, i.e., output tensor channels
- **dim_kernel** – **[in]** filter kernel size
- **padding** – **[in]** padding sizes
- **stride** – **[in]** convolution stride
- **bias** – **[in]** pointer to bias
- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **Im_out** – **[inout]** pointer to output tensor
- **dim_im_out** – **[in]** output tensor dimension

- **bufferA** – **[inout]** pointer to buffer space for input
- **bufferB** – **[inout]** pointer to buffer space for output

Returns The function returns either `RISCV_NMSIS_NN_SIZE_MISMATCH` or `RISCV_NMSIS_NN_SUCCESS` based on the outcome of size checking.

riscv_nmsis_nn_status **riscv_depthwise_separable_conv_HWC_q7_nonsquare**(const q7_t *Im_in, const uint16_t dim_im_in_x, const uint16_t dim_im_in_y, const uint16_t ch_im_in, const q7_t *wt, const uint16_t ch_im_out, const uint16_t dim_kernel_x, const uint16_t dim_kernel_y, const uint16_t padding_x, const uint16_t padding_y, const uint16_t stride_x, const uint16_t stride_y, const q7_t *bias, const uint16_t bias_shift, const uint16_t out_shift, q7_t *Im_out, const uint16_t dim_im_out_x, const uint16_t dim_im_out_y, q15_t *bufferA, q7_t *bufferB)

Q7 depthwise separable convolution function (non-square shape)

This function is the version with full list of optimization tricks, but with some constraints: ch_im_in is equal to ch_im_out

Parameters

- **Im_in** – **[in]** pointer to input tensor
- **dim_im_in_x** – **[in]** input tensor dimension x
- **dim_im_in_y** – **[in]** input tensor dimension y
- **ch_im_in** – **[in]** number of input tensor channels
- **wt** – **[in]** pointer to kernel weights
- **ch_im_out** – **[in]** number of filters, i.e., output tensor channels
- **dim_kernel_x** – **[in]** filter kernel size x
- **dim_kernel_y** – **[in]** filter kernel size y
- **padding_x** – **[in]** padding sizes x
- **padding_y** – **[in]** padding sizes y
- **stride_x** – **[in]** convolution stride x
- **stride_y** – **[in]** convolution stride y

- **bias** – **[in]** pointer to bias
- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **Im_out** – **[inout]** pointer to output tensor
- **dim_im_out_x** – **[in]** output tensor dimension x
- **dim_im_out_y** – **[in]** output tensor dimension y
- **bufferA** – **[inout]** pointer to buffer space for input
- **bufferB** – **[inout]** pointer to buffer space for output

Returns The function returns either `RISCV_NMSIS_NN_SIZE_MISMATCH` or `RISCV_NMSIS_NN_SUCCESS` based on the outcome of size checking.

Fully-connected Layer Functions

GetBufferSizeFC

int32_t **riscv_fully_connected_s16_get_buffer_size**(const nmsis_nn_dims *filter_dims)

int32_t **riscv_fully_connected_s16_get_buffer_size_dsp**(const nmsis_nn_dims *filter_dims)

int32_t **riscv_fully_connected_s8_get_buffer_size**(const nmsis_nn_dims *filter_dims)

int32_t **riscv_fully_connected_s8_get_buffer_size_dsp**(const nmsis_nn_dims *filter_dims)

group `GetBufferSizeFC`

Functions

int32_t **riscv_fully_connected_s16_get_buffer_size**(const nmsis_nn_dims *filter_dims)

Get the required buffer size for S16 basic fully-connected and matrix multiplication layer function for TF Lite.

Parameters **filter_dims** – **[in]** dimension of filter

Returns The function returns required buffer size in bytes

int32_t **riscv_fully_connected_s16_get_buffer_size_dsp**(const nmsis_nn_dims *filter_dims)

int32_t **riscv_fully_connected_s8_get_buffer_size**(const nmsis_nn_dims *filter_dims)

Get the required buffer size for S8 basic fully-connected and matrix multiplication layer function for TF Lite.

Parameters **filter_dims** – **[in]** dimension of filter

Returns The function returns required buffer size in bytes

int32_t **riscv_fully_connected_s8_get_buffer_size_dsp**(const nmsis_nn_dims *filter_dims) riscv_nmsis_nn_status **riscv_fully_connected_mat_q7_vec_q15**(const q15_t *pV, const q7_t *pM, const uint16_t dim_vec, const uint16_t num_of_rows, const uint16_t bias_shift, const uint16_t out_shift, const q7_t *bias, q15_t *pOut, q15_t *vec_buffer)

riscv_nmsis_nn_status **riscv_fully_connected_mat_q7_vec_q15_opt**(const q15_t *pV, const q7_t *pM, const uint16_t dim_vec, const uint16_t num_of_rows, const uint16_t bias_shift, const uint16_t out_shift, const q7_t *bias, q15_t *pOut, q15_t *vec_buffer)

riscv_nmsis_nn_status **riscv_fully_connected_q15**(const q15_t *pV, const q15_t *pM, const uint16_t dim_vec, const uint16_t num_of_rows, const uint16_t bias_shift, const uint16_t out_shift, const q15_t *bias, q15_t *pOut, q15_t *vec_buffer)

riscv_nmsis_nn_status **riscv_fully_connected_q15_opt**(const q15_t *pV, const q15_t *pM, const uint16_t dim_vec, const uint16_t num_of_rows, const uint16_t bias_shift, const uint16_t out_shift, const q15_t *bias, q15_t *pOut, q15_t *vec_buffer)

riscv_nmsis_nn_status **riscv_fully_connected_q7**(const q7_t *pV, const q7_t *pM, const uint16_t dim_vec, const uint16_t num_of_rows, const uint16_t bias_shift, const uint16_t out_shift, const q7_t *bias, q7_t *pOut, q15_t *vec_buffer)

riscv_nmsis_nn_status **riscv_fully_connected_q7_opt**(const q7_t *pV, const q7_t *pM, const uint16_t dim_vec, const uint16_t num_of_rows, const uint16_t bias_shift, const uint16_t out_shift, const q7_t *bias, q7_t *pOut, q15_t *vec_buffer)

riscv_nmsis_nn_status **riscv_fully_connected_s16**(const nmsis_nn_context *ctx, const nmsis_nn_fc_params *fc_params, const nmsis_nn_per_tensor_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int16_t *input, const nmsis_nn_dims *filter_dims, const int8_t *kernel, const nmsis_nn_dims *bias_dims, const int64_t *bias, const nmsis_nn_dims *output_dims, int16_t *output)

riscv_nmsis_nn_status **riscv_fully_connected_s8**(const nmsis_nn_context *ctx, const nmsis_nn_fc_params *fc_params, const nmsis_nn_per_tensor_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input, const nmsis_nn_dims *filter_dims, const int8_t *kernel, const nmsis_nn_dims *bias_dims, const int32_t *bias, const nmsis_nn_dims *output_dims, int8_t *output)

group **FC**

Collection of fully-connected and matrix multiplication functions.

Fully-connected layer is basically a matrix-vector multiplication with bias. The matrix is the weights and the input/output vectors are the activation values. Supported {weight, activation} precisions include {8-bit, 8-bit} and {8-bit, 16-bit}

Functions

riscv_nmsis_nn_status **riscv_fully_connected_mat_q7_vec_q15**(const q15_t *pV, const q7_t *pM, const uint16_t dim_vec, const uint16_t num_of_rows, const uint16_t bias_shift, const uint16_t out_shift, const q7_t *bias, q15_t *pOut, q15_t *vec_buffer)

Mixed Q15-Q7 fully-connected layer function.

Buffer size:

vec_buffer size: 0

Q7_Q15 version of the fully connected layer

Weights are in q7_t and Activations are in q15_t

Parameters

- **pV** – **[in]** pointer to input vector
- **pM** – **[in]** pointer to matrix weights
- **dim_vec** – **[in]** length of the vector
- **num_of_rows** – **[in]** number of rows in weight matrix
- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **bias** – **[in]** pointer to bias
- **pOut** – **[inout]** pointer to output vector
- **vec_buffer** – **[inout]** pointer to buffer space for input

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

riscv_nmsis_nn_status **riscv_fully_connected_mat_q7_vec_q15_opt**(const q15_t *pV, const q7_t *pM, const uint16_t dim_vec, const uint16_t num_of_rows, const uint16_t bias_shift, const uint16_t out_shift, const q7_t *bias, q15_t *pOut, q15_t *vec_buffer)

Mixed Q15-Q7 opt fully-connected layer function.

Buffer size:

vec_buffer size: 0

Q7_Q15 version of the fully connected layer

Weights are in q7_t and Activations are in q15_t

Limitation: x4 version requires weight reordering to work

Here we use only one pointer to read 4 rows in the weight matrix. So if the original q7_t matrix looks like this:

| a11 | a12 | a13 | a14 | a15 | a16 | a17 |

| a21 | a22 | a23 | a24 | a25 | a26 | a27 |

| a31 | a32 | a33 | a34 | a35 | a36 | a37 |

| a41 | a42 | a43 | a44 | a45 | a46 | a47 |

| a51 | a52 | a53 | a54 | a55 | a56 | a57 |

| a61 | a62 | a63 | a64 | a65 | a66 | a67 |

We operates on multiple-of-4 rows, so the first four rows becomes

| a11 | a21 | a12 | a22 | a31 | a41 | a32 | a42 |

| a13 | a23 | a14 | a24 | a33 | a43 | a34 | a44 |

| a15 | a25 | a16 | a26 | a35 | a45 | a36 | a46 |

The column left over will be in-order. which is: | a17 | a27 | a37 | a47 |

For the left-over rows, we do 1x1 computation, so the data remains as its original order.

So the stored weight matrix looks like this:

| a11 | a21 | a12 | a22 | a31 | a41 |

| a32 | a42 | a13 | a23 | a14 | a24 |

| a33 | a43 | a34 | a44 | a15 | a25 |

| a16 | a26 | a35 | a45 | a36 | a46 |

| a17 | a27 | a37 | a47 | a51 | a52 |

| a53 | a54 | a55 | a56 | a57 | a61 |

| a62 | a63 | a64 | a65 | a66 | a67 |

Parameters

- **pV** – **[in]** pointer to input vector
- **pM** – **[in]** pointer to matrix weights
- **dim_vec** – **[in]** length of the vector
- **num_of_rows** – **[in]** number of rows in weight matrix
- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **bias** – **[in]** pointer to bias
- **pOut** – **[inout]** pointer to output vector
- **vec_buffer** – **[inout]** pointer to buffer space for input

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

riscv_nmsis_nn_status **riscv_fully_connected_q15**(const q15_t *pV, const q15_t *pM, const uint16_t dim_vec, const uint16_t num_of_rows, const uint16_t bias_shift, const uint16_t out_shift, const q15_t *bias, q15_t *pOut, q15_t *vec_buffer)

Q15 opt fully-connected layer function.

Q15 basic fully-connected layer function.

Buffer size:

vec_buffer size: 0

Parameters

- **pV** – **[in]** pointer to input vector
- **pM** – **[in]** pointer to matrix weights
- **dim_vec** – **[in]** length of the vector
- **num_of_rows** – **[in]** number of rows in weight matrix
- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **bias** – **[in]** pointer to bias
- **pOut** – **[inout]** pointer to output vector
- **vec_buffer** – **[inout]** pointer to buffer space for input

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

riscv_nmsis_nn_status **riscv_fully_connected_q15_opt**(const q15_t *pV, const q15_t *pM, const uint16_t dim_vec, const uint16_t num_of_rows, const uint16_t bias_shift, const uint16_t out_shift, const q15_t *bias, q15_t *pOut, q15_t *vec_buffer)

Q15 opt fully-connected layer function.

Buffer size:

vec_buffer size: 0

Here we use only one pointer to read 4 rows in the weight matrix. So if the original matrix looks like this:

| a11 | a12 | a13 |

| a21 | a22 | a23 |

| a31 | a32 | a33 |

| a41 | a42 | a43 |

| a51 | a52 | a53 |

| a61 | a62 | a63 |

We operates on multiple-of-4 rows, so the first four rows becomes

| a11 | a12 | a21 | a22 | a31 | a32 | a41 | a42 |

| a13 | a23 | a33 | a43 |

Remaining rows are kept the same original order.

So the stored weight matrix looks like this:

| a11 | a12 | a21 | a22 | a31 | a32 | a41 | a42 |

| a13 | a23 | a33 | a43 | a51 | a52 | a53 | a61 |

| a62 | a63 |

Parameters

- **pV** – **[in]** pointer to input vector
- **pM** – **[in]** pointer to matrix weights
- **dim_vec** – **[in]** length of the vector
- **num_of_rows** – **[in]** number of rows in weight matrix

- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **bias** – **[in]** pointer to bias
- **pOut** – **[inout]** pointer to output vector
- **vec_buffer** – **[inout]** pointer to buffer space for input

Returns The function returns RISCV_NMSIS_NN_SUCCESS

riscv_nmsis_nn_status **riscv_fully_connected_q7**(const q7_t *pV, const q7_t *pM, const uint16_t dim_vec, const uint16_t num_of_rows, const uint16_t bias_shift, const uint16_t out_shift, const q7_t *bias, q7_t *pOut, q15_t *vec_buffer)

Q7 basic fully-connected layer function.

Buffer size:

vec_buffer size: dim_vec

This basic function is designed to work with regular weight matrix without interleaving.

Parameters

- **pV** – **[in]** pointer to input vector
- **pM** – **[in]** pointer to matrix weights
- **dim_vec** – **[in]** length of the vector
- **num_of_rows** – **[in]** number of rows in weight matrix
- **bias_shift** – **[in]** amount of left-shift for bias
- **out_shift** – **[in]** amount of right-shift for output
- **bias** – **[in]** pointer to bias
- **pOut** – **[inout]** pointer to output vector
- **vec_buffer** – **[inout]** pointer to buffer space for input

Returns The function returns RISCV_NMSIS_NN_SUCCESS

riscv_nmsis_nn_status **riscv_fully_connected_q7_opt**(const q7_t *pV, const q7_t *pM, const uint16_t dim_vec, const uint16_t num_of_rows, const uint16_t bias_shift, const uint16_t out_shift, const q7_t *bias, q7_t *pOut, q15_t *vec_buffer)

Q7 opt fully-connected layer function.

Buffer size:

vec_buffer size: dim_vec

This opt function is designed to work with interleaved weight matrix. The vector input is assumed in q7_t format, we call riscv_q7_to_q15_no_shift_shuffle function to expand into q15_t format with certain weight re-ordering, refer to the function comments for more details. Here we use only one pointer to read 4 rows in the weight matrix. So if the original q7_t matrix looks like this:

| a11 | a12 | a13 | a14 | a15 | a16 | a17 |

| a21 | a22 | a23 | a24 | a25 | a26 | a27 |

| a31 | a32 | a33 | a34 | a35 | a36 | a37 |

| a41 | a42 | a43 | a44 | a45 | a46 | a47 |

| a51 | a52 | a53 | a54 | a55 | a56 | a57 |

| a61 | a62 | a63 | a64 | a65 | a66 | a67 |

We operates on multiple-of-4 rows, so the first four rows becomes

| a11 | a21 | a13 | a23 | a31 | a41 | a33 | a43 |

| a12 | a22 | a14 | a24 | a32 | a42 | a34 | a44 |

| a15 | a25 | a35 | a45 | a16 | a26 | a36 | a46 |

So within the kernel, we first read the re-ordered vector in as:

| b1 | b3 | and | b2 | b4 |

the four q31_t weights will look like

| a11 | a13 |, | a21 | a23 |, | a31 | a33 |, | a41 | a43 |

| a12 | a14 |, | a22 | a24 |, | a32 | a34 |, | a42 | a44 |

The column left over will be in-order. which is:

| a17 | a27 | a37 | a47 |

For the left-over rows, we do 1x1 computation, so the data remains as its original order.

So the stored weight matrix looks like this:

| a11 | a21 | a13 | a23 | a31 | a41 |

| a33 | a43 | a12 | a22 | a14 | a24 |

| a32 | a42 | a34 | a44 | a15 | a25 |

| a35 | a45 | a16 | a26 | a36 | a46 |

| a17 | a27 | a37 | a47 | a51 | a52 |

| a53 | a54 | a55 | a56 | a57 | a61 |

| a62 | a63 | a64 | a65 | a66 | a67 |

Parameters

- **`pV`** – **[in]** pointer to input vector
- **`pM`** – **[in]** pointer to matrix weights
- **`dim_vec`** – **[in]** length of the vector
- **`num_of_rows`** – **[in]** number of rows in weight matrix
- **`bias_shift`** – **[in]** amount of left-shift for bias
- **`out_shift`** – **[in]** amount of right-shift for output
- **`bias`** – **[in]** pointer to bias
- **`pOut`** – **[inout]** pointer to output vector
- **`vec_buffer`** – **[inout]** pointer to buffer space for input

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

riscv_nmsis_nn_status **riscv_fully_connected_s16**(const nmsis_nn_context *ctx, const nmsis_nn_fc_params *fc_params, const nmsis_nn_per_tensor_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int16_t *input, const nmsis_nn_dims *filter_dims, const int8_t *kernel, const nmsis_nn_dims *bias_dims, const int64_t *bias, const nmsis_nn_dims *output_dims, int16_t *output)

Basic s16 Fully Connected function.

- Supported framework: TensorFlow Lite

Parameters

- **ctx** – **[inout]** Function context (e.g. temporary buffer). Check the function definition file to see if an additional buffer is required. Optional function {API}_get_buffer_size() provides the buffer size if an additional buffer is required. The caller is expected to clear the buffer ,if applicable, for security reasons.
- **fc_params** – **[in]** Fully Connected layer parameters. fc_params->input_offset : 0 fc_params->filter_offset : 0 fc_params->output_offset : 0
- **quant_params** – **[in]** Per-tensor quantization info. It contains the multiplier and shift values to be applied to the output tensor.
- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN] Input dimension is taken as Nx(H * W * C_IN)
- **input_data** – **[in]** Input (activation) data pointer. Data type: int16
- **filter_dims** – **[in]** Two dimensional filter dimensions. Format: [N, C] N : accumulation depth and equals (H * W * C_IN) from input_dims C : output depth and equals C_OUT in output_dims H & W : Not used
- **filter_data** – **[in]** Filter data pointer. Data type: int8
- **bias_dims** – **[in]** Bias tensor dimensions. Format: [C_OUT] N, H, W : Not used
- **bias_data** – **[in]** Bias data pointer. Data type: int64
- **output_dims** – **[in]** Output tensor dimensions. Format: [N, C_OUT] N : Batches C_OUT : Output depth H & W : Not used.
- **output_data** – **[inout]** Output data pointer. Data type: int16

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

riscv_nmsis_nn_status **riscv_fully_connected_s8**(const nmsis_nn_context *ctx, const nmsis_nn_fc_params *fc_params, const nmsis_nn_per_tensor_quant_params *quant_params, const nmsis_nn_dims *input_dims, const int8_t *input, const nmsis_nn_dims *filter_dims, const int8_t *kernel, const nmsis_nn_dims *bias_dims, const int32_t *bias, const nmsis_nn_dims *output_dims, int8_t *output)

Basic s8 Fully Connected function.

- Supported framework: TensorFlow Lite

Parameters

- **ctx** – **[inout]** Function context (e.g. temporary buffer). Check the function definition file to see if an additional buffer is required. Optional function {API}_get_buffer_size() provides the buffer size if an additional buffer is required. The caller is expected to clear the buffer ,if applicable, for security reasons.
- **fc_params** – **[in]** Fully Connected layer parameters. Range of fc_params->input_offset : [-127, 128] fc_params->filter_offset : 0 Range of fc_params->output_offset : [-128, 127]
- **quant_params** – **[in]** Per-tensor quantization info. It contains the multiplier and shift values to be applied to the output tensor.
- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [N, H, W, C_IN] Input dimension is taken as Nx(H * W * C_IN)
- **input_data** – **[in]** Input (activation) data pointer. Data type: int8
- **filter_dims** – **[in]** Two dimensional filter dimensions. Format: [N, C] N : accumulation depth and equals (H * W * C_IN) from input_dims C : output depth and equals C_OUT in output_dims H & W : Not used
- **filter_data** – **[in]** Filter data pointer. Data type: int8
- **bias_dims** – **[in]** Bias tensor dimensions. Format: [C_OUT] N, H, W : Not used
- **bias_data** – **[in]** Bias data pointer. Data type: int32
- **output_dims** – **[in]** Output tensor dimensions. Format: [N, C_OUT] N : Batches C_OUT : Output depth H & W : Not used.
- **output_data** – **[inout]** Output data pointer. Data type: int8

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

LSTM Layer Functions

riscv_nmsis_nn_status **riscv_lstm_unidirectional_s16_s8**(nmsis_nn_lstm_context *scratch_buffers, const int8_t *input_data, const nmsis_nn_lstm_dims *lstm_dims, const int8_t *in_to_in_weights, const int8_t *in_to_forget_weights, const int8_t *in_to_cell_weights, const int8_t *in_to_out_weights, const int8_t *recurrent_to_in_weights, const int8_t *recurrent_to_forget_weights, const int8_t *recurrent_to_cell_weights, const int8_t *recurrent_to_out_weights, const int16_t *cell_to_in_weights, const int16_t *cell_to_forget_weights, const int16_t *cell_to_out_weights, const int8_t *projection_weights, const nmsis_nn_lstm_params *lstm, int8_t *output_state, int16_t *cell_state, int8_t *output_data)

group `LSTM`

Functions

riscv_nmsis_nn_status **riscv_lstm_unidirectional_s16_s8**(nmsis_nn_lstm_context *scratch_buffers, const int8_t *input_data, const nmsis_nn_lstm_dims *lstm_dims, const int8_t *in_to_in_weights, const int8_t *in_to_forget_weights, const int8_t *in_to_cell_weights, const int8_t *in_to_out_weights, const int8_t *recurrent_to_in_weights, const int8_t *recurrent_to_forget_weights, const int8_t *recurrent_to_cell_weights, const int8_t *recurrent_to_out_weights, const int16_t *cell_to_in_weights, const int16_t *cell_to_forget_weights, const int16_t *cell_to_out_weights, const int8_t *projection_weights, const nmsis_nn_lstm_params *lstm, int8_t *output_state, int16_t *cell_state, int8_t *output_data)

LSTM unidirectional function with 8 bit input and output and 16 bit gate output Peephole connections, projection, clipping, combined input/forget gate and layer normalization are not supported.

1 Input to input weight can not be nullptr. Otherwise nullptr for combined input/forgat gate. 2 Cell weights are not used and should be nullptr. Otherwise needed for peephole connections. 3 Projection weight is not used and should be nullpr. Otherwise needed for projection.

a. Supported framework: TensorFlow Lite micro

Note: Following assumptions are done based on LSTM functionality as supported by Keras version 2.9.0 at the time of development. As stated here, https://github.com/tensorflow/community/blob/master/rfcs/20180920-unify-rnn-interface.md Keras's LSTMCell is equivalent to TensorFlow's BasicLSTMCell, which does not support peephole, clipping or projection. Layer normalization and combined input/forget gate are not supported either.

Parameters

- **scratch_buffers** – **[in]** Struct containing scratch buffers Expected size for each scratch buffer is lstm_dims->num_batches * lstm_dims->num_outputs.
- **input_data** – **[in]** Pointer to input data
- **lstm_dims** – **[in]** LSTM input parameters related to dimensions
- **input_to_input_weights** – **[in]** Input to input weights
- **input_to_forget_weights** – **[in]** Input to forget weights
- **input_to_cell_weights** – **[in]** Input to cell weights
- **input_to_output_weights** – **[in]** Input to output weights
- **recurrent_to_input_weights** – **[in]** Recurrent to input weights
- **recurrent_to_forget_weights** – **[in]** Recurrent to forget weights

- **recurrent_to_cell_weights** – **[in]** Recurrent to cell weights
- **recurrent_to_output_weights** – **[in]** Recurrent to output weights
- **cell_to_input_weights** – **[in]** Cell to input weights. Not used.
- **cell_to_forget_weights** – **[in]** Cell to forget weights. Not used.
- **cell_to_output_weights** – **[in]** Cell to output weights. Not used.
- **projection_weights** – **[in]** Projection weights. Not used.
- **lstm** – **[in]** LSTM parameters. See struct declaration
- **output_state** – **[in]** Pointer to (recurrent) output state
- **cell_state** – **[in]** Pointer to cell state
- **output_data** – **[in]** Pointer to output state

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

Pooling Functions

GetBufferSizePooling

int32_t **riscv_avgpool_s16_get_buffer_size**(const int output_x, const int ch_src)

int32_t **riscv_avgpool_s16_get_buffer_size_dsp**(const int output_x, const int ch_src)

int32_t **riscv_avgpool_s8_get_buffer_size**(const int output_x, const int ch_src)

int32_t **riscv_avgpool_s8_get_buffer_size_dsp**(const int output_x, const int ch_src)

group **GetBufferSizePooling**

Functions

int32_t **riscv_avgpool_s16_get_buffer_size**(const int output_x, const int ch_src)

Get the required buffer size for S16 average pooling function.

Parameters

- **dim_dst_width** – **[in]** output tensor dimension
- **ch_src** – **[in]** number of input tensor channels

Returns The function returns required buffer size in bytes

int32_t **riscv_avgpool_s16_get_buffer_size_dsp**(const int output_x, const int ch_src)

Get the required buffer size for S16 average pooling function for processors with DSP extension. Refer to riscv_avgpool_s16_get_buffer_size() for function argument details.

Note: Intended for compilation on Host. If compiling for an Arm target, use riscv_avgpool_s16_get_buffer_size().

int32_t **riscv_avgpool_s8_get_buffer_size**(const int output_x, const int ch_src)

Get the required buffer size for S8 average pooling function.

Parameters

- **dim_dst_width** – **[in]** output tensor dimension
- **ch_src** – **[in]** number of input tensor channels

Returns The function returns required buffer size in bytes

int32_t **riscv_avgpool_s8_get_buffer_size_dsp**(const int output_x, const int ch_src)

Get the required buffer size for S8 average pooling function for processors with DSP extension. Refer to riscv_avgpool_s8_get_buffer_size() for function argument details.

> **Note:** Intended for compilation on Host. If compiling for an Arm target, use riscv_avgpool_s8_get_buffer_size().

riscv_nmsis_nn_status **riscv_avgpool_s16**(const nmsis_nn_context *ctx, const nmsis_nn_pool_params *pool_params, const nmsis_nn_dims *input_dims, const int16_t *src, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims, int16_t *dst)

riscv_nmsis_nn_status **riscv_avgpool_s8**(const nmsis_nn_context *ctx, const nmsis_nn_pool_params *pool_params, const nmsis_nn_dims *input_dims, const int8_t *src, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims, int8_t *dst)

riscv_nmsis_nn_status **riscv_max_pool_s16**(const nmsis_nn_context *ctx, const nmsis_nn_pool_params *pool_params, const nmsis_nn_dims *input_dims, const int16_t *src, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims, int16_t *dst)

riscv_nmsis_nn_status **riscv_max_pool_s8**(const nmsis_nn_context *ctx, const nmsis_nn_pool_params *pool_params, const nmsis_nn_dims *input_dims, const int8_t *src, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims, int8_t *dst)

void **riscv_maxpool_q7_HWC**(q7_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const uint16_t dim_im_out, q7_t *bufferA, q7_t *Im_out)

void **riscv_avepool_q7_HWC**(q7_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const uint16_t dim_im_out, q7_t *bufferA, q7_t *Im_out)

group **Pooling**

Perform pooling functions, including max pooling and average pooling.

Perform max and average pooling operations.

Functions

riscv_nmsis_nn_status **riscv_avgpool_s16**(const nmsis_nn_context *ctx, const nmsis_nn_pool_params *pool_params, const nmsis_nn_dims *input_dims, const int16_t *src, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims, int16_t *dst)

s16 average pooling function.

- Supported Framework: TensorFlow Lite

Parameters

- **ctx** – **[inout]** Function context (e.g. temporary buffer). Check the function definition file to see if an additional buffer is required. Optional function {API}_get_buffer_size() provides the buffer size if an additional buffer is required. The caller is expected to clear the buffer ,if applicable, for security reasons.
- **pool_params** – **[in]** Pooling parameters
- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [H, W, C_IN] Argument 'N' is not used.
- **input_data** – **[in]** Input (activation) data pointer. Data type: int16
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [H, W] Argument N and C are not used.
- **output_dims** – **[in]** Output tensor dimensions. Format: [H, W, C_OUT] Argument N is not used. C_OUT equals C_IN.
- **output_data** – **[inout]** Output data pointer. Data type: int16

Returns The function returns `RISCV_NMSIS_NN_SUCCESS` - Successful operation `RISCV_NMSIS_NN_ARG_ERROR` - In case of invalid arguments

riscv_nmsis_nn_status **riscv_avgpool_s8**(const nmsis_nn_context *ctx, const nmsis_nn_pool_params *pool_params, const nmsis_nn_dims *input_dims, const int8_t *src, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims, int8_t *dst)

s8 average pooling function.

- Supported Framework: TensorFlow Lite

Parameters

- **ctx** – **[inout]** Function context (e.g. temporary buffer). Check the function definition file to see if an additional buffer is required. Optional function {API}_get_buffer_size() provides the buffer size if an additional buffer is required. The caller is expected to clear the buffer ,if applicable, for security reasons.
- **pool_params** – **[in]** Pooling parameters
- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [H, W, C_IN] Argument 'N' is not used.
- **input_data** – **[in]** Input (activation) data pointer. Data type: int8

- `filter_dims` – **[in]** Filter tensor dimensions. Format: [H, W] Argument N and C are not used.
- `output_dims` – **[in]** Output tensor dimensions. Format: [H, W, C_OUT] Argument N is not used. C_OUT equals C_IN.
- `output_data` – **[inout]** Output data pointer. Data type: int8

Returns The function returns `RISCV_NMSIS_NN_SUCCESS` - Successful operation

riscv_nmsis_nn_status **`riscv_max_pool_s16`**(const nmsis_nn_context *ctx, const nmsis_nn_pool_params *pool_params, const nmsis_nn_dims *input_dims, const int16_t *src, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims, int16_t *dst)

s16 max pooling function.

- Supported Framework: TensorFlow Lite

Parameters

- `ctx` – **[inout]** Function context (e.g. temporary buffer). Check the function definition file to see if an additional buffer is required. Optional function {API}_get_buffer_size() provides the buffer size if an additional buffer is required. The caller is expected to clear the buffer ,if applicable, for security reasons.
- `pool_params` – **[in]** Pooling parameters
- `input_dims` – **[in]** Input (activation) tensor dimensions. Format: [H, W, C_IN] Argument 'N' is not used.
- `src` – **[in]** Input (activation) data pointer. The input tensor must not overlap with the output tensor. Data type: int16
- `filter_dims` – **[in]** Filter tensor dimensions. Format: [H, W] Argument N and C are not used.
- `output_dims` – **[in]** Output tensor dimensions. Format: [H, W, C_OUT] Argument N is not used. C_OUT equals C_IN.
- `dst` – **[inout]** Output data pointer. Data type: int16

Returns The function returns `RISCV_NMSIS_NN_SUCCESS` - Successful operation

riscv_nmsis_nn_status **`riscv_max_pool_s8`**(const nmsis_nn_context *ctx, const nmsis_nn_pool_params *pool_params, const nmsis_nn_dims *input_dims, const int8_t *src, const nmsis_nn_dims *filter_dims, const nmsis_nn_dims *output_dims, int8_t *dst)

s8 max pooling function.

- Supported Framework: TensorFlow Lite

Parameters

- `ctx` – **[inout]** Function context (e.g. temporary buffer). Check the function definition file to see if an additional buffer is required. Optional function {API}_get_buffer_size() provides the buffer size if an additional buffer is required. The caller is expected to clear the buffer ,if applicable, for security reasons.

- **pool_params** – **[in]** Pooling parameters
- **input_dims** – **[in]** Input (activation) tensor dimensions. Format: [H, W, C_IN] Argument 'N' is not used.
- **input_data** – **[in]** Input (activation) data pointer. The input tensor must not overlap with the output tensor. Data type: int8
- **filter_dims** – **[in]** Filter tensor dimensions. Format: [H, W] Argument N and C are not used.
- **output_dims** – **[in]** Output tensor dimensions. Format: [H, W, C_OUT] Argument N is not used. C_OUT equals C_IN.
- **output_data** – **[inout]** Output data pointer. Data type: int8

Returns The function returns `RISCV_NMSIS_NN_SUCCESS` - Successful operation

void **riscv_maxpool_q7_HWC**(q7_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const uint16_t dim_im_out, q7_t *bufferA, q7_t *Im_out)

Q7 max pooling function.

The pooling function is implemented as split x-pooling then y-pooling.

This pooling function is input-destructive. Input data is undefined after calling this function.

Parameters

- **Im_in** – **[inout]** pointer to input tensor
- **dim_im_in** – **[in]** input tensor dimention
- **ch_im_in** – **[in]** number of input tensor channels
- **dim_kernel** – **[in]** filter kernel size
- **padding** – **[in]** padding sizes
- **stride** – **[in]** convolution stride
- **dim_im_out** – **[in]** output tensor dimension
- **bufferA** – **[inout]** Not used
- **Im_out** – **[inout]** pointer to output tensor

void **riscv_avepool_q7_HWC**(q7_t *Im_in, const uint16_t dim_im_in, const uint16_t ch_im_in, const uint16_t dim_kernel, const uint16_t padding, const uint16_t stride, const uint16_t dim_im_out, q7_t *bufferA, q7_t *Im_out)

Q7 average pooling function.

Buffer size:

bufferA size: 2*dim_im_out*ch_im_in

The pooling function is implemented as split x-pooling then y-pooling.

This pooling function is input-destructive. Input data is undefined after calling this function.

Parameters

- **Im_in** – **[inout]** pointer to input tensor
- **dim_im_in** – **[in]** input tensor dimention

- **ch_im_in** – **[in]** number of input tensor channels
- **dim_kernel** – **[in]** filter kernel size
- **padding** – **[in]** padding sizes
- **stride** – **[in]** convolution stride
- **dim_im_out** – **[in]** output tensor dimension
- **bufferA** – **[inout]** pointer to buffer space for input
- **Im_out** – **[inout]** pointer to output tensor

Reshape Functions

void **riscv_reshape_s8**(const int8_t *input, int8_t *output, const uint32_t total_size)

group **Reshape**

Functions

void **riscv_reshape_s8**(const int8_t *input, int8_t *output, const uint32_t total_size)

Reshape a s8 vector into another with different shape.

Note: The output is expected to be in a memory area that does not overlap with the input's

Parameters

- **input** – **[in]** points to the s8 input vector
- **output** – **[out]** points to the s8 output vector
- **total_size** – **[in]** total size of the input and output vectors in bytes

Softmax Functions

void **riscv_softmax_q15**(const q15_t *vec_in, const uint16_t dim_vec, q15_t *p_out)

void **riscv_softmax_q7**(const q7_t *vec_in, const uint16_t dim_vec, q7_t *p_out)

riscv_nmsis_nn_status **riscv_softmax_s16**(const int16_t *input, const int32_t num_rows, const int32_t row_size, const int32_t mult, const int32_t shift, const nmsis_nn_softmax_lut_s16 *softmax_params, int16_t *output)

void **riscv_softmax_s8**(const int8_t *input, const int32_t num_rows, const int32_t row_size, const int32_t mult, const int32_t shift, const int32_t diff_min, int8_t *output)

void **riscv_softmax_s8_s16**(const int8_t *input, const int32_t num_rows, const int32_t row_size, const int32_t mult, const int32_t shift, const int32_t diff_min, int16_t *output)

void **riscv_softmax_u8**(const uint8_t *input, const int32_t num_rows, const int32_t row_size, const int32_t mult, const int32_t shift, const int32_t diff_min, uint8_t *output) void **riscv_softmax_with_batch_q7**(const q7_t *vec_in, const uint16_t nb_batches, const uint16_t dim_vec, q7_t *p_out)

group **Softmax**

Functions

void **riscv_softmax_q15**(const q15_t *vec_in, const uint16_t dim_vec, q15_t *p_out)

Q15 softmax function.

Here, instead of typical e based softmax, we use 2-based softmax, i.e.,:

y_i = 2^(x_i) / sum(2^x_j)

The relative output will be different here. But mathematically, the gradient will be the same with a log(2) scaling factor.

Parameters

- **vec_in** – **[in]** pointer to input vector
- **dim_vec** – **[in]** input vector dimention
- **p_out** – **[out]** pointer to output vector

void **riscv_softmax_q7**(const q7_t *vec_in, const uint16_t dim_vec, q7_t *p_out)

Q7 softmax function.

Here, instead of typical natural logarithm e based softmax, we use 2-based softmax here, i.e.,:

y_i = 2^(x_i) / sum(2^x_j)

The relative output will be different here. But mathematically, the gradient will be the same with a log(2) scaling factor.

Parameters

- **vec_in** – **[in]** pointer to input vector
- **dim_vec** – **[in]** input vector dimention
- **p_out** – **[out]** pointer to output vector

riscv_nmsis_nn_status **riscv_softmax_s16**(const int16_t *input, const int32_t num_rows, const int32_t row_size, const int32_t mult, const int32_t shift, const nmsis_nn_softmax_lut_s16 *softmax_params, int16_t *output)

S16 softmax function.

Note: Supported framework: TensorFlow Lite micro (bit-accurate)

Parameters

- **input** – **[in]** Pointer to the input tensor
- **num_rows** – **[in]** Number of rows in the input tensor
- **row_size** – **[in]** Number of elements in each input row

- **mult** – **[in]** Input quantization multiplier
- **shift** – **[in]** Input quantization shift within the range [0, 31]
- **softmax_params** – **[in]** Softmax s16 layer parameters with two pointers to LUTs speficied below. For indexing the high 9 bits are used and 7 remaining for interpolation. That means 512 entries for the 9-bit indexing and 1 extra for interpolation, i.e. 513 values for each LUT.
  - Lookup table for exp(x), where x uniform distributed between [-10.0 , 0.0]
  - Lookup table for 1 / (1 + x), where x uniform distributed between [0.0 , 1.0]
- **output** – **[out]** Pointer to the output tensor

Returns The function returns `RISCV_NMSIS_NN_ARG_ERROR` Argument error check failed `RISCV_NMSIS_NN_SUCCESS` - Successful operation

void **riscv_softmax_s8**(const int8_t *input, const int32_t num_rows, const int32_t row_size, const int32_t mult, const int32_t shift, const int32_t diff_min, int8_t *output)

S8 softmax function.

Note: Supported framework: TensorFlow Lite micro (bit-accurate)

Parameters

- **input** – **[in]** Pointer to the input tensor
- **num_rows** – **[in]** Number of rows in the input tensor
- **row_size** – **[in]** Number of elements in each input row
- **mult** – **[in]** Input quantization multiplier
- **shift** – **[in]** Input quantization shift within the range [0, 31]
- **diff_min** – **[in]** Minimum difference with max in row. Used to check if the quantized exponential operation can be performed
- **output** – **[out]** Pointer to the output tensor

void **riscv_softmax_s8_s16**(const int8_t *input, const int32_t num_rows, const int32_t row_size, const int32_t mult, const int32_t shift, const int32_t diff_min, int16_t *output)

S8 to s16 softmax function.

Note: Supported framework: TensorFlow Lite micro (bit-accurate)

Parameters

- **input** – **[in]** Pointer to the input tensor
- **num_rows** – **[in]** Number of rows in the input tensor
- **row_size** – **[in]** Number of elements in each input row
- **mult** – **[in]** Input quantization multiplier
- **shift** – **[in]** Input quantization shift within the range [0, 31]
- **diff_min** – **[in]** Minimum difference with max in row. Used to check if the quantized exponential operation can be performed

- **output** – **[out]** Pointer to the output tensor

void **riscv_softmax_u8**(const uint8_t *input, const int32_t num_rows, const int32_t row_size, const int32_t mult, const int32_t shift, const int32_t diff_min, uint8_t *output)

U8 softmax function.

Note: Supported framework: TensorFlow Lite micro (bit-accurate)

Parameters

- **input** – **[in]** Pointer to the input tensor
- **num_rows** – **[in]** Number of rows in the input tensor
- **row_size** – **[in]** Number of elements in each input row
- **mult** – **[in]** Input quantization multiplier
- **shift** – **[in]** Input quantization shift within the range [0, 31]
- **diff_min** – **[in]** Minimum difference with max in row. Used to check if the quantized exponential operation can be performed
- **output** – **[out]** Pointer to the output tensor

void **riscv_softmax_with_batch_q7**(const q7_t *vec_in, const uint16_t nb_batches, const uint16_t dim_vec, q7_t *p_out)

Q7 softmax function with batch parameter.

Here, instead of typical natural logarithm e based softmax, we use 2-based softmax here, i.e.,:

y_i = 2^(x_i) / sum(2^x_j)

The relative output will be different here. But mathematically, the gradient will be the same with a log(2) scaling factor.

Parameters

- **vec_in** – **[in]** pointer to input vector
- **nb_batches** – **[in]** number of batches
- **dim_vec** – **[in]** input vector dimention
- **p_out** – **[out]** pointer to output vector

SVDF Functions

riscv_nmsis_nn_status **riscv_svdf_s8**(const nmsis_nn_context *input_ctx, const nmsis_nn_context *output_ctx, const nmsis_nn_svdf_params *svdf_params, const nmsis_nn_per_tensor_quant_params *input_quant_params, const nmsis_nn_per_tensor_quant_params *output_quant_params, const nmsis_nn_dims *input_dims, const int8_t *input_data, const nmsis_nn_dims *state_dims, int8_t *state_data, const nmsis_nn_dims *weights_feature_dims, const int8_t *weights_feature_data, const nmsis_nn_dims *weights_time_dims, const int8_t *weights_time_data, const nmsis_nn_dims *bias_dims, const int32_t *bias_data, const nmsis_nn_dims *output_dims, int8_t *output_data) riscv_nmsis_nn_status **riscv_svdf_state_s16_s8**(const nmsis_nn_context *input_ctx, const nmsis_nn_context *output_ctx, const nmsis_nn_svdf_params *svdf_params, const nmsis_nn_per_tensor_quant_params *input_quant_params, const nmsis_nn_per_tensor_quant_params *output_quant_params, const nmsis_nn_dims *input_dims, const int8_t *input_data, const nmsis_nn_dims *state_dims, int16_t *state_data, const nmsis_nn_dims *weights_feature_dims, const int8_t *weights_feature_data, const nmsis_nn_dims *weights_time_dims, const int16_t *weights_time_data, const nmsis_nn_dims *bias_dims, const int32_t *bias_data, const nmsis_nn_dims *output_dims, int8_t *output_data)

group **SVDF**

Functions

riscv_nmsis_nn_status **riscv_svdf_s8**(const nmsis_nn_context *input_ctx, const nmsis_nn_context *output_ctx, const nmsis_nn_svdf_params *svdf_params, const nmsis_nn_per_tensor_quant_params *input_quant_params, const nmsis_nn_per_tensor_quant_params *output_quant_params, const nmsis_nn_dims *input_dims, const int8_t *input_data, const nmsis_nn_dims *state_dims, int8_t *state_data, const nmsis_nn_dims *weights_feature_dims, const int8_t *weights_feature_data, const nmsis_nn_dims *weights_time_dims, const int8_t *weights_time_data, const nmsis_nn_dims *bias_dims, const int32_t *bias_data, const nmsis_nn_dims *output_dims, int8_t *output_data)

s8 SVDF function with 8 bit state tensor and 8 bit time weights

a. Supported framework: TensorFlow Lite micro

Parameters

- **input_ctx** – **[in]** Temporary scratch buffer The caller is expected to clear the buffer ,if applicable, for security reasons.
- **output_ctx** – **[in]** Temporary output scratch buffer The caller is expected to clear the buffer ,if applicable, for security reasons.
- **svdf_params** – **[in]** SVDF Parameters Range of svdf_params->input_offset : [-128, 127] Range of svdf_params->output_offset : [-128, 127]
- **input_quant_params** – **[in]** Input quantization parameters
- **output_quant_params** – **[in]** Output quantization parameters
- **input_dims** – **[in]** Input tensor dimensions
- **input_data** – **[in]** Pointer to input tensor
- **state_dims** – **[in]** State tensor dimensions
- **state_data** – **[in]** Pointer to state tensor

- **weights_feature_dims** – **[in]** Weights (feature) tensor dimensions
- **weights_feature_data** – **[in]** Pointer to the weights (feature) tensor
- **weights_time_dims** – **[in]** Weights (time) tensor dimensions
- **weights_time_data** – **[in]** Pointer to the weights (time) tensor
- **bias_dims** – **[in]** Bias tensor dimensions
- **bias_data** – **[in]** Pointer to bias tensor
- **output_dims** – **[in]** Output tensor dimensions
- **output_data** – **[out]** Pointer to the output tensor

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

riscv_nmsis_nn_status **riscv_svdf_state_s16_s8**(const nmsis_nn_context *input_ctx, const nmsis_nn_context *output_ctx, const nmsis_nn_svdf_params *svdf_params, const nmsis_nn_per_tensor_quant_params *input_quant_params, const nmsis_nn_per_tensor_quant_params *output_quant_params, const nmsis_nn_dims *input_dims, const int8_t *input_data, const nmsis_nn_dims *state_dims, int16_t *state_data, const nmsis_nn_dims *weights_feature_dims, const int8_t *weights_feature_data, const nmsis_nn_dims *weights_time_dims, const int16_t *weights_time_data, const nmsis_nn_dims *bias_dims, const int32_t *bias_data, const nmsis_nn_dims *output_dims, int8_t *output_data)

s8 SVDF function with 16 bit state tensor and 16 bit time weights

a. Supported framework: TensorFlow Lite micro

Parameters

- **input_ctx** – **[in]** Temporary scratch buffer The caller is expected to clear the buffer ,if applicable, for security reasons.
- **output_ctx** – **[in]** Temporary output scratch buffer The caller is expected to clear the buffer ,if applicable, for security reasons.
- **svdf_params** – **[in]** SVDF Parameters Range of svdf_params->input_offset : [-128, 127] Range of svdf_params->output_offset : [-128, 127]
- **input_quant_params** – **[in]** Input quantization parameters
- **output_quant_params** – **[in]** Output quantization parameters
- **input_dims** – **[in]** Input tensor dimensions
- **input_data** – **[in]** Pointer to input tensor
- **state_dims** – **[in]** State tensor dimensions
- **state_data** – **[in]** Pointer to state tensor
- **weights_feature_dims** – **[in]** Weights (feature) tensor dimensions

- **weights_feature_data** – **[in]** Pointer to the weights (feature) tensor
- **weights_time_dims** – **[in]** Weights (time) tensor dimensions
- **weights_time_data** – **[in]** Pointer to the weights (time) tensor
- **bias_dims** – **[in]** Bias tensor dimensions
- **bias_data** – **[in]** Pointer to bias tensor
- **output_dims** – **[in]** Output tensor dimensions
- **output_data** – **[out]** Pointer to the output tensor

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

group **Public**

A collection of functions to perform basic operations for neural network layers. Functions with a _s8 suffix support TensorFlow Lite framework.

4.3.4 Private

Convolution

riscv_nmsis_nn_status **riscv_nn_depthwise_conv_nt_t_padded_s8**(const int8_t *lhs, const int8_t *rhs, const int32_t input_offset, const int32_t active_ch, const int32_t total_ch, const int32_t *out_shift, const int32_t *out_mult, const int32_t out_offset, const int32_t activation_min, const int32_t activation_max, const uint16_t row_x_col, const int32_t *const output_bias, int8_t *out)

int16_t ***riscv_nn_depthwise_conv_nt_t_s16**(const int16_t *lhs, const int8_t *rhs, const uint16_t num_ch, const int32_t *out_shift, const int32_t *out_mult, const int32_t activation_min, const int32_t activation_max, const uint16_t row_x_col, const int64_t *const output_bias, int16_t *out)

riscv_nmsis_nn_status **riscv_nn_depthwise_conv_nt_t_s8**(const int8_t *lhs, const int8_t *rhs, const int32_t input_offset, const int32_t active_ch, const int32_t total_ch, const int32_t *out_shift, const int32_t *out_mult, const int32_t out_offset, const int32_t activation_min, const int32_t activation_max, const uint16_t row_x_col, const int32_t *const output_bias, int8_t *out)

riscv_nmsis_nn_status **riscv_nn_mat_mul_core_1x_s8**(int32_t row_elements, const int32_t skipped_row_elements, const int8_t *row_base_ref, const int8_t *col_base_ref, const int32_t out_ch, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const int32_t *bias, int8_t *output) int8_t ***riscv_nn_mat_mul_core_4x_s8**(const int32_t row_elements, const int32_t offset, const int8_t *row_base, const int8_t *col_base_ref, const int32_t out_ch, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const int32_t *bias, int8_t *output)

int16_t ***riscv_nn_mat_mult_kernel_s16**(const int8_t *input_a, const int16_t *input_b, const int32_t output_ch, const int32_t *out_shift, const int32_t *out_mult, const int16_t activation_min, const int16_t activation_max, const int32_t num_col_a, const int64_t *const output_bias, int16_t *out_0)

riscv_nmsis_nn_status **riscv_nn_mat_mult_nt_t_s8**(const int8_t *lhs, const int8_t *rhs, const int32_t *bias, int8_t *dst, const int32_t *dst_multipliers, const int32_t *dst_shifts, const int32_t lhs_rows, const int32_t rhs_rows, const int32_t rhs_cols, const int32_t lhs_offset, const int32_t dst_offset, const int32_t activation_min, const int32_t activation_max, const int32_t lhs_cols_offset)

group **supportConvolution**

Support functions for Convolution and DW Convolution.

Functions

riscv_nmsis_nn_status **riscv_nn_depthwise_conv_nt_t_padded_s8**(const int8_t *lhs, const int8_t *rhs, const int32_t input_offset, const int32_t active_ch, const int32_t total_ch, const int32_t *out_shift, const int32_t *out_mult, const int32_t out_offset, const int32_t activation_min, const int32_t activation_max, const uint16_t row_x_col, const int32_t *const output_bias, int8_t *out)

Depthwise convolution of transposed rhs matrix with 4 lhs matrices. To be used in padded cases where the padding is -lhs_offset(Range: int8). Dimensions are the same for lhs and rhs.

Note: If number of channels is not a multiple of 4, upto 3 elements outside the boundary will be read out for the following.

- Output shift
- Output multiplier
- Output bias
- rhs

Parameters

- **lhs** – **[in]** Input left-hand side matrix
- **rhs** – **[in]** Input right-hand side matrix (transposed)
- **lhs_offset** – **[in]** LHS matrix offset(input offset). Range: -127 to 128

- **active_ch** – **[in]** Subset of total_ch processed
- **total_ch** – **[in]** Number of channels in LHS/RHS
- **out_shift** – **[in]** Per channel output shift. Length of vector is equal to number of channels
- **out_mult** – **[in]** Per channel output multiplier. Length of vector is equal to number of channels
- **out_offset** – **[in]** Offset to be added to the output values. Range: -127 to 128
- **activation_min** – **[in]** Minimum value to clamp the output to. Range: int8
- **activation_max** – **[in]** Maximum value to clamp the output to. Range: int8
- **row_x_col** – **[in]** (row_dimension * col_dimension) of LHS/RHS matrix
- **output_bias** – **[in]** Per channel output bias. Length of vector is equal to number of channels
- **out** – **[in]** Output pointer

Returns The function returns one of the two

- Updated output pointer if an implementation is available
- NULL if no implementation is available.

int16_t ***riscv_nn_depthwise_conv_nt_t_s16**(const int16_t *lhs, const int8_t *rhs, const uint16_t num_ch, const int32_t *out_shift, const int32_t *out_mult, const int32_t activation_min, const int32_t activation_max, const uint16_t row_x_col, const int64_t *const output_bias, int16_t *out)

Depthwise convolution of transposed rhs matrix with 4 lhs matrices. To be used in non-padded cases. Dimensions are the same for lhs and rhs.

Note: If number of channels is not a multiple of 4, upto 3 elements outside the boundary will be read out for the following.

- Output shift
- Output multiplier
- Output bias
- rhs

Parameters

- **lhs** – **[in]** Input left-hand side matrix
- **rhs** – **[in]** Input right-hand side matrix (transposed)
- **num_ch** – **[in]** Number of channels in LHS/RHS
- **out_shift** – **[in]** Per channel output shift. Length of vector is equal to number of channels.
- **out_mult** – **[in]** Per channel output multiplier. Length of vector is equal to number of channels.
- **activation_min** – **[in]** Minimum value to clamp the output to. Range: int8
- **activation_max** – **[in]** Maximum value to clamp the output to. Range: int8

- **row_x_col** – **[in]** (row_dimension * col_dimension) of LHS/RHS matrix
- **output_bias** – **[in]** Per channel output bias. Length of vector is equal to number of channels.
- **out** – **[in]** Output pointer

Returns The function returns one of the two

- Updated output pointer if an implementation is available
- NULL if no implementation is available.

riscv_nmsis_nn_status **riscv_nn_depthwise_conv_nt_t_s8**(const int8_t *lhs, const int8_t *rhs, const int32_t input_offset, const int32_t active_ch, const int32_t total_ch, const int32_t *out_shift, const int32_t *out_mult, const int32_t out_offset, const int32_t activation_min, const int32_t activation_max, const uint16_t row_x_col, const int32_t *const output_bias, int8_t *out)

Depthwise convolution of transposed rhs matrix with 4 lhs matrices. To be used in non-padded cases. Dimensions are the same for lhs and rhs.

Note: If number of channels is not a multiple of 4, upto 3 elements outside the boundary will be read out for the following.

- Output shift
- Output multiplier
- Output bias
- rhs

Parameters

- **lhs** – **[in]** Input left-hand side matrix
- **rhs** – **[in]** Input right-hand side matrix (transposed)
- **lhs_offset** – **[in]** LHS matrix offset(input offset). Range: -127 to 128
- **active_ch** – **[in]** Subset of total_ch processed
- **total_ch** – **[in]** Number of channels in LHS/RHS
- **out_shift** – **[in]** Per channel output shift. Length of vector is equal to number of channels.
- **out_mult** – **[in]** Per channel output multiplier. Length of vector is equal to number of channels.
- **out_offset** – **[in]** Offset to be added to the output values. Range: -127 to 128
- **activation_min** – **[in]** Minimum value to clamp the output to. Range: int8
- **activation_max** – **[in]** Maximum value to clamp the output to. Range: int8
- **row_x_col** – **[in]** (row_dimension * col_dimension) of LHS/RHS matrix
- **output_bias** – **[in]** Per channel output bias. Length of vector is equal to number of channels.

- **out** – **[in]** Output pointer

Returns The function returns one of the two

- Updated output pointer if an implementation is available
- NULL if no implementation is available.

riscv_nmsis_nn_status **riscv_nn_mat_mul_core_1x_s8**(int32_t row_elements, const int32_t skipped_row_elements, const int8_t *row_base_ref, const int8_t *col_base_ref, const int32_t out_ch, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const int32_t *bias, int8_t *output)

General Vector by Matrix multiplication with requantization and storage of result.

Pseudo-code *output = 0 sum_col = 0 for (j = 0; j < out_ch; j++) for (i = 0; i < row_elements; i++) *output += row_base_ref[i] * col_base_ref[i] sum_col += col_base_ref[i] scale sum_col using quant_params and bias store result in 'output'

Parameters

- **row_elements** – **[in]** number of row elements
- **skipped_row_elements** – **[in]** number of row elements skipped due to padding. row_elements + skipped_row_elements = (kernel_x * kernel_y) * input_ch
- **row_base_ref** – **[in]** pointer to row operand
- **col_base_ref** – **[in]** pointer to col operand
- **out_ch** – **[out]** Number of output channels
- **conv_params** – **[in]** Pointer to convolution parameters like offsets and activation values
- **quant_params** – **[in]** Pointer to per-channel quantization parameters
- **bias** – **[in]** Pointer to optional per-channel bias
- **output** – **[out]** Pointer to output where int8 results are stored.

Returns The function performs matrix(row_base_ref) multiplication with vector(col_base_ref) and scaled result is stored in memory.

int8_t ***riscv_nn_mat_mul_core_4x_s8**(const int32_t row_elements, const int32_t offset, const int8_t *row_base, const int8_t *col_base_ref, const int32_t out_ch, const nmsis_nn_conv_params *conv_params, const nmsis_nn_per_channel_quant_params *quant_params, const int32_t *bias, int8_t *output)

Matrix-multiplication with requantization & activation function for four rows and one column.

Compliant to TFLM int8 specification. MVE implementation only

Parameters

- **row_elements** – **[in]** number of row elements

- **offset** – **[in]** offset between rows. Can be the same as row_elements. For e.g, in a 1x1 conv scenario with stride as 1.
- **row_base** – **[in]** pointer to row operand
- **col_base** – **[in]** pointer to col operand
- **out_ch** – **[in]** Number of output channels
- **conv_params** – **[in]** Pointer to convolution parameters like offsets and activation values
- **quant_params** – **[in]** Pointer to per-channel quantization parameters
- **bias** – **[in]** Pointer to per-channel bias
- **output** – **[out]** Pointer to output where int8 results are stored.

Returns The function returns the updated output pointer or NULL if implementation is not available.

int16_t ***riscv_nn_mat_mult_kernel_s16**(const int8_t *input_a, const int16_t *input_b, const int32_t output_ch, const int32_t *out_shift, const int32_t *out_mult, const int16_t activation_min, const int16_t activation_max, const int32_t num_col_a, const int64_t *const output_bias, int16_t *out_0)

Matrix-multiplication function for convolution with per-channel requantization for 16 bits convolution.

This function does the matrix multiplication of weight matrix for all output channels with 2 columns from im2col and produces two elements/output_channel. The outputs are clamped in the range provided by activation min and max. Supported framework: TensorFlow Lite micro.

Parameters

- **input_a** – **[in]** pointer to operand A
- **input_b** – **[in]** pointer to operand B, always consists of 2 vectors.
- **output_ch** – **[in]** number of rows of A
- **out_shift** – **[in]** pointer to per output channel requantization shift parameter.
- **out_mult** – **[in]** pointer to per output channel requantization multiplier parameter.
- **activation_min** – **[in]** minimum value to clamp the output to. Range : int16
- **activation_max** – **[in]** maximum value to clamp the output to. Range : int16
- **num_col_a** – **[in]** number of columns of A
- **output_bias** – **[in]** per output channel bias. Range : int64
- **out_0** – **[inout]** pointer to output

Returns The function returns one of the two

a. The incremented output pointer for a successful operation or
b. NULL if implementation is not available.

riscv_nmsis_nn_status **riscv_nn_mat_mult_nt_t_s8**(const int8_t *lhs, const int8_t *rhs, const int32_t *bias, int8_t *dst, const int32_t *dst_multipliers, const int32_t *dst_shifts, const int32_t lhs_rows, const int32_t rhs_rows, const int32_t rhs_cols, const int32_t lhs_offset, const int32_t dst_offset, const int32_t activation_min, const int32_t activation_max, const int32_t lhs_cols_offset)

General Matrix-multiplication function with per-channel requantization. This function assumes:

- LHS input matrix NOT transposed (nt)
- RHS input matrix transposed (t)

Note: This operation also performs the broadcast bias addition before the requantization

Parameters

- **lhs** – **[in]** Pointer to the LHS input matrix
- **rhs** – **[in]** Pointer to the RHS input matrix
- **bias** – **[in]** Pointer to the bias vector. The length of this vector is equal to the number of output columns (or RHS input rows)
- **dst** – **[out]** Pointer to the output matrix with "m" rows and "n" columns
- **dst_multipliers** – **[in]** Pointer to the multipliers vector needed for the per-channel requantization. The length of this vector is equal to the number of output columns (or RHS input rows)
- **dst_shifts** – **[in]** Pointer to the shifts vector needed for the per-channel requantization. The length of this vector is equal to the number of output columns (or RHS input rows)
- **lhs_rows** – **[in]** Number of LHS input rows
- **rhs_rows** – **[in]** Number of RHS input rows
- **rhs_cols** – **[in]** Number of LHS/RHS input columns
- **lhs_offset** – **[in]** Offset to be applied to the LHS input value
- **dst_offset** – **[in]** Offset to be applied the output result
- **activation_min** – **[in]** Minimum value to clamp down the output. Range : int8
- **activation_max** – **[in]** Maximum value to clamp up the output. Range : int8
- **lhs_cols_offset** – **[in]** Column offset between subsequent lhs_rows

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

LSTM

void **riscv_nn_lstm_calculate_gate_s8_s16**(const int8_t *input, const int8_t *input_to_gate_weights, const int32_t *input_to_gate_bias, const nmsis_nn_scaling input_to_gate_scaling, const int8_t *output_state, const int8_t *recurrent_to_gate_weights, const int32_t *recurrent_to_gate_bias, const nmsis_nn_scaling recurrent_to_gate, const int32_t n_batch, const int32_t n_input, const int32_t n_output, const int32_t n_cell, const riscv_nn_activation_type activation_type, int16_t *gate)

riscv_nmsis_nn_status **riscv_nn_lstm_step_s8_s16**(const int8_t *input, const int8_t *input_to_input_weight, const int8_t *input_to_forget_weight, const int8_t *input_to_cell_weight, const int8_t *input_to_output_weight, const int8_t *recurrent_to_input_weight, const int8_t *recurrent_to_forget_weight, const int8_t *recurrent_to_cell_weight, const int8_t *recurrent_to_output_weight, const nmsis_nn_lstm_params *lstm, const int n_batch, const int n_cell, const int n_input, const int n_output, int8_t *output_state, int16_t *cell_state, int8_t *output, nmsis_nn_lstm_context *scratch_buffers)

void **riscv_nn_lstm_update_cell_state_s16**(const int32_t n_block, const int32_t cell_state_scale, int16_t *cell_state, const int16_t *input_gate, const int16_t *forget_gate, const int16_t *cell_gate)

void **riscv_nn_lstm_update_output_s8_s16**(const int n_batch, const int n_cell, int16_t *cell_state, const int32_t cell_state_scale, const int16_t *output_gate, const nmsis_nn_scaling hidden_scaling, const int32_t hidden_offset, int8_t *output_state, int16_t *cell_gate_scratch)

void **riscv_nn_vec_mat_mul_result_acc_s8**(const int8_t *lhs_in, const int8_t *rhs_in, const int32_t *bias, int16_t *dst, const int32_t dst_offset, const int32_t dst_multiplier, const int32_t dst_shift, const int32_t rhs_cols, const int32_t rhs_rows, const int32_t batch)

group **supportLSTM**

Support functions for LSTM.

Functions

void **riscv_nn_lstm_calculate_gate_s8_s16**(const int8_t *input, const int8_t *input_to_gate_weights, const int32_t *input_to_gate_bias, const nmsis_nn_scaling input_to_gate_scaling, const int8_t *output_state, const int8_t *recurrent_to_gate_weights, const int32_t *recurrent_to_gate_bias, const nmsis_nn_scaling recurrent_to_gate, const int32_t n_batch, const int32_t n_input, const int32_t n_output, const int32_t n_cell, const riscv_nn_activation_type activation_type, int16_t *gate)

Updates a LSTM gate for an iteration step of LSTM function, int8x8_16 version.

param[in] input Input data param[in] input_to_gate_weights Input to gate weights param[in] input_to_gate_bias Input to gate weights param[in] input_to_gate_scaling Input to gate scaling param[in] activation Actival min and max values param[in] output_state Output state param[in] recurrent_to_gate_weights Recurrent to gate weights param[in] recurrent_to_gate_bias Recurrent to gate bias param[in] recurrent_to_gate_scaling Recurrent to gate scaling param[in] n_batch Batch size param[in] n_input Input size param[out] n_output Output size param[in] activation_type Activation type (sigmoid or tanh) param[out] n_cell Cell size

riscv_nmsis_nn_status **riscv_nn_lstm_step_s8_s16**(const int8_t *input, const int8_t *input_to_input_weight, const int8_t *input_to_forget_weight, const int8_t *input_to_cell_weight, const int8_t *input_to_output_weight, const int8_t *recurrent_to_input_weight, const int8_t *recurrent_to_forget_weight, const int8_t *recurrent_to_cell_weight, const int8_t *recurrent_to_output_weight, const nmsis_nn_lstm_params *lstm, const int n_batch, const int n_cell, const int n_input, const int n_output, int8_t *output_state, int16_t *cell_state, int8_t *output, nmsis_nn_lstm_context *scratch_buffers)

Update LSTM function for an iteration step.

param[in] input Input data param[in] input_to_input_weight Input to input gate weights param[in] input_to_forget_weight Input to forget gate weights param[in] input_to_cell_weight Input to cell gate weights param[in] input_to_output_weight Input to output weights param[in] recurrent_to_input_weight Recurrent signal to input weights param[in] recurrent_to_forget_weight Recurrent signal to forget gate weights param[in] recurrent_to_cell_weight Recurrent signal to cell gate weighst param[in] recurrent_to_output_weight Recurrent signal to output weights param[in] lstm LSTM parameters param[in] n_batch Batch size param[in] n_cell Cell size param[in] n_input Input size param[in] n_output Output size param[out] output_state Output state param[out] cell_state Internal state param[out] output Output signal param[in] *scratch_buffers Struct containing scratch buffers

void **riscv_nn_lstm_update_cell_state_s16**(const int32_t n_block, const int32_t cell_state_scale, int16_t *cell_state, const int16_t *input_gate, const int16_t *forget_gate, const int16_t *cell_gate)

Update cell state for a single LSTM iteration step, int8x8_16 version.

Parameters

- `n_block` – **[in]** total number of cells for all batches
- `cell_state_scale` – **[in]** Scaling factor of cell state
- `cell_state` – **[in]** Input/output vector, size n_batch*n_cell
- `input_gate` – **[in]** Input vector of size n_block
- `forget_gate` – **[in]** Input/scratch vector of size n_block, always modified
- `cell_gate` – **[in]** Input vector of size, n_block

void **riscv_nn_lstm_update_output_s8_s16**(const int n_batch, const int n_cell, int16_t *cell_state, const int32_t cell_state_scale, const int16_t *output_gate, const nmsis_nn_scaling hidden_scaling, const int32_t hidden_offset, int8_t *output_state, int16_t *cell_gate_scratch)

Calculate the output state tensor of an LSTM step, s8 input/output and s16 weight version.

Parameters

- `n_batch` – **[in]** The number of distinct vectors in each array

- **n_cell** – **[in]** Number of cells
- **cell_state** – **[inout]** Cell state, size n_batch*n_cell
- **cell_state_scale** – **[in]** Scaling of cell_state
- **output_gate** – **[in]** Output gate
- **hidden_scale** – **[in]** Effective scaling of cell_state .* output_gate
- **hidden_offset** – **[in]** Zero point for cell_state .* output_gate
- **output_state** – **[out]** Output state
- **cell_gate_scratch** – **[in]** Scratch buffer

void **riscv_nn_vec_mat_mul_result_acc_s8**(const int8_t *lhs_in, const int8_t *rhs_in, const int32_t *bias, int16_t *dst, const int32_t dst_offset, const int32_t dst_multiplier, const int32_t dst_shift, const int32_t rhs_cols, const int32_t rhs_rows, const int32_t batch)

The result of the multiplication is accumulated to the passed result buffer. Multiplies a matrix by a "batched" vector (i.e. a matrix with a batch dimension composed by input vectors independent from each other).

Parameters

- **lhs_in** – **[in]** Batched vector
- **rhs_in** – **[in]** Weights - input matrix (H(Rows)xW(Columns))
- **bias** – **[in]** Bias vector
- **dst** – **[out]** Output
- **dst_offset** – **[in]** Output offset
- **dst_multiplier** – **[in]** Multiplier for quantization
- **dst_shift** – **[in]** Shift for quantization
- **rhs_cols** – **[in]** Vector/matarix column length
- **rhs_rows** – **[in]** Row count of matrix
- **batch** – **[in]** Batch size

Fully Connected

riscv_nmsis_nn_status **riscv_nn_vec_mat_mult_t_s16**(const int16_t *lhs, const int8_t *rhs, const int64_t *bias, int16_t *dst, const int32_t dst_multiplier, const int32_t dst_shift, const int32_t rhs_cols, const int32_t rhs_rows, const int32_t activation_min, const int32_t activation_max)

riscv_nmsis_nn_status **riscv_nn_vec_mat_mult_t_s8**(const int8_t *lhs, const int8_t *rhs, const int32_t *bias, int8_t *dst, const int32_t lhs_offset, const int32_t dst_offset, const int32_t dst_multiplier, const int32_t dst_shift, const int32_t rhs_cols, const int32_t rhs_rows, const int32_t activation_min, const int32_t activation_max, const int32_t address_offset) riscv_nmsis_nn_status **riscv_nn_vec_mat_mult_t_svdf_s8**(const int8_t *lhs, const int8_t *rhs, int16_t *dst, const int32_t lhs_offset, const int32_t dst_offset, const int32_t dst_multiplier, const int32_t dst_shift, const int32_t rhs_cols, const int32_t rhs_rows, const int32_t activation_min, const int32_t activation_max)

group **supportFC**

Support functions for Fully Connected.

Functions

riscv_nmsis_nn_status **riscv_nn_vec_mat_mult_t_s16**(const int16_t *lhs, const int8_t *rhs, const int64_t *bias, int16_t *dst, const int32_t dst_multiplier, const int32_t dst_shift, const int32_t rhs_cols, const int32_t rhs_rows, const int32_t activation_min, const int32_t activation_max)

s16 Vector by Matrix (transposed) multiplication

Parameters

- **lhs** – **[in]** Input left-hand side vector
- **rhs** – **[in]** Input right-hand side matrix (transposed)
- **bias** – **[in]** Input bias
- **dst** – **[out]** Output vector
- **dst_multiplier** – **[in]** Output multiplier
- **dst_shift** – **[in]** Output shift
- **rhs_cols** – **[in]** Number of columns in the right-hand side input matrix
- **rhs_rows** – **[in]** Number of rows in the right-hand side input matrix
- **activation_min** – **[in]** Minimum value to clamp the output to. Range: int16
- **activation_max** – **[in]** Maximum value to clamp the output to. Range: int16

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

riscv_nmsis_nn_status **riscv_nn_vec_mat_mult_t_s8**(const int8_t *lhs, const int8_t *rhs, const int32_t *bias, int8_t *dst, const int32_t lhs_offset, const int32_t dst_offset, const int32_t dst_multiplier, const int32_t dst_shift, const int32_t rhs_cols, const int32_t rhs_rows, const int32_t activation_min, const int32_t activation_max, const int32_t address_offset)

s8 Vector by Matrix (transposed) multiplication

Parameters

- **lhs** – **[in]** Input left-hand side vector
- **rhs** – **[in]** Input right-hand side matrix (transposed)
- **bias** – **[in]** Input bias
- **dst** – **[out]** Output vector

- `lhs_offset` – **[in]** Offset to be added to the input values of the left-hand side vector. Range: -127 to 128
- `dst_offset` – **[in]** Offset to be added to the output values. Range: -127 to 128
- `dst_multiplier` – **[in]** Output multiplier
- `dst_shift` – **[in]** Output shift
- `rhs_cols` – **[in]** Number of columns in the right-hand side input matrix
- `rhs_rows` – **[in]** Number of rows in the right-hand side input matrix
- `activation_min` – **[in]** Minimum value to clamp the output to. Range: int8
- `activation_max` – **[in]** Maximum value to clamp the output to. Range: int8
- `address_offset` – **[in]** Memory position offset for dst. First output is stored at 'dst', the second at 'dst + address_offset' and so on. Default value is typically 1.

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

riscv_nmsis_nn_status **`riscv_nn_vec_mat_mult_t_svdf_s8`**(const int8_t *lhs, const int8_t *rhs, int16_t *dst, const int32_t lhs_offset, const int32_t dst_offset, const int32_t dst_multiplier, const int32_t dst_shift, const int32_t rhs_cols, const int32_t rhs_rows, const int32_t activation_min, const int32_t activation_max)

s8 Vector by Matrix (transposed) multiplication with s16 output

Parameters

- `lhs` – **[in]** Input left-hand side vector
- `rhs` – **[in]** Input right-hand side matrix (transposed)
- `dst` – **[out]** Output vector
- `lhs_offset` – **[in]** Offset to be added to the input values of the left-hand side vector. Range: -127 to 128
- `scatter_offset` – **[in]** Address offset for dst. First output is stored at 'dst', the second at 'dst + scatter_offset' and so on.
- `dst_multiplier` – **[in]** Output multiplier
- `dst_shift` – **[in]** Output shift
- `rhs_cols` – **[in]** Number of columns in the right-hand side input matrix
- `rhs_rows` – **[in]** Number of rows in the right-hand side input matrix
- `activation_min` – **[in]** Minimum value to clamp the output to. Range: int16
- `activation_max` – **[in]** Maximum value to clamp the output to. Range: int16

Returns The function returns `RISCV_NMSIS_NN_SUCCESS`

Softmax

void **riscv_nn_softmax_common_s8**(const int8_t *input, const int32_t num_rows, const int32_t row_size, const int32_t mult, const int32_t shift, const int32_t diff_min, const bool int16_output, void *output)

group **supportSoftmax**

Support functions for Softmax.

Functions

void **riscv_nn_softmax_common_s8**(const int8_t *input, const int32_t num_rows, const int32_t row_size, const int32_t mult, const int32_t shift, const int32_t diff_min, const bool int16_output, void *output)

Common softmax function for s8 input and s8 or s16 output.

Note: Supported framework: TensorFlow Lite micro (bit-accurate)

Parameters

- **input** – **[in]** Pointer to the input tensor
- **num_rows** – **[in]** Number of rows in the input tensor
- **row_size** – **[in]** Number of elements in each input row
- **mult** – **[in]** Input quantization multiplier
- **shift** – **[in]** Input quantization shift within the range [0, 31]
- **diff_min** – **[in]** Minimum difference with max in row. Used to check if the quantized exponential operation can be performed
- **int16_output** – **[in]** Indicating s8 output if 0 else s16 output
- **output** – **[out]** Pointer to the output tensor

Basic math functions

riscv_nmsis_nn_status **riscv_elementwise_mul_s16_s8**(const int16_t *input_1_vect, const int16_t *input_2_vect, int8_t *output, const int32_t out_offset, const int32_t out_mult, const int32_t out_shift, const int32_t block_size)

group **BasicMath**

Elementwise add and multiplication functions.

Functions

riscv_nmsis_nn_status **riscv_elementwise_mul_s16_s8**(const int16_t *input_1_vect, const int16_t *input_2_vect, int8_t *output, const int32_t out_offset, const int32_t out_mult, const int32_t out_shift, const int32_t block_size)

s16 elementwise multiplication with s8 output

Supported framework: TensorFlow Lite micro

Parameters

- **input_1_vect** – **[in]** pointer to input vector 1
- **input_2_vect** – **[in]** pointer to input vector 2
- **output** – **[inout]** pointer to output vector
- **out_offset** – **[in]** output offset
- **out_mult** – **[in]** output multiplier
- **out_shift** – **[in]** output shift
- **block_size** – **[in]** number of samples

Returns The function returns RISCV_NMSIS_NN_SUCCESS

Basic Math Functions for Neural Network Computation

void **riscv_nn_accumulate_q7_to_q15**(q15_t *pDst, const q7_t *pSrc, uint32_t length)

void **riscv_nn_add_q7**(const q7_t *input, q31_t *output, uint32_t block_size)

void **riscv_nn_mult_q15**(q15_t *pSrcA, q15_t *pSrcB, q15_t *pDst, const uint16_t out_shift, uint32_t blockSize)

void **riscv_nn_mult_q7**(q7_t *pSrcA, q7_t *pSrcB, q7_t *pDst, const uint16_t out_shift, uint32_t blockSize)

group **NNBasicMath**

Basic Math Functions for Neural Network Computation.

Functions

void **riscv_nn_accumulate_q7_to_q15**(q15_t *pDst, const q7_t *pSrc, uint32_t length)

Converts the elements from a q7 vector and accumulate to a q15 vector.

The equation used for the conversion process is:

Description:

Parameters

- ***src** – **[in]** points to the q7 input vector

- ***dst** – **[out]** points to the q15 output vector
- **block_size** – **[in]** length of the input vector

void **riscv_nn_add_q7**(const q7_t *input, q31_t *output, uint32_t block_size)

Non-saturating addition of elements of a q7 vector.

2^24 samples can be added without saturating the result.

Description:

The equation used for the conversion process is:

Parameters

- ***input** – **[in]** Pointer to the q7 input vector
- ***output** – **[out]** Pointer to the q31 output variable.
- **block_size** – **[in]** length of the input vector

void **riscv_nn_mult_q15**(q15_t *pSrcA, q15_t *pSrcB, q15_t *pDst, const uint16_t out_shift, uint32_t blockSize)

Q7 vector multiplication with variable output shifts.

q7 vector multiplication with variable output shifts

Scaling and Overflow Behavior:

The function uses saturating arithmetic. Results outside of the allowable Q15 range [0x8000 0x7FFF] will be saturated.

Parameters

- ***pSrcA** – **[in]** pointer to the first input vector
- ***pSrcB** – **[in]** pointer to the second input vector
- ***pDst** – **[out]** pointer to the output vector
- **out_shift** – **[in]** amount of right-shift for output
- **blockSize** – **[in]** number of samples in each vector

void **riscv_nn_mult_q7**(q7_t *pSrcA, q7_t *pSrcB, q7_t *pDst, const uint16_t out_shift, uint32_t blockSize)

Q7 vector multiplication with variable output shifts.

q7 vector multiplication with variable output shifts

Scaling and Overflow Behavior:

The function uses saturating arithmetic. Results outside of the allowable Q7 range [0x80 0x7F] will be saturated.

Parameters

- ***pSrcA** – **[in]** pointer to the first input vector
- ***pSrcB** – **[in]** pointer to the second input vector

- `*pDst` – **[out]** pointer to the output vector
- `out_shift` – **[in]** amount of right-shift for output
- `blockSize` – **[in]** number of samples in each vector

Copy

void **riscv_nn_copy_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_nn_copy_q7**(const q7_t *pSrc, q7_t *pDst, uint32_t blockSize)

group **copy**

Functions

void **riscv_nn_copy_q15**(const q15_t *pSrc, q15_t *pDst, uint32_t blockSize)

Copies the elements of a Q15 vector.

Parameters

- `pSrc` – **[in]** points to input vector
- `pDst` – **[out]** points to output vector
- `blockSize` – **[in]** number of samples in each vector

Returns none

void **riscv_nn_copy_q7**(const q7_t *pSrc, q7_t *pDst, uint32_t blockSize)

Copies the elements of a Q7 vector.

Parameters

- `pSrc` – **[in]** points to input vector
- `pDst` – **[out]** points to output vector
- `blockSize` – **[in]** number of samples in each vector

Returns none

Fill

void **riscv_nn_fill_q15**(q15_t value, q15_t *pDst, uint32_t blockSize)

void **riscv_nn_fill_q7**(q7_t value, q7_t *pDst, uint32_t blockSize)

group **Fill**

Functions

void **riscv_nn_fill_q15**(q15_t value, q15_t *pDst, uint32_t blockSize)

Fills a constant value into a Q15 vector.

Parameters

- **value** – **[in]** input value to be filled
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

void **riscv_nn_fill_q7**(q7_t value, q7_t *pDst, uint32_t blockSize)

Fills a constant value into a Q7 vector.

Parameters

- **value** – **[in]** input value to be filled
- **pDst** – **[out]** points to output vector
- **blockSize** – **[in]** number of samples in each vector

Returns none

Nndata_convert

void **riscv_q7_to_q15_no_shift**(const q7_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_q7_to_q15_reordered_no_shift**(const q7_t *pSrc, q15_t *pDst, uint32_t blockSize)

void **riscv_q7_to_q15_reordered_with_offset**(const q7_t *src, q15_t *dst, uint32_t block_size, q15_t offset)

void **riscv_q7_to_q7_no_shift**(const q7_t *pSrc, q7_t *pDst, uint32_t blockSize)

void **riscv_q7_to_q7_reordered_no_shift**(const q7_t *pSrc, q7_t *pDst, uint32_t blockSize)

group **Nndata_convert**

Functions

void **riscv_q7_to_q15_no_shift**(const q7_t *pSrc, q15_t *pDst, uint32_t blockSize)

Converts the elements of the Q7 vector to Q15 vector without left-shift.

Converts the elements of the q7 vector to q15 vector without left-shift.

The equation used for the conversion process is:

Description:

Parameters

- ***pSrc** – **[in]** points to the Q7 input vector

- ***pDst** – **[out]** points to the Q15 output vector
- **blockSize** – **[in]** length of the input vector

void **riscv_q7_to_q15_reordered_no_shift**(const q7_t *pSrc, q15_t *pDst, uint32_t blockSize)

Converts the elements of the Q7 vector to reordered Q15 vector without left-shift.

Converts the elements of the s8 vector to reordered q15 vector without left-shift.

This function does the q7 to q15 expansion with re-ordering

is converted into:

This looks strange but is natural considering how sign-extension is done at assembly level.

The expansion of other other oprand will follow the same rule so that the end results are the same.

The tail (i.e., last (N % 4) elements) will still be in original order.

Parameters

- ***pSrc** – **[in]** points to the Q7 input vector
- ***pDst** – **[out]** points to the Q15 output vector
- **blockSize** – **[in]** length of the input vector

void **riscv_q7_to_q15_reordered_with_offset**(const q7_t *src, q15_t *dst, uint32_t block_size, q15_t offset)

Converts the elements of the Q7 vector to a reordered Q15 vector with an added offset.

Converts the elements from a s8 vector to a s16 vector with an added offset.

Note: Refer header file for details.

---

void **riscv_q7_to_q7_no_shift**(const q7_t *pSrc, q7_t *pDst, uint32_t blockSize)

Converts the elements of the Q7 vector to Q7 vector without left-shift.

The equation used for the conversion process is:

Description:

Parameters

- ***pSrc** – **[in]** points to the Q7 input vector
- ***pDst** – **[out]** points to the Q7 output vector
- **blockSize** – **[in]** length of the input vector

Returns none.

void **riscv_q7_to_q7_reordered_no_shift**(const q7_t *pSrc, q7_t *pDst, uint32_t blockSize)

Converts the elements of the Q7 vector to reordered Q7 vector without left-shift.

This function does the q7 to q7 expansion with re-ordering is converted into:

This looks strange but is natural considering how sign-extension is done at assembly level.

The expansion of other other oprand will follow the same rule so that the end results are the same.

The tail (i.e., last (N % 4) elements) will still be in original order.

Parameters

- `*pSrc` – **[in]** points to the Q7 input vector
- `*pDst` – **[out]** points to the Q7 output vector
- `blockSize` – **[in]** length of the input vector

Returns none.

SupportConversion

void **riscv_q7_to_q15_with_offset**(const int8_t *src, int16_t *dst, int32_t block_size, int16_t offset)

group `SupportConversion`

Functions

void **riscv_q7_to_q15_with_offset**(const int8_t *src, int16_t *dst, int32_t block_size, int16_t offset)

Converts the elements from a s8 vector to a s16 vector with an added offset.

Output elements are ordered. The equation used for the conversion process is:

Description:

Parameters

- `src` – **[in]** pointer to the s8 input vector
- `dst` – **[out]** pointer to the s16 output vector
- `block_size` – **[in]** length of the input vector
- `offset` – **[in]** s16 offset to be added to each input vector element.

group `groupSupport`

Perform data type conversion in-between neural network operations.

4.4 Changelog

4.4.1 V1.2.0

Note:

- This 1.2.0 version will no longer support old gcc 10 verison, and it now only support Nuclei Toolchain 2023.10(gcc13 and clang17) or later. The major changes that can be felt are as follows:
- The prefix of toolchain has changed from `riscv-nuclei-elf-` to `riscv64-unknown-elf-`
- The `-march` option has changed a lot, for example:
  - `b` extension changed to `_zba_zbb_zbc_zbs` extension,
  - `p` extension changed to `_xxldsp` or `_xxldspn1x` or `_xxldspn2x` or `_xxldspn3x` extensions which means stardard DSP extension, Nuclei N1, N2, N3 DSP extensions
  - `v` extension changed to `v` or `_zve32f` or `_zve64f` extensions according to the riscv cpu isa used

  These extensions need be combined in a certain order to get a correct arch name to match the prebuilt library name, please be cautious
- The name of libraries changed due to `-march` in gcc13 updated, for example, the library named `libnmsis_nn_rv32imacb.a` is now named `libnmsis_nn_rv32imac_zba_zbb_zbc_zbs.a` since `b` extension changed to `_zba_zbb_zbc_zbs`

This is release `1.2.0` version of NMSIS-NN library.

- Defined `NUCLEI_DSP_DEFAULT`, `NUCLEI_DSP_N1`, `NUCLEI_DSP_N2`, `NUCLEI_DSP_N3` in `riscv_nn_math_types.h` according to gcc options now, no longer define it in cmake files.
- RVV intrinsic APIs is update to v0.12.0
- Clean code(nnref lib)

4.4.2 V1.1.1

This is release `1.1.1` version of NMSIS-NN library.

- Sync changes from CMSIS NN v4.1.0
- Optimized more for RVP/RVV
- Add support for RV32 Vector
- Some bugfix that make tflite-micro test successfully

4.4.3 V1.1.0

This is release `1.1.0` version of NMSIS-NN library.

- Sync changes from CMSIS 5.9.0 release
- Optimized more for RVP/RVV
- Add experimental support for RV32 Vector

4.4.4 V1.0.3

This is release `1.0.3` version of NMSIS-NN library.

- Update build system for NMSIS-NN library
- Rename `RISCV_VECTOR` to `RISCV_MATH_VECTOR` in header file and source code
- Using new python script to generate NMSIS-NN library
- Support Nuclei RISC-V GCC 10.2

4.4.5 V1.0.2

This is release `1.0.2` version of NMSIS-NN library.

- Sync up to CMSIS NN library 3.0.0
- Initial support for RISC-V vector extension support

4.4.6 V1.0.1

This is release `V1.0.1` version of NMSIS-DSP library.

- Both Nuclei RISC-V 32 and 64 bit cores are supported now.
- Libraries are optimized for RISC-V 32 and 64 bit DSP instructions.
- The DSP examples are now using Nuclei SDK as running environment.

4.4.7 V1.0.0

This is the first version of NMSIS-NN library.

We adapt the CMSIS-NN v1.0.0 library to use RISCV DSP instructions, all the API names now are renamed from `arm_xxx` to `riscv_xxx`.

CHAPTER FIVE

CHANGELOG

5.1 V1.2.0

This is the version `V1.2.0` release.

Note:

- This 1.2.0 version will no longer support old gcc 10 verison, and it now only support Nuclei Toolchain 2023.10 (gcc13 and clang17) or later. The major changes that can be felt are as follows:
- The prefix of toolchain has changed from `riscv-nuclei-elf-` to `riscv64-unknown-elf-`
- The `-march` option has changed a lot, see https://github.com/riscv-non-isa/riscv-toolchain-conventions/pull/26, for examples:
  - `b` extension changed to `_zba_zbb_zbc_zbs` extension,
  - `p` extension changed to `_xxldsp` , `_xxldspn1x` , `_xxldspn2x` , `_xxldspn3x` extensions which means stardard DSP extension, Nuclei N1, N2, N3 DSP extensions
  - `v` extension changed to `v`, `_zve32f`, `_zve64f` extensions

  These extensions also can be combined in a certain order, please be cautious
- The name of Libraries has changed with `-march`, for examples, the library named `libnmsis_dsp_rv32imacb.a` is now named `libnmsis_dsp_rv32imac_zba_zbb_zbc_zbs.a` since `b` extension changed to `_zba_zbb_zbc_zbs`
- NMSIS v1.2.0 should be used with Nuclei SDK v0.5.0 or later
- RVV intrinsic APIs is update to v0.12.0, please visit rvv-intrinsic-doc[24]

- **NMSIS-Core**
  - Add more Nuclei DSP N1/N2/N3 intrinsic APIs and fix some intrinsic API definition and descriptions in `core_feature_dsp.h`
  - Add basic IAR support for NMSIS Core header files and device template, for sample usage, see Nuclei SDK 0.5.0 release
  - Fix missing break in `__set_hpm_event` function API in core_feature_base.h, which affected the nmsis_bench.h
  - Use IAR custom instruction and IAR P-ext 0.5.0 support to support Nuclei DSP extension based on P-ext 0.5.4, see changes maded in `core_feature_dsp.h`, only Xxldsp is supported, no N1/N2/N3 supported,

[24] https://github.com/riscv-non-isa/rvv-intrinsic-doc/releases/tag/v0.12.0

and some instructions can't be supported using custom instruction, but in future, we will cooperate with IAR to do full Nuclei DSP support

- Add more CSRs definition according to Nuclei ISA updates such as Zc/stack check
- No more bitmanip extension intrinsic header <rvintrin.h> for gcc13
- Fix __RV_CLAMP macro and add __MACHINE/SUPERVISOR/USER_INTERRUPT macros
- Add __get_hart_index and SysTimer_GetHartID and modify __get_hart_id API
- In <Device.h>, we introduced __HARTID_OFFSET and __SYSTIMER_HARTID macro to represent timer hart index relation with cpu hartid for AMP SoC
- Clean compiler warning of NMSIS-Core header files
- Fix Cache CCM API missing return value in some case

- **NMSIS-DSP**
  - Defined `NUCLEI_DSP_DEFAULT`, `NUCLEI_DSP_N1`, `NUCLEI_DSP_N2`, `NUCLEI_DSP_N3` in `riscv_math_types.h` according to gcc options. This means that if compile with `--march=rv32imafc_xxldspn1x`, the `NUCLEI_DSP_N1` will defined, if compile with `--march=rv32imafc_xxldspn2x`, the `NUCLEI_DSP_N1` and `NUCLEI_DSP_N2` will defined, and so on
  - Optimize some functions with DSP N1/N2/N3 (such as FilteringFunctions, TransformFunctions, ComplexMathFunctions)
  - RVV intrinsic APIs is update to v0.12.0
  - Add f16 support(include f16 rvv extension support)
  - Fix the use of expd80 instruction(Nuclei default dsp instruction)
  - Fix some testcases bugs(such as MatrixFunctions, TransformFunctions)
- **NMSIS-NN**
  - Defined `NUCLEI_DSP_DEFAULT`, `NUCLEI_DSP_N1`, `NUCLEI_DSP_N2`, `NUCLEI_DSP_N3` in `riscv_nn_math_types.h` according to gcc options
  - RVV intrinsic APIs is update to v0.12.0
  - Clean code(nnref lib)
- **Build System**
  - Toolchain change to gcc13, The prefix of toolchain has changed to `riscv64-unknown-elf-`, old gcc10 `riscv-nuclei-elf-gcc` changed to gcc 13 `riscv64-unknown-elf-gcc`
  - Add ci configurations to support different instruction combinations, please check `Scripts/Build/nmsis_dsp.json` and `Scripts/Build/nmsis_nn.json`
  - Library naming scheme changed due to march changes, which means the library name will not be compatiable with previous release, check dsp/nn get started guide for details
  - F16 library build is supported now when zfh/zvfh extension enabled
- **CI**
  - Change NMSIS to use Nuclei SDK evalsoc as ci run target, demosoc is removed in 0.5.0 Nuclei SDK release.
  - Spilt DSP and NN test jobs to reduce ci running time

  - Build DSP/NN library in one job now, since N1/N2/N3 library naming are different, and library build speed for risc-v vector increased now

5.2 V1.1.1

This is the version `V1.1.1` release.

- **NMSIS-Core**
  - Add CIDU support via core_feature_cidu.h, and `__CIDU_PRESENT` macro is required in `<Device>.h` to represent CIDU present or not
  - Add macros of HPM m/s/u event enable, events type, events idx
  - Fix define error of HPM_INIT macro
  - Update systimer/pmp/spmp/eclic API comment and implementation
  - Add Cache ECC related APIs
  - Due to mhartid csr update, two new API added called `__get_hart_id` and `__get_cluster_id`
    * mhartid in Nuclei RISC-V processor are now used to present cluster id and hart id
    * bit 0-7 is used for hart id in current cluster
    * bit 8-15 is used for cluster id of current cluster
- **NMSIS-DSP**
  - Sync with CMSIS-DSP library(branch:main, commit id:1d9e38a, after CMSIS-DSP v1.14.4)
  - Optimize some functions with RVV(such as: ComplexMathFunctions, FilteringFunctions, MatrixFunctions, StatisticsFunctions, etc.)
  - Some bugfix(riscv_mat_inverse_f32.c rvv fix, riscv_offset_q15.c p fix, riscv_fir_q15.c rvv fix etc.)
- **NMSIS-NN**
  - Sync with CMSIS-NN library(branch:main, commit id:61d1bb6, CMSIS-NN v4.1.0)
  - Compile independent, no longer depend on NMSIS-DSP
  - Optimize some functions with RVV(such as: ActivationFunctions, FullyConnectedFunctions, PoolingFunctions, etc.)
  - Some bugfix that make tflite-micro test successfully
- Documentation
  - Update sphinx and doxygen document version to 1.1.1
  - Use mathjax to render latex formulas instead of latex, which can avoid strange compile error
  - Change dsp/nn sphinx rst document structure to match dsp/nn doxygen documentation update
- NPK
  - Add `nmsis_dsp_nn` choice for `nmsislibsel`, it will select nmsis dsp and nn library
  - `nmsis_nn` library no longer select dsp library, since now it can live without dsp library

5.3 V1.1.0

This is the version `V1.1.0` release of Nuclei MCU Software Interface Standard(NMSIS).

- **NMSIS-Core**
  - Add `nmsis_bench.h` for benchmark and hpm helper functions.
  - Add hpm related API
  - Update `riscv_encoding.h` for latest riscv changes.
  - Add `core_feature_spmp.h` for TEE/sPMP unit.
  - Add more Nuclei DSP N1/N2/N3 intrinsic APIs in `core_feature_dsp.h`
  - Bring SMP/AMP support in `core_feature_eclic.h` and `core_feature_timer.h`
- **NMSIS-DSP**
  - Sync with DSP library in CMSIS 5.9.0 release.
  - Add experimental RV32 Vector support.
  - Optimize with RVP/RVV for DSP library.
- **NMSIS-NN**
  - Sync with NN library in CMSIS 5.9.0 release.
  - Add experimental RV32 Vector support.
  - Optimize with RVP/RVV for NN library.
- **Build System**
  - **DSP64** is removed, and replaced by **NUCLEI_DSP_N1**, which means Nuclei DSP N1 extension present.
  - **NUCLEI_DSP_N2** and **NUCLEI_DSP_N3** are introduced to standard for Nuclei DSP N2/N3 extension present.
  - Now you build different DSP/NN library optimized Nuclei DSP N1/N2/N3 via command such as `make NUCLEI_DSP=N1 gen`
  - Add `nmsis_help` make target to show help message to build nmsis dsp/nn library.
  - Add `check_build` and `check_run` make target for locally build or run on a small test suite configuration.
  - Add fpga related test script located in `Scripts/Configs/fpga/`.
  - Fix bugs found in `nlbuild.py` script.
- **Device Tempates**
  - Update Device templates to support SMP/AMP and new linker script changes to align with Nuclei SDK 0.4.0
- **CI**
  - Misc changes for github and gitlab ci, see commit history
  - gitlab ci will now test `NUCLEI_DSP=NO/N1/N2/N3` cases and also check rv32 with VPU for DSP/NN test cases
- **Documentation**
  - Update Core/DSP/NN documentation
- **Misc**

- Nuclei SDK 0.4.0 will use NMSIS 1.1.0

5.4 V1.0.4

This is the version `V1.0.4` release of Nuclei MCU Software Interface Standard(NMSIS).

- **NMSIS-Core**
  - add `__CCM_PRESENT` macro in NMSIS-Core, if CCM hardware unit is present in your CPU, `__CCM_PRESENT` macro need to be set to 1 in `<Device>.h`
  - Fixed mtvec related api comment in `core_feature_eclic.h`
  - Add safely write mtime/mtimecmp register for 32bit risc-v processor
  - rearrage #include header files for all NMSIS Core header files
  - removed some not good #pragma gcc diagnostic lines in `nmsis_gcc.h`
- **NMSIS-DSP**
  - Add initial bitmainp extension support
  - Fix bug in riscv_cmplx_mult_cmplx_q15 function when XLEN=64
- **NMSIS-NN**
  - Add initial bitmainp extension support
  - Change riscv_maxpool_q7_HWC implementation for rvv
  - Re-org NN_Lib_Tests to Tests
- **Build System**
  - Change minimal version of cmake to 3.14
  - Add REBUILD=0 to reuse previous generated Makefile
- **Device Tempates**
  - Fix bss section lma and vma not aligned and tbss space not reserved
- **CI**
  - Change NMSIS to use Nuclei SDK demosoc as ci run target
  - only run ci on master/develop branch
- **Documentation**
  - Update get started guide for dsp/nn library

5.5 V1.0.3

This is the official release version `V1.0.3` release of Nuclei MCU Software Interface Standard(NMSIS).

This release is only supported by Nuclei GNU Toolchain 2022.01 and its later version, since it required intrinsic header files in RISC-V GCC for B/P/V extensions.

The following changes has been made since `V1.0.2`.

- **Documentation**

- Update NMSIS Core/DSP/NN related documentation

- **Device Templates**
  - Add `__INC_INTRINSIC_API`, `__BITMANIP_PRESENT` and `__VECTOR_PRESENT` in `<Device>.h`
  - Add more REG/ADDR/BIT access macros in `<Device>.h`
  - Update linker script for `<Device>.ld` for Nuclei C Runtime Library
  - Add tp register initialization and add early exception setup during startup in `startup_<Device>.S`
  - Adding support for Nuclei C Runtime library
- **NMSIS-Core**
  - Update `core_feature_eclic.h`, `core_feature_timer.h` and `core_feature_dsp.h`
  - Added `core_feature_vector.h` and `core_feature_bitmainp.h`
  - Add more nuclei customized csr in `riscv_encoding.h`
  - Include rvb/rvp/rvv header files when __INC_INTRINSIC_API = 1
- **NMSIS-DSP/NN**
  - Add support for Nuclei GNU Toolchain 2021.12
  - Add new build system to generate NMSIS DSP and NN library
  - Update cmake files for both DSP and NN library
  - No need to define `__RISCV_FEATURE_DSP` and `__RISCV_FEATURE_VECTOR` when using DSP or NN library, it will be defined in `riscv_math_types.h` via the predefined macros in Nuclei RISC-V gcc 10.2
  - Rename `RISCV_VECTOR` to `RISCV_MATH_VECTOR`
  - Fix FLEN and XLEN mis-usage in library

5.6 V1.0.2

This is the official release version `V1.0.2` release of Nuclei MCU Software Interface Standard(NMSIS).

The following changes has been made since `V1.0.1`.

- **Documentation**
  - Update NMSIS Core/DSP/NN related documentation
- **Device Templates**
  - DOWNLOAD_MODE_xxx macros are removed from riscv_encoding.h, it is now defined as enum in <`Device.h`>, and can be customized by soc vendor.
  - startup code now don't rely on DOWNLOAD_MODE macro, instead it now rely on a new macro called VECTOR_TABLE_REMAPPED, when VECTOR_TABLE_REMAPPED is defined, it means the vector table's lma != vma, such as vector table need to be copied from flash to ilm when boot up
  - Add more customized csr of Nuclei RISC-V Core
  - Add **BIT**, **BITS**, **REG**, **ADDR** related macros in <`Device.h`>
- **NMSIS-Core**
  - Nuclei Cache CCM operation APIs are now introduced in core_feature_cache.h
  - Update NMSIS-Core header files

- **NMSIS-DSP/NN**
  - Merged the official CMSIS 5.8.0 release, CMSIS-DSP 1.9.0, CMSIS-NN 3.0.0
  - RISC-V Vector extension and P-extension support for DSP/NN libraries are added

5.7 V1.0.2-RC2

This is the release candidate version `V1.0.2-RC2` release of Nuclei MCU Software Interface Standard(NMSIS).

The following changes has been made since `V1.0.2-RC1`.

- **Documentation**
  - Update NMSIS Core/DSP/NN related documentation

5.8 V1.0.2-RC1

This is the release candidate version `V1.0.2-RC1` release of Nuclei MCU Software Interface Standard(NMSIS).

The following changes has been made since `V1.0.1`.

- **Device Templates**
  - DOWNLOAD_MODE_xxx macros are removed from riscv_encoding.h, it is now defined as enum in <`Device.h`>, and can be customized by soc vendor.
  - startup code now don't rely on DOWNLOAD_MODE macro, instead it now rely on a new macro called VECTOR_TABLE_REMAPPED, when VECTOR_TABLE_REMAPPED is defined, it means the vector table's lma != vma, such as vector table need to be copied from flash to ilm when boot up
  - Add **BIT**, **BITS**, **REG**, **ADDR** related macros in <`Device.h`>
- **NMSIS-Core**
  - Nuclei Cache CCM operation APIs are now introduced in core_feature_cache.h
- **NMSIS-DSP/NN**
  - Merged the official CMSIS 5.8.0 release, CMSIS-DSP 1.9.0, CMSIS-NN 3.0.0
  - RISC-V Vector extension and P-extension support for DSP/NN libraries are added

5.9 V1.0.1

This is the official `V1.0.1` release of Nuclei MCU Software Interface Standard(NMSIS).

The following changes has been maded since `V1.0.1-RC1`.

- **Device Templates**
  - I/D Cache enable assemble code in startup_<Device>.S are removed now
  - Cache control updates in System_<Device>.c
    - I-Cache will be enabled if __ICACHE_PRESENT = 1 defined in <Device.h>
    - D-Cache will be enabled if __DCACHE_PRESENT = 1 defined in <Device.h>

5.10 V1.0.1-RC1

This is release candidate version `V1.0.1-RC1` of NMSIS.

- **NMSIS-Core**
  - Add RISC-V DSP 64bit intrinsic functions in `core_feature_dsp.h`
  - Add more CSR definitions in `riscv_encoding.h`
  - Update arm compatiable functions for RISC-V dsp instruction cases in `core_compatiable.h`
- **NMSIS-DSP**
  - Optimize RISC-V 32bit DSP library implementation
  - Add support for Nuclei RISC-V 64bit DSP SIMD instruction for DSP library
  - Add test cases used for DSP library testing, mainly for internal usage
  - Change the examples and tests to use Nuclei SDK as running environment
- **NMSIS-NN**
  - Add support for Nuclei RISC-V 64bit DSP SIMD instruction for NN library
  - Change the examples and tests to use Nuclei SDK as running environment
- **Device Templates**
  - Add `DDR DOWNLOAD_MODE` in device templates
  - Modifications to `startup_<Device>.S` files
    * `_premain_init` is added to replace `_init`
    * `_postmain_fini` is added to replace `_fini`
  - If you have implemented your init or de-init functions through `_init` or `_fini`, please use `_premain_init` and `_postmain_fini` functions defined `system_<Device>.c` now

5.11 V1.0.0-beta1

Main changes in release **V1.0.0-beta1**.

- **NMSIS-Core**
  - Fix `SysTick_Reload` implementation
  - Update `ECLIC_Register_IRQ` implementation to allow handler == NULL
  - Fix `MTH` offset from 0x8 to 0xB, this will affect function of `ECLIC_GetMth` and `ECLIC_SetMth`
  - Fix wrong macro check in cache function
  - Add missing `SOC_INT_MAX` enum definition in Device template
  - In `System_<Device>.c`, ECLIC NLBits set to `__ECLIC_INTCTLBITS`, which means all the bits are for level, no bits for priority

5.12 V1.0.0-beta

Main changes in release **V1.0.0-beta**.

- **NMSIS-Core**
  - Fix error typedef of `CSR_MCAUSE_Type`
  - Change `CSR_MCACHE_CTL_DE` to future value `0x00010000`
  - Fix names in CSR naming, `CSR_SCRATCHCSW -> CSR_MSCRATCHCSW`, and `CSR_SCRATCHCSWL -> CSR_MSCRATCHCSWL`
  - Add macros in `riscv_encoding.h`: `MSTATUS_FS_INITIAL`, `MSTATUS_FS_CLEAN`, `MSTATUS_FS_DIRTY`
- **Documentation**
  - Fix an typo in *core_template_intexc.rst*
  - Add cross references of Nuclei ISA Spec
  - Update appendix
  - Refines tables and figures

5.13 V1.0.0-alpha.1

API changes has been maded to system timer.

- Start from Nuclei N core version 1.4, MSTOP register is renamed to MTIMECTL to provide more features
- Changes made to NMSIS/Core/core_feature_timer.h
  - MSTOP register name changed to MTIMECTL due to core spec changes
  - SysTimer_SetMstopValue renamed to SysTimer_SetControlValue
  - SysTimer_GetMstopValue renamed to SysTimer_GetControlValue
  - Add SysTimer_Start and SysTimer_Stop to start or stop system timer counter
  - SysTick_Reload function is introduced to reload system timer
  - Macro names started with SysTimer_xxx are changed, please check in the code.
- Removed unused lines of code in DSP and NN library source code which has unused macros which will not work for RISCV cores.
- Fix some documentation issues, mainly typos and invalid cross references.

5.14 V1.0.0-alpha

This is the `V1.0.0-alpha` release of Nuclei MCU Software Interface Standard(NMSIS).

In this release, we have release three main compoments:

- **NMSIS-Core**: Standardized API for the Nuclei processor core and peripherals.
- **NMSIS-DSP**: DSP library collection optimized for the Nuclei Processors which has RISC-V SIMD instruction set.

- **NMSIS-NN**: Efficient neural network library developed to maximize the performance and minimize the memory footprint Nuclei Processors which has RISC-V SIMD instruction set.

We also released totally new Nuclei-SDK[25] which is an SDK implementation based on the **NMSIS-Core** for Nuclei N/NX evaluation cores running on HummingBird Evaluation Kit.

[25] https://github.com/Nuclei-Software/nuclei-sdk

CHAPTER SIX

GLOSSARY

API (Application Program Interface) A defined set of routines and protocols for building application software.

DSP (Digital Signal Processing) is the use of digital processing, such as by computers or more specialized digital signal processors, to perform a wide variety of signal processing operations.

ISR (Interrupt Service Routine) Also known as an interrupt handler, an ISR is a callback function whose execution is triggered by a hardware interrupt (or software interrupt instructions) and is used to handle high-priority conditions that require interrupting the current code executing on the processor.

NN (Neural Network) is a network or circuit of neurons, or in a modern sense, an artificial neural network, composed of artificial neurons or nodes.

XIP (eXecute In Place) a method of executing programs directly from long term storage rather than copying it into RAM, saving writable memory for dynamic data and not the static program code.

CHAPTER

SEVEN

APPENDIX

- **Nuclei Tools and Documents**: https://nucleisys.com/download.php
- **Nuclei Software Opensource Organization**: https://github.com/Nuclei-Software
- **RISC-V MCU Opensource Organization**: https://github.com/riscv-mcu
- **Nuclei Toolchain Repo**: https://github.com/riscv-mcu/riscv-gnu-toolchain
- **Nuclei OpenOCD Repo**: https://github.com/riscv-mcu/riscv-openocd
- **Nuclei QEMU Repo**: https://github.com/riscv-mcu/qemu
- **Nuclei SDK**: https://github.com/Nuclei-Software/nuclei-sdk
- **NMSIS**: https://github.com/Nuclei-Software/NMSIS
- **Nuclei RISC-V IP Products**: https://www.nucleisys.com/product.php
- **RISC-V MCU Community Website**: https://www.riscv-mcu.com/
- **Nuclei RISC-V CPU Spec**: https://doc.nucleisys.com/nuclei_spec
- **RISC-V ISA Specfications(Ratified)**: https://riscv.org/technical/specifications
- **RISC-V Architecture Profiles**: https://github.com/riscv/riscv-profiles
- **RISC-V Bitmanip(B) Extension Spec**: https://github.com/riscv/riscv-bitmanip
- **RISC-V Packed SIMD(P) Extension Spec**: https://github.com/riscv/riscv-p-spec
- **RISC-V Cryptography(K) Extension Spec**: https://github.com/riscv/riscv-crypto
- **RISC-V Vector(V) Extension Spec**: https://github.com/riscv/riscv-v-spec
- **RISC-V Vector Intrinsic API Spec**: https://github.com/riscv-non-isa/rvv-intrinsic-doc
- **RISC-V ISA Extension Spec Status**: https://wiki.riscv.org/display/HOME/Specification+Status
- **Nuclei Bumblebee Core Document**: https://github.com/nucleisys/Bumblebee_Core_Doc

CHAPTER

EIGHT

INDICES AND TABLES

- genindex
- search

INDEX

Symbols

_FLD2VAL (*C macro*), 540, 541
_VAL2FLD (*C macro*), 540, 541
__ALIGNED (*C macro*), 79
__ASM (*C macro*), 78
__CLZ (*C macro*), 637
__COMPILER_BARRIER (*C macro*), 79
__CPU_RELAX (*C macro*), 149
__DMB (*C macro*), 636
__DSB (*C macro*), 636
__EXPD_BYTE (*C macro*), 637
__FENCE (*C macro*), 149
__I (*C macro*), 540
__IM (*C macro*), 540, 541
__INLINE (*C macro*), 78
__INTERRUPT (*C macro*), 79
__IO (*C macro*), 540
__IOM (*C macro*), 540, 541
__ISB (*C macro*), 636
__LDRBT (*C macro*), 636
__LDRHT (*C macro*), 636
__LDRT (*C macro*), 636
__MACHINE_INTERRUPT (*C macro*), 79
__NMSIS_VERSION (*C macro*), 77
__NMSIS_VERSION_MAJOR (*C macro*), 77
__NMSIS_VERSION_MINOR (*C macro*), 77
__NMSIS_VERSION_PATCH (*C macro*), 77
__NO_RETURN (*C macro*), 78
__NUCLEI_CPU_REV (*C macro*), 77
__NUCLEI_CPU_SERIES (*C macro*), 77
__NUCLEI_NX_REV (*C macro*), 77
__NUCLEI_N_REV (*C macro*), 77
__O (*C macro*), 540
__OM (*C macro*), 540, 541
__PACKED (*C macro*), 78
__PACKED_STRUCT (*C macro*), 79
__PACKED_UNION (*C macro*), 79
__RARELY (*C macro*), 79
__RBIT (*C macro*), 636
__RESTRICT (*C macro*), 79
__RISCV_FLEN (*C macro*), 589
__RISCV_XLEN (*C macro*), 126
__RMB (*C macro*), 149
__RV_BITREVI (*C macro*), 280
__RV_CSR_CLEAR (*C macro*), 81
__RV_CSR_READ (*C macro*), 80
__RV_CSR_READ_CLEAR (*C macro*), 81
__RV_CSR_READ_SET (*C macro*), 81
__RV_CSR_SET (*C macro*), 81
__RV_CSR_SWAP (*C macro*), 80
__RV_CSR_WRITE (*C macro*), 81
__RV_DSCLIP16 (*C macro*), 449, 461
__RV_DSCLIP32 (*C macro*), 449, 462
__RV_DSCLIP8 (*C macro*), 449, 460
__RV_FLD (*C macro*), 590
__RV_FLOAD (*C macro*), 591
__RV_FLW (*C macro*), 589
__RV_FSD (*C macro*), 591
__RV_FSTORE (*C macro*), 592
__RV_FSW (*C macro*), 590
__RV_INSB (*C macro*), 280
__RV_KSLLI16 (*C macro*), 187, 188
__RV_KSLLI32 (*C macro*), 398
__RV_KSLLI8 (*C macro*), 199, 200
__RV_KSLLIW (*C macro*), 260
__RV_SCLIP16 (*C macro*), 233, 234
__RV_SCLIP32 (*C macro*), 334, 335
__RV_SCLIP8 (*C macro*), 240, 241
__RV_SLLI16 (*C macro*), 187, 188
__RV_SLLI32 (*C macro*), 398, 399
__RV_SLLI8 (*C macro*), 199, 200
__RV_SRAI16 (*C macro*), 187, 189
__RV_SRAI16_U (*C macro*), 187, 190
__RV_SRAI32 (*C macro*), 398, 399
__RV_SRAI32_U (*C macro*), 398, 400
__RV_SRAI8 (*C macro*), 199, 201
__RV_SRAI8_U (*C macro*), 199, 202
__RV_SRAIW_U (*C macro*), 438
__RV_SRAI_U (*C macro*), 280, 281
__RV_SRLI16 (*C macro*), 187, 190
__RV_SRLI16_U (*C macro*), 187, 191
__RV_SRLI32 (*C macro*), 398, 401
__RV_SRLI32_U (*C macro*), 398, 401
__RV_SRLI8 (*C macro*), 199, 202

__RV_SRLI8_U (*C macro*), 199, 203
__RV_UCLIP16 (*C macro*), 233, 234
__RV_UCLIP32 (*C macro*), 334, 335
__RV_UCLIP8 (*C macro*), 240, 241
__RV_WEXTI (*C macro*), 280, 282
__RWMB (*C macro*), 149
__SMP_RMB (*C macro*), 149
__SMP_RWMB (*C macro*), 149
__SMP_WMB (*C macro*), 149
__SSAT (*C macro*), 636
__STATIC_FORCEINLINE (*C macro*), 78
__STATIC_INLINE (*C macro*), 78
__STRBT (*C macro*), 636
__STRHT (*C macro*), 636
__STRT (*C macro*), 636
__SUPERVISOR_INTERRUPT (*C macro*), 79
__UNALIGNED_UINT16_READ (*C macro*), 79
__UNALIGNED_UINT16_WRITE (*C macro*), 79
__UNALIGNED_UINT32_READ (*C macro*), 79
__UNALIGNED_UINT32_WRITE (*C macro*), 79
__USAT (*C macro*), 636
__USED (*C macro*), 78
__USER_INTERRUPT (*C macro*), 79
__USUALLY (*C macro*), 79
__VECTOR_SIZE (*C macro*), 78
__WEAK (*C macro*), 78
__WMB (*C macro*), 149
__disable_FPU (*C macro*), 589
__enable_FPU (*C macro*), 589
__get_FCSR (*C macro*), 589
__get_FFLAGS (*C macro*), 589
__get_FRM (*C macro*), 589
__has_builtin (*C macro*), 78
__set_FCSR (*C macro*), 589
__set_FFLAGS (*C macro*), 589
__set_FRM (*C macro*), 589
__sync_harts (*C++ function*), 630
_fini (*C++ function*), 631
_get_iregion_info (*C++ function*), 630
_init (*C++ function*), 631
_postmain_fini (*C++ function*), 631
_premain_init (*C++ function*), 630

A

API, **1137**

B

BREAKPOINT (*C macro*), 125

C

CacheInfo (*C++ struct*), 600, 603
CAUSE_BREAKPOINT (*C macro*), 124
CAUSE_FAULT_FETCH (*C macro*), 124
CAUSE_FAULT_LOAD (*C macro*), 124
CAUSE_FAULT_STORE (*C macro*), 124
CAUSE_FETCH_PAGE_FAULT (*C macro*), 125
CAUSE_HYPERVISOR_ECALL (*C macro*), 124
CAUSE_ILLEGAL_INSTRUCTION (*C macro*), 124
CAUSE_LOAD_PAGE_FAULT (*C macro*), 125
CAUSE_MACHINE_ECALL (*C macro*), 125
CAUSE_MISALIGNED_FETCH (*C macro*), 124
CAUSE_MISALIGNED_LOAD (*C macro*), 124
CAUSE_MISALIGNED_STORE (*C macro*), 124
CAUSE_STORE_PAGE_FAULT (*C macro*), 125
CAUSE_SUPERVISOR_ECALL (*C macro*), 124
CAUSE_USER_ECALL (*C macro*), 124
CCM_CMD (*C++ enum*), 600, 601
CCM_CMD::CCM_DC_INVAL (*C++ enumerator*), 600, 601
CCM_CMD::CCM_DC_INVAL_ALL (*C++ enumerator*), 600, 602
CCM_CMD::CCM_DC_LOCK (*C++ enumerator*), 600, 602
CCM_CMD::CCM_DC_UNLOCK (*C++ enumerator*), 600, 602
CCM_CMD::CCM_DC_WB (*C++ enumerator*), 600, 602
CCM_CMD::CCM_DC_WB_ALL (*C++ enumerator*), 600, 602
CCM_CMD::CCM_DC_WBINVAL (*C++ enumerator*), 600, 602
CCM_CMD::CCM_DC_WBINVAL_ALL (*C++ enumerator*), 600, 602
CCM_CMD::CCM_IC_INVAL (*C++ enumerator*), 600, 602
CCM_CMD::CCM_IC_INVAL_ALL (*C++ enumerator*), 600, 602
CCM_CMD::CCM_IC_LOCK (*C++ enumerator*), 600, 602
CCM_CMD::CCM_IC_UNLOCK (*C++ enumerator*), 600, 602
CCM_COMMAND_COMMAND (*C macro*), 119
CCM_DATA_DATA (*C macro*), 119
CCM_OP_FINFO (*C++ enum*), 599, 601
CCM_OP_FINFO::CCM_OP_ECC_ERR (*C++ enumerator*), 600, 601
CCM_OP_FINFO::CCM_OP_EXCEED_ERR (*C++ enumerator*), 599, 601
CCM_OP_FINFO::CCM_OP_PERM_CHECK_ERR (*C++ enumerator*), 599, 601
CCM_OP_FINFO::CCM_OP_REFILL_BUS_ERR (*C++ enumerator*), 599, 601
CCM_OP_FINFO::CCM_OP_SUCCESS (*C++ enumerator*), 599, 601
CCM_SUEN_SUEN (*C macro*), 119
CCM_SUEN_SUEN_Msk (*C macro*), 600, 601
CFFTINIT_F16 (*C macro*), 899
CFFTINIT_F32 (*C macro*), 903, 904
CFFTINIT_F64 (*C macro*), 907, 908
CFFTINIT_Q15 (*C macro*), 911, 912
CFFTINIT_Q31 (*C macro*), 915, 916
CLIC_CLICCFG_NLBIT_Msk (*C macro*), 141
CLIC_CLICCFG_NLBIT_Pos (*C macro*), 141

CLIC_CLICINFO_CTLBIT_Msk (*C macro*), 141
CLIC_CLICINFO_CTLBIT_Pos (*C macro*), 141
CLIC_CLICINFO_NUM_Msk (*C macro*), 142
CLIC_CLICINFO_NUM_Pos (*C macro*), 142
CLIC_CLICINFO_VER_Msk (*C macro*), 142
CLIC_CLICINFO_VER_Pos (*C macro*), 141
CLIC_CTRL_Type (*C++ struct*), 144
CLIC_INTATTR_MODE_Msk (*C macro*), 142
CLIC_INTATTR_MODE_Pos (*C macro*), 142
CLIC_INTATTR_SHV_Msk (*C macro*), 142
CLIC_INTATTR_SHV_Pos (*C macro*), 142
CLIC_INTATTR_TRIG_Msk (*C macro*), 142
CLIC_INTATTR_TRIG_Pos (*C macro*), 142
CLIC_INTIE_IE_Msk (*C macro*), 142
CLIC_INTIE_IE_Pos (*C macro*), 142
CLIC_INTIP_IP_Msk (*C macro*), 142
CLIC_INTIP_IP_Pos (*C macro*), 142
CLIC_Type (*C++ struct*), 144
CLICCFG_Type (*C++ union*), 143
CLICCFG_Type::b (*C++ member*), 144
CLICCFG_Type::w (*C++ member*), 144
CLICINFO_Type (*C++ union*), 144
CLICINFO_Type::b (*C++ member*), 144
CLINT_MSIP (*C macro*), 628
core_exception_handler (*C++ function*), 633
core_exception_handler_s (*C++ function*), 634
cos_factors_128 (*C++ member*), 931, 932
cos_factors_2048 (*C++ member*), 931, 932
cos_factors_512 (*C++ member*), 931, 932
cos_factors_8192 (*C++ member*), 931, 932
cos_factorsQ31_128 (*C++ member*), 931, 932
cos_factorsQ31_2048 (*C++ member*), 931, 933
cos_factorsQ31_512 (*C++ member*), 931, 933
cos_factorsQ31_8192 (*C++ member*), 931, 933
CSR_CCM_FPIPE (*C macro*), 109
CSR_CCM_MBEGINADDR (*C macro*), 108
CSR_CCM_MCOMMAND (*C macro*), 108
CSR_CCM_MDATA (*C macro*), 108
CSR_CCM_SBEGINADDR (*C macro*), 108
CSR_CCM_SCOMMAND (*C macro*), 108
CSR_CCM_SDATA (*C macro*), 109
CSR_CCM_SUEN (*C macro*), 108
CSR_CCM_UBEGINADDR (*C macro*), 109
CSR_CCM_UCOMMAND (*C macro*), 109
CSR_CCM_UDATA (*C macro*), 109
CSR_CYCLE (*C macro*), 85
CSR_CYCLEH (*C macro*), 99
CSR_DCSR (*C macro*), 95
CSR_DPC (*C macro*), 95
CSR_DSCRATCH0 (*C macro*), 95
CSR_DSCRATCH1 (*C macro*), 95
CSR_FCSR (*C macro*), 84
CSR_FFLAGS (*C macro*), 84
CSR_FRM (*C macro*), 84
CSR_HCONTEXT (*C macro*), 89
CSR_HCOUNTEREN (*C macro*), 88
CSR_HEDELEG (*C macro*), 88
CSR_HENVCFG (*C macro*), 88
CSR_HENVCFGH (*C macro*), 98
CSR_HGATP (*C macro*), 89
CSR_HGEIE (*C macro*), 88
CSR_HGEIP (*C macro*), 89
CSR_HIDELEG (*C macro*), 88
CSR_HIE (*C macro*), 88
CSR_HIP (*C macro*), 89
CSR_HPMCOUNTER10 (*C macro*), 85
CSR_HPMCOUNTER10H (*C macro*), 99
CSR_HPMCOUNTER11 (*C macro*), 85
CSR_HPMCOUNTER11H (*C macro*), 99
CSR_HPMCOUNTER12 (*C macro*), 85
CSR_HPMCOUNTER12H (*C macro*), 99
CSR_HPMCOUNTER13 (*C macro*), 85
CSR_HPMCOUNTER13H (*C macro*), 99
CSR_HPMCOUNTER14 (*C macro*), 85
CSR_HPMCOUNTER14H (*C macro*), 99
CSR_HPMCOUNTER15 (*C macro*), 85
CSR_HPMCOUNTER15H (*C macro*), 99
CSR_HPMCOUNTER16 (*C macro*), 86
CSR_HPMCOUNTER16H (*C macro*), 99
CSR_HPMCOUNTER17 (*C macro*), 86
CSR_HPMCOUNTER17H (*C macro*), 99
CSR_HPMCOUNTER18 (*C macro*), 86
CSR_HPMCOUNTER18H (*C macro*), 100
CSR_HPMCOUNTER19 (*C macro*), 86
CSR_HPMCOUNTER19H (*C macro*), 100
CSR_HPMCOUNTER20 (*C macro*), 86
CSR_HPMCOUNTER20H (*C macro*), 100
CSR_HPMCOUNTER21 (*C macro*), 86
CSR_HPMCOUNTER21H (*C macro*), 100
CSR_HPMCOUNTER22 (*C macro*), 86
CSR_HPMCOUNTER22H (*C macro*), 100
CSR_HPMCOUNTER23 (*C macro*), 86
CSR_HPMCOUNTER23H (*C macro*), 100
CSR_HPMCOUNTER24 (*C macro*), 86
CSR_HPMCOUNTER24H (*C macro*), 100
CSR_HPMCOUNTER25 (*C macro*), 86
CSR_HPMCOUNTER25H (*C macro*), 100
CSR_HPMCOUNTER26 (*C macro*), 86
CSR_HPMCOUNTER26H (*C macro*), 100
CSR_HPMCOUNTER27 (*C macro*), 86
CSR_HPMCOUNTER27H (*C macro*), 100
CSR_HPMCOUNTER28 (*C macro*), 86
CSR_HPMCOUNTER28H (*C macro*), 100
CSR_HPMCOUNTER29 (*C macro*), 86
CSR_HPMCOUNTER29H (*C macro*), 100
CSR_HPMCOUNTER3 (*C macro*), 85
CSR_HPMCOUNTER30 (*C macro*), 86
CSR_HPMCOUNTER30H (*C macro*), 100

CSR_HPMCOUNTER31 (*C macro*), 86
CSR_HPMCOUNTER31H (*C macro*), 100
CSR_HPMCOUNTER3H (*C macro*), 99
CSR_HPMCOUNTER4 (*C macro*), 85
CSR_HPMCOUNTER4H (*C macro*), 99
CSR_HPMCOUNTER5 (*C macro*), 85
CSR_HPMCOUNTER5H (*C macro*), 99
CSR_HPMCOUNTER6 (*C macro*), 85
CSR_HPMCOUNTER6H (*C macro*), 99
CSR_HPMCOUNTER7 (*C macro*), 85
CSR_HPMCOUNTER7H (*C macro*), 99
CSR_HPMCOUNTER8 (*C macro*), 85
CSR_HPMCOUNTER8H (*C macro*), 99
CSR_HPMCOUNTER9 (*C macro*), 85
CSR_HPMCOUNTER9H (*C macro*), 99
CSR_HSTATEEN0 (*C macro*), 88
CSR_HSTATEEN0H (*C macro*), 98
CSR_HSTATEEN1 (*C macro*), 88
CSR_HSTATEEN1H (*C macro*), 99
CSR_HSTATEEN2 (*C macro*), 88
CSR_HSTATEEN2H (*C macro*), 99
CSR_HSTATEEN3 (*C macro*), 88
CSR_HSTATEEN3H (*C macro*), 99
CSR_HSTATUS (*C macro*), 88
CSR_HTIMEDELTA (*C macro*), 88
CSR_HTIMEDELTAH (*C macro*), 98
CSR_HTINST (*C macro*), 89
CSR_HTVAL (*C macro*), 88
CSR_HVIP (*C macro*), 89
CSR_INSTRET (*C macro*), 85
CSR_INSTRETH (*C macro*), 99
CSR_JALMNXTI (*C macro*), 106
CSR_JALSNXTI (*C macro*), 108
CSR_JVT (*C macro*), 85
CSR_LSTEPFORC (*C macro*), 106
CSR_MARCHID (*C macro*), 98
CSR_MATTRI0_BASE (*C macro*), 107
CSR_MATTRI0_MASK (*C macro*), 107
CSR_MATTRI1_BASE (*C macro*), 107
CSR_MATTRI1_MASK (*C macro*), 107
CSR_MATTRI2_BASE (*C macro*), 107
CSR_MATTRI2_MASK (*C macro*), 107
CSR_MATTRI3_BASE (*C macro*), 107
CSR_MATTRI3_MASK (*C macro*), 107
CSR_MATTRI4_BASE (*C macro*), 107
CSR_MATTRI4_MASK (*C macro*), 107
CSR_MBADADDR (*C macro*), 91
CSR_MCACHE_CTL (*C macro*), 106
CSR_MCACHE_CTL_DE (*C macro*), 115
CSR_MCACHE_CTL_IE (*C macro*), 115
CSR_MCACHECTL_Type (*C++ union*), 133
CSR_MCACHECTL_Type::_reserved0 (*C++ member*), 134
CSR_MCACHECTL_Type::_reserved1 (*C++ member*), 134
CSR_MCACHECTL_Type::b (*C++ member*), 134
CSR_MCACHECTL_Type::d (*C++ member*), 134
CSR_MCACHECTL_Type::dc_ecc_en (*C++ member*), 134
CSR_MCACHECTL_Type::dc_ecc_excp_en (*C++ member*), 134
CSR_MCACHECTL_Type::dc_en (*C++ member*), 134
CSR_MCACHECTL_Type::dc_rwdecc (*C++ member*), 134
CSR_MCACHECTL_Type::dc_rwtecc (*C++ member*), 134
CSR_MCACHECTL_Type::ic_ecc_en (*C++ member*), 133
CSR_MCACHECTL_Type::ic_ecc_excp_en (*C++ member*), 133
CSR_MCACHECTL_Type::ic_en (*C++ member*), 133
CSR_MCACHECTL_Type::ic_rwdecc (*C++ member*), 134
CSR_MCACHECTL_Type::ic_rwtecc (*C++ member*), 133
CSR_MCACHECTL_Type::ic_scpd_mod (*C++ member*), 133
CSR_MCAUSE (*C macro*), 90
CSR_MCAUSE_Type (*C++ union*), 130
CSR_MCAUSE_Type::_reserved0 (*C++ member*), 130
CSR_MCAUSE_Type::_reserved1 (*C++ member*), 130
CSR_MCAUSE_Type::b (*C++ member*), 131
CSR_MCAUSE_Type::d (*C++ member*), 131
CSR_MCAUSE_Type::exccode (*C++ member*), 130
CSR_MCAUSE_Type::interrupt (*C++ member*), 131
CSR_MCAUSE_Type::minhv (*C++ member*), 131
CSR_MCAUSE_Type::mpie (*C++ member*), 130
CSR_MCAUSE_Type::mpil (*C++ member*), 130
CSR_MCAUSE_Type::mpp (*C++ member*), 131
CSR_MCFG_INFO (*C macro*), 108
CSR_MCFGINFO_Type (*C++ union*), 136
CSR_MCFGINFO_Type::_reserved0 (*C++ member*), 137
CSR_MCFGINFO_Type::b (*C++ member*), 137
CSR_MCFGINFO_Type::clic (*C++ member*), 137
CSR_MCFGINFO_Type::d (*C++ member*), 137
CSR_MCFGINFO_Type::dcache (*C++ member*), 137
CSR_MCFGINFO_Type::dlm (*C++ member*), 137
CSR_MCFGINFO_Type::ecc (*C++ member*), 137
CSR_MCFGINFO_Type::fio (*C++ member*), 137
CSR_MCFGINFO_Type::icache (*C++ member*), 137
CSR_MCFGINFO_Type::ilm (*C++ member*), 137
CSR_MCFGINFO_Type::nice (*C++ member*), 137
CSR_MCFGINFO_Type::plic (*C++ member*), 137
CSR_MCFGINFO_Type::ppi (*C++ member*), 137
CSR_MCFGINFO_Type::tee (*C++ member*), 137
CSR_MCLICBASE (*C macro*), 105

CSR_MCONFIGPTR (*C macro*), 98
CSR_MCONTEXT (*C macro*), 95
CSR_MCOUNTEREN (*C macro*), 90
CSR_MCOUNTINHIBIT (*C macro*), 90
CSR_MCOUNTINHIBIT_Type (*C++ union*), 131
CSR_MCOUNTINHIBIT_Type::_reserved0 (*C++ member*), 131
CSR_MCOUNTINHIBIT_Type::_reserved1 (*C++ member*), 131
CSR_MCOUNTINHIBIT_Type::b (*C++ member*), 131
CSR_MCOUNTINHIBIT_Type::cy (*C++ member*), 131
CSR_MCOUNTINHIBIT_Type::d (*C++ member*), 131
CSR_MCOUNTINHIBIT_Type::ir (*C++ member*), 131
CSR_MCYCLE (*C macro*), 95
CSR_MCYCLEH (*C macro*), 102
CSR_MDCAUSE (*C macro*), 106
CSR_MDCAUSE_Type (*C++ union*), 132
CSR_MDCAUSE_Type::_reserved0 (*C++ member*), 132
CSR_MDCAUSE_Type::b (*C++ member*), 132
CSR_MDCAUSE_Type::d (*C++ member*), 132
CSR_MDCAUSE_Type::mdcause (*C++ member*), 132
CSR_MDCFG_INFO (*C macro*), 108
CSR_MDCFGINFO_Type (*C++ union*), 138
CSR_MDCFGINFO_Type::_reserved0 (*C++ member*), 139
CSR_MDCFGINFO_Type::_reserved1 (*C++ member*), 139
CSR_MDCFGINFO_Type::b (*C++ member*), 139
CSR_MDCFGINFO_Type::cache_ecc (*C++ member*), 139
CSR_MDCFGINFO_Type::d (*C++ member*), 139
CSR_MDCFGINFO_Type::lm_ecc (*C++ member*), 139
CSR_MDCFGINFO_Type::lm_size (*C++ member*), 139
CSR_MDCFGINFO_Type::lm_xonly (*C++ member*), 139
CSR_MDCFGINFO_Type::lsize (*C++ member*), 138
CSR_MDCFGINFO_Type::set (*C++ member*), 138
CSR_MDCFGINFO_Type::way (*C++ member*), 138
CSR_MDEVB (*C macro*), 107
CSR_MDEVM (*C macro*), 107
CSR_MDLM_CTL (*C macro*), 106
CSR_MDLMCTL_Type (*C++ union*), 136
CSR_MDLMCTL_Type::_reserved0 (*C++ member*), 136
CSR_MDLMCTL_Type::b (*C++ member*), 136
CSR_MDLMCTL_Type::d (*C++ member*), 136
CSR_MDLMCTL_Type::dlm_bpa (*C++ member*), 136
CSR_MDLMCTL_Type::dlm_ecc_en (*C++ member*), 136
CSR_MDLMCTL_Type::dlm_ecc_excp_en (*C++ member*), 136
CSR_MDLMCTL_Type::dlm_en (*C++ member*), 136
CSR_MDLMCTL_Type::dlm_rwecc (*C++ member*), 136
CSR_MECC_CODE (*C macro*), 106
CSR_MECC_LOCK (*C macro*), 106
CSR_MECC_STATUS (*C macro*), 108
CSR_MECCCODE_Type (*C++ union*), 140
CSR_MECCCODE_Type::_reserved0 (*C++ member*), 141
CSR_MECCCODE_Type::_reserved1 (*C++ member*), 141
CSR_MECCCODE_Type::_reserved2 (*C++ member*), 141
CSR_MECCCODE_Type::b (*C++ member*), 141
CSR_MECCCODE_Type::code (*C++ member*), 141
CSR_MECCCODE_Type::d (*C++ member*), 141
CSR_MECCCODE_Type::ramid (*C++ member*), 141
CSR_MECCCODE_Type::sramid (*C++ member*), 141
CSR_MECCLOCK_Type (*C++ union*), 140
CSR_MECCLOCK_Type::_reserved0 (*C++ member*), 140
CSR_MECCLOCK_Type::b (*C++ member*), 140
CSR_MECCLOCK_Type::d (*C++ member*), 140
CSR_MECCLOCK_Type::ecc_lock (*C++ member*), 140
CSR_MEDELEG (*C macro*), 90
CSR_MENVCFG (*C macro*), 90
CSR_MENVCFGH (*C macro*), 100
CSR_MEPC (*C macro*), 90
CSR_MFIOCFG_INFO (*C macro*), 107
CSR_MFIOCFGINFO_Type (*C++ union*), 140
CSR_MFIOCFGINFO_Type::_reserved0 (*C++ member*), 140
CSR_MFIOCFGINFO_Type::_reserved1 (*C++ member*), 140
CSR_MFIOCFGINFO_Type::b (*C++ member*), 140
CSR_MFIOCFGINFO_Type::d (*C++ member*), 140
CSR_MFIOCFGINFO_Type::fio_bpa (*C++ member*), 140
CSR_MFIOCFGINFO_Type::fio_size (*C++ member*), 140
CSR_MFP16MODE (*C macro*), 106
CSR_MHARTID (*C macro*), 98
CSR_MHPMCOUNTER10 (*C macro*), 96
CSR_MHPMCOUNTER10H (*C macro*), 102
CSR_MHPMCOUNTER11 (*C macro*), 96
CSR_MHPMCOUNTER11H (*C macro*), 102
CSR_MHPMCOUNTER12 (*C macro*), 96
CSR_MHPMCOUNTER12H (*C macro*), 102
CSR_MHPMCOUNTER13 (*C macro*), 96
CSR_MHPMCOUNTER13H (*C macro*), 102
CSR_MHPMCOUNTER14 (*C macro*), 96
CSR_MHPMCOUNTER14H (*C macro*), 103
CSR_MHPMCOUNTER15 (*C macro*), 96
CSR_MHPMCOUNTER15H (*C macro*), 103
CSR_MHPMCOUNTER16 (*C macro*), 96
CSR_MHPMCOUNTER16H (*C macro*), 103
CSR_MHPMCOUNTER17 (*C macro*), 96
CSR_MHPMCOUNTER17H (*C macro*), 103
CSR_MHPMCOUNTER18 (*C macro*), 96
CSR_MHPMCOUNTER18H (*C macro*), 103
CSR_MHPMCOUNTER19 (*C macro*), 96

CSR_MHPMCOUNTER19H (C macro), 103
CSR_MHPMCOUNTER20 (C macro), 96
CSR_MHPMCOUNTER20H (C macro), 103
CSR_MHPMCOUNTER21 (C macro), 96
CSR_MHPMCOUNTER21H (C macro), 103
CSR_MHPMCOUNTER22 (C macro), 96
CSR_MHPMCOUNTER22H (C macro), 103
CSR_MHPMCOUNTER23 (C macro), 96
CSR_MHPMCOUNTER23H (C macro), 103
CSR_MHPMCOUNTER24 (C macro), 96
CSR_MHPMCOUNTER24H (C macro), 103
CSR_MHPMCOUNTER25 (C macro), 96
CSR_MHPMCOUNTER25H (C macro), 103
CSR_MHPMCOUNTER26 (C macro), 96
CSR_MHPMCOUNTER26H (C macro), 103
CSR_MHPMCOUNTER27 (C macro), 96
CSR_MHPMCOUNTER27H (C macro), 103
CSR_MHPMCOUNTER28 (C macro), 96
CSR_MHPMCOUNTER28H (C macro), 103
CSR_MHPMCOUNTER29 (C macro), 97
CSR_MHPMCOUNTER29H (C macro), 103
CSR_MHPMCOUNTER3 (C macro), 95
CSR_MHPMCOUNTER30 (C macro), 97
CSR_MHPMCOUNTER30H (C macro), 103
CSR_MHPMCOUNTER31 (C macro), 97
CSR_MHPMCOUNTER31H (C macro), 103
CSR_MHPMCOUNTER3H (C macro), 102
CSR_MHPMCOUNTER4 (C macro), 95
CSR_MHPMCOUNTER4H (C macro), 102
CSR_MHPMCOUNTER5 (C macro), 95
CSR_MHPMCOUNTER5H (C macro), 102
CSR_MHPMCOUNTER6 (C macro), 95
CSR_MHPMCOUNTER6H (C macro), 102
CSR_MHPMCOUNTER7 (C macro), 95
CSR_MHPMCOUNTER7H (C macro), 102
CSR_MHPMCOUNTER8 (C macro), 96
CSR_MHPMCOUNTER8H (C macro), 102
CSR_MHPMCOUNTER9 (C macro), 96
CSR_MHPMCOUNTER9H (C macro), 102
CSR_MHPMEVENT10 (C macro), 97
CSR_MHPMEVENT10H (C macro), 101
CSR_MHPMEVENT11 (C macro), 97
CSR_MHPMEVENT11H (C macro), 101
CSR_MHPMEVENT12 (C macro), 97
CSR_MHPMEVENT12H (C macro), 101
CSR_MHPMEVENT13 (C macro), 97
CSR_MHPMEVENT13H (C macro), 101
CSR_MHPMEVENT14 (C macro), 97
CSR_MHPMEVENT14H (C macro), 101
CSR_MHPMEVENT15 (C macro), 97
CSR_MHPMEVENT15H (C macro), 101
CSR_MHPMEVENT16 (C macro), 97
CSR_MHPMEVENT16H (C macro), 101
CSR_MHPMEVENT17 (C macro), 97
CSR_MHPMEVENT17H (C macro), 101
CSR_MHPMEVENT18 (C macro), 97
CSR_MHPMEVENT18H (C macro), 101
CSR_MHPMEVENT19 (C macro), 97
CSR_MHPMEVENT19H (C macro), 101
CSR_MHPMEVENT20 (C macro), 97
CSR_MHPMEVENT20H (C macro), 101
CSR_MHPMEVENT21 (C macro), 98
CSR_MHPMEVENT21H (C macro), 101
CSR_MHPMEVENT22 (C macro), 98
CSR_MHPMEVENT22H (C macro), 101
CSR_MHPMEVENT23 (C macro), 98
CSR_MHPMEVENT23H (C macro), 101
CSR_MHPMEVENT24 (C macro), 98
CSR_MHPMEVENT24H (C macro), 101
CSR_MHPMEVENT25 (C macro), 98
CSR_MHPMEVENT25H (C macro), 102
CSR_MHPMEVENT26 (C macro), 98
CSR_MHPMEVENT26H (C macro), 102
CSR_MHPMEVENT27 (C macro), 98
CSR_MHPMEVENT27H (C macro), 102
CSR_MHPMEVENT28 (C macro), 98
CSR_MHPMEVENT28H (C macro), 102
CSR_MHPMEVENT29 (C macro), 98
CSR_MHPMEVENT29H (C macro), 102
CSR_MHPMEVENT3 (C macro), 97
CSR_MHPMEVENT30 (C macro), 98
CSR_MHPMEVENT30H (C macro), 102
CSR_MHPMEVENT31 (C macro), 98
CSR_MHPMEVENT31H (C macro), 102
CSR_MHPMEVENT3H (C macro), 100
CSR_MHPMEVENT4 (C macro), 97
CSR_MHPMEVENT4H (C macro), 101
CSR_MHPMEVENT5 (C macro), 97
CSR_MHPMEVENT5H (C macro), 101
CSR_MHPMEVENT6 (C macro), 97
CSR_MHPMEVENT6H (C macro), 101
CSR_MHPMEVENT7 (C macro), 97
CSR_MHPMEVENT7H (C macro), 101
CSR_MHPMEVENT8 (C macro), 97
CSR_MHPMEVENT8H (C macro), 101
CSR_MHPMEVENT9 (C macro), 97
CSR_MHPMEVENT9H (C macro), 101
CSR_MICFG_INFO (C macro), 108
CSR_MICFGINFO_Type (C++ union), 137
CSR_MICFGINFO_Type::_reserved0 (C++ member), 138
CSR_MICFGINFO_Type::_reserved1 (C++ member), 138
CSR_MICFGINFO_Type::b (C++ member), 138
CSR_MICFGINFO_Type::cache_ecc (C++ member), 138
CSR_MICFGINFO_Type::d (C++ member), 138
CSR_MICFGINFO_Type::lm_ecc (C++ member), 138

CSR_MICFGINFO_Type::lm_size (*C++ member*), 138
CSR_MICFGINFO_Type::lm_xonly (*C++ member*), 138
CSR_MICFGINFO_Type::lsize (*C++ member*), 138
CSR_MICFGINFO_Type::set (*C++ member*), 138
CSR_MICFGINFO_Type::way (*C++ member*), 138
CSR_MIDELEG (*C macro*), 90
CSR_MIE (*C macro*), 90
CSR_MILM_CTL (*C macro*), 105
CSR_MILMCTL_Type (*C++ union*), 135
CSR_MILMCTL_Type::_reserved0 (*C++ member*), 135
CSR_MILMCTL_Type::b (*C++ member*), 136
CSR_MILMCTL_Type::d (*C++ member*), 136
CSR_MILMCTL_Type::ilm_bpa (*C++ member*), 135
CSR_MILMCTL_Type::ilm_ecc_en (*C++ member*), 135
CSR_MILMCTL_Type::ilm_ecc_excp_en (*C++ member*), 135
CSR_MILMCTL_Type::ilm_en (*C++ member*), 135
CSR_MILMCTL_Type::ilm_rwecc (*C++ member*), 135
CSR_MIMPID (*C macro*), 98
CSR_MINSTRET (*C macro*), 95
CSR_MINSTRETH (*C macro*), 102
CSR_MINTSTATUS (*C macro*), 89, 90
CSR_MIP (*C macro*), 91
CSR_MIRGB_INFO (*C macro*), 107
CSR_MISA (*C macro*), 90
CSR_MISA_Type (*C++ union*), 126
CSR_MISA_Type::_reserved1 (*C++ member*), 127
CSR_MISA_Type::_reserved2 (*C++ member*), 127
CSR_MISA_Type::_reserved4 (*C++ member*), 128
CSR_MISA_Type::_reserved5 (*C++ member*), 128
CSR_MISA_Type::_resreved3 (*C++ member*), 128
CSR_MISA_Type::a (*C++ member*), 127
CSR_MISA_Type::b (*C++ member*), 127, 128
CSR_MISA_Type::c (*C++ member*), 127
CSR_MISA_Type::d (*C++ member*), 127
CSR_MISA_Type::e (*C++ member*), 127
CSR_MISA_Type::f (*C++ member*), 127
CSR_MISA_Type::g (*C++ member*), 127
CSR_MISA_Type::h (*C++ member*), 127
CSR_MISA_Type::i (*C++ member*), 127
CSR_MISA_Type::j (*C++ member*), 127
CSR_MISA_Type::l (*C++ member*), 127
CSR_MISA_Type::m (*C++ member*), 127
CSR_MISA_Type::mxl (*C++ member*), 128
CSR_MISA_Type::n (*C++ member*), 127
CSR_MISA_Type::p (*C++ member*), 128
CSR_MISA_Type::q (*C++ member*), 128
CSR_MISA_Type::s (*C++ member*), 128
CSR_MISA_Type::t (*C++ member*), 128
CSR_MISA_Type::u (*C++ member*), 128
CSR_MISA_Type::v (*C++ member*), 128
CSR_MISA_Type::x (*C++ member*), 128
CSR_MMISC_CTL (*C macro*), 106
CSR_MMISCCTL_Type (*C++ type*), 126
CSR_MMISCCTRL_Type (*C++ union*), 132
CSR_MMISCCTRL_Type::_reserved0 (*C++ member*), 133
CSR_MMISCCTRL_Type::_reserved1 (*C++ member*), 133
CSR_MMISCCTRL_Type::_reserved2 (*C++ member*), 133
CSR_MMISCCTRL_Type::_reserved3 (*C++ member*), 133
CSR_MMISCCTRL_Type::b (*C++ member*), 133
CSR_MMISCCTRL_Type::bpu (*C++ member*), 133
CSR_MMISCCTRL_Type::d (*C++ member*), 133
CSR_MMISCCTRL_Type::misalign (*C++ member*), 133
CSR_MMISCCTRL_Type::nmi_cause (*C++ member*), 133
CSR_MNOCB (*C macro*), 107
CSR_MNOCM (*C macro*), 107
CSR_MNVEC (*C macro*), 106
CSR_MNXTI (*C macro*), 89
CSR_MPPICFG_INFO (*C macro*), 107
CSR_MPPICFGINFO_Type (*C++ union*), 139
CSR_MPPICFGINFO_Type::_reserved0 (*C++ member*), 139
CSR_MPPICFGINFO_Type::_reserved1 (*C++ member*), 139
CSR_MPPICFGINFO_Type::b (*C++ member*), 139
CSR_MPPICFGINFO_Type::d (*C++ member*), 139
CSR_MPPICFGINFO_Type::ppi_bpa (*C++ member*), 139
CSR_MPPICFGINFO_Type::ppi_size (*C++ member*), 139
CSR_MSAVECAUSE1 (*C macro*), 106
CSR_MSAVECAUSE2 (*C macro*), 106
CSR_MSAVEDCAUSE1 (*C macro*), 106
CSR_MSAVEDCAUSE2 (*C macro*), 106
CSR_MSAVEEPC1 (*C macro*), 106
CSR_MSAVEEPC2 (*C macro*), 106
CSR_MSAVESTATUS (*C macro*), 106
CSR_MSAVESTATUS_Type (*C++ union*), 134
CSR_MSAVESTATUS_Type::_reserved0 (*C++ member*), 134
CSR_MSAVESTATUS_Type::_reserved1 (*C++ member*), 135
CSR_MSAVESTATUS_Type::_reserved2 (*C++ member*), 135
CSR_MSAVESTATUS_Type::b (*C++ member*), 135
CSR_MSAVESTATUS_Type::mpie1 (*C++ member*), 134
CSR_MSAVESTATUS_Type::mpie2 (*C++ member*), 135
CSR_MSAVESTATUS_Type::mpp1 (*C++ member*), 134
CSR_MSAVESTATUS_Type::mpp2 (*C++ member*), 135
CSR_MSAVESTATUS_Type::ptyp1 (*C++ member*), 134
CSR_MSAVESTATUS_Type::ptyp2 (*C++ member*), 135
CSR_MSAVESTATUS_Type::w (*C++ member*), 135
CSR_MSCONTEXT (*C macro*), 95

CSR_MSCRATCH (*C macro*), 90
CSR_MSCRATCHCSW (*C macro*), 90
CSR_MSCRATCHCSWL (*C macro*), 90
CSR_MSECCFG (*C macro*), 95
CSR_MSECCFGH (*C macro*), 102
CSR_MSMPCFG_INFO (*C macro*), 107
CSR_MSTACK_BASE (*C macro*), 108
CSR_MSTACK_BOUND (*C macro*), 108
CSR_MSTACK_CTRL (*C macro*), 108
CSR_MSTATEEN0 (*C macro*), 90
CSR_MSTATEEN0H (*C macro*), 100
CSR_MSTATEEN1 (*C macro*), 90
CSR_MSTATEEN1H (*C macro*), 100
CSR_MSTATEEN2 (*C macro*), 90
CSR_MSTATEEN2H (*C macro*), 100
CSR_MSTATEEN3 (*C macro*), 90
CSR_MSTATEEN3H (*C macro*), 100
CSR_MSTATUS (*C macro*), 90
CSR_MSTATUS_Type (*C++ union*), 128
CSR_MSTATUS_Type::_reserved0 (*C++ member*), 129
CSR_MSTATUS_Type::_reserved1 (*C++ member*), 129
CSR_MSTATUS_Type::_reserved2 (*C++ member*), 129
CSR_MSTATUS_Type::_reserved3 (*C++ member*), 129
CSR_MSTATUS_Type::_reserved4 (*C++ member*), 129
CSR_MSTATUS_Type::_reserved6 (*C++ member*), 129
CSR_MSTATUS_Type::b (*C++ member*), 130
CSR_MSTATUS_Type::d (*C++ member*), 130
CSR_MSTATUS_Type::fs (*C++ member*), 129
CSR_MSTATUS_Type::mie (*C++ member*), 129
CSR_MSTATUS_Type::mpie (*C++ member*), 129
CSR_MSTATUS_Type::mpp (*C++ member*), 129
CSR_MSTATUS_Type::mprv (*C++ member*), 129
CSR_MSTATUS_Type::sd (*C++ member*), 129
CSR_MSTATUS_Type::sie (*C++ member*), 129
CSR_MSTATUS_Type::spie (*C++ member*), 129
CSR_MSTATUS_Type::sum (*C++ member*), 129
CSR_MSTATUS_Type::xs (*C++ member*), 129
CSR_MSTATUSH (*C macro*), 100
CSR_MSUBM (*C macro*), 106
CSR_MSUBM_Type (*C++ union*), 131
CSR_MSUBM_Type::_reserved0 (*C++ member*), 132
CSR_MSUBM_Type::_reserved1 (*C++ member*), 132
CSR_MSUBM_Type::b (*C++ member*), 132
CSR_MSUBM_Type::d (*C++ member*), 132
CSR_MSUBM_Type::ptyp (*C++ member*), 132
CSR_MSUBM_Type::typ (*C++ member*), 132
CSR_MTINST (*C macro*), 91
CSR_MTLB_CTL (*C macro*), 106
CSR_MTLBCFG_INFO (*C macro*), 108
CSR_MTVAL (*C macro*), 91
CSR_MTVAL2 (*C macro*), 91
CSR_MTVEC (*C macro*), 90
CSR_MTVEC_Type (*C++ union*), 130
CSR_MTVEC_Type::addr (*C++ member*), 130
CSR_MTVEC_Type::b (*C++ member*), 130
CSR_MTVEC_Type::d (*C++ member*), 130
CSR_MTVEC_Type::mode (*C++ member*), 130
CSR_MTVT (*C macro*), 89
CSR_MTVT2 (*C macro*), 106
CSR_MVENDORID (*C macro*), 98
CSR_PMPADDR0 (*C macro*), 92
CSR_PMPADDR1 (*C macro*), 92
CSR_PMPADDR10 (*C macro*), 92
CSR_PMPADDR11 (*C macro*), 92
CSR_PMPADDR12 (*C macro*), 92
CSR_PMPADDR13 (*C macro*), 92
CSR_PMPADDR14 (*C macro*), 92
CSR_PMPADDR15 (*C macro*), 92
CSR_PMPADDR16 (*C macro*), 92
CSR_PMPADDR17 (*C macro*), 92
CSR_PMPADDR18 (*C macro*), 92
CSR_PMPADDR19 (*C macro*), 92
CSR_PMPADDR2 (*C macro*), 92
CSR_PMPADDR20 (*C macro*), 92
CSR_PMPADDR21 (*C macro*), 93
CSR_PMPADDR22 (*C macro*), 93
CSR_PMPADDR23 (*C macro*), 93
CSR_PMPADDR24 (*C macro*), 93
CSR_PMPADDR25 (*C macro*), 93
CSR_PMPADDR26 (*C macro*), 93
CSR_PMPADDR27 (*C macro*), 93
CSR_PMPADDR28 (*C macro*), 93
CSR_PMPADDR29 (*C macro*), 93
CSR_PMPADDR3 (*C macro*), 92
CSR_PMPADDR30 (*C macro*), 93
CSR_PMPADDR31 (*C macro*), 93
CSR_PMPADDR32 (*C macro*), 93
CSR_PMPADDR33 (*C macro*), 93
CSR_PMPADDR34 (*C macro*), 93
CSR_PMPADDR35 (*C macro*), 93
CSR_PMPADDR36 (*C macro*), 93
CSR_PMPADDR37 (*C macro*), 93
CSR_PMPADDR38 (*C macro*), 93
CSR_PMPADDR39 (*C macro*), 93
CSR_PMPADDR4 (*C macro*), 92
CSR_PMPADDR40 (*C macro*), 93
CSR_PMPADDR41 (*C macro*), 93
CSR_PMPADDR42 (*C macro*), 94
CSR_PMPADDR43 (*C macro*), 94
CSR_PMPADDR44 (*C macro*), 94
CSR_PMPADDR45 (*C macro*), 94
CSR_PMPADDR46 (*C macro*), 94
CSR_PMPADDR47 (*C macro*), 94
CSR_PMPADDR48 (*C macro*), 94
CSR_PMPADDR49 (*C macro*), 94
CSR_PMPADDR5 (*C macro*), 92
CSR_PMPADDR50 (*C macro*), 94
CSR_PMPADDR51 (*C macro*), 94

CSR_PMPADDR52 (*C macro*), 94
CSR_PMPADDR53 (*C macro*), 94
CSR_PMPADDR54 (*C macro*), 94
CSR_PMPADDR55 (*C macro*), 94
CSR_PMPADDR56 (*C macro*), 94
CSR_PMPADDR57 (*C macro*), 94
CSR_PMPADDR58 (*C macro*), 94
CSR_PMPADDR59 (*C macro*), 94
CSR_PMPADDR6 (*C macro*), 92
CSR_PMPADDR60 (*C macro*), 94
CSR_PMPADDR61 (*C macro*), 94
CSR_PMPADDR62 (*C macro*), 94
CSR_PMPADDR63 (*C macro*), 95
CSR_PMPADDR7 (*C macro*), 92
CSR_PMPADDR8 (*C macro*), 92
CSR_PMPADDR9 (*C macro*), 92
CSR_PMPCFG0 (*C macro*), 91
CSR_PMPCFG1 (*C macro*), 91
CSR_PMPCFG10 (*C macro*), 91
CSR_PMPCFG11 (*C macro*), 91
CSR_PMPCFG12 (*C macro*), 91
CSR_PMPCFG13 (*C macro*), 91
CSR_PMPCFG14 (*C macro*), 91
CSR_PMPCFG15 (*C macro*), 91
CSR_PMPCFG2 (*C macro*), 91
CSR_PMPCFG3 (*C macro*), 91
CSR_PMPCFG4 (*C macro*), 91
CSR_PMPCFG5 (*C macro*), 91
CSR_PMPCFG6 (*C macro*), 91
CSR_PMPCFG7 (*C macro*), 91
CSR_PMPCFG8 (*C macro*), 91
CSR_PMPCFG9 (*C macro*), 91
CSR_PUSHMCAUSE (*C macro*), 107
CSR_PUSHMEPC (*C macro*), 107
CSR_PUSHMSUBM (*C macro*), 106
CSR_PUSHSCAUSE (*C macro*), 108
CSR_PUSHSEPC (*C macro*), 108
CSR_SATP (*C macro*), 87
CSR_SCAUSE (*C macro*), 87
CSR_SCONTEXT (*C macro*), 87
CSR_SCOUNTEREN (*C macro*), 87
CSR_SCOUNTOVF (*C macro*), 89
CSR_SDCAUSE (*C macro*), 108
CSR_SEDELEG (*C macro*), 86
CSR_SEED (*C macro*), 85
CSR_SENVCFG (*C macro*), 87
CSR_SEPC (*C macro*), 87
CSR_SIDELEG (*C macro*), 87
CSR_SIE (*C macro*), 87
CSR_SINTSTATUS (*C macro*), 89
CSR_SIP (*C macro*), 87
CSR_SLEEPVALUE (*C macro*), 107
CSR_SNXTI (*C macro*), 89
CSR_SPMPADDR0 (*C macro*), 104
CSR_SPMPADDR1 (*C macro*), 104
CSR_SPMPADDR10 (*C macro*), 104
CSR_SPMPADDR11 (*C macro*), 104
CSR_SPMPADDR12 (*C macro*), 104
CSR_SPMPADDR13 (*C macro*), 104
CSR_SPMPADDR14 (*C macro*), 104
CSR_SPMPADDR15 (*C macro*), 104
CSR_SPMPADDR2 (*C macro*), 104
CSR_SPMPADDR3 (*C macro*), 104
CSR_SPMPADDR4 (*C macro*), 104
CSR_SPMPADDR5 (*C macro*), 104
CSR_SPMPADDR6 (*C macro*), 104
CSR_SPMPADDR7 (*C macro*), 104
CSR_SPMPADDR8 (*C macro*), 104
CSR_SPMPADDR9 (*C macro*), 104
CSR_SPMPCFG0 (*C macro*), 103
CSR_SPMPCFG1 (*C macro*), 103
CSR_SPMPCFG2 (*C macro*), 103
CSR_SPMPCFG3 (*C macro*), 104
CSR_SPMUADDR0 (*C macro*), 105
CSR_SPMUADDR1 (*C macro*), 105
CSR_SPMUADDR10 (*C macro*), 105
CSR_SPMUADDR11 (*C macro*), 105
CSR_SPMUADDR12 (*C macro*), 105
CSR_SPMUADDR13 (*C macro*), 105
CSR_SPMUADDR14 (*C macro*), 105
CSR_SPMUADDR15 (*C macro*), 105
CSR_SPMUADDR2 (*C macro*), 105
CSR_SPMUADDR3 (*C macro*), 105
CSR_SPMUADDR4 (*C macro*), 105
CSR_SPMUADDR5 (*C macro*), 105
CSR_SPMUADDR6 (*C macro*), 105
CSR_SPMUADDR7 (*C macro*), 105
CSR_SPMUADDR8 (*C macro*), 105
CSR_SPMUADDR9 (*C macro*), 105
CSR_SPMUCFG0 (*C macro*), 104
CSR_SPMUCFG1 (*C macro*), 104
CSR_SPMUCFG2 (*C macro*), 104
CSR_SPMUCFG3 (*C macro*), 104
CSR_SPMUSWITCH0 (*C macro*), 105
CSR_SPMUSWITCH1 (*C macro*), 105
CSR_SSCRATCH (*C macro*), 87
CSR_SSCRATCHCSW (*C macro*), 89
CSR_SSCRATCHCSWL (*C macro*), 89
CSR_SSTATEEN0 (*C macro*), 87
CSR_SSTATEEN1 (*C macro*), 87
CSR_SSTATEEN2 (*C macro*), 87
CSR_SSTATEEN3 (*C macro*), 87
CSR_SSTATUS (*C macro*), 86
CSR_STIMECMP (*C macro*), 87
CSR_STIMECMPH (*C macro*), 98
CSR_STVAL (*C macro*), 87
CSR_STVEC (*C macro*), 87
CSR_STVT (*C macro*), 87

CSR_STVT2 (*C macro*), 108
CSR_TCONTROL (*C macro*), 95
CSR_TDATA1 (*C macro*), 95
CSR_TDATA2 (*C macro*), 95
CSR_TDATA3 (*C macro*), 95
CSR_TIME (*C macro*), 85
CSR_TIMEH (*C macro*), 99
CSR_TINFO (*C macro*), 95
CSR_TSELECT (*C macro*), 95
CSR_TXEVT (*C macro*), 108
CSR_UCODE (*C macro*), 105
CSR_UINTSTATUS (*C macro*), 89
CSR_UNXTI (*C macro*), 89
CSR_USCRATCHCSW (*C macro*), 89
CSR_USCRATCHCSWL (*C macro*), 89
CSR_USTATUS (*C macro*), 84
CSR_UTVT (*C macro*), 89
CSR_VCSR (*C macro*), 85
CSR_VL (*C macro*), 86
CSR_VLENB (*C macro*), 86
CSR_VSATP (*C macro*), 88
CSR_VSCAUSE (*C macro*), 88
CSR_VSEPC (*C macro*), 88
CSR_VSIE (*C macro*), 87
CSR_VSIP (*C macro*), 88
CSR_VSSCRATCH (*C macro*), 88
CSR_VSSTATUS (*C macro*), 87
CSR_VSTART (*C macro*), 84
CSR_VSTIMECMP (*C macro*), 88
CSR_VSTIMECMPH (*C macro*), 98
CSR_VSTVAL (*C macro*), 88
CSR_VSTVEC (*C macro*), 88
CSR_VTYPE (*C macro*), 86
CSR_VXRM (*C macro*), 85
CSR_VXSAT (*C macro*), 85
CSR_WFE (*C macro*), 108

D

DCAUSE_FAULT_FETCH_INST (*C macro*), 125
DCAUSE_FAULT_FETCH_PMP (*C macro*), 125
DCAUSE_FAULT_LOAD_INST (*C macro*), 125
DCAUSE_FAULT_LOAD_NICE (*C macro*), 125
DCAUSE_FAULT_LOAD_PMP (*C macro*), 125
DCAUSE_FAULT_STORE_INST (*C macro*), 126
DCAUSE_FAULT_STORE_PMP (*C macro*), 126
DCSR_CAUSE (*C macro*), 112
DCSR_CAUSE_DEBUGINT (*C macro*), 112
DCSR_CAUSE_HALT (*C macro*), 112
DCSR_CAUSE_HWBP (*C macro*), 112
DCSR_CAUSE_NONE (*C macro*), 112
DCSR_CAUSE_STEP (*C macro*), 112
DCSR_CAUSE_SWBP (*C macro*), 112
DCSR_DEBUGINT (*C macro*), 112
DCSR_EBREAKH (*C macro*), 112
DCSR_EBREAKM (*C macro*), 112
DCSR_EBREAKS (*C macro*), 112
DCSR_EBREAKU (*C macro*), 112
DCSR_FULLRESET (*C macro*), 112
DCSR_HALT (*C macro*), 112
DCSR_NDRESET (*C macro*), 112
DCSR_PRV (*C macro*), 112
DCSR_STEP (*C macro*), 112
DCSR_STOPCYCLE (*C macro*), 112
DCSR_STOPTIME (*C macro*), 112
DCSR_XDEBUGVER (*C macro*), 111
default_intexc_handler (*C++ function*), 629
depthwise_conv_s16_generic_s16 (*C++ function*), 1057, 1076
depthwise_conv_s8_generic (*C++ function*), 1058, 1078
depthwise_conv_s8_mult_4 (*C++ function*), 1058, 1077
depthwise_conv_u8_generic (*C++ function*), 1058, 1079
depthwise_conv_u8_mult_4 (*C++ function*), 1058, 1079
DSP, **1137**

E

ECLIC (*C macro*), 143
ECLIC_BASE (*C macro*), 143
ECLIC_ClearPendingIRQ (*C macro*), 563, 565
ECLIC_DisableIRQ (*C macro*), 563, 565
ECLIC_DisableIRQ_S (*C macro*), 564, 567
ECLIC_EnableIRQ (*C macro*), 563, 565
ECLIC_EnableIRQ_S (*C macro*), 564, 566
ECLIC_GetCfgNlbits (*C macro*), 562, 565
ECLIC_GetCtrlIRQ (*C macro*), 563, 566
ECLIC_GetCtrlIRQ_S (*C macro*), 564, 566
ECLIC_GetEnableIRQ (*C macro*), 563, 565
ECLIC_GetEnableIRQ_S (*C macro*), 564, 566
ECLIC_GetInfoCtlbits (*C macro*), 563, 565
ECLIC_GetInfoNum (*C macro*), 563, 565
ECLIC_GetInfoVer (*C macro*), 563, 565
ECLIC_GetLevelIRQ (*C macro*), 563, 566
ECLIC_GetLevelIRQ_S (*C macro*), 564, 566
ECLIC_GetMth (*C macro*), 563, 565
ECLIC_GetPendingIRQ (*C macro*), 563, 565
ECLIC_GetPriorityIRQ (*C macro*), 563, 566
ECLIC_GetPriorityIRQ_S (*C macro*), 564, 566
ECLIC_GetShvIRQ (*C macro*), 563, 565
ECLIC_GetShvIRQ_S (*C macro*), 564, 566
ECLIC_GetSth (*C macro*), 564, 566
ECLIC_GetTrigIRQ (*C macro*), 563, 565
ECLIC_GetTrigIRQ_S (*C macro*), 564, 566
ECLIC_GetVector (*C macro*), 564, 567
ECLIC_GetVector_S (*C macro*), 564, 567
ECLIC_Init (*C++ function*), 629

ECLIC_MAX_NLBITS (*C macro*), 142
ECLIC_MODE_MTVEC_Msk (*C macro*), 142
ECLIC_NON_VECTOR_INTERRUPT (*C macro*), 143
ECLIC_Register_IRQ (*C++ function*), 629
ECLIC_Register_IRQ_S (*C++ function*), 630
ECLIC_SetCfgNlbits (*C macro*), 562, 565
ECLIC_SetCtrlIRQ (*C macro*), 563, 566
ECLIC_SetCtrlIRQ_S (*C macro*), 564, 566
ECLIC_SetLevelIRQ (*C macro*), 563, 566
ECLIC_SetLevelIRQ_S (*C macro*), 564, 566
ECLIC_SetModeIRQ (*C macro*), 564, 566
ECLIC_SetMth (*C macro*), 563, 565
ECLIC_SetPendingIRQ (*C macro*), 563, 565
ECLIC_SetPriorityIRQ (*C macro*), 563, 566
ECLIC_SetPriorityIRQ_S (*C macro*), 564, 566
ECLIC_SetShvIRQ (*C macro*), 563, 565
ECLIC_SetShvIRQ_S (*C macro*), 564, 566
ECLIC_SetSth (*C macro*), 564, 566
ECLIC_SetTrigIRQ (*C macro*), 563, 565
ECLIC_SetTrigIRQ_S (*C macro*), 564, 566
ECLIC_SetVector (*C macro*), 564, 567
ECLIC_SetVector_S (*C macro*), 564, 567
ECLIC_TRIGGER (*C++ enum*), 143
ECLIC_TRIGGER::ECLIC_LEVEL_TRIGGER (*C++ enumerator*), 143
ECLIC_TRIGGER::ECLIC_MAX_TRIGGER (*C++ enumerator*), 143
ECLIC_TRIGGER::ECLIC_NEGTIVE_EDGE_TRIGGER (*C++ enumerator*), 143
ECLIC_TRIGGER::ECLIC_POSTIVE_EDGE_TRIGGER (*C++ enumerator*), 143
ECLIC_VECTOR_INTERRUPT (*C macro*), 143
exc_entry_s (*C++ member*), 631
EXC_HANDLER (*C++ type*), 632
Exception_DumpFrame (*C++ function*), 632
Exception_Get_EXC (*C++ function*), 633
Exception_Get_EXC_S (*C++ function*), 634
Exception_Init (*C++ function*), 632
Exception_Register_EXC (*C++ function*), 633
Exception_Register_EXC_S (*C++ function*), 634

F

FALLBACK_DEFAULT_ECLIC_BASE (*C macro*), 628
FALLBACK_DEFAULT_SYSTIMER_BASE (*C macro*), 628
FAULT_FETCH (*C macro*), 125
FAULT_LOAD (*C macro*), 125
FAULT_STORE (*C macro*), 125
FETCH_PAGE_FAULT (*C macro*), 125
FFLAGS_AE_DZ (*C macro*), 122
FFLAGS_AE_NV (*C macro*), 122
FFLAGS_AE_NX (*C macro*), 122
FFLAGS_AE_OF (*C macro*), 122
FFLAGS_AE_UF (*C macro*), 122
FFTINIT (*C macro*), 899, 903, 904, 911, 912, 915, 916
fnptr (*C++ type*), 629
FREG (*C macro*), 122
FRM_RNDMODE_DYN (*C macro*), 122
FRM_RNDMODE_RDN (*C macro*), 122
FRM_RNDMODE_RMM (*C macro*), 122
FRM_RNDMODE_RNE (*C macro*), 122
FRM_RNDMODE_RTZ (*C macro*), 122
FRM_RNDMODE_RUP (*C macro*), 122

I

ILLEGAL_INSTRUCTION (*C macro*), 125
IREGION_DEBUG_OFS (*C macro*), 119
IREGION_DPREFETCH_OFS (*C macro*), 120
IREGION_ECLIC_OFS (*C macro*), 119
IREGION_IDU_OFS (*C macro*), 120
IREGION_IINFO_OFS (*C macro*), 119
IREGION_PL2_OFS (*C macro*), 120
IREGION_PLIC_OFS (*C macro*), 120
IREGION_SMP_OFS (*C macro*), 120
IREGION_TIMER_OFS (*C macro*), 120
IRQ_COP (*C macro*), 122
irq_entry_s (*C++ member*), 631
IRQ_H_EXT (*C macro*), 121
IRQ_H_SOFT (*C macro*), 121
IRQ_H_TIMER (*C macro*), 121
IRQ_HOST (*C macro*), 122
IRQ_M_EXT (*C macro*), 121
IRQ_M_SOFT (*C macro*), 121
IRQ_M_TIMER (*C macro*), 121
IRQ_S_EXT (*C macro*), 121
IRQ_S_SOFT (*C macro*), 121
IRQ_S_TIMER (*C macro*), 121
IRQn (*C++ enum*), 559, 568
IRQn::FirstDeviceSpecificInterrupt_IRQn (*C++ enumerator*), 560, 569
IRQn::Reserved0_IRQn (*C++ enumerator*), 559, 568
IRQn::Reserved10_IRQn (*C++ enumerator*), 560, 569
IRQn::Reserved11_IRQn (*C++ enumerator*), 560, 569
IRQn::Reserved12_IRQn (*C++ enumerator*), 560, 569
IRQn::Reserved13_IRQn (*C++ enumerator*), 560, 569
IRQn::Reserved14_IRQn (*C++ enumerator*), 560, 569
IRQn::Reserved15_IRQn (*C++ enumerator*), 560, 569
IRQn::Reserved16_IRQn (*C++ enumerator*), 560, 569
IRQn::Reserved1_IRQn (*C++ enumerator*), 559, 568
IRQn::Reserved2_IRQn (*C++ enumerator*), 559, 568
IRQn::Reserved3_IRQn (*C++ enumerator*), 559, 568
IRQn::Reserved4_IRQn (*C++ enumerator*), 559, 568
IRQn::Reserved5_IRQn (*C++ enumerator*), 559, 568
IRQn::Reserved6_IRQn (*C++ enumerator*), 560, 569
IRQn::Reserved7_IRQn (*C++ enumerator*), 560, 569
IRQn::Reserved8_IRQn (*C++ enumerator*), 560, 569
IRQn::Reserved9_IRQn (*C++ enumerator*), 560, 569
IRQn::SOC_INT_MAX (*C++ enumerator*), 560, 569
IRQn::SysTimer_IRQn (*C++ enumerator*), 559, 569

IRQn::SysTimerSW_IRQn (*C++ enumerator*), 559, 568
ISR, **1137**

L

LOAD_PAGE_FAULT (*C macro*), 125

M

MAX_SYSTEM_EXCEPTION_NUM (*C macro*), 632
MCACHE_CTL_DC_ECC_EN (*C macro*), 117
MCACHE_CTL_DC_ECC_EXCP_EN (*C macro*), 117
MCACHE_CTL_DC_EN (*C macro*), 117
MCACHE_CTL_DC_RWDECC (*C macro*), 117
MCACHE_CTL_DC_RWTECC (*C macro*), 117
MCACHE_CTL_IC_CANCEL_EN (*C macro*), 117
MCACHE_CTL_IC_ECC_EN (*C macro*), 117
MCACHE_CTL_IC_ECC_EXCP_EN (*C macro*), 117
MCACHE_CTL_IC_EN (*C macro*), 117
MCACHE_CTL_IC_PF_EN (*C macro*), 117
MCACHE_CTL_IC_RWDECC (*C macro*), 117
MCACHE_CTL_IC_RWTECC (*C macro*), 117
MCACHE_CTL_IC_SCPD_MOD (*C macro*), 117
MCAUSE_CAUSE (*C macro*), 115
MCAUSE_INTR (*C macro*), 115
MCFG_INFO_CLIC (*C macro*), 117
MCFG_INFO_DCACHE (*C macro*), 118
MCFG_INFO_DLM (*C macro*), 118
MCFG_INFO_DSP_N1 (*C macro*), 118
MCFG_INFO_DSP_N2 (*C macro*), 118
MCFG_INFO_DSP_N3 (*C macro*), 118
MCFG_INFO_ECC (*C macro*), 117
MCFG_INFO_FIO (*C macro*), 118
MCFG_INFO_ICACHE (*C macro*), 118
MCFG_INFO_ILM (*C macro*), 118
MCFG_INFO_IREGION_EXIST (*C macro*), 118
MCFG_INFO_NICE (*C macro*), 118
MCFG_INFO_PLIC (*C macro*), 117
MCFG_INFO_PPI (*C macro*), 118
MCFG_INFO_SMP (*C macro*), 118
MCFG_INFO_TEE (*C macro*), 117
MCFG_INFO_VP (*C macro*), 118
MCONTROL_ACTION (*C macro*), 113
MCONTROL_ACTION_DEBUG_EXCEPTION (*C macro*), 113
MCONTROL_ACTION_DEBUG_MODE (*C macro*), 113
MCONTROL_ACTION_TRACE_EMIT (*C macro*), 113
MCONTROL_ACTION_TRACE_START (*C macro*), 113
MCONTROL_ACTION_TRACE_STOP (*C macro*), 113
MCONTROL_CHAIN (*C macro*), 113
MCONTROL_DMODE (*C macro*), 112
MCONTROL_EXECUTE (*C macro*), 113
MCONTROL_H (*C macro*), 113
MCONTROL_LOAD (*C macro*), 113
MCONTROL_M (*C macro*), 113
MCONTROL_MASKMAX (*C macro*), 112
MCONTROL_MATCH (*C macro*), 113
MCONTROL_MATCH_EQUAL (*C macro*), 113
MCONTROL_MATCH_GE (*C macro*), 114
MCONTROL_MATCH_LT (*C macro*), 114
MCONTROL_MATCH_MASK_HIGH (*C macro*), 114
MCONTROL_MATCH_MASK_LOW (*C macro*), 114
MCONTROL_MATCH_NAPOT (*C macro*), 113
MCONTROL_S (*C macro*), 113
MCONTROL_SELECT (*C macro*), 113
MCONTROL_STORE (*C macro*), 113
MCONTROL_TIMING (*C macro*), 113
MCONTROL_TYPE (*C macro*), 112
MCONTROL_TYPE_MATCH (*C macro*), 113
MCONTROL_TYPE_NONE (*C macro*), 113
MCONTROL_U (*C macro*), 113
MCOUNTINHIBIT_CY (*C macro*), 116
MCOUNTINHIBIT_IR (*C macro*), 116
MDCAUSE_MDCAUSE (*C macro*), 116
MDCFG_DC_ECC (*C macro*), 119
MDCFG_DC_LSIZE (*C macro*), 119
MDCFG_DC_SET (*C macro*), 118
MDCFG_DC_WAY (*C macro*), 119
MDCFG_DLM_ECC (*C macro*), 119
MDCFG_DLM_SIZE (*C macro*), 119
MDLM_CTL_DLM_BPA (*C macro*), 116
MDLM_CTL_DLM_ECC_EN (*C macro*), 116
MDLM_CTL_DLM_ECC_EXCP_EN (*C macro*), 116
MDLM_CTL_DLM_EN (*C macro*), 116
MDLM_CTL_DLM_RWECC (*C macro*), 116
MECC_CODE_CODE (*C macro*), 119
MECC_CODE_RAMID (*C macro*), 119
MECC_CODE_SRAMID (*C macro*), 119
MECC_LOCK_ECC_LOCK (*C macro*), 119
MENVCFG_CBCFE (*C macro*), 115
MENVCFG_CBIE_EN (*C macro*), 115
MENVCFG_CBIE_FLUSH (*C macro*), 115
MENVCFG_CBIE_INVAL (*C macro*), 115
MENVCFG_CBZE (*C macro*), 115
MFCC_INIT_F16 (*C macro*), 939, 940
MFCC_INIT_F32 (*C macro*), 959
MFCC_INIT_Q15 (*C macro*), 946
MFCC_INIT_Q31 (*C macro*), 952
MFIOCFG_INFO_FIO_BPA (*C macro*), 119
MFIOCFG_INFO_FIO_SIZE (*C macro*), 119
MICFG_IC_ECC (*C macro*), 118
MICFG_IC_LSIZE (*C macro*), 118
MICFG_IC_SET (*C macro*), 118
MICFG_IC_WAY (*C macro*), 118
MICFG_ILM_ECC (*C macro*), 118
MICFG_ILM_SIZE (*C macro*), 118
MICFG_ILM_XONLY (*C macro*), 118
MIE_HEIE (*C macro*), 114
MIE_HSIE (*C macro*), 114
MIE_HTIE (*C macro*), 114
MIE_MEIE (*C macro*), 115

MIE_MSIE (*C macro*), 114
MIE_MTIE (*C macro*), 114
MIE_SEIE (*C macro*), 114
MIE_SSIE (*C macro*), 114
MIE_STIE (*C macro*), 114
MILM_CTL_ILM_BPA (*C macro*), 116
MILM_CTL_ILM_ECC_EN (*C macro*), 116
MILM_CTL_ILM_ECC_EXCP_EN (*C macro*), 116
MILM_CTL_ILM_EN (*C macro*), 116
MILM_CTL_ILM_RWECC (*C macro*), 116
MIP_HEIP (*C macro*), 114
MIP_HSIP (*C macro*), 114
MIP_HTIP (*C macro*), 114
MIP_MEIP (*C macro*), 114
MIP_MSIP (*C macro*), 114
MIP_MTIP (*C macro*), 114
MIP_SEIP (*C macro*), 114
MIP_SSIP (*C macro*), 114
MIP_STIP (*C macro*), 114
MIRGB_INFO_IREGION_SIZE_BOFS (*C macro*), 119
MIRGB_INFO_IRG_BASE_ADDR_BOFS (*C macro*), 119
MISALIGNED_FETCH (*C macro*), 125
MISALIGNED_LOAD (*C macro*), 125
MISALIGNED_STORE (*C macro*), 125
MMISC_CTL_BPU (*C macro*), 117
MMISC_CTL_CODE_BUS_ERR (*C macro*), 116
MMISC_CTL_IMRETURN_ENABLE (*C macro*), 116
MMISC_CTL_LDSPEC_ENABLE (*C macro*), 116
MMISC_CTL_MISALIGN (*C macro*), 116
MMISC_CTL_NMI_CAUSE_FFF (*C macro*), 116
MMISC_CTL_SIJUMP_ENABLE (*C macro*), 116
MMISC_CTL_ZC (*C macro*), 117
MPPICFG_INFO_PPI_BPA (*C macro*), 119
MPPICFG_INFO_PPI_SIZE (*C macro*), 119
MSTACK_CTRL_MODE (*C macro*), 120
MSTACK_CTRL_OVF_TRACK_EN (*C macro*), 120
MSTACK_CTRL_UDF_EN (*C macro*), 120
MSTATUS32_SD (*C macro*), 110
MSTATUS64_SD (*C macro*), 110
MSTATUS_FS (*C macro*), 109
MSTATUS_FS_CLEAN (*C macro*), 110
MSTATUS_FS_DIRTY (*C macro*), 110
MSTATUS_FS_INITIAL (*C macro*), 110
MSTATUS_GVA (*C macro*), 110
MSTATUS_HIE (*C macro*), 109
MSTATUS_MBE (*C macro*), 110
MSTATUS_MIE (*C macro*), 109
MSTATUS_MPIE (*C macro*), 109
MSTATUS_MPP (*C macro*), 109
MSTATUS_MPRV (*C macro*), 110
MSTATUS_MPV (*C macro*), 110
MSTATUS_MXR (*C macro*), 110
MSTATUS_SBE (*C macro*), 110
MSTATUS_SIE (*C macro*), 109
MSTATUS_SPIE (*C macro*), 109
MSTATUS_SPP (*C macro*), 109
MSTATUS_SUM (*C macro*), 110
MSTATUS_SXL (*C macro*), 110
MSTATUS_TSR (*C macro*), 110
MSTATUS_TVM (*C macro*), 110
MSTATUS_TW (*C macro*), 110
MSTATUS_UBE (*C macro*), 109
MSTATUS_UIE (*C macro*), 109
MSTATUS_UPIE (*C macro*), 109
MSTATUS_UXL (*C macro*), 110
MSTATUS_VS (*C macro*), 109
MSTATUS_VS_CLEAN (*C macro*), 110
MSTATUS_VS_DIRTY (*C macro*), 110
MSTATUS_VS_INITIAL (*C macro*), 110
MSTATUS_XS (*C macro*), 110
MSTATUSH_GVA (*C macro*), 111
MSTATUSH_MBE (*C macro*), 111
MSTATUSH_MPV (*C macro*), 111
MSTATUSH_SBE (*C macro*), 111
MSUBM_PTYP (*C macro*), 116
MSUBM_TYP (*C macro*), 116
MTVT2_COMMON_CODE_ENTRY (*C macro*), 117
MTVT2_MTVT2EN (*C macro*), 117

N

NN, **1137**

P

PMP_A (*C macro*), 123
PMP_A_NA4 (*C macro*), 123
PMP_A_NAPOT (*C macro*), 123
PMP_A_TOR (*C macro*), 123
PMP_CONFIG (*C++ struct*), 593, 596
PMP_COUNT (*C macro*), 123
PMP_L (*C macro*), 123
PMP_R (*C macro*), 122
PMP_SHIFT (*C macro*), 123
PMP_W (*C macro*), 123
PMP_X (*C macro*), 123
PRV_H (*C macro*), 120
PRV_M (*C macro*), 120
PRV_S (*C macro*), 120
PRV_U (*C macro*), 120
PTE_A (*C macro*), 124
PTE_D (*C macro*), 124
PTE_G (*C macro*), 124
PTE_PPN_SHIFT (*C macro*), 124
PTE_R (*C macro*), 124
PTE_SOFT (*C macro*), 124
PTE_TABLE (*C macro*), 124
PTE_U (*C macro*), 124
PTE_V (*C macro*), 123
PTE_W (*C macro*), 124

PTE_X (*C macro*), 124

R

realCoefA (*C++ member*), 983, 984
realCoefAQ31 (*C++ member*), 983, 984
realCoefB (*C++ member*), 983, 984
realCoefBQ31 (*C++ member*), 983, 984
RESTORE_FPU_CONTEXT (*C macro*), 592
RESTORE_IRQ_CSR_CONTEXT (*C macro*), 565, 567
RESTORE_IRQ_CSR_CONTEXT_S (*C macro*), 565, 568
RFFTINIT_Q15 (*C macro*), 970
RFFTINIT_Q31 (*C macro*), 976
riscv_abs_f16 (*C++ function*), 645, 646
riscv_abs_f32 (*C++ function*), 645, 646
riscv_abs_f64 (*C++ function*), 645, 646
riscv_abs_q15 (*C++ function*), 645, 646
riscv_abs_q31 (*C++ function*), 645, 647
riscv_abs_q7 (*C++ function*), 645, 647
riscv_absmax_f16 (*C++ function*), 833, 834
riscv_absmax_f32 (*C++ function*), 833, 834
riscv_absmax_f64 (*C++ function*), 833, 834
riscv_absmax_no_idx_f16 (*C++ function*), 833, 834
riscv_absmax_no_idx_f32 (*C++ function*), 833, 835
riscv_absmax_no_idx_f64 (*C++ function*), 833, 835
riscv_absmax_no_idx_q15 (*C++ function*), 833, 835
riscv_absmax_no_idx_q31 (*C++ function*), 833, 835
riscv_absmax_no_idx_q7 (*C++ function*), 833, 835
riscv_absmax_q15 (*C++ function*), 833, 835
riscv_absmax_q31 (*C++ function*), 833, 836
riscv_absmax_q7 (*C++ function*), 833, 836
riscv_absmin_f16 (*C++ function*), 836, 837
riscv_absmin_f32 (*C++ function*), 836, 837
riscv_absmin_f64 (*C++ function*), 836, 837
riscv_absmin_no_idx_f16 (*C++ function*), 836, 837
riscv_absmin_no_idx_f32 (*C++ function*), 836, 838
riscv_absmin_no_idx_f64 (*C++ function*), 836, 838
riscv_absmin_no_idx_q15 (*C++ function*), 836, 838
riscv_absmin_no_idx_q31 (*C++ function*), 836, 838
riscv_absmin_no_idx_q7 (*C++ function*), 836, 838
riscv_absmin_q15 (*C++ function*), 836, 839
riscv_absmin_q31 (*C++ function*), 837, 839
riscv_absmin_q7 (*C++ function*), 837, 839
riscv_accumulate_f16 (*C++ function*), 839, 840
riscv_accumulate_f32 (*C++ function*), 839, 840
riscv_accumulate_f64 (*C++ function*), 839, 840
riscv_add_f16 (*C++ function*), 647, 648
riscv_add_f32 (*C++ function*), 647, 648
riscv_add_f64 (*C++ function*), 647, 648
riscv_add_q15 (*C++ function*), 647, 648
riscv_add_q31 (*C++ function*), 647, 648
riscv_add_q7 (*C++ function*), 647, 649
riscv_and_u16 (*C++ function*), 649, 650
riscv_and_u32 (*C++ function*), 649, 650
riscv_and_u8 (*C++ function*), 649, 650
riscv_atan2_f16 (*C++ function*), 704, 705
riscv_atan2_f32 (*C++ function*), 704, 705
riscv_atan2_q15 (*C++ function*), 704, 705
riscv_atan2_q31 (*C++ function*), 704, 705
riscv_avepool_q7_HWC (*C++ function*), 1096, 1099
riscv_avgpool_s16 (*C++ function*), 1096, 1097
riscv_avgpool_s16_get_buffer_size (*C++ function*), 1095
riscv_avgpool_s16_get_buffer_size_dsp (*C++ function*), 1095
riscv_avgpool_s8 (*C++ function*), 1096, 1097
riscv_avgpool_s8_get_buffer_size (*C++ function*), 1095
riscv_avgpool_s8_get_buffer_size_dsp (*C++ function*), 1095, 1096
riscv_bartlett_f32 (*C++ function*), 1003
riscv_bartlett_f64 (*C++ function*), 1003, 1004
riscv_barycenter_f16 (*C++ function*), 862, 863
riscv_barycenter_f32 (*C++ function*), 862
riscv_bilinear_interp_f16 (*C++ function*), 791, 792
riscv_bilinear_interp_f32 (*C++ function*), 791, 792
riscv_bilinear_interp_q15 (*C++ function*), 791, 792
riscv_bilinear_interp_q31 (*C++ function*), 791, 792
riscv_bilinear_interp_q7 (*C++ function*), 791, 792
riscv_biquad_cas_df1_32x64_init_q31 (*C++ function*), 712, 714
riscv_biquad_cas_df1_32x64_q31 (*C++ function*), 712, 715
riscv_biquad_cascade_df1_f16 (*C++ function*), 716, 718
riscv_biquad_cascade_df1_f32 (*C++ function*), 716, 719
riscv_biquad_cascade_df1_fast_q15 (*C++ function*), 716, 719
riscv_biquad_cascade_df1_fast_q31 (*C++ function*), 716, 719
riscv_biquad_cascade_df1_init_f16 (*C++ function*), 716, 720
riscv_biquad_cascade_df1_init_f32 (*C++ function*), 716, 721
riscv_biquad_cascade_df1_init_q15 (*C++ function*), 716, 721
riscv_biquad_cascade_df1_init_q31 (*C++ function*), 716, 722
riscv_biquad_cascade_df1_q15 (*C++ function*), 716, 722
riscv_biquad_cascade_df1_q31 (*C++ function*), 716, 723
riscv_biquad_cascade_df2T_f16 (*C++ function*), 723, 726

riscv_biquad_cascade_df2T_f32 (*C++ function*), 723, 726
riscv_biquad_cascade_df2T_f64 (*C++ function*), 723, 726
riscv_biquad_cascade_df2T_init_f16 (*C++ function*), 723, 726
riscv_biquad_cascade_df2T_init_f32 (*C++ function*), 723, 727
riscv_biquad_cascade_df2T_init_f64 (*C++ function*), 723, 728
riscv_biquad_cascade_stereo_df2T_f16 (*C++ function*), 724, 728
riscv_biquad_cascade_stereo_df2T_f32 (*C++ function*), 724, 728
riscv_biquad_cascade_stereo_df2T_init_f16 (*C++ function*), 724, 729
riscv_biquad_cascade_stereo_df2T_init_f32 (*C++ function*), 724, 729
riscv_bitonic_sort_f32 (*C++ function*), 863
riscv_blackman_harris_92db_f32 (*C++ function*), 1004, 1005
riscv_blackman_harris_92db_f64 (*C++ function*), 1004, 1005
riscv_braycurtis_distance_f16 (*C++ function*), 692, 693
riscv_braycurtis_distance_f32 (*C++ function*), 692, 693
riscv_bubble_sort_f32 (*C++ function*), 863
riscv_canberra_distance_f16 (*C++ function*), 693
riscv_canberra_distance_f32 (*C++ function*), 693
riscv_cfft_f16 (*C++ function*), 899, 900
riscv_cfft_f32 (*C++ function*), 903, 904
riscv_cfft_f64 (*C++ function*), 907, 908
riscv_cfft_init_f16 (*C++ function*), 899, 902
riscv_cfft_init_f32 (*C++ function*), 903, 906
riscv_cfft_init_f64 (*C++ function*), 907, 910
riscv_cfft_init_q15 (*C++ function*), 911, 914
riscv_cfft_init_q31 (*C++ function*), 915, 918
riscv_cfft_q15 (*C++ function*), 911, 914
riscv_cfft_q31 (*C++ function*), 915, 918
riscv_cfft_radix2_f16 (*C++ function*), 919, 920
riscv_cfft_radix2_f32 (*C++ function*), 919, 920
riscv_cfft_radix2_init_f16 (*C++ function*), 919, 920
riscv_cfft_radix2_init_f32 (*C++ function*), 919, 921
riscv_cfft_radix2_init_q15 (*C++ function*), 919, 922
riscv_cfft_radix2_init_q31 (*C++ function*), 919, 922
riscv_cfft_radix2_q15 (*C++ function*), 919, 923
riscv_cfft_radix2_q31 (*C++ function*), 919, 923
riscv_cfft_radix4_f16 (*C++ function*), 919, 924
riscv_cfft_radix4_f32 (*C++ function*), 919, 924
riscv_cfft_radix4_init_f16 (*C++ function*), 919, 924
riscv_cfft_radix4_init_f32 (*C++ function*), 919, 925
riscv_cfft_radix4_init_q15 (*C++ function*), 919, 926
riscv_cfft_radix4_init_q31 (*C++ function*), 919, 926
riscv_cfft_radix4_q15 (*C++ function*), 920, 927
riscv_cfft_radix4_q31 (*C++ function*), 920, 927
riscv_cfft_radix4by2_f16 (*C++ function*), 919, 924
riscv_chebyshev_distance_f16 (*C++ function*), 694
riscv_chebyshev_distance_f32 (*C++ function*), 694
riscv_chebyshev_distance_f64 (*C++ function*), 694
riscv_cityblock_distance_f16 (*C++ function*), 695
riscv_cityblock_distance_f32 (*C++ function*), 695
riscv_cityblock_distance_f64 (*C++ function*), 695
riscv_clip_f16 (*C++ function*), 650, 651
riscv_clip_f32 (*C++ function*), 650, 651
riscv_clip_q15 (*C++ function*), 650, 651
riscv_clip_q31 (*C++ function*), 650, 651
riscv_clip_q7 (*C++ function*), 650, 652
riscv_cmplx_conj_f16 (*C++ function*), 670
riscv_cmplx_conj_f32 (*C++ function*), 670
riscv_cmplx_conj_q15 (*C++ function*), 670, 671
riscv_cmplx_conj_q31 (*C++ function*), 670, 671
riscv_cmplx_dot_prod_f16 (*C++ function*), 671, 672
riscv_cmplx_dot_prod_f32 (*C++ function*), 671, 672
riscv_cmplx_dot_prod_q15 (*C++ function*), 671, 672
riscv_cmplx_dot_prod_q31 (*C++ function*), 671, 673
riscv_cmplx_mag_f16 (*C++ function*), 673, 674
riscv_cmplx_mag_f32 (*C++ function*), 673, 674
riscv_cmplx_mag_f64 (*C++ function*), 673, 674
riscv_cmplx_mag_fast_q15 (*C++ function*), 673, 674
riscv_cmplx_mag_q15 (*C++ function*), 673, 675
riscv_cmplx_mag_q31 (*C++ function*), 673, 675
riscv_cmplx_mag_squared_f16 (*C++ function*), 675, 676
riscv_cmplx_mag_squared_f32 (*C++ function*), 675, 676
riscv_cmplx_mag_squared_f64 (*C++ function*), 675, 676
riscv_cmplx_mag_squared_q15 (*C++ function*), 675, 676
riscv_cmplx_mag_squared_q31 (*C++ function*), 675, 677
riscv_cmplx_mult_cmplx_f16 (*C++ function*), 677, 678
riscv_cmplx_mult_cmplx_f32 (*C++ function*), 677, 678
riscv_cmplx_mult_cmplx_f64 (*C++ function*), 677, 678
riscv_cmplx_mult_cmplx_q15 (*C++ function*), 677, 678

riscv_cmplx_mult_cmplx_q31 (*C++ function*), 677, 679
riscv_cmplx_mult_real_f16 (*C++ function*), 679, 680
riscv_cmplx_mult_real_f32 (*C++ function*), 679, 680
riscv_cmplx_mult_real_q15 (*C++ function*), 679, 680
riscv_cmplx_mult_real_q31 (*C++ function*), 679, 680
riscv_concatenation_s8_w (*C++ function*), 1046
riscv_concatenation_s8_x (*C++ function*), 1046, 1047
riscv_concatenation_s8_y (*C++ function*), 1046, 1047
riscv_concatenation_s8_z (*C++ function*), 1046, 1048
riscv_conv_f32 (*C++ function*), 730, 731
riscv_conv_fast_opt_q15 (*C++ function*), 730, 731
riscv_conv_fast_q15 (*C++ function*), 730, 732
riscv_conv_fast_q31 (*C++ function*), 730, 733
riscv_conv_opt_q15 (*C++ function*), 730, 733
riscv_conv_opt_q7 (*C++ function*), 730, 734
riscv_conv_partial_f32 (*C++ function*), 736, 737
riscv_conv_partial_fast_opt_q15 (*C++ function*), 736, 738
riscv_conv_partial_fast_q15 (*C++ function*), 736, 738
riscv_conv_partial_fast_q31 (*C++ function*), 736, 739
riscv_conv_partial_opt_q15 (*C++ function*), 736, 740
riscv_conv_partial_opt_q7 (*C++ function*), 737, 740
riscv_conv_partial_q15 (*C++ function*), 737, 741
riscv_conv_partial_q31 (*C++ function*), 737, 741
riscv_conv_partial_q7 (*C++ function*), 737, 742
riscv_conv_q15 (*C++ function*), 730, 734
riscv_conv_q31 (*C++ function*), 730, 735
riscv_conv_q7 (*C++ function*), 730, 736
riscv_convolve_1_x_n_s8 (*C++ function*), 1054, 1060
riscv_convolve_1_x_n_s8_get_buffer_size (*C++ function*), 1049, 1051
riscv_convolve_1x1_HWC_q7_fast_nonsquare (*C++ function*), 1054, 1061
riscv_convolve_1x1_s8 (*C++ function*), 1054, 1062
riscv_convolve_1x1_s8_fast (*C++ function*), 1054, 1063
riscv_convolve_1x1_s8_fast_get_buffer_size (*C++ function*), 1049, 1052
riscv_convolve_fast_s16 (*C++ function*), 1055, 1064
riscv_convolve_fast_s16_get_buffer_size (*C++ function*), 1049, 1050
riscv_convolve_HWC_q15_basic (*C++ function*), 1055, 1065
riscv_convolve_HWC_q15_fast (*C++ function*), 1055, 1066
riscv_convolve_HWC_q15_fast_nonsquare (*C++ function*), 1055, 1067
riscv_convolve_HWC_q7_basic (*C++ function*), 1055, 1068
riscv_convolve_HWC_q7_basic_nonsquare (*C++ function*), 1055, 1069
riscv_convolve_HWC_q7_fast (*C++ function*), 1056, 1070
riscv_convolve_HWC_q7_fast_nonsquare (*C++ function*), 1056, 1071
riscv_convolve_HWC_q7_RGB (*C++ function*), 1056, 1072
riscv_convolve_s16 (*C++ function*), 1056, 1072
riscv_convolve_s16_get_buffer_size (*C++ function*), 1049, 1051
riscv_convolve_s8 (*C++ function*), 1056, 1073
riscv_convolve_s8_get_buffer_size (*C++ function*), 1049, 1051
riscv_convolve_wrapper_s16 (*C++ function*), 1057, 1074
riscv_convolve_wrapper_s16_get_buffer_size (*C++ function*), 1049, 1051
riscv_convolve_wrapper_s16_get_buffer_size_dsp (*C++ function*), 1049, 1051
riscv_convolve_wrapper_s8 (*C++ function*), 1057, 1075
riscv_convolve_wrapper_s8_get_buffer_size (*C++ function*), 1049, 1052
riscv_convolve_wrapper_s8_get_buffer_size_dsp (*C++ function*), 1049, 1052
riscv_copy_f16 (*C++ function*), 866, 867
riscv_copy_f32 (*C++ function*), 866, 867
riscv_copy_f64 (*C++ function*), 866, 867
riscv_copy_q15 (*C++ function*), 866, 867
riscv_copy_q31 (*C++ function*), 866, 867
riscv_copy_q7 (*C++ function*), 866, 868
riscv_correlate_f16 (*C++ function*), 743, 744
riscv_correlate_f32 (*C++ function*), 743, 744
riscv_correlate_f64 (*C++ function*), 743, 745
riscv_correlate_fast_opt_q15 (*C++ function*), 743, 745
riscv_correlate_fast_q15 (*C++ function*), 743, 746
riscv_correlate_fast_q31 (*C++ function*), 743, 746
riscv_correlate_opt_q15 (*C++ function*), 743, 747
riscv_correlate_opt_q7 (*C++ function*), 743, 747
riscv_correlate_q15 (*C++ function*), 743, 748
riscv_correlate_q31 (*C++ function*), 743, 748
riscv_correlate_q7 (*C++ function*), 743, 749
riscv_correlation_distance_f16 (*C++ function*),

696
riscv_correlation_distance_f32 (*C++ function*), 696
riscv_cos_f32 (*C++ function*), 706
riscv_cos_q15 (*C++ function*), 706
riscv_cos_q31 (*C++ function*), 706, 707
riscv_cosine_distance_f16 (*C++ function*), 696, 697
riscv_cosine_distance_f32 (*C++ function*), 696, 697
riscv_cosine_distance_f64 (*C++ function*), 696, 697
riscv_dct4_f32 (*C++ function*), 933
riscv_dct4_init_f32 (*C++ function*), 933
riscv_dct4_init_q15 (*C++ function*), 934
riscv_dct4_init_q31 (*C++ function*), 936
riscv_dct4_q15 (*C++ function*), 934, 935
riscv_dct4_q31 (*C++ function*), 936
riscv_depthwise_conv_3x3_s8 (*C++ function*), 1057, 1075
riscv_depthwise_conv_fast_s16 (*C++ function*), 1057, 1076
riscv_depthwise_conv_fast_s16_get_buffer_size (*C++ function*), 1050, 1052
riscv_depthwise_conv_s16 (*C++ function*), 1057, 1077
riscv_depthwise_conv_s8 (*C++ function*), 1058, 1078
riscv_depthwise_conv_s8_opt (*C++ function*), 1058, 1079
riscv_depthwise_conv_s8_opt_get_buffer_size (*C++ function*), 1050, 1053
riscv_depthwise_conv_u8_basic_ver1 (*C++ function*), 1059, 1080
riscv_depthwise_conv_wrapper_s16 (*C++ function*), 1059, 1081
riscv_depthwise_conv_wrapper_s16_get_buffer_size (*C++ function*), 1050, 1053
riscv_depthwise_conv_wrapper_s16_get_buffer_size_dsp (*C++ function*), 1050, 1053
riscv_depthwise_conv_wrapper_s8 (*C++ function*), 1059, 1082
riscv_depthwise_conv_wrapper_s8_get_buffer_size (*C++ function*), 1050, 1053
riscv_depthwise_conv_wrapper_s8_get_buffer_size_dsp (*C++ function*), 1050, 1054
riscv_depthwise_separable_conv_HWC_q7 (*C++ function*), 1059, 1083
riscv_depthwise_separable_conv_HWC_q7_nonsquare (*C++ function*), 1059, 1084
riscv_dice_distance (*C++ function*), 702
riscv_divide_q15 (*C++ function*), 707
riscv_divide_q31 (*C++ function*), 707
riscv_dot_prod_f16 (*C++ function*), 652, 653
riscv_dot_prod_f32 (*C++ function*), 652, 653
riscv_dot_prod_f64 (*C++ function*), 652, 653
riscv_dot_prod_q15 (*C++ function*), 652, 653
riscv_dot_prod_q31 (*C++ function*), 652, 654
riscv_dot_prod_q7 (*C++ function*), 652, 654
riscv_dtw_distance_f32 (*C++ function*), 697, 698
riscv_dtw_init_window_q7 (*C++ function*), 697, 698
riscv_dtw_path_f32 (*C++ function*), 697, 698
riscv_elementwise_add_s16 (*C++ function*), 1043
riscv_elementwise_add_s8 (*C++ function*), 1043, 1044
riscv_elementwise_mul_s16 (*C++ function*), 1043, 1045
riscv_elementwise_mul_s16_s8 (*C++ function*), 1118, 1119
riscv_elementwise_mul_s8 (*C++ function*), 1043, 1045
riscv_entropy_f16 (*C++ function*), 840, 841
riscv_entropy_f32 (*C++ function*), 840, 841
riscv_entropy_f64 (*C++ function*), 840, 841
riscv_euclidean_distance_f16 (*C++ function*), 699
riscv_euclidean_distance_f32 (*C++ function*), 699
riscv_euclidean_distance_f64 (*C++ function*), 699, 700
riscv_f16_to_f64 (*C++ function*), 868
riscv_f16_to_float (*C++ function*), 868
riscv_f16_to_q15 (*C++ function*), 868, 869
riscv_f64_to_f16 (*C++ function*), 869
riscv_f64_to_float (*C++ function*), 869, 870
riscv_f64_to_q15 (*C++ function*), 869, 870
riscv_f64_to_q31 (*C++ function*), 869, 870
riscv_f64_to_q7 (*C++ function*), 869, 871
riscv_fill_f16 (*C++ function*), 871, 872
riscv_fill_f32 (*C++ function*), 871, 872
riscv_fill_f64 (*C++ function*), 871, 872
riscv_fill_q15 (*C++ function*), 871, 872
riscv_fill_q31 (*C++ function*), 871, 872
riscv_fill_q7 (*C++ function*), 871, 872
riscv_fir_decimate_f32 (*C++ function*), 750, 751
riscv_fir_decimate_fast_q15 (*C++ function*), 750, 751
riscv_fir_decimate_fast_q31 (*C++ function*), 750, 752
riscv_fir_decimate_init_f32 (*C++ function*), 750, 753
riscv_fir_decimate_init_q15 (*C++ function*), 750, 753
riscv_fir_decimate_init_q31 (*C++ function*), 750, 754
riscv_fir_decimate_q15 (*C++ function*), 750, 754
riscv_fir_decimate_q31 (*C++ function*), 750, 755
riscv_fir_f16 (*C++ function*), 755, 758
riscv_fir_f32 (*C++ function*), 755, 758
riscv_fir_f64 (*C++ function*), 755, 758

riscv_fir_fast_q15 (*C++ function*), 755, 758
riscv_fir_fast_q31 (*C++ function*), 755, 759
riscv_fir_init_f16 (*C++ function*), 755, 759
riscv_fir_init_f32 (*C++ function*), 755, 760
riscv_fir_init_f64 (*C++ function*), 755, 761
riscv_fir_init_q15 (*C++ function*), 755, 761
riscv_fir_init_q31 (*C++ function*), 755, 762
riscv_fir_init_q7 (*C++ function*), 756, 762
riscv_fir_interpolate_f32 (*C++ function*), 787, 788
riscv_fir_interpolate_init_f32 (*C++ function*), 787, 788
riscv_fir_interpolate_init_q15 (*C++ function*), 787, 789
riscv_fir_interpolate_init_q31 (*C++ function*), 787, 789
riscv_fir_interpolate_q15 (*C++ function*), 787, 790
riscv_fir_interpolate_q31 (*C++ function*), 787, 790
riscv_fir_lattice_f32 (*C++ function*), 764, 766
riscv_fir_lattice_init_f32 (*C++ function*), 764, 766
riscv_fir_lattice_init_q15 (*C++ function*), 764, 766
riscv_fir_lattice_init_q31 (*C++ function*), 764, 766
riscv_fir_lattice_q15 (*C++ function*), 764, 767
riscv_fir_lattice_q31 (*C++ function*), 765, 767
riscv_fir_q15 (*C++ function*), 756, 763
riscv_fir_q31 (*C++ function*), 756, 763
riscv_fir_q7 (*C++ function*), 756, 764
riscv_fir_sparse_f32 (*C++ function*), 767, 769
riscv_fir_sparse_init_f32 (*C++ function*), 767, 769
riscv_fir_sparse_init_q15 (*C++ function*), 767, 770
riscv_fir_sparse_init_q31 (*C++ function*), 767, 770
riscv_fir_sparse_init_q7 (*C++ function*), 767, 771
riscv_fir_sparse_q15 (*C++ function*), 768, 771
riscv_fir_sparse_q31 (*C++ function*), 768, 771
riscv_fir_sparse_q7 (*C++ function*), 768, 772
riscv_float_to_f16 (*C++ function*), 873
riscv_float_to_f64 (*C++ function*), 873
riscv_float_to_q15 (*C++ function*), 873
riscv_float_to_q31 (*C++ function*), 873, 874
riscv_float_to_q7 (*C++ function*), 873, 874
riscv_fully_connected_mat_q7_vec_q15 (*C++ function*), 1085, 1087
riscv_fully_connected_mat_q7_vec_q15_opt (*C++ function*), 1086, 1087
riscv_fully_connected_q15 (*C++ function*), 1086, 1088
riscv_fully_connected_q15_opt (*C++ function*), 1086, 1089
riscv_fully_connected_q7 (*C++ function*), 1086, 1090
riscv_fully_connected_q7_opt (*C++ function*), 1086, 1090
riscv_fully_connected_s16 (*C++ function*), 1086, 1091
riscv_fully_connected_s16_get_buffer_size (*C++ function*), 1085
riscv_fully_connected_s16_get_buffer_size_dsp (*C++ function*), 1085
riscv_fully_connected_s8 (*C++ function*), 1086, 1092
riscv_fully_connected_s8_get_buffer_size (*C++ function*), 1085
riscv_fully_connected_s8_get_buffer_size_dsp (*C++ function*), 1085
riscv_gaussian_naive_bayes_predict_f16 (*C++ function*), 669
riscv_gaussian_naive_bayes_predict_f32 (*C++ function*), 669, 670
riscv_hamming_distance (*C++ function*), 702
riscv_hamming_f32 (*C++ function*), 1006
riscv_hamming_f64 (*C++ function*), 1006
riscv_hanning_f32 (*C++ function*), 1007
riscv_hanning_f64 (*C++ function*), 1007
riscv_heap_sort_f32 (*C++ function*), 864
riscv_hft116d_f32 (*C++ function*), 991, 992
riscv_hft116d_f64 (*C++ function*), 991, 992
riscv_hft144d_f32 (*C++ function*), 993
riscv_hft144d_f64 (*C++ function*), 993
riscv_hft169d_f32 (*C++ function*), 994
riscv_hft169d_f64 (*C++ function*), 994, 995
riscv_hft196d_f32 (*C++ function*), 996
riscv_hft196d_f64 (*C++ function*), 996
riscv_hft223d_f32 (*C++ function*), 997
riscv_hft223d_f64 (*C++ function*), 997, 998
riscv_hft248d_f32 (*C++ function*), 999
riscv_hft248d_f64 (*C++ function*), 999
riscv_hft90d_f32 (*C++ function*), 1000
riscv_hft90d_f64 (*C++ function*), 1000, 1001
riscv_hft95_f32 (*C++ function*), 1002
riscv_hft95_f64 (*C++ function*), 1002
riscv_householder_f16 (*C++ function*), 797, 798
riscv_householder_f32 (*C++ function*), 797, 798
riscv_householder_f64 (*C++ function*), 797, 798
riscv_iir_lattice_f32 (*C++ function*), 773, 774
riscv_iir_lattice_init_f32 (*C++ function*), 773, 774
riscv_iir_lattice_init_q15 (*C++ function*), 773, 774
riscv_iir_lattice_init_q31 (*C++ function*), 773, 775

riscv_iir_lattice_q15 (*C++ function*), 773, 775
riscv_iir_lattice_q31 (*C++ function*), 773, 775
riscv_insertion_sort_f32 (*C++ function*), 864
riscv_jaccard_distance (*C++ function*), 702
riscv_jensenshannon_distance_f16 (*C++ function*), 700
riscv_jensenshannon_distance_f32 (*C++ function*), 700
riscv_kullback_leibler_f16 (*C++ function*), 841
riscv_kullback_leibler_f32 (*C++ function*), 841, 842
riscv_kullback_leibler_f64 (*C++ function*), 841, 842
riscv_kulsinski_distance (*C++ function*), 702, 703
riscv_levinson_durbin_f16 (*C++ function*), 776
riscv_levinson_durbin_f32 (*C++ function*), 776
riscv_levinson_durbin_q31 (*C++ function*), 776, 777
riscv_linear_interp_f16 (*C++ function*), 793, 794
riscv_linear_interp_f32 (*C++ function*), 793, 794
riscv_linear_interp_q15 (*C++ function*), 793, 794
riscv_linear_interp_q31 (*C++ function*), 793, 794
riscv_linear_interp_q7 (*C++ function*), 793, 795
riscv_lms_f32 (*C++ function*), 777, 779
riscv_lms_init_f32 (*C++ function*), 777, 779
riscv_lms_init_q15 (*C++ function*), 777, 780
riscv_lms_init_q31 (*C++ function*), 777, 780
riscv_lms_norm_f32 (*C++ function*), 782, 784
riscv_lms_norm_init_f32 (*C++ function*), 782, 784
riscv_lms_norm_init_q15 (*C++ function*), 782, 785
riscv_lms_norm_init_q31 (*C++ function*), 782, 785
riscv_lms_norm_q15 (*C++ function*), 782, 786
riscv_lms_norm_q31 (*C++ function*), 782, 786
riscv_lms_q15 (*C++ function*), 777, 781
riscv_lms_q31 (*C++ function*), 777, 781
riscv_logsumexp_dot_prod_f16 (*C++ function*), 842, 843
riscv_logsumexp_dot_prod_f32 (*C++ function*), 842, 843
riscv_logsumexp_f16 (*C++ function*), 842, 843
riscv_logsumexp_f32 (*C++ function*), 842, 843
riscv_lstm_unidirectional_s16_s8 (*C++ function*), 1093, 1094
riscv_mat_add_f16 (*C++ function*), 799
riscv_mat_add_f32 (*C++ function*), 799, 800
riscv_mat_add_q15 (*C++ function*), 799, 800
riscv_mat_add_q31 (*C++ function*), 799, 800
riscv_mat_cholesky_f16 (*C++ function*), 801
riscv_mat_cholesky_f32 (*C++ function*), 801
riscv_mat_cholesky_f64 (*C++ function*), 801, 802
riscv_mat_cmplx_mult_f16 (*C++ function*), 803, 804
riscv_mat_cmplx_mult_f32 (*C++ function*), 803, 804
riscv_mat_cmplx_mult_q15 (*C++ function*), 803, 804
riscv_mat_cmplx_mult_q31 (*C++ function*), 803, 805
riscv_mat_cmplx_trans_f16 (*C++ function*), 806
riscv_mat_cmplx_trans_f32 (*C++ function*), 806
riscv_mat_cmplx_trans_q15 (*C++ function*), 806, 807
riscv_mat_cmplx_trans_q31 (*C++ function*), 806, 807
riscv_mat_init_f16 (*C++ function*), 807, 808
riscv_mat_init_f32 (*C++ function*), 807, 808
riscv_mat_init_f64 (*C++ function*), 807, 808
riscv_mat_init_q15 (*C++ function*), 807, 808
riscv_mat_init_q31 (*C++ function*), 807, 808
riscv_mat_init_q7 (*C++ function*), 807, 809
riscv_mat_inverse_f16 (*C++ function*), 809, 810
riscv_mat_inverse_f32 (*C++ function*), 809, 810
riscv_mat_inverse_f64 (*C++ function*), 809, 811
riscv_mat_ldlt_f32 (*C++ function*), 801, 802
riscv_mat_ldlt_f64 (*C++ function*), 801, 803
riscv_mat_mult_f16 (*C++ function*), 813, 814
riscv_mat_mult_f32 (*C++ function*), 813, 814
riscv_mat_mult_f64 (*C++ function*), 813, 814
riscv_mat_mult_fast_q15 (*C++ function*), 813, 814
riscv_mat_mult_fast_q31 (*C++ function*), 813, 815
riscv_mat_mult_opt_q31 (*C++ function*), 813, 816
riscv_mat_mult_q15 (*C++ function*), 813, 816
riscv_mat_mult_q31 (*C++ function*), 813, 817
riscv_mat_mult_q7 (*C++ function*), 813, 817
riscv_mat_qr_f16 (*C++ function*), 818, 819
riscv_mat_qr_f32 (*C++ function*), 818, 820
riscv_mat_qr_f64 (*C++ function*), 818, 820
riscv_mat_scale_f16 (*C++ function*), 821
riscv_mat_scale_f32 (*C++ function*), 821, 822
riscv_mat_scale_q15 (*C++ function*), 821, 822
riscv_mat_scale_q31 (*C++ function*), 821, 822
riscv_mat_solve_lower_triangular_f16 (*C++ function*), 809, 811
riscv_mat_solve_lower_triangular_f32 (*C++ function*), 809, 811
riscv_mat_solve_lower_triangular_f64 (*C++ function*), 809, 811
riscv_mat_solve_upper_triangular_f16 (*C++ function*), 809, 812
riscv_mat_solve_upper_triangular_f32 (*C++ function*), 809, 812
riscv_mat_solve_upper_triangular_f64 (*C++ function*), 809, 812
riscv_mat_sub_f16 (*C++ function*), 823
riscv_mat_sub_f32 (*C++ function*), 823
riscv_mat_sub_f64 (*C++ function*), 823, 824
riscv_mat_sub_q15 (*C++ function*), 823, 824
riscv_mat_sub_q31 (*C++ function*), 823, 824
riscv_mat_trans_f16 (*C++ function*), 825, 826
riscv_mat_trans_f32 (*C++ function*), 825, 826
riscv_mat_trans_f64 (*C++ function*), 825, 826
riscv_mat_trans_q15 (*C++ function*), 825, 826

riscv_mat_trans_q31 (*C++ function*), 825, 826
riscv_mat_trans_q7 (*C++ function*), 825, 827
riscv_mat_vec_mult_f16 (*C++ function*), 827
riscv_mat_vec_mult_f32 (*C++ function*), 827, 828
riscv_mat_vec_mult_q15 (*C++ function*), 827, 828
riscv_mat_vec_mult_q31 (*C++ function*), 827, 828
riscv_mat_vec_mult_q7 (*C++ function*), 827, 828
riscv_max_f16 (*C++ function*), 844
riscv_max_f32 (*C++ function*), 844, 845
riscv_max_f64 (*C++ function*), 844, 845
riscv_max_no_idx_f16 (*C++ function*), 844, 845
riscv_max_no_idx_f32 (*C++ function*), 844, 845
riscv_max_no_idx_f64 (*C++ function*), 844, 845
riscv_max_no_idx_q15 (*C++ function*), 844, 846
riscv_max_no_idx_q31 (*C++ function*), 844, 846
riscv_max_no_idx_q7 (*C++ function*), 844, 846
riscv_max_pool_s16 (*C++ function*), 1096, 1098
riscv_max_pool_s8 (*C++ function*), 1096, 1098
riscv_max_q15 (*C++ function*), 844, 846
riscv_max_q31 (*C++ function*), 844, 846
riscv_max_q7 (*C++ function*), 844, 847
riscv_maxpool_q7_HWC (*C++ function*), 1096, 1099
riscv_mean_f16 (*C++ function*), 847
riscv_mean_f32 (*C++ function*), 847
riscv_mean_f64 (*C++ function*), 847, 848
riscv_mean_q15 (*C++ function*), 847, 848
riscv_mean_q31 (*C++ function*), 847, 848
riscv_mean_q7 (*C++ function*), 847, 849
riscv_merge_sort_f32 (*C++ function*), 863, 864
riscv_merge_sort_init_f32 (*C++ function*), 863, 865
riscv_mfcc_f16 (*C++ function*), 939, 940
riscv_mfcc_f32 (*C++ function*), 938, 939
riscv_mfcc_init_f16 (*C++ function*), 939, 940
riscv_mfcc_init_f32 (*C++ function*), 958, 959
riscv_mfcc_init_q15 (*C++ function*), 945, 946
riscv_mfcc_init_q31 (*C++ function*), 952, 953
riscv_mfcc_q15 (*C++ function*), 946, 951
riscv_mfcc_q31 (*C++ function*), 952, 958
riscv_min_f16 (*C++ function*), 849, 850
riscv_min_f32 (*C++ function*), 849, 850
riscv_min_f64 (*C++ function*), 849, 850
riscv_min_no_idx_f16 (*C++ function*), 849, 850
riscv_min_no_idx_f32 (*C++ function*), 849, 850
riscv_min_no_idx_f64 (*C++ function*), 849, 851
riscv_min_no_idx_q15 (*C++ function*), 849, 851
riscv_min_no_idx_q31 (*C++ function*), 849, 851
riscv_min_no_idx_q7 (*C++ function*), 849, 851
riscv_min_q15 (*C++ function*), 849, 851
riscv_min_q31 (*C++ function*), 849, 852
riscv_min_q7 (*C++ function*), 849, 852
riscv_minkowski_distance_f16 (*C++ function*), 701
riscv_minkowski_distance_f32 (*C++ function*), 701
riscv_mse_f16 (*C++ function*), 852, 853
riscv_mse_f32 (*C++ function*), 852, 853
riscv_mse_f64 (*C++ function*), 852, 853
riscv_mse_q15 (*C++ function*), 852, 853
riscv_mse_q31 (*C++ function*), 852, 853
riscv_mse_q7 (*C++ function*), 852, 854
riscv_mult_f16 (*C++ function*), 654, 655
riscv_mult_f32 (*C++ function*), 654, 655
riscv_mult_f64 (*C++ function*), 654, 655
riscv_mult_q15 (*C++ function*), 654, 655
riscv_mult_q31 (*C++ function*), 654, 656
riscv_mult_q7 (*C++ function*), 655, 656
riscv_negate_f16 (*C++ function*), 656, 657
riscv_negate_f32 (*C++ function*), 656, 657
riscv_negate_f64 (*C++ function*), 656, 657
riscv_negate_q15 (*C++ function*), 656, 657
riscv_negate_q31 (*C++ function*), 656, 658
riscv_negate_q7 (*C++ function*), 657, 658
riscv_nn_accumulate_q7_to_q15 (*C++ function*), 1119
riscv_nn_activation_s16 (*C++ function*), 1041
riscv_nn_activations_direct_q15 (*C++ function*), 1041
riscv_nn_activations_direct_q7 (*C++ function*), 1041, 1042
riscv_nn_add_q7 (*C++ function*), 1119, 1120
riscv_nn_copy_q15 (*C++ function*), 1121
riscv_nn_copy_q7 (*C++ function*), 1121
riscv_nn_depthwise_conv_nt_t_padded_s8 (*C++ function*), 1106, 1107
riscv_nn_depthwise_conv_nt_t_s16 (*C++ function*), 1106, 1108
riscv_nn_depthwise_conv_nt_t_s8 (*C++ function*), 1106, 1109
riscv_nn_fill_q15 (*C++ function*), 1121, 1122
riscv_nn_fill_q7 (*C++ function*), 1121, 1122
riscv_nn_lstm_calculate_gate_s8_s16 (*C++ function*), 1113
riscv_nn_lstm_step_s8_s16 (*C++ function*), 1113, 1114
riscv_nn_lstm_update_cell_state_s16 (*C++ function*), 1113, 1114
riscv_nn_lstm_update_output_s8_s16 (*C++ function*), 1113, 1114
riscv_nn_mat_mul_core_1x_s8 (*C++ function*), 1106, 1110
riscv_nn_mat_mul_core_4x_s8 (*C++ function*), 1106, 1110
riscv_nn_mat_mult_kernel_s16 (*C++ function*), 1107, 1111
riscv_nn_mat_mult_nt_t_s8 (*C++ function*), 1107, 1111
riscv_nn_mult_q15 (*C++ function*), 1119, 1120
riscv_nn_mult_q7 (*C++ function*), 1119, 1120
riscv_nn_softmax_common_s8 (*C++ function*), 1118

riscv_nn_vec_mat_mul_result_acc_s8 (*C++ function*), 1113, 1115
riscv_nn_vec_mat_mult_t_s16 (*C++ function*), 1115, 1116
riscv_nn_vec_mat_mult_t_s8 (*C++ function*), 1115, 1116
riscv_nn_vec_mat_mult_t_svdf_s8 (*C++ function*), 1115, 1117
riscv_not_u16 (*C++ function*), 658, 659
riscv_not_u32 (*C++ function*), 658, 659
riscv_not_u8 (*C++ function*), 658, 659
riscv_nuttall3_f32 (*C++ function*), 1008
riscv_nuttall3_f64 (*C++ function*), 1008
riscv_nuttall3a_f32 (*C++ function*), 1009
riscv_nuttall3a_f64 (*C++ function*), 1009
riscv_nuttall3b_f32 (*C++ function*), 1010
riscv_nuttall3b_f64 (*C++ function*), 1010
riscv_nuttall4_f32 (*C++ function*), 1011
riscv_nuttall4_f64 (*C++ function*), 1011, 1012
riscv_nuttall4a_f32 (*C++ function*), 1012
riscv_nuttall4a_f64 (*C++ function*), 1012, 1013
riscv_nuttall4b_f32 (*C++ function*), 1013
riscv_nuttall4b_f64 (*C++ function*), 1013, 1014
riscv_nuttall4c_f32 (*C++ function*), 1014
riscv_nuttall4c_f64 (*C++ function*), 1014, 1015
riscv_offset_f16 (*C++ function*), 659, 660
riscv_offset_f32 (*C++ function*), 659, 660
riscv_offset_f64 (*C++ function*), 659, 660
riscv_offset_q15 (*C++ function*), 659, 660
riscv_offset_q31 (*C++ function*), 659, 660
riscv_offset_q7 (*C++ function*), 659, 661
riscv_or_u16 (*C++ function*), 661, 662
riscv_or_u32 (*C++ function*), 661, 662
riscv_or_u8 (*C++ function*), 661, 662
riscv_pid_init_f32 (*C++ function*), 682, 684
riscv_pid_init_q15 (*C++ function*), 682, 685
riscv_pid_init_q31 (*C++ function*), 682, 685
riscv_pid_instance_f32 (*C++ struct*), 682, 686
riscv_pid_instance_q15 (*C++ struct*), 682, 686
riscv_pid_instance_q31 (*C++ struct*), 682, 686
riscv_pid_reset_f32 (*C++ function*), 682, 685
riscv_pid_reset_q15 (*C++ function*), 682, 686
riscv_pid_reset_q31 (*C++ function*), 682, 686
riscv_power_f16 (*C++ function*), 854, 855
riscv_power_f32 (*C++ function*), 854, 855
riscv_power_f64 (*C++ function*), 854, 855
riscv_power_q15 (*C++ function*), 854, 855
riscv_power_q31 (*C++ function*), 854, 855
riscv_power_q7 (*C++ function*), 854, 856
riscv_q15_to_f16 (*C++ function*), 875
riscv_q15_to_f64 (*C++ function*), 875
riscv_q15_to_float (*C++ function*), 875, 876
riscv_q15_to_q31 (*C++ function*), 875, 876
riscv_q15_to_q7 (*C++ function*), 875, 876
riscv_q31_to_f64 (*C++ function*), 877
riscv_q31_to_float (*C++ function*), 877
riscv_q31_to_q15 (*C++ function*), 877
riscv_q31_to_q7 (*C++ function*), 877, 878
riscv_q7_to_f64 (*C++ function*), 878
riscv_q7_to_float (*C++ function*), 878
riscv_q7_to_q15 (*C++ function*), 878, 879
riscv_q7_to_q15_no_shift (*C++ function*), 1122
riscv_q7_to_q15_reordered_no_shift (*C++ function*), 1122, 1123
riscv_q7_to_q15_reordered_with_offset (*C++ function*), 1122, 1123
riscv_q7_to_q15_with_offset (*C++ function*), 1124
riscv_q7_to_q31 (*C++ function*), 878, 879
riscv_q7_to_q7_no_shift (*C++ function*), 1122, 1123
riscv_q7_to_q7_reordered_no_shift (*C++ function*), 1122, 1123
riscv_quaternion2rotation_f32 (*C++ function*), 829
riscv_quaternion_conjugate_f32 (*C++ function*), 830
riscv_quaternion_inverse_f32 (*C++ function*), 831
riscv_quaternion_norm_f32 (*C++ function*), 831
riscv_quaternion_normalize_f32 (*C++ function*), 832
riscv_quaternion_product_f32 (*C++ function*), 832
riscv_quaternion_product_single_f32 (*C++ function*), 833
riscv_quick_sort_f32 (*C++ function*), 865
riscv_relu6_s8 (*C++ function*), 1041, 1042
riscv_relu_q15 (*C++ function*), 1041, 1042
riscv_relu_q7 (*C++ function*), 1041, 1042
riscv_reshape_s8 (*C++ function*), 1100
riscv_rfft_f32 (*C++ function*), 987
riscv_rfft_fast_f16 (*C++ function*), 964, 965
riscv_rfft_fast_f32 (*C++ function*), 985
riscv_rfft_fast_f64 (*C++ function*), 967
riscv_rfft_fast_init_1024_f16 (*C++ function*), 964, 966
riscv_rfft_fast_init_1024_f32 (*C++ function*), 985, 986
riscv_rfft_fast_init_1024_f64 (*C++ function*), 967, 968
riscv_rfft_fast_init_128_f16 (*C++ function*), 964, 965
riscv_rfft_fast_init_128_f32 (*C++ function*), 985, 986
riscv_rfft_fast_init_128_f64 (*C++ function*), 967, 968
riscv_rfft_fast_init_2048_f16 (*C++ function*), 964, 966
riscv_rfft_fast_init_2048_f32 (*C++ function*), 985, 986

riscv_rfft_fast_init_2048_f64 (*C++ function*), 967, 968
riscv_rfft_fast_init_256_f16 (*C++ function*), 964, 965
riscv_rfft_fast_init_256_f32 (*C++ function*), 985, 986
riscv_rfft_fast_init_256_f64 (*C++ function*), 967, 968
riscv_rfft_fast_init_32_f16 (*C++ function*), 964, 965
riscv_rfft_fast_init_32_f32 (*C++ function*), 985
riscv_rfft_fast_init_32_f64 (*C++ function*), 967
riscv_rfft_fast_init_4096_f16 (*C++ function*), 964, 966
riscv_rfft_fast_init_4096_f32 (*C++ function*), 985, 986
riscv_rfft_fast_init_4096_f64 (*C++ function*), 967, 968
riscv_rfft_fast_init_512_f16 (*C++ function*), 964, 965
riscv_rfft_fast_init_512_f32 (*C++ function*), 985, 986
riscv_rfft_fast_init_512_f64 (*C++ function*), 967, 968
riscv_rfft_fast_init_64_f16 (*C++ function*), 964, 965
riscv_rfft_fast_init_64_f32 (*C++ function*), 985
riscv_rfft_fast_init_64_f64 (*C++ function*), 967
riscv_rfft_fast_init_f16 (*C++ function*), 964, 966
riscv_rfft_fast_init_f32 (*C++ function*), 985, 987
riscv_rfft_fast_init_f64 (*C++ function*), 967, 969
riscv_rfft_init_f32 (*C++ function*), 987, 988
riscv_rfft_init_q15 (*C++ function*), 970, 975
riscv_rfft_init_q31 (*C++ function*), 976, 981
riscv_rfft_q15 (*C++ function*), 988, 990
riscv_rfft_q31 (*C++ function*), 976, 982
riscv_rms_f16 (*C++ function*), 856, 857
riscv_rms_f32 (*C++ function*), 856, 857
riscv_rms_q15 (*C++ function*), 856, 857
riscv_rms_q31 (*C++ function*), 856, 857
riscv_rogerstanimoto_distance (*C++ function*), 702, 703
riscv_rotation2quaternion_f32 (*C++ function*), 830
riscv_russellrao_distance (*C++ function*), 702, 703
riscv_scale_f16 (*C++ function*), 662, 663
riscv_scale_f32 (*C++ function*), 662, 663
riscv_scale_f64 (*C++ function*), 662, 663
riscv_scale_q15 (*C++ function*), 662, 663
riscv_scale_q31 (*C++ function*), 662, 664
riscv_scale_q7 (*C++ function*), 662, 664
riscv_selection_sort_f32 (*C++ function*), 865
riscv_shift_q15 (*C++ function*), 665
riscv_shift_q31 (*C++ function*), 665
riscv_shift_q7 (*C++ function*), 665, 666
riscv_sin_cos_f32 (*C++ function*), 681, 682
riscv_sin_cos_q31 (*C++ function*), 681, 682
riscv_sin_f32 (*C++ function*), 708
riscv_sin_q15 (*C++ function*), 708
riscv_sin_q31 (*C++ function*), 708
riscv_softmax_q15 (*C++ function*), 1100, 1101
riscv_softmax_q7 (*C++ function*), 1100, 1101
riscv_softmax_s16 (*C++ function*), 1100, 1101
riscv_softmax_s8 (*C++ function*), 1100, 1102
riscv_softmax_s8_s16 (*C++ function*), 1100, 1102
riscv_softmax_u8 (*C++ function*), 1100, 1103
riscv_softmax_with_batch_q7 (*C++ function*), 1100, 1103
riscv_sokalmichener_distance (*C++ function*), 702, 703
riscv_sokalsneath_distance (*C++ function*), 702, 703
riscv_sort_f32 (*C++ function*), 863, 866
riscv_sort_init_f32 (*C++ function*), 863, 866
riscv_spline_f32 (*C++ function*), 795, 796
riscv_spline_init_f32 (*C++ function*), 795, 796
riscv_sqrt_q15 (*C++ function*), 710, 711
riscv_sqrt_q31 (*C++ function*), 710, 711
riscv_std_f16 (*C++ function*), 858
riscv_std_f32 (*C++ function*), 858
riscv_std_f64 (*C++ function*), 858
riscv_std_q15 (*C++ function*), 858, 859
riscv_std_q31 (*C++ function*), 858, 859
riscv_sub_f16 (*C++ function*), 666
riscv_sub_f32 (*C++ function*), 666
riscv_sub_f64 (*C++ function*), 666, 667
riscv_sub_q15 (*C++ function*), 666, 667
riscv_sub_q31 (*C++ function*), 666, 667
riscv_sub_q7 (*C++ function*), 666, 668
riscv_svdf_s8 (*C++ function*), 1103, 1104
riscv_svdf_state_s16_s8 (*C++ function*), 1104, 1105
riscv_svm_linear_init_f16 (*C++ function*), 880, 881
riscv_svm_linear_init_f32 (*C++ function*), 880, 881
riscv_svm_linear_predict_f16 (*C++ function*), 880, 881
riscv_svm_linear_predict_f32 (*C++ function*), 880, 882
riscv_svm_polynomial_init_f16 (*C++ function*), 882
riscv_svm_polynomial_init_f32 (*C++ function*), 882, 883
riscv_svm_polynomial_predict_f16 (*C++ function*), 882, 883

riscv_svm_polynomial_predict_f32 (*C++ function*), 882, 883
riscv_svm_rbf_init_f16 (*C++ function*), 884
riscv_svm_rbf_init_f32 (*C++ function*), 884
riscv_svm_rbf_predict_f16 (*C++ function*), 884, 885
riscv_svm_rbf_predict_f32 (*C++ function*), 884, 885
riscv_svm_sigmoid_init_f16 (*C++ function*), 885, 886
riscv_svm_sigmoid_init_f32 (*C++ function*), 885, 886
riscv_svm_sigmoid_predict_f16 (*C++ function*), 885, 887
riscv_svm_sigmoid_predict_f32 (*C++ function*), 885, 887
riscv_var_f16 (*C++ function*), 860
riscv_var_f32 (*C++ function*), 860
riscv_var_f64 (*C++ function*), 860
riscv_var_q15 (*C++ function*), 860
riscv_var_q31 (*C++ function*), 860, 861
riscv_vexp_f16 (*C++ function*), 709
riscv_vexp_f32 (*C++ function*), 709
riscv_vlog_f16 (*C++ function*), 709, 710
riscv_vlog_f32 (*C++ function*), 709, 710
riscv_vlog_q15 (*C++ function*), 709, 710
riscv_vlog_q31 (*C++ function*), 709, 710
riscv_weighted_sum_f16 (*C++ function*), 879, 880
riscv_weighted_sum_f32 (*C++ function*), 879, 880
riscv_welch_f32 (*C++ function*), 1015, 1016
riscv_welch_f64 (*C++ function*), 1015, 1016
riscv_xor_u16 (*C++ function*), 668
riscv_xor_u32 (*C++ function*), 668
riscv_xor_u8 (*C++ function*), 668, 669
riscv_yule_distance (*C++ function*), 702, 704
riscvBitRevTable (*C++ member*), 887, 890
rv_csr_t (*C++ type*), 126
rv_fpu_t (*C++ type*), 593

S

SATP32_ASID (*C macro*), 121
SATP32_MODE (*C macro*), 121
SATP32_PPN (*C macro*), 121
SATP64_ASID (*C macro*), 121
SATP64_MODE (*C macro*), 121
SATP64_PPN (*C macro*), 121
SATP_MODE_OFF (*C macro*), 121
SATP_MODE_SV32 (*C macro*), 121
SATP_MODE_SV39 (*C macro*), 121
SATP_MODE_SV48 (*C macro*), 121
SATP_MODE_SV57 (*C macro*), 121
SATP_MODE_SV64 (*C macro*), 121
SAVE_FPU_CONTEXT (*C macro*), 592
SAVE_IRQ_CSR_CONTEXT (*C macro*), 564, 567
SAVE_IRQ_CSR_CONTEXT_S (*C macro*), 565, 567
SCAUSE_CAUSE (*C macro*), 115
SCAUSE_INTR (*C macro*), 115
SENVCFG_CBCFE (*C macro*), 115
SENVCFG_CBIE_EN (*C macro*), 115
SENVCFG_CBIE_FLUSH (*C macro*), 115
SENVCFG_CBIE_INVAL (*C macro*), 115
SENVCFG_CBZE (*C macro*), 115
SIP_SSIP (*C macro*), 120
SIP_STIP (*C macro*), 120
SLEEPVALUE_SLEEPVALUE (*C macro*), 115
SMP_CTRLREG (*C macro*), 628
SPMP_A (*C macro*), 123
SPMP_A_NA4 (*C macro*), 123
SPMP_A_NAPOT (*C macro*), 123
SPMP_A_TOR (*C macro*), 123
SPMP_CONFIG (*C++ struct*), 596, 599
SPMP_COUNT (*C macro*), 123
SPMP_L (*C macro*), 123
SPMP_R (*C macro*), 123
SPMP_SHIFT (*C macro*), 123
SPMP_U (*C macro*), 123
SPMP_W (*C macro*), 123
SPMP_X (*C macro*), 123
SSTATUS32_SD (*C macro*), 111
SSTATUS64_SD (*C macro*), 111
SSTATUS_FS (*C macro*), 111
SSTATUS_MXR (*C macro*), 111
SSTATUS_SIE (*C macro*), 111
SSTATUS_SPIE (*C macro*), 111
SSTATUS_SPP (*C macro*), 111
SSTATUS_SUM (*C macro*), 111
SSTATUS_UBE (*C macro*), 111
SSTATUS_UIE (*C macro*), 111
SSTATUS_UPIE (*C macro*), 111
SSTATUS_UXL (*C macro*), 111
SSTATUS_VS (*C macro*), 111
SSTATUS_XS (*C macro*), 111
STORE_PAGE_FAULT (*C macro*), 125
system_default_exception_handler (*C++ function*), 632
system_default_exception_handler_s (*C++ function*), 634
SystemBannerPrint (*C++ function*), 629
SystemCoreClock (*C++ member*), 631
SystemCoreClockUpdate (*C++ function*), 629
SystemExceptionHandlers (*C++ member*), 635
SystemExceptionHandlers_S (*C++ member*), 635
SystemInit (*C++ function*), 629
SystemIRegionInfo (*C++ member*), 631
SysTimer (*C macro*), 146
SysTimer_BASE (*C macro*), 146
SysTimer_CLINT_MSIP_BASE (*C macro*), 146
SysTimer_CLINT_MSIP_OFS (*C macro*), 146

SysTimer_CLINT_MTIME_BASE (*C macro*), 146
SysTimer_CLINT_MTIME_OFS (*C macro*), 146
SysTimer_CLINT_MTIMECMP_BASE (*C macro*), 146
SysTimer_CLINT_MTIMECMP_OFS (*C macro*), 146
SysTimer_GetHartID (*C macro*), 543
SysTimer_MSFRST_KEY (*C macro*), 145
SysTimer_MSFTRST_Msk (*C macro*), 145
SysTimer_MSIP_MSIP_Msk (*C macro*), 145
SysTimer_MSIP_MSIP_Pos (*C macro*), 145
SysTimer_MSIP_Msk (*C macro*), 145
SysTimer_MTIMECTL_CLKSRC_Msk (*C macro*), 145
SysTimer_MTIMECTL_CLKSRC_Pos (*C macro*), 145
SysTimer_MTIMECTL_CMPCLREN_Msk (*C macro*), 145
SysTimer_MTIMECTL_CMPCLREN_Pos (*C macro*), 145
SysTimer_MTIMECTL_Msk (*C macro*), 145
SysTimer_MTIMECTL_TIMESTOP_Msk (*C macro*), 145
SysTimer_MTIMECTL_TIMESTOP_Pos (*C macro*), 145
SysTimer_MTIMER_Msk (*C macro*), 145
SysTimer_MTIMERCMP_Msk (*C macro*), 145
SysTimer_Type (*C++ struct*), 146

T

T_UINT16_READ (*C++ member*), 80
T_UINT16_WRITE (*C++ member*), 80
T_UINT32_READ (*C++ member*), 80
T_UINT32_WRITE (*C++ member*), 80
Trap_Init (*C++ function*), 630
twiddleCoef_1024 (*C++ member*), 888, 893
twiddleCoef_1024_q15 (*C++ member*), 889, 896
twiddleCoef_1024_q31 (*C++ member*), 888, 894
twiddleCoef_128 (*C++ member*), 888, 892
twiddleCoef_128_q15 (*C++ member*), 889, 895
twiddleCoef_128_q31 (*C++ member*), 888, 894
twiddleCoef_16 (*C++ member*), 888, 892
twiddleCoef_16_q15 (*C++ member*), 889, 895
twiddleCoef_16_q31 (*C++ member*), 888, 893
twiddleCoef_2048 (*C++ member*), 888, 893
twiddleCoef_2048_q15 (*C++ member*), 889, 896
twiddleCoef_2048_q31 (*C++ member*), 889, 894
twiddleCoef_256 (*C++ member*), 888, 892
twiddleCoef_256_q15 (*C++ member*), 889, 896
twiddleCoef_256_q31 (*C++ member*), 888, 894
twiddleCoef_32 (*C++ member*), 888, 892
twiddleCoef_32_q15 (*C++ member*), 889, 895
twiddleCoef_32_q31 (*C++ member*), 888, 893
twiddleCoef_4096 (*C++ member*), 888, 893
twiddleCoef_4096_q15 (*C++ member*), 889, 896
twiddleCoef_4096_q31 (*C++ member*), 889, 895
twiddleCoef_512 (*C++ member*), 888, 892
twiddleCoef_512_q15 (*C++ member*), 889, 896
twiddleCoef_512_q31 (*C++ member*), 888, 894
twiddleCoef_64 (*C++ member*), 888, 892
twiddleCoef_64_q15 (*C++ member*), 889, 895
twiddleCoef_64_q31 (*C++ member*), 888, 894
twiddleCoefF16_1024 (*C++ member*), 889, 898
twiddleCoefF16_128 (*C++ member*), 889, 897
twiddleCoefF16_16 (*C++ member*), 889, 897
twiddleCoefF16_2048 (*C++ member*), 889, 898
twiddleCoefF16_256 (*C++ member*), 889, 897
twiddleCoefF16_32 (*C++ member*), 889, 897
twiddleCoefF16_4096 (*C++ member*), 889, 898
twiddleCoefF16_512 (*C++ member*), 889, 898
twiddleCoefF16_64 (*C++ member*), 889, 897
twiddleCoefF16_rfft_1024 (*C++ member*), 890, 898
twiddleCoefF16_rfft_128 (*C++ member*), 890, 898
twiddleCoefF16_rfft_2048 (*C++ member*), 890, 899
twiddleCoefF16_rfft_256 (*C++ member*), 890, 898
twiddleCoefF16_rfft_32 (*C++ member*), 889, 898
twiddleCoefF16_rfft_4096 (*C++ member*), 890, 899
twiddleCoefF16_rfft_512 (*C++ member*), 890, 898
twiddleCoefF16_rfft_64 (*C++ member*), 890, 898
twiddleCoefF64_1024 (*C++ member*), 888, 891
twiddleCoefF64_128 (*C++ member*), 887, 891
twiddleCoefF64_16 (*C++ member*), 887, 890
twiddleCoefF64_2048 (*C++ member*), 888, 891
twiddleCoefF64_256 (*C++ member*), 888, 891
twiddleCoefF64_32 (*C++ member*), 887, 890
twiddleCoefF64_4096 (*C++ member*), 888, 891
twiddleCoefF64_512 (*C++ member*), 888, 891
twiddleCoefF64_64 (*C++ member*), 887, 891
TXEVT_TXEVT (*C macro*), 115

U

UCODE_OV (*C macro*), 115
USER_ECALL (*C macro*), 125
USTATUS_UIE (*C macro*), 111
USTATUS_UPIE (*C macro*), 111

V

VM_MBARE (*C macro*), 120
VM_MBB (*C macro*), 120
VM_MBBID (*C macro*), 120
VM_SV32 (*C macro*), 120
VM_SV39 (*C macro*), 120
VM_SV48 (*C macro*), 120

W

Weights_128 (*C++ member*), 931, 932
Weights_2048 (*C++ member*), 931, 932
Weights_512 (*C++ member*), 931, 932
Weights_8192 (*C++ member*), 931, 932
WeightsQ31_128 (*C++ member*), 931, 932
WeightsQ31_2048 (*C++ member*), 931, 933
WeightsQ31_512 (*C++ member*), 931, 933
WeightsQ31_8192 (*C++ member*), 931, 933
WFE_WFE (*C macro*), 115
WFI_SleepMode (*C++ enum*), 147, 150

WFI_SleepMode::WFI_DEEP_SLEEP (*C++ enumerator*), 147, 150
WFI_SleepMode::WFI_SHALLOW_SLEEP (*C++ enumerator*), 147, 150

X

XIP, **1137**