

🌐 IT 네트워크 시스템 *IT Network Systems Administration*

✍ Written by **Donghyun Choi (KGU)**

❖ - Worldskills Korea - Assessment Task (IT Network Systems) - [Written by NullBins]

- By default, the commands are executed as a root user.

[Project-1] <🐧 Linux Environments>

8. SSSD 구성 (Samba AD Client Joining)

- 🔒 DONG-CLI 에서 SSSD 구성 시 패키지 도구는 SSSD를 사용함.

< Configuration >

- [DONG-CLI]

```
apt install krb5-user krb5-config samba sssd -y
```

```
scp DONG-SRV1:/etc/krb5.conf
```

```
vim /etc/samba/smb.conf
```

```
[global]
workgroup = DONGHYUN
realm = DONGHYUN.NET

client signing = yes
client use spnego = yes
kerberos method = secrets and keytab
security = ads
```

```
net ads join -UAdministrator
systemctl restart smbd nmbd
cp /usr/share/doc/sssd-common/examples/sssd-example.conf /etc/sssd/sssd.conf
```

```
vim /etc/sssd/sssd.conf
```

```
[sssd]
config_file_version = 2
services = nss, pam
domains = AD

[domain/AD]
id_provider = ad
auth_provider = ad

override_homedir = /home%u
default_shell = /bin/bash
ldap_id_mapping = false
enumerate = true

ad_hostname = DONG-CLI.donghyun.net
ad_server = DONG-SRV1.donghyun.net
ad_domain = donghyun.net
```

```
chown root:root /etc/sssd/sssd.conf
chmod 700 /etc/sssd/sssd.conf
echo -e "session optional pam_mkhomedir.so" >> /etc/pam.d/common-session
systemctl restart sssd
```